

Configuring Administrative Information for Retailers (SRC CLI)

Use the following configuration statements to configure administrative information about the retailer:

```
subscribers retailer name info {  
    contact contact ;  
    e-mail e-mail ;  
    url url ;  
}
```

To add administrative information about retailers:

1. From configuration mode, enter the retailer subscriber info configuration. In this procedure, retailer-one is the name of the retailer.

```
user@host# edit subscribers retailer retailer-one info
```

2. (Optional) Configure a contact name for the retailer.

```
[edit subscribers retailer retailer-one info]  
user@host# set contact contact
```

3. (Optional) Configure an e-mail address for the retailer.

```
[edit subscribers retailer retailer-one info]  
user@host# set e-mail e-mail
```

4. (Optional) Configure a URL for the retailer.

```
[edit subscribers retailer retailer-one info]  
user@host# set url url
```

5. (Optional) Verify your configuration.

```
[edit subscribers retailer retailer-one info]  
user@host# show  
contact "Mary Smith";  
e-mail msmith@abc.com;  
url www.abc.com;
```

- Related Topics**
- Configuring Administrative Information for Retailers (C-Web Interface)
 - Configuring Administrative Information for Enterprise Subscribers (SRC CLI)
 - Adding Retailers (SRC CLI)
 - Overview of Subscribers

