

Configuration Tasks for Integrating Third-Party Network Devices

To integrate third-party devices into your SRC network, complete the following tasks:

- Write a script and add a script service that references the script.

See Setting Up Script Services .

- Add objects for the devices.

See Adding Objects for Network Devices .

- Configure an SAE community.

See Setting Up SAE Communities .

- (Optional) Configure SAE properties for the Event Notification API if you are using the event notification method to log in subscribers.

See Configuring SAE Properties for the Event Notification API with SRC CLI.

- Configure the session store.

See Storing Subscriber and Service Session Data.

- If you are using the event notification method to log in subscribers, integrate the SAE with an IP address manager. There are two ways to do so:

- Use the event notification API to create an application that notifies the SAE when events occur between the DHCP server and the network device.

See the event notification API documentation in the SAE CORBA remote API documentation on the Juniper Networks Web site at <http://www.juniper.net/techpubs/software/management/src/api-index.html>

- Use Monitoring Agent, a sample application that was created with the event notification API and that monitors DHCP or RADIUS messages for DHCP or RADIUS servers.

See the *SRC-PE Sample Applications Guide*.

Related Topics

- Configuration Tasks for Integrating Third-Party Network Devices (C-Web Interface)
- Overview of Integrating Network Devices into the SRC Network
- Logging In Subscribers and Creating Sessions

