

Configuring Services That Are Available for PCMM Clients (SRC CLI)

Application managers require that usernames be specified from the Web Services Security: Username Token Profile 1.0, OASIS Standard.

Use the following configuration statements to configure available services for PCMM clients:

```
shared dsa group name configuration client name
```

```
shared dsa group name configuration client name permissions {  
  pcmm-service [pcmm-service...];  
}
```

To configure PCMM clients and the services that are available to the clients:

1. From configuration mode, access the configuration statement that configures the PCMM client. You must use the same name for the PCMM client that is configured on the Web application server.

If you disable the access control mechanism and you configure the Web application server to authenticate clients with any username and password, Dynamic Service Activator sends the text string “anonymous client” as the first argument to the SAE’s Java scripts interface module.

[edit]

```
user@host# edit shared dsa group name configuration client name permissions
```

2. Specify the services available to the PCMM client.

[edit shared dsa group *name* configuration client *name* permissions]

```
user@host# set pcmm-service [pcmm-service...]
```

- Related Topics**
- Overview of Web Service Interface for PCMM
 - Sample Data for Dynamic Service Activator
 - Configuring PCMM Policies and Parameter Substitutions (SRC CLI)
 - Configuring User Accounts for Web Applications (SRC CLI)
 - SRC PCMM Web Service Interface Methods

