

Configuring External Subscriber Monitor

Configure initial properties, including directory connection and directory eventing properties.

Tasks to configure External Subscriber Monitor are:

1. Configuring Basic Local Properties for External Subscriber Monitor on page 1
2. Configuring Initial Properties for External Subscriber Monitor on page 1
3. Configuring Directory Connection Properties for External Subscriber Monitor on page 1
4. Configuring Eventing Properties for External Subscriber Monitor on page 2
5. Configuring Logging Destinations for External Subscriber Monitor on page 2

Configuring Basic Local Properties for External Subscriber Monitor

To configure basic local properties:

1. Click **Configure > Slot**, then a specified slot (for example, slot0), and then **External Subscriber Monitor**.

The External Subscriber Monitor pane appears.

2. From the Create new list, select **Logger**. Type a name for the new logger in the dialog box, and click **OK**.
3. Enter the maximum java heap size in the **Java Heap Size** box, as described in the Help text.
4. Click **Apply**.

Configuring Initial Properties for External Subscriber Monitor

To configure initial properties:

1. Click **Configure > Slot**, then a specified slot (for example, slot0).
2. Expand **External Subscriber Monitor**.
3. Click **Initial**.

The Initial pane appears.

Configuring Directory Connection Properties for External Subscriber Monitor

To configure directory connection properties:

1. Click **Configure > Slot**, then a specified slot (for example, slot0).
2. Expand **External Subscriber Monitor**.
3. Expand **Initial**and, then click **Directory Connection**.

The Directory Connection pane appears.

4. Enter the information as described in the Help text box.
5. Click **Apply**.

Configuring Eventing Properties for External Subscriber Monitor

To configure eventing properties:

1. Click **Configure > Slot**, then a specified slot (for example, slot0).
2. Expand **External Subscriber Monitor**.
3. Expand **Initial**, and then click **Directory Eventing**.

The Directory Eventing pane appears.

4. Enter the information as described in the Help text box.
5. Click **Apply**.

Configuring Logging Destinations for External Subscriber Monitor

You can configure the logging destination to store messages in a file or a system logging facility (Syslog). You can create or modify loggers.

To configure logging destinations to store log messages:

1. Click **Configure > Slot**, then a specified slot (for example, slot0).
2. Expand **External Subscriber Monitor**.
3. From the Create new list, select **Logger**.
4. In the dialog box, type a name for the new logger, and click **OK**.

The name of the logger appears in the side pane and the Logger pane.

5. Expand the logger in the side pane, and then click **File** or **Syslog**.
6. Click **Create**, enter information as described in the Help text in the main pane, and click **Apply**.