

## Specifying the Type of Event Queue

---

To specify whether the event queue is persistent or nonpersistent:

1. Create a folder for the VTA on a host.

```
mkdir vta
```

2. Copy the EAR file for the VTA from the archive file to the folder that you created in Step 1.
3. From the EAR file, extract the file *vtacore.jar* into the folder you created.

```
cd vta  
jar xvf quotavta.ear vtacore.jar
```

4. From the file *vtacore.jar*, extract the file *META-INF/ejb-jar.xml*.

```
jar xvf vtacore.jar META-INF/ejb-jar.xml
```

5. In the folder that you created in Step 1, edit the *META-INF/ejb-jar.xml* file.

See “Event Queue Property” on page 1 for information about the property that specifies the type of event queue.

6. Replace the file *META-INF/ejb-jar.xml* in the file *vtacore.jar*.

```
jar uvf vtacore.jar META-INF/ejb-jar.xml
```

7. Replace the file *vtacore.jar* in the EAR file.

```
jar uvf quotavta.ear vtacore.jar
```

- Related Topics**
- Setting the Size of the Event Queue
  - Calculating the Size of the Nonpersistent Event Queue
  - Configuring the Event Queue Size
  - Configuring Events

## Event Queue Property

This topic describes the event queue property.

### PersistentQueue

- Type of queue—persistent or nonpersistent.
- Value—true or false
- Default—false

