

## Configuring Protocol Conditions with Parameters (C-Web Interface)

---

Before you assign a parameter for the protocol, you must create a parameter of type protocol and commit the parameter configuration.

To configure a protocol condition that contains a parameter value for the protocol:

1. In the side pane, select a policy rule.
2. From the Create new list, expand a traffic condition, and select **Parameter Protocol Condition**.
3. Click **Create**, enter information as described in the Help text in the main pane, and click **Apply**.
4. (Optional) To configure protocol attributes:
  - a. In the side pane, expand **Parameter Protocol Condition**, and select **Proto Attr**.
  - b. Click **Create**, enter information as described in the Help text in the main pane, and click **Apply**.

To configure source and destination ports:

1. In the side pane, expand **Proto Attr > Source Port**, and select **Port**.
2. Click **Create**, enter information as described in the Help text in the main pane, and click **Apply**.
3. In the side pane, expand **Proto Attr > Destination Port**, and select **Port**.
4. Click **Create**, enter information as described in the Help text in the main pane, and click **Apply**.

- Related Topics**
- [Configuring Protocol Conditions with Parameters \(SRC CLI\)](#)
  - [Configuring Protocol Conditions \(C-Web Interface\)](#)
  - [Configuring Protocol Conditions with Ports \(C-Web Interface\)](#)

---

Published: 2009-09-18