



---

# Standards Supported in Junos OS 11.2



Published: 2011-05-16  
Part Number: , Revision

Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, California 94089  
USA  
408-745-2000  
www.juniper.net

This product includes the Envoy SNMP Engine, developed by Epilogue Technology, an Integrated Systems Company. Copyright © 1986-1997, Epilogue Technology Corporation. All rights reserved. This program and its documentation were developed at private expense, and no part of them is in the public domain.

This product includes memory allocation software developed by Mark Moraes, copyright © 1988, 1989, 1993, University of Toronto.

This product includes FreeBSD software developed by the University of California, Berkeley, and its contributors. All of the documentation and software included in the 4.4BSD and 4.4BSD-Lite Releases is copyrighted by the Regents of the University of California. Copyright © 1979, 1980, 1983, 1986, 1988, 1989, 1991, 1992, 1993, 1994. The Regents of the University of California. All rights reserved.

GateD software copyright © 1995, the Regents of the University. All rights reserved. Gate Daemon was originated and developed through release 3.0 by Cornell University and its collaborators. Gated is based on Kirton's EGP, UC Berkeley's routing daemon (routed), and DCN's HELLO routing protocol. Development of Gated has been supported in part by the National Science Foundation. Portions of the GateD software copyright © 1988, Regents of the University of California. All rights reserved. Portions of the GateD software copyright © 1991, D. L. S. Associates.

This product includes software developed by Maker Communications, Inc., copyright © 1996, 1997, Maker Communications, Inc.

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Products made or sold by Juniper Networks or components thereof might be covered by one or more of the following patents that are owned by or licensed to Juniper Networks: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

*Standards Supported in Junos OS 11.2*  
Copyright © 2011, Juniper Networks, Inc.  
All rights reserved.

Revision History  
May 2011—R1 Junos OS 11.2

The information in this document is current as of the date listed in the revision history.

## END USER LICENSE AGREEMENT

**READ THIS END USER LICENSE AGREEMENT ("AGREEMENT") BEFORE DOWNLOADING, INSTALLING, OR USING THE SOFTWARE.** BY DOWNLOADING, INSTALLING, OR USING THE SOFTWARE OR OTHERWISE EXPRESSING YOUR AGREEMENT TO THE TERMS CONTAINED HEREIN, YOU (AS CUSTOMER OR IF YOU ARE NOT THE CUSTOMER, AS A REPRESENTATIVE/AGENT AUTHORIZED TO BIND THE CUSTOMER) CONSENT TO BE BOUND BY THIS AGREEMENT. IF YOU DO NOT OR CANNOT AGREE TO THE TERMS CONTAINED HEREIN, THEN (A) DO NOT DOWNLOAD, INSTALL, OR USE THE SOFTWARE, AND (B) YOU MAY CONTACT JUNIPER NETWORKS REGARDING LICENSE TERMS.

1. **The Parties.** The parties to this Agreement are (i) Juniper Networks, Inc. (if the Customer's principal office is located in the Americas) or Juniper Networks (Cayman) Limited (if the Customer's principal office is located outside the Americas) (such applicable entity being referred to herein as "Juniper"), and (ii) the person or organization that originally purchased from Juniper or an authorized Juniper reseller the applicable license(s) for use of the Software ("Customer") (collectively, the "Parties").

2. **The Software.** In this Agreement, "Software" means the program modules and features of the Juniper or Juniper-supplied software, for which Customer has paid the applicable license or support fees to Juniper or an authorized Juniper reseller, or which was embedded by Juniper in equipment which Customer purchased from Juniper or an authorized Juniper reseller. "Software" also includes updates, upgrades and new releases of such software. "Embedded Software" means Software which Juniper has embedded in or loaded onto the Juniper equipment and any updates, upgrades, additions or replacements which are subsequently embedded in or loaded onto the equipment.

3. **License Grant.** Subject to payment of the applicable fees and the limitations and restrictions set forth herein, Juniper grants to Customer a non-exclusive and non-transferable license, without right to sublicense, to use the Software, in executable form only, subject to the following use restrictions:

- a. Customer shall use Embedded Software solely as embedded in, and for execution on, Juniper equipment originally purchased by Customer from Juniper or an authorized Juniper reseller.
- b. Customer shall use the Software on a single hardware chassis having a single processing unit, or as many chassis or processing units for which Customer has paid the applicable license fees; provided, however, with respect to the Steel-Belted Radius or Odyssey Access Client software only, Customer shall use such Software on a single computer containing a single physical random access memory space and containing any number of processors. Use of the Steel-Belted Radius or IMS AAA software on multiple computers or virtual machines (e.g., Solaris zones) requires multiple licenses, regardless of whether such computers or virtualizations are physically contained on a single chassis.
- c. Product purchase documents, paper or electronic user documentation, and/or the particular licenses purchased by Customer may specify limits to Customer's use of the Software. Such limits may restrict use to a maximum number of seats, registered endpoints, concurrent users, sessions, calls, connections, subscribers, clusters, nodes, realms, devices, links, ports or transactions, or require the purchase of separate licenses to use particular features, functionalities, services, applications, operations, or capabilities, or provide throughput, performance, configuration, bandwidth, interface, processing, temporal, or geographical limits. In addition, such limits may restrict the use of the Software to managing certain kinds of networks or require the Software to be used only in conjunction with other specific Software. Customer's use of the Software shall be subject to all such limitations and purchase of all applicable licenses.
- d. For any trial copy of the Software, Customer's right to use the Software expires 30 days after download, installation or use of the Software. Customer may operate the Software after the 30-day trial period only if Customer pays for a license to do so. Customer may not extend or create an additional trial period by re-installing the Software after the 30-day trial period.
- e. The Global Enterprise Edition of the Steel-Belted Radius software may be used by Customer only to manage access to Customer's enterprise network. Specifically, service provider customers are expressly prohibited from using the Global Enterprise Edition of the Steel-Belted Radius software to support any commercial network access services.

The foregoing license is not transferable or assignable by Customer. No license is granted herein to any user who did not originally purchase the applicable license(s) for the Software from Juniper or an authorized Juniper reseller.

4. **Use Prohibitions.** Notwithstanding the foregoing, the license provided herein does not permit the Customer to, and Customer agrees not to and shall not: (a) modify, unbundle, reverse engineer, or create derivative works based on the Software; (b) make unauthorized copies of the Software (except as necessary for backup purposes); (c) rent, sell, transfer, or grant any rights in and to any copy of the Software, in any form, to any third party; (d) remove any proprietary notices, labels, or marks on or in any copy of the Software or any product in which the Software is embedded; (e) distribute any copy of the Software to any third party, including as may be embedded in Juniper equipment sold in the secondhand market; (f) use any 'locked' or key-restricted feature, function, service, application, operation, or capability without first purchasing the applicable license(s) and obtaining a valid key from Juniper, even if such feature, function, service, application, operation, or capability is enabled without a key; (g) distribute any key for the Software provided by Juniper to any third party; (h) use the

Software in any manner that extends or is broader than the uses purchased by Customer from Juniper or an authorized Juniper reseller; (i) use Embedded Software on non-Juniper equipment; (j) use Embedded Software (or make it available for use) on Juniper equipment that the Customer did not originally purchase from Juniper or an authorized Juniper reseller; (k) disclose the results of testing or benchmarking of the Software to any third party without the prior written consent of Juniper; or (l) use the Software in any manner other than as expressly provided herein.

5. **Audit.** Customer shall maintain accurate records as necessary to verify compliance with this Agreement. Upon request by Juniper, Customer shall furnish such records to Juniper and certify its compliance with this Agreement.

6. **Confidentiality.** The Parties agree that aspects of the Software and associated documentation are the confidential property of Juniper. As such, Customer shall exercise all reasonable commercial efforts to maintain the Software and associated documentation in confidence, which at a minimum includes restricting access to the Software to Customer employees and contractors having a need to use the Software for Customer's internal business purposes.

7. **Ownership.** Juniper and Juniper's licensors, respectively, retain ownership of all right, title, and interest (including copyright) in and to the Software, associated documentation, and all copies of the Software. Nothing in this Agreement constitutes a transfer or conveyance of any right, title, or interest in the Software or associated documentation, or a sale of the Software, associated documentation, or copies of the Software.

8. **Warranty, Limitation of Liability, Disclaimer of Warranty.** The warranty applicable to the Software shall be as set forth in the warranty statement that accompanies the Software (the "Warranty Statement"). Nothing in this Agreement shall give rise to any obligation to support the Software. Support services may be purchased separately. Any such support shall be governed by a separate, written support services agreement. TO THE MAXIMUM EXTENT PERMITTED BY LAW, JUNIPER SHALL NOT BE LIABLE FOR ANY LOST PROFITS, LOSS OF DATA, OR COSTS OR PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, OR FOR ANY SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THIS AGREEMENT, THE SOFTWARE, OR ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. IN NO EVENT SHALL JUNIPER BE LIABLE FOR DAMAGES ARISING FROM UNAUTHORIZED OR IMPROPER USE OF ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. EXCEPT AS EXPRESSLY PROVIDED IN THE WARRANTY STATEMENT TO THE EXTENT PERMITTED BY LAW, JUNIPER DISCLAIMS ANY AND ALL WARRANTIES IN AND TO THE SOFTWARE (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT DOES JUNIPER WARRANT THAT THE SOFTWARE, OR ANY EQUIPMENT OR NETWORK RUNNING THE SOFTWARE, WILL OPERATE WITHOUT ERROR OR INTERRUPTION, OR WILL BE FREE OF VULNERABILITY TO INTRUSION OR ATTACK. In no event shall Juniper's or its suppliers' or licensors' liability to Customer, whether in contract, tort (including negligence), breach of warranty, or otherwise, exceed the price paid by Customer for the Software that gave rise to the claim, or if the Software is embedded in another Juniper product, the price paid by Customer for such other product. Customer acknowledges and agrees that Juniper has set its prices and entered into this Agreement in reliance upon the disclaimers of warranty and the limitations of liability set forth herein, that the same reflect an allocation of risk between the Parties (including the risk that a contract remedy may fail of its essential purpose and cause consequential loss), and that the same form an essential basis of the bargain between the Parties.

9. **Termination.** Any breach of this Agreement or failure by Customer to pay any applicable fees due shall result in automatic termination of the license granted herein. Upon such termination, Customer shall destroy or return to Juniper all copies of the Software and related documentation in Customer's possession or control.

10. **Taxes.** All license fees payable under this agreement are exclusive of tax. Customer shall be responsible for paying Taxes arising from the purchase of the license, or importation or use of the Software. If applicable, valid exemption documentation for each taxing jurisdiction shall be provided to Juniper prior to invoicing, and Customer shall promptly notify Juniper if their exemption is revoked or modified. All payments made by Customer shall be net of any applicable withholding tax. Customer will provide reasonable assistance to Juniper in connection with such withholding taxes by promptly: providing Juniper with valid tax receipts and other required documentation showing Customer's payment of any withholding taxes; completing appropriate applications that would reduce the amount of withholding tax to be paid; and notifying and assisting Juniper in any audit or tax proceeding related to transactions hereunder. Customer shall comply with all applicable tax laws and regulations, and Customer will promptly pay or reimburse Juniper for all costs and damages related to any liability incurred by Juniper as a result of Customer's non-compliance or delay with its responsibilities herein. Customer's obligations under this Section shall survive termination or expiration of this Agreement.

11. **Export.** Customer agrees to comply with all applicable export laws and restrictions and regulations of any United States and any applicable foreign agency or authority, and not to export or re-export the Software or any direct product thereof in violation of any such restrictions, laws or regulations, or without all necessary approvals. Customer shall be liable for any such violations. The version of the Software supplied to Customer may contain encryption or other capabilities restricting Customer's ability to export the Software without an export license.

12. **Commercial Computer Software.** The Software is "commercial computer software" and is provided with restricted rights. Use, duplication, or disclosure by the United States government is subject to restrictions set forth in this Agreement and as provided in DFARS 227.7201 through 227.7202-4, FAR 12.212, FAR 27.405(b)(2), FAR 52.227-19, or FAR 52.227-14 (ALT III) as applicable.

13. **Interface Information.** To the extent required by applicable law, and at Customer's written request, Juniper shall provide Customer with the interface information needed to achieve interoperability between the Software and another independently created program, on payment of applicable fee, if any. Customer shall observe strict obligations of confidentiality with respect to such information and shall use such information in compliance with any applicable terms and conditions upon which Juniper makes such information available.

14. **Third Party Software.** Any licensor of Juniper whose software is embedded in the Software and any supplier of Juniper whose products or technology are embedded in (or services are accessed by) the Software shall be a third party beneficiary with respect to this Agreement, and such licensor or vendor shall have the right to enforce this Agreement in its own name as if it were Juniper. In addition, certain third party software may be provided with the Software and is subject to the accompanying license(s), if any, of its respective owner(s). To the extent portions of the Software are distributed under and subject to open source licenses obligating Juniper to make the source code for such portions publicly available (such as the GNU General Public License ("GPL") or the GNU Library General Public License ("LGPL")), Juniper will make such source code portions (including Juniper modifications, as appropriate) available upon request for a period of up to three years from the date of distribution. Such request can be made in writing to Juniper Networks, Inc., 1194 N. Mathilda Ave., Sunnyvale, CA 94089, ATTN: General Counsel. You may obtain a copy of the GPL at <http://www.gnu.org/licenses/gpl.html>, and a copy of the LGPL at <http://www.gnu.org/licenses/lgpl.html>.

15. **Miscellaneous.** This Agreement shall be governed by the laws of the State of California without reference to its conflicts of laws principles. The provisions of the U.N. Convention for the International Sale of Goods shall not apply to this Agreement. For any disputes arising under this Agreement, the Parties hereby consent to the personal and exclusive jurisdiction of, and venue in, the state and federal courts within Santa Clara County, California. This Agreement constitutes the entire and sole agreement between Juniper and the Customer with respect to the Software, and supersedes all prior and contemporaneous agreements relating to the Software, whether oral or written (including any inconsistent terms contained in a purchase order), except that the terms of a separate written agreement executed by an authorized Juniper representative and Customer shall govern to the extent such terms are inconsistent or conflict with terms contained herein. No modification to this Agreement nor any waiver of any rights hereunder shall be effective unless expressly assented to in writing by the party to be charged. If any portion of this Agreement is held invalid, the Parties agree that such invalidity shall not affect the validity of the remainder of this Agreement. This Agreement and associated documentation has been written in the English language, and the Parties agree that the English version will govern. (For Canada: Les parties aux présentes confirment leur volonté que cette convention de même que tous les documents y compris tout avis qui s'y rattache, soient rédigés en langue anglaise. (Translation: The parties confirm that this Agreement and all related documentation is and will be in the English language)).



# Table of Contents

<b>Part 1</b>	<b>Overview</b>	
<b>Chapter 1</b>	<b>Accessing Standards Documents</b>	<b>3</b>
	Accessing Standards Documents on the Internet	3
<b>Part 2</b>	<b>Supported Standards</b>	
<b>Chapter 2</b>	<b>Chassis and System Standards</b>	<b>7</b>
	Supported BOOTP and DHCP Standards	7
	Supported Mobile IP Standards	8
	Supported Network Management Standards	9
	Supported RADIUS and TACACS+ Standards for User Authentication	18
	Supported System Access Standards	19
	Supported Time Synchronization Standard	20
<b>Chapter 3</b>	<b>Interface Standards</b>	<b>21</b>
	Supported ATM Interface Standards	21
	Supported Ethernet Interface Standards	22
	Supported Frame Relay Interface Standards	22
	Supported GRE and IP-IP Interface Standards	23
	Supported PPP Interface Standards	24
	Supported SDH and SONET Interface Standards	24
	Supported Serial Interface Standards	25
	Supported T3 Interface Standard	26
<b>Chapter 4</b>	<b>Layer 2 Standards</b>	<b>27</b>
	Supported Layer 2 Networking Standards	27
	Supported L2TP Standards	28
	Supported Layer 2 Circuit Standards	28
	Supported Layer 2 VPN Standard	29
<b>Chapter 5</b>	<b>MPLS Applications Standards</b>	<b>31</b>
	Supported GMPLS Standards	31
	Supported LDP Standards	32
	Supported MPLS Standards	33
	Supported RSVP Standards	35
<b>Chapter 6</b>	<b>Packet Processing Standards</b>	<b>37</b>
	Supported CoS Standards	37
	Supported Packet Filtering Standards	38
	Supported Policing Standard	38

<b>Chapter 7</b>	<b>Routing Protocol Standards . . . . .</b>	<b>41</b>
	Supported BGP Standards . . . . .	41
	Supported ES-IS Standards . . . . .	42
	Supported ICMP and Neighbor Discovery Standards . . . . .	43
	Supported IP Multicast Protocol Standards . . . . .	43
	Supported IPv4, TCP, and UDP Standards . . . . .	45
	Supported IPv6 Standards . . . . .	46
	Supported IS-IS Standards . . . . .	49
	Supported OSPF and OSPFv3 Standards . . . . .	50
	Supported RIP and RIPng Standards . . . . .	51
<b>Chapter 8</b>	<b>Services PIC and DPC Standards . . . . .</b>	<b>53</b>
	Supported DTCP Standard . . . . .	53
	Supported Flow Monitoring and Discard Accounting Standards . . . . .	53
	Supported IPsec and IKE Standards . . . . .	54
	Supported L2TP Standards . . . . .	55
	Supported Link Services Standards . . . . .	55
	Supported NAT and SIP Standards . . . . .	55
	Supported RPM Standard . . . . .	56
	Supported Voice Services Standards . . . . .	56
<b>Chapter 9</b>	<b>VPLS and VPN Standards . . . . .</b>	<b>57</b>
	Supported Carrier-of-Carriers and Interprovider VPN Standards . . . . .	57
	Supported Layer 2 VPN Standard . . . . .	57
	Supported Layer 3 VPN Standards . . . . .	58
	Supported Multicast VPN Standards . . . . .	59
	Supported VPLS Standards . . . . .	59
<b>Part 3</b>	<b>Index</b>	
	Index . . . . .	63
	Index of Supported Software Standards . . . . .	67

## PART 1

# Overview

- Accessing Standards Documents on page 3



## CHAPTER 1

# Accessing Standards Documents

- Accessing Standards Documents on the Internet on page 3

### Accessing Standards Documents on the Internet

---

The following information about the location of standards on the Internet is accurate as of February 2011. It is subject to change and is provided only as a courtesy to the reader.

Information about accessing MIBs is provided in the entry for each MIB.

- ANSI standards are published by the American National Standards Institute. You can search for specific standards at <http://webstore.ansi.org>.
- FRF (Frame Relay Forum) standards are published by the Broadband Forum. They can be accessed at <http://www.broadband-forum.org/technical/frametechspec.php>.
- GR (Generic Requirements) standards are published by Telcordia. Information about them can be accessed by clicking the “Document Center” link at <http://telecom-info.telcordia.com/site-cgi/ido/>.
- IEEE standards are published by the Institute of Electrical and Electronics Engineers. They can be accessed at <http://standards.ieee.org/getieee802/index.html>.
- ISO/IEC standards are published by the International Organization for Standardization/International Electrotechnical Commission. They can be accessed at [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/](http://www.iso.org/iso/iso_catalogue/catalogue_tc/).
- INCITS standards are published by the InterNational Committee for Information Technology Standards. They can be accessed at <https://standards.incits.org/>.
- Internet drafts are published by the Internet Engineering Task Force (IETF). They can be accessed at <http://tools.ietf.org/id/>.
- ITU–T Recommendations are published by the International Telecommunication Union. They can be accessed at <http://www.itu.int/rec/T-REC>.
- RFCs are published by the IETF. They can be accessed at <http://www.ietf.org/rfc.html>.



## PART 2

# Supported Standards

- Chassis and System Standards on page 7
- Interface Standards on page 21
- Layer 2 Standards on page 27
- MPLS Applications Standards on page 31
- Packet Processing Standards on page 37
- Routing Protocol Standards on page 41
- Services PIC and DPC Standards on page 53
- VPLS and VPN Standards on page 57



## CHAPTER 2

# Chassis and System Standards

- Supported BOOTP and DHCP Standards on page 7
- Supported Mobile IP Standards on page 8
- Supported Network Management Standards on page 9
- Supported RADIUS and TACACS+ Standards for User Authentication on page 18
- Supported System Access Standards on page 19
- Supported Time Synchronization Standard on page 20

### Supported BOOTP and DHCP Standards

---

The Junos OS substantially supports the following RFCs, which define standards for bootstrap protocol (BOOTP) and Dynamic Host Control Protocol (DHCP).

- RFC 951, *BOOTSTRAP PROTOCOL (BOOTP)*
- RFC 1001, *PROTOCOL STANDARD FOR A NetBIOS SERVICE ON A TCP/UDP TRANSPORT: CONCEPTS AND METHODS*
- RFC 1002, *PROTOCOL STANDARD FOR A NetBIOS SERVICE ON A TCP/UDP TRANSPORT: DETAILED SPECIFICATIONS*
- RFC 1035, *DOMAIN NAMES - IMPLEMENTATION AND SPECIFICATION*
- RFC 1534, *Interoperation Between DHCP and BOOTP*
- RFC 1700, *ASSIGNED NUMBERS*
- RFC 2131, *Dynamic Host Configuration Protocol*
- DHCP over virtual LAN (VLAN)-tagged interfaces is not supported.
- RFC 2132, *DHCP Options and BOOTP Vendor Extensions*
- RFC 3046, *DHCP Relay Agent Information Option*
- RFC 3118, *Authentication for DHCP Messages*

Only Section 4, "Configuration token," is supported.

- RFC 3315, *Dynamic Host Configuration Protocol for IPv6 (DHCPv6)*
- Address assignment is supported with IP version 4 (IPv4) but not IP version 6 (IPv6).
- RFC 3397, *Dynamic Host Configuration Protocol (DHCP) Domain Search Option*

- RFC 3633, *IPv6 Prefix Options for Dynamic Host Configuration Protocol (DHCP) version 6*
- RFC 3925, *Vendor-Identifying Vendor Options for Dynamic Host Configuration Protocol version 4 (DHCPv4)*
- RFC 4649, *Dynamic Host Configuration Protocol for IPv6 (DHCPv6) Relay Agent Remote-ID Option*

**Related  
Documentation**

- Accessing Standards Documents on the Internet on page 3

---

## Supported Mobile IP Standards

---

The Junos OS supports only static configuration of home agent addresses and IP tunnels; dynamic configuration is not supported. The Junos OS does not support the Mobile IP foreign agent, accounting, QoS, policy, data path, or logical interfaces per mobile node (for a mobile subscriber).

The Junos OS substantially supports the following RFCs, which define standards for Mobile IP.

- RFC 2794, *Mobile IP Network Access Identifier Extension for IPv4*
- RFC 3024, *Reverse Tunneling for Mobile IP, revised*
- RFC 3344, *IP Mobility Support for IPv4*

Only the Mobile IP home agent is supported.

- RFC 3543, *Registration Revocation in Mobile IPv4*
- RFC 4433, *Mobile IPv4 Dynamic Home Agent (HA) Assignment*

The following RFC does not define a standard, but provides information about Mobile IP. The IETF classifies it as “Informational.”

- RFC 2977, *Mobile IP Authentication, Authorization, and Accounting Requirements*  
Accounting is not supported.

**Related  
Documentation**

- Accessing Standards Documents on the Internet on page 3

## Supported Network Management Standards

The Junos OS supports the majority of network management features defined in the following standards documents.

- Extended Security Options (ESO) Consortium, *ESO Consortium MIB*.

As of February 2011, the text of this MIB is accessible at

<http://www.snmp.com/eso/esoConsortiumMIB.txt>.

- Institute of Electrical and Electronics Engineers (IEEE) Standard 802.3ad, *Aggregation of Multiple Link Segments* (published as Clause 43 in Section 3 of the 802.3 specification)

Only the following MIB objects are supported:

- dot3adAggPortDebugActorChangeCount**
- dot3adAggPortDebugActorSyncTransitionCount**
- dot3adAggPortDebugMuxState**
- dot3adAggPortDebugPartnerChangeCount**
- dot3adAggPortDebugPartnerSyncTransitionCount**
- dot3adAggPortDebugRxState**
- dot3adAggPortListTable**
- dot3adAggPortStatsTable**
- dot3adAggPortTable**
- dot3adAggTable**
- dot3adTablesLastChanged**

Gigabit Ethernet interfaces on J Series Services Routers do not support the 802.3ad MIB.

- Integrated Local Management Interface (ILMI) MIB in the *Integrated Local Management Interface (ILMI) Specification, Version 4.0*.

As of February 2011, this document is accessible at

<http://www.broadband-forum.org/ftp/pub/approved-specs/af-ilmi-0065.000.pdf>.

Only the **atmfMYIPNmAddress** and **atmfPortMyIfname** objects are supported.

- Internet Assigned Numbers Authority (IANA), *IANAiftype Textual Convention MIB* (referenced by RFC 2863, *The Interfaces Group MIB*)

As of February 2011, the text of this MIB is accessible at

<http://www.iana.org/assignments/ianaiftype-mib>.

- RFC 1122, *Requirements for Internet Hosts -- Communication Layers*

- RFC 1155, *Structure and Identification of Management Information for TCP/IP-based Internets*
- RFC 1156, *Management Information Base for Network Management of TCP/IP-based internets*
- RFC 1157, *A Simple Network Management Protocol (SNMP)*
- RFC 1195, *Use of OSI IS-IS for Routing in TCP/IP and Dual Environments*

Only the following MIB objects are supported:

- **isisAdjIPAddr**
- **isisAreaAddr**
- **isisCirc**
- **isisCircLevel**
- **isisIPRA**
- **isisISAdj**
- **isisISAdjAreaAddr**
- **isisISAdjProtSupp**
- **isisMANAreaAddr**
- **isisPacketCount**
- **isisRa**
- **isisSysProtSupp**
- **isisSummAddr**
- **isisSystem**
- RFC 1212, *Concise MIB Definitions*

- RFC 1213, *Management Information Base for Network Management of TCP/IP-based internets: MIB-II*

Only the following features are supported:

- Junos-specific secured access list
- Master configuration keywords
- MIB II and its SNMP version 2 derivatives, including the following:
  - Interface management
  - IP (except for the **ipRouteTable** object, which has been replaced by **ipCidrRouteTable** [RFC 2096, *IP Forwarding Table MIB*])
  - SNMP management
  - Statistics counters
- Reconfigurations upon receipt of the SIGHUP signal
- SNMP version 1 **Get** and **GetNext** requests and version 2 **GetBulk** requests

- RFC 1215, *A Convention for Defining Traps for use with the SNMP*

Only MIB II SNMP version 1 traps and version 2 notifications are supported.

- RFC 1406, *Definitions of Managed Objects for the DS1 and E1 Interface Types* (obsoleted by RFC 2495)

The T1 MIB is supported.

- RFC 1407, *Definitions of Managed Objects for the DS3/E3 Interface Type* (obsoleted by RFC 2496)

The T3 MIB is supported.

- RFC 1472, *The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol*
- RFC 1473, *The Definitions of Managed Objects for the IP Network Control Protocol of the Point-to-Point Protocol*
- RFC 1657, *Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIv2*

The **bgpBackwardTransition** and **bgpEstablished** notifications are not supported.

- RFC 1695, *Definitions of Managed Objects for ATM Management Version 8.0 Using SMIv2* (obsoleted by RFC 2515)
- RFC 1724, *RIP Version 2 MIB Extension*

- RFC 1850, *OSPF Version 2 Management Information Base*

The following features are not supported:

- Host Table
- **ospfLsdbApproachingOverflow** trap
- **ospfLsdbOverflow** trap
- **ospfOriginateLSA** trap
- **ospfOriginateNewLsas** MIB object
- **ospfRxNewLsas** MIB object
- RFC 1905, *Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)* (obsoleted by RFC 3416)
- RFC 1907, *Management Information Base for Version 2 of the Simple Network Management Protocol (SNMPv2)* (obsoleted by RFC 3418)
- RFC 2011, *SNMPv2 Management Information Base for the Internet Protocol using SMIv2*
- RFC 2012, *SNMPv2 Management Information Base for the Transmission Control Protocol using SMIv2*
- RFC 2013, *SNMPv2 Management Information Base for the User Datagram Protocol using SMIv2*
- RFC 2068, *Hypertext Transfer Protocol -- HTTP/1.1*
- RFC 2096, *IP Forwarding Table MIB*

The **ipCidrRouteTable** object is extended to include the tunnel name when the next hop is through an RSVP-signaled label-switched path (LSP).

- RFC 2115, *Management Information Base for Frame Relay DTEs Using SMIv2*

Only the **frDlcmiTable** object is supported.

- RFC 2233, *The Interfaces Group MIB using SMIv2* (obsoleted by RFC 2863)
- RFC 2287, *Definitions of System-Level Managed Objects for Applications*

Only the following MIB objects are supported:

- **sysApplElmtRunTable**
- **sysApplInstallElmtTable**
- **sysApplInstallPkgTable**
- **sysApplMapTable**
- RFC 2465, *Management Information Base for IP Version 6: Textual Conventions and General Group*

IP version 6 (IPv6) and Internet Control Message Protocol version 6 (ICMPv6) statistics are not supported.

- RFC 2466, *Management Information Base for IP Version 6: ICMPv6 Group*
- RFC 2495, *Definitions of Managed Objects for the DS1, E1, DS2 and E2 Interface Types*

The following MIB objects are not supported:

- **dsx1FarEndConfigTable**
  - **dsx1FarEndCurrentTable**
  - **dsx1FarEndIntervalTable**
  - **dsx1FarEndTotalTable**
  - **dsx1FracTable**
- RFC 2496, *Definitions of Managed Objects for the DS3/E3 Interface Type*

The following MIB objects are not supported:

- **dsx3FarEndConfigTable**
  - **dsx3FarEndCurrentTable**
  - **dsx3FarEndIntervalTable**
  - **dsx3FarEndTotalTable**
  - **dsx3FracTable**
- RFC 2515, *Definitions of Managed Objects for ATM Management*

The following MIB objects are not supported:

- **aal5VccTable**
  - **atmVcCrossConnectTable**
  - **atmVpCrossConnectTable**
- RFC 2558, *Definitions of Managed Objects for the SONET/SDH Interface Type* (obsoleted by RFC 3592)
  - RFC 2571, *An Architecture for Describing SNMP Management Frameworks*  
Only read-only access is supported.
  - RFC 2572, *Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)* (obsoleted by RFC 3412)  
Only read-only access is supported.
  - RFC 2578, *Structure of Management Information Version 2 (SMIv2)*
  - RFC 2579, *Textual Conventions for SMIv2*
  - RFC 2580, *Conformance Statements for SMIv2*

- RFC 2662, *Definitions of Managed Objects for the ADSL Lines*

Supported on J Series Services Routers. All MIB tables, objects, and traps applicable to the asymmetric digital subscriber line (ADSL) transceiver unit-remote (ATU-R) agent are supported.

- RFC 2665, *Definitions of Managed Objects for the Ethernet-like Interface Types*
- RFC 2667, *IP Tunnel MIB*
- RFC 2787, *Definitions of Managed Objects for the Virtual Router Redundancy Protocol*

The following features are not supported:

- Row creation
- **Set** operation
- **vrpStatsPacketLengthErrors** MIB object
- RFC 2790, *Host Resources MIB*

Only the following MIB objects are supported:

- **hrStorageTable** object. The file systems **/**, **/config**, **/var**, and **/tmp** always return the same index number. When SNMP restarts, the index numbers for the remaining file systems might change.
- Objects in the **hrSystem** group.
- Objects in the **hrSWInstalled** group.

- RFC 2819, *Remote Network Monitoring Management Information Base*

Only the following MIB objects are supported:

- **alarmTable**
- **etherStatsTable** object for Ethernet interfaces
- **eventTable**
- **logTable**
- RFC 2863, *The Interfaces Group MIB*
- RFC 2864, *The Inverted Stack Table Extension to the Interfaces Group MIB*

- RFC 2925, *Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations*

Only the following MIB objects are supported:

- **pingCtlTable**
- **pingMaxConcurrentRequests**
- **pingProbeHistoryTable**
- **pingResultsTable**
- **traceRouteCtlTable**
- **traceRouteHopsTable**
- **traceRouteProbeHistoryTable**
- **traceRouteResultsTable**
- RFC 2932, *IPv4 Multicast Routing MIB*
- RFC 2933, *Internet Group Management Protocol MIB*
- RFC 2981, *Event MIB*
- RFC 3014, *Notification Log MIB*
- RFC 3019, *IP Version 6 Management Information Base for The Multicast Listener Discovery Protocol*
- RFC 3411, *An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks*
- RFC 3412, *Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)*
- RFC 3413, *Simple Network Management Protocol (SNMP) Applications*

The proxy MIB is not supported.

- RFC 3414, *User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)*
- RFC 3415, *View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)*
- RFC 3416, *Version 2 of the Protocol Operations for the Simple Network Management Protocol (SNMP)*
- RFC 3417, *Transport Mappings for the Simple Network Management Protocol (SNMP)*
- RFC 3418, *Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)*
- RFC 3498, *Definitions of Managed Objects for Synchronous Optical Network (SONET) Linear Automatic Protection Switching (APS) Architectures*

Support is implemented under the Juniper Networks enterprise branch.

- RFC 3592, *Definitions of Managed Objects for the Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH) Interface Type*
- RFC 3811, *Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management*
- RFC 3812, *Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)*

Only read-only access is supported, and the following features and MIB objects are not supported:

- MPLS tunnels as interfaces
- **mplsTunnelCRLDPResTable** object
- **mplsTunnelPerfTable** object
- The following objects in the **TunnelResource** table:
  - **mplsTunnelResourceExBurstSize**
  - **mplsTunnelResourceMaxBurstSize**
  - **mplsTunnelResourceMeanBurstSize**
  - **mplsTunnelResourceMeanRate**
  - **mplsTunnelResourceWeight**

The **mplsTunnelCHopTable** object is supported on ingress routers only.



**NOTE:** The branch used by the proprietary LDP MIB (**ldpmib.mib**) conflicts with RFC 3812. **ldpmib.mib** has been deprecated and replaced by **jnx-mpls-ldp.mib**.

- RFC 3813, *Multiprotocol Label Switching (MPLS) Label Switching Router (LSR) Management Information Base (MIB)*

Only read-only access is supported, and the following MIB objects are not supported:

- **mplsInSegmentMapTable**
- **mplsInSegmentPerfTable**
- **mplsInterfacePerfTable**
- **mplsOutSegmentPerfTable**
- **mplsXCDown**
- **mplsXCUp**

- RFC 3815, *Definitions of Managed Objects for the Multiprotocol Label Switching (MPLS), Label Distribution Protocol (LDP)*

Only the following MIB objects are supported:

- **mplsLdpLsrID**
- **mplsLdpSesPeerAddrTable**
- RFC 3826, *The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model*
- RFC 4188, *Definitions of Managed Objects for Bridges*
- Internet draft draft-ietf-bfd-mib-02.txt, *Bidirectional Forwarding Detection Management Information Base*

Only read-only access is supported, and the **bfdSessDown** and **bfdSessUp** traps are supported. Objects in the **bfdSessMapTable** and **bfdSessPerfTable** tables are not supported. The MIB that supports this draft is **mib-jnx-bfd-exp.txt** under the Juniper Networks Enterprise **jnxExperiment** branch.

- Internet draft draft-ietf-idr-bgp4-mibv2-04.txt, *Definitions of Managed Objects for the Fourth Version of Border Gateway Protocol (BGP-4), Second Version*

Only the following MIB objects are supported:

- **jnxBgpM2PrefixInPrefixes**
- **jnxBgpM2PrefixInPrefixesAccepted**
- **jnxBgpM2PrefixInPrefixesRejected**
- Internet draft draft-ietf-isis-wg-mib-07.txt, *Management Information Base for IS-IS*

Only the following tables are supported:

- **isisSAdjAreaAddrTable**
- **isisSAdjIPAddrTable**
- **isisSAdjProtSuppTable**
- **isisSAdjTable**
- Internet draft draft-ietf-msdp-mib-08.txt, *Multicast Source Discovery protocol MIB*

The following MIB objects are not supported:

- **msdpBackwardTransition**
- **msdpEstablished**
- **msdpRequestsTable**

- Internet draft draft-ietf-ospf-ospfv3-mib-11.txt, *Management Information Base for OSPFv3*

Only read-only access is supported, and only for the **ospfv3NbrTable** table. The MIB that supports this draft is **mib-jnx-ospfv3mib.txt** under the Juniper Networks Enterprise **jnxExperiment** branch; MIB object names are prefixed with **jnx** (for example, **jnxOspfv3NbrAddressType**).

- Internet draft draft-reeder-snmpv3-usm-3desede-00.txt, *Extension to the User-Based Security Model (USM) to Support Triple-DES EDE in “Outside” CBC Mode*

The following RFCs do not define standards, but provide information about network management. The IETF classifies them variously as “Best Current Practice,” “Experimental” or “Informational.”

- RFC 1901, *Introduction to Community-based SNMPv2*
- RFC 2330, *Framework for IP Performance Metrics*
- RFC 2934, *Protocol Independent Multicast MIB for IPv4*
- RFC 3410, *Introduction and Applicability Statements for Internet Standard Management Framework*
- RFC 3584, *Coexistence between Version 1, Version 2, and Version 3 of the Internet-standard Network Management Framework*

**Related  
Documentation**

- Network Management Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

---

## Supported RADIUS and TACACS+ Standards for User Authentication

For validation of the identity of users who attempt to access a router, the Junos OS supports RADIUS authentication, TACACS+ authentication, and authentication by means of Junos user accounts configured on the router. The Junos OS supports the configuration of Juniper Networks-specific RADIUS and TACACS+ attributes, and the creation of template accounts.

All users who can log in to the router must already be assigned to a Junos login class. A *login class* defines its members' access privileges during a login session, the commands they can and cannot issue, the configuration statements they can and cannot view or change, and the idle time before a member's login session is terminated.

The Junos OS substantially supports the following RFCs, which define standards for RADIUS and TACACS+.

- RFC 1492, *An Access Control Protocol, Sometimes Called TACACS*
- RFC 2865, *Remote Authentication Dial In User Service (RADIUS)*
- RFC 3162, *RADIUS and IPv6*
- RFC 4818, *RADIUS Delegated-IPv6-Prefix Attribute*

The following Internet drafts do not define standards, but provide information about RADIUS. The IETF classifies them as “Informational.”

- RFC 2866, *RADIUS Accounting*
- RFC 2868, *RADIUS Attributes for Tunnel Protocol Support*
- RFC 2869, *RADIUS Extensions*
- RFC 4679, *DSL Forum Vendor-Specific RADIUS Attributes*
- RFC 5176, *Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS)*

**Related  
Documentation**

- Supported System Access Standards on page 19
- Accessing Standards Documents on the Internet on page 3

---

## Supported System Access Standards

The Junos OS substantially supports the following protocols and applications for remote access to routers: telnet, FTP, rlogin, and finger. In addition, the Canada and U.S. version of the Junos OS substantially supports SSH as an access protocol.

The Junos OS substantially supports RFC 1994, *PPP Challenge Handshake Authentication Protocol (CHAP)*.

The Canada and U.S. version of the Junos OS substantially supports the following RFCs, which define standards for technologies used with Secure Sockets Layer (SSL):

- RFC 1319, *The MD2 Message-Digest Algorithm*
- RFC 1321, *The MD5 Message-Digest Algorithm*
- RFC 2246, *The TLS Protocol Version 1.0*
- RFC 3280, *Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile*

The following RFCs provide information about TFTP, which Junos OS supports as a remote access protocol. The IETF does not include the RFCs in its Standards track, instead assigning them status “Unknown (Legacy Stream)”.

- RFC 783, *THE TFTP PROTOCOL (REVISION 2)*.
- RFC 906, *Bootstrap Loading using TFTP*.

**Related  
Documentation**

- Supported RADIUS and TACACS+ Standards for User Authentication on page 18
- Accessing Standards Documents on the Internet on page 3

## Supported Time Synchronization Standard

---

The Junos OS substantially supports RFC 1305, *Network Time Protocol (Version 3) Specification, Implementation and Analysis*.

RFC 2030, *Simple Network Time Protocol (SNTP) Version 4 for IPv4, IPv6 and OSI*, does not define a standard, but provides information about time synchronization technology. The IETF classifies it as “Informational.”

In CLI operational mode, you can set the current date and time on the router manually or from an NTP server.

### **Related Documentation**

- [Accessing Standards Documents on the Internet on page 3](#)

## CHAPTER 3

# Interface Standards

- Supported ATM Interface Standards on page 21
- Supported Ethernet Interface Standards on page 22
- Supported Frame Relay Interface Standards on page 22
- Supported GRE and IP-IP Interface Standards on page 23
- Supported PPP Interface Standards on page 24
- Supported SDH and SONET Interface Standards on page 24
- Supported Serial Interface Standards on page 25
- Supported T3 Interface Standard on page 26

### Supported ATM Interface Standards

---

The Junos OS substantially supports the following standards for Asynchronous Transfer Mode (ATM) interfaces.

- International Telecommunication Union–Telecommunication Standardization (ITU–T) Recommendation I.432.3, *B-ISDN user-network interface - Physical layer specification: 1544 kbit/s and 2048 kbit/s operation*
- RFC 1483, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*  
Only routed protocol data units (PDUs) are supported.
- RFC 2225, *Classical IP and ARP over ATM*  
Only responses are supported.
- RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*  
Only routed PDUs and Ethernet bridged PDUs are supported.

#### Related Documentation

- Accessing Standards Documents on the Internet on page 3

## Supported Ethernet Interface Standards

---

The Junos OS substantially supports the following standards for Ethernet interfaces.

- Institute of Electrical and Electronics Engineers (IEEE) Standard 802.1ag, *IEEE Standard for Local and metropolitan area networks—Virtual Bridged Local Area Networks, Amendment 5: Connectivity Fault Management*
- IEEE Standard 802.1ah, *IEEE Standard for Local and metropolitan area networks—Virtual Bridged Local Area Networks, Amendment 7: Provider Backbone Bridges*
- IEEE Standard 802.1Q, *IEEE Standard for Local and metropolitan area networks—Virtual Bridged Local Area Networks*
- IEEE Standard 802.1Qbb, *IEEE Standard for Local and Metropolitan Area Networks---Virtual Bridged Local Area Networks - Amendment: Enhanced Transmission Selection*
- IEEE Standard 802.1Qbb, *IEEE Standard for Local and Metropolitan Area Networks---Virtual Bridged Local Area Networks - Amendment: Priority-based Flow Control*
- IEEE Standard 802.3, *IEEE Standard for Information technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 3: Carrier sense multiple access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications*
- IEEE Standard 802.3ad, *Aggregation of Multiple Link Segments* (published as Clause 43 in Section 3 of the 802.3 specification)
- IEEE Standard 802.3ah, *Operations, Administration, and Maintenance (OAM)* (published as Clause 57 in Section 5 of the 802.3 specification)
- InterNational Committee for Information Technology Standards (INCITS) T11, *Fibre Channel Interfaces*
- International Telecommunication Union—Telecommunication Standardization (ITU-T) Recommendation Y.1731, *OAM functions and mechanisms for Ethernet based networks*

### Related Documentation

- Accessing Standards Documents on the Internet on page 3

## Supported Frame Relay Interface Standards

---

The Junos OS substantially supports the following standards for Frame Relay interfaces.

- American National Standards Institute (ANSI), *Annex D, Additional Procedures for Permanent Virtual Connections (PVCs) Using Unnumbered Information Frames* to T1.617-1991, *Integrated Services Digital Network (ISDN)—Signaling Specification for Frame Relay Bearer Service for Digital Subscriber Signaling System Number 1 (DSS1)*
- Broadband Forum standard FRF.12, *Frame Relay Fragmentation Implementation Agreement*

- FRF.15, *End-to-End Multilink Frame Relay Implementation Agreement*
- FRF.16.1, *Multilink Frame Relay UNI/NNI Implementation Agreement*
- International Telecommunication Union–Telecommunication Standardization (ITU–T), *Annex A, Additional procedures for Permanent Virtual Connection (PVC) status management (using Unnumbered Information frames)* to Recommendation Q.933, *ISDN Digital Subscriber Signalling System No. 1 (DSS1) - Signalling specifications for frame mode switched and permanent virtual connection control and status monitoring*
- RFC 1973, *PPP in Frame Relay*
- RFC 2390, *Inverse Address Resolution Protocol*
- RFC 2427, *Multiprotocol Interconnect over Frame Relay* (obsoletes RFC 1490)
- RFC 2590, *Transmission of IPv6 Packets over Frame Relay Networks Specification*
- Internet draft draft-martini-frame-encap-mpls-01.txt, *Frame Relay Encapsulation over Pseudo-Wires* (expires December 2002)

Translation of the command/response bit and sequence numbers and padding are not supported.

**Related  
Documentation**

- Accessing Standards Documents on the Internet on page 3

---

## Supported GRE and IP-IP Interface Standards

---

The Junos OS substantially supports the following RFCs, which define standards for generic routing encapsulation (GRE) and IP-IP interfaces.

- RFC 2003, *IP Encapsulation within IP*
- RFC 2784, *Generic Routing Encapsulation (GRE)*
- RFC 2890, *Key and Sequence Number Extensions to GRE*

The key field is supported, but the sequence number field is not.

The following RFCs do not define standards, but provide information about GRE, IP-IP, and related technologies. The IETF classifies them as “Informational.”

- RFC 1701, *Generic Routing Encapsulation (GRE)*
- RFC 1702, *Generic Routing Encapsulation over IPv4 networks*
- RFC 2547, *BGP/MPLS VPNs* (over GRE tunnels)

**Related  
Documentation**

- Accessing Standards Documents on the Internet on page 3

## Supported PPP Interface Standards

---

The Junos OS substantially supports the following RFCs, which define standards for Point-to-Point Protocol (PPP) interfaces.

- RFC 1332, *The PPP Internet Protocol Control Protocol (IPCP)*
- RFC 1334, *PPP Authentication Protocols*
- RFC 1661, *The Point-to-Point Protocol (PPP)*
- RFC 1662, *PPP in HDLC-like Framing*
- RFC 1989, *PPP Link Quality Monitoring*
- RFC 1990, *The PPP Multilink Protocol (MP)*
- RFC 2364, *PPP Over AAL5*
- RFC 2615, *PPP over SONET/SDH*
- RFC 2686, *The Multi-Class Extension to Multi-Link PPP*

The following features are not supported:

- Negotiation of address field compression and protocol field compression PPP NCP options; instead, a full 4-byte PPP header is always sent
- Prefix elision
- RFC 3021, *Using 31-Bit Prefixes on IPv4 Point-to-Point Links*

The following RFCs do not define standards, but provide information about PPP. The IETF classifies them as “Informational.”

- RFC 1877, *PPP Internet Protocol Control Protocol Extensions for Name Server Addresses*
- RFC 2153, *PPP Vendor Extensions*

### Related Documentation

- Accessing Standards Documents on the Internet on page 3

## Supported SDH and SONET Interface Standards

---

The Junos OS substantially supports the following standards for SDH and SONET interfaces.

- American National Standards Institute (ANSI) standard T1.105-2001, *Synchronous Optical Network (SONET) – Basic Description including Multiplex Structure, Rates, and Formats*
- ANSI standard T1.105.02-2001, *Synchronous Optical Network (SONET) – Payload Mappings*
- ANSI standard T1.105.06-2002, *Synchronous Optical Network (SONET): Physical Layer Specifications*

- GR-253-CORE (Telcordia Generic Requirements standard), *Synchronous Optical Network (SONET) Transport Systems: Common Generic Criteria* (replaces GR-1377-CORE, *SONET OC-192 Transport System Generic Criteria*)
- GR-499-CORE, *Transport Systems Generic Requirements (TSGR): Common Requirements*
- International Telecommunication Union–Telecommunication Standardization (ITU–T) Recommendation G.691, *Optical interfaces for single channel STM-64 and other SDH systems with optical amplifiers*
- ITU–T Recommendation G.707 (1996), *Network node interface for the synchronous digital hierarchy (SDH)*
- ITU–T Recommendation G.783 (1994), *Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks*
- ITU–T Recommendation G.813 (1996), *Timing characteristics of SDH equipment slave clocks (SEC)*
- ITU–T Recommendation G.825 (1993), *The control of jitter and wander within digital networks which are based on the synchronous digital hierarchy (SDH)*
- ITU–T Recommendation G.826 (1999), *Error performance parameters and objectives for international, constant bit-rate digital paths at or above the primary rate*
- ITU–T Recommendation G.831 (1993), *Management capabilities of transport networks based on the synchronous digital hierarchy (SDH)*
- ITU–T Recommendation G.957 (1995), *Optical interfaces for equipments and systems relating to the synchronous digital hierarchy*
- ITU–T Recommendation G.958 (1994), *Digital line systems based on the synchronous digital hierarchy for use on optical fibre cables*
- ITU–T Recommendation I.432 (1993), *B-ISDN user-network interface – Physical layer specification*
- RFC 1619, *PPP over SONET/SDH*

**Related  
Documentation**

- Accessing Standards Documents on the Internet on page 3

---

## Supported Serial Interface Standards

The Junos OS substantially supports the following standards for serial interfaces.

- International Telecommunication Union–Telecommunication Standardization (ITU–T) Recommendation V.35, *Data transmission at 48 kilobits per second using 60-108 kHz group band circuits*
- ITU–T Recommendation X.21 (1992), *Interface between Data Terminal Equipment and Data Circuit-terminating Equipment for synchronous operation on public data networks*

- Related Documentation**
- Accessing Standards Documents on the Internet on page 3

## Supported T3 Interface Standard

---

The Junos OS substantially supports International Telecommunication Union–Telecommunication Standardization (ITU–T) Recommendation G.703, *Physical/electrical characteristics of hierarchical digital interfaces*.

- Related Documentation**
- Accessing Standards Documents on the Internet on page 3

## CHAPTER 4

# Layer 2 Standards

- Supported Layer 2 Networking Standards on page 27
- Supported L2TP Standards on page 28
- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 2 VPN Standard on page 29

### Supported Layer 2 Networking Standards

---

The Junos OS substantially supports the following standards for Layer 2 networking.

- Institute of Electrical and Electronics Engineers (IEEE) Standard 802.1ab, *IEEE Standard for Local and metropolitan area networks—Station and Media Access Control Connectivity Discovery*
- IEEE Standard 802.1D, *IEEE Standard for Local and Metropolitan Area Networks: Media Access Control (MAC) Bridges*

This document includes the standard for Rapid Spanning Tree Protocol (RSTP), which is often referred to as 802.1w. It also discusses Quality of Service (QoS) at the MAC level, often referred to as 802.1p.

#### Related Documentation

- Supported L2TP Standards on page 28
- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 2 VPN Standard on page 29
- Accessing Standards Documents on the Internet on page 3

## Supported L2TP Standards

---

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Junos OS substantially supports the following RFC, which defines the standard for Layer 2 Tunneling Protocol (L2TP).

- RFC 2661, *Layer Two Tunneling Protocol "L2TP"*

The following RFC does not define a standard, but provides information about technology related to L2TP. The IETF classifies it as "Informational."

- RFC 2866, *RADIUS Accounting*

### Related Documentation

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported Layer 2 Circuit Standards

---

The Junos OS substantially supports the following RFCs, which define standards for Layer 2 circuits.

- RFC 4447, *Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)*

The Junos OS does not support Section 5.3, "The Generalized PWid FEC Element."

- RFC 4448, *Encapsulation Methods for Transport of Ethernet over MPLS Networks*

The following Internet drafts do not define standards, but provide information about Layer 2 technologies. The IETF classifies them as "Historic."

- Internet draft draft-martini-l2circuit-encap-mpls-11.txt, *Encapsulation Methods for Transport of Layer 2 Frames Over IP and MPLS Networks*

The Junos OS differs from the Internet draft in the following ways:

- A packet with a sequence number of 0 (zero) is treated as out of sequence.
- Any packet that does not have the next incremental sequence number is considered out of sequence.
- When out-of-sequence packets arrive, the expected sequence number for the neighbor is set to the sequence number in the Layer 2 circuit control word.
- Internet draft draft-martini-l2circuit-trans-mpls-19.txt, *Transport of Layer 2 Frames Over MPLS*

### Related Documentation

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 VPN Standard on page 29
- Supported Layer 3 VPN Standards on page 58

- Supported Multicast VPN Standards on page 59
- Supported VPLS Standards on page 59
- Accessing Standards Documents on the Internet on page 3

## Supported Layer 2 VPN Standard

---

The Junos OS substantially supports Internet draft draft-kompella-ppvnp-l2vpn-03.txt, *Layer 2 VPNs Over Tunnels*.

### **Related Documentation**

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 3 VPN Standards on page 58
- Supported Multicast VPN Standards on page 59
- Supported VPLS Standards on page 59
- Accessing Standards Documents on the Internet on page 3



## CHAPTER 5

# MPLS Applications Standards

- Supported GMPLS Standards on page 31
- Supported LDP Standards on page 32
- Supported MPLS Standards on page 33
- Supported RSVP Standards on page 35

### Supported GMPLS Standards

---

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for Generalized MPLS (GMPLS).

- RFC 3471, *Generalized Multi-Protocol [sic] Label Switching (GMPLS) Signaling Functional Description*

Only the following features are supported:

- Bidirectional LSPs (upstream label only)
  - Control channel separation
  - Generalized label (suggested label only)
  - Generalized label request (bandwidth encoding only)
- RFC 3473, *Generalized Multi-Protocol [sic] Label Switching (GMPLS) Signaling Resource ReserVation [sic] Protocol-Traffic Engineering (RSVP-TE) Extensions*

Only Section 9, "Fault Handling," is supported.

- RFC 4206, *Label Switched Paths (LSP) Hierarchy with Generalized Multi-Protocol [sic] Label Switching (GMPLS) Traffic Engineering (TE)*
- Internet draft draft-ietf-ccamp-gmpls-routing-09.txt, *Routing Extensions in Support of Generalized Multi-Protocol [sic] Label Switching*

Only interface switching is supported.

- Internet draft draft-ietf-ccamp-gmpls-rsvp-te-ason-02.txt, *Generalized MPLS (GMPLS) RSVP-TE Signalling in support of Automatically Switched Optical Network (ASON)* (expires January 2005)

- Internet draft draft-ietf-ccamp-gmpls-sonet-sdh-08.txt, *Generalized Multi-Protocol [sic] Label Switching Extensions for SONET and SDH Control*

Only S,U,K,L,M-format labels and SONET traffic parameters are supported.

- Internet draft draft-ietf-ccamp-lmp-10.txt, *Link Management Protocol (LMP)*
- Internet draft draft-ietf-ccamp-ospf-gmpls-extensions-12.txt, *OSPF Extensions in Support of Generalized Multi-Protocol [sic] Label Switching*

The following sub-TLV types for the Link type, link, value (TLV) are not supported:

- Link Local/Remote Identifiers (type 11)
- Link Protection Type (type 14)
- Shared Risk Link Group (SRLG) (type 16)

The features described in Section 2 of the draft, “Implications on Graceful Restart,” are also not supported.

The Interface Switching Capability Descriptor (type 15) sub-TLV type is implemented, but only for packet switching.

- Internet draft draft-ietf-mpls-bundle-04.txt, *Link Bundling in MPLS Traffic Engineering*

#### **Related Documentation**

- Supported LDP Standards on page 32
- Supported MPLS Standards on page 33
- Supported RSVP Standards on page 35
- Accessing Standards Documents on the Internet on page 3

---

## **Supported LDP Standards**

The Junos OS substantially supports the following RFCs, which define standards for LDP.

- RFC 3212, *Constraint-Based LSP Setup using LDP*
- RFC 3478, *Graceful Restart Mechanism for Label Distribution Protocol*

The following RFCs do not define standards, but provide information about LDP. The IETF classifies them as “Informational.”

- RFC 3215, *LDP State Machine*
- RFC 5036, *LDP Specification*

For the following features described in the indicated sections of the RFC, the Junos OS supports one of the possible modes but not the other:

- Label distribution control (section 2.6.1): Ordered mode is supported, but not Independent mode.
- Label retention (section 2.6.2): Liberal mode is supported, but not Conservative mode.

- Label advertisement (section 2.6.3): Downstream Unsolicited mode is supported, but not Downstream on Demand mode.
  - RFC 5443, *LDP IGP Synchronization*
- Related Documentation**
- Supported GMPLS Standards on page 31
  - Supported MPLS Standards on page 33
  - Supported RSVP Standards on page 35
  - Accessing Standards Documents on the Internet on page 3

## Supported MPLS Standards

---

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for MPLS and traffic engineering.

- RFC 2858, *Multiprotocol Extensions for BGP-4*
- RFC 3031, *Multiprotocol Label Switching Architecture*
- RFC 3032, *MPLS Label Stack Encoding*
- RFC 3140, *Per Hop Behavior Identification Codes*
- RFC 3270, *Multi-Protocol [sic] Label Switching (MPLS) Support of Differentiated Services*  
Only E-LSPs are supported.
- RFC 3443, *Time To Live (TTL) Processing in Multi-Protocol [sic] Label Switching (MPLS) Networks*
- RFC 3478, *Graceful Restart Mechanism for Label Distribution Protocol*
- RFC 4090, *Fast Reroute Extensions to RSVP-TE for LSP Tunnels*  
Node protection in facility backup is not supported.
- RFC 4124, *Protocol Extensions for Support of Diffserv-aware MPLS Traffic Engineering*
- RFC 4364, *BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4379, *Detecting Multi-Protocol [sic] Label Switched (MPLS) Data Plane Failures*  
The traceroute functionality is supported only on transit routers.
- RFC 4950, *ICMP Extensions for Multiprotocol Label Switching*
- Internet draft draft-ietf-bfd-mpls-02.txt, *BFD for MPLS LSPs*
- Internet draft draft-ietf-mpls-rsvp-te-p2mp-01.txt, *Extensions to RSVP-TE for Point to Multipoint TE LSPs* (expires June 2005)
- Internet draft draft-ietf-mpls-soft-preemption-02.txt, *MPLS Traffic Engineering Soft preemption*

The following RFCs and Internet drafts do not define standards, but provide information about MPLS, traffic engineering, and related technologies. The IETF classifies them variously as “Experimental,” “Historic,” or “Informational.”

- RFC 2547, *BGP/MPLS VPNs*
- RFC 2702, *Requirements for Traffic Engineering Over MPLS*
- RFC 3063, *MPLS Loop Prevention Mechanism*
- RFC 3208, *PGM Reliable Transport Protocol Specification*

Only the network element is supported.

- RFC 3469, *Framework for Multi-Protocol [sic] Label Switching (MPLS)-based Recovery*
- RFC 3564, *Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering*
- RFC 4125, *Maximum Allocation Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering*
- RFC 4127, *Russian Dolls Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering*
- Internet draft draft-martini-l2circuit-encap-mpls-11.txt, *Encapsulation Methods for Transport of Layer 2 Frames Over IP and MPLS Networks*

The Junos OS differs from the Internet draft in the following ways:

- A packet with a sequence number of 0 is treated as out of sequence.
- Any packet which does not have the next incremental sequence number is considered out of sequence.
- When out-of-sequence packets arrive, the expected sequence number for the neighbor is set to the sequence number in the Layer 2 circuit control word.
- Internet draft draft-martini-l2circuit-trans-mpls-19.txt, *Transport of Layer 2 Frames Over MPLS*
- Internet draft draft-raggarwa-mpls-p2mp-te-02.txt, *Establishing Point to Multipoint MPLS TE LSPs*

The features discussed in the indicated sections of the draft are not supported:

- Nonadjacent signaling for branch LSPs (section 7.1)
- Make-before-break and fast reroute (section 9)
- LSP hierarchy using point-to-point LSPs (section 10)

#### **Related Documentation**

- Supported GMPLS Standards on page 31
- Supported LDP Standards on page 32
- Supported RSVP Standards on page 35
- Accessing Standards Documents on the Internet on page 3

## Supported RSVP Standards

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for RSVP.

- RFC 2205, *Resource ReSerVation [sic] Protocol (RSVP)—Version 1 Functional Specification*
- RFC 2210, *The Use of RSVP with IETF Integrated Services*
- RFC 2211, *Specification of the Controlled-Load Network Element Service*
- RFC 2212, *Specification of Guaranteed Quality of Service*
- RFC 2215, *General Characterization Parameters for Integrated Service Network Elements*
- RFC 2745, *RSVP Diagnostic Messages*
- RFC 2747, *RSVP Cryptographic Authentication* (updated by RFC 3097)
- RFC 2961, *RSVP Refresh Overhead Reduction Extensions*
- RFC 3097, *RSVP Cryptographic Authentication—Updated Message Type Value*
- RFC 3209, *RSVP-TE: Extensions to RSVP for LSP Tunnels*

The Null Service Object for maximum transmission unit (MTU) signaling in RSVP is not supported.

- RFC 3473, *Generalized Multi-Protocol [sic] Label Switching (GMPLS) Signaling Resource ReserVation [sic] Protocol-Traffic Engineering (RSVP-TE) Extensions*

Only Section 9, “Fault Handling,” is supported.

- RFC 3477, *Signalling Unnumbered Links in Resource ReSerVation [sic] Protocol - Traffic Engineering (RSVP-TE)*
- RFC 4090, *Fast Reroute Extensions to RSVP-TE for LSP Tunnels*

Node protection in facility backup is not supported.

- RFC 4203, *OSPF Extensions in Support of Generalized Multi-Protocol [sic] Label Switching (GMPLS)*

(OSPF extensions can carry traffic engineering information over unnumbered links.)

- RFC 4558, *Node-ID Based Resource Reservation Protocol (RSVP) Hello: A Clarification Statement*
- RFC 4561, *Definition of a Record Route Object (RRO) Node-Id Sub-Object*

The RRO node ID subobject is for use in inter-AS link and node protection configurations.

- Internet draft draft-ietf-mpls-rsvp-te-p2mp-01.txt, *Extensions to RSVP-TE for Point to Multipoint TE LSPs* (expires June 2005)

The following RFCs do not define standards, but provide information about RSVP and related technologies. The IETF classifies them variously as “Experimental” or “Informational.”

- RFC 2209, *Resource ReSerVation [sic] Protocol (RSVP)—Version 1 Message Processing Rules*
- RFC 2216, *Network Element Service Specification Template*
- RFC 4125, *Maximum Allocation Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering*
- RFC 4127, *Russian Dolls Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering*

**Related  
Documentation**

- Supported GMPLS Standards on page 31
- Supported LDP Standards on page 32
- Supported MPLS Standards on page 33
- Accessing Standards Documents on the Internet on page 3

## CHAPTER 6

# Packet Processing Standards

- Supported CoS Standards on page 37
- Supported Packet Filtering Standards on page 38
- Supported Policing Standard on page 38

### Supported CoS Standards

---

The Junos OS substantially supports the following standards for class of service (CoS).

- IEEE Standard 802.1D, *IEEE Standard for Local and Metropolitan Area Networks: Media Access Control (MAC) Bridges*

This document discusses Quality of Service (QoS) at the MAC level, often referred to as 802.1p.

- RFC 2474, *Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers*
- RFC 2597, *Assured Forwarding PHB Group*
- RFC 2598, *An Expedited Forwarding PHB*

The following RFCs do not define standards, but provide information about CoS and related technologies. The IETF classifies them as “Informational.”

- RFC 2475, *An Architecture for Differentiated Services*
- RFC 2697, *A Single Rate Three Color Marker*
- RFC 2698, *A Two Rate Three Color Marker*
- RFC 2983, *Differentiated Services and Tunnels*
- RFC 3140, *Per Hop Behavior Identification Codes*
- RFC 3246, *An Expedited Forwarding PHB (Per-Hop Behavior)*
- RFC 3260, *New Terminology and Clarifications for Diffserv*

#### **Related Documentation**

- CoS Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported Packet Filtering Standards

---

The Junos OS provides a packet-filtering language that enables you to control the flow of packets being forwarded to a network destination, as well as packets destined for and sent by the router. It substantially supports the following RFCs, which define standards for packet filtering.

- RFC 792, *INTERNET CONTROL MESSAGE PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION*
- RFC 2460, *Internet Protocol, Version 6 (IPv6) Specification*
- RFC 2474, *Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers*
- RFC 2597, *Assured Forwarding PHB Group*
- RFC 2598, *An Expedited Forwarding PHB*
- RFC 3246, *An Expedited Forwarding PHB (Per-Hop Behavior)*
- RFC 4291, *IP Version 6 Addressing Architecture*
- RFC 4443, *Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification*

The following RFCs do not define standards, but provide information about packet filtering and related technologies. The IETF classifies them as “Informational.”

- RFC 2267, *Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing*
- RFC 2475, *An Architecture for Differentiated Services*
- RFC 2983, *Differentiated Services and Tunnels*
- RFC 3260, *New Terminology and Clarifications for Diffserv*

### Related Documentation

- Packet Filtering Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported Policing Standard

---

The Junos OS supports policing, or rate limiting, to limit the amount of traffic that passes through an interface. For information about rate limiting, see RFC 2698, *A Two Rate Three Color Marker*.

The Junos implementation of policing uses a token-bucket algorithm and supports the following features:

- Adaptive shaping for Frame Relay traffic
- Virtual channels

- Related Documentation**
- Accessing Standards Documents on the Internet on page 3



## CHAPTER 7

# Routing Protocol Standards

- Supported BGP Standards on page 41
- Supported ES-IS Standards on page 42
- Supported ICMP and Neighbor Discovery Standards on page 43
- Supported IP Multicast Protocol Standards on page 43
- Supported IPv4, TCP, and UDP Standards on page 45
- Supported IPv6 Standards on page 46
- Supported IS-IS Standards on page 49
- Supported OSPF and OSPFv3 Standards on page 50
- Supported RIP and RIPng Standards on page 51

### Supported BGP Standards

---

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for IP version 4 (IPv4) BGP.

For a list of supported IP version 6 (IPv6) BGP standards, see “Supported IPv6 Standards” on page 46.

Junos BGP supports authentication for protocol exchanges (MD5 authentication).

- RFC 1745, *BGP4/IDRP for IP—OSPF Interaction*
- RFC 1772, *Application of the Border Gateway Protocol in the Internet*
- RFC 1997, *BGP Communities Attribute*
- RFC 2283, *Multiprotocol Extensions for BGP-4*
- RFC 2385, *Protection of BGP Sessions via the TCP MD5 Signature Option*
- RFC 2439, *BGP Route Flap Damping*
- RFC 2545, *Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing*
- RFC 2796, *BGP Route Reflection – An Alternative to Full Mesh IBGP*
- RFC 2858, *Multiprotocol Extensions for BGP-4*
- RFC 2918, *Route Refresh Capability for BGP-4*

- RFC 3065, *Autonomous System Confederations for BGP*
- RFC 3107, *Carrying Label Information in BGP-4*
- RFC 3392, *Capabilities Advertisement with BGP-4*
- RFC 4271, *A Border Gateway Protocol 4 (BGP-4)*
- RFC 4360, *BGP Extended Communities Attribute*
- RFC 4364, *BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4456, *BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)*
- RFC 4659, *BGP/MPLS IP Virtual Private Network (VPN) Extension for IPv6 VPN*
- RFC 4724, *Graceful Restart Mechanism for BGP*
- RFC 4781, *Graceful Restart Mechanism for BGP with MPLS*
- RFC 4893, *BGP Support for Four-octet AS Number Space*
- Internet draft draft-ietf-idr-flow-spec-00.txt, *Dissemination of flow specification rules*
- Internet draft draft-ietf-idr-link-bandwidth-01.txt, *BGP Link Bandwidth Extended Community* (expires August 2010)
- Internet draft draft-kato-bgp-ipv6-link-local-00.txt, *BGP4+ Peering Using IPv6 Link-local Address*
- Internet draft draft-ooms-v6ops-bgp-tunnel-06.txt, *Connecting IPv6 Islands over IPv4 MPLS using IPv6 Provider Edge Routers (6PE)* (expires July 2006)

The following RFCs and Internet draft do not define standards, but provide information about BGP and related technologies. The IETF classifies them variously as “Experimental” or “Informational.”

- RFC 1965, *Autonomous System Confederations for BGP*
- RFC 1966, *BGP Route Reflection—An alternative to full mesh IBGP*
- RFC 2270, *Using a Dedicated AS for Sites Homed to a Single Provider*
- Internet draft draft-ietf-ngtrans-bgp-tunnel-04.txt, *Connecting IPv6 Islands across IPv4 Clouds with BGP* (expires July 2002)

**Related  
Documentation**

- Supported IPv6 Standards on page 46
- Accessing Standards Documents on the Internet on page 3

---

## Supported ES-IS Standards

The Junos OS substantially supports the following standards for End System-to-Intermediate System (ES-IS).

- International Organization for Standardization/International Electrotechnical Commission (ISO/IEC) standard 8473, *Information technology — Protocol for providing the connectionless-mode network service*

- ISO/IEC standard 9542, *Information processing systems — Telecommunications and information exchange between systems — End system to Intermediate system routing [sic] exchange protocol for use in conjunction with the Protocol for providing the connectionless-mode network service (ISO 8473)*

**Related  
Documentation**

- Supported IS-IS Standards on page 49
- IS-IS Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

---

## Supported ICMP and Neighbor Discovery Standards

The Junos OS substantially supports the following RFCs, which define standards for Internet Control Message Protocol (ICMP, for IP version 4 [IPv4]) and neighbor discovery (for IP version 6 [IPv6]).

- RFC 1256, *ICMP Router Discovery Messages*
- RFC 4861, *Neighbor Discovery for IP Version 6 (IPv6)*
- RFC 4862, *IPv6 Stateless Address Autoconfiguration*
- RFC 4443, *Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification*

**Related  
Documentation**

- Supported IPv4, TCP, and UDP Standards on page 45
- Supported IPv6 Standards on page 46
- Accessing Standards Documents on the Internet on page 3

---

## Supported IP Multicast Protocol Standards

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for IP multicast protocols, including Distance Vector Multicast Routing Protocol (DVMRP), Internet Group Management Protocol (IGMP), Multicast Listener Discovery (MLD), Multicast Source Discovery Protocol (MSDP), Pragmatic General Multicast (PGM), Protocol Independent Multicast (PIM), Session Announcement Protocol (SAP), and Session Description Protocol (SDP).

- RFC 1112, *Host Extensions for IP Multicasting* (defines IGMP Version 1)
- RFC 2236, *Internet Group Management Protocol, Version 2*
- RFC 2327, *SDP: Session Description Protocol*
- RFC 2710, *Multicast Listener Discovery (MLD) for IPv6*
- RFC 2858, *Multiprotocol Extensions for BGP-4*
- RFC 3031, *Multiprotocol Label Switching Architecture*
- RFC 3376, *Internet Group Management Protocol, Version 3*

- RFC 3590, *Source Address Selection for the Multicast Listener Discovery (MLD) Protocol*
- RFC 4601, *Protocol Independent Multicast – Sparse Mode (PIM-SM): Protocol Specification (Revised)*
- RFC 4607, *Source-Specific Multicast for IP*
- Internet draft draft-holbrook-idmr-igmpv3-ssm-07.txt, *Using IGMPv3 and MLDv2 for Source-Specific Multicast* (expires December 2004)
- Internet draft draft-ietf-l3vpn-2547bis-mcast-02.txt, *Multicast in MPLS/BGP IP VPNs*
- Internet draft draft-ietf-l3vpn-2547bis-mcast-bgp-03.txt, *BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs*
- Internet draft draft-ietf-pim-sm-bsr-05.txt, *Bootstrap Router (BSR) Mechanism for PIM*

The scoping mechanism is not supported.

- Internet draft draft-raggarwa-l3vpn-2547-mvpn-00.txt, *Base Specification for Multicast in BGP/MPLS VPNs* (expires December 2004)

The following RFCs and Internet drafts do not define standards, but provide information about multicast protocols and related technologies. The IETF classifies them variously as “Best Current Practice,” “Experimental,” or “Informational.”

- RFC 1075, *Distance Vector Multicast Routing Protocol*
- RFC 2362, *Protocol Independent Multicast-Sparse Mode (PIM-SM): Protocol Specification*
- RFC 2365, *Administratively Scoped IP Multicast*
- RFC 2547, *BGP/MPLS VPNs*
- RFC 2974, *Session Announcement Protocol*
- RFC 3208, *PGM Reliable Transport Protocol Specification*
- RFC 3446, *Anycast Rendezvous [sic] Point (RP) mechanism using Protocol Independent Multicast (PIM) and Multicast Source Discovery Protocol (MSDP)*
- RFC 3569, *An Overview of Source-Specific Multicast (SSM)*
- RFC 3618, *Multicast Source Discovery Protocol (MSDP)*
- RFC 3810, *Multicast Listener Discovery Version 2 (MLDv2) for IPv6*
- RFC 3973, *Protocol Independent Multicast – Dense Mode (PIM-DM): Protocol Specification (Revised)*
- RFC 4364, *BGP/MPLS IP Virtual Private Networks (VPNs)*
- Internet draft draft-ietf-idmr-dvmrp-v3-11.txt, *Distance Vector Multicast Routing Protocol*
- Internet draft draft-ietf-mboned-ssm232-08.txt, *Source-Specific Protocol Independent Multicast in 232/8*

- Internet draft draft-ietf-mmusic-sap-00.txt, *SAP: Session Announcement Protocol*
- Internet draft draft-rosen-vpn-mcast-07.txt, *Multicast in MPLS/BGP VPNs*

Only section 7, “Data MDT: Optimizing flooding,” is supported.

#### Related Documentation

- Accessing Standards Documents on the Internet on page 3

## Supported IPv4, TCP, and UDP Standards

The Junos OS substantially supports the following RFCs, which define standards for IP version 4 (IPv4), Transmission Control Protocol (TCP), and User Datagram Protocol (UDP).

- RFC 768, *User Datagram Protocol*
- RFC 791, *INTERNET PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION*
- RFC 792, *INTERNET CONTROL MESSAGE PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION*
- RFC 793, *TRANSMISSION CONTROL PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION*
- RFC 826, *Ethernet Address Resolution Protocol—or—Converting Network Protocol Addresses to 48.bit Ethernet Address for Transmission on Ethernet Hardware*
- RFC 854, *TELNET PROTOCOL SPECIFICATION*
- RFC 862, *Echo Protocol*
- RFC 863, *Discard Protocol*
- RFC 894, *A Standard for the Transmission of IP Datagrams over Ethernet Networks*
- RFC 896, *Congestion Control in IP/TCP Internetworks*
- RFC 903, *A Reverse Address Resolution Protocol*
- RFC 919, *BROADCASTING INTERNET DATAGRAMS*
- RFC 922, *BROADCASTING INTERNET DATAGRAMS IN THE PRESENCE OF SUBNETS*
- RFC 959, *FILE TRANSFER PROTOCOL (FTP)*
- RFC 1027, *Using ARP to Implement Transparent Subnet Gateways*
- RFC 1042, *A Standard for the Transmission of IP Datagrams over IEEE 802 Networks*
- RFC 1157, *A Simple Network Management Protocol (SNMP)*
- RFC 1166, *INTERNET NUMBERS*
- RFC 1195, *Use of OSI IS-IS for Routing in TCP/IP and Dual Environments*
- RFC 1256, *ICMP Router Discovery Messages*
- RFC 1305, *Network Time Protocol (Version 3) Specification, Implementation and Analysis*

- RFC 1519, *Classless Inter-Domain Routing (CIDR): an Address Assignment and Aggregation Strategy*
- RFC 1812, *Requirements for IP Version 4 Routers*
- RFC 2338, *Virtual Router Redundancy Protocol* (obsoleted by RFC 3768 in April 2004)
- RFC 2873, *TCP Processing of the IPv4 Precedence Field*
- RFC 3021, *Using 31-Bit Prefixes on IPv4 Point-to-Point Links*
- RFC 3246, *An Expedited Forwarding PHB (Per-Hop Behavior)*

The following RFCs do not define standards, but provide information about IP, TCP, UDP, and related technologies. The IETF classifies them as “Informational.”

- RFC 1878, *Variable Length Subnet Table For IPv4*
- RFC 1948, *Defending Against Sequence Number Attacks*

**Related  
Documentation**

- Supported IPv6 Standards on page 46
- Accessing Standards Documents on the Internet on page 3

---

## Supported IPv6 Standards

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for IP version 6 (IPv6).

- RFC 1157, *A Simple Network Management Protocol (SNMP)*
- RFC 1195, *Use of OSI IS-IS for Routing in TCP/IP and Dual Environments*
- RFC 1213, *Management Information Base for Network Management of TCP/IP-based internets: MIB-II*

Only the following features are supported:

- Junos-specific secured access list
- Master configuration keywords
- MIB II and its SNMP version 2 derivatives, including the following:
  - Interface management
  - IP (except for the **ipRouteTable** object, which has been replaced by **ipCidrRouteTable** [RFC 2096, *IP Forwarding Table MIB*])
  - SNMP management
  - Statistics counters
- Reconfigurations upon receipt of the SIGHUP signal
- SNMP version 1 **Get** and **GetNext** requests and version 2 **GetBulk** requests

- RFC 1215, *A Convention for Defining Traps for use with the SNMP*

Only MIB II SNMP version 1 traps and version 2 notifications are supported.

- RFC 1771, *A Border Gateway Protocol 4 (BGP-4)*
- RFC 1772, *Application of the Border Gateway Protocol in the Internet*
- RFC 1902, *Structure of Management Information for Version 2 of the Simple Network Management Protocol (SNMPv2)*
- RFC 1905, *Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)*
- RFC 1981, *Path MTU Discovery for IP version 6*
- RFC 2080, *RIPng for IPv6*
- RFC 2081, *RIPng Protocol Applicability Statement*
- RFC 2283, *Multiprotocol Extensions for BGP-4*
- RFC 2373, *IP Version 6 Addressing Architecture*
- RFC 2460, *Internet Protocol, Version 6 (IPv6) Specification*
- RFC 2464, *Transmission of IPv6 Packets over Ethernet Networks*
- RFC 2465, *Management Information Base for IP Version 6: Textual Conventions and General Group*

IP version 6 (IPv6) and Internet Control Message Protocol version 6 (ICMPv6) statistics are not supported.

- RFC 2472, *IP Version 6 over PPP*
  - RFC 2474, *Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers*
  - RFC 2491, *IPv6 Over Non-Broadcast Multiple Access (NBMA) networks*
  - RFC 2492, *IPv6 over ATM Networks*
  - RFC 2526, *Reserved IPv6 Subnet Anycast Addresses*
  - RFC 2545, *Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing*
  - RFC 2578, *Structure of Management Information Version 2 (SMIv2)*
  - RFC 2675, *IPv6 Jumbograms*
  - RFC 2711, *IPv6 Router Alert Option*
  - RFC 2740, *OSPF for IPv6*
  - RFC 2878, *PPP Bridging Control Protocol (BCP)*
  - RFC 2893, *Transition Mechanisms for IPv6 Hosts and Routers*
  - RFC 3315, *Dynamic Host Configuration Protocol for IPv6 (DHCPv6)*
- Address assignment is supported with IP version 4 (IPv4) but not IP version 6 (IPv6).
- RFC 3484, *Default Address Selection for Internet Protocol version 6 (IPv6)*

- RFC 3513, *Internet Protocol Version 6 (IPv6) Addressing Architecture*
- RFC 3515, *The Session Initiation Protocol (SIP) Refer Method*
- RFC 3768, *Virtual Router Redundancy Protocol (VRRP)*
- RFC 3810, *Multicast Listener Discovery Version 2 (MLDv2) for IPv6*
- RFC 4291, *IP Version 6 Addressing Architecture*
- RFC 4443, *Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification*
- RFC 4659, *BGP-MPLS IP Virtual Private Network (VPN) Extension for IPv6 VPN*
- RFC 4861, *Neighbor Discovery for IP Version 6 (IPv6)*
- RFC 4862, *IPv6 Stateless Address Autoconfiguration*
- RFC 5095, *Deprecation of Type 0 Routing Headers in IPv6*
- RFC 5308, *Routing IPv6 with IS-IS*
- Internet draft draft-ietf-idr-flow-spec-00.txt, *Dissemination of flow specification rules*
- Internet draft draft-ietf-softwire-dual-stack-lite-04.txt, *Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion*
- Internet draft draft-kato-bgp-ipv6-link-local-00.txt, *BGP4+ Peering Using IPv6 Link-local Address*
- Internet draft draft-ooms-v6ops-bgp-tunnel-06.txt, *Connecting IPv6 Islands over IPv4 MPLS using IPv6 Provider Edge Routers (6PE)* (expires July 2006)

Only MP-BGP over IPv4 approach is supported.

The following RFCs and Internet draft do not define standards, but provide information about IPv6 and related technologies. The IETF classifies them variously as “Experimental” or “Informational.”

- RFC 1901, *Introduction to Community-based SNMPv2*
- RFC 2767, *Dual Stack Hosts using the "Bump-In-the-Stack" Technique (BIS)*
- RFC 3587, *IPv6 Global Unicast Address Format*
- Internet draft-ietf-ngtrans-bgp-tunnel-04.txt, *Connecting IPv6 Islands across IPv4 Clouds with BGP*

Only MP-BGP over IP version 4 (IPv4) approach is supported.

**Related  
Documentation**

- Supported IPv4, TCP, and UDP Standards on page 45
- Accessing Standards Documents on the Internet on page 3

## Supported IS-IS Standards

The Junos OS substantially supports the following standards for IS-IS.

- International Organization for Standardization/International Electrotechnical Commission (ISO/IEC) 8473, *Information technology — Protocol for providing the connectionless-mode network service*
- ISO/IEC 10589, *Information technology — Telecommunications and information exchange between systems — Intermediate System to Intermediate System intra-domain routing [sic] information exchange protocol for use in conjunction with the protocol for providing the connectionless-mode network service (ISO 8473)*
- RFC 1195, *Use of OSI IS-IS for Routing in TCP/IP and Dual Environments*
- RFC 5120, *M-ISIS: Multi Topology (MT) Routing in Intermediate System to Intermediate Systems (IS-ISs)*
- RFC 5130, *A Policy Control Mechanism in IS-IS Using Administrative Tags*
- RFC 5286, *Basic Specification for IP Fast Reroute: Loop-Free Alternates*
- RFC 5301, *Dynamic Hostname Exchange Mechanism for IS-IS*
- RFC 5302, *Domain-wide Prefix Distribution with Two-Level IS-IS*
- RFC 5303, *Three-Way Handshake for IS-IS Point-to-Point Adjacencies*
- RFC 5304, *IS-IS Cryptographic Authentication*
- RFC 5305, *IS-IS Extensions for Traffic Engineering*
- RFC 5306, *Restart Signaling for IS-IS*
- RFC 5307, *IS-IS Extensions in Support of Generalized Multi-Protocol [sic] Label Switching (GMPLS)*
- RFC 5308, *Routing IPv6 with IS-IS*
- Internet draft draft-ietf-bfd-base-09.txt, *Bidirectional Forwarding Detection*

Transmission of echo packets is not supported.

The following RFCs do not define standards, but provide information about IS-IS and related technologies. The IETF classifies them as “Informational.”

- RFC 2973, *IS-IS Mesh Groups*
- RFC 3358, *Optional Checksums in Intermediate System to Intermediate System (ISIS) [sic]*
- RFC 3359, *Reserved Type, Length and Value (TLV) Codepoints in Intermediate System to Intermediate System*
- RFC 3373, *Three-Way Handshake for Intermediate System to Intermediate System (IS-IS) Point-to-Point Adjacencies*
- RFC 3567, *Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication*

- RFC 3787, *Recommendations for Interoperable IP Networks using Intermediate System to Intermediate System (IS-IS)*
- RFC 5309, *Point-to-Point Operation over LAN in Link State Routing Protocols*
- Internet draft draft-ietf-isis-wg-255adj-02.txt, *Maintaining more than 255 circuits in IS-IS*

**Related  
Documentation**

- IS-IS Features in the Junos OS
- Supported ES-IS Standards on page 42
- Accessing Standards Documents on the Internet on page 3

---

## Supported OSPF and OSPFv3 Standards

The Junos OS substantially supports the following RFCs and Internet drafts, which define standards for OSPF and OSPF version 3 (OSPFv3).

- RFC 1583, *OSPF Version 2*
  - RFC 1793, *Extending OSPF to Support Demand Circuits*
  - RFC 2328, *OSPF Version 2*
  - RFC 2370, *The OSPF Opaque LSA Option*
- Support is provided by the **update-threshold** configuration statement at the **[edit protocols rsvp interface *interface-name* ]** hierarchy level.
- RFC 2740, *OSPF for IPv6*
  - RFC 3101, *The OSPF Not-So-Stubby Area (NSSA) Option*
  - RFC 3623, *Graceful OSPF Restart*
  - RFC 3630, *Traffic Engineering (TE) Extensions to OSPF Version 2*
  - RFC 4203, *OSPF Extensions in Support of Generalized Multi-Protocol [sic] Label Switching (GMPLS)*

Only interface switching is supported.

- RFC 4552, *Authentication/Confidentiality for OSPFv3*
- RFC 4576, *Using a Link State Advertisement (LSA) Options Bit to Prevent Looping in BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4577, *OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4915, *Multi-Topology (MT) Routing in OSPF*
- RFC 5185, *OSPF Multi-Area Adjacency*
- RFC 5286, *Basic Specification for IP Fast Reroute: Loop-Free Alternates*
- Internet draft draft-ietf-ospf-af-alt-10.txt, *Support of address families in OSPFv3*
- Internet draft draft-katz-ward-bfd-02.txt, *Bidirectional Forwarding Detection*

Transmission of echo packets is not supported.

The following RFCs and Internet drafts do not define standards, but provide information about OSPF and related technologies. The IETF classifies them as “Informational.”

- RFC 3137, *OSPF Stub Router Advertisement*
- RFC 3509, *Alternative Implementations of OSPF Area Border Routers*
- RFC 5309, *Point-to-Point Operation over LAN in Link State Routing Protocols*

**Related  
Documentation**

- Supported IPv6 Standards on page 46
- OSPF Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

---

## Supported RIP and RIPng Standards

The Junos OS substantially supports the following RFCs, which define standards for RIP (for IP version 4 [IPv4]) and RIP next generation (RIPng, for IP version 6 [IPv6]).

The Junos OS supports authentication for all RIP protocol exchanges (MD5 or simple authentication).

- RFC 1058, *Routing Information Protocol*
- RFC 2080, *RIPng for IPv6*
- RFC 2082, *RIP-2 MD5 Authentication*

Multiple keys using distinct key IDs are not supported.

- RFC 2453, *RIP Version 2*

The following RFC does not define a standard, but provides information about RIPng. The IETF classifies it as “Informational.”

- RFC 2081, *RIPng Protocol Applicability Statement*

**Related  
Documentation**

- Supported IPv4, TCP, and UDP Standards on page 45
- Supported IPv6 Standards on page 46
- Accessing Standards Documents on the Internet on page 3



## CHAPTER 8

# Services PIC and DPC Standards

- Supported DTCP Standard on page 53
- Supported Flow Monitoring and Discard Accounting Standards on page 53
- Supported IPsec and IKE Standards on page 54
- Supported L2TP Standards on page 55
- Supported Link Services Standards on page 55
- Supported NAT and SIP Standards on page 55
- Supported RPM Standard on page 56
- Supported Voice Services Standards on page 56

### Supported DTCP Standard

---

The Junos OS substantially supports Internet draft draft-cavuto-dtcp-03.txt, *DTCP: Dynamic Tasking Control Protocol*.

#### Related Documentation

- Accessing Standards Documents on the Internet on page 3

### Supported Flow Monitoring and Discard Accounting Standards

---

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions), Monitoring Services PICs, or Multiservices PICs or DPCs, the Junos OS substantially supports the standards for cflowd version 5 and version 8 formats that are maintained by CAIDA and accessible at <http://www.caida.org>.

The following RFC does not define a standard, but provides information about flow monitoring. The IETF classifies it as “Informational.”

- RFC 3954, *Cisco Systems NetFlow Services Export Version 9*

#### Related Documentation

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported IPsec and IKE Standards

---

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Canada and U.S. version of the Junos OS substantially supports the following RFCs, which define standards for IP Security (IPsec) and Internet Key Exchange (IKE).

- RFC 2085, *HMAC-MD5 IP Authentication with Replay Prevention*
- RFC 2401, *Security Architecture for the Internet Protocol*
- RFC 2402, *IP Authentication Header*

This RFC is not supported on the ES PIC.

- RFC 2403, *The Use of HMAC-MD5-96 within ESP and AH*
- RFC 2404, *The Use of HMAC-SHA-1-96 within ESP and AH*
- RFC 2405, *The ESP DES-CBC Cipher Algorithm With Explicit IV*
- RFC 2406, *IP Encapsulating Security Payload (ESP)*
- RFC 2407, *The Internet IP Security Domain of Interpretation for ISAKMP*
- RFC 2408, *Internet Security Association and Key Management Protocol (ISAKMP)*
- RFC 2409, *The Internet Key Exchange (IKE)*
- RFC 2410, *The NULL Encryption Algorithm and Its Use With IPsec*
- RFC 3602, *The AES-CBC Cipher Algorithm and Its Use with IPsec*
- RFC 3948, *UDP Encapsulation of IPsec ESP Packets*
- RFC 4301, *Security Architecture for the Internet Protocol*
- RFC 4302, *IP Authentication Header*

This RFC is not supported on the ES PIC.

- RFC 4303, *IP Encapsulating Security Payload (ESP)*

The following RFCs and Internet draft do not define standards, but provide information about IPsec, IKE, and related technologies. The IETF classifies them as "Informational."

- RFC 2104, *HMAC: Keyed-Hashing for Message Authentication*
- RFC 2412, *The OAKLEY Key Determination Protocol*
- RFC 3706, *A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers*
- Internet draft draft-eastlake-sha2-02.txt, *US Secure Hash Algorithms (SHA and HMAC-SHA)* (expires July 2006)

### Related Documentation

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported L2TP Standards

---

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Junos OS substantially supports the following RFC, which defines the standard for Layer 2 Tunneling Protocol (L2TP).

- RFC 2661, *Layer Two Tunneling Protocol "L2TP"*

The following RFC does not define a standard, but provides information about technology related to L2TP. The IETF classifies it as "Informational."

- RFC 2866, *RADIUS Accounting*

### **Related Documentation**

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported Link Services Standards

---

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Junos OS substantially supports the following RFCs, which define standards for link services.

- RFC 1990, *The PPP Multilink Protocol (MP)*
- RFC 2364, *PPP Over AAL5*
- RFC 2686, *The Multi-Class Extension to Multi-Link PPP*

The following features are not supported:

- Negotiation of address field compression and protocol field compression PPP NCP options; instead, a full 4-byte PPP header is always sent
- Prefix elision

### **Related Documentation**

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported NAT and SIP Standards

---

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Junos OS substantially supports the following Network Address Translation (NAT) and Session Initiation Protocol (SIP) standards. NAT supports SIP dialogs and UDP/IP version 4 (IPv4) transport of SIP messages.

The Junos OS substantially supports the following RFC and Internet draft.

- RFC 3261, *SIP: Session Initiation Protocol*

- Internet draft draft-mrw-behave-nat66-01.txt, *IPv6-to-IPv6 Network Address Translation (NAT66)*

The following RFCs do not define standards, but provide information about NAT. The IETF classifies them variously as “Best Current Practice,” “Historic” or “Informational.”

- RFC 1631, *The IP Network Address Translator (NAT)*
- RFC 2663, *IP Network Address Translator (NAT) Terminology and Considerations*
- RFC 2766, *Network Address Translation - Protocol Translation (NAT-PT)*
- RFC 2993, *Architectural Implications of NAT*
- RFC 3022, *Traditional IP Network Address Translator (Traditional NAT)*
- RFC 4787, *Network Address Translation (NAT) Behavioral Requirements for Unicast UDP*
- RFC 5382, *NAT Behavioral Requirements for TCP*
- RFC 5508, *NAT Behavioral Requirements for ICMP*

**Related  
Documentation**

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

---

## Supported RPM Standard

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Junos OS substantially supports real-time performance monitoring (RPM), and provides MIB support with extensions in substantial support of RFC 2925, *Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations*.

**Related  
Documentation**

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

---

## Supported Voice Services Standards

On routers equipped with one or more Adaptive Services PICs (both standalone and integrated versions) or Multiservices PICs or DPCs, the Junos OS substantially supports the following following RFCs, which define standards for technologies used with voice services.

- RFC 2508, *Compressing IP/UDP/RTP Headers for Low-Speed Serial Links*
- RFC 2509, *IP Header Compression over PPP*

**Related  
Documentation**

- Services PIC and DPC Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## CHAPTER 9

# VPLS and VPN Standards

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 VPN Standard on page 57
- Supported Layer 3 VPN Standards on page 58
- Supported Multicast VPN Standards on page 59
- Supported VPLS Standards on page 59

### Supported Carrier-of-Carriers and Interprovider VPN Standards

---

The Junos OS substantially supports the following RFCs and Internet draft, which define standards for carrier-of-carriers and interprovider virtual private networks (VPNs).

- RFC 3107, *Carrying Label Information in BGP-4*
- RFC 4364, *BGP/MPLS IP Virtual Private Networks (VPNs)*
- Internet draft draft-marques-ppvnp-ibgp-00.txt, *RFC2547bis networks using internal BGP as PE-CE protocol*

#### Related Documentation

- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 2 VPN Standard on page 29
- Supported Layer 3 VPN Standards on page 58
- Supported Multicast VPN Standards on page 59
- Supported VPLS Standards on page 59
- Supported BGP Standards on page 41
- Accessing Standards Documents on the Internet on page 3

### Supported Layer 2 VPN Standard

---

The Junos OS substantially supports Internet draft draft-kompella-ppvnp-l2vpn-03.txt, *Layer 2 VPNs Over Tunnels*.

#### Related Documentation

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 Circuit Standards on page 28

- Supported Layer 3 VPN Standards on page 58
- Supported Multicast VPN Standards on page 59
- Supported VPLS Standards on page 59
- Accessing Standards Documents on the Internet on page 3

---

## Supported Layer 3 VPN Standards

The Junos OS substantially supports the following RFCs, which define standards for Layer 3 virtual private networks (VPNs).

- RFC 2283, *Multiprotocol Extensions for BGP-4*
- RFC 2685, *Virtual Private Networks Identifier*
- RFC 2858, *Multiprotocol Extensions for BGP-4*
- RFC 4364, *BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4379, *Detecting Multi-Protocol [sic] Label Switched (MPLS) Data Plane Failures*

The traceroute functionality is supported only on transit routers.

- RFC 4576, *Using a Link State Advertisement (LSA) Options Bit to Prevent Looping in BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4577, *OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)*
- RFC 4659, *BGP-MPLS IP Virtual Private Network (VPN) Extension for IPv6 VPN*
- RFC 4684, *Constrained Route Distribution for Border Gateway Protocol/MultiProtocol [sic] Label Switching (BGP/MPLS) Internet Protocol (IP) Virtual Private Networks (VPNs)*

The following RFC does not define a standard, but provides information about technology related to Layer 3 VPNs. The IETF classifies it as a “Best Current Practice.”

- RFC 1918, *Address Allocation for Private Internets*

### Related Documentation

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 2 VPN Standard on page 29
- Supported Multicast VPN Standards on page 59
- Supported VPLS Standards on page 59
- Supported MPLS Standards on page 33
- Supported BGP Standards on page 41
- OSPF Features in the Junos OS
- Accessing Standards Documents on the Internet on page 3

## Supported Multicast VPN Standards

---

The Junos OS substantially supports the following Internet drafts, which define standards for multicast virtual private networks (VPNs).

- Internet draft draft-ietf-l3vpn-2547bis-mcast-02.txt, *Multicast in MPLS/BGP IP VPNs*
- Internet draft draft-ietf-l3vpn-2547bis-mcast-bgp-03.txt, *BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs*

### Related Documentation

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 2 VPN Standard on page 29
- Supported Layer 3 VPN Standards on page 58
- Supported VPLS Standards on page 59
- Supported MPLS Standards on page 33
- Supported BGP Standards on page 41
- Accessing Standards Documents on the Internet on page 3

## Supported VPLS Standards

---

The Junos OS substantially supports the following following RFCs, which define standards for virtual private LAN service (VPLS).

- RFC 4761, *Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling*
- RFC 4762, *Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling*

FEC 128, FEC 129, control bit 0, and Ethernet pseudowire type hexadecimal 0x0005 are supported.

### Related Documentation

- Supported Carrier-of-Carriers and Interprovider VPN Standards on page 57
- Supported Layer 2 Circuit Standards on page 28
- Supported Layer 2 VPN Standard on page 29
- Supported Layer 3 VPN Standards on page 58
- Supported Multicast VPN Standards on page 59
- Accessing Standards Documents on the Internet on page 3



## PART 3

# Index

- Index on page 63
- Index of Supported Software Standards on page 67



# Index

## A

ANSI standards supported See Index of Supported Software Standards

ATM interfaces  
supported software standards.....21

## B

BGP  
supported software standards.....41

BOOTP  
supported software standards.....7

## C

CoS  
supported software standards.....37

## D

DHCP  
supported software standards.....7

discard accounting  
supported software standards.....53

DTCP  
supported software standards.....53

DVMRP  
supported software standards.....43

## E

ES-IS  
supported software standards.....42

ESO Consortium standards supported See Index of Supported Software Standards

Ethernet interfaces  
supported software standards.....22

## F

flow monitoring  
supported software standards.....53

Frame Relay interfaces  
supported software standards.....22

FRF (Broadband Forum) standards supported See Index of Supported Software Standards

## G

GMPLS  
supported software standards.....31

GR (Generic Requirements) standards supported  
See Index of Supported Software Standards

GRE interfaces  
supported software standards.....23

## I

IANA standards supported See Index of Supported Software Standards

ICMP  
supported software standards.....43

IEEE standards supported See Index of Supported Software Standards

IGMP  
supported software standards.....43

IKE  
supported software standards.....54

INCITS standards supported See Index of Supported Software Standards

Internet drafts supported See Index of Supported Software Standards

IP multicast  
supported software standards.....43

IP-IP interfaces  
supported software standards.....23

IPsec  
supported software standards.....54

IPv4  
supported software standards.....45

IPv6  
supported software standards.....46

IS-IS  
supported software standards.....49

ISO/IEC standards supported See Index of Supported Software Standards

ITU–T Recommendations supported See Index of  
Supported Software Standards

## L

L2TP  
    supported software standards.....28, 55  
Layer 2 circuits  
    supported software standards.....28  
Layer 2 networking  
    supported software standards.....27  
LDP  
    supported software standards.....32  
link services  
    supported software standards.....55

## M

MLD  
    supported software standards.....43  
Mobile IP  
    supported software standards.....8  
MPLS  
    supported software standards.....33  
MSDP  
    supported software standards.....43

## N

NAT  
    supported software standards.....55  
neighbor discovery  
    supported software standards.....43  
network management  
    supported software standards.....9  
NTP  
    supported software standards.....20

## O

OSPF  
    supported software standards.....50  
OSPFv3  
    supported software standards.....50

## P

packet filtering  
    supported software standards.....38  
PGM  
    supported software standards.....43  
PIM  
    supported software standards.....43

PPP interfaces  
    supported software standards.....24

## R

RADIUS  
    supported software standards.....18  
RFCs supported See Index of Supported Software  
Standards  
RIP  
    supported software standards.....51  
RIPng  
    supported software standards.....51  
RPM  
    supported software standards.....56  
RSVP  
    supported software standards.....35

## S

SAP  
    supported software standards.....43  
SDH  
    supported software standards.....24  
SDP  
    supported software standards.....43  
serial interfaces  
    supported software standards.....25  
SIP  
    supported software standard.....55  
SONET  
    supported software standards.....24  
system access and access management  
    supported software standards.....19

## T

T3 interfaces  
    supported software standards.....26  
TACACS+  
    supported software standards.....18  
TCP  
    supported software standards.....45  
time synchronization  
    supported software standards.....20

## U

UDP  
    supported software standards.....45

---

## V

### voice services

supported software standards.....56

### VPLS

supported software standards.....59

### VPNs

#### carrier-of-carriers

supported software standards.....57

#### interprovider

supported software standards.....57

#### Layer 2

supported software standards.....29, 57

#### Layer 3

supported software standards.....58

#### multicast

supported software standards.....59



# Index of Supported Software Standards

## A

ANSI T1.105-2001, Synchronous Optical Network (SONET) – Basic Description including Multiplex Structure, Rates, and Formats.....	24
ANSI T1.105.02-2001, Synchronous Optical Network (SONET) – Payload Mappings.....	24
ANSI T1.105.06-2002, Synchronous Optical Network (SONET): Physical Layer Specifications.....	24
ANSI T1.617-1991, Annex D, Additional Procedures for Permanent Virtual Connections (PVCs) Using Unnumbered Information Frames.....	22

## E

ESO Consortium MIB.....	9
-------------------------	---

## F

FRF.12, Frame Relay Fragmentation Implementation Agreement.....	22
FRF.15, End-to-End Multilink Frame Relay Implementation Agreement.....	23
FRF.16.1, Multilink Frame Relay UNI/NNI Implementation Agreement.....	23

## G

GR-253-CORE, Synchronous Optical Network (SONET) Transport Systems: Common Generic Criteria.....	25
GR-499-CORE, Transport Systems Generic Requirements (TSGR): Common Requirements.....	25

## I

IANA, IANAiftype Textual Convention MIB.....	9
IEEE 802.1ab, Station and Media Access Control Connectivity Discovery.....	27
IEEE 802.1ag, Virtual Bridged Local Area Networks, Amendment 5: Connectivity Fault Management.....	22
IEEE 802.1ah, Virtual Bridged Local Area Networks, Amendment 7: Provider Backbone Bridges.....	22
IEEE 802.1D, Media Access Control (MAC) Bridges.....	27, 37
IEEE 802.1Q, Virtual Bridged Local Area Networks.....	22
IEEE 802.1Qaz, Enhanced Transmission Selection.....	22
IEEE 802.1Qbb, Priority-based Flow Control.....	22
IEEE 802.3, Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications.....	22
IEEE 802.3ad, Aggregation of Multiple Link Segments.....	9, 22
IEEE 802.3ah, Operations, Administration, and Maintenance (OAM).....	22
INCITS T11, Fibre Channel Interfaces.....	22
Internet draft draft-blumenthal-aes-usm-08.txt, The AES Cipher Algorithm in the SNMP User-based Security Model See RFC 3826	
Internet draft draft-cavuto-dtcp-03.txt, DTCP: Dynamic Tasking Control Protocol.....	53
Internet draft draft-eastlake-sha2-02.txt, US Secure Hash Algorithms (SHA and HMAC-SHA).....	54
Internet draft draft-holbrook-idmr-igmpv3-ssm-07.txt, Using IGMPv3 and MLDv2 for Source-Specific Multicast.....	44

Internet draft draft-ietf-atommib-sonetaps-mib-10.txt, Definitions of Managed Objects for SONET Linear APS architectures See RFC 3498	
Internet draft draft-ietf-bfd-base-09.txt, Bidirectional Forwarding Detection.....	49
Internet draft draft-ietf-bfd-mib-02.txt, Bidirectional Forwarding Detection Management Information Base.....	17
Internet draft draft-ietf-bfd-mpls-02.txt, BFD for MPLS LSPs.....	33
Internet draft draft-ietf-ccamp-gmpls-routing-09.txt, Routing Extensions in Support of Generalized Multi-Protocol Label Switching.....	31
Internet draft draft-ietf-ccamp-gmpls-rsvp-te-ason-02.txt, Generalized MPLS (GMPLS) RSVP-TE Signalling in support of Automatically Switched Optical Network (ASON).....	31
Internet draft draft-ietf-ccamp-gmpls-sonet-sdh-08.txt, Generalized Multi-Protocol Label Switching Extensions for SONET and SDH Control.....	32
Internet draft draft-ietf-ccamp-lmp-10.txt, Link Management Protocol (LMP).....	32
Internet draft draft-ietf-ccamp-ospf-gmpls-extensions-12.txt, OSPF Extensions in Support of Generalized Multi-Protocol Label Switching.....	32, 50 See RFC 4203
Internet draft draft-ietf-dhc-dhcpv6-16.txt, Dynamic Host Configuration Protocol for IPv6 (DHCPv6) See RFC 3315	
Internet draft draft-ietf-idmr-dvmrp-v3-11.txt, Distance Vector Multicast Routing Protocol.....	44
Internet draft draft-ietf-idr-bgp4-cap-neg-01.txt, Capabilities Negotiation with BGP-4 See RFC 3392	
Internet draft draft-ietf-idr-bgp4-mibv2-04.txt, Definitions of Managed Objects for the Fourth Version of Border Gateway Protocol (BGP-4), Second Version.....	17
Internet draft draft-ietf-idr-flow-spec-00.txt, Dissemination of flow specification rules.....	42, 48
Internet draft draft-ietf-idr-link-bandwidth-01.txt, BGP Link Bandwidth Extended Community.....	42
Internet draft draft-ietf-idr-restart-10.txt, Traffic Engineering Extensions to OSPF Version 2draft-ietf-idr-restart-10.txt See RFC 4724	
Internet draft draft-ietf-isis-admin-tags-03.txt, A Policy Control Mechanism in IS-IS Using Administrative Tags See RFC 5130	
Internet draft draft-ietf-isis-igp-p2p-over-lan-06.txt, Point-to-point operation over LAN in link-state routing protocols See RFC 5309	
Internet draft draft-ietf-isis-ipv6-06.txt, Routing IPv6 with IS-IS See RFC 5308	
Internet draft draft-ietf-isis-wg-255adj-02.txt, Maintaining more than 255 circuits in IS-IS.....	50
Internet draft draft-ietf-isis-wg-mib-07.txt, Management Information Base for IS-IS.....	17
Internet draft draft-ietf-isis-wg-multi-topology-11.txt, M-ISIS: Multi Topology (MT) Routing in IS-IS See RFC 5120	
Internet draft draft-ietf-l2vpn-vpls-bgp-08.txt, Virtual Private LAN Service (VPLS) Using BGP for Auto-discovery and Signaling See RFC 4761	
Internet draft draft-ietf-l3vpn-2547bis-mcast-02.txt, Multicast in MPLS/BGP IP VPNs.....	44, 59
Internet draft draft-ietf-l3vpn-2547bis-mcast-bgp-03.txt, BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs.....	44, 59
Internet draft draft-ietf-l3vpn-bgp-ipv6-07.txt, BGP-MPLS VPN extension for IPv6 VPN See RFC 4659	
Internet draft draft-ietf-l3vpn-rfc2547bis-03.txt, BGP/MPLS IP VPNs See RFC 4364	
Internet draft draft-ietf-mboned-ssm232-08.txt, Source-Specific Protocol Independent Multicast in 232/8.....	44
Internet draft draft-ietf-mmusic-sap-00.txt, SAP: Session Announcement Protocol.....	45
Internet draft draft-ietf-mpls-bgp-mpls-restart-03.txt, Graceful Restart Mechanism for BGP with MPLS See RFC 4781	
Internet draft draft-ietf-mpls-bundle-04.txt, Link Bundling in MPLS Traffic Engineering.....	32
Internet draft draft-ietf-mpls-icmp-01.txt, ICMP Extensions for MultiProtocol Label Switching See RFC 4950	
Internet draft draft-ietf-mpls-label-encaps-07.txt, MPLS Label Stack Encoding See RFC 3032	
Internet draft draft-ietf-mpls-ldp-igp-sync-04.txt, LDP IGP Synchronization See RFC 5443	

Internet draft draft-ietf-mpls-rsvp-lsp-fastreroute-03.txt, Fast Reroute Extensions to RSVP-TE for LSP Tunnels See RFC 4090	
Internet draft draft-ietf-mpls-rsvp-te-p2mp-01.txt, Extensions to RSVP-TE for Point to Multipoint TE LSPs.....	33, 35
Internet draft draft-ietf-mpls-soft-preemption-02.txt, MPLS Traffic Engineering Soft preemption.....	33
Internet draft draft-ietf-msdp-mib-08.txt, Multicast Source Discovery protocol MIB.....	17
Internet draft draft-ietf-ngtrans-bgp-tunnel-04.txt, Connecting IPv6 Islands across IPv4 Clouds with BGP....	42, 48
Internet draft draft-ietf-ospf-af-alt-10.txt, Support of address families in OSPFv3.....	50
Internet draft draft-ietf-ospf-ospfv3-mib-11.txt, Management Information Base for OSPFv3.....	18
Internet draft draft-ietf-pim-sm-bsr-05.txt, Bootstrap Router (BSR) Mechanism for PIM.....	44
Internet draft draft-ietf-software-dual-stack-lite-04.txt, Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion.....	48
Internet draft draft-ietf-ssm-arch-06.txt, Source-Specific Multicast for IP See RFC 4607	
Internet draft draft-kato-bgp-ipv6-link-local-00.txt, BGP4+ Peering Using IPv6 Link-local Address.....	42, 48
Internet draft draft-katz-ward-bfd-02.txt, Bidirectional Forwarding Detection.....	50
Internet draft draft-katz-yeung-ospf-traffic-01.txt, Traffic Engineering Extensions to OSPF Version 2 See RFC 3630	
Internet draft draft-kompella-ppvpn-l2vpn-03.txt, Layer 2 VPNs Over Tunnels.....	29, 57
Internet draft draft-marques-ppvpn-ibgp-00.txt, RFC2547bis networks using internal BGP as PE-CE protocol.....	57
Internet draft draft-marques-ppvpn-rt-constrain-01.txt, Constrained VPN route distribution See RFC 4684	
Internet draft draft-martini-frame-encap-mpls-01.txt, Frame Relay Encapsulation over Pseudo-Wires.....	23
Internet draft draft-martini-l2circuit-encap-mpls-11.txt, Encapsulation Methods for Transport of Layer 2 Frames Over IP and MPLS Networks.....	28, 34
Internet draft draft-martini-l2circuit-trans-mpls-19.txt, Transport of Layer 2 Frames Over MPLS.....	28, 34
Internet draft draft-ooms-v6ops-bgp-tunnel-06.txt, Connecting IPv6 Islands over IPv4 MPLS using IPv6 Provider Edge Routers (6PE).....	42, 48
Internet draft draft-raggarwa-l3vpn-2547-mvpn-00.txt, Base Specification for Multicast in BGP/MPLS VPNs.....	44
Internet draft draft-raggarwa-mpls-p2mp-te-02.txt, Establishing Point to Multipoint MPLS TE LSPs.....	34
Internet draft draft-reeder-snmpv3-usm-3desede-00.txt, Extension to the User-Based Security Model (USM) to Support Triple-DES EDE in "Outside" CBC Mode.....	18
Internet draft draft-rosen-vpn-mcast-07.txt, Multicast in MPLS/BGP VPNs.....	45
Internet draft draft-mrw-behave-nat66-01.txt, IPv6-to-IPv6 Network Address Translation (NAT66).....	56
ISO/IEC 10589, Information technology — Telecommunications and information exchange between systems — Intermediate System to Intermediate System intra-domain routeing information exchange protocol for use in conjunction with the protocol for providing the connectionless-mode network service (ISO 8473).....	49
ISO/IEC 8473, Information technology — Protocol for providing the connectionless-mode network service.....	42, 49
ISO/IEC 9542, Information processing systems — Telecommunications and information exchange between systems — End system to Intermediate system routeing exchange protocol for use in conjunction with the Protocol for providing the connectionless-mode network service (ISO 8473).....	43
ITU-T Recommendation G.691, Optical interfaces for single channel STM-64 and other SDH systems with optical amplifiers.....	25
ITU-T Recommendation G.703, Physical/electrical characteristics of hierarchical digital interfaces.....	26
ITU-T Recommendation G.707, Network node interface for the synchronous digital hierarchy (SDH).....	25
ITU-T Recommendation G.783, Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks.....	25
ITU-T Recommendation G.813, Timing characteristics of SDH equipment slave clocks (SEC).....	25
ITU-T Recommendation G.825, The control of jitter and wander within digital networks which are based on the synchronous digital hierarchy (SDH).....	25

ITU–T Recommendation G.826, Error performance parameters and objectives for international, constant bit-rate digital paths at or above the primary rate.....	25
ITU–T Recommendation G.831, Management capabilities of transport networks based on the synchronous digital hierarchy (SDH).....	25
ITU–T Recommendation G.957, Optical interfaces for equipments and systems relating to the synchronous digital hierarchy.....	25
ITU–T Recommendation G.958, Digital line systems based on the synchronous digital hierarchy for use on optical fibre cables.....	25
ITU–T Recommendation I.432, B-ISDN user-network interface – Physical layer specification.....	25
ITU–T Recommendation I.432.3, B-ISDN user-network interface - Physical layer specification: 1544 kbit/s and 2048 kbit/s operation.....	21
ITU–T Recommendation Q.933a: Additional procedures for Permanent Virtual Connection (PVC) status management (using Unnumbered Information frames).....	23
ITU–T Recommendation V.35, Data transmission at 48 kilobits per second using 60-108 kHz group band circuits.....	25
ITU–T Recommendation X.21, Interface between Data Terminal Equipment and Data Circuit-terminating Equipment for synchronous operation on public data networks.....	25
ITU–T Recommendation Y.1731, OAM functions and mechanisms for Ethernet based networks.....	22

## R

RFC 0768, User Datagram Protocol.....	45
RFC 0783, THE TFTP PROTOCOL (REVISION 2).....	19
RFC 0791, INTERNET PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION.....	45
RFC 0792, INTERNET CONTROL MESSAGE PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION.....	38, 45
RFC 0793, TRANSMISSION CONTROL PROTOCOL - DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION.....	45
RFC 0826, An Ethernet Address Resolution Protocol.....	45
RFC 0854, TELNET PROTOCOL SPECIFICATION.....	45
RFC 0862, Echo Protocol.....	45
RFC 0863, Discard Protocol.....	45
RFC 0894, A Standard for the Transmission of IP Datagrams over Ethernet Networks.....	45
RFC 0896, Congestion Control in IP/TCP Internetworks.....	45
RFC 0903, A Reverse Address Resolution Protocol.....	45
RFC 0906, Bootstrap Loading using TFTP.....	19
RFC 0919, BROADCASTING INTERNET DATAGRAMS.....	45
RFC 0922, BROADCASTING INTERNET DATAGRAMS IN THE PRESENCE OF SUBNETS.....	45
RFC 0951, BOOTSTRAP PROTOCOL (BOOTP).....	7
RFC 0959, FILE TRANSFER PROTOCOL (FTP).....	45
RFC 1001, PROTOCOL STANDARD FOR A NetBIOS SERVICE ON A TCP/UDP TRANSPORT: CONCEPTS AND METHODS.....	7
RFC 1002, PROTOCOL STANDARD FOR A NetBIOS SERVICE ON A TCP/UDP TRANSPORT: DETAILED SPECIFICATIONS.....	7
RFC 1027, Using ARP to Implement Transparent Subnet Gateways.....	45
RFC 1035, DOMAIN NAMES - IMPLEMENTATION AND SPECIFICATION.....	7
RFC 1042, A Standard for the Transmission of IP Datagrams over IEEE 802 Networks.....	45
RFC 1058, Routing Information Protocol.....	51
RFC 1075, Distance Vector Multicast Routing Protocol.....	44
RFC 1112, Host Extensions for IP Multicasting.....	43

RFC 1122, Requirements for Internet Hosts -- Communication Layers.....	9
RFC 1155, Structure and Identification of Management Information for TCP/IP-based Internets.....	10
RFC 1156, Management Information Base for Network Management of TCP/IP-based internets.....	10
RFC 1157, A Simple Network Management Protocol (SNMP).....	10, 45, 46
RFC 1166, INTERNET NUMBERS.....	45
RFC 1195, Use of OSI IS-IS for Routing in TCP/IP and Dual Environments.....	10, 45, 46, 49
RFC 1212, Concise MIB Definitions.....	10
RFC 1213, Management Information Base for Network Management of TCP/IP-based internets: MIB-II.....	11, 46
RFC 1215, A Convention for Defining Traps for use with the SNMP.....	11, 47
RFC 1256, ICMP Router Discovery Messages.....	43, 45
RFC 1305, Network Time Protocol (Version 3) Specification, Implementation and Analysis.....	20, 45
RFC 1319, The MD2 Message-Digest Algorithm.....	19
RFC 1321, The MD5 Message-Digest Algorithm.....	19
RFC 1332, The PPP Internet Protocol Control Protocol (IPCP).....	24
RFC 1334, PPP Authentication Protocols.....	24
RFC 1406, Definitions of Managed Objects for the DS1 and E1 Interface Types.....	11
RFC 1407, Definitions of Managed Objects for the DS3/E3 Interface Type.....	11
RFC 1472, The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol.....	11
RFC 1473, The Definitions of Managed Objects for the IP Network Control Protocol of the Point-to-Point Protocol.....	11
RFC 1483, Multiprotocol Encapsulation over ATM Adaptation Layer 5.....	21
RFC 1490 See RFC 2427	
RFC 1492, An Access Control Protocol, Sometimes Called TACACS.....	18
RFC 1519, Classless Inter-Domain Routing (CIDR): an Address Assignment and Aggregation Strategy.....	46
RFC 1534, Interoperation Between DHCP and BOOTP.....	7
RFC 1583, OSPF Version 2.....	50
RFC 1587, The OSPF NSSA Option See RFC 3101	
RFC 1619, PPP over SONET/SDH.....	25
RFC 1631, The IP Network Address Translator (NAT).....	56
RFC 1657, Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIv2.....	11
RFC 1661, The Point-to-Point Protocol (PPP).....	24
RFC 1662, PPP in HDLC-like Framing.....	24
RFC 1695, Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2.....	11
RFC 1700, ASSIGNED NUMBERS.....	7
RFC 1701, Generic Routing Encapsulation (GRE).....	23
RFC 1702, Generic Routing Encapsulation over IPv4 networks.....	23
RFC 1717, The PPP Multilink Protocol (MP) See RFC 1990	
RFC 1724, RIP Version 2 MIB Extension.....	11
RFC 1745, BGP4/IDRP for IP—OSPF Interaction.....	41
RFC 1771, A Border Gateway Protocol 4 (BGP-4).....	47
RFC 1772, Application of the Border Gateway Protocol in the Internet.....	41, 47
RFC 1793, Extending OSPF to Support Demand Circuits.....	50
RFC 1812, Requirements for IP Version 4 Routers.....	46
RFC 1850, OSPF Version 2 Management Information Base.....	12
RFC 1877, PPP Internet Protocol Control Protocol Extensions for Name Server Addresses.....	24
RFC 1878, Variable Length Subnet Table For IPv4.....	46
RFC 1901, Introduction to Community-based SNMPv2.....	18, 48

RFC 1902, Structure of Management Information for Version 2 of the Simple Network Management Protocol (SNMPv2).....	47
RFC 1905, Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2).....	12, 47
RFC 1907, Management Information Base for Version 2 of the Simple Network Management Protocol (SNMPv2).....	12
RFC 1918, Address Allocation for Private Internets.....	58
RFC 1948, Defending Against Sequence Number Attacks.....	46
RFC 1965, Autonomous System Confederations for BGP.....	42
RFC 1966, BGP Route Reflection—An alternative to full mesh IBGP.....	42
RFC 1973, PPP in Frame Relay.....	23
RFC 1981, Path MTU Discovery for IP version 6.....	47
RFC 1989, PPP Link Quality Monitoring.....	24
RFC 1990, The PPP Multilink Protocol (MP).....	24, 55
RFC 1994, PPP Challenge Handshake Authentication Protocol (CHAP).....	19
RFC 1997, BGP Communities Attribute.....	41
RFC 2003, IP Encapsulation within IP.....	23
RFC 2011, SNMPv2 Management Information Base for the Internet Protocol using SMIv2.....	12
RFC 2012, SNMPv2 Management Information Base for the Transmission Control Protocol using SMIv2.....	12
RFC 2013, SNMPv2 Management Information Base for the User Datagram Protocol using SMIv2.....	12
RFC 2030, Simple Network Time Protocol (SNTP) Version 4 for IPv4, IPv6 and OSI.....	20
RFC 2068, Hypertext Transfer Protocol -- HTTP/1.1.....	12
RFC 2080, RIPng for IPv6.....	47, 51
RFC 2081, RIPng Protocol Applicability Statement.....	47, 51
RFC 2082, RIP-2 MD5 Authentication.....	51
RFC 2085, HMAC-MD5 IP Authentication with Replay Prevention.....	54
RFC 2096, IP Forwarding Table MIB.....	12
RFC 2104, HMAC: Keyed-Hashing for Message Authentication.....	54
RFC 2115, Management Information Base for Frame Relay DTEs Using SMIv2.....	12
RFC 2117, Protocol Independent Multicast-Sparse Mode (PIM-SM): Protocol Specification See RFC 2362	
RFC 2131, Dynamic Host Configuration Protocol.....	7
RFC 2132, DHCP Options and BOOTP Vendor Extensions.....	7
RFC 2138, Remote Authentication Dial In User Service (RADIUS) See RFC 2865	
RFC 2139, RADIUS Accounting See RFC 2866	
RFC 2153, PPP Vendor Extensions.....	24
RFC 2205, Resource ReSerVation Protocol (RSVP)—Version 1 Functional Specification.....	35
RFC 2209, Resource ReSerVation Protocol (RSVP)—Version 1 Message Processing Rules.....	36
RFC 2210, The Use of RSVP with IETF Integrated Services.....	35
RFC 2211, Specification of the Controlled-Load Network Element Service.....	35
RFC 2212, Specification of Guaranteed Quality of Service.....	35
RFC 2215, General Characterization Parameters for Integrated Service Network Elements.....	35
RFC 2216, Network Element Service Specification Template.....	36
RFC 2225, Classical IP and ARP over ATM.....	21
RFC 2233, The Interfaces Group MIB using SMIv2.....	12
RFC 2236, Internet Group Management Protocol, Version 2.....	43
RFC 2246, The TLS Protocol Version 1.0.....	19
RFC 2267, Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing.....	38
RFC 2270, Using a Dedicated AS for Sites Homed to a Single Provider.....	42
RFC 2283, Multiprotocol Extensions for BGP-4.....	41, 47, 58

RFC 2287, Definitions of System-Level Managed Objects for Applications.....	12
RFC 2327, SDP: Session Description Protocol.....	43
RFC 2328, OSPF Version 2.....	50
RFC 2330, Framework for IP Performance Metrics.....	18
RFC 2338, Virtual Router Redundancy Protocol.....	46
RFC 2362, Protocol Independent Multicast-Sparse Mode (PIM-SM): Protocol Specification.....	44
RFC 2364, PPP Over AAL5.....	24, 55
RFC 2365, Administratively Scoped IP Multicast.....	44
RFC 2370, The OSPF Opaque LSA Option.....	50
RFC 2373, IP Version 6 Addressing Architecture.....	47
RFC 2385, Protection of BGP Sessions via the TCP MD5 Signature Option.....	41
RFC 2390, Inverse Address Resolution Protocol.....	23
RFC 2401, Security Architecture for the Internet Protocol.....	54
RFC 2402, IP Authentication Header.....	54
RFC 2403, The Use of HMAC-MD5-96 within ESP and AH.....	54
RFC 2404, The Use of HMAC-SHA-1-96 within ESP and AH.....	54
RFC 2405, The ESP DES-CBC Cipher Algorithm With Explicit IV.....	54
RFC 2406, IP Encapsulating Security Payload (ESP).....	54
RFC 2407, The Internet IP Security Domain of Interpretation for ISAKMP.....	54
RFC 2408, Internet Security Association and Key Management Protocol (ISAKMP).....	54
RFC 2409, The Internet Key Exchange (IKE).....	54
RFC 2410, The NULL Encryption Algorithm and Its Use With IPsec.....	54
RFC 2412, The OAKLEY Key Determination Protocol.....	54
RFC 2427, Multiprotocol Interconnect over Frame Relay.....	23
RFC 2439, BGP Route Flap Damping.....	41
RFC 2453, RIP Version 2.....	51
RFC 2460, Internet Protocol, Version 6 (IPv6) Specification.....	38, 47
RFC 2461, Neighbor Discovery for IP Version 6 (IPv6) See RFC 4861	
RFC 2462, IPv6 Stateless Address Autoconfiguration See RFC 4862	
RFC 2463, Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification See RFC 4443	
RFC 2464, Transmission of IPv6 Packets over Ethernet Networks.....	47
RFC 2465, Management Information Base for IP Version 6: Textual Conventions and General Group.....	12, 47
RFC 2466, Management Information Base for IP Version 6: ICMPv6 Group.....	13
RFC 2472, IP Version 6 over PPP.....	47
RFC 2474, Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers.....	37, 38, 47
RFC 2475, An Architecture for Differentiated Services.....	37, 38
RFC 2491, IPv6 Over Non-Broadcast Multiple Access (NBMA) networks.....	47
RFC 2492, IPv6 over ATM Networks.....	47
RFC 2495, Definitions of Managed Objects for the DS1, E1, DS2 and E2 Interface Types.....	13
RFC 2496, Definitions of Managed Objects for the DS3/E3 Interface Type.....	13
RFC 2508, Compressing IP/UDP/RTP Headers for Low-Speed Serial Links.....	56
RFC 2509, IP Header Compression over PPP.....	56
RFC 2515, Definitions of Managed Objects for ATM Management.....	13
RFC 2526, Reserved IPv6 Subnet Anycast Addresses.....	47
RFC 2545, Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing.....	41, 47
RFC 2547, BGP/MPLS VPNs.....	23, 34, 44
RFC 2558, Definitions of Managed Objects for the SONET/SDH Interface Type.....	13
RFC 2570, Introduction to Version 3 of the Internet-standard Network Management Framework See RFC 3410	

RFC 2571, An Architecture for Describing SNMP Management Frameworks.....	13
RFC 2572, Message Processing and Dispatching for the Simple Network Management Protocol (SNMP).....	13
RFC 2576, Coexistence between Version 1, Version 2, and Version 3 of the Internet-standard Network Management Framework See RFC 3584	
RFC 2578, Structure of Management Information Version 2 (SMIv2).....	13, 47
RFC 2579, Textual Conventions for SMIv2.....	13
RFC 2580, Conformance Statements for SMIv2.....	13
RFC 2590, Transmission of IPv6 Packets over Frame Relay Networks Specification.....	23
RFC 2597, Assured Forwarding PHB Group.....	37, 38
RFC 2598, An Expedited Forwarding PHB.....	37, 38
RFC 2615, PPP over SONET/SDH.....	24
RFC 2661, Layer Two Tunneling Protocol "L2TP".....	28, 55
RFC 2662, Definitions of Managed Objects for the ADSL Lines.....	14
RFC 2663, IP Network Address Translator (NAT) Terminology and Considerations.....	56
RFC 2665, Definitions of Managed Objects for the Ethernet-like Interface Types.....	14
RFC 2667, IP Tunnel MIB.....	14
RFC 2675, IPv6 Jumbograms.....	47
RFC 2684, Multiprotocol Encapsulation over ATM Adaptation Layer 5.....	21
RFC 2685, Virtual Private Networks Identifier.....	58
RFC 2686, The Multi-Class Extension to Multi-Link PPP.....	24, 55
RFC 2697, A Single Rate Three Color Marker.....	37
RFC 2698, A Two Rate Three Color Marker.....	37, 38
RFC 2702, Requirements for Traffic Engineering Over MPLS.....	34
RFC 2710, Multicast Listener Discovery (MLD) for IPv6.....	43
RFC 2711, IPv6 Router Alert Option.....	47
RFC 2740, OSPF for IPv6.....	47, 50
RFC 2745, RSVP Diagnostic Messages.....	35
RFC 2747, RSVP Cryptographic Authentication.....	35
RFC 2763, Dynamic Hostname Exchange Mechanism for IS-IS See RFC 5301	
RFC 2766, Network Address Translation - Protocol Translation (NAT-PT).....	56
RFC 2767, Dual Stack Hosts using the "Bump-In-the-Stack" Technique (BIS).....	48
RFC 2784, Generic Routing Encapsulation (GRE).....	23
RFC 2787, Definitions of Managed Objects for the Virtual Router Redundancy Protocol.....	14
RFC 2790, Host Resources MIB.....	14
RFC 2794, Mobile IP Network Access Identifier Extension for IPv4.....	8
RFC 2796, BGP Route Reflection – An Alternative to Full Mesh IBGP.....	41
RFC 2819, Remote Network Monitoring Management Information Base.....	14
RFC 2842, Capabilities Advertisement with BGP-4 See RFC 3392	
RFC 2858, Multiprotocol Extensions for BGP-4.....	33, 41, 43, 58
RFC 2863, The Interfaces Group MIB.....	14
RFC 2864, The Inverted Stack Table Extension to the Interfaces Group MIB.....	14
RFC 2865, Remote Authentication Dial In User Service (RADIUS).....	18
RFC 2866, RADIUS Accounting.....	19, 28, 55
RFC 2868, RADIUS Attributes for Tunnel Protocol Support.....	19
RFC 2869, RADIUS Extensions.....	19
RFC 2873, TCP Processing of the IPv4 Precedence Field.....	46
RFC 2878, PPP Bridging Control Protocol (BCP).....	47
RFC 2890, Key and Sequence Number Extensions to GRE.....	23
RFC 2893, Transition Mechanisms for IPv6 Hosts and Routers.....	47

RFC 2918, Route Refresh Capability for BGP-4.....	41
RFC 2925, Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations.....	15, 56
RFC 2932, IPv4 Multicast Routing MIB.....	15
RFC 2933, Internet Group Management Protocol MIB.....	15
RFC 2934, Protocol Independent Multicast MIB for IPv4.....	18
RFC 2961, RSVP Refresh Overhead Reduction Extensions.....	35
RFC 2973, IS-IS Mesh Groups.....	49
RFC 2974, Session Announcement Protocol.....	44
RFC 2977, Mobile IP Authentication, Authorization, and Accounting Requirements.....	8
RFC 2981, Event MIB.....	15
RFC 2983, Differentiated Services and Tunnels.....	37, 38
RFC 2993, Architectural Implications of NAT.....	56
RFC 3014, Notification Log MIB.....	15
RFC 3019, IP Version 6 Management Information Base for The Multicast Listener Discovery Protocol.....	15
RFC 3021, Using 31-Bit Prefixes on IPv4 Point-to-Point Links.....	24, 46
RFC 3022, Traditional IP Network Address Translator (Traditional NAT).....	56
RFC 3024, Reverse Tunneling for Mobile IP, revised.....	8
RFC 3031, Multiprotocol Label Switching Architecture.....	33, 43
RFC 3032, MPLS Label Stack Encoding.....	33
RFC 3036, LDP Specification See RFC 5036	
RFC 3046, DHCP Relay Agent Information Option.....	7
RFC 3063, MPLS Loop Prevention Mechanism.....	34
RFC 3065, Autonomous System Confederations for BGP.....	42
RFC 3097, RSVP Cryptographic Authentication—Updated Message Type Value.....	35
RFC 3101, The OSPF Not-So-Stubby Area (NSSA) Option.....	50
RFC 3107, Carrying Label Information in BGP-4.....	42, 57
RFC 3118, Authentication for DHCP Messages.....	7
RFC 3137, OSPF Stub Router Advertisement.....	51
RFC 3140, Per Hop Behavior Identification Codes.....	33, 37
RFC 3162, RADIUS and IPv6.....	18
RFC 3208, PGM Reliable Transport Protocol Specification.....	34, 44
RFC 3209, RSVP-TE: Extensions to RSVP for LSP Tunnels.....	35
RFC 3212, Constraint-Based LSP Setup using LDP.....	32
RFC 3215, LDP State Machine.....	32
RFC 3246, An Expedited Forwarding PHB (Per-Hop Behavior).....	37, 38, 46
RFC 3260, New Terminology and Clarifications for Diffserv.....	37, 38
RFC 3261, SIP: Session Initiation Protocol.....	55
RFC 3270, Multi-Protocol Label Switching (MPLS) Support of Differentiated Services.....	33
RFC 3280, Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile.....	19
RFC 3315, Dynamic Host Configuration Protocol for IPv6 (DHCPv6).....	7, 47
RFC 3344, IP Mobility Support for IPv4.....	8
RFC 3358, Optional Checksums in Intermediate System to Intermediate System (ISIS).....	49
RFC 3359, Reserved Type, Length and Value (TLV) Codepoints in Intermediate System to Intermediate System.....	49
RFC 3373, Three-Way Handshake for Intermediate System to Intermediate System (IS-IS) Point-to-Point Adjacencies.....	49
RFC 3376, Internet Group Management Protocol, Version 3.....	43
RFC 3392, Capabilities Advertisement with BGP-4.....	42
RFC 3397, Dynamic Host Configuration Protocol (DHCP) Domain Search Option.....	7

RFC 3410, Introduction and Applicability Statements for Internet Standard Management Framework.....	18
RFC 3411, An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks.....	15
RFC 3412, Message Processing and Dispatching for the Simple Network Management Protocol (SNMP).....	15
RFC 3413, Simple Network Management Protocol (SNMP) Applications.....	15
RFC 3414, User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3).....	15
RFC 3415, View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP).....	15
RFC 3416, Version 2 of the Protocol Operations for the Simple Network Management Protocol (SNMP).....	15
RFC 3417, Transport Mappings for the Simple Network Management Protocol (SNMP).....	15
RFC 3418, Management Information Base (MIB) for the Simple Network Management Protocol (SNMP).....	15
RFC 3443, Time To Live (TTL) Processing in Multi-Protocol Label Switching (MPLS) Networks.....	33
RFC 3446, Anycast Rendezvous Point (RP) mechanism using Protocol Independent Multicast (PIM) and Multicast Source Discovery Protocol (MSDP).....	44
RFC 3469, Framework for Multi-Protocol Label Switching (MPLS)-based Recovery.....	34
RFC 3471, Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description.....	31
RFC 3473, Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Extensions.....	31, 35
RFC 3477, Signalling Unnumbered Links in Resource ReSerVation Protocol - Traffic Engineering (RSVP-TE).....	35
RFC 3478, Graceful Restart Mechanism for Label Distribution Protocol.....	32, 33
RFC 3484, Default Address Selection for Internet Protocol version 6 (IPv6).....	47
RFC 3498, Definitions of Managed Objects for Synchronous Optical Network (SONET) Linear Automatic Protection Switching (APS) Architectures.....	15
RFC 3509, Alternative Implementations of OSPF Area Border Routers.....	51
RFC 3513, Internet Protocol Version 6 (IPv6) Addressing Architecture.....	48
RFC 3515, The Session Initiation Protocol (SIP) Refer Method.....	48
RFC 3543, Registration Revocation in Mobile IPv4.....	8
RFC 3564, Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering.....	34
RFC 3567, Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication.....	49
RFC 3569, An Overview of Source-Specific Multicast (SSM).....	44
RFC 3576, Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS) See RFC 5176	
RFC 3584, Coexistence between Version 1, Version 2, and Version 3 of the Internet-standard Network Management Framework.....	18
RFC 3587, IPv6 Global Unicast Address Format.....	48
RFC 3590, Source Address Selection for the Multicast Listener Discovery (MLD) Protocol.....	44
RFC 3592, Definitions of Managed Objects for the Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH) Interface Type.....	16
RFC 3602, The AES-CBC Cipher Algorithm and Its Use with IPsec.....	54
RFC 3618, Multicast Source Discovery Protocol (MSDP).....	44
RFC 3623, Graceful OSPF Restart.....	50
RFC 3630, Traffic Engineering (TE) Extensions to OSPF Version 2.....	50
RFC 3633, IPv6 Prefix Options for Dynamic Host Configuration Protocol (DHCP) version 6.....	8
RFC 3706, A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers.....	54
RFC 3768, Virtual Router Redundancy Protocol (VRRP).....	48
RFC 3784, Intermediate System to Intermediate System (IS-IS) Extensions for Traffic Engineering (TE) See RFC 5305	
RFC 3787, Recommendations for Interoperable IP Networks using Intermediate System to Intermediate System (IS-IS).....	50

RFC 3810, Multicast Listener Discovery Version 2 (MLDv2) for IPv6.....	44, 48
RFC 3811, Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management.....	16
RFC 3812, Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB).....	16
RFC 3813, Multiprotocol Label Switching (MPLS) Label Switching Router (LSR) Management Information Base (MIB).....	16
RFC 3815, Definitions of Managed Objects for the Multiprotocol Label Switching (MPLS), Label Distribution Protocol (LDP).....	17
RFC 3826, The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model.....	17
RFC 3925, Vendor-Identifying Vendor Options for Dynamic Host Configuration Protocol version 4 (DHCPv4).....	8
RFC 3948, UDP Encapsulation of IPsec ESP Packets.....	54
RFC 3954, Cisco Systems NetFlow Services Export Version 9.....	53
RFC 3973, Protocol Independent Multicast – Dense Mode (PIM-DM): Protocol Specification (Revised).....	44
RFC 4090, Fast Reroute Extensions to RSVP-TE for LSP Tunnels.....	33, 35
RFC 4124, Protocol Extensions for Support of Diffserv-aware MPLS Traffic Engineering.....	33
RFC 4125, Maximum Allocation Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering.....	34, 36
RFC 4127, Russian Dolls Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering.....	34, 36
RFC 4188, Definitions of Managed Objects for Bridges.....	17
RFC 4203, OSPF Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS).....	35, 50
RFC 4206, Label Switched Paths (LSP) Hierarchy with Generalized Multi-Protocol Label Switching (GMPLS) Traffic Engineering (TE).....	31
RFC 4271, A Border Gateway Protocol 4 (BGP-4).....	42
RFC 4291, IP Version 6 Addressing Architecture.....	38, 48
RFC 4301, Security Architecture for the Internet Protocol.....	54
RFC 4302, IP Authentication Header.....	54
RFC 4303, IP Encapsulating Security Payload (ESP).....	54
RFC 4360, BGP Extended Communities Attribute.....	42
RFC 4364, BGP/MPLS IP Virtual Private Networks (VPNs).....	33, 42, 44, 57, 58
RFC 4379, Detecting Multi-Protocol Label Switched (MPLS) Data Plane Failures.....	33, 58
RFC 4433, Mobile IPv4 Dynamic Home Agent (HA) Assignment.....	8
RFC 4443, Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification.....	38, 43, 48
RFC 4447, Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP).....	28
RFC 4448, Encapsulation Methods for Transport of Ethernet over MPLS Networks.....	28
RFC 4456, BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP).....	42
RFC 4552, Authentication/Confidentiality for OSPFv3.....	50
RFC 4558, Node-ID Based Resource Reservation Protocol (RSVP) Hello: A Clarification Statement.....	35
RFC 4561, Definition of a Record Route Object (RRO) Node-Id Sub-Object.....	35
RFC 4576, Using a Link State Advertisement (LSA) Options Bit to Prevent Looping in BGP/MPLS IP Virtual Private Networks (VPNs).....	50, 58
RFC 4577, OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs).....	50, 58
RFC 4601, Protocol Independent Multicast – Sparse Mode (PIM-SM): Protocol Specification (Revised).....	44
RFC 4607, Source-Specific Multicast for IP.....	44
RFC 4649, Dynamic Host Configuration Protocol for IPv6 (DHCPv6) Relay Agent Remote-ID Option.....	8
RFC 4659, BGP-MPLS IP Virtual Private Network (VPN) Extension for IPv6 VPN.....	42, 48, 58
RFC 4679, DSL Forum Vendor-Specific RADIUS Attributes.....	19

RFC 4684, Constrained Route Distribution for Border Gateway Protocol/MultiProtocol Label Switching (BGP/MPLS) Internet Protocol (IP) Virtual Private Networks (VPNs).....	58
RFC 4724, Graceful Restart Mechanism for BGP.....	42
RFC 4761, Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling.....	59
RFC 4762, Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling.....	59
RFC 4781, Graceful Restart Mechanism for BGP with MPLS.....	42
RFC 4787, Network Address Translation (NAT) Behavioral Requirements for Unicast UDP.....	56
RFC 4818, RADIUS Delegated-IPv6-Prefix Attribute.....	18
RFC 4861, Neighbor Discovery for IP version 6 (IPv6).....	43, 48
RFC 4862, IPv6 Stateless Address Autoconfiguration.....	43, 48
RFC 4893, BGP Support for Four-octet AS Number Space.....	42
RFC 4915, Multi-Topology Routing (MT) in OSPF.....	50
RFC 4950, ICMP Extensions for Multiprotocol Label Switching.....	33
RFC 5036, LDP Specification.....	32
RFC 5095, Deprecation of Type 0 Routing Headers in IPv6.....	48
RFC 5120, M-ISIS: Multi Topology (MT) Routing in Intermediate System to Intermediate Systems (IS-ISs).....	49
RFC 5130, A Policy Control Mechanism in IS-IS Using Administrative Tags.....	49
RFC 5176, Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS).....	19
RFC 5185, OSPF Multi-Area Adjacency.....	50
RFC 5286, Basic Specification for IP Fast Reroute: Loop-Free Alternates.....	49, 50
RFC 5301, Dynamic Hostname Exchange Mechanism for IS-IS.....	49
RFC 5302, Domain-wide Prefix Distribution with Two-Level IS-IS.....	49
RFC 5303, Three-Way Handshake for IS-IS Point-to-Point Adjacencies.....	49
RFC 5304, IS-IS Cryptographic Authentication.....	49
RFC 5305, IS-IS Extensions for Traffic Engineering.....	49
RFC 5306, Restart Signaling for IS-IS.....	49
RFC 5307, IS-IS Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS).....	49
RFC 5308, Routing IPv6 with IS-IS.....	48, 49
RFC 5309, Point-to-Point Operation over LAN in Link State Routing Protocols.....	50, 51
RFC 5382, NAT Behavioral Requirements for TCP.....	56
RFC 5443, LDP IGP Synchronization.....	33
RFC 5508, NAT Behavioral Requirements for ICMP.....	56