



---

Junos<sup>®</sup> OS

# Firewall Filters Configuration Guide

Release  
12.3



---

Published: 2012-12-10



Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, California 94089  
USA  
408-745-2000  
[www.juniper.net](http://www.juniper.net)

This product includes the Envoy SNMP Engine, developed by Epilogue Technology, an Integrated Systems Company. Copyright © 1986-1997, Epilogue Technology Corporation. All rights reserved. This program and its documentation were developed at private expense, and no part of them is in the public domain.

This product includes memory allocation software developed by Mark Moraes, copyright © 1988, 1989, 1993, University of Toronto.

This product includes FreeBSD software developed by the University of California, Berkeley, and its contributors. All of the documentation and software included in the 4.4BSD and 4.4BSD-Lite Releases is copyrighted by the Regents of the University of California. Copyright © 1979, 1980, 1983, 1986, 1988, 1989, 1991, 1992, 1993, 1994. The Regents of the University of California. All rights reserved.

GateD software copyright © 1995, the Regents of the University. All rights reserved. Gate Daemon was originated and developed through release 3.0 by Cornell University and its collaborators. Gated is based on Kirton's EGP, UC Berkeley's routing daemon (routed), and DCN's HELLO routing protocol. Development of Gated has been supported in part by the National Science Foundation. Portions of the GateD software copyright © 1988, Regents of the University of California. All rights reserved. Portions of the GateD software copyright © 1991, D. L. S. Associates.

This product includes software developed by Maker Communications, Inc., copyright © 1996, 1997, Maker Communications, Inc.

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Products made or sold by Juniper Networks or components thereof might be covered by one or more of the following patents that are owned by or licensed to Juniper Networks: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

### *Junos® OS Firewall Filters Configuration Guide*

12.3

Copyright © 2012, Juniper Networks, Inc.  
All rights reserved.

The information in this document is current as of the date on the title page.

### YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

### END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <http://www.juniper.net/support/eula.html>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.



# Table of Contents

	About the Documentation . . . . .	xv
	Documentation and Release Notes . . . . .	xv
	Supported Platforms . . . . .	xv
	Using the Examples in This Manual . . . . .	xv
	Merging a Full Example . . . . .	xvi
	Merging a Snippet . . . . .	xvi
	Documentation Conventions . . . . .	xvii
	Documentation Feedback . . . . .	xix
	Requesting Technical Support . . . . .	xix
	Self-Help Online Tools and Resources . . . . .	xix
	Opening a Case with JTAC . . . . .	xx
<b>Part 1</b>	<b>Overview</b>	
<b>Chapter 1</b>	<b>Introduction to Stateless Firewall Filters . . . . .</b>	<b>3</b>
	Router Data Flow Overview . . . . .	3
	Flow of Routing Information . . . . .	3
	Flow of Data Packets . . . . .	4
	Flow of Local Packets . . . . .	4
	Interdependent Flows of Routing Information and Packets . . . . .	4
	Stateless Firewall Filter Overview . . . . .	5
	Packet Flow Control . . . . .	5
	Data Packet Flow Control . . . . .	5
	Local Packet Flow Control . . . . .	5
	Stateless and Stateful Firewall Filters . . . . .	5
	Purpose of Stateless Firewall Filters . . . . .	6
	Stateless Firewall Filter Types . . . . .	6
	Standard Stateless Firewall Filters . . . . .	6
	Service Filters . . . . .	7
	Simple Filters . . . . .	7
	Stateless Firewall Filter Components . . . . .	7
	Protocol Family . . . . .	7
	Filter Type . . . . .	8
	Terms . . . . .	9
	Match Conditions . . . . .	10
	Actions . . . . .	11
	Filter-Terminating Actions . . . . .	11
	Nonterminating Actions . . . . .	11
	Flow Control Action . . . . .	12
	Stateless Firewall Filter Application Points . . . . .	13



<b>Chapter 2</b>	<b>Standard Firewall Filters Overview . . . . .</b>	<b>17</b>
	Standard Stateless Firewall Filter Overview . . . . .	17
	How Standard Firewall Filters Evaluate Packets . . . . .	18
	Firewall Filters That Contain a Single Term . . . . .	18
	Firewall Filters That Contain Multiple Terms . . . . .	18
	Firewall Filter Terms That Do Not Contain Any Match Conditions . . . . .	19
	Firewall Filter Terms That Do Not Contain Any Actions . . . . .	19
	Firewall Filter Default Action . . . . .	19
	Guidelines for Configuring Standard Firewall Filters . . . . .	19
	Statement Hierarchy for Configuring Standard Firewall Filters . . . . .	20
	Standard Firewall Filter Protocol Families . . . . .	20
	Standard Firewall Filter Names and Options . . . . .	21
	Standard Firewall Filter Terms . . . . .	21
	Standard Firewall Filter Match Conditions . . . . .	22
	Standard Firewall Filter Actions . . . . .	23
	Guidelines for Applying Standard Firewall Filters . . . . .	25
	Applying Standard Firewall Filters Overview . . . . .	25
	Applying a Firewall Filter to a Router's Physical Interfaces . . . . .	25
	Applying a Firewall Filter to the Router's Loopback Interface . . . . .	25
	Applying a Firewall Filter to Multiple Interfaces . . . . .	25
	Statement Hierarchy for Applying Standard Firewall Filters . . . . .	25
	Restrictions on Applying Standard Firewall Filters . . . . .	26
	Number of Input and Output Filters Per Logical Interface . . . . .	26
	MPLS and Layer 2 CCC Firewall Filters in Lists . . . . .	26
	Layer 2 CCC Firewall Filters on MX Series Routers . . . . .	27
	Protocol-Independent Firewall Filters on the Loopback Interface . . . . .	27
	Understanding How to Use Standard Firewall Filters . . . . .	27
	Using Standard Firewall Filters to Affect Local Packets . . . . .	27
	Trusted Sources . . . . .	27
	Flood Prevention . . . . .	28
	Using Standard Firewall Filters to Affect Data Packets . . . . .	28
<b>Chapter 3</b>	<b>Standard Firewall Filter Match Conditions Overview . . . . .</b>	<b>29</b>
	Firewall Filter Match Conditions Based on Numbers or Text Aliases . . . . .	29
	Matching on a Single Numeric Value . . . . .	29
	Matching on a Range of Numeric Values . . . . .	29
	Matching on a Text Alias for a Numeric Value . . . . .	30
	Matching on a List of Numeric Values or Text Aliases . . . . .	30
	Firewall Filter Match Conditions Based on Bit-Field Values . . . . .	30
	Match Conditions for Bit-Field Values . . . . .	30
	Match Conditions for Common Bit-Field Values or Combinations . . . . .	31
	Logical Operators for Bit-Field Values . . . . .	32
	Matching on a Single Bit-Field Value or Text Alias . . . . .	33
	Matching on Multiple Bit-Field Values or Text Aliases . . . . .	33
	Matching on a Negated Bit-Field Value . . . . .	34
	Matching on the Logical OR of Two Bit-Field Values . . . . .	34
	Matching on the Logical AND of Two Bit-Field Values . . . . .	34
	Grouping Bit-Field Match Conditions . . . . .	34



	Firewall Filter Match Conditions Based on Address Fields . . . . .	35
	Implied Match on the '0/0 except' Address for Firewall Filter Match	
	Conditions Based on Address Fields . . . . .	35
	Matching an Address Field to a Subnet Mask or Prefix . . . . .	35
	IPv4 Subnet Mask Notation . . . . .	35
	Prefix Notation . . . . .	35
	Default Prefix Length for IPv4 Addresses . . . . .	36
	Default Prefix Length for IPv6 Addresses . . . . .	36
	Default Prefix Length for MAC Addresses . . . . .	36
	Matching an Address Field to an Excluded Value . . . . .	36
	Excluding IP Addresses in IPv4 or IPv6 Traffic . . . . .	36
	Excluding IP Addresses in VPLS or Layer 2 Bridging Traffic . . . . .	37
	Excluding MAC Addresses in VPLS or Layer 2 Bridging Traffic . . . . .	38
	Excluding All Addresses Requires an Explicit Match on the '0/0' Address . . . . .	38
	Matching Either IP Address Field to a Single Value . . . . .	40
	Matching Either IP Address Field in IPv4 or IPv6 Traffic . . . . .	40
	Matching Either IP Address Field in VPLS or Layer 2 Bridging Traffic . . . . .	40
	Matching an Address Field to Noncontiguous Prefixes . . . . .	40
	Matching an Address Field to a Prefix List . . . . .	42
	Firewall Filter Match Conditions Based on Address Classes . . . . .	43
	Source-Class Usage . . . . .	43
	Destination-Class Usage . . . . .	43
	Guidelines for Applying SCU or DCU Firewall Filters to Output Interfaces . . . . .	43
<b>Chapter 4</b>	<b>Introduction to Standard Firewall Filters for Fragment Handling . . . . .</b>	<b>45</b>
	Firewall Filters That Handle Fragmented Packets Overview . . . . .	45
<b>Chapter 5</b>	<b>Introduction to Standard Firewall Filters Configuration . . . . .</b>	<b>47</b>
	Stateless Firewall Filters That Reference Policers Overview . . . . .	47
	Multiple Standard Firewall Filters Applied as a List Overview . . . . .	48
	The Challenge: Simplify Large-Scale Firewall Filter Administration . . . . .	48
	A Solution: Apply Lists of Firewall Filters . . . . .	49
	Configuration of Multiple Filters for Filter Lists . . . . .	49
	Application of Filter Lists to a Router Interface . . . . .	50
	Interface-Specific Names for Filter Lists . . . . .	50
	How Filter Lists Evaluate Packets . . . . .	50
	Guidelines for Applying Multiple Standard Firewall Filters as a List . . . . .	51
	Statement Hierarchy for Applying Lists of Multiple Firewall Filters . . . . .	51
	Filter Input Lists and Output Lists for Router Interfaces . . . . .	52
	Types of Filters Supported in Lists . . . . .	52
	Restrictions on Applying Filter Lists for MPLS or Layer 2 CCC Traffic . . . . .	52
	Multiple Standard Firewall Filters in a Nested Configuration Overview . . . . .	52
	The Challenge: Simplify Large-Scale Firewall Filter Administration . . . . .	53
	A Solution: Configure Nested References to Firewall Filters . . . . .	53
	Configuration of Nested Firewall Filters . . . . .	53
	Application of Nested Firewall Filters to a Router Interface . . . . .	54
	Guidelines for Nesting References to Multiple Standard Firewall Filters . . . . .	54
	Statement Hierarchy for Configuring Nested Firewall Filters . . . . .	54
	Filter-Defining Terms and Filter-Referencing Terms . . . . .	54



	Types of Filters Supported in Nested Configurations . . . . .	55
	Number of Filter References in a Single Filter . . . . .	55
	Depth of Filter Nesting . . . . .	55
	Interface-Specific Firewall Filter Instances Overview . . . . .	55
	Instantiation of Interface-Specific Firewall Filters . . . . .	55
	Interface-Specific Names for Firewall Filter Instances . . . . .	56
	Interface-Specific Firewall Filter Counters . . . . .	57
	Interface-Specific Firewall Filter Policers . . . . .	57
	Filtering Packets Received on a Set of Interface Groups Overview . . . . .	57
	Filtering Packets Received on an Interface Set Overview . . . . .	58
	Filter-Based Forwarding Overview . . . . .	58
	Filters That Classify Packets or Direct Them to Routing Instances . . . . .	58
	Input Filtering to Classify and Forward Packets Within the Router . . . . .	59
	Output Filtering to Forward Packets to Another Routing Table . . . . .	59
	Restrictions for Applying Filter-Based Forwarding . . . . .	60
	Accounting for Standard Firewall Filters Overview . . . . .	60
	System Logging Overview . . . . .	60
	System Logging of Events Generated for the Firewall Facility . . . . .	61
	Logging of Packet Headers Evaluated by a Firewall Filter Term . . . . .	63
<b>Chapter 6</b>	<b>Introduction to Service Filters Configuration . . . . .</b>	<b>65</b>
	Service Filter Overview . . . . .	65
	Services . . . . .	65
	Service Rules . . . . .	65
	Service Rule Refinement . . . . .	66
	Service Filter Counters . . . . .	66
	How Service Filters Evaluate Packets . . . . .	67
	Service Filters That Contain a Single Term . . . . .	67
	Service Filters That Contain Multiple Terms . . . . .	67
	Service Filter Terms That Do Not Contain Any Match Conditions . . . . .	67
	Service Filter Terms That Do Not Contain Any Actions . . . . .	67
	Service Filter Default Action . . . . .	67
	Guidelines for Configuring Service Filters . . . . .	68
	Statement Hierarchy for Configuring Service Filters . . . . .	68
	Service Filter Protocol Families . . . . .	69
	Service Filter Names . . . . .	69
	Service Filter Terms . . . . .	69
	Service Filter Match Conditions . . . . .	69
	Service Filter Terminating Actions . . . . .	69
	Guidelines for Applying Service Filters . . . . .	70
	Restrictions for Adaptive Services Interfaces . . . . .	70
	Adaptive Services Interfaces . . . . .	70
	System Logging to a Remote Host from M Series Routers . . . . .	71
	Statement Hierarchy for Applying Service Filters . . . . .	71
	Associating Service Rules with Adaptive Services Interfaces . . . . .	71
	Filtering Traffic Before Accepting Packets for Service Processing . . . . .	72
	Postservice Filtering of Returning Service Traffic . . . . .	72



<b>Chapter 7</b>	<b>Introduction to Simple Filters Configuration . . . . .</b>	<b>75</b>
	Simple Filter Overview . . . . .	75
	How Simple Filters Evaluate Packets . . . . .	75
	Simple Filters That Contain a Single Term . . . . .	76
	Simple Filters That Contain Multiple Terms . . . . .	76
	Simple Filter Terms That Do Not Contain Any Match Conditions . . . . .	76
	Simple Filter Terms That Do Not Contain Any Actions . . . . .	76
	Simple Filter Default Action . . . . .	76
	Guidelines for Configuring Simple Filters . . . . .	77
	Statement Hierarchy for Configuring Simple Filters . . . . .	77
	Simple Filter Protocol Families . . . . .	77
	Simple Filter Names . . . . .	77
	Simple Filter Terms . . . . .	78
	Simple Filter Match Conditions . . . . .	78
	Simple Filter Terminating Actions . . . . .	79
	Simple Filter Nonterminating Actions . . . . .	79
	Guidelines for Applying Simple Filters . . . . .	80
	Statement Hierarchy for Applying Simple Filters . . . . .	80
	Restrictions for Applying Simple Filters . . . . .	80
<b>Chapter 8</b>	<b>Introduction to Firewall Filters Configuration in Logical Systems . . . . .</b>	<b>83</b>
	Stateless Firewall Filters in Logical Systems Overview . . . . .	83
	Logical Systems . . . . .	83
	Stateless Firewall Filters in Logical Systems . . . . .	83
	Identifiers for Firewall Objects in Logical Systems . . . . .	83
	Guidelines for Configuring and Applying Firewall Filters in Logical Systems . . . .	84
	Statement Hierarchy for Configuring Firewall Filters in Logical Systems . . . .	84
	Filter Types in Logical Systems . . . . .	85
	Firewall Filter Protocol Families in Logical Systems . . . . .	85
	Firewall Filter Match Conditions in Logical Systems . . . . .	86
	Firewall Filter Actions in Logical Systems . . . . .	86
	Statement Hierarchy for Applying Firewall Filters in Logical Systems . . . . .	86
	References from a Firewall Filter in a Logical System to Subordinate Objects . . .	87
	Resolution of References from a Firewall Filter to Subordinate Objects . . . .	87
	Valid Reference from a Firewall Filter to a Subordinate Object . . . . .	87
	References from a Firewall Filter in a Logical System to Nonfirewall Objects . . .	88
	Resolution of References from a Firewall Filter to Nonfirewall Objects . . . .	88
	Valid Reference to a Nonfirewall Object Outside of the Logical System . . . .	89
	References from a Nonfirewall Object in a Logical System to a Firewall Filter . . .	90
	Resolution of References from a Nonfirewall Object to a Firewall Filter . . . .	91
	Invalid Reference to a Firewall Filter Outside of the Logical System . . . . .	91
	Valid Reference to a Firewall Filter Within the Logical System . . . . .	92
	Valid Reference to a Firewall Filter Outside of the Logical System . . . . .	94
<b>Part 2</b>	<b>Configuration</b>	
<b>Chapter 9</b>	<b>Standard Firewall Filter Configurations to Match Packets . . . . .</b>	<b>99</b>
	Example: Configuring a Filter to Match on IPv6 Flags . . . . .	99
	Example: Configuring a Filter to Match on Port and Protocol Fields . . . . .	100



	Example: Configuring a Filter to Match on Two Unrelated Criteria . . . . .	103
	Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List . . . . .	106
<b>Chapter 10</b>	<b>Standard Firewall Filters to Count Packets . . . . .</b>	<b>111</b>
	Example: Configuring a Filter to Count Accepted and Rejected Packets . . . . .	111
	Example: Configuring a Filter to Count and Discard IP Options Packets . . . . .	114
	Example: Configuring a Filter to Count IP Options Packets . . . . .	117
<b>Chapter 11</b>	<b>Standard Firewall Filters to Act on Packets . . . . .</b>	<b>123</b>
	Example: Configuring a Filter to Set the DSCP Bit to Zero . . . . .	123
	Example: Configuring a Filter to Count and Sample Accepted Packets . . . . .	126
<b>Chapter 12</b>	<b>Standard Firewall Filters for Trusted Sources . . . . .</b>	<b>131</b>
	Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources . . . . .	131
	Example: Configuring a Filter to Block Telnet and SSH Access . . . . .	136
	Example: Configuring a Filter to Block TFTP Access . . . . .	141
	Example: Configuring a Filter to Accept OSPF Packets from a Prefix . . . . .	144
	Example: Configuring a Filter to Accept DHCP Packets Based on Address . . . . .	147
	Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers . . . . .	150
<b>Chapter 13</b>	<b>Standard Firewall Filters for Flood Prevention . . . . .</b>	<b>157</b>
	Example: Configuring a Stateless Firewall Filter to Protect Against TCP and ICMP Floods . . . . .	157
	Example: Configuring a Filter to Accept Packets Based on IPv6 TCP Flags . . . . .	164
<b>Chapter 14</b>	<b>Standard Firewall Filters for Fragment Handling . . . . .</b>	<b>167</b>
	Example: Configuring a Stateless Firewall Filter to Handle Fragments . . . . .	167
<b>Chapter 15</b>	<b>Standard Firewall Filters for Setting Rate Limits . . . . .</b>	<b>173</b>
	Example: Configuring a Rate-Limiting Filter Based on Destination Class . . . . .	173
<b>Chapter 16</b>	<b>Examples of Standard Firewall Filters Configuration . . . . .</b>	<b>177</b>
	Example: Applying Lists of Multiple Standard Firewall Filters . . . . .	177
	Example: Nesting References to Multiple Standard Firewall Filters . . . . .	182
	Example: Configuring Interface-Specific Firewall Filter Counters . . . . .	186
	Example: Filtering Packets Received on an Interface Group . . . . .	190
	Example: Filtering Packets Received on an Interface Set . . . . .	194
	Example: Configuring Filter-Based Forwarding on the Source Address . . . . .	200
	Example: Configuring Filter-Based Forwarding on Logical Systems . . . . .	206
	Example: Configuring Filter-Based Forwarding to a Specific Outgoing Interface or Destination IP Address . . . . .	215
	Understanding Filter-Based Forwarding to a Specific Outgoing Interface or Destination IP Address . . . . .	216
	Example: Configuring Filter-Based Forwarding to a Specific Outgoing Interface . . . . .	217
<b>Chapter 17</b>	<b>Examples of Standard Firewall Filters Configuration Options . . . . .</b>	<b>223</b>
	Example: Configuring Statistics Collection for a Standard Firewall Filter . . . . .	223
	Example: Configuring Logging for a Stateless Firewall Filter Term . . . . .	228



<b>Chapter 18</b>	<b>Service Filters Configuration . . . . .</b>	<b>233</b>
	Example: Configuring and Applying Service Filters . . . . .	233
<b>Chapter 19</b>	<b>Simple Filters Configuration . . . . .</b>	<b>239</b>
	Example: Configuring and Applying a Simple Filter . . . . .	239
<b>Chapter 20</b>	<b>Firewall Filters Configuration in Logical Systems . . . . .</b>	<b>245</b>
	Example: Configuring a Stateless Firewall Filter to Protect a Logical System Against ICMP Floods . . . . .	245
<b>Part 3</b>	<b>Administration</b>	
<b>Chapter 21</b>	<b>Firewall Filters Standards . . . . .</b>	<b>251</b>
	Supported Standards for Filtering . . . . .	251
<b>Chapter 22</b>	<b>Firewall Filters Reference . . . . .</b>	<b>253</b>
	Using the CLI Editor in Configuration Mode . . . . .	253
<b>Chapter 23</b>	<b>Standard Firewall Filter Match Conditions and Actions . . . . .</b>	<b>257</b>
	Standard Firewall Filter Match Conditions for Protocol-Independent Traffic . . . . .	257
	Standard Firewall Filter Match Conditions for IPv4 Traffic . . . . .	258
	Standard Firewall Filter Match Conditions for IPv6 Traffic . . . . .	267
	Standard Firewall Filter Match Conditions for MPLS Traffic . . . . .	274
	Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic . . . . .	276
	Matching on IPv4 or IPv6 Packet Header Address or Port Fields in MPLS Flows . . . . .	276
	IP Address Match Conditions for MPLS Traffic . . . . .	277
	IP Port Match Conditions for MPLS Traffic . . . . .	277
	Standard Firewall Filter Match Conditions for VPLS Traffic . . . . .	278
	Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic . . . . .	285
	Standard Firewall Filter Match Conditions for Layer 2 Bridging Traffic . . . . .	287
	Standard Firewall Filter Terminating Actions . . . . .	293
	Standard Firewall Filter Nonterminating Actions . . . . .	294
<b>Chapter 24</b>	<b>Standard Firewall Filter Match Conditions and Actions for ACX Series Routers . . . . .</b>	<b>301</b>
	Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview . . . . .	301
	Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers . . . . .	303
	Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers . . . . .	306
	Standard Firewall Filter Terminating Actions on ACX Series Routers . . . . .	306
	Standard Firewall Filter Nonterminating Actions on ACX Series Routers . . . . .	308
<b>Chapter 25</b>	<b>Service Filter Match Conditions and Actions . . . . .</b>	<b>311</b>
	Service Filter Match Conditions for IPv4 or IPv6 Traffic . . . . .	311
	Service Filter Terminating Actions . . . . .	317
	Service Filter Nonterminating Actions . . . . .	318



<b>Chapter 26</b>	<b>Reference Information for Firewall Filters in Logical Systems . . . . .</b>	<b>319</b>
	Unsupported Firewall Filter Statements for Logical Systems . . . . .	319
	Unsupported Actions for Firewall Filters in Logical Systems . . . . .	321
<b>Chapter 27</b>	<b>Firewall Filters Statement Hierarchies . . . . .</b>	<b>325</b>
	Statement Hierarchy for Configuring Interface-Specific Firewall Filters . . . . .	325
	Statement Hierarchy for Applying Interface-Specific Firewall Filters . . . . .	326
	Statement Hierarchy for Assigning Interfaces to Interface Groups . . . . .	327
	Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups . . . . .	327
	Statement Hierarchy for Applying Filters to an Interface Group . . . . .	328
	Statement Hierarchy for Defining an Interface Set . . . . .	329
	Statement Hierarchy for Configuring a Filter to Match on an Interface Set . . . . .	329
	Statement Hierarchy for Configuring FBF for IPv4 or IPv6 Traffic . . . . .	330
	Statement Hierarchy for Configuring FBF for IPv4 Traffic on ACX Series Routers . . . . .	331
	Statement Hierarchy for Configuring FBF for MPLS-Tagged IPv4 Traffic . . . . .	331
	Matching on IPv4 Address and TCP/UDP Port Fields . . . . .	331
	Configuration Example . . . . .	332
	Statement Hierarchy for Configuring Routing Instances for FBF . . . . .	333
	Statement Hierarchy for Applying FBF Filters to Interfaces . . . . .	334
	Statement Hierarchy for Configuring Firewall Filter Accounting Profiles . . . . .	335
	Statement Hierarchy for Applying Firewall Filter Accounting Profiles . . . . .	336
<b>Chapter 28</b>	<b>Summary of Firewall Filters Configuration Statements . . . . .</b>	<b>339</b>
	accounting-profile . . . . .	339
	destination-address . . . . .	339
	destination-port . . . . .	340
	enhanced-mode . . . . .	341
	family (Firewall) . . . . .	342
	filter (Applying to a Logical Interface) . . . . .	343
	filter (Configuring) . . . . .	344
	firewall . . . . .	345
	interface-set . . . . .	345
	interface-specific (Firewall Filters) . . . . .	346
	ip-version . . . . .	346
	prefix-list . . . . .	347
	protocol . . . . .	348
	service-filter (Firewall) . . . . .	349
	simple-filter . . . . .	350
	source-address . . . . .	351
	source-checking . . . . .	351
	source-port . . . . .	352
	term (Firewall Filter) . . . . .	353
<b>Part 4</b>	<b>Index</b>	
	Index . . . . .	357



# List of Figures

<b>Part 1</b>	<b>Overview</b>	
<b>Chapter 1</b>	<b>Introduction to Stateless Firewall Filters . . . . .</b>	<b>3</b>
	Figure 1: Flows of Routing Information and Packets . . . . .	4
<b>Part 2</b>	<b>Configuration</b>	
<b>Chapter 12</b>	<b>Standard Firewall Filters for Trusted Sources . . . . .</b>	<b>131</b>
	Figure 2: Typical Network with BGP Peer Sessions . . . . .	150
<b>Chapter 16</b>	<b>Examples of Standard Firewall Filters Configuration . . . . .</b>	<b>177</b>
	Figure 3: Logical Systems with Filter-Based Forwarding . . . . .	208
	Figure 4: Filter-Based Forwarding to Specified Outgoing Interfaces . . . . .	218
<b>Chapter 20</b>	<b>Firewall Filters Configuration in Logical Systems . . . . .</b>	<b>245</b>
	Figure 5: Logical System with a Stateless Firewall . . . . .	246







# List of Tables

	<b>About the Documentation</b> . . . . .	<b>xv</b>
	Table 1: Notice Icons . . . . .	xvii
	Table 2: Text and Syntax Conventions . . . . .	xvii
<b>Part 1</b>	<b>Overview</b>	
<b>Chapter 1</b>	<b>Introduction to Stateless Firewall Filters</b> . . . . .	<b>3</b>
	Table 3: Firewall Filter Protocol Families . . . . .	8
	Table 4: Filter Types . . . . .	9
	Table 5: Stateless Firewall Filter Configuration and Application Summary . . . . .	14
<b>Chapter 2</b>	<b>Standard Firewall Filters Overview</b> . . . . .	<b>17</b>
	Table 6: Standard Firewall Filter Match Conditions by Protocol Family . . . . .	22
	Table 7: Standard Firewall Filter Action Categories . . . . .	24
<b>Chapter 3</b>	<b>Standard Firewall Filter Match Conditions Overview</b> . . . . .	<b>29</b>
	Table 8: Binary and Bit-Field Match Conditions for Firewall Filters . . . . .	31
	Table 9: Bit-Field Match Conditions for Common Combinations . . . . .	32
	Table 10: Bit-Field Logical Operators . . . . .	32
<b>Chapter 5</b>	<b>Introduction to Standard Firewall Filters Configuration</b> . . . . .	<b>47</b>
	Table 11: Syslog Message Destinations for the Firewall Facility . . . . .	62
	Table 12: Packet-Header Logs for Stateless Firewall Filter Terms . . . . .	64
<b>Chapter 7</b>	<b>Introduction to Simple Filters Configuration</b> . . . . .	<b>75</b>
	Table 13: Simple Filter Match Conditions . . . . .	78
<b>Part 3</b>	<b>Administration</b>	
<b>Chapter 23</b>	<b>Standard Firewall Filter Match Conditions and Actions</b> . . . . .	<b>257</b>
	Table 14: Standard Firewall Filter Match Conditions for Protocol-Independent Traffic . . . . .	258
	Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic . . . . .	258
	Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic . . . . .	268
	Table 17: Standard Firewall Filter Match Conditions for MPLS Traffic . . . . .	274
	Table 18: IP Address-Specific Firewall Filter Match Conditions for MPLS Traffic . . . . .	277
	Table 19: IP Port-Specific Firewall Filter Match Conditions for MPLS Traffic . . . . .	278
	Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic . . . . .	279
	Table 21: Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic . . . . .	285
	Table 22: Standard Firewall Filter Match Conditions for Layer 2 Bridging (MX Series 3D Universal Edge Routers Only) . . . . .	288



	Table 23: Terminating Actions for Standard Firewall Filters . . . . .	293
	Table 24: Nonterminating Actions for Standard Firewall Filters . . . . .	295
<b>Chapter 24</b>	<b>Standard Firewall Filter Match Conditions and Actions for ACX Series Routers . . . . .</b>	<b>301</b>
	Table 25: Standard Firewall Filter Match Conditions by Protocol Family for ACX Series Routers . . . . .	301
	Table 26: Standard Firewall Filter Action Categories for ACX Series Routers . . .	302
	Table 27: Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers . . . . .	303
	Table 28: Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers . . . . .	306
	Table 29: Terminating Actions for Standard Firewall Filters on ACX Series Routers . . . . .	307
	Table 30: Nonterminating Actions for Standard Firewall Filters on ACX Series Routers . . . . .	308
<b>Chapter 25</b>	<b>Service Filter Match Conditions and Actions . . . . .</b>	<b>311</b>
	Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic . . . . .	311
	Table 32: Terminating Actions for Service Filters . . . . .	317
	Table 33: Nonterminating Actions for Service Filters . . . . .	318
<b>Chapter 26</b>	<b>Reference Information for Firewall Filters in Logical Systems . . . . .</b>	<b>319</b>
	Table 34: Unsupported Firewall Statements for Logical Systems . . . . .	319
	Table 35: Unsupported Actions for Firewall Filters in Logical Systems . . . . .	321



# About the Documentation

- Documentation and Release Notes on page xv
- Supported Platforms on page xv
- Using the Examples in This Manual on page xv
- Documentation Conventions on page xvii
- Documentation Feedback on page xix
- Requesting Technical Support on page xix

## Documentation and Release Notes

---

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at <http://www.juniper.net/techpubs/>.

If the information in the latest release notes differs from the information in the documentation, follow the product Release Notes.

Juniper Networks Books publishes books by Juniper Networks engineers and subject matter experts. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration. The current list can be viewed at <http://www.juniper.net/books>.

## Supported Platforms

---

For the features described in this document, the following platforms are supported:

- M Series
- T Series
- MX Series
- PTX Series

## Using the Examples in This Manual

---

If you want to use the examples in this manual, you can use the **load merge** or the **load merge relative** command. These commands cause the software to merge the incoming configuration into the current candidate configuration. The example does not become active until you commit the candidate configuration.



If the example configuration contains the top level of the hierarchy (or multiple hierarchies), the example is a *full example*. In this case, use the **load merge** command.

If the example configuration does not start at the top level of the hierarchy, the example is a *snippet*. In this case, use the **load merge relative** command. These procedures are described in the following sections.

## Merging a Full Example

To merge a full example, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration example into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following configuration to a file and name the file **ex-script.conf**. Copy the **ex-script.conf** file to the **/var/tmp** directory on your routing platform.

```
system {
  scripts {
    commit {
      file ex-script.xml;
    }
  }
}
interfaces {
  fxp0 {
    disable;
    unit 0 {
      family inet {
        address 10.0.0.1/24;
      }
    }
  }
}
```

2. Merge the contents of the file into your routing platform configuration by issuing the **load merge** configuration mode command:

```
[edit]
user@host# load merge /var/tmp/ex-script.conf
load complete
```

## Merging a Snippet

To merge a snippet, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration snippet into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following snippet to a file and name the file **ex-script-snippet.conf**. Copy the **ex-script-snippet.conf** file to the **/var/tmp** directory on your routing platform.

```
commit {
  file ex-script-snippet.xml; }
```



2. Move to the hierarchy level that is relevant for this snippet by issuing the following configuration mode command:

```
[edit]
user@host# edit system scripts
[edit system scripts]
```

3. Merge the contents of the file into your routing platform configuration by issuing the **load merge relative** configuration mode command:

```
[edit system scripts]
user@host# load merge relative /var/tmp/ex-script-snippet.conf
load complete
```

For more information about the **load** command, see the CLI User Guide.

## Documentation Conventions

Table 1 on page xvii defines notice icons used in this guide.

Table 1: Notice Icons





Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.

Table 2 on page xvii defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
<b>Bold text like this</b>	Represents text that you type.	To enter configuration mode, type the <b>configure</b> command:  user@host> <b>configure</b>
Fixed-width text like this	Represents output that appears on the terminal screen.	user@host> <b>show chassis alarms</b> No alarms currently active



Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
<i>Italic text like this</i>	<ul style="list-style-type: none"> <li>Introduces or emphasizes important new terms.</li> <li>Identifies book names.</li> <li>Identifies RFC and Internet draft titles.</li> </ul>	<ul style="list-style-type: none"> <li>A policy <i>term</i> is a named structure that defines match conditions and actions.</li> <li><i>Junos OS System Basics Configuration Guide</i></li> <li>RFC 1997, <i>BGP Communities Attribute</i></li> </ul>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name:  [edit] root@# <b>set system domain-name</b> <i>domain-name</i>
<b>Text like this</b>	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none"> <li>To configure a stub area, include the <b>stub</b> statement at the [edit protocols ospf area area-id] hierarchy level.</li> <li>The console port is labeled <b>CONSOLE</b>.</li> </ul>
< > (angle brackets)	Enclose optional keywords or variables.	<b>stub &lt;default-metric metric&gt;;</b>
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	<b>broadcast   multicast</b>  <i>(string1   string2   string3)</i>
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	<b>rsvp { # Required for dynamic MPLS only</b>
[ ] (square brackets)	Enclose a variable for which you can substitute one or more values.	<b>community name members [ community-ids ]</b>
Indentation and braces ( { } )	Identify a level in the configuration hierarchy.	[edit] routing-options { static { route default { nexthop <i>address</i> ; retain; } } }
;(semicolon)	Identifies a leaf statement at a configuration hierarchy level.	
<b>J-Web GUI Conventions</b>		
<b>Bold text like this</b>	Represents J-Web graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none"> <li>In the Logical Interfaces box, select <b>All Interfaces</b>.</li> <li>To cancel the configuration, click <b>Cancel</b>.</li> </ul>
> (bold right angle bracket)	Separates levels in a hierarchy of J-Web selections.	In the configuration editor hierarchy, select <b>Protocols&gt;Ospf</b> .



## Documentation Feedback

---

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation. You can send your comments to [techpubs-comments@juniper.net](mailto:techpubs-comments@juniper.net), or fill out the documentation feedback form at <https://www.juniper.net/cgi-bin/docbugreport/>. If you are using e-mail, be sure to include the following information with your comments:

- Document or topic name
- URL or page number
- Software release version (if applicable)

## Requesting Technical Support

---

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or JNASC support contract, or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <http://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

## Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Search for known bugs: <http://www2.juniper.net/kb/>
- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>
- Download the latest versions of software and review release notes: <http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <https://www.juniper.net/alerts/>



- Join and participate in the Juniper Networks Community Forum:  
<http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://tools.juniper.net/SerialNumberEntitlementSearch/>

## Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <http://www.juniper.net/support/requesting-support.html>.



## PART 1

# Overview

- [Introduction to Stateless Firewall Filters on page 3](#)
- [Standard Firewall Filters Overview on page 17](#)
- [Standard Firewall Filter Match Conditions Overview on page 29](#)
- [Introduction to Standard Firewall Filters for Fragment Handling on page 45](#)
- [Introduction to Standard Firewall Filters Configuration on page 47](#)
- [Introduction to Service Filters Configuration on page 65](#)
- [Introduction to Simple Filters Configuration on page 75](#)
- [Introduction to Firewall Filters Configuration in Logical Systems on page 83](#)







## CHAPTER 1

# Introduction to Stateless Firewall Filters

- [Router Data Flow Overview on page 3](#)
- [Stateless Firewall Filter Overview on page 5](#)
- [Stateless Firewall Filter Types on page 6](#)
- [Stateless Firewall Filter Components on page 7](#)
- [Stateless Firewall Filter Application Points on page 13](#)

## Router Data Flow Overview

---

The Junos<sup>®</sup> OS provides a *policy framework*, which is a collection of Junos OS policies that enable you to control flows of routing information and packets within the router.

- [Flow of Routing Information on page 3](#)
- [Flow of Data Packets on page 4](#)
- [Flow of Local Packets on page 4](#)
- [Interdependent Flows of Routing Information and Packets on page 4](#)

## Flow of Routing Information

*Routing information* is the information about routes learned by the routing protocols from a router's neighbors. This information is stored in routing tables. The routing protocols advertise active routes only from the routing tables. An *active route* is a route that is chosen from all routes in the routing table to reach a destination.

To control which routes the routing protocols place in the routing tables and which routes the routing protocols advertise from the routing tables, you can configure *routing policies*, which are sets of rules that the policy framework uses to preempt default routing policies.

The Routing Engine, which is the router's control plane, handles the flow of routing information between the routing protocols and the routing tables and between the routing tables and the forwarding table. The Routing Engine runs the Junos OS and routing policies and stores the active router configuration, the master routing table, and the master forwarding table,



## Flow of Data Packets

*Data packets* are chunks of data that transit the router as they are being forwarded from a source to a destination. When a router receives a data packet on an interface, it determines where to forward the packet by looking in the forwarding table for the best route to a destination. The router then forwards the data packet toward its destination through the appropriate interface.

The Packet Forwarding Engine, which is the router's forwarding plane, handles the flow of data packets in and out of the router's physical interfaces. Although the Packet Forwarding Engine contains Layer 3 and Layer 4 header information, it does not contain the packet data itself (the packet's payload).

## Flow of Local Packets


*Local packets* are chunks of data that are destined for or sent by the router. Local packets usually contain routing protocol data, data for IP services such as Telnet or SSH, and data for administrative protocols such as the Internet Control Message Protocol (ICMP). When the Routing Engine receives a local packet, it forwards the packet to the appropriate process or to the kernel, which are both part of the Routing Engine, or to the Packet Forwarding Engine.

The Routing Engine handles the flow of local packets from the router's physical interfaces and to the Routing Engine.

## Interdependent Flows of Routing Information and Packets

Figure 1 on page 4 illustrates the flow of data through a router. Although routing information flows and packet flows are very different from one another, they are also interdependent.

**Figure 1: Flows of Routing Information and Packets**



Routing policies determine which routes the Routing Engine places in the forwarding table. The forwarding table, in turn, has an integral role in determining the appropriate physical interface through which to forward a packet.

### Related Documentation

- [Stateless Firewall Filter Overview on page 5](#)
- "Packet Flow Within Routers Overview" in the Junos OS Class of Service Configuration Guide



- “Understanding BGP Path Selection” in the Junos OS Routing Protocols Configuration Guide
- “Understanding Route Preference Values” in the Junos OS Routing Protocols Configuration Guide
- “Understanding Routing Policies” in the Routing Policy Configuration Guide

## Stateless Firewall Filter Overview

---

This topic covers the following information:

- [Packet Flow Control on page 5](#)
- [Stateless and Stateful Firewall Filters on page 5](#)
- [Purpose of Stateless Firewall Filters on page 6](#)

### Packet Flow Control

To influence which packets are allowed to transit the system and to apply special actions to packets as necessary, you can configure *stateless firewall filters*. A stateless firewall specifies a sequence of one or more packet-filtering rules, called *filter terms*. A filter term specifies *match conditions* to use to determine a match and *actions* to take on a matched packet. A stateless firewall filter enables you to manipulate any packet of a particular protocol family, including fragmented packets, based on evaluation of Layer 3 and Layer 4 header fields. You typically apply a stateless firewall filter to one or more interfaces that have been configured with protocol family features. You can apply a stateless firewall filter to an ingress interface, an egress interface, or both.

#### Data Packet Flow Control

---

To control the flow of data packets transiting the device as the packets are being forwarded from a source to a destination, you can apply stateless firewall filters to the input or output of the router's physical interfaces.

To enforce a specified bandwidth and maximum burst size for traffic sent or received on an interface, you can configure *policers*. Policers are a specialized type of stateless firewall filter and a primary component of the Junos OS *class-of-service* (CoS).

#### Local Packet Flow Control

---

To control the flow of local packets between the physical interfaces and the Routing Engine, you can apply stateless firewall filters to the input or output of the *loopback interface*. The loopback interface (**lo0**) is the interface to the Routing Engine and carries no data packets.

### Stateless and Stateful Firewall Filters

A stateless firewall filter, also known as an *access control list* (ACL), does not statefully inspect traffic. Instead, it evaluates packet contents statically and does not keep track of the state of network connections. In contrast, a *stateful firewall filter* uses connection



state information derived from other applications and past communications in the data flow to make dynamic control decisions.

The Junos OS Firewall Filters and Traffic Policers Configuration Guide describes *stateless firewall filters* supported on T Series, M Series, and MX Series routers.

## Purpose of Stateless Firewall Filters

The basic purpose of a stateless firewall filter is to enhance security through the use of packet filtering. Packet filtering enables you to inspect the components of incoming or outgoing packets and then perform the actions you specify on packets that match the criteria you specify. The typical use of a stateless firewall filter is to protect the Routing Engine processes and resources from malicious or untrusted packets.

### Related Documentation

- [Router Data Flow Overview on page 3](#)
- [Stateless Firewall Filter Types on page 6](#)
- “Traffic Policing Overview” in the Junos OS Firewall Filters and Traffic Policers Configuration Guide
- “Packet Flow Through the CoS Process Overview” in the Junos OS Class of Service Configuration Guide

## Stateless Firewall Filter Types

---

This topic covers the following information:

- [Standard Stateless Firewall Filters on page 6](#)
- [Service Filters on page 7](#)
- [Simple Filters on page 7](#)

## Standard Stateless Firewall Filters

The Junos OS standard stateless firewall filters support a rich set of packet-matching criteria that you can use to match on specific traffic and perform specific actions, such as forwarding or dropping packets that match the criteria you specify. You can configure firewall filters to protect the local router or to protect another device that is either directly or indirectly connected to the local router. For example, you can use the filters to restrict the local packets that pass from the router's physical interfaces to the Routing Engine. Such filters are useful in protecting the IP services that run on the Routing Engine, such as Telnet, SSH, and BGP, from denial-of-service attacks.



**NOTE:** If you configured targeted broadcast for virtual routing and forwarding (VRF) by including the `forward-and-send-to-re` statement, any firewall filter that is configured on the Routing Engine loopback interface (lo0) cannot be applied to the targeted broadcast packets that are forwarded to the Routing Engine. This is because broadcast packets are forwarded as flood next hop traffic and not as local next hop traffic, and you can only apply a firewall filter to local next hop routes for traffic directed toward the Routing Engine.

---



## Service Filters

A service filter defines packet-filtering (a set of match conditions and a set of actions) for IPv4 or IPv6 traffic. You can apply a service filter to the inbound or outbound traffic at an adaptive services interface to perform packet filtering on traffic before it is accepted for service processing. You can also apply a service filter to the traffic that is returning to the services interface after service processing to perform postservice processing.

Service filters filter IPv4 and IPv6 traffic only and can be applied to logical interfaces on Adaptive Services PICs, MultiServices PICs, and MultiServices DPCs only. Service filters are not supported on J Series devices and Branch SRX devices.

## Simple Filters

Simple filters are supported on Gigabit Ethernet intelligent queuing (IQ2) and Enhanced Queuing Dense Port Concentrator (EQ DPC) interfaces only. Unlike standard filters, simple filters support IPv4 traffic only and have a number of restrictions. For example, you cannot configure a terminating action for a simple filter. Simple filters always accept packets. Also, simple filters can be applied only as input filters. They are not supported on outbound traffic. Simple filters are recommended for metropolitan Ethernet applications.

### Related Documentation

- [Stateless Firewall Filter Overview on page 5](#)
- [Stateless Firewall Filter Components on page 7](#)

---

## Stateless Firewall Filter Components

This topic covers the following information:

- [Protocol Family on page 7](#)
- [Filter Type on page 8](#)
- [Terms on page 9](#)
- [Match Conditions on page 10](#)
- [Actions on page 11](#)

## Protocol Family

Under the **firewall** statement, you can specify the protocol family for which you want to filter traffic.

[Table 3 on page 8](#) describes the firewall filter protocol families.



Table 3: Firewall Filter Protocol Families

Type of Traffic to Be Filtered	Protocol Family Configuration Statement	Comments
Protocol Independent	<b>family any</b>	All protocol families configured on a logical interface.
Internet Protocol version 4 (IPv4)	<b>family inet</b>	The <b>family inet</b> statement is optional for IPv4.
Internet Protocol version 6 (IPv6)	<b>family inet6</b>	
MPLS	<b>family mpls</b>	
MPLS-tagged IPv4	<b>family mpls</b>	Supports matching on IP addresses and ports, up to five MPLS stacked labels.
MPLS-tagged IPv6	<b>family mpls</b>	Supports matching on IP addresses and ports, up to five MPLS stacked labels.
Virtual private LAN service (VPLS)	<b>family vpls</b>	
Layer 2 Circuit Cross-Connection	<b>family ccc</b>	
Layer 2 Bridging	<b>family bridge</b>	MX Series routers only.

## Filter Type

Under the **family *family-name*** statement, you can specify the type and name of the filter you want to configure.

[Table 4 on page 9](#) describes the firewall filter types.



Table 4: Filter Types

Filter Type	Filter Configuration Statement	Description
Stateless Firewall Filter	<b>filter</b> <i>filter-name</i>	<p>Filters the following traffic types:</p> <ul style="list-style-type: none"> <li>• Protocol independent</li> <li>• IPv4</li> <li>• IPv6</li> <li>• MPLS</li> <li>• MPLS-tagged IPv4</li> <li>• MPLS-tagged IPv6</li> <li>• VPLS</li> <li>• Layer 2 CCC</li> <li>• Layer 2 bridging (MX Series routers only)</li> </ul>
Service Filter	<b>service-filter</b> <i>service-filter-name</i>	<p>Defines packet-filtering to be applied to ingress or egress before it is accepted for service processing or applied to returning service traffic after service processing has completed.</p> <p>Filters the following traffic types:</p> <ul style="list-style-type: none"> <li>• IPv4</li> <li>• IPv6</li> </ul> <p>Supported at logical interfaces configured on the following hardware only:</p> <ul style="list-style-type: none"> <li>• Adaptive Services (AS) PICs on M Series and T Series routers</li> <li>• Multiservices (MS) PICs on M Series and T Series routers</li> <li>• Multiservices (MS) DPCs on MX Series routers</li> </ul>
Simple Filter	<b>simple-filter</b> <i>simple-filter-name</i>	<p>Defines packet filtering to be applied to ingress traffic only.</p> <p>Filters the following traffic type:</p> <ul style="list-style-type: none"> <li>• IPv4</li> </ul> <p>Supported at logical interfaces configured on the following hardware only:</p> <ul style="list-style-type: none"> <li>• Gigabit Ethernet Intelligent Queuing (IQ2) PICs installed on M120, M320, or T Series routers</li> <li>• Enhanced Queuing Dense Port Concentrators (EQ DPCs) installed on MX Series routers</li> </ul>

## Terms

Under the **filter**, **service-filter**, or **simple-filter** statement, you must configure at least one firewall filter *term*. A term is a named structure in which match conditions and actions are defined. Within a firewall filter, you must configure a unique name for each term.





**TIP:** You cannot apply a different filter on each direction of traffic on the same interface. As a result, it is common to create firewall filters with multiple terms.

All stateless firewall filters contain one or more terms, and each term consists of two components—match conditions and actions. The match conditions define the values or fields that the packet must contain to be considered a match. If a packet is a match, the corresponding action is taken. By default, a packet that does not match a firewall filter is discarded.

If a packet arrives on an interface for which no firewall filter is applied for the incoming traffic on that interface, the packet is accepted by default.



**NOTE:** A firewall filter with a large number of terms can adversely affect both the configuration commit time and the performance of the Routing Engine.

Additionally, you can configure a stateless firewall filter within the term of another filter. This method enables you to add common terms to multiple filters without having to modify all filter definitions. You can configure one filter with the desired common terms, and configure this filter as a term in other filters. Consequently, to make a change in these common terms, you need to modify only one filter that contains the common terms, instead of multiple filters.

## Match Conditions

A firewall filter term must contain at least one packet-filtering criteria, called a *match condition*, to specify the field or value that a packet must contain in order to be considered a match for the firewall filter term. For a match to occur, the packet must match all the conditions in the term. If a packet matches a firewall filter term, the router takes the configured action on the packet.

If a firewall filter term contains multiple match conditions, a packet must meet *all* match conditions to be considered a match for the firewall filter term.

If a single match condition is configured with multiple values, such as a range of values, a packet must match only *one* of the values to be considered a match for the firewall filter term.

The scope of match conditions you can specify in a firewall filter term depends on the protocol family under which the firewall filter is configured. You can define various match conditions, including the IP source address field, IP destination address field, TCP or UDP source port field, IP protocol field, Internet Control Message Protocol (ICMP) packet type, IP options, TCP flags, incoming logical or physical interface, and outgoing logical or physical interface.

Each protocol family supports a different set of match conditions, and some match conditions are supported only on certain routing devices. For example, a number of match conditions for VPLS traffic are supported only on the MX Series 3D Universal Edge Routers.



In the **from** statement in a firewall filter term, you specify characteristics that the packet must have for the action in the subsequent **then** statement to be performed. The characteristics are referred to as *match conditions*. The packet must match all conditions in the **from** statement for the action to be performed, which also means that the order of the conditions in the **from** statement is not important.

If an individual match condition can specify a list of values (such as multiple source and destination addresses) or a range of numeric values, a match occurs if any of the values matches the packet.

If a filter term does not specify match conditions, the term accepts all packets and the actions specified in the term's **then** statement are optional.



**NOTE:**

Some of the numeric range and bit-field match conditions allow you to specify a text synonym. For a complete list of synonyms:

- If you are using the J-Web interface, select the synonym from the appropriate list.
- If you are using the CLI, type a question mark (?) after the **from** statement.

## Actions

The actions specified in a firewall filter term define the actions to take for any packet that matches the conditions specified in the term.

Actions that are configured within a single term are all taken on traffic that matches the conditions configured.



**BEST PRACTICE:** We strongly recommend that you explicitly configure one or more actions per firewall filter term. Any packet that matches all the conditions of the term is automatically accepted unless the term specifies other or additional actions.

Firewall filter actions fall into the following categories:

### Filter-Terminating Actions

---

A filter-terminating action halts all evaluation of a firewall filter for a specific packet. The router performs the specified action, and no additional terms are examined.

### Nonterminating Actions

---

Nonterminating actions are used to perform other functions on a packet, such as incrementing a counter, logging information about the packet header, sampling the packet data, or sending information to a remote host using the system log functionality.



The presence of a nonterminating action, such as **count**, **log**, or **syslog**, without an explicit terminating action, such as **accept**, **discard**, or **reject**, results in a default terminating action of **accept**. If you do not want the firewall filter action to terminate, use the **next term** action after the nonterminating action.

In this example, term 2 is never evaluated, because term 1 has the implicit default **accept** terminating action.

```
[edit firewall filter test]
term 1 {
  from {
    source-address {
      0.0.0.0/0;
    }
  }
  then {
    log;
    <accept> #By default if not specified
  }
}
term 2 {
  then {
    reject;
  }
}
```

In this example, term 2 is evaluated, because term 1 has the explicit **next term** flow control action.

```
[edit firewall filter test]
term 1 {
  from {
    source-address {
      0.0.0.0/0;
    }
  }
  then {
    log;
    next term;
  }
}
term 2 {
  then {
    reject;
  }
}
```

---

### Flow Control Action

For standard stateless firewall filters only, the action **next term** enables the router to perform configured actions on the packet and then evaluate the following term in the filter, rather than terminating the filter.

A maximum of 1024 **next term** actions are supported per standard stateless firewall filter configuration. If you configure a standard filter that exceeds this limit, your candidate configuration results in a commit error.



- Related Documentation**
- [Stateless Firewall Filter Types on page 6](#)
  - “Inserting a New Identifier in a Junos Configuration” in the CLI User Guide

## Stateless Firewall Filter Application Points

---

After you define the firewall filter, you must apply it to an application point. These application points include logical interfaces, physical interfaces, routing interfaces, and routing instances.

In most cases, you can apply a firewall filter as an *input* filter or an *output* filter, or both at the same time. Input filters take action on packets being received on the specified interface, whereas output filters take action on packets that are transmitted through the specified interface.

You typically apply one filter with multiple terms to a single logical interface, to incoming traffic, outbound traffic, or both. However, there are times when you might want to chain together multiple firewall filters (with single or multiple terms) and apply them to an interface. You use an *input list* to apply multiple firewall filters to the incoming traffic on an interface. You use an *output list* to apply multiple firewall filters to the outbound traffic on an interface. You can include up to 16 filters in an input list or an output list.

There is no limit to the number of filters and counters you can set, but there are some practical considerations. More counters require more terms, and a large number of terms can take a long time to process during a commit operation. However, filters with more than 4000 terms and counters have been implemented successfully.

[Table 5 on page 14](#) describes each point to which you can apply a firewall filter. For each application point, the table describes the types of firewall filters supported at that point, the router hierarchy level at which the filter can be applied, and any platform-specific limitations.



Table 5: Stateless Firewall Filter Configuration and Application Summary

Filter Type	Application Point	Restrictions
<p><b>Stateless firewall filter</b></p> <p>Configure by including the <b>filter <i>filter-name</i></b> statement the <b>[edit firewall]</b> hierarchy level:</p> <pre>filter <i>filter-name</i>;</pre> <p><b>NOTE:</b> If you do not include the <b>family</b> statement, the firewall filter processes IPv4 traffic by default.</p>	<p><b>Logical interface</b></p> <p>Apply at the <b>[edit interfaces <i>interface-name</i> unit <i>unit-number</i> family inet]</b> hierarchy level by including the <b>input <i>filter-name</i></b> or <b>output <i>filter-name</i></b> statements:</p> <pre>filter {   input <i>filter-name</i>;   output <i>filter-name</i>; }</pre> <p><b>NOTE:</b> A filter configured with the implicit <b>inet</b> protocol family cannot be included in an input filter list or an output filter list.</p> <p><b>NOTE:</b> On T4000 Type 5 FPCs, a filter attached at the Layer 2 application point (that is, at the logical interface level) is unable to match with the forwarding class of a packet that is set by a Layer 3 classifier such as DSCP, DSCP V6, <b>inet-precedence</b>, and <b>mpls-exp</b>.</p>	<p>Supported on the following routers:</p> <ul style="list-style-type: none"> <li>• T Series routers</li> <li>• M320 routers</li> <li>• M7i routers with the enhanced CFEB (CFEB-e)</li> <li>• M10i routers with the enhanced CFEB-e</li> </ul> <p>Also supported on the following Modular Port Concentrators (MPCs) on MX Series routers:</p> <ul style="list-style-type: none"> <li>• 10-Gigabit Ethernet MPC</li> <li>• 60-Gigabit Ethernet Queuing MPC</li> <li>• 60-Gigabit Ethernet Enhanced Queuing MPC</li> <li>• 100-Gigabit Ethernet MPC</li> </ul>
<p><b>Stateless firewall filter</b></p> <p>Configure at the <b>[edit firewall family <i>family-name</i>]</b> hierarchy level by including the following statement:</p> <pre>filter <i>filter-name</i>;</pre> <p>The <b><i>family-name</i></b> can be any of the following protocol families:</p> <ul style="list-style-type: none"> <li>• any</li> <li>• bridge</li> <li>• ccc</li> <li>• inet</li> <li>• inet6</li> <li>• mpls</li> <li>• vpls</li> </ul>	<p><b>Protocol family on a logical interface</b></p> <p>Apply at the <b>[edit interfaces <i>interface-name</i> unit <i>unit-number</i> family <i>family-name</i>]</b> hierarchy level by, including the <b>input</b>, <b>input-list</b>, <b>output</b>, or <b>output-list</b> statements:</p> <pre>filter {   input <i>filter-name</i>;   input-list [ <i>filter-names</i> ];   output <i>filter-name</i>;   output-list [ <i>filter-names</i> ]; }</pre>	<p>The protocol family <b>bridge</b> is supported only on MX Series routers.</p>
Stateless firewall filter	Routing Engine loopback interface	



Table 5: Stateless Firewall Filter Configuration and Application Summary (*continued*)

Filter Type	Application Point	Restrictions
<p><b>Service filter</b></p> <p>Configure at the [edit firewall family (inet   inet6)] hierarchy level by including the following statement:</p> <pre>service-filter   service-filter-name;</pre>	<p><b>Family inet or inet6 on a logical interface</b></p> <p>Apply at the [edit interfaces <i>interface-name</i> unit <i>unit-number</i> family (inet   inet6)] hierarchy level by using the <b>service-set</b> statement to apply a service filter as an input or output filter to a service set:</p> <pre>service {   input {     service-set service-set-name     service-filter filter-name;   }   output {     service-set service-set-name     service-filter filter-name;   } }</pre> <p>Configure a service set at the [edit services] hierarchy level by including the following statement:</p> <pre>service-set service-set-name;</pre>	Supported only on Adaptive Services (AS) and Multiservices (MS) PICs.
<p><b>Postservice filter</b></p> <p>Configure at the [edit firewall family (inet   inet6)] hierarchy level by including the following statement:</p> <pre>service-filter   service-filter-name;</pre>	<p><b>Family inet or inet6 on a logical interface</b></p> <p>Apply at the [edit interfaces <i>interface-name</i> unit <i>unit-number</i> family (inet   inet6)] hierarchy level by including the <b>post-service-filter</b> statement to apply a service filter as an input filter:</p> <pre>service {   input {     post-service-filter filter-name;   } }</pre>	A postservice filter is applied to traffic returning to the services interface after service processing. The filter is applied only if a service set is configured and selected.
<p><b>Simple filter</b></p> <p>Configure at the [edit firewall family inet] hierarchy level by including the following statement:</p> <pre>simple-filter filter-name</pre>	<p><b>Family inet on a logical interface</b></p> <p>Apply at the [edit interfaces <i>interface-name</i> unit <i>unit-number</i> family inet] hierarchy level by including the following statement:</p> <pre>simple-filter simple-filter-name;</pre>	<p>Simple filters can only be applied as input filters.</p> <p>Supported on the following platforms only:</p> <ul style="list-style-type: none"> <li>Gigabit Ethernet intelligent queuing (IQ2) PICs on the M120, M320, and T Series routers.</li> <li>Enhanced Queuing Dense Port Concentrators (EQ DPC) on MX Series routers.</li> </ul>



Table 5: Stateless Firewall Filter Configuration and Application Summary (*continued*)

Filter Type	Application Point	Restrictions
<b>Reverse packet forwarding (RPF) check filter</b>  Configured at the <code>[edit firewall family (inet   inet6)]</code> hierarchy level by including the following statement:  <code>filter <i>filter-name</i>;</code>	<b>Family inet or inet6 on a logical interface</b>  Apply at the <code>[edit interfaces <i>interface-name</i> unit <i>unit-number</i> family (inet   inet6)]</code> hierarchy level by including the following statement:  <code>    rpf-check fail-filter <i>filter-name</i></code>  to apply the stateless firewall filter as an RPF check filter.  <pre> rpf-check {   fail-filter <i>filter-name</i>;   mode loose; } </pre>	Supported on MX Series routers only.

- Related Documentation**
- [Stateless Firewall Filter Components on page 7](#)
  - [Supported Standards for Filtering on page 251](#)



## CHAPTER 2

# Standard Firewall Filters Overview

- [Standard Stateless Firewall Filter Overview on page 17](#)
- [How Standard Firewall Filters Evaluate Packets on page 18](#)
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Guidelines for Applying Standard Firewall Filters on page 25](#)
- [Understanding How to Use Standard Firewall Filters on page 27](#)

## Standard Stateless Firewall Filter Overview

---

Firewall filters provide a means of protecting your router from excessive traffic transiting the router to a network destination or destined for the Routing Engine. Firewall filters that control local packets can also protect your router from external incidents.

You can configure a firewall filter to do the following:

- Restrict traffic destined for the Routing Engine based on its source, protocol, and application.
- Limit the traffic rate of packets destined for the Routing Engine to protect against flood, or denial-of-service (DoS) attacks.
- Address special circumstances associated with fragmented packets destined for the Routing Engine. Because the device evaluates every packet against a firewall filter (including fragments), you must configure the filter to accommodate fragments that do not contain packet header information. Otherwise, the filter discards all but the first fragment of a fragmented packet.

### Related Documentation

- [Stateless Firewall Filter Types on page 6](#)
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Guidelines for Applying Standard Firewall Filters on page 25](#)
- [Understanding How to Use Standard Firewall Filters on page 27](#)



## How Standard Firewall Filters Evaluate Packets

---

This topic covers the following information:

- [Firewall Filters That Contain a Single Term on page 18](#)
- [Firewall Filters That Contain Multiple Terms on page 18](#)
- [Firewall Filter Terms That Do Not Contain Any Match Conditions on page 19](#)
- [Firewall Filter Terms That Do Not Contain Any Actions on page 19](#)
- [Firewall Filter Default Action on page 19](#)

### Firewall Filters That Contain a Single Term

For a standard stateless firewall filter that consists of a single term, the policy framework software evaluates a packet as follows:

- If the packet matches all the conditions, the actions are taken.
- If the packet matches all the conditions and no actions are specified, the packet is accepted.
- If the packet does not match all the conditions, it is discarded.



**NOTE:** When the device compares the stateless firewall filter match conditions to a packet, it compares only the header fields specified in the match condition. There is no implied protocol match. For example, if you specify a match of destination-port ssh, the device checks for a value of 0x22 in the 2-byte field that is two bytes after the IP packet header. The protocol field of the packet is not checked.

---

### Firewall Filters That Contain Multiple Terms

For a standard stateless firewall filter that consists of multiple terms, the policy framework software evaluates a packet against the terms in the filter sequentially, beginning with the first term in the filter, until either the packet matches all the conditions in one of the terms or there are no more terms in the filter.

- If the packet matches all the conditions in a term, the actions in that term are performed.
- Unlike service filters and simple filters, standard stateless firewall filters support the **next term** action, which is neither a terminating action nor a nonterminating action but a flow control action.:
  - If the actions do not include the **next term** action, evaluation of the packet ends at this term of the filter, and any subsequent terms in the filter are not used.
  - If the actions include the **next term** action, the evaluation continues to the next term.



- If the packet does not match all the conditions in the term, evaluation of the packet proceeds to the next term in the filter.
- Evaluation of the packet continues until either the packet matches a term without **next term** action or until the end of the filter is reached.

A maximum of 1024 **next term** actions are supported per standard stateless firewall filter configuration. If you configure a standard filter that exceeds this limit, your candidate configuration results in a commit error.

## Firewall Filter Terms That Do Not Contain Any Match Conditions

For standard stateless filters with a single term and for standard stateless firewall filters with multiple terms, if a term does not specify any match conditions, the actions are taken on any packet evaluated.

## Firewall Filter Terms That Do Not Contain Any Actions

If a standard stateless firewall filter term does not contain any actions, and if the packet matches the conditions in the term, the packet is accepted.

## Firewall Filter Default Action

Each standard stateless firewall filter has an *implicit* **discard** action at the end of the filter, which is equivalent to including the following example term **explicit\_discard** as the final term in the standard stateless firewall filter:

```
term explicit_discard {  
    then discard;  
}
```

By default, if a packet matches none of the terms in a standard stateless firewall filter, the packet is discarded.

### Related Documentation

- [How Service Filters Evaluate Packets on page 67](#)
- [How Simple Filters Evaluate Packets on page 75](#)
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Understanding How to Use Standard Firewall Filters on page 27](#)

## Guidelines for Configuring Standard Firewall Filters

This topic covers the following information:

- [Statement Hierarchy for Configuring Standard Firewall Filters on page 20](#)
- [Standard Firewall Filter Protocol Families on page 20](#)
- [Standard Firewall Filter Names and Options on page 21](#)
- [Standard Firewall Filter Terms on page 21](#)
- [Standard Firewall Filter Match Conditions on page 22](#)
- [Standard Firewall Filter Actions on page 23](#)



## Statement Hierarchy for Configuring Standard Firewall Filters

To configure a standard firewall filter, you can include the following statements. For an IPv4 standard firewall filter, the **family inet** statement is optional.

```
firewall {  
  family family-name {  
    filter filter-name {  
      accounting-profile name;  
      interface-specific;  
      physical-interface-filter;  
      term term-name {  
        filter filter-name;  
      }  
      term term-name {  
        from {  
          match-conditions;  
          ip-version ipv4 {  
            match-conditions;  
            protocol (tcp | udp) {  
              match conditions;  
            }  
          }  
        }  
        then {  
          actions;  
        }  
      }  
    }  
  }  
}
```

You can include the firewall configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**



**NOTE:** For stateless firewall filtering, you must allow the output tunnel traffic through the firewall filter applied to input traffic on the interface that is the next-hop interface toward the tunnel destination. The firewall filter affects only the packets exiting the router by way of the tunnel.

---

## Standard Firewall Filter Protocol Families

A standard firewall filter configuration is specific to a particular protocol family. Under the **firewall** statement, include one of the following statements to specify the protocol family for which you want to filter traffic:

- **family any**—To filter protocol-independent traffic.
- **family inet**—To filter Internet Protocol version 4 (IPv4) traffic.



- **family inet6**—To filter Internet Protocol version 6 (IPv6) traffic.
- **family mpls**—To filter MPLS traffic.
- **family vpls**—To filter virtual private LAN service (VPLS) traffic.
- **family ccc**—To filter Layer 2 circuit cross-connection (CCC) traffic.
- **family bridge**—To filter Layer 2 bridging traffic for MX Series 3D Universal Edge Routers only.

The **family *family-name*** statement is required only to specify a protocol family other than IPv4. To configure an IPv4 firewall filter, you can configure the filter at the **[edit firewall]** hierarchy level without including the **family inet** statement, because the **[edit firewall]** and **[edit firewall family inet]** hierarchy levels are equivalent.

## Standard Firewall Filter Names and Options

Under the **family *family-name*** statement, you can include **filter *filter-name*** statements to create and name standard firewall filters. The filter name can contain letters, numbers, and hyphens (-) and be up to 64 characters long. To include spaces in the name, enclose the entire name in quotation marks (" ").

At the **[edit firewall family *family-name* filter *filter-name*]** hierarchy level, the following statements are optional:

- **accounting-profile**
- **interface-specific**
- **physical-interface-filter**

## Standard Firewall Filter Terms

Under the **filter *filter-name*** statement, you can include **term *term-name*** statements to create and name filter terms.

- You must configure at least one term in a firewall filter.
- You must specify a unique name for each term within a firewall filter. The term name can contain letters, numbers, and hyphens (-) and can be up to 64 characters long. To include spaces in the name, enclose the entire name in quotation marks (" ").
- The order in which you specify terms within a firewall filter configuration is important. Firewall filter terms are evaluated in the order in which they are configured. By default, new terms are always added to the end of the existing filter. You can use the **insert** configuration mode command to reorder the terms of a firewall filter.

At the **[edit firewall family *family-name* filter *filter-name* term *term-name*]** hierarchy level, the **filter *filter-name*** statement is not valid in the same term as **from** or **then** statements. When included at this hierarchy level, the **filter *filter-name*** statement is used to *nest* firewall filters.



## Standard Firewall Filter Match Conditions

Standard firewall filter match conditions are specific to the type of traffic being filtered.

With the exception of MPLS-tagged IPv4 or IPv6 traffic, you specify the term's match conditions under the **from** statement. For MPLS-tagged IPv4 traffic, you specify the term's IPv4 address-specific match conditions under the **ip-version ipv4** statement and the term's IPv4 port-specific match conditions under the **protocol (tcp | udp)** statement.

For MPLS-tagged IPv6 traffic, you specify the term's IPv6 address-specific match conditions under the **ip-version ipv6** statement and the term's IPv6 port-specific match conditions under the **protocol (tcp | udp)** statement.

[Table 6 on page 22](#) describes the types of traffic for which you can configure standard stateless firewall filters.

**Table 6: Standard Firewall Filter Match Conditions by Protocol Family**

Traffic Type	Hierarchy Level at Which Match Conditions Are Specified
Protocol-independent	<p><b>[edit firewall family any filter <i>filter-name</i> term <i>term-name</i>]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for Protocol-Independent Traffic” on page 257.</p>
IPv4	<p><b>[edit firewall family inet filter <i>filter-name</i> term <i>term-name</i>]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for IPv4 Traffic” on page 258.</p>
IPv6	<p><b>[edit firewall family inet6 filter <i>filter-name</i> term <i>term-name</i>]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for IPv6 Traffic” on page 267.</p>
MPLS	<p><b>[edit firewall family mpls filter <i>filter-name</i> term <i>term-name</i>]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for MPLS Traffic” on page 274.</p>
IPv4 addresses in MPLS flows	<p><b>[edit firewall family mpls filter <i>filter-name</i> term <i>term-name</i> ip-version ipv4 ]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic” on page 276.</p>
IPv4 ports in MPLS flows	<p><b>[edit firewall family mpls filter <i>filter-name</i> term <i>term-name</i> ip-version ipv4 protocol (tcp   udp)]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic” on page 276.</p>
IPv6 addresses in MPLS flows	<p><b>[edit firewall family mpls filter <i>filter-name</i> term <i>term-name</i> ip-version ipv6 ]</b></p> <p>For the complete list of match conditions, see “Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic” on page 276.</p>



**Table 6: Standard Firewall Filter Match Conditions by Protocol Family (*continued*)**

Traffic Type	Hierarchy Level at Which Match Conditions Are Specified
IPv6 ports in MPLS flows	<p><b>[edit firewall family mpls filter <i>filter-name</i> term <i>term-name</i> ip-version ipv6 protocol (tcp   udp)]</b></p> <p>For the complete list of match conditions, see “<a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic</a>” on page 276.</p>
VPLS	<p><b>[edit firewall family vpls filter <i>filter-name</i> term <i>term-name</i>]</b></p> <p>For the complete list of match conditions, see “<a href="#">Standard Firewall Filter Match Conditions for VPLS Traffic</a>” on page 278.</p>
Layer 2 CCC	<p><b>[edit firewall family ccc filter <i>filter-name</i> term <i>term-name</i>]</b></p> <p>For the complete list of match conditions, see “<a href="#">Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic</a>” on page 285.</p>
Layer 2 Bridging	<b>[edit firewall family bridge filter <i>filter-name</i> term <i>term-name</i>]</b>
(MX Series routers only)	For the complete list of match conditions, see “ <a href="#">Standard Firewall Filter Match Conditions for Layer 2 Bridging Traffic</a> ” on page 287.

If you specify an IPv6 address in a match condition (the **address**, **destination-address**, or **source-address** match conditions), use the syntax for text representations described in RFC 2373, *IP Version 6 Addressing Architecture*. For more information about IPv6 addresses, see “IPv6 Overview” and “IPv6 Standards” in the Junos OS Routing Protocols Configuration Guide.

## Standard Firewall Filter Actions

Under the **then** statement for a standard stateless firewall filter term, you can specify the actions to be taken on a packet that matches the term.

[Table 7 on page 24](#) summarizes the types of actions you can specify in a standard stateless firewall filter term.



Table 7: Standard Firewall Filter Action Categories

Type of Action	Description	Comment
Terminating	<p>Halts all evaluation of a firewall filter for a specific packet. The router performs the specified action, and no additional terms are used to examine the packet.</p> <p>You can specify only one <i>terminating action</i> in a standard firewall filter. You can, however, specify one terminating action with one or more <i>nonterminating actions</i> in a single term. For example, within a term, you can specify <b>accept</b> with <b>count</b> and <b>syslog</b>.</p>	See <a href="#">"Standard Firewall Filter Terminating Actions"</a> on page 293.
Nonterminating	<p>Performs other functions on a packet (such as incrementing a counter, logging information about the packet header, sampling the packet data, or sending information to a remote host using the system log functionality), but any additional terms are used to examine the packet.</p>	See <a href="#">"Standard Firewall Filter Nonterminating Actions"</a> on page 294.
Flow control	<p>For standard stateless firewall filters only, the <b>next term</b> action directs the router to perform configured actions on the packet and then, rather than terminate the filter, use the next term in the filter to evaluate the packet. If the <b>next term</b> action is included, the matching packet is evaluated against the next term in the firewall filter. Otherwise, the matching packet is not evaluated against subsequent terms in the firewall filter.</p> <p>For example, when you configure a term with the nonterminating action <b>count</b>, the term's action changes from an implicit <b>discard</b> to an implicit <b>accept</b>. The <b>next term</b> action forces the continued evaluation of the firewall filter.</p>	<p>You cannot configure the <b>next term</b> action with a terminating action in the same filter term. However, you can configure the next term action with another nonterminating action in the same filter term.</p> <p>A maximum of 1024 <b>next term</b> actions are supported per standard stateless firewall filter configuration. If you configure a standard filter that exceeds this limit, your candidate configuration results in a commit error.</p>

**Related Documentation**

- [Guidelines for Applying Standard Firewall Filters on page 25](#)
- [Understanding How to Use Standard Firewall Filters on page 27](#)



## Guidelines for Applying Standard Firewall Filters

This topic covers the following information:

- [Applying Standard Firewall Filters Overview on page 25](#)
- [Statement Hierarchy for Applying Standard Firewall Filters on page 25](#)
- [Restrictions on Applying Standard Firewall Filters on page 26](#)

### Applying Standard Firewall Filters Overview

You can apply a standard stateless firewall filter to a physical interface on the router or to the loopback interface on the router. You can apply a firewall filter to a single interface or to multiple interfaces on the router.

#### Applying a Firewall Filter to a Router's Physical Interfaces

When you apply a standard firewall filter to a physical interface on the router, the filter evaluates all data packet that pass through that interface.

#### Applying a Firewall Filter to the Router's Loopback Interface

The router's loopback interface, **lo0**, is the interface to the Routing Engine and carries no data packets. When you apply a standard firewall filter to the loopback interface, the filter evaluates the local packets received or transmitted by the Routing Engine.

#### Applying a Firewall Filter to Multiple Interfaces

You can use the same standard firewall filter one or more times.

On M Series routers, except the M120 and M320 routers, if you apply a firewall filter to multiple interfaces, the filter acts on the sum of traffic entering or exiting those interfaces.

On T Series, M120, M320, and MX Series routers, interfaces are distributed among multiple packet-forwarding components. On these routers, you can configure standard stateless firewall filters and service filters that, when applied to multiple interfaces, act on the individual traffic streams entering or exiting each interface, regardless of the sum of traffic on the multiple interfaces.

For more information, see [“Interface-Specific Firewall Filter Instances Overview” on page 55](#).

### Statement Hierarchy for Applying Standard Firewall Filters

To apply a standard stateless firewall filter to a logical interface, configure the **input *filter-name***, **input-list *filter-name***, **output *filter-name***, or **output-list *filter-name*** statements in the **filter** stanza for the logical interface protocol family.

```

interfaces {
  interface-name {
    unit logical-unit-number {
      family family-name {
        ...
        filter {

```



```
group group-number;
  input filter-name;
  input-list [ filter-names ];
  output filter-name;
  output-list [ filter-names ];
}
}
```

You can include the interface configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

## Restrictions on Applying Standard Firewall Filters

- [Number of Input and Output Filters Per Logical Interface on page 26](#)
- [MPLS and Layer 2 CCC Firewall Filters in Lists on page 26](#)
- [Layer 2 CCC Firewall Filters on MX Series Routers on page 27](#)
- [Protocol-Independent Firewall Filters on the Loopback Interface on page 27](#)

---

### Number of Input and Output Filters Per Logical Interface

**Input filters**—Although you can use the same filter multiple times, you can apply only one input filter or one input filter list to an interface.

- To specify a single firewall filter to be used to evaluate packets received on the interface, include the **input *filter-name*** statement in the **filter** stanza.
- To specify an ordered list of firewall filters to be used to evaluate packets received on the interface, include the **input-list [ *filter-names* ]** statement in the **filter** stanza. You can specify up to 16 firewall filters for the filter input list.

**Output filters**—Although you can use the same filter multiple times, you can apply only one output filter or one output filter list to an interface.

- To specify a single firewall filter to be used to evaluate packets transmitted on the interface, include the **output *filter-name*** statement in the **filter** stanza.
- To specify an ordered list of firewall filters to be used to evaluate packets transmitted on the interface, include the **output-list [ *filter-names* ]** statement in the **filter** stanza. You can specify up to 16 firewall filters in a filter output list.

---

### MPLS and Layer 2 CCC Firewall Filters in Lists

The **input-list *filter-names*** and **output-list *filter-names*** statements for firewall filters for the **ccc** and **mpls** protocol families are supported on all interfaces with the exception of the following:

- Management interfaces and internal Ethernet interfaces (**fxp** or **em0**)



- Loopback interfaces (**lo0**)
- USB modem interfaces (**umd**)

### Layer 2 CCC Firewall Filters on MX Series Routers

On MX Series routers only, you cannot apply a Layer 2 CCC stateless firewall filter (a firewall filter configured at the **[edit firewall filter family ccc]** hierarchy level) as an output filter. On MX Series routers, firewall filters configured for the **family ccc** statement can be applied only as input filters.

### Protocol-Independent Firewall Filters on the Loopback Interface

Protocol-independent firewall filters—stateless firewall filters configured at the **[edit firewall family any]** hierarchy level—are not supported on the router loopback interface (**lo0**).

#### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Understanding How to Use Standard Firewall Filters on page 27](#)

## Understanding How to Use Standard Firewall Filters

This topic covers the following information:

- [Using Standard Firewall Filters to Affect Local Packets on page 27](#)
- [Using Standard Firewall Filters to Affect Data Packets on page 28](#)

### Using Standard Firewall Filters to Affect Local Packets

On a router, you can configure one physical loopback interface, **lo0**, and one or more addresses on the interface. The loopback interface is the interface to the Routing Engine, which runs and monitors all the control protocols. The loopback interface carries local packets only. Standard firewall filters applied to the loopback interface affect the local packets destined for or transmitted from the Routing Engine.



**NOTE:** When you create an additional loopback interface, it is important to apply a filter to it so the Routing Engine is protected. We recommend that when you apply a filter to the loopback interface, you include the **apply-groups** statement. Doing so ensures that the filter is automatically inherited on every loopback interface, including **lo0** and other loopback interfaces.

### Trusted Sources

The typical use of a standard stateless firewall filter is to protect the Routing Engine processes and resources from malicious or untrusted packets. To protect the processes and resources owned by the Routing Engine, you can use a standard stateless firewall filter that specifies which protocols and services, or applications, are allowed to reach the Routing Engine. Applying this type of filter to the loopback interface ensures that the



local packets are from a trusted source and protects the processes running on the Routing Engine from an external attack.

### Flood Prevention

---

You can create standard stateless firewall filters that limit certain TCP and ICMP traffic destined for the Routing Engine. A router without this kind of protection is vulnerable to TCP and ICMP flood attacks, which are also called denial-of-service (DoS) attacks. For example:

- A TCP flood attack of SYN packets initiating connection requests can overwhelm the device until it can no longer process legitimate connection requests, resulting in denial of service.
- An ICMP flood can overload the device with so many echo requests (ping requests) that it expends all its resources responding and can no longer process valid network traffic, also resulting in denial of service.

Applying the appropriate firewall filters to the Routing Engine protects against these types of attacks.

## Using Standard Firewall Filters to Affect Data Packets

Standard firewall filters that you apply to your router's transit interfaces evaluate only the user data packets that transit the router from one interface directly to another as they are being forwarded from a source to a destination. To protect the network as a whole from unauthorized access and other threats at specific interfaces, you can apply firewall filters router transit interfaces .

### Related Documentation

- [How Standard Firewall Filters Evaluate Packets on page 18](#)
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Guidelines for Applying Standard Firewall Filters on page 25](#)



## CHAPTER 3

# Standard Firewall Filter Match Conditions Overview

- [Firewall Filter Match Conditions Based on Numbers or Text Aliases on page 29](#)
- [Firewall Filter Match Conditions Based on Bit-Field Values on page 30](#)
- [Firewall Filter Match Conditions Based on Address Fields on page 35](#)
- [Firewall Filter Match Conditions Based on Address Classes on page 43](#)

## Firewall Filter Match Conditions Based on Numbers or Text Aliases

---

This topic covers the following information:

- [Matching on a Single Numeric Value on page 29](#)
- [Matching on a Range of Numeric Values on page 29](#)
- [Matching on a Text Alias for a Numeric Value on page 30](#)
- [Matching on a List of Numeric Values or Text Aliases on page 30](#)

### Matching on a Single Numeric Value

You can specify a firewall filter match condition based on whether a particular packet field value is a specified numeric value. In the following example, a match occurs if the packet source port number is 25:

```
[edit firewall family inet filter filter1 term term1 from]
user@host# set source-port 25
```

### Matching on a Range of Numeric Values

You can specify a firewall filter match condition based on whether a particular packet field value falls within a specified range of numeric values. In the following example, a match occurs for source ports values from 1024 through 65,535, inclusive:

```
[edit firewall family inet filter filter2 term term1 from]
user@host# set source-port 1024-65535
```



## Matching on a Text Alias for a Numeric Value

You can specify a firewall filter match condition based on whether a particular packet field value is a numeric value that you specify by using a text string as an *alias* for the numeric value. In the following example, a match occurs if the packet source port number is 25. For the **source-port** and **destination-port** match conditions, the text alias **smtp** corresponds to the numeric value 25.

```
[edit firewall family inet filter filter3 term term1 from]
user@host# set source-port smtp
```

## Matching on a List of Numeric Values or Text Aliases

You can specify a firewall filter match condition based on whether a particular packet field value matches any one of multiple numeric values or text aliases that you specify within square brackets and delimited by spaces. In the following example, a match occurs if the packet source port number is any of the following values: 20 (which corresponds to the text aliases **ftp-data**), 25, or any value from 1024 through 65535.

```
[edit firewall family inet filter filter3 term term1 from]
user@host# set source-port [ smtp ftp-data 25 1024-65535 ]
```

### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Firewall Filter Match Conditions Based on Bit-Field Values on page 30](#)
- [Firewall Filter Match Conditions Based on Address Fields on page 35](#)
- [Firewall Filter Match Conditions Based on Address Classes on page 43](#)

---

## Firewall Filter Match Conditions Based on Bit-Field Values

- [Match Conditions for Bit-Field Values on page 30](#)
- [Match Conditions for Common Bit-Field Values or Combinations on page 31](#)
- [Logical Operators for Bit-Field Values on page 32](#)
- [Matching on a Single Bit-Field Value or Text Alias on page 33](#)
- [Matching on Multiple Bit-Field Values or Text Aliases on page 33](#)
- [Matching on a Negated Bit-Field Value on page 34](#)
- [Matching on the Logical OR of Two Bit-Field Values on page 34](#)
- [Matching on the Logical AND of Two Bit-Field Values on page 34](#)
- [Grouping Bit-Field Match Conditions on page 34](#)

## Match Conditions for Bit-Field Values

Table 8 on page 31 lists the firewall filter match conditions that are based on whether certain bit fields in a packet are set or not set. The second and third columns list the types of traffic for which the match condition is supported.



Table 8: Binary and Bit-Field Match Conditions for Firewall Filters

Bit-Field Match Condition	Match Values	Protocol Families for Standard Stateless Firewall Filters	Protocol Families for Service Filters
<b>fragment-flags <i>flags</i></b>	Hexadecimal values or text aliases for the three-bit IP fragmentation flags field in the IP header.	<b>family inet</b>	<b>family inet</b>
<b>fragment-offset <i>value</i></b>	Hexadecimal values or text aliases for the 13-bit fragment offset field in the IP header.	<b>family inet</b>	<b>family inet</b>
<b>tcp-flags <i>value</i><sup>†</sup></b>	Hexadecimal values or text aliases for the low-order 6 bits of the 8-bit TCP flags field in the TCP header.	<b>family inet</b> <b>family inet6</b> <b>family vpls</b> <b>family bridge</b>	<b>family inet</b> <b>family inet6</b>

<sup>†</sup> The Junos OS does not automatically check the first fragment bit when matching TCP flags for IPv4 traffic. To check the first fragment bit for IPv4 traffic only, use the **first-fragment** match condition.

## Match Conditions for Common Bit-Field Values or Combinations

Table 9 on page 32 describes firewall filter match conditions that are based on whether certain commonly used values or *combinations* of bit fields in a packet are set or not set.

You can use text synonyms to specify some common bit-field matches. In the previous example, you can specify **tcp-initial** as the same match condition.



### NOTE:

Some of the numeric range and bit-field match conditions allow you to specify a text synonym. For a complete list of synonyms:

- If you are using the J-Web interface, select the synonym from the appropriate list.
- If you are using the CLI, type a question mark (?) after the **from** statement.



Table 9: Bit-Field Match Conditions for Common Combinations

Match Condition	Description	Protocol Families for Standard Stateless Firewall Filters	Protocol Families for Service Filters
<b>first-fragment</b>	Text alias for the bit-field match condition <b>fragment-offset 0</b> , which indicates the first fragment of a fragmented packet.	<b>family inet</b>	<b>family inet</b>
<b>is-fragment</b>	Text alias for the bit-field match condition <b>fragment-offset 0 except</b> , which indicates a trailing fragment of a fragmented packet.	<b>family inet</b>	<b>family inet</b>
<b>tcp-established</b>	Alias for the bit-field match condition <b>tcp-flags "(ack   rst)"</b> , which indicates an established TCP session, but not the first packet of a TCP connection.	<b>family inet</b> <b>family inet6</b>	—
<b>tcp-initial</b>	Alias for the bit-field match condition <b>tcp-flags "(!ack &amp; syn)"</b> , which indicates the first packet of a TCP connection, but not an established TCP session.	<b>family inet</b> <b>family inet6</b>	—

## Logical Operators for Bit-Field Values

Table 10 on page 32 lists the logical operators you can apply to *single* bit-field values when specifying stateless firewall filter match conditions. The operators are listed in order, from highest precedence to lowest precedence. Operations are left-associative, meaning that the operations are processed from left to right.

Table 10: Bit-Field Logical Operators

Precedence Order	Bit-Field Logical Operator	Description
1	<b>(<i>complex-match-condition</i>)</b>	Grouping—The complex match condition is evaluated before any operators outside the parentheses are applied.
2	<b>! <i>match-condition</i></b>	Negation—A match occurs if the match condition is false.
3	<b><i>match-condition-1</i> &amp; <i>match-condition-2</i></b> or <b><i>match-condition-1</i> + <i>match-condition-2</i></b>	Logical AND—A match occurs if both match conditions are true.



Table 10: Bit-Field Logical Operators (*continued*)

Precedence Order	Bit-Field Logical Operator	Description
4	<i>match-condition-1</i>   <i>match-condition-2</i> or <i>match-condition-1</i> , <i>match-condition-2</i>	Logical OR—A match occurs if either match condition is true.

### Matching on a Single Bit-Field Value or Text Alias

For the **fragment-flags** and **tcp-flags** bit-match conditions, you can specify firewall filter match conditions based on whether a particular bit in the packet field is set or not set.

- Numeric value to specify a single bit—You can specify a single bit-field match condition by using a numeric value that has one bit set. Depending on the match condition, you can specify a decimal value, a binary value, or a hexadecimal value. To specify a binary value, specify the number with the prefix **b**. To specify a hexadecimal value, specify the number with the prefix **0x**.

In the following example, a match occurs if the **RST** bit in the TCP flags field is set:

```
[edit firewall family inet filter filter_tcp_rst_number term term1 from]
user@host# set tcp-flags 0x04
```

- Text alias to specify a single bit—You generally specify a single bit-field match condition by using a text alias enclosed in double-quotation marks (“ ”).

In the following example, a match occurs if the **RST** bit in the TCP flags field is set:

```
[edit firewall family inet filter filter_tcp_rst_alias term term1 from]
user@host# set tcp-flags "rst"
```

### Matching on Multiple Bit-Field Values or Text Aliases

You can specify a firewall filter match condition based on whether a particular set of bits in a packet field are set.

- Numeric values to specify multiple set bits—When you specify a numeric value whose binary representation has more than one set bit, the value is treated as a logical AND of the set bits.

In the following example, the two match conditions are the same. A match occurs if either bit **0x01** or **0x02** is not set:

```
[edit firewall family inet filter reset_or_not_initial_packet term term5 from]
user@host# set tcp-flags "!0x3"
user@host# set tcp-flags "!(0x01 & 0x02)"
```

- Text aliases that specify common bit-field matches—You can use text aliases to specify some common bit-field matches. You specify these matches as a single keyword.

In the following example, the **tcp-established** condition, which is an alias for “(ack | rst)”, specifies that a match occurs on TCP packets other than the first packet of a connection:

```
[edit firewall family inet filter reset_or_not_initial_packet term term6 from]
```



```
user@host# set tcp-established
```

## Matching on a Negated Bit-Field Value

To negate a match, precede the value with an exclamation point.

In the following example, a match occurs if the **RST** bit in the TCP flags field is *not* set:

```
[edit firewall family inet filter filter_tcp_rst term term1 from]
user@host# set tcp-flags "!rst"
```

## Matching on the Logical OR of Two Bit-Field Values

You can use the *logical OR operator* (**|** or **,**) to specify that a match occurs if a bit field matches either of two bit-field values specified.

In the following example, a match occurs if the packet is *not* the initial packet in a TCP session:

```
[edit firewall family inet filter not_initial_packet term term3 from]
user@host# set tcp-flags "!syn | ack"
```

In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet. In a packet that is not the initial packet in a TCP session, either the SYN flag is not set or the ACK flag is set.

## Matching on the Logical AND of Two Bit-Field Values

You can use the *logical AND operator* (**&** or **+**) to specify that a match occurs if a bit field matches both of two bit-field values specified.

In the following example, a match occurs if the packet is the initial packet in a TCP session:

```
[edit firewall family inet filter initial_packet term term2 from]
user@host# set tcp-flags "syn & !ack"
```

In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet. In a packet that is an initial packet in a TCP session, the SYN flag is set and the ACK flag is not set.

## Grouping Bit-Field Match Conditions

You can use the *logical grouping notation* to specify that the complex match condition inside the parentheses is evaluated before any operators outside the parentheses are applied.

In the following example, a match occurs if the packet is a TCP reset or if the packet is not the initial packet in the TCP session:

```
[edit firewall family inet filter reset_or_not_initial_packet term term4 from]
user@host# set tcp-flags "!(syn & !ack) | rst"
```

In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet. In a packet that is *not* the initial packet in a TCP session, the SYN flag is not set and the ACK field is set.

### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)



- [Firewall Filter Match Conditions Based on Numbers or Text Aliases on page 29](#)
- [Firewall Filter Match Conditions Based on Address Fields on page 35](#)
- [Firewall Filter Match Conditions Based on Address Classes on page 43](#)

## Firewall Filter Match Conditions Based on Address Fields

You can configure firewall filter match conditions that evaluate packet address fields—IPv4 source and destination addresses, IPv6 source and destination addresses, or media access control (MAC) source and destination addresses—against specified addresses or prefix values.

- [Implied Match on the '0/0 except' Address for Firewall Filter Match Conditions Based on Address Fields on page 35](#)
- [Matching an Address Field to a Subnet Mask or Prefix on page 35](#)
- [Matching an Address Field to an Excluded Value on page 36](#)
- [Matching Either IP Address Field to a Single Value on page 40](#)
- [Matching an Address Field to Noncontiguous Prefixes on page 40](#)
- [Matching an Address Field to a Prefix List on page 42](#)

### Implied Match on the '0/0 except' Address for Firewall Filter Match Conditions Based on Address Fields

Every firewall filter match condition based on a set of addresses or address prefixes is associated with an implicit match on the address **0.0.0.0/0 except** (for IPv4 or VPLS traffic) or **0:0:0:0:0:0:0:0 except** (for IPv6 traffic). As a result, any packet whose specified address field does not match any of the specified addresses or address prefixes fails to match the entire term.

### Matching an Address Field to a Subnet Mask or Prefix

You can specify a single match condition to match a source address or destination address that falls within a specified address prefix.

#### IPv4 Subnet Mask Notation

For an IPv4 address, you can specify a subnet mask value rather than a prefix length. For example:

```
[edit firewall family inet filter filter_on_dst_addr term term3 from]
user@host# set address 10.0.0.10/255.0.0.255
```

#### Prefix Notation

To specify the address prefix, use the notation **prefix/prefix-length**. In the following example, a match occurs if a destination address matches the prefix **10.0.0.0/8**:

```
[edit firewall family inet filter filter_on_dst_addr term term1 from]
user@host# set destination-address 10.0.0.0/8
```



### Default Prefix Length for IPv4 Addresses

---

If you do not specify */prefix-length* for an IPv4 address, the prefix length defaults to */32*. The following example illustrates the default prefix value:

```
[edit firewall family inet filter filter_on_dst_addr term term2 from]
user@host# set destination-address 10
user@host# show
destination-address {
    10.0.0.0/32;
}
```

### Default Prefix Length for IPv6 Addresses

---

If you do not specify */prefix-length* for an IPv6 address, the prefix length defaults to */128*. The following example illustrates the default prefix value:

```
[edit firewall family inet6 filter filter_on_dst_addr term term1 from]
user@host# set destination-address ::10
user@host# show
destination-address {
    ::10/128;
}
```

### Default Prefix Length for MAC Addresses

---

If you do not specify */prefix-length* for a media access control (MAC) address of a VPLS, Layer 2 CCC, or Layer 2 bridging packet, the prefix length defaults to */48*. The following example illustrates the default prefix value:

```
[edit firewall family vpls filter filter_on_dst_mac_addr term term1 from]
user@host# set destination-mac-address 01:00:0c:cc:cc:cd
user@host# show
destination-address {
    01:00:0c:cc:cc:cd/48;
}
```

## Matching an Address Field to an Excluded Value

For the address-field match conditions, you can include the **except** keyword to specify that a match occurs for an address field that does not match the specified address or prefix.

### Excluding IP Addresses in IPv4 or IPv6 Traffic

---

For the following IPv4 and IPv6 match conditions, you can include the **except** keyword to specify that a match occurs for an IP address field that does not match the specified IP address or prefix:

- **address address except**—A match occurs if either the source IP address or the destination IP address does not match the specified address or prefix.
- **source-address address except**—A match occurs if the source IP address does not match the specified address or prefix.



- **destination-address *address* except**—A match occurs if the destination IP address does not match the specified address or prefix.

In the following example, a match occurs for any IPv4 destination addresses that fall under the **192.168.10.0/8** prefix, except for addresses that fall under **192.168.0.0/16**. All other addresses implicitly do not match this condition.

```
[edit firewall family inet filter filter_on_dst_addr term term1 from]
user@host# set 192.168.0.0/16 except
user@host# set 192.168.10.0/8
user@host# show
destination-address {
    192.168.0.0/16 except;
    192.168.10.0/8;
}
```

In the following example, a match occurs for any IPv4 destination address that does not fall within the prefix **10.1.1.0/24**:

```
[edit firewall family inet filter filter_on_dst_addr term term24 from]
user@host# set destination-address 0.0.0.0/0
user@host# set destination-address 10.1.1.0/24 except
user@host# show
destination-address {
    0.0.0.0/0;
    10.1.1.0/24 except;
}
```

### Excluding IP Addresses in VPLS or Layer 2 Bridging Traffic

For the following VPLS and Layer 2 bridging match conditions on MX Series routers only, you can include the **except** keyword to specify that a match occurs for an IP address field that does not match the specified IP address or prefix:

- **ip-address *address* except**—A match occurs if either the source IP address or the destination IP address does not match the specified address or prefix.
- **source-ip-address *address* except**—A match occurs if the source IP address does not match the specified address or prefix.
- **destination-ip-address *address* except**—A match occurs if the destination IP address does not match the specified address or prefix.



In the following example for filtering VPLS traffic on an MX Series router, a match occurs if the source IP address falls within the exception range of **55.0.1.0/255.0.255.0** and the destination IP address matches **55.0.0.0/8**:

```
[edit]
firewall {
  family vpls {
    filter fvpls {
      term 1 {
        from {
          ip-address {
            55.0.0.0/8;
            55.0.1.0/255.0.255.0 except;
          }
        }
        then {
          count from-55/8;
          discard;
        }
      }
    }
  }
}
```

### Excluding MAC Addresses in VPLS or Layer 2 Bridging Traffic

For the following VPLS or Layer 2 bridging traffic match conditions, you can include the **except** keyword to specify that a match occurs for a MAC address field that does not match the specified MAC address or prefix:

- **source-mac-address *address* except**—A match occurs if the source MAC address does not match the specified address or prefix.
- **destination-mac-address *address* except**—A match occurs if either the destination MAC address does not match the specified address or prefix.

### Excluding All Addresses Requires an Explicit Match on the '0/0' Address

If you specify a firewall filter match condition that consists of one or more *address-exception* match conditions (address match conditions that use the **except** keyword) but no *matchable* address match conditions, packets that do not match any of the configured prefixes fails the overall match operation. To configure a firewall filter term of address-exception match conditions to match any address that is not in the prefix list, include an explicit match of **0/0** so that the term contain a matchable address.

For the following example firewall filter for IPv4 traffic, the **from-trusted-addresses** term fails to discard matching traffic, and the **INTRUDERS-COUNT** counter is missing from the output of the **show firewall** operational mode command:

```
[edit]
user@host# show policy-options
prefix-list TRUSTED-ADDRESSES {
  10.2.1.0/24;
  192.168.122.0/24;
}
```



```
[edit firewall family inet filter protect-RE]
user@host# show
term from-trusted-addresses {
  from {
    source-prefix-list {
      TRUSTED-ADDRESSES except;
    }
    protocol icmp;
  }
  then {
    count INTRUDERS-COUNT;
    discard;
  }
}
term other-icmp {
  from {
    protocol icmp;
  }
  then {
    count VALID-COUNT;
    accept;
  }
}
term all {
  then accept;
}
```

```
[edit]
user@host# run show firewall
Filter: protect-RE
Counters:
Name                                     Bytes      Packets
VALID-COUNT                             2770        70
Filter: __default_bpdu_filter__
```

To cause a filter term of address-exception match conditions to match any address that is not in the prefix list, include an explicit match of **0/0** in the set of match conditions:

```
[edit firewall family inet filter protect-RE]
user@host# show term from-trusted-addresses
from {
  source-prefix-list {
    0.0.0.0/0;
    TRUSTED-ADDRESSES except;
  }
  protocol icmp;
}
```

With the addition of the **0.0.0.0/0** source prefix address to the match condition, the **from-trusted-addresses** term discards matching traffic, and the INTRUDERS-COUNT counter displays in the output of the **show firewall** operational mode command:

```
[edit]
user@host# run show firewall
Filter: protect-RE
Counters:
Name                                     Bytes      Packets
```



VALID-COUNT	2770	70
INTRUDERS-COUNT	420	5
Filter: __default_bpdu_filter__		

## Matching Either IP Address Field to a Single Value

For IPv4 and IPv6 traffic and for VPLS and Layer 2 bridging traffic on MX Series routers only, you can use a single match condition to match a single address or prefix value to either the source or destination IP address field.

### Matching Either IP Address Field in IPv4 or IPv6 Traffic

---

For IPv4 or IPv6 traffic, you can use a single match condition to specify the same address or prefix value as the match for either the source or destination IP address field. Instead of creating separate filter terms that specify the same address for the **source-address** and **destination-address** match conditions, you use only the **address** match condition. A match occurs if *either* the source IP address *or* the destination IP address matches the specified address or prefix.

If you use the **except** keyword with the **address** match condition, a match occurs if *both* the source IP address and the destination IP address match the specified value *before* the exception applies.

In a firewall filter term that specifies either the **source-address** or the **destination-address** match condition, you cannot also specify the **address** match condition.

### Matching Either IP Address Field in VPLS or Layer 2 Bridging Traffic

---

For VPLS or Layer 2 bridging traffic on MX Series routers only, you can use a single match condition to specify the same address or prefix value as the match for either the source or destination IP address field. Instead of creating separate filter terms that specify the same address for the **source-ip-address** and **destination-ip-address** match conditions, you use only the **ip-address** match condition. A match occurs if *either* the source IP address *or* the destination IP address matches the specified address or prefix.

If you use the **except** keyword with the **ip-address** match condition, a match occurs if *both* the source IP address and the destination IP address match the specified value *before* the exception applies.

In a firewall filter term that specifies either the **source-ip-address** or the **destination-ip-address** match condition, you cannot also specify the **ip-address** match condition.

## Matching an Address Field to Noncontiguous Prefixes

For IPv4 traffic only, specify a single match condition to match the IP source or destination address field to any prefix specified. The prefixes do not need to be contiguous. That is, the prefixes under the **source-address** or **destination-address** match condition do not need to be adjacent or neighboring to one another.

In the following example, a match occurs if a destination address matches either the 10.0.0.0/8 prefix or the 192.168.0.0/32 prefix:

```
[edit firewall family inet filter filter_on_dst_addr term term5 from]
```



```

user@host# set destination-address 10.0.0.0/8
user@host# set destination-address 192.168.0.0/32
user@host# show
destination-address {
    destination-address 10.0.0.0/8;
    destination-address 192.168.0.0/32;
}

```

The order in which you specify the prefixes within the match condition is not significant. Packets are evaluated against all the prefixes in the match condition to determine whether a match occurs. If prefixes overlap, longest-match rules are used to determine whether a match occurs. A match condition of noncontiguous prefixes includes an implicit **0/0 except** statement, which means that any prefix that does not match any prefix included in the match condition is explicitly considered not to match.

Because the prefixes are order-independent and use longest-match rules, longer prefixes subsume shorter ones as long as they are the same type (whether you specify **except** or not). This is because anything that would match the longer prefix would also match the shorter one.

Consider the following example:

```

[edit firewall family inet filter filter_on_src_addr term term1 from]
source-address {
    172.16.0.0/10;
    172.16.2.0/24 except;
    192.168.1.0;
    192.168.1.192/26 except;
    192.168.1.254;
    172.16.3.0/24; # ignored
    10.2.2.2 except; # ignored
}

```

Within the **source-address** match condition, two addresses are ignored. The **172.16.3.0/16** value is ignored because it falls under the address **172.16.0.0/10**, which is the same type. The **10.2.2.2 except** value is ignored because it is subsumed by the implicit **0.0.0.0/0 except** match value.

Suppose the following source IP address are evaluated by this firewall filter:

- Source IP address **172.16.1.2**—This address matches the **172.16.0.0/10** prefix, and thus the action in the **then** statement is taken.
- Source IP address **172.16.2.2**—This address matches the **172.16.2.0/24** prefix. Because this prefix is negated (that is, includes the **except** keyword), an explicit *mismatch* occurs. The next term in the filter is evaluated, if there is one. If there are no more terms, the packet is discarded.
- Source IP address **10.1.2.3**—This address does not match any of the prefixes included in the **source-address** condition. Instead, it matches the implicit **0.0.0.0/0 except** at the end of the list of prefixes configured under the **source-address** match condition, and is considered to be a mismatch.

The **172.16.3.0/24** statement is ignored because it falls under the address **172.16.0.0/10**—both are the same type.



The **10.2.2.2 except** statement is ignored because it is subsumed by the implicit **0.0.0.0/0 except** statement at the end of the list of prefixes configured under the **source-address** match condition.



**BEST PRACTICE:** When a firewall filter term includes the **from address *address*** match condition and a subsequent term includes the **from source-address *address*** match condition for the same address, packets might be processed by the latter term before they are evaluated by any intervening terms. As a result, packets that should be rejected by the intervening terms might be accepted instead, or packets that should be accepted might be rejected instead.

To prevent this from occurring, we recommend that you do the following. For every firewall filter term that contains the **from address *address*** match condition, replace that term with two separate terms: one that contains the **from source-address *address*** match condition, and another that contains the **from destination-address *address*** match condition.

## Matching an Address Field to a Prefix List

You can define a list of IPv4 or IPv6 address prefixes for use in a routing policy statement or in a stateless firewall filter match condition that evaluates packet address fields.

To define a list of IPv4 or IPv6 address prefixes, include the **prefix-list *prefix-list*** statement.

```
prefix-list name {
  ip-addresses;
  apply-path path;
}
```

You can include the statement at the following hierarchy levels:

- **[edit policy-options]**
- **[edit logical-systems *logical-system-name* policy-options]**

After you have defined a prefix list, you can use it when specifying a firewall filter match condition based on an IPv4 or IPv6 address prefix.

```
[edit firewall family family-name filter filter-name term term-name]
from {
  source-prefix-list {
    prefix-lists;
  }
  destination-prefix-list {
    prefix-lists;
  }
}
```

### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Firewall Filter Match Conditions Based on Numbers or Text Aliases on page 29](#)



- [Firewall Filter Match Conditions Based on Bit-Field Values on page 30](#)
- [Firewall Filter Match Conditions Based on Address Classes on page 43](#)

## Firewall Filter Match Conditions Based on Address Classes

For IPv4 and IPv6 traffic only, you can use class-based firewall filter conditions to match packet fields based on source class or destination class.

- [Source-Class Usage on page 43](#)
- [Destination-Class Usage on page 43](#)
- [Guidelines for Applying SCU or DCU Firewall Filters to Output Interfaces on page 43](#)

### Source-Class Usage

A *source class* is a set of source prefixes grouped together and given a class name. To configure a firewall filter term that matches an IP source address field to one or more source classes, use the **source-class *class-name*** match condition under the **[edit firewall family (inet | inet6) filter *filter-name* term *term-name* from]** hierarchy level.

*Source-class usage* (SCU) enables you to monitor the amount of traffic originating from a specific prefix. With this feature, usage can be tracked and customers can be billed for the traffic they receive.

### Destination-Class Usage

A *destination class* is a set of destination prefixes grouped together and given a class name. To configure a firewall filter term that matches an IP destination address field to one or more destination classes, use the **destination-class *class-name*** match condition at the **[edit firewall family (inet | inet6) filter *filter-name* term *term-name* from]** hierarchy level.

*Destination-class usage* (DCU) enables you can track how much traffic is sent to a specific prefix in the core of the network originating from one of the specified interfaces.

Note, however, that DCU limits your ability to keep track of traffic moving in the reverse direction. It can account for all traffic that arrives on a core interface and heads toward a specific customer, but it cannot count traffic that arrives on a core interface from a specific prefix.

### Guidelines for Applying SCU or DCU Firewall Filters to Output Interfaces

When applying a SCU or DCU firewall filter to an interface, keep the following guidelines in mind:

- Output interfaces—Class-based firewall filter match conditions work only for firewall filters that you apply to output interfaces. This is because the SCU and DCU are determined after route lookup occurs.



- Input interfaces—Although you can specify a source class and destination class for an input firewall filter, the counters are incremented only if the firewall filter is applied on the output interface.
- Output interfaces for tunnel traffic—SCU and DCU are not supported on the interfaces you configure as the output interface for tunnel traffic for transit packets exiting the router through the tunnel.

**Related  
Documentation**

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Match Conditions for IPv4 Traffic on page 258](#)
- [Standard Firewall Filter Match Conditions for IPv6 Traffic on page 267](#)
- [Source Class Usage](#)
- [Firewall Filter Match Conditions Based on Numbers or Text Aliases on page 29](#)
- [Firewall Filter Match Conditions Based on Bit-Field Values on page 30](#)
- [Firewall Filter Match Conditions Based on Address Fields on page 35](#)



## CHAPTER 4

# Introduction to Standard Firewall Filters for Fragment Handling

- [Firewall Filters That Handle Fragmented Packets Overview on page 45](#)

## Firewall Filters That Handle Fragmented Packets Overview

---

You can create stateless firewall filters that handle fragmented packets destined for the Routing Engine. By applying these policies to the Routing Engine, you protect against the use of IP fragmentation as a means to disguise TCP packets from a firewall filter.

For example, consider an IP packet that is fragmented into the smallest allowable fragment size of 8 bytes (a 20-byte IP header plus an 8-byte payload). If this IP packet carries a TCP packet, the first fragment (fragment offset of 0) that arrives at the device contains only the TCP source and destination ports (first 4 bytes), and the sequence number (next 4 bytes). The TCP flags, which are contained in the next 8 bytes of the TCP header, arrive in the second fragment (fragment offset of 1).

On all SRX Series and J Series devices, fragmented packets are not sampled correctly by the firewall filter. When file sampling, port-mirroring and CFLOW is applied on an interface in output direction, packets are sampled before fragmenting the packet and packet-capture captures packet after fragmentation.

See RFC 1858, *Security Considerations for IP Fragment Filtering*.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Handle Fragments on page 167](#)







## CHAPTER 5

# Introduction to Standard Firewall Filters Configuration

- [Stateless Firewall Filters That Reference Policers Overview on page 47](#)
- [Multiple Standard Firewall Filters Applied as a List Overview on page 48](#)
- [Guidelines for Applying Multiple Standard Firewall Filters as a List on page 51](#)
- [Multiple Standard Firewall Filters in a Nested Configuration Overview on page 52](#)
- [Guidelines for Nesting References to Multiple Standard Firewall Filters on page 54](#)
- [Interface-Specific Firewall Filter Instances Overview on page 55](#)
- [Filtering Packets Received on a Set of Interface Groups Overview on page 57](#)
- [Filtering Packets Received on an Interface Set Overview on page 58](#)
- [Filter-Based Forwarding Overview on page 58](#)
- [Accounting for Standard Firewall Filters Overview on page 60](#)
- [System Logging Overview on page 60](#)
- [System Logging of Events Generated for the Firewall Facility on page 61](#)
- [Logging of Packet Headers Evaluated by a Firewall Filter Term on page 63](#)

### Stateless Firewall Filters That Reference Policers Overview

---

Policing, or rate limiting, is an important component of firewall filters that lets you limit the amount of traffic that passes into or out of an interface.

A stateless firewall filter that references a policer can provide protection from denial-of-service (DOS) attacks. Traffic that exceeds the rate limits configured for the policer is either discarded or marked as lower priority than traffic that conforms to the configured rate limits. Packets can be marked for a lower priority by being set to a specific output queue, set to a specific packet loss priority (PLP) level, or both. When necessary, low-priority traffic can be discarded to prevent congestion.

A policer specifies two types of rate limits on traffic:

- **Bandwidth limit**—The average traffic rate permitted, specified as a number of bits per second.



- Maximum burst size—The packet size permitted for bursts of data that exceed the bandwidth limit.

Policing uses an algorithm to enforce a limit on average bandwidth while allowing bursts up to a specified maximum value. You can use policing to define specific classes of traffic on an interface and apply a set of rate limits to each class. After you name and configure a policer, it is stored as a template. You can then apply the policer in an interface configuration or, to rate-limit packet-filtered traffic only, in a firewall filter configuration.

For an IPv4 firewall filter term only, you can also specify a *prefix-specific action* as a nonterminating action that applies a policer to the matched packets. A prefix-specific action applies additional matching criteria on the filter-matched packets based on specified address prefix bits and then associates the matched packets with a counter and policer instance for that filter term or for all terms in the firewall filter.

To apply a policer or a prefix action to packet-filtered traffic, you can use the following firewall filter nonterminating actions:

- **policer** *policer-name*
- **three-color-policer (single-rate | two-rate)** *policer-name*
- **prefix-action** *action-name*

#### Related Documentation

- [Standard Firewall Filter Nonterminating Actions on page 294](#)
- [Traffic Policing Overview](#)
- [Prefix-Specific Counting and Policing Overview](#)

---

## Multiple Standard Firewall Filters Applied as a List Overview

This topic covers the following information:

- [The Challenge: Simplify Large-Scale Firewall Filter Administration on page 48](#)
- [A Solution: Apply Lists of Firewall Filters on page 49](#)
- [Configuration of Multiple Filters for Filter Lists on page 49](#)
- [Application of Filter Lists to a Router Interface on page 50](#)
- [Interface-Specific Names for Filter Lists on page 50](#)
- [How Filter Lists Evaluate Packets on page 50](#)

### The Challenge: Simplify Large-Scale Firewall Filter Administration

Typically, you apply a single stateless firewall filter to an interface in the input or output direction or both. However, this approach might not be practical, when you have a device configured with many interfaces. In large environments, you want the flexibility of being able to modify filtering terms common to multiple interfaces without having to reconfigure the filter of every affected interface.



In general, the solution is to apply an effectively “chained” structure of multiple stateless firewall filters to a single interface. You partition your filtering terms into multiple firewall filters that each perform a filtering task. You can then choose which filtering tasks you want to perform for a given interface and apply the filtering tasks to that interface. In this way, you only manage the configuration for a filtering task in a single firewall filter.

The Junos OS policy framework provides two options for managing the application of multiple separate firewall filters to individual router interfaces. One option is to apply multiple filters as a single input list or output list. The other option is to reference a stateless firewall filter from within the term of another stateless firewall filter.

### A Solution: Apply Lists of Firewall Filters

The most straightforward way to avoid configuring duplicate filtering terms common to multiple stateless firewall filters is to configure multiple firewall filters and then apply a customized *list* of filters to each interface. The Junos OS uses the filters—in the order in which they appear in the list—to evaluate packets that transit the interface. If you need to modify filtering terms shared across multiple interfaces, you only need to modify one firewall filter that contains those terms.



**NOTE:** In contrast with the alternative approach (configuring nested firewall filters) applying firewall filter lists combines multiple firewall filters at each interface application point.

### Configuration of Multiple Filters for Filter Lists

Configuring firewall filters to be applied in unique lists for each router interface involves separating shared packet-filtering rules from interface-specific packet-filtering rules as follows:

- **Unique filters**—For each set of packet-filtering rules unique to a specific interface, configure a separate firewall filter that contains only the filtering terms for that interface.
- **Shared filters**—For each set of packet-filtering rules common across two or more interfaces, consider configuring a separate firewall filter that contains the shared filtering terms.



**TIP:** When planning for a large number firewall filters to be applied using filter lists, administrators often organize the shared filters by filtering criteria, by the services to which customers subscribe, or by the purposes of the interfaces.



## Application of Filter Lists to a Router Interface

Applying a list of firewall filters to an interface is a matter of selecting the filters that meet the packet-filtering requirements of that interface. For each interface, you can include an **input-list** or **output-list** statement (or both) within the **filter** stanza to specify the relevant filters in the order in which they are to be used:

- Include any filters that contain common filtering terms relevant to the interface.
- Include the filter that contain only the filtering terms unique to the interface.

## Interface-Specific Names for Filter Lists

Because a filter list is configured under an interface, the resulting concatenated filter is *interface-specific*.



**NOTE:** When a filter list is configured under an interface, the resulting concatenated filter is interface-specific, regardless whether the firewall filters in the filter list are configured as interface-specific or not. Furthermore, the instantiation of interface-specific firewall filters not only create separate instances of any firewall filter counters, but also separate instances of any policer actions. Any policers applied through an action specified in the firewall filter configuration are applied separately to each interface in the interface group.

The system-generated name of an interface-specific filter consists of the full interface name followed by either **-i** for an input filter list or **-o** for an output filter list.

- **Input filter list name**—For example, if you use the **input-list** statement to apply a chain of filters to logical interface **ge-1/3/0.0**, the Junos OS uses the following name for the filter:

**ge-1/3/0.0-i**

- **Output filter list name**—For example, if you use the **output-list** statement to apply a chain of filters to logical interface **fe-0/1/2.0**, the Junos OS uses the following name for the filter:

**fe-0/1/2.0-o**

You can use the interface-specific name of a filter list when you enter a Junos OS operational mode command that specifies a stateless firewall filter name.

## How Filter Lists Evaluate Packets

The policy framework software evaluates a packet against the filters in a list sequentially, beginning with the first filter in the list until either a terminating action occurs or the packet is implicitly discarded:

- If the packet matches a filter term that specifies a terminating action, any subsequent filters in the list are not used to evaluate the packet. Terminating actions include the



following: **accept**, **discard**, **reject**, **logical-system** *logical-system-name*, **routing-instance** *routing-instance-name*, and **topology** *topology-name*.

- If the packet matches a filter term that does not specify either a terminating action or the **next term** action, any nonterminating actions are taken and then the packet is implicitly accepted. The **accept** action is a terminating action, and therefore any subsequent filters in the list are not used to evaluate the packet.

If the packet matches a term that includes the **next term** action, the matching packet is evaluated against the next term in the firewall filter; otherwise, the matching packet is not evaluated against subsequent terms in the firewall filter. For example, if a packet matches a standard firewall filter term that is configured with the **count** nonterminating action and the **next term** flow control action, the packet is counted and evaluation of the packet continues with the next term or firewall filter.

- Otherwise, if no packet match results in an implicit or explicit terminating action, the packet is implicitly discarded.

#### Related Documentation

- [How Standard Firewall Filters Evaluate Packets on page 18](#)
- [Guidelines for Applying Multiple Standard Firewall Filters as a List on page 51](#)
- [Example: Applying Lists of Multiple Standard Firewall Filters on page 177](#)

## Guidelines for Applying Multiple Standard Firewall Filters as a List

This topic covers the following information:

- [Statement Hierarchy for Applying Lists of Multiple Firewall Filters on page 51](#)
- [Filter Input Lists and Output Lists for Router Interfaces on page 52](#)
- [Types of Filters Supported in Lists on page 52](#)
- [Restrictions on Applying Filter Lists for MPLS or Layer 2 CCC Traffic on page 52](#)

### Statement Hierarchy for Applying Lists of Multiple Firewall Filters

To apply a single filter to the input or output direction of a router logical interface, you include the **input** *filter-name* or **output** *filter-name* statement under the **filter** stanza for a protocol family.

To apply a list of multiple filters to the input or output direction of a router logical interface, include the **input-list** [ *filter-names* ] or **output-list** [ *filter-names* ] statement under the **filter** stanza for a protocol family:

```
interfaces {
  interface-name {
    unit logical-unit-number {
      family family-name {
        filter {
          ...filter-options...
          input-list [ filter-names ];
          output-list [ filter-names ];
        }
      }
    }
  }
}
```



```
    }  
  }  
}
```

You can include the interface configuration at one of the following hierarchy levels:

- `[edit]`
- `[edit logical-systems logical-system-name]`

## Filter Input Lists and Output Lists for Router Interfaces

When applying a list of firewall filters as a list, the following limitations apply:

- You can specify up to 16 firewall filters for a filter input list.
- You can specify up to 16 firewall filters for a filter output list.

## Types of Filters Supported in Lists

Lists of multiple firewall filters applied to a router interface support standard stateless firewall filters only. You cannot apply lists containing service filters or simple filters to a router interface.

## Restrictions on Applying Filter Lists for MPLS or Layer 2 CCC Traffic

When applying stateless firewall filters that evaluate MPLS traffic (**family mpls**) or Layer 2 circuit cross-connection traffic (**family ccc**), you can use the **input-list [ *filter-names* ]** and **output-list [ *filter-names* ]** statements for all interfaces except the following:

- Management and internal Ethernet (**fxp**) interfaces
- Loopback (**lo0**) interfaces
- USB modem (**umd**) interfaces

### Related Documentation

- [Multiple Standard Firewall Filters Applied as a List Overview on page 48](#)
- [Example: Applying Lists of Multiple Standard Firewall Filters on page 177](#)

---

## Multiple Standard Firewall Filters in a Nested Configuration Overview

This topic covers the following information:

- [The Challenge: Simplify Large-Scale Firewall Filter Administration on page 53](#)
- [A Solution: Configure Nested References to Firewall Filters on page 53](#)
- [Configuration of Nested Firewall Filters on page 53](#)
- [Application of Nested Firewall Filters to a Router Interface on page 54](#)



## The Challenge: Simplify Large-Scale Firewall Filter Administration

Typically, you apply a single stateless firewall filter to an interface in the input or output direction or both. This approach might not be practical, however, when you have a router configured with many, even hundreds of interfaces. In an environment of this scale, you want the flexibility of being able to modify filtering terms common to multiple interfaces without having to reconfigure the filter of every affected interface.

In general, the solution is to apply an effectively “chained” structure of multiple stateless firewall filters to a single interface. You partition your filtering terms into multiple firewall filters configured so that you can apply a unique filter to each router interface but also apply common filters to multiple router interfaces as required. The Junos OS policy framework provides two options for managing the application of multiple separate firewall filters to individual router interfaces. One option is to apply multiple filters as a single input list or output list. The other option is to reference a stateless firewall filter from within the term of another stateless firewall filter.

## A Solution: Configure Nested References to Firewall Filters

The most structured way to avoid configuring duplicate filtering terms common to multiple stateless firewall filters is to configure multiple stateless firewall filters so that each filter includes the shared filtering terms by *referencing* a separate filter that contains the common filtering terms. The Junos OS uses the filter terms—in the order in which they appear in the filter definition—to evaluate packets that transit the interface. If you need to modify filtering terms shared across multiple interfaces, you only need to modify one firewall filter.



**NOTE:** Similar to the alternative approach (applying a list of firewall filters), configuring a nested firewall filter combines multiple firewall filters into a new firewall filter definition.

## Configuration of Nested Firewall Filters

Configuring a nested firewall filter for each router interface involves separating shared packet-filtering rules from interface-specific packet-filtering rules as follows:

- For each set of packet-filtering rules common across multiple interfaces, configure a separate firewall filter that contains the shared filtering terms.
- For each router interface, configure a separate firewall filter that contains:
  - All the filtering terms unique to that interface.
  - An additional filtering term that includes a **filter** reference to the firewall filter that contains the common filtering terms.



## Application of Nested Firewall Filters to a Router Interface

Applying nested firewall filters is no different from applying an unnested firewall filter. For each interface, you can include an **input** or **output** statement (or both) within the **filter** stanza to specify the appropriate nested firewall filter.

Applying nested firewall filters to an interface, the shared filtering terms and the interface-specific firewall filters are applied through a *single nested firewall filter* that includes other filters through the **filter** statement within a separate filtering term.

- Related Documentation**
- [Guidelines for Nesting References to Multiple Standard Firewall Filters on page 54](#)
  - [Example: Nesting References to Multiple Standard Firewall Filters on page 182](#)

---

## Guidelines for Nesting References to Multiple Standard Firewall Filters

This topic covers the following information:

- [Statement Hierarchy for Configuring Nested Firewall Filters on page 54](#)
- [Filter-Defining Terms and Filter-Referencing Terms on page 54](#)
- [Types of Filters Supported in Nested Configurations on page 55](#)
- [Number of Filter References in a Single Filter on page 55](#)
- [Depth of Filter Nesting on page 55](#)

### Statement Hierarchy for Configuring Nested Firewall Filters

To reference a filter from within a filter, include the **filter** *filter-name* statement as a separate filter term:

```
firewall firewall-name {  
  family family-name {  
    filter filter-name {  
      term term-name {  
        filter filter-name;  
      }  
    }  
  }  
}
```

You can include the firewall configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

### Filter-Defining Terms and Filter-Referencing Terms

You cannot configure a firewall filter term that both references another firewall filter and defines a match condition or action. If a firewall filter term includes the **filter** statement, then it cannot also include the **from** or **then** statement.



For example, the firewall filter term **term term1** in the configuration is *not* valid:

```
[edit]
firewall {
  family inet {
    filter filter_1 {
      term term1 {
        filter filter_2;
        from {
          source-address 1.1.1.1/32;
        }
        then {
          accept;
        }
      }
    }
  }
}
```

In order for **term term1** to be a valid filter term, you must either remove the **filter filter\_2** statement or remove both the **from** and **then** stanzas.

## Types of Filters Supported in Nested Configurations

Nested configurations of firewall filters support standard stateless firewall filters only. You cannot use service filters or simple filters in a nested firewall filter configuration.

## Number of Filter References in a Single Filter

The total number of filters referenced from within a filter cannot exceed 256.

## Depth of Filter Nesting

The Junos OS supports a single level of firewall filter nesting. If **filter\_1** references **filter\_2**, you cannot configure a filter that references a filter that references **filter\_1**.

### Related Documentation

- [Multiple Standard Firewall Filters in a Nested Configuration Overview on page 52](#)
- [Example: Nesting References to Multiple Standard Firewall Filters on page 182](#)

## Interface-Specific Firewall Filter Instances Overview

This topic covers the following information:

- [Instantiation of Interface-Specific Firewall Filters on page 55](#)
- [Interface-Specific Names for Firewall Filter Instances on page 56](#)
- [Interface-Specific Firewall Filter Counters on page 57](#)
- [Interface-Specific Firewall Filter Policers on page 57](#)

## Instantiation of Interface-Specific Firewall Filters

On T Series, M120, M320, and MX Series routers, you can enable the Junos OS to automatically create an interface-specific instance of a firewall filter for each interface



to which you apply the filter. If you enable interface-specific instantiation of a firewall filter and then apply that filter to multiple interfaces, any **count** actions or **policer** actions configured in the filter terms act on the traffic stream entering or exiting each individual interface, regardless of the sum of traffic on the multiple interfaces.

You can enable this option per firewall filter by including the **interface-specific** statement in the filter configuration.



**NOTE:** On T Series, M120, M320, and MX Series routers, interfaces are distributed among multiple packet-forwarding components.

Interface-specific firewall filtering is not supported on M Series routers other than the M120 and M320 routers. If you apply a firewall filter to multiple interfaces on an M Series router other than the M120 or M320 routers, the filter acts on the sum of traffic entering or exiting those interfaces.

Interface-specific firewall filtering is supported for standard stateless firewall filters and for service filters. Interface-specific instances are not supported for simple filters.

## Interface-Specific Names for Firewall Filter Instances

When the Junos OS creates a separate instance of a firewall filter for a logical interface, the instance is associated with an interface-specific name. The system-generated name of a firewall filter instance consists of the name of the configured filter followed by a hyphen ('-'), the full interface name, and either '-i' for an input filter instance or '-o' for an output filter instance.

- **Input filter instance name**—For example, if you apply the interface-specific firewall filter **filter\_s\_tcp** to the input at logical interface **at-1/1/1.0**, the Junos OS instantiates an interface-specific filter instance with the following system-generated name:  
  
**filter\_s\_tcp-at-1/1/1.0-i**
- **Output filter instance name**—For example, if you apply the interface-specific firewall filter **filter\_s\_tcp** to the output at logical interface **so-2/2/2.2**, the Junos OS instantiates an interface-specific filter instance with the following system-generated name:

**count\_s\_tcp-so-2/2/2.2-o**

You can use the interface-specific name of a filter instance when you enter a Junos OS operational mode command that specifies a stateless firewall filter name.



**TIP:** When you configure a firewall filter with interface-specific instances enabled, we recommend you limit the filter name to *52 bytes* in length. This is because firewall filter names are restricted to *64 bytes* in length. If a system-generated filter instance name exceeds this maximum length, the policy framework software might reject the instance name.



## Interface-Specific Firewall Filter Counters

Instantiation of interface-specific firewall filters causes the Packet Forwarding Engine to maintain any counters for the firewall filter separately for each interface. You specify interface-specific counters per firewall filter term by specifying the **count *counter-name*** non-terminating action.

The system-generated name of an interface-specific firewall filter counter consists of the name of the configured counter followed by a hyphen ('-'), the full interface name, and either '-i' for an input filter instance or '-o' for an output filter instance.

- **Interface-specific input filter counter name**—For example, suppose you configure the filter counter **count\_tcp** for an interface-specific firewall filter. If the filter is applied to the input at logical interface **at-1/1/1.0**, the Junos OS creates the following system-generated counter name:

```
count_tcp-at-1/1/1.0-i
```

- **Interface-specific output filter counter name**—For example, suppose you configure the filter counter **count\_udp** for an interface-specific firewall filter. If the filter is applied to the output at logical interface **so-2/2/2.2**, the Junos OS creates the following system-generated counter name:

```
count_udp-so-2/2/2.2-o
```

## Interface-Specific Firewall Filter Policers

Instantiation of interface-specific firewall filters not only creates separate instances of any firewall filter counters but also creates separate instances of any policer actions. Any policers applied through an action specified in the firewall filter configuration are applied separately to each interface in the interface group. You specify interface-specific policers per firewall filter term by specifying the **policer *policer-name*** non-terminating action.

### Related Documentation

- [Statement Hierarchy for Configuring Interface-Specific Firewall Filters on page 325](#)
- [Statement Hierarchy for Applying Interface-Specific Firewall Filters on page 326](#)
- [Example: Configuring Interface-Specific Firewall Filter Counters on page 186](#)

## Filtering Packets Received on a Set of Interface Groups Overview

You can configure a firewall filter term that matches packets tagged for a specified *interface group* or set of interface groups. An interface group consists of one or more logical interfaces with the same group number. Packets received on an interface in an interface group are tagged as being part of that group.

For standard stateless firewall filters, you can filter packets received on an interface group for IPv4, IPv6, virtual private LAN service (VPLS), Layer 2 circuit cross-connection (CCC), and Layer 2 bridging traffic. For service filters, you can filter packets received on an interface group for either IPv4 or IPv6 traffic.





**NOTE:** You can also configure a firewall filter term that matches on packets tagged for a specified *interface set*. For more information, see [“Filtering Packets Received on an Interface Set Overview”](#) on page 58.

**Related Documentation**

- [Statement Hierarchy for Assigning Interfaces to Interface Groups on page 327](#)
- [Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups on page 327](#)
- [Example: Filtering Packets Received on an Interface Group on page 190](#)

---

## Filtering Packets Received on an Interface Set Overview

You can configure a standard stateless firewall filter term that matches packets tagged for a specified *interface set*. An interface set groups two or more physical or logical interfaces into a single interface-set name. You can filter packets received on an interface set for protocol-independent, IPv4, IPv6, MPLS, VPLS, or bridging traffic.



**NOTE:** You can also configure a standard stateless firewall filter term or a service filter term that matches on packets tagged for a specified *interface group*. For more information, see [“Filtering Packets Received on a Set of Interface Groups Overview”](#) on page 57.

**Related Documentation**

- [Statement Hierarchy for Defining an Interface Set on page 329](#)
- [Statement Hierarchy for Configuring a Filter to Match on an Interface Set on page 329](#)
- [Example: Configuring a Rate-Limiting Filter Based on Destination Class on page 173](#)
- [Example: Filtering Packets Received on an Interface Set on page 194](#)

---

## Filter-Based Forwarding Overview

- [Filters That Classify Packets or Direct Them to Routing Instances on page 58](#)
- [Input Filtering to Classify and Forward Packets Within the Router on page 59](#)
- [Output Filtering to Forward Packets to Another Routing Table on page 59](#)
- [Restrictions for Applying Filter-Based Forwarding on page 60](#)

### Filters That Classify Packets or Direct Them to Routing Instances

For IPv4 or IPv6 traffic only, you can use stateless firewall filters in conjunction with forwarding classes and routing instances to control how packets travel in a network. This is called *filter-based forwarding* (FBF).

You can define a filtering term that matches incoming packets based on source address and then classifies matching packets to a specified forwarding class. This type of filtering



can be configured to grant certain types of traffic preferential treatment or to improve load balancing. To configure a stateless firewall filter to classify packets to a forwarding class, configure a term with the *nonterminating action* **forwarding-class class-name**.

You can also define a filtering term that directs matching packets to a specified routing instance. This type of filtering can be configured to route specific types of traffic through a firewall or other security device before the traffic continues on its path. To configure a stateless firewall filter to direct traffic to a routing instance, configure a term with the *terminating action* **routing-instance routing-instance-name <topology topology-name>** to specify the routing instance to which matching packets will be forwarded.

To forward traffic to the master routing instance, reference **routing-instance default** in the firewall configuration, as shown here:

```
[edit firewall]
family inet {
  filter test {
    term 1 {
      then {
        routing-instance default;
      }
    }
  }
}
```



**NOTE:** Do not reference **routing-instance master**. This does not work.

## Input Filtering to Classify and Forward Packets Within the Router

You can configure filters to classify packets based on source address and specify the forwarding path the packets take within the router by configuring a filter on the ingress interface.

For example, you can use this filter for applications to differentiate traffic from two clients that have a common access layer (for example, a Layer 2 switch) but are connected to different Internet service providers (ISPs). When the filter is applied, the router can differentiate the two traffic streams and direct each to the appropriate network. Depending on the media type the client is using, the filter can use the source IP address to forward the traffic to the corresponding network through a tunnel. You can also configure filters to classify packets based on IP protocol type or IP precedence bits.

## Output Filtering to Forward Packets to Another Routing Table

You can also forward packets based on output filters by configuring a filter on the egress interfaces. In the case of port mirroring, it is useful for port-mirrored packets to be distributed to multiple monitoring PICs and collection PICs based on patterns in packet headers. FBF on the port-mirroring egress interface must be configured.

Packets forwarded to the output filter have been through at least one route lookup when an FBF filter is configured on the egress interface. After the packet is classified at the



egress interface by the FBF filter, it is redirected to another routing table for further route lookup.

## Restrictions for Applying Filter-Based Forwarding

An interface configured with filter-based forwarding does not support source-class usage (SCU) filter matching and unicast reverse-path forwarding (RPF) check filters.

### Related Documentation

- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)
- [Example: Configuring Filter-Based Forwarding on Logical Systems on page 206](#)

## Accounting for Standard Firewall Filters Overview

---

Juniper Networks devices can collect various kinds of data about traffic passing through the device. You can set up one or more accounting profiles that specify some common characteristics of this data, including the following:

- Fields used in the accounting records.
- Number of files that the routing platform retains before discarding, and the number of bytes per file.
- Polling period that the system uses to record the data

There are several types of accounting profiles: interface, firewall filter, source class and destination class usage, and Routing Engine. If you apply the same profile name to both a firewall filter and an interface, it causes an error.

### Related Documentation

- [Statement Hierarchy for Configuring Firewall Filter Accounting Profiles on page 335](#)
- [Statement Hierarchy for Applying Firewall Filter Accounting Profiles on page 336](#)
- [Example: Configuring Statistics Collection for a Standard Firewall Filter on page 223](#)

## System Logging Overview

---

The Junos OS generates system log messages (also called *syslog messages*) to record *system events* that occur on the device. Events consist of routine operations, failure and error conditions, and critical conditions that might require urgent resolution. This system logging utility is similar to the UNIX **syslogd** utility.

Each Junos OS system log message belongs to a message category, called a *facility*, that reflects the hardware- or software-based source of the triggering event. A group of messages belonging to the same facility are either generated by the same software process or concern a similar hardware condition or user activity (such as authentication attempts). Each system log message is also preassigned a *severity*, which indicates how seriously the triggering event affects router functions. Together, the facility and severity of an event are known as the message *priority*. The content of a syslog message identifies the Junos OS *process* that generates the message and briefly describes the operation or error that occurred.



By default, syslog messages that have a severity of **info** or more serious are written to the main system log file **messages** in the **/var/log** directory of the local Routing Engine. To configure global settings and facility-specific settings that override these default values, you can include statements at the **[edit system syslog]** hierarchy level.

For all syslog facilities or for a specified facility, you can configure the syslog message utility to redirect messages of a specified severity to a specified file instead of to the main system log file. You can also configure the syslog message utility to write syslog messages of a specified severity, for all syslog facilities or for a specified facility, to additional destinations. In addition to writing syslog messages to a log file, you can write syslog messages to the terminal sessions of any logged-in users, to the router console, or to a remote host or the other Routing Engine.

At the global level—for all system logging messages, regardless of facility, severity, or destination—you can override the default values for file-archiving properties and the default timestamp format.

**Related Documentation**

- [System Logging of Events Generated for the Firewall Facility on page 61](#)
- [Logging of Packet Headers Evaluated by a Firewall Filter Term on page 63](#)
- [Example: Configuring Logging for a Stateless Firewall Filter Term on page 228](#)

## System Logging of Events Generated for the Firewall Facility

System log messages generated for firewall filter actions belong to the **firewall** facility. Just as you can for any other Junos OS system logging facility, you can direct **firewall** facility syslog messages to one or more specific destinations: to a specified file, to the terminal session of one or more logged in users (or to all users), to the router console, or to a remote host or the other Routing Engine on the router.

When you configure a syslog message destination for **firewall** facility syslog messages, you include a statement at the **[edit system syslog]** hierarchy level, and you specify the **firewall** facility name together with a severity level. Messages from the **firewall** that are rated at the specified level or more severe are logged to the destination.

System log messages with the **DFWD\_** prefix are generated by the firewall process (**dfwd**), which manages compilation and downloading of Junos OS firewall filters. System log messages with the **PFE\_FW\_** prefix are messages about firewall filters, generated by the Packet Forwarding Engine controller, which manages packet forwarding functions. For more information, see the *Junos OS System Log Messages Reference*.

[Table 11 on page 62](#) lists the system log destinations you can configure for the **firewall** facility.



Table 11: Syslog Message Destinations for the Firewall Facility

Destination	Description	Configuration Statements
File	<p>Configuring this option keeps the <b>firewall</b> syslog messages out of the main system log file.</p> <p>To include priority and facility with messages written to the file, include the <b>explicit-priority</b> statement.</p> <p>To override the default standard message format, which is based on a UNIX system log format, include the <b>structured-data</b> statement.<sup>†</sup></p>	<pre>[edit] system {   syslog {     file <i>filename</i> {       firewall severity;       allow-duplicates; # File option       archive <i>archive-options</i>; # File option       explicit-priority; # File option       structured-data; # File option     }     allow-duplicates; # All destinations     archive <i>archive-options</i>; # All files     time-format (<i>option</i>); # Local destinations   } }</pre>
Terminal session	<p>Configuring this option causes a copy of the <b>firewall</b> syslog messages to be written to the specified terminal sessions. Specify one or more user names, or specify * for all logged in users.</p>	<pre>[edit] system {   syslog {     user (<i>username</i>   *) {       firewall severity;     }     time-format (<i>option</i>); # Local destinations   } }</pre>
Router console	<p>Configuring this option causes a copy of the <b>firewall</b> syslog messages to be written to the router console.</p>	<pre>[edit] system {   syslog {     console {       firewall severity;     }     time-format (<i>option</i>); # Local destinations   } }</pre>
Remote host or the other Routing Engine	<p>Configuring this option causes a copy of the <b>firewall</b> syslog messages to be written to the specified remote host or to the other Routing Engine.</p> <p>To override the default alternative facility for forwarding <b>firewall</b> syslog messages to a remote machine (<b>local3</b>), include the <b>facility-override</b> firewall statement.</p> <p>To include priority and facility with messages written to the file, include the <b>explicit-priority</b> statement.</p>	<pre>[edit] system {   syslog {     host (<i>hostname</i>   other-routing-engine) {       firewall severity;       allow-duplicates; # Host option       archive <i>archive-options</i>; # File option       facility-override firewall; # Host option       explicit-priority; # Host option     }     allow-duplicates; # All destinations     archive <i>archive-options</i>; # All files     time-format (<i>option</i>); # Local destinations   } }</pre>

<sup>†</sup> When the **structured-data** statement is included, other statements that specify the format for messages written to the file are ignored (the **explicit-priority** statement at the [edit system syslog file *filename*] hierarchy level and the **time-format** statement at the [edit system syslog] hierarchy level).



By default, the timestamp recorded in a standard-format system log message specifies the month, date, hour, minute, and second when the message was logged, as in the example:

**Sep 07 08:00:10**

To include the year, the millisecond, or both in the timestamp for all system logging messages, regardless of the facility, include one of the following statement at the **[edit system syslog]** hierarchy level:

- **time-format year;**
- **time-format millisecond;**
- **time-format year millisecond;**

The following example illustrates the format for a timestamp that includes both the millisecond (401) and the year (2010):

**Sep 07 08:00:10.401.2010**

#### Related Documentation

- [System Logging Overview on page 60](#)
- [Logging of Packet Headers Evaluated by a Firewall Filter Term on page 63](#)
- [Example: Configuring Logging for a Stateless Firewall Filter Term on page 228](#)
- “Junos OS System Logging Facilities and Message Severity Levels” in the Junos OS System Basics Configuration Guide
- “Junos OS System Log Configuration Hierarchy” in the Junos OS System Basics Configuration Guide
- “Junos OS Default System Log Settings” in the Junos OS System Basics Configuration Guide
- “Logging Messages in Structured-Data Format” in the Junos OS System Basics Configuration Guide
- “Including the Year or Millisecond in Timestamps” in the Junos OS System Basics Configuration Guide
- “Changing the Alternative Facility Name for Remote System Log Messages” in the Junos OS System Basics Configuration Guide
- “Junos OS System Log Alternate Facilities for Remote Logging” in the Junos OS System Basics Configuration Guide

## Logging of Packet Headers Evaluated by a Firewall Filter Term

Built in to the stateless firewall filtering software is the capability to log packet-header information for the packets evaluated by a stateless firewall filter term. You can write the packet header information to the system log file on the local Routing Engine or to a firewall filter buffer in the Packet Forwarding Engine. Logging of packet headers evaluated by firewall filters is supported for standard stateless firewall filters for IPv4 or IPv6 traffic only. Service filters and simple filters do not support logging of packet headers.



Table 12 on page 64 lists the packet-header logs you can configure for a firewall filter action.

Table 12: Packet-Header Logs for Stateless Firewall Filter Terms

Log	Description	Configuration Statements
Syslog message destinations configured for the firewall facility	<p>Configure this option by using the <b>syslog</b> nonterminating action.</p> <p><b>NOTE:</b> Packet header information is interspersed with event messages.</p> <p>To list log files, enter the <b>show log</b> operational mode command without command options.</p> <p>To display log file contents for a specific file in the <b>/var/log</b> directory on the local Routing Engine, enter the <b>show log filename</b> operational mode command or the <b>file show /var/log/filename</b> operational mode command.</p> <p>To clear log file contents, enter the <b>clear log filename &lt;all&gt;</b> operational mode command. If you include the <b>all</b> option, the specified log file is truncated, all archived versions of the log file are deleted.</p>	<pre>firewall {   family {     filter filter-name {       from {         match-conditions;       }       then {         ...         syslog;         terminating-action;       }     }   } }</pre>
Buffer in the Packet Forwarding Engine	<p>Configure this option by using the <b>log</b> nonterminating action.</p> <p><b>NOTE:</b> Restarting the router causes the contents of this buffer to be cleared.</p> <p>To display the local log entries for firewall filters, enter the <b>show firewall log</b> operational mode command.</p>	<pre>firewall {   family {     filter filter-name {       from {         match-conditions;       }       then {         ...         log;         terminating-action;       }     }   } }</pre>

- Related Documentation**
- [System Logging Overview on page 60](#)
  - [System Logging of Events Generated for the Firewall Facility on page 61](#)
  - [Example: Configuring Logging for a Stateless Firewall Filter Term on page 228](#)



## CHAPTER 6

# Introduction to Service Filters Configuration

- [Service Filter Overview on page 65](#)
- [How Service Filters Evaluate Packets on page 67](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Guidelines for Applying Service Filters on page 70](#)

## Service Filter Overview

---

This topic covers the following information:

- [Services on page 65](#)
- [Service Rules on page 65](#)
- [Service Rule Refinement on page 66](#)
- [Service Filter Counters on page 66](#)

## Services

The Adaptive Services Physical Interface Cards (PICs), Multiservices PICs, and Multiservices Dense Port Concentrators (DPCs) provide *adaptive services interfaces*. Adaptive services interfaces enable you to coordinate a special range of services on a single PIC or DPC by configuring a set of services and applications.



**NOTE:** Service filters are not supported on T4000 routers, J Series devices and Branch SRX devices.

## Service Rules

A *service set* is an optional definition you can apply to the traffic at an adaptive services interface. A service set enables you to configure combinations of directional rules and default settings that control the behavior of each service in the service set.



## Service Rule Refinement

When you apply a service set to the traffic at an adaptive services interface, you can optionally use *service filters* to refine the target of the set of services and also to process traffic. Service filters enable you to manipulate traffic by performing packet filtering to a defined set of services on an adaptive services interface before the traffic is delivered to its destination. You can apply a service filter to traffic before packets are accepted for input or output service processing or after packets return from input service processing.

## Service Filter Counters

Like standard firewall filters, service filters support counting of matched packets. When you display counters for a service filter, however, the syntax for specifying the filter name includes the name of the *service set* to which the service filter is applied.

- To enable counting of the packets matched by a service filter term, specify the **count** *counter-name* nonterminating action in that term.
- To display counters for service filters, use the **show firewall filter** *filter-name* <counter *counter-name*> operational mode command, and specify the *filter-name* as follows:

**\_\_service-service-set-name:service-filter-name**

For example, suppose you configure a service filter named **out\_filter** with a counter named **out\_counter** and apply that service filter to a logical interface to direct certain packets for processing by the output services associated with the service set **nat\_set**. In this scenario, the syntax for using the **show firewall** operational mode command to display the counter is as follows:

```
[edit]
user@host> show firewall filter __service-nat_set:out_filter counter out_counter
```

### Related Documentation

- [Stateless Firewall Filter Types on page 6](#)
- [How Service Filters Evaluate Packets on page 67](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Guidelines for Applying Service Filters on page 70](#)
- [Example: Configuring and Applying Service Filters on page 233](#)
- “Adaptive Services Overview” in the Junos Services Interfaces Configuration Release 11.2
- “Configuring Service Sets to be Applied to Services Interfaces” in the Junos Services Interfaces Configuration Release 11.2
- “Configuring Service Rules” in the Junos Services Interfaces Configuration Release 11.2



---

## How Service Filters Evaluate Packets

---

This topic covers the following information:

- [Service Filters That Contain a Single Term on page 67](#)
- [Service Filters That Contain Multiple Terms on page 67](#)
- [Service Filter Terms That Do Not Contain Any Match Conditions on page 67](#)
- [Service Filter Terms That Do Not Contain Any Actions on page 67](#)
- [Service Filter Default Action on page 67](#)

### Service Filters That Contain a Single Term

For a service filter that consists of a single term, the policy framework software evaluates a packet as follows:

- If the packet matches all the conditions, the actions are taken.
- If the packet matches all the conditions and no actions are specified, the packet is accepted.
- If the packet does not match all the conditions, it is discarded.

### Service Filters That Contain Multiple Terms

For a service filter that consists of multiple terms, the policy framework software evaluates a packet against the terms in the filter sequentially, beginning with the first term in the filter, until either the packet matches all the conditions in one of the terms or there are no more terms in the filter.

- If the packet matches all the conditions in a term, the actions in that term are performed and evaluation of the packet ends at that term. Any subsequent terms in the filter are not used.
- If the packet does not match all the conditions in the term, evaluation of the packet proceeds to the next term in the filter.

### Service Filter Terms That Do Not Contain Any Match Conditions

For service filters with a single term and for filters with multiple terms, if a term does not contain any match conditions, the actions are taken on any packet evaluated.

### Service Filter Terms That Do Not Contain Any Actions

If a term does not contain any actions, and if the packet matches the conditions in the term, the packet is accepted.

### Service Filter Default Action

Each service filter has an *implicit skip* action at the end of the filter, which is equivalent to including the following example term **explicit\_skip** as the final term in the service filter:

```
term explicit_skip {
```



```
    then skip;
}
```

By default, if a packet matches none of the terms in a service filter, the packet bypasses service processing.

**Related  
Documentation**

- [Service Filter Overview on page 65](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Guidelines for Applying Service Filters on page 70](#)
- [Example: Configuring and Applying Service Filters on page 233](#)

---

## Guidelines for Configuring Service Filters

This topic covers the following information:

- [Statement Hierarchy for Configuring Service Filters on page 68](#)
- [Service Filter Protocol Families on page 69](#)
- [Service Filter Names on page 69](#)
- [Service Filter Terms on page 69](#)
- [Service Filter Match Conditions on page 69](#)
- [Service Filter Terminating Actions on page 69](#)

### Statement Hierarchy for Configuring Service Filters

To configure a service filter, include the **service-filter** *service-filter-name* statement at the **[edit firewall family (inet | inet6)]** hierarchy level:

```
[edit]
firewall {
  family (inet | inet6) {
    service-filter service-filter-name {
      term term-name {
        from {
          match-conditions;
        }
        then {
          actions;
        }
      }
    }
  }
}
```

Individual statements supported under the **service-filter** *service-filter-name* statement are described separately in this topic and are illustrated in the example of configuring and applying a service filter.



## Service Filter Protocol Families

You can configure service filters to filter IPv4 traffic (**family inet**) and IPv6 traffic (**family inet6**) only. No other protocol families are supported for service filters.

## Service Filter Names

Under the **family inet** or **family inet6** statement, you can include **service-filter service-filter-name** statements to create and name service filters. The filter name can contain letters, numbers, and hyphens (-) and be up to 64 characters long. To include spaces in the name, enclose the entire name in quotation marks (" ").

## Service Filter Terms

Under the **service-filter service-filter-name** statement, you can include **term term-name** statements to create and name filter terms.

- You must configure at least one term in a firewall filter.
- You must specify a unique name for each term within a firewall filter. The term name can contain letters, numbers, and hyphens (-) and can be up to 64 characters long. To include spaces in the name, enclose the entire name in quotation marks (" ").
- The order in which you specify terms within a firewall filter configuration is important. Firewall filter terms are evaluated in the order in which they are configured. By default, new terms are always added to the end of the existing filter. You can use the **insert** configuration mode command to reorder the terms of a firewall filter.

## Service Filter Match Conditions

Service filter terms support only a subset of the IPv4 and IPv6 match conditions that are supported for standard stateless firewall filters.

If you specify an IPv6 address in a match condition (the **address**, **destination-address**, or **source-address** match conditions), use the syntax for text representations described in RFC 2373, *IP Version 6 Addressing Architecture*. For more information about IPv6 addresses, see "IPv6 Overview" and "IPv6 Standards" in the Junos OS Routing Protocols Configuration Guide.

## Service Filter Terminating Actions

When configuring a service filter term, you must specify one of the following filter-terminating actions:

- **service**
- **skip**



**NOTE:** These actions are unique to service filters.



Service filter terms support only a subset of the IPv4 and IPv6 nonterminating actions that are supported for standard stateless firewall filters:

- **count** *counter-name*
- **log**
- **port-mirror**
- **sample**

Service filters do not support the **next** action.

**Related  
Documentation**

- [Service Filter Overview on page 65](#)
- [How Service Filters Evaluate Packets on page 67](#)
- [Guidelines for Applying Service Filters on page 70](#)
- [Service Filter Match Conditions for IPv4 or IPv6 Traffic on page 311](#)
- [Service Filter Terminating Actions on page 317](#)
- [Service Filter Nonterminating Actions on page 318](#)
- [Example: Configuring and Applying Service Filters on page 233](#)

---

## Guidelines for Applying Service Filters

This topic covers the following information:

- [Restrictions for Adaptive Services Interfaces on page 70](#)
- [Statement Hierarchy for Applying Service Filters on page 71](#)
- [Associating Service Rules with Adaptive Services Interfaces on page 71](#)
- [Filtering Traffic Before Accepting Packets for Service Processing on page 72](#)
- [Postservice Filtering of Returning Service Traffic on page 72](#)

### Restrictions for Adaptive Services Interfaces

The following restrictions apply to adaptive services interfaces and service filters.

---

#### Adaptive Services Interfaces

You can apply a service filter to IPv4 or IPv6 traffic associated with a service set at an *adaptive services interface* only. Adaptive services interfaces are supported for the following hardware only:

- Adaptive Services (AS) PICs on M Series and T Series routers
- Multiservices (MS) PICs on M Series and T Series routers
- Multiservices (MS) DPCs on MX Series routers



### System Logging to a Remote Host from M Series Routers

Logging of adaptive services interfaces messages to an external server by means of the **fxp0** or **em0** port is not supported on M Series routers. The architecture does not support system logging traffic out of a management interface. Instead, access to an external server is supported on a Packet Forwarding Engine interface.

### Statement Hierarchy for Applying Service Filters

You can enable packet filtering of IPv4 or IPv6 traffic before a packet is accepted for input or output service processing. To do this, apply a service filter to the adaptive services interface input or output in conjunction with an interface service set.

You can also enable packet filtering of IPv4 or IPv6 traffic that is returning to the Packet Forwarding Engine after input service processing completes. To do this, apply a post-service filter to the adaptive services interface input.

The following configuration shows the hierarchy levels at which you can apply the service filters to adaptive services interfaces:

```
[edit]
interfaces {
  interface-name {
    unit unit-number {
      family (inet | inet6) {
        service {
          input {
            service-set service-set-name service-filter service-filter-name;
            post-service-filter service-filter-name;
          }
          output {
            service-set service-set-name service-filter service-filter-name;
          }
        }
      }
    }
  }
}
```

### Associating Service Rules with Adaptive Services Interfaces

To define and group the service rules be applied to an adaptive services interface, you define an *interface service set* by including the **service-set service-set-name** statement at the **[edit services]** hierarchy level.

To apply an interface service set to the input and output of an adaptive services interface, you include the **service-set service-set-name** at the following hierarchy levels:

- **[edit interfaces interface-name unit unit-number input]**
- **[edit interfaces interface-name unit unit-number output]**



If you apply a service set to one direction of an adaptive services interface but do not apply a service set to the other direction, an error occurs when you commit the configuration.

The adaptive services PIC performs different actions depending on whether the packet is sent to the PIC for input service or for output service. For example, you can configure a single service set to perform Network Address Translation (NAT) in one direction and destination NAT (dNAT) in the other direction.

## Filtering Traffic Before Accepting Packets for Service Processing

To filter IPv4 or IPv6 traffic before accepting packets for input or output service processing, include the **service-set** *service-set-name* **service-filter** *service-filter-name* at one of the following interfaces:

- **[edit interfaces** *interface-name* **unit** *unit-number* **family** (inet | inet6) **service** input]
- **[edit interfaces** *interface-name* **unit** *unit-number* **family** (inet | inet6) **service** output]

For the **service-set-name**, specify a service set configured at the **[edit services service-set]** hierarchy level.

The service set retains the input interface information even after services are applied, so that functions such as filter-class forwarding and destination class usage (DCU) that depend on input interface information continue to work.

The following requirements apply to filtering inbound or outbound traffic before accepting packets for service processing:

- You configure the same service set on the input and output sides of the interface.
- If you include the **service-set** statement without an optional **service-filter** definition, the Junos OS assumes the match condition is true and selects the service set for processing automatically.
- The service filter is applied only if a service set is configured and selected.

You can include more than one service set definition on each side of an interface. The following guidelines apply:

- If you include multiple service sets, the router software evaluates them in the order in which they appear in the configuration. The system executes the first service set for which it finds a match in the service filter and ignores the subsequent definitions.
- A maximum of six service sets can be applied to an interface.
- When you apply multiple service sets to an interface, you must also configure and apply a service filter to the interface.

## Postservice Filtering of Returning Service Traffic

As an option to filtering of IPv4 or IPv6 input service traffic, you can apply a service filter to IPv4 or IPv6 traffic that is returning to the services interface after the service set is executed. To apply a service filter in this manner, include the **post-service-filter**



*service-filter-name* statement at the [edit interfaces *interface-name* unit *unit-number* family (inet | inet6) service input] hierarchy level.

**Related  
Documentation**

- [Service Filter Overview on page 65](#)
- [How Service Filters Evaluate Packets on page 67](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Example: Configuring and Applying Service Filters on page 233](#)
- “Adaptive Services Overview” in the Junos Services Interfaces Configuration Release 11.2
- “Configuring Service Sets to be Applied to Services Interfaces” in the Junos Services Interfaces Configuration Release 11.2
- “Configuring Service Rules” in the Junos Services Interfaces Configuration Release 11.2







## CHAPTER 7

# Introduction to Simple Filters Configuration

- [Simple Filter Overview on page 75](#)
- [How Simple Filters Evaluate Packets on page 75](#)
- [Guidelines for Configuring Simple Filters on page 77](#)
- [Guidelines for Applying Simple Filters on page 80](#)

## Simple Filter Overview

---

Simple filters are supported on Gigabit Ethernet intelligent queuing 2 (IQ2) and Enhanced Queuing Dense Port Concentrator (DPC) interfaces only.

Simple filters are recommended for metropolitan Ethernet applications.

### Related Documentation

- [How Simple Filters Evaluate Packets on page 75](#)
- [Guidelines for Configuring Simple Filters on page 77](#)
- [Guidelines for Applying Simple Filters on page 80](#)
- [Example: Configuring and Applying a Simple Filter on page 239](#)

## How Simple Filters Evaluate Packets

---

This topic covers the following information:

- [Simple Filters That Contain a Single Term on page 76](#)
- [Simple Filters That Contain Multiple Terms on page 76](#)
- [Simple Filter Terms That Do Not Contain Any Match Conditions on page 76](#)
- [Simple Filter Terms That Do Not Contain Any Actions on page 76](#)
- [Simple Filter Default Action on page 76](#)



## Simple Filters That Contain a Single Term

For a simple filter that consists of a single term, the policy framework software evaluates a packet as follows:

- If the packet matches all the conditions, the actions are taken.
- If the packet matches all the conditions and no actions are specified, the packet is accepted.
- If the packet does not match all the conditions, it is discarded.

## Simple Filters That Contain Multiple Terms

For a simple filter that consists of multiple terms, the policy framework software evaluates a packet against the terms in the filter sequentially, beginning with the first term in the filter, until either the packet matches all the conditions in one of the terms or there are no more terms in the filter.

- If the packet matches all the conditions in a term, the actions in that term are performed and evaluation of the packet ends at that term. Any subsequent terms in the filter are not used.
- If the packet does not match all the conditions in the term, evaluation of the packet proceeds to the next term in the filter.

## Simple Filter Terms That Do Not Contain Any Match Conditions

For simple filters with a single term and for filters with multiple terms, if a term does not contain any match conditions, the actions are taken on any packet evaluated.

## Simple Filter Terms That Do Not Contain Any Actions

If a simple filter term does not contain any actions, and if the packet matches the conditions in the term, the packet is accepted.

## Simple Filter Default Action

Each simple filter has an *implicit discard* action at the end of the filter, which is equivalent to including the following example term **explicit\_discard** as the final term in the simple filter:

```
term explicit_discard {  
    then discard;  
}
```

By default, if a packet matches none of the terms in a simple filter, the packet is discarded.

### Related Documentation

- [Simple Filter Overview on page 75](#)
- [Guidelines for Configuring Simple Filters on page 77](#)
- [Guidelines for Applying Simple Filters on page 80](#)
- [Example: Configuring and Applying a Simple Filter on page 239](#)



## Guidelines for Configuring Simple Filters

This topic covers the following information:

- [Statement Hierarchy for Configuring Simple Filters on page 77](#)
- [Simple Filter Protocol Families on page 77](#)
- [Simple Filter Names on page 77](#)
- [Simple Filter Terms on page 78](#)
- [Simple Filter Match Conditions on page 78](#)
- [Simple Filter Terminating Actions on page 79](#)
- [Simple Filter Nonterminating Actions on page 79](#)

### Statement Hierarchy for Configuring Simple Filters

To configure a simple filter, include the **simple-filter** *simple-filter-name* statement at the **[edit firewall family inet]** hierarchy level.

```
[edit]
firewall {
  family inet {
    simple-filter simple-filter-name {
      term term-name {
        from {
          match-conditions;
        }
        then {
          actions;
        }
      }
    }
  }
}
```

Individual statements supported under the **simple-filter** *simple-filter-name* statement are described separately in this topic and are illustrated in the example of configuring and applying a simple filter.

### Simple Filter Protocol Families

You can configure simple filters to filter IPv4 traffic (**family inet**) only. No other protocol family is supported for simple filters.

### Simple Filter Names

Under the **family inet** statement, you can include **simple-filter** *simple-filter-name* statements to create and name simple filters. The filter name can contain letters, numbers, and hyphens (-) and be up to 64 characters long. To include spaces in the name, enclose the entire name in quotation marks (" ").



## Simple Filter Terms

Under the **simple-filter** *simple-filter-name* statement, you can include **term** *term-name* statements to create and name filter terms.

- You must configure at least one term in a firewall filter.
- You must specify a unique name for each term within a firewall filter. The term name can contain letters, numbers, and hyphens (-) and can be up to 64 characters long. To include spaces in the name, enclose the entire name in quotation marks (" ").
- The order in which you specify terms within a firewall filter configuration is important. Firewall filter terms are evaluated in the order in which they are configured. By default, new terms are always added to the end of the existing filter. You can use the **insert** configuration mode command to reorder the terms of a firewall filter.

Simple filters do *not* support the **next term** action.

## Simple Filter Match Conditions

Simple filter terms support only a subset of the IPv4 match conditions that are supported for standard stateless firewall filters.

Unlike standard stateless firewall filters, the following restrictions apply to simple filters:

- On MX Series routers with the Enhanced Queuing DPC, simple filters do *not* support the **forwarding-class** match condition.
- Simple filters support only one **source-address** and one **destination-address** prefix for each filter term. If you configure multiple prefixes, only the last one is used.
- Simple filters do *not* support multiple source addresses and destination addresses in a single term. If you configure multiple addresses, only the last one is used.
- Simple filters do *not* support negated match conditions, such as the **protocol-except** match condition or the **exception** keyword.
- Simple filters support a range of values for **source-port** and **destination-port** match conditions only. For example, you can configure **source-port 400-500** or **destination-port 600-700**.
- Simple filters do *not* support noncontiguous mask values.

Table 13 on page 78 lists the simple filter match conditions.

**Table 13: Simple Filter Match Conditions**

Match Condition	Description
<b>destination-address</b> <i>destination-address</i>	Match IP destination address.



Table 13: Simple Filter Match Conditions (*continued*)

Match Condition	Description
<b>destination-port number</b>	<p>TCP or UDP destination port field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol</b> match statement to determine which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the following text aliases (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobilip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rkinit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xmcp</b> (177).</p>
<b>forwarding-class class</b>	<p>Match the forwarding class of the packet.</p> <p>Specify <b>assured-forwarding</b>, <b>best-effort</b>, <b>expedited-forwarding</b>, or <b>network-control</b>.</p> <p>For information about forwarding classes and router-internal output queues, see the Junos OS Class of Service Configuration Guide.</p>
<b>protocol number</b>	<p>IP protocol field. In place of the numeric value, you can specify one of the following text aliases (the field values are also listed): <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipvp6</b> (41), <b>ospf</b> (89), <b>pim</b> (103), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrp</b> (112).</p>
<b>source-address ip-source-address</b>	<p>Match the IP source address.</p>
<b>source-port number</b>	<p>Match the UDP or TCP source port field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol</b> match statement to determine which protocol is being used on the port.</p> <p>In place of the numeric field, you can specify one of the text aliases listed for <b>destination-port</b>.</p>

## Simple Filter Terminating Actions

Simple filters do *not* support explicitly configurable terminating actions, such as **accept**, **reject**, and **discard**. Terms configured in a simple filter always accept packets.

Simple filters do *not* support the **next** action.

## Simple Filter Nonterminating Actions

Simple filters support only the following nonterminating actions:

- **forwarding-class** (*forwarding-class* | **assured-forwarding** | **best-effort** | **expedited-forwarding** | **network-control**)





**NOTE:** On the MX Series routers with the Enhanced Queuing DPC, the forwarding class is not supported as a from match condition.

- **loss-priority (high | low | medium-high | medium-low)**

Simple filters do not support actions that perform other functions on a packet (such as incrementing a counter, logging information about the packet header, sampling the packet data, or sending information to a remote host using the system log functionality).

#### Related Documentation

- [Simple Filter Overview on page 75](#)
- [How Simple Filters Evaluate Packets on page 75](#)
- [Guidelines for Applying Simple Filters on page 80](#)
- [Example: Configuring and Applying a Simple Filter on page 239](#)

## Guidelines for Applying Simple Filters

This topic covers the following information:

- [Statement Hierarchy for Applying Simple Filters on page 80](#)
- [Restrictions for Applying Simple Filters on page 80](#)

### Statement Hierarchy for Applying Simple Filters

You can apply a simple filter to the IPv4 ingress traffic at a logical interface by including the **simple-filter input *simple-filter-name*** statement at the **[edit interfaces *interface-name* unit *unit-number* family inet]** hierarchy level.

```
[edit]
interfaces {
  interface-name {
    unit logical-unit-number {
      family inet {
        simple-filter {
          input filter-name;
        }
      }
    }
  }
}
```

### Restrictions for Applying Simple Filters

You can apply a simple filter to the ingress IPv4 traffic at a logical interface configured on the following hardware only:

- Gigabit Ethernet intelligent queuing (IQ2) PICs installed on M120, M320, or T Series routers.
- Enhanced Queuing Dense Port Concentrators (EQ DPCs) installed on MX Series routers.



For more information about Ethernet IQ2 PICs and EQ DPCs and related features, see the Junos OS Class of Service Configuration Guide. For more information about configuring the MX Series routers, on which EQ DPCs are supported, see the Junos OS Layer 2 Configuration Guide.

The following additional restrictions pertain to applying simple filters:

- Simple filters are not supported on Modular Port Concentrator (MPC) interfaces, including Enhanced Queuing MPC interfaces.
- Simple filters are not supported for interfaces in an aggregated-Ethernet bundle.
- You can apply simple filters to **family inet** traffic only. No other protocol family is supported.
- You can apply simple filters to ingress traffic only. Egress traffic is not supported.
- You can apply only a single simple filter to a supported logical interface. Input lists are not supported.

**Related  
Documentation**

- [Simple Filter Overview on page 75](#)
- [How Simple Filters Evaluate Packets on page 75](#)
- [Guidelines for Configuring Simple Filters on page 77](#)
- [Example: Configuring and Applying a Simple Filter on page 239](#)







## CHAPTER 8

# Introduction to Firewall Filters Configuration in Logical Systems

- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
- [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
- [References from a Firewall Filter in a Logical System to Subordinate Objects on page 87](#)
- [References from a Firewall Filter in a Logical System to Nonfirewall Objects on page 88](#)
- [References from a Nonfirewall Object in a Logical System to a Firewall Filter on page 90](#)

## Stateless Firewall Filters in Logical Systems Overview

---

This topic covers the following information:

- [Logical Systems on page 83](#)
- [Stateless Firewall Filters in Logical Systems on page 83](#)
- [Identifiers for Firewall Objects in Logical Systems on page 83](#)

## Logical Systems

With the Junos OS, you can partition a single physical router into multiple logical devices that perform independent routing tasks. Because logical systems perform a subset of the tasks once handled by the physical router, logical systems offer an effective way to maximize the use of a single router.

## Stateless Firewall Filters in Logical Systems

You can configure a separate set of stateless firewall filters for each logical system on a router. To configure a filter in a logical system, you must define the filter in the **firewall** stanza at the **[edit logical-systems *logical-system-name*]** hierarchy level, and you must apply the filter to a logical interface that is also configured at the **[edit logical-systems *logical-system-name*]** hierarchy level.

## Identifiers for Firewall Objects in Logical Systems

To identify firewall objects configured under logical systems, operational **show** commands and firewall-related SNMP MIB objects include a **\_\_logical-system-name/** prefix in the object name. For example, firewall objects configured under the **ls1** logical system include **\_\_ls1/** as the prefix.



- Related Documentation**
- [Stateless Firewall Filter Types on page 6](#)
  - [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
  - [Unsupported Firewall Filter Statements for Logical Systems on page 319](#)
  - [Unsupported Actions for Firewall Filters in Logical Systems on page 321](#)
  - [Example: Configuring a Stateless Firewall Filter to Protect a Logical System Against ICMP Floods on page 245](#)
  - "Introduction to Logical Systems" in the Logical Systems Configuration Guide
  - "Logical Systems Operations and Restrictions" in the Logical Systems Configuration Guide

---

## Guidelines for Configuring and Applying Firewall Filters in Logical Systems

This topic covers the following information:

- [Statement Hierarchy for Configuring Firewall Filters in Logical Systems on page 84](#)
- [Filter Types in Logical Systems on page 85](#)
- [Firewall Filter Protocol Families in Logical Systems on page 85](#)
- [Firewall Filter Match Conditions in Logical Systems on page 86](#)
- [Firewall Filter Actions in Logical Systems on page 86](#)
- [Statement Hierarchy for Applying Firewall Filters in Logical Systems on page 86](#)

### Statement Hierarchy for Configuring Firewall Filters in Logical Systems

To configure a firewall filter in a logical system, include the **filter**, **service-filter**, or **simple-filter** statement at the `[edit logical-systems logical-system-name firewall family family-name]` hierarchy level.

```
[edit]
logical systems {
  logical-system-name {
    firewall {
      family family-name {
        filter filter-name {
          interface-specific;
          physical-interface-filter;
          term term-name {
            filter filter-name;
            from {
              match-conditions;
            }
            then {
              actions;
            }
          }
        }
        service-filter filter-name { # For 'family inet' or 'family inet6' only.
          term term-name {
```



```

    from {
        match-conditions;
    }
    then {
        actions;
    }
}

simple-filter filter-name { # For 'family inet' only.
    term term-name {
        from {
            match-conditions;
        }
        then {
            actions;
        }
    }
}
}
}
}
```

## Filter Types in Logical Systems

There are no special restrictions on the types of stateless firewall filter types that you can configure in logical systems.

In a logical system, you can use the same types of stateless firewall filters that are available on a physical router:

- Standard stateless firewall filters
- Service filters
- Simple filters

## Firewall Filter Protocol Families in Logical Systems

There are no special restrictions on the protocol families supported with stateless firewall filters in logical systems.

In a logical system, you can filter the same protocol families as you can on a physical router.

- Standard stateless firewall filters—In logical systems, you can filter the following traffic types: protocol-independent, IPv4, IPv6, MPLS, MPLS-tagged IPv4 or IPv6, VPLS, Layer 2 circuit cross-connection, and Layer 2 bridging.
- Service filters—In logical systems, you can filter IPv4 and IPv6 traffic.
- Simple filters—In logical systems, you can filter IPv4 traffic only.



## Firewall Filter Match Conditions in Logical Systems

There are no special restrictions on the match conditions supported with stateless firewall filters in logical systems.

## Firewall Filter Actions in Logical Systems

There are no special restrictions on the actions supported with stateless firewall filters in logical systems.

## Statement Hierarchy for Applying Firewall Filters in Logical Systems

To apply a firewall filter in a logical system, include the **filter** *filter-name*, **service-filter** *service-filter-name*, or **simple-filter** *simple-filter-name* statement to a logical interface in the logical system.

The following configuration shows the hierarchy levels at which you can apply the statements:

```
[edit]
logical-systems logical-system-name {
  interfaces {
    interface-name {
      unit logical-unit-number {
        family family-name {
          filter {
            group group-name;
            input filter-name;
            input-list [ filter-names ];
            output filter-name;
            output-list [ filter-names ]
          }
          rpf-check { # For 'family inet' or 'family inet6' only.
            fail-filter filter-name;
            mode loose;
          }
          service { # For 'family inet' or 'family inet6' only.
            input {
              service-set service-set-name <service-filter service-filter-name>;
              post-service-filter service-filter-name;
            }
            output {
              service-set service-set-name <service-filter service-filter-name>;
            }
          }
          simple-filter { # For 'family inet' only.
            input simple-filter-name;
          }
        }
      }
    }
  }
}
```



- Related Documentation**
- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
  - [References from a Firewall Filter in a Logical System to Subordinate Objects on page 87](#)
  - [References from a Firewall Filter in a Logical System to Nonfirewall Objects on page 88](#)
  - [References from a Nonfirewall Object in a Logical System to a Firewall Filter on page 90](#)
  - [Example: Configuring a Stateless Firewall Filter to Protect a Logical System Against ICMP Floods on page 245](#)
  - [Unsupported Firewall Filter Statements for Logical Systems on page 319](#)
  - [Unsupported Actions for Firewall Filters in Logical Systems on page 321](#)

## References from a Firewall Filter in a Logical System to Subordinate Objects

---

This topic covers the following information:

- [Resolution of References from a Firewall Filter to Subordinate Objects on page 87](#)
- [Valid Reference from a Firewall Filter to a Subordinate Object on page 87](#)

### Resolution of References from a Firewall Filter to Subordinate Objects

If a firewall filter defined in a logical system references a subordinate object (for example, a policer or prefix list), that subordinate object must be defined within the **firewall** stanza of the same logical system. For example, if a firewall filter configuration references a policer, the firewall filter and the policer must be configured under the same **[edit logical-systems logical-system-name firewall]** hierarchy level.

This rule applies even if the same policer is configured under the main firewall configuration or if the same policer is configured as part of a firewall in another logical system.

### Valid Reference from a Firewall Filter to a Subordinate Object

In this example, the firewall filter **filter1** references the policer **pol1**. Both **filter1** and **pol1** are defined under the same firewall object. This configuration is valid. If **pol1** had been defined under another firewall object, the configuration would not be valid.

```
[edit]
logical systems {
  ls-A {
    firewall {
      policer pol1 {
        if-exceeding {
          bandwidth-limit 401k;
          burst-size-limit 50k;
        }
        then discard;
      }
      filter filter1 {
        term one {
          from {
            source-address 12.1.0.0/16;
```



```
    }
    then {
        reject host-unknown;
    }
}
term two {
    from {
        source-address 12.2.0.0/16;
    }
    then policer pol1;
}
}
}
```

**Related  
Documentation**

- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
- [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
- [References from a Firewall Filter in a Logical System to Nonfirewall Objects on page 88](#)
- [References from a Nonfirewall Object in a Logical System to a Firewall Filter on page 90](#)

---

## References from a Firewall Filter in a Logical System to Nonfirewall Objects

This topic covers the following information:

- [Resolution of References from a Firewall Filter to Nonfirewall Objects on page 88](#)
- [Valid Reference to a Nonfirewall Object Outside of the Logical System on page 89](#)

### Resolution of References from a Firewall Filter to Nonfirewall Objects

In many cases, a firewall configuration references objects outside the firewall configuration. As a general rule, the referenced object must be defined under the same logical system as the referencing object. However, there are cases when the configuration of the referenced object is not supported at the `[edit logical-systems logical-system-name]` hierarchy level.



## Valid Reference to a Nonfirewall Object Outside of the Logical System

This example configuration illustrates an exception to the general rule that the objects referenced by a firewall filter in a logical system must be defined under the same logical system as the referencing object.

In the following scenario, the service filter **inetsf1** is applied to IPv4 traffic associated with the service set **fred** at the logical interface **fe-0/3/2.0**, which is on an adaptive services interface.

- Service filter **inetsf1** is defined in **ls-B** and references prefix list **prefix1**.
- Service set **fred** is defined at the main services hierarchy level, and the policy framework software searches the **[edit services]** hierarchy for the definition of the **fred** service set.

Because service rules cannot be configured in logical systems, firewall filter configurations in the **[edit logical-systems logical-system *logical-system-name*]** hierarchy are allowed to reference *service sets* outside the logical system hierarchy.

```
[edit]
logical-systems {
  ls-B {
    interfaces {
      fe-0/3/2 {
        unit 0 {
          family inet {
            service {
              input {
                service-set fred service-filter inetsf1;
              }
            }
          }
        }
      }
    }
  }
  policy-options {
    prefix-list prefix1 {
      1.1.0.0/16;
      1.2.0.0/16;
      1.3.0.0/16;
    }
  }
  firewall { # Under logical-system 'ls-B'.
    family inet {
      filter filter1 {
        term one {
          from {
            source-address {
              12.1.0.0/16;
            }
          }
          then {
            reject host-unknown;
          }
        }
        term two {
```



```
        from {
            source-address {
                12.2.0.0/16;
            }
        }
        then policer pol1;
    }
}
service-filter inetsf1 {
    term term1 {
        from {
            source-prefix-list {
                prefix1;
            }
        }
        then count prefix1;
    }
}
policer pol1 {
    if-exceeding {
        bandwidth-limit 401k;
        burst-size-limit 50k;
    }
    then discard;
}
}
} # End of logical systems configuration.
services { # Main services hierarchy level.
    service-set fred {
        max-flows 100;
        interface-service {
            service-interface sp-1/2/0.0;
        }
    }
}
```

**Related Documentation**

- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
- [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
- [References from a Firewall Filter in a Logical System to Subordinate Objects on page 87](#)
- [References from a Nonfirewall Object in a Logical System to a Firewall Filter on page 90](#)

---

## References from a Nonfirewall Object in a Logical System to a Firewall Filter

This topic covers the following information:

- [Resolution of References from a Nonfirewall Object to a Firewall Filter on page 91](#)
- [Invalid Reference to a Firewall Filter Outside of the Logical System on page 91](#)
- [Valid Reference to a Firewall Filter Within the Logical System on page 92](#)
- [Valid Reference to a Firewall Filter Outside of the Logical System on page 94](#)



## Resolution of References from a Nonfirewall Object to a Firewall Filter

If a nonfirewall filter object in a logical system references an object in a firewall filter configured in a logical system, the reference is resolved using the following logic:

- If the nonfirewall filter object is configured in a logical system that includes firewall filter configuration statements, the policy framework software searches the **[edit logical-systems *logical-system-name* firewall]** hierarchy level. Firewall filter configurations that belong to *other* logical systems or to the main **[edit firewall]** hierarchy level are not searched.
- If the nonfirewall filter object is configured in a logical system that does not include any firewall filter configuration statements, the policy framework software searches the firewall configurations defined at the **[edit firewall]** hierarchy level.

## Invalid Reference to a Firewall Filter Outside of the Logical System

This example configuration illustrates an unresolvable reference from a nonfirewall object in a logical system to a firewall filter.

In the following scenario, the stateless firewall filters **filter1** and **fred** are applied to the logical interface **fe-0/3/2.0** in the logical system **ls-C**.

- Filter **filter1** is defined in **ls-C**.
- Filter **fred** is defined in the main firewall configuration.

Because **ls-C** contains firewall filter statements (for **filter1**), the policy framework software resolves references to and from firewall filters by searching the **[edit logical systems ls-C firewall]** hierarchy level. Consequently, the reference from **fe-0/3/2.0** in the logical system to **fred** in the main firewall configuration cannot be resolved.

```
[edit]
logical-systems {
  ls-C {
    interfaces {
      fe-0/3/2 {
        unit 0 {
          family inet {
            filter {
              input-list [ filter1 fred ];
            }
          }
        }
      }
    }
  }
  firewall { # Under logical system 'ls-C'.
    family inet {
      filter filter1 {
        term one {
          from {
            source-address 12.1.0.0/16;
          }
          then {
            reject host-unknown;
          }
        }
      }
    }
  }
}
```



```

    }
  }
  term two {
    from {
      source-address 12.2.0.0/16;
    }
    then policer pol1;
  }
}
}
}
policer pol1 {
  if-exceeding {
    bandwidth-limit 401k;
    burst-size-limit 50k;
  }
  then discard;
}
}
}
} # End of logical systems
firewall { # Under the main firewall hierarchy level
  family inet {
    filter fred {
      term one {
        from {
          source-address 11.1.0.0/16;
        }
        then {
          log;
          reject host-unknown;
        }
      }
    }
  }
}
} # End of main firewall configurations.

```

## Valid Reference to a Firewall Filter Within the Logical System

This example configuration illustrates resolvable references from a nonfirewall object in a logical system to two firewall filter.

In the following scenario, the stateless firewall filters **filter1** and **fred** are applied to the logical interface **fe-0/3/2.0** in the logical system **ls-C**.

- Filter **filter1** is defined in **ls-C**.
- Filter **fred** is defined in **ls-C** and also in the main firewall configuration.

Because **ls-C** contains firewall filter statements, the policy framework software resolves references to and from firewall filters by searching the **[edit logical systems ls-C firewall]** hierarchy level. Consequently, the references from **fe-0/3/2.0** in the logical system to **filter1** and **fred** use the stateless firewall filters configured in **ls-C**.

```

[edit]
logical-systems {
  ls-C {
    interfaces {

```



```
fe-0/3/2 {
  unit 0 {
    family inet {
      filter {
        input-list [ filter1 fred ];
      }
    }
  }
}
}
firewall { # Under logical system 'ls-C'.
  family inet {
    filter filter1 {
      term one {
        from {
          source-address 12.1.0.0/16;
        }
        then {
          reject host-unknown;
        }
      }
      term two {
        from {
          source-address 12.2.0.0/16;
        }
        then policer pol1;
      }
    }
  }
  filter fred { # This 'fred' is in 'ls-C'.
    term one {
      from {
        source-address 10.1.0.0/16;
      }
      then {
        log;
        reject host-unknown;
      }
    }
  }
}
}
policer pol1 {
  if-exceeding {
    bandwidth-limit 401k;
    burst-size-limit 50k;
  }
  then discard;
}
}
}
} # End of logical systems configurations.
firewall { # Main firewall filter hierarchy level
  family inet {
    filter fred {
      term one {
        from {
          source-address 11.1.0.0/16;
```



```

    }
    then {
        log;
        reject host-unknown;
    }
}
}
}
} # End of main firewall configurations.

```

## Valid Reference to a Firewall Filter Outside of the Logical System

This example configuration illustrates resolvable references from a nonfirewall object in a logical system to two firewall filter.

In the following scenario, the stateless firewall filters **filter1** and **fred** are applied to the logical interface **fe-0/3/2.0** in the logical system **ls-C**.

- Filter **filter1** is defined in the main firewall configuration.
- Filter **fred** is defined in the main firewall configuration.

Because **ls-C** does not contain any firewall filter statements, the policy framework software resolves references to and from firewall filters by searching the **[edit firewall]** hierarchy level. Consequently, the references from **fe-0/3/2.0** in the logical system to **filter1** and **fred** use the stateless firewall filters configured in the main firewall configuration.

```

[edit]
logical-systems {
  ls-C {
    interfaces {
      fe-0/3/2 {
        unit 0 {
          family inet {
            filter {
              input-list [ filter1 fred ];
            }
          }
        }
      }
    }
  }
} # End of logical systems configurations.
firewall { # Main firewall hierarchy level.
  family inet {
    filter filter1 {
      term one {
        from {
          source-address 12.1.0.0/16;
        }
        then {
          reject host-unknown;
        }
      }
      term two {
        from {
          source-address 12.2.0.0/16;
        }
      }
    }
  }
}

```



```
        }
        then policer pol1;
    }
}
filter fred {
    term one {
        from {
            source-address 11.1.0.0/16;
        }
        then {
            log;
            reject host-unknown;
        }
    }
}
}
}
policer pol1 {
    if-exceeding {
        bandwidth-limit 701k;
        burst-size-limit 70k;
    }
    then discard;
}
} # End of main firewall configurations.
```

**Related  
Documentation**

- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
- [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
- [References from a Firewall Filter in a Logical System to Subordinate Objects on page 87](#)
- [References from a Firewall Filter in a Logical System to Nonfirewall Objects on page 88](#)







## PART 2

# Configuration

- [Standard Firewall Filter Configurations to Match Packets on page 99](#)
- [Standard Firewall Filters to Count Packets on page 111](#)
- [Standard Firewall Filters to Act on Packets on page 123](#)
- [Standard Firewall Filters for Trusted Sources on page 131](#)
- [Standard Firewall Filters for Flood Prevention on page 157](#)
- [Standard Firewall Filters for Fragment Handling on page 167](#)
- [Standard Firewall Filters for Setting Rate Limits on page 173](#)
- [Examples of Standard Firewall Filters Configuration on page 177](#)
- [Examples of Standard Firewall Filters Configuration Options on page 223](#)
- [Service Filters Configuration on page 233](#)
- [Simple Filters Configuration on page 239](#)
- [Firewall Filters Configuration in Logical Systems on page 245](#)







## CHAPTER 9

# Standard Firewall Filter Configurations to Match Packets

- [Example: Configuring a Filter to Match on IPv6 Flags on page 99](#)
- [Example: Configuring a Filter to Match on Port and Protocol Fields on page 100](#)
- [Example: Configuring a Filter to Match on Two Unrelated Criteria on page 103](#)
- [Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List on page 106](#)

### Example: Configuring a Filter to Match on IPv6 Flags

---

This example shows how to configure a filter to match on IPv6 TCP flags.

- [Requirements on page 99](#)
- [Overview on page 99](#)
- [Configuration on page 99](#)
- [Verification on page 100](#)

### Requirements

No special configuration beyond device initialization is required before configuring this example.

### Overview

In this example, you configure a filter to match on IPv6 TCP flags. You can use this example to configure IPv6 TCP flags in the SRX100, SRX210, SRX240, SRX650, and J Series security devices and in M Series, MX Series, and T Series routing devices.

### Configuration

#### Step-by-Step Procedure

To configure a filter to match on IPv6 TCP flags:

1. Include the family statement at the firewall hierarchy level, specifying **inet6** as the protocol family.

```
[edit]  
user@host# edit firewall family inet6
```



2. Create the stateless firewall filter.

```
[edit firewall family inet6]  
user@host# edit filter tcpfilt
```

3. Define the first term for the filter.

```
[edit firewall family inet6 filter tcpfilt]  
user@host# edit term 1
```

4. Define the source address match conditions for the term.

```
[edit firewall family inet6 filter tcpfilt term 1]  
user@host# set from next-header tcp tcp-flags syn
```

5. Define the actions for the term.

```
[edit firewall family inet6 filter tcpfilt term 1]  
user@host# set then count tcp_syn_pkt log accept
```

6. If you are done configuring the device, commit the configuration.

```
[edit firewall family inet6 filter tcpfilt term 1]  
user@host# top
```

```
[edit]  
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter tcpfilt** command.

---

## Example: Configuring a Filter to Match on Port and Protocol Fields

This example shows how to configure a standard stateless firewall filter to match on destination port and protocol fields.

- [Requirements on page 100](#)
- [Overview on page 100](#)
- [Configuration on page 101](#)
- [Verification on page 103](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you configure a stateless firewall filter that accepts all IPv4 packets except for TCP and UDP packets. TCP and UDP packets are accepted if destined for the SSH port or the Telnet port. All other packets are rejected.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Stateless Firewall Filter on page 101](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 102](#)
- [Confirm and Commit Your Candidate Configuration on page 102](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level:

```
set firewall family inet filter filter1 term term1 from protocol-except tcp
set firewall family inet filter filter1 term term1 from protocol-except udp
set firewall family inet filter filter1 term term1 then accept
set firewall family inet filter filter1 term term2 from address 192.168.0.0/16
set firewall family inet filter filter1 term term2 then reject
set firewall family inet filter filter1 term term3 from destination-port ssh
set firewall family inet filter filter1 term term3 from destination-port telnet
set firewall family inet filter filter1 term term3 then accept
set firewall family inet filter filter1 term term4 then reject
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input filter1
```

### Configure the Stateless Firewall Filter

### Step-by-Step Procedure

To configure the stateless firewall filter **filter1**:

1. Create the IPv4 stateless firewall filter.  
  
[edit]  
user@host# edit firewall family inet filter filter1
2. Configure a term to accept all traffic except for TCP and UDP packets.  
  
[edit firewall family inet filter filter1]  
user@host# set term term1 from protocol-except tcp  
user@host# set term term1 from protocol-except udp  
user@host# set term term1 then accept
3. Configure a term to reject packets to or from the **192.168/16** prefix.  
  
[edit firewall family inet filter filter1]  
user@host# set term term2 from address 192.168.0.0/16  
user@host# set term term2 then reject
4. Configure a term to accept packets destined for either the SSH port or the Telnet port.  
  
[edit firewall family inet filter filter1]  
user@host# set term term3 from destination-port ssh  
user@host# set term term3 from destination-port telnet  
user@host# set term term3 then accept



5. Configure the last term to reject all packets.

```
[edit firewall family inet filter filter1]
user@host# set term term4 then reject
```

---

### Apply the Stateless Firewall Filter to a Logical Interface

---

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input filter1
```

---

### Confirm and Commit Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter filter1 {
    term term1 {
      from {
        protocol-except [tcp udp];
      }
      then {
        accept;
      }
    }
    term term2 {
      from {
        address 192.168/16;
      }
      then {
        reject;
      }
    }
    term term3 {
      from {
        destination-port [ssh telnet];
      }
    }
  }
}
```



```

        then {
            accept;
        }
    }
    term term4 {
        then {
            reject;
        }
    }
}

```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@host# show interfaces
ge-0/0/1 {
    unit 0 {
        family inet {
            filter {
                input filter1;
            }
            address 10.1.2.3/30;
        }
    }
}

```

3. If you are done configuring the device, commit your candidate configuration.

```

[edit]
user@host# commit

```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter filter1** operational mode command.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Filter to Match on IPv6 Flags on page 99](#)
- [Example: Configuring a Filter to Match on Two Unrelated Criteria on page 103](#)

## Example: Configuring a Filter to Match on Two Unrelated Criteria

This example shows how to configure a standard stateless firewall filter to match on two unrelated criteria.

- [Requirements on page 104](#)
- [Overview on page 104](#)



- [Configuration on page 104](#)
- [Verification on page 106](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you use a standard stateless firewall filter to match IPv4 packets that are either OSPF packets or packets that come from an address in the prefix **10.108/16**, and send an **administratively-prohibited** ICMP message for all packets that do not match.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configuring the IPv4 Firewall Filter on page 104](#)
- [Applying the IPv4 Firewall Filter to a Logical Interface on page 105](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter ospf_or_131 term protocol_match from protocol ospf
set firewall family inet filter ospf_or_131 term address-match from source-address
  10.108.0.0/16
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input ospf_or_131
```

---

### Configuring the IPv4 Firewall Filter

### Step-by-Step Procedure

To configure the IPv4 firewall filter:

1. Enable configuration of the IPv4 firewall filter.

```
[edit]
user@host# edit firewall family inet filter ospf_or_131
```

2. Configure the first term to accept OSPF packets.

```
[edit firewall family inet filter ospf_or_131]
user@host# set term protocol_match from protocol ospf
```

Packets that match the condition are accepted by default. Because another term follows this term, packets that do not match this condition are evaluated by the next term.



3. Configure the second term to accept packets from any IPv4 address in a particular prefix.

```
[edit firewall family inet filter ospf_or_131]
user@host# set term address_match from source-address 10.108.0.0/16
```

Packets that match this condition are accepted by default. Because this is the last term in the filter, packets that do not match this condition are discarded by default.

**Results** Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this procedure to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter ospf_or_131 {
    term protocol_match {
      from {
        protocol ospf;
      }
    }
    term address_match {
      from {
        source-address {
          10.108.0.0/16;
        }
      }
    }
  }
}
```

### Applying the IPv4 Firewall Filter to a Logical Interface

**Step-by-Step Procedure** To apply the stateless firewall filter to a logical interface:

1. Enable configuration of a logical interface.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure an IP address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the IPv4 firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input ospf_or_131
```

**Results** Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this procedure to correct the configuration.

```
[edit]
```



```
user@host# show interfaces
ge-0/0/1 {
  unit 0 {
    family inet {
      filter {
        input ospf_or_131;
      }
      address 10.1.2.3/30;
    }
  }
}
```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter ospf\_or\_131** operational mode command.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Filter to Match on IPv6 Flags on page 99](#)
- [Example: Configuring a Filter to Match on Port and Protocol Fields on page 100](#)

---

## Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List

This example shows how to configure a standard stateless firewall filter that limits certain TCP and Internet Control Message Protocol (ICMP) traffic destined for the Routing Engine by specifying a list of prefix sources that contain allowed BGP peers.

- [Requirements on page 106](#)
- [Overview on page 106](#)
- [Configuration on page 107](#)
- [Verification on page 109](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you create a stateless firewall filter that blocks all TCP connection attempts to port 179 from all requesters except BGP peers that have a specified prefix.

A source prefix list, **plist\_bgp179**, is created that specifies the list of source prefixes that contain allowed BGP peers.

The stateless firewall filter **filter\_bgp179** matches all packets from the source prefix list **plist\_bgp179** to the destination port number 179.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Filter on page 107](#)
- [Results on page 108](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set policy-options prefix-list plist_bgp179 apply-path "protocols bgp group <*> neighbor <*>"
set firewall family inet filter filter_bgp179 term 1 from source-address 0.0.0.0/0
set firewall family inet filter filter_bgp179 term 1 from source-prefix-list plist_bgp179 except
set firewall family inet filter filter_bgp179 term 1 from destination-port bgp
set firewall family inet filter filter_bgp179 term 1 then reject
set firewall family inet filter filter_bgp179 term 2 then accept
set interfaces lo0 unit 0 family inet filter input filter_bgp179
set interfaces lo0 unit 0 family inet address 127.0.0.1/32
```

### Configure the Filter

### Step-by-Step Procedure

The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure the filter:

1. Expand the prefix list **bgp179** to include all prefixes pointed to by the BGP peer group defined by **protocols bgp group <\*> neighbor <\*>**.

```
[edit policy-options prefix-list plist_bgp179]
user@host# set apply-path "protocols bgp group <*> neighbor <*>"
```

2. Define the filter term that rejects TCP connection attempts to port 179 from all requesters except the specified BGP peers.

```
[edit firewall family inet filter filter_bgp179]
user@host# set term term1 from source-address 0.0.0.0/0
user@host# set term term1 from source-prefix-list bgp179 except
user@host# set term term1 from destination-port bgp
user@host# set term term1 then reject
```

3. Define the other filter term to accept all packets.

```
[edit firewall family inet filter filter_bgp179]
user@host# set term term2 then accept
```

4. Apply the firewall filter to the loopback interface.

```
[edit interfaces lo0 unit 0 family inet]
user@host# set filter input filter_bgp179
```



```
user@host# set address 127.0.0.1/32
```

From configuration mode, confirm your configuration by entering the **show firewall**, **show interfaces**, and **show policy-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show firewall
family inet {
  filter filter_bgp179 {
    term 1 {
      from {
        source-address {
          0.0.0.0/0;
        }
        source-prefix-list {
          plist_bgp179 except;
        }
        destination-port bgp;
      }
      then {
        reject;
      }
    }
    term 2 {
      then {
        accept;
      }
    }
  }
}

user@host# show interfaces
lo0 {
  unit 0 {
    family inet {
      filter {
        input filter_bgp179;
      }
      address 127.0.0.1/32;
    }
  }
}

user@host# show policy-options
prefix-list plist_bgp179 {
  apply-path "protocols bgp group <*> neighbor <*>";
}
```

If you are done configuring the device, enter **commit** from configuration mode.

Repeat the procedure, where appropriate, for every BGP-enabled device in the network, using the appropriate interface names and addresses for each BGP-enabled device.



## Verification

Confirm that the configuration is working properly.

### Displaying the Firewall Filter Applied to the Loopback Interface

**Purpose** Verify that the firewall filter **filter\_bgp179** is applied to the IPv4 input traffic at logical interface **lo0.0**.

**Action** Use the **show interfaces statistics** operational mode command for logical interface **lo0.0**, and include the **detail** option. Under the **Protocol inet** section of the command output section, the **Input Filters** field displays the name of the stateless firewall filter applied to the logical interface in the input direction:

```
[edit]
user@host> show interfaces statistics lo0.0 detail
Logical interface lo0.0 (Index 321) (SNMP ifIndex 16) (Generation 130)
  Flags: SNMP-Traps Encapsulation: Unspecified
  Traffic statistics:
    Input bytes : 0
    Output bytes : 0
    Input packets: 0
    Output packets: 0
  Local statistics:
    Input bytes : 0
    Output bytes : 0
    Input packets: 0
    Output packets: 0
  Transit statistics:
    Input bytes : 0 0 bps
    Output bytes : 0 0 bps
    Input packets: 0 0 pps
    Output packets: 0 0 pps
  Protocol inet, MTU: Unlimited, Generation: 145, Route table: 0
    Flags: Sendbroadcast-pkt-to-re
    Input Filters: filter_bgp179
    Addresses, Flags: Primary
      Destination: Unspecified, Local: 127.0.0.1, Broadcast: Unspecified,
      Generation: 138
```

- Related Documentation**
- [Understanding How to Use Standard Firewall Filters on page 27](#)
  - [Firewall Filter Match Conditions Based on Address Fields on page 35](#)
  - [Example: Configuring a Stateless Firewall Filter to Protect Against TCP and ICMP Floods on page 157](#)
  - [Example: Configuring a Filter to Accept Packets Based on IPv6 TCP Flags on page 164](#)
  - [“prefix-list on page 347” in the Routing Policy Configuration Guide](#)







## CHAPTER 10

# Standard Firewall Filters to Count Packets

- [Example: Configuring a Filter to Count Accepted and Rejected Packets on page 111](#)
- [Example: Configuring a Filter to Count and Discard IP Options Packets on page 114](#)
- [Example: Configuring a Filter to Count IP Options Packets on page 117](#)

### Example: Configuring a Filter to Count Accepted and Rejected Packets

---

This example shows how to configure a firewall filter to count packets.

- [Requirements on page 111](#)
- [Overview on page 111](#)
- [Configuration on page 111](#)
- [Verification on page 114](#)

#### Requirements

No special configuration beyond device initialization is required before configuring this example.

#### Overview

In this example, you use a stateless firewall filter to reject all addresses except 192.168.5.0/24.

#### Topology

---

In the first term, the match condition **address 192.168.5.0/24 except** causes this address to be considered a mismatch, and this address is passed to the next term in the filter. The match condition **address 0.0.0.0/0** matches all other packets, and these are counted, logged, and rejected.

In the second term, all packets that passed through the first term (that is, packets whose address matches **192.168.5.0/24**) are counted, logged, and accepted.

#### Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).



To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 112](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 112](#)
- [Confirm and Commit Your Candidate Configuration on page 113](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter fire1 term 1 from address 192.168.5.0/24 except
set firewall family inet filter fire1 term 1 from address 0.0.0.0/0
set firewall family inet filter fire1 term 1 then count reject_pref1_1
set firewall family inet filter fire1 term 1 then log
set firewall family inet filter fire1 term 1 then reject
set firewall family inet filter fire1 term 2 then count reject_pref1_2
set firewall family inet filter fire1 term 2 then log
set firewall family inet filter fire1 term 2 then accept
set interfaces ge-0/0/1 unit 0 family inet filter input fire1
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
```

---

#### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter **fire1**:

1. Create the stateless firewall filter **fire1**.

```
[edit]
user@host# edit firewall family inet filter fire1
```

2. Configure the first term to reject all addresses except those to or from the **192.168.5.0/24** prefix and then count, log, and reject all other packets.

```
[edit firewall family inet filter fire1]
user@host# set term 1 from address 192.168.5.0/24 except
user@host# set term 1 from address 0.0.0.0/0
user@host# set term 1 then count reject_pref1_1
user@host# set term 1 then log
user@host# set term 1 then reject
```

3. Configure the next term to count, log, and accept packets in the **192.168.5.0/24** prefix.

```
[edit firewall family inet filter fire1]
user@host# set term 2 then count reject_pref1_2
user@host# set term 2 then log
user@host# set term 2 then accept
```

---

#### Apply the Stateless Firewall Filter to a Logical Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```



2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input fire1
```

### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter fire1 {
    term 1 {
      from {
        address {
          192.168.5.0/24 except;
          0.0.0.0/0;
        }
      }
      then {
        count reject_pref1_1;
        log;
        reject;
      }
    }
    term 2 {
      then {
        count reject_pref1_2;
        log;
        accept;
      }
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
ge-0/0/1 {
  unit 0 {
    family inet {
      filter {
        input fire1;
      }
    }
  }
}
```



```
        address 10.1.2.3/30;
    }
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter fire1** operational mode command. You can also display the log and individual counters separately by using the following forms of the command:

- **show firewall counter reject\_pref1\_1**
- **show firewall counter reject\_pref1\_2**
- **show firewall log**

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Filter to Count IP Options Packets on page 117](#)
- [Example: Configuring a Filter to Count and Discard IP Options Packets on page 114](#)

---

## Example: Configuring a Filter to Count and Discard IP Options Packets

This example shows how to configure a standard stateless firewall to count packets.

- [Requirements on page 114](#)
- [Overview on page 114](#)
- [Configuration on page 115](#)
- [Verification on page 117](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

Because the filter term matches on *any* IP option value, the filter term can use the **count** nonterminating action without the **discard** terminating action or (alternatively) without requiring an interface on a 10-Gigabit Ethernet Modular Port Concentrator (MPC), 60-Gigabit Ethernet MPC, 60-Gigabit Queuing Ethernet MPC, or 60-Gigabit Ethernet Enhanced Queuing MPC on an MX Series router.

## Overview

In this example, you use a standard stateless firewall filter to count and discard packets that include any IP option value but accept all other packets.



The IP option header field is an optional field in IPv4 headers only. The **ip-options** and **ip-options-except** match conditions are supported for standard stateless firewall filters and service filters only.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 115](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 115](#)
- [Confirm and Commit Your Candidate Configuration on page 116](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter block_ip_options term 10 from ip-options any
set firewall family inet filter block_ip_options term 10 then count option_any
set firewall family inet filter block_ip_options term 10 then discard
set firewall family inet filter block_ip_options term 999 then accept
set interfaces ge-0/0/1 unit 0 family inet filter input block_ip_options
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
```

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter:

1. Create the stateless firewall filter **block\_ip\_options**.  
  
[edit]  
user@host# edit firewall family inet filter block\_ip\_options
2. Configure the first term to count and discard packets that include any IP options header fields.  
  
[edit firewall family inet filter block\_ip\_options]  
user@host# set term 10 from ip-options any  
user@host# set term 10 then count option\_any  
user@host# set term 10 then discard
3. Configure the other term to accept all other packets.  
  
[edit firewall family inet filter block\_ip\_options]  
user@host# set term 999 then accept

### Apply the Stateless Firewall Filter to a Logical Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.  
  
[edit]



```
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
```

```
user@host# set address 10.1.2.3/30
```

3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
```

```
user@host# set filter input block_ip_options
```

### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter block_ip_options {
    term 10 {
      from {
        ip-options any;
      }
      then {
        count option_any;
        discard;
      }
    }
    term 999 {
      then accept;
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
ge-0/0/1 {
  unit 0 {
    family inet {
      filter {
        input block_ip_options;
      }
      address 10.1.2.3/30;
    }
  }
}
```



3. If you are done configuring the device, commit your candidate configuration.

```
[edit]  
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter block\_ip\_options** operational mode command. To display the count of discarded packets separately, enter the **show firewall count option\_any** form of the command.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Filter to Count Accepted and Rejected Packets on page 111](#)
- [Example: Configuring a Filter to Count IP Options Packets on page 117](#)

---

## Example: Configuring a Filter to Count IP Options Packets

This example shows how use a stateless firewall filter to count individual IP options packets:

- [Requirements on page 117](#)
- [Overview on page 117](#)
- [Configuration on page 118](#)
- [Verification on page 121](#)

## Requirements

This example uses an interface on a 10-Gigabit Ethernet Modular Port Concentrator (MPC), 60-Gigabit Ethernet MPC, 60-Gigabit Queuing Ethernet MPC, or 60-Gigabit Ethernet Enhanced Queuing MPC on an MX Series router. This interface enables you to apply an IPv4 firewall filter (standard or service filter) that can use the **count**, **log**, and **syslog** nonterminating actions on packets that match a *specific ip-option* value without having to also use the **discard** terminating action.

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you use a stateless firewall filter to count IP options packets but not block any traffic. Also, the filter logs packets that have loose or strict source routing.

The IP option header field is an optional field in IPv4 headers only. The **ip-options** and **ip-options-except** match conditions are supported for standard stateless firewall filters and service filters only.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 118](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 119](#)
- [Confirm and Commit Your Candidate Configuration on page 120](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter ip_options_filter term match_strict_source from ip-options
strict-source-route
set firewall family inet filter ip_options_filter term match_strict_source then count
strict_source_route
set firewall family inet filter ip_options_filter term match_strict_source then log
set firewall family inet filter ip_options_filter term match_strict_source then accept
set firewall family inet filter ip_options_filter term match_loose_source from ip-options
loose-source-route
set firewall family inet filter ip_options_filter term match_loose_source then count
loose_source_route
set firewall family inet filter ip_options_filter term match_loose_source then log
set firewall family inet filter ip_options_filter term match_loose_source then accept
set firewall family inet filter ip_options_filter term match_record from ip-options
record-route
set firewall family inet filter ip_options_filter term match_record then count record_route
set firewall family inet filter ip_options_filter term match_record then accept
set firewall family inet filter ip_options_filter term match_timestamp from ip-options
timestamp
set firewall family inet filter ip_options_filter term match_timestamp then count timestamp
set firewall family inet filter ip_options_filter term match_timestamp then accept
set firewall family inet filter ip_options_filter term match_router_alert from ip-options
router-alert
set firewall family inet filter ip_options_filter term match_router_alert then count
router_alert
set firewall family inet filter ip_options_filter term match_router_alert then accept
set firewall family inet filter ip_options_filter term match_all then accept
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input ip_options_filter
```

---

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter **ip\_option\_filter**:

1. Create the stateless firewall filter **ip\_option\_filter**.

```
[edit]
user@host# edit firewall family inet filter ip_options_filter
```



2. Configure the first term to count, log, and accept packets with the **strict\_source\_route** IP optional header field.

```
[edit firewall family inet filter ip_option_filter]
user@host# set term match_strict_source from ip-options strict_source_route
user@host# set term match_strict_source then count strict_source_route
user@host# set term match_strict_source then log
user@host# set term match_strict_source then accept
```

3. Configure the next term to count, log, and accept packets with the **loose-source-route** IP optional header field.

```
[edit firewall family inet filter ip_option_filter]
user@host# set term match_loose_source from ip-options loose-source-route
user@host# set term match_loose_source then count loose_source_route
user@host# set term match_loose_source then log
user@host# set term match_loose_source then accept
```

4. Configure the next term to count and accept packets with the **record-route** IP optional header field.

```
[edit firewall family inet filter ip_option_filter]
user@host# set term match_record from ip-options record-route
user@host# set term match_record then count record_route
user@host# set term match_record then accept
```

5. Configure the next term to count and accept packets with the **timestamp** IP optional header field.

```
[edit firewall family inet filter ip_option_filter]
user@host# set term match_timestamp from ip-options timestamp
user@host# set term match_timestamp then count timestamp
user@host# set term match_timestamp then accept
```

6. Configure the next term to count and accept packets with the **router-alert** IP optional header field.

```
[edit firewall family inet filter ip_option_filter]
user@host# set term match_router_alert from ip-options router-alert
user@host# set term match_router_alert then count router_alert
user@host# set term match_router_alert then accept
```

7. Create the last term to accept any packet without incrementing any counters.

```
[edit firewall family inet filter ip_option_filter]
user@host# set term match_all then accept
```

### Apply the Stateless Firewall Filter to a Logical Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
```



```
user@host# set address 10.1.2.3/30
```

3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]  
user@host# set filter input ip_options_filter
```

---

### Confirm and Commit Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]  
user@host# show firewall  
family inet {  
  filter ip_options_filter {  
    term match_strict_source {  
      from {  
        ip-options strict-source-route;  
      }  
      then {  
        count strict_source_route;  
        log;  
        accept;  
      }  
    }  
    term match_loose_source {  
      from {  
        ip-options loose-source-route;  
      }  
      then {  
        count loose_source_route;  
        log;  
        accept;  
      }  
    }  
    term match_record {  
      from {  
        ip-options record-route;  
      }  
      then {  
        count record_route;  
        accept;  
      }  
    }  
    term match_timestamp {  
      from {  
        ip-options timestamp;  
      }  
      then {  
        count timestamp;  
        accept;  
      }  
    }  
  }  
}
```



```

    }
    term match_router_alert {
        from {
            ip-options router-alert;
        }
        then {
            count router_alert;
            accept;
        }
    }
    term match_all {
        then accept;
    }
}
}

```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@host# show interfaces
ge-0/0/1 {
    unit 0 {
        family inet {
            filter {
                input ip_option_filter;
            }
            address 10.1.2.3/30;
        }
    }
}

```

3. If you are done configuring the device, commit your candidate configuration.

```

[edit]
user@host# commit

```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter ip\_option\_filter** operational mode command. You can also display the log and individual counters separately by using the following forms of the command:

- **show firewall counter strict\_source\_route**
- **show firewall counter loose\_source\_route**
- **show firewall counter record\_route**
- **show firewall counter timestamp**
- **show firewall counter router\_alert**
- **show firewall log**



**Related  
Documentation**

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Filter to Count Accepted and Rejected Packets on page 111](#)
- [Example: Configuring a Filter to Count and Discard IP Options Packets on page 114](#)



## CHAPTER 11

# Standard Firewall Filters to Act on Packets

- [Example: Configuring a Filter to Set the DSCP Bit to Zero on page 123](#)
- [Example: Configuring a Filter to Count and Sample Accepted Packets on page 126](#)

### Example: Configuring a Filter to Set the DSCP Bit to Zero

---

This example shows how to configure a standard stateless firewall filter based on the Differentiated Services code point (DSCP).

- [Requirements on page 123](#)
- [Overview on page 123](#)
- [Configuration on page 123](#)
- [Verification on page 126](#)

#### Requirements

No special configuration beyond device initialization is required before configuring this example.

#### Overview

In this example, you use a stateless firewall filter to match packets on DSCP bit patterns. If the DSCP is **2**, the packet is classified to the **best-effort** forwarding class, and the DSCP is set to **0**. If the DSCP is **3**, the packet is classified to the **best-effort** forwarding class.

#### Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 124](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 124](#)
- [Confirm and Commit Your Candidate Configuration on page 125](#)



**CLI Quick Configuration** To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall filter filter1 term 1 from dscp 2
set firewall filter filter1 term 1 then forwarding-class best-effort
set firewall filter filter1 term 1 then dscp 0
set firewall filter filter1 term 2 from dscp 3
set firewall filter filter1 term 2 then forwarding-class best-effort
set interfaces so-0/1/0 unit 0 family inet filter input filter1
```

---

### Configure the Stateless Firewall Filter

**Step-by-Step Procedure** To configure the stateless firewall filter **filter1**:

1. Create the stateless firewall filter.

```
[edit]
user@host# edit firewall filter filter1
```

2. Configure the first term to match a packet with a DSCP of **2**, change the DSCP to **0**, and classify the packet to the **best-effort** forwarding class.

```
[edit firewall filter filter1]
user@host# set term 1 from dscp 2
user@host# set term 1 then forwarding-class best-effort
user@host# set term 1 then dscp 0
```

3. Configure the other term to match a packet with a DSCP of **3** and classify the packet to the **best-effort** forwarding class.

```
[edit firewall filter filter1]
user@host# set term 2 from dscp 3
user@host# set term 2 then forwarding-class best-effort
```

---

### Apply the Stateless Firewall Filter to a Logical Interface

**Step-by-Step Procedure** To apply the stateless firewall filter to the logical interface corresponding to the VPN routing and forwarding (VRF) instance:

1. Configure the logical interface to which you will apply the stateless firewall filter.

```
[edit]
user@host# edit interfaces so-0/1/0 unit 0 family inet
```

2. Apply the stateless firewall filter to the logical interface.

```
[ input filter1]
user@host# set filter input filter1
```



### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
filter filter1 {
  term term1 {
    from {
      dscp 2;
    }
    then {
      forwarding-class best-effort;
      dscp 0;
    }
  }
  term term2 {
    from {
      dscp 3;
    }
    then {
      forwarding-class best-effort;
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
so-0/1/0 {
  unit 0 {
    family inet {
      filter input filter1;
    }
  }
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]
user@host# commit
```



## Verification

To confirm that the configuration is working properly, enter the following operational mode commands:

- **show class-of-service**—Displays the entire class-of-service (CoS) configuration, including system-chosen defaults.
- **show class-of-service classifier type dscp**—Displays only the classifiers of the DSCP for IPv4 type.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Filter to Count and Sample Accepted Packets on page 126](#)

---

## Example: Configuring a Filter to Count and Sample Accepted Packets

This example shows how to configure a standard stateless firewall filter to count and sample accepted packets.

- [Requirements on page 126](#)
- [Overview on page 126](#)
- [Configuration on page 126](#)
- [Verification on page 128](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

Before you begin, configure traffic sampling by including the **sampling** statement at the **[edit forwarding-options]** hierarchy level.

## Overview

In this example, you use a standard stateless firewall filter to count and sample all packets received on a logical interface.



**NOTE:** When you enable reverse path forwarding (RPF) on an interface with an input filter for firewall log and count, the input firewall filter does not log the packets rejected by RPF, although the rejected packets are counted. To log the rejected packets, use an RPF check fail filter.

---

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).



To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 127](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 127](#)
- [Confirm and Commit Your Candidate Configuration on page 128](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter sam term all then count count_sam
set firewall family inet filter sam term all then sample
set interfaces at-2/0/0 unit 301 family inet address 10.1.2.3/30
set interfaces at-2/0/0 unit 301 family inet filter input sam
```

#### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter **sam**:

1. Create the stateless firewall filter **sam**.  
  

```
[edit]
user@host# edit firewall family inet filter sam
```
2. Configure the term to count and sample all packets.  
  

```
[edit firewall family inet filter sam]
user@host# set term all then count count_sam
user@host# set term all then sample
```

#### Apply the Stateless Firewall Filter to a Logical Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.  
  

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```
2. Configure the interface address for the logical interface.  
  

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```
3. Apply the stateless firewall filter to the logical interface.  
  

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input sam
```



**NOTE:** The Junos OS does not sample packets originating from the router. If you configure a filter and apply it to the output side of an interface, then only the transit packets going through that interface are sampled. Packets that are sent from the Routing Engine to the Packet Forwarding Engine are not sampled.



### Confirm and Commit Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter sam {
    term all {
      then {
        count count_sam;
        sample; # default action is accept
      }
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
interfaces {
  at-2/0/0 {
    unit 301 {
      family inet {
        filter {
          input sam;
        }
        address 10.1.2.3/30;
      }
    }
  }
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]
user@host# commit
```

### Verification

Confirm that the configuration is working properly.

- [Displaying the Packet Counter on page 129](#)
- [Displaying the Firewall Filter Log Output on page 129](#)
- [Displaying the Sampling Output on page 130](#)



### Displaying the Packet Counter

**Purpose** Verify that the firewall filter is evaluating packets.

**Action** user@host> show firewall filter sam  
 Filter:  
 Counters:  

Name	Bytes	Packets
sam		
sam-1	98	8028

### Displaying the Firewall Filter Log Output

**Purpose** Display the packet header information for all packets evaluated by the firewall filter.

**Action** user@host> show firewall log

Time	Filter	A	Interface	Pro	Source address	Destination address
23:09:09	-	A	at-2/0/0.301	TCP	10.2.0.25	10.211.211.1:80
23:09:07	-	A	at-2/0/0.301	TCP	10.2.0.25	10.211.211.1:56
23:09:07	-	A	at-2/0/0.301	ICM	10.2.0.25	10.211.211.1:49552
23:02:27	-	A	at-2/0/0.301	TCP	10.2.0.25	10.211.211.1:56
23:02:25	-	A	at-2/0/0.301	TCP	10.2.0.25	10.211.211.1:80
23:01:22	-	A	at-2/0/0.301	ICM	10.2.2.101	10.211.211.1:23251
23:01:21	-	A	at-2/0/0.301	ICM	10.2.2.101	10.211.211.1:16557
23:01:20	-	A	at-2/0/0.301	ICM	10.2.2.101	10.211.211.1:29471
23:01:19	-	A	at-2/0/0.301	ICM	10.2.2.101	10.211.211.1:26873

**Meaning** This output file contains the following fields:

- **Time**—Time at which the packet was received (not shown in the default).
- **Filter**—Name of a filter that has been configured with the **filter** statement at the **[edit firewall]** hierarchy level. A hyphen (-) or the abbreviation **pfe** indicates that the packet was handled by the Packet Forwarding Engine. A space (no hyphen) indicates that the packet was handled by the Routing Engine.
- **A**—Filter action:
  - **A**—Accept (or next term)
  - **D**—Discard
  - **R**—Reject
- **Interface**—Interface on which the filter is configured.



**NOTE:** We strongly recommend that you always explicitly configure an action in the **then** statement.

- **Pro**—Packet's protocol name or number.
- **Source address**—Source IP address in the packet.
- **Destination address**—Destination IP address in the packet.



## Displaying the Sampling Output

---

**Purpose** Verify that the sampling output contains appropriate data.

**Action**

```
wtmp.0.gz          Size: 15017, Last changed: Dec 19 13:15:54 wtmp.1.gz
                  Size: 493, Last changed: Nov 19 13:47:29
wtmp.2.gz          Size: 57, Last changed: Oct 20 15:24:34
|                  Pipe through a command
```

```
user@host> show log /var/tmp/sam
```

```
# Apr 7 15:48:50
```

Time	Dest addr	Src addr	Dest port	Src port	Proto	TOS	Pkt len	Intf num	IP frag	TCP flags
Apr 7 15:48:54	192.168.9.194	192.168.9.195	0	0	1	0x0	84	8	0x0	0x0
Apr 7 15:48:55	192.168.9.194	192.168.9.195	0	0	1	0x0	84	8	0x0	0x0
Apr 7 15:48:56	192.168.9.194	192.168.9.195	0	0	1	0x0	84	8	0x0	0x0

- Related Documentation**
- [Understanding How to Use Standard Firewall Filters on page 27](#)
  - [Example: Configuring a Filter to Set the DSCP Bit to Zero on page 123](#)



## CHAPTER 12

# Standard Firewall Filters for Trusted Sources

- [Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources on page 131](#)
- [Example: Configuring a Filter to Block Telnet and SSH Access on page 136](#)
- [Example: Configuring a Filter to Block TFTP Access on page 141](#)
- [Example: Configuring a Filter to Accept OSPF Packets from a Prefix on page 144](#)
- [Example: Configuring a Filter to Accept DHCP Packets Based on Address on page 147](#)
- [Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers on page 150](#)

### Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources

This example shows how to create a stateless firewall filter that protects the Routing Engine from traffic originating from untrusted sources.

- [Requirements on page 131](#)
- [Overview on page 131](#)
- [Configuration on page 132](#)
- [Verification on page 134](#)

#### Requirements

No special configuration beyond device initialization is required before configuring stateless firewall filters.

#### Overview

In this example, you create a stateless firewall filter called `protect-RE` that discards all traffic destined for the Routing Engine except SSH and BGP protocol packets from specified trusted sources. This example includes the following firewall filter terms:

- **ssh-term**—Accepts TCP packets with a source address of `192.168.122.0/24` and a destination port that specifies SSH.



- **bgp-term**—Accepts TCP packets with a source address of 10.2.1.0/24 and a destination port that specifies BGP.
- **discard-rest-term**—For all packets that are not accepted by **ssh-term** or **bgp-term**, creates a firewall filter log and system logging records, then discards all packets.



**NOTE:** You can move terms within the firewall filter using the `insert` command. See `insert` in the CLI User Guide.

## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the `[edit]` hierarchy level.

```
set firewall family inet filter protect-RE term ssh-term from source-address
  192.168.122.0/24
set firewall family inet filter protect-RE term ssh-term from protocol tcp
set firewall family inet filter protect-RE term ssh-term from destination-port ssh
set firewall family inet filter protect-RE term ssh-term then accept
set firewall family inet filter protect-RE term bgp-term from source-address 10.2.1.0/24
set firewall family inet filter protect-RE term bgp-term from protocol tcp
set firewall family inet filter protect-RE term bgp-term from destination-port bgp
set firewall family inet filter protect-RE term bgp-term then accept
set firewall family inet filter protect-RE term discard-rest-term then log
set firewall family inet filter protect-RE term discard-rest-term then syslog
set firewall family inet filter protect-RE term discard-rest-term then discard
set interfaces lo0 unit 0 family inet filter input protect-RE
```

### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure the stateless firewall filter:

1. Create the stateless firewall filter.

```
[edit]
user@host# edit firewall family inet filter protect-RE
```

2. Create the first filter term.

```
[edit firewall family inet filter protect-RE]
user@host# edit term ssh-term
```

3. Define the protocol, destination port, and source address match conditions for the term.

```
[edit firewall family inet filter protect-RE term ssh-term]
user@host# set from protocol tcp destination-port ssh source-address
  192.168.122.0/24
```



4. Define the actions for the term.

```
[edit firewall family inet filter protect-RE term ssh-term]
user@host# set then accept
```

5. Create the second filter term.

```
[edit firewall family inet filter protect-RE]
user@host# edit term bgp-term
```

6. Define the protocol, destination port, and source address match conditions for the term.

```
[edit firewall family inet filter protect-RE term bgp-term]
user@host# set from protocol tcp destination-port bgp source-address 10.2.1.0/24
```

7. Define the action for the term.

```
[edit firewall family inet filter protect-RE term bgp-term]
user@host# set then accept
```

8. Create the third filter term.

```
[edit firewall family inet filter protect-RE]
user@host# edit term discard-rest-term
```

9. Define the action for the term.

```
[edit firewall family inet filter protect-RE term discard-rest]
user@host# set then log syslog discard
```

10. Apply the filter to the input side of the Routing Engine interface.

```
[edit]
user@host# set interfaces lo0 unit 0 family inet filter input protect-RE
```

**Results** Confirm your configuration by entering the **show firewall** command and the **show interfaces lo0** command from configuration mode. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show firewall
family inet {
  filter protect-RE {
    term ssh-term {
      from {
        source-address {
          192.168.122.0/24;
        }
        protocol tcp;
        destination-port ssh;
      }
      then accept;
    }
    term bgp-term {
      from {
        source-address {
          10.2.1.0/24;
        }
      }
    }
  }
}
```



```
        protocol tcp;
        destination-port bgp;
    }
    then accept;
}
term discard-rest-term {
    then {
        log;
        syslog;
        discard;
    }
}
}
}
```

```
user@host# show interfaces lo0
unit 0 {
    family inet {
        filter {
            input protect-RE;
        }
        address 127.0.0.1/32;
    }
}
```

If you are done configuring the device, enter **commit** from configuration mode.

```
[edit]
user@host# commit
```

## Verification

To confirm that the configuration is working properly, perform these tasks:

- [Displaying Stateless Firewall Filter Configurations on page 134](#)
- [Verifying a Services, Protocols, and Trusted Sources Firewall Filter on page 134](#)
- [Displaying Stateless Firewall Filter Logs on page 135](#)

---

### Displaying Stateless Firewall Filter Configurations

<b>Purpose</b>	Verify the configuration of the firewall filter.
<b>Action</b>	From configuration mode, enter the <b>show firewall</b> command and the <b>show interfaces lo0</b> command.
<b>Meaning</b>	Verify that the output shows the intended configuration of the firewall filter. In addition, verify that the terms are listed in the order in which you want the packets to be tested. You can move terms within a firewall filter by using the <b>insert</b> CLI command.

---

### Verifying a Services, Protocols, and Trusted Sources Firewall Filter

<b>Purpose</b>	Verify that the actions of the firewall filter terms are taken.
----------------	---



**Action** Send packets to the device that match the terms. In addition, verify that the filter actions are *not* taken for packets that do not match.

- Use the **ssh *host-name*** command from a host at an IP address that matches **192.168.122.0/24** to verify that you can log in to the device using only SSH from a host with this address prefix.
- Use the **show route summary** command to verify that the routing table on the device does not contain any entries with a protocol other than **Direct**, **Local**, **BGP**, or **Static**.

## Sample Output

```
% ssh 192.168.249.71
%ssh host
user@host's password:
--- JUNOS 6.4-20040518.0 (JSERIES) #0: 2004-05-18 09:27:50 UTC

user@host>

user@host> show route summary
Router ID: 192.168.249.71

inet.0: 34 destinations, 34 routes (33 active, 0 holddown, 1 hidden)
      Direct: 10 routes, 9 active
        Local: 9 routes, 9 active
         BGP: 10 routes, 10 active
        Static: 5 routes, 5 active
...
```

**Meaning** Verify the following information:

- You can successfully log in to the device using SSH.
- The **show route summary** command does not display a protocol other than **Direct**, **Local**, **BGP**, or **Static**.

## Displaying Stateless Firewall Filter Logs

**Purpose** Verify that packets are being logged. If you included the **log** or **syslog** action in a term, verify that packets matching the term are recorded in the firewall log or your system logging facility.

**Action** From operational mode, enter the **show firewall log** command.

## Sample Output

```
user@host> show firewall log
Log :
Time      Filter  Action Interface  Protocol  Src Addr  Dest Addr
15:11:02  pfe         D    ge-0/0/0.0   TCP       172.17.28.19 192.168.70.71
15:11:01  pfe         D    ge-0/0/0.0   TCP       172.17.28.19 192.168.70.71
15:11:01  pfe         D    ge-0/0/0.0   TCP       172.17.28.19 192.168.70.71
15:11:01  pfe         D    ge-0/0/0.0   TCP       172.17.28.19 192.168.70.71
...
```



**Meaning** Each record of the output contains information about the logged packet. Verify the following information:

- Under **Time**, the time of day the packet was filtered is shown.
- The **Filter** output is always **pfe**.
- Under **Action**, the configured action of the term matches the action taken on the packet—**A** (accept), **D** (discard), **R** (reject).
- Under **Interface**, the inbound (ingress) interface on which the packet arrived is appropriate for the filter.
- Under **Protocol**, the protocol in the IP header of the packet is appropriate for the filter.
- Under **Src Addr**, the source address in the IP header of the packet is appropriate for the filter.
- Under **Dest Addr**, the destination address in the IP header of the packet is appropriate for the filter.

**Related Documentation**

- *Junos OS Feature Support Reference for SRX Series and J Series Devices*
- show route summary in the Junos OS Operational Mode Commands
- show firewall in the Junos OS Operational Mode Commands
- show firewall log in the Junos OS Operational Mode Commands
- show interfaces (Loopback) in the Junos OS Operational Mode Commands

---

## Example: Configuring a Filter to Block Telnet and SSH Access

---

- [Requirements on page 136](#)
- [Overview on page 136](#)
- [Configuration on page 137](#)
- [Verification on page 139](#)

### Requirements

You must have access to a remote host that has network connectivity with this router.

### Overview

In this example, you create an IPv4 stateless firewall filter that logs and rejects Telnet or SSH access packets unless the packet is destined for or originates from the 192.168.1.0/24 subnet.

- To match packets destined for or originating from the **address 192.168.1.0/24** subnet, you use the **address 192.168.1.0/24** IPv4 match condition.
- To match packets destined for or originating from a TCP port, Telnet port, or SSH port, you use the **protocol tcp**, **port telnet**, and **telnet ssh** IPv4 match conditions.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 137](#)
- [Apply the Firewall Filter to the Loopback Interface on page 138](#)
- [Confirm and Commit Your Candidate Configuration on page 138](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter local_acl term terminal_access from address 192.168.1.0/24
set firewall family inet filter local_acl term terminal_access from protocol tcp
set firewall family inet filter local_acl term terminal_access from port ssh
set firewall family inet filter local_acl term terminal_access from port telnet
set firewall family inet filter local_acl term terminal_access then accept
set firewall family inet filter local_acl term terminal_access_denied from protocol tcp
set firewall family inet filter local_acl term terminal_access_denied from port ssh
set firewall family inet filter local_acl term terminal_access_denied from port telnet
set firewall family inet filter local_acl term terminal_access_denied then log
set firewall family inet filter local_acl term terminal_access_denied then reject
set firewall family inet filter local_acl term default-term then accept
set interfaces lo0 unit 0 family inet filter input local_acl
set interfaces lo0 unit 0 family inet address 127.0.0.1/32
```

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter that selectively blocks Telnet and SSH access:

1. Create the stateless firewall filter **local\_acl**.

```
[edit]
user@myhost# edit firewall family inet filter local_acl
```

2. Define the filter term **terminal\_access**.

```
[edit firewall family inet filter local_acl]
user@myhost# set term terminal_access from address 192.168.1.0/24
user@myhost# set term terminal_access from protocol tcp
user@myhost# set term terminal_access from port ssh
user@myhost# set term terminal_access from port telnet
user@myhost# set term terminal_access then accept
```

3. Define the filter term **terminal\_access\_denied**.

```
[edit firewall family inet filter local_acl]
user@myhost# set term terminal_access_denied from protocol tcp
user@myhost# set term terminal_access_denied from port ssh
user@myhost# set term terminal_access_denied from port telnet
user@myhost# set term terminal_access_denied then log
```



```
user@myhost# set term terminal_access_denied then reject
user@myhost# set term default-term then accept
```

### Apply the Firewall Filter to the Loopback Interface

---

#### Step-by-Step Procedure

- To apply the firewall filter to the loopback interface:  
  
[edit]  
user@myhost# set interfaces lo0 unit 0 family inet filter input local\_acl  
user@myhost# set interfaces lo0 unit 0 family inet address 127.0.0.1/32

### Confirm and Commit Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@myhost# show firewall
family inet {
  filter local_acl {
    term terminal_access {
      from {
        address {
          192.168.1.0/24;
        }
        protocol tcp;
        port [ssh telnet];
      }
      then accept;
    }
    term terminal_access_denied {
      from {
        protocol tcp;
        port [ssh telnet];
      }
      then {
        log;
        reject;
      }
    }
    term default-term {
      then accept;
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@myhost# show interfaces
```



```
lo0 {  
  unit 0 {  
    family inet {  
      filter {  
        input local_acl;  
      }  
      address 127.0.0.1/32;  
    }  
  }  
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]  
user@myhost# commit
```

## Verification

Confirm that the configuration is working properly.

- [Verifying Accepted Packets on page 139](#)
- [Verifying Logged and Rejected Packets on page 140](#)

### Verifying Accepted Packets

---

**Purpose** Verify that the actions of the firewall filter terms are taken.



- Action** 1. Clear the firewall log on your router.

```
user@myhost> clear firewall log
```

2. From a host at an IP address *within* the 192.168.1.0/24 subnet, use the **ssh *hostname*** command to verify that you can log in to the device using only SSH. This packet should be accepted, and the packet header information for this packet should not be logged in the firewall filter log buffer in the Packet Forwarding Engine.

```
user@host-A> ssh myhost
user@myhosts's password:
--- JUNOS 11.1-20101102.0 built 2010-11-02 04:48:46 UTC

% cli
user@myhost>
```

3. From a host at an IP address *within* the 192.168.1.0/24 subnet, use the **telnet *hostname*** command to verify that you can log in to your router using only Telnet. This packet should be accepted, and the packet header information for this packet should not be logged in the firewall filter log buffer in the Packet Forwarding Engine.

```
user@host-A> telnet myhost
Trying 192.168.249.71...
Connected to myhost-fxp0.acme.net.
Escape character is '^J'.

host (ttyp0)

login: user
Password:

--- JUNOS 11.1-20101102.0 built 2010-11-02 04:48:46 UTC

% cli
user@myhost>
```

4. Use the **show firewall log** command to verify that the routing table on the device does not contain any entries with a source address in the 192.168.1.0/24 subnet.

```
user@myhost> show firewall log
```

---

### Verifying Logged and Rejected Packets

- Purpose** Verify that the actions of the firewall filter terms are taken.



- Action** 1. Clear the firewall log on your router.

```
user@myhost> clear firewall log
```

2. From a host at an IP address *outside of* the 192.168.1.0/24 subnet, use the **ssh hostname** command to verify that you cannot log in to the device using only SSH. This packet should be rejected, and the packet header information for this packet should be logged in the firewall filter log buffer in the Packet Forwarding Engine.

```
user@host-B ssh myhost
ssh: connect to host sugar port 22: Connection refused
--- JUNOS 11.1-20101102.0 built 2010-11-02 04:48:46 UTC
%
```

3. From a host at an IP address *outside of* the 192.168.1.0/24 subnet, use the **telnet hostname** command to verify that you can log in to the device using only Telnet. This packet should be rejected, and the packet header information for this packet should be logged in the firewall filter log buffer in the PFE.

```
user@host-B> telnet myhost
Trying 192.168.249.71...
telnet: connect to address 192.168.187.3: Connection refused
telnet: Unable to connect to remote host
%
```

4. Use the **show firewall log** command to verify that the routing table on the device does not contain any entries with a source address in the 192.168.1.0/24 subnet.

```
user@myhost> show firewall log
```

Time	Filter	Action	Interface	Protocol	Src Addr	Dest Addr
18:41:25	local_acl	R	fxp0.0	TCP	192.168.187.5	192.168.187.1
18:41:25	local_acl	R	fxp0.0	TCP	192.168.187.5	192.168.187.1
18:41:25	local_acl	R	fxp0.0	TCP	192.168.187.5	192.168.187.1
...						
18:43:06	local_acl	R	fxp0.0	TCP	192.168.187.5	192.168.187.1
18:43:06	local_acl	R	fxp0.0	TCP	192.168.187.5	192.168.187.1
18:43:06	local_acl	R	fxp0.0	TCP	192.168.187.5	192.168.187.1
...						

#### Related Documentation

- [Logging of Packet Headers Evaluated by a Firewall Filter Term on page 63](#)
- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources on page 131](#)
- [Example: Configuring a Filter to Block TFTP Access on page 141](#)
- [Example: Configuring a Filter to Accept OSPF Packets from a Prefix on page 144](#)
- [Example: Configuring a Filter to Accept DHCP Packets Based on Address on page 147](#)

## Example: Configuring a Filter to Block TFTP Access

- [Requirements on page 142](#)
- [Overview on page 142](#)



- [Configuration on page 142](#)
- [Verification on page 144](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

By default, to decrease vulnerability to denial-of-service (DoS) attacks, the Junos OS filters and discards Dynamic Host Configuration Protocol (DHCP) or Bootstrap Protocol (BOOTP) packets that have a source address of 0.0.0.0 and a destination address of 255.255.255.255. This default filter is known as a unicast RPF check. However, some vendors' equipment automatically accepts these packets.

To interoperate with other vendors' equipment, you can configure a filter that checks for both of these addresses and overrides the default RPF-check filter by accepting these packets. In this example, you block Trivial File Transfer Protocol (TFTP) access, logging any attempts to establish TFTP connections.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 142](#)
- [Apply the Firewall Filter to the Loopback Interface on page 143](#)
- [Confirm and Commit Your Candidate Configuration on page 143](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter tftp_access_control term one from protocol udp
set firewall family inet filter tftp_access_control term one from port tftp
set firewall family inet filter tftp_access_control term one then log
set firewall family inet filter tftp_access_control term one then discard
set interfaces lo0 unit 0 family inet filter input tftp_access_control
set interfaces lo0 unit 0 family inet address 127.0.0.1/32
```

---

### Configure the Stateless Firewall Filter

### Step-by-Step Procedure

To configure the stateless firewall filter that selectively blocks TFTP access:

1. Create the stateless firewall filter **tftp\_access\_control**.  
  
[edit]  
user@host# edit firewall family inet filter tftp\_access\_control



- Specify a match on packets received on UDP port 69.

```
[edit firewall family inet filter tftp_access_control]
user@host# set term one from protocol udp
user@host# set term one from port tftp
```

- Specify that matched packets be logged to the buffer on the Packet Forwarding Engine and then discarded.

```
[edit firewall family inet filter tftp_access_control]
user@host# set term one then log
user@host# set term one then discard
```

### Apply the Firewall Filter to the Loopback Interface

**Step-by-Step Procedure** To apply the firewall filter to the loopback interface:

- [edit]  
user@host# set interfaces lo0 unit 0 family inet filter input tftp\_access\_control  
user@host# set interfaces lo0 unit 0 family inet address 127.0.0.1/32

### Confirm and Commit Your Candidate Configuration

**Step-by-Step Procedure** To confirm and then commit your candidate configuration:

- Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter tftp_access_control {
    term one {
      from {
        protocol udp;
        port tftp;
      }
      then {
        log;
        discard;
      }
    }
  }
}
```

- Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
lo0 {
  unit 0 {
    family inet {
      filter {
```



```
        input tftp_access_control;
      }
    address 127.0.0.1/32;
  }
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]
user@host# commit
```

## Verification

Confirm that the configuration is operating properly:

- [Verifying Logged and Discarded Packets on page 144](#)

---

### Verifying Logged and Discarded Packets

**Purpose** Verify that the actions of the firewall filter terms are taken.

**Action** To

1. Clear the firewall log on your router.

```
user@myhost> clear firewall log
```

2. From another host, send a packet to UDP port **69** on this router.

**Related Documentation**

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources on page 131](#)
- [Example: Configuring a Filter to Block Telnet and SSH Access on page 136](#)
- [Example: Configuring a Filter to Accept OSPF Packets from a Prefix on page 144](#)
- [Example: Configuring a Filter to Accept DHCP Packets Based on Address on page 147](#)

---

## Example: Configuring a Filter to Accept OSPF Packets from a Prefix

This example shows how to configure a standard stateless firewall filter to accept packets from a trusted source.

- [Requirements on page 145](#)
- [Overview on page 145](#)
- [Configuration on page 145](#)
- [Verification on page 147](#)



## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you create a filter that accepts only OSPF packets from an address in the prefix 10.108.0.0/16, discarding all other packets with an **administratively-prohibited** ICMP message

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Stateless Firewall Filter on page 145](#)
- [Apply the Firewall Filter to the Loopback Interface on page 146](#)
- [Confirm and Commit Your Candidate Configuration on page 146](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter ospf_filter term term1 from source-address 10.108.0.0/16
set firewall family inet filter ospf_filter term term1 from protocol ospf
set firewall family inet filter ospf_filter term term1 then accept
set firewall family inet filter ospf_filter term default-term then reject
administratively-prohibited
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input ospf_filter
```

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter **ospf\_filter**:

1. Create the filter.

```
[edit]
user@host# edit firewall family inet filter ospf_filter
```

2. Configure the term that accepts packets.

```
[edit firewall family inet filter ospf_filter]
user@host# set term term1 from source-address 10.108.0.0/16
user@host# set term term1 from protocol ospf
user@host# set term term1 then accept
```

3. Configure the term that rejects all other packets.

```
[edit firewall family inet filter ospf_filter]
user@host# set term default_term then reject administratively-prohibited
```



### Apply the Firewall Filter to the Loopback Interface

---

#### Step-by-Step Procedure

To apply the firewall filter to the loopback interface:

1. Configure the interface.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure the logical interface IP address.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the filter to the input.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input ospf_filter
```

### Confirm and Commit Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter ospf_filter {
    term term1 {
      from {
        source-address {
          10.108.0.0/16;
        }
        protocol ospf;
      }
      then {
        accept;
      }
    }
    term default_term {
      then {
        reject administratively-prohibited; # default reject action
      }
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
lo0 {
```



```

unit 0 {
  family inet {
    filter {
      input ospf_filter;
    }
    address 10.1.2.3/30;
  }
}

```

3. If you are done configuring the device, commit your candidate configuration.

```

[edit]
user@host# commit

```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter ospf\_filter** operational mode command.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources on page 131](#)
- [Example: Configuring a Filter to Block Telnet and SSH Access on page 136](#)
- [Example: Configuring a Filter to Block TFTP Access on page 141](#)
- [Example: Configuring a Filter to Accept DHCP Packets Based on Address on page 147](#)

## Example: Configuring a Filter to Accept DHCP Packets Based on Address

This example shows how to configure a standard stateless firewall filter to accept packets from a trusted source.

- [Requirements on page 147](#)
- [Overview on page 147](#)
- [Configuration on page 148](#)
- [Verification on page 149](#)

## Requirements

This example is supported on MX Series routers only.

## Overview

In this example, you create a filter (**rpf\_dhcp**) that accepts DHCP packets with a source address of **0.0.0.0** and a destination address of **255.255.255.255**.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Stateless Firewall Filter on page 148](#)
- [Apply the Firewall Filter to the Loopback Interface on page 148](#)
- [Confirm and Commit Your Candidate Configuration on page 149](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter rpf_dhcp term dhcp_term from source-address 0.0.0.0/32
set firewall family inet filter rpf_dhcp term dhcp_term from destination-address
  255.255.255.255/32
set firewall family inet filter rpf_dhcp term dhcp_term then accept
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input sam
```

---

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter:

1. Create the stateless firewall filter **rpf\_dhcp**.

```
[edit]
user@host# edit firewall family inet filter rpf_dhcp
```

2. Configure the term to match packets with a source address of **0.0.0.0** and a destination address of **255.255.255.255**.

```
[edit firewall family inet filter rpf_dhcp]
user@host# set term dhcp_term from source-address 0.0.0.0/32
user@host# set term dhcp_term from destination-address 255.255.255.255/32
```

3. Configure the term to accept packets that match the specified conditions.

```
[edit firewall family inet filter rpf_dhcp]
set term dhcp_term then accept
```

---

### Apply the Firewall Filter to the Loopback Interface

#### Step-by-Step Procedure

To apply the filter to the input at the loopback interface:

1. Apply the **rpf\_dhcp** filter if packets are not arriving on an expected path.

```
[edit]
user@host# set interfaces lo0 unit 0 family inet rpf-check fail-filter rpf_dhcp
```

2. Configure an address for the loopback interface.

```
[edit]
user@host# set interfaces lo0 unit 0 family inet address 127.0.0.1/32
```



### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter rpf_dhcp {
    term dhcp_term {
      from {
        source-address {
          0.0.0.0/32;
        }
        destination-address {
          255.255.255.255/32;
        }
      }
      then accept;
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
lo0 {
  unit 0 {
    family inet {
      filter {
        rpf-check {
          fail-filter rpf_dhcp;
          mode loose;
        }
      }
      address 127.0.0.1/32;
    }
  }
}
```

3. When you are done configuring the device, commit your candidate configuration.

```
[edit]
user@host# commit
```

### Verification

To confirm that the configuration is working properly, enter the **show firewall** operational mode command.



**Related Documentation**

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources on page 131](#)
- [Example: Configuring a Filter to Block Telnet and SSH Access on page 136](#)
- [Example: Configuring a Filter to Block TFTP Access on page 141](#)
- [Example: Configuring a Filter to Accept OSPF Packets from a Prefix on page 144](#)

## Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers

This example shows how to configure a standard stateless firewall filter that blocks all TCP connection attempts to port 179 from all requesters except from specified BGP peers.

- [Requirements on page 150](#)
- [Overview on page 150](#)
- [Configuration on page 151](#)
- [Verification on page 154](#)

### Requirements

No special configuration beyond device initialization is required before you configure this example.


### Overview

In this example, you create a stateless firewall filter that blocks all TCP connection attempts to port 179 from all requesters except the specified BGP peers.

The stateless firewall filter **filter\_bgp179** matches all packets from the directly connected interfaces on Device A and Device B to the destination port number 179.

[Figure 2 on page 150](#) shows the topology used in this example. Device C attempts to make a TCP connection to Device E. Device E blocks the connection attempt. This example shows the configuration on Device E.

**Figure 2: Typical Network with BGP Peer Sessions**





## Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device C**

```
set interfaces ge-1/2/0 unit 10 description to-E
set interfaces ge-1/2/0 unit 10 family inet address 10.10.10.10/30
set protocols bgp group external-peers type external
set protocols bgp group external-peers peer-as 17
set protocols bgp group external-peers neighbor 10.10.10.9
set routing-options autonomous-system 22
```

**Device E**

```
set interfaces ge-1/2/0 unit 0 description to-A
set interfaces ge-1/2/0 unit 0 family inet address 10.10.10.1/30
set interfaces ge-1/2/1 unit 5 description to-B
set interfaces ge-1/2/1 unit 5 family inet address 10.10.10.5/30
set interfaces ge-1/0/0 unit 9 description to-C
set interfaces ge-1/0/0 unit 9 family inet address 10.10.10.9/30
set interfaces lo0 unit 2 family inet filter input filter_bgp179
set interfaces lo0 unit 2 family inet address 192.168.0.1/32
set protocols bgp group external-peers type external
set protocols bgp group external-peers peer-as 22
set protocols bgp group external-peers neighbor 10.10.10.2
set protocols bgp group external-peers neighbor 10.10.10.6
set protocols bgp group external-peers neighbor 10.10.10.10
set routing-options autonomous-system 17
set firewall family inet filter filter_bgp179 term 1 from source-address 10.10.10.2/32
set firewall family inet filter filter_bgp179 term 1 from source-address 10.10.10.6/32
set firewall family inet filter filter_bgp179 term 1 from destination-port bgp
set firewall family inet filter filter_bgp179 term 1 then accept
set firewall family inet filter filter_bgp179 term 2 then reject
```

### Configuring Device E

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure Device E with a stateless firewall filter that blocks all TCP connection attempts to port 179 from all requestors except specified BGP peers:

1. Configure the interfaces.

```
user@E# set interfaces ge-1/2/0 unit 0 description to-A
user@E# set interfaces ge-1/2/0 unit 0 family inet address 10.10.10.1/30
```

```
user@E# set interfaces ge-1/2/1 unit 5 description to-B
user@E# set interfaces ge-1/2/1 unit 5 family inet address 10.10.10.5/30
```

```
user@E# set interfaces ge-1/0/0 unit 9 description to-C
user@E# set interfaces ge-1/0/0 unit 9 family inet address 10.10.10.9/30
```



2. Configure BGP.

```
[edit protocols bgp group external-peers]
user@E# set type external
user@E# set peer-as 22
user@E# set neighbor 10.10.10.2
user@E# set neighbor 10.10.10.6
user@E# set neighbor 10.10.10.10
```

3. Configure the autonomous system number.

```
[edit routing-options]
user@E# set autonomous-system 17
```

4. Define the filter term that accepts TCP connection attempts to port 179 from the specified BGP peers.

```
[edit firewall family inet filter filter_bgp179]
user@E# set term 1 from source-address 10.10.10.2/32
user@E# set term 1 from source-address 10.10.10.6/32
user@E# set term 1 from destination-port bgp
user@E# set term 1 then accept
```

5. Define the other filter term to reject packets from other sources.

```
[edit firewall family inet filter filter_bgp179]
user@E# set term 2 then reject
```

6. Apply the firewall filter to the loopback interface.

```
[edit interfaces lo0 unit 2 family inet]
user@E# set filter input filter_bgp179
user@E# set address 192.168.0.1/32
```

**Results** From configuration mode, confirm your configuration by entering the **show firewall**, **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@E# show firewall
family inet {
  filter filter_bgp179 {
    term 1 {
      from {
        source-address {
          10.10.10.2/32;
          10.10.10.6/32;
        }
        destination-port bgp;
      }
      then accept;
    }
    term 2 {
      then {
        reject;
      }
    }
  }
}
```



```

}

user@E# show interfaces
lo0 {
  unit 2 {
    family inet {
      filter {
        input filter_bgp179;
      }
      address 192.168.0.1/32;
    }
  }
}
ge-1/2/0 {
  unit 0 {
    description to-A;
    family inet {
      address 10.10.10.1/30;
    }
  }
}
ge-1/2/1 {
  unit 5 {
    description to-B;
    family inet {
      address 10.10.10.5/30;
    }
  }
}
ge-1/0/0 {
  unit 9 {
    description to-C;
    family inet {
      address 10.10.10.9/30;
    }
  }
}

user@E# show protocols
bgp {
  group external-peers {
    type external;
    peer-as 22;
    neighbor 10.10.10.2;
    neighbor 10.10.10.6;
    neighbor 10.10.10.10;
  }
}

user@E# show routing-options
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.



## Verification

Confirm that the configuration is working properly.

- [Verifying That the Filter Is Configured on page 154](#)
- [Verifying the TCP Connections on page 154](#)
- [Monitoring Traffic on the Interfaces on page 154](#)

### Verifying That the Filter Is Configured

**Purpose** Make sure that the filter is listed in output of the **show firewall filter** command.

**Action** user@E> **show firewall filter filter\_bgp179**  
Filter: filter\_bgp179

### Verifying the TCP Connections

**Purpose** Verify the TCP connections.

**Action** From operational mode, run the **show system connections extensive** command on Device C and Device E.

The output on Device C shows the attempt to establish a TCP connection. The output on Device E shows that connections are established with Device A and Device B only.

user@C> **show system connections extensive | match 10.10.10**

tcp4	0	0	10.10.10.9.51872	10.10.10.10.179	SYN_SENT
------	---	---	------------------	-----------------	----------

user@E> **show system connections extensive | match 10.10.10**

tcp4	0	0	10.10.10.5.179	10.10.10.6.62096	ESTABLISHED
tcp4	0	0	10.10.10.6.62096	10.10.10.5.179	ESTABLISHED
tcp4	0	0	10.10.10.1.179	10.10.10.2.61506	ESTABLISHED
tcp4	0	0	10.10.10.2.61506	10.10.10.1.179	ESTABLISHED

### Monitoring Traffic on the Interfaces

**Purpose** Use the **monitor traffic** command to compare the traffic on an interface that establishes a TCP connection with the traffic on an interface that does not establish a TCP connection.

**Action** From operational mode, run the **monitor traffic** command on the Device E interface to Device B and on the Device E interface to Device C. The following sample output verifies that in the first example, acknowledgment (**ack**) messages are received. In the second example, **ack** messages are not received.

```
user@E> monitor traffic size 1500 interface ge-1/2/1.5
19:02:49.700912 Out IP 10.10.10.5.bgp > 10.10.10.6.62096: P
3330573561:3330573580(19) ack 915601686 win 16384 <nop,nop,timestamp 1869518816
1869504850>: BGP, length: 19
19:02:49.801244 In IP 10.10.10.6.62096 > 10.10.10.5.bgp: . ack 19 win 16384
<nop,nop,timestamp 1869518916 1869518816>
19:03:03.323018 In IP 10.10.10.6.62096 > 10.10.10.5.bgp: P 1:20(19) ack 19 win
16384 <nop,nop,timestamp 1869532439 1869518816>: BGP, length: 19
```



```

19:03:03.422418 Out IP 10.10.10.5.bgp > 10.10.10.6.62096: . ack 20 win 16384
<nop,nop,timestamp 1869532539 1869532439>
19:03:17.220162 Out IP 10.10.10.5.bgp > 10.10.10.6.62096: P 19:38(19) ack 20 win
16384 <nop,nop,timestamp 1869546338 1869532439>: BGP, length: 19
19:03:17.320501 In IP 10.10.10.6.62096 > 10.10.10.5.bgp: . ack 38 win 16384
<nop,nop,timestamp 1869546438 1869546338>

```

```

user@E> monitor traffic size 1500 interface ge-1/0/0.9

```

```

18:54:20.175471 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,nop,wscale 0,nop,nop,timestamp 1869009240 0,sackOK,eol>
18:54:23.174422 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,nop,wscale 0,nop,nop,timestamp 1869012240 0,sackOK,eol>
18:54:26.374118 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,nop,wscale 0,nop,nop,timestamp 1869015440 0,sackOK,eol>
18:54:29.573799 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,sackOK,eol>
18:54:32.773493 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,sackOK,eol>
18:54:35.973185 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,sackOK,eol>

```

#### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Protect Against TCP and ICMP Floods on page 157](#)
- [Example: Configuring a Filter to Accept Packets Based on IPv6 TCP Flags on page 164](#)







## CHAPTER 13

# Standard Firewall Filters for Flood Prevention

- [Example: Configuring a Stateless Firewall Filter to Protect Against TCP and ICMP Floods on page 157](#)
- [Example: Configuring a Filter to Accept Packets Based on IPv6 TCP Flags on page 164](#)

## Example: Configuring a Stateless Firewall Filter to Protect Against TCP and ICMP Floods

---

This example shows how to create a stateless firewall filter that protects against TCP and ICMP denial-of-service attacks.

- [Requirements on page 157](#)
- [Overview on page 157](#)
- [Configuration on page 158](#)
- [Verification on page 161](#)

### Requirements

No special configuration beyond device initialization is required before configuring stateless firewall filters.

### Overview

In this example, you create a stateless firewall filter called **protect-RE** that polices TCP and ICMP packets. This example includes the following policers:

- **tcp-connection-policer**—Limits the traffic rate of the TCP packets to 500,000 bps and the burst size to 15,000 bytes. Packets that exceed the traffic rate are discarded.
- **icmp-policer**—Limits the traffic rate of the ICMP packets to 1,000,000 bps and the burst size to 15,000 bytes. Packets that exceed the traffic rate are discarded.

When specifying limits, the bandwidth limit can be from 32,000 bps to 32,000,000,000 bps and the burst-size limit can be from 1,500 bytes through 100,000,000 bytes. Use the following abbreviations when specifying limits: k (1,000), m (1,000,000), and g (1,000,000,000).



Each policer is incorporated into the action of a filter term. This example includes the following terms:

- **tcp-connection-term**—Policies certain TCP packets with a source address of 192.168.122.0/24 or 10.2.1.0/24. These addresses are defined in the **trusted-addresses** prefix list.

Policed packets include connection request packets (SYN and ACK flag bits equal 1 and 0), connection release packets (FIN flag bit equals 1), and connection reset packets (RST flag bit equals 1).

- **icmp-term**—Policies echo request packets, echo response packets, unreachable packets, and time-exceeded packets. All of these ICMP packets are counted in the **icmp-counter** counter.



**NOTE:** You can move terms within the firewall filter by using the **insert** command. See **insert** in the CLI User Guide.

If you want to include the terms created in this procedure in the **protect-RE** firewall filter configured in [“Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources” on page 131](#), perform the configuration tasks in this example first. Then configure the terms as described in [“Example: Configuring a Stateless Firewall Filter to Accept Traffic from Trusted Sources” on page 131](#). This approach ensures that the rate-limiting terms are included as the first two terms in the firewall filter.



**NOTE:** You can move terms within the firewall filter by using the **insert** command. See **insert** in the CLI User Guide.

## Configuration

### CLI Quick Configuration

To quickly configure the stateless firewall filter, copy the following commands to a text file, remove any line breaks, and then paste the commands into the CLI.

```
[edit]
set firewall family inet filter protect-RE term tcp-connection-term from source-prefix-list
trusted-addresses
set firewall family inet filter protect-RE term tcp-connection-term from protocol tcp
set firewall family inet filter protect-RE term tcp-connection-term from tcp-flags "(syn
& !ack) | fin | rst"
set firewall family inet filter protect-RE term tcp-connection-term then policer
tcp-connection-policer
set firewall family inet filter protect-RE term tcp-connection-term then accept
set firewall family inet filter protect-RE term icmp-term from protocol icmp
set firewall family inet filter protect-RE term icmp-term from icmp-type echo-request
set firewall family inet filter protect-RE term icmp-term from icmp-type echo-reply
set firewall family inet filter protect-RE term icmp-term from icmp-type unreachable
set firewall family inet filter protect-RE term icmp-term from icmp-type time-exceeded
set firewall family inet filter protect-RE term icmp-term then policer icmp-policer
set firewall family inet filter protect-RE term icmp-term then count icmp-counter
set firewall family inet filter protect-RE term icmp-term then accept
```



```

set firewall policer tcp-connection-policer filter-specific
set firewall policer tcp-connection-policer if-exceeding bandwidth-limit 1m
set firewall policer tcp-connection-policer if-exceeding burst-size-limit 15k
set firewall policer tcp-connection-policer then discard
set firewall policer icmp-policer filter-specific
set firewall policer icmp-policer if-exceeding bandwidth-limit 1m
set firewall policer icmp-policer if-exceeding burst-size-limit 15k
set firewall policer icmp-policer then discard
set policy-options prefix-list trusted-addresses 10.2.1.0/24
set policy-options prefix-list trusted-addresses 192.168.122.0/24

```

### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure stateless firewall filter policers:

1. Define the first policer.
 

```

[edit]
user@host# edit firewall policer tcp-connection-policer

```
2. Define the action for the policer.
 

```

[edit firewall policer tcp-connection-policer]
user@host# set then discard

```
3. Define the rate limits for the policer.
 

```

[edit firewall policer tcp-connection-policer]
user@host# set filter-specific
user@host# set if-exceeding burst-size-limit 15k bandwidth-limit 1m

```
4. Define the second policer.
 

```

[edit]
user@host# edit firewall policer icmp-policer

```
5. Define the action for the policer.
 

```

[edit firewall policer icmp-policer]
user@host# set then discard

```
6. Set the rate limits for the policer.
 

```

[edit firewall policer icmp-policer]
user@host# set filter-specific
user@host# set if-exceeding burst-size-limit 15k bandwidth-limit 1m

```
7. Define the prefix list.
 

```

[edit]
user@host# set policy-options prefix-list trusted-addresses 192.168.122.0/24
user@host# set policy-options prefix-list trusted-addresses 10.2.1.0/24

```
8. Create the stateless firewall filter.
 

```

[edit]
user@host# edit firewall family inet filter protect-RE

```



9. Define the first term for the filter.

```
[edit firewall family inet filter protect-RE]
user@host# edit term tcp-connection-term
```

10. Define the source address match condition for the term.

```
[edit firewall family inet filter protect-RE term tcp-connection-term]
user@host# set from source-prefix-list trusted-addresses
```

11. Define protocol match conditions for the term.

```
[edit firewall family inet filter protect-RE term tcp-connection-term]
user@host# set from protocol tcp tcp-flags "(syn & !ack) | fin | rst"
```

12. Define the actions for the term.

```
[edit firewall family inet filter protect-RE term tcp-connection-term]
user@host# set then policer tcp-connection-policer accept
```

13. Define the second term.

```
[edit]
user@host# edit firewall family inet filter protect-RE term icmp-term
```

14. Define the protocol for the term.

```
[edit firewall family inet filter protect-RE term icmp-term]
user@host# set from protocol icmp
```

15. Define the match conditions for the term.

```
[edit firewall family inet filter protect-RE term icmp-term]
user@host# set from icmp-type [echo-request echo-reply unreachable
time-exceeded]
```

16. Define the action for the term.

```
[edit firewall family inet filter protect-RE term icmp-term]
user@host# set then policer icmp-policer count icmp-counter accept
```

**Results** Confirm your configuration by entering the **show firewall** command and the **show policy-options** command from configuration mode. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show firewall
family inet {
  filter protect-RE {
    term tcp-connection-term {
      from {
        source-prefix-list {
          trusted-addresses;
        }
        protocol tcp;
        tcp-flags "(syn & !ack) | fin | rst";
      }
      then {
        policer tcp-connection-policer;
        accept;
      }
    }
  }
}
```



```

    }
  }
  term icmp-term {
    from {
      protocol icmp;
      icmp-type [ echo-request echo-reply unreachable time-exceeded ];
    }
    then {
      policer icmp-policer;
      count icmp-counter;
      accept;
    }
  }
}
}
policer tcp-connection-policer {
  filter-specific;
  if-exceeding {
    bandwidth-limit 1m;
    burst-size-limit 15k;
  }
  then discard;
}
policer icmp-policer {
  filter-specific;
  if-exceeding {
    bandwidth-limit 1m;
    burst-size-limit 15k;
  }
  then discard;
}

user@host# show policy-options
prefix-list trusted-addresses {
  10.2.1.0/24;
  192.168.122.0/24;
}

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Displaying Stateless Firewall Filter Configurations on page 161](#)
- [Verifying a TCP and ICMP Flood Firewall Filter on page 162](#)
- [Displaying Firewall Filter Statistics on page 163](#)

### Displaying Stateless Firewall Filter Configurations

**Purpose** Verify the configuration of the firewall filter.

**Action** From configuration mode, enter the **show firewall** command.



**Meaning** Verify that the output shows the intended configuration of the firewall filter. In addition, verify that the terms are listed in the order in which you want the packets to be tested. You can move terms within a firewall filter by using the **insert** CLI command.

### Verifying a TCP and ICMP Flood Firewall Filter

---

**Purpose** Verify that the actions of the firewall filter terms are taken.

**Action** Send packets to the device that match the terms. In addition, verify that the filter actions are *not* taken for packets that do not match.

- Verify that the device can establish only TCP sessions with a host at an IP address that matches 192.168.122.0/24 or 10.2.1.0/24. For example, log in to the device with the **telnet *host-name*** command from another host with one of these address prefixes.
- Use the **ping *host-name*** command to verify that the device responds only to ICMP packets (such as ping requests) that do not exceed the policer traffic rates.
- Use the **ping *host-name size bytes*** command to exceed the policer traffic rates by sending ping requests with large data payloads.

### Sample Output

```
user@host> telnet 192.168.249.71
Trying 192.168.249.71...
Connected to host.acme.net.
Escape character is '^]'.

host (ttyp0)

login: user
Password:

--- JUNOS 6.4-20040521.1 built 2004-05-21 09:38:12 UTC

user@host>

user@host> ping 192.168.249.71
PING host-ge-000.acme.net (192.168.249.71): 56 data bytes
64 bytes from 192.168.249.71: icmp_seq=0 ttl=253 time=11.946 ms
64 bytes from 192.168.249.71: icmp_seq=1 ttl=253 time=19.474 ms
64 bytes from 192.168.249.71: icmp_seq=2 ttl=253 time=14.639 ms
...

user@host> ping 192.168.249.71 size 20000
PING host-ge-000.acme.net (192.168.249.71): 20000 data bytes
^C
--- host-ge-000.acme.net ping statistics ---
12 packets transmitted, 0 packets received, 100% packet loss
```

**Meaning** Verify the following information:

- You can successfully log in to the device using Telnet.
- The device sends responses to the **ping host** command.



- The device does not send responses to the **ping host size 20000** command.

### Displaying Firewall Filter Statistics

**Purpose** Verify that packets are being policed and counted.

**Action** From operational mode, enter the **show firewall filter *filter-name*** command.

### Sample Output

```
user@host> show firewall filter protect-RE
Filter: protect-RE
Counters:
Name                               Bytes          Packets
icmp-counter                        1040000        5600
Policers:
Name                               Packets
tcp-connection-policer             643254873
icmp-policer                       7391
```

**Meaning** Verify the following information:

- Next to **Filter**, the name of the firewall filter is correct.
- Under **Counters**:
  - Under **Name**, the names of any counters configured in the firewall filter are correct.
  - Under **Bytes**, the number of bytes that match the filter term containing the **count *counter-name*** action are shown.
  - Under **Packets**, the number of packets that match the filter term containing the **count *counter-name*** action are shown.
- Under **Policers**:
  - Under **Name**, the names of any policers configured in the firewall filter are correct.
  - Under **Packets**, the number of packets that match the conditions specified for the policer are shown.

### Related Documentation

- Two-Color Policer Configuration Overview
- *Junos OS Feature Support Reference for SRX Series and J Series Devices*
- show firewall
- ping.
- telnet.



## Example: Configuring a Filter to Accept Packets Based on IPv6 TCP Flags

---

This example shows how to configure a standard stateless firewall filter to accept packets from a trusted source.

- [Requirements on page 164](#)
- [Overview on page 164](#)
- [Configuration on page 164](#)
- [Verification on page 166](#)

### Requirements

No special configuration beyond device initialization is required before configuring this example.

### Overview

In this example, you create a filter that accepts packets with specific IPv6 TCP flags.

### Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Stateless Firewall Filter on page 164](#)
- [Apply the Firewall Filter to the Loopback Interface on page 165](#)
- [Confirm and Commit Your Candidate Configuration on page 165](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet6 filter tcp_filter term 1 from next-header tcp
set firewall family inet6 filter tcp_filter term 1 from tcp-flags syn
set firewall family inet6 filter tcp_filter term 1 then count tcp_syn_pkt
set firewall family inet6 filter tcp_filter term 1 then log
set firewall family inet6 filter tcp_filter term 1 then accept
set interfaces lo0 unit 0 family inet6 filter input tcp_filter
set interfaces lo0 unit 0 family inet6 address ::10.34.1.0/120
```

---

### Configure the Stateless Firewall Filter

---

#### Step-by-Step Procedure

To configure the firewall filter

1. Create the IPv6 stateless firewall filter **tcp\_filter**.

```
[edit]
user@host# edit firewall family inet6 filter tcp_filter
```

2. Specify that a packet matches if it is the initial packet in a TCP session and the next header after the IPv6 header is type TCP.

```
[edit firewall family inet6 filter tcp_filter]
```



```
user@host# set term 1 from next-header tcp
user@host# set term 1 from tcp-flags syn
```

3. Specify that matched packets are counted, logged to the buffer on the Packet Forwarding Engine, and accepted.

```
[edit firewall family inet6 filter tcp_filter]
user@host# set term 1 then count tcp_syn_pkt
user@host# set term 1 then log
user@host# set term 1 then accept
```

### Apply the Firewall Filter to the Loopback Interface

**Step-by-Step Procedure** To apply the firewall filter to the loopback interface:

- [edit]  
user@host# set interfaces lo0 unit 0 family inet6 filter input tcp\_filter  
user@host# set interfaces lo0 unit 0 family inet6 address ::10.34.1.0/120

### Confirm and Commit Your Candidate Configuration

**Step-by-Step Procedure** To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet6 {
  filter tcp_filter {
    term 1 {
      from {
        next-header tcp;
        tcp-flags syn;
      }
      then {
        count tcp_syn_pkt;
        log;
        accept;
      }
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
lo0 {
  unit 0 {
    family inet6 {
      filter {
        input tcp_filter;
```



```
        }  
        address ::10.34.1.0/120;  
    }  
}
```

3. When you are done configuring the device, commit your candidate configuration.

```
[edit]  
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show firewall** operational mode command.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Example: Configuring a Stateless Firewall Filter to Protect Against TCP and ICMP Floods on page 157](#)
- [Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers on page 150](#)



# Standard Firewall Filters for Fragment Handling

- [Example: Configuring a Stateless Firewall Filter to Handle Fragments on page 167](#)

## Example: Configuring a Stateless Firewall Filter to Handle Fragments

---

This example shows how to create a stateless firewall filter that handles packet fragments.

- [Requirements on page 167](#)
- [Overview on page 167](#)
- [Configuration on page 168](#)
- [Verification on page 171](#)

### Requirements

No special configuration beyond device initialization is required before configuring stateless firewall filters.

### Overview

In this example, you create a stateless firewall filter called **fragment-RE** that accepts fragmented packets originating from 10.2.1.0/24 and destined for the BGP port. This example includes the following firewall filter terms:

- **not-from-prefix-term**—Discards packets that are not from 10.2.1.0/24 to ensure that subsequent terms in the firewall filter are matched against packets from 10.2.1.0/24 only.
- **small-offset-term**—Discards small (1–5) offset packets to ensure that subsequent terms in the firewall filter can be matched against all the headers in the packet. In addition, the term adds a record to the system logging destinations for the firewall facility.
- **not-fragmented-term**—Accepts unfragmented TCP packets with a destination port that specifies the BGP protocol. A packet is considered unfragmented if the MF flag is not set and the fragment offset equals 0.



- **first-fragment-term**—Accepts the first fragment of a fragmented TCP packet with a destination port that specifies the BGP protocol.
- **fragment-term**—Accepts all fragments that were not discarded by **small-offset-term**. (packet fragments 6–8191). However, only those fragments that are part of a packet containing a first fragment accepted by **first-fragment-term** are reassembled by the destination device.

Packet fragments offset can be from 1 through 8191.



**NOTE:** You can move terms within the firewall filter by using the `insert` command. For more information, see “insert” in the CLI User Guide.

## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the `[edit]` hierarchy level.

```
set firewall family inet filter fragment-RE term not-from-prefix-term from source-address 0.0.0.0/0
set firewall family inet filter fragment-RE term not-from-prefix-term from source-address 10.2.1.0/24 except
set firewall family inet filter fragment-RE term not-from-prefix-term then discard
set firewall family inet filter fragment-RE term small-offset-term from fragment-offset 1-5
set firewall family inet filter fragment-RE term small-offset-term then syslog
set firewall family inet filter fragment-RE term small-offset-term then discard
set firewall family inet filter fragment-RE term not-fragmented-term from fragment-offset 0
set firewall family inet filter fragment-RE term not-fragmented-term from fragment-flags "!more-fragments"
set firewall family inet filter fragment-RE term not-fragmented-term from protocol tcp
set firewall family inet filter fragment-RE term not-fragmented-term from destination-port bgp
set firewall family inet filter fragment-RE term not-fragmented-term then accept
set firewall family inet filter fragment-RE term first-fragment-term from first-fragment
set firewall family inet filter fragment-RE term first-fragment-term from protocol tcp
set firewall family inet filter fragment-RE term first-fragment-term from destination-port bgp
set firewall family inet filter fragment-RE term first-fragment-term then accept
set firewall family inet filter fragment-RE term fragment-term from fragment-offset 6-8191
set firewall family inet filter fragment-RE term fragment-term then accept
```



**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure the stateless firewall filter:

1. Define the stateless firewall filter.
 

```
[edit]
user@host# edit firewall family inet filter fragment-RE
```
2. Configure the first term for the filter.
 

```
[edit firewall family inet filter fragment-RE ]
user@host# set term not-from-prefix-term from source-address 0.0.0.0/0
user@host# set term not-from-prefix-term from source-address 10.2.1.0/24 except
user@host# set term not-from-prefix-term then discard
```
3. Define the second term for the filter.
 

```
[edit firewall family inet filter fragment-RE]
user@host# edit term small-offset-term
```
4. Define the match conditions for the term.
 

```
[edit firewall family inet filter fragment-RE term small-offset-term]
user@host# set from fragment-offset 1-5
```
5. Define the action for the term.
 

```
[edit firewall family inet filter fragment-RE term small-offset-term]
user@host# set then syslog discard
```
6. Define the third term for the filter.
 

```
[edit]
user@host# edit firewall family inet filter fragment-RE term not-fragmented-term
```
7. Define the match conditions for the term.
 

```
[edit firewall family inet filter fragment-RE term not-fragmented-term]
user@host# set from fragment-flags "!more-fragments" fragment-offset 0 protocol
tcp destination-port bgp
```
8. Define the action for the term.
 

```
[edit firewall family inet filter fragment-RE term not-fragmented-term]
user@host# set then accept
```
9. Define the fourth term for the filter.
 

```
[edit]
user@host# edit firewall family inet filter fragment-RE term first-fragment-term
```
10. Define the match conditions for the term.
 

```
[edit firewall family inet filter fragment-RE term first-fragment-term]
user@host# set from first-fragment protocol tcp destination-port bgp
```



11. Define the action for the term.

```
[edit firewall family inet filter fragment-RE term first-fragment-term]
user@host# set then accept
```

12. Define the last term for the filter.

```
[edit]
user@host# edit firewall family inet filter fragment-RE term fragment-term
```

13. Define the match conditions for the term.

```
[edit firewall family inet filter fragment-RE term fragment-term]
user@host# set from fragment-offset 6–8191
```

14. Define the action for the term.

```
[edit firewall family inet filter fragment-RE term fragment-term]
user@host# set then accept
```

**Results** Confirm your configuration by entering the **show firewall** command from configuration mode. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show firewall
family inet {
  filter fragment-RE {
    term not-from-prefix-term {
      from {
        source-address {
          0.0.0.0/0;
          10.2.1.0/24 except;
        }
      }
      then discard;
    }
    term small-offset-term {
      from {
        fragment-offset 1-5;
      }
      then {
        syslog;
        discard;
      }
    }
    term not-fragmented-term {
      from {
        fragment-offset 0;
        fragment-flags "!more-fragments";
        protocol tcp;
        destination-port bgp;
      }
      then accept;
    }
    term first-fragment-term {
      from {
        first-fragment;
      }
    }
  }
}
```



```

        protocol tcp;
        destination-port bgp;
    }
    then accept;
}
term fragment-term {
    from {
        fragment-offset 6-8191;
    }
    then accept;
}
}
}

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

To confirm that the configuration is working properly, perform these tasks:

- [Displaying Stateless Firewall Filter Configurations on page 171](#)
- [Verifying a Firewall Filter that Handles Fragments on page 171](#)

### Displaying Stateless Firewall Filter Configurations

<b>Purpose</b>	Verify the configuration of the firewall filter. You can analyze the flow of the filter terms by displaying the entire configuration.
<b>Action</b>	From configuration mode, enter the <b>show firewall</b> command.
<b>Meaning</b>	Verify that the output shows the intended configuration of the firewall filter. In addition, verify that the terms are listed in the order in which you want the packets to be tested. You can move terms within a firewall filter by using the <b>insert</b> CLI command.

### Verifying a Firewall Filter that Handles Fragments

<b>Purpose</b>	Verify that the actions of the firewall filter terms are taken.
<b>Action</b>	Send packets to the device that match the terms.
<b>Meaning</b>	Verify that packets from 10.2.1.0/24 with small fragment offsets are recorded in the device's system logging destinations for the firewall facility.

<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• show route summary in the Junos OS Operational Mode Commands.</li> </ul>
------------------------------	---







## CHAPTER 15

# Standard Firewall Filters for Setting Rate Limits

- [Example: Configuring a Rate-Limiting Filter Based on Destination Class on page 173](#)

## Example: Configuring a Rate-Limiting Filter Based on Destination Class

---

This example shows how to configure a rate-limiting stateless firewall filter.

- [Requirements on page 173](#)
- [Overview on page 173](#)
- [Configuration on page 174](#)
- [Verification on page 176](#)

### Requirements

No special configuration beyond device initialization is required before configuring this example.

Before you begin, configure the destination class **class1**.

### Overview

In this example, you use a stateless firewall filter to set rate limits based on a destination class.

To activate a policer from within a stateless firewall filter configuration:

- Create a template for the policer by including the **policer *policer-name*** statement.
- Reference the policer in a filter term that specifies the policer in the **policer *policer-name*** nonterminating action.

You can also activate a policer by including the **policer (input | output) *policer-template-name*** statement at a logical interface.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Stateless Firewall Filter on page 174](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 174](#)
- [Confirm and Commit Your Candidate Configuration on page 175](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall filter rl_dclass1 policer police_class1 if-exceeding bandwidth-limit 25
set firewall filter rl_dclass1 policer police_class1 if-exceeding burst-size-limit 1000
set firewall filter rl_dclass1 policer police_class1 then discard
set firewall filter rl_dclass1 term term1 from destination-class class1
set firewall filter rl_dclass1 term term1 then policer police_class1
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input ospf_or_131
```

---

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter **rl\_dclass1** with policer **police\_class1** for destination class **class1**:

1. Create the stateless firewall filter **rl\_dclass1**.

```
[edit]
user@host# edit firewall filter rl_dclass1
```

2. Configure the policer template **police\_class1**.

```
[edit firewall filter rl_dclass1]
user@host# set policer police_class1 if-exceeding bandwidth-limit 25
user@host# set policer police_class1 if-exceeding burst-size-limit 1000
user@host# set policer police_class1 then discard
```

3. Configure a filter term that uses policer **police\_class1** to rate-limit traffic for destination class **class1**.

```
[edit firewall filter rl_dclass1]
user@host# set term term1 from destination-class class1
user@host# set term term1 then policer police_class1
```

---

### Apply the Stateless Firewall Filter to a Logical Interface

#### Step-by-Step Procedure

To apply the filter **rl\_dclass1** to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```



2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input rl_dclass1
```

### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
filter rl_dclass1 {
  policer police_class1 {
    if-exceeding {
      bandwidth-limit 25;
      burst-size-limit 1000;
    }
    then {
      discard;
    }
  }
  term term1 {
    from {
      destination-class class1;
    }
    then {
      policer police_class1;
    }
  }
}
```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
ge-0/0/1 {
  unit 0 {
    family inet {
      filter {
        input rl_dclass1;
      }
      address 10.1.2.3/30;
    }
  }
}
```



3. If you are done configuring the device, commit your candidate configuration.

```
[edit]  
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show class-of-service ge-0/0/1** operational mode command.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Filtering Packets Received on an Interface Set Overview on page 58](#)
- [Statement Hierarchy for Defining an Interface Set on page 329](#)
- [Statement Hierarchy for Configuring a Filter to Match on an Interface Set on page 329](#)
- [Example: Filtering Packets Received on an Interface Set on page 194](#)



## CHAPTER 16

# Examples of Standard Firewall Filters Configuration

- [Example: Applying Lists of Multiple Standard Firewall Filters on page 177](#)
- [Example: Nesting References to Multiple Standard Firewall Filters on page 182](#)
- [Example: Configuring Interface-Specific Firewall Filter Counters on page 186](#)
- [Example: Filtering Packets Received on an Interface Group on page 190](#)
- [Example: Filtering Packets Received on an Interface Set on page 194](#)
- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)
- [Example: Configuring Filter-Based Forwarding on Logical Systems on page 206](#)
- [Example: Configuring Filter-Based Forwarding to a Specific Outgoing Interface or Destination IP Address on page 215](#)

### Example: Applying Lists of Multiple Standard Firewall Filters

This example shows how to apply lists of multiple stateless firewall filters.

- [Requirements on page 177](#)
- [Overview on page 178](#)
- [Configuration on page 178](#)
- [Verification on page 181](#)

### Requirements

Before you begin, be sure that you have:

- Installed your router and supported PIC, DPC, or MPC and performed the initial router configuration.
- Configured basic Ethernet in the topology.
- Configured a logical interface to run the IP version 4 (IPv4) protocol (**family inet**) and configured the logical interface with an interface address. This example uses logical interface **ge-1/3/0.0** configured with the IP address 1.1.1.2/30.





**NOTE:** For completeness, the configuration section of this example includes setting an IP address for logical interface `ge-1/3/0.0`.

- Verified that traffic is flowing in the topology and that ingress and egress IPv4 traffic is flowing through logical interface `ge-1/3/0.0`.
- Verified that you have access to the remote host that is connected to this router's logical interface `ge-1/3/0.0`.

## Overview

In this example, you configure three IPv4 stateless firewall filters and apply each filter directly to the same logical interface by using a list.

### Topology

---

This example applies the following firewall filters as a *list of input filters* at logical interface `ge-1/3/0.0`. Each filter contains a single term that evaluates IPv4 packets and accepts packets based on the value of the **destination port** field in the TCP header:

- Filter `filter_FTP` matches on the FTP port number (21).
- Filter `filter_SSH` matches on the SSH port number (22).
- Filter `filter_Telnet` matches on the Telnet port number (23).

If an inbound packet does not match any of the filters in the input list, the packet is discarded.



**NOTE:** The Junos OS uses filters in a list in the order in which the filter names appear in the list. In this simple example, the order is irrelevant because all of the filters specify the same action.

Any of the filters can be applied to other interfaces, either alone (using the **input** or **output** statement) or in combination with other filters (using the **input-list** or **output-list** statement). The objective is to configure multiple “minimalist” firewall filters that you can reuse in interface-specific filter lists.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure Multiple IPv4 Stateless Firewall Filters on page 179](#)
- [Apply the Filters to a Logical Interface as an Input List and an Output List on page 180](#)
- [Confirm and Commit Your Candidate Configuration on page 180](#)



**CLI Quick Configuration** To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter filter_FTP term 0 from protocol tcp
set firewall family inet filter filter_FTP term 0 from destination-port 21
set firewall family inet filter filter_FTP term 0 then count pkts_FTP
set firewall family inet filter filter_FTP term 0 then accept
set firewall family inet filter filter_SSH term 0 from protocol tcp
set firewall family inet filter filter_SSH term 0 from destination-port 23
set firewall family inet filter filter_SSH term 0 then count pkts_SSH
set firewall family inet filter filter_SSH term 0 then accept
set firewall family inet filter filter_Telnet term 0 from protocol tcp
set firewall family inet filter filter_Telnet term 0 from destination-port 22
set firewall family inet filter filter_Telnet term 0 then count pkts_Telnet
set firewall family inet filter filter_Telnet term 0 then accept
set firewall family inet filter filter_discard term 1 then count pkts_discarded
set firewall family inet filter filter_discard term 1 then discard
set interfaces ge-1/3/0 unit 0 family inet address 1.1.1.2/30
set interfaces ge-1/3/0 unit 0 family inet filter input-list filter_FTP
set interfaces ge-1/3/0 unit 0 family inet filter input-list filter_SSH
set interfaces ge-1/3/0 unit 0 family inet filter input-list filter_Telnet
set interfaces ge-1/3/0 unit 0 family inet filter input-list filter_discard
```

### Configure Multiple IPv4 Stateless Firewall Filters

**Step-by-Step Procedure** To configure the IPv4 stateless firewall filters:

1. Navigate the CLI to the hierarchy level at which you configure IPv4 firewall filters.

```
[edit]
user@host# edit firewall family inet
```

2. Configure the first firewall filter to count and accept packets for port 21.

```
[edit firewall family inet]
user@host# set filter filter_FTP term 0 from protocol tcp
user@host# set filter filter_FTP term 0 from destination-port 21
user@host# set filter filter_FTP term 0 then count pkts_FTP
user@host# set filter filter_FTP term 0 then accept
```

3. Configure the second firewall filter to count and accept packets for port 23.

```
[edit firewall family inet]
user@host# set filter filter_SSH term 0 from protocol tcp
user@host# set filter filter_SSH term 0 from destination-port 23
user@host# set filter filter_SSH term 0 then count pkt_SSH
user@host# set filter filter_SSH term 0 then accept
```

4. Configure the third firewall filter to count and accept packets from port 22.

```
[edit firewall family inet]
user@host# set filter filter_Telnet term 0 from protocol tcp
user@host# set filter filter_Telnet term 0 from destination-port 22
user@host# set filter filter_Telnet term 0 then count pkts_Telnet
user@host# set filter filter_Telnet term 0 then accept
```



5. Configure the last firewall filter to count the discarded packets.

```
[edit firewall family inet]
user@host# set filter filter_discard term 1 then count pkts_discarded
user@host# set filter filter_discard term 1 then discard
```

---

### Apply the Filters to a Logical Interface as an Input List and an Output List

**Step-by-Step Procedure** To apply the six IPv4 stateless firewall filters as a list of input filters and a list of output filters:

1. Navigate the CLI to the hierarchy level at which you apply IPv4 firewall filters to logical interface **ge-1/3/0.0**.

```
[edit]
user@host# edit interfaces ge-1/3/0 unit 0 family inet
```

2. Configure the IPv4 protocol family for the logical interface.

```
[edit interfaces ge-1/3/0 unit 0 family inet]
user@host# set address 1.1.1.2/30
```

3. Apply the filters as a list of input filters.

```
[edit interfaces ge-1/3/0 unit 0 family inet]
user@host# set filter input-list [ filter_FTP filter_SSH filter_Telnet filter_discard ]
```

---

### Confirm and Commit Your Candidate Configuration

**Step-by-Step Procedure** To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filters by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter filter_FTP {
    term 0 {
      from {
        protocol tcp;
        destination-port 21;
      }
      then {
        count pkts_FTP;
        accept;
      }
    }
  }
  filter filter_SSH {
    term 0 {
      from {
        protocol tcp;
        destination-port 23;
      }
    }
  }
}
```



```

        then {
            count pkts_SSH;
            accept;
        }
    }
}
filter filter_Telnet {
    term 0 {
        from {
            protocol tcp;
            destination-port 22;
        }
        then {
            count pkts_Telnet;
            accept;
        }
    }
}
filter filter_discard {
    term 1 {
        then {
            count pkts_discarded;
            discard;
        }
    }
}
}
}

```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@host# show interfaces
ge-1/3/0 {
    unit 0 {
        family inet {
            filter {
                input-list [ filter_FTP filter_SSH filter_Telnet filter_discard ];
            }
            address 1.1.1.2/30;
        }
    }
}
}

```

3. If you are done configuring the device, commit your candidate configuration.

```

[edit]
user@host# commit

```

## Verification

Confirm that the configuration is working properly.

- [Verifying That Inbound Packets Are Accepted Only If Destined for the FTP, SSH or Telnet Port on page 182](#)



### Verifying That Inbound Packets Are Accepted Only If Destined for the FTP, SSH or Telnet Port

---

**Purpose** Verify that all three filters are active for the logical interface.

**Action** To verify that input packets are accepted according to the three filters:

1. From the remote host that is connected to this router's logical interface **ge-1/3/0.0**, send a packet with destination port number 21 in the header. The packet should be accepted.
2. From the remote host that is connected to this router's logical interface **ge-1/3/0.0**, send a packet with destination port number 23 in the header. The packet should be accepted.
3. From the remote host that is connected to this router's logical interface **ge-1/3/0.0**, send a packet with destination port number 22 in the header. The packet should be accepted.
4. From the remote host that is connected to this router's logical interface **ge-1/3/0.0**, send a packet with a destination port number *other than* 21, 22, or 23. The packet should be discarded.
5. To display counter information for the list of filters applied to the input at **ge-1/3/0.0-i** enter the **show firewall filter ge-1/3/0.0-i** operational mode command. The command output displays the number of bytes and packets that match filter terms associated with the following counters:
  - **pkts\_FTP-ge-1/3/0.0-i**
  - **pkts\_SSH-ge-1/3/0.0-i**
  - **pkts\_Telnet-ge-1/3/0.0-i**
  - **pkts\_discard-ge-1/3/0.0-i**

**Related Documentation**

- [Multiple Standard Firewall Filters Applied as a List Overview on page 48](#)
- [Guidelines for Applying Multiple Standard Firewall Filters as a List on page 51](#)

### Example: Nesting References to Multiple Standard Firewall Filters

---

This example shows how to configure nested references to multiple stateless firewall filters.

- [Requirements on page 183](#)
- [Overview on page 183](#)
- [Configuration on page 183](#)
- [Verification on page 186](#)



## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you configure a stateless firewall filter for a match condition and action combination that can be shared among multiple firewall filters. You then configure two firewall filters that reference the first firewall filter. Later, if the common filtering criteria needs to be changed, you would modify only the one shared firewall filter configuration.

### Topology

The **common\_filter** firewall filter discards packets that have a UDP source or destination port field number of **69**. Both of the two additional firewall filters, **filter1** and **filter2**, reference the **common\_filter**.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Nested Firewall Filters on page 183](#)
- [Apply Both Nested Firewall Filters to Interfaces on page 184](#)
- [Confirm and Commit Your Candidate Configuration on page 184](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter common_filter term common_term from protocol udp
set firewall family inet filter common_filter term common_term from port tftp
set firewall family inet filter common_filter term common_term then discard
set firewall family inet filter filter1 term term1 filter common-filter
set firewall family inet filter filter1 term term2 from address 192.168.0.0/16
set firewall family inet filter filter1 term term2 then reject
set firewall family inet filter filter2 term term1 filter common-filter
set firewall family inet filter filter2 term term2 from protocol udp
set firewall family inet filter filter2 term term2 from port bootps
set firewall family inet filter filter2 term term2 then accept
set interfaces ge-0/0/0 unit 0 family inet address 10.1.0.1/24
set interfaces ge-0/0/0 unit 0 family inet filter input filter1
set interfaces ge-0/0/3 unit 0 family inet address 10.1.3.1/24
set interfaces ge-0/0/0 unit 0 family inet filter input filter2
```

### Configure the Nested Firewall Filters

### Step-by-Step Procedure

To configure two nested firewall filters that share a common filter:

1. Navigate the CLI to the hierarchy level at which you configure IPv4 firewall filters.  

```
[edit]
user@host# edit firewall family inet
```



2. Configure the common filter that will be referenced by multiple other filters.

```
[edit firewall family inet]
user@host# set filter common_filter term common_term from protocol udp
user@host# set filter common_filter term common_term from port tftp
user@host# set filter common_filter term common_term then discard
```

3. Configure a filter that references the common filter.

```
[edit firewall family inet]
user@host# set filter filter1 term term1 filter common-filter
user@host# set filter filter1 term term2 from address 192.168.0.0/16
user@host# set filter filter1 term term2 then reject
```

4. Configure a second filter that references the common filter.

```
[edit firewall family inet]
user@host# set filter filter2 term term1 filter common-filter
user@host# set filter filter2 term term2 from protocol udp
user@host# set filter filter2 term term2 from port bootps
user@host# set filter filter2 term term2 then accept
```

---

### Apply Both Nested Firewall Filters to Interfaces

---

#### Step-by-Step Procedure

To apply both nested firewall filters to logical interfaces:

1. Apply the first nested filter to a logical interface input.

```
[edit]
user@host# set interfaces ge-0/0/0 unit 0 family inet address 10.1.0.1/24
user@host# set interfaces ge-0/0/0 unit 0 family inet filter input filter1
```

2. Apply the second nested filter to a logical interface input.

```
[edit]
user@host# set interfaces ge-0/0/3 unit 0 family inet address 10.1.3.1/24
user@host# set interfaces ge-0/0/0 unit 0 family inet filter input filter2
```

---

### Confirm and Commit Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter common_filter {
    term common_term {
      from {
        protocol udp;
        port tftp;
      }
      then {
        discard;
      }
    }
  }
}
```



```

    }
  }
}
filter filter1 {
  term term1 {
    filter common-filter;
  }
  term term2 {
    from {
      address 192.168/16;
    }
    then {
      reject;
    }
  }
}
filter filter2 {
  term term1 {
    filter common-filter;
  }
  term term2 {
    from {
      protocol udp;
      port bootps;
    }
    then {
      accept;
    }
  }
}
}
}

```

2. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@host# show interfaces
ge-0/0/0 {
  unit 0 {
    family inet {
      filter {
        input filter1;
      }
      address 10.1.0.1/24;
    }
  }
}
ge-0/0/3 {
  unit 0 {
    family inet {
      filter {
        input filter2;
      }
      address 10.1.3.1/24;
    }
  }
}

```



```
}  
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]  
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show firewall filter filter1** and **show firewall filter filter2** operational mode commands.

### Related Documentation

- [Multiple Standard Firewall Filters in a Nested Configuration Overview on page 52](#)
- [Guidelines for Nesting References to Multiple Standard Firewall Filters on page 54](#)

---

## Example: Configuring Interface-Specific Firewall Filter Counters

---

This example shows how to configure and apply an interface-specific standard stateless firewall filter.

- [Requirements on page 186](#)
- [Overview on page 186](#)
- [Configuration on page 187](#)
- [Verification on page 189](#)

## Requirements

Interface-specific stateless firewall filters are supported on T Series, M120, M320, and MX Series routers only.

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you create an interface-specific stateless firewall filter that counts and accepts packets with source or destination addresses in a specified prefix and the IP protocol type field set to a specific value.

---

### Topology

---

You configure the interface-specific stateless firewall filter **filter\_s\_tcp** to count and accept packets with IP source or destination addresses in the **10.0.0.0/12** prefix and the IP protocol type field set to **tcp** (or the numeric value **6**).

The name of the firewall filter counter is **count\_s\_tcp**.

You apply the firewall filter to multiple logical interfaces:

- **at-1/1/1.0** input



- **so-2/2/2.2** output

Applying the filter to these two interfaces results in two instances of the filter: **filter\_s\_tcp-at-1/1/1.0-i** and **filter\_s\_tcp-so-2/2/2.2-o**, respectively.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Interface-Specific Firewall Filter on page 187](#)
- [Apply the Interface-Specific Firewall Filter to Multiple Interfaces on page 188](#)
- [Confirm Your Candidate Configuration on page 188](#)
- [Clear the Counters and Commit Your Candidate Configuration on page 189](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter filter_s_tcp interface-specific
set firewall family inet filter filter_s_tcp term 1 from address 10.0.0.0/12
set firewall family inet filter filter_s_tcp term 1 from protocol tcp
set firewall family inet filter filter_s_tcp term 1 then count count_s_tcp
set firewall family inet filter filter_s_tcp term 1 then accept
set interfaces at-1/1/1 unit 0 family inet filter input filter_s_tcp
set interfaces so-2/2/2 unit 2 family inet filter filter_s_tcp
```

### Configure the Interface-Specific Firewall Filter

#### Step-by-Step Procedure

To configure the interface-specific firewall filter:

1. Create the IPv4 firewall filter **filter\_s\_tcp**.  
  

```
[edit]
user@host# edit firewall family inet filter filter_s_tcp
```
2. Enable interface-specific instances of the filter.  
  

```
[edit firewall family inet filter filter_s_tcp]
user@host# set interface-specific
```
3. Configure the match conditions for the term.  
  

```
[edit firewall family inet filter filter_s_tcp]
user@host# set term 1 from address 10.0.0.0/12
user@host# set term 1 from protocol tcp
```
4. Configure the actions for the term.  
  

```
[edit firewall family inet filter filter_s_tcp]
user@host# set term 1 then count count_s_tcp
user@host# set term 1 then accept
```



### Apply the Interface-Specific Firewall Filter to Multiple Interfaces

---

#### Step-by-Step Procedure

To apply the filter **filter\_s\_tcp** to logical interfaces **at-1/1/1.0** and **so-2/2/2.2**:

1. Apply the interface-specific filter to packets received on logical interface **at-1/1/1.0**.

```
[edit]
user@host# set interfaces at-1/1/1 unit 0 family inet filter input filter_s_tcp
```

2. Apply the interface-specific filter to packets transmitted from logical interface **so-2/2/2.2**.

```
[edit]
user@host# set interfaces so-2/2/2 unit 2 family inet filter filter_s_tcp
```

### Confirm Your Candidate Configuration

---

#### Step-by-Step Procedure

To confirm your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter filter_s_tcp {
    interface-specific;
    term 1 {
      from {
        address {
          10.0.0.0/12;
        }
        protocol tcp;
      }
      then {
        count count_s_tcp;
        accept;
      }
    }
  }
}
```

2. Confirm the configuration of the interfaces by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
at-1/1/1 {
  unit 0
    family inet {
      filter {
        input filter_s_tcp;
      }
    }
}
```



```

    ]
  }
  so-2/2/2 {
    unit 2
      family inet {
        filter {
          output filter_s_tcp;
        }
      }
    }
  }
}

```

### Clear the Counters and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To clear the counters and commit your candidate configuration:

1. From operational command mode, use the **clear firewall all** command to clear the statistics for all firewall filters.

To clear only the counters used in this example, include the interface-specific filter instance names:

```

[edit]
user@host> clear firewall filter filter_s_tcp-at-1/1/1.0-i
user@host> clear firewall filter filter_s_tcp-so-2/2/2.2-o

```

2. Commit your candidate configuration.

```

[edit]
user@host# commit

```

### Verification

Confirm that the configuration is working properly.

- [Verifying That the Filter Is Applied to Each of the Multiple Interfaces on page 189](#)
- [Verifying That the Counters Are Collected Separately by Interface on page 190](#)

### Verifying That the Filter Is Applied to Each of the Multiple Interfaces

**Purpose** Verify that the filter is applied to each of the multiple interfaces.

**Action** Run the **show interfaces** command with the **detail** or **extensive** output level.

1. Verify that the filter is applied to the input for **at-1/1/1.0**:

```

user@host> show interfaces at-1/1/1 detail
Physical interface: at-1/1/1, Enabled, Physical link is Up
  Interface index: 300, SNMP ifIndex: 194, Generation: 183
...
  Logical interface at-1/1/1.0 (Index 64) (SNMP ifIndex 204) (Generation 5)
    Flags: Point-To-Point SNMP-Traps 0x4000 Encapsulation: ATM-SNAP
...

```



```

Protocol inet, MTU: 4470, Generation: 13, Route table: 0
Flags: Sendbroadcast-pkt-to-re
Input Filters: filter_s_tcp-at-1/1/1.0-i,,,,,

```

2. Verify that the filter is applied to the output for **so-2/2/2.2**:

```

user@host> show interfaces so-2/2/2 detail
Physical interface: so-2/2/2, Enabled, Physical link is Up
Interface index: 129, SNMP ifIndex: 502, Generation: 132

...
Logical interface so-2/2/2.2 (Index 70) (SNMP ifIndex 536) (Generation 135)

Flags: Point-To-Point SNMP-Traps 0x4000 Encapsulation: PPP

...
Protocol inet, MTU: 4470, Generation: 146, Route table: 0
Flags: Sendbroadcast-pkt-to-re
Output Filters: filter_s_tcp-so-2/2/2.2-o,,,,,

```

### Verifying That the Counters Are Collected Separately by Interface

**Purpose** Make sure that the **count\_s\_tcp** counters are collected separately for the two logical interfaces.

**Action** Run the **show firewall** command.

```

user@host> show firewall filter filter_s_tcp
Filter: filter_s_tcp
Counters:

```

Name	Bytes	Packets
count_s_tcp-at-1/1/1.0-i	420	5
count_s_tcp-so-2/2/2.2-o	8888	101

**Related Documentation**

- [Interface-Specific Firewall Filter Instances Overview on page 55](#)
- [Statement Hierarchy for Configuring Interface-Specific Firewall Filters on page 325](#)
- [Statement Hierarchy for Applying Interface-Specific Firewall Filters on page 326](#)

## Example: Filtering Packets Received on an Interface Group

This example shows how to configure a standard stateless firewall filter to match packets tagged for a particular interface group.

- [Requirements on page 190](#)
- [Overview on page 191](#)
- [Configuration on page 191](#)
- [Verification on page 194](#)

### Requirements

No special configuration beyond device initialization is required before configuring this example.



## Overview

In this example, you configure two router interfaces to belong to the interface group. You also configure a stateless firewall filter that matches packets that have been tagged as received on that interface group, contain a source or destination address within a particular prefix, and contain a TCP source or destination port of a specific type and port number. The filter counts, logs, and rejects packets that match this criteria. The filter counts, logs, and rejects all other packets. By applying this firewall filter to only one of the two interfaces in the interface group, you can apply the filtering mechanism to all packets input to the two interfaces.

### Topology

You configure the interface group number 1 to consist of the management port **fxp0.0** and the loopback port **lo0.0**.

You configure the firewall filter **filter\_if\_group** to accept only packets from interface group 1, received from or destined for IP addresses in the 192.168.80.114/32 prefix, and received from or destined for TCP port number 79.

You apply the firewall filter **filter\_if\_group** to the router's loopback interface.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

- [Configure the Stateless Firewall Filter on page 192](#)
- [Assign Interfaces to the Interface Group on page 192](#)
- [Apply the Firewall Filter to the Loopback Interface on page 192](#)
- [Confirm and Commit Your Candidate Configuration on page 193](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet filter filter_if_group term term1 from interface-group 1
set firewall family inet filter filter_if_group term term1 from address 192.168.80.114/32
set firewall family inet filter filter_if_group term term1 from protocol tcp
set firewall family inet filter filter_if_group term term1 from port finger
set firewall family inet filter filter_if_group term term1 then count if_group_counter1
set firewall family inet filter filter_if_group term term1 then log
set firewall family inet filter filter_if_group term term1 then reject
set firewall family inet filter filter_if_group term term2 then count if_group_counter2
set firewall family inet filter filter_if_group term term2 then log
set firewall family inet filter filter_if_group term term2 then accept
set interfaces fxp0 unit 0 family inet filter group 1
set interfaces fxp0 unit 0 family inet address 192.168.5.38/24
set interfaces lo0 unit 0 family inet filter group 1
set interfaces lo0 unit 0 family inet address 10.0.0.1/32
set interfaces lo0 unit 0 family inet address 192.168.77.1/32
set interfaces lo0 unit 0 family inet filter input filter_if_group
```



### Configure the Stateless Firewall Filter

---

#### Step-by-Step Procedure

To configure the stateless firewall filter `filter_if_group`:

1. Create the stateless firewall filter `filter_if_group`.  
  
[edit]  
user@host# edit firewall family inet filter filter\_if\_group
2. Configure term `term1` to match packets received on interface group 1, with the source or destination address field in the 192.168.80.114/32 prefix, and with the TCP source or destination port number 79.  
  
[edit firewall family inet filter filter\_if\_group]  
user@host# set term term1 from interface-group 1  
user@host# set term term1 from address 192.168.80.114/32  
user@host# set term term1 from protocol tcp  
user@host# set term term1 from port finger
3. Configure term `term1` to count, log, and reject matching packets.  
  
[edit firewall family inet filter filter\_if\_group]  
user@host# set term term1 then count if\_group\_counter1  
user@host# set term term1 then log  
user@host# set term term1 then reject
4. Configure the term `term2` to count, log, and accept all other packets.  
  
[edit firewall family inet filter filter\_if\_group]  
user@host# set term term2 then count if\_group\_counter2  
user@host# set term term2 then log  
user@host# set term term2 then accept

### Assign Interfaces to the Interface Group

---

#### Step-by-Step Procedure

To assign logical interfaces to the interface group number 1 referenced by the firewall filter match term `term1`:

1. Assign the management port to interface group number 1.  
  
[edit]  
user@host# set interfaces fxp0 unit 0 family inet filter group 1  
user@host# set interfaces fxp0 unit 0 family inet address 192.168.5.38/24
2. Assign a second logical interface to interface group number 1.  
  
[edit]  
user@host# set interfaces lo0 unit 0 family inet filter group 1  
user@host# set interfaces lo0 unit 0 family inet address 10.0.0.1/32  
user@host# set interfaces lo0 unit 0 family inet address 192.168.77.1/32

### Apply the Firewall Filter to the Loopback Interface

---

#### Step-by-Step Procedure

- To apply the firewall filter to the router's loopback interface:  
  
[edit]  
user@host# set interfaces lo0 unit 0 family inet filter input filter\_if\_group



### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter filter_if_group {
    term term1 {
      from {
        interface-group 1;
        address {
          192.168.80.114/32;
        }
        protocol tcp;
        port finger;
      }
      then {
        count if_group_counter1;
        log;
        reject;
      }
    }
    term term2 {
      then {
        count if_group_counter2;
        log;
        accept;
      }
    }
  }
}
```

2. Confirm the configuration of the interfaces by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
fxp0 {
  unit 0 {
    family inet {
      filter {
        group 1;
      }
      address 192.168.5.38/24;
    }
  }
}
lo0 {
  unit 0 {
    family inet {
```



```
filter {  
    input filter_if_group;  
    group 1;  
}  
address 10.0.0.1/32;  
address 192.168.77.1/32;  
}  
}
```

3. If you are done configuring the device, commit your candidate configuration.

```
[edit]  
user@host# commit
```

## Verification

To display the firewall filter counters, enter the **show firewall filter filter\_if\_group** operational mode command:

```
user@host> show firewall filter filter_if_group
```

```
Filter: filter_if_group
```

```
Counters:
```

Name	Bytes	Packets
if_group_counter1	0	0
if_group_counter2	6452105	82667

To display the local log of packet headers for packets evaluated by the firewall filter, enter the **show firewall log** operational mode command.

### Related Documentation

- [Filtering Packets Received on a Set of Interface Groups Overview on page 57](#)
- [Statement Hierarchy for Assigning Interfaces to Interface Groups on page 327](#)
- [Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups on page 327](#)

---

## Example: Filtering Packets Received on an Interface Set

This example shows how to configure a standard stateless firewall filter to match packets tagged for a particular interface set.

- [Requirements on page 194](#)
- [Overview on page 195](#)
- [Configuration on page 195](#)
- [Verification on page 200](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.



## Overview

In this example, you apply a stateless firewall filter to the input of the router loopback interface. The firewall filter includes a term that matches packets tagged for a particular interface set.

### Topology

You create the firewall filter **L2\_filter** to apply rate limits to the protocol-independent traffic received on the following interfaces:

- **fe-0/0/0.0**
- **fe-1/0/0.0**
- **fe-1/1/0.0**

First, for protocol-independent traffic received on **fe-0/0/0.0**, the firewall filter term **t1** applies policer **p1**.

For protocol-independent traffic received on any other Fast Ethernet interfaces, firewall filter term **t2** applies policer **p2**. To define an interface set that consists of all Fast Ethernet interfaces, you include the **interface-set interface-set-name interface-name** statement at the **[edit firewall]** hierarchy level. To define a packet-matching criteria based on the interface on which a packet arrives to a specified interface set, you configure a term that uses the **interface-set** firewall filter match condition.

Finally, for any other protocol-independent traffic, firewall filter term **t3** applies policer **p3**.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configuring the Interfaces for Which the Stateless Firewall Filter Terms Take Rate-Limiting Actions on page 196](#)
- [Configuring the Stateless Firewall Filter That Rate-Limits Protocol-Independent Traffic Based on the Interfaces on Which Packets Arrive on page 197](#)
- [Applying the Stateless Firewall Filter to the Routing Engine Input Interface on page 199](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set interfaces fe-0/0/0 unit 0 family inet address 10.1.1.1/30
set interfaces fe-1/0/0 unit 0 family inet address 10.2.2.1/30
set interfaces fe-1/1/0 unit 0 family inet address 10.4.4.1/30
set firewall policer p1 if-exceeding bandwidth-limit 5m
set firewall policer p1 if-exceeding burst-size-limit 10m
set firewall policer p1 then discard
```



```

set firewall policer p2 if-exceeding bandwidth-limit 40m
set firewall policer p2 if-exceeding burst-size-limit 100m
set firewall policer p2 then discard
set firewall policer p3 if-exceeding bandwidth-limit 600m
set firewall policer p3 if-exceeding burst-size-limit 1g
set firewall policer p3 then discard
set firewall interface-set ifset fe-*
set firewall family any filter L2_filter term t1 from interface fe-0/0/0.0
set firewall family any filter L2_filter term t1 then count c1
set firewall family any filter L2_filter term t1 then policer p1
set firewall family any filter L2_filter term t2 from interface-set ifset
set firewall family any filter L2_filter term t2 then count c2
set firewall family any filter L2_filter term t2 then policer p2
set firewall family any filter L2_filter term t3 then count c3
set firewall family any filter L2_filter term t3 then policer p3
set interfaces lo0 unit 0 family inet address 1.1.1.157/30
set interfaces lo0 unit 0 filter input L2_filter

```

### Configuring the Interfaces for Which the Stateless Firewall Filter Terms Take Rate-Limiting Actions

#### Step-by-Step Procedure

To configure the interfaces for which the stateless firewall filter terms take rate-limiting actions:

1. Configure the logical interface whose input traffic will be matched by the first term of the firewall filter.

```

[edit]
user@host# set interfaces fe-0/0/0 unit 0 family inet address 10.1.1.1/30

```

2. Configure the logical interfaces whose input traffic will be matched by the second term of the firewall filter.

```

[edit ]
user@host# set interfaces fe-1/0/0 unit 0 family inet address 10.2.2.1/30
user@host# set interfaces fe-1/1/0 unit 0 family inet address 10.4.4.1/30

```

3. If you are done configuring the device, commit the configuration.

```

[edit]
user@host# commit

```

**Results** Confirm the configuration of the router transit interfaces by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this procedure to correct the configuration.

```

[edit]
user@host# show interfaces
fe-0/0/0 {
  unit 0 {
    family inet {
      address 10.1.1.1/30;
    }
  }
}
fe-1/0/0 {

```



```

unit 0 {
  family inet {
    address 10.2.2.1/30;
  }
}
fe-1/1/0 {
  unit 0 {
    family inet {
      address 10.4.4.1/30;
    }
  }
}

```

### Configuring the Stateless Firewall Filter That Rate-Limits Protocol-Independent Traffic Based on the Interfaces on Which Packets Arrive

#### Step-by-Step Procedure

To configure the standard stateless firewall **L2\_filter** that uses policers (**p1**, **p2**, and **p3**) to rate-limit protocol-independent traffic based on the interfaces on which the packets arrive:

1. Configure the firewall statements.

```

[edit]
user@host# edit firewall

```

2. Configure the policer **p1** to discard traffic that exceeds a traffic rate of **5m** bps or a burst size of **10m** bytes.

```

[edit firewall]
user@host# set policer p1 if-exceeding bandwidth-limit 5m
user@host# set policer p1 if-exceeding burst-size-limit 10m
user@host# set policer p1 then discard

```

3. Configure the policer **p2** to discard traffic that exceeds a traffic rate of **40m** bps or a burst size of **100m** bytes.

```

[edit firewall]
user@host# set policer p2 if-exceeding bandwidth-limit 40m
user@host# set policer p2 if-exceeding burst-size-limit 100m
user@host# set policer p2 then discard

```

4. Configure the policer **p3** to discard traffic that exceeds a traffic rate of **600m** bps or a burst size of **1g** bytes.

```

[edit firewall]
user@host# set policer p3 if-exceeding bandwidth-limit 600m
user@host# set policer p3 if-exceeding burst-size-limit 1g
user@host# set policer p3 then discard

```

5. Define the interface set **ifset** to be the group of all Fast Ethernet interfaces on the router.

```

[edit firewall]
user@host# set interface-set ifset fe-*

```



6. Create the stateless firewall filter **L2\_filter**.

```
[edit firewall]
user@host# edit family any filter L2_filter
```

7. Configure filter term **t1** to match IPv4, IPv6, or MPLS packets received on interface **fe-0/0/0.0** and use policer **p1** to rate-limit that traffic.

```
[edit firewall family any filter L2_filter]
user@host# set term t1 from interface fe-0/0/0.0
user@host# set term t1 then count c1
user@host# set term t1 then policer p1
```

8. Configure filter term **t2** to match packets received on interface-set **ifset** and use policer **p2** to rate-limit that traffic.

```
[edit firewall family any filter L2_filter]
user@host# set term t2 from interface-set ifset
user@host# set term t2 then count c2
user@host# set term t2 then policer p2
```

9. Configure filter term **t3** to use policer **p3** to rate-limit all other traffic.

```
[edit firewall family any filter L2_filter]
user@host# set term t3 then count c3
user@host# set term t3 then policer p3
```

10. If you are done configuring the device, commit the configuration.

```
[edit]
user@host# commit
```

**Results** Confirm the configuration of the stateless firewall filter and the policers referenced as firewall filter actions by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this procedure to correct the configuration.

```
[edit]
user@host# show firewall
family any {
  filter L2_filter {
    term t1 {
      from {
        interface fe-0/0/0.0;
      }
      then {
        policer p1;
        count c1;
      }
    }
    term t2 {
      from {
        interface-set ifset;
      }
      then {
        policer p2;
        count c2;
      }
    }
  }
}
```



```

    }
    term t3 {
        then {
            policer p3;
            count c3;
        }
    }
}
}
policer p1 {
    if-exceeding {
        bandwidth-limit 5m;
        burst-size-limit 10m;
    }
    then discard;
}
policer p2 {
    if-exceeding {
        bandwidth-limit 40m;
        burst-size-limit 100m;
    }
    then discard;
}
policer p3 {
    if-exceeding {
        bandwidth-limit 600m;
        burst-size-limit 1g;
    }
    then discard;
}
interface-set ifset {
    fe-*;
}

```

### Applying the Stateless Firewall Filter to the Routing Engine Input Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to the Routing Engine input interface:

1. Apply the stateless firewall filter to the Routing Engine interface in the input direction.

[edit]

```
user@host# set interfaces lo0 unit 0 family inet address 1.1.1.157/30
```

```
user@host# set interfaces lo0 unit 0 filter input L2_filter
```

2. If you are done configuring the device, commit the configuration.

[edit]

```
user@host# commit
```

#### Results

Confirm the application of the firewall filter to the Routing Engine input interface by entering the **show interfaces** command again. If the command output does not display the intended configuration, repeat the instructions in this procedure to correct the configuration.

```
user@host# show interfaces
fe-0/0/0 {
```



```
...
}
fe-1/0/0 {
...
}
fe-1/1/0 {
...
}
lo0 {
  unit 0 {
    filter {
      input L2_filter;
    }
    family inet {
      address 1.1.1.157/30;
    }
  }
}
```

## Verification

To confirm that the configuration is working properly, use the **show firewall filter L2\_filter** operational mode command to monitor traffic statistics about the firewall filter and three counters.

### Related Documentation

- [Understanding How to Use Standard Firewall Filters on page 27](#)
- [Filtering Packets Received on an Interface Set Overview on page 58](#)
- [Statement Hierarchy for Defining an Interface Set on page 329](#)
- [Statement Hierarchy for Configuring a Filter to Match on an Interface Set on page 329](#)

---

## Example: Configuring Filter-Based Forwarding on the Source Address

This example shows how to configure filter-based forwarding (FBF).

- [Requirements on page 200](#)
- [Overview on page 200](#)
- [Configuration on page 201](#)
- [Verification on page 204](#)

## Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, the router receives IPv4 traffic from one application server that is destined for a different application server. The router matches this flow of data packets using a firewall filter based on the packet IP source address. Any matching packets are routed



to a routing instance that first sends all traffic to a security device, then forwards the traffic to the designated destination address.

### Topology

The source application server is at host IP address 10.1.0.1/24, and the destination application server is at host IP address 10.1.3.1/24.

The router interface to the source application server is **ge-0/0/0.0**, and the router interface to the destination application server is **ge-0/0/3.0**.

The routing instance **ri\_fbf** routing table **ri\_fbf.inet0** is configured with the interface **ge-0/0/1.0** to the security device and the interface **ge-0/0/3.0** to the destination application server.

The firewall filter **filter\_fbf** matches packets on the source IP address 1.1.1.1/32 and directs matching packets to the routing instance **ri\_fbf**,

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Routing Instance on page 202](#)
- [Configure the Stateless Firewall Filter on page 202](#)
- [Configure the Interfaces to the Application Servers and Apply the Stateless Firewall Filter on page 202](#)
- [Confirm and Commit Your Candidate Configuration on page 203](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set interfaces ge-0/0/0 unit 0 family inet address 10.1.0.1/24
set interfaces ge-0/0/3 unit 0 family inet address 10.1.3.1/24
set routing-instances ri_fbf instance-type forwarding
set routing-instances ri_fbf interface ge-0/0/1.0
set routing-instances ri_fbf interface ge-0/0/3.0
set routing-instances ri_fbf routing-options static route 12.34.56.0/24 next-hop 10.1.3.254
set firewall family inet filter filter_fbf term t1 from protocol tcp
set firewall family inet filter filter_fbf term t1 from source-address 1.1.1.1/32
set firewall family inet filter filter_fbf term t1 then routing-instance ri_fbf
set interfaces ge-0/0/0 unit 0 family inet filter input filter_fbf
```



### Configure the Routing Instance

---

#### Step-by-Step Procedure

To configure the routing instance:

1. Create the routing instance. The **forwarding** routing instance type supports filter-based forwarding, where interfaces are not associated with instances. For this instance type, there is no one-to-one mapping between an interface and a routing instance. All interfaces belong to the default instance **inet.0**.

```
[edit]
user@host# set routing-instances ri_fbf instance-type forwarding
```

2. Associate the interfaces with the routing instance.

```
[edit]
user@host# set routing-instances ri_fbf interface ge-0/0/1.0
user@host# set routing-instances ri_fbf interface ge-0/0/3.0
```

3. Configure the routing information for the routing instance.

```
[edit]
user@host# set routing-instances ri_fbf routing-options static route 12.34.56.0/24
next-hop 10.1.3.254
```

### Configure the Stateless Firewall Filter

---

#### Step-by-Step Procedure

To configure the stateless firewall filter:

1. Create the firewall filter.

```
[edit]
user@host# set firewall family inet filter filter_fbf term t1 from protocol tcp
```

2. Set the firewall filter to match the correct source address.

```
[edit]
user@host# set firewall family inet filter filter_fbf term t1 from source-address
1.1.1.1/32
```

3. Set the firewall filter to forward packets to the routing instance.

```
[edit]
user@host# set firewall family inet filter filter_fbf term t1 then routing-instance ri_fbf
```

### Configure the Interfaces to the Application Servers and Apply the Stateless Firewall Filter

---

#### Step-by-Step Procedure

To configure the interfaces to the application servers and apply the stateless firewall filter to the interface to the source application server:

1. Configure the interface to the source application server.

```
[edit]
user@host# set interfaces ge-0/0/0 unit 0 family inet address 10.1.0.1/24
```



2. Configure the interface to the destination application server.

```
[edit]
user@host# set interfaces ge-0/0/3 unit 0 family inet address 10.1.3.1/24
```

3. Apply the stateless firewall filter to the input from the source application server.

```
[edit]
user@host# set interfaces ge-0/0/0 unit 0 family inet filter input filter_fbf
```

### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the routing instance by entering the **show routing-instances** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show routing-instances
ri_fbf {
  instance-type forwarding;
  interface ge-0/0/1.0;
  interface ge-0/0/3.0;
  routing-options {
    static {
      route 12.34.56.0/24 next-hop 10.1.3.254;
    }
  }
}
```

2. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter filter_fbf {
    term t1 {
      from {
        source-address {
          1.1.1.1/32;
        }
        protocol tcp;
      }
      then {
        routing-instance ri_fbf;
      }
    }
  }
}
```



3. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
ge-0/0/0 {
  unit 0 {
    family inet {
      filter {
        input filter_fbf;
      }
      address 10.1.0.1/24;
    }
  }
}
ge-0/0/3 {
  unit 0 {
    family inet {
      address 10.1.3.1/24;
    }
  }
}
```

## Verification

Confirm that the configuration is working properly.

### Verifying That Filter-Based Forwarding Is Configured

**Purpose** Verify that the firewall filter is enabled on the interface to the source application server and that the router forwarding table and the routing instance forwarding table contain the correct information.

**Action** To perform the verification:

1. Use the **show interfaces filters** command to display firewall filter information for the interface to the source application server.

```
user@host> show interfaces filters ge-0/0/0.0
Interface      Admin Link Proto Input Filter      Output Filter
ge-0/0/0.0     up    down inet  filter_fbf
```

2. Use the **show route forwarding-table** command to verify the contents of the router forwarding table and the routing instance forwarding table.

```
user@host> show route forwarding-table
```

```
Routing table: default.inet
Internet:
Destination      Type RtRef Next hop      Type Index NhRef Netif
default          user  1 0:12:f2:21:cf:0 ucst  331  4 me0.0
default          perm  0                rjct  36   3
0.0.0.0/32       perm  0                dscl  34   1
10.1.0.0/24      ifdn  0                rslv  613  1 ge-0/0/0.0
10.1.0.0/32      iddn  0 10.1.0.0       recv  611  1 ge-0/0/0.0
10.1.0.1/32      user  0                rjct  36   3
```



```

10.1.0.1/32      intf    0 10.1.0.1      locl  612    2
10.1.0.1/32      iddn    0 10.1.0.1      locl  612    2
10.1.0.255/32    iddn    0 10.1.0.255    bcst  610    1 ge-0/0/0.0
10.1.1.0/26      ifdn    0                rslv  583    1 vlan.0
10.1.1.0/32      iddn    0 10.1.1.0      recv  581    1 vlan.0
10.1.1.1/32      user    0                rjct   36    3
10.1.1.1/32      intf    0 10.1.1.1      locl  582    2
10.1.1.1/32      iddn    0 10.1.1.1      locl  582    2
10.1.1.63/32     iddn    0 10.1.1.63     bcst  580    1 vlan.0
255.255.255.255/32 perm    0                bcst   32    1

```

#### Routing table: ri\_fbf.inet

##### Internet:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	559	2	
0.0.0.0/32	perm	0		dscd	545	1	
10.1.3.0/24	ifdn	0		rslv	617	1	ge-0/0/3.0
10.1.3.0/32	iddn	0	10.1.3.0	recv	615	1	ge-0/0/3.0
10.1.3.1/32	user	0		rjct	559	2	
10.1.3.1/32	intf	0	10.1.3.1	locl	616	2	
10.1.3.1/32	iddn	0	10.1.3.1	locl	616	2	
10.1.3.255/32	iddn	0	10.1.3.255	bcst	614	1	ge-0/0/3.0
224.0.0.0/4	perm	0		mdsc	546	1	
224.0.0.1/32	perm	0	224.0.0.1	mcst	529	1	
255.255.255.255/32	perm	0		bcst	543	1	

#### Routing table: default.iso

##### ISO:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	60	1	

#### Routing table: ri\_fbf.iso

##### ISO:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	600	1	

**Meaning** The output indicates that the filter was created on the interface and that the routing instance is forwarding matching traffic to the correct IP address.

- Related Documentation**
- [Filter-Based Forwarding Overview on page 58](#)
  - [Filter-Based Forwarding for Routing Instances](#)
  - [Statement Hierarchy for Configuring FBF for IPv4 or IPv6 Traffic on page 330](#)
  - [Statement Hierarchy for Configuring FBF for IPv4 Traffic on ACX Series Routers on page 331](#)
  - [Statement Hierarchy for Configuring FBF for MPLS-Tagged IPv4 Traffic on page 331](#)
  - [Statement Hierarchy for Configuring Routing Instances for FBF on page 333](#)
  - [Statement Hierarchy for Applying FBF Filters to Interfaces on page 334](#)



## Example: Configuring Filter-Based Forwarding on Logical Systems

---

This example shows how to configure filter-based forwarding within a logical system. The filter classifies packets to determine their forwarding path within the ingress routing device.

- [Requirements on page 206](#)
- [Overview on page 206](#)
- [Configuration on page 208](#)
- [Verification on page 214](#)

### Requirements

In this example, no special configuration beyond device initialization is required.

### Overview

Filter-based forwarding is supported for IP version 4 (IPv4) and IP version 6 (IPv6).

Use filter-based forwarding for service provider selection when customers have Internet connectivity provided by different ISPs yet share a common access layer. When a shared media (such as a cable modem) is used, a mechanism on the common access layer looks at Layer 2 or Layer 3 addresses and distinguishes between customers. You can use filter-based forwarding when the common access layer is implemented using a combination of Layer 2 switches and a single router.

With filter-based forwarding, all packets received on an interface are considered. Each packet passes through a filter that has match conditions. If the match conditions are met for a filter and you have created a routing instance, filter-based forwarding is applied to a packet. The packet is forwarded based on the next hop specified in the routing instance. For static routes, the next hop can be a specific LSP.



**NOTE:** Source-class usage filter matching and unicast reverse-path forwarding checks are not supported on an interface configured with filter-based forwarding (FBF).

To configure filter-based forwarding, perform the following tasks:

- Create a match filter on an ingress router. To specify a match filter, include the **filter filter-name** statement at the **[edit firewall]** hierarchy level. A packet that passes through the filter is compared against a set of rules to classify it and to determine its membership in a set. Once classified, the packet is forwarded to a routing table specified in the accept action in the filter description language. The routing table then forwards the packet to the next hop that corresponds to the destination address entry in the table.
- Create routing instances that specify the routing table(s) to which a packet is forwarded, and the destination to which the packet is forwarded at the **[edit routing-instances]** or



[edit logical-systems *logical-system-name* routing-instances] hierarchy level. For example:

```
[edit]
routing-instances {
  routing-table-name1 {
    instance-type forwarding;
    routing-options {
      static {
        route 0.0.0.0/0 nexthop 10.0.0.1;
      }
    }
  }
  routing-table-name2 {
    instance-type forwarding;
    routing-options {
      static {
        route 0.0.0.0/0 nexthop 10.0.0.2;
      }
    }
  }
}
```

- Create a routing table group that adds interface routes to the forwarding routing instances used in filter-based forwarding (FBF), as well as to the default routing instance **inet.0**. This part of the configuration resolves the routes installed in the routing instances to directly connected next hops on that interface. Create the routing table group at the [edit routing-options] or [edit logical-systems *logical-system-name* routing-options] hierarchy level.



**NOTE:** Specify **inet.0** as one of the routing instances that the interface routes are imported into. If the default instance **inet.0** is not specified, interface routes are not imported into the default routing instance.

This example shows a packet filter that directs customer traffic to a next-hop router in the domains, SP 1 or SP 2, based on the packet's source address.

If the packet has a source address assigned to an SP 1 customer, destination-based forwarding occurs using the `sp1-route-table.inet.0` routing table. If the packet has a source address assigned to an SP 2 customer, destination-based forwarding occurs using the `sp2-route-table.inet.0` routing table. If a packet does not match either of these conditions, the filter accepts the packet, and destination-based forwarding occurs using the standard `inet.0` routing table.

One way to make filter-based forwarding work within a logical system is to configure the firewall filter on the logical system that receives the packets. Another way is to configure the firewall filter on the main router and then reference the logical system in the firewall filter. This example uses the second approach. The specific routing instances are configured within the logical system. Because each routing instance has its own routing table, you have to reference the routing instances in the firewall filter, as well. The syntax looks as follows:




```
[edit firewall filter filter-name term term-name]
user@host# set then logical-system logical-system-name routing-instance
routing-instance-name
```

Figure 3 on page 208 shows the topology used in this example.

On Logical System P1, an input filter classifies packets received from Logical System PE3 and Logical System PE4. The packets are routed based on the source addresses. Packets with source addresses in the 10.1.1.0/24 and 10.1.2.0/24 networks are routed to Logical System PE1. Packets with source addresses in the 10.2.1.0/24 and 10.2.2.0/24 networks are routed to Logical System PE2.

**Figure 3: Logical Systems with Filter-Based Forwarding**



To establish connectivity, OSPF is configured on all of the interfaces. For demonstration purposes, loopback interface addresses are configured on the routing devices to represent networks in the clouds.

The “[CLI Quick Configuration](#)” on page 208 section shows the entire configuration for all of the devices in the topology. The “[Configuring the Routing Instances on the Logical System P1](#)” on page 211 and “[Configuring the Firewall Filter on the Main Router](#)” on page 210 sections shows the step-by-step configuration of the ingress routing device, Logical System P1.

## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall filter classify-customers term sp1-customers from source-address 10.1.1.0/24
set firewall filter classify-customers term sp1-customers from source-address 10.1.2.0/24
set firewall filter classify-customers term sp1-customers then log
set firewall filter classify-customers term sp1-customers then logical-system P1
  routing-instance sp1-route-table
set firewall filter classify-customers term sp2-customers from source-address 10.2.1.0/24
set firewall filter classify-customers term sp2-customers from source-address 10.2.2.0/24
set firewall filter classify-customers term sp2-customers then log
set firewall filter classify-customers term sp2-customers then logical-system P1
  routing-instance sp2-route-table
```



```

set firewall filter classify-customers term default then accept
set logical-systems P1 interfaces lt-1/2/0 unit 10 encapsulation ethernet
set logical-systems P1 interfaces lt-1/2/0 unit 10 peer-unit 9
set logical-systems P1 interfaces lt-1/2/0 unit 10 family inet filter input classify-customers
set logical-systems P1 interfaces lt-1/2/0 unit 10 family inet address 172.16.0.10/30
set logical-systems P1 interfaces lt-1/2/0 unit 13 encapsulation ethernet
set logical-systems P1 interfaces lt-1/2/0 unit 13 peer-unit 14
set logical-systems P1 interfaces lt-1/2/0 unit 13 family inet address 172.16.0.13/30
set logical-systems P1 interfaces lt-1/2/0 unit 17 encapsulation ethernet
set logical-systems P1 interfaces lt-1/2/0 unit 17 peer-unit 18
set logical-systems P1 interfaces lt-1/2/0 unit 17 family inet address 172.16.0.17/30
set logical-systems P1 protocols ospf rib-group fbf-group
set logical-systems P1 protocols ospf area 0.0.0.0 interface all
set logical-systems P1 protocols ospf area 0.0.0.0 interface fxp0.0 disable
set logical-systems P1 routing-instances sp1-route-table instance-type forwarding
set logical-systems P1 routing-instances sp1-route-table routing-options static route
    0.0.0.0/0 next-hop 172.16.0.13
set logical-systems P1 routing-instances sp2-route-table instance-type forwarding
set logical-systems P1 routing-instances sp2-route-table routing-options static route
    0.0.0.0/0 next-hop 172.16.0.17
set logical-systems P1 routing-options rib-groups fbf-group import-rib inet.0
set logical-systems P1 routing-options rib-groups fbf-group import-rib
    sp1-route-table.inet.0
set logical-systems P1 routing-options rib-groups fbf-group import-rib
    sp2-route-table.inet.0
set logical-systems P2 interfaces lt-1/2/0 unit 2 encapsulation ethernet
set logical-systems P2 interfaces lt-1/2/0 unit 2 peer-unit 1
set logical-systems P2 interfaces lt-1/2/0 unit 2 family inet address 172.16.0.2/30
set logical-systems P2 interfaces lt-1/2/0 unit 6 encapsulation ethernet
set logical-systems P2 interfaces lt-1/2/0 unit 6 peer-unit 5
set logical-systems P2 interfaces lt-1/2/0 unit 6 family inet address 172.16.0.6/30
set logical-systems P2 interfaces lt-1/2/0 unit 9 encapsulation ethernet
set logical-systems P2 interfaces lt-1/2/0 unit 9 peer-unit 10
set logical-systems P2 interfaces lt-1/2/0 unit 9 family inet address 172.16.0.9/30
set logical-systems P2 protocols ospf area 0.0.0.0 interface all
set logical-systems P2 protocols ospf area 0.0.0.0 interface fxp0.0 disable
set logical-systems PE1 interfaces lt-1/2/0 unit 14 encapsulation ethernet
set logical-systems PE1 interfaces lt-1/2/0 unit 14 peer-unit 13
set logical-systems PE1 interfaces lt-1/2/0 unit 14 family inet address 172.16.0.14/30
set logical-systems PE1 interfaces lo0 unit 3 family inet address 1.1.1.1/32
set logical-systems PE1 protocols ospf area 0.0.0.0 interface all
set logical-systems PE1 protocols ospf area 0.0.0.0 interface fxp0.0 disable
set logical-systems PE2 interfaces lt-1/2/0 unit 18 encapsulation ethernet
set logical-systems PE2 interfaces lt-1/2/0 unit 18 peer-unit 17
set logical-systems PE2 interfaces lt-1/2/0 unit 18 family inet address 172.16.0.18/30
set logical-systems PE2 interfaces lo0 unit 4 family inet address 2.2.2.2/32
set logical-systems PE2 protocols ospf area 0.0.0.0 interface all
set logical-systems PE2 protocols ospf area 0.0.0.0 interface fxp0.0 disable
set logical-systems PE3 interfaces lt-1/2/0 unit 1 encapsulation ethernet
set logical-systems PE3 interfaces lt-1/2/0 unit 1 peer-unit 2
set logical-systems PE3 interfaces lt-1/2/0 unit 1 family inet address 172.16.0.1/30
set logical-systems PE3 interfaces lo0 unit 1 family inet address 10.1.1.1/32
set logical-systems PE3 interfaces lo0 unit 1 family inet address 10.1.2.1/32
set logical-systems PE3 protocols ospf area 0.0.0.0 interface all
set logical-systems PE3 protocols ospf area 0.0.0.0 interface fxp0.0 disable
set logical-systems PE4 interfaces lt-1/2/0 unit 5 encapsulation ethernet

```



```
set logical-systems PE4 interfaces lt-1/2/0 unit 5 peer-unit 6
set logical-systems PE4 interfaces lt-1/2/0 unit 5 family inet address 172.16.0.5/30
set logical-systems PE4 interfaces lo0 unit 2 family inet address 10.2.1.1/32
set logical-systems PE4 interfaces lo0 unit 2 family inet address 10.2.2.1/32
set logical-systems PE4 protocols ospf area 0.0.0.0 interface all
set logical-systems PE4 protocols ospf area 0.0.0.0 interface fxp0.0 disable
```

---

### Configuring the Firewall Filter on the Main Router

---

#### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure the firewall filter on the main router:

1. Configure the source addresses for SP1 customers.

```
[edit firewall filter classify-customers term sp1-customers]
user@host# set from source-address 10.1.1.0/24
user@host# set from source-address 10.1.2.0/24
```

2. Configure the actions that are taken when packets are received with the specified source addresses.

To track the action of the firewall filter, a log action is configured. The sp1-route-table.inet.0 routing table on Logical System P1 routes the packets.

```
[edit firewall filter classify-customers term sp1-customers]
user@host# set then log
user@host# set then logical-system P1 routing-instance sp1-route-table
```

3. Configure the source addresses for SP2 customers.

```
[edit firewall filter classify-customers term sp2-customers]
user@host# set from source-address 10.2.1.0/24
user@host# set from source-address 10.2.2.0/24
```

4. Configure the actions that are taken when packets are received with the specified source addresses.

To track the action of the firewall filter, a log action is configured. The sp2-route-table.inet.0 routing table on Logical System P1 routes the packet.

```
[edit firewall filter classify-customers term sp2-customers]
user@host# set then log
user@host# set then logical-system P1 routing-instance sp2-route-table
```

5. Configure the action to take when packets are received from any other source address.

All of these packets are simply accepted and routed using the default IPv4 unicast routing table, inet.0.

```
[edit firewall filter classify-customers term default]
user@host# set then accept
```



### Configuring the Routing Instances on the Logical System P1

- Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.
- To configure the routing instances on a logical system:
1. Configure the interfaces on the logical system.
 

```
[edit logical-systems P1 interfaces lt-1/2/0]
user@host# set unit 10 encapsulation ethernet
user@host# set unit 10 peer-unit 9
user@host# set unit 10 family inet address 172.16.0.10/30

user@host# set unit 13 encapsulation ethernet
user@host# set unit 13 peer-unit 14
user@host# set unit 13 family inet address 172.16.0.13/30

user@host# set unit 17 encapsulation ethernet
user@host# set unit 17 peer-unit 18
user@host# set unit 17 family inet address 172.16.0.17/30
```
  2. Assign the **classify-customers** firewall filter to router interface lt-1/2/0.10 as an input packet filter.
 

```
[edit logical-systems P1 interfaces lt-1/2/0]
user@host# set unit 10 family inet filter input classify-customers
```
  3. Configure connectivity, using either a routing protocol or static routing.
 

As a best practice, disable routing on the management interface.

```
[edit logical-systems P1 protocols ospf area 0.0.0.0]
user@host# set interface all
user@host# set interface fxp0.0 disable
```
  4. Create the routing instances.
 

These routing instances are referenced in the **classify-customers** firewall filter.

The forwarding instance type provides support for filter-based forwarding, where interfaces are not associated with instances. All interfaces belong to the default instance, in this case Logical System P1.

```
[edit logical-systems P1 routing-instances]
user@host# set sp1-route-table instance-type forwarding

user@host# set sp2-route-table instance-type forwarding
```
  5. Resolve the routes installed in the routing instances to directly connected next hops.
 

```
[edit logical-systems P1 routing-instances]
user@host# set sp1-route-table routing-options static route 0.0.0.0/0 next-hop
172.16.0.13
```



```
user@host# set sp2-route-table routing-options static route 0.0.0.0/0 next-hop
172.16.0.17
```

6. Group together the routing tables to form a routing table group.

The first routing table, inet.0, is the primary routing table, and the additional routing tables are the secondary routing tables.

The primary routing table determines the address family of the routing table group, in this case IPv4.

```
[edit logical-systems P1 routing-options]
user@host# set rib-groups fbf-group import-rib inet.0
user@host# set rib-groups fbf-group import-rib sp1-route-table.inet.0
user@host# set rib-groups fbf-group import-rib sp2-route-table.inet.0
```

7. Apply the routing table group to OSPF.

This causes the OSPF routes to be installed into all the routing tables in the group.

```
[edit logical-systems P1 protocols ospf]
user@host# set rib-group fbf-group
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@host# commit
```

Confirm your configuration by issuing the **show firewall** and **show logical-systems P1** commands.

```
user@host# show firewall
filter classify-customers {
  term sp1-customers {
    from {
      source-address {
        10.1.1.0/24;
        10.1.2.0/24;
      }
    }
    then {
      log;
      logical-system P1 routing-instance sp1-route-table;
    }
  }
  term sp2-customers {
    from {
      source-address {
        10.2.1.0/24;
        10.2.2.0/24;
      }
    }
    then {
      log;
      logical-system P1 routing-instance sp2-route-table;
    }
  }
  term default {
```



```

        then accept;
    }
}

user@host# show logical-systems P1
interfaces {
    lt-1/2/0 {
        unit 10 {
            encapsulation ethernet;
            peer-unit 9;
            family inet {
                filter {
                    input classify-customers;
                }
                address 172.16.0.10/30;
            }
        }
        unit 13 {
            encapsulation ethernet;
            peer-unit 14;
            family inet {
                address 172.16.0.13/30;
            }
        }
        unit 17 {
            encapsulation ethernet;
            peer-unit 18;
            family inet {
                address 172.16.0.17/30;
            }
        }
    }
}

protocols {
    ospf {
        rib-group fbf-group;
        area 0.0.0.0 {
            interface all;
            interface fxp0.0 {
                disable;
            }
        }
    }
}

routing-instances {
    sp1-route-table {
        instance-type forwarding;
        routing-options {
            static {
                route 0.0.0.0/0 next-hop 172.16.0.13;
            }
        }
    }
    sp2-route-table {
        instance-type forwarding;
        routing-options {

```



```

        static {
            route 0.0.0.0/0 next-hop 172.16.0.17;
        }
    }
}
routing-options {
    rib-groups {
        fbf-group {
            import-rib [ inet.0 sp1-route-table.inet.0 sp2-route-table.inet.0 ];
        }
    }
}

```

## Verification

Confirm that the configuration is working properly.

### Pinging with Specified Source Addresses

**Purpose** Send some ICMP packets across the network to test the firewall filter.

**Action** 1. Log in to Logical System PE3.

```

user@host> set cli logical-system PE3
Logical system: PE3

```

2. Run the **ping** command, pinging the lo0.3 interface on Logical System PE1.

The address configured on this interface is 1.1.1.1.

Specify the source address 10.1.2.1, which is the address configured on the lo0.1 interface on Logical System PE3.

```

user@host:PE3> ping 1.1.1.1 source 10.1.2.1
PING 1.1.1.1 (1.1.1.1): 56 data bytes
64 bytes from 1.1.1.1: icmp_seq=0 ttl=62 time=1.444 ms
64 bytes from 1.1.1.1: icmp_seq=1 ttl=62 time=2.094 ms
^C
--- 1.1.1.1 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.444/1.769/2.094/0.325 ms

```

3. Log in to Logical System PE4.

```

user@host:PE3> set cli logical-system PE4
Logical system: PE4

```

4. Run the **ping** command, pinging the lo0.4 interface on Logical System PE2.

The address configured on this interface is 2.2.2.2.

Specify the source address 10.2.1.1, which is the address configured on the lo0.2 interface on Logical System PE4.

```

user@host:PE4> ping 2.2.2.2 source 10.2.1.1
PING 2.2.2.2 (2.2.2.2): 56 data bytes
64 bytes from 2.2.2.2: icmp_seq=0 ttl=62 time=1.473 ms
64 bytes from 2.2.2.2: icmp_seq=1 ttl=62 time=1.407 ms
^C

```



```

--- 2.2.2.2 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.407/1.440/1.473/0.033 ms

```

**Meaning** Sending these pings activates the firewall filter actions.

### Verifying the Firewall Filter

**Purpose** Make sure the firewall filter actions take effect.

- Action**
1. Log in to Logical System P1.
  2. Run the **show firewall log** command on Logical System P1.

```

user@host: P1> show firewall log
Log :
Time      Filter  Action Interface  Protocol  Src Addr
Dest Addr
13:52:20  pfe        A          1t-1/2/0.10  ICMP      10.2.1.1
2.2.2.2
13:52:19  pfe        A          1t-1/2/0.10  ICMP      10.2.1.1
2.2.2.2
13:51:53  pfe        A          1t-1/2/0.10  ICMP      10.1.2.1
1.1.1.1
13:51:52  pfe        A          1t-1/2/0.10  ICMP      10.1.2.1
1.1.1.1

```

- Related Documentation**
- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)
  - [Example: Configuring Multitopology Routing Based on Applications](#)
  - [Configuring Filter-Based Forwarding](#)
  - [Copying and Redirecting Traffic with Port Mirroring and Filter-Based Forwarding](#)
  - [Using Filter-Based Forwarding to Export Monitored Traffic to Multiple Destinations](#)
  - [Filter-Based Forwarding Overview on page 58](#)

### Example: Configuring Filter-Based Forwarding to a Specific Outgoing Interface or Destination IP Address

- [Understanding Filter-Based Forwarding to a Specific Outgoing Interface or Destination IP Address on page 216](#)
- [Example: Configuring Filter-Based Forwarding to a Specific Outgoing Interface on page 217](#)



## Understanding Filter-Based Forwarding to a Specific Outgoing Interface or Destination IP Address

Policy-based routing (also known as filter-based forwarding) refers to the use of firewall filters that are applied to an interface to match certain IP header characteristics and to route only those matching packets differently than the packets would normally be routed.

Starting in Junos OS Release 12.2, you can use **then next-interface**, **then next-ip**, or **then next-ip6** as an action in a firewall filter.

For example:

```
from {  
    set of match conditions  
}  
then {  
    IP-address (or)  
    IPv6-address (or)  
    Interface name  
}
```

The set of match conditions can be as follows:

- Layer-3 properties (for example, the source or destination IP address or the TOS byte)
- Layer-4 properties (for example, the source or destination port)

The route for the given IPv4 or IPv6 address has to be present in the routing table for policy-based routing to take effect. Similarly, the route through the given interface has to be present in the forwarding table for **next-interface** action to take effect. This can be achieved by configuring an interior gateway protocol (IGP), such as OSPF or IS-IS, to advertise Layer 3 routes.

The firewall filter matches the conditions and forwards the packet to one of the following:

- An IPv4 address (using the **next-ip** firewall filter action)
- An IPv6 address (using the **next-ip6** firewall filter action)
- An interface (using the **next-interface** firewall filter action)

Suppose, for example, that you want to offer services to your customers, and the services reside on different servers. An example of a service might be hosted DNS or hosted FTP. As customer traffic arrives at the Juniper Networks routing device, you can use filter-based forwarding to send traffic to the servers by applying a match condition on a MAC address or an IP address or simply an incoming interface and send the packets to a certain outgoing interface that is associated with the appropriate server. Some of your destinations might be IPv4 or IPv6 addresses, in which case the **next-ip** or **next-ip6** action is useful.

Optionally, you can associate the outgoing interfaces or IP addresses with routing instances.

For example:

```
firewall {
```



```

filter filter1 {
  term t1 {
    from {
      source-address {
        10.1.1.3/32;
      }
    }
    then {
      next-interface {
        xe-0/1/0.1;
        routing-instance rins1;
      }
    }
  }
  term t2 {
    from {
      source-address {
        10.1.1.4/32;
      }
    }
    then {
      next-interface {
        xe-0/1/0.2;
        routing-instance rins2;
      }
    }
  }
}
routing-instances {
  rins1 {
    instance-type virtual-router;
    interface xe-0/1/0.1;
  }
  rins2 {
    instance-type virtual-router;
    interface xe-0/1/0.2;
  }
}

```

### Example: Configuring Filter-Based Forwarding to a Specific Outgoing Interface

This example shows how to use **then next-interface** as an action in a firewall filter.

- [Requirements on page 218](#)
- [Overview on page 218](#)
- [Configuration on page 218](#)
- [Verification on page 221](#)



## Requirements

This example has the following hardware and software requirements:

- MX Series 3D Universal Edge Router as the routing device with the firewall filter configured.
- Junos OS Release 12.2 running on the routing device with the firewall filter configured.
- The filter with the **next-interface** (or **next-ip**) action can only be applied to an interface that is hosted on a Trio MPC. If you apply the filter to an I-chip based DPC, the commit operation fails.
- The outgoing interface referred to in the **next-interface *interface-name*** action can be hosted on a Trio MPC or an I-chip based DPC.

## Overview


In this example, Device R1 has two loopback interface addresses configured: 172.16.1.1 and 172.16.2.2.

On Device R2, a firewall filter has multiple terms configured. Each term matches one of the source addresses in incoming traffic, and routes the traffic to specified outgoing interfaces. The outgoing interfaces are configured as VLAN-tagged interfaces between Device R2 and Device R3.

IS-IS is used for connectivity among the devices.

Figure 4 on page 218 shows the topology used in this example.

### Figure 4: Filter-Based Forwarding to Specified Outgoing Interfaces



This example shows the configuration on Device R2.

## Configuration

## CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

## Device R2

```
set interfaces ge-2/1/0 unit 0 family inet filter input filter1
set interfaces ge-2/1/0 unit 0 family inet address 10.0.0.10/30
set interfaces ge-2/1/0 unit 0 description to-R1
set interfaces ge-2/1/0 unit 0 family iso
set interfaces ge-2/1/1 vlan-tagging
set interfaces ge-2/1/1 description to-R3
```



```

set interfaces ge-2/1/1 unit 0 vlan-id 1001
set interfaces ge-2/1/1 unit 0 family inet address 10.0.0.13/30
set interfaces ge-2/1/1 unit 0 family iso
set interfaces ge-2/1/1 unit 1 vlan-id 1002
set interfaces ge-2/1/1 unit 1 family inet address 10.0.0.25/30
set interfaces ge-2/1/1 unit 1 family iso
set interfaces lo0 unit 0 family inet address 10.255.4.4/32
set interfaces lo0 unit 0 family iso address 49.0001.0010.0000.0404.00
set firewall family inet filter filter1 term t1 from source-address 172.16.1.1/32
set firewall family inet filter filter1 term t1 then next-interface ge-2/1/1.0
set firewall family inet filter filter1 term t2 from source-address 172.16.2.2/32
set firewall family inet filter filter1 term t2 then next-interface ge-2/1/1.1
set protocols isis interface all level 1 disable
set protocols isis interface fxp0.0 disable
set protocols isis interface lo0.0

```

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure Device R2:

1. Configure the interfaces.

```

[edit interfaces]
user@R2# set ge-2/1/0 unit 0 family inet filter input filter1
user@R2# set ge-2/1/0 unit 0 family inet address 10.0.0.10/30
user@R2# set ge-2/1/0 unit 0 description to-R1
user@R2# set ge-2/1/0 unit 0 family iso

user@R2# set ge-2/1/1 vlan-tagging
user@R2# set ge-2/1/1 description to-R3

user@R2# set ge-2/1/1 unit 0 vlan-id 1001
user@R2# set ge-2/1/1 unit 0 family inet address 10.0.0.13/30
user@R2# set ge-2/1/1 unit 0 family iso

user@R2# set ge-2/1/1 unit 1 vlan-id 1002
user@R2# set ge-2/1/1 unit 1 family inet address 10.0.0.25/30
user@R2# set ge-2/1/1 unit 1 family iso

user@R2# set lo0 unit 0 family inet address 10.255.4.4/32
user@R2# set lo0 unit 0 family iso address 49.0001.0010.0000.0404.00

```

2. Configure the firewall filter.

```

[edit firewall family inet filter filter1]
user@R2# set term t1 from source-address 172.16.1.1/32
user@R2# set term t1 then next-interface ge-2/1/1.0

user@R2# set term t2 from source-address 172.16.2.2/32
user@R2# set term t2 then next-interface ge-2/1/1.1

```

3. Enable IS-IS on the interfaces.



```
[edit protocols is-is]
user@R2# set interface all level 1 disable
user@R2# set interface fxp0.0 disable
user@R2# set interface lo0.0
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show firewall**, and **show protocols** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
user@R2# show interfaces
ge-2/1/0 {
  unit 0 {
    description to-R1;
    family inet {
      filter {
        input filter1;
      }
      address 10.0.0.10/30;
    }
    family iso;
  }
}
ge-2/1/1 {
  description to-R3;
  vlan-tagging;
  unit 0 {
    vlan-id 1001;
    family inet {
      address 10.0.0.13/30;
    }
    family iso;
  }
  unit 1 {
    vlan-id 1002;
    family inet {
      address 10.0.0.25/30;
    }
    family iso;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.255.4.4/32;
    }
    family iso {
      address 49.0001.0010.0000.0404.00;
    }
  }
}
}

user@R2# show firewall
family inet {
  filter filter1 {
    term t1 {
```



```

        from {
            source-address {
                172.16.1.1/32;
            }
        }
    then {
        next-interface {
            ge-2/1/1.0;
        }
    }
}
term t2 {
    from {
        source-address {
            172.16.2.2/32;
        }
    }
    then {
        next-interface {
            ge-2/1/1.1;
        }
    }
}
}
}
}

user@R2# show protocols
isis {
    interface all {
        level 1 disable;
    }
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}

```

If you are done configuring the device, enter **commit** from configuration mode.

### Verification

Confirm that the configuration is working properly.

#### Checking the Paths Used

**Purpose** Make sure that the expected paths are used when sending traffic from Device R1 to Device R4.

**Action** On Device R1, enter the **traceroute** command.

```

user@R1> traceroute 10.255.6.6 source 172.16.1.1
traceroute to 10.255.6.6 (10.255.6.6) from 172.16.1.1, 30 hops max, 40 byte packets
 1  10.0.0.10 (10.0.0.10)  0.976 ms  0.895 ms  0.815 ms
 2  10.0.0.14 (10.0.0.14)  0.868 ms  0.888 ms  0.813 ms
 3  10.255.6.6 (10.255.6.6)  1.715 ms  1.442 ms  1.382 ms

```



```
user@R1> traceroute 10.255.6.6 source 172.16.2.2
traceroute to 10.255.6.6 (10.255.6.6) from 172.16.2.2, 30 hops max, 40 byte packets

 1  10.0.0.10 (10.0.0.10)  0.973 ms  0.907 ms  0.782 ms
 2  10.0.0.26 (10.0.0.26)  0.844 ms  0.890 ms  0.852 ms
 3  10.255.6.6 (10.255.6.6)  1.384 ms  1.516 ms  1.462 ms
```

**Meaning** The output shows that the second hop changes, depending on the source address used in the **traceroute** command.

To verify this feature, a traceroute operation is performed on Device R1 to Device R4. When the source IP address is 172.16.1.1, packets are forwarded out the ge-2/1/1.0 interface on Device R2. When the source IP address is 172.16.2.2, packets are forwarded out the ge-2/1/1.1 interface on Device R2.

- Related Documentation**
- [Example: Configuring Filter-Based Forwarding on Logical Systems on page 206](#)
  - [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)
  - [Standard Firewall Filter Nonterminating Actions on page 294](#)



# Examples of Standard Firewall Filters Configuration Options

- [Example: Configuring Statistics Collection for a Standard Firewall Filter on page 223](#)
- [Example: Configuring Logging for a Stateless Firewall Filter Term on page 228](#)

## Example: Configuring Statistics Collection for a Standard Firewall Filter

---

This example shows how to configure and apply a stateless firewall filter that collects data according to parameters specified in an associated accounting profile.

- [Requirements on page 223](#)
- [Overview on page 223](#)
- [Configuration on page 224](#)
- [Verification on page 227](#)

### Requirements

Firewall filter accounting profiles are supported for all traffic types except **family any**.

No special configuration beyond device initialization is required before configuring this example.

### Overview

In this example, you create a firewall filter accounting profile and apply it to a stateless firewall filter. The accounting profile specifies how frequently to collect packet and byte count statistics and the name of the file to which the statistics are written. The profile also specifies that statistics are to be collected for three firewall filter counters.

### Topology

---

The firewall filter accounting profile **filter\_acctg\_profile** specifies that statistics are collected every 60 minutes, and the statistics are written to the file **/var/log/ff\_accounting\_file**. Statistics are collected for counters named **counter1**, **counter2**, and **counter3**.

The IPv4 stateless firewall filter named **my\_firewall\_filter** increments a counter for each of three filter terms. The filter is applied to logical interface **ge-0/0/1.0**.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure an Accounting Profile on page 224](#)
- [Configure a Firewall Filter That References the Accounting Profile on page 225](#)
- [Apply the Firewall Filter to an Interface on page 225](#)
- [Confirm Your Candidate Configuration on page 226](#)
- [Clear the Counters and Commit Your Candidate Configuration on page 227](#)

### CLI Quick Configuration

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set accounting-options filter-profile filter_acctg_profile file ff_accounting_file
set accounting-options filter-profile filter_acctg_profile interval 60
set accounting-options filter-profile filter_acctg_profile counters counter1
set accounting-options filter-profile filter_acctg_profile counters counter2
set accounting-options filter-profile filter_acctg_profile counters counter3
set firewall family inet filter my_firewall_filter accounting-profile filter_acctg_profile
set firewall family inet filter my_firewall_filter term term1 from protocol ospf
set firewall family inet filter my_firewall_filter term term1 then count counter1
set firewall family inet filter my_firewall_filter term term1 then discard
set firewall family inet filter my_firewall_filter term term2 from source-address
10.108.0.0/16
set firewall family inet filter my_firewall_filter term term2 then count counter2
set firewall family inet filter my_firewall_filter term term2 then discard
set firewall family inet filter my_firewall_filter term accept-all then count counter3
set firewall family inet filter my_firewall_filter term accept-all then accept
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input my_firewall_filter
```

---

### Configure an Accounting Profile

#### Step-by-Step Procedure

To configure an accounting profile:

1. Create the accounting profile **filter\_acctg\_profile**.

```
[edit]
user@host# edit accounting-options filter-profile filter_acctg_profile
```

2. Configure the accounting profile to filter and collect packet and byte count statistics every 60 minutes and write them to the **/var/log/ff\_accounting\_file** file.

```
[edit accounting-options filter-profile filter_acctg_profile]
user@host# set file ff_accounting_file
user@host# set interval 60
```



3. Configure the accounting profile to collect filter profile statistics (packet and byte counts) for three counters.

```
[edit accounting-options filter-profile filter_acctg_profile]
user@host# set counters counter1
user@host# set counters counter2
user@host# set counters counter3
```

### Configure a Firewall Filter That References the Accounting Profile

#### Step-by-Step Procedure

To configure a firewall filter that references the accounting profile:

1. Create the stateless firewall filter **my\_firewall\_filter**.

```
[edit]
user@host# edit firewall family inet filter my_firewall_filter
```

2. Apply the filter-accounting profile **filter\_acctg\_profile** to the firewall filter.

```
[edit firewall family inet filter my_firewall_filter]
user@host# set accounting-profile filter_acctg_profile
```

3. Configure the first filter term and counter.

```
[edit firewall family inet filter my_firewall_filter]
user@host# set term term1 from protocol ospf
user@host# set term term1 then count counter1
user@host# set term term1 then discard
```

4. Configure the second filter term and counter.

```
[edit firewall family inet filter my_firewall_filter]
user@host# set term term2 from source-address 10.108.0.0/16
user@host# set term term2 then count counter2
user@host# set term term2 then discard
```

5. Configure the third filter term and counter.

```
[edit firewall family inet filter my_firewall_filter]
user@host# set term accept-all then count counter3
user@host# set term accept-all then accept
```

### Apply the Firewall Filter to an Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```



3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input my_firewall_filter
```

---

### Confirm Your Candidate Configuration

#### Step-by-Step Procedure

To confirm your candidate configuration:

1. Confirm the configuration of the accounting profile by entering the **show accounting-options** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show accounting-options
filter-profile filter_acctg_profile {
  file ff_accounting_file;
  interval 60;
  counters {
    counter1;
    counter2;
    counter3;
  }
}
```

2. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter my_firewall_filter {
    accounting-profile filter_acctg_profile;
    term term1 {
      from {
        protocol ospf;
      }
      then {
        count counter1;
        discard;
      }
    }
    term term2 {
      from {
        source-address {
          10.108.0.0/16;
        }
      }
      then {
        count counter2;
        discard;
      }
    }
    term accept-all {
```



```

        then {
            count counter3;
            accept;
        }
    }
}

```

3. Confirm the configuration of the interfaces by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@host# show interfaces
ge-0/0/1 {
    unit 0 {
        family inet {
            filter {
                input my_firewall_filter;
            }
            address 10.1.2.3/30;
        }
    }
}

```

### Clear the Counters and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To clear the counters and commit your candidate configuration:

1. From operational command mode, use the **clear firewall all** command to clear the statistics for all firewall filters.

To clear only the counters incremented in this example, include the name of the firewall filter.

```

[edit]
user@host> clear firewall filter my_firewall_filter

```

2. Commit your candidate configuration.

```

[edit]
user@host# commit

```

### Verification

To verify that the filter is applied to the logical interface, run the **show interfaces** command with the **detail** or **extensive** output level.

To verify that the three counters are collected separately, run the **show firewall filter my\_firewall\_filter** command.

```

user@host> show firewall filter my_firewall_filter

```

```

Filter: my_firewall_filter

```

```

Counters:

```

Name	Bytes	Packets
counter1	0	0



counter2	0	0
counter3	0	0

**Related Documentation**

- [Accounting for Standard Firewall Filters Overview on page 60](#)
- [Statement Hierarchy for Configuring Firewall Filter Accounting Profiles on page 335](#)
- [Statement Hierarchy for Applying Firewall Filter Accounting Profiles on page 336](#)

---

## Example: Configuring Logging for a Stateless Firewall Filter Term

---

This example shows how to configure a standard stateless firewall filter to log packet headers.

- [Requirements on page 228](#)
- [Overview on page 228](#)
- [Configuration on page 228](#)
- [Verification on page 231](#)

### Requirements

No special configuration beyond device initialization is required before configuring this example.

### Overview

In this example, you use a stateless firewall filter that logs and counts ICMP packets that have 192.168.207.222 as either their source or destination.

### Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configure the Syslog Messages File for the Firewall Facility on page 229](#)
- [Configure the Stateless Firewall Filter on page 229](#)
- [Apply the Stateless Firewall Filter to a Logical Interface on page 229](#)
- [Confirm and Commit Your Candidate Configuration on page 230](#)

**CLI Quick Configuration**

To quickly configure this example, copy the following configuration commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set system syslog file messages_firewall_any firewall any
set system syslog file messages_firewall_any archive no-world-readable
set firewall family inet filter icmp_syslog term icmp_match from address
  192.168.207.222/32
set firewall family inet filter icmp_syslog term icmp_match from protocol icmp
```



```

set firewall family inet filter icmp_syslog term icmp_match then count packets
set firewall family inet filter icmp_syslog term icmp_match then log
set firewall family inet filter icmp_syslog term icmp_match then accept
set firewall family inet filter icmp_syslog term default_term then accept
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
set interfaces ge-0/0/1 unit 0 family inet filter input icmp_syslog

```

### Configure the Syslog Messages File for the Firewall Facility

#### Step-by-Step Procedure

To configure a syslog messages file for the **firewall** facility:

1. Configure a messages file for all syslog messages generated for the **firewall** facility.  
  

```

user@host# set system syslog file messages_firewall_any firewall any

```
2. Restrict permission to the archived **firewall** facility syslog files to the root user and users who have the Junos OS maintenance permission.  
  

```

user@host# set system syslog file messages_firewall_any archive no-world-readable

```

### Configure the Stateless Firewall Filter

#### Step-by-Step Procedure

To configure the stateless firewall filter **icmp\_syslog** that logs and counts ICMP packets that have **192.168.207.222** as either their source or destination:

1. Create the stateless firewall filter **icmp\_syslog**.  
  

```

[edit]
user@host# edit firewall family inet filter icmp_syslog

```
2. Configure matching on the ICMP protocol and an address.  
  

```

[edit firewall family inet filter icmp_syslog]
user@host# set term icmp_match from address 192.168.207.222/32
user@host# set term icmp_match from protocol icmp

```
3. Count, log, and accept matching packets.  
  

```

[edit firewall family inet filter icmp_syslog]
user@host# set term icmp_match then count packets
user@host# set term icmp_match then log
user@host# set term icmp_match then accept

```
4. Accept all other packets.  
  

```

[edit firewall family inet filter icmp_syslog]
user@host# set term default_term then accept

```

### Apply the Stateless Firewall Filter to a Logical Interface

#### Step-by-Step Procedure

To apply the stateless firewall filter to a logical interface:

1. Configure the logical interface to which you will apply the stateless firewall filter.  
  

```

[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet

```



2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the stateless firewall filter to the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set filter input icmp_syslog
```

---

### Confirm and Commit Your Candidate Configuration

#### Step-by-Step Procedure

To confirm and then commit your candidate configuration:

1. Confirm the configuration of the syslog message file for the **firewall** facility by entering the **show system** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show system
syslog {
  file messages_firewall_any {
    firewall any;
    archive no-world-readable;
  }
}
```

2. Confirm the configuration of the stateless firewall filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show firewall
family inet {
  filter icmp_syslog {
    term icmp_match {
      from {
        address {
          192.168.207.222/32;
        }
        protocol icmp;
      }
      then {
        count packets;
        log;
        accept;
      }
    }
    term default_term {
      then accept;
    }
  }
}
```



3. Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
ge-0/0/1 {
  unit 0 {
    family inet {
      filter {
        input icmp_syslog;
      }
      address 10.1.2.3/30;
    }
  }
}
```

4. If you are done configuring the device, commit your candidate configuration.

```
[edit]
user@host# commit
```

## Verification

To confirm that the configuration is working properly, enter the **show log filter** command:

```
user@host> show log messages_firewall_any
Mar 20 08:03:11 hostname feb FW: so-0/1/0.0   A icmp 192.168.207.222
192.168.207.223      0      0 (1 packets)
```

This output file contains the following fields:

- **Date and Time**—Date and time at which the packet was received (not shown in the default).
- **Filter action**:
  - **A**—Accept (or next term)
  - **D**—Discard
  - **R**—Reject
- **Protocol**—Packet's protocol name or number.
- **Source address**—Source IP address in the packet.
- **Destination address**—Destination IP address in the packet.



**NOTE:** If the protocol is ICMP, the ICMP type and code are displayed. For all other protocols, the source and destination ports are displayed.

The last two fields (both zero) are the source and destination TCP/UDP ports, respectively, and are shown for TCP or UDP packets only. This log message indicates that only one packet for this match has been detected in about a 1-second interval. If packets arrive



faster, the system log function compresses the information so that less output is generated, and displays an output similar to the following:

```
user@host> show log filter
Mar 20 08:08:45 hostname feb FW: so-0/1/0.0  A icmp 192.168.207.222
192.168.207.223      0      0 (515 packets)
```

**Related  
Documentation**

- [System Logging Overview on page 60](#)
- [Logging of Packet Headers Evaluated by a Firewall Filter Term on page 63](#)
- System log messages with the **DFWD\_** prefix, described in the *Junos OS System Log Messages Reference*
- System log messages with the **PFE\_FW\_\*** prefix, described in the *Junos OS System Log Messages Reference*



## CHAPTER 18

# Service Filters Configuration

- [Example: Configuring and Applying Service Filters on page 233](#)

### Example: Configuring and Applying Service Filters

---

This example shows how to configure and apply service filters.

- [Requirements on page 233](#)
- [Overview on page 233](#)
- [Configuration on page 234](#)
- [Verification on page 237](#)

### Requirements

This example use the logical interface **xe-0/1/0.0** on any of the following hardware components:

- Adaptive Services (AS) PIC on an M Series or T Series router
- Multiservices (MS) PIC on an M Series or T Series router
- Multiservices (MS) DPC on an MX Series router

Before you begin, make sure that you have:

- Installed your supported router and PICs or DPCs and performed the initial router configuration.
- Configured basic Ethernet in the topology, and verified that traffic is flowing in the topology and that IPv4 traffic is flowing through logical interface **xe-0/1/0.0**.
- Configured the service set **vrf\_svcs** with service input and output rules and default settings for services at a service interface.

For guidelines for configuring service sets, see “Configuring Service Sets to be Applied to Services Interfaces” in the Junos Services Interfaces Configuration Release 11.2.

### Overview

In this example, you create three types of service filters for IPv4 traffic: one input service filter, one postservice input filter, and one output service filter.



## Topology

You apply the input service filter and postservice input filter to input traffic at logical interface **xe-0/1/0.0**, and you apply the output service filter to the output traffic at the same logical interface.

- Filtering IPv4 traffic before it is accepted for input service processing—At logical interface **xe-0/1/0.0**, you use the service filter **in\_filter\_presvc** to filter IPv4 input traffic before the traffic can be accepted for processing by services associated with service set **vrf\_svcs**. The **in\_filter\_presvc** service filter counts packets sent from ICMP port 179, directs these packets to the input services associated with the service set **vrf\_svcs**, and discards all other packets.
- Filtering IPv4 traffic after it has completed input service processing—At logical interface **xe-0/1/0.0**, you use the service filter **in\_filter\_postsvc** to filter traffic that is returning to the services interface after the input service set **in\_filter\_presvc** is executed. The **in\_filter\_postsvc** service filter counts packets sent from ICMP port 179 and then discards them.
- Filtering IPv4 traffic before it is accepted for output service processing—At logical interface **xe-0/1/0.0**, you use the service-filter **out\_filter\_presvc** to filter IPv4 output traffic before the traffic can be accepted for processing by the services associated with service set **vrf\_svcs**. The **out\_filter\_presvc** service filter counts packets destined for TCP port 179 and then directs the packets to the output services associated with the service set **vrf\_svcs**.

## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configuring the Three Service Filters on page 235](#)
- [Applying the Three Service Filters on page 236](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet service-filter in_filter_presvc term t1 from protocol tcp
set firewall family inet service-filter in_filter_presvc term t1 from source-port bgp
set firewall family inet service-filter in_filter_presvc term t1 then count svc_in_pkts
set firewall family inet service-filter in_filter_postsvc term t2 from protocol tcp
set firewall family inet service-filter in_filter_postsvc term t2 from source-port bgp
set firewall family inet service-filter in_filter_postsvc term t2 then count svc_in_pkts_rtn
set firewall family inet service-filter in_filter_postsvc term t2 then skip
set firewall family inet service-filter out_filter_presvc term t3 from protocol icmp
set firewall family inet service-filter out_filter_presvc term t3 from destination-port bgp
set firewall family inet service-filter out_filter_presvc term t3 then count svc_out_pkts
set firewall family inet service-filter out_filter_presvc term t3 then service
```



```

set interfaces xe-0/1/0 unit 0 family inet service input service-set vrf_svcs service-filter
in_filter_presvc
set interfaces xe-0/1/0 unit 0 family inet service input post-service-filter in_filter_postsvc
set interfaces xe-0/1/0 unit 0 family inet service output service-set vrf_svcs service-filter
out_filter_presvc

```

### Configuring the Three Service Filters

#### Step-by-Step Procedure

To configure the three service filters:

1. Configure the input service filter.

```

[edit]
user@host# edit firewall family inet service-filter in_filter_presvc

```

```

[edit firewall family inet service-filter in_filter_presvc]
user@host# set term t1 from protocol tcp
user@host# set term t1 from source-port bgp
user@host# set term t1 then count svc_in_pkts
user@host# set term t1 then service

```

2. Configure the postservice input filter.

```

[edit]
user@host# edit firewall family inet service-filter in_filter_postsvc

```

```

[edit firewall family inet service-filter in_filter_postsvc]
user@host# set term t2 from protocol tcp
user@host# set term t2 from source-port bgp
user@host# set term t2 then count svc_in_pkts_rtn
user@host# set term t2 then skip

```

3. Configure the output service filter.

```

[edit]
user@host# edit firewall family inet service-filter out_filter_presvc

```

```

[edit firewall family inet service-filter out_filter_presvc]
user@host# set term t3 from protocol icmp
user@host# set term t3 from destination-port bgp
user@host# set term t3 then count svc_out_pkts
user@host# set term t3 then service

```

**Results** Confirm the configuration of the input and output service filters and the postservice input filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this procedure to correct the configuration.

```

[edit]
user@host# show firewall
family inet {
  service-filter in_filter_presvc {
    term t1 {
      from {
        protocol tcp;
        source-port bgp;

```



```

    }
    then {
        count svc_in_pkts;
        service;
    }
}
}
service-filter in_filter_postsvc {
    term t2 {
        from {
            protocol tcp;
            source-port bgp;
        }
        then {
            count svc_in_pkts_rtn;
            skip;
        }
    }
}
service-filter out_filter_presvc {
    term t3 {
        from {
            protocol icmp;
            destination-port bgp;
        }
        then {
            count svc_out_pkts;
            service;
        }
    }
}
}
}

```

### Applying the Three Service Filters

#### Step-by-Step Procedure

To apply the three service filters:

1. Access the IPv4 protocol on the input interface **xe-0/1/0.0**.

[edit]

user@host# **edit interfaces xe-0/1/0 unit 0 family inet**

2. Apply the input service filter and the postservice input filter.

[edit interfaces xe-0/1/0 unit 0 family inet]

user@host# **set service input service-set vrf\_svcs service-filter in\_filter\_presvc**

user@host# **set service input post-service-filter in\_filter\_postsvc**

user@host# **set service output service-set vrf\_svcs service-filter out\_filter\_presvc**

#### Results

Confirm the configuration of the interfaces by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

[edit]

user@host# **show interfaces**

xe-0/1/0 {



```

unit 0 {
  family inet {
    service {
      input {
        service-set vrf_svcs service-filter in_filter_presvc;
        post-service-filter in_filter_postsvc;
      }
      output {
        service-set vrf_svcs service-filter out_filter_presvc;
      }
    }
  }
}

```

When you are done configuring the device, commit your candidate configuration.

## Verification

Confirm that the configuration is working properly.

- [Verifying That Inbound Traffic Is Filtered Before Input Service on page 237](#)
- [Verifying That Inbound Traffic Is Filtered After Input Service Processing on page 237](#)
- [Verifying That Outbound Traffic Is Filtered Before Output Service Processing on page 237](#)

### Verifying That Inbound Traffic Is Filtered Before Input Service

**Purpose** Verify that inbound packets sent from TCP port 179 are sent for processing by the *input* services associated with the service set **vrf\_svcs**.

**Action** Display the count of packets sent for processing by the *input* services associated with the service set **vrf\_svcs**.

```

[edit]
user@host> show firewall filter in_filter_presvc-vrf_svcs counter svc_in_pkts

```

### Verifying That Inbound Traffic Is Filtered After Input Service Processing

**Purpose** Verify that inbound packets sent from TCP port 179 are returned from processing by the *input* services associated with the service set **vrf\_svcs**.

**Action** Display the count of packets returned from processing by the *input* services associated with the service set **vrf\_svcs**.

```

[edit]
user@host> show firewall filter in_filter_postsvc-vrf_svcs counter svc_in_pkts_rtn

```

### Verifying That Outbound Traffic Is Filtered Before Output Service Processing

**Purpose** Verify that outbound packets sent to ICMP port 179 are sent for processing by the *output* services associated with the service set **vrf\_svcs**.



**Action** Display the count of packets sent for processing by the *output* services associated with the service set **vrf\_svcs**.

[edit]

user@host> **show firewall filter out\_filter\_presvc-vrf\_svcs counter svc\_out\_pkts**

**Related  
Documentation**

- [Service Filter Overview on page 65](#)
- [How Service Filters Evaluate Packets on page 67](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Guidelines for Applying Service Filters on page 70](#)



## CHAPTER 19

# Simple Filters Configuration

- [Example: Configuring and Applying a Simple Filter on page 239](#)

### Example: Configuring and Applying a Simple Filter

---

This example shows how to configure a simple filter.

- [Requirements on page 239](#)
- [Overview on page 239](#)
- [Configuration on page 240](#)
- [Verification on page 242](#)

### Requirements

This example uses one of the following hardware components:

- One Gigabit Ethernet intelligent queuing (IQ2) PIC installed on an M120, M320, or T Series router
- One Enhanced Queuing Dense Port Concentrator (EQ DPC) installed on an MX Series router

Before you begin, make sure that you have:

- Installed your supported router and PIC or DPC and performed the initial router configuration.
- Configured basic Ethernet in the topology, and verified that traffic is flowing in the topology and that ingress IPv4 traffic is flowing into logical interface **ge-0/0/1.0**.

### Overview

This simple filter sets the loss priority to low for TCP traffic with source address **1.1.1.1**, sets the loss priority to high for HTTP (Web) traffic with source addresses in the **4.0.0.0/8** range, and sets the loss priority to low for all traffic with destination address **6.6.6.6**.

### Topology

---

The simple filter is applied as an input filter (arriving packets are checking for destination address **6.6.6.6**, not queued output packets) on interface **ge-0/0/1.0**.



## Configuration

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#).

To configure this example, perform the following tasks:

- [Configuring the Simple Firewall Filter on page 240](#)
- [Applying the Simple Filter to the Logical Interface Input on page 242](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands into a text file, remove any line breaks, and then paste the commands into the CLI at the **[edit]** hierarchy level.

```
set firewall family inet simple-filter sf_classify_1 term 1 from source-address 1.1.1.1/32
set firewall family inet simple-filter sf_classify_1 term 1 from protocol tcp
set firewall family inet simple-filter sf_classify_1 term 1 then loss-priority low
set firewall family inet simple-filter sf_classify_1 term 2 from source-address 4.0.0.0/8
set firewall family inet simple-filter sf_classify_1 term 2 from protocol tcp
set firewall family inet simple-filter sf_classify_1 term 2 from source-port http
set firewall family inet simple-filter sf_classify_1 term 2 then loss-priority high
set firewall family inet simple-filter sf_classify_1 term 3 from destination-address
6.6.6.6/32
set firewall family inet simple-filter sf_classify_1 term 3 then loss-priority low
set firewall family inet simple-filter sf_classify_1 term 3 then forwarding-class best-effort
set interfaces ge-0/0/1 unit 0 family inet simple-filter input sf_classify_1
set interfaces ge-0/0/1 unit 0 family inet address 10.1.2.3/30
```

---

### Configuring the Simple Firewall Filter

### Step-by-Step Procedure

To configure the simple filter:

1. Create the simple filter **sf\_classify\_1**.  

```
[edit]
user@host# edit firewall family inet simple-filter sf_classify_1
```
2. Configure classification of TCP traffic based on the source IP address.  

```
[edit firewall family inet simple-filter sf_classify_1]
user@host# set term 1 from source-address 1.1.1.1/32
user@host# set term 1 from protocol tcp
user@host# set term 1 then loss-priority low
```
3. Configure classification of HTTP traffic based on the source IP address.  

```
[edit firewall family inet simple-filter sf_classify_1]
user@host# set term 2 from source-address 4.0.0.0/8
user@host# set term 2 from protocol tcp
user@host# set term 2 from source-port http
user@host# set term 2 then loss-priority high
```
4. Configure classification of other traffic based on the destination IP address.  

```
[edit firewall family inet simple-filter sf_classify_1]
user@host# set term 3 from destination-address 6.6.6.6/32
```



```

user@host# set term 3 then loss-priority low
user@host# set term 3 then forwarding-class best-effort

```

**Results** Confirm the configuration of the simple filter by entering the **show firewall** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@host# show firewall
family inet {
  simple-filter sf_classify_1 {
    term 1 {
      from {
        source-address {
          1.1.1.1/32;
        }
        protocol {
          tcp;
        }
      }
      then loss-priority low;
    }
    term 2 {
      from {
        source-address {
          4.0.0.0/8;
        }
        source-port {
          http;
        }
        protocol {
          tcp;
        }
      }
      then loss-priority high;
    }
    term 3 {
      from {
        destination-address {
          6.6.6.6/32;
        }
      }
      then {
        loss-priority low;
        forwarding-class best-effort;
      }
    }
  }
}

```



### Applying the Simple Filter to the Logical Interface Input

#### Step-by-Step Procedure

To apply the simple filter to the logical interface input:

1. Configure the logical interface to which you will apply the simple filter.

```
[edit]
user@host# edit interfaces ge-0/0/1 unit 0 family inet
```

2. Configure the interface address for the logical interface.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set address 10.1.2.3/30
```

3. Apply the simple filter to the logical interface input.

```
[edit interfaces ge-0/0/1 unit 0 family inet]
user@host# set simple-filter input sf_classify_1
```

#### Results

Confirm the configuration of the interface by entering the **show interfaces** configuration mode command. If the command output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@host# show interfaces
ge-0/0/1 {
  unit 0 {
    family inet {
      simple-filter {
        input sf_classify_1;
      }
      address 10.1.2.3/30;
    }
  }
}
```

When you are done configuring the device, commit your candidate configuration.

### Verification

Confirm that the configuration is working properly.

- [Displaying the Mapping of Forwarding Class Maps and Names to Queue Numbers on page 242](#)
- [Displaying CoS Queue Counters for the Interface on page 243](#)
- [Displaying CoS Queue Counter Details for the Physical Interface on page 243](#)

### Displaying the Mapping of Forwarding Class Maps and Names to Queue Numbers

#### Purpose

Display the mapping of forwarding class names to queue numbers.

#### Action

Enter the **show class-of-service forwarding-class** operational mode command.

```
[edit]
user@host> show class-of-service forwarding-class
```



For information about the command output, see “**show class-of-service forwarding-class**” in the Junos OS Operational Mode Commands.

### Displaying CoS Queue Counters for the Interface

**Purpose** Verify that the class-of-service (CoS) queue counters for the interface reflect the simple filter applied to the logical interface.

**Action** Enter the **show interfaces** command for the physical interface on which the simple filter is applied, and specify **detail** or **extensive** output level.

[edit]

```
user@host> show interfaces ge-0/0/1 detail
```

In the **Physical interface** section, under **Ingress queues**, the **Queue counters** section displays ingress queue counters for each forwarding class.

For more detailed information about the command output, see “**show interfaces (Gigabit Ethernet)**” or “**show interfaces (10-Gigabit Ethernet)**” in the Junos OS Operational Mode Commands.

### Displaying CoS Queue Counter Details for the Physical Interface

**Purpose** Verify that the CoS queue counter details for the physical interface reflect the simple filter applied to the logical interface.

**Action** Enter the **show interfaces queue** command for the physical interface on which the simple filter is applied, and specify the **ingress** option.

[edit]

```
user@host> show interfaces queue ge-0/0/1 ingress
```

For information about the command output, see “**show interfaces queue**” in the Junos OS Operational Mode Commands.

- Related Documentation**
- [Simple Filter Overview on page 75](#)
  - [How Simple Filters Evaluate Packets on page 75](#)
  - [Guidelines for Configuring Simple Filters on page 77](#)
  - [Guidelines for Applying Simple Filters on page 80](#)







## CHAPTER 20

# Firewall Filters Configuration in Logical Systems

- [Example: Configuring a Stateless Firewall Filter to Protect a Logical System Against ICMP Floods on page 245](#)

## Example: Configuring a Stateless Firewall Filter to Protect a Logical System Against ICMP Floods

---

This example shows how to configure a stateless firewall filter that protects against ICMP denial-of-service attacks on a logical system.

- [Requirements on page 245](#)
- [Overview on page 245](#)
- [Configuration on page 246](#)
- [Verification on page 248](#)

### Requirements

In this example, no special configuration beyond device initialization is required.

### Overview

This example shows a stateless firewall filter called `protect-RE` that polices ICMP packets. The **icmp-policer** limits the traffic rate of the ICMP packets to 1,000,000 bps and the burst size to 15,000 bytes. Packets that exceed the traffic rate are discarded.


The policer is incorporated into the action of a filter term called **icmp-term**.

In this example, a ping is sent from a directly connected physical router to the interface configured on the logical system. The logical system accepts the ICMP packets if they are received at a rate of up to 1 Mbps (`bandwidth-limit`). The logical system drops all ICMP packets when this rate is exceeded. The **burst-size-limit** statement accepts traffic bursts up to 15 Kbps. If bursts exceed this limit, all packets are dropped. When the flow rate subsides, ICMP packets are again accepted.

[Figure 5 on page 246](#) shows the topology used in this example.



Figure 5: Logical System with a Stateless Firewall



## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set logical-systems LS1 interfaces so-0/0/2 unit 0 family inet policer input icmp-policer
set logical-systems LS1 interfaces so-0/0/2 unit 0 family inet address 10.0.45.2/30
set logical-systems LS1 firewall family inet filter protect-RE term icmp-term from protocol icmp
set logical-systems LS1 firewall family inet filter protect-RE term icmp-term then policer icmp-policer
set logical-systems LS1 firewall family inet filter protect-RE term icmp-term then accept
set logical-systems LS1 firewall policer icmp-policer if-exceeding bandwidth-limit 1m
set logical-systems LS1 firewall policer icmp-policer if-exceeding burst-size-limit 15k
set logical-systems LS1 firewall policer icmp-policer then discard
```

### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see [“Using the CLI Editor in Configuration Mode” on page 253](#) in the CLI User Guide.

To configure an ICMP firewall filter on a logical system:

1. Configure the interface on the logical system.

```
[edit]
user@host# set logical-systems LS1 interfaces so-0/0/2 unit 0 family inet address 10.0.45.2/30
```

2. Explicitly enable ICMP packets to be received on the interface.

```
[edit]
user@host# set logical-systems LS1 firewall family inet filter protect-RE term icmp-term from protocol icmp
user@host# set logical-systems LS1 firewall family inet filter protect-RE term icmp-term then accept
```



3. Create the policer.

```
[edit]
user@host# set logical-systems LS1 firewall policer icmp-policer if-exceeding
bandwidth-limit 1m
user@host# set logical-systems LS1 firewall policer icmp-policer if-exceeding
burst-size-limit 15k
user@host# set logical-systems LS1 firewall policer icmp-policer then discard
```

4. Apply the policer to a filter term.

```
[edit]
user@host# set logical-systems LS1 firewall family inet filter protect-RE term
icmp-term then policer icmp-policer
```

5. Apply the policer to the logical system interface.

```
[edit]
user@host# set logical-systems LS1 interfaces so-0/0/2 unit 0 family inet policer
input icmp-policer
```

6. If you are done configuring the device, commit the configuration.

```
[edit]
user@host# commit
```

Confirm your configuration by issuing the **show logical-systems LS1** command.

```
user@host# show logical-systems LS1
interfaces {
  so-0/0/2 {
    unit 0 {
      family inet {
        policer {
          input icmp-policer;
        }
        address 10.0.45.2/30;
      }
    }
  }
}
firewall {
  family inet {
    filter protect-RE {
      term icmp-term {
        from {
          protocol icmp;
        }
        then {
          policer icmp-policer;
          accept;
        }
      }
    }
  }
}
policer icmp-policer {
  if-exceeding {
```



```
        bandwidth-limit 1m;  
        burst-size-limit 15k;  
    }  
    then discard;  
}  
}
```

## Verification

Confirm that the configuration is working properly.

### Verifying That Ping Works Unless the Limits Are Exceeded

**Purpose** Make sure that the logical system interface is protected against ICMP-based DoS attacks.

**Action** Log in to a system that has connectivity to the logical system and run the **ping** command.

```
user@R2> ping 10.0.45.2  
PING 10.0.45.2 (10.0.45.2): 56 data bytes  
64 bytes from 10.0.45.2: icmp_seq=0 ttl=64 time=1.316 ms  
64 bytes from 10.0.45.2: icmp_seq=1 ttl=64 time=1.277 ms  
64 bytes from 10.0.45.2: icmp_seq=2 ttl=64 time=1.269 ms  
  
user@R2> ping 10.0.45.2 size 20000  
PING 10.0.45.2 (10.0.45.2): 20000 data bytes  
^C  
--- 10.0.45.2 ping statistics ---  
4 packets transmitted, 0 packets received, 100% packet loss
```

**Meaning** When you send a normal ping, the packet is accepted. When you send a ping packet that exceeds the filter limit, the packet is discarded.

**Related Documentation**

- Example: Creating an Interface on a Logical System



## PART 3

# Administration

- [Firewall Filters Standards on page 251](#)
- [Firewall Filters Reference on page 253](#)
- [Standard Firewall Filter Match Conditions and Actions on page 257](#)
- [Standard Firewall Filter Match Conditions and Actions for ACX Series Routers on page 301](#)
- [Service Filter Match Conditions and Actions on page 311](#)
- [Reference Information for Firewall Filters in Logical Systems on page 319](#)
- [Firewall Filters Statement Hierarchies on page 325](#)
- [Summary of Firewall Filters Configuration Statements on page 339](#)







# Firewall Filters Standards

- [Supported Standards for Filtering on page 251](#)

## Supported Standards for Filtering

---

The Junos OS supports the following RFCs related to filtering:

- RFC 792, *Internet Control Message Protocol*
- RFC 2460, *Internet Protocol, Version 6 (IPv6)*
- RFC 2474, *Definition of the Differentiated Services (DS) Field*
- RFC 2475, *An Architecture for Differentiated Services*
- RFC 2597, *Assured Forwarding PHB Group*
- RFC 3246, *An Expedited Forwarding PHB (Per-Hop Behavior)*
- RFC 4291, *IP Version 6 Addressing Architecture*
- RFC 4443, *Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification*

### Related Documentation

- [Standard Stateless Firewall Filter Overview on page 17](#)
- [Service Filter Overview on page 65](#)
- [Simple Filter Overview on page 75](#)
- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)







## CHAPTER 22

# Firewall Filters Reference

- [Using the CLI Editor in Configuration Mode on page 253](#)

## Using the CLI Editor in Configuration Mode

This topic describes some of the basic commands that you must use to enter configuration mode in the command-line interface (CLI) editor, navigate through the configuration hierarchy, get help, and commit or revert the changes that you make during the configuration session.

Task	Command/Statement	Example
<b>Edit Your Configuration</b>		
Enter configuration mode.  When you first log in to the device, the device is in operational mode. You must explicitly enter configuration mode. When you do, the CLI prompt changes from <b>user@host&gt;</b> to <b>user@host#</b> and the hierarchy level appears in square brackets.	<b>configure</b>	<b>user@host&gt; configure</b>  [edit] user@host#
Create a statement hierarchy.  You can use the <b>edit</b> command to simultaneously create a hierarchy and move to that new level in the hierarchy. You cannot use the <b>edit</b> command to change the value of identifiers.	<b>edit <i>hierarchy-level value</i></b>	[edit] user@host# <b>edit security zones</b> <b>security-zone myzone</b>  [edit security zones security-zone myzone] user@host#
Create a statement hierarchy and set identifier values.  The <b>set</b> command is similar to <b>edit</b> except that your current level in the hierarchy does not change.	<b>set <i>hierarchy-level value</i></b>	[edit] user@host# <b>set security zones</b> <b>security-zone myzone</b>  [edit] user@host#
<b>Navigate the Hierarchy</b>		



Task	Command/Statement	Example
Navigate down to an existing hierarchy level.	<code>edit <i>hierarchy-level</i></code>	[edit] user@host# <code>edit security zones</code>  [edit security zones] user@host#
Navigate up one level in the hierarchy.	<code>up</code>	[edit security zones] user@host# <code>up</code>  [edit security] user@host#
Navigate to the top of the hierarchy.	<code>top</code>	[edit security zones] user@host# <code>top</code>  [edit] user@host#
<b>Commit or Revert Changes</b>		
Commit your configuration.	<code>commit</code>	[edit] user@host# <code>commit</code>  commit complete
Roll back changes from the current session.  Use the <b>rollback</b> command to revert all changes from the current configuration session. When you run the <b>rollback</b> command before exiting your session or committing changes, the software loads the most recently committed configuration onto the device. You must enter the <b>rollback</b> statement at the <b>edit</b> level in the hierarchy.	<code>rollback</code>	[edit] user@host# <code>rollback</code>  load complete
<b>Exit Configuration Mode</b>		
Commit the configuration and exit configuration mode.	<code>commit and-quit</code>	[edit] user@host# <code>commit and-quit</code>  user@host>
Exit configuration mode without committing your configuration.  You must navigate to the top of the hierarchy using the <b>up</b> or <b>top</b> commands before you can exit configuration mode.	<code>exit</code>	[edit] user@host# <code>exit</code>  The configuration has been changed but not committed Exit with uncommitted changes? [yes,no] (yes)
<b>Get Help</b>		



Task	Command/Statement	Example
Display a list of valid options for the current hierarchy level.	?	<pre>[edit ] user@host# edit security zones ?  Possible completions: &lt;[Enter]&gt; Execute this command &gt; functional-zone Functional zone &gt; security-zone Security zones   Pipe through a command [edit]</pre>

**Related  
Documentation**

- Understanding Junos OS CLI Configuration Mode
- Entering and Exiting the Junos OS CLI Configuration Mode
- Displaying the Current Junos OS Configuration







# Standard Firewall Filter Match Conditions and Actions

- Standard Firewall Filter Match Conditions for Protocol-Independent Traffic on page 257
- Standard Firewall Filter Match Conditions for IPv4 Traffic on page 258
- Standard Firewall Filter Match Conditions for IPv6 Traffic on page 267
- Standard Firewall Filter Match Conditions for MPLS Traffic on page 274
- Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276
- Standard Firewall Filter Match Conditions for VPLS Traffic on page 278
- Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic on page 285
- Standard Firewall Filter Match Conditions for Layer 2 Bridging Traffic on page 287
- Standard Firewall Filter Terminating Actions on page 293
- Standard Firewall Filter Nonterminating Actions on page 294

## Standard Firewall Filter Match Conditions for Protocol-Independent Traffic

---

You can configure a standard stateless firewall filter with match conditions for protocol-independent traffic (**family any**).



**NOTE:** Protocol-independent standard firewall filters—firewall filters configured at the [edit firewall family any] hierarchy level— are not supported on the router loopback interface (lo0).

Table 14 on page 258 describes the *match-conditions* you can configure at the [edit firewall family any filter *filter-name* term *term-name* from] hierarchy level.



Table 14: Standard Firewall Filter Match Conditions for Protocol-Independent Traffic

Match Condition	Description
<b>forwarding-class</b> <i>class</i>	<p>Match the forwarding class of the packet.</p> <p>Specify <b>assured-forwarding</b>, <b>best-effort</b>, <b>expedited-forwarding</b>, or <b>network-control</b>.</p> <p>For information about forwarding classes and router-internal output queues, see the Junos OS Class of Service Configuration Guide.</p> <p><b>NOTE:</b> On T4000 Type 5 FPCs, a filter attached at the Layer 2 application point (that is, at the logical interface level) is unable to match with the forwarding class of a packet that is set by a Layer 3 classifier such as DSCP, DSCP V6, <b>inet-precedence</b>, and <b>mpls-exp</b>.</p>
<b>forwarding-class-except</b> <i>class</i>	Do not match on the forwarding class. For details, see the <b>forwarding-class</b> match condition.
<b>interface</b> <i>interface-name</i>	<p>Match the interface on which the packet was received.</p> <p><b>NOTE:</b> If you configure this match condition with an interface that does not exist, the term does not match any packet.</p>
<b>interface-set</b> <i>interface-set-name</i>	<p>Match the interface on which the packet was received to the specified interface set.</p> <p>To define an interface set, include the <b>interface-set</b> statement at the <b>[edit firewall]</b> hierarchy level. For more information, see “<a href="#">Filtering Packets Received on an Interface Set Overview</a>” on page 58.</p>
<b>packet-length</b> <i>bytes</i>	Match the length of the received packet, in bytes. The length refers only to the IP packet, including the packet header, and does not include any Layer 2 encapsulation overhead.
<b>packet-length-except</b> <i>bytes</i>	Do not match on the received packet length, in bytes. For details, see the <b>packet-length</b> match type.

#### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Terminating Actions on page 293](#)
- [Standard Firewall Filter Nonterminating Actions on page 294](#)

## Standard Firewall Filter Match Conditions for IPv4 Traffic

You can configure a standard stateless firewall filter with match conditions for Internet Protocol version 4 (IPv4) traffic (**family inet**). [Table 15 on page 258](#) describes the **match-conditions** you can configure at the **[edit firewall family inet filter filter-name term term-name from]** hierarchy level.

Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic

Match Condition	Description
<b>address</b> <i>address</i> [ <b>except</b> ]	Match the IPv4 source or destination address field unless the <b>except</b> option is included. If the option is included, do not match the IPv4 source or destination address field.



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>ah-spi</b> <i>spi-value</i>	(M Series routers, except M120 and M320) Match the IPsec authentication header (AH) security parameter index (SPI) value.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>ah-spi-except</b> <i>spi-value</i>	(M Series routers, except M120 and M320) Do not match the IPsec AH SPI value.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>apply-groups</b>	Specify which groups to inherit configuration data from. You can specify more than one group name. You must list them in order of inheritance priority. The configuration data in the first group takes priority over the data in subsequent groups.
<b>apply-groups-except</b>	Specify which groups not to inherit configuration data from. You can specify more than one group name.
<b>destination-address</b> <i>address</i> [ <b>except</b> ]	Match the IPv4 destination address field unless the <b>except</b> option is included. If the option is included, do not match the IPv4 destination address field..  You cannot specify both the <b>address</b> and <b>destination-address</b> match conditions in the same term.
<b>destination-class</b> <i>class-names</i>	Match one or more specified destination class names (sets of destination prefixes grouped together and given a class name). For more information, see <a href="#">“Firewall Filter Match Conditions Based on Address Classes” on page 43</a> .  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>destination-class-except</b> <i>class-names</i>	Do not match one or more specified destination class names. For details, see the <b>destination-class</b> match condition.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>destination-port</b> <i>number</i>	Match the UDP or TCP destination port field.  You cannot specify both the <b>port</b> and <b>destination-port</b> match conditions in the same term.  If you configure this match condition, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.  In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>ldp</b> (646), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobilip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rkinit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs</b> (49), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xmcp</b> (177).
<b>destination-port-except</b> <i>number</i>	Do not match the UDP or TCP destination port field. For details, see the <b>destination-port</b> match condition.



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>destination-prefix-list</b> <i>name</i> [ <b>except</b> ]	<p>Match destination prefixes in the specified list unless the <b>except</b> option is included. If the option is included, do not match the destination prefixes in the specified list.</p> <p>Specify the name of a prefix list defined at the [edit policy-options prefix-list <i>prefix-list-name</i>] hierarchy level.</p>
<b>dscp</b> <i>number</i>	<p>Match the Differentiated Services code point (DSCP). The DiffServ protocol uses the type-of-service (ToS) byte in the IP header. The most significant 6 bits of this byte form the DSCP. For more information, see the Junos OS Class of Service Configuration Guide.</p> <p>You can specify a numeric value from <b>0</b> through <b>63</b>. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> <li>• RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: <b>ef</b> (46).</li> <li>• RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points: <ul style="list-style-type: none"> <li>• <b>af11</b> (10), <b>af12</b> (12), <b>af13</b> (14)</li> <li>• <b>af21</b> (18), <b>af22</b> (20), <b>af23</b> (22)</li> <li>• <b>af31</b> (26), <b>af32</b> (28), <b>af33</b> (30)</li> <li>• <b>af41</b> (34), <b>af42</b> (36), <b>af43</b> (38)</li> </ul> </li> </ul>
<b>dscp-except</b> <i>number</i>	Do not match on the DSCP number. For more information, see the <b>dscp</b> match condition.
<b>esp-spi</b> <i>spi-value</i>	<p>Match the IPsec encapsulating security payload (ESP) SPI value. Match on this specific SPI value. You can specify the ESP SPI value in hexadecimal, binary, or decimal form.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>esp-spi-except</b> <i>spi-value</i>	<p>Match the IPsec ESP SPI value. Do not match on this specific SPI value.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>first-fragment</b>	<p>Match if the packet is the first fragment of a fragmented packet. Do not match if the packet is a trailing fragment of a fragmented packet. The first fragment of a fragmented packet has a fragment offset value of <b>0</b>.</p> <p>This match condition is an alias for the bit-field match condition <b>fragment-offset 0</b> match condition.</p> <p>To match both first and trailing fragments, you can use two terms that specify different match conditions: <b>first-fragment</b> and <b>is-fragment</b>.</p>
<b>forwarding-class</b> <i>class</i>	<p>Match the forwarding class of the packet.</p> <p>Specify <b>assured-forwarding</b>, <b>best-effort</b>, <b>expedited-forwarding</b>, or <b>network-control</b>.</p> <p>For information about forwarding classes and router-internal output queues, see the Junos OS Class of Service Configuration Guide.</p>
<b>forwarding-class-except</b> <i>class</i>	Do not match the forwarding class of the packet. For details, see the <b>forwarding-class</b> match condition.



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>fragment-flags</b> <i>number</i>	<p>(Ingress only) Match the three-bit IP fragmentation flags field in the IP header.</p> <p>In place of the numeric field value, you can specify one of the following keywords (the field values are also listed): <b>dont-fragment</b> (0x4), <b>more-fragments</b> (0x2), or <b>reserved</b> (0x8).</p>
<b>fragment-offset</b> <i>value</i>	<p>Match the 13-bit fragment offset field in the IP header. The value is the offset, in 8-byte units, in the overall datagram message to the data fragment. Specify a numeric value, a range of values, or a set of values. An offset value of 0 indicates the first fragment of a fragmented packet.</p> <p>The <b>first-fragment</b> match condition is an alias for the <b>fragment-offset 0</b> match condition.</p> <p>To match both first and trailing fragments, you can use two terms that specify different match conditions (<b>first-fragment</b> and <b>is-fragment</b>).</p>
<b>fragment-offset-except</b> <i>number</i>	Do not match the 13-bit fragment offset field.
<b>icmp-code</b> <i>number</i>	<p>Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol icmp</b> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <b>icmp-type message-type</b> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> <li>parameter-problem: <b>ip-header-bad</b> (0), <b>required-option-missing</b> (1)</li> <li>redirect: <b>redirect-for-host</b> (1), <b>redirect-for-network</b> (0), <b>redirect-for-tos-and-host</b> (3), <b>redirect-for-tos-and-net</b> (2)</li> <li>time-exceeded: <b>ttl-eq-zero-during-reassembly</b> (1), <b>ttl-eq-zero-during-transit</b> (0)</li> <li>unreachable: <b>communication-prohibited-by-filtering</b> (13), <b>destination-host-prohibited</b> (10), <b>destination-host-unknown</b> (7), <b>destination-network-prohibited</b> (9), <b>destination-network-unknown</b> (6), <b>fragmentation-needed</b> (4), <b>host-precedence-violation</b> (14), <b>host-unreachable</b> (1), <b>host-unreachable-for-TOS</b> (12), <b>network-unreachable</b> (0), <b>network-unreachable-for-TOS</b> (11), <b>port-unreachable</b> (3), <b>precedence-cutoff-in-effect</b> (15), <b>protocol-unreachable</b> (2), <b>source-host-isolated</b> (8), <b>source-route-failed</b> (5)</li> </ul>
<b>icmp-code-except</b> <i>message-code</i>	Do not match the ICMP message code field. For details, see the <b>icmp-code</b> match condition.
<b>icmp-type</b> <i>number</i>	<p>Match the ICMP message type field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol icmp</b> match condition in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>echo-reply</b> (0), <b>echo-request</b> (8), <b>info-reply</b> (16), <b>info-request</b> (15), <b>mask-request</b> (17), <b>mask-reply</b> (18), <b>parameter-problem</b> (12), <b>redirect</b> (5), <b>router-advertisement</b> (9), <b>router-solicit</b> (10), <b>source-quench</b> (4), <b>time-exceeded</b> (11), <b>timestamp</b> (13), <b>timestamp-reply</b> (14), or <b>unreachable</b> (3).</p>



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>icmp-type-except</b> <i>message-type</i>	Do not match the ICMP message type field. For details, see the <b>icmp-type</b> match condition.
<b>interface</b> <i>interface-name</i>	<p>Match the interface on which the packet was received.</p> <p><b>NOTE:</b> If you configure this match condition with an interface that does not exist, the term does not match any packet.</p>
<b>interface-group</b> <i>group-number</i>	<p>Match the logical interface on which the packet was received to the specified interface group or set of interface groups. For <i>group-number</i>, specify a single value or a range of values from 0 through 255.</p> <p>To assign a logical interface to an interface group <i>group-number</i>, specify the <i>group-number</i> at the [interfaces <i>interface-name</i> unit <i>number</i> family <i>family</i> filter group] hierarchy level.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see “Filtering Packets Received on a Set of Interface Groups Overview” on page 57.</p>
<b>interface-group-except</b> <i>group-number</i>	<p>Do not match the logical interface on which the packet was received to the specified interface group or set of interface groups. For details, see the <b>interface-group</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>interface-set</b> <i>interface-set-name</i>	<p>Match the interface on which the packet was received to the specified interface set.</p> <p>To define an interface set, include the <b>interface-set</b> statement at the [edit firewall] hierarchy level.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see “Filtering Packets Received on an Interface Set Overview” on page 58.</p>



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>ip-options values</b>	<p>Match the 8-bit IP option field, if present, to the specified value or list of values.</p> <p>In place of a numeric value, you can specify one of the following text synonyms (the option values are also listed): <b>loose-source-route</b> (131), <b>record-route</b> (7), <b>router-alert</b> (148), <b>security</b> (130), <b>stream-id</b> (136), <b>strict-source-route</b> (137), or <b>timestamp</b> (68).</p> <p>To match <i>any</i> value for the IP option, use the text synonym <b>any</b>. To match on <i>multiple</i> values, specify the list of values within square brackets ('[' and ']'). To match a <i>range</i> of values, use the value specification [ <i>value1</i>-<i>value2</i> ].</p> <p>For example, the match condition <b>ip-options [ 0-147 ]</b> matches on an IP options field that contains the <b>loose-source-route</b>, <b>record-route</b>, or <b>security</b> values, or any other value from 0 through 147. However, this match condition does not match on an IP options field that contains only the <b>router-alert</b> value (148).</p> <p>For most interfaces, a filter term that specifies an <b>ip-option</b> match on one or more <i>specific</i> IP option values (a value other than <b>any</b>) causes packets to be sent to the Routing Engine so that the kernel can parse the IP option field in the packet header.</p> <ul style="list-style-type: none"> <li>For a firewall filter term that specifies an <b>ip-option</b> match on one or more specific IP option values, you cannot specify the <b>count</b>, <b>log</b>, or <b>syslog</b> nonterminating actions <i>unless</i> you also specify the <b>discard</b> terminating action in the same term. This behavior prevents double-counting of packets for a filter applied to a transit interface on the router.</li> <li>Packets processed on the kernel might be dropped in case of a system bottleneck. To ensure that matched packets are instead sent to the Packet Forwarding Engine (where packet processing is implemented in hardware), use the <b>ip-options any</b> match condition.</li> </ul> <p>The 10-Gigabit Ethernet Modular Port Concentrator (MPC), 100-Gigabit Ethernet MPC, 60-Gigabit Ethernet MPC, 60-Gigabit Queuing Ethernet MPC, and 60-Gigabit Ethernet Enhanced Queuing MPC on MX Series routers are capable of parsing the IP option field of the IPv4 packet header. For interfaces configured on those MPCs, <i>all</i> packets that are matched using the <b>ip-options</b> match condition are sent to the Packet Forwarding Engine for processing.</p>
<b>ip-options-except values</b>	<p>Do not match the IP option field to the specified value or list of values. For details about specifying the <i>values</i>, see the <b>ip-options</b> match condition.</p>
<b>is-fragment</b>	<p>Match if the packet is a trailing fragment of a fragmented packet. Do not match the first fragment of a fragmented packet.</p> <p><b>NOTE:</b> To match both first and trailing fragments, you can use two terms that specify different match conditions (<b>first-fragment</b> and <b>is-fragment</b>).</p>



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>loss-priority level</b>	<p>Match the packet loss priority (PLP) level.</p> <p>Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>loss-priority-except level</b>	<p>Do not match the PLP level. For details, see the <b>loss-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>packet-length bytes</b>	<p>Match the length of the received packet, in bytes. The length refers only to the IP packet, including the packet header, and does not include any Layer 2 encapsulation overhead.</p>
<b>packet-length-except bytes</b>	<p>Do not match the length of the received packet, in bytes. For details, see the <b>packet-length</b> match type.</p>
<b>port number</b>	<p>Match the UDP or TCP source or destination port field.</p> <p>If you configure this match condition, you cannot configure the <b>destination-port</b> match condition or the <b>source-port</b> match condition in the same term.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed under <b>destination-port</b>.</p>
<b>port-except number</b>	<p>Do not match the UDP or TCP source or destination port field. For details, see the <b>port</b> match condition.</p>
<b>precedence</b> <b>ip-precedence-value</b>	<p>Match the IP precedence field.</p> <p>In place of the numeric field value, you can specify one of the following text synonyms (the field values are also listed): <b>critical-ecp</b> (0xa0), <b>flash</b> (0x60), <b>flash-override</b> (0x80), <b>immediate</b> (0x40), <b>internet-control</b> (0xc0), <b>net-control</b> (0xe0), <b>priority</b> (0x20), or <b>routine</b> (0x00). You can specify precedence in hexadecimal, binary, or decimal form.</p>



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<del>precedence-<b>except</b></del> <del>precedence-value</del>	Do not match the IP precedence field.  In place of the numeric field value, you can specify one of the following text synonyms (the field values are also listed): <b>critical-ecp</b> (0xa0), <b>flash</b> (0x60), <b>flash-override</b> (0x80), <b>immediate</b> (0x40), <b>internet-control</b> (0xc0), <b>net-control</b> (0xe0), <b>priority</b> (0x20), or <b>routine</b> (0x00). You can specify precedence in hexadecimal, binary, or decimal form.
<b>prefix-list</b> <i>name</i>	Match the prefixes of the source or destination address fields to the prefixes in the specified list unless the <b>except</b> option is included. If the option is included, do not match the prefixes of the source or destination address fields to the prefixes in the specified list.  The prefix list is defined at the <b>[edit policy-options prefix-list <i>prefix-list-name</i>]</b> hierarchy level.
<b>protocol</b> <i>number</i>	Match the IP protocol type field. In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipv6</b> (41), <b>ospf</b> (89), <b>pim</b> (103), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrrp</b> (112).
<b>protocol-except</b> <i>number</i>	Do not match the IP protocol type field. In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipv6</b> (41), <b>ospf</b> (89), <b>pim</b> (103), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrrp</b> (112).
<b>rat-type</b> <i>tech-type-value</i>	Match the radio-access technology (RAT) type specified in the 8-bit Tech-Type field of Proxy Mobile IPv4 (PMIPv4) access technology type extension. The technology type specifies the access technology through which the mobile device is connected to the access network.  Specify a single value, a range of values, or a set of values. You can specify a technology type as a numeric value from 0 through 255 or as a system keyword.  <ul style="list-style-type: none"> <li>The following numeric values are examples of well-known technology types: <ul style="list-style-type: none"> <li>Numeric value 1 matches IEEE 802.3.</li> <li>Numeric value 2 matches IEEE 802.11a/b/g.</li> <li>Numeric value 3 matches IEEE 802.16e</li> <li>Numeric value 4 matches IEEE 802.16m.</li> </ul> </li> <li>Text string <b>eutran</b> matches 4G.</li> <li>Text string <b>geran</b> matches 2G.</li> <li>Text string <b>utran</b> matches 3G.</li> </ul>
<b>rat-type-except</b> <i>tech-type-value</i>	Do not match the RAT Type.
<b>service-filter-hit</b>	Match a packet received from a filter where a <b>service-filter-hit</b> action was applied.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>source-address</b> <i>address</i> <b>[ except ]</b>	Match the IPv4 address of the source node sending the packet unless the <b>except</b> option is included. If the option is included, do not match the IPv4 address of the source node sending the packet.  You cannot specify both the <b>address</b> and <b>source-address</b> match conditions in the same term.



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>source-class</b> <i>class-names</i>	<p>Match one or more specified source class names (sets of source prefixes grouped together and given a class name). For more information, see <a href="#">“Firewall Filter Match Conditions Based on Address Classes”</a> on page 43.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>source-class-except</b> <i>class-names</i>	<p>Do not match one or more specified source class names. For details, see the <b>source-class</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>source-port</b> <i>number</i>	<p>Match the UDP or TCP source port field.</p> <p>You cannot specify the <b>port</b> and <b>source-port</b> match conditions in the same term.</p> <p>If you configure this match condition for IPv4 traffic, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed with the <b>destination-port</b> <i>number</i> match condition.</p>
<b>source-port-except</b> <i>number</i>	<p>Do not match the UDP or TCP source port field. For details, see the <b>source-port</b> match condition.</p>
<b>source-prefix-list</b> <i>name</i> [ <b>except</b> ]	<p>Match source prefixes in the specified list unless the <b>except</b> option is included. If the option is included, do not match the source prefixes in the specified list.</p> <p>Specify the name of a prefix list defined at the [edit policy-options prefix-list <i>prefix-list-name</i>] hierarchy level.</p>
<b>tcp-established</b>	<p>Match TCP packets of an established TCP session (packets other than the first packet of a connection). This is an alias for <b>tcp-flags</b> "(ack   rst)".</p> <p>This match condition does not implicitly check that the protocol is TCP. To check this, specify the <b>protocol tcp</b> match condition.</p>



Table 15: Standard Firewall Filter Match Conditions for IPv4 Traffic (*continued*)

Match Condition	Description
<b>tcp-flags <i>value</i></b>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> <li>• <b>fin</b> (0x01)</li> <li>• <b>syn</b> (0x02)</li> <li>• <b>rst</b> (0x04)</li> <li>• <b>push</b> (0x08)</li> <li>• <b>ack</b> (0x10)</li> <li>• <b>urgent</b> (0x20)</li> </ul> <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>For combined bit-field match conditions, see the <b>tcp-established</b> and <b>tcp-initial</b> match conditions.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol tcp</b> match statement in the same term to specify that the TCP protocol is being used on the port.</p> <p>For IPv4 traffic only, this match condition does not implicitly check whether the datagram contains the first fragment of a fragmented packet. To check for this condition for IPv4 traffic only, use the <b>first-fragment</b> match condition.</p>
<b>tcp-initial</b>	<p>Match the initial packet of a TCP connection. This is an alias for <b>tcp-flags "(lack &amp; syn)"</b>.</p> <p>This condition does not implicitly check that the protocol is TCP. If you configure this match condition, we recommend that you also configure the <b>protocol tcp</b> match condition in the same term.</p>
<b>ttl <i>number</i></b>	<p>Match the IPv4 time-to-live number. Specify a TTL value or a range of TTL values. For <b><i>number</i></b>, you can specify one or more values from <b>0</b> through <b>255</b>. This match condition is supported only on M120, M320, MX Series, and T Series routers.</p>
<b>ttl-except <i>number</i></b>	<p>Do not match on the IPv4 TTL number. For details, see the <b>ttl</b> match condition.</p>

**Related Documentation**

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Terminating Actions on page 293](#)
- [Standard Firewall Filter Nonterminating Actions on page 294](#)

## Standard Firewall Filter Match Conditions for IPv6 Traffic

You can configure a standard stateless firewall filter with match conditions for Internet Protocol version 6 (IPv6) traffic (**family inet6**). [Table 16 on page 268](#) describes the **match-conditions** you can configure at the **[edit firewall family inet6 filter *filter-name* term *term-name* from]** hierarchy level.



Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic

Match Condition	Description
<b>address</b> <i>address</i> [ <b>except</b> ]	Match the IPv6 source or destination address field unless the <b>except</b> option is included. If the option is included, do not match the IPv6 source or destination address field.
<b>apply-groups</b>	Specify which groups to inherit configuration data from. You can specify more than one group name. You must list them in order of inheritance priority. The configuration data in the first group takes priority over the data in subsequent groups.
<b>apply-groups-except</b>	Specify which groups not to inherit configuration data from. You can specify more than one group name.
<b>destination-address</b> <i>address</i> [ <b>except</b> ]	Match the IPv6 destination address field unless the <b>except</b> option is included. If the option is included, do not match the IPv6 destination address field.  You cannot specify both the <b>address</b> and <b>destination-address</b> match conditions in the same term.
<b>destination-class</b> <i>class-names</i>	Match one or more specified destination class names (sets of destination prefixes grouped together and given a class name).  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.  For more information, see <a href="#">"Firewall Filter Match Conditions Based on Address Classes" on page 43</a> .
<b>destination-class-except</b> <i>class-names</i>	Do not match one or more specified destination class names. For details, see the <b>destination-class</b> match condition.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>destination-port</b> <i>number</i>	Match the UDP or TCP destination port field.  You cannot specify both the <b>port</b> and <b>destination-port</b> match conditions in the same term.  If you configure this match condition, we recommend that you also configure the <b>next-header udp</b> or <b>next-header tcp</b> match condition in the same term to specify which protocol is being used on the port.  In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>ldp</b> (646), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobileip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rkinit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs</b> (49), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xdmcp</b> (177).
<b>destination-port-except</b> <i>number</i>	Do not match the UDP or TCP destination port field. For details, see the <b>destination-port</b> match condition.
<b>destination-prefix-list</b> <i>prefix-list-name</i> [ <b>except</b> ]	Match the IPv6 destination prefix to the specified list unless the <b>except</b> option is included. If the option is included, do not match the IPv6 destination prefix to the specified list.  The prefix list is defined at the [edit policy-options prefix-list <i>prefix-list-name</i> ] hierarchy level.



Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic (*continued*)

Match Condition	Description
<b>forwarding-class</b> <i>class</i>	<p>Match the forwarding class of the packet.</p> <p>Specify <b>assured-forwarding</b>, <b>best-effort</b>, <b>expedited-forwarding</b>, or <b>network-control</b>.</p> <p>For information about forwarding classes and router-internal output queues, see the Junos OS Class of Service Configuration Guide.</p>
<b>forwarding-class-except</b> <i>class</i>	Do not match the forwarding class of the packet. For details, see the <b>forwarding-class</b> match condition.
<b>hop-limit</b> <i>hop-limit</i>	Match the hop limit to the specified hop limit or set of hop limits. For <b>hop-limit</b> , specify a single value or a range of values from 0 through 255..
<b>hop-limit-except</b> <i>message-code</i>	Do not match the hop limit to the specified hop limit or set of hop limits. For details, see the <b>hop-limit</b> match condition.
<b>icmp-code</b> <i>message-code</i>	<p>Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header icmp</b> or <b>next-header icmp6</b> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <b>icmp-type message-type</b> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> <li>parameter-problem: <b>ip6-header-bad</b> (0), <b>unrecognized-next-header</b> (1), <b>unrecognized-option</b> (2)</li> <li>time-exceeded: <b>ttl-eq-zero-during-reassembly</b> (1), <b>ttl-eq-zero-during-transit</b> (0)</li> <li>destination-unreachable: <b>administratively-prohibited</b> (1), <b>address-unreachable</b> (3), <b>no-route-to-destination</b> (0), <b>port-unreachable</b> (4)</li> </ul>
<b>icmp-code-except</b> <i>message-code</i>	Do not match the ICMP message code field. For details, see the <b>icmp-code</b> match condition.
<b>icmp-type</b> <i>message-type</i>	<p>Match the ICMP message type field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header icmp</b> or <b>next-header icmp6</b> match condition in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>destination-unreachable</b> (1), <b>echo-reply</b> (129), <b>echo-request</b> (128), <b>membership-query</b> (130), <b>membership-report</b> (131), <b>membership-termination</b> (132), <b>neighbor-advertisement</b> (136), <b>neighbor-solicit</b> (135), <b>node-information-reply</b> (140), <b>node-information-request</b> (139), <b>packet-too-big</b> (2), <b>parameter-problem</b> (4), <b>redirect</b> (137), <b>router-advertisement</b> (134), <b>router-renumbering</b> (138), <b>router-solicit</b> (133), or <b>time-exceeded</b> (3).</p>
<b>icmp-type-except</b> <i>message-type</i>	Do not match the ICMP message type field. For details, see the <b>icmp-type</b> match condition.



Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic (*continued*)

Match Condition	Description
<b>interface</b> <i>interface-name</i>	<p>Match the interface on which the packet was received.</p> <p><b>NOTE:</b> If you configure this match condition with an interface that does not exist, the term does not match any packet.</p>
<b>interface-group</b> <i>group-number</i>	<p>Match the logical interface on which the packet was received to the specified interface group or set of interface groups. For <i>group-number</i>, specify a single value or a range of values from 0 through 255.</p> <p>To assign a logical interface to an interface group <i>group-number</i>, specify the <i>group-number</i> at the <b>[interfaces interface-name unit number family family filter group]</b> hierarchy level.</p> <p>For more information, see <a href="#">“Filtering Packets Received on a Set of Interface Groups Overview” on page 57</a>.</p>
<b>interface-group-except</b> <i>group-number</i>	<p>Do not match the logical interface on which the packet was received to the specified interface group or set of interface groups. For details, see the <b>interface-group</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>interface-set</b> <i>interface-set-name</i>	<p>Match the interface on which the packet was received to the specified interface set.</p> <p>To define an interface set, include the <b>interface-set</b> statement at the <b>[edit firewall]</b> hierarchy level.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see <a href="#">“Filtering Packets Received on an Interface Set Overview” on page 58</a>.</p>
<b>loss-priority</b> <i>level</i>	<p>Match the packet loss priority (PLP) level.</p> <p>Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>loss-priority-except</b> <i>level</i>	<p>Do not match the PLP level. For details, see the <b>loss-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>



Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic (*continued*)

Match Condition	Description
<b>next-header <i>header-type</i></b>	<p>Match the 8-bit Next Header field that identifies the type of header between the IPv6 header and payload.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipv6</b> (41), <b>no-next-header</b> (59), <b>ospf</b> (89), <b>pim</b> (103), <b>routing</b> (43), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrp</b> (112).</p> <p><b>NOTE:</b> <b>next-header icmp6</b> and <b>next-header icmpv6</b> match conditions perform the same function. <b>next-header icmp6</b> is the preferred option. <b>next-header icmpv6</b> is hidden in the Junos OS CLI.</p>
<b>next-header-except <i>header-type</i></b>	Do not match the 8-bit Next Header field that identifies the type of header between the IPv6 header and payload. For details, see the <b>next-header</b> match type.
<b>packet-length <i>bytes</i></b>	Match the length of the received packet, in bytes. The length refers only to the IP packet, including the packet header, and does not include any Layer 2 encapsulation overhead.
<b>packet-length-except <i>bytes</i></b>	Do not match the length of the received packet, in bytes. For details, see the <b>packet-length</b> match type.
<b>payload-protocol <i>protocol-type</i></b>	<p>Match the payload protocol type.</p> <p>In place of the <b>protocol-type</b> numeric value, you can specify one of the following text synonyms (the field values are also listed): specify one or a set of of the following: <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipv6</b> (41), <b>no-next-header</b>, <b>ospf</b> (89), <b>pim</b> (103), <b>routing</b>, <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrp</b> (112).</p>
<b>payload-protocol-except <i>protocol-type</i></b>	Do not match the payload protocol type. For details, see the <b>payload-protocol</b> match type.
<b>port <i>number</i></b>	<p>Match the UDP or TCP source or destination port field.</p> <p>If you configure this match condition, you cannot configure the <b>destination-port</b> match condition or the <b>source-port</b> match condition in the same term.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header udp</b> or <b>next-header tcp</b> match condition in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed under <b>destination-port</b>.</p>
<b>port-except <i>number</i></b>	Do not match the UDP or TCP source or destination port field. For details, see the <b>port</b> match condition.
<b>prefix-list <i>prefix-list-name</i> [ except ]</b>	<p>Match the prefixes of the source or destination address fields to the prefixes in the specified list unless the <b>except</b> option is included. If the option is included, do not match the prefixes of the source or destination address fields to the prefixes in the specified list.</p> <p>The prefix list is defined at the <b>[edit policy-options prefix-list <i>prefix-list-name</i>]</b> hierarchy level.</p>



Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic (*continued*)

Match Condition	Description
<b>service-filter-hit</b>	<p>Match a packet received from a filter where a <b>service-filter-hit</b> action was applied.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>source-address</b> <i>address</i> [ <b>except</b> ]	<p>Match the IPv6 address of the source node sending the packet unless the <b>except</b> option is included. If the option is included, do not match the IPv6 address of the source node sending the packet.</p> <p>You cannot specify both the <b>address</b> and <b>source-address</b> match conditions in the same term.</p>
<b>source-class</b> <i>class-names</i>	<p>Match one or more specified source class names (sets of source prefixes grouped together and given a class name).</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see <a href="#">“Firewall Filter Match Conditions Based on Address Classes” on page 43</a>.</p>
<b>source-class-except</b> <i>class-names</i>	<p>Do not match one or more specified source class names. For details, see the <b>source-class</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>source-port</b> <i>number</i>	<p>Match the UDP or TCP source port field.</p> <p>You cannot specify the <b>port</b> and <b>source-port</b> match conditions in the same term.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header udp</b> or <b>next-header tcp</b> match condition in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed with the <b>destination-port number</b> match condition.</p>
<b>source-port-except</b> <i>number</i>	<p>Do not match the UDP or TCP source port field. For details, see the <b>source-port</b> match condition.</p>
<b>source-prefix-list</b> <i>name</i> [ <b>except</b> ]	<p>Match the IPv6 address prefix of the packet source field unless the <b>except</b> option is included. If the option is included, do not match the IPv6 address prefix of the packet source field.</p> <p>Specify a prefix list name defined at the <b>[edit policy-options prefix-list prefix-list-name]</b> hierarchy level.</p>
<b>tcp-established</b>	<p>Match TCP packets other than the first packet of a connection. This is a text synonym for <b>tcp-flags "(ack   rst)" (0x14)</b>.</p> <p><b>NOTE:</b> This condition does not implicitly check that the protocol is TCP. To check this, specify the <b>protocol tcp</b> match condition.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header tcp</b> match condition in the same term.</p>



Table 16: Standard Firewall Filter Match Conditions for IPv6 Traffic (*continued*)

Match Condition	Description
<b>tcp-flags</b> <i>flags</i>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> <li>• <b>fin</b> (0x01)</li> <li>• <b>syn</b> (0x02)</li> <li>• <b>rst</b> (0x04)</li> <li>• <b>push</b> (0x08)</li> <li>• <b>ack</b> (0x10)</li> <li>• <b>urgent</b> (0x20)</li> </ul> <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>For combined bit-field match conditions, see the <b>tcp-established</b> and <b>tcp-initial</b> match conditions.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header tcp</b> match condition in the same term to specify that the TCP protocol is being used on the port.</p>
<b>tcp-initial</b>	<p>Match the initial packet of a TCP connection. This is a text synonym for <b>tcp-flags "(!ack &amp; syn)"</b>.</p> <p>This condition does not implicitly check that the protocol is TCP. If you configure this match condition, we recommend that you also configure the <b>next-header tcp</b> match condition in the same term.</p>
<b>traffic-class</b> <i>number</i>	<p>Match the 8-bit field that specifies the class-of-service (CoS) priority of the packet.</p> <p>This field was previously used as the type-of-service (ToS) field in IPv4.</p> <p>You can specify a numeric value from <b>0</b> through <b>63</b>. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> <li>• RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: <b>ef</b> (46).</li> <li>• RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points: <ul style="list-style-type: none"> <li>• <b>af11</b> (10), <b>af12</b> (12), <b>af13</b> (14)</li> <li>• <b>af21</b> (18), <b>af22</b> (20), <b>af23</b> (22)</li> <li>• <b>af31</b> (26), <b>af32</b> (28), <b>af33</b> (30)</li> <li>• <b>af41</b> (34), <b>af42</b> (36), <b>af43</b> (38)</li> </ul> </li> </ul>
<b>traffic-class-except</b> <i>number</i>	<p>Do not match the 8-bit field that specifies the CoS priority of the packet. For details, see the <b>traffic-class</b> match description.</p>





**NOTE:** If you specify an IPv6 address in a match condition (the *address*, *destination-address*, or *source-address* match conditions), use the syntax for text representations described in RFC 2373, *IP Version 6 Addressing Architecture*. For more information about IPv6 addresses, see “IPv6 Overview” and “IPv6 Standards” in the Junos OS Routing Protocols Configuration Guide.

#### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Terminating Actions on page 293](#)
- [Standard Firewall Filter Nonterminating Actions on page 294](#)

## Standard Firewall Filter Match Conditions for MPLS Traffic

You can configure a standard stateless firewall filter with match conditions for MPLS traffic (*family mpls*).



**NOTE:** The input-list *filter-names* and output-list *filter-names* statements for firewall filters for the *mpls* protocol family are supported on all interfaces with the exception of management interfaces and internal Ethernet interfaces (*fxp* or *em0*), loopback interfaces (*lo0*), and USB modem interfaces (*umd*).

Table 17 on page 274 describes the *match-conditions* you can configure at the [edit firewall family *mpls* filter *filter-name* term *term-name* from] hierarchy level.

Table 17: Standard Firewall Filter Match Conditions for MPLS Traffic

Match Condition	Description
<b>apply-groups</b>	Specify which groups to inherit configuration data from. You can specify more than one group name. You must list them in order of inheritance priority. The configuration data in the first group takes priority over the data in subsequent groups.
<b>apply-groups-except</b>	Specify which groups not to inherit configuration data from. You can specify more than one group name.
<b>exp <i>number</i></b>	Experimental (EXP) bit number or range of bit numbers in the MPLS header. For <i>number</i> , you can specify one or more values from 0 through 7 in decimal, binary, or hexadecimal format.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>exp-except <i>number</i></b>	Do not match on the EXP bit number or range of bit numbers in the MPLS header. For <i>number</i> , you can specify one or more values from 0 through 7.  <b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.
<b>forwarding-class <i>class</i></b>	Forwarding class. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .
<b>forwarding-class-except <i>class</i></b>	Do not match on the forwarding class. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .



Table 17: Standard Firewall Filter Match Conditions for MPLS Traffic (*continued*)

Match Condition	Description
<b>interface</b> <i>interface-name</i>	<p>Interface on which the packet was received. You can configure a match condition that matches packets based on the interface on which they were received.</p> <p><b>NOTE:</b> If you configure this match condition with an interface that does not exist, the term does not match any packet.</p>
<b>interface-set</b> <i>interface-set-name</i>	<p>Match the interface on which the packet was received to the specified interface set.</p> <p>To define an interface set, include the <b>interface-set</b> statement at the <b>[edit firewall]</b> hierarchy level.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see “<a href="#">Filtering Packets Received on an Interface Set Overview</a>” on page 58.</p>
<b>ip-version</b> <i>number</i>	<p>(Interfaces on Enhanced Scaling flexible PIC concentrators [FPCs] on supported T Series routers only) Inner IP version. To match MPLS-tagged IPv4 packets, match on the text synonym <b>ipv4</b>.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>loss-priority</b> <i>level</i>	<p>Match the packet loss priority (PLP) level.</p> <p>Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>loss-priority-except</b> <i>level</i>	<p>Do not match the PLP level. For details, see the <b>loss-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>

**Related  
Documentation**

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Terminating Actions on page 293](#)
- [Standard Firewall Filter Nonterminating Actions on page 294](#)



## Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic

---

This topic covers the following information:

- [Matching on IPv4 or IPv6 Packet Header Address or Port Fields in MPLS Flows on page 276](#)
- [IP Address Match Conditions for MPLS Traffic on page 277](#)
- [IP Port Match Conditions for MPLS Traffic on page 277](#)

### Matching on IPv4 or IPv6 Packet Header Address or Port Fields in MPLS Flows

To support network-based service in a core network, you can configure a standard firewall filter that matches Internet Protocol version 4 (IPv4) or version 6 (IPv6) packet header fields in MPLS traffic (**family mpls**). The firewall filter can match IPv4 or IPv6 packets as an inner payload of an MPLS packet that has a single MPLS label or up to five MPLS labels stacked together. You can configure match conditions based on IPv4 addresses and IPv4 port numbers or IPv6 addresses and IPv6 port numbers in the header.

Standard firewall filters based on MPLS-tagged IPv4 headers are supported for interfaces on Enhanced Scaling flexible PIC concentrators (FPCs) on T320, T640, T1600, TX Matrix, and TX Matrix Plus routers only. However, the standard firewall filters based on MPLS-tagged IPv6 headers are supported for interfaces on the Type 5 FPC on T4000 Core Routers only. The feature is not supported for the router loopback interface (**lo0**), the router management interface (**fxp0** or **em0**), or USB modem interfaces (**umd**).

To configure a stateless firewall filter term that matches an address or port fields in the Layer 4 header of packets in an MPLS flow, you use the **ip-version ipv4** match condition to specify that the term is to match packets based on inner IP fields:

- To match an MPLS-tagged IPv4 packet on the source or destination address field in the IPv4 header, specify the match condition at the **[edit firewall family mpls filter filter-name term term-name from ip-version ipv4]** hierarchy level.
- To match an MPLS-tagged IPv4 packet on the source or destination port field in the Layer 4 header, specify the match condition at the **[edit firewall family mpls filter filter-name term term-name from ip-version ipv4 protocol (udp | tcp)]** hierarchy level.

To configure a stateless firewall filter term that matches an address or port fields in the IPv6 header of packets in an MPLS flow, you use the **ip-version ipv6** match condition to specify that the term is to match packets based on inner IP fields:

- To match an MPLS-tagged IPv6 packet on the source or destination address field in the IPv6 header, specify the match condition at the **[edit firewall family mpls filter filter-name term term-name from ip-version ipv6]** hierarchy level.
- To match an MPLS-tagged IPv6 packet on the source or destination port field in the Layer 4 header, specify the match condition at the **[edit firewall family mpls filter filter-name term term-name from ip-version ipv6 protocol (udp | tcp)]** hierarchy level.



## IP Address Match Conditions for MPLS Traffic

Table 18 on page 277 describes the IP address-specific match conditions you can configure at the `[edit firewall family mpls filter filter-name term term-name from ip-version ip-version]` hierarchy level.

**Table 18: IP Address-Specific Firewall Filter Match Conditions for MPLS Traffic**

Match Condition	Description
<code>destination-address <i>address</i></code>	Match the address of the destination node to receive the packet.
<code>destination-address <i>address</i> except</code>	Do not match the address of the destination node to receive the packet.
<code>protocol <i>number</i></code>	Match the IP protocol type field. In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>ah</b> (51), <b>dstop</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipv6</b> (41), <b>ospf</b> (89), <b>pim</b> (103), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrp</b> (112).
<code>source-address <i>address</i></code>	Match the address of the source node sending the packet.
<code>source-address <i>address</i> except</code>	Do not match the address of the source node sending the packet.

## IP Port Match Conditions for MPLS Traffic

Table 19 on page 278 describes the IP port-specific *match-conditions* you can configure at the `[edit firewall family mpls filter filter-name term term-name from ip-version ip-version protocol (udp | tcp )]` hierarchy level.



Table 19: IP Port-Specific Firewall Filter Match Conditions for MPLS Traffic

Match Condition	Description
<b>destination-port <i>number</i></b>	<p>Match on the UDP or TCP destination port field.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>ldp</b> (646), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobilip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rkinit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs</b> (49), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xmcp</b> (177).</p>
<b>destination-port-except <i>number</i></b>	<p>Do not match on the UDP or TCP destination port field.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed with the <b>destination-port</b> match condition.</p>
<b>source-port <i>number</i></b>	<p>Match on the TCP or UDP source port field.</p> <p>In place of the numeric field, you can specify one of the text synonyms listed under <b>destination-port</b>.</p>
<b>source-port-except <i>number</i></b>	Do not match on the TCP or UDP source port field.

#### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Terminating Actions on page 293](#)
- [Standard Firewall Filter Nonterminating Actions on page 294](#)

## Standard Firewall Filter Match Conditions for VPLS Traffic

In the **from** statement in the VPLS filter term, you specify conditions that the packet must match for the action in the **then** statement to be taken. All conditions in the **from** statement must match for the action to be taken. The order in which you specify match conditions is not important, because a packet must match all the conditions in a term for a match to occur.

If you specify no match conditions in a term, that term matches all packets.

An individual condition in a **from** statement can contain a list of values. For example, you can specify numeric ranges. You can also specify multiple source addresses or destination addresses. When a condition defines a list of values, a match occurs if one of the values in the list matches the packet.



Individual conditions in a **from** statement can be negated. When you negate a condition, you are defining an explicit mismatch. For example, the negated match condition for **forwarding-class** is **forwarding-class-except**. If a packet matches a negated condition, it is immediately considered not to match the **from** statement, and the next term in the filter is evaluated, if there is one. If there are no more terms, the packet is discarded.

You can configure a standard firewall filter with match conditions for Virtual Private LAN Service (VPLS) traffic (**family vpls**). [Table 20 on page 279](#) describes the **match-conditions** you can configure at the **[edit firewall family vpls filter *filter-name* term *term-name* from]** hierarchy level.



**NOTE:** Not all match conditions for VPLS traffic are supported on all routing platforms. A number of match conditions for VPLS traffic are supported only on MX Series 3D Universal Edge Routers.

**Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic**

Match Condition	Description
<b>destination-mac-address address</b>	Match the destination media access control (MAC) address of a VPLS packet.
<b>destination-port number</b>	<p>(MX Series routers only) Match the UDP or TCP destination port field.</p> <p>You cannot specify both the <b>port</b> and <b>destination-port</b> match conditions in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>ldp</b> (646), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobileip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rkinit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs</b> (49), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xmcp</b> (177).</p>
<b>destination-port-except number</b>	(MX Series routers only) Do not match on the TCP or UDP destination port field. You cannot specify both the <b>port</b> and <b>destination-port</b> match conditions in the same term.
<b>destination-prefix-list name</b>	<p>(MX Series routers only) Match destination prefixes in the specified list. Specify the name of a prefix list defined at the <b>[edit policy-options prefix-list <i>prefix-list-name</i>]</b> hierarchy level.</p> <p><b>NOTE:</b> VPLS prefix lists support only IPv4 addresses. IPv6 addresses included in a VPLS prefix list will be discarded.</p>
<b>destination-prefix-list name except</b>	(MX Series routers only) Do not match destination prefixes in the specified list. For more information, see the <b>destination-prefix-list</b> match condition.



Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic (*continued*)

Match Condition	Description
<b>dscp number</b>	<p>(MX Series routers only) Match the Differentiated Services code point (DSCP). The DiffServ protocol uses the type-of-service (ToS) byte in the IP header. The most significant 6 bits of this byte form the DSCP. For more information, see the Junos OS Class of Service Configuration Guide.</p> <p>You can specify a numeric value from <b>0</b> through <b>63</b>. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> <li>• RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: <b>ef</b> (46).</li> <li>• RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points:</li> </ul> <p><b>af11</b> (10), <b>af12</b> (12), <b>af13</b> (14),</p> <p><b>af21</b> (18), <b>af22</b> (20), <b>af23</b> (22),</p> <p><b>af31</b> (26), <b>af32</b> (28), <b>af33</b> (30),</p> <p><b>af41</b> (34), <b>af42</b> (36), <b>af43</b> (38)</p>
<b>dscp-except number</b>	(MX Series routers only) Do not match on the DSCP. For details, see the <b>dscp</b> match condition.
<b>ether-type values</b>	<p>Match the 2-octet IEEE 802.3 Length/EtherType field to the specified value or list of values.</p> <p>You can specify decimal or hexadecimal values from 0 through 65535 (0xFFFF). A value from 0 through 1500 (0x05DC) specifies the length of an Ethernet Version 1 frame. A value from 1536 (0x0600) through 65535 specifies the EtherType (nature of the MAC client protocol) of an Ethernet Version 2 frame.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the hexadecimal values are also listed): <b>aarp</b> (0x80F3), <b>appletalk</b> (0x809B), <b>arp</b> (0x0806), <b>ipv4</b> (0x0800), <b>ipv6</b> (0x86DD), <b>mpls-multicast</b> (0x8848), <b>mpls-unicast</b> (0x8847), <b>oam</b> (0x8902), <b>ppp</b> (0x880B), <b>pppoe-discovery</b> (0x8863), <b>pppoe-session</b> (0x8864), or <b>sna</b> (0x80D5).</p>
<b>ether-type-except values</b>	<p>Do not match the 2-octet Length/EtherType field to the specified value or list of values.</p> <p>For details about specifying the <b>values</b>, see the <b>ether-type</b> match condition.</p>
<b>forwarding-class class</b>	Match the forwarding class. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .
<b>forwarding-class-except class</b>	Do not match the forwarding class. For details, see the <b>forwarding-class</b> match condition.



Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic (*continued*)

Match Condition	Description
<b>icmp-code message-code</b>	<p>Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>next-header icmp</b> or <b>next-header icmp6</b> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <b>icmp-type message-type</b> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> <li>parameter-problem: <b>ip6-header-bad</b> (0), <b>unrecognized-next-header</b> (1), <b>unrecognized-option</b> (2)</li> <li>time-exceeded: <b>ttl-eq-zero-during-reassembly</b> (1), <b>ttl-eq-zero-during-transit</b> (0)</li> <li>destination-unreachable: <b>address-unreachable</b> (3), <b>administratively-prohibited</b> (1), <b>no-route-to-destination</b> (0), <b>port-unreachable</b> (4)</li> </ul>
<b>icmp-code-except message-code</b>	Do not match the ICMP message code field. For details, see the <b>icmp-code</b> match condition.
<b>icmp-code number</b>	<p>(MX Series routers only) Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>ip-protocol icmp</b> or <b>ip-protocol icmp6</b> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <b>icmp-type message-type</b> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> <li>parameter-problem: <b>ip6-header-bad</b> (0), <b>unrecognized-next-header</b> (1), <b>unrecognized-option</b> (2)</li> <li>time-exceeded: <b>ttl-eq-zero-during-reassembly</b> (1), <b>ttl-eq-zero-during-transit</b> (0)</li> <li>destination-unreachable: <b>address-unreachable</b> (3), <b>administratively-prohibited</b> (1), <b>no-route-to-destination</b> (0), <b>port-unreachable</b> (4)</li> </ul>
<b>icmp-code-except number</b>	(MX Series routers only) Do not match on the ICMP code field. For details, see the <b>icmp-code</b> match condition.
<b>icmp-type number</b>	<p>(MX Series routers only) Match the ICMP message type field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>ip-protocol icmp</b>, <b>ip-protocol icmp6</b>, or <b>ip-protocol icmpv6</b> match condition in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>destination-unreachable</b> (1), <b>echo-reply</b> (129), <b>echo-request</b> (128), <b>membership-query</b> (130), <b>membership-report</b> (131), <b>membership-termination</b> (132), <b>neighbor-advertisement</b> (136), <b>neighbor-solicit</b> (135), <b>node-information-reply</b> (140), <b>node-information-request</b> (139), <b>packet-too-big</b> (2), <b>parameter-problem</b> (4), <b>redirect</b> (137), <b>router-advertisement</b> (134), <b>router-renumbering</b> (138), <b>router-solicit</b> (133), or <b>time-exceeded</b> (3).</p>



Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic (*continued*)

Match Condition	Description
<b>icmp-type-except</b> <i>number</i>	(MX Series routers only) Do not match the ICMP message type field. For details, see the <b>icmp-type</b> match condition.
<b>interface</b> <i>interface-name</i>	Interface on which the packet was received. You can configure a match condition that matches packets based on the interface on which they were received.  <b>NOTE:</b> If you configure this match condition with an interface that does not exist, the term does not match any packet.
<b>interface-group</b> <i>group-number</i>	Match the logical interface on which the packet was received to the specified interface group or set of interface groups. For <i>group-number</i> , specify a single value or a range of values from 0 through 255.  To assign a logical interface to an interface group <i>group-number</i> , specify the <i>group-number</i> at the [interfaces <i>interface-name</i> unit <i>number</i> family <i>family</i> filter group] hierarchy level.  For more information, see “Filtering Packets Received on a Set of Interface Groups Overview” on page 57.  <b>NOTE:</b> This match condition is not supported on T4000 Type 5 FPCs.
<b>interface-group-except</b> <i>group-name</i>	Do not match the logical interface on which the packet was received to the specified interface group or set of interface groups. For details, see the <b>interface-group</b> match condition.  <b>NOTE:</b> This match condition is not supported on T4000 Type 5 FPCs.
<b>interface-set</b> <i>interface-set-name</i>	Match the interface on which the packet was received to the specified interface set.  To define an interface set, include the <b>interface-set</b> statement at the [edit firewall] hierarchy level. For more information, see “Filtering Packets Received on an Interface Set Overview” on page 58.
<b>ip-address</b> <i>address</i>	(MX Series routers only) 32-bit address that supports the standard syntax for IPv4 addresses.
<b>ip-destination-address</b> <i>address</i>	(MX Series routers only) 32-bit address that is the final destination node address for the packet.
<b>ip-precedence</b> <i>ip-precedence-field</i>	(MX Series routers only) IP precedence field. In place of the numeric field value, you can specify one of the following text synonyms (the field values are also listed): <b>critical-ecp</b> (0xa0), <b>flash</b> (0x60), <b>flash-override</b> (0x80), <b>immediate</b> (0x40), <b>internet-control</b> (0xc0), <b>net-control</b> (0xe0), <b>priority</b> (0x20), or <b>routine</b> (0x00).
<b>ip-precedence-except</b> <i>ip-precedence-field</i>	(MX Series routers only) Do not match on the IP precedence field.
<b>ip-protocol</b> <i>number</i>	(MX Series routers only) IP protocol field.
<b>ip-protocol-except</b> <i>number</i>	(MX Series routers only) Do not match on the IP protocol field.
<b>ip-source-address</b> <i>address</i>	(MX Series routers only) IP address of the source node sending the packet.



Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic (*continued*)

Match Condition	Description
<b>learn-vlan-1p-priority</b> <i>number</i>	<p>(MX Series routers only) Match on the IEEE 802.1p learned VLAN priority bits in the provider VLAN tag (the only tag in a single-tag frame with 802.1Q VLAN tags or the outer tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <b>user-vlan-1p-priority</b> match condition.</p>
<b>learn-vlan-1p-priority-except</b> <i>number</i>	(MX Series routers only) Do not match on the IEEE 802.1p learned VLAN priority bits. For details, see the <b>learn-vlan-1p-priority</b> match condition.
<b>learn-vlan-dei</b>	(MX Series routers only) Match the user VLAN ID drop eligibility indicator (DEI) bit.
<b>learn-vlan-dei-except</b>	(MX Series routers only) Do not match the user VLAN ID DEI bit.
<b>learn-vlan-id</b> <i>number</i>	(MX Series routers only) VLAN identifier used for MAC learning.
<b>learn-vlan-id-except</b> <i>number</i>	(MX Series routers only) Do not match on the VLAN identifier used for MAC learning.
<b>loss-priority</b> <i>level</i>	<p>Packet loss priority (PLP) level. Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p>For information about the <b>tri-color</b> statement and about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>loss-priority-except</b> <i>level</i>	<p>Do not match on the packet loss priority level. Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>For information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>port</b> <i>number</i>	(MX Series routers only) TCP or UDP source or destination port. You cannot specify both the <b>port</b> match condition and either the <b>destination-port</b> or <b>source-port</b> match condition in the same term.
<b>port-except</b> <i>number</i>	(MX Series routers only) Do not match on the TCP or UDP source or destination port. You cannot specify both the <b>port</b> match condition and either the <b>destination-port</b> or <b>source-port</b> match condition in the same term.
<b>prefix-list</b> <i>name</i>	<p>(MX Series routers only) Match the destination or source prefixes in the specified list. Specify the name of a prefix list defined at the <b>[edit policy-options prefix-list prefix-list-name]</b> hierarchy level.</p> <p><b>NOTE:</b> VPLS prefix lists support only IPV4 addresses. IPV6 addresses included in a VPLS prefix list will be discarded.</p>
<b>prefix-list</b> <i>name</i> <b>except</b>	(MX Series routers only) Do not match the destination or source prefixes in the specified list. For more information, see the <b>destination-prefix-list</b> match condition.



Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic (*continued*)

Match Condition	Description
<b>source-mac-address</b> <i>address</i>	Source MAC address of a VPLS packet.
<b>source-port</b> <i>number</i>	(MX Series routers only) TCP or UDP source port field. You cannot specify the <b>port</b> and <b>source-port</b> match conditions in the same term.
<b>source-port-except</b> <i>number</i>	(MX Series routers only) Do not match on the TCP or UDP source port field. You cannot specify the <b>port</b> and <b>source-port</b> match conditions in the same term.
<b>source-prefix-list</b> <i>name</i>	<p>(MX Series routers only) Match the source prefixes in the specified prefix list. Specify a prefix list name defined at the <b>[edit policy-options prefix-list <i>prefix-list-name</i>]</b> hierarchy level.</p> <p><b>NOTE:</b> VPLS prefix lists support only IPv4 addresses. IPv6 addresses included in a VPLS prefix list will be discarded.</p>
<b>source-prefix-list</b> <i>name</i> <b>except</b>	(MX Series routers only) Do not match the source prefixes in the specified prefix list. For more information, see the <b>source-prefix-list</b> match condition.
<b>tcp-flags</b> <i>flags</i>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> <li>• <b>fin</b> (0x01)</li> <li>• <b>syn</b> (0x02)</li> <li>• <b>rst</b> (0x04)</li> <li>• <b>push</b> (0x08)</li> <li>• <b>ack</b> (0x10)</li> <li>• <b>urgent</b> (0x20)</li> </ul> <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>If you configure this match condition for IPv6 traffic, we recommend that you also configure the <b>next-header tcp</b> match condition in the same term to specify that the TCP protocol is being used on the port.</p>
<b>traffic-type</b> <i>type-name</i>	(MX Series routers only) Traffic type. Specify <b>broadcast</b> , <b>multicast</b> , <b>unknown-unicast</b> , or <b>known-unicast</b> .
<b>traffic-type-except</b> <i>type-name</i>	(MX Series routers only) Do not match on the traffic type. Specify <b>broadcast</b> , <b>multicast</b> , <b>unknown-unicast</b> , or <b>known-unicast</b> .
<b>user-vlan-1p-priority</b> <i>number</i>	<p>(MX Series routers only) Match on the IEEE 802.1p user priority bits in the customer VLAN tag (the inner tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <b>learn-vlan-1p-priority</b> match condition.</p>
<b>user-vlan-1p-priority-except</b> <i>number</i>	(MX Series routers only) Do not match on the IEEE 802.1p user priority bits. For details, see the <b>user-vlan-1p-priority</b> match condition.



Table 20: Standard Firewall Filter Match Conditions for VPLS Traffic (*continued*)

Match Condition	Description
<code>user-vlan-id number</code>	(MX Series routers only) Match the first VLAN identifier that is part of the payload.
<code>user-vlan-id-except number</code>	(MX Series routers only) Do not match on the first VLAN identifier that is part of the payload.
<code>vlan-ether-type value</code>	VLAN Ethernet type field of a VPLS packet.
<code>vlan-ether-type-except value</code>	Do not match on the VLAN Ethernet type field of a VPLS packet.

- Related Documentation**
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
  - [Standard Firewall Filter Terminating Actions on page 293](#)
  - [Standard Firewall Filter Nonterminating Actions on page 294](#)

## Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic

You can configure a standard stateless firewall filter with match conditions for Layer 2 circuit cross-connect (CCC) traffic (**family ccc**).

The following restrictions apply to firewall filters for Layer 2 CCC traffic:

- The **input-list filter-names** and **output-list filter-names** statements for firewall filters for the **ccc** protocol family are supported on all interfaces with the exception of management interfaces and internal Ethernet interfaces (**fxp** or **em0**), loopback interfaces (**lo0**), and USB modem interfaces (**umd**).
- On MX Series routers only, you cannot apply a Layer 2 CCC stateless firewall filter (a firewall filter configured at the **[edit firewall filter family ccc]** hierarchy level) as an output filter. On MX Series routers, firewall filters configured for the **family ccc** statement can be applied only as input filters.

[Table 21 on page 285](#) describes the **match-conditions** you can configure at the **[edit firewall family ccc filter filter-name term term-name from]** hierarchy level.

Table 21: Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic

Match Condition	Description
<code>apply-groups</code>	Specify which groups to inherit configuration data from. You can specify more than one group name. You must list them in order of inheritance priority. The configuration data in the first group takes priority over the data in subsequent groups.
<code>apply-groups-except</code>	Specify which groups not to inherit configuration data from. You can specify more than one group name.



Table 21: Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic (*continued*)

Match Condition	Description
<b>destination-mac-address address</b>	<p>(MX Series routers only) Match the destination media access control (MAC) address of a virtual private LAN service (VPLS) packet.</p> <p>To have packets correctly evaluated by this match condition when applied to egress traffic flowing over a CCC circuit from a logical interface on an I-chip DPC in a Layer 2 virtual private network (VPN) routing instance, you must make a configuration change to the Layer 2 VPN routing instance. You must explicitly disable the use of a control word for traffic flowing out over a Layer 2 circuit. The use of a control word is enabled by default for Layer 2 VPN routing instances to support the emulated virtual circuit (VC) encapsulation for Layer 2 circuits.</p> <p>To explicitly disable the use of a control word for Layer 2 VPNs, include the <b>no-control-word</b> statement at either of the following hierarchy levels:</p> <ul style="list-style-type: none"> <li>• <b>[edit routing-instances routing-instance-name protocols l2vpn]</b></li> <li>• <b>[edit logical-systems logical-system-name routing-instances routing-instance-name protocols l2vpn]</b></li> </ul> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see “Disabling the Control Word for Layer 2 VPNs” in the Junos OS VPNs Configuration Guide.</p>
<b>forwarding-class class</b>	Forwarding class. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .
<b>forwarding-class-except class</b>	Do not match on the forwarding class. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .
<b>interface-group group-number</b>	<p>Match the logical interface on which the packet was received to the specified interface group or set of interface groups. For <b>group-number</b>, specify a single value or a range of values from 0 through 255.</p> <p>To assign a logical interface to an interface group <b>group-number</b>, specify the <b>group-number</b> at the <b>[interfaces interface-name unit number family family filter group]</b> hierarchy level.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For more information, see “Filtering Packets Received on a Set of Interface Groups Overview” on page 57.</p>
<b>interface-group-except number</b>	<p>Do not match the logical interface on which the packet was received to the specified interface group or set of interface groups. For details, see the <b>interface-group</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>learn-vlan-1p-priority number</b>	<p>(MX Series routers only) Match on the IEEE 802.1p learned VLAN priority bits in the provider VLAN tag (the only tag in a single-tag frame with 802.1Q VLAN tags or the outer tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <b>user-vlan-1p-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>



Table 21: Standard Firewall Filter Match Conditions for Layer 2 CCC Traffic (*continued*)

Match Condition	Description
<b>learn-vlan-1p-priority-except number</b>	<p>(MX Series routers only) Do not match on the IEEE 802.1p learned VLAN priority bits. For details, see the <b>learn-vlan-1p-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>loss-priority level</b>	<p>Packet loss priority (PLP) level. Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>loss-priority-except level</b>	<p>Do not match on the packet loss priority level. Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p> <p>For information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>user-vlan-1p-priority number</b>	<p>(MX Series routers only) Match on the IEEE 802.1p user priority bits in the customer VLAN tag (the inner tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <b>learn-vlan-1p-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>
<b>user-vlan-1p-priority-except number</b>	<p>(MX Series routers only) Do not match on the IEEE 802.1p user priority bits. For details, see the <b>user-vlan-1p-priority</b> match condition.</p> <p><b>NOTE:</b> This match condition is not supported on PTX series packet transport switches.</p>

- Related Documentation**
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
  - [Standard Firewall Filter Terminating Actions on page 293](#)
  - [Standard Firewall Filter Nonterminating Actions on page 294](#)

## Standard Firewall Filter Match Conditions for Layer 2 Bridging Traffic

On MX Series routers only, you can configure a standard stateless firewall filter with match conditions for Layer 2 bridging traffic (**family bridge**). [Table 22 on page 288](#) describes



the **match-conditions** you can configure at the [edit firewall family bridge filter *filter-name* term *term-name* from] hierarchy level.

**Table 22: Standard Firewall Filter Match Conditions for Layer 2 Bridging (MX Series 3D Universal Edge Routers Only)**

Match Condition	Description
<b>destination-mac-address address</b>	Destination media access control (MAC) address of a Layer 2 packet in a bridging environment.
<b>destination-port number</b>	TCP or UDP destination port field. You cannot specify both the <b>port</b> and <b>destination-port</b> match conditions in the same term.
<b>destination-port-except</b>	Do not match the TCP/UDP destination port.
<b>destination-prefix-list</b>	Match the IP destination prefixes in a named list.
<b>dscp number</b>	<p>Differentiated Services code point (DSCP). The DiffServ protocol uses the type-of-service (ToS) byte in the IP header. The most significant 6 bits of this byte form the DSCP. For more information, see the Junos OS Class of Service Configuration Guide.</p> <p>You can specify a numeric value from <b>0</b> through <b>63</b>. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> <li>• RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: <b>ef</b> (46).</li> <li>• RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points:</li> </ul> <p><b>af11</b> (10), <b>af12</b> (12), <b>af13</b> (14),</p> <p><b>af21</b> (18), <b>af22</b> (20), <b>af23</b> (22),</p> <p><b>af31</b> (26), <b>af32</b> (28), <b>af33</b> (30),</p> <p><b>af41</b> (34), <b>af42</b> (36), <b>af43</b> (38)</p>
<b>dscp-except number</b>	Do not match on the DSCP number. For more information, see the <b>dscp-except</b> match condition.
<b>ether-type value</b>	<p>Match the 2-octet IEEE 802.3 Length/EtherType field to the specified value or list of values.</p> <p>You can specify decimal or hexadecimal values from 0 through 65535 (0xFFFF). A value from 0 through 1500 (0x05DC) specifies the length of an Ethernet Version 1 frame. A value from 1536 (0x0600) through 65535 specifies the EtherType (nature of the MAC client protocol) of an Ethernet Version 2 frame.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the hexadecimal values are also listed): <b>aarp</b> (0x80F3), <b>appletalk</b> (0x809B), <b>arp</b> (0x0806), <b>ipv4</b> (0x0800), <b>ipv6</b> (0x86DD), <b>mpls-multicast</b> (0x8848), <b>mpls-unicast</b> (0x8847), <b>oam</b> (0x8902), <b>ppp</b> (0x880B), <b>pppoe-discovery</b> (0x8863), <b>pppoe-session</b> (0x8864), <b>sna</b> (0x80D5).</p>
<b>ether-type-except value</b>	<p>Do not match the 2-octet IEEE 802.3 Length/EtherType field to the specified value or list of values.</p> <p>For details about specifying the <b>values</b>, see the <b>ether-type</b> match condition.</p>



Table 22: Standard Firewall Filter Match Conditions for Layer 2 Bridging (MX Series 3D Universal Edge Routers Only) (*continued*)

Match Condition	Description
<b>forwarding class</b> <i>class</i>	Forwarding class. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .
<b>forwarding-class-except class</b>	Ethernet type field of a Layer 2 packet environment. Specify <b>assured-forwarding</b> , <b>best-effort</b> , <b>expedited-forwarding</b> , or <b>network-control</b> .
<b>icmp-code</b> <i>message-code</i>	<p>Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>ip-protocol icmp</b>, <b>ip-protocol icmp6</b>, or <b>ip-protocol icmpv6</b> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <b>icmp-type message-type</b> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> <li>parameter-problem: <b>ip6-header-bad</b> (0), <b>unrecognized-next-header</b> (1), <b>unrecognized-option</b> (2)</li> <li>time-exceeded: <b>ttl-eq-zero-during-reassembly</b> (1), <b>ttl-eq-zero-during-transit</b> (0)</li> <li>destination-unreachable: <b>address-unreachable</b> (3), <b>administratively-prohibited</b> (1), <b>no-route-to-destination</b> (0), <b>port-unreachable</b> (4)</li> </ul>
<b>icmp-code-except message-code</b>	Do not match the ICMP message code field. For details, see the <b>icmp-code</b> match condition.
<b>icmp-type</b> <i>message-type</i>	<p>Match the ICMP message type field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>ip-protocol icmp</b>, <b>ip-protocol icmp6</b>, or <b>ip-protocol icmpv6</b> match condition in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>destination-unreachable</b> (1), <b>echo-reply</b> (129), <b>echo-request</b> (128), <b>membership-query</b> (130), <b>membership-report</b> (131), <b>membership-termination</b> (132), <b>neighbor-advertisement</b> (136), <b>neighbor-solicit</b> (135), <b>node-information-reply</b> (140), <b>node-information-request</b> (139), <b>packet-too-big</b> (2), <b>parameter-problem</b> (4), <b>redirect</b> (137), <b>router-advertisement</b> (134), <b>router-renumbering</b> (138), <b>router-solicit</b> (133), or <b>time-exceeded</b> (3).</p>
<b>icmp-type-except message-type</b>	Do not match the ICMP message type field. For details, see the <b>icmp-type</b> match condition.
<b>interface</b> <i>interface-name</i>	<p>Interface on which the packet was received. You can configure a match condition that matches packets based on the interface on which they were received.</p> <p><b>NOTE:</b> If you configure this match condition with an interface that does not exist, the term does not match any packet.</p>



Table 22: Standard Firewall Filter Match Conditions for Layer 2 Bridging (MX Series 3D Universal Edge Routers Only) (*continued*)

Match Condition	Description
<b>interface-group</b> <i>group-number</i>	<p>Match the logical interface on which the packet was received to the specified interface group or set of interface groups. For <i>group-number</i>, specify a single value or a range of values from 0 through 255.</p> <p>To assign a logical interface to an interface group <i>group-number</i>, specify the <i>group-number</i> at the [interfaces <i>interface-name</i> unit <i>number</i> family <i>family</i> filter <i>group</i>] hierarchy level.</p> <p>For more information, see <a href="#">“Filtering Packets Received on a Set of Interface Groups Overview” on page 57</a>.</p>
<b>interface-group-except</b> <i>number</i>	Do not match the logical interface on which the packet was received to the specified interface group or set of interface groups. For details, see the <b>interface-group</b> match condition.
<b>interface-set</b> <i>interface-set-name</i>	<p>Match the interface on which the packet was received to the specified interface set.</p> <p>To define an interface set, include the <b>interface-set</b> statement at the [edit firewall] hierarchy level. For more information, see <a href="#">“Filtering Packets Received on an Interface Set Overview” on page 58</a>.</p>
<b>ip-address</b> <i>address</i>	32-bit address that supports the standard syntax for IPv4 addresses.
<b>ip-destination-address</b> <i>address</i>	32-bit address that is the final destination node address for the packet.
<b>ip-precedence</b> <i>ip-precedence-field</i>	IP precedence field. In place of the numeric field value, you can specify one of the following text synonyms (the field values are also listed): <b>critical-ecp</b> (0xa0), <b>flash</b> (0x60), <b>flash-override</b> (0x80), <b>immediate</b> (0x40), <b>internet-control</b> (0xc0), <b>net-control</b> (0xe0), <b>priority</b> (0x20), or <b>routine</b> (0x00).
<b>ip-precedence-except</b> <i>ip-precedence-field</i>	Do not match on the IP precedence field.
<b>ip-protocol</b> <i>number</i>	IP protocol field.
<b>ip-protocol-except</b>	Do not match the IP protocol type.
<b>ip-source-address</b> <i>address</i>	IP address of the source node sending the packet.
<b>isid</b> <i>number</i>	(Supported with Provider Backbone Bridging [PBB]) Match internet service identifier.
<b>isid-dei</b> <i>number</i>	(Supported with PBB) Match the Internet service identifier drop eligibility indicator (DEI) bit.
<b>isid-dei-except</b> <i>number</i>	(Supported with PBB) Do not match the Internet service identifier DEI bit.
<b>isid-priority-code-point</b> <i>number</i>	(Supported with PBB) Match the Internet service identifier priority code point.
<b>isid-priority-code-point-except</b> <i>number</i>	(Supported with PBB) Do not match the Internet service identifier priority code point.



Table 22: Standard Firewall Filter Match Conditions for Layer 2 Bridging (MX Series 3D Universal Edge Routers Only) (*continued*)

Match Condition	Description
<b>learn-vlan-1p-priority value</b>	<p>(MX Series routers only) Match on the IEEE 802.1p learned VLAN priority bits in the provider VLAN tag (the only tag in a single-tag frame with 802.1Q VLAN tags or the outer tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <b>user-vlan-1p-priority</b> match condition.</p>
<b>learn-vlan-1p-priority-except value</b>	(MX Series routers only) Do not match on the IEEE 802.1p learned VLAN priority bits. For details, see the <b>learn-vlan-1p-priority</b> match condition.
<b>learn-vlan-dei number</b>	(Supported with bridging) Match user virtual LAN (VLAN) identifier DEI bit.
<b>learn-vlan-dei-except number</b>	(Supported with bridging) Do not match user VLAN identifier DEI bit.
<b>learn-vlan-id number</b>	VLAN identifier used for MAC learning.
<b>learn-vlan-id-except number</b>	Do not match on the VLAN identifier used for MAC learning.
<b>loss-priority level</b>	<p>Packet loss priority (PLP) level. Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>loss-priority-except level</b>	<p>Do not match on the packet loss priority level. Specify a single level or multiple levels: <b>low</b>, <b>medium-low</b>, <b>medium-high</b>, or <b>high</b>.</p> <p>For information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>
<b>port number</b>	TCP or UDP source or destination port. You cannot specify both the <b>port</b> match condition and either the <b>destination-port</b> or <b>source-port</b> match conditions in the same term.
<b>source-mac-address address</b>	Source MAC address of a Layer 2 packet.
<b>source-port number</b>	TCP or UDP source port field. You cannot specify the <b>port</b> and <b>source-port</b> match conditions in the same term.
<b>source-port-except</b>	Do not match the TCP/UDP source port.



Table 22: Standard Firewall Filter Match Conditions for Layer 2 Bridging (MX Series 3D Universal Edge Routers Only) (*continued*)

Match Condition	Description
<b>tcp-flags flags</b>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> <li>• <b>fin</b> (0x01)</li> <li>• <b>syn</b> (0x02)</li> <li>• <b>rst</b> (0x04)</li> <li>• <b>push</b> (0x08)</li> <li>• <b>ack</b> (0x10)</li> <li>• <b>urgent</b> (0x20)</li> </ul> <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>Configuring the <b>tcp-flags</b> match condition requires that you configure the <b>next-header-tcp</b> match condition.</p>
<b>traffic-type type</b>	Traffic type. Specify <b>broadcast</b> , <b>multicast</b> , <b>unknown-unicast</b> , or <b>known-unicast</b> .
<b>traffic-type-except type</b>	Do not match on the traffic type.
<b>user-vlan-1p-priority value</b>	<p>(MX Series routers only) Match on the IEEE 802.1p user priority bits in the customer VLAN tag (the inner tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <b>learn-vlan-1p-priority</b> match condition.</p>
<b>user-vlan-1p-priority-except value</b>	(MX Series routers only) Do not match on the IEEE 802.1p user priority bits. For details, see the <b>user-vlan-1p-priority</b> match condition.
<b>user-vlan-id number</b>	(MX Series routers only) Match the first VLAN identifier that is part of the payload.
<b>user-vlan-id-except number</b>	(MX Series routers only) Do not match on the first VLAN identifier that is part of the payload.
<b>vlan-ether-type value</b>	VLAN Ethernet type field of a Layer 2 bridging packet.
<b>vlan-ether-type-except value</b>	Do not match on the VLAN Ethernet type field of a Layer 2 bridging packet.

- Related Documentation**
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
  - [Standard Firewall Filter Terminating Actions on page 293](#)
  - [Standard Firewall Filter Nonterminating Actions on page 294](#)



## Standard Firewall Filter Terminating Actions

Standard stateless firewall filters support different sets of terminating actions for each protocol family.



**NOTE:** You cannot configure the next term action with a *terminating* action in the same filter term. However, you can configure the next term action with another *nonterminating* action in the same filter term.

Table 23 on page 293 describes the terminating actions you can specify in a standard firewall filter term.

**Table 23: Terminating Actions for Standard Firewall Filters**

Terminating Action	Description	Protocols
<b>accept</b>	Accept the packet.	<ul style="list-style-type: none"> <li>family any</li> <li>family inet</li> <li>family inet6</li> <li>family mpls</li> <li>family vpls</li> <li>family ccc</li> <li>family bridge</li> </ul>
<b>discard</b>	Discard a packet silently, without sending an Internet Control Message Protocol (ICMP) message. Discarded packets are available for logging and sampling.	<ul style="list-style-type: none"> <li>family any</li> <li>family inet</li> <li>family inet6</li> <li>family mpls</li> <li>family vpls</li> <li>family ccc</li> <li>family bridge</li> </ul>
<b>logical-system</b> <i>logical-system-name</i>	Direct the packet to the specified logical system.  <b>NOTE:</b> This action is not supported on PTX series packet transport switches.	<ul style="list-style-type: none"> <li>family inet</li> <li>family inet6</li> </ul>



Table 23: Terminating Actions for Standard Firewall Filters (*continued*)

Terminating Action	Description	Protocols
<code>reject message-type</code>	<p>Reject the packet and return an ICMPv4 or ICMPv6 message:</p> <ul style="list-style-type: none"> <li>If no <i>message-type</i> is specified, a <b>destination unreachable</b> message is returned by default.</li> <li>If <b>tcp-reset</b> is specified as the <i>message-type</i>, <b>tcp-reset</b> is returned only if the packet is a TCP packet. Otherwise, the <b>administratively-prohibited</b> message, which has a value of 13, is returned.</li> <li>If any other <i>message-type</i> is specified, that message is returned.</li> </ul> <p><b>NOTE:</b> Rejected packets can be sampled or logged if you configure the <b>sample</b> or <b>syslog</b> action.</p> <p>The <i>message-type</i> can be one of the following values: <b>address-unreachable</b>, <b>administratively-prohibited</b>, <b>bad-host-tos</b>, <b>bad-network-tos</b>, <b>beyond-scope</b>, <b>fragmentation-needed</b>, <b>host-prohibited</b>, <b>host-unknown</b>, <b>host-unreachable</b>, <b>network-prohibited</b>, <b>network-unknown</b>, <b>network-unreachable</b>, <b>no-route</b>, <b>port-unreachable</b>, <b>precedence-cutoff</b>, <b>precedence-violation</b>, <b>protocol-unreachable</b>, <b>source-host-isolated</b>, <b>source-route-failed</b>, or <b>tcp-reset</b>.</p>	<ul style="list-style-type: none"> <li>family inet</li> <li>family inet6</li> </ul>
<code>routing-instance</code> <code>routing-instance-name</code>	<p>Direct the packet to the specified routing instance.</p> <p><b>NOTE:</b> This action is not supported on PTX series packet transport switches.</p>	<ul style="list-style-type: none"> <li>family inet</li> <li>family inet6</li> </ul>
<code>topology</code> <code>topology-name</code>	<p>Direct the packet to the specified topology.</p> <p><b>NOTE:</b> This action is not supported on PTX series packet transport switches.</p> <p>Each routing instance (master or virtual-router) supports one default topology to which all forwarding classes are forwarded. For Multitopology Routing, you can configure a firewall filter on the ingress interface to match a specific forwarding class, such as expedited forwarding, with a specific topology. The traffic that matches the specified forwarding class is then added to the routing table for that topology.</p>	<ul style="list-style-type: none"> <li>family inet</li> <li>family inet6</li> </ul>

- Related Documentation**
- Guidelines for Configuring Standard Firewall Filters on page 19
  - Standard Firewall Filter Nonterminating Actions on page 294

## Standard Firewall Filter Nonterminating Actions

Standard stateless firewall filters support different sets of nonterminating actions for each protocol family.



**NOTE:** You cannot configure the next term action with a *terminating* action in the same filter term. However, you can configure the next term action with another *nonterminating* action in the same filter term.

Table 24 on page 295 describes the nonterminating actions you can configure for a standard firewall filter term.



Table 24: Nonterminating Actions for Standard Firewall Filters

Nonterminating Action	Description	Protocol Families
<code>count</code> <i>counter-name</i>	Count the packet in the named counter.	<ul style="list-style-type: none"><li>• <code>family any</code></li><li>• <code>family inet</code></li><li>• <code>family inet6</code></li><li>• <code>family mpls</code></li><li>• <code>family vpls</code></li><li>• <code>family ccc</code></li><li>• <code>family bridge</code></li></ul>



Table 24: Nonterminating Actions for Standard Firewall Filters (*continued*)

Nonterminating Action	Description	Protocol Families
<b>dscp value</b>	<p>Set the IPv4 Differentiated Services code point (DSCP) bit. You can specify a numerical value from <b>0</b> through <b>63</b>. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.</p> <p>The default DSCP value is best effort, that is, <b>be</b> or <b>0</b>.</p> <p>You can also specify on the following text synonyms:</p> <ul style="list-style-type: none"> <li>• <b>af11</b>—Assured forwarding class 1, low drop precedence</li> <li>• <b>af12</b>—Assured forwarding class 1, medium drop precedence</li> <li>• <b>af13</b>—Assured forwarding class 1, high drop precedence</li> <li>• <b>af21</b>—Assured forwarding class 2, low drop precedence</li> <li>• <b>af22</b>—Assured forwarding class 2, medium drop precedence</li> <li>• <b>af23</b>—Assured forwarding class 2, high drop precedence</li> <li>• <b>af31</b>—Assured forwarding class 3, low drop precedence</li> <li>• <b>af32</b>—Assured forwarding class 3, medium drop precedence</li> <li>• <b>af33</b>—Assured forwarding class 3, high drop precedence</li> <li>• <b>af41</b>—Assured forwarding class 4, low drop precedence</li> <li>• <b>af42</b>—Assured forwarding class 4, medium drop precedence</li> <li>• <b>af43</b>—Assured forwarding class 4, high drop precedence</li> <li>• <b>be</b>—Best effort</li> <li>• <b>cs0</b>—Class selector 0</li> <li>• <b>cs1</b>—Class selector 1</li> <li>• <b>cs2</b>—Class selector 2</li> <li>• <b>cs3</b>—Class selector 3</li> <li>• <b>cs4</b>—Class selector 4</li> <li>• <b>cs5</b>—Class selector 5</li> <li>• <b>cs6</b>—Class selector 6</li> <li>• <b>cs7</b>—Class selector 7</li> <li>• <b>ef</b>—Expedited forwarding</li> </ul> <p><b>NOTE:</b> This action is not supported on PTX Series packet transport switches.</p> <p><b>NOTE:</b> The actions <b>dscp 0</b> or <b>dscp be</b> are supported only on T320, T640, T1600, TX Matrix, TX Matrix Plus, and M320 routers and on the 10-Gigabit Ethernet Modular Port Concentrators (MPC), 60-Gigabit Ethernet MPC, 60-Gigabit Ethernet Queuing MPC, and 60-Gigabit Ethernet Enhanced Queuing MPC on MX Series routers. However, these actions are not supported on Enhanced III Flexible PIC Concentrators (FPCs) on M320 routers.</p> <p><b>NOTE:</b> On T4000 routers, the <b>dscp 0</b> action is not supported during the interoperation between a T1600 Enhanced Scaling Type 4 FPC and a T4000 Type 5 FPC.</p>	<b>family inet</b>



Table 24: Nonterminating Actions for Standard Firewall Filters (*continued*)

Nonterminating Action	Description	Protocol Families
<b>forwarding-class</b> <i>class-name</i>	Classify the packet to the named forwarding class: <ul style="list-style-type: none"> <li><i>forwarding-class-name</i></li> <li><b>assured-forwarding</b></li> <li><b>best-effort</b></li> <li><b>expedited-forwarding</b></li> <li><b>network-control</b></li> </ul>	<ul style="list-style-type: none"> <li><b>family any</b></li> <li><b>family inet</b></li> <li><b>family inet6</b></li> <li><b>family mpls</b></li> <li><b>family vpls</b></li> <li><b>family ccc</b></li> <li><b>family bridge</b></li> </ul>
<b>ipsec-sa</b> <i>ipsec-sa</i>	Use the specified IPsec security association.  <b>NOTE:</b> This action is not supported on MX Series routers, Type 5 FPCs on T4000 routers, and PTX Series packet transport switches.	<b>family inet</b>
<b>load-balance</b> <i>group-name</i>	Use the specified load-balancing group.  <b>NOTE:</b> This action is not supported on MX Series routers or PTX Series packet transport switches.	<b>family inet</b>
<b>log</b>	Log the packet header information in a buffer within the Packet Forwarding Engine. You can access this information by issuing the <b>show firewall log</b> command at the command-line interface (CLI).	<ul style="list-style-type: none"> <li><b>family inet</b></li> <li><b>family inet6</b></li> </ul>
<b>logical-system</b> <i>logical-system-name</i>	Direct packets to a specific logical system.	<ul style="list-style-type: none"> <li><b>family inet</b></li> <li><b>family inet6</b></li> </ul>
<b>loss-priority</b> (high   medium-high   medium-low   low)	<p>Set the packet loss priority (PLP) level.</p> <p>You cannot also configure the <b>three-color-policer</b> nonterminating action for the same firewall filter term. These two nonterminating actions are mutually exclusive.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs), you must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can only configure the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p>	<ul style="list-style-type: none"> <li><b>family any</b></li> <li><b>family inet</b></li> <li><b>family inet6</b></li> <li><b>family mpls</b></li> <li><b>family vpls</b></li> <li><b>family ccc</b></li> <li><b>family bridge</b></li> </ul>
<b>next-hop-group</b> <i>group-name</i>	Use the specified next-hop group.	<b>family inet</b>
<b>next-interface</b> <i>interface-name</i>	(MX Series) Direct packets to the specified outgoing interface.	<ul style="list-style-type: none"> <li><b>family inet</b></li> <li><b>family inet6</b></li> </ul>
<b>next-ip</b> <i>ip-address</i>	(MX Series) Direct packets to the specified destination IPv4 address.	<b>family inet</b>



Table 24: Nonterminating Actions for Standard Firewall Filters (*continued*)

Nonterminating Action	Description	Protocol Families
<b>next-ip6</b> <i>ipv6-address</i>	(MX Series) Direct packets to the specified destination IPv6 address.	<b>family inet6</b>
<b>packet-mode</b>	Updates a bit field in the packet key buffer, which specifies traffic that will bypass flow-based forwarding. Packets with the <b>packet-mode</b> action modifier follow the packet-based forwarding path and bypass flow-based forwarding completely. For more information about selective stateless packet-based services, see the <i>Junos OS Security Configuration Guide</i> .	<b>family any</b>
<b>policer</b> <i>policer-name</i>	Name of policer to use to rate-limit traffic.  <b>NOTE:</b> For IPv6, applies to SRX100, SRX210, SRX220, SRX240, and SRX650 devices only.	<ul style="list-style-type: none"> <li>• <b>family any</b></li> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> <li>• <b>family mpls</b></li> <li>• <b>family vpls</b></li> <li>• <b>family ccc</b></li> <li>• <b>family bridge</b></li> </ul>
<b>port-mirror</b>	Port-mirror the packet based on the specified family. Supported on M120 routers, M320 routers configured with Enhanced III FPCs, and MX Series routers only.	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> <li>• <b>family vpls</b></li> <li>• <b>family ccc</b></li> <li>• <b>family bridge</b></li> </ul>
<b>prefix-action</b> <i>action-name</i>	Count or police packets based on the specified action name.  <b>NOTE:</b> This action is not supported on PTX Series packet transport switches.	<b>family inet</b>
<b>routing-instance</b> <i>routing-instance-name</i>	Direct packets to the specified routing instance.	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> </ul>
<b>sample</b>	Sample the packet.  <b>NOTE:</b> The Junos OS does not sample packets originating from the router. If you configure a filter and apply it to the output side of an interface, then only the transit packets going through that interface are sampled. Packets that are sent from the Routing Engine to the Packet Forwarding Engine are not sampled.	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> <li>• <b>family mpls</b></li> </ul>
<b>service-accounting</b>	Count the packet for service accounting. The count is applied to a specific named counter ( <b>_junos-dyn-service-counter</b> ) that RADIUS can obtain.  <b>NOTE:</b> This action is not supported on T4000 Type 5 FPCs and PTX Series packet transport switches.	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> </ul>



Table 24: Nonterminating Actions for Standard Firewall Filters (*continued*)

Nonterminating Action	Description	Protocol Families
<b>service-filter-hit</b>	<p>(Only if the <b>service-filter-hit</b> flag is marked by a previous filter in the current type of chained filters) Direct the packet to the next type of filters.</p> <p>Indicate to subsequent filters in the chain that the packet was already processed. This action, coupled with the <b>service-filter-hit</b> match condition in receiving filters, helps to streamline filter processing.</p> <p><b>NOTE:</b> This action is not supported on T4000 Type 5 FPCs and PTX Series packet transport switches.</p>	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> </ul>
<b>syslog</b>	Log the packet to the system log file.	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> </ul>
<b>three-color-policer</b> <b>(single-rate  </b> <b>two-rate)</b> <b>policer-name</b>	<p>Police the packet using the specified single-rate or two-rate three-color-policer.</p> <p>You cannot also configure the <b>loss-priority</b> action for the same firewall filter term. These two actions are mutually exclusive.</p>	<ul style="list-style-type: none"> <li>• <b>family inet</b></li> <li>• <b>family inet6</b></li> <li>• <b>family mpls</b></li> <li>• <b>family vpls</b></li> <li>• <b>family ccc</b></li> <li>• <b>family bridge</b></li> </ul>



Table 24: Nonterminating Actions for Standard Firewall Filters (*continued*)

Nonterminating Action	Description	Protocol Families
<b>traffic-class value</b>	<p>Specify the traffic-class code point. You can specify a numerical value from <b>0</b> through <b>63</b>. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.</p> <p>The default traffic-class value is best effort, that is, <b>be</b> or <b>0</b>.</p> <p>In place of the numeric value, you can specify one of the following text synonyms:</p> <ul style="list-style-type: none"> <li>• <b>af11</b>—Assured forwarding class 1, low drop precedence</li> <li>• <b>af12</b>—Assured forwarding class 1, medium drop precedence</li> <li>• <b>af13</b>—Assured forwarding class 1, high drop precedence</li> <li>• <b>af21</b>—Assured forwarding class 2, low drop precedence</li> <li>• <b>af22</b>—Assured forwarding class 2, medium drop precedence</li> <li>• <b>af23</b>—Assured forwarding class 2, high drop precedence</li> <li>• <b>af31</b>—Assured forwarding class 3, low drop precedence</li> <li>• <b>af32</b>—Assured forwarding class 3, medium drop precedence</li> <li>• <b>af33</b>—Assured forwarding class 3, high drop precedence</li> <li>• <b>af41</b>—Assured forwarding class 4, low drop precedence</li> <li>• <b>af42</b>—Assured forwarding class 4, medium drop precedence</li> <li>• <b>af43</b>—Assured forwarding class 4, high drop precedence</li> <li>• <b>be</b>—Best effort</li> <li>• <b>cs0</b>—Class selector 0</li> <li>• <b>cs1</b>—Class selector 1</li> <li>• <b>cs2</b>—Class selector 2</li> <li>• <b>cs3</b>—Class selector 3</li> <li>• <b>cs4</b>—Class selector 4</li> <li>• <b>cs5</b>—Class selector 5</li> <li>• <b>cs6</b>—Class selector 6</li> <li>• <b>cs7</b>—Class selector 7</li> <li>• <b>ef</b>—Expedited forwarding</li> </ul> <p><b>NOTE:</b> The actions <b>traffic-class 0</b> or <b>traffic-class be</b> are supported only on T Series and M320 routers and on the 10-Gigabit Ethernet Modular Port Concentrator (MPC), 60-Gigabit Ethernet MPC, 60-Gigabit Ethernet Queuing MPC, and 60-Gigabit Ethernet Enhanced Queuing MPC on MX Series routers. However, these actions are not supported on Enhanced III Flexible PIC Concentrators (FPCs) on M320 routers.</p>	<b>family inet6</b>

**Related Documentation**

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Terminating Actions on page 293](#)



# Standard Firewall Filter Match Conditions and Actions for ACX Series Routers

- [Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview on page 301](#)
- [Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers on page 303](#)
- [Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers on page 306](#)
- [Standard Firewall Filter Terminating Actions on ACX Series Routers on page 306](#)
- [Standard Firewall Filter Nonterminating Actions on ACX Series Routers on page 308](#)

## Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview

On ACX Series Universal Access Routers, you can configure firewall filters to filter packets and to perform an action on packets that match the filter. The match conditions specified to filter the packets are specific to the type of traffic being filtered.



**NOTE:** On ACX Series routers, the filter for the exiting traffic (egress filter) can be applied only for interface-specific instances of the firewall filter.

[Table 25 on page 301](#) describes the types of traffic for which you can configure standard stateless firewall filters.

**Table 25: Standard Firewall Filter Match Conditions by Protocol Family for ACX Series Routers**

Traffic Type	Hierarchy Level at Which Match Conditions Are Specified
Protocol-independent	<p><code>[edit firewall family any filter <i>filter-name</i> term <i>term-name</i>]</code></p> <p>No match conditions are supported for this traffic type on ACX Series routers.</p>



Table 25: Standard Firewall Filter Match Conditions by Protocol Family for ACX Series Routers (*continued*)

Traffic Type	Hierarchy Level at Which Match Conditions Are Specified
IPv4	<b>[edit firewall family inet filter <i>filter-name</i> term <i>term-name</i></b>  For the complete list of match conditions, see “ <a href="#">Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers</a> ” on page 303.
MPLS	<b>[edit firewall family mpls filter <i>filter-name</i> term <i>term-name</i>]</b>  For the complete list of match conditions, see “ <a href="#">Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers</a> ” on page 306.
Layer 2 CCC	<b>[edit firewall family ccc filter <i>filter-name</i> term <i>term-name</i>]</b>  No match conditions are supported for this traffic type on ACX Series routers.

Under the **then** statement for a standard stateless firewall filter term, you can specify the actions to be taken on a packet that matches the term.

[Table 26 on page 302](#) summarizes the types of actions you can specify in a standard stateless firewall filter term.

Table 26: Standard Firewall Filter Action Categories for ACX Series Routers

Type of Action	Description	Comment
Terminating	Halts all evaluation of a firewall filter for a specific packet. The router performs the specified action, and no additional terms are used to examine the packet.  You can specify only one <i>terminating action</i> in a standard firewall filter. You can, however, specify one terminating action with one or more <i>nonterminating actions</i> in a single term. For example, within a term, you can specify <b>accept</b> with <b>count</b> and <b>syslog</b> .	See “ <a href="#">Standard Firewall Filter Terminating Actions on ACX Series Routers</a> ” on page 306.
Nonterminating	Performs other functions on a packet (such as incrementing a counter, logging information about the packet header, sampling the packet data, or sending information to a remote host using the system log functionality), but any additional terms are used to examine the packet.	See “ <a href="#">Standard Firewall Filter Nonterminating Actions on ACX Series Routers</a> ” on page 308.

- Related Documentation**
- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
  - [Interface-Specific Firewall Filter Instances Overview on page 55](#)



## Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers

On ACX Series routers, you can configure a standard stateless firewall filter with match conditions for IP version 4 (IPv4) traffic (**family inet**). [Table 27 on page 303](#) describes the match conditions you can configure at the `[edit firewall family inet filter filter-name term term-name from]` hierarchy level.

**Table 27: Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers**

Match Condition	Description
<b>destination-address</b> <i>address</i>	<p>Match the IPv4 destination address field.</p> <p><b>NOTE:</b> On ACX Series routers, you can specify only one destination address. A list of IPv4 destination addresses is not supported.</p>
<b>destination-port</b> <i>number</i>	<p>Match the UDP or TCP destination port field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p><b>NOTE:</b> On ACX Series routers, you can specify only one destination port number. A list of port numbers is not supported.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>ldp</b> (646), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobileip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rkit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs</b> (49), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xmcp</b> (177).</p>
<b>dscp</b> <i>number</i>	<p>Match the Differentiated Services code point (DSCP). The DiffServ protocol uses the type-of-service (ToS) byte in the IP header. The most significant 6 bits of this byte form the DSCP. For more information, see the Junos OS Class of Service Configuration Guide.</p> <p>You can specify a numeric value from 0 through 63. To specify the value in hexadecimal form, include 0x as a prefix. To specify the value in binary form, include b as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> <li>• RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: <b>ef</b> (46).</li> <li>• RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points: <ul style="list-style-type: none"> <li>• <b>af11</b> (10), <b>af12</b> (12), <b>af13</b> (14)</li> <li>• <b>af21</b> (18), <b>af22</b> (20), <b>af23</b> (22)</li> <li>• <b>af31</b> (26), <b>af32</b> (28), <b>af33</b> (30)</li> <li>• <b>af41</b> (34), <b>af42</b> (36), <b>af43</b> (38)</li> </ul> </li> </ul>



**Table 27: Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers (*continued*)**

Match Condition	Description
<b>fragment-flags <i>number</i></b>	<p>(Ingress only) Match the three-bit IP fragmentation flags field in the IP header.</p> <p>In place of the numeric field value, you can specify one of the following keywords (the field values are also listed): <b>dont-fragment</b> (0x4), <b>more-fragments</b> (0x2), or <b>reserved</b> (0x8).</p>
<b>icmp-code <i>number</i></b>	<p>Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol icmp</b> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <b>icmp-type <i>message-type</i></b> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> <li>parameter-problem: <b>ip-header-bad</b> (0), <b>required-option-missing</b> (1)</li> <li>redirect: <b>redirect-for-host</b> (1), <b>redirect-for-network</b> (0), <b>redirect-for-tos-and-host</b> (3), <b>redirect-for-tos-and-net</b> (2)</li> <li>time-exceeded: <b>ttl-eq-zero-during-reassembly</b> (1), <b>ttl-eq-zero-during-transit</b> (0)</li> <li>unreachable: <b>communication-prohibited-by-filtering</b> (13), <b>destination-host-prohibited</b> (10), <b>destination-host-unknown</b> (7), <b>destination-network-prohibited</b> (9), <b>destination-network-unknown</b> (6), <b>fragmentation-needed</b> (4), <b>host-precedence-violation</b> (14), <b>host-unreachable</b> (1), <b>host-unreachable-for-TOS</b> (12), <b>network-unreachable</b> (0), <b>network-unreachable-for-TOS</b> (11), <b>port-unreachable</b> (3), <b>precedence-cutoff-in-effect</b> (15), <b>protocol-unreachable</b> (2), <b>source-host-isolated</b> (8), <b>source-route-failed</b> (5)</li> </ul>
<b>icmp-type <i>number</i></b>	<p>Match the ICMP message type field.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol icmp</b> match condition in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>echo-reply</b> (0), <b>echo-request</b> (8), <b>info-reply</b> (16), <b>info-request</b> (15), <b>mask-request</b> (17), <b>mask-reply</b> (18), <b>parameter-problem</b> (12), <b>redirect</b> (5), <b>router-advertisement</b> (9), <b>router-solicit</b> (10), <b>source-quench</b> (4), <b>time-exceeded</b> (11), <b>timestamp</b> (13), <b>timestamp-reply</b> (14), or <b>unreachable</b> (3).</p>
<b>ip-options <i>values</i></b>	<p>Match the 8-bit IP option field, if present, to the specified value.</p> <p>ACX Series routers support only the <b>ip-options_any</b> match condition, which ensures that the packets are sent to the Packet Forwarding Engine for processing.</p> <p><b>NOTE:</b> On ACX Series routers, you can specify only one IP option value. Configuring multiple values is not supported.</p>



Table 27: Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers (*continued*)

Match Condition	Description
<b>precedence</b> <i>ip-precedence-field</i>	<p>Match the IP precedence field.</p> <p>In place of the numeric field value, you can specify one of the following text synonyms (the field values are also listed): <b>critical-ecp</b> (0xa0), <b>flash</b> (0x60), <b>flash-override</b> (0x80), <b>immediate</b> (0x40), <b>internet-control</b> (0xc0), <b>net-control</b> (0xe0), <b>priority</b> (0x20), or <b>routine</b> (0x00). You can specify precedence in hexadecimal, binary, or decimal form.</p>
<b>protocol number</b>	<p>Match the IP protocol type field. In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ip6</b> (41), <b>ospf</b> (89), <b>pim</b> (103), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrp</b> (112).</p>
<b>source-address address</b>	Match the IPv4 address of the source node sending the packet.
<b>source-port number</b>	<p>Match the UDP or TCP source port field.</p> <p>If you configure this match condition for IPv4 traffic, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed with the <b>destination-port number</b> match condition.</p>
<b>tcp-flags value</b>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> <li>• <b>fin</b> (0x01)</li> <li>• <b>syn</b> (0x02)</li> <li>• <b>rst</b> (0x04)</li> <li>• <b>push</b> (0x08)</li> <li>• <b>ack</b> (0x10)</li> <li>• <b>urgent</b> (0x20)</li> </ul> <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>For combined bit-field match conditions, see the <b>tcp-initial</b> match conditions.</p> <p>If you configure this match condition, we recommend that you also configure the <b>protocol tcp</b> match statement in the same term to specify that the TCP protocol is being used on the port.</p>
<b>tcp-initial</b>	<p>Match the initial packet of a TCP connection. This is an alias for <b>tcp-flags "(lack &amp; syn)"</b>.</p> <p>This condition does not implicitly check that the protocol is TCP. If you configure this match condition, we recommend that you also configure the <b>protocol tcp</b> match condition in the same term.</p>



Table 27: Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers (*continued*)

Match Condition	Description
<b>t</b> tl <i>number</i>	Match the IPv4 time-to-live number. Specify a TTL value or a range of TTL values. For <i>number</i> , you can specify one or more values from 2 through 255.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>Guidelines for Configuring Standard Firewall Filters on page 19</li> <li>Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview on page 301</li> <li>Standard Firewall Filter Terminating Actions on ACX Series Routers on page 306</li> <li>Standard Firewall Filter Nonterminating Actions on ACX Series Routers on page 308</li> </ul>

## Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers

On ACX Series routers, you can configure a standard stateless firewall filter with match conditions for MPLS traffic (**family mpls**).



**NOTE:** The input-list *filter-names* and output-list *filter-names* statements for firewall filters for the mpls protocol family are supported on all interfaces with the exception of management interfaces and internal Ethernet interfaces (fxp or em0), loopback interfaces (lo0), and USB modem interfaces (umd).

Table 28 on page 306 describes the match conditions you can configure at the [edit firewall family mpls filter *filter-name* term *term-name* from] hierarchy level.

Table 28: Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers

Match Condition	Description
<b>e</b> xp <i>number</i>	Experimental (EXP) bit number or range of bit numbers in the MPLS header. For <i>number</i> , you can specify one or more values from 0 through 7 in decimal, binary, or hexadecimal format.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>Guidelines for Configuring Standard Firewall Filters on page 19</li> <li>Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview on page 301</li> <li>Standard Firewall Filter Terminating Actions on ACX Series Routers on page 306</li> <li>Standard Firewall Filter Nonterminating Actions on ACX Series Routers on page 308</li> </ul>

## Standard Firewall Filter Terminating Actions on ACX Series Routers

Standard stateless firewall filters support different sets of terminating actions for each protocol family.





**NOTE:** ACX Series routers do not support the `next term` action.

Table 29 on page 307 describes the terminating actions you can specify in a standard firewall filter term.

**Table 29: Terminating Actions for Standard Firewall Filters on ACX Series Routers**

Terminating Action	Description	Protocols
<b>accept</b>	Accept the packet.	<ul style="list-style-type: none"> <li>family any</li> <li>family inet</li> <li>family mpls</li> <li>family ccc</li> </ul>
<b>discard</b>	Discard a packet silently, without sending an Internet Control Message Protocol (ICMP) message. Discarded packets are available for logging and sampling.	<ul style="list-style-type: none"> <li>family any</li> <li>family inet</li> <li>family mpls</li> <li>family ccc</li> </ul>
<b>reject <i>message-type</i></b>	Reject the packet and return an ICMPv4 or ICMPv6 message: <ul style="list-style-type: none"> <li>If no message type is specified, a <b>destination-unreachable</b> message is returned by default.</li> <li>If <b>tcp-reset</b> is specified as the message type, <b>tcp-reset</b> is returned only if the packet is a TCP packet. Otherwise, the <b>administratively-prohibited</b> message, which has a value of 13, is returned.</li> <li>If any other message type is specified, that message is returned.</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>Rejected packets can be sampled or logged if you configure the <b>sample</b> or <b>syslog</b> action.</li> <li>This action is supported on ingress only.</li> </ul> <p>The <b>message-type</b> option can have one of the following values: <b>address-unreachable</b>, <b>administratively-prohibited</b>, <b>bad-host-tos</b>, <b>bad-network-tos</b>, <b>beyond-scope</b>, <b>fragmentation-needed</b>, <b>host-prohibited</b>, <b>host-unknown</b>, <b>host-unreachable</b>, <b>network-prohibited</b>, <b>network-unknown</b>, <b>network-unreachable</b>, <b>no-route</b>, <b>port-unreachable</b>, <b>precedence-cutoff</b>, <b>precedence-violation</b>, <b>protocol-unreachable</b>, <b>source-host-isolated</b>, <b>source-route-failed</b>, or <b>tcp-reset</b>.</p>	family inet
<b>routing-instance <i>routing-instance-name</i></b>	Direct the packet to the specified routing instance.	<ul style="list-style-type: none"> <li>family inet</li> </ul>

**Related Documentation**

- Guidelines for Configuring Standard Firewall Filters on page 19
- Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview on page 301
- Standard Firewall Filter Nonterminating Actions on ACX Series Routers on page 308



## Standard Firewall Filter Nonterminating Actions on ACX Series Routers

Standard stateless firewall filters support different sets of nonterminating actions for each protocol family.



**NOTE:** ACX Series routers do not support the **next term** action.

Table 30 on page 308 describes the nonterminating actions you can configure for a standard firewall filter term.

**Table 30: Nonterminating Actions for Standard Firewall Filters on ACX Series Routers**

Nonterminating Action	Description	
<code>count <i>counter-name</i></code>	Count the packet in the named counter.	• • • •
<code>forwarding-class <i>class-name</i></code>	Classify the packet based on the specified forwarding class: <ul style="list-style-type: none"> <li>• <b>assured-forwarding</b></li> <li>• <b>best-effort</b></li> <li>• <b>expedited-forwarding</b></li> <li>• <b>network-control</b></li> </ul> <p><b>NOTE:</b> This action is supported on ingress only.</p>	• • •
<code>log</code>	Log the packet header information in a buffer within the Packet Forwarding Engine. You can access this information by issuing the <b>show firewall log</b> command at the command-line interface (CLI). <p><b>NOTE:</b> This action is supported on ingress only.</p>	f
<code>loss-priority (high   medium-high   low)</code>	Set the packet loss priority (PLP) level. <p>You cannot also configure the <b>three-color-policer</b> nonterminating action for the same firewall filter term. These two nonterminating actions are mutually exclusive.</p> <p>You must include the <b>tri-color</b> statement at the <b>[edit class-of-service]</b> hierarchy level to commit a PLP configuration with any of the four levels specified. If the <b>tri-color</b> statement is not enabled, you can configure only the <b>high</b> and <b>low</b> levels. This applies to all protocol families.</p> <p>For information about the <b>tri-color</b> statement and for information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see the Junos OS Class of Service Configuration Guide.</p> <p><b>NOTE:</b> This action is supported on ingress only.</p>	• • • •



Table 30: Nonterminating Actions for Standard Firewall Filters on ACX Series Routers (*continued*)

Nonterminating Action	Description	
<b>policer</b> <i>policer-name</i>	Name of policer to use to rate-limit traffic.	• • • •
<b>port-mirror</b>	Port-mirror the packet based on the specified family.  <i>NOTE:</i> This action is supported on ingress only.	f
<b>syslog</b>	Log the packet to the system log file.  <i>NOTE:</i> This action is supported on ingress only.	f
<b>three-color-policer (single-rate   two-rate)</b> <i>policer-name</i>	Police the packet using the specified single-rate or two-rate three-color policer.  You cannot also configure the <b>loss-priority</b> action for the same firewall filter term. These two actions are mutually exclusive.	• • • •

**Related  
Documentation**

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview on page 301](#)
- [Standard Firewall Filter Terminating Actions on ACX Series Routers on page 306](#)







# Service Filter Match Conditions and Actions

- [Service Filter Match Conditions for IPv4 or IPv6 Traffic on page 311](#)
- [Service Filter Terminating Actions on page 317](#)
- [Service Filter Nonterminating Actions on page 318](#)

## Service Filter Match Conditions for IPv4 or IPv6 Traffic

Service filters support only a subset of the stateless firewall filter match conditions for IPv4 and IPv6 traffic. [Table 31 on page 311](#) describes the service filter match conditions.

**Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic**

Match Condition	Description	Protocol Families	
<b>address</b> <i>address</i>	Match the IP source or destination address field.	<b>family inet</b>	<b>family inet6</b>
<b>address</b> <i>address</i> <b>except</b>	Do not match the IP source or destination address field.	<b>family inet</b>	<b>family inet6</b>
<b>ah-spi</b> <i>spi-value</i>	(M Series routers, except M120 and M320) Match on the IPsec authentication header (AH) security parameter index (SPI) value.	<b>family inet</b>	—
<b>ah-spi-except</b> <i>spi-value</i>	(M Series routers, except M120 and M320) Do not match on the IPsec AH SPI value.	<b>family inet</b>	—
<b>destination-address</b> <i>address</i>	Match the IP destination address field.  You cannot specify both the <b>address</b> and <b>destination-address</b> match conditions in the same term.	<b>family inet</b>	<b>family inet6</b>
<b>destination-address</b> <i>address address</i>	Do not match the IP destination address field.  You cannot specify both the <b>address</b> and <b>destination-address</b> match conditions in the same term.	<b>family inet</b>	<b>family inet6</b>



Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic (*continued*)

Match Condition	Description	Protocol Families	
<b>destination-port</b> <i>number</i>	<p>Match the UDP or TCP destination port field.</p> <p>You cannot specify both the <b>port</b> and <b>destination-port</b> match conditions in the same term.</p> <p>If you configure this match condition for IPv4 traffic, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p>If you configure this match condition for IPv6 traffic, we recommend that you also configure the <b>next-header udp</b> or <b>next-header tcp</b> match condition in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): <b>afs</b> (1483), <b>bgp</b> (179), <b>biff</b> (512), <b>bootpc</b> (68), <b>bootps</b> (67), <b>cmd</b> (514), <b>cvspserver</b> (2401), <b>dhcp</b> (67), <b>domain</b> (53), <b>eklogin</b> (2105), <b>ekshell</b> (2106), <b>exec</b> (512), <b>finger</b> (79), <b>ftp</b> (21), <b>ftp-data</b> (20), <b>http</b> (80), <b>https</b> (443), <b>ident</b> (113), <b>imap</b> (143), <b>kerberos-sec</b> (88), <b>klogin</b> (543), <b>kpasswd</b> (761), <b>krb-prop</b> (754), <b>krbupdate</b> (760), <b>kshell</b> (544), <b>ldap</b> (389), <b>ldp</b> (646), <b>login</b> (513), <b>mobileip-agent</b> (434), <b>mobileip-mn</b> (435), <b>msdp</b> (639), <b>netbios-dgm</b> (138), <b>netbios-ns</b> (137), <b>netbios-ssn</b> (139), <b>nfsd</b> (2049), <b>nntp</b> (119), <b>ntalk</b> (518), <b>ntp</b> (123), <b>pop3</b> (110), <b>pptp</b> (1723), <b>printer</b> (515), <b>radacct</b> (1813), <b>radius</b> (1812), <b>rip</b> (520), <b>rinit</b> (2108), <b>smtp</b> (25), <b>snmp</b> (161), <b>snmptrap</b> (162), <b>snpp</b> (444), <b>socks</b> (1080), <b>ssh</b> (22), <b>sunrpc</b> (111), <b>syslog</b> (514), <b>tacacs</b> (49), <b>tacacs-ds</b> (65), <b>talk</b> (517), <b>telnet</b> (23), <b>tftp</b> (69), <b>timed</b> (525), <b>who</b> (513), or <b>xdmcp</b> (177).</p>	<b>family inet</b>	<b>family inet6</b>
<b>destination-port-except</b> <i>number</i>	Do not match the UDP or TCP destination port field. For details, see the <b>destination-port</b> match description.	<b>family inet</b>	<b>family inet6</b>
<b>destination-prefix-list</b> <i>name</i>	Match the list of destination prefixes. The prefix list is defined at the [edit <b>policy-options prefix-list</b> <i>prefix-list-name</i> ] hierarchy level.	<b>family inet</b>	<b>family inet6</b>
<b>esp-spi</b> <i>value</i>	Match the IPsec encapsulating security payload (ESP) SPI value. Specify a single value or a range of values. You can specify a <i>value</i> in hexadecimal, binary, or decimal form. To specify the value in hexadecimal form, include <b>0x</b> as a prefix. To specify the value in binary form, include <b>b</b> as a prefix.	<b>family inet</b>	<b>family inet6</b>
<b>esp-spi-except</b> <i>value</i>	Do not match the IPsec ESP SPI value or range of values. For details, see the <b>esp-spi</b> match condition.	<b>family inet</b>	<b>family inet6</b>
<b>first-fragment</b>	<p>Match if the packet is the first fragment of a fragmented packet. Do not match if the packet is a trailing fragment of a fragmented packet. The first fragment of a fragmented packet has a fragment offset value of <b>0</b>.</p> <p>This match condition is an alias for the bit-field match condition <b>fragment-offset 0</b> match condition.</p> <p>To match both first and trailing fragments, you can use two terms that specify different match conditions: <b>first-fragment</b> and <b>is-fragment</b>.</p>	<b>family inet</b>	—



**Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic (*continued*)**

Match Condition	Description	Protocol Families	
<b>fragment-flags</b> <i>number</i>	<p>(Ingress only) Match the three-bit IP fragmentation flags field in the IP header.</p> <p>In place of the numeric field value, you can specify one of the following keywords (the field values are also listed): <b>dont-fragment</b> (0x4), <b>more-fragments</b> (0x2), or <b>reserved</b> (0x8).</p>	<b>family inet</b>	—
<b>fragment-offset</b> <i>number</i>	<p>Match the 13-bit fragment offset field in the IP header. The value is the offset, in 8-byte units, in the overall datagram message to the data fragment. Specify a numeric value, a range of values, or a set of values. An offset value of 0 indicates the first fragment of a fragmented packet.</p> <p>The <b>first-fragment</b> match condition is an alias for the <b>fragment-offset 0</b> match condition.</p> <p>To match both first and trailing fragments, you can use two terms that specify different match conditions (<b>first-fragment</b> and <b>is-fragment</b>).</p>	<b>family inet</b>	—
<b>fragment-offset-except</b> <i>number</i>	Do not match the 13-bit fragment offset field.	<b>family inet</b>	—
<b>interface-group</b> <i>group-number</i>	<p>Match the interface group (set of one or more logical interfaces) on which the packet was received. For <i>group-number</i>, specify a value from 0 through 255.</p> <p>For information about configuring interface groups, see <a href="#">"Filtering Packets Received on a Set of Interface Groups Overview"</a> on page 57.</p>	<b>family inet</b>	<b>family inet6</b>
<b>interface-group-except</b> <i>group-number</i>	Do not match the interface group on which the packet was received. for details, see the <b>interface-group</b> match condition.	<b>family inet</b>	<b>family inet6</b>



Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic (*continued*)

Match Condition	Description	Protocol Families
<b>ip-options values</b>	<p>Match the 8-bit IP option field, if present, to the specified value or list of values.</p> <p>In place of a numeric value, you can specify one of the following text synonyms (the option values are also listed): <b>loose-source-route</b> (131), <b>record-route</b> (7), <b>router-alert</b> (148), <b>security</b> (130), <b>stream-id</b> (136), <b>strict-source-route</b> (137), or <b>timestamp</b> (68).</p> <p>To match <i>any</i> value for the IP option, use the text synonym <b>any</b>. To match on <i>multiple</i> values, specify the list of values within square brackets ('[' and ']'). To match a <i>range</i> of values, use the value specification [ <i>value1-value2</i> ].</p> <p>For example, the match condition <b>ip-options [ 0-147 ]</b> matches on an IP options field that contains the <b>loose-source-route</b>, <b>record-route</b>, or <b>security</b> values, or any other value from 0 through 147. However, this match condition does not match on an IP options field that contains only the <b>router-alert</b> value (148).</p> <p>For most interfaces, a filter term that specifies an <b>ip-option</b> match on one or more <i>specific</i> IP option values (a value other than <b>any</b>) causes packets to be sent to the Routing Engine so that the kernel can parse the IP option field in the packet header.</p> <ul style="list-style-type: none"> <li>For a firewall filter term that specifies an <b>ip-option</b> match on one or more specific IP option values, you cannot specify the <b>count</b>, <b>log</b>, or <b>syslog</b> nonterminating actions <i>unless</i> you also specify the <b>discard</b> terminating action in the same term. This behavior prevents double-counting of packets for a filter applied to a transit interface on the router.</li> <li>Packets processed on the kernel might be dropped in case of a system bottleneck. To ensure that matched packets are instead sent to the Packet Forwarding Engine (where packet processing is implemented in hardware), use the <b>ip-options any</b> match condition.</li> </ul> <p>The 10-Gigabit Ethernet Modular Port Concentrator (MPC), 60-Gigabit Ethernet MPC, 60-Gigabit Queuing Ethernet MPC, and 60-Gigabit Ethernet Enhanced Queuing MPC on MX Series routers are capable of parsing the IP option field of the IPv4 packet header. For interfaces configured on those MPCs, <i>all</i> packets that are matched using the <b>ip-options</b> match condition are sent to the Packet Forwarding Engine for processing.</p>	family inet —
<b>ip-options-except values</b>	Do not match the IP option field to the specified value or list of values. For details about specifying the <b>values</b> , see the <b>ip-options</b> match condition.	family inet —
<b>is-fragment</b>	<p>Match if the packet is a trailing fragment of a fragmented packet. Do not match the first fragment of a fragmented packet.</p> <p>This match condition is an alias for the bit-field match condition <b>fragment-offset 0 except</b> bits.</p> <p><b>NOTE:</b> To match both first and trailing fragments, you can use two terms that specify different match conditions (<b>first-fragment</b> and <b>is-fragment</b>).</p>	family inet —



Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic (*continued*)

Match Condition	Description	Protocol Families	
<b>port number</b>	<p>Match the UDP or TCP source or destination port field.</p> <p>If you configure this match condition, you cannot configure the <b>destination-port</b> match condition or the <b>source-port</b> match condition in the same term.</p> <p>If you configure this match condition for IPv4 traffic, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p>If you configure this match condition for IPv6 traffic, we recommend that you also configure the <b>next-header udp</b> or <b>next-header tcp</b> match condition in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed under <b>destination-port</b>.</p>	<b>family inet</b>	<b>family inet6</b>
<b>port-except number</b>	Do not match the UDP or TCP source or destination port field. For details, see the <b>port</b> match condition.	<b>family inet</b>	<b>family inet6</b>
<b>prefix-list</b> <b>prefix-list-name</b>	Match the prefixes of the source or destination address fields to the prefixes in the specified list. The prefix list is defined at the [edit policy-options prefix-list <b>prefix-list-name</b> ] hierarchy level.	<b>family inet</b>	<b>family inet6</b>
<b>protocol number</b>	<p>Match the IP protocol type field.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed): <b>ah</b> (51), <b>dstopts</b> (60), <b>egp</b> (8), <b>esp</b> (50), <b>fragment</b> (44), <b>gre</b> (47), <b>hop-by-hop</b> (0), <b>icmp</b> (1), <b>icmp6</b> (58), <b>icmpv6</b> (58), <b>igmp</b> (2), <b>ipip</b> (4), <b>ipv6</b> (41), <b>ospf</b> (89), <b>pim</b> (103), <b>rsvp</b> (46), <b>sctp</b> (132), <b>tcp</b> (6), <b>udp</b> (17), or <b>vrrp</b> (112).</p>	<b>family inet</b>	—
<b>protocol-except number</b>	Do not match the IP protocol type field. For details, see the <b>protocol</b> match condition.	<b>family inet</b>	—
<b>source-address address</b>	<p>Match the IP source address.</p> <p>You cannot specify both the <b>address</b> and <b>source-address</b> match conditions in the same term.</p>	<b>family inet</b>	<b>family inet6</b>
<b>source-address address except</b>	<p>Do not match the IP source address.</p> <p>You cannot specify both the <b>address</b> and <b>source-address</b> match conditions in the same term.</p>	<b>family inet</b>	<b>family inet6</b>



Table 31: Service Filter Match Conditions for IPv4 or IPv6 Traffic (*continued*)

Match Condition	Description	Protocol Families	
<b>source-port <i>number</i></b>	<p>Match the UDP or TCP source port field.</p> <p>You cannot specify the <b>port</b> and <b>source-port</b> match conditions in the same term.</p> <p>If you configure this match condition for IPv4 traffic, we recommend that you also configure the <b>protocol udp</b> or <b>protocol tcp</b> match statement in the same term to specify which protocol is being used on the port.</p> <p>If you configure this match condition for IPv6 traffic, we recommend that you also configure the <b>next-header udp</b> or <b>next-header tcp</b> match condition in the same term to specify which protocol is being used on the port.</p> <p>In place of the numeric value, you can specify one of the text synonyms listed with the <b>destination-port <i>number</i></b> match condition.</p>	<b>family inet</b>	<b>family inet6</b>
<b>source-port-except <i>number</i></b>	Do not match the UDP or TCP source port field. For details, see the <b>source-port</b> match condition.	<b>family inet</b>	<b>family inet6</b>
<b>source-prefix-list <i>name</i></b>	Match source prefixes in the specified list. Specify the name of a prefix list defined at the <b>[edit policy-options prefix-list <i>prefix-list-name</i>]</b> hierarchy level.	<b>family inet</b>	<b>family inet6</b>
<b>tcp-flags <i>value</i></b>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> <li>• <b>fin</b> (0x01)</li> <li>• <b>syn</b> (0x02)</li> <li>• <b>rst</b> (0x04)</li> <li>• <b>push</b> (0x08)</li> <li>• <b>ack</b> (0x10)</li> <li>• <b>urgent</b> (0x20)</li> </ul> <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>For combined bit-field match conditions, see the <b>tcp-established</b> and <b>tcp-initial</b> match conditions.</p> <p>If you configure this match condition for IPv4 traffic, we recommend that you also configure the <b>protocol tcp</b> match statement in the same term to specify that the TCP protocol is being used on the port.</p> <p>If you configure this match condition for IPv6 traffic, we recommend that you also configure the <b>next-header tcp</b> match condition in the same term to specify that the TCP protocol is being used on the port.</p>	<b>family inet</b>	<b>family inet6</b>





**NOTE:** If you specify an IPv6 address in a match condition (the address, destination-address, or source-address match conditions), use the syntax for text representations described in RFC 2373, *IP Version 6 Addressing Architecture*. For more information about IPv6 addresses, see “IPv6 Overview” and “IPv6 Standards” in the Junos OS Routing Protocols Configuration Guide.

**Related Documentation**

- [Service Filter Overview on page 65](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Example: Configuring and Applying Service Filters on page 233](#)
- [Service Filter Terminating Actions on page 317](#)
- [Service Filter Nonterminating Actions on page 318](#)

## Service Filter Terminating Actions

Service filters support different sets of terminating actions than standard stateless firewall filters or simple filters.



**NOTE:** Service filters do not support the next term action.

Table 32 on page 317 describes the terminating actions you can configure in a service filter term.

**Table 32: Terminating Actions for Service Filters**

Terminating Action	Description	Protocol Families
service	Direct the packet to service processing.	<ul style="list-style-type: none"><li>• inet</li><li>• inet6</li></ul>
skip	Let the packet bypass service processing.	<ul style="list-style-type: none"><li>• inet</li><li>• inet6</li></ul>

**Related Documentation**

- [Service Filter Overview on page 65](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Example: Configuring and Applying Service Filters on page 233](#)
- [Service Filter Match Conditions for IPv4 or IPv6 Traffic on page 311](#)
- [Service Filter Nonterminating Actions on page 318](#)



## Service Filter Nonterminating Actions

Service filters support different sets of terminating actions for each protocol family.



**NOTE:** Service filters do not support the next term action.

Table 33 on page 318 describes the nonterminating actions you can configure in a service filter term.

**Table 33: Nonterminating Actions for Service Filters**

Nonterminating Action	Description	Protocol Families
<b>count</b> <i>counter-name</i>	Count the packet in the named counter.	<ul style="list-style-type: none"> <li>• <b>inet</b></li> <li>• <b>inet6</b></li> </ul>
<b>log</b>	Log the packet header information in a buffer within the Packet Forwarding Engine. You can access this information by issuing the <b>show firewall log</b> command at the command-line interface (CLI).	<ul style="list-style-type: none"> <li>• <b>inet</b></li> <li>• <b>inet6</b></li> </ul>
<b>port-mirror</b>	Port-mirror the packet based on the specified family. Supported on M120 routers, M320 routers configured with Enhanced III FPCs, and MX Series routers only.	<ul style="list-style-type: none"> <li>• <b>inet</b></li> <li>• <b>inet6</b></li> </ul>
<b>sample</b>	Sample the packet.	<ul style="list-style-type: none"> <li>• <b>inet</b></li> <li>• <b>inet6</b></li> </ul>

### Related Documentation

- [Service Filter Overview on page 65](#)
- [Guidelines for Configuring Service Filters on page 68](#)
- [Example: Configuring and Applying Service Filters on page 233](#)
- [Service Filter Match Conditions for IPv4 or IPv6 Traffic on page 311](#)
- [Service Filter Terminating Actions on page 317](#)



# Reference Information for Firewall Filters in Logical Systems

- [Unsupported Firewall Filter Statements for Logical Systems on page 319](#)
- [Unsupported Actions for Firewall Filters in Logical Systems on page 321](#)

## Unsupported Firewall Filter Statements for Logical Systems

[Table 34 on page 319](#) shows statements that are supported at the `[edit firewall]` hierarchy level but not at the `[edit logical-systems logical-system-name firewall]` hierarchy level.

Table 34: Unsupported Firewall Statements for Logical Systems

Statement	Example	Description
accounting-profile	<pre>[edit] logical-systems {   ls1 {     firewall {       family inet {         filter myfilter {           accounting-profile fw-profile;           ...           term accept-all {             then {               count counter1;               accept;             }           }         }       }     }   } }</pre>	In this example, the <b>accounting-profile</b> statement is not allowed because the accounting profile <b>fw-profile</b> is configured under the <code>[edit accounting-options]</code> hierarchy.



Table 34: Unsupported Firewall Statements for Logical Systems (*continued*)

Statement	Example	Description
hierarchical-policer	<pre>[edit] logical-systems {   ls1 {     firewall {       hierarchical-policer {         ...       }     }   } }</pre>	In this example, the <b>hierarchical policer</b> statement requires a class-of-service configuration, which is not supported under logical systems.
load-balance-group	<pre>[edit] logical-systems {   ls1 {     firewall {       load-balance-group lb-group {         next-hop-group nh-group;       }     }   } }</pre>	<p>This configuration is not allowed because the <b>next-hop-group nh-group</b> statement must be configured at the <b>[edit forwarding-options next-hop-group]</b> hierarchy level—outside the <b>[edit logical-systems logical-system-name firewall]</b> hierarchy.</p> <p>Currently, the <b>forwarding-options dhcp-relay</b> statement is the only forwarding option supported for logical systems.</p>
virtual-channel	<pre>[edit] logical-systems {   ls1 {     firewall {       family inet {         filter foo {           term one {             from {               source-address 10.1.0.0/16;             }             then {               virtual-channel sammy;             }           }         }       }     }   } }</pre>	<p>This configuration is not allowed because the virtual channel <b>sammy</b> refers to an object defined at the <b>[edit class-of-service]</b> hierarchy level, and class of service is not supported for logical systems.</p> <p><b>NOTE:</b></p> <p>The <b>virtual-channel</b> statement is supported for J Series devices only, provided the firewall filter is configured outside of a logical-system.</p>

- Related Documentation**
- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
  - [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
  - [Unsupported Actions for Firewall Filters in Logical Systems on page 321](#)
  - “Introduction to Logical Systems” in the Logical Systems Configuration Guide
  - “Logical Systems Operations and Restrictions” in the Logical Systems Configuration Guide



## Unsupported Actions for Firewall Filters in Logical Systems

Table 35 on page 321 describes the firewall filter actions that are supported at the `[edit firewall]` hierarchy level, but not supported at the `[edit logical-systems logical-system-name firewall]` hierarchy level.

Table 35: Unsupported Actions for Firewall Filters in Logical Systems

Firewall Filter Action	Example	Description
<b>Terminating Actions Not Supported in a Logical System</b>		
<b>logical-system</b>	<pre>[edit] logical-systems {   ls1 {     firewall {       family inet {         filter foo {           term one {             from {               source-address 10.1.0.0/16;             }             then {               logical-system fred;             }           }         }       }     }   } }</pre>	Because the <b>logical-system</b> action refers to <b>fred</b> —a logical system defined outside the local logical system—, this action is not supported.
<b>Nonterminating Actions Not Supported in a Logical System</b>		
<b>ipsec-sa</b>	<pre>[edit] logical-systems {   ls1 {     firewall {       family inet {         filter foo {           term one {             from {               source-address 10.1.0.0/16;             }             then {               ipsec-sa barney;             }           }         }       }     }   } }</pre>	Because the <b>ipsec-sa</b> action modifier references <b>barney</b> —a security association defined outside the local logical system—this action is not supported.



Table 35: Unsupported Actions for Firewall Filters in Logical Systems (*continued*)

Firewall Filter Action	Example	Description
<b>next-hop-group</b>	<pre> [edit] logical-systems {   ls1 {     firewall {       family inet {         filter foo {           term one {             from {               source-address 10.1.0.0/16;             }             then {               next-hop-group fred;             }           }         }       }     }   } } </pre>	Because the <b>next-hop-group</b> action refers to <b>fred</b> —an object defined at the <b>[edit forwarding-options next-hop-group]</b> hierarchy level—this action is not supported.
<b>port-mirror</b>	<pre> [edit] logical-systems {   ls1 {     firewall {       family inet {         filter foo {           term one {             from {               source-address 10.1.0.0/16;             }             then {               port-mirror;             }           }         }       }     }   } } </pre>	Because the <b>port-mirror</b> action relies on a configuration defined at the <b>[edit forwarding-options port-mirroring]</b> hierarchy level, this action is not supported.



Table 35: Unsupported Actions for Firewall Filters in Logical Systems (*continued*)

Firewall Filter Action	Example	Description
sample	<pre> [edit] logical-systems {   ls1 {     firewall {       family inet {         filter foo {           term one {             from {               source-address 10.1.0.0/16;             }             then {               sample;             }           }         }       }     }   } } </pre>	<p>In this example, the <b>sample</b> action depends on the sampling configuration defined under the <b>[edit forwarding-options]</b> hierarchy. Therefore, the <b>sample</b> action is not supported.</p>
syslog	<pre> [edit] logical-systems {   ls1 {     firewall {       family inet {         filter icmp-syslog {           term icmp-match {             from {               address {                 192.168.207.222/32;               }               protocol icmp;             }             then {               count packets;               syslog;               accept;             }           }           term default {             then accept;           }         }       }     }   } } </pre>	<p>In this example, there must be at least one system log (<b>system syslog file filename</b>) with the <b>firewall</b> facility enabled for the <b>icmp-syslog</b> filter's logs to be stored.</p> <p>Because this firewall configuration relies on a configuration outside the logical system, the <b>syslog</b> action modifier is not supported.</p>

- Related Documentation**
- [Stateless Firewall Filters in Logical Systems Overview on page 83](#)
  - [Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84](#)
  - [Unsupported Firewall Filter Statements for Logical Systems on page 319](#)
  - “Introduction to Logical Systems” in the Logical Systems Configuration Guide



- "Logical Systems Operations and Restrictions" in the Logical Systems Configuration Guide



# Firewall Filters Statement Hierarchies

- [Statement Hierarchy for Configuring Interface-Specific Firewall Filters on page 325](#)
- [Statement Hierarchy for Applying Interface-Specific Firewall Filters on page 326](#)
- [Statement Hierarchy for Assigning Interfaces to Interface Groups on page 327](#)
- [Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups on page 327](#)
- [Statement Hierarchy for Applying Filters to an Interface Group on page 328](#)
- [Statement Hierarchy for Defining an Interface Set on page 329](#)
- [Statement Hierarchy for Configuring a Filter to Match on an Interface Set on page 329](#)
- [Statement Hierarchy for Configuring FBF for IPv4 or IPv6 Traffic on page 330](#)
- [Statement Hierarchy for Configuring FBF for IPv4 Traffic on ACX Series Routers on page 331](#)
- [Statement Hierarchy for Configuring FBF for MPLS-Tagged IPv4 Traffic on page 331](#)
- [Statement Hierarchy for Configuring Routing Instances for FBF on page 333](#)
- [Statement Hierarchy for Applying FBF Filters to Interfaces on page 334](#)
- [Statement Hierarchy for Configuring Firewall Filter Accounting Profiles on page 335](#)
- [Statement Hierarchy for Applying Firewall Filter Accounting Profiles on page 336](#)

## Statement Hierarchy for Configuring Interface-Specific Firewall Filters

---

To enable interface-specific instances for stateless firewall filters, include the **interface-specific** statement in the **filter *filter-name*** or **service-filter *service-filter-name*** stanza. Any counters specified as actions in an interface-specific filter are maintained separately per filter instance. Any policers specified as actions in an interface-specific filter are applied per filter instance.

```
firewall {
  family family-name {
    (filter filter-name | service-filter service-filter-name) {
      ...
      interface-specific;
      ...
      term term-name {
        from {
          match-conditions;
        }
      }
    }
  }
}
```



```
        then {
            count counter-name;
            policer policer-name;
        }
    }
    ...
}
]
```

You can include the firewall configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

**Related  
Documentation**

- [Interface-Specific Firewall Filter Instances Overview on page 55](#)
- [Statement Hierarchy for Applying Interface-Specific Firewall Filters on page 326](#)
- [Example: Configuring Interface-Specific Firewall Filter Counters on page 186](#)

---

## Statement Hierarchy for Applying Interface-Specific Firewall Filters

To apply an interface-specific stateless firewall filter to a logical interface, include the **input *filter-name*** or **output *filter-name*** statement in the **filter** or **service-filter** stanza of the interfaces configuration:

```
interfaces {
    interface-name {
        unit unit-number {
            family family-name {
                filter {
                    input filter-name-1;
                    output filter-name-2;
                }
                service-filter {
                    input service-filter-name-1;
                    output service-filter-name-2;
                }
            }
        }
    }
}
```

You can include the interface configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

**Related  
Documentation**

- [Interface-Specific Firewall Filter Instances Overview on page 55](#)
- [Statement Hierarchy for Configuring Interface-Specific Firewall Filters on page 325](#)
- [Example: Configuring Interface-Specific Firewall Filter Counters on page 186](#)



## Statement Hierarchy for Assigning Interfaces to Interface Groups

To assign a logical interface to an interface group, specify the group number by including the **group** *interface-group-number* statement in the **filter** stanza:

```
interfaces {
  interface-name {
    unit unit-number {
      family ( inet | inet6 | vpls | ccc | bridge ) {
        filter {
          group interface-group-number;
        }
      }
    }
  }
}
```



**NOTE:** The number 0 is not a valid number for an interface group.

You can configure the firewall filter at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

### Related Documentation

- [Filtering Packets Received on a Set of Interface Groups Overview on page 57](#)
- [Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups on page 327](#)
- [Example: Filtering Packets Received on an Interface Group on page 190](#)

## Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups

You can configure a standard stateless firewall filter or a service filter term that matches packets tagged for a specified interface group or set of interface groups.

To configure a standard stateless firewall filter that matches packets tagged for a specified interface group or set of interface groups, configure a filter term that uses the **interface-group** *interface-group-number* match condition:

```
firewall {
  family (inet | inet6 | vpls | ccc | bridge) {
    filter filter-name {
      term term-name {
        from {
          interface-group interface-group-number;
        }
        then {
          filter-actions;
        }
      }
    }
  }
}
```



```
    }  
  }  
}
```

To configure a service filter that matches packets tagged for a specified interface group or set of interface groups, configure a filter term that uses the **interface-group** *interface-group-name* match condition:

```
firewall {  
  family (inet | inet6) {  
    service-filter filter-name {  
      term term-name {  
        from {  
          interface-group interface-group-number;  
        }  
        then {  
          service-filter-actions;  
        }  
      }  
    }  
  }  
}
```

You can configure the firewall filter at one of the following hierarchy levels:

- [edit]
- [edit logical-systems *logical-system-name*]

#### Related Documentation

- [Filtering Packets Received on a Set of Interface Groups Overview on page 57](#)
- [Statement Hierarchy for Assigning Interfaces to Interface Groups on page 327](#)
- [Example: Filtering Packets Received on an Interface Group on page 190](#)

---

## Statement Hierarchy for Applying Filters to an Interface Group

To apply a standard stateless firewall filter to an interface group, include the **input** *filter-name* or **output** *filter-name* in the **filter** stanza:

```
interfaces {  
  interface-name {  
    unit unit-number {  
      family family-name {  
        ...  
        filter {  
          input filter-name;  
          output filter-name;  
        }  
      }  
    }  
  }  
}
```



You can include the interface configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

#### Related Documentation

- [Interface-Specific Firewall Filter Instances Overview on page 55](#)
- [Statement Hierarchy for Assigning Interfaces to Interface Groups on page 327](#)
- [Statement Hierarchy for Configuring a Filter to Match on a Set of Interface Groups on page 327](#)
- [Example: Filtering Packets Received on an Interface Group on page 190](#)

## Statement Hierarchy for Defining an Interface Set

To configure a named group of interfaces that can be referenced in a stateless firewall filter match condition, use the **interface-set** statement to define the interface-set name and two or more interfaces:

```
firewall {
  interface-set interface-set-name {
    interface-name;
  }
}
```

You can include the statements at one of the following hierarchy levels:

- **[edit firewall]**
- **[edit logical-systems *logical-system-name* firewall]**

To specify that the interface set contains all interfaces of a particular type, you can use the '\*' (asterisk) wildcard character. For example, use **fe-\*** to specify all Fast Ethernet interfaces.

#### Related Documentation

- [Filtering Packets Received on an Interface Set Overview on page 58](#)
- [Statement Hierarchy for Configuring a Filter to Match on an Interface Set on page 329](#)
- [Example: Configuring a Rate-Limiting Filter Based on Destination Class on page 173](#)
- [Example: Filtering Packets Received on an Interface Set on page 194](#)

## Statement Hierarchy for Configuring a Filter to Match on an Interface Set

To configure a standard stateless firewall filter that matches packets tagged for a specified interface group or set of interface groups, configure a filter term that uses the **interface-group** *interface-group-name* match condition:

```
firewall {
  family (any | inet | inet6 | mpls | vpls | bridge) {
    filter filter-name {
      term term-name {
```



```

        from {
            interface-set interface-set-name;
        }
        then {
            filter-actions;
        }
    }
}

```

#### Related Documentation

- [Filtering Packets Received on an Interface Set Overview on page 58](#)
- [Statement Hierarchy for Defining an Interface Set on page 329](#)
- [Example: Configuring a Rate-Limiting Filter Based on Destination Class on page 173](#)
- [Example: Filtering Packets Received on an Interface Set on page 194](#)

## Statement Hierarchy for Configuring FBF for IPv4 or IPv6 Traffic

You can configure stateless firewall filters for filter-based forwarding by configuring filter terms that specify the **forwarding-class** *class-name* nonterminating action or the **routing-instance** *routing-instance-name* terminating action:

```

firewall {
    family (inet | inet6) {
        filter filter-name {
            term term-name {
                from {
                    ipv4-or-ipv6-match-conditions;
                }
                then {
                    forwarding-class class-name; #optional
                    other-optional-nonterminating-actions;
                    routing-instance routing-instance-name <topology topology-name>;
                }
            }
        }
    }
}

```

You can include the firewall configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

#### Related Documentation

- [Filter-Based Forwarding Overview on page 58](#)
- [Standard Firewall Filter Match Conditions for IPv4 Traffic on page 258](#)
- [Standard Firewall Filter Match Conditions for IPv6 Traffic on page 267](#)
- [Statement Hierarchy for Configuring Routing Instances for FBF on page 333](#)
- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)



## Statement Hierarchy for Configuring FBF for IPv4 Traffic on ACX Series Routers

On ACX Series routers, you can configure stateless firewall filters for filter-based forwarding (FBF) by configuring filter terms that specify the optional nonterminating actions or the **routing-instance *routing-instance-name*** terminating action:

```
firewall {
  family inet {
    filter filter-name {
      term term-name {
        from {
          ipv4-match-conditions;
        }
        then {
          optional-nonterminating-actions;
          routing-instance routing-instance-name ;
        }
      }
    }
  }
}
```

You can include the firewall configuration at the **[edit]** hierarchy level:

The **[edit logical-systems *logical-system-name*]** hierarchy level is not supported on the ACX Series routers.

### Related Documentation

- [Guidelines for Configuring Standard Firewall Filters on page 19](#)
- [Standard Firewall Filter Match Conditions and Actions on ACX Series Routers Overview on page 301](#)
- [Standard Firewall Filter Terminating Actions on ACX Series Routers on page 306](#)
- [Standard Firewall Filter Nonterminating Actions on ACX Series Routers on page 308](#)
- [Standard Firewall Filter Match Conditions for IPv4 Traffic on ACX Series Routers on page 303](#)
- [Standard Firewall Filter Match Conditions for MPLS Traffic on ACX Series Routers on page 306](#)

## Statement Hierarchy for Configuring FBF for MPLS-Tagged IPv4 Traffic

- [Matching on IPv4 Address and TCP/UDP Port Fields on page 331](#)
- [Configuration Example on page 332](#)

### Matching on IPv4 Address and TCP/UDP Port Fields

To configure a firewall filter term that matches on IP source and destination address fields, and TCP and UDP ports in the IPv4 header of packets in an MPLS flow, you can specify supported match conditions as shown here:

```
[edit]
```



```
interfaces {
  interface-name {
    unit logical-unit-number {
      family family {
        address ip-address;
      }
      family mpls {
        filter {
          input filter-name;
        }
      }
    }
  }
}
firewall {
  family mpls {
    filter filter-name {
      term term-name {
        from {
          ip-version ipv4 {
            destination-address {
              ip-address;
            }
            source-address {
              ip-address;
            }
          }
          protocol tcp {
            destination-port tcp-port;
            destination-port-except tcp-port;
            source-port tcp-port;
            source-port-except tcp-port;
          }
          protocol udp {
            destination-port udp-port;
            destination-port-except udp-port;
            source-port udp-port;
            source-port-except udp-port;
          }
        }
      }
    }
  }
  then {
    ...
  }
}
```

## Configuration Example

```
interfaces {
  ge-6/0/0 {
    unit 0 {
      family inet {
        address 20.20.20.1/30;
      }
    }
  }
}
```



```

        family mpls {
            filter {
                input mpls-ipv4-filter1;
            }
        }
    }
}
firewall {
    family mpls {
        filter mpls-ipv4-filter1 {
            term term1 {
                from {
                    ip-version ipv4 {
                        source-address {
                            10.0.0.1/32;
                        }
                    }
                    protocol tcp {
                        destination-port ftp;
                    }
                }
            }
            then {
                count counter1;
                discard;
            }
        }
    }
}
}

```

#### Related Documentation

- [Filter-Based Forwarding Overview on page 58](#)
- [Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276](#)
- [Statement Hierarchy for Configuring Routing Instances for FBF on page 333](#)
- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)

## Statement Hierarchy for Configuring Routing Instances for FBF

A routing instance is a collection of routing tables, interfaces, and routing protocol parameters. The set of interfaces belongs to the routing tables, and the routing protocol parameters control the information in the routing tables.

To configure a routing instance for filter-based forwarding:

1. The **instance-type** must be **forwarding**. The **forwarding** routing instance type supports filter-based forwarding, where interfaces are not associated with instances. For this instance type, there is no one-to-one mapping between an interface and a routing instance. All interfaces belong to the default instance **inet.0**.
2. The name of the routing instance name must be the one referenced in the firewall filter action.





**NOTE:** In Junos OS Release 9.0 and later, you can no longer specify a routing-instance name of **default** or include special characters within the name of a routing instance.

You must also create a routing table group that adds interface routes to the following routing instances:

- Routing instance named in the action
- Default routing table **inet.0**

You create a routing table group to resolve the routes installed in the routing instance to directly connected next hops on that interface. For more information on routing table groups and interface routes, see the Junos OS Routing Protocols Configuration Guide.

```
routing-instances {
  routing-table-name {
    instance-type forwarding;
    routing-options {
      static {
        route destination-prefix nexthop address;
      }
    }
  }
}
```

You can include the **forwarding** routing instance at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

#### Related Documentation

- [Filter-Based Forwarding Overview on page 58](#)
- [Statement Hierarchy for Configuring FBF for IPv4 or IPv6 Traffic on page 330](#)
- [Statement Hierarchy for Configuring FBF for IPv4 Traffic on ACX Series Routers on page 331](#)
- [Statement Hierarchy for Configuring FBF for MPLS-Tagged IPv4 Traffic on page 331](#)
- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)

## Statement Hierarchy for Applying FBF Filters to Interfaces

To apply filter-based forwarding to a logical interface, include the **input** or **output** statement in the **filter** stanza.



**NOTE:** An interface configured with filter-based forwarding does not support source-class usage (SCU) filter matching and unicast reverse-path forwarding (RPF) check filters.



```

interfaces {
  interface-name {
    unit unit-number {
      family (inet | inet6 | mpls) {
        filter {
          input filter-name;
          output filter-name;
        }
        address address;
      }
    }
  }
}

```

You can include the interfaces configuration at one of the following hierarchy levels:

- `[edit]`
- `[edit logical-systems logical-system-name]`

#### Related Documentation

- [Filter-Based Forwarding Overview on page 58](#)
- [Statement Hierarchy for Configuring FBF for IPv4 or IPv6 Traffic on page 330](#)
- [Statement Hierarchy for Configuring FBF for MPLS-Tagged IPv4 Traffic on page 331](#)
- [Statement Hierarchy for Configuring Routing Instances for FBF on page 333](#)
- [Example: Configuring Filter-Based Forwarding on the Source Address on page 200](#)

## Statement Hierarchy for Configuring Firewall Filter Accounting Profiles

To configure an accounting profile that you can apply to a firewall filter, include the **filter-profile** *filter-profile-name* statement in the **accounting-options** stanza.

```

accounting-options {
  filter-profile filter-profile-name {
    file log-filename {
      archive-sites {
        site-urls;
      }
      files number;
      size bytes;
      start-time time;
      transfer-interval minutes;
    }
    interval minutes;
    counters {
      counter-name-1;
      counter-name-2;
    }
  }
}

```



You can include the accounting options configuration at one of the following hierarchy levels:

- **[edit]**
- **[edit logical-systems *logical-system-name*]**

To specify the name of the accounting data log file in the `/var/log` directory to be used in conjunction with the accounting profile, include the **file *log-filename*** statement.

To specify how often statistics are collected for the accounting profile, include the **interval *minutes*** statement.

To specify the names of the firewall filter counters for which filter profile statistics are collected, include the **counters** statement.

**Related  
Documentation**

- [Accounting for Standard Firewall Filters Overview on page 60](#)
- [Statement Hierarchy for Applying Firewall Filter Accounting Profiles on page 336](#)
- [Example: Configuring Statistics Collection for a Standard Firewall Filter on page 223](#)

---

## Statement Hierarchy for Applying Firewall Filter Accounting Profiles

You can apply an accounting profile to a standard stateless firewall filter for any supported protocol family except **family any**.

To apply a filter-accounting profile to a stateless firewall filter, include the **accounting-profile *accounting-profile-name*** statement at the firewall **filter** stanza:

```
firewall {  
  family family-name {  
    filter filter-name {  
      accounting-profile accounting-profile-name;  
      interface-specific;  
      physical-interface-policer;  
      term {  
        filter filter-profile-name;  
      }  
      term term-name {  
        from {  
          match-conditions;  
        }  
        then {  
          actions;  
        }  
      }  
    }  
  }  
}
```

You can include the firewall configuration at one of the following hierarchy levels:

- **[edit]**



- **[edit logical-systems *logical-system-name*]**

**Related  
Documentation**

- [Accounting for Standard Firewall Filters Overview on page 60](#)
- [Statement Hierarchy for Configuring Firewall Filter Accounting Profiles on page 335](#)
- [Example: Configuring Statistics Collection for a Standard Firewall Filter on page 223](#)







## CHAPTER 28

# Summary of Firewall Filters Configuration Statements

### accounting-profile

---

<b>Syntax</b>	<code>accounting-profile <i>name</i>;</code>
<b>Hierarchy Level</b>	[edit <code>firewall family <i>family-name</i> filter <i>filter-name</i></code> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Enable collection of accounting data for the specified filter.
<b>Options</b>	<i>name</i> —Name assigned to the accounting profile.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Accounting for Standard Firewall Filters Overview on page 60</a></li></ul>

### destination-address

---

<b>Syntax</b>	<code>destination-address <i>address</i>;</code>
<b>Hierarchy Level</b>	[edit <code>firewall family <i>family-name</i> filter <i>filter-name</i> term <i>term-name</i> from ip-version <i>ip-version</i></code> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1R1.
<b>Description</b>	Configure the IPv4 or IPv6 address of the destination node that receives the packet.
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276</a></li></ul>




## destination-port

---

<b>Syntax</b>	<code>destination-port &lt;destination-port&gt;;</code>
<b>Hierarchy Level</b>	[edit firewall family <i>family-name</i> filter <i>filter-name</i> term <i>term-name</i> from ip-version <i>ip-version</i> protocol (tcp udp)]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1R1.
<b>Description</b>	Configure the destination port of the Layer 4 header.
<b>Options</b>	<b><i>destination-port</i></b> —The destination port of the Layer 4 header. <b>Range:</b> 0 through 65,535
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276</a></li></ul>



## enhanced-mode

<b>Syntax</b>	enhanced-mode;
<b>Hierarchy Level</b>	[edit <b>firewall filter</b> <i>filter-name</i> ], [edit <b>firewall family</b> <i>family-name filter filter-name</i> ], [edit logical-systems <i>logical-system-name firewall filter filter-name</i> ], [edit logical-systems <i>logical-system-name firewall family family-name filter filter-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.4.
<b>Description</b>	<p>Limit static service filters or API-client filters to term-based filter format only for inet or inet6 families when enhanced network services mode is configured at the <b>[edit chassis network-services]</b> hierarchy level. When used with one of the chassis enhanced network services modes, firewall filters are generated in term-based format for use with MPC modules.</p> <p>If enhanced network services are not configured for the chassis, the <b>enhanced-mode</b> statement is ignored and any enhanced mode firewall filters are generated in both term-based and compiled format (the default).</p>
	<div>  <p><b>NOTE:</b> You cannot attach enhanced mode filters to local loopback, management, or MS-DPC interfaces. These interfaces are processed by the Routing Engine kernel and DPC modules and can accept only compiled firewall filter format.</p> </div>
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Network Services Mode Overview in the Junos OS System Basics Configuration Guide</li> <li>• Firewall Filters and Enhanced Network Services Mode Overview in the Junos OS Subscriber Management, Release 12.3</li> <li>• Configuring a Filter for Use with Enhanced Network Services Mode in the Junos OS Subscriber Management, Release 12.3</li> </ul>



## family (Firewall)

**Syntax**

```
family family-name {
    filter filter-name {
        accounting-profile name;
        enhanced-mode;
        interface-specific;
        physical-interface-filter;
    }
    prefix-action name {
        count;
        destination-prefix-length prefix-length;
        policer policer-name;
        source-prefix-length prefix-length;
        subnet-prefix-length prefix-length;
    }
    simple-filter filter-name {
        term term-name {
            from {
                match-conditions;
            }
            then {
                action;
                action-modifiers;
            }
        }
    }
}
```

**Hierarchy Level** [edit [firewall](#)],  
[edit logical-systems *logical-system-name* [firewall](#)]

**Release Information** Statement introduced before Junos OS Release 7.4.  
Logical systems support introduced in Junos OS Release 9.3.  
**simple-filter** statement introduced in Junos OS Release 7.6.  
**any** family type introduced in Junos OS Release 8.0.  
**bridge** family type introduced in Junos OS Release 8.4 (MX Series routers only).

**Description** Configure a firewall filter for IP version 4 (IPv4) or IP version 6 (IPv6) traffic. On the MX Series routers only, configure a firewall filter for Layer 2 traffic in a bridging environment.

**Options** *family-name*—Version or type of addressing protocol:

- **any**—Protocol-independent match conditions.
- **bridge**—(MX Series routers only) Layer 2 packets that are part of bridging domain.
- **ccc**—Layer 2 switching cross-connects.
- **inet**—IPv4 addressing protocol.
- **inet6**—IPv6 addressing protocol.
- **mpls**—MPLS.



- **vpls**—Virtual private LAN service (VPLS).

The remaining statements are explained separately.

<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Guidelines for Configuring Standard Firewall Filters on page 19</a></li> <li>• <a href="#">Guidelines for Configuring Service Filters on page 68</a></li> <li>• <a href="#">Guidelines for Configuring Simple Filters on page 77</a></li> </ul>

## filter (Applying to a Logical Interface)

<b>Syntax</b>	<pre>filter {   group <i>filter-group-number</i>;   input <i>filter-name</i>;   input-list [ <i>filter-names</i> ];   output <i>filter-name</i>;   output-list [ <i>filter-names</i> ]; }</pre>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family <i>family</i> ], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family <i>family</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Apply a stateless firewall filter to a logical interface at a specific protocol level.
<b>Options</b>	<p><b>group <i>filter-group-number</i></b>—Number of the group to which the interface belongs. Range: 1 through 255</p> <p><b>input <i>filter-name</i></b>—Name of one filter to evaluate when packets are received on the interface.</p> <p><b>input-list [ <i>filter-names</i> ]</b>—Names of filters to evaluate when packets are received on the interface. Up to 16 filters can be included in a filter input list.</p> <p><b>output <i>filter-name</i></b>—Name of one filter to evaluate when packets are transmitted on the interface.</p> <p><b>output-list [ <i>filter-names</i> ]</b>—Names of filters to evaluate when packets are transmitted on the interface. Up to 16 filters can be included in a filter output list.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Guidelines for Configuring Standard Firewall Filters on page 19</a></li> <li>• <a href="#">Guidelines for Applying Standard Firewall Filters on page 25</a></li> </ul>



## filter (Configuring)

---

Syntax	<pre>filter <i>filter-name</i> {     accounting-profile <i>name</i>;     enhanced-mode;     interface-shared;     interface-specific;     physical-interface-filter;     term <i>term-name</i> {         filter <i>filter-name</i>;         from {             match-conditions;         }         then {             actions;         }     } }</pre>
Hierarchy Level	[edit dynamic-profiles <i>profile-name</i> <b>firewall family</b> <i>family-name</i> ], [edit <b>firewall family</b> <i>family-name</i> ], [edit logical-systems <i>logical-system-name</i> <b>firewall family</b> <i>family-name</i> ]
Release Information	Statement introduced before Junos OS Release 7.4. Logical systems support introduced in Junos OS Release 9.3. <b>physical-interface-filter</b> statement introduced in Junos OS Release 9.6. Support at the [edit dynamic-profiles ... <b>family family-name</b> ] hierarchy level introduced in Junos OS Release 11.4. Support for the <b>interface-shared</b> > statement introduced in Junos OS Release 12.2.
Description	Configure firewall filters.
Options	<p><b>filter-name</b>—Name that identifies the filter. This must be a non-reserved string of not more than 64 characters. To include spaces in the name, enclose it in quotation marks (" "). In Junos OS Release 9.0 and later, you can no longer use special characters within the name of a firewall filter. Firewall filter names are restricted from having the form <b>_.*</b> (beginning and ending with underscores) or <b>_.*</b> (beginning with an underscore).</p> <p>The remaining statements are explained separately.</p>
Required Privilege Level	<b>firewall</b> —To view this statement in the configuration. <b>firewall-control</b> —To add this statement to the configuration.
Related Documentation	<ul style="list-style-type: none"><li>• <a href="#">Guidelines for Configuring Standard Firewall Filters on page 19</a></li><li>• <a href="#">Guidelines for Applying Standard Firewall Filters on page 25</a></li><li>• <a href="#">Configuring Multifield Classifiers</a></li><li>• <a href="#">Using Multifield Classifiers to Set PLP</a></li><li>• <a href="#">simple-filter on page 350</a></li></ul>



## firewall

---

<b>Syntax</b>	<code>firewall { ... }</code>
<b>Hierarchy Level</b>	[edit], [edit logical-systems <i>logical-system-name</i> ] [edit dynamic-profiles <i>profile-name</i> ],
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. Logical systems support introduced in Junos OS Release 9.3.
<b>Description</b>	Configure firewall filters.  The statements are explained separately.
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Guidelines for Configuring Standard Firewall Filters on page 19</a></li> <li>• <a href="#">Guidelines for Configuring Service Filters on page 68</a></li> <li>• <a href="#">Guidelines for Configuring Simple Filters on page 77</a></li> <li>• Configuring Multifield Classifiers</li> <li>• Using Multifield Classifiers to Set PLP</li> </ul>

## interface-set

---

<b>Syntax</b>	<code>interface-set <i>interface-set-name</i> {     <i>interface-name</i>; }</code>
<b>Hierarchy Level</b>	[edit <a href="#">firewall</a> ], [edit logical-systems <i>logical-system-name</i> <a href="#">firewall</a> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. Logical systems support introduced in Junos OS Release 9.3.
<b>Description</b>	Configure an interface set.
<b>Options</b>	<i>interface-name</i> —Names of each interface to include in the interface set. You must specify more than one name.
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Filtering Packets Received on an Interface Set Overview on page 58</a></li> </ul>



## interface-specific (Firewall Filters)

---

<b>Syntax</b>	interface-specific;
<b>Hierarchy Level</b>	[edit <b>firewall family</b> <i>family-name</i> <b>filter</b> <i>filter-name</i> ], [edit logical-systems <i>logical-system-name</i> <b>firewall family</b> <i>family-name</i> <b>filter</b> <i>filter-name</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. Logical systems support introduced in Junos OS Release 9.3.
<b>Description</b>	Configure interface-specific names for firewall counters.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Interface-Specific Firewall Filter Instances Overview on page 55</a></li></ul>

## ip-version

---

<b>Syntax</b>	ip-version <i>ip-version</i> ;
<b>Hierarchy Level</b>	[edit firewall family <i>family-name</i> filter <i>filter-name</i> term <i>term-name</i> from]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1R1. Option <b>ipv6</b> introduced in Junos OS Release 12.2R1.
<b>Description</b>	Configure the IP version for the firewall filter.
<b>Options</b>	<i>ip-version</i> —Version of the IP addressing. <ul style="list-style-type: none"><li>• <b>ipv4</b>—IP version 4</li><li>• <b>ipv6</b>—IP version 6</li></ul>
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276</a></li></ul>



## prefix-list

<b>Syntax</b>	<pre>prefix-list name {   ip-addresses;   apply-path path; }</pre>
<b>Hierarchy Level</b>	[edit dynamic policy-options], [edit logical-systems <i>logical-system-name</i> policy-options], [edit policy-options]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. Statement introduced in Junos OS Release 9.0 for EX Series switches. Support for configuration in the dynamic database introduced in Junos OS Release 9.5. Support for configuration in the dynamic database introduced in Junos OS Release 9.5 for EX Series switches. Support for the <b>vpls</b> protocol family introduced in Junos OS Release 10.2.
<b>Description</b>	<p>Define a list of IPv4 or IPv6 address prefixes for use in a routing policy statement or firewall filter statement.</p> <p>You can configure up to 85,325 prefixes in each prefix list. To configure more than 85,325 prefixes, configure multiple prefix lists and apply them to multiple firewall filter terms.</p>
<b>Options</b>	<p><b>name</b>—Name that identifies the list of IPv4 or IPv6 address prefixes.</p> <p><b>ip-addresses</b>—List of IPv4 or IPv6 address prefixes, one IP address per line in the configuration.</p> <p>The remaining statement is explained separately.</p>
<b>Required Privilege Level</b>	<p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>Configuring Prefix Lists for Use in Routing Policy Match Conditions</li> <li><a href="#">Firewall Filter Match Conditions Based on Address Fields on page 35</a></li> <li><a href="#">Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List on page 106</a></li> </ul>



## protocol

---

<b>Syntax</b>	<code>protocol (tcp udp);</code>
<b>Hierarchy Level</b>	[edit firewall family <i>family-name</i> filter <i>filter-name</i> term <i>term-name</i> from ip-version <i>ip-version</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1R1.
<b>Description</b>	Configure the protocol field of IPv4 or the next-header field of the IPv6 address.
<b>Options</b>	<b>tcp</b> —Transmission Control Protocol. <b>udp</b> —User Datagram Protocol.
<b>Required Privilege Level</b>	<b>firewall</b> —To view this statement in the configuration. <b>firewall-control</b> —To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276</a></li></ul>



## service-filter (Firewall)

<b>Syntax</b>	<pre> service-filter <i>filter-name</i> {     term <i>term-name</i> {         from {             <i>match-conditions</i>;         }         then {             <i>actions</i>;         }     } } </pre>
<b>Hierarchy Level</b>	[edit <b>firewall family</b> (inet   inet6), [edit logical-systems <i>logical-system-name</i> <b>firewall family</b> (inet   inet6)]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. Logical systems support introduced in Junos OS Release 9.3.
<b>Description</b>	Configure service filters.
<b>Options</b>	<p><b><i>filter-name</i></b>—Name that identifies the service filter. The name can contain letters, numbers, and hyphens (-) and can be up to 255 characters long. To include spaces in the name, enclose it in quotation marks (" ").</p> <p>The remaining statements are explained separately.</p>
<b>Required Privilege Level</b>	<b>firewall</b> —To view this statement in the configuration. <b>firewall-control</b> —To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Guidelines for Configuring Service Filters on page 68</a></li> <li>• <a href="#">Guidelines for Applying Service Filters on page 70</a></li> </ul>



## simple-filter

---

<b>Syntax</b>	<pre>simple-filter <i>filter-name</i> {     term <i>term-name</i> {         from {             <i>match-conditions</i>;         }         then {             <i>actions</i>;         }     } }</pre>
<b>Hierarchy Level</b>	[edit <a href="#">firewall family inet</a> ], [edit logical-systems <i>logical-system-name</i> <a href="#">firewall family inet</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 7.6. Logical systems support introduced in Junos OS Release 9.3.
<b>Description</b>	Configure simple filters.
<b>Options</b>	<p><b><i>filter-name</i></b>—Name that identifies the simple filter. This must be a non-reserved string of not more than 64 characters. No special characters are restricted. However, to include spaces in the name, enclose it in quotation marks (" ").</p> <p>The remaining statements are explained separately.</p>
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Simple Filter Overview on page 75</a></li><li>• <a href="#">How Simple Filters Evaluate Packets on page 75</a></li><li>• <a href="#">Guidelines for Configuring Simple Filters on page 77</a></li><li>• <a href="#">Guidelines for Applying Simple Filters on page 80</a></li></ul>



## source-address

<b>Syntax</b>	source-address <i>address</i> ;
<b>Hierarchy Level</b>	[edit firewall family <i>family-name</i> filter <i>filter-name</i> term <i>term-name</i> from ip-version <i>ip-version</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1R1.
<b>Description</b>	Configure the IPv4 or IPv6 address of the source node that sends the packet.
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276</a></li> </ul>

## source-checking

<b>Syntax</b>	source-checking;
<b>Hierarchy Level</b>	[edit forwarding-options family inet6]
<b>Description</b>	<p>(MX Series 3D Universal Edge Routers Only) Discard IPv6 packets when the source address type is unspecified, loopback, multicast or link-local</p> <p>RFC 4291, <i>IP Version 6 Addressing Architecture</i>, refers to four address types that require special treatment when they are used as source addresses. The four address types are:</p> <ul style="list-style-type: none"> <li>• Unspecified</li> <li>• Loopback</li> <li>• Multicast</li> <li>• Link-Local Unicast</li> </ul> <p>The loopback and multicast addresses must never be used as a source address in IPv6 packets. The unspecified and link-local addresses can be used as source addresses but routers must never forward packets that have these addresses as source addresses. Typically, packets that contain unspecified or link-local addresses as source addresses are delivered to the local host. If the destination is not the local host, then the packet must not be forwarded. Configuring this statement filters or discards IPv6 packets of these four address types.</p>
<b>Required Privilege Level</b>	routing—To view this statement in the configuration. routing-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Applying Filters to Forwarding Tables</a></li> </ul>



## source-port

---

<b>Syntax</b>	source-port < <i>source-port</i> >;
<b>Hierarchy Level</b>	[edit firewall family <i>family-name</i> filter <i>filter-name</i> term <i>term-name</i> from ip-version <i>ip-version</i> protocol (tcp udp)]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1R1.
<b>Description</b>	Configure the source port of the Layer 4 header.
<b>Options</b>	<b>source-port</b> —The source port of the Layer 4 header. <b>Range:</b> 0 through 65,535
<b>Required Privilege Level</b>	firewall—To view this statement in the configuration. firewall-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Standard Firewall Filter Match Conditions for MPLS-Tagged IPv4 or IPv6 Traffic on page 276</a></li></ul>



## term (Firewall Filter)

<b>Syntax</b>	<pre> term <i>term-name</i> {     from {         <i>match-conditions</i>;         ip-version ipv4 {             <i>match-conditions-mpls-ipv4-address</i>;             protocol (tcp   udp) {                 <i>match conditions-mpls-ipv4-port</i>;             }         }     }     then {         <i>actions</i>;     } } </pre>
<b>Hierarchy Level</b>	<pre> [edit <b>firewall family</b> <i>family-name</i> <b>filter</b> <i>filter-name</i>], [edit <b>firewall family</b> <i>family-name</i> <b>service-filter</b> <i>filter-name</i>], [edit <b>firewall family</b> <i>family-name</i> <b>simple-filter</b> <i>filter-name</i>], [edit logical-systems <i>logical-system-name</i> <b>firewall family</b> <i>family-name</i> <b>filter</b> <i>filter-name</i>], [edit logical-systems <i>logical-system-name</i> <b>firewall family</b> <i>family-name</i> <b>service-filter</b> <i>filter-name</i>], [edit logical-systems <i>logical-system-name</i> <b>firewall family</b> <i>family-name</i> <b>simple-filter</b> <i>filter-name</i>] </pre>
<b>Release Information</b>	<p>Statement introduced before Junos OS Release 7.4.</p> <p><b>filter</b> option introduced in Junos OS Release 7.6.</p> <p>Logical systems support introduced in Junos OS Release 9.3.</p> <p><b>ip-version ipv4</b> support introduced in Junos OS Release 10.1.</p>
<b>Description</b>	Define a firewall filter term.
<b>Options</b>	<p><b>actions</b>—(Optional) Actions to perform on the packet if conditions match. You can specify one <i>terminating action</i> supported for the specified filter type. If you do not specify a terminating action, the packets that match the conditions in the <b>from</b> statement are accepted by default. As an option, you can specify one or more <i>nonterminating actions</i> supported for the specified filter type.</p> <p><b>filter-name</b>—(Optional) For <b>family</b> <i>family-name</i> <b>filter</b> <i>filter-name</i> only, reference another standard stateless firewall filter from within this term.</p> <p><b>from</b>—(Optional) Match packet fields to values. If not included, all packets are considered to match and the actions and action modifiers in the <b>then</b> statement are taken.</p> <p><b>match-conditions</b>—One or more conditions to use to make a match on a packet.</p> <p><b>match-conditions-mpls-ipv4-address</b>—(MPLS-tagged IPv4 traffic only) One or more IP address match conditions to match on the IPv4 packet header. Supports network-based service in a core network with IPv4 packets as an inner payload of an MPLS packet with labels stacked up to five deep.</p>



***match-conditions-mpls-ipv4-port***—(MPLS-tagged IPv4 traffic only) One or more UDP or TCP port match conditions to use to match a packet in an MPLS flow. Supports network-based service in a core network with IPv4 packets as an inner payload of an MPLS packet with labels stacked up to five deep.

***term-name***—Name that identifies the term. The name can contain letters, numbers, and hyphens (-) and can be up to 64 characters long. To include spaces in the name, enclose it in quotation marks (" ").

***then***—(Optional) Actions to take on matching packets. If not included and a packet matches all the conditions in the **from** statement, the packet is accepted.

<b>Required Privilege</b>	firewall—To view this statement in the configuration.
<b>Level</b>	firewall-control—To add this statement to the configuration.

<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Guidelines for Configuring Standard Firewall Filters on page 19</a></li><li>• <a href="#">Guidelines for Configuring Service Filters on page 68</a></li><li>• <a href="#">Guidelines for Configuring Simple Filters on page 77</a></li><li>• <a href="#">Guidelines for Configuring and Applying Firewall Filters in Logical Systems on page 84</a></li></ul>
------------------------------	---



## PART 4

# Index

- [Index on page 357](#)







# Index

## Symbols

! (negation)	
in firewall filters	
bit-field logical operator.....	30
#, comments in configuration statements.....	xviii
&, bit-field logical operator.....	30
( ), in syntax descriptions.....	xviii
+	
bit-field logical operator.....	30
, (comma), bit-field logical operator.....	30
< >, in syntax descriptions.....	xviii
[ ], in configuration statements.....	xviii
{ }, in configuration statements.....	xviii
(pipe)	
in firewall filters	
bit-field logical operator.....	30
(pipe), in syntax descriptions.....	xviii

## A

accounting	
standard stateless firewall filters	
applying firewall filter accounting	
profiles.....	336
configuring firewall filter accounting	
profiles.....	335
example.....	223
overview.....	60
accounting-profile statement.....	339
actions, flow control.....	23
actions, nonterminating	
for service filters.....	318
for simple filters.....	79
for standard stateless firewall	
filters.....	294, 308
actions, terminating	
for service filters.....	317
for simple filters.....	79
for standard stateless firewall	
filters.....	293, 306

address class, source or destination	
stateless firewall filter match conditions	
IPv4 traffic.....	258, 303
IPv6 traffic.....	267
overview.....	43
address prefix, source or destination	
stateless firewall filter match conditions	
MPLS-tagged IPv4 traffic.....	276
VPLS traffic.....	278
address, source or destination	
stateless firewall filter match conditions	
IPv4 traffic.....	258, 303
IPv6 traffic.....	267
Layer 2 bridging traffic.....	287
VPLS traffic.....	278
ampersand (&), bit-field logical operator.....	30
apply-path statement	
firewall filter match condition.....	106

## B

bit-field	
logical operators.....	30
braces, in configuration statements.....	xviii
brackets	
angle, in syntax descriptions.....	xviii
square, in configuration statements.....	xviii

## C

comments, in configuration statements.....	xviii
configuration examples	
service filters.....	233
simple filter.....	239
conventions	
text and syntax.....	xvii
curly braces, in configuration statements.....	xviii
customer support.....	xix
contacting JTAC.....	xix

## D

denial-of-service attacks, preventing.....	157
destination MAC address	
stateless firewall filter match conditions	
Layer 2 CCC traffic.....	285
MPLS-tagged IPv4 traffic.....	276
VPLS traffic.....	278
destination-address statement.....	339
destination-port statement.....	340



diagnosis	
displaying stateless firewall filter configurations.....	134, 161, 171
displaying stateless firewall filter statistics.....	163
verifying firewall filter handles fragments.....	171
verifying stateless firewall filter actions.....	134
verifying stateless firewall filter DoS protection.....	162
verifying stateless firewall filter flood protection.....	162
verifying stateless firewall filters with packet logs.....	135
documentation	
comments on.....	xix
DoS (denial-of-service) attacks, preventing.....	157
DSCP code point	
stateless firewall filter match condition	
IPv4 traffic.....	258, 303
Layer 2 bridging traffic.....	287
VPLS traffic.....	278
<b>E</b>	
enhanced-mode statement	
firewall.....	341
exclamation point ( ! ), bit-field logical operator.....	30
<b>F</b>	
family statement	
firewall filter.....	342
FBF, configuring.....	206
files	
firewall log output file.....	129
filter statement	
firewall.....	344
filter-based forwarding	
configuring on logical systems.....	206
next-interface.....	216, 217
next-ip.....	216
next-ip6.....	216
routing-instance.....	216, 217
standard stateless firewall filters	
applying filters to interfaces.....	333
configuring for IPv4 or IPv6 traffic.....	330
configuring for IPv4 traffic on ACX Series routers.....	331
configuring for MPLS-tagged IPv4 traffic.....	331
example.....	200
overview.....	58
firewall filters	
configuring on logical systems.....	245
log output file.....	129
verifying fragment handling.....	171
firewall filters in logical systems	
restrictions	
references from nonfirewall filter objects.....	90
references to nonfirewall filter objects.....	88
references to subordinate objects.....	87
firewall log output file.....	129
firewall statement.....	345
flooding, preventing.....	157
font conventions.....	xvii
forwarding class	
stateless firewall filter match conditions	
IPv4 traffic.....	258, 303
IPv6 traffic.....	267
Layer 2 bridging traffic.....	287
Layer 2 CCC traffic.....	285
protocol-independent traffic.....	257
VPLS traffic.....	278
fxp0.....	70
<b>H</b>	
handling packet fragments.....	167
<b>I</b>	
ICMP (Internet Control Message Protocol),	
policers.....	157
interface groups	
filtering packets received on	
applying filters.....	328
assigning logical interfaces to groups.....	327
configuring filters.....	327
example.....	190
overview.....	57
interface set	
filtering packets received on	
configuring filters.....	329
defining the interfaces in the set.....	329
overview.....	58
interface-set statement.....	345



- interface-specific counters
    - example
      - example.....186
  - interface-specific firewall filter instances
    - filtering packets received on
      - guidelines for applying.....326
      - guidelines for configuring.....325
      - overview.....55
    - interface-specific names
      - filter instance.....56
  - interface-specific statement.....346
  - Internet Control Message Protocol policers.....157
  - ip-version statement.....346
  - IPv4 traffic
    - match conditions
      - standard stateless firewall
        - filters.....258, 303
    - service filter actions, nonterminating.....318
    - service filter actions, terminating.....317
    - service filter match conditions.....311
    - stateless firewall filter match conditions
      - protocol-independent traffic.....257
  - IPv6 traffic
    - match conditions
      - standard stateless firewall filters.....267
    - service filter actions, nonterminating.....318
    - service filter actions, terminating.....317
    - service filter match conditions.....311
    - stateless firewall filter match conditions
      - protocol-independent traffic.....257
- L**
- Layer 2 bridging traffic
    - match conditions
      - standard stateless firewall filters.....287
  - Layer 2 CCC traffic
    - match conditions
      - standard stateless firewall filter.....285
  - log output
    - firewall filters.....129
  - logging
    - standard stateless firewall filters
      - example.....228
      - system logging of firewall facility
        - events.....61
      - system logging of packet headers.....63
      - system logging overview.....60
  - logical systems
    - configuring filter-based forwarding.....206
    - configuring firewall filters.....245
    - restrictions for firewall filters
      - references from nonfirewall filter
        - objects.....90
      - references to nonfirewall filter
        - objects.....88
      - references to subordinate objects.....87
    - stateless firewall filters
      - applying.....84
      - configuring.....84
      - overview.....83
      - unsupported firewall filter actions.....321
      - unsupported firewall filter statements.....319
  - loopback interface, applying stateless firewall filters
    - to (configuration editor).....157
  - loss priority
    - stateless firewall filter match conditions
      - IPv4 traffic.....258, 303
      - IPv6 traffic.....267
      - Layer 2 bridging traffic.....287
      - Layer 2 CCC traffic.....285
      - VPLS traffic.....278
- M**
- management interface.....70
  - manuals
    - comments on.....xix
  - match condition categories
    - stateless firewall filters
      - matching on address classes.....43
      - matching on address prefixes.....35
      - matching on bit-field values.....30
      - matching on numeric values.....29
      - matching on text strings.....29
  - match conditions
    - for service filters.....311
  - match conditions for standard stateless firewall
    - filters
      - IPv4 traffic.....258, 303
      - IPv6 traffic.....267
      - Layer 2 bridging traffic.....287
      - Layer 2 CCC traffic.....285
      - MPLS traffic.....274, 306
      - MPLS-tagged IPv4 traffic.....276
      - MPLS-tagged IPv6 traffic.....276
      - protocol-independent traffic.....257
      - VPLS traffic.....278



MPLS traffic	
match conditions	
standard stateless firewall filters.....	274, 306
MPLS-tagged IPv4 traffic	
match conditions	
standard stateless firewall filters.....	276
MPLS-tagged IPv6 traffic	
match conditions	
standard stateless firewall filters.....	276
multiple standard firewall filters	
applied as a list	
example.....	177
guidelines for applying.....	51
overview.....	47, 48
in a nested configuration	
example.....	182
guidelines for configuring.....	54
overview.....	52
multiple stateless firewall filters	
applied as a list	
filter list name.....	50
<b>N</b>	
next term action.....	23
next-interface	
usage guidelines.....	217
noncontiguous address filter.....	35
<b>O</b>	
output files	
firewall log output file.....	129
<b>P</b>	
packet evaluation	
service filters.....	67
simple filters.....	75
standard stateless firewall filters.....	18
packets	
handling packet fragments (configuration editor).....	167
parentheses, in syntax descriptions.....	xviii
ping command (stateless firewall filter).....	162
explanation.....	162
pipe (   )	
bit-field logical operator.....	30
plus sign (+), bit-field logical operator.....	30
policers	
for stateless firewall filters.....	157
policy framework.....	3
policy, routing	
prefix list.....	347
policy-based routing See filter-based forwarding	
port number (TCP or UDP), source or destination	
stateless firewall filter match conditions	
IPv4 traffic.....	258, 303
IPv6 traffic.....	267
Layer 2 bridging traffic.....	287
MPLS-tagged IPv4 traffic.....	276
VPLS traffic.....	278
prefix list.....	347
prefix list statement	
firewall filter match condition.....	106
prefix-list statement.....	347
usage guidelines.....	35
protocol statement.....	348
protocol-independent traffic	
match conditions	
standard stateless firewall filters.....	257
<b>R</b>	
reverse-path forwarding (RPF)	
stateless firewall filters	
example.....	147
with an input firewall log or count.....	126
router data flow.....	3
Routing Engine	
handling packet fragments for (configuration editor).....	167
protecting against DoS attacks.....	157
protecting against untrusted services and protocols (configuration editor).....	131
Routing Engine traffic from trusted sources	
stateless firewall filters	
accepting OSPF packets from addresses in a prefix.....	144
blocking Telnet and SSH access.....	136
blocking TFTP access.....	141
example: accepting DHCP packets with specific addresses.....	147
routing solutions	
filtering unwanted services and protocols.....	131
handling packet fragments (configuration editor).....	167
protecting against DoS attacks.....	157
RPF	
firewall log and count.....	126



## S

### sample configurations

firewall filter configurations.....134, 161, 171

### service filters

#### actions

nonterminating.....318

terminating.....317

configuration example.....233

#### filtering packets received on a set of interface

##### groups

configuring filters.....327

guidelines for applying.....70

guidelines for configuring.....68

#### interface-specific counters

example.....186

guidelines for applying.....326

guidelines for configuring.....325

overview.....55

#### interface-specific policers

guidelines for applying.....326

guidelines for configuring.....325

overview.....55

match conditions.....311

overview.....7, 65

packet evaluation.....67

### service-filter statement

firewall.....349

show firewall command.....134, 161, 171

show firewall filter protect-RE command.....163

show firewall log command.....135

show interfaces lo0 command.....157

show log command.....130

show route summary command.....135, 171

explanation.....134

### simple filters

configuration example.....239

guidelines for applying.....80

guidelines for configuring.....77

overview.....7, 75

packet evaluation.....75

### simple-filter statement

firewall.....350

source-address statement.....351

source-port statement.....352

ssh command.....134

### standard stateless firewall filters

#### accounting

applying firewall filter accounting

profiles.....336

configuring firewall filter accounting

profiles.....335

example.....223

overview.....60

#### actions

nonterminating.....294, 308

terminating.....293, 306

applying.....25

configuring.....19

actions.....23

filter names and options.....21

filter terms.....21

match conditions.....22

protocol families.....20

#### examples

filter-based forwarding.....200

logging for standard stateless firewall filter

term.....228

#### filter-based forwarding

configuring for IPv4 or IPv6 traffic.....330

configuring for IPv4 traffic on ACX Series

routers.....331

configuring for MPLS-tagged IPv4

traffic.....331

example.....200

overview.....58

#### filtering packets received on a set of interface

##### groups

assigning logical interfaces to

groups.....327

configuring filters.....327

overview.....57

#### filtering packets received on a specific interface

##### group

applying filters.....328

example.....190

#### filtering packets received on a specific interface

##### set

configuring filters.....329

overview.....58

#### filtering packets received on an interface set

defining the interfaces in the set.....329

#### interface-specific counters

example.....186



interface-specific policers		
guidelines for applying.....	326	
guidelines for configuring.....	325	
overview.....	55	
logging		
example.....	228	
system logging of firewall facility		
events.....	61	
system logging of packet headers.....	63	
system logging overview.....	60	
multiple filters applied as a list		
example.....	177	
guidelines for applying.....	51	
overview.....	47, 48	
multiple filters in a nested configuration		
example.....	182	
guidelines for configuring.....	54	
overview.....	52	
overview.....	17	
packet evaluation.....	18	
standards		
supported for filtering.....	251	
stateless firewall filter		
supported standards.....	251	
stateless firewall filters		
accepting Routing Engine traffic from trusted		
sources		
example: blocking TCP access.....	150	
example: blocking Telnet and SSH		
access.....	106, 164	
actions.....	11	
firewall filters in logical systems.....	84	
service filters.....	68	
standard stateless firewall filters.....	23	
unsupported in logical systems.....	321	
actions, nonterminating		
service filters.....	318	
simple filters.....	79	
standard stateless firewall		
filters.....	294, 308	
actions, terminating		
service filters.....	317	
simple filters.....	79	
standard stateless firewall		
filters.....	293, 306	
application points		
overview.....	13	
service filters.....	70	
simple filters.....	80	
applying to an interface (configuration		
editor).....	157	
basic use		
filtering data packets.....	27	
filtering local packets.....	27	
handling packet fragments.....	45	
displaying configurations.....	134, 161, 171	
displaying statistics.....	163	
examples		
accepting DHCP packets with specific		
addresses.....	147	
accepting OSPF packets from addresses		
in a prefix.....	144	
accepting packets with specific IPv6 TCP		
flags.....	164	
accounting for standard stateless firewall		
filters.....	223	
applying lists of standard firewall filters to		
a single interface.....	177	
blocking TCP access.....	150	
blocking Telnet and SSH access.....	106, 136	
blocking TFTP access.....	141	
counting accepted and rejected		
packets.....	111	
counting and discarding IP options		
packets.....	114	
counting and sampling accepted		
packets.....	126	
counting IP option packets.....	117	
matching on destination port and		
protocol.....	100	
matching on IPv6 flags.....	99	
matching on unrelated fields.....	103	
nesting references to multiple firewall		
filters.....	182	
setting rate limits based on destination		
class.....	173	
setting rate limits for traffic received on an		
interface set.....	194	
setting the DSCP bit to zero.....	123	
filter names		
service filters.....	68	
simple filters.....	77	
filter names and options		
standard stateless firewall filters.....	21	
filter terms.....	9	
service filters.....	68	
simple filters.....	77	
standard stateless firewall filters.....	21	



- filter-based forwarding
    - applying filters to interfaces.....333, 334
  - filtering router transit traffic
    - overview.....27
  - filtering Routing Engine traffic
    - overview.....27
  - firewall filter statements
    - unsupported in logical systems.....319
  - handling packet fragments
    - overview.....45
  - handling packet fragments (configuration editor).....167
  - hardware requirements for applying
    - service filters.....70
    - simple filters.....80
  - in logical systems
    - applying.....84
    - configuring.....84
    - overview.....83
  - interface-specific names
    - filter list name.....50
  - logical systems
    - unsupported firewall filter actions.....321
    - unsupported firewall filter statements.....319
  - match condition categories
    - matching on address classes.....43
    - matching on address prefixes.....35
    - matching on bit-field values.....30
    - matching on numeric values.....29
    - matching on text strings.....29
  - match conditions.....10
    - firewall filters in logical systems.....84
    - service filters.....68, 311
    - simple filters.....77
    - standard stateless firewall filters.....22
  - multiple filters applied as a list
    - filter list name.....50
  - overview.....5
  - policers for.....157
  - protecting the Routing Engine against TCP floods.....157
  - protecting the Routing Engine against untrusted protocols (configuration editor).....131
  - protecting the Routing Engine against untrusted services (configuration editor).....131
  - protocol families.....7
    - firewall filters in logical systems.....84
    - service filters.....68
    - simple filters.....77
    - standard stateless firewall filters.....20
  - reverse-path forwarding (RPF)
    - example.....147
    - with an input firewall log or count.....126
  - sample terms, to filter fragments.....167
  - sample terms, to filter services and protocols.....131
  - service filters.....65
    - statement hierarchy for applying.....70
    - statement hierarchy for configuring.....68
  - simple filters.....75
  - standard stateless firewall filters.....17
  - statement hierarchy
    - applying simple filters.....80
    - configuring simple filters.....77
  - type
    - overview.....7
  - types.....6
  - verifying actions.....134
  - verifying configuration.....134, 161, 171
  - verifying flood protection.....162
  - verifying packet logging.....135
  - statement hierarchy
    - service filters
      - applying.....70
      - configuring.....68
    - simple filters
      - applying.....80
      - configuring.....77
    - stateless firewall filters
      - applying filters to interfaces.....334
  - statistics
    - stateless firewall filters.....163
  - support, technical See technical support
  - syntax conventions.....xvii
- ## T
- TCP policers.....157
  - technical support
    - contacting JTAC.....xix
  - telnet command.....162
  - term statement
    - firewall.....353
  - traffic
    - sampling
      - show log command.....130



**V**

## verification

filter-based forwarding.....	214
firewall filter handles fragments.....	171
OSPF policy.....	248
stateless firewall filter actions.....	134
stateless firewall filter flood protection.....	162
stateless firewall filter operation.....	135
stateless firewall filters.....	134, 161, 171
stateless firewall statistics.....	163

## VPLS traffic

## match conditions

standard stateless firewall filters.....	278
--	-----