



---

Junos<sup>®</sup> OS

## Application Aware Services Interfaces Feature Guide for Routing Devices



---

Modified: 2018-08-23

Juniper Networks, Inc.  
1133 Innovation Way  
Sunnyvale, California 94089  
USA  
408-745-2000  
[www.juniper.net](http://www.juniper.net)

Juniper Networks, the Juniper Networks logo, Juniper, and Junos are registered trademarks of Juniper Networks, Inc. and/or its affiliates in the United States and other countries. All other trademarks may be property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

*Junos® OS Application Aware Services Interfaces Feature Guide for Routing Devices*  
Copyright © 2018 Juniper Networks, Inc. All rights reserved.

The information in this document is current as of the date on the title page.

#### YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

#### END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <https://www.juniper.net/support/eula/>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

# Table of Contents

	About the Documentation . . . . .	xi
	Documentation and Release Notes . . . . .	xi
	Using the Examples in This Manual . . . . .	xi
	Merging a Full Example . . . . .	xii
	Merging a Snippet . . . . .	xii
	Documentation Conventions . . . . .	xiii
	Documentation Feedback . . . . .	xv
	Requesting Technical Support . . . . .	xv
	Self-Help Online Tools and Resources . . . . .	xvi
	Opening a Case with JTAC . . . . .	xvi
<b>Chapter 1</b>	<b>Configuring Stateless, Rule-Based Services Using Application-Aware Access Lists . . . . .</b>	<b>17</b>
	AACL Overview . . . . .	17
	Best-Effort Application Identification of DPI-Serviced Flows . . . . .	18
	Features That Support Application-Level Filtering . . . . .	19
	Best-Effort Application Determination . . . . .	19
	APPID, AACL, and L-PDF Processing in Preconvergence Scenarios . . . . .	19
	Prior to a Final or Best-Effort Application Identification . . . . .	19
	Upon Best-Effort Application Identification . . . . .	20
	While Application Identification Is on a Best-Effort Basis . . . . .	20
	If a Flow Ends Before an Application Identification Is Made . . . . .	20
	If a Flow Ends While Application Identification on a Best-Effort Basis . . . . .	20
	Configuring AACL Rules . . . . .	21
	Configuring Match Direction for AACL Rules . . . . .	22
	Configuring Match Conditions in AACL Rules . . . . .	22
	Configuring Actions in AACL Rules . . . . .	23
	Logging AACL Flows Based on Application . . . . .	24
	Example: Configuring AACL Rules . . . . .	25
	Configuring AACL Rule Sets . . . . .	26
	Configuring Logging of AACL Flows . . . . .	27
<b>Chapter 2</b>	<b>Grouping Applications Together Using APPID . . . . .</b>	<b>29</b>
	APPID Overview . . . . .	29
	Best-Effort Application Identification of DPI-Serviced Flows . . . . .	32
	Features That Support Application-Level Filtering . . . . .	32
	Best-Effort Application Determination . . . . .	32
	APPID, AACL, and L-PDF Processing in Preconvergence Scenarios . . . . .	32
	Prior to a Final or Best-Effort Application Identification . . . . .	32
	Upon Best-Effort Application Identification . . . . .	33

	While Application Identification Is on a Best-Effort Basis . . . . .	33
	If a Flow Ends Before an Application Identification Is Made . . . . .	33
	If a Flow Ends While Application Identification on a Best-Effort Basis . . . . .	33
	Defining an Application Identification . . . . .	34
	Configuring APPID Rules . . . . .	36
	Using Stateful Firewall Rules to Identify Data Sessions . . . . .	37
	Configuring Application Profiles . . . . .	39
	Configuring Application Groups . . . . .	40
	Application Identification for Nested Applications . . . . .	41
	Disabling Application Identification for Nested Applications . . . . .	42
	Configuring Global APPID Properties . . . . .	43
	Configuring APPID Support for Heuristics . . . . .	44
	Configuring APPID Support for Unidirectional Traffic . . . . .	45
	Configuring Automatic Download of Application Package Updates . . . . .	46
	Tracing APPID Operations . . . . .	46
	Configuring the APPID Log Filename . . . . .	47
	Configuring the Number and Size of APPID Log Files . . . . .	47
	Configuring Access to the Log File . . . . .	48
	Configuring a Regular Expression for Lines to Be Logged . . . . .	48
	Configuring the Tracing Flags . . . . .	48
	Examples: Configuring Application Identification Properties . . . . .	48
<b>Chapter 3</b>	<b>Collecting Statistics and Tracking Data Using L-PDF . . . . .</b>	<b>51</b>
	L-PDF Overview . . . . .	51
	Best-Effort Application Identification of DPI-Serviced Flows . . . . .	53
	Features That Support Application-Level Filtering . . . . .	54
	Best-Effort Application Determination . . . . .	54
	APPID, ACL, and L-PDF Processing in Preconvergence Scenarios . . . . .	54
	Prior to a Final or Best-Effort Application Identification . . . . .	54
	Upon Best-Effort Application Identification . . . . .	55
	While Application Identification Is on a Best-Effort Basis . . . . .	55
	If a Flow Ends Before an Application Identification Is Made . . . . .	55
	If a Flow Ends While Application Identification on a Best-Effort Basis . . . . .	55
	Configuring Statistics Profiles . . . . .	56
	Configuring an L-PDF Statistics Profile . . . . .	57
	Configuring an ACL Statistics Profile . . . . .	58
	Applying L-PDF Profiles to Service Sets . . . . .	59
	Tracing L-PDF Operations . . . . .	61
<b>Chapter 4</b>	<b>Configuration Statements . . . . .</b>	<b>63</b>
	acl-fields . . . . .	66
	acl-statistics-profile . . . . .	67
	address . . . . .	68
	application (Defining) . . . . .	69
	application (Including in Rule) . . . . .	70
	application-aware-access-list-fields . . . . .	71
	application-group . . . . .	72
	application-group-any . . . . .	72

application-groups (Services ACL) .....	73
application-groups (Services Application Identification) .....	73
application-system-cache-timeout .....	74
application-unknown .....	74
applications (Services ACL) .....	75
applications (Services Application Identification) .....	75
automatic .....	76
bypass-traffic-on-exceeding-flow-limits .....	76
chain-order .....	77
context .....	77
destination (Services) .....	78
destination-address .....	78
destination-address-range .....	79
destination-prefix-list (Services ACL) .....	79
direction .....	80
disable (APPID Application) .....	80
disable (APPID Application Group) .....	81
disable (APPID Port Mapping) .....	81
disable-global-timeout-override .....	82
download .....	82
enable-asymmetric-traffic-processing .....	83
enable-heuristics .....	83
file .....	84
from .....	85
idle-timeout .....	86
ignore-errors .....	87
index (Applications) .....	88
index (Nested Applications) .....	88
inactivity-non-tcp-timeout .....	89
inactivity-tcp-timeout .....	89
ip .....	90
local-policy-decision-function .....	91
log (acl) .....	92
match-direction .....	93
max-checked-bytes .....	93
maximum-transactions .....	94
member .....	94
min-checked-bytes .....	95
nested-application .....	96
nested-applications .....	97
nested-application-settings .....	97
nested-application-unknown .....	98
no-application-identification .....	98
no-application-system-cache .....	99
no-clear-application-system-cache .....	99
no-nested-application .....	100
no-protocol-method .....	100
no-signature-based .....	101
order (Services Application Identification) .....	101

pattern	102
policy-decision-statistics-profile	103
port-mapping	104
port-range	105
profile	106
protocol	106
rule (AACL Rule Set)	107
rule (Application Identification)	108
rule (Including in Rule Set)	109
rule-set (Services AACL)	109
rule-set (Services Application Identification)	110
service-set-options	111
statistics (System Services)	112
support-uni-directional-traffic	113
service-set (Services)	114
services (AACL)	116
services (Application Identification)	117
session-timeout (Application Identification)	117
session-timeout (Interfaces)	118
signature	119
signature-method-all-ports	120
source	120
source-address (AACL)	121
source-address-range	121
source-prefix-list (Services AACL)	122
source-prefix-list (Services IDS)	122
term	123
then	124
traceoptions (Application Identification)	126
traceoptions (Services Local Policy Decision Function)	128
type	129
type-of-service	130
url	130
<b>Chapter 5</b>	
<b>Operational Commands</b>	<b>131</b>
clear services application-aware-access-list statistics	132
clear services application-identification application-system-cache	133
clear services application-identification counter	134
clear services flows	135
clear services local-policy-decision-function statistics	138
request services application-identification application	139
request services application-identification download	140
request services application-identification download status	141
request services application-identification group	142
request services application-identification install	144
request services application-identification install status	145
show services application-aware-access-list flows	146
show services application-identification application-system-cache	149
show services application-identification counter	151

show services application-identification group . . . . .	154
show services application-aware-access-list statistics . . . . .	156
show services application-identification application . . . . .	158
show services application-identification version . . . . .	164
show services flows . . . . .	165
show services local-policy-decision-function flows . . . . .	172
show services local-policy-decision-function statistics . . . . .	174
show services sessions . . . . .	176



# List of Tables

	<b>About the Documentation</b> . . . . .	<b>xi</b>
	Table 1: Notice Icons . . . . .	xiii
	Table 2: Text and Syntax Conventions . . . . .	xiii
<b>Chapter 5</b>	<b>Operational Commands</b> . . . . .	<b>131</b>
	Table 3: clear services flows Output Fields . . . . .	137
	Table 4: show services application-aware-access-list flows Output Fields . . . .	146
	Table 5: show application-identification application-system-cache Output Fields . . . . .	149
	Table 6: show services application-identification counter Output Fields . . . . .	151
	Table 7: show services application-identification group Output Fields . . . . .	154
	Table 8: show services application-aware-access-list statistics Output Fields . . . . .	156
	Table 9: show services application-identification application summary Output Fields . . . . .	158
	Table 10: show services application-identification application Output Fields . . .	159
	Table 11: show services flows Output Fields . . . . .	167
	Table 12: show services local-policy-decision-function flows Output Fields . . .	172
	Table 13: show services local-policy-decision-function statistics Output Fields . . . . .	174
	Table 14: show services sessions Output Fields . . . . .	179



# About the Documentation

- Documentation and Release Notes on page xi
- Using the Examples in This Manual on page xi
- Documentation Conventions on page xiii
- Documentation Feedback on page xv
- Requesting Technical Support on page xv

## Documentation and Release Notes

---

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at <https://www.juniper.net/documentation/>.

If the information in the latest release notes differs from the information in the documentation, follow the product Release Notes.

Juniper Networks Books publishes books by Juniper Networks engineers and subject matter experts. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration. The current list can be viewed at <https://www.juniper.net/books>.

## Using the Examples in This Manual

---

If you want to use the examples in this manual, you can use the **load merge** or the **load merge relative** command. These commands cause the software to merge the incoming configuration into the current candidate configuration. The example does not become active until you commit the candidate configuration.

If the example configuration contains the top level of the hierarchy (or multiple hierarchies), the example is a *full example*. In this case, use the **load merge** command.

If the example configuration does not start at the top level of the hierarchy, the example is a *snippet*. In this case, use the **load merge relative** command. These procedures are described in the following sections.

## Merging a Full Example

To merge a full example, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration example into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following configuration to a file and name the file **ex-script.conf**. Copy the **ex-script.conf** file to the **/var/tmp** directory on your routing platform.

```
system {
  scripts {
    commit {
      file ex-script.xml;
    }
  }
}
interfaces {
  fxp0 {
    disable;
    unit 0 {
      family inet {
        address 10.0.0.1/24;
      }
    }
  }
}
```

2. Merge the contents of the file into your routing platform configuration by issuing the **load merge** configuration mode command:

```
[edit]
user@host# load merge /var/tmp/ex-script.conf
load complete
```

## Merging a Snippet

To merge a snippet, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration snippet into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following snippet to a file and name the file **ex-script-snippet.conf**. Copy the **ex-script-snippet.conf** file to the **/var/tmp** directory on your routing platform.

```
commit {
  file ex-script-snippet.xml; }
```

2. Move to the hierarchy level that is relevant for this snippet by issuing the following configuration mode command:

```
[edit]
```

```
user@host# edit system scripts
[edit system scripts]
```

3. Merge the contents of the file into your routing platform configuration by issuing the **load merge relative** configuration mode command:

```
[edit system scripts]
user@host# load merge relative /var/tmp/ex-script-snippet.conf
load complete
```

For more information about the **load** command, see [CLI Explorer](#).

## Documentation Conventions

Table 1 on page xiii defines notice icons used in this guide.

Table 1: Notice Icons







Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.
	Tip	Indicates helpful information.
	Best practice	Alerts you to a recommended use or implementation.

Table 2 on page xiii defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
<b>Bold text like this</b>	Represents text that you type.	To enter configuration mode, type the <b>configure</b> command:  user@host> <b>configure</b>

Table 2: Text and Syntax Conventions (continued)

Convention	Description	Examples
Fixed-width text like this	Represents output that appears on the terminal screen.	<pre>user@host&gt; show chassis alarms</pre> <p>No alarms currently active</p>
<i>Italic text like this</i>	<ul style="list-style-type: none"> <li>Introduces or emphasizes important new terms.</li> <li>Identifies guide names.</li> <li>Identifies RFC and Internet draft titles.</li> </ul>	<ul style="list-style-type: none"> <li>A policy <i>term</i> is a named structure that defines match conditions and actions.</li> <li><i>Junos OS CLI User Guide</i></li> <li>RFC 1997, <i>BGP Communities Attribute</i></li> </ul>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	<p>Configure the machine's domain name:</p> <pre>[edit] root@# set system domain-name domain-name</pre>
Text like this	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none"> <li>To configure a stub area, include the <b>stub</b> statement at the <code>[edit protocols ospf area area-id]</code> hierarchy level.</li> <li>The console port is labeled <b>CONSOLE</b>.</li> </ul>
< > (angle brackets)	Encloses optional keywords or variables.	<code>stub &lt;default-metric metric&gt;;</code>
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	<pre>broadcast   multicast</pre> <p><i>(string1   string2   string3)</i></p>
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	<code>rsvp { # Required for dynamic MPLS only</code>
[ ] (square brackets)	Encloses a variable for which you can substitute one or more values.	<code>community name members [ community-ids ]</code>
Indentation and braces ( { } )	Identifies a level in the configuration hierarchy.	<pre>[edit] routing-options {   static {     route default {       nexthop address;       retain;     }   } }</pre>
;(semicolon)	Identifies a leaf statement at a configuration hierarchy level.	
<b>GUI Conventions</b>		
<b>Bold text like this</b>	Represents graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none"> <li>In the Logical Interfaces box, select <b>All Interfaces</b>.</li> <li>To cancel the configuration, click <b>Cancel</b>.</li> </ul>


Table 2: Text and Syntax Conventions (continued)

Convention	Description	Examples
> (bold right angle bracket)	Separates levels in a hierarchy of menu selections.	In the configuration editor hierarchy, select <b>Protocols&gt;Ospf</b> .

## Documentation Feedback

We encourage you to provide feedback so that we can improve our documentation. You can use either of the following methods:

- Online feedback system—Click TechLibrary Feedback, on the lower right of any page on the [Juniper Networks TechLibrary](#) site, and do one of the following:



- Click the thumbs-up icon if the information on the page was helpful to you.
- Click the thumbs-down icon if the information on the page was not helpful to you or if you have suggestions for improvement, and use the pop-up form to provide feedback.
- E-mail—Send your comments to [techpubs-comments@juniper.net](mailto:techpubs-comments@juniper.net). Include the document or topic name, URL or page number, and software version (if applicable).

## Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or Partner Support Service support contract, or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <https://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <https://www.juniper.net/support/warranty/>.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

## Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <https://www.juniper.net/customers/support/>
- Search for known bugs: <https://prsearch.juniper.net/>
- Find product documentation: <https://www.juniper.net/documentation/>
- Find solutions and answer questions using our Knowledge Base: <https://kb.juniper.net/>
- Download the latest versions of software and review release notes: <https://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <https://kb.juniper.net/InfoCenter/>
- Join and participate in the Juniper Networks Community Forum: <https://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <https://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://entitlementsearch.juniper.net/entitlementsearch/>

## Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <https://www.juniper.net/cm/>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <https://www.juniper.net/support/requesting-support.html>.

## CHAPTER 1

# Configuring Stateless, Rule-Based Services Using Application-Aware Access Lists

- [AACL Overview on page 17](#)
- [Best-Effort Application Identification of DPI-Serviced Flows on page 18](#)
- [Configuring AACL Rules on page 21](#)
- [Example: Configuring AACL Rules on page 25](#)
- [Configuring AACL Rule Sets on page 26](#)
- [Configuring Logging of AACL Flows on page 27](#)

## AACL Overview

---



**NOTE:** Starting with Junos OS Release 12.1, all interface-style services are supported for dynamic Point-to-Point Protocol over Ethernet (PPPoE) subscribers on all MX Series routers with modular Modular Port Concentrators (MPCs).

The application-aware access list (AACL) service adds support for a new service that uses application names and groups as matching criteria for filtering traffic. AACL is a stateless, rules-based service that must be combined with application identification to enable policies to be applied to flows based on application and application group membership in addition to traditional packet matching rules. It is supported on MX Series routers equipped with Multiservices DPCs and on M120 or M320 routers equipped with Multiservices 400 PICs. Starting with Junos OS Release 11.3, AACL is supported on T320, T640, and T1600 routers also.

AACL is configured in a similar way to other rules-based services such as Network Address Translation (NAT), class of service (CoS), and stateful firewall. To configure AACL, include rule specifications for match criteria and actions at the **[edit services aacl]** hierarchy level. You can chain AACL rules along with other service rules by including them in a service-set definition at the **[edit services service-set]** hierarchy level, as previously documented.

There is one pair of related operational commands, **show/clear application-aware-access-list statistics**.

For more information on the CLI configuration, see the *Application Aware Services Interfaces Feature Guide for Routing Devices*. For more information on the operational command, see the [CLI Explorer](#).



**NOTE:** Because the Junos OS extension-provider package framework lacks aggressive constraint checks, you should not set the `policy-db-size` statement at the `[edit chassis fpc slot-number pic pic-number adaptive-services service-package extension-provider]` hierarchy level to a high value. For Junos Application Aware (previously known as dynamic application awareness) configurations, the recommended values for the extension-provider options at this hierarchy level are as follows:

- `control-cores = 1`
- `data-cores = 7`
- `object-cache-size = 1280` (for Multiservices 400 PIC and Multiservices DPC)
- `policy-db-size = 200`
- Include these package values: `jservices-idp`, `jservices-appid`, `jservices-llpdf`, `jservices-aacl`

For more information about this configuration, see the following topics in the *SDK Applications Configuration Guide and Command Reference*:

- *Configuring Control and Data Cores*
- *Configuring Packages on the PIC*

---

**Related Documentation**

- [Configuring AACL Rules on page 21](#)
- [Configuring AACL Rule Sets on page 26](#)
- [Configuring Logging of AACL Flows on page 27](#)
- [Example: Configuring AACL Rules on page 25](#)

---

## Best-Effort Application Identification of DPI-Serviced Flows

This topic describes the following information:

- [Features That Support Application-Level Filtering on page 19](#)
- [Best-Effort Application Determination on page 19](#)
- [APPID, AACL, and L-PDF Processing in Preconvergence Scenarios on page 19](#)

## Features That Support Application-Level Filtering

The application-aware access list (ACL) service uses application names and groups as matching criteria for filtering traffic. The service defines the applications and application groups for which statistics are collected for a specific user or interface.

The local policy decision function (L-PDF) enables you to configure properties for statistics output. L-PDF supports a process that regulates collection of statistics related to applications and application groups and tracking of information about dynamic subscribers and static interfaces.

## Best-Effort Application Determination

Typically, APPID conclusively determines the Layer 7 application associated with a given DPI-serviced flow. In these cases, the application identification is final. Occasionally, APPID is only able to make an initial, inconclusive determination of the Layer 7 application associated with a given flow. This is referred to as a *best-effort* application identification. In such cases, the APPID process continues processing packets on that flow and might subsequently make a conclusive determination of the application associated with that flow. In some cases of best-effort application identification, the flow ends before a final application determination can be made.

## APPID, ACL, and L-PDF Processing in Preconvergence Scenarios

The following sections describe APPID, ACL, and L-PDF processing in various stages of application identification for a DPI-serviced flow of TCP/UDP/ICMP traffic.

- [Prior to a Final or Best-Effort Application Identification on page 19](#)
- [Upon Best-Effort Application Identification on page 20](#)
- [While Application Identification Is on a Best-Effort Basis on page 20](#)
- [If a Flow Ends Before an Application Identification Is Made on page 20](#)
- [If a Flow Ends While Application Identification on a Best-Effort Basis on page 20](#)

### Prior to a Final or Best-Effort Application Identification

During the time that APPID has not yet made either a final or best-effort determination of the application associated with a given flow, the flow does not contribute to any per-subscriber or per-application statistics collection.

The output of the following operational mode commands includes flows for which APPID has not yet made either a final or best-effort determination of the associated application:

- **show services local-policy-decision-function flows** (interface *interface-name* | subscriber *subscriber-name*)
- **show services application-aware-access-list flows** (interface *interface-name* | subscriber *subscriber-name*)

In the command output, the **Action** field displays **accept** and the **Application** or **Application group** field displays **unknown** for a flow for which APPID has not yet made either a final or best-effort determination of the associated application.

### Upon Best-Effort Application Identification

---

When a best-effort application determination is made, ACL does not apply any ACL term actions configured for that flow. There are a number of reasons for this, one being that the action itself (such as **discard**) can make a final application determination impossible. Instead, ACL or L-PDF tracks the flow and accepts all packets for that flow until a final determination is made, at which time the normal ACL or L-PDF actions are fully applied to the flow.

### While Application Identification Is on a Best-Effort Basis

---

During the time that APPID identification of the application associated with a given flow is on a best-effort basis, the flow does not contribute to any per-subscriber or per-application statistics collection.

The output of the following operational mode commands includes flows for which APPID has only made a best-effort determination of the associated application:

- **show services local-policy-decision-function flows** (interface *interface-name* | subscriber *subscriber-name*)
- **show services application-aware-access-list flows** (interface *interface-name* | subscriber *subscriber-name*)

In the command output, the **Action** field displays **accept** and the **Application** or **Application group** field displays **unknown** for a flow for which APPID has only made a best-effort determination of the associated application.

### If a Flow Ends Before an Application Identification Is Made

---

If a flow ends before APPID has made either a final or a best-effort application identification, ACL or L-PDF uses the **unknown** application ID as a final determination and performs any necessary collection, aggregation, and reporting of statistics based on that Layer 7 application. In particular, if the **count** ACL term action is configured for the **application-group-any** application, then the statistics for that flow are collected and aggregated against the count bucket type, and reported as such.

### If a Flow Ends While Application Identification on a Best-Effort Basis

---

If a flow ends while the application identification is on a best-effort basis, ACL or L-PDF uses that best-effort determination as a final determination. ACL or L-PDF performs any necessary collection, aggregation, and reporting of statistics based on that Layer 7 application. In particular, if the **count** ACL term action is configured for that Layer 7 application, then the statistics for the flow are collected and aggregated against the ACL or L-PDF statistics. However, in the case of nested applications, ACL and L-PDF do not consider the best-effort determination as final and the nested application is reported as an unknown application.

#### Related Documentation

- [Configuring ACL Rules on page 21](#)
- [Configuring Statistics Profiles on page 56](#)
- [acl-fields on page 66](#)

- [aacl-statistics-profile on page 67](#)
- [rule on page 107](#)
- [services on page 116](#)
- [term on page 123](#)
- [then on page 124](#)

---

## Configuring AACL Rules

To configure an AACL rule, include the **rule** *rule-name* statement at the **[edit services aacl]** hierarchy level:

```
rule rule-name {
  match-direction (input | output | input-output);
  term term-name {
    from {
      application-group-any;
      application-groups [ application-group-names ];
      applications [ application-names ];
      destination-address address <any-unicast>;
      destination-address-range low minimum-value high maximum-value;
      destination-prefix-list list-name;
      nested-applications [ nested-application-names ];
      nested-application-unknown
      source-address address <any-unicast>;
      source-address-range low minimum-value high maximum-value;
      source-prefix-list list-name;
    }
    then {
      (accept | discard);
      count (application | application-group | application-group-any | nested-application
        | none);
      forwarding-class class-name;
      policer policer-name;
    }
  }
}
```

Each AACL rule consists of a set of terms, similar to a filter configured at the **[edit firewall]** hierarchy level. A term consists of the following:

- **from** statement—Specifies the match conditions and applications that are included and excluded.
- **then** statement—Specifies the actions and action modifiers to be performed by the router software.

The following sections explain how to configure the components of AACL rules:

- [Configuring Match Direction for AACL Rules on page 22](#)
- [Configuring Match Conditions in AACL Rules on page 22](#)

- [Configuring Actions in ACL Rules on page 23](#)
- [Logging ACL Flows Based on Application on page 24](#)

## Configuring Match Direction for ACL Rules

Each rule must include a **match-direction** statement that specifies the direction in which the rule match is applied. To configure where the match is applied, include the **match-direction** statement at the **[edit services aac1 rule *rule-name*]** hierarchy level:

```
match-direction (input | output | input-output);
```

If you configure **match-direction input-output**, bidirectional rule creation is allowed.

The match direction is used with respect to the traffic flow through the services PIC or DPC. When a packet is sent to the PIC or DPC, direction information is carried along with it.

With an interface service set, packet direction is determined by whether a packet is entering or leaving the interface on which the service set is applied.

With a next-hop service set, packet direction is determined by the interface used to route the packet to the services PIC or DPC. If the inside interface is used to route the packet, the packet direction is input. If the outside interface is used to direct the packet to the PIC or DPC, the packet direction is output. For more information on inside and outside interfaces, see *Configuring Service Sets to be Applied to Services Interfaces*.

On the PIC or DPC, a flow lookup is performed. If no flow is found, rule processing is performed. All rules in the service set are considered. During rule processing, the packet direction is compared against rule directions. Only rules with direction information that matches the packet direction are considered.

## Configuring Match Conditions in ACL Rules

To configure ACL match conditions, include the **from** statement at the **[edit services aac1 rule *rule-name* term *term-name*]** hierarchy level:

```
from {  
  application-group-any;  
  application-groups [ application-group-names ];  
  applications [ application-names ];  
  destination-address address <any-unicast>;  
  destination-address-range low minimum-value high maximum-value;  
  destination-prefix-list list-name;  
  nested-applications [ nested-application-names ];  
  nested-application-unknown;  
  source-address address <any-unicast>;  
  source-address-range low minimum-value high maximum-value;  
  source-prefix-list list-name;  
}
```

IPv4 and IPv6 source and destination addresses are supported. You can use either the source address or the destination address as a match condition, in the same way that you configure a firewall filter; for more information, see the *Routing Policies, Firewall Filters, and Traffic Policers Feature Guide*.

Alternatively, you can specify a list of source or destination prefixes by configuring the **prefix-list** statement at the **[edit policy-options]** hierarchy level and then including either the **destination-prefix-list** or the **source-prefix-list** statement in the ACL rule. For an example, see [“Example: Configuring ACL Rules” on page 25](#).

If you omit the **from** term, the ACL rule accepts all traffic and the default protocol handlers take effect:

- User Datagram Protocol (UDP), Transmission Control Protocol (TCP), and Internet Control Message Protocol (ICMP) create a bidirectional flow with a predicted reverse flow.
- IP creates a unidirectional flow.

You can also include application and application group definitions you have configured at the **[edit services application-identification]** hierarchy level; for more information, see the topics in [“APPID Overview” on page 29](#).

- To apply one or more specific application protocol definitions, include the **applications** statement at the **[edit services aacl rule rule-name term term-name from]** hierarchy level.
- To apply one or more sets of application group definitions you have defined, include the **application-groups** statement at the **[edit services aacl rule rule-name term term-name from]** hierarchy level.



**NOTE:** If you include one of the statements that specifies application protocols, the router derives port and protocol information from the corresponding configuration at the **[edit services application-identification]** hierarchy level; you cannot specify these properties as match conditions.

- To consider any application group defined in the database as a match, include the **application-group-any** statement at the **[edit services aacl rule rule-name term term-name from]** hierarchy level.
- To consider any nested application defined in the database a match, include the **nested-applications** statement at the **[edit services aacl rule rule-name term term-name from]** hierarchy level. Nested applications are protocols that run on a parent application. For example, if the Facebook application runs on the parent application `junos:http`, the nested application is `junos:http:facebook`.

## Configuring Actions in ACL Rules

To configure ACL actions, include the **then** statement at the **[edit services aacl rule rule-name term term-name]** hierarchy level:

```
then {
  (accept | discard);
  (count (application | application-group | application-group-any | nested-application |
    none) | forwarding-class class-name);
}
```

You must include one of the following actions:

- **accept**—The packet is accepted and sent on to its destination.
- **discard**—The packet is not accepted and is not processed further.

When you select **accept** as the action, you can optionally configure one or both of the following action modifiers. No action modifiers are allowed with the **discard** action.

- **count (application | application-group | application-group-any | nested-application | none)**—For all accepted packets that match the rules, record a packet count using AACL statistics practices. You can specify one of the following options; there is no default setting:
  - **application**—Count the application that matched in the **from** clause.
  - **application-group**—Count the application group that matched in the **from** clause.
  - **application-group-any**—Count all application groups that match **from** **application-group-any** under the **any** group name.
  - **nested-application**—Count all nested applications that matched in the **from** clause.
  - **none**—Same as not specifying **count** as an action.



NOTE:

- When a session closes before APPID has identified nested applications, the session is treated as a best-effort session and AACL does not get the nested application information. In such cases, nested applications are reported as unknown applications.
- During the time that the application identification (APPID) feature has not yet made a final determination of the application associated with a given flow, the flow does not contribute to any per-subscriber or per-application statistics collection. For more information, see [“Best-Effort Application Identification of DPI-Serviced Flows” on page 18](#).

- **forwarding-class *class-name***—Specify the packets' forwarding-class name.

You can optionally include a **policer** that has been specified at the **[edit firewall]** hierarchy level. Only the bit-rate and burst-size properties specified for the policer are applied in the AACL rule set. The only action application when a policer is configured is **discard**. For more information on policer definitions, see the *Routing Policies, Firewall Filters, and Traffic Policers Feature Guide*.

## Logging AACL Flows Based on Application

You can now log AACL flows based on application. You can select a specific application or request information on unknown applications.

You can now configure AACL rules to match unknown applications. All existing actions that can apply to recognized applications can also apply to unknown applications. You

can use the following statements at the **[edit services aacl rule *rule-name* term *term-name* from]** hierarchy level:

- application-group-any
- application-groups
- application-unknown
- applications
- nested-application-unknown
- nested-applications

The addition of matching **application-unknown** enables the specific logging of the input flows associated with applications that cannot be identified. Because logging is triggered by an input event, you must specify **match-direction** as **input-output** or **input**.

To configure logging of flows for AACL, include the **match-direction input** or **match-direction input-output** statement at the **[edit services aacl rule *rule-name*]** hierarchy level, include an **applications** or **application-unknown** statement at the **[edit services aacl rule *rule-name* term *term-name* from]** hierarchy level, and include only one **log** statement at the **[edit services aacl rule *rule-name* term *term-name* then]** hierarchy level. The log statements can include any of the following options:

- session-start
- session-end
- session-start-end-no-stats
- session-start-interim-end
- session-interim-end
- session-end

#### Related Documentation

- [APPID Overview on page 29](#)
- [Configuring AACL Rule Sets on page 26](#)
- [Configuring Logging of AACL Flows on page 27](#)
- [Example: Configuring AACL Rules on page 25](#)

---

## Example: Configuring AACL Rules

The following example shows an AACL configuration containing a rule with three terms using a variety of match conditions and actions:

```
[edit services aacl]
rule aacl-test {
  match-direction input;
  term term1 {
    from {
```

```
        source-address 10.0.1.1
        application test1;
    }
    then {
        accept;
    }
}
term term2 {
    from {
        source-address {
            any-unicast;
        }
        application test1;
    }
    then {
        discard;
    }
}
term term3 {
    from {
        source-address {
            any-unicast;
        }
        application test1 test2;
    }
    then {
        accept;
        count application;
    }
}
}
```

- Related Documentation**
- [AACL Overview on page 17](#)
  - [Configuring AACL Rules on page 21](#)

---

## Configuring AACL Rule Sets

The **rule-set** statement defines a collection of AACL rules that determine what actions the router software performs on packets in the data stream. You define each rule by specifying a rule name and configuring terms. Then, you specify the order of the rules by including the **rule-set** statement at the **[edit services aacl]** hierarchy level with a **rule** statement for each rule:

```
rule-set rule-set-name {
    rule rule-name;
}
```

The router software processes the rules in the order in which you specify them in the configuration. If a term in a rule matches the packet, the router performs the corresponding action and the rule processing stops. If no term in a rule matches the packet, processing continues to the next rule in the rule set. If none of the rules matches the packet, the packet is dropped by default.

- Related Documentation**
- [AACL Overview on page 17](#)
  - [Configuring AACL Rules on page 21](#)
  - [Configuring Logging of AACL Flows on page 27](#)
  - [Example: Configuring AACL Rules on page 25](#)

---

## Configuring Logging of AACL Flows

You can configure logging of AACL flows for a given application or for all unknown applications using AACL rules. You must set **match-direction** to **input** or **input-output** for logging to occur.

1. Create a rule and term.

```
user@host# edit services aacl rule rule-name term term-name
```

2. Specify selection of an application.

```
[edit services aacl rule rule-name term term-name]  
user@host# set from applications application-name
```

OR

Specify selection of all unknown applications.

```
[edit services aacl rule <variable>rule-name</variable> term  
<variable>term-name</variable>]  
set from application-unknown
```

3. In the **then** statement, specify logging of input flow.

```
[edit services aacl rule rule-name term term-name]  
user@host# set then log input-flows]
```

### Example—Configuration of Logging of Input Flows for Unknown Applications

```
[edit services aacl rule aacl_rule5]  
match-direction input-output;  
term t0 {  
  from {  
    application-unknown;  
  }  
  then {  
    count application;  
    log input-flow;  
    accept;  
  }  
}
```

### Example—Setup of a Specific Log File

The following example shows how to direct the aacl flow log to a file other than the default syslog file on the Routing Engine file system.

```
[edit system syslog]  
file aacl_log {
```

```
external any;  
match aacl-flow-log;  
}
```

- Related Documentation**
- [AACL Overview on page 17](#)
  - [Configuring AACL Rules on page 21](#)
  - [Configuring AACL Rule Sets on page 26](#)
  - [Example: Configuring AACL Rules on page 25](#)

## CHAPTER 2

# Grouping Applications Together Using APPID

- [APPID Overview on page 29](#)
- [Best-Effort Application Identification of DPI-Serviced Flows on page 32](#)
- [Defining an Application Identification on page 34](#)
- [Configuring APPID Rules on page 36](#)
- [Using Stateful Firewall Rules to Identify Data Sessions on page 37](#)
- [Configuring Application Profiles on page 39](#)
- [Configuring Application Groups on page 40](#)
- [Application Identification for Nested Applications on page 41](#)
- [Disabling Application Identification for Nested Applications on page 42](#)
- [Configuring Global APPID Properties on page 43](#)
- [Configuring APPID Support for Heuristics on page 44](#)
- [Configuring APPID Support for Unidirectional Traffic on page 45](#)
- [Configuring Automatic Download of Application Package Updates on page 46](#)
- [Tracing APPID Operations on page 46](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

## APPID Overview

---



**NOTE:** Starting with Junos OS Release 16.1R1, the APPID feature is not supported.



**NOTE:** Starting with Junos OS Release 12.1, all interface-style services are supported for dynamic Point-to-Point Protocol over Ethernet (PPPoE) subscribers on all MX Series routers with modular Modular Port Concentrators (MPCs).

The APPID feature identifies applications as constituents of application groups in TCP/UDP/ICMP traffic. It is supported on MX Series routers equipped with Multiservices DPCs and on M120 or M320 routers equipped with Multiservices 400 PICs and Aggregated Multiservices (AMS) PICs. Aggregated Multiservices PICs (ams- interfaces) enable multiple ms- interfaces to be grouped together in a single bundle and cause the traffic destined for this AMS group to be distributed over the member services PICs of the group. Junos OS Trio chipsets enable the calculation of a symmetric hash for the forward and reverse flows, and support a microcode map in the forwarding plane. This capability enables load-balancing of traffic across various services PICs in an AMS group. Starting with Junos OS Release 12.1, ams- interfaces enable an N:1 redundancy mechanism to cluster together N number of ms- interfaces in an AMS group that supports load sharing.



**NOTE:** For ams- interfaces and rms- interfaces, the statistics data in the bulk statistics file is collected using the reports received from the MS PICs. For the ams- interfaces, the retrieval and storage of statistics is not possible because of multiple PICs containing statistics data for the same subscriber. For interfaces in an AMS group, statistics data from different MS PICs in the AMS group are collected and aggregated on the Routing Engine where a timer control is activated and the data is saved in the bulkstats file based on this timer. This method of collection causes the statistics data in the bulkstats file to be displayed with a small delay period.

To configure APPID, include statements at the **[edit services application-identification]** hierarchy level to specify parameter values for defining applications, enable or disable application rules, and gather the applications and rules into groups.

The following are related operational commands:

- **show/clear application-identification application-system-cache**
- **show/clear application-identification counters**

For more information on the CLI configuration, see the [“Configuring APPID Rules” on page 36](#). For more information on the operational commands, see the [CLI Explorer](#).



**NOTE:** Because the extension-provider package framework lacks aggressive constraint checks, you should not set the `policy-db-size` statement at the `[edit chassis fpc slot-number pic pic-number adaptive-services service-package extension-provider]` hierarchy level to a high value. For Junos Application Aware (previously known as Dynamic Application Awareness) configurations, the recommended values for the extension-provider package options at this hierarchy level are as follows:

- `control-cores = 1`
- `data-cores = 7`
- `object-cache-size = 1280` (for Multiservices 400 PIC and Multiservices DPC)
- `policy-db-size = 200`
- Include these package values: `jservices-idp`, `jservices-appid`, `jservices-llpdf`, `jservices-aac1`

For more information about this configuration, see the following topics in the *SDK Applications Configuration Guide and Command Reference*:

- *Configuring Control and Data Cores*
- *Configuring Packages on the PIC*



**NOTE:** In the export version of Junos OS, signature download is not expected to work for the AppID feature in Junos Application Aware. In order to make it work, you must additionally install the Crypto Software Suite.

Release History Table

Release	Description
16.1R1	Starting with Junos OS Release 16.1R1, the APPID feature is not supported.

#### Related Documentation

- [Defining an Application Identification on page 34](#)
- [Configuring APPID Rules on page 36](#)
- [Application Identification for Nested Applications on page 41](#)
- [Configuring Global APPID Properties on page 43](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

## Best-Effort Application Identification of DPI-Serviced Flows

---

This topic describes the following information:

- [Features That Support Application-Level Filtering on page 32](#)
- [Best-Effort Application Determination on page 32](#)
- [APPID, AACL, and L-PDF Processing in Preconvergence Scenarios on page 32](#)

### Features That Support Application-Level Filtering

The application-aware access list (AACL) service uses application names and groups as matching criteria for filtering traffic. The service defines the applications and application groups for which statistics are collected for a specific user or interface.

The local policy decision function (L-PDF) enables you to configure properties for statistics output. L-PDF supports a process that regulates collection of statistics related to applications and application groups and tracking of information about dynamic subscribers and static interfaces.

### Best-Effort Application Determination

Typically, APPID conclusively determines the Layer 7 application associated with a given DPI-serviced flow. In these cases, the application identification is final. Occasionally, APPID is only able to make an initial, inconclusive determination of the Layer 7 application associated with a given flow. This is referred to as a *best-effort* application identification. In such cases, the APPID process continues processing packets on that flow and might subsequently make a conclusive determination of the application associated with that flow. In some cases of best-effort application identification, the flow ends before a final application determination can be made.

### APPID, AACL, and L-PDF Processing in Preconvergence Scenarios

The following sections describe APPID, AACL, and L-PDF processing in various stages of application identification for a DPI-serviced flow of TCP/UDP/ICMP traffic.

- [Prior to a Final or Best-Effort Application Identification on page 32](#)
- [Upon Best-Effort Application Identification on page 33](#)
- [While Application Identification Is on a Best-Effort Basis on page 33](#)
- [If a Flow Ends Before an Application Identification Is Made on page 33](#)
- [If a Flow Ends While Application Identification on a Best-Effort Basis on page 33](#)

#### Prior to a Final or Best-Effort Application Identification

During the time that APPID has not yet made either a final or best-effort determination of the application associated with a given flow, the flow does not contribute to any per-subscriber or per-application statistics collection.

The output of the following operational mode commands includes flows for which APPID has not yet made either a final or best-effort determination of the associated application:

- **show services local-policy-decision-function flows** (interface *interface-name* | subscriber *subscriber-name*)
- **show services application-aware-access-list flows** (interface *interface-name* | subscriber *subscriber-name*)

In the command output, the **Action** field displays **accept** and the **Application** or **Application group** field displays **unknown** for a flow for which APPID has not yet made either a final or best-effort determination of the associated application.

### Upon Best-Effort Application Identification

When a best-effort application determination is made, AACL does not apply any AACL term actions configured for that flow. There are a number of reasons for this, one being that the action itself (such as **discard**) can make a final application determination impossible. Instead, AACL or L-PDF tracks the flow and accepts all packets for that flow until a final determination is made, at which time the normal AACL or L-PDFL actions are fully applied to the flow.

### While Application Identification Is on a Best-Effort Basis

During the time that APPID identification of the application associated with a given flow is on a best-effort basis, the flow does not contribute to any per-subscriber or per-application statistics collection.

The output of the following operational mode commands includes flows for which APPID has only made a best-effort determination of the associated application:

- **show services local-policy-decision-function flows** (interface *interface-name* | subscriber *subscriber-name*)
- **show services application-aware-access-list flows** (interface *interface-name* | subscriber *subscriber-name*)

In the command output, the **Action** field displays **accept** and the **Application** or **Application group** field displays **unknown** for a flow for which APPID has only made a best-effort determination of the associated application.

### If a Flow Ends Before an Application Identification Is Made

If a flow ends before APPID has made either a final or a best-effort application identification, AACL or L-PDF uses the **unknown** application ID as a final determination and performs any necessary collection, aggregation, and reporting of statistics based on that Layer 7 application. In particular, if the **count** AACL term action is configured for the **application-group-any** application, then the statistics for that flow are collected and aggregated against the count bucket type, and reported as such.

### If a Flow Ends While Application Identification on a Best-Effort Basis

If a flow ends while the application identification is on a best-effort basis, AACL or L-PDF uses that best-effort determination as a final determination. AACL or L-PDF performs

any necessary collection, aggregation, and reporting of statistics based on that Layer 7 application. In particular, if the **count** ACL term action is configured for that Layer 7 application, then the statistics for the flow are collected and aggregated against the ACL or L-PDF statistics. However, in the case of nested applications, ACL and L-PDF do not consider the best-effort determination as final and the nested application is reported as an unknown application.

**Related Documentation**

- [Configuring ACL Rules on page 21](#)
- [Configuring Statistics Profiles on page 56](#)
- [aacl-fields on page 66](#)
- [aacl-statistics-profile on page 67](#)
- [rule on page 107](#)
- [services on page 116](#)
- [term on page 123](#)
- [then on page 124](#)

---

## Defining an Application Identification

To configure a specific IP address or port-based application identification, include the **application** *application-name* statement at the **[edit services application-identification]** hierarchy level:

```
application application-name {  
  disable;  
  idle-timeout seconds;  
  index number;  
  session-timeout seconds;  
  type type;  
  type-of-service service-type;  
  port-mapping {  
    port-range {  
      tcp [ ports-and-port-ranges ];  
      udp [ ports-and-port-ranges ];  
    }  
    disable;  
  }  
}
```

You can include the following general properties in the configuration:

- **application**—Application name, a required statement; maximum 31 characters. Predefined applications have the prefix **junos-** to avoid conflict with user-defined ones.
- **idle-timeout**—Amount of time that a session remains idle before it is deleted.
- **index**—Application index number in the range from 1 through 65,534, with integers 1 through 1024 reserved for predefined applications.
- **session-timeout**—Lifetime of a session.

- **type**—Well known applications, such as HTTP or FTP.
- **type-of-service**—Type of service, defined by service objective. There is no default value; options are **maximize-reliability**, **maximize-throughput**, **minimize-delay**, and **minimize-monetary-cost**.
- **disable**—Disable this application definition in the APPID service.



**NOTE:** You can also specify session and idle timeout values globally for a Multiservices interface by including the following statements at the [edit interfaces *interface-name* services-options] hierarchy level:

- **inactivity-non-tcp-timeout**—Inactivity timeout period for non-TCP established sessions.
- **inactivity-tcp-timeout**—Inactivity timeout period for TCP established sessions.
- **session-timeout**—Lifetime of a session.
- **disable-global-timeout-override**—Disallow overriding a global inactivity or session timeout.

You can include the following port-mapping properties at the [edit services application-identification port-mapping] hierarchy level:

- **port-range**—TCP or UDP port number or numeric range, entered as [*minimum-value* – *maximum-value*]. For port-mapping configurations, this entry is required if the parent node exists.
- **disable**—Disable port-mapping properties for this application.



**NOTE:** For applications with signatures for both client-to-server and server-to-client directions, the APPID for Junos Application Aware (previously known as Dynamic Application Awareness) must accept the data packets in both directions on the same session to complete the identification process.

For a configuration example, see “[Examples: Configuring Application Identification Properties](#)” on page 48.

#### Related Documentation

- [APPID Overview on page 29](#)
- [Configuring APPID Rules on page 36](#)
- [Using Stateful Firewall Rules to Identify Data Sessions on page 37](#)
- [Configuring Application Profiles on page 39](#)
- [Configuring Application Groups on page 40](#)
- [Tracing APPID Operations on page 46](#)

## Configuring APPID Rules

This configuration specifies the properties for identifying an application for which a source or destination IP address and port is used for a known application, without the requirement of an application signature. For example, the Session Initiation Protocol (SIP) server initiates a session from its identified port, 5060. You can therefore specify the SIP server IP address and port 5060 in the port mapping configuration for the SIP application. The advantage of using this method is to provide efficiency and accuracy of application identification for your network.

To configure application rule properties, include the **rule** statement at the **[edit services application-identification]** hierarchy level:

```
rule rule-name {
  address address-name {
    destination {
      ip address</prefix-length>;
      port-range {
        tcp [ ports-and-port-ranges ];
        udp [ ports-and-port-ranges ];
      }
    }
    source {
      ip address</prefix-length>;
      port-range {
        tcp [ ports-and-port-ranges ];
        udp [ ports-and-port-ranges ];
      }
    }
    order number;
  }
  application application-name;
  disable;
}
```

You can include the following application rule properties:

- **address**—Address properties for APPID rule processing. This statement is mandatory; you must specify either destination or source properties.
- **destination**—Destination address and port information. The **ip** statement defines the IP address and netmask (IPv4 only), and the **port-range** statement defines the TCP or UDP port number or numeric range, entered as **[*minimum-value* – *maximum-value*]**.
- **source**—Source address and port information. The **ip** statement defines the IP address and netmask (IPv4 only), and the **port-range** statement defines the TCP or UDP port number or numeric range, entered as **[*minimum-value* – *maximum-value*]**.
- **order**—Application matching priority. For address configurations, the order number resolves the conflict when multiple address entries are matched for a specific session; the lower the number, the higher the priority. This statement is mandatory and must contain a unique value.

- **application**—Name of the application to be included in the rule.
- **disable**—Disable processing for this application rule.

The **rule-set** statement defines a collection of APPID rules that determine what actions the router software performs on packets in the data stream. You define each rule by specifying a rule name and configuring terms. Then, you specify the order of the rules by including the **rule-set** statement at the **[edit services application-identification]** hierarchy level with a **rule** statement for each rule:

```
rule-set rule-set-name {  
  rule application-rule-name;  
}
```

**Related  
Documentation**

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Using Stateful Firewall Rules to Identify Data Sessions on page 37](#)
- [Configuring Application Profiles on page 39](#)
- [Configuring Application Groups on page 40](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

---

## Using Stateful Firewall Rules to Identify Data Sessions

The APPID configuration properties enable the Junos OS to detect applications based on signatures, ports, and addresses. For signature-based detection, most of the protocol control sessions are identified, but data sessions are not identified. For example, APPID identifies FTP connections to port 21 (FTP control sessions); however, FTP can open child/data sessions to transfer files and data. These sessions are not identified by signature-based APPID because they do not have well-defined signatures.

Application-level gateways (ALGs) configured using stateful firewall rules can assist APPID in identifying these data sessions. These sessions include file and video transfers that are heavy consumers of bandwidth, so a mechanism for policing and classifying this traffic effectively is a useful tool. In addition to FTP, this mechanism applies to TFTP and RTSP traffic.

To incorporate the stateful firewall rules into Junos Application Aware (previously known as Dynamic Application Awareness for Junos OS) sessions, include the following configurations:

1. Include the stateful firewall package at the **[edit chassis fpc slot-number pic pic-number adaptive-services service-package extension-provider]** hierarchy level:  

```
package jservices-sfw;
```
2. Define two stateful firewall rules as shown in the following example, one to identify the appropriate ALGs for FTP, TFTP, or RTSP traffic and the other to allow all traffic:



**NOTE:** Session Initiation Protocol (SIP) is already covered by APPID and the SIP ALG is not supported by stateful firewall, hence a SIP configuration is not needed.

```
[edit services]
stateful-firewall {
  rule rule1 {
    match-direction input-output;
    term term1 {
      from {
        applications [ junos-ftp junos-tftp junos-rtsp ];
      }
      then {
        accept;
      }
    }
  }
  rule rule2 {
    match-direction input-output;
    term term1 {
      then {
        accept;
      }
    }
  }
  rule-set rs1 {
    rule rule1;
    rule rule2;
  }
}
```



**NOTE:** The existing AACL and L-PDF operational mode commands should report the new applications when they are identified.

3. Attach the stateful firewall rule set to a service set, as shown in the following example:

```
service-set test-chaining {
  application-identification-profile add-based;
  stateful-firewall-rule-sets rs1;
  idp-profile idp1;
  aacl-rules rule1;
  interface-service {
    service-interface ms-2/0/0.0;
  }
}
```

4. Include *no-drop* settings for stateful firewall and TCP, as needed.

Stateful firewall processing drops packets in a number of scenarios:

- TCP sessions do not start with a SYN flag. (This prevents sessions from resuming; otherwise, when the PIC starts for the first time, all existing TCP sessions in flight are dropped).
- If the TCP tracker detects SYN but no SYN/ACK or only an ACK, then the ACK is dropped. There are a number of similar checks to verify the TCP connection, window checks, and so forth.
- TCP checks for stateful firewall are aggressive when ALGs are run. It is not possible to ignore TCP errors when an ALG is run on a session.
- If an ALG detects malformed packets (for example, if the FTP PORT command is not RFC-compliant), it drops packets. If an ALG is not able to allocate resources, it drops packets.

You can include the settings shown in the following example to assist in controlling these packet drops:

```
[edit interfaces]
ms-1/2/0 {
  services-options {
    ignore-errors {
      tcp;
      alg;
    }
  }
}
```

The **tcp** statement mediates the first two issues listed, with reference to TCP SYN detection. The **alg** statement handles the fourth issue. ALGs require strict TCP processing, which cannot be relaxed.

#### Related Documentation

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Application Identification for Nested Applications on page 41](#)
- [Configuring Global APPID Properties on page 43](#)
- [Tracing APPID Operations on page 46](#)

---

## Configuring Application Profiles

You can define an application profile for use in a service set. The profile consists of one or more rule sets, but only one profile can be included per service set.

To specify the application profile constituents, include the **profile** statement at the **[edit services application-identification]** hierarchy level:

```
profile profile-name {
  [ rule-set rule-set-name ];
}
```

You assign a profile name and include one or more predefined rule sets. For more information on rule sets, see [“Configuring APPID Rules” on page 36](#). You can then include the profile in a service-set definition:

```
[edit services]
service-set service-set-name {
  profile profile-name;
}
```

The definitions specific to Junos Application Aware (previously known as Dynamic Application Awareness) include the APPID profile and the ACL rule set. For more information on service sets, see *Understanding Service Sets*.

- Related Documentation**
- [APPID Overview on page 29](#)
  - [Defining an Application Identification on page 34](#)
  - [Configuring Application Groups on page 40](#)
  - [Configuring Global APPID Properties on page 43](#)

---

## Configuring Application Groups

You can define an application group to process a number of applications or subgroups at the same time. To configure application group properties, include the **application-group** statement at the **[edit services application-identification]** hierarchy level:

```
application-group group-name {
  application-groups {
    application-group-name;
  }
  applications {
    application-name;
  }
  index number;
  disable;
}
```

You can include the following application group properties:

- **applications**—List of applications to include in this application group. The **name** statement is mandatory and must include at least one entry.
- **application-groups**—List of application groups to include in a larger application group. The **name** statement is mandatory and must include at least one entry.
- **index**—Application group index number in the range from 1 through 65,534. This mandatory value must be unique.
- **disable**—Disable processing for this application group.

- Related Documentation**
- [Defining an Application Identification on page 34](#)
  - [Configuring APPID Rules on page 36](#)

- [Configuring Application Profiles on page 39](#)
- [Configuring Global APPID Properties on page 43](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

## Application Identification for Nested Applications

*Nested applications* are protocols running over the parent application. For example, both Facebook and Yahoo Messenger can run over HTTP, but there is a need to identify them as two different applications. To do this, the application layer is split into two layers: Layer 7 applications and Layer 7 protocols.

The predefined application signatures included with Junos OS have been created to detect the Layer 7 nested applications. Predefined application signatures can be used in attack objects.

To configure nested application properties, include the **nested-application** statement at the **[edit services application-identification]** hierarchy level:

```
nested-application name {
  index number;
  protocol protocol;
  signature name {
    chain-order ;
    maximum-transactions number;
    member name {
      context (http-header-content-type | http-header-host | http-url-parsed |
        http-url-parsed-param-parsed);
      direction (any | client-to-server | server-to-client);
      pattern dfa-pattern;
    }
    order number;
  }
  type type;
}
```

You can include the following application rule properties:

- **chain-order**—Signatures can contain multiple members. If the chain order feature is on, those members are read in order. The default for this option is no chain order. If a signature contains only one member, this option is ignored.
- **context**—Define a service specific context. The options are **http-header-content-type**, **http-header-host**, **http-url-parsed**, **http-url-parsed-param-parsed**. This statement is mandatory.
- **direction**—The connection direction of the packets to apply pattern matching. The options are **client-to-server**, **server-to-client**, or **any**. This statement is mandatory.
- **index**—A number that is a one-to-one mapping to the application name that is used to ensure that each signature definition is unique. The index range for predefined applications is 1 through 32767. The index range for custom applications and custom nested applications is 32768 through 65534.

- **maximum transactions**—The maximum number of transactions that should occur before a match is made. This statement is mandatory.
- **member**—Define a member name for a custom nested application signature definition. Custom definitions can contain multiple members that define attributes for an application.
- **order**—Define application matching priority. For address configurations, the order number resolves the conflict when multiple address entries are matched for a specific session. The lower number has higher priority. This statement is mandatory.
- **pattern**—Define an attack pattern to be detected. This statement is mandatory.
- **protocol**—The protocol that is monitored to identify nested applications. The value **http** is supported. This statement is mandatory.
- **signature**—Name of the custom nested application signature definition. Must be a unique name with a maximum length of 32 characters. This statement is mandatory.
- **type**—Well-known application name for this application definition, such as Facebook or Kazza. This application name must be unique with a maximum length of 32 characters. This statement is mandatory.

**Related  
Documentation**

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Disabling Application Identification for Nested Applications on page 42](#)
- [Configuring Global APPID Properties on page 43](#)
- [Tracing APPID Operations on page 46](#)

---

## Disabling Application Identification for Nested Applications

Sometimes there is a need to identify multiple different applications running on the same Layer 7 protocols. For example, both Facebook and Yahoo Messenger can run over HTTP, but there is a need to identify them as two different applications. To do this, the application layer is split into two layers: Layer 7 applications and Layer 7 protocols. Application identification for nested applications is turned on by default. You can manually turn it off by using the CLI.

To disable nested application identification:

- Set the **no-nested-application** statement.

```
[edit services application-identification nested-application-settings]  
user@host# no-nested-application
```

To verify the configuration, issue the **show services application-identification nested-application-settings** command.

To reenabling nested application identification:

- Delete the **no-nested-application** statement.

```
[edit services application-identification nested-application-settings]
user@host# delete services application-identification nested-application-settings
no-nested-application
```

If you are finished configuring the device, commit the configuration.

**Related  
Documentation**

- [APPID Overview on page 29](#)
- [Application Identification for Nested Applications on page 41](#)

## Configuring Global APPID Properties

You can define additional properties that apply on a global basis to APPID processing and are not part of a specific application, group, rule, or profile definition. To configure these global APPID properties, include the following statements at the **[edit services application-identification]** hierarchy level:

```
application-identification {
  application-system-cache-timeout seconds;
  max-checked-bytes bytes;
  min-checked-bytes bytes;
  nested-application name
  nested-application-settings
  no-application-identification
  no-application-system-cache;
  no-clear-application-system-cache;
  no-protocol-method;
  no-signature-based;
  signature-method-all-ports;
}
```

The global application properties have the following effect:

- **application-system-cache-timeout**—Lifetime for system cache entries, in seconds.
- **max-checked-bytes**—The maximum number of bytes to be inspected in APPID processing, in the range from 0 through 100,000 bytes.
- **min-checked-bytes**—The minimum number of bytes to be inspected in APPID processing, in the range from 0 through 2000 bytes.
- **nested-application**—Configure a custom nested application definition for the desired application name that is used by the system to identify the nested application as it passes through the device. For more information see [nested-application](#).
- **nested-application-settings**—Configure nested application options for application identification services. For more information see [nested-application-settings](#).
- **no-application-identification**—Disable all application identification methods.
- **no-application-system-cache**—Disable storing application identification results in the application system cache.
- **no-clear-application-system-cache**—Disable clearing the application system cache.

- **no-protocol-method**—Disable the protocol-based application identification method, which is enabled by default.
- **no-signature-based**—Disable the signature-based application identification method.
- **signature-method-all-ports**—Run signature matching on all traffic.

**Related  
Documentation**

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Application Identification for Nested Applications on page 41](#)
- [Disabling Application Identification for Nested Applications on page 42](#)
- [Tracing APPID Operations on page 46](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

---

## Configuring APPID Support for Heuristics

---

Heuristics methodology provides a mechanism for identifying encrypted data packets in point-to-point applications. These packets are not normally detected by the existing application signatures.

To enable APPID to employ heuristics in traffic identification:

1. Include the **enable-heuristics** statement:

```
[edit services application-identification]  
user@host# enable-heuristics
```

The **show services application-identification counter** operational command includes additional output fields that report the number of encrypted sessions.



**NOTE:** When you enable heuristics, performance and scaling values might be negatively affected. This mechanism assists the APPID module in identifying encrypted traffic, but only if the identifications are supported by the current signature package.

---

**Related  
Documentation**

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Application Identification for Nested Applications on page 41](#)
- [Configuring Global APPID Properties on page 43](#)
- [Configuring APPID Support for Unidirectional Traffic on page 45](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

## Configuring APPID Support for Unidirectional Traffic

With asymmetrical routing, a networking device sees only one side of the network sessions, either from client to server or from server to client. Additional functionality is required to support application identification with unidirectional traffic. This addition enables a session for a specified service set to support an asymmetrical routing environment, and allows complete application matches using existing application signatures for traffic in the client-to-server direction only.

To enable APPID to support application matching on unidirectional traffic:

1. Include the **support-uni-directional-traffic** statement:

```
[edit services service-set service-set-name service-set-options]
user@host# support-uni-directional-traffic
```

This enables the session belonging to the specified service set to support the asymmetrical routing environment. The APPID module then reports complete matches for the unidirectional traffic.

2. Include the **enable-asymmetric-traffic-processing** statement:

```
[edit services service-set service-set-name service-set-options]
user@host# enable-asymmetric-traffic-processing
```

This enables the framework and plug-in to handle unidirectional traffic at a service-set level.

When you enable these settings, APPID treats unidirectional TCP traffic like a UDP connection. UDP traffic itself does not receive any special treatment because the service PIC cannot determine whether UDP traffic is unidirectional or bidirectional. The settings do not affect processing of sessions created with bidirectional traffic.

If the traffic includes both unidirectional and bidirectional sessions, the APPID module uses heuristics to decide whether to change the reporting logic.



**NOTE:** This feature does not change the processing for any services except APPID. However, other services, including stateful firewall and AACL, can process unidirectional traffic in a limited manner.

### Related Documentation

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Application Identification for Nested Applications on page 41](#)
- [Configuring Global APPID Properties on page 43](#)
- [Configuring APPID Support for Heuristics on page 44](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

## Configuring Automatic Download of Application Package Updates

---

You can set up automatic downloading of application package updates. To configure downloads, include the **download** statement at the **[edit services application-identification]** hierarchy level:

```
download {  
  automatic {  
    interval hour;  
    start-time time;  
  }  
  url url;  
}
```

You can include the following download statements:

- **download**—Define download properties.
- **automatic**—Set **start-time** value and **interval** in hours for automatic downloads. The default **start-time** is **0:00** and the range is from 0:00 through 24:00. The default **interval** is **24** and the range is from 1 through 168.
- **url**—Specify the download URL.

### Related Documentation

- [APPID Overview on page 29](#)
- [Defining an Application Identification on page 34](#)
- [Examples: Configuring Application Identification Properties on page 48](#)

## Tracing APPID Operations

---

Tracing operations track all adaptive services operations and record them in a log file. The logged error descriptions provide detailed information to help you solve problems faster.

By default, no events are traced. If you include the **traceoptions** statement at the **[edit services application-identification]** hierarchy level, the default tracing behavior is as follows:

- Important events are logged in a file called **serviced** located in the **/var/log** directory.
- When the file **serviced** reaches 128 kilobytes (KB), it is renamed **serviced.0**, then **serviced.1**, and so on, until there are three trace files. Then the oldest trace file (**serviced.2**) is overwritten. (For more information about how log files are created, see the [System Log Explorer](#).)
- Only the user who configures the tracing operation can access the log files.
- To display the end of the log, issue the **show log serviced | last** operational mode command:

```
[edit]
```

```
user@host# run show log serviced | last
```

You cannot change the directory (`/var/log`) in which trace files are located. However, you can customize the other trace file settings by including the following statements:

```
file filename <files number> <match regex> <size size> <(world-readable |  
no-world-readable);  
flag {  
  all;  
}
```

You configure these statements at the **[edit services application-identification traceoptions]** hierarchy level.

These statements are described in the following sections:

- [Configuring the APPID Log Filename on page 47](#)
- [Configuring the Number and Size of APPID Log Files on page 47](#)
- [Configuring Access to the Log File on page 48](#)
- [Configuring a Regular Expression for Lines to Be Logged on page 48](#)
- [Configuring the Tracing Flags on page 48](#)

## Configuring the APPID Log Filename

By default, the name of the file that records trace output is **serviced**. You can specify a different name by including the **file** statement at the **[edit services application-identification traceoptions]** hierarchy level:

```
file filename;
```

## Configuring the Number and Size of APPID Log Files

By default, when the trace file reaches 128 kilobytes (KB) in size, it is renamed **filename.0**, then **filename.1**, and so on, until there are three trace files. Then the oldest trace file (**filename.2**) is overwritten.

You can configure the limits on the number and size of trace files by including the following statements at the **[edit services application-identification traceoptions]** hierarchy level:

```
file files number size size;
```

For example, set the maximum file size to 2 MB, and the maximum number of files to 20. When the file that receives the output of the tracing operation (**filename**) reaches 2 MB, **filename** is renamed **filename.0**, and a new file called **filename** is created. When the new **filename** reaches 2 MB, **filename.0** is renamed **filename.1** and **filename** is renamed **filename.0**. This process repeats until there are 20 trace files. Then the oldest file (**filename.19**) is overwritten by the newest file (**filename.0**).

The number of files can be from 2 through 1000 files. The file size of each file can be from 10 KB through 1 gigabyte (GB).

## Configuring Access to the Log File

By default, only the user who configures the tracing operation can access log files.

To specify that any user can read all log files, include the **file world-readable** statement at the **[edit services application-identification traceoptions]** hierarchy level:

```
file world-readable;
```

To explicitly set the default behavior, include the **file no-world-readable** statement at the **[edit services application-identification traceoptions]** hierarchy level:

```
file no-world-readable;
```

## Configuring a Regular Expression for Lines to Be Logged

By default, the trace operation output includes all lines relevant to the logged events.

You can refine the output by including the **match** statement at the **[edit services application-identification traceoptions file filename]** hierarchy level and specifying a regular expression (regex) to be matched:

```
file filename match regex;
```

## Configuring the Tracing Flags

By default, if the **traceoptions** configuration is present, only important events are logged. You can configure the trace operations to be logged by including the following statements at the **[edit services application-identification traceoptions]** hierarchy level:

```
flag {  
  all;  
}
```

Currently, the only supported flag is **all**, which instructs the router to trace all operations.

- Related Documentation**
- [APPID Overview on page 29](#)
  - [Defining an Application Identification on page 34](#)
  - [Examples: Configuring Application Identification Properties on page 48](#)

---

## Examples: Configuring Application Identification Properties

The following examples show an address-based application identification configuration:

```
[edit services application-identification]  
rule rule1 {  
  application-name test2;  
  address 1 {  
    source {  
      ip 10.110.1.1/16;  
      port-range {  
        tcp 1110-1150;      }  
    }  
  }  
}
```

```
    }  
  }  
  destination {  
    ip 10.11.1.1/16;  
    port-range {  
      tcp 111-1100;  
    }  
  }  
  order 1;  
}  
}  
}  
[edit services application-identification]  
rule-set rs1 {  
  rule rule1;  
}  
profile pf1 {  
  rule-set rs1;  
}  
[edit services]  
service-set sset1 {  
  application-identification-profile pf1;  
}
```

The following examples show application group configuration:

```
[edit services application-identification]  
application-group junos:peer-to-peer {  
  index 5;  
  application-groups {  
    junos:chat;  
    junos:file-sharing;  
    junos:voip;  
  }  
}  
[edit services application-identification]  
application-group junos:voip {  
  index 14;  
  applications {  
    junos:h225ras;  
    junos:h225sgn;  
    junos:mgcp;  
    junos:sip;  
  }  
}
```

The following examples show application identification for nested application configuration:

```
nested-application nested1 {  
  type nested1;  
  index 65345;  
  protocol HTTP;  
  signature nestedcust001 {  
    member m01 {
```

```
context http-url-parsed;  
pattern .*nested.*;  
direction any;  
}  
maximum-transactions 2;  
order 3825;
```

## CHAPTER 3

# Collecting Statistics and Tracking Data Using L-PDF

- L-PDF Overview on page 51
- Best-Effort Application Identification of DPI-Serviced Flows on page 53
- Configuring Statistics Profiles on page 56
- Applying L-PDF Profiles to Service Sets on page 59
- Tracing L-PDF Operations on page 61

## L-PDF Overview

---



**NOTE:** Starting with Junos OS Release 16.1R1, the local policy decision function is not supported.



**NOTE:** Starting with Junos OS Release 12.1, all interface-style services are supported for dynamic Point-to-Point Protocol over Ethernet (PPPoE) subscribers on all MX Series routers with modular Modular Port Concentrators (MPCs).

Starting with Junos OS Release 12.1, the local policy decision function (L-PDF) plug-in can offload flows to the Packet Forwarding Engine. Offloading is supported only on MX Series routers with Modular Port Concentrators (MPCs) and accomplished using the Juniper Forwarding Mechanism (JFM). JFM allows services flows to be offloaded to the Packet Forwarding Engine. However, 5-tuple flows cannot be offloaded. Apart from the local L-PDF plug-in, offloading is supported on the packet-triggered subscribers and policy control (PTSP) plug-in. The `show services application-aware-access-list flows subscriber subscriber-name` command displays offload status.

Local policy decision functionality for application-related services adds support for a new process that regulates collection of statistics related to applications and application groups and tracking of information about dynamic subscribers and static interfaces. This

functionality is collectively named the local policy decision function (L-PDF). L-PDF is supported on:

- MX Series routers equipped with Multiservices DPCs.
- M120 or M320 routers equipped with Multiservices 400 PICs.
- Aggregated Multiservices (AMS) PICs.

Multiple **ms-** interfaces can be bundled together in an AMS PIC interface, which causes the traffic destined for this AMS group to be distributed over the member services PICs of the group. Junos OS Trio chipsets enable the calculation of a symmetric hash for the forward and reverse flows, and support a microcode map in the forwarding plane. This capability enables load-balancing of traffic across various services PICs in an AMS group. Starting with Junos OS Release 12.1, **ams-** interfaces enable an N:1 redundancy mechanism to cluster together N number of **ms- interfaces** in an AMS group that supports load sharing.

Starting with Junos OS Release 11.3, local L-PDF that resides on the services PIC is supported on T320, T640, and T1600 routers. The application identification (APPID) service defines the applications and how they are grouped. The application-aware access list (AACL) service defines the applications and application groups for which statistics are collected for a specific user or interface. The L-PDF configuration defines the way in which the statistics are output.

To configure properties for statistics output, include the **policy-decision-statistics-profile** statement at the **[edit accounting-options]** hierarchy level. A new **traceoptions** configuration is available at the **[edit system services local-policy-decision-function]** hierarchy level. To configure a dynamic profile to attach a specified service set to an interface, include the **service** statement at the **[edit dynamic-profiles *profile-name* interfaces *interface-name* unit *logical-unit-number* family inet]** hierarchy level. To attach a service set to a static interface, include the **service-set *service-set-name*** statement at the **[edit interfaces *interface-name* unit *logical-unit-number* family inet service (input | output)]** hierarchy level. For more information on service sets, see *Understanding Service Sets*.

The following related operational commands are supported:

- **show services local-policy-decision-function flows**
- **show/clear services local-policy-decision-function statistics**
- **show/clear services application-aware-access-list statistics**

For more information on the CLI configuration, see the [“Best-Effort Application Identification of DPI-Serviced Flows” on page 18](#). For more information on the operational commands, see the [CLI Explorer](#).



**NOTE:** Because the Junos OS extension-provider package (variously known as JSF, MP-SDK, and eJunos in releases earlier than 12.3) lacks aggressive constraint checks, you should not set the `policy-db-size` statement at the [edit chassis fpc slot-number pic pic-number adaptive-services service-package extension-provider] hierarchy level to a high value. For Junos Application Aware (previously known as Dynamic Application Awareness) configurations, the recommended values for the extension-provider package options at this hierarchy level are as follows:

- `control-cores` = 1
- `data-cores` = 7
- `object-cache-size` = 1280 (for Multiservices 400 PIC and Multiservices DPC)
- `policy-db-size` = 200
- Include these package values: `jservices-idp`, `jservices-appid`, `jservices-llpdf`, `jservices-aacl`

For more information about this configuration, see the following topics in the *SDK Applications Configuration Guide and Command Reference*:

- *Configuring Control and Data Cores*
- *Configuring Packages on the PIC*

Release History Table

Release	Description
16.1R1	Starting with Junos OS Release 16.1R1, the local policy decision function is not supported.

Related Documentation

- [Best-Effort Application Identification of DPI-Serviced Flows on page 18](#)
- [Configuring Statistics Profiles on page 56](#)
- [Applying L-PDF Profiles to Service Sets on page 59](#)
- [Tracing L-PDF Operations on page 61](#)

## Best-Effort Application Identification of DPI-Serviced Flows

This topic describes the following information:

- [Features That Support Application-Level Filtering on page 54](#)
- [Best-Effort Application Determination on page 54](#)
- [APPID, AAACL, and L-PDF Processing in Preconvergence Scenarios on page 54](#)

## Features That Support Application-Level Filtering

The application-aware access list (ACL) service uses application names and groups as matching criteria for filtering traffic. The service defines the applications and application groups for which statistics are collected for a specific user or interface.

The local policy decision function (L-PDF) enables you to configure properties for statistics output. L-PDF supports a process that regulates collection of statistics related to applications and application groups and tracking of information about dynamic subscribers and static interfaces.

## Best-Effort Application Determination

Typically, APPID conclusively determines the Layer 7 application associated with a given DPI-serviced flow. In these cases, the application identification is final. Occasionally, APPID is only able to make an initial, inconclusive determination of the Layer 7 application associated with a given flow. This is referred to as a *best-effort* application identification. In such cases, the APPID process continues processing packets on that flow and might subsequently make a conclusive determination of the application associated with that flow. In some cases of best-effort application identification, the flow ends before a final application determination can be made.

## APPID, ACL, and L-PDF Processing in Preconvergence Scenarios

The following sections describe APPID, ACL, and L-PDF processing in various stages of application identification for a DPI-serviced flow of TCP/UDP/ICMP traffic.

- [Prior to a Final or Best-Effort Application Identification on page 54](#)
- [Upon Best-Effort Application Identification on page 55](#)
- [While Application Identification Is on a Best-Effort Basis on page 55](#)
- [If a Flow Ends Before an Application Identification Is Made on page 55](#)
- [If a Flow Ends While Application Identification on a Best-Effort Basis on page 55](#)

### Prior to a Final or Best-Effort Application Identification

During the time that APPID has not yet made either a final or best-effort determination of the application associated with a given flow, the flow does not contribute to any per-subscriber or per-application statistics collection.

The output of the following operational mode commands includes flows for which APPID has not yet made either a final or best-effort determination of the associated application:

- **show services local-policy-decision-function flows** (interface *interface-name* | subscriber *subscriber-name*)
- **show services application-aware-access-list flows** (interface *interface-name* | subscriber *subscriber-name*)

In the command output, the **Action** field displays **accept** and the **Application** or **Application group** field displays **unknown** for a flow for which APPID has not yet made either a final or best-effort determination of the associated application.

### Upon Best-Effort Application Identification

When a best-effort application determination is made, ACL does not apply any ACL term actions configured for that flow. There are a number of reasons for this, one being that the action itself (such as **discard**) can make a final application determination impossible. Instead, ACL or L-PDF tracks the flow and accepts all packets for that flow until a final determination is made, at which time the normal ACL or L-PDF actions are fully applied to the flow.

### While Application Identification Is on a Best-Effort Basis

During the time that APPID identification of the application associated with a given flow is on a best-effort basis, the flow does not contribute to any per-subscriber or per-application statistics collection.

The output of the following operational mode commands includes flows for which APPID has only made a best-effort determination of the associated application:

- **show services local-policy-decision-function flows** (interface *interface-name* | subscriber *subscriber-name*)
- **show services application-aware-access-list flows** (interface *interface-name* | subscriber *subscriber-name*)

In the command output, the **Action** field displays **accept** and the **Application** or **Application group** field displays **unknown** for a flow for which APPID has only made a best-effort determination of the associated application.

### If a Flow Ends Before an Application Identification Is Made

If a flow ends before APPID has made either a final or a best-effort application identification, ACL or L-PDF uses the **unknown** application ID as a final determination and performs any necessary collection, aggregation, and reporting of statistics based on that Layer 7 application. In particular, if the **count** ACL term action is configured for the **application-group-any** application, then the statistics for that flow are collected and aggregated against the count bucket type, and reported as such.

### If a Flow Ends While Application Identification on a Best-Effort Basis

If a flow ends while the application identification is on a best-effort basis, ACL or L-PDF uses that best-effort determination as a final determination. ACL or L-PDF performs any necessary collection, aggregation, and reporting of statistics based on that Layer 7 application. In particular, if the **count** ACL term action is configured for that Layer 7 application, then the statistics for the flow are collected and aggregated against the ACL or L-PDF statistics. However, in the case of nested applications, ACL and L-PDF do not consider the best-effort determination as final and the nested application is reported as an unknown application.

#### Related Documentation

- [Configuring ACL Rules on page 21](#)
- [Configuring Statistics Profiles on page 56](#)
- [acl-fields on page 66](#)

- [aocl-statistics-profile on page 67](#)
- [rule on page 107](#)
- [services on page 116](#)
- [term on page 123](#)
- [then on page 124](#)

## Configuring Statistics Profiles

---

The local policy decision function (L-PDF) enables you to configure properties for statistics output. To do this, you create a statistics profile, which configures the files to which statistics records are exported and the format that is exported. There are two configurations you can use to specify the profile, as described in the following subsections:

- [Configuring an L-PDF Statistics Profile on page 57](#)
- [Configuring an ACL Statistics Profile on page 58](#)



**NOTE:** You must use the same configuration stanza for specifying the profile and the file selection. If configurations are committed in both hierarchies, the one at the `[edit system services local-policy-decision-function]` hierarchy level takes precedence.



**NOTE:**

- When a session closes before APPID has identified nested applications, the session is treated as a best-effort session and L-PDF does not get the nested application information. In such cases, nested applications are reported as unknown applications.
- During the time that the application identification (APPID) feature has not yet made a final determination of the application associated with a given flow, the flow does not contribute to any per-subscriber or per-application statistics collection. For more information, see [“Best-Effort Application Identification of DPI-Serviced Flows” on page 18](#).



**NOTE:** For rms- interfaces, the statistics received from the active Multiservices PICs in the RMS group are combined with the statistics of the reported ended flows kept on the Routing Engine. The aggregated value is written to the statistics file. In the case of AMS interfaces, all the Multiservices PICs consisting of the AMS group reports statistics independently. These statistics are aggregated on the Routing Engine. The Routing Engine runs an independent timer, which on expiry writes the aggregated entry in the statistics file. This method of collection causes the statistics data in the statistics file to be displayed with a small delay.

## Configuring an L-PDF Statistics Profile

You can specify an L-PDF statistics profile by including the following configuration at the **[edit accounting-options]** hierarchy level:

```
[edit accounting-options]
policy-decision-statistics-profile profile-name {
  application-aware-access-list-fields [ field-name ];
  file filename;
  files number;
  size bytes;
}
```



**NOTE:** This configuration method is not the preferred method for configuring Junos Application Aware (previously known as Dynamic Application Awareness) statistics. It is only maintained for backwards compatibility and may be deprecated in a future software release and does not support the use of IPv6 address and prefix length. The new, preferred configuration is found at the **[edit system services local-policy-decision-function]** hierarchy level, as described in “[Configuring an ACL Statistics Profile](#)” on page 58. We encourage you to migrate to the new configuration method.

You specify a profile name to identify the profile and other properties as needed by including the **policy-decision-statistics-profile** statement. The **acl-fields** statement specifies which statistics to collect in an accounting-data log file. This log file is located on the **/var/log** directory on the router. You specify the log file by including the **file filename** statement. The filename is prefixed by the **acl\_statistics\_** prefix; for example, if you specify the filename **lpdfd**, the log file is **/var/log/acl\_statistics\_lpdfd**.

The **application-aware-access-list-fields** statement supports the following options:

- **address**—IP Address
- **application**—Application name
- **application-group**—Application group name
- **input-bytes**—Number of input bytes
- **input-interface**—Input interface name
- **input-packets**—Number of input packets
- **mask**—Netmask
- **output-bytes**—Number of output bytes
- **output-packets**—Number of output packets
- **subscriber-name**—Subscriber name
- **timestamp**—Timestamp
- **vrf-name**—VPN routing and forwarding (VRF) name

For more information on configuring profiles, see the *Network Management and Monitoring Guide*.

## Configuring an ACL Statistics Profile

You can specify an ACL statistics profile by including the following configuration at the **[edit system services]** hierarchy level:

```
local-policy-decision-function {
  statistics {
    file filename {
      archive-sites [ url ];
      files number;
      size bytes;
      transfer-interval minutes;
    }
    aacl-statistics-profile profile-name {
      aacl-fields [ field-name ];
      file filename;
      report-interval minutes;
      record-mode (interim-active-only | interim-full);
    }
    record-type (delta | interim);
  }
}
```

To specify the file properties, include the **file** statement at the **[edit system services local-policy-decision-function statistics]** hierarchy level with a unique filename:

- The **archive-sites** statement specifies one or more URLs for archiving the files. Archiving can be done by using FTP or SCP.
- The **files** statement specifies the maximum number of files that are maintained at one time.
- The **size** statement specifies the maximum size of each file.
- The **transfer-interval** statement specifies the interval between data transfers in minutes.

You specify a profile name to identify the profile and other properties as needed by including the **aacl-statistics-profile** statement. The **aacl-fields** statement specifies which statistics to collect in an accounting-data log file. This log file is located on the **/var/stats/aacl** directory on the router. You specify the log file by including the **file filename** statement.

The **aacl-fields** statement supports the following options:

- **address**—IP Address
- **all-fields**—All available fields
- **application**—Application name
- **application-group**—Application group name
- **input-bytes**—Number of input bytes
- **input-interface**—Input interface name

- **ipv6-address**—IPv6 address
- **ipv6-prefix-length**—Prefix length associated with the displayed IPv6 address
- **input-packets**—Number of input packets
- **mask**—Netmask
- **output-bytes**—Number of output bytes
- **output-packets**—Number of output packets
- **subscriber-name**—Subscriber name
- **timestamp**—Timestamp
- **vrf-name**—VPN routing and forwarding (VRF) name

The **record-type** statement specifies whether a record is **delta** or **interim**; **delta** is the default setting. The **report-interval** statement specifies the reporting interval in minutes; the default setting is 15 minutes and the range is 5 through 1440 minutes. The **record-mode** statement specifies how the statistics are reported for each reporting interval; the default setting is **interim-full** and reports all available statistics. To report only statistics that have changed for the reporting interval, use the **interim-active-only** setting.



**NOTE:** The IPv6 fields (**ipv6-address** and **ipv6-prefix-length**) are not supported for **record-type delta**. The IPv6 fields are supported for **record-type interim** only, meaning that the fields are restricted to the S- (Login) record.

For more information on configuring profiles, see the *Network Management and Monitoring Guide*.

#### Related Documentation

- [L-PDF Overview on page 51](#)
- [Best-Effort Application Identification of DPI-Serviced Flows on page 18](#)
- [Applying L-PDF Profiles to Service Sets on page 59](#)
- [Tracing L-PDF Operations on page 61](#)

## Applying L-PDF Profiles to Service Sets

You can optionally apply policy decision statistics profiles as part of a service-set definition. To do this, you include the **policy-decision-statistics-profile** statement at the **[edit services service-set *service-set-name*]** hierarchy level:

```
policy-decision-statistics-profile profile-name;
```



**NOTE:** To provide high availability for the policy decision statistics, associate the service-set definition with a redundant services PIC (rsp) interface.

You can include only one profile name in the specification for the **application-aware access-list** statement.

The following example shows a sample configuration for attachment of an L-PDF statistics profile:

```
services {
  service-set test_aacl_sset {
    aacl-rules aacl_rule;
    policy-decision-statistics-profile {
      pdf_stats_prof;
    }
    interface-service {
      service-interface ms-0/3/0.0;
    }
  }
}
```



**NOTE:** Only one service set can be applied to a single interface when L-PDF functionality is used.

The following example shows a sample configuration for attachment of a service set to a static interface:

```
interfaces {
  fe-0/0/0 {
    vlan-tagging;
    unit 1 {
      vlan-id 1;
      family inet {
        service {
          input {
            service-set test_aacl_sset;
          }
          output {
            service-set test_aacl_sset;
          }
        }
      }
      address 10.1.1.1/24;
    }
  }
}
```



**NOTE:** The `session-offload` statement at the `[edit chassis fpc slot-number pic number adaptive-services service-package extension-provider]` hierarchy level controls session offload behavior for Multiservices DPCs on MX Series routers. It controls session offload on a per-device basis, where a device is a Multiservices interface (`ms-fpc-pic-port`). Currently, the session offload function is supported for at most one Multiservices interface. When the offload function is enabled, we recommended that you limit Junos Application Aware (previously known as Dynamic Application Awareness) features to that Multiservices interface.

The default is to not offload any sessions. For more information on chassis configuration, see the *Junos OS Administration Library*.

#### Related Documentation

- [L-PDF Overview on page 51](#)
- [Best-Effort Application Identification of DPI-Serviced Flows on page 18](#)
- [Configuring Statistics Profiles on page 56](#)
- [Tracing L-PDF Operations on page 61](#)

## Tracing L-PDF Operations

Tracing operations track L-PDF operations and record them in a log file. The logged error descriptions provide detailed information to help you solve problems faster.

By default, no events are traced. If you include the `traceoptions` statement at the `[edit system services local-policy-decision-function]` hierarchy level, you can customize the trace file settings:

```
traceoptions {
    file filename <files number> <size size>;
    flag flag;
}
```

The flags track the following information:

- **all**—Everything
- **configuration**—Configuration traces
- **database**—Database traces
- **general**—Miscellaneous traces
- **gres**—Graceful Routing Engine switchover (GRES) traces
- **ptsp-statistics**—PTSP statistics traces
- **rtsock**—Routing socket traces

- **statistics**—Statistics traces
- **subscriber**—Subscriber traces

**Related  
Documentation**

- [L-PDF Overview on page 51](#)
- [Best-Effort Application Identification of DPI-Serviced Flows on page 18](#)
- [Configuring Statistics Profiles on page 56](#)
- [Applying L-PDF Profiles to Service Sets on page 59](#)

## CHAPTER 4

# Configuration Statements

- [aacl-fields](#) on page 66
- [aacl-statistics-profile](#) on page 67
- [address](#) on page 68
- [application \(Defining\)](#) on page 69
- [application \(Including in Rule\)](#) on page 70
- [application-aware-access-list-fields](#) on page 71
- [application-group](#) on page 72
- [application-group-any](#) on page 72
- [application-groups \(Services AAACL\)](#) on page 73
- [application-groups \(Services Application Identification\)](#) on page 73
- [application-system-cache-timeout](#) on page 74
- [application-unknown](#) on page 74
- [applications \(Services AAACL\)](#) on page 75
- [applications \(Services Application Identification\)](#) on page 75
- [automatic](#) on page 76
- [bypass-traffic-on-exceeding-flow-limits](#) on page 76
- [chain-order](#) on page 77
- [context](#) on page 77
- [destination \(Services\)](#) on page 78
- [destination-address](#) on page 78
- [destination-address-range](#) on page 79
- [destination-prefix-list \(Services AAACL\)](#) on page 79
- [direction](#) on page 80
- [disable \(APPID Application\)](#) on page 80
- [disable \(APPID Application Group\)](#) on page 81
- [disable \(APPID Port Mapping\)](#) on page 81
- [disable-global-timeout-override](#) on page 82
- [download](#) on page 82

- [enable-asymmetric-traffic-processing](#) on page 83
- [enable-heuristics](#) on page 83
- [file](#) on page 84
- [from](#) on page 85
- [idle-timeout](#) on page 86
- [ignore-errors](#) on page 87
- [index \(Applications\)](#) on page 88
- [index \(Nested Applications\)](#) on page 88
- [inactivity-non-tcp-timeout](#) on page 89
- [inactivity-tcp-timeout](#) on page 89
- [ip](#) on page 90
- [local-policy-decision-function](#) on page 91
- [log \(aACL\)](#) on page 92
- [match-direction](#) on page 93
- [max-checked-bytes](#) on page 93
- [maximum-transactions](#) on page 94
- [member](#) on page 94
- [min-checked-bytes](#) on page 95
- [nested-application](#) on page 96
- [nested-applications](#) on page 97
- [nested-application-settings](#) on page 97
- [nested-application-unknown](#) on page 98
- [no-application-identification](#) on page 98
- [no-application-system-cache](#) on page 99
- [no-clear-application-system-cache](#) on page 99
- [no-nested-application](#) on page 100
- [no-protocol-method](#) on page 100
- [no-signature-based](#) on page 101
- [order \(Services Application Identification\)](#) on page 101
- [pattern](#) on page 102
- [policy-decision-statistics-profile](#) on page 103
- [port-mapping](#) on page 104
- [port-range](#) on page 105
- [profile](#) on page 106
- [protocol](#) on page 106
- [rule \(AACL Rule Set\)](#) on page 107
- [rule \(Application Identification\)](#) on page 108

- [rule \(Including in Rule Set\) on page 109](#)
- [rule-set \(Services ACL\) on page 109](#)
- [rule-set \(Services Application Identification\) on page 110](#)
- [service-set-options on page 111](#)
- [statistics \(System Services\) on page 112](#)
- [support-uni-directional-traffic on page 113](#)
- [service-set \(Services\) on page 114](#)
- [services \(ACL\) on page 116](#)
- [services \(Application Identification\) on page 117](#)
- [session-timeout \(Application Identification\) on page 117](#)
- [session-timeout \(Interfaces\) on page 118](#)
- [signature on page 119](#)
- [signature-method-all-ports on page 120](#)
- [source on page 120](#)
- [source-address \(ACL\) on page 121](#)
- [source-address-range on page 121](#)
- [source-prefix-list \(Services ACL\) on page 122](#)
- [source-prefix-list \(Services IDS\) on page 122](#)
- [term on page 123](#)
- [then on page 124](#)
- [traceoptions \(Application Identification\) on page 126](#)
- [traceoptions \(Services Local Policy Decision Function\) on page 128](#)
- [type on page 129](#)
- [type-of-service on page 130](#)
- [url on page 130](#)

## aac1-fields

---

<b>Syntax</b>	<pre>aac1-fields {     field-name; }</pre>
<b>Hierarchy Level</b>	[edit system services local-policy-decision-function statistics aac1-statistics-profile profile-name]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.0. IPv6 support introduced in Junos OS Release 12.2.
<b>Description</b>	Define the statistics to collect in a data log file.
<b>Options</b>	<p><i>field-name</i>—Name of the field:</p> <ul style="list-style-type: none"><li>• <b>address</b>—IPv4 address</li><li>• <b>all-fields</b>—All available fields</li><li>• <b>application</b>—Application name</li><li>• <b>application-group</b>—Application group name</li><li>• <b>input-bytes</b>—Number of input bytes</li><li>• <b>input-interface</b>—Input interface name</li><li>• <b>input-packets</b>—Number of input packets</li><li>• <b>ipv6-address</b>—IPv6 address</li><li>• <b>ipv6-prefix-length</b>—Prefix length associated with the displayed IPv6 address</li><li>• <b>mask</b>—Netmask</li><li>• <b>output-bytes</b>—Number of output bytes</li><li>• <b>output-packets</b>—Number of output packets</li><li>• <b>subscriber-name</b>—Subscriber name</li><li>• <b>timestamp</b>—Timestamp</li><li>• <b>vrf-name</b>—VPN routing and forwarding (VRF) name</li></ul>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Statistics Profiles on page 56</a></li></ul>

## aac1-statistics-profile

<b>Syntax</b>	<pre> aac1-statistics-profile <i>profile-name</i> {   aac1-fields {     <i>field-name</i>;   }   file <i>filename</i>;   record-mode (interim-active-only   interim-full);   report-interval <i>minutes</i>; } </pre>
<b>Hierarchy Level</b>	<p>[edit services service-set <i>service-set-name</i>],</p> <p>[edit system services local-policy-decision-function statistics]</p>
<b>Release Information</b>	<p>Statement introduced in Junos OS Release 10.0.</p> <p><b>record-mode</b> option introduced in Junos OS Release 10.2.</p>
<b>Description</b>	Create an AAC1 statistics profile, which configures the files to which statistics records are exported and the format that is exported.
<b>Options</b>	<p><b>file <i>filename</i></b>—Name of the file to receive the statistics data output. Enclose the name within quotation marks. All files are placed in the directory <b>/var/stats/aac1</b>.</p> <p><b><i>profile-name</i></b>—Identifier for the profile.</p> <p><b>record-mode</b>—Record mode for the reporting interval; possible values are <b>interim-active-only</b>, which reports only statistics that have changed, or <b>interim-full</b>, which reports all available statistics.</p> <p><b>report-interval <i>minutes</i></b>—Frequency at which statistics are recorded, in minutes.</p> <p><b>Default:</b> 15 minutes</p> <p><b>Range:</b> 5 through 1440 minutes</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>For more information on profiles, see the <i>Network Management and Monitoring Guide</i>.</li> <li><a href="#">Configuring Statistics Profiles on page 56</a></li> </ul>

## address

---

**Syntax**    `address address-name {  
              destination {  
                  ip address </prefix-length>;  
                  port-range {  
                      tcp [ ports-and-port-ranges ];  
                      udp [ ports-and-port-ranges ];  
                  }  
              }  
              source {  
                  ip address </prefix-length>;  
                  port-range {  
                      tcp [ ports-and-port-ranges ];  
                      udp [ ports-and-port-ranges ];  
                  }  
              }  
              order number;  
          }`

**Hierarchy Level**    [edit services application-identification **rule** rule-name]

**Release Information**    Statement introduced in Junos OS Release 9.5.

**Description**    Define address properties for application-identification rule processing. This statement is mandatory; you must specify either the destination or source properties.

**Options**    **address-name**—Identifier for address information.

The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level**    interface—To view this statement in the configuration.  
                                  interface-control—To add this statement to the configuration.

**Related Documentation**    • [Configuring APPID Rules on page 36](#)

## application (Defining)

**Syntax**

```

application application-name {
    disable;
    idle-timeout seconds;
    index number;
    port-mapping {
        disable;
        port-range {
            tcp [ ports-and-port-ranges ];
            udp [ ports-and-port-ranges ];
        }
    }
    session-timeout seconds;
    type type;
    type-of-service service-type;
}

```

**Hierarchy Level** [edit services application-identification]

**Release Information** Statement introduced in Junos OS Release 9.5.

**Description** Define the application and its properties.

The remaining statements are explained separately. See [CLI Explorer](#).

**Options** *application-name*—Identifier for the application. This is a mandatory value and has a maximum length of 32 characters.

**Required Privilege Level**

interface—To view this statement in the configuration.
interface-control—To add this statement to the configuration.

**Related Documentation**

- [Defining an Application Identification on page 34](#)

## application (Including in Rule)

---

<b>Syntax</b>	<code>application <i>application-name</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">rule</a> <i>rule-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Identify the application for inclusion in a rule.
<b>Options</b>	<i>application-name</i> —Identifier for the application.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring APPID Rules on page 36</a></li></ul>

## application-aware-access-list-fields

---

<b>Syntax</b>	<pre>application-aware-access-list-fields {     field-name; }</pre>
<b>Hierarchy Level</b>	[edit accounting-options policy-decision-statistics-profile <i>profile-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define the statistics to collect in a data log file.
<b>Options</b>	<p><i>field-name</i>—Name of the field:</p> <ul style="list-style-type: none"> <li>• <b>address</b>—IP address</li> <li>• <b>application</b>—Application name</li> <li>• <b>application-group</b>—Application group name</li> <li>• <b>input-bytes</b>—Number of input bytes</li> <li>• <b>input-interface</b>—Input interface name</li> <li>• <b>input-packets</b>—Number of input packets</li> <li>• <b>mask</b>—Netmask</li> <li>• <b>output-bytes</b>—Number of output bytes</li> <li>• <b>output-packets</b>—Number of output packets</li> <li>• <b>subscriber-name</b>—Subscriber name</li> <li>• <b>timestamp</b>—Timestamp</li> <li>• <b>vrf-name</b>—VPN routing and forwarding (VRF) name</li> </ul>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Statistics Profiles on page 56</a></li> </ul>

## application-group

---

<b>Syntax</b>	<pre>application-group <i>group-name</i> {     disable;     application-groups {         <i>application-group-name</i>;     }     applications {         <i>application-name</i>;     }     index <i>number</i>; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define the properties and contents of the application group.
<b>Options</b>	<p><i>group-name</i>—Unique identifier for the group.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Application Groups on page 40</a></li></ul>

## application-group-any

---

<b>Syntax</b>	<pre>application-group-any;</pre>
<b>Hierarchy Level</b>	[edit services aacl <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Match any application group defined in the database.
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Match Conditions in ACL Rules on page 22</a></li></ul>

## application-groups (Services AACL)

---

<b>Syntax</b>	<code>application-groups [ <i>application-group-names</i> ];</code>
<b>Hierarchy Level</b>	[edit services aacl <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Identify one or more application groups defined in the application identification configuration for inclusion as a match condition.
<b>Options</b>	<i>application-group-names</i> —Identifiers of the application groups.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in AACL Rules on page 22</a></li> </ul>

## application-groups (Services Application Identification)

---

<b>Syntax</b>	<code>application-groups {     <i>application-group-name</i>; }</code>
<b>Hierarchy Level</b>	[edit services application-identification <b>application-group</b> <i>group-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Identify the list of application groups for inclusion in a larger application group. An <i>application-group-name</i> statement is mandatory.
<b>Options</b>	<i>application-group-name</i> —Identifier for the application group. Maximum length is 32 characters.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Application Groups on page 40</a></li> </ul>

## application-system-cache-timeout

---

<b>Syntax</b>	<code>application-system-cache-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Configure the lifetime for entries in the application system cache.
<b>Options</b>	<i>seconds</i> — Lifetime for system cache entries, in seconds.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Global APPID Properties on page 43</a></li></ul>

## application-unknown

---

<b>Syntax</b>	<code>application-unknown</code>
<b>Hierarchy Level</b>	[edit services aacl <i>rule rule-name term term-name from</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.2.
<b>Description</b>	Enable AACL logging of flows for unknown applications.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• See <a href="#">Configuring Logging of AACL Flows on page 27</a>.</li></ul>

## applications (Services ACL)

---

<b>Syntax</b>	<code>applications [ <i>application-names</i> ];</code>
<b>Hierarchy Level</b>	[edit services aac <b>l</b> <i>rule rule-name</i> <b>t</b> <i>term term-name</i> <b>f</b> rom]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Identify one or more applications defined in the application identification configuration for inclusion as a match condition.
<b>Options</b>	<i>application-names</i> —Identifiers of the applications.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in ACL Rules on page 22</a></li> </ul>

## applications (Services Application Identification)

---

<b>Syntax</b>	<code>applications {     <i>application-name</i>; }</code>
<b>Hierarchy Level</b>	[edit services application-identification <b>a</b> pplication-group <i>group-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Identify the list of applications for inclusion in the application group.
<b>Options</b>	<i>application-name</i> —Identifier for the application. Maximum length is 32 characters.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Application Groups on page 40</a></li> </ul>

## automatic

---

<b>Syntax</b>	<pre>automatic {     interval <i>hour</i>;     start-time <i>time</i>; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">download</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define automatic download properties.
<b>Options</b>	<p><b>interval <i>hour</i></b>—Download interval in hours. The default is <b>24</b> and the range is from 1 through 168.</p> <p><b>start-time <i>time</i></b>—Start-time value. The default is <b>0:00</b> and the range is from 0:00 through 24:00.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Automatic Download of Application Package Updates on page 46</a></li></ul>

## bypass-traffic-on-exceeding-flow-limits

---

<b>Syntax</b>	<pre>bypass-traffic-on-exceeding-flow-limits;</pre>
<b>Hierarchy Level</b>	[edit services service-set <i>service-set-name</i> service-set-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1.
<b>Description</b>	Enable packets to bypass without creating a new session when the flow in the service set exceeds the limit that is set by the <b>max-flows</b> statement at the [edit services service-set <i>service-set-name</i> ] hierarchy level.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Service Sets to be Applied to Services Interfaces</a></li></ul>

## chain-order

---

<b>Syntax</b>	chain-order;
<b>Hierarchy Level</b>	[edit services application-identification <b>nested-application name</b> <b>signature name</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Signatures can contain multiple members. If the chain order feature is on, those members are read in order. By default, chain ordering is turned off. If a signature contains only one member, this option is ignored.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Application Identification for Nested Applications on page 41</a></li> </ul>

## context

---

<b>Syntax</b>	context <i>value</i> ;
<b>Hierarchy Level</b>	[edit services application-identification <b>nested-application name</b> <b>signature name</b> <b>member name</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Define a service-specific context, such as <b>http-url</b> .
<b>Options</b>	<b>value</b> —Use the specified service-specific context: <ul style="list-style-type: none"> <li>• <b>http-header-content-type</b>—Use the service context http-header-content-type.</li> <li>• <b>http-header-host</b>—Use the service context http-header-host.</li> <li>• <b>http-url-parsed</b>—Use the service context http-url-parsed.</li> <li>• <b>http-url-parsed-param-parsed</b>—Use the service context http-url-parsed-param-parsed.</li> </ul>
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Application Identification for Nested Applications on page 41</a></li> </ul>

## destination (Services)

---

<b>Syntax</b>	<pre>destination {     ip address &lt;/prefix-length&gt;;     port-range {         tcp [ ports-and-port-ranges ];         udp [ ports-and-port-ranges ];     } }</pre>
<b>Hierarchy Level</b>	[edit services application-identification <b>rule</b> <i>rule-name</i> <b>address</b> <i>address-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define destination properties for application-identification rule processing.  The remaining statements are explained separately. See <a href="#">CLI Explorer</a> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring APPID Rules on page 36</a></li></ul>

## destination-address

---

<b>Syntax</b>	<pre>destination-address <i>address</i>;</pre>
<b>Hierarchy Level</b>	[edit services aacl <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5. IPv6 support introduced in Junos OS Release 12.2.
<b>Description</b>	Specify the destination address for rule matching.
<b>Options</b>	<b>address</b> —Destination IPv4 or IPv6 address or prefix value.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Match Conditions in ACL Rules on page 22</a></li></ul>

## destination-address-range

<b>Syntax</b>	<code>destination-address-range low <i>minimum-value</i> high <i>maximum-value</i>;</code>
<b>Hierarchy Level</b>	<code>[edit services aacl <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b>]</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5. IPv6 support introduced in Junos OS Release 12.2.
<b>Description</b>	Specify the destination address range for rule matching.
<b>Options</b>	<i>minimum-value</i> —Lower boundary for the IPv4 or IPv6 address range. <i>maximum-value</i> —Upper boundary for the IPv4 or IPv6 address range.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in AACL Rules on page 22</a></li> </ul>

## destination-prefix-list (Services AACL)

<b>Syntax</b>	<code>destination-prefix-list <i>list-name</i>;</code>
<b>Hierarchy Level</b>	<code>[edit services aacl <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b>]</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the destination prefix list for rule matching. You configure the prefix list by including the <b>prefix-list</b> statement at the <b>[edit policy-options]</b> hierarchy level.
<b>Options</b>	<i>list-name</i> —Destination prefix list.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in AACL Rules on page 22</a></li> </ul>

## direction

---

<b>Syntax</b>	direction (any   client-to-server   server-to-client) ;
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application name signature name member name</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Specify the connection direction of the packets to apply pattern matching.
<b>Options</b>	<b>any</b> —Apply pattern matching to the packets from a client to a server and from a server to a client.  <b>client-to-server</b> —Apply pattern matching to the packets from a client to the server.  <b>server-to-client</b> —Apply pattern matching to the packets from a server to a client.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41.</a></li></ul>

## disable (APPID Application)

---

<b>Syntax</b>	disable;
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application application-name</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable this application definition.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Defining an Application Identification on page 34</a></li></ul>

## disable (APPID Application Group)

---

<b>Syntax</b>	disable;
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application-group</a> <i>group-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable application group properties.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Application Groups on page 40</a></li> </ul>

## disable (APPID Port Mapping)

---

<b>Syntax</b>	disable;
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application</a> <i>application-name</i> <a href="#">port-mapping</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable port-mapping properties for application identification.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Defining an Application Identification on page 34</a></li> </ul>

## disable-global-timeout-override

---

<b>Syntax</b>	disable-global-timeout-override;
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> services-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.0.
<b>Description</b>	Disallow overriding a global inactivity or session timeout.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Defining an Application Identification on page 34</a></li></ul>

## download

---

<b>Syntax</b>	<pre>download {   automatic {     interval <i>hour</i>;     start-time <i>time</i>;   }   url <i>url</i>; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define application download properties.  The remaining statements are explained separately. See <a href="#">CLI Explorer</a> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Automatic Download of Application Package Updates on page 46</a></li></ul>

## enable-asymmetric-traffic-processing

---

<b>Syntax</b>	enable-asymmetric-traffic-processing;
<b>Hierarchy Level</b>	[edit services service-set <i>service-set-name</i> service-set-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.2.
<b>Description</b>	Enable APPID to perform application matching on unidirectional traffic.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring APPID Support for Unidirectional Traffic on page 45</a></li> </ul>

## enable-heuristics

---

<b>Syntax</b>	enable-heuristics;
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.2.
<b>Description</b>	Enable APPID to identify encrypted data packets in point-to-point applications by using heuristics methodology.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring APPID Support for Heuristics on page 44</a></li> </ul>

## file

---

<b>Syntax</b>	<pre>file <i>file-name</i> {     archive-sites <i>url</i>;     files <i>file-number</i>;     size <i>bytes</i>;     transfer-interval <i>minutes</i>; }</pre>
<b>Hierarchy Level</b>	[edit system services local-policy-decision-function statistics]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.0.
<b>Description</b>	Specify a file to which statistics records are exported and the format that is exported.
<b>Options</b>	<p><b>archive-sites</b> [<i>url</i>]<b>—</b>Use one or more of the specified destinations for archiving data.</p> <p><b><i>file-name</i></b><b>—</b>Name of the file to receive the statistics data output.</p> <p><b>files</b> <i>file-number</i><b>—</b>(Optional) Use the specified maximum number of accounting files.</p> <p><b>Range:</b> 3 through 1000 files</p> <p><b>Default:</b> 3 files</p> <p>If you specify a maximum number of files, you also must specify a maximum file size with the <b>size</b> option.</p> <p><b>size</b> <i>bytes</i><b>—</b>(Optional) Use the specified maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB).</p> <p><b>Syntax:</b> <i>xk</i> to specify KB, <i>xm</i> to specify MB, or <i>xg</i> to specify GB</p> <p><b>Range:</b> 262144 through 1073741824 or the maximum file size supported on your system</p> <p>If you specify a maximum file size, you also must specify a maximum number of trace files with the <b>files</b> option.</p> <p><b>transfer-interval</b> <i>minutes</i><b>—</b>Use the specified frequency at which to transfer files to archive sites, in minutes.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Statistics Profiles on page 56</a></li></ul>

## from

---

<b>Syntax</b>	<pre> from {   application-group-any;   application-groups [ application-group-names ];   application-unknown;   applications [ application-names ];   destination-address address &lt;any-unicast&gt;;   destination-address-range low minimum-value high maximum-value;   destination-prefix-list list-name;   nested-application-unknown;   source-address address &lt;any-unicast&gt;;   source-address-range low minimum-value high maximum-value;   source-prefix-list list-name; } </pre>
<b>Hierarchy Level</b>	[edit <a href="#">services</a> aacl <a href="#">rule</a> rule-name <a href="#">term</a> term-name]
<b>Release Information</b>	Statement introduced before Junos OS Release 9.5.
<b>Description</b>	Specify match conditions for the AACL term.
<b>Options</b>	<p>For information on match conditions, see the description of firewall filter match conditions in the <i>Routing Policies, Firewall Filters, and Traffic Policers Feature Guide</i>.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><a href="#">Configuring AACL Rules on page 21</a></li> </ul>

## idle-timeout

---

<b>Syntax</b>	<code>idle-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application</a> <i>application-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define idle timeout for an application in seconds. When the timeout period expires, the session ends if no packets have been received.
<b>Options</b>	<b><i>seconds</i></b> —Idle timeout period. <b>Default:</b> 30 <b>Range:</b> 1 through 604,800
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">APPID Overview on page 29</a></li><li>• <a href="#">Defining an Application Identification on page 34</a></li></ul>

## ignore-errors

---

**Syntax** `ignore-errors <alg> <tcp>;`

**Hierarchy Level** [edit interfaces *interface-name* services-options]

**Release Information** Statement introduced in Junos OS Release 10.1.

**Description** Define settings for minimizing TCP packet drops during stateful firewall processing.



**NOTE:** `ignore-errors` option is not supported on adaptive services interfaces (`sp-x/y/z`).

**Options** `alg`—(Optional) Mediate ALG behavior that results in dropping malformed packets or random packets when the software is unable to allocate resources.

`tcp`—(Optional) Prevent software from dropping packets that fail TCP SYN checks.

**Required Privilege** `interface`—To view this statement in the configuration.

**Level** `interface-control`—To add this statement to the configuration.

**Related Documentation**

- [Defining an Application Identification on page 34](#)

## index (Applications)

---

<b>Syntax</b>	<code>index <i>number</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application <i>application-name</i></a> ], [edit services application-identification <a href="#">application-group <i>group-name</i></a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Assign an application or application-group index number. This is a mandatory value.
<b>Options</b>	<b><i>number</i></b> —Index number; must be a unique, unsigned value. <b>Range:</b> 0 through 65,535
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Defining an Application Identification on page 34</a></li><li>• <a href="#">Configuring Application Groups on page 40</a></li></ul>

## index (Nested Applications)

---

<b>Syntax</b>	<code>index <i>number</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application <i>name</i></a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Set a number that is a one-to-one mapping to the application name. The application name is used to ensure that each signature definition is unique.
<b>Options</b>	<b><i>number</i></b> —Numeric value associated with an application name. The index range for predefined applications is from 1 through 32,767. The index range for custom applications and custom nested applications is from 32,768 through 65,534.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41</a>.</li></ul>

## inactivity-non-tcp-timeout

---

<b>Syntax</b>	<code>inactivity-non-tcp-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> services-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.0.
<b>Description</b>	Define the inactivity timeout period for non-TCP established sessions in seconds.
<b>Options</b>	<i>seconds</i> —Timeout period. <b>Range:</b> 4 through 86,400
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Defining an Application Identification on page 34</a></li> </ul>

## inactivity-tcp-timeout

---

<b>Syntax</b>	<code>inactivity-tcp-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> services-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.0.
<b>Description</b>	Define the inactivity timeout period for TCP established sessions in seconds.
<b>Options</b>	<i>seconds</i> —Timeout period. <b>Range:</b> 4 through 86,400
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Defining an Application Identification on page 34</a></li> </ul>

## ip

---

<b>Syntax</b>	<code>ip address&lt;/prefix-length&gt;;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">rule rule-name address destination</a> ], [edit services application-identification <a href="#">rule rule-name address source</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define an IP address and netmask for identifying the traffic destination or source.
<b>Options</b>	<code>address&lt;/prefix-length&gt;</code> —IP address and netmask.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring APPID Rules on page 36</a></li></ul>

## local-policy-decision-function

**Syntax**

```
local-policy-decision-function {
  statistics {
    aacl-statistics-profile profile-name {
      aacl-fields {
        field-name;
      }
      file filename;
      report-interval minutes;
    }
    file file-name {
      archive-sites url;
      files file-number;
      size bytes;
      transfer-interval minutes;
    }
    record-type (delta | interim);
  }
  traceoptions {
    file filename <files number> <size size>;
    flag flag;
    no-remote-trace;
  }
}
```

**Hierarchy Level** [edit system services]

**Release Information** Statement introduced in Junos OS Release 10.0.

**Description** Specify L-PDF properties.

The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Documentation**

- [Configuring Statistics Profiles on page 56](#)

## log (aACL)

---

<b>Syntax</b>	log <i>event-type</i>
<b>Hierarchy Level</b>	[edit services aACL <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>then</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.2.
<b>Description</b>	Enable AACL logging of flows for known or unknown applications.
<b>Options</b>	<i>event-type</i> —Enable logging of the specified <i>event-type</i> : <ul style="list-style-type: none"><li>• session-start</li><li>• session-end</li><li>• session-start-end-no-stats</li><li>• session-start-interim-end</li><li>• session-interim end</li><li>• session-end</li></ul>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• See <a href="#">Configuring Logging of AACL Flows on page 27</a>.</li></ul>

## match-direction

---

<b>Syntax</b>	<code>match-direction (input   output   input-output);</code>
<b>Hierarchy Level</b>	<code>[edit services aacl <a href="#">rule rule-name</a>]</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the direction in which the rule match is applied.
<b>Options</b>	<p><b>input</b>—Apply the rule match on the input side of the interface.</p> <p><b>output</b>—Apply the rule match on the output side of the interface.</p> <p><b>input-output</b>—Apply the rule match bidirectionally.</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Direction for AACL Rules on page 22</a></li> </ul>

## max-checked-bytes

---

<b>Syntax</b>	<code>max-checked-bytes <i>bytes</i>;</code>
<b>Hierarchy Level</b>	<code>[edit services application-identification]</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the maximum number of bytes to be inspected.
<b>Options</b>	<p><b>bytes</b>—Maximum number of bytes.</p> <p><b>Range:</b> 0 through 100,000</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Global APPID Properties on page 43</a></li> </ul>

## maximum-transactions

---

<b>Syntax</b>	<code>maximum-transactions <i>number</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application name</a> <a href="#">signature name</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Set the maximum number of transactions required before a match is made.
<b>Options</b>	<i>number</i> —Maximum number of transactions.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41</a></li></ul>

## member

---

<b>Syntax</b>	<code>member <i>name</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application name</a> <a href="#">signature name</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Define a member name for a custom nested application signature definition. Custom definitions can contain multiple members that define attributes for an application.
<b>Options</b>	<i>name</i> —Name of member for a custom nested application signature definition.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41</a></li></ul>

## min-checked-bytes

---

<b>Syntax</b>	min-checked-bytes <i>bytes</i> ;
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the minimum number of bytes to be inspected.
<b>Options</b>	<i>bytes</i> —Minimum number of bytes. <b>Range:</b> 0 through 2000
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Global APPID Properties on page 43</a></li></ul>

## nested-application

---

**Syntax**    `nested-application name {  
                  index number;  
                  protocol protocol ;  
                  signature name {  
                    chain-order ;  
                    maximum-transactions number;  
                    member name {  
                      context (http-header-content-type | http-header-host | http-url-parsed |  
                        http-url-parsed-param-parsed);  
                      direction (any | client-to-server | server-to-client);  
                      pattern dfa-pattern;  
                    }  
                    order number;  
                  }  
                  type type;  
                }`

**Hierarchy Level**    [edit services application-identification]

**Release Information**    Statement introduced in Junos OS Release 10.2.

**Description**    Configure a custom nested application definition, which is used by the system to identify the nested application as it passes through the device. Custom nested application definitions can be used for nested applications that are not part of the Juniper Networks predefined nested application database.

**Options**    *name*—Name of nested application.

The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level**    system—To view this statement in the configuration.  
                                  system control—To add this statement to the configuration.

**Related Documentation**    • [Application Identification for Nested Applications on page 41](#)

## nested-applications

---

<b>Syntax</b>	<code>nested-applications [ <i>nested-application-names</i> ];</code>
<b>Hierarchy Level</b>	[edit services aacl <a href="#">rule rule-name</a> <a href="#">term term-name</a> <a href="#">from</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.1.
<b>Description</b>	Identify one or more nested applications defined in the application identification configuration for inclusion as a match condition.
<b>Options</b>	<i>nested-application-names</i> —Identifiers of the nested applications.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in ACL Rules on page 22</a></li> </ul>

## nested-application-settings

---

<b>Syntax</b>	<pre>nested-application-settings {   <a href="#">no-application-system-cache</a>;   <a href="#">no-nested-application</a>; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	<p>Configure nested application options for application identification services.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Application Identification for Nested Applications on page 41</a>.</li> </ul>

## nested-application-unknown

---

<b>Syntax</b>	nested-application-unknown
<b>Hierarchy Level</b>	[edit services aacl <a href="#">rule rule-name term term-name from</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.4.
<b>Description</b>	Enable AACL logging of flows for unknown nested applications.
<b>Required Privilege Level</b>	<b>interface</b> —To view this statement in the configuration. <b>interface-control</b> —To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Logging of AACL Flows on page 27.</a></li></ul>

## no-application-identification

---

<b>Syntax</b>	no-application-identification;
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable all application identification methods.
<b>Required Privilege Level</b>	<b>interface</b> —To view this statement in the configuration. <b>interface-control</b> —To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Global APPID Properties on page 43</a></li></ul>

## no-application-system-cache

---

<b>Syntax</b>	no-application-system-cache;
<b>Hierarchy Level</b>	[edit services application-identification], [edit services application-identification <a href="#">nested-application-settings</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable storing application identification results in the application system cache. Nested application identification information is saved in the application system cache to improve performance. This cache is updated when a different application is identified. This caching is turned on by default. Use the no-application-system-cache statement to turn it off.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Global APPID Properties on page 43</a></li> <li>• <a href="#">Application Identification for Nested Applications on page 41.</a></li> </ul>

## no-clear-application-system-cache

---

<b>Syntax</b>	no-clear-application-system-cache;
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable clearing the application system cache.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Global APPID Properties on page 43</a></li> </ul>

## no-nested-application

---

<b>Syntax</b>	no-nested-application;
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application-settings</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Sometimes there is a need to identify multiple different applications running on the same Layer 7 protocols. For example, both Facebook and Yahoo Messenger can run over HTTP, but there is a need to identify them as two different applications. To do this, the application layer is split into two layers: Layer 7 applications and Layer 7 protocols. This function is turned on by default. Use the <b>no-nested-application</b> statement to turn it off.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41</a></li></ul>

## no-protocol-method

---

<b>Syntax</b>	no-protocol-method;
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.1.
<b>Description</b>	Disable the protocol-based application identification method.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Global APPID Properties on page 43</a></li></ul>

## no-signature-based

---

<b>Syntax</b>	no-signature-based;
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Disable the signature-based application identification method.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Global APPID Properties on page 43</a></li> </ul>

## order (Services Application Identification)

---

<b>Syntax</b>	order <i>number</i> ;
<b>Hierarchy Level</b>	[edit services application-identification <i>nested-application name signature name member name</i> ], [edit services application-identification <i>rule rule-name address</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define application matching priority. For address configurations, the order number resolves the conflict when multiple address entries are matched for a specific session. The lower number has higher priority.
<b>Options</b>	<i>number</i> —Order number. This value is mandatory and must be unique.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring APPID Rules on page 36</a></li> <li>• <a href="#">Application Identification for Nested Applications on page 41</a></li> </ul>

## pattern

---

<b>Syntax</b>	<code>pattern <i>dfa-pattern</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application name</a> <a href="#">signature name</a> <a href="#">member name</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Define an attack pattern to be detected.
<b>Options</b>	<b><i>dfa-pattern</i></b> —Pattern of attack to match. Deterministic Finite Automata (DFA) is a powerful pattern matching engine.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41</a></li></ul>

## policy-decision-statistics-profile

<b>Syntax</b>	<pre> policy-decision-statistics-profile <i>profile-name</i> {     aacl-fields {         <i>field-name</i>;     }     file <i>filename</i>;     files <i>file-number</i>;     size <i>bytes</i>; } </pre>
<b>Hierarchy Level</b>	[edit accounting-options], [edit services service-set <i>service-set-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Create a policy decision statistics profile, which configures the files to which statistics records are exported and the format that is exported.
<b>Options</b>	<p><b>file <i>filename</i></b>—Use the specified file to receive the accounting-data output. Enclose the name within quotation marks. All files are placed in the directory <b>/var/log</b>.</p> <p><b>files <i>number</i></b>—(Optional) Use the specified maximum number of accounting files.  <b>Range:</b> 2 through 1000 files  <b>Default:</b> 2 files</p> <p>If you specify a maximum number of files, you also must specify a maximum file size with the <b>size</b> option.</p> <p><b><i>profile-name</i></b>—Name of the policy decision statistics profile.</p> <p><b>size <i>size</i></b>—(Optional) Use the specified maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB).  <b>Syntax:</b> <i>xk</i> to specify KB, <i>xm</i> to specify MB, or <i>xg</i> to specify GB  <b>Range:</b> 10,240 through 1,073,741,824 or the maximum file size supported on your system</p> <p>If you specify a maximum file size, you also must specify a maximum number of trace files with the <b>files</b> option.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>For more information on profiles, see the <i>Network Management and Monitoring Guide</i>.</li> <li><a href="#">Configuring Statistics Profiles on page 56</a></li> </ul>

## port-mapping

---

**Syntax**    port-mapping {  
              disable;  
              port-range {  
                  tcp [ *ports-and-port-ranges* ];  
                  udp [ *ports-and-port-ranges* ];  
              }  
          }

**Hierarchy Level**    [edit services application-identification [application](#) *application-name*]

**Release Information**    Statement introduced in Junos OS Release 9.5.

**Description**    Define port-mapping properties for application identification.  
  
                  The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level**    interface—To view this statement in the configuration.  
                                  interface-control—To add this statement to the configuration.

**Related Documentation**    • [Defining an Application Identification on page 34](#)

## port-range

---

<b>Syntax</b>	<pre>port-range {     tcp [ <i>ports-and-port-ranges</i> ];     udp [ <i>ports-and-port-ranges</i> ]; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application</a> <i>application-name</i> <a href="#">port-mapping</a> ], [edit services application-identification <a href="#">rule</a> <i>rule-name</i> <a href="#">address destination</a> ], [edit services application-identification <a href="#">rule</a> <i>rule-name</i> <a href="#">address source</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define TCP and UDP port numbers or numeric ranges. For port-mapping configurations, this entry is required if the parent node exists.
<b>Options</b>	<b><i>ports-and-port-ranges</i></b> —Individual port numbers, numeric port ranges, or both. Separate the values with spaces. The format for numeric port ranges is <b><i>minimum-value–maximum-value</i></b> .
<b>Required Privilege</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Defining an Application Identification on page 34</a></li> <li>• <a href="#">Configuring APPID Rules on page 36</a></li> </ul>

## profile

---

<b>Syntax</b>	<code>profile <i>profile-name</i> {     <i>rule-set</i> <i>rule-set-name</i>; }</code>
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define members of application profile, which consists of one or more rule sets.
<b>Options</b>	<i>profile-name</i> —Identifier for application profile.  The remaining statement is explained separately. See <a href="#">CLI Explorer</a> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Application Profiles on page 39</a></li></ul>

## protocol

---

<b>Syntax</b>	<code>protocol <i>protocol</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <i>nested-application name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Identify the protocol that is monitored to identify nested applications. HTTP is supported.
<b>Options</b>	<i>protocol</i> —An agreed-upon or standardized method for transmitting data and establishing communications between different devices. The value <b>http</b> is supported.
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Application Identification for Nested Applications on page 41</a></li></ul>

## rule (AACL Rule Set)

<b>Syntax</b>	<pre> rule <i>rule-name</i> {   match-direction (input   output   input-output);   term <i>term-name</i> {     from {       application-group-any;       application-groups [ <i>application-group-names</i> ];       application-unknown;       applications [ <i>application-names</i> ];       destination-address <i>address</i> &lt;any-unicast&gt;;       destination-address-range low <i>minimum-value</i> high <i>maximum-value</i>;       destination-prefix-list <i>list-name</i>;       nested-application-unknown;       source-address <i>address</i> &lt;any-unicast&gt;;       source-address-range low <i>minimum-value</i> high <i>maximum-value</i>;       source-prefix-list <i>list-name</i>;     }     then {       (accept   discard);       count (application   application-group   application-group-any   nested-application           none);       forwarding-class <i>class-name</i>;       policer <i>policer-name</i>;     }   } } </pre>
<b>Hierarchy Level</b>	<pre> [edit services aacl], [edit services aacl <b>rule-set</b> <i>rule-set-name</i>] </pre>
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the rule the router uses when applying this service.
<b>Options</b>	<p><b>rule-name</b>—Identifier for the collection of terms that constitute this rule.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><a href="#">Configuring AACL Rules on page 21</a></li> </ul>

## rule (Application Identification)

---

**Syntax**

```
rule rule-name {  
  address {  
    destination {  
      ip address </prefix-length>;  
      port-range {  
        tcp [ ports-and-port-ranges ];  
        udp [ ports-and-port-ranges ];  
      }  
    }  
    source {  
      ip address </prefix-length>;  
      port-range {  
        tcp [ ports-and-port-ranges ];  
        udp [ ports-and-port-ranges ];  
      }  
    }  
    order number;  
  }  
  application application-name;  
}
```

**Hierarchy Level** [edit services application-identification]

**Release Information** Statement introduced in Junos OS Release 9.5.

**Description** Define properties for application-identification rule processing.

**Options** *rule-name*—Unique identifier for the rule.

The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Documentation**

- [Configuring APPID Rules on page 36](#)

## rule (Including in Rule Set)

---

<b>Syntax</b>	<code>rule <i>rule-name</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">rule-set</a> <i>rule-set-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Identify rules for inclusion in application rule set.
<b>Options</b>	<i>rule-name</i> —Unique identifier for the rule.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring APPID Rules on page 36</a></li> </ul>

## rule-set (Services ACL)

---

<b>Syntax</b>	<code>rule-set <i>rule-set-name</i> {     [<a href="#">rule</a> <i>rule-names</i>]; }</code>
<b>Hierarchy Level</b>	[edit services aacl]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the rule set the router uses when applying this service.
<b>Options</b>	<i>rule-set-name</i> —Identifier for the collection of rules that constitute this rule set.  The remaining statements are explained separately. See <a href="#">CLI Explorer</a> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring ACL Rule Sets on page 26</a></li> </ul>

## rule-set (Services Application Identification)

---

<b>Syntax</b>	<pre>rule-set <i>rule-set-name</i> {     <b>rule</b> <i>application-rule-name</i>; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification], [edit services application-identification <b>profile</b> <i>profile-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define members of rule set.
<b>Options</b>	<p><b><i>rule-set-name</i></b>—Unique identifier for the rule set.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring APPID Rules on page 36</a></li></ul>

## service-set-options

<b>Syntax</b>	<pre> service-set-options {   bypass-traffic-on-exceeding-flow-limits;   bypass-traffic-on-pic-failure;   enable-asymmetric-traffic-processing;   header-integrity-check;   routing-engine-services;   support-uni-directional-traffic;   tcp-fast-open {     disabled;     drop;   }   tcp-non-syn {     drop-flow;     drop-flow-send-rst;   } } </pre>
<b>Hierarchy Level</b>	[edit services service-set <i>service-set-name</i> ]
<b>Release Information</b>	<p>Statement introduced in Junos OS Release 10.1.</p> <p><b>enable-asymmetric-traffic-processing</b> and <b>support-uni-directional-traffic</b> options added in Junos OS Release 11.2.</p> <p><b>routing-engine-services</b> option added in Junos OS Release 15.1.</p> <p><b>enable-change-on-ams-redistribution</b> option added in Junos OS Release 15.1.</p> <p><b>tcp-fast-open</b> option added in Junos OS Release 17.2.</p>
<b>Description</b>	<p>Specify the service set options to apply to a service set.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <i>Configuring Service Sets to be Applied to Services Interfaces</i></li> <li>• <a href="#">Configuring APPID Support for Unidirectional Traffic on page 45</a></li> </ul>

## statistics (System Services)

---

**Syntax**

```
statistics {
  aacl-statistics-profile profile-name {
    aacl-fields {
      field-name;
    }
    file filename;
    report-interval minutes;
  }
  file file-name {
    archive-sites [ url ];
    files file-number;
    size bytes;
    transfer-interval minutes;
  }
  record-type (delta | interim);
}
```

**Hierarchy Level** [edit system services local-policy-decision-function]

**Release Information** Statement introduced in Junos OS Release 10.0.

**Description** Configure file and data specifications for recording ACL statistics.

**Options** **record-type**—Use the specified record type; possible values are **delta** or **interim**.  
The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Documentation**

- [Configuring Statistics Profiles on page 56](#)

## support-uni-directional-traffic

---

<b>Syntax</b>	support-uni-directional-traffic;
<b>Hierarchy Level</b>	[edit services service-set <i>service-set-name</i> service-set-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.2.
<b>Description</b>	Enable APPID to perform application matching on unidirectional traffic.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring APPID Support for Unidirectional Traffic on page 45</a></li></ul>

## service-set (Services)

```

Syntax  service-set service-set-name {
        allow-multicast;
        captive-portal-content-delivery-profile;
        cos-options {
            match-rules-on-reverse-flow;
        }
        cos-rules [cos-rule-name];
        extension-service service-name {
            provider-specific-rules-configuration;
        }
        (ids-rules rule-name | ids-rule-sets rule-set-name);
        interface-service {
            load-balancing-options {
                hash-keys {
                    egress-key (destination-ip | source-ip);
                    ingress-key (destination-ip | source-ip);
                }
            }
            service-interface interface-name;
        }
        ipsec-vpn-options {
            anti-replay-window-size bits;
            clear-dont-fragment-bit;
            ike-access-profile profile-name;
            local-gateway address;
            no-anti-replay;
            no-certificate-chain-in-ike;
            passive-mode-tunneling;
            trusted-ca [ ca-profile-names ];
            tunnel-mtu bytes;
            udp-encapsulation {
                <udp-dest-port destination-port>;
            }
        }
        ip-reassembly-rules rule-name;
        (ipsec-vpn-rules rule-name | ipsec-vpn-rule-sets rule-set-name);
        max-flows number;
        max-drop-flows {
            ingress ingress-flows;
            egress egress-flows;
        }
        max-session-creation-rate max-setup-rate;
        nat-options {
            land-attack-check (ip-only | ip-port);
            max-sessions-per-subscriber session-number;
            stateful-nat64 {
                clear-dont-fragment-bit;
            }
        }
        (nat-rules rule-name | nat-rule-sets rule-set-name);
        next-hop-service {
            inside-service-interface interface-name.unit-number;

```

```

    outside-service-interface interface-name.unit-number;
    outside-service-interface-type local;
    service-interface-pool name;
}
pcp-rules rule-name;
(pgcp-rules rule-name | pgcp-rule-sets rule-set-name);
(ptsr-rules rule-name | ptsr-rule-sets rule-set-name);
service-set-options {
    bypass-traffic-on-exceeding-flow-limits;
    bypass-traffic-on-pic-failure;
    enable-asymmetric-traffic-processing;
    header-integrity-check
    routing-engine-services;
    support-uni-directional-traffic;
}
snmp-trap-thresholds{
    flows high high-threshold | low low-threshold;
    nat-address-port high-threshold | low low-threshold;
}
}
software-options {
    dslite-ipv6-prefix-length dslite-ipv6-prefix-length;
}
}
(stateful-firewall-rules rule-name | stateful-firewall-rule-sets rule-set-name);
syslog {
    host hostname {
        class {
            alg-logs;
            deterministic-nat-configuration-log;
            ids-logs;
            nat-logs;
            packet-logs;
            pcp-logs;
            session-logs <open | close>;
            stateful-firewall-logs ;
        }
        services severity-level;
        facility-override facility-name;
        interface-service prefix-value;
        port port-number;
        services severity-level;
    }
}
}
url-filter-profile profile-name;
}

```

Hierarchy Level [edit services]

<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. <b>pcp-rules</b> option added in Junos OS Release 13.2R1. <b>pgcp-rules</b> and <b>pgcp-rule-sets</b> options added in Junos OS Release 8.4. <b>server-set-options</b> option added in Junos OS Release 10.1. <b>ptsp-rules</b> and <b>ptsp-rule-sets</b> options added in Junos OS Release 10.2. <b>software-rules</b> and <b>clear-rule-sets</b> options added in Junos OS Release 10.4. <b>software-options</b> option added in Junos OS Release 14.1. <b>url-filter-profile</b> option added in Junos OS Release 17.2R1. <b>match-rules-on-reverse-flow</b> option added in Junos OS Release 16.1R5 and 17.4R1
<b>Description</b>	Define the service set.
<b>Options</b>	<b>service-set-name</b> —Name of the service set. You can include special characters, such as a forward slash (/), colon (:), or a period (.). <b>Range:</b> Up to 64 alphanumeric characters.  The remaining statements are explained separately. See <a href="#">CLI Explorer</a> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Understanding Service Sets</i></li></ul>

---

## services (AACL)

---

<b>Syntax</b>	services aacl { ... }
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	<b>aacl</b> statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define the services to be applied to traffic.
<b>Options</b>	<b>aacl</b> —Use the values configured for application-aware-access-list matching rules.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Application Aware Services Interfaces Feature Guide for Routing Devices</i></li></ul>

## services (Application Identification)

---

<b>Syntax</b>	<code>services application-identification { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	<code>services</code> statement introduced before Junos OS Release 7.4. <code>application-identification</code> statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define the services to be applied to traffic.
<b>Options</b>	<code>application-identification</code> —Use the values configured for application-identification properties.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">APPID Overview on page 29</a></li> </ul>

## session-timeout (Application Identification)

---

<b>Syntax</b>	<code>session-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application</a> <i>application-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define session lifetime for the specified application in seconds.
<b>Options</b>	<p><code>seconds</code>—Duration of session.</p> <p><b>Default:</b> 3600</p> <p><b>Range:</b> 1 through 604,800</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Defining an Application Identification on page 34</a></li> </ul>

## session-timeout (Interfaces)

---

<b>Syntax</b>	<code>session-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> services-options]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.0.
<b>Description</b>	Define session lifetime globally for the Multiservices interface in seconds.
<b>Options</b>	<b><i>seconds</i></b> —Duration of session. <b>Range:</b> 4 through 86,400
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Defining an Application Identification on page 34</a></li></ul>

## signature

---

<b>Syntax</b>	<pre>signature <i>name</i> {   chain-order;   maximum-transactions <i>number</i>;   member <i>name</i> {     context <i>value</i>;     direction (any   client-to-server   server-to-client);     pattern <i>dfa-pattern</i>;   }   order <i>number</i>; }</pre>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">nested-application name</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2.
<b>Description</b>	Identify the name of the custom nested application signature definition. The name must be unique with a maximum length of 32 characters.
<b>Options</b>	<p><b><i>name</i></b>—Name of the signature definition.</p> <p>The remaining statements are described separately.</p>
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Application Identification for Nested Applications on page 41</a></li> </ul>

## signature-method-all-ports

---

<b>Syntax</b>	signature-method-all-ports
<b>Hierarchy Level</b>	[edit services application-identification]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.2.
<b>Description</b>	<p>Run signature matching on all traffic in application-identification. This is called the signature-match mode.</p> <p>In the default mode, or fast-port-match mode, all traffic destined to well-known ports (up to 1024) immediately returns the final port match. However, the device runs signature matching for all traffic destined for port 80,</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Global APPID Properties on page 43</a></li></ul>

## source

---

<b>Syntax</b>	<pre>source {   ip address&lt;/prefix-length&gt;;   port-range {     tcp [ ports-and-port-ranges ];     udp [ ports-and-port-ranges ];   } }</pre>
<b>Hierarchy Level</b>	[edit services application-identification <b>rule</b> <i>rule-name</i> <b>address</b> <i>address-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	<p>Define source properties for application-identification rule processing.</p> <p>The remaining statements are explained separately. See <a href="#">CLI Explorer</a>.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring APPID Rules on page 36</a></li></ul>

## source-address (AACL)

---

<b>Syntax</b>	<code>source-address <i>address</i>;</code>
<b>Hierarchy Level</b>	[edit services aacl <a href="#">rule rule-name</a> <a href="#">term term-name</a> <a href="#">from</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5. IPv6 support introduced in Junos OS Release 12.2.
<b>Description</b>	Specify the source address for rule matching.
<b>Options</b>	<b><i>address</i></b> —Source IPv4 or IPv6 address or prefix value.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in AACL Rules on page 22</a></li> </ul>

## source-address-range

---

<b>Syntax</b>	<code>source-address-range low <i>minimum-value</i> high <i>maximum-value</i>;</code>
<b>Hierarchy Level</b>	[edit services aacl <a href="#">rule rule-name</a> <a href="#">term term-name</a> <a href="#">from</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5. IPv6 support introduced in Junos OS Release 12.2.
<b>Description</b>	Specify the source address range for rule matching.
<b>Options</b>	<b><i>minimum-value</i></b> —Lower boundary for the IPv4 or IPv6 address range.  <b><i>maximum-value</i></b> —Upper boundary for the IPv4 or IPv6 address range.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Match Conditions in AACL Rules on page 22</a></li> </ul>

## source-prefix-list (Services AACL)

---

<b>Syntax</b>	<code>source-prefix-list <i>list-name</i>;</code>
<b>Hierarchy Level</b>	<code>[edit services aacl <b>rule</b> <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b>]</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Specify the source prefix list for rule matching. You configure the prefix list by including the <b>prefix-list</b> statement at the <b>[edit policy-options]</b> hierarchy level.
<b>Options</b>	<i>list-name</i> —Source prefix list.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Match Conditions in AACL Rules on page 22</a></li></ul>

## source-prefix-list (Services IDS)

---

<b>Syntax</b>	<code>source-prefix-list <i>list-name</i> &lt;except&gt;;</code>
<b>Hierarchy Level</b>	<code>[edit services ids rule <i>rule-name</i> <b>term</b> <i>term-name</i> <b>from</b>]</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 8.2.
<b>Description</b>	Specify the source prefix list for rule matching. You configure the prefix list by including the <b>prefix-list</b> statement at the <b>[edit policy-options]</b> hierarchy level.
<b>Options</b>	<i>list-name</i> —Destination prefix list.  <b>except</b> —(Optional) Exclude the specified prefix list from rule matching.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Match Conditions in IDS Rules</a></li><li>• <a href="#">Routing Policies, Firewall Filters, and Traffic Policers Feature Guide</a></li></ul>

## term

**Syntax**    `term term-name {`  
                   `from {`  
                     `application-group-any;`  
                     `application-groups [ application-group-names ];`  
                     `application-unknown;`  
                     `applications [ application-names ];`  
                     `destination-address address <any-unicast>;`  
                     `destination-address-range low minimum-value high maximum-value;`  
                     `destination-prefix-list list-name;`  
                     `nested-application-unknown;`  
                     `source-address address <any-unicast>;`  
                     `source-address-range low minimum-value high maximum-value;`  
                     `source-prefix-list list-name;`  
                   `}`  
                   `then {`  
                     `(accept | discard);`  
                     `count (application | application-group | application-group-any | nested-application |`  
                       `none);`  
                     `forwarding-class class-name;`  
                     `policer policer-name;`  
                   `}`  
                   `}`

**Hierarchy Level**    `[edit services aacl rule rule-name]`

**Release Information**    Statement introduced in Junos OS Release 9.5.

**Description**    Define the ACL term properties.

**Options**    *term-name*—Identifier for the term.

The remaining statements are explained separately. See [CLI Explorer](#).

**Required Privilege Level**    interface—To view this statement in the configuration.  
                                   interface-control—To add this statement to the configuration.

**Related Documentation**    • [Configuring ACL Rules on page 21](#)

## then

---

**Syntax**    then {  
              (accept | discard);  
              count (application | application-group | application-group-any | nested-application | none);  
              forwarding-class *class-name*;  
              log *event-type*;  
              policer *policer-name*;  
              }

**Hierarchy Level**    [edit services aacl **rule** *rule-name* **term** *term-name*]

**Release Information**    Statement introduced in Junos OS Release 9.5.  
                              **policer** statement added in Junos OS Release 9.6.  
                              **nested-application** option for the **count** statement added in Junos OS Release 11.1.

**Description**    Define the AACL term actions. You can configure the router to accept or discard the targeted traffic. The action modifiers (count and forwarding-class) are optional.

**Options**    You can configure one of the following actions:

- **accept**—Accept the packets and all subsequent packets in flows that match the rules.
- **discard**—Discard the packet and all subsequent packets in flows that match the rules.

When you select **accept** as the action, you can optionally configure one or both of the following action modifiers. No action modifiers are allowed with the **discard** action.

- **count (application | application-group | application-group-any | nested-application | none)**—For all accepted packets that match the rules, record a packet count using AACL statistics practices. You can specify one of the following options; there is no default setting:
  - **application**—Count the application that matched in the **from** clause.
  - **application-group**—Count the application group that matched in the **from** clause.
  - **application-group-any**—Count all application groups that match **from application-group-any** under the **any** group name.
  - **nested-application**—Count all nested applications that matched in the **from** clause.
  - **none**—Same as not specifying **count** as an action.
- **forwarding-class class-name**—Specify the packets' forwarding-class name.

**policer policer-name**—Apply rate-limiting properties to the traffic as configured at the [edit firewall policer *policer-name*] hierarchy level. This configuration allows bit-rate and burst-size attributes to be applied to the traffic that are not supported by AACL rules. When you include a policer, the only allowed action is **discard**. For more information on policers, see the *Routing Policies, Firewall Filters, and Traffic Policers Feature Guide*.

The remaining statements are explained separately. See [CLI Explorer](#).

<b>Required Privilege</b>	interface—To view this statement in the configuration.
<b>Level</b>	interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring AACL Rules on page 21</a></li><li>• <i>Routing Policies, Firewall Filters, and Traffic Policers Feature Guide</i></li></ul>

## tracoptions (Application Identification)

---

Syntax	<pre>tracoptions {     file <i>filename</i> &lt;files <i>number</i>&gt; &lt;match <i>regex</i>&gt; &lt;size <i>size</i>&gt; &lt;world-readable           no-world-readable&gt;;     flag <i>flag</i>;     no-remote-trace; }</pre>
Hierarchy Level	[edit services application-identification]
Release Information	Statement introduced in Junos OS Release 9.5.
Description	<p>Configure application identification tracing options.</p> <p>To specify more than one tracing operation, include multiple <b>flag</b> statements.</p>
Options	<p><b>file <i>filename</i></b>—Use the specified file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory <b>/var/log</b>.</p> <p><b>files <i>number</i></b>—(Optional) Use the specified maximum number of trace files. When a trace file named <b><i>trace-file</i></b> reaches its maximum size, it is renamed <b><i>trace-file.0</i></b>, then <b><i>trace-file.1</i></b>, and so on, until the maximum number of trace files is reached. Then the oldest trace file is overwritten.</p> <p><b>Range:</b> 2 through 1000 files</p> <p><b>Default:</b> 2 files</p> <p>If you specify a maximum number of files, you also must specify a maximum file size with the <b>size</b> option.</p> <p><b><i>flag</i></b>—Tracing operation to perform. <b>all</b> is the only valid completion.</p> <ul style="list-style-type: none"><li>• <b>all</b>—Trace all events.</li></ul> <p><b>match <i>regex</i></b>—(Optional) Use the specified regular expression for lines to be logged.</p> <p><b>no-world-readable</b>—(Optional) Disallow any user to read the log file.</p> <p><b>size <i>size</i></b>—(Optional) Use the specified maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named <b><i>trace-file</i></b> reaches this size, it is renamed <b><i>trace-file.0</i></b>. When the <b><i>trace-file</i></b> again reaches its maximum size, <b><i>trace-file.0</i></b> is renamed <b><i>trace-file.1</i></b> and <b><i>trace-file</i></b> is renamed <b><i>trace-file.0</i></b>. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.</p> <p><b>Syntax:</b> <b>xk</b> to specify KB, <b>xm</b> to specify MB, or <b>xg</b> to specify GB</p> <p><b>Range:</b> 10,240 through 1,073,741,824 or the maximum file size supported on your system</p> <p>If you specify a maximum file size, you also must specify a maximum number of trace files with the <b>files</b> option.</p>

**world-readable**—(Optional) Allow any user to read the log file.

**Required Privilege** interface—To view this statement in the configuration.  
**Level** interface-control—To add this statement to the configuration.

**Related Documentation** • [Tracing APPID Operations on page 46](#)

## traceoptions (Services Local Policy Decision Function)

---

Syntax	<pre>traceoptions {     file <i>filename</i> &lt;files <i>number</i>&gt; &lt;size <i>size</i>&gt;;     flag <i>flag</i>;     no-remote-trace; }</pre>
Hierarchy Level	[edit services local-policy-decision-function], [edit system services local-policy-decision-function]
Release Information	Statement introduced in Junos OS Release 9.5.
Description	Configure local policy decision function (L-PDF) tracing options.
Options	<p><b>file <i>filename</i></b>—Use the specified file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory <b>/var/log</b>.</p> <p><b>files <i>number</i></b>—(Optional) Use the specified maximum number of trace files. When a trace file named <b><i>trace-file</i></b> reaches its maximum size, it is renamed <b><i>trace-file.0</i></b>, then <b><i>trace-file.1</i></b>, and so on, until the maximum number of trace files is reached. Then the oldest trace file is overwritten.</p> <p><b>Range:</b> 2 through 1000 files <b>Default:</b> 2 files</p> <p>If you specify a maximum number of files, you also must specify a maximum file size with the <b>size</b> option.</p> <p><b><i>flag</i></b>—Tracing operation to perform. To specify more than one flag, include multiple <b>flag</b> statements.</p> <ul style="list-style-type: none"><li>• <b>all</b>—Everything</li><li>• <b>configuration</b>—Configuration traces</li><li>• <b>database</b>—Database traces</li><li>• <b>general</b>—Miscellaneous traces</li><li>• <b>gres</b>—Graceful Routing Engine switchover (GRES) traces</li><li>• <b>ptsp-statistics</b>—PTSP statistics traces</li><li>• <b>rtsock</b>—Routing socket traces</li><li>• <b>statistics</b>—Statistics traces</li><li>• <b>subscriber</b>—Subscriber traces</li></ul> <p><b>no-remote-trace</b>—Disable remote tracing.</p> <p><b>size <i>size</i></b>—(Optional) Use the specified maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named <b><i>trace-file</i></b> reaches</p>

this size, it is renamed **trace-file.0**. When the **trace-file** again reaches its maximum size, **trace-file.0** is renamed **trace-file.1** and **trace-file** is renamed **trace-file.0**. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

**Syntax:** **xk** to specify KB, **xm** to specify MB, or **xg** to specify GB

**Range:** 10,240 through 1,073,741,824 or the maximum file size supported on your system

If you specify a maximum file size, you also must specify a maximum number of trace files with the **files** option.

<b>Required Privilege Level</b>	routing and trace—To view this statement in the configuration. routing-control and trace-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Tracing L-PDF Operations on page 61</a></li> </ul>

## type

<b>Syntax</b>	type type;
<b>Hierarchy Level</b>	[edit services application-identification <b>application</b> application-name], [edit services application-identification <b>nested-application</b> name]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define type of application, such as HTTP or FTP.
<b>Options</b>	<b>type</b> —Application type. This is a mandatory value and has a maximum length of 32 characters.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Defining an Application Identification on page 34</a></li> <li>• <a href="#">Application Identification for Nested Applications on page 41</a></li> </ul>

## type-of-service

---

<b>Syntax</b>	<code>type-of-service <i>service-type</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">application</a> <i>application-name</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define the type of service by service objective. There is no default value.
<b>Options</b>	<p>The following <b><i>service-type</i></b> options are available:</p> <ul style="list-style-type: none"><li>• <b>maximize-reliability</b>—Service designed for maximum reliability in packet transmission.</li><li>• <b>maximize-throughput</b>—Service designed for maximum throughput.</li><li>• <b>minimize-delay</b>—Service designed for minimum delay in packet transmission.</li><li>• <b>minimize-monetary-cost</b>—Service designed for minimum monetary cost.</li></ul>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Defining an Application Identification on page 34</a></li></ul>

## url

---

<b>Syntax</b>	<code>url <i>url</i>;</code>
<b>Hierarchy Level</b>	[edit services application-identification <a href="#">download</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.5.
<b>Description</b>	Define the URL for application package downloads.
<b>Options</b>	<b><i>url</i></b> —Download URL.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Automatic Download of Application Package Updates on page 46</a></li></ul>

## CHAPTER 5

# Operational Commands

- clear services application-aware-access-list statistics
- clear services application-identification application-system-cache
- clear services application-identification counter
- clear services flows
- clear services local-policy-decision-function statistics
- request services application-identification application
- request services application-identification download
- request services application-identification download status
- request services application-identification group
- request services application-identification install
- request services application-identification install status
- show services application-aware-access-list flows
- show services application-identification application-system-cache
- show services application-identification counter
- show services application-identification group
- show services application-aware-access-list statistics
- show services application-identification application
- show services application-identification version
- show services flows
- show services local-policy-decision-function flows
- show services local-policy-decision-function statistics
- show services sessions

## **clear services application-aware-access-list statistics**

---

<b>Syntax</b>	clear services application-aware-access-list statistics
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Clear application-aware access list (ACL) statistics.
<b>Options</b>	This command has no options.
<b>Required Privilege Level</b>	clear
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">show services application-aware-access-list statistics on page 156</a></li></ul>

## **clear services application-identification application-system-cache**

---

<b>Syntax</b>	clear services application-identification application-system-cache
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Clear entries from application system cache.
<b>Options</b>	This command has no options.
<b>Required Privilege Level</b>	clear
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">show services application-identification application-system-cache on page 149</a></li></ul>

## clear services application-identification counter

---

<b>Syntax</b>	clear services application-identification counter
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Clear application identification counters.
<b>Options</b>	This command has no options.
<b>Required Privilege Level</b>	clear
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">show services application-identification counter on page 151</a></li></ul>

## clear services flows

<b>Syntax</b>	<pre>clear services flows &lt;application-protocol <i>protocol</i>&gt; &lt;destination-port <i>destination-port</i>&gt; &lt;destination-prefix <i>destination-prefix</i>&gt; &lt;interface <i>interface-name</i>&gt; &lt;protocol <i>protocol</i>&gt; &lt;service-set <i>service-set</i>&gt; &lt;source-port <i>source-port</i>&gt; &lt;source-prefix <i>source-prefix</i>&gt;</pre>
<b>Release Information</b>	<p>Command introduced in Junos OS Release 9.5.</p> <p><b>application-protocol</b> option introduced in Junos OS Release 11.1.</p>
<b>Description</b>	Clear flow session table entries.
<b>Options</b>	<p><b>none</b>—Clear all flows.</p> <p><b>application-protocol <i>protocol</i></b>—(Optional) Clear flows for one of the following application protocols:</p> <ul style="list-style-type: none"> <li>• <b>bootp</b>—Bootstrap protocol</li> <li>• <b>dce-rpc</b>—Distributed Computing Environment-Remote Procedure Call protocols</li> <li>• <b>dce-rpc-portmap</b>—Distributed Computing Environment-Remote Procedure Call protocols portmap service</li> <li>• <b>dns</b>—Domain Name System protocol</li> <li>• <b>exec</b>—Exec</li> <li>• <b>ftp</b>—File Transfer Protocol</li> <li>• <b>h323</b>—H.323 standards</li> <li>• <b>icmp</b>—Internet Control Message Protocol</li> <li>• <b>iiop</b>—Internet Inter-ORB Protocol</li> <li>• <b>login</b>—Login</li> <li>• <b>netbios</b>—NetBIOS</li> <li>• <b>netshow</b>—NetShow</li> <li>• <b>pptp</b>—Point-to-Point Tunneling Protocol</li> <li>• <b>realaudio</b>—RealAudio</li> <li>• <b>rpc</b>—Remote Procedure Call protocol</li> <li>• <b>rpc-portmap</b>—Remote Procedure Call protocol portmap service</li> <li>• <b>rtsp</b>—Real-Time Streaming Protocol</li> </ul>

- **shell**—Shell
- **sip**—Session Initiation Protocol
- **snmp**—Simple Network Management Protocol
- **sqlnet**—SQLNet
- **talk**—Talk Program
- **tftp**—Trivial File Transfer Protocol
- **traceroute**—Traceroute
- **winframe**—WinFrame

**destination-port** *destination-port*—(Optional) Clear flows for the specified destination port. The range of values is from 0 to 65535.

**destination-prefix** *destination-prefix*—(Optional) Clear flows for the specified destination prefix.

**interface** *interface-name*—(Optional) Clear flows for the specified interface. On M Series and T Series routers, the *interface-name* can be *ms-fpc/pic/port* or *rspnumber*. On J Series routers, the *interface-name* is *ms-pim/O/port*.

**protocol** *protocol*—(Optional) Clear flows for one of the following IP types:

- **number**—Numeric protocol value from 0 to 255
- **ah**—IPsec Authentication Header protocol
- **egp**—An exterior gateway protocol
- **esp**—IPsec Encapsulating Security Payload protocol
- **gre**—A generic routing encapsulation protocol
- **icmp**—Internet Control Message Protocol
- **icmp6**—Internet Control Message Protocol version 6
- **igmp**—Internet Group Management Protocol
- **ipip**—IP-over-IP Encapsulation Protocol
- **ospf**—Open Shortest Path First protocol
- **pim**—Protocol Independent Multicast protocol
- **rsvp**—Resource Reservation Protocol
- **sctp**—Stream Control Transmission Protocol
- **tcp**—Transmission Control Protocol
- **udp**—User Datagram Protocol

**service-set** *service-set*—(Optional) Clear flows for the specified service set.

**source-port *source-port***—(Optional) Clear flows for the specified source port. The range of values is from 0 through 65535.

**source-prefix *source-prefix***—(Optional) Clear flows for the specified source prefix.

**Required Privilege Level**

clear

**Related Documentation**

- [show services flows on page 165](#)

**List of Sample Output**

[clear services flows on page 137](#)  
[clear services flows ip-action on page 137](#)

**Output Fields**

[Table 3 on page 137](#) lists the output fields for the **clear services flows** command. Output fields are listed in the approximate order in which they appear.

*Table 3: clear services flows Output Fields*

Field Name	Field Description
Interface	Name of an interface.
Service set	Name of the service set from which flows are being cleared.
Flows removed	Number of flows removed.

## Sample Output

### clear services flows

```
user@host> clear services flows
Interface  Service set      Flows removed
ms-2/0/0   IDP               1
```

### clear services flows ip-action

```
user@host> clear services flows ip-action
Interface  Service set      Flows removed
ms-4/0/0   idp-service      1
```

## [clear services local-policy-decision-function statistics](#)

---

<b>Syntax</b>	clear services local-policy-decision-function statistics
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Clear local policy decision function (L-PDF) statistics.
<b>Options</b>	This command has no options.
<b>Required Privilege Level</b>	view
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">show services local-policy-decision-function statistics on page 174</a></li></ul>

## request services application-identification application

<b>Syntax</b>	<code>request services application-identification application [disable   enable] predefined-application-name</code>
<b>Release Information</b>	Command introduced in Junos OS Release 11.4.
<b>Description</b>	Disable, or enable a predefined application signature.
<b>Options</b>	<p><b>disable</b>—(Optional) Disable a predefined application signature, initiate signature recompilation, and commit all pending uncompiled signatures to the configuration.</p> <p>The following conditions apply:</p> <ul style="list-style-type: none"> <li>You cannot disable a predefined application signature that is referenced by an active security policy or custom application signature. First modify or deactivate the policy or custom application signature.</li> <li>If you disable an application signature, for example, <code>junos:HTTP</code>, that has nested applications, the nested applications are not recognized.</li> </ul> <p><b>enable</b>—(Optional) Enable a predefined application signature, initiate signature recompilation, and commit all pending uncompiled signatures to the configuration.</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><a href="#">show services application-identification application on page 158</a></li> </ul>
<b>Output Fields</b>	When you enter this command, the system provides feedback on the status of your request.

## Sample Output

### request services application-identification application disable

```

user@host> request services application-identification application disable junos:163
Please wait while we are updating signatures ...
Please wait while we are updating signatures ...
Please wait while we are updating signatures ...
Please wait while we are updating signatures ...
Please wait while we are updating signatures ...
Please wait while we are updating signatures ...
Disable application junos:163 succeed.

```

## request services application-identification download

---

<b>Syntax</b>	<code>request services application-identification download &lt;version&gt;;</code>
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2. Statement modified in Junos OS Release 11.4.
<b>Description</b>	Manually download the application package for Junos OS application identification. The application package is extracted from the IDP signature database and contains signature definitions for known applications, such as: DNS, Facebook, FTP, Skype, and SNMP.
<b>Options</b>	<b>version</b> —(Optional) Download a specific version of the application package from the Juniper Networks security website. If you do not enter a version, the most recent version is downloaded.
<b>Required Privilege Level</b>	maintenance
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">request services application-identification download status on page 141</a></li><li>• <a href="#">request services application-identification install on page 144</a></li></ul>
<b>List of Sample Output</b>	<a href="#">request services application-identification download on page 140</a>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.

## Sample Output

### request services application-identification download

```
user@host> request services application-identifications download
Please use command "request services application-identification download status"
to check status
```

---

## request services application-identification download status

---

<b>Syntax</b>	request services application-identification download status
<b>Release Information</b>	Statement introduced in Junos OS Release 10.2. Statement modified in Junos OS Release 11.4.
<b>Description</b>	Check the download status of the application signature package. The downloaded application package is saved under <code>/var/db/appid/sec-download/</code> .
<b>Required Privilege Level</b>	maintenance
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">request services application-identification download on page 140</a></li></ul>
<b>List of Sample Output</b>	<a href="#">request services application-identification download status on page 141</a>
<b>Output Fields</b>	When you enter this command, the system provides feedback on the status of your request.

### Sample Output

#### request services application-identification download status

```
user@host> request services application-identifications download status
Application package 1608 is downloaded successfully.
```

## request services application-identification group

<b>Syntax</b>	<code>request services application-identification group [copy   disable   enable] predefined-application-group-name</code>
<b>Release Information</b>	Command introduced in Junos OS Release 11.4.
<b>Description</b>	Copy, disable, or enable a predefined application signature group.
<b>Options</b>	<p><b>copy</b>—(Optional) Copy a predefined application signature group from the database to the configuration and change the name (for example, my:FTP). The ID and order are generated automatically. Do not name your custom application signature group with the <b>junos</b> prefix; this prefix is reserved for predefined application signature groups. You can copy the same predefined application signature group only once; duplicate custom signature groups are not allowed.</p> <p><b>disable</b>—(Optional) Disable a predefined application signature group.</p> <p><b>enable</b>—(Optional) Enable a predefined application signature group.</p> <p><b>predefined-application-group-name</b>—Name of the predefined application signature group.</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><a href="#">show services application-identification group on page 154</a></li> </ul>
<b>Output Fields</b>	When you enter this command, the system provides feedback on the status of your request.



**NOTE:** In configuration mode, if an uncommitted action is pending, the **request services application-identification group copy** command fails.



**NOTE:** You cannot disable a predefined application signature group that is referenced by an active security policy or custom application signature group. First modify or deactivate the policy or custom application signature group.

## Sample Output

### request services application-identification group

```
user@host> request services application-identification group disable
junos:infrastructure:networking
Disable application group junos:infrastructure:networking succeed.
```

### request services application-identification group

```
user@host> request services application-identification group enable
junos:infrastructure:networking
Enable application group junos:infrastructure:networking succeed.
```

### request services application-identification group

```
user@host> request services application-identification group copy junos:infrastructure:networking
Please wait while we are copying group ...
Copy application group junos:infrastructure:networking succeed.
```

## request services application-identification install

---

<b>Syntax</b>	request services application-identification install
<b>Release Information</b>	Statement introduced in Junos OS Release 11.4.
<b>Description</b>	Install the downloaded predefined application signature package.
<b>Required Privilege Level</b>	maintenance
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">request services application-identification install status on page 145</a></li><li>• <a href="#">request services application-identification download on page 140</a></li></ul>
<b>Output Fields</b>	When you enter this command, the system provides feedback on the status of your request.

### Sample Output

```
user@host> request services application-identification install
Please use command "request services application-identification install status"
to check status and use command "request services application-identification
proto-bundle-status" to check protocol bundle status
```

## request services application-identification install status

---

<b>Syntax</b>	request services application-identification install status
<b>Release Information</b>	Statement introduced in Junos OS Release 11.4.
<b>Description</b>	Display the status of the install operation.
<b>Required Privilege Level</b>	maintenance
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">request services application-identification install on page 144</a></li></ul>
<b>Output Fields</b>	When you enter this command, the system provides feedback on the status of your request.

### Sample Output

```
user@host> request services application-identification install status
Install application package version (1776) succeed.
```

## show services application-aware-access-list flows

<b>Syntax</b>	<b>show services application-aware-access-list flows</b> <b>&lt;interface <i>interface-name</i>&gt;</b> <b>&lt;subscriber <i>subscriber-name</i>&gt;</b>
<b>Release Information</b>	Command introduced in Junos OS Release 10.1. Offload status for flows using Juniper Forwarding Mechanism (JFM) added in Junos OS Release 12.1.
<b>Description</b>	Display application-aware-access-list (AACL) flows. Offloading using JFM is supported only on MX Series routers with Modular Port Concentrators (MPCs).
<b>Options</b>	<b>interface <i>interface-name</i></b> —Displays AACL flows for the specified interfaces only. The keyword, <b>interface</b> , must be appended to the command.  <b>subscriber <i>subscriber-name</i></b> —Displays AACL flows for the specified subscribers only. The keyword, <b>subscriber</b> , must be appended to the command.
<b>Required Privilege Level</b>	view
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><i>Application Aware Services Interfaces Feature Guide for Routing Devices</i></li> </ul>
<b>List of Sample Output</b>	<a href="#">show services application-aware-access-list flows interface on page 147</a> <a href="#">show services application-aware-access-list flows subscriber on page 148</a> <a href="#">show services application-aware-access-list flows subscriber (Offloading Using JFM) on page 148</a>
<b>Output Fields</b>	<a href="#">Table 4 on page 146</a> lists the output fields for the <b>show services application-aware-access-list flows</b> command. Output fields are listed in the approximate order in which they appear.

*Table 4: show services application-aware-access-list flows Output Fields*

Field Name	Field Description	Level of Output
<b>5-tuple</b>	This field comprises five components of the given flow. The components are: <ul style="list-style-type: none"> <li>• Src IP</li> <li>• Dest IP</li> <li>• Src Port</li> <li>• Dest Port</li> <li>• Protocol</li> </ul>	All levels
<b>Application-ID</b>	The identification number associated with the application.	All levels

Table 4: show services application-aware-access-list flows Output Fields (continued)

Field Name	Field Description	Level of Output
<b>Dir</b>	The direction in terms of input or output.  <ul style="list-style-type: none"> <li>• Input (I)</li> <li>• Output (O)</li> </ul>	All levels
<b>Off</b>	The status of offload to Packet Forwarding Engine. The various options are:  <ul style="list-style-type: none"> <li>• Not Offloaded (-)</li> <li>• Policer Offloaded, Flow Not Offloaded (P)</li> <li>• Policer Not Offloaded, Flow Offloaded (F)</li> <li>• Policer and Offloaded (P+F)</li> </ul>	All levels
<b>Off</b>	The status of offload to Packet Forwarding Engine using JFM. The various options are:  <ul style="list-style-type: none"> <li>• Not Offloaded (-)</li> <li>• Offload requested but not completed (R)</li> <li>• Offload requested and completed (O)</li> </ul>	All levels
<b>Actions</b>	The types of actions displayed are:  <ul style="list-style-type: none"> <li>• discard: (D)</li> <li>• accept : A</li> <li>• accept, count [T]: C-A or C-G or C-T</li> <li>• accept, fwd-class [C]: FC</li> <li>• accept, policer [P]: P</li> <li>• accept, count [T], fwd-class [C]: C-T+FC</li> <li>• accept, count [T], policer [P]: C-T+P</li> <li>• accept, fwd-class [C], policer [P]: FC+P</li> <li>• accept, count[T],fwd-class[C],policer[P]: C-T+FC+P</li> </ul>	All levels

## Sample Output

### show services application-aware-access-list flows interface

```

user@host>show services application-aware-access-list flows interface ge-1/0/5.0
Interface: ge-1/0/5.0
service-set: aacl-countApps
service-set interface: ms-0/0/0
Currently active flows: 2
High watermark flows: 2

5-tuple                                     Application-ID
Dir Off Action
-----
198.51.100.2:47072-> 10.10.254.116:80 ,6   junos:http [64]
I  -   C-T
10.10.254.116:80  ->  198.51.100.2:47072,6   junos:http [64]
O  -   C-T

```

**show services application-aware-access-list flows subscriber**

```
user@host>show services application-aware-access-list flows subscriber user@example.com
Subscriber: user@example.com
```

```
Service-set: ss1
Service-set interface: ms-2/0/0
Currently active flows: 4
High watermark flows: 40
```

5-tuple	Application-ID	Dir	Off	Action
192.0.2.100:20109->160.200.200.200:80,17	junos:http [64]	I	-	C-T+FC+P
203.0.113.200:80->192.0.2.100:20109,17	junos:http [64]	O	-	C-T+FC+P
192.0.2.100:20108->203.0.113.100:80,17	junos:http [64]	I	P+F	C-T+FC+P
203.0.113.100:80->192.0.2.100:20108,17	junos:http [64]	O	P+F	C-T+FC+P

**show services application-aware-access-list flows subscriber (Offloading Using JFM)**

```
user@host>show services application-aware-access-list flows subscriber user@example.com
Subscriber: user@example.com
```

```
Service-set: ss1
Service-set interface: ms-2/0/0
Currently active flows: 4
High watermark flows: 40
```

5-tuple	Application-ID	Dir	Off	Action
192.0.2.100:20109->160.200.200.200:80,17	junos:http [64]	I	-	C-T+FC+P
203.0.113.200:80 ->192.0.2.100:20109,17	junos:http [64]	O	-	C-T+FC+P
192.0.2.100:20108->203.0.113.100:80,17	junos:http [64]	I	R	C-T+FC+P
203.0.113.100:80 ->192.0.2.100:20108,17	junos:http [64]	O	O	C-T+FC+P

## show services application-identification application-system-cache

**Syntax** `show application-identification application-system-cache`  
`<interface interface-name>`

**Release Information** Command introduced in Junos OS Release 9.5.  
**interface** option added in Junos OS Release 10.1.

**Description** Display the database of cached values stored by the application identification (APPID) system.



**NOTE:** The `show services application-identification application-system-cache` command gives the information only when the application identifier (AI) is matched with the signature.

**Options** `interface interface-name`—Display the specified services interfaces to query.

**Required Privilege Level** view

**List of Sample Output** [show application-identification application-system-cache on page 150](#)

**Output Fields** [Table 5 on page 149](#) lists the output fields for the `show services application-identification application-system-cache` command. Output fields are listed in the approximate order in which they appear.

*Table 5: show application-identification application-system-cache Output Fields*

Field Name	Field Description	Level of Output
IP address	IP address.	All levels
Port	Port number.	All levels
Protocol	Protocol name.	All levels
Application	Application number.	All levels
CPU	CPU number	All levels

## Sample Output

### show application-identification application-system-cache

```
user@host> show application-identification application-system-cache interface ms-1/0/0  
pic: 2/0
```

IP address	Port	Protocol	Application	CPU
10.1.1.2	81	TCP	63	18

## show services application-identification counter

<b>Syntax</b>	<b>show services application-identification counter</b> <b>&lt;interface <i>interface-name</i>&gt;</b>
<b>Release Information</b>	Command introduced in Junos OS Release 9.5. <b>interface</b> option added in Junos OS Release 10.1.
<b>Description</b>	Display application identification (APPID) counter statistics.
<b>Options</b>	<b>interface <i>interface-name</i></b> —Display the specified services interfaces to query.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	<a href="#">show services application-identification counter on page 152</a> <a href="#">show services application-identification counter on page 152</a>
<b>Output Fields</b>	<a href="#">Table 6 on page 151</a> lists the output fields for the <b>show services application-identification counter</b> command. Output fields are listed in the approximate order in which they appear.

*Table 6: show services application-identification counter Output Fields*

Field Name	Field Description
pic	PIC number.
Total sessions	Total number of sessions.
Total identified sessions	Total number of identified sessions.
Total unidentified sessions	Total number of unidentified sessions.
Total identified-by-address sessions	Number of sessions identified by address.
Total unidentified-by-address sessions	Number of sessions not identified by address.
Total identified-by-port sessions	Number of sessions identified by port.
Total unidentified-by-port sessions	Number of sessions not identified by port.
Total identified-by-icmp sessions	Number of sessions identified by ICMP.
Total unidentified-by-icmp sessions	Number of sessions not identified by ICMP.
Total identified-by-ip-protocol sessions	Number of sessions identified by IP protocol.
Total unidentified-by-ip-protocol sessions	Number of sessions not identified by IP protocol.

Table 6: show services application-identification counter Output Fields (continued)

Field Name	Field Description
Total identified-by-signature sessions	Number of sessions identified by signature.
Total unidentified-by-signature sessions	Number of sessions not identified by signature.
Total unspecified encrypted sessions	Number of encrypted sessions not specified by normal processes.
Total encrypted P2P sessions	Number of encrypted point-to-point sessions.
Total application system cache hits	Number of sessions found in the application system cache.
Total application system cache misses	Number of sessions not found in the application system cache.
Total identified-by-protocol sessions	Number of sessions identified by protocol.
Total unidentified-by-protocol sessions	Number of sessions not identified by protocol.

## Sample Output

### show services application-identification counter

```

user@host> show services application-identification counter interface ms-1/0/0
Counter Statistics:
  pic: 1/1
  Total sessions: 11
  Total identified sessions: 11
  Total un-identified sessions: 0
Address Method
  Total identified-by-address sessions: 0
  Total unidentified-by-address sessions: 11
Port Method
  Total identified-by-port sessions: 1
  Total unidentified-by-port sessions: 0
  Total identified-by-icmp sessions: 0
  Total unidentified-by-icmp sessions: 0
  Total identified-by-ip-protocol sessions: 0
  Total unidentified-by-ip-protocol sessions: 0
Signature Method
  Total identified-by-signature sessions: 11
  Total unidentified-by-signature sessions: 0
  Total unspecified encrypted sessions: 2
  Total encrypted P2P sessions: 2
  Total application system cache hits: 10
  Total application system cache misses: 1
Protocol Method
  Total identified-by-protocol sessions: 0
  Total unidentified-by-protocol sessions: 0

```

### show services application-identification counter

```

user@host> show services application-identification counter interface ams0
Counter Statistics:
  pic: ams0

```

```
Total sessions: 20
Total identified sessions: 20
Total un-identified sessions: 0
Protocol Method
  Total identified-by-protocol sessions: 0
  Total un-identified-by-protocol sessions: 0
Address Method
  Total identified-by-address sessions: 0
  Total un-identified-by-address sessions: 0
Port Method
  Total identified-by-port sessions: 0
  Total un-identified-by-port sessions: 0
  Total identified-by-icmp sessions: 0
  Total un-identified-by-icmp sessions: 0
  Total identified-by-ip-protocol sessions: 0
  Total un-identified-by-ip-protocol sessions: 0
Signature Method
  Total identified-by-signature sessions: 20
  Total identified-by-signature uni-directional sessions: 0
  Total un-identified-by-signature sessions: 0
  Total application system cache hits: 0
  Total application system cache misses: 0
```

## show services application-identification group

<b>Syntax</b>	<code>show services application-identification group [detail <i>application-group name</i>   summary]</code>
<b>Release Information</b>	Command introduced in Junos OS Release 11.4.
<b>Description</b>	Display detailed or summary information about a specified application signature group or all application signature groups. Both custom and predefined application signature groups can be displayed.
<b>Options</b>	<p><b>detail <i>application-group name</i></b>—(Optional) Display detailed information for the specified application signature group.</p> <p><b>summary</b>—(Optional) Display summary information for all application signature groups.</p>
<b>Required Privilege Level</b>	view
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">request services application-identification group on page 142</a></li> </ul>
<b>List of Sample Output</b>	<p><a href="#">show services application-identification group summary on page 155</a></p> <p><a href="#">show services application-identification group detail on page 155</a></p>
<b>Output Fields</b>	<a href="#">Table 7 on page 154</a> lists the output fields for the <b>show services application-identification group</b> command. Output fields are listed in the approximate order in which they appear.

Table 7: show services application-identification group Output Fields

Field Name	Field Description
Description	Description of the specified application in the detailed display.
Group ID or ID	The unique ID number of an application signature or application signature group. ID numbers 1 through 32,767 are automatically generated for predefined application signatures and application signature groups; these IDs do not change. ID numbers for custom application signatures and application signature groups use ID numbers 32,768 to 65,534.
Disabled	The status of the application signature group and whether the signature method is currently used to identify this application. The default is No.
Application Group(s)	The application signature groups present.
Applications	The application signatures associated with this application signature group.

## Sample Output

### show services application-identification group summary

```
user@host> show services application-identification group summary
Application Group(s): 24
Application Groups                                Disabled  ID
my:enterprise                                     No        32770
junos:enterprise:voip                             No         25
junos:peer-to-peer:voip                           No         24
junos:peer-to-peer:chat                           No         23
junos:peer-to-peer:file-sharing                   No         22
...
```

### show services application-identification group detail

```
user@host> show services application-identification group detail junos:social-networking
Group Name: junos:social-networking
Group ID: 36
Description: N/A
Disabled: No
Number of Applications: 0
Number of Sub-Groups: 2
Number of Parent-Groups: 1
Sub Groups:
  junos:social-networking:applications
  junos:social-networking:business
```

## show services application-aware-access-list statistics

<b>Syntax</b>	<b>show services application-aware-access-list statistics</b> <b>&lt;interface <i>interface-name</i>&gt;</b> <b>&lt;subscriber <i>subscriber-name</i>&gt;</b>
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Display application-aware access list (AACL) statistics.
<b>Options</b>	<b>interface <i>interface-name</i></b> —(Optional) Display AACL statistics for the specified interface only.  <b>subscriber <i>subscriber-name</i></b> —(Optional) Display AACL statistics for the specified subscriber only.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	<a href="#">show services application-aware-access-list statistics interface on page 157</a> <a href="#">show services application-aware-access-list statistics subscriber on page 157</a>
<b>Output Fields</b>	<a href="#">Table 8 on page 156</a> lists the output fields for the <b>show services application-aware-access-list statistics</b> command. Output fields are listed in the approximate order in which they appear.

*Table 8: show services application-aware-access-list statistics Output Fields*

Field Name	Field Description	Level of Output
<b>Interface</b>	Interface name.	Subscriber option
<b>Subscriber</b>	Subscriber identifier.	Interface option
<b>Service-set-interface</b>	Service set interface name.	All levels
<b>Service set</b>	Service set name.	All levels
<b>Application group</b>	Application group identifier.	All levels
<b>Packets in</b>	Number of ingress packets.	All levels
<b>Bytes in</b>	Number of ingress bytes.	All levels
<b>Packets out</b>	Number of egress packets.	All levels
<b>Bytes out</b>	Number of egress bytes.	All levels

## Sample Output

### show services application-aware-access-list statistics interface

```
user@host> show services application-aware-access-list statistics interface ge-0/0/0.100
Subscriber: user@example.com
```

```
service-set: IDP
service-set interface: ms-2/0/0
```

Application group	Application	Packets in	Bytes in
Packets out	Bytes out		
6	junos:ftp [63] 346	5	334

### show services application-aware-access-list statistics subscriber

```
user@host> show services application-aware-access-list statistics subscriber user@example.com
Interface: ge-1/1/0.0
```

```
Service-set-interface: ms-1/3/0
Service set: aacl-svc-set
```

#### Application-aware-access-list statistics

Application group	Packets in	Bytes in	Packets out	Bytes
out				
P2P	16284	400	32025	200
FTP	8700	20000	5231000	100

## show services application-identification application

<b>Syntax</b>	show services application-identification application (detail   summary)
<b>Release Information</b>	Command introduced in Junos OS Release 11.4. Starting in Junos OS Release 15.1X49-D100, the options <b>Cacheable</b> , <b>Activation Date</b> , and <b>Last modified</b> are introduced for <b>show services application-identification application detail</b> command. The <b>Underlying consolidated Protocols/ports application is dependent on</b> and <b>Layer-7 Immediate Protocol(s)</b> options are introduced in Junos OS Release 18.2R1.
<b>Description</b>	Display detailed information about a specified application signature, detailed information about all application signatures, or a summary of the existing application signatures.
<b>Options</b>	<b>detail</b> —Display detailed information for all application signatures. <b>summary</b> —Display summary information for all application signatures.
<b>Required Privilege Level</b>	view
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><a href="#">request services application-identification application on page 139</a></li> </ul>
<b>List of Sample Output</b>	<a href="#">show services application-identification application summary on page 160</a> <a href="#">show services application-identification application detail on page 161</a> <a href="#">show services application-identification application detail (Custom Applications) on page 161</a> <a href="#">show services application-identification application detail (Unified Policies) on page 162</a>
<b>Output Fields</b>	<a href="#">Table 9 on page 158</a> lists shows the output details for the <b>show services application-identification application detail</b> command.

*Table 9: show services application-identification application summary Output Fields*

Field Name	Field Description
Application(s)	The number of applications present.
Application	Name of the custom application.
Disabled	The status of the application and whether the mapping method is currently used to identify this application.
ID	The unique ID number of an application. ID numbers 1 through 32,767 are automatically generated for applications; these IDs do not change. ID numbers for custom applications use 16,777,216 to 33,554,431.
Order	Number used to specify priority when multiple applications match the traffic. The lowest order number takes the highest priority.

Table 10 on page 159 lists the output fields for the **show services application-identification application** command. Output fields are listed in the approximate order in which they appear.

*Table 10: show services application-identification application Output Fields*

Field Name	Field Description
Application Name	Name of the application.
Application Type	The basic application type, such as HTTP.
Description	A description of the application.
Application ID	The unique ID number of an application signature. ID numbers 1 through 32,767 are automatically generated for application; these IDs do not change.  ID numbers for custom applications use 16,777,216 to 33,554,431.
Priority	Priority over other signature applications.
Disabled	The status of the application and whether the mapping method is currently used to identify this application.
Cacheable	The status whether the application identification results caching is enabled or not for the application.  When this option is enabled, you can cache the application detection result in an ASC table.
Activation Date	Date when the application was activated for the first time.
Last Modified	Date when the application was last updated.
Number of Parent Group(s)	Total number of parent groups in this application signature group or cluster.
Application Group	Name of the application signature group associated with this application signature. Must be a unique name with a maximum length of 32 characters.
Application Tags	General information about this application type, for example, associated risk factors, technology, type of traffic, and so on.  Support of application signature tags is dependent on the version of the loaded signature database ( <a href="#">Juniper Networks security website</a> ).
Underlying consolidated Protocols/ports application is dependent on	List of default protocols and ports for dependent applications of the specified application.
Layer-7 Immediate Protocol(s)	List of applications over which that dynamic application can be identified.
Application Specific Ports:	The default port for this application type.

Table 10: show services application-identification application Output Fields (continued)

Field Name	Field Description
<b>Signature:</b>	Signature mapping criteria for application identification: Port range, Client-to-server, and Order.
<b>Alias List:</b>	An alternative name for an application.

## Sample Output

### show services application-identification application summary

```

user@host> show services application-identification application summary
Application(s): 3616
Applications                               Disabled      ID      Order
junos:SLACKER                             No            1179    1
junos:GOOGLE-TRUSTED-STORE                No            2819    5
junos:AMJILT                              No            2272    4
junos:DSI                                 No            2644    3
junos:HLN                                 No            2096    2
junos:ETSI-LI                             No            537     1
junos:CRAZYSALOON                         No            1720    5
junos:EKSISOZLUK                          No            2436    4
junos:SABAH                               No            2574    3
junos:AFREECA                             No            2373    2
junos:SENEWEB                             No            2068    1
junos:DIINO                               No            776     5
junos:CARE2                               No            376     4
junos:MOBAGE                              No            1456    3
junos:CARTOONNETWORK                      No            982     2
junos:AVATARS-UNITED                      No            363     1
junos:CONVIVA                             No            2015    5
junos:DREAMORA                            No            1725    4
junos:ELWATANNEWS                         No            2381    3
junos:REUTERS                             No            1044    2
junos:BABYCENTER                          No            364     1
junos:SOUTHWEST                           No            289     5

```

```

junos:ONEDIO                                     No                2517      4

```

```

.....
.....

```

### show services application-identification application detail

```

user@host> show services application-identification application detail junos:FTP

Application Name: junos:FTP
Application type: FTP
Description: This signature detects the File Transfer Protocol (FTP), which
provides facilities for transferring files to and from remote computer systems.
It usually runs on TCP port 21.
Application ID: 45
Priority: high
Order: 0
Disabled: Yes
Cacheable: Yes
Activation Date: 2003-05-05
Last Modified: 2016-04-11
Number of Parent Group(s): 1
Application Groups:
    junos:infrastructure:file-servers
Application Tags:
    characteristic      : Supports File Transfer
    characteristic      : Known Vulnerabilities
    characteristic      : Capable of Tunneling
    risk                 : 3
    subcategory          : File-Servers
    category             : Infrastructure
Layer-7 Protocol(s):
    Protocol: TCP        / 205
    Protocol: SPDY       / 1469
    Protocol: SOCKS5     / 193
    Protocol: SOCKS4     / 192
    Protocol: HTTPS      / 68
    Protocol: HTTP2      / 2553
    Protocol: HTTP       / 67
Port Mapping:
    Default ports: TCP/21

```

### show services application-identification application detail (Custom Applications)

```

user@host> show services application-identification application detail my-custom-app

Application Name: my-custom-app
Application type: MY-CUSTOM-APP
Description: custom App
Application ID: 16777216
Priority: high
Order: 65500
Disabled: No
Cacheable: No
Activation Date: N/A
Last Modified: N/A
Layer-7 Protocol(s):

```

```
Protocol: http          / http
Port range: N/A
Member(s): 1
  Member m01
    Context: http-header-host
    Pattern: MY-SERVER.COM
    Direction: CTS
```

## Sample Output

### show services application-identification application detail (Unified Policies)

```
user@host> show services application-identification application detail
```

```
Application Name: junos:GOOGLE
Application type: GOOGLE
Description: This signature detects SSL connections to Google.com. Google is a
             company best known for their search engine but offers many cloud
             based services.
Application ID: 54
Priority: high
Order: 0
Disabled: No
Cacheable: No
Activation Date: 2003-05-05
Last Modified: 2017-06-28
Number of Parent Group(s): 2
Application Groups:
  junos:web:applications
  junos:web:portal
Application Tags:
  characteristic      : Can Leak Information
  characteristic      : Loss of Productivity
  characteristic      : Supports File Transfer
  risk                : 3
  subcategory         : Applications
  category            : Web
Underlying consolidated Protocols/ports application is dependent on:
Protocols:
  Protocol: junos:GOOGLE-GEN / 943
  Protocol: junos:STUN / 201
  Protocol: junos:UDP / 216
  Protocol: junos:TCP / 205
  Protocol: junos:HTTP-PROXY / 2956
  Protocol: junos:SSL / 199
  Protocol: junos:SPDY / 1469
  Protocol: junos:POSTGRESQL / 150
  Protocol: junos:HTTPS / 68
  Protocol: junos:HTTP / 67
  Protocol: junos:NET-PROXY / 2629
  Protocol: junos:HTTP2 / 2553
  Protocol: junos:HTTP-TUNNEL / 750
  Protocol: junos:COTP / 22
  Protocol: junos:RTSP / 176
  Protocol: junos:RTP / 175
  Protocol: junos:DTLS / 1291
  Protocol: junos:RTMP / 337
  Protocol: junos:QUIC / 2521
  Protocol: junos:JABBER / 94
```

TCP Ports:  
  Port: 443  
  Port: 554  
  Port: 80  
UDP Ports:  
  Port: 554  
Layer-7 Immediate Protocol(s):  
  Protocol: GOOGLE-GEN / 943  
Alias List:  
  junos:GOOGLE-SSL  
Application Specific Ports:  
  Default ports: N/A  
Signature:  
  Port range: N/A  
  Client-to-server  
  Order: 1

## show services application-identification version

---

<b>Syntax</b>	show services application-identification version
<b>Release Information</b>	Command introduced in Junos OS Release 10.2. Command introduced in Junos OS Release 18.3R1 for logical systems.
<b>Description</b>	Displays the Junos OS application package version.
<b>Required Privilege Level</b>	view
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">request services application-identification download on page 140</a></li></ul>
<b>List of Sample Output</b>	<a href="#">show services application-identification version on page 164</a> <a href="#">show services application-identification version (Logical Systems) on page 164</a>

## Sample Output

### show services application-identification version

The following output shows that the application package version is 1608.

```
user@host> show services application-identification version
Application package version: 1608
```

### show services application-identification version (Logical Systems)

The following output shows that the application package version is 534.

```
user@host> show services application-identification version
Application package version: 534
```

## show services flows

**Syntax** show services flows  
 <all | brief | extensive | terse>  
 <application-protocol *protocol*>  
 <count>  
 <destination-port *destination-port*>  
 <destination-prefix *destination-prefix*>  
 <interface *interface-name*>  
 <limit *number*>  
 <protocol *protocol*>  
 <service-set *service-set*>  
 <source-port *source-port*>  
 <source-prefix *source-prefix*>

**Release Information** Command introduced in Junos OS Release 9.5.  
**all** option added in Junos OS Release 11.1.  
**application-protocol** option added in Junos OS Release 11.1.

**Description** Display flow session table entries.

**Options** **none**—Display standard information about all flows.

**all | brief | extensive | terse**—(Optional) Display the specified level of output.

**application-protocol** *protocol*—(Optional) Display information about one of the following application protocols:

- **bootp**—Bootstrap protocol
- **dce-rpc**—Distributed Computing Environment-Remote Procedure Call protocols
- **dce-rpc-portmap**—Distributed Computing Environment-Remote Procedure Call protocols portmap service
- **dns**—Domain Name System protocol
- **exec**—Exec
- **ftp**—File Transfer Protocol
- **h323**—H.323 standards
- **icmp**—Internet Control Message Protocol
- **iiop**—Internet Inter-ORB Protocol
- **login**—Login
- **netbios**—NetBIOS
- **netshow**—NetShow
- **pptp**—Point-to-Point Tunneling Protocol
- **realaudio**—RealAudio

- **rpc**—Remote Procedure Call protocol
- **rpc-portmap**—Remote Procedure Call protocol portmap service
- **rtsp**—Real-Time Streaming Protocol
- **shell**—Shell
- **sip**—Session Initiation Protocol
- **snmp**—Simple Network Management Protocol
- **sqlnet**—SQLNet
- **talk**—Talk Program
- **tftp**—Trivial File Transfer Protocol
- **traceroute**—Traceroute
- **winframe**—WinFrame



**NOTE:** The flows for the DCE RPC ALG match the flows for the DCE RPC Portmap ALG. The flows for the RPC ALG match the flows for the RPC Portmap ALG.

---

**count**—(Optional) Display a count of the matching entries.

**destination-port *destination-port***—(Optional) Display information for the specified destination port. The range of values is from 0 to 65535.

**destination-prefix *destination-prefix***—(Optional) Display information for the specified destination prefix.

**interface *interface-name***—(Optional) Display information about the specified interface. On M Series and T Series routers, *interface-name* can be *ms-fpc/pic/port* or *rspnumber*.

**limit *number***—(Optional) Maximum number of entries to display.

**protocol *protocol***—(Optional) Display information about one of the following IP types:

- ***number***—Numeric protocol value from 0 to 255
- **ah**—IPsec Authentication Header protocol
- **egp**—An exterior gateway protocol
- **esp**—IPsec Encapsulating Security Payload protocol
- **gre**—A generic routing encapsulation protocol
- **icmp**—Internet Control Message Protocol
- **icmp6**—Internet Control Message Protocol version 6

- **igmp**—Internet Group Management Protocol
- **ipip**—IP-within-IP Encapsulation Protocol
- **ospf**—Open Shortest Path First protocol
- **pim**—Protocol Independent Multicast protocol
- **rsvp**—Resource Reservation Protocol
- **sctp**—Stream Control Transmission Protocol
- **tcp**—Transmission Control Protocol
- **udp**—User Datagram Protocol

**service-set *service-set***—(Optional) Display information for the specified service set.

**source-port *source-port***—(Optional) Display information for the specified source port.  
The range of values is from 0 to 65535.

**source-prefix *source-prefix***—(Optional) Display information for the specified source prefix.

**Required Privilege Level**

view

**Related Documentation**

- [clear services flows on page 135](#)

**List of Sample Output**

[show services flows on page 168](#)  
[show services flows all on page 169](#)  
[show services flows brief on page 169](#)  
[show services flows extensive on page 169](#)  
[show services flows application-protocol on page 169](#)  
[show services flows count on page 170](#)  
[show services flows destination-port on page 170](#)  
[show services flows destination-prefix on page 170](#)  
[show services flows interface on page 170](#)  
[show services flows protocol on page 170](#)  
[show services flows service-set on page 170](#)  
[show services flows source-port on page 171](#)  
[show services flows source-prefix on page 171](#)

**Output Fields** [Table 11 on page 167](#) lists the output fields for the **show services flows** command. Output fields are listed in the approximate order in which they appear.

*Table 11: show services flows Output Fields*

Field Name	Field Description	Level of Output
<b>Interface</b>	Name of the interface.	All levels

Table 11: show services flows Output Fields (continued)

Field Name	Field Description	Level of Output
<b>Service set</b>	Name of a service set. Individual empty service sets are not displayed. If no service set has any flows, a flow table header is displayed for each service set.	All levels
<b>Flow Count</b>	Number of flows in a session.	<b>count</b> only
<b>Flow or Flow Prot</b>	Protocol used for this flow.	All levels
<b>Source</b>	Source prefix of the flow in the format <i>source-prefix:port</i> . For ICMP flows, port information is not displayed.	All levels
<b>Dest</b>	Destination prefix of the flow. For ICMP flows, port information is not displayed.	All levels
<b>State</b>	Status of the flow: <ul style="list-style-type: none"> <li>• <b>Drop</b>—Drop all packets in the flow without response.</li> <li>• <b>Forward</b>—Forward the packet in the flow without looking at it.</li> <li>• <b>Reject</b>—Drop all packets in the flow with response.</li> <li>• <b>Watch</b>—Inspect packets in the flow.</li> </ul>	All levels
<b>Dir</b>	Direction of the flow: input (I) or output (O).	All levels
<b>Frm count</b>	Number of frames in the flow.	All levels
<b>Byte count</b>	Number of bytes in the flow.	<b>extensive</b>
<b>Flow role</b>	Flow role.	<b>extensive</b>
<b>Timeout</b>	Timeout value.	<b>extensive</b>
<b>Flow path</b>	Flow path: symmetric or asymmetric.	<b>extensive</b>

## Sample Output

### show services flows

```

user@host> show services flows
Interface: ms-2/0/0, Service set: IDP
Flow
TCP      10.2.2.2:33656 -> 10.1.1.2:80    Forward I      6
TCP      10.1.1.2:80   -> 10.2.2.2:33656 Forward O      5
ICMP     10.1.1.2       -> 10.2.2.2       Forward I     102
ICMP     10.2.2.2       -> 10.1.1.2       Forward O     102
ICMP     10.2.2.2       -> 10.1.1.2       Forward I      97
ICMP     10.1.1.2       -> 10.2.2.2       Forward O      97

```

### show services flows all

```

user@host> show services flows all
Interface: ms-2/0/0, Service set: idp-1
Flow                                     State   Dir      Frm count
TCP      10.1.1.2:32769 ->      192.0.2.2:80   Forward I      353431
TCP      192.0.2.2:80  ->      10.1.1.2:32769 Forward O      353429
TCP      10.1.1.2:32771 ->      192.0.2.2:80   Forward I      353562
TCP      192.0.2.2:80  ->      10.1.1.2:32771 Forward O      353560
TCP      10.1.1.2:32770 ->      192.0.2.2:80   Forward I      353577
TCP      192.0.2.2:80  ->      10.1.1.2:32770 Forward O      353575
TCP      10.1.1.2:32768 ->      192.0.2.2:80   Forward I      353610
TCP      192.0.2.2:80  ->      10.1.1.2:32768 Forward O      353608
TCP      10.1.1.2:32777 ->      192.0.2.2:80   Forward I      353625
TCP      192.0.2.2:80  ->      10.1.1.2:32777 Forward O      353624
TCP      10.1.1.2:32776 ->      192.0.2.2:80   Forward I      353643
TCP      192.0.2.2:80  ->      10.1.1.2:32776 Forward O      353642
TCP      10.1.1.2:32775 ->      192.0.2.2:80   Forward I      353658
TCP      192.0.2.2:80  ->      10.1.1.2:32775 Forward O      353657
TCP      10.1.1.2:32774 ->      192.0.2.2:80   Forward I      353676
TCP      192.0.2.2:80  ->      10.1.1.2:32774 Forward O      353674
TCP      10.1.1.2:32773 ->      192.0.2.2:80   Forward I      353692
TCP      192.0.2.2:80  ->      10.1.1.2:32773 Forward O      353690
TCP      10.1.1.2:32772 ->      192.0.2.2:80   Forward I      353704
TCP      192.0.2.2:80  ->      10.1.1.2:32772 Forward O      353702

```

### show services flows brief

The output for the **show services flows brief** command is identical to that for the **show services flows** command. For sample output, see [show services flows](#).

### show services flows extensive

```

user@host> show services flows extensive
Interface: ms-2/0/0, Service set: IDP
Flow                                     State   Dir      Frm count
TCP      10.2.2.2:33656 ->      10.1.1.2:80    Forward I      6
  Byte count: 346
  Flow role: Unknown, Timeout: 0, Flow path: Asymmetric
TCP      10.1.1.2:80  ->      10.2.2.2:33656 Forward O      5
  Byte count: 334
  Flow role: Unknown, Timeout: 0, Flow path: Symmetric
ICMP     10.1.1.2     ->      10.2.2.2       Forward I      144
  Byte count: 12096
  Flow role: Unknown, Timeout: 0, Flow path: Symmetric
ICMP     10.2.2.2     ->      10.1.1.2       Forward O      144
  Byte count: 12096
  Flow role: Unknown, Timeout: 0, Flow path: Symmetric

```

### show services flows application-protocol

```

user@host> show services flows application-protocol dce-rpc
Interface: ms-2/0/0, Service set: ss-1
Flow                                     State   Dir      Frm count
TCP      192.168.200.65:1260 -> 192.168.200.69:5315 Forward I      14
TCP      192.168.200.69:5315 -> 198.51.100.16:1031 Forward O      11
TCP      192.168.200.65:1251 -> 192.168.200.69:1026 Forward I      7

```

```
TCP      192.168.200.69:1026  ->    198.51.100.16:1029  Forward  0
5
```

### show services flows count

```
user@host> show services flows count
Interface  Service set      Flow count
ms-2/0/0   IDP              6
```

### show services flows destination-port

```
user@host> show services flows destination-port 80
Interface: ms-2/0/0, Service set: IDP
Flow      State  Dir      Frm count
TCP       10.2.2.2:33656 ->    10.1.1.2:80  Forward  I        6
```

### show services flows destination-prefix

```
user@host> show services flows destination-prefix 10.1.1.2
Interface: ms-2/0/0, Service set: IDP
Flow      State  Dir      Frm count
TCP       10.2.2.2:33656 ->    10.1.1.2:80  Forward  I        6
ICMP      10.2.2.2        ->    10.1.1.2      Forward  O       137
ICMP      10.2.2.2        ->    10.1.1.2      Forward  I       132
```

### show services flows interface

```
user@host> show services flows interface ms-2/0/0
Interface: ms-2/0/0, Service set: IDP
Flow      State  Dir      Frm count
TCP       10.2.2.2:33656 ->    10.1.1.2:80  Forward  I        6
TCP       10.1.1.2:80   ->    10.2.2.2:33656 Forward  O        5
ICMP      10.1.1.2        ->    10.2.2.2      Forward  I       162
ICMP      10.2.2.2        ->    10.1.1.2      Forward  O       162
ICMP      10.2.2.2        ->    10.1.1.2      Forward  I       157
ICMP      10.1.1.2        ->    10.2.2.2      Forward  O       157
```

### show services flows protocol

```
user@host> show services flows protocol icmp
Interface: ms-2/0/0, Service set: IDP
Flow      State  Dir      Frm count
ICMP      10.1.1.2        ->    10.2.2.2      Forward  I       202
ICMP      10.2.2.2        ->    10.1.1.2      Forward  O       202
ICMP      10.2.2.2        ->    10.1.1.2      Forward  I       197
ICMP      10.1.1.2        ->    10.2.2.2      Forward  O       197
```

### show services flows service-set

```
user@host> show services flows service-set sample
Interface: ms-2/0/0, Service set: sample
Flow      State  Dir      Frm count
TCP       10.2.2.2:33656 ->    10.1.1.2:80  Forward  I        6
TCP       10.1.1.2:80   ->    10.2.2.2:33656 Forward  O        5
ICMP      10.1.1.2        ->    10.2.2.2      Forward  I       220
ICMP      10.2.2.2        ->    10.1.1.2      Forward  O       220
ICMP      10.2.2.2        ->    10.1.1.2      Forward  I       215
ICMP      10.1.1.2        ->    10.2.2.2      Forward  O       215
```

**show services flows source-port**

```

user@host> show services flows source-port 0
Interface: ms-2/0/0, Service set: IDP
Flow
TCP      10.2.2.2:33656 -> 10.1.1.2:80 Forward I      6
TCP      10.1.1.2:80 -> 10.2.2.2:33656 Forward 0      5
ICMP     10.1.1.2 -> 10.2.2.2 Forward I     235
ICMP     10.2.2.2 -> 10.1.1.2 Forward 0     235
ICMP     10.2.2.2 -> 10.1.1.2 Forward I     230
ICMP     10.1.1.2 -> 10.2.2.2 Forward 0     230

```

**show services flows source-prefix**

```

user@host> show services flows source-prefix 10.2.2.2
Interface: ms-2/0/0, Service set: IDP
Flow
TCP      10.2.2.2:33656 -> 10.1.1.2:80 Forward I      6
TCP      10.1.1.2:80 -> 10.2.2.2:33656 Forward 0      5
ICMP     10.1.1.2 -> 10.2.2.2 Forward I     235
ICMP     10.2.2.2 -> 10.1.1.2 Forward 0     235
ICMP     10.2.2.2 -> 10.1.1.2 Forward I     230
ICMP     10.1.1.2 -> 10.2.2.2 Forward 0     230

```

## show services local-policy-decision-function flows

<b>Syntax</b>	<b>show services local-policy-decision-function flows</b> (interface <i>interface-name</i>   subscriber <i>subscriber-name</i> )
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Display local policy decision function (L-PDF) flows.
<b>Options</b>	<b>interface <i>interface-name</i></b> —Display L-PDF flows for the specified interface only. <b>subscriber <i>subscriber-name</i></b> —Display L-PDF flows for the specified subscriber only.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	<a href="#">show services local-policy-decision-function flows subscriber on page 173</a> <a href="#">show services local-policy-decision-function flows interface on page 173</a>
<b>Output Fields</b>	Table 12 on page 172 lists the output fields for the <b>show services local-policy-decision-function flows</b> command. Output fields are listed in the approximate order in which they appear.

Table 12: show services local-policy-decision-function flows Output Fields

Field Name	Field Description
Interface	Interface name.
service-set	Service set name.
service-set-interface	Service set interface name.
Currently active flows	Number of currently active flows.
High watermark flows	Maximum number of flows.
Protocol	(With <b>interface</b> option) Protocol identifier.
Source address	(With <b>interface</b> option) Source address.
Source port	(With <b>interface</b> option) Source port.
Destination address	(With <b>interface</b> option) Destination address.
Destination port	(With <b>interface</b> option) Destination port.
Application	(With <b>interface</b> option) Application name.

Table 12: show services local-policy-decision-function flows Output Fields (continued)

Field Name	Field Description
Application group	(With interface option) Application group identifier.

## Sample Output

### show services local-policy-decision-function flows subscriber

```

user@host> show services local-policy-decision-function flows subscriber user@example.com
Interface: ge-0/0/5.26

service-set: aacl_ms30
service-set interface: ms-3/0/0

Currently active flows: 0
High watermark flows: 0

```

### show services local-policy-decision-function flows interface

```

user@host> show services local-policy-decision-function flows interface ge-1/1/0
Interface: ge-1/1/0.0

service-set: IDP
service-set interface: ms-2/0/0

Currently active flows: 2
High watermark flows: 2

```

Protocol	Source address	Source port	Destination address	Destination port
Application		Application group		
tcp	10.1.1.2	81	198.51.100.2	32813
	junos:ftp [63]	unknown [1023]		
tcp	198.51.10.2	32813	10.1.1.2	81
	junos:ftp [63]	unknown [1023]		

## show services local-policy-decision-function statistics

<b>Syntax</b>	<code>show services local-policy-decision-function statistics (interface <i>interface-name</i>   subscriber <i>subscriber-name</i>)</code>
<b>Release Information</b>	Command introduced in Junos OS Release 9.5.
<b>Description</b>	Display local-policy-decision-function (L-PDF) statistics.
<b>Options</b>	<p><code>interface <i>interface-name</i></code>—Display L-PDF statistics for the specified interface only.</p> <p><code>subscriber <i>subscriber-name</i></code>—Display L-PDF statistics for the specified subscriber only.</p>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	<p><a href="#">show services local-policy-decision-function statistics interface on page 175</a></p> <p><a href="#">show services local-policy-decision-function statistics subscriber on page 175</a></p>
<b>Output Fields</b>	<p><a href="#">Table 13 on page 174</a> lists the output fields for the <b>show services local-policy-decision-function statistics</b> command. Output fields are listed in the approximate order in which they appear.</p>

*Table 13: show services local-policy-decision-function statistics Output Fields*

Field Name	Field Description
Interface	Interface name.
service-set	Service set name.
service-set-interface	Service set interface name.
Application group	Application group identifier.
Application	Application name.
Packets in	Number of ingress packets.
Bytes in	Number of ingress bytes.
Packets out	Number of egress packets.
Bytes out	Number of egress bytes.

## Sample Output

### show services local-policy-decision-function statistics interface

```
user@host> show services local-policy-decision-function statistics interface ge-1/1/0
Interface: ge-1/1/0.0
```

```
service-set: IDP
service-set interface: ms-2/0/0
```

Application group	Application	Packets in	Bytes in
Packets out	Bytes out		
6	junos:ftp [63]	5	334
	346		

### show services local-policy-decision-function statistics subscriber

```
user@host> show services local-policy-decision-function statistics subscriber user@example.com
Service-set-interface: ms-1/3/0
Service set: aacl-svc-set
```

Application-aware-access-list statistics

Application group	Packets in	Bytes in	Packets out	Bytes
out				
P2P	16284	400	32025	200
FTP	8700	20000	5231000	100

## show services sessions

**Syntax** show services sessions  
 <brief | extensive | terse>  
 <application-protocol *protocol*>  
 <count>  
 <destination-port *destination-port*>  
 <destination-prefix *destination-prefix*>  
 <interface *interface-name*>  
 <limit *number*>  
 <protocol *protocol*>  
 <service-set *service-set*>  
 <source-port *source-port*>  
 <source-prefix *source-prefix*>  
 <utilization>

**Release Information** Command introduced in Junos OS Release 10.4.

**Description** Display session information.



**NOTE:** On MX Series routers (with interchassis redundancy configured), the idle timeout for every flow is displayed in the **show services session extensive** and **show services flows extensive** commands.

**Options** **none**—Display standard information about all sessions.

**brief | extensive | terse**—(Optional) Display the specified level of output.

**application-protocol *protocol***—(Optional) Display information about one of the following application protocols:

- **bootp**—Bootstrap protocols
- **dce-rpc**—Distributed Computing Environment-Remote Procedure Call protocols
- **dce-rpc-portmap**—Distributed Computing Environment-Remote Procedure Call protocols portmap service
- **dns**—Domain Name System protocol
- **exec**—Remote Execution Protocol
- **ftp**—File Transfer Protocol
- **h323**—H.323
- **icmp**—ICMP
- **icmpv6**—ICMPv6
- **iiop**—Internet Inter-ORB Protocol

- **ike-esp-nat**—IKE ALG
- **ip**—IP
- **login**—LOGIN
- **netbios**—NETBIOS
- **netshow**—NETSHOW
- **pptp**—Point-to-Point Tunneling Protocol
- **realaudio**—RealAudio
- **rpc**—Remote Procedure Call protocol
- **rpc-portmap**—Remote Procedure Call protocol portmap service
- **rtsp**—Real-Time Streaming Protocol
- **rsh**—Remote Shell
- **sip**—Session Initiation Protocol
- **shell**—Shell
- **snmp**—SNMP
- **sql**—SQLNet
- **talk**—Talk Program
- **tftp**—Trivial File Transfer Protocol
- **traceroute**—Traceroute
- **winframe**—WinFrame



**NOTE:** You can use the **none** option with the **show services sessions count application-protocol** command to display information about sessions other than ALG sessions.

**count**—(Optional) Display a count of the matching entries.

**destination-port *destination-port***—(Optional) Display information for the specified destination port. The range of values is from 0 to 65,535.

**destination-prefix *destination-prefix***—(Optional) Display information for the specified destination prefix.

**interface *interface-name***—(Optional) Display information about the specified interface. On M Series and T Series routers, *interface-name* can be **ms-fpc/pic/port** or **rspnumber**. On J Series routers, *interface-name* is **ms-pim/0/port**.

**limit *number***—(Optional) Maximum number of entries to display.

**protocol *protocol***—(Optional) Display information about one of the following IP types:

- ***number***—Numeric protocol value from 0 to 255
- ***ah***—IPsec Authentication Header protocol
- ***egp***—An exterior gateway protocol
- ***esp***—IPsec Encapsulating Security Payload protocol
- ***gre***—A generic routing encapsulation protocol
- ***icmp***—Internet Control Message Protocol
- ***icmp6***—Internet Control Message Protocol version 6
- ***igmp***—Internet Group Management Protocol
- ***ipip***—IP-within-IP Encapsulation Protocol
- ***ospf***—Open Shortest Path First protocol
- ***pim***—Protocol Independent Multicast protocol
- ***rsvp***—Resource Reservation Protocol
- ***sctp***—Stream Control Transmission Protocol
- ***tcp***—Transmission Control Protocol
- ***udp***—User Datagram Protocol

**service-set *service-set***—(Optional) Display information for the specified service set.

**source-port *source-port***—(Optional) Display information for the specified source port.  
The range of values is from 0 to 65,535.

**source-prefix *source-prefix***—(Optional) Display information for the specified source prefix.

**utilization**—(Optional) Display statistical details about session utilization.

**Required Privilege  
Level**

view

**List of Sample Output**

[show services sessions on page 179](#)  
[show services sessions brief on page 180](#)  
[show services sessions extensive on page 180](#)  
[show services sessions terse on page 180](#)  
[show services sessions application-protocol on page 180](#)  
[show services sessions count on page 182](#)  
[show services sessions destination-port on page 183](#)  
[show services sessions destination-prefix on page 183](#)  
[show services sessions interface on page 183](#)  
[show services sessions protocol on page 183](#)  
[show services sessions service-set on page 183](#)

[show services sessions source-port on page 183](#)

[show services sessions source-prefix on page 183](#)

**Output Fields** Table 14 on page 179 lists the output fields for the **show services sessions** command. Output fields are listed in the approximate order in which they appear.

*Table 14: show services sessions Output Fields*

Field Name	Field Description	Level of Output
<b>Interface</b>	Name of the interface.	<b>application-protocol</b>
<b>Session</b>	Session ID that uniquely identifies the session.	All levels
<b>ALG</b>	Name of the application.	<b>terse</b>
<b>Flags</b>	Session flag for the ALG: <ul style="list-style-type: none"> <li>• <b>0x1</b>—Found an existing session.</li> <li>• <b>0x2</b>—Reached session or flow limit.</li> <li>• <b>0x3</b>—No memory available for new sessions.</li> <li>• <b>0x4</b>—No free session ID available.</li> <li>• <b>0x0000</b>—No session ID found.</li> </ul>	All levels
<b>IP Action</b>	Flag indicating whether IP action has been set for the session.	All levels
<b>Offload</b>	Flag indicating whether the session has been offloaded to the Packet Forwarding Engine.	All levels
<b>Asymmetric</b>	Flag indicating whether the session is uni-directional.	<b>terse</b>  <b>application-protocol</b>
<b>Service set</b>	Name of a service set. Individual empty service sets are not displayed.	<b>count</b>
<b>Sessions Count</b>	Number of sessions.	<b>count</b>

## Sample Output

### show services sessions

```

user@host> show services sessions
ms-2/0/0
Session: 293, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP    10.10.10.2:43677 ->    10.20.20.1:53    Forward I      1
UDP    10.20.20.1:53    ->    192.0.2.1:43677 Forward 0      1
Session: 53, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP    10.10.10.2:37494 ->    10.20.20.1:53    Forward I      1
UDP    10.20.20.1:53    ->    10.11.11.11:37494 Forward 0      1
Session: 66, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP    10.10.10.2:48161 ->    10.20.20.1:53    Forward I      1
UDP    10.20.20.1:53    ->    10.11.11.11:48161 Forward 0      1
Session: 17, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP    10.10.10.2:38908 ->    10.20.20.1:53    Forward I      1

```

```

UDP    10.20.20.1:53    ->      10.11.11.11:38908 Forward  0      1
Session: 42, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP    10.10.10.2:58189 ->      10.20.20.1:53    Forward  I      1
UDP    10.20.20.1:53    ->      10.11.11.11:58189 Forward  0      1

```

### show services sessions brief

The output for the **show services flows brief** command is identical to that for the **show services sessions** command. For sample output, see [show services sessions on page 179](#).

### show services sessions extensive

```

user@host> show services sessions extensive
ms-0/1/0
Session: 2, ALG: 0, Flags: 0x0080, IP Action: no, Offload: no
NAT Pugin Data:
  NAT Action: Translation Type - DYNAMIC NAT44
  NAT source   192.0.21.2    ->   10.10.10.127
TCP    192.0.2.2:52145 ->   198.51.100.2:23    Forward  I
      22
  Byte count: 1483
  Flow role: Unknown, Timeout: 0
TCP    198.51.100.2:23    ->   10.10.10.127:52145 Forward  0
      18
  Byte count: 2712
  Flow role: Unknown, Timeout: 0

```

### show services sessions terse

```

user@router> show services sessions terse
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP    10.2.2.2:52138 ->   10.1.1.2:21    Forward  I      33
TCP    10.1.1.2:21    ->   10.2.2.2:52138 Forward  0      31

```

### show services sessions application-protocol

This command has the same output for the rpc, dce-rpc, rpc-portmap and dce-rpc-portmap ALGs.

```

user@router> show services sessions application-protocol dce-rpc
Interface name: ms-1/1/0
Session: 8, ALG: portmapper, Flags: 0x1800, IP Action: no, Offload: no
UDP    192.168.203.198:1019 ->192.168.203.194:2049 Forward  I      4
UDP    192.168.203.194:2049 ->192.168.203.198:1019 Forward  0      4
Session: 7, ALG: portmapper, Flags: 0x1800, IP Action: no, Offload: no
UDP    192.168.203.198:954  ->192.168.203.194:613  Forward  I      1
UDP    192.168.203.194:613  ->192.168.203.198:954  Forward  0      1
Session: 6, ALG: portmapper, Flags: 0x1800, IP Action: no, Offload: no
UDP    192.168.203.198:53836 ->192.168.203.194:613  Forward  I      1
UDP    192.168.203.194:613  ->192.168.203.198:53836 Forward  0      1
Session: 5, ALG: portmapper, Flags: 0x1000, IP Action: no, Offload: no
UDP    192.168.203.198:59813 ->192.168.203.194:111  Forward  I      1
UDP    192.168.203.194:111  ->192.168.203.198:59813 Forward  0      1
Session: 4, ALG: portmapper, Flags: 0x1800, IP Action: no, Offload: no
UDP    192.168.203.198:36595 ->192.168.203.194:2049 Forward  I      1
UDP    192.168.203.194:2049 ->192.168.203.198:36595 Forward  0      1

```

```

Session: 3, ALG: portmapper, Flags: 0x1000, IP Action: no, Offload: no
UDP 192.168.203.198:56050 ->192.168.203.194:111 Forward I 1
UDP 192.168.203.194:111 ->192.168.203.198:56050 Forward 0 1

user@router> show services sessions application-protocol dns
Interface name: ms-2/0/0
Session: 293, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP 198.51.100.2:43677 -> 203.0.113.10:53 Forward I 1
UDP 203.0.113.10:53 -> 192.0.2.1:43677 Forward 0 1
Session: 53, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP 198.51.100.2:37494 -> 203.0.113.10:53 Forward I 1
UDP 203.0.113.10:53 -> 192.0.2.1:37494 Forward 0 1
Session: 66, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP 198.51.100.2:48161 -> 203.0.113.10:53 Forward I 1
UDP 203.0.113.10:53 -> 192.0.2.1:48161 Forward 0 1
Session: 17, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP 198.51.100.2:38908 -> 203.0.113.10:53 Forward I 1
UDP 203.0.113.10:53 -> 192.0.2.1:38908 Forward 0 1
Session: 42, ALG: 16, Flags: 0x0040, IP Action: no, Offload: no
UDP 198.51.100.2:58189 -> 203.0.113.10:53 Forward I 1
UDP 203.0.113.10:53 -> 192.0.2.1:58189 Forward 0 1

user@router> show services sessions application-protocol ftp
Interface name: ms-4/1/0
Session: 1, ALG: 1, Flags: 0x0040, IP Action: no, Offload: no
TCP 192.0.2.129:32843 -> 198.51.100.129:21 Forward I 26
TCP 198.51.100.129:21 -> 192.0.2.0:32843 Forward 0 30

user@router> show services sessions application-protocol ike-esp-nat
Service Set: ss_ipv4, Session: 33554435, ALG: ike-esp-nat, Flags: 0x0800, IP
Action: no, Offload: no, Asymmetric: no
ESP 198.51.100.2:4689 -> 203.0.113.1:62108 Forward 0 2199
ESP 192.0.2.2:62108 -> 198.51.100.2:4689 Forward I 0
Service Set: ss_ipv4, Session: 33554434, ALG: ike-esp-nat, Flags: 0x0800, IP
Action: no, Offload: no, Asymmetric: no
ESP 192.0.2.2:44179 -> 198.51.100.2:43809 Forward I 2199
ESP 198.51.100.2:43809 -> 203.0.113.1:44179 Forward 0 0
Service Set: ss_ipv4, Session: 33554433, ALG: ike-esp-nat, Flags: 0x0000, IP
Action: no, Offload: no, Asymmetric: no
UDP 192.0.2.2:500 -> 198.51.100.2:500 Forward I 8
UDP 198.51.100.2:500 -> 203.0.113.1:57730 Forward 0 0

user@router> show services sessions application-protocol pptp
Interface name: ms-2/0/0
Session: 3, ALG: pptp, Flags: 0x2800, IP Action: no, Offload: no, Asymmetric: no
GRE 203.0.113.138:0 -> 203.0.113.138:0 Forward 0
21
GRE 192.0.2.794:0 -> 203.0.113.138:0:65000 Forward I
0
Session: 2, ALG: pptp, Flags: 0x2800, IP Action: no, Offload: no, Asymmetric: no
GRE 192.0.2.794:0 -> 203.0.113.138:0:49913 Forward I
88
GRE 203.0.113.138:0:49913 -> 192.0.2.794:65001 Forward 0
0
Session: 1, ALG: pptp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP 192.0.2.794:1511 -> 203.0.113.138:0:1723 Forward I
13
TCP 203.0.113.138:0:1723 -> 192.0.2.794:1511 Forward 0
12

user@router> show services sessions application-protocol rtsp
Interface name: ms-0/1/0
Session: 13, ALG: rtsp, Flags: 0x0800, IP Action: no, Offload: no

```

```

UDP      203.0.113.66:5004 ->      198.51.100.66:3989 Forward 0      152
UDP      198.51.100.66:3989 ->      192.0.2.161:5004 Forward I      0
Session: 9, ALG: rtsp, Flags: 0x0800, IP Action: no, Offload: no
UDP      203.0.113.66:5004 ->      198.51.100.66:3986 Forward 0      3
UDP      198.51.100.66:3986 ->      192.0.2.161:5004 Forward I      0

user@router> show services sessions application-protocol rsh
Interface name: ms-2/0/0
Session: 3, ALG: 2, Flags: 0x0840, IP Action: no, Offload: no
TCP      203.0.113.10:1023 ->      198.51.100.2:1020 Forward 0      4
TCP      198.51.100.2:1020 ->      203.0.113.10:1023 Forward I      3
Session: 1, ALG: 2, Flags: 0x0040, IP Action: no, Offload: no
TCP      198.51.100.2:1021 ->      203.0.113.10:514 Forward I      1331
TCP      203.0.113.10:514 ->      198.51.100.2:1021 Forward 0      2485

user@router> show services sessions application-protocol sip
Interface name: ms-2/0/0
Session: 4, ALG: sip, Flags: 0x0800, IP Action: no, Offload: no
UDP      198.51.100.130:6000 ->      192.0.2.129:12682 Forward I
246
UDP      192.0.2.129:12682 ->      198.51.100.162:6000 Forward 0
0
Session: 1, ALG: sip, Flags: 0x0000, IP Action: no, Offload: no
UDP      198.51.100.130:5060 ->      192.0.2.130:5060 Forward I
10
UDP      192.0.2.130:5060 ->      198.51.100.162:5060 Forward 0
9

user@router> show services sessions application-protocol sql
Interface name: ms-2/0/0
Session: 3934, ALG: sqlnet, Flags: 0x0800, IP Action: no, Offload: no
TCP      198.51.100.2:39754 ->      203.0.113.138:0:1408 Forward I      26
TCP      203.0.113.138:0:1408 ->      192.0.2.1:39754 Forward 0      23

user@router> show services sessions application-protocol talk
Interface name: ms-0/2/0
Session: 4, ALG: 65, Flags: 0x0800, IP Action: no, Offload: no
TCP      203.0.113.162:36888 ->      192.0.2.2:33294 Forward 0
4
TCP      192.0.2.1:33294 ->      203.0.113.162:36888 Forward I
3
Session: 7, ALG: 65, Flags: 0x0800, IP Action: no, Offload: no
UDP      203.0.113.162:1165 ->      192.0.2.2:518 Forward 0
1
UDP      192.0.2.2:518 ->      203.0.113.162:1165 Forward I
1
Session: 8, ALG: 65, Flags: 0x0000, IP Action: no, Offload: no
UDP      192.0.2.2:1509 ->      203.0.113.162:518 Forward I
3
UDP      203.0.113.162:518 ->      192.0.2.2:1509 Forward 0
3
Session: 6, ALG: 0, Flags: 0x0000, IP Action: no, Offload: no
UDP      192.0.2.1:123 ->      192.0.2.2:123 Forward 0
4

```

### show services sessions count

```

user@host> show services sessions count
Interface  Service set                      Sessions count
ms-1/1/0   ss                                  2

```

### show services sessions destination-port

```

user@router> show services sessions destination-port 21
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      25
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      24

```

### show services sessions destination-prefix

```

user@router> show services sessions destination-prefix 10.1.1.2
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      25
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      24

```

### show services sessions interface

```

user@router> show services sessions interface ms-1/1/0
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      30
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      29

```

### show services sessions protocol

```

user@router> show services sessions protocol tcp
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      30
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      29

```

### show services sessions service-set

```

user@router> show services sessions service-set sample
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      33
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      31

```

### show services sessions source-port

```

user@router> show services sessions source-port 21
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      33
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      31

```

### show services sessions source-prefix

```

user@router> show services sessions source-prefix 10.2.2.2
ms-1/1/0
Session: 1, ALG: ftp, Flags: 0x2000, IP Action: no, Offload: no, Asymmetric: no
TCP      10.2.2.2:52138 ->      10.1.1.2:21    Forward I      33
TCP      10.1.1.2:21    ->      10.2.2.2:52138 Forward 0      31

```

