

# BGP Feature Guide for EX4600 Switches

Release

16.1



Modified: 2016-12-13

Juniper Networks, Inc.  
1133 Innovation Way  
Sunnyvale, California 94089  
USA  
408-745-2000  
[www.juniper.net](http://www.juniper.net)

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

*BGP Feature Guide for EX4600 Switches*

16.1

Copyright © 2016, Juniper Networks, Inc.  
All rights reserved.

The information in this document is current as of the date on the title page.

#### YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

#### END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <http://www.juniper.net/support/eula.html>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

# Table of Contents

	About the Documentation . . . . .	xiii
	Documentation and Release Notes . . . . .	xiii
	Supported Platforms . . . . .	xiii
	Using the Examples in This Manual . . . . .	xiii
	Merging a Full Example . . . . .	xiv
	Merging a Snippet . . . . .	xiv
	Documentation Conventions . . . . .	xv
	Documentation Feedback . . . . .	xvii
	Requesting Technical Support . . . . .	xvii
	Self-Help Online Tools and Resources . . . . .	xvii
	Opening a Case with JTAC . . . . .	xviii
<b>Part 1</b>	<b>Overview</b>	
<b>Chapter 1</b>	<b>BGP Overview . . . . .</b>	<b>3</b>
	Understanding BGP . . . . .	4
	Autonomous Systems . . . . .	4
	AS Paths and Attributes . . . . .	4
	External and Internal BGP . . . . .	5
	Multiple Instances of BGP . . . . .	5
	BGP Routes Overview . . . . .	6
	BGP Messages Overview . . . . .	7
	Open Messages . . . . .	7
	Update Messages . . . . .	8
	Keepalive Messages . . . . .	8
	Notification Messages . . . . .	8
	Route-Refresh Messages . . . . .	8
	Understanding the Advertisement of Multiple Paths to a Single Destination in BGP . . . . .	9

<b>Part 2</b>	<b>Configuration</b>	
<b>Chapter 2</b>	<b>Basic BGP Configuration</b>	<b>13</b>
	Examples: Configuring External BGP Peering	13
	Understanding External BGP Peering Sessions	13
	Example: Configuring External BGP Point-to-Point Peer Sessions	14
	Example: Configuring External BGP on Logical Systems with IPv6	
	Interfaces	21
	Examples: Configuring Internal BGP Peering	36
	Understanding Internal BGP Peering Sessions	36
	Example: Configuring Internal BGP Peer Sessions	37
	Example: Configuring Internal BGP Peering Sessions on Logical Systems	48
	Configuring BGP Monitoring Protocol Version 3	59
<b>Chapter 3</b>	<b>BGP Path Attribute Configuration</b>	<b>61</b>
	Example: Configuring BGP Local Preference	61
	Understanding the Local Preference Metric for Internal BGP Routes	61
	Example: Configuring the Local Preference Value for BGP Routes	61
	Examples: Configuring BGP MED	74
	Understanding the MED Attribute That Determines the Exit Point in an	
	AS	74
	Example: Configuring the MED Attribute That Determines the Exit Point in	
	an AS	77
	Example: Configuring the MED Using Route Filters	89
	Example: Configuring the MED Using Communities	102
	Example: Associating the MED Path Attribute with the IGP Metric and	
	Delaying MED Updates	103
	Examples: Configuring BGP Local AS	113
	Understanding the BGP Local AS Attribute	113
	Example: Configuring a Local AS for EBGp Sessions	118
	Example: Configuring a Private Local AS for EBGp Sessions	128
	Example: Configuring the Accumulated IGP Attribute for BGP	133
	Understanding the Accumulated IGP Attribute for BGP	134
	Example: Configuring the Accumulated IGP Attribute for BGP	134
<b>Chapter 4</b>	<b>BGP Policy Configuration</b>	<b>173</b>
	Example: Configuring BGP Interactions with IGP	173
	Understanding Routing Policies	173
	Example: Injecting OSPF Routes into the BGP Routing Table	174
	Example: Configuring BGP Route Advertisement	177
	Configuring Routing Policies to Control BGP Route Advertisements	177
	Applying Routing Policy	177
	Setting BGP to Advertise Inactive Routes	178
	Configuring BGP to Advertise the Best External Route to Internal	
	Peers	178
	Configuring How Often BGP Exchanges Routes with the Routing	
	Table	180
	Disabling Suppression of Route Advertisements	181
	Example: Configuring BGP Prefix-Based Outbound Route Filtering	181

	Example: Configuring EBGP Multihop . . . . .	185
	Understanding EBGP Multihop . . . . .	185
	Example: Configuring EBGP Multihop Sessions . . . . .	186
	Example: Configuring BGP Route Preference (Administrative Distance) . . . . .	195
	Understanding Route Preference Values (Administrative Distance) . . . . .	195
	Example: Configuring the Preference Value for BGP Routes . . . . .	197
	Example: Configuring BGP Path Selection . . . . .	202
	Understanding BGP Path Selection . . . . .	202
	Routing Table Path Selection . . . . .	204
	Effects of Advertising Multiple Paths to a Destination . . . . .	205
	Example: Ignoring the AS Path Attribute When Selecting the Best Path . . . . .	205
	Example: Removing Private AS Numbers . . . . .	212
	Understanding Private AS Number Removal from AS Paths . . . . .	213
	Example: Removing Private AS Numbers from AS Paths . . . . .	214
<b>Chapter 5</b>	<b>BGP BFD Configuration . . . . .</b>	<b>221</b>
	Example: Configuring BFD for BGP . . . . .	221
	Understanding BFD for BGP . . . . .	221
	Example: Configuring BFD on Internal BGP Peer Sessions . . . . .	222
	Example: Configuring BFD Authentication for BGP . . . . .	230
	Understanding BFD Authentication for BGP . . . . .	230
	BFD Authentication Algorithms . . . . .	231
	Security Authentication Keychains . . . . .	232
	Strict Versus Loose Authentication . . . . .	232
	Example: Configuring BFD Authentication for BGP . . . . .	232
	Configuring BFD Authentication Parameters . . . . .	232
	Viewing Authentication Information for BFD Sessions . . . . .	234
<b>Chapter 6</b>	<b>BGP Load Balancing Configuration . . . . .</b>	<b>237</b>
	Examples: Configuring BGP Multipath . . . . .	237
	Understanding BGP Multipath . . . . .	237
	Example: Load Balancing BGP Traffic . . . . .	238
	Example: Configuring Single-Hop EBGP Peers to Accept Remote Next Hops . . . . .	243
	Example: Advertising Multiple BGP Paths to a Destination . . . . .	254
	Understanding the Advertisement of Multiple Paths to a Single Destination in BGP . . . . .	254
	Example: Advertising Multiple Paths in BGP . . . . .	255
	Configuring ECMP Next Hops for RSVP and LDP LSPs for Load Balancing . . . . .	281
<b>Chapter 7</b>	<b>IBGP Scaling Configuration . . . . .</b>	<b>285</b>
	Example: Configuring BGP Route Reflectors . . . . .	285
	Understanding BGP Route Reflectors . . . . .	285
	Example: Configuring a Route Reflector . . . . .	288
	Example: Configuring BGP Confederations . . . . .	303
	Understanding BGP Confederations . . . . .	303
	Example: Configuring BGP Confederations . . . . .	304

<b>Chapter 8</b>	<b>BGP Security Configuration . . . . .</b>	<b>311</b>
	Example: Configuring BGP Route Authentication . . . . .	311
	Understanding Route Authentication . . . . .	311
	Example: Configuring Route Authentication for BGP . . . . .	312
	Examples: Configuring TCP and BGP Security . . . . .	318
	Understanding Security Options for BGP with TCP . . . . .	318
	Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers . . . . .	318
	Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List . . . . .	323
	Example: Limiting TCP Segment Size for BGP . . . . .	326
<b>Chapter 9</b>	<b>BGP Flap Configuration . . . . .</b>	<b>333</b>
	Example: Preventing BGP Session Resets . . . . .	333
	Understanding BGP Session Resets . . . . .	333
	Example: Preventing BGP Session Flaps When VPN Families Are Configured . . . . .	333
	Examples: Configuring BGP Flap Damping . . . . .	340
	Understanding Damping Parameters . . . . .	340
	Example: Configuring BGP Route Flap Damping Parameters . . . . .	341
	Example: Configuring BGP Route Flap Damping Based on the MBGP MVPN Address Family . . . . .	350
<b>Part 3</b>	<b>Administration</b>	
<b>Chapter 10</b>	<b>Routine Monitoring . . . . .</b>	<b>363</b>
	Tracing BMP Operations . . . . .	363
	Monitoring BGP Routing Information . . . . .	364
	Example: Configuring BGP Trace Operations . . . . .	365
	Understanding Trace Operations for BGP Protocol Traffic . . . . .	365
	Example: Viewing BGP Trace Files on Logical Systems . . . . .	367
<b>Part 4</b>	<b>Configuration Statements and Operational Commands</b>	
<b>Chapter 11</b>	<b>Configuration Statements . . . . .</b>	<b>375</b>
	accept-remote-nexthop . . . . .	378
	advertise-external . . . . .	379
	advertise-inactive . . . . .	381
	advertise-peer-as . . . . .	383
	algorithm (BGP BFD Authentication) . . . . .	384
	apply-groups . . . . .	386
	apply-groups-except . . . . .	386
	authentication (BGP BFD Liveness Detection) . . . . .	387
	authentication-algorithm . . . . .	389
	authentication-key (Protocols BGP and BMP) . . . . .	392
	authentication-key-chain (Protocols BGP and BMP) . . . . .	393
	bfd-liveness-detection (Protocols BGP) . . . . .	395
	bgp . . . . .	399
	bgp-orf-cisco-mode . . . . .	400
	cluster . . . . .	402

connection-mode	403
damping (Protocols BGP)	404
description (Protocols BGP)	406
detection-time (BFD Liveness Detection)	407
disable (Protocols BGP)	408
disable (BGP Graceful Restart)	409
export (Protocols BGP)	410
family (Protocols BGP)	411
graceful-restart (Protocols BGP)	415
group (Protocols BGP)	417
hold-down	421
hold-down-interval (BGP BFD Liveness Detection)	423
hold-time (Protocols BGP)	425
import	427
include-mp-next-hop	429
initiation-message	430
keep	431
key-chain (BGP BFD Authentication)	433
local-address (Protocols BGP)	435
local-address (Protocols BMP)	437
local-as	438
local-port	441
local-preference	442
log-updown	443
loops (BGP Address Family)	444
loose-check (BGP BFD Authentication)	446
maximum-ecmp	447
metric-out	448
minimum-interval (BFD Liveness Detection)	450
minimum-interval (transmit-interval)	452
minimum-receive-interval (BFD Liveness Detection)	454
monitor (Protocols BMP)	455
mtu-discovery	456
multihop	458
multiplier (BFD Liveness Detection)	460
neighbor (Protocols BGP)	462
no-adaptation (BFD Liveness Detection)	465
no advertise-peer-as	466
no-aggregator-id	467
no-client-reflect	468
out-delay	469
outbound-route-filter	471
passive (Protocols BGP)	472
path-selection	473
peer-as (Protocols BGP)	475
post-policy	476
pre-policy	477
preference (Protocols BGP)	478
priority (Protocols BMP)	479

	remove-private .....	480
	restart-time (BGP Graceful Restart) .....	482
	route-monitoring .....	483
	session-mode .....	485
	stale-routes-time .....	486
	station .....	487
	station-address .....	488
	station-port .....	489
	statistics-timeout .....	490
	tcp-mss (Protocols BGP) .....	491
	threshold (detection-time) .....	492
	threshold (transmit-interval) .....	494
	traceoptions (Protocols BGP) .....	496
	traceoptions (Protocols BMP) .....	499
	transmit-interval (BFD Liveness Detection) .....	501
	version (BFD Liveness Detection) .....	503
<b>Chapter 12</b>	<b>Operational Commands .....</b>	<b>505</b>
	clear bgp damping .....	506
	clear bgp neighbor .....	507
	clear bgp table .....	510
	show bgp bmp .....	512
	show bgp group .....	514
	show bgp neighbor .....	521
	show bgp summary .....	538
	show policy damping .....	544
	show route damping .....	546
	show route detail .....	551



# List of Figures

<b>Part 1</b>	<b>Overview</b>	
<b>Chapter 1</b>	<b>BGP Overview</b>	<b>3</b>
	Figure 1: ASs, EBGp, and IBGP	5
<b>Part 2</b>	<b>Configuration</b>	
<b>Chapter 2</b>	<b>Basic BGP Configuration</b>	<b>13</b>
	Figure 2: BGP Peering Session	13
	Figure 3: Typical Network with BGP Peer Sessions	15
	Figure 4: Typical Network with BGP Peer Sessions	22
	Figure 5: Internal and External BGP	36
	Figure 6: Typical Network with IBGP Sessions	39
	Figure 7: Typical Network with IBGP Sessions	49
<b>Chapter 3</b>	<b>BGP Path Attribute Configuration</b>	<b>61</b>
	Figure 8: Typical Network with IBGP Sessions and Multiple Exit Points	62
	Figure 9: Default MED Example	75
	Figure 10: Typical Network with IBGP Sessions and Multiple Exit Points	78
	Figure 11: Typical Network with IBGP Sessions and Multiple Exit Points	90
	Figure 12: Topology for Delaying the MED Update	105
	Figure 13: Local AS Configuration	116
	Figure 14: Topology for Configuring the Local AS	119
	Figure 15: Topology for Configuring a Private Local AS	129
	Figure 16: Advertisement of Multiple Paths in BGP	136
<b>Chapter 4</b>	<b>BGP Policy Configuration</b>	<b>173</b>
	Figure 17: BGP Prefix-Based Outbound Route Filtering	182
	Figure 18: EBGp Multihop Peering	185
	Figure 19: Typical Network with EBGp Multihop Sessions	187
	Figure 20: BGP Preference Value Topology	198
	Figure 21: Topology for Ignoring the AS-Path Length	207
	Figure 22: Topology for Removing a Private AS from the Advertised AS Path	214
<b>Chapter 5</b>	<b>BGP BFD Configuration</b>	<b>221</b>
	Figure 23: Typical Network with IBGP Sessions	223
<b>Chapter 6</b>	<b>BGP Load Balancing Configuration</b>	<b>237</b>
	Figure 24: BGP Load Balancing	239
	Figure 25: Topology for Accepting a Remote Next Hop	244
	Figure 26: Advertisement of Multiple Paths in BGP	257
<b>Chapter 7</b>	<b>IBGP Scaling Configuration</b>	<b>285</b>

	Figure 27: Simple Route Reflector Topology (One Cluster) . . . . .	286
	Figure 28: Basic Route Reflection (Multiple Clusters) . . . . .	287
	Figure 29: Hierarchical Route Reflection (Clusters of Clusters) . . . . .	288
	Figure 30: IBGP Network Using a Route Reflector . . . . .	289
	Figure 31: BGP Confederations . . . . .	304
	Figure 32: Typical Network Using BGP Confederations . . . . .	305
<b>Chapter 8</b>	<b>BGP Security Configuration . . . . .</b>	<b>311</b>
	Figure 33: Authentication for BGP . . . . .	314
	Figure 34: Typical Network with BGP Peer Sessions . . . . .	319
	Figure 35: TCP Maximum Segment Size for BGP . . . . .	327
<b>Chapter 9</b>	<b>BGP Flap Configuration . . . . .</b>	<b>333</b>
	Figure 36: Topology for the EBGp Case . . . . .	336
	Figure 37: Topology for the RR Case . . . . .	336
	Figure 38: BGP Flap Damping Topology . . . . .	342
	Figure 39: MBGP MVPN with BGP Route Flap Damping . . . . .	350

# List of Tables

	<b>About the Documentation</b> . . . . .	<b>xiii</b>
	Table 1: Notice Icons . . . . .	xv
	Table 2: Text and Syntax Conventions . . . . .	xv
<b>Part 2</b>	<b>Configuration</b>	
<b>Chapter 3</b>	<b>BGP Path Attribute Configuration</b> . . . . .	<b>61</b>
	Table 3: MED Options for Routing Table Path Selection . . . . .	76
<b>Chapter 4</b>	<b>BGP Policy Configuration</b> . . . . .	<b>173</b>
	Table 4: Default Route Preference Values . . . . .	195
<b>Chapter 9</b>	<b>BGP Flap Configuration</b> . . . . .	<b>333</b>
	Table 5: Damping Parameters . . . . .	341
<b>Part 4</b>	<b>Configuration Statements and Operational Commands</b>	
<b>Chapter 12</b>	<b>Operational Commands</b> . . . . .	<b>505</b>
	Table 6: show bgp bmp Output Fields . . . . .	512
	Table 7: show bgp group Output Fields . . . . .	515
	Table 8: show bgp neighbor Output Fields . . . . .	522
	Table 9: show bgp summary Output Fields . . . . .	539
	Table 10: show policy damping Output Fields . . . . .	545
	Table 11: show route damping Output Fields . . . . .	547
	Table 12: show route detail Output Fields . . . . .	551
	Table 13: Next-hop Types Output Field Values . . . . .	557
	Table 14: State Output Field Values . . . . .	559
	Table 15: Communities Output Field Values . . . . .	561



# About the Documentation

- Documentation and Release Notes on page xiii
- Supported Platforms on page xiii
- Using the Examples in This Manual on page xiii
- Documentation Conventions on page xv
- Documentation Feedback on page xvii
- Requesting Technical Support on page xvii

## Documentation and Release Notes

---

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at <http://www.juniper.net/techpubs/>.

If the information in the latest release notes differs from the information in the documentation, follow the product Release Notes.

Juniper Networks Books publishes books by Juniper Networks engineers and subject matter experts. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration. The current list can be viewed at <http://www.juniper.net/books>.

## Supported Platforms

---

For the features described in this document, the following platforms are supported:

- EX Series

## Using the Examples in This Manual

---

If you want to use the examples in this manual, you can use the **load merge** or the **load merge relative** command. These commands cause the software to merge the incoming configuration into the current candidate configuration. The example does not become active until you commit the candidate configuration.

If the example configuration contains the top level of the hierarchy (or multiple hierarchies), the example is a *full example*. In this case, use the **load merge** command.

If the example configuration does not start at the top level of the hierarchy, the example is a *snippet*. In this case, use the **load merge relative** command. These procedures are described in the following sections.

## Merging a Full Example

To merge a full example, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration example into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following configuration to a file and name the file **ex-script.conf**. Copy the **ex-script.conf** file to the **/var/tmp** directory on your routing platform.

```
system {
  scripts {
    commit {
      file ex-script.xml;
    }
  }
}
interfaces {
  fxp0 {
    disable;
    unit 0 {
      family inet {
        address 10.0.0.1/24;
      }
    }
  }
}
```

2. Merge the contents of the file into your routing platform configuration by issuing the **load merge** configuration mode command:

```
[edit]
user@host# load merge /var/tmp/ex-script.conf
load complete
```

## Merging a Snippet

To merge a snippet, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration snippet into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following snippet to a file and name the file **ex-script-snippet.conf**. Copy the **ex-script-snippet.conf** file to the **/var/tmp** directory on your routing platform.

```
commit {
  file ex-script-snippet.xml; }
```

2. Move to the hierarchy level that is relevant for this snippet by issuing the following configuration mode command:

```
[edit]
user@host# edit system scripts
[edit system scripts]
```

3. Merge the contents of the file into your routing platform configuration by issuing the **load merge relative** configuration mode command:

```
[edit system scripts]
user@host# load merge relative /var/tmp/ex-script-snippet.conf
load complete
```

For more information about the **load** command, see [CLI Explorer](#).

## Documentation Conventions

Table 1 on page xv defines notice icons used in this guide.

Table 1: Notice Icons

Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.
	Tip	Indicates helpful information.
	Best practice	Alerts you to a recommended use or implementation.

Table 2 on page xv defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
<b>Bold text like this</b>	Represents text that you type.	To enter configuration mode, type the <b>configure</b> command:  user@host> <b>configure</b>

Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
Fixed-width text like this	Represents output that appears on the terminal screen.	<code>user@host&gt; show chassis alarms</code> <code>No alarms currently active</code>
<i>Italic text like this</i>	<ul style="list-style-type: none"><li>Introduces or emphasizes important new terms.</li><li>Identifies guide names.</li><li>Identifies RFC and Internet draft titles.</li></ul>	<ul style="list-style-type: none"><li>A policy <i>term</i> is a named structure that defines match conditions and actions.</li><li><i>Junos OS CLI User Guide</i></li><li>RFC 1997, <i>BGP Communities Attribute</i></li></ul>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name:  [edit] root@# <b>set system domain-name</b> <i>domain-name</i>
Text like this	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none"><li>To configure a stub area, include the <b>stub</b> statement at the [edit protocols ospf area area-id] hierarchy level.</li><li>The console port is labeled <b>CONSOLE</b>.</li></ul>
< > (angle brackets)	Encloses optional keywords or variables.	<b>stub &lt;default-metric <i>metric</i>&gt;;</b>
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	<b>broadcast   multicast</b>  <b>(<i>string1</i>   <i>string2</i>   <i>string3</i>)</b>
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	<b>rsvp { # Required for dynamic MPLS only</b>
[ ] (square brackets)	Encloses a variable for which you can substitute one or more values.	<b>community name members [</b> <i>community-ids</i> <b>]</b>
Indentation and braces ( { } )	Identifies a level in the configuration hierarchy.	[edit] routing-options { static { route default { nexthop <i>address</i> ; retain; } } }
;(semicolon)	Identifies a leaf statement at a configuration hierarchy level.	}
GUI Conventions		
Bold text like this	Represents graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none"><li>In the Logical Interfaces box, select <b>All Interfaces</b>.</li><li>To cancel the configuration, click <b>Cancel</b>.</li></ul>



Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
> (bold right angle bracket)	Separates levels in a hierarchy of menu selections.	In the configuration editor hierarchy, select <b>Protocols&gt;Ospf</b> .

## Documentation Feedback

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation. You can provide feedback by using either of the following methods:

- Online feedback rating system—On any page of the Juniper Networks TechLibrary site at <http://www.juniper.net/techpubs/index.html>, simply click the stars to rate the content, and use the pop-up form to provide us with information about your experience. Alternately, you can use the online feedback form at <http://www.juniper.net/techpubs/feedback/>.
- E-mail—Send your comments to [techpubs-comments@juniper.net](mailto:techpubs-comments@juniper.net). Include the document or topic name, URL or page number, and software version (if applicable).

## Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or Partner Support Service support contract, or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <http://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

## Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Search for known bugs: <http://www2.juniper.net/kb/>
- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>

- Download the latest versions of software and review release notes:  
<http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications:  
<http://kb.juniper.net/InfoCenter/>
- Join and participate in the Juniper Networks Community Forum:  
<http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://tools.juniper.net/SerialNumberEntitlementSearch/>

## Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <http://www.juniper.net/support/requesting-support.html>.

## PART 1

# Overview

- [BGP Overview on page 3](#)



## CHAPTER 1

# BGP Overview

- [Understanding BGP on page 4](#)
- [BGP Routes Overview on page 6](#)
- [BGP Messages Overview on page 7](#)
- [Understanding the Advertisement of Multiple Paths to a Single Destination in BGP on page 9](#)

## Understanding BGP

---

BGP is an exterior gateway protocol (EGP) that is used to exchange routing information among routers in different autonomous systems (ASs). BGP routing information includes the complete route to each destination. BGP uses the routing information to maintain a database of network reachability information, which it exchanges with other BGP systems. BGP uses the network reachability information to construct a graph of AS connectivity, which enables BGP to remove routing loops and enforce policy decisions at the AS level.

Multiprotocol BGP (MBGP) extensions enable BGP to support IP version 6 (IPv6). MBGP defines the attributes `MP_REACH_NLRI` and `MP_UNREACH_NLRI`, which are used to carry IPv6 reachability information. Network layer reachability information (NLRI) update messages carry IPv6 address prefixes of feasible routes.

BGP allows for policy-based routing. You can use routing policies to choose among multiple paths to a destination and to control the redistribution of routing information.

BGP uses TCP as its transport protocol, using port 179 for establishing connections. Running over a reliable transport protocol eliminates the need for BGP to implement update fragmentation, retransmission, acknowledgment, and sequencing.

The Junos OS routing protocol software supports BGP version 4. This version of BGP adds support for Classless Interdomain Routing (CIDR), which eliminates the concept of network classes. Instead of assuming which bits of an address represent the network by looking at the first octet, CIDR allows you to explicitly specify the number of bits in the network address, thus providing a means to decrease the size of the routing tables. BGP version 4 also supports aggregation of routes, including the aggregation of AS paths.

This section discusses the following topics:

- [Autonomous Systems on page 4](#)
- [AS Paths and Attributes on page 4](#)
- [External and Internal BGP on page 5](#)
- [Multiple Instances of BGP on page 5](#)

### Autonomous Systems

An *autonomous system* (AS) is a set of routers that are under a single technical administration and normally use a single interior gateway protocol and a common set of metrics to propagate routing information within the set of routers. To other ASs, an AS appears to have a single, coherent interior routing plan and presents a consistent picture of what destinations are reachable through it.

### AS Paths and Attributes

The routing information that BGP systems exchange includes the complete route to each destination, as well as additional information about the route. The route to each destination is called the *AS path*, and the additional route information is included in *path attributes*. BGP uses the AS path and the path attributes to completely determine the network topology. Once BGP understands the topology, it can detect and eliminate


routing loops and select among groups of routes to enforce administrative preferences and routing policy decisions.

## External and Internal BGP

BGP supports two types of exchanges of routing information: exchanges among different ASs and exchanges within a single AS. When used among ASs, BGP is called *external BGP* (EBGP) and BGP sessions perform *inter-AS routing*. When used within an AS, BGP is called *internal BGP* (IBGP) and BGP sessions perform *intra-AS routing*.

Figure 1 on page 5 illustrates ASs, IBGP, and EBGP.

Figure 1: ASs, EBGP, and IBGP



A BGP system shares network reachability information with adjacent BGP systems, which are referred to as *neighbors* or *peers*.

BGP systems are arranged into *groups*. In an IBGP group, all peers in the group—called *internal peers*—are in the same AS. Internal peers can be anywhere in the local AS and do not have to be directly connected to one another. Internal groups use routes from an IGP to resolve forwarding addresses. They also propagate external routes among all other internal routers running IBGP, computing the next hop by taking the BGP next hop received with the route and resolving it using information from one of the interior gateway protocols.

In an EBGP group, the peers in the group—called *external peers*—are in different ASs and normally share a subnet. In an external group, the next hop is computed with respect to the interface that is shared between the external peer and the local router.

## Multiple Instances of BGP

You can configure multiple instances of BGP at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols]

Multiple instances of BGP are primarily used for Layer 3 VPN support.

IGP peers and external BGP (EBGP) peers (both nonmultihop and multihop) are all supported for routing instances. BGP peering is established over one of the interfaces configured under the **routing-instances** hierarchy.



**NOTE:** When a BGP neighbor sends BGP messages to the local routing device, the incoming interface on which these messages are received must be configured in the same routing instance that the BGP neighbor configuration exists in. This is true for neighbors that are a single hop away or multiple hops away.

Routes learned from the BGP peer are added to the **instance-name.inet.0** table by default. You can configure import and export policies to control the flow of information into and out of the instance routing table.

For Layer 3 VPN support, configure BGP on the provider edge (PE) router to receive routes from the customer edge (CE) router and to send the instances' routes to the CE router if necessary. You can use multiple instances of BGP to maintain separate per-site forwarding tables for keeping VPN traffic separate on the PE router.

You can configure import and export policies that allow the service provider to control and rate-limit traffic to and from the customer.

You can configure an EBGP multihop session for a VRF routing instance. Also, you can set up the EBGP peer between the PE and CE routers by using the loopback address of the CE router instead of the interface addresses.

- Related Documentation**
- [BGP Routes Overview on page 6](#)
  - [BGP Messages Overview on page 7](#)

---

## BGP Routes Overview

A BGP route is a destination, described as an IP address prefix, and information that describes the path to the destination.

The following information describes the path:

- AS path, which is a list of numbers of the ASs that a route passes through to reach the local router. The first number in the path is that of the last AS in the path—the AS closest to the local router. The last number in the path is the AS farthest from the local router, which is generally the origin of the path.
- Path attributes, which contain additional information about the AS path that is used in routing policy.

BGP peers advertise routes to each other in update messages.

BGP stores its routes in the Junos OS routing table (**inet.0**). The routing table stores the following information about BGP routes:



- Routing information learned from update messages received from peers
- Local routing information that BGP applies to routes because of local policies
- Information that BGP advertises to BGP peers in update messages

For each prefix in the routing table, the routing protocol process selects a single best path, called the active path. Unless you configure BGP to advertise multiple paths to the same destination, BGP advertises only the active path.

The BGP router that first advertises a route assigns it one of the following values to identify its origin. During route selection, the lowest origin value is preferred.

- 0—The router originally learned the route through an IGP (OSPF, IS-IS, or a static route).
- 1—The router originally learned the route through an EGP (most likely BGP).
- 2—The route's origin is unknown.

#### Related Documentation

- [Understanding BGP Path Selection on page 202](#)
- [Example: Advertising Multiple Paths in BGP on page 255](#)

## BGP Messages Overview

All BGP messages have the same fixed-size header, which contains a marker field that is used for both synchronization and authentication, a length field that indicates the length of the packet, and a type field that indicates the message type (for example, open, update, notification, keepalive, and so on).

This section discusses the following topics:

- [Open Messages on page 7](#)
- [Update Messages on page 8](#)
- [Keepalive Messages on page 8](#)
- [Notification Messages on page 8](#)
- [Route-Refresh Messages on page 8](#)

### Open Messages

After a TCP connection is established between two BGP systems, they exchange BGP open messages to create a BGP connection between them. Once the connection is established, the two systems can exchange BGP messages and data traffic.

Open messages consist of the BGP header plus the following fields:

- Version—The current BGP version number is 4.
- Local AS number—You configure this by including the **autonomous-system** statement at the **[edit routing-options]** or **[edit logical-systems *logical-system-name* routing-options]** hierarchy level.

- Hold time—Proposed hold-time value. You configure the local hold time with the BGP **hold-time** statement.
- BGP identifier—IP address of the BGP system. This address is determined when the system starts and is the same for every local interface and every BGP peer. You can configure the BGP identifier by including the **router-id** statement at the **[edit routing-options]** or **[edit logical-systems *logical-system-name* routing-options]** hierarchy level. By default, BGP uses the IP address of the first interface it finds in the router.
- Parameter field length and the parameter itself—These are optional fields.

## Update Messages

BGP systems send update messages to exchange network reachability information. BGP systems use this information to construct a graph that describes the relationships among all known ASs.

Update messages consist of the BGP header plus the following optional fields:

- Unfeasible routes length—Length of the withdrawn routes field
- Withdrawn routes—IP address prefixes for the routes being withdrawn from service because they are no longer deemed reachable
- Total path attribute length—Length of the path attributes field; it lists the path attributes for a feasible route to a destination
- Path attributes—Properties of the routes, including the path origin, the multiple exit discriminator (MED), the originating system's preference for the route, and information about aggregation, communities, confederations, and route reflection
- Network layer reachability information (NLRI)—IP address prefixes of feasible routes being advertised in the update message

## Keepalive Messages

BGP systems exchange keepalive messages to determine whether a link or host has failed or is no longer available. Keepalive messages are exchanged often enough so that the hold timer does not expire. These messages consist only of the BGP header.

## Notification Messages

BGP systems send notification messages when an error condition is detected. After the message is sent, the BGP session and the TCP connection between the BGP systems are closed. Notification messages consist of the BGP header plus the error code and subcode, and data that describes the error.

## Route-Refresh Messages

BGP systems send route-refresh messages to a peer only if they have received the route refresh capability advertisement from the peer. A BGP system must advertise the route refresh capability to its peers using BGP capabilities advertisement if it wants to receive route-refresh messages. This optional message is sent to request dynamic, inbound, BGP route updates from BGP peers or to send outbound route updates to a BGP peer.

Route-refresh messages consist of the following fields:

- AFI—Address Family Identifier (16-bit).
- Res—Reserved (8-bit) field, which must be set to 0 by the sender and ignored by the receiver.
- SAFI—Subsequent Address Family Identifier (8-bit).

If a peer without the route-refresh capability receives a route-refresh request message from a remote peer, the receiver ignores the message.

**Related  
Documentation**

- [Understanding BGP on page 4](#)
- [BGP Routes Overview on page 6](#)

## Understanding the Advertisement of Multiple Paths to a Single Destination in BGP

BGP peers advertise routes to each other in update messages. BGP stores its routes in the Junos OS routing table (**inet.0**). For each prefix in the routing table, the routing protocol process selects a single best path, called the active path. Unless you configure BGP to advertise multiple paths to the same destination, BGP advertises only the active path.

Instead of advertising only the active path to a destination, you can configure BGP to advertise multiple paths to the destination. Within an autonomous system (AS), the availability of multiple exit points to reach a destination provides the following benefits:

- Fault tolerance—Path diversity leads to reduction in restoration time after failure. For instance, a border after receiving multiple paths to the same destination can precompute a backup path and have it ready so that when the primary path becomes invalid, the border routing device can use the backup to quickly restore connectivity. Without a backup path, the restoration time depends on BGP reconvergence, which includes withdraw and advertisement messages in the network before a new best path can be learned.
- Load balancing—The availability of multiple paths to reach the same destination enables load balancing of traffic, if the routing within the AS meets certain constraints.
- Maintenance—The availability of alternate exit points allows for graceful maintenance operation of routers.

The following limitations apply to advertising multiple routes in BGP:

- Address families supported:
  - IPv4 unicast (**family inet unicast**)
  - IPv6 unicast (**family inet6 unicast**)
  - IPv4 labeled unicast (**family inet labeled-unicast**)
  - IPv6 labeled unicast (**family inet6 labeled-unicast**)
- Internal BGP (IBGP) peers only. No support on external BGP (EBGP) peers.

- Master instance only. No support for routing instances.
- Graceful restart and nonstop active routing (NSR) are supported.
- No BGP Monitoring Protocol (BMP) support.
- No support for EBGP sessions between confederations.
- Prefix policies enable you to filter routes on a router that is configured to advertise multiple paths to a destination. Prefix policies can only match prefixes. They cannot match route attributes, and they cannot change the attributes of routes.

**Related  
Documentation**

- [Understanding BGP Path Selection on page 202](#)
- [Example: Advertising Multiple Paths in BGP on page 255](#)

## PART 2

# Configuration

- [Basic BGP Configuration on page 13](#)
- [BGP Path Attribute Configuration on page 61](#)
- [BGP Policy Configuration on page 173](#)
- [BGP BFD Configuration on page 221](#)
- [BGP Load Balancing Configuration on page 237](#)
- [IBGP Scaling Configuration on page 285](#)
- [BGP Security Configuration on page 311](#)
- [BGP Flap Configuration on page 333](#)



## CHAPTER 2

# Basic BGP Configuration

- [Examples: Configuring External BGP Peering on page 13](#)
- [Examples: Configuring Internal BGP Peering on page 36](#)
- [Configuring BGP Monitoring Protocol Version 3 on page 59](#)


### Examples: Configuring External BGP Peering

- [Understanding External BGP Peering Sessions on page 13](#)
- [Example: Configuring External BGP Point-to-Point Peer Sessions on page 14](#)
- [Example: Configuring External BGP on Logical Systems with IPv6 Interfaces on page 21](#)

### Understanding External BGP Peering Sessions

To establish point-to-point connections between peer autonomous systems (ASs), you configure a BGP session on each interface of a point-to-point link. Generally, such sessions are made at network exit points with neighboring hosts outside the AS. [Figure 2 on page 13](#) shows an example of a BGP peering session.

Figure 2: BGP Peering Session



In [Figure 2 on page 13](#), Router A is a gateway router for AS 3, and Router B is a gateway router for AS 10. For traffic internal to either AS, an interior gateway protocol (IGP) is used (OSPF, for instance). To route traffic between peer ASs, a BGP session is used.

You arrange BGP routing devices into groups of peers. Different peer groups can have different group types, AS numbers, and route reflector cluster identifiers.

To define a BGP group that recognizes only the specified BGP systems as peers, statically configure all the system's peers by including one or more **neighbor** statements. The peer neighbor's address can be either an IPv6 or IPv4 address.



**NOTE:** On SRX Series devices, the default mode for processing traffic is flow mode. To configure an SRX Series device as a border router, you must change the mode from flow-based processing to packet-based processing. Use the **set security forwarding-options family mpls mode packet-based** statement to configure the SRX device to packet mode. You must reboot the device for the configuration to take effect.

As the number of external BGP (EBGP) groups increases, the ability to support a large number of BGP sessions might become a scaling issue. The preferred way to configure a large number of BGP neighbors is to configure a few groups consisting of multiple neighbors per group. Supporting fewer EBGP groups generally scales better than supporting a large number of EBGP groups. This becomes more evident in the case of hundreds of EBGP groups when compared with a few EBGP groups with multiple peers in each group.

After the BGP peers are established, non-BGP routes are not automatically advertised by the BGP peers. At each BGP-enabled device, policy configuration is required to export the local, static, or IGP-learned routes into the BGP RIB and then advertise them as BGP routes to the other peers. BGP's advertisement policy, by default, does not advertise any non-BGP routes (such as local routes) to peers.

## Example: Configuring External BGP Point-to-Point Peer Sessions

This example shows how to configure BGP point-to-point peer sessions.

- [Requirements on page 14](#)
- [Overview on page 14](#)
- [Configuration on page 15](#)
- [Verification on page 17](#)

---

### Requirements

Before you begin, if the default BGP policy is not adequate for your network, configure routing policies to filter incoming BGP routes and to advertise BGP routes.


---

### Overview

[Figure 3 on page 15](#) shows a network with BGP peer sessions. In the sample network, Device E in AS 17 has BGP peer sessions to a group of peers called **external-peers**. Peers A, B, and C reside in AS 22 and have IP addresses 10.10.10.2, 10.10.10.6, and 10.10.10.10. Peer D resides in AS 79, at IP address 10.21.7.2. This example shows the configuration on Device E.



Figure 3: Typical Network with BGP Peer Sessions



### Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set interfaces ge-1/2/0 unit 0 description to-A
set interfaces ge-1/2/0 unit 0 family inet address 10.10.10.1/30
set interfaces ge-0/0/1 unit 5 description to-B
set interfaces ge-0/0/1 unit 5 family inet address 10.10.10.5/30
set interfaces ge-0/1/0 unit 9 description to-C
set interfaces ge-0/1/0 unit 9 family inet address 10.10.10.9/30
set interfaces ge-1/2/1 unit 21 description to-D
set interfaces ge-1/2/1 unit 21 family inet address 10.21.7.1/30
set protocols bgp group external-peers type external
set protocols bgp group external-peers peer-as 22
set protocols bgp group external-peers neighbor 10.10.10.2
set protocols bgp group external-peers neighbor 10.10.10.6
set protocols bgp group external-peers neighbor 10.10.10.10
set protocols bgp group external-peers neighbor 10.21.7.2 peer-as 79
set routing-options autonomous-system 17
```

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the BGP peer sessions:

1. Configure the interfaces to Peers A, B, C, and D.

[edit interfaces]

```
user@E# set ge-1/2/0 unit 0 description to-A
user@E# set ge-1/2/0 unit 0 family inet address 10.10.10.1/30
user@E# set ge-0/0/1 unit 5 description to-B
user@E# set ge-0/0/1 unit 5 family inet address 10.10.10.5/30
user@E# set ge-0/1/0 unit 9 description to-C
user@E# set ge-0/1/0 unit 9 family inet address 10.10.10.9/30
user@E# set ge-1/2/1 unit 21 description to-D
user@E# set ge-1/2/1 unit 21 family inet address 10.21.7.1/30
```

2. Set the autonomous system (AS) number.

```
[edit routing-options]
user@E# set autonomous-system 17
```

3. Create the BGP group, and add the external neighbor addresses.

```
[edit protocols bgp group external-peers]
user@E# set neighbor 10.10.10.2
user@E# set neighbor 10.10.10.6
user@E# set neighbor 10.10.10.10
```

4. Specify the autonomous system (AS) number of the external AS.

```
[edit protocols bgp group external-peers]
user@E# set peer-as 22
```

5. Add Peer D, and set the AS number at the individual neighbor level.

The neighbor configuration overrides the group configuration. So, while **peer-as 22** is set for all the other neighbors in the group, **peer-as 79** is set for neighbor 10.21.7.2.

```
[edit protocols bgp group external-peers]
user@E# set neighbor 10.21.7.2 peer-as 79
```

6. Set the peer type to external BGP (EBGP).

```
[edit protocols bgp group external-peers]
user@E# set type external
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@E# show interfaces
ge-1/2/0 {
  unit 0 {
    description to-A;
    family inet {
      address 10.10.10.1/30;
    }
  }
}
ge-0/0/1 {
  unit 5 {
    description to-B;
    family inet {
      address 10.10.10.5/30;
    }
  }
}
```

```

    }
  }
  ge-0/1/0 {
    unit 9 {
      description to-C;
      family inet {
        address 10.10.10.9/30;
      }
    }
  }
  ge-1/2/1 {
    unit 21 {
      description to-D;
      family inet {
        address 10.21.7.1/30;
      }
    }
  }
}

[edit]
user@E# show protocols
bgp {
  group external-peers {
    type external;
    peer-as 22;
    neighbor 10.10.10.2;
    neighbor 10.10.10.6;
    neighbor 10.10.10.10;
    neighbor 10.21.7.2 {
      peer-as 79;
    }
  }
}

[edit]
user@E# show routing-options
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Verifying BGP Neighbors on page 17](#)
- [Verifying BGP Groups on page 20](#)
- [Verifying BGP Summary Information on page 20](#)

### Verifying BGP Neighbors

**Purpose** Verify that BGP is running on configured interfaces and that the BGP session is active for each neighbor address.

**Action** From operational mode, run the **show bgp neighbor** command.

```
user@E> show bgp neighbor
```

```

Peer: 10.10.10.2+179 AS 22      Local: 10.10.10.1+65406 AS 17
Type: External      State: Established      Flags: <Sync>
Last State: OpenConfirm      Last Event: RecvKeepAlive
Last Error: None
Options: <Preference PeerAS Refresh>
Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 10.10.10.2      Local ID: 10.10.10.1      Active Holdtime: 90
Keepalive Interval: 30      Peer index: 0
BFD: disabled, down
Local Interface: ge-1/2/0.0
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 22)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        0
  Accepted prefixes:        0
  Suppressed due to damping: 0
  Advertised prefixes:      0
Last traffic (seconds): Received 10   Sent 6   Checked 1
Input messages: Total 8522   Updates 1   Refreshes 0   Octets 161922
Output messages: Total 8433   Updates 0   Refreshes 0   Octets 160290
Output Queue[0]: 0

Peer: 10.10.10.6+54781 AS 22      Local: 10.10.10.5+179 AS 17
Type: External      State: Established      Flags: <Sync>
Last State: OpenConfirm      Last Event: RecvKeepAlive
Last Error: None
Options: <Preference PeerAS Refresh>
Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 10.10.10.6      Local ID: 10.10.10.1      Active Holdtime: 90
Keepalive Interval: 30      Peer index: 1
BFD: disabled, down
Local Interface: ge-0/0/1.5
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 22)
Peer does not support Addpath

```

```

Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        0
  Accepted prefixes:        0
  Suppressed due to damping: 0
  Advertised prefixes:      0
Last traffic (seconds): Received 12   Sent 6   Checked 33
Input messages:  Total 8527   Updates 1   Refreshes 0   Octets 162057
Output messages: Total 8430   Updates 0   Refreshes 0   Octets 160233
Output Queue[0]: 0

Peer: 10.10.10.10+55012 AS 22  Local: 10.10.10.9+179 AS 17
  Type: External  State: Established  Flags: <Sync>
  Last State: OpenConfirm  Last Event: RecvKeepAlive
  Last Error: None
  Options: <Preference PeerAS Refresh>
  Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 10.10.10.10      Local ID: 10.10.10.1      Active Holdtime: 90
  Keepalive Interval: 30    Peer index: 2
  BFD: disabled, down
  Local Interface: fe-0/1/0.9
  NLRI for restart configured on peer: inet-unicast
  NLRI advertised by peer: inet-unicast
  NLRI for this session: inet-unicast
  Peer supports Refresh capability (2)
  Restart time configured on the peer: 120
  Stale routes from peer are kept for: 300
  Restart time requested by this peer: 120
  NLRI that peer supports restart for: inet-unicast
  NLRI that restart is negotiated for: inet-unicast
  NLRI of received end-of-rib markers: inet-unicast
  NLRI of all end-of-rib markers sent: inet-unicast
  Peer supports 4 byte AS extension (peer-as 22)
  Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        0
  Accepted prefixes:        0
  Suppressed due to damping: 0
  Advertised prefixes:      0
Last traffic (seconds): Received 15   Sent 6   Checked 37
Input messages:  Total 8527   Updates 1   Refreshes 0   Octets 162057
Output messages: Total 8429   Updates 0   Refreshes 0   Octets 160214
Output Queue[0]: 0

Peer: 10.21.7.2+61867 AS 79  Local: 10.21.7.1+179 AS 17
  Type: External  State: Established  Flags: <ImportEval Sync>
  Last State: OpenConfirm  Last Event: RecvKeepAlive
  Last Error: None
  Options: <Preference PeerAS Refresh>
  Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 10.21.7.2      Local ID: 10.10.10.1      Active Holdtime: 90
  Keepalive Interval: 30    Peer index: 3
  BFD: disabled, down
  Local Interface: ge-1/2/1.21

```

```

NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 79)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        0
  Accepted prefixes:        0
  Suppressed due to damping: 0
  Advertised prefixes:      0
Last traffic (seconds): Received 28   Sent 24   Checked 47
Input messages: Total 8521   Updates 1     Refreshes 0     Octets 161943
Output messages: Total 8427   Updates 0     Refreshes 0     Octets 160176
Output Queue[0]: 0

```

### Verifying BGP Groups

**Purpose** Verify that the BGP groups are configured correctly.

**Action** From operational mode, run the **show bgp group** command.

```

user@E> show bgp group
Group Type: External                               Local AS: 17
Name: external-peers  Index: 0                     Flags: <>
Holdtime: 0
Total peers: 4      Established: 4
10.10.10.2+179
10.10.10.6+54781
10.10.10.10+55012
10.21.7.2+61867
inet.0: 0/0/0/0

Groups: 1  Peers: 4   External: 4   Internal: 0   Down peers: 0   Flaps: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State   Pending
inet.0          0         0         0           0        0    0         0

```

### Verifying BGP Summary Information

**Purpose** Verify that the BGP configuration is correct.

**Action** From operational mode, run the **show bgp summary** command.

```

user@E> show bgp summary
Groups: 1 Peers: 4 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State   Pending
inet.0          0         0         0           0        0    0         0
Peer      AS      InPkt   OutPkt   OutQ   Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.10.10.2      22      8559      8470        0        0 2d 16:12:56

```

0/0/0/0	0/0/0/0				
10.10.10.6	22	8566	8468	0	0 2d 16:12:12
0/0/0/0	0/0/0/0				
10.10.10.10	22	8565	8466	0	0 2d 16:11:31
0/0/0/0	0/0/0/0				
10.21.7.2	79	8560	8465	0	0 2d 16:10:58
0/0/0/0	0/0/0/0				

## Example: Configuring External BGP on Logical Systems with IPv6 Interfaces

This example shows how to configure external BGP (EBGP) point-to-point peer sessions on logical systems with IPv6 interfaces.

- [Requirements on page 21](#)
- [Overview on page 21](#)
- [Configuration on page 22](#)
- [Verification on page 31](#)

### Requirements

In this example, no special configuration beyond device initialization is required.

### Overview

Junos OS supports EBGP peer sessions by means of IPv6 addresses. An IPv6 peer session can be configured when an IPv6 address is specified in the **neighbor** statement. This example uses EUI-64 to generate IPv6 addresses that are automatically applied to the interfaces. An EUI-64 address is an IPv6 address that uses the IEEE EUI-64 format for the interface identifier portion of the address (the last 64 bits).



**NOTE:** Alternatively, you can configure EBGP sessions using manually assigned 128-bit IPv6 addresses.

If you use 128-bit link-local addresses for the interfaces, you must include the **local-interface** statement. This statement is valid only for 128-bit IPv6 link-local addresses and is mandatory for configuring an IPv6 EBGP link-local peer session.


Configuring EBGP peering using link-local addresses is only applicable for directly connected interfaces. There is no support for multihop peering.

After your interfaces are up, you can use the **show interfaces terse** command to view the EUI-64-generated IPv6 addresses on the interfaces. You must use these generated addresses in the BGP **neighbor** statements. This example demonstrates the full end-to-end procedure.

In this example, Frame Relay interface encapsulation is applied to the logical tunnel (**lt**) interfaces. This is a requirement because only Frame Relay encapsulation is supported when IPv6 addresses are configured on the **lt** interfaces.

Figure 4 on page 22 shows a network with BGP peer sessions. In the sample network, Router R1 has five logical systems configured. Device E in autonomous system (AS) 17 has BGP peer sessions to a group of peers called **external-peers**. Peers A, B, and C reside in AS 22. This example shows the step-by-step configuration on Logical System A and Logical System E.

Figure 4: Typical Network with BGP Peer Sessions



### Configuration

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the **[edit]** hierarchy level, and then enter **commit** from configuration mode.

#### Device A

```
set logical-systems A interfaces lt-0/1/0 unit 1 description to-E
set logical-systems A interfaces lt-0/1/0 unit 1 encapsulation frame-relay
set logical-systems A interfaces lt-0/1/0 unit 1 dlci 1
set logical-systems A interfaces lt-0/1/0 unit 1 peer-unit 25
set logical-systems A interfaces lt-0/1/0 unit 1 family inet6 address 2001:db8:0:1::/64
  eui-64
set logical-systems A interfaces lo0 unit 1 family inet6 address 2001:db8::1/128
set logical-systems A protocols bgp group external-peers type external
set logical-systems A protocols bgp group external-peers peer-as 17
```



```

set logical-systems A protocols bgp group external-peers neighbor
  2001:db8:0:1:2a0:a502:0:19da
set logical-systems A routing-options router-id 172.16.1.1
set logical-systems A routing-options autonomous-system 22

Device B
set logical-systems B interfaces lt-0/1/0 unit 6 description to-E
set logical-systems B interfaces lt-0/1/0 unit 6 encapsulation frame-relay
set logical-systems B interfaces lt-0/1/0 unit 6 dlci 6
set logical-systems B interfaces lt-0/1/0 unit 6 peer-unit 5
set logical-systems B interfaces lt-0/1/0 unit 6 family inet6 address 2001:db8:0:2::/64
  eui-64
set logical-systems B interfaces lo0 unit 2 family inet6 address 2001:db8::2/128
set logical-systems B protocols bgp group external-peers type external
set logical-systems B protocols bgp group external-peers peer-as 17
set logical-systems B protocols bgp group external-peers neighbor
  2001:db8:0:2:2a0:a502:0:5da
set logical-systems B routing-options router-id 172.16.2.2
set logical-systems B routing-options autonomous-system 22

Device C
set logical-systems C interfaces lt-0/1/0 unit 10 description to-E
set logical-systems C interfaces lt-0/1/0 unit 10 encapsulation frame-relay
set logical-systems C interfaces lt-0/1/0 unit 10 dlci 10
set logical-systems C interfaces lt-0/1/0 unit 10 peer-unit 9
set logical-systems C interfaces lt-0/1/0 unit 10 family inet6 address 2001:db8:0:3::/64
  eui-64
set logical-systems C interfaces lo0 unit 3 family inet6 address 2001:db8::3/128
set logical-systems C protocols bgp group external-peers type external
set logical-systems C protocols bgp group external-peers peer-as 17
set logical-systems C protocols bgp group external-peers neighbor
  2001:db8:0:3:2a0:a502:0:9da
set logical-systems C routing-options router-id 172.16.3.3
set logical-systems C routing-options autonomous-system 22

Device D
set logical-systems D interfaces lt-0/1/0 unit 7 description to-E
set logical-systems D interfaces lt-0/1/0 unit 7 encapsulation frame-relay
set logical-systems D interfaces lt-0/1/0 unit 7 dlci 7
set logical-systems D interfaces lt-0/1/0 unit 7 peer-unit 21
set logical-systems D interfaces lt-0/1/0 unit 7 family inet6 address 2001:db8:0:4::/64
  eui-64
set logical-systems D interfaces lo0 unit 4 family inet6 address 2001:db8::4/128
set logical-systems D protocols bgp group external-peers type external
set logical-systems D protocols bgp group external-peers peer-as 17
set logical-systems D protocols bgp group external-peers neighbor
  2001:db8:0:4:2a0:a502:0:15da
set logical-systems D routing-options router-id 172.16.4.4
set logical-systems D routing-options autonomous-system 79

Device E
set logical-systems E interfaces lt-0/1/0 unit 5 description to-B
set logical-systems E interfaces lt-0/1/0 unit 5 encapsulation frame-relay
set logical-systems E interfaces lt-0/1/0 unit 5 dlci 6
set logical-systems E interfaces lt-0/1/0 unit 5 peer-unit 6
set logical-systems E interfaces lt-0/1/0 unit 5 family inet6 address 2001:db8:0:2::/64
  eui-64
set logical-systems E interfaces lt-0/1/0 unit 9 description to-C
set logical-systems E interfaces lt-0/1/0 unit 9 encapsulation frame-relay

```

```

set logical-systems E interfaces lt-0/1/0 unit 9 dlci 10
set logical-systems E interfaces lt-0/1/0 unit 9 peer-unit 10
set logical-systems E interfaces lt-0/1/0 unit 9 family inet6 address 2001:db8:0:3::/64
  eui-64
set logical-systems E interfaces lt-0/1/0 unit 21 description to-D
set logical-systems E interfaces lt-0/1/0 unit 21 encapsulation frame-relay
set logical-systems E interfaces lt-0/1/0 unit 21 dlci 7
set logical-systems E interfaces lt-0/1/0 unit 21 peer-unit 7
set logical-systems E interfaces lt-0/1/0 unit 21 family inet6 address 2001:db8:0:4::/64
  eui-64
set logical-systems E interfaces lt-0/1/0 unit 25 description to-A
set logical-systems E interfaces lt-0/1/0 unit 25 encapsulation frame-relay
set logical-systems E interfaces lt-0/1/0 unit 25 dlci 1
set logical-systems E interfaces lt-0/1/0 unit 25 peer-unit 1
set logical-systems E interfaces lt-0/1/0 unit 25 family inet6 address 2001:db8:0:1::/64
  eui-64
set logical-systems E interfaces lo0 unit 5 family inet6 address 2001:db8::5/128
set logical-systems E protocols bgp group external-peers type external
set logical-systems E protocols bgp group external-peers peer-as 22
set logical-systems E protocols bgp group external-peers neighbor
  2001:db8:0:1:2a0:a502:0:1da
set logical-systems E protocols bgp group external-peers neighbor
  2001:db8:0:2:2a0:a502:0:6da
set logical-systems E protocols bgp group external-peers neighbor
  2001:db8:0:3:2a0:a502:0:ada
set logical-systems E protocols bgp group external-peers neighbor
  2001:db8:0:4:2a0:a502:0:7da peer-as 79
set logical-systems E routing-options router-id 172.16.5.5
set logical-systems E routing-options autonomous-system 17

```

#### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the BGP peer sessions:

1. Run the **show interfaces terse** command to verify that the physical router has a logical tunnel (lt) interface.
2. On Logical System A, configure the interface encapsulation, peer-unit number, and DLCI to reach Logical System E.

```

user@R1> show interfaces terse
Interface           Admin Link Proto  Local          Remote
...
lt-0/1/0             up    up
...

```

```

user@R1> set cli logical-system A
Logical system: A
[edit]
user@R1:A> edit
Entering configuration mode
[edit]
user@R1:A# edit interfaces
[edit interfaces]
user@R1:A# set lt-0/1/0 unit 1 encapsulation frame-relay

```

```
user@R1:A# set lt-0/1/0 unit 1 dlci 1
user@R1:A# set lt-0/1/0 unit 1 peer-unit 25
```

3. On Logical System A, configure the network address for the link to Peer E, and configure a loopback interface.

```
[edit interfaces]
user@R1:A# set lt-0/1/0 unit 1 description to-E
user@R1:A# set lt-0/1/0 unit 1 family inet6 address 2001:db8:0:1::/64 eui-64
user@R1:A# set lo0 unit 1 family inet6 address 2001:db8::1/128
```

4. On Logical System E, configure the interface encapsulation, peer-unit number, and DLCI to reach Logical System A.

```
user@R1> set cli logical-system E
Logical system: E
[edit]
user@R1:E> edit
Entering configuration mode
[edit]
user@R1:E# edit interfaces
[edit interfaces]
user@R1:E# set lt-0/1/0 unit 25 encapsulation frame-relay
user@R1:E# set lt-0/1/0 unit 25 dlci 1
user@R1:E# set lt-0/1/0 unit 25 peer-unit 1
```

5. On Logical System E, configure the network address for the link to Peer A, and configure a loopback interface.

```
[edit interfaces]
user@R1:E# set lt-0/1/0 unit 25 description to-A
user@R1:E# set lt-0/1/0 unit 25 family inet6 address 2001:db8:0:1::/64 eui-64
user@R1:E# set lo0 unit 5 family inet6 address 2001:db8::5/128
```

6. Run the **show interfaces terse** command to see the IPv6 addresses that are generated by EUI-64.

The 2001 addresses are used in this example in the BGP **neighbor** statements.



**NOTE:** The fe80 addresses are link-local addresses and are not used in this example.

```
user@R1:A> show interfaces terse
Interface          Admin Link Proto  Local                  Remote
Logical system: A

betsy@tp8:A> show interfaces terse
Interface          Admin Link Proto  Local                  Remote
lt-0/1/0
lt-0/1/0.1          up    up    inet6    2001:db8:0:1:2a0:a502:0:1da/64
                                     fe80::2a0:a502:0:1da/64
lo0
lo0.1               up    up    inet6    2001:db8::1
                                     fe80::2a0:a50f:fc56:1da

user@R1:E> show interfaces terse
```

Interface	Admin	Link	Proto	Local	Remote
1t-0/1/0					
1t-0/1/0.25	up	up	inet6	2001:db8:0:1:2a0:a502:0:19da/64	
				fe80::2a0:a502:0:19da/64	
1o0					
1o0.5	up	up	inet6	2001:db8::5	
				fe80::2a0:a50f:fc56:1da	

- Repeat the interface configuration on the other logical systems.

### Configuring the External BGP Sessions

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the BGP peer sessions:

- On Logical System A, create the BGP group, and add the external neighbor address.  

```
[edit protocols bgp group external-peers]
user@R1:A# set neighbor 2001:db8:0:1:2a0:a502:0:19da
```
- On Logical System E, create the BGP group, and add the external neighbor address.  

```
[edit protocols bgp group external-peers]
user@R1:E# set neighbor 2001:db8:0:1:2a0:a502:0:1da
```
- On Logical System A, specify the autonomous system (AS) number of the external AS.  

```
[edit protocols bgp group external-peers]
user@R1:A# set peer-as 17
```
- On Logical System E, specify the autonomous system (AS) number of the external AS.  

```
[edit protocols bgp group external-peers]
user@R1:E# set peer-as 22
```
- On Logical System A, set the peer type to EBGp.  

```
[edit protocols bgp group external-peers]
user@R1:A# set type external
```
- On Logical System E, set the peer type to EBGp.  

```
[edit protocols bgp group external-peers]
user@R1:E# set type external
```
- On Logical System A, set the autonomous system (AS) number and router ID.  

```
[edit routing-options]
user@R1:A# set router-id 172.16.1.1
user@R1:A# set autonomous-system 22
```
- On Logical System E, set the AS number and router ID.  

```
[edit routing-options]
user@R1:E# set router-id 172.16.5.5
```

```
user@R1:E# set autonomous-system 17
```

9. Repeat these steps for Peers A, B, C, and D.

**Results** From configuration mode, confirm your configuration by entering the **show logical-systems** command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@R1# show logical-systems
A {
  interfaces {
    lt-0/1/0 {
      unit 1 {
        description to-E;
        encapsulation frame-relay;
        dlci 1;
        peer-unit 25;
        family inet6 {
          address 2001:db8:0:1::/64 {
            eui-64;
          }
        }
      }
    }
  }
  lo0 {
    unit 1 {
      family inet6 {
        address 2001:db8::1/128;
      }
    }
  }
  protocols {
    bgp {
      group external-peers {
        type external;
        peer-as 17;
        neighbor 2001:db8:0:1:2a0:a502:0:19da;
      }
    }
    routing-options {
      router-id 172.16.1.1;
      autonomous-system 22;
    }
  }
}
B {
  interfaces {
    lt-0/1/0 {
      unit 6 {
        description to-E;
        encapsulation frame-relay;
        dlci 6;
        peer-unit 5;
        family inet6 {
```

```
        address 2001:db8:0:2::/64 {
            eui-64;
        }
    }
}
lo0 {
    unit 2 {
        family inet6 {
            address 2001:db8::2/128;
        }
    }
}
protocols {
    bgp {
        group external-peers {
            type external;
            peer-as 17;
            neighbor 2001:db8:0:2:2a0:a502:0:5da;
        }
    }
    routing-options {
        router-id 172.16.2.2;
        autonomous-system 22;
    }
}
C {
    interfaces {
        lt-0/1/0 {
            unit 10 {
                description to-E;
                encapsulation frame-relay;
                dlci 10;
                peer-unit 9;
                family inet6 {
                    address 2001:db8:0:3::/64 {
                        eui-64;
                    }
                }
            }
        }
    }
    lo0 {
        unit 3 {
            family inet6 {
                address 2001:db8::3/128;
            }
        }
    }
}
protocols {
    bgp {
        group external-peers {
            type external;
            peer-as 17;
            neighbor 2001:db8:0:3:2a0:a502:0:9da;
```

```

    }
  }
}
routing-options {
  router-id 172.16.3.3;
  autonomous-system 22;
}
}
D {
  interfaces {
    lt-0/1/0 {
      unit 7 {
        description to-E;
        encapsulation frame-relay;
        dlci 7;
        peer-unit 21;
        family inet6 {
          address 2001:db8:0:4::/64 {
            eui-64;
          }
        }
      }
    }
  }
  lo0 {
    unit 4 {
      family inet6 {
        address 2001:db8::4/128;
      }
    }
  }
}
protocols {
  bgp {
    group external-peers {
      type external;
      peer-as 17;
      neighbor 2001:db8:0:4:2a0:a502:0:15da;
    }
  }
  routing-options {
    router-id 172.16.4.4;
    autonomous-system 79;
  }
}
}
E {
  interfaces {
    lt-0/1/0 {
      unit 5 {
        description to-B;
        encapsulation frame-relay;
        dlci 6;
        peer-unit 6;
        family inet6 {
          address 2001:db8:0:2::/64 {
            eui-64;
          }
        }
      }
    }
  }
}

```

```
    }
  }
  unit 9 {
    description to-C;
    encapsulation frame-relay;
    dlci 10;
    peer-unit 10;
    family inet6 {
      address 2001:db8:0:3::/64 {
        eui-64;
      }
    }
  }
  unit 21 {
    description to-D;
    encapsulation frame-relay;
    dlci 7;
    peer-unit 7;
    family inet6 {
      address 2001:db8:0:4::/64 {
        eui-64;
      }
    }
  }
  unit 25 {
    description to-A;
    encapsulation frame-relay;
    dlci 1;
    peer-unit 1;
    family inet6 {
      address 2001:db8:0:1::/64 {
        eui-64;
      }
    }
  }
}
lo0 {
  unit 5 {
    family inet6 {
      address 2001:db8::5/128;
    }
  }
}
}
protocols {
  bgp {
    group external-peers {
      type external;
      peer-as 22;
      neighbor 2001:db8:0:1:2a0:a502:0:1da;
      neighbor 2001:db8:0:2:2a0:a502:0:6da;
      neighbor 2001:db8:0:3:2a0:a502:0:ada;
      neighbor 2001:db8:0:4:2a0:a502:0:7da {
        peer-as 79;
      }
    }
  }
}
```



```

    }
  }
  routing-options {
    router-id 172.16.5.5;
    autonomous-system 17;
  }
}

```

If you are done configuring the device, enter **commit** from configuration mode.

### Verification

Confirm that the configuration is working properly.

- [Verifying BGP Neighbors on page 31](#)
- [Verifying BGP Groups on page 34](#)
- [Verifying BGP Summary Information on page 34](#)
- [Checking the Routing Table on page 34](#)

#### *Verifying BGP Neighbors*

**Purpose** Verify that BGP is running on configured interfaces and that the BGP session is active for each neighbor address.

**Action** From operational mode, run the **show bgp neighbor** command.

```

user@R1:E> show bgp neighbor
Peer: 2001:db8:0:1:2a0:a502:0:1da+54987 AS 22 Local:
2001:db8:0:1:2a0:a502:0:19da+179 AS 17
  Type: External    State: Established    Flags: <Sync>
  Last State: OpenConfirm    Last Event: RecvKeepAlive
  Last Error: Open Message Error
  Options: <Preference PeerAS Refresh>
  Holdtime: 90 Preference: 170
  Number of flaps: 0
  Error: 'Open Message Error' Sent: 20 Recv: 0
  Peer ID: 172.16.1.1          Local ID: 172.16.5.5          Active Holdtime: 90

  Keepalive Interval: 30          Peer index: 0
  BFD: disabled, down
  Local Interface: lt-0/1/0.25
  NLRI for restart configured on peer: inet6-unicast
  NLRI advertised by peer: inet6-unicast
  NLRI for this session: inet6-unicast
  Peer supports Refresh capability (2)
  Stale routes from peer are kept for: 300
  Peer does not support Restarter functionality
  NLRI that restart is negotiated for: inet6-unicast
  NLRI of received end-of-rib markers: inet6-unicast
  NLRI of all end-of-rib markers sent: inet6-unicast
  Peer supports 4 byte AS extension (peer-as 22)
  Peer does not support Addpath
  Table inet6.0 Bit: 10000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          0
    Received prefixes:        0

```

```

Accepted prefixes:          0
Suppressed due to damping:  0
Advertised prefixes:       0
Last traffic (seconds): Received 7    Sent 18    Checked 81
Input messages:  Total 1611    Updates 1      Refreshes 0    Octets 30660
Output messages: Total 1594    Updates 0      Refreshes 0    Octets 30356
Output Queue[0]: 0

Peer: 2001:db8:0:2:2a0:a502:0:6da+179 AS 22 Local:
2001:db8:0:2:2a0:a502:0:5da+55502 AS 17
Type: External    State: Established    Flags: <Sync>
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: Open Message Error
Options: <Preference PeerAS Refresh>
Holdtime: 90 Preference: 170
Number of flaps: 0
Error: 'Open Message Error' Sent: 26 Recv: 0
Peer ID: 172.16.2.2          Local ID: 172.16.5.5          Active Holdtime: 90

Keepalive Interval: 30          Peer index: 2
BFD: disabled, down
Local Interface: lt-0/1/0.5
NLRI for restart configured on peer: inet6-unicast
NLRI advertised by peer: inet6-unicast
NLRI for this session: inet6-unicast
Peer supports Refresh capability (2)
Stale routes from peer are kept for: 300
Peer does not support Restarter functionality
NLRI that restart is negotiated for: inet6-unicast
NLRI of received end-of-rib markers: inet6-unicast
NLRI of all end-of-rib markers sent: inet6-unicast
Peer supports 4 byte AS extension (peer-as 22)
Peer does not support Addpath
Table inet6.0 Bit: 10000
RIB State: BGP restart is complete
Send state: in sync
Active prefixes:          0
Received prefixes:        0
Accepted prefixes:        0
Suppressed due to damping: 0
Advertised prefixes:      0
Last traffic (seconds): Received 15    Sent 8    Checked 8
Input messages:  Total 1610    Updates 1      Refreshes 0    Octets 30601
Output messages: Total 1645    Updates 0      Refreshes 0    Octets 32417
Output Queue[0]: 0

Peer: 2001:db8:0:3:2a0:a502:0:ada+55983 AS 22 Local:
2001:db8:0:3:2a0:a502:0:9da+179 AS 17
Type: External    State: Established    Flags: <Sync>
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: None
Options: <Preference PeerAS Refresh>
Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 172.16.3.3          Local ID: 172.16.5.5          Active Holdtime: 90

Keepalive Interval: 30          Peer index: 3
BFD: disabled, down
Local Interface: lt-0/1/0.9
NLRI for restart configured on peer: inet6-unicast
NLRI advertised by peer: inet6-unicast

```

```

NLRI for this session: inet6-unicast
Peer supports Refresh capability (2)
Stale routes from peer are kept for: 300
Peer does not support Restarter functionality
NLRI that restart is negotiated for: inet6-unicast
NLRI of received end-of-rib markers: inet6-unicast
NLRI of all end-of-rib markers sent: inet6-unicast
Peer supports 4 byte AS extension (peer-as 22)
Peer does not support Addpath
Table inet6.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        0
  Accepted prefixes:        0
  Suppressed due to damping: 0
  Advertised prefixes:      0
Last traffic (seconds): Received 21   Sent 21   Checked 67
Input messages: Total 1610   Updates 1       Refreshes 0       Octets 30641
Output messages: Total 1587   Updates 0       Refreshes 0       Octets 30223
Output Queue[0]: 0

Peer: 2001:db8:0:4:2a0:a502:0:7da+49255 AS 79 Local:
2001:db8:0:4:2a0:a502:0:15da+179 AS 17
Type: External   State: Established   Flags: <Sync>
Last State: OpenConfirm   Last Event: RecvKeepAlive
Last Error: None
Options: <Preference PeerAS Refresh>
Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 172.16.4.4          Local ID: 172.16.5.5          Active Holdtime: 90

Keepalive Interval: 30          Peer index: 1
BFD: disabled, down
Local Interface: lt-0/1/0.21
NLRI for restart configured on peer: inet6-unicast
NLRI advertised by peer: inet6-unicast
NLRI for this session: inet6-unicast
Peer supports Refresh capability (2)
Stale routes from peer are kept for: 300
Peer does not support Restarter functionality
NLRI that restart is negotiated for: inet6-unicast
NLRI of received end-of-rib markers: inet6-unicast
NLRI of all end-of-rib markers sent: inet6-unicast
Peer supports 4 byte AS extension (peer-as 79)
Peer does not support Addpath
Table inet6.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        0
  Accepted prefixes:        0
  Suppressed due to damping: 0
  Advertised prefixes:      0
Last traffic (seconds): Received 6     Sent 17    Checked 25
Input messages: Total 1615   Updates 1       Refreshes 0       Octets 30736
Output messages: Total 1593   Updates 0       Refreshes 0       Octets 30337
Output Queue[0]: 0

```

**Meaning** IPv6 unicast network layer reachability information (NLRI) is being exchanged between the neighbors.

**Verifying BGP Groups**

**Purpose** Verify that the BGP groups are configured correctly.

**Action** From operational mode, run the **show bgp group** command.

```
user@R1:~> show bgp group
Group Type: External                               Local AS: 17
  Name: external-peers  Index: 0                   Flags: <>
  Holdtime: 0
  Total peers: 4      Established: 4
  2001:db8:0:1:2a0:a502:0:1da+54987
  2001:db8:0:2:2a0:a502:0:6da+179
  2001:db8:0:3:2a0:a502:0:ada+55983
  2001:db8:0:4:2a0:a502:0:7da+49255
  inet6.0: 0/0/0/0

Groups: 1  Peers: 4   External: 4   Internal: 0   Down peers: 0   Flaps: 0
Table      Tot Paths  Act Paths  Suppressed  History  Damp State  Pending
inet6.0           0         0           0          0        0         0
inet6.2           0         0           0          0        0         0
```

**Meaning** The group type is external, and the group has four peers.

**Verifying BGP Summary Information**

**Purpose** Verify that the BGP that the peer relationships are established.

**Action** From operational mode, run the **show bgp summary** command.

```
user@R1:~> show bgp summary
Groups: 1 Peers: 4 Down peers: 0
Table      Tot Paths  Act Paths  Suppressed  History  Damp State  Pending
inet6.0           0         0           0          0        0         0
inet6.2           0         0           0          0        0         0
Peer      AS      InPkt    OutPkt    OutQ    Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
2001:db8:0:1:2a0:a502:0:1da      22     1617     1600        0        0
  12:07:00 Estab1
    inet6.0: 0/0/0/0
2001:db8:0:2:2a0:a502:0:6da      22     1616     1651        0        0
  12:06:56 Estab1
    inet6.0: 0/0/0/0
2001:db8:0:3:2a0:a502:0:ada      22     1617     1594        0        0
  12:04:32 Estab1
    inet6.0: 0/0/0/0
2001:db8:0:4:2a0:a502:0:7da      79     1621     1599        0        0
  12:07:00 Estab1
    inet6.0: 0/0/0/0
```

**Meaning** The Down peers: 0 output shows that the BGP peers are in the established state.

**Checking the Routing Table**

**Purpose** Verify that the inet6.0 routing table is populated with local and direct routes.

**Action** From operational mode, run the **show route** command.

```

user@R1:~> show route
inet6.0: 15 destinations, 18 routes (15 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

2001:db8::5/128    * [Direct/0] 12:41:18
                  > via lo0.5
2001:db8:0:1::/64 * [Direct/0] 14:40:01
                  > via lt-0/1/0.25
2001:db8:0:1:2a0:a502:0:19da/128
                  * [Local/0] 14:40:01
                  Local via lt-0/1/0.25
2001:db8:0:2::/64 * [Direct/0] 14:40:02
                  > via lt-0/1/0.5
2001:db8:0:2:2a0:a502:0:5da/128
                  * [Local/0] 14:40:02
                  Local via lt-0/1/0.5
2001:db8:0:3::/64 * [Direct/0] 14:40:02
                  > via lt-0/1/0.9
2001:db8:0:3:2a0:a502:0:9da/128
                  * [Local/0] 14:40:02
                  Local via lt-0/1/0.9
2001:db8:0:4::/64 * [Direct/0] 14:40:01
                  > via lt-0/1/0.21
2001:db8:0:4:2a0:a502:0:15da/128
                  * [Local/0] 14:40:01
                  Local via lt-0/1/0.21
fe80::/64         * [Direct/0] 14:40:02
                  > via lt-0/1/0.5
                  [Direct/0] 14:40:02
                  > via lt-0/1/0.9
                  [Direct/0] 14:40:01
                  > via lt-0/1/0.21
                  [Direct/0] 14:40:01
                  > via lt-0/1/0.25
fe80::2a0:a502:0:5da/128
                  * [Local/0] 14:40:02
                  Local via lt-0/1/0.5
fe80::2a0:a502:0:9da/128
                  * [Local/0] 14:40:02
                  Local via lt-0/1/0.9
fe80::2a0:a502:0:15da/128
                  * [Local/0] 14:40:01
                  Local via lt-0/1/0.21
fe80::2a0:a502:0:19da/128
                  * [Local/0] 14:40:01
                  Local via lt-0/1/0.25
fe80::2a0:a50f:fc56:1da/128
                  * [Direct/0] 12:41:18
                  > via lo0.5

```

**Meaning** The inet6.0 routing table contains local and direct routes. To populate the routing table with other types of routes, you must configure routing policies.

**Related Documentation**

- [Examples: Configuring Internal BGP Peering on page 36](#)
- [BGP Configuration Overview](#)


## Examples: Configuring Internal BGP Peering

- [Understanding Internal BGP Peering Sessions on page 36](#)
- [Example: Configuring Internal BGP Peer Sessions on page 37](#)
- [Example: Configuring Internal BGP Peering Sessions on Logical Systems on page 48](#)

### Understanding Internal BGP Peering Sessions

When two BGP-enabled devices are in the same autonomous system (AS), the BGP session is called an *internal* BGP session, or IBGP session. BGP uses the same message types on IBGP and external BGP (EBGP) sessions, but the rules for when to send each message and how to interpret each message differ slightly. For this reason, some people refer to IBGP and EBGP as two separate protocols.

Figure 5: Internal and External BGP



In [Figure 5 on page 36](#), Device Jackson, Device Memphis, and Device Biloxi have IBGP peer sessions with each other. Likewise, Device Miami and Device Atlanta have IBGP peer sessions between each other.

The purpose of IBGP is to provide a means by which EBGP route advertisements can be forwarded throughout the network. In theory, to accomplish this task you could redistribute all of your EBGP routes into an interior gateway protocol (IGP), such as OSPF or IS-IS. This, however, is not recommended in a production environment because of the large number of EBGP routes in the Internet and because of the way that IGPs operate. In short, with that many routes the IGP churns or crashes.

Generally, the loopback interface (lo0) is used to establish connections between IBGP peers. The loopback interface is always up as long as the device is operating. If there is a route to the loopback address, the IBGP peering session stays up. If a physical interface address is used instead and that interface goes up and down, the IBGP peering session also goes up and down. Thus the loopback interface provides fault tolerance in case the physical interface or the link goes down, if the device has link redundancy.

While IBGP neighbors do not need to be directly connected, they do need to be fully meshed. In this case, fully meshed means that each device is logically connected to every

other device through neighbor peer relationships. The **neighbor** statement creates the mesh. Because of the full mesh requirement of IBGP, you must configure individual peering sessions between all IBGP devices in the AS. The full mesh need not be physical links. Rather, the configuration on each routing device must create a full mesh of peer sessions (using multiple **neighbor** statements).



**NOTE:** The requirement for a full mesh is waived if you configure a confederation or route reflection.

To understand the full-mesh requirement, consider that an IBGP-learned route cannot be readvertised to another IBGP peer. The reason for preventing the readvertisement of IBGP routes and requiring the full mesh is to avoid routing loops within an AS. The AS path attribute is the means by which BGP routing devices avoid loops. The path information is examined for the local AS number only when the route is received from an EBGP peer. Because the attribute is only modified across AS boundaries, this system works well. However, the fact that the attribute is only modified across AS boundaries presents an issue inside the AS. For example, suppose that routing devices A, B, and C are all in the same AS. Device A receives a route from an EBGP peer and sends the route to Device B, which installs it as the active route. The route is then sent to Device C, which installs it locally and sends it back to Device A. If Device A installs the route, a loop is formed within the AS. The routing devices are not able to detect the loop because the AS path attribute is not modified during these advertisements. Therefore, the BGP protocol designers decided that the only assurance of never forming a routing loop was to prevent an IBGP peer from advertising an IBGP-learned route within the AS. For route reachability, the IBGP peers are fully meshed.

IBGP supports multihop connections, so IBGP neighbors can be located anywhere within the AS and often do not share a link. A recursive route lookup resolves the loopback peering address to an IP forwarding next hop. The lookup service is provided by static routes or an IGP such as OSPF, or BGP routes.

## Example: Configuring Internal BGP Peer Sessions

This example shows how to configure internal BGP peer sessions.

- [Requirements on page 37](#)
- [Overview on page 37](#)
- [Configuration on page 39](#)
- [Verification on page 46](#)

### Requirements

No special configuration beyond device initialization is required before you configure this example.

### Overview

In this example, you configure internal BGP (IBGP) peer sessions. The loopback interface (lo0) is used to establish connections between IBGP peers. The loopback interface is

always up as long as the device is operating. If there is a route to the loopback address, the IBGP peer session stays up. If a physical interface address is used instead and that interface goes up and down, the IBGP peer session also goes up and down. Thus, if the device has link redundancy, the loopback interface provides fault tolerance in case the physical interface or one of the links goes down.

When a device peers with a remote device's loopback interface address, the local device expects BGP update messages to come from (be sourced by) the remote device's loopback interface address. The **local-address** statement enables you to specify the source information in BGP update messages. If you omit the **local-address** statement, the expected source of BGP update messages is based on the device's source address selection rules, which normally results in the egress interface address being the expected source of update messages. When this happens, the peer session is not established because a mismatch exists between the expected source address (the egress interface of the peer) and the actual source (the loopback interface of the peer). To make sure that the expected source address matches the actual source address, specify the loopback interface address in the **local-address** statement.

Because IBGP supports multihop connections, IBGP neighbors can be located anywhere within the autonomous system (AS) and often do not share a link. A recursive route lookup resolves the loopback peer address to an IP forwarding next hop. In this example, this service is provided by OSPF. Although interior gateway protocol (IGP) neighbors do not need to be directly connected, they do need to be fully meshed. In this case, fully meshed means that each device is logically connected to every other device through neighbor peer relationships. The **neighbor** statement creates the mesh.



**NOTE:** The requirement for a full mesh is waived if you configure a confederation or route reflection.

---


After the BGP peers are established, local routes are not automatically advertised by the BGP peers. At each BGP-enabled device, policy configuration is required to export the local, static, or IGP-learned routes into the BGP routing information base (RIB) and then advertise them as BGP routes to the other peers. BGP's advertisement policy, by default, does not advertise any non-BGP routes (such as local routes) to peers.

In the sample network, the devices in AS 17 are fully meshed in the group **internal-peers**. The devices have loopback addresses 192.168.6.5, 192.163.6.4, and 192.168.40.4.

Figure 6 on page 39 shows a typical network with internal peer sessions.



Figure 6: Typical Network with IBGP Sessions



### Configuration

- [Configuring Device A on page 40](#)
- [Configuring Device B on page 42](#)
- [Configuring Device C on page 44](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

##### Device A

```
set interfaces ge-0/1/0 unit 1 description to-B
set interfaces ge-0/1/0 unit 1 family inet address 10.10.10.1/30
set interfaces lo0 unit 1 family inet address 192.168.6.5/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers description "connections to B and C"
set protocols bgp group internal-peers local-address 192.168.6.5
set protocols bgp group internal-peers export send-direct
set protocols bgp group internal-peers neighbor 192.163.6.4
set protocols bgp group internal-peers neighbor 192.168.40.4
set protocols ospf area 0.0.0.0 interface lo0.1 passive
set protocols ospf area 0.0.0.0 interface ge-0/1/0.1
set policy-options policy-statement send-direct term 2 from protocol direct
set policy-options policy-statement send-direct term 2 then accept
set routing-options router-id 192.168.6.5
set routing-options autonomous-system 17
```

##### Device B

```
set interfaces ge-0/1/0 unit 2 description to-A
set interfaces ge-0/1/0 unit 2 family inet address 10.10.10.2/30
set interfaces ge-0/1/1 unit 5 description to-C
set interfaces ge-0/1/1 unit 5 family inet address 10.10.10.5/30
set interfaces lo0 unit 2 family inet address 192.163.6.4/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers description "connections to A and C"
set protocols bgp group internal-peers local-address 192.163.6.4
set protocols bgp group internal-peers export send-direct
set protocols bgp group internal-peers neighbor 192.168.40.4
set protocols bgp group internal-peers neighbor 192.168.6.5
```

```
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set protocols ospf area 0.0.0.0 interface ge-0/1/0.2
set protocols ospf area 0.0.0.0 interface ge-0/1/1.5
set policy-options policy-statement send-direct term 2 from protocol direct
set policy-options policy-statement send-direct term 2 then accept
set routing-options router-id 192.163.6.4
set routing-options autonomous-system 17
```

Device C

```
set interfaces ge-0/1/0 unit 6 description to-B
set interfaces ge-0/1/0 unit 6 family inet address 10.10.10.6/30
set interfaces lo0 unit 3 family inet address 192.168.40.4/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers description "connections to A and B"
set protocols bgp group internal-peers local-address 192.168.40.4
set protocols bgp group internal-peers export send-direct
set protocols bgp group internal-peers neighbor 192.163.6.4
set protocols bgp group internal-peers neighbor 192.168.6.5
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ospf area 0.0.0.0 interface ge-0/1/0.6
set policy-options policy-statement send-direct term 2 from protocol direct
set policy-options policy-statement send-direct term 2 then accept
set routing-options router-id 192.168.40.4
set routing-options autonomous-system 17
```

### Configuring Device A

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure internal BGP peer sessions on Device A:

1. Configure the interfaces.

```
[edit interfaces ge-0/1/0 unit 1]
user@A# set description to-B
user@A# set family inet address 10.10.10.1/30
```

```
[edit interfaces]
user@A# set lo0 unit 1 family inet address 192.168.6.5/32
```

2. Configure BGP.

The **neighbor** statements are included for both Device B and Device C, even though Device A is not directly connected to Device C.

```
[edit protocols bgp group internal-peers]
user@A# set type internal
user@A# set description "connections to B and C"
user@A# set local-address 192.168.6.5
user@A# set export send-direct
user@A# set neighbor 192.163.6.4
user@A# set neighbor 192.168.40.4
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
```

```

user@A# set interface lo0.1 passive
user@A# set interface ge-0/1/0.1

```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```

[edit policy-options policy-statement send-direct term 2]
user@A# set from protocol direct
user@A# set then accept

```

5. Configure the router ID and the AS number.

```

[edit routing-options]
user@A# set router-id 192.168.6.5
user@A# set autonomous-system 17

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@A# show interfaces
ge-0/1/0 {
  unit 1 {
    description to-B;
    family inet {
      address 10.10.10.1/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.6.5/32;
    }
  }
}

user@A# show policy-options
policy-statement send-direct {
  term 2 {
    from protocol direct;
    then accept;
  }
}

user@A# show protocols
bgp {
  group internal-peers {
    type internal;
    description "connections to B and C";
    local-address 192.168.6.5;
    export send-direct;
    neighbor 192.163.6.4;
    neighbor 192.168.40.4;
  }
}

```

```

    }
  }
  ospf {
    area 0.0.0.0 {
      interface lo0.1 {
        passive;
      }
      interface ge-0/1/0.1;
    }
  }
}

user@A# show routing-options
router-id 192.168.6.5;
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device B

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure internal BGP peer sessions on Device B:

1. Configure the interfaces.

```

[edit interfaces ge-0/1/0 unit 2]
user@B# set description to-A
user@B# set family inet address 10.10.10.2/30

```

```

[edit interfaces ge-0/1/1]
user@B# set unit 5 description to-C
user@B# set unit 5 family inet address 10.10.10.5/30

```

```

[edit interfaces]
user@B# set lo0 unit 2 family inet address 192.163.6.4/32

```

2. Configure BGP.

The **neighbor** statements are included for both Device B and Device C, even though Device A is not directly connected to Device C.

```

[edit protocols bgp group internal-peers]
user@B# set type internal
user@B# set description "connections to A and C"
user@B# set local-address 192.163.6.4
user@B# set export send-direct
user@B# set neighbor 192.168.40.4
user@B# set neighbor 192.168.6.5

```

3. Configure OSPF.

```

[edit protocols ospf area 0.0.0.0]
user@B# set interface lo0.2 passive
user@B# set interface ge-0/1/0.2
user@B# set interface ge-0/1/1.5

```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 2]
user@B# set from protocol direct
user@B# set then accept
```

5. Configure the router ID and the AS number.

```
[edit routing-options]
user@B# set router-id 192.163.6.4
user@B# set autonomous-system 17
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@B# show interfaces
ge-0/1/0 {
  unit 2 {
    description to-A;
    family inet {
      address 10.10.10.2/30;
    }
  }
}
ge-0/1/1 {
  unit 5 {
    description to-C;
    family inet {
      address 10.10.10.5/30;
    }
  }
}
lo0 {
  unit 2 {
    family inet {
      address 192.163.6.4/32;
    }
  }
}

user@B# show policy-options
policy-statement send-direct {
  term 2 {
    from protocol direct;
    then accept;
  }
}

user@B# show protocols
bgp {
  group internal-peers {
    type internal;
```

```

        description "connections to A and C";
        local-address 192.163.6.4;
        export send-direct;
        neighbor 192.168.40.4;
        neighbor 192.168.6.5;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.2 {
            passive;
        }
        interface ge-0/1/0.2;
        interface ge-0/1/1.5;
    }
}

```

```

user@B# show routing-options
router-id 192.163.6.4;
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device C

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure internal BGP peer sessions on Device C:

1. Configure the interfaces.

```

[edit interfaces ge-0/1/0 unit 6]
user@C# set description to-B
user@C# set family inet address 10.10.10.6/30

[edit interfaces]
user@C# set lo0 unit 3 family inet address 192.168.40.4/32

```

2. Configure BGP.

The **neighbor** statements are included for both Device B and Device C, even though Device A is not directly connected to Device C.

```

[edit protocols bgp group internal-peers]
user@C# set type internal
user@C# set description "connections to A and B"
user@C# set local-address 192.168.40.4
user@C# set export send-direct
user@C# set neighbor 192.163.6.4
user@C# set neighbor 192.168.6.5

```

3. Configure OSPF.

```

[edit protocols ospf area 0.0.0.0]
user@C# set interface lo0.3 passive
user@C# set interface ge-0/1/0.6

```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 2]
user@C# set from protocol direct
user@C# set then accept
```

5. Configure the router ID and the AS number.

```
[edit routing-options]
user@C# set router-id 192.168.40.4
user@C# set autonomous-system 17
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@C# show interfaces
ge-0/1/0 {
  unit 6 {
    description to-B;
    family inet {
      address 10.10.10.6/30;
    }
  }
}
lo0 {
  unit 3 {
    family inet {
      address 192.168.40.4/32;
    }
  }
}

user@C# show policy-options
policy-statement send-direct {
  term 2 {
    from protocol direct;
    then accept;
  }
}

user@C# show protocols
bgp {
  group internal-peers {
    type internal;
    description "connections to A and B";
    local-address 192.168.40.4;
    export send-direct;
    neighbor 192.163.6.4;
    neighbor 192.168.6.5;
  }
}
ospf {
```

```
area 0.0.0.0 {  
    interface lo0.3 {  
        passive;  
    }  
    interface ge-0/1/0.6;  
}  
}  
  
user@C# show routing-options  
router-id 192.168.40.4;  
autonomous-system 17;
```

If you are done configuring the device, enter **commit** from configuration mode.

---

### Verification

Confirm that the configuration is working properly.

- [Verifying BGP Neighbors on page 46](#)
- [Verifying BGP Groups on page 47](#)
- [Verifying BGP Summary Information on page 48](#)
- [Verifying That BGP Routes Are Installed in the Routing Table on page 48](#)

#### *Verifying BGP Neighbors*

**Purpose** Verify that BGP is running on configured interfaces and that the BGP session is active for each neighbor address.

**Action** From operational mode, enter the **show bgp neighbor** command.

```
user@A> show bgp neighbor  
Peer: 192.163.6.4+179 AS 17    Local: 192.168.6.5+58852 AS 17  
  Type: Internal    State: Established    Flags: Sync  
  Last State: OpenConfirm    Last Event: RecvKeepAlive  
  Last Error: None  
  Export: [ send-direct ]  
  Options: Preference LocalAddress Refresh  
  Local Address: 192.168.6.5 Holdtime: 90 Preference: 170  
  Number of flaps: 0  
  Peer ID: 192.163.6.4    Local ID: 192.168.6.5    Active Holdtime: 90  
  Keepalive Interval: 30    Peer index: 0  
  BFD: disabled, down  
  NLRI for restart configured on peer: inet-unicast  
  NLRI advertised by peer: inet-unicast  
  NLRI for this session: inet-unicast  
  Peer supports Refresh capability (2)  
  Restart time configured on the peer: 120  
  Stale routes from peer are kept for: 300  
  Restart time requested by this peer: 120  
  NLRI that peer supports restart for: inet-unicast  
  NLRI that restart is negotiated for: inet-unicast  
  NLRI of received end-of-rib markers: inet-unicast  
  NLRI of all end-of-rib markers sent: inet-unicast  
  Peer supports 4 byte AS extension (peer-as 17)  
  Peer does not support Addpath  
  Table inet.0 Bit: 10000  
    RIB State: BGP restart is complete
```



```

Send state: in sync
Active prefixes:          0
Received prefixes:        3
Accepted prefixes:        3
Suppressed due to damping: 0
Advertised prefixes:      2
Last traffic (seconds): Received 25   Sent 19   Checked 67
Input messages:  Total 2420   Updates 4     Refreshes 0     Octets 46055
Output messages: Total 2411   Updates 2     Refreshes 0     Octets 45921
Output Queue[0]: 0

Peer: 192.168.40.4+179 AS 17   Local: 192.168.6.5+56466 AS 17
Type: Internal   State: Established   Flags: Sync
Last State: OpenConfirm   Last Event: RecvKeepAlive
Last Error: None
Export: [ send-direct ]
Options: Preference LocalAddress Refresh
Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 192.168.40.4   Local ID: 192.168.6.5   Active Holdtime: 90
Keepalive Interval: 30   Peer index: 1
BFD: disabled, down
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 17)
Peer does not support Addpath
Table inet.0 Bit: 10000
RIB State: BGP restart is complete
Send state: in sync
Active prefixes:          0
Received prefixes:        2
Accepted prefixes:        2
Suppressed due to damping: 0
Advertised prefixes:      2
Last traffic (seconds): Received 7   Sent 21   Checked 24
Input messages:  Total 2412   Updates 2     Refreshes 0     Octets 45867
Output messages: Total 2409   Updates 2     Refreshes 0     Octets 45883
Output Queue[0]: 0

```

### Verifying BGP Groups

**Purpose** Verify that the BGP groups are configured correctly.

**Action** From operational mode, enter the **show bgp group** command.

```

user@A> show bgp group
Group Type: Internal   AS: 17   Local AS: 17
Name: internal-peers  Index: 0   Flags: <Export Eval>
Export: [ send-direct ]
Holdtime: 0
Total peers: 2   Established: 2
192.163.6.4+179

```

```

192.168.40.4+179
inet.0: 0/5/5/0

Groups: 1 Peers: 2 External: 0 Internal: 2 Down peers: 0 Flaps: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
inet.0 5 0 0 0 0 0 0

```

### Verifying BGP Summary Information

**Purpose** Verify that the BGP configuration is correct.

**Action** From operational mode, enter the **show bgp summary** command.

```

user@A> show bgp summary
Groups: 1 Peers: 2 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
inet.0 5 0 0 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
192.163.6.4 17 2441 2432 0 0 18:18:52
0/3/3/0 0/0/0/0
192.168.40.4 17 2432 2430 0 0 18:18:48
0/2/2/0 0/0/0/0

```

### Verifying That BGP Routes Are Installed in the Routing Table

**Purpose** Verify that the export policy configuration is causing the BGP routes to be installed in the routing tables of the peers.

**Action** From operational mode, enter the **show route protocol bgp** command.

```

user@A> show route protocol bgp
inet.0: 7 destinations, 12 routes (7 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.0/30 [BGP/170] 07:09:57, localpref 100, from 192.163.6.4
AS path: I
> to 10.10.10.2 via ge-0/1/0.1
10.10.10.4/30 [BGP/170] 07:09:57, localpref 100, from 192.163.6.4
AS path: I
> to 10.10.10.2 via ge-0/1/0.1
[BGP/170] 07:07:12, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via ge-0/1/0.1
192.163.6.4/32 [BGP/170] 07:09:57, localpref 100, from 192.163.6.4
AS path: I
> to 10.10.10.2 via ge-0/1/0.1
192.168.40.4/32 [BGP/170] 07:07:12, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via ge-0/1/0.1

```

## Example: Configuring Internal BGP Peering Sessions on Logical Systems

This example shows how to configure internal BGP peer sessions on logical systems.

- [Requirements on page 49](#)
- [Overview on page 49](#)

- [Configuration on page 49](#)
- [Verification on page 56](#)

## Requirements

In this example, no special configuration beyond device initialization is required.


## Overview

In this example, you configure internal BGP (IBGP) peering sessions.

In the sample network, the devices in AS 17 are fully meshed in the group **internal-peers**. The devices have loopback addresses 192.168.6.5, 192.163.6.4, and 192.168.40.4.

[Figure 7 on page 49](#) shows a typical network with internal peer sessions.

**Figure 7: Typical Network with IBGP Sessions**



## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set logical-systems A interfaces lt-0/1/0 unit 1 description to-B
set logical-systems A interfaces lt-0/1/0 unit 1 encapsulation ethernet
set logical-systems A interfaces lt-0/1/0 unit 1 peer-unit 2
set logical-systems A interfaces lt-0/1/0 unit 1 family inet address 10.10.10.1/30
set logical-systems A interfaces lo0 unit 1 family inet address 192.168.6.5/32
set logical-systems A protocols bgp group internal-peers type internal
set logical-systems A protocols bgp group internal-peers local-address 192.168.6.5
set logical-systems A protocols bgp group internal-peers export send-direct
set logical-systems A protocols bgp group internal-peers neighbor 192.163.6.4
set logical-systems A protocols bgp group internal-peers neighbor 192.168.40.4
set logical-systems A protocols ospf area 0.0.0.0 interface lo0.1 passive
set logical-systems A protocols ospf area 0.0.0.0 interface lt-0/1/0.1
set logical-systems A policy-options policy-statement send-direct term 2 from protocol direct
set logical-systems A policy-options policy-statement send-direct term 2 then accept
```

```

set logical-systems A routing-options router-id 192.168.6.5
set logical-systems A routing-options autonomous-system 17
set logical-systems B interfaces lt-0/1/0 unit 2 description to-A
set logical-systems B interfaces lt-0/1/0 unit 2 encapsulation ethernet
set logical-systems B interfaces lt-0/1/0 unit 2 peer-unit 1
set logical-systems B interfaces lt-0/1/0 unit 2 family inet address 10.10.10.2/30
set logical-systems B interfaces lt-0/1/0 unit 5 description to-C
set logical-systems B interfaces lt-0/1/0 unit 5 encapsulation ethernet
set logical-systems B interfaces lt-0/1/0 unit 5 peer-unit 6
set logical-systems B interfaces lt-0/1/0 unit 5 family inet address 10.10.10.5/30
set logical-systems B interfaces lo0 unit 2 family inet address 192.163.6.4/32
set logical-systems B protocols bgp group internal-peers type internal
set logical-systems B protocols bgp group internal-peers local-address 192.163.6.4
set logical-systems B protocols bgp group internal-peers export send-direct
set logical-systems B protocols bgp group internal-peers neighbor 192.168.40.4
set logical-systems B protocols bgp group internal-peers neighbor 192.168.6.5
set logical-systems B protocols ospf area 0.0.0.0 interface lo0.2 passive
set logical-systems B protocols ospf area 0.0.0.0 interface lt-0/1/0.2
set logical-systems B protocols ospf area 0.0.0.0 interface lt-0/1/0.5
set logical-systems B policy-options policy-statement send-direct term 2 from protocol
    direct
set logical-systems B policy-options policy-statement send-direct term 2 then accept
set logical-systems B routing-options router-id 192.163.6.4
set logical-systems B routing-options autonomous-system 17
set logical-systems C interfaces lt-0/1/0 unit 6 description to-B
set logical-systems C interfaces lt-0/1/0 unit 6 encapsulation ethernet
set logical-systems C interfaces lt-0/1/0 unit 6 peer-unit 5
set logical-systems C interfaces lt-0/1/0 unit 6 family inet address 10.10.10.6/30
set logical-systems C interfaces lo0 unit 3 family inet address 192.168.40.4/32
set logical-systems C protocols bgp group internal-peers type internal
set logical-systems C protocols bgp group internal-peers local-address 192.168.40.4
set logical-systems C protocols bgp group internal-peers export send-direct
set logical-systems C protocols bgp group internal-peers neighbor 192.163.6.4
set logical-systems C protocols bgp group internal-peers neighbor 192.168.6.5
set logical-systems C protocols ospf area 0.0.0.0 interface lo0.3 passive
set logical-systems C protocols ospf area 0.0.0.0 interface lt-0/1/0.6
set logical-systems C policy-options policy-statement send-direct term 2 from protocol
    direct
set logical-systems C policy-options policy-statement send-direct term 2 then accept
set logical-systems C routing-options router-id 192.168.40.4
set logical-systems C routing-options autonomous-system 17

```

### Device A

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure internal BGP peer sessions on Device A:

1. Configure the interfaces.
 

```

[edit logical-systems A interfaces lt-0/1/0 unit 1]
user@R1# set description to-B
user@R1# set encapsulation ethernet
user@R1# set peer-unit 2

```

```

user@R1# set family inet address 10.10.10.1/30
user@R1# set family inet address 192.168.6.5/32
user@R1# up
user@R1# up
[edit logical-systems A interfaces]
user@R1# set lo0 unit 1 family inet address 192.168.6.5/32
user@R1# exit
[edit]
user@R1# edit logical-systems B interfaces lt-0/1/0
[edit logical-systems B interfaces lt-0/1/0]
user@R1# set unit 2 description to-A
user@R1# set unit 2 encapsulation ethernet
user@R1# set unit 2 peer-unit 1
user@R1# set unit 2 family inet address 10.10.10.2/30
user@R1# set unit 5 description to-C
user@R1# set unit 5 encapsulation ethernet
user@R1# set unit 5 peer-unit 6
user@R1# set family inet address 10.10.10.5/30
user@R1# up
[edit logical-systems B interfaces]
user@R1# set lo0 unit 2 family inet address 192.163.6.4/32
user@R1# exit
[edit]
user@R1# edit logical-systems C interfaces lt-0/1/0 unit 6
[edit logical-systems C interfaces lt-0/1/0 unit 6]
set description to-B
set encapsulation ethernet
set peer-unit 5
set family inet address 10.10.10.6/30
user@R1# up
user@R1# up
[edit logical-systems C interfaces]
set lo0 unit 3 family inet address 192.168.40.4/32

```

## 2. Configure BGP.

On Logical System A, the **neighbor** statements are included for both Device B and Device C, even though Logical System A is not directly connected to Device C.

```

[edit logical-systems A protocols bgp group internal-peers]
user@R1# set type internal
user@R1# set local-address 192.168.6.5
user@R1# set export send-direct
user@R1# set neighbor 192.163.6.4
user@R1# set neighbor 192.168.40.4

```

```

[edit logical-systems B protocols bgp group internal-peers]
user@R1# set type internal
user@R1# set local-address 192.163.6.4
user@R1# set export send-direct
user@R1# set neighbor 192.168.40.4
user@R1# set neighbor 192.168.6.5

```

```

[edit logical-systems C protocols bgp group internal-peers]
user@R1# set type internal
user@R1# set local-address 192.168.40.4

```

```
user@R1# set export send-direct
user@R1# set neighbor 192.163.6.4
user@R1# set neighbor 192.168.6.5
```

3. Configure OSPF.

```
[edit logical-systems A protocols ospf area 0.0.0.0]
user@R1# set interface lo0.1 passive
user@R1# set interface lt-0/1/0.1
```

```
[edit logical-systems A protocols ospf area 0.0.0.0]
user@R1# set interface lo0.2 passive
user@R1# set interface lt-0/1/0.2
user@R1# set interface lt-0/1/0.5
```

```
[edit logical-systems A protocols ospf area 0.0.0.0]
user@R1# set interface lo0.3 passive
user@R1# set interface lt-0/1/0.6
```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit logical-systems A policy-options policy-statement send-direct term 2]
user@R1# set from protocol direct
user@R1# set then accept
```

```
[edit logical-systems B policy-options policy-statement send-direct term 2]
user@R1# set from protocol direct
user@R1# set then accept
```

```
[edit logical-systems C policy-options policy-statement send-direct term 2]
user@R1# set from protocol direct
user@R1# set then accept
```

5. Configure the router ID and the autonomous system (AS) number.

```
[edit logical-systems A routing-options]
user@R1# set router-id 192.168.6.5
user@R1# set autonomous-system 17
```

```
[edit logical-systems B routing-options]
user@R1# set router-id 192.163.6.4
user@R1# set autonomous-system 17
```

```
[edit logical-systems C routing-options]
user@R1# set router-id 192.168.40.4
user@R1# set autonomous-system 17
```

**Results** From configuration mode, confirm your configuration by entering the **show logical-systems** command. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
user@R1# show logical-systems
```

```

A {
  interfaces {
    lt-0/1/0 {
      unit 1 {
        description to-B;
        encapsulation ethernet;
        peer-unit 2;
        family inet {
          address 10.10.10.1/30;
        }
      }
    }
  }
  lo0 {
    unit 1 {
      family inet {
        address 192.168.6.5/32;
      }
    }
  }
}
protocols {
  bgp {
    group internal-peers {
      type internal;
      local-address 192.168.6.5;
      export send-direct;
      neighbor 192.163.6.4;
      neighbor 192.168.40.4;
    }
  }
  ospf {
    area 0.0.0.0 {
      interface lo0.1 {
        passive;
      }
      interface lt-0/1/0.1;
    }
  }
}
policy-options {
  policy-statement send-direct {
    term 2 {
      from protocol direct;
      then accept;
    }
  }
}
routing-options {
  router-id 192.168.6.5;
  autonomous-system 17;
}
}
B {
  interfaces {
    lt-0/1/0 {
      unit 2 {

```

```
        description to-A;
        encapsulation ethernet;
        peer-unit 1;
        family inet {
            address 10.10.10.2/30;
        }
    }
    unit 5 {
        description to-C;
        encapsulation ethernet;
        peer-unit 6;
        family inet {
            address 10.10.10.5/30;
        }
    }
}
lo0 {
    unit 2 {
        family inet {
            address 192.163.6.4/32;
        }
    }
}
}
protocols {
    bgp {
        group internal-peers {
            type internal;
            local-address 192.163.6.4;
            export send-direct;
            neighbor 192.168.40.4;
            neighbor 192.168.6.5;
        }
    }
    ospf {
        area 0.0.0.0 {
            interface lo0.2 {
                passive;
            }
            interface lt-0/1/0.2;
            interface lt-0/1/0.5;
        }
    }
}
policy-options {
    policy-statement send-direct {
        term 2 {
            from protocol direct;
            then accept;
        }
    }
}
routing-options {
    router-id 192.163.6.4;
    autonomous-system 17;
}
```



```

}
C {
  interfaces {
    lt-0/1/0 {
      unit 6 {
        description to-B;
        encapsulation ethernet;
        peer-unit 5;
        family inet {
          address 10.10.10.6/30;
        }
      }
    }
    lo0 {
      unit 3 {
        family inet {
          address 192.168.40.4/32;
        }
      }
    }
  }
  protocols {
    bgp {
      group internal-peers {
        type internal;
        local-address 192.168.40.4;
        export send-direct;
        neighbor 192.163.6.4;
        neighbor 192.168.6.5;
      }
    }
    ospf {
      area 0.0.0.0 {
        interface lo0.3 {
          passive;
        }
        interface lt-0/1/0.6;
      }
    }
  }
  policy-options {
    policy-statement send-direct {
      term 2 {
        from protocol direct;
        then accept;
      }
    }
  }
  routing-options {
    router-id 192.168.40.4;
    autonomous-system 17;
  }
}

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Verifying BGP Neighbors on page 56](#)
- [Verifying BGP Groups on page 57](#)
- [Verifying BGP Summary Information on page 57](#)
- [Verifying That BGP Routes Are Installed in the Routing Table on page 58](#)

### Verifying BGP Neighbors

**Purpose** Verify that BGP is running on configured interfaces and that the BGP session is active for each neighbor address.

**Action** From the operational mode, enter the **show bgp neighbor** command.

```

user@R1> show bgp neighbor logical-system A
Peer: 192.163.6.4+179 AS 17      Local: 192.168.6.5+58852 AS 17
  Type: Internal    State: Established    Flags: <Sync>
  Last State: OpenConfirm    Last Event: RecvKeepAlive
  Last Error: None
  Export: [ send-direct ]
  Options: <Preference LocalAddress Refresh>
  Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 192.163.6.4      Local ID: 192.168.6.5      Active Holdtime: 90
  Keepalive Interval: 30      Peer index: 0
  BFD: disabled, down
  NLRI for restart configured on peer: inet-unicast
  NLRI advertised by peer: inet-unicast
  NLRI for this session: inet-unicast
  Peer supports Refresh capability (2)
  Restart time configured on the peer: 120
  Stale routes from peer are kept for: 300
  Restart time requested by this peer: 120
  NLRI that peer supports restart for: inet-unicast
  NLRI that restart is negotiated for: inet-unicast
  NLRI of received end-of-rib markers: inet-unicast
  NLRI of all end-of-rib markers sent: inet-unicast
  Peer supports 4 byte AS extension (peer-as 17)
  Peer does not support Addpath
  Table inet.0 Bit: 10000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          0
    Received prefixes:        3
    Accepted prefixes:        3
    Suppressed due to damping: 0
    Advertised prefixes:      2
  Last traffic (seconds): Received 16    Sent 1    Checked 63
  Input messages: Total 15713 Updates 4    Refreshes 0    Octets 298622
  Output messages: Total 15690 Updates 2    Refreshes 0    Octets 298222
  Output Queue[0]: 0

Peer: 192.168.40.4+179 AS 17      Local: 192.168.6.5+56466 AS 17
  Type: Internal    State: Established    Flags: <Sync>
  Last State: OpenConfirm    Last Event: RecvKeepAlive
  Last Error: None

```

```

Export: [ send-direct ]
Options: <Preference LocalAddress Refresh>
Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 192.168.40.4    Local ID: 192.168.6.5    Active Holdtime: 90
Keepalive Interval: 30    Peer index: 1
BFD: disabled, down
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 17)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:      0
  Received prefixes:    2
  Accepted prefixes:    2
  Suppressed due to damping: 0
  Advertised prefixes:  2
Last traffic (seconds): Received 15    Sent 22    Checked 68
Input messages: Total 15688 Updates 2    Refreshes 0    Octets 298111
Output messages: Total 15688 Updates 2    Refreshes 0    Octets 298184
Output Queue[0]: 0

```

### Verifying BGP Groups

**Purpose** Verify that the BGP groups are configured correctly.

**Action** From the operational mode, enter the **show bgp group** command.

```

user@A> show bgp group logical-system A
Group Type: Internal    AS: 17                      Local AS: 17
Name: internal-peers   Index: 0                    Flags: <Export Eval>
Export: [ send-direct ]
Holdtime: 0
Total peers: 2          Established: 2
192.163.6.4+179
192.168.40.4+179
inet.0: 0/5/5/0

Groups: 1  Peers: 2   External: 0   Internal: 2   Down peers: 0   Flaps: 0
Table      Tot Paths  Act Paths  Suppressed   History Damp State   Pending
inet.0           5           0           0           0         0         0

```

### Verifying BGP Summary Information

**Purpose** Verify that the BGP configuration is correct.

**Action** From the operational mode, enter the **show bgp summary** command.

```

user@A> show bgp summary logical-system A

```

```

Groups: 1 Peers: 2 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History  Damp State  Pending
inet.0      5          0          0          0          0      0      0
Peer        AS      InPkt    OutPkt    OutQ    Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
192.163.6.4  17      15723    15700      0        0 4d 22:13:15
0/3/3/0      0/0/0/0
192.168.40.4 17      15698    15699      0        0 4d 22:13:11
0/2/2/0      0/0/0/0

```

### Verifying That BGP Routes Are Installed in the Routing Table

**Purpose** Verify that the export policy configuration is working.

**Action** From the operational mode, enter the **show route protocol bgp** command.

```

user@A> show route protocol bgp logical-system A
inet.0: 7 destinations, 12 routes (7 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.0/30      [BGP/170] 4d 11:05:55, localpref 100, from 192.163.6.4
                  AS path: I
                  > to 10.10.10.2 via lt-0/1/0.1
10.10.10.4/30      [BGP/170] 4d 11:05:55, localpref 100, from 192.163.6.4
                  AS path: I
                  > to 10.10.10.2 via lt-0/1/0.1
                  [BGP/170] 4d 11:03:10, localpref 100, from 192.168.40.4
                  AS path: I
                  > to 10.10.10.2 via lt-0/1/0.1
192.163.6.4/32     [BGP/170] 4d 11:05:55, localpref 100, from 192.163.6.4
                  AS path: I
                  > to 10.10.10.2 via lt-0/1/0.1
192.168.40.4/32    [BGP/170] 4d 11:03:10, localpref 100, from 192.168.40.4
                  AS path: I
                  > to 10.10.10.2 via lt-0/1/0.1

```

**Related Documentation**

- [Examples: Configuring External BGP Peering on page 13](#)

## Configuring BGP Monitoring Protocol Version 3

BGP Monitoring Protocol (BMP) allows the Junos OS to send the BGP route information from the router to a monitoring application on a separate device. The monitoring application is called the BMP monitoring station or BMP station. To deploy BMP in your network, you need to configure BMP on each router and you also need to configure at least one BMP station. This procedure describes how to configure BMP on a router.

You can specify these settings for all BMP stations by configuring the statements described here at the **[edit routing-options bmp]** hierarchy level. You can also configure settings for specific BMP stations by configuring these statements at the **[edit routing-options bmp station *station-name*]** hierarchy level.

The following procedure describes how to configure BMP version 3 on the router:

1. Specify the memory limit for the BMP monitoring station by configuring the **memory limit** statement. The value must be in bytes.

**memory limit** *bytes*;

2. Specify the name or address for the BMP monitoring station by configuring the **station-address** statement. You can specify one or the other but not both. The address must be a valid IPv4 or IPv6 address.

**station-address** (*ip-address* | *station-name*);

3. Specify the port number for the BMP monitoring station by configuring the **station-port** statement. See also [connection-mode](#).

**station-port** *port-number*;

4. Configure how often statistics messages are sent to the BMP monitoring station by specifying the number of seconds between message transmissions using **statistics-timeout** statement. If you configure a value of 0, no statistics messages are sent.

**statistics-timeout** *seconds*;

**Related Documentation**

- [Example: Configuring Route Authentication for BGP on page 312](#)



## CHAPTER 3

# BGP Path Attribute Configuration

- [Example: Configuring BGP Local Preference on page 61](#)
- [Examples: Configuring BGP MED on page 74](#)
- [Examples: Configuring BGP Local AS on page 113](#)
- [Example: Configuring the Accumulated IGP Attribute for BGP on page 133](#)

### Example: Configuring BGP Local Preference

---

- [Understanding the Local Preference Metric for Internal BGP Routes on page 61](#)
- [Example: Configuring the Local Preference Value for BGP Routes on page 61](#)

### Understanding the Local Preference Metric for Internal BGP Routes

Internal BGP (IBGP) sessions use a metric called the *local preference*, which is carried in IBGP update packets in the path attribute LOCAL\_PREF. When an autonomous system (AS) has multiple routes to another AS, the local preference indicates the degree of preference for one route over the other routes. The route with the highest local preference value is preferred.

The LOCAL\_PREF path attribute is always advertised to IBGP peers and to neighboring confederations. It is never advertised to external BGP (EBGP) peers. The default behavior is to not modify the LOCAL\_PREF path attribute if it is present.

The LOCAL\_PREF path attribute applies at export time only, when the routes are exported from the routing table into BGP.

If a BGP route is received without a LOCAL\_PREF attribute, the route is stored in the routing table and advertised by BGP as if it were received with a LOCAL\_PREF value of 100. A non-BGP route that is advertised by BGP is advertised with a LOCAL\_PREF value of 100 by default.

### Example: Configuring the Local Preference Value for BGP Routes

This example shows how to configure local preference in internal BGP (IBGP) peer sessions.

- [Requirements on page 62](#)
- [Overview on page 62](#)

- [Configuration on page 63](#)
- [Verification on page 72](#)

## Requirements

No special configuration beyond device initialization is required before you configure this example.


## Overview

To change the local preference metric advertised in the path attribute, you must include the **local-preference** statement, specifying a value from 0 through 4,294,967,295 ( $2^{32} - 1$ ).

There are several reasons you might want to prefer one path over another. For example, compared to other paths, one path might be less expensive to use, might have higher bandwidth, or might be more stable.

[Figure 8 on page 62](#) shows a typical network with internal peer sessions and multiple exit points to a neighboring AS.

**Figure 8: Typical Network with IBGP Sessions and Multiple Exit Points**



To reach Device R4, Device R1 can take a path through either Device R2 or Device R3. By default, the local preference is 100 for either route. When the local preferences are equal, Junos OS has rules for breaking the tie and choosing a path. (See [“Understanding BGP Path Selection” on page 202](#).) In this example, the active route is through Device R2 because the router ID of Device R2 is lower than the router ID of Device R3. The following example shows how to override the default behavior with an explicit setting for the local preference. The example configures a local preference of 300 on Device R3, thereby making Device R3 the preferred path to reach Device R4.



## Configuration

- [Configuring Device R1 on page 64](#)
- [Configuring Device R2 on page 66](#)
- [Configuring Device R3 on page 68](#)
- [Configuring Device R4 on page 71](#)

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device R1**

```

set interfaces fe-1/2/0 unit 1 family inet address 12.12.12.1/24
set interfaces fe-1/2/1 unit 2 family inet address 13.13.13.1/24
set interfaces lo0 unit 1 family inet address 192.168.1.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.1.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.2.1
set protocols bgp group internal neighbor 192.168.3.1
set protocols ospf area 0.0.0.0 interface lo0.1 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.1
set protocols ospf area 0.0.0.0 interface fe-1/2/1.2
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.1.1

```

**Device R2**

```

set interfaces fe-1/2/0 unit 3 family inet address 12.12.12.2/24
set interfaces fe-1/2/1 unit 4 family inet address 24.24.24.2/24
set interfaces lo0 unit 2 family inet address 192.168.2.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.2.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.1.1
set protocols bgp group internal neighbor 192.168.3.1
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 4
set protocols bgp group external neighbor 24.24.24.4
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.3
set protocols ospf area 0.0.0.0 interface fe-1/2/1.4
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.2.1

```

**Device R3**

```

set interfaces fe-1/2/0 unit 5 family inet address 13.13.13.3/24
set interfaces fe-1/2/1 unit 6 family inet address 34.34.34.3/24
set interfaces lo0 unit 3 family inet address 192.168.3.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.3.1

```

```
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.1.1
set protocols bgp group internal neighbor 192.168.2.1
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 4
set protocols bgp group external neighbor 34.34.34.4
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.5
set protocols ospf area 0.0.0.0 interface fe-1/2/1.6
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.3.1
```

**Device R4**

```
set interfaces fe-1/2/0 unit 7 family inet address 24.24.24.4/24
set interfaces fe-1/2/1 unit 8 family inet address 34.34.34.4/24
set interfaces lo0 unit 4 family inet address 192.168.4.1/32
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 123
set protocols bgp group external neighbor 34.34.34.3
set protocols bgp group external neighbor 24.24.24.2
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 4
set routing-options router-id 192.168.4.1
```

### *Configuring Device R1*

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.

```
[edit interfaces fe-1/2/0 unit 1]
user@R1# set family inet address 12.12.12.1/24
```

```
[edit interfaces fe-1/2/1 unit 2]
user@R1# set family inet address 13.13.13.1/24
```

```
[edit interfaces lo0 unit 1]
user@R1# set family inet address 192.168.1.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]
user@R1# set type internal
user@R1# set local-address 192.168.1.1
user@R1# set export send-direct
user@R1# set neighbor 192.168.2.1
user@R1# set neighbor 192.168.3.1
```

## 3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R1# set interface lo0.1 passive
user@R1# set interface fe-1/2/0.1
user@R1# set interface fe-1/2/1.2
```

## 4. Configure a policy that accepts direct routes.



**NOTE:** Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R1# set from protocol direct
user@R1# set then accept
```

## 5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R1# set autonomous-system 123
user@R1# set router-id 192.168.1.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-1/2/0 {
  unit 1 {
    family inet {
      address 12.12.12.1/24;
    }
  }
}
fe-1/2/1 {
  unit 2 {
    family inet {
      address 13.13.13.1/24;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.1.1/32;
    }
  }
}

user@R1# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
```

```

        then accept;
    }
}

user@R1# show protocols
bgp {
    group internal {
        type internal;
        local-address 192.168.1.1;
        export send-direct;
        neighbor 192.168.2.1;
        neighbor 192.168.3.1;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.1 {
            passive;
        }
        interface fe-1/2/0.1;
        interface fe-1/2/1.2;
    }
}

user@R1# show routing-options
autonomous-system 123;
router-id 192.168.1.1;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R2

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R2:

1. Configure the interfaces.
 

```

[edit interfaces fe-1/2/0 unit 3]
user@R2# set family inet address 12.12.12.21/24

[edit interfaces fe-1/2/1 unit 4]
user@R2# set family inet address 24.24.24.2/24

[edit interfaces lo0 unit 2]
user@R2# set family inet address 192.168.2.1/32

```
2. Configure BGP.
 

```

[edit protocols bgp group internal]
user@R2# set type internal
user@R2# set local-address 192.168.2.1
user@R2# set export send-direct
user@R2# set neighbor 192.168.1.1
user@R2# set neighbor 192.168.3.1

```

```
[edit protocols bgp group external]
user@R2# set type external
user@R2# set export send-direct
user@R2# set peer-as 4
user@R2# set neighbor 24.24.24.4
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R2# set interface lo0.2 passive
user@R2# set interface fe-1/2/0.3
user@R2# set interface fe-1/2/1.4
```

4. Configure a policy that accepts direct routes.



**NOTE:** Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R2# set from protocol direct
user@R2# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R2# set autonomous-system 123
user@R2# set router-id 192.168.2.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
fe-1/2/0 {
  unit 3 {
    family inet {
      address 12.12.12.2/24;
    }
  }
}
fe-1/2/1 {
  unit 4 {
    family inet {
      address 24.24.24.2/24;
    }
  }
}
lo0 {
  unit 2 {
    family inet {
      address 192.168.2.1/32;
    }
  }
}
```

```
}
user@R2# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R2# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.2.1;
    export send-direct;
    neighbor 192.168.1.1;
    neighbor 192.168.3.1;
  }
  group external {
    type external;
    export send-direct;
    peer-as 4;
    neighbor 24.24.24.4;
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.2 {
      passive;
    }
    interface fe-1/2/0.3;
    interface fe-1/2/1.4;
  }
}

user@R2# show routing-options
autonomous-system 123;
router-id 192.168.2.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

### ***Configuring Device R3***

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R3:

1. Configure the interfaces.  
  
[edit interfaces fe-1/2/0 unit 5]  
user@R3# set family inet address 13.13.13.3/24  
  
[edit interfaces fe-1/2/1 unit 6]  
user@R3# set family inet address 34.34.34.3/24

```
[edit interfaces lo0 unit 3]
user@R3# set family inet address 192.168.3.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]
user@R3# set type internal
user@R3# set local-address 192.168.3.1
user@R3# set export send-direct
user@R3# set neighbor 192.168.1.1
user@R3# set neighbor 192.168.2.1
```

```
[edit protocols bgp group external]
user@R3# set type external
user@R3# set export send-direct
user@R3# set peer-as 4
user@R3# set neighbor 34.34.34.4
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R3# set interface lo0.3 passive
user@R3# set interface fe-1/2/0.5
user@R3# set interface fe-1/2/1.6
```

4. Configure a policy that accepts direct routes.



**NOTE:** Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R3# set from protocol direct
user@R3# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R3# set autonomous-system 123
user@R3# set router-id 192.168.3.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R3# show interfaces
fe-1/2/0 {
  unit 5 {
    family inet {
      address 13.13.13.3/24;
    }
  }
}
fe-1/2/1 {
```

```
    unit 6 {
      family inet {
        address 34.34.34.3/24;
      }
    }
  }
lo0 {
  unit 3 {
    family inet {
      address 192.168.3.1/32;
    }
  }
}

user@R3# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R3# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.3.1;
    export send-direct;
    neighbor 192.168.1.1;
    neighbor 192.168.2.1;
  }
  group external {
    type external;
    export send-direct;
    peer-as 4;
    neighbor 34.34.34.4;
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.3 {
      passive;
    }
    interface fe-1/2/0.5;
    interface fe-1/2/1.6;
  }
}

user@R3# show routing-options
autonomous-system 123;
router-id 192.168.3.1;
```

If you are done configuring the device, enter **commit** from configuration mode.



**Configuring Device R4**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R4:

1. Configure the interfaces.  

```
[edit interfaces fe-1/2/0 unit 7]
user@R4# set family inet address 24.24.24.4/24

[edit interfaces fe-1/2/1 unit 8]
user@R4# set family inet address 34.34.34.4/24

[edit interfaces lo0 unit 4]
user@R4# set family inet address 192.168.4.1/32
```
2. Configure BGP.  

```
[edit protocols bgp group external]
user@R4# set type external
user@R4# set export send-direct
user@R4# set peer-as 123
user@R4# set neighbor 34.34.34.3
user@R4# set neighbor 24.24.24.2
```
3. Configure a policy that accepts direct routes.



**NOTE:** Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

- ```
[edit policy-options policy-statement send-direct term 1]
user@R4# set from protocol direct
user@R4# set then accept
```
4. Configure the router ID and autonomous system (AS) number.  

```
[edit routing-options]
user@R4# set autonomous-system 4
user@R4# set router-id 192.168.4.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R4# show interfaces
fe-1/2/0 {
  unit 7 {
    family inet {
      address 24.24.24.4/24;
```

```
    }
  }
}
fe-1/2/1 {
  unit 8 {
    family inet {
      address 34.34.34.4/24;
    }
  }
}
lo0 {
  unit 4 {
    family inet {
      address 192.168.4.1/32;
    }
  }
}

user@R4# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R4# show protocols
bgp {
  group external {
    type external;
    export send-direct;
    peer-as 123;
    neighbor 34.34.34.3;
    neighbor 24.24.24.2;
  }
}

user@R4# show routing-options
autonomous-system 4;
router-id 192.168.4.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

---

### Verification

Confirm that the configuration is working properly.

- [Checking the Active Path From Device R1 to Device R4 on page 72](#)
- [Altering the Local Preference to Change the Path Selection on page 73](#)
- [Rechecking the Active Path From Device R1 to Device R4 on page 73](#)

#### *Checking the Active Path From Device R1 to Device R4*

**Purpose** Verify that the active path from Device R1 to Device R4 goes through Device R2.

**Action** From operational mode, enter the **show route protocol bgp** command.

```
user@R1> show route protocol bgp
inet.0: 11 destinations, 18 routes (11 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

12.12.12.0/24      [BGP/170] 00:11:48, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 12.12.12.2 via fe-1/2/0.1
13.13.13.0/24      [BGP/170] 00:11:48, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 13.13.13.3 via fe-1/2/1.2
24.24.24.0/24      [BGP/170] 00:11:48, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 12.12.12.2 via fe-1/2/0.1
34.34.34.0/24      [BGP/170] 00:11:48, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 13.13.13.3 via fe-1/2/1.2
192.168.2.1/32     [BGP/170] 00:11:48, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 12.12.12.2 via fe-1/2/0.1
192.168.3.1/32     [BGP/170] 00:11:48, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 13.13.13.3 via fe-1/2/1.2
192.168.4.1/32     *[BGP/170] 00:05:14, localpref 100, from 192.168.2.1
                  AS path: 4 I
                  > to 12.12.12.2 via fe-1/2/0.1
                  [BGP/170] 00:05:14, localpref 100, from 192.168.3.1
                  AS path: 4 I
                  > to 13.13.13.3 via fe-1/2/1.2
```

**Meaning** The asterisk (\*) shows that the preferred path is through Device R2. In the default configuration, Device R2 has a lower router ID than Device R3. The router ID is controlling the path selection.

### *Altering the Local Preference to Change the Path Selection*

**Purpose** Change the path so that it goes through Device R3.

**Action** From configuration mode, enter the **set local-preference 300** command.

```
[edit protocols bgp group internal]
user@R3# set local-preference 300
user@R3# commit
```

### *Rechecking the Active Path From Device R1 to Device R4*

**Purpose** Verify that the active path from Device R1 to Device R4 goes through Device R3.

**Action** From operational mode, enter the **show route protocol bgp** command.

```
user@R1> show route protocol bgp
inet.0: 11 destinations, 17 routes (11 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

12.12.12.0/24      [BGP/170] 00:16:48, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 12.12.12.2 via fe-1/2/0.1
13.13.13.0/24      [BGP/170] 00:00:22, localpref 300, from 192.168.3.1
```

```

                AS path: I
                > to 13.13.13.3 via fe-1/2/1.2
24.24.24.0/24   [BGP/170] 00:16:48, localpref 100, from 192.168.2.1
                AS path: I
                > to 12.12.12.2 via fe-1/2/0.1
34.34.34.0/24   [BGP/170] 00:00:22, localpref 300, from 192.168.3.1
                AS path: I
                > to 13.13.13.3 via fe-1/2/1.2
192.168.2.1/32  [BGP/170] 00:16:48, localpref 100, from 192.168.2.1
                AS path: I
                > to 12.12.12.2 via fe-1/2/0.1
192.168.3.1/32  [BGP/170] 00:00:22, localpref 300, from 192.168.3.1
                AS path: I
                > to 13.13.13.3 via fe-1/2/1.2
192.168.4.1/32  * [BGP/170] 00:00:21, localpref 300, from 192.168.3.1
                AS path: 4 I
                > to 13.13.13.3 via fe-1/2/1.2

```

**Meaning** The asterisk (\*) shows that the preferred path is through Device R3. In the altered configuration, Device R3 has a higher local preference than Device R2. The local preference is controlling the path selection.

**Related Documentation**

- [Examples: Configuring Internal BGP Peering on page 36](#)
- [BGP Configuration Overview](#)

## Examples: Configuring BGP MED

- [Understanding the MED Attribute That Determines the Exit Point in an AS on page 74](#)
- [Example: Configuring the MED Attribute That Determines the Exit Point in an AS on page 77](#)
- [Example: Configuring the MED Using Route Filters on page 89](#)
- [Example: Configuring the MED Using Communities on page 102](#)
- [Example: Associating the MED Path Attribute with the IGP Metric and Delaying MED Updates on page 103](#)

### Understanding the MED Attribute That Determines the Exit Point in an AS

The BGP multiple exit discriminator (MED, or MULTI\_EXIT\_DISC) is a non-transitive attribute, meaning that it is not propagated throughout the Internet, but only to adjacent autonomous systems (ASs). The MED attribute is optional, meaning that it is not always sent with the BGP updates. The purpose of MED is to influence how other ASs enter your AS to reach a certain prefix.

The MED attribute has a value that is referred to as a *metric*. If all other factors in determining an exit point are equal, the exit point with the lowest metric is preferred.

If a MED is received over an external BGP link, it is propagated over internal links to other BGP-enabled devices within the AS.

BGP update messages include a MED metric if the route was learned from BGP and already had a MED metric associated with it, or if you configure the MED metric in the configuration file.

A MED metric is advertised with a route according to the following general rules:

- A more specific metric overrides a less specific metric. That is, a group-specific metric overrides a global BGP metric, and a peer-specific metric overrides a global BGP or group-specific metric.
- A metric defined with a routing policy overrides a metric defined with the **metric-out** statement.
- If any metric is defined, it overrides a metric received in a route.
- If the received route does not have an associated MED metric, and if you do not explicitly configure a metric value, no metric is advertised. When you do not explicitly configure a metric value, the MED value is equivalent to zero (0) when advertising an active route.

Because the AS path rather than the number of hops between hosts is the primary criterion for BGP route selection, an AS with multiple connections to a peer AS can have multiple equivalent AS paths. When the routing table contains two routes to the same host in a neighboring AS, a MED metric assigned to each route can determine which to include in the forwarding table. The MED metric you assign can force traffic through a particular exit point in an AS.

Figure 9 on page 75 illustrates how MED metrics are used to determine route selection.

**Figure 9: Default MED Example**




Figure 9 on page 75 shows AS 1 and AS 2 connected by two separate BGP links to Routers C and D. Host E in AS 1 is located nearer to Router C. Host F, also in AS 1, is located nearer to Router D. Because the AS paths are equivalent, two routes exist for each host, one through Router C and one through Router D. To force all traffic destined for Host E through Router C, the network administrator for AS 1 assigns a MED metric for each router to Host E at its exit point. A MED metric of 10 is assigned to the route to Host E through

Router C, and a MED metric of 20 is assigned to the route to Host E through Router D. BGP routers in AS 2 select the route with the lower MED metric for the forwarding table.

By default, only the MEDs of routes that have the same peer ASs are compared. However, you can configure the routing table path selection options listed in [Table 3 on page 76](#) to compare MEDs in different ways. The MED options are not mutually exclusive and can be configured in combination or independently. For the MED options to take effect, you must configure them uniformly all through your network. The MED option or options you configure determine the route selected. Thus we recommend that you carefully evaluate your network for preferred routes before configuring the MED options.

**Table 3: MED Options for Routing Table Path Selection**

| Option (Name)                                                                   | Function                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Use                                                                                                                                                                                                                                            |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Always comparing MEDs ( <b>always-compare-med</b> )                             | Ensures that the MEDs for paths from peers in different ASs are always compared in the route selection process.                                                                                                                                                                                                                                                                                                                                                                                                                      | Useful when all enterprises participating in a network agree on a uniform policy for setting MEDs. For example, in a network shared by two ISPs, both must agree that a certain path is the better path to configure the MED values correctly. |
| Adding IGP cost to MED ( <b>med-plus-igp</b> )                                  | <p>Before comparing MED values for path selection, adds to the MED the cost of the IGP route to the BGP next-hop destination.</p> <p>This option replaces the MED value for the router, but does not affect the IGP metric comparison. As a result, when multiple routes have the same value after the MED-plus-IGP comparison, and route selection continues, the IGP route metric is also compared, even though it was added to the MED value and compared earlier in the selection process.</p>                                   | Useful when the downstream AS requires the complete cost of a certain route that is received across multiple ASs.                                                                                                                              |
| Applying Cisco IOS nondeterministic behavior ( <b>cisco-non-deterministic</b> ) | <p>Specifies the nondeterministic behavior of the Cisco IOS software:</p> <ul style="list-style-type: none"> <li>The active path is always first. All nonactive but eligible paths follow the active path and are maintained in the order in which they were received. Ineligible paths remain at the end of the list.</li> <li>When a new path is added to the routing table, path comparisons are made among all routes, including those paths that must never be selected because they lose the MED tie-breaking rule.</li> </ul> | We recommend that you do not configure this option, because the nondeterministic behavior sometimes prevents the system from properly comparing the MEDs between paths.                                                                        |

## Example: Configuring the MED Attribute That Determines the Exit Point in an AS

This example shows how to configure a multiple exit discriminator (MED) metric to advertise in BGP update messages.

- [Requirements on page 77](#)
- [Overview on page 77](#)
- [Configuration on page 78](#)
- [Verification on page 88](#)

### Requirements

No special configuration beyond device initialization is required before you configure this example.

### Overview

To directly configure a MED metric to advertise in BGP update messages, include the **metric-out** statement:

**metric-out** (*metric* | *minimum-igp offset* | *igp delay-med-update* | *offset*);

**metric** is the primary metric on all routes sent to peers. It can be a value in the range from 0 through 4,294,967,295 ( $2^{32} - 1$ ).


The following optional settings are also supported:

- **minimum-igp**—Sets the metric to the minimum metric value calculated in the interior gateway protocol (IGP) to get to the BGP next hop. If a newly calculated metric is greater than the minimum metric value, the metric value remains unchanged. If a newly calculated metric is lower, the metric value is lowered to that value.
- **igp**—Sets the metric to the most recent metric value calculated in the IGP to get to the BGP next hop.
- **delay-med-update**—Delays sending MED updates when the MED value increases. Include the **delay-med-update** statement when you configure the **igp** statement. The default interval to delay sending updates, unless the MED is lower or another attribute associated with the route has changed is 10 minutes. Include the **med-igp-update-interval minutes** statement at the **[edit routing-options]** hierarchy level to modify the default interval.
- **offset**—Specifies a value for **offset** to increase or decrease the metric that is used from the metric value calculated in the IGP. The metric value is offset by the value specified. The metric calculated in the IGP (by specifying either **igp** or **igp-minimum**) is increased if the **offset** value is positive. The metric calculated in the IGP (by specifying either **igp** or **igp-minimum**) is decreased if the **offset** value is negative.

**offset** can be a value in the range from  $-2^{31}$  through  $2^{31} - 1$ . Note that the adjusted metric can never go below 0 or above  $2^{32} - 1$ .

Figure 10 on page 78 shows a typical network with internal peer sessions and multiple exit points to a neighboring autonomous system (AS).

Figure 10: Typical Network with IBGP Sessions and Multiple Exit Points



8041151

Device R4 has multiple loopback interfaces configured to simulate advertised prefixes. The extra loopback interface addresses are 44.44.44.44/32 and 144.144.144.144/32. This example shows how to configure Device R4 to advertise a MED value of 30 to Device R3 and a MED value of 20 to Device R2. This causes all of the devices in AS 123 to prefer the path through Device R2 to reach AS 4.

### Configuration

- [Configuring Device R1 on page 80](#)
- [Configuring Device R2 on page 82](#)
- [Configuring Device R3 on page 84](#)
- [Configuring Device R4 on page 86](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

#### Device R1

```
set interfaces fe-1/2/0 unit 1 family inet address 12.12.12.1/24
set interfaces fe-1/2/1 unit 2 family inet address 13.13.13.1/24
set interfaces lo0 unit 1 family inet address 192.168.1.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.1.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.2.1
set protocols bgp group internal neighbor 192.168.3.1
set protocols ospf area 0.0.0.0 interface lo0.1 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.1
set protocols ospf area 0.0.0.0 interface fe-1/2/1.2
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
```



```
set routing-options autonomous-system 123
set routing-options router-id 192.168.1.1
```

**Device R2**

```
set interfaces fe-1/2/0 unit 3 family inet address 12.12.12.2/24
set interfaces fe-1/2/1 unit 4 family inet address 24.24.24.2/24
set interfaces lo0 unit 2 family inet address 192.168.2.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.2.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.1.1
set protocols bgp group internal neighbor 192.168.3.1
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 4
set protocols bgp group external neighbor 24.24.24.4
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.3
set protocols ospf area 0.0.0.0 interface fe-1/2/1.4
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.2.1
```

**Device R3**

```
set interfaces fe-1/2/0 unit 5 family inet address 13.13.13.3/24
set interfaces fe-1/2/1 unit 6 family inet address 34.34.34.3/24
set interfaces lo0 unit 3 family inet address 192.168.3.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.3.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.1.1
set protocols bgp group internal neighbor 192.168.2.1
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 4
set protocols bgp group external neighbor 34.34.34.4
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.5
set protocols ospf area 0.0.0.0 interface fe-1/2/1.6
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.3.1
```

**Device R4**

```
set interfaces fe-1/2/0 unit 7 family inet address 24.24.24.4/24
set interfaces fe-1/2/1 unit 8 family inet address 34.34.34.4/24
set interfaces lo0 unit 4 family inet address 192.168.4.1/32
set interfaces lo0 unit 4 family inet address 44.44.44.44/32
set interfaces lo0 unit 4 family inet address 144.144.144.144/32
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 123
set protocols bgp group external neighbor 34.34.34.3 metric-out 30
set protocols bgp group external neighbor 24.24.24.2 metric-out 20
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
```

```
set routing-options autonomous-system 4
set routing-options router-id 192.168.4.1
```

### *Configuring Device R1*

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.

```
[edit interfaces fe-1/2/0 unit 1]
user@R1# set family inet address 12.12.12.1/24
```

```
[edit interfaces fe-1/2/1 unit 2]
user@R1# set family inet address 13.13.13.1/24
```

```
[edit interfaces lo0 unit 1]
user@R1# set family inet address 192.168.1.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]
user@R1# set type internal
user@R1# set local-address 192.168.1.1
user@R1# set export send-direct
user@R1# set neighbor 192.168.2.1
user@R1# set neighbor 192.168.3.1
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R1# set interface lo0.1 passive
user@R1# set interface fe-1/2/0.1
user@R1# set interface fe-1/2/1.2
```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R1# set from protocol direct
user@R1# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R1# set autonomous-system 123
user@R1# set router-id 192.168.1.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-1/2/0 {
  unit 1 {
    family inet {
      address 12.12.12.1/24;
    }
  }
}
fe-1/2/1 {
  unit 2 {
    family inet {
      address 13.13.13.1/24;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.1.1/32;
    }
  }
}

user@R1# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R1# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.1.1;
    export send-direct;
    neighbor 192.168.2.1;
    neighbor 192.168.3.1;
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.1 {
      passive;
    }
    interface fe-1/2/0.1;
    interface fe-1/2/1.2;
  }
}

user@R1# show routing-options
autonomous-system 123;
router-id 192.168.1.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R2

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R2:

1. Configure the interfaces.

```
[edit interfaces fe-1/2/0 unit 3]  
user@R2# set family inet address 12.12.12.21/24
```

```
[edit interfaces fe-1/2/1 unit 4]  
user@R2# set family inet address 24.24.24.2/24
```

```
[edit interfaces lo0 unit 2]  
user@R2# set family inet address 192.168.2.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]  
user@R2# set type internal  
user@R2# set local-address 192.168.2.1  
user@R2# set export send-direct  
user@R2# set neighbor 192.168.1.1  
user@R2# set neighbor 192.168.3.1
```

```
[edit protocols bgp group external]  
user@R2# set type external  
user@R2# set export send-direct  
user@R2# set peer-as 4  
user@R2# set neighbor 24.24.24.4
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]  
user@R2# set interface lo0.2 passive  
user@R2# set interface fe-1/2/0.3  
user@R2# set interface fe-1/2/1.4
```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]  
user@R2# set from protocol direct  
user@R2# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]  
user@R2# set autonomous-system 123  
user@R2# set router-id 192.168.2.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R2# show interfaces
fe-1/2/0 {
  unit 3 {
    family inet {
      address 12.12.12.2/24;
    }
  }
}
fe-1/2/1 {
  unit 4 {
    family inet {
      address 24.24.24.2/24;
    }
  }
}
lo0 {
  unit 2 {
    family inet {
      address 192.168.2.1/32;
    }
  }
}
}

user@R2# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R2# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.2.1;
    export send-direct;
    neighbor 192.168.1.1;
    neighbor 192.168.3.1;
  }
  group external {
    type external;
    export send-direct;
    peer-as 4;
    neighbor 24.24.24.4;
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.2 {
      passive;
    }
  }
}

```

```
}
interface fe-1/2/0.3;
interface fe-1/2/1.4;
}
}

user@R2# show routing-options
autonomous-system 123;
router-id 192.168.2.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

### **Configuring Device R3**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R3:

1. Configure the interfaces.

```
[edit interfaces fe-1/2/0 unit 5]
user@R3# set family inet address 13.13.13.3/24
```

```
[edit interfaces fe-1/2/1 unit 6]
user@R3# set family inet address 34.34.34.3/24
```

```
[edit interfaces lo0 unit 3]
user@R3# set family inet address 192.168.3.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]
user@R3# set type internal
user@R3# set local-address 192.168.3.1
user@R3# set export send-direct
user@R3# set neighbor 192.168.1.1
user@R3# set neighbor 192.168.2.1
```

```
[edit protocols bgp group external]
user@R3# set type external
user@R3# set export send-direct
user@R3# set peer-as 4
user@R3# set neighbor 34.34.34.4
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R3# set interface lo0.3 passive
user@R3# set interface fe-1/2/0.5
user@R3# set interface fe-1/2/1.6
```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R3# set from protocol direct
user@R3# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R3# set autonomous-system 123
user@R3# set router-id 192.168.3.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R3# show interfaces
fe-1/2/0 {
  unit 5 {
    family inet {
      address 13.13.13.3/24;
    }
  }
}
fe-1/2/1 {
  unit 6 {
    family inet {
      address 34.34.34.3/24;
    }
  }
}
lo0 {
  unit 3 {
    family inet {
      address 192.168.3.1/32;
    }
  }
}

user@R3# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R3# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.3.1;
    export send-direct;
    neighbor 192.168.1.1;
    neighbor 192.168.2.1;
  }
  group external {
```

```

        type external;
        export send-direct;
        peer-as 4;
        neighbor 34.34.34.4;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.3 {
            passive;
        }
        interface fe-1/2/0.5;
        interface fe-1/2/1.6;
    }
}

user@R3# show routing-options
autonomous-system 123;
router-id 192.168.3.1;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R4

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R4:

1. Configure the interfaces.

```

[edit interfaces fe-1/2/0 unit 7]
user@R4# set family inet address 24.24.24.4/24

```

```

[edit interfaces fe-1/2/1 unit 8]
user@R4# set family inet address 34.34.34.4/24

```

```

[edit interfaces lo0 unit 4]
user@R4# set family inet address 192.168.4.1/32
user@R4# set family inet address 44.44.44.44/32
user@R4# set family inet address 144.144.144.144/32

```

Device R4 has multiple loopback interface addresses to simulate advertised prefixes.

2. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```

[edit policy-options policy-statement send-direct term 1]
user@R4# set from protocol direct
user@R4# set then accept

```

3. Configure BGP.

```

[edit protocols bgp group external]
user@R4# set type external

```



```
user@R4# set export send-direct
user@R4# set peer-as 123
```

4. Configure a MED value of 30 for neighbor Device R3, and a MED value of 20 for neighbor Device R2.

```
[edit protocols bgp group external]
user@R4# set neighbor 34.34.34.3 metric-out 30
user@R4# set neighbor 24.24.24.2 metric-out 20
```

This configuration causes autonomous system (AS) 123 (of which Device R1, Device R2, and Device R3 are members) to prefer the path through Device R2 to reach AS 4.

5. Configure the router ID and AS number.

```
[edit routing-options]
user@R4# set autonomous-system 4
user@R4# set router-id 192.168.4.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R4# show interfaces
fe-1/2/0 {
  unit 7 {
    family inet {
      address 24.24.24.4/24;
    }
  }
}
fe-1/2/1 {
  unit 8 {
    family inet {
      address 34.34.34.4/24;
    }
  }
}
lo0 {
  unit 4 {
    family inet {
      address 192.168.4.1/32;
      address 44.44.44.44/32;
      address 144.144.144.144/32;
    }
  }
}

user@R4# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}
```

```

user@R4# show protocols
bgp {
  group external {
    type external;
    export send-direct;
    peer-as 123;
    neighbor 34.34.34.3 {
      metric-out 30;
    }
    neighbor 24.24.24.2 {
      metric-out 20;
    }
  }
}

user@R4# show routing-options
autonomous-system 4;
router-id 192.168.4.1;

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Checking the Active Path From Device R1 to Device R4 on page 88](#)
- [Verifying That Device R4 Is Sending Its Routes Correctly on page 89](#)

### *Checking the Active Path From Device R1 to Device R4*

**Purpose** Verify that the active path goes through Device R2.

**Action** From operational mode, enter the **show route protocol bgp** command.

```

user@R1> show route protocol bgp
inet.0: 13 destinations, 19 routes (13 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

12.12.12.0/24      [BGP/170] 3d 22:52:38, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 12.12.12.2 via fe-1/2/0.1
13.13.13.0/24      [BGP/170] 3d 03:15:16, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 13.13.13.3 via fe-1/2/1.2
24.24.24.0/24      [BGP/170] 3d 22:52:38, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 12.12.12.2 via fe-1/2/0.1
34.34.34.0/24      [BGP/170] 3d 03:15:16, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 13.13.13.3 via fe-1/2/1.2
44.44.44.44/32     *[BGP/170] 01:41:11, MED 20, localpref 100, from 192.168.2.1
                  AS path: 4 I
                  > to 12.12.12.2 via fe-1/2/0.1
144.144.144.144/32 *[BGP/170] 00:08:13, MED 20, localpref 100, from 192.168.2.1
                  AS path: 4 I
                  > to 12.12.12.2 via fe-1/2/0.1
192.168.2.1/32     [BGP/170] 3d 22:52:38, localpref 100, from 192.168.2.1
                  AS path: I

```

```

192.168.3.1/32      > to 12.12.12.2 via fe-1/2/0.1
                  [BGP/170] 3d 03:15:16, localpref 100, from 192.168.3.1
                  AS path: I
192.168.4.1/32      > to 13.13.13.3 via fe-1/2/1.2
                  *[BGP/170] 01:41:11, MED 20, localpref 100, from 192.168.2.1
                  AS path: 4 I
                  > to 12.12.12.2 via fe-1/2/0.1

```

**Meaning** The asterisk (\*) shows that the preferred path is through Device R2. The reason for the path selection is listed as MED 20.

### *Verifying That Device R4 Is Sending Its Routes Correctly*

**Purpose** Make sure that Device R4 is sending update messages with a value of 20 to Device R2 and a value of 30 to Device R3.

**Action** From operational mode, enter the **show route advertising-protocol bgp 24.24.24.2** command.

```

user@R4> show route advertising-protocol bgp 24.24.24.2
inet.0: 11 destinations, 13 routes (11 active, 0 holddown, 0 hidden)
  Prefix            Nexthop          MED      Lclpref  AS path
* 24.24.24.0/24      Self              20             I
* 34.34.34.0/24      Self              20             I
* 44.44.44.44/32     Self              20             I
* 144.144.144.144/32 Self              20             I
* 192.168.4.1/32     Self              20             I

user@R4> show route advertising-protocol bgp 34.34.34.3
inet.0: 11 destinations, 13 routes (11 active, 0 holddown, 0 hidden)
  Prefix            Nexthop          MED      Lclpref  AS path
* 24.24.24.0/24      Self              30             I
* 34.34.34.0/24      Self              30             I
* 44.44.44.44/32     Self              30             I
* 144.144.144.144/32 Self              30             I
* 192.168.4.1/32     Self              30             I

```

**Meaning** The MED column shows that Device R4 is sending the correct MED values to its two external BGP (EBGP) neighbors.

## Example: Configuring the MED Using Route Filters

This example shows how to configure a policy that uses route filters to modify the multiple exit discriminator (MED) metric to advertise in BGP update messages.

- [Requirements on page 89](#)
- [Overview on page 90](#)
- [Configuration on page 90](#)
- [Verification on page 101](#)

### Requirements


No special configuration beyond device initialization is required before you configure this example.

## Overview

To configure a route-filter policy that modifies the advertised MED metric in BGP update messages, include the **metric** statement in the policy action.

Figure 11 on page 90 shows a typical network with internal peer sessions and multiple exit points to a neighboring autonomous system (AS).

Figure 11: Typical Network with IBGP Sessions and Multiple Exit Points



Device R4 has multiple loopback interfaces configured to simulate advertised prefixes. The extra loopback interface addresses are 172.16.44.0/32 and 172.16.144.0/32. This example shows how to configure Device R4 to advertise a MED value of 30 to Device R3 for all routes except 172.16.144.0. For 172.16.144.0, a MED value of 10 is advertised to Device 3. A MED value of 20 is advertised to Device R2, regardless of the route prefix.

## Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
Device R1
set interfaces fe-1/2/0 unit 1 family inet address 172.16.12.1/24
set interfaces fe-1/2/1 unit 2 family inet address 172.16.13.1/24
set interfaces lo0 unit 1 family inet address 192.168.1.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.1.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.2.1
set protocols bgp group internal neighbor 192.168.3.1
set protocols ospf area 0.0.0.0 interface lo0.1 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.1
```

```

set protocols ospf area 0.0.0.0 interface fe-1/2/1.2
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.1.1

```

Device R2

```

set interfaces fe-1/2/0 unit 3 family inet address 172.16.12.2/24
set interfaces fe-1/2/1 unit 4 family inet address 172.16.24.2/24
set interfaces lo0 unit 2 family inet address 192.168.2.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.2.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.1.1
set protocols bgp group internal neighbor 192.168.3.1
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 4
set protocols bgp group external neighbor 172.16.24.4
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.3
set protocols ospf area 0.0.0.0 interface fe-1/2/1.4
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.2.1

```

Device R3

```

set interfaces fe-1/2/0 unit 5 family inet address 172.16.13.3/24
set interfaces fe-1/2/1 unit 6 family inet address 172.16.34.3/24
set interfaces lo0 unit 3 family inet address 192.168.3.1/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.3.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.1.1
set protocols bgp group internal neighbor 192.168.2.1
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 4
set protocols bgp group external neighbor 172.16.34.4
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.5
set protocols ospf area 0.0.0.0 interface fe-1/2/1.6
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 123
set routing-options router-id 192.168.3.1

```

Device R4

```

set interfaces fe-1/2/0 unit 7 family inet address 172.16.24.4/24
set interfaces fe-1/2/1 unit 8 family inet address 172.16.34.4/24
set interfaces lo0 unit 4 family inet address 192.168.4.1/32
set interfaces lo0 unit 4 family inet address 172.16.44.0/32
set interfaces lo0 unit 4 family inet address 172.16.144.0/32
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 123
set protocols bgp group external neighbor 172.16.34.3 export med-10

```

```
set protocols bgp group external neighbor 172.16.34.3 export med-30
set protocols bgp group external neighbor 172.16.24.2 metric-out 20
set policy-options policy-statement med-10 from route-filter 172.16.144.0/32 exact
set policy-options policy-statement med-10 then metric 10
set policy-options policy-statement med-10 then accept
set policy-options policy-statement med-30 from route-filter 0.0.0.0/0 longer
set policy-options policy-statement med-30 then metric 30
set policy-options policy-statement med-30 then accept
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 4
set routing-options router-id 192.168.4.1
```

### *Configuring Device R1*

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the device interfaces.

```
[edit interfaces fe-1/2/0 unit 1]
user@R1# set family inet address 172.16.12.1/24
```

```
[edit interfaces fe-1/2/1 unit 2]
user@R1# set family inet address 172.16.13.1/24
```

```
[edit interfaces lo0 unit 1]
user@R1# set family inet address 192.168.1.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]
user@R1# set type internal
user@R1# set local-address 192.168.1.1
user@R1# set export send-direct
user@R1# set neighbor 192.168.2.1
user@R1# set neighbor 192.168.3.1
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R1# set interface lo0.1 passive
user@R1# set interface fe-1/2/0.1
user@R1# set interface fe-1/2/1.2
```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R1# set from protocol direct
user@R1# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R1# set autonomous-system 123
user@R1# set router-id 192.168.1.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-1/2/0 {
  unit 1 {
    family inet {
      address 172.16.12.1/24;
    }
  }
}
fe-1/2/1 {
  unit 2 {
    family inet {
      address 172.16.13.1/24;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.1.1/32;
    }
  }
}

user@R1# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.1.1;
    export send-direct;
    neighbor 192.168.2.1;
    neighbor 192.168.3.1;
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.1 {
      passive;
    }
    interface fe-1/2/0.1;
    interface fe-1/2/1.2;
  }
}

user@R1# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
```

```
        then accept;
    }
}

user@R1# show routing-options
autonomous-system 123;
router-id 192.168.1.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

### **Configuring Device R2**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R2:

1. Configure the device interfaces.

```
[edit interfaces fe-1/2/0 unit 3]
user@R2# set family inet address 172.16.12.21/24
```

```
[edit interfaces fe-1/2/1 unit 4]
user@R2# set family inet address 172.16.24.2/24
```

```
[edit interfaces lo0 unit 2]
user@R2# set family inet address 192.168.2.1/32
```

2. Configure BGP.

```
[edit protocols bgp group internal]
user@R2# set type internal
user@R2# set local-address 192.168.2.1
user@R2# set export send-direct
user@R2# set neighbor 192.168.1.1
user@R2# set neighbor 192.168.3.1
```

```
[edit protocols bgp group external]
user@R2# set type external
user@R2# set export send-direct
user@R2# set peer-as 4
user@R2# set neighbor 172.16.24.4
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R2# set interface lo0.2 passive
user@R2# set interface fe-1/2/0.3
user@R2# set interface fe-1/2/1.4
```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R2# set from protocol direct
```



```
user@R2# set then accept
```

5. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R2# set autonomous-system 123
user@R2# set router-id 192.168.2.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
fe-1/2/0 {
  unit 3 {
    family inet {
      address 172.16.12.2/24;
    }
  }
}
fe-1/2/1 {
  unit 4 {
    family inet {
      address 172.16.24.2/24;
    }
  }
}
lo0 {
  unit 2 {
    family inet {
      address 192.168.2.1/32;
    }
  }
}
```

```
user@R2# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.2.1;
    export send-direct;
    neighbor 192.168.1.1;
    neighbor 192.168.3.1;
  }
  group external {
    type external;
    export send-direct;
    peer-as 4;
    neighbor 172.16.24.4;
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.2 {
      passive;
    }
  }
}
```

```
    }  
    interface fe-1/2/0.3;  
    interface fe-1/2/1.4;  
  }  
}  
  
user@R2# show policy-options  
policy-statement send-direct {  
  term 1 {  
    from protocol direct;  
    then accept;  
  }  
}  
  
user@R2# show routing-options  
autonomous-system 123;  
router-id 192.168.2.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

### ***Configuring Device R3***

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R3:

1. Configure the device interfaces.  
  
[edit interfaces fe-1/2/0 unit 5]  
user@R3# set family inet address 172.16.13.3/24  
  
[edit interfaces fe-1/2/1 unit 6]  
user@R3# set family inet address 172.16.34.3/24  
  
[edit interfaces lo0 unit 3]  
user@R3# set family inet address 192.168.3.1/32
2. Configure BGP.  
  
[edit protocols bgp group internal]  
user@R3# set type internal  
user@R3# set local-address 192.168.3.1  
user@R3# set export send-direct  
user@R3# set neighbor 192.168.1.1  
user@R3# set neighbor 192.168.2.1  
  
[edit protocols bgp group external]  
user@R3# set type external  
user@R3# set export send-direct  
user@R3# set peer-as 4  
user@R3# set neighbor 172.16.34.4
3. Configure OSPF.  
  
[edit protocols ospf area 0.0.0.0]

```

user@R3# set interface lo0.3 passive
user@R3# set interface fe-1/2/0.5
user@R3# set interface fe-1/2/1.6

```

4. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```

[edit policy-options policy-statement send-direct term 1]
user@R3# set from protocol direct
user@R3# set then accept

```

5. Configure the router ID and autonomous system (AS) number.

```

[edit routing-options]
user@R3# set autonomous-system 123
user@R3# set router-id 192.168.3.1

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R3# show interfaces
fe-1/2/0 {
  unit 5 {
    family inet {
      address 172.16.13.3/24;
    }
  }
}
fe-1/2/1 {
  unit 6 {
    family inet {
      address 172.16.34.3/24;
    }
  }
}
lo0 {
  unit 3 {
    family inet {
      address 192.168.3.1/32;
    }
  }
}

```

```

user@R3# show protocols
bgp {
  group internal {
    type internal;
    local-address 192.168.3.1;
    export send-direct;
    neighbor 192.168.1.1;
    neighbor 192.168.2.1;
  }
  group external {

```

```

        type external;
        export send-direct;
        peer-as 4;
        neighbor 172.16.34.4;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.3 {
            passive;
        }
        interface fe-1/2/0.5;
        interface fe-1/2/1.6;
    }
}

user@R3# show policy-options
policy-statement send-direct {
    term 1 {
        from protocol direct;
        then accept;
    }
}

user@R3# show routing-options
autonomous-system 123;
router-id 192.168.3.1;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R4

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R4:

1. Configure the device interfaces.

```

[edit interfaces fe-1/2/0 unit 7]
user@R4# set family inet address 172.16.24.4/24

```

```

[edit interfaces fe-1/2/1 unit 8]
user@R4# set family inet address 172.16.34.4/24

```

```

[edit interfaces lo0 unit 4]
user@R4# set family inet address 192.168.4.1/32
user@R4# set family inet address 172.16.44.0/32
user@R4# set family inet address 172.16.144.0/32

```

Device R4 has multiple loopback interface addresses to simulate advertised prefixes.

2. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R4# set from protocol direct
user@R4# set then accept
```

3. Configure BGP.

```
[edit protocols bgp group external]
user@R4# set type external
user@R4# set export send-direct
user@R4# set peer-as 123
```

4. Configure the two MED policies.

```
[edit policy-options]
set policy-statement med-10 from route-filter 172.16.144.0/32 exact
set policy-statement med-10 then metric 10
set policy-statement med-10 then accept

set policy-statement med-30 from route-filter 0.0.0.0/0 longer
set policy-statement med-30 then metric 30
set policy-statement med-30 then accept
```

5. Configure the two EBGP neighbors, applying the two MED policies to Device R3, and a MED value of 20 to Device R2.

```
[edit protocols bgp group external]
user@R4# set neighbor 172.16.34.3 export med-10
user@R4# set neighbor 172.16.34.3 export med-30
user@R4# set neighbor 172.16.24.2 metric-out 20
```

6. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R4# set autonomous-system 4
user@R4# set router-id 192.168.4.1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R4# show interfaces
fe-1/2/0 {
  unit 7 {
    family inet {
      address 172.16.24.4/24;
    }
  }
}
fe-1/2/1 {
  unit 8 {
    family inet {
      address 172.16.34.4/24;
    }
  }
}
lo0 {
```

```
unit 4 {
  family inet {
    address 192.168.4.1/32;
    address 172.16.44.0/32;
    address 172.16.144.0/32;
  }
}

user@R4# show protocols
bgp {
  group external {
    type external;
    export send-direct;
    peer-as 123;
    neighbor 172.16.24.2 {
      metric-out 20;
    }
    neighbor 172.16.34.3 {
      export [ med-10 med-30 ];
    }
  }
}

user@R4# show policy-options
policy-statement med-10 {
  from {
    route-filter 172.16.144.0/32 exact;
  }
  then {
    metric 10;
    accept;
  }
}
policy-statement med-30 {
  from {
    route-filter 0.0.0.0/0 longer;
  }
  then {
    metric 30;
    accept;
  }
}
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R4# show routing-options
autonomous-system 4;
router-id 192.168.4.1;
```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Checking the Active Path from Device R1 to Device R4 on page 101](#)
- [Verifying That Device R4 Is Sending Its Routes Correctly on page 101](#)

### *Checking the Active Path from Device R1 to Device R4*

**Purpose** Verify that the active path goes through Device R2.

**Action** From operational mode, enter the **show route protocol bgp** command.

```
user@R1> show route protocol bgp
inet.0: 13 destinations, 19 routes (13 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

172.16.12.0/24      [BGP/170] 4d 01:13:32, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 172.16.12.2 via fe-1/2/0.1
172.16.13.0/24      [BGP/170] 3d 05:36:10, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 172.16.13.3 via fe-1/2/1.2
172.16.24.0/24      [BGP/170] 4d 01:13:32, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 172.16.12.2 via fe-1/2/0.1
172.16.34.0/24      [BGP/170] 3d 05:36:10, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 172.16.13.3 via fe-1/2/1.2
172.16.44.0/32      *[BGP/170] 00:06:03, MED 20, localpref 100, from 192.168.2.1
                  AS path: 4 I
                  > to 172.16.12.2 via fe-1/2/0.1
172.16.144.0/32    *[BGP/170] 00:06:03, MED 10, localpref 100, from 192.168.3.1
                  AS path: 4 I
                  > to 172.16.13.3 via fe-1/2/1.2
192.168.2.1/32      [BGP/170] 4d 01:13:32, localpref 100, from 192.168.2.1
                  AS path: I
                  > to 172.16.12.2 via fe-1/2/0.1
192.168.3.1/32      [BGP/170] 3d 05:36:10, localpref 100, from 192.168.3.1
                  AS path: I
                  > to 172.16.13.3 via fe-1/2/1.2
192.168.4.1/32      *[BGP/170] 00:06:03, MED 20, localpref 100, from 192.168.2.1
                  AS path: 4 I
                  > to 172.16.12.2 via fe-1/2/0.1
```

**Meaning** The output shows that the preferred path to the routes advertised by Device R4 is through Device R2 for all routes except 172.16.144.0/32. For 172.16.144.0/32, the preferred path is through Device R3.

### *Verifying That Device R4 Is Sending Its Routes Correctly*

**Purpose** Make sure that Device R4 is sending update messages with a value of 20 to Device R2 and a value of 30 to Device R3.

**Action** From operational mode, enter the **show route advertising-protocol bgp** command.

```
user@R4> show route advertising-protocol bgp 172.16.24.2
```

```
inet.0: 11 destinations, 13 routes (11 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED      Lclpref    AS path
* 172.16.24.0/24        Self                20
* 172.16.34.0/24        Self                20
* 172.16.44.0/32        Self                20
* 172.16.144.0/32       Self                20          I
* 192.168.4.1/32        Self                20          I
```

```
user@R4> show route advertising-protocol bgp 172.16.34.3
inet.0: 11 destinations, 13 routes (11 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED      Lclpref    AS path
* 172.16.24.0/24        Self                30
* 172.16.34.0/24        Self                30
* 172.16.44.0/32        Self                30
* 172.16.144.0/32       Self                10          I
* 192.168.4.1/32        Self                30          I
```

**Meaning** The MED column shows that Device R4 is sending the correct MED values to its two EBGp neighbors.

### Example: Configuring the MED Using Communities

Set the multiple exit discriminator (MED) metric to 20 for all routes from a particular community.

```
[edit]
routing-options {
  router-id 10.0.0.1;
  autonomous-system 23;
}
policy-options {
  policy-statement from-otago {
    from community otago;
    then metric 20;
  }
  community otago members [56:2379 23:46944];
}
protocols {
  bgp {
    import from-otago;
    group 23 {
      type external;
      peer-as 56;
      neighbor 192.168.0.1 {
        traceoptions {
          file bgp-log-peer;
          flag packets;
        }
        log-updown;
      }
    }
  }
}
```



## Example: Associating the MED Path Attribute with the IGP Metric and Delaying MED Updates

This example shows how to associate the multiple exit discriminator (MED) path attribute with the interior gateway protocol (IGP) metric, and configure a timer to delay update of the MED attribute.

- [Requirements on page 103](#)
- [Overview on page 103](#)
- [Configuration on page 105](#)
- [Verification on page 111](#)

### Requirements

No special configuration beyond device initialization is required before you configure this example.

### Overview

BGP can be configured to advertise the MED attribute for a route based on the IGP distance of its internal BGP (IBGP) route next-hop. The IGP metric enables internal routing to follow the shortest path according to the administrative setup. In some deployments, it might be ideal to communicate IGP shortest-path knowledge to external BGP (EBGP) peers in a neighboring autonomous system (AS). This allows those EBGP peers to forward traffic into your AS using the shortest paths possible.

Routes learned from an EBGP peer usually have a next hop on a directly connected interface, and thus the IGP value is equal to zero. Zero is the value advertised. The IGP metric is a nonzero value when a BGP peer sends third-party next hops that require the local system to perform next-hop resolution—IBGP configurations, configurations within confederation peers, or EBGP configurations that include the **multihop** command. In these scenarios, it might make sense to associate the MED value with the IGP metric by including the **metric-out minimum-igp** or **metric-out igp** option.

The drawback of associating the MED with the IGP metric is the risk of excessive route advertisements when there are IGP instabilities in the network. Configuring a delay for the MED update provides a mechanism to reduce route advertisements in such scenarios. The delay works by slowing down MED updates when the IGP metric for the next hop changes. The approach uses a timer to periodically advertise MED updates. When the timer expires, the MED attribute for routes with **metric-out igp delay-updates** configured is updated to the current IGP metric of the next hop. The BGP-enabled device sends out advertisements for routes for which the MED attribute has changed.

The **delay-updates** option identifies the BGP groups (or peers) for which the MED updates must be suppressed. The time for advertising MED updates is set to 10 minutes by default. You can increase the interval up to 600 minutes by including the **med-igp-update-interval** statement in the **routing-options** configuration.



.....

**NOTE:** If you have nonstop active routing (NSR) enabled and a switchover occurs, the delayed MED updates might be advertised as soon as the switchover occurs.

.....


When you configure the **metric-out igp** option, the IGP metric directly tracks the IGP cost to the IBGP peer. When the IGP cost goes down, so does the advertised MED value. Conversely, when the IGP cost goes up, the MED value goes up as well.

When you configure the **metric-out minimum-igp** option, the advertised MED value changes only when the IGP cost to the IBGP peer goes down. An increase in the IGP cost does not affect the MED value. The router monitors and remembers the lowest IGP cost until the routing process (rpd) is restarted. The BGP peer sends an update only if the MED is lower than the previously advertised value or another attribute associated with the route has changed, or if the BGP peer is responding to a refresh route request.

This example uses the **metric** statement in the OSPF configuration to demonstrate that when the IGP metric changes, the MED also changes after the configured delay interval. The OSPF metric can range from 1 through 65,535.

[Figure 12 on page 105](#) shows the sample topology.

Figure 12: Topology for Delaying the MED Update



In this example, the MED value advertised by Device R1 is associated with the IGP running in AS 1. The MED value advertised by Device R1 impacts the decisions of the neighboring AS (AS 2) when AS 2 is forwarding traffic into AS 1.

### Configuration

- [Configuring Device R1 on page 109](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

#### Device R1

```
set interfaces fe-1/2/0 unit 2 description R1->R2
set interfaces fe-1/2/0 unit 2 family inet address 10.0.0.1/30
set interfaces fe-1/2/1 unit 7 description R1->R4
set interfaces fe-1/2/1 unit 7 family inet address 172.16.0.1/30
set interfaces lo0 unit 1 family inet address 192.168.0.1/32
```

```
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.1
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.2
set protocols bgp group internal neighbor 192.168.0.3
set protocols bgp group external type external
set protocols bgp group external metric-out igp delay-med-update
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 2
set protocols bgp group external neighbor 172.16.0.2
set protocols ospf area 0.0.0.0 interface fe-1/2/0.2 metric 600
set protocols ospf area 0.0.0.0 interface lo0.1 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options med-igp-update-interval 12
set routing-options router-id 192.168.0.1
set routing-options autonomous-system 1
```

**Device R2**

```
set interfaces fe-1/2/0 unit 1 description R2->R1
set interfaces fe-1/2/0 unit 1 family inet address 10.0.0.2/30
set interfaces fe-1/2/1 unit 4 description R2->R3
set interfaces fe-1/2/1 unit 4 family inet address 10.0.2.2/30
set interfaces lo0 unit 2 family inet address 192.168.0.2/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.2
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.1
set protocols bgp group internal neighbor 192.168.0.3
set protocols ospf area 0.0.0.0 interface fe-1/2/0.1
set protocols ospf area 0.0.0.0 interface fe-1/2/1.4
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.2
set routing-options autonomous-system 1
```

**Device R3**

```
set interfaces fe-1/2/0 unit 3 description R3->R2
set interfaces fe-1/2/0 unit 3 family inet address 10.0.2.1/30
set interfaces fe-1/2/1 unit 5 description R3->R5
set interfaces fe-1/2/1 unit 5 family inet address 172.16.0.5/30
set interfaces lo0 unit 3 family inet address 192.168.0.3/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.3
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.1
set protocols bgp group internal neighbor 192.168.0.2
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 2
set protocols bgp group external neighbor 172.16.0.6
set protocols ospf area 0.0.0.0 interface fe-1/2/0.3
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.3
```

```
set routing-options autonomous-system 1
```

**Device R4**

```

set interfaces fe-1/2/0 unit 8 description R4->R1
set interfaces fe-1/2/0 unit 8 family inet address 172.16.0.2/30
set interfaces fe-1/2/1 unit 9 description R4->R5
set interfaces fe-1/2/1 unit 9 family inet address 10.0.4.1/30
set interfaces fe-1/2/2 unit 13 description R4->R6
set interfaces fe-1/2/2 unit 13 family inet address 172.16.0.9/30
set interfaces lo0 unit 4 family inet address 192.168.0.4/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.4
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.5
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external neighbor 172.16.0.10 peer-as 3
set protocols bgp group external neighbor 172.16.0.1 peer-as 1
set protocols ospf area 0.0.0.0 interface fe-1/2/1.9
set protocols ospf area 0.0.0.0 interface lo0.4 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.4
set routing-options autonomous-system 2

```

**Device R5**

```

set interfaces fe-1/2/0 unit 6 description R5->R3
set interfaces fe-1/2/0 unit 6 family inet address 172.16.0.6/30
set interfaces fe-1/2/1 unit 10 description R5->R4
set interfaces fe-1/2/1 unit 10 family inet address 10.0.4.2/30
set interfaces fe-1/2/2 unit 11 description R5->R8
set interfaces fe-1/2/2 unit 11 family inet address 172.16.0.13/30
set interfaces lo0 unit 5 family inet address 192.168.0.5/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.5
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.4
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external neighbor 172.16.0.5 peer-as 1
set protocols bgp group external neighbor 172.16.0.14 peer-as 3
set protocols ospf area 0.0.0.0 interface fe-1/2/1.10
set protocols ospf area 0.0.0.0 interface lo0.5 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.5
set routing-options autonomous-system 2

```

**Device R6**

```

set interfaces fe-1/2/0 unit 14 description R6->R4
set interfaces fe-1/2/0 unit 14 family inet address 172.16.0.10/30
set interfaces fe-1/2/1 unit 15 description R6->R7
set interfaces fe-1/2/1 unit 15 family inet address 10.0.6.1/30
set interfaces lo0 unit 6 family inet address 192.168.0.6/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.6
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.7

```

```
set protocols bgp group internal neighbor 192.168.0.8
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 2
set protocols bgp group external neighbor 172.16.0.9 peer-as 2
set protocols ospf area 0.0.0.0 interface fe-1/2/1.15
set protocols ospf area 0.0.0.0 interface lo0.6 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.6
set routing-options autonomous-system 3
```

Device R7

```
set interfaces fe-1/2/0 unit 16 description R7->R6
set interfaces fe-1/2/0 unit 16 family inet address 10.0.6.2/30
set interfaces fe-1/2/1 unit 17 description R7->R8
set interfaces fe-1/2/1 unit 17 family inet address 10.0.7.2/30
set interfaces lo0 unit 7 family inet address 192.168.0.7/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.7
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.6
set protocols bgp group internal neighbor 192.168.0.8
set protocols ospf area 0.0.0.0 interface fe-1/2/0.16
set protocols ospf area 0.0.0.0 interface fe-1/2/1.17
set protocols ospf area 0.0.0.0 interface lo0.7 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.7
set routing-options autonomous-system 3
```

Device R8

```
set interfaces fe-1/2/0 unit 12 description R8->R5
set interfaces fe-1/2/0 unit 12 family inet address 172.16.0.14/30
set interfaces fe-1/2/1 unit 18 description R8->R7
set interfaces fe-1/2/1 unit 18 family inet address 10.0.7.1/30
set interfaces lo0 unit 8 family inet address 192.168.0.8/32
set protocols bgp group internal type internal
set protocols bgp group internal local-address 192.168.0.8
set protocols bgp group internal export send-direct
set protocols bgp group internal neighbor 192.168.0.6
set protocols bgp group internal neighbor 192.168.0.7
set protocols bgp group external type external
set protocols bgp group external export send-direct
set protocols bgp group external peer-as 2
set protocols bgp group external neighbor 172.16.0.13 peer-as 2
set protocols ospf area 0.0.0.0 interface fe-1/2/1.18
set protocols ospf area 0.0.0.0 interface lo0.8 passive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options router-id 192.168.0.8
set routing-options autonomous-system 3
```

**Configuring Device R1**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.

```
[edit interfaces fe-1/2/0 unit 2]
user@R1# set description R1->R2
user@R1# set family inet address 10.0.0.1/30
```

```
[edit interfaces fe-1/2/1 unit 7]
user@R1# set description R1->R4
user@R1# set family inet address 172.16.0.1/30
```

```
[edit interfaces lo0 unit 1]
user@R1# set family inet address 192.168.0.1/32
```

2. Configure IBGP.

```
[edit protocols bgp group internal]
user@R1# set type internal
user@R1# set local-address 192.168.0.1
user@R1# set export send-direct
user@R1# set neighbor 192.168.0.2
user@R1# set neighbor 192.168.0.3
```

3. Configure EBGP.

```
[edit protocols bgp group external]
user@R1# set type external
user@R1# set export send-direct
user@R1# set peer-as 2
user@R1# set neighbor 172.16.0.2
```

4. Associate the MED value with the IGP metric.

```
[edit protocols bgp group external]
user@R1# set metric-out igp delay-med-update
```

The default for the MED update is 10 minutes when you include the **delay-med-update** option. When you exclude the **delay-med-update** option, the MED update occurs immediately after the IGP metric changes.

5. (Optional) Configure the update interval for the MED update.

```
[edit routing-options]
user@R1# set med-igp-update-interval 12
```

You can configure the interval from 10 minutes through 600 minutes.

6. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@R1# set interface fe-1/2/0.2 metric 600
user@R1# set interface lo0.1 passive
```

The **metric** statement is used here to demonstrate what happens when the IGP metric changes.

7. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 1]
user@R1# set from protocol direct
user@R1# set then accept
```

8. Configure the router ID and autonomous system (AS) number.

```
[edit routing-options]
user@R1# set router-id 192.168.0.1
user@R1# set autonomous-system 1
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-1/2/0 {
  unit 2 {
    description R1->R2;
    family inet {
      address 10.0.0.1/30;
    }
  }
}
fe-1/2/1 {
  unit 7 {
    description R1->R4;
    family inet {
      address 172.16.0.1/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.0.1/32;
    }
  }
}

user@R1# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}

user@R1# show protocols
```



```

bgp {
  group internal {
    type internal;
    local-address 192.168.0.1;
    export send-direct;
    neighbor 192.168.0.2;
    neighbor 192.168.0.3;
  }
  group external {
    type external;
    metric-out igp delay-med-update;
    export send-direct;
    peer-as 2;
    neighbor 172.16.0.2;
  }
}
ospf {
  area 0.0.0.0 {
    interface fe-1/2/0.2 {
      metric 600;
    }
    interface lo0.1 {
      passive;
    }
  }
}

```

```

user@R1# show routing-options
med-igp-update-interval 12;
router-id 192.168.0.1;
autonomous-system 1;

```

If you are done configuring the device, enter **commit** from configuration mode. Repeat the configuration steps on the other devices in the topology, as needed for your network.

## Verification

Confirm that the configuration is working properly.

- [Checking the BGP Advertisements on page 111](#)
- [Verifying That the MED Value Changes When the OSPF Metric Changes on page 112](#)
- [Testing the minimum-igp Setting on page 112](#)

### Checking the BGP Advertisements

**Purpose** Verify that Device R1 is advertising to Device R4 a BGP MED value that reflects the IGP metric.

**Action** From operational mode, enter the **show route advertising-protocol bgp 172.16.0.2** command.

```

user@R1> show route advertising-protocol bgp 172.16.0.2
inet.0: 19 destinations, 33 routes (19 active, 0 holddown, 0 hidden)
  Prefix                Nexthop        MED      Lc1pref  AS path
* 10.0.0.0/30           Self           0         I         I
* 172.16.0.0/30         Self           0         I         I

```

|                  |      |     |   |
|------------------|------|-----|---|
| * 172.16.0.4/30  | Self | 601 | I |
| * 192.168.0.1/32 | Self | 0   | I |

**Meaning** The 601 value in the MED column shows that the MED value has been updated to reflect the configured OSPF metric.

#### *Verifying That the MED Value Changes When the OSPF Metric Changes*

**Purpose** Make sure that when you raise the OSPF metric to 700, the MED value is updated to reflect this change.

**Action** From configuration mode, enter the **set protocols ospf area 0 interface fe-1/2/0.2 metric 700** command.

```
user@R1# set protocols ospf area 0 interface fe-1/2/0.2 metric 700
user@R1# commit
```

After waiting 12 minutes (the configured delay period), enter the **show route advertising-protocol bgp** command from operational mode.

```
user@R1> show route advertising-protocol bgp 172.16.0.2
inet.0: 19 destinations, 33 routes (19 active, 0 holddown, 0 hidden)
  Prefix            Nexthop      MED      Lclpref  AS path
* 10.0.0.0/30       Self         0         I
* 172.16.0.0/30     Self         0         I
* 172.16.0.4/30     Self         701        I
* 192.168.0.1/32    Self         0         I
```

**Meaning** The 701 value in the MED column shows that the MED value has been updated to reflect the configured OSPF metric.

#### *Testing the minimum-igp Setting*

**Purpose** Change the configuration to use the **minimum-igp** statement instead of the **igp** statement. When you increase the OSPF metric, the MED value remains unchanged, but when you decrease the OSPF metric, the MED value reflects the new OSPF metric.

**Action** From configuration mode, delete the **igp** statement, add the **minimum-igp** statement, and increase the OSPF metric.

```
user@R1# delete protocols bgp group external metric-out igp
user@R1# set protocols bgp group external metric-out minimum-igp
user@R1# set protocols ospf area 0 interface fe-1/2/0.2 metric 800
user@R1# commit
```

From operational mode, enter the **show route advertising-protocol bgp** command to make sure that the MED value does not change.

```
user@R1> show route advertising-protocol bgp 172.16.0.2
inet.0: 19 destinations, 33 routes (19 active, 0 holddown, 0 hidden)
  Prefix            Nexthop      MED      Lclpref  AS path
* 10.0.0.0/30       Self         0         I
* 172.16.0.0/30     Self         0         I
* 172.16.0.4/30     Self         701        I
* 192.168.0.1/32    Self         0         I
```

From configuration mode, decrease the OSPF metric.

```
user@R1# set protocols ospf area 0 interface fe-1/2/0.2 metric 20
user@R1# commit
```

From operational mode, enter the **show route advertising-protocol bgp** command to make sure that the MED value does change.

```
user@R1> show route advertising-protocol bgp 172.16.0.2
inet.0: 19 destinations, 33 routes (19 active, 0 holddown, 0 hidden)
  Prefix            Nexthop          MED      Lc1pref    AS path
* 10.0.0.0/30       Self             0         I          I
* 172.16.0.0/30     Self             0         I          I
* 172.16.0.4/30     Self             21        I          I
* 192.168.0.1/32    Self             0         I          I
```

**Meaning** When the **minimum-igp** statement is configured, the MED value changes only when a shorter path is available.

**Related Documentation**

- [Examples: Configuring External BGP Peering on page 13](#)
- [BGP Configuration Overview](#)

## Examples: Configuring BGP Local AS

- [Understanding the BGP Local AS Attribute on page 113](#)
- [Example: Configuring a Local AS for EBGp Sessions on page 118](#)
- [Example: Configuring a Private Local AS for EBGp Sessions on page 128](#)

### Understanding the BGP Local AS Attribute

When an Internet service provider (ISP) acquires a network that belongs to a different autonomous system (AS), there is no seamless method for moving the BGP peers of the acquired network to the AS of the acquiring ISP. The process of configuring the BGP peers with the new AS number can be time-consuming and cumbersome. Sometimes customers do not want to or are not immediately able to modify their peer arrangements or configuration. During this kind of transition period, it can be useful to configure BGP-enabled devices in the new AS to use the former AS number in BGP updates. This former AS number is called a *local AS*.

Using a local AS number permits the routing devices in an acquired network to appear to belong to the former AS.

For example, ISP A, with an AS of 200, acquires ISP B, with an AS of 250. ISP B has a customer, ISP C, that does not want to change its configuration. After ISP B becomes part of ISP A, a local AS number of 250 is configured for use in EBGp peer sessions with ISP C. Consequently, the local AS number of 250 is either prepended before or used instead of the global AS number of 200 in the AS path used to export routes to direct external peers in ISP C.

If the route is received from an internal BGP (IBGP) peer, the AS path includes the local AS number prepended before the global AS number.

The local AS number is used instead of the global AS number if the route is an external route, such as a static route or an interior gateway protocol (IGP) route that is imported into BGP. If the route is external and you want the global AS number to be included in the AS path, you can apply a routing policy that uses **as-path-expand** or **as-path-prepend**. Use the **as-path-expand** policy action to place the global AS number behind the local AS number. Use the **as-path-prepend** policy action to place the global AS number in front of the local AS number.

For example:

```

user@R2# show policy-options
policy-statement prepend-global {
  term 1 {
    from protocol static;
    then {
      as-path-prepend 200; # or use as-path-expand
      accept;
    }
  }
}

user@R2# show protocols bgp
group ext {
  export prepend-global;
  type external;
  local-as 250;
  neighbor 10.0.0.1 {
    peer-as 100;
  }
  neighbor 10.1.0.2 {
    peer-as 300;
  }
}

user@R2# show routing-options
static {
  route 1.1.1.1/32 next-hop 10.0.0.1;
}
autonomous-system 200;

user@R3# run show route 1.1.1.1 protocol bgp
inet.0: 6 destinations, 6 routes (6 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1.1.1.1/32          *[BGP/170] 00:05:11, localpref 100
                   AS path: 200 250 I, validation-state: unverified
                   > to 10.1.0.1 via 1t-1/2/0.4

```

In a Layer 3 VPN scenario, in which a provider edge (PE) device uses external BGP (EBGP) to peer with a customer edge (CE) device, the **local-as** statement behaves differently than in the non-VPN scenario. In the VPN scenario, the global AS number defined in the master instance is prepended to the AS path by default. To override this behavior, you can configure the **no-prepend-global-as** in the routing-instance BGP configuration on the PE device, as shown here:

```

user@R2# show routing-instances

```

```
red {
  instance-type vrf;
  interface fe-1/2/0.2;
  route-distinguisher 2:1;
  vrf-target target:2:1;
  protocols {
    bgp {
      group toR1 {
        type external;
        peer-as 1;
        local-as 200 no-prepend-global-as;
        neighbor 10.1.1.1;
      }
    }
  }
}
```

The Junos operating system (Junos OS) implementation of the local AS attribute supports the following options:


- **Local AS with private option**—When you use the **private** option, the local AS is used during the establishment of the BGP session with an EBGP neighbor but is hidden in the AS path sent to other EBGP peers. Only the global AS is included in the AS path sent to external peers.

The **private** option is useful for establishing local peering with routing devices that remain configured with their former AS or with a specific customer that has not yet modified its peer arrangements. The local AS is used to establish the BGP session with the EBGP neighbor but is hidden in the AS path sent to external peers in another AS.

Include the **private** option so that the local AS is not prepended before the global AS in the AS path sent to external peers. When you specify the **private** option, the local AS is prepended only in the AS path sent to the EBGP neighbor.

For example, in [Figure 13 on page 116](#), Router 1 and Router 2 are in AS 64496, Router 4 is in AS 64511, and Router 3 is in AS 64510. Router 2 formerly belonged to AS 64497, which has merged with another network and now belongs to AS 64496. Because Router 3 still peers with Router 2 using its former AS (64497), Router 2 needs to be configured with a local AS of 64497 in order to maintain peering with Router 3. Configuring a local AS of 64497 permits Router 2 to add AS 64497 when advertising routes to Router 3. Router 3 sees an AS path of 64497 64496 for the prefix 10/8.

**Figure 13: Local AS Configuration**



To prevent Router 2 from adding the local AS number in its announcements to other peers, use the **local-as 64497 private** statement. This statement configures Router 2 to not include local AS 64497 when announcing routes to Router 1 and to Router 4. In this case, Router 4 sees an AS path of 64496 64510 for the prefix 10.222/16.

- **Local AS with alias option**—In Junos OS Release 9.5 and later, you can configure a local AS as an alias. During the establishment of the BGP open session, the AS used in the open message alternates between the local AS and the global AS. If the local AS is used to connect with the EBGP neighbor, then only the local AS is prepended to the AS path when the BGP peer session is established. If the global AS is used to connect with the EBGP neighbor, then only the global AS is prepended to the AS path when the BGP peer session is established. The use of the **alias** option also means that

the local AS is not prepended to the AS path for any routes learned from that EBGp neighbor. Therefore, the local AS remains hidden from other external peers.

Configuring a local AS with the **alias** option is especially useful when you are migrating the routing devices in an acquired network to the new AS. During the migration process, some routing devices might be configured with the new AS while others remain configured with the former AS. For example, it is good practice to start by first migrating to the new AS any routing devices that function as route reflectors. However, as you migrate the route reflector clients incrementally, each route reflector has to peer with routing devices configured with the former AS, as well as peer with routing devices configured with the new AS. To establish local peer sessions, it can be useful for the BGP peers in the network to use both the local AS and the global AS. At the same time, you want to hide this local AS from external peers and use only the global AS in the AS path when exporting routes to another AS. In this kind of situation, configure the **alias** option.

Include the **alias** option to configure the local AS as an alias to the global AS configured at the **[edit routing-options]** hierarchy level. When you configure a local AS as an alias, during the establishment of the BGP open session, the AS used in the open message alternates between the local AS and the global AS. The local AS is prepended to the AS path only when the peer session with an EBGp neighbor is established using that local AS. The local AS is hidden in the AS path sent to any other external peers. Only the global AS is prepended to the AS path when the BGP session is established using the global AS.



**NOTE:** The **private** and **alias** options are mutually exclusive. You cannot configure both options with the same **local-as** statement.

- **Local AS with option not to prepend the global AS**—In Junos OS Release 9.6 and later, you can configure a local AS with the option not to prepend the global AS. Only the local AS is included in the AS path sent to external peers.

Use the **no-prepend-global-as** option when you want to strip the global AS number from outbound BGP updates in a virtual private network (VPN) scenario. This option is useful in a VPN scenario in which you want to hide the global AS from the VPN.

Include the **no-prepend-global-as** option to have the global AS configured at the **[edit routing-options]** hierarchy level removed from the AS path sent to external peers. When you use this option, only the local AS is included in the AS path for the routes sent to a customer edge (CE) device.

- **Number of loops option**—The local AS feature also supports specifying the number of times that detection of the AS number in the AS\_PATH attribute causes the route to be discarded or hidden. For example, if you configure **loops 1**, the route is hidden if the AS number is detected in the path one or more times. This is the default behavior. If you configure **loops 2**, the route is hidden if the AS number is detected in the path two or more times.

For the **loops number** statement, you can configure 1 through 10.



**NOTE:** If you configure the local AS values for any BGP group, the detection of routing loops is performed using both the AS and the local AS values for all BGP groups.

If the local AS for the EBGP or IBGP peer is the same as the current AS, do not use the `local-as` statement to specify the local AS number.

When you configure the local AS within a VRF, this impacts the AS path loop-detection mechanism. All of the `local-as` statements configured on the device are part of a single AS domain. The AS path loop-detection mechanism is based on looking for a matching AS present in the domain.

---

## Example: Configuring a Local AS for EBGP Sessions

This example shows how to configure a local autonomous system (AS) for a BGP peer so that both the global AS and the local AS are used in BGP inbound and outbound updates.

- [Requirements on page 118](#)
- [Overview on page 118](#)
- [Configuration on page 119](#)
- [Verification on page 125](#)

### Requirements

---

No special configuration beyond device initialization is required before you configure this example.

### Overview

---

Use the **local-as** statement when ISPs merge and want to preserve a customer's configuration, particularly the AS with which the customer is configured to establish a peer relationship. The **local-as** statement simulates the AS number already in place in customer routers, even if the ISP's router has moved to a different AS.

This example shows how to use the **local-as** statement to configure a local AS. The **local-as** statement is supported for BGP at the global, group, and neighbor hierarchy levels.


When you configure the **local-as** statement, you must specify an AS number. You can specify a number from 1 through 4,294,967,295 in plain-number format. In Junos OS Release 9.1 and later, the range for AS numbers is extended to provide BGP support for 4-byte AS numbers as defined in RFC 4893, *BGP Support for Four-octet AS Number Space*. In Junos OS Release 9.3 and later, you can also configure a 4-byte AS number using the AS-dot notation format of two integer values joined by a period: *<16-bit high-order value in decimal>.<16-bit low-order value in decimal>*. For example, the 4-byte AS number of 65,546 in plain-number format is represented as 1.10 in the AS-dot notation format. You can specify a value from 0.0 through 65535.65535 in AS-dot notation format. Junos



OS continues to support 2-byte AS numbers. The 2-byte AS number range is 1 through 65,535 (this is a subset of the 4-byte range).

[Figure 14 on page 119](#) shows the sample topology.

**Figure 14: Topology for Configuring the Local AS**



In this example, Device R2 formerly belonged to AS 250 and now is in AS 200. Device R1 and Device R3 are configured to peer with AS 250 instead of with the new AS number (AS 200). Device R2 has the new AS number configured with the **autonomous-system 200** statement. To enable the peering sessions to work, the **local-as 250** statement is added in the BGP configuration. Because **local-as 250** is configured, Device R2 includes both the global AS (200) and the local AS (250) in its BGP inbound and outbound updates.

### Configuration

- [Configuring Device R1 on page 120](#)
- [Configuring Device R2 on page 122](#)
- [Configuring Device R3 on page 124](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```

Device R1  set interfaces fe-1/2/0 unit 1 family inet address 10.0.0.1/30
            set interfaces lo0 unit 1 family inet address 192.168.0.1/32
            set protocols bgp group ext type external
            set protocols bgp group ext export send-direct
            set protocols bgp group ext export send-static
            set protocols bgp group ext peer-as 250
            set protocols bgp group ext neighbor 10.0.0.2
            set policy-options policy-statement send-direct term 1 from protocol direct
            set policy-options policy-statement send-direct term 1 then accept
            set policy-options policy-statement send-static term 1 from protocol static
            set policy-options policy-statement send-static term 1 then accept
            set routing-options static route 10.1.0.0/30 next-hop 10.0.0.2
            set routing-options autonomous-system 100

Device R2  set interfaces fe-1/2/0 unit 2 family inet address 10.0.0.2/30
            set interfaces fe-1/2/1 unit 3 family inet address 10.1.0.1/30
            set interfaces lo0 unit 2 family inet address 192.168.0.2/32
  
```

```
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext local-as 250
set protocols bgp group ext neighbor 10.0.0.1 peer-as 100
set protocols bgp group ext neighbor 10.1.0.2 peer-as 300
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options autonomous-system 200
```

**Device R3**

```
set interfaces fe-1/2/0 unit 4 family inet address 10.1.0.2/30
set interfaces lo0 unit 3 family inet address 192.168.0.3/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext peer-as 250
set protocols bgp group ext neighbor 10.1.0.1
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 10.0.0.0/30 next-hop 10.1.0.1
set routing-options autonomous-system 300
```

### *Configuring Device R1*

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.  
  
[edit interfaces]  
user@R1# set fe-1/2/0 unit 1 family inet address 10.0.0.1/30  
  
user@R1# set lo0 unit 1 family inet address 192.168.0.1/32
2. Configure external BGP (EBGP).  
  
[edit protocols bgp group ext]  
user@R1# set type external  
user@R1# set export send-direct  
user@R1# set export send-static  
user@R1# set peer-as 250  
user@R1# set neighbor 10.0.0.2
3. Configure the routing policy.  
  
[edit policy-options]  
user@R1# set policy-statement send-direct term 1 from protocol direct  
user@R1# set policy-statement send-direct term 1 then accept  
user@R1# set policy-statement send-static term 1 from protocol static  
user@R1# set policy-statement send-static term 1 then accept

4. Configure a static route to the remote network between Device R2 and Device R3.

```
[edit routing-options]
user@R1# set static route 10.1.0.0/30 next-hop 10.0.0.2
```

5. Configure the global AS number.

```
[edit routing-options]
user@R1# set autonomous-system 100
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-1/2/0 {
  unit 1 {
    family inet {
      address 10.0.0.1/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.0.1/32;
    }
  }
}

user@R1# show policy-options
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}
policy-statement send-static {
  term 1 {
    from protocol static;
    then accept;
  }
}

user@R1# show protocols
bgp {
  group ext {
    type external;
    export [ send-direct send-static ];
    peer-as 250;
    neighbor 10.0.0.2;
  }
}

user@R1# show routing-options
static {
```

```
    route 10.1.0.0/30 next-hop 10.0.0.2;
}
autonomous-system 100;
```

When you are done configuring the device, enter **commit** from configuration mode.

### **Configuring Device R2**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R2:

1. Configure the interfaces.

```
[edit interfaces]
user@R2# set fe-1/2/0 unit 2 family inet address 10.0.0.2/30

user@R2# set fe-1/2/1 unit 3 family inet address 10.1.0.1/30

user@R2# set lo0 unit 2 family inet address 192.168.0.2/32
```

2. Configure EBGp.

```
[edit protocols bgp group ext]
user@R2# set type external
user@R2# set export send-direct
user@R2# set export send-static
user@R2# set neighbor 10.0.0.1 peer-as 100
user@R2# set neighbor 10.1.0.2 peer-as 300
```

3. Configure the local autonomous system (AS) number.

```
[edit protocols bgp group ext]
user@R2# set local-as 250
```

4. Configure the global AS number.

```
[edit routing-options]
user@R2# set autonomous-system 200
```

5. Configure the routing policy.

```
[edit policy-options]
user@R2# set policy-statement send-direct term 1 from protocol direct
user@R2# set policy-statement send-direct term 1 then accept
user@R2# set policy-statement send-static term 1 from protocol static
user@R2# set policy-statement send-static term 1 then accept
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
fe-1/2/0 {
  unit 2 {
```

```

        family inet {
            address 10.0.0.2/30;
        }
    }
}
fe-1/2/1 {
    unit 3 {
        family inet {
            address 10.1.0.1/30;
        }
    }
}
lo0 {
    unit 2 {
        family inet {
            address 192.168.0.2/32;
        }
    }
}

user@R2# show policy-options
policy-statement send-direct {
    term 1 {
        from protocol direct;
        then accept;
    }
}
policy-statement send-static {
    term 1 {
        from protocol static;
        then accept;
    }
}

user@R2# show protocols
bgp {
    group ext {
        type external;
        export [ send-direct send-static ];
        local-as 250;
        neighbor 10.0.0.1 {
            peer-as 100;
        }
        neighbor 10.1.0.2 {
            peer-as 300;
        }
    }
}

user@R2# show routing-options
autonomous-system 200;

```

When you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R3

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R3:

1. Configure the interfaces.  

```
[edit interfaces]
user@R3# set fe-1/2/0 unit 4 family inet address 10.1.0.2/30

user@R3# set lo0 unit 3 family inet address 192.168.0.3/32
```
2. Configure EBGP.  

```
[edit protocols bgp group ext]
user@R3# set type external
user@R3# set export send-direct
user@R3# set export send-static
user@R3# set peer-as 250
user@R3# set neighbor 10.1.0.1
```
3. Configure the global autonomous system (AS) number.  

```
[edit routing-options]
user@R3# set autonomous-system 300
```
4. Configure a static route to the remote network between Device R1 and Device R2.  

```
[edit routing-options]
user@R3# set static route 10.0.0.0/30 next-hop 10.1.0.1
```
5. Configure the routing policy.  

```
[edit policy-options]
user@R3# set policy-statement send-direct term 1 from protocol direct
user@R3# set policy-statement send-direct term 1 then accept
user@R3# set policy-statement send-static term 1 from protocol static
user@R3# set policy-statement send-static term 1 then accept
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R3# show interfaces
fe-1/2/0 {
  unit 4 {
    family inet {
      address 10.1.0.2/30;
    }
  }
}
lo0 {
  unit 3 {
```

```

        family inet {
            address 192.168.0.3/32;
        }
    }
}

user@R3# show policy-options
policy-statement send-direct {
    term 1 {
        from protocol direct;
        then accept;
    }
}
policy-statement send-static {
    term 1 {
        from protocol static;
        then accept;
    }
}

user@R3# show protocols
bgp {
    group ext {
        type external;
        export [ send-direct send-static ];
        peer-as 250;
        neighbor 10.1.0.1;
    }
}

user@R3# show routing-options
static {
    route 10.0.0.0/30 next-hop 10.1.0.1;
}
autonomous-system 300;

```

When you are done configuring the device, enter **commit** from configuration mode.

### Verification

Confirm that the configuration is working properly.

- [Checking the Local and Global AS Settings on page 125](#)
- [Checking the BGP Peering Sessions on page 127](#)
- [Verifying the BGP AS Paths on page 127](#)

#### *Checking the Local and Global AS Settings*

**Purpose** Make sure that Device R2 has the local and global AS settings configured.

**Action** From operational mode, enter the **show bgp neighbors** command.

```

user@R2> show bgp neighbors
Peer: 10.0.0.1+179 AS 100      Local: 10.0.0.2+61036 AS 250
Type: External  State: Established  Flags: <Sync>
Last State: OpenConfirm  Last Event: RecvKeepAlive
Last Error: None

```

```

Export: [ send-direct send-static ]
Options: <Preference PeerAS LocalAS Refresh>
Holdtime: 90 Preference: 170 Local AS: 250 Local System AS: 200
Number of flaps: 0
Peer ID: 192.168.0.1      Local ID: 192.168.0.2      Active Holdtime: 90
Keepalive Interval: 30      Peer index: 0
BFD: disabled, down
Local Interface: fe-1/2/0.2
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Stale routes from peer are kept for: 300
Peer does not support Restarter functionality
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 100)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          1
  Received prefixes:        3
  Accepted prefixes:        2
  Suppressed due to damping: 0
  Advertised prefixes:      4
Last traffic (seconds): Received 6    Sent 14    Checked 47
Input messages: Total 258    Updates 3    Refreshes 0    Octets 4969
Output messages: Total 258    Updates 2    Refreshes 0    Octets 5037
Output Queue[0]: 0

Peer: 10.1.0.2+179 AS 300      Local: 10.1.0.1+52296 AS 250
Type: External    State: Established    Flags: <Sync>
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: None
Export: [ send-direct send-static ]
Options: <Preference PeerAS LocalAS Refresh>
Holdtime: 90 Preference: 170 Local AS: 250 Local System AS: 200
Number of flaps: 0
Peer ID: 192.168.0.3      Local ID: 192.168.0.2      Active Holdtime: 90
Keepalive Interval: 30      Peer index: 1
BFD: disabled, down
Local Interface: fe-1/2/1.3
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Stale routes from peer are kept for: 300
Peer does not support Restarter functionality
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 300)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          1
  Received prefixes:        3
  Accepted prefixes:        2

```



```

    Suppressed due to damping:    0
    Advertised prefixes:          4
    Last traffic (seconds): Received 19    Sent 26    Checked 9
    Input messages:  Total 256    Updates 3      Refreshes 0    Octets 4931
    Output messages: Total 256    Updates 2      Refreshes 0    Octets 4999
    Output Queue[0]: 0

```

**Meaning** The Local AS: 250 and Local System AS: 200 output shows that Device R2 has the expected settings. Additionally, the output shows that the options list includes LocalAS.

### *Checking the BGP Peering Sessions*

**Purpose** Ensure that the sessions are established and that the local AS number 250 is displayed.

**Action** From operational mode, enter the **show bgp summary** command.

```

user@R1> show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History  Damp State   Pending
inet.0      4          2          0          0        0      0        0
Peer        AS      InPkt    OutPkt    OutQ   Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.0.0.2      250      232      233       0        4    1:42:37
2/4/4/0      0/0/0/0

```

```

user@R3> show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History  Damp State   Pending
inet.0      4          2          0          0        0      0        0
Peer        AS      InPkt    OutPkt    OutQ   Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.1.0.1      250      235      236       0        4    1:44:25
2/4/4/0      0/0/0/0

```

**Meaning** Device R1 and Device R3 appear to be peering with a device in AS 250, even though Device R2 is actually in AS 200.

### *Verifying the BGP AS Paths*

**Purpose** Make sure that the routes are in the routing tables and that the AS paths show the local AS number 250.

**Action** From configuration mode, enter the **set route protocol bgp** command.

```

user@R1> show route protocol bgp
inet.0: 6 destinations, 8 routes (6 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.0.0.0/30      [BGP/170] 01:46:44, localpref 100
                  AS path: 250 I
                  > to 10.0.0.2 via fe-1/2/0.1
10.1.0.0/30      [BGP/170] 01:46:44, localpref 100
                  AS path: 250 I
                  > to 10.0.0.2 via fe-1/2/0.1
192.168.0.2/32   *[BGP/170] 01:46:44, localpref 100
                  AS path: 250 I
                  > to 10.0.0.2 via fe-1/2/0.1

```

```
192.168.0.3/32      *[BGP/170] 01:46:40, localpref 100
                   AS path: 250 300 I
                   > to 10.0.0.2 via fe-1/2/0.1

user@R3> show route protocol bgp

inet.0: 6 destinations, 8 routes (6 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.0.0.0/30        [BGP/170] 01:47:10, localpref 100
                   AS path: 250 I
                   > to 10.1.0.1 via fe-1/2/0.4
10.1.0.0/30        [BGP/170] 01:47:10, localpref 100
                   AS path: 250 I
                   > to 10.1.0.1 via fe-1/2/0.4
192.168.0.1/32     *[BGP/170] 01:47:10, localpref 100
                   AS path: 250 100 I
                   > to 10.1.0.1 via fe-1/2/0.4
192.168.0.2/32     *[BGP/170] 01:47:10, localpref 100
                   AS path: 250 I
                   > to 10.1.0.1 via fe-1/2/0.4
```

**Meaning** The output shows that Device R1 and Device R3 appear to have routes with AS paths that include AS 250, even though Device R2 is actually in AS 200.

## Example: Configuring a Private Local AS for EBGp Sessions

This example shows how to configure a private local autonomous system (AS) number. The local AS is considered to be private because it is advertised to peers that use the local AS number for peering, but is hidden in the announcements to peers that can use the global AS number for peering.

- [Requirements on page 128](#)
- [Overview on page 128](#)
- [Configuration on page 130](#)
- [Verification on page 132](#)

---

### Requirements

No special configuration beyond device initialization is required before you configure this example.

---

### Overview

Use the **local-as** statement when ISPs merge and want to preserve a customer's configuration, particularly the AS with which the customer is configured to establish a peer relationship. The **local-as** statement simulates the AS number already in place in customer routers, even if the ISP's router has moved to a different AS.


When you use the **private** option, the local AS is used during the establishment of the BGP session with an external BGP (EBGP) neighbor, but is hidden in the AS path sent to other EBGp peers. Only the global AS is included in the AS path sent to external peers.

The **private** option is useful for establishing local peering with routing devices that remain configured with their former AS or with a specific customer that has not yet modified its peer arrangements. The local AS is used to establish the BGP session with the EBGP neighbor, but is hidden in the AS path sent to external peers in another AS.

Include the **private** option so that the local AS is not prepended before the global AS in the AS path sent to external peers. When you specify the **private** option, the local AS is prepended only in the AS path sent to the EBGP neighbor.

Figure 15 on page 129 shows the sample topology.

Figure 15: Topology for Configuring a Private Local AS



Device R1 is in AS 64496. Device R2 is in AS 64510. Device R3 is in AS 64511. Device R4 is in AS 64512. Device R1 formerly belonged to AS 64497, which has merged with another network and now belongs to AS 64496. Because Device R3 still peers with Device R1, using its former AS, 64497, Device R1 needs to be configured with a local AS of 64497 in order to maintain peering with Device R3. Configuring a local AS of 64497 permits Device R1 to add AS 64497 when advertising routes to Device R3. Device R3 sees an AS path of 64497 64496 for the prefix 10.1.1.2/32, which is Device R2's loopback interface. Device R4, which is behind Device R3, sees an AS path of 64511 64497 64496 64510 to Device R2's loopback interface. To prevent Device R1 from adding the local AS number in its announcements to other peers, this example includes the **local-as 64497 private** statement. The **private** option configures Device R1 to not include the local AS 64497 when announcing routes to other peers. Device R2 sees an AS path of 64496 64511 to Device R3 and an AS path of 64496 64511 64512 to Device R4. The **private** option in Device R1's configuration causes the AS number 64497 to be missing from the AS paths that Device R1 readvertises to Device R2.

Device R2 is hiding the private local AS from all the routers, except Device R3. The **private** option applies to the routes that Device R1 receives (learns) from Device R3 and that Device R1, in turn, readvertises to other routers. When these routes learned from Device R3 are readvertised by Device R1 to Device R2, the private local AS is missing from the AS path advertised to Device R2.

## Configuration

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CLI Quick Configuration</b> | To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the <b>[edit]</b> hierarchy level.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Device R1</b>               | <pre> set interfaces fe-1/2/0 unit 3 family inet address 192.168.1.1/24 set interfaces fe-1/2/1 unit 5 family inet address 192.168.10.1/24 set interfaces lo0 unit 2 family inet address 10.1.1.1/32 set protocols bgp group external-AS64511 type external set protocols bgp group external-AS64511 peer-as 64511 set protocols bgp group external-AS64511 local-as 64497 set protocols bgp group external-AS64511 local-as private set protocols bgp group external-AS64511 neighbor 192.168.1.2 set protocols bgp group external-AS64510 type external set protocols bgp group external-AS64510 peer-as 64510 set protocols bgp group external-AS64510 neighbor 192.168.10.2 set policy-options policy-statement send-direct term 1 from protocol direct set policy-options policy-statement send-direct term 1 then accept set routing-options autonomous-system 64496 </pre> |
| <b>Device R2</b>               | <pre> set interfaces fe-1/2/0 unit 6 family inet address 192.168.10.2/24 set interfaces lo0 unit 3 family inet address 10.1.1.2/32 set protocols bgp group external type external set protocols bgp group external export send-direct set protocols bgp group external peer-as 64496 set protocols bgp group external neighbor 192.168.10.1 set policy-options policy-statement send-direct term 1 from protocol direct set policy-options policy-statement send-direct term 1 then accept set routing-options autonomous-system 64510 </pre>                                                                                                                                                                                                                                                                                                                                     |
| <b>Device R3</b>               | <pre> set interfaces fe-1/2/0 unit 4 family inet address 192.168.1.2/24 set interfaces fe-1/2/1 unit 7 family inet address 192.168.5.1/24 set interfaces lo0 unit 4 family inet address 10.1.1.3/32 set protocols bgp group external type external set protocols bgp group external export send-direct set protocols bgp group external neighbor 192.168.1.1 peer-as 64497 set protocols bgp group external neighbor 192.168.5.2 peer-as 64512 set policy-options policy-statement send-direct term 1 from protocol direct set policy-options policy-statement send-direct term 1 then accept set routing-options autonomous-system 64511 </pre>                                                                                                                                                                                                                                  |
| <b>Device R4</b>               | <pre> set interfaces fe-1/2/0 unit 8 family inet address 192.168.5.2/24 set interfaces lo0 unit 5 family inet address 10.1.1.4/32 set protocols bgp group external type external set protocols bgp group external export send-direct set protocols bgp group external peer-as 64511 set protocols bgp group external neighbor 192.168.5.1 set policy-options policy-statement send-direct term 1 from protocol direct set policy-options policy-statement send-direct term 1 then accept set routing-options autonomous-system 64512 </pre>                                                                                                                                                                                                                                                                                                                                       |

**Configuring Device R1**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.
 

```
[edit interfaces fe-1/2/0 unit 3]
user@R1# set family inet address 192.168.1.1/24

[edit interfaces fe-1/2/1 unit 5]
user@R1# set family inet address 192.168.10.1/24

[edit interfaces lo0 unit 2]
user@R1# set family inet address 10.1.1.1/32
```
2. Configure the EBGP peering session with Device R2.
 

```
[edit protocols bgp group external-AS64510]
user@R1# set type external
user@R1# set peer-as 64510
user@R1# set neighbor 192.168.10.2
```
3. Configure the EBGP peering session with Device R3.
 

```
[edit protocols bgp group external-AS64511]
user@R1# set type external
user@R1# set peer-as 64511
user@R1# set local-as 64497
user@R1# set local-as private
user@R1# set neighbor 192.168.1.2
```
4. Configure the routing policy.
 

```
[edit policy-options policy-statement send-direct term 1]
user@R1# set from protocol direct
user@R1# set then accept
```
5. Configure the global autonomous system (AS) number.
 

```
[edit routing-options]
user@R1# set autonomous-system 64496
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-1/2/0 {
  unit 3 {
    family inet {
      address 192.168.1.1/24;
    }
  }
}
```

```
    }  
  }  
  fe-1/2/1 {  
    unit 5 {  
      family inet {  
        address 192.168.10.1/24;  
      }  
    }  
  }  
  lo0 {  
    unit 2 {  
      family inet {  
        address 10.1.1.1/32;  
      }  
    }  
  }  
}  
  
user@R1# show policy-options  
policy-statement send-direct {  
  term 1 {  
    from protocol direct;  
    then accept;  
  }  
}  
  
user@R1# show protocols  
bgp {  
  group external-AS64511 {  
    type external;  
    peer-as 64511;  
    local-as 64497 private;  
    neighbor 192.168.1.2;  
  }  
  group external-AS64510 {  
    type external;  
    peer-as 64510;  
    neighbor 192.168.10.2;  
  }  
}  
  
user@R1# show routing-options  
autonomous-system 64496;
```

If you are done configuring the device, enter **commit** from configuration mode.

Repeat the configuration as needed for the other devices in the topology.

---

### Verification

Confirm that the configuration is working properly.

- [Checking Device R2's AS Paths on page 133](#)
- [Checking Device R3's AS Paths on page 133](#)

**Checking Device R2's AS Paths**

**Purpose** Make sure that Device R2 does not have AS 64497 in its AS paths to Device R3 and Device R4.

**Action** From operational mode, enter the **show route protocol bgp** command.

```
user@R2> show route protocol bgp
inet.0: 6 destinations, 6 routes (6 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.1.1.3/32      *[BGP/170] 01:33:11, localpref 100
                  AS path: 64496 64511 I
                  > to 192.168.10.1 via fe-1/2/0.6
10.1.1.4/32      *[BGP/170] 01:33:11, localpref 100
                  AS path: 64496 64511 64512 I
                  > to 192.168.10.1 via fe-1/2/0.6
192.168.5.0/24  *[BGP/170] 01:49:15, localpref 100
                  AS path: 64496 64511 I
                  > to 192.168.10.1 via fe-1/2/0.6
```

**Meaning** Device R2's AS paths do not include AS 64497.

**Checking Device R3's AS Paths**

**Purpose** Make sure that Device R3 does not have AS 64497 in its AS path to Device R4.

**Action** From operational mode, enter the **show route protocol bgp** command.

```
user@R3> show route protocol bgp
inet.0: 7 destinations, 8 routes (7 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.1.1.2/32      *[BGP/170] 01:35:11, localpref 100
                  AS path: 64497 64496 64510 I
                  > to 192.168.1.1 via fe-1/2/0.4
10.1.1.4/32      *[BGP/170] 01:35:11, localpref 100
                  AS path: 64512 I
                  > to 192.168.5.2 via fe-1/2/1.7
192.168.5.0/24  [BGP/170] 01:51:15, localpref 100
                  AS path: 64512 I
                  > to 192.168.5.2 via fe-1/2/1.7
```

**Meaning** Device R3's route to Device R2 (prefix 10.1.1.2) includes both the local and the global AS configured on Device R1 (64497 and 64496, respectively).

**Related Documentation**

- [Examples: Configuring External BGP Peering on page 13](#)
- [BGP Configuration Overview](#)

**Example: Configuring the Accumulated IGP Attribute for BGP**

- [Understanding the Accumulated IGP Attribute for BGP on page 134](#)
- [Example: Configuring the Accumulated IGP Attribute for BGP on page 134](#)

## Understanding the Accumulated IGP Attribute for BGP

The interior gateway protocols (IGPs) are designed to handle routing within a single domain or an autonomous system (AS). Each link is assigned a particular value called a metric. The distance between the two nodes is calculated as a sum of all the metric values of links along the path. The IGP selects the shortest path between two nodes based on distance.

BGP is designed to provide routing over a large number of independent ASs with limited or no coordination among respective administrations. BGP does not use metrics in the path selection decisions.

The accumulated IGP (AIGP) metric attribute for BGP enables deployment in which a single administration can run several contiguous BGP ASs. Such deployments allow BGP to make routing decisions based on the IGP metric. In such networks, it is possible for BGP to select paths based on metrics as is done by IGPs. In this case, BGP chooses the shortest path between two nodes, even though the nodes might be in two different ASs.

The AIGP attribute is particularly useful in networks that use tunneling to deliver a packet to its BGP next hop. The Juniper Networks® Junos® operating system (Junos OS) currently supports the AIGP attribute for two BGP address families, **family inet labeled-unicast** and **family inet6 labeled-unicast**.

AIGP impacts the BGP best-route decision process. The AIGP attribute preference rule is applied after the local-preference rule. The AIGP distance is compared to break a tie. The BGP best-route decision process also impacts the way the interior cost rule is applied if the resolving next hop has an AIGP attribute. Without AIGP enabled, the interior cost of a route is based on the calculation of the metric to the next hop for the route. With AIGP enabled, the resolving AIGP distance is added to the interior cost.

The AIGP attribute is an optional non-transitive BGP path attribute and is specified in Internet draft draft-ietf-idr-aigp-06, *The Accumulated IGP Metric Attribute for BGP*.

## Example: Configuring the Accumulated IGP Attribute for BGP

This example shows how to configure the accumulated IGP (AIGP) metric attribute for BGP.

- [Requirements on page 134](#)
- [Overview on page 135](#)
- [Configuration on page 136](#)
- [Verification on page 166](#)

---

### Requirements

This example uses the following hardware and software components:

- Seven BGP-speaking devices.
- Junos OS Release 12.1 or later.



## Overview

The AIGP attribute enables deployments in which a single administration can run several contiguous BGP autonomous systems (ASs). Such deployments allow BGP to make routing decisions based on the IGP metric. With AIGP enabled, BGP can select paths based on IGP metrics. This enables BGP to choose the shortest path between two nodes, even though the nodes might be in different ASs. The AIGP attribute is particularly useful in networks that use tunneling to deliver a packet to its BGP next hop. This example shows AIGP configured with MPLS label-switched paths.

To enable AIGP, you include the **aigp** statement in the BGP configuration on a protocol family basis. Configuring AIGP on a particular family enables sending and receiving of the AIGP attribute on that family. By default, AIGP is disabled. An AIGP-disabled neighbor does not send an AIGP attribute and silently discards a received AIGP attribute.

Junos OS supports AIGP for **family inet labeled-unicast** and **family inet6 labeled-unicast**. The **aigp** statement can be configured for a given family at the global BGP, group, or neighbor level.

By default, the value of the AIGP attribute for a local prefix is zero. An AIGP-enabled neighbor can originate an AIGP attribute for a given prefix by export policy, using the **aigp-originate** policy action. The value of the AIGP attribute reflects the IGP distance to the prefix. Alternatively, you can specify a value, by using the **aigp-originate distance distance** policy action. The configurable range is 0 through 4,294,967,295. Only one node needs to originate an AIGP attribute. The AIGP attribute is retained and readvertised if the neighbors are AIGP enabled with the **aigp** statement in the BGP configuration.

The policy action to originate the AIGP attribute has the following requirements:

- Neighbor must be AIGP enabled.
- Policy must be applied as an export policy.
- Prefix must have no current AIGP attribute.
- Prefix must export with next-hop self.
- Prefix must reside within the AIGP domain. Typically, a loopback IP address is the prefix to originate.


The policy is ignored if these requirements are not met.

## Topology Diagram

Figure 16 on page 136 shows the topology used in this example. OSPF is used as the interior gateway protocol (IGP). Internal BGP (IBGP) is configured between Device PE1 and Device PE4. External BGP (EBGP) is configured between Device PE7 and Device PE1, between Device PE4 and Device PE3, and between Device PE4 and Device PE2. Devices PE4, PE2, and PE3 are configured for multihop. Device PE4 selects a path based on the AIGP value and then readvertises the AIGP value based on the AIGP and policy configuration. Device PE1 readvertises the AIGP value to Device PE7, which is in another administrative domain. Every device has two loopback interface addresses: 10.9.9.x is used for BGP peering and the router ID, and 10.100.1.x is used for the BGP next hop.

The network between Device PE1 and PE3 has IBGP peering and multiple OSPF areas. The external link to Device PE7 is configured to show that the AIGP attribute is readadvertised to a neighbor outside of the administrative domain, if that neighbor is AIGP enabled.

**Figure 16: Advertisement of Multiple Paths in BGP**



For origination of an AIGP attribute, the BGP next hop is required to be itself. If the BGP next hop remains unchanged, the received AIGP attribute is readadvertised, as is, to another AIGP neighbor. If the next hop changes, the received AIGP attribute is readadvertised with an increased value to another AIGP neighbor. The increase in value reflects the IGP distance to the previous BGP next hop. To demonstrate, this example uses loopback interface addresses for Device PE4's EBGP peering sessions with Device PE2 and Device PE3. Multihop is enabled on these sessions so that a recursive lookup is performed to determine the point-to-point interface. Because the next hop changes, the IGP distance is added to the AIGP distance.

### Configuration

- [Configuring Device P1 on page 142](#)
- [Configuring Device P2 on page 145](#)
- [Configuring Device PE4 on page 148](#)
- [Configuring Device PE1 on page 153](#)
- [Configuring Device PE2 on page 157](#)
- [Configuring Device PE3 on page 161](#)
- [Configuring Device PE7 on page 164](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
Device P1    set interfaces fe-1/2/0 unit 1 description P1-to-PE1
              set interfaces fe-1/2/0 unit 1 family inet address 10.0.0.2/30
              set interfaces fe-1/2/0 unit 1 family mpls
```

```

set interfaces fe-1/2/1 unit 4 description P1-to-P2
set interfaces fe-1/2/1 unit 4 family inet address 10.0.0.29/30
set interfaces fe-1/2/1 unit 4 family mpls
set interfaces fe-1/2/2 unit 8 description P1-to-PE4
set interfaces fe-1/2/2 unit 8 family inet address 10.0.0.17/30
set interfaces fe-1/2/2 unit 8 family mpls
set interfaces lo0 unit 3 family inet address 10.9.9.2/32
set interfaces lo0 unit 3 family inet address 10.100.1.2/32
set protocols rsvp interface fe-1/2/0.1
set protocols rsvp interface fe-1/2/2.8
set protocols rsvp interface fe-1/2/1.4
set protocols mpls label-switched-path P1-to-P2 to 10.9.9.3
set protocols mpls label-switched-path P1-to-PE1 to 10.9.9.1
set protocols mpls label-switched-path P1-to-PE4 to 10.9.9.4
set protocols mpls interface fe-1/2/0.1
set protocols mpls interface fe-1/2/2.8
set protocols mpls interface fe-1/2/1.4
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.9.9.2
set protocols bgp group internal family inet labeled-unicast aigp
set protocols bgp group internal neighbor 10.9.9.1
set protocols bgp group internal neighbor 10.9.9.3
set protocols bgp group internal neighbor 10.9.9.4
set protocols ospf area 0.0.0.1 interface fe-1/2/0.1 metric 1
set protocols ospf area 0.0.0.1 interface fe-1/2/1.4 metric 1
set protocols ospf area 0.0.0.0 interface fe-1/2/2.8 metric 1
set protocols ospf area 0.0.0.0 interface 10.9.9.2 passive
set protocols ospf area 0.0.0.0 interface 10.9.9.2 metric 1
set protocols ospf area 0.0.0.0 interface 10.100.1.2 passive
set protocols ospf area 0.0.0.0 interface 10.100.1.2 metric 1
set routing-options router-id 10.9.9.2
set routing-options autonomous-system 13979

```

#### Device P2

```

set interfaces fe-1/2/0 unit 3 description P2-to-PE1
set interfaces fe-1/2/0 unit 3 family inet address 10.0.0.6/30
set interfaces fe-1/2/0 unit 3 family mpls
set interfaces fe-1/2/1 unit 5 description P2-to-P1
set interfaces fe-1/2/1 unit 5 family inet address 10.0.0.30/30
set interfaces fe-1/2/1 unit 5 family mpls
set interfaces fe-1/2/2 unit 6 description P2-to-PE4
set interfaces fe-1/2/2 unit 6 family inet address 10.0.0.13/30
set interfaces fe-1/2/2 unit 6 family mpls
set interfaces lo0 unit 5 family inet address 10.9.9.3/32
set interfaces lo0 unit 5 family inet address 10.100.1.3/32
set protocols rsvp interface fe-1/2/1.5
set protocols rsvp interface fe-1/2/2.6
set protocols rsvp interface fe-1/2/0.3
set protocols mpls label-switched-path P2-to-PE1 to 10.9.9.1
set protocols mpls label-switched-path P2-to-P1 to 10.9.9.2
set protocols mpls label-switched-path P2-to-PE4 to 10.9.9.4
set protocols mpls interface fe-1/2/1.5
set protocols mpls interface fe-1/2/2.6
set protocols mpls interface fe-1/2/0.3
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.9.9.3
set protocols bgp group internal family inet labeled-unicast aigp

```

```

set protocols bgp group internal neighbor 10.9.9.1
set protocols bgp group internal neighbor 10.9.9.2
set protocols bgp group internal neighbor 10.9.9.4
set protocols ospf area 0.0.0.0 interface fe-1/2/2.6 metric 1
set protocols ospf area 0.0.0.0 interface 10.9.9.3 passive
set protocols ospf area 0.0.0.0 interface 10.9.9.3 metric 1
set protocols ospf area 0.0.0.0 interface 10.100.1.3 passive
set protocols ospf area 0.0.0.0 interface 10.100.1.3 metric 1
set routing-options router-id 10.9.9.3
set routing-options autonomous-system 13979

```

**Device PE4**

```

set interfaces fe-1/2/0 unit 7 description PE4-to-P2
set interfaces fe-1/2/0 unit 7 family inet address 10.0.0.14/30
set interfaces fe-1/2/0 unit 7 family mpls
set interfaces fe-1/2/1 unit 9 description PE4-to-P1
set interfaces fe-1/2/1 unit 9 family inet address 10.0.0.18/30
set interfaces fe-1/2/1 unit 9 family mpls
set interfaces fe-1/2/2 unit 10 description PE4-to-PE2
set interfaces fe-1/2/2 unit 10 family inet address 10.0.0.21/30
set interfaces fe-1/2/2 unit 10 family mpls
set interfaces fe-1/0/2 unit 12 description PE4-to-PE3
set interfaces fe-1/0/2 unit 12 family inet address 10.0.0.25/30
set interfaces fe-1/0/2 unit 12 family mpls
set interfaces lo0 unit 7 family inet address 10.9.9.4/32
set interfaces lo0 unit 7 family inet address 10.100.1.4/32
set protocols rsvp interface fe-1/2/0.7
set protocols rsvp interface fe-1/2/1.9
set protocols rsvp interface fe-1/2/2.10
set protocols rsvp interface fe-1/0/2.12
set protocols mpls label-switched-path PE4-to-PE2 to 10.9.9.5
set protocols mpls label-switched-path PE4-to-PE3 to 10.9.9.6
set protocols mpls label-switched-path PE4-to-P1 to 10.9.9.2
set protocols mpls label-switched-path PE4-to-P2 to 10.9.9.3
set protocols mpls interface fe-1/2/0.7
set protocols mpls interface fe-1/2/1.9
set protocols mpls interface fe-1/2/2.10
set protocols mpls interface fe-1/0/2.12
set protocols bgp export next-hop
set protocols bgp export aigp
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.9.9.4
set protocols bgp group internal family inet labeled-unicast aigp
set protocols bgp group internal neighbor 10.9.9.1
set protocols bgp group internal neighbor 10.9.9.3
set protocols bgp group internal neighbor 10.9.9.2
set protocols bgp group external type external
set protocols bgp group external multihop ttl 2
set protocols bgp group external local-address 10.9.9.4
set protocols bgp group external family inet labeled-unicast aigp
set protocols bgp group external peer-as 7018
set protocols bgp group external neighbor 10.9.9.5
set protocols bgp group external neighbor 10.9.9.6
set protocols ospf area 0.0.0.0 interface fe-1/2/1.9 metric 1
set protocols ospf area 0.0.0.0 interface fe-1/2/0.7 metric 1
set protocols ospf area 0.0.0.0 interface 10.9.9.4 passive
set protocols ospf area 0.0.0.0 interface 10.9.9.4 metric 1

```

```

set protocols ospf area 0.0.0.0 interface 10.100.1.4 passive
set protocols ospf area 0.0.0.0 interface 10.100.1.4 metric 1
set protocols ospf area 0.0.0.2 interface fe-1/2/2.10 metric 1
set protocols ospf area 0.0.0.3 interface fe-1/0/2.12 metric 1
set policy-options policy-statement aigp term 10 from protocol static
set policy-options policy-statement aigp term 10 from route-filter 44.0.0.0/24 exact
set policy-options policy-statement aigp term 10 then aigp-originate distance 200
set policy-options policy-statement aigp term 10 then next-hop 10.100.1.4
set policy-options policy-statement aigp term 10 then accept
set policy-options policy-statement next-hop term 10 from protocol bgp
set policy-options policy-statement next-hop term 10 then next-hop 10.100.1.4
set policy-options policy-statement next-hop term 10 then accept
set policy-options policy-statement next-hop term 20 from protocol direct
set policy-options policy-statement next-hop term 20 from route-filter 10.9.9.4/32 exact
set policy-options policy-statement next-hop term 20 from route-filter 10.100.1.4/32
  exact
set policy-options policy-statement next-hop term 20 then next-hop 10.100.1.4
set policy-options policy-statement next-hop term 20 then accept
set routing-options static route 44.0.0.0/24 discard
set routing-options router-id 10.9.9.4
set routing-options autonomous-system 13979

```

**Device PE1**

```

set interfaces fe-1/2/0 unit 0 description PE1-to-P1
set interfaces fe-1/2/0 unit 0 family inet address 10.0.0.1/30
set interfaces fe-1/2/0 unit 0 family mpls
set interfaces fe-1/2/1 unit 2 description PE1-to-P2
set interfaces fe-1/2/1 unit 2 family inet address 10.0.0.5/30
set interfaces fe-1/2/1 unit 2 family mpls
set interfaces fe-1/2/2 unit 14 description PE1-to-PE7
set interfaces fe-1/2/2 unit 14 family inet address 10.0.0.9/30
set interfaces lo0 unit 1 family inet address 10.9.9.1/32
set interfaces lo0 unit 1 family inet address 10.100.1.1/32
set protocols rsvp interface fe-1/2/0.0
set protocols rsvp interface fe-1/2/1.2
set protocols rsvp interface fe-1/2/2.14
set protocols mpls label-switched-path PE1-to-P1 to 10.9.9.2
set protocols mpls label-switched-path PE1-to-P2 to 10.9.9.3
set protocols mpls interface fe-1/2/0.0
set protocols mpls interface fe-1/2/1.2
set protocols mpls interface fe-1/2/2.14
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.9.9.1
set protocols bgp group internal family inet labeled-unicast aigp
set protocols bgp group internal export SET_EXPORT_ROUTES
set protocols bgp group internal vpn-apply-export
set protocols bgp group internal neighbor 10.9.9.4
set protocols bgp group internal neighbor 10.9.9.2
set protocols bgp group internal neighbor 10.9.9.3
set protocols bgp group external type external
set protocols bgp group external family inet labeled-unicast aigp
set protocols bgp group external export SET_EXPORT_ROUTES
set protocols bgp group external peer-as 7019
set protocols bgp group external neighbor 10.0.0.10
set protocols ospf area 0.0.0.1 interface fe-1/2/0.0 metric 1
set protocols ospf area 0.0.0.1 interface fe-1/2/1.2 metric 1
set protocols ospf area 0.0.0.1 interface 10.9.9.1 passive

```

```

set protocols ospf area 0.0.0.1 interface 10.9.9.1 metric 1
set protocols ospf area 0.0.0.1 interface 10.100.1.1 passive
set protocols ospf area 0.0.0.1 interface 10.100.1.1 metric 1
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol direct
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol bgp
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then next-hop
  10.100.1.1
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then accept
set routing-options router-id 10.9.9.1
set routing-options autonomous-system 13979

```

**Device PE2**

```

set interfaces fe-1/2/0 unit 11 description PE2-to-PE4
set interfaces fe-1/2/0 unit 11 family inet address 10.0.0.22/30
set interfaces fe-1/2/0 unit 11 family mpls
set interfaces lo0 unit 9 family inet address 10.9.9.5/32 primary
set interfaces lo0 unit 9 family inet address 10.100.1.5/32
set protocols rsvp interface fe-1/2/0.11
set protocols mpls label-switched-path PE2-to-PE4 to 10.9.9.4
set protocols mpls interface fe-1/2/0.11
set protocols bgp group external type external
set protocols bgp group external multihop ttl 2
set protocols bgp group external local-address 10.9.9.5
set protocols bgp group external family inet labeled-unicast aigp
set protocols bgp group external export next-hop
set protocols bgp group external export aigp
set protocols bgp group external export SET_EXPORT_ROUTES
set protocols bgp group external vpn-apply-export
set protocols bgp group external peer-as 13979
set protocols bgp group external neighbor 10.9.9.4
set protocols ospf area 0.0.0.2 interface 10.9.9.5 passive
set protocols ospf area 0.0.0.2 interface 10.9.9.5 metric 1
set protocols ospf area 0.0.0.2 interface 10.100.1.5 passive
set protocols ospf area 0.0.0.2 interface 10.100.1.5 metric 1
set protocols ospf area 0.0.0.2 interface fe-1/2/0.11 metric 1
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol direct
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol static
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol bgp
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then next-hop
  10.100.1.5
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then accept
set policy-options policy-statement aigp term 10 from route-filter 55.0.0.0/24 exact
set policy-options policy-statement aigp term 10 then aigp-originate distance 20
set policy-options policy-statement aigp term 10 then next-hop 10.100.1.5
set policy-options policy-statement aigp term 10 then accept
set policy-options policy-statement aigp term 20 from route-filter 99.0.0.0/24 exact
set policy-options policy-statement aigp term 20 then aigp-originate distance 30
set policy-options policy-statement aigp term 20 then next-hop 10.100.1.5
set policy-options policy-statement aigp term 20 then accept
set policy-options policy-statement next-hop term 10 from protocol bgp
set policy-options policy-statement next-hop term 10 then next-hop 10.100.1.5
set policy-options policy-statement next-hop term 10 then accept
set policy-options policy-statement next-hop term 20 from protocol direct
set policy-options policy-statement next-hop term 20 from route-filter 10.9.9.5/32 exact
set policy-options policy-statement next-hop term 20 from route-filter 10.100.1.5/32
  exact
set policy-options policy-statement next-hop term 20 then next-hop 10.100.1.5

```

```

set policy-options policy-statement next-hop term 20 then accept
set routing-options static route 99.0.0.0/24 discard
set routing-options static route 55.0.0.0/24 discard
set routing-options router-id 10.9.9.5
set routing-options autonomous-system 7018

```

**Device PE3**

```

set interfaces fe-1/2/0 unit 13 description PE3-to-PE4
set interfaces fe-1/2/0 unit 13 family inet address 10.0.0.26/30
set interfaces fe-1/2/0 unit 13 family mpls
set interfaces lo0 unit 11 family inet address 10.9.9.6/32
set interfaces lo0 unit 11 family inet address 10.100.1.6/32
set protocols rsvp interface fe-1/2/0.13
set protocols mpls label-switched-path PE3-to-PE4 to 10.9.9.4
set protocols mpls interface fe-1/2/0.13
set protocols bgp group external type external
set protocols bgp group external multihop ttl 2
set protocols bgp group external local-address 10.9.9.6
set protocols bgp group external family inet labeled-unicast aigp
set protocols bgp group external export next-hop
set protocols bgp group external export SET_EXPORT_ROUTES
set protocols bgp group external vpn-apply-export
set protocols bgp group external peer-as 13979
set protocols bgp group external neighbor 10.9.9.4
set protocols ospf area 0.0.0.3 interface 10.9.9.6 passive
set protocols ospf area 0.0.0.3 interface 10.9.9.6 metric 1
set protocols ospf area 0.0.0.3 interface 10.100.1.6 passive
set protocols ospf area 0.0.0.3 interface 10.100.1.6 metric 1
set protocols ospf area 0.0.0.3 interface fe-1/2/0.13 metric 1
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol direct
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol static
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol bgp
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then next-hop
    10.100.1.6
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then accept
set policy-options policy-statement next-hop term 10 from protocol bgp
set policy-options policy-statement next-hop term 10 then next-hop 10.100.1.6
set policy-options policy-statement next-hop term 10 then accept
set policy-options policy-statement next-hop term 20 from protocol direct
set policy-options policy-statement next-hop term 20 from route-filter 10.9.9.6/32 exact
set policy-options policy-statement next-hop term 20 from route-filter 10.100.1.6/32
    exact
set policy-options policy-statement next-hop term 20 then next-hop 10.100.1.6
set policy-options policy-statement next-hop term 20 then accept
set routing-options router-id 10.9.9.6
set routing-options autonomous-system 7018

```

**Device PE7**

```

set interfaces fe-1/2/0 unit 15 description PE7-to-PE1
set interfaces fe-1/2/0 unit 15 family inet address 10.0.0.10/30
set interfaces lo0 unit 13 family inet address 10.9.9.7/32
set interfaces lo0 unit 13 family inet address 10.100.1.7/32
set protocols bgp group external type external
set protocols bgp group external family inet labeled-unicast aigp
set protocols bgp group external export SET_EXPORT_ROUTES
set protocols bgp group external peer-as 13979
set protocols bgp group external neighbor 10.0.0.9

```

```

set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol direct
set policy-options policy-statement SET_EXPORT_ROUTES term 10 from protocol bgp
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then next-hop
  10.100.1.7
set policy-options policy-statement SET_EXPORT_ROUTES term 10 then accept
set routing-options router-id 10.9.9.7
set routing-options autonomous-system 7019

```

### Configuring Device P1

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device P1:

1. Configure the interfaces.

```

[edit interfaces]
user@P1# set fe-1/2/0 unit 1 description P1-to-PE1
user@P1# set fe-1/2/0 unit 1 family inet address 10.0.0.2/30
user@P1# set fe-1/2/0 unit 1 family mpls
user@P1# set fe-1/2/1 unit 4 description P1-to-P2
user@P1# set fe-1/2/1 unit 4 family inet address 10.0.0.29/30
user@P1# set fe-1/2/1 unit 4 family mpls
user@P1# set fe-1/2/2 unit 8 description P1-to-PE4
user@P1# set fe-1/2/2 unit 8 family inet address 10.0.0.17/30
user@P1# set fe-1/2/2 unit 8 family mpls
user@P1# set lo0 unit 3 family inet address 10.9.9.2/32
user@P1# set lo0 unit 3 family inet address 10.100.1.2/32

```

2. Configure MPLS and a signaling protocol, such as RSVP or LDP.

```

[edit protocols]
user@P1# set rsvp interface fe-1/2/0.1
user@P1# set rsvp interface fe-1/2/2.8
user@P1# set rsvp interface fe-1/2/1.4
user@P1# set mpls label-switched-path P1-to-P2 to 10.9.9.3
user@P1# set mpls label-switched-path P1-to-PE1 to 10.9.9.1
user@P1# set mpls label-switched-path P1-to-PE4 to 10.9.9.4
user@P1# set mpls interface fe-1/2/0.1
user@P1# set mpls interface fe-1/2/2.8
user@P1# set mpls interface fe-1/2/1.4

```

3. Configure BGP.

```

[edit protocols bgp group internal]
user@P1# set type internal
user@P1# set local-address 10.9.9.2
user@P1# set neighbor 10.9.9.1
user@P1# set neighbor 10.9.9.3
user@P1# set neighbor 10.9.9.4

```

4. Enable AIGP.

```

[edit protocols bgp group internal]
user@P1# set family inet labeled-unicast aigp

```



5. Configure an IGP, such as OSPF, RIP, or IS-IS.

```
[edit protocols ospf]
user@P1# set area 0.0.0.1 interface fe-1/2/0.1 metric 1
user@P1# set area 0.0.0.1 interface fe-1/2/1.4 metric 1
user@P1# set area 0.0.0.0 interface fe-1/2/2.8 metric 1
user@P1# set area 0.0.0.0 interface 10.9.9.2 passive
user@P1# set area 0.0.0.0 interface 10.9.9.2 metric 1
user@P1# set area 0.0.0.0 interface 10.100.1.2 passive
user@P1# set area 0.0.0.0 interface 10.100.1.2 metric 1
```

6. Configure the router ID and the autonomous system number.

```
[edit routing-options]
user@P1# set router-id 10.9.9.2
user@P1# set autonomous-system 13979
```

7. If you are done configuring the device, commit the configuration.

```
user@P1# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@P1# show interfaces
fe-1/2/0 {
  unit 1 {
    description P1-to-PE1;
    family inet {
      address 10.0.0.2/30;
    }
    family mpls;
  }
}
fe-1/2/1 {
  unit 4 {
    description P1-to-P2;
    family inet {
      address 10.0.0.29/30;
    }
    family mpls;
  }
}
fe-1/2/2 {
  unit 8 {
    description P1-to-PE4;
    family inet {
      address 10.0.0.17/30;
    }
    family mpls;
  }
}
lo0 {
  unit 3 {
    family inet {
```

```
        address 10.9.9.2/32;
        address 10.100.1.2/32;
    }
}
}

user@P1# show protocols
rsvp {
    interface fe-1/2/0.1;
    interface fe-1/2/2.8;
    interface fe-1/2/1.4;
}
mpls {
    label-switched-path P1-to-P2 {
        to 10.9.9.3;
    }
    label-switched-path P1-to-PE1 {
        to 10.9.9.1;
    }
    label-switched-path P1-to-PE4 {
        to 10.9.9.4;
    }
    interface fe-1/2/0.1;
    interface fe-1/2/2.8;
    interface fe-1/2/1.4;
}
bgp {
    group internal {
        type internal;
        local-address 10.9.9.2;
        family inet {
            labeled-unicast {
                aigp;
            }
        }
        neighbor 10.9.9.1;
        neighbor 10.9.9.3;
        neighbor 10.9.9.4;
    }
}
ospf {
    area 0.0.0.1 {
        interface fe-1/2/0.1 {
            metric 1;
        }
        interface fe-1/2/1.4 {
            metric 1;
        }
    }
    area 0.0.0.0 {
        interface fe-1/2/2.8 {
            metric 1;
        }
        interface 10.9.9.2 {
            passive;
            metric 1;
        }
    }
}
```

```

    }
    interface 10.100.1.2 {
        passive;
        metric 1;
    }
}

user@P1# show routing-options
router-id 10.9.9.2;
autonomous-system 13979;

```

### Configuring Device P2

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device P2:

1. Configure the interfaces.

```

[edit interfaces]
user@P2# set fe-1/2/0 unit 3 description P2-to-PE1
user@P2# set fe-1/2/0 unit 3 family inet address 10.0.0.6/30
user@P2# set fe-1/2/0 unit 3 family mpls
user@P2# set fe-1/2/1 unit 5 description P2-to-P1
user@P2# set fe-1/2/1 unit 5 family inet address 10.0.0.30/30
user@P2# set fe-1/2/1 unit 5 family mpls
user@P2# set fe-1/2/2 unit 6 description P2-to-PE4
user@P2# set fe-1/2/2 unit 6 family inet address 10.0.0.13/30
user@P2# set fe-1/2/2 unit 6 family mpls
user@P2# set lo0 unit 5 family inet address 10.9.9.3/32
user@P2# set lo0 unit 5 family inet address 10.100.1.3/32

```

2. Configure MPLS and a signaling protocol, such as RSVP or LDP.

```

[edit protocols]
user@P2# set rsvp interface fe-1/2/1.5
user@P2# set rsvp interface fe-1/2/2.6
user@P2# set rsvp interface fe-1/2/0.3
user@P2# set mpls label-switched-path P2-to-PE1 to 10.9.9.1
user@P2# set mpls label-switched-path P2-to-P1 to 10.9.9.2
user@P2# set mpls label-switched-path P2-to-PE4 to 10.9.9.4
user@P2# set mpls interface fe-1/2/1.5
user@P2# set mpls interface fe-1/2/2.6
user@P2# set mpls interface fe-1/2/0.3

```

3. Configure BGP.

```

[edit protocols bgp group internal]
user@P2# set type internal
user@P2# set local-address 10.9.9.3
user@P2# set neighbor 10.9.9.1
user@P2# set neighbor 10.9.9.2
user@P2# set neighbor 10.9.9.4

```

4. Enable AIGP.

```
[edit protocols bgp group internal]
user@P2# set family inet labeled-unicast aigp
```

5. Configure an IGP, such as OSPF, RIP, or IS-IS.

```
[edit protocols ospf]
user@P2# set area 0.0.0.0 interface fe-1/2/2.6 metric 1
user@P2# set area 0.0.0.0 interface 10.9.9.3 passive
user@P2# set area 0.0.0.0 interface 10.9.9.3 metric 1
user@P2# set area 0.0.0.0 interface 10.100.1.3 passive
user@P2# set area 0.0.0.0 interface 10.100.1.3 metric 1
```

6. Configure the router ID and the autonomous system number.

```
[edit routing-options]
user@P2# set router-id 10.9.9.3
user@P2# set autonomous-system 13979
```

7. If you are done configuring the device, commit the configuration.

```
user@P2# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@P2# show interfaces
fe-1/2/0 {
  unit 3 {
    description P2-to-PE1;
    family inet {
      address 10.0.0.6/30;
    }
    family mpls;
  }
}
fe-1/2/1 {
  unit 5 {
    description P2-to-P1;
    family inet {
      address 10.0.0.30/30;
    }
    family mpls;
  }
}
fe-1/2/2 {
  unit 6 {
    description P2-to-PE4;
    family inet {
      address 10.0.0.13/30;
    }
    family mpls;
  }
}
lo0 {
```

```

unit 5 {
    family inet {
        address 10.9.9.3/32;
        address 10.100.1.3/32;
    }
}

user@P2# show protocols
rsvp {
    interface fe-1/2/1.5;
    interface fe-1/2/2.6;
    interface fe-1/2/0.3;
}
mpls {
    label-switched-path P2-to-PE1 {
        to 10.9.9.1;
    }
    label-switched-path P2-to-P1 {
        to 10.9.9.2;
    }
    label-switched-path P2-to-PE4 {
        to 10.9.9.4;
    }
    interface fe-1/2/1.5;
    interface fe-1/2/2.6;
    interface fe-1/2/0.3;
}
bgp {
    group internal {
        type internal;
        local-address 10.9.9.3;
        family inet {
            labeled-unicast {
                aigp;
            }
        }
        neighbor 10.9.9.1;
        neighbor 10.9.9.2;
        neighbor 10.9.9.4;
    }
}
ospf {
    area 0.0.0.0 {
        interface fe-1/2/2.6 {
            metric 1;
        }
        interface 10.9.9.3 {
            passive;
            metric 1;
        }
        interface 10.100.1.3 {
            passive;
            metric 1;
        }
    }
}

```

```

}
user@P2# show routing-options
router-id 10.9.9.3;
autonomous-system 13979;

```

### Configuring Device PE4

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device PE4:

1. Configure the interfaces.

```

[edit interfaces]
user@PE4# set fe-1/2/0 unit 7 description PE4-to-P2
user@PE4# set fe-1/2/0 unit 7 family inet address 10.0.0.14/30
user@PE4# set fe-1/2/0 unit 7 family mpls
user@PE4# set fe-1/2/1 unit 9 description PE4-to-P1
user@PE4# set fe-1/2/1 unit 9 family inet address 10.0.0.18/30
user@PE4# set fe-1/2/1 unit 9 family mpls
user@PE4# set fe-1/2/2 unit 10 description PE4-to-PE2
user@PE4# set fe-1/2/2 unit 10 family inet address 10.0.0.21/30
user@PE4# set fe-1/2/2 unit 10 family mpls
user@PE4# set fe-1/0/2 unit 12 description PE4-to-PE3
user@PE4# set fe-1/0/2 unit 12 family inet address 10.0.0.25/30
user@PE4# set fe-1/0/2 unit 12 family mpls
user@PE4# set lo0 unit 7 family inet address 10.9.9.4/32
user@PE4# set lo0 unit 7 family inet address 10.100.1.4/32

```

2. Configure MPLS and a signaling protocol, such as RSVP or LDP.

```

[edit protocols]
user@PE4# set rsvp interface fe-1/2/0.7
user@PE4# set rsvp interface fe-1/2/1.9
user@PE4# set rsvp interface fe-1/2/2.10
user@PE4# set rsvp interface fe-1/0/2.12
user@PE4# set mpls label-switched-path PE4-to-PE2 to 10.9.9.5
user@PE4# set mpls label-switched-path PE4-to-PE3 to 10.9.9.6
user@PE4# set mpls label-switched-path PE4-to-P1 to 10.9.9.2
user@PE4# set mpls label-switched-path PE4-to-P2 to 10.9.9.3
user@PE4# set mpls interface fe-1/2/0.7
user@PE4# set mpls interface fe-1/2/1.9
user@PE4# set mpls interface fe-1/2/2.10
user@PE4# set mpls interface fe-1/0/2.12

```

3. Configure BGP.

```

[edit protocols bgp]
user@PE4# set export next-hop
user@PE4# set export aigp
user@PE4# set group internal type internal
user@PE4# set group internal local-address 10.9.9.4
user@PE4# set group internal neighbor 10.9.9.1
user@PE4# set group internal neighbor 10.9.9.3

```

```

user@PE4# set group internal neighbor 10.9.9.2
user@PE4# set group external type external
user@PE4# set group external multihop ttl 2
user@PE4# set group external local-address 10.9.9.4
user@PE4# set group external peer-as 7018
user@PE4# set group external neighbor 10.9.9.5
user@PE4# set group external neighbor 10.9.9.6

```

4. Enable AIGP.

```

[edit protocols bgp]
user@PE4# set group external family inet labeled-unicast aigp
user@PE4# set group internal family inet labeled-unicast aigp

```

5. Originate a prefix, and configure an AIGP distance.

By default, a prefix is originated using the current IGP distance. Optionally, you can configure a distance for the AIGP attribute, using the **distance** option, as shown here.

```

[edit policy-options policy-statement aigp term 10]
user@PE4# set from protocol static
user@PE4# set from route-filter 44.0.0.0/24 exact
user@PE4# set then aigp-originate distance 200
user@PE4# set then next-hop 10.100.1.4
user@PE4# set then accept

```

6. Enable the policies.

```

[edit policy-options policy-statement next-hop]
user@PE4# set term 10 from protocol bgp
user@PE4# set term 10 then next-hop 10.100.1.4
user@PE4# set term 10 then accept
user@PE4# set term 20 from protocol direct
user@PE4# set term 20 from route-filter 10.9.9.4/32 exact
user@PE4# set term 20 from route-filter 10.100.1.4/32 exact
user@PE4# set term 20 then next-hop 10.100.1.4
user@PE4# set term 20 then accept

```

7. Configure a static route.

```

[edit routing-options]
user@PE4# set static route 44.0.0.0/24 discard

```

8. Configure an IGP, such as OSPF, RIP, or IS-IS.

```

[edit protocols ospf]
user@PE4# set area 0.0.0.0 interface fe-1/2/1.9 metric 1
user@PE4# set area 0.0.0.0 interface fe-1/2/0.7 metric 1
user@PE4# set area 0.0.0.0 interface 10.9.9.4 passive
user@PE4# set area 0.0.0.0 interface 10.9.9.4 metric 1
user@PE4# set area 0.0.0.0 interface 10.100.1.4 passive
user@PE4# set area 0.0.0.0 interface 10.100.1.4 metric 1
user@PE4# set area 0.0.0.2 interface fe-1/2/2.10 metric 1
user@PE4# set area 0.0.0.3 interface fe-1/0/2.12 metric 1

```

9. Configure the router ID and the autonomous system number.

```

[edit routing-options]

```

```
user@PE4# set router-id 10.9.9.4
user@PE4# set autonomous-system 13979
```

10. If you are done configuring the device, commit the configuration.

```
user@PE4# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE4# show interfaces
fe-1/0/2 {
  unit 12 {
    description PE4-to-PE3;
    family inet {
      address 10.0.0.25/30;
    }
    family mpls;
  }
}
fe-1/2/0 {
  unit 7 {
    description PE4-to-P2;
    family inet {
      address 10.0.0.14/30;
    }
    family mpls;
  }
}
fe-1/2/1 {
  unit 9 {
    description PE4-to-P1;
    family inet {
      address 10.0.0.18/30;
    }
    family mpls;
  }
}
fe-1/2/2 {
  unit 10 {
    description PE4-to-PE2;
    family inet {
      address 10.0.0.21/30;
    }
    family mpls;
  }
}
lo0 {
  unit 7 {
    family inet {
      address 10.9.9.4/32;
      address 10.100.1.4/32;
    }
  }
}
```



```
    }  
  }  
user@PE4# show policy-options  
policy-statement aigp {  
  term 10 {  
    from {  
      protocol static;  
      route-filter 44.0.0.0/24 exact;  
    }  
    then {  
      aigp-originate distance 200;  
      next-hop 10.100.1.4;  
      accept;  
    }  
  }  
}  
policy-statement next-hop {  
  term 10 {  
    from protocol bgp;  
    then {  
      next-hop 10.100.1.4;  
      accept;  
    }  
  }  
  term 20 {  
    from {  
      protocol direct;  
      route-filter 10.9.9.4/32 exact;  
      route-filter 10.100.1.4/32 exact;  
    }  
    then {  
      next-hop 10.100.1.4;  
      accept;  
    }  
  }  
}  
user@PE4# show protocols  
rsvp {  
  interface fe-1/2/0.7;  
  interface fe-1/2/1.9;  
  interface fe-1/2/2.10;  
  interface fe-1/0/2.12;  
}  
mpls {  
  label-switched-path PE4-to-PE2 {  
    to 10.9.9.5;  
  }  
  label-switched-path PE4-to-PE3 {  
    to 10.9.9.6;  
  }  
  label-switched-path PE4-to-P1 {  
    to 10.9.9.2;  
  }  
  label-switched-path PE4-to-P2 {  
    to 10.9.9.3;  
  }  
}
```

```
    }
    interface fe-1/2/0.7;
    interface fe-1/2/1.9;
    interface fe-1/2/2.10;
    interface fe-1/0/2.12;
  }
  bgp {
    export [ next-hop aigp ];
    group internal {
      type internal;
      local-address 10.9.9.4;
      family inet {
        labeled-unicast {
          aigp;
        }
      }
      neighbor 10.9.9.1;
      neighbor 10.9.9.3;
      neighbor 10.9.9.2;
    }
    group external {
      type external;
      multihop {
        ttl 2;
      }
      local-address 10.9.9.4;
      family inet {
        labeled-unicast {
          aigp;
        }
      }
      peer-as 7018;
      neighbor 10.9.9.5;
      neighbor 10.9.9.6;
    }
  }
  ospf {
    area 0.0.0.0 {
      interface fe-1/2/1.9 {
        metric 1;
      }
      interface fe-1/2/0.7 {
        metric 1;
      }
      interface 10.9.9.4 {
        passive;
        metric 1;
      }
      interface 10.100.1.4 {
        passive;
        metric 1;
      }
    }
    area 0.0.0.2 {
      interface fe-1/2/2.10 {
        metric 1;
      }
    }
  }
}
```

```

    }
  }
  area 0.0.0.3 {
    interface fe-1/0/2.12 {
      metric 1;
    }
  }
}

user@PE4# show routing-options
static {
  route 44.0.0.0/24 discard;
}
router-id 10.9.9.4;
autonomous-system 13979;

```

### Configuring Device PE1

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device PE1:

1. Configure the interfaces.

```

[edit interfaces]
user@PE1# set fe-1/2/0 unit 0 description PE1-to-P1
user@PE1# set fe-1/2/0 unit 0 family inet address 10.0.0.1/30
user@PE1# set fe-1/2/0 unit 0 family mpls
user@PE1# set fe-1/2/1 unit 2 description PE1-to-P2
user@PE1# set fe-1/2/1 unit 2 family inet address 10.0.0.5/30
user@PE1# set fe-1/2/1 unit 2 family mpls
user@PE1# set fe-1/2/2 unit 14 description PE1-to-PE7
user@PE1# set fe-1/2/2 unit 14 family inet address 10.0.0.9/30
user@PE1# set lo0 unit 1 family inet address 10.9.9.1/32
user@PE1# set lo0 unit 1 family inet address 10.100.1.1/32

```

2. Configure MPLS and a signaling protocol, such as RSVP or LDP.

```

[edit protocols]
user@PE1# set rsvp interface fe-1/2/0.0
user@PE1# set rsvp interface fe-1/2/1.2
user@PE1# set rsvp interface fe-1/2/2.14
user@PE1# set mpls label-switched-path PE1-to-P1 to 10.9.9.2
user@PE1# set mpls label-switched-path PE1-to-P2 to 10.9.9.3
user@PE1# set mpls interface fe-1/2/0.0
user@PE1# set mpls interface fe-1/2/1.2
user@PE1# set mpls interface fe-1/2/2.14

```

3. Configure BGP.

```

[edit protocols bgp]
user@PE1# set group internal type internal
user@PE1# set group internal local-address 10.9.9.1
user@PE1# set group internal export SET_EXPORT_ROUTES
user@PE1# set group internal vpn-apply-export

```

```

user@PE1# set group internal neighbor 10.9.9.4
user@PE1# set group internal neighbor 10.9.9.2
user@PE1# set group internal neighbor 10.9.9.3
user@PE1# set group external type external
user@PE1# set group external export SET_EXPORT_ROUTES
user@PE1# set group external peer-as 7019
user@PE1# set group external neighbor 10.0.0.10

```

4. Enable AIGP.

```

[edit protocols bgp]
user@PE1# set group internal family inet labeled-unicast aigp
user@PE1# set group external family inet labeled-unicast aigp

```

5. Enable the policies.

```

[edit policy-options policy-statement SET_EXPORT_ROUTES term 10]
user@PE1# set from protocol direct
user@PE1# set from protocol bgp
user@PE1# set then next-hop 10.100.1.1
user@PE1# set then accept

```

6. Configure an IGP, such as OSPF, RIP, or IS-IS.

```

[edit protocols ospf area 0.0.0.1]
user@PE1# set interface fe-1/2/0.0 metric 1
user@PE1# set interface fe-1/2/1.2 metric 1
user@PE1# set interface 10.9.9.1 passive
user@PE1# set interface 10.9.9.1 metric 1
user@PE1# set interface 10.100.1.1 passive
user@PE1# set interface 10.100.1.1 metric 1

```

7. Configure the router ID and the autonomous system number.

```

[edit routing-options]
user@PE1# set router-id 10.9.9.1
user@PE1# set autonomous-system 13979

```

8. If you are done configuring the device, commit the configuration.

```

user@PE1# commit

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE1# show interfaces
fe-1/2/0 {
  unit 0 {
    description PE1-to-P1;
    family inet {
      address 10.0.0.1/30;
    }
    family mpls;
  }
}
fe-1/2/1 {

```

```

    unit 2 {
      description PE1-to-P2;
      family inet {
        address 10.0.0.5/30;
      }
      family mpls;
    }
  }
  fe-1/2/2 {
    unit 14 {
      description PE1-to-PE7;
      family inet {
        address 10.0.0.9/30;
      }
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 10.9.9.1/32;
      address 10.100.1.1/32;
    }
  }
}

user@PE1# show policy-options
policy-statement SET_EXPORT_ROUTES {
  term 10 {
    from protocol [ direct bgp ];
    then {
      next-hop 10.100.1.1;
      accept;
    }
  }
}

user@PE1# show protocols
rsvp {
  interface fe-1/2/0.0;
  interface fe-1/2/1.2;
  interface fe-1/2/2.14;
}
mpls {
  label-switched-path PE1-to-P1 {
    to 10.9.9.2;
  }
  label-switched-path PE1-to-P2 {
    to 10.9.9.3;
  }
  interface fe-1/2/0.0;
  interface fe-1/2/1.2;
  interface fe-1/2/2.14;
}
bgp {
  group internal {
    type internal;
    local-address 10.9.9.1;
  }
}

```

```
family inet {
    labeled-unicast {
        aigp;
    }
}
export SET_EXPORT_ROUTES;
vpn-apply-export;
neighbor 10.9.9.4;
neighbor 10.9.9.2;
neighbor 10.9.9.3;
}
group external {
    type external;
    family inet {
        labeled-unicast {
            aigp;
        }
    }
    export SET_EXPORT_ROUTES;
    peer-as 7019;
    neighbor 10.0.0.10;
}
}
ospf {
    area 0.0.0.1 {
        interface fe-1/2/0.0 {
            metric 1;
        }
        interface fe-1/2/1.2 {
            metric 1;
        }
        interface 10.9.9.1 {
            passive;
            metric 1;
        }
        interface 10.100.1.1 {
            passive;
            metric 1;
        }
    }
}
}
```

```
user@PE1# show routing-options
router-id 10.9.9.1;
autonomous-system 13979;
```

### Configuring Device PE2

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device PE2:

1. Configure the interfaces.

```
[edit interfaces]
user@PE2# set fe-1/2/0 unit 11 description PE2-to-PE4
user@PE2# set fe-1/2/0 unit 11 family inet address 10.0.0.22/30
user@PE2# set fe-1/2/0 unit 11 family mpls
user@PE2# set lo0 unit 9 family inet address 10.9.9.5/32 primary
user@PE2# set lo0 unit 9 family inet address 10.100.1.5/32
```

2. Configure MPLS and a signaling protocol, such as RSVP or LDP.

```
[edit protocols]
user@PE2# set rsvp interface fe-1/2/0.11
user@PE2# set mpls label-switched-path PE2-to-PE4 to 10.9.9.4
user@PE2# set mpls interface fe-1/2/0.11
```

3. Configure BGP.

```
[edit protocols bgp]
user@PE2# set group external type external
user@PE2# set group external multihop ttl 2
user@PE2# set group external local-address 10.9.9.5
user@PE2# set group external export next-hop
user@PE2# set group external export aigp
user@PE2# set group external export SET_EXPORT_ROUTES
user@PE2# set group external vpn-apply-export
user@PE2# set group external peer-as 13979
user@PE2# set group external neighbor 10.9.9.4
```

4. Enable AIGP.

```
[edit protocols bgp]
user@PE2# set group external family inet labeled-unicast aigp
```

5. Originate a prefix, and configure an AIGP distance.

By default, a prefix is originated using the current IGP distance. Optionally, you can configure a distance for the AIGP attribute, using the **distance** option, as shown here.

```
[edit policy-options policy-statement aigp]
user@PE2# set term 10 from route-filter 55.0.0.0/24 exact
user@PE2# set term 10 then aigp-originate distance 20
user@PE2# set term 10 then next-hop 10.100.1.5
user@PE2# set term 10 then accept
user@PE2# set term 20 from route-filter 99.0.0.0/24 exact
user@PE2# set term 20 then aigp-originate distance 30
user@PE2# set term 20 then next-hop 10.100.1.5
user@PE2# set term 20 then accept
```

6. Enable the policies.

```
[edit policy-options]
user@PE2# set policy-statement SET_EXPORT_ROUTES term 10 from protocol
direct
user@PE2# set policy-statement SET_EXPORT_ROUTES term 10 from protocol
static
user@PE2# set policy-statement SET_EXPORT_ROUTES term 10 from protocol
bgp
user@PE2# set policy-statement SET_EXPORT_ROUTES term 10 then next-hop
10.100.1.5
user@PE2# set policy-statement SET_EXPORT_ROUTES term 10 then accept
user@PE2# set policy-statement next-hop term 10 from protocol bgp
user@PE2# set policy-statement next-hop term 10 then next-hop 10.100.1.5
user@PE2# set policy-statement next-hop term 10 then accept
user@PE2# set policy-statement next-hop term 20 from protocol direct
user@PE2# set policy-statement next-hop term 20 from route-filter 10.9.9.5/32
exact
user@PE2# set policy-statement next-hop term 20 from route-filter 10.100.1.5/32
exact
user@PE2# set policy-statement next-hop term 20 then next-hop 10.100.1.5
user@PE2# set policy-statement next-hop term 20 then accept
```

7. Enable some static routes.

```
[edit routing-options]
user@PE2# set static route 99.0.0.0/24 discard
user@PE2# set static route 55.0.0.0/24 discard
```

8. Configure an IGP, such as OSPF, RIP, or IS-IS.

```
[edit protocols ospf area 0.0.0.2]
user@PE2# set interface 10.9.9.5 passive
user@PE2# set interface 10.9.9.5 metric 1
user@PE2# set interface 10.100.1.5 passive
user@PE2# set interface 10.100.1.5 metric 1
user@PE2# set interface fe-1/2/0.11 metric 1
```

9. Configure the router ID and the autonomous system number.

```
[edit routing-options]
user@PE2# set router-id 10.9.9.5
user@PE2# set autonomous-system 7018
```

10. If you are done configuring the device, commit the configuration.

```
user@PE2# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE2# show interfaces
fe-1/2/0 {
  unit 11 {
    description PE2-to-PE4;
```



```
        family inet {
            address 10.0.0.22/30;
        }
        family mpls;
    }
}
lo0 {
    unit 9 {
        family inet {
            address 10.9.9.5/32 {
                primary;
            }
            address 10.100.1.5/32;
        }
    }
}

user@PE2# show policy-options
policy-statement SET_EXPORT_ROUTES {
    term 10 {
        from protocol [ direct static bgp ];
        then {
            next-hop 10.100.1.5;
            accept;
        }
    }
}

policy-statement aigp {
    term 10 {
        from {
            route-filter 55.0.0.0/24 exact;
        }
        then {
            aigp-originate distance 20;
            next-hop 10.100.1.5;
            accept;
        }
    }
    term 20 {
        from {
            route-filter 99.0.0.0/24 exact;
        }
        then {
            aigp-originate distance 30;
            next-hop 10.100.1.5;
            accept;
        }
    }
}

policy-statement next-hop {
    term 10 {
        from protocol bgp;
        then {
            next-hop 10.100.1.5;
            accept;
        }
    }
}
```

```
}
term 20 {
  from {
    protocol direct;
    route-filter 10.9.9.5/32 exact;
    route-filter 10.100.1.5/32 exact;
  }
  then {
    next-hop 10.100.1.5;
    accept;
  }
}
}

user@PE2# show protocols
rsvp {
  interface fe-1/2/0.11;
}
mpls {
  label-switched-path PE2-to-PE4 {
    to 10.9.9.4;
  }
  interface fe-1/2/0.11;
}
bgp {
  group external {
    type external;
    multihop {
      ttl 2;
    }
    local-address 10.9.9.5;
    family inet {
      labeled-unicast {
        aigp;
      }
    }
    export [ next-hop aigp SET_EXPORT_ROUTES ];
    vpn-apply-export;
    peer-as 13979;
    neighbor 10.9.9.4;
  }
}
ospf {
  area 0.0.0.2 {
    interface 10.9.9.5 {
      passive;
      metric 1;
    }
    interface 10.100.1.5 {
      passive;
      metric 1;
    }
    interface fe-1/2/0.11 {
      metric 1;
    }
  }
}
```

```

}
user@PE2# show routing-options
static {
    route 99.0.0.0/24 discard;
    route 55.0.0.0/24 discard;
}
router-id 10.9.9.5;
autonomous-system 7018;

```

### Configuring Device PE3

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device PE3:

1. Configure the interfaces.

```

[edit interfaces]
user@PE3# set fe-1/2/0 unit 13 description PE3-to-PE4
user@PE3# set fe-1/2/0 unit 13 family inet address 10.0.0.26/30
user@PE3# set fe-1/2/0 unit 13 family mpls
user@PE3# set lo0 unit 11 family inet address 10.9.9.6/32
user@PE3# set lo0 unit 11 family inet address 10.100.1.6/32

```

2. Configure MPLS and a signaling protocol, such as RSVP or LDP.

```

[edit protocols]
user@PE3# set rsvp interface fe-1/2/0.13
user@PE3# set mpls label-switched-path PE3-to-PE4 to 10.9.9.4
user@PE3# set mpls interface fe-1/2/0.13

```

3. Configure BGP.

```

[edit protocols bgp group external]
user@PE3# set type external
user@PE3# set multihop ttl 2
user@PE3# set local-address 10.9.9.6
user@PE3# set export next-hop
user@PE3# set export SET_EXPORT_ROUTES
user@PE3# set vpn-apply-export
user@PE3# set peer-as 13979
user@PE3# set neighbor 10.9.9.4

```

4. Enable AIGP.

```

[edit protocols bgp group external]
user@PE3# set family inet labeled-unicast aigp

```

5. Enable the policies.

```

[edit policy-options]
user@PE3# set policy-statement SET_EXPORT_ROUTES term 10 from protocol
    direct
user@PE3# set policy-statement SET_EXPORT_ROUTES term 10 from protocol
    static

```

```

user@PE3# set policy-statement SET_EXPORT_ROUTES term 10 from protocol
bgp
user@PE3# set policy-statement SET_EXPORT_ROUTES term 10 then next-hop
10.100.1.6
user@PE3# set policy-statement SET_EXPORT_ROUTES term 10 then accept
user@PE3# set policy-statement next-hop term 10 from protocol bgp
user@PE3# set policy-statement next-hop term 10 then next-hop 10.100.1.6
user@PE3# set policy-statement next-hop term 10 then accept
user@PE3# set policy-statement next-hop term 20 from protocol direct
user@PE3# set policy-statement next-hop term 20 from route-filter 10.9.9.6/32
exact
user@PE3# set policy-statement next-hop term 20 from route-filter 10.100.1.6/32
exact
user@PE3# set policy-statement next-hop term 20 then next-hop 10.100.1.6
user@PE3# set policy-statement next-hop term 20 then accept

```

6. Configure an IGP, such as OSPF, RIP, or IS-IS.

```

[edit protocols ospf area 0.0.0.3]
user@PE3# set interface 10.9.9.6 passive
user@PE3# set interface 10.9.9.6 metric 1
user@PE3# set interface 10.100.1.6 passive
user@PE3# set interface 10.100.1.6 metric 1
user@PE3# set interface fe-1/2/0.13 metric 1

```

7. Configure the router ID and the autonomous system number.

```

[edit routing-options]
user@PE3# set router-id 10.9.9.6
user@PE3# set autonomous-system 7018

```

8. If you are done configuring the device, commit the configuration.

```

user@PE3# commit

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE3# show interfaces
fe-1/2/0 {
  unit 13 {
    description PE3-to-PE4;
    family inet {
      address 10.0.0.26/30;
    }
    family mpls;
  }
}
lo0 {
  unit 11 {
    family inet {
      address 10.9.9.6/32;
      address 10.100.1.6/32;
    }
  }
}

```

```

    }
  }
user@PE3# show policy-options
policy-statement SET_EXPORT_ROUTES {
  term 10 {
    from protocol [ direct static bgp ];
    then {
      next-hop 10.100.1.6;
      accept;
    }
  }
}
policy-statement next-hop {
  term 10 {
    from protocol bgp;
    then {
      next-hop 10.100.1.6;
      accept;
    }
  }
  term 20 {
    from {
      protocol direct;
      route-filter 10.9.9.6/32 exact;
      route-filter 10.100.1.6/32 exact;
    }
    then {
      next-hop 10.100.1.6;
      accept;
    }
  }
}
user@PE3# show protocols
rsvp {
  interface fe-1/2/0.13;
}
mpls {
  label-switched-path PE3-to-PE4 {
    to 10.9.9.4;
  }
  interface fe-1/2/0.13;
}
bgp {
  group external {
    type external;
    multihop {
      ttl 2;
    }
    local-address 10.9.9.6;
    family inet {
      labeled-unicast {
        aigp;
      }
    }
  }
  export [ next-hop SET_EXPORT_ROUTES ];
}

```

```
        vpn-apply-export;
        peer-as 13979;
        neighbor 10.9.9.4;
    }
}
ospf {
    area 0.0.0.3 {
        interface 10.9.9.6 {
            passive;
            metric 1;
        }
        interface 10.100.1.6 {
            passive;
            metric 1;
        }
        interface fe-1/2/0.13 {
            metric 1;
        }
    }
}

user@PE3# show routing-options
router-id 10.9.9.6;
autonomous-system 7018;
```

### **Configuring Device PE7**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device PE7:

1. Configure the interfaces.

```
[edit interfaces]
user@PE7# set fe-1/2/0 unit 15 description PE7-to-PE1
user@PE7# set fe-1/2/0 unit 15 family inet address 10.0.0.10/30
user@PE7# set lo0 unit 13 family inet address 10.9.9.7/32
user@PE7# set lo0 unit 13 family inet address 10.100.1.7/32
```

2. Configure BGP.

```
[edit protocols bgp group external]
user@PE7# set type external
user@PE7# set export SET_EXPORT_ROUTES
user@PE7# set peer-as 13979
user@PE7# set neighbor 10.0.0.9
```

3. Enable AIGP.

```
[edit protocols bgp group external]
user@PE7# set family inet labeled-unicast aigp
```

4. Configure the routing policy.

```
[edit policy-options policy-statement SET_EXPORT_ROUTES term 10]
user@PE7# set from protocol direct
```

```

user@PE7# set from protocol bgp
user@PE7# set then next-hop 10.100.1.7
user@PE7# set then accept

```

5. Configure the router ID and the autonomous system number.

```

[edit routing-options]
user@PE7# set router-id 10.9.9.7
user@PE7# set autonomous-system 7019

```

6. If you are done configuring the device, commit the configuration.

```

user@PE7# commit

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE7# show interfaces
interfaces {
  fe-1/2/0 {
    unit 15 {
      description PE7-to-PE1;
      family inet {
        address 10.0.0.10/30;
      }
    }
  }
  lo0 {
    unit 13 {
      family inet {
        address 10.9.9.7/32;
        address 10.100.1.7/32;
      }
    }
  }
}

user@PE7# show policy-options
policy-statement SET_EXPORT_ROUTES {
  term 10 {
    from protocol [ direct bgp ];
    then {
      next-hop 10.100.1.7;
      accept;
    }
  }
}

user@PE7# show protocols
bgp {
  group external {
    type external;
    family inet {
      labeled-unicast {
        aigp;
      }
    }
  }
}

```

```

    }
  }
  export SET_EXPORT_ROUTES;
  peer-as 13979;
  neighbor 10.0.0.9;
}
}

user@PE7# show routing-options
router-id 10.9.9.7;
autonomous-system 7019;

```

### Verification

Confirm that the configuration is working properly.

- [Verifying That Device PE4 Is Receiving the AIGP Attribute from Its EBGp Neighbor PE2 on page 166](#)
- [Checking the IGP Metric on page 166](#)
- [Verifying That Device PE4 Adds the IGP Metric to the AIGP Attribute on page 167](#)
- [Verifying That Device PE7 Is Receiving the AIGP Attribute from Its EBGp Neighbor PE1 on page 167](#)
- [Verifying the Resolving AIGP Metric on page 168](#)
- [Verifying the Presence of AIGP Attributes in BGP Updates on page 171](#)

#### *Verifying That Device PE4 Is Receiving the AIGP Attribute from Its EBGp Neighbor PE2*

**Purpose** Make sure that the AIGP policy on Device PE2 is working.

**Action**

```

user@PE4> show route receive-protocol bgp 10.9.9.5 extensive
* 55.0.0.0/24 (1 entry, 1 announced)
  Accepted
  Route Label: 299888
  Nexthop: 10.100.1.5
  AS path: 7018 I
  AIGP: 20

* 99.0.0.0/24 (1 entry, 1 announced)
  Accepted
  Route Label: 299888
  Nexthop: 10.100.1.5
  AS path: 7018 I
  AIGP: 30

```

**Meaning** On Device PE2, the **aigp-originate** statement is configured with a distance of 20 (**aigp-originate distance 20**). This statement is applied to route 55.0.0.0/24. Likewise, the **aigp-originate distance 30** statement is applied to route 99.0.0.0/24. Thus, when Device PE4 receives these routes, the AIGP attribute is attached with the configured metrics.

#### *Checking the IGP Metric*

**Purpose** From Device PE4, check the IGP metric to the BGP next hop 10.100.1.5.



**Action** user@PE4> show route 10.100.1.5  
 inet.0: 30 destinations, 40 routes (30 active, 0 holddown, 0 hidden)  
 + = Active Route, - = Last Active, \* = Both

```

10.100.1.5/32      * [OSPF/10] 05:35:50, metric 2
                   > to 10.0.0.22 via fe-1/2/2.10
                   [BGP/170] 03:45:07, localpref 100, from 10.9.9.5
                   AS path: 7018 I
                   > to 10.0.0.22 via fe-1/2/2.10
  
```

**Meaning** The IGP metric for this route is 2.

#### *Verifying That Device PE4 Adds the IGP Metric to the AIGP Attribute*

**Purpose** Make sure that Device PE4 adds the IGP metric to the AIGP attribute when it readvertises routes to its IBGP neighbor, Device PE1.

**Action** user@PE4> show route advertising-protocol bgp 10.9.9.1 extensive

```

* 55.0.0.0/24 (1 entry, 1 announced)
  BGP group internal type Internal
  Route Label: 300544
  Nexthop: 10.100.1.4
  Flags: Nexthop Change
  Localpref: 100
  AS path: [13979] 7018 I
  AIGP: 22

* 99.0.0.0/24 (1 entry, 1 announced)
  BGP group internal type Internal
  Route Label: 300544
  Nexthop: 10.100.1.4
  Flags: Nexthop Change
  Localpref: 100
  AS path: [13979] 7018 I
  AIGP: 32
  
```

**Meaning** The IGP metric is added to the AIGP metric ( $20 + 2 = 22$  and  $30 + 2 = 32$ ), because the next hop is changed for these routes.

#### *Verifying That Device PE7 Is Receiving the AIGP Attribute from Its EBGP Neighbor PE1*

**Purpose** Make sure that the AIGP policy on Device PE1 is working.

**Action** user@PE7> show route receive-protocol bgp 10.0.0.9 extensive

\* 44.0.0.0/24 (1 entry, 1 announced)

Accepted  
Route Label: 300096  
Nexthop: 10.0.0.9  
AS path: 13979 I  
AIGP: 203

\* 55.0.0.0/24 (1 entry, 1 announced)

Accepted  
Route Label: 300112  
Nexthop: 10.0.0.9  
AS path: 13979 7018 I  
AIGP: 25

\* 99.0.0.0/24 (1 entry, 1 announced)

Accepted  
Route Label: 300112  
Nexthop: 10.0.0.9  
AS path: 13979 7018 I  
AIGP: 35

**Meaning** The 44.0.0.0/24 route is originated at Device PE4. The 55.0.0.0/24 and 99.0.0.0/24 routes are originated at Device PE2. The IGP distances are added to the configured AIGP distances.

#### *Verifying the Resolving AIGP Metric*

**Purpose** Confirm that if the prefix is resolved through recursion and the recursive next hops have AIGP metrics, the prefix has the sum of the AIGP values that are on the recursive BGP next hops.

**Action** 1. Add a static route to 66.0.0.0/24.

```
[edit routing-options]
user@PE2# set static route 66.0.0.0/24 discard
```

2. Delete the existing terms in the **aigp** policy statement on Device PE2.

```
[edit policy-options policy-statement aigp]
user@PE2# delete term 10
user@PE2# delete term 20
```

3. Configure a recursive route lookup for the route to 66.0.0.0.

The policy shows the AIGP metric for prefix 66.0.0.0/24 (none) and its recursive next hop. Prefix 66.0.0.0/24 is resolved by 55.0.0.1. Prefix 66.0.0.0/24 does not have its own AIGP metric being originated, but its recursive next hop, 55.0.0.1, has an AIGP value.

```
[edit policy-options policy-statement aigp]
user@PE2# set term 10 from route-filter 55.0.0.1/24 exact
user@PE2# set term 10 then aigp-originate distance 20
user@PE2# set term 10 then next-hop 10.100.1.5
user@PE2# set term 10 then accept
user@PE2# set term 20 from route-filter 66.0.0.0/24 exact
user@PE2# set term 20 then next-hop 55.0.0.1
```

**user@PE2# set term 20 then accept**

4. On Device PE4, run the **show route 55.0.0.0 extensive** command.

The value of Metric2 is the IGP metric to the BGP next hop. When Device PE4 readvertises these routes to its IBGP peer, Device PE1, the AIGP metric is the sum of AIGP + its Resolving AIGP metric + Metric2.

Prefix 55.0.0.0 shows its own IGP metric 20, as defined and advertised by Device PE2. It does not show a resolving AIGP value because it does not have a recursive BGP next hop. The value of Metric2 is 2.

```
user@PE4> show route 55.0.0.0 extensive
inet.0: 31 destinations, 41 routes (31 active, 0 holddown, 0 hidden)
55.0.0.0/24 (1 entry, 1 announced)
TSI:
KRT in-kernel 55.0.0.0/24 -> {indirect(262151)}
Page 0 idx 0 Type 1 val 928d1b8
  Flags: Nexthop Change
  Nexthop: 10.100.1.4
  Localpref: 100
  AS path: [13979] 7018 I
  Communities:
  AIGP: 22
Path 55.0.0.0 from 10.9.9.5 Vector len 4. Val: 0
  *BGP   Preference: 170/-101
        Next hop type: Indirect
        Address: 0x925da38
        Next-hop reference count: 4
        Source: 10.9.9.5
        Next hop type: Router, Next hop index: 1004
        Next hop: 10.0.0.22 via fe-1/2/2.10, selected
        Label operation: Push 299888
        Label TTL action: prop-ttl
        Protocol next hop: 10.100.1.5
        Push 299888
        Indirect next hop: 93514d8 262151
        State: <Active Ext>
        Local AS: 13979 Peer AS: 7018
        Age: 22:03:26   Metric2: 2
        AIGP: 20
        Task: BGP_7018.10.9.9.5+58560
        Announcement bits (3): 3-KRT 4-BGP_RT_Background 5-Resolve tree 1
        AS path: 7018 I
        Accepted
        Route Label: 299888
        Localpref: 100
        Router ID: 10.9.9.5
        Indirect next hops: 1
          Protocol next hop: 10.100.1.5 Metric: 2
          Push 299888
          Indirect next hop: 93514d8 262151
          Indirect path forwarding next hops: 1
            Next hop type: Router
            Next hop: 10.0.0.22 via fe-1/2/2.10
            10.100.1.5/32 Originating RIB: inet.0
            Metric: 2                               Node path count: 1
            Forwarding nexthops: 1
              Nexthop: 10.0.0.22 via fe-1/2/2.10
```

5. On Device PE4, run the **show route 66.0.0.0 extensive** command.

Prefix 66.0.0.0/24 shows the Resolving AIGP, which is the sum of its own AIGP metric and its recursive BGP next hop:

66.0.0.1 = 0, 55.0.0.1 = 20, 0+20 = 20

```

user@PE4> show route 66.0.0.0 extensive
inet.0: 31 destinations, 41 routes (31 active, 0 holddown, 0 hidden)
66.0.0.0/24 (1 entry, 1 announced)
TSI:
KRT in-kernel 66.0.0.0/24 -> {indirect(262162)}
Page 0 idx 0 Type 1 val 928cefc
  Flags: Nexthop Change
  Nexthop: 10.100.1.4
  Localpref: 100
  AS path: [13979] 7018 I
  Communities:
Path 66.0.0.0 from 10.9.9.5 Vector len 4. Val: 0
  *BGP Preference: 170/-101
    Next hop type: Indirect
    Address: 0x925d4e0
    Next-hop reference count: 4
    Source: 10.9.9.5
    Next hop type: Router, Next hop index: 1006
    Next hop: 10.0.0.22 via fe-1/2/2.10, selected
    Label operation: Push 299888, Push 299888(top)
    Label TTL action: prop-ttl, prop-ttl(top)
    Protocol next hop: 55.0.0.1
    Push 299888
    Indirect next hop: 9353e88 262162
    State: <Active Ext>
    Local AS: 13979 Peer AS: 7018
    Age: 31:42 Metric2:2
    Resolving-AIGP: 20
    Task: BGP_7018.10.9.9.5+58560
    Announcement bits (3): 3-KRT 4-BGP_RT_Background 5-Resolve tree 1
    AS path: 7018 I
    Accepted
    Route Label: 299888
    Localpref: 100
    Router ID: 10.9.9.5
    Indirect next hops: 1
      Protocol next hop: 55.0.0.1 Metric: 2 AIGP: 20
      Push 299888
      Indirect next hop: 9353e88 262162
      Indirect path forwarding next hops: 1
        Next hop type: Router
        Next hop: 10.0.0.22 via fe-1/2/2.10
      55.0.0.0/24 Originating RIB: inet.0
        Metric: 2 Node path count: 1
        Indirect nexthops: 1
          Protocol Nexthop: 10.100.1.5 Metric: 2 Push 299888
          Indirect nexthop: 93514d8 262151
          Indirect path forwarding nexthops: 1
            Nexthop: 10.0.0.22 via fe-1/2/2.10
          10.100.1.5/32 Originating RIB: inet.0
            Metric: 2 Node path count: 1
            Forwarding nexthops: 1
              Nexthop: 10.0.0.22 via fe-1/2/2.10

```

*Verifying the Presence of AIGP Attributes in BGP Updates*

**Purpose** If the AIGP attribute is not enabled under BGP (or the **group** or **neighbor** hierarchies), the AIGP attribute is silently discarded. Enable **traceoptions** and include the **packets** flag in the **detail** option in the configuration to confirm the presence of the AIGP attribute in transmitted or received BGP updates. This is useful when debugging AIGP issues.

**Action** 1. Configure Device PE2 and Device PE4 for **traceoptions**.

```
user@host> show protocols bgp
traceoptions {
  file bgp size 1m files 5;
  flag packets detail;
}
```

2. Check the **traceoptions** file on Device PE2.

The following sample shows Device PE2 advertising prefix 99.0.0.0/24 to Device PE4 (10.9.9.4) with an AIGP metric of 20:

```
user@PE2> show log bgp
Mar 22 09:27:18.982150 BGP SEND 10.9.9.5+49652 -> 10.9.9.4+179
Mar 22 09:27:18.982178 BGP SEND message type 2 (Update) length 70
Mar 22 09:27:18.982198 BGP SEND Update PDU length 70
Mar 22 09:27:18.982248 BGP SEND flags 0x40 code Origin(1): IGP
Mar 22 09:27:18.982273 BGP SEND flags 0x40 code ASPath(2) length 6: 7018
Mar 22 09:27:18.982295 BGP SEND flags 0x80 code AIGP(26): AIGP: 20
Mar 22 09:27:18.982316 BGP SEND flags 0x90 code MP_reach(14): AFI/SAFI 1/4
Mar 22 09:27:18.982341 BGP SEND      nhop 10.100.1.5 len 4
Mar 22 09:27:18.982372 BGP SEND    99.0.0.0/24 (label 301664)
Mar 22 09:27:33.665412 bgp_send: sending 19 bytes to abcd::10:255:170:84
(External AS 13979)
```

3. Verify that the route was received on Device PE4 using the **show route receive-protocol** command.

AIGP is not enabled on Device PE4, so the AIGP attribute is silently discarded for prefix 99.0.0.0/24 and does not appear in the following output:

```
user@PE4> show route receive-protocol bgp 10.9.9.5 extensive | find 55.0.0.0
* 99.0.0.0/24 (2 entries, 1 announced)
  Accepted
  Route Label: 301728
  Nexthop: 10.100.1.5
  AS path: 7018 I
```

4. Check the **traceoptions** file on Device PE4.

The following output from the **traceoptions** log shows that the 99.0.0.0/24 prefix was received with the AIGP attribute attached:

```
user@PE4> show log bgp
Mar 22 09:41:39.650295 BGP RECV 10.9.9.5+64690 -> 10.9.9.4+179
Mar 22 09:41:39.650331 BGP RECV message type 2 (Update) length 70
Mar 22 09:41:39.650350 BGP RECV Update PDU length 70
Mar 22 09:41:39.650370 BGP RECV flags 0x40 code Origin(1): IGP
Mar 22 09:41:39.650394 BGP RECV flags 0x40 code ASPath(2) length 6: 7018
Mar 22 09:41:39.650415 BGP RECV flags 0x80 code AIGP(26): AIGP: 20
Mar 22 09:41:39.650436 BGP RECV flags 0x90 code MP_reach(14): AFI/SAFI 1/4
Mar 22 09:41:39.650459 BGP RECV      nhop 10.100.1.5 len 4
```

```
Mar 22 09:41:39.650495 BGP RECV    99.0.0.0/24 (label 301728)
Mar 22 09:41:39.650574 bgp_rcv_nlri: 99.0.0.0/24
Mar 22 09:41:39.650607 bgp_rcv_nlri: 99.0.0.0/24 belongs to meshgroup
Mar 22 09:41:39.650629 bgp_rcv_nlri: 99.0.0.0/24 qualified bnp->ribact 0x0
12afcb 0x0
```

**Meaning** Performing this verification helps with AIGP troubleshooting and debugging issues. It enables you to verify which devices in your network send and receive AIGP attributes.

- Related Documentation**
- [Understanding BGP Path Selection on page 202](#)
  - [Examples: Configuring Internal BGP Peering on page 36](#)

## CHAPTER 4

# BGP Policy Configuration

- [Example: Configuring BGP Interactions with IGPs on page 173](#)
- [Example: Configuring BGP Route Advertisement on page 177](#)
- [Example: Configuring EBGP Multihop on page 185](#)
- [Example: Configuring BGP Route Preference \(Administrative Distance\) on page 195](#)
- [Example: Configuring BGP Path Selection on page 202](#)
- [Example: Removing Private AS Numbers on page 212](#)

### Example: Configuring BGP Interactions with IGPs

---

- [Understanding Routing Policies on page 173](#)
- [Example: Injecting OSPF Routes into the BGP Routing Table on page 174](#)

### Understanding Routing Policies

Each routing policy is identified by a policy name. The name can contain letters, numbers, and hyphens (-) and can be up to 255 characters long. To include spaces in the name, enclose the entire name in double quotation marks. Each routing policy name must be unique within a configuration.

Once a policy is created and named, it must be applied before it is active. You apply routing policies using the **import** and **export** statements at the **protocols>protocol-name** level in the configuration hierarchy.

In the **import** statement, you list the name of the routing policy to be evaluated when routes are imported into the routing table from the routing protocol.

In the **export** statement, you list the name of the routing policy to be evaluated when routes are being exported from the routing table into a dynamic routing protocol. Only active routes are exported from the routing table.

To specify more than one policy and create a policy chain, you list the policies using a space as a separator. If multiple policies are specified, the policies are evaluated in the order in which they are specified. As soon as an accept or reject action is executed, the policy chain evaluation ends.

## Example: Injecting OSPF Routes into the BGP Routing Table

This example shows how to create a policy that injects OSPF routes into the BGP routing table.

- [Requirements on page 174](#)
- [Overview on page 174](#)
- [Configuration on page 174](#)
- [Verification on page 176](#)
- [Troubleshooting on page 176](#)

---

### Requirements

Before you begin:

- Configure network interfaces.
- Configure external peer sessions. See [“Example: Configuring External BGP Point-to-Point Peer Sessions” on page 14](#).
- Configure interior gateway protocol (IGP) sessions between peers.

---

### Overview

In this example, you create a routing policy called **injectpolicy1** and a routing term called **injectterm1**. The policy injects OSPF routes into the BGP routing table.

---

### Configuration

- [Configuring the Routing Policy on page 174](#)
- [Configuring Tracing for the Routing Policy on page 175](#)

#### *Configuring the Routing Policy*

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then enter **commit** from configuration mode.

```
set policy-options policy-statement injectpolicy1 term injectterm1 from protocol ospf
set policy-options policy-statement injectpolicy1 term injectterm1 from area 0.0.0.1
set policy-options policy-statement injectpolicy1 term injectterm1 then accept
set protocols bgp export injectpolicy1
```

#### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To inject OSPF routes into a BGP routing table:

1. Create the policy term.

```
[edit policy-options policy-statement injectpolicy1]
```



```
user@host# set term injectterm1
```

2. Specify OSPF as a match condition.

```
[edit policy-options policy-statement injectpolicy1 term injectterm1]
user@host# set from protocol ospf
```

3. Specify the routes from an OSPF area as a match condition.

```
[edit policy-options policy-statement injectpolicy1 term injectterm1]
user@host# set from area 0.0.0.1
```

4. Specify that the route is to be accepted if the previous conditions are matched.

```
[edit policy-options policy-statement injectpolicy1 term injectterm1]
user@host# set then accept
```

5. Apply the routing policy to BGP.

```
[edit]
user@host# set protocols bgp export injectpolicy1
```

**Results** Confirm your configuration by entering the **show policy-options** and **show protocols bgp** commands from configuration mode. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show policy-options
policy-statement injectpolicy1 {
  term injectterm1 {
    from {
      protocol ospf;
      area 0.0.0.1;
    }
    then accept;
  }
}
```

```
user@host# show protocols bgp
export injectpolicy1;
```

If you are done configuring the device, enter **commit** from configuration mode.

### *Configuring Tracing for the Routing Policy*

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then enter **commit** from configuration mode.

```
set policy-options policy-statement injectpolicy1 term injectterm1 then trace
set routing-options traceoptions file ospf-bgp-policy-log
set routing-options traceoptions file size 5m
set routing-options traceoptions file files 5
set routing-options traceoptions flag policy
```

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

1. Include a trace action in the policy.

```
[edit policy-options policy-statement injectpolicy] term injectterm1]
user@host# then trace
```

2. Configure the tracing file for the output.

```
[edit routing-options traceoptions]
user@host# set file ospf-bgp-policy-log
user@host# set file size 5m
user@host# set file files 5
user@host# set flag policy
```

**Results** Confirm your configuration by entering the **show policy-options** and **show routing-options** commands from configuration mode. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show policy-options
policy-statement injectpolicy1 {
  term injectterm1 {
    then {
      trace;
    }
  }
}

user@host# show routing-options
traceoptions {
  file ospf-bgp-policy-log size 5m files 5;
  flag policy;
}
```

If you are done configuring the device, enter **commit** from configuration mode.

---

### Verification

Confirm that the configuration is working properly.

#### *Verifying That the Expected BGP Routes Are Present*

**Purpose** Verify the effect of the export policy.

**Action** From operational mode, enter the **show route** command.

---

### Troubleshooting

- [Using the show log Command to Examine the Actions of the Routing Policy on page 176](#)

#### *Using the show log Command to Examine the Actions of the Routing Policy*

**Problem** The routing table contains unexpected routes, or routes are missing from the routing table.

**Solution** If you configure policy tracing as shown in this example, you can run the **show log ospf-bgp-policy-log** command to diagnose problems with the routing policy. The **show log ospf-bgp-policy-log** command displays information about the routes that the **injectpolicy1** policy term analyzes and acts upon.

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

## Example: Configuring BGP Route Advertisement

- [Configuring Routing Policies to Control BGP Route Advertisements on page 177](#)
- [Example: Configuring BGP Prefix-Based Outbound Route Filtering on page 181](#)

## Configuring Routing Policies to Control BGP Route Advertisements

All routing protocols use the Junos OS routing table to store the routes that they learn and to determine which routes they should advertise in their protocol packets. Routing policy allows you to control which routes the routing protocols store in and retrieve from the routing table. For information about routing policy, see the *Routing Policies, Firewall Filters, and Traffic Policers Feature Guide*.

When configuring BGP routing policy, you can perform the following tasks:

- [Applying Routing Policy on page 177](#)
- [Setting BGP to Advertise Inactive Routes on page 178](#)
- [Configuring BGP to Advertise the Best External Route to Internal Peers on page 178](#)
- [Configuring How Often BGP Exchanges Routes with the Routing Table on page 180](#)
- [Disabling Suppression of Route Advertisements on page 181](#)

### Applying Routing Policy

You define routing policy at the **[edit policy-options]** hierarchy level. To apply policies you have defined for BGP, include the **import** and **export** statements within the BGP configuration.

You can apply policies as follows:

- BGP global **import** and **export** statements—Include these statements at the **[edit protocols bgp]** hierarchy level (for routing instances, include these statements at the **[edit routing-instances routing-instance-name protocols bgp]** hierarchy level).
- Group **import** and **export** statements—Include these statements at the **[edit protocols bgp group group-name]** hierarchy level (for routing instances, include these statements at the **[edit routing-instances routing-instance-name protocols bgp group group-name]** hierarchy level).
- Peer **import** and **export** statements—Include these statements at the **[edit protocols bgp group group-name neighbor address]** hierarchy level (for routing instances, include

these statements at the `[edit routing-instances routing-instance-name protocols bgp group group-name neighbor address]` hierarchy level).

A peer-level **import** or **export** statement overrides a group **import** or **export** statement. A group-level **import** or **export** statement overrides a global BGP **import** or **export** statement.

To apply policies, see the following sections:

- [Applying Policies to Routes Being Imported into the Routing Table from BGP on page 178](#)
- [Applying Policies to Routes Being Exported from the Routing Table into BGP on page 178](#)

#### ***Applying Policies to Routes Being Imported into the Routing Table from BGP***

To apply policy to routes being imported into the routing table from BGP, include the **import** statement, listing the names of one or more policies to be evaluated:

```
import [ policy-names ];
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

If you specify more than one policy, they are evaluated in the order specified, from first to last, and the first matching filter is applied to the route. If no match is found, BGP places into the routing table only those routes that were learned from BGP routing devices.

#### ***Applying Policies to Routes Being Exported from the Routing Table into BGP***

To apply policy to routes being exported from the routing table into BGP, include the **export** statement, listing the names of one or more policies to be evaluated:

```
export [ policy-names ];
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

If you specify more than one policy, they are evaluated in the order specified, from first to last, and the first matching filter is applied to the route. If no routes match the filters, the routing table exports into BGP only the routes that it learned from BGP.

---

#### ***Setting BGP to Advertise Inactive Routes***

By default, BGP stores the route information it receives from update messages in the Junos OS routing table, and the routing table exports only active routes into BGP, which BGP then advertises to its peers. To have the routing table export to BGP the best route learned by BGP even if Junos OS did not select it to be an active route, include the **advertise-inactive** statement:

```
advertise-inactive;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

---

#### ***Configuring BGP to Advertise the Best External Route to Internal Peers***

In general, deployed BGP implementations do not advertise the external route with the highest local preference value to internal peers unless it is the best route. Although this

behavior was required by an earlier version of the BGP version 4 specification, RFC 1771, it was typically not followed in order to minimize the amount of advertised information and to prevent routing loops. However, there are scenarios in which advertising the best external route is beneficial, in particular, situations that can result in IBGP route oscillation.

In Junos OS Release 9.3 and later, you can configure BGP to advertise the best external route into an internal BGP (IBGP) mesh group, a route reflector cluster, or an autonomous system (AS) confederation, even when the best route is an internal route.



**NOTE:** In order to configure the `advertise-external` statement on a route reflector, you must disable intracluster reflection with the `no-client-reflect` statement.

When a routing device is configured as a route reflector for a cluster, a route advertised by the route reflector is considered internal if it is received from an internal peer with the same cluster identifier or if both peers have no cluster identifier configured. A route received from an internal peer that belongs to another cluster, that is, with a different cluster identifier, is considered external.

In a confederation, when advertising a route to a confederation border router, any route from a different confederation sub-AS is considered external.

You can also configure BGP to advertise the external route only if the route selection process reaches the point where the multiple exit discriminator (MED) metric is evaluated. As a result, an external route with an AS path worse (that is, longer) than that of the active path is not advertised.

Junos OS also provides support for configuring a BGP export policy that matches on the state of an advertised route. You can match on either active or inactive routes. For more information, see the *Routing Policies, Firewall Filters, and Traffic Policers Feature Guide*.

To configure BGP to advertise the best external path to internal peers, include the `advertise-external` statement:

```
advertise-external;
```



**NOTE:** The `advertise-external` statement is supported at both the group and neighbor level. If you configure the statement at the neighbor level, you must configure it for all neighbors in a group. Otherwise, the group is automatically split into different groups.

For a complete list of hierarchy levels at which you can configure this statement, see the statement summary section for this statement.

To configure BGP to advertise the best external path only if the route selection process reaches the point where the MED value is evaluated, include the `conditional` statement:

```
advertise-external {
  conditional;
```

```
}
```

### Configuring How Often BGP Exchanges Routes with the Routing Table

---

BGP stores the route information it receives from update messages in the routing table, and the routing table exports active routes from the routing table into BGP. BGP then advertises the exported routes to its peers. By default, the exchange of route information between BGP and the routing table occurs immediately after the routes are received. This immediate exchange of route information might cause instabilities in the network reachability information. To guard against this, you can delay the time between when BGP and the routing table exchange route information.

To configure how often BGP and the routing table exchange route information, include the **out-delay** statement:

```
out-delay seconds;
```

By default, the routing table retains some of the route information learned from BGP. To have the routing table retain all or none of this information, include the **keep** statement:

```
keep (all | none);
```

For a list of hierarchy levels at which you can include these statements, see the statement summary sections for these statements.

The routing table can retain the route information learned from BGP in one of the following ways:

- Default (omit the **keep** statement)—Keep all route information that was learned from BGP, except for routes whose AS path is looped and whose loop includes the local AS.
- **keep all**—Keep all route information that was learned from BGP.
- **keep none**—Discard routes that were received from a peer and that were rejected by import policy or other sanity checking, such as AS path or next hop. When you configure **keep none** for the BGP session and the inbound policy changes, Junos OS forces readvertisement of the full set of routes advertised by the peer.

In an AS path healing situation, routes with looped paths theoretically could become usable during a soft reconfiguration when the AS path loop limit is changed. However, there is a significant memory usage difference between the default and **keep all**.

Consider the following scenarios:

- A peer readvertises routes back to the peer from which it learned them.

This can happen in the following cases:

- Another vendor's routing device advertises the routes back to the sending peer.
- The Junos OS peer's default behavior of not readvertising routes back to the sending peer is overridden by configuring **advertise-peer-as**.
- A provider edge (PE) routing device discards any VPN route that does not have any of the expected route targets.

When **keep all** is configured, the behavior of discarding routes received in the above scenarios is overridden.

### Disabling Suppression of Route Advertisements

Junos OS does not advertise the routes learned from one EBGP peer back to the same external BGP (EBGP) peer. In addition, the software does not advertise those routes back to any EBGP peers that are in the same AS as the originating peer, regardless of the routing instance. You can modify this behavior by including the **advertise-peer-as** statement in the configuration. To disable the default advertisement suppression, include the **advertise-peer-as** statement:

```
advertise-peer-as;
```



**NOTE:** The route suppression default behavior is disabled if the **as-override** statement is included in the configuration.

If you include the **advertise-peer-as** statement in the configuration, BGP advertises the route regardless of this check.

To restore the default behavior, include the **no-advertise-peer-as** statement in the configuration:

```
no-advertise-peer-as;
```

If you include both the **as-override** and **no-advertise-peer-as** statements in the configuration, the **no-advertise-peer-as** statement is ignored. You can include these statements at multiple hierarchy levels.

For a list of hierarchy levels at which you can include these statements, see the statement summary section for these statements.

### Example: Configuring BGP Prefix-Based Outbound Route Filtering

This example shows how to configure a Juniper Networks router to accept route filters from remote peers and perform outbound route filtering using the received filters.

- [Requirements on page 181](#)
- [Overview on page 182](#)
- [Configuration on page 182](#)
- [Verification on page 184](#)

#### Requirements

Before you begin:

- Configure the router interfaces.
- Configure an interior gateway protocol (IGP).

## Overview

You can configure a BGP peer to accept route filters from remote peers and perform outbound route filtering using the received filters. By filtering out unwanted updates, the sending peer saves resources needed to generate and transmit updates, and the receiving peer saves resources needed to process updates. This feature can be useful, for example, in a virtual private network (VPN) in which subsets of customer edge (CE) devices are not capable of processing all the routes in the VPN. The CE devices can use prefix-based outbound route filtering to communicate to the provider edge (PE) routing device to transmit only a subset of routes, such as routes to the main data centers only.

The maximum number of prefix-based outbound route filters that a BGP peer can accept is 5000. If a remote peer sends more than 5000 outbound route filters to a peer address, the additional filters are discarded, and a system log message is generated.


You can configure interoperability for the routing device as a whole or for specific BGP groups or peers only.

## Topology

In the sample network, Device CE1 is a router from another vendor. The configuration shown in this example is on Juniper Networks Router PE1.

Figure 17 on page 182 shows the sample network.

Figure 17: BGP Prefix-Based Outbound Route Filtering



## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```

PE1 set protocols bgp group cisco-peers type external
    set protocols bgp group cisco-peers description "to CE1"
    set protocols bgp group cisco-peers local-address 192.168.165.58
    set protocols bgp group cisco-peers peer-as 35
    set protocols bgp group cisco-peers outbound-route-filter bgp-orf-cisco-mode
    set protocols bgp group cisco-peers outbound-route-filter prefix-based accept inet
    set protocols bgp group cisco-peers neighbor 192.168.165.56
    set routing-options autonomous-system 65500
  
```



**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Router PE1 to accept route filters from Device CE1 and perform outbound route filtering using the received filters:

1. Configure the local autonomous system.

```
[edit routing-options]
user@PE1# set autonomous-system 65500
```

2. Configure external peering with Device CE1.

```
[edit protocols bgp group cisco-peers]
user@PE1# set type external
user@PE1# set description "to CE1"
user@PE1# set local-address 192.168.165.58
user@PE1# set peer-as 35
user@PE1# set neighbor 192.168.165.56
```

3. Configure Router PE1 to accept IPv4 route filters from Device CE1 and perform outbound route filtering using the received filters.

```
[edit protocols bgp group cisco-peers]
user@PE1# set outbound-route-filter prefix-based accept inet
```

4. (Optional) Enable interoperability with routing devices that use the vendor-specific compatibility code of 130 for outbound route filters and the code type of 128.

The IANA standard code is 3, and the standard code type is 64.

```
[edit protocols bgp group cisco-peers]
user@PE1# set outbound-route-filter bgp-orf-cisco-mode
```

**Results** From configuration mode, confirm your configuration by entering the **show protocols** and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show protocols
group cisco-peers {
  type external;
  description "to CE1";
  local-address 192.168.165.58;
  peer-as 35;
  outbound-route-filter {
    bgp-orf-cisco-mode;
    prefix-based {
      accept {
        inet;
      }
    }
  }
  neighbor 192.168.165.56;
}

user@PE1# show routing-options
autonomous-system 65500;
```

If you are done configuring the device, enter **commit** from configuration mode.

### Verification

Confirm that the configuration is working properly.

- [Verifying the Outbound Route Filter on page 184](#)
- [Verifying the BGP Neighbor Mode on page 184](#)

#### *Verifying the Outbound Route Filter*

**Purpose** Display information about the prefix-based outbound route filter received from Device CE1.

**Action** From operational mode, enter the **show bgp neighbor orf detail** command.

```
user@PE1> show bgp neighbor orf 192.168.165.56 detail
Peer: 192.168.165.56 Type: External
Group: cisco-peers

inet-unicast
Filter updates rcv:          4 Immediate:          0
Filter: prefix-based         receive
Updates rcv:                4
Received filter entries:
seq 10 2.2.0.0/16 deny minlen 0 maxlen 0
seq 20 3.3.0.0/16 deny minlen 24 maxlen 0
seq 30 4.4.0.0/16 deny minlen 0 maxlen 28
seq 40 5.5.0.0/16 deny minlen 24 maxlen 28
```

#### *Verifying the BGP Neighbor Mode*

**Purpose** Verify that the **bgp-orf-cisco-mode** setting is enabled for the peer by making sure that the **ORFCiscoMode** option is displayed in the **show bgp neighbor** command output.

**Action** From operational mode, enter the **show bgp neighbor** command.

```
user@PE1> show bgp neighbor
Peer: 192.168.165.56 AS 35 Local: 192.168.165.58 AS 65500
Type: External State: Active Flags: <>
Last State: Idle Last Event: Start
Last Error: None
Export: [ adv_stat ]
Options: <Preference LocalAddress AddressFamily PeerAS Refresh>
Options: <ORF ORFCiscoMode>
Address families configured: inet-unicast
Local Address: 192.168.165.58 Holdtime: 90 Preference: 170
Number of flaps: 0
Trace options: detail open detail refresh
Trace file: /var/log/orf size 5242880 files 20
```

- Related Documentation**
- [Understanding External BGP Peering Sessions on page 13](#)
  - [BGP Configuration Overview](#)
  - [Example: Configuring a Routing Policy to Advertise the Best External Route to Internal Peers](#)

- *Example: Configuring BGP to Advertise Inactive Routes*

## Example: Configuring EBGP Multihop

- [Understanding EBGP Multihop on page 185](#)
- [Example: Configuring EBGP Multihop Sessions on page 186](#)

### Understanding EBGP Multihop

BGP is an exterior gateway protocol (EGP) that is used to exchange routing information among routers in different autonomous systems (ASs). The following are two ways of establishing EBGP multihop between routers:

1. When external BGP (EBGP) peers are not directly connected to each other, they must cross one or more non-BGP routers to reach each other.

Configuring multihop EBGP enables the peers to pass through the other routers to form peer relationships and exchange update messages. This type of configuration is typically used when a Juniper Networks routing device needs to run EBGP with a third-party router that does not allow direct connection of the two EBGP peers. EBGP multihop enables a neighbor connection between two EBGP peers that do not have a direct connection.

2. The default behavior for an EBGP connection is to peer over a single physical hop using the physical interface address of the peer. In some cases, it is advantageous to alter this default, one-hop, physical peering EBGP behavior. One such case is when multiple physical links connect two routers that are to be EBGP peers. In this case, if one of the point-to-point links fails, reachability on the alternate link still exists.

Figure 18: EBGP Multihop Peering



In figure 1, router R1 belongs to AS 1 and router R2 belongs to AS 2. The two physical links between the routers is used for load balancing. The EBGP multihop peering works with one physical link as well.

The following configuration example helps to establish a single BGP peering session across these multiple physical links:

1. Each router must establish the peering session with the loopback address of the remote router. You can configure this session using the **local-address** statement, which alters the peer address header information in the BGP packets.
2. Use the **multihop** statement to alter the default use of the neighbor's physical address. In addition, you can also specify a time-to-live (TTL) value in the BGP packets to control how far they propagate. We use a TTL value of 1 to ensure that the session cannot be established across any other backdoor links in the network.



**NOTE:** When multihop is configured, the Junos OS sets the TTL value of 64, by default.

A TTL value of 1 is sufficient to enable an EBGP session to the loopback address of a directly connected neighbor.

3. Each router must have IP routing capability to the remote router's loopback address. This capability is often accomplished by using a static route to map the loopback address to the interface physical addresses.

```
[edit protocols bgp group ext-peers]
type external;
local-address 192.168.3.4;
neighbor 172.16.128.1 {
    multihop ttl 1;
}

[edit routing-options]
static {
    route 172.16.128.1 next-hop (10.10.1.1 | 10.10.2.1);
}
```

## Example: Configuring EBGP Multihop Sessions

This example shows how to configure an external BGP (EBGP) peer that is more than one hop away from the local router. This type of session is called a *multihop* BGP session.

- [Requirements on page 186](#)
- [Overview on page 186](#)
- [Configuration on page 187](#)
- [Verification on page 193](#)

### Requirements

No special configuration beyond device initialization is required before you configure this example.

### Overview

The configuration to enable multihop EBGP sessions requires connectivity between the two EBGP peers. This example uses static routes to provide connectivity between the devices.

Unlike directly connected EBGP sessions in which physical address are typically used in the **neighbor** statements, you must use loopback interface addresses for multihop EBGP by specifying the loopback interface address of the indirectly connected peer. In this way, EBGP multihop is similar to internal BGP (IBGP).


Finally, you must add the **multihop** statement. Optionally, you can set a maximum time-to-live (TTL) value with the **ttl** statement. The TTL is carried in the IP header of BGP packets. If you do not specify a TTL value, the system's default maximum TTL value

is used. The default TTL value is 64 for multihop EBGP sessions. Another option is to retain the BGP next-hop value for route advertisements by including the **no-nexthop-change** statement.

Figure 19 on page 187 shows a typical EBGP multihop network.

Device C and Device E have an established EBGP session. Device D is not a BGP-enabled device. All of the devices have connectivity via static routes.

Figure 19: Typical Network with EBGP Multihop Sessions



### Configuration

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

#### Device C

```
set interfaces fe-1/2/0 unit 9 description to-D
set interfaces fe-1/2/0 unit 9 family inet address 10.10.10.9/30
set interfaces lo0 unit 3 family inet address 192.168.40.4/32
set protocols bgp group external-peers type external
set protocols bgp group external-peers multihop ttl 2
set protocols bgp group external-peers local-address 192.168.40.4
set protocols bgp group external-peers export send-static
set protocols bgp group external-peers peer-as 18
set protocols bgp group external-peers neighbor 192.168.6.7
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 10.10.10.14/32 next-hop 10.10.10.10
set routing-options static route 192.168.6.7/32 next-hop 10.10.10.10
set routing-options router-id 192.168.40.4
set routing-options autonomous-system 17
```

#### Device D

```
set interfaces fe-1/2/0 unit 10 description to-C
set interfaces fe-1/2/0 unit 10 family inet address 10.10.10.10/30
set interfaces fe-1/2/1 unit 13 description to-E
set interfaces fe-1/2/1 unit 13 family inet address 10.10.10.13/30
set interfaces lo0 unit 4 family inet address 192.168.6.6/32
set routing-options static route 192.168.40.4/32 next-hop 10.10.10.9
set routing-options static route 192.168.6.7/32 next-hop 10.10.10.14
set routing-options router-id 192.168.6.6
```

**Device E**

```
set interfaces fe-1/2/0 unit 14 description to-D
set interfaces fe-1/2/0 unit 14 family inet address 10.10.10.14/30
set interfaces lo0 unit 5 family inet address 192.168.6.7/32
set protocols bgp group external-peers multihop ttl 2
set protocols bgp group external-peers local-address 192.168.6.7
set protocols bgp group external-peers export send-static
set protocols bgp group external-peers peer-as 17
set protocols bgp group external-peers neighbor 192.168.40.4
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 10.10.10.8/30 next-hop 10.10.10.13
set routing-options static route 192.168.40.4/32 next-hop 10.10.10.13
set routing-options router-id 192.168.6.7
set routing-options autonomous-system 18
```

### *Device C*

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device C:

1. Configure the interface to the directly connected device (to-D), and configure the loopback interface.

```
[edit interfaces fe-1/2/0 unit 9]
user@C# set description to-D
user@C# set family inet address 10.10.10.9/30
```

```
[edit interfaces lo0 unit 3]
user@C# set family inet address 192.168.40.4/32
```

2. Configure an EBGP session with Device E.

The **neighbor** statement points to the loopback interface on Device E.

```
[edit protocols bgp group external-peers]
user@C# set type external
user@C# set local-address 192.168.40.4
user@C# set export send-static
user@C# set peer-as 18
user@C# set neighbor 192.168.6.7
```

3. Configure the multihop statement to enable Device C and Device E to become EBGP peers.

Because the peers are two hops away from each other, the example uses the **ttl 2** statement.

```
[edit protocols bgp group external-peers]
user@C# set multihop ttl 2
```

4. Configure connectivity to Device E, using static routes.

You must configure a route to both the loopback interface address and to the address on the physical interface.

```
[edit routing-options]
user@C# set static route 10.10.10.14/32 next-hop 10.10.10.10
user@C# set static route 192.168.6.7/32 next-hop 10.10.10.10
```

5. Configure the local router ID and the autonomous system (AS) number.

```
[edit routing-options]
user@C# set router-id 192.168.40.4
user@C# set autonomous-system 17
```

6. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-static term 1]
user@C# set from protocol static
user@C# set then accept
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@C# show interfaces
fe-1/2/0 {
  unit 9 {
    description to-D;
    family inet {
      address 10.10.10.9/30;
    }
  }
}
lo0 {
  unit 3 {
    family inet {
      address 192.168.40.4/32;
    }
  }
}

user@C# show protocols
bgp {
  group external-peers {
    type external;
    multihop {
      ttl 2;
    }
    local-address 192.168.40.4;
    export send-static;
    peer-as 18;
    neighbor 192.168.6.7;
  }
}

user@C# show policy-options
policy-statement send-static {
```

```
term 1 {  
    from protocol static;  
    then accept;  
}  
}  
  
user@C# show routing-options  
static {  
    route 10.10.10.14/32 next-hop 10.10.10.10;  
    route 192.168.6.7/32 next-hop 10.10.10.10;  
}  
router-id 192.168.40.4;  
autonomous-system 17;
```

If you are done configuring the device, enter **commit** from configuration mode.  
Repeat these steps for all BFD sessions in the topology.

### **Configuring Device D**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device D:

1. Set the CLI to Device D.  
  
user@host> **set cli logical-system D**
2. Configure the interfaces to the directly connected devices, and configure a loopback interface.

```
[edit interfaces fe-1/2/0 unit 10]  
user@D# set description to-C  
user@D# set family inet address 10.10.10.10/30
```

```
[edit interfaces fe-1/2/1 unit 13]  
user@D# set description to-E  
user@D# set family inet address 10.10.10.13/30
```

```
[edit interfaces lo0 unit 4]  
user@D# set family inet address 192.168.6.6/32
```

3. Configure connectivity to the other devices using static routes to the loopback interface addresses.

On Device D, you do not need static routes to the physical addresses because Device D is directly connected to Device C and Device E.

```
[edit routing-options]  
user@D# set static route 192.168.40.4/32 next-hop 10.10.10.9  
user@D# set static route 192.168.6.7/32 next-hop 10.10.10.14
```

4. Configure the local router ID.  
  
[edit routing-options]  
user@D# set router-id 192.168.6.6



**Results** From configuration mode, confirm your configuration by entering the **show interfaces** and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@D# show interfaces
fe-1/2/0 {
  unit 10 {
    description to-C;
    family inet {
      address 10.10.10.10/30;
    }
  }
}
fe-1/2/1 {
  unit 13 {
    description to-E;
    family inet {
      address 10.10.10.13/30;
    }
  }
}
lo0 {
  unit 4 {
    family inet {
      address 192.168.6.6/32;
    }
  }
}

user@D# show protocols

user@D# show routing-options
static {
  route 192.168.40.4/32 next-hop 10.10.10.9;
  route 192.168.6.7/32 next-hop 10.10.10.14;
}
router-id 192.168.6.6;

```

If you are done configuring the device, enter **commit** from configuration mode. Repeat these steps for all BFD sessions in the topology.

### **Configuring Device E**

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device E:

1. Set the CLI to Device E.  

```
user@host> set cli logical-system E
```
2. Configure the interface to the directly connected device (to-D), and configure the loopback interface.  

```
[edit interfaces fe-1/2/0 unit 14]
```

```
user@E# set description to-D
user@E# set family inet address 10.10.10.14/30
```

```
[edit interfaces lo0 unit 5]
user@E# set family inet address 192.168.6.7/32
```

3. Configure an EBGP session with Device E.

The **neighbor** statement points to the loopback interface on Device C.

```
[edit protocols bgp group external-peers]
user@E# set local-address 192.168.6.7
user@E# set export send-static
user@E# set peer-as 17
user@E# set neighbor 192.168.40.4
```

4. Configure the **multihop** statement to enable Device C and Device E to become EBGP peers.

Because the peers are two hops away from each other, the example uses the **ttl 2** statement.

```
[edit protocols bgp group external-peers]
user@E# set multihop ttl 2
```

5. Configure connectivity to Device E, using static routes.

You must configure a route to both the loopback interface address and to the address on the physical interface.

```
[edit routing-options]
user@E# set static route 10.10.10.8/30 next-hop 10.10.10.13
user@E# set static route 192.168.40.4/32 next-hop 10.10.10.13
```

6. Configure the local router ID and the autonomous system (AS) number.

```
[edit routing-options]
user@E# set router-id 192.168.6.7
user@E# set autonomous-system 18
```

7. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-static term 1]
user@E# set from protocol static
user@E# set then accept
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@E# show interfaces
fe-1/2/0 {
  unit 14 {
    description to-D;
    family inet {
```

```

        address 10.10.10.14/30;
    }
}
lo0 {
    unit 5 {
        family inet {
            address 192.168.6.7/32;
        }
    }
}

user@E# show protocols
bgp {
    group external-peers {
        multihop {
            ttl 2;
        }
        local-address 192.168.6.7;
        export send-static;
        peer-as 17;
        neighbor 192.168.40.4;
    }
}

user@E# show policy-options
policy-statement send-static {
    term 1 {
        from protocol static;
        then accept;
    }
}

user@E# show routing-options
static {
    route 10.10.10.8/30 next-hop 10.10.10.13;
    route 192.168.40.4/32 next-hop 10.10.10.13;
}
router-id 192.168.6.7;
autonomous-system 18;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Verification

Confirm that the configuration is working properly.

- [Verifying Connectivity on page 193](#)
- [Verifying That BGP Sessions Are Established on page 194](#)
- [Viewing Advertised Routes on page 195](#)

#### Verifying Connectivity

**Purpose** Make sure that Device C can ping Device E, specifying the loopback interface address as the source of the ping request.

The loopback interface address is the source address that BGP will use.

**Action** From operational mode, enter the **ping 10.10.10.14 source 192.168.40.4** command from Device C, and enter the **ping 10.10.10.9 source 192.168.6.7** command from Device E.

```
user@C> ping 10.10.10.14 source 192.168.40.4
```

```
PING 10.10.10.14 (10.10.10.14): 56 data bytes
64 bytes from 10.10.10.14: icmp_seq=0 ttl=63 time=1.262 ms
64 bytes from 10.10.10.14: icmp_seq=1 ttl=63 time=1.202 ms
^C
--- 10.10.10.14 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.202/1.232/1.262/0.030 ms
```

```
user@E> ping 10.10.10.9 source 192.168.6.7
```

```
PING 10.10.10.9 (10.10.10.9): 56 data bytes
64 bytes from 10.10.10.9: icmp_seq=0 ttl=63 time=1.255 ms
64 bytes from 10.10.10.9: icmp_seq=1 ttl=63 time=1.158 ms
^C
--- 10.10.10.9 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.158/1.206/1.255/0.049 ms
```

**Meaning** The static routes are working if the pings work.

### *Verifying That BGP Sessions Are Established*

**Purpose** Verify that the BGP sessions are up.

**Action** From operational mode, enter the **show bgp summary** command.

```
user@C> show bgp summary
```

```
Groups: 1 Peers: 1 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History  Damp State  Pending
inet.0          2         0          0          0          0          0          0
Peer        AS      InPkt    OutPkt    OutQ   Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
192.168.6.7      18      147      147       0        1    1:04:27
0/2/2/0          0/0/0/0
```

```
user@E> show bgp summary
```

```
Groups: 1 Peers: 1 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History  Damp State  Pending
inet.0          2         0          0          0          0          0          0
Peer        AS      InPkt    OutPkt    OutQ   Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
192.168.40.4     17      202      202       0        1    1:02:18
0/2/2/0          0/0/0/0
```

**Meaning** The output shows that both devices have one peer each. No peers are down.

**Viewing Advertised Routes**

**Purpose** Check to make sure that routes are being advertised by BGP.

**Action** From operational mode, enter the `show route advertising-protocol bgp neighbor` command.

```
user@C> show route advertising-protocol bgp 192.168.6.7
```

```
inet.0: 5 destinations, 7 routes (5 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED      Lc1pref  AS path
* 10.10.10.14/32        Self                      I
* 192.168.6.7/32        Self                      I
```

```
user@E> show route advertising-protocol bgp 192.168.40.4
```

```
inet.0: 5 destinations, 7 routes (5 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED      Lc1pref  AS path
* 10.10.10.8/30         Self                      I
* 192.168.40.4/32       Self                      I
```

**Meaning** The `send-static` routing policy is exporting the static routes from the routing table into BGP. BGP is advertising these routes between the peers because the BGP peer session is established.

**Related Documentation**

- [Examples: Configuring External BGP Peering on page 13](#)
- [BGP Configuration Overview](#)

## Example: Configuring BGP Route Preference (Administrative Distance)

- [Understanding Route Preference Values \(Administrative Distance\) on page 195](#)
- [Example: Configuring the Preference Value for BGP Routes on page 197](#)

### Understanding Route Preference Values (Administrative Distance)

The Junos OS routing protocol process assigns a default preference value (also known as an *administrative distance*) to each route that the routing table receives. The default value depends on the source of the route. The preference value is a value from 0 through 4,294,967,295 ( $2^{32} - 1$ ), with a lower value indicating a more preferred route.

[Table 4 on page 195](#) lists the default preference values.

**Table 4: Default Route Preference Values**

| How Route Is Learned       | Default Preference | Statement to Modify Default Preference |
|----------------------------|--------------------|----------------------------------------|
| Directly connected network | 0                  | —                                      |
| System routes              | 4                  | —                                      |
| Static and Static LSPs     | 5                  | <i>static</i>                          |

Table 4: Default Route Preference Values (*continued*)

| How Route Is Learned         | Default Preference | Statement to Modify Default Preference                                             |
|------------------------------|--------------------|------------------------------------------------------------------------------------|
| Static LSPs                  | 6                  | –                                                                                  |
| RSVP-signaled LSPs           | 7                  | RSVP <b>preference</b> as described in the <i>MPLS Applications Feature Guide</i>  |
| LDP-signaled LSPs            | 9                  | LDP <b>preference</b> , as described in the <i>MPLS Applications Feature Guide</i> |
| OSPF internal route          | 10                 | OSPF <i>preference</i>                                                             |
| IS-IS Level 1 internal route | 15                 | IS-IS <i>preference</i>                                                            |
| IS-IS Level 2 internal route | 18                 | IS-IS <i>preference</i>                                                            |
| Redirects                    | 30                 | –                                                                                  |
| Kernel                       | 40                 | –                                                                                  |
| SNMP                         | 50                 | –                                                                                  |
| Router discovery             | 55                 | –                                                                                  |
| RIP                          | 100                | RIP <i>preference</i>                                                              |
| RIPng                        | 100                | RIPng <i>preference</i>                                                            |
| PIM                          | 105                | <i>Multicast Protocols Feature Guide</i>                                           |
| DVMRP                        | 110                | <i>Multicast Protocols Feature Guide</i>                                           |
| Aggregate                    | 130                | <i>aggregate</i>                                                                   |
| OSPF AS external routes      | 150                | OSPF <i>external-preference</i>                                                    |
| IS-IS Level 1 external route | 160                | IS-IS <i>external-preference</i>                                                   |
| IS-IS Level 2 external route | 165                | IS-IS <i>external-preference</i>                                                   |
| BGP                          | 170                | BGP <b>preference</b> , <b>export</b> , <b>import</b>                              |
| MSDP                         | 175                | <i>Multicast Protocols Feature Guide</i>                                           |

In general, the narrower the scope of the statement, the higher precedence its preference value is given, but the smaller the set of routes it affects. To modify the default preference value for routes learned by routing protocols, you generally apply routing policy when

configuring the individual routing protocols. You also can modify some preferences with other configuration statements, which are indicated in the table.

### Example: Configuring the Preference Value for BGP Routes

This example shows how to specify the preference for routes learned from BGP. Routing information can be learned from multiple sources. To break ties among equally specific routes learned from multiple sources, each source has a preference value. Routes that are learned through explicit administrative action, such as static routes, are preferred over routes learned from a routing protocol, such as BGP or OSPF. This concept is called *administrative distance* by some vendors.

- [Requirements on page 197](#)
- [Overview on page 197](#)
- [Configuration on page 199](#)
- [Verification on page 201](#)

#### Requirements

No special configuration beyond device initialization is required before you configure this example.

#### Overview

Routing information can be learned from multiple sources, such as through static configuration, BGP, or an interior gateway protocol (IGP). When Junos OS determines a route's preference to become the active route, it selects the route with the lowest preference as the active route and installs this route into the forwarding table. By default, the routing software assigns a preference of 170 to routes that originated from BGP. Of all the routing protocols, BGP has the highest default preference value, which means that routes learned by BGP are the least likely to become the active route.

Some vendors have a preference (distance) of 20 for external BGP (EBGP) and a distance of 200 for internal BGP (IBGP). Junos OS uses the same value (170) for both EBGP and IBGP. However, this difference between vendors has no operational impact because Junos OS always prefers EBGP routes over IBGP routes.

Another area in which vendors differ is in regard to IGP distance compared to BGP distance. For example, some vendors assign a distance of 110 to OSPF routes. This is higher than the EBGP distance of 20, and results in the selection of an EBGP route over an equivalent OSPF route. In the same scenario, Junos OS chooses the OSPF route, because of the default preference 10 for an internal OSPF route and 150 for an external OSPF route, which are both lower than the 170 preference assigned to all BGP routes.

In a multivendor environment, you might want to change the preference value for BGP routes so that Junos OS chooses an EBGP route instead of an OSPF route. To accomplish this goal, one option is to include the **preference** statement in the EBGP configuration. To modify the default BGP preference value, include the **preference** statement, specifying a value from 0 through 4,294,967,295 ( $2^{32} - 1$ ).



**TIP:** Another way to achieve multivendor compatibility is to include the `advertise-inactive` statement in the EBGP configuration. This causes the routing table to export to BGP the best route learned by BGP even if Junos OS did not select it to be an active route. By default, BGP stores the route information it receives from update messages in the Junos OS routing table, and the routing table exports only active routes into BGP, which BGP then advertises to its peers. The `advertise-inactive` statement causes Junos OS to advertise the best BGP route that is inactive because of IGP preference. When you use the `advertise-inactive` statement, the Junos OS device uses the OSPF route for forwarding, and the other vendor's device uses the EBGP route for forwarding. However, from the perspective of an EBGP peer in a neighboring AS, both vendors' devices appear to behave the same way.

### Topology


In the sample network, Device R1 and Device R2 have EBGP routes to each other and also OSPF routes to each other.

This example shows the routing tables in the following cases:

- Accept the default preference values of 170 for BGP and 10 for OSPF.
- Change the BGP preference to 8.

Figure 20 on page 198 shows the sample network.

**Figure 20: BGP Preference Value Topology**





## Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device R1**

```
set interfaces fe-1/2/0 unit 4 family inet address 1.12.0.1/30
set interfaces lo0 unit 2 family inet address 10.255.71.24/32
set protocols bgp export send-direct
set protocols bgp group ext type external
set protocols bgp group ext preference 8
set protocols bgp group ext peer-as 65000
set protocols bgp group ext neighbor 1.12.0.2
set protocols ospf area 0.0.0.0 interface fe-1/2/0.4
set protocols ospf area 0.0.0.0 interface 10.255.71.24
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 65500
```

**Device R2**

```
set interfaces fe-1/2/0 unit 6 family inet address 1.12.0.2/30
set interfaces lo0 unit 3 family inet address 10.255.14.177/32
set protocols bgp export send-direct
set protocols bgp group ext type external
set protocols bgp group ext peer-as 65500
set protocols bgp group ext neighbor 1.12.0.1
set protocols ospf area 0.0.0.0 interface fe-1/2/0.6
set protocols ospf area 0.0.0.0 interface 10.255.14.177
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set routing-options autonomous-system 65000
```

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.  

```
[edit interfaces]
user@R1# set fe-1/2/0 unit 4 family inet address 1.12.0.1/30
user@R1# set lo0 unit 2 family inet address 10.255.71.24/32
```
2. Configure the local autonomous system.  

```
[edit routing-options]
user@R1# set autonomous-system 65500
```
3. Configure the external peering with Device R2.  

```
[edit protocols bgp]
user@R1# set export send-direct
user@R1# set group ext type external
user@R1# set group ext preference 8
user@R1# set group ext peer-as 65000
```

```
user@R1# set group ext neighbor 1.12.0.2
```

4. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]  
user@R1# set interface fe-1/2/0.4  
user@R1# set interface 10.255.71.24
```

5. Configure the routing policy.

```
[edit policy-options policy-statement send-direct term 1]  
user@R1# set from protocol direct  
user@R1# set then accept
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces  
fe-1/2/0 {  
  unit 4 {  
    family inet {  
      address 1.12.0.1/30;  
    }  
  }  
}  
lo0 {  
  unit 2 {  
    family inet {  
      address 10.255.71.24/32;  
    }  
  }  
}  
  
user@R1# show policy-options  
policy-statement send-direct {  
  term 1 {  
    from protocol direct;  
    then accept;  
  }  
}  
  
user@R1# show protocols  
protocols {  
  bgp {  
    export send-direct;  
    group ext {  
      type external;  
      preference 8;  
      peer-as 65000;  
      neighbor 1.12.0.2;  
    }  
  }  
  ospf {  
    area 0.0.0.0 {  
      interface fe-1/2/0.4;  
    }  
  }  
}
```

```

        interface 10.255.71.24;
    }
}

user@R1# show routing-options
autonomous-system 65500;

```

If you are done configuring the device, enter **commit** from configuration mode.  
Repeat these steps on Device R2.

### Verification

Confirm that the configuration is working properly.

#### Verifying the Preference

**Purpose** Make sure that the routing tables on Device R1 and Device R2 reflect the fact that Device R1 is using the configured EBGp preference of 8, and Device R2 is using the default EBGp preference of 170.

**Action** From operational mode, enter the **show route** command.

```

user@R1> show route
inet.0: 5 destinations, 7 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

```

```

1.12.0.0/30      *[Direct/0] 3d 07:03:01
                  > via fe-1/2/0.4
                  [BGP/8] 01:04:49, localpref 100
                  AS path: 65000 I
                  > to 1.12.0.2 via fe-1/2/0.4
1.12.0.1/32      *[Local/0] 3d 07:03:01
                  Local via fe-1/2/0.4
10.255.14.177/32 *[BGP/8] 01:04:49, localpref 100
                  AS path: 65000 I
                  > to 1.12.0.2 via fe-1/2/0.4
                  [OSPF/10] 3d 07:02:16, metric 1
                  > to 1.12.0.2 via fe-1/2/0.4
10.255.71.24/32  *[Direct/0] 3d 07:03:01
                  > via lo0.2
224.0.0.5/32     *[OSPF/10] 5d 03:42:16, metric 1
                  MultiRecv

```

```

user@R2> show route
inet.0: 5 destinations, 7 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

```

```

1.12.0.0/30      *[Direct/0] 3d 07:03:30
                  > via fe-1/2/0.6
                  [BGP/170] 00:45:36, localpref 100
                  AS path: 65500 I
                  > to 1.12.0.1 via fe-1/2/0.6
1.12.0.2/32      *[Local/0] 3d 07:03:30
                  Local via fe-1/2/0.6
10.255.14.177/32 *[Direct/0] 3d 07:03:30
                  > via lo0.3
10.255.71.24/32  *[OSPF/10] 3d 07:02:45, metric 1
                  > to 1.12.0.1 via fe-1/2/0.6

```

```
224.0.0.5/32      [BGP/170] 00:45:36, localpref 100
                  AS path: 65500 I
                  > to 1.12.0.1 via fe-1/2/0.6
                  *[OSPF/10] 5d 03:42:45, metric 1
                  MultiRecv
```

**Meaning** The output shows that on Device R1, the active path to Device R2's loopback interface (10.255.14.177/32) is a BGP route. The output also shows that on Device R2, the active path to Device R1's loopback interface (10.255.71.24/32) is an OSPF route.

**Related Documentation**

- [Route Preferences Overview](#)
- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

---

## Example: Configuring BGP Path Selection

- [Understanding BGP Path Selection on page 202](#)
- [Example: Ignoring the AS Path Attribute When Selecting the Best Path on page 205](#)

### Understanding BGP Path Selection

For each prefix in the routing table, the routing protocol process selects a single best path. After the best path is selected, the route is installed in the routing table. The best path becomes the active route if the same prefix is not learned by a protocol with a lower (more preferred) global preference value, also known as the administrative distance. The algorithm for determining the active route is as follows:

1. Verify that the next hop can be resolved.
2. Choose the path with the lowest preference value (routing protocol process preference).  
  
Routes that are not eligible to be used for forwarding (for example, because they were rejected by routing policy or because a next hop is inaccessible) have a preference of -1 and are never chosen.
3. Prefer the path with higher local preference.  
  
For non-BGP paths, choose the path with the lowest **preference2** value.
4. If the accumulated interior gateway protocol (AIGP) attribute is enabled, prefer the path with the lower AIGP attribute.
5. Prefer the path with the shortest autonomous system (AS) path value (skipped if the **as-path-ignore** statement is configured).  
  
A confederation segment (sequence or set) has a path length of 0. An AS set has a path length of 1.
6. Prefer the route with the lower origin code.

Routes learned from an IGP have a lower origin code than those learned from an exterior gateway protocol (EGP), and both have lower origin codes than incomplete routes (routes whose origin is unknown).

7. Prefer the path with the lowest multiple exit discriminator (MED) metric.

Depending on whether nondeterministic routing table path selection behavior is configured, there are two possible cases:

- If nondeterministic routing table path selection behavior is not configured (that is, if the **path-selection cisco-nondeterministic** statement is not included in the BGP configuration), for paths with the same neighboring AS numbers at the front of the AS path, prefer the path with the lowest MED metric. To always compare MEDs whether or not the peer ASs of the compared routes are the same, include the **path-selection always-compare-med** statement.
- If nondeterministic routing table path selection behavior is configured (that is, the **path-selection cisco-nondeterministic** statement is included in the BGP configuration), prefer the path with the lowest MED metric.

Confederations are not considered when determining neighboring ASs. A missing MED metric is treated as if a MED were present but zero.



**NOTE:** MED comparison works for single path selection within an AS (when the route does not include an AS path), though this usage is uncommon.

By default, only the MEDs of routes that have the same peer autonomous systems (ASs) are compared. You can configure routing table path selection options to obtain different behaviors.

8. Prefer strictly internal paths, which include IGP routes and locally generated routes (static, direct, local, and so forth).
9. Prefer strictly external BGP (EBGP) paths over external paths learned through internal BGP (IBGP) sessions.
10. Prefer the path whose next hop is resolved through the IGP route with the lowest metric.



**NOTE:** A path is considered a BGP equal-cost path (and will be used for forwarding) if a tie-break is performed after the previous step. All paths with the same neighboring AS, learned by a multipath-enabled BGP neighbor, are considered.

BGP multipath does not apply to paths that share the same MED-plus-IGP cost yet differ in IGP cost. Multipath path selection is based on the IGP cost metric, even if two paths have the same MED-plus-IGP cost.

11. If both paths are external, prefer the currently active path to minimize route-flapping. This rule is not used if any one of the following conditions is true:

- **path-selection external-router-id** is configured.
  - Both peers have the same router ID.
  - Either peer is a confederation peer.
  - Neither path is the current active path.
12. Prefer a primary route over a secondary route. A primary route is one that belongs to the routing table. A secondary route is one that is added to the routing table through an export policy.
  13. Prefer the path from the peer with the lowest router ID. For any path with an originator ID attribute, substitute the originator ID for the router ID during router ID comparison.
  14. Prefer the path with the shortest cluster list length. The length is 0 for no list.
  15. Prefer the path from the peer with the lowest peer IP address.

### Routing Table Path Selection

The shortest AS path step of the algorithm, by default, evaluates the length of the AS path and determines the active path. You can configure an option that enables Junos OS to skip this step of the algorithm by including the **as-path-ignore** option.



**NOTE:** The **as-path-ignore** option is not supported for routing instances.

To configure routing table path selection behavior, include the **path-selection** statement:

```
path-selection {
  (always-compare-med | cisco-non-deterministic | external-router-id);
  as-path-ignore;
  med-plus-igp {
    igp-multiplier number;
    med-multiplier number;
  }
}
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

Routing table path selection can be configured in one of the following ways:

- Emulate the Cisco IOS default behavior (**cisco-non-deterministic**). This mode evaluates routes in the order that they are received and does not group them according to their neighboring AS. With **cisco-non-deterministic** mode, the active path is always first. All inactive, but eligible, paths follow the active path and are maintained in the order in which they were received, with the most recent path first. Ineligible paths remain at the end of the list.

As an example, suppose you have three path advertisements for the 192.168.1.0 /24 route:

- Path 1—learned through EBGp; AS Path of 65010; MED of 200

- Path 2—learned through IBGP; AS Path of 65020; MED of 150; IGP cost of 5
- Path 3—learned through IBGP; AS Path of 65010; MED of 100; IGP cost of 10

These advertisements are received in quick succession, within a second, in the order listed. Path 3 is received most recently, so the routing device compares it against path 2, the next most recent advertisement. The cost to the IBGP peer is better for path 2, so the routing device eliminates path 3 from contention. When comparing paths 1 and 2, the routing device prefers path 1 because it is received from an EBGP peer. This allows the routing device to install path 1 as the active path for the route.



**NOTE:** We do not recommend using this configuration option in your network. It is provided solely for interoperability to allow all routing devices in the network to make consistent route selections.

- Always comparing MEDs whether or not the peer ASs of the compared routes are the same (**always-compare-med**).
- Override the rule that If both paths are external, the currently active path is preferred (**external-router-id**). Continue with the next step (Step 12) in the path-selection process.
- Adding the IGP cost to the next-hop destination to the MED value before comparing MED values for path selection (**med-plus-igp**).

BGP multipath does not apply to paths that share the same MED-plus-IGP cost, yet differ in IGP cost. Multipath path selection is based on the IGP cost metric, even if two paths have the same MED-plus-IGP cost.

### Effects of Advertising Multiple Paths to a Destination

BGP advertises only the active path, unless you configure BGP to advertise multiple paths to a destination.

Suppose a routing device has in its routing table four paths to a destination and is configured to advertise up to three paths (**add-path send path-count 3**). The three paths are chosen based on path selection criteria. That is, the three best paths are chosen in path-selection order. The best path is the active path. This path is removed from consideration and a new best path is chosen. This process is repeated until the specified number of paths is reached.

### Example: Ignoring the AS Path Attribute When Selecting the Best Path

If multiple BGP routes to the same destination exist, BGP selects the best path based on the route attributes of the paths. One of the route attributes that affects the best-path decision is the length of the AS paths of each route. Routes with shorter AS paths are preferred over those with longer AS paths. Although not typically practical, some scenarios might require that the AS path length be ignored in the route selection process. This example shows how to configure a routing device to ignore the AS path attribute.

- [Requirements on page 206](#)
- [Overview on page 206](#)

- [Configuration on page 207](#)
- [Verification on page 212](#)

---

## Requirements

No special configuration beyond device initialization is required before you configure this example.

---

## Overview

On externally connected routing devices, the purpose of skipping the AS path comparison might be to force an external BGP (EBGP) versus internal BGP (IBGP) decision to remove traffic from your network as soon as possible. On internally connected routing devices, you might want your IBGP-only routers to default to the local externally connected gateway. The local IBGP-only (internal) routers skip the AS path comparison and move down the decision tree to use the closest interior gateway protocol (IGP) gateway (lowest IGP metric). Doing this might be an effective way to force these routers to use a LAN connection instead of their WAN connection.



**CAUTION:** When you include the `as-path-ignore` statement on a routing device in your network, you might need to include it on all other BGP-enabled devices in your network to prevent routing loops and convergence issues. This is especially true for IBGP path comparisons.

---

In this example, Device R2 is learning about the loopback interface address on Device R4 (4.4.4.4/32) from Device R1 and Device R3. Device R1 is advertising 4.4.4.4/32 with an AS-path of 1 5 4, and Device R3 is advertising 4.4.4.4/32 with an AS-path of 3 4. Device R2 selects the path for 4.4.4.4/32 from Device R3 as the best path because the AS path is shorter than the AS path from Device R1.


This example modifies the BGP configuration on Device R2 so that the AS-path length is not used in the best-path selection.

Device R1 has a lower router ID (1.1.1.1) than Device R3 (1.1.1.1). If all other path selection criteria are equal (or, as in this case, ignored), the route learned from Device R1 is used. Because the AS-path attribute is being ignored, the best path is toward Device R1 because of its lower router ID value.

[Figure 21 on page 207](#) shows the sample topology.



Figure 21: Topology for Ignoring the AS-Path Length



g041166

### Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device R1**

```

set interfaces fe-1/2/0 unit 1 family inet address 192.168.10.1/24
set interfaces fe-1/2/1 unit 10 family inet address 192.168.50.2/24
set interfaces lo0 unit 1 family inet address 1.1.1.1/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext export send-local
set protocols bgp group ext neighbor 192.168.10.2 peer-as 2
set protocols bgp group ext neighbor 192.168.50.1 peer-as 5
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-local term 1 from protocol local

```

```
set policy-options policy-statement send-local term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.20.0/24 next-hop 192.168.10.2
set routing-options static route 192.168.30.0/24 next-hop 192.168.10.2
set routing-options static route 192.168.40.0/24 next-hop 192.168.50.1
set routing-options router-id 1.1.1.1
set routing-options autonomous-system 1
```

**Device R2**

```
set interfaces fe-1/2/0 unit 2 family inet address 192.168.10.2/24
set interfaces fe-1/2/1 unit 3 family inet address 192.168.20.2/24
set interfaces lo0 unit 2 family inet address 2.2.2.2/32
set protocols bgp path-selection as-path-ignore
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext export send-local
set protocols bgp group ext neighbor 192.168.10.1 peer-as 1
set protocols bgp group ext neighbor 192.168.20.1 peer-as 3
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-local term 1 from protocol local
set policy-options policy-statement send-local term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.50.0/24 next-hop 192.168.10.1
set routing-options static route 192.168.40.0/24 next-hop 192.168.10.1
set routing-options static route 192.168.30.0/24 next-hop 192.168.20.1
set routing-options router-id 2.2.2.2
set routing-options autonomous-system 2
```

**Device R3**

```
set interfaces fe-1/2/0 unit 4 family inet address 192.168.20.1/24
set interfaces fe-1/2/1 unit 5 family inet address 192.168.30.1/24
set interfaces lo0 unit 3 family inet address 1.1.1.1/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext export send-local
set protocols bgp group ext neighbor 192.168.20.2 peer-as 2
set protocols bgp group ext neighbor 192.168.30.2 peer-as 4
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-local term 1 from protocol local
set policy-options policy-statement send-local term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.10.0/24 next-hop 192.168.20.2
set routing-options static route 192.168.50.0/24 next-hop 192.168.20.2
set routing-options static route 192.168.40.0/24 next-hop 192.168.30.2
set routing-options router-id 3.3.3.3
set routing-options autonomous-system 3
```

**Device R4**

```
set interfaces fe-1/2/0 unit 6 family inet address 192.168.30.2/24
set interfaces fe-1/2/1 unit 7 family inet address 192.168.40.1/24
set interfaces lo0 unit 4 family inet address 4.4.4.4/32
```

```

set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext export send-local
set protocols bgp group ext neighbor 192.168.30.1 peer-as 3
set protocols bgp group ext neighbor 192.168.40.2 peer-as 5
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-local term 1 from protocol local
set policy-options policy-statement send-local term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.10.0/24 next-hop 192.168.40.2
set routing-options static route 192.168.50.0/24 next-hop 192.168.40.2
set routing-options static route 192.168.40.0/24 next-hop 192.168.30.1
set routing-options router-id 4.4.4.4
set routing-options autonomous-system 4

```

**Device R5**

```

set interfaces fe-1/2/0 unit 8 family inet address 192.168.40.2/24
set interfaces fe-1/2/1 unit 9 family inet address 192.168.50.1/24
set interfaces lo0 unit 5 family inet address 5.5.5.5/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext export send-local
set protocols bgp group ext neighbor 192.168.40.1 peer-as 4
set protocols bgp group ext neighbor 192.168.50.2 peer-as 1
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-local term 1 from protocol local
set policy-options policy-statement send-local term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.10.0/24 next-hop 192.168.50.2
set routing-options static route 192.168.20.0/24 next-hop 192.168.50.2
set routing-options static route 192.168.30.0/24 next-hop 192.168.40.1
set routing-options router-id 5.5.5.5
set routing-options autonomous-system 5

```

### Configuring Device R2

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R2:

1. Configure the interfaces.  

```

[edit interfaces]
user@R2# set fe-1/2/0 unit 2 family inet address 192.168.10.2/24
user@R2# set fe-1/2/1 unit 3 family inet address 192.168.20.2/24
user@R2# set lo0 unit 2 family inet address 2.2.2.2/32

```
2. Configure EBGp.  

```

[edit protocols bgp group ext]

```

```

user@R2# set type external
user@R2# set export send-direct
user@R2# set export send-static
user@R2# set export send-local
user@R2# set neighbor 192.168.10.1 peer-as 1
user@R2# set neighbor 192.168.20.1 peer-as 3

```

3. Configure the autonomous system (AS) path attribute to be ignored in the Junos OS path selection algorithm.

```

[edit protocols bgp]
user@R2# set path-selection as-path-ignore

```

4. Configure the routing policy.

```

[edit policy-options]
user@R2# set policy-statement send-direct term 1 from protocol direct
user@R2# set policy-statement send-direct term 1 then accept
user@R2# set policy-statement send-local term 1 from protocol local
user@R2# set policy-statement send-local term 1 then accept
user@R2# set policy-statement send-static term 1 from protocol static
user@R2# set policy-statement send-static term 1 then accept

```

5. Configure some static routes.

```

[edit routing-options static]
user@R2# set route 192.168.50.0/24 next-hop 192.168.10.1
user@R2# set route 192.168.40.0/24 next-hop 192.168.10.1
user@R2# set route 192.168.30.0/24 next-hop 192.168.20.1

```

6. Configure the autonomous system (AS) number and the router ID.

```

[edit routing-options]
user@R2# set router-id 2.2.2.2
user@R2# set autonomous-system 2

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R2# show interfaces
fe-1/2/0 {
  unit 2 {
    family inet {
      address 192.168.10.2/24;
    }
  }
}
fe-1/2/1 {
  unit 3 {
    family inet {
      address 192.168.20.2/24;
    }
  }
}
lo0 {
  unit 2 {

```

```

        family inet {
            address 2.2.2.2/32;
        }
    }
}

user@R2# show policy-options
policy-statement send-direct {
    term 1 {
        from protocol direct;
        then accept;
    }
}
policy-statement send-local {
    term 1 {
        from protocol local;
        then accept;
    }
}
policy-statement send-static {
    term 1 {
        from protocol static;
        then accept;
    }
}

user@R2# show protocols
bgp {
    path-selection as-path-ignore;
    group ext {
        type external;
        export [ send-direct send-static send-local ];
        neighbor 192.168.10.1 {
            peer-as 1;
        }
        neighbor 192.168.20.1 {
            peer-as 3;
        }
    }
}

user@R2# show routing-options
static {
    route 192.168.50.0/24 next-hop 192.168.10.1;
    route 192.168.40.0/24 next-hop 192.168.10.1;
    route 192.168.30.0/24 next-hop 192.168.20.1;
}
router-id 2.2.2.2;
autonomous-system 2;

```

If you are done configuring the device, enter **commit** from configuration mode. Repeat the configuration on the other devices in the network, changing the interface names and IP addresses, as needed.

## Verification

Confirm that the configuration is working properly.

- [Checking the Neighbor Status on page 212](#)

### Checking the Neighbor Status

**Purpose** Make sure that from Device R2, the active path to get to AS 4 is through AS 1 and AS 5, not through AS 3.



**NOTE:** To verify the functionality of the `as-path-ignore` statement, you might need to run the `restart routing` command to force reevaluation of the active path. This is because for BGP, if both paths are external, the Junos OS behavior is to prefer the currently active path. This behavior helps to minimize route-flapping. Use caution when restarting the routing protocol process in a production network.

**Action** From operational mode, enter the `restart routing` command.

```
user@R2> restart routing
Routing protocols process started, pid 49396
```

From operational mode, enter the `show route 4.4.4.4 protocol bgp` command.

```
user@R2> show route 4.4.4.4 protocol bgp
inet.0: 12 destinations, 25 routes (12 active, 0 holddown, 4 hidden)
+ = Active Route, - = Last Active, * = Both

4.4.4.4/32          *[BGP/170] 00:00:12, localpref 100
                   AS path: 1 5 4 I
                   > to 192.168.10.1 via fe-1/2/0.2
                   [BGP/170] 00:00:08, localpref 100
                   AS path: 3 4 I
                   > to 192.168.20.1 via fe-1/2/1.3
```

**Meaning** The asterisk (\*) is next to the path learned from R1, meaning that this is the active path. The AS path for the active path is 1 5 4, which is longer than the AS path (3 4) for the nonactive path learned from Router R3.

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

## Example: Removing Private AS Numbers

- [Understanding Private AS Number Removal from AS Paths on page 213](#)
- [Example: Removing Private AS Numbers from AS Paths on page 214](#)

## Understanding Private AS Number Removal from AS Paths

By default, when BGP advertises AS paths to remote systems, it includes all AS numbers, including private AS numbers. You can configure the software so that it removes private AS numbers from AS paths. Doing this is useful when any of the following circumstances are true:

- A remote AS for which you provide connectivity is multihomed, but only to the local AS.
- The remote AS does not have an officially allocated AS number.
- It is not appropriate to make the remote AS a confederation member AS of the local AS.

Most companies acquire their own AS number. Some companies also use private AS numbers to connect to their public AS network. These companies might use a different private AS number for each region in which their company does business. In any implementation, announcing a private AS number to the Internet must be avoided. Service providers can use the **remove-private** statement to prevent advertising private AS numbers to the Internet.

In an enterprise scenario, suppose that you have multiple AS numbers in your company, some of which are private AS numbers, and one with a public AS number. The one with a public AS number has a direct connection to the service provider. In the AS that connects directly to the service provider, you can use the **remove-private** statement to filter out any private AS numbers in the advertisements that are sent to the service provider.



**CAUTION:** Changing configuration statements that affect BGP peers, such as enabling or disabling **remove-private** or renaming a BGP group, resets the BGP sessions. Changes that affect BGP peers should only be made when resetting a BGP session is acceptable.

The AS numbers are stripped from the AS path starting at the left end of the AS path (the end where AS paths have been most recently added). The routing device stops searching for private ASs when it finds the first nonprivate AS or a peer's private AS. If the AS path contains the AS number of the external BGP (EBGP) neighbor, BGP does not remove the private AS number.



**NOTE:** As of Junos OS 10.0R2 and later, if there is a need to send prefixes to an EBGP peer that has an AS number that matches an AS number in the AS path, consider using the **as-override** statement instead of the **remove-private** statement.

The operation takes place after any confederation member ASs have already been removed from the AS path, if applicable.

The software is preconfigured with knowledge of the set of AS numbers that is considered private, a range that is defined in the Internet Assigned Numbers Authority (IANA) assigned numbers document. The set of AS numbers reserved as private are in the range from 64,512 through 65,534, inclusive.

### Example: Removing Private AS Numbers from AS Paths

This example demonstrates the removal of a private AS number from the advertised AS path to avoid announcing the private AS number to the Internet.

- [Requirements on page 214](#)
- [Overview on page 214](#)
- [Configuration on page 215](#)
- [Verification on page 217](#)

#### Requirements


No special configuration beyond device initialization is required before you configure this example.

#### Overview

Service providers and enterprise networks use the **remove-private** statement to prevent advertising private AS numbers to the Internet. The **remove-private** statement works in the outbound direction. You configure the **remove-private** statement on a device that has a public AS number and that is connected to one or more devices that have private AS numbers. Generally, you would not configure this statement on a device that has a private AS number.

Figure 22 on page 214 shows the sample topology.

**Figure 22: Topology for Removing a Private AS from the Advertised AS Path**



In this example, Device R1 is connected to its service provider using private AS number 65530. The example shows the **remove-private** statement configured on Device ISP to prevent Device R1's private AS number from being announced to Device R2. Device R2 sees only the AS number of the service provider.



## Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device R1**

```
set interfaces fe-1/2/0 unit 1 family inet address 192.168.10.1/24
set interfaces lo0 unit 1 family inet address 10.10.10.1/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext peer-as 100
set protocols bgp group ext neighbor 192.168.10.10
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.20.0/24 next-hop 192.168.10.10
set routing-options autonomous-system 65530
```

**Device ISP**

```
set interfaces fe-1/2/0 unit 2 family inet address 192.168.10.10/24
set interfaces fe-1/2/1 unit 3 family inet address 192.168.20.20/24
set interfaces lo0 unit 2 family inet address 10.10.0.1/32
set protocols bgp group ext type external
set protocols bgp group ext neighbor 192.168.10.1 peer-as 65530
set protocols bgp group ext neighbor 192.168.20.1 remove-private
set protocols bgp group ext neighbor 192.168.20.1 peer-as 200
set routing-options autonomous-system 100
```

**Device R2**

```
set interfaces fe-1/2/0 unit 4 family inet address 192.168.20.1/24
set interfaces lo0 unit 3 family inet address 10.10.20.1/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct
set protocols bgp group ext export send-static
set protocols bgp group ext peer-as 100
set protocols bgp group ext neighbor 192.168.20.20
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options policy-statement send-static term 1 from protocol static
set policy-options policy-statement send-static term 1 then accept
set routing-options static route 192.168.10.0/24 next-hop 192.168.20.20
set routing-options autonomous-system 200
```

### Device ISP

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device ISP:

1. Configure the interfaces.

[edit interfaces]

```

user@ISP# set fe-1/2/0 unit 2 family inet address 192.168.10.10/24
user@ISP# set fe-1/2/1 unit 3 family inet address 192.168.20.20/24
user@ISP# set lo0 unit 2 family inet address 10.10.0.1/32

```

2. Configure EBGP.

```

[edit protocols bgp group ext]
user@ISP# set type external
user@ISP# set neighbor 192.168.10.1 peer-as 65530
user@ISP# set neighbor 192.168.20.1 peer-as 200

```

3. For the neighbor in autonomous system (AS) 200 (Device R2), remove private AS numbers from the advertised AS paths.

```

[edit protocols bgp group ext]
user@ISP# set neighbor 192.168.20.1 remove-private

```

4. Configure the AS number.

```

[edit routing-options]
user@ISP# set autonomous-system 100

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@ISP# show interfaces
fe-1/2/0 {
  unit 2 {
    family inet {
      address 192.168.10.10/24;
    }
  }
}
fe-1/2/1 {
  unit 3 {
    family inet {
      address 192.168.20.20/24;
    }
  }
}
lo0 {
  unit 2 {
    family inet {
      address 10.10.0.1/32;
    }
  }
}
}

user@ISP# show protocols
bgp {
  group ext {
    type external;
    neighbor 192.168.10.1 {
      peer-as 65530;
    }
    neighbor 192.168.20.1 {
      remove-private;
    }
  }
}

```

```

        peer-as 200;
    }
}

user@ISP# show routing-options
autonomous-system 100;

```

If you are done configuring the device, enter **commit** from configuration mode. Repeat the configuration on Device R1 and Device R2, changing the interface names and IP address, as needed, and adding the routing policy configuration.

### Verification

Confirm that the configuration is working properly.

- [Checking the Neighbor Status on page 217](#)
- [Checking the Routing Tables on page 218](#)
- [Checking the AS Path When the remove-private Statement Is Deactivated on page 218](#)

#### Checking the Neighbor Status

**Purpose** Make sure that Device ISP has the **remove-private** setting enabled in its neighbor session with Device R2.

**Action** From operational mode, enter the **show bgp neighbor 192.168.20.1** command.

```

user@ISP> show bgp neighbor 192.168.20.1
Peer: 192.168.20.1+179 AS 200 Local: 192.168.20.20+60216 AS 100
  Type: External  State: Established  Flags: <ImportEval Sync>
  Last State: OpenConfirm  Last Event: RecvKeepAlive
  Last Error: None
  Options: <Preference RemovePrivateAS PeerAS Refresh>
  Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 10.10.20.1      Local ID: 10.10.0.1      Active Holdtime: 90
  Keepalive Interval: 30      Peer index: 0
  BFD: disabled, down
  Local Interface: fe-1/2/1.3
  NLRI for restart configured on peer: inet-unicast
  NLRI advertised by peer: inet-unicast
  NLRI for this session: inet-unicast
  Peer supports Refresh capability (2)
  Stale routes from peer are kept for: 300
  Peer does not support Restarter functionality
  NLRI that restart is negotiated for: inet-unicast
  NLRI of received end-of-rib markers: inet-unicast
  NLRI of all end-of-rib markers sent: inet-unicast
  Peer supports 4 byte AS extension (peer-as 200)
  Peer does not support Addpath
  Table inet.0 Bit: 10001
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          1
    Received prefixes:        3
    Accepted prefixes:        2
    Suppressed due to damping: 0
    Advertised prefixes:      1

```

```

Last traffic (seconds): Received 10    Sent 16    Checked 55
Input messages: Total 54    Updates 3    Refreshes 0    Octets 1091
Output messages: Total 54    Updates 1    Refreshes 0    Octets 1118
Output Queue[0]: 0

```

**Meaning** The **RemovePrivateAS** option shows that Device ISP has the expected setting.

### *Checking the Routing Tables*

**Purpose** Make sure that the devices have the expected routes and AS paths.

**Action** From operational mode, enter the **show route protocol bgp** command.

```

user@R1> show route protocol bgp
inet.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.20.1/32      *[BGP/170] 00:28:57, localpref 100
                   AS path: 100 200 I
                   > to 192.168.10.10 via fe-1/2/0.1

user@ISP> show route protocol bgp

inet.0: 7 destinations, 11 routes (7 active, 0 holddown, 2 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.1/32      *[BGP/170] 00:29:40, localpref 100
                   AS path: 65530 I
                   > to 192.168.10.1 via fe-1/2/0.2
10.10.20.1/32      *[BGP/170] 00:29:36, localpref 100
                   AS path: 200 I
                   > to 192.168.20.1 via fe-1/2/1.3
192.168.10.0/24    [BGP/170] 00:29:40, localpref 100
                   AS path: 65530 I
                   > to 192.168.10.1 via fe-1/2/0.2
192.168.20.0/24    [BGP/170] 00:29:36, localpref 100
                   AS path: 200 I
                   > to 192.168.20.1 via fe-1/2/1.3

user@R2> show route protocol bgp
inet.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.1/32      *[BGP/170] 00:29:53, localpref 100
                   AS path: 100 I
                   > to 192.168.20.20 via fe-1/2/0.4

```

**Meaning** Device ISP has the private AS number 65530 in its AS path to Device R1. However, Device ISP does not advertise this private AS number to Device R2. This is shown in the routing table of Device R2. Device R2's path to Device R1 contains only the AS number for Device ISP.

### *Checking the AS Path When the remove-private Statement Is Deactivated*

**Purpose** Verify that without the **remove-private** statement, the private AS number appears in Device R2's routing table.

**Action** From configuration mode on Device ISP, enter the **deactivate remove-private** command and then recheck the routing table on Device R2.

```
[protocols bgp group ext neighbor 192.168.20.1]
user@ISP# deactivate remove-private
user@ISP# commit

user@R2> show route protocol bgp
inet.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.1/32      *[BGP/170] 00:00:54, localpref 100
                  AS path: 100 65530 I
                  > to 192.168.20.20 via fe-1/2/0.4
```

**Meaning** Private AS number 65530 appears in Device R2's AS path to Device R1.

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- *BGP Configuration Overview*



## CHAPTER 5

# BGP BFD Configuration

- [Example: Configuring BFD for BGP on page 221](#)
- [Example: Configuring BFD Authentication for BGP on page 230](#)

### Example: Configuring BFD for BGP

---

- [Understanding BFD for BGP on page 221](#)
- [Example: Configuring BFD on Internal BGP Peer Sessions on page 222](#)

### Understanding BFD for BGP

The Bidirectional Forwarding Detection (BFD) protocol is a simple hello mechanism that detects failures in a network. Hello packets are sent at a specified, regular interval. A neighbor failure is detected when the routing device stops receiving a reply after a specified interval. BFD works with a wide variety of network environments and topologies. The failure detection timers for BFD have shorter time limits than default failure detection mechanisms for BGP, so they provide faster detection.

The BFD failure detection timers are adaptive and can be adjusted to be faster or slower. The lower the BFD failure detection timer value, the faster the failure detection and vice versa. For example, the timers can adapt to a higher value if the adjacency fails (that is, the timer detects failures more slowly). Or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds. A back-off algorithm increases the receive (Rx) interval by two if the local BFD instance is the reason for the session flap. The transmission (Tx) interval is increased by two if the remote BFD instance is the reason for the session flap. You can use the **clear bfd adaptation** command to return BFD interval timers to their configured values. The **clear bfd adaptation** command is hitless, meaning that the command does not affect traffic flow on the routing device.

In Junos OS Release 8.3 and later, BFD is supported on internal BGP (IBGP) and multihop external BGP (EBGP) sessions as well as on single-hop EBGP sessions. In Junos OS Release 9.1 through Junos OS Release 11.1, BFD supports IPv6 interfaces in static routes only. In Junos OS Release 11.2 and later, BFD supports IPv6 interfaces with BGP.

## Example: Configuring BFD on Internal BGP Peer Sessions

This example shows how to configure internal BGP (IBGP) peer sessions with the Bidirectional Forwarding Detection (BFD) protocol to detect failures in a network.

- [Requirements on page 222](#)
- [Overview on page 222](#)
- [Configuration on page 223](#)
- [Verification on page 227](#)

---

### Requirements

No special configuration beyond device initialization is required before you configure this example.

---

### Overview

The minimum configuration to enable BFD on IBGP sessions is to include the **bfd-liveness-detection minimum-interval** statement in the BGP configuration of all neighbors participating in the BFD session. The **minimum-interval** statement specifies the minimum transmit and receive intervals for failure detection. Specifically, this value represents the minimum interval after which the local routing device transmits hello packets as well as the minimum interval that the routing device expects to receive a reply from a neighbor with which it has established a BFD session. You can configure a value from 1 through 255,000 milliseconds.

Optionally, you can specify the minimum transmit and receive intervals separately using the **transmit-interval minimum-interval** and **minimum-receive-interval** statements. For information about these and other optional BFD configuration statements, see [bfd-liveness-detection](#).





**NOTE:** BFD is an intensive protocol that consumes system resources. Specifying a minimum interval for BFD less than 100 ms for Routing Engine-based sessions and less than 10 ms for distributed BFD sessions can cause undesired BFD flapping.


Depending on your network environment, these additional recommendations might apply:

- For large-scale network deployments with a large number of BFD sessions, specify a minimum interval of 300 ms for Routing Engine-based sessions and 100 ms for distributed BFD sessions.
- For very large-scale network deployments with a large number of BFD sessions, contact Juniper Networks customer support for more information.
- For BFD sessions to remain up during a Routing Engine switchover event when nonstop active routing (NSR) is configured, specify a minimum interval of 2500 ms for Routing Engine-based sessions. For distributed BFD sessions with NSR configured, the minimum interval recommendations are unchanged and depend only on your network deployment.

BFD is supported on the default routing instance (the main router), routing instances, and logical systems. This example shows BFD on logical systems.

Figure 23 on page 223 shows a typical network with internal peer sessions.

**Figure 23: Typical Network with IBGP Sessions**



### Configuration

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device A**    **set logical-systems A interfaces lt-1/2/0 unit 1 description to-B**  
**set logical-systems A interfaces lt-1/2/0 unit 1 encapsulation ethernet**  
**set logical-systems A interfaces lt-1/2/0 unit 1 peer-unit 2**

```
set logical-systems A interfaces lt-1/2/0 unit 1 family inet address 10.10.10.1/30
set logical-systems A interfaces lo0 unit 1 family inet address 192.168.6.5/32
set logical-systems A protocols bgp group internal-peers type internal
set logical-systems A protocols bgp group internal-peers traceoptions file bgp-bfd
set logical-systems A protocols bgp group internal-peers traceoptions flag bfd detail
set logical-systems A protocols bgp group internal-peers local-address 192.168.6.5
set logical-systems A protocols bgp group internal-peers export send-direct
set logical-systems A protocols bgp group internal-peers bfd-liveness-detection
    minimum-interval 1000
set logical-systems A protocols bgp group internal-peers neighbor 192.163.6.4
set logical-systems A protocols bgp group internal-peers neighbor 192.168.40.4
set logical-systems A protocols ospf area 0.0.0.0 interface lo0.1 passive
set logical-systems A protocols ospf area 0.0.0.0 interface lt-1/2/0.1
set logical-systems A policy-options policy-statement send-direct term 2 from protocol
    direct
set logical-systems A policy-options policy-statement send-direct term 2 then accept
set logical-systems A routing-options router-id 192.168.6.5
set logical-systems A routing-options autonomous-system 17
```

Device B

```
set logical-systems B interfaces lt-1/2/0 unit 2 description to-A
set logical-systems B interfaces lt-1/2/0 unit 2 encapsulation ethernet
set logical-systems B interfaces lt-1/2/0 unit 2 peer-unit 1
set logical-systems B interfaces lt-1/2/0 unit 2 family inet address 10.10.10.2/30
set logical-systems B interfaces lt-1/2/0 unit 5 description to-C
set logical-systems B interfaces lt-1/2/0 unit 5 encapsulation ethernet
set logical-systems B interfaces lt-1/2/0 unit 5 peer-unit 6
set logical-systems B interfaces lt-1/2/0 unit 5 family inet address 10.10.10.5/30
set logical-systems B interfaces lo0 unit 2 family inet address 192.163.6.4/32
set logical-systems B protocols bgp group internal-peers type internal
set logical-systems B protocols bgp group internal-peers local-address 192.163.6.4
set logical-systems B protocols bgp group internal-peers export send-direct
set logical-systems B protocols bgp group internal-peers bfd-liveness-detection
    minimum-interval 1000
set logical-systems B protocols bgp group internal-peers neighbor 192.168.40.4
set logical-systems B protocols bgp group internal-peers neighbor 192.168.6.5
set logical-systems B protocols ospf area 0.0.0.0 interface lo0.2 passive
set logical-systems B protocols ospf area 0.0.0.0 interface lt-1/2/0.2
set logical-systems B protocols ospf area 0.0.0.0 interface lt-1/2/0.5
set logical-systems B policy-options policy-statement send-direct term 2 from protocol
    direct
set logical-systems B policy-options policy-statement send-direct term 2 then accept
set logical-systems B routing-options router-id 192.163.6.4
set logical-systems B routing-options autonomous-system 17
```

Device C

```
set logical-systems C interfaces lt-1/2/0 unit 6 description to-B
set logical-systems C interfaces lt-1/2/0 unit 6 encapsulation ethernet
set logical-systems C interfaces lt-1/2/0 unit 6 peer-unit 5
set logical-systems C interfaces lt-1/2/0 unit 6 family inet address 10.10.10.6/30
set logical-systems C interfaces lo0 unit 3 family inet address 192.168.40.4/32
set logical-systems C protocols bgp group internal-peers type internal
set logical-systems C protocols bgp group internal-peers local-address 192.168.40.4
set logical-systems C protocols bgp group internal-peers export send-direct
set logical-systems C protocols bgp group internal-peers bfd-liveness-detection
    minimum-interval 1000
set logical-systems C protocols bgp group internal-peers neighbor 192.163.6.4
```

```

set logical-systems C protocols bgp group internal-peers neighbor 192.168.6.5
set logical-systems C protocols ospf area 0.0.0.0 interface lo0.3 passive
set logical-systems C protocols ospf area 0.0.0.0 interface lt-1/2/0.6
set logical-systems C policy-options policy-statement send-direct term 2 from protocol
  direct
set logical-systems C policy-options policy-statement send-direct term 2 then accept
set logical-systems C routing-options router-id 192.168.40.4
set logical-systems C routing-options autonomous-system 17

```

### Configuring Device A

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device A:

1. Set the CLI to Logical System A.

```
user@host> set cli logical-system A
```

2. Configure the interfaces.

```

[edit interfaces lt-1/2/0 unit 1]
user@host:A# set description to-B
user@host:A# set encapsulation ethernet
user@host:A# set peer-unit 2
user@host:A# set family inet address 10.10.10.1/30

```

```

[edit interfaces lo0 unit 1]
user@host:A# set family inet address 192.168.6.5/32

```

3. Configure BGP.

The **neighbor** statements are included for both Device B and Device C, even though Device A is not directly connected to Device C.

```

[edit protocols bgp group internal-peers]
user@host:A# set type internal
user@host:A# set local-address 192.168.6.5
user@host:A# set export send-direct
user@host:A# set neighbor 192.163.6.4
user@host:A# set neighbor 192.168.40.4

```

4. Configure BFD.

```

[edit protocols bgp group internal-peers]
user@host:A# set bfd-liveness-detection minimum-interval 1000

```

You must configure the same minimum interval on the connecting peer.

5. (Optional) Configure BFD tracing.

```

[edit protocols bgp group internal-peers]
user@host:A# set traceoptions file bgp-bfd
user@host:A# set traceoptions flag bfd detail

```

6. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
```

```
user@host:A# set interface lo0.1 passive
user@host:A# set interface lt-1/2/0.1
```

7. Configure a policy that accepts direct routes.

Other useful options for this scenario might be to accept routes learned through OSPF or local routes.

```
[edit policy-options policy-statement send-direct term 2]
user@host:A# set from protocol direct
user@host:A# set then accept
```

8. Configure the router ID and the autonomous system (AS) number.

```
[edit routing-options]
user@host:A# set router-id 192.168.6.5
user@host:A# set autonomous-system 17
```

9. If you are done configuring the device, enter **commit** from configuration mode. Repeat these steps to configure Device B and Device C.

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host:A# show interfaces
lt-1/2/0 {
  unit 1 {
    description to-B;
    encapsulation ethernet;
    peer-unit 2;
    family inet {
      address 10.10.10.1/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 192.168.6.5/32;
    }
  }
}

user@host:A# show policy-options
policy-statement send-direct {
  term 2 {
    from protocol direct;
    then accept;
  }
}

user@host:A# show protocols
bgp {
  group internal-peers {
    type internal;
    traceoptions {
```

```

        file bgp-bfd;
        flag bfd detail;
    }
    local-address 192.168.6.5;
    export send-direct;
    bfd-liveness-detection {
        minimum-interval 1000;
    }
    neighbor 192.163.6.4;
    neighbor 192.168.40.4;
}
}
ospf {
    area 0.0.0.0 {
        interface lo0.1 {
            passive;
        }
        interface lt-1/2/0.1;
    }
}

user@host:A# show routing-options
router-id 192.168.6.5;
autonomous-system 17;

```

### Verification

Confirm that the configuration is working properly.

- [Verifying That BFD Is Enabled on page 227](#)
- [Verifying That BFD Sessions Are Up on page 228](#)
- [Viewing Detailed BFD Events on page 228](#)
- [Viewing Detailed BFD Events After Deactivating and Reactivating a Loopback Interface on page 229](#)

#### *Verifying That BFD Is Enabled*

|                |                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Purpose</b> | Verify that BFD is enabled between the IBGP peers.                                                                                                                                                                                                                                                                                                                                                     |
| <b>Action</b>  | <p>From operational mode, enter the <b>show bgp neighbor</b> command. You can use the <b>  match bfd</b> filter to narrow the output.</p> <pre> user@host:A&gt; show bgp neighbor   match bfd Options: &lt;BfdEnabled&gt; BFD: enabled, up Trace file: /var/log/A/bgp-bfd size 131072 files 10 Options: &lt;BfdEnabled&gt; BFD: enabled, up Trace file: /var/log/A/bgp-bfd size 131072 files 10 </pre> |
| <b>Meaning</b> | The output shows that Logical System A has two neighbors with BFD enabled. When BFD is not enabled, the output displays <b>BFD: disabled, down</b> , and the <b>&lt;BfdEnabled&gt;</b> option is absent. If BFD is enabled and the session is down, the output displays <b>BFD: enabled</b> ,                                                                                                          |

**down.** The output also shows that BFD-related events are being written to a log file because trace operations are configured.

### *Verifying That BFD Sessions Are Up*

**Purpose** Verify that the BFD sessions are up, and view details about the BFD sessions.

**Action** From operational mode, enter the **show bfd session extensive** command.

```
user@host:A> show bfd session extensive
```

| Address                                                              | State | Interface | Detect Time | Transmit Interval | Multiplier |
|----------------------------------------------------------------------|-------|-----------|-------------|-------------------|------------|
| 192.163.6.4                                                          | Up    |           | 3.000       | 1.000             | 3          |
| Client BGP, TX interval 1.000, RX interval 1.000                     |       |           |             |                   |            |
| Session up time 00:54:40                                             |       |           |             |                   |            |
| Local diagnostic None, remote diagnostic None                        |       |           |             |                   |            |
| Remote state Up, version 1                                           |       |           |             |                   |            |
| Logical system 12, routing table index 25                            |       |           |             |                   |            |
| Min async interval 1.000, min slow interval 1.000                    |       |           |             |                   |            |
| Adaptive async TX interval 1.000, RX interval 1.000                  |       |           |             |                   |            |
| Local min TX interval 1.000, minimum RX interval 1.000, multiplier 3 |       |           |             |                   |            |
| Remote min TX interval 1.000, min RX interval 1.000, multiplier 3    |       |           |             |                   |            |
| Local discriminator 10, remote discriminator 9                       |       |           |             |                   |            |
| Echo mode disabled/inactive                                          |       |           |             |                   |            |
| Multi-hop route table 25, local-address 192.168.6.5                  |       |           |             |                   |            |

| Address                                                              | State | Interface | Detect Time | Transmit Interval | Multiplier |
|----------------------------------------------------------------------|-------|-----------|-------------|-------------------|------------|
| 192.168.40.4                                                         | Up    |           | 3.000       | 1.000             | 3          |
| Client BGP, TX interval 1.000, RX interval 1.000                     |       |           |             |                   |            |
| Session up time 00:48:03                                             |       |           |             |                   |            |
| Local diagnostic None, remote diagnostic None                        |       |           |             |                   |            |
| Remote state Up, version 1                                           |       |           |             |                   |            |
| Logical system 12, routing table index 25                            |       |           |             |                   |            |
| Min async interval 1.000, min slow interval 1.000                    |       |           |             |                   |            |
| Adaptive async TX interval 1.000, RX interval 1.000                  |       |           |             |                   |            |
| Local min TX interval 1.000, minimum RX interval 1.000, multiplier 3 |       |           |             |                   |            |
| Remote min TX interval 1.000, min RX interval 1.000, multiplier 3    |       |           |             |                   |            |
| Local discriminator 14, remote discriminator 13                      |       |           |             |                   |            |
| Echo mode disabled/inactive                                          |       |           |             |                   |            |
| Multi-hop route table 25, local-address 192.168.6.5                  |       |           |             |                   |            |

2 sessions, 2 clients

Cumulative transmit rate 2.0 pps, cumulative receive rate 2.0 pps

**Meaning** The TX interval 1.000, RX interval 1.000 output represents the setting configured with the **minimum-interval** statement. All of the other output represents the default settings for BFD. To modify the default settings, include the optional statements under the [bfd-liveness-detection](#) statement.

### *Viewing Detailed BFD Events*

**Purpose** View the contents of the BFD trace file to assist in troubleshooting, if needed.

**Action** From operational mode, enter the **file show /var/log/A/bgp-bfd** command.

```
user@host:A> file show /var/log/A/bgp-bfd
```

```

Aug 15 17:07:25 trace_on: Tracing to "/var/log/A/bgp-bfd" started
Aug 15 17:07:26.492190 bgp_peer_init: BGP peer 192.163.6.4 (Internal AS 17) local
address 192.168.6.5 not found. Leaving peer idled
Aug 15 17:07:26.493176 bgp_peer_init: BGP peer 192.168.40.4 (Internal AS 17) local
address 192.168.6.5 not found. Leaving peer idled
Aug 15 17:07:32.597979 task_connect: task BGP_17.192.163.6.4+179 addr
192.163.6.4+179: No route to host
Aug 15 17:07:32.599623 bgp_connect_start: connect 192.163.6.4 (Internal AS 17):
No route to host
Aug 15 17:07:36.869394 task_connect: task BGP_17.192.168.40.4+179 addr
192.168.40.4+179: No route to host
Aug 15 17:07:36.870624 bgp_connect_start: connect 192.168.40.4 (Internal AS 17):
No route to host
Aug 15 17:08:04.599220 task_connect: task BGP_17.192.163.6.4+179 addr
192.163.6.4+179: No route to host
Aug 15 17:08:04.601135 bgp_connect_start: connect 192.163.6.4 (Internal AS 17):
No route to host
Aug 15 17:08:08.869717 task_connect: task BGP_17.192.168.40.4+179 addr
192.168.40.4+179: No route to host
Aug 15 17:08:08.869934 bgp_connect_start: connect 192.168.40.4 (Internal AS 17):
No route to host
Aug 15 17:08:36.603544 advertising receiving-speaker only capability to neighbor
192.163.6.4 (Internal AS 17)
Aug 15 17:08:36.606726 bgp_read_message: 192.163.6.4 (Internal AS 17): 0 bytes
buffered
Aug 15 17:08:36.609119 Initiated BFD session to peer 192.163.6.4 (Internal AS
17): address=192.163.6.4 ifindex=0 ifname=(none) txivl=1000 rxivl=1000 mult=3
ver=255
Aug 15 17:08:36.734033 advertising receiving-speaker only capability to neighbor
192.168.40.4 (Internal AS 17)
Aug 15 17:08:36.738436 Initiated BFD session to peer 192.168.40.4 (Internal AS
17): address=192.168.40.4 ifindex=0 ifname=(none) txivl=1000 rxivl=1000 mult=3
ver=255
Aug 15 17:08:40.537552 BFD session to peer 192.163.6.4 (Internal AS 17) up
Aug 15 17:08:40.694410 BFD session to peer 192.168.40.4 (Internal AS 17) up

```

**Meaning** Before the routes are established, the **No route to host** message appears in the output. After the routes are established, the last two lines show that both BFD sessions come up.

#### *Viewing Detailed BFD Events After Deactivating and Reactivating a Loopback Interface*

**Purpose** Check to see what happens after bringing down a router or switch and then bringing it back up. To simulate bringing down a router or switch, deactivate the loopback interface on Logical System B.

**Action** 1. From configuration mode, enter the **deactivate logical-systems B interfaces lo0 unit 2 family inet** command.

```

user@host:A# deactivate logical-systems B interfaces lo0 unit 2 family inet
user@host:A# commit

```

2. From operational mode, enter the **file show /var/log/A/bgp-bfd** command.

```

user@host:A> file show /var/log/A/bgp-bfd
...
Aug 15 17:20:55.995648 bgp_read_v4_message:9747: NOTIFICATION received from
192.163.6.4 (Internal AS 17): code 6 (Cease) subcode 6 (Other Configuration
Change)

```

```

Aug 15 17:20:56.004508 Terminated BFD session to peer 192.163.6.4 (Internal
AS 17)
Aug 15 17:21:28.007755 task_connect: task BGP_17.192.163.6.4+179 addr
192.163.6.4+179: No route to host
Aug 15 17:21:28.008597 bgp_connect_start: connect 192.163.6.4 (Internal AS
17): No route to host

```

- From configuration mode, enter the **activate logical-systems B interfaces lo0 unit 2 family inet** command.

```

user@host:A# activate logical-systems B interfaces lo0 unit 2 family inet
user@host:A# commit

```

- From operational mode, enter the **file show /var/log/A/bgp-bfd** command.

```

user@host:A> file show /var/log/A/bgp-bfd
...
Aug 15 17:25:53.623743 advertising receiving-speaker only capability to neighbor
192.163.6.4 (Internal AS 17)
Aug 15 17:25:53.631314 Initiated BFD session to peer 192.163.6.4 (Internal AS
17): address=192.163.6.4 ifindex=0 ifname=(none) txivl=1000 rxivl=1000 mult=3
ver=255
Aug 15 17:25:57.570932 BFD session to peer 192.163.6.4 (Internal AS 17) up

```

Release History Table

| Release | Description                                                                                                                                                  |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.2    | In Junos OS Release 11.2 and later, BFD supports IPv6 interfaces with BGP.                                                                                   |
| 9.1     | In Junos OS Release 9.1 through Junos OS Release 11.1, BFD supports IPv6 interfaces in static routes only.                                                   |
| 8.3     | In Junos OS Release 8.3 and later, BFD is supported on internal BGP (IBGP) and multihop external BGP (EBGP) sessions as well as on single-hop EBGP sessions. |

#### Related Documentation

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

## Example: Configuring BFD Authentication for BGP

- [Understanding BFD Authentication for BGP on page 230](#)
- [Example: Configuring BFD Authentication for BGP on page 232](#)

### Understanding BFD Authentication for BGP

Bidirectional Forwarding Detection protocol (BFD) enables rapid detection of communication failures between adjacent systems. By default, authentication for BFD sessions is disabled. However, when you run BFD over Network Layer protocols, the risk of service attacks can be significant. We strongly recommend using authentication if you are running BFD over multiple hops or through insecure tunnels. Beginning with Junos OS Release 9.6, Junos OS supports authentication for BFD sessions running over BGP. BFD authentication is not supported on MPLS OAM sessions. BFD authentication is only



supported in the Canada and United States version of the Junos OS image and is not available in the export version.

You authenticate BFD sessions by specifying an authentication algorithm and keychain, and then associating that configuration information with a security authentication keychain using the keychain name.

The following sections describe the supported authentication algorithms, security keychains, and level of authentication that can be configured:

- [BFD Authentication Algorithms on page 231](#)
- [Security Authentication Keychains on page 232](#)
- [Strict Versus Loose Authentication on page 232](#)

### BFD Authentication Algorithms

---

Junos OS supports the following algorithms for BFD authentication:

- **simple-password**—Plain-text password. One to 16 bytes of plain text are used to authenticate the BFD session. One or more passwords can be configured. This method is the least secure and should be used only when BFD sessions are not subject to packet interception.
- **keyed-md5**—Keyed Message Digest 5 hash algorithm for sessions with transmit and receive intervals greater than 100 ms. To authenticate the BFD session, keyed MD5 uses one or more secret keys (generated by the algorithm) and a sequence number that is updated periodically. With this method, packets are accepted at the receiving end of the session if one of the keys matches and the sequence number is greater than or equal to the last sequence number received. Although more secure than a simple password, this method is vulnerable to replay attacks. Increasing the rate at which the sequence number is updated can reduce this risk.
- **meticulous-keyed-md5**—Meticulous keyed Message Digest 5 hash algorithm. This method works in the same manner as keyed MD5, but the sequence number is updated with every packet. Although more secure than keyed MD5 and simple passwords, this method might take additional time to authenticate the session.
- **keyed-sha-1**—Keyed Secure Hash Algorithm I for sessions with transmit and receive intervals greater than 100 ms. To authenticate the BFD session, keyed SHA uses one or more secret keys (generated by the algorithm) and a sequence number that is updated periodically. The key is not carried within the packets. With this method, packets are accepted at the receiving end of the session if one of the keys matches and the sequence number is greater than the last sequence number received.
- **meticulous-keyed-sha-1**—Meticulous keyed Secure Hash Algorithm I. This method works in the same manner as keyed SHA, but the sequence number is updated with every packet. Although more secure than keyed SHA and simple passwords, this method might take additional time to authenticate the session.



**NOTE:** Nonstop active routing (NSR) is not supported with meticulous-keyed-md5 and meticulous-keyed-sha-1 authentication algorithms. BFD sessions using these algorithms might go down after a switchover.

---

### Security Authentication Keychains

The security authentication keychain defines the authentication attributes used for authentication key updates. When the security authentication keychain is configured and associated with a protocol through the keychain name, authentication key updates can occur without interrupting routing and signaling protocols.

The authentication keychain contains one or more keychains. Each keychain contains one or more keys. Each key holds the secret data and the time at which the key becomes valid. The algorithm and keychain must be configured on both ends of the BFD session, and they must match. Any mismatch in configuration prevents the BFD session from being created.

BFD allows multiple clients per session, and each client can have its own keychain and algorithm defined. To avoid confusion, we recommend specifying only one security authentication keychain.

---

### Strict Versus Loose Authentication

By default, strict authentication is enabled and authentication is checked at both ends of each BFD session. Optionally, to smooth migration from nonauthenticated sessions to authenticated sessions, you can configure *loose checking*. When loose checking is configured, packets are accepted without authentication being checked at each end of the session. This feature is intended for transitional periods only.

### Example: Configuring BFD Authentication for BGP

Beginning with Junos OS Release 9.6, you can configure authentication for BFD sessions running over BGP. Only three steps are needed to configure authentication on a BFD session:

1. Specify the BFD authentication algorithm for the BGP protocol.
2. Associate the authentication keychain with the BGP protocol.
3. Configure the related security authentication keychain.

The following sections provide instructions for configuring and viewing BFD authentication on BGP:

- [Configuring BFD Authentication Parameters on page 232](#)
- [Viewing Authentication Information for BFD Sessions on page 234](#)

---

### Configuring BFD Authentication Parameters

BFD authentication can be configured for the entire BGP protocol, or a specific BGP group, neighbor, or routing instance.

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure BFD authentication:

1. Specify the algorithm (**keyed-md5**, **keyed-sha-1**, **meticulous-keyed-md5**, **meticulous-keyed-sha-1**, or **simple-password**) to use.

```
[edit]
user@host# set protocols bgp bfd-liveness-detection authentication algorithm
keyed-sha-1
user@host# set protocols bgp group bgp-gr1 bfd-liveness-detection authentication
algorithm keyed-sha-1
user@host# set protocols bgp group bgp-gr1 neighbor 10.10.10.7 bfd-liveness-detection
authentication algorithm keyed-sha-1
```



**NOTE:** Nonstop active routing is not supported with meticulous-keyed-md5 and meticulous-keyed-sha-1 authentication algorithms. BFD sessions using these algorithms might go down after a switchover.

2. Specify the keychain to be used to associate BFD sessions on BGP with the unique security authentication keychain attributes.

The keychain name you specify must match a keychain name configured at the **[edit security authentication key-chains]** hierarchy level.

```
[edit]
user@host# set protocols bgp bfd-liveness-detection authentication keychain bfd-bgp
user@host# set protocols bgp group bgp-gr1 bfd-liveness-detection authentication
keychain bfd-bgp
user@host# set protocols bgp group bgp-gr1 neighbor 10.10.10.7 bfd-liveness-detection
authentication keychain bfd-bgp
```



**NOTE:** The algorithm and keychain must be configured on both ends of the BFD session, and they must match. Any mismatch in configuration prevents the BFD session from being created.

3. Specify the unique security authentication information for BFD sessions:
  - The matching keychain name as specified in Step 2.
  - At least one key, a unique integer between **0** and **63**. Creating multiple keys allows multiple clients to use the BFD session.
  - The secret data used to allow access to the session.
  - The time at which the authentication key becomes active, in the format *yyyy-mm-dd.hh:mm:ss*.

```
[edit security]
```

```
user@host# set authentication-key-chains key-chain bfd-bgp key 53 secret
$ABC123$ABC123 start-time 2009-06-14.10:00:00
```

4. (Optional) Specify loose authentication checking if you are transitioning from nonauthenticated sessions to authenticated sessions.

```
[edit]
user@host# set protocols bgp bfd-liveness-detection authentication loose-check
user@host# set protocols bgp group bgp-gr1 bfd-liveness-detection authentication
loose-check
user@host# set protocols bgp group bgp-gr1 neighbor 10.10.10.7 bfd-liveness-detection
authentication loose-check
```

5. (Optional) View your configuration using the **show bfd session detail** or **show bfd session extensive** command.
6. Repeat these steps to configure the other end of the BFD session.



**NOTE:** BFD authentication is only supported in the Canada and United States version of the Junos OS image and is not available in the export version.

### Viewing Authentication Information for BFD Sessions

You can view the existing BFD authentication configuration using the **show bfd session detail** and **show bfd session extensive** commands.

The following example shows BFD authentication configured for the **bgp-gr1** BGP group. It specifies the keyed SHA-1 authentication algorithm and a keychain name of **bfd-bgp**. The authentication keychain is configured with two keys. Key 1 contains the secret data “\$ABC123\$ABC123” and a start time of June 1, 2009, at 9:46:02 AM PST. Key 2 contains the secret data “\$ABC123\$ABC123” and a start time of June 1, 2009, at 3:29:20 PM PST.

```
[edit protocols bgp]
group bgp-gr1 {
  bfd-liveness-detection {
    authentication {
      algorithm keyed-sha-1;
      key-chain bfd-bgp;
    }
  }
}
[edit security]
authentication key-chains {
  key-chain bfd-bgp {
    key 1 {
      secret "$ABC123$ABC123";
      start-time "2009-6-1.09:46:02 -0700";
    }
    key 2 {
      secret "$ABC123$ABC123";
      start-time "2009-6-1.15:29:20 -0700";
    }
  }
}
```

If you commit these updates to your configuration, you see output similar to the following. In the output for the **show bfd session detail** command, **Authenticate** is displayed to indicate that BFD authentication is configured. For more information about the configuration, use the **show bfd session extensive** command. The output for this command provides the keychain name, the authentication algorithm and mode for each client in the session, and the overall BFD authentication configuration status, keychain name, and authentication algorithm and mode.

#### show bfd session detail

```
user@host# show bfd session detail
```

| Address   | State | Interface  | Detect Time | Transmit Interval | Multiplier |
|-----------|-------|------------|-------------|-------------------|------------|
| 192.0.2.2 | Up    | ge-0/1/5.0 | 0.900       | 0.300             | 3          |

Client BGP, TX interval 0.300, RX interval 0.300, **Authenticate**  
 Session up time 3d 00:34  
 Local diagnostic None, remote diagnostic NbrSignal  
 Remote state Up, version 1  
 Replicated

#### show bfd session extensive

```
user@host# show bfd session extensive
```

| Address   | State | Interface  | Detect Time | Transmit Interval | Multiplier |
|-----------|-------|------------|-------------|-------------------|------------|
| 192.0.2.2 | Up    | ge-0/1/5.0 | 0.900       | 0.300             | 3          |

Client BGP, TX interval 0.300, RX interval 0.300, **Authenticate**  
**keychain bfd-bgp, algo keyed-sha-1, mode strict**  
 Session up time 00:04:42  
 Local diagnostic None, remote diagnostic NbrSignal  
 Remote state Up, version 1  
 Replicated  
 Min async interval 0.300, min slow interval 1.000  
 Adaptive async TX interval 0.300, RX interval 0.300  
 Local min TX interval 0.300, minimum RX interval 0.300, multiplier 3  
 Remote min TX interval 0.300, min RX interval 0.300, multiplier 3  
 Local discriminator 2, remote discriminator 2  
 Echo mode disabled/inactive  
**Authentication enabled/active, keychain bfd-bgp, algo keyed-sha-1, mode strict**

- Related Documentation**
- [Understanding External BGP Peering Sessions on page 13](#)
  - [BGP Configuration Overview](#)



## CHAPTER 6

# BGP Load Balancing Configuration

- [Examples: Configuring BGP Multipath on page 237](#)
- [Example: Advertising Multiple BGP Paths to a Destination on page 254](#)
- [Example: Advertising Multiple Paths in BGP on page 255](#)
- [Configuring ECMP Next Hops for RSVP and LDP LSPs for Load Balancing on page 281](#)

## Examples: Configuring BGP Multipath

---

- [Understanding BGP Multipath on page 237](#)
- [Example: Load Balancing BGP Traffic on page 238](#)
- [Example: Configuring Single-Hop EBGP Peers to Accept Remote Next Hops on page 243](#)

## Understanding BGP Multipath

BGP multipath allows you to install multiple internal BGP paths and multiple external BGP paths to the forwarding table. Selecting multiple paths enables BGP to load-balance traffic across multiple links.

A path is considered a BGP equal-cost path (and is used for forwarding) if the BGP path selection process performs a tie-break after comparing the IGP cost to the next-hop. By default, all paths with the same neighboring AS, learned by a multipath-enabled BGP neighbor are considered in the multipath selection process.

BGP, typically selects only one best path for each prefix and installs that route in the forwarding table. When BGP multipath is enabled, the device selects multiple equal-cost BGP paths to reach a given destination, and all these paths are installed in the forwarding table. BGP advertises only the active path to its neighbors, unless add-path is in use.

The Junos OS BGP multipath feature supports the following applications:

- Load balancing across multiple links between two routing devices belonging to different autonomous systems (ASs)
- Load balancing across a common subnet or multiple subnets to different routing devices belonging to the same peer AS

- Load balancing across multiple links between two routing devices belonging to different external confederation peers
- Load balancing across a common subnet or multiple subnets to different routing devices belonging to external confederation peers

In a common scenario for load balancing, a customer is multihomed to multiple routers in a point of presence (POP). The default behavior is to send all traffic across only one of the available links. Load balancing causes traffic to use two or more of the links.

BGP multipath does not apply to paths that share the same MED-plus-IGP cost, yet differ in IGP cost. Multipath path selection is based on the IGP cost metric, even if two paths have the same MED-plus-IGP cost.

### Example: Load Balancing BGP Traffic

This example shows how to configure BGP to select multiple equal-cost external BGP (EBGP) or internal BGP (IBGP) paths as active paths.

- [Requirements on page 238](#)
- [Overview on page 238](#)
- [Configuration on page 239](#)
- [Verification on page 241](#)

---

#### Requirements

Before you begin:

- Configure the device interfaces.
- Configure an interior gateway protocol (IGP).
- Configure BGP.
- Configure a routing policy that exports routes (such as direct routes or IGP routes) from the routing table into BGP.

---

#### Overview

The following steps show how to configure per-packet load balancing:

1. Define a load-balancing routing policy by including one or more **policy-statement** statements at the **[edit policy-options]** hierarchy level, defining an action of **load-balance per-packet**:

```
policy-statement policy-name {  
  from {  
    match-conditions;  
    route-filter destination-prefix match-type <actions>;  
    prefix-list name;  
  }  
  then {  
    load-balance per-packet;  
  }  
}
```



2. Apply the policy to routes exported from the routing table to the forwarding table. To do this, include the **forwarding-table** and **export** statements:

```
forwarding-table {
  export policy-name;
}
```

You cannot apply the export policy to VRF routing instances.

3. Specify all next hops of that route, if more than one exists, when allocating a label corresponding to a route that is being advertised.
4. Configure the forwarding-options hash key for MPLS to include the IP payload.




**NOTE:** On some platforms, you can increase the number of paths that are load balanced by using the `chassis maximum-ecmp` statement. With this statement, you can change the maximum number of equal-cost load-balanced paths to 32 or 64.

In this example, Device R1 is in AS 65000 and is connected to both Device R2 and Device R3, which are in AS 65001. This example shows the configuration on Device R1.

#### Topology

Figure 24 on page 239 shows the topology used in this example.

Figure 24: BGP Load Balancing



#### Configuration

##### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set protocols bgp group external type external
set protocols bgp group external peer-as 65001
```

```

set protocols bgp group external multipath
set protocols bgp group external neighbor 10.0.1.1
set protocols bgp group external neighbor 10.0.0.2
set policy-options policy-statement loadbal from route-filter 10.0.0.0/16 orlonger
set policy-options policy-statement loadbal then load-balance per-packet
set routing-options forwarding-table export loadbal
set routing-options autonomous-system 65000

```

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the BGP peer sessions:

1. Configure the BGP group.  

```

[edit protocols bgp group external]
user@R1# set type external
user@R1# set peer-as 65001
user@R1# set neighbor 10.0.1.1
user@R1# set neighbor 10.0.0.2

```
2. Enable the BGP group to use multiple paths.



**NOTE:** To disable the default check requiring that paths accepted by BGP multipath must have the same neighboring autonomous system (AS), include the `multiple-as` option.

```

[edit protocols bgp group external]
user@R1# set multipath

```

3. Configure the load-balancing policy.  

```

[edit policy-options policy-statement loadbal]
user@R1# set from route-filter 10.0.0.0/16 orlonger
user@R1# set then load-balance per-packet

```
4. Apply the load-balancing policy.  

```

[edit routing-options]
user@R1# set forwarding-table export loadbal

```
5. Configure the local autonomous system (AS) number.  

```

[edit routing-options]
user@R1# set autonomous-system 65000

```

**Results** From configuration mode, confirm your configuration by entering the **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@R1# show protocols
bgp {

```

```

group external {
  type external;
  peer-as 65001;
  multipath;
  neighbor 10.0.1.1;
  neighbor 10.0.0.2;
}
}

[edit]
user@R1# show policy-options
policy-statement loadbal {
  from {
    route-filter 10.0.0.0/16 orlonger;
  }
  then {
    load-balance per-packet;
  }
}

[edit]
user@R1# show routing-options
autonomous-system 65000;
forwarding-table {
  export loadbal;
}

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly:

- [Verifying Routes on page 241](#)
- [Verifying Forwarding on page 242](#)

### Verifying Routes

**Purpose** Verify that routes are learned from both routers in the neighboring AS.

**Action** From operational mode, run the **show route** command.

```

user@R1> show route 10.0.2.0
inet.0: 12 destinations, 15 routes (12 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.0.2.0/30          *[BGP/170] 03:12:32, localpref 100
                    AS path: 65001 I
                    to 10.0.1.1 via ge-1/2/0.0
                    > to 10.0.0.2 via ge-1/2/1.0
                    [BGP/170] 03:12:32, localpref 100
                    AS path: 65001 I
                    > to 10.0.1.1 via ge-1/2/0.0

user@R1> show route 10.0.2.0 detail
inet.0: 12 destinations, 15 routes (12 active, 0 holddown, 0 hidden)
10.0.2.0/30 (2 entries, 1 announced)
    *BGP      Preference: 170/-101

```

```

Next hop type: Router, Next hop index: 262142
Next-hop reference count: 3
Source: 10.0.0.2
Next hop: 10.0.1.1 via ge-1/2/0.0
Next hop: 10.0.0.2 via ge-1/2/1.0, selected
State: <Active Ext>
Local AS: 65000 Peer AS: 65001
Age: 3:18:30
Task: BGP_65001.10.0.0.2+55402
Announcement bits (1): 2-KRT
AS path: 65001 I
Accepted Multipath
Localpref: 100
Router ID: 192.168.2.1
BGP Preference: 170/-101
Next hop type: Router, Next hop index: 602
Next-hop reference count: 5
Source: 10.0.1.1
Next hop: 10.0.1.1 via ge-1/2/0.0, selected
State: <NotBest Ext>
Inactive reason: Not Best in its group - Active preferred
Local AS: 65000 Peer AS: 65001
Age: 3:18:30
Task: BGP_65001.10.0.1.1+53135
AS path: 65001 I
Accepted
Localpref: 100
Router ID: 192.168.3.1

```

**Meaning** The active path, denoted with an asterisk (\*), has two next hops: 10.0.1.1 and 10.0.0.2 to the 10.0.2.0 destination. The 10.0.1.1 next hop is copied from the inactive path to the active path.



**NOTE:** The `show route detail` command output designates one gateway as selected. This output is potentially confusing in the context of load balancing. The selected gateway is used for many purposes in addition to deciding which gateway to install into the kernel when Junos OS is not performing per-packet load-balancing. For instance, the `ping mpls` command uses the selected gateway when sending packets. Multicast protocols use the selected gateway in some cases to determine the upstream interface. Therefore, even when Junos OS is performing per-packet load-balancing by way of a forwarding-table policy, the selected gateway information is still required for other purposes. It is useful to display the selected gateway for troubleshooting purposes. Additionally, it is possible to use forwarding-table policy to override what is installed into the kernel (for example, by using the `install-nexthop` action). In this case, the next-hop gateway installed in the forwarding table might be a subset of the total gateways displayed in the `show route` command.

### Verifying Forwarding

**Purpose** Verify that both next hops are installed in the forwarding table.

**Action** From operational mode, run the **show route forwarding-table** command.

```
user@R1> show route forwarding-table destination 10.0.2.0
Routing table: default.inet
Internet:
Destination          Type RtRef Next hop          Type Index NhRef Netif
10.0.2.0/30          user   0          10.0.1.1          ucst   602    5 ge-1/2/0.0
                    user   0          10.0.0.2          ucst   522    6 ge-1/2/1.0
```

## Example: Configuring Single-Hop EBGP Peers to Accept Remote Next Hops

This example shows how to configure a single-hop external BGP (EBGP) peer to accept a remote next hop with which it does not share a common subnet.

- [Requirements on page 243](#)
- [Overview on page 243](#)
- [Configuration on page 244](#)
- [Verification on page 252](#)

### Requirements

No special configuration beyond device initialization is required before you configure this example.

### Overview

In some situations, it is necessary to configure a single-hop EBGP peer to accept a remote next hop with which it does not share a common subnet. The default behavior is for any next-hop address received from a single-hop EBGP peer that is not recognized as sharing a common subnet to be discarded. The ability to have a single-hop EBGP peer accept a remote next hop to which it is not directly connected also prevents you from having to configure the single-hop EBGP neighbor as a multihop session. When you configure a multihop session in this situation, all next-hop routes learned through this EBGP peer are labeled indirect even when they do share a common subnet. This situation breaks multipath functionality for routes that are recursively resolved over routes that include these next-hop addresses. Configuring the [accept-remote-nexthop](#) statement allows a single-hop EBGP peer to accept a remote next hop, which restores multipath functionality for routes that are resolved over these next-hop addresses. You can configure this statement at the global, group, and neighbor hierarchy levels for BGP. The statement is also supported on logical systems and the VPN routing and forwarding (VRF) routing instance type. Both the remote next-hop and the EBGP peer must support BGP route refresh as defined in RFC 2918, *Route Refresh Capability in BGP-4*. If the remote peer does not support BGP route refresh, the session is reset.




**NOTE:** You cannot configure both the **multihop** and **accept-remote-nexthop** statements for the same EBGP peer.

When you enable a single-hop EBGP peer to accept a remote next hop, you must also configure an import routing policy on the EBGP peer that specifies the remote next-hop address.

This example includes an import routing policy, **agg\_route**, that enables a single-hop external BGP peer (Device R1) to accept the remote next-hop 1.1.10.10 for the route to the 1.1.230.0/23 network. At the **[edit protocols bgp]** hierarchy level, the example includes the **import agg\_route** statement to apply the policy to the external BGP peer and includes the **accept-remote-nexthop** statement to enable the single-hop EBGP peer to accept the remote next hop.

Figure 25 on page 244 shows the sample topology.

Figure 25: Topology for Accepting a Remote Next Hop



### Configuration

- [Device R0 on page 245](#)
- [Configuring Device R1 on page 248](#)
- [Configuring Device R2 on page 250](#)

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

#### Device R0

```
set interfaces fe-1/2/0 unit 1 family inet address 1.1.0.1/30
set interfaces fe-1/2/1 unit 2 family inet address 1.1.1.1/30
set interfaces lo0 unit 1 family inet address 10.255.14.179/32
set protocols bgp group ext type external
set protocols bgp group ext export test_route
set protocols bgp group ext export agg_route
set protocols bgp group ext peer-as 65000
set protocols bgp group ext multipath
set protocols bgp group ext neighbor 1.1.0.2
set protocols bgp group ext neighbor 1.1.1.2
set policy-options policy-statement agg_route term 1 from protocol static
```

```

set policy-options policy-statement agg_route term 1 from route-filter 1.1.230.0/23 exact
set policy-options policy-statement agg_route term 1 then accept
set policy-options policy-statement test_route term 1 from protocol static
set policy-options policy-statement test_route term 1 from route-filter 1.1.10.10/32 exact
set policy-options policy-statement test_route term 1 then accept
set routing-options static route 1.1.10.10/32 reject
set routing-options static route 1.1.230.0/23 reject
set routing-options autonomous-system 65500

```

**Device R1**

```

set interfaces fe-1/2/0 unit 3 family inet address 1.1.0.2/30
set interfaces fe-1/2/1 unit 4 family inet address 1.12.0.1/30
set interfaces fe-1/2/2 unit 5 family inet address 1.1.1.2/30
set interfaces lo0 unit 2 family inet address 10.255.71.24/32
set protocols bgp accept-remote-nexthop
set protocols bgp group ext type external
set protocols bgp group ext import agg_route
set protocols bgp group ext peer-as 65500
set protocols bgp group ext multipath
set protocols bgp group ext neighbor 1.1.0.1
set protocols bgp group ext neighbor 1.1.1.1
set protocols bgp group int type internal
set protocols bgp group int local-address 10.255.71.24
set protocols bgp group int neighbor 10.255.14.177
set protocols ospf area 0.0.0.0 interface fe-1/2/1.4
set protocols ospf area 0.0.0.0 interface 10.255.71.24
set policy-options policy-statement agg_route term 1 from protocol bgp
set policy-options policy-statement agg_route term 1 from route-filter 1.1.230.0/23 exact
set policy-options policy-statement agg_route term 1 then next-hop 1.1.10.10
set policy-options policy-statement agg_route term 1 then accept
set routing-options autonomous-system 65000

```

**Device R2**

```

set interfaces fe-1/2/0 unit 6 family inet address 1.12.0.2/30
set interfaces lo0 unit 3 family inet address 10.255.14.177/32
set protocols bgp group int type internal
set protocols bgp group int local-address 10.255.14.177
set protocols bgp group int neighbor 10.255.71.24
set protocols ospf area 0.0.0.0 interface fe-1/2/0.6
set protocols ospf area 0.0.0.0 interface 10.255.14.177
set routing-options autonomous-system 65000

```

### ***Device R0***

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R0:

1. Configure the interfaces.
 

```

[edit interfaces fe-1/2/0 unit 1]
user@R0# set family inet address 1.1.0.1/30

[edit interfaces fe-1/2/1 unit 2]
user@R0# set family inet address 1.1.1.1/30

```

- ```
[edit interfaces lo0 unit 1]
user@R0# set family inet address 10.255.14.179/32
```
2. Configure EBGp.

```
[edit protocols bgp group ext]
user@R0# set type external
user@R0# set peer-as 65000
user@R0# set neighbor 1.1.0.2
user@R0# set neighbor 1.1.1.2
```
  3. Enable multipath BGP between Device R0 and Device R1.

```
[edit protocols bgp group ext]
user@R0# set multipath
```
  4. Configure static routes to remote networks.  
These routes are not part of the topology. The purpose of these routes is to demonstrate the functionality in this example.

```
[edit routing-options]
user@R0# set static route 1.1.10.10/32 reject
user@R0# set static route 1.1.230.0/23 reject
```
  5. Configure routing policies that accept the static routes.

```
[edit policy-options policy-statement agg_route term 1]
user@R0# set from protocol static
user@R0# set from route-filter 1.1.230.0/23 exact
user@R0# set then accept

[edit policy-options policy-statement test_route term 1]
user@R0# set from protocol static
user@R0# set from route-filter 1.1.10.10/32 exact
user@R0# set then accept
```
  6. Export the **agg\_route** and **test\_route** policies from the routing table into BGP.

```
[edit protocols bgp group ext]
user@R0# set export test_route
user@R0# set export agg_route
```
  7. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@R0# set autonomous-system 65500
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R0# show interfaces
fe-1/2/0 {
  unit 1 {
    family inet {
      address 1.1.0.1/30;
    }
  }
}
```



```

}
fe-1/2/1 {
  unit 2 {
    family inet {
      address 1.1.1.1/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 10.255.14.179/32;
    }
  }
}

user@R0# show policy-options
policy-statement agg_route {
  term 1 {
    from {
      protocol static;
      route-filter 1.1.230.0/23 exact;
    }
    then accept;
  }
}
policy-statement test_route {
  term 1 {
    from {
      protocol static;
      route-filter 1.1.10.10/32 exact;
    }
    then accept;
  }
}

user@R0# show protocols
bgp {
  group ext {
    type external;
    export [ test_route agg_route ];
    peer-as 65000;
    multipath;
    neighbor 1.1.0.2;
    neighbor 1.1.1.2;
  }
}

user@R0# show routing-options
static {
  route 1.1.10.10/32 reject;
  route 1.1.230.0/23 reject;
}
autonomous-system 65500;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R1

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R1:

1. Configure the interfaces.  

```
[edit interfaces fe-1/2/0 unit 3]
user@R1# set family inet address 1.1.0.2/30

[edit interfaces fe-1/2/1 unit 4]
user@R1# set family inet address 1.12.0.1/30

[edit interfaces fe-1/2/2 unit 5]
user@R1# set family inet address 1.1.1.2/30

[edit interfaces lo0 unit 2]
user@R1# set family inet address 10.255.71.24/32
```
2. Configure OSPF.  

```
[edit protocols ospf area 0.0.0.0]
user@R1# set interface fe-1/2/1.4
user@R1# set interface 10.255.71.24
```
3. Enable Device R1 to accept the remote next hop.  

```
[edit protocols bgp]
user@R1# set accept-remote-nexthop
```
4. Configure IBGP.  

```
[edit protocols bgp group int]
user@R1# set type internal
user@R1# set local-address 10.255.71.24
user@R1# set neighbor 10.255.14.177
```
5. Configure EBGP.  

```
[edit protocols bgp group ext]
user@R1# set type external
user@R1# set peer-as 65500
user@R1# set neighbor 1.1.0.1
user@R1# set neighbor 1.1.1.1
```
6. Enable multipath BGP between Device R0 and Device R1.  

```
[edit protocols bgp group ext]
user@R1# set multipath
```
7. Configure a routing policy that enables a single-hop external BGP peer (Device R1) to accept the remote next-hop 1.1.10.10 for the route to the 1.1.230.0/23 network.  

```
[edit policy-options policy-statement agg_route term 1]
user@R1# set from protocol bgp
user@R1# set from route-filter 1.1.230.0/23 exact
```

```

user@R1# set then next-hop 1.1.10.10
user@R1# set then accept

```

8. Import the **agg\_route** policy into the routing table on Device R1.

```

[edit protocols bgp group ext]
user@R1# set import agg_route

```

9. Configure the autonomous system (AS) number.

```

[edit routing-options]
user@R1# set autonomous-system 65000

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show policy-options**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R1# show interfaces
fe-1/2/0 {
  unit 3 {
    family inet {
      address 1.1.0.2/30;
    }
  }
}
fe-1/2/1 {
  unit 4 {
    family inet {
      address 1.12.0.1/30;
    }
  }
}
fe-1/2/2 {
  unit 5 {
    family inet {
      address 1.1.1.2/30;
    }
  }
}
lo0 {
  unit 2 {
    family inet {
      address 10.255.71.24/32;
    }
  }
}
}

user@R1# show policy-options
policy-statement agg_route {
  term 1 {
    from {
      protocol bgp;
      route-filter 1.1.230.0/23 exact;
    }
    then {
      next-hop 1.1.10.10;
    }
  }
}

```

```

        accept;
    }
}
}

user@R1# show protocols
bgp {
    accept-remote-nexthop;
    group ext {
        type external;
        import agg_route;
        peer-as 65500;
        multipath;
        neighbor 1.1.0.1;
        neighbor 1.1.1.1;
    }
    group int {
        type internal;
        local-address 10.255.71.24;
        neighbor 10.255.14.177;
    }
}
}
ospf {
    area 0.0.0.0 {
        interface fe-1/2/1.4;
        interface 10.255.71.24;
    }
}
}

user@R1# show routing-options
autonomous-system 65000;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Configuring Device R2

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R2:

1. Configure the interfaces.
 

```

[edit interfaces fe-1/2/0 unit 6]
user@R2# set family inet address 1.12.0.2/30

[edit interfaces lo0 unit 3]
user@R2# set family inet address 10.255.14.177/32

```
2. Configure OSPF.
 

```

[edit protocols ospf area 0.0.0.0]
user@R2# set interface fe-1/2/0.6
user@R2# set interface 10.255.14.177

```
3. Configure IBGP.

```
[edit protocols bgp group int]
user@R2# set type internal
user@R2# set local-address 10.255.14.177
user@R2# set neighbor 10.255.71.24
```

4. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@R1# set autonomous-system 65000
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
fe-1/2/0 {
  unit 6 {
    family inet {
      address 1.12.0.2/30;
    }
  }
}
lo0 {
  unit 3 {
    family inet {
      address 10.255.14.177/32;
    }
  }
}

user@R2# show protocols
bgp {
  group int {
    type internal;
    local-address 10.255.14.177;
    neighbor 10.255.71.24;
  }
}
ospf {
  area 0.0.0.0 {
    interface fe-1/2/0.6;
    interface 10.255.14.177;
  }
}

user@R2# show routing-options
autonomous-system 65000;
```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Verifying That the Multipath Route with the Indirect Next Hop Is in the Routing Table on page 252](#)
- [Deactivating and Reactivating the accept-remote-nexthop Statement on page 253](#)

### *Verifying That the Multipath Route with the Indirect Next Hop Is in the Routing Table*

**Purpose** Verify that Device R1 has a route to the 1.1.230.0/23 network.

**Action** From operational mode, enter the **show route 1.1.230.0 extensive** command.

```

user@R1> show route 1.1.230.0 extensive
inet.0: 11 destinations, 13 routes (11 active, 0 holddown, 0 hidden)
Restart Complete
1.1.230.0/23 (2 entries, 1 announced)
TSI:
KRT in-kernel 1.1.230.0/23 -> {indirect(262142)}
Page 0 idx 1 Type 1 val 9168f6c
  Nexthop: 1.1.10.10
  Localpref: 100
  AS path: [65000] 65500 I
  Communities:
Path 1.1.230.0 from 1.1.0.1 Vector len 4. Val: 1
  *BGP   Preference: 170/-101
        Next hop type: Indirect
        Address: 0x90c44d8
        Next-hop reference count: 4
        Source: 1.1.0.1
        Next hop type: Router, Next hop index: 262143
        Next hop: 1.1.0.1 via fe-1/2/0.3, selected
        Next hop: 1.1.1.1 via fe-1/2/2.5
        Protocol next hop: 1.1.10.10
        Indirect next hop: 91c0000 262142
        State: <Active Ext>
        Local AS: 65000 Peer AS: 65500
        Age: 2:55:31 Metric2: 0
        Task: BGP_65500.1.1.0.1+64631
        Announcement bits (3): 2-KRT 3-BGP_RT_Background 4-Resolve tree
1
        AS path: 65500 I
        Accepted Multipath
        Localpref: 100
        Router ID: 10.255.14.179
        Indirect next hops: 1
          Protocol next hop: 1.1.10.10
          Indirect next hop: 91c0000 262142
          Indirect path forwarding next hops: 2
            Next hop type: Router
            Next hop: 1.1.0.1 via fe-1/2/0.3
            Next hop: 1.1.1.1 via fe-1/2/2.5
          1.1.10.10/32 Originating RIB: inet.0
            Node path count: 1
            Forwarding nexthops: 2
              Nexthop: 1.1.0.1 via fe-1/2/0.3
              Nexthop: 1.1.1.1 via fe-1/2/2.5
  BGP   Preference: 170/-101

```

```

Next hop type: Indirect
Address: 0x90c44d8
Next-hop reference count: 4
Source: 1.1.1.1
Next hop type: Router, Next hop index: 262143
Next hop: 1.1.0.1 via fe-1/2/0.3, selected
Next hop: 1.1.1.1 via fe-1/2/2.5
Protocol next hop: 1.1.10.10
Indirect next hop: 91c0000 262142
State: <NotBest Ext>
Inactive reason: Not Best in its group - Update source
Local AS: 65500 Peer AS: 65500
Age: 2:55:27 Metric2: 0
Task: BGP_65500.1.1.1+53260
AS path: 65500 I
Accepted
Localpref: 100
Router ID: 10.255.14.179
Indirect next hops: 1
  Protocol next hop: 1.1.10.10
  Indirect next hop: 91c0000 262142
  Indirect path forwarding next hops: 2
    Next hop type: Router
    Next hop: 1.1.0.1 via fe-1/2/0.3
    Next hop: 1.1.1.1 via fe-1/2/2.5
  1.1.10.10/32 Originating RIB: inet.0
  Node path count: 1
  Forwarding nexthops: 2
    Nexthop: 1.1.0.1 via fe-1/2/0.3
    Nexthop: 1.1.1.1 via fe-1/2/2.5

```

**Meaning** The output shows that Device R1 has a route to the 1.1.230.0 network with the multipath feature enabled (**Accepted Multipath**). The output also shows that the route has an indirect next hop of 1.1.10.10.

### *Deactivating and Reactivating the accept-remote-nexthop Statement*

**Purpose** Make sure that the multipath route with the indirect next hop is removed from the routing table when you deactivate the **accept-remote-nexthop** statement.

**Action** 1. From configuration mode, enter the **deactivate protocols bgp accept-remote-nexthop** command.

```

user@R1# deactivate protocols bgp accept-remote-nexthop
user@R1# commit

```

2. From operational mode, enter the **show route 1.1.230.0** command.

```

user@R1> show route 1.1.230.0

```

3. From configuration mode, reactivate the statement by entering the **activate protocols bgp accept-remote-nexthop** command.

```

user@R1# activate protocols bgp accept-remote-nexthop
user@R1# commit

```

4. From operational mode, reenter the **show route 1.1.230.0** command.

```

user@R1> show route 1.1.230.0

```

```

inet.0: 11 destinations, 13 routes (11 active, 0 holddown, 0 hidden)

```

**Restart Complete**

+ = Active Route, - = Last Active, \* = Both

```

1.1.230.0/23      *[BGP/170] 03:13:19, localpref 100
                   AS path: 65500 I
                   > to 1.1.0.1 via fe-1/2/0.3
                   to 1.1.1.1 via fe-1/2/2.5
[BGP/170] 03:13:15, localpref 100, from 1.1.1.1
AS path: 65500 I
> to 1.1.0.1 via fe-1/2/0.3
to 1.1.1.1 via fe-1/2/2.5

```

**Meaning** When the **accept-remote-nexthop** statement is deactivated, the multipath route to the 1.1.230.0 network is removed from the routing table .

- Related Documentation**
- *Example: Overriding the Default BGP Routing Policy on PTX Series Packet Transport Routers*
  - *Example: Load Balancing BGP Traffic with Unequal Bandwidth Allocated to the Paths*

## Example: Advertising Multiple BGP Paths to a Destination

- [Understanding the Advertisement of Multiple Paths to a Single Destination in BGP on page 254](#)

### Understanding the Advertisement of Multiple Paths to a Single Destination in BGP

BGP peers advertise routes to each other in update messages. BGP stores its routes in the Junos OS routing table (**inet.0**). For each prefix in the routing table, the routing protocol process selects a single best path, called the active path. Unless you configure BGP to advertise multiple paths to the same destination, BGP advertises only the active path.

Instead of advertising only the active path to a destination, you can configure BGP to advertise multiple paths to the destination. Within an autonomous system (AS), the availability of multiple exit points to reach a destination provides the following benefits:

- **Fault tolerance**—Path diversity leads to reduction in restoration time after failure. For instance, a border after receiving multiple paths to the same destination can precompute a backup path and have it ready so that when the primary path becomes invalid, the border routing device can use the backup to quickly restore connectivity. Without a backup path, the restoration time depends on BGP reconvergence, which includes withdraw and advertisement messages in the network before a new best path can be learned.
- **Load balancing**—The availability of multiple paths to reach the same destination enables load balancing of traffic, if the routing within the AS meets certain constraints.
- **Maintenance**—The availability of alternate exit points allows for graceful maintenance operation of routers.

The following limitations apply to advertising multiple routes in BGP:

- Address families supported:



- IPv4 unicast (**family inet unicast**)
- IPv6 unicast (**family inet6 unicast**)
- IPv4 labeled unicast (**family inet labeled-unicast**)
- IPv6 labeled unicast (**family inet6 labeled-unicast**)
- Internal BGP (IBGP) peers only. No support on external BGP (EBGP) peers.
- Master instance only. No support for routing instances.
- Graceful restart and nonstop active routing (NSR) are supported.
- No BGP Monitoring Protocol (BMP) support.
- No support for EBGP sessions between confederations.
- Prefix policies enable you to filter routes on a router that is configured to advertise multiple paths to a destination. Prefix policies can only match prefixes. They cannot match route attributes, and they cannot change the attributes of routes.

**Related  
Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

## Example: Advertising Multiple Paths in BGP

In this example, BGP routers are configured to advertise multiple paths instead of advertising only the active path. Advertising multiple paths in BGP is specified in Internet draft draft-ietf-idr-add-paths-04, *Advertisement of Multiple Paths in BGP*.

- [Requirements on page 255](#)
- [Overview on page 256](#)
- [Configuration on page 257](#)
- [Verification on page 275](#)

## Requirements

This example uses the following hardware and software components:

- Eight BGP-enabled devices.
- Five of the BGP-enabled devices do not necessarily need to be routers. For example, they can be EX Series Ethernet Switches.
- Three of the BGP-enabled devices are configured to send multiple paths or receive multiple paths (or both send and receive multiple paths). These three BGP-enabled devices must be M Series Multiservice Edge Routers, MX Series 3D Universal Edge Routers, or T Series Core Routers.
- The three routers must be running Junos OS Release 11.4 or later.

## Overview

The following statements are used for configuring multiple paths to a destination:

```
[edit protocols bgp group group-name family family]  
add-path {  
  receive;  
  send {  
    path-count number;  
    prefix-policy [ policy-names ];  
  }  
}
```

In this example, Router R5, Router R6, and Router R7 redistribute static routes into BGP. Router R1 and Router R4 are route reflectors. Router R2 and Router R3 are clients to Route Reflector R1. Router R8 is a client to Route Reflector R4.

Route reflection is optional when multiple-path advertisement is enabled in BGP.

With the **add-path send path-count 6** configuration, Router R1 is configured to send up to six paths (per destination) to Router R4.

With the **add-path receive** configuration, Router R4 is configured to receive multiple paths from Router R1.

With the **add-path send path-count 6** configuration, Router R4 is configured to send up to six paths to Router R8.

With the **add-path receive** configuration, Router R8 is configured to receive multiple paths from Router R4.


The **add-path send prefix-policy allow\_199** policy configuration (along with the corresponding route filter) limits Router R4 to sending multiple paths for only the 172.16.199.1/32 route.

---

### Topology Diagram

Figure 26 on page 257 shows the topology used in this example.

Figure 26: Advertisement of Multiple Paths in BGP



## Configuration

- [Configuring Router R1 on page 260](#)
- [Configuring Router R2 on page 262](#)
- [Configuring Router R3 on page 264](#)
- [Configuring Router R4 on page 266](#)
- [Configuring Router R5 on page 269](#)
- [Configuring Router R6 on page 271](#)
- [Configuring Router R7 on page 272](#)
- [Configuring Router R8 on page 274](#)
- [Results on page 274](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
Router R1
set interfaces fe-0/0/0 unit 12 family inet address 10.0.12.1/24
set interfaces fe-0/0/1 unit 13 family inet address 10.0.13.1/24
set interfaces fe-1/0/0 unit 14 family inet address 10.0.14.1/24
set interfaces fe-1/2/0 unit 15 family inet address 10.0.15.1/24
set interfaces lo0 unit 10 family inet address 10.0.0.10/32
set protocols bgp group rr type internal
set protocols bgp group rr local-address 10.0.0.10
set protocols bgp group rr cluster 10.0.0.10
set protocols bgp group rr neighbor 10.0.0.20
set protocols bgp group rr neighbor 10.0.0.30
set protocols bgp group e1 type external
set protocols bgp group e1 neighbor 10.0.15.2 local-address 10.0.15.1
set protocols bgp group e1 neighbor 10.0.15.2 peer-as 2
set protocols bgp group rr_rr type internal
set protocols bgp group rr_rr local-address 10.0.0.10
```

```
set protocols bgp group rr_rr neighbor 10.0.0.40 family inet unicast add-path send
  path-count 6
set protocols ospf area 0.0.0.0 interface lo0.10 passive
set protocols ospf area 0.0.0.0 interface fe-0/0/0.12
set protocols ospf area 0.0.0.0 interface fe-0/0/1.13
set protocols ospf area 0.0.0.0 interface fe-1/0/0.14
set protocols ospf area 0.0.0.0 interface fe-1/2/0.15
set routing-options router-id 10.0.0.10
set routing-options autonomous-system 1
```

Router R2

```
set interfaces fe-1/2/0 unit 21 family inet address 10.0.12.2/24
set interfaces fe-1/2/1 unit 26 family inet address 10.0.26.1/24
set interfaces lo0 unit 20 family inet address 10.0.0.20/32
set protocols bgp group rr type internal
set protocols bgp group rr local-address 10.0.0.20
set protocols bgp group rr neighbor 10.0.0.10 export set_nh_self
set protocols bgp group e1 type external
set protocols bgp group e1 neighbor 10.0.26.2 peer-as 2
set protocols ospf area 0.0.0.0 interface lo0.20 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.21
set protocols ospf area 0.0.0.0 interface fe-1/2/1.28
set policy-options policy-statement set_nh_self then next-hop self
set routing-options autonomous-system 1
```

Router R3

```
set interfaces fe-1/0/1 unit 31 family inet address 10.0.13.2/24
set interfaces fe-1/0/2 unit 37 family inet address 10.0.37.1/24
set interfaces lo0 unit 30 family inet address 10.0.0.30/32
set protocols bgp group rr type internal
set protocols bgp group rr local-address 10.0.0.30
set protocols bgp group rr neighbor 10.0.0.10 export set_nh_self
set protocols bgp group e1 type external
set protocols bgp group e1 neighbor 10.0.37.2 peer-as 2
set protocols ospf area 0.0.0.0 interface lo0.30 passive
set protocols ospf area 0.0.0.0 interface fe-1/0/1.31
set protocols ospf area 0.0.0.0 interface fe-1/0/2.37
set policy-options policy-statement set_nh_self then next-hop self
set routing-options autonomous-system 1
```

Router R4

```
set interfaces fe-1/2/0 unit 41 family inet address 10.0.14.2/24
set interfaces fe-1/2/1 unit 48 family inet address 10.0.48.1/24
set interfaces lo0 unit 40 family inet address 10.0.0.40/32
set protocols bgp group rr type internal
set protocols bgp group rr local-address 10.0.0.40
set protocols bgp group rr family inet unicast add-path receive
set protocols bgp group rr neighbor 10.0.0.10
set protocols bgp group rr_client type internal
set protocols bgp group rr_client local-address 10.0.0.40
set protocols bgp group rr_client cluster 10.0.0.40
set protocols bgp group rr_client neighbor 10.0.0.80 family inet unicast add-path send
  path-count 6
set protocols bgp group rr_client neighbor 10.0.0.80 family inet unicast add-path send
  prefix-policy allow_199
set protocols ospf area 0.0.0.0 interface fe-1/2/0.41
set protocols ospf area 0.0.0.0 interface lo0.40 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/1.48
```

```

set policy-options policy-statement allow_199 from route-filter 172.16.199.1/32 exact
set policy-options policy-statement allow_199 term match_199 from prefix-list match_199
set policy-options policy-statement allow_199 then add-path send-count 20
set policy-options policy-statement allow_199 then accept
set routing-options autonomous-system 1

```

**Router R5**

```

set interfaces fe-1/2/0 unit 51 family inet address 10.0.15.2/24
set interfaces lo0 unit 50 family inet address 10.0.0.50/32
set protocols bgp group e1 type external
set protocols bgp group e1 neighbor 10.0.15.1 export s2b
set protocols bgp group e1 neighbor 10.0.15.1 peer-as 1
set policy-options policy-statement s2b from protocol static
set policy-options policy-statement s2b from protocol direct
set policy-options policy-statement s2b then as-path-expand 2
set policy-options policy-statement s2b then accept
set routing-options autonomous-system 2
set routing-options static route 172.16.199.1/32 reject
set routing-options static route 172.16.198.1/32 reject

```

**Router R6**

```

set interfaces fe-1/2/0 unit 62 family inet address 10.0.26.2/24
set interfaces lo0 unit 60 family inet address 10.0.0.60/32
set protocols bgp group e1 type external
set protocols bgp group e1 neighbor 10.0.26.1 export s2b
set protocols bgp group e1 neighbor 10.0.26.1 peer-as 1
set policy-options policy-statement s2b from protocol static
set policy-options policy-statement s2b from protocol direct
set policy-options policy-statement s2b then accept
set routing-options autonomous-system 2
set routing-options static route 172.16.199.1/32 reject
set routing-options static route 172.16.198.1/32 reject

```

**Router R7**

```

set interfaces fe-1/2/0 unit 73 family inet address 10.0.37.2/24
set interfaces lo0 unit 70 family inet address 10.0.0.70/32
set protocols bgp group e1 type external
set protocols bgp group e1 neighbor 10.0.37.1 export s2b
set protocols bgp group e1 neighbor 10.0.37.1 peer-as 1
set policy-options policy-statement s2b from protocol static
set policy-options policy-statement s2b from protocol direct
set policy-options policy-statement s2b then accept
set routing-options autonomous-system 2
set routing-options static route 172.16.199.1/32 reject

```

**Router R8**

```

set interfaces fe-1/2/0 unit 84 family inet address 10.0.48.2/24
set interfaces lo0 unit 80 family inet address 10.0.0.80/32
set protocols bgp group rr type internal
set protocols bgp group rr local-address 10.0.0.80
set protocols bgp group rr neighbor 10.0.0.40 family inet unicast add-path receive
set protocols ospf area 0.0.0.0 interface lo0.80 passive
set protocols ospf area 0.0.0.0 interface fe-1/2/0.84
set routing-options autonomous-system 1

```

### Configuring Router R1

---

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Router R1:

1. Configure the interfaces to Router R2, Router R3, Router R4, and Router R5, and configure the loopback (lo0) interface.

```
[edit interfaces]
user@R1# set fe-0/0/0 unit 12 family inet address 10.0.12.1/24

user@R1# set fe-0/0/1 unit 13 family inet address 10.0.13.1/24

user@R1# set fe-1/0/0 unit 14 family inet address 10.0.14.1/24

user@R1# set fe-1/2/0 unit 15 family inet address 10.0.15.1/24

user@R1# set lo0 unit 10 family inet address 10.0.0.10/32
```

2. Configure BGP on the interfaces, and configure IBGP route reflection.

```
[edit protocols bgp]
user@R1# set group rr type internal
user@R1# set group rr local-address 10.0.0.10
user@R1# set group rr cluster 10.0.0.10
user@R1# set group rr neighbor 10.0.0.20
user@R1# set group rr neighbor 10.0.0.30

user@R1# set group rr_rr type internal
user@R1# set group rr_rr local-address 10.0.0.10

user@R1# set group e1 type external
user@R1# set group e1 neighbor 10.0.15.2 local-address 10.0.15.1
user@R1# set group e1 neighbor 10.0.15.2 peer-as 2
```

3. Configure Router R1 to send up to six paths to its neighbor, Router R4.

The destination of the paths can be any destination that Router R1 can reach through multiple paths.

```
[edit protocols bgp]
user@R1# set group rr_rr neighbor 10.0.0.40 family inet unicast add-path send
path-count 6
```

4. Configure OSPF on the interfaces.

```
[edit protocols ospf]
user@R1# set area 0.0.0.0 interface lo0.10 passive
user@R1# set area 0.0.0.0 interface fe-0/0/0.12
user@R1# set area 0.0.0.0 interface fe-0/0/1.13
user@R1# set area 0.0.0.0 interface fe-1/0/0.14
user@R1# set area 0.0.0.0 interface fe-1/2/0.15
```

5. Configure the router ID and the autonomous system number.

```
[edit routing-options]
user@R1# set router-id 10.0.0.10
user@R1# set autonomous-system 1
```

6. If you are done configuring the device, commit the configuration.

```
user@R1# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show interfaces
fe-0/0/0 {
  unit 12 {
    family inet {
      address 10.0.12.1/24;
    }
  }
}
fe-0/0/1 {
  unit 13 {
    family inet {
      address 10.0.13.1/24;
    }
  }
}
fe-1/0/0 {
  unit 14 {
    family inet {
      address 10.0.14.1/24;
    }
  }
}
fe-1/2/0 {
  unit 15 {
    family inet {
      address 10.0.15.1/24;
    }
  }
}
lo0 {
  unit 10 {
    family inet {
      address 10.0.0.10/32;
    }
  }
}

user@R1# show protocols
bgp {
  group rr {
    type internal;
```

```

local-address 10.0.0.10;
cluster 10.0.0.10;
neighbor 10.0.0.20;
neighbor 10.0.0.30;
}
group el {
    type external;
    neighbor 10.0.15.2 {
        local-address 10.0.15.1;
        peer-as 2;
    }
}
group rr_rr {
    type internal;
    local-address 10.0.0.10;
    neighbor 10.0.0.40 {
        family inet {
            unicast {
                add-path {
                    send {
                        path-count 6;
                    }
                }
            }
        }
    }
}
}
}
}
}
}
}
}
ospf {
    area 0.0.0.0 {
        interface lo0.10 {
            passive;
        }
        interface fe-0/0/0.12;
        interface fe-0/0/1.13;
        interface fe-1/0/0.14;
        interface fe-1/2/0.15;
    }
}
}
}
user@R1# show routing-options
router-id 10.0.0.10;
autonomous-system 1;

```

## Configuring Router R2

### Step-by-Step Procedure

To configure Router R2:

1. Configure the loopback (lo0) interface and the interfaces to Router R6 and Router R1.

[edit interfaces]

```
user@R2# set fe-1/2/0 unit 21 family inet address 10.0.12.2/24
```

```
user@R2# set fe-1/2/1 unit 26 family inet address 10.0.26.1/24
```



```
user@R2# set lo0 unit 20 family inet address 10.0.0.20/32
```

2. Configure BGP and OSPF on Router R2's interfaces.

```
[edit protocols]
user@R2# set bgp group rr type internal
user@R2# set bgp group rr local-address 10.0.0.20
```

```
user@R2# set bgp group e1 type external
user@R2# set bgp group e1 neighbor 10.0.26.2 peer-as 2
```

```
user@R2# set ospf area 0.0.0.0 interface lo0.20 passive
user@R2# set ospf area 0.0.0.0 interface fe-1/2/0.21
user@R2# set ospf area 0.0.0.0 interface fe-1/2/1.28
```

3. For routes sent from Router R2 to Router R1, advertise Router R2 as the next hop, because Router R1 does not have a route to Router R6's address on the 10.0.26.0/24 network.

```
[edit]
user@R2# set policy-options policy-statement set_nh_self then next-hop self
```

```
user@R2# set protocols bgp group rr neighbor 10.0.0.10 export set_nh_self
```

4. Configure the autonomous system number.

```
[edit]
user@R2# set routing-options autonomous-system 1
```

5. If you are done configuring the device, commit the configuration.

```
user@R2# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
fe-1/2/0 {
  unit 21 {
    family inet {
      address 10.0.12.2/24;
    }
  }
}
fe-1/2/1 {
  unit 26 {
    family inet {
      address 10.0.26.1/24;
    }
  }
}
lo0 {
  unit 20 {
    family inet {
```

```

        address 10.0.0.20/32;
    }
}
}

user@R2# show protocols
bgp {
    group rr {
        type internal;
        local-address 10.0.0.20;
        neighbor 10.0.0.10 {
            export set_nh_self;
        }
    }
    group e1 {
        type external;
        neighbor 10.0.26.2 {
            peer-as 2;
        }
    }
}

ospf {
    area 0.0.0.0 {
        interface lo0.20 {
            passive;
        }
        interface fe-1/2/0.21;
        interface fe-1/2/1.28;
    }
}

user@R2# show policy-options
policy-statement set_nh_self {
    then {
        next-hop self;
    }
}

user@R2# show routing-options
autonomous-system 1;

```

### Configuring Router R3

#### Step-by-Step Procedure

To configure Router R3:

1. Configure the loopback (lo0) interface and the interfaces to Router R7 and Router R1.

```
[edit interfaces]
```

```
user@R3# set fe-1/0/1 unit 31 family inet address 10.0.13.2/24
```

```
user@R3# set fe-1/0/2 unit 37 family inet address 10.0.37.1/24
```

```
user@R3# set lo0 unit 30 family inet address 10.0.0.30/32
```

2. Configure BGP and OSPF on Router R3's interfaces.

```
[edit protocols]
user@R3# set bgp group rr type internal
user@R3# set bgp group rr local-address 10.0.0.30

user@R3# set bgp group e1 type external
user@R3# set bgp group e1 neighbor 10.0.37.2 peer-as 2

user@R3# set ospf area 0.0.0.0 interface lo0.30 passive
user@R3# set ospf area 0.0.0.0 interface fe-1/0/1.31
user@R3# set ospf area 0.0.0.0 interface fe-1/0/2.37
```

3. For routes sent from Router R3 to Router R1, advertise Router R3 as the next hop, because Router R1 does not have a route to Router R7's address on the 10.0.37.0/24 network.

```
[edit]
user@R3# set policy-options policy-statement set_nh_self then next-hop self

user@R3# set protocols bgp group rr neighbor 10.0.0.10 export set_nh_self
```

4. Configure the autonomous system number.

```
[edit]
user@R3# set routing-options autonomous-system 1
```

5. If you are done configuring the device, commit the configuration.

```
user@R3# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R3# show interfaces
fe-1/0/1 {
  unit 31 {
    family inet {
      address 10.0.13.2/24;
    }
  }
}
fe-1/0/2 {
  unit 37 {
    family inet {
      address 10.0.37.1/24;
    }
  }
}
lo0 {
  unit 30 {
    family inet {
      address 10.0.0.30/32;
    }
  }
}
```

```

    }
  }
}
user@R3# show protocols
bgp {
  group rr {
    type internal;
    local-address 10.0.0.30;
    neighbor 10.0.0.10 {
      export set_nh_self;
    }
  }
  group e1 {
    type external;
    neighbor 10.0.37.2 {
      peer-as 2;
    }
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.30 {
      passive;
    }
    interface fe-1/0/1.31;
    interface fe-1/0/2.37;
  }
}
user@R3# show policy-options
policy-statement set_nh_self {
  then {
    next-hop self;
  }
}
user@R3# show routing-options
autonomous-system 1;

```

### Configuring Router R4

#### Step-by-Step Procedure

To configure Router R4:

1. Configure the interfaces to Router R1 and Router R8, and configure the loopback (lo0) interface.

[edit interfaces]

```
user@R4# set fe-1/2/0 unit 41 family inet address 10.0.14.2/24
```

```
user@R4# set fe-1/2/1 unit 48 family inet address 10.0.48.1/24
```

```
user@R4# set lo0 unit 40 family inet address 10.0.0.40/32
```

2. Configure BGP on the interfaces, and configure IBGP route reflection.

[edit protocols bgp]

```

user@R4# set group rr type internal
user@R4# set group rr local-address 10.0.0.40
user@R4# set group rr neighbor 10.0.0.10

```

```

user@R4# set group rr_client type internal
user@R4# set group rr_client local-address 10.0.0.40
user@R4# set group rr_client cluster 10.0.0.40

```

3. Configure Router R4 to send up to six paths to its neighbor, Router R8.

The destination of the paths can be any destination that Router R4 can reach through multiple paths.

```

[edit protocols bgp]
user@R4# set group rr_client neighbor 10.0.0.80 family inet unicast add-path send
path-count 6

```

4. Configure Router R4 to receive multiple paths from its neighbor, Router R1.

The destination of the paths can be any destination that Router R1 can reach through multiple paths.

```

[edit protocols bgp group rr family inet unicast]
user@R4# set add-path receive

```

5. Configure OSPF on the interfaces.

```

[edit protocols ospf area 0.0.0.0]
user@R4# set interface fe-1/2/0.41
user@R4# set interface lo0.40 passive
user@R4# set interface fe-1/2/1.48

```

6. Configure a policy that allows Router R4 to send Router R8 multiple paths to the 172.16.199.1/32 route.

- Router R4 receives multiple paths for the 172.16.198.1/32 route and the 172.16.199.1/32 route. However, because of this policy, Router R4 only sends multiple paths for the 172.16.199.1/32 route.

```

[edit protocols bgp group rr_client neighbor 10.0.0.80 family inet unicast]
user@R4# set add-path send prefix-policy allow_199
[edit policy-options policy-statement allow_199]
user@R4# set from route-filter 172.16.199.1/32 exact
user@R4# set then accept

```

- Router R4 can also be configured to send up-to 20 BGP **add-path** routes for a subset of *add-path advertised prefixes*.

```

[edit policy-options policy-statement allow_199]
user@R4# set term match_199 from prefix-list match_199
user@R4# set then add-path send-count 20

```

7. Configure the autonomous system number.

```

[edit routing-options]
user@R4# set autonomous-system 1

```

8. If you are done configuring the device, commit the configuration.

```

user@R4# commit

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R4# show interfaces
fe-1/2/0 {
  unit 41 {
    family inet {
      address 10.0.14.2/24;
    }
  }
}
fe-1/2/1 {
  unit 48 {
    family inet {
      address 10.0.48.1/24;
    }
  }
}
lo0 {
  unit 40 {
    family inet {
      address 10.0.0.40/32;
    }
  }
}

user@R4# show protocols
bgp {
  group rr {
    type internal;
    local-address 10.0.0.40;
    family inet {
      unicast {
        add-path {
          receive;
        }
      }
    }
  }
  neighbor 10.0.0.10;
}
group rr_client {
  type internal;
  local-address 10.0.0.40;
  cluster 10.0.0.40;
  neighbor 10.0.0.80 {
    family inet {
      unicast {
        add-path {
          send {
            path-count 6;
            prefix-policy allow_199;
          }
        }
      }
    }
  }
}
```

```

    }
  }
}
ospf {
  area 0.0.0.0 {
    interface lo0.40 {
      passive;
    }
    interface fe-1/2/0.41;
    interface fe-1/2/1.48;
  }
}

user@R4# show policy-options
policy-statement allow_199 {
  from {
    route-filter 172.16.199.1/32 exact;
  }
  from term match_199 {
    prefix-list match_199;
  }
  then add-path send-count 20;
  then accept;
}

user@R4# show routing-options
autonomous-system 1;

```

### Configuring Router R5

#### Step-by-Step Procedure

To configure Router R5:

1. Configure the loopback (lo0) interface and the interface to Router R1.

```

[edit interfaces]
user@R5# set fe-1/2/0 unit 51 family inet address 10.0.15.2/24

user@R5# set lo0 unit 50 family inet address 10.0.0.50/32

```

2. Configure BGP on Router R5's interface.

```

[edit protocols bgp group e1]
user@R5# set type external
user@R5# set neighbor 10.0.15.1 peer-as 1

```

3. Create static routes for redistribution into BGP.

```

[edit routing-options]
user@R5# set static route 172.16.199.1/32 reject
user@R5# set static route 172.16.198.1/32 reject

```

4. Redistribute static and direct routes into BGP.

```

[edit protocols bgp group e1 neighbor 10.0.15.1]
user@R5# set export s2b

```

```

[edit policy-options policy-statement s2b]

```

```
user@R5# set from protocol static
user@R5# set from protocol direct
user@R5# set then as-path-expand 2
user@R5# set then accept
```

5. Configure the autonomous system number.

```
[edit routing-options]
user@R5# set autonomous-system 2
```

6. If you are done configuring the device, commit the configuration.

```
user@R5# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R5# show interfaces
fe-1/2/0 {
  unit 51 {
    family inet {
      address 10.0.15.2/24;
    }
  }
}
lo0 {
  unit 50 {
    family inet {
      address 10.0.0.50/32;
    }
  }
}

user@R5# show protocols
bgp {
  group e1 {
    type external;
    neighbor 10.0.15.1 {
      export s2b;
      peer-as 1;
    }
  }
}

user@R5# show policy-options
policy-statement s2b {
  from protocol [ static direct ];
  then {
    as-path-expand 2;
    accept;
  }
}

user@R5# show routing-options
static {
```



```

route 172.16.198.1/32 reject;
route 172.16.199.1/32 reject;
}
autonomous-system 2;

```

### Configuring Router R6

#### Step-by-Step Procedure

To configure Router R6:

1. Configure the loopback (lo0) interface and the interface to Router R2.  
  

```

[edit interfaces]
user@R6# set fe-1/2/0 unit 62 family inet address 10.0.26.2/24

user@R6# set lo0 unit 60 family inet address 10.0.0.60/32

```
2. Configure BGP on Router R6's interface.  
  

```

[edit protocols]
user@R6# set bgp group e1 type external
user@R6# set bgp group e1 neighbor 10.0.26.1 peer-as 1

```
3. Create static routes for redistribution into BGP.  
  

```

[edit]
user@R6# set routing-options static route 172.16.199.1/32 reject
user@R6# set routing-options static route 172.16.198.1/32 reject

```
4. Redistribute static and direct routes from Router R6's routing table into BGP.  
  

```

[edit protocols bgp group e1 neighbor 10.0.26.1]
user@R6# set export s2b

[edit policy-options policy-statement s2b]
user@R6# set from protocol static
user@R6# set from protocol direct
user@R6# set then accept

```
5. Configure the autonomous system number.  
  

```

[edit routing-options]
user@R6# set autonomous-system 2

```
6. If you are done configuring the device, commit the configuration.  
  

```

user@R6# commit

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R6# show interfaces
fe-1/2/0 {
  unit 62 {
    family inet {
      address 10.0.26.2/24;

```

```

    }
  }
}
lo0 {
  unit 60 {
    family inet {
      address 10.0.0.60/32;
    }
  }
}

user@R6# show protocols
bgp {
  group e1 {
    type external;
    neighbor 10.0.26.1 {
      export s2b;
      peer-as 1;
    }
  }
}

user@R6# show policy-options
policy-statement s2b {
  from protocol [ static direct ];
  then accept;
}

user@R6# show routing-options
static {
  route 172.16.198.1/32 reject;
  route 172.16.199.1/32 reject;
}
autonomous-system 2;

```

### Configuring Router R7

#### Step-by-Step Procedure

To configure Router R7:

1. Configure the loopback (lo0) interface and the interface to Router R3.

```

[edit interfaces]
user@R7# set fe-1/2/0 unit 73 family inet address 10.0.37.2/24

```

```

user@R7# set lo0 unit 70 family inet address 10.0.0.70/32

```

2. Configure BGP on Router R7's interface.

```

[edit protocols bgp group e1]
user@R7# set type external
user@R7# set neighbor 10.0.37.1 peer-as 1

```

3. Create a static route for redistribution into BGP.

```

[edit]
user@R7# set routing-options static route 172.16.199.1/32 reject

```

4. Redistribute static and direct routes from Router R7's routing table into BGP.

```
[edit protocols bgp group e1 neighbor 10.0.37.1]
user@R7# set export s2b
```

```
[edit policy-options policy-statement s2b]
user@R7# set from protocol static
user@R7# set from protocol direct
user@R7# set then accept
```

5. Configure the autonomous system number.

```
[edit routing-options]
user@R7# set autonomous-system 2
```

6. If you are done configuring the device, commit the configuration.

```
user@R7# commit
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R7# show interfaces
fe-1/2/0 {
  unit 73 {
    family inet {
      address 10.0.37.2/24;
    }
  }
}
lo0 {
  unit 70 {
    family inet {
      address 10.0.0.70/32;
    }
  }
}
```

```
user@R7# show protocols
bgp {
  group e1 {
    type external;
    neighbor 10.0.37.1 {
      export s2b;
      peer-as 1;
    }
  }
}
```

```
user@R7# show policy-options
policy-statement s2b {
  from protocol [ static direct ];
  then accept;
}
```

```
user@R7# show routing-options
static {
    route 172.16.199.1/32 reject;
}
autonomous-system 2;
```

---

### Configuring Router R8

---

#### Step-by-Step Procedure

To configure Router R8:

1. Configure the loopback (lo0) interface and the interface to Router R4.

```
[edit interfaces]
user@R8# set fe-1/2/0 unit 84 family inet address 10.0.48.2/24

user@R8# set lo0 unit 80 family inet address 10.0.0.80/32
```

2. Configure BGP and OSPF on Router R8's interface.

```
[edit protocols]
user@R8# set bgp group rr type internal
user@R8# set bgp group rr local-address 10.0.0.80

user@R8# set ospf area 0.0.0.0 interface lo0.80 passive
user@R8# set ospf area 0.0.0.0 interface fe-1/2/0.84
```

3. Configure Router R8 to receive multiple paths from its neighbor, Router R4.

The destination of the paths can be any destination that Router R4 can reach through multiple paths.

```
[edit protocols]
user@R8# set bgp group rr neighbor 10.0.0.40 family inet unicast add-path receive
```

4. Configure the autonomous system number.

```
[edit]
user@R8# set routing-options autonomous-system 1
```

5. If you are done configuring the device, commit the configuration.

```
user@R8# commit
```

---

### Results

---

From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R8# show interfaces
fe-1/2/0 {
    unit 84 {
        family inet {
            address 10.0.48.2/24;
        }
    }
}
```

```

    }
  }
  lo0 {
    unit 80 {
      family inet {
        address 10.0.0.80/32;
      }
    }
  }
}

user@R8# show protocols
bgp {
  group rr {
    type internal;
    local-address 10.0.0.80;
    neighbor 10.0.0.40 {
      family inet {
        unicast {
          add-path {
            receive;
          }
        }
      }
    }
  }
}
}
}
}
ospf {
  area 0.0.0.0 {
    interface lo0.80 {
      passive;
    }
    interface fe-1/2/0.84;
  }
}
}

user@R8# show routing-options
autonomous-system 1;

```

## Verification

Confirm that the configuration is working properly.

- Verifying That the BGP Peers Have the Ability to Send and Receive Multiple Paths on page 276
- Verifying That Router R1 Is Advertising Multiple Paths on page 276
- Verifying That Router R4 Is Receiving and Advertising Multiple Paths on page 277
- Verifying That Router R8 Is Receiving Multiple Paths on page 278
- Checking the Path ID on page 278

### Verifying That the BGP Peers Have the Ability to Send and Receive Multiple Paths

**Purpose** Make sure that one or both of the following strings appear in the output of the **show bgp neighbor** command:

- NLRI's for which peer can receive multiple paths: inet-unicast
- NLRI's for which peer can send multiple paths: inet-unicast

**Action**

```
user@R1> show bgp neighbor 10.0.0.40
Peer: 10.0.0.40+179 AS 1      Local: 10.0.0.10+64227 AS 1
  Type: Internal   State: Established   Flags: <Sync>
... NLRI's for which peer can receive multiple paths: inet-unicast
...

user@R4> show bgp neighbor 10.0.0.10
Peer: 10.0.0.10+64227 AS 1    Local: 10.0.0.40+179 AS 1
  Type: Internal   State: Established   Flags: <Sync>
...
  NLRI's for which peer can send multiple paths: inet-unicast
...

user@R4> show bgp neighbor 10.0.0.80
Peer: 10.0.0.80+55416 AS 1    Local: 10.0.0.40+179 AS 1
  Type: Internal   State: Established (route reflector client)Flags: <Sync>
...
  NLRI's for which peer can receive multiple paths: inet-unicast
...

user@R8> show bgp neighbor 10.0.0.40
Peer: 10.0.0.40+179 AS 1      Local: 10.0.0.80+55416 AS 1
  Type: Internal   State: Established   Flags: <Sync>
...
  NLRI's for which peer can send multiple paths: inet-unicast
...
```

### Verifying That Router R1 Is Advertising Multiple Paths

**Purpose** Make sure that multiple paths to the 172.16.198.1/32 destination and multiple paths to the 172.16.199.1/32 destination are advertised to Router R4.

**Action** user@R1> show route advertising-protocol bgp 10.0.0.40  
 inet.0: 21 destinations, 25 routes (21 active, 0 holddown, 0 hidden)

Prefix	Nexthop	MED	Lc1pref	AS path
* 10.0.0.50/32	10.0.15.2		100	2 2 I
* 10.0.0.60/32	10.0.0.20		100	2 I
* 10.0.0.70/32	10.0.0.30		100	2 I
* 172.16.198.1/32	10.0.0.20		100	2 I
	10.0.15.2		100	2 2 I
* 172.16.199.1/32	10.0.0.20		100	2 I
	10.0.0.30		100	2 I
	10.0.15.2		100	2 2 I
* 172.16.200.0/30	10.0.0.20		100	2 I

**Meaning** When you see one prefix and more than one next hop, it means that multiple paths are advertised to Router R4.

### Verifying That Router R4 Is Receiving and Advertising Multiple Paths

**Purpose** Make sure that multiple paths to the 172.16.199.1/32 destination are received from Router R1 and advertised to Router R8. Make sure that multiple paths to the 172.16.198.1/32 destination are received from Router R1, but only one path to this destination is advertised to Router R8.

**Action** user@R4> show route receive-protocol bgp 10.0.0.10  
 inet.0: 19 destinations, 22 routes (19 active, 0 holddown, 0 hidden)

Prefix	Nexthop	MED	Lc1pref	AS path
* 10.0.0.50/32	10.0.15.2		100	2 2 I
* 10.0.0.60/32	10.0.0.20		100	2 I
* 10.0.0.70/32	10.0.0.30		100	2 I
* 172.16.198.1/32	10.0.0.20		100	2 I
	10.0.15.2		100	2 2 I
* 172.16.199.1/32	10.0.0.20		100	2 I
	10.0.0.30		100	2 I
	10.0.15.2		100	2 2 I
* 172.16.200.0/30	10.0.0.20		100	2 I

user@R4> show route advertising-protocol bgp 10.0.0.80  
 inet.0: 19 destinations, 22 routes (19 active, 0 holddown, 0 hidden)

Prefix	Nexthop	MED	Lc1pref	AS path
* 10.0.0.50/32	10.0.15.2		100	2 2 I
* 10.0.0.60/32	10.0.0.20		100	2 I
* 10.0.0.70/32	10.0.0.30		100	2 I
* 172.16.198.1/32	10.0.0.20		100	2 I
* 172.16.199.1/32	10.0.0.20		100	2 I
	10.0.0.30		100	2 I
	10.0.15.2		100	2 2 I
* 172.16.200.0/30	10.0.0.20		100	2 I

**Meaning** The **show route receive-protocol** command shows that Router R4 receives two paths to the 172.16.198.1/32 destination and three paths to the 172.16.199.1/32 destination. The **show route advertising-protocol** command shows that Router R4 advertises only one

path to the 172.16.198.1/32 destination and advertises all three paths to the 172.16.199.1/32 destination.

Because of the prefix policy that is applied to Router R4, Router R4 does not advertise multiple paths to the 172.16.198.1/32 destination. Router R4 advertises only one path to the 172.16.198.1/32 destination even though it receives multiple paths to this destination.

### Verifying That Router R8 Is Receiving Multiple Paths

**Purpose** Make sure that Router R8 receives multiple paths to the 172.16.199.1/32 destination through Router R4. Make sure that Router R8 receives only one path to the 172.16.198.1/32 destination through Router R4.

**Action** user@R8> show route receive-protocol bgp 10.0.0.40

```
inet.0: 18 destinations, 20 routes (18 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED      Lclpref    AS path
* 10.0.0.50/32          10.0.15.2              100        2 2 I
* 10.0.0.60/32          10.0.0.20             100        2 I
* 10.0.0.70/32          10.0.0.30             100        2 I
* 172.16.198.1/32       10.0.0.20              100        2 I
* 172.16.199.1/32       10.0.0.20              100        2 I
                        10.0.0.30              100        2 I
                        10.0.15.2              100        2 2 I
* 200.1.1.0/30          10.0.0.20              100        2 I
```

### Checking the Path ID

**Purpose** On the downstream devices, Router R4 and Router R8, verify that a path ID uniquely identifies the path. Look for the **Addpath Path ID:** string.



**Action** user@R4> show route 172.16.199.1/32 detail

```
inet.0: 18 destinations, 20 routes (18 active, 0 holddown, 0 hidden)
172.16.199.1/32 (3 entries, 3 announced)
  *BGP
    Preference: 170/-101
    Next hop type: Indirect
    Next-hop reference count: 9
    Source: 10.0.0.10
    Next hop type: Router, Next hop index: 676
    Next hop: 10.0.14.1 via lt-1/2/0.41, selected
    Protocol next hop: 10.0.0.20
    Indirect next hop: 92041c8 262146
    State: <Active Int Ext>
    Local AS: 1 Peer AS: 1
    Age: 1:44:37 Metric2: 2
    Task: BGP_1.10.0.0.10+64227
    Announcement bits (3): 2-KRT 3-BGP RT Background 4-Resolve tree

  1
    AS path: 2 I (Originator) Cluster list: 10.0.0.10
    AS path: Originator ID: 10.0.0.20
    Accepted
    Localpref: 100
    Router ID: 10.0.0.10
    Addpath Path ID: 1
  BGP
    Preference: 170/-101
    Next hop type: Indirect
    Next-hop reference count: 4
    Source: 10.0.0.10
    Next hop type: Router, Next hop index: 676
    Next hop: 10.0.14.1 via lt-1/2/0.41, selected
    Protocol next hop: 10.0.0.30
    Indirect next hop: 92042ac 262151
    State: <NotBest Int Ext>
    Inactive reason: Not Best in its group - Router ID
    Local AS: 1 Peer AS: 1
    Age: 1:44:37 Metric2: 2
    Task: BGP_1.10.0.0.10+64227
    Announcement bits (1): 3-BGP RT Background
    AS path: 2 I (Originator) Cluster list: 10.0.0.10
    AS path: Originator ID: 10.0.0.30
    Accepted
    Localpref: 100
    Router ID: 10.0.0.10
    Addpath Path ID: 2
  BGP
    Preference: 170/-101
    Next hop type: Indirect
    Next-hop reference count: 4
    Source: 10.0.0.10
    Next hop type: Router, Next hop index: 676
    Next hop: 10.0.14.1 via lt-1/2/0.41, selected
    Protocol next hop: 10.0.15.2
    Indirect next hop: 92040e4 262150
    State: <Int Ext>
    Inactive reason: AS path
    Local AS: 1 Peer AS: 1
    Age: 1:44:37 Metric2: 2
    Task: BGP_1.10.0.0.10+64227
    Announcement bits (1): 3-BGP RT Background
    AS path: 2 2 I
    Accepted
```

```

Localpref: 100
Router ID: 10.0.0.10
Addpath Path ID: 3

```

```
user@R8> show route 172.16.199.1/32 detail
```

```

inet.0: 17 destinations, 19 routes (17 active, 0 holddown, 0 hidden)
172.16.199.1/32 (3 entries, 1 announced)
*BGP Preference: 170/-101
  Next hop type: Indirect
  Next-hop reference count: 9
  Source: 10.0.0.40
  Next hop type: Router, Next hop index: 1045
  Next hop: 10.0.48.1 via lt-1/2/0.84, selected
  Protocol next hop: 10.0.0.20
  Indirect next hop: 91fc0e4 262148
  State: <Active Int Ext>
  Local AS: 1 Peer AS: 1
  Age: 1:56:51 Metric2: 3
  Task: BGP_1.10.0.0.40+179
  Announcement bits (2): 2-KRT 4-Resolve tree 1
  AS path: 2 I (Originator) Cluster list: 10.0.0.40 10.0.0.10
  AS path: Originator ID: 10.0.0.20
  Accepted
  Localpref: 100
  Router ID: 10.0.0.40
  Addpath Path ID: 1
BGP Preference: 170/-101
  Next hop type: Indirect
  Next-hop reference count: 4
  Source: 10.0.0.40
  Next hop type: Router, Next hop index: 1045
  Next hop: 10.0.48.1 via lt-1/2/0.84, selected
  Protocol next hop: 10.0.0.30
  Indirect next hop: 91fc1c8 262152
  State: <NotBest Int Ext>
  Inactive reason: Not Best in its group - Router ID
  Local AS: 1 Peer AS: 1
  Age: 1:56:51 Metric2: 3
  Task: BGP_1.10.0.0.40+179
  AS path: 2 I (Originator) Cluster list: 10.0.0.40 10.0.0.10
  AS path: Originator ID: 10.0.0.30
  Accepted
  Localpref: 100
  Router ID: 10.0.0.40
  Addpath Path ID: 2
BGP Preference: 170/-101
  Next hop type: Indirect
  Next-hop reference count: 4
  Source: 10.0.0.40
  Next hop type: Router, Next hop index: 1045
  Next hop: 10.0.48.1 via lt-1/2/0.84, selected
  Protocol next hop: 10.0.15.2
  Indirect next hop: 91fc2ac 262153
  State: <Int Ext>
  Inactive reason: AS path
  Local AS: 1 Peer AS: 1
  Age: 1:56:51 Metric2: 3
  Task: BGP_1.10.0.0.40+179
  AS path: 2 2 I (Originator) Cluster list: 10.0.0.40
  AS path: Originator ID: 10.0.0.10

```

```
Accepted
Localpref: 100
Router ID: 10.0.0.40
Addpath Path ID: 3
```

#### Related Documentation

- [Understanding the Advertisement of Multiple Paths to a Single Destination in BGP on page 9](#)
- [Understanding Adding AS Numbers to BGP AS Paths](#)

## Configuring ECMP Next Hops for RSVP and LDP LSPs for Load Balancing

The Junos OS supports configurations of 16, 32, or 64 equal-cost multipath (ECMP) next hops for RSVP and LDP LSPs on M10i routers with an Enhanced CFEB, M320, M120, MX Series, and T Series routers, and routing devices. For networks with high-volume traffic, this provides more flexibility to load-balance the traffic over as many as 64 LSPs.

To configure the maximum limit for ECMP next hops, include the **maximum-ecmp next-hops** statement at the **[edit chassis]** hierarchy level:

```
[edit chassis]
maximum-ecmp next-hops;
```

You can configure a maximum ECMP next-hop limit of 16, 32, or 64 using this statement. The default limit is 16. On QFX5100 and QFX5110 switches, the default limit is 16.



**NOTE:** MX Series routers with one or more Modular Port Concentrator (MPC) cards and with Junos OS 11.4 or earlier installed, support the configuration of the **maximum-ecmp** statement with only 16 next hops. You should *not* configure the **maximum-ecmp** statement with 32 or 64 next hops. When you commit the configuration with 32 or 64 next hops, the following warning message appears:

**Error: Number of members in Unilist NH exceeds the maximum supported 16 on Trio.**

The following types of routes support the ECMP maximum next-hop configuration for as many as 64 ECMP gateways:

- Static IPv4 and IPv6 routes with direct and indirect next-hop ECMPs
- LDP ingress and transit routes learned through associated IGP routes
- RSVP ECMP next hops created for LSPs
- OSPF IPv4 and IPv6 route ECMPs
- ISIS IPv4 and IPv6 route ECMPs
- EBGp IPv4 and IPv6 route ECMPs
- IBGP (resolving over IGP routes) IPv4 and IPv6 route ECMPs

The enhanced ECMP limit of up to 64 ECMP next hops is also applicable for Layer 3 VPNs, Layer 2 VPNs, Layer 2 circuits, and VPLS services that resolve over an MPLS route, because the available ECMP paths in the MPLS route can also be used by such traffic.



**NOTE:**

The following FPCs on M320, T640, and T1600 routers only support 16 ECMP next hops:

- (M320, T640, and T1600 routers only) Enhanced II FPC1
- (M320, T640, and T1600 routers only) Enhanced II FPC2
- (M320 and T640 routers only) Enhanced II FPC3
- (T640 and T1600 routers only) FPC2
- (T640 and T1600 routers only) FPC3

If a maximum ECMP next-hop limit of 32 or 64 is configured on an M320, T640, or T1600 router with any of these FPCs installed, the Packet Forwarding Engines on these FPCs use only the first 16 ECMP next hops. For Packet Forwarding Engines on FPCs that support only 16 ECMP next hops, the Junos OS generates a system log message if a maximum ECMP next-hop limit of 32 or 64 is configured. However, for Packet Forwarding Engines on other FPCs installed on the router, a maximum configured ECMP limit of 32 or 64 ECMP next hops is applicable.



**NOTE:** If RSVP LSPs are configured with bandwidth allocation, for ECMP next hops with more than 16 LSPs, traffic is not distributed optimally based on bandwidths configured. Some LSPs with smaller allocated bandwidths receive more traffic than the ones configured with higher bandwidths. Traffic distribution does not strictly comply with the configured bandwidth allocation. This caveat is applicable to the following routers:

- T1600 and T640 routers with Enhanced Scaling FPC1, Enhanced Scaling FPC2, Enhanced Scaling FPC3, Enhanced Scaling FPC 4, and all Type 4 FPCs
- M320 routers with Enhanced III FPC1, Enhanced III FPC2, and Enhanced III FPC3
- MX Series routers with all types of FPCs and DPCs, excluding MPCs. This caveat is not applicable to MX Series routers with line cards based on the Junos Trio chipset.
- M120 routers with Type 1, Type 2, and Type 3 FPCs
- M10i routers with Enhanced CFEB

Next-hop cloning and permutations are disabled on T Series routers with Enhanced Scaling FPCs (Enhanced Scaling FPC1, Enhanced Scaling FPC2, Enhanced Scaling FPC3,

and Enhanced Scaling FPC 4) that support enhanced load-balancing capability. As a result, memory utilization is reduced for a highly scaled system with a high number of next hops on ECMP or aggregated interfaces. Next-hop cloning and permutations are also disabled on T Series routers with Type-4 FPCs.

To view the details of the ECMP next hops, issue the **show route** command. The **show route summary command** also shows the current configuration for the maximum ECMP limit. To view details of the ECMP LDP paths, issue the **traceroute mpls ldp** command.

**Related Documentation**

- *maximum-ecmp*



## CHAPTER 7

# IBGP Scaling Configuration

- [Example: Configuring BGP Route Reflectors on page 285](#)
- [Example: Configuring BGP Confederations on page 303](#)

### Example: Configuring BGP Route Reflectors

---

- [Understanding BGP Route Reflectors on page 285](#)
- [Example: Configuring a Route Reflector on page 288](#)

### Understanding BGP Route Reflectors

This topic discusses using route reflectors to simplify configuration and aid in scaling. A further way to reduce the workload on a route reflector that is not in the traffic-forwarding path is to use the **no-install** statement at the **[edit protocols bgp family *family-name*]** hierarchy level. Starting in Junos OS Release 15.1, the **no-install** statement eliminates interaction between the routing protocols daemon (rpd) and other components in the Junos system such as the kernel or the distributed firewall daemon (dfwd). This interaction is eliminated by prohibiting any routes in the associated rpd routing information bases (RIBs), also known as routing tables, from being published to those components.



**NOTE:** In releases previous to Junos OS Release 15.1, you can reduce the workload on a route reflector that is not in the traffic-forwarding path by using a forwarding-table export policy that rejects routes learned from BGP.

Because of the internal BGP (IBGP) full-mesh requirement, most networks use route reflectors to simplify configuration. The formula to compute the number of sessions required for a full mesh is  $v * (v - 1) / 2$ , where  $v$  is the number of BGP-enabled devices. The full-mesh model does not scale well. Using a route reflector, you group routers into clusters, which are identified by numeric identifiers unique to the autonomous system (AS). Within the cluster, you must configure a BGP session from a single router (the route reflector) to each internal peer. With this configuration, the IBGP full-mesh requirement is met.


To use route reflection in an AS, you designate one or more routers as a route reflector—typically, one per point of presence (POP). Route reflectors have the special BGP ability to readvertise routes learned from an internal peer to other internal peers. So rather than requiring all internal peers to be fully meshed with each other, route

reflection requires only that the route reflector be fully meshed with all internal peers. The route reflector and all of its internal peers form a cluster, as shown in [Figure 27 on page 286](#).



**NOTE:** For some Juniper Networks devices, you must have an Advanced BGP Feature license installed on each device that uses a route reflector. For license details, see the *Installation and Upgrade Guide*.

**Figure 27: Simple Route Reflector Topology (One Cluster)**



[Figure 27 on page 286](#) shows Router RR configured as the route reflector for Cluster 127. The other routers are designated internal peers within the cluster. BGP routes are advertised to Router RR by any of the internal peers. RR then readvertises those routes to all other peers within the cluster.

You can configure multiple clusters and link them by configuring a full mesh of route reflectors (see [Figure 28 on page 287](#)).



Figure 28: Basic Route Reflection (Multiple Clusters)




Figure 28 on page 287 shows Route Reflectors RR 1, RR 2, RR 3, and RR 4 as fully meshed internal peers. When a router advertises a route to RR 1, RR 1 readvertises the route to the other route reflectors, which, in turn, readvertise the route to the remaining routers within the AS. Route reflection allows the route to be propagated throughout the AS without the scaling problems created by the full mesh requirement.



**NOTE:** A route reflector that supports multiple clusters does not accept a route with the same cluster ID from a non-client router. Therefore, you must configure a different cluster ID for a redundant RR to reflect the route to other clusters.

However, as clusters become large, a full mesh with a route reflector becomes difficult to scale, as does a full mesh between route reflectors. To help offset this problem, you can group clusters of routers together into clusters of clusters for hierarchical route reflection (see Figure 29 on page 288).

Figure 29: Hierarchical Route Reflection (Clusters of Clusters)




Figure 29 on page 288 shows RR 2, RR 3, and RR 4 as the route reflectors for Clusters 127, 19, and 45, respectively. Rather than fully mesh those route reflectors, the network administrator has configured them as part of another cluster (Cluster 6) for which RR 1 is the route reflector. When a router advertises a route to RR 2, RR 2 readvertises the route to all the routers within its own cluster, and then readvertises the route to RR 1. RR 1 readvertises the route to the routers in its cluster, and those routers propagate the route down through their clusters.

### Example: Configuring a Route Reflector

This example shows how to configure a route reflector.

- [Requirements on page 288](#)
- [Overview on page 288](#)
- [Configuration on page 290](#)
- [Verification on page 298](#)

#### Requirements

No special configuration beyond device initialization is required before you configure this example.

#### Overview

Generally, internal BGP (IBGP)-enabled devices need to be fully meshed, because IBGP does not readvertise updates to other IBGP-enabled devices. The full mesh is a logical mesh achieved through configuration of multiple **neighbor** statements on each IBGP-enabled device. The full mesh is not necessarily a physical full mesh. Maintaining a full mesh (logical or physical) does not scale well in large deployments.

Figure 30 on page 289 shows an IBGP network with Device A acting as a route reflector. Device B and Device C are clients of the route reflector. Device D and Device E are outside the cluster, so they are nonclients of the route reflector.

On Device A (the route reflector), you must form peer relationships with all of the IBGP-enabled devices by including the **neighbor** statement for the clients (Device B and

Device C) and the nonclients (Device D and Device E). You must also include the **cluster** statement and a cluster identifier. The cluster identifier can be any 32-bit value. This example uses the loopback interface IP address of the route reflector.


On Device B and Device C, the route reflector clients, you only need one **neighbor** statement that forms a peer relationship with the route reflector, Device A.

On Device D and Device E, the nonclients, you need a **neighbor** statement for each nonclient device (D-to-E and E-to-D). You also need a **neighbor** statement for the route reflector (D-to-A and E-to-A). Device D and Device E do not need **neighbor** statements for the client devices (Device B and Device C).



**TIP:** Device D and Device E are considered to be nonclients because they have explicitly configured peer relationships with each other. To make them RRroute reflector clients, remove the **neighbor 192.168.5.5** statement from the configuration on Device D, and remove the **neighbor 192.168.0.1** statement from the configuration on Device E.

Figure 30: IBGP Network Using a Route Reflector



## Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device A**

```

set interfaces fe-0/0/0 unit 1 description to-B
set interfaces fe-0/0/0 unit 1 family inet address 10.10.10.1/30
set interfaces fe-0/0/1 unit 3 description to-D
set interfaces fe-0/0/1 unit 3 family inet address 10.10.10.9/30
set interfaces lo0 unit 1 family inet address 192.168.6.5/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.168.6.5
set protocols bgp group internal-peers export send-ospf
set protocols bgp group internal-peers cluster 192.168.6.5
set protocols bgp group internal-peers neighbor 192.163.6.4
set protocols bgp group internal-peers neighbor 192.168.40.4
set protocols bgp group internal-peers neighbor 192.168.0.1
set protocols bgp group internal-peers neighbor 192.168.5.5
set protocols ospf area 0.0.0.0 interface lo0.1 passive
set protocols ospf area 0.0.0.0 interface fe-0/0/0.1
set protocols ospf area 0.0.0.0 interface fe-0/0/1.3
set policy-options policy-statement send-ospf term 2 from protocol ospf
set policy-options policy-statement send-ospf term 2 then accept
set routing-options router-id 192.168.6.5
set routing-options autonomous-system 17

```

**Device B**

```

set interfaces fe-0/0/0 unit 2 description to-A
set interfaces fe-0/0/0 unit 2 family inet address 10.10.10.2/30
set interfaces fe-0/0/1 unit 5 description to-C
set interfaces fe-0/0/1 unit 5 family inet address 10.10.10.5/30
set interfaces lo0 unit 2 family inet address 192.163.6.4/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.163.6.4
set protocols bgp group internal-peers export send-ospf
set protocols bgp group internal-peers neighbor 192.168.6.5
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set protocols ospf area 0.0.0.0 interface fe-0/0/0.2
set protocols ospf area 0.0.0.0 interface fe-0/0/1.5
set policy-options policy-statement send-ospf term 2 from protocol ospf
set policy-options policy-statement send-ospf term 2 then accept
set routing-options router-id 192.163.6.4
set routing-options autonomous-system 17

```

**Device C**

```

set interfaces fe-0/0/0 unit 6 description to-B
set interfaces fe-0/0/0 unit 6 family inet address 10.10.10.6/30
set interfaces lo0 unit 3 family inet address 192.168.40.4/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.168.40.4
set protocols bgp group internal-peers export send-ospf
set protocols bgp group internal-peers neighbor 192.168.6.5
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ospf area 0.0.0.0 interface fe-0/0/0.6
set policy-options policy-statement send-ospf term 2 from protocol ospf

```

```

set policy-options policy-statement send-ospf term 2 then accept
set routing-options router-id 192.168.40.4
set routing-options autonomous-system 17

```

**Device D**

```

set interfaces fe-0/0/0 unit 4 description to-A
set interfaces fe-0/0/0 unit 4 family inet address 10.10.10.10/30
set interfaces fe-0/0/1 unit 7 description to-E
set interfaces fe-0/0/1 unit 7 family inet address 10.10.10.13/30
set interfaces lo0 unit 4 family inet address 192.168.0.1/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.168.0.1
set protocols bgp group internal-peers export send-ospf
set protocols bgp group internal-peers neighbor 192.168.6.5
set protocols bgp group internal-peers neighbor 192.168.5.5
set protocols ospf area 0.0.0.0 interface lo0.4 passive
set protocols ospf area 0.0.0.0 interface fe-0/0/0.4
set protocols ospf area 0.0.0.0 interface fe-0/0/1.7
set policy-options policy-statement send-ospf term 2 from protocol ospf
set policy-options policy-statement send-ospf term 2 then accept
set routing-options router-id 192.168.0.1
set routing-options autonomous-system 17

```

**Device E**

```

set interfaces fe-0/0/0 unit 8 description to-D
set interfaces fe-0/0/0 unit 8 family inet address 10.10.10.14/30
set interfaces lo0 unit 5 family inet address 192.168.5.5/32
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.168.5.5
set protocols bgp group internal-peers export send-ospf
set protocols bgp group internal-peers neighbor 192.168.0.1
set protocols bgp group internal-peers neighbor 192.168.6.5
set protocols ospf area 0.0.0.0 interface lo0.5 passive
set protocols ospf area 0.0.0.0 interface fe-0/0/0.8
set policy-options policy-statement send-ospf term 2 from protocol ospf
set policy-options policy-statement send-ospf term 2 then accept
set routing-options router-id 192.168.5.5
set routing-options autonomous-system 17

```

### Configuring the Route Reflector

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure IBGP in the network using Juniper Networks Device A as a route reflector:

1. Configure the interfaces.
 

```

[edit interfaces]
user@A# set fe-0/0/0 unit 1 description to-B
user@A# set fe-0/0/0 unit 1 family inet address 10.10.10.1/30
user@A# set fe-0/0/1 unit 3 description to-D
user@A# set fe-0/0/1 unit 3 family inet address 10.10.10.9/30
user@A# set lo0 unit 1 family inet address 192.168.6.5/32

```
2. Configure BGP, including the cluster identifier and neighbor relationships with all IBGP-enabled devices in the autonomous system (AS).

Also apply the policy that redistributes OSPF routes into BGP.

```
[edit protocols bgp group internal-peers]
user@A# set type internal
user@A# set local-address 192.168.6.5
user@A# set export send-ospf
user@A# set cluster 192.168.6.5
user@A# set neighbor 192.163.6.4
user@A# set neighbor 192.168.40.4
user@A# set neighbor 192.168.0.1
user@A# set neighbor 192.168.5.5
```

3. Configure static routing or an interior gateway protocol (IGP).

This example uses OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@A# set interface lo0.1 passive
user@A# set interface fe-0/0/0.1
user@A# set interface fe-0/0/1.3
```

4. Configure the policy that redistributes OSPF routes into BGP.

```
[edit policy-options policy-statement send-ospf term 2]
user@A# set from protocol ospf
user@A# set then accept
```

5. Configure the router ID and the autonomous system (AS) number.

```
[edit routing-options]
user@A# set router-id 192.168.6.5
user@A# set autonomous-system 17
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@A# show interfaces
fe-0/0/0 {
  unit 1 {
    description to-B;
    family inet {
      address 10.10.10.1/30;
    }
  }
}
fe-0/0/1 {
  unit 3 {
    description to-D;
    family inet {
      address 10.10.10.9/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
```

```

        address 192.168.6.5/32;
    }
}
}

user@A# show protocols
bgp {
    group internal-peers {
        type internal;
        local-address 192.168.6.5;
        export send-ospf;
        cluster 192.168.6.5;
        neighbor 192.163.6.4;
        neighbor 192.168.40.4;
        neighbor 192.168.0.1;
        neighbor 192.168.5.5;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.1 {
            passive;
        }
        interface fe-0/0/0.1;
        interface fe-0/0/1.3;
    }
}

user@A# show policy-options
policy-statement send-ospf {
    term 2 {
        from protocol ospf;
        then accept;
    }
}

user@A# show routing-options
router-id 192.168.6.5;
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.



**NOTE:** Repeat these steps for each nonclient BGP peer within the cluster that you are configuring, if the other nonclient devices are from Juniper Networks. Otherwise, consult the device's documentation for instructions.

### Configuring Client Peers

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure client peers:

1. Configure the interfaces.  
  
[edit interfaces]  
user@B# set fe-0/0/0 unit 2 description to-A  
user@B# set fe-0/0/0 unit 2 family inet address 10.10.10.2/30  
user@B# set fe-0/0/1 unit 5 description to-C  
user@B# set fe-0/0/1 unit 5 family inet address 10.10.10.5/30  
user@B# set lo0 unit 2 family inet address 192.163.6.4/32
2. Configure the BGP neighbor relationship with the route reflector.

Also apply the policy that redistributes OSPF routes into BGP.

- ```
[edit protocols bgp group internal-peers]
user@B# set type internal
user@B# set local-address 192.163.6.4
user@B# set export send-ospf
user@B# set neighbor 192.168.6.5
```
3. Configure OSPF.  
  
[edit protocols ospf area 0.0.0.0]  
user@B# set interface lo0.2 passive  
user@B# set interface fe-0/0/0.2  
user@B# set interface fe-0/0/1.5
  4. Configure the policy that redistributes OSPF routes into BGP.  
  
[edit policy-options policy-statement send-ospf term 2]  
user@B# set from protocol ospf  
user@B# set then accept
  5. Configure the router ID and the AS number.  
  
[edit routing-options]  
user@B# set router-id 192.163.6.4  
user@B# set autonomous-system 17

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@B# show interfaces
fe-0/0/0 {
  unit 2 {
    description to-A;
    family inet {
      address 10.10.10.2/30;
    }
  }
}
```



```

    }
  }
  fe-0/0/1 {
    unit 5 {
      description to-C;
      family inet {
        address 10.10.10.5/30;
      }
    }
  }
  lo0 {
    unit 2 {
      family inet {
        address 192.163.6.4/32;
      }
    }
  }
}

user@B# show protocols
bgp {
  group internal-peers {
    type internal;
    local-address 192.163.6.4;
    export send-ospf;
    neighbor 192.168.6.5;
  }
}

ospf {
  area 0.0.0.0 {
    interface lo0.2 {
      passive;
    }
    interface fe-0/0/0.2;
    interface fe-0/0/1.5;
  }
}

user@B# show policy-options
policy-statement send-ospf {
  term 2 {
    from protocol ospf;
    then accept;
  }
}

user@B# show routing-options
router-id 192.163.6.4;
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.



**NOTE:** Repeat these steps for each client BGP peer within the cluster that you are configuring if the other client devices are from Juniper Networks. Otherwise, consult the device's documentation for instructions.

### Configuring Nonclient Peers

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure nonclient peers:

1. Configure the interfaces.

```
[edit interfaces]
user@D# set fe-0/0/0 unit 4 description to-A
user@D# set fe-0/0/0 unit 4 family inet address 10.10.10.10/30
user@D# set fe-0/0/1 unit 7 description to-E
user@D# set fe-0/0/1 unit 7 family inet address 10.10.10.13/30
user@D# set lo0 unit 4 family inet address 192.168.0.1/32
```

2. Configure the BGP neighbor relationships with the RRroute reflector and with the other nonclient peers.

Also apply the policy that redistributes OSPF routes into BGP.

```
[edit protocols bgp group internal-peers]
user@D# set type internal
user@D# set local-address 192.168.0.1
user@D# set export send-ospf
user@D# set neighbor 192.168.6.5
user@D# set neighbor 192.168.5.5
```

3. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@D# set interface lo0.4 passive
user@D# set interface fe-0/0/0.4
user@D# set interface fe-0/0/1.7
```

4. Configure the policy that redistributes OSPF routes into BGP.

```
[edit policy-options policy-statement send-ospf term 2]
user@D# set from protocol ospf
user@D# set then accept
```

5. Configure the router ID and the AS number.

```
[edit routing-options]
user@D# set router-id 192.168.0.1
user@D# set autonomous-system 17
```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@D# show interfaces
fe-0/0/0 {
  unit 4 {
    description to-A;
    family inet {
```

```

        address 10.10.10.10/30;
    }
}
}
fe-0/0/1 {
    unit 7 {
        description to-E;
        family inet {
            address 10.10.10.13/30;
        }
    }
}
lo0 {
    unit 4 {
        family inet {
            address 192.168.0.1/32;
        }
    }
}

user@D# show protocols
bgp {
    group internal-peers {
        type internal;
        local-address 192.168.0.1;
        export send-ospf;
        neighbor 192.168.6.5;
        neighbor 192.168.5.5;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.4 {
            passive;
        }
        interface fe-0/0/0.4;
        interface fe-0/0/1.7;
    }
}

user@D# show policy-options
policy-statement send-ospf {
    term 2 {
        from protocol ospf;
        then accept;
    }
}

user@D# show routing-options
router-id 192.168.0.1;
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.



**NOTE:** Repeat these steps for each nonclient BGP peer within the cluster that you are configuring if the other nonclient devices are from Juniper Networks. Otherwise, consult the device's documentation for instructions.

## Verification

Confirm that the configuration is working properly.

- [Verifying BGP Neighbors on page 298](#)
- [Verifying BGP Groups on page 300](#)
- [Verifying BGP Summary Information on page 301](#)
- [Verifying Routing Table Information on page 301](#)

### Verifying BGP Neighbors

**Purpose** Verify that BGP is running on configured interfaces and that the BGP session is established for each neighbor address.

**Action** From operational mode, enter the **show bgp neighbor** command.

```
user@A> show bgp neighbor
Peer: 192.163.6.4+179 AS 17    Local: 192.168.6.5+62857 AS 17
  Type: Internal    State: Established (route reflector client)Flags: <Sync>
  Last State: OpenConfirm    Last Event: RecvKeepAlive
  Last Error: None
  Export: [ send-ospf ]
  Options: <Preference LocalAddress Cluster Refresh>
  Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 192.163.6.4    Local ID: 192.168.6.5    Active Holdtime: 90
  Keepalive Interval: 30    Peer index: 0
  BFD: disabled, down
  NLRI for restart configured on peer: inet-unicast
  NLRI advertised by peer: inet-unicast
  NLRI for this session: inet-unicast
  Peer supports Refresh capability (2)
  Restart time configured on the peer: 120
  Stale routes from peer are kept for: 300
  Restart time requested by this peer: 120
  NLRI that peer supports restart for: inet-unicast
  NLRI that restart is negotiated for: inet-unicast
  NLRI of received end-of-rib markers: inet-unicast
  NLRI of all end-of-rib markers sent: inet-unicast
  Peer supports 4 byte AS extension (peer-as 17)
  Peer does not support Addpath
  Table inet.0 Bit: 10000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          0
    Received prefixes:        6
    Accepted prefixes:        1
    Suppressed due to damping: 0
    Advertised prefixes:      6
  Last traffic (seconds): Received 5    Sent 3    Checked 19
```

```

Input messages: Total 2961    Updates 7        Refreshes 0    Octets 56480
Output messages: Total 2945    Updates 6        Refreshes 0    Octets 56235
Output Queue[0]: 0

Peer: 192.168.0.1+179 AS 17    Local: 192.168.6.5+60068 AS 17
Type: Internal    State: Established (route reflector client)Flags: <Sync>
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: None
Export: [ send-ospf ]
Options: <Preference LocalAddress Cluster Refresh>
Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 192.168.0.1    Local ID: 192.168.6.5    Active Holdtime: 90
Keepalive Interval: 30    Peer index: 3
BFD: disabled, down
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 17)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        6
  Accepted prefixes:        1
  Suppressed due to damping: 0
  Advertised prefixes:      6
Last traffic (seconds): Received 18    Sent 20    Checked 12
Input messages: Total 15    Updates 5        Refreshes 0    Octets 447
Output messages: Total 554    Updates 4        Refreshes 0    Octets 32307
Output Queue[0]: 0

Peer: 192.168.5.5+57458 AS 17    Local: 192.168.6.5+179 AS 17
Type: Internal    State: Established (route reflector client)Flags: <Sync>
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: None
Export: [ send-ospf ]
Options: <Preference LocalAddress Cluster Refresh>
Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 192.168.5.5    Local ID: 192.168.6.5    Active Holdtime: 90
Keepalive Interval: 30    Peer index: 2
BFD: disabled, down
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast

```

```

NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 17)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        7
  Accepted prefixes:        7
  Suppressed due to damping: 0
  Advertised prefixes:      6
Last traffic (seconds): Received 17   Sent 3   Checked 9
Input messages:  Total 2967   Updates 7   Refreshes 0   Octets 56629
Output messages: Total 2943   Updates 6   Refreshes 0   Octets 56197
Output Queue[0]: 0

Peer: 192.168.40.4+53990 AS 17 Local: 192.168.6.5+179 AS 17
Type: Internal   State: Established (route reflector client)Flags: <Sync>
Last State: OpenConfirm   Last Event: RecvKeepAlive
Last Error: None
Export: [ send-ospf ]
Options: <Preference LocalAddress Cluster Refresh>
Local Address: 192.168.6.5 Holdtime: 90 Preference: 170
Number of flaps: 0
Peer ID: 192.168.40.4   Local ID: 192.168.6.5   Active Holdtime: 90
Keepalive Interval: 30   Peer index: 1
BFD: disabled, down
NLRI for restart configured on peer: inet-unicast
NLRI advertised by peer: inet-unicast
NLRI for this session: inet-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-unicast
NLRI that restart is negotiated for: inet-unicast
NLRI of received end-of-rib markers: inet-unicast
NLRI of all end-of-rib markers sent: inet-unicast
Peer supports 4 byte AS extension (peer-as 17)
Peer does not support Addpath
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          0
  Received prefixes:        7
  Accepted prefixes:        7
  Suppressed due to damping: 0
  Advertised prefixes:      6
Last traffic (seconds): Received 5   Sent 23   Checked 52
Input messages:  Total 2960   Updates 7   Refreshes 0   Octets 56496
Output messages: Total 2943   Updates 6   Refreshes 0   Octets 56197
Output Queue[0]: 0

```

### Verifying BGP Groups

**Purpose** Verify that the BGP groups are configured correctly.

**Action** From operational mode, enter the **show bgp group** command.

```
user@A> show bgp group
Group Type: Internal    AS: 17                      Local AS: 17
Name: internal-peers   Index: 0                    Flags: <>
Export: [ send-ospf ]
Options: <Cluster>
Holdtime: 0
Total peers: 4          Established: 4
192.163.6.4+179
192.168.40.4+53990
192.168.0.1+179
192.168.5.5+57458
inet.0: 0/26/16/0

Groups: 1 Peers: 4 External: 0 Internal: 4 Down peers: 0 Flaps: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State  Pending
inet.0           26          0          0          0      0      0      0
```

### Verifying BGP Summary Information

**Purpose** Verify that the BGP configuration is correct.

**Action** From operational mode, enter the **show bgp summary** command.

```
user@A> show bgp summary

Groups: 1 Peers: 4 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State  Pending
inet.0           26          0          0          0      0      0      0
Peer      AS      InPkt    OutPkt    OutQ   Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
192.163.6.4      17      2981      2965      0       0    22:19:15 0/6/1/0      0/0/0/0
192.168.0.1      17       36       575      0       0    13:43 0/6/1/0      0/0/0/0
192.168.5.5      17     2988     2964      0       0    22:19:10 0/7/7/0      0/0/0/0
192.168.40.4     17     2980     2964      0       0    22:19:14 0/7/7/0      0/0/0/0
```

### Verifying Routing Table Information

**Purpose** Verify that the routing table contains the IBGP routes.

**Action** From operational mode, enter the **show route** command.

```
user@A> show route
inet.0: 12 destinations, 38 routes (12 active, 0 holddown, 10 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.0/30      * [Direct/0] 22:22:03
> via fe-0/0/0.1
[BGP/170] 22:20:55, MED 2, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
[BGP/170] 22:20:51, MED 3, localpref 100, from 192.168.5.5
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
10.10.10.1/32     * [Local/0] 22:22:03
Local via fe-0/0/0.1
10.10.10.4/30     * [OSPF/10] 22:21:13, metric 2
> to 10.10.10.2 via fe-0/0/0.1
[BGP/170] 22:20:51, MED 4, localpref 100, from 192.168.5.5
```

```

AS path: I
> to 10.10.10.10 via fe-0/0/1.3
10.10.10.8/30 * [Direct/0] 22:22:03
> via fe-0/0/1.3
[BGP/170] 22:20:51, MED 2, localpref 100, from 192.168.5.5
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 22:20:55, MED 3, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
10.10.10.9/32 * [Local/0] 22:22:03
Local via fe-0/0/1.3
10.10.10.12/30 * [OSPF/10] 22:21:08, metric 2
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 22:20:55, MED 4, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
192.163.6.4/32 * [OSPF/10] 22:21:13, metric 1
> to 10.10.10.2 via fe-0/0/0.1
[BGP/170] 22:20:55, MED 1, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
[BGP/170] 22:20:51, MED 3, localpref 100, from 192.168.5.5
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
192.168.0.1/32 * [OSPF/10] 22:21:08, metric 1
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 22:20:51, MED 1, localpref 100, from 192.168.5.5
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 22:20:55, MED 3, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
192.168.5.5/32 * [OSPF/10] 22:21:08, metric 2
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 00:15:24, MED 1, localpref 100, from 192.168.0.1
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 22:20:55, MED 4, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
192.168.6.5/32 * [Direct/0] 22:22:04
> via lo0.1
[BGP/170] 22:20:51, MED 2, localpref 100, from 192.168.5.5
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
[BGP/170] 22:20:55, MED 2, localpref 100, from 192.168.40.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
192.168.40.4/32 * [OSPF/10] 22:21:13, metric 2
> to 10.10.10.2 via fe-0/0/0.1
[BGP/170] 22:20:55, MED 1, localpref 100, from 192.163.6.4
AS path: I
> to 10.10.10.2 via fe-0/0/0.1
[BGP/170] 22:20:51, MED 4, localpref 100, from 192.168.5.5
AS path: I
> to 10.10.10.10 via fe-0/0/1.3
224.0.0.5/32 * [OSPF/10] 22:22:07, metric 1
MultiRecv

```



## Release History Table

| Release | Description                                                                                                                                                                                                                                 |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 15.1    | Starting in Junos OS Release 15.1, the <b>no-install</b> statement eliminates interaction between the routing protocols daemon (rpd) and other components in the Junos system such as the kernel or the distributed firewall daemon (dfwd). |
| 15.1    | In releases previous to Junos OS Release 15.1, you can reduce the workload on a route reflector that is not in the traffic-forwarding path by using a forwarding-table export policy that rejects routes learned from BGP.                  |

## Related Documentation

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

## Example: Configuring BGP Confederations

- [Understanding BGP Confederations on page 303](#)
- [Example: Configuring BGP Confederations on page 304](#)

### Understanding BGP Confederations

BGP confederations are another way to solve the scaling problems created by the BGP full mesh requirement. BGP confederations effectively break up a large autonomous system (AS) into subautonomous systems (sub-ASs). Each sub-AS must be uniquely identified within the confederation AS by a sub-AS number. Typically, sub-AS numbers are taken from the private AS numbers between 64,512 and 65,535.

Within a sub-AS, the same internal BGP (IBGP) full mesh requirement exists. Connections to other confederations are made with standard external BGP (EBGP), and peers outside the sub-AS are treated as external. To avoid routing loops, a sub-AS uses a confederation sequence, which operates like an AS path but uses only the privately assigned sub-AS numbers.

The confederation AS appears whole to other confederation ASs. The AS path received by other ASs shows only the globally assigned AS number. It does not include the confederation sequence or the privately assigned sub-AS numbers. The sub-AS numbers are removed when the route is advertised out of the confederation AS. [Figure 31 on page 304](#) shows an AS divided into four confederations.

Figure 31: BGP Confederations




Figure 31 on page 304 shows AS 3 divided into four sub-ASs, 64517, 64550, 65300, and 65410, which are linked through EBGP sessions. Because the confederations are connected by EBGP, they do not need to be fully meshed. EBGP routes are readvertised to other sub-ASs.

### Example: Configuring BGP Confederations

This example shows how to configure BGP confederations.

- [Requirements on page 304](#)
- [Overview on page 304](#)
- [Configuration on page 305](#)
- [Verification on page 307](#)

#### Requirements

- Configure network interfaces.
- Configure external peer sessions. See [“Example: Configuring External BGP Point-to-Point Peer Sessions” on page 14](#).
- Configure interior gateway protocol (IGP) sessions between peers.
- Configure a routing policy to advertise the BGP routes.

#### Overview


Within a BGP confederation, the links between the confederation member autonomous systems (ASs) must be external BGP (EBGP) links, not internal BGP (IBGP) links.

Similar to route reflectors, BGP confederations reduce the number of peer sessions and TCP sessions to maintain connections between IBGP routing devices. BGP confederation is one method used to solve the scaling problems created by the IBGP full mesh

requirement. BGP confederations effectively break up a large AS into subautonomous systems. Each sub-AS must be uniquely identified within the confederation AS by a sub-AS number. Typically, sub-AS numbers are taken from the private AS numbers between 64512 and 65535. Within a sub-AS, the same IBGP full mesh requirement exists. Connections to other confederations are made with standard EBGP, and peers outside the sub-AS are treated as external. To avoid routing loops, a sub-AS uses a confederation sequence, which operates like an AS path but uses only the privately assigned sub-AS numbers.

Figure 32 on page 305 shows a sample network in which AS 17 has two separate confederations: sub-AS 64512 and sub-AS 64513, each of which has multiple routers. Within a sub-AS, an IGP is used to establish network connectivity with internal peers. Between sub-ASs, an EBGP peer session is established.

Figure 32: Typical Network Using BGP Confederations



### Configuration

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

|                               |                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| All Devices in Sub-AS 64512   | <pre> set routing-options autonomous-system 64512 set routing-options confederation 17 members 64512 set routing-options confederation 17 members 64513 set protocols bgp group sub-AS-64512 type internal set protocols bgp group sub-AS-64512 local-address 192.168.5.1 set protocols bgp group sub-AS-64512 neighbor 192.168.8.1 set protocols bgp group sub-AS-64512 neighbor 192.168.15.1 </pre> |
| Border Device in Sub-AS 64512 | <pre> set protocols bgp group to-sub-AS-64513 type external set protocols bgp group to-sub-AS-64513 peer-as 64513 set protocols bgp group to-sub-AS-64513 neighbor 192.168.5.2 </pre>                                                                                                                                                                                                                 |
| All Devices in Sub-AS 64513   | <pre> set routing-options autonomous-system 64513 set routing-options confederation 17 members 64512 set routing-options confederation 17 members 64513 set protocols bgp group sub-AS-64513 type internal </pre>                                                                                                                                                                                     |

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                               | <pre>set protocols bgp group sub-AS-64513 local-address 192.168.5.2 set protocols bgp group sub-AS-64513 neighbor 192.168.9.1 set protocols bgp group sub-AS-64513 neighbor 192.168.16.1</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Border Device in Sub-AS 64513 | <pre>set protocols bgp group to-sub-AS-64512 type external set protocols bgp group to-sub-AS-64512 peer-as 64512 set protocols bgp group to-sub-AS-64512 neighbor 192.168.5.1</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Step-by-Step Procedure        | <p>This procedure shows the steps for the devices that are in sub-AS 64512.</p> <p>The <b>autonomous-system</b> statement sets the sub-AS number of the device.</p> <p>The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see <i>Using the CLI Editor in Configuration Mode</i> in the <i>CLI User Guide</i>.</p> <p>To configure BGP confederations:</p> <ol style="list-style-type: none"><li>1. Set the sub-AS number for the device.<br/><pre>[edit routing-options] user@host# set autonomous-system 64512</pre></li><li>2. In the confederation, include all sub-ASs in the main AS.<br/><p>The number 17 represents the main AS. The <b>members</b> statement lists all the sub-ASs in the main AS.</p><pre>[edit routing-options confederation] user@host# set 17 members 64512 user@host# set 17 members 64513</pre></li><li>3. On the border device in sub-AS 64512, configure an EBGP connection to the border device in AS 64513.<br/><pre>[edit protocols bgp group to-sub-AS-64513] user@host# set type external user@host# set neighbor 192.168.5.2 user@host# set peer-as 64513</pre></li><li>4. Configure an IBGP group for peering with the devices within sub-AS 64512.<br/><pre>[edit protocols bgp group sub-AS-64512] user@host# set type internal user@host# set local-address 192.168.5.1 user@host# neighbor 192.168.8.1 user@host# neighbor 192.168.15.1</pre></li></ol> |
| Results                       | <p>From configuration mode, confirm your configuration by entering the <b>show routing-options</b> and <b>show protocols</b> commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.</p> <pre>user@host# show routing-options autonomous-system 64512; confederation 17 members [ 64512 64513 ];  user@host# show protocols bgp {</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

```

group to-sub-AS-64513 { # On the border devices only
  type external;
  peer-as 64513;
  neighbor 192.168.5.2;
}
group sub-AS-64512 {
  type internal;
  local-address 192.168.5.1;
  neighbor 192.168.8.1;
  neighbor 192.168.15.1;
}
}

```

If you are done configuring the device, enter **commit** from configuration mode.  
Repeat these steps for sSub-AS 64513.

### Verification

Confirm that the configuration is working properly.

- [Verifying BGP Neighbors on page 307](#)
- [Verifying BGP Groups on page 308](#)
- [Verifying BGP Summary Information on page 309](#)

#### Verifying BGP Neighbors

**Purpose** Verify that BGP is running on configured interfaces and that the BGP session is active for each neighbor address.

**Action** From the CLI, enter the **show bgp neighbor** command.

### Sample Output

```

user@host> show bgp neighbor
Peer: 10.255.245.12+179 AS 35 Local: 10.255.245.13+2884 AS 35
  Type: Internal State: Established (route reflector client)Flags: Sync
  Last State: OpenConfirm Last Event: RecvKeepAlive
  Last Error: None
  Options: Preference LocalAddress HoldTime Cluster AddressFamily Rib-group Refresh

  Address families configured: inet-vpn-unicast inet-labeled-unicast
  Local Address: 10.255.245.13 Holdtime: 90 Preference: 170
  Flags for NLRI inet-vpn-unicast: AggregateLabel
  Flags for NLRI inet-labeled-unicast: AggregateLabel
  Number of flaps: 0
  Peer ID: 10.255.245.12 Local ID: 10.255.245.13 Active Holdtime: 90
  Keepalive Interval: 30
  NLRI advertised by peer: inet-vpn-unicast inet-labeled-unicast
  NLRI for this session: inet-vpn-unicast inet-labeled-unicast
  Peer supports Refresh capability (2)
Restart time configured on the peer: 300
Stale routes from peer are kept for: 60
Restart time requested by this peer: 300
NLRI that peer supports restart for: inet-unicast inet6-unicast
NLRI that restart is negotiated for: inet-unicast inet6-unicast
NLRI of received end-of-rib markers: inet-unicast inet6-unicast
NLRI of all end-of-rib markers sent: inet-unicast inet6-unicast

```

```

Table inet.0 Bit: 10000
  RIB State: restart is complete
  Send state: in sync
  Active prefixes: 4
  Received prefixes: 6
  Suppressed due to damping: 0
Table inet6.0 Bit: 20000
  RIB State: restart is complete
  Send state: in sync
  Active prefixes: 0
  Received prefixes: 2
  Suppressed due to damping: 0
Last traffic (seconds): Received 3    Sent 3    Checked 3
Input messages: Total 9    Updates 6    Refreshes 0    Octets 403
Output messages: Total 7    Updates 3    Refreshes 0    Octets 365
Output Queue[0]: 0
Output Queue[1]: 0
Trace options: detail packets
Trace file: /var/log/bgpr size 131072 files 10

```

**Meaning** The output shows a list of the BGP neighbors with detailed session information. Verify the following information:

- Each configured peering neighbor is listed.
- For **State**, each BGP session is **Established**.
- For **Type**, each peer is configured as the correct type (either internal or external).
- For **AS**, the AS number of the BGP neighbor is correct.

#### Verifying BGP Groups

**Purpose** Verify that the BGP groups are configured correctly.

**Action** From the CLI, enter the **show bgp group** command.

### Sample Output

```

user@host> show bgp group
Group Type: Internal  AS: 10045      Local AS: 10045
Name: pe-to-asbr2      Flags: Export Eval
Export: [ match-all ]
Total peers: 1      Established: 1
10.0.0.4+179
bgp.l3vpn.0: 1/1/0
vpn-green.inet.0: 1/1/0

Groups: 1  Peers: 1  External: 0  Internal: 1  Down peers: 0  Flaps: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State  Pending
bgp.l3vpn.0      1          1          0          0          0          0

```

**Meaning** The output shows a list of the BGP groups with detailed group information. Verify the following information:

- Each configured group is listed.
- For **AS**, each group's remote AS is configured correctly.

- For **Local AS**, each group's local AS is configured correctly.
- For **Group Type**, each group has the correct type (either internal or external).
- For **Total peers**, the expected number of peers within the group is shown.
- For **Established**, the expected number of peers within the group have BGP sessions in the **Established** state.
- The IP addresses of all the peers within the group are present.

### Verifying BGP Summary Information

**Purpose** Verify that the BGP configuration is correct.

**Action** From the CLI, enter the **show bgp summary** command.

### Sample Output

```
user@host> show bgp summary
Groups: 1 Peers: 3 Down peers: 0
Table          Tot Paths  Act Paths Suppressed  History  Damp State   Pending
inet.0          6          4          0          0        0      0        0
Peer           AS      InPkt    OutPkt    OutQ    Flaps  Last Up/Dwn
State|#Active/Received/Damped...
10.0.0.2        65002    88675    88652      0        2      42:38 2/4/0
0/0/0
10.0.0.3        65002    54528    54532      0        1     2w4d22h 0/0/0
0/0/0
10.0.0.4        65002    51597    51584      0        0     2w3d22h 2/2/0
0/0/0
```

**Meaning** The output shows a summary of BGP session information. Verify the following information:

- For **Groups**, the total number of configured groups is shown.
- For **Peers**, the total number of BGP peers is shown.
- For **Down Peers**, the total number of unestablished peers is 0. If this value is not zero, one or more peering sessions are not yet established.
- Under **Peer**, the IP address for each configured peer is shown.
- Under **AS**, the peer AS for each configured peer is correct.
- Under **Up/Dwn State**, the BGP state reflects the number of paths received from the neighbor, the number of these paths that have been accepted, and the number of routes being damped (such as 0/0/0). If the field is **Active**, it indicates a problem in the establishment of the BGP session.

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)





## CHAPTER 8

# BGP Security Configuration

- [Example: Configuring BGP Route Authentication on page 311](#)
- [Examples: Configuring TCP and BGP Security on page 318](#)

### Example: Configuring BGP Route Authentication

---

- [Understanding Route Authentication on page 311](#)
- [Example: Configuring Route Authentication for BGP on page 312](#)

### Understanding Route Authentication

The use of router and route authentication and route integrity greatly mitigates the risk of being attacked by a machine or router that has been configured to share incorrect routing information with another router. In this kind of attack, the attacked router can be tricked into creating a routing loop, or the attacked router's routing table can be greatly increased thus impacting performance, or routing information can be redirected to a place in the network for the attacker to analyze it. Bogus route advertisements can be sent out on a segment. These updates can be accepted into the routing tables of neighbor routers unless an authentication mechanism is in place to verify the source of the routes.

Router and route authentication enables routers to share information only if they can verify that they are talking to a trusted source, based on a password (key). In this method, a hashed key is sent along with the route being sent to another router. The receiving router compares the sent key to its own configured key. If they are the same, it accepts the route. By using a hashing algorithm, the key is not sent over the wire in plain text. Instead, a hash is calculated using the configured key. The routing update is used as the input text, along with the key, into the hashing function. This hash is sent along with the route update to the receiving router. The receiving router compares the received hash with a hash it generates on the route update using the preshared key configured on it. If the two hashes are the same, the route is assumed to be from a trusted source. The key is known only to the sending and receiving routers.

To further strengthen security, you can configure a series of authentication keys (a *keychain*). Each key has a unique start time within the keychain. Keychain authentication allows you to change the password information periodically without bringing down peering sessions. This keychain authentication method is referred to as *hitless* because the keys roll over from one to the next without resetting any peering sessions or interrupting the routing protocol.

The sending peer uses the following rules to identify the active authentication key:

- The start time is less than or equal to the current time (in other words, not in the future).
- The start time is greater than that of all other keys in the chain whose start time is less than the current time (in other words, closest to the current time).

The receiving peer determines the key with which it authenticates based on the incoming key identifier.

The sending peer identifies the current authentication key based on a configured start time and then generates a hash value using the current key. The sending peer then inserts a TCP-enhanced authentication option object into the BGP update message. The object contains an object ID (assigned by IANA), the object length, the current key, and a hash value.

The receiving peer examines the incoming TCP-enhanced authentication option, looks up the received authentication key, and determines whether the key is acceptable based on the start time, the system time, and the tolerance parameter. If the key is accepted, the receiving peer calculates a hash and authenticates the update message.

Initial application of a keychain to a TCP session causes the session to reset. However, once the keychain is applied, the addition or removal of a password from the keychain does not cause the TCP session to reset. Also, the TCP session does not reset when the keychain changes from one authentication algorithm to another.

## Example: Configuring Route Authentication for BGP

All BGP protocol exchanges can be authenticated to guarantee that only trusted routing devices participate in autonomous system (AS) routing updates. By default, authentication is disabled.

- [Requirements on page 312](#)
- [Overview on page 312](#)
- [Configuration on page 314](#)
- [Verification on page 316](#)

---

### Requirements

Before you begin:

- Configure the router interfaces.
- Configure an interior gateway protocol (IGP).

---

### Overview

When you configure authentication, the algorithm creates an encoded checksum that is included in the transmitted packet. The receiving routing device uses an authentication key (password) to verify the packet's checksum.

This example includes the following statements for configuring and applying the keychain:

- **key**—A keychain can have multiple keys. Each key within a keychain must be identified by a unique integer value. The range of valid identifier values is from 0 through 63.  
The key can be up to 126 characters long. Characters can include any ASCII strings. If you include spaces, enclose all characters in quotation marks (" ").
- **tolerance**—(Optional) For each keychain, you can configure a clock-skew tolerance value in seconds. The clock-skew tolerance is applicable to the receiver accepting keys for BGP updates. The configurable range is 0 through 999,999,999 seconds. During the tolerance period, either the current or previous password is acceptable.
- **key-chain**—For each keychain, you must specify a name. This example defines one keychain: **bgp-auth**. You can have multiple keychains on a routing device. For example, you can have a keychain for BGP, a keychain for OSPF, and a keychain for LDP.
- **secret**—For each key in the keychain, you must set a secret password. This password can be entered in either encrypted or plain text format in the **secret** statement. It is always displayed in encrypted format.
- **start-time**—Each key must specify a start time in UTC format. Control gets passed from one key to the next. When a configured start time arrives (based on the routing device's clock), the key with that start time becomes active. Start times are specified in the local time zone for a routing device and must be unique within the keychain.
- **authentication-key-chain**—Enables you to apply a keychain at the global BGP level for all peers, for a group, or for a neighbor. This example applies the keychain to the peers defined in the external BGP (EBGP) group called **ext**.
- **authentication-algorithm**—For each keychain, you can specify a hashing algorithm. The algorithm can be AES-128, MD5, or SHA-1.


You associate a keychain and an authentication algorithm with a BGP neighboring session.

This example configures a keychain named **bgp-auth**. Key 0 will be sent and accepted starting at 2011-6-23.20:19:33 -0700, and will stop being sent and accepted when the next key in the keychain (key 1) becomes active. Key 1 becomes active one year later at 2012-6-23.20:19:33 -0700, and will not stop being sent and accepted unless another key is configured with a start time that is later than the start time of key 1. A clock-skew tolerance of 30 seconds applies to the receiver accepting the keys. During the tolerance period, either the current or previous key is acceptable. The keys are shared-secret passwords. This means that the neighbors receiving the authenticated routing updates must have the same authentication keychain configuration, including the same keys (passwords). So Router R0 and Router R1 must have the same authentication-key-chain configuration if they are configured as peers. This example shows the configuration on only one of the routing devices.

### **Topology Diagram**

Figure 33 on page 314 shows the topology used in this example.

Figure 33: Authentication for BGP



### Configuration

#### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set protocols bgp group ext type external
set protocols bgp group ext peer-as 65530
set protocols bgp group ext neighbor 172.16.2.1
set routing-options autonomous-system 65533
set protocols bgp group ext authentication-key-chain bgp-auth
set protocols bgp group ext authentication-algorithm md5
set security authentication-key-chains key-chain bgp-auth tolerance 30
set security authentication-key-chains key-chain bgp-auth key 0 secret
  this-is-the-secret-password
set security authentication-key-chains key-chain bgp-auth key 0 start-time
  2011-6-23.20:19:33-0700
set security authentication-key-chains key-chain bgp-auth key 1 secret
  this-is-another-secret-password
set security authentication-key-chains key-chain bgp-auth key 1 start-time
  2012-6-23.20:19:33-0700
```

#### Step-by-Step Procedure

The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Router R1 to accept route filters from Device CE1 and perform outbound route filtering using the received filters:

1. Configure the local autonomous system.
 

```
[edit routing-options]
user@R1# set autonomous-system 65533
```
2. Configure one or more BGP groups.
 

```
[edit protocols bgp group ext]
user@R1# set type external
user@R1# set peer-as 65530
user@R1# set neighbor 172.16.2.1
```
3. Configure authentication with multiple keys.
 

```
[edit security authentication-key-chains key-chain bgp-auth]
user@R1# set key 0 secret this-is-the-secret-password
user@R1# set key 0 start-time 2011-6-23.20:19:33-0700
user@R1# set key 1 secret this-is-another-secret-password
user@R1# set key 1 start-time 2012-6-23.20:19:33-0700
```

The start time of each key must be unique within the keychain.

4. Apply the authentication keychain to BGP, and set the hashing algorithm.

```
[edit protocols bgp group ext]
user@R1# set authentication-key-chain bgp-auth
user@R1# set authentication-algorithm md5
```

5. (Optional) Apply a clock-skew tolerance value in seconds.

```
[edit security authentication-key-chains key-chain bgp-auth]
user@R1# set tolerance 30
```

**Results** From configuration mode, confirm your configuration by entering the **show protocols**, **show routing-options**, and **show security** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R1# show protocols
bgp {
  group ext {
    type external;
    peer-as 65530;
    neighbor 172.16.2.1;
    authentication-key-chain bgp-auth;
    authentication-algorithm md5;
  }
}

user@R1# show routing-options
autonomous-system 65533;

user@R1# show security
authentication-key-chains {
  key-chain bgp-auth {
    tolerance 30;
    key 0 {
      secret $ABC123$ABC123
      start-time "2011-6-23.20:19:33 -0700";
    }
    key 1 {
      secret $ABC123$ABC123
      start-time "2012-6-23.20:19:33 -0700";
    }
  }
}
```

If you are done configuring the device, enter **commit** from configuration mode.

Repeat the procedure for every BGP-enabled device in the network, using the appropriate interface names and addresses for each BGP-enabled device.

## Verification

Confirm that the configuration is working properly.

- [Verifying Authentication for the Neighbor on page 316](#)
- [Verifying That Authorization Messages Are Sent on page 316](#)
- [Checking Authentication Errors on page 317](#)
- [Verifying the Operation of the Keychain on page 317](#)

### *Verifying Authentication for the Neighbor*

**Purpose** Make sure that the **AutheKeyChain** option appears in the output of the **show bgp neighbor** command.

**Action** From operational mode, enter the **show bgp neighbor** command.

```
user@R1> show bgp neighbor
Peer: 172.16.2.1+179 AS 65530 Local: 172.16.2.2+1222 AS 65533
  Type: External State: Established Flags: <Sync>
  Last State: OpenConfirm Last Event: RecvKeepAlive
  Last Error: None
  Export: [ direct-lo0 ]
  Options: <Preference PeerAS Refresh>
  Options: <AutheKeyChain>
  Authentication key is configured
  Authentication key chain: jni
  Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 172.16.2.1 Local ID: 10.255.124.35 Active Holdtime: 90
  Keepalive Interval: 30 Peer index: 0
  Local Interface: fe-0/0/1.0
  NLRI advertised by peer: inet-unicast
  NLRI for this session: inet-unicast
  Peer supports Refresh capability (2)
  Table inet.0 Bit: 10000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes: 2
    Received prefixes: 2
    Suppressed due to damping: 0
    Advertised prefixes: 1
  Last traffic (seconds): Received 2 Sent 2 Checked 2
  Input messages: Total 21 Updates 2 Refreshes 0 Octets 477
  Output messages: Total 22 Updates 1 Refreshes 0 Octets 471
  Output Queue[0]: 0
```

### *Verifying That Authorization Messages Are Sent*

**Purpose** Confirm that BGP has the enhanced authorization option.

**Action** From operational mode, enter the **monitor traffic interface fe-0/0/1** command.

```
user@R1> monitor traffic interface fe-0/0/1
verbose output suppressed, use <detail> or <extensive> for full protocol decode
Listening on fe-0/0/1, capture size 96 bytes
```

```
13:08:00.618402 In arp who-has 172.16.2.66 tell 172.16.2.69
```

```

13:08:02.408249 Out IP 172.16.2.2.1122 > 172.16.2.1.646: P
1889289217:1889289235(18) ack 2215740969 win 58486 <nop,nop,timestamp 167557
1465469,nop,Enhanced Auth keyid 0 diglen 12 digest: fe3366001f45767165f17037>:
13:08:02.418396 In IP 172.16.2.1.646 > 172.16.2.2.1122: P 1:19(18) ack 18 win
57100 <nop,nop,timestamp 1466460 167557,nop,Enhanced Auth keyid 0 diglen 12
digest: a18c31eda1b14b2900921675>:
13:08:02.518146 Out IP 172.16.2.2.1122 > 172.16.2.1.646: . ack 19 win 58468
<nop,nop,timestamp 167568 1466460,nop,Enhanced Auth keyid 0 diglen 12 digest:
c3b6422eb6bd3fd9cf79742b>
13:08:28.199557 Out IP 172.16.2.2.nerv > 172.16.2.1.bgp: P
286842489:286842508(19) ack 931203976 win 57200 <nop,Enhanced Auth keyid 0
diglen 12 digest: fc0e42900a73736bcc07c1a4>: BGP, length: 19
13:08:28.209661 In IP 172.16.2.1.bgp > 172.16.2.2.nerv: P 1:20(19) ack 19 win
56835 <nop,Enhanced Auth keyid 0 diglen 12 digest: 0fc8578c489fabce63aeb2c3>:
BGP, length: 19
13:08:28.309525 Out IP 172.16.2.2.nerv > 172.16.2.1.bgp: . ack 20 win 57181
<nop,Enhanced Auth keyid 0 diglen 12 digest: ef03f282fb2ece0039491df8>
13:08:32.439708 Out IP 172.16.2.2.1122 > 172.16.2.1.646: P 54:72(18) ack 55 win
58432 <nop,nop,timestamp 170560 1468472,nop,Enhanced Auth keyid 0 diglen 12
digest: 76e0cf926f348b726c631944>:
13:08:32.449795 In IP 172.16.2.1.646 > 172.16.2.2.1122: P 55:73(18) ack 72 win
57046 <nop,nop,timestamp 1469463 170560,nop,Enhanced Auth keyid 0 diglen 12
digest: dae3eec390d18a114431f4d8>:
13:08:32.549726 Out IP 172.16.2.2.1122 > 172.16.2.1.646: . ack 73 win 58414
<nop,nop,timestamp 170571 1469463,nop,Enhanced Auth keyid 0 diglen 12 digest:
851df771aee2ea7a43a0c46c>
13:08:33.719880 In arp who-has 172.16.2.66 tell 172.16.2.69
^C
35 packets received by filter
0 packets dropped by kernel

```

### Checking Authentication Errors

**Purpose** Check the number of packets dropped by TCP because of authentication errors.

**Action** From operational mode, enter the **show system statistics tcp | match auth** command.

```

user@R1> show system statistics tcp | match auth
      0 send packets dropped by TCP due to auth errors
      58 rcv packets dropped by TCP due to auth errors

```

### Verifying the Operation of the Keychain

**Purpose** Check the number of packets dropped by TCP because of authentication errors.

**Action** From operational mode, enter the **show security keychain detail** command.

```

user@R1> show security keychain detail
keychain          Active-ID      Next-ID      Transition  Tolerance
                  Send Receive  Send Receive
bgp-auth          3      3      1      1      1d 23:58      30
Id 3, Algorithm hmac-md5, State send-receive, Option basic
Start-time Wed Aug 11 16:28:00 2010, Mode send-receive
Id 1, Algorithm hmac-md5, State inactive, Option basic
Start-time Fri Aug 20 11:30:57 2010, Mode send-receive

```

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)

## Examples: Configuring TCP and BGP Security

---

- [Understanding Security Options for BGP with TCP on page 318](#)
- [Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers on page 318](#)
- [Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List on page 323](#)
- [Example: Limiting TCP Segment Size for BGP on page 326](#)

### Understanding Security Options for BGP with TCP

Among routing protocols, BGP is unique in using TCP as its transport protocol. BGP peers are established by manual configuration between routing devices to create a TCP session on port 179. A BGP-enabled device periodically sends keepalive messages to maintain the connection.

Over time, BGP has become the dominant interdomain routing protocol on the Internet. However, it has limited guarantees of stability and security. Configuring security options for BGP must balance suitable security measures with acceptable costs. No one method has emerged as superior to other methods. Each network administrator must configure security measures that meet the needs of the network being used.

For detailed information about the security issues associated with BGP's use of TCP as a transport protocol, see RFC 4272, *BGP Security Vulnerabilities Analysis*.

### Example: Configuring a Filter to Block TCP Access to a Port Except from Specified BGP Peers

This example shows how to configure a standard stateless firewall filter that blocks all TCP connection attempts to port 179 from all requesters except from specified BGP peers.

- [Requirements on page 318](#)
- [Overview on page 318](#)
- [Configuration on page 319](#)
- [Verification on page 322](#)

#### Requirements

---

No special configuration beyond device initialization is required before you configure this example.

#### Overview

---


In this example, you create a stateless firewall filter that blocks all TCP connection attempts to port 179 from all requesters except the specified BGP peers.

The stateless firewall filter **filter\_bgp179** matches all packets from the directly connected interfaces on Device A and Device B to the destination port number 179.



Figure 34 on page 319 shows the topology used in this example. Device C attempts to make a TCP connection to Device E. Device E blocks the connection attempt. This example shows the configuration on Device E.

Figure 34: Typical Network with BGP Peer Sessions



### Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device C**

```
set interfaces ge-1/2/0 unit 10 description to-E
set interfaces ge-1/2/0 unit 10 family inet address 10.10.10.10/30
set protocols bgp group external-peers type external
set protocols bgp group external-peers peer-as 17
set protocols bgp group external-peers neighbor 10.10.10.9
set routing-options autonomous-system 22
```

**Device E**

```
set interfaces ge-1/2/0 unit 0 description to-A
set interfaces ge-1/2/0 unit 0 family inet address 10.10.10.1/30
set interfaces ge-1/2/1 unit 5 description to-B
set interfaces ge-1/2/1 unit 5 family inet address 10.10.10.5/30
set interfaces ge-1/0/0 unit 9 description to-C
set interfaces ge-1/0/0 unit 9 family inet address 10.10.10.9/30
set interfaces lo0 unit 2 family inet filter input filter_bgp179
set interfaces lo0 unit 2 family inet address 192.168.0.1/32
set protocols bgp group external-peers type external
set protocols bgp group external-peers peer-as 22
set protocols bgp group external-peers neighbor 10.10.10.2
set protocols bgp group external-peers neighbor 10.10.10.6
set protocols bgp group external-peers neighbor 10.10.10.10
set routing-options autonomous-system 17
set firewall family inet filter filter_bgp179 term 1 from source-address 10.10.10.2/32
set firewall family inet filter filter_bgp179 term 1 from source-address 10.10.10.6/32
set firewall family inet filter filter_bgp179 term 1 from destination-port bgp
set firewall family inet filter filter_bgp179 term 1 then accept
set firewall family inet filter filter_bgp179 term 2 then reject
```

### Configuring Device E

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device E with a stateless firewall filter that blocks all TCP connection attempts to port 179 from all requestors except specified BGP peers:

1. Configure the interfaces.

```
user@E# set interfaces ge-1/2/0 unit 0 description to-A
user@E# set interfaces ge-1/2/0 unit 0 family inet address 10.10.10.1/30
```

```
user@E# set interfaces ge-1/2/1 unit 5 description to-B
user@E# set interfaces ge-1/2/1 unit 5 family inet address 10.10.10.5/30
```

```
user@E# set interfaces ge-1/0/0 unit 9 description to-C
user@E# set interfaces ge-1/0/0 unit 9 family inet address 10.10.10.9/30
```

2. Configure BGP.

```
[edit protocols bgp group external-peers]
user@E# set type external
user@E# set peer-as 22
user@E# set neighbor 10.10.10.2
user@E# set neighbor 10.10.10.6
user@E# set neighbor 10.10.10.10
```

3. Configure the autonomous system number.

```
[edit routing-options]
user@E# set autonomous-system 17
```

4. Define the filter term that accepts TCP connection attempts to port 179 from the specified BGP peers.

```
[edit firewall family inet filter filter_bgp179]
user@E# set term 1 from source-address 10.10.10.2/32
user@E# set term 1 from source-address 10.10.10.6/32
user@E# set term 1 from destination-port bgp
user@E# set term 1 then accept
```

5. Define the other filter term to reject packets from other sources.

```
[edit firewall family inet filter filter_bgp179]
user@E# set term 2 then reject
```

6. Apply the firewall filter to the loopback interface.

```
[edit interfaces lo0 unit 2 family inet]
user@E# set filter input filter_bgp179
user@E# set address 192.168.0.1/32
```

**Results** From configuration mode, confirm your configuration by entering the **show firewall**, **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not

display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@E# show firewall
family inet {
  filter filter_bgp179 {
    term 1 {
      from {
        source-address {
          10.10.10.2/32;
          10.10.10.6/32;
        }
        destination-port bgp;
      }
      then accept;
    }
    term 2 {
      then {
        reject;
      }
    }
  }
}

user@E# show interfaces
lo0 {
  unit 2 {
    family inet {
      filter {
        input filter_bgp179;
      }
      address 192.168.0.1/32;
    }
  }
}
ge-1/2/0 {
  unit 0 {
    description to-A;
    family inet {
      address 10.10.10.1/30;
    }
  }
}
ge-1/2/1 {
  unit 5 {
    description to-B;
    family inet {
      address 10.10.10.5/30;
    }
  }
}
ge-1/0/0 {
  unit 9 {
    description to-C;
    family inet {
      address 10.10.10.9/30;
    }
  }
}

```

```

    }
  }
}

user@E# show protocols
bgp {
  group external-peers {
    type external;
    peer-as 22;
    neighbor 10.10.10.2;
    neighbor 10.10.10.6;
    neighbor 10.10.10.10;
  }
}

user@E# show routing-options
autonomous-system 17;

```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

- [Verifying That the Filter Is Configured on page 322](#)
- [Verifying the TCP Connections on page 322](#)
- [Monitoring Traffic on the Interfaces on page 323](#)

### *Verifying That the Filter Is Configured*

**Purpose** Make sure that the filter is listed in output of the **show firewall filter** command.

**Action** user@E> show firewall filter filter\_bgp179  
Filter: filter\_bgp179

### *Verifying the TCP Connections*

**Purpose** Verify the TCP connections.

**Action** From operational mode, run the **show system connections extensive** command on Device C and Device E.

The output on Device C shows the attempt to establish a TCP connection. The output on Device E shows that connections are established with Device A and Device B only.

user@C> show system connections extensive | match 10.10.10

```
tcp4      0      0  10.10.10.9.51872      10.10.10.10.179      SYN_SENT
```

user@E> show system connections extensive | match 10.10.10

```
tcp4      0      0  10.10.10.5.179        10.10.10.6.62096     ESTABLISHED
tcp4      0      0  10.10.10.6.62096      10.10.10.5.179      ESTABLISHED
tcp4      0      0  10.10.10.1.179        10.10.10.2.61506     ESTABLISHED
tcp4      0      0  10.10.10.2.61506      10.10.10.1.179      ESTABLISHED
```

### Monitoring Traffic on the Interfaces

**Purpose** Use the **monitor traffic** command to compare the traffic on an interface that establishes a TCP connection with the traffic on an interface that does not establish a TCP connection.

**Action** From operational mode, run the **monitor traffic** command on the Device E interface to Device B and on the Device E interface to Device C. The following sample output verifies that in the first example, acknowledgment (**ack**) messages are received. In the second example, **ack** messages are not received.

```
user@E> monitor traffic size 1500 interface ge-1/2/1.5
19:02:49.700912 Out IP 10.10.10.5.bgp > 10.10.10.6.62096: P
3330573561:3330573580(19) ack 915601686 win 16384 <nop,nop,timestamp 1869518816
1869504850>: BGP, length: 19
19:02:49.801244 In IP 10.10.10.6.62096 > 10.10.10.5.bgp: . ack 19 win 16384
<nop,nop,timestamp 1869518916 1869518816>
19:03:03.323018 In IP 10.10.10.6.62096 > 10.10.10.5.bgp: P 1:20(19) ack 19 win
16384 <nop,nop,timestamp 1869532439 1869518816>: BGP, length: 19
19:03:03.422418 Out IP 10.10.10.5.bgp > 10.10.10.6.62096: . ack 20 win 16384
<nop,nop,timestamp 1869532539 1869532439>
19:03:17.220162 Out IP 10.10.10.5.bgp > 10.10.10.6.62096: P 19:38(19) ack 20 win
16384 <nop,nop,timestamp 1869546338 1869532439>: BGP, length: 19
19:03:17.320501 In IP 10.10.10.6.62096 > 10.10.10.5.bgp: . ack 38 win 16384
<nop,nop,timestamp 1869546438 1869546338>
```

```
user@E> monitor traffic size 1500 interface ge-1/0/0.9
```

```
18:54:20.175471 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,nop,wscale 0,nop,nop,timestamp 1869009240 0,sackOK,eol>
18:54:23.174422 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,nop,wscale 0,nop,nop,timestamp 1869012240 0,sackOK,eol>
18:54:26.374118 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,nop,wscale 0,nop,nop,timestamp 1869015440 0,sackOK,eol>
18:54:29.573799 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,sackOK,eol>
18:54:32.773493 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,sackOK,eol>
18:54:35.973185 Out IP 10.10.10.9.61335 > 10.10.10.10.bgp: S 573929123:573929123(0)
win 16384 <mss 1460,sackOK,eol>
```

### Example: Configuring a Filter to Limit TCP Access to a Port Based On a Prefix List

This example shows how to configure a standard stateless firewall filter that limits certain TCP and Internet Control Message Protocol (ICMP) traffic destined for the Routing Engine by specifying a list of prefix sources that contain allowed BGP peers.

- [Requirements on page 323](#)
- [Overview on page 324](#)
- [Configuration on page 324](#)
- [Verification on page 326](#)

#### Requirements

No special configuration beyond device initialization is required before configuring this example.

## Overview

In this example, you create a stateless firewall filter that blocks all TCP connection attempts to port 179 from all requesters except BGP peers that have a specified prefix.

A source prefix list, **plist\_bgp179**, is created that specifies the list of source prefixes that contain allowed BGP peers.

The stateless firewall filter **filter\_bgp179** matches all packets from the source prefix list **plist\_bgp179** to the destination port number 179.

## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set policy-options prefix-list plist_bgp179 apply-path "protocols bgp group <*> neighbor <*>"
set firewall family inet filter filter_bgp179 term 1 from source-address 0.0.0.0/0
set firewall family inet filter filter_bgp179 term 1 from source-prefix-list plist_bgp179 except
set firewall family inet filter filter_bgp179 term 1 from destination-port bgp
set firewall family inet filter filter_bgp179 term 1 then reject
set firewall family inet filter filter_bgp179 term 2 then accept
set interfaces lo0 unit 0 family inet filter input filter_bgp179
set interfaces lo0 unit 0 family inet address 127.0.0.1/32
```

### Configure the Filter

### Step-by-Step Procedure

The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the filter:

1. Expand the prefix list **bgp179** to include all prefixes pointed to by the BGP peer group defined by **protocols bgp group <\*> neighbor <\*>**.

```
[edit policy-options prefix-list plist_bgp179]
user@host# set apply-path " protocolsbgp group <*> neighbor <*>"
```

2. Define the filter term that rejects TCP connection attempts to port 179 from all requesters except the specified BGP peers.

```
[edit firewall family inet filter filter_bgp179]
user@host# set term term1 from source-address 0.0.0.0/0
user@host# set term term1 from source-prefix-list bgp179 except
user@host# set term term1 from destination-port bgp
user@host# set term term1 then reject
```

3. Define the other filter term to accept all packets.

```
[edit firewall family inet filter filter_bgp179]
user@host# set term term2 then accept
```

4. Apply the firewall filter to the loopback interface.

```
[edit interfaces lo0 unit 0 family inet]
user@host# set filter input filter_bgp179
user@host# set address 127.0.0.1/32
```

### Results

From configuration mode, confirm your configuration by entering the **show firewall**, **show interfaces**, and **show policy-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show firewall
family inet {
  filter filter_bgp179 {
    term 1 {
      from {
        source-address {
          0.0.0.0/0;
        }
        source-prefix-list {
          plist_bgp179 except;
        }
        destination-port bgp;
      }
      then {
        reject;
      }
    }
    term 2 {
      then {
        accept;
      }
    }
  }
}

user@host# show interfaces
lo0 {
  unit 0 {
    family inet {
      filter {
        input filter_bgp179;
      }
      address 127.0.0.1/32;
    }
  }
}

user@host# show policy-options
prefix-list plist_bgp179 {
  apply-path "protocols bgp group <*> neighbor <*>";
}
```

If you are done configuring the device, enter **commit** from configuration mode.

## Verification

Confirm that the configuration is working properly.

### *Displaying the Firewall Filter Applied to the Loopback Interface*

**Purpose** Verify that the firewall filter **filter\_bgp179** is applied to the IPv4 input traffic at logical interface **lo0.0**.

**Action** Use the **show interfaces statistics operational mode** command for logical interface **lo0.0**, and include the **detail** option. Under the **Protocol inet** section of the command output section, the **Input Filters** field displays the name of the stateless firewall filter applied to the logical interface in the input direction.

```
[edit]
user@host> show interfaces statistics lo0.0 detail
  Logical interface lo0.0 (Index 321) (SNMP ifIndex 16) (Generation 130)
  Flags: SNMP-Traps Encapsulation: Unspecified
  Traffic statistics:
    Input bytes : 0
    Output bytes : 0
    Input packets: 0
    Output packets: 0
  Local statistics:
    Input bytes : 0
    Output bytes : 0
    Input packets: 0
    Output packets: 0
  Transit statistics:
    Input bytes : 0 0 bps
    Output bytes : 0 0 bps
    Input packets: 0 0 pps
    Output packets: 0 0 pps
  Protocol inet, MTU: Unlimited, Generation: 145, Route table: 0
  Flags: Sendbroadcast-pkt-to-re
  Input Filters: filter_bgp179
  Addresses, Flags: Primary
    Destination: Unspecified, Local: 127.0.0.1, Broadcast: Unspecified,
  Generation: 138
```

## Example: Limiting TCP Segment Size for BGP

This example shows how to avoid Internet Control Message Protocol (ICMP) vulnerability issues by limiting TCP segment size when you are using maximum transmission unit (MTU) discovery. Using MTU discovery on TCP paths is one method of avoiding BGP packet fragmentation.

- [Requirements on page 327](#)
- [Overview on page 327](#)
- [Configuration on page 327](#)
- [Verification on page 329](#)
- [Troubleshooting on page 330](#)



## Requirements

No special configuration beyond device initialization is required before you configure this example.

## Overview

TCP negotiates a maximum segment size (MSS) value during session connection establishment between two peers. The MSS value negotiated is primarily based on the maximum transmission unit (MTU) of the interfaces to which the communicating peers are directly connected. However, due to variations in link MTU on the path taken by the TCP packets, some packets in the network that are well within the MSS value might be fragmented when the packet size exceeds the link's MTU.

To configure the TCP MSS value, include the `tcp-mss` statement with a segment size from 1 through 4096.

If the router receives a TCP packet with the SYN bit and the MSS option set, and the MSS option specified in the packet is larger than the MSS value specified by the `tcp-mss` statement, the router replaces the MSS value in the packet with the lower value specified by the `tcp-mss` statement.


The configured MSS value is used as the maximum segment size for the sender. The assumption is that the TCP MSS value used by the sender to communicate with the BGP neighbor is the same as the TCP MSS value that the sender can accept from the BGP neighbor. If the MSS value from the BGP neighbor is less than the MSS value configured, the MSS value from the BGP neighbor is used as the maximum segment size for the sender.

This feature is supported with TCP over IPv4 and TCP over IPv6.

## Topology Diagram

Figure 35 on page 327 shows the topology used in this example.

**Figure 35: TCP Maximum Segment Size for BGP**



## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the `[edit]` hierarchy level.

```

R0    set interfaces fe-1/2/0 unit 1 family inet address 1.1.0.1/30
      set interfaces lo0 unit 1 family inet address 10.255.14.179/32
      set protocols bgp group-int tcp-mss 2020
      set protocols bgp group int type internal

```

```

set protocols bgp group int local-address 10.255.14.179
set protocols bgp group int mtu-discovery
set protocols bgp group int neighbor 10.255.71.24 tcp-mss 2000
set protocols bgp group int neighbor 10.255.14.177
set protocols bgp group int neighbor 10.0.14.4 tcp-mss 4000
set protocols ospf area 0.0.0.0 interface fe-1/2/0.1
set protocols ospf area 0.0.0.0 interface 10.255.14.179
set routing-options autonomous-system 65000

```

**Step-by-Step Procedure** The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Router R0:

1. Configure the interfaces.

```

[edit interfaces]
user@R0# set fe-1/2/0 unit 1 family inet address 1.1.0.1/30
user@R0# set lo0 unit 1 family inet address 10.255.14.179/32

```

2. Configure an interior gateway protocol (IGP), OSPF in this example.

```

[edit protocols ospf area 0.0.0.0]
user@R0# set interface fe-1/2/0.1
user@R0# set interface 10.255.14.179

```

3. Configure one or more BGP groups.

```

[edit protocols bgp group int]
user@R0# set type internal
user@R0# set local-address 10.255.14.179

```

4. Configure MTU discovery to prevent packet fragmentation.

```

[edit protocols bgp group int]
user@R0# set mtu-discovery

```

5. Configure the BGP neighbors, with the TCP MSS set globally for the group or specifically for the various neighbors.

```

[edit protocols bgo group int]
user@R0# set tcp-mss 2020
user@R0# set neighbor 10.255.14.177
user@R0# set neighbor 10.255.71.24 tcp-mss 2000
user@R0# set neighbor 10.0.14.4 tcp-mss 4000

```



**NOTE:** The TCP MSS neighbor setting overrides the group setting.

6. Configure the local autonomous system.

```

[edit routing-options]
user@R0# set autonomous-system 65000

```

**Results** From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R0# show interfaces
fe-1/2/0 {
  unit 1 {
    family inet {
      address 1.1.0.1/30;
    }
  }
}
lo0 {
  unit 1 {
    family inet {
      address 10.255.14.179/32;
    }
  }
}

user@R0# show protocols
bgp {
  group int {
    type internal;
    local-address 10.255.14.179;
    mtu-discovery;
    tcp-mss 2020;
    neighbor 10.255.71.24 {
      tcp-mss 2000;
    }
    neighbor 10.255.14.177;
    neighbor 10.0.14.4 {
      tcp-mss 4000;
    }
  }
}
ospf {
  area 0.0.0.0 {
    interface fe-1/2/0.1;
    interface 10.255.14.179;
  }
}

user@R0# show routing-options
autonomous-system 65000;

```

If you are done configuring the device, enter **commit** from configuration mode.

### Verification

To confirm that the configuration is working properly, run the following commands:

- **show system connections extensive | find <neighbor-address>**, to check the negotiated TCP MSS value.

- **monitor traffic interface**, to monitor BGP traffic and to make sure that the configured TCP MSS value is used as the MSS option in the TCP SYN packet.

## Troubleshooting

- [MSS Calculation with MTU Discovery on page 330](#)

### MSS Calculation with MTU Discovery

**Problem** Consider an example in which two routing devices (R1 and R2) have an internal BGP (IBGP) connection. On both of the routers, the connected interfaces have 4034 as the IPv4 MTU.

```
user@R1# show protocols bgp | display set
[edit]
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 45.45.45.2
set protocols bgp group ibgp mtu-discovery
set protocols bgp group ibgp neighbor 45.45.45.1
```

```
user@R1# run show interfaces xe-0/0/3 extensive | match mtu
```

```
Link-level type: Ethernet, MTU: 4048, LAN-PHY mode, Speed: 10Gbps,
FIFO errors: 0, HS link CRC errors: 0, MTU errors: 0, Resource errors: 0
Protocol inet, MTU: 4034, Generation: 180, Route table: 0
Protocol multiservice, MTU: Unlimited, Generation: 181, Route table: 0
```

In the following packet capture on Device R1, the negotiated MSS is 3994. In the **show system connections extensive** information for MSS, it is set to 2048.

```
05:50:01.575218 Out
  Juniper PCAP Flags [Ext], PCAP Extension(s) total length 16
    Device Media Type Extension TLV #3, length 1, value: Ethernet (1)
    Logical Interface Encapsulation Extension TLV #6, length 1, value:
Ethernet (14)
    Device Interface Index Extension TLV #1, length 2, value: 137
    Logical Interface Index Extension TLV #4, length 4, value: 69
    -----original packet-----
    00:21:59:e1:e8:03 > 00:19:e2:20:79:01, ethertype IPv4 (0x0800), length
78: (tos 0xc0, ttl 64, id 53193, offset 0, flags [DF], proto: TCP (6), length:
64) 45.45.45.2.62840 > 45.45.45.1.bgp: S 2939345813:2939345813(0) win 16384 **mss
3994,nop,wscale 0,nop,nop,timestamp 70559970 0,sackOK,eol>
05:50:01.575875 In
  Juniper PCAP Flags [Ext, no-L2, In], PCAP Extension(s) total length 16
    Device Media Type Extension TLV #3, length 1, value: Ethernet (1)
    Logical Interface Encapsulation Extension TLV #6, length 1, value:
Ethernet (14)
    Device Interface Index Extension TLV #1, length 2, value: 137
    Logical Interface Index Extension TLV #4, length 4, value: 69
    -----original packet-----
    PFE proto 2 (ipv4): (tos 0xc0, ttl 255, id 37709, offset 0, flags [DF], proto:
TCP (6), length: 64) 45.45.45.1.bgp > 45.45.45.2.62840: S 2634967984:2634967984(0)
ack 2939345814 win 16384 **mss 3994,nop,wscale 0,nop,nop,timestamp 174167273
70559970,sackOK,eol>
```

```
user@R1# run show system connections extensive | find 45.45
```

```
tcp4      0      0  45.45.45.2.62840          45.45.45.1.179
                        ESTABLISHED
```

```

sndsbcc:          0 sndsbmbcnt:          0 sndsbmbmax:      131072
sndsblowat:       2048 sndsbhiwat:       16384
rcvsbcc:          0 rcvsbmbcnt:          0 rcvsbmbmax:      131072
rcvsblowat:       1 rcvsbhiwat:       16384
proc id:         19725 proc name:         rpd
  iss: 2939345813   sndup: 2939345972
snduna: 2939345991   sndnxt: 2939345991   sndwnd:      16384
sndmax: 2939345991   sndcwnd:      10240 sndssthresh: 1073725440
  irs: 2634967984   rcvup: 2634968162
rcvnxt: 2634968162   rcvadv: 2634984546   rcvwnd:      16384
  rtt:      0       srtt:      1538       rttv:      1040
rxtcur:      1200   rxtshift:      0       rtseq: 2939345972
rttmin:      1000   mss:          2048

```

**Solution** This is expected behavior with Junos OS. The MSS value is equal to the MTU value minus the IP or IPv6 and TCP headers. This means that the MSS value is generally 40 bytes less than the MTU (for IPv4) and 60 bytes less than the MTU (for IPv6). This value is negotiated between the peers. In this example, it is  $4034 - 40 = 3994$ . Junos OS then rounds this value to a multiple of 2 KB. The value is  $3994 / 2048 * 2048 = 2048$ . So it is not necessary to see same MSS value with in the **show system connections** output.

$3994 / 2048 = 1.95$

1.95 is rounded to 1.

$1 * 2048 = 2048$

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)



## CHAPTER 9

# BGP Flap Configuration

- [Example: Preventing BGP Session Resets on page 333](#)
- [Examples: Configuring BGP Flap Damping on page 340](#)

### Example: Preventing BGP Session Resets

---

- [Understanding BGP Session Resets on page 333](#)
- [Example: Preventing BGP Session Flaps When VPN Families Are Configured on page 333](#)

### Understanding BGP Session Resets

Certain configuration actions and events cause BGP sessions to be reset (dropped and then reestablished).

If you configure both route reflection and VPNs on the same routing device, the following modifications to the route reflection configuration cause current BGP sessions to be reset:

- Adding a cluster ID—If a BGP session shares the same autonomous system (AS) number with the group where you add the cluster ID, all BGP sessions are reset regardless of whether the BGP sessions are contained in the same group.
- Creating a new route reflector—If you have an internal BGP (IBGP) group with an AS number and create a new route reflector group with the same AS number, all BGP sessions in the IBGP group and the new route reflector group are reset.
- Changing configuration statements that affect BGP peers, such as renaming a BGP group, resets the BGP sessions.
- If you change the address family specified in the **[edit protocols bgp family]** hierarchy level, all current BGP sessions on the routing device are dropped and then reestablished.

### Example: Preventing BGP Session Flaps When VPN Families Are Configured

This example shows a workaround for a known issue in which BGP sessions sometimes go down and then come back up (in other words, flap) when virtual private network (VPN) families are configured. If any VPN family (for example, **inet-vpn**, **inet6-vpn**, **inet-mpvn**, **inet-mdt**, **inet6-mpvn**, **l2vpn**, **iso-vpn**, and so on) is configured on a BGP master instance, a flap of either a route reflector (RR) internal BGP (IBGP) session or an external

BGP (EBGP) session causes flaps of other BGP sessions configured with the same VPN family.

- [Requirements on page 334](#)
- [Overview on page 335](#)
- [Configuration on page 336](#)
- [Verification on page 339](#)

## Requirements

---

Before you begin:

- Configure router interfaces.
- Configure an interior gateway protocol (IGP).
- Configure BGP.
- Configure VPNs.



## Overview

When a router or switch is configured as either a route reflector (RR) or an AS boundary router (an external BGP peer) and a VPN family (for example, the **family inet-vpn unicast** statement) is configured, a flap of either the RR IBGP session or the EBGP session causes flaps of all other BGP sessions that are configured with the **family inet-vpn unicast** statement. This example shows how to prevent these unnecessary session flaps.

The reason for the flapping behavior is related to BGP operation in Junos OS when originating VPN routes.

BGP has the following two modes of operation with respect to originating VPN routes:

- If BGP does not need to propagate VPN routes because the session has no EBGP peer and no RR clients, BGP exports VPN routes directly from the *instance.inet.0* routing table to other PE routers. This behavior is efficient in that it avoids the creation of two copies of many routes (one in the *instance.inet.0* table and one in the *bgp.l3vpn.0* table).
- If BGP does need to propagate VPN routes because the session has an EBGP peer or RR clients, BGP first exports the VPN routes from the *instance.inet.0* table to the *bgp.l3vpn.0* table. Then BGP exports the routes to other PE routers. In this scenario, two copies of the route are needed to enable best-route selection. A PE router might receive the same VPN route from a CE device and also from an RR client or EBGP peer.



**NOTE:** The route export is not performed if the route in *instance.inet.0* is a secondary route. In Junos OS, a route is only exported one time from one routing table as a primary route to another routing table as a secondary route. Because the route in *instance.inet.0* is already a secondary route, it is not allowed to be moved again to the *bgp.l3vpn.0* table, as needed to be advertised. The route does not reach the *bgp.l3vpn.0* table and thus is not advertised. One workaround is to send the routes that should be advertised to *inet.0* so that they are advertised.

When, because of a configuration change, BGP transitions from needing two copies of a route to not needing two copies of a route (or the reverse), all sessions over which VPN routes are exchanged go down and then come back up. Although this example focuses on the **family inet-vpn unicast** statement, the concept applies to all VPN network layer reachability information (NLRI) families. This issue impacts logical systems as well. All BGP sessions in the master instance related to the VPN NLRI family are brought down to implement the table advertisement change for the VPN NLRI family. Changing an RR to a non-RR or the reverse (by adding or removing the **cluster** statement) causes the table advertisement change. Also, configuring the first EBGP session or removing the EBGP session from the configuration in the master instance for a VPN NLRI family causes the table advertisement change.

The way to prevent these unnecessary session flaps is to configure an extra RR client or EBGP session as a passive session with a neighbor address that does not exist. This example focuses on the EBGP case, but the same workaround works for the RR case.

When a session is passive, the routing device does not send Open requests to a peer. Once you configure the routing device to be passive, the routing device does not originate the TCP connection. However, when the routing device receives a connection from the peer and an Open message, it replies with another BGP Open message. Each routing device declares its own capabilities.

Figure 36 on page 336 shows the topology for the EBGp case. Router R1 has an IBGP session with Routers R2 and R3 and an EBGp session with Router R4. All sessions have the **family inet-vpn unicast** statement configured. If the R1-R4 EBGp session flaps, the R1-R2 and R1-R3 BGP sessions flap also.

Figure 36: Topology for the EBGp Case





Figure 37 on page 336 shows the topology for the RR case. Router R1 is the RR, and Router R3 is the client. Router R1 has IBGP sessions with Routers R2 and R3. All sessions have the **family inet-vpn unicast** statement configured. If the R1-R3 session flaps, the R1-R2 and R1-R4 sessions flap also.

Figure 37: Topology for the RR Case



## Configuration

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network

configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set protocols bgp family inet-vpn unicast
set protocols bgp family l2vpn signaling
set protocols bgp group R1-R4 type external
set protocols bgp group R1-R4 local-address 4.4.4.2
set protocols bgp group R1-R4 neighbor 4.4.4.1 peer-as 200
set protocols bgp group R1-R2-R3 type internal
set protocols bgp group R1-R2-R3 log-updown
set protocols bgp group R1-R2-R3 local-address 15.15.15.15
set protocols bgp group R1-R2-R3 neighbor 12.12.12.12
set protocols bgp group R1-R2-R3 neighbor 13.13.13.13
set protocols bgp group Fake type external
set protocols bgp group Fake passive
set protocols bgp group Fake neighbor 100.100.100.100 peer-as 500
```

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the EBGp scenario:

1. Configure one or more VPN families.

```
[edit protocols bgp]
user@R1# set family inet-vpn unicast
user@R1# set family l2vpn signaling
```

2. Configure the EBGp session.

```
[edit protocols bgp]
user@R1# set group R1-R4 type external
user@R1# set group R1-R4 local-address 4.4.4.2
user@R1# set group R1-R4 neighbor 4.4.4.1 peer-as 200
```

3. Configure the IBGP sessions.

```
[edit protocols bgp]
user@R1# set group R1-R2-R3 type internal
user@R1# set group R1-R2-R3 local-address 15.15.15.15
user@R1# set group R1-R2-R3 neighbor 12.12.12.12
user@R1# set group R1-R2-R3 neighbor 13.13.13.13
```

4. (Optional) Configure BGP so that it generates a **syslog** message whenever a BGP peer makes a state transition.

```
[edit protocols bgp]
user@R1# set group R1-R2-R3 log-updown
```

Enabling the **log-updown** statement causes BGP state transitions to be logged at **warning** level.

**Step-by-Step Procedure** To verify that unnecessary session flaps are occurring:

1. Run the **show bgp summary** command to verify that the sessions have been established.

```

user@R1> show bgp summary
Groups: 2 Peers: 3 Down peers: 0
Table      Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 0      0      0      0      0      0      0
bgp.12vpn.0 0      0      0      0      0      0      0
inet.0      0      0      0      0      0      0      0
Peer      AS  InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
4.4.4.1    200 6      5      0      0      1:08 Establ
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0
12.12.12.12 100 3      7      0      0      1:18 Establ
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0
13.13.13.13 100 3      6      0      0      1:14 Establ
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0

```

2. Deactivate the EBGp session.

```

user@R1# deactivate group R1-R4
user@R1# commit

```

```

Mar 10 18:27:40 R1: rpd[1464]: bgp_peer_delete:6589: NOTIFICATION sent to 4.4.4.1 (External AS 200): code
6 (Cease) subcode 3 (Peer Unconfigured), Reason: Peer Deletion
Mar 10 18:27:40 R1: rpd[1464]: bgp_adv_main_update:7253: NOTIFICATION sent to 12.12.12.12 (Internal AS
100): code 6 (Cease) subcode 6 (Other Configuration Change), Reason: Configuration change - VPN table
advertise
Mar 10 18:27:40 R1: rpd[1464]: bgp_adv_main_update:7253: NOTIFICATION sent to 13.13.13.13 (Internal AS
100): code 6 (Cease) subcode 6 (Other Configuration Change), Reason: Configuration change - VPN table
advertise

```

3. Run the **show bgp summary** command to view the session flaps.

```

user@R1> show bgp summary
Groups: 1 Peers: 2 Down peers: 2
Table      Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 0      0      0      0      0      0      0
bgp.12vpn.0 0      0      0      0      0      0      0
inet.0      0      0      0      0      0      0      0
Peer      AS  InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
12.12.12.12 100 4      9      0      1      19 Active
13.13.13.13 100 4      8      0      1      19 Active

user@R1> show bgp summary
Groups: 1 Peers: 2 Down peers: 0
Table      Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 0      0      0      0      0      0      0
bgp.12vpn.0 0      0      0      0      0      0      0
inet.0      0      0      0      0      0      0      0
Peer      AS  InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
12.12.12.12 100 2      3      0      1      0 Establ
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0
13.13.13.13 100 2      3      0      1      0 Establ
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0

```

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To prevent unnecessary BGP session flaps:

1. Add a passive EBGp session with a neighbor address that does not exist in the peer autonomous system (AS).

```
[edit protocols bgp]
user@R1# set group Fake type external
user@R1# set group Fake passive
user@R1# set neighbor 100.100.100.100 peer-as 500
```

2. Run the **show bgp summary** command to verify that the real sessions have been established and the passive session is idle.

```
user@R1> show bgp summary
Groups: 3 Peers: 4 Down peers: 1
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 0 0 0 0 0 0
bgp.12vpn.0 0 0 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
4.4.4.1 200 9500 9439 0 0 2d 23:14:23 Estab1
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0
12.12.12.12 100 10309 10239 0 0 3d 5:17:49 Estab1
bgp.13vpn.0: 0/0/0/0
13.13.13.13 100 10306 10241 0 0 3d 5:18:25 Estab1
bgp.13vpn.0: 0/0/0/0
100.100.100.100 500 0 0 0 0 2d 23:38:52 Idle
```

### Verification

Confirm that the configuration is working properly.

- [Bringing Down the EBGp Session on page 339](#)
- [Verifying That the IBGP Sessions Remain Up on page 339](#)

#### *Bringing Down the EBGp Session*

**Purpose** Try to cause the flap issue after the workaround is configured.

**Action** user@R1# deactivate group R1-R4  
user@R1# commit

#### *Verifying That the IBGP Sessions Remain Up*

**Purpose** Make sure that the IBGP sessions do not flap after the EBGp session is deactivated.

**Action** user@R1> show bgp summary

```

Groups: 2 Peers: 3 Down peers: 1
Table      Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 0      0      0      0      0      0      0
bgp.12vpn.0 0      0      0      0      0      0      0
Peer      AS  InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
12.12.12.12 100 10312 10242 0 0 3d 5:19:01 Establ
bgp.13vpn.0: 0/0/0/0
13.13.13.13 100 10309 10244 0 0 3d 5:19:37 Establ
bgp.13vpn.0: 0/0/0/0
100.100.100.100 500 0 0 0 2d 23:40:04 Idle

```

## user@R1&gt; show bgp summary

```

Groups: 3 Peers: 4 Down peers: 1
Table      Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 0      0      0      0      0      0      0
bgp.12vpn.0 0      0      0      0      0      0      0
Peer      AS  InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
4.4.4.1    200 5 4 0 0 28      Establ
bgp.13vpn.0: 0/0/0/0
bgp.12vpn.0: 0/0/0/0
12.12.12.12 100 10314 10244 0 0 3d 5:19:55 Establ
bgp.13vpn.0: 0/0/0/0
13.13.13.13 100 10311 10246 0 0 3d 5:20:31 Establ
bgp.13vpn.0: 0/0/0/0
100.100.100.100 500 0 0 0 2d 23:40:58 Idle

```

- Related Documentation**
- [Understanding External BGP Peering Sessions on page 13](#)
  - [BGP Configuration Overview](#)

## Examples: Configuring BGP Flap Damping

- [Understanding Damping Parameters on page 340](#)
- [Example: Configuring BGP Route Flap Damping Parameters on page 341](#)
- [Example: Configuring BGP Route Flap Damping Based on the MBGP MVPN Address Family on page 350](#)

### Understanding Damping Parameters

BGP *route flapping* describes the situation in which BGP systems send an excessive number of update messages to advertise network reachability information. BGP *flap damping* is a method of reducing the number of update messages sent between BGP peers, thereby reducing the load on these peers, without adversely affecting the route convergence time for stable routes.

Flap damping reduces the number of update messages by marking routes as ineligible for selection as the active or preferable route. Marking routes in this way leads to some delay, or *suppression*, in the propagation of route information, but the result is increased network stability. You typically apply flap damping to external BGP (EBGP) routes (routes in different ASs). You can also apply flap damping within a confederation, between

confederation member ASs. Because routing consistency within an AS is important, do not apply flap damping to internal BGP (IBGP) routes. (If you do, it is ignored.) The exception to this rule is when flap damping is applied at the address family level, which is supported in Junos OS Release 12.2 and later. When you apply flap damping at the address family level, it works for both IBGP and EBGP.

By default, route flap damping is not enabled. Damping is applied to external peers and to peers at confederation boundaries.

When you enable damping, default parameters are applied, as summarized in [Table 5 on page 341](#).

**Table 5: Damping Parameters**

| Damping Parameter                  | Description                                                                                                             | Default Value | Possible Values  |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------|---------------|------------------|
| <b>half-life <i>minutes</i></b>    | Decay half-life—Number of minutes after which an arbitrary value is halved if a route stays stable.                     | 15 (minutes)  | 1 through 45     |
| <b>max-suppress <i>minutes</i></b> | Maximum hold-down time for a route, in minutes.                                                                         | 60 (minutes)  | 1 through 720    |
| <b>reuse</b>                       | Reuse threshold—Arbitrary value below which a suppressed route can be used again.                                       | 750           | 1 through 20,000 |
| <b>suppress</b>                    | Cutoff (suppression) threshold—Arbitrary value above which a route can no longer be used or included in advertisements. | 3000          | 1 through 20,000 |

To change the default BGP flap damping values, you define actions by creating a named set of damping parameters and including it in a routing policy with the damping action. For the damping routing policy to work, you also must enable BGP route flap damping.

### Example: Configuring BGP Route Flap Damping Parameters

This example shows how to configure damping parameters.

- [Requirements on page 341](#)
- [Overview on page 341](#)
- [Configuration on page 342](#)
- [Verification on page 346](#)

#### Requirements

Before you begin, configure router interfaces and configure routing protocols.

#### Overview

This example has three routing devices. Device R2 has external BGP (EBGP) connections with Device R1 and Device R3.

Device R1 and Device R3 have some static routes configured for testing purposes, and these static routes are advertised through BGP to Device R2.


Device R2 damps routes received from Device R1 and Device R3 according to these criteria:

- Damp all prefixes with a mask length equal to or greater than 17 more aggressively than routes with a mask length between 9 and 16.
- Damp routes with a mask length between 0 and 8, inclusive, less than routes with a mask length greater than 8.
- Do not damp the 10.128.0.0/9 prefix at all.

The routing policy is evaluated when routes are being exported from the routing table into the forwarding table. Only the active routes are exported from the routing table.

Figure 38 on page 342 shows the sample network.

**Figure 38: BGP Flap Damping Topology**



“CLI Quick Configuration” on page 342 shows the configuration for all of the devices in Figure 38 on page 342.

The section “Step-by-Step Procedure” on page 343 describes the steps on Device R2.

### Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

**Device R1**

```

set interfaces fe-1/2/0 unit 0 family inet address 10.0.0.1/30
set interfaces lo0 unit 0 family inet address 192.168.0.1/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct-and-static
set protocols bgp group ext peer-as 200
set protocols bgp group ext neighbor 10.0.0.2
set policy-options policy-statement send-direct-and-static term 1 from protocol direct
set policy-options policy-statement send-direct-and-static term 1 from protocol static
set policy-options policy-statement send-direct-and-static term 1 then accept
set routing-options static route 172.16.0.0/16 reject
set routing-options static route 172.16.128.0/17 reject
set routing-options static route 172.16.192.0/20 reject
set routing-options static route 10.0.0.0/9 reject
set routing-options static route 172.16.233.0/7 reject
set routing-options static route 10.224.0.0/11 reject
set routing-options static route 0.0.0.0/0 reject
set routing-options autonomous-system 100
  
```

**Device R2**

```

set interfaces fe-1/2/0 unit 0 family inet address 10.0.0.2/30
  
```



```

set interfaces fe-1/2/1 unit 0 family inet address 10.1.0.1/30
set interfaces lo0 unit 0 family inet address 192.168.0.2/32
set protocols bgp damping
set protocols bgp group ext type external
set protocols bgp group ext import damp
set protocols bgp group ext export send-direct
set protocols bgp group ext neighbor 10.0.0.1 peer-as 100
set protocols bgp group ext neighbor 10.1.0.2 peer-as 300
set policy-options policy-statement damp term 1 from route-filter 10.128.0.0/9 exact
damping dry
set policy-options policy-statement damp term 1 from route-filter 0.0.0.0/0
prefix-length-range /0-/8 damping timid
set policy-options policy-statement damp term 1 from route-filter 0.0.0.0/0
prefix-length-range /17-/32 damping aggressive
set policy-options policy-statement send-direct term 1 from protocol direct
set policy-options policy-statement send-direct term 1 then accept
set policy-options damping aggressive half-life 30
set policy-options damping aggressive suppress 2500
set policy-options damping timid half-life 5
set policy-options damping dry disable
set routing-options autonomous-system 200

```

**Device R3**

```

set interfaces fe-1/2/1 unit 0 family inet address 10.1.0.2/30
set interfaces lo0 unit 0 family inet address 192.168.0.3/32
set protocols bgp group ext type external
set protocols bgp group ext export send-direct-and-static
set protocols bgp group ext peer-as 200
set protocols bgp group ext neighbor 10.1.0.1
set policy-options policy-statement send-direct-and-static term 1 from protocol direct
set policy-options policy-statement send-direct-and-static term 1 from protocol static
set policy-options policy-statement send-direct-and-static term 1 then accept
set routing-options static route 10.128.0.0/9 reject
set routing-options autonomous-system 300

```

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure damping parameters:

1. Configure the interfaces.

```

[edit interfaces]
user@R2# set fe-1/2/0 unit 0 family inet address 10.0.0.2/30

user@R2# set fe-1/2/1 unit 0 family inet address 10.1.0.1/30

user@R2# set lo0 unit 0 family inet address 192.168.0.2/32

```

2. Configure the BGP neighbors.

```

[edit protocols bgp group ext]
user@R2# set type external
user@R2# set neighbor 10.0.0.1 peer-as 100
user@R2# set neighbor 10.1.0.2 peer-as 300

```

3. Create and configure the damping parameter groups.

```
[edit policy-options]
user@R2# set damping aggressive half-life 30
user@R2# set damping aggressive suppress 2500
user@R2# set damping timid half-life 5
user@R2# set damping dry disable
```

4. Configure the damping policy.

```
[edit policy-options policy-statement damp term 1]
user@R2# set from route-filter 10.128.0.0/9 exact damping dry
user@R2# set from route-filter 0.0.0.0/0 prefix-length-range /0-/8 damping timid
user@R2# set from route-filter 0.0.0.0/0 prefix-length-range /17-/32 damping
    aggressive
```

5. Enable damping for BGP.

```
[edit protocols bgp]
user@R2# set damping
```

6. Apply the policy as an import policy for the BGP neighbor.

```
[edit protocols bgp group ext]
user@R2# set import damp
```



**NOTE:** You can refer to the same routing policy one or more times in the same or different import statements.

7. Configure an export policy.

```
[edit policy-options policy-statement send-direct term 1]
user@R2# set from protocol direct
user@R2# set then accept
```

8. Apply the export policy.

```
[edit protocols bgp group ext]
user@R2# set export send-direct
```

9. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@R2# set autonomous-system 200
```

**Results** From configuration mode, confirm your configuration by issuing the **show interfaces**, **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
fe-1/2/0 {
  unit 0 {
    family inet {
      address 10.0.0.2/30;
    }
  }
}
```

```

    }
  }
  fe-1/2/1 {
    unit 0 {
      family inet {
        address 10.1.0.1/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 192.168.0.2/32;
      }
    }
  }
}

user@R2# show protocols
bgp {
  damping;
  group ext {
    type external;
    import damp;
    export send-direct;
    neighbor 10.0.0.1 {
      peer-as 100;
    }
    neighbor 10.1.0.2 {
      peer-as 300;
    }
  }
}

user@R2# show policy-options
policy-statement damp {
  term 1 {
    from {
      route-filter 10.128.0.0/9 exact damping dry;
      route-filter 0.0.0.0/0 prefix-length-range /0-/8 damping timid;
      route-filter 0.0.0.0/0 prefix-length-range /17-/32 damping aggressive;
    }
  }
}
policy-statement send-direct {
  term 1 {
    from protocol direct;
    then accept;
  }
}
damping aggressive {
  half-life 30;
  suppress 2500;
}
damping timid {
  half-life 5;
}
damping dry {

```

```
disable;
}

user@R2# show routing-options
autonomous-system 200;
```

If you are done configuring the device, enter **commit** from configuration mode.

---

### Verification

Confirm that the configuration is working properly.

- [Causing Some Routes to Flap on page 346](#)
- [Checking the Route Flaps on page 346](#)
- [Verifying Route Flap Damping on page 347](#)
- [Displaying the Details of a Damped Route on page 348](#)
- [Verifying That Default Damping Parameters Are in Effect on page 348](#)
- [Filtering the Damping Information on page 349](#)

#### *Causing Some Routes to Flap*

**Purpose** To verify your route flap damping policy, some routes must flap. Having a live Internet feed almost guarantees that a certain number of route flaps will be present. If you have control over a remote system that is advertising the routes, you can modify the advertising router's policy to effect the advertisement and withdrawal of all routes or of a given prefix. In a test environment, you can cause routes to flap by clearing the BGP neighbors or by restarting the routing process on the BGP neighbors, as shown here.

**Action** From operational mode on Device R1 and Device R3, enter the **restart routing** command.



**CAUTION:** Use this command cautiously in a production network.

---

```
user@R1> restart routing
```

```
R1 started, pid 10474
```

```
user@R3> restart routing
```

```
R3 started, pid 10478
```

**Meaning** On Device R2, all of the routes from the neighbors are withdrawn and re-advertised.

#### *Checking the Route Flaps*

**Purpose** View the number of neighbor flaps.

**Action** From operational mode, enter the **show bgp summary** command.

```
user@R2> show bgp summary
```

```

Groups: 1 Peers: 2 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State  Pending
inet.0
          12         1         11         0         11         0
Peer      AS      InPkt    OutPkt    OutQ    Flaps  Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.0.0.1   100         10         10         0         4        2:50
0/9/0/9    0/0/0/0
10.1.0.2   300         10         10         0         4        2:53
1/3/1/2    0/0/0/0

```

**Meaning** This output was captured after the routing process was restarted on Device R2's neighbors four times.

### *Verifying Route Flap Damping*

**Purpose** Verify that routes are being hidden due to damping.

**Action** From operational mode, enter the **show route damping suppressed** command.

```
user@R2> show route damping suppressed
```

```
inet.0: 15 destinations, 17 routes (6 active, 0 holddown, 11 hidden)
+ = Active Route, - = Last Active, * = Both
```

```

0.0.0.0/0      [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
10.0.0.0/9     [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
10.0.0.0/30    [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
10.1.0.0/30    [BGP ] 00:00:15, localpref 100
                AS path: 300 I, validation-state: unverified
                > to 10.1.0.2 via fe-1/2/1.0
10.224.0.0/11  [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
172.16.0.0/16  [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
172.16.128.0/17 [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
172.16.192.0/20 [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
192.168.0.1/32 [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0
192.168.0.3/32 [BGP ] 00:00:15, localpref 100
                AS path: 300 I, validation-state: unverified
                > to 10.1.0.2 via fe-1/2/1.0
172.16.233.0/7 [BGP ] 00:00:12, localpref 100
                AS path: 100 I, validation-state: unverified
                > to 10.0.0.1 via fe-1/2/0.0

```

**Meaning** The output shows some routing instability. Eleven routes are hidden due to damping.

#### *Displaying the Details of a Damped Route*

**Purpose** Display the details of damped routes.

**Action** From operational mode, enter the **show route damping suppressed 172.16.192.0/20 detail** command.

```
user@R2> show route damping suppressed 172.16.192.0/20 detail

inet.0: 15 destinations, 17 routes (6 active, 0 holddown, 11 hidden)
172.16.192.0/20 (1 entry, 0 announced)
    BGP                /-101
        Next hop type: Router, Next hop index: 758
        Address: 0x9414484
        Next-hop reference count: 9
        Source: 10.0.0.1
        Next hop: 10.0.0.1 via fe-1/2/0.0, selected
        Session Id: 0x100201
        State: <Hidden Ext>
        Local AS: 200 Peer AS: 100
        Age: 52
        Validation State: unverified
        Task: BGP_100.10.0.0.1+55922
        AS path: 100 I
        Localpref: 100
        Router ID: 192.168.0.1
        Merit (last update/now): 4278/4196
        damping-parameters: aggressive
        Last update: 00:00:52 First update: 01:01:55
        Flaps: 8
        Suppressed. Reusable in: 01:14:40
        Preference will be: 170
```

**Meaning** This output indicates that the displayed route has a mask length that is equal to or greater than /17, and confirms that it has been correctly mapped to the aggressive damping profile. You can also see the route's current (and last) figure of merit value, and when the route is expected to become active if it remains stable.

#### *Verifying That Default Damping Parameters Are in Effect*

**Purpose** Locating a damped route with a /16 mask confirms that the default parameters are in effect.

**Action** From operational mode, enter the **show route damping suppressed detail | match 0/16** command.

```
user@R2> show route damping suppressed detail | match 0/16

172.16.0.0/16 (1 entry, 0 announced)

user@R2> show route damping suppressed 172.16.0.0/16 detail

inet.0: 15 destinations, 17 routes (6 active, 0 holddown, 11 hidden)
172.16.0.0/16 (1 entry, 0 announced)
```

```

BGP                               /-101
Next hop type: Router, Next hop index: 758
Address: 0x9414484
Next-hop reference count: 9
Source: 10.0.0.1
Next hop: 10.0.0.1 via fe-1/2/0.0, selected
Session Id: 0x100201
State: <Hidden Ext>
Local AS: 200 Peer AS: 100
Age: 1:58
Validation State: unverified
Task: BGP_100.10.0.0.1+55922
AS path: 100 I
Localpref: 100
Router ID: 192.168.0.1
Merit (last update/now): 3486/3202
Default damping parameters used
Last update: 00:01:58 First update: 01:03:01
Flaps: 8
Suppressed. Reusable in: 00:31:40
Preference will be: 170

```

**Meaning** Routes with a /16 mask are not impacted by the custom damping rules. Therefore, the default damping rules are in effect.

To repeat, the custom rules are as follows:

- Damp all prefixes with a mask length equal to or greater than 17 more aggressively than routes with a mask length between 9 and 16.
- Damp routes with a mask length between 0 and 8, inclusive, less than routes with a mask length greater than 8.
- Do not damp the 10.128.0.0/9 prefix at all.

#### *Filtering the Damping Information*

**Purpose** Use OR groupings or cascaded piping to simplify the determination of what damping profile is being used for routes with a given mask length.

**Action** From operational mode, enter the **show route damping suppressed** command.

```
user@R2> show route damping suppressed detail | match "0 announced | damp"
```

```

0.0.0.0/0 (1 entry, 0 announced)
    damping-parameters: timid
10.0.0.0/9 (1 entry, 0 announced)
    Default damping parameters used
    damping-parameters: aggressive
    damping-parameters: aggressive
10.224.0.0/11 (1 entry, 0 announced)
    Default damping parameters used
172.16.0.0/16 (1 entry, 0 announced)
    Default damping parameters used
172.16.128.0/17 (1 entry, 0 announced)
    damping-parameters: aggressive
172.16.192.0/20 (1 entry, 0 announced)
    damping-parameters: aggressive
192.168.0.1/32 (1 entry, 0 announced)

```

```

damping-parameters: aggressive
192.168.0.3/32 (1 entry, 0 announced)
damping-parameters: aggressive
172.16.233.0/7 (1 entry, 0 announced)
damping-parameters: timid

```

**Meaning** When you are satisfied that your EBGp routes are correctly associated with a damping profile, you can issue the **clear bgp damping** operational mode command to restore an active status to your damped routes, which will return your connectivity to normal operation.

### Example: Configuring BGP Route Flap Damping Based on the MBGP MVPN Address Family

This example shows how to configure an multiprotocol BGP multicast VPN (also called Next-Generation MVPN) with BGP route flap damping.

- [Requirements on page 350](#)
- [Overview on page 350](#)
- [Configuration on page 351](#)
- [Verification on page 358](#)

#### Requirements

This example uses Junos OS Release 12.2. BGP route flap damping support for MBGP MVPN, specifically, and on an address family basis, in general, is introduced in Junos OS Release 12.2.


#### Overview

BGP route flap damping helps to diminish route instability caused by routes being repeatedly withdrawn and readvertised when a link is intermittently failing.

This example uses the default damping parameters and demonstrates an MBGP MVPN scenario with three provider edge (PE) routing devices, three customer edge (CE) routing devices, and one provider (P) routing device.

[Figure 39 on page 350](#) shows the topology used in this example.

**Figure 39: MBGP MVPN with BGP Route Flap Damping**





On PE Device R4, BGP route flap damping is configured for address family **inet-mvpn**. A routing policy called **dampPolicy** uses the **nlri-route-type** match condition to damp only MVPN route types 3, 4, and 5. All other MVPN route types are not damped.

This example shows the full configuration on all devices in the “[CLI Quick Configuration](#)” on page 351 section. The “[Configuring Device R4](#)” on page 354 section shows the step-by-step configuration for PE Device R4.

### Configuration

**CLI Quick Configuration** To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```

Device R1    set interfaces ge-1/2/0 unit 1 family inet address 10.1.1.1/30
              set interfaces ge-1/2/0 unit 1 family mpls
              set interfaces lo0 unit 1 family inet address 172.16.1.1/32
              set protocols ospf area 0.0.0.0 interface lo0.1 passive
              set protocols ospf area 0.0.0.0 interface ge-1/2/0.1
              set protocols pim rp static address 172.16.100.1
              set protocols pim interface all
              set routing-options router-id 172.16.1.1

Device R2    set interfaces ge-1/2/0 unit 2 family inet address 10.1.1.2/30
              set interfaces ge-1/2/0 unit 2 family mpls
              set interfaces ge-1/2/1 unit 5 family inet address 10.1.1.5/30
              set interfaces ge-1/2/1 unit 5 family mpls
              set interfaces vt-1/2/0 unit 2 family inet
              set interfaces lo0 unit 2 family inet address 172.16.1.2/32
              set interfaces lo0 unit 102 family inet address 172.16.100.1/32
              set protocols mpls interface ge-1/2/1.5
              set protocols bgp group ibgp type internal
              set protocols bgp group ibgp local-address 172.16.1.2
              set protocols bgp group ibgp family inet-vpn any
              set protocols bgp group ibgp family inet-mvpn signaling
              set protocols bgp group ibgp neighbor 172.16.1.4
              set protocols bgp group ibgp neighbor 172.16.1.5
              set protocols ospf area 0.0.0.0 interface lo0.2 passive
              set protocols ospf area 0.0.0.0 interface ge-1/2/1.5
              set protocols ldp interface ge-1/2/1.5
              set protocols ldp p2mp
              set policy-options policy-statement parent_vpn_routes from protocol bgp
              set policy-options policy-statement parent_vpn_routes then accept
              set routing-instances vpn-1 instance-type vrf
              set routing-instances vpn-1 interface ge-1/2/0.2
              set routing-instances vpn-1 interface vt-1/2/0.2
              set routing-instances vpn-1 interface lo0.102
              set routing-instances vpn-1 route-distinguisher 100:100
              set routing-instances vpn-1 provider-tunnel ldp-p2mp
              set routing-instances vpn-1 vrf-target target:1:1
              set routing-instances vpn-1 protocols ospf export parent_vpn_routes
              set routing-instances vpn-1 protocols ospf area 0.0.0.0 interface lo0.102 passive
              set routing-instances vpn-1 protocols ospf area 0.0.0.0 interface ge-1/2/0.2
              set routing-instances vpn-1 protocols pim rp static address 172.16.1.2 with 172.16.4.1100.1

```

```
set routing-instances vpn-1 protocols pim interface ge-1/2/0.2 mode sparse
set routing-instances vpn-1 protocols mvpn
set routing-options router-id 172.16.1.2
set routing-options autonomous-system 1001
```

Device R3

```
set interfaces ge-1/2/0 unit 6 family inet address 10.1.1.6/30
set interfaces ge-1/2/0 unit 6 family mpls
set interfaces ge-1/2/1 unit 9 family inet address 10.1.1.9/30
set interfaces ge-1/2/1 unit 9 family mpls
set interfaces ge-1/2/2 unit 13 family inet address 10.1.1.13/30
set interfaces ge-1/2/2 unit 13 family mpls
set interfaces lo0 unit 3 family inet address 172.16.1.3/32
set protocols mpls interface ge-1/2/0.6
set protocols mpls interface ge-1/2/1.9
set protocols mpls interface ge-1/2/2.13
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ospf area 0.0.0.0 interface ge-1/2/0.6
set protocols ospf area 0.0.0.0 interface ge-1/2/1.9
set protocols ospf area 0.0.0.0 interface ge-1/2/2.13
set protocols ldp interface ge-1/2/0.6
set protocols ldp interface ge-1/2/1.9
set protocols ldp interface ge-1/2/2.13
set protocols ldp p2mp
set routing-options router-id 172.16.1.3
```

Device R4

```
set interfaces ge-1/2/0 unit 10 family inet address 10.1.1.10/30
set interfaces ge-1/2/0 unit 10 family mpls
set interfaces ge-1/2/1 unit 17 family inet address 10.1.1.17/30
set interfaces ge-1/2/1 unit 17 family mpls
set interfaces vt-1/2/0 unit 4 family inet
set interfaces lo0 unit 4 family inet address 172.16.1.4/32
set interfaces lo0 unit 104 family inet address 172.16.100.1/32
set protocols rsvp interface all aggregate
set protocols mpls interface all
set protocols mpls interface ge-1/2/0.10
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 172.16.1.4
set protocols bgp group ibgp family inet-vpn unicast
set protocols bgp group ibgp family inet-vpn any
set protocols bgp group ibgp family inet-mvpn signaling damping
set protocols bgp group ibgp neighbor 172.16.1.2 import dampPolicy
set protocols bgp group ibgp neighbor 172.16.1.5
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.4 passive
set protocols ospf area 0.0.0.0 interface ge-1/2/0.10
set protocols ldp interface ge-1/2/0.10
set protocols ldp p2mp
set policy-options policy-statement dampPolicy term term1 from family inet-mvpn
set policy-options policy-statement dampPolicy term term1 from nlri-route-type 3
set policy-options policy-statement dampPolicy term term1 from nlri-route-type 4
set policy-options policy-statement dampPolicy term term1 from nlri-route-type 5
set policy-options policy-statement dampPolicy then accept
set policy-options policy-statement dampPolicy then damping no-damp
set policy-options policy-statement dampPolicy then accept
```

```

set policy-options policy-statement parent_vpn_routes from protocol bgp
set policy-options policy-statement parent_vpn_routes then accept
set policy-options damping no-damp disable
set routing-instances vpn-1 instance-type vrf
set routing-instances vpn-1 interface vt-1/2/0.4
set routing-instances vpn-1 interface ge-1/2/1.17
set routing-instances vpn-1 interface lo0.104
set routing-instances vpn-1 route-distinguisher 100:100
set routing-instances vpn-1 vrf-target target:1:1
set routing-instances vpn-1 protocols ospf export parent_vpn_routes
set routing-instances vpn-1 protocols ospf area 0.0.0.0 interface lo0.104 passive
set routing-instances vpn-1 protocols ospf area 0.0.0.0 interface ge-1/2/1.17
set routing-instances vpn-1 protocols pim rp static address 172.16.100.1
set routing-instances vpn-1 protocols pim interface ge-1/2/1.17 mode sparse
set routing-instances vpn-1 protocols mvpn
set routing-options router-id 172.16.1.4
set routing-options autonomous-system 64501

```

Device R5

```

set interfaces ge-1/2/0 unit 14 family inet address 10.1.1.14/30
set interfaces ge-1/2/0 unit 14 family mpls
set interfaces ge-1/2/1 unit 21 family inet address 10.1.1.21/30
set interfaces ge-1/2/1 unit 21 family mpls
set interfaces vt-1/2/0 unit 5 family inet
set interfaces lo0 unit 5 family inet address 172.16.1.5/32
set interfaces lo0 unit 105 family inet address 172.16.100.5/32
set protocols mpls interface ge-1/2/0.14
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 172.16.1.5
set protocols bgp group ibgp family inet-vpn any
set protocols bgp group ibgp family inet-mvpn signaling
set protocols bgp group ibgp neighbor 172.16.1.2
set protocols bgp group ibgp neighbor 172.16.1.4
set protocols ospf area 0.0.0.0 interface lo0.5 passive
set protocols ospf area 0.0.0.0 interface ge-1/2/0.14
set protocols ldp interface ge-1/2/0.14
set protocols ldp p2mp
set policy-options policy-statement parent_vpn_routes from protocol bgp
set policy-options policy-statement parent_vpn_routes then accept
set routing-instances vpn-1 instance-type vrf
set routing-instances vpn-1 interface vt-1/2/0.5
set routing-instances vpn-1 interface ge-1/2/1.21
set routing-instances vpn-1 interface lo0.105
set routing-instances vpn-1 route-distinguisher 100:100
set routing-instances vpn-1 vrf-target target:1:1
set routing-instances vpn-1 protocols ospf export parent_vpn_routes
set routing-instances vpn-1 protocols ospf area 0.0.0.0 interface lo0.105 passive
set routing-instances vpn-1 protocols ospf area 0.0.0.0 interface ge-1/2/1.21
set routing-instances vpn-1 protocols pim rp static address 172.16.100.2
set routing-instances vpn-1 protocols pim interface ge-1/2/1.21 mode sparse
set routing-instances vpn-1 protocols mvpn
set routing-options router-id 172.16.1.5
set routing-options autonomous-system 1001

```

Device R6

```

set interfaces ge-1/2/0 unit 18 family inet address 10.1.1.18/30
set interfaces ge-1/2/0 unit 18 family mpls

```

```

set interfaces lo0 unit 6 family inet address 172.16.1.6/32
set protocols sap listen 233.1.1.1
set protocols ospf area 0.0.0.0 interface lo0.6 passive
set protocols ospf area 0.0.0.0 interface ge-1/2/0.18
set protocols pim rp static address 172.16.100.2
set protocols pim interface all
set routing-options router-id 172.16.1.6

```

Device R7

```

set interfaces ge-1/2/0 unit 22 family inet address 10.1.1.22/30
set interfaces ge-1/2/0 unit 22 family mpls
set interfaces lo0 unit 7 family inet address 172.16.1.7/32
set protocols ospf area 0.0.0.0 interface lo0.7 passive
set protocols ospf area 0.0.0.0 interface ge-1/2/0.22
set protocols pim rp static address 172.16.100.2
set protocols pim interface all
set routing-options router-id 172.16.1.7

```

### Configuring Device R4

**Step-by-Step Procedure** The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure Device R4:

1. Configure the interfaces.

```

[edit interfaces]
user@R4# set ge-1/2/0 unit 10 family inet address 10.1.1.10/30
user@R4# set ge-1/2/0 unit 10 family mpls

user@R4# set ge-1/2/1 unit 17 family inet address 10.1.1.17/30
user@R4# set ge-1/2/1 unit 17 family mpls

user@R4# set vt-1/2/0 unit 4 family inet

user@R4# set lo0 unit 4 family inet address 172.16.1.4/32
user@R4# set lo0 unit 104 family inet address 172.16.100.4/32

```

2. Configure MPLS and the signaling protocols on the interfaces.

```

[edit protocols]
user@R4# set mpls interface all
user@R4# set mpls interface ge-1/2/0.10
user@R4# set rsvp interface all aggregate
user@R4# set ldp interface ge-1/2/0.10
user@R4# set ldp p2mp

```

3. Configure BGP.

The BGP configuration enables BGP route flap damping for the **inet-mvpn** address family. The BGP configuration also imports into the routing table the routing policy called **dampPolicy**. This policy is applied to neighbor PE Device R2.

```

[edit protocols bgp group ibgp]
user@R4# set type internal

```

```

user@R4# set local-address 172.16.1.4
user@R4# set family inet-vpn unicast
user@R4# set family inet-vpn any
user@R4# set family inet-mvpn signaling damping
user@R4# set neighbor 172.16.1.2 import dampPolicy
user@R4# set neighbor 172.16.1.5

```

4. Configure an interior gateway protocol.

```

[edit protocols ospf]
user@R4# set traffic-engineering

[edit protocols ospf area 0.0.0.0]
user@R4# set interface all
user@R4# set interface lo0.4 passive
user@R4# set interface ge-1/2/0.10

```

5. Configure a damping policy that uses the **nlri-route-type** match condition to damp only MVPN route types 3, 4, and 5.

```

[edit policy-options policy-statement dampPolicy term term1]
user@R4# set from family inet-mvpn
user@R4# set from nlri-route-type 3
user@R4# set from nlri-route-type 4
user@R4# set from nlri-route-type 5
user@R4# set then accept

```

6. Configure the **damping** policy to disable BGP route flap damping.

The **no-damp** policy (**damping no-damp disable**) causes any damping state that is present in the routing table to be deleted. The **then damping no-damp** statement applies the **no-damp** policy as an action and has no **from** match conditions. Therefore, all routes that are not matched by **term1** are matched by this term, with the result that all other MVPN route types are not damped.

```

[edit policy-options policy-statement dampPolicy]
user@R4# set then damping no-damp
user@R4# set then accept

```

```

[edit policy-options]
user@R4# set damping no-damp disable

```

7. Configure the **parent\_vpn\_routes** to accept all other BGP routes that are not from the **inet-mvpn** address family.

This policy is applied as an OSPF export policy in the routing instance.

```

[edit policy-options policy-statement parent_vpn_routes]
user@R4# set from protocol bgp
user@R4# set then accept

```

8. Configure the VPN routing and forwarding (VRF) instance.

```

[edit routing-instances vpn-1]
user@R4# set instance-type vrf
user@R4# set interface vt-1/2/0.4
user@R4# set interface ge-1/2/1.17
user@R4# set interface lo0.104

```

```

user@R4# set route-distinguisher 100:100
user@R4# set vrf-target target:1:1
user@R4# set protocols ospf export parent_vpn_routes
user@R4# set protocols ospf area 0.0.0.0 interface lo0.104 passive
user@R4# set protocols ospf area 0.0.0.0 interface ge-1/2/1.17
user@R4# set protocols pim rp static address 172.16.100.2
user@R4# set protocols pim interface ge-1/2/1.17 mode sparse
user@R4# set protocols mvpn

```

9. Configure the router ID and the autonomous system (AS) number.

```

[edit routing-options]
user@R4# set router-id 172.16.1.4
user@R4# set autonomous-system 1001

```

10. If you are done configuring the device, commit the configuration.

```

user@R4# commit

```

### Results

From configuration mode, confirm your configuration by entering the **show interfaces**, **show protocols**, **show policy-options**, **show routing-instances**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R4# show interfaces
ge-1/2/0 {
  unit 10 {
    family inet {
      address 10.1.1.10/30;
    }
    family mpls;
  }
}
ge-1/2/1 {
  unit 17 {
    family inet {
      address 10.1.1.17/30;
    }
    family mpls;
  }
}
vt-1/2/0 {
  unit 4 {
    family inet;
  }
}
lo0 {
  unit 4 {
    family inet {
      address 172.16.1.4/32;
    }
  }
}
unit 104 {
  family inet {

```

```

        address 172.16.100.4/32;
    }
}
}
user@R4# show protocols
rsvp {
    interface all {
        aggregate;
    }
}
mpls {
    interface all;
    interface ge-1/2/0.10;
}
bgp {
    group ibgp {
        type internal;
        local-address 172.16.1.4;
        family inet-vpn {
            unicast;
            any;
        }
        family inet-mvpn {
            signaling {
                damping;
            }
        }
        neighbor 172.16.1.2 {
            import dampPolicy;
        }
        neighbor 172.16.1.5;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface lo0.4 {
            passive;
        }
        interface ge-1/2/0.10;
    }
}
ldp {
    interface ge-1/2/0.10;
    p2mp;
}
user@R4# show policy-options
policy-statement dampPolicy {
    term term1 {
        from {
            family inet-mvpn;
            nlri-route-type [ 3 4 5 ];
        }
        then accept;
    }
}

```

```
    }
    then {
        damping no-damp;
        accept;
    }
}
policy-statement parent_vpn_routes {
    from protocol bgp;
    then accept;
}
damping no-damp {
    disable;
}
```

user@R4# show routing-instances

```
vpn-1 {
    instance-type vrf;
    interface vt-1/2/0.4;
    interface ge-1/2/1.17;
    interface lo0.104;
    route-distinguisher 100:100;
    vrf-target target:1:1;
    protocols {
        ospf {
            export parent_vpn_routes;
            area 0.0.0.0 {
                interface lo0.104 {
                    passive;
                }
                interface ge-1/2/1.17;
            }
        }
        pim {
            rp {
                static {
                    address 172.16.100.2;
                }
            }
            interface ge-1/2/1.17 {
                mode sparse;
            }
        }
        mvpn;
    }
}
```

user@R4# show routing-options

```
router-id 172.16.1.4;
autonomous-system 1001;
```

---

### Verification

Confirm that the configuration is working properly.

- [Verifying That Route Flap Damping Is Disabled on page 359](#)
- [Verifying Route Flap Damping on page 359](#)



**Verifying That Route Flap Damping Is Disabled**

**Purpose** Verify the presence of the **no-damp** policy, which disables damping for MVPN route types other than 3, 4, and 5.

**Action** From operational mode, enter the **show policy damping** command.

```
user@R4> show policy damping
Default damping information:
  Halflife: 15 minutes
  Reuse merit: 750 Suppress/cutoff merit: 3000
  Maximum suppress time: 60 minutes
  Computed values:
    Merit ceiling: 12110
    Maximum decay: 6193
Damping information for "no-damp":
  Damping disabled
```

**Meaning** The output shows that the default damping parameters are in effect and that the **no-damp** policy is also in effect for the specified route types.

**Verifying Route Flap Damping**

**Purpose** Check whether BGP routes have been damped.

**Action** From operational mode, enter the **show bgp summary** command.

```
user@R4> show bgp summary
Groups: 1 Peers: 2 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0
      6      6      0      0      0      0
bgp.13vpn.2
      0      0      0      0      0      0
bgp.mvpn.0
      2      2      0      0      0      0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
172.16.1.2 1001 3159 3155 0 0 23:43:47
  Estab1
    bgp.13vpn.0: 3/3/3/0
    bgp.13vpn.2: 0/0/0/0
    bgp.mvpn.0: 1/1/1/0
    vpn-1.inet.0: 3/3/3/0
    vpn-1.mvpn.0: 1/1/1/0
172.16.1.5 1001 3157 3154 0 0 23:43:40
  Estab1
    bgp.13vpn.0: 3/3/3/0
    bgp.13vpn.2: 0/0/0/0
    bgp.mvpn.0: 1/1/1/0
    vpn-1.inet.0: 3/3/3/0
    vpn-1.mvpn.0: 1/1/1/0
```

**Meaning** The Damp State field shows that zero routes in the bgp.mvpn.0 routing table have been damped. Further down, the last number in the State field shows that zero routes have been damped for BGP peer 172.16.1.2.

- Related Documentation**
- [Understanding External BGP Peering Sessions on page 13](#)
  - *BGP Configuration Overview*

## PART 3

# Administration

- [Routine Monitoring on page 363](#)



## CHAPTER 10

# Routine Monitoring

- [Tracing BMP Operations on page 363](#)
- [Monitoring BGP Routing Information on page 364](#)
- [Example: Configuring BGP Trace Operations on page 365](#)

## Tracing BMP Operations

---

You can trace BMP operations for all BMP stations by configuring the **traceoptions** statement at the **[edit routing-options bmp]** hierarchy level or for specific BMP stations at the **[edit routing-options bmp station station-name]** hierarchy level.

To trace BMP operations, complete the following steps:

1. Configure the **traceoptions** statement:

```
traceoptions {  
    file filename <files number> <size size> <world-readable | no-world-readable>;  
    flag flag <flag-modifier> <disable>;  
}
```

2. Specify the name of the file to receive the output of the tracing operation using the **file** option. Enclose the name within quotation marks. All files are placed in the directory **/var/log**. We recommend that you place BMP tracing output in the file **bmp-log**.
3. (Optional) Specify the maximum number of trace files using the **files** option. When a trace file named **trace-file.0** reaches its maximum size, it is renamed **trace-file.0**, then **trace-file.1**, and so on, until the maximum number of trace files is reached. Then, the oldest trace file is overwritten. If you specify a maximum number of files, you must also specify a maximum file size with the **size** option.
4. (Optional) Specify the maximum size of each trace file using the **size** option in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named **trace-file** reaches this size, it is renamed **trace-file.0**. When the **trace-file** again reaches its maximum size, **trace-file.0** is renamed **trace-file.1** and **trace-file** is renamed **trace-file.0**. This renaming scheme continues until the maximum number of trace files is reached. Then, the oldest trace file is overwritten. If you specify a maximum file size, you also must specify a maximum number of trace files with the **files** option.

5. (Optional) You can specify that the log files are either **world-readable** (accessible to all users on the device) or **no-world-readable** (not accessible to all users on the device).
6. You can specify the following BMP-specific trace options using the **flag** statement:
  - **all**—Trace all BMP monitoring operations.
  - **down**—Down messages.
  - **error**—Error conditions.
  - **event**—Major events, session establishment, errors, and events.
  - **general**—General events.
  - **normal**—Normal events.
  - **packets**—All messages.
  - **policy**—Policy processing.
  - **route**—Routing information.
  - **route-monitoring**—Route monitoring messages.
  - **state**—State transitions.
  - **statistics**—Statistics messages.
  - **task**—Routing protocol task processing.
  - **timer**—Routing protocol timer processing.
  - **up**—Up messages.
  - **write**—Writing of messages.

You can optionally specify one or more of the following flag modifiers:

- **detail**—Provide detailed trace information.
- **disable**—Disable the tracing flag.
- **receive**—Trace the packets being received.
- **send**—Trace the packets being transmitted.



**NOTE:** Use the **all** trace flag and the **detail** flag modifier with caution due to the increased computer processing power required.

---

**Related  
Documentation**

- [Configuring BGP Monitoring Protocol Version 3 on page 59](#)

---

## Monitoring BGP Routing Information

**Purpose** Use the monitoring functionality to monitor BGP routing information on the routing device.

**Action** To view BGP routing information in the CLI, enter the following commands:

- `show bgp summary`
- `show bgp neighbor`

**Related Documentation**

- [show bgp neighbor on page 521](#)
- [show bgp summary on page 538](#)

## Example: Configuring BGP Trace Operations

- [Understanding Trace Operations for BGP Protocol Traffic on page 365](#)
- [Example: Viewing BGP Trace Files on Logical Systems on page 367](#)

### Understanding Trace Operations for BGP Protocol Traffic

You can trace various BGP protocol traffic to help you debug BGP protocol issues. To trace BGP protocol traffic, include the **traceoptions** statement at the **[edit protocols bgp]** hierarchy level. For routing instances, include the **traceoptions** statement at the **[edit routing-instances routing-instance-name protocols bgp]** hierarchy level.

```
traceoptions {
  file filename <files number> <size size> <world-readable | no-world-readable>;
  flag flag <flag-modifier> <disable>;
}
```

You can specify the following BGP protocol-specific trace options using the **flag** statement:

- **4byte-as**—4-byte AS events.
- **bfd**—BFD protocol events.
- **damping**—Damping operations.
- **graceful-restart**—Graceful restart events.
- **keepalive**—BGP keepalive messages.
- **nsr-synchronization**—Nonstop active routing synchronization events.
- **open**—BGP open packets. These packets are sent between peers when they are establishing a connection.
- **packets**—All BGP protocol packets.
- **refresh**—BGP refresh packets.
- **update**—BGP update packets. These packets provide routing updates to BGP systems.

Global tracing options are inherited from the configuration set by the **traceoptions** statement at the **[edit routing-options]** hierarchy level. You can override the following global trace options for the BGP protocol using the **traceoptions flag** statement included at the **[edit protocols bgp]** hierarchy level:

- **all**—All tracing operations
- **general**—All normal operations and routing table changes (a combination of the normal and route trace operations)
- **normal**—Normal events
- **policy**—Policy processing
- **route**—Routing information
- **state**—State transitions
- **task**—Routing protocol task processing
- **timer**—Routing protocol timer processing

You can optionally specify one or more of the following flag modifiers:

- **detail**—Detailed trace information.
- **filter**—Filter trace information. Applies only to **route** and **damping** tracing flags.
- **receive**—Packets being received.
- **send**—Packets being transmitted.



**NOTE:** Use the **all** trace flag and the **detail** flag modifier with caution because these might cause the CPU to become very busy.

---



**NOTE:** If you only enable the **update** flag, received keepalive messages do not generate a trace message.

---

You can filter trace statements and display only the statement information that passes through the filter by specifying the **filter** flag modifier. The **filter** modifier is only supported for the **route** and **damping** tracing flags.

The **match-on** statement specifies filter matches based on prefixes. It is used to match on route filters.



**NOTE:** Per-neighbor trace filtering is not supported on a BGP per-neighbor level for **route** and **damping** flags. Trace option filtering support is on a peer group level.

---



## Example: Viewing BGP Trace Files on Logical Systems

This example shows how to list and view files that are stored on a logical system.

- [Requirements on page 367](#)
- [Overview on page 367](#)
- [Configuration on page 368](#)
- [Verification on page 371](#)

### Requirements

- You must have the **view** privilege for the logical system.
- Configure a network, such as the BGP network shown in “[Example: Configuring Internal BGP Peering Sessions on Logical Systems](#)” on page 48.

### Overview

Logical systems have their individual directory structure created in the `/var/logical-systems/logical-system-name` directory. It contains the following subdirectories:

- `/config`—Contains the active configuration specific to the logical system.
- `/log`—Contains system log and tracing files specific to the logical system.

To maintain backward compatibility for the log files with previous versions of Junos OS, a symbolic link (symlink) from the `/var/logs/logical-system-name` directory to the `/var/logical-systems/logical-system-name` directory is created when a logical system is configured.

- `/tmp`—Contains temporary files specific to the logical system.

The file system for each logical system enables logical system users to view trace logs and modify logical system files. Logical system administrators have full access to view and modify all files specific to the logical system.

Logical system users and administrators can save and load configuration files at the logical-system level using the **save** and **load** configuration mode commands. In addition, they can also issue the **show log**, **monitor**, and **file** operational mode commands at the logical-system level.

This example shows how to configure and view a BGP trace file on a logical system. The steps can be adapted to apply to trace operations for any Junos OS hierarchy level that supports trace operations.



**TIP:** To view a list of hierarchy levels that support tracing operations, enter the `help apropos traceoptions` command in configuration mode.

## Configuration

- [Configuring Trace Operations on page 368](#)
- [Viewing the Trace File on page 368](#)
- [Deactivating and Reactivating Trace Logging on page 370](#)
- [Results on page 371](#)

### CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the **[edit]** hierarchy level.

```
set logical-systems A protocols bgp group internal-peers traceoptions file bgp-log
set logical-systems A protocols bgp group internal-peers traceoptions file size 10k
set logical-systems A protocols bgp group internal-peers traceoptions file files 2
set logical-systems A protocols bgp group internal-peers traceoptions flag update detail
```

### Configuring Trace Operations

#### Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the *CLI User Guide*.

To configure the trace operations:

1. Configure trace operations on the logical system.

```
[edit logical-systems A protocols bgp group internal-peers]
user@host# set traceoptions file bgp-log
user@host# set traceoptions file size 10k
user@host# set traceoptions file files 2
user@host# set traceoptions flag update detail
```

2. If you are done configuring the device, commit the configuration.

```
[edit]
user@host# commit
```

### Viewing the Trace File

#### Step-by-Step Procedure

To view the trace file:

1. In operational mode on the main router, list the directories on the logical system.

```
user@host> file list /var/logical-systems/A
/var/logical-systems/A:
config/
log/
tmp/
```

2. In operational mode on the main router, list the log files on the logical system.

```
user@host> file list /var/logical-systems/A/log/
/var/logical-systems/A/log:
bgp-log
```

3. View the contents of the **bgp-log** file.

```
user@host> file show /var/logical-systems/A/log/bgp-log
Aug 10 17:12:01 trace_on: Tracing to "/var/log/A/bgp-log" started
Aug 10 17:14:22.826182 bgp_peer_mgmt_clear:5829: NOTIFICATION sent to
192.163.6.4 (Internal AS 17): code 6 (Cease) subcode 4 (Administratively
Reset), Reason: Management session cleared BGP neighbor
Aug 10 17:14:22.826445 bgp_send: sending 21 bytes to 192.163.6.4 (Internal
AS 17)
Aug 10 17:14:22.826499
Aug 10 17:14:22.826499 BGP SEND 192.168.6.5+64965 -> 192.163.6.4+179
Aug 10 17:14:22.826559 BGP SEND message type 3 (Notification) length 21
Aug 10 17:14:22.826598 BGP SEND Notification code 6 (Cease) subcode 4
(Administratively Reset)
Aug 10 17:14:22.831756 bgp_peer_mgmt_clear:5829: NOTIFICATION sent to
192.168.40.4 (Internal AS 17): code 6 (Cease) subcode 4 (Administratively
Reset), Reason: Management session cleared BGP neighbor
Aug 10 17:14:22.831851 bgp_send: sending 21 bytes to 192.168.40.4 (Internal
AS 17)
Aug 10 17:14:22.831901
Aug 10 17:14:22.831901 BGP SEND 192.168.6.5+53889 -> 192.168.40.4+179
Aug 10 17:14:22.831959 BGP SEND message type 3 (Notification) length 21
Aug 10 17:14:22.831999 BGP SEND Notification code 6 (Cease) subcode 4
(Administratively Reset)
...
```

4. Filter the output of the log file.

```
user@host> file show /var/logical-systems/A/log/bgp-log | match "flags 0x40"
Aug 10 17:14:54.867460 BGP SEND flags 0x40 code Origin(1): IGP
Aug 10 17:14:54.867595 BGP SEND flags 0x40 code ASPath(2) length 0: <null>
Aug 10 17:14:54.867650 BGP SEND flags 0x40 code NextHop(3): 192.168.6.5
Aug 10 17:14:54.867692 BGP SEND flags 0x40 code LocalPref(5): 100
Aug 10 17:14:54.884529 BGP RECV flags 0x40 code Origin(1): IGP
Aug 10 17:14:54.884581 BGP RECV flags 0x40 code ASPath(2) length 0: <null>
Aug 10 17:14:54.884628 BGP RECV flags 0x40 code NextHop(3): 192.163.6.4
Aug 10 17:14:54.884667 BGP RECV flags 0x40 code LocalPref(5): 100
Aug 10 17:14:54.911377 BGP RECV flags 0x40 code Origin(1): IGP
Aug 10 17:14:54.911422 BGP RECV flags 0x40 code ASPath(2) length 0: <null>
Aug 10 17:14:54.911466 BGP RECV flags 0x40 code NextHop(3): 192.168.40.4
Aug 10 17:14:54.911507 BGP RECV flags 0x40 code LocalPref(5): 100
Aug 10 17:14:54.916008 BGP SEND flags 0x40 code Origin(1): IGP
Aug 10 17:14:54.916054 BGP SEND flags 0x40 code ASPath(2) length 0: <null>
Aug 10 17:14:54.916100 BGP SEND flags 0x40 code NextHop(3): 192.168.6.5
Aug 10 17:14:54.916143 BGP SEND flags 0x40 code LocalPref(5): 100
Aug 10 17:14:54.920304 BGP RECV flags 0x40 code Origin(1): IGP
Aug 10 17:14:54.920348 BGP RECV flags 0x40 code ASPath(2) length 0: <null>
Aug 10 17:14:54.920393 BGP RECV flags 0x40 code NextHop(3): 10.0.0.10
Aug 10 17:14:54.920434 BGP RECV flags 0x40 code LocalPref(5): 100
```

5. View the tracing operations in real time.

```
user@host> clear bgp neighbor logical-system A
Cleared 2 connections
```



**CAUTION:** Clearing the BGP neighbor table is disruptive in a production environment.

- Run the **monitor start** command with an optional **match** condition.

```
user@host> monitor start A/bgp-log | match 0.0.0.0/0
Aug 10 19:21:40.773467 BGP RECV          0.0.0.0/0
Aug 10 19:21:40.773685 bgp_rcv_nlri: 0.0.0.0/0
Aug 10 19:21:40.773778 bgp_rcv_nlri: 0.0.0.0/0 belongs to meshgroup
Aug 10 19:21:40.773832 bgp_rcv_nlri: 0.0.0.0/0 qualified bnp->ribact 0x0
12afcb 0x0
```

- Pause the **monitor** command by pressing Esc-Q.  
To unpause the output, press Esc-Q again.
- Halt the **monitor** command by pressing Enter and typing **monitor stop**.  
[Enter]  
user@host> **monitor stop**
- When you are finished troubleshooting, consider deactivating trace logging to avoid any unnecessary impact to system resources.

```
[edit protocols bgp group internal-peers]
user@host:A# deactivate traceoptions
user@host:A# commit
```

When configuration is deactivated, it appears in the configuration with the **inactive** tag. To reactivate trace operations, use the **activate** configuration-mode statement.

```
[edit protocols bgp group internal-peers]
user@host:A# show
```

```
type internal;
inactive: traceoptions {
    file bgp-log size 10k files 2;
    flag update detail;
    flag all;
}
local-address 192.168.6.5;
export send-direct;
neighbor 192.163.6.4;
neighbor 192.168.40.4;
```

- To reactivate trace operations, use the **activate** configuration-mode statement.  
[edit protocols bgp group internal-peers]  
user@host:A# **activate traceoptions**  
user@host:A# **commit**

### ***Deactivating and Reactivating Trace Logging***

#### **Step-by-Step Procedure**

To deactivate and reactivate the trace file:

- When you are finished troubleshooting, consider deactivating trace logging to avoid an unnecessary impact to system resources.

```
[edit protocols bgp group internal-peers]
user@host:A# deactivate traceoptions
user@host:A# commit
```

When configuration is deactivated, the statement appears in the configuration with the **inactive** tag.

```
[edit protocols bgp group internal-peers]
user@host:A# show
```

```
type internal;
inactive: traceoptions {
  file bgp-log size 10k files 2;
  flag update detail;
  flag all;
}
local-address 192.168.6.5;
export send-direct;
neighbor 192.163.6.4;
neighbor 192.168.40.4;
```

2. To reactivate logging, use the **activate** configuration-mode statement.

```
[edit protocols bgp group internal-peers]
user@host:A# activate traceoptions
user@host:A# commit
```

### Results

From configuration mode, confirm your configuration by entering the **show logical-systems A protocols bgp group internal-peers** command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host:# show logical-systems A protocols bgp group internal-peers
traceoptions {
  file bgp-log size 10k files 2;
  flag update detail;
}
```

### Verification

Confirm that the configuration is working properly.

#### Verifying That the Trace Log File Is Operating

**Purpose** Make sure that events are being written to the log file.

**Action** user@host:A> **show log bgp-log**  
 Aug 12 11:20:57 trace\_on: Tracing to "/var/log/A/bgp-log" started

**Related Documentation**

- [Understanding External BGP Peering Sessions on page 13](#)
- [BGP Configuration Overview](#)



## PART 4

# Configuration Statements and Operational Commands

- [Configuration Statements on page 375](#)
- [Operational Commands on page 505](#)





# Configuration Statements

- [accept-remote-nexthop](#) on page 378
- [advertise-external](#) on page 379
- [advertise-inactive](#) on page 381
- [advertise-peer-as](#) on page 383
- [algorithm \(BGP BFD Authentication\)](#) on page 384
- [apply-groups](#) on page 386
- [apply-groups-except](#) on page 386
- [authentication \(BGP BFD Liveness Detection\)](#) on page 387
- [authentication-algorithm](#) on page 389
- [authentication-key \(Protocols BGP and BMP\)](#) on page 392
- [authentication-key-chain \(Protocols BGP and BMP\)](#) on page 393
- [bfd-liveness-detection \(Protocols BGP\)](#) on page 395
- [bgp](#) on page 399
- [bgp-orf-cisco-mode](#) on page 400
- [cluster](#) on page 402
- [connection-mode](#) on page 403
- [damping \(Protocols BGP\)](#) on page 404
- [description \(Protocols BGP\)](#) on page 406
- [detection-time \(BFD Liveness Detection\)](#) on page 407
- [disable \(Protocols BGP\)](#) on page 408
- [disable \(BGP Graceful Restart\)](#) on page 409
- [export \(Protocols BGP\)](#) on page 410
- [family \(Protocols BGP\)](#) on page 411
- [graceful-restart \(Protocols BGP\)](#) on page 415
- [group \(Protocols BGP\)](#) on page 417
- [hold-down](#) on page 421
- [hold-down-interval \(BGP BFD Liveness Detection\)](#) on page 423
- [hold-time \(Protocols BGP\)](#) on page 425

- [import](#) on page 427
- [include-mp-next-hop](#) on page 429
- [initiation-message](#) on page 430
- [keep](#) on page 431
- [key-chain \(BGP BFD Authentication\)](#) on page 433
- [local-address \(Protocols BGP\)](#) on page 435
- [local-address \(Protocols BMP\)](#) on page 437
- [local-as](#) on page 438
- [local-port](#) on page 441
- [local-preference](#) on page 442
- [log-updown](#) on page 443
- [loops \(BGP Address Family\)](#) on page 444
- [loose-check \(BGP BFD Authentication\)](#) on page 446
- [maximum-ecmp](#) on page 447
- [metric-out](#) on page 448
- [minimum-interval \(BFD Liveness Detection\)](#) on page 450
- [minimum-interval \(transmit-interval\)](#) on page 452
- [minimum-receive-interval \(BFD Liveness Detection\)](#) on page 454
- [monitor \(Protocols BMP\)](#) on page 455
- [mtu-discovery](#) on page 456
- [multihop](#) on page 458
- [multiplier \(BFD Liveness Detection\)](#) on page 460
- [neighbor \(Protocols BGP\)](#) on page 462
- [no-adaptation \(BFD Liveness Detection\)](#) on page 465
- [no-advertise-peer-as](#) on page 466
- [no-aggregator-id](#) on page 467
- [no-client-reflect](#) on page 468
- [out-delay](#) on page 469
- [outbound-route-filter](#) on page 471
- [passive \(Protocols BGP\)](#) on page 472
- [path-selection](#) on page 473
- [peer-as \(Protocols BGP\)](#) on page 475
- [post-policy](#) on page 476
- [pre-policy](#) on page 477
- [preference \(Protocols BGP\)](#) on page 478
- [priority \(Protocols BMP\)](#) on page 479
- [remove-private](#) on page 480

- [restart-time \(BGP Graceful Restart\) on page 482](#)
- [route-monitoring on page 483](#)
- [session-mode on page 485](#)
- [stale-routes-time on page 486](#)
- [station on page 487](#)
- [station-address on page 488](#)
- [station-port on page 489](#)
- [statistics-timeout on page 490](#)
- [tcp-mss \(Protocols BGP\) on page 491](#)
- [threshold \(detection-time\) on page 492](#)
- [threshold \(transmit-interval\) on page 494](#)
- [traceoptions \(Protocols BGP\) on page 496](#)
- [traceoptions \(Protocols BMP\) on page 499](#)
- [transmit-interval \(BFD Liveness Detection\) on page 501](#)
- [version \(BFD Liveness Detection\) on page 503](#)

## accept-remote-nexthop

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | accept-remote-nexthop;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp group <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 8.5.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | <p>Specify that a single-hop EBGp peer accepts a remote next hop with which it does not share a common subnet. Configure a separate import policy on the EBGp peer to specify the remote next hop.</p> <p>For Junos OS Release 13.3 and later releases, specify that a multihop EBGp peer accepts a remote next hop with which it does not share a common subnet. This allows working around current resolver limitations to realize multipath forwarding in recursive next-hop resolution scenarios.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring Single-Hop EBGp Peers to Accept Remote Next Hops on page 243</a></li> <li>• <a href="#">Configuring Routing Policies to Control BGP Route Advertisements on page 177</a></li> <li>• <i>multipath</i></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## advertise-external

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>advertise-external {conditional};</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>],<br/>         [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],<br/>         [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],<br/>         [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],<br/>         [edit protocols bgp group <i>group-name</i>],<br/>         [edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],<br/>         [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],<br/>         [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>neighbor-address</i>]</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 9.3.</p> <p>Statement introduced in Junos OS Release 9.3 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Description</b>         | <p>Specify BGP to advertise the best external route into an IBGP mesh group, a route reflector cluster, or an AS confederation even if the best route is an internal route.</p> <p>In general, deployed BGP implementations do not advertise the external route with the highest local preference value to internal peers unless it is the best route. Although this behavior was required by an earlier version of the BGP version 4 specification, RFC 1771, it was typically not followed in order to minimize the amount of advertised information and to prevent routing loops. However, there are scenarios in which advertising the best external route is beneficial, in particular, situations that can result in IBGP route oscillation.</p> <p>The <b>advertise-external</b> statement is supported at both the group and neighbor level. If you configure the statement at the neighbor level, you must configure it for all neighbors in a group. Otherwise, the group is automatically split into different groups.</p> <p>In a confederation, when advertising a route to a confederation border router, any route from a different confederation sub-AS is considered external. When configuring the <b>advertise-external</b> statement for an AS confederation, it is recommended that EBGP peers belonging to different autonomous systems are configured in a separate EBGP peer group. This ensures consistency while BGP sends the best external route to peers in the configured peer group.</p> <p>To configure the <b>advertise-external</b> statement on a route reflector, you must disable intracluster reflection with the <b>no-client-reflect</b> statement.</p> <p>When a routing device is configured as a route reflector for a cluster, a route advertised by the route reflector is considered internal if it is received from an internal peer with the same cluster identifier or if both peers have no cluster identifier configured. A route received from an internal peer that belongs to another cluster, that is, with a different cluster identifier, is considered external.</p> |

The **conditional** option causes BGP to advertise the external route only if the route selection process reaches the point where the multiple exit discriminator (MED) metric is evaluated. As a result, an external route with an AS path longer than that of the active path is not advertised.

Junos OS also provides support for configuring a BGP export policy that matches on the state of an advertised route. You can match on either active or inactive routes.

**Default** BGP does not advertise the external route with the highest local preference value to internal peers unless it is the best route.


**Options** **conditional**—(Optional) Advertise the best external path only if the route selection process reaches the point at which the multiple exit discriminator (MED) metric is evaluated. The **conditional** option restricts advertisement to when the best external path and the active path are equal until the MED step of the route selection process. This implies that external routes with a longer AS path length than the active path, for instance, are not advertised. The criteria used for selecting the best external path is the same whether or not the **conditional** option is configured.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- *Example: Configuring a Routing Policy to Advertise the Best External Route to Internal Peers*
- [advertise-inactive on page 381](#)

## advertise-inactive

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | advertise-inactive;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p>                                                                                                                                                                                                             |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>         | <p>Configure the routing table to export to BGP the best route learned by BGP even if Junos OS did not select this route to be an active route.</p> <p>One way to achieve multivendor compatibility is to include the <b>advertise-inactive</b> statement in the external BGP (EBGP) configuration. By default, BGP stores the route information it receives from update messages in the Junos OS routing table, and the routing table exports only active routes into BGP, which BGP then advertises to its peers. The <b>advertise-inactive</b> statement causes Junos OS to advertise the best BGP route that is inactive because of IGP preference. When you use the <b>advertise-inactive</b> statement, the Junos OS device uses, for example, the OSPF route for forwarding, and the other vendor's device uses the EBGP route for forwarding. However, from the perspective of an EBGP peer in a neighboring AS, both vendors' devices appear to behave the same way.</p> <div style="border: 1px solid #ccc; padding: 10px; margin-top: 20px;"> <p> <b>NOTE:</b> When BGP advertises a network layer reachability information (NLRI) with a label, and the advertised route resides in xxx.xxx.3 routing table such as inet.3, Junos OS automatically advertises such inactive routes even if you have not configured the <b>advertise-inactive</b> statement.</p> </div> |
| <b>Default</b>             | By default, BGP stores the route information it receives from update messages in the Junos OS routing table, and the routing table exports only active routes into BGP, which BGP then advertises to its peers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

|                                 |                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                              |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <i>Example: Configuring BGP to Advertise Inactive Routes</i></li><li>• <a href="#">Example: Configuring the Preference Value for BGP Routes on page 197</a></li><li>• <a href="#">Example: Configuring BGP Route Preference (Administrative Distance) on page 195</a></li><li>• <a href="#">advertise-external on page 379</a></li></ul> |



## advertise-peer-as

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | advertise-peer-as;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Description</b>              | <p>Disable the default behavior of suppressing AS routes.</p> <p>If you include the <b>advertise-peer-as</b> statement in the configuration, BGP advertises routes learned from one external BGP (EBGP) peer back to another EBGP peer in the same autonomous system (AS) but not back to the originating peer.</p> <p>Another way to disable the route suppression default behavior is with the <b>as-override</b> statement. If you include both the <b>as-override</b> and <b>no-advertise-peer-as</b> statements in the configuration, the <b>no-advertise-peer-as</b> statement is ignored.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Default</b>                  | By default, Junos OS does not advertise the routes learned from one EBGP peer back to the same external BGP (EBGP) peer. In addition, the software does not advertise those routes back to any EBGP peers that are in the same AS as the originating peer, regardless of the routing instance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <i>Example: Enabling BGP Route Advertisements</i></li> <li>• <i>Example: Configuring a Layer 3 VPN with Route Reflection and AS Override</i></li> <li>• <a href="#">no-advertise-peer-as on page 466</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## algorithm (BGP BFD Authentication)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>algorithm <i>algorithm-name</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit protocols bgp bgp bfd-liveness-detection authentication],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bgp bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.1.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>         | Configure the algorithm used to authenticate the specified BFD session.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Options</b>             | <p><b><i>algorithm-name</i></b>—Authentication algorithm name: <b>simple-password</b>, <b>keyed-md5</b>, <b>keyed-sha-1</b>, <b>meticulous-keyed-md5</b>, <b>meticulous-keyed-sha-1</b>.</p> <p><b>simple-password</b>—Plain-text password. One to 16 bytes of plain text are used to authenticate the BFD session. One or more passwords can be configured. This method is the least secure and should be used only when BFD sessions are not subject to packet interception.</p> <p><b>keyed-md5</b>—Keyed Message Digest 5 hash algorithm for sessions with transmit and receive intervals greater than 100 ms. To authenticate the BFD session, keyed MD5 uses one or more secret keys (generated by the algorithm) and a sequence number that is updated periodically. With this method, packets are accepted at the receiving end of the session if one of the keys matches and the sequence number is greater than or equal to the last sequence number received. Although more secure than a simple password, this method is vulnerable to replay attacks. Increasing the rate at which the sequence number is updated can reduce this risk.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

**meticulous-keyed-md5**—Meticulous keyed Message Digest 5 hash algorithm. This method works in the same manner as keyed MD5, but the sequence number is updated with every packet. Although more secure than keyed MD5 and simple passwords, this method can take additional time to authenticate the session.

**keyed-sha-1**—Keyed Secure Hash Algorithm I for sessions with transmit and receive intervals greater than 100 ms. To authenticate the BFD session, keyed SHA uses one or more secret keys (generated by the algorithm) and a sequence number that is updated periodically. The key is not carried within the packets. With this method, packets are accepted at the receiving end of the session if one of the keys matches and the sequence number is greater than the last sequence number received.

**meticulous-keyed-sha-1**—Meticulous keyed Secure Hash Algorithm I. This method works in the same manner as keyed SHA, but the sequence number is updated with every packet. Although more secure than keyed SHA and simple passwords, this method can take additional time to authenticate the session.

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>Required Privilege</b> | routing—To view this statement in the configuration.        |
| <b>Level</b>              | routing-control—To add this statement to the configuration. |

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Related Documentation</b> | <ul style="list-style-type: none"><li>• <i>Example: Configuring BFD Authentication for Securing Static Routes</i></li><li>• <a href="#">Example: Configuring BGP Route Authentication on page 311</a></li><li>• <a href="#">Example: Configuring EBGp Multihop Sessions on page 186</a></li><li>• <a href="#">authentication on page 387</a></li><li>• <a href="#">bfd-liveness-detection on page 395</a></li><li>• <a href="#">key-chain on page 433</a></li><li>• <a href="#">loose-check on page 446</a></li></ul> |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## apply-groups

---

|                                 |                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>apply-groups [ <i>group-names</i> ];</code>                                                                                                                                                                                                                                                                                                                  |
| <b>Hierarchy Level</b>          | All hierarchy levels                                                                                                                                                                                                                                                                                                                                               |
| <b>Release Information</b>      | Statement introduced before Junos OS Release 7.4.                                                                                                                                                                                                                                                                                                                  |
| <b>Description</b>              | <p>Apply a configuration group to a specific hierarchy level in a configuration, to have a configuration inherit the statements in the configuration group.</p> <p>You can specify more than one group name. You must list them in order of inheritance priority. The configuration data in the first group takes priority over the data in subsequent groups.</p> |
| <b>Options</b>                  | <i>group-names</i> —One or more names specified in the <b>groups</b> statement.                                                                                                                                                                                                                                                                                    |
| <b>Required Privilege Level</b> | configure—To enter configuration mode, but other required privilege levels depend on where the statement is located in the configuration hierarchy.                                                                                                                                                                                                                |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <i>Applying the Junos OS Configuration Group</i></li><li>• <i>groups</i></li></ul>                                                                                                                                                                                                                                         |

## apply-groups-except

---

|                                 |                                                                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>apply-groups-except [ <i>group-names</i> ];</code>                                                                                            |
| <b>Hierarchy Level</b>          | All hierarchy levels except the top level                                                                                                           |
| <b>Release Information</b>      | Statement introduced before Junos OS Release 7.4.                                                                                                   |
| <b>Description</b>              | Disable inheritance of a configuration group.                                                                                                       |
| <b>Options</b>                  | <i>group-names</i> —One or more names specified in the <b>groups</b> statement.                                                                     |
| <b>Required Privilege Level</b> | configure—To enter configuration mode, but other required privilege levels depend on where the statement is located in the configuration hierarchy. |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <i>groups</i></li><li>• <i>Disabling Inheritance of a Junos OS Configuration Group</i></li></ul>            |

## authentication (BGP BFD Liveness Detection)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <pre>authentication {   algorithm <i>algorithm-name</i>;   key-chain <i>key-chain-name</i>;   loose-check ; }</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Hierarchy Level</b>          | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>   bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>   bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp group <i>group-name</i> bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection], [edit protocols bgp bgp bfd-liveness-detection], [edit protocols bgp group <i>group-name</i> bfd-liveness-detection], [edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>   bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor   <i>address</i> bfd-liveness-detection]</pre> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 8.1.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Description</b>              | <p>Specify the router and route authentication to mitigate the risk of being attacked by a machine or router that has been configured to share incorrect routing information with another router. Router and route authentication enables routers to share information only if they can verify that they are talking to a trusted source, based on a password (key). In this method, a hashed key is sent along with the route being sent to another router. The receiving router compares the sent key to its own configured key. If they are the same, the receiving router accepts the route.</p> <p>The remaining statements are explained separately.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li> <li>• <i>Example: Configuring BFD Authentication for Securing Static Routes</i></li> <li>• <a href="#">Example: Configuring BGP Route Authentication on page 311</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

- [algorithm on page 384](#)
- [bfd-liveness-detection on page 395](#)
- [key-chain on page 433](#)
- [loose-check on page 446](#)

## authentication-algorithm

**Syntax** authentication-algorithm *algorithm*;

**Hierarchy Level** [edit logical-systems *logical-system-name* protocols bgp],  
 [edit logical-systems *logical-system-name* protocols bgp **group** *group-name*],  
 [edit logical-systems *logical-system-name* protocols bgp **group** *group-name* neighbor *address*],  
 [edit logical-systems *logical-system-name* protocols ldp session *session-address*],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp **group** *group-name*],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp group *group-name* **neighbor** *address*],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols ldp session *session-address*],  
 [edit logical-systems *logical-system-name* routing-options bmp],  
 [edit logical-systems *logical-system-name* routing-options bmp **station** *station-name*],  
 [edit protocols bgp],  
 [edit protocols bgp **group** *group-name*],  
 [edit protocols bgp group *group-name* **neighbor** *address*],  
 [edit protocols ldp session *session-address*],  
 [edit routing-instances *routing-instance-name* protocols bgp],  
 [edit routing-instances *routing-instance-name* protocols bgp **group** *group-name*],  
 [edit routing-instances *routing-instance-name* protocols bgp group *group-name* **neighbor** *address*],  
 [edit routing-instances *routing-instance-name* protocols ldp session *session-address*],  
 [edit routing-options bmp],  
 [edit routing-options bmp **station** *station-name*]

**Release Information** Statement introduced in Junos OS Release 7.6.  
 Statement introduced for BGP in Junos OS Release 8.0.  
 Statement introduced in Junos OS Release 9.0 for EX Series switches.  
 Statement introduced in Junos OS Release 12.3X50 for the QFX Series.  
 Statement introduced for BMP in Junos OS Release 13.2X51-D15 for the QFX Series.  
 Statement introduced for BMP in Junos OS Release 13.3.  
 Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.

**Description** Configure an authentication algorithm type.



**NOTE:** Keep the following points in mind when you configure the authentication algorithm in an IPsec proposal:

- When both ends of an IPsec VPN tunnel contain the same IKE proposal but different IPsec proposals, an error occurs and the tunnel is not established in this scenario. For example, if one end of the tunnel contains router 1 configured with the authentication algorithm as hmac-sha-256-128 and the other end of the tunnel contains router 2 configured with the authentication algorithm as hmac-md5-96, the VPN tunnel is not established.

- When both ends of an IPsec VPN tunnel contain the same IKE proposal but different IPsec proposals, and when one end of the tunnel contains two IPsec proposals to check whether a less secure algorithm is selected or not, an error occurs and the tunnel is not established. For example, if you configure two authentication algorithms for an IPsec proposal as `hmac-sha-256-128` and `hmac-md5-96` on one end of the tunnel, router 1, and if you configure the algorithm for an IPsec proposal as `hmac-md5-96` on the other end of the tunnel, router 2, the tunnel is not established and the number of proposals mismatch.
  - When you configure two IPsec proposals at both ends of a tunnel, such as the `authentication-algorithm hmac-sha-256-128` and `authentication-algorithm hmac-md5-96` statements at the `[edit services ipsec-vpn ipsec proposal proposal-name]` hierarchy level on one of the tunnel, router 1 (with the algorithms in two successive statements to specify the order), and the `authentication-algorithm hmac-md5-96` and `authentication-algorithm hmac-sha-256-128` statements at the `[edit services ipsec-vpn ipsec proposal proposal-name]` hierarchy level on one of the tunnel, router 2 (with the algorithms in two successive statements to specify the order, which is the reverse order of router 1), the tunnel is established in this combination as expected because the number of proposals is the same on both ends and they contain the same set of algorithms. However, the authentication algorithm selected is `hmac-md5-96` and not the stronger algorithm of `hmac-sha-256-128`. This method of selection of the algorithm occurs because the first matching proposal is selected. Also, for a default proposal, regardless of whether the router supports the Advanced Encryption Standard (AES) encryption algorithm, the `3des-cbc` algorithm is chosen and not the `aes-cfb` algorithm, which is because of the first algorithm in the default proposal being selected. In the sample scenario described here, on router 2, if you reverse the order of the algorithm configuration in the proposal so that it is the same order as the one specified on router 1, `hmac-sha-256-128` is selected as the authentication method.
  - You must be aware of the order of proposals in an IPsec policy at the time of configuration if you want the matching of proposals to happen in a certain order of preference, such as the strongest algorithm to be considered first when a match is made when both policies from the two peers have a proposal.
-



**Options** *algorithm*—Specify one of the following types of authentication algorithms:

- **aes-128-cmac-96**—Cipher-based message authentication code (AES128, 96 bits).
- **hmac-sha-1-96**—Hash-based message authentication code (SHA1, 96 bits).
- **md5**—Message digest 5.

**Default:** hmac-sha-1-96



**NOTE:** The default is not displayed in the output of the `show bgp bmp` command unless a key or key-chain is also configured.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.


**Related Documentation**

- [Example: Configuring Route Authentication for BGP on page 312](#)
- [Configuring BGP Monitoring Protocol Version 3 on page 59](#)

## authentication-key (Protocols BGP and BMP)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | authentication-key <i>key</i> ;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-options bmp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-options bmp],</p> <p>[edit routing-options bmp <b>station</b> <i>station-name</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced for BMP in Junos OS Release 13.2X51-D15 for the QFX Series.</p> <p>Statement introduced for BMP version 3 in Junos OS Release 13.3.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Description</b>              | Configure an MD5 authentication key (password). Neighboring routing devices use the same password to verify the authenticity of BGP packets sent from this system.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Options</b>                  | <b>key</b> —Authentication password. It can be up to 126 characters. Characters can include any ASCII strings. If you include spaces, enclose all characters in quotation marks (" ").                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring Route Authentication for BGP on page 312</a></li> <li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## authentication-key-chain (Protocols BGP and BMP)

|                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                                                                                                                                                                                                                                                        | <code>authentication-key-chain <i>key-chain</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>                                                                                                                                                                                                                                               | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-options bmp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-options bmp],</p> <p>[edit routing-options bmp <b>station</b> <i>station-name</i>]</p> |
| <b>Release Information</b>                                                                                                                                                                                                                                           | <p>Statement introduced in Junos OS Release 8.0.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced for BMP in Junos OS Release 13.2X51-D15 for the QFX Series.</p> <p>Statement introduced for BMP in Junos OS Release 13.3.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>                                                                                                                                                                                                                                                   | Apply and enable an authentication keychain to the routing device. Note that the referenced key chain must be defined. When configuring the authentication key update feature for BGP, you cannot commit the <b>0.0.0.0/allow</b> statement with authentication keys or key chains. The CLI issues a warning and fails to commit the configuration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Options</b>                                                                                                                                                                                                                                                       | <b>key-chain</b> —Authentication keychain name. It can be up to 126 characters. Characters can include any ASCII strings. If you include spaces, enclose all characters in quotation marks (" ").                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <div>  <p><b>NOTE:</b> For BGP, you must also configure an authentication algorithm by including the <code>authentication-algorithm <i>algorithm</i></code> statement.</p> </div> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Required Privilege Level</b>                                                                                                                                                                                                                                      | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

**Related  
Documentation**

- [Example: Configuring Route Authentication for BGP on page 312](#)
- *Example: Configuring BFD Authentication for Securing Static Routes*
- *Configuring the Authentication Key Update Mechanism for BGP and LDP Routing Protocols*
- [Configuring BGP Monitoring Protocol Version 3 on page 59](#)
- [authentication-algorithm on page 389](#)

## bfd-liveness-detection (Protocols BGP)

**Syntax**

```

bfd-liveness-detection {
  authentication {
    algorithm algorithm-name;
    key-chain key-chain-name;
    loose-check;
  }
  detection-time {
    threshold milliseconds;
  }
  hold-down-interval milliseconds;
  minimum-interval milliseconds;
  minimum-receive-interval milliseconds;
  multiplier number;
  no-adaptation;
  session-mode (automatic | multihop | single-hop);
  transmit-interval {
    minimum-interval milliseconds;
    threshold milliseconds;
  }
  version (1 | automatic);
}

```

**Hierarchy Level**

```

[edit logical-systems logical-system-name protocols bgp],
[edit logical-systems logical-system-name protocols bgp group group-name],
[edit logical-systems logical-system-name protocols bgp group group-name neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
bgp],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
bgp group group-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
bgp group group-name neighbor address],
[edit protocols bgp],
[edit protocols bgp group group-name],
[edit protocols bgp group group-name neighbor address],
[edit routing-instances routing-instance-name protocols bgp],
[edit routing-instances routing-instance-name protocols bgp group group-name],
[edit routing-instances routing-instance-name protocols bgp group group-name neighbor
address]

```

**Release Information**

Statement introduced in Junos OS Release 8.1.

Statement introduced in Junos OS Release 9.0 for EX Series switches.

**detection-time threshold** and **transmit-interval threshold** options introduced in Junos OS Release 8.2

Support for logical routers introduced in Junos OS Release 8.3.

Support for IBGP and multihop EBGP sessions introduced in Junos OS Release 8.3.

**holddown-interval** statement introduced in Junos OS Release 8.5. You can configure this statement only for EBGP peers at the **[edit protocols bgp group *group-name* neighbor *address*]** hierarchy level.

**no-adaptation** statement introduced in Junos OS Release 9.0.

Support for BFD authentication introduced in Junos OS Release 9.6.

Support for BFD on IPv6 interfaces with BGP introduced in Junos OS Release 11.2.  
Statement introduced in Junos OS Release 12.1 for the QFX Series.  
Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.

**Description** Configure bidirectional failure detection (BFD) timers and authentication for BGP.

For IBGP and multihop EBGP support, configure the **bfd-liveness-detection** statement at the global **[edit bgp protocols]** hierarchy level. You can also configure IBGP and multihop support for a routing instance or a logical system.

**Options** **authentication algorithm** *algorithm-name* (Optional)—Configure the algorithm used to authenticate the specified BFD session: **simple-password**, **keyed-md5**, **keyed-sha-1**, **meticulous-keyed-md5**, **meticulous-keyed-sha-1**.

**authentication key-chain** *key-chain-name* (Optional)—Associate a security key with the specified BFD session using the name of the security keychain. The keychain name must match one of the keychains configured in the **authentication-key-chains key-chain** statement at the **[edit security]** hierarchy level.

**authentication loose-check**—(Optional) Configure loose authentication checking on the BFD session. Use only for transitional periods when authentication may not be configured at both ends of the BFD session.

**detection-time threshold** *milliseconds* (Optional)—Configure a threshold. When the BFD session detection time adapts to a value equal to or greater than the threshold, a single trap and a single system log message are sent.

**holddown-interval** *milliseconds* (Optional)—Configure an interval specifying how long a BFD session must remain up before a state change notification is sent. When you configure the hold-down interval for the BFD protocol for EBGp, the BFD session is unaware of the BGP session during this time. In this case, if the BGP session goes down during the configured hold-down interval, BFD already assumes it is down and does not send a state change notification. The **holddown-interval** statement is supported only for EBGp peers at the **[edit protocols bgp group group-name neighbor address]** hierarchy level. If the BFD session goes down and then comes back up during the configured hold-down interval, the timer is restarted. You must configure the hold-down interval on both EBGp peers. If you configure the hold-down interval for a multihop EBGp session, you must also configure a local IP address by including the **local-address** statement at the **[edit protocols bgp group group-name]** hierarchy level.

**Range:** 0 through 255,000

**Default:** 0

**minimum-interval** *milliseconds* (Required)—Configure the minimum intervals at which the local routing device transmits hello packets and then expects to receive a reply from a neighbor with which it has established a BFD session. This value represents the minimum interval at which the local routing device transmits hello packets as well as the minimum interval that the routing device expects to receive a reply from a neighbor with which it has established a BFD session. You can configure a value in the range from 1 through 255,000 milliseconds. Optionally, instead of using this statement, you can specify the minimum transmit and receive intervals separately (using the **minimum-receive-interval** and **transmit-interval** statements).

**Range:** 1 through 255,000

**minimum-receive-interval** *milliseconds* (Optional)—Configure only the minimum interval at which the local routing device expects to receive a reply from a neighbor with which it has established a BFD session.

**Range:** 1 through 255,000

**multiplier *number*** (Optional)—Configure the number of hello packets not received by a neighbor that causes the originating interface to be declared down.

**Range:** 1 through 255

**Default:** 3

**no-adaptation** (Optional)—Configure BFD sessions not to adapt to changing network conditions. We recommend that you not disable BFD adaptation unless it is preferable to not to have BFD adaptation enabled in your network.

**transmit-interval threshold *milliseconds*** (Optional)—Configure a threshold. When the BFD session transmit interval adapts to a value greater than the threshold, a single trap and a single system message are sent. The interval threshold must be greater than the minimum transmit interval.

**Range:** 0 through 4,294,967,295 ( $2^{32} - 1$ )

**transmit-interval minimum-interval *milliseconds*** (Optional)—Configure only the minimum interval at which the local routing device transmits hello packets to a neighbor with which it has established a BFD session.

**Range:** 1 through 255,000

**version** (Optional)—Configure the BFD version to detect.

**Range:** 1 or **automatic** (autodetect the BFD version)

**Default:** **automatic**

The remaining statements are explained separately.

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration. |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Related Documentation</b> | <ul style="list-style-type: none"><li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li><li>• <i>Example: Configuring BFD Authentication for Securing Static Routes</i></li><li>• <a href="#">Example: Configuring BFD on Internal BGP Peer Sessions on page 222</a></li><li>• <a href="#">Example: Configuring BFD Authentication for BGP on page 232</a></li><li>• <a href="#">Understanding BFD for BGP on page 221</a></li></ul> |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|




## bgp

---

|                                 |                                                                                                                                                                                                                                                                             |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>bgp { ... }</code>                                                                                                                                                                                                                                                    |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> protocols bgp],<br>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],<br>[edit protocols],<br>[edit routing-instances <i>routing-instance-name</i> protocols] |
| <b>Release Information</b>      | Statement introduced before Junos OS Release 7.4.<br>Statement introduced in Junos OS Release 9.0 for EX Series switches.<br>Statement introduced in Junos OS Release 11.3 for the QFX Series.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.  |
| <b>Description</b>              | Enable BGP on the routing device or for a routing instance.                                                                                                                                                                                                                 |
| <b>Default</b>                  | BGP is disabled.                                                                                                                                                                                                                                                            |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                         |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <i>BGP Feature Guide</i></li> </ul>                                                                                                                                                                                                |

## bgp-orf-cisco-mode

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>bgp-orf-cisco-mode;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> routing-options <b>outbound-route-filter</b>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-options <b>outbound-route-filter</b>],</p> <p>[edit protocols bgp <b>outbound-route-filter</b>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>outbound-route-filter</b>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> <b>outbound-route-filter</b>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>outbound-route-filter</b>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>outbound-route-filter</b>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> <b>outbound-route-filter</b>],</p> <p>[edit routing-instances <i>routing-instance-name</i> routing-options <b>outbound-route-filter</b>],</p> <p>[edit routing-options <b>outbound-route-filter</b>]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 9.2.</p> <p>Statement introduced in Junos OS Release 9.2 for EX Series switches.</p> <p>Support for the BGP group and neighbor hierarchy levels introduced in Junos OS Release 9.2.</p> <p>Support for the BGP group and neighbor hierarchy levels introduced in Junos OS Release 9.3 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 12.3 for ACX Series routers.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>         | Enable interoperability with routing devices that use the vendor-specific outbound route filter compatibility code of 130 and code type of 128.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                            | <p> <b>NOTE:</b> To enable interoperability for all BGP peers configured on the routing device, include the statement at the [edit routing-options outbound-route-filter] hierarchy level.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Default</b>             | Disabled                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

|                              |                                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege</b>    | routing—To view this statement in the configuration.                                                                                         |
| <b>Level</b>                 | routing-control—To add this statement to the configuration.                                                                                  |
| <b>Related Documentation</b> | <ul style="list-style-type: none"><li>• <a href="#">Example: Configuring BGP Prefix-Based Outbound Route Filtering on page 181</a></li></ul> |

## cluster

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>cluster <i>cluster-identifier</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Description</b>         | Specify the cluster identifier to be used by the route reflector cluster in an internal BGP group.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



### CAUTION:

If you configure both route reflection and VPNs on the same routing device, the following modifications to the route reflection configuration cause current BGP sessions to be reset:

- Adding a cluster ID—If a BGP session shares the same AS number with the group where you add the cluster ID, all BGP sessions are reset regardless of whether the BGP sessions are contained in the same group.
- Creating a new route reflector—If you have an IBGP group with an AS number and create a new route reflector group with the same AS number, all BGP sessions in the IBGP group and the new route reflector group are reset.



**NOTE:** If you change the address family specified in the [edit protocols bgp family] hierarchy level, all current BGP sessions on the routing device are dropped and then reestablished.

|                                 |                                                                                                                                                                                                                                                                      |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Options</b>                  | <i>cluster-identifier</i> —4-byte number (such as an IPv4 address).                                                                                                                                                                                                  |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                  |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring BGP Route Reflectors on page 285</a></li> <li>• <a href="#">Understanding External BGP Peering Sessions on page 13</a></li> <li>• <a href="#">no-client-reflect on page 468</a></li> </ul> |

## connection-mode

|                                 |                                                                                                                                                                                                                                                                         |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | connection-mode (active   passive);                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <i>station station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <i>station station-name</i> ] |
| <b>Release Information</b>      | Statement introduced for BMP in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced for BMP in Junos OS Release 13.3.                                                                                                                              |
| <b>Description</b>              | Specifies whether the BMP station connection is <b>active</b> or <b>passive</b> .                                                                                                                                                                                       |
| <b>Options</b>                  | <p><b>active</b>—BMP initiates the connection to the BMP station.</p> <p><b>passive</b>—BMP does not initiate a connection the BMP station. However, it does listen for a connection request from active BMP stations and will connect if a station is available.</p>   |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                     |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li> </ul>                                                                                                                                            |

## damping (Protocols BGP)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | damping;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i> family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i> family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> family <i>family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i> family <i>family</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> family <i>family</i>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i> family <i>family</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp family <i>family</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> family <i>family</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i> family <i>family</i>]</p> |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Support for flap damping at the address family level introduced in Junos OS Release 12.2.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>         | Enable route flap damping. BGP route flapping describes the situation in which BGP systems send an excessive number of update messages to advertise network reachability                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

information. Flap damping reduces the number of update messages sent between BGP peers, thereby reducing the load on these peers, without adversely affecting the route convergence time for stable routes.

You typically apply flap damping to external BGP (EBGP) routes (that is, to routes in different ASs). You can also apply it within a confederation, between confederation member ASs. Because routing consistency within an AS is important, do not apply flap damping to internal BGP (IBGP) routes. (If you do, it is ignored.) The exception to this rule is when flap damping is applied at the address family level. When you apply flap damping at the address family level, it works for both IBGP and EBGP.

**Default** Flap damping is disabled on the routing device.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- [Examples: Configuring BGP Flap Damping on page 340](#)
- [Example: Configuring BGP Route Flap Damping Based on the MBGP MVPN Address Family on page 350](#)

## description (Protocols BGP)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>description text-description;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>              | Provide a description of the global, group, or neighbor configuration. If the text includes one or more spaces, enclose it in quotation marks (" "). The text is displayed in the output of the <b>show</b> command and has no effect on the configuration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Options</b>                  | <i>text-description</i> —Text description of the configuration. It is limited to 255 characters.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li><i>BGP Feature Guide</i></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |



## detection-time (BFD Liveness Detection)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <pre> detection-time {     threshold milliseconds; } </pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Hierarchy Level</b>     | <pre> [edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>   bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>   bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp group <i>group-name</i> bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   l2vpn oam bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   vpls oam bfd-liveness-detection], [edit protocols bgp bfd-liveness-detection], [edit protocols bgp group <i>group-name</i> bfd-liveness-detection], [edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>   bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor   <i>address</i> bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam   bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i>   neighbor <i>neighbor-id</i> oam bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection] </pre> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.2.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPNs and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Description</b>         | <p>Enable BFD failure detection. The BFD failure detection timers are adaptive and can be adjusted to be faster or slower. The lower the BFD failure detection timer value, the faster the failure detection and vice versa. For example, the timers can adapt to a higher value if the adjacency fails (that is, the timer detects failures more slowly). Or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

A back-off algorithm increases the receive (Rx) interval by two if the local BFD instance is the reason for the session flap. The transmission (Tx) interval is increased by two if the remote BFD instance is the reason for the session flap. You can use the **clear bfd adaptation** command to return BFD interval timers to their configured values. The **clear bfd adaptation** command is hitless, meaning that the command does not affect traffic flow on the routing device.

The remaining statement is explained separately.

|                                 |                                                                |
|---------------------------------|----------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.           |
|                                 | routing-control—To add this statement to the configuration.    |
| <b>Related Documentation</b>    | • <i>Configuring BFD for Layer 2 VPN and VPLS</i>              |
|                                 | • <a href="#">Example: Configuring BFD for BGP on page 221</a> |
|                                 | • <a href="#">bfd-liveness-detection on page 395</a>           |
|                                 | • <a href="#">threshold on page 492</a>                        |

---

## disable (Protocols BGP)

---

|                                 |                                                                                                                                                                                                                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | disable;                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> protocols bgp],<br>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],<br>[edit protocols bgp],<br>[edit routing-instances <i>routing-instance-name</i> protocols bgp] |
| <b>Release Information</b>      | Statement introduced before Junos OS Release 7.4.<br>Statement introduced in Junos OS Release 9.0 for EX Series switches.<br>Statement introduced in Junos OS Release 11.3 for the QFX Series.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.          |
| <b>Description</b>              | Disable BGP on the system.                                                                                                                                                                                                                                                          |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.                                                                                                                                                                                                                                |
|                                 | routing-control—To add this statement to the configuration.                                                                                                                                                                                                                         |

## disable (BGP Graceful Restart)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | disable;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Hierarchy Level</b>     | [edit logical-systems <i>logical-system-name</i> protocols bgp graceful-restart],<br>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> graceful-restart],<br>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i> graceful-restart],<br>[edit protocols bgp graceful-restart],<br>[edit protocols bgp <b>group</b> <i>group-name</i> graceful-restart],<br>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i> graceful-restart] |
| <b>Release Information</b> | Statement introduced before Junos OS Release 7.4.<br>Statement introduced in Junos OS Release 9.0 for EX Series switches.<br>Statement introduced in Junos OS Release 12.1 for the QFX Series.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>         | Disable graceful restart for BGP. Graceful restart allows a routing device undergoing a restart to inform its adjacent neighbors and peers of its condition.                                                                                                                                                                                                                                                                                                                                                                                                                       |



**NOTE:** When you disable graceful restart at one level in the configuration statement hierarchy, it is also disabled at lower levels in the same hierarchy. For example, if you disable graceful restart at the [edit protocols bgp **group** *group-name*] hierarchy level, it is disabled for all the peers in the group. Therefore, if you want to enable graceful restart for some peers in a group and disable it for others, enable graceful restart at the [edit protocols bgp **group** *group-name*] hierarchy level and disable graceful restart for each peer at the [edit protocols bgp **group** *group-name* **neighbor** *address*] hierarchy level.

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>Required Privilege</b> | routing—To view this statement in the configuration.        |
| <b>Level</b>              | routing-control—To add this statement to the configuration. |

|                              |                                                                                                                                                                                                                                                                              |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Related Documentation</b> | <ul style="list-style-type: none"> <li>• <i>Configuring Graceful Restart Options for BGP</i></li> <li>• <a href="#">graceful-restart on page 415</a></li> <li>• <a href="#">restart-time on page 482</a></li> <li>• <a href="#">stale-routes-time on page 486</a></li> </ul> |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## export (Protocols BGP)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>export [ <i>policy-names</i> ];</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | <p>Apply one or more policies to routes being exported from the routing table into BGP.</p> <p>If you specify more than one policy, they are evaluated in the order specified, from left to right, and the first matching filter is applied to the route. If no routes match the filters, the routing table exports into BGP only the routes that it learned from BGP. If an action specified in one of the policies manipulates a route characteristic, the policy framework software carries the new route characteristic forward during the evaluation of the remaining policies. For example, if the action specified in the first policy of a chain sets a route's metric to 500, this route matches the criterion of <b>metric 500</b> defined in the next policy.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Options</b>                  | <i>policy-names</i> —Name of one or more policies.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Configuring Routing Policies to Control BGP Route Advertisements on page 177</a></li> <li>• <a href="#">Routing Policies, Firewall Filters, and Traffic Policers Feature Guide</a></li> <li>• <a href="#">import on page 427</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## family (Protocols BGP)

```

Syntax  family {
        (inet | inet6 | inet-vpn | inet6-vpn | iso-vpn) {
            (any | flow | labeled-unicast | multicast | unicast) {
                accepted-prefix-limit {
                    maximum number;
                    teardown <percentage-threshold> idle-timeout (forever | minutes);
                }
                add-path {
                    send {
                        path-count number;
                        prefix-policy [ policy-names ];
                    }
                    receive;
                }
                algp [disable];
                loops number;
                prefix-limit {
                    maximum number;
                    teardown <percentage> <idle-timeout (forever | minutes)>;
                }
                protection;
                rib-group group-name;
                topology name {
                    community {
                        target identifier;
                    }
                }
            }
            flow {
                no-install;
                no-validate policy-name;
            }
            labeled-unicast {
                accepted-prefix-limit {
                    maximum number;
                    teardown <percentage> <idle-timeout (forever | minutes)>;
                }
                aggregate-label {
                    community community-name;
                }
                explicit-null {
                    connected-only;
                }
                prefix-limit {
                    maximum number;
                    teardown <percentage> <idle-timeout (forever | minutes)>;
                }
                resolve-vpn;
                rib (inet.3 | inet6.3);
                rib-group group-name;
                traffic-statistics {
                    file filename <world-readable | no-world-readable>;
                    interval seconds;
                }
            }
        }
    }

```

```

    }
  }
}
route-target {
  accepted-prefix-limit {
    maximum number;
    proxy-generate <route-target-policy route-target-policy-name>;
    teardown <percentage> <idle-timeout (forever | minutes)>;
  }
  advertise-default;
  external-paths number;
  prefix-limit {
    maximum number;
    teardown <percentage> <idle-timeout (forever | minutes)>;
  }
}
}
(evpn | inet-mdt | inet-mvpn | inet6-mvpn | l2vpn) {
  signaling {
    accepted-prefix-limit {
      maximum number;
      teardown <percentage-threshold> idle-timeout (forever | minutes);
    }
  }
  add-path {
    send {
      path-count number;
      prefix-policy [ policy-names ];
    }
    receive;
  }
  aigp [disable];
  damping;
  loops number;
  prefix-limit {
    maximum number;
    teardown <percentage> <idle-timeout (forever | minutes)>;
  }
  rib-group group-name;
}
}
traffic-engineering;
}

```

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hierarchy Level</b>     | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>], [edit protocols bgp], [edit protocols bgp <b>group</b> <i>group-name</i>], [edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</pre> |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 14.1X53-D30 for the QFX Series.</p> <p>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p> <p><b>inet-mvpn</b> and <b>inet6-mvpn</b> statements introduced in Junos OS Release 8.4.</p> <p><b>inet-mdt</b> statement introduced in Junos OS Release 9.4.</p> <p>Support for the <b>loops</b> statement introduced in Junos OS Release 9.6.</p> <p><b>evpn</b> statement introduced in Junos OS Release 13.2.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p> <p><b>traffic-engineering</b> statement introduced in Junos OS Release 14.2.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>         | <p>Enable multiprotocol BGP (MP-BGP) by configuring BGP to carry network layer reachability information (NLRI) for address families other than unicast IPv4, to specify MP-BGP to carry NLRI for the IPv6 address family, or to carry NLRI for VPNs.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

- Options**
- any**—Configure the family type to be both unicast and multicast.
  - evpn**—Configure NLRI parameters for Ethernet VPNs (EVPNs).
  - inet**—Configure NLRI parameters for IPv4.
  - inet6**—Configure NLRI parameters for IPv6.
  - inet-mdt**—Configure NLRI parameters for the multicast distribution tree (MDT) subaddress family identifier (SAFI) for IPv4 traffic in Layer 3 VPNs.
  - inet-mvpn**—Configure NLRI parameters for IPv4 for multicast VPNs.
  - inet6-mvpn**—Configure NLRI parameters for IPv6 for multicast VPNs.
  - inet-vpn**—Configure NLRI parameters for IPv4 for Layer 3 VPNs.
  - inet6-vpn**—Configure NLRI parameters for IPv6 for Layer 3 VPNs.
  - iso-vpn**—Configure NLRI parameters for IS-IS for Layer 3 VPNs.
  - l2vpn**—Configure NLRI parameters for IPv4 for MPLS-based Layer 2 VPNs and VPLS.
  - labeled-unicast**—Configure the family type to be labeled-unicast. This means that the BGP peers are being used only to carry the unicast routes that are being used by labeled-unicast for resolving the labeled-unicast routes. This statement is supported only with **inet** and **inet6**.
  - multicast**—Configure the family type to be multicast. This means that the BGP peers are being used only to carry the unicast routes that are being used by multicast for resolving the multicast routes.
  - unicast**—Configure the family type to be unicast. This means that the BGP peers only carry the unicast routes that are being used for unicast forwarding purposes. The default family type is **unicast**.

The remaining statements are explained separately.

**Required Privilege Level**


- routing—To view this statement in the configuration.
- routing-control—To add this statement to the configuration.

**Related Documentation**

- *Configuring IBGP Sessions Between PE Routers in VPNs*
- *Understanding Multiprotocol BGP*
- *autonomous-system*
- [local-as on page 438](#)



## graceful-restart (Protocols BGP)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <pre> graceful-restart {     disable;     restart-time seconds;     stale-routes-time seconds; } </pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],<br/> [edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],<br/> [edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],<br/> [edit protocols bgp],<br/> [edit protocols bgp <b>group</b> <i>group-name</i>],<br/> [edit protocols bgp <i>group</i> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.<br/> Statement introduced in Junos OS Release 9.0 for EX Series switches.<br/> Statement introduced in Junos OS Release 12.1 for the QFX Series.<br/> Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Description</b>              | <p>Configure graceful restart for BGP. Graceful restart allows a routing device undergoing a restart to inform its adjacent neighbors and peers of its condition. Graceful restart is disabled by default. However, helper mode, the ability to assist a neighboring router attempting a graceful restart, is enabled by default.</p> <p>To configure the duration of the BGP graceful restart period, include the <b>restart-time</b> statement at the [edit protocols bgp graceful-restart] hierarchy level. To set the length of time the router waits to receive messages from restarting neighbors before declaring them down, include the <b>stale-routes-time</b> statement at the [edit protocols bgp graceful-restart] hierarchy level.</p> <div style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"> <p> <b>NOTE:</b> If you configure graceful restart after a BGP session has been established, the BGP session restarts and the peers negotiate graceful restart capabilities.</p> </div> <p>Configure graceful restart globally at the [edit routing-options] or [edit routing-instances <i>instance-name</i> routing-options] hierarchy level to enable the feature. You cannot enable graceful restart for specific protocols unless graceful restart is also enabled globally. Configuring graceful restart at the global [edit routing-options] hierarchy level enables graceful restart for all protocols. You can, optionally, modify the global settings at the individual protocol level. For example, disable graceful restart for BGP at the protocol level.</p> <p>The remaining statements are explained separately.</p> |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.<br/> routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

- Related Documentation**
- *Configuring Graceful Restart Options for BGP*
  - *Configuring Graceful Restart for QFabric Systems*
  - *Junos OS High Availability Library for Routing Devices*

## group (Protocols BGP)

```
Syntax  group group-name {
    advertise-bgp-static
    advertise-inactive;
    allow [ network/mask-length ];
    authentication-key key;
    cluster cluster-identifier;
    damping;
    description text-description;
    enforce-first-as;
    export [ policy-names ];
    family {
        (inet | inet6 | inet-vpn | inet6-vpn | l2-vpn) {
            (any | multicast | unicast | signaling) {
                accepted-prefix-limit {
                    maximum number;
                    teardown <percentage> <idle-timeout (forever | minutes)>;
                }
            }
            add-path {
                send {
                    path-count number;
                    prefix-policy [ policy-names ];
                }
                receive;
            }
            aigp [disable];
            damping;
            prefix-limit {
                maximum number;
                teardown <percentage> <idle-timeout (forever | minutes)>;
            }
            rib-group group-name;
            topology name {
                community {
                    target identifier;
                }
            }
        }
    }
    flow {
        no-validate policy-name;
    }
    labeled-unicast {
        accepted-prefix-limit {
            maximum number;
            teardown <percentage> <idle-timeout (forever | minutes)>;
        }
        explicit-null {
            connected-only;
        }
        prefix-limit {
            maximum number;
            teardown <percentage> <idle-timeout (forever | minutes)>;
        }
    }
}
```

```

        resolve-vpn;
        rib inet.3;
        rib-group group-name;
    }
}
route-target {
    accepted-prefix-limit {
        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
    }
    advertise-default;
    external-paths number;
    prefix-limit {
        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
    }
}
}
graceful-restart {
    long-lived {
        receiver {
            enable;
            disable;
        }
        advertise-to-non-llgr-neighbor {
            omit-no-export;
        }
    }
}
graceful-restart {
    long-lived {
        disable-notification-flag;
        disable-notification-extensions {
            omit-no-export;
        }
        forwarding-state-bit (from-fib | set); /* Configurable to be common for all address
        families */
        forwarding-state-bit (as-rr-client | from-fib); /* Configurable for each address family
        */
        restarter {
            disable;
            stale-time interval;
        }
    }
}
}
hold-time seconds;
import [ policy-names ];
ipsec-sa ipsec-sa;
keep (all | none);
local-address address;
local-as autonomous-system <private>;
local-preference local-preference;
log-updown;
metric-out metric;
multihop <ttl-value>;
multipath {

```

```

    multiple-as;
}
mvpn-iana-rt-import;
no-aggregator-id;
no-client-reflect;
out-delay seconds;
passive;
peer-as autonomous-system;
preference preference;
remove-private;
rfc6514-compliant-safi129;
tcp-aggressive-transmission;
tcp-mss segment-size;
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
type type;
neighbor address {
    ... peer-specific-options ...
}
}

```

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hierarchy Level          | [edit logical-systems <i>logical-system-name</i> protocols bgp],<br>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],<br>[edit protocols bgp],<br>[edit routing-instances <i>routing-instance-name</i> protocols bgp]                                                                                                                                                                                                                                                                                                     |
| Release Information      | Statement introduced before Junos OS Release 7.4.<br>Statement introduced in Junos OS Release 9.0 for EX Series switches.<br>Statement introduced in Junos OS Release 11.3 for the QFX Series.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                              |
| Description              | <p>Define a BGP peer group. BGP peer groups share a common type, peer autonomous system (AS) number, and cluster ID, if present. To configure multiple BGP groups, include multiple <b>group</b> statements.</p> <p>By default, the group's options are identical to the global BGP options. To override the global options, include group-specific options within the <b>group</b> statement.</p> <p>The <b>group</b> statement is one of the statements you must include in the configuration to run BGP on the routing device.</p> <p>Each group must contain at least one peer.</p> |
| Options                  | <p><b>group-name</b>—Name of the BGP group.</p> <p>The remaining statements are explained separately.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Required Privilege Level | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

**Related Documentation**

- *BGP Feature Guide*

## hold-down

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <pre>hold-down {     seconds;     flaps number;     period seconds; }</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Hierarchy Level</b>          | <pre>[edit logical-systems logical-system-name routing-options bmp], [edit logical-systems logical-system-name routing-options bmp station station-name], [edit routing-options bmp], [edit routing-options bmp station station-name]</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.3.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Description</b>              | <p>If the connection to a BMP station flaps and the <b>hold-down</b> statement is configured, the station is prevented from reconnecting to the device for the specified period of time. A flap is when the TCP session unexpectedly switches from established to non-established. If you alter the configuration of the <b>hold-down</b> statement, the hold down timer and flap counter are reset.</p> <p>You can effectively disable the <b>hold-down</b> statement by setting the <b>flaps</b> option to 10 and the <b>period</b> option to 30 seconds.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Options</b>                  | <p><b>seconds</b>—Specify the time in seconds to wait before allowing the BMP station to reconnect to the device.</p> <p><b>Default:</b> 600 seconds</p> <p><b>Range:</b> 30 through 65,535 seconds</p> <p><b>flaps number</b>—Specify the number of BMP station flaps allowed before terminating the connection to the BMP station and triggering the hold down timer.</p> <p><b>Default:</b> 3 flaps</p> <p><b>Range:</b> 2 to 10 flaps</p> <p><b>period seconds</b>—Specify the time in seconds for the BGP station flaps (specified using the <b>flaps</b> option) to occur before triggering the hold down timer. Every time a flap occurs, the number of flaps in the last time period is checked to see if the criteria is met.</p> <p>For example, if you defined the <b>period</b> as 60 seconds and the <b>flaps</b> as 4 and the BGP station flaps just 2 times in a 60 second period, the hold down timer would not be triggered. However, if the BGP station flaps 4 times in a 60 second period, the hold down timer would be triggered.</p> <p><b>Default:</b> 300 seconds</p> <p><b>Range:</b> 30 through 65,535 seconds</p> |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

- Related Documentation**
- [Configuring BGP Monitoring Protocol Version 3 on page 59](#)



## hold-down-interval (BGP BFD Liveness Detection)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>holddown-interval <i>milliseconds</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit protocols bgp bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 8.5.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Description</b>              | <p>Configure an interval specifying how long a BFD session must remain up before a state change notification is sent.</p> <p>When you configure the hold-down interval for the BFD protocol for EBG, the BFD session is unaware of the BGP session during this time. In this case, if the BGP session goes down during the configured hold-down interval, BFD already assumes the BGP session is down and does not send a state change notification. The <b>holddown-interval</b> statement is supported only for EBG peers at the <b>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>]</b> hierarchy level. If the BFD session goes down and then comes back up during the configured hold-down interval, the timer is restarted. You must configure the hold-down interval on both EBG peers. If you configure the hold-down interval for a multihop EBG session, you must also configure a local IP address by including the <b>local-address</b> statement at the <b>[edit protocols bgp group <i>group-name</i>]</b> hierarchy level.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Options</b>                  | <p><b><i>milliseconds</i></b>—Specify the hold-down interval value.</p> <p><b>Range:</b> 0 through 255,000</p> <p><b>Default:</b> 0</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

- Related Documentation**
- *Example: Configuring BFD for Static Routes for Faster Network Failure Detection*
  - [bfd-liveness-detection on page 395](#)

## hold-time (Protocols BGP)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>hold-time seconds;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Hierarchy Level</b>     | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i> <i>neighbor address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name neighbor address</i>], [edit protocols bgp], [edit protocols bgp <i>group group-name</i>], [edit protocols bgp <i>group group-name neighbor address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i> <i>neighbor address</i>]</pre>                                                                                                                           |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Description</b>         | <p>Specify the hold-time value to use when negotiating a connection with the peer. The hold-time value is advertised in open packets and indicates to the peer the length of time that it should consider the sender valid. If the peer does not receive a keepalive, update, or notification message within the specified hold time, the BGP connection to the peer is closed and routing devices through that peer become unavailable.</p> <p>The hold time is three times the interval at which keepalive messages are sent.</p> <p>BGP on the local routing device uses the smaller of either the local hold-time value or the peer's hold-time value received in the open message as the hold time for the BGP connection between the two peers.</p> <p>Starting in Junos OS Release 12.3, the BGP hold-time value can be zero (0). This implies that the speaker does not expect keepalive messages from its peer to maintain the BGP session. When negotiating between two peers, if one side requests a nonzero hold time and the other requests a zero hold time, the negotiation settles on the nonzero value and keepalive intervals are determined accordingly. Both sides must be set to zero for keepalive messages to stop being sent.</p> |
| <b>Options</b>             | <p><b>seconds</b>—Hold time.</p> <p><b>Range:</b> 10 through 65,535 seconds (or 0 for infinite hold time)</p> <p><b>Default:</b> 90 seconds</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |



**TIP:** When you set a hold-time value of 1 through 19 seconds, we recommend that you also configure the BGP `precision-timers` statement. The `precision-timers` statement ensures that if scheduler slip messages occur, the routing device continues to send keepalive messages. When the `precision-timers` statement is included, keepalive message generation is performed in a dedicated kernel thread, which helps to prevent BGP session flaps.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- [BGP Messages Overview on page 7](#)
- *precision-timers*

## import

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>import [ <i>policy-names</i> ];</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p>                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Description</b>         | <p>Apply one or more routing policies to routes being imported into the Junos OS routing table from BGP.</p> <p>If you specify more than one policy, they are evaluated in the order specified, from left to right, and the first matching filter is applied to the route. If no match is found, BGP places into the routing table only those routes that were learned from BGP routing devices. The policy framework software evaluates the routing policies in a chain sequentially. If an action specified in one of the policies manipulates a route characteristic, the policy framework software carries the new route characteristic forward during the evaluation of the remaining policies. For example, if the action specified in the first policy of a chain sets a route's metric to 500, this route matches the criterion of <b>metric 500</b> defined in the next policy.</p> <p>It is also important to understand that in Junos OS, although an import policy (inbound route filter) might reject a route, not use it for traffic forwarding, and not include it in an advertisement to other peers, the router retains these routes as hidden routes. These hidden routes are not available for policy or routing purposes. However, they do occupy memory space on the router. A service provider filtering routes to control the amount of information being kept in memory and processed by a router might want the router to entirely drop the routes being rejected by the import policy.</p> <p>Hidden routes can be viewed by using the <b>show route receive-protocol bgp neighbor-address hidden</b> command. The hidden routes can then be retained or dropped from the routing</p> |

table by configuring the **keep all | none** statement at the **[edit protocols bgp]** or **[edit protocols bgp group *group-name*]** hierarchy level.

The rules of BGP route retention are as follows:

- By default, all routes learned from BGP are retained, except those where the AS path is looped. (The AS path includes the local AS.)
- By configuring the **keep all** statement, all routes learned from BGP are retained, even those with the local AS in the AS path.
- By configuring the **keep none** statement, all routes received are discarded. When this statement is configured and the inbound policy changes, Junos OS re-advertises all the routes advertised by the peer.

**Options**    *policy-names*—Name of one or more policies.

**Required Privilege Level**    routing—To view this statement in the configuration.  
                                         routing-control—To add this statement to the configuration.

**Related Documentation**

- [Example: Configuring BGP Interactions with IGP](#)s on page 173
- [Configuring Routing Policies to Control BGP Route Advertisements](#) on page 177
- [Understanding Routing Policies](#) on page 173
- [export](#) on page 410

## include-mp-next-hop

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | include-mp-next-hop;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | Enable multiprotocol updates to contain next-hop reachability information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <i>Example: Configuring IPv6 BGP Routes over IPv4 Transport</i></li> <li>• <i>Enabling Layer 2 VPN and VPLS Signaling</i></li> <li>• <i>Understanding Multiprotocol BGP</i></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## initiation-message

---

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | initiation-message <i>text</i> ;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <b>station</b> <i>station-name</i> ]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Description</b>              | <p>(Optional) Allows you to specify an initiation message for a type 0 TLV to be sent to the BMP station. The message is transmitted when a BMP station establishes a connection to the device. You can provide some information to the BMP station system administrator (for example, a contact phone number). The initiation message includes a type 1 TLV containing the SNMP sysDescr value specified in RFC 1213 <i>Management Information Base for Network Management of TCP/IP-based internets: MIB-II</i> and a type 2 TLV containing the SNMP sysName value also from RFC 1213. The string in the initiation-message message is UTF-8.</p> <p>The normal time for sending an initiation message is when the BMP session is first established. However, an initiation message change also triggers the transmission of an initiation message to current BMP sessions.</p> <p>Another event that triggers the transmission of an initiation message is when you change in the sysName or sysDescr values in the SNMP configuration. The initiation message is sent to current BMP sessions.</p> |
| <b>Options</b>                  | <b>text</b> —Specify a character string for a type 0 TLV to send with the initiation message.<br><b>Range:</b> 1 through 255 characters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



## keep

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | keep (all   none);                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>     | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>   <i>neighbor address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp <i>group group-name</i> <i>neighbor address</i>], [edit protocols bgp], [edit protocols bgp <i>group group-name</i>], [edit protocols bgp <i>group group-name</i> <i>neighbor address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>   <i>neighbor address</i>]</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>         | <p>Control whether or not Junos OS keeps in memory and hides certain routes.</p> <p>If the <b>keep none</b> statement is used, Junos OS does not retain in memory and hide routes that are rejected because of a BGP import policy. Nor does BGP keep in memory and hide routes that are declared unfeasible due to BGP sanity checks. The <b>keep none</b> statement causes Junos OS to discard from memory the routes that are rejected due to BGP-specific logic or BGP evaluation. When a route is rejected because of some non-BGP-specific reason, the <b>keep none</b> statement has no effect on this route. This rejected route is retained in memory and hidden even though <b>keep none</b> is configured. An example of this type of hidden route is a route for which the protocol nexthop is unresolved.</p> <p>The routing table can retain the route information learned from BGP in one of the following ways:</p> <ul style="list-style-type: none"> <li>• Default (omit the <b>keep</b> statement)—Keep all route information that was learned from BGP, except for routes whose AS path is looped and whose loop includes the local AS.</li> <li>• <b>keep all</b>—Keep all route information that was learned from BGP.</li> <li>• <b>keep none</b>—Discard routes that were received from a peer and that were rejected by import policy or other sanity checking, such as AS path or next hop. When you configure <b>keep none</b> for the BGP session and the inbound policy changes, Junos OS forces readvertisement of the full set of routes advertised by the peer.</li> </ul> |

In an AS path healing situation, routes with looped paths theoretically could become usable during a soft reconfiguration when the AS path loop limit is changed. However, there is a significant memory usage difference between the default and **keep all**.

Consider the following scenarios:

- A peer readadvertises routes back to the peer from which it learned them.

This can happen in the following cases:

- Another vendor's routing device advertises the routes back to the sending peer.
- The Junos OS peer's default behavior of not readvertising routes back to the sending peer is overridden by configuring **advertise-peer-as**.
- A provider edge (PE) routing device discards any VPN route that does not have any of the expected route targets.

When **keep all** is configured, the behavior of discarding routes received in the above scenarios is overridden.



**CAUTION:** If you add or remove **keep all** or **keep none** and the peer does not support session restart, the associated BGP sessions are restarted (flapped). To determine if a peer supports refresh, check for **Peer supports Refresh capability** in the output of the **show bgp neighbor** command.

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Default</b>                  | By default, BGP retains incoming rejected routes in memory and hides them. If you do not include the <b>keep</b> statement, most routes are retained in the routing table. BGP keeps all route information that was learned from BGP, except for routes whose AS path is looped and whose loop includes the local AS.                                                                                                                 |
| <b>Options</b>                  | <p><b>all</b>—Retain all routes.</p> <p><b>none</b>—Discard routes that were received from a peer and that were rejected by import policy or other sanity checking. When <b>keep none</b> is configured for the BGP session and the inbound policy changes, Junos OS forces readvertisement of the full set of routes advertised by the peer.</p>                                                                                     |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                        |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Configuring Routing Policies to Control BGP Route Advertisements on page 177</a></li> <li>• <a href="#">out-delay on page 469</a></li> <li>• <i>Interprovider VPN Example—MP-EBGP Between ISP Peer Routers</i></li> <li>• <i>Example: Configuring a Routing Policy for Conditional Advertisement Enabling Conditional Installation of Prefixes in a Routing Table</i></li> </ul> |

## key-chain (BGP BFD Authentication)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>key-chain <i>key-chain-name</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit protocols bgp bgp bfd-liveness-detection authentication],</p> <p>[edit protocols bgp group <i>group-name</i> bgp bfd-liveness-detection authentication],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 8.1.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>              | Associate a security key with the specified BFD session using the name of the security keychain. Each key has a unique start time within the keychain. Keychain authentication allows you to change the password information periodically without bringing down peering sessions. This keychain authentication method is referred to as <i>hitless</i> because the keys roll over from one to the next without resetting any peering sessions or interrupting the routing protocol.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Options</b>                  | <b><i>key-chain-name</i></b> —Name of the authentication keychain. The keychain name must match one of the keychains configured with the <b>key-chain <i>key-chain-name</i></b> statement at the [edit security authentication-key-chain] hierarchy level.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li> <li>• <i>Example: Configuring BFD Authentication for Securing Static Routes</i></li> <li>• <a href="#">Example: Configuring BFD on Internal BGP Peer Sessions on page 222</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

- [Example: Configuring BGP Route Authentication on page 311](#)
- [Example: Configuring EBGP Multihop Sessions on page 186](#)

## local-address (Protocols BGP)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>local-address address;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Hierarchy Level</b>     | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>   <i>neighbor address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp <i>group group-name</i> <i>neighbor address</i>], [edit protocols bgp], [edit protocols bgp <i>group group-name</i>], [edit protocols bgp <i>group group-name</i> <i>neighbor address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>   <i>neighbor address</i>]</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Description</b>         | <p>Specify the address of the local end of a BGP session. This address is used to accept incoming connections to the peer and to establish connections to the remote peer. When none of the operational interfaces are configured with the specified local address, a session with a BGP peer is placed in the idle state.</p> <p>You generally configure a local address to explicitly configure the system's IP address from BGP's point of view. This IP address can be either an IPv6 or IPv4 address. Typically, an IP address is assigned to a loopback interface, and that IP address is configured here.</p> <p>For internal BGP (IBGP) peering sessions, generally the loopback interface (lo0) is used to establish connections between the IBGP peers. The loopback interface is always up as long as the device is operating. If there is a route to the loopback address, the IBGP peering session stays up. If a physical interface address is used instead and that interface goes up and down, the IBGP peering session also goes up and down. Thus, the loopback interface provides fault tolerance in case the physical interface or the link goes down, if the device has link redundancy.</p> <p>When a device peers with a remote device's loopback interface address, the local device expects BGP update messages to come from (be sourced by) the remote device's loopback interface address. The <b>local-address</b> statement enables you to specify the source information in BGP update messages. If you omit the <b>local-address</b> statement, the expected source of BGP update messages is based on the device's source address selection rules, which normally result in the egress interface address being the expected source of update messages. When this happens, the peering session is not established</p> |

because a mismatch exists between the expected source address (the egress interface of the peer) and the actual source (the loopback interface of the peer). To ensure that the expected source address matches the actual source address, specify the loopback interface address in the **local-address** statement.



**NOTE:** Although a BGP session can be established when only one of the paired routing devices has **local-address** configured, we strongly recommend that you configure **local-address** on both paired routing devices for IBGP and multihop EBGP sessions. The **local-address** statement ensures that deterministic fixed addresses are used for the BGP session end-points.

If you include the **default-address-selection** statement in the configuration, the software chooses the system default address as the source for most locally generated IP packets. For protocols in which the local address is unconstrained by the protocol specification, for example IBGP and multihop EBGP, if you do not configure a specific local address when configuring the protocol, the local address is chosen using the same methods as other locally generated IP packets.

**Default** If you do not configure a local address, BGP uses the routing device's source address selection rules to set the local address.

**Options** **address**—IPv6 or IPv4 address of the local end of the connection.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- [Example: Configuring Internal BGP Peering Sessions on Logical Systems on page 48](#)
- [Example: Configuring Internal BGP Peer Sessions on page 37](#)
- [Understanding Internal BGP Peering Sessions on page 36](#)
- *router-id*

## local-address (Protocols BMP)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>local-address <i>address</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> routing-options bmp],<br/> [edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i>],<br/> [edit routing-options bmp],<br/> [edit routing-options bmp <b>station</b> <i>station-name</i>]</p>                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.3.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Description</b>              | <p>(Optional) Specifies the IPv4 or IPv6 address for the BMP connection on the device. We recommend that you configure a local address. For both active and passive modes, configure a loopback local address. This provides a consistent local endpoint, is useful for debugging, and assures greater reliability for the BMP connection since it is not tied to a single router interface.</p> <p>For passive mode, specifying a local address is required. It also provides some security against a malicious BMP connection. For active mode, we also recommend configuring a local address to help ensure reliability.</p> <p>If you change the local address, the BMP station connection flaps when you commit the configuration.</p> |
| <b>Options</b>                  | <b>address</b> —Specify the IPv4 or IPv6 address for the BMP connection on the local device.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## local-as

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>local-as <i>autonomous-system</i> &lt;loops number&gt; &lt;private   alias&gt; &lt;no-prepend-global-as&gt;;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <i>group group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p> |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p><i>alias</i> option introduced in Junos OS Release 9.5.</p> <p><i>no-prepend-global-as</i> option introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Description</b>         | <p>Specify the local autonomous system (AS) number. An AS is a set of routing devices that are under a single technical administration and generally use a single interior gateway protocol (IGP) and metrics to propagate routing information within the set of routing devices.</p> <p>Internet service providers (ISPs) sometimes acquire networks that belong to a different AS. When this occurs, there is no seamless method for moving the BGP peers of the acquired network to the AS of the acquiring ISP. The process of configuring the BGP peers with the new AS number can be time-consuming and cumbersome. In this case, it might not be desirable to modify peer arrangements or configuration. During this kind of transition period, it can be useful to configure BGP-enabled devices in the new AS to use the former AS number in BGP updates. This former AS number is called a <i>local</i> AS.</p>                                                                                                                                                                                                                                                                                              |



**NOTE:** If you are using BGP on the routing device, you must configure an AS number before you specify the local as number.

In Junos OS Release 9.1 and later, the AS numeric range in plain-number format is extended to provide BGP support for 4-byte AS numbers, as defined in RFC 4893, *BGP Support for Four-octet AS Number Space*.

In Junos OS Release 9.3 and later, you can also configure a 4-byte AS number using the AS-dot notation format of two integer values joined by a period:



*<16-bit high-order value in decimal>.<16-bit low-order value in decimal>.* For example, the 4-byte AS number of 65546 in plain-number format is represented as 1.10 in the AS-dot notation format.

The auto route target feature does not support the local AS number for BGP neighbors associated with the Ethernet Virtual Private Network Instance (EVI).

---

**Options** **alias**—(Optional) Configure the local AS as an alias of the global AS number configured for the router at the **[edit routing-options]** hierarchy level. As a result, a BGP peer considers any local AS to which it is assigned as equivalent to the primary AS number configured for the routing device. When you use the **alias** option, only the AS (global or local) used to establish the BGP session is prepended in the AS path sent to the BGP neighbor.

**autonomous-system**—AS number.

**Range:** 1 through 4,294,967,295 ( $2^{32} - 1$ ) in plain-number format

**Range:** 0.0 through 65535.65535 in AS-dot notation format

**loops number**—(Optional) Specify the number of times detection of the AS number in the AS\_PATH attribute causes the route to be discarded or hidden. For example, if you configure **loops 1**, the route is hidden if the AS number is detected in the path one or more times. This is the default behavior. If you configure **loops 2**, the route is hidden if the AS number is detected in the path two or more times.



**NOTE:** If you configure the local AS values for any BGP group, the detection of routing loops is performed using both the AS and the local AS values for all BGP groups.

If the local AS for the EBGp or IBGP peer is the same as the current AS, do not use the **local-as** statement to specify the local AS number.

When you configure the local AS within a VRF, this impacts the AS path loop-detection mechanism. All of the **local-as** statements configured on the device are part of a single AS domain. The AS path loop-detection mechanism is based on looking for a matching AS present in the domain.

**Range:** 1 through 10

**Default:** 1

**no-prepend-global-as**—(Optional) Specify to strip the global AS and to prepend only the local AS in AS paths sent to external peers.

**private**—(Optional) Configure to use the local AS only during the establishment of the BGP session with a BGP neighbor but to hide it in the AS path sent to external BGP peers. Only the global AS is included in the AS path sent to external peers.



**NOTE:** The **private** and **alias** options are mutually exclusive. You cannot configure both options with the same **local-as** statement.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

- Related Documentation**
- [Examples: Configuring BGP Local AS on page 113](#)
  - [Example: Configuring a Local AS for EBGp Sessions on page 118](#)
  - *autonomous-system*
  - [family on page 411](#)

## local-port

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>local-port port;</code>                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <b>station</b> <i>station-name</i> ]                                                                                                                                             |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                            |
| <b>Description</b>              | Specifies the listening port for the BMP station connection.<br><br>If you configure the <b>connection-mode</b> statement as <b>active</b> , do not configure the <b>local-port</b> statement. If you configure the <b>connection-mode</b> statement as <b>passive</b> , you must configure <b>local-port</b> statement.<br><br>If you change the local port, the BMP station connection flaps when you commit the configuration. |
| <b>Options</b>                  | <b>port</b> —Specify the local port for the BMP station connection.<br><b>Range:</b> 1 through 65,535                                                                                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                               |
| <b>Related Documentation</b>    | • <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a>                                                                                                                                                                                                                                                                                                                                                        |

## local-preference

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>local-preference <i>local-preference</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name neighbor address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name neighbor address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <i>group group-name</i>],</p> <p>[edit protocols bgp group <i>group-name neighbor address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name neighbor address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | <p>Modify the value of the <b>LOCAL_PREF</b> path attribute, which is a metric used by IBGP sessions to indicate the degree of preference for an external route. The route with the highest local preference value is preferred.</p> <p>The <b>LOCAL_PREF</b> path attribute always is advertised to internal BGP peers and to neighboring confederations. It is never advertised to external BGP peers.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Default</b>                  | If you omit this statement, the <b>LOCAL_PREF</b> path attribute, if present, is not modified.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Options</b>                  | <p><b><i>local-preference</i></b>—Preference to assign to routes learned from BGP or from the group or peer.</p> <p><b>Range:</b> 0 through 4,294,967,295 (<math>2^{32} - 1</math>)</p> <p><b>Default:</b> If the <b>LOCAL_PREF</b> path attribute is present, do not modify its value. If a BGP route is received without a <b>LOCAL_PREF</b> attribute, the route is handled locally (it is stored in the routing table and advertised by BGP) as if it were received with a <b>LOCAL_PREF</b> value of 100. By default, non-BGP routes that are advertised by BGP are advertised with a <b>LOCAL_PREF</b> value of 100.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring the Local Preference Value for BGP Routes on page 61</a></li> <li>• <a href="#">Understanding Internal BGP Peering Sessions on page 36</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

- [preference on page 478](#)

## log-updown

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | log-updown;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group</i> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <i>group</i> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group</i> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | <p>Specify to generate a log a message whenever a BGP peer makes a state transition. Messages are logged using the system logging mechanism located at the <b>[edit system syslog]</b> hierarchy level.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Preventing BGP Session Resets on page 333</a></li> <li>• <a href="#">Configuring System Logging of BGP Peer State Transitions</a></li> <li>• <a href="#">traceoptions on page 496</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## loops (BGP Address Family)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>loops <i>number</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp family <i>address-family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> family <i>address-family</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> family <i>address-family</i>],</p> <p>[edit protocols bgp family <i>address-family</i>],</p> <p>[edit protocols bgp group <i>group-name</i> family <i>address-family</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> family <i>address-family</i>]</p> |
| <b>Release Information</b> | Statement introduced in Junos OS Release 9.6.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Description</b>         | <p>For the specified BGP address family, allow the local device's AS number in the received AS paths and specify the number of times the detection of the local device's AS in the AS_PATH attribute is allowed. If the count exceeds the specified loop count, the system discards this route. For example, if you configure <b>loops 1</b>, the route is discarded if the neighbor's local AS is detected in the path more than once. This prevents routing loops and is the default behavior. If you configure <b>loops 2</b>, the route is discarded if the neighbor's local AS is detected more than 2 times.</p>                      |

For debugging, you can configure the **keep all** option. If you want to hide this route.

Some examples of BGP address families are as follows:

- **inet unicast**
- **inet-vpn multicast**
- **inet6 any**
- **l2vpn auto-discovery-only**
- ...

This list is truncated for brevity. For a complete list of protocol families for which you can specify the **loops** statement, enter the **help apropos loops** configuration command at the **[edit protocols bgp]** hierarchy level on your device.

```
[edit protocols bgp]
user@host# help apropos loops
set family inet unicast loops
    Allow local AS in received AS paths
set family inet unicast loops <loops>
    AS-Path loop count
set family inet multicast loops
    Allow local AS in received AS paths
set family inet multicast loops <loops>
    AS-Path loop count
set family inet flow loops
    Allow local AS in received AS paths
set family inet flow loops <loops>
    AS-Path loop count
set family inet any loops
```

```

    Allow local AS in received AS paths
set family inet any loops <loops>
    AS-Path loop count
set family inet labeled-unicast loops
    Allow local AS in received AS paths
...

```



**NOTE:** The behavior of this statement is slightly different from the *loops (Autonomous System)* statement.

**Options** *number*—Maximum number of times that the local device's AS number is allowed in the AS\_PATH attribute to accept the route.

**Range:** 1 through 10

**Default:** None. The system does not take any action unless the **loops (BGP Address Family)** statement is configured.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- *Example: Enabling BGP Route Advertisements*
- *autonomous-system*
- [family on page 411](#)
- [local-as on page 438](#)
- *loops (Autonomous System)*

## loose-check (BGP BFD Authentication)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | loose-check ;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit protocols bgp bgp bfd-liveness-detection authentication],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection authentication],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection authentication]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 8.1.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Description</b>              | <p>Specify loose authentication checking on the BFD session. Use loose authentication for transitional periods only when authentication might not be configured at both ends of the BFD session.</p> <p>By default, strict authentication is enabled and authentication is checked at both ends of each BFD session. Optionally, to smooth migration from nonauthenticated sessions to authenticated sessions, you can configure <i>loose checking</i>. When loose checking is configured, packets are accepted without authentication being checked at each end of the session.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring BFD for Static Routes for Faster Network Failure Detection</a></li> <li>• <a href="#">Example: Configuring BFD Authentication for Securing Static Routes</a></li> <li>• <a href="#">Example: Configuring BFD on Internal BGP Peer Sessions on page 222</a></li> <li>• <a href="#">Example: Configuring BGP Route Authentication on page 311</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |



- [Example: Configuring EBGp Multihop Sessions on page 186](#)

---

## maximum-ecmp

---

|                                 |                                                                                                                                                                         |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>maximum-ecmp <i>next-hops</i>;</code>                                                                                                                             |
| <b>Hierarchy Level</b>          | [edit chassis]                                                                                                                                                          |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2 for QFX switches.                                                                                                         |
| <b>Description</b>              | Configure 16, 32, or 64 ECMP next hops for RSVP or LDP LSPs, or MPLS static LSPs that are configured using <code>set protocols mpls static-label-switched-path</code> . |
| <b>Default</b>                  | 16                                                                                                                                                                      |
| <b>Options</b>                  | <b>next-hops</b> — Specify the number of next hops (16, 32, or 64) for RSVP or LDP LSPs, or MPLS static LSPs                                                            |
| <b>Required Privilege Level</b> | interface—To view this statement in the configuration.<br>interface-control—To add this statement to the configuration.                                                 |

## metric-out

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>metric-out (<i>metric</i>   minimum-igp <i>offset</i>   igp (delay-med-update   <i>offset</i>);</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p>                                                                                                                                                                                                                                 |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Option <b>delay-med-update</b> introduced in Junos OS Release 9.0.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>         | <p>Specify the metric for all routes sent using the multiple exit discriminator (MED, or <b>MULTI_EXIT_DISC</b>) path attribute in update messages. This path attribute is used to discriminate among multiple exit points to a neighboring AS. If all other factors are equal, the exit point with the lowest metric is preferred.</p> <p>You can specify a constant metric value by including the <b>metric</b> option. For configurations in which a BGP peer sends third-party next hops that require the local system to perform next-hop resolution—IBGP configurations, configurations within confederation peers, or EBGP configurations that include the <b>multihop</b> command—you can specify a variable metric by including the <b>minimum-igp</b> or <b>igp</b> option.</p> <p>You can increase or decrease the variable metric calculated from the IGP metric (either from the <b>igp</b> or <b>minimum-igp</b> statement) by specifying a value for <b>offset</b>. The metric is increased by specifying a positive value for <b>offset</b>, and decreased by specifying a negative value for <b>offset</b>.</p> <p>In Junos OS Release 9.0 and later, you can specify that a BGP group or peer not advertise updates for the MED path attributes used to calculate IGP costs for BGP next hops unless the MED is lower. You can also configure an interval to delay when MED updates are sent by including the <b>med-igp-update-interval</b> <i>minutes</i> statement at the [edit routing-options] hierarchy level.</p> |

**Options** **delay-med-update**—Specify that a BGP group or peer configured with the **metric-out igp** statement not advertise MED updates unless the current MED value is lower than the previously advertised MED value, or another attribute associated with the route has changed, or the BGP peer is responding to a refresh route request.



**NOTE:** You cannot configure the **delay-med-update** statement at the global BGP level.

**igp**—Set the metric to the most recent metric value calculated in the IGP to get to the BGP next hop. Routes learned from an EBGp peer usually have a next hop on a directly connected interface and thus the IGP value is equal to zero. This is the value advertised.

**metric**—Primary metric on all routes sent to peers.

**Range:** 0 through 4,294,967,295 ( $2^{32} - 1$ )

**Default:** No metric is sent.

**minimum-igp**—Set the metric to the minimum metric value calculated in the IGP to get to the BGP next hop. If a newly calculated metric is greater than the minimum metric value, the metric value remains unchanged. If a newly calculated metric is lower, the metric value is lowered to that value. When you change a neighbor's export policy from any configuration to a configuration that sets the minimum IGP offset on an exported route, the advertised MED is not updated if the value would increase as a result, even if the previous configuration does not use a minimum IGP-based MED value. This behavior helps to prevent unnecessary route flapping when an IGP cost changes, by not forcing a route update if the metric value increases past the previous lowest known value.

**offset**—Increases or decreases the metric by this value.

**Range:**  $-2^{31}$  through  $2^{31} - 1$

**Default:** None

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

- Related Documentation**
- [Example: Associating the MED Path Attribute with the IGP Metric and Delaying MED Updates on page 103](#)
  - [Examples: Configuring BGP MED on page 74](#)
  - [Example: Configuring the MED Attribute That Determines the Exit Point in an AS on page 77](#)
  - [Understanding the MED Attribute That Determines the Exit Point in an AS on page 74](#)
  - *med-igp-update-interval*

## minimum-interval (BFD Liveness Detection)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>minimum-interval <i>milliseconds</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection],</p> <p>[edit protocols bgp bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.5.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Description</b>         | <p>Configure the minimum interval after which the local routing device transmits hello packets and then expects to receive a reply from a neighbor with which it has established a BFD session. Optionally, instead of using this statement, you can specify the minimum transmit and receive intervals separately using the <a href="#">minimum-interval</a> (specified under the <a href="#">transmit-interval</a> statement) and <a href="#">minimum-receive-interval</a> statements.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Options</b>             | <p><i>milliseconds</i>—Specify the minimum interval value for BFD liveliness detection.</p> <p><b>Range:</b> 1 through 255,000</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                                 |                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                    |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <i>Configuring BFD for Layer 2 VPN and VPLS</i></li><li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li><li>• <a href="#">bfd-liveness-detection on page 395</a></li><li>• <a href="#">minimum-receive-interval on page 454</a></li><li>• <a href="#">transmit-interval on page 501</a></li></ul> |

## minimum-interval (transmit-interval)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>minimum-interval <i>milliseconds</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection transmit-interval],</p> <p>[edit protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection transmit-interval]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.2.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Description</b>         | Configure the minimum interval at which the local routing device transmits hello packets to a neighbor with which it has established a BFD session. Optionally, instead of using                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

this statement at this hierarchy level, you can configure the minimum transmit interval using the [minimum-interval](#) statement at the **bfd-liveness-detection** hierarchy level.

**Options** *milliseconds*—Minimum transmit interval value.

**Range:** 1 through 255,000



**NOTE:** The threshold value specified in the **threshold** statement must be greater than the value specified in the **minimum-interval** statement for the **transmit-interval** statement.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- *Configuring BFD for Layer 2 VPN and VPLS*
- *Example: Configuring BFD for Static Routes for Faster Network Failure Detection*
- [bfd-liveness-detection on page 395](#)
- [minimum-interval on page 450](#)
- [threshold on page 494](#)

## minimum-receive-interval (BFD Liveness Detection)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>minimum-receive-interval <i>milliseconds</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection],</p> <p>[edit protocols bgp bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.5.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Description</b>         | Configure the minimum interval after which the local routing device must receive a reply from a neighbor with which it has established a BFD session. Optionally, instead of using this statement, you can configure the minimum receive interval using the <b>minimum-interval</b> statement.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Options</b>             | <p><b><i>milliseconds</i></b>—Specify the minimum receive interval value.</p> <p><b>Range:</b> 1 through 255,000</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |



|                                 |                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                  |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <i>Configuring BFD for Layer 2 VPN and VPLS</i></li> <li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li> <li>• <a href="#">bfd-liveness-detection on page 395</a></li> <li>• <a href="#">minimum-interval on page 450</a></li> <li>• <a href="#">transmit-interval on page 501</a></li> </ul> |

## monitor (Protocols BMP)


|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | monitor (enable   disable);                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> protocols bgp bmp],<br>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bmp],<br>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <a href="#">station</a> <i>station-name</i> ],<br>[edit protocols bgp bmp],<br>[edit protocols bgp group <i>group-name</i> bmp],<br>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bmp],<br>[edit routing-options bmp],<br>[edit routing-options bmp <a href="#">station</a> <i>station-name</i> ] |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Description</b>              | BMP monitoring is enabled by default. You can explicitly enable BMP monitoring or disable it. You can also selectively enable or disable BMP monitoring at various hierarchy levels (for example, [edit protocols bgp group <i>group-name</i> ] or [edit protocols bgp group <i>group-name</i> neighbor <i>address</i> ]). If you disable BMP monitoring, withdrawal messages are sent for any previously advertised routes. These are followed by a down message. If you enable BMP monitoring, an up message is sent first and then the route advertisements follow.                                                                                                                                                                                                 |
| <b>Options</b>                  | <b>enable</b> —Enable BMP monitoring.<br><b>Default:</b> BMP monitoring is enabled by default.<br><b>disable</b> —Disable BMP monitoring.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## mtu-discovery

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | mtu-discovery;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p>                                                                                                                                                                                                                            |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>              | <p>Configure TCP path maximum transmission unit (MTU) discovery.</p> <p>TCP path MTU discovery enables BGP to automatically discover the best TCP path MTU for each BGP session. In Junos OS, TCP path MTU discovery is disabled by default for all BGP neighbor sessions.</p> <p>When MTU discovery is disabled, TCP sessions that are not directly connected transmit packets of 512-byte maximum segment size (MSS). These small packets minimize the chances of packet fragmentation at a device along the path to the destination. However, because most links use an MTU of at least 1500 bytes, 512-byte packets do not result in the most efficient use of link bandwidth. For directly connected EBGP sessions, MTU mismatches prevent the BGP session from being established. As a workaround, enable path MTU discovery within the EBGP group.</p> <p>Path MTU discovery dynamically determines the MTU size on the network path between the source and the destination, with the goal of avoiding IP fragmentation. Path MTU discovery works by setting the Don't Fragment (DF) bit in the IP headers of outgoing packets. When a device along the path has an MTU that is smaller than the packet, the device drops the packet. The device also sends back an ICMP Fragmentation Needed (Type 3, Code 4) message that contains the device's MTU, thus allowing the source to reduce its path MTU appropriately. The process repeats until the MTU is small enough to traverse the entire path without fragmentation.</p> |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

- Related Documentation**
- [Example: Limiting TCP Segment Size for BGP on page 326](#)
  - *Configuring Junos OS for IPv6 Path MTU Discovery*
  - *Configuring the Junos OS for Path MTU Discovery on Outgoing GRE Tunnel Connections*

## multihop

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <pre>multihop {     no-nexthop-change;     ttl <i>ttl-value</i>; }</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],<br/>         [edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],<br/>         [edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],<br/>         [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],<br/>         [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],<br/>         [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],<br/>         [edit protocols bgp],<br/>         [edit protocols bgp <b>group</b> <i>group-name</i>],<br/>         [edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],<br/>         [edit routing-instances <i>routing-instance-name</i> protocols bgp],<br/>         [edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],<br/>         [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.<br/>         Statement introduced in Junos OS Release 9.0 for EX Series switches.<br/>         Statement introduced in Junos OS Release 11.3 for the QFX Series.<br/>         Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>         | <p>Configure an EBGp multihop session.</p> <p>For Layer 3 VPNs, you configure the EBGp multihop session between the PE and CE routing devices. This allows you to configure one or more routing devices between the PE and CE routing devices.</p> <p>An external confederation peer is a special case that allows unconnected third-party next hops. You do not need to configure multihop sessions explicitly in this particular case because multihop behavior is implied.</p> <p>If you have external BGP confederation peer-to-loopback addresses, you still need the multihop configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|                            | <div>  <p><b>NOTE:</b> You cannot configure the <code>accept-remote-nexthop</code> statement at the same time.</p> </div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Default</b>             | <p>If you omit this statement, all EBGp peers are assumed to be directly connected (that is, you are establishing a nonmultihop, or “regular,” BGP session), and the default time-to-live (TTL) value is 1.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

The remaining statements are explained separately.

|                                 |                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                           |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <a href="#">Example: Configuring EBGp Multihop Sessions on page 186</a></li><li>• <i>Configuring EBGp Multihop Sessions Between PE and CE Routers in Layer 3 VPNs</i></li><li>• <a href="#">accept-remote-nextthop on page 378</a></li><li>• <i>no-nextthop-change</i></li><li>• <i>tth</i></li></ul> |

## multiplier (BFD Liveness Detection)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>multiplier <i>number</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection],</p> <p>[edit protocols bgp bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.5.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Description</b>         | Configure the number of hello packets not received by a neighbor that causes the originating interface to be declared down.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Options</b>             | <p><i>number</i>—Number of hello packets.</p> <p><b>Range:</b> 1 through 255</p> <p><b>Default:</b> 3</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

|                                 |                                                                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <i>Configuring BFD for Layer 2 VPN and VPLS</i></li><li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li><li>• <a href="#">bfd-liveness-detection on page 395</a></li></ul> |

## neighbor (Protocols BGP)

```
Syntax neighbor address {
    accept-remote-nexthop;
    advertise-bgp-static
    advertise-external <conditional>;
    advertise-inactive;
    (advertise-peer-as | no-advertise-peer-as);
    as-override;
    authentication-algorithm algorithm;
    authentication-key key;
    authentication-key-chain key-chain;
    cluster cluster-identifier;
    damping;
    description text-description;
    enforce-first-as;
    export [ policy-names ];
    family {
        (inet | inet6 | inet-mvpn | inet6-mpvn | inet-vpn | inet6-vpn | iso-vpn | l2-vpn) {
            (any | flow | multicast | unicast | signaling) {
                accepted-prefix-limit {
                    maximum number;
                    teardown <percentage> <idle-timeout (forever | minutes)>;
                }
                damping;
                prefix-limit {
                    maximum number;
                    teardown <percentage> <idle-timeout (forever | minutes)>;
                }
                rib-group group-name;
                topology name {
                    community {
                        target identifier;
                    }
                }
            }
        }
        flow {
            no-validate policy-name;
        }
        labeled-unicast {
            accepted-prefix-limit {
                maximum number;
                teardown <percentage> <idle-timeout (forever | minutes)>;
            }
            aggregate-label {
                community community-name;
            }
            explicit-null {
                connected-only;
            }
            prefix-limit {
                maximum number;
                teardown <percentage> <idle-timeout (forever | minutes)>;
            }
        }
    }
}
```



```

    resolve-vpn;
    rib inet.3;
    rib-group group-name;
    topology name {
        community {
            target identifier;
        }
    }
}
forwarding-context
route-target {
    advertise-default;
    external-paths number;
    accepted-prefix-limit {
        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
    }
    prefix-limit {
        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
    }
}
signaling {
    prefix-limit {
        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
    }
}
}
forwarding-context rti-name;
graceful-restart {
    disable;
    restart-time seconds;
    stale-routes-time seconds;
}
hold-time seconds;
import [ policy-names ];
ipsec-sa ipsec-sa;
keep (all | none);
local-address address;
local-as autonomous-system <private>;
local-interface interface-name;
local-preference preference;
log-updown;
metric-out (metric | minimum-igp <offset> | igp <offset>);
mtu-discovery;
multihop <ttl-value>;
multipath {
    multiple-as;
}
no-aggregator-id;
no-client-reflect;
out-delay seconds;
passive;
peer-as autonomous-system;

```

```
preference preference;  
rfc6514-compliant-safil29;  
tcp-aggressive-transmission;  
tcp-mss segment-size;  
traceoptions {  
    file filename <files number> <size size> <world-readable | no-world-readable>;  
    flag flag <flag-modifier> <disable>;  
}  
vpn-apply-export;  
}
```

**Hierarchy Level** [edit logical-systems *logical-system-name* protocols bgp **group** *group-name*],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols  
bgp **group** *group-name*],  
[edit protocols bgp **group** *group-name*],  
[edit routing-instances *routing-instance-name* protocols bgp **group** *group-name*]

**Release Information** Statement introduced before Junos OS Release 7.4.  
Statement introduced in Junos OS Release 9.0 for EX Series switches.  
Statement introduced in Junos OS Release 11.3 for the QFX Series.  
Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.

**Description** Explicitly configure a neighbor (peer). To configure multiple BGP peers, include multiple **neighbor** statements.

By default, the peer's options are identical to those of the group. You can override these options by including peer-specific option statements within the **neighbor** statement.

The **neighbor** statement is one of the statements you can include in the configuration to define a minimal BGP configuration on the routing device. (You can include an **allow all** statement in place of a **neighbor** statement.)

**Options** **address**—IPv6 or IPv4 address of a single peer.

The remaining statements are explained separately.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- *BGP Feature Guide*

## no-adaptation (BFD Liveness Detection)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | no-adaptation;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection],</p> <p>[edit protocols bgp bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 9.0</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Description</b>              | Configure BFD sessions not to adapt to changing network conditions. We recommend that you <i>do not</i> disable BFD adaptation unless it is preferable to have BFD adaptation disabled in your network.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

- Related Documentation**
- [Configuring BFD for Layer 2 VPN and VPLS](#)
  - [Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)
  - [bfd-liveness-detection on page 395](#)

## no advertise-peer-as

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | no-advertise-peer-as;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>          | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i> neighbor <i>address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i> neighbor <i>address</i>], [edit protocols bgp], [edit protocols bgp <i>group group-name</i>], [edit protocols bgp <i>group group-name</i> neighbor <i>address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i> neighbor <i>address</i>]</pre> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Description</b>              | Enable the default behavior of suppressing AS routes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring BGP Route Advertisement on page 177</a></li> <li>• <a href="#">Configuring Routing Policies to Control BGP Route Advertisements on page 177</a></li> <li>• <a href="#">advertise-peer-as on page 383</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## no-aggregator-id

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | no-aggregator-id;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Description</b>              | <p>Prevent different routing devices within an AS from creating aggregate routes that contain different AS paths.</p> <p>Junos OS performs route aggregation, which is the process of combining the characteristics of different routes so that only a single route is advertised. Aggregation reduces the amount of information that BGP must store and exchange with other BGP systems. When aggregation occurs, the local routing device adds the local AS number and the router ID to the aggregator path attribute. The <b>no-aggregator-id</b> statement causes Junos OS to place a 0 in the router ID field and thus eliminate the possibility of having multiple aggregate advertisements in the network, each with different path information.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Default</b>                  | If you omit this statement, the router ID is included in the BGP aggregator path attribute.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Update Messages on page 8</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## no-client-reflect

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | no-client-reflect;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | Disable intracluster route redistribution by the system acting as the route reflector. Include this statement when the client cluster is fully meshed to prevent the sending of redundant route advertisements. Route reflection provides a way to decrease BGP control traffic and minimizing the number of update messages sent within the AS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring BGP Route Reflectors on page 285</a></li> <li>• <a href="#">cluster on page 402</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## out-delay

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>out-delay seconds;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>     | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i> <i>neighbor address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name neighbor address</i>], [edit protocols bgp], [edit protocols bgp <i>group group-name</i>], [edit protocols bgp <i>group group-name neighbor address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i> <i>neighbor address</i>]</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Description</b>         | <p>Control how often BGP and the routing table exchange route information by specifying how long a route must be present in the Junos OS routing table before it is exported to BGP. Use this time delay to help bundle routing updates and to avoid sending updates too often.</p> <p>Alternatively or in addition, external BGP (EBGP) sessions can also use the route-flap damping mechanism upon the reception of BGP messages coming from an external neighbor.</p> <p>BGP stores the route information it receives from update messages in the routing table, and the routing table exports active routes from the routing table into BGP. BGP then advertises the exported routes to its peers. The <b>out-delay</b> statement enables a form of rate limiting. The delay is added to each update for each prefix individually. When a routing device changes its best path to a destination prefix, the device does not inform its peer about the change unless the route has been present in its routing table for the specified <b>out-delay</b>. If you use <b>out-delay</b> to perform rate-limiting, you can expect a less bursty pattern of updates. You will see a pattern in which updates arrive in a steady flow, and two updates for the same prefix are always spaced by at least the <b>out-delay</b> timer value (for example, 30 seconds). Thus, the <b>out-delay</b> setting is useful for limiting oscillation (sometimes called <i>churn</i>) in a network. Keep in mind that, regardless of the <b>out-delay</b> setting, BGP peers exchange routes immediately after neighbor establishment. The <b>out-delay</b> setting is only designed to delay the exchange of routes between BGP and the local routing table.</p> |

Caution is warranted because an **out-delay** can delay convergence. If your network is configured in a way that avoids oscillation, setting an **out-delay** is not necessary.

When configured, the **out-delay** value displays as **Outbound Timer** when using **show bgp group** or **show bgp group neighbor** commands.

**Default** By default, the exchange of route information between BGP and the routing table occurs immediately after the routes are received. This immediate exchange of route information might cause instabilities in the network reachability information. If you omit this statement, routes are exported to BGP immediately after they have been added to the routing table.


**Options** *seconds*—Output delay time.  
**Range:** 0 through 65,535 seconds  
**Default:** 0 seconds

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation** • [keep on page 431](#)



## outbound-route-filter

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <pre> outbound-route-filter {     <b>bgp-orf-cisco-mode</b>;     prefix-based {         accept {             (inet   inet6);         }     } } </pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],<br/> [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>],<br/> [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],<br/> [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],<br/> [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],<br/> [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],<br/> [edit protocols bgp],<br/> [edit protocols bgp group <i>group-name</i>],<br/> [edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],<br/> [edit routing-instances <i>routing-instance-name</i> protocols bgp],<br/> [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],<br/> [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 9.2.<br/> Statement introduced in Junos OS Release 9.2 for EX Series switches.<br/> Statement introduced in Junos OS Release 11.3 for the QFX Series.<br/> Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>              | Configure a BGP peer to accept outbound route filters from a remote peer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Options</b>                  | <p><b>accept</b>—Specify that outbound route filters from a BGP peer be accepted.</p> <p><b>inet</b>—Specify that IPv4 prefix-based outbound route filters be accepted.</p> <p><b>inet6</b>—Specify that IPv6 prefix-based outbound route filters be accepted.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                                 | <p> <b>NOTE:</b> You can specify that both IPv4 and IPv6 outbound route filters be accepted.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                                 | <p><b>prefix-based</b>—Specify that prefix-based filters be accepted.</p> <p>The <b>bgp-orf-cisco-mode</b> statement is explained separately.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

- Related Documentation**
- [Example: Configuring BGP Prefix-Based Outbound Route Filtering on page 181](#)

---

## passive (Protocols BGP)

---

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | passive;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Hierarchy Level</b>          | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> protocols bgp <i>group group-name</i> <i>neighbor address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name neighbor address</i>], [edit protocols bgp], [edit protocols bgp <i>group group-name</i>], [edit protocols bgp <i>group group-name neighbor address</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i>], [edit routing-instances <i>routing-instance-name</i> protocols bgp <i>group group-name</i> <i>neighbor address</i>]</pre> |
| <b>Release Information</b>      | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Description</b>              | Configure the routing device so that active open messages are not sent to the peer. Once you configure the routing device to be passive, the routing device will wait for the peer to issue an open request before a message is sent.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Default</b>                  | If you omit this statement, all explicitly configured peers are active, and each peer periodically sends open requests until its peer responds.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <a href="#">Example: Preventing BGP Session Flaps When VPN Families Are Configured on page 333</a></li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## path-selection

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <pre> path-selection {   (always-compare-med   cisco-non-deterministic   external-router-id);   as-path-ignore;   l2vpn-use-bgp-rules;   med-plus-igp {     igp-multiplier <i>number</i>;     med-multiplier <i>number</i>;   } } </pre>                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>     | <pre> [edit logical-systems <i>logical-system-name</i> protocols bgp], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp], [edit protocols bgp], [edit routing-instances <i>routing-instance-name</i> protocols bgp] </pre>                                                                                                                                                                                    |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p><b>med-plus-igp</b> option introduced in Junos OS Release 8.1.</p> <p><b>as-path-ignore</b> and <b>l2vpn-use-bgp-rules</b> options introduced in Junos OS Release 10.2.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p> |
| <b>Description</b>         | Configure BGP path selection.                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Default</b>             | If the <b>path-selection</b> statement is not included in the configuration, only the multiple exit discriminators (MEDs) of routes that have the same peer ASs are compared.                                                                                                                                                                                                                                                                                                |
| <b>Options</b>             | <b>always-compare-med</b> —Always compare MEDs whether or not the peer ASs of the compared routes are the same.                                                                                                                                                                                                                                                                                                                                                              |



**NOTE:** We recommend that you configure the **always-compare-med** option.

**as-path-ignore**—In the best-path algorithm, skip the step that compares the autonomous system (AS) path lengths. By default, the best-path algorithm evaluates the length of the AS paths and prefers the route with the shortest AS path length.



**NOTE:** The **as-path-ignore** statement is not supported with routing instances.

**cisco-non-deterministic**—Emulate the Cisco IOS default behavior. This mode evaluates routes in the order that they are received and does not group them according to their neighboring AS. With **cisco-non-deterministic** mode, the active path is always first. All inactive, but eligible, paths follow the active path and are maintained in the order

in which they were received, with the most recent path first. Ineligible paths remain at the end of the list.

As an example, suppose you have three path advertisements for the 192.168.1.0 /24 route:

- Path 1—learned through EBGp; AS Path of 65010; MED of 200
- Path 2—learned through IBGP; AS Path of 65020; MED of 150; IGP cost of 5
- Path 3—learned through IBGP; AS Path of 65010; MED of 100; IGP cost of 10

These advertisements are received in quick succession, within a second, in the order listed. Path 3 is received most recently, so the routing device compares it against path 2, the next most recent advertisement. The cost to the IBGP peer is better for path 2, so the routing device eliminates path 3 from contention. When comparing paths 1 and 2, the routing device prefers path 1 because it is received from an EBGp peer. This allows the routing device to install path 1 as the active path for the route.



**NOTE:** We do not recommend using this configuration option in your network. It is provided solely for interoperability to allow all routing devices in the network to make consistent route selections.

**external-router-id**—Compare the router ID between external BGP paths to determine the active path.

**igp-multiplier *number***—The multiplier value for the IGP cost to a next-hop address. This option is useful for making the MED and IGP cost comparable.

**Range:** 1 through 1000

**Default:** 1

**med-multiplier *number***—The multiplier value for the MED calculation. This option is useful for making the MED and IGP cost comparable.

**Range:** 1 through 1000

**Default:** 1

**med-plus-igp**—Add the IGP cost to the indirect next-hop destination to the MED before comparing MED values for path selection. This statement only affects best-path selection. It does not affect the advertised MED.

The other option is explained separately.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- [Understanding BGP Path Selection on page 202](#)
- [Example: Ignoring the AS Path Attribute When Selecting the Best Path on page 205](#)

## peer-as (Protocols BGP)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>peer-as <i>autonomous-system</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>]</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Release Information</b> | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Description</b>         | <p>Specify the neighbor (peer) autonomous system (AS) number.</p> <p>For EBGP, the peer is in another AS, so the AS number you specify in the <b>peer-as</b> statement must be different from the local router's AS number, which you specify in the <b>autonomous-system</b> statement. For IBGP, the peer is in the same AS, so the two AS numbers that you specify in the <b>autonomous-system</b> and <b>peer-as</b> statements must be the same.</p> <p>The AS numeric range in plain-number format has been extended in Junos OS Release 9.1 to provide BGP support for 4-byte AS numbers, as defined in RFC 4893, <i>BGP Support for Four-octet AS Number Space</i>. RFC 4893 introduces two new optional transitive BGP attributes, AS4_PATH and AS4_AGGREGATOR. These new attributes are used to propagate 4-byte AS path information across BGP speakers that do not support 4-byte AS numbers. RFC 4893 also introduces a reserved, well-known, 2-byte AS number, AS 23456. This reserved AS number is called AS_TRANS in RFC 4893. All releases of the Junos OS support 2-byte AS numbers.</p> <p>In Junos OS Release 9.2 and later, you can also configure a 4-byte AS number using the AS-dot notation format of two integer values joined by a period: <i>&lt;16-bit high-order value in decimal&gt;.&lt;16-bit low-order value in decimal&gt;</i>. For example, the 4-byte AS number of 65,546 in plain-number format is represented as 1.10 in the AS-dot notation format.</p> <p>With the introduction of 4-byte AS numbers, you might have a combination of routers that support 4-byte AS numbers and 2-byte AS numbers. For more information about what happens when establishing BGP peer relationships between 4-byte and 2-byte capable routers, see the following topics:</p> |

- *Using 4-Byte Autonomous System Numbers in BGP Networks Technology Overview.*

**Options** *autonomous-system*—AS number.  
**Range:** 1 through 4,294,967,295 ( $2^{32} - 1$ ) in plain-number format for 4-byte AS numbers  
**Range:** 1 through 65,535 in plain-number format for 2-byte AS numbers (this is a subset of the 4-byte range)  
**Range:** 0.0 through 65535.65535 in AS-dot notation format for 4-byte AS numbers

**Required Privilege** routing—To view this statement in the configuration.  
**Level** routing-control—To add this statement to the configuration.

---

## post-policy

---

**Syntax** `post-policy {  
 exclude-non-eligible;  
}`

**Hierarchy Level** [edit protocols bgp bmp [route-monitoring](#)],  
[edit protocols bgp group *group-name* bmp route-monitoring],  
[edit protocols bgp group *neighborgroup-name* neighbor *address* bmp route-monitoring],  
[edit routing-options bmp route-monitoring],  
[edit routing-options bmp station *station-name* route-monitoring]

**Release Information** Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.  
Statement introduced in Junos OS Release 13.3.  
Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.

**Description** For BMP route monitoring, allows you to excludes routes that are non-eligible for the decision process (for example, protocol nexthop not resolved). This represents the view of the BGP routes after running the import policy. If the import policy has rejected the BGP route, the route does not exist in the post policy view.

**Options** *exclude-non-eligible*—Exclude routes that are non-eligible for the decision process.

**Required Privilege** routing—To view this statement in the configuration.  
**Level** routing-control—To add this statement to the configuration.


**Related Documentation** • [Configuring BGP Monitoring Protocol Version 3 on page 59](#)

## pre-policy

---


|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | pre-policy {<br>exclude-non-feasible;<br>}                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Hierarchy Level</b>          | [edit protocols bgp bmp <a href="#">route-monitoring</a> ],<br>[edit protocols bgp group <i>group-name</i> bmp <a href="#">route-monitoring</a> ],<br>[edit protocols bgp group neighbor <i>group-name</i> neighbor <i>address</i> bmp <a href="#">route-monitoring</a> ],<br>[edit routing-options bmp <a href="#">route-monitoring</a> ],<br>[edit routing-options bmp station <i>station-name</i> <a href="#">route-monitoring</a> ] |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                  |
| <b>Description</b>              | Excludes routes that are non-feasible from the BMP route monitoring decision process (for example, a route loop). This represents the view of the BGP routes before running the import policy.                                                                                                                                                                                                                                          |
| <b>Options</b>                  | <b>exclude-non-feasible</b> —Exclude routes that are non-feasible for the decision process.                                                                                                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                     |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li> </ul>                                                                                                                                                                                                                                                                                                            |

## preference (Protocols BGP)

|                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                                                                                                                                                      | <code>preference <i>preference</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>                                                                                                                                             | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> <b>neighbor</b> <i>address</i>]</p> |
| <b>Release Information</b>                                                                                                                                         | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Description</b>                                                                                                                                                 | <p>Specify the preference for routes learned from BGP.</p> <p>At the BGP global level, the preference statement sets the preference for routes learned from BGP. You can override this preference in a BGP group or peer preference statement.</p> <p>At the group or peer level, the preference statement sets the preference for routes learned from the group or peer. Use this statement to override the preference set in the BGP global preference statement when you want to favor routes from one group or peer over those of another.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <div>  <b>NOTE:</b> Do not set preference2 for BGP route-policy.         </div> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Options</b>                                                                                                                                                     | <p><b>preference</b>—Preference to assign to routes learned from BGP or from the group or peer.</p> <p><b>Range:</b> 0 through 4,294,967,295 (<math>2^{32} - 1</math>)</p> <p><b>Default:</b> 170 for the primary preference</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Required Privilege Level</b>                                                                                                                                    | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Related Documentation</b>                                                                                                                                       | <ul style="list-style-type: none"> <li>• <a href="#">local-preference on page 442</a></li> <li>• <a href="#">Example: Configuring the Preference Value for BGP Routes on page 197</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |



## priority (Protocols BMP)

|                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                                                                                                                                                                                                                                                    | priority (high   medium   low);                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>                                                                                                                                                                                                                                           | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <b>station</b> <i>station-name</i> ]                                                                                                                                                                                                                                 |
| <b>Release Information</b>                                                                                                                                                                                                                                       | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                                |
| <b>Description</b>                                                                                                                                                                                                                                               | Specifies the dispatch priority for BMP. The dispatch priority controls the frequency with which the device is able to forward BMP messages to BMP stations.                                                                                                                                                                                                                                                                                                                                                          |
| <b>Options</b>                                                                                                                                                                                                                                                   | <p><b>high</b>—Specifies that the routing protocol process handle BMP requests with high urgency.</p> <p><b>medium</b>—Specifies that the routing protocol process handle BMP requests with medium urgency.</p> <p><b>low</b>—Specifies that the routing protocol process handle BMP requests with low urgency.</p> <p><b>Default:</b> The default dispatch priority is <b>low</b> to minimize interference with other routing protocol process priorities and to match the behavior of previous versions of BMP.</p> |
| <div>  <p><b>NOTE:</b> Setting high or medium priority may reduce the performance of the routing protocol process in its handling route convergence or other work.</p> </div> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Required Privilege Level</b>                                                                                                                                                                                                                                  | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Related Documentation</b>                                                                                                                                                                                                                                     | <ul style="list-style-type: none"> <li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                          |

## remove-private

**Syntax** `remove-private;`

**Hierarchy Level** [edit logical-systems *logical-system-name* protocols bgp],  
 [edit logical-systems *logical-system-name* protocols bgp **group** *group-name*],  
 [edit logical-systems *logical-system-name* protocols bgp **group** *group-name* neighbor *address*],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp **group** *group-name*],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp group *group-name* **neighbor** *address*],  
 [edit protocols bgp],  
 [edit protocols bgp **group** *group-name*],  
 [edit protocols bgp group *group-name* **neighbor** *address*],  
 [edit routing-instances *routing-instance-name* protocols bgp],  
 [edit routing-instances *routing-instance-name* protocols bgp **group** *group-name*],  
 [edit routing-instances *routing-instance-name* protocols bgp group *group-name* **neighbor** *address*]

**Release Information** Statement introduced before Junos OS Release 7.4.  
 Statement introduced in Junos OS Release 9.0 for EX Series switches.  
 Statement introduced in Junos OS Release 11.3 for the QFX Series.  
 Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.  
**no-peer-loop-check** option added in Junos OS Release 15.1.

**Description** When advertising AS paths to remote systems, have the local system strip private AS numbers from the AS path. The numbers are stripped from the AS path starting at the left end of the AS path (the end where AS paths have been most recently added). The routing device stops searching for private ASs when it finds the first nonprivate AS or a peer's private AS. If the AS path contains the AS number of the external BGP (EBGP) neighbor, BGP does not remove the private AS number.



**NOTE:** As of Junos OS 10.0R2 and higher, if there is a need to send prefixes to an EBGP peer that has an AS number that matches an AS number in the AS path, consider using the **as-override** statement instead of the **remove-private** statement.

The operation takes place after any confederation member ASs have already been removed from the AS path, if applicable.

Junos OS recognizes the set of AS numbers that is considered private, a range that is defined in the Internet Assigned Numbers Authority (IANA) assigned numbers document.

The set of reserved AS numbers is in the range from 64,512 through 65,535.

**Options** **all**—Remove all private AS numbers from the original path. Do not stop the process of removing private AS numbers, even if a public AS number is encountered.

**nearest**—When you use the **all** and **replace** options, choose the last (right-most) public AS number encountered in the original AS path for the replacement value, as the AS path is processed from left to right. If no public AS number is encountered, the default replacement value is used. (See the **replace** option for information about the default replacement value.)

**replace**—When you use the **all** option, instead of removing private AS numbers, perform a replace operation. The default replacement value for the private AS number is the local AS number at the BGP group level for the BGP peer. If you are unsure about the replacement value, check the local AS value displayed in the output of the **show bgp group group-name** command.

**no-peer-loop-check**—Peer loop check is removed. By default, the **remove-private** statement has a peer loop check restriction. If a private AS in the AS path has the same value as the configured **peer-as** for the neighbor, **remove-private** does not remove or replace this private AS number. This restriction provides peer-as loop protection. However, you can remove this restriction using the **no-peer-loop-check** option.

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>Required Privilege</b> | routing—To view this statement in the configuration.        |
| <b>Level</b>              | routing-control—To add this statement to the configuration. |

|                              |                                                                                                                                  |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Related Documentation</b> | <ul style="list-style-type: none"><li>• <a href="#">Example: Removing Private AS Numbers from AS Paths on page 214</a></li></ul> |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------|

## restart-time (BGP Graceful Restart)

---

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>restart-time seconds;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Hierarchy Level</b>          | <code>[edit protocols (bgp   rip   ripng) graceful-restart],</code><br><code>[edit logical-systems <i>logical-system-name</i> protocols (bgp   rip   ripng) graceful-restart</code><br><code>(Enabling Globally)],</code><br><code>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols</code><br><code>bgp graceful-restart],</code><br><code>[edit routing-instances <i>routing-instance-name</i> protocols bgp graceful-restart]</code> |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 8.3.<br>Statement introduced in Junos OS Release 9.0 for EX Series switches.<br>Statement introduced in Junos OS Release 12.1 for the QFX Series.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                          |
| <b>Description</b>              | Configure the duration of the BGP, RIP, or next-generation RIP (RIPng) graceful restart period.                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Options</b>                  | <b>seconds</b> —Length of time for the graceful restart period.<br><b>Range:</b> 1 through 600 seconds<br><b>Default:</b> Varies by protocol: <ul style="list-style-type: none"><li>• BGP—120 seconds</li><li>• RIP and RIPng—60 seconds</li></ul>                                                                                                                                                                                                                                              |
| <b>Required Privilege Level</b> | <code>routing</code> —To view this statement in the configuration.<br><code>routing-control</code> —To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                 |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <i>Configuring Graceful Restart Options for BGP</i></li><li>• <i>Configuring Graceful Restart Options for RIP and RIPng</i></li><li>• <i>Configuring Graceful Restart for QFabric Systems</i></li><li>• <a href="#">stale-routes-time on page 486</a></li></ul>                                                                                                                                                                                         |

## route-monitoring

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <pre>route-monitoring {   none;   post-policy {     exclude-non-eligible;   }   pre-policy {     exclude-non-feasible;   } }</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bmp],<br/> [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bmp],<br/> [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bmp],<br/> [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br/> [edit logical-systems <i>logical-system-name</i> routing-options bmp <i>station station-name</i>],<br/> [edit protocols bgp bmp],<br/> [edit protocols bgp group <i>group-name</i> bmp],<br/> [edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bmp],<br/> [edit routing-options bmp],<br/> [edit routing-options bmp <i>station station-name</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br/> Statement introduced in Junos OS Release 13.3.<br/> Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Description</b>              | <p>Specify whether BMP should send pre-policy route monitoring messages, post-policy route monitoring messages, both types of messages, or none at all. The pre-policy can be configured to exclude routes that are non-feasible for the decision process (for example, a route loop). The post-policy can be configured to exclude routes that are not eligible for the decision process (for example, protocol nexthop not resolved).</p> <p>You can also selectively enable or disable BMP route monitoring at various hierarchy levels (for example, [edit protocols bgp group <i>group-name</i>] or [edit protocols bgp group <i>group-name</i> neighbor <i>address</i>]).</p>                                                                           |
| <b>Options</b>                  | <p><b>none</b>—Explicitly disables BMP route monitoring.</p> <p><b>Default:</b> If you configure the <b>route-monitoring</b> statement at the [edit routing-options bmp] hierarchy level, the default option is <b>pre-policy</b>. If you configure the <b>route-monitoring</b> statement at any of the [edit protocols bgp] hierarchy levels, the default option is to inherit the configuration from the <b>route-monitoring</b> statement configured at the [edit routing-options bmp] hierarchy level.</p> <p>The other statements are explained separately.</p>                                                                                                                                                                                          |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.<br/> routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

- Related Documentation**
- [Configuring BGP Monitoring Protocol Version 3 on page 59](#)

## session-mode

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>session-mode (automatic   multihop   single-hop);</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 11.1.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>              | <p>Configure BFD session mode to be single-hop or multihop. By default, BGP uses single-hop BFD sessions if the peer is directly connected to the router's interface. BGP uses multihop BFD sessions if the peer is not directly connected to the router's interface. If the peer session's <b>local-address</b> option is configured, the directly connected check is based partly on the source address that would be used for BGP and BFD.</p> <p>For backward compatibility, you can override the default behavior by configuring the <b>single-hop</b> or <b>multihop</b> option. Before Junos OS Release 11.1, the behavior was to assume that IBGP peer sessions were multihop.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Options</b>                  | <p><b>automatic</b>—Configure BGP to use single-hop BFD sessions if the peer is directly connected to the router's interface, and multihop BFD sessions if the peer is not directly connected to the router's interface</p> <p><b>multihop</b>—Configure BGP to use multihop BFD sessions.</p> <p><b>single-hop</b>—Configure BGP to use single-hop BFD sessions.</p> <p><b>Default:</b> automatic</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Configuring BFD Authentication for BGP on page 232</a></li> <li>• <a href="#">Example: Configuring BFD on Internal BGP Peer Sessions on page 222</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

- [Example: Configuring BFD Authentication for BGP on page 232](#)
- [Understanding BFD Authentication for BGP on page 230](#)

---

## stale-routes-time

---

|                          |                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Syntax                   | stale-routes-time <i>seconds</i> ;                                                                                                                                                                                                                                                                                                                           |
| Hierarchy Level          | [edit logical-systems <i>logical-routing-name</i> protocols bgp graceful-restart],<br>[edit logical-systems <i>logical-routing-name</i> routing-instances <i>routing-instance-name</i> protocols<br>bgp graceful-restart],<br>[edit protocols bgp graceful-restart],<br>[edit routing-instances <i>routing-instance-name</i> protocols bgp graceful-restart] |
| Release Information      | Statement introduced in Junos OS Release 8.3.<br>Statement introduced in Junos OS Release 9.0 for EX Series switches.<br>Statement introduced in Junos OS Release 12.1 for the QFX Series.<br>Statement introduced in Junos OS Release 14.1x53-D20 for the OCX Series.                                                                                       |
| Description              | Specify the maximum time that stale routes are kept during a restart. The <b>stale-routes-time</b> statement allows you to set the length of time the routing device waits to receive messages from restarting neighbors before declaring them down.                                                                                                         |
| Options                  | <b>seconds</b> —Time the router device waits to receive messages from restarting neighbors before declaring them down.<br><b>Range:</b> 1 through 600 seconds<br><b>Default:</b> 300 seconds                                                                                                                                                                 |
| Required Privilege Level | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                          |
| Related Documentation    | <ul style="list-style-type: none"><li>• <a href="#">Configuring Graceful Restart Options for BGP</a></li><li>• <a href="#">Configuring Graceful Restart for QFabric Systems</a></li><li>• <a href="#">restart-time (BGP Graceful Restart) on page 482</a></li></ul>                                                                                          |



## station

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <pre> station <i>station-name</i> {     authentication-algorithm (aes-128-cmac-96   hmac-sha-1-96   md5);     authentication-key <i>key</i>;     authentication-key-chain <i>authentication-key-chain</i>;     connection-mode (active   passive);     hold-down {         seconds;         flaps <i>flaps</i>;         period <i>seconds</i>;     }     initiation-message <i>text</i>;     local-address <i>address</i>;     local-port <i>port</i>;     monitor (disable   enable);     priority (high   low   medium);     route-monitoring {         none;         post-policy {             exclude-non-eligible;         }         pre-policy {             exclude-non-feasible;         }     }     station-address (<i>ip-address</i>   <i>name</i>);     station-port <i>port-number</i>;     statistics-timeout <i>seconds</i>;     traceoptions {         file <i>filename</i> &lt;files <i>number</i>&gt; &lt;size <i>size</i>&gt; &lt;world-readable   no-world-readable&gt;;         flag <i>flag</i> &lt;flag-modifier&gt;;     } } </pre> |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit routing-options bmp]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Description</b>              | Specify and configure a BMP monitoring station. Be aware that each BMP monitoring station can use a significant amount of a device's resources. You can configure up to 3 BMP monitoring stations.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Options</b>                  | <p><b><i>station-name</i></b>—Specify a name for the BMP station.</p> <p>The other statements are explained separately.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## station-address

---

|                                 |                                                                                                                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>station-address (address   station-name);</code>                                                                                                                                                                                                                                |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <b>station</b> <i>station-name</i> ] |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                |
| <b>Description</b>              | Specify the name or address for the BMP monitoring station. You can specify one or the other but not both.                                                                                                                                                                            |
| <b>Options</b>                  | <b>station-address</b> —Specify the address for the BMP station. The address should be a valid IPv4 or IPv6 address.<br><br><b>station-name</b> —Specify the name for the BMP station.                                                                                                |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                   |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li></ul>                                                                                                                                                            |

## station-port

---

|                                 |                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>station-port port;</code>                                                                                                                                                                                                                                                                                                         |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <b>station</b> <i>station-name</i> ]                                                   |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                  |
| <b>Description</b>              | Specify the port number for the BMP monitoring station.                                                                                                                                                                                                                                                                                 |
| <b>Options</b>                  | <b>port</b> —Specify the port number for the BMP monitoring station. If the <b>connection-mode</b> statement is configured as <b>active</b> a station port number is required. If the <b>connection-mode</b> statement is configured as <b>passive</b> , you must not configure a station port number.<br><b>Range:</b> 1 through 65535 |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                     |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li> <li>• <a href="#">connection-mode on page 403</a></li> </ul>                                                                                                                                                     |

## statistics-timeout

---

|                                 |                                                                                                                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>statistics-timeout <i>seconds</i>;</code>                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>          | [edit logical-systems <i>logical-system-name</i> routing-options bmp],<br>[edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i> ],<br>[edit routing-options bmp],<br>[edit routing-options bmp <b>station</b> <i>station-name</i> ] |
| <b>Release Information</b>      | Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Statement introduced in Junos OS Release 13.3.<br>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                |
| <b>Description</b>              | Specify how often statistics messages are sent to the BMP monitoring station. If you configure a value of 0, no statistics messages are sent.                                                                                                                                         |
| <b>Options</b>                  | <b>seconds</b> —Specify the number for the BMP monitoring station.<br><b>Default:</b> 3600 seconds<br><b>Range:</b> 15 through 65535 seconds                                                                                                                                          |
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                   |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <a href="#">Configuring BGP Monitoring Protocol Version 3 on page 59</a></li></ul>                                                                                                                                                            |

## tcp-mss (Protocols BGP)

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <code>tcp-mss <i>segment-size</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Hierarchy Level</b>          | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>neighbor-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>neighbor-name</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocol bgp group <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>neighbor-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>neighbor-name</i>]</p> |
| <b>Release Information</b>      | <p>Statement introduced in Junos OS Release 8.1.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Description</b>              | <p>Configure the maximum segment size (MSS) for the TCP connection for BGP neighbors.</p> <p>The MSS is only valid in increments of 2 KB. The value used is based on the value set, but is rounded down to the nearest multiple of 2048.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Options</b>                  | <p><b><i>segment-size</i></b>—MSS for the TCP connection.</p> <p><b>Range:</b> 1 through 4096</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | <p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">Example: Limiting TCP Segment Size for BGP on page 326</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## threshold (detection-time)

**Syntax** threshold *milliseconds*;

**Hierarchy Level** [edit logical-systems *logical-system-name* protocols bgp bfd-liveness-detection detection-time],  
 [edit logical-systems *logical-system-name* protocols bgp group *group-name* bfd-liveness-detection detection-time],  
 [edit logical-systems *logical-system-name* protocols bgp group *group-name* neighbor *address* bfd-liveness-detection detection-time],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp bfd-liveness-detection detection-time],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp group *group-name* bfd-liveness-detection detection-time],  
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols bgp group *group-name* neighbor *address* bfd-liveness-detection detection-time],  
 [edit logical-system *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn oam bfd-liveness-detection detection-time],  
 [edit logical-system *logical-system-name* routing-instances *routing-instance-name* protocols vpls neighbor *neighbor-id* oam bfd-liveness-detection detection-time],  
 [edit logical-system *logical-system-name* routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name* neighbor *neighbor-id* oam bfd-liveness-detection detection-time],  
 [edit logical-system *logical-system-name* routing-instances *routing-instance-name* protocols vpls oam bfd-liveness-detection detection-time],  
 [edit protocols bgp bfd-liveness-detection detection-time],  
 [edit protocols bgp group *group-name* bfd-liveness-detection detection-time],  
 [edit protocols bgp group *group-name* neighbor *address* bgp bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols bgp bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols bgp group *group-name* bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols bgp group *group-name* neighbor *address* bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols l2vpn oam bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols vpls neighbor *neighbor-id* oam bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name* neighbor *neighbor-id* oam bfd-liveness-detection detection-time],  
 [edit routing-instances *routing-instance-name* protocols vpls oam bfd-liveness-detection detection-time]

**Release Information** Statement introduced in Junos OS Release 8.2.  
 Statement introduced in Junos OS Release 9.0 for EX Series switches.  
 Support for BFD authentication introduced in Junos OS Release 9.6.  
 Statement introduced in Junos OS Release 12.1 for the QFX Series.  
 Statement introduced in Junos OS Release 13.2 for Layer 2 VPNs and VPLS.  
 Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.

**Description** Specify the threshold for the adaptation of the BFD session detection time. When the detection time adapts to a value equal to or greater than the threshold, a single trap and a single system log message are sent.



**NOTE:** The threshold value must be equal to or greater than the transmit interval.

The threshold time must be equal to or greater than the value specified in the `minimum-interval` or the `minimum-receive-interval` statement.

**Options** *milliseconds*—Value for the detection time adaptation threshold.  
**Range:** 1 through 255,000

**Required Privilege Level** routing—To view this statement in the configuration.  
 routing-control—To add this statement to the configuration.

**Related Documentation**

- *Configuring BFD for Layer 2 VPN and VPLS*
- *Example: Configuring BFD for Static Routes for Faster Network Failure Detection*

## threshold (transmit-interval)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <code>threshold <i>milliseconds</i>;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection transmit-interval],</p> <p>[edit protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection transmit-interval],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection transmit-interval]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.2.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 12.1 for QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Description</b>         | Specify the threshold for the adaptation of the BFD session transmit interval. When the transmit interval adapts to a value greater than the threshold, a single trap and a single system message are sent.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |



**Options** *milliseconds*—Value for the transmit interval adaptation threshold.

**Range:** 0 through 4,294,967,295 ( $2^{32} - 1$ )




**NOTE:** The threshold value specified in the `threshold` statement must be greater than the value specified in the `minimum-interval` statement for the `transmit-interval` statement.

**Required Privilege Level** routing—To view this statement in the configuration.  
routing-control—To add this statement to the configuration.

**Related Documentation**

- *Configuring BFD for Layer 2 VPN and VPLS*
- *Example: Configuring BFD for Static Routes for Faster Network Failure Detection*
- [bfd-liveness-detection on page 395](#)

## traceoptions (Protocols BGP)

|                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                                                                                                                                                                        | <pre> traceoptions {     file <i>filename</i> &lt;files <i>number</i>&gt; &lt;size <i>size</i>&gt; &lt;world-readable   no-world-readable&gt;;     flag <i>flag</i> &lt;flag-modifier&gt; &lt;disable&gt;; } </pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>                                                                                                                                                               | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp <b>group</b> <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit protocols bgp],</p> <p>[edit protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp <b>group</b> <i>group-name</i>],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>]</p> |
| <b>Release Information</b>                                                                                                                                                           | <p>Statement introduced before Junos OS Release 7.4.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 11.3 for the QFX Series.</p> <p><b>4byte-as</b> statement introduced in Junos OS Release 9.2.</p> <p><b>4byte-as</b> statement introduced in Junos OS Release 9.2 for EX Series switches.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Description</b>                                                                                                                                                                   | Configure BGP protocol-level tracing options. To specify more than one tracing operation, include multiple flag statements.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <div>  <b>NOTE:</b> The <b>traceoptions</b> statement is not supported on QFabric systems. </div> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Default</b>                                                                                                                                                                       | The default BGP protocol-level tracing options are inherited from the routing protocols <b>traceoptions</b> statement included at the [edit routing-options] hierarchy level. The default group-level trace options are inherited from the BGP protocol-level <b>traceoptions</b> statement. The default peer-level trace options are inherited from the group-level <b>traceoptions</b> statement.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Options</b>                                                                                                                                                                       | <b>disable</b> —(Optional) Disable the tracing operation. You can use this option to disable a single operation when you have defined a broad group of tracing operations, such as <b>all</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

**file *name***—Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory `/var/log`. We recommend that you place BGP tracing output in the file `bgp-log`.

**files *number***—(Optional) Maximum number of trace files. When a trace file named `trace-file.0` reaches its maximum size, it is renamed `trace-file.0`, then `trace-file.1`, and so on, until the maximum number of trace files is reached. Then, the oldest trace file is overwritten. If you specify a maximum number of files, you must also specify a maximum file size with the **size** option.

**Range:** 2 through 1000 files

**Default:** 10 files

**flag**—Tracing operation to perform. To specify more than one tracing operation, include multiple **flag** statements.

#### BGP Tracing Flags

- **4byte-as**—4-byte AS events.
- **bfd**—BFD protocol events.
- **damping**—Damping operations.
- **graceful-restart**—Graceful restart events.
- **keepalive**—BGP keepalive messages. If you enable the the BGP **update** flag only, received keepalive messages do not generate a trace message.
- **nsr-synchronization**—Nonstop routing synchronization events.
- **open**—Open packets. These packets are sent between peers when they are establishing a connection.
- **packets**—All BGP protocol packets.
- **refresh**—BGP refresh packets.
- **update**—Update packets. These packets provide routing updates to BGP systems. If you enable only this flag, received keepalive messages do not generate a trace message. Use the **keepalive** flag to generate a trace message for keepalive messages.

#### Global Tracing Flags

- **all**—All tracing operations
- **general**—A combination of the **normal** and **route** trace operations
- **normal**—All normal operations

**Default:** If you do not specify this option, only unusual or abnormal operations are traced.

- **policy**—Policy operations and actions
- **route**—Routing table changes
- **state**—State transitions
- **task**—Routing protocol task processing
- **timer**—Routing protocol timer processing

**flag-modifier**—(Optional) Modifier for the tracing flag. You can specify one or more of these modifiers:

- **detail**—Provide detailed trace information.
- **filter**—Provide filter trace information. Applies only to **route**, **damping**, and **update** tracing flags.
- **receive**—Trace the packets being received.
- **send**—Trace the packets being transmitted.

**no-world-readable**—(Optional) Prevent any user from reading the log file.

**size size**—(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named **trace-file** reaches this size, it is renamed **trace-file.0**. When the **trace-file** again reaches its maximum size, **trace-file.0** is renamed **trace-file.1** and **trace-file** is renamed **trace-file.0**. This renaming scheme continues until the maximum number of trace files is reached. Then, the oldest trace file is overwritten. If you specify a maximum file size, you also must specify a maximum number of trace files with the **files** option.

**Syntax:** **xk** to specify KB, **xm** to specify MB, or **xg** to specify GB

**Range:** 10 KB through the maximum file size supported on your system

**Default:** 128 KB

**world-readable**—(Optional) Allow any user to read the log file.

|                                 |                                                                                                                                                 |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing and trace—To view this statement in the configuration.<br>routing-control and trace-control—To add this statement to the configuration. |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|

|                              |                                                                                                                                                                                                                                                                                                                                                               |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Related Documentation</b> | <ul style="list-style-type: none"><li>• <a href="#">log-updown on page 443</a> statement</li><li>• <i>Tracing Nonstop Active Routing Synchronization Events</i></li><li>• <a href="#">Understanding Trace Operations for BGP Protocol Traffic on page 365</a></li><li>• <i>Configuring OSPF Refresh and Flooding Reduction in Stable Topologies</i></li></ul> |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## traceoptions (Protocols BMP)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <pre> traceoptions {     file <i>file-name</i> &lt;files <i>number</i>&gt; &lt;size <i>size</i>&gt; &lt;world-readable   no-world-readable&gt;;     flag <i>flag</i> &lt;<i>flag-modifier</i>&gt; &lt;disable&gt;; } </pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> routing-options bmp],<br/> [edit logical-systems <i>logical-system-name</i> routing-options bmp <b>station</b> <i>station-name</i>],<br/> [edit routing-options bmp],<br/> [edit routing-options bmp <b>station</b> <i>station-name</i>]</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br/> Statement introduced in Junos OS Release 13.3.<br/> Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Description</b>         | <p>Configure tracing options for BMP monitoring. To specify more than one tracing operation, include multiple flag statements.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Options</b>             | <p><b>file</b> <i>file-name</i>—Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory <b>/var/log</b>. We recommend that you place BMP tracing output in the file <b>bmp-log</b>.</p> <p><b>files</b> <i>number</i>—(Optional) Maximum number of trace files. When a trace file named <b>trace-file.0</b> reaches its maximum size, it is renamed <b>trace-file.0</b>, then <b>trace-file.1</b>, and so on, until the maximum number of trace files is reached. Then, the oldest trace file is overwritten. If you specify a maximum number of files, you must also specify a maximum file size with the <b>size</b> option.</p> <p><b>Range:</b> 2 through 1000 files<br/> <b>Default:</b> 10 files</p> <p><b>flag</b>—Tracing operation to perform. To specify more than one tracing operation, include multiple <b>flag</b> statements.</p> <ul style="list-style-type: none"> <li>• <b>all</b>—Trace all BMP monitoring operations.</li> <li>• <b>down</b>—Down messages.</li> <li>• <b>error</b>—Error conditions.</li> <li>• <b>event</b>—Major events, station establishment, errors, and events.</li> <li>• <b>general</b>—General events.</li> <li>• <b>normal</b>—Normal events.</li> <li>• <b>packets</b>—All messages.</li> <li>• <b>policy</b>—Policy processing.</li> <li>• <b>route</b>—Routing information.</li> <li>• <b>route-monitoring</b>—Route monitoring messages.</li> <li>• <b>state</b>—State transitions.</li> </ul> |

- **statistics**—Statistics messages.
- **task**—Routing protocol task processing.
- **timer**—Routing protocol timer processing.
- **up**—Up messages.
- **write**—Writing of messages.

**flag-modifier**—(Optional) Modifier for the tracing flag. You can specify one or more of these modifiers:

- **detail**—Provide detailed trace information.
- **disable**—Disable the tracing flag.
- **receive**—Trace the packets being received.
- **send**—Trace the packets being transmitted.

**no-world-readable**—(Optional) Prevent any user from reading the log file.

**size size**—(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named **trace-file** reaches this size, it is renamed **trace-file.0**. When the **trace-file** again reaches its maximum size, **trace-file.0** is renamed **trace-file.1** and **trace-file** is renamed **trace-file.0**. This renaming scheme continues until the maximum number of trace files is reached. Then, the oldest trace file is overwritten. If you specify a maximum file size, you also must specify a maximum number of trace files with the **files** option.

**Syntax:** **xk** to specify KB, **xm** to specify MB, or **xg** to specify GB

**Range:** 10 KB through the maximum file size supported on your system

**Default:** 128 KB

**world-readable**—(Optional) Allow any user to read the log file.

|                                 |                                                                                        |
|---------------------------------|----------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing and trace—To view this statement in the configuration.                         |
|                                 | routing-control and trace-control—To add this statement to the configuration.          |
| <b>Related Documentation</b>    | • <a href="#">Tracing BMP Operations on page 363</a>                                   |
|                                 | • <a href="#">Understanding Trace Operations for BGP Protocol Traffic on page 365</a>  |
|                                 | • <a href="#">Configuring OSPF Refresh and Flooding Reduction in Stable Topologies</a> |

## transmit-interval (BFD Liveness Detection)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | <pre>transmit-interval {     minimum-interval milliseconds;     threshold milliseconds; }</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Hierarchy Level</b>     | <pre>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i>   bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i>   bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp group <i>group-name</i> bfd-liveness-detection], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   l2vpn oam bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection], [edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols   vpls oam bfd-liveness-detection], [edit protocols bgp bfd-liveness-detection], [edit protocols bgp group <i>group-name</i> bfd-liveness-detection], [edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i>   bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor   <i>address</i> bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam   bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i>   neighbor <i>neighbor-id</i> oam bfd-liveness-detection], [edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection]</pre> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.2.</p> <p>Statement introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Support for BFD authentication introduced in Junos OS Release 9.6.</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b>         | <p>Specify the transmit interval for the <b>bfd-liveness-detection</b> statement. The negotiated transmit interval for a peer is the interval between the sending of BFD packets to peers. The receive interval for a peer is the minimum time that it requires between packets sent from its peer; the receive interval is not negotiated between peers. To determine the transmit interval, each peer compares its configured minimum transmit interval with its</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

peer's minimum receive interval. The larger of the two numbers is accepted as the transmit interval for that peer.

The remaining statements are explained separately.

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>Required Privilege</b> | routing—To view this statement in the configuration.        |
| <b>Level</b>              | routing-control—To add this statement to the configuration. |

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Related Documentation</b> | <ul style="list-style-type: none"><li>• <i>Configuring BFD for Layer 2 VPN and VPLS</i></li><li>• <i>Example: Configuring BFD for Static Routes for Faster Network Failure Detection</i></li><li>• <a href="#">bfd-liveness-detection on page 395</a></li><li>• <a href="#">threshold on page 494</a></li><li>• <a href="#">minimum-interval on page 452</a></li><li>• <a href="#">minimum-receive-interval on page 454</a></li></ul> |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



## version (BFD Liveness Detection)

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>              | version (0   1   automatic);                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Hierarchy Level</b>     | <p>[edit logical-systems <i>logical-system-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit logical-system <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection],</p> <p>[edit protocols bgp bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit protocols bgp group <i>group-name</i> neighbor <i>address</i> bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols bgp group <i>group-name</i> neighbor <i>address</i> bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols l2vpn oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls mesh-group <i>mesh-group-name</i> neighbor <i>neighbor-id</i> oam bfd-liveness-detection],</p> <p>[edit routing-instances <i>routing-instance-name</i> protocols vpls oam bfd-liveness-detection]</p> |
| <b>Release Information</b> | <p>Statement introduced in Junos OS Release 8.1</p> <p>Statement introduced in Junos OS Release 12.1 for the QFX Series.</p> <p>Statement introduced in Junos OS Release 13.2 for Layer 2 VPN and VPLS.</p> <p>Statement introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Description</b>         | Specify the BFD version for detection. You can explicitly configure BFD version 0, version 1, or the routing device can automatically detect the BFD version. By default, the routing device automatically detects the BFD version, which is either 0 or 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Options</b>             | <p>Configure the BFD version to detect: <b>0</b> (BFD version 0), <b>1</b> (BFD version 1), or <b>automatic</b> (autodetect the BFD version)</p> <p><b>Default:</b> automatic</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Required Privilege Level</b> | routing—To view this statement in the configuration.<br>routing-control—To add this statement to the configuration.                                                                                                                                                                                                                                                                                                                                                |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"><li>• <a href="#">Configuring BFD for Layer 2 VPN and VPLS</a></li><li>• <a href="#">Example: Configuring BFD Authentication for BGP on page 232</a></li><li>• <a href="#">Example: Configuring BFD on Internal BGP Peer Sessions on page 222</a></li><li>• <a href="#">Example: Configuring BFD Authentication for BGP on page 232</a></li><li>• <a href="#">Understanding BFD Authentication for BGP on page 230</a></li></ul> |

## CHAPTER 12

# Operational Commands

- `clear bgp damping`
- `clear bgp neighbor`
- `clear bgp table`
- `show bgp bmp`
- `show bgp group`
- `show bgp neighbor`
- `show bgp summary`
- `show policy damping`
- `show route damping`
- `show route detail`

## clear bgp damping

---

|                                          |                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| List of Syntax                           | <a href="#">Syntax on page 506</a><br><a href="#">Syntax (EX Series Switch and QFX Series) on page 506</a>                                                                                                                                                                                                                               |
| Syntax                                   | <code>clear bgp damping</code><br><code>&lt;logical-system (all   <i>logical-system-name</i>)&gt;</code><br><code>&lt;prefix&gt;</code>                                                                                                                                                                                                  |
| Syntax (EX Series Switch and QFX Series) | <code>clear bgp damping</code><br><code>&lt;prefix&gt;</code>                                                                                                                                                                                                                                                                            |
| Release Information                      | Command introduced before Junos OS Release 7.4.<br>Command introduced in Junos OS Release 9.0 for EX Series switches.<br>Command introduced in Junos OS Release 11.3 for the QFX Series.<br>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                       |
| Description                              | Clear BGP route flap damping information.                                                                                                                                                                                                                                                                                                |
| Options                                  | <b>none</b> —Clear all BGP route flap damping information.<br><br><b>logical-system (all   <i>logical-system-name</i>)</b> —(Optional) Perform this operation on all logical systems or on a particular logical system.<br><br><b>prefix</b> —(Optional) Clear route flap damping information for only the specified destination prefix. |
| Required Privilege Level                 | clear                                                                                                                                                                                                                                                                                                                                    |
| Related Documentation                    | <ul style="list-style-type: none"><li>• <a href="#">show policy damping on page 544</a></li><li>• <a href="#">show route damping on page 546</a></li></ul>                                                                                                                                                                               |
| List of Sample Output                    | <a href="#">clear bgp damping on page 506</a>                                                                                                                                                                                                                                                                                            |
| Output Fields                            | This command produces no output.                                                                                                                                                                                                                                                                                                         |

### Sample Output

#### clear bgp damping

```
user@host> clear bgp damping
```

## clear bgp neighbor

**List of Syntax**    [Syntax on page 507](#)  
                          [Syntax \(EX Series Switch and QFX Series\) on page 507](#)

**Syntax**    clear bgp neighbor  
                  <all>  
                  <as *as-number*>  
                  <gracefully>  
                  <instance *instance-name*>  
                  <logical-system (all | *logical-system-name*)>  
                  <malformed-route>  
                  <neighbor>  
                  <soft | soft-inbound>  
                  <soft-minimum-igp>  
                  <stale-routes>

**Syntax (EX Series Switch and QFX Series)**    clear bgp neighbor  
                  <all>  
                  <as *as-number*>  
                  <instance *instance-name*>  
                  <malformed-route>  
                  <neighbor>  
                  <soft | soft-inbound>  
                  <soft-minimum-igp>

**Release Information**    Command introduced before Junos OS Release 7.4.  
                                  Command introduced in Junos OS Release 9.0 for EX Series switches.  
                                  Command introduced in Junos OS Release 11.3 for the QFX Series.  
                                  Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.  
                                  **malformed-route** option introduced in Junos OS Release 13.2.  
                                  **all** option introduced in Junos OS Release 14.2.  
                                  **gracefully** and **stale-routes** options introduced in Junos OS Release 15.1.

**Description**    Perform one of the following tasks:

- Change the state of one or more BGP neighbors to **IDLE**. For neighbors in the **ESTABLISHED** state, this command drops the TCP connection to the neighbors and then reestablishes the connection.
- (**soft** keyword only) Reapply export policies and send refresh updates to one or more BGP neighbors without changing their state.
- (**soft-inbound** keyword only) Send a route-refresh message to one or more BGP neighbors without changing their state, and reapply import policies on the received updates.

**Options**    **all**—Change the state of all BGP neighbors to **IDLE**.  
                  **as *as-number***—(Optional) Apply this command only to neighbors in the specified autonomous system (AS).

**gracefully**—(Optional) Enable the BGP peer to start graceful-restart receiving-speaker mode. The receiving speaker also sends its own routes to the restarted speaker, and sends an End-of-RIB marker when it completes the update. The **clear bgp neighbor neighbor-address gracefully** command is the same as **clear bgp neighbor hard** (the default for **clear bgp neighbor**), but it does not use the new Hard Reset subcode on the Notify and Cease messages that are sent. This allows the neighbor to enter GR or LLGR helper mode, if negotiated. The session is still cleared on this router, and this router does not enter GR or LLGR helper mode.

**instance instance-name**—(Optional) Apply this command only to neighbors for the specified routing instance.

**logical-system (all | logical-system-name)**—(Optional) Perform this operation on all logical systems or on a particular logical system.

**malformed-route**—(Optional) Remove malformed routes. If a specific neighbor is provided, Junos OS removes malformed routes for that particular neighbor. Otherwise, Junos OS removes malformed routes for all BGP neighbors. To find routes that have malformed attributes, run the **show route hidden** command, and look for routes marked with **MalformedAttr** in the AS path field.

**neighbor**—(Optional) IP address of a BGP peer. Apply this command only to the specified neighbor.

**soft**—(Optional) Reapply any export policies and send refresh updates to neighbors without clearing the state.

**soft-inbound**—(Optional) Send a route-refresh message to BGP neighbors and reapply import policies on the route updates received from the BGP neighbors without clearing the BGP state.

**soft-minimum-igp**—(Optional) Provide soft refresh of the outbound state when the interior gateway protocol (IGP) metric is reset.

**stale-routes**—(Optional) Any stale route currently being held for the specified neighbor because of BGP graceful restart (GR) or long-lived graceful restart (LLGR) receiver mode operations.

**Required Privilege Level**

clear

**Related Documentation**

- [show bgp neighbor on page 521](#)

**List of Sample Output**

[clear bgp neighbor on page 508](#)

**Output Fields**

When you enter this command, you are provided feedback on the status of your request.

## Sample Output

**clear bgp neighbor**

```
user@host> clear bgp neighbor
```



## clear bgp table

---

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                                   | <code>clear bgp table <i>table-name</i></code><br><code>&lt;logical-system (all   <i>logical-system-name</i>)&gt;</code>                                                                                                                                                                                                                                                                                 |
| <b>Syntax (EX Series Switch and QFX Series)</b> | <code>clear bgp table <i>table-name</i></code>                                                                                                                                                                                                                                                                                                                                                           |
| <b>Release Information</b>                      | Command introduced in Junos OS Release 9.0.<br>Command introduced in Junos OS Release 9.0 for EX Series switches.<br>Command introduced in Junos OS Release 11.3 for the QFX Series.<br>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                           |
| <b>Description</b>                              | Request that BGP refresh routes in a specified routing table.                                                                                                                                                                                                                                                                                                                                            |
| <b>Options</b>                                  | <b><code>logical-system (all   <i>logical-system-name</i>)</code></b> —(Optional) Perform this operation on all logical systems or on a particular logical system.<br><br><b><code>table-name</code></b> —Request that BGP refresh routes in the specified table.                                                                                                                                        |
| <b>Additional Information</b>                   | In some cases, a prefix limit is associated with a routing table for a VPN instance. When this limit is exceeded (for example, because of a network misconfiguration), some routes might not be inserted in the table. Such routes need to be added to the table after the network issue is resolved. Use the <b>clear bgp table</b> command to request that BGP refresh routes in a VPN instance table. |
| <b>Required Privilege Level</b>                 | clear                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>List of Sample Output</b>                    | <a href="#">clear bgp table private.inet.0 on page 510</a><br><a href="#">clear bgp table inet.6 logical-system all on page 510</a><br><a href="#">clear bgp table private.inet.6 logical-system ls1 on page 510</a><br><a href="#">clear bgp table logical-system all inet.0 on page 510</a><br><a href="#">clear bgp table logical-system ls2 private.inet.0 on page 511</a>                           |
| <b>Output Fields</b>                            | This command produces no output.                                                                                                                                                                                                                                                                                                                                                                         |

## Sample Output

[clear bgp table private.inet.0](#)

```
user@host> clear bgp table private.inet.0
```

[clear bgp table inet.6 logical-system all](#)

```
user@host> clear bgp table inet.6 logical-system all
```

[clear bgp table private.inet.6 logical-system ls1](#)

```
user@host> clear bgp table private.inet.6 logical-system ls1
```

[clear bgp table logical-system all inet.0](#)

```
user@host> clear bgp table logical-system all inet.0
```



`clear bgp table logical-system ls2 private.inet.0`

`user@host> clear bgp table logical-system ls2 private.inet.0`

## show bgp bmp

|                                 |                                                                                                                                                                                                                                                                                          |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Syntax</b>                   | <b>show bgp bmp</b>                                                                                                                                                                                                                                                                      |
| <b>Release Information</b>      | <p>Command introduced in Junos OS Release 9.5.</p> <p>Command introduced in Junos OS Release 9.5 for EX Series switches.</p> <p>Command introduced in Junos OS Release 13.2X51-D15 for the QFX Series.</p> <p>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p> |
| <b>Description</b>              | Display information about the BGP Monitoring Protocol (BMP).                                                                                                                                                                                                                             |
| <b>Options</b>                  | This command has no options.                                                                                                                                                                                                                                                             |
| <b>Required Privilege Level</b> | view                                                                                                                                                                                                                                                                                     |
| <b>List of Sample Output</b>    | <a href="#">show bgp bmp on page 512</a>                                                                                                                                                                                                                                                 |
| <b>Output Fields</b>            | <a href="#">Table 6 on page 512</a> lists the output fields for the <b>show bgp bmp</b> command. Output fields are listed in the approximate order in which they appear.                                                                                                                 |

**Table 6: show bgp bmp Output Fields**

| Field Name                          | Field Description                                                                                                                                              |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BMP station address/port</b>     | IP address and port number of the monitoring station to which BGP Monitoring Protocol (BMP) statistics are sent.                                               |
| <b>BMP session state</b>            | Status of the BMP session: <b>UP</b> or <b>DOWN</b> .                                                                                                          |
| <b>Memory consumed by BMP</b>       | Memory used by the active BMP session.                                                                                                                         |
| <b>Statistics timeout</b>           | Amount of time, in seconds, between transmissions of BMP data to the monitoring station.                                                                       |
| <b>Memory limit</b>                 | Threshold, in bytes, at which the routing device stops collecting BMP data.                                                                                    |
| <b>Memory-connect retry timeout</b> | Amount of time, in seconds, after which the routing device attempts to resume a BMP session that was ended after the configured memory threshold was exceeded. |

## Sample Output

### show bgp bmp

```

user@host> show bgp bmp
  BMP station address/port: 172.24.24.157+5454
  BMP session state: DOWN
  Memory consumed by BMP: 0
  Statistics timeout: 15
  Memory limit: 10485760
  Memory connect retry timeout: 600

```



## show bgp group

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>List of Syntax</b>                           | <a href="#">Syntax on page 514</a><br><a href="#">Syntax (EX Series Switch and QFX Series) on page 514</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Syntax</b>                                   | <pre>show bgp group &lt;brief   detail   summary&gt; &lt;group-name&gt; &lt;exact-instance instance-name&gt; &lt;instance instance-name&gt; &lt;logical-system (all   logical-system-name)&gt; &lt;rtf&gt;</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Syntax (EX Series Switch and QFX Series)</b> | <pre>show bgp group &lt;brief   detail   summary&gt; &lt;group-name&gt; &lt;exact-instance instance-name&gt; &lt;instance instance-name&gt;</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Release Information</b>                      | <p>Command introduced before Junos OS Release 7.4.</p> <p>Command introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Command introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p> <p><b>exact-instance</b> option introduced in Junos OS Release 11.4.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Description</b>                              | Display information about the configured BGP groups.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Options</b>                                  | <p><b>none</b>—Display group information about all BGP groups.</p> <p><b>brief   detail   summary</b>—(Optional) Display the specified level of output.</p> <p><b>group-name</b>—(Optional) Display group information for the specified group.</p> <p><b>exact-instance instance-name</b>—(Optional) Display information for the specified instance only.</p> <p><b>instance instance-name</b>—(Optional) Display information about BGP groups for all routing instances whose name begins with this string (for example, <b>cust1</b>, <b>cust11</b>, and <b>cust111</b> are all displayed when you run the <b>show bgp group instance cust1</b> command). The instance name can be master for the main instance, or any valid configured instance name or its prefix.</p> <p><b>logical-system (all   logical-system-name)</b>—(Optional) Perform this operation on all logical systems or on a particular logical system.</p> <p><b>rtf</b>—(Optional) Display BGP group route targeting information.</p> |
| <b>Required Privilege Level</b>                 | view                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>List of Sample Output</b>                    | <a href="#">show bgp group on page 518</a><br><a href="#">show bgp group on page 518</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

[show bgp group brief on page 519](#)  
[show bgp group detail on page 519](#)  
[show bgp group rtf detail on page 520](#)  
[show bgp group summary on page 520](#)

**Output Fields** Table 7 on page 515 describes the output fields for the **show bgp group** command. Output fields are listed in the approximate order in which they appear.

**Table 7: show bgp group Output Fields**

| Field Name                             | Field Description                                                                                                                                                                                                                                      | Level of Output             |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| <b>Group Type or Group</b>             | Type of BGP group: <b>Internal</b> or <b>External</b> .                                                                                                                                                                                                | All levels                  |
| <b>group-index</b>                     | Index number for the BGP peer group. The index number differentiates between groups when a single BGP group is split because of different configuration options at the group and peer levels.                                                          | <b>rtf detail</b>           |
| <b>AS</b>                              | AS number of the peer. For internal BGP (IBGP), this number is the same as <b>Local AS</b> .                                                                                                                                                           | <b>brief detail</b><br>none |
| <b>Local AS</b>                        | AS number of the local routing device.                                                                                                                                                                                                                 | <b>brief detail</b><br>none |
| <b>Name</b>                            | Name of a specific BGP group.                                                                                                                                                                                                                          | <b>brief detail</b><br>none |
| <b>Options</b>                         | The Network Layer Reachability Information (NLRI) format used for BGP VPN multicast.                                                                                                                                                                   | <b>none</b> none            |
| <b>Index</b>                           | Unique index number of a BGP group.                                                                                                                                                                                                                    | <b>brief detail</b><br>none |
| <b>Flags</b>                           | Flags associated with the BGP group. This field is used by Juniper Networks customer support.                                                                                                                                                          | <b>brief detail</b><br>none |
| <b>BGP-Static Advertisement Policy</b> | Policies configured for the BGP group with the <b>advertise-bgp-static policy</b> statement.                                                                                                                                                           | <b>brief</b> none           |
| <b>Remove-private options</b>          | Options associated with the <b>remove-private</b> statement.                                                                                                                                                                                           | <b>brief detail</b><br>none |
| <b>Holdtime</b>                        | Maximum number of seconds allowed to elapse between successive keepalive or update messages that BGP receives from a peer in the BGP group, after which the connection to the peer is closed and routing devices through that peer become unavailable. | <b>brief detail</b><br>none |
| <b>Export</b>                          | Export policies configured for the BGP group with the <b>export</b> statement.                                                                                                                                                                         | <b>brief detail</b><br>none |
| <b>Optimal Route Reflection</b>        | Client nodes (primary and backup) configured in the BGP group.                                                                                                                                                                                         | <b>brief detail</b><br>none |

Table 7: show bgp group Output Fields (*continued*)

| Field Name                                | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Level of Output             |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| <b>MED tracks IGP metric update delay</b> | Time, in seconds, that updates to multiple exit discriminator (MED) are delayed. Also displays the time remaining before the interval is set to expire                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | All levels                  |
| <b>Traffic Statistics Interval</b>        | Time between sample periods for labeled-unicast traffic statistics, in seconds.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | <b>brief detail</b><br>none |
| <b>Total peers</b>                        | Total number of peers in the group.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <b>brief detail</b><br>none |
| <b>Established</b>                        | Number of peers in the group that are in the established state.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | All levels                  |
| <b>Active/Received/Accepted/Damped</b>    | <p>Multipurpose field that displays information about BGP peer sessions. The field's contents depend upon whether a session is established and whether it was established in the main routing device or in a routing instance.</p> <ul style="list-style-type: none"> <li>If a peer is not established, the field shows the state of the peer session: <b>Active</b>, <b>Connect</b>, or <b>Idle</b>.</li> <li>If a BGP session is established in the main routing device, the field shows the number of active, received, accepted, and damped routes that are received from a neighbor and appear in the <b>inet.0</b> (main) and <b>inet.2</b> (multicast) routing tables. For example, <b>8/10/10/2</b> and <b>2/4/4/0</b> indicate the following: <ul style="list-style-type: none"> <li>8 active routes, 10 received routes, 10 accepted routes, and 2 damped routes from a BGP peer appear in the <b>inet.0</b> routing table.</li> <li>2 active routes, 4 received routes, 4 accepted routes, and no damped routes from a BGP peer appear in the <b>inet.2</b> routing table.</li> </ul> </li> </ul> | <b>summary</b>              |
| <b>ip-addresses</b>                       | List of peers who are members of the group. The address is followed by the peer's port number.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | All levels                  |
| <b>Route Queue Timer</b>                  | Number of seconds until queued routes are sent. If this time has already elapsed, this field displays the number of seconds by which the updates are delayed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>detail</b>               |
| <b>Route Queue</b>                        | Number of prefixes that are queued up for sending to the peers in the group.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>detail</b>               |
| <b>inet.number</b>                        | <p>Number of active, received, accepted, and damped routes in the routing table. For example, <b>inet.0: 7/10/9/0</b> indicates the following:</p> <ul style="list-style-type: none"> <li>7 active routes, 10 received routes, 9 accepted routes, and no damped routes from a BGP peer appear in the <b>inet.0</b> routing table.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | none                        |

Table 7: show bgp group Output Fields (*continued*)

| Field Name                      | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Level of Output     |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| <b>Table</b> <i>inet.number</i> | Information about the routing table. <ul style="list-style-type: none"> <li>• <b>Received prefixes</b>—Total number of prefixes from the peer, both active and inactive, that are in the routing table.</li> <li>• <b>Active prefixes</b>—Number of prefixes received from the peer that are active in the routing table.</li> <li>• <b>Suppressed due to damping</b>—Number of routes currently inactive because of damping or other reasons. These routes do not appear in the forwarding table and are not exported by routing protocols.</li> <li>• <b>Advertised prefixes</b>—Number of prefixes advertised to a peer.</li> <li>• <b>Received external prefixes</b>—Total number of prefixes from the external BGP (EBGP) peers, both active and inactive, that are in the routing table.</li> <li>• <b>Active external prefixes</b>—Number of prefixes received from the EBGP peers that are active in the routing table.</li> <li>• <b>Externals suppressed</b>—Number of routes received from EBGP peers currently inactive because of damping or other reasons.</li> <li>• <b>Received internal prefixes</b>—Total number of prefixes from the IBGP peers, both active and inactive, that are in the routing table.</li> <li>• <b>Active internal prefixes</b>—Number of prefixes received from the IBGP peers that are active in the routing table.</li> <li>• <b>Internals suppressed</b>—Number of routes received from IBGP peers currently inactive because of damping or other reasons.</li> <li>• <b>RIB State</b>—Status of the graceful restart process for this routing table: <b>BGP restart is complete</b>, <b>BGP restart in progress</b>, <b>VPN restart in progress</b>, or <b>VPN restart is complete</b>.</li> </ul> | <b>detail</b>       |
| <b>Groups</b>                   | Total number of groups.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | All levels          |
| <b>Peers</b>                    | Total number of peers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | All levels          |
| <b>External</b>                 | Total number of external peers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | All levels          |
| <b>Internal</b>                 | Total number of internal peers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | All levels          |
| <b>Down peers</b>               | Total number of unavailable peers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | All levels          |
| <b>Flaps</b>                    | Total number of flaps that occurred.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | All levels          |
| <b>Table</b>                    | Name of a routing table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <b>brief</b> , none |
| <b>Tot Paths</b>                | Total number of routes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>brief</b> , none |
| <b>Act Paths</b>                | Number of active routes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <b>brief</b> , none |
| <b>Suppressed</b>               | Number of routes currently inactive because of damping or other reasons. These routes do not appear in the forwarding table and are not exported by routing protocols.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <b>brief</b> , none |

Table 7: show bgp group Output Fields (*continued*)

| Field Name   | Field Description                                                                                                                                                                                           | Level of Output |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| History      | Number of withdrawn routes stored locally to keep track of damping history.                                                                                                                                 | brief, none     |
| Damp State   | Number of active routes with a figure of merit greater than zero, but lower than the threshold at which suppression occurs.                                                                                 | brief, none     |
| Pending      | Routes being processed by the BGP import policy.                                                                                                                                                            | brief, none     |
| Group        | Group the peer belongs to in the BGP configuration.                                                                                                                                                         | detail          |
| Receive mask | Mask of the received target included in the advertised route.                                                                                                                                               | detail          |
| Entries      | Number of route entries received.                                                                                                                                                                           | detail          |
| Target       | Route target that is to be passed by route-target filtering. If a route advertised from the provider edge (PE) routing device matches an entry in the route-target filter, the route is passed to the peer. | detail          |
| Mask         | Mask which specifies that the peer receive routes with the given route target.                                                                                                                              | detail          |

## Sample Output

### show bgp group

```
user@host> show bgp group
```

### show bgp group

```
user@host> show bgp group
```

```
Group Type: Internal    AS: 1001                Local AS: 1001
Name: ibgp              Index: 2                Flags: Export Eval
Holdtime: 0
Optimal Route Reflection: igp-primary 1.1.1.1, igp-backup 1.1.2.1
Total peers: 1          Established: 1
1.1.1.2+179
Trace options: all
Trace file: /var/log/bgp-log size 10485760 files 10
bgp.13vpn.2: 0/0/0/0
vpn-1.inet.2: 0/0/0/0
```

```
Group Type: Internal    AS: 1001                Local AS: 1001
Name: ibgp              Index: 3                Flags: Export Eval
Options: RFC6514CompliantSafi129
Holdtime: 0
Optimal Route Reflection: igp-primary 1.1.1.1, igp-backup 1.1.2.1
Total peers: 1          Established: 1
1.1.1.5+61698
Trace options: all
Trace file: /var/log/bgp-log size 10485760 files 10
bgp.13vpn.2: 2/2/2/0
vpn-1.inet.2: 2/2/2/0
```



```

Groups: 2 Peers: 2 External: 0 Internal: 2 Down peers: 0 Flaps: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.l3vpn.2
vpn-1.inet.0 2 2 0 0 0 0
vpn-1.inet.2 0 0 0 0 0 0
vpn-1.inet6.0 2 2 0 0 0 0
vpn-1.mdt.0 0 0 0 0 0 0
vpn-1.mdt.0 0 0 0 0 0 0

```

### show bgp group brief

```

user@host> show bgp group brief
Groups: 2 Peers: 2 External: 0 Internal: 2 Down peers: 1 Flaps: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
inet.0
0 0 0 0 0 0
bgp.l3vpn.0
0 0 0 0 0 0
bgp.rtarget.0
2 0 0 0 0 0

```

### show bgp group detail

```

user@host> show bgp group detail
Group Type: Internal AS: 1 Local AS: 1
Name: ibgp Index: 0 Flags: <Export Eval>
Holdtime: 0
Optimal Route Reflection: igp-primary 1.1.1.1, igp-backup 1.1.2.1
Total peers: 3 Established: 0
22.0.0.2
22.0.0.8
22.0.0.5

Groups: 1 Peers: 3 External: 0 Internal: 3 Down peers: 3 Flaps: 3
Table bgp.l3vpn.0
Received prefixes: 0
Accepted prefixes: 0
Active prefixes: 0
Suppressed due to damping: 0
Received external prefixes: 0
Active external prefixes: 0
Externals suppressed: 0
Received internal prefixes: 0
Active internal prefixes: 0
Internals suppressed: 0
RIB State: BGP restart is complete
RIB State: VPN restart is complete
Table bgp.mdt.0
Received prefixes: 0
Accepted prefixes: 0
Active prefixes: 0
Suppressed due to damping: 0
Received external prefixes: 0

```

```

Active external prefixes: 0
Externals suppressed: 0
Received internal prefixes: 0
Active internal prefixes: 0
Internals suppressed: 0
RIB State: BGP restart is complete
RIB State: VPN restart is complete
Table VPN-A.inet.0
Received prefixes: 0
Accepted prefixes: 0
Active prefixes: 0
Suppressed due to damping: 0
Received external prefixes: 0
Active external prefixes: 0
Externals suppressed: 0
Received internal prefixes: 0
Active internal prefixes: 0
Internals suppressed: 0
RIB State: BGP restart is complete
RIB State: VPN restart is complete
Table VPN-A.mdt.0
Received prefixes: 0
Accepted prefixes: 0
Active prefixes: 0
Suppressed due to damping: 0
Received external prefixes: 0
Active external prefixes: 0
Externals suppressed: 0
Received internal prefixes: 0
Active internal prefixes: 0
Internals suppressed: 0
RIB State: BGP restart is complete
RIB State: VPN restart is complete

```

### show bgp group rtf detail

```

user@host> show bgp group rtf detail
Group: internal (group-index: 0)
  Receive mask: 00000002
  Table: bgp.rtarget.0                                     Entries: 2
    Target
    100:100/64                                             Mask
    200:201/64                                             00000002
                                                         (Group)
Group: internal (group-index: 1)
  Table: bgp.rtarget.0                                     Entries: 1
    Target
    200:201/64                                             Mask
                                                         (Group)

```

### show bgp group summary

```

user@host> show bgp group summary
Group      Type      Peers    Established    Active/Received/Accepted/Damped
ibgp       Internal  3        0

```

| Groups       | Peers | External | Internal | Down peers | Flaps |
|--------------|-------|----------|----------|------------|-------|
| bgp.l3vpn.0  | 3     | 0        | 3        | 3          | 3     |
| bgp.mdt.0    | 3     | 0        | 3        | 3          | 3     |
| VPN-A.inet.0 | 3     | 0        | 3        | 3          | 3     |
| VPN-A.mdt.0  | 3     | 0        | 3        | 3          | 3     |

## show bgp neighbor

|                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>List of Syntax</b>                                        | <a href="#">Syntax on page 521</a><br><a href="#">Syntax (EX Series Switch, QFX Series, and OCX Series) on page 521</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Syntax</b>                                                | <pre>show bgp neighbor &lt;exact-instance <i>instance-name</i>&gt; &lt;instance <i>instance-name</i>&gt; &lt;logical-system (all   <i>logical-system-name</i>)&gt; &lt;neighbor-address&gt; &lt;output-queue&gt; &lt;orf (detail   <i>neighbor-address</i>)</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Syntax (EX Series Switch, QFX Series, and OCX Series)</b> | <pre>show bgp neighbor &lt;instance <i>instance-name</i>&gt; &lt;exact-instance <i>instance-name</i>&gt; &lt;neighbor-address&gt; &lt;orf (<i>neighbor-address</i>   detail)</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Release Information</b>                                   | <p>Command introduced before Junos OS Release 7.4.</p> <p>Command introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Command introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Command introduced in Junos OS Release 14.1x53-D20 for the OCX Series.</p> <p><b>orf</b> option introduced in Junos OS Release 9.2.</p> <p><b>exact-instance</b> option introduced in Junos OS Release 11.4.</p> <p><b>output-queue</b> option introduced in Junos OS Release 16.1</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Description</b>                                           | Display information about BGP peers.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Options</b>                                               | <p><b>none</b>—Display information about all BGP peers.</p> <p><b>exact-instance <i>instance-name</i></b>—(Optional) Display information for the specified instance only.</p> <p><b>instance <i>instance-name</i></b>—(Optional) Display information about BGP peers for all routing instances whose name begins with this string (for example, <b>cust1</b>, <b>cust11</b>, and <b>cust111</b> are all displayed when you run the <b>show bgp neighbor instance cust1</b> command).</p> <p><b>logical-system (all   <i>logical-system-name</i>)</b>—(Optional) Perform this operation on all logical systems or on a particular logical system.</p> <p><b>neighbor-address</b>—(Optional) Display information for only the BGP peer at the specified IP address.</p> <p><b>output-queue</b>—(Optional) Display information regarding the number of routes currently queued in the 17 prioritized BGP output queues.</p> <p><b>orf (detail   <i>neighbor-address</i>)</b>—(Optional) Display outbound route-filtering information for all BGP peers or only for the BGP peer at the specified IP address. The default is to display brief output. Use the <b>detail</b> option to display detailed output.</p> |

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Additional Information</b>   | For information about the <b>local-address</b> , <b>nlri</b> , <b>hold-time</b> , and <b>preference</b> statements, see the <i>Junos OS Routing Protocols Library</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Required Privilege Level</b> | view                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Related Documentation</b>    | <ul style="list-style-type: none"> <li>• <a href="#">clear bgp neighbor on page 507</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>List of Sample Output</b>    | <a href="#">show bgp neighbor on page 529</a><br><a href="#">show bgp neighbor (CLNS) on page 530</a><br><a href="#">show bgp neighbor (Layer 2 VPN) on page 531</a><br><a href="#">show bgp neighbor (Layer 3 VPN) (Not supported on the OCX Series.) on page 533</a><br><a href="#">show bgp neighbor neighbor-address on page 534</a><br><a href="#">show bgp neighbor neighbor-address on page 535</a><br><a href="#">show bgp neighbor neighbor-address (BGP Graceful Restart Enabled) on page 535</a><br><a href="#">show bgp neighbor neighbor-address (BGP Long-Lived Graceful Restart) on page 536</a><br><a href="#">show bgp neighbor orf neighbor-address detail on page 536</a><br><a href="#">show bgp neighbor logical-system on page 537</a><br><a href="#">show bgp neighbor output-queue on page 537</a> |
| <b>Output Fields</b>            | <a href="#">Table 8 on page 522</a> describes the output fields for the <b>show bgp neighbor</b> command. Output fields are listed in the approximate order in which they appear.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

Table 8: show bgp neighbor Output Fields

| Field Name | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Peer       | Address of the BGP neighbor. The address is followed by the neighbor port number.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| AS         | AS number of the peer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local      | Address of the local routing device. The address is followed by the peer port number.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Type       | Type of peer: <b>Internal</b> or <b>External</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| State      | <p>Current state of the BGP session:</p> <ul style="list-style-type: none"> <li>• <b>Active</b>—BGP is initiating a transport protocol connection in an attempt to connect to a peer. If the connection is successful, BGP sends an Open message.</li> <li>• <b>Connect</b>—BGP is waiting for the transport protocol connection to be completed.</li> <li>• <b>Established</b>—The BGP session has been established, and the peers are exchanging update messages.</li> <li>• <b>Idle</b>—This is the first stage of a connection. BGP is waiting for a Start event.</li> <li>• <b>OpenConfirm</b>—BGP has acknowledged receipt of an open message from the peer and is waiting to receive a keepalive or notification message.</li> <li>• <b>OpenSent</b>—BGP has sent an open message and is waiting to receive an open message from the peer.</li> <li>• <b>route reflector client</b>—The BGP session is established with a route reflector client.</li> </ul> |

Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name        | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Flags</b>      | <p>Internal BGP flags:</p> <ul style="list-style-type: none"> <li>• <b>Aggregate Label</b>—BGP has aggregated a set of incoming labels (labels received from the peer) into a single forwarding label.</li> <li>• <b>CleanUp</b>—The peer session is being shut down.</li> <li>• <b>Delete</b>—This peer has been deleted.</li> <li>• <b>Idled</b>—This peer has been permanently idled.</li> <li>• <b>ImportEval</b>—At the last commit operation, this peer was identified as needing to reevaluate all received routes.</li> <li>• <b>Initializing</b>—The peer session is initializing.</li> <li>• <b>SendRtn</b>—Messages are being sent to the peer.</li> <li>• <b>Sync</b>—This peer is synchronized with the rest of the peer group.</li> <li>• <b>RSync</b>—This peer in the backup Routing Engine is synchronized with the BGP peer in the master Routing Engine for nonstop active routing.</li> <li>• <b>TryConnect</b>—Another attempt is being made to connect to the peer.</li> <li>• <b>Unconfigured</b>—This peer is not configured.</li> <li>• <b>WriteFailed</b>—An attempt to write to this peer failed.</li> </ul>                                                                                                       |
| <b>Last state</b> | <p>Previous state of the BGP session:</p> <ul style="list-style-type: none"> <li>• <b>Active</b>—BGP is initiating a transport protocol connection in an attempt to connect to a peer. If the connection is successful, BGP sends an Open message.</li> <li>• <b>Connect</b>—BGP is waiting for the transport protocol connection to be completed.</li> <li>• <b>Established</b>—The BGP session has been established, and the peers are exchanging update messages.</li> <li>• <b>Idle</b>—This is the first stage of a connection. BGP is waiting for a Start event.</li> <li>• <b>OpenConfirm</b>—BGP has acknowledged receipt of an open message from the peer and is waiting to receive a keepalive or notification message.</li> <li>• <b>OpenSent</b>—BGP has sent an open message and is waiting to receive an open message from the peer.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Last event</b> | <p>Last activity that occurred in the BGP session:</p> <ul style="list-style-type: none"> <li>• <b>Closed</b>—The BGP session closed.</li> <li>• <b>ConnectRetry</b>—The transport protocol connection failed, and BGP is trying again to connect.</li> <li>• <b>HoldTime</b>—The session ended because the hold timer expired.</li> <li>• <b>KeepAlive</b>—The local routing device sent a BGP keepalive message to the peer.</li> <li>• <b>Open</b>—The local routing device sent a BGP open message to the peer.</li> <li>• <b>OpenFail</b>—The local routing device did not receive an acknowledgment of a BGP open message from the peer.</li> <li>• <b>RecvKeepAlive</b>—The local routing device received a BGP keepalive message from the peer.</li> <li>• <b>RecvNotify</b>—The local routing device received a BGP notification message from the peer.</li> <li>• <b>RecvOpen</b>—The local routing device received a BGP open message from the peer.</li> <li>• <b>RecvUpdate</b>—The local routing device received a BGP update message from the peer.</li> <li>• <b>Start</b>—The peering session started.</li> <li>• <b>Stop</b>—The peering session stopped.</li> <li>• <b>TransportError</b>—A TCP error occurred.</li> </ul> |

Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name                                                     | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Last error                                                     | <p>Last error that occurred in the BGP session:</p> <ul style="list-style-type: none"> <li>• <b>Cease</b>—An error occurred, such as a version mismatch, that caused the session to close.</li> <li>• <b>Finite State Machine Error</b>—In setting up the session, BGP received a message that it did not understand.</li> <li>• <b>Hold Time Expired</b>—The session's hold time expired.</li> <li>• <b>Message Header Error</b>—The header of a BGP message was malformed.</li> <li>• <b>Open Message Error</b>—A BGP open message contained an error.</li> <li>• <b>None</b>—No errors occurred in the BGP session.</li> <li>• <b>Update Message Error</b>—A BGP update message contained an error.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Export                                                         | Name of the export policy that is configured on the peer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Import                                                         | Name of the import policy that is configured on the peer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Options                                                        | <p>Configured BGP options:</p> <ul style="list-style-type: none"> <li>• <b>AddressFamily</b>—Configured address family: <b>inet</b> or <b>inet-vpn</b>.</li> <li>• <b>AdvertiseBGPStatic</b>—Configured BGP static routes are advertised.</li> <li>• <b>AuthKeyChain</b>—Authentication key change is enabled.</li> <li>• <b>DropPathAttributes</b>—Certain path attributes are configured to be dropped from neighbor updates during inbound processing.</li> <li>• <b>GracefulRestart</b>—Graceful restart is configured.</li> <li>• <b>HoldTime</b>—Hold time configured with the <b>hold-time</b> statement. The hold time is three times the interval at which keepalive messages are sent.</li> <li>• <b>IgnorePathAttributes</b>—Certain path attributes are configured to be ignored in neighbor updates during inbound processing.</li> <li>• <b>Local Address</b>—Address configured with the <b>local-address</b> statement.</li> <li>• <b>LLGR</b>—BGP long-lived graceful restart capability is configured.</li> <li>• <b>LLGRHelperDisabled</b>—BGP long-lived graceful restart is completely disabled for a neighbor.</li> <li>• <b>Multihop</b>—Allow BGP connections to external peers that are not on a directly connected network.</li> <li>• <b>NLRI</b>—Configured MBGP state for the BGP group: <b>multicast</b>, <b>unicast</b>, or both if you have configured <b>nlri any</b>.</li> <li>• <b>Peer AS</b>—Configured peer autonomous system (AS).</li> <li>• <b>Preference</b>—Preference value configured with the <b>preference</b> statement.</li> <li>• <b>Refresh</b>—Configured to refresh automatically when the policy changes.</li> <li>• <b>Rib-group</b>—Configured routing table group.</li> <li>• <b>RFC6514CompliantSafi129</b>—Configured SAFI 129 according to RFC 6514 (BGP VPN multicast used to use SAFI 128).</li> </ul> |
| Path-attributes dropped                                        | Path attribute codes that are dropped from neighbor updates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Path-attributes ignored                                        | Path attribute codes that are ignored during neighbor updates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Peer does not support LLGR Restarter or Receiver functionality | BGP neighbor does not support long-lived graceful restart (LLGR) restarter mode completely.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name                                         | Field Description                                                                                                                                                                                                                                                                                                                                                               |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Peer does not support LLGR Restarter functionality | BGP neighbor does not support long-lived graceful restart (LLGR) restarter mode for any family.                                                                                                                                                                                                                                                                                 |
| Authentication key change                          | (appears only if the <b>authentication-keychain</b> statement has been configured) Name of the authentication keychain enabled.                                                                                                                                                                                                                                                 |
| Authentication algorithm                           | (appears only if the <b>authentication-algorithm</b> statement has been configured) Type of authentication algorithm enabled: <b>hmac</b> or <b>md5</b> .                                                                                                                                                                                                                       |
| Address families configured                        | Names of configured address families for the VPN.                                                                                                                                                                                                                                                                                                                               |
| BGP-Static Advertisement Policy                    | Name of the bgp static policy that is configured on the peer.                                                                                                                                                                                                                                                                                                                   |
| Local Address                                      | Address of the local routing device.                                                                                                                                                                                                                                                                                                                                            |
| Remove-private options                             | Options associated with the <b>remove-private</b> statement.                                                                                                                                                                                                                                                                                                                    |
| Holdtime                                           | Hold time configured with the <b>hold-time</b> statement. The hold time is three times the interval at which keepalive messages are sent.                                                                                                                                                                                                                                       |
| Flags for NLRI inet-label-unicast                  | Flags related to labeled-unicast: <ul style="list-style-type: none"> <li>• <b>TrafficStatistics</b>—Collection of statistics for labeled-unicast traffic is enabled.</li> </ul>                                                                                                                                                                                                 |
| Traffic statistics                                 | Information about labeled-unicast traffic statistics: <ul style="list-style-type: none"> <li>• <b>Options</b>—Options configured for collecting statistics about labeled-unicast traffic.</li> <li>• <b>File</b>—Name and location of statistics log files.</li> <li>• <b>size</b>—Size of all the log files, in bytes.</li> <li>• <b>files</b>—Number of log files.</li> </ul> |
| Traffic Statistics Interval                        | Time between sample periods for labeled-unicast traffic statistics, in seconds.                                                                                                                                                                                                                                                                                                 |
| Preference                                         | Preference value configured with the <b>preference</b> statement.                                                                                                                                                                                                                                                                                                               |
| Outbound Timer                                     | Time for which the route is available in Junos OS routing table before it is exported to BGP. This field is displayed in the output only if the <b>out-delay</b> parameter is configured to a non-zero value.                                                                                                                                                                   |
| Number of flaps                                    | Number of times the BGP session has gone down and then come back up.                                                                                                                                                                                                                                                                                                            |
| Peer ID                                            | Router identifier of the peer.                                                                                                                                                                                                                                                                                                                                                  |
| Group index                                        | Index number for the BGP peer group. The index number differentiates between groups when a single BGP group is split because of different configuration options at the group and peer levels.                                                                                                                                                                                   |

Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name                                                     | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Peer index                                                     | Index that is unique within the BGP group to which the peer belongs.                                                                                                                                                                                                                                                                                                                                                                                  |
| Local ID                                                       | Router identifier of the local routing device.                                                                                                                                                                                                                                                                                                                                                                                                        |
| Local Interface                                                | Name of the interface on the local routing device.                                                                                                                                                                                                                                                                                                                                                                                                    |
| Active holdtime                                                | Hold time that the local routing device negotiated with the peer.                                                                                                                                                                                                                                                                                                                                                                                     |
| Keepalive Interval                                             | Keepalive interval, in seconds.                                                                                                                                                                                                                                                                                                                                                                                                                       |
| BFD                                                            | Status of BFD failure detection.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Local Address                                                  | Name of directly connected interface over which direct EBGP peering is established.                                                                                                                                                                                                                                                                                                                                                                   |
| NLRI and times for LLGR configured on peer                     | <p>Names of address families and stale time for BGP long-lived graceful restart configured on the BGP peer or neighbor.</p> <p>Times are displayed using the routing protocol daemon (rpd) %#OT format:</p> <p><b>&lt;weeks&gt;w&lt;days&gt;d &lt;hours&gt;:&lt;minutes&gt;:&lt;seconds&gt;</b></p> <p>Zero leading elements are omitted, for example, a value less than one week do not include the weeks.</p>                                       |
| NLRI and times that peer supports LLGR Restarter for           | <p>Names of address families and stale time that the BGP peer supports for restarter mode for BGP long-lived graceful restart.</p> <p>Times are displayed using the routing protocol daemon (rpd) %#OT format:</p> <p><b>&lt;weeks&gt;w&lt;days&gt;d &lt;hours&gt;:&lt;minutes&gt;:&lt;seconds&gt;</b></p> <p>Zero leading elements are omitted, for example, a value less than one week do not include the weeks.</p>                                |
| NLRI that peer saved LLGR forwarding for                       | Name of the address family for which the BGP peer saved BGP long-lived graceful restart forwarding.                                                                                                                                                                                                                                                                                                                                                   |
| Graceful Restart Details                                       | Amount of time that is remaining until LLGR expires and the time remaining on the GR stale timer, along with RIB details, are displayed while LLGR receiver mode is active (a peer that negotiated LLGR has disconnected and not yet reconnected)                                                                                                                                                                                                     |
| NLRI we are holding stale routes for                           | Names of address families (NLRIs) for which that stale routes are held or preserved when BGP graceful restart receiver mode is active for a neighbor.                                                                                                                                                                                                                                                                                                 |
| Time until end-of-rib is assumed for stale routes              | <p>Amount of time remaining on the stale timer until which end-of-RIB (EoR) markers are assumed when BGP graceful restart receiver mode is active for a neighbor.</p> <p>Time is displayed in Coordinated Universal Time (UTC) format (YYYY-MM-DD-HH:MM:SS). Note that the stale timer display ('Time until end-of-rib is assumed') is also present when a session is active, but the neighbor as not yet sent all of the end-of-rib indications.</p> |
| Time until stale routes are deleted or become long-lived stale | Amount of time up to which stale routes are deleted or become long-lived stale routes when BGP graceful restart receiver mode is active for a neighbor.                                                                                                                                                                                                                                                                                               |



Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name                                    | Field Description                                                                                                                                                                                           |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NLRI for restart configured on peer           | Names of address families configured for restart.                                                                                                                                                           |
| NLRI advertised by peer                       | Address families supported by the peer: <b>unicast</b> or <b>multicast</b> .                                                                                                                                |
| NLRI for this session                         | Address families being used for this session.                                                                                                                                                               |
| Peer supports Refresh capability              | Remote peer's ability to send and request full route table readvertisement (route refresh capability). For more information, see RFC 2918, <i>Route Refresh Capability for BGP-4</i> .                      |
| Restart time configured on peer               | Configured time allowed for restart on the neighbor.                                                                                                                                                        |
| Stale routes from peer are kept for           | When graceful restart is negotiated, the maximum time allowed to hold routes from neighbors after the BGP session has gone down.                                                                            |
| Peer does not support Restarter functionality | Graceful restart restarter-mode is disabled on the peer.                                                                                                                                                    |
| Peer does not support Receiver functionality  | Graceful restart helper-mode is disabled on the peer.                                                                                                                                                       |
| Restart time requested by this peer           | Restart time requested by this neighbor during capability negotiation.                                                                                                                                      |
| Restart flag received from the peer           | When this field appears, the BGP speaker has restarted (Restarting), and this peer should not wait for the <b>end-of-rib</b> marker from the speaker before advertising routing information to the speaker. |
| NLRI that peer supports restart for           | Neighbor supports graceful restart for this address family.                                                                                                                                                 |
| NLRI peer can save forwarding state           | Neighbor supporting this address family saves all forwarding states.                                                                                                                                        |
| NLRI that peer saved forwarding for           | Neighbor saves all forwarding states for this address family.                                                                                                                                               |
| NLRI that restart is negotiated for           | Router supports graceful restart for this address family.                                                                                                                                                   |
| NLRI of received end-of-rib markers           | Address families for which end-of-routing-table markers are received from the neighbor.                                                                                                                     |
| NLRI of all end-of-rib markers sent           | Address families for which end-of-routing-table markers are sent to the neighbor.                                                                                                                           |
| Peer supports 4 byte AS extension (peer-as 1) | Peer understands 4-byte AS numbers in BGP messages. The peer is running Junos OS Release 9.1 or later.                                                                                                      |

Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name                                                 | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NLRIs for which peer can receive multiple paths            | <p>Appears in the command output of the local router if the downstream peer is configured to receive multiple BGP routes to a single destination, instead of only receiving the active route.</p> <p>Possible value is <b>inet-unicast</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| NLRIs for which peer can send multiple paths: inet-unicast | <p>Appears in the command output of the local router if the upstream peer is configured to send multiple BGP routes to a single destination, instead of only sending the active route.</p> <p>Possible value is <b>inet-unicast</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Table inet.number                                          | <p>Information about the routing table:</p> <ul style="list-style-type: none"> <li>• <b>RIB State</b>—BGP is in the graceful restart process for this routing table: <b>restart is complete</b> or <b>restart in progress</b>.</li> <li>• <b>Bit</b>—Number that represents the entry in the routing table for this peer.</li> <li>• <b>Send state</b>—State of the BGP group: <b>in sync</b>, <b>not in sync</b>, or <b>not advertising</b>.</li> <li>• <b>Active prefixes</b>—Number of prefixes received from the peer that are active in the routing table.</li> <li>• <b>Received prefixes</b>—Total number of prefixes from the peer, both active and inactive, that are in the routing table.</li> <li>• <b>Accepted prefixes</b>—Total number of prefixes from the peer that have been accepted by a routing policy.</li> <li>• <b>Suppressed due to damping</b>—Number of routes currently inactive because of damping or other reasons. These routes do not appear in the forwarding table and are not exported by routing protocols.</li> </ul> |
| Last traffic (seconds)                                     | Last time any traffic was received from the peer or sent to the peer, and the last time the local routing device checked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Input messages                                             | Messages that BGP has received from the receive socket buffer, showing the total number of messages, number of update messages, number of times a policy is changed and refreshed, and the buffer size in octets. The buffer size is 16 KB.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Output messages                                            | Messages that BGP has written to the transmit socket buffer, showing the total number of messages, number of update messages, number of times a policy is changed and refreshed, and the buffer size in octets. The buffer size is 16 KB.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Input dropped path attributes                              | <p>Information about dropped path attributes:</p> <ul style="list-style-type: none"> <li>• <b>Code</b>—Path attribute code.</li> <li>• <b>Count</b>—Path attribute count.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Input ignored path attributes                              | <p>Information about ignored path attributes:</p> <ul style="list-style-type: none"> <li>• <b>Code</b>—Path attribute code.</li> <li>• <b>Count</b>—Path attribute count.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

Table 8: show bgp neighbor Output Fields (*continued*)

| Field Name                     | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Output queue</b>            | <p>Number of BGP packets that are queued to be transmitted to a particular neighbor for a particular routing table. Output queue 0 is for unicast NLRIs, and queue 1 is for multicast NLRIs.</p> <p>It also specifies the routing table name and the NLRI that the table was advertised through, in the format (<i>routing table name, NLRI</i>).</p> <p><b>NOTE:</b> The output queue of routing tables that are not advertised, will only show up at <b>extensive</b> output level.</p> |
| <b>Trace options</b>           | Configured tracing of BGP protocol packets and operations.                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Trace file</b>              | Name of the file to receive the output of the tracing operation.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Filter Updates rcv</b>      | <p>(<b>orf</b> option only) Number of outbound-route filters received for each configured address family.</p> <p><b>NOTE:</b> The counter is cumulative. For example, the counter is increased after the remote peer either resends or clears the outbound route filtering prefix list.</p>                                                                                                                                                                                               |
| <b>Immediate</b>               | <p>(<b>orf</b> option only) Number of route updates received with the immediate flag set. The immediate flag indicates that the BGP peer should readvertise the updated routes.</p> <p><b>NOTE:</b> The counter is cumulative. For example, the counter is increased after the remote peer either resends or clears the outbound route filtering prefix list.</p>                                                                                                                         |
| <b>Filter</b>                  | ( <b>orf</b> option only) Type of prefix filter received: <b>prefix-based</b> or <b>extended-community</b> .                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Received filter entries</b> | ( <b>orf</b> option only) List of received filters displayed.                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>seq</b>                     | ( <b>orf</b> option only) Numerical order assigned to this prefix entry among all the received outbound route filter prefix entries.                                                                                                                                                                                                                                                                                                                                                      |
| <b>prefix</b>                  | ( <b>orf</b> option only) Address for the prefix entry that matches the filter.                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>minlength</b>               | ( <b>orf</b> option only) Minimum prefix length, in bits, required to match this prefix.                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>maxlength</b>               | ( <b>orf</b> option only) Maximum prefix length, in bits, required to match this prefix.                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>match</b>                   | ( <b>orf</b> option only) For this prefix match, whether to <b>permit</b> or <b>deny</b> route updates.                                                                                                                                                                                                                                                                                                                                                                                   |

## Sample Output

### show bgp neighbor

```
user@host > show bgp neighbor
```

For M Series, MX Series, and T Series routers running Junos OS Release 16.1 or later, the **show bgp neighbor** output includes the BGP group the peer belongs to, the routing instance (if any) that the peer is configured in, and the routing instance that the peer is using for the forwarding context (if applicable). An example follows.

```

Peer: 10.255.7.250+179 AS 10   Local: 10.255.7.248+63740 AS 10
  Group: toAsbr2               Routing-Instance: master
  Forwarding routing-instance: toAs2
    Type: Internal   State: Established   Flags: <Sync>
  Last State: OpenConfirm   Last Event: RecvKeepAlive
  Last Error: None
  Export: [ redist_static ]
  Options: <Preference LocalAddress PeerAS Refresh>
  Options: <AdvertiseBGPStatic>
  Local Address: 10.255.7.248 Holdtime: 90 Preference: 170 Outbound Timer: 50
  Number of flaps: 0
  Peer ID: 10.255.7.250   Local ID: 10.255.7.248   Active Holdtime: 90
  Keepalive Interval: 30   Group index: 0   Peer index: 0
  BFD: disabled, down
  NLRI for restart configured on peer: inet-unicast
  NLRI advertised by peer: inet-unicast
  NLRI for this session: inet-unicast
  Peer supports Refresh capability (2)
  Stale routes from peer are kept for: 300
  Peer does not support Restarter functionality
  NLRI that restart is negotiated for: inet-unicast
  NLRI of received end-of-rib markers: inet-unicast
  NLRI of all end-of-rib markers sent: inet-unicast
  Peer supports 4 byte AS extension (peer-as 10)
  Peer does not support Addpath
  Table inet.0 Bit: 10000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          1
    Received prefixes:        1
    Accepted prefixes:        1
    Suppressed due to damping: 0
    Advertised prefixes:      1
  Last traffic (seconds): Received 9   Sent 5   Checked 5
  Input messages: Total 36   Updates 2   Refreshes 0   Octets 718
  Output messages: Total 37   Updates 1   Refreshes 0   Octets 796
  Output Queue[0]: 0 (inet.0, inet-unicast)

Peer: 10.255.162.214+52193 AS 100 Local: 10.255.167.205+179 AS 100
  Type: Internal   State: Established (route reflector client)Flags: <Sync>
  Last State: OpenConfirm   Last Event: RecvKeepAlive
  Last Error: None
  Options: <Preference LocalAddress Cluster AddressFamily Rib-group Refresh>
  Address families configured: inet-unicast inet-vpn-unicast route-target
  Local Address: 10.255.167.205 Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 10.255.162.214   Local ID: 10.255.167.205   Active Holdtime: 90
  Keepalive Interval: 30   Group index: 0   Peer index: 1

```

### show bgp neighbor (CLNS)

```

user@host> show bgp neighbor
Peer: 10.245.245.1+179 AS 200   Local: 10.245.245.3+3770 AS 100
  Type: External   State: Established   Flags: <ImportEval Sync>
  Last State: OpenConfirm   Last Event: RecvKeepAlive
  Last Error: None
  Options: <Multihop Preference LocalAddress HoldTime AddressFamily PeerAS
  Rib-group Refresh>
  Address families configured: iso-vpn-unicast
  Local Address: 10.245.245.3 Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 10.245.245.1   Local ID: 10.245.245.3   Active Holdtime: 90

```

```

Keepalive Interval: 30          Peer index: 0
NLRI advertised by peer: iso-vpn-unicast
NLRI for this session: iso-vpn-unicast
Peer supports Refresh capability (2)
Table bgp.isovpn.0 Bit: 10000
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: in sync
  Active prefixes:              3
  Received prefixes:            3
  Suppressed due to damping:    0
  Advertised prefixes:          3
Table aaaa.iso.0
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: not advertising
  Active prefixes:              3
  Received prefixes:            3
  Suppressed due to damping:    0
Last traffic (seconds): Received 6   Sent 5   Checked 5
Input messages: Total 1736   Updates 4   Refreshes 0   Octets 33385
Output messages: Total 1738   Updates 3   Refreshes 0   Octets 33305
Output Queue[0]: 0 (bgp.isovpn.0, iso-vpn-unicast)
Output Queue[1]: 0 (aaaa.iso.0, iso-vpn-unicast)

```

### show bgp neighbor (Layer 2 VPN)

```

user@host> show bgp neighbor
Peer: 10.69.103.2      AS 65536 Local: 10.69.103.1      AS 65539
  Type: External      State: Active      Flags: <ImportEval>
  Last State: Idle     Last Event: Start
  Last Error: None
  Export: [ BGP-INET-import ]
  Options: <Preference LocalAddress HoldTime GracefulRestart AddressFamily PeerAS
Refresh>
  Address families configured: inet-unicast
  Local Address: 10.69.103.1 Holdtime: 90 Preference: 170
  Number of flaps: 0
Peer: 10.69.104.2      AS 65539 Local: 10.69.104.1      AS 65539
  Type: External      State: Active      Flags: <ImportEval>
  Last State: Idle     Last Event: Start
  Last Error: None
  Export: [ BGP-L-import ]
  Options: <Preference LocalAddress HoldTime GracefulRestart AddressFamily PeerAS
Refresh>
  Address families configured: inet-labeled-unicast
  Local Address: 10.69.104.1 Holdtime: 90 Preference: 170
  Number of flaps: 0
Peer: 10.255.14.182+179 AS 69   Local: 10.255.14.176+2131 AS 69
  Type: Internal      State: Established  Flags: <ImportEval>
  Last State: OpenConfirm Last Event: RecvKeepAlive
  Last Error: None
  Options: <Preference LocalAddress HoldTime GracefulRestart AddressFamily
Rib-group Refresh>
  Address families configured: inet-vpn-unicast l2vpn
  Local Address: 10.255.14.176 Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 10.255.14.182   Local ID: 10.255.14.176   Active Holdtime: 90
  Keepalive Interval: 30
  NLRI for restart configured on peer: inet-vpn-unicast l2vpn
  NLRI advertised by peer: inet-vpn-unicast l2vpn

```

```

NLRI for this session: inet-vpn-unicast 12vpn
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-vpn-unicast 12vpn
NLRI peer can save forwarding state: inet-vpn-unicast 12vpn
NLRI that peer saved forwarding for: inet-vpn-unicast 12vpn
NLRI that restart is negotiated for: inet-vpn-unicast 12vpn
NLRI of received end-of-rib markers: inet-vpn-unicast 12vpn
Table bgp.13vpn.0 Bit: 10000
  RIB State: BGP restart in progress
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          10
  Received prefixes:        10
  Suppressed due to damping: 0
Table bgp.12vpn.0 Bit: 20000
  RIB State: BGP restart in progress
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          1
  Received prefixes:        1
  Suppressed due to damping: 0
Table BGP-INET.inet.0 Bit: 30000
  RIB State: BGP restart in progress
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          2
  Received prefixes:        2
  Suppressed due to damping: 0
Table BGP-L.inet.0 Bit: 40000
  RIB State: BGP restart in progress
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          2
  Received prefixes:        2
  Suppressed due to damping: 0
Table LDP.inet.0 Bit: 50000
  RIB State: BGP restart is complete
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          1
  Received prefixes:        1
  Suppressed due to damping: 0
Table OSPF.inet.0 Bit: 60000
  RIB State: BGP restart is complete
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          2
  Received prefixes:        2
  Suppressed due to damping: 0
Table RIP.inet.0 Bit: 70000
  RIB State: BGP restart is complete
  RIB State: VPN restart in progress
  Send state: in sync
  Active prefixes:          2
  Received prefixes:        2
  Suppressed due to damping: 0
Table STATIC.inet.0 Bit: 80000
  RIB State: BGP restart is complete

```

```

RIB State: VPN restart in progress
Send state: in sync
Active prefixes:          1
Received prefixes:        1
Suppressed due to damping: 0
Table L2VPN.l2vpn.0 Bit: 90000
RIB State: BGP restart is complete
RIB State: VPN restart in progress
Send state: in sync
Active prefixes:          1
Received prefixes:        1
Suppressed due to damping: 0
Last traffic (seconds): Received 0    Sent 0    Checked 0
Input messages: Total 14    Updates 13    Refreshes 0    Octets 1053
Output messages: Total 3    Updates 0    Refreshes 0    Octets 105
Output Queue[0]: 0 (bgp.l3vpn.0, inet-vpn-unicast)
Output Queue[1]: 0 (bgp.l2vpn.0, inet-vpn-unicast)
Output Queue[2]: 0 (BGP-INET.inet.0, inet-vpn-unicast)
Output Queue[3]: 0 (BGP-L.inet.0, inet-vpn-unicast)
Output Queue[4]: 0 (LDP.inet.0, inet-vpn-unicast)
Output Queue[5]: 0 (OSPF.inet.0, inet-vpn-unicast)
Output Queue[6]: 0 (RIP.inet.0, inet-vpn-unicast)
Output Queue[7]: 0 (STATIC.inet.0, inet-vpn-unicast)
Output Queue[8]: 0 (L2VPN.l2vpn.0, inet-vpn-unicast)

```

#### show bgp neighbor (Layer 3 VPN) (Not supported on the OCX Series.)

```

user@host> show bgp neighbor
Peer: 192.0.2.0.179    AS 10045 Local: 192.0.2.1+1214    AS 10045
Type: Internal    State: Established    Flags: <ImportEval>
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: None
Export: [ match-all ] Import: [ match-all ]
Options: <Preference LocalAddress HoldTime GracefulRestart AddressFamily
Rib-group Refresh>
Address families configured: inet-vpn-unicast
Local Address: 192.0.2.1 Holdtime: 90 Preference: 170
Flags for NLRI inet-labeled-unicast: TrafficStatistics
Traffic Statistics: Options: all File: /var/log/bstat.log
                                size 131072 files 10

Traffic Statistics Interval: 60
Number of flaps: 0
Peer ID: 192.168.1.110    Local ID: 192.168.1.111    Active Holdtime: 90
Keepalive Interval: 30
NLRI for restart configured on peer: inet-vpn-unicast
NLRI advertised by peer: inet-vpn-unicast
NLRI for this session: inet-vpn-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-vpn-unicast
NLRI peer can save forwarding state: inet-vpn-unicast
NLRI that peer saved forwarding for: inet-vpn-unicast
NLRI that restart is negotiated for: inet-vpn-unicast
NLRI of received end-of-rib markers: inet-vpn-unicast
NLRI of all end-of-rib markers sent: inet-vpn-unicast
Table bgp.l3vpn.0 Bit: 10000
RIB State: BGP restart is complete
RIB State: VPN restart is complete
Send state: in sync

```

```

Active prefixes:          2
Received prefixes:       2
Suppressed due to damping: 0
Table vpn-green.inet.0 Bit: 20001
RIB State: BGP restart is complete
RIB State: VPN restart is complete
Send state: in sync
Active prefixes:          2
Received prefixes:       2
Suppressed due to damping: 0
Last traffic (seconds): Received 15   Sent 20   Checked 20
Input messages: Total 40   Updates 2   Refreshes 0   Octets 856
Output messages: Total 44   Updates 2   Refreshes 0   Octets 1066
Output Queue[0]: 0 (bgp.l3vpn.0, inet-vpn-unicast)
Output Queue[1]: 0 (vpn-green.inet.0, inet-vpn-unicast)
Trace options: detail packets
Trace file: /var/log/bgpr.log size 131072 files 10

```

### show bgp neighbor neighbor-address

```

user@host> show bgp neighbor 192.168.1.111
Peer: 10.255.245.12+179 AS 35 Local: 10.255.245.13+2884 AS 35
Type: Internal State: Established (route reflector client)Flags: <Sync>
Last State: OpenConfirm Last Event: RecvKeepAlive
Last Error: None
Options: <Preference LocalAddress HoldTime Cluster AddressFamily Rib-group
Refresh>
Options: RFC6514CompliantSafi129
Address families configured: inet-vpn-unicast inet-labeled-unicast
Local Address: 10.255.245.13 Holdtime: 90 Preference: 170
Flags for NLRI inet-vpn-unicast: AggregateLabel
Flags for NLRI inet-labeled-unicast: AggregateLabel
Number of flaps: 0
Peer ID: 10.255.245.12 Local ID: 10.255.245.13 Active Holdtime: 90
Keepalive Interval: 30
BFD: disabled
NLRI advertised by peer: inet-vpn-unicast inet-labeled-unicast
NLRI for this session: inet-vpn-unicast inet-labeled-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 300
Stale routes from peer are kept for: 60
Restart time requested by this peer: 300
NLRI that peer supports restart for: inet-unicast inet6-unicast
NLRI that restart is negotiated for: inet-unicast inet6-unicast
NLRI of received end-of-rib markers: inet-unicast inet6-unicast
NLRI of all end-of-rib markers sent: inet-unicast inet6-unicast
Table inet.0 Bit: 10000
RIB State: restart is complete
Send state: in sync
Active prefixes: 4
Received prefixes: 6
Suppressed due to damping: 0
Table inet6.0 Bit: 20000
RIB State: restart is complete
Send state: in sync
Active prefixes: 0
Received prefixes: 2
Suppressed due to damping: 0
Last traffic (seconds): Received 3   Sent 3   Checked 3
Input messages: Total 9   Updates 6   Refreshes 0   Octets 403
Output messages: Total 7   Updates 3   Refreshes 0   Octets 365

```



```

Output Queue[0]: 0 (inet.0, inet-unicast)
Output Queue[1]: 0 (inet6.0, inet6-unicast)
Trace options: detail packets
Trace file: /var/log/bgpgr size 131072 files 10

```

### show bgp neighbor neighbor-address

```

user@host> show bgp neighbor 192.168.4.222
Peer: 192.168.4.222+4902 AS 65501 Local: 192.168.4.221+179 AS 65500
  Type: External    State: Established    Flags: <Sync>
  Last State: OpenConfirm    Last Event: RecvKeepAlive
  Last Error: Cease
  Export: [ export-policy ] Import: [ import-policy ]
  Options: <Preference HoldTime AddressFamily PeerAS PrefixLimit Refresh>
  Address families configured: inet-unicast inet-multicast
  Holdtime: 60000 Preference: 170
  Number of flaps: 4
  Last flap event: RecvUpdate
  Error: 'Cease' Sent: 5 Recv: 0
  Peer ID: 10.255.245.6    Local ID: 10.255.245.5    Active Holdtime: 60000
  Keepalive Interval: 20000    Peer index: 0
  BFD: disabled, down
  Local Interface: fxp0.0
  NLRI advertised by peer: inet-unicast inet-multicast
  NLRI for this session: inet-unicast inet-multicast
  Peer supports Refresh capability (2)
  Table inet.0 Bit: 10000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          8
    Received prefixes:        10
    Accepted prefixes:        10
    Suppressed due to damping: 0
    Advertised prefixes:      3
  Table inet.2 Bit: 20000
    RIB State: BGP restart is complete
    Send state: in sync
    Active prefixes:          0
    Received prefixes:        0
    Accepted prefixes:        0
    Suppressed due to damping: 0
    Advertised prefixes:      0
  Last traffic (seconds): Received 357 Sent 357 Checked 357
  Input messages: Total 4 Updates 2 Refreshes 0 Octets 211
  Output messages: Total 4 Updates 1 Refreshes 0 Octets 147
  Output Queue[0]: 0 (inet.0, inet-unicast)
  Output Queue[1]: 0 (inet.2, inet-multiicast)
  Trace options: all
  Trace file: /var/log/bgp size 10485760 files 10

```

### show bgp neighbor neighbor-address (BGP Graceful Restart Enabled)

```

user@router> show bgp neighbor 10.255.255.16

Peer: 10.255.255.16 AS 100    Local: 10.255.255.12 AS 100
  Type: Internal    State: Active        Flags: <>
  Last State: Idle    Last Event: Start
  Last Error: None
  Options: <Preference LocalAddress AddressFamily Rib-group Refresh>
  Options: <LLGR>
  Address families configured: l2vpn

```

```

Local Address: 10.255.255.12 Holdtime: 90 Preference: 170
NLRI l2vpn:
Number of flaps: 6
Last flap event: Restart
NLRI we are holding stale routes for: inet-vpn-unicast
Time until stale routes are deleted or become long-lived stale: 00:01:57
Time until end-of-rib is assumed for stale routes: 00:04:43
Table bgp.l3vpn.0
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: not advertising
  Active prefixes:          0
  Received prefixes:        7
  Accepted prefixes:        7
  Suppressed due to damping: 0
Table foo.inet.0 Bit: 30000
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: not in sync
  Active prefixes:          0
  Received prefixes:        7
  Accepted prefixes:        7
  Suppressed due to damping: 0

```

### show bgp neighbor neighbor-address (BGP Long-Lived Graceful Restart)

```

user@router> show bgp neighbor 10.4.12.11

Peer: 10.4.12.11 AS 100      Local: 10.6.128.225 AS 100
Type: Internal      State: Active      Flags: <>
Last State: Idle      Last Event: Start
Last Error: None
Export: [ foo ]
Options: <Preference LocalAddress Refresh GracefulRestart>
Options: <LLGR>
Local Address: 10.6.128.225 Holdtime: 90 Preference: 170
Number of flaps: 3
Last flap event: Restart
Error: 'Cease' Sent: 0 Recv: 1
Time until long-lived stale routes deleted: inet-vpn-unicast 10:00:22
route-target 10:00:22
Table bgp.l3vpn.0
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: not advertising
  Active prefixes:          0
  Received prefixes:        7
  Accepted prefixes:        7
  Suppressed due to damping: 0
Table foo.inet.0 Bit: 30000
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: not in sync
  Active prefixes:          0
  Received prefixes:        7
  Accepted prefixes:        7
  Suppressed due to damping: 0

```

### show bgp neighbor orf neighbor-address detail

```

user@host > show bgp neighbor orf 192.168.165.56 detail

```

```

Peer: 192.168.165.56+179 Type: External
Group: ext1

inet-unicast
  Filter updates rcv:          1 Immediate:          1
  Filter: prefix-based receive
  Received filter entries:
    seq 1: prefix 2.2.2.2/32: minlen 32: maxlen 32: match deny:

inet6-unicast
  Filter updates rcv:          0 Immediate:          1
  Filter: prefix-based receive
  Received filter entries:
    *:*
```

### show bgp neighbor logical-system

```

user@host > show bgp neighbor logical-system ITR1
Peer: 10.79.8.2+179 AS 65536 Local: 10.79.8.1+50891 AS 65500
Description: MX1
Type: External State: Established Flags: <ImportEval Sync>
Last State: OpenConfirm Last Event: RecvKeepAlive
Last Error: None
...
Table inet.0 Bit: 10000
RIB State: BGP restart is complete
Send state: in sync
Active prefixes:          1
Received prefixes:        1
Accepted prefixes:        1
Suppressed due to damping: 0
Advertised prefixes:      10
Stale prefixes:           4: <=new, line only appears if count is non-0
It is the Number of prefixes marked as stale;
LLGR-stale prefixes:      5: <=new, line only appears if count is non-0
It is the Number of prefixes marked as LLGR-stale
```

### show bgp neighbor output-queue

```

user@host > show bgp neighbor output-queue
Peer: 192.0.2.2+179 AS 103 Local: 192.0.2.1+50799 AS 102
Output Queue[0]: 0 (inet.0, inet-unicast)
Priority 1 : 0
Priority 2 : 0
Priority 3 : 0
Priority 4 : 0
Priority 5 : 0
Priority 6 : 0
Priority 7 : 0
Priority 8 : 0
Priority 9 : 0
Priority 10: 0
Priority 11: 0
Priority 12: 0
Priority 13: 0
Priority 14: 0
Priority 15: 0
Priority 16: 0
Expedited : 0
```

## show bgp summary

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>List of Syntax</b>                           | <a href="#">Syntax on page 538</a><br><a href="#">Syntax (EX Series Switch and QFX Series) on page 538</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Syntax</b>                                   | <pre>show bgp summary &lt;exact-instance <i>instance-name</i>&gt; &lt;group <i>group-name</i>&gt; &lt;instance <i>instance-name</i>&gt; &lt;logical-system (all   <i>logical-system-name</i>)&gt;</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Syntax (EX Series Switch and QFX Series)</b> | <pre>show bgp summary &lt;exact-instance <i>instance-name</i>&gt; &lt;instance <i>instance-name</i>&gt;</pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Release Information</b>                      | <p>Command introduced before Junos OS Release 7.4.</p> <p>Command introduced in Junos OS Release 9.0 for EX Series switches.</p> <p>Command introduced in Junos OS Release 11.3 for the QFX Series.</p> <p>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.</p> <p><b>exact-instance</b> option introduced in Junos OS Release 11.4.</p> <p><b>group</b> option introduced in Junos OS Release 13.3.</p>                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Description</b>                              | Display BGP summary information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Options</b>                                  | <p><b>none</b>—Display BGP summary information for all routing instances.</p> <p><b>exact-instance <i>instance-name</i></b>—(Optional) Display information for the specified instance only.</p> <p><b>group</b>—Display overview of bgp information for a particular group</p> <p><b>instance <i>instance-name</i></b>—(Optional) Display information for all routing instances whose name begins with this string (for example, <b>cust1</b>, <b>cust11</b>, and <b>cust111</b> are all displayed when you run the <b>show bgp summary instance cust1</b> command). The instance name can be master for the main instance, or any valid configured instance name or its prefix.</p> <p><b>logical-system (all   <i>logical-system-name</i>)</b>—(Optional) Perform this operation on all logical systems or on a particular logical system.</p> |
| <b>Required Privilege Level</b>                 | view                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>List of Sample Output</b>                    | <a href="#">show bgp summary (When a Peer Is Not Established) on page 541</a><br><a href="#">show bgp summary (When a Peer Is Established) on page 541</a><br><a href="#">show bgp summary (CLNS) on page 541</a><br><a href="#">show bgp summary (Layer 2 VPN) on page 542</a><br><a href="#">show bgp summary (Layer 3 VPN) on page 542</a><br><a href="#">show bgp summary group on page 542</a><br><a href="#">show bgp summary (BGP Graceful Restart or Long-Lived Graceful Restart) on page 543</a>                                                                                                                                                                                                                                                                                                                                        |

**Output Fields** Table 9 on page 539 describes the output fields for the **show bgp summary** command. Output fields are listed in the approximate order in which they appear.

**Table 9: show bgp summary Output Fields**

| Field Name          | Field Description                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Groups</b>       | Number of BGP groups.                                                                                                                                                  |
| <b>Peers</b>        | Number of BGP peers.                                                                                                                                                   |
| <b>Down peers</b>   | Number of down BGP peers.                                                                                                                                              |
| <b>Table</b>        | Name of routing table.                                                                                                                                                 |
| <b>Tot Paths</b>    | Total number of paths.                                                                                                                                                 |
| <b>Act Paths</b>    | Number of active routes.                                                                                                                                               |
| <b>Suppressed</b>   | Number of routes currently inactive because of damping or other reasons. These routes do not appear in the forwarding table and are not exported by routing protocols. |
| <b>History</b>      | Number of withdrawn routes stored locally to keep track of damping history.                                                                                            |
| <b>Damp State</b>   | Number of routes with a figure of merit greater than zero, but still active because the value has not reached the threshold at which suppression occurs.               |
| <b>Pending</b>      | Routes in process by BGP import policy.                                                                                                                                |
| <b>Peer</b>         | Address of each BGP peer. Each peer has one line of output.                                                                                                            |
| <b>AS</b>           | Peer's AS number.                                                                                                                                                      |
| <b>InPkt</b>        | Number of packets received from the peer.                                                                                                                              |
| <b>OutPkt</b>       | Number of packets sent to the peer.                                                                                                                                    |
| <b>OutQ</b>         | Number of BGP packets that are queued to be transmitted to a particular neighbor. It normally is 0 because the queue usually is emptied quickly.                       |
| <b>Flaps</b>        | Number of times the BGP session has gone down and then come back up.                                                                                                   |
| <b>Last Up/Down</b> | Last time since the neighbor transitioned to or from the established state.                                                                                            |

Table 9: show bgp summary Output Fields (*continued*)

| Field Name                                              | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>State #Active<br/>/Received/Accepted<br/>/Damped</b> | <p>Multipurpose field that displays information about BGP peer sessions. The field's contents depend upon whether a session is established and whether it was established on the main routing device or in a routing instance.</p> <ul style="list-style-type: none"> <li>If a peer is not established, the field shows the state of the peer session: <b>Active</b>, <b>Connect</b>, or <b>Idle</b>. In general, the Idle state is the first stage of a connection. BGP is waiting for a Start event. A session can be idle for other reasons as well. The reason that a session is idle is sometimes displayed. For example: <b>Idle (Removal in progress)</b> or <b>Idle (LicenseFailure)</b>.</li> <li>If a BGP session is established on the main routing device, the field shows the number of active, received, accepted, and damped routes that are received from a neighbor and appear in the <b>inet.0</b> (main) and <b>inet.2</b> (multicast) routing tables. For example, <b>8/10/10/2</b> and <b>2/4/4/0</b> indicate the following: <ul style="list-style-type: none"> <li>8 active routes, 10 received routes, 10 accepted routes, and 2 damped routes from a BGP peer appear in the <b>inet.0</b> routing table.</li> <li>2 active routes, 4 received routes, 4 accepted routes, and no damped routes from a BGP peer appear in the <b>inet.2</b> routing table.</li> </ul> </li> <li>If a BGP session is established in a routing instance, the field indicates the established (<b>Establ</b>) state, identifies the specific routing table that receives BGP updates, and shows the number of active, received, and damped routes that are received from a neighbor. For example, <b>Establ VPN-AB.inet.0: 2/4/0</b> indicates the following: <ul style="list-style-type: none"> <li>The BGP session is established.</li> <li>Routes are received in the <b>VPN-AB.inet.0</b> routing table.</li> <li>The local routing device has two active routes, four received routes, and no damped routes from a BGP peer.</li> </ul> </li> </ul> <p>When a BGP session is established, the peers are exchanging update messages.</p> <p><b>NOTE:</b> When graceful restart or LLGR helper mode is active, the RIB information is now displayed by the <b>show bgp summary</b> command. If a BGP session is established on the main routing device, the field shows the number of active, received, accepted, and damped routes that are received from a neighbor and appear in the inet.0 (main) and inet.2 (multicast) routing tables. For example, 8/10/10/2 and 2/4/4/0 indicate the following:</p> <ul style="list-style-type: none"> <li>8 active routes, 10 received routes, 10 accepted routes, and 2 damped routes from a BGP peer appear in the inet.0 routing table.</li> <li>2 active routes, 4 received routes, 4 accepted routes, and no damped routes from a BGP peer appear in the inet.2 routing table.</li> </ul> |

## Sample Output

### show bgp summary (When a Peer Is Not Established)

```

user@host> show bgp summary
Groups: 2 Peers: 4 Down peers: 1
Table Tot Paths Act Paths Suppressed History Damp State Pending
inet.0 6 4 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Damped...
10.0.0.3 65002 86 90 0 2 42:54 0/0/0

0/0/0
10.0.0.4 65002 90 91 0 1 42:54 0/2/0

0/0/0
10.0.0.6 65002 87 90 0 3 3 Active
10.1.12.1 65001 89 89 0 1 42:54 4/4/0

0/0/0

```

### show bgp summary (When a Peer Is Established)

```

user@host> show bgp summary
Groups: 1 Peers: 3 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
inet.0 6 4 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Damped...
10.0.0.2 65002 88675 88652 0 2 42:38 2/4/0

0/0/0
10.0.0.3 65002 54528 54532 0 1 2w4d22h 0/0/0

0/0/0
10.0.0.4 65002 51597 51584 0 0 2w3d22h 2/2/0

0/0/0
user@host> show bgp summary logical-system R3
Groups: 2 Peers: 2 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.13vpn.0 2 2 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
1.1.1.2 2 204 206 0 0 1:30:59
Establ
  bgp.13vpn.0: 2/2/2/0
  red.inet.0: 2/2/2/0
10.1.1.10 3 206 207 0 0 1:31:36
Establ
  red.inet.0: 2/2/2/0

```

### show bgp summary (CLNS)

```

user@host> show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Damped...
10.245.245.1 200 1735 1737 0 0 14:26:12 Establ

```

```

bgp.isovpn.0: 3/3/0
aaaa.iso.0: 3/3/0

```

### show bgp summary (Layer 2 VPN)

```

user@host> show bgp summary
Groups: 1 Peers: 5 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.l2vpn.0 1 1 0 0 0
inet.0 0 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last
Up/Dwn State|#Active/Received/Damped...
10.255.245.35 65299 72 74 0 1 19:00 Establ
  bgp.l2vpn.0: 1/1/0
  frame-vpn.l2vpn.0: 1/1/0
10.255.245.36 65299 2164 2423 0 4 19:50 Establ
  bgp.l2vpn.0: 0/0/0
  frame-vpn.l2vpn.0: 0/0/0
10.255.245.37 65299 36 37 0 4 17:07 Establ
  inet.0: 0/0/0
10.255.245.39 65299 138 168 0 6 53:48 Establ
  bgp.l2vpn.0: 0/0/0
  frame-vpn.l2vpn.0: 0/0/0
10.255.245.69 65299 134 140 0 6 53:42 Establ
  inet.0: 0/0/0

```

### show bgp summary (Layer 3 VPN)

```

user@host> show bgp summary
Groups: 2 Peers: 2 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.l3vpn.0 2 2 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Damped...
10.39.1.5 2 21 22 0 0 6:26 Establ
  VPN-AB.inet.0: 1/1/0
10.255.71.15 1 19 21 0 0 6:17 Establ
  bgp.l3vpn.0: 2/2/0
  VPN-A.inet.0: 1/1/0
  VPN-AB.inet.0: 2/2/0
  VPN-B.inet.0: 1/1/0

```

### show bgp summary group

```

user@host> show bgp summary group Group2
Groups: 3 Peers: 3 Down peers: 3
Table Tot Paths Act Paths Suppressed History Damp State Pending
inet.0 0 0 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.0.0.1 56 0 0 0 0 51
Idle

user@host> show bgp summary logical-system R3 group toR4
Groups: 2 Peers: 2 Down peers: 0
Table Tot Paths Act Paths Suppressed History Damp State Pending
bgp.l3vpn.0 2 2 0 0 0
Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.1.1.10 3 207 207 0 0 1:31:40

```



```
Establ
red.inet.0: 2/2/2/0
```

### show bgp summary (BGP Graceful Restart or Long-Lived Graceful Restart)

```
user@router> show route receive-protocol bgp 10.4.12.11 detail
Groups: 2 Peers: 9 Down peers: 1
...
Peer          AS      InPkt    OutPkt    OutQ    Flaps Last Up/Dwn
State|#Active/Received/Accepted/Damped...
10.255.255.16 100        7         6         0         4         4
Idle
  bgp.13vpn.0: 0/7/7/0
  foo.inet.0: 0/7/7/0
```

## show policy damping

---

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>List of Syntax</b>                           | <a href="#">Syntax on page 544</a><br><a href="#">Syntax (EX Series Switch and QFX Series) on page 544</a>                                                                                                                                                                                                                                                                                                                                                           |
| <b>Syntax</b>                                   | show policy damping<br><logical-system (all   <i>logical-system-name</i> )>                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Syntax (EX Series Switch and QFX Series)</b> | show policy damping                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Release Information</b>                      | Command introduced before Junos OS Release 7.4.<br>Command introduced in Junos OS Release 9.0 for EX Series switches.<br>Command introduced in Junos OS Release 11.3 for the QFX Series.<br>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                   |
| <b>Description</b>                              | Display information about BGP route flap damping parameters.                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Options</b>                                  | <b>none</b> —Display information about BGP route flap damping parameters.<br><br><b>logical-system (all   <i>logical-system-name</i>)</b> —(Optional) Perform this operation on all logical systems or on a particular logical system.                                                                                                                                                                                                                               |
| <b>Additional Information</b>                   | In the output from this command, figure-of-merit values correlate with the probability of future instability of a routing device. Routes with higher figure-of-merit values are suppressed for longer periods of time. The figure-of-merit value decays exponentially over time. A figure-of-merit value of zero is assigned to each new route. The value is increased each time the route is withdrawn or readvertised, or when one of its path attributes changes. |
| <b>Required Privilege Level</b>                 | view                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Related Documentation</b>                    | <ul style="list-style-type: none"><li>• “Configuring BGP Flap Damping Parameters” in the <i>Routing Policies, Firewall Filters, and Traffic Policers Feature Guide</i></li><li>• <a href="#">clear bgp damping on page 506</a></li><li>• <a href="#">show route damping on page 546</a></li></ul>                                                                                                                                                                    |
| <b>List of Sample Output</b>                    | <a href="#">show policy damping on page 545</a>                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Output Fields</b>                            | <a href="#">Table 10 on page 545</a> describes the output fields for the <b>show policy damping</b> command. Output fields are listed in the approximate order in which they appear.                                                                                                                                                                                                                                                                                 |

Table 10: show policy damping Output Fields

| Field Name                   | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Halflife</b>              | Decay half-life, in minutes. The value represents the period during which the accumulated figure-of-merit value is reduced by half if the route remains stable. If a route has flapped, but then becomes stable, the figure-of-merit value for the route decays exponentially. For example, for a route with a figure-of-merit value of 1500, if no incidents occur, its figure-of-merit value is reduced to 750 after 15 minutes and to 375 after another 15 minutes. |
| <b>Reuse merit</b>           | Figure-of-merit value below which a suppressed route can be used again. A suppressed route becomes reusable when its figure-of-merit value decays to a value below a reuse threshold, and the route once again is considered usable and can be installed in the forwarding table and exported from the routing table.                                                                                                                                                  |
| <b>Suppress/cutoff merit</b> | Figure-of-merit value above which a route is suppressed for use or inclusion in advertisements. When a route's figure-of-merit value reaches a particular level, called the cutoff or suppression threshold, the route is suppressed. When a route is suppressed, the routing table no longer installs the route into the forwarding table and no longer exports this route to any of the routing protocols.                                                           |
| <b>Maximum suppress time</b> | Maximum hold-down time, in minutes. The value represents the maximum time that a route can be suppressed no matter how unstable it has been before this period of stability.                                                                                                                                                                                                                                                                                           |
| <b>Computed values</b>       | <ul style="list-style-type: none"> <li>• <b>Merit ceiling</b>—Maximum merit that a flapping route can collect.</li> <li>• <b>Maximum decay</b>—Maximum decay half-life, in minutes.</li> </ul>                                                                                                                                                                                                                                                                         |

## Sample Output

### show policy damping

```

user@host> show policy damping
Default damping information:
  Halflife: 15 minutes
  Reuse merit: 750 Suppress/cutoff merit: 3000
  Maximum suppress time: 60 minutes
  Computed values:
    Merit ceiling: 12110
    Maximum decay: 6193
Damping information for "standard-damping":
  Halflife: 10 minutes
  Reuse merit: 4000 Suppress/cutoff merit: 8000
  Maximum suppress time: 30 minutes
  Computed values:
    Merit ceiling: 32120
    Maximum decay: 12453

```

## show route damping

---

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| List of Syntax                           | <a href="#">Syntax on page 546</a><br><a href="#">Syntax (EX Series Switch and QFX Series) on page 546</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Syntax                                   | <code>show route damping (decayed   history   suppressed)</code><br><code>&lt;brief   detail   extensive   terse&gt;</code><br><code>&lt;logical-system (all   <i>logical-system-name</i>)&gt;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Syntax (EX Series Switch and QFX Series) | <code>show route damping (decayed   history   suppressed)</code><br><code>&lt;brief   detail   extensive   terse&gt;</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Release Information                      | Command introduced before Junos OS Release 7.4.<br>Command introduced in Junos OS Release 9.0 for EX Series switches.<br>Command introduced in Junos OS Release 11.3 for the QFX Series.<br>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Description                              | Display the BGP routes for which updates might have been reduced because of route flap damping.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Options                                  | <b>brief   detail   extensive   terse</b> —(Optional) Display the specified level of output. If you do not specify a level of output, the system defaults to brief.<br><br><b>decayed</b> —Display route damping entries that might no longer be valid, but are not suppressed.<br><br><b>history</b> —Display entries that have already been withdrawn, but have been logged.<br><br><b>logical-system (all   <i>logical-system-name</i>)</b> —(Optional) Perform this operation on all logical systems or on a particular logical system.<br><br><b>suppressed</b> —Display entries that have been suppressed and are no longer being installed into the forwarding table or exported by routing protocols. |
| Required Privilege Level                 | view                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Related Documentation                    | <ul style="list-style-type: none"><li>• <a href="#">clear bgp damping on page 506</a></li><li>• <a href="#">show policy damping on page 544</a></li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| List of Sample Output                    | <a href="#">show route damping decayed detail on page 549</a><br><a href="#">show route damping history on page 550</a><br><a href="#">show route damping history detail on page 550</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Output Fields                            | <a href="#">Table 11 on page 547</a> lists the output fields for the <b>show route damping</b> command. Output fields are listed in the approximate order in which they appear.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Table 11: show route damping Output Fields

| Field Name                                   | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Level of Output         |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| <i>routing-table-name</i>                    | Name of the routing table—for example, <b>inet.0</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | All levels              |
| <b>destinations</b>                          | Number of destinations for which there are routes in the routing table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | All levels              |
| <b>number routes</b>                         | Number of routes in the routing table and total number of routes in the following states: <ul style="list-style-type: none"> <li>• <b>active</b></li> <li>• <b>holdddown</b> (routes that are in a pending state before being declared inactive)</li> <li>• <b>hidden</b> (the routes are not used because of a routing policy)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | All levels              |
| <b>destination-prefix (entry, announced)</b> | Destination prefix. The <b>entry</b> value is the number of routes for this destination, and the <b>announced</b> value is the number of routes being announced for this destination.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>detail extensive</b> |
| <b>[protocol, preference]</b>                | Protocol from which the route was learned and the preference value for the route. <ul style="list-style-type: none"> <li>• <b>+</b>—A plus sign indicates the active route, which is the route installed from the routing table into the forwarding table.</li> <li>• <b>-</b>—A hyphen indicates the last active route.</li> <li>• <b>*</b>—An asterisk indicates that the route is both the active and the last active route. An asterisk before a <b>to</b> line indicates the best subpath to the route.</li> </ul> <p>In every routing metric except for the BGP <b>LocalPref</b> attribute, a lesser value is preferred. In order to use common comparison routines, Junos OS stores the 1's complement of the <b>LocalPref</b> value in the <b>Preference2</b> field. For example, if the <b>LocalPref</b> value for Route 1 is 100, the <b>Preference2</b> value is -101. If the <b>LocalPref</b> value for Route 2 is 155, the <b>Preference2</b> value is -156. Route 2 is preferred because it has a higher <b>LocalPref</b> value and a lower <b>Preference2</b> value.</p> | All levels              |
| <b>Next-hop reference count</b>              | Number of references made to the next hop.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | <b>detail extensive</b> |
| <b>Source</b>                                | IP address of the route source.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>detail extensive</b> |
| <b>Next hop</b>                              | Network layer address of the directly reachable neighboring system.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <b>detail extensive</b> |
| <b>via</b>                                   | Interface used to reach the next hop. If there is more than one interface available to the next hop, the interface that is actually used is followed by the word <b>Selected</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <b>detail extensive</b> |
| <b>Protocol next hop</b>                     | Network layer address of the remote routing device that advertised the prefix. This address is used to derive a forwarding next hop.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <b>detail extensive</b> |
| <b>Indirect next hop</b>                     | Index designation used to specify the mapping between protocol next hops, tags, kernel export policy, and the forwarding next hops.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <b>detail extensive</b> |
| <b>State</b>                                 | Flags for this route. For a description of possible values for this field, see the output field table for the <a href="#">show route detail</a> command.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>detail extensive</b> |

Table 11: show route damping Output Fields (*continued*)

| Field Name        | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Level of Output  |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| Local AS          | AS number of the local routing device.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | detail extensive |
| Peer AS           | AS number of the peer routing device.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | detail extensive |
| Age               | How long the route has been known.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | detail extensive |
| Metric            | Metric for the route.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | detail extensive |
| Task              | Name of the protocol that has added the route.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | detail extensive |
| Announcement bits | List of protocols that announce this route. <i>n-Resolve inet</i> indicates that the route is used for route resolution for next hops found in the routing table. <i>n</i> is an index used by Juniper Networks customer support only.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | detail extensive |
| AS path           | <p>AS path through which the route was learned. The letters at the end of the AS path indicate the path origin, providing an indication of the state of the route at the point at which the AS path originated:</p> <ul style="list-style-type: none"> <li>• I—IGP.</li> <li>• E—EGP.</li> <li>• ?—Incomplete; typically, the AS path was aggregated.</li> </ul> <p>When AS path numbers are included in the route, the format is as follows:</p> <ul style="list-style-type: none"> <li>• [ ]—Brackets enclose the local AS number associated with the AS path if more than one AS number is configured on the routing device or if AS path prepending is configured.</li> <li>• { }—Braces enclose AS sets, which are groups of AS numbers in which the order does not matter. A set commonly results from route aggregation. The numbers in each AS set are displayed in ascending order.</li> <li>• ( )—Parentheses enclose a confederation.</li> <li>• ( [ ] )—Parentheses and brackets enclose a confederation set.</li> </ul> <p><b>NOTE:</b> In Junos OS Release 10.3 and later, the AS path field displays an unrecognized attribute and associated hexadecimal value if BGP receives attribute 128 (attribute set) and you have not configured an independent domain in any routing instance.</p> | All levels       |
| to                | Next hop to the destination. An angle bracket (>) indicates that the route is the selected route.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | brief none       |
| via               | Interface used to reach the next hop. If there is more than one interface available to the next hop, the interface that is actually used is followed by the word <b>Selected</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | brief none       |
| Communities       | Community path attribute for the route. See the output field table for the <a href="#">show route detail</a> command.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | detail extensive |
| Localpref         | Local preference value included in the route.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | All levels       |
| Router ID         | BGP router ID as advertised by the neighbor in the open message.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | detail extensive |

Table 11: show route damping Output Fields (*continued*)

| Field Name                     | Field Description                                                                                                                                                        | Level of Output         |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| <b>Merit (last update/now)</b> | Last updated and current figure-of-merit value.                                                                                                                          | <b>detail extensive</b> |
| <b>damping-parameters</b>      | Name that identifies the damping parameters used, which is defined in the damping statement at the <b>[edit policy-options]</b> hierarchy level.                         | <b>detail extensive</b> |
| <b>Last update</b>             | Time of most recent change in path attributes.                                                                                                                           | <b>detail extensive</b> |
| <b>First update</b>            | Time of first change in path attributes, which started the route damping process.                                                                                        | <b>detail extensive</b> |
| <b>Flaps</b>                   | Number of times the route has gone up or down or its path attributes have changed.                                                                                       | <b>detail extensive</b> |
| <b>Suppressed</b>              | ( <b>suppressed</b> keyword only) This route is currently suppressed. A suppressed route does not appear in the forwarding table and routing protocols do not export it. | All levels              |
| <b>Reusable in</b>             | ( <b>suppressed</b> keyword only) Time when a suppressed route will again be available.                                                                                  | All levels              |
| <b>Preference will be</b>      | ( <b>suppressed</b> keyword only) Preference value that will be applied to the route when it is again active.                                                            | All levels              |

## Sample Output

### show route damping decayed detail

```

user@host> show route damping decayed detail
inet.0: 173319 destinations, 1533668 routes (172625 active, 4 holddown, 108083
hidden)
10.0.111.0/24 (7 entries, 1 announced)
  *BGP      Preference: 170/-101
            Next-hop reference count: 151973
            Source: 172.23.2.129
            Next hop: via so-1/2/0.0
            Next hop: via so-5/1/0.0, selected
            Next hop: via so-6/0/0.0
            Protocol next hop: 172.23.2.129
            Indirect next hop: 89a1a00 264185
            State: <Active Ext>
            Local AS: 64500 Peer AS: 64490
            Age: 3:28      Metric2: 0
            Task: BGP_64490.172.23.2.129+179
            Announcement bits (6): 0-KRT 1-RT 4-KRT 5-BGP.0.0.0.0+179

  6-Resolve tree 2 7-Resolve tree 3
    AS path: 64499 64510 645511 645511 645511 645511 I ()
    Communities: 65551:390 65551:2000 65551:3000 65550:701
    Localpref: 100
    Router ID: 172.23.2.129
    Merit (last update/now): 1934/1790
    damping-parameters: damping-high

```

```
Last update:      00:03:28 First update:      00:06:40
Flaps: 2
```

### show route damping history

```
user@host> show route damping history
inet.0: 173320 destinations, 1533529 routes (172624 active, 6 holddown, 108122
hidden)
+ = Active Route, - = Last Active, * = Both

10.108.0.0/15      [BGP ] 2d 22:47:58, localpref 100
                  AS path: 64220 65541 65542 I
                  > to 192.168.60.85 via so-3/1/0.0
```

### show route damping history detail

```
user@host> show route damping history detail
inet.0: 173319 destinations, 1533435 routes (172627 active, 2 holddown, 108105
hidden)
10.108.0.0/15 (3 entries, 1 announced)
    BGP                /-101
        Next-hop reference count: 69058
        Source: 192.168.60.85
        Next hop: 192.168.60.85 via so-3/1/0.0, selected
        State: <Hidden Ext>
        Inactive reason: Unusable path
        Local AS: 64500 Peer AS: 64220
        Age: 2d 22:48:10
        Task: BGP_64220.192.168.60.85+179
        AS path: 64220 65541 65542 I ()
        Communities: 65541:390 65541:2000 65541:3000 65504:3561
        Localpref: 100
        Router ID: 192.168.80.25
        Merit (last update/now): 1000/932
        damping-parameters: set-normal
        Last update:      00:01:05 First update:      00:01:05
        Flaps: 1
```



## show route detail

|                                    |                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>List of Syntax</b>              | <a href="#">Syntax on page 551</a><br><a href="#">Syntax (EX Series Switches) on page 551</a>                                                                                                                                                                                                                                                           |
| <b>Syntax</b>                      | show route detail<br><destination-prefix><br><logical-system (all   logical-system-name)>                                                                                                                                                                                                                                                               |
| <b>Syntax (EX Series Switches)</b> | show route detail<br><destination-prefix>                                                                                                                                                                                                                                                                                                               |
| <b>Release Information</b>         | Command introduced before Junos OS Release 7.4.<br>Command introduced in Junos OS Release 9.0 for EX Series switches.<br>Command introduced in Junos OS Release 13.2X51-D15 for the QFX Series.<br>Command introduced in Junos OS Release 14.1X53-D20 for the OCX Series.                                                                               |
| <b>Description</b>                 | Display detailed information about the active entries in the routing tables.                                                                                                                                                                                                                                                                            |
| <b>Options</b>                     | <b>none</b> —Display all active entries in the routing table on all systems.<br><br><b>destination-prefix</b> —(Optional) Display active entries for the specified address or range of addresses.<br><br><b>logical-system (all   logical-system-name)</b> —(Optional) Perform this operation on all logical systems or on a particular logical system. |
| <b>Required Privilege Level</b>    | view                                                                                                                                                                                                                                                                                                                                                    |
| <b>List of Sample Output</b>       | <a href="#">show route detail on page 562</a><br><a href="#">show route detail (with BGP Multipath) on page 568</a><br><a href="#">show route label detail (Multipoint LDP Inband Signaling for Point-to-Multipoint LSPs) on page 569</a><br><a href="#">show route label detail (Multipoint LDP with Multicast-Only Fast Reroute) on page 569</a>      |
| <b>Output Fields</b>               | Table 12 on page 551 describes the output fields for the <b>show route detail</b> command. Output fields are listed in the approximate order in which they appear.                                                                                                                                                                                      |

**Table 12: show route detail Output Fields**

| Field Name                 | Field Description                                                                                                                                                                                                                                                                                                                                               |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>routing-table-name</i>  | Name of the routing table (for example, inet.0).                                                                                                                                                                                                                                                                                                                |
| <i>number destinations</i> | Number of destinations for which there are routes in the routing table.                                                                                                                                                                                                                                                                                         |
| <i>number routes</i>       | Number of routes in the routing table and total number of routes in the following states: <ul style="list-style-type: none"> <li><b>active</b> (routes that are active)</li> <li><b>holddown</b> (routes that are in the pending state before being declared inactive)</li> <li><b>hidden</b> (routes that are not used because of a routing policy)</li> </ul> |

Table 12: show route detail Output Fields (*continued*)

| Field Name                                     | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>route-destination</b><br>(entry, announced) | <p>Route destination (for example:10.0.0.1/24). The <b>entry</b> value is the number of routes for this destination, and the <b>announced</b> value is the number of routes being announced for this destination. Sometimes the route destination is presented in another format, such as:</p> <ul style="list-style-type: none"> <li>• <b>MPLS-label</b> (for example, 80001).</li> <li>• <b>interface-name</b> (for example, ge-1/0/2).</li> <li>• <b>neighbor-address:control-word-status:encapsulation type:vc-id:source</b> (Layer 2 circuit only; for example, 10.1.1.195:NoCtrlWord:1:1:Local/96). <ul style="list-style-type: none"> <li>• <b>neighbor-address</b>—Address of the neighbor.</li> <li>• <b>control-word-status</b>—Whether the use of the control word has been negotiated for this virtual circuit: <b>NoCtrlWord</b> or <b>CtrlWord</b>.</li> <li>• <b>encapsulation type</b>—Type of encapsulation, represented by a number: (1) Frame Relay DLCI, (2) ATM AAL5 VCC transport, (3) ATM transparent cell transport, (4) Ethernet, (5) VLAN Ethernet, (6) HDLC, (7) PPP, (8) ATM VCC cell transport, (10) ATM VPC cell transport.</li> <li>• <b>vc-id</b>—Virtual circuit identifier.</li> <li>• <b>source</b>—Source of the advertisement: <b>Local</b> or <b>Remote</b>.</li> <li>• <b>source</b>—Source of the advertisement: <b>Local</b> or <b>Remote</b>.</li> </ul> </li> </ul> |
| <b>label stacking</b>                          | <p>(Next-to-the-last-hop routing device for MPLS only) Depth of the MPLS label stack, where the label-popping operation is needed to remove one or more labels from the top of the stack. A pair of routes is displayed, because the pop operation is performed only when the stack depth is two or more labels.</p> <ul style="list-style-type: none"> <li>• <b>S=0 route</b> indicates that a packet with an incoming label stack depth of 2 or more exits this routing device with one fewer label (the label-popping operation is performed).</li> <li>• If there is no <b>S=</b> information, the route is a normal MPLS route, which has a stack depth of 1 (the label-popping operation is not performed).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

Table 12: show route detail Output Fields (*continued*)

| Field Name                    | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[protocol, preference]</b> | <p>Protocol from which the route was learned and the preference value for the route.</p> <ul style="list-style-type: none"> <li>• <b>+</b>—A plus sign indicates the active route, which is the route installed from the routing table into the forwarding table.</li> <li>• <b>-</b>—A hyphen indicates the last active route.</li> <li>• <b>*</b>—An asterisk indicates that the route is both the active and the last active route. An asterisk before a <b>to</b> line indicates the best subpath to the route.</li> </ul> <p>In every routing metric except for the BGP <b>LocalPref</b> attribute, a lesser value is preferred. In order to use common comparison routines, Junos OS stores the 1's complement of the <b>LocalPref</b> value in the <b>Preference2</b> field. For example, if the <b>LocalPref</b> value for Route 1 is 100, the <b>Preference2</b> value is -101. If the <b>LocalPref</b> value for Route 2 is 155, the <b>Preference2</b> value is -156. Route 2 is preferred because it has a higher <b>LocalPref</b> value.</p> <p><b>Preference2</b> values are signed integers, that is, <b>Preference2</b> values can be either positive or negative values. However, Junos OS evaluates <b>Preference2</b> values as unsigned integers that are represented by positive values. Based on the <b>Preference2</b> values, Junos OS evaluates a preferred route differently in the following scenarios:</p> <ul style="list-style-type: none"> <li>• <b>Both Signed Preference2 values</b> <ul style="list-style-type: none"> <li>• Route A = -101</li> <li>• Route B = -156</li> </ul> <p>Where both the <b>Preference2</b> values are signed, Junos OS evaluates only the unsigned value of <b>Preference2</b> and Route A, which has a lower <b>Preference2</b> value is preferred.</p> </li> <li>• <b>Unsigned Preference2 values</b> <p>Now consider both unsigned <b>Preference2</b> values:</p> <ul style="list-style-type: none"> <li>• Route A = 4294967096</li> <li>• Route B = 200</li> </ul> <p>Here, Junos OS considers the lesser <b>Preference2</b> value and Route B with a <b>Preference2</b> value of 200 is preferred because it is less than 4294967096.</p> </li> <li>• <b>Combination of signed and unsigned Preference2 values</b> <p>When <b>Preference2</b> values of two routes are compared, and for one route the <b>Preference2</b> is a signed value, and for the other route it is an unsigned value, Junos OS prefers the route with the positive <b>Preference2</b> value over the negative <b>Preference2</b> value. For example, consider the following signed and unsigned <b>Preference2</b> values:</p> <ul style="list-style-type: none"> <li>• Route A = -200</li> <li>• Route B = 200</li> </ul> <p>In this case, Route B with a <b>Preference2</b> value of 200 is preferred although this value is greater than -200, because Junos OS evaluates only the unsigned value of the <b>Preference2</b> value.</p> </li> </ul> |
| <b>Level</b>                  | (IS-IS only). In IS-IS, a single AS can be divided into smaller groups called areas. Routing between areas is organized hierarchically, allowing a domain to be administratively divided into smaller areas. This organization is accomplished by configuring Level 1 and Level 2 intermediate systems. Level 1 systems route within an area. When the destination is outside an area, they route toward a Level 2 system. Level 2 intermediate systems route between areas and toward other ASs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Route Distinguisher</b>    | IP subnet augmented with a 64-bit prefix.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>PMSI</b>                   | Provider multicast service interface (MVPN routing table).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

Table 12: show route detail Output Fields (*continued*)

| Field Name                                           | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Next-hop type</b>                                 | Type of next hop. For a description of possible values for this field, see <a href="#">Table 13 on page 557</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Next-hop reference count</b>                      | Number of references made to the next hop.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Flood nexthop branches exceed maximum message</b> | Indicates that the number of flood next-hop branches exceeded the system limit of 32 branches, and only a subset of the flood next-hop branches were installed in the kernel.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Source</b>                                        | IP address of the route source.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Next hop</b>                                      | Network layer address of the directly reachable neighboring system.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>via</b>                                           | <p>Interface used to reach the next hop. If there is more than one interface available to the next hop, the name of the interface that is actually used is followed by the word <b>Selected</b>. This field can also contain the following information:</p> <ul style="list-style-type: none"> <li>• <b>Weight</b>—Value used to distinguish primary, secondary, and fast reroute backup routes. Weight information is available when MPLS label-switched path (LSP) link protection, node-link protection, or fast reroute is enabled, or when the standby state is enabled for secondary paths. A lower weight value is preferred. Among routes with the same weight value, load balancing is possible.</li> <li>• <b>Balance</b>—Balance coefficient indicating how traffic of unequal cost is distributed among next hops when a routing device is performing unequal-cost load balancing. This information is available when you enable BGP multipath load balancing.</li> </ul> |
| <b>Label-switched-path<br/>lsp-path-name</b>         | Name of the LSP used to reach the next hop.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Label operation</b>                               | MPLS label and operation occurring at this routing device. The operation can be <b>pop</b> (where a label is removed from the top of the stack), <b>push</b> (where another label is added to the label stack), or <b>swap</b> (where a label is replaced by another label).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Interface</b>                                     | (Local only) Local interface name.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Protocol next hop</b>                             | Network layer address of the remote routing device that advertised the prefix. This address is used to derive a forwarding next hop.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Indirect next hop</b>                             | Index designation used to specify the mapping between protocol next hops, tags, kernel export policy, and the forwarding next hops.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>State</b>                                         | State of the route (a route can be in more than one state). See <a href="#">Table 14 on page 559</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Local AS</b>                                      | AS number of the local routing device.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Age</b>                                           | How long the route has been known.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>AIGP</b>                                          | Accumulated interior gateway protocol (AIGP) BGP attribute.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

Table 12: show route detail Output Fields (*continued*)

| Field Name               | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Metric</b>            | Cost value of the indicated route. For routes within an AS, the cost is determined by IGP and the individual protocol metrics. For external routes, destinations, or routing domains, the cost is determined by a preference value.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>MED-plus-IGP</b>      | Metric value for BGP path selection to which the IGP cost to the next-hop destination has been added.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>TTL-Action</b>        | For MPLS LSPs, state of the TTL propagation attribute. Can be enabled or disabled for all RSVP-signaled and LDP-signaled LSPs or for specific VRF routing instances.<br><br>For sample output, see <b>show route table</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Task</b>              | Name of the protocol that has added the route.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Announcement bits</b> | The number of BGP peers or protocols to which Junos OS has announced this route, followed by the list of the recipients of the announcement. Junos OS can also announce the route to the KRT for installing the route into the Packet Forwarding Engine, to a resolve tree, a L2 VC, or even a VPN. For example, <b>n-Resolve inet</b> indicates that the specified route is used for route resolution for next hops found in the routing table.<br><br><ul style="list-style-type: none"> <li><b>n</b>—An index used by Juniper Networks customer support only.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>AS path</b>           | <p>AS path through which the route was learned. The letters at the end of the AS path indicate the path origin, providing an indication of the state of the route at the point at which the AS path originated:</p> <ul style="list-style-type: none"> <li><b>I</b>—IGP.</li> <li><b>E</b>—EGP.</li> <li><b>Recorded</b>—The AS path is recorded by the sample process (sampled).</li> <li><b>?</b>—Incomplete; typically, the AS path was aggregated.</li> </ul> <p>When AS path numbers are included in the route, the format is as follows:</p> <ul style="list-style-type: none"> <li><b>[ ]</b>—Brackets enclose the number that precedes the AS path. This number represents the number of ASs present in the AS path, when calculated as defined in RFC 4271. This value is used in the AS-path merge process, as defined in RFC 4893.</li> <li><b>[ ]</b>—If more than one AS number is configured on the routing device, or if AS path prepending is configured, brackets enclose the local AS number associated with the AS path.</li> <li><b>{ }</b>—Braces enclose AS sets, which are groups of AS numbers in which the order does not matter. A set commonly results from route aggregation. The numbers in each AS set are displayed in ascending order.</li> <li><b>( )</b>—Parentheses enclose a confederation.</li> <li><b>( [ ] )</b>—Parentheses and brackets enclose a confederation set.</li> </ul> <p><b>NOTE:</b> In Junos OS Release 10.3 and later, the AS path field displays an unrecognized attribute and associated hexadecimal value if BGP receives attribute 128 (attribute set) and you have not configured an independent domain in any routing instance.</p> |

Table 12: show route detail Output Fields (*continued*)

| Field Name              | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>validation-state</b> | <p>(BGP-learned routes) Validation status of the route:</p> <ul style="list-style-type: none"> <li>• <b>Invalid</b>—Indicates that the prefix is found, but either the corresponding AS received from the EBGP peer is not the AS that appears in the database, or the prefix length in the BGP update message is longer than the maximum length permitted in the database.</li> <li>• <b>Unknown</b>—Indicates that the prefix is not among the prefixes or prefix ranges in the database.</li> <li>• <b>Unverified</b>—Indicates that the origin of the prefix is not verified against the database. This is because the database got populated and the validation is not called for in the BGP import policy, although origin validation is enabled, or the origin validation is not enabled for the BGP peers.</li> <li>• <b>Valid</b>—Indicates that the prefix and autonomous system pair are found in the database.</li> </ul> |
| ORR Generation-ID       | Displays the optimal route reflection (ORR) generation identifier. ISIS and OSPF interior gateway protocol (IGP) updates filed whenever any of the corresponding ORR route has its metric valued changed, or if the ORR route is added or deleted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| FECs bound to route     | Point-to-multipoint root address, multicast source address, and multicast group address when multipoint LDP (M-LDP) inband signaling is configured.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Primary Upstream        | When multipoint LDP with multicast-only fast reroute (MoFRR) is configured, the primary upstream path. MoFRR transmits a multicast join message from a receiver toward a source on a primary path, while also transmitting a secondary multicast join message from the receiver toward the source on a backup path.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| RPF Nexthops            | When multipoint LDP with MoFRR is configured, the reverse-path forwarding (RPF) next-hop information. Data packets are received from both the primary path and the secondary paths. The redundant packets are discarded at topology merge points due to the RPF checks.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Label                   | Multiple MPLS labels are used to control MoFRR stream selection. Each label represents a separate route, but each references the same interface list check. Only the primary label is forwarded while all others are dropped. Multiple interfaces can receive packets using the same label.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| weight                  | Value used to distinguish MoFRR primary and backup routes. A lower weight value is preferred. Among routes with the same weight value, load balancing is possible.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| VC Label                | MPLS label assigned to the Layer 2 circuit virtual connection.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| MTU                     | Maximum transmission unit (MTU) of the Layer 2 circuit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| VLAN ID                 | VLAN identifier of the Layer 2 circuit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Prefixes bound to route | Forwarding equivalent class (FEC) bound to this route. Applicable only to routes installed by LDP.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Communities             | Community path attribute for the route. See <a href="#">Table 15 on page 561</a> for all possible values for this field.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Layer2-info: encaps     | Layer 2 encapsulation (for example, VPLS).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| control flags           | Control flags: <b>none</b> or <b>Site Down</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| mtu                     | Maximum transmission unit (MTU) information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

Table 12: show route detail Output Fields (*continued*)

| Field Name                                 | Field Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Label-Base, range</b>                   | First label in a block of labels and label block size. A remote PE routing device uses this first label when sending traffic toward the advertising PE routing device.                                                                                                                                                                                                                                                                                                               |
| <b>status vector</b>                       | Layer 2 VPN and VPLS network layer reachability information (NLRI).                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Accepted Multipath</b>                  | Current active path when BGP multipath is configured.                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Accepted LongLivedStale</b>             | The LongLivedStale flag indicates that the route was marked LLGR-stale by this router, as part of the operation of LLGR receiver mode. Either this flag or the LongLivedStaleImport flag may be displayed for a route. Neither of these flags are displayed at the same time as the Stale (ordinary GR stale) flag.                                                                                                                                                                  |
| <b>Accepted LongLivedStaleImport</b>       | <p>The LongLivedStaleImport flag indicates that the route was marked LLGR-stale when it was received from a peer, or by import policy. Either this flag or the LongLivedStale flag may be displayed for a route. Neither of these flags are displayed at the same time as the Stale (ordinary GR stale) flag.</p> <p>Accept all received BGP long-lived graceful restart (LLGR) and LLGR stale routes learned from configured neighbors and import into the inet.0 routing table</p> |
| <b>ImportAccepted LongLivedStaleImport</b> | <p>Accept all received BGP long-lived graceful restart (LLGR) and LLGR stale routes learned from configured neighbors and imported into the inet.0 routing table</p> <p>The LongLivedStaleImport flag indicates that the route was marked LLGR-stale when it was received from a peer, or by import policy.</p>                                                                                                                                                                      |
| <b>Accepted MultipathContrib</b>           | Path currently contributing to BGP multipath.                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Localpref</b>                           | Local preference value included in the route.                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Router ID</b>                           | BGP router ID as advertised by the neighbor in the open message.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Primary Routing Table</b>               | In a routing table group, the name of the primary routing table in which the route resides.                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Secondary Tables</b>                    | In a routing table group, the name of one or more secondary tables in which the route resides.                                                                                                                                                                                                                                                                                                                                                                                       |

[Table 13 on page 557](#) describes all possible values for the Next-hop Types output field.

Table 13: Next-hop Types Output Field Values

| Next-Hop Type            | Description         |
|--------------------------|---------------------|
| <b>Broadcast (bcast)</b> | Broadcast next hop. |
| <b>Deny</b>              | Deny next hop.      |
| <b>Discard</b>           | Discard next hop.   |

Table 13: Next-hop Types Output Field Values (*continued*)

| Next-Hop Type                   | Description                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Flood</b>                    | Flood next hop. Consists of components called branches, up to a maximum of 32 branches. Each flood next-hop branch sends a copy of the traffic to the forwarding interface. Used by point-to-multipoint RSVP, point-to-multipoint LDP, point-to-multipoint CCC, and multicast.                                                                                                                             |
| <b>Hold</b>                     | Next hop is waiting to be resolved into a unicast or multicast type.                                                                                                                                                                                                                                                                                                                                       |
| <b>Indexed (idxd)</b>           | Indexed next hop.                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Indirect (indr)</b>          | Used with applications that have a protocol next hop address that is remote. You are likely to see this next-hop type for internal BGP (IBGP) routes when the BGP next hop is a BGP neighbor that is not directly connected.                                                                                                                                                                               |
| <b>Interface</b>                | Used for a network address assigned to an interface. Unlike the router next hop, the interface next hop does not reference any specific node on the network.                                                                                                                                                                                                                                               |
| <b>Local (locl)</b>             | Local address on an interface. This next-hop type causes packets with this destination address to be received locally.                                                                                                                                                                                                                                                                                     |
| <b>Multicast (mcst)</b>         | Wire multicast next hop (limited to the LAN).                                                                                                                                                                                                                                                                                                                                                              |
| <b>Multicast discard (mdsc)</b> | Multicast discard.                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Multicast group (mgrp)</b>   | Multicast group member.                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Receive (recv)</b>           | Receive.                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Reject (rjct)</b>            | Discard. An ICMP unreachable message was sent.                                                                                                                                                                                                                                                                                                                                                             |
| <b>Resolve (rslv)</b>           | Resolving next hop.                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Routed multicast (mcrt)</b>  | Regular multicast next hop.                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Router</b>                   | <p>A specific node or set of nodes to which the routing device forwards packets that match the route prefix.</p> <p>To qualify as next-hop type router, the route must meet the following criteria:</p> <ul style="list-style-type: none"> <li>• Must not be a direct or local subnet for the routing device.</li> <li>• Must have a next hop that is directly connected to the routing device.</li> </ul> |
| <b>Table</b>                    | Routing table next hop.                                                                                                                                                                                                                                                                                                                                                                                    |



Table 13: Next-hop Types Output Field Values (*continued*)

| Next-Hop Type  | Description                                                                                 |
|----------------|---------------------------------------------------------------------------------------------|
| Unicast (ucst) | Unicast.                                                                                    |
| Unilist (ulst) | List of unicast next hops. A packet sent to this next hop goes to any next hop in the list. |

Table 14 on page 559 describes all possible values for the State output field. A route can be in more than one state (for example, **<Active NoReadvrt Int Ext>**).

Table 14: State Output Field Values

| Value                                 | Description                                                                                                                                                                          |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accounting                            | Route needs accounting.                                                                                                                                                              |
| Active                                | Route is active.                                                                                                                                                                     |
| Always Compare MED                    | Path with a lower multiple exit discriminator (MED) is available.                                                                                                                    |
| AS path                               | Shorter AS path is available.                                                                                                                                                        |
| Cisco Non-deterministic MED selection | Cisco nondeterministic MED is enabled, and a path with a lower MED is available.                                                                                                     |
| Clone                                 | Route is a clone.                                                                                                                                                                    |
| Cluster list length                   | Length of cluster list sent by the route reflector.                                                                                                                                  |
| Delete                                | Route has been deleted.                                                                                                                                                              |
| Ex                                    | Exterior route.                                                                                                                                                                      |
| Ext                                   | BGP route received from an external BGP neighbor.                                                                                                                                    |
| FlashAll                              | Forces all protocols to be notified of a change to any route, active or inactive, for a prefix. When not set, protocols are informed of a prefix only when the active route changes. |
| Hidden                                | Route not used because of routing policy.                                                                                                                                            |
| IfCheck                               | Route needs forwarding RPF check.                                                                                                                                                    |
| IGP metric                            | Path through next hop with lower IGP metric is available.                                                                                                                            |
| Inactive reason                       | Flags for this route, which was not selected as best for a particular destination.                                                                                                   |
| Initial                               | Route being added.                                                                                                                                                                   |

Table 14: State Output Field Values (*continued*)

| Value                                                    | Description                                                                   |
|----------------------------------------------------------|-------------------------------------------------------------------------------|
| <b>Int</b>                                               | Interior route.                                                               |
| <b>Int Ext</b>                                           | BGP route received from an internal BGP peer or a BGP confederation peer.     |
| <b>Interior &gt; Exterior &gt; Exterior via Interior</b> | Direct, static, IGP, or EBGp path is available.                               |
| <b>Local Preference</b>                                  | Path with a higher local preference value is available.                       |
| <b>Martian</b>                                           | Route is a martian (ignored because it is obviously invalid).                 |
| <b>MartianOK</b>                                         | Route exempt from martian filtering.                                          |
| <b>Next hop address</b>                                  | Path with lower metric next hop is available.                                 |
| <b>No difference</b>                                     | Path from neighbor with lower IP address is available.                        |
| <b>NoReadvrt</b>                                         | Route not to be advertised.                                                   |
| <b>NotBest</b>                                           | Route not chosen because it does not have the lowest MED.                     |
| <b>Not Best in its group</b>                             | Incoming BGP AS is not the best of a group (only one AS can be the best).     |
| <b>NotInstall</b>                                        | Route not to be installed in the forwarding table.                            |
| <b>Number of gateways</b>                                | Path with a greater number of next hops is available.                         |
| <b>Origin</b>                                            | Path with a lower origin code is available.                                   |
| <b>Pending</b>                                           | Route pending because of a hold-down configured on another route.             |
| <b>Programmed</b>                                        | Route installed programmatically by on-box or off-box applications using API. |
| <b>Release</b>                                           | Route scheduled for release.                                                  |
| <b>RIB preference</b>                                    | Route from a higher-numbered routing table is available.                      |
| <b>Route Distinguisher</b>                               | 64-bit prefix added to IP subnets to make them unique.                        |
| <b>Route Metric or MED comparison</b>                    | Route with a lower metric or MED is available.                                |
| <b>Route Preference</b>                                  | Route with lower preference value is available                                |
| <b>Router ID</b>                                         | Path through a neighbor with lower ID is available.                           |

Table 14: State Output Field Values (*continued*)

| Value                | Description                                                                                                                                                                                                                       |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Secondary</b>     | Route not a primary route.                                                                                                                                                                                                        |
| <b>Unusable path</b> | Path is not usable because of one of the following conditions: <ul style="list-style-type: none"> <li>• The route is damped.</li> <li>• The route is rejected by an import policy.</li> <li>• The route is unresolved.</li> </ul> |
| <b>Update source</b> | Last tiebreaker is the lowest IP address value.                                                                                                                                                                                   |

Table 15 on page 561 describes the possible values for the Communities output field.

Table 15: Communities Output Field Values

| Value                                                   | Description                                                                                                                                                                                                                                                                                             |
|---------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>area-number</i>                                      | 4 bytes, encoding a 32-bit area number. For AS-external routes, the value is <b>0</b> . A nonzero value identifies the route as internal to the OSPF domain, and as within the identified area. Area numbers are relative to a particular OSPF domain.                                                  |
| <b>bandwidth: local AS number:link-bandwidth-number</b> | Link-bandwidth community value used for unequal-cost load balancing. When BGP has several candidate paths available for multipath purposes, it does not perform unequal-cost load balancing according to the link-bandwidth community unless all candidate paths have this attribute.                   |
| <b>domain-id</b>                                        | Unique configurable number that identifies the OSPF domain.                                                                                                                                                                                                                                             |
| <b>domain-id-vendor</b>                                 | Unique configurable number that further identifies the OSPF domain.                                                                                                                                                                                                                                     |
| <i>link-bandwidth-number</i>                            | Link-bandwidth number: from <b>0</b> through <b>4,294,967,295</b> (bytes per second).                                                                                                                                                                                                                   |
| <i>local AS number</i>                                  | Local AS number: from <b>1</b> through <b>65,535</b> .                                                                                                                                                                                                                                                  |
| <i>options</i>                                          | 1 byte. Currently this is only used if the route type is <b>5</b> or <b>7</b> . Setting the least significant bit in the field indicates that the route carries a type 2 metric.                                                                                                                        |
| <b>origin</b>                                           | (Used with VPNs) Identifies where the route came from.                                                                                                                                                                                                                                                  |
| <i>ospf-route-type</i>                                  | 1 byte, encoded as <b>1</b> or <b>2</b> for intra-area routes (depending on whether the route came from a type 1 or a type 2 LSA); <b>3</b> for summary routes; <b>5</b> for external routes (area number must be <b>0</b> ); <b>7</b> for NSSA routes; or <b>129</b> for sham link endpoint addresses. |
| <b>route-type-vendor</b>                                | Displays the area number, OSPF route type, and option of the route. This is configured using the BGP extended community attribute <b>0x8000</b> . The format is <i>area-number:ospf-route-type:options</i> .                                                                                            |
| <b>rte-type</b>                                         | Displays the area number, OSPF route type, and option of the route. This is configured using the BGP extended community attribute <b>0x0306</b> . The format is <i>area-number:ospf-route-type:options</i> .                                                                                            |

Table 15: Communities Output Field Values (*continued*)

| Value                                | Description                                                                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>target</b>                        | Defines which VPN the route participates in; <b>target</b> has the format <b>32-bit IP address:16-bit number</b> . For example, 10.19.0.0:100.    |
| <b>unknown IANA</b>                  | Incoming IANA codes with a value between 0x1 and 0x7fff. This code of the BGP extended community attribute is accepted, but it is not recognized. |
| <b>unknown OSPF vendor community</b> | Incoming IANA codes with a value above 0x8000. This code of the BGP extended community attribute is accepted, but it is not recognized.           |

## Sample Output

### show route detail

```

user@host> show route detail

inet.0: 22 destinations, 23 routes (21 active, 0 holddown, 1 hidden)
10.10.0.0/16 (1 entry, 1 announced)
    *Static Preference: 5
        Next-hop reference count: 29
        Next hop: 192.168.71.254 via fxp0.0, selected
        State: <Active NoReadvrt Int Ext>
        Local AS: 69
        Age: 1:31:43
        Task: RT
        Announcement bits (2): 0-KRT 3-Resolve tree 2
        AS path: I

10.31.1.0/30 (2 entries, 1 announced)
    *Direct Preference: 0
        Next hop type: Interface
        Next-hop reference count: 2
        Next hop: via so-0/3/0.0, selected
        State: <Active Int>
        Local AS: 69
        Age: 1:30:17
        Task: IF
        Announcement bits (1): 3-Resolve tree 2
        AS path: I
    OSPF Preference: 10
        Next-hop reference count: 1
        Next hop: via so-0/3/0.0, selected
        State: <Int>
        Inactive reason: Route Preference
        Local AS: 69
        Age: 1:30:17 Metric: 1
        ORR Generation-ID: 1
    Area: 0.0.0.0
        Task: OSPF
        AS path: I

10.31.1.1/32 (1 entry, 1 announced)
    *Local Preference: 0
        Next hop type: Local
        Next-hop reference count: 7
        Interface: so-0/3/0.0

```

```

        State: <Active NoReadvrt Int>
        Local AS: 69
        Age: 1:30:20
        Task: IF
        Announcement bits (1): 3-Resolve tree 2
        AS path: I

...

10.31.2.0/30 (1 entry, 1 announced)
  *OSPF Preference: 10
    Next-hop reference count: 9
    Next hop: via so-0/3/0.0
    Next hop: 10.31.1.6 via ge-3/1/0.0, selected
    State: <Active Int>
    Local AS: 69
    Age: 1:29:56 Metric: 2
    Area: 0.0.0.0
    ORR Generation-ID: 1
  Task: OSPF
    Announcement bits (2): 0-KRT 3-Resolve tree 2
    AS path: I

...

172.16.233.2/32 (1 entry, 1 announced)
  *PIM Preference: 0
    Next-hop reference count: 18
    State: <Active NoReadvrt Int>
    Local AS: 69
    Age: 1:31:45
    Task: PIM Recv
    Announcement bits (2): 0-KRT 3-Resolve tree 2
    AS path: I

...

172.16.233.22/32 (1 entry, 1 announced)
  *IGMP Preference: 0
    Next-hop reference count: 18
    State: <Active NoReadvrt Int>
    Local AS: 69
    Age: 1:31:43
    Task: IGMP
    Announcement bits (2): 0-KRT 3-Resolve tree 2
    AS path: I

inet.3: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)

10.255.70.103/32 (1 entry, 1 announced)
  State: <FlashAll>
  *RSVP Preference: 7
    Next-hop reference count: 6
    Next hop: 10.31.1.6 via ge-3/1/0.0 weight 0x1, selected
    Label-switched-path green-r1-r3
    Label operation: Push 100096
    State: <Active Int>
    Local AS: 69
    Age: 1:25:49 Metric: 2
    Task: RSVP
    Announcement bits (2): 1-Resolve tree 1 2-Resolve tree 2

```

```

AS path: I

10.255.71.238/32 (1 entry, 1 announced)
  State: <FlashAll>
  *RSVP   Preference: 7
          Next-hop reference count: 6
          Next hop: via so-0/3/0.0 weight 0x1, selected
          Label-switched-path green-r1-r2
          State: <Active Int>
          Local AS: 69
          Age: 1:25:49   Metric: 1
          Task: RSVP
          Announcement bits (2): 1-Resolve tree 1 2-Resolve tree 2
          AS path: I

private__inet.0: 2 destinations, 3 routes (2 active, 0 holddown, 0 hidden)

iso.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

47.0005.80ff.f800.0000.0108.0001.0102.5507.1052/152 (1 entry, 0 announced)
  *Direct Preference: 0
          Next hop type: Interface
          Next-hop reference count: 1
          Next hop: via lo0.0, selected
          State: <Active Int>
          Local AS: 69
          Age: 1:31:44
          Task: IF
          AS path: I

mpls.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
0 (1 entry, 1 announced)
  *MPLS   Preference: 0
          Next hop type: Receive
          Next-hop reference count: 6
          State: <Active Int>
          Local AS: 69
          Age: 1:31:45   Metric: 1
          Task: MPLS
          Announcement bits (1): 0-KRT
          AS path: I

...

mpls.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)

299840 (1 entry, 1 announced)
TSI:
KRT in-kernel 299840 /52 -> {indirect(1048575)}
  *RSVP   Preference: 7/2
          Next hop type: Flood
          Address: 0x9174a30
          Next-hop reference count: 4
          Next hop type: Router, Next hop index: 798
          Address: 0x9174c28
          Next-hop reference count: 2
          Next hop: 172.16.0.2 via lt-1/2/0.9 weight 0x1
          Label-switched-path R2-to-R4-2p2mp
          Label operation: Pop
          Next hop type: Router, Next hop index: 1048574
          Address: 0x92544f0

```

```

Next-hop reference count: 2
Next hop: 172.16.0.2 via lt-1/2/0.7 weight 0x1
Label-switched-path R2-to-R200-p2mp
Label operation: Pop
Next hop: 172.16.0.2 via lt-1/2/0.5 weight 0x8001
Label operation: Pop
State: <Active Int>
Age: 1:29      Metric: 1
Task: RSVP
Announcement bits (1): 0-KRT
AS path: I...

800010 (1 entry, 1 announced)
  *VPLS Preference: 7
    Next-hop reference count: 2
    Next hop: via vt-3/2/0.32769, selected
    Label operation: Pop
    State: <Active Int>
    Age: 1:29:30
    Task: Common L2 VC
    Announcement bits (1): 0-KRT
    AS path: I

vt-3/2/0.32769 (1 entry, 1 announced)
  *VPLS Preference: 7
    Next-hop reference count: 2
    Next hop: 10.31.1.6 via ge-3/1/0.0 weight 0x1, selected
    Label-switched-path green-r1-r3
    Label operation: Push 800012, Push 100096(top)
    Protocol next hop: 10.255.70.103
    Push 800012
    Indirect next hop: 87272e4 1048574
    State: <Active Int>
    Age: 1:29:30      Metric2: 2
    Task: Common L2 VC
    Announcement bits (2): 0-KRT 1-Common L2 VC
    AS path: I
    Communities: target:11111:1 Layer2-info: encaps:VPLS,
    control flags:, mtu: 0

inet6.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)

abcd::10:255:71:52/128 (1 entry, 0 announced)
  *Direct Preference: 0
    Next hop type: Interface
    Next-hop reference count: 1
    Next hop: via lo0.0, selected
    State: <Active Int>
    Local AS: 69
    Age: 1:31:44
    Task: IF
    AS path: I

fe80::280:42ff:fe10:f179/128 (1 entry, 0 announced)
  *Direct Preference: 0
    Next hop type: Interface
    Next-hop reference count: 1
    Next hop: via lo0.0, selected
    State: <Active NoReadvrt Int>
    Local AS: 69
    Age: 1:31:44

```

```
Task: IF
AS path: I

ff02::2/128 (1 entry, 1 announced)
  *PIM Preference: 0
        Next-hop reference count: 18
        State: <Active NoReadvrt Int>
        Local AS: 69
        Age: 1:31:45
        Task: PIM Recv6
        Announcement bits (1): 0-KRT
        AS path: I

ff02::d/128 (1 entry, 1 announced)
  *PIM Preference: 0
        Next-hop reference count: 18
        State: <Active NoReadvrt Int>
        Local AS: 69
        Age: 1:31:45
        Task: PIM Recv6
        Announcement bits (1): 0-KRT
        AS path: I

ff02::16/128 (1 entry, 1 announced)
  *MLD Preference: 0
        Next-hop reference count: 18
        State: <Active NoReadvrt Int>
        Local AS: 69
        Age: 1:31:43
        Task: MLD
        Announcement bits (1): 0-KRT
        AS path: I

private.inet6.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

fe80::280:42ff:fe10:f179/128 (1 entry, 0 announced)
  *Direct Preference: 0
        Next hop type: Interface
        Next-hop reference count: 1
        Next hop: via lo0.16385, selected
        State: <Active NoReadvrt Int>
        Age: 1:31:44
        Task: IF
        AS path: I

green.l2vpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)

10.255.70.103:1:3:1/96 (1 entry, 1 announced)
  *BGP Preference: 170/-101
        Route Distinguisher: 10.255.70.103:1
        Next-hop reference count: 7
        Source: 10.255.70.103
        Protocol next hop: 10.255.70.103
        Indirect next hop: 2 no-forward
        State: <Secondary Active Int Ext>
        Local AS: 69 Peer AS: 69
        Age: 1:25:49 Metric2: 1
        AIGP 210
        Task: BGP_69.10.255.70.103+179
        Announcement bits (1): 0-green-l2vpn
        AS path: I
```



```

Communities: target:11111:1 Layer2-info: encaps:VPLS,
control flags:, mtu: 0
Label-base: 800008, range: 8
Localpref: 100
Router ID: 10.255.70.103
Primary Routing Table bgp.l2vpn.0

10.255.71.52:1:1:1/96 (1 entry, 1 announced)
  *L2VPN Preference: 170/-1
    Next-hop reference count: 5
    Protocol next hop: 10.255.71.52
    Indirect next hop: 0 -
    State: <Active Int Ext>
    Age: 1:31:40 Metric2: 1
    Task: green-l2vpn
    Announcement bits (1): 1-BGP.0.0.0.0+179
    AS path: I
    Communities: Layer2-info: encaps:VPLS, control flags:Site-Down,
    mtu: 0
    Label-base: 800016, range: 8, status-vector: 0x9F

10.255.71.52:1:5:1/96 (1 entry, 1 announced)
  *L2VPN Preference: 170/-101
    Next-hop reference count: 5
    Protocol next hop: 10.255.71.52
    Indirect next hop: 0 -
    State: <Active Int Ext>
    Age: 1:31:40 Metric2: 1
    Task: green-l2vpn
    Announcement bits (1): 1-BGP.0.0.0.0+179
    AS path: I
    Communities: Layer2-info: encaps:VPLS, control flags:, mtu: 0
    Label-base: 800008, range: 8, status-vector: 0x9F

...

l2circuit.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
10.245.255.63:CtrlWord:4:3:Local/96 (1 entry, 1 announced)
  *L2CKT Preference: 7
    Next hop: via so-1/1/2.0 weight 1, selected
    Label-switched-path my-lsp
    Label operation: Push 100000[0]
    Protocol next hop: 10.245.255.63 Indirect next hop: 86af000 296
    State: <Active Int>
    Local AS: 99
    Age: 10:21
    Task: l2 circuit
    Announcement bits (1): 0-LDP
    AS path: I
    VC Label 100000, MTU 1500, VLAN ID 512

inet.0: 45 destinations, 47 routes (44 active, 0 holddown, 1 hidden)
1.1.1.3/32 (1 entry, 1 announced)
  *IS-IS Preference: 18
    Level: 2
    Next hop type: Router, Next hop index: 580
    Address: 0x9db6ed0
    Next-hop reference count: 8
    Next hop: 10.1.1.6 via lt-1/0/10.5, selected
    Session Id: 0x18a
    State: <Active Int>

```

```

Local AS:      2
Age: 1:32      Metric: 10
Validation State: unverified
ORR Generation-ID: 1
Task: IS-IS
Announcement bits (3): 0-KRT 5-Resolve tree 4 6-Resolve_IGP_FRR
task
AS path: I

inet.0: 61 destinations, 77 routes (61 active, 1 holddown, 0 hidden)
1.1.1.1/32 (2 entries, 1 announced)
  *OSPF Preference: 10
    Next hop type: Router, Next hop index: 673
    Address: 0xc008830
    Next-hop reference count: 3
    Next hop: 10.1.1.1 via ge-0/0/2.0, selected
    Session Id: 0x1b7
    State: <Active Int>
    Local AS:      1
    Age: 3:06:59    Metric: 100
    Validation State: unverified
    ORR Generation-ID: 1
    Area: 0.0.0.0
    Task: OSPF
    Announcement bits (2): 1-KRT 9-Resolve tree 2
    AS path: I

```

#### show route detail (with BGP Multipath)

```

user@host> show route detail

10.1.1.8/30 (2 entries, 1 announced)
  *BGP Preference: 170/-101
    Next hop type: Router, Next hop index: 262142
    Address: 0x901a010
    Next-hop reference count: 2
    Source: 10.1.1.2
    Next hop: 10.1.1.2 via ge-0/3/0.1, selected
    Next hop: 10.1.1.6 via ge-0/3/0.5
    State: <Active Ext>
    Local AS:      1 Peer AS:      2
    Age: 5:04:43
    Validation State: unverified
    Task: BGP_2.10.1.1.2+59955
    Announcement bits (1): 0-KRT
    AS path: 2 I
    Accepted Multipath
    Localpref: 100
    Router ID: 172.16.1.2
  BGP Preference: 170/-101
    Next hop type: Router, Next hop index: 678
    Address: 0x8f97520
    Next-hop reference count: 9
    Source: 10.1.1.6
    Next hop: 10.1.1.6 via ge-0/3/0.5, selected
    State: <NotBest Ext>
    Inactive reason: Not Best in its group - Active preferred
    Local AS:      1 Peer AS:      2
    Age: 5:04:43
    Validation State: unverified
    Task: BGP_2.10.1.1.6+58198

```

```

AS path: 2 I
Accepted MultipathContrib
Localpref: 100
Router ID: 172.16.1.3

```

### show route label detail (Multipoint LDP Inband Signaling for Point-to-Multipoint LSPs)

```

user@host> show route label 299872 detail
mpls.0: 13 destinations, 13 routes (13 active, 0 holddown, 0 hidden)
299872 (1 entry, 1 announced)
  *LDP    Preference: 9
           Next hop type: Flood
           Next-hop reference count: 3
           Address: 0x9097d90
           Next hop: via vt-0/1/0.1
           Next-hop index: 661
           Label operation: Pop
           Address: 0x9172130
           Next hop: via so-0/0/3.0
           Next-hop index: 654
           Label operation: Swap 299872
           State: **Active Int>
           Local AS: 1001
           Age: 8:20      Metric: 1
           Task: LDP
           Announcement bits (1): 0-KRT
           AS path: I
           FECs bound to route: P2MP root-addr 10.255.72.166, grp 232.1.1.1,
src 192.168.142.2

```

### show route label detail (Multipoint LDP with Multicast-Only Fast Reroute)

```

user@host> show route label 301568 detail

mpls.0: 18 destinations, 18 routes (18 active, 0 holddown, 0 hidden)
301568 (1 entry, 1 announced)
  *LDP    Preference: 9
           Next hop type: Flood
           Address: 0x2735208
           Next-hop reference count: 3
           Next hop type: Router, Next hop index: 1397
           Address: 0x2735d2c
           Next-hop reference count: 3
           Next hop: 1.3.8.2 via ge-1/2/22.0
           Label operation: Pop
           Load balance label: None;
           Next hop type: Router, Next hop index: 1395
           Address: 0x2736290
           Next-hop reference count: 3
           Next hop: 1.3.4.2 via ge-1/2/18.0
           Label operation: Pop
           Load balance label: None;
           State: <Active Int AckRequest MulticastRPF>
           Local AS: 10
           Age: 54:05      Metric: 1
           Validation State: unverified
           Task: LDP
           Announcement bits (1): 0-KRT
           AS path: I
           FECs bound to route: P2MP root-addr 172.16.1.1, grp: 232.1.1.1,
src: 192.168.219.11

```

```
Primary Upstream : 172.16.1.3:0--172.16.1.2:0
  RPF Nexthops :
    ge-1/2/15.0, 1.2.94.1, Label: 301568, weight: 0x1
    ge-1/2/14.0, 1.2.3.1, Label: 301568, weight: 0x1
Backup Upstream : 172.16.1.3:0--172.16.1.6:0
  RPF Nexthops :
    ge-1/2/20.0, 1.2.96.1, Label: 301584, weight: 0xfffe
    ge-1/2/19.0, 1.3.6.1, Label: 301584, weight: 0xfffe
```