

Juniper Extension Toolkit API Guide

Published
2021-12-14

Juniper Networks, Inc.
1133 Innovation Way
Sunnyvale, California 94089
USA
408-745-2000
www.juniper.net

Juniper Networks, the Juniper Networks logo, Juniper, and Junos are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Juniper Extension Toolkit API Guide

Copyright © 2021 Juniper Networks, Inc. All rights reserved.

The information in this document is current as of the date on the title page.

YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <https://support.juniper.net/support/eula/>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

Table of Contents

About This Guide | iv

1

JET APIs: Release 18.1 and Later

Overview of JET APIs | 2

JET Notification API Overview | 4

2

JET APIs: Before Release 18.1

JET APIs Reference | 9

About This Guide

Use this guide to learn more about Juniper Extension Toolkit (JET) APIs. For more information about developing JET applications, see the [Juniper Extension Toolkit Developer Guide](#).

1

CHAPTER

JET APIs: Release 18.1 and Later

[Overview of JET APIs | 2](#)

[JET Notification API Overview | 4](#)

Overview of JET APIs

IN THIS SECTION

- [Notification API | 2](#)
- [Base Types APIs | 2](#)
- [Service APIs | 2](#)

JET provides APIs that extend the functionality of Junos OS. These APIs fall into three main categories: the notification API, base type APIs, and service APIs.

Notification API

The notification API provides interfaces that allow you to subscribe to events and designate a callback function to receive events when they occur. See ["JET Notification API Overview" on page 4](#) for more information about this API.

Base Types APIs

If you are using JET Release 18.1 or later, go to [Juniper EngNet](#) for complete documentation of base types APIs. If you are using a JET release before 18.1, go to ["JET APIs Reference" on page 9](#).

- jnx Common Address API
- jnx Common Base Types API

Service APIs

Service APIs provide interfaces to access the control plane on the device and a management interface to run operational and configuration commands. If you are using JET Release 18.1 or later, go to [Juniper EngNet](#) for complete documentation of services APIs. If you are using a JET release before 18.1, go to ["JET APIs Reference" on page 9](#).

Routing

- BFD Service APIs
- BGP Route Service API
- ECMP Tracer Flow Monitoring APIs
- Flexible Tunnel Profile
- Flexible Tunnel Service
- gRIBi
- MPLS Service API
- PRPD Common API
- PRPD Service API
- RIB Service API
- Routing Interface Service API

Firewall

Firewall Service API

Interfaces

Interfaces Service API

Infrastructure

Infrastructure Service APIs

Management

- JNX Management Service API
- JNX Authentication Service API
- JNX Registration Service API
- Versioning Service APIs

JET Notification API Overview

IN THIS SECTION

- [JSON Format of JET Notification Messages | 4](#)
- [Subscribing to Events | 5](#)
- [Programming JET Notification for Non-Python Languages | 7](#)

The JET Notification API allows you to subscribe to events and designate a callback function to receive events when they occur. These Python interfaces provide an interface to the MQTT notification system that, for languages other than Python, must be handled outside of JET (see "[Programming JET Notification for Non-Python Languages](#)" on page 7). For details about MQTT and Python, see <https://mosquitto.org/>.

JSON Format of JET Notification Messages

JET notification is delivered in JSON format. The JSON message has two parts: the header and the attributes. The header is common for all events. It contains the event ID, hostname, time, severity, and facility of the event. The attributes contain information about the event and vary depending event's topic name.

All kernel rtsock events will have `info` as the severity and `KERNEL` as the facility. For syslog events, the severity and facility will be same as that of the Junos OS syslog messages.

The following is an example event JSON file.

```
{
  "jet-event": {
    "event-id": "KERNEL_EVENT_IFD_ADD",
    "hostname": "mydevice",
    "time": "2016-01-07",
    "severity": "info",
    "facility": "KERNEL",
    "attributes": {
      "name": "ge-0/0/0",
      "snmp-id": 520,
    }
  }
}
```



```

    "flags": 8
  }
}

```

See [Package JET Applications](#) for more information about JSON.

Subscribing to Events

Applications developed using JET can subscribe to the events listed in [Table 1 on page 5](#). A *topic* is an endpoint to which the clients connect. A topic acts as the central distribution hub for publishing and subscribing messages. Topics are simple, hierarchical strings, encoded in UTF-8, delimited by a forward slash.

Table 1: Junos Event Topics

Events	Topic	Event Information Returned
Physical Interface (IFD)	<ul style="list-style-type: none"> • <code>/junos/events/kernel/interfaces/ifd/add/<i>ifdname</i></code> • <code>/junos/events/kernel/interfaces/ifd/change/<i>ifdname</i></code> • <code>/junos/events/kernel/interfaces/ifd/delete/<i>ifdname</i></code> 	name, snmp-id, flags
Logical Interface (IFL)	<ul style="list-style-type: none"> • <code>/junos/events/kernel/interfaces/ifl/add/<i>iflname</i></code> • <code>/junos/events/kernel/interfaces/ifl/change/<i>iflname</i></code> • <code>/junos/events/kernel/interfaces/ifl/delete/<i>iflname</i></code> 	name, subunit, snmp-id, flags
Family (IFF)	<ul style="list-style-type: none"> • <code>/junos/events/kernel/interfaces/iff/add/<i>iflname</i>/<i>family-type</i></code> • <code>/junos/events/kernel/interfaces/iff/change/<i>iflname</i>/<i>family-type</i></code> • <code>/junos/events/kernel/interfaces/iff/delete/<i>iflname</i>/<i>family-type</i></code> 	name, subunit, family, table-name, flags

Table 1: Junos Event Topics (*Continued*)

Events	Topic	Event Information Returned
Address	<ul style="list-style-type: none"> • <i>/junos/events/kernel/interfaces/ifa/add/ iflname/ family-type/ address</i> • <i>/junos/events/kernel/interfaces/ifa/change/ iflname/ family-type/ address</i> • <i>/junos/events/kernel/interfaces/ifa/delete/ iflname/ family-type/ address</i> 	name, subunit, family, local-address, destination-address, broadcast-address, flags
Firewall	<ul style="list-style-type: none"> • <i>/junos/events/kernel/firewall/filter/add/ filtername</i> • <i>/junos/events/kernel/firewall/filter/change/ filtername</i> • <i>/junos/events/kernel/firewall/filter/delete/ filtername</i> 	name, version, client-id, filter-type, protocol, interface-name, flags
Route	<ul style="list-style-type: none"> • <i>/junos/events/kernel/route/add/ family/ prefix-with-length</i> • <i>/junos/events/kernel/route/change/ family/ prefix-with-length</i> • <i>/junos/events/kernel/route/delete/ family/ prefix-with-length</i> 	table-name, logical-router-name, address-family, route-type, route-prefix, arrayof(nextthop-address), flags
Route-table	<ul style="list-style-type: none"> • <i>/junos/events/kernel/route-table/add/ tablename/ lname</i> • <i>/junos/events/kernel/route-table/change/ tablename/ lname</i> • <i>/junos/events/kernel/route-table/delete/ tablename/ lname</i> 	name, logical-router-name, address-family, flags
Syslog	<i>/junos/events/syslog/ event-id</i>	arrayof(attribute-value pairs)

Programming JET Notification for Non-Python Languages

Many of high-level languages have an MQTT library available. A JET application can use the corresponding library to connect to the MQTT broker running on Junos OS and subscribe to events. For example, here is a sample JAVA program connecting to an MQTT broker and subscribing to events:

[Example MQTT Messaging in Java](#).

For details on example MQTT libraries for different languages, see [Table 2 on page 7](#).

Table 2: MQTT Libraries by Language

Language Name	License Link
C, Mosquitto	FreeBSD
C++, Mosquitto	FreeBSD
Python, Mosquitto	FreeBSD
Ruby, Ruby-mqtt	MIT License
Java, Eclipse Paho Java	Eclipse Public License
Go, Eclipse Paho Go	Eclipse Public License
C#, MqttDotNet	Custom License

RELATED DOCUMENTATION

[Notification API](#)

2

CHAPTER

JET APIs: Before Release 18.1

JET APIs Reference | 9

JET APIs Reference

IN THIS SECTION

- [JET Release 18.3 | 9](#)
- [JET Release 18.2 | 10](#)
- [JET Release 18.1 | 10](#)
- [JET Release 17.4 | 10](#)
- [JET Release 17.3 | 11](#)
- [JET Release 17.2 | 11](#)
- [JET Release 17.1 | 12](#)
- [JET Release 16.2 | 12](#)

If you are using JET Release 18.1 or later, see ["JET Notification API Overview" on page 4](#) for information about the notification API and [Juniper EngNet](#), the Juniper Engineering Network website, for JET API documentation.

Use this reference guide to view documentation for JET APIs before JET Release 18.4.

JET Release 18.3

Authentication Service API	BGP Service API	Interfaces Service API
Firewall Service API	jnx Address API	jnx Base Types API
Management Service API	MPLS Service API	Notification API
PRPD Common API	PRPD Service API	Registration Service API
RIB Service API	Routing Interface Service API	

JET Release 18.2

Authentication Service API	BGP Service API	Interfaces Service API
Firewall Service API	jnx Address API	jnx Base Types API
Management Service API	MPLS Service API	Notification API
PRPD Common API	PRPD Service API	Registration Service API
RIB Service API	Routing Interface Service API	

JET Release 18.1

Authentication Service API	BGP Service API	Interfaces Service API
Firewall Service API	jnx Address API	jnx Base Types API
Management Service API	MPLS Service API	Notification API
PRPD Common API	PRPD Service API	Registration Service API
RIB Service API	Routing Interface Service API	

JET Release 17.4

Authentication Service API	BGP Service API	Class of Service API
----------------------------	-----------------	----------------------

Interfaces Service API	Firewall Service API	jnx Address API
jnx Base Types API	Management Service API	MPLS Service API
Notification API	PRPD Common API	PRPD Service API
Registration Service API	RIB Service API	Routing Interface Service API

JET Release 17.3

Authentication Service API	BGP Service API	Class of Service API
Interfaces Service API	Firewall Service API	jnx Address API
jnx Base Types API	Management Service API	MPLS Service API
Notification API	PRPD Common API	PRPD Service API
Registration Service API	RIB Service API	Routing Interface Service API

JET Release 17.2

Authentication Service API	BGP Service API	Class of Service API
Interfaces Service API	Firewall Service API	jnx Address API
Manageability RPC Service API	MPLS Service API	Notification API

PRPD Common API	PRPD Service API	Registration Service API
RIB Service API		

JET Release 17.1

Authentication Service API	BGP Service API	Class of Service API
Interfaces Service API	Firewall Service API	jnx Address API
Manageability RPC Service API	MPLS Service API	Notification API
PRPD Common API	PRPD Service API	Registration Service API
RIB Service API		

JET Release 16.2

Authentication Service API	BGP Service API	DCD Service API
Firewall Service API	jnx Address API	Manageability RPC Service API
Notification API	PRPD Common API	PRPD Service API
Registration Service API		