

Junos® OS

Layer 2 VPNs and VPLS User Guide for Routing Devices

Published
2022-09-13

Juniper Networks, Inc.
1133 Innovation Way
Sunnyvale, California 94089
USA
408-745-2000
www.juniper.net

Juniper Networks, the Juniper Networks logo, Juniper, and Junos are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Junos® OS Layer 2 VPNs and VPLS User Guide for Routing Devices
Copyright © 2022 Juniper Networks, Inc. All rights reserved.

The information in this document is current as of the date on the title page.

YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <https://support.juniper.net/support/eula/>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

Table of Contents

1

[About This Guide | xxvii](#)

Common Configuration for All VPNs

[VPNs Overview | 2](#)

[VPLS | 2](#)

[Types of VPNs | 2](#)

[VPNs and Logical Systems | 6](#)

[Layer 2 VPNs | 7](#)

[Routers in a VPN | 8](#)

Assigning Routing Instances to VPNs | 9

[Configuring Routing Instances on PE Routers in VPNs | 9](#)

[Configuring Virtual-Router Routing Instances in VPNs | 15](#)

[Configuring Path MTU Checks for VPN Routing Instances | 18](#)

Distributing Routes in VPNs | 20

[Enabling Routing Information Exchange for VPNs | 20](#)

[Configuring IBGP Sessions Between PE Routers in VPNs | 20](#)

[Configuring Aggregate Labels for VPNs | 22](#)

[Configuring a Signaling Protocol and LSPs for VPNs | 23](#)

[Configuring Policies for the VRF Table on PE Routers in VPNs | 28](#)

[Configuring the Route Origin for VPNs | 36](#)

Distributing VPN Routes with Target Filtering | 42

[Configuring BGP Route Target Filtering for VPNs | 42](#)

[Example: BGP Route Target Filtering for VPNs | 44](#)

[Example: Configuring BGP Route Target Filtering for VPNs | 47](#)

[Configuring Static Route Target Filtering for VPNs | 59](#)

Understanding Proxy BGP Route Target Filtering for VPNs | 60

Example: Configuring Proxy BGP Route Target Filtering for VPNs | 61

Requirements | 61

Overview | 62

Configuration | 64

Verification | 82

Example: Configuring an Export Policy for BGP Route Target Filtering for VPNs | 83

Requirements | 84

Overview | 84

Configuration | 86

Verification | 105

Reducing Network Resource Use with Static Route Target Filtering for VPNs | 107

Configuring Forwarding Options for VPNs | 109

Chained Composite Next Hops for VPNs and Layer 2 Circuits | 109

Example: Configuring Chained Composite Next Hops for Direct PE-PE Connections in VPNs | 110

Requirements | 111

Overview and Topology | 111

Configuration | 111

Configuring Graceful Restart for VPNs | 119

VPN Graceful Restart | 119

Configuring Graceful Restart for VPNs | 120

Enabling Unicast Reverse-Path Forwarding Check for VPNs | 123

Understanding and Preventing Unknown Unicast Forwarding | 124

Verifying That Unknown Unicast Packets Are Forwarded to a Single Interface | 124

Configuring Unknown Unicast Forwarding (ELS) | 126

Configuring Unknown Unicast Forwarding on EX4300 Switches | 126

Configuring Unknown Unicast Forwarding on EX9200 Switches | 127

Verifying That Unknown Unicast Packets Are Forwarded to a Trunk Interface | 129

Configuring Unknown Unicast Forwarding (CLI Procedure) | 130

Configuring Class of Service for VPNs | 132

VPNs and Class of Service | 132

Rewriting Class of Service Markers and VPNs | 132

Pinging VPNs | 133

Pinging VPNs, VPLS, and Layer 2 Circuits | 133

Setting the Forwarding Class of the Ping Packets | 134

Pinging a VPLS Routing Instance | 134

Pinging a Layer 2 VPN | 135

Pinging a Layer 3 VPN | 136

Pinging a Layer 2 Circuit | 136

Pinging Customer Edge Device IP Address | 136

Common Configuration for Layer 2 VPNs and VPLS

Overview | 143

Understanding Layer 2 VPNs | 143

Layer 2 VPN Applications | 145

Supported Layer 2 VPN Standards | 145

Layer 2 VPNs Configuration Overview | 147

Introduction to Configuring Layer 2 VPNs | 147

Configuring the Local Site on PE Routers in Layer 2 VPNs | 149

Layer 2 VPN Configuration Example | 156

Example: Configure MPLS-Based Layer 2 VPNs | 179

Requirements | 180

Overview and Topology | 181

Quick Configurations | 182

Configure the Local PE (PE1) Device for a MPLS-Based Layer 2 VPN | 185

Configure the Remote PE (PE2) Device for a MPLS-Based Layer 2 VPN | 193

Verification | 199

Transmitting Nonstandard BPDUs in Layer 2 VPNs and VPLS | 208

Configuring Layer 2 Interfaces | 209

Configuring CCC Encapsulation for Layer 2 VPNs | 209

Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits | 210

Configuring the MTU for Layer 2 Interfaces | 212

Disabling the Control Word for Layer 2 VPNs | 214

Configuring Path Selection for Layer 2 VPNs and VPLS | 215

Understanding BGP Path Selection | 215

Enabling BGP Path Selection for Layer 2 VPNs and VPLS | 220

Creating Backup Connections with Redundant Pseudowires | 223

Redundant Pseudowires for Layer 2 Circuits and VPLS | 223

Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS | 226

Configuring Class of Service for Layer 2 VPNs | 229

Configuring Traffic Policing in Layer 2 VPNs | 229

Monitoring Layer 2 VPNs | 231

Configuring BFD for Layer 2 VPN and VPLS | 231

BFD Support for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 233

Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 234

Connectivity Fault Management Support for EVPN and Layer 2 VPN Overview | 235

Configuring a MEP to Generate and Respond to CFM Protocol Messages | 238

Configuring a Maintenance Association End Point (MEP) | 239

Configuring a remote Maintenance Association End Point (MEP) | 241

3

Configuring Group VPNs

Configuring Group VPNv2 | 244

Group VPNv2 Overview | 244

Configuring Group VPNs in Group VPNv2 on Routing Devices | 270

Group VPN on AMS interfaces | 274

Use Case for Configuring Group VPNv2 | 275

Example: Configuring Group VPNs in Group VPNv2 on Routing Devices | 276

Requirements | 276

Overview | 277

4

- Configuration | 279
- Verification | 291
- Troubleshooting | 294

Configuring Public Key Infrastructure

Configuring Digital Certificate Validation | 300

Understanding Digital Certificate Validation | 300

Example: Improving Digital Certificate Validation by Configuring Policy OIDs on an MX Series Device | 307

- Requirements | 307
- Overview | 308
- Configuration | 308
- Verification | 309

Configuring a Device for Certificate Chains | 313

IKE Authentication (Certificate-Based Authentication) | 313

Example: Configuring a Device for Peer Certificate Chain Validation | 316

- Requirements | 316
- Overview | 317
- Configuration | 318
- Verification | 325
- IKE and IPsec SA Failure for a Revoked Certificate | 327

Managing Certificate Revocation | 329

Understanding Online Certificate Status Protocol and Certificate Revocation Lists | 329

Example: Improving Security by Configuring OCSP for Certificate Revocation Status | 332

- Requirements | 332
- Overview | 332
- Configuration | 335
- Verification | 346

5

Configuring Layer 2 Circuits

Overview | 354

Layer 2 Circuit Overview | 354

Layer 2 Circuits Configuration Overview | 356

Configuring Static Layer 2 Circuits | 356

Configuring Local Interface Switching in Layer 2 Circuits | 357

Configuring Interfaces for Layer 2 Circuits | 360

Example: Configuring the Pseudowire Status TLV | 370

Requirements | 370

Overview | 370

Configuration | 370

Configuring Policies for Layer 2 Circuits | 373

Configuring LDP for Layer 2 Circuits | 377

Configuring Class of Service with Layer 2 Circuits | 378

Configuring ATM Trunking on Layer 2 Circuits | 378

Layer 2 Circuit Bandwidth Accounting and Call Admission Control | 380

Configuring Bandwidth Allocation and Call Admission Control in Layer 2 Circuits | 383

Configuring Pseudowire Redundancy for Layer 2 Circuits | 385

Understanding Pseudowire Redundancy Mobile Backhaul Scenarios | 385

Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario | 391

Requirements | 391

Overview | 392

Configuration | 392

Verification | 416

Extension of Pseudowire Redundancy Condition Logic to Pseudowire Service Logical Interface
Overview | 421

Configuring Load Balancing for Layer 2 Circuits | 426

Reducing APS Switchover Time in Layer 2 Circuits | 426

Configuring Per-Packet Load Balancing | 427

Configuring Fast APS Switchover | 428

Configuring Protection Features for Layer 2 Circuits | 431

Egress Protection LSPs for Layer 2 Circuits | 432

Configuring Egress Protection Service Mirroring for BGP Signaled Layer 2 Services | 433

Example: Configuring an Egress Protection LSP for a Layer 2 Circuit | 438

- Requirements | 439
- Egress Protection LSP Overview | 439
- Egress Protection LSP Configuration | 441

Example: Configuring Layer 2 Circuit Protect Interfaces | 454

Example: Configuring Layer 2 Circuit Switching Protection | 461

- Requirements | 461
- Overview | 462
- Configuration | 463

Monitoring Layer 2 Circuits with BFD | 481

Configuring BFD for VCCV for Layer 2 Circuits | 481

Example: Configuring BFD for VCCV for Layer 2 Circuits | 484

- Requirements | 484
- Overview | 485
- Configuration | 486
- Verification | 492

Troubleshooting Layer 2 Circuits | 496

Tracing Layer 2 Circuit Operations | 496

6

Configuring VPWS VPNs

Overview | 498

Understanding VPWS | 498

Supported VPWS Standards | 502

FAT Flow Labels Overview | 503

Configuring VPWS VPNs | 505

Understanding FEC 129 BGP Autodiscovery for VPWS | 505

Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 508

- Requirements | 509
- Overview | 509
- Configuration | 514
- Verification | 520

Example: Configuring MPLS Egress Protection Service Mirroring for BGP Signaled Layer 2 Services | 526

Requirements | 526

Overview | 526

Configuration | 528

Verification | 545

Understanding Multisegment Pseudowire for FEC 129 | 550

Example: Configuring a Multisegment Pseudowire | 556

Requirements | 556

Overview | 557

Configuration | 563

Verification | 591

Troubleshooting | 602

Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605

Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608

7

Configuring VPLS

Overview | 613

Introduction to VPLS | 613

Supported VPLS Standards | 614

Supported Platforms and PICs | 614

VPLS Configuration Overview | 616

Introduction to Configuring VPLS | 616

Configuring an Ethernet Switch as the CE Device for VPLS | 618

Configuring Signaling Protocols for VPLS | 619

VPLS Routing and Virtual Ports | 619

BGP Signaling for VPLS PE Routers Overview | 621

Control Word for BGP VPLS Overview | 622

Configuring a Control Word for BGP VPLS | 623

BGP Route Reflectors for VPLS | 625

Interoperability Between BGP Signaling and LDP Signaling in VPLS | 626

Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS | 629

Example: VPLS Configuration (BGP Signaling) | 636

Example: VPLS Configuration (BGP and LDP Interworking) | 653

Assigning Routing Instances to VPLS | 674

Configuring VPLS Routing Instances | 674

Configuring a VPLS Routing Instance | 692

Support of Inner VLAN List and Inner VLAN Range for Qualified BUM Pruning on a Dual-Tagged Interface for a VPLS Routing Instance Overview | 693

Configuring Qualified BUM Pruning for a Dual-Tagged Interface with Inner VLAN list and InnerVLAN range for a VPLS Routing Instance | 695

Configuring a Layer 2 Control Protocol Routing Instance | 697

PE Router Mesh Groups for VPLS Routing Instances | 698

Configuring VPLS Fast Reroute Priority | 699

Specifying the VT Interfaces Used by VPLS Routing Instances | 701

Understanding PIM Snooping for VPLS | 702

Example: Configuring PIM Snooping for VPLS | 703

Requirements | 703

Overview | 703

Configuration | 705

Verification | 714

VPLS Label Blocks Operation | 718

Configuring the Label Block Size for VPLS | 723

Example: Building a VPLS From Router 1 to Router 3 to Validate Label Blocks | 725

Requirements | 725

Overview and Topology | 725

Configuration | 727

Associating Interfaces with VPLS | 733

Configuring Interfaces for VPLS Routing | 733

Configuring the VPLS Interface Name | 734

Configuring VPLS Interface Encapsulation | 735

Enabling VLAN Tagging | 737

Configuring VLAN IDs for Logical Interfaces | 738

Enabling VLANs for Hub and Spoke VPLS Networks | 739

Sample Scenario of Hierarchical Virtual Private LAN Service on Logical Tunnel Interface | 739

Configuring Aggregated Ethernet Interfaces for VPLS | 741

VPLS and Aggregated Ethernet Interfaces | 743

Configuring VLAN Identifiers for VLANs and VPLS Routing Instances | 744

Enabling VLAN Tagging | 748

Configuring VPLS Without a Tunnel Services PIC | 749

Configuring Pseudowires | 751

Configuring Static Pseudowires for VPLS | 751

VPLS Path Selection Process for PE Routers | 753

BGP and VPLS Path Selection for Multihomed PE Routers | 755

Dynamic Profiles for VPLS Pseudowires | 757

Use Cases for Dynamic Profiles for VPLS Pseudowires | 758

Example: Configuring VPLS Pseudowires with Dynamic Profiles—Basic Solutions | 759

Example: Configuring VPLS Pseudowires with Dynamic Profiles—Complex Solutions | 765

Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770

Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772

Example: Configuring H-VPLS BGP-Based and LDP-Based VPLS Interoperation | 775

Requirements | 775

Overview | 775

Configuration | 776

Verification | 793

Example: Configuring BGP-Based H-VPLS Using Different Mesh Groups for Each Spoke Router | 805

Requirements | 806

Overview and Topology | 807

Configuration | 809

Example: Configuring LDP-Based H-VPLS Using a Single Mesh Group to Terminate the Layer 2 Circuits | **834**

- Requirements | **835**
- Overview and Topology | **836**
- Configuration | **837**

Example: Configuring H-VPLS With VLANs | **843**

- Requirements | **843**
- Overview | **843**
- Configuration | **845**
- Verification | **856**

Example: Configuring H-VPLS Without VLANs | **861**

- Requirements | **861**
- Overview | **861**
- Configuration | **862**
- Verification | **872**

Sample Scenario of H-VPLS on ACX Series Routers for IPTV Services | **877**

Configuring Multihoming | 881

VPLS Multihoming Overview | **881**

Advantages of Using Autodiscovery for VPLS Multihoming | **884**

Example: Configuring FEC 129 BGP Autodiscovery for VPWS | **885**

- Understanding VPWS | **885**
- Understanding FEC 129 BGP Autodiscovery for VPWS | **888**
- Example: Configuring FEC 129 BGP Autodiscovery for VPWS | **891**
 - Requirements | **892**
 - Overview | **892**
 - Configuration | **897**
 - Verification | **903**

Example: Configuring BGP Autodiscovery for LDP VPLS | **909**

- Requirements | **909**
- Overview | **910**
- Configuration | **912**
- Verification | **933**

Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934

Requirements | 934

Overview | 934

Configuration | 935

Verification | 943

VPLS Multihoming Reactions to Network Failures | 949

Configuring VPLS Multihoming | 950

Example: VPLS Multihoming, Improved Convergence Time | 953

Requirements | 954

Overview | 954

Configuration | 956

Example: Configuring VPLS Multihoming (FEC 129) | 971

VPLS Multihoming Overview | 971

Example: Configuring VPLS Multihoming (FEC 129) | 973

Requirements | 974

Overview | 974

Configuration | 976

Verification | 986

Next-Generation VPLS for Multicast with Multihoming Overview | 991

Example: Next-Generation VPLS for Multicast with Multihoming | 997

Requirements | 997

Overview and Topology | 999

Configuration | 1001

Configuring Point-to-Multipoint LSPs | 1024

Next-Generation VPLS Point-to-Multipoint Forwarding Overview | 1024

Example: NG-VPLS Using Point-to-Multipoint LSPs | 1030

Requirements | 1031

Overview and Topology | 1032

Configuration | 1034

Flooding Unknown Traffic Using Point-to-Multipoint LSPs in VPLS | 1073

Example: Configuring Ingress Replication for IP Multicast Using MBGP MVPNs | 1078

Requirements | 1078

Overview | 1079

Configuration | 1081

Verification | 1086

Mapping VPLS Traffic to Specific LSPs | 1096

Configuring Inter-AS VPLS and IRB VPLS | 1098

Example: Configuring Inter-AS VPLS with MAC Processing at the ASBR | 1098

Requirements | 1098

Overview and Topology | 1099

Configuration | 1100

Configuring VPLS and Integrated Routing and Bridging | 1134

Configuring Integrated Routing and Bridging in a VPLS Instance (MX Series Routers Only) | 1137

Configuring L2PT for VPLS | 1137

Configuring Load Balancing and Performance | 1140

Configuring VPLS Load Balancing | 1141

Configuring VPLS Load Balancing Based on IP and MPLS Information | 1143

Configuring VPLS Load Balancing on MX Series 5G Universal Routing Platforms | 1145

Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves | 1147

MAC Moves Loop Prevention in VPLS Network Overview | 1147

Configuring VPLS Loop Prevention Due to MAC Moves | 1149

Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves | 1151

Requirements | 1151

Overview | 1152

Configuration | 1154

Verification | 1164

Understanding MAC Pinning | 1169

Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171

Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172

Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174

Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176

Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance (LDP and BGP) | **1178**

Configuring MAC Pinning on VPLS CE Interface | **1180**

Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance | **1182**

Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance | **1184**

Configuring MAC Pinning on Access Interfaces for Logical Systems | **1186**

Configuring MAC Pinning on Trunk Interfaces for Logical Systems | **1188**

Configuring MAC Pinning on Access Interfaces in Virtual Switches for Logical Systems | **1190**

Configuring MAC Pinning on Trunk Interfaces in Virtual Switches for Logical Systems | **1193**

Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance (LDP and BGP) for Logical Systems | **1195**

Configuring MAC Pinning on VPLS CE Interface for Logical Systems | **1198**

Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance for Logical Systems | **1200**

Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance for Logical Systems | **1202**

Example: Prevention of Loops in Bridge Domains by Enabling the MAC Pinning Feature on Access Interfaces | **1204**

Requirements | **1205**

Overview | **1205**

Configuration | **1206**

Verification | **1209**

Example: Prevention of Loops in Bridge Domains by Enabling the MAC Pinning Feature on Trunk Interfaces | **1210**

Requirements | **1211**

Overview | **1211**

Configuration | **1212**

Verification | **1218**

Configuring Improved VPLS MAC Address Learning on T4000 Routers with Type 5 FPCs | **1220**

Understanding Qualified MAC Learning | **1222**

Qualified Learning VPLS Routing Instance Behavior | 1223

Configuring Qualified MAC Learning | 1230

Configuring Class of Service and Firewall Filters in VPLS | 1232

Configuring EXP-Based Traffic Classification for VPLS | 1232

Configuring Firewall Filters and Policers for VPLS | 1233

Firewall Filter Match Conditions for VPLS Traffic | 1239

Monitoring and Tracing VPLS | 1259

Configuring Port Mirroring for VPLS Traffic | 1259

Configuring Y.1731 Functionality for VPLS to Support Delay and Delay Variation | 1259

Tracing VPLS Traffic and Operations | 1261

Connecting Layer 2 VPNs and Circuits to Other VPNs

Connecting Layer 2 VPNs to Other VPNs | 1263

Layer 2 VPN to Layer 2 VPN Connections | 1263

Using the Layer 2 Interworking Interface to Interconnect a Layer 2 VPN to a Layer 2 VPN | 1264

Example: Interconnecting a Layer 2 VPN with a Layer 2 VPN | 1266

Requirements | 1266

Overview and Topology | 1267

Configuration | 1268

Interconnecting Layer 2 VPNs with Layer 3 VPNs Overview | 1288

Example: Interconnecting a Layer 2 VPN with a Layer 3 VPN | 1290

Requirements | 1290

Overview and Topology | 1290

Configuration | 1294

Verification | 1314

Connecting Layer 2 Circuits to Other VPNs | 1321

Using the Layer 2 Interworking Interface to Interconnect a Layer 2 Circuit to a Layer 2 VPN | 1321

Applications for Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | 1323

Example: Interconnecting a Layer 2 Circuit with a Layer 2 VPN | 1323

Requirements | **1324**
 Overview and Topology | **1324**
 Configuration | **1326**

Example: Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | **1336**

Requirements | **1336**
 Overview and Topology | **1336**
 Configuration | **1338**

Applications for Interconnecting a Layer 2 Circuit with a Layer 3 VPN | **1357**

Example: Interconnecting a Layer 2 Circuit with a Layer 3 VPN | **1358**

Requirements | **1358**
 Overview and Topology | **1359**
 Configuration | **1360**
 Verifying the Layer 2 Circuit to Layer 3 VPN Interconnection | **1375**

9

Configuration Statements and Operational Commands

Configuration Statements (All VPNs) | **1387**

aggregate-label | **1388**

backup-neighbor | **1389**

description (Routing Instances) | **1391**

family route-target | **1392**

graceful-restart (Enabling Globally) | **1394**

instance-type | **1397**

interface (Routing Instances) | **1400**

no-forwarding | **1402**

forward-policy-mismatch (Security Group VPN Member) | **1403**

proxy-generate | **1404**

revert-time (Protocols Layer 2 Circuits) | **1406**

route-distinguisher | **1409**

route-distinguisher-id | **1412**

route-target-filter | **1414**

switchover-delay | 1416

unicast-reverse-path | 1417

vpn-apply-export | 1419

vrf-export | 1420

vrf-import | 1422

vrf-mtu-check | 1424

vrf-target | 1425

Configuration Statements (Layer 2 VPNs and VPLS) | 1428

action-priority | 1433

active-interface (VPLS Multihoming) | 1435

any (VPLS Multihoming) | 1436

auto-discovery-only | 1438

automatic-site-id | 1440

backup-interface (Layer 2 Circuits) | 1442

bandwidth (Protocols Layer 2 Circuit) | 1443

best-site | 1444

bfd-liveness-detection (Layer 2 VPN and VPLS) | 1446

community (Protocols Layer 2 Circuit) | 1448

connection-protection | 1450

connectivity-type | 1451

control-channel (Protocols OAM) | 1453

control-word (Protocols Layer 2 Circuit Neighbor) | 1454

control-word (Protocols Layer 2 VPN) | 1456

control-word | 1458

deep-vlan-qualified-learning | 1460

default-isid | 1461

description (Protocols Layer 2 Circuit Neighbor) | **1463**

description (Protocols Layer 2 VPN) | **1464**

detection-time (BFD Liveness Detection) | **1465**

egress-protection (Layer 2 circuit) | **1469**

egress-protection (MPLS) | **1470**

encapsulation (Logical Interface) | **1472**

encapsulation | **1477**

encapsulation-type (Layer 2 Circuits) | **1484**

encapsulation-type (Layer 2 VPNs) | **1486**

end-interface | **1489**

exclusive-mac | **1490**

extended-vlan-list | **1492**

family (Protocols BGP) | **1494**

family multiservice | **1499**

fast-aps-switch | **1502**

fast-reroute-priority | **1504**

flow-label | **1506**

flow-label-receive | **1507**

flow-label-receive-static | **1509**

flow-label-static | **1510**

flow-label-transmit | **1512**

flow-label-transmit-static | **1514**

global-mac-move | **1515**

hot-standby | **1517**

hot-standby (Protocols Layer 2 Circuit) | **1518**

hot-standby-vc-on (Protocols Layer 2 Circuit) | **1520**

identifier (VPLS Multihoming for FEC 129) | **1522**

ignore-encapsulation-mismatch | **1524**

ignore-mtu-mismatch | **1525**

import-labeled-routes (Routing Instances VPLS) | **1527**

interface (Protocols Layer 2 Circuit) | **1528**

interface (Protocols Layer 2 VPN) | **1531**

interface (VPLS Mesh-Group) | **1533**

interface (VPLS Multihoming for FEC 129) | **1534**

interface (VPLS Routing Instances) | **1535**

interface-mac-limit (VPLS) | **1537**

install-nexthop | **1539**

l2circuit | **1540**

l2ckt | **1543**

l2-learning | **1544**

l2vpn | **1546**

l2vpn (routing-options) | **1549**

l2vpn-id | **1551**

label-allocation | **1552**

label-block-size | **1553**

label-switched-path-template (Multicast) | **1555**

local-switching (Layer 2 Circuits) | **1557**

local-switching (VPLS) | **1559**

mac-flush | **1560**

mac-pinning | **1562**

mac-statistics | **1564**

mac-table-size | **1567**

map-dest-bmac-to-dest-cmac | **1569**

mesh-group (Protocols VPLS) | **1570**

minimum-interval (BFD Liveness Detection) | **1572**

minimum-receive-interval (BFD Liveness Detection) | **1574**

mtu | **1576**

multicast-mode (EVPN) | **1580**

multiplier (BFD Liveness Detection) | **1582**

multi-homing (VPLS Multihoming for BGP VPLS) | **1584**

multi-homing (VPLS Multihoming for FEC 129) | **1585**

neighbor (Protocols Layer 2 Circuit) | **1587**

neighbor (Protocols VPLS) | **1590**

no-adaptation (BFD Liveness Detection) | **1592**

no-control-word | **1594**

no-control-word (Protocols Layer 2 VPN) | **1596**

no-l2ckt | **1597**

no-l2vpn | **1599**

no-local-switching (VPLS) | **1600**

no-mac-learning | **1601**

no-normalization | **1605**

no-revert (Local Switching) | **1607**

no-revert (Neighbor Interface) | **1608**

no-tunnel-services | **1610**

oam | **1612**

packet-action | **1613**

path-selection | **1617**

pbb-service-options | **1621**

peer-active (VPLS Multihoming for FEC 129) | **1622**

peer-as (VPLS) | **1625**

ping-interval | **1626**

policer (Layer 2 VPN) | **1628**

policy-oids | **1630**

preference (Interface-Level Preference for VPLS Multihoming for FEC 129) | **1631**

preference (Site-Level Preference for VPLS Multihoming for FEC 129) | **1633**

primary (VPLS Multihoming) | **1634**

protect-interface | **1636**

protected-l2circuit | **1638**

protector-interface | **1639**

protector-pe | **1641**

proxy (Interfaces) | **1642**

pseudowire-status-tlv | **1644**

psn-tunnel-endpoint | **1645**

qualified-bum-pruning-mode | **1646**

remote | **1648**

remote-site-id | **1649**

routing-instances | **1651**

rsvp-te (Routing Instances Provider Tunnel) | **1652**

send-oam | **1654**

service-groups | **1655**

service-type | **1656**

site (Layer 2 Circuits) | **1658**

site (VPLS Multihoming for FEC 128) | **1660**

site (VPLS Multihoming for FEC 129) | **1661**

site-identifier (Layer 2 Circuits) | **1663**

site-identifier (VPLS) | **1664**

site-preference | **1666**

site-range | **1668**

source-attachment-identifier (Protocols VPWS) | **1669**

source-bmac | **1671**

standby (Protocols Layer 2 Circuit) | **1673**

static (Protocols Layer 2 Circuit) | **1674**

static (Protocols VPLS) | **1676**

static-mac | **1678**

target-attachment-identifier (Protocols VPWS) | **1680**

template | **1682**

traceoptions (Egress Protection) | **1683**

traceoptions (Protocols Layer 2 Circuit) | **1685**

traceoptions (Protocols Layer 2 VPN) | **1687**

traceoptions (Protocols VPLS) | **1690**

transmit-interval (BFD Liveness Detection) | **1693**

tunnel-services (Routing Instances VPLS) | **1696**

version (BFD Liveness Detection) | **1698**

virtual-circuit-id | **1700**

virtual-gateway-address | **1702**

virtual-mac | **1703**

vlan-id | **1705**

vlan-id (routing instance) | **1706**

vlan-id inner-all | **1708**

vlan-id-list (Interface in VPLS) | **1709**

vlan-tagging | **1710**

vlan-tags (Stacked VLAN Tags) | **1713**

vpls (Interfaces) | **1716**

vpls (Routing Instance) | **1717**

vpls-id | **1721**

vpls-id-list (protocols vpls mesh-group) | **1722**

vpls-mac-move | **1724**

vpws-service-id | **1725**

Operational Commands | 1728

clear bridge statistics | **1729**

clear pim snooping join | **1731**

clear pim snooping statistics | **1734**

clear security group-vpn member group | **1736**

clear security group-vpn member ike security-associations | **1738**

clear security group-vpn member kek security-associations | **1739**

clear vpls mac-address | **1740**

clear vpls mac-move-action | **1742**

clear vpls mac-table | **1744**

ping mpls l2circuit | **1745**

ping mpls l2vpn | **1749**

ping vpls instance | **1753**

request l2circuit-switchover | **1756**

show interfaces lsi (Label-Switched Interface) | **1757**

show l2circuit connections | **1762**

show l2vpn connections | **1773**

show pim snooping interfaces | **1783**

show pim snooping join | **1787**

show pim snooping neighbors | **1793**

show pim snooping statistics | **1800**

show route | **1807**

show route table | **1820**

show route forwarding-table | **1849**

show security group-vpn member ike security-associations | **1863**

show security pki ca-certificate (View) | **1869**

show vpls connections | **1874**

show vpls flood event-queue | **1890**

show vpls flood instance | **1892**

show vpls flood route | **1896**

show vpls mac-move-action | **1899**

show vpls mac-table | **1901**

show vpls statistics | **1909**

About This Guide

The Junos operating system (Junos OS) supports layer 2 VPN service which allows customers to have geographically dispersed private networks across service provider's networks. Use the topics on this page to configure VPWS, VPLS, and layer 2 VPN routing instances to enable layer 2 VPN service.

RELATED DOCUMENTATION

[Learn About Secure VPNs](#)

[Day One Poster: VPNs](#)

[FAQ: VPLS on MX Series Routers](#)

[FAQ: Layer 2 Circuits and Layer 2 VPN on MX Series Routers](#)

1

PART

Common Configuration for All VPNs

[VPNs Overview | 2](#)

[Assigning Routing Instances to VPNs | 9](#)

[Distributing Routes in VPNs | 20](#)

[Distributing VPN Routes with Target Filtering | 42](#)

[Configuring Forwarding Options for VPNs | 109](#)

[Configuring Graceful Restart for VPNs | 119](#)

[Configuring Class of Service for VPNs | 132](#)

[Pinging VPNs | 133](#)

CHAPTER 1

VPNs Overview

IN THIS CHAPTER

- [VPLS | 2](#)
- [Types of VPNs | 2](#)
- [VPNs and Logical Systems | 6](#)
- [Layer 2 VPNs | 7](#)
- [Routers in a VPN | 8](#)

VPLS

In a Layer 3 network only, you can configure virtual private LAN service (VPLS), which is an Ethernet-based point-to-multipoint Layer 2 VPN. It enables you to connect geographically dispersed Ethernet local area networks (LAN) sites to each other across an MPLS backbone. For ISP customers who implement VPLS, all sites appear to be in the same Ethernet LAN even though traffic travels across the service provider's network.

RELATED DOCUMENTATION[Junos OS VPNs Library for Routing Devices](#)[MX Series Router Architecture](#)

Types of VPNs

IN THIS SECTION

- [Layer 2 VPNs | 3](#)

- Layer 3 VPNs | 4
- VPLS | 4
- Virtual-Router Routing Instances | 5

A virtual private network (VPN) consists of two topological areas: the provider's network and the customer's network. The customer's network is commonly located at multiple physical sites and is also private (non-Internet). A customer site would typically consist of a group of routers or other networking equipment located at a single physical location. The provider's network, which runs across the public Internet infrastructure, consists of routers that provide VPN services to a customer's network as well as routers that provide other services. The provider's network connects the various customer sites in what appears to the customer and the provider to be a private network.

To ensure that VPNs remain private and isolated from other VPNs and from the public Internet, the provider's network maintains policies that keep routing information from different VPNs separate. A provider can service multiple VPNs as long as its policies keep routes from different VPNs separate. Similarly, a customer site can belong to multiple VPNs as long as it keeps routes from the different VPNs separate.

The Junos® Operating System (Junos OS) provides several types of VPNs; you can choose the best solution for your network environment. Each of the following VPNs has different capabilities and requires different types of configuration:

Layer 2 VPNs

Implementing a Layer 2 VPN on a router is similar to implementing a VPN using a Layer 2 technology such as ATM or Frame Relay. However, for a Layer 2 VPN on a router, traffic is forwarded to the router in Layer 2 format. It is carried by MPLS over the service provider's network and then converted back to Layer 2 format at the receiving site. You can configure different Layer 2 formats at the sending and receiving sites. The security and privacy of an MPLS Layer 2 VPN are equal to those of an ATM or Frame Relay VPN.

On a Layer 2 VPN, routing occurs on the customer's routers, typically on the CE router. The CE router connected to a service provider on a Layer 2 VPN must select the appropriate circuit on which to send traffic. The PE router receiving the traffic sends it across the service provider's network to the PE router connected to the receiving site. The PE routers do not need to store or process the customer's routes; they only need to be configured to send data to the appropriate tunnel.

For a Layer 2 VPN, customers need to configure their own routers to carry all Layer 3 traffic. The service provider needs to know only how much traffic the Layer 2 VPN needs to carry. The service provider's

routers carry traffic between the customer's sites using Layer 2 VPN interfaces. The VPN topology is determined by policies configured on the PE routers.

Layer 3 VPNs

In a Layer 3 VPN, the routing occurs on the service provider's routers. Therefore, Layer 3 VPNs require more configuration on the part of the service provider, because the service provider's PE routers must store and process the customer's routes.

In the Junos OS, Layer 3 VPNs are based on RFC 4364, *BGP/MPLS IP Virtual Private Networks (VPNs)*. This RFC defines a mechanism by which service providers can use their IP backbones to provide Layer 3 VPN services to their customers. The sites that make up a Layer 3 VPN are connected over a provider's existing public Internet backbone.

VPNs based on RFC 4364 are also known as BGP/MPLS VPNs because BGP is used to distribute VPN routing information across the provider's backbone, and MPLS is used to forward VPN traffic across the backbone to remote VPN sites.

Customer networks, because they are private, can use either public addresses or private addresses, as defined in RFC 1918, *Address Allocation for Private Internets*. When customer networks that use private addresses connect to the public Internet infrastructure, the private addresses might overlap with the private addresses used by other network users. BGP/MPLS VPNs solve this problem by prefixing a VPN identifier to each address from a particular VPN site, thereby creating an address that is unique both within the VPN and within the public Internet. In addition, each VPN has its own VPN-specific routing table that contains the routing information for that VPN only.

VPLS

Virtual private LAN service (VPLS) allows you to connect geographically dispersed customer sites as if they were connected to the same LAN. In many ways, it works like a Layer 2 VPN. VPLS and Layer 2 VPNs use the same network topology and function similarly. A packet originating within a customer's network is sent first to a CE device. It is then sent to a PE router within the service provider's network. The packet traverses the service provider's network over an MPLS LSP. It arrives at the egress PE router, which then forwards the traffic to the CE device at the destination customer site.

The key difference in VPLS is that packets can traverse the service provider's network in a point-to-multipoint fashion, meaning that a packet originating from a CE device can be broadcast to PE routers in the VPLS. In contrast, a Layer 2 VPN forwards packets in a point-to-point fashion only. The destination of a packet received from a CE device by a PE router must be known for the Layer 2 VPN to function properly.

In a Layer 3 network only, you can configure virtual private LAN service (VPLS), to connect geographically dispersed Ethernet local area networks (LAN) sites to each other across an MPLS backbone. For ISP customers who implement VPLS, all sites appear to be in the same Ethernet LAN

even though traffic travels across the service provider's network. VPLS is designed to carry Ethernet traffic across an MPLS-enabled service provider network. In certain ways, VPLS mimics the behavior of an Ethernet network. When a PE router configured with a VPLS routing instance receives a packet from a CE device, it first checks the appropriate routing table for the destination of the VPLS packet. If the router has the destination, it forwards it to the appropriate PE router. If it does not have the destination, it broadcasts the packet to all the other PE routers that are members of the same VPLS routing instance. The PE routers forward the packet to their CE devices. The CE device that is the intended recipient of the packet forwards it to its final destination. The other CE devices discard it.

Virtual-Router Routing Instances


A virtual-router routing instance, like a VPN routing and forwarding (VRF) routing instance, maintains separate routing and forwarding tables for each instance. However, many configuration steps required for VRF routing instances are not required for virtual-router routing instances. Specifically, you do not need to configure a route distinguisher, a routing table policy (the `vrf-export`, `vrf-import`, and `route-distinguisher` statements), or MPLS between the P routers.

However, you need to configure separate logical interfaces between each of the service provider routers participating in a virtual-router routing instance. You also need to configure separate logical interfaces between the service provider routers and the customer routers participating in each routing instance. Each virtual-router instance requires its own unique set of logical interfaces to all participating routers.

[Figure 1 on page 6](#) shows how this works. The service provider routers G and H are configured for virtual-router routing instances Red and Green. Each service provider router is directly connected to two local customer routers, one in each routing instance. The service provider routers are also connected to each other over the service provider network. These routers need four logical interfaces: a *logical*

interface to each of the locally connected customer routers and a logical interface to carry traffic between the two service provider routers for each virtual-router instance.

Figure 1: Logical Interface per Router in a Virtual-Router Routing Instance



Layer 3 VPNs do not have this configuration requirement. If you configure several Layer 3 VPN routing instances on a PE router, all the instances can use the same logical interface to reach another PE router. This is possible because Layer 3 VPNs use MPLS (VPN) labels that differentiate traffic going to and from various routing instances. Without MPLS and VPN labels, as in a virtual-router routing instance, you need separate logical interfaces to separate traffic from different instances.

One method of providing this logical interface between the service provider routers is by configuring tunnels between them. You can configure IP Security (IPsec), generic routing encapsulation (GRE), or IP-IP tunnels between the service provider routers, terminating the tunnels at the virtual-router instance.

VPNs and Logical Systems

You can partition a single physical router into multiple logical systems that perform independent routing tasks. Because logical systems perform a subset of the tasks once handled by the physical router, logical systems offer an effective way to maximize the use of a single routing platform.

Logical systems perform a subset of the actions of a physical router and have their own unique routing tables, interfaces, policies, and routing instances. A set of logical systems within a single router can handle the functions previously performed by several small routers.

Logical systems support Layer 2 VPNs, Layer 3 VPNs, VPLS, and Layer 2 circuits. For more information about logical systems, see the [Logical Systems User Guide for Routers and Switches](#).

Starting in Junos OS release 17.4R1, Ethernet VPN (EVPN) support has also been extended to logical systems running on MX devices. The same EVPN options and performance are available, and can be configured under the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols evpn] hierarchy.

Release History Table

Release	Description
17.4	Starting in Junos OS release 17.4R1, Ethernet VPN (EVPN) support has also been extended to logical systems running on MX devices. The same EVPN options and performance are available, and can be configured under the [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> protocols evpn] hierarchy.

Layer 2 VPNs

In a Layer 3 network only, you can configure Layer 2 virtual private network (VPN) under a Layer 2 VPN routing instance type **l2vpn**.

In a Layer 2 environment, you can use a **l2vpn** routing instance to transparently carry Layer 2 traffic over an IP/MPLS backbone. Layer 2 traffic is sent to the provider edge (PE) router in Layer 2 format. The PE router encapsulates the frames and transports them over the IP/MPLS backbone to the PE router on the other side of the cloud. The remote PE router removes encapsulation and sends the frames to the receiving site in Layer 2 format.

RELATED DOCUMENTATION

[MX Series Router Architecture](#)


[Layer 2 and Layer 3 Features on MX Series Routers](#)

[Junos OS VPNs Library for Routing Devices](#)

Routers in a VPN

Figure 2 on page 8 illustrates how VPN functionality is provided by the provider edge (PE) routers; the provider and customer edge (CE) routers have no special configuration requirements for VPNs.

Figure 2: Routers in a VPN



Assigning Routing Instances to VPNs

IN THIS CHAPTER

- [Configuring Routing Instances on PE Routers in VPNs | 9](#)
- [Configuring Virtual-Router Routing Instances in VPNs | 15](#)
- [Configuring Path MTU Checks for VPN Routing Instances | 18](#)

Configuring Routing Instances on PE Routers in VPNs

IN THIS SECTION

- [Configuring the Routing Instance Name for a VPN | 10](#)
- [Configuring the Description | 10](#)
- [Configuring the Instance Type | 11](#)
- [Configuring Interfaces for VPN Routing | 12](#)
- [Configuring the Route Distinguisher | 14](#)
- [Configuring Automatic Route Distinguishers | 15](#)

You need to configure a routing instance for each VPN on each of the PE routers participating in the VPN. The configuration procedures outlined in this section are applicable to Layer 2 VPNs, Layer 3 VPNs, and VPLS. The configuration procedures specific to each type of VPN are described in the corresponding sections in the other configuration chapters.

To configure routing instances for VPNs, include the following statements:

```
description text;  
instance-type type;  
interface interface-name;
```

```

route-distinguisher (as-number:number | ip-address:number);
vrf-import [ policy-names ];
vrf-export [ policy-names ];
vrf-target {
    export community-name;
    import community-name;
}

```

You can include these statements at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

To configure VPN routing instances, you perform the steps in the following sections:

Configuring the Routing Instance Name for a VPN

The name of the routing instance for a VPN can be a maximum of 128 characters and can contain letters, numbers, and hyphens. In Junos OS Release 9.0 and later, you can no longer specify `default` as the actual routing-instance name. You also cannot use any special characters (! @ # \$ % ^ & *, + < > : ;) within the name of a routing instance.

NOTE: In Junos OS Release 9.6 and later, you can include a slash (/) in a routing instance name only if a logical system is not configured. That is, you cannot include the slash character in a routing instance name if a logical system other than the default is explicitly configured.

Specify the routing-instance name with the `routing-instance` statement:

```

routing-instance routing-instance-name {...}

```

You can include this statement at the following hierarchy levels:

- [edit]
- [edit logical-systems *logical-system-name*]

Configuring the Description

To provide a text description for the routing instance, include the `description` statement. If the text includes one or more spaces, enclose them in quotation marks (" "). Any descriptive text you include is

displayed in the output of the `show route instance detail` command and has no effect on the operation of the routing instance.

To configure a text description, include the `description` statement:

```
description text;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

Configuring the Instance Type

The instance type you configure varies depending on whether you are configuring Layer 2 VPNs, Layer 3 VPNs, VPLS, or virtual routers. Specify the instance type by including the `instance-type` statement:

- To enable Layer 2 VPN routing on a PE router, include the `instance-type` statement and specify the value `l2vpn`:

```
instance-type l2vpn;
```

- To enable VPLS routing on a PE router, include the `instance-type` statement and specify the value `vpls`:

```
instance-type vpls;
```

- Layer 3 VPNs require that each PE router have a VPN routing and forwarding (VRF) table for distributing routes within the VPN. To create the VRF table on the PE router, include the `instance-type` statement and specify the value `vrf`:

```
instance-type vrf;
```

NOTE: Routing Engine based sampling is not supported on VRF routing instances.

- To enable the virtual-router routing instance, include the `instance-type` statement and specify the value `virtual-router`:

```
instance-type virtual-router;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

Configuring Interfaces for VPN Routing

On each PE router, you must configure an interface over which the VPN traffic travels between the PE and CE routers.

The sections that follow describe how to configure interfaces for VPNs:

General Configuration for VPN Routing

The configuration described in this section applies to all types of VPNs. For Layer 3 VPNs and carrier-of-carriers VPNs, complete the configuration described in this section before proceeding to the interface configuration sections specific to those topics.

To configure interfaces for VPN routing, include the `interface` statement:

```
interface interface-name;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

Specify both the physical and logical portions of the interface name, in the following format:

```
physical.logical
```

For example, in `at-1/2/1.2`, `at-1/2/1` is the physical portion of the interface name and `2` is the logical portion. If you do not specify the logical portion of the interface name, the value `0` is set by default.

A logical interface can be associated with only one routing instance. If you enable a routing protocol on all instances by specifying `interfaces all` when configuring the master instance of the protocol at the

[edit protocols] hierarchy level, and if you configure a specific interface for VPN routing at the [edit routing-instances *routing-instance-name*] hierarchy level or at the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*] hierarchy level, the latter interface statement takes precedence and the interface is used exclusively for the VPN.

If you explicitly configure the same interface name at the [edit protocols] hierarchy level and at either the [edit routing-instances *routing-instance-name*] or [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*] hierarchy levels, an attempt to commit the configuration fails.

Configuring Interfaces for Layer 3 VPNs

When you configure the Layer 3 VPN interfaces at the [edit interfaces] hierarchy level, you must also configure family inet when configuring the logical interface:

```
[edit interfaces]
interface-name {
    unit logical-unit-number {
        family inet;
    }
}
```

Configuring Interfaces for Carrier-of-Carriers VPNs

When you configure carrier-of-carriers VPNs, you need to configure the family mpls statement in addition to the family inet statement for the interfaces between the PE and CE routers. For carrier-of-carriers VPNs, configure the logical interface as follows:

```
[edit interfaces]
interface-name {
    unit logical-unit-number {
        family inet;
        family mpls;
    }
}
```

If you configure family mpls on the logical interface and then configure this interface for a non-carrier-of-carriers routing instance, the family mpls statement is automatically removed from the configuration for the logical interface, since it is not needed.

Configuring Unicast RPF on VPN Interfaces

For VPN interfaces that carry IP version 4 or version 6 (IPv4 or IPv6) traffic, you can reduce the impact of denial-of-service (DoS) attacks by configuring unicast reverse path forwarding (RPF). Unicast RPF helps determine the source of attacks and rejects packets from unexpected source addresses on interfaces where unicast RPF is enabled.

You can configure unicast RPF on a VPN interface by enabling unicast RPF on the interface and including the `interface` statement at the `[edit routing-instances routing-instance-name]` hierarchy level.

You cannot configure unicast RPF on the core-facing interfaces. You can only configure unicast RPF on the CE router-to-PE router interfaces on the PE router. However, for virtual-router routing instances, unicast RPF is supported on all interfaces you specify in the routing instance.

For information about how to configure unicast RPF on VPN interfaces, see [Understanding Unicast RPF \(Routers\)](#).

Configuring the Route Distinguisher

Each routing instance that you configure on a PE router must have a unique route distinguisher associated with it. VPN routing instances need a route distinguisher to help BGP to distinguish between potentially identical network layer reachability information (NLRI) messages received from different VPNs. If you configure different VPN routing instances with the same route distinguisher, the commit fails.

For Layer 2 VPNs and VPLS, if you have configured the `l2vpn-use-bgp-rules` statement, you must configure a unique route distinguisher for each PE router participating in a specific routing instance.

For other types of VPNs, we recommend that you use a unique route distinguisher for each PE router participating in the routing instance. Although you can use the same route distinguisher on all PE routers for the same VPN routing instance (except for Layer 2 VPNs and VPLS), if you use a unique route distinguisher, you can determine the CE router from which a route originated within the VPN.

To configure a route distinguisher on a PE router, include the `route-distinguisher` statement:

```
route-distinguisher (as-number:number | ip-address:number);
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

The route distinguisher is a 6-byte value that you can specify in one of the following formats:

- *as-number:number*, where *as-number* is an autonomous system (AS) number (a 2-byte value) and *number* is any 4-byte value. The AS number can be in the range 1 through 65,535. We recommend that you use

an Internet Assigned Numbers Authority (IANA)-assigned, nonprivate AS number, preferably the Internet service provider's (ISP's) own or the customer's own AS number.

- *ip-address:number*, where *ip-address* is an IP address (a 4-byte value) and *number* is any 2-byte value. The IP address can be any globally unique unicast address. We recommend that you use the address that you configure in the *router-id* statement, which is a nonprivate address in your assigned prefix range.

Configuring Automatic Route Distinguishers

If you configure the *route-distinguisher-id* statement at the [edit routing-options] hierarchy level, a route distinguisher is automatically assigned to the routing instance. If you also configure the *route-distinguisher* statement in addition to the *route-distinguisher-id* statement, the value configured for *route-distinguisher* supersedes the value generated from *route-distinguisher-id*.

To assign a route distinguisher automatically, include the *route-distinguisher-id* statement:

```
route-distinguisher-id ip-address;
```

You can include this statement at the following hierarchy levels:

- [edit routing-options]
- [edit logical-systems *logical-system-name* routing-options]

A type 1 route distinguisher is automatically assigned to the routing instance using the format *ip-address:number*. The IP address is specified by the *route-distinguisher-id* statement and the number is unique for the routing instance.

Configuring Virtual-Router Routing Instances in VPNs

IN THIS SECTION

- [Configuring a Routing Protocol Between the Service Provider Routers | 16](#)
- [Configuring Logical Interfaces Between Participating Routers | 17](#)

A virtual-router routing instance, like a VRF routing instance, maintains separate routing and forwarding tables for each instance. However, many of the configuration steps required for VRF routing instances

are not required for virtual-router routing instances. Specifically, you do not need to configure a route distinguisher, a routing table policy (the `vrf-export`, `vrf-import`, and `route-distinguisher` statements), or MPLS between the service provider routers.

Configure a virtual-router routing instance by including the following statements:

```
description text;  
instance-type virtual-router;  
interface interface-name;  
protocols { ... }
```

You can include these statements at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

The following sections explain how to configure a virtual-router routing instance:

Configuring a Routing Protocol Between the Service Provider Routers

The service provider routers need to be able to exchange routing information. You can configure the following protocols for the virtual-router routing instance `protocols` statement configuration at the [edit routing-instances *routing-instance-name*] hierarchy level:

- BGP
- IS-IS
- LDP
- OSPF
- Protocol Independent Multicast (PIM)
- RIP

You can also configure static routes.

IBGP route reflection is not supported for virtual-router routing instances.

If you configure LDP under a virtual-router instance, LDP routes are placed by default in the routing instance's inet.0 and inet.3 routing tables (for example, sample.inet.0 and sample.inet.3). To restrict LDP routes to only the routing instance's inet.3 table, include the `no-forwarding` statement:

```
no-forwarding;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols ldp]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols ldp]

When you restrict the LDP routes to only the inet.3 routing table, the corresponding IGP route in the inet.0 routing table can be redistributed and advertised into other routing protocols.

For information about routing tables, see [Understanding Junos OS Routing Tables](#).

Configuring Logical Interfaces Between Participating Routers

You must configure an interface to each customer router participating in the routing instance and to each P router participating in the routing instance. Each virtual-router routing instance requires its own separate logical interfaces to all P routers participating in the instance. To configure interfaces for virtual-router instances, include the `interface` statement:

```
interface interface-name;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

Specify both the physical and logical portions of the interface name, in the following format:

```
physical.logical
```

For example, in at-1/2/1.2, at-1/2/1 is the physical portion of the interface name and 2 is the logical portion. If you do not specify the logical portion of the interface name, 0 is set by default.

You must also configure the interfaces at the [edit interfaces] hierarchy level.

One method of providing this logical interface between the provider routers is by configuring tunnels between them. You can configure IP Security (IPsec), generic routing encapsulation (GRE), or IP-IP tunnels between the provider routers, terminating the tunnels at the virtual-router instance.

For information about how to configure tunnels and interfaces, see the [Junos OS Services Interfaces Library for Routing Devices](#).

Configuring Path MTU Checks for VPN Routing Instances

IN THIS SECTION

- [Enabling Path MTU Checks for a VPN Routing Instance | 19](#)
- [Assigning an IP Address to the VPN Routing Instance | 19](#)

By default, the maximum transmission unit (MTU) check for VPN routing instances is disabled on M Series routers (except the M320 router) and enabled for the M320 router. On M Series routers, you can configure path MTU checks on the outgoing interfaces for unicast traffic routed on VRF routing instances and on virtual-router routing instances.

When you enable an MTU check, the routing platform sends an Internet Control Message Protocol (ICMP) message when a packet traversing the routing instance exceeds the MTU size and has the do-not-fragment bit set. The ICMP message uses the VRF local address as its source address.

For an MTU check to work in a routing instance, you must both include the `vrf-mtu-check` statement at the `[edit chassis]` hierarchy level and assign at least one interface containing an IP address to the routing instance.

For more information about the path MTU check, see the [Junos OS Administration Library for Routing Devices](#).

To configure path MTU checks, do the tasks described in the following sections:

Enabling Path MTU Checks for a VPN Routing Instance

To enable path checks on the outgoing interface for unicast traffic routed on a VRF or virtual-router routing instance, include the `vrf-mtu-check` statement at the `[edit chassis]` hierarchy level:

```
[edit chassis]
vrf-mtu-check;
```

Assigning an IP Address to the VPN Routing Instance

To ensure that the path MTU check functions properly, at least one IP address must be associated with each VRF or virtual-router routing instance. If an IP address is not associated with the routing instance, ICMP reply messages cannot be sent.

Typically, the VRF or virtual-router routing instance IP address is drawn from among the IP addresses associated with interfaces configured for that routing instance. If none of the interfaces associated with a VRF or virtual-router routing instance is configured with an IP address, you need to explicitly configure a logical loopback interface with an IP address. This interface must then be associated with the routing instance. See *Configuring Logical Units on the Loopback Interface for Routing Instances in Layer 3 VPNs* for details.

Distributing Routes in VPNs

IN THIS CHAPTER

- [Enabling Routing Information Exchange for VPNs | 20](#)
- [Configuring IBGP Sessions Between PE Routers in VPNs | 20](#)
- [Configuring Aggregate Labels for VPNs | 22](#)
- [Configuring a Signaling Protocol and LSPs for VPNs | 23](#)
- [Configuring Policies for the VRF Table on PE Routers in VPNs | 28](#)
- [Configuring the Route Origin for VPNs | 36](#)

Enabling Routing Information Exchange for VPNs

For Layer 2 VPNs, Layer 3 VPNs, virtual-router routing instances, VPLS, EVPNs, and Layer 2 circuits to function properly, the service provider's PE and P routers must be able to exchange routing information. For this to happen, you must configure either an IGP (such as OSPF or IS-IS) or static routes on these routers. You configure the IGP on the master instance of the routing protocol process at the [edit protocols] hierarchy level, not within the routing instance used for the VPN—that is, not at the [edit routing-instances] hierarchy level.

When you configure the PE router, do not configure any summarization of the PE router's loopback addresses at the area boundary. Each PE router's loopback address should appear as a separate route.

Configuring IBGP Sessions Between PE Routers in VPNs

You must configure an IBGP session between the PE routers to allow the PE routers to exchange information about routes originating and terminating in the VPN. The PE routers rely on this information to determine which labels to use for traffic destined for remote sites.

Configure an IBGP session for the VPN as follows:

```
[edit protocols]
bgp {
  group group-name {
    type internal;
    local-address ip-address;
    family evpn {
      signaling;
    }
    family (inet-vpn | inet6-vpn) {
      unicast;
    }
    family l2vpn {
      signaling;
    }
    neighbor ip-address;
  }
}
```

The IP address in the `local-address` statement is the address of the loopback interface on the local PE router. The IBGP session for the VPN runs through the loopback address. (You must also configure the loopback interface at the `[edit interfaces]` hierarchy level.)

The IP address in the `neighbor` statement is the loopback address of the neighboring PE router. If you are using RSVP signaling, this IP address is the same address you specify in the `to` statement at the `[edit mpls label-switched-path lsp-path-name]` hierarchy level when you configure the MPLS LSP.

The `family` statement allows you to configure the IBGP session for Layer 2 VPNs, VPLS, EVPNs or for Layer 3 VPNs.

- To configure an IBGP session for Layer 2 VPNs and VPLS, include the `signaling` statement at the `[edit protocols bgp group group-name family l2vpn]` hierarchy level:

```
[edit protocols bgp group group-name family l2vpn]
signaling;
```


- To configure an IBGP session for EVPNs, include the signaling statement at the `[edit protocols bgp group group-name family evpn]` hierarchy level:

```
[edit protocols bgp group group-name family evpn]
signaling;
```

- To configure an IPv4 IBGP session for Layer 3 VPNs, configure the unicast statement at the `[edit protocols bgp group group-name family inet-vpn]` hierarchy level:

```
[edit protocols bgp group group-name family inet-vpn]
unicast;
```

- To configure an IPv6 IBGP session for Layer 3 VPNs, configure the unicast statement at the `[edit protocols bgp group group-name family inet6-vpn]` hierarchy level:

```
[edit protocols bgp group group-name family inet6-vpn]
unicast;
```

NOTE: You can configure both `family inet` and `family inet-vpn` or both `family inet6` and `family inet6-vpn` within the same peer group. This allows you to enable support for both IPv4 and IPv4 VPN routes or both IPv6 and IPv6 VPN routes within the same peer group.

Configuring Aggregate Labels for VPNs

Aggregate labels for VPNs allow a Juniper Networks routing platform to aggregate a set of incoming labels (labels received from a peer router) into a single forwarding label that is selected from the set of incoming labels. The single forwarding label corresponds to a single next hop for that set of labels. Label aggregation reduces the number of VPN labels that the router must examine.

For a set of labels to share an aggregate forwarding label, they must belong to the same forwarding equivalence class (FEC). The labeled packets must have the same destination egress interface.

Including the `community community-name` statement with the `aggregate-label` statement lets you specify prefixes with a common origin community. Set by policy on the peer PE, these prefixes represent an FEC on the peer PE router.



CAUTION: If the target community is set by mistake instead of the origin community, forwarding problems at the egress PE can result. All prefixes from the peer PE will appear to be in the same FEC, resulting in a single inner label for all CE routers behind a given PE in the same VPN.

To work with route reflectors in Layer 3 VPN networks, the Juniper Networks M10i router aggregates a set of incoming labels only when the routes:

- Are received from the same peer router
- Have the same site of origin community
- Have the same next hop

The next hop requirement is important because route reflectors forward routes originated from different BGP peers to another BGP peer without changing the next hop of those routes.

To configure aggregate labels for VPNs, include the *aggregate-label* statement:

```
aggregate-label {
    community community-name;
}
```

For a list of hierarchy levels at which you can include this statement, see the statement summary for this statement.

For information about how to configure a community, see [Understanding BGP Communities, Extended Communities, and Large Communities as Routing Policy Match Conditions](#).

Configuring a Signaling Protocol and LSPs for VPNs

IN THIS SECTION

- [Using LDP for VPN Signaling | 24](#)
- [Using RSVP for VPN Signaling | 26](#)

For VPNs to function, you must enable a signaling protocol, either the LDP or RSVP on the provider edge (PE) routers and on the provider (P) routers. You also need to configure label-switched paths (LSPs) between the ingress and egress routers. In a typical VPN configuration, you need to configure LSPs from each PE router to all of the other PE routers participating in the VPN in a full mesh.

NOTE: As with any configuration involving MPLS, you cannot configure any of the core-facing interfaces on the PE routers over dense Fast Ethernet PICs.

To enable a signaling protocol, perform the steps in one of the following sections:

Using LDP for VPN Signaling

To use LDP for VPN signaling, perform the following steps on the PE and provider (P) routers:

1. Configure LDP on the interfaces in the core of the service provider's network by including the `ldp` statement at the `[edit protocols]` hierarchy level.

You need to configure LDP only on the interfaces between PE routers or between PE and P routers. You can think of these as the “core-facing” interfaces. You do not need to configure LDP on the interface between the PE and customer edge (CE) routers.

```
[edit]
protocols {
  ldp {
    interface type-fpc/pic/port;
  }
}
```

2. Configure the MPLS address family on the interfaces on which you enabled LDP (the interfaces you configured in Step "1" on page 24) by including the `family mpls` statement at the `[edit interfaces type-fpc/pic/port unit logical-unit-number]` hierarchy level.

```
[edit]
interfaces {
  type-fpc/pic/port {
    unit logical-unit-number {
      family mpls;
    }
  }
}
```

```

    }
}

```

3. Configure OSPF or IS-IS on each PE and P router.

You configure these protocols at the master instance of the routing protocol, not within the routing instance used for the VPN.

- To configure OSPF, include the `ospf` statement at the `[edit protocols]` hierarchy level. At a minimum, you must configure a backbone area on at least one of the router's interfaces.

```

[edit]
protocols {
  ospf {
    area 0.0.0.0 {
      interface type-fpc/pic/port;
    }
  }
}

```

- To configure IS-IS, include the `isis` statement at the `[edit protocols]` hierarchy level and configure the loopback interface and International Organization for Standardization (ISO) family at the `[edit interfaces]` hierarchy level. At a minimum, you must enable IS-IS on the router, configure a network entity title (NET) on one of the router's interfaces (preferably the loopback interface, `lo0`), and configure the ISO family on all interfaces on which you want IS-IS to run. When you enable IS-IS, Level 1 and Level 2 are enabled by default. The following is the minimum IS-IS configuration. In the address statement, *address* is the NET.

```

[edit]
interfaces {
  lo0 {
    unit logical-unit-number {
      family iso {
        address address;
      }
    }
  }
  type-fpc/pic/port {
    unit logical-unit-number {
      family iso;
    }
  }
}

```

```

    }
  }
  protocols {
    isis {
      interface all;
    }
  }
}

```

Using RSVP for VPN Signaling

To use RSVP for VPN signaling, perform the following steps:

1. On each PE router, configure traffic engineering.

To do this, you must configure an interior gateway protocol (IGP) that supports traffic engineering (either IS-IS or OSPF) and enable traffic engineering support for that protocol.

To enable OSPF traffic engineering support, include the `traffic-engineering` statement at the `[edit protocols ospf]` hierarchy level:

```

[edit protocols ospf]
traffic-engineering {
  shortcuts;
}

```

For IS-IS, traffic engineering support is enabled by default.

2. On each PE and P router, enable RSVP on the interfaces that participate in the label-switched path (LSP).

On the PE router, these interfaces are the ingress and egress points to the LSP. On the P router, these interfaces connect the LSP between the PE routers. Do not enable RSVP on the interface between the PE and the CE routers, because this interface is not part of the LSP.

To configure RSVP on the PE and P routers, include the `interface` statement at the `[edit protocols rsvp]` hierarchy level. Include one `interface` statement for each interface on which you are enabling RSVP.

```

[edit protocols]
rsvp {
  interface interface-name;
  interface interface-name;
}

```

3. On each PE router, configure an MPLS LSP to the PE router that is the LSP's egress point.

To do this, include the `interface` and `label-switched-path` statements at the `[edit protocols mpls]` hierarchy level:

```
[edit protocols]
mpls {
  interface interface-name;
  label-switched-path path-name {
    to ip-address;
  }
}
```

In the `to` statement, specify the address of the LSP's egress point, which is an address on the remote PE router.

In the `interface` statement, specify the name of the interface (both the physical and logical portions). Include one `interface` statement for the interface associated with the LSP.

When you configure the logical portion of the same interface at the `[edit interfaces]` hierarchy level, you must also configure the `family inet` and `family mpls` statements:

```
[edit interfaces]
interface-name {
  unit logical-unit-number {
    family inet;
    family mpls;
  }
}
```

4. On all P routers that participate in the LSP, enable MPLS by including the `interface` statement at the `[edit mpls]` hierarchy level.

Include one `interface` statement for each connection to the LSP.

```
[edit]
mpls {
  interface interface-name;
  interface interface-name;
}
```

5. Enable MPLS on the interface between the PE and CE routers by including the `interface` statement at the `[edit mpls]` hierarchy level.

Doing this allows the PE router to assign an MPLS label to traffic entering the LSP or to remove the label from traffic exiting the LSP.

```
[edit]
mpls {
  interface interface-name;
}
```

For information about configuring MPLS, see the [Configuring the Ingress Router for MPLS-Signaled LSPs](#).

RELATED DOCUMENTATION

| [Configuring the Ingress Router for MPLS-Signaled LSPs](#)

Configuring Policies for the VRF Table on PE Routers in VPNs

IN THIS SECTION

- [Configuring the Route Target | 29](#)
- [Configuring the Route Origin | 29](#)
- [Configuring an Import Policy for the PE Router's VRF Table | 30](#)
- [Configuring an Export Policy for the PE Router's VRF Table | 32](#)
- [Applying Both the VRF Export and the BGP Export Policies | 34](#)
- [Configuring a VRF Target | 35](#)

On each PE router, you must define policies that define how routes are imported into and exported from the router's VRF table. In these policies, you must define the route target, and you can optionally define the route origin.

To configure policy for the VRF tables, you perform the steps in the following sections:

Configuring the Route Target

As part of the policy configuration for the VPN routing table, you must define a route target, which defines which VPN the route is a part of. When you configure different types of VPN services (Layer 2 VPNs, Layer 3 VPNs, EVPNs, or VPLS) on the same PE router, be sure to assign unique route target values to avoid the possibility of adding route and signaling information to the wrong VPN routing table.

To configure the route target, include the `target` option in the `community` statement:

```
community name members target:community-id;
```

You can include this statement at the following hierarchy levels:

- [edit policy-options]
- [edit logical-systems *logical-system-name* policy-options]

name is the name of the community.

community-id is the identifier of the community. Specify it in one of the following formats:

- *as-number:number*, where *as-number* is an AS number (a 2-byte value) and *number* is a 4-byte community value. The AS number can be in the range 1 through 65,535. We recommend that you use an IANA-assigned, nonprivate AS number, preferably the ISP's own or the customer's own AS number. The community value can be a number in the range 0 through 4,294,967,295 ($2^{32} - 1$).
- *ip-address:number*, where *ip-address* is an IPv4 address (a 4-byte value) and *number* is a 2-byte community value. The IP address can be any globally unique unicast address. We recommend that you use the address that you configure in the `router-id` statement, which is a nonprivate address in your assigned prefix range. The community value can be a number in the range 1 through 65,535.

Configuring the Route Origin

In the import and export policies for the PE router's VRF table, you can optionally assign the route origin (also known as the site of origin) for a PE router's VRF routes using a VRF export policy applied to multiprotocol external BGP (MP-EBGP) VPN IPv4 route updates sent to other PE routers.

Matching on the assigned route origin attribute in a receiving PE's VRF import policy helps ensure that VPN-IPv4 routes learned through MP-EBGP updates from one PE are not reimported to the same VPN site from a different PE connected to the same site.

To configure a route origin, complete the following steps:

1. Include the `community` statement with the `origin` option:

```
community name members origin:community-id;
```

You can include this statement at the following hierarchy levels:

- [edit policy-options]
- [edit logical-systems *logical-system-name* policy-options]

name is the name of the community.

community-id is the identifier of the community. Specify it in one of the following formats:

- *as-number.number*, where *as-number* is an AS number (a 2-byte value) and *number* is a 4-byte community value. The AS number can be in the range 1 through 65,535. We recommend that you use an IANA-assigned, nonprivate AS number, preferably the ISP's own or the customer's own AS number. The community value can be a number in the range 0 through 4,294,967,295 ($2^{32} - 1$).
- *ip-address:number*, where *ip-address* is an IPv4 address (a 4-byte value) and *number* is a 2-byte community value. The IP address can be any globally unique unicast address. We recommend that you use the address that you configure in the `router-id` statement, which is a nonprivate address in your assigned prefix range. The community value can be a number in the range 1 through 65,535.

2. Include the community in the import policy for the PE router's VRF table by configuring the `community` statement with the *community-id* identifier defined in Step "1" on page 30 at the [edit policy-options policy-statement *import-policy-name* term *import-term-name* from] hierarchy level. See ["Configuring an Import Policy for the PE Router's VRF Table" on page 30](#).

If the policy's `from` clause does not specify a community condition, the `vrf-import` statement in which the policy is applied cannot be committed. The Junos OS commit operation does not pass the validation check.

3. Include the community in the export policy for the PE router's VRF table by configuring the `community` statement with the *community-id* identifier defined in Step "1" on page 30 at the [edit policy-options policy-statement *export-policy-name* term *export-term-name* then] hierarchy level. See ["Configuring an Export Policy for the PE Router's VRF Table" on page 32](#).

See *Configuring the Route Origin for VPNs* for a configuration example.

Configuring an Import Policy for the PE Router's VRF Table

Each VPN can have a policy that defines how routes are imported into the PE router's VRF table. An import policy is applied to routes received from other PE routers in the VPN. A policy must evaluate all routes received over the IBGP session with the peer PE router. If the routes match the conditions, the

route is installed in the PE router's *routing-instance-name.inet.0* VRF table. An import policy must contain a second term that rejects all other routes.

Unless an import policy contains only a `then reject` statement, it must include a reference to a community. Otherwise, when you try to commit the configuration, the commit fails. You can configure multiple import policies.

An import policy determines what to import to a specified VRF table based on the VPN routes learned from the remote PE routers through IBGP. The IBGP session is configured at the `[edit protocols bgp]` hierarchy level. If you also configure an import policy at the `[edit protocols bgp]` hierarchy level, the import policies at the `[edit policy-options]` hierarchy level and the `[edit protocols bgp]` hierarchy level are combined through a logical AND operation. This allows you to filter traffic as a group.

To configure an import policy for the PE router's VRF table, follow these steps:

1. To define an import policy, include the `policy-statement` statement. For all PE routers, an import policy must always include the `policy-statement` statement, at a minimum:

```
policy-statement import-policy-name {
  term import-term-name {
    from {
      protocol bgp;
      community community-id;
    }
    then accept;
  }
  term term-name {
    then reject;
  }
}
```

You can include the `policy-statement` statement at the following hierarchy levels:

- `[edit policy-options]`
- `[edit logical-systems logical-system-name policy-options]`

The *import-policy-name* policy evaluates all routes received over the IBGP session with the other PE router. If the routes match the conditions in the `from` statement, the route is installed in the PE router's *routing-instance-name.inet.0* VRF table. The second term in the policy rejects all other routes.

For more information about creating policies, see the [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

2. You can optionally use a regular expression to define a set of communities to be used for the VRF import policy.

For example you could configure the following using the `community` statement at the `[edit policy-options policy-statement policy-statement-name]` hierarchy level:

```
[edit policy-options vrf-import-policy-sample]
community high-priority members *:50
```

Note that you cannot configure a regular expression as a part of a route target extended community. For more information about how to configure regular expressions for communities, see [Understanding How to Define BGP Communities and Extended Communities](#).

3. To configure an import policy, include the `vrf-import` statement:

```
vrf-import import-policy-name;
```

You can include this statement at the following hierarchy levels:

- `[edit routing-instances routing-instance-name]`
- `[edit logical-systems logical-system-name routing-instances routing-instance-name]`

Configuring an Export Policy for the PE Router's VRF Table

Each VPN can have a policy that defines how routes are exported from the PE router's VRF table. An export policy is applied to routes sent to other PE routers in the VPN. An export policy must evaluate all routes received over the routing protocol session with the CE router. (This session can use the BGP, OSPF, or Routing Information Protocol [RIP] routing protocols, or static routes.) If the routes match the conditions, the specified community target (which is the route target) is added to them and they are exported to the remote PE routers. An export policy must contain a second term that rejects all other routes.

Export policies defined within the VPN routing instance are the only export policies that apply to the VRF table. Any export policy that you define on the IBGP session between the PE routers has no effect on the VRF table. You can configure multiple export policies.

To configure an export policy for the PE router's VRF table, follow these steps:

1. For all PE routers, an export policy must distribute VPN routes to and from the connected CE routers in accordance with the type of routing protocol that you configure between the CE and PE routers within the routing instance.

To define an export policy, include the `policy-statement` statement. An export policy must always include the `policy-statement` statement, at a minimum:

```
policy-statement export-policy-name {
  term export-term-name {
    from protocol (bgp | ospf | rip | static);
    then {
      community add community-id;
      accept;
    }
  }
  term term-name {
    then reject;
  }
}
```

NOTE: Configuring the `community add` statement is a requirement for Layer 2 VPN VRF export policies. If you change the `community add` statement to the `community set` statement, the router at the egress of the Layer 2 VPN link might drop the connection.

NOTE: When configuring draft-rosen multicast VPNs operating in source-specific mode and using the `vrf-export` statement to specify the export policy, the policy must have a term that accepts routes from the `vrf-name.mdt.0` routing table. This term ensures proper PE autodiscovery using the `inet-mdt` address family.

When configuring draft-rosen multicast VPNs operating in source-specific mode and using the `vrf-target` statement, the VRF export policy is automatically generated and automatically accepts routes from the `vrf-name.mdt.0` routing table.

You can include the `policy-statement` statement at the following hierarchy levels:

- [edit `policy-options`]
- [edit `logical-systems logical-system-name policy-options`]

The `export-policy-name` policy evaluates all routes received over the routing protocol session with the CE router. (This session can use the BGP, OSPF, or RIP routing protocols, or static routes.) If the routes match the conditions in the `from` statement, the community target specified in the `then community add` statement is added to them and they are exported to the remote PE routers. The second term in the policy rejects all other routes.

For more information about creating policies, see the [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

2. To apply the policy, include the `vrf-export` statement:

```
vrf-export export-policy-name;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

Applying Both the VRF Export and the BGP Export Policies

When you apply a VRF export policy as described in "[Configuring an Export Policy for the PE Router's VRF Table](#)" on page 32, routes from VPN routing instances are advertised to other PE routers based on this policy, whereas the BGP export policy is ignored.

If you include the `vpn-apply-export` statement in the BGP configuration, both the VRF export and BGP group or neighbor export policies are applied (VRF first, then BGP) before routes are advertised in the VPN routing tables to other PE routers.

NOTE: When a PE device is also acting as a Route Reflector (RR) or an Autonomous system boundary router (ASBR) in a Carrier-over-Carrier or inter-AS VPN, the next-hop manipulation in the `vrf-export` policy is ignored.

When you include the `vpn-apply-export` statement, be aware of the following:

- Routes imported into the `bgp.l3vpn.0` routing table retain the attributes of the original routes (for example, an OSPF route remains an OSPF route even when it is stored in the `bgp.l3vpn.0` routing table). You should be aware of this when you configure an export policy for connections between an IBGP PE router and a PE router, a route reflector and a PE router, or AS boundary router (ASBR) peer routers.
- By default, all routes in the `bgp.l3vpn.0` routing table are exported to the IBGP peers. If the last statement of the export policy is `deny all` and if the export policy does not specifically match on routes in the `bgp.l3vpn.0` routing table, no routes are exported.

To apply both the VRF export and BGP export policies to VPN routes, include the `vpn-apply-export` statement:

```
vpn-apply-export;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

Configuring a VRF Target

Including the `vrf-target` statement in the configuration for a VRF target community causes default VRF import and export policies to be generated that accept and tag routes with the specified target community. You can still create more complex policies by explicitly configuring VRF import and export policies. These policies override the default policies generated when you configure the `vrf-target` statement.

If you do not configure the `import` and `export` options of the `vrf-target` statement, the specified community string is applied in both directions. The `import` and `export` keywords give you more flexibility, allowing you to specify a different community for each direction.

The syntax for the VRF target community is not a name. You must specify it in the format `target:x.y`. A community name cannot be specified because this would also require you to configure the community members for that community using the `policy-options` statement. If you define the `policy-options` statements, then you can just configure VRF import and export policies as usual. The purpose of the `vrf-target` statement is to simplify the configuration by allowing you to configure most statements at the `[edit routing-instances]` hierarchy level.

To configure a VRF target, include the `vrf-target` statement:

```
vrf-target community;
```

You can include this statement at the following hierarchy levels:

- `[edit routing-instances routing-instance-name]`
- `[edit logical-systems logical-system-name routing-instances routing-instance-name]`

An example of how you might configure the `vrf-target` statement follows:

```
[edit routing-instances sample]
vrf-target target:69:102;
```

To configure the `vrf-target` statement with the `export` and `import` options, include the following statements:

```
vrf-target {  
    export community-name;  
    import community-name;  
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

Configuring the Route Origin for VPNs


IN THIS SECTION

- [Configuring the Site of Origin Community on CE Router A | 37](#)
- [Configuring the Community on CE Router A | 38](#)
- [Applying the Policy Statement on CE Router A | 38](#)
- [Configuring the Policy on PE Router D | 39](#)
- [Configuring the Community on PE Router D | 40](#)
- [Applying the Policy on PE Router D | 40](#)

You can use route origin to prevent routes learned from one customer edge (CE) router marked with origin community from being advertised back to it from another CE router in the same AS.

In the example, the route origin is used to prevent routes learned from CE Router A that are marked with origin community from being advertised back to CE Router E by AS 200. The example topology is shown in [Figure 3 on page 37](#).

Figure 3: Network Topology of Site of Origin Example



In this topology, CE Router A and CE Router E are in the same AS (AS200). They use EBGP to exchange routes with their respective provider edge (PE) routers, PE Router B and PE Router D. The two CE routers have a back connection.

The following sections describe how to configure the route origin for a group of VPNs:

Configuring the Site of Origin Community on CE Router A

The following section describes how to configure CE Router A to advertise routes with a site of origin community to PE Router B for this example.

NOTE: In this example, direct routes are configured to be advertised, but any route can be configured.

Configure a policy to advertise routes with my-soo community on CE Router A as follows:

```
[edit]
policy-options {
  policy-statement export-to-my-isp {
    term a {
      from {
        protocol direct;
      }
      then {
        community add my-soo;
        accept;
      }
    }
  }
}
```



```

    }
  }
}

```

Configuring the Community on CE Router A

Configure the `my-soo` community on CE Router A as follows:

```

[edit]
policy-options {
  community my-soo {
    members origin:100:1;
  }
}

```

Applying the Policy Statement on CE Router A

Apply the `export-to-my-isp` policy statement as an export policy to the EBGP peering on the CE Router A as follows:

```

[edit]
protocols {
  bgp {
    group my_isp {
      export export-to-my-isp;
    }
  }
}

```

When you issue the `show route receive-protocol bgp detail` command, you should see the following routes originated from PE Router B with `my-soo` community:

```

user@host> show route receive-protocol bgp 10.12.99.2 detail
inet.0: 16 destinations, 16 routes (15 active, 0 holddown, 1 hidden)
inet.3: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
vpn_blue.inet.0: 8 destinations, 10 routes (8 active, 0 holddown, 0 hidden)
* 10.12.33.0/30 (2 entries, 1 announced)
  Nexthop: 10.12.99.2
  AS path: 100 I

```

```

Communities: origin:100:1
10.12.99.0/30 (2 entries, 1 announced)
  Nexthop: 10.12.99.2
  AS path: 100 I
  Communities: origin:100:1
* 10.255.71.177/32 (1 entry, 1 announced)
  Nexthop: 10.12.99.2
  AS path: 100 I
  Communities: origin:100:1
* 192.168.64.0/21 (1 entry, 1 announced)
  Nexthop: 10.12.99.2
  AS path: 100 I
  Communities: origin:100:1
iso.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
mpls.0: 8 destinations, 8 routes (8 active, 0 holddown, 0 hidden)
bgp.l3vpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
inet6.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
__juniper_private1__.inet6.0: 1 destinations, 1 routes (1 active, 0 holddown, 0
hidden)

```

Configuring the Policy on PE Router D

Configure a policy on PE Router D that prevents routes with `my-soo` community tagged by CE Router A from being advertised to CE Router E as follows:

```

[edit]
policy-options {
  policy-statement soo-ce1-policy {
    term a {
      from {
        community my-soo;
      }
      then {
        reject;
      }
    }
  }
}

```

Configuring the Community on PE Router D

Configure the community on PE Router D as follows:

```
[edit]
policy-options {
  community my-soo {
    members origin:100:1;
  }
}
```

Applying the Policy on PE Router D

To prevent routes learned from CE Router A from being advertised to CE Router E (the two routers can communicate these routes directly), apply the `soo-ce1-policy` policy statement as an export policy to the PE Router D and CE Router E EBGP session `vpn_blue`.

View the EBGP session on PE Router D using the `show routing-instances` command.

```
user@host# show routing-instances
vpn_blue {
  instance-type vrf;
  interface fe-2/0/0.0;
  vrf-target target:100:200;
  protocols {
    bgp {
      group ce2 {
        advertise-peer-as;
        peer-as 100;
        neighbor 10.12.99.6;
      }
    }
  }
}
```

Apply the `soo-ce1-policy` policy statement as an export policy to the PE Router D and CE Router E EBGP session `vpn_blue` as follows:

```
[edit routing-instances]
vpn_blue {
```

```
protocols {  
  bgp {  
    group ce2{  
      export soo-ce1-policy;  
    }  
  }  
}
```

Distributing VPN Routes with Target Filtering

IN THIS CHAPTER

- [Configuring BGP Route Target Filtering for VPNs | 42](#)
- [Example: BGP Route Target Filtering for VPNs | 44](#)
- [Example: Configuring BGP Route Target Filtering for VPNs | 47](#)
- [Configuring Static Route Target Filtering for VPNs | 59](#)
- [Understanding Proxy BGP Route Target Filtering for VPNs | 60](#)
- [Example: Configuring Proxy BGP Route Target Filtering for VPNs | 61](#)
- [Example: Configuring an Export Policy for BGP Route Target Filtering for VPNs | 83](#)
- [Reducing Network Resource Use with Static Route Target Filtering for VPNs | 107](#)

Configuring BGP Route Target Filtering for VPNs

IN THIS SECTION

- [BGP Route Target Filtering Overview | 43](#)
- [Configuring BGP Route Target Filtering for VPNs | 43](#)

BGP route target filtering allows you to distribute VPN routes to only the routers that need them. In VPN networks without BGP route target filtering configured, BGP distributes all VPN routes to all VPN peer routers.

For more information about BGP route target filtering, see RFC 4684, *Constrained Route Distribution for Border Gateway Protocol/MultiProtocol Label Switching (BGP/MPLS) Internet Protocol (IP) Virtual Private Networks (VPNs)*.

The following sections provide an overview of BGP route target filtering and how to configure it for VPNs:

BGP Route Target Filtering Overview

PE routers, unless they are configured as route reflectors or are running an EBGp session, discard any VPN routes that do not include a route target extended community as specified in the local VRF import policies. This is the default behavior of the Junos OS.

However, unless it is explicitly configured not to store VPN routes, any router configured either as a route reflector or border router for a VPN address family must store all of the VPN routes that exist in the service provider's network. Also, though PE routers can automatically discard routes that do not include a route target extended community, route updates continue to be generated and received.

By reducing the number of routers receiving VPN routes and route updates, BGP route target filtering helps to limit the amount of overhead associated with running a VPN. BGP route target filtering is most effective at reducing VPN-related administrative traffic in networks where there are many route reflectors or AS border routers that do not participate in the VPNs directly (not acting as PE routers for the CE devices).

BGP route target filtering uses standard UPDATE messages to distribute route target extended communities between routers. The use of UPDATE messages allows BGP to use its standard loop detection mechanisms, path selection, policy support, and database exchange implementation.

Configuring BGP Route Target Filtering for VPNs

BGP route target filtering is enabled through the exchange of the route-target address family, stored in the `bgp.rtarget.0` routing table. Based on the route-target address family, the route target NLRI (address family indicator [AFI]=1, subsequent AFI [SAFI]=132) is negotiated with its peers.

On a system that has locally configured VRF instances, BGP automatically generates local routes corresponding to targets referenced in the `vrf-import` policies.

To configure BGP route target filtering, include the `family route-target` statement:

```
family route-target {  
    advertise-default;  
    external-paths number;  
    prefix-limit number;  
}
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

The `advertise-default`, `external-paths`, and `prefix-limit` statements affect the BGP route target filtering configuration as follows:

- The `advertise-default` statement causes the router to advertise the default route target route (0:0:0/0) and suppress all routes that are more specific. This can be used by a route reflector on BGP groups consisting of neighbors that act as PE routers only. PE routers often need to advertise all routes to the route reflector.

Suppressing all route target advertisements other than the default route reduces the amount of information exchanged between the route reflector and the PE routers. The Junos OS further helps to reduce route target advertisement overhead by not maintaining dependency information unless a nondefault route is received.

- The `external-paths` statement (which has a default value of 1) causes the router to advertise the VPN routes that reference a given route target. The number you specify determines the number of external peer routers (currently advertising that route target) that receive the VPN routes.
- The `prefix-limit` statement limits the number of prefixes that can be received from a peer router.

The `route-target`, `advertise-default`, and `external-path` statements affect the RIB-OUT state and must be consistent between peer routers that share the same BGP group. The `prefix-limit` statement affects the receive side only and can have different settings between different peer routers in a BGP group.

RELATED DOCUMENTATION

| *Configuring the Route Origin for VPNs*

Example: BGP Route Target Filtering for VPNs

BGP route target filtering is enabled by configuring the `family route-target` statement at the appropriate BGP hierarchy level. This statement enables the exchange of a new `route-target` address family, which is stored in the `bgp.rtarget.0` routing table.

The following configuration illustrates how you could configure BGP route target filtering for a BGP group titled `to_vpn04`:

```
[edit]
protocols {
  bgp {
    group to_vpn04 {
      type internal;
      local-address 10.255.14.182;
      peer-as 200;
      neighbor 10.255.14.174 {
```

```

        family inet-vpn {
            unicast;
        }
        family route-target;
    }
}
}
}
}

```

The following configuration illustrates how you could configure a couple of local VPN routing and forwarding (VRF) routing instances to take advantage of the functionality provided by BGP route target filtering. Based on this configuration, BGP would automatically generate local routes corresponding to the route targets referenced in the VRF import policies (note the targets defined by the `vrf-target` statements).

```

[edit]
routing-instances {
    vpn1 {
        instance-type vrf;
        interface t1-0/1/2.0;
        vrf-target target:200:101;
        protocols {
            ospf {
                export bgp-routes;
                area 0.0.0.0 {
                    interface t1-0/1/2.0;
                }
            }
        }
    }
    vpn2 {
        instance-type vrf;
        interface t1-0/1/2.1;
        vrf-target target:200:102;
        protocols {
            ospf {
                export bgp-routes;
                area 0.0.0.0 {
                    interface t1-0/1/2.1;
                }
            }
        }
    }
}

```



```
}
}
```

Issue the **show route table bgp.rtarget.0** show command to verify the BGP route target filtering configuration:

```
user@host> show route table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 6 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both
200:200:101/96
    *[RTarget/5] 00:10:00
    Local
200:200:102/96
    *[RTarget/5] 00:10:00
    Local
200:200:103/96
    *[BGP/170] 00:09:48, localpref 100, from 10.255.14.174
    AS path: I
    > t3-0/0/0.0
200:200:104/96
    *[BGP/170] 00:09:48, localpref 100, from 10.255.14.174
    AS path: I
    > t3-0/0/0.0
```

The show command display format for route target prefixes is:

AS number:route target extended community/length

The first number represents the autonomous system (AS) of the router that sent this advertisement. The remainder of the display follows the Junos show command convention for extended communities.

The output from the show route table bgp-rtarget.0 command displays the locally generated and remotely generated routes.

The first two entries correspond to the route targets configured for the two local VRF routing instances (vpn1 and vpn2):

- 200:200:101/96—Community 200:101 in the vpn1 routing instance
- 200:200:102/96—Community 200:102 in the vpn2 routing instance

The last two entries are prefixes received from a BGP peer:

- 200:200:103/96—Tells the local router that routes tagged with this community (200:103) should be advertised to peer 10.255.14.174 through t3-0/0/0.0
- 200:200:104/96—Tells the local router that routes tagged with this community (200:104) should be advertised to peer 10.255.14.174 through t3-0/0/0.0

Example: Configuring BGP Route Target Filtering for VPNs


IN THIS SECTION

- [Configure BGP Route Target Filtering on Router PE1 | 48](#)
- [Configure BGP Route Target Filtering on Router PE2 | 51](#)
- [Configure BGP Route Target Filtering on the Route Reflector | 54](#)
- [Configure BGP Route Target Filtering on Router PE3 | 56](#)

BGP route target filtering reduces the number of routers that receive VPN routes and route updates, helping to limit the amount of overhead associated with running a VPN. BGP route target filtering is most effective at reducing VPN-related administrative traffic in networks where there are many route reflectors or AS border routers that do not participate in the VPNs directly (do not act as PE routers for the CE devices).

Figure 4 on page 48 illustrates the topology for a network configured with BGP route target filtering for a group of VPNs.

Figure 4: BGP Route Target Filtering Enabled for a Group of VPNs



The following sections describe how to configure BGP route target filtering for a group of VPNs:

Configure BGP Route Target Filtering on Router PE1

This section describes how to enable BGP route target filtering on Router PE1 for this example.

Configure the routing options on router PE1 as follows:

```
[edit]
routing-options {
  route-distinguisher-id 10.255.14.182;
  autonomous-system 198;
}
```

Configure the BGP protocol on Router PE1 as follows:

```
[edit]
protocols {
  bgp {
    group to_VPN_D {
      type internal;
      local-address 10.255.14.182;
    }
  }
}
```

```

        peer-as 198;
        neighbor 10.255.14.174 {
            family inet-vpn {
                unicast;
            }
            family route-target;
        }
    }
}

```

Configure the vpn1 routing instance as follows:

```

[edit]
routing-instances {
    vpn1 {
        instance-type vrf;
        interface t1-0/1/2.0;
        vrf-target target:198:101;
        protocols {
            ospf {
                export bgp-routes;
                area 0.0.0.0 {
                    interface t1-0/1/2.0;
                }
            }
        }
    }
}

```

Configure the vpn2 routing instance on Router PE1 as follows:

```

[edit]
routing-instances {
    vpn2 {
        instance-type vrf;
        interface t1-0/1/2.1;
        vrf-target target:198:102;
        protocols {
            ospf {
                export bgp-routes;
            }
        }
    }
}

```

```

        area 0.0.0.0 {
            interface t1-0/1/2.1;
        }
    }
}
}
}
}

```

Once you have implemented this configuration, you should see the following when you issue a `show route table bgp.rtarget.0` command:

```

user@host> show route table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 6 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

198.198:101/96
    *[RTarget/5] 00:27:42
        Local
        [BGP/170] 00:27:30, localpref 100, from
10.255.14.174
        AS path: I
        > via t3-0/0/0.0
198.198:102/96
    *[RTarget/5] 00:27:42
        Local
        [BGP/170] 00:27:30, localpref 100, from
10.255.14.174
        AS path: I
        > via t3-0/0/0.0
198.198:103/96
    *[BGP/170] 00:27:30, localpref 100, from
10.255.14.174
        AS path: I
        > via t3-0/0/0.0
198.198:104/96
    *[BGP/170] 00:27:30, localpref 100, from
10.255.14.174
        AS path: I
        > via t3-0/0/0.0

```

Configure BGP Route Target Filtering on Router PE2

This section describes how to enable BGP route target filtering on Router PE2 for this example.

Configure the routing options on Router PE2 as follows:

```
[edit]
routing-options {
  route-distinguisher-id 10.255.14.176;
  autonomous-system 198;
}
```

Configure the BGP protocol on Router PE2 as follows:

```
[edit]
protocols {
  bgp {
    group to_vpn04 {
      type internal;
      local-address 10.255.14.176;
      peer-as 198;
      neighbor 10.255.14.174 {
        family inet-vpn {
          unicast;
        }
        family route-target;
      }
    }
  }
}
```

Configure the vpn1 routing instance on Router PE2 as follows:

```
[edit]
routing-instances {
  vpn1 {
    instance-type vrf;
    interface t3-0/0/0.0;
    vrf-target target:198:101;
    protocols {
      bgp {
```

```

        group vpn1 {
            type external;
            peer-as 101;
            as-override;
            neighbor 10.49.11.2;
        }
    }
}

```

Configure the vpn2 routing instance on Router PE2 as follows:

```

[edit]
routing-instances {
    vpn2 {
        instance-type vrf;
        interface t3-0/0/0.1;
        vrf-target target:198:102;
        protocols {
            bgp {
                group vpn2 {
                    type external;
                    peer-as 102;
                    as-override;
                    neighbor 10.49.21.2;
                }
            }
        }
    }
}

```

Configure the vpn3 routing instance on Router PE2 as follows:

```

[edit]
routing-instances {
    vpn3 {
        instance-type vrf;
        interface t3-0/0/0.2;
        vrf-import vpn3-import;
        vrf-export vpn3-export;
    }
}

```

```

    protocols {
        bgp {
            group vpn3 {
                type external;
                peer-as 103;
                as-override;
                neighbor 10.49.31.2;
            }
        }
    }
}

```

Once you have configured router PE2 in this manner, you should see the following when you issue the `show route table bgp.rtarget.0` command:

```

user@host> show route table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 7 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

198.198:101/96
    *[RTarget/5] 00:28:15
        Local
        [BGP/170] 00:28:03, localpref 100, from
10.255.14.174
    AS path: I
    > via t1-0/1/0.0
198.198:102/96
    *[RTarget/5] 00:28:15
        Local
        [BGP/170] 00:28:03, localpref 100, from
10.255.14.174
    AS path: I
    > via t1-0/1/0.0
198.198:103/96
    *[RTarget/5] 00:28:15
        Local
        [BGP/170] 00:28:03, localpref 100, from
10.255.14.174
    AS path: I
    > via t1-0/1/0.0
198.198:104/96

```



```

*[BGP/170] 00:28:03, localpref 100, from
10.255.14.174
      AS path: I
      > via t1-0/1/0.0

```

Configure BGP Route Target Filtering on the Route Reflector

This section illustrates how to enable BGP route target filtering on the route reflector for this example.

Configure the routing options on the route reflector as follows:

```

[edit]
routing-options {
  route-distinguisher-id 10.255.14.174;
  autonomous-system 198;
}

```

Configure the BGP protocol on the route reflector as follows:

```

[edit]
protocols {
  bgp {
    group rr-group {
      type internal;
      local-address 10.255.14.174;
      cluster 10.255.14.174;
      peer-as 198;
      neighbor 10.255.14.182 {
        description to_PE1_vpn12;
        family inet-vpn {
          unicast;
        }
        family route-target;
      }
      neighbor 10.255.14.176 {
        description to_PE2_vpn06;
        family inet-vpn {
          unicast;
        }
        family route-target;
      }
    }
  }
}

```

```

        neighbor 10.255.14.178 {
            description to_PE3_vpn08;
            family inet-vpn {
                unicast;
            }
            family route-target;
        }
    }
}
}

```

Once you have configured the route reflector in this manner, you should see the following when you issue the `show route table bgp.rtarget.0` command:

```

user@host> show route table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 8 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

198.198:101/96
    * [BGP/170] 00:29:03, localpref 100, from
    10.255.14.176
        AS path: I
        > via t1-0/2/0.0
        [BGP/170] 00:29:03, localpref 100, from
    10.255.14.178
        AS path: I
        > via t3-0/1/1.0
        [BGP/170] 00:29:03, localpref 100, from
    10.255.14.182
        AS path: I
        > via t3-0/1/3.0

198.198:102/96
    * [BGP/170] 00:29:03, localpref 100, from
    10.255.14.176
        AS path: I
        > via t1-0/2/0.0
        [BGP/170] 00:29:03, localpref 100, from
    10.255.14.182
        AS path: I
        > via t3-0/1/3.0

198.198:103/96
    * [BGP/170] 00:29:03, localpref 100, from

```

```

10.255.14.176
    AS path: I
    > via t1-0/2/0.0
    [BGP/170] 00:29:03, localpref 100, from
10.255.14.178
    AS path: I
    > via t3-0/1/1.0
198.198:104/96
    *[BGP/170] 00:29:03, localpref 100, from
10.255.14.178
    AS path: I
    > via t3-0/1/1.0

```

Configure BGP Route Target Filtering on Router PE3

The following section describes how to enable BGP route target filtering on Router PE3 for this example.

Configure the routing options on Router PE3 as follows:

```

[edit]
routing-options {
    route-distinguisher-id 10.255.14.178;
    autonomous-system 198;
}

```

Configure the BGP protocol on Router PE3 as follows:

```

[edit]
protocols {
    bgp {
        group to_vpn04 {
            type internal;
            local-address 10.255.14.178;
            peer-as 198;
            neighbor 10.255.14.174 {
                family inet-vpn {
                    unicast;
                }
                family route-target;
            }
        }
    }
}

```

```

    }
  }
}

```

Configure the vpn1 routing instance on Router PE3 as follows:

```

[edit]
routing-instances {
  vpn1 {
    instance-type vrf;
    interface t3-0/0/0.0;
    vrf-target target:198:101;
    protocols {
      rip {
        group vpn1 {
          export bgp-routes;
          neighbor t3-0/0/0.0;
        }
      }
    }
  }
}

```

Configure the vpn3 routing instance on Router PE3 as follows:

```

[edit]
routing-instances {
  vpn3 {
    instance-type vrf;
    interface t3-0/0/0.1;
    vrf-target target:198:103;
    protocols {
      rip {
        group vpn3 {
          export bgp-routes;
          neighbor t3-0/0/0.1;
        }
      }
    }
  }
}

```

Configure the vpn4 routing instance on Router PE3 as follows:

```
[edit]
routing-instances {
  vpn4 {
    instance-type vrf;
    interface t3-0/0/0.2;
    vrf-target target:198:104;
    protocols {
      rip {
        group vpn4 {
          export bgp-routes;
          neighbor t3-0/0/0.2;
        }
      }
    }
  }
}
```

Once you have configured Router PE3 in this manner, you should see the following when you issue the `show route table bgp.rtarget.0` command:

```
user@host> show route table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 7 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

198.198:101/96
    * [RTarget/5] 00:29:42
        Local
    [BGP/170] 00:29:30, localpref 100, from
10.255.14.174
    AS path: I
    > via t3-0/0/1.0

198.198:102/96
    * [BGP/170] 00:29:29, localpref 100, from
10.255.14.174
    AS path: I
    > via t3-0/0/1.0

198.198:103/96
    * [RTarget/5] 00:29:42
        Local
```

```

10.255.14.174      [BGP/170] 00:29:30, localpref 100, from
                  AS path: I
                  > via t3-0/0/1.0
198.198:104/96    *[RTarget/5] 00:29:42
                  Local
                  [BGP/170] 00:29:30, localpref 100, from
10.255.14.174      AS path: I
                  > via t3-0/0/1.0

```

Configuring Static Route Target Filtering for VPNs

The BGP VPN route target extended community (RFC 4360, *BGP Extended Communities Attribute*) is used to determine VPN membership. Static route target filtering helps to prevent resources from being consumed in portions of the network where the VPN routes are not needed due to the lack of member PE routers (RFC 4684, *Constrained Route Distribution for Border Gateway Protocol/MultiProtocol Label Switching (BGP/MPLS) Internet Protocol (IP) Virtual Private Networks (VPNs)*). Routers can originate routes into the RT-Constrain protocol to indicate their interest in receiving VPN routes containing route targets that match the RT-Constrain NLRI.

To configure static route target filtering for VPNs:

- Configure the route-target-filter statement at the [edit routing-options rib bgp.rtarget.0 static] hierarchy level.

The following example illustrates how you could configure the ["route-target-filter" on page 1414](#) statement:

```

[edit routing-options rib bgp.rtarget.0 static]
route-target-filter destination {
  group bgp-group;
  local;
  neighbor bgp-peer;
}

```

- You can display route target filtering information using the `show bgp group rtf detail` command.

Understanding Proxy BGP Route Target Filtering for VPNs

BGP route target filtering (also known as route target constrain, or RTC) allows you to distribute VPN routes to only the devices that need them. In VPN networks without BGP route target filtering configured, BGP distributes all VPN routes to all VPN peer devices, which can strain network resources. The route target filtering feature was introduced to reduce the number of devices receiving VPN routes and VPN routing updates, thereby limiting the amount of overhead associated with running a VPN. The Junos OS implementation for BGP route target filtering is based on RFC 4684, *Constrained Route Distribution for Border Gateway Protocol/MultiProtocol Label Switching (BGP/MPLS) Internet Protocol (IP) Virtual Private Networks (VPNs)*.

What if you have a network environment where route target filtering is not widely deployed, or what if some devices do not support route target filtering? For example, you might have a BGP speaker with route target filtering enabled that is peered with a BGP speaker that does not support or have route target filtering configured. In this case, the BGP speaker with route target filtering configured must advertise default route target membership (RT membership) on behalf of its peer. The route target filtering resource savings are unrealized because the device supporting the filtering must now send all VPN routes to the device that does not support the filter. Proxy BGP route target filtering (or Proxy RTC) permits the generation of RT membership for devices that do not support route target filtering. This eases the deployment of route target filtering in networks where it is incompletely deployed or not fully supported.

Proxy BGP route target filtering allows you to distribute proxy RT membership advertisements created from the received BGP VPN routes to other devices in the network that need them. These are known as proxy advertisements because the device creates the RT membership on behalf of its peers without the route target filtering functionality. Proxy BGP route target filtering uses BGP route target extended communities that are exported to a specific BGP speaker to generate the route targets. Generated proxy RTC routes are stored in the `bgp.target.0` routing table.

You can also configure a policy to control which VPN routes are used to generate the proxy RTC routes. This can help control which RT membership is generated by the proxying device. In addition, you can configure a policy to reduce the memory overhead associated with proxy RTC. Proxy RTC only uses additional memory on a per-VPN route basis when it is permitted by a policy to be used for generating RT membership.

Example: Configuring Proxy BGP Route Target Filtering for VPNs

IN THIS SECTION

- [Requirements | 61](#)
- [Overview | 62](#)
- [Configuration | 64](#)
- [Verification | 82](#)

This example shows how to configure proxy BGP route target filtering (also known as proxy route target constrain, or proxy RTC).

Requirements

This example uses the following hardware and software components:

- Four Juniper Networks devices that can be a combination of M Series, MX Series, or T Series routers.
- Junos OS Release 12.2 or later on one or more devices configured for proxy BGP route filtering. In this example, you explicitly configure proxy BGP route filtering on the route reflectors.

Before configuring proxy BGP route target filtering, make sure that you are familiar with and understand the following concepts:

- ["Layer 2 VPNs" on page 143](#)
- *Understanding Layer 3 VPNs*
- *Understanding VPN-IPv4 Addresses and Route Distinguishers*
- *Configuring Policies for the VRF Table on PE Routers in VPNs*
- *Configuring BGP Route Target Filtering for VPNs*
- [BGP extended communities](#)

Overview

IN THIS SECTION

- [Topology Diagram | 63](#)

Route target filtering decreases the number of devices in a network that receive VPN routes that are not needed. Proxy BGP route target filtering allows networks to take advantage of route target filtering in locations where the feature is not currently supported. By configuring this feature, you can realize many of the same network resource savings that are available to you if your network fully supported BGP route target filtering.

To configure proxy BGP route target filtering, you include the `family route-target proxy-generate` statement on the devices that will distribute proxy route target membership (RT membership) advertisements for the devices that do not support BGP route target filtering. The proxy BGP route target filtering routes are then stored in the `bgp.rtarget.0` routing table.


Proxy BGP route target filtering is intended to create RT membership advertisements for devices that do not support the BGP route target filtering feature. If the `proxy-generate` statement is present, but the route target family is negotiated with the BGP peer, the `proxy-generate` functionality is disabled. This allows simplified configuration of BGP peer groups where a portion of the peers in the group support route target filtering but others do not. In such an example case, the `family route-target proxy-generate` statement might be part of the BGP peer group configuration.

NOTE: When deploying proxy BGP route target filtering in your network, the `advertise-default` statement for BGP route target filtering causes the device to advertise the default route target route (0:0:0/0) and suppress all routes that are more specific. If you have proxy BGP route target filtering configured on one device and one or more peers have the `advertise-default` statement configured as part of their BGP route target filtering configuration, the `advertise-default` configuration is ignored.

Topology Diagram

Figure 5 on page 63 shows the topology used in this example.

Figure 5: Proxy BGP Route Target Filtering Topology



In this example, BGP route target filtering is configured on the route reflectors (Device RR1 and Device RR2) and the provider edge (PE) Device PE2, but the other PE, Device PE1, does not support the BGP route target filtering functionality. Device PE2 has four VPNs configured (vpn1, vpn2, vpn3, and vpn4). Device PE1 has two VPNs configured (vpn1 and vpn2), so this device is only interested in receiving route updates for vpn1 and vpn2. Currently, this is impossible because both route reflectors (Device RR1 and Device RR2) learn and share information about all of the incoming VPN routes (vpn1 through vpn4) with Device PE1. In the sample topology, all devices participate in autonomous system (AS) 203, OSPF is the configured interior gateway protocol (IGP), and LDP is the signaling protocol used by the VPNs. In this example, we use static routes in the VPN routing and forwarding (VRF) instances to generate VPN routes. This is done in place of using a PE to customer edge (CE) protocol such as OSPF or BGP.

To minimize the number of VPN route updates being processed by Device PE1, you include the `family route-target proxy-generate` statement to configure proxy BGP route target filtering on each route reflector. Each route reflector has a peering session with Device PE1 and supports route target filtering to the core. However, Device PE1 does not support route target filtering, so the network resource savings are unrealized by Device PE1 since it receives all of the VPN updates. By configuring proxy BGP route target filtering on the peering sessions facing Device PE1, you limit the number of VPN updates processed by Device PE1, and the route reflectors generate the proxy BGP route target routes for Device PE1 throughout the network.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 64](#)
- [Configuring Device PE1 | 67](#)
- [Configuring Device RR1 | 71](#)
- [Configuring Device RR2 | 74](#)
- [Configuring Device PE2 | 77](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device PE1

```
set interfaces ge-1/0/0 unit 0 description PE1-to-RR1
set interfaces ge-1/0/0 unit 0 family inet address 10.49.0.1/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description PE1-to-RR2
set interfaces ge-1/0/1 unit 0 family inet address 10.49.10.1/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.255.163.58
set protocols bgp group internal neighbor 10.255.165.220 family inet-vpn unicast
set protocols bgp group internal neighbor 10.255.165.28 family inet-vpn unicast
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.163.58
set routing-options autonomous-system 203
set routing-instances vpn1 instance-type vrf
set routing-instances vpn1 vrf-target target:203:100
set routing-instances vpn1 routing-options static route 203.0.113.1/24 discard
```

```

set routing-instances vpn2 instance-type vrf
set routing-instances vpn2 vrf-target target:203:101
set routing-instances vpn2 routing-options static route 203.0.113.2/24 discard

```

Device RR1

```

set interfaces ge-1/0/0 unit 0 description RR1-to-PE1
set interfaces ge-1/0/0 unit 0 family inet address 10.49.0.2/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description RR1-to-PE2
set interfaces ge-1/0/1 unit 0 family inet address 10.50.0.2/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 198.51.100.1
set protocols bgp group internal cluster 198.51.100.1
set protocols bgp group internal neighbor 10.255.163.58 description vpn1-to-pe1 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.163.58 family route-target proxy-generate
set protocols bgp group internal neighbor 10.255.168.42 description vpn1-to-pe2 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.168.42 family route-target
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.165.220
set routing-options autonomous-system 203

```

Device RR2

```

set interfaces ge-1/0/0 unit 0 description RR2-to-PE1
set interfaces ge-1/0/0 unit 0 family inet address 10.49.10.2/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description RR2-to-PE2
set interfaces ge-1/0/1 unit 0 family inet address 10.50.10.2/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.255.165.28

```

```

set protocols bgp group internal cluster 198.51.100.1
set protocols bgp group internal neighbor 10.255.163.58 description vpn2-to-pe1 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.163.58 family route-target proxy-generate
set protocols bgp group internal neighbor 10.255.168.42 description vpn2-to-pe2 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.168.42 family route-target
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.165.28
set routing-options autonomous-system 203

```

Device PE2

```

set interfaces ge-1/0/0 unit 0 description PE2-to-RR1
set interfaces ge-1/0/0 unit 0 family inet address 10.50.0.1/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description PE2-to-RR2
set interfaces ge-1/0/1 unit 0 family inet address 10.50.10.1/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.255.168.42
set protocols bgp group internal family inet-vpn unicast
set protocols bgp group internal family route-target
set protocols bgp group internal neighbor 10.255.165.220
set protocols bgp group internal neighbor 10.255.165.28
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.168.42
set routing-options autonomous-system 203
set routing-instances vpn1 instance-type vrf
set routing-instances vpn1 vrf-target target:203:100
set routing-instances vpn1 routing-options static route 203.0.113.1/24 discard
set routing-instances vpn2 instance-type vrf
set routing-instances vpn2 vrf-target target:203:101
set routing-instances vpn2 routing-options static route 203.0.113.2/24 discard
set routing-instances vpn3 instance-type vrf
set routing-instances vpn3 vrf-target target:203:103

```

```

set routing-instances vpn3 routing-options static route 203.0.113.3/24 discard
set routing-instances vpn4 instance-type vrf
set routing-instances vpn4 vrf-target target:203:104
set routing-instances vpn4 routing-options static route 203.0.113.4/24 discard

```

Configuring Device PE1

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device PE1:

1. Configure the interfaces.

```

[edit interfaces]
user@PE1# set ge-1/0/0 unit 0 description PE1-to-RR1
user@PE1# set ge-1/0/0 unit 0 family inet address 10.49.0.1/30
user@PE1# set ge-1/0/0 unit 0 family mpls
user@PE1# set ge-1/0/1 unit 0 description PE1-to-RR2
user@PE1# set ge-1/0/1 unit 0 family inet address 10.49.10.1/30
user@PE1# set ge-1/0/1 unit 0 family mpls

```

2. Configure the route distinguisher and the AS number.

```

[edit routing-options]
user@PE1# set route-distinguisher-id 10.255.163.58
user@PE1# set autonomous-system 203

```

3. Configure LDP as the signaling protocol used by the VPN.

```

[edit protocols ldp]
user@PE1# set interface ge-1/0/0
user@PE1# set interface ge-1/0/1

```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@PE1# set type internal
user@PE1# set local-address 10.255.163.58
user@PE1# set neighbor 10.255.165.220 family inet-vpn unicast
user@PE1# set neighbor 10.255.165.28 family inet-vpn unicast
```

5. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@PE1# set interface ge-1/0/0
user@PE1# set interface ge-1/0/1
user@PE1# set interface lo0.0 passive
```

6. Configure the VPN routing instances.

```
[edit routing-instances vpn1]
user@PE1# set instance-type vrf
user@PE1# set vrf-target target:203:100
user@PE1# set routing-options static route 203.0.113.1/24 discard
```

```
[edit routing-instances vpn2]
user@PE1# set instance-type vrf
user@PE1# set vrf-target target:203:101
user@PE1# set routing-options static route 203.0.113.2/24 discard
```

7. If you are done configuring the device, commit the configuration.

```
[edit]
user@PE1# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show interfaces
ge-1/0/0 {
  unit 0 {
    description PE1-to-RR1;
    family inet {
      address 10.49.0.1/30;
    }
    family mpls;
  }
}
ge-1/0/1 {
  unit 0 {
    description PE1-to-RR2;
    family inet {
      address 10.49.10.1/30;
    }
    family mpls;
  }
}
```

```
user@PE1# show protocols
bgp {
  group internal {
    type internal;
    local-address 10.255.163.58;
    neighbor 10.255.165.220 {
      family inet-vpn {
        unicast;
      }
    }
    neighbor 10.255.165.28 {
      family inet-vpn {
        unicast;
      }
    }
  }
}
```



```

    }
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}

```

```

user@PE1# show routing-options
route-distinguisher-id 10.255.14.182;
autonomous-system 203;

```

```

user@PE1# show routing-instances
vpn1 {
    instance-type vrf;
    vrf-target target:203:100;
    routing-options {
        static {
            route 203.0.113.1/24 discard;
        }
    }
}
vpn2 {
    instance-type vrf;
    vrf-target target:203:101;
    routing-options {
        static {
            route 203.0.113.2/24 discard;
        }
    }
}

```

Configuring Device RR1

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device RR1:

1. Configure the interfaces.

```
[edit interfaces]
user@RR1# set ge-1/0/0 unit 0 description RR1-to-PE1
user@RR1# set ge-1/0/0 unit 0 family inet address 10.49.0.2/30
user@RR1# set ge-1/0/0 unit 0 family mpls
user@RR1# set ge-1/0/1 unit 0 description RR1-to-PE2
user@RR1# set ge-1/0/1 unit 0 family inet address 10.50.0.2/30
user@RR1# set ge-1/0/1 unit 0 family mpls
```

2. Configure the route distinguisher and the AS number.

```
[edit routing-options]
user@RR1# set route-distinguisher-id 10.255.165.220
user@RR1# set autonomous-system 203
```

3. Configure LDP as the signaling protocol used by the VPN.

```
[edit protocols ldp]
user@RR1# set interface ge-1/0/0
user@RR1# set interface ge-1/0/1
```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@RR1# set type internal
user@RR1# set local-address 10.255.165.220
user@RR1# set cluster 198.51.100.1
user@RR1# set neighbor 10.255.163.58 description vpn1-to-pe1 family inet-vpn unicast
user@RR1# set neighbor 10.255.168.42 description vpn1-to-pe2 family inet-vpn unicast
```

5. Configure BGP route target filtering on the peering session with Device PE2.

```
[edit protocols bgp group internal]
user@RR1# set neighbor 10.255.168.42 family route-target
```

6. Configure proxy BGP route target filtering on the peering session with Device PE1.

```
[edit protocols bgp group internal]
user@RR1# set neighbor 10.255.163.58 family route-target proxy-generate
```

7. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@RR1# set interface ge-1/0/0
user@RR1# set interface ge-1/0/1
user@RR1# set interface lo0.0 passive
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@RR1# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols` and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@RR1# show interfaces
ge-1/0/0 {
  unit 0 {
    description RR1-to-PE1;
    family inet {
      address 10.49.0.2/30;
    }
    family mpls;
  }
}
```

```

}
ge-1/0/1 {
  unit 0 {
    description RR1-to-PE2;
    family inet {
      address 10.50.0.2/30;
    }
    family mpls;
  }
}

```

```

user@RR1# show protocols
bgp {
  group internal {
    type internal;
    local-address 198.51.100.1;
    cluster 198.51.100.1;
    neighbor 10.255.163.58 {
      description vpn1-to-pe1;
      family inet-vpn {
        unicast;
      }
      family route-target {
        proxy-generate;
      }
    }
    neighbor 10.255.168.42 {
      description vpn1-to-pe2;
      family inet-vpn {
        unicast;
      }
      family route-target;
    }
  }
}
ospf {
  area 0.0.0.0 {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
    interface lo0.0 {
      passive;
    }
  }
}

```

```

    }
  }
}
ldp {
  interface ge-1/0/0.0;
  interface ge-1/0/1.0;
}

```

```

user@RR1# show routing-options
route-distinguisher-id 10.255.165.220;
autonomous-system 203;

```

Configuring Device RR2

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device RR2:

1. Configure the interfaces.

```

[edit interfaces]
user@RR2# set ge-1/0/0 unit 0 description RR2-to-PE1
user@RR2# set ge-1/0/0 unit 0 family inet address 10.49.10.2/30
user@RR2# set ge-1/0/0 unit 0 family mpls
user@RR2# set ge-1/0/1 unit 0 description RR2-to-PE2
user@RR2# set ge-1/0/1 unit 0 family inet address 10.50.10.2/30
user@RR2# set ge-1/0/1 unit 0 family mpls

```

2. Configure the route distinguisher and the AS number.

```

[edit routing-options]
user@RR2# set route-distinguisher-id 10.255.165.28
user@RR2# set autonomous-system 203

```

3. Configure LDP as the signaling protocol used by the VPN.

```
[edit protocols ldp]
user@RR2# set interface ge-1/0/0
user@RR2# set interface ge-1/0/1
```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@RR2# set type internal
user@RR2# set local-address 10.255.165.28
user@RR2# set cluster 198.51.100.1
user@RR2# set neighbor 10.255.163.58 description vpn2-to-pe1 family inet-vpn unicast
user@RR2# set neighbor 10.255.168.42 description vpn2-to-pe2 family inet-vpn unicast
```

5. Configure BGP route target filtering on the peering session with Device PE2.

```
[edit protocols bgp group internal]
user@RR2# set neighbor 10.255.168.42 family route-target
```

6. Configure proxy BGP route target filtering on the peering session with Device PE1.

```
[edit protocols bgp group internal]
user@RR2# set neighbor 10.255.163.58 family route-target proxy-generate
```

7. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@RR2# set interface ge-1/0/0
user@RR2# set interface ge-1/0/1
user@RR2# set interface lo0.0 passive
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@RR2# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@RR2# show interfaces
ge-1/0/0 {
  unit 0 {
    description RR2-to-PE1;
    family inet {
      address 10.49.10.2/30;
    }
    family mpls;
  }
}
ge-1/0/1 {
  unit 0 {
    description RR2-to-PE2;
    family inet {
      address 10.50.10.2/30;
    }
    family mpls;
  }
}
```

```
user@RR2# show protocols
bgp {
  group internal {
    local-address 10.255.165.28;
    cluster 198.51.100.1;
    neighbor 10.255.163.58 {
      description vpn2-to-pe1;
      family inet-vpn {
        unicast;
      }
      family route-target {
        proxy-generate;
      }
    }
  }
  neighbor 10.255.168.42 {
```

```

        description vpn2-to-pe2;
        family inet-vpn {
            unicast;
        }
        family route-target;
    }
}
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}

```

```

user@RR2# show routing-options
route-distinguisher-id 10.255.165.28;
autonomous-system 203;

```

Configuring Device PE2

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device PE2:

1. Configure the interfaces.

```

[edit interfaces]
user@PE2# set ge-1/0/0 unit 0 description PE2-to-RR1
user@PE2# set ge-1/0/0 unit 0 family inet address 10.50.0.1/30
user@PE2# set ge-1/0/0 unit 0 family mpls

```



```

user@PE2# set ge-1/0/1 unit 0 description PE2-to-RR2
user@PE2# set ge-1/0/1 unit 0 family inet address 10.50.10.1/30
user@PE2# set ge-1/0/1 unit 0 family mpls

```

2. Configure the route distinguisher and the AS number.

```

[edit routing-options]
user@PE2# set route-distinguisher-id 10.255.168.42
user@PE2# set autonomous-system 203

```

3. Configure LDP as the signaling protocol used by the VPN.

```

[edit protocols ldp]
user@PE2# set interface ge-1/0/0
user@PE2# set interface ge-1/0/1

```

4. Configure BGP.

```

[edit protocols bgp group internal]
user@PE2# set type internal
user@PE2# set local-address 10.255.168.42
user@PE2# set family inet-vpn unicast
user@PE2# set family route-target
user@PE2# set neighbor 10.255.165.220
user@PE2# set neighbor 10.255.165.28

```

5. Configure OSPF.

```

[edit protocols ospf area 0.0.0.0]
user@PE2# set interface ge-1/0/0
user@PE2# set interface ge-1/0/1
user@PE2# set interface lo0.0 passive

```

6. Configure the VPN routing instances.

```

[edit routing-instances vpn1]
user@PE2# set instance-type vrf

```

```
user@PE2# set vrf-target target:203:100
user@PE2# set routing-options static route 203.0.113.1/24 discard
```

```
[edit routing-instances vpn2]
user@PE2# set instance-type vrf
user@PE2# set vrf-target target:203:101
user@PE2# set routing-options static route 203.0.113.2/24 discard
```

```
[edit routing-instances vpn3]
user@PE2# set instance-type vrf
user@PE2# set vrf-target target:203:103
user@PE2# set routing-options static route 203.0.113.3/24 discard
```

```
[edit routing-instances vpn4]
user@PE2# set instance-type vrf
user@PE2# set vrf-target target:203:104
user@PE2# set routing-options static route 203.0.113.4/24 discard
```

7. If you are done configuring the device, commit the configuration.

```
[edit]
user@PE2# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE2# show interfaces
ge-1/0/0 {
  unit 0 {
    description PE2-to-RR1;
    family inet {
      address 10.50.0.1/30;
    }
  }
}
```

```

        family mpls;
    }
}
ge-1/0/1 {
    unit 0 {
        description PE2-to-RR2;
        family inet {
            address 10.50.10.1/30;
        }
        family mpls;
    }
}
}

```

```

user@PE2# show protocols
bgp {
    group internal {
        type internal;
        local-address 10.255.168.42;
        family inet-vpn {
            unicast;
        }
        family route-target;
        neighbor 10.255.165.220;
        neighbor 10.255.165.28;
    }
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
}

```

```
interface ge-1/0/1.0;  
}
```

```
user@PE2# show routing-options  
route-distinguisher-id 10.255.168.42;  
autonomous-system 203;
```

```
user@PE2# show routing-instances  
vpn1 {  
  instance-type vrf;  
  vrf-target target:203:100;  
  routing-options {  
    static {  
      route 203.0.113.1/24 discard;  
    }  
  }  
}  
vpn2 {  
  instance-type vrf;  
  vrf-target target:203:101;  
  routing-options {  
    static {  
      route 203.0.113.2/24 discard;  
    }  
  }  
}  
vpn3 {  
  instance-type vrf;  
  vrf-target target:203:103;  
  routing-options {  
    static {  
      route 203.0.113.3/24 discard;  
    }  
  }  
}  
vpn4 {  
  instance-type vrf;  
  vrf-target target:203:104;  
  routing-options {  
    static {
```

```

        route 203.0.113.4/24 discard;
    }
}
}

```

Verification

IN THIS SECTION

- [Verifying the Proxy BGP Route Target Routes | 82](#)

Confirm that the configuration is working properly.

Verifying the Proxy BGP Route Target Routes

Purpose

Verify that the proxy BGP route target routes are displayed in the `bgp.rtarget.0` table on Device RR1.

Action

From operational mode, enter the `show route table bgp.rtarget.0` command to display the proxy BGP route targets.

```

user@RR1# show route table bgp.rtarget.0
4 destinations, 6 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

203:203:100/96
    *[RTarget/5] 00:01:22
        Type Proxy
        for 10.255.163.58
        Local
        [BGP/170] 00:04:55, localpref 100, from 10.255.168.42
        AS path: I, validation-state: unverified
        > to 10.50.0.1 via ge-1/0/1

203:203:101/96
    *[RTarget/5] 00:01:22

```

```

Type Proxy
  for 10.255.163.58
    Local
      [BGP/170] 00:04:55, localpref 100, from 10.255.168.42
      AS path: I, validation-state: unverified
      > to 10.50.0.1 via ge-1/0/1
203:203:103/96
      *[BGP/170] 00:04:55, localpref 100, from 10.255.168.42
      AS path: I, validation-state: unverified
      > to 10.50.0.1 via ge-1/0/1
203:203:104/96
      *[BGP/170] 00:04:55, localpref 100, from 10.255.168.42
      AS path: I, validation-state: unverified
      > to 10.50.0.1 via ge-1/0/1

```

Meaning

Device RR1 is generating the proxy BGP route target routes on behalf of its peer Device PE1. The proxy BGP route target routes are identified with the protocol and preference [RTarget/5] and the route target type of Proxy.

Example: Configuring an Export Policy for BGP Route Target Filtering for VPNs

IN THIS SECTION

- [Requirements | 84](#)
- [Overview | 84](#)
- [Configuration | 86](#)
- [Verification | 105](#)

This example shows how to configure an export routing policy for BGP route target filtering (also known as route target constrain, or RTC).

Requirements

This example uses the following hardware and software components:

- Four Juniper Networks devices that support BGP route target filtering.
- Junos OS Release 12.2 or later on one or more devices configured for proxy BGP route filtering. In this example, you explicitly configure proxy BGP route filtering on the route reflectors.

Before configuring an export policy for BGP route target filtering, make sure that you are familiar with and understand the following concepts:

- ["Layer 2 VPNs" on page 143](#)
- *Understanding Layer 3 VPNs*
- *Understanding VPN-IPv4 Addresses and Route Distinguishers*
- *Configuring Policies for the VRF Table on PE Routers in VPNs*
- *Configuring BGP Route Target Filtering for VPNs*
- [BGP extended communities](#)

Overview

IN THIS SECTION

- [Topology Diagram | 85](#)

BGP route target filtering allows you to reduce network resource consumption by distributing route target membership (RT membership) advertisements throughout the network. BGP uses the RT membership information to send VPN routes only to the devices that need them in the network. Similar to other types of BGP reachability, you can apply a routing policy to route target filtering routes to influence the network. When route target filtering is configured, restricting the flow of route target filtering routes also restricts the VPN routes that might be attracted by this RT membership. Configuring this policy involves:

- Creating a filter that defines the list of route target prefixes.
- Creating a policy to select a subset of the route target filters to use for BGP route target filtering.

To define the list of route target prefixes:

- You configure the `rtf-prefix-list` statement at the [edit [policy-options](#)] hierarchy level to specify the name of the route target prefix list and one or more route target prefixes to use. This configuration allows you to specify the incoming route target filtering routes that the device will use and then distribute them throughout the network.

To configure the routing policy and apply the route target prefix list to that policy, you can specify the following policy options:

- `family route-target`—(Optional) The route-target family match condition specifies matching BGP route target filtering routes. You define this criteria in the `from` statement. This example shows how to create an export policy using the `family route-target` match condition.
- `protocol route-target`—(Optional) The route-target protocol match condition defines the criteria that an incoming route must match. You define this criteria in the `from` statement. This statement is primarily useful for restricting the policy to locally generated route target filtering routes.


NOTE: When you use the `show route table bgp.rtarget.0` command to view proxy BGP route target filtering routes, you will see the BGP protocol for received routes and the route target protocol routes for local route target filtering routes.

- `rtf-prefix-list name`—The `rtf-prefix-list` statement applies the list of route target prefixes that you already configured to the policy. You define this criteria in the `from` statement.

Topology Diagram

[Figure 6 on page 85](#) shows the topology used in this example.

Figure 6: BGP Route Target Filtering Export Policy Topology



In this example, BGP route target filtering is configured on the route reflectors (Device RR1 and Device RR2) and provider edge (PE) Device PE2. The other PE, Device PE1, does not support BGP route target

filtering. Proxy BGP route target filtering is also configured on the peering sessions between the route reflectors and Device PE1 to minimize the number of VPN route updates processed by Device PE1. Device PE2 has four VPNs configured (vpn1, vpn2, vpn3, and vpn4), and Device PE1 has two VPNs configured (vpn1 and vpn2). In the sample topology, all devices participate in autonomous system (AS) 203, OSPF is the configured interior gateway protocol (IGP), and LDP is the signaling protocol used by the VPNs. In this example, we use static routes in the VPN routing and forwarding (VRF) instances to generate VPN routes. This is done in place of using a PE to customer edge (CE) protocol such as OSPF or BGP.

In this example, you further control the routes being advertised from Device PE2 to Device PE1 by configuring an export policy on Device PE2 to prevent vpn3 routes from being advertised to Device RR1. You create a policy that specifies the family route-target match condition, defines the list of route target prefixes, and applies the list of route target prefixes by defining the rtf-prefix-list criteria.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 86](#)
- [Configuring Device PE1 | 89](#)
- [Configuring Device RR1 | 93](#)
- [Configuring Device RR2 | 97](#)
- [Configuring Device PE2 | 100](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device PE1

```
set interfaces ge-1/0/0 unit 0 description PE1-to-RR1
set interfaces ge-1/0/0 unit 0 family inet address 10.49.0.1/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description PE1-to-RR2
set interfaces ge-1/0/1 unit 0 family inet address 10.49.10.1/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
```

```

set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.255.163.58
set protocols bgp group internal neighbor 10.255.165.220 family inet-vpn unicast
set protocols bgp group internal neighbor 10.255.165.28 family inet-vpn unicast
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.163.58
set routing-options autonomous-system 203
set routing-instances vpn1 instance-type vrf
set routing-instances vpn1 vrf-target target:203:100
set routing-instances vpn1 routing-options static route 203.0.113.1/24 discard
set routing-instances vpn2 instance-type vrf
set routing-instances vpn2 vrf-target target:203:101
set routing-instances vpn2 routing-options static route 203.0.113.2/24 discard

```

Device RR1

```

set interfaces ge-1/0/0 unit 0 description RR1-to-PE1
set interfaces ge-1/0/0 unit 0 family inet address 10.49.0.2/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description RR1-to-PE2
set interfaces ge-1/0/1 unit 0 family inet address 10.50.0.2/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 198.51.100.0
set protocols bgp group internal cluster 198.51.100.1
set protocols bgp group internal neighbor 10.255.163.58 description vpn1-to-pe1 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.163.58 family route-target proxy-generate
set protocols bgp group internal neighbor 10.255.168.42 description vpn1-to-pe2 family inet-vpn
unicast
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.165.220
set routing-options autonomous-system 203

```

Device RR2

```

set interfaces ge-1/0/0 unit 0 description RR2-to-PE1
set interfaces ge-1/0/0 unit 0 family inet address 10.49.10.2/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description RR2-to-PE2
set interfaces ge-1/0/1 unit 0 family inet address 10.50.10.2/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.255.165.28
set protocols bgp group internal cluster 198.51.100.1
set protocols bgp group internal neighbor 10.255.163.58 description vpn2-to-pe1 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.163.58 family route-target proxy-generate
set protocols bgp group internal neighbor 10.255.168.42 description vpn2-to-pe2 family inet-vpn
unicast
set protocols bgp group internal neighbor 10.255.163.58 family route-target
set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set routing-options route-distinguisher-id 10.255.165.28
set routing-options autonomous-system 203

```

Device PE2

```

set interfaces ge-1/0/0 unit 0 description PE2-to-RR1
set interfaces ge-1/0/0 unit 0 family inet address 10.50.0.1/30
set interfaces ge-1/0/0 unit 0 family mpls
set interfaces ge-1/0/1 unit 0 description PE2-to-RR2
set interfaces ge-1/0/1 unit 0 family inet address 10.50.10.2/30
set interfaces ge-1/0/1 unit 0 family mpls
set protocols ldp interface ge-1/0/0
set protocols ldp interface ge-1/0/1
set protocols bgp group internal type internal
set protocols bgp group internal local-address 10.255.168.42
set protocols bgp group internal family inet-vpn unicast
set protocols bgp group internal family route-target
set protocols bgp group internal neighbor 10.255.165.220 export filter-rtc
set protocols bgp group internal neighbor 10.255.165.28

```

```

set protocols ospf area 0.0.0.0 interface ge-1/0/0
set protocols ospf area 0.0.0.0 interface ge-1/0/1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set policy-options rtf-prefix-list exclude-103 203:203:103/96
set policy-options policy-statement filter-rtc from family route-target
set policy-options policy-statement filter-rtc from rtf-prefix-list exclude-103
set policy-options policy-statement filter-rtc then reject
set routing-options route-distinguisher-id 10.255.168.42
set routing-options autonomous-system 203
set routing-instances vpn1 instance-type vrf
set routing-instances vpn1 vrf-target target:203:100
set routing-instances vpn1 routing-options static route 203.0.113.1/24 discard
set routing-instances vpn2 instance-type vrf
set routing-instances vpn2 vrf-target target:203:101
set routing-instances vpn2 routing-options static route 203.0.113.2/24 discard
set routing-instances vpn3 instance-type vrf
set routing-instances vpn3 vrf-target target:203:103
set routing-instances vpn3 routing-options static route 203.0.113.3/24 discard
set routing-instances vpn4 instance-type vrf
set routing-instances vpn4 vrf-target target:203:104
set routing-instances vpn4 routing-options static route 203.0.113.4/24 discard

```

Configuring Device PE1

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device PE1:

1. Configure the interfaces.

```

[edit interfaces]
user@PE1# set ge-1/0/0 unit 0 description PE1-to-RR1
user@PE1# set ge-1/0/0 unit 0 family inet address 10.49.0.1/30
user@PE1# set ge-1/0/0 unit 0 family mpls
user@PE1# set ge-1/0/1 unit 0 description PE1-to-RR2
user@PE1# set ge-1/0/1 unit 0 family inet address 10.49.10.1/30
user@PE1# set ge-1/0/1 unit 0 family mpls

```

2. Configure the route distinguisher and the AS number.

```
[edit routing-options]
user@PE1# set route-distinguisher-id 10.255.163.58
user@PE1# set autonomous-system 203
```

3. Configure LDP as the signaling protocol used by the VPN.

```
[edit protocols ldp]
user@PE1# set interface ge-1/0/0
user@PE1# set interface ge-1/0/1
```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@PE1# set type internal
user@PE1# set local-address 10.255.163.58
user@PE1# set neighbor 10.255.165.220 family inet-vpn unicast
user@PE1# set neighbor 10.255.165.28 family inet-vpn unicast
```

5. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@PE1# set interface ge-1/0/0
user@PE1# set interface ge-1/0/1
user@PE1# set interface lo0.0 passive
```

6. Configure the VPN routing instances.

```
[edit routing-instances vpn1]
user@PE1# set instance-type vrf
user@PE1# set vrf-target target:203:100
user@PE1# set routing-options static route 203.0.113.1/24 discard
```

```
[edit routing-instances vpn2]
user@PE1# set instance-type vrf
```

```

user@PE1# set vrf-target target:203:101
user@PE1# set routing-options static route 203.0.113.2/24 discard

```

7. If you are done configuring the device, commit the configuration.

```

[edit]
user@PE1# commit

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE1# show interfaces
ge-1/0/0 {
  unit 0 {
    description PE1-to-RR1;
    family inet {
      address 10.49.0.1/30;
    }
    family mpls;
  }
}
ge-1/0/1 {
  unit 0 {
    description PE1-to-RR2;
    family inet {
      address 10.49.10.1/30;
    }
    family mpls;
  }
}

```

```

user@PE1# show protocols
bgp {
  group internal {
    type internal;
    local-address 10.255.163.58;
  }
}

```

```

        neighbor 10.255.165.220 {
            family inet-vpn {
                unicast;
            }
        }
        neighbor 10.255.165.28 {
            family inet-vpn {
                unicast;
            }
        }
    }
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}

```

```

user@PE1# show routing-options
route-distinguisher-id 10.255.14.182;
autonomous-system 203;

```

```

user@PE1# show routing-instances
vpn1 {
    instance-type vrf;
    vrf-target target:203:100;
    routing-options {
        static {
            route 203.0.113.1/24 discard;
        }
    }
}

```

```

vpn2 {
    instance-type vrf;
    vrf-target target:203:101;
    routing-options {
        static {
            route 203.0.113.2/24 discard;
        }
    }
}

```

Configuring Device RR1

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device RR1:

1. Configure the interfaces.

```

[edit interfaces]
user@RR1# set ge-1/0/0 unit 0 description RR1-to-PE1
user@RR1# set ge-1/0/0 unit 0 family inet address 10.49.0.2/30
user@RR1# set ge-1/0/0 unit 0 family mpls
user@RR1# set ge-1/0/1 unit 0 description RR1-to-PE2
user@RR1# set ge-1/0/1 unit 0 family inet address 10.50.0.2/30
user@RR1# set ge-1/0/1 unit 0 family mpls

```

2. Configure the route distinguisher and the AS number.

```

[edit routing-options]
user@RR1# set route-distinguisher-id 10.255.165.220
user@RR1# set autonomous-system 203

```


3. Configure LDP as the signaling protocol used by the VPN.

```
[edit protocols ldp]
user@RR1# set interface ge-1/0/0
user@RR1# set interface ge-1/0/1
```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@RR1# set type internal
user@RR1# set local-address 10.255.165.220
user@RR1# set cluster 198.51.100.1
user@RR1# set neighbor 10.255.163.58 description vpn1-to-pe1 family inet-vpn unicast
user@RR1# set neighbor 10.255.168.42 description vpn1-to-pe2 family inet-vpn unicast
```

5. Configure BGP route target filtering on the peering session with Device PE2.

```
[edit protocols bgp group internal]
user@RR1# set neighbor 10.255.168.42 family route-target
```

6. Configure proxy BGP route target filtering on the peering session with Device PE1.

```
[edit protocols bgp group internal]
user@RR1# set neighbor 10.255.163.58 family route-target proxy-generate
```

7. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@RR1# set interface ge-1/0/0
user@RR1# set interface ge-1/0/1
user@RR1# set interface lo0.0 passive
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@RR1# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@RR1# show interfaces
ge-1/0/0 {
  unit 0 {
    description RR1-to-PE1;
    family inet {
      address 10.49.0.2/30;
    }
    family mpls;
  }
}
ge-1/0/1 {
  unit 0 {
    description RR1-to-PE2;
    family inet {
      address 10.50.0.2/30;
    }
    family mpls;
  }
}
```

```
user@RR1# show protocols
bgp {
  group internal {
    type internal;
    local-address 198.51.100.0;
    cluster 198.51.100.1;
    neighbor 10.255.163.58 {
      description vpn1-to-pe1;
      family inet-vpn {
        unicast;
      }
      family route-target {
        proxy-generate;
      }
    }
  }
}
```

```

        neighbor 10.255.168.42 {
            description vpn1-to-pe2;
            family inet-vpn {
                unicast;
            }
            family route-target;
        }
    }
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}

```

```

user@RR1# show routing-options
route-distinguisher-id 10.255.165.220;
autonomous-system 203;

```

Configuring Device RR2

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device RR2:

1. Configure the interfaces.

```
[edit interfaces]
user@RR2# set ge-1/0/0 unit 0 description RR2-to-PE1
user@RR2# set ge-1/0/0 unit 0 family inet address 10.49.10.2/30
user@RR2# set ge-1/0/0 unit 0 family mpls
user@RR2# set ge-1/0/1 unit 0 description RR2-to-PE2
user@RR2# set ge-1/0/1 unit 0 family inet address 10.50.10.2/30
user@RR2# set ge-1/0/1 unit 0 family mpls
```

2. Configure the route distinguisher and the AS number.

```
[edit routing-options]
user@RR2# set route-distinguisher-id 10.255.165.28
user@RR2# set autonomous-system 203
```

3. Configure LDP as the signaling protocol used by the VPN.

```
[edit protocols ldp]
user@RR2# set interface ge-1/0/0
user@RR2# set interface ge-1/0/1
```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@RR2# set type internal
user@RR2# set local-address 10.255.165.28
user@RR2# set cluster 198.51.100.1
user@RR2# set neighbor 10.255.163.58 description vpn2-to-pe1 family inet-vpn unicast
user@RR2# set neighbor 10.255.168.42 description vpn2-to-pe2 family inet-vpn unicast
```

5. Configure BGP route target filtering on the peering session with Device PE2.

```
[edit protocols bgp group internal]
user@RR2# set neighbor 10.255.168.42 family route-target
```

6. Configure proxy BGP route target filtering on the peering session with Device PE1.

```
[edit protocols bgp group internal]
user@RR2# set neighbor 10.255.163.58 family route-target proxy-generate
```

7. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@RR2# set interface ge-1/0/0
user@RR2# set interface ge-1/0/1
user@RR2# set interface lo0.0 passive
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@RR2# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@RR2# show interfaces
ge-1/0/0 {
  unit 0 {
    description RR2-to-PE1;
    family inet {
      address 10.49.10.2/30;
    }
    family mpls;
  }
}
```

```

}
ge-1/0/1 {
    unit 0 {
        description RR2-to-PE2;
        family inet {
            address 10.50.10.2/30;
        }
        family mpls;
    }
}

```

```

user@RR2# show protocols
bgp {
    group internal {
        local-address 10.255.165.28;
        cluster 198.51.100.1;
        neighbor 10.255.163.58 {
            description vpn2-to-pe1;
            family inet-vpn {
                unicast;
            }
            family route-target {
                proxy-generate;
            }
        }
        neighbor 10.255.168.42 {
            description vpn2-to-pe2;
            family inet-vpn {
                unicast;
            }
            family route-target;
        }
    }
}
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}

```

```

    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}

```

```

user@RR2# show routing-options
route-distinguisher-id 10.255.165.28;
autonomous-system 203;

```

Configuring Device PE2

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure Device PE2:

1. Configure the interfaces.

```

[edit interfaces]
user@PE2# set ge-1/0/0 unit 0 description PE2-to-RR1
user@PE2# set ge-1/0/0 unit 0 family inet address 10.50.0.1/30
user@PE2# set ge-1/0/0 unit 0 family mpls
user@PE2# set ge-1/0/1 unit 0 description PE2-to-RR2
user@PE2# set ge-1/0/1 unit 0 family inet address 10.50.10.2/30
user@PE2# set ge-1/0/1 unit 0 family mpls

```

2. Configure the route distinguisher and the AS number.

```

[edit routing-options]
user@PE2# set route-distinguisher-id 10.255.168.42
user@PE2# set autonomous-system 203

```

3. Configure LDP as the signaling protocol used by the VPN.

```
[edit protocols ldp]
user@PE2# set interface ge-1/0/0
user@PE2# set interface ge-1/0/1
```

4. Configure BGP.

```
[edit protocols bgp group internal]
user@PE2# set type internal
user@PE2# set local-address 10.255.168.42
user@PE2# set family inet-vpn unicast
user@PE2# set family route-target
user@PE2# set neighbor 10.255.165.220
user@PE2# set neighbor 10.255.165.28
```

5. Configure OSPF.

```
[edit protocols ospf area 0.0.0.0]
user@PE2# set interface ge-1/0/0
user@PE2# set interface ge-1/0/1
user@PE2# set interface lo0.0 passive
```

6. Configure the VPN routing instances.

```
[edit routing-instances vpn1]
user@PE2# set instance-type vrf
user@PE2# set vrf-target target:203:100
user@PE2# set routing-options static route 203.0.113.1/24 discard
```

```
[edit routing-instances vpn2]
user@PE2# set instance-type vrf
```



```

user@PE2# set vrf-target target:203:101
user@PE2# set routing-options static route 203.0.113.2/24 discard

```

```

[edit routing-instances vpn3]
user@PE2# set instance-type vrf
user@PE2# set vrf-target target:203:103
user@PE2# set routing-options static route 203.0.113.3/24 discard

```

```

[edit routing-instances vpn4]
user@PE2# set instance-type vrf
user@PE2# set vrf-target target:203:104
user@PE2# set routing-options static route 203.0.113.4/24 discard

```

7. Configure and apply the export routing policy.

```

[edit policy-options]
user@PE2# set rtf-prefix-list exclude-103 203:203:103/96
[edit policy-options policy-statement filter-rtc]
user@PE2# set from family route-target
user@PE2# set from rtf-prefix-list exclude-103
user@PE2# set then reject
[edit protocols bgp group internal]
user@PE2# set neighbor 10.255.165.220 export filter-rtc

```

8. If you are done configuring the device, commit the configuration.

```

[edit]
user@PE2# commit

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show policy-options`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE2# show interfaces
ge-1/0/0 {
  unit 0 {
    description PE2-to-RR1;
    family inet {
      address 10.50.0.1/30;
    }
    family mpls;
  }
}
ge-1/0/1 {
  unit 0 {
    description PE2-to-RR2;
    family inet {
      address 10.50.10.2/30;
    }
    family mpls;
  }
}
```

```
user@PE2# show protocols
bgp {
  group internal {
    type internal;
    local-address 10.255.168.42;
    family inet-vpn {
      unicast;
    }
    family route-target;
    neighbor 10.255.165.220 {
      export filter-rtc;
    }
    neighbor 10.255.165.28;
  }
}
```

```
ospf {
    area 0.0.0.0 {
        interface ge-1/0/0.0;
        interface ge-1/0/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-1/0/0.0;
    interface ge-1/0/1.0;
}
```

```
user@PE2# show routing-options
route-distinguisher-id 10.255.168.42;
autonomous-system 203;
```

```
user@PE2# show policy-options
policy-statement filter-rtc {
    from {
        family route-target;
        rtf-prefix-list exclude-103;
    }
    then reject;
}
rtf-prefix-list exclude-103 {
    203:203:103/96;
}
```

```
user@PE2# show routing-instances
vpn1 {
    instance-type vrf;
    vrf-target target:203:100;
    routing-options {
        static {
            route 203.0.113.1/24 discard;
        }
    }
}
```

```
}  
vpn2 {  
    instance-type vrf;  
    vrf-target target:203:101;  
    routing-options {  
        static {  
            route 203.0.113.2/24 discard;  
        }  
    }  
}  
}  
vpn3 {  
    instance-type vrf;  
    vrf-target target:203:103;  
    routing-options {  
        static {  
            route 203.0.113.3/24 discard;  
        }  
    }  
}  
}  
vpn4 {  
    instance-type vrf;  
    vrf-target target:203:104;  
    routing-options {  
        static {  
            route 203.0.113.4/24 discard;  
        }  
    }  
}  
}
```

Verification

IN THIS SECTION

- [Verifying the Route Target Filtering Routes in the bgp.rtarget.0 Routing Table for Device RR1 | 106](#)
- [Verifying the Route Target Filtering Routes in the bgp.rtarget.0 Routing Table for Device RR2 | 106](#)

Confirm that the configuration is working properly.

Verifying the Route Target Filtering Routes in the bgp.rtarget.0 Routing Table for Device RR1

Purpose

Verify that the route prefix for vpn3 is not in Device RR1's bgp.rtarget.0 table. Since an export policy on Device PE2 was applied to prevent the advertisement of vpn3 routes to Device RR1, Device RR1 should not receive those advertisements.

Action

From operational mode, enter the `show route advertising-protocol bgp 10.255.165.220 table bgp.rtarget.0` command.

```
user@PE2# show route advertising-protocol bgp 10.255.165.220 table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 11 routes
(4 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED    Lclpref    AS path
  203:203:100/96        *                Self    100        I
  203:203:101/96        *                Self    100        I
  203:203:104/96        *                Self    100        I
```

Meaning

The bgp.rtarget.0 table does not display 203:203:103/96, which is the route prefix for vpn3. That means the export policy was applied correctly.

Verifying the Route Target Filtering Routes in the bgp.rtarget.0 Routing Table for Device RR2

Purpose

Verify that the route prefix for vpn3 is in Device RR2's bgp.rtarget.0 table. Since an export policy was not applied on Device PE2 to prevent the advertisement of vpn3 routes to Device RR2, Device RR2 should receive advertisements from all of the VPNs.

Action

From operational mode, enter the `show route advertising-protocol bgp 10.255.165.28 table bgp.rtarget.0` command.

```
user@PE2# show route advertising-protocol bgp 10.255.165.28 table bgp.rtarget.0
bgp.rtarget.0: 4 destinations, 11 routes (4 active, 0 holddown, 0 hidden)
(4 active, 0 holddown, 0 hidden)
```

Prefix	Nexthop	MED	Lclpref	AS path
203:203:100/96	*	Self	100	I
203:203:101/96	*	Self	100	I
203:203:103/96	*	Self	100	I
203:203:104/96	*	Self	100	I

Meaning

The `bgp.rtarget.0` table displays the route prefixes for all of the VPNs.

Reducing Network Resource Use with Static Route Target Filtering for VPNs

The BGP VPN route target extended community (RFC 4360, *BGP Extended Communities Attribute*) is used to determine VPN membership. Static route target filtering helps to prevent resources from being consumed in portions of the network where the VPN routes are not needed due to the lack of member PE routers (RFC 4684, *Constrained Route Distribution for Border Gateway Protocol/MultiProtocol Label Switching (BGP/MPLS) Internet Protocol (IP) Virtual Private Networks (VPNs)*). Routers can originate routes into the RT-Constrain protocol to indicate their interest in receiving VPN routes containing route targets that match the RT-Constrain NLRI.

Normally, for the RT-Constrain feature to function properly, it must be broadly deployed throughout a network. If this is not the case, the feature is less useful, because the RT-Constrain BGP speaker facing a non-RT-Constrain speaker must advertise a default RT-Constrain route to the other RT-Constrain speakers on behalf of the peer that does not support the feature. This effectively removes the resource saving benefits of the feature in portions of the network where it is not supported since a default RT-Constrain route causes the PE router and all intervening PE routers to need to receive all VPN routes.

The static RT-Constrain feature enables you to partially deploy the RT-Constrain feature in a network. The feature is enabled at a boundary in the network where RT-Constrain is configured. However, some BGP VPN peers do not support RT-Constrain, typically PE routers. The route targets of those PE routers

must be statically configured on the router. These route targets are disseminated using the RT-Constrain protocol.

The proxy RT-Constrain feature permits BGP VPN peers that do not support the protocol to have their route-targets discovered and disseminated automatically. However, this feature can only support symmetric route-targets. For example, the import and export route-targets for a VRF routing instance are identical. However, for a hub-and-spoke VPN, the import and export route-targets are not identical. In this scenario, the import and export route-target may be statically configured to be disseminated in the RT-Constrain protocol.

Configuring Forwarding Options for VPNs

IN THIS CHAPTER

- [Chained Composite Next Hops for VPNs and Layer 2 Circuits | 109](#)
- [Example: Configuring Chained Composite Next Hops for Direct PE-PE Connections in VPNs | 110](#)

Chained Composite Next Hops for VPNs and Layer 2 Circuits

IN THIS SECTION

- [Benefits of chained composite next hops | 110](#)

The Juniper Networks PTX Series Packet Transport Routers, MX Series 5G Universal Routing Platforms with MIC and MPC interfaces, and T4000 Core Routers are principally designed to handle large volumes of traffic in the core of large networks. Chained CNHs help to facilitate this capability by allowing the router to process much larger volumes of routes. A chained CNH allows the router to direct sets of routes sharing the same destination to a common forwarding next hop, rather than having each route also include the destination. In the event that a network destination is changed, rather than having to update all of the routes sharing that destination with the new information, only the shared forwarding next hop is updated with the new information. The chained CNHs continue to point to this forwarding next hop, which now contains the new destination.

When the next hops for MPLS LSPs are created on the routers, the tag information corresponding to the innermost MPLS label is extracted into a chained CNH. The chained CNH is stored in the ingress Packet Forwarding Engine. The chained CNH points to a next hop called the forwarding next hop that resides on the egress Packet Forwarding Engine. The forwarding next hop contains all the other information (all of the labels except for the inner-most labels as well as the IFA/IP information corresponding to the actual next-hop node). Many chained composite next hops can share the same forwarding next hop. Additionally, separating the inner-most label (that is the VPN label) from the forwarding next hop and storing it on the ingress PFE (within the chained composite next hop) helps to conserve egress Packet

Forwarding Engine memory by reducing the number of rewrite strings stored on the egress Packet Forwarding Engine.

Table 1 on page 110 shows support for chained CNHs for ingress or transit routers on the MPLS network.

Table 1: Support for Chained Composite Next Hops

Platform	L2 VPN	L3 VPN	L2 CKT
PTX Series	Ingress and transit	Ingress and transit	Ingress only
MX Series	Ingress only	Ingress only	Ingress only

To enable chained CNHs on a T4000 router, the chassis must be configured to use the enhanced-mode option in network services mode.

Benefits of chained composite next hops

Chained CNH optimizes the memory and performance of the router by reducing the size of the forwarding table. The router can use the same next-hop entry in the forwarding table for routes with different destinations when the next-hop is the same. This reduces the number of entries in the forwarding table and reduces the number of changes when the next hop entry has to be modified.

Example: Configuring Chained Composite Next Hops for Direct PE-PE Connections in VPNs

IN THIS SECTION

- Requirements | 111
- Overview and Topology | 111
- Configuration | 111

Requirements


This example shows how to enable a Provider Edge (PE) router Layer 2 Virtual Private Network (VPN) connection with chained composite next hops for MIC and MPC interfaces on MX Series and T4000 routers. This example uses the following hardware and software components

- Five routers that can be a combination of MX240, MX480, MX960, or T4000 routers.
- Junos OS Release 17.3R1 or later running on all the devices.

Overview and Topology

Figure 7 on page 111 shows the sample topology of a Layer 2 VPN connection with chained composite next hops for MIC and MPC interfaces on MX series routers.

Figure 7: Chained Composite Next Hop on a PE Router



Configuration

IN THIS SECTION

- [CLI Quick Configuration | 111](#)
- [Procedure | 114](#)
- [Results | 116](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

CE1

```

set interfaces ge-1/1/1 unit 0 family inet address 192.0.2.2/24
set interfaces ge-1/1/1 unit 0 family iso
set interfaces ge-1/1/1 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 198.51.100.1/24

```

PE1

```

set interfaces ge-0/0/4 unit 0 family inet address 10.38.0.5/30
set interfaces ge-0/0/4 unit 0 family mpls
set interfaces ge-0/1/1 encapsulation ethernet-ccc
set interfaces ge-0/1/1 unit 0 family ccc
set interfaces lo0 unit 0 family inet address 10.255.104.133/32
set routing-options forwarding-table chained-composite-next-hop ingress l2vpn
set routing-options autonomous-system 200
set routing-options forwarding-table export lbpp
set protocols mpls interface ge-0/0/4.0
set protocols ospf area 0.0.0.0 interface ge-0/0/4.0
set protocols bgp group PEs type internal
set protocols bgp group PEs local-address 10.255.104.133
set protocols bgp group PEs family l2vpn signaling
set protocols bgp group PEs family inet-vpn unicast
set protocols bgp group PEs neighbor 10.255.104.134
set routing-instances vpn-a instance-type l2vpn
set routing-instances vpn-a interface ge-0/1/1.0
set routing-instances vpn-a route-distinguisher 200:1
set routing-instances vpn-a vrf-target target:200:1
set routing-instances vpn-a protocols l2vpn encapsulation-type ethernet
  set routing-instances vpn-a protocols l2vpn site 100 site-identifier 100
set routing-instances vpn-a protocols l2vpn site 100 interface ge-0/1/1.0 remote-site-id 200

```

PE2

```

set interfaces ge-1/0/2 unit 0 family inet address 10.38.0.13/30
set interfaces ge-1/0/2 unit 0 family mpls
set interfaces ge-1/0/5 encapsulation ethernet-ccc
set interfaces ge-1/0/5 unit 0 family ccc
set interfaces lo0 unit 0 family inet address 10.255.104.134/32
set routing-options forwarding-table chained-composite-next-hop ingress l2vpn
set routing-options autonomous-system 200

```

```

set routing-options forwarding-table export lbpp
set protocols mpls interface ge-1/0/2.0
set protocols ospf area 0.0.0.0 interface ge-1/0/2.0
set protocols bgp group PEs type internal
set protocols bgp group PEs local-address 10.255.104.134
set protocols bgp group PEs family l2vpn signaling
set protocols bgp group PEs family inet-vpn unicast
set protocols bgp group PEs neighbor 10.255.104.133
set routing-instances vpn-a instance-type l2vpn
set routing-instances vpn-a interface ge-1/0/5.0
set routing-instances vpn-a route-distinguisher 200:1
set routing-instances vpn-a vrf-target target:200:1
set routing-instances vpn-a protocols l2vpn encapsulation-type ethernet
set routing-instances vpn-a protocols l2vpn site 200 site-identifier 200
set routing-instances vpn-a protocols l2vpn site 200 interface ge-1/0/5.0 remote-site-id 100

```

P

```

set interfaces ge-2/0/1 unit 0 family inet address 10.38.0.6/30
set interfaces ge-2/0/1 unit 0 family mpls
set interfaces ge-2/0/2 unit 0 family inet address 10.38.0.14/30
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.104.136/32
set protocols mpls interface ge-2/0/1.0
set protocols ospf area 0.0.0.0 interface ge-2/0/1.0
set protocols mpls interface ge-2/0/2.0
set protocols ospf area 0.0.0.0 interface ge-2/0/2.0
set routing-options autonomous-system 200

```

CE2

```

set interfaces ge-2/2/2 unit 0 family inet address 192.0.2.4/24
set interfaces ge-2/2/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 198.51.100.2/24

```

Procedure

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure basic Layer 2 VPN with chained composite next hop on the PE1 router:

NOTE: Repeat this procedure for the PE2 router in the MPLS domain, after modifying the appropriate interface names, addresses, and any other parameters for the router.

1. Configure the interfaces on the PE1 router.

PE1 to CE1

[edit interfaces]

```
user@PE1# set interfaces ge-0/1/1 encapsulation ethernet-ccc
```

```
user@PE1# set interfaces ge-0/1/1 unit 0 family ccc
```

PE1 to P

[edit interfaces]

```
user@PE1 # set ge-0/0/4 unit 0 family inet address 10.38.0.5/30
```

```
user@PE1 # set ge-0/0/4 unit 0 family mpls
```

Loopback interface

[edit interfaces]

```
user@PE1 # set lo0 unit 0 family inet address 10.255.104.133/32
```

2. Enable chained composite next hop on the global Layer 2 VPN.

[edit routing-options]

```
use@PE1# set forwarding-table chained-composite-next-hop ingress l2vpn
```

3. Configure the autonomous system for PE1.

```
[edit routing-options]
user@PE1# set autonomous-system 200
```

4. Export the policy configured for load balancing.

```
[edit routing-options]
user@PE1# set forwarding-table export lbpp
```

5. Configure MPLS on the PE1 interfaces that connects to the P router.

```
[edit protocols]
set mpls interface ge-0/0/4.0
```

6. Configure OSPF on the PE1 nterface.

```
[edit protocols]
user@PE1# set ospf area 0.0.0.0 interface ge-0/0/4.0
```

7. Configure the IBGP group for PE1 to PE2 router.

```
[edit protocols]
user@PE1# set bgp group PEs type internal
user@PE1# set bgp group PEs local-address 10.255.104.133
user@PE1# set bgp group PEs family l2vpn signaling
user@PE1# set bgp group PEs family inet-vpn unicast
user@PE1# set bgp group PEs neighbor 10.255.104.134
```

8. Configure the routing instance parameters.

```
[edit routing-instances]
user@PE1# set vpn-a instance-type l2vpn
user@PE1# set vpn-a interface ge-0/1/1.0
user@PE1# set vpn-a route-distinguisher 200:1
user@PE1# set vpn-a vrf-target target:200:1
user@PE1# set vpn-a protocols l2vpn encapsulation-type ethernet
```

```

user@PE1# set vpn-a protocols l2vpn site 100 site-identifier 100
user@PE1# set vpn-a protocols l2vpn site 100 interface ge-0/1/1.0 remote-site-id 200

```

Results

From configuration mode, confirm your configuration by entering the `show chassis`, `show interfaces`, `show protocols`, `show routing-options`, `show routing-instances`, and `show policy-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

PE1

```

user@PE1# show interfaces
ge-0/0/4 {
  unit 0 {
    family inet {
      address 10.38.0.5/30;
    }
    family mpls;
  }
}
ge-0/1/1 {
  encapsulation ethernet-ccc;
  unit 0 {
    family iso;
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.255.104.133/32;
    }
  }
}

```

```

user@PE1# show protocols
mpls {
  interface ge0/0/4.0;
}

```

```

bgp {
  group PEs {
    type internal;
    local-address 10.255.104.133;
    family inet-vpn {
      unicast;
    }
    family l2vpn {
      signaling;
    }
    neighbor 10.255.104.134;
  }
}
ospf {
  area 0.0.0.0 {
    interface ge-0/0/4.0;
  }
}

```

```

user@PE1# show routing-options
autonomous-system 200;
forwarding-table {
  export lbpp;
  chained-composite-next-hop {
    ingress {
      l2vpn;
    }
  }
}

```

```

user@PE1# show routing-instances
vpn-a {
  instance-type l2vpn;
  interface ge-0/1/1.0;
  route-distinguisher 200:1;
  vrf-target target:200:1;
  protocols {
    l2vpn {
      encapsulation-type ethernet;
      site 100 {

```



```
        site-identifier 100;  
        interface ge-0/1/1.0 {  
            remote-site-id 200;  
        }  
    }  
}  
}
```

Configuring Graceful Restart for VPNs

IN THIS CHAPTER

- [VPN Graceful Restart | 119](#)
- [Configuring Graceful Restart for VPNs | 120](#)
- [Enabling Unicast Reverse-Path Forwarding Check for VPNs | 123](#)
- [Understanding and Preventing Unknown Unicast Forwarding | 124](#)

VPN Graceful Restart

IN THIS SECTION

- [Benefit of a VPN graceful restart | 120](#)

With routing protocols, any service interruption requires that an affected router recalculate adjacencies with neighboring routers, restore routing table entries, and update other protocol-specific information. An unprotected restart of the router results in forwarding delays, route flapping, wait times stemming from protocol reconvergence, and even dropped packets. Graceful restart allows a routing device undergoing a restart to inform its adjacent neighbors and peers of its condition. During a graceful restart, the restarting device and its neighbors continue forwarding packets without disrupting network performance.

For VPN graceful restart to function properly, the following items need to be configured on the PE router:

- BGP graceful restart must be active on the PE-to-PE sessions carrying any service-signaling data in the session's network layer reachability information (NLRI).
- OSPF, IS-IS, LDP, and RSVP graceful restart must be active, because routes added by these protocols are used to resolve VPN NLRIs.

- For other protocols (static, Routing Information Protocol [RIP], and so on), graceful restart functionality must also be active when these protocols are run between the PE and CE routers. Layer 2 VPNs do not rely on this, because protocols are not configured between the PE and CE routers.

In VPN graceful restart, a restarting router completes the following procedures:

- Waits for all the BGP NLRI information from other PE routers before it starts advertising routes to its CE routers.
- Waits for all protocols in all routing instances to converge (or finish graceful restart) before sending CE router information to the other PE routers.
- Waits for all routing instance information (whether it is local configuration or advertisements from a remote peer router) to be processed before sending it to the other PE routers.
- Preserves all forwarding state information in the MPLS routing tables until new labels and transit routes are allocated and then advertises them to other PE routers (and CE routers in carrier-of-carriers VPNs).

Graceful restart is supported on Layer 2 VPNs, Layer 3 VPNs, and virtual-router routing instances.

Benefit of a VPN graceful restart

The main benefit of a VPN graceful restart is that it allows a router whose VPN control plane is undergoing a restart to continue to forward traffic while recovering its state from neighboring routers. It temporarily suppresses all routing protocol updates and enables a router to pass through intermediate convergence states that are hidden from the rest of the network. Without graceful restart, a control plane restart disrupts the VPN services provided by the router.

Configuring Graceful Restart for VPNs

You can configure graceful restart to enable a router to pass through intermediate convergence states that are hidden from the rest of the network. Graceful restart allows a router whose VPN control plane is undergoing a restart (restarting router) to continue to forward traffic while recovering its state from neighboring routers (helper routers).

The restarting router requests a grace period from the neighbor or peer, which can then cooperate with the restarting router. When a restart event occurs and graceful restart is enabled, the restarting router can still forward traffic during the restart period, and convergence in the network is not disrupted. The helper routers hide the restart event from other devices not directly connected to the restarting router. In other words, the restart is not visible to the rest of the network, and the restarting router is not removed from the network topology.

Without graceful restart, a control plane restart disrupts any VPN services provided by the router. Graceful restart is supported on Layer 2 VPNs, Layer 3 VPNs, virtual-router routing instances, and VPLS.

The graceful restart request occurs only if the following conditions are met:

- The network topology is stable.
- The neighbor or peer routers cooperate.
- The restarting router is not already cooperating with another restart already in progress.
- The grace period does not expire.

Before you begin:

- Configure the devices for network communication.
- Configure the device interfaces.

Graceful restart is disabled by default. To enable VPN graceful restart:

1. Configure graceful restart globally.

```
[edit routing-options]  
user@host# set graceful-restart
```

NOTE:

- Graceful restart can be enabled on logical systems. To configure graceful restart globally, include the graceful-restart statement at the [edit logical-systems *logical-system-name* routing-options] or the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* routing-options] hierarchy levels.
- To disable graceful restart globally, include the disable statement at the [edit routing-options graceful-restart] hierarchy level.

For example:

```
[edit routing-options]  
user@host# set graceful-restart disable
```

2. Enable or disable graceful restart on a per-protocol, per-group, or per-neighbor basis, depending on the specific protocol, where the most specific definition is used.

```
[edit protocols]
user@host# set bgp graceful-restart
user@host# set bgp group group-name type internal local-address local-ip-address neighbor
neighbor1-address
user@host# set bgp group group-name type internal local-address local-ip-address neighbor
neighbor2-address graceful-restart disable
```

3. Configure graceful restart for Layer 3 VPNS for all routing and MPLS-related protocols within a routing instance. Because you can configure multi-instance BGP and multi-instance LDP, graceful restart for a carrier-of-carriers scenario is supported.

```
[edit routing-instance]
user@host# set routing-instance-name routing-options graceful-restart
```

NOTE:

- To disable graceful restart globally, include the disable statement at the [edit routing-instances *routing-instance-name* routing-options graceful-restart] hierarchy level.

For example:

```
[edit routing-instances]
user@host# set instance1 routing-options graceful-restart disable
```

- To disable graceful restart for individual protocols, include the disable statement at the [edit routing-instances *routing-instance-name* protocols *protocol-name* graceful-restart] hierarchy level.

For example:

```
[edit routing-instances]
user@host# set instance1 protocols ospf graceful-restart disable
```

4. Configure the duration of the graceful restart period for the routing instance.

```
[edit routing-options]
user@host# set graceful-restart restart-duration seconds
```

The `restart-duration` option sets the period of time that the router waits for a graceful restart to be completed. You can configure a time between 1 through 600 seconds. The default value is 300 seconds. At the end of the configured time period, the router performs a standard restart without recovering its state from the neighboring routers. This disrupts VPN services, but is probably necessary if the router is not functioning normally.

NOTE: You can include the `restart-duration` option at either the global or routing instance level.

Enabling Unicast Reverse-Path Forwarding Check for VPNs

IP spoofing may occur during a denial-of-service (DoS) attack. IP spoofing allows an intruder to pass IP packets to a destination as genuine traffic, when in fact the packets are not actually meant for the destination. This type of spoofing is harmful because it consumes the destination's resources.

Unicast reverse-path forwarding (RPF) check is a tool to reduce forwarding of IP packets that may be spoofing an address. A unicast RPF check performs a route table lookup on an IP packet's source address, and checks the incoming interface. The router determines whether the packet is arriving from a path that the sender would use to reach the destination. If the packet is from a valid path, the router forwards the packet to the destination address. If it is not from a valid path, the router discards the packet. Unicast RPF is supported for the IPv4 and IPv6 protocol families, as well as for the virtual private network (VPN) address family. You can also enable unicast RPF within a VPN routing instance.

To enable unicast RPF check, include the `unicast-reverse-path` statement:

```
unicast-reverse-path (active-paths | feasible-paths);
```

For a list of hierarchy levels at which you can configure this statement, see the statement summary section for this statement.

To consider only active paths during the unicast RPF check, include the `active-paths` option. To consider all feasible paths during the unicast RPF check, include the `feasible-paths` option.

For more information about how to configure the `unicast-reverse-path` statement, see *Example: Configuring Unicast RPF (On a Router)* and .

RELATED DOCUMENTATION

| *Example: Configuring Unicast RPF (On a Router)*

Understanding and Preventing Unknown Unicast Forwarding

IN THIS SECTION

- [Verifying That Unknown Unicast Packets Are Forwarded to a Single Interface | 124](#)
- [Configuring Unknown Unicast Forwarding \(ELS\) | 126](#)
- [Verifying That Unknown Unicast Packets Are Forwarded to a Trunk Interface | 129](#)
- [Configuring Unknown Unicast Forwarding \(CLI Procedure\) | 130](#)

Unknown unicast traffic consists of unicast packets with unknown destination MAC addresses. By default, the switch floods these unicast packets that traverse a VLAN to all interfaces that are members of that VLAN. Forwarding this type of traffic can create unnecessary traffic that leads to poor network performance or even a complete loss of network service. This flooding of packets is known as a traffic storm.

To prevent a traffic storm, you can disable the flooding of unknown unicast packets to all VLAN interfaces by configuring specific VLANs or all VLANs to forward all unknown unicast traffic traversing them to a specific interface. You can configure multiple VLANs to forward unknown unicast packets to the same interface or configure different interfaces for different VLANs. This channels the unknown unicast traffic traversing VLANs to specific interfaces instead of flooding all interfaces.

Verifying That Unknown Unicast Packets Are Forwarded to a Single Interface

IN THIS SECTION

- [Purpose | 125](#)
- [Action | 125](#)
- [Meaning | 125](#)

Purpose

Verify that a VLAN is forwarding all unknown unicast packets (those with unknown destination MAC addresses) to a single interface instead of flooding unknown unicast packets across all interfaces that are members of that VLAN.

NOTE: This procedure uses Junos OS for EX Series switches with support for the Enhanced Layer 2 Software (ELS) configuration style. For ELS details see: [Using the Enhanced Layer 2 Software CLI](#).

Action

(EX4300 Switches) Display the forwarding interface for unknown unicast packets for a VLAN (here, the VLAN name is v1):

```
user@switch> show configuration switch-options

unknown-unicast-forwarding {
  vlan v1 {
    interface ge-0/0/7.0;
  }
}
```

(EX9200 Switches) Display the forwarding interface for unknown unicast packets:

```
user@switch> show forwarding-options

next-hop-group uuf-nhg {
  group-type layer-2;
  interface ge-0/0/7.0;
}
```

Meaning

The sample output from the `show` commands show that the unknown unicast forwarding interface for VLAN v1 is interface `ge-0/0/7`.

Configuring Unknown Unicast Forwarding (ELS)

IN THIS SECTION

- [Configuring Unknown Unicast Forwarding on EX4300 Switches | 126](#)
- [Configuring Unknown Unicast Forwarding on EX9200 Switches | 127](#)

NOTE: This task uses Junos OS for EX Series switches or QFX Series with support for the Enhanced Layer 2 Software (ELS) configuration style. For ELS details, see [Using the Enhanced Layer 2 Software CLI](#)

Unknown unicast traffic consists of packets with unknown destination MAC addresses. By default, the switch floods these packets that traverse a VLAN to all interfaces associated with that VLAN. This flooding of packets is known as a traffic storm and can negatively impact network performance.

To prevent flooding unknown unicast traffic across the switch, configure unknown unicast forwarding to direct all unknown unicast packets within a VLAN to a specific interface. You can configure each VLAN to divert unknown unicast traffic to a different interface or use the same interface for multiple VLANs.

Configuring Unknown Unicast Forwarding on EX4300 Switches

To configure unknown unicast forwarding options on EX4300 switches:

- Configure unknown unicast forwarding for a specific VLAN and specify the interface to which all unknown unicast traffic will be forwarded:

```
[edit switch-options]
user@switch# set unknown-unicast-forwarding vlan vlan-name interface interface-name
```

- Configure unknown unicast forwarding for all VLANs and specify the interface to which all unknown unicast traffic will be forwarded:

```
[edit switch-options]
user@switch# set unknown-unicast-forwarding vlan all interface interface-name
```

Configuring Unknown Unicast Forwarding on EX9200 Switches

To configure unknown unicast forwarding on EX9200 switches, you must configure a flood filter and apply it to VLANs for which you want to configure unknown unicast forwarding. Flood filters are firewall filters that are applied only to broadcast, unknown unicast, and multicast (BUM) traffic. If a flood filter is configured, only traffic packets that are of the packet type `unknown-unicast` are forwarded to the interface on which unicast forwarding is configured. A next-hop group redirects the packets according to the action specified in the flood filter.

To configure the next-hop group that receives Layer 2 packets and then configure the interface to which these packets are forwarded:

1. Configure the `next-hop-group` action for the Layer 2 interface expected to receive unknown unicast packets:

```
[edit forwarding-options]
user@switch# set next-hop-group next-hop-group-name group-type layer-2
[edit forwarding-options]
user@switch# set next-hop-group next-hop-group-name interface interface-name
```

For example:

```
[edit forwarding-options]
user@switch# set next-hop-group uuf-nhg group-type layer-2
[edit forwarding-options]
user@switch# set next-hop-group uuf-nhg interface ge-3/1/7.0
```

2. Configure a firewall filter with family address type `ethernet-switching`:

```
[edit firewall]
user@switch# set family ethernet-switching filter filter-name
```

For example:

```
[edit firewall]
user@switch# set family ethernet-switching filter uuf_filter
```

3. Configure a term in the firewall filter for the interface that receives unknown unicast packets (the interface specified in Step 1) to discard unknown unicast packets:

```
[edit firewall family ethernet-switching filter filter-name]
user@switch# set term term-name from interface interface-name
user@switch# set term term-name from traffic-type unknown-unicast
user@switch# set term term-name then discard
```

For example:

```
[edit firewall family ethernet-switching filter uuf_filter]
user@switch# set term source-drop from interface ge-3/1/7.0
user@switch# set term source-drop from traffic-type unknown-unicast
user@switch# set term source-drop then discard
```

4. Configure a term in the firewall filter for unknown unicast packets to be flooded to the interface enabled for unknown unicast forwarding by using next-hop-group (in step 1):

```
[edit firewall family ethernet-switching filter filter-name]

user@switch# set term term-name from traffic-type unknown-unicast
user@switch# set term term-name then next-hop-group group-name
```

For example:

```
[edit firewall family ethernet-switching filter uuf_filter]

user@switch# set term uuf-flood from traffic-type unknown-unicast
user@switch# set term uuf-flood then next-hop-group uuf-nhg
```

5. Configure a default term for the firewall filter to forward packets other than unknown unicast packets:

```
[edit firewall family ethernet-switching filter filter-name]

user@switch# set term term-name then accept
```

For example:

```
[edit firewall family ethernet-switching filter uuf_filter]

user@switch# set term fwd-default then accept
```

6. Apply the filter as a flood filter on the VLAN that includes the interface which will receive unknown unicast packets:

```
[edit vlans vlan-name]

user@switch# set forwarding-options flood input filter-name
```

For example:

```
[edit vlans v1]

user@switch# set forwarding-options flood input uuf_filter
```

Verifying That Unknown Unicast Packets Are Forwarded to a Trunk Interface

IN THIS SECTION

- Purpose | 129
- Action | 130
- Meaning | 130

Purpose

Verify that a VLAN is forwarding all unknown unicast packets (those with unknown destination MAC addresses) to a single trunk interface instead of flooding unknown unicast packets across all interfaces that are members of the same VLAN.

Action

Display the forwarding interface for unknown unicast packets for a VLAN (here, the VLAN name is **v1**):

```
user@switch> show configuration ethernet-switching-options

unknown-unicast-forwarding {
    vlan v1 {
        interface ge-0/0/7.0;
    }
}
```

Display the Ethernet switching table:

```
user@switch> show ethernet-switching table vlan v1
Ethernet-switching table: 3 unicast entries
```

VLAN	MAC address	Type	Age	Interfaces
v1	*	Flood		- All-members
v1	00:01:09:00:00:00	Learn	24	ge-0/0/7.0
v1	00:11:09:00:01:00	Learn	37	ge-0/0/3.0

Meaning

The sample output from the `show configuration ethernet-switching-options` command shows that the unknown unicast forwarding interface for VLAN **v1** is interface **ge-0/0/7**. The `show ethernet-switching table` command shows that an unknown unicast packet is received on interface **ge-0/0/3** with the destination MAC address (DMAC) **00:01:09:00:00:00** and the source MAC address (SMAC) of **00:11:09:00:01:00**. This shows that the SMAC of the packet is learned in the normal way (through the interface **ge-0/0/3.0**), while the DMAC is learned on interface **ge-0/0/7**.

Configuring Unknown Unicast Forwarding (CLI Procedure)

Unknown unicast traffic consists of packets with unknown destination MAC addresses. By default, the switch floods these packets to all interfaces associated with a VLAN. Forwarding such traffic to interfaces on the switch can create a security issue.

To prevent flooding unknown unicast traffic across the switch, configure unknown unicast forwarding to direct all unknown unicast packets within a VLAN out to a specific trunk interface. From there, the

destination MAC address can be learned and added to the Ethernet switching table. You can configure each VLAN to divert unknown unicast traffic to different trunk interfaces or use one trunk interface for multiple VLANs.

NOTE: For Junos OS for EX Series switches or QFX Series with support for the Enhanced Layer 2 Software (ELS) configuration style, see *Configuring Unknown Unicast Forwarding (ELS)*.

To configure unknown unicast forwarding options:

NOTE: Before you can configure unknown unicast forwarding within a VLAN, you must first configure that VLAN.

1. Configure unknown unicast forwarding for a specific VLAN (here, the VLAN name is **employee**):

```
[edit ethernet-switching-options]
user@switch# set unknown-unicast-forwarding vlan employee
```

2. Specify the trunk interface to which all unknown unicast traffic will be forwarded:

```
[edit ethernet-switching-options]
user@switch# set unknown-unicast-forwarding vlan employee interface ge-0/0/3.0
```

RELATED DOCUMENTATION

[Understanding Storm Control](#)

[Configuring Autorecovery for Port Security Events](#)

Configuring Class of Service for VPNs

IN THIS CHAPTER

- VPNs and Class of Service | 132
- Rewriting Class of Service Markers and VPNs | 132

VPNs and Class of Service

You can configure Junos class-of-service (CoS) features to provide multiple classes of service for VPNs. The CoS features are supported on Layer2 VPNs, Layer 3 VPNs, and VPLS. On the router, you can configure multiple forwarding classes for transmitting packets, define which packets are placed into each output queue, schedule the transmission service level for each queue, and manage congestion using a random early detection (RED) algorithm.

VPNs use the standard CoS configuration.

Rewriting Class of Service Markers and VPNs

A marker reads the current forwarding class and loss priority information associated with a packet and finds the chosen code point from a table. It then writes the code point information into the packet header. Entries in a marker configuration represent the mapping of the current forwarding class into a new forwarding class, to be written into the header.

You define markers in the *rewrite rules* section of the class-of-service (CoS) configuration hierarchy and reference them in the *logical interface* configuration. You can configure different rewrite rules to handle VPN traffic and non-VPN traffic. The rewrite rule can be applied to MPLS and IPv4 packet headers simultaneously, making it possible to initialize MPLS experimental (EXP) and IP precedence bits at LSP ingress.

For a detailed example of how to configure rewrite rules for MPLS and IPv4 packets and for more information about how to configure statements at the [edit class-of-service] hierarchy level, see the [Class of Service User Guide \(Routers and EX9200 Switches\)](#).

Pinging VPNs

IN THIS CHAPTER

- Pinging VPNs, VPLS, and Layer 2 Circuits | 133
- Setting the Forwarding Class of the Ping Packets | 134
- Pinging a VPLS Routing Instance | 134
- Pinging a Layer 2 VPN | 135
- Pinging a Layer 3 VPN | 136
- Pinging a Layer 2 Circuit | 136
- Pinging Customer Edge Device IP Address | 136

Pinging VPNs, VPLS, and Layer 2 Circuits

For testing purposes, you can ping Layer 2 VPNs, Layer 3 VPNs, and Layer 2 circuits by using the `ping mpls` command. The `ping mpls` command helps to verify that a VPN or circuit has been enabled and tests the integrity of the VPN or Layer 2 circuit connection between the PE routers. It does not test the connection between a PE router and a CE router. To ping a VPLS routing instance, you issue a `ping vpls instance` command (see *Pinging a VPLS Routing Instance*).

You issue the `ping mpls` command from the ingress PE router of the VPN or Layer 2 circuit to the egress PE router of the same VPN or Layer 2 circuit. When you execute the `ping mpls` command, echo requests are sent as MPLS packets.

The payload is a User Datagram Protocol (UDP) packet forwarded to the address 127.0.0.1. The contents of this packet are defined in RFC 4379, *Detecting Multi-Protocol Label Switched (MPLS) Data Plane Failures*. The label and interface information for building and sending this information as an MPLS packet is the same as for standard VPN traffic, but the time-to-live (TTL) of the innermost label is set to 1.

When the echo request arrives at the egress PE router, the contents of the packet are checked, and then a reply that contains the correct return is sent by means of UDP. The PE router sending the echo request waits to receive an echo reply after a timeout of 2 seconds (you cannot configure this value).

You must configure MPLS at the `[edit protocols mpls]` hierarchy level on the egress PE router (the router receiving the MPLS echo packets) to be able to ping the VPN or Layer 2 circuit. You must also configure the address 127.0.0.1/32 on the egress PE router's `lo0` interface. If this is not configured, the egress PE router does not have this forwarding entry and therefore simply drops the incoming MPLS pings.

The `ping mpls` command has the following limitations:

- You cannot ping an IPv6 destination prefix.
- You cannot ping a VPN or Layer 2 circuit from a router that is attempting a graceful restart.
- You cannot ping a VPN or Layer 2 circuit from a logical system.

You can also determine whether an LSP linking two PE routers in a VPN is up by pinging the end point address of the LSP. The command you use to ping an MPLS LSP end point is `ping mpls lsp-end-point address`. This command tells you what type of LSP (RSVP or LDP) terminates at the address specified and whether that LSP is up or down.

For a detailed description of this command, see the *Junos Routing Protocols and Policies Command Reference*.

Setting the Forwarding Class of the Ping Packets

When you execute the `ping mpls` command, the ping packets forwarded to the destination include MPLS labels. It is possible to set the value of the forwarding class for these ping packets by using the `exp` option with the `ping mpls` command. For example, to set the forwarding class to 5 when pinging a Layer 3 VPN, issue the following command:

```
ping mpls l3vpn westcoast source 192.0.2.0 prefix 192.0.2.1 exp 5 count 20 detail
```

This command would make the router attempt to ping the Layer 3 VPN `westcoast` using ping packets with an EXP forwarding class of 5. The default forwarding class used for the `ping mpls` command packets is 7.

Pinging a VPLS Routing Instance

The `ping vpls instance` command uses a different command structure and operates in a different fashion than the `ping mpls` command used for VPNs and Layer 2 circuits. The `ping vpls instance` command is only supported on MX Series routers, the M120 router, the M320 router, and the T1600 router.

To ping a VPLS routing instance, use the following command:

```
ping vpls instance instance-name destination-mac address source-ip address <count number> <data-plane-response> <detail> <learning-vlan-id number> <logical-system logical-system-name>
```

Pinging a VPLS routing instance requires using the `ping vpls instance` command with a combination of the routing instance name, the destination MAC address, and the source IP address (IP address of the outgoing interface).

When you run this command, you are provided feedback on the status of your request. An exclamation point (!) indicates that an echo reply was received. A period (.) indicates that an echo reply was not received within the timeout period. An x indicates that an echo reply was received with an error code these packets are not counted in the received packets count. They are accounted for separately.

For more details, including argument descriptions and additional options, see [ping vpls instance](#).

Pinging a Layer 2 VPN

To ping a Layer 2 VPN, use one of the following commands:

- `ping mpls l2vpn interface interface-name`

You ping an interface configured for the Layer 2 VPN on the egress PE router.

- `ping mpls l2vpn instance l2vpn-instance-name local-site-id local-site-id-number remote-site-id remote-site-id-number`

You ping a combination of the Layer 2 VPN routing instance name, the local site identifier, and the remote site identifier to test the integrity of the Layer 2 VPN connection (specified by the identifiers) between the ingress and egress PE routers.

RELATED DOCUMENTATION

| [Example: Configure MPLS-Based Layer 2 VPNs](#) | 179

Pinging a Layer 3 VPN

To ping a Layer 3 VPN, use the following command:

```
ping mpls l3vpn l3vpn-name prefix prefix <count count>
```

You ping a combination of an IPv4 destination prefix and a Layer 3 VPN name on the egress PE router to test the integrity of the VPN connection between the ingress and egress PE routers. The destination prefix corresponds to a prefix in the Layer 3 VPN. However, the ping tests only whether the prefix is present in a PE router's VRF table. It does not test the connection between a PE router and a CE router.

Pinging a Layer 2 Circuit

To ping a Layer 2 circuit, use one of the following commands:

- `ping mpls l2circuit interface interface-name`

You ping an interface configured for the Layer 2 circuit on the egress PE router.

- `ping mpls l2circuit virtual-circuit neighbor <prefix> <virtual-circuit-id>`

You ping a combination of the IPv4 prefix and the virtual circuit identifier on the egress PE router to test the integrity of the Layer 2 circuit between the ingress and egress PE routers.

Pinging Customer Edge Device IP Address

IN THIS SECTION

- [VPLS or EVPN Use Case | 137](#)
- [H-VPLS Use Case | 138](#)
- [Supported and Unsupported Features for CE-IP Ping | 140](#)

In a virtual private LAN service (VPLS), hierarchical VPLS (H-VPLS), and Ethernet VPN (EVPN) network, you can test the connectivity to a given customer edge (CE) IP address to get the CE device's MAC address and attachment points (name of the provider edge [PE] device and local interfaces) to the

provider network. This is beneficial in Layer 2 VPN technologies, which have a large number of PE devices and for which getting connectivity information about customers is a challenge.


The capability to ping CE IP address has the following use cases and feature support:

VPLS or EVPN Use Case

Prior to Junos OS Release 17.3R1, the ping utility for VPLS was for destination MAC addresses. Junos OS Release 17.3R1 introduces the CE-IP ping utility, which is based on the LSP ping infrastructure defined in RFC 4379. With the CE-IP ping feature, the ping utility is enhanced with the capability to ping an IP address for a VPLS and EVPN network. Separate unicast LSP ping echo requests are sent to all neighboring PE devices, and only one PE device responds back with the information about the CE device.

Figure 8 on page 137 illustrates a use case for implementing the CE-IP ping feature in a VPLS or EVPN network. There are three PE devices—Devices PE1, PE2, and PE3—connected to four customer sites—Devices CE1, CE2, CE3, and CE4. In this use case, Device PE1 tests the connectivity to an IP host—10.0.0.2—to get the MAC address and attachment point of the host in the VPLS or EVPN service provider network for a specific routing instance. This is done using the `ce-ip` command. The command output displays the required information depending on the type of routing instance configured.

Figure 8: CE-IP Ping Feature in a VPLS/EVPN Network



When the `ce-ip ping` command is executed in a VPLS or EVPN network, the packet flow is as follows:

1. 1—LSP ping echo request

The `ce-ip` LSP ping echo request packet is sent using the data plane.

Device PE1 sends an LSP ping echo request to all the neighboring PE devices, Devices PE2 and PE3. The IP address to the target host is carried in the LSP ping echo request using type, length, and value (TLV).

2. 2—ARP request

Remote PE devices send host-injected Address Resolution Protocol (ARP) requests on all the CE-facing interfaces for the destination IP address. The ARP request is sent to the host 10.0.0.2 from Device PE2 to Device CE2 and from Device PE3 to Devices CE3 and CE4. The source IP address in the ARP request is set to 0.0.0.0 by default.

3. 3—ARP response

Device CE2 responds to the ARP request from Device PE2.

4. 4—LSP ping echo response

If an ARP response is received from a CE device, the remote PE device responds to the PE device initiating the ARP request with the MAC address and attachment point encoded as TLV in the LSP ping echo response packet.

The `ce-ip` LSP ping echo response packet is sent using IP/UDP protocol in the control plane.

Device PE2 sends an LSP ping response to Device PE1. The other remote PE device, Device PE3, does not respond to the LSP ping because an ARP response is not received from Device CE3.


The output of the `ce-ip ping` command on Device PE1 displays the information that is received from the LSP ping response.

H-VPLS Use Case

In a VPLS or EVPN network, all the PE devices are connected in a mesh topology and therefore the devices are reachable to each other through one hop in terms of virtual circuit label reachability. However, in an H-VPLS network, there are spoke PE devices connected to the VPLS full-mesh network. These spoke PE devices cannot be reached by the remote PE devices through one hop. Because the VPLS ping feature always uses a virtual circuit label TTL value of one, the ping packets are received by the control plane in all the PE devices that are one hop away. The control plane then reinjects the ping packets to the next hop (that is, the spoke PE device) in the H-VPLS network for the ping packet to reach all the PE devices.

Figure 9 on page 139 illustrates a use case for implementing the CE-IP ping feature in an H-VPLS network. There are three PE devices—Devices PE1, PE2, and PE3—connected to four customer sites—Devices CE1, CE2, CE3, and CE4. Device PE3 is connected to an H-VPLS spoke that connects to Device CE4. In this use case, Device PE1 tests the connectivity to an IP host— 10.0.0.4—to get the MAC address and attachment point of the host in the H-VPLS service provider network using the `ce-ip` command.

Figure 9: CE-IP Ping Feature in H-VPLS Network



When the `ce-ip` ping command is executed in an H-VPLS network, the packet flow is as follows:

1. 1—LSP ping echo request

The `ce-ip` LSP ping echo request packet is sent using the data plane.

Device PE1 sends an LSP ping echo request to all the neighboring PE devices, Devices PE2 and PE3. The IP address to the target host is carried in the LSP ping echo request using type, length, and value (TLV).

2. 1A—LSP re-injected ping request

Device PE3 re-injects the LSP ping request to the spoke PE device, Device HPE3.

3. 2—ARP request

The remote PE devices, Devices PE2 and PE3, and the spoke PE device, Device HPE3, send host-injected ARP requests on all the CE-facing interfaces for the destination IP address. The ARP request is sent to the host 10.0.0.4. The source IP address in the ARP request is set to 0.0.0.0 by default.

4. 3—ARP response

Device CE4 responds to the ARP request from Device HPE3.

5. 4—LSP ping echo response

If an ARP response is received from a CE device, the remote PE device responds to the PE device initiating the ARP request with the MAC address and attachment point encoded as TLV in the LSP ping echo response packet.

The ce-ip LSP ping echo response packet is sent using IP/UDP protocol in the control plane.

Device HPE3 sends an LSP ping response to Device PE1. The other remote PE devices, Device PE2 and PE3, do not respond to the LSP ping because they do not receive an ARP response from the CE device.

Supported and Unsupported Features for CE-IP Ping

The following features are supported with the CE-IP address ping feature:

- The CE-IP ping feature in a VPLS or H-VPLS network is supported on routing instance type VPLS only
- The CE-IP ping feature in an EVPN network is supported on routing instance type EVPN only.
- Support for VPLS and EVPN hybrid routing instances, where the routing instance type is EVPN and the CE-IP ping support is available on single-homing seamless migration nodes with LDP-VPLS only.

The CE-IP ping feature has the following considerations and limitations:

- If the CE destination IP address that is being pinged is behind the very same PE device where the ping command is issued, the ce-ip ping functionality does not work.
- The LSP ping echo response packet is always sent using the IP/UDP protocol in the control plane. This requires that the PE devices are IP reachable to each other for the feature to work.
- The CE-IP feature does not provide support for the following:
 - Virtual switch routing instance
 - IPv6 addresses
 - Logical systems
 - Integrated routing and bridging (IRB) configured in the EVPN or VPLS routing instance

RELATED DOCUMENTATION

[Pinging LSPs](#)

Pinging VPNs, VPLS, and Layer 2 Circuits

[Pinging a Layer 2 VPN | 135](#)

Pinging a VPLS Routing Instance

[ping](#)

2

PART

Common Configuration for Layer 2 VPNs and VPLS

[Overview | 143](#)

[Layer 2 VPNs Configuration Overview | 147](#)

[Configuring Layer 2 Interfaces | 209](#)

[Configuring Path Selection for Layer 2 VPNs and VPLS | 215](#)

[Creating Backup Connections with Redundant Pseudowires | 223](#)

[Configuring Class of Service for Layer 2 VPNs | 229](#)

[Monitoring Layer 2 VPNs | 231](#)

Overview

IN THIS CHAPTER

- Understanding Layer 2 VPNs | 143
- Layer 2 VPN Applications | 145
- Supported Layer 2 VPN Standards | 145

Understanding Layer 2 VPNs

NOTE: On EX9200 switches, graceful Routing Engine switchover (GRES), nonstop active routing (NSR), and logical systems are not supported on Layer 2 VPN configurations. Layer 2 VPN is not supported on the EX9200 Virtual Chassis.

As the need to link different Layer 2 services to one another for expanded service offerings grows, Layer 2 Multiprotocol Label Switching (*MPLS*) VPN services are increasingly in demand.


Implementing a Layer 2 VPN on a router is similar to implementing a VPN using a Layer 2 technology such as Asynchronous Transfer Mode (ATM) or Frame Relay. However, for a Layer 2 VPN on a router, traffic is forwarded to the router in a Layer 2 format. It is carried by MPLS over the service provider's network, and then converted back to Layer 2 format at the receiving site. You can configure different Layer 2 formats at the sending and receiving sites. The security and privacy of an MPLS Layer 2 VPN are equal to those of an ATM or Frame Relay VPN. The service provisioned with Layer 2 VPNs is also known as *Virtual Private Wire Service (VPWS)*.

On a Layer 2 VPN, routing occurs on the customer's routers, typically on the customer edge (CE) router. The CE router connected to a service provider on a Layer 2 VPN must select the appropriate circuit on which to send traffic. The provider edge (PE) router receiving the traffic sends it across the service provider's network to the PE router connected to the receiving site. The PE routers do not need to store or process the customer's routes; they only need to be configured to send data to the appropriate tunnel.

For a Layer 2 VPN, customers need to configure their own routers to carry all Layer 3 traffic. The service provider needs to know only how much traffic the Layer 2 VPN will need to carry. The service provider's routers carry traffic between the customer's sites using Layer 2 VPN interfaces. The VPN topology is determined by policies configured on the PE routers.

Customers need to know only which VPN interfaces connect to which of their own sites. [Figure 10 on page 144](#) illustrates a Layer 2 VPN in which each site has a VPN interface linked to each of the other customer sites.

Figure 10: Layer 2 VPN Connecting CE Routers



Implementing a Layer 2 MPLS VPN includes the following benefits:

- Service providers do not have to invest in separate Layer 2 equipment to provide Layer 2 VPN service. A Layer 2 MPLS VPN allows you to provide Layer 2 VPN service over an existing IP and MPLS backbone.
- You can configure the PE router to run any Layer 3 protocol in addition to the Layer 2 protocols.
- Customers who prefer to maintain control over most of the administration of their own networks might want Layer 2 VPN connections with their service provider instead of a Layer 3 VPN.
- Because Layer 2 VPNs use *BGP* as the signaling protocol, they have a simpler design and require less overhead than traditional VPNs over Layer 2 circuits. BGP signaling also enables autodiscovery of Layer 2 VPN peers. Layer 2 VPNs are similar to BGP or MPLS VPNs and *VPLS* in many respects; all three types of services employ BGP for signaling.

Layer 2 VPN Applications

Implementing a Layer 2 VPN includes the following benefits:

- Terminating a Layer 2 VPN into a Layer 2 VPN using the interworking (iw0) software interface eliminates the limitation of bandwidth on the tunnel interfaces used for these configuration scenarios. Instead of using a physical Tunnel PIC for looping the packet received from the Layer 2 VPN to another Layer 2 VPN, Junos OS is used to link both the Layer 2 VPN routes.
- Layer 2 VPNs enable the sharing of a provider's core network infrastructure between IP and Layer 2 VPN services, reducing the cost of providing those services. A Layer 2 MPLS VPN allows you to provide Layer 2 VPN service over an existing IP and MPLS backbone.
- From a service provider's point of view, a Layer 2 MPLS VPN allows the use of a single Layer 3 VPN (such as RFC 2547bis), MPLS traffic engineering, and Differentiated Services (DiffServ).
- Service providers do not have to invest in separate Layer 2 equipment to provide Layer 2 VPN service. You can configure the PE router to run any Layer 3 protocol in addition to the Layer 2 protocols. Customers who prefer to maintain control over most of the administration of their own networks might want Layer 2 VPN connections with their service provider instead of a Layer 3 VPN.

RELATED DOCUMENTATION

[Understanding Layer 2 VPNs | 143](#)

[Using the Layer 2 Interworking Interface to Interconnect a Layer 2 Circuit to a Layer 2 VPN | 1321](#)

[Using the Layer 2 Interworking Interface to Interconnect a Layer 2 VPN to a Layer 2 VPN | 1264](#)

[Example: Interconnecting a Layer 2 Circuit with a Layer 2 VPN | 1323](#)

[Example: Interconnecting a Layer 2 VPN with a Layer 2 VPN | 1266](#)

Example: Interconnecting a Layer 2 VPN with a Layer 3 VPN

Supported Layer 2 VPN Standards

Junos OS substantially supports the following standards and Internet drafts, which define standards for Layer 2 virtual private networks (VPNs).

- RFC 7348, *Virtual eXtensible Local Area Network (VXLAN): A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks*
- Internet draft draft-kompella-l2vpn-vpls-multihoming, *Multi-homing in BGP-based Virtual Private LAN Service*

- Internet draft draft-kompella-ppvpn-l2vpn-03.txt, *Layer 2 VPNs Over Tunnels*

RELATED DOCUMENTATION

Supported Carrier-of-Carriers and Interprovider VPN Standards

[Supported VPWS Standards | 502](#)

Supported Layer 3 VPN Standards

Supported Multicast VPN Standards

[Supported VPLS Standards | 614](#)

[Accessing Standards Documents on the Internet](#)

Layer 2 VPNs Configuration Overview

IN THIS CHAPTER

- [Introduction to Configuring Layer 2 VPNs | 147](#)
- [Configuring the Local Site on PE Routers in Layer 2 VPNs | 149](#)
- [Layer 2 VPN Configuration Example | 156](#)
- [Example: Configure MPLS-Based Layer 2 VPNs | 179](#)
- [Transmitting Nonstandard BPDUs in Layer 2 VPNs and VPLS | 208](#)

Introduction to Configuring Layer 2 VPNs

To configure Layer 2 virtual private network (VPN) functionality, you must enable Layer 2 VPN support on the provider edge (PE) router. You must also configure PE routers to distribute routing information to the other PE routers in the VPN and configure the circuits between the PE routers and the customer edge (CE) routers.

Each Layer 2 VPN is configured under a routing instance of type `l2vpn`. An `l2vpn` routing instance can transparently carry Layer 3 traffic across the service provider's network. As with other routing instances, all logical interfaces belonging to a Layer 2 VPN routing instance are listed under that instance.

The configuration of the CE routers is not relevant to the service provider. The CE routers need to provide only appropriate Layer 2 circuits (with appropriate circuit identifiers, such as data-link connection identifier [DLCI], virtual path identifier/virtual channel identifier [VPI/VCI], or virtual LAN [VLAN] ID) to send traffic to the PE router.

To configure Layer 2 VPNs, include the following statements:

NOTE: On the EX9200 switches, replace *encapsulation-type* with the *encapsulation* statement.

```
description text;  
instance-type l2vpn;
```

```

interface interface-name;
route-distinguisher (as-number:id| ip-address:id);
vrf-export [ policy-names ];
vrf-import [ policy-names ];
vrf-target {
    community;
    import community-name;
    export community-name;
}
protocols {
    l2vpn {
        (control-word | no-control-word);
        encapsulation-type type;
        site site-name {
            interface interface-name {
                description text;
                remote-site-id remote-site-id;
            }
            site-identifier identifier;
            site-preference preference-value {
                backup;
                primary;
            }
        }
        traceoptions {
            file filename <files number> <size size> <world-readable | no-world-readable>;
            flag flag <flag-modifier> <disable>;
        }
    }
}

```

You can include these statements at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

For Layer 2 VPNs, only some of the statements in the [edit routing-instances] hierarchy are valid. For the full hierarchy, see [Junos OS Routing Protocols Library](#).

In addition to these statements, you must configure MPLS label-switched paths (LSPs) between the PE routers, IBGP sessions between the PE routers, and an interior gateway protocol (IGP) on the PE and provider (P) routers. You must also configure the statements that are required for all types of VPN configuration.

By default, Layer 2 VPNs are disabled.

Many of the configuration procedures for Layer 2 VPNs are identical to the procedures for Layer 3 VPNs and virtual private LAN service (VPLS).

Configuring the Local Site on PE Routers in Layer 2 VPNs

IN THIS SECTION

- [Configuring a Layer 2 VPN Routing Instance | 149](#)
- [Configuring the Site | 150](#)
- [Configuring the Remote Site ID | 151](#)
- [Configuring the Encapsulation Type | 153](#)
- [Configuring a Site Preference and Layer 2 VPN Multihoming | 154](#)
- [Tracing Layer 2 VPN Traffic and Operations | 155](#)

For each local site, the PE router advertises a set of VPN labels to the other PE routers servicing the Layer 2 VPN. The VPN labels constitute a single block of contiguous labels; however, to allow for reprovisioning, more than one such block can be advertised. Each label block consists of a label base, a range (the size of the block), and a remote site ID that identifies the sequence of remote sites that connect to the local site using this label block (the remote site ID is the first site identifier in the sequence). The encapsulation type is also advertised along with the label block.

The following sections explain how to configure the connections to the local site on the PE router.

NOTE: Not all subtasks are supported on all platforms; check the CLI on your device.

Configuring a Layer 2 VPN Routing Instance

To configure a Layer 2 VPN on your network, configure a Layer 2 VPN routing instance on the PE router by including the `l2vpn` statement:

NOTE: On the EX9200 switches, replace *encapsulation-type* with the *encapsulation* statement.

```
l2vpn {
  (control-word | no-control-word);
  encapsulation-type type;
  traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
  }
  site site-name {
    site-identifier identifier;
    site-preference preference-value {
      backup;
      primary;
    }
    interface interface-name {
      description text;
      remote-site-id remote-site-id;
    }
  }
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols]

NOTE: You cannot configure a routing protocol (OSPF, RIP, IS-IS or BGP) inside a Layer 2 VPN routing instance (instance-type *l2vpn*). The Junos CLI disallows this configuration.

Instructions for how to configure the remaining statements are included in the sections that follow.

Configuring the Site

All the Layer 2 circuits provisioned for a local site are listed as the set of logical interfaces (specified by including the *interface* statement) within the *site* statement.

On each PE router, you must configure each site that has a circuit to the PE router. To do this, include the site statement:

```
site site-name {
  site-identifier identifier;
  site-preference preference-value {
    backup;
    primary;
  }
  interface interface-name {
    description text;
    remote-site-id remote-site-ID;
  }
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols l2vpn]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn]

You must configure the following for each site:


- *site-name*—Name of the site.
- site-identifier *identifier*—Unsigned 16-bit number greater than zero that uniquely identifies the local Layer 2 VPN site. The site identifier corresponds to the remote site ID configured on another site within the same VPN.
- interface *interface-name*—The name of the interface and, optionally, a remote site ID for remote site connections. See ["Configuring the Remote Site ID" on page 151](#).

Configuring the Remote Site ID

The remote site ID allows you to configure a sparse Layer 2 VPN topology. A sparse topology means that each site does not have to connect to all the other sites in the VPN; thus it is unnecessary to allocate circuits for all the remote sites. Remote site IDs are particularly important if you configure a topology more complicated than full-mesh, such as a hub-and-spoke topology.

The remote site ID (configured with the `remote-site-id` statement) corresponds to the site ID (configured with the `site-identifier` statement) configured at a separate site. [Figure 11 on page 152](#) illustrates the relationship between the site identifier and the remote site ID.

Figure 11: Relationship Between the Site Identifier and the Remote Site ID



As illustrated by the figure, the configuration for Router PE1 connected to Router CE1 is as follows:

```
site-identifier 1;
interface so-0/0/0 {
    remote-site-id 2;
}
```

The configuration for Router PE2 connected to Router CE2 is as follows:

```
site-identifier 2;
interface so-0/0/1 {
    remote-site-id 1;
}
```

The remote site ID (2) on Router PE1 corresponds to the site identifier (2) on Router PE2. On Router PE2, the remote site ID (1) corresponds to the site identifier (1) on Router PE1.

To configure the remote site ID, include the `remote-site-id` statement:

```
remote-site-id remote-site-id;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols l2vpn site *site-name* interface *interface-name*]

- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn site *site-name* interface *interface-name*]

If you do not explicitly include the `remote-site-id` statement for the interface configured at the [edit routing-instances *routing-instance-name* protocols l2vpn site *site-name*] hierarchy level, a remote site ID is assigned to that interface.

The remote site ID for an interface is automatically set to 1 higher than the remote site ID for the previous interface. The order of the interfaces is based on their `site-identifier` statements. For example, if the first interface in the list does not have a remote site ID, its ID is set to 1. The second interface in the list has its remote site ID set to 2, and the third has its remote site ID set to 3. The remote site IDs of any interfaces that follow are incremented in the same manner if you do not explicitly configure them.

Configuring the Encapsulation Type

The encapsulation type you configure at each Layer 2 VPN site varies depending on which Layer 2 protocol you choose to configure. If you configure `ethernet-vlan` as the encapsulation type, you need to use the same protocol at each Layer 2 VPN site.

You do not need to use the same protocol at each Layer 2 VPN site if you configure any of the following encapsulation types:

- `atm-aal5`—Asynchronous Transfer Mode (ATM) Adaptation Layer (AAL5)
- `atm-cell`—ATM cell relay
- `atm-cell-port-mode`—ATM cell relay port promiscuous mode
- `atm-cell-vc-mode`—ATM virtual circuit (VC) cell relay nonpromiscuous mode
- `atm-cell-vp-mode`—ATM virtual path (VP) cell relay promiscuous mode
- `cisco-hdlc`—Cisco Systems-compatible High-Level Data Link Control (HDLC)
- `ethernet`—Ethernet
- `ethernet-vlan`—Ethernet virtual LAN (VLAN)
- `frame-relay`—Frame Relay
- `frame-relay-port-mode`—Frame Relay port mode
- `interworking`—Layer 2.5 interworking VPN
- `ppp`—Point-to-Point Protocol (PPP)

If you configure different protocols at your Layer 2 VPN sites, you need to configure a translational cross-connect (TCC) encapsulation type. For more information, see ["Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits" on page 210](#).

To configure the Layer 2 protocol accepted by the PE router, specify the encapsulation type by including the `encapsulation-type` statement:

```
encapsulation-type type;
```

For EX9200 switches, specify the encapsulation type by including the `encapsulation` statement:

```
encapsulation type;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols l2vpn]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn]

Configuring a Site Preference and Layer 2 VPN Multihoming

You can specify the preference value advertised for a particular Layer 2 VPN site. The site preference value is encoded in the BGP local preference attribute. When a PE router receives multiple advertisements with the same CE device identifier, the advertisement with the highest local preference value is preferred.

You can also use the `site-preference` statement to enable multihoming for Layer 2 VPNs. Multihoming allows you to connect a CE device to multiple PE routers. In the event that a connection to the primary PE router fails, traffic can be automatically switched to the backup PE router.

To configure a site preference for a Layer 2 VPN, include the `site-preference` statement:

```
site-preference preference-value {
    backup;
    primary;
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols l2vpn site *site-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn site *site-name*]

You can also specify either the backup option or the primary option for the site-preference statement. The backup option specifies the preference value as 1, the lowest possible value, ensuring that the Layer 2 VPN site is the least likely to be selected. The primary option specifies the preference value as 65,535, the highest possible value, ensuring that the Layer 2 VPN site is the most likely to be selected.

For Layer 2 VPN multihoming configurations, specifying the primary option for a Layer 2 VPN site designates the connection from the PE router to the CE device as the preferred connection if the CE device is also connected to another PE router. Specifying the backup option for a Layer 2 VPN site designates the connection from the PE router to the CE device as the secondary connection if the CE device is also connected to another PE router.

Tracing Layer 2 VPN Traffic and Operations

To trace Layer 2 VPN protocol traffic, specify options for the traceoptions statement in the Layer 2 VPN configuration:

```
traceoptions {
  file filename <files number> <size size> <world-readable | no-world-readable>;
  flag flag <flag-modifier> <disable>;
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols l2vpn]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn]

The following trace flags display the operations associated with Layer 2 VPNs:

- all—All Layer 2 VPN tracing options.
- connections—Layer 2 connections (events and state changes).
- error—Error conditions.
- general—General events.
- nlri—Layer 2 advertisements received or sent by means of the BGP.
- normal—Normal events.
- policy—Policy processing.
- route—Routing information.
- state—State transitions.

- `task`—Routing protocol task processing.
- `timer`—Routing protocol timer processing.
- `topology`—Layer 2 VPN topology changes caused by reconfiguration or advertisements received from other PE routers using BGP.

Disabling Normal TTL Decrementing for VPNs

To diagnose networking problems related to VPNs, it can be useful to disable normal time-to-live (TTL) decrementing. In Junos, you can do this with the `no-propagate-ttl` and `no-decrement-ttl` statements. However, when you are tracing VPN traffic, only the `no-propagate-ttl` statement is effective.

For the `no-propagate-ttl` statement to have an effect on VPN behavior, you need to clear the PE-router-to-PE-router BGP session, or disable and then enable the VPN routing instance.

For more information about the `no-propagate-ttl` and `no-decrement-ttl` statements, see the [MPLS Applications User Guide](#).

Layer 2 VPN Configuration Example

IN THIS SECTION


- [Simple Full-Mesh Layer 2 VPN Overview | 157](#)
- [Enabling an IGP on the PE Routers | 157](#)
- [Configuring MPLS LSP Tunnels Between the PE Routers | 158](#)
- [Configuring IBGP on the PE Routers | 159](#)
- [Configuring Routing Instances for Layer 2 VPNs on the PE Routers | 161](#)
- [Configuring CCC Encapsulation on the Interfaces | 164](#)
- [Configuring VPN Policy on the PE Routers | 165](#)
- [Layer 2 VPN Configuration Summarized by Router | 169](#)

The following sections explain how to configure Layer 2 VPN functionality on the provider edge (PE) routers connected to each site:

Simple Full-Mesh Layer 2 VPN Overview

In the sections that follow, you configure a simple full-mesh Layer 2 VPN spanning three sites: Sunnyvale, Austin, and Portland. Each site connects to a PE router. The customer edge (CE) routers at each site use Frame Relay to carry Layer 2 traffic to the PE routers. Since this example uses a full-mesh topology between all three sites, each site requires two logical interfaces (one for each of the other CE routers), although only one physical link is needed to connect each PE router to each CE router. [Figure 12 on page 157](#) illustrates the topology of this Layer 2 VPN.

Figure 12: Example of a Simple Full-Mesh Layer 2 VPN Topology



Enabling an IGP on the PE Routers

To allow the PE routers to exchange routing information among themselves, you must configure an interior gateway protocol (IGP) or static routes on these routers. You configure the IGP on the primary instance of the routing protocol process (`rp`) (that is, at the `[edit protocols]` hierarchy level), not within the Layer 2 VPN routing instance (that is, not at the `[edit routing-instances]` hierarchy level). Turn on traffic engineering on the IGP.

You configure the IGP in the standard way. This example does not include this portion of the configuration.

Configuring MPLS LSP Tunnels Between the PE Routers

In this configuration example, RSVP is used for MPLS signaling. Therefore, in addition to configuring RSVP, you must create an MPLS label-switched path (LSP) to tunnel the VPN traffic.

On Router A, enable RSVP and configure one end of the MPLS LSP tunnel to Router B. When configuring the MPLS LSP, include all interfaces using the `interface all` statement.

```
[edit]
protocols {
  rsvp {
    interface all;
  }
  mpls {
    interface all;
    label-switched-path RouterA-to-RouterB {
      to 192.168.37.5;
      primary Path-to-RouterB;
    }
    label-switched-path RouterA-to-RouterC {
      to 192.168.37.10;
      primary Path-to-RouterC;
    }
  }
}
```

On Router B, enable RSVP and configure the other end of the MPLS LSP tunnel. Again, configure the interfaces by using the `interface all` statement.

```
[edit]
protocols {
  rsvp {
    interface all;
  }
  mpls {
    interface all;
    label-switched-path RouterB-to-RouterA {
      to 192.168.37.1;
      primary Path-to-RouterA;
    }
    label-switched-path RouterB-to-RouterC {
      to 192.168.37.10;
    }
  }
}
```

```

        primary Path-to-RouterC;
    }
}
}

```

On Router C, enable RSVP and configure the other end of the MPLS LSP tunnel. Again, configure all interfaces using the `interface all` statement.

```

[edit]
protocols {
  rsvp {
    interface all;
  }
  mpls {
    interface all;
    label-switched-path RouterC-to-RouterA {
      to 192.168.37.1;
      primary Path-to-RouterA;
    }
    label-switched-path RouterC-to-RouterB {
      to 192.168.37.5;
      primary Path-to-RouterB;
    }
  }
}
}

```

Configuring IBGP on the PE Routers

On the PE routers, configure an IBGP session with the following parameters:

- **Layer 2 VPN**—To indicate that the IBGP session is for a Layer 2 VPN, include the `family l2vpn` statement.
- **Local address**—The IP address in the `local-address` statement is the same as the address configured in the `to` statement at the `[edit protocols mpls label-switched-path lsp-path-name]` hierarchy level on the remote PE router. The IBGP session for Layer 2 VPNs runs through this address.
- **Neighbor address**—Include the `neighbor` statement, specifying the IP address of the neighboring PE router.

On Router A, configure IBGP:

```
[edit]
protocols {
  bgp {
    import match-all;
    export match-all;
    group pe-pe {
      type internal;
      neighbor 192.168.37.5 {
        local-address 192.168.37.1;
        family l2vpn {
          signaling;
        }
      }
      neighbor 192.168.37.10 {
        local-address 192.168.37.1;
        family l2vpn {
          signaling;
        }
      }
    }
  }
}
```

On Router B, configure IBGP:

```
[edit]
protocols {
  bgp {
    local-address 192.168.37.5;
    import match-all;
    export match-all;
    group pe-pe {
      type internal;
      neighbor 192.168.37.1 {
        local-address 192.168.37.5;
        family l2vpn {
          signaling;
        }
      }
    }
  }
}
```

```

        neighbor 192.168.37.10 {
            local-address 192.168.37.5;
            family l2vpn {
                signaling;
            }
        }
    }
}

```

On Router C, configure IBGP:

```

[edit]
protocols {
    bgp {
        local-address 192.168.37.10;
        import match-all;
        export match-all;
        group pe-pe {
            type internal;
            neighbor 192.168.37.1 {
                local-address 192.168.37.10;
                family l2vpn {
                    signaling;
                }
            }
            neighbor 192.168.37.5 {
                local-address 192.168.37.10;
                family l2vpn {
                    signaling;
                }
            }
        }
    }
}

```

Configuring Routing Instances for Layer 2 VPNs on the PE Routers

The three PE routers service the Layer 2 VPN, so you need to configure a routing instance on each router. For the VPN, you must define the following in each routing instance:

- Route distinguisher, which must be unique for each routing instance on the PE router. It is used to distinguish the addresses in one VPN from those in another VPN.
- Instance type of `l2vpn`, which configures the router to run a Layer 2 VPN.
- Interfaces connected to the CE routers.
- Virtual routing and forwarding (*VRF*) import and export policies, which must be the same on each PE router that services the same VPN and are used to control the network topology. Unless the import policy contains only a `then reject` statement, it must include a reference to a community. Otherwise, when you attempt to commit the configuration, the commit operation fails.

On Router A, configure the following routing instance for the Layer 2 VPN:

```
[edit]
routing-instances {
  VPN-Sunnyvale-Portland-Austin {
    instance-type l2vpn;
    interface so-6/0/0.0;
    interface so-6/0/0.1;
    route-distinguisher 100:1;
    vrf-import vpn-SPA-import;
    vrf-export vpn-SPA-export;
    protocols {
      l2vpn {
        encapsulation-type frame-relay;
        site Sunnyvale {
          site-identifier 1;
          interface so-6/0/0.0 {
            remote-site-id 2;
          }
          interface so-6/0/0.1 {
            remote-site-id 3;
          }
        }
      }
    }
  }
}
```

On Router B, configure the following routing instance for the Layer 2 VPN:

```
[edit]
routing-instances {
  VPN-Sunnyvale-Portland-Austin {
    instance-type l2vpn;
    interface so-6/0/0.2;
    interface so-6/0/0.3;
    route-distinguisher 100:1;
    vrf-import vpn-SPA-import;
    vrf-export vpn-SPA-export;
    protocols {
      l2vpn {
        encapsulation-type frame-relay;
        site Austin {
          site-identifier 2;
          interface so-6/0/0.2 {
            remote-site-id 1;
          }
          interface so-6/0/0.3 {
            remote-site-id 3;
          }
        }
      }
    }
  }
}
```

On Router C, configure the following routing instance for the Layer 2 VPN:

```
[edit]
routing-instances {
  VPN-Sunnyvale-Portland-Austin {
    instance-type l2vpn;
    interface so-6/0/0.4;
    interface so-6/0/0.5;
    route-distinguisher 100:1;
    vrf-import vpn-SPA-import;
    vrf-export vpn-SPA-export;
    protocols {
      l2vpn {
```



```

    encapsulation frame-relay-ccc;
    unit 2 {
        encapsulation frame-relay-ccc;
    }
}
interfaces so-6/0/0 {
    encapsulation frame-relay-ccc;
    unit 3 {
        encapsulation frame-relay-ccc;
    }
}

```

Configure the following CCC encapsulation types for the interfaces on Router C:

```

[edit]
interface so-6/0/0 {
    encapsulation frame-relay-ccc;
    unit 4 {
        encapsulation frame-relay-ccc;
    }
}
interface so-6/0/0 {
    encapsulation frame-relay-ccc;
    unit 5 {
        encapsulation frame-relay-ccc;
    }
}

```

Configuring VPN Policy on the PE Routers

You must configure VPN import and export policies on each of the PE routers so that they install the appropriate routes in their VRF tables, which the routers use to forward packets within the VPN.

NOTE: Use the `community add community-name` statement at the `[edit policy-options policy-statement policy-statement-name term term-name then]` hierarchy level to facilitate Layer 2 VPN VRF export policies.

On Router A, configure the following VPN import and export policies:

```
[edit]
policy-options {
  policy-statement match-all {
    term acceptable {
      then accept;
    }
  }
  policy-statement vpn-SPA-export {
    term a {
      then {
        community add SPA-com;
        accept;
      }
    }
    term b {
      then reject;
    }
  }
  policy-statement vpn-SPA-import {
    term a {
      from {
        protocol bgp;
        community SPA-com;
      }
      then accept;
    }
    term b {
      then reject;
    }
  }
  community SPA-com members target:69:100;
}
```

On Router B, configure the following VPN import and export policies:

```
[edit]
policy-options {
  policy-statement match-all {
    term acceptable {
```

```

        then accept;
    }
}
policy-statement vpn-SPA-import {
    term a {
        from {
            protocol bgp;
            community SPA-com;
        }
        then accept;
    }
    term b {
        then reject;
    }
}
policy-statement vpn-SPA-export {
    term a {
        then {
            community add SPA-com;
            accept;
        }
    }
    term b {
        then reject;
    }
}
community SPA-com members target:69:100;
}

```

On Router C, configure the following VPN import and export policies:

```

[edit]
policy-options {
    policy-statement match-all {
        term acceptable {
            then accept;
        }
    }
}
policy-statement vpn-SPA-import {
    term a {
        from {
            protocol bgp;

```

```

        community SPA-com;
    }
    then accept;
}
term b {
    then reject;
}
}
policy-statement vpn-SPA-export {
    term a {
        then {
            community add SPA-com;
            accept;
        }
    }
    term b {
        then reject;
    }
}
community SPA-com members target:69:100;
}

```

To apply the VPN policies on the routers, include the `vrf-export` and `vrf-import` statements when you configure the routing instance. The VRF import and export policies handle the route distribution across the IBGP session running between the PE routers.

To apply the VPN policies on Router A, include the following statements:

```

[edit]
routing-instances {
    VPN-Sunnyvale-Portland-Austin {
        vrf-import vpn-SPA-import;
        vrf-export vpn-SPA-export;
    }
}

```

To apply the VPN policies on Router B, include the following statements:

```

[edit]
routing-instances {
    VPN-Sunnyvale-Portland-Austin {
        vrf-import vpn-SPA-import;
    }
}

```

```

        vrf-export vpn-SPA-export;
    }
}

```

To apply the VPN policies on Router C, include the following statements:

```

[edit]
routing-instances {
    VPN-Sunnyvale-Portland-Austin {
        vrf-import vpn-SPA-import;
        vrf-export vpn-SPA-export;
    }
}

```

Layer 2 VPN Configuration Summarized by Router

For a summary of the configuration on each router in the examples in this chapter, see the following sections:

Summary for Router A (PE Router for Sunnyvale)

Routing Instance for Layer 2 VPN

```

[edit]
routing-instances {
    VPN-Sunnyvale-Portland-Austin {
        instance-type l2vpn;
        interface so-6/0/0.0;
        interface so-6/0/0.1;
        route-distinguisher 100:1;
        vrf-import vpn-SPA-import;
        vrf-export vpn-SPA-export;
        protocols {
            l2vpn {
                encapsulation-type frame-relay;
                site Sunnyvale {
                    site-identifier 1;
                    interface so-6/0/0.0 {
                        remote-site-id 2;
                    }
                }
            }
        }
    }
}

```

```

        interface so-6/0/0.1 {
            remote-site-id 3;
        }
    }
}
}
}
}
}
}
}

```

Configure CCC Encapsulation Types for Interfaces

```

interfaces {
    interface so-6/0/0 {
        encapsulation frame-relay-ccc;
        unit 0 {
            encapsulation frame-relay-ccc;
        }
    }
    interface so-6/0/0 {
        encapsulation frame-relay-ccc;
        unit 1 {
            encapsulation frame-relay-ccc;
        }
    }
}

```

Primary Protocol Instance

```

protocols {
}

```

Enable RSVP

```

rsvp {
    interface all;
}

```

Configure MPLS LSPs

```
mpls {
  label-switched-path RouterA-to-RouterB {
    to 192.168.37.5;
    primary Path-to-RouterB {
      cspf;
    }
  }
  label-switched-path RouterA-to-RouterC {
    to 192.168.37.10;
    primary Path-to-RouterC {
      cspf;
    }
  }
  interface all;
}
```

Configure IBGP

```
bgp {
  import match-all;
  export match-all;
  group pe-pe {
    type internal;
    neighbor 192.168.37.5 {
      local-address 192.168.37.1;
      family l2vpn {
        signaling;
      }
    }
    neighbor 192.168.37.10 {
      local-address 192.168.37.1;
      family l2vpn {
        signaling;
      }
    }
  }
}
```

Configure VPN Policy

```

policy-options {
  policy-statement match-all {
    term acceptable {
      then accept;
    }
  }
  policy-statement vpn-SPA-export {
    term a {
      then {
        community add SPA-com;
        accept;
      }
    }
    term b {
      then reject;
    }
  }
  policy-statement vpn-SPA-import {
    term a {
      from {
        protocol bgp;
        community SPA-com;
      }
      then accept;
    }
    term b {
      then reject;
    }
  }
  community SPA-com members target:69:100;
}

```

Summary for Router B (PE Router for Austin)

Routing Instance for VPN

```

[edit]
routing-instances {
  VPN-Sunnyvale-Portland-Austin {

```

```

        instance-type l2vpn;
        interface so-6/0/0.2;
        interface so-6/0/0.3;
        route-distinguisher 100:1;
        vrf-import vpn-SPA-import;
        vrf-export vpn-SPA-export;
    }
}

```

Configure Layer 2 VPN

```

protocols {
    l2vpn {
        encapsulation-type frame-relay;
        site Austin {
            site-identifier 2;
            interface so-6/0/0.2 {
                remote-site-id 1;
            }
            interface so-6/0/0.3 {
                remote-site-id 3;
            }
        }
    }
}

```

Configure CCC Encapsulation Types for Interfaces

```

[edit]
interfaces {
    interface so-6/0/0 {
        encapsulation frame-relay-ccc;
        unit 2 {
            encapsulation frame-relay-ccc;
        }
    }
    interface so-6/0/0 {
        encapsulation frame-relay-ccc;
        unit 3 {
            encapsulation frame-relay-ccc;
        }
    }
}

```



```
    }
}
```

Primary Protocol Instance

```
protocols {
}
```

Enable RSVP

```
rsvp {
    interface all;
}
```

Configure MPLS LSPs

```
mpls {
    label-switched-path RouterB-to-RouterA {
        to 192.168.37.1;
        primary Path-to-RouterA {
            cspf;
        }
    }
    label-switched-path RouterB-to-RouterC {
        to 192.168.37.10;
        primary Path-to-RouterC {
            cspf;
        }
    }
    interface all;
}
```

Configure IBGP

```
bgp {
    local-address 192.168.37.5;
    import match-all;
    export match-all;
    group pe-pe {
        type internal;
    }
}
```

```

    neighbor 192.168.37.1 {
        local-address 192.168.37.5;
        family l2vpn {
            signaling;
        }
    }
    neighbor 192.168.37.10 {
        local-address 192.168.37.5;
        family l2vpn {
            signaling;
        }
    }
}

```

Configure VPN Policy

```

policy-options {
    policy-statement match-all {
        term acceptable {
            then accept;
        }
    }
    policy-statement vpn-SPA-import {
        term a {
            from {
                protocol bgp;
                community SPA-com;
            }
            then accept;
        }
        term b {
            then reject;
        }
    }
    policy-statement vpn-SPA-export {
        term a {
            then {
                community add SPA-com;
                accept;
            }
        }
    }
}

```

```

        term b {
            then reject;
        }
    }
    community SPA-com members target:69:100;
}

```

Summary for Router C (PE Router for Portland)

Routing Instance for VPN

```

[edit]
routing-instances {
    VPN-Sunnyvale-Portland-Austin {
        instance-type l2vpn;
        interface so-6/0/0.3;
        interface so-6/0/0.4;
        route-distinguisher 100:1;
        vrf-import vpn-SPA-import;
        vrf-export vpn-SPA-export;
    }
}

```

Configure Layer 2 VPN

```

protocols {
    l2vpn {
        encapsulation-type frame-relay;
        site Portland {
            site-identifier 3;
            interface so-6/0/0.4 {
                remote-site-id 1;
            }
            interface so-6/0/0.5 {
                remote-site-id 2;
            }
        }
    }
}

```

Configure CCC Encapsulation Types for Interfaces

```
[edit]
interfaces {
  interface so-6/0/0 {
    encapsulation frame-relay-ccc;
    unit 4 {
      encapsulation frame-relay-ccc;
    }
  }
  interface so-6/0/0 {
    encapsulation frame-relay-ccc;
    unit 5 {
      encapsulation frame-relay-ccc;
    }
  }
}
```

Primary Protocol Instance

```
protocols {
}
```

Enable RSVP

```
rsvp {
  interface all;
}
```

Configure MPLS LSPs

```
mpls {
  label-switched-path RouterC-to-RouterA {
    to 192.168.37.1;
    primary Path-to-RouterA {
      cspf;
    }
  }
  label-switched-path RouterC-to-RouterB {
    to 192.168.37.5;
```

```

        primary Path-to-RouterB {
            cspf;
        }
    }
    interface all;
}

```

Configure IBGP

```

bgp {
    local-address 192.168.37.10;
    import match-all;
    export match-all;
    group pe-pe {
        type internal;
        neighbor 192.168.37.1 {
            local-address 192.168.37.10;
            family l2vpn {
                signaling;
            }
        }
        neighbor 192.168.37.5 {
            local-address 192.168.37.10;
            family l2vpn {
                signaling;
            }
        }
    }
}

```

Configure VPN Policy

```

policy-options {
    policy-statement match-all {
        term acceptable {
            then accept;
        }
    }
    policy-statement vpn-SPA-import {
        term a {
            from {

```

```

        protocol bgp;
        community SPA-com;
    }
    then accept;
}
term b {
    then reject;
}
}
policy-statement vpn-SPA-export {
    term a {
        then {
            community add SPA-com;
            accept;
        }
    }
    term b {
        then reject;
    }
}
community SPA-com members target:69:100;
}

```

Example: Configure MPLS-Based Layer 2 VPNs

IN THIS SECTION

- [Requirements | 180](#)
- [Overview and Topology | 181](#)
- [Quick Configurations | 182](#)
- [Configure the Local PE \(PE1\) Device for a MPLS-Based Layer 2 VPN | 185](#)
- [Configure the Remote PE \(PE2\) Device for a MPLS-Based Layer 2 VPN | 193](#)
- [Verification | 199](#)

This example shows how to configure and validate an MPLS-based Layer 2 VPN on routers or switches running Junos OS.

NOTE: Our content testing team has validated and updated this example.

You can deploy an MPLS-based Layer 2 virtual private network using routers and switches running Junos OS to interconnect customer sites with Layer 2 connectivity. Layer 2 VPNs give customers complete control over their choice of transport and routing protocols.

MPLS-based VPNs require baseline MPLS functionality in the provider network. Once basic MPLS is operational, you are able to configure VPNs that use Label-switched paths (LSPs) for transport over the provider's core.

The addition of VPN services does not affect the basic MPLS switching operations in the provider network. In fact, the provider (P) devices require only a baseline MPLS configuration because they are not VPN aware. VPN state is maintained only on the PE devices. This is a key reason why MPLS-based VPNs are so scalable.

Requirements

This example uses the following hardware and software components:

- Junos OS Release 15.1 or later
 - Revalidated on Junos OS Release 20.1R1
- Two Provider edge (PE) devices
- One provider (P) device
- Two customer edge (CE) devices

The example focuses on how to add Layer 2 VPN to a pre-existing MPLS baseline. A basic MPLS configuration is provided in case your network does not already have MPLS deployed.

To support MPLS-based VPNs the underlying MPLS baseline must provide the following functionality:

- Core-facing and loopback interfaces operational with MPLS family support
- An interior gateway protocol such as OSPF or IS-IS to provide reachability between the loopback addresses of the provider (P and PE) devices
- An MPLS signalling protocol such as LDP or RSVP to signal LSPs
- LSPs established between PE device loopback addresses

LSPs are needed between each pair of PE devices that participate in a given VPN. It's a good idea to build LSPs between all PE devices to accommodate future VPN growth. You configure LSPs at the [edit protocols mpls] hierarchy level. Unlike an MPLS configuration for circuit cross-connect (CCC), you do not need to manually associate the LSP with the PE device's customer-facing (edge) interface. Instead, Layer 2 VPNs use BGP signaling to convey Layer 2 site reachability. This BGP signaling automates the mapping of remote Layer 2 VPN sites to LSP forwarding next hops. This means that with a Layer 2 VPN explicit mapping of an LSP to a PE device's edge-facing interface is not required.

For details on CCC, refer to [Configuring an MPLS-Based VLAN CCC Using a Layer 2 Circuit](#).

Overview and Topology

A Layer 2 VPN provides complete separation between the provider and customer networks. The benefits of a Layer 2 VPN include support for nonstandard transport protocols and the isolation of link addressing and routing protocol operation between the customer and provider networks.

Definition of a VPN involves changes to the local and remote PE devices only. No additional configuration is needed on the provider devices (aside from baseline MPLS support), because these devices only provide basic MPLS switching functions. The CE devices do not use MPLS. They require only a basic interface, and if desired, protocol configuration, to operate over the Layer 2 VPN. For a Layer 2 VPN you configure the CE devices as if they were attached to a shared link.


Once an MPLS baseline is in place, you must configure the following functionality on the PE devices to establish an MPLS-based Layer 2 VPN:

- A BGP group with family l2vpn signaling
- A routing instance with instance type l2vpn
- The customer-facing interfaces on the PE devices must be configured as follows:
 - Specify ethernet-ccc or vlan-ccc physical layer encapsulation depending on whether VLAN tagging is in use.
 - Configure a matching encapsulation type in the routing instance configuration.
 - Configure the logical interface (unit) used for the Layer 2 VPN with family ccc.

[Figure 13 on page 182](#) provides the topology for this MPLS-based Layer 2 VPN example. The figure details the interface names, IP addressing, and protocols used in the provider network. It also highlights the end-to-end nature of the CE device addressing and protocol stack operation. Unlike a Layer 3 VPN, CE device operation is opaque to the provider network in a Layer 2 VPN. There is no peering

relationship between the CE devices and the provider network. As a result you expect the CE devices to form an OSPF adjacency *across, not to*, the provider network.

Figure 13: An MPLS-Based Layer 2 VPN



Quick Configurations

IN THIS SECTION

- [CLI Quick Configuration | 182](#)

Use the configurations in this section to quickly get your MPLS-based Layer 2 VPN up and running. The configurations include a functional MPLS baseline to support your Layer 2 VPN. This example focuses on the VPN aspects of the configuration. Refer to the following links for additional information on the baseline MPLS functionality used in this example:

- [Configuring MPLS on Provider Edge EX8200 and EX4500 Switches Using Circuit Cross-Connect](#)
- [Configuring MPLS on EX8200 and EX4500 Provider Switches](#)

CLI Quick Configuration

NOTE: The device configurations omit the management interface, static routes, system logging, system services, and user login information. These parts of the configuration vary by location and are not directly related to MPLS or VPN functionality.

Edit the following commands as needed for the specifics of your environment and paste them into the local CE (CE1) device terminal window:

The complete configuration for the CE1 device.

```
set system host-name ce1
set interfaces ge-0/0/0 description "Link from CE1 to PE1"
set interfaces ge-0/0/0 unit 0 family inet address 172.16.1.1/30
set interfaces lo0 unit 0 family inet address 172.16.255.1/32
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface ge-0/0/0.0
```

Edit the following commands as needed for the specifics of your environment and paste them into the local PE (PE1) device terminal window:

The complete configuration for PE1 device.

```
set system host-name pe1
set interfaces ge-0/0/0 description "Link from PE1 to CE1"
set interfaces ge-0/0/0 encapsulation ethernet-ccc
set interfaces ge-0/0/0 unit 0 family ccc
set interfaces ge-0/0/1 description "Link from PE1 to P-router"
set interfaces ge-0/0/1 mtu 4000
set interfaces ge-0/0/1 unit 0 family inet address 10.1.23.1/24
set interfaces ge-0/0/1 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.168.0.1/32
set routing-instances l2vpn1 protocols l2vpn interface ge-0/0/0.0 description "EDGE LINK BETWEEN
PE1 AND CE1"
set routing-instances l2vpn1 protocols l2vpn site CE-1 interface ge-0/0/0.0 remote-site-id 2
set routing-instances l2vpn1 protocols l2vpn site CE-1 site-identifier 1
set routing-instances l2vpn1 protocols l2vpn encapsulation-type ethernet
set routing-instances l2vpn1 instance-type l2vpn
set routing-instances l2vpn1 interface ge-0/0/0.0
set routing-instances l2vpn1 route-distinguisher 192.168.0.1:12
set routing-instances l2vpn1 vrf-target target:65412:12
set routing-options autonomous-system 65412
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 192.168.0.1
set protocols bgp group ibgp family l2vpn signaling
set protocols bgp group ibgp neighbor 192.168.0.3
set protocols mpls label-switched-path lsp_to_pe2 to 192.168.0.3
set protocols mpls interface ge-0/0/1.0
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface ge-0/0/1.0
```

```
set protocols rsvp interface lo0.0
set protocols rsvp interface ge-0/0/1.0
```

The complete configuration for the P device.

```
set system host-name p
set interfaces ge-0/0/0 description "Link from P-router to PE1"
set interfaces ge-0/0/0 mtu 4000
set interfaces ge-0/0/0 unit 0 family inet address 10.1.23.2/24
set interfaces ge-0/0/0 unit 0 family mpls
set interfaces ge-0/0/1 description "Link from P-router to PE2"
set interfaces ge-0/0/1 mtu 4000
set interfaces ge-0/0/1 unit 0 family inet address 10.1.34.1/24
set interfaces ge-0/0/1 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.168.0.2/32
set protocols mpls interface ge-0/0/0.0
set protocols mpls interface ge-0/0/1.0
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface ge-0/0/0.0
set protocols ospf area 0.0.0.0 interface ge-0/0/1.0
set protocols rsvp interface lo0.0
set protocols rsvp interface ge-0/0/0.0
set protocols rsvp interface ge-0/0/1.0
```

The complete configuration for the PE2 device.

```
set system host-name pe2
set interfaces ge-0/0/0 description "Link from PE2 to CE2"
set interfaces ge-0/0/0 encapsulation ethernet-ccc
set interfaces ge-0/0/0 unit 0 family ccc
set interfaces ge-0/0/1 description "Link from PE2 to P-router"
set interfaces ge-0/0/1 mtu 4000
set interfaces ge-0/0/1 unit 0 family inet address 10.1.34.2/24
set interfaces ge-0/0/1 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.168.0.3/32
set routing-instances l2vpn1 protocols l2vpn interface ge-0/0/0.0 description "EDGE LINK BETWEEN
PE2 AND CE2"
set routing-instances l2vpn1 protocols l2vpn site CE-2 interface ge-0/0/0.0 remote-site-id 1
set routing-instances l2vpn1 protocols l2vpn site CE-2 site-identifier 2
set routing-instances l2vpn1 protocols l2vpn encapsulation-type ethernet
```

```

set routing-instances l2vpn1 instance-type l2vpn
set routing-instances l2vpn1 interface ge-0/0/0.0
set routing-instances l2vpn1 route-distinguisher 192.168.0.3:12
set routing-instances l2vpn1 vrf-target target:65412:12
set routing-options autonomous-system 65412
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 192.168.0.3
set protocols bgp group ibgp family l2vpn signaling
set protocols bgp group ibgp neighbor 192.168.0.1
set protocols mpls label-switched-path lsp_to_pe1 to 192.168.0.1
set protocols mpls interface ge-0/0/1.0
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface ge-0/0/1.0
set protocols rsvp interface lo0.0
set protocols rsvp interface ge-0/0/1.0

```

The complete configuration for the CE2 device.

```

set system host-name ce2
set interfaces ge-0/0/0 description "Link from CE2 to PE2"
set interfaces ge-0/0/0 unit 0 family inet address 172.16.1.2/30
set interfaces lo0 unit 0 family inet address 172.16.255.2/32
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface ge-0/0/0.0

```

Be sure to commit the configuration changes on all devices when satisfied with your work.

Congratulations on your new MPLS-based Layer 2 VPN! Refer to the ["Verification" on page 199](#) section for the steps needed to confirm your VPN is working as expected.

Configure the Local PE (PE1) Device for a MPLS-Based Layer 2 VPN

IN THIS SECTION

- [Procedure | 187](#)
- [Results | 190](#)

This section covers the steps needed to configure the PE1 device for this example. Refer to the ["Example: Configure MPLS-Based Layer 2 VPNs" on page 179](#) section for the CE device and P device configurations used in this example.

Configure the MPLS Baseline (if Needed)

Before you configure the Layer 2 VPN make sure the PE device has a working MPLS baseline. If you already having a an MPLS baseline you can skip to the step-by-step procedure to add the Layer 2 VPN to the local PE device.

- Configure the hostname.

```
[edit]
user@pe1# set system host-name pe1
```

- Configure the interfaces.

```
[edit]
user@pe1# set interfaces ge-0/0/1 description "Link from PE1 to P-router"
[edit]
user@pe1# set interfaces ge-0/0/1 mtu 4000
[edit]
user@pe1# set interfaces ge-0/0/1 unit 0 family inet address 10.1.23.1/24
[edit]
user@pe1# set interfaces ge-0/0/1 unit 0 family mpls
[edit]
user@pe1# set interfaces lo0 unit 0 family inet address 192.168.0.1/32
```



CAUTION: Layer 2 VPNs don't support fragmentation in the provider network. It is critical that the provider network supports the largest frame that the CE devices can generate *after* the MPLS and virtual routing and forwarding (VRF) labels are added by the PE devices. This example leaves the CE devices at the default 1500-byte maximum transmission unit (MTU) while configuring the provider core to support a 4000 byte MTU. This configuration avoids discards by ensuring the CE devices cannot exceed the MTU in the provider's network.

- Configure the protocols.

NOTE: Traffic engineering is supported for RSVP-signaled LSPs but is not required for basic MPLS switching or VPN deployment. The provided MPLS baseline uses RSVP to signal LSPs, and enables traffic engineering for OSPF. However, no path constraints are configured so you expect the LSPs to be routed over the interior gateway protocol's shortest path.

```
[edit]
user@pe1# set protocols ospf area 0.0.0.0 interface lo0.0
[edit]
user@pe1# set protocols ospf area 0.0.0.0 interface ge-0/0/1.0
[edit]
user@pe1# set protocols ospf traffic-engineering
[edit]
user@pe1# set protocols mpls interface ge-0/0/1.0
[edit]
user@pe1# set protocols rsvp interface lo0.0
[edit]
user@pe1# set protocols rsvp interface ge-0/0/1.0
```

- Define the LSP to the remote PE device's loopback address.

```
[edit]
user@pe1# set protocols mpls label-switched-path lsp_to_pe2 to 192.168.0.3
```

Procedure

Step-by-Step Procedure

Follow these steps to configure the PE1 device for a Layer 2 VPN.

1. Configure the edge-facing interface. Specify a physical encapsulation type of ethernet-ccc with family ccc on unit 0. This is the only valid unit number for an untagged Ethernet interface. If you are using VLAN tagging specify vlan-ccc encapsulation and add the CCC family to the desired unit(s).

TIP: You can configure both an MPLS-based Layer 2 VPN and an MPLS-based Layer 3 VPN on the same PE device. However, you cannot configure the same customer edge-facing interface to support both a Layer 2 VPN and a Layer 3 VPN.

```
[edit]user@pe1# set interfaces ge-0/0/0 encapsulation ethernet-ccc
[edit]
user@pe1# set interfaces ge-0/0/0 unit 0 family ccc
[edit]
user@pe1# set interfaces ge-0/0/0 description "Link from PE1 to CE1"
```

NOTE: A Layer 2 VPN requires that the PE device's edge-facing interfaces be configured with CCC encapsulation at the physical device level with the CCC family configured at the unit level. The provider devices are configured in the same way whether you are deploying CCC, an MPLS-based Layer 2 VPN, or an MPLS-based Layer 3 VPN. This is because they have no edge-facing interfaces or VPN awareness.

2. Configure a BGP group for the peering between the local and remote PE devices. Use the PE device's loopback address as the local address and enable family l2vpn signaling.

```
[edit protocols bgp]
user@pe1# set group ibgp local-address 192.168.0.1 family l2vpn signaling
```

3. Configure the BGP group type as internal.

```
[edit protocols bgp]
user@pe1# set group ibgp type internal
```

4. Configure the remote PE device's loopback address as a BGP neighbor.

```
[edit protocols bgp]
user@pe1# set group ibgp neighbor 192.168.0.3
```

5. Configure the BGP autonomous system number.

```
[edit routing-options]
user@pe1# set autonomous-system 65412
```

6. Configure the routing instance. Start by specifying the instance name *l2vpn1*, with an instance-type of *l2vpn*.

```
[edit routing-instances]
user@pe1# set l2vpn1 instance-type l2vpn
```

7. Configure the PE device's customer-facing interface to belong to the routing instance.

```
[edit routing-instances]
user@pe1# set l2vpn1 interface ge-0/0/0
```

8. Configure the routing instance's route distinguisher. This setting is used to distinguish the routes sent from a particular VRF on a particular PE device. It should be unique for each routing instance on each PE device.

```
[edit routing-instances]
user@pe1# set l2vpn1 route-distinguisher 192.168.0.1:12
```

9. Configure the instance's virtual routing and forwarding (VRF) table route target. The *vrf-target* statement adds the specified community tag to all advertised routes while automatically matching the same value for route import. Configuring matching route targets on the PE devices that share a given VPN is required for proper route exchange.

```
[edit routing-instances]
user@pe1# set l2vpn1 vrf-target target:65412:12
```

NOTE: You can create more complex policies by explicitly configuring VRF import and export policies using the *import* and *export* options. See *vrf-import* and *vrf-export* for details.

10. Configure the l2vpn protocol in the instance and specify the encapsulation that is used on the edge-facing link. If the edge interface is VLAN tagged, be sure to specify ethernet-vlan.

```
[edit routing-instances]
user@pe1# set l2vpn1 protocols l2vpn encapsulation-type ethernet
```

11. Add the edge-facing interface under the instance's l2vpn stanza along with a description.

```
[edit routing-instances]
user@pe1# set l2vpn1 protocols l2vpn interface ge-0/0/0.0 description "L2vpn Link Between
PE1 and CE1"
```

12. Configure the Layer 2 VPN site information and associate the edge-facing interface with the local customer site.

```
[edit routing-instances]
user@pe1# set l2vpn1 protocols l2vpn site CE-1 site-identifier 1 interface ge-0/0/0.0
remote-site-id 2
```

NOTE: In this example, the site ID for the PE1 device is *1* and the site ID for the PE2 device is *2*. For the local PE device (PE1), the remote site is correctly configured with a `remote-site-id` value of *2*.

13. Commit your changes at the PE1 device and return to CLI operational mode.

```
[edit]
user@pe1# commit and-quit
```

Results

Display the results of the configuration on the PE1 device. The output reflects only the functional configuration added in this example.

```
user@pe1> show configuration
interfaces {
  ge-0/0/0 {
```

```

        description "Link from PE1 to CE1";
        encapsulation ethernet-ccc;
        unit 0 {
            family ccc;
        }
    }
    ge-0/0/1 {
        description "Link from PE1 to P-router";
        mtu 4000;
        unit 0 {
            family inet {
                address 10.1.23.1/24;
            }
            family mpls;
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 192.168.0.1/32;
            }
        }
    }
}

routing-instances {
    l2vpn1 {
        protocols {
            l2vpn {
                interface ge-0/0/0.0 {
                    description "L2vpn Link Between PE1 and CE1" ;
                }
                site CE-1 {
                    interface ge-0/0/0.0 {
                        remote-site-id 2;
                    }
                    site-identifier 1;
                }
                encapsulation-type ethernet;
            }
        }
        instance-type l2vpn;
        interface ge-0/0/0.0;
        route-distinguisher 192.168.0.1:12;
    }
}

```

```

        vrf-target target:65412:12;
    }
}
routing-options {
    autonomous-system 65412;
}
protocols {
    bgp {
        group ibgp {
            type internal;
            local-address 192.168.0.1;
            family l2vpn {
                signaling;
            }
            neighbor 192.168.0.3;
        }
    }
    mpls {
        label-switched-path lsp_to_pe2 {
            to 192.168.0.3;
        }
        interface ge-0/0/1.0;
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface lo0.0;
            interface ge-0/0/1.0;
        }
    }
    rsvp {
        interface lo0.0;
        interface ge-0/0/1.0;
    }
}

```

Configure the Remote PE (PE2) Device for a MPLS-Based Layer 2 VPN

IN THIS SECTION

- Procedure | 194

This section covers the steps needed to configure the PE2 device for this example. Refer to the ["Example: Configure MPLS-Based Layer 2 VPNs" on page 179](#) section for the CE device and P device configurations used in this example.

Configure the MPLS Baseline (if Needed)

Before you configure the Layer 2 VPN make sure the PE device has a working MPLS baseline. If you already having an MPLS baseline you can skip to the step-by-step procedure to add the Layer 2 VPN to the local PE device.

- Configure the hostname.

```
[edit]
user@pe2# set system host-name pe2
```

- Configure the interfaces.

```
[edit]
user@pe2# set interfaces ge-0/0/1 description "Link from PE2 to P-router"
[edit]
user@pe2# set interfaces ge-0/0/1 mtu 4000
[edit]
user@pe2# set interfaces ge-0/0/1 unit 0 family inet address 10.1.34.1/24
[edit]
user@pe2# set interfaces ge-0/0/1 unit 0 family mpls
[edit]
user@pe2# set interfaces lo0 unit 0 family inet address 192.168.0.3/32
```



CAUTION: Layer 2 VPNs don't support fragmentation in the provider network. It is critical that the provider network supports the largest frame that the CE devices can

generate *after* the MPLS and virtual routing and forwarding (VRF) labels are added by the PE devices. This example leaves the CE devices at the default 1500-byte maximum transmission unit (MTU) while configuring the provider core to support a 4000 byte MTU. This configuration avoids discards by ensuring the CE devices cannot exceed the MTU in the provider's network.

- Configure the protocols.

NOTE: Traffic engineering is supported for RSVP-signaled LSPs but is not required for basic MPLS switching or VPN deployment. The provided MPLS baseline uses RSVP to signal LSPs, and enables traffic engineering for OSPF. However, no path constraints are configured so you expect the LSPs to be routed over the interior gateway protocol's shortest path.

```
[edit]
user@pe2# set protocols ospf area 0.0.0.0 interface lo0.0
[edit]
user@pe2# set protocols ospf area 0.0.0.0 interface ge-0/0/1.0
[edit]
user@pe2# set protocols ospf traffic-engineering
[edit]
user@pe2# set protocols mpls interface ge-0/0/1.0
[edit]
user@pe2# set protocols rsvp interface lo0.0
[edit]
user@pe2# set protocols rsvp interface ge-0/0/1.0
```

- Define the LSP to the remote PE device's loopback address.

```
[edit]
user@pe2# set protocols mpls label-switched-path lsp_to_pe1 to 192.168.0.1
```

Procedure

Step-by-Step Procedure

Follow these steps to configure the PE2 device for a Layer 2 VPN.

1. Configure the edge-facing interface encapsulation and family. Recall this is an untagged interface, therefore only unit 0 is valid for the ccc family.

```
[edit]user@pe2# set interfaces ge-0/0/0 encapsulation ethernet-ccc
[edit]
user@pe2# set interfaces ge-0/0/0 unit 0 family ccc
[edit]
user@pe1# set interfaces ge-0/0/0 description "Link from PE2 to CE2"
```

2. Configure a BGP group. Specify the PE device's loopback address as the local address and enable family l2vpn signaling.

```
[edit protocols bgp]
user@pe2# set group ibgp local-address 192.168.0.3 family l2vpn signaling
```

3. Configure the BGP group type as internal.

```
[edit protocols bgp]
user@pe2# set group ibgp type internal
```

4. Configure the PE1 device as a BGP neighbor. Be sure to specify PE1's loopback address as the BGP neighbor.

```
[edit protocols bgp]
user@pe2# set group ibgp neighbor 192.168.0.1
```

5. Configure the BGP autonomous system number.

```
[edit routing-options]
user@pe2# set autonomous-system 65412
```

6. Configure the routing instance. Start by specifying the instance name *l2vpn1* with an instance-type of l2vpn.

```
[edit routing-instances]
user@pe2# set l2vpn1 instance-type l2vpn
```

7. Configure the PE device's customer edge-facing interface to belong to the routing instance.

```
[edit routing-instances]
user@pe2# set l2vpn1 interface ge-0/0/0
```

8. Configure the instance's route distinguisher.

```
[edit routing-instances]
user@pe2# set l2vpn1 route-distinguisher 192.168.0.3:12
```

9. Configure the instance's VPN virtual routing and forwarding (VRF) table route target. The assigned target must match the one configured at the PE1 device.

```
[edit routing-instances]
user@pe2# set l2vpn1 vrf-target target:65412:12
```

10. Configure the instance for the l2vpn protocol and specify the encapsulation used on the edge-facing link.

```
[edit routing-instances]
user@pe2# set l2vpn1 protocols l2vpn encapsulation-type ethernet
```

11. Add the PE device's edge-facing interface under the instance's l2vpn hierarchy along with a description .

```
[edit routing-instances]
user@pe2# set l2vpn1 protocols l2vpn interface ge-0/0/0.0 description "L2vpn Link Between
PE2 and CE2"
```

12. Configure the instance's Layer 2 VPN site information and list the PE device's edge-facing interface under the local site. The local site ID configured on the PE2 device must match the remote site ID you configured on the PE1 device, and vice versa.

```
[edit routing-instances]
user@pe1# set l2vpn1 protocols l2vpn site CE-2 site-identifier 2 interface ge-0/0/0.0
remote-site-id 1
```

NOTE: In this example, the site ID for the PE2 device is 2 and the site ID for the PE1 device is 1. For the PE2 device the remote site is correctly configured with a `remote-site-id` value of 1.

13. Commit your changes at the PE2 device and return to CLI operational mode.

```
[edit]
user@pe1# commit and-quit
```

Results

Display the results of the configuration on the PE2 device.

```
user@pe2# show
```

```
interfaces {
  ge-0/0/0 {
    description "Link from PE2 to CE2";
    encapsulation ethernet-ccc;
    unit 0 {
      family ccc;
    }
  }
  ge-0/0/1 {
    description "Link from PE2 to P-router";
    mtu 4000;
    unit 0 {
      family inet {
        address 10.1.34.2/24;
      }
      family mpls;
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 192.168.0.3/32;
      }
    }
  }
}
```



```

    }
  }
}
routing-instances {
  l2vpn1 {
    protocols {
      l2vpn {
        interface ge-0/0/0.0 {
          description "L2vpn Link Between PE2 and CE2" ;
        }
        site CE-2 {
          interface ge-0/0/0.0 {
            remote-site-id 1;
          }
          site-identifier 2;
        }
        encapsulation-type ethernet;
      }
    }
    instance-type l2vpn;
    interface ge-0/0/0.0;
    route-distinguisher 192.168.0.3:12;
    vrf-target target:65412:12;
  }
}
routing-options {
  autonomous-system 65412;
}
protocols {
  bgp {
    group ibgp {
      type internal;
      local-address 192.168.0.3;
      family l2vpn {
        signaling;
      }
      neighbor 192.168.0.1;
    }
  }
  mpls {
    label-switched-path lsp_to_pe1 {
      to 192.168.0.1;
    }
  }
}

```

```

    }
    interface ge-0/0/1.0;
  }
  ospf {
    traffic-engineering;
    area 0.0.0.0 {
      interface lo0.0;
      interface ge-0/0/1.0;
    }
  }
  rsvp {
    interface lo0.0;
    interface ge-0/0/1.0;
  }
}

```

Verification

IN THIS SECTION

- [Verify Provider OSPF Adjacencies and Route Exchange | 200](#)
- [Verify MPLS and RSVP Interface Settings | 200](#)
- [Verify RSVP Signaled LSPs | 201](#)
- [Verify BGP Session Status | 202](#)
- [Verify Layer 2 VPN Routes in the Routing Table | 203](#)
- [Verify Layer 2 VPN Connection Status | 204](#)
- [Ping the Remote PE Device Using the Layer 2 VPN Connection | 205](#)
- [Verify End-to-End Operation of the CE Devices Over the Layer 2 VPN | 207](#)

Perform these tasks to verify that the MPLS-based Layer 2 VPN works properly:

Verify Provider OSPF Adjacencies and Route Exchange

Purpose

Confirm the OSPF protocol is working properly in the provider network by verifying adjacency status and OSPF learned routes to the loopback addresses of the remote provider devices. Proper IGP operation is critical for the successful establishment of MPLS LSPs.

Action

```
user@pe1> show ospf neighbor
```

Address	Interface	State	ID	Pri	Dead
10.1.23.2	ge-0/0/1.0	Full	192.168.0.2	128	38

```
user@pe1> show route protocol ospf | match 192.168
```

192.168.0.2/32	*[OSPF/10] 1w5d 20:48:59, metric 1
192.168.0.3/32	*[OSPF/10] 2w0d 00:08:30, metric 2

Meaning

The output shows that the PE1 device has established an OSPF adjacency to the P device (192.168.0.2). It also shows that the P and remote PE device loopback addresses (192.168.0.2) and (192.168.0.3) are learned via OSPF at the local PE device.

Verify MPLS and RSVP Interface Settings

Purpose

Verify that the RSVP and MPLS protocols are configured to operate on the PE device's core-facing interfaces. This step also verifies that `family mpls` is correctly configured at the unit level of the core-facing interfaces.

Action

```
user@pe1> show mpls interface
```

Interface	State	Administrative groups (x: extended)
ge-0/0/1.0	Up	<none>

```
user@pe1> show rsvp interface
```

Rsvp interface: 2 active

Interface	State	Active resv	Subscr- ption	Static BW	Available BW	Reserved BW	Highwater mark
ge-0/0/1.0	Up	1	100%	1000Mbps	1000Mbps	0bps	0bps
lo0.0	Up	0	100%	0bps	0bps	0bps	0bps

Meaning

The output shows that MPLS and RSVP are correctly configured on the local PE device's core-facing and loopback interfaces.

Verify RSVP Signaled LSPs

Purpose

Verify that the RSVP sessions (ingress and egress) are properly established between the PE devices.

Action

```
user@pe1> show rsvp session
```

To	From	State	Rt	Style	Labelin	Labelout	LSPname
192.168.0.3	192.168.0.1	Up	0	1 FF	-	299888	lsp_to_pe2

Total 1 displayed, Up 1, Down 0

Egress RSVP: 1 sessions

To	From	State	Rt	Style	Labelin	Labelout	LSPname
192.168.0.1	192.168.0.3	Up	0	1 FF	3	-	lsp_to_pe1

Total 1 displayed, Up 1, Down 0

Transit RSVP: 0 sessions

Total 0 displayed, Up 0, Down 0

Meaning

The output shows that both the ingress and egress RSVP sessions are correctly established between the PE devices. Successful LSP establishment indicates the MPLS baseline is operational.

Verify BGP Session Status

Purpose

Verify that the BGP session between the PE devices is correctly established with support for Layer 2 VPN network layer reachability information (NLRI).

Action

```

user@pe1> show bgp summary
Threading mode: BGP I/O
Groups: 1 Peers: 1 Down peers: 0
Table          Tot Paths  Act Paths Suppressed    History Damp State   Pending
bgp.l2vpn.0
              1          1          0          0          0          0
Peer          AS      InPkt    OutPkt    OutQ   Flaps Last Up/Dwn State|#Active/
Received/Accepted/Damped...
192.168.0.3   65412        6         5         0         0        1:34 Establ
  bgp.l2vpn.0: 1/1/1/0
  l2vpn1.l2vpn.0: 1/1/1/0

```

Meaning

The output shows the BGP session to the remote PE device (192.168.0.3) has been correctly established (Establ), and through the Up/Dwn field, how long the session has been in the current state (1:34). It also shows the number of BGP packets sent to (5) and received from (6) the remote PE device. The flaps field confirms that no state transitions have occurred (0), indicating the session is stable. Also note that Layer 2 VPN NLRI is correctly exchanged between the PE devices. This output confirms the BGP peering between the PE devices is ready to support a Layer 2 VPN.

Verify Layer 2 VPN Routes in the Routing Table

Purpose

Verify that the routing table on the PE1 device is populated with the Layer 2 VPN routes used to forward traffic between the CE devices.

Action

```
user@pe1> show route table bgp.l2vpn.0
```

```
bgp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
```

```
+ = Active Route, - = Last Active, * = Both
```

```
192.168.0.3:12:2:1/96
```

```
*[BGP/170] 00:51:36, localpref 100, from 192.168.0.3
```

```
AS path: I, validation-state: unverified
```

```
> to 10.1.23.2 via ge-0/0/1.0, label-switched-path lsp_to_pe2
```

```
user@pe1> show route table l2vpn1.l2vpn.0
```

```
l2vpn1.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
```

```
+ = Active Route, - = Last Active, * = Both
```

```
192.168.0.1:12:1:1/96
```

```
*[L2VPN/170/-101] 01:48:30, metric2 1
```

```
Indirect
```

```
192.168.0.3:12:2:1/96
```

```
*[BGP/170] 00:51:57, localpref 100, from 192.168.0.3
```

```
AS path: I, validation-state: unverified
```

```
> to 10.1.23.2 via ge-0/0/1.0, label-switched-path lsp_to_pe2
```

Meaning

The command `show route table bgp.l2vpn.0` displays all Layer 2 VPN routes that have been received on the PE device. The command `show route table l2vpn1.l2vpn.0` shows the Layer 2 VPN routes that have been imported into the `l2vpn1` routing instance as a result of a matching route target. The `l2vpn1.l2vpn.0` table contains both the local PE device's Layer 2 VPN route as well as a remote route learned via the BGP peering to the remote PE device. Both tables show the remote Layer 2 VPN route is correctly associated

with the `lsp_to_pe2` LSP as a forwarding next hop. The outputs confirm the local PE device has learned about the remote customer site from the PE2 device. It also shows that it can forward Layer 2 VPN traffic to the PE2 device using MPLS transport over the provider network.

Verify Layer 2 VPN Connection Status

Purpose

Verify the status of the Layer 2 VPN connection.

Action

```
user@pe1> show l2vpn connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	HS -- Hot-standby Connection

Legend for interface status

Up -- operational
Dn -- down

Instance: l2vpn1

```

Edge protection: Not-Primary
Local site: CE-1 (1)
  connection-site      Type  St      Time last up      # Up trans
  2                    rmt   Up      Jul 28 10:47:18 2020      1
    Remote PE: 192.168.0.3, Negotiated control-word: Yes (Null)
    Incoming label: 800009, Outgoing label: 800006
    Local interface: ge-0/0/0.0, Status: Up, Encapsulation: ETHERNET
    Flow Label Transmit: No, Flow Label Receive: No

```

Meaning

The St field in the output shows that the Layer 2 VPN connection to Remote PE 192.168.0.3 at connection-site 2 is Up. The output also confirms the PE device's edge-facing interface name `ge-0/0/0.0` and operational status as up. You also verify that Ethernet encapsulation is configured on the PE device's customer-facing interface. This is the correct encapsulation for the untagged Ethernet interfaces used in this example. The verification steps performed thus far indicate that the Layer 2 VPN's control plane is operational. You verify the data plane of the Layer 2 VPN in the following steps.

Ping the Remote PE Device Using the Layer 2 VPN Connection

Purpose

Verify Layer 2 VPN connectivity between the local and remote PE devices. Two forms of the `ping mpls l2vpn` command are shown. Both test Layer 2 VPN routing and MPLS forwarding between the PE devices. The first command assumes a single remote site while the second specifies the local and remote site identifiers, which is useful when testing a multi-site Layer 2 VPN. This is because the remote site ID can be used to target the desired remote PE device.

NOTE: The `ping mpls l2vpn` command validates Layer 2 VPN route exchange and MPLS forwarding between the PE devices. This is done by generating traffic from the local PE's Layer 2 VPN routing instance to the remote PE device's 127.0.0.1 loopback address. This command does not validate the operation of the CE device interfaces or their configuration. This is because CE device operation is opaque to the provider network in a Layer 2 VPN.

Action

```
user@pe1> ping mpls l2vpn interface ge-0/0/0.0 reply-mode ip-udp
```

```
!!!!!
```



```
--- lsping statistics ---
```

```
5 packets transmitted, 5 packets received, 0% packet loss
```

```
user@pe1> ping mpls l2vpn instance l2vpn1 remote-site-id 2 local-site-id 1 detail
```

```
Request for seq 1, to interface 334, labels <800002, 299840>, packet size 88
```

```
Reply for seq 1, return code: Egress-ok, time: 593.784 ms
```

```
    Local transmit time: 2020-07-13 16:15:55 UTC 241.357 ms
```

```
    Remote receive time: 2020-07-13 16:15:55 UTC 835.141 ms
```

```
Request for seq 2, to interface 334, labels <800002, 299840>, packet size 88
```

```
Reply for seq 2, return code: Egress-ok, time: 591.700 ms
```

```
    Local transmit time: 2020-07-13 16:15:56 UTC 241.405 ms
```

```
    Remote receive time: 2020-07-13 16:15:56 UTC 833.105 ms
```

```
Request for seq 3, to interface 334, labels <800002, 299840>, packet size 88
```

```
Reply for seq 3, return code: Egress-ok, time: 626.084 ms
```

```
    Local transmit time: 2020-07-13 16:15:57 UTC 241.407 ms
```

```
    Remote receive time: 2020-07-13 16:15:57 UTC 867.491 ms
```

```
Request for seq 4, to interface 334, labels <800002, 299840>, packet size 88
```

```
Reply for seq 4, return code: Egress-ok, time: 593.061 ms
```

```
    Local transmit time: 2020-07-13 16:15:58 UTC 241.613 ms
```

```
    Remote receive time: 2020-07-13 16:15:58 UTC 834.674 ms
```

```
Request for seq 5, to interface 334, labels <800002, 299840>, packet size 88
```

```
Reply for seq 5, return code: Egress-ok, time: 594.192 ms
```

```
    Local transmit time: 2020-07-13 16:15:59 UTC 241.357 ms
```

```
    Remote receive time: 2020-07-13 16:15:59 UTC 835.549 ms
```

```
--- lsping statistics ---
```

```
5 packets transmitted, 5 packets received, 0% packet loss
```

Meaning

The output confirms that the Layer 2 VPN forwarding plane is operating correctly between the PE devices.

Verify End-to-End Operation of the CE Devices Over the Layer 2 VPN

Purpose

Verify Layer 2 VPN connectivity between the CE devices. This step confirms the CE devices have operational interfaces and are properly configured for Layer 2 connectivity. This is done by verifying the CE devices have established an OSPF adjacency and are able to pass traffic end-to-end between their loopback addresses.

Action

```
user@ce1> show ospf neighbor
```

Address	Interface	State	ID	Pri	Dead
172.16.1.2	ge-0/0/0.0	Full	172.16.255.2	128	32

```
user@ce1> show ospf route | match 172
```

```
172.16.255.2/32    *[OSPF/10] 01:34:50, metric 1
                  > to 172.16.1.2 via ge-0/0/0.0
```

```
user@ce1> ping 172.16.255.2 size 1472 do-not-fragment count 2
```

```
PING 172.16.255.2 (172.16.255.2): 1472 data bytes
1480 bytes from 172.16.255.2: icmp_seq=0 ttl=64 time=4.404 ms
1480 bytes from 172.16.255.2: icmp_seq=1 ttl=64 time=5.807 ms
```

```
--- 172.16.255.2 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 4.404/5.106/5.807/0.702 ms
```

Meaning

The output shows that Layer 2 VPN connectivity is working correctly between the CE devices. It confirms that the local CE device has established an OSPF adjacency over the provider core to the remote CE device 172.16.1.2, and that the local CE device has learned a route to the remote CE device's loopback address 172.16.255.2 via OSPF. The output also shows that the CE devices are able to pass

1500-byte IP packets without evoking local fragmentation. The successful pings also verify the frames did not exceed the MTU supported by the provider's network.

NOTE: The size argument added to the ping command generates 1472 bytes of echo data. An additional 8 bytes of Internet Control Message Protocol (ICMP) and 20 bytes of IP header are added to bring the total packet size to 1500-bytes. Adding the do-not-fragment switch ensures the CE device cannot perform fragmentation based on its local MTU. This method confirms that no fragmentation is possible, or needed, when sending standard length Ethernet frames between the CE devices.

RELATED DOCUMENTATION

Example: Configuring MPLS on EX8200 and EX4500 Switches

Example: Configure a Basic MPLS-Based Layer 3 VPN

Transmitting Nonstandard BPDUs in Layer 2 VPNs and VPLS

Circuit cross-connect (CCC) protocol, Layer 2 circuit, and Layer 2 VPN configurations can transmit nonstandard bridge protocol data units (BPDUs) generated by other vendors' equipment. This is the default behavior on all supported PICs and requires no additional configuration.

The following PICs are supported on T Series Core Routers and the M320 Multiservice Edge router and can transmit nonstandard BPDUs:

- 1-port Gigabit Ethernet PIC
- 2-port Gigabit Ethernet PIC
- 4-port Gigabit Ethernet PIC
- 10-port Gigabit Ethernet PIC

Configuring Layer 2 Interfaces

IN THIS CHAPTER

- [Configuring CCC Encapsulation for Layer 2 VPNs | 209](#)
- [Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits | 210](#)
- [Configuring the MTU for Layer 2 Interfaces | 212](#)
- [Disabling the Control Word for Layer 2 VPNs | 214](#)

Configuring CCC Encapsulation for Layer 2 VPNs

You need to specify a circuit cross-connect (CCC) encapsulation type for each PE-router-to-CE-router interface running a Layer 2 VPN. This encapsulation type should match the encapsulation type configured under the routing instance. For information about how to configure the encapsulation type under the routing instance, see ["Configuring the Encapsulation Type" on page 153](#).

NOTE: A Layer 2 VPN or Layer 2 circuit is not supported if the PE-router-to-P-router interface has VLAN-tagging enabled and uses a nonenhanced Flexible PIC Concentrator (FPC).

For Layer 2 VPNs, you need to configure the CCC encapsulation on the logical interface. You also need to configure an encapsulation on the physical interface. The physical interface encapsulation does not have to be a CCC encapsulation. However, it should match the logical interface encapsulation. For example, if you configure an ATM CCC encapsulation type on the logical interface, you should configure a compatible ATM encapsulation on the physical interface.

NOTE: The EX9200 switches only use ethernet and ethernet-vlan encapsulation types.

To configure the CCC encapsulation type, include the `encapsulation-type` statement:

```
encapsulation-type ccc-encapsulation-type;
```

On the EX9200 switches, replace `encapsulation-type` with the `encapsulation` statement:

```
encapsulation ccc-encapsulation;
```

To configure the CCC encapsulation type on the physical interface, include this statement at the following hierarchy levels:

- [edit interfaces *interface-name*]
- [edit logical-systems *logical-system-name* interfaces *interface-name*]

To configure the CCC encapsulation type on the logical interface, include this statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number*]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number*]

You configure the encapsulation type at the [edit interfaces] hierarchy level differently from the [edit routing-instances] hierarchy level. For example, you specify the encapsulation as `frame-relay` at the [edit routing-instances] hierarchy level and as `frame-relay-ccc` at the [edit interfaces] hierarchy level.

You can run both standard Frame Relay and CCC Frame Relay on the same device. If you specify Frame Relay encapsulation (`frame-relay-ccc`) for the interface, you should also configure the encapsulation at the [edit interfaces *interface name* unit *unit-number*] hierarchy level as `frame-relay-ccc`. Otherwise, the logical interface unit defaults to standard Frame Relay.

Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits

Also known as Layer 2.5 VPNs, the translation cross-connect (TCC) encapsulation types allow you to configure different encapsulation types at the ingress and egress of a Layer 2 VPN or the ingress and egress of a Layer 2 circuit. For example, a CE router at the ingress of a Layer 2 VPN path can send traffic in a Frame Relay encapsulation. A CE router at the egress of that path can receive the traffic in an ATM encapsulation.

NOTE: The EX9200 switches only use ethernet and ethernet-vlan encapsulation types.

For information about how to configure encapsulations for Layer 2 circuits, see ["Configuring the Interface Encapsulation Type for Layer 2 Circuits" on page 369](#)

The configuration for TCC encapsulation types is similar to the configuration for CCC encapsulation types. For Layer 2 VPNs, you specify a TCC encapsulation type for each PE-router-to-CE-router interface. The encapsulation type configured for the interface should match the encapsulation type configured under the routing instance. For information about how to configure the encapsulation type under the routing instance, see ["Configuring the Encapsulation Type" on page 153](#).

NOTE: Some platform and FPC combinations can not pass TCC encapsulated ISO traffic. See [Platforms/FPCs That Cannot Forward TCC Encapsulated ISO Traffic](#) for details.

You need to configure the TCC encapsulation on both the physical and logical interfaces. To configure the TCC encapsulation type, include the `encapsulation-type` statement:

```
encapsulation-type tcc-encapsulation-type;
```

On the EX9200 switches, replace `encapsulation-type` with the `encapsulation` statement:

```
encapsulation tcc-encapsulation;
```

To configure the TCC encapsulation type on the physical interface, include this statement at the following hierarchy levels:

- [edit interfaces *interface-name*]
- [edit logical-systems *logical-system-name* interfaces *interface-name*]

To configure the TCC encapsulation type on the logical interface, include this statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number*]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number*]

You configure the encapsulation type at the [edit interfaces] hierarchy level differently than at the [edit routing-instances] hierarchy level. For example, you specify the encapsulation as `frame-relay` at the [edit routing-instances] hierarchy level and as `frame-relay-tcc` at the [edit interfaces] hierarchy level.

For Layer 2.5 VPNs employing an Ethernet interface as the TCC router, you can configure an Ethernet TCC or an extended VLAN TCC.

To configure an Ethernet TCC or an extended VLAN TCC, include the `proxy` and `remote` statements:

```
proxy inet-address;
remote (inet-address | mac-address);
```

You can include these statements at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number* family tcc]
- [edit logical-interfaces *logical-interface-name* interfaces *interface-name* unit *logical-unit-number* family tcc]

The `proxy inet-address` address statement defines the IP address for which the TCC router is acting as proxy.

The `remote (inet-address | mac-address)` statement defines the location of the remote router.

Ethernet TCC is supported on interfaces that carry IP version 4 (IPv4) traffic only. However, Ethernet TCC encapsulation is not supported on 8-port, 12-port, and 48-port Fast Ethernet PICs.

Configuring the MTU for Layer 2 Interfaces

By default, the MTU used to advertise a Layer 2 pseudowire is determined by taking the interface MTU for the associated physical interface and subtracting the encapsulation overhead for sending IP packets based on the encapsulation. However, encapsulations that support multiple logical interfaces (and multiple Layer 2 pseudowires) rely on the same interface MTU (since they are all associated with the same physical interface). This can prove to be a limitation for VLAN Layer 2 pseudowires using the same Ethernet interface or for Layer 2 pseudowire DLCIs using the same Frame Relay interface.

This can also affect multivendor environments. For example, if you have three PE devices supplied by different vendors and one of the devices only supports an MTU of 1500, even if the other devices support larger MTUs you must configure the MTU as 1500 (the smallest MTU of the three PE devices).

You can explicitly configure which MTU is advertised for a Layer 2 pseudowire, even if the Layer 2 pseudowire is sharing a physical interface with other Layer pseudowires. When you explicitly configure an MTU for a Layer 2 pseudowire, be aware of the following:

- For BGP-based applications such as l2vpn, the advertised MTU will be zero unless an MTU value is explicitly set at the [edit routing-instances *routing-instance-name* protocols (*l2vpn*) site *site-name*] hierarchy level.

- An explicitly configured MTU is signaled to the remote PE device. The configured MTU is also compared to the MTU received from the remote PE device. If there is a conflict, the Layer 2 pseudowire is taken down.
- If you configure an MTU for an ATM cell relay interface on an ATM II PIC, the configured MTU is used to compute the cell bundle size advertised for that Layer 2 pseudowire, instead of the default interface MTU.
- A configured MTU is used only in the control plane. It is not enforced in the data plane. You need to ensure that the CE device for a given Layer 2 pseudowire uses the correct MTU for data transmission.

The following procedure describes how to configure the MTU for the Layer 2 interface. This information applies to the following Layer 2 technologies:

- Layer 2 VPNs
- Layer 2 Circuits

1. To configure the MTU for a Layer 2 circuit, include the `mtu` statement:

```
mtu mtu-number;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

2. To allow a Layer 2 pseudowire to be established even though the MTU configured on the local PE router does not match the MTU configured on the remote PE router, include the `ignore-mtu-mismatch` statement:

```
ignore-mtu-mismatch;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

RELATED DOCUMENTATION

[ignore-mtu-mismatch](#) | 1525

[mtu](#)

Disabling the Control Word for Layer 2 VPNs

A 4-byte control word provides support for the emulated VC encapsulation for Layer 2 VPNs. This control word is added between the Layer 2 protocol data unit (PDU) being transported and the VC label that is used for demultiplexing. Various networking formats (ATM, Frame Relay, Ethernet, and so on) use the control word in a variety of ways.

On networks with equipment that does not support the control word, you can disable it by including the `no-control-word` statement:

```
no-control-word;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols l2vpn]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols l2vpn]

For more information about configuring the control word, see "[Configuring the Control Word for Layer 2 Circuits](#)" on page 362 and the *Layer 2 Circuits User Guide*.

NOTE: Use the `no-control-word` statement to disable the control word when the topology uses generic routing encapsulation (GRE) as the connection mechanism between PEs, and one of the PEs is an M Series router.

RELATED DOCUMENTATION

[Configuring the Control Word for Layer 2 Circuits | 362](#)

[control-word \(Protocols Layer 2 VPN\) | 1456](#)

l2vpn

Configuring Path Selection for Layer 2 VPNs and VPLS

IN THIS CHAPTER

- [Understanding BGP Path Selection | 215](#)
- [Enabling BGP Path Selection for Layer 2 VPNs and VPLS | 220](#)

Understanding BGP Path Selection

IN THIS SECTION

- [Routing Table Path Selection | 217](#)
- [BGP Table path selection | 219](#)
- [Effects of Advertising Multiple Paths to a Destination | 219](#)

For each prefix in the routing table, the routing protocol process selects a single best path. After the best path is selected, the route is installed in the routing table. The best path becomes the active route if the same prefix is not learned by a protocol with a lower (more preferred) global preference value, also known as the administrative distance. The algorithm for determining the active route is as follows:

1. Verify that the next hop can be resolved.
2. Choose the path with the lowest preference value (routing protocol process preference).

Routes that are not eligible to be used for forwarding (for example, because they were rejected by routing policy or because a next hop is inaccessible) have a preference of -1 and are never chosen.

3. Prefer the path with higher local preference.

For non-BGP paths, choose the path with the lowest **preference2** value.

4. If the accumulated interior gateway protocol (AIGP) attribute is enabled, prefer the path with the lower AIGP attribute.
5. Prefer the path with the shortest autonomous system (AS) path value (skipped if the `as-path-ignore` statement is configured).

A confederation segment (sequence or set) has a path length of 0. An AS set has a path length of 1.

6. Prefer the route with the lower origin code.

Routes learned from an IGP have a lower origin code than those learned from an exterior gateway protocol (EGP), and both have lower origin codes than incomplete routes (routes whose origin is unknown).

7. Prefer the path with the lowest multiple exit discriminator (MED) metric.

Depending on whether nondeterministic routing table path selection behavior is configured, there are two possible cases:

- If nondeterministic routing table path selection behavior is not configured (that is, if the `path-selection cisco-nondeterministic` statement is not included in the BGP configuration), for paths with the same neighboring AS numbers at the front of the AS path, prefer the path with the lowest MED metric. To always compare MEDs whether or not the peer ASs of the compared routes are the same, include the `path-selection always-compare-med` statement.
- If nondeterministic routing table path selection behavior is configured (that is, the `path-selection cisco-nondeterministic` statement is included in the BGP configuration), prefer the path with the lowest MED metric.

Confederations are not considered when determining neighboring ASs. A missing MED metric is treated as if a MED were present but zero.

NOTE: MED comparison works for single path selection within an AS (when the route does not include an AS path), though this usage is uncommon.

By default, only the MEDs of routes that have the same peer autonomous systems (ASs) are compared. You can configure routing table path selection options to obtain different behaviors.

8. Prefer strictly internal paths, which include IGP routes and locally generated routes (static, direct, local, and so forth).
9. Prefer strictly external BGP (EBGP) paths over external paths learned through internal BGP (IBGP) sessions.
10. Prefer the path whose next hop is resolved through the IGP route with the lowest metric.

NOTE: A path is considered a BGP equal-cost path (and will be used for forwarding) if a tie-break is performed after the previous step. All paths with the same neighboring AS, learned by a multipath-enabled BGP neighbor, are considered.

BGP multipath does not apply to paths that share the same MED-plus-IGP cost yet differ in IGP cost. Multipath path selection is based on the IGP cost metric, even if two paths have the same MED-plus-IGP cost.

BGP compares the type of IGP metric before comparing the metric value itself in `rt_metric2_cmp`. For example, BGP routes that are resolved through IGP are preferred over discarded or rejected next-hops that are of type `RTM_TYPE_UNREACH`. Such routes are declared inactive because of their `metric-type`.

11. If both paths are external, prefer the currently active path to minimize route-flapping. This rule is not used if any one of the following conditions is true:
 - **path-selection external-router-id** is configured.
 - Both peers have the same router ID.
 - Either peer is a confederation peer.
 - Neither path is the current active path.
12. Prefer a primary route over a secondary route. A primary route is one that belongs to the routing table. A secondary route is one that is added to the routing table through an export policy.
13. Prefer the path from the peer with the lowest router ID. For any path with an originator ID attribute, substitute the originator ID for the router ID during router ID comparison.
14. Prefer the path with the shortest cluster list length. The length is 0 for no list.
15. Prefer the path from the peer with the lowest peer IP address.

Routing Table Path Selection

The shortest AS path step of the algorithm, by default, evaluates the length of the AS path and determines the active path. You can configure an option that enables Junos OS to skip this step of the algorithm by including the **as-path-ignore** option.

NOTE: Starting with Junos OS Release 14.1R8, 14.2R7, 15.1R4, 15.1F6, and 16.1R1, the **as-path-ignore** option is supported for routing instances.

The routing process path selection takes place before BGP hands off the path to the routing table to make its decision. To configure routing table path selection behavior, include the `path-selection` statement:

```
path-selection {
  (always-compare-med | cisco-non-deterministic | external-router-id);
  as-path-ignore;
  l2vpn-use-bgp-rules;
  med-plus-igp {
    igp-multiplier number;
    med-multiplier number;
  }
}
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

Routing table path selection can be configured in one of the following ways:

- Emulate the Cisco IOS default behavior (**cisco-non-deterministic**). This mode evaluates routes in the order that they are received and does not group them according to their neighboring AS. With `cisco-non-deterministic` mode, the active path is always first. All inactive, but eligible, paths follow the active path and are maintained in the order in which they were received, with the most recent path first. Ineligible paths remain at the end of the list.

As an example, suppose you have three path advertisements for the 192.168.1.0 /24 route:

- Path 1—learned through EBGp; AS Path of 65010; MED of 200
- Path 2—learned through IBGP; AS Path of 65020; MED of 150; IGP cost of 5
- Path 3—learned through IBGP; AS Path of 65010; MED of 100; IGP cost of 10

These advertisements are received in quick succession, within a second, in the order listed. Path 3 is received most recently, so the routing device compares it against path 2, the next most recent advertisement. The cost to the IBGP peer is better for path 2, so the routing device eliminates path 3 from contention. When comparing paths 1 and 2, the routing device prefers path 1 because it is received from an EBGp peer. This allows the routing device to install path 1 as the active path for the route.

NOTE: We do not recommend using this configuration option in your network. It is provided solely for interoperability to allow all routing devices in the network to make consistent route selections.

- Always comparing MEDs whether or not the peer ASs of the compared routes are the same (**always-compare-med**).
- Override the rule that If both paths are external, the currently active path is preferred (**external-router-id**). Continue with the next step (Step "12" on page 217) in the path-selection process.
- Adding the IGP cost to the next-hop destination to the MED value before comparing MED values for path selection (**med-plus-igp**).

BGP multipath does not apply to paths that share the same MED-plus-IGP cost, yet differ in IGP cost. Multipath path selection is based on the IGP cost metric, even if two paths have the same MED-plus-IGP cost.

BGP Table path selection

The following parameters are followed for BGP's path selection:

1. Prefer the highest local-preference value.
2. Prefer the shortest AS-path length.
3. Prefer the lowest origin value.
4. Prefer the lowest MED value.
5. Prefer routes learned from an EBGP peer over an IBGP peer.
6. Prefer best exit from AS.
7. For EBGP-received routes, prefer the current active route.
8. Prefer routes from the peer with the lowest Router ID.
9. Prefer paths with the shortest cluster length.
10. Prefer routes from the peer with the lowest peer IP address. Steps 2, 6 and 12 are the RPD criteria.

Effects of Advertising Multiple Paths to a Destination

BGP advertises only the active path, unless you configure BGP to advertise multiple paths to a destination.

Suppose a routing device has in its routing table four paths to a destination and is configured to advertise up to three paths (**add-path send path-count 3**). The three paths are chosen based on path selection criteria. That is, the three best paths are chosen in path-selection order. The best path is the

active path. This path is removed from consideration and a new best path is chosen. This process is repeated until the specified number of paths is reached.

Release History Table

Release	Description
14.1R8	Starting with Junos OS Release 14.1R8, 14.2R7, 15.1R4, 15.1F6, and 16.1R1, the as-path-ignore option is supported for routing instances.

RELATED DOCUMENTATION

[Example: Ignoring the AS Path Attribute When Selecting the Best Path](#)

[Examples: Configuring BGP MED](#)

[Example: Advertising Multiple BGP Paths to a Destination](#)

Enabling BGP Path Selection for Layer 2 VPNs and VPLS

Layer 2 VPNs and VPLS share the same path selection process for determining the optimal path to reach all of the destinations shared within a single routing instance. For Layer 2 VPN and VPLS topologies, the path selection process is straightforward if there is just a single path from each PE router to each CE device. However, the path selection process becomes more complex if the PE routers receive two or more valid paths to reach a specific CE device.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The following network scenarios provide examples of what might cause a PE router to receive more than one valid path to reach a specific CE device:

- **Multihoming**—One or more CE devices within a routing instance are multihomed to two or more PE routers. Each multihomed CE device has at least two valid paths.
- **Route reflectors**—There are multiple route reflectors deployed within the same network and they are supporting PE routers within the same routing instance. Due to time delays in large complex networks, the route reflectors can separately receive a different valid path to reach a CE device at different times. When they readvertise these valid paths, a PE router could receive two or more separate but apparently valid paths to the same CE device.

By default, Juniper Networks routers use just the designated forwarder path selection algorithm to select the best path to reach each Layer 2 VPN or VPLS routing instance destination (for more information, see ["VPLS Path Selection Process for PE Routers" on page 753](#)). However, you can also configure the routers in your network to use both the BGP path selection algorithm and the designated forwarder path selection algorithm as follows:

- On the Provider routers within the service providers network, the standard BGP path selection algorithm is used (for more information, see *Understanding BGP Path Selection*). Using the standard BGP path selection for Layer 2 VPN and VPLS routes allows a service provider to leverage the existing Layer 3 VPN network infrastructure to also support Layer 2 VPNs and VPLS. The BGP path selection algorithm also helps to ensure that the service provider's network behaves predictably with regard to Layer 2 VPN and VPLS path selection. This is particularly important in networks employing route reflectors and multihoming.

When a Provider router receives multiple paths for the same destination prefix (for example, a multihomed CE device), one path is selected based on the BGP path selection algorithm and placed in the `bgp.l2vpn.0` routing table and the appropriate `instance.l2vpn.0` routing table.

- When a PE router receives all of the available paths to each CE device, it runs the designated forwarder path selection algorithm to select the preferred path to reach each CE device, independently of the results of the earlier BGP path selection algorithm run on the Provider router. The VPLS designated forwarder algorithm uses the D-bit, preference, and PE router identifier to determine which of the valid paths to each CE device to use. The PE router might select a path to reach a CE device which is different from the path selected by the BGP-based Provider routers. In this scenario, the following is the expected behavior for traffic sent to the multihomed CE device:
 - If the path selected by the remote PE router is available, traffic will traverse the network to the multihomed CE device using the remote PE router's preferred path (again, ignoring the path selected by the BGP-based Provider routers).
 - If the path selected by the remote PE router fails:
 1. The Provider routers switch the traffic destined for the multihomed CE device to the alternate path as soon as failure is detected.
 2. The Provider routers notify the remote PE routers of the path failure.
 3. The remote PE routers update their routing tables accordingly.

For more information about the VPLS designated forwarder path selection algorithm, see ["VPLS Path Selection Process for PE Routers" on page 753](#). This algorithm is also described in the Internet draft `draft-kompella-l2vpn-vpls-multihoming-03.txt`, *Multi-homing in BGP-based Virtual Private LAN Service*.

To enable the BGP path selection algorithm for Layer 2 VPN and VPLS routing instances, complete the following steps:

1. Run Junos OS Release 12.3 or later on all of the PE and Provider routers participating in Layer 2 VPN or VPLS routing instances.
Attempting to enable this functionality on a network with a mix of routers that both do and do not support this feature can result in anomalous behavior.
2. Specify a unique route distinguisher on each PE router participating in a Layer 2 VPN or VPLS routing instance.
3. Configure the `l2vpn-use-bgp-rules` statement on all of the PE and Provider routers participating in Layer 2 VPN or VPLS routing instances.

You can configure this statement at the `[edit protocols bgp path-selection]` hierarchy level to apply this behavior to all of the routing instances on the router or at the `[edit routing-instances routing-instance-name protocols bgp path-selection]` hierarchy level to apply this behavior to a specific routing instance.

RELATED DOCUMENTATION

Understanding BGP Path Selection

[VPLS Path Selection Process for PE Routers | 753](#)

path-selection

route-distinguisher

Creating Backup Connections with Redundant Pseudowires

IN THIS CHAPTER

- [Redundant Pseudowires for Layer 2 Circuits and VPLS | 223](#)
- [Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS | 226](#)

Redundant Pseudowires for Layer 2 Circuits and VPLS

IN THIS SECTION

- [Types of Redundant Pseudowire Configurations | 224](#)
- [Pseudowire Failure Detection | 225](#)

A redundant pseudowire can act as a backup connection between PE routers and CE devices, maintaining Layer 2 circuit and VPLS services after certain types of failures. This feature can help improve the reliability of certain types of networks (metro for example) where a single point of failure could interrupt service for multiple customers. Redundant pseudowires cannot reduce traffic loss to zero. However, they provide a way to gracefully recover from pseudowire failures in such a way that service can be restarted within a known time limit.

NOTE: VPLS is not supported on ACX Series routers.

When you configure redundant pseudowires to remote PE routers, you configure one to act as the primary pseudowire over which customer traffic is being transmitted and you configure another pseudowire to act as a backup in the event the primary fails. You configure the two pseudowires statically. A separate label is allocated for the primary and backup neighbors.

For information about how to configure redundant pseudowires, see ["Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS" on page 226](#).

The following sections provide an overview of redundant pseudowires for Layer 2 circuits and VPLS:

Types of Redundant Pseudowire Configurations

You can configure redundant pseudowires for Layer 2 circuits and VPLS in either of the following manners:

NOTE: VPLS is not supported on ACX Series routers.

- You can configure a single active pseudowire. The PE router configured as the primary neighbor is given preference and this connection is the one used for customer traffic. For the LDP signalling, labels are exchanged for both incoming and outgoing traffic with the primary neighbor. The LDP label advertisement is accepted from the backup neighbor, but no label advertisement is forwarded to it, leaving the pseudowire in an incomplete state. The pseudowire to the backup neighbor is completed only when the primary neighbor fails. The decision to switch between the two pseudowires is made by the device configured with the redundant pseudowires. The primary remote PE router is unaware of the redundant configuration, ensuring that traffic is always switched using just the active pseudowire.
- Alternatively, you can configure two active pseudowires, one to each of the PE routers. Using this approach, control plane signalling is completed and active pseudowires are established with both the primary and backup neighbors. However, the data plane forwarding is done only over a one of the pseudowires (designated as the active pseudowire by the local device). The other pseudowire is on standby. The active pseudowire is preferably established with the primary neighbor and can switch to the backup pseudowire if the primary fails.

The decision to switch between the active and standby pseudowires is controlled by the local device. The remote PE routers are unaware of the redundant connection, and so both remote PE routers send traffic to the local device. The local device only accepts traffic from the active pseudowire and drops the traffic from the standby. In addition, the local device only sends traffic to the active pseudowire. If the active pseudowire fails, traffic is immediately switched to the standby pseudowire.

The two configurations available for pseudowire redundancy have the following limitations:

- For the single active pseudowire configuration, it takes more time (compared to the two active pseudowire configuration) to switchover to the backup pseudowire when a failure is detected. This approach requires additional control plane signalling to complete the pseudowire with the backup neighbor and traffic can be lost during the switchover from primary to backup.

- If you configure two active pseudowires, bandwidth is lost on the link carrying the backup pseudowire between the remote PE router and the local device. Traffic is always duplicated over both the active and standby pseudowires. The single active pseudowire configuration does not waste bandwidth in this fashion.

Pseudowire Failure Detection

The following events are used to detect a failure (control and data plane) of the pseudowire configured between a local device and a remote PE router and initiates the switch to a redundant pseudowire:

- Manual switchover (user initiated)
- Remote PE router withdraws the label advertisement
- LSP to the remote PE router goes down
- LDP session with the remote PE router goes down
- Local configuration changes
- Periodic pseudowire OAM procedure fails (Layer 2 circuit-based MPLS ping to the PE router fails)

When you configure a redundant pseudowire between a CE device and a PE router, a periodic (once a minute) ping packet is forwarded through the active pseudowire to verify data plane connectivity. If the ping fails, traffic is automatically switched to the redundant pseudowire.

When a failure is detected, traffic is switched from the failed active pseudowire to the redundant pseudowire. The redundant pseudowire is then designated as the active pseudowire. The switch is nonreversible, meaning that once the redundant pseudowire assumes the role of the active pseudowire at the time of a failover, it remains as the active pseudowire even though the previously active pseudowire comes up again.

For example, a primary pseudowire has failed and traffic has been successfully switched to the redundant pseudowire. After a period of time, the cause of the failure of the primary pseudowire has been resolved and it is now possible to reestablish the original connection. However, traffic is not switched back to the original pseudowire unless a failure is detected on the currently active pseudowire.

RELATED DOCUMENTATION

| [Example: Configuring H-VPLS Without VLANs](#) | 861

Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS

IN THIS SECTION

- [Configuring Pseudowire Redundancy on the PE Router | 226](#)
- [Configuring the Switchover Delay for the Pseudowires | 227](#)
- [Configuring a Revert Time for the Redundant Pseudowire | 227](#)

A redundant pseudowire can act as a backup connection between PE routers and CE devices, maintaining Layer 2 circuit and VPLS services after certain types of failures. This feature can help improve the reliability of certain types of networks (metro for example) where a single point of failure could interrupt service for multiple customers. Redundant pseudowires cannot reduce traffic loss to zero. However, they provide a way to gracefully recover from pseudowire failures in such a way that service can be restarted within a known time limit.

NOTE: VPLS is not supported on ACX Series routers.

For an overview of how redundant pseudowires work, see ["Redundant Pseudowires for Layer 2 Circuits and VPLS" on page 223](#).

To configure pseudowire redundancy for Layer 2 circuits and VPLS, complete the procedures in the following sections:

Configuring Pseudowire Redundancy on the PE Router

You configure pseudowire redundancy on the PE router acting as the egress for the primary and standby pseudowires using the `backup-neighbor` statement.

To configure pseudowire redundancy on the PE router, include the `backup-neighbor` statement:

```
backup-neighbor {  
    community name;  
    psn-tunnel-endpoint address;  
    standby;  
    virtual-circuit-id number;  
}
```

For a list of hierarchy levels at which you can include this statement, see the statement summary for this statement.

The `backup-neighbor` statement includes the following configuration options:

- `community`—Specifies the community for the backup neighbor.
- `psn-tunnel-endpoint`—Specifies the endpoint address for the packet switched network (PSN) tunnel on the remote PE router. The PSN tunnel endpoint address is the destination address for the LSP on the remote PE router.
- `standby`—Configures the pseudowire to the specified backup neighbor as the standby. When you configure this statement, traffic flows over both the active and standby pseudowires to the CE device. The CE device drops the traffic from the standby pseudowire, unless the active pseudowire fails. If the active pseudowire fails, the CE device automatically switches to the standby pseudowire.
- `virtual-circuit-id`—Uniquely identifies the primary and standby Layer 2 circuits. This option is configurable for Layer 2 circuits only.

Configuring the Switchover Delay for the Pseudowires

To configure the time the router waits before switching traffic from the failed primary pseudowire to a backup pseudowire, include the `switchover-delay` statement:

```
switchover-delay milliseconds;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary for this statement.

Configuring a Revert Time for the Redundant Pseudowire

You can specify a revert time for redundant Layer 2 circuit and VPLS pseudowires. When you have configured redundant pseudowires for Layer 2 circuits or VPLS, traffic is switched to the backup pseudowire in the event that the primary pseudowire fails. If you configure a revert time, when the configured time expires traffic is reverted back to the primary pseudowire, assuming the primary pseudowire has been restored.

To configure a revert time for redundant pseudowires, specify the time in seconds using the `revert-time` statement:

```
revert-time (Protocols Layer 2 Circuits) seconds maximum seconds;
```

With the `maximum` option, specify a maximum reversion interval to add after the `revert-time` delay. If a `revert-time` delay is defined but a maximum timer is not defined, VCs are restored upon the revert-timer's expiration.

To reduce as much as possible the amount of traffic discarded, and potential data-path asymmetries observed during primary-to-backup transition periods, you can use this restoration timer. This restoration timer is activated when the backup path is performing as active, and then the primary path is restored. The goal is to avoid moving traffic back to the primary path right away, to make sure that the control plane's related tasks (such as IGP, LDP, RSVP, and internal BGP) have enough time to complete their updating cycle.

By enabling a gradual return of traffic to the primary path, you can ensure that the relatively-slow control-plane processing and updating does not have a negative impact on the restoration process.

The `maximum` option extends the revert timer's functionality to provide a jittered interval over which a certain number of circuits can be transitioned back to the primary path. By making use of this maximum value, you can define a time interval during which circuits are expected to switch over. As a consequence, circuits' effective transitions are scattered during restoration periods.

When making use of `revert-time x maximum y` statement, you can ensure that the corresponding circuit that is active is moved to the primary path within a time-slot (t1) such as that: $x \leq t1 \leq y$. In other words, by activating this statement, you can ensure the following:

- VCs stay in the backup path for at least x seconds after the primary path comes back up.
- VCs are moved back to the primary path before y seconds have elapsed.
- $y \text{ maximum value} = x \text{ maximum value} * 2 = 1200 \text{ seconds}$.

The ideal values for x and y will be conditioned to internal aspects of your network. For this reason, there are no default values for these settings. If no `revert-time` is set, the default behavior is non-revertive. That is, circuits are not returned to the primary path upon restoration. They are kept on the backup path.

For a list of hierarchy levels at which you can include this statement, see the statement summary for this statement.

RELATED DOCUMENTATION

[Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario | 391](#)

[Example: Configuring H-VPLS Without VLANs | 861](#)

Configuring Class of Service for Layer 2 VPNs

IN THIS CHAPTER

- [Configuring Traffic Policing in Layer 2 VPNs | 229](#)

Configuring Traffic Policing in Layer 2 VPNs

You can use policing to control the amount of traffic flowing over the interfaces servicing a Layer 2 VPN. If policing is disabled on an interface, all the available bandwidth on a Layer 2 VPN tunnel can be used by a single CCC or TCC interface.

For information on how to configure traffic policers, see the [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

To enable Layer 2 VPN policing on an interface, include the `policer` statement:

```
policer {  
    input policer-template-name;  
    output policer-template-name;  
}
```

If you configure CCC encapsulation, you can include the `policer` statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number* family ccc]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number* family ccc]

If you configure TCC encapsulation, you can include the `policer` statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number* family tcc]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number* family tcc]

For information about how to configure the encapsulation type, see "[Configuring the Encapsulation Type](#)" on page 153.

Monitoring Layer 2 VPNs

IN THIS CHAPTER

- [Configuring BFD for Layer 2 VPN and VPLS | 231](#)
- [BFD Support for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 233](#)
- [Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 234](#)
- [Connectivity Fault Management Support for EVPN and Layer 2 VPN Overview | 235](#)
- [Configuring a MEP to Generate and Respond to CFM Protocol Messages | 238](#)

Configuring BFD for Layer 2 VPN and VPLS

The following procedure describes how to configure Bidirectional Forwarding Detection (BFD) for Layer 2 VPN and VPLS. For VPNs, you configure the BFD sessions on the interfaces carrying traffic from the PE routers to the CE routers.

The BFD protocol is a simple hello mechanism that detects failures in a network. Hello packets are sent at a specified, regular interval. A neighbor failure is detected when the routing device stops receiving a reply after a specified interval. BFD works with a wide variety of network environments and topologies. The failure detection timers for BFD have shorter time limits than default failure detection mechanisms for BGP, so they provide faster detection.

The BFD failure detection timers are adaptive and can be adjusted to be faster or slower. The lower the BFD failure detection timer value, the faster the failure detection and vice versa. For example, the timers can adapt to a higher value if the adjacency fails (that is, the timer detects failures more slowly). Or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds. A back-off algorithm increases the receive interval by two if the local BFD instance is the reason for the session flap. The transmission interval is increased by two if the remote BFD instance is the reason for the session flap. You can use the `clear bfd adaptation` command to return BFD interval timers to their configured values. The `clear bfd adaptation` command is hitless, meaning that the command does not affect traffic flow on the routing device.

1. You can enable BFD failure detection. The BFD failure detection timers are adaptive and can be adjusted to be faster or slower. The lower the BFD failure detection timer value, the faster the failure

detection and vice versa. For example, the timers can adapt to a higher value if the adjacency fails (that is, the timer detects failures more slowly). Or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds. A back-off algorithm increases the receive (Rx) interval by two if the local BFD instance is the reason for the session flap. The transmission (Tx) interval is increased by two if the remote BFD instance is the reason for the session flap.

To enable BFD failure detection and specify the threshold for the adaptation of the BFD session detection time, specify a time in milliseconds using the threshold statement. When the detection time adapts to a value equal to or greater than the threshold, a single trap and a single system log message are sent.

NOTE: The threshold time must be equal to or greater than the value specified in the minimum-interval or the minimum-receive-interval statement.

You can use the `clear bfd adaptation` command to return BFD interval timers to their configured values. The `clear bfd adaptation` command is hitless, meaning that the command does not affect traffic flow on the routing device.

2. You can specify the minimum interval after which the local routing device transmits hello packets and then expects to receive a reply from a neighbor with which it has established a BFD session. You specify the interval in milliseconds using the ["minimum-interval" on page 1572](#) statement.
Optionally, instead of using this statement, you can specify the minimum transmit and receive intervals separately using the minimum-interval (specified under the transmit-interval statement) and minimum-receive-interval statements.
3. You can configure the minimum interval after which the local routing device must receive a reply from a neighbor with which it has established a BFD session. Specify the number of milliseconds using the ["minimum-receive-interval" on page 1574](#) statement.
4. You can specify that an interface be declared down when a certain number of hello packets have not been received from a neighboring router through that interface. Specify the number of hello packets by including the ["multiplier" on page 1582](#) statement.
5. You can configure BFD sessions not to adapt to changing network conditions by including the ["no-adaptation" on page 1592](#) statement. We recommend that you *do not* disable BFD adaptation unless it is preferable to have BFD adaptation disabled in your network.
6. Specify the transmit interval options for `bfd-liveness-detection` statement by including the *transmit-interval* statement. The negotiated transmit interval for a peer is the interval between the sending of BFD packets to peers. The receive interval for a peer is the minimum time that it requires between packets sent from its peer; the receive interval is not negotiated between peers. To determine the transmit interval, each peer compares its configured minimum transmit interval with its peer's minimum receive interval. The larger of the two numbers is accepted as the transmit interval for that peer.

The `transmit-interval` statement specifies how often BFD statements are transmitted and includes the following options:

- `minimum-interval milliseconds`—Specify the minimum interval in milliseconds at which the local routing device transmits hello packets to a neighbor with which it has established a BFD session.
- `threshold milliseconds`—Specify the threshold for the adaptation of the BFD session transmit interval. When the transmit interval adapts to a value greater than the threshold, a single trap and a single system message are sent.

NOTE: The threshold value specified in the `threshold` statement must be greater than the value specified in the `minimum-interval` statement for the `transmit-interval` statement.

7. Specify the BFD version by including the ["version" on page 1698](#) statement. You can set BFD to version 1 or allow BFD to determine what version it needs to be by including the `automatic` option.

RELATED DOCUMENTATION

[bfd-liveness-detection \(Layer 2 VPN and VPLS\) | 1446](#)

clear bfd adaptation

BFD Support for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS

Bidirectional Forwarding Detection (BFD) support for virtual circuit connectivity verification (VCCV) on MX Series devices enables you to configure a control channel for a pseudowire, in addition to the corresponding operations, administration, and management functions to be used over that control channel.

BFD provides a low resource mechanism for the continuous monitoring of the pseudowire data path and for detecting data plane failures. This feature provides support for asynchronous mode BFD for VCCV as described in RFC 5885, *Bidirectional Forwarding Detection (BFD) for the Pseudowire Virtual Circuit Connectivity Verification (VCCV)*. Alternatively, you can use a ping operation to detect pseudowire failures. However, the processing resources required for a ping operation are greater than what is needed for BFD. In addition, BFD is capable of detecting data plane failure faster than a VCCV ping. BFD for pseudowires is supported for Layer 2 circuits (LDP-based), Layer 2 VPNs (BGP-based), and VPLS (LDP-based or BGP-based).

Starting with Release 12.1, Junos OS introduces a distributed model for the BFD for VCCV. Unlike in previous releases where the BFD for VCCV followed a Routing Engine-based implementation, in Release

12.1 and later, the BFD for VCCV follows a distributed implementation over PIC concentrators, such as DPC, FPC, and MPC.

For distributed BFD, you need to configure the lo0 interface with unit 0 and the appropriate family enabled.

NOTE: For the distributed BFD for VCCV to work, you must configure MPLS family (`family mpls`) on the loopback interface.

```
user@router# set interfaces lo0 unit 0 family mpls
```

In Junos OS Release 12.1 and later, the periodic packet management process (ppmd) on the PIC concentrators handles the periodic packet management (send and receive) for BFD for VCCV. This enables Junos OS to create more BFD for VCCV sessions, and to reduce the time taken for error detection. Similarly, the distributed implementation improves the performance of Routing Engines because the Routing Engine resources used for BFD for VCCV implementation become available for Routing Engine-related applications when the BFD for VCCV-related processing moves to the PIC concentrators. The distributed BFD for VCCV implementation also enables the BFD for VCCV sessions to remain across graceful restarts.

RELATED DOCUMENTATION

[Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 234](#)

Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS

Bidirectional Forwarding Detection (BFD) support for virtual circuit connection verification (VCCV) allows you to configure a control channel for a pseudowire, in addition to the corresponding operations and management functions to be used over that control channel. BFD provides a low resource mechanism for the continuous monitoring of the pseudowire data path and for detecting data plane failures.

This feature provides support for asynchronous mode BFD for VCCV as described in RFC 5885, *Bidirectional Forwarding Detection (BFD) for the Pseudowire Virtual Circuit Connectivity Verification (VCCV)*. You can also use a ping operation to detect pseudowire failures. However, the processing resources required for a ping operation are greater than what is needed for BFD. In addition, BFD is capable of detecting data plane failure faster than VCCV ping. BFD for pseudowires is supported for Layer 2 circuits (LDP-based), Layer 2 VPNs (BGP-based), and VPLS (LDP-based or BGP-based).

To configure OAM and BFD for Layer 2 VPNs, include the `oam` statement and sub-statements at the [edit routing-instances *routing-instance-name* protocols l2vpn] hierarchy level:

```
oam {
  bfd-liveness-detection;
  ping-interval ;
  ping-multiplier;
}
```

You can configure many of the same OAM statements for VPLS and Layer 2 circuits:

- To enable OAM for VPLS, configure the `oam` statement and substatements at the [edit routing-instances *routing-instance-name* protocols vpls] hierarchy level and at the [edit routing-instances *routing-instance-name* protocols vpls neighbor *address*] hierarchy level. The `pwe3-control-word` statement configured at the [edit routing-instances *routing-instance-name* protocols l2vpn oam control-channel] hierarchy level is not applicable to VPLS configurations.
- To enable OAM for Layer 2 circuits, configure the `oam` statement and substatements at the [edit protocols l2circuit neighbor *address* interface *interface-name*] hierarchy level. The `control-channel` statement and sub-statements configured at the [edit routing-instances *routing-instance-name* protocols l2vpn oam] hierarchy level do not apply to Layer 2 circuit configurations.

You can use the `show ldp database extensive` command to display information about the VCCV control channel and the `show bfd session extensive` command to display information about BFD for Layer 2 VPNs, Layer 2 circuits, and VPLS.

RELATED DOCUMENTATION

[Junos OS Routing Protocols Library](#)

Connectivity Fault Management Support for EVPN and Layer 2 VPN Overview

IN THIS SECTION

- [Limitations of CFM on layer 2 VPN and EVPNs | 237](#)

The IEEE 802.1ag specification provides for Ethernet connectivity fault management (CFM). The goal of CFM is to monitor an Ethernet network that consists of one or more service instances through the use of CFM protocol messages. CFM partitions the service network into various administrative domains. Each administrative domain is mapped into a maintenance domain. A maintenance association end point (MEP) refers to the boundary of a domain. A MEP generates and responds to CFM protocol messages. You can configure multiple up (PE to PE) MEPs or down (PE to CE) MEPs for a single instance of a maintenance domain identifier and a maintenance association name to monitor services in a VPN.

For Layer 2 VPNs and EVPN networks, you can configure multiple up MEPs for a single combination of maintenance association ID and maintenance domain ID on a routing instance on the logical interfaces (IFLs), regardless of whether the logical interface is composed of physical interfaces on the same device or on different devices. The devices must be in enhanced IP network services mode.

In an EVPN network, the following CFM features are supported:

- Monitoring the connectivity between two provider edge (PE) routers in an active-active or active-standby multihomed configuration.
- Delay measurement and Synthetic Loss measurement. This feature is not supported when multiple MEPs are configured on multiple logical interfaces (IFLs) on the same physical interface (IFD).
- CFM monitoring between PE devices and customer edge (CE) devices. When the customer edge device is not a Juniper Networks device, you can enable CFM monitoring by using either the remote defect indication (RDI) bit or the Interface Status TLV. For more information, see [Understanding CFM Monitoring between CE and PE Devices](#)
- Starting with 18.3R1, Junos OS supports CFM configuration in attachment circuits (AC) on EVPN with ETREE services. The AC is a physical or virtual circuit that connects a CE device to a PE device. You can configure multiple Up MEPs on the MD or MA to monitor each AC between the CE and PE.
- Starting with 18.3R1, Junos OS supports maintenance intermediate points (MIPs) on Attachment Circuits on EVPN with ETREE and EVPN with ELAN services. When you configure MIP using the named bridge domain, all the interfaces will be enabled except for the EVPN core interface. For more information on MIPs, see [Configuring Maintenance Intermediate Points \(MIPs\)](#).
- Starting with 19.2R1, Junos OS supports MEPs and MIPs on ACs in an EVPN-VPWS network. CFM monitoring on EVPN-VPWS supports continuity check messages (CCM), delay measurements, synthetic loss measurement, loopback and link trace messages on single-active multihomed networks.
- Starting in Junos OS Release 20.2R1, Junos OS supports inline performance monitoring on an EVPN network. When inline performance monitoring is enabled, the router offloads performance monitoring packet processing from the CPU to other hardware, thereby decreasing the load on the CPU and allowing an increase in the number of performance monitoring session. Inline performance monitor only applies to delay measurements (DM) and synthetic loss measurements (SLM).

For more information on inline performance monitoring, see [Enabling Inline Mode Of Performance Monitoring To Achieve Maximum Scaling](#).

For more information on configuring delay measurement, see [Configuring Ethernet Frame Delay Measurement Sessions](#).

For more information on configuring synthetic loss measurement, see [Configuring Ethernet Synthetic Loss Measurements](#).

Limitations of CFM on layer 2 VPN and EVPNs

- In a circuit cross-connect (ccc) layer 2 VPN or local switch with MEPs and maintenance intermediate points (MIPs), the counter for link trace messages (LTMs) received on the MAC address of the up MEP does not get incremented when the MIP in the path is configured at the same level. The MIP traps the LTM packet, while the LTR message is sent. This leads to a discrepancy between the number of LTMs received and the number of LTRs sent.
- CFM up MEP on an EVPN network does not support the use of action profiles for interface down. In other words, you can configure an action profile, but no action is taken.
- CFM up MEP is supported on EVPN with ELAN and EVPN with ETREE services.
- CFM monitoring between leaf nodes on EVPN with ETREE services is not supported. CFM monitors MEP session from a leaf node to a root node and from a root node to another root node.
- CFM monitors the AC connectivity from between PE devices, learning about local adjacencies. In EVPN with E-TREE services, performance monitoring on local adjacencies is not supported.

For more information on CFM, see [IEEE 802.1ag OAM Connectivity Fault Management Overview](#).

Release History Table

Release	Description
19.2R1	Starting with 19.2R1, Junos OS supports MEPs and MIPs on ACs in an EVPN-VPWS network.
18.3R1	Starting with 18.3R1, Junos OS supports CFM configuration in attachment circuits (AC) on EVPN with ETREE services.
18.3R1	Starting with 18.3R1, Junos OS supports maintenance intermediate points (MIPs) on Attachment Circuits on EVPN with ETREE and EVPN with ELAN services.

RELATED DOCUMENTATION

[IEEE 802.1ag OAM Connectivity Fault Management Overview](#)

[Creating a Maintenance Domain](#)

[Creating a Maintenance Association](#)

[Configuring a MEP to Generate and Respond to CFM Protocol Messages](#)

[show oam ethernet connectivity-fault-management interfaces](#)

Configuring a MEP to Generate and Respond to CFM Protocol Messages

IN THIS SECTION

- [Configuring a Maintenance Association End Point \(MEP\) | 239](#)
- [Configuring a remote Maintenance Association End Point \(MEP\) | 241](#)

A maintenance association end point (MEP) refers to the boundary of a domain. A MEP generates and responds to connectivity fault management (CFM) protocol messages. You can configure multiple up MEPs for a single combination of maintenance association ID and maintenance domain ID for interfaces belonging to a particular VPLS service or a bridge domain. You can configure multiple down MEPs for a single instance of maintenance domain identifier and maintenance association name to monitor services provided by Virtual Private LAN service (VPLS), bridge domain, circuit cross-connect (CCC), or IPv4 domains.

For layer 2 VPNs routing instances (local switching) and EVPN routing instances, you can also configure multiple up MEPs for a single combination of maintenance association ID and maintenance domain ID on logical interfaces. The logical interface can be configured on different devices or on the same device. To support multiple up MEPs on two IFLs, enhanced IP network services must be configured for the chassis.

You can enable automatic discovery of a MEP. With automatic discovery a MEP is enabled to accept continuity check messages (CCMs) from all remote MEPs of the same maintenance association. If automatic discovery is not enabled, the remote MEPs must be configured. If the remote MEP is not configured, the CCMs from the remote MEP are treated as errors.

Continuity measurement is provided by an existing continuity check protocol. The continuity for every remote MEP is measured as the percentage of time that remote MEP was operationally up over the total administratively enabled time. Here, the operational uptime is the total time during which the CCM adjacency is active for a particular remote MEP and the administrative enabled time is the total time

during which the local MEP is active. You can also restart the continuity measurement by clearing the currently measured operational uptime and the administrative enabled time.

Configuring a Maintenance Association End Point (MEP)

To configure a maintenance association end point:

1. Specify an ID for the MEP at the [edit protocols oam ethernet connectivity-fault-management maintenance-domain *domain-name* maintenance-association *ma-name*]. You can specify any value from 1 through 8191.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name]
user@host# set mep mep-id
```

2. Enable maintenance end point automatic discovery so the MEP can accept continuity check messages (CCMs) from all remote MEPs of the same maintenance association.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name mep mep-id]
user@host# set auto-discovery
```

3. Specify the direction in which the CCM packets are transmitted for the MEP. You can specify up or down. If you specify the direction as up, CCMs are transmitted out of every logical interface that is part of the same bridging or VPLS instance except for the interface configured on the MEP. If you specify the direction as down, CCMs are transmitted only out of the interface configured on the MEP.

NOTE: Ports in the Spanning Tree Protocol (STP) blocking state do not block CFM packets destined to a down MEP. Ports in an STP blocking state without the continuity check protocol configured do block CFM packets.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name mep mep-id]
user@host# set direction down
```

NOTE: Starting with Junos OS Release 12.3, for all interfaces configured on Modular Port Concentrators (MPCs) on MX Series 5G Universal Routing Platforms, you no longer need to configure the no-control-word statement for all Layer 2 VPNs and Layer 2 circuits over which

you are running CFM MEPs. For all other interfaces on MX Series routers and on all other routers and switches, you must continue to configure the `no-control-word` statement at the [edit routing-instances *routing-instance-name* protocols l2vpn] or [edit protocols l2circuit neighbor *neighbor-id* interface *interface-name*] hierarchy level when you configure CFM MEPs. Otherwise, the CFM packets are not transmitted, and the `show oam ethernet connectivity-fault-management mep-database` command does not display any remote MEPs.

4. Specify the interface to which the MEP is attached. It can be a physical interface, logical interface, or trunk interface. On MX Series routers, the MEP can be attached to a specific VLAN of a trunk interface.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name mep mep-id]
user@host# set interface interface-name
```

5. Specify the IEEE 802.1 priority bits that are used by continuity check and link trace messages. You can specify a value from through 7 as the priority.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name mep mep-id]
user@host# set priority number
```

6. Specify the lowest priority defect that generates a fault alarm whenever CFM detects a defect. Possible values include: `all -defects`, `err-xcon`, `mac-rem-err-xcon`, `no-defect`, `rem-err-xcon`, and `xcon`.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name mep mep-id]
user@host# set lowest-priority-defect mac-rem-err-xcon
```

7. Specify the ID of the remote MEP at the [edit protocols oam ethernet connectivity-fault-management maintenance-domain *domain-name* maintenance-association *ma-name* mep *mep-id*]. You can specify any value from 1 through 8191.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-name mep mep-id]
user@host# set remote-mep mep-id
```

SEE ALSO

| [priority](#)

Configuring a remote Maintenance Association End Point (MEP)

To configure a remote maintenance association end point:

1. Configure the remote MEP by specifying the MEP ID at the [edit protocols oam ethernet connectivity-fault-management maintenance-domain *domain-name* maintenance-association *ma-name* mep *mep-id*]. You can specify any value from 1 through 8191.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-namemep mep-id]
user@host# edit remote-mep mep-id
```

2. Specify the name of the action profile to be used for the remote MEP by including the action-profile *profile-name* statement at the [edit protocols oam ethernet connectivity-fault-management maintenance-domain *domain-name* maintenance-association *ma-name* mep *mep-id* remote-mep *remote-mep-id*]. The profile must be defined at the [edit protocols oam ethernet connectivity-fault-management] hierarchy level.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-namemep mep-id remote-mep remote-mep-id]
user@host# set action-profile profile-name
```

3. Configure the remote MEP to detect initial loss of connectivity. By default, the MEP does not generate loss-of-continuity (LOC) defect messages. When you configure the detect-loc statement, a loss-of-continuity (LOC) defect is detected if no continuity check message is received from the remote MEP within a period equal to 3.5 times the continuity check interval configured for the maintenance association. If a LOC defect is detected, a syslog error message is generated.

NOTE: When you configure connectivity-fault management (CFM) along with detect-loc, any action-profile configured to bring down the interface is executed if continuity check message is not received. However, the action-profile is not executed if you have not configured detect-loc and continuity check message is not received.

```
[edit protocols oam ethernet connectivity-fault-management maintenance-domain domain-name
maintenance-association ma-namemep mep-id remote-mep remote-mep-id]
user@host# set detect-loc
```

SEE ALSO

[remote-mep](#)

Release History Table

Release	Description
12.3	Starting with Junos OS Release 12.3, for all interfaces configured on Modular Port Concentrators (MPCs) on MX Series 5G Universal Routing Platforms, you no longer need to configure the no-control-word statement for all Layer 2 VPNs and Layer 2 circuits over which you are running CFM MEPs.

RELATED DOCUMENTATION

action-profile
auto-discovery
connectivity-fault-management
detect-loc
direction
lowest-priority-defect

3

PART

Configuring Group VPNs

[Configuring Group VPNv2](#) | 244

Configuring Group VPNv2

IN THIS CHAPTER

- [Group VPNv2 Overview | 244](#)
- [Configuring Group VPNs in Group VPNv2 on Routing Devices | 270](#)
- [Group VPN on AMS interfaces | 274](#)
- [Use Case for Configuring Group VPNv2 | 275](#)
- [Example: Configuring Group VPNs in Group VPNv2 on Routing Devices | 276](#)

Group VPNv2 Overview

IN THIS SECTION

- [Group VPNv2 Technology Overview | 244](#)
- [Group VPNv2 Implementation Overview | 255](#)

Group VPNv2 Technology Overview

NOTE: Group VPNv2 is the name of the Group VPN technology on MX5, MX10, MX40, MX80, MX104, MX240, MX480, and MX960 routers. Group VPNv2 is different from the Group VPN technology implemented on SRX Security Gateways. The term Group VPN is sometimes used in this document to refer to the technology in general, not to the SRX technology.

For more information about Group VPN on SRX Security Gateway devices, see [Group VPNv2 Overview](#).

This section explains the technological concepts of Group VPNv2.

Understanding Group VPNv2

Group VPN is a trusted group to eliminate point-to-point tunnels and their associated overlay routing. All group members share a common security association (SA), known as a group SA (GSA). The GSA enables group members to decrypt traffic that was encrypted by any other group member. Starting in Junos OS Release 18.2R1, we confirm the Group VPN redundancy with service redundancy protocol [SRD] running on MX routers. MX routers with redundancy between them acts as Group VPN members. For more details on service redundancy protocol see [Service Redundancy Daemon Overview](#).

Starting in Junos OS Release 15.1, Junos OS supports Group VPNv2. Group VPNv2 is a category of VPN that eliminates the need for point-to-point VPN tunnels in a mesh architecture. It is a set of features that are necessary to secure unicast traffic over a private WAN that originates on or flows through a router.

Group VPNv2 introduces the concept of a trusted group to eliminate point-to-point tunnels and their associated overlay routing. All group members share a common security association (SA), also known as a group SA. This enables group members to decrypt traffic that was encrypted by any other group member.

Group VPNv2 provides the following advantages:

- Provides data security and transport authentication, helping to meet security compliance and internal regulation by encrypting all WAN traffic.
- Enables high-scale network meshes and eliminates complex peer-to-peer key management with group encryption keys.
- Reduces the number of endpoint changes that need to be made due to group member change or policy change.
- Maintains network intelligence such as full-mesh connectivity, natural routing path, and quality of service (QoS) in MPLS networks.
- Grants authenticated membership control with a centralized key server.
- Allows encryption and decryption of traffic among all group members defined in the group policy.
- Helps to ensure low latency and jitter by enabling full-time, direct communications between sites, without requiring transport through a central hub.
- Reduces traffic loads on customer premises equipment (CPE) and provider edge (PE) encryption devices by using the core network for traffic replication, avoiding packet replication at each individual peer site.

Group VPNv2 and Standard IPsec VPN


Group VPNv2 is built on standards-based technologies that integrate routing and encryption together in the network. An IPsec security SA is a unidirectional agreement between VPN participants that defines the rules to use for authentication and encryption algorithms, key exchange mechanisms, and secure communications.

Traditional IPsec VPN deployments tackle the problem of securing traffic between gateways in the network by creating an overlay network based on the use of point-to-point tunnels. Traffic carried over these tunnels is normally encrypted and authenticated in order to provide data integrity and confidentiality. Secure group members are managed through the Group Domain of Interpretation protocol (GDOI). The GDOI solution takes a different approach by disassociating the encryption and authentication problem from the transport. By doing this, GDOI-based solutions provide a way to encrypt branch-to-branch communications without the need to configure branch-to-branch tunnels.

With current VPN implementations, the SA is a point-to-point tunnel between two end points. Group VPNv2 extends the IPsec architecture to support SAs that are shared by a group of routers (see [Figure 14 on page 248](#)). A key server distributes keys and policies to all registered and authenticated member routers. By distributing policies from a centralized point and by sharing the same group security

association (the entire group has a single Phase 2 SA) with authenticated group members, key distribution and management are greatly simplified.

Figure 14: Standard IPsec VPN and Group VPNv2



8042234

Group VPNv2 is a client/server architecture. All members have a unique Phase 1 IKE SA with the key server. Hence, if there are n members, there is a total of n Phase 1 IKE SAs. However, the entire group shares a single Phase 2 SA.

In traditional IPsec, the tunnel endpoint addresses are used as a new packet source and destination. The packet is then routed over the IP infrastructure, using the encrypting end point source IP address and the decrypting end point destination IP address. In the case of Group VPN, IPsec-protected data packets preserve the original source and destination addresses of the host in the outer IP header in order to preserve the IP address. This is known as tunnel header preservation. The biggest advantages of tunnel header preservation is the ability to route encrypted packets using the underlying network routing infrastructure.

Table 2: Group VPN vs Traditional Point-to-Point IPsec

Feature	Traditional Point-to-Point IPsec Tunnels	Group VPN
Scalability	IKE/IPsec tunnels between each pair of peers increases management and configuration complexity.	Single SA and key pair used for the entire any-to-any group. Reduced management and configuration complexity.
Any-to-any instant connectivity	Cannot be done to scale due to management and configuration complexity.	Scales well due to the use of GDOI and shared SA within the group.
Overlay routing	Requires overlay routing.	No overlays-native routing.
IP Header Preservation	New IP Header added to original packet results in limited advanced quality of service (QoS). Will work in NAT environments.	Keeps original IP header on IPsec packet. Preserves advanced QoS capabilities. Will not work in NAT environments.

Understanding the GDOI Protocol

The Group Domain of Interpretation (GDOI) protocol described in RFC 6407 is used to distribute a set of cryptographic keys and policies to a group of devices. GDOI is defined as the Internet Security Association Key Management Protocol (ISAKMP) Domain of Interpretation (DOI) for group key management. In a group management model, the GDOI protocol operates between a group member and a group controller or key server (GC/KS) and manages group security associations and group-keys for a set of security participants. The ISAKMP defines two phases of negotiation. GDOI is a Phase 2 protocol

protected by a Phase 1 ISAKMP security association. IKEv1 is specified in RFC 6407 as a Phase 1 protocol.

GDOI introduces two different encryption keys:

- Key encryption key (KEK)—Used to secure the control plane. KEK is the name of the key used by the group members to decrypt rekey messages from the GC/KS. This key is part of the Security Association Key Encryption Key (SAK).
- Traffic encryption key (TEK)—Used to secure the data plane. TEK is the name of the key used by the group members to encrypt or decrypt communication between other group members. This key is part of the Security Association Transport Encryption Key (SA TEK).

As with standard IPsec, all keys have a lifetime and have to be rekeyed. The keys distributed through GDOI are group keys and are used by the entire group.

The group SAs and key management are handled through two types of GDOI exchanges:

- `groupkey-pull`—This exchange allows a member to request SAs and keys shared by the group from the server.

In the pull method, the group member requests the group SA and policy from the key server. This request is protected over the IKE SA.

The `groupkey-pull` is the first exchange in the GDOI protocol and is used for group member registration with the GC/KS. The group member specifies the group with which it wants to register, and the GC/KS sends all necessary group SAs and keys to the group member if the member is authorized to join the group. The complete exchange is secured by a Phase 1 SA (IKEv1 SA), which is established with IKEv1 before the `groupkey-pull` exchange begins. The `groupkey-pull` is part of Phase 2 of the GDOI protocol.

- `groupkey-push`—This exchange is a single rekey message that allows the server to send group SAs and keys to members before existing group SAs expire. Rekey messages are unsolicited messages sent from the server to members.

The `groupkey-push` is the second exchange in the GDOI protocol and is initiated by the GC/KS to all registered members of the group. [Table 3 on page 251](#) shows the payloads that the MX Series group member expects to receive in `groupkey-push` messages.

Table 3: groupkey-push Message Payloads

Payload	Description
group associated policy (GAP)	A GAP payload allows for the distribution of group-wide policy, such as instructions as to when to activate and deactivate SAs. This payload contains values for activation time delay (ATD) and deactivation time delay (DTD) for the traffic encryption key (TEK) as well as IP-Delivery Delayed Detection Protocol window type and window size for the IPsec traffic.
Security Association Transport Encryption Key (SA TEK)	Traffic selectors.
Security Association Key Encryption Key (SAK) (Optional)	The security association (SA) for the key encryption key (KEK). Also known as SA KEK. NOTE: groupkey-push messages that do not include the optional payloads are still valid messages.
traffic encryption key (TEK) (Optional)	Key for encrypting the data traffic between group members.
key encryption key (KEK) (Optional)	Used to protect the TEK.

The groupkey-push exchange is secured by an SA KEK (SAK), which is installed during the groupkey-pull exchange. The groupkey-push is part of Phase 2 of the GDOI protocol.


In some cases, the GC/KS may want to receive group key push acknowledgment messages from group members. The push acknowledgment messages from group members confirms that the member received the message and has taken action on their policy. The GC/KS can also use the acknowledgment to determine which group members are receiving the current group policy and which group members are no longer participating in the group. Starting in Junos OS 19.2R1, Junos OS sends an acknowledgment message with SHA-256 checksum when it receives a groupkey push message with a standard KEK_ACK_REQUESTED value of 9 in the SA KEK payload as defined in RFC 8263 or a KEK_ACK_REQUESTED value of 129 that is used is older key servers.

GDOI Protocol and Group VPNv2

Group VPNv2 is the name of the security technology implemented on the MX5, MX10, MX40, MX240, MX480, MX960 routers from Juniper Networks. Group VPNv2 uses the GDOI protocol (RFC 6407) as a base, in addition to other functionalities.

Group VPNv2 technology is based on the GDOI protocol to handle the most important functionality. This protocol is specified in RFC 6407 and defines an ISAKMP Domain of Interpretation (DOI) to manage group SAs and keys for a group of security participants. Thus, all members of the group share identical information to encrypt and decrypt traffic among each other. The creation, management, and distribution of group SAs and group keys are centralized and performed by the GC/KS. [Figure 15 on page 252](#) provides a brief overview of the Group VPNv2 functionality using GDOI.


Figure 15: Group VPNv2 Using GDOI



The group members use the Encapsulating Security Payload (ESP) protocol in tunnel mode to secure the traffic. However, in Group VPN the tunnel mode is modified. Because there is no direct association between the group members, it is not necessary to use special IP addresses in the outer IP header (that is, IP addresses of IPsec gateways). Every group member can decrypt the traffic of every other group member. Thus, the inner IP-Header is copied to the outer IP-Header, and the underlying routing

infrastructure and QoS infrastructure can be used. This feature is called Header Preservation and is shown in [Figure 16 on page 253](#).

Figure 16: Header Preservation



To get group SAs and group keys, the group member must register with the GC/KS for a specific group. The result is an IKEv1 SA, which is only needed to secure the registration process. After the registration, the group member has all the information to communicate with the other group members (SA TEK), as well as the information to successfully decrypt the rekeying messages (SAK). The GC/KS sends out rekeying messages before either the SA TEK or SAK lifetime expires. It is also possible to send an SA TEK update as well as a SAK update in the same rekey message. The IKEv1 SA is no longer needed and is deleted after the lifetime expires (no IKEv1-rekeying).

Group VPNv2 Traffic

Group VPNv2 traffic includes:

- Control-plane-traffic—Traffic from the group members to the GC/KS in the Group VPNv2 deployment with the GDOI protocol only.
- Data-plane-traffic—Traffic between the group members in the Group VPNv2 deployment with the ESP protocol only which is already known from IPsec.

Group Security Association

Unlike traditional IPsec encryption solutions, Group VPN uses the concept of group security association. A group SA is similar to an SA in terms of functionality. Group SAs are shared among all group members of a common GDOI group. All members in the Group VPN group can communicate with each other using a common encryption policy and a shared group SA. With a common encryption policy and a shared group SA, there is no need to negotiate IPsec between group members. This reduces the resource load on the group members. Traditional IPsec scalability issues (number of tunnels and associated SAs) do not apply to Group VPN group members.

Group Controller/Key Server

A group controller or key server (GC/KS) is a device used for creating and maintaining the Group VPNv2 control plane. It is responsible for creation and distribution of group SAs and group keys. All information the group members need to communicate with other group members is provided by the GC/KS. All encryption policies, such as interesting traffic, encryption protocols, security association, rekey timers, and so on, are centrally defined on the GC/KS and are pushed down to all group members at registration time. Group members authenticate with the GC/KS using IKE Phase 1 and then download the encryption policies and keys required for Group VPN operation. The GC/KS is also responsible for refreshing and distributing the keys.

NOTE: The GC/KS functionality is not supported on MX Series routers. The MX Series routers that are configured as group members can connect with Cisco GC/KS only. There is no support for MX Series group members to interact with the Juniper Networks SRX Series acting as a GC. See [Table 6 on page 269](#) for compatibility between the various types of group members and GC/KSs.

Group Member

A group member is an IPsec endpoint device used for the traffic encryption process and is responsible for the actual encryption and decryption of data traffic. A group member is configured with IKE Phase 1 parameters and GC/KS information. Encryption policies are defined centrally on the GC/KS and downloaded to the group member at the time of successful registration. Each group member then determines whether incoming and outgoing traffic should be decrypted or encrypted (using its SA) based on its group membership.

From a functionality point of view, a group member is similar to an IPsec gateway. However, the SAs in normal IPsec exist between two IPsec gateways. In GDOI, the group member registers with the GC/KS in order to participate in the Group VPN. During registration, the group member provides the group ID to the GC/KS to get the respective policies, SAs, and keys needed for this group. Rekeying is accomplished by the group members through the `groupkey-pull` method (re-registration) or by the GC/KS through the `groupkey-push` method.

Anti-Replay Protection for Group VPNv2 Traffic

Since Group VPN communication is essentially any-to-any communication over the same shared security association, the use of sequence numbers for anti-replay protection does not work. Because of this, Junos OS supports an IETF draft specification for a time-based anti-replay mechanism, draft-weis-delay-detection-01. It is available at <http://tools.ietf.org/html/draft-weis-delay-detection-01>.

To implement this feature, MX Series member routers make use of a new IP Delivery Delay Detection Protocol time-stamp header within the packet. See ["Implementing IP Delivery Delay Detection Protocol \(Time-Based Anti-Replay Protection\)" on page 262](#) for details.

Partial Fail-Open on MX Series Member Routers

Group members in a Group VPN rely on the GC/KS to generate keying material for the shared SA. Therefore, connectivity between the group members and GC/KSs is required to initially protect traffic and to continually protect traffic over rekey events. In the event of communication failure between the group member and the GC/KS, the default behavior of the group members is to stop forwarding traffic. This is known as fail-closed.

A nondefault configuration option is available to permit some specifically defined traffic to flow through the group member without being encrypted until such time as the member is able to contact the GC/KS and retrieve the active SA. This is known as partial fail-open.

The partial fail-open feature requires a policy configuration option that creates a rule on the applicable MX Series group member for a particular Group VPNv2 defined by source and destination addresses. This fail-open rule is active only when group SA is in disabled state because of connectivity failure with the key server. Traffic that would normally pass through the Group VPN but does not match the fail-open rule is dropped. More than one fail-open rule can be defined for the Group VPN object. If no fail-open rules are configured, then the fail-open feature is disabled.

Group VPNv2 Implementation Overview

This section explains the Juniper Networks solution for implementing Group VPNv2.

Enabling Group VPNv2

A service set is used to enable Group VPNv2 on a particular interface on applicable MX Series routers.

Configuring the Service Set

Group VPNv2 is configured inside a service set using the `ipsec-group-vpn` statement at the `[edit services service-set service-set-name]` hierarchy level.

Sample Service Set Configuration

```
[edit services]
service-set service-set-name {
  interface-service {
    service-interface service-interface-name;
  }
}
ipsec-group-vpn vpn-name;
```

NOTE:

- Only one group member can be configured per service set.
- Next-hop style service set is not supported with Group VPNv2.

Applying the Service Set

A service set is applied at the interface level.

Sample Applying Service Set Configuration

```
[edit interfaces]
interface-name {
  unit 0 {
    family inet {
      service {
        input {
          service-set service-set-name;
        }
        output {
          service-set service-set-name;
        }
      }
      address 10.0.30.2/30;
    }
  }
}
```

Packet Steering

The interface-style service set configuration is used to steer traffic from the Packet Forwarding Engine to the PIC. Packets received on an interface with a service set pointing to the Group VPNv2 object are forwarded to the PIC by being injected into the corresponding service interface.

Registering a Group Member

The group member registration to the server starts when the `ipsec-group-vpn` statement is configured for a service set and the service interface is up. When the service interface goes down, all group SAs associated with this interface are cleared, and no registration is triggered for these Group VPNs until the interface comes up.

Group member registration involves establishing IKE SA with the GC/KS followed by a `groupkey-pull` exchange to download the SAs and the traffic keys for the specified group identifier.

NOTE: Junos OS does not support traffic-based SA negotiation triggering for Group VPNs in Group VPNv2.

Rekeying a Group Member (groupkey-push Method)

The GC/KS will send out a unicast `groupkey-push` message to registered group members in order to:

- Send new key encryption keys (KEKs) or traffic encryption keys (TEKs).

The push messages can contain all or only some of the payload elements shown in [Table 3 on page 251](#). When the GAP payload contains both old SAs and new replacement SAs, the group member router will apply the ATD and DTD values as a normal rekey by means of push. If there is no ATD value in the update, the member router installs the new SAs immediately. If there is no DTD value, the old SAs will remain in place until their expiration.

- Update group associated policy (GAP) for an existing SA.

A GC/KS can send a unicast push message to update the configuration to group members at any time. The GAP payload can include configuration changes to the IP Delivery Delay Detection Protocol, encryption algorithm, lifetime, and so on. The updated configuration is either applied immediately or with a delay. ATD and DTD values are used to achieve the timing for the activation of the new TEK and deletion of the existing TEK, respectively. If the existing TEK lifetime has to be reduced, then the DTD value is set accordingly in the push message. The new TEK in the push message is activated based on the ATD value in the payload.

- Send delete key notifications for TEK or KEK.

The GC/KS can send the optional delete notification payload in the push message for deleting keys and SAs on the member. The push message contains the protocol ID that indicates whether the delete notification is for TEK or KEK. The group member router deletes the key based on the group ID and SPI value contained in the payload. Deleting a specific TEK or KEK can be done with a delay value specified in the DTD attribute. If the delay value is 0, and the payload contains a specific SPI, then the matching TEK or KEK is deleted immediately. If all the TEKs or KEKs (or both) need to be deleted in the group, then the SPI value is set to 0 for the corresponding protocol ID in the payload.

- Remove a member router from the Group VPN in Group VPNv2.

The push messages are used to allow the GC/KS to delete members from the Group VPN. In one case, the GC/KS sends a rekey message with only the old SAs and a smaller DTD value. The group member router installs the new, smaller DTD value. Since it did not receive new SA keys, the member router tries to re-register using the `groupkey-pull` method. This re-registration attempt is rejected by the GC/KS, thus deleting the member from the Group VPN. In the second case, the GC/KS sends a delete payload for the SPI of the old SA. The group member router deletes the SA immediately and attempts to re-register using the `groupkey-pull` method. This re-registration attempt is rejected by the GC/KS, thus deleting the member from the Group VPN.

Registered MX Series group members send a unicast PUSH ACK message back to the GC/KS to acknowledge the receipt of the original push message.

Rekeying a Group Member (groupkey-pull Method)

For group member rekeying, using the groupkey-pull method, the group members typically re-register with the GC/KS when there is between 7 percent and 5 percent remaining in the existing TEK or KEK soft lifetime. If the existing IKE SA is available, it is used in the pull message. After the GC/KS responds with a new key, both the old key and the new key can be used for decryption. However, the new key is not used for encryption until 30 seconds of lifetime of the old key is remaining. If the existing IKE SA is not available, the pull message results in new IKE negotiations between the group member and the GC/KS.


Upon receiving the pull message regarding a specific Group VPN from the group member, the GC/KS responds with all the TEKs and the KEK for that group.

If any existing SA is not included in the response from the GC/KS, then the missing SAs are deleted by the group member.

Taking as an example, the GC/KS is configured with a lifetime of 3600 seconds and is connected to one group member without retransmit. Based on the server configuration, the GC/KS generates a new key when 10 percent of the lifetime is remaining. The group member, however, re-registers with the GC/KS when 5 percent to 7 percent of the lifetime is remaining.

Figure 17 on page 259 represents the rekeying process between the GC/KS and the group member.

Figure 17: Group Member Rekeying



Authenticating a Group Member

Junos OS does not provide public key infrastructure (PKI) support for Group VPN in Group VPNv2. As a result, pre-shared keys are used for group member authentication.

Fragmenting Group VPNv2 Traffic

Because of the header preservation functionality and the usage of the underlying routing infrastructure, it is necessary to fragment the packets before encryption occurs (if it cannot be prevented).

Hence, pre-fragmentation is supported and is recommended for all deployments.

To avoid post-fragmentation, set the `clear`, `set`, and `copy` options for the DF bit in the Group VPNv2 configuration.

Based on this flag setting, the IPsec header has either the `df-bit` set to `clear`, `set`, or `copy` from the inner packet.

NOTE: The DF bit has the `clear` option set as default.

Sample DF Bit Configuration

```
[edit]
security {
  group-vpn {
    member {
      ipsec {
        vpn group-vpn-name {
          df-bit clear;
        }
      }
    }
  }
}
```

Encrypting Group VPNv2 Traffic

Group members encrypt traffic based on the group SAs and keys provided by the GC/KS. The Group VPNv2 encryption path is as follows:

1. Packet received by the Packet Forwarding Engine is checked against a flow match. If a match is found, the packet is further processed and transmitted.
2. If a match is not found, a rule lookup is performed. If a match is found, a flow is created, and the packet is further processed and transmitted.

3. If the rule lookup fails, the packet is dropped.

NOTE: Group SA is not triggered during packet processing.

Decrypting Group VPNv2 Traffic

After registration is successful and Group VPN SAs are installed, an ESP session is created. Group VPNv2 creates the ESP session with a zero source and destination IP. Because the ESP session is already created at SA installation, packets are expected to match the existing ESP session.

The Group VPNv2 decryption path is as follows:

1. Packet received by the Packet Forwarding Engine undergoes a fragmentation check. If the packet is fragmented, it is assembled for further processing.
2. After packet assembling or if the packet is not fragmented, a zero source and destination IP is used in the 5-tuple decrypt flow lookup. If a match is found, the packet is further processed and transmitted.
3. If the decrypt flow lookup fails, the packet is checked against an SPI flow with zero source and destination IP.
4. If the SPI flow lookup fails, the packet is dropped.
5. If an SPI flow match is found, a decrypt flow is created to avoid the SPI flow lookup for subsequent packets.

Configuring a Routing Instance for Group VPNv2

Routing instances are supported for both control and data traffic. To enable routing instance support on control plane traffic for a group member to reach the GC/KS in a given VRF routing instance, add the routing-instance statement at the [edit security group-vpn member ike gateway *gateway-name* local-address *address*] hierarchy level.

No additional CLI is required to support a routing instance for data-plane packets, as it is determined based on the media interface on which the service set is applied.

Establishing Multiple Groups, Policies, and SAs

Junos OS provides support for one Group VPN per service set in Group VPNv2. However, multiple service sets can be created to support multiple groups in a routing instance. Multiple SAs can be configured per group. However, multiple policies for the same traffic key/SPI is not supported. If the server sends two policies for the same TEK, then they must be paired to be accepted, for instance, A-B

and B-A, where A and B are IP addresses or subnets. If multiple unpaired policies for a given TEK are received, registration fails and a system log message is generated.

Connecting with Multiple Cooperative GC/KSs

For a group member to work with a GC/KS in the cooperative mode, the configuration is extended to allow a maximum of four servers in the server list.

During rekeying when using the groupkey-pull method, the group member tries to connect to the GC/KS. When the connection to the GC/KS fails, the group member tries to reconnect to the GC/KS. After three retries with an interval of 10 seconds, if the connection to the GC/KS is not restored, the group member tries to establish a connection with the next available server on the server list. This process is repeated until the group member connects to a GC/KS. During this time, the unexpired GDOI SAs on the group members are not cleaned up, so Group VPN traffic is not affected. The time gap between rekeying and hard lifetime expiry provides sufficient time for the group members to connect to the next available server, in such cases.

Implementing IP Delivery Delay Detection Protocol (Time-Based Anti-Replay Protection)

There is no configuration needed to implement the IP Delivery Delay Detection Protocol. MX Series group members get the replay window size to use as a part of the GAP payload in push or pull messages from the key server. If the received window size is 0, time-based anti-replay protection is disabled.

If IP Delivery Delay Detection Protocol is enabled, the sender adds its current timestamp and encrypts the packet. The receiver decrypts the packet and compares its current time with the timestamp in the packet. Packets that fall outside of the window size are dropped. Because of this, all group members should have their clocks synchronized using Network Time Protocol (NTP).

IP Delivery Delay Detection Protocol times are measured in seconds. See [IP Delivery Delay Detection Protocol-draft-weis-delay-detection-01](#) for more information.

NOTE: All latency issues associated with NTP also apply within IP Delivery Delay Detection Protocol. Thus, a minimum window size of 1 second is recommended.

Changing Group VPNv2 Configuration

Most Group VPNv2 configuration changes result in deleting both existing SAs and re-registration. This triggers both phase 1 and SA download with new traffic keys.

Bypassing Group VPNv2 Configuration

If certain traffic like a routing protocol needs to bypass a Group VPN in Group VPNv2, a service filter needs to be configured on the interface on which the service set is applied. Packets matching the service filter do not come to the PIC for service processing and are directly forwarded to the Routing Engine.

Sample Service Set Filter Configuration

```
[edit interfaces]
interface-name {
  unit 0 {
    family inet {
      service {
        input {
          service-set service-set-name service-filter filter-name;
        }
        output {
          service-set service-set-name service-filter filter-name;
        }
      }
    }
  }
}
```

Implementing Partial Fail-open on MX Series Member Routers

By default, packets are dropped if a group member router is unable to get SAs from the GC/KS due to loss of connectivity. If you want to allow some traffic to pass unencrypted in the event of a communication failure between the group member and the GC/KS, you must configure a fail-open rule at the `[edit security group-vpn member ipsec vpn vpn-name]` hierarchy level.

Fail-open rules will be applied to the traffic only in the event of loss of server connectivity. Fail-open rules will be deactivated once connectivity is restored and keys are received from the GC/KS.

Sample Fail-Open Rule Configuration

```
[edit security group-vpn member ipsec vpn vpn-name]
fail-open {
  rule rule-name{
    source-address source-ip-address
    destination-address destination-ip-address}
  }
}
```

A maximum of 10 fail-open rules can be configured for any given group.

Supported GDOI IPsec Parameters

Every GDOI group has a unique ID. It is used as a common base between GC/KS and the group member to communicate about group SAs and group keys.

During the registration process, the GC/KS sends Security Association Transport Encryption Keys (SA TEKs) to the group members. All parameters regarding the whole group security policy are configured on the GC/KS. The SA TEK is used by the group members to protect the traffic exchanged among each other. [Table 4 on page 264](#) shows the parameters of the SA TEK.

Table 4: SA TEK Parameters

Parameters	Supported Values
Encryption	<ul style="list-style-type: none">• DES-CBC• 3DES-CBC• AES-CBC 128• AES-CBC 192• AES-CBC 256

Table 4: SA TEK Parameters *(Continued)*

Parameters	Supported Values
Integrity	<ul style="list-style-type: none"> • HMAC-MD5-96 • HMAC-SHA1-96 • HMAC-SHA-256-128
Lifetime	Any supported value

Besides the cryptographic algorithms, the traffic, which should be encrypted by the group members, is part of the SA TEK policy (traffic selector).

The following statements can be used on a Juniper Networks group member. Thus, the addresses have to be specified under the IKE hierarchy level. The enumeration is also prioritized. Thus, in the following example configuration, KS1 is contacted before KS2.

Sample GDOI IPsec Parameters Configuration

```
[edit security]
group-vpn {
  member {
    ike {
      gateway gateway-name {
        ike-policy policy-name;
        server-address <IP_KS1> <IP_KS2> <IP_KS3> <IP_KS4>;
        local-address <IP_GM> routing-instance routing-instance-name;
      }
    }
    ipsec {
      vpn vpn-group-name {
        ike-gateway gateway-name;
        fail-open {
          rule rule-name {
            source-address 198.51.100.1/24
            destination-address 192.0.2.1/24
          }
        }
        group group-ID;
        match-direction output;
      }
    }
  }
}
```

Supported GDOI IKEv1 Parameters

The group members use only IKEv1 during the registration process in the Group VPNv2 environment. [Table 5 on page 267](#) provides an overview of the defined parameters of the IKEv1 SA.

Table 5: IKEv1 SA Parameters of Group Member

Parameter	Supported Values
Encryption	<ul style="list-style-type: none"> • DES-CBC • 3DES-CBC • AES-CBC 128 • AES-CBC 192 • AES-CBC 256
Authentication	Pre-shared key (minimum 20 signs)
Integrity	<ul style="list-style-type: none"> • MD5 • SHA1 • SHA256
Diffie-Hellman Group	<ul style="list-style-type: none"> • Group 1 • Group 2 • Group 5 • Group 14
Lifetime	Any supported value

The above-mentioned IKEv1 standards are configured as follows:

Sample IKEv1 Configuration

```
[edit security]
group-vpn {
  member {
    ike {
      proposal proposal-name {
        authentication-algorithm sha1;
        authentication-method pre-shared-keys;
        dh-group group5;
        encryption-algorithm aes-128-cbc;
        lifetime-seconds 3600;
      }
      policy policy-name {
        mode main;
        proposals proposal-name;
        pre-shared-key ascii-text "SECRET DATA";
      }
    }
  }
}
```

Applying Dynamic Policies

The `input` and `output` options under the `ipsec-group-vpn` statement specify if the dynamic policies received from the server are used when the interface on which the service set is applied is the incoming or outgoing interface. This provides flexibility to specify different rules in the incoming and outgoing directions.

Supporting TOS and DSCP

Type of service (TOS) and DiffServ Code Points (DSCP) bits are copied from the inner packet to the ESP packet.

Interoperability of Group Members

Cisco's implementation of GDOI is called Group Encryption Transport (GET) VPN. While Group VPNv2 in Junos OS and Cisco's GET VPN are both based on RFC 6407, *The Group Domain of Interpretation*, there are some implementation differences that you need to be aware of when deploying GDOI in a

networking environment that includes both Juniper Networks security and routing devices and Cisco routers. For more information, see the current Junos OS release notes.

Group VPNv2 interoperability is as follows:

- Junos OS provides interoperability support with Cisco IOS GC/KS support.
- Junos OS does not provide support for Group VPNv2 interoperability with the SRX Series Group VPN server.

Table 6: Group VPNv2 Interoperability

Group Member	SRX Group Member	MX Group VPNv2 Member	Cisco Group Member	SRX GC	SRX KS	Cisco GC/KS
MX Group VPNv2 Member	No	Yes	Yes	No	Yes	Yes
SRX Group Member	Yes	No	No	Yes	Yes	Yes

Junos OS does not support the deny policy used on a Cisco GC/SK server to add an exception to the group policy. As a workaround, this can be done by configuring firewall rules on an MX Series group member. Also, Junos OS group members can work with the deny policy by not failing the negotiation and simply ignoring the contents. This allows system administrators to easily manage networks where both Cisco group members and Junos OS group members co-exist.

Group VPNv2 Limitations

Junos OS Group VPNv2 does not provide support for the following:

- Multicast push messages
- Multicast traffic
- GDOI SNMP MIBs
- Protocol and port in the policies sent by the server. The group member honors only the IP address/subnet specified in the policy.
- Multiple unpaired policies for the same traffic key/SPI
- Overlapping of both local and remote IP across routing instances in an IKE gateway configuration

- Overlapping Group VPNv2 policies that can result in mismatched SAs
- IPv6 for control and data traffic
- Co-existence of IPsec and Group VPN on the same service set
- Co-existence of services like NAT and ALG on the same service set. NAT and Group VPN can co-exist on different service sets. However, they cannot co-exist on the same service set.
- Site To Site (S2S) VPN and dynamic end point (DEP) VPN can co-exist with Group VPN on different service sets. However, they cannot co-exist on the same service set.
- Multiple groups on same service set
- Group member support with SRX Series GC/KS
- Group member support with SRX Series group member
- Logical Key Hierarchy (LKH)
- Graceful restart
- High availability
- Unified ISSU
- PKI support for authentication

Release History Table

Release	Description
15.1	Starting in Junos OS Release 15.1, Junos OS supports Group VPNv2.

RELATED DOCUMENTATION

- Example: Configuring Group VPNs in Group VPNv2 on Routing Devices | 276
- Service Redundancy Daemon Overview

Configuring Group VPNs in Group VPNv2 on Routing Devices

You can configure an MX Series router with MS-MIC-16G and MS-MPC-PIC line cards to provide the Group VPNv2 member functionality support with one or more Cisco group controllers or key servers

(GC/KSs). The group members can connect to a maximum of four Cisco GC/KSs with minimum interoperability with the cooperative servers.

The Group VPNv2 feature also provides system logging support for the Group VPNv2 functionality, and routing instance support for both control and data traffic.

Before you begin:

1. Configure the routers for network communication.
2. Configure the Cisco GC/KS.
3. Configure the group member device interfaces.
4. Configure a static route to reach the group server.

To configure a Group VPNv2 member, complete the following tasks:

1. In configuration mode, go to the following hierarchy level:

```
[edit]
user@GM1# edit security
```

2. Define the IKE proposal.

```
[edit security]
user@GM1# set group-vpn member ike proposal proposal-name
```

3. Configure the Phase 1 SA for the IKE proposal.

```
[edit security]
user@GM1# set group-vpn member ike proposal proposal-name authentication-method pre-shared-keys
user@GM1# set group-vpn member ike proposal proposal-name dh-group group
user@GM1# set group-vpn member ike proposal proposal-name authentication-algorithm sha1
user@GM1# set group-vpn member ike proposal proposal-name encryption-algorithm 3des-cbc
```

4. Define the IKE policy.

```
[edit security]
user@GM1# set group-vpn member ike policy policy-name mode main
user@GM1# set group-vpn member ike policy policy-name proposals proposal-name
user@GM1# set group-vpn member ike policy policy-name pre-shared-key ascii-text text
```

5. Set the remote gateways for the IKE gateway group.

```
[edit security]
user@GM1# set group-vpn member ike gateway gateway-group-name ike-policy policy-name
user@GM1# set group-vpn member ike gateway gateway-group-name server-address server-IP-address
user@GM1# set group-vpn member ike gateway gateway-group-name local-address server-facing-interface-IP-address
```

NOTE: To configure a group member to connect to multiple group servers, add the IP address of all the servers to the remote IKE gateway group configuration.

For example,

```
[edit security]
user@GM1# set group-vpn member ike gateway gw-group1 server-address 203.0.113.0
user@GM1# set group-vpn member ike gateway gw-group1 server-address 203.0.113.1
```

6. Configure the group identifier and IKE gateway for the remote gateway group.

```
[edit security]
user@GM1# set group-vpn member ipsec vpn vpn-name ike-gateway gateway-group-name
user@GM1# set group-vpn member ipsec vpn vpn-name group group-ID
user@GM1# set group-vpn member ipsec vpn vpn-name match-direction output
```

7. In configuration mode, go to the following hierarchy level:

```
[edit]
user@GM1# edit services
```

8. Configure the service set for the remote gateway group.

```
[edit services]
user@GM1# set service-set service-set-name interface-service service-interface service-interface
user@GM1# set service-set service-set-name ipsec-group-vpn vpn-name
```

NOTE: The service set has to be applied on the interface connecting to the other group member.

For example:

```
[edit interfaces]
user@GM1# set xe-0/3/1 unit 1 family inet service input service-set gvpn-service-set
user@GM1# set xe-0/3/1 unit 1 family inet service output service-set gvpn-service-set
```

9. Verify and commit the configuration.

For example:

```
[edit security]
user@GM1# set group-vpn member ike proposal ike-proposal authentication-method pre-shared-
keys
user@GM1# set group-vpn member ike proposal ike-proposal dh-group group2
user@GM1# set group-vpn member ike proposal ike-proposal authentication-algorithm sha1
user@GM1# set group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc
user@GM1# set group-vpn member ike policy ike-policy mode main
user@GM1# set group-vpn member ike policy ike-policy proposals ike-proposal
user@GM1# set group-vpn member ike policy ike-policy pre-shared-key ascii-text ""$9$QEni3/
t1RSM87u087-V4oz36"
user@GM1# set group-vpn member ike gateway gw-group1 ike-policy ike-policy
user@GM1# set group-vpn member ike gateway gw-group1 server-address 203.0.113.0
user@GM1# set group-vpn member ike gateway gw-group1 local-address 192.0.2.0
user@GM1# set group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
user@GM1# set group-vpn member ipsec vpn vpn-group1 group 1
user@GM1# set group-vpn member ipsec vpn vpn-group1 match-direction output
```

```
[edit services]
user@GM1# set service-set gvpn-service-set interface-service service-interface ms-4/0/0.1
user@GM1# set service-set gvpn-service-set ipsec-group-vpn vpn-group1
```

```
[edit]
user@GM1# commit
commit complete
```

RELATED DOCUMENTATION

[Example: Configuring Group VPNs in Group VPNv2 on Routing Devices](#) | 276

Group VPN on AMS interfaces

Starting with Junos OS Release 18.4R1, Junos OS supports load balancing Group VPN services on Aggregated multiservices interface (AMS) interfaces. AMS is a bundle of multiple service interfaces combined together that functions as a single interface. Group VPN configured on AMS leverages the load balancing option in AMS to distribute traffic over the member interfaces that comprise the AMS interface. The Group VPN load balanced traffic follows the behavior defined by the hash key in the service set of the AMS interface.

Group VPN on AMS interface has the following limitation:

- Group VPN on AMS only supports load balancing.
- High Available is not supported on the AMS interface on Group VPNs.
- AMS is only supported on MX Series routers with more than one service PIC.

The following output shows a sample service set configuration on an AMS interface.

```
user@router1# show services service-set ss-gvpn400
interface-service {
  service-interface ams1.1;
  load-balancing-options {
    hash-keys {
      ingress-key [ source-ip protocol destination-ip ];
      egress-key [ destination-ip protocol source-ip ];
    }
  }
}
ipsec-group-vpn gvpn400;
```

For more information on configuring AMS, see [Configuring Aggregated Multiservices Interfaces](#).

Use Case for Configuring Group VPNv2

NOTE: Group VPNv2 is the name of the Group VPN technology on MX5, MX10, MX40, MX80, MX104, MX240, MX480, and MX960 routers. Group VPNv2 is different from the Group VPN technology implemented on SRX Security Gateways. The term Group VPN is sometimes used in this document to refer to the technology in general, not to the SRX technology.

Today's networks support critical applications such as distributed computing, voice, and video over IP, which all require real-time branch-to-branch communication. With the increasing use of applications that are highly sensitive to latency and other delays, enterprise networks are tending toward meshed configurations where remote sites are directly connected to each other rather than through a central site. To provide the required infrastructure for supporting such applications and technologies, large service provider and enterprise networks implement any-to-any connectivity through IP VPNs and MPLS networks.

Although IP VPN and MPLS services separate enterprise traffic from the public Internet to provide security, there is an increasing need for enterprises to also encrypt private WANs that are built using service provider networks such as BGP over MPLS. In recent years, government regulations, such as the Health Insurance Portability and Accountability Act (HIPAA), Gramm-Leach-Bliley Act (GLBA), and Payment Card Industry Data Security Standard (PCI DSS), mandate encryption even over private IP networks.

Hub and spoke VPNs solve the problem of secure communication for enterprise WANs over the public Internet. For private IP and MPLS networks, Group VPNv2 addresses the above-mentioned issues across multiple sites using a group IPsec security paradigm.

Group VPNv2 on certain MX Series routers with MS-MIC-16G or MS-MPC-PIC line cards provides tunnel-less any-to-any encryption between devices in a private IP and MPLS network. Each device is a group member, using the same IPsec security association (SA) pair and keys provided by one or more Cisco Group Controllers or Key Servers (GC/KS).

Group VPNv2 is manageable and scalable. It provides any-to-any encrypted communication by replacing statically configured pair-wise IKE connections per peer with a dynamic group key management system. By providing encryption across private IP and MPLS networks, the Group VPNv2 implementation simplifies the management of secure branch-to-branch communication.

In addition to simplified key management, reduced latency, and improved any-to-any connectivity capabilities, Group VPNv2 also provides encryption for all WAN traffic, providing security compliance for internal governance and regulations.

Configuring Group VPNv2 provides an innovative and scalable solution to protect enterprise traffic as it passes through the meshed private WAN. Group VPNv2 optimizes network utilization and provides

increased revenue by maintaining full-mesh connectivity and routing paths with existing MPLS backbones, eliminating the management and performance cost of a traditional full-mesh VPN network.

RELATED DOCUMENTATION

[Group VPNv2 Overview | 244](#)

[Example: Configuring Group VPNs in Group VPNv2 on Routing Devices | 276](#)

Example: Configuring Group VPNs in Group VPNv2 on Routing Devices

IN THIS SECTION

- [Requirements | 276](#)
- [Overview | 277](#)
- [Configuration | 279](#)
- [Verification | 291](#)
- [Troubleshooting | 294](#)

NOTE: Group VPNv2 is the name of the Group VPN technology on MX5, MX10, MX40, MX80, MX104, MX240, MX480, and MX960 routers. Group VPNv2 is different from the Group VPN technology implemented on SRX Security Gateways. The term Group VPN is sometimes used in this document to refer to the technology in general, not to the SRX technology.

This example shows how to configure Group VPNs in Group VPNv2 to extend the IP Security (IPsec) architecture to support group security associations (GSAs) that are shared by a group of routers.

Requirements

This example uses the following hardware and software components:

- Two MX Series 5G Universal Routing Platforms with MS-MIC-16G or MS-MPC-PIC line cards
- Reachability to one or more Cisco Group Controllers or Key Servers (GC/KS)
- Junos OS Release 14.1 or later running on the MX Series routers

Before you begin:

1. Configure the routers for network communication.
2. Configure the Cisco GC/KS.
3. Configure the group member device interfaces.

Overview

IN THIS SECTION

- [Topology | 277](#)

Starting with Junos OS Release 14.1, MX Series routers with MS-MIC-16G and MS-MPC-PIC line cards provide the Group VPNv2 member functionality support with one or more Cisco Group Controllers or Key Servers (GC/KS). The group members can connect to a maximum of four Cisco GC/KSs with minimum interoperability with the cooperative servers.

This feature also provides system logging support for Group VPNv2 functionality, and routing instance support for both control and data traffic.

Topology

In [Figure 18 on page 278](#), a Group VPN is configured between a Cisco group server, GC/KS – and two group members, GM1 and GM2. The group members are connected to host devices.

In [Figure 19 on page 278](#), a Group VPN is configured between GM1 and GM2, and GC/KS1 and GC/KS2 are the primary and secondary group servers, respectively.

Figure 18: Group VPN with Single GC/KS





Figure 19: Group VPN with Multiple GC/KS



Configuration

IN THIS SECTION

- [Configuring Group VPNv2 with a Single GC/KS | 279](#)
- [Configuring Group VPNv2 with Multiple GC/KS | 285](#)

Configuring Group VPNv2 with a Single GC/KS

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then commit the configuration.

GM1

```
set interfaces ms-4/0/0 unit 1 family inet
set interfaces ge-0/1/9 vlan-tagging
set interfaces ge-0/1/9 unit 1 vlan-id 11
set interfaces ge-0/1/9 unit 1 family inet address 198.51.100.0/24
set interfaces xe-0/3/1 vlan-tagging
set interfaces xe-0/3/1 unit 1 vlan-id 1
set interfaces xe-0/3/1 unit 1 family inet service input service-set gvpn-service-set
set interfaces xe-0/3/1 unit 1 family inet service output service-set gvpn-service-set
set interfaces xe-0/3/1 unit 1 family inet address 10.0.1.2/24
set interfaces xe-4/3/1 unit 0 family inet address 203.0.113.1/24
set routing-options static route 192.0.2.0/24 next-hop 198.51.100.2
set routing-options static route 203.0.113.0/24 next-hop 10.0.1.1
set security group-vpn member ike proposal ike-proposal authentication-method pre-shared-keys
set security group-vpn member ike proposal ike-proposal dh-group group2
set security group-vpn member ike proposal ike-proposal authentication-algorithm sha1
set security group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc
set security group-vpn member ike policy ike-policy mode main
set security group-vpn member ike policy ike-policy proposals ike-proposal
set security group-vpn member ike policy ike-policy pre-shared-key ascii-text ""$9$QEni3/
t1RSM87u087-V4oz36"
set security group-vpn member ike gateway gw-group1 ike-policy ike-policy
set security group-vpn member ike gateway gw-group1 server-address 192.0.2.0
```

```

set security group-vpn member ike gateway gw-group1 local-address 198.51.100.0
set security group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
set security group-vpn member ipsec vpn vpn-group1 group 1
set security group-vpn member ipsec vpn vpn-group1 match-direction output
set services service-set gvpn-service-set interface-service service-interface ms-4/0/0.1
set services service-set gvpn-service-set ipsec-group-vpn vpn-group1

```

GM2

```

set interfaces ms-0/2/0 unit 1 family inet
set interfaces xe-0/0/0 unit 0 family inet address 203.0.113.2/24
set interfaces xe-0/1/1 vlan-tagging
set interfaces xe-0/1/1 unit 1 vlan-id 1
set interfaces xe-0/1/1 unit 1 family inet service input service-set gvpn-service-set
set interfaces xe-0/1/1 unit 1 family inet service output service-set gvpn-service-set
set interfaces xe-0/1/1 unit 1 family inet address 10.0.1.1/24
set interfaces ge-1/3/5 vlan-tagging
set interfaces ge-1/3/5 unit 1 vlan-id 11
set interfaces ge-1/3/5 unit 1 family inet address 198.51.100.1/24
set routing-options static route 192.0.2.0/24 next-hop 198.51.100.3
set routing-options static route 203.0.113.2/24 next-hop 10.0.1.2
set security group-vpn member ike proposal ike-proposal authentication-method pre-shared-keys
set security group-vpn member ike proposal ike-proposal dh-group group2
set security group-vpn member ike proposal ike-proposal authentication-algorithm sha1
set security group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc
set security group-vpn member ike policy ike-policy mode main
set security group-vpn member ike policy ike-policy proposals ike-proposal
set security group-vpn member ike policy ike-policy pre-shared-key ascii-text "$9$QEni3/
t1RSM87u087-V4oz36"
set security group-vpn member ike gateway gw-group1 ike-policy ike-policy
set security group-vpn member ike gateway gw-group1 server-address 192.0.2.0
set security group-vpn member ike gateway gw-group1 local-address 198.51.100.0
set security group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
set security group-vpn member ipsec vpn vpn-group1 group 1
set security group-vpn member ipsec vpn vpn-group1 match-direction output
set services service-set gvpn-service-set interface-service service-interface ms-0/2/0.1
set services service-set gvpn-service-set ipsec-group-vpn vpn-group1

```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure GM1:

1. Configure the Router GM1 interfaces.

```
[edit interfaces]
user@GM1# set ms-4/0/0 unit 1 family inet
user@GM1# set ge-0/1/9 vlan-tagging
user@GM1# set ge-0/1/9 unit 1 vlan-id 11
user@GM1# set ge-0/1/9 unit 1 family inet address 198.51.100.0/24
user@GM1# set xe-0/3/1 vlan-tagging
user@GM1# set xe-0/3/1 unit 1 vlan-id 1
user@GM1# set xe-0/3/1 unit 1 family inet service input service-set gvpn-service-set
user@GM1# set xe-0/3/1 unit 1 family inet service output service-set gvpn-service-set
user@GM1# set xe-0/3/1 unit 1 family inet address 10.0.1.2/24
user@GM1# set interfaces xe-4/3/1 unit 0 family inet address 203.0.113.1/24
```

2. Configure static routes to reach the group server and member 2.

```
[edit routing-options]
user@GM1# set static route 192.0.2.0/24 next-hop 198.51.100.2
user@GM1# set static route 203.0.113.0/24 next-hop 10.0.1.1
```

3. Define the IKE proposal.

```
[edit security]
user@GM1# set group-vpn member ike proposal ike-proposal
```

4. Configure the Phase 1 SA for ike-proposal.

```
[edit security]
user@GM1# set group-vpn member ike proposal ike-proposal authentication-method pre-shared-keys
user@GM1# set group-vpn member ike proposal ike-proposal dh-group group2
```

```
user@GM1# set group-vpn member ike proposal ike-proposal authentication-algorithm sha1
user@GM1# set group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc
```

5. Define the IKE policy.

```
[edit security]
user@GM1# set group-vpn member ike policy ike-policy mode main
user@GM1# set group-vpn member ike policy ike-policy proposals ike-proposal
user@GM1# set group-vpn member ike policy ike-policy pre-shared-key ascii-text "$9$QEni3/
t1RSM87u087-V4oz36"
```

6. Set the remote gateways for gw-group1.

```
[edit security]
user@GM1# set group-vpn member ike gateway gw-group1 ike-policy ike-policy
user@GM1# set group-vpn member ike gateway gw-group1 server-address 192.0.2.0
user@GM1# set group-vpn member ike gateway gw-group1 local-address 198.51.100.0
```

7. Configure the group identifier and IKE gateway for gw-group1.

```
[edit security]
user@GM1# set group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
user@GM1# set group-vpn member ipsec vpn vpn-group1 group 1
user@GM1# set group-vpn member ipsec vpn vpn-group1 match-direction output
```

8. Configure the service set for gw-group1.

```
[edit services]
user@GM1# set service-set gvpn-service-set interface-service service-interface ms-4/0/0.1
user@GM1# set service-set gvpn-service-set ipsec-group-vpn vpn-group1
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show routing-options`, `show security`, and `show services` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

GM1

```
user@GM1# show interfaces
ge-0/1/9 {
  vlan-tagging;
  unit 1 {
    vlan-id 11;
    family inet {
      address 198.51.100.0/24;
    }
  }
}
xe-0/3/1 {
  vlan-tagging;
  unit 1 {
    vlan-id 1;
    family inet {
      service {
        input {
          service-set gvpn-service-set;
        }
        output {
          service-set gvpn-service-set;
        }
      }
      address 10.0.1.2/24;
    }
  }
}
ms-4/0/0 {
  unit 1 {
    family inet;
  }
}
xe-4/3/1 {
  unit 0 {
    family inet {
      address 203.0.113.1/24;
    }
  }
}
```

```
    }
}
```

```
user@GM1# show routing-options
static {
    route 192.0.2.0/24 next-hop 198.51.100.2;
    route 203.0.113.0/24 next-hop 10.0.1.1;
}
```

```
user@GM1# show security
group-vpn {
    member {
        ike {
            proposal ike-proposal {
                authentication-method pre-shared-keys;
                dh-group group2;
                authentication-algorithm sha1;
                encryption-algorithm 3des-cbc;
            }
            policy ike-policy {
                mode main;
                pre-shared-key ascii-text "$9$QEni3/t1RSM87u087-V4oz36"; ## SECRET-DATA
                proposals ike-proposal;
            }
            gateway gw-group1 {
                ike-policy ike-policy;
                server-address 192.0.2.0;
                local-address 198.51.100.0;
            }
        }
    }
    ipsec {
        vpn vpn-group1 {
            ike-gateway gw-group1;
            group 1;
            match-direction output;
        }
    }
}
```

```
}
}
```

```
user@GM1# show services
service-set gvpn-service-set {
  interface-service {
    service-interface ms-4/0/0.1;
  }
  ipsec-group-vpn vpn-group1;
}
```

Configuring Group VPNv2 with Multiple GC/KS

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then commit the configuration.

GM1

```
set interfaces ms-4/0/0 unit 1 family inet
set interfaces ge-0/1/9 vlan-tagging
set interfaces ge-0/1/9 unit 1 vlan-id 11
set interfaces ge-0/1/9 unit 1 family inet address 198.51.100.0/24
set interfaces xe-0/3/1 vlan-tagging
set interfaces xe-0/3/1 unit 1 vlan-id 1
set interfaces xe-0/3/1 unit 1 family inet service input service-set gvpn-service-set
set interfaces xe-0/3/1 unit 1 family inet service output service-set gvpn-service-set
set interfaces xe-0/3/1 unit 1 family inet address 10.0.1.2/24
set interfaces xe-4/3/1 unit 0 family inet address 203.0.113.1/24
set routing-options static route 192.0.2.0/24 next-hop 198.51.100.2
set routing-options static route 203.0.113.0/24 next-hop 10.0.1.1
set security group-vpn member ike proposal ike-proposal authentication-method pre-shared-keys
set security group-vpn member ike proposal ike-proposal dh-group group2
set security group-vpn member ike proposal ike-proposal authentication-algorithm sha1
set security group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc
set security group-vpn member ike policy ike-policy mode main
set security group-vpn member ike policy ike-policy proposals ike-proposal
set security group-vpn member ike policy ike-policy pre-shared-key ascii-text "$9$QEni3/
```



```
t1RSM87u087-V4oz36"
```

```
set security group-vpn member ike gateway gw-group1 ike-policy ike-policy
set security group-vpn member ike gateway gw-group1 server-address 192.0.2.0
set security group-vpn member ike gateway gw-group1 server-address 172.16.0.0
set security group-vpn member ike gateway gw-group1 local-address 198.51.100.0
set security group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
set security group-vpn member ipsec vpn vpn-group1 group 1
set security group-vpn member ipsec vpn vpn-group1 match-direction output
set services service-set gvpn-service-set interface-service service-interface ms-4/0/0.1
set services service-set gvpn-service-set ipsec-group-vpn vpn-group1
```

GM2

```
set interfaces ms-0/2/0 unit 1 family inet
set interfaces xe-0/0/0 unit 0 family inet address 203.0.113.2/24
set interfaces xe-0/1/1 vlan-tagging
set interfaces xe-0/1/1 unit 1 vlan-id 1
set interfaces xe-0/1/1 unit 1 family inet service input service-set gvpn-service-set
set interfaces xe-0/1/1 unit 1 family inet service output service-set gvpn-service-set
set interfaces xe-0/1/1 unit 1 family inet address 10.0.1.1/24
set interfaces ge-1/3/5 vlan-tagging
set interfaces ge-1/3/5 unit 1 vlan-id 11
set interfaces ge-1/3/5 unit 1 family inet address 198.51.100.1/24
set routing-options static route 192.0.2.0/24 next-hop 198.51.100.3
set routing-options static route 203.0.113.2/24 next-hop 10.0.1.2
set security group-vpn member ike proposal ike-proposal authentication-method pre-shared-keys
set security group-vpn member ike proposal ike-proposal dh-group group2
set security group-vpn member ike proposal ike-proposal authentication-algorithm sha1
set security group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc
set security group-vpn member ike policy ike-policy mode main
set security group-vpn member ike policy ike-policy proposals ike-proposal
set security group-vpn member ike policy ike-policy pre-shared-key ascii-text ""$9$QEni3/
t1RSM87u087-V4oz36"
set security group-vpn member ike gateway gw-group1 ike-policy ike-policy
set security group-vpn member ike gateway gw-group1 server-address 192.0.2.0
set security group-vpn member ike gateway gw-group1 server-address 172.16.0.0
set security group-vpn member ike gateway gw-group1 local-address 198.51.100.1
set security group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
set security group-vpn member ipsec vpn vpn-group1 group 1
set security group-vpn member ipsec vpn vpn-group1 match-direction output
```

```
set services service-set gvpn-service-set interface-service service-interface ms-0/2/0.1
set services service-set gvpn-service-set ipsec-group-vpn vpn-group1
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure GM1:

1. Configure the Router GM1 interfaces.

```
[edit interfaces]
user@GM1# set ms-4/0/0 unit 1 family inet
user@GM1# set ge-0/1/9 vlan-tagging
user@GM1# set ge-0/1/9 unit 1 vlan-id 11
user@GM1# set ge-0/1/9 unit 1 family inet address 198.51.100.0/24
user@GM1# set xe-0/3/1 vlan-tagging
user@GM1# set xe-0/3/1 unit 1 vlan-id 1
user@GM1# set xe-0/3/1 unit 1 family inet service input service-set gvpn-service-set
user@GM1# set xe-0/3/1 unit 1 family inet service output service-set gvpn-service-set
user@GM1# set xe-0/3/1 unit 1 family inet address 10.0.1.2/24
user@GM1# set xe-4/3/1 unit 0 family inet address 203.0.113.1/24
```

2. Configure static routes to reach the group server and member 2.

```
[edit routing-options]
user@GM1# set static route 192.0.2.0/24 next-hop 198.51.100.2
user@GM1# set static route 203.0.1.0/24 next-hop 10.0.1.1
```

3. Define the IKE proposal.

```
[edit security]
user@GM1# set group-vpn member ike proposal ike-proposal
```

4. Configure the Phase 1 SA for ike-proposal.

```
[edit security]
user@GM1# set group-vpn member ike proposal ike-proposal authentication-method pre-shared-
```

keys

```

user@GM1# set group-vpn member ike proposal ike-proposal dh-group group2
user@GM1# set group-vpn member ike proposal ike-proposal authentication-algorithm sha1
user@GM1# set group-vpn member ike proposal ike-proposal encryption-algorithm 3des-cbc

```

5. Define the IKE policy.

```

[edit security]
user@GM1# set group-vpn member ike policy ike-policy mode main
user@GM1# set group-vpn member ike policy ike-policy proposals ike-proposal
user@GM1# set group-vpn member ike policy ike-policy pre-shared-key ascii-text "$9$QEni3/
t1RSM87u087-V4oz36"

```

6. Set the remote gateways for gw-group1.

```

[edit security]
user@GM1# set group-vpn member ike gateway gw-group1 ike-policy ike-policy
user@GM1# set group-vpn member ike gateway gw-group1 server-address 192.0.2.0
user@GM1# set group-vpn member ike gateway gw-group1 server-address 172.16.0.0
user@GM1# set group-vpn member ike gateway gw-group1 local-address 198.51.100.0

```

7. Configure the group identifier and IKE gateway for gw-group1.

```

[edit security]
user@GM1# set group-vpn member ipsec vpn vpn-group1 ike-gateway gw-group1
user@GM1# set group-vpn member ipsec vpn vpn-group1 group 1
user@GM1# set group-vpn member ipsec vpn vpn-group1 match-direction output

```

8. Configure the service set for gw-group1.

```

[edit services]
user@GM1# set service-set gvpn-service-set interface-service service-interface ms-4/0/0.1
user@GM1# set service-set gvpn-service-set ipsec-group-vpn vpn-group1

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show routing-options`, `show security`, and `show services` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

GM1

```
user@GM1# show interfaces
ge-0/1/9 {
  vlan-tagging;
  unit 1 {
    vlan-id 11;
    family inet {
      address 198.51.100.0/24;
    }
  }
}
xe-0/3/1 {
  vlan-tagging;
  unit 1 {
    vlan-id 1;
    family inet {
      service {
        input {
          service-set gvpn-service-set;
        }
        output {
          service-set gvpn-service-set;
        }
      }
      address 10.0.1.2/24;
    }
  }
}
ms-4/0/0 {
  unit 1 {
    family inet;
  }
}
xe-4/3/1 {
  unit 0 {
```

```

        family inet {
            address 203.0.113.1/24;
        }
    }
}

```

```

user@GM1# show routing-options
static {
    route 192.0.2.0/24 next-hop 198.51.100.2;
    route 203.0.113.0/24 next-hop 10.0.1.1;
}

```

```

user@GM1# show security
group-vpn {
    member {
        ike {
            proposal ike-proposal {
                authentication-method pre-shared-keys;
                dh-group group2;
                authentication-algorithm sha1;
                encryption-algorithm 3des-cbc;
            }
            policy ike-policy {
                mode main;
                pre-shared-key ascii-text "$9$QEni3/t1RSM87u087-V4oz36"; ## SECRET-DATA
                proposals ike-proposal;
            }
            gateway gw-group1 {
                ike-policy ike-policy;
                server-address [ 192.0.2.0 172.16.0.0 ];
                local-address 198.51.100.0;
            }
        }
    }
    ipsec {
        vpn vpn-group1 {
            ike-gateway gw-group1;
            group 1;
            match-direction output;
        }
    }
}

```

```
}
}
```

```
user@GM1# show services
service-set gvpn-service-set {
  interface-service {
    service-interface ms-4/0/0.1;
  }
  ipsec-group-vpn vpn-group1;
}
```

Verification

IN THIS SECTION

- [Verifying the Group Member IKE SA | 291](#)
- [Verifying the Group Member IPsec SA | 292](#)
- [Verifying the Group Member IPsec Statistics | 293](#)

Confirm that the configuration is working properly.

Verifying the Group Member IKE SA

Purpose

Verify the IKE SAs on Router GM1.

Action

From operational mode, run the `show security group-vpn member ike security-associations detail` command.

```
user@GM1> show security group-vpn member ike security-associations detail
IKE peer 192.0.2.0, Index 2994970, Gateway Name: gw-group1
  Role: Initiator, State: UP
  Initiator cookie: 7fad16089a123bcd, Responder cookie: 536b33ffe89799de
  Exchange type: Main, Authentication method: Pre-shared-keys
```

```

Local: 198.51.100.0:848, Remote: 192.0.2.0:848
Lifetime: Expires in 175 seconds
Peer ike-id: 192.0.2.0
Xauth user-name: not available
Xauth assigned IP: 0.0.0.0
Algorithms:
  Authentication      : hmac-sha1-96
  Encryption          : 3des-cbc
  Pseudo random function: hmac-sha1
  Diffie-Hellman group : DH-group-2
Traffic statistics:
  Input bytes  :          752
  Output bytes :          716
  Input packets:           5
  Output packets:          5
Flags: IKE SA is created
IPSec security associations: 0 created, 0 deleted
Phase 2 negotiations in progress: 0

```

Meaning

Router GM1 has established the IKE SA with the GC/KS for the group.

Verifying the Group Member IPsec SA

Purpose

Verify the IPsec SAs on Router GM1.

Action

From operational mode, run the `show security group-vpn member ipsec security-associations detail` command.

```

user@GM1> show security group-vpn member ipsec security-associations detail
Virtual-system: root Group VPN Name: vpn-group1
Local Gateway: 198.51.100.1, GDOI Server: 192.0.2.0
Group Id: 1
Rule Match Direction: output, Tunnel-MTU: 1500
Routing Instance: default
DF-bit: clear
Stats:

```

```

Pull Succeeded           : 18
Pull Failed              : 0
Pull Timeout             : 0
Pull Aborted             : 0
Server Failover          : 0
Delete Received          : 0
Exceed Maximum Keys(4)   : 0
Exceed Maximum Policies(1): 0
Unsupported Algo         : 0
Flags:
  Rekey Needed:    no

List of policies received from server:
Tunnel-id: 10001
  Source IP: ipv4_subnet(any:0,[0..7]=203.0.2.0/24)
  Destination IP: ipv4_subnet(any:0,[0..7]=203.0.1.0/24)

  Direction: bi-directional, SPI: e1c117c7
  Protocol: ESP, Authentication: sha1, Encryption: 3des
  Hard lifetime: Expires in 2526 seconds
  Lifesize Remaining: Unlimited
  Soft lifetime: Expires in 2366 seconds
  Mode: Tunnel, Type: Group VPN, State: installed
  Anti-replay service: N/A

```

Meaning

Router GM1 has established the IPsec SA with the GC/KS.

Verifying the Group Member IPsec Statistics

Purpose

Verify the IPsec statistics on Router GM1.

Action

From operational mode, run the `show security group-vpn member ipsec statistics` command.

```

user@GM1> show security group-vpn member ipsec statistics
PIC: ms-0/2/0, Service set: gvpn-service-set

```



```

ESP Statistics:
  Encrypted bytes:      264
  Decrypted bytes:      264
  Encrypted packets:    3
  Decrypted packets:    3
AH Statistics:
  Input bytes:          0
  Output bytes:         0
  Input packets:        0
  Output packets:       0
Errors:
  AH authentication failures: 0
  ESP authentication failures: 0
  ESP decryption failures: 0
  Bad headers: 0, Bad trailers: 0
  Replay before window drops: 0, Replayed pkts: 0
  IP integrity errors: 0, Exceeds tunnel MTU: 0
  Rule lookup failures: 0, No SA errors: 0
  Flow errors: 0, Misc errors: 0

```

Meaning

ESP Statistics shows that packet flows have been encrypted and decrypted between the group members. Router GM1 has encrypted 3 packets and has received 3 decrypted packets from Router GM2.

Troubleshooting

IN THIS SECTION

- [Negotiating the IKE SA | 295](#)
- [Establishing the IKE SA | 295](#)
- [Downloading the GDOI IPsec SA | 296](#)
- [Traffic Encryption and Decryption | 297](#)
- [Troubleshooting System Log Messages | 297](#)

To troubleshoot the Group VPNv2 configuration, see:

Negotiating the IKE SA

Problem

The IKE SA negotiation is not triggered on the group member.

The output of the `show ike` and `show security group-vpn member ike security-associations` commands does not display the IKE negotiations.

Solution

To troubleshoot the IKE negotiation issue:

1. Check if the service interface status is up.

Use `show interfaces terse | match ms` to check if the MS interface is down. An MS interface goes down when the PIC is rebooting.

2. Look for `Ignore gvpn vpn_name` since it is inactive in the log file `/var/log/gkmd`.

Check if the Group VPN is referenced by any service set in the configuration.

- a. Enable `security group-vpn member ike traceoptions`.

- b. Look for the following system log messages in the trace log file:

- Dec 2 16:09:54 GVPN:iked_pm_gvpn_trigger called for gvpn200
- Dec 2 16:09:54 GVPN:PM NULL for gvpn gvpn200
- Dec 2 16:09:54 GVPN:Ignore gvpn gvpn200 since it is inactive

This means either the service set is inactive or the service interface is down.

Establishing the IKE SA

Problem

The IKE SA is not getting established with the GC/KS.

In this scenario, the IKE SA state is down in the `show security group-vpn member ike security-associations` command output:

```
user@GM1> show security group-vpn member ike security-associations
Index   State Initiator cookie Responder cookie Mode Remote Address
5295626 DOWN 2d47c125d2a9805e 0000000000000000 Main 192.0.2.2
```

Solution

To troubleshoot the IKE SA issue:

1. Check if the server address configured under `[edit security group-vpn member ike gateway]` is the correct one and is reachable.
2. Use the `ping` command between the remote devices to check network connectivity.
3. Check if the local address in the `group-vpn` configuration is also a configured address on any of the physical interfaces in the configuration.
4. Check if the IKE proposals match between the group member and the GC/KS.

If there is a misconfiguration on the IKE SA negotiation, then do the following:

a. Enable `security group-vpn member ike traceoption`.

b. Look for the following message in the trace log file:

```
Dec 2 15:39:54 ikev2_fb_negotiation_done_isakmp: Entered IKE error code No proposal chosen (14), IKE SA
8dd7000 (neg 8dda800).
```

5. Look for a `No proposal chosen` error in the log file `/var/log/gkmd`.

Downloading the GDOI IPsec SA

Problem

The GDOI IPsec SAs are not downloaded from the GC/KS.

In this scenario, the `GDOI groupkey-pull` with the configured GC/KS fails, and the `show security group-vpn member ipsec sa` command output does not display anything.

Solution

To troubleshoot the GDOI IPsec SA issue:

1. Check if the IKE SA has been established with the GC/KS.
2. Check if the group ID configured on the GC/KS and the group member match.
3. Look for any group SA installation failures or other failures in the log file `/var/log/gkmd`.

Look for the following syslog messages to confirm use of an unsupported GDOI SA algorithm:

- Dec 2 15:32:49 simpleman gkmd[1701]: Failed to install SA because of unsupported algo(encr: 3des-cbc, auth : (null)) for SPI 0x6645cdb5 from server 192.0.2.1
- Dec 2 15:32:49 simpleman gkmd[1701]: Member registration failed with key server 192.0.2.1 for group vpn gvpn200, reason SA unusable

Look for the following syslog messages to confirm use of unsupported GDOI policies:

- Dec 2 15:34:34 simpleman gkmd[1701]: Failed to install SA because of too many(2) policies for SPI 0x6951550c from server 192.0.2.1
- Dec 2 15:34:34 simpleman gkmd[1701]: Member registration failed with key server 192.0.2.1 for group vpn gvpn200, reason SA unusable

Traffic Encryption and Decryption

Problem

The CLI shows IPsec SAs as installed, but traffic does not go through the SAs.

In this scenario, traffic matching the rules received from the server fails to get encrypted or decrypted. The `show security group-vpn member ipsec statistics` command output displays a zero value for encrypt and decrypt packet count.

Solution

Look for Rule lookup failures counter in the error section of the CLI output.

Troubleshooting System Log Messages

Problem

System log messages are generated to record the different Group VPNv2 events.

Solution

To interpret the system log messages, refer to the following:

- Dec 2 15:29:10 simpleman gkmd[1701]: Member registration succeeded with key server 192.0.2.1 for group vpn gvpn200—GDOI pull was successful.
- Dec 2 15:21:18 simpleman gkmd[1701]: Member registration failed with key server 192.0.2.1 for group vpn gvpn200, reason Timed out—GDOI pull failed.
- Dec 2 15:34:34 simpleman gkmd[1701]: Failed to install SA because of too many(2) policies for SPI 0x6951550c from server 192.0.2.1—GDOI SA installation failed because of too many policies.
- Dec 2 15:21:18 simpleman gkmd[1701]: Server 192.0.2.1 is unreachable for group vpn gvpn200—Single GC/KS failed (Non-COOP).
- Dec 2 15:51:49 simpleman gkmd[1701]: Current key server 192.0.2.1 is unreachable and will try registering with next Key Server 192.1.1.2 for group vpn gvpn200—Particular GC/KS is not responding (COOP).
- Dec 2 15:56:24 simpleman gkmd[1701]: All servers are unreachable for group vpn gvpn200—None of the GC/KS are responding (COOP).
- Dec 2 16:01:43 simpleman gkmd[1701]: Member re-registering with Key Server 192.0.2.1 for group-vpn gvpn200—Member re-registration with the GC/KS.
- Dec 2 16:01:43 simpleman gkmd[1701]: Creating TEK with SPI 0xb35200ac tunnel_id 10001 for group vpn gvpn200—GDOI SA TEK creation was successful.
- Dec 2 16:29:01 simpleman gkmd[1701]: Deleting TEK with SPI 0x6dba2a76 tunnel_id 10001 for group vpn gvpn200 and reason cleared from CLI—GDOI SA TEK destroy was successful with reason.

Different reasons for the GDOI SA TEK destroy are as follows:

- Cleared from CLI
- Hard lifetime expired
- Too many TEKs
- Configuration change
- SA install error
- Stale SA
- Interface down

RELATED DOCUMENTATION

[Use Case for Configuring Group VPNv2 | 275](#)

[Group VPNv2 Overview | 244](#)

4

PART

Configuring Public Key Infrastructure

[Configuring Digital Certificate Validation | 300](#)

[Configuring a Device for Certificate Chains | 313](#)

[Managing Certificate Revocation | 329](#)

Configuring Digital Certificate Validation

IN THIS CHAPTER

- [Understanding Digital Certificate Validation | 300](#)
- [Example: Improving Digital Certificate Validation by Configuring Policy OIDs on an MX Series Device | 307](#)

Understanding Digital Certificate Validation

IN THIS SECTION

- [Policy Validation | 300](#)
- [Path Length Validation | 303](#)
- [Key Usage | 304](#)
- [Issuer and Subject Distinguished Name Validation | 305](#)

Starting in Junos OS Release 16.1R3, MX Series devices support digital certificate validation. During IKE negotiation, the PKI daemon on an MX Series device validates X509 certificates received from VPN peers. The certificate validation performed is specified in RFC 5280, *Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile*. Basic certificate and certificate chain validations include signature and date validation as well as revocation checks. This topic describes additional digital certificate validations performed by the PKI daemon.

Policy Validation

X509 certificates can include optional policy validation fields. If a policy validation field is present, policy validation is performed for the entire certificate chain including the end entity (EE) certificate and intermediate certificate authority (CA) certificates. Policy validation is not applicable to the root certificate. Policy validation ensures that the EE and intermediate CA certificates have a common policy. If no common policy exists for the certificate chain being validated, certificate validation fails.

Prior to policy validation, a certificate chain containing the self-signed root certificate, intermediate CA certificates, and EE certificate must be built. The policy validation starts with the intermediate CA certificate issued by the self-signed root certificate and continues through the EE certificate.

The following optional certificate fields are used for policy validation:

- **policy-oids**
- **requireExplicitPolicy**
- **skipCerts**

These fields are described in the following sections.

Policy OIDs Configured on MX Series Devices

In some situations, it might be desirable to only accept certificates with known policy object identifiers (OIDs) from peers. This optional configuration allows certificate validation to succeed only if the certificate chain received from the peer contains at least one policy OID that is configured on the MX Series device.

On the MX Series device, policy OIDs are configured in an IKE policy with the **policy-oids** configuration statement at the [edit security ike policy *policy-name* certificate] hierarchy level. You can configure up to five policy OIDs. For a peer's certificate to be validated successfully, the peer's certificate chain must contain at least one of the policy OIDs configured on the MX Series device. Note that the **policy-oids** field in a certificate is optional. If you configure policy OIDs on the MX Series device but the peer's certificate chain does not contain any policy OIDs, certificate validation fails.


No Policy OIDs Configured on MX Series Devices

If no policy OID is configured on the MX Series device, policy validation starts whenever the **requireExplicitPolicy** field is encountered in the certificate chain. A certificate may contain one or more certificate policy OIDs. For policy validation to succeed, there must be a common policy OID in the certificate chain.

[Figure 20 on page 302](#) shows a certificate chain that consists of certificates for a root CA, three intermediate CAs, and an EE. The CA certificate for Int-CA-2 contains the **requireExplicitPolicy** field; therefore, policy validation starts with Int-CA-2 and continues through EE-1. The certificate for Int-CA-2 contains policy OIDs P1, P2, and P3. The certificate for Int-CA-3 contains policy OIDs P2, P3, and P4.

The certificate for EE-1 contains policy OIDs P2 and P5. Because the policy OID P2 is common to the certificates being validated, policy validation succeeds.

Figure 20: Policy Validation with requireExplicitPolicy Field




The optional **skipCerts** field in an intermediate CA certificate indicates the number of certificates, including the current CA certificate, that are to be excluded from policy validation. If **skipCerts** is 0, policy validation starts from the current certificate. If **skipCerts** is 1, the current certificate is excluded from policy validation. The value of the **skipCerts** field is checked in every intermediate CA certificate. If a **skipCerts** value is encountered that is lower than the current number of certificates being excluded, the lower **skipCerts** value is used.

[Figure 21 on page 303](#) shows a certificate chain consisting of a root CA, four intermediate CAs, and an EE. The **skipCerts** value in Int-CA-1 is 12, which skips 12 certificates including the certificate for Int-CA-1. However, the **skipCerts** value is checked in every intermediate CA certificate in the chain. The

skipCerts value in Int-CA-2 is 2, which is lower than 12, so now 2 certificates are skipped. The **skipCerts** value in Int-CA-4 is 5, which is greater than 2, so the Int-CA-4 **skipCerts** value is ignored.

Figure 21: Policy Validation with skipCerts Field



When policy OIDs are configured on the MX Series device, the certificate fields **requireExplicitPolicy** and **skipCerts** are ignored.


Path Length Validation

Certificate validation can involve a certificate chain that includes a root CA, one or more optional intermediate CAs, and an EE certificate. The number of intermediate CAs can grow depending upon the deployment scenario. Path length validation provides a mechanism to limit the number of intermediate certificates involved in certificate validation. **path-length** is an optional field in an X509 certificate. The value of **path-length** indicates the number of non-self-signed intermediate CA certificates allowed for certificate validation. The last certificate, which is generally the EE certificate, is not included in the path limit. If the root certificate contains a **path-length** value of 0, no intermediate CA certificates are allowed. If the **path-length** value is 1, there can be 0 or 1 intermediate CA certificates.

path-length can be present in multiple CA certificates in the certificate chain. The path length validation always begins with the self-signed root certificate. The path limit is decremented by 1 at each intermediate certificate in the chain. If an intermediate certificate contains a **path-length** value less than the current path limit, the new limit is enforced. On the other hand, if the **path-length** value is larger than the current path limit, it is ignored.

Figure 22 on page 304 shows a certificate chain that consists of a root CA, four intermediate CAs, and an EE. The **path-length** value in Root-CA is 10, therefore the initial path limit of non-self-signed intermediate CA certificates allowed for certificate validation is 10. At Int-CA-1, the path limit is 10-1 or 9. The **path-length** value in Int-CA-1 is 4, which is less than the path limit of 9, so the new path limit becomes 4. At Int-CA-2, the path limit is 4-1 or 3. The **path-length** value in Int-CA-2 is 5, which is larger than the path limit of 3, so it is ignored. At Int-CA-3, the path limit is 3-1 or 2. The **path-length** value in Int-CA-3 is 20, which is larger than the path limit of 2, so it is also ignored.

Figure 22: Path Length Validation



Key Usage

The key usage field in an EE or CA certificate defines the purpose of the key contained in the certificate.

EE Certificates

For EE certificates, if the key usage field is present but the certificate does not contain **digitalSignature** or **nonrepudiation** flags, the certificate is rejected. If the key usage field is not present, then key usage is not checked.

CA Certificates

The key can be used for certificate or CRL signature validation. Because the PKI daemon is responsible for both X509 certificate validation and CRL downloads, key usage must be checked before validating the certificate or CRL.

Certificate Signature Validation

The **keyCertSign** flag indicates that a CA certificate can be used for certificate signature validation. If this flag is not set, certificate validation is terminated.

CRL Signature Validation

In Phase 1 negotiations, participants check the certificate revocation list (CRL) to see if certificates received during an IKE exchange are still valid. The CRL is periodically downloaded for CA profiles configured with CRL as the certificate revocation check. Downloaded CRL files must be verified before they are downloaded into the device. One of the verification steps is to validate the CRL signature using a CA certificate. The downloaded CRL is signed with the CA certificate's private key and it must be verified with the CA certificate's public key stored in the device. The key usage field in the CA certificate must contain the **CRLSign** flag to verify the downloaded CRL. If this flag is not present, the CRL is discarded.


Issuer and Subject Distinguished Name Validation

Signature validation is performed for certificates received from a peer as well as for the CRL file downloaded from a CA server. Signature validation involves looking up the CA certificate in a CA database based on the issuer's distinguished name (DN) in the certificate or the CRL being verified.

[Figure 23 on page 306](#) shows the lookup for CA certificates based on the issuer DN. In the EE certificate, the issuer DN is CA-1, which is the subject DN of the intermediate CA certificate in the chain. In the intermediate CA certificate, the issuer DN is CA-Root, which is the subject DN of the self-

signed Root-CA certificate in the chain. In the CRL, the issuer DN is CA-Root, which is the subject DN of the self-signed Root-CA certificate.

Figure 23: Issuer and Subject DN Validation



The lookup for the issuer or subject DN must follow these rules for attribute values:

- Attribute values encoded in different ASN.1 types (for example, PrintableString and BMPString) are assumed to represent different strings.
- Attribute values encoded in PrintableString types are not case-sensitive. These attribute values are compared after removing leading and trailing white spaces and converting internal substrings of one or more consecutive white spaces to a single space.
- Attribute values encoded in types other than PrintableString are case-sensitive.

Release History Table

Release	Description
16.1R3	Starting in Junos OS Release 16.1R3, MX Series devices support digital certificate validation.

RELATED DOCUMENTATION

[Example: Improving Digital Certificate Validation by Configuring Policy OIDs on an MX Series Device | 307](#)

[policy-oids | 1630](#)

Example: Improving Digital Certificate Validation by Configuring Policy OIDs on an MX Series Device

IN THIS SECTION

- [Requirements | 307](#)
- [Overview | 308](#)
- [Configuration | 308](#)
- [Verification | 309](#)

In some situations, it might be desirable to only accept certificates with known policy object identifiers (OIDs) from peers. This optional configuration allows certificate validation to succeed only if the certificate chain received from the peer contains at least one policy OID that is configured on the MX Series device. This example shows how to configure policy OIDs in the IKE policy on an MX Series device.

NOTE: You must ensure that at least one of the policy OIDs configured on the MX Series device is included in a peer's certificate or certificate chain. Note that the **policy-oids** field in a peer's certificate is optional. If you configure policy OIDs in an IKE policy and the peer's certificate chain does not contain any policy OIDs, certificate validation for the peer fails.

Requirements

Before you begin:

- Ensure that you are using Junos OS Release 16.1 or later for MX Series devices.
- Configure an IPsec VPN tunnel.

Overview

This example shows an IKE policy configuration where policy OIDs 2.16.840.1.101.3.1.48.2 and 5.16.40.1.101.3.1.55.2 are specified. The IKE policy `ike_cert_pol` references the IKE proposal `ike_cert_prop`, which is not shown. The local certificate on the MX Series device is `lc-igloo-root`.

Configuration

IN THIS SECTION

- [Procedure | 308](#)

Procedure

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the `[edit]` hierarchy level, and then enter `commit` from configuration mode.

```
set services ipsec-vpn ike policy ike_cert_pol mode main
set services ipsec-vpn ike policy ike_cert_pol proposals ike_cert_prop
set services ipsec-vpn ike policy ike_cert_pol certificate local-certificate lc-igloo-root
set services ipsec-vpn ike policy ike_cert_pol certificate policy-oids 2.16.840.1.101.3.1.48.2
set services ipsec-vpn ike policy ike_cert_pol certificate policy-oids 5.16.40.1.101.3.1.55.2
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure policy OIDs for certificate validation:

- Configure the IKE policy:

```
[edit services ipsec-vpn ike policy ike_cert_pol]
user@host# set mode main
user@host# set proposals ike_cert_prop
```

```
user@host# set certificate local-certificate lc-igloo-root
user@host# set certificate policy-oids 2.16.840.1.101.3.1.48.2
user@host# set certificate policy-oids 5.16.40.1.101.3.1.55.2
```

Results

From configuration mode, confirm your configuration by entering the `show services ipsec-vpn ike policy ike_cert_pol` command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show services ipsec-vpn ike policy ike_cert_pol
mode main;
proposals ike_cert_prop;
certificate {
    local-certificate lc-igloo-root;
    policy-oids [ 2.16.840.1.101.3.1.48.2 5.16.40.1.101.3.1.55.2 ];
}
```

If you are done configuring the device, enter `commit` from configuration mode.

Verification

IN THIS SECTION

- [Verifying the CA Certificate | 309](#)
- [Verifying Policy OID Validation | 311](#)

Confirm that the configuration is working properly.

Verifying the CA Certificate

Purpose

Display the CA certificate configured on the device.

Action

From operational mode, enter the `show security pki ca-certificate ca-profile ca-tmp detail` command.

```

user@host> show security pki ca-certificate ca-profile ca-tmp detail
    Certificate identifier: ca-tmp
    Certificate version: 3
    Serial number: 00000047
    Issuer:
      Organization: U.S. Government,
      Organizational unit: DoD, Organizational unit: Testing, Country: US,
      Common name: Trust Anchor
    Subject:
      Organization: U.S. Government,
      Organizational unit: Dod, Organizational unit: Testing, Country: US,
      Common name: CA1-PP.01.03
    Subject string:
      C=US, O=U.S. Government, OU=Dod, OU=Testing, CN=CA1-PP.01.03
    Validity:
      Not before: 07- 3-2015 10:54 UTC
      Not after: 07- 1-2020 10:54 UTC

?Public key algorithm: rsaEncryption(1024 bits)
  30:81:89:02:81:81:00:cb:fd:78:0c:be:87:ac:cd:c0:33:66:a3:18
  9e:fd:40:b7:9b:bc:dc:66:ff:08:45:f7:7e:fe:8e:d6:32:f8:5b:75
  db:76:f0:4d:21:9a:6e:4f:04:21:4c:7e:08:a1:f9:3d:ac:8b:90:76
  44:7b:c4:e9:9b:93:80:2a:64:83:6e:6a:cd:d8:d4:23:dd:ce:cb:3b
  b5:ea:da:2b:40:8d:ad:a9:4d:97:58:cf:60:af:82:94:30:47:b7:7d
  88:c3:76:c0:97:b4:6a:59:7e:f7:86:5d:d8:1f:af:fb:72:f1:b8:5c
  2a:35:1e:a7:9e:14:51:d4:19:ae:c7:5c:65:ea:f5:02:03:01:00:01
Signature algorithm: sha1WithRSAEncryption
Certificate Policy:
  Policy Identifier = 2.16.840.1.101.3.1.48.2
Use for key: CRL signing, Certificate signing
Fingerprint:
  e0:b3:2f:2e:a1:c5:ee:ad:af:dd:96:85:f6:78:24:c5:89:ed:39:40 (sha1)
  f3:47:6e:55:bc:9d:80:39:5a:40:70:8b:10:0e:93:c5 (md5)

```

Verifying Policy OID Validation

Purpose

If the peer's certificate is successfully validated, IKE and IPsec security associations are established. If the validation of the peer's certificate fails, no IKE security association is established.

Action

From operational mode, enter the `show services ipsec-vpn ike security-associations` and `show services ipsec-vpn ipsec security-associations` commands.

```
user@host> show services ipsec-vpn ike security-associations
node0:
-----
Index   State Initiator cookie Responder cookie Mode      Remote Address
821765168 UP    88875c981252c1d8 b744ac9c21bde57e IKEv2     192.0.2.1
1106977837 UP    1a09e32d1e6f20f1 e008278091060acb IKEv2     198.51.100.0
```

```
user@host> show services ipsec-vpn ipsec security-associations
node0:
-----
Total active tunnels: 2
ID      Algorithm      SPI      Life:sec/kb Mon lsys Port Gateway
<213909506 ESP:aes-cbc-192/sha256 8cb9e40a 1295/ unlim - root 500 192.0.2.1
>213909506 ESP:aes-cbc-192/sha256 8271d2b2 1295/ unlim - root 500 192.0.2.1
<218365954 ESP:aes-cbc-192/sha256 d0153bc0 1726/ unlim - root 1495 198.51.100.0
>218365954 ESP:aes-cbc-192/sha256 97611813 1726/ unlim - root 1495 198.51.100.0
```

Meaning

The `show services ipsec-vpn ike security-associations` command lists all active IKE Phase 1 SAs. If no SAs are listed, there was a problem with Phase 1 establishment. In this case, check for the `PKID_CERT_POLICY_CHECK_FAIL` message in the system logs. This message indicates that the peer's certificate chain does not contain a policy OID that is configured on the MX Series device. Check the **policy-oids** values in the peer's certificate chain with the values configured on the MX Series device.

It might also be that the peer's certificate chain does not contain any **policy-oids** fields, which are optional fields. If this is the case, certificate validation fails if there are any policy OIDs configured on the MX Series device.

RELATED DOCUMENTATION

[Understanding Digital Certificate Validation](#) | 300

[policy-oids](#) | 1630

Configuring a Device for Certificate Chains

IN THIS CHAPTER

- [IKE Authentication \(Certificate-Based Authentication\) | 313](#)
- [Example: Configuring a Device for Peer Certificate Chain Validation | 316](#)

IKE Authentication (Certificate-Based Authentication)

IN THIS SECTION

- [Multilevel Hierarchy for Certificate Authentication | 313](#)

Multilevel Hierarchy for Certificate Authentication

Certificate-based authentication is an authentication method supported on SRX Series devices during IKE negotiation. In large networks, multiple certificate authorities (CAs) can issue end entity (EE) certificates to their respective end devices. It is common to have separate CAs for individual locations, departments, or organizations.

When a single-level hierarchy for certificate-based authentication is employed, all EE certificates in the network must be signed by the same CA. All firewall devices must have the same CA certificate enrolled for peer certificate validation. The certificate payload sent during IKE negotiation only contains EE certificates.

Alternatively, the certificate payload sent during IKE negotiation can contain a chain of EE and CA certificates. A *certificate chain* is the list of certificates required to validate a peer's EE certificate. The certificate chain includes the EE certificate and any CA certificates that are not present in the local peer.


The network administrator needs to ensure that all peers participating in an IKE negotiation have at least one common trusted CA in their respective certificate chains. The common trusted CA does not

have to be the root CA. The number of certificates in the chain, including certificates for EEs and the topmost CA in the chain, cannot exceed 10.

Starting with Junos OS Release 18.1R1, validation of a configured IKE peer can be done with a specified CA server or group of CA servers. With certificate chains, the root CA must match the trusted CA group or CA server configured in the IKE policy

In the example CA hierarchy shown in [Figure 24 on page 314](#), Root-CA is the common trusted CA for all devices in the network. Root-CA issues CA certificates to the engineering and sales CAs, which are identified as Eng-CA and Sales-CA, respectively. Eng-CA issues CA certificates to the development and quality assurance CAs, which are identified as Dev-CA and Qa-CA, respectively. Host-A receives its EE certificate from Dev-CA while Host-B receives its EE certificate from Sales-CA.

Figure 24: Multilevel Hierarchy for Certificate-Based Authentication



Each end device needs to be loaded with the CA certificates in its hierarchy. Host-A must have Root-CA, Eng-CA, and Dev-CA certificates; Sales-CA and Qa-CA certificates are not necessary. Host-B must have Root-CA and Sales-CA certificates. Certificates can be loaded manually in a device or enrolled using the Simple Certificate Enrollment Process (SCEP).

Each end device must be configured with a CA profile for each CA in the certificate chain. The following output shows the CA profiles configured on Host-A:

```
admin@host-A# show security
pki {
  ca-profile Root-CA {
    ca-identity Root-CA;
    enrollment {
      url "www.example.net/scep/Root/";
    }
  }
  ca-profile Eng-CA {
    ca-identity Eng-CA;
    enrollment {
      url "www.example.net/scep/Eng/";
    }
  }
  ca-profile Dev-CA {
    ca-identity Dev-CA;
    enrollment {
      url "www.example.net/scep/Dev/";
    }
  }
}
```

The following output shows the CA profiles configured on Host-B:

```
admin@host-B# show security
pki {
  ca-profile Root-CA {
    ca-identity Root-CA;
    enrollment {
      url "www.example.net/scep/Root/";
    }
  }
  ca-profile Sales-CA {
    ca-identity Sales-CA;
    enrollment {
      url "www.example.net/scep/Sales/";
    }
  }
}
```

```
}
}
```

Release History Table

Release	Description
18.1R1	Starting with Junos OS Release 18.1R1, validation of a configured IKE peer can be done with a specified CA server or group of CA servers.

RELATED DOCUMENTATION

- Basic Elements of PKI in Junos OS
- Understanding Certificate Authority Profiles

Example: Configuring a Device for Peer Certificate Chain Validation

IN THIS SECTION

- Requirements | 316
- Overview | 317
- Configuration | 318
- Verification | 325
- IKE and IPsec SA Failure for a Revoked Certificate | 327

This example shows how to configure a device for certificate chains used to validate peer devices during IKE negotiation.

Requirements

Before you begin, obtain the address of the certificate authority (CA) and the information they require (such as the challenge password) when you submit requests for local certificates.

Overview

IN THIS SECTION


- Topology | 317

This example shows how to configure a local device for certificate chains, enroll CA and local certificates, check the validity of enrolled certificates, and check the revocation status of the peer device.

Topology

This example shows the configuration and operational commands on Host-A, as shown in [Figure 25 on page 317](#). A dynamic CA profile is automatically created on Host-A to allow Host-A to download the CRL from Sales-CA and check the revocation status of Host-B's certificate.

Figure 25: Certificate Chain Example



NOTE: The IPsec VPN configuration for Phase 1 and Phase 2 negotiation is shown for Host-A in this example. The peer device (Host-B) must be properly configured so that Phase 1 and Phase 2 options are successfully negotiated and security associations (SAs) are established.

Configuration

IN THIS SECTION

- [Configure CA Profiles | 318](#)
- [Enroll Certificates | 320](#)
- [Configure IPsec VPN Options | 323](#)

To configure a device for certificate chains:

Configure CA Profiles

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then enter `commit` from configuration mode.

```
set security pki ca-profile Root-CA ca-identity CA-Root
set security pki ca-profile Root-CA enrollment url http://10.157.88.230:8080/scep/Root/
set security pki ca-profile Root-CA revocation-check use-crl
set security pki ca-profile Eng-CA ca-identity Eng-CA
set security pki ca-profile Eng-CA enrollment url http://10.157.88.230:8080/scep/Eng/
set security pki ca-profile Eng-CA revocation-check use-crl
set security pki ca-profile Dev-CA ca-identity Dev-CA
set security pki ca-profile Dev-CA enrollment url http://10.157.88.230:8080/scep/Dev/
set security pki ca-profile Dev-CA revocation-check use-crl
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure CA profiles:

1. Create the CA profile for Root-CA.

```
[edit security pki]
user@host# set ca-profile Root-CA ca-identity CA-Root
user@host# set ca-profile Root-CA enrollment url http://10.157.88.230:8080/scep/Root/
user@host# set ca-profile Root-CA revocation-check use-crl
```

2. Create the CA profile for Eng-CA.

```
[edit security pki]
user@host# set ca-profile Eng-CA ca-identity Eng-CA
user@host# set ca-profile Eng-CA enrollment url http://10.157.88.230:8080/scep/Eng/
user@host# set ca-profile Eng-CA revocation-check use-crl
```

3. Create the CA profile for Dev-CA.

```
[edit security pki]
user@host# set ca-profile Dev-CA ca-identity Dev-CA
user@host# set ca-profile Dev-CA enrollment url http://10.157.88.230:8080/scep/Dev/
user@host# set ca-profile Dev-CA revocation-check use-crl
```

Results

From configuration mode, confirm your configuration by entering the `show security pki` command. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
[edit]
user@host# show security pki
ca-profile Root-CA {
  ca-identity Root-CA;
  enrollment {
```

```

        url "http://10.157.88.230:8080/scep/Root/";
    }
    revocation-check {
        use-crl;
    }
}
ca-profile Eng-CA {
    ca-identity Eng-CA;
    enrollment {
        url "http://10.157.88.230:8080/scep/Eng/";
    }
    revocation-check {
        use-crl;
    }
}
ca-profile Dev-CA {
    ca-identity Dev-CA;
    enrollment {
        url "http://10.157.88.230:8080/scep/Dev/";
    }
    revocation-check {
        use-crl;
    }
}
}

```

If you are done configuring the device, enter `commit` from configuration mode.

Enroll Certificates

Step-by-Step Procedure

To enroll certificates:

1. Enroll the CA certificates.

```
user@host> request security pki ca-certificate enroll ca-profile Root-CA
```

```
user@host> request security pki ca-certificate enroll ca-profile Eng-CA
```

```
user@host> request security pki ca-certificate enroll ca-profile Dev-CA
```

Type **yes** at the prompts to load the CA certificate.

2. Verify that the CA certificates are enrolled in the device.

```
user@host> show security pki ca-certificate ca-profile Root-CA
Certificate identifier: Root-CA
    Issued to: Root-CA, Issued by: C = us, O = juniper, CN = Root-CA
    Validity:
        Not before: 07- 3-2015 10:54 UTC
        Not after:  07- 1-2020 10:54 UTC
    Public key algorithm: rsaEncryption(2048 bits)
```

```
user@host> show security pki ca-certificate ca-profile Eng-CA
Certificate identifier: Eng-CA
    Issued to: Eng-CA, Issued by: C = us, O = juniper, CN = Root-CA
    Validity:
        Not before: 07- 3-2015 10:54 UTC
        Not after:  07- 1-2020 10:54 UTC
    Public key algorithm: rsaEncryption(2048 bits)
```

```
user@host> show security pki ca-certificate ca-profile Dev-CA
Certificate identifier: Dev-CA
    Issued to: Dev-CA, Issued by: C = us, O = juniper, CN = Eng-CA
    Validity:
        Not before: 07- 3-2015 10:54 UTC
        Not after:  07- 1-2020 10:54 UTC
    Public key algorithm: rsaEncryption(2048 bits)
```

3. Verify the validity of the enrolled CA certificates.

```
user@host> request security pki ca-certificate verify ca-profile Root-CA
CA certificate Root-CA verified successfully
```

```
user@host> request security pki ca-certificate verify ca-profile Eng-CA
CA certificate Eng-CA verified successfully
```

```
user@host> request security pki ca-certificate verify ca-profile Dev-CA
CA certificate Dev-CA verified successfully
```

4. Enroll the local certificate.

```
user@host> request security pki local-certificate enroll certificate-id      Host-A ca-
profile Dev-CA challenge-password juniper domain-name host-a.company.net email host-
a@company.net subject DC=juniper,CN=Host-A,      OU=DEV,O=PKI,L=Sunnyvale,ST=CA,C=US
```

5. Verify that the local certificate is enrolled in the device.

```
user@host> show security pki local-certificate
Issued to: Host-A, Issued by: C = us, O = juniper, CN = Dev-CA
Validity:
  Not before: 07- 3-2015 10:54 UTC
  Not after:  07- 1-2020 10:54 UTC
Public key algorithm: rsaEncryption(1024 bits)
```

6. Verify the validity of the enrolled local certificate.

```
user@host> request security pki local-certificate verify certificate-id Host-A
Local certificate Host-A verification success
```

7. Check the CRL download for configured CA profiles.

```
user@host> show security pki crl
CA profile: Root-CA
```

```
CRL version: V00000001
CRL issuer: C = us, O = juniper, CN = Root-CA
Effective date: 09- 9-2015 13:08
Next update: 09-21-2015 02:55
```

```
CA profile: Eng-CA
CRL version: V00000001
CRL issuer: C = us, O = juniper, CN = Eng-CA
Effective date: 08-22-2015 17:46
Next update: 10-24-2015 03:33
```

```
CA profile: Dev-CA
CRL version: V00000001
CRL issuer: C = us, O = juniper, CN = Dev-CA
Effective date: 09-14-2015 21:15
Next update: 09-26-2012 11:02
```

Configure IPsec VPN Options

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then enter `commit` from configuration mode.

```
set services ipsec-vpn ike proposal ike_cert_prop_01 authentication-method rsa-signatures
set services ipsec-vpn ike proposal ike_cert_prop_01 dh-group group5
set services ipsec-vpn ike proposal ike_cert_prop_01 authentication-algorithm sha1
set services ipsec-vpn ike proposal ike_cert_prop_01 encryption-algorithm aes-256-cbc
set services ipsec-vpn ike policy ike_cert_pol_01 mode main
set services ipsec-vpn ike policy ike_cert_pol_01 proposals ike_cert_prop_01
set services ipsec-vpn ike policy ike_cert_pol_01 certificate local-certificate Host-A
set services ipsec-vpn ipsec proposal ipsec_prop_01 protocol esp
set services ipsec-vpn ipsec proposal ipsec_prop_01 authentication-algorithm hmac-sha1-96
set services ipsec-vpn ipsec proposal ipsec_prop_01 encryption-algorithm 3des-cbc
set services ipsec-vpn ipsec proposal ipsec_prop_01 lifetime-seconds 300
set services ipsec-vpn ipsec policy ipsec_pol_01 proposals ipsec_prop_01
set services ipsec-vpn ipsec vpn ipsec_cert_vpn_01 ike ipsec-policy ipsec_pol_01
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure IPsec VPN options:

1. Configure Phase 1 options.

```
[edit services ipsec-vpn ike proposal ike_cert_prop_01]
user@host# set authentication-method rsa-signatures
user@host# set dh-group group5
user@host# set authentication-algorithm sha1
user@host# set encryption-algorithm aes-256-cbc
[edit services ipsec-vpn ike policy ike_cert_pol_01]
user@host# set mode main
user@host# set proposals ike_cert_prop_01
user@host# set certificate local-certificate Host-A
```

2. Configure Phase 2 options.

```
[edit services ipsec-vpn ipsec proposal ipsec_prop_01]
user@host# set protocol esp
user@host# set authentication-algorithm hmac-sha1-96
user@host# set encryption-algorithm 3des-cbc
user@host# set lifetime-seconds 300
[edit services ipsec-vpn ipsec policy ipsec_pol_01]
user@host# set proposals ipsec_prop_01
[edit services ipsec-vpn ipsec vpn ipsec_cert_vpn_01]
user@host# set ike ipsec-policy ipsec_pol_01
```

Results

From configuration mode, confirm your configuration by entering the `show security ike` and `show security ipsec` commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
[edit]
user@host# show services ipsec-vpn ike
proposal ike_cert_prop_01 {
```

```

authentication-method rsa-signatures;
dh-group group5;
authentication-algorithm sha1;
encryption-algorithm aes-256-cbc;
}

policy ike_cert_pol_01 {
    mode main;
    proposals ike_cert_prop_01;
    certificate {
        local-certificate Host-A;
    }
}

[edit]
user@host# show services ipsec-vpn ipsec
proposal ipsec_prop_01 {
    protocol esp;
    authentication-algorithm hmac-sha1-96;
    encryption-algorithm 3des-cbc;
    lifetime-seconds 300;
}

policy ipsec_pol_01 {
    proposals ipsec_prop_01;
}

```

If you are done configuring the device, enter `commit` from configuration mode.

Verification

IN THIS SECTION

- [Verifying IKE Phase 1 Status | 326](#)
- [Verifying IPsec Phase 2 Status | 326](#)

If certificate validation is successful during IKE negotiation between peer devices, both IKE and IPsec security associations (SAs) are established.

Verifying IKE Phase 1 Status

Purpose

Verify the IKE Phase 1 status.

Action

Enter the **show services ipsec-vpn ike security-associations** command from operational mode.

```
user@host> show services ipsec-vpn ike security-associations
```

Remote Address	State	Initiator cookie	Responder cookie	Exchange type
192.0.2.0	Matured	63b3445edda507fb	2715ee5895ed244d	Main

Verifying IPsec Phase 2 Status

Purpose

Verify the IPsec Phase 2 status.

Action

Enter the **show services ipsec-vpn ipsec security-associations** command from operational mode.

```
user@host> show services ipsec-vpn ipsec security-associations
```

Service set: ips_ssl, IKE Routing-instance: default

Rule: vpn_rule_ms_2_2_01, Term: term11, Tunnel index: 1

Local gateway: 10.0.1.2, Remote gateway: 172.16.0.0

IPSec inside interface: ms-2/2/0.1, Tunnel MTU: 1500

UDP encapsulate: Disabled, UDP Destination port: 0

Direction	SPI	AUX-SPI	Mode	Type	Protocol
inbound	2151932129	0	tunnel	dynamic	ESP
outbound	4169263669	0	tunnel	dynamic	ESP

IKE and IPsec SA Failure for a Revoked Certificate

IN THIS SECTION

- [Checking for Revoked Certificates | 327](#)

Checking for Revoked Certificates

Problem

If certificate validation fails during IKE negotiation between peer devices, check to make sure that the peer's certificate has not been revoked. A dynamic CA profile allows the local device to download the CRL from the peer's CA and check the revocation status of the peer's certificate. To enable dynamic CA profiles, the `revocation-check crl` option must be configured on a parent CA profile.

Solution

To check the revocation status of a peer's certificate:

1. Identify the dynamic CA profile that will show the CRL for the peer device by entering the **show security pki crl** command from operational mode.

```
user@host> show security pki crl

CA profile: Root-CA
  CRL version: V00000001
  CRL issuer: C = us, O = juniper, CN = Root-CA
  Effective date: 09- 9-2012 13:08
  Next update: 09-21-2012 02:55

CA profile: Eng-CA
  CRL version: V00000001
  CRL issuer: C = us, O = juniper, CN = Eng-CA
  Effective date: 08-22-2012 17:46
  Next update: 10-24-2015 03:33

CA profile: Dev-CA
  CRL version: V00000001
  CRL issuer: C = us, O = juniper, CN = Dev-CA
  Effective date: 09-14-2012 21:15
```

```
Next update: 09-26-2012 11:02
```

```
CA profile: dynamic-001
```

```
CRL version: V00000001
```

```
CRL issuer: C = us, O = juniper, CN = Sales-CA
```

```
Effective date: 09-14-2012 21:15
```

```
Next update: 09-26-2012 11:02
```

The CA profile `dynamic-001` is automatically created on Host-A so that Host-A can download the CRL from Host-B's CA (Sales-CA) and check the revocation status of the peer's certificate.

2. Display CRL information for the dynamic CA profile by entering the **`show security pki crl ca-profile dynamic-001 detail`** command from operational mode.

Enter

```
user@host> show security pki crl ca-profile dynamic-001 detail
```

```
CA profile: dynamic-001
```

```
CRL version: V00000001
```

```
CRL issuer: C = us, O = juniper, CN = Sub11
```

```
Effective date: 09-19-2012 17:29
```

```
Next update: 09-20-2012 01:49
```

```
Revocation List:
```

Serial number	Revocation date
10647C84	09-19-2012 17:29 UTC

Host-B's certificate (serial number 10647084) has been revoked.

RELATED DOCUMENTATION

| [IKE Authentication \(Certificate-Based Authentication\)](#) | 313

Managing Certificate Revocation

IN THIS CHAPTER

- [Understanding Online Certificate Status Protocol and Certificate Revocation Lists | 329](#)
- [Example: Improving Security by Configuring OCSP for Certificate Revocation Status | 332](#)

Understanding Online Certificate Status Protocol and Certificate Revocation Lists

IN THIS SECTION

- [Comparison of Online Certificate Status Protocol and Certificate Revocation List | 331](#)

OCSP is used to check the revocation status of X509 certificates. OCSP provides revocation status on certificates in real time and is useful in time-sensitive situations such as bank transactions and stock trades.

The revocation status of a certificate is checked by sending a request to an OCSP server that resides outside of an SRX Series device. Based on the response from the server, the VPN connection is allowed or denied. OCSP responses are not cached on SRX Series devices.

The OCSP server can be the *certificate authority (CA)* that issues a certificate or a designated authorized responder. The location of the OCSP server can be configured manually or extracted from the certificate that is being verified. Requests are sent first to OCSP server locations that are manually configured in CA profiles with the `ocsp url` statement at the `[edit security pki ca-profile profile-name revocation-check]` hierarchy level; up to two locations can be configured for each CA profile. If the first configured OCSP server is not reachable, the request is sent to the second OCSP server. If the second OCSP server is not reachable, the request is then sent to the location in the certificate's AuthorityInfoAccess extension field. The `use-ocsp` option must also be configured, as *certificate revocation list (CRL)* is the default checking method.

SRX Series devices accept only signed OCSP responses from the CA or authorized responder. The response received is validated using trusted certificates. The response is validated as follows:

1. The CA certificate enrolled for the configured CA profile is used to validate the response.
2. The OCSP response might contain a certificate to validate the OCSP response. The received certificate must be signed by a CA certificate enrolled in the SRX Series device. After the received certificate is validated by the CA certificate, it is used to validate the OCSP response.

The response from the OCSP server can be signed by different CAs. The following scenarios are supported:

- The CA server that issues the end entity certificate for a device also signs the OCSP revocation status response. The SRX Series device verifies the OCSP response signature using the CA certificate enrolled in the SRX Series device. After the OCSP response is validated, the certificate revocation status is checked.
- An authorized responder signs the OCSP revocation status response. The certificate for the authorized responder and the end entity certificate being verified must be issued by the same CA. The authorized responder is first verified using the CA certificate enrolled in the SRX Series device. The OCSP response is validated using the responder's CA certificate. The SRX Series device then uses the OCSP response to check the revocation status of the end entity certificate.
- There are different CA signers for the end entity certificate being verified and the OCSP response. The OCSP response is signed by a CA in the certificate chain for the end entity certificate being verified. (All peers participating in an IKE negotiation need to have at least one common trusted CA in their respective certificate chains.) The OCSP responder's CA is verified using a CA in the certificate chain. After validating the responder CA certificate, the OCSP response is validated using the responder's CA certificate.

To prevent replay attacks, a *nonce* payload can be sent in an OCSP request. Nonce payloads are sent by default unless it is explicitly disabled. If enabled, the SRX Series device expects the OCSP response to contain a nonce payload, otherwise the revocation check fails. If OCSP responders are not capable of responding with a nonce payload, then the nonce payload must be disabled on the SRX Series device.

In the normal course of business, certificates are revoked for various reasons. You might wish to revoke a certificate if you suspect that it has been compromised, for example, or when a certificate holder leaves the company.

You can manage certificate revocations and validations in two ways:

- Locally— This is a limited solution.
- By referencing a Certificate Authority (CA) certificate revocation list (CRL)— You can automatically access the CRL online at intervals you specify or at the default interval set by the CA.

In Phase 1 negotiations, SRX Series device verifies the EE certificate received from the peer during an IKE exchange and uses the CRL to make sure the EE certificate is not revoked by its CA.

If a CRL is not loaded on the device and the peer certificate issuer is a trusted CA:

1. Junos OS retrieves the CRL through the configured LDAP or HTTP CRL locations (that is, the CRL Distribution Points (CDP)), if they are defined in the CA profile.
2. If the CRL Distribution Points is not configured in the CA profile, the device uses the CDP extension in a certificate issued by the CA (if present). The certificate issued by the CA can be a certificate enrolled by the administrator or received during the Phase 1 negotiation.

If the EE certificate is not issued by a root CA, the certificates of each intermediate CAs goes through the same verification and revocation check. The CRL of the root CA is used to check if the certificate issued by the root CA is revoked. If the CDP is not configured in the root CA profile, the device uses the CDP extension in the certificate issued by the CA (if present).

The CRL distribution point extension (.cdp) in an X509 certificate can be added to either an HTTP URL or an LDAP URL.

If the certificate does not contain a certificate distribution point extension, and you cannot automatically retrieve the CRL through Lightweight Directory Access Protocol (LDAP) or Hypertext Transfer Protocol (HTTP), you can retrieve a CRL manually and load that in the device.

Local certificates are being validated against certificate revocation list (CRL) even when CRL check is disabled. This can be stopped by disabling the CRL check through the Public Key Infrastructure (PKI) configuration. When CRL check is disabled, PKI will not validate local certificate against CRL.

Comparison of Online Certificate Status Protocol and Certificate Revocation List

Online Certificate Status Protocol (OCSP) and certificate revocation list (CRL) can both be used to check the revocation status of a certificate. There are advantages and disadvantages to each method.

- OCSP provides certificate status in real time, while CRL uses cached data. For time-sensitive applications, OCSP is the preferred approach.
- CRL checking is faster because lookup for certificate status is done on information cached on the VPN device. OCSP requires time to obtain the revocation status from an external server.
- CRL requires additional memory to store the revocation list received from a CRL server. OCSP does not require additional memory to save the revocation status of certificates.
- OCSP requires that the OCSP server be available at all times. CRL can use cached data to check the revocation status of certificates when the server is unreachable.

On MX Series and SRX Series devices, CRL is the default method used to check the revocation status of a certificate.

RELATED DOCUMENTATION

[Certificate Validation](#)

Example: Improving Security by Configuring OCSP for Certificate Revocation Status

IN THIS SECTION

- [Requirements | 332](#)
- [Overview | 332](#)
- [Configuration | 335](#)
- [Verification | 346](#)

This example shows how to improve security by configuring two peers using the Online Certificate Status Protocol (OCSP) to check the revocation status of the certificates used in Phase 1 negotiations for the IPsec VPN tunnel.

Requirements

On each device:

- Obtain and enroll a local certificate. This can be done either manually or by using the Simple Certificate Enrollment Protocol (SCEP).
- Optionally, enable automatic renewal of the local certificate.
- Configure security policies to permit traffic to and from the peer device.

Overview

IN THIS SECTION

- [Topology | 335](#)

On both peers, a certificate authority (CA) profile Root is configured with the following options:

- CA name is Root.
- Enrollment URL is `http://10.1.1.1:8080/scep/Root/`. This is the URL where SCEP requests to the CA are sent.
- The URL for the OCSP server is `http://10.157.88.56:8210/Root/`.
- OCSP is used first to check the certificate revocation status. If there is no response from the OCSP server, then the certificate revocation list (CRL) is used to check the status. The CRL URL is `http://10.1.1.1:8080/crl-as-der/currentcrl-45.crlid=45`.
- The CA certificate received in an OCSP response is not checked for certificate revocation. Certificates received in an OCSP response generally have shorter lifetimes and a revocation check is not required.

[Table 7 on page 333](#) shows the Phase 1 options used in this example.

Table 7: Phase 1 Options for OCSP Configuration Example

Option	Peer A	Peer B
IKE proposal	ike_policy_ms_2_2_0	ike_proposal_ms_2_0_0
Authentication method	rsa-signatures	rsa-signatures
DH group	group2	group2
Authentication algorithm	SHA 1	SHA 1
Encryption algorithm	3des-cbc	3des-cbc
Lifetime seconds	3000	3000
IKE policy	ike_policy_ms_2_2_0	ike_policy_ms_2_0_0
Mode	main	main
Proposal	ike_proposal_ms_2_2_0	ike_proposal_ms_2_0_0

Table 7: Phase 1 Options for OCSP Configuration Example (Continued)

Option	Peer A	Peer B
Certificate	local7_neg	local7_moji
Policy	ike_policy	ike_policy
Gateway address	10.0.1.2	192.0.2.0
Remote identity	fqdn company.net	fqdn company.net
Local identity	fqdn company.net	fqdn company.net
External interface	ge-1/3/0	ge-1/3/0
Version	1	1

[Table 8 on page 334](#) shows the Phase 2 options used in this example.

Table 8: Phase 2 Options for OCSP Configuration Example

Option	Peer A	Peer B
IPsec proposal	ipsec_proposal_ms_2_2_0	ipsec_proposal_ms_2_0_0
Protocol	esp	esp
Authentication algorithm	hmac-sha1-96	hmac-sha1-96
Encryption algorithm	3des-cbc	3des-cbc
Lifetime seconds	2000	2000
IPsec policy	ipsec_policy_ms_2_2_0	ipsec_policy_ms_2_0_0


Table 8: Phase 2 Options for OCSP Configuration Example *(Continued)*

Option	Peer A	Peer B
PFC keys	group2	group2
Proposal	ipsec_proposal_ms_2_2_0	ipsec_proposal_ms_2_0_0
VPN	test_vpn	test_vpn
Policy	ipsec_policy	ipsec_policy
Establish tunnels	-	immediately

Topology

Figure 26 on page 335 shows the peer devices that are configured in this example.

Figure 26: OCSP Configuration Example



Configuration

IN THIS SECTION

- Configuring Peer A | 336

Configuring Peer A

CLI Quick Configuration

To quickly configure VPN peer A to use OCSP, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then enter **commit** from configuration mode.

```
set interfaces ge-1/3/0 unit 0 family inet address 10.0.1.2
set interfaces ms-2/2/0 unit 0 family inet
set interfaces ms-2/2/0 unit 1 family inet
set interfaces ms-2/2/0 unit 1 family inet6
set interfaces ms-2/2/0 unit 1 service-domain inside
set interfaces ms-2/2/0 unit 2 family inet
set interfaces ms-2/2/0 unit 2 family inet6
set interfaces ms-2/2/0 unit 2 service-domain outside
set security pki ca-profile Root ca-identity Root
set security pki ca-profile Root enrollment url http://10.1.1.1:8080/scep/Root/
set security pki ca-profile Root revocation-check ocsp url http://10.157.88.56:8210/Root/
set security pki ca-profile Root revocation-check use-ocsp
set security pki ca-profile Root revocation-check ocsp disable-responder-revocation-check
set security pki ca-profile Root revocation-check ocsp connection-failure fallback-crl
set services ipsec-vpn ike proposal ike_prop authentication-method rsa-signatures
set services service-set ips_ssl next-hop-service inside-service-interface ms-2/2/0.1
set services service-set ips_ssl next-hop-service outside-service-interface ms-2/2/0.2
set services service-set ips_ssl ipsec-vpn-options local-gateway 10.0.1.2
set services service-set ips_ssl ipsec-vpn-rules vpn_rule_ms_2_2_01
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 from source-address 203.0.113.0/24
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 from destination-address
198.51.100.0/24
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 then remote-gateway 192.0.2.0
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 then dynamic ike-policy
ike_policy_ms_2_2_0
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 then dynamic ipsec-policy
ipsec_policy_ms_2_2_0
set services ipsec-vpn rule vpn_rule_ms_2_2_01 match-direction input
```

```

set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 protocol esp
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 authentication-algorithm hmac-sha1-96
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 encryption-algorithm 3des-cbc
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 lifetime-seconds 2000
set services ipsec-vpn ipsec policy ipsec_policy_ms_2_2_0 proposals ipsec_proposal_ms_2_2_0
set services ipsec-vpn ike proposal ike_proposal_ms_2_2_0 authentication-method rsa-signatures
set services ipsec-vpn ike proposal ike_proposal_ms_2_2_0 dh-group group2
set services ipsec-vpn ike proposal ike_proposal_ms_2_2_0 lifetime-seconds 3000
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 mode main
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 version 1
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 proposals ike_proposal_ms_2_2_0
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 local-id fqdn company.net
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 local-certificate local7_neg
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 remote-id fqdn company.net
set services ipsec-vpn traceoptions level all
set services ipsec-vpn traceoptions flag all
set services ipsec-vpn establish-tunnels immediately

```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure VPN peer A to use OCSP:

1. Configure interfaces.

```

[edit interfaces]
set interfaces ge-1/3/0 unit 0 family inet address 10.0.1.2
set interfaces ms-2/2/0 unit 0 family inet
set interfaces ms-2/2/0 unit 1 family inet
set interfaces ms-2/2/0 unit 1 family inet6
set interfaces ms-2/2/0 unit 1 service-domain inside
set interfaces ms-2/2/0 unit 2 family inet
set interfaces ms-2/2/0 unit 2 family inet6
set interfaces ms-2/2/0 unit 2 service-domain outside

```

2. Configure the CA profile.

```
[edit security pki ca-profile Root]
set security pki ca-profile Root ca-identity Root
set security pki ca-profile Root enrollment url http://10.1.1.1:8080/scep/Root/
set security pki ca-profile Root revocation-check ocsp url http://10.157.88.56:8210/Root/
set security pki ca-profile Root revocation-check use-ocsp
set security pki ca-profile Root revocation-check ocsp disable-responder-revocation-check
set security pki ca-profile Root revocation-check ocsp connection-failure fallback-crl
```

3. Configure Phase 1 options.

```
[edit services ipsec-vpn ike proposal ike_proposal_ms_2_2_0]
set services ipsec-vpn ike proposal ike_proposal_ms_2_2_0 authentication-method rsa-signatures
set services ipsec-vpn ike proposal ike_proposal_ms_2_2_0 dh-group group2
set services ipsec-vpn ike proposal ike_proposal_ms_2_2_0 lifetime-seconds 3000

[edit services ipsec-vpn ike policy ike_policy_ms_2_2_0]
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 mode main
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 version 1
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 proposals ike_proposal_ms_2_2_0
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 local-id fqdn company.net
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 local-certificate local7_neg
set services ipsec-vpn ike policy ike_policy_ms_2_2_0 remote-id fqdn company.net
```

4. Configure Phase 2 options.

```
[edit services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0]
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 protocol esp
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 authentication-algorithm hmac-sha1-96
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 encryption-algorithm 3des-cbc
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_2_0 lifetime-seconds 2000

[edit services ipsec-vpn ipsec policy ipsec_policy_ms_2_2_0]
set services ipsec-vpn ipsec policy ipsec_policy_ms_2_2_0 proposals ipsec_proposal_ms_2_2_0

[edit services service-set ips_ss1]
set services service-set ips_ss1 next-hop-service inside-service-interface ms-2/2/0.1
set services service-set ips_ss1 next-hop-service outside-service-interface ms-2/2/0.2
```

```

set services service-set ips_ss1 ipsec-vpn-options local-gateway 10.0.1.2
set services service-set ips_ss1 ipsec-vpn-rules vpn_rule_ms_2_2_01

[edit services ipsec-vpn rule vpn_rule_ms_2_2_01]
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 from source-address 203.0.113.0/24
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 from destination-address
198.51.100.0/24
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 then remote-gateway 192.0.2.0
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 then dynamic ike-policy
ike_policy_ms_2_2_0
set services ipsec-vpn rule vpn_rule_ms_2_2_01 term term11 then dynamic ipsec-policy
ipsec_policy_ms_2_2_0
set services ipsec-vpn rule vpn_rule_ms_2_2_01 match-direction input

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show security pki ca-profile Root`, `show services ipsec-vpn ike`, and `show services ipsec-vpn ipsec` commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```

[edit]
user@host# show interfaces
ge-1/3/0 {
    unit 0 {
        family inet {
            address 10.0.1.2/24;
        }
    }
}
ms-2/2/0 {
    unit 0 {
        family inet;
    }
    unit 1 {
        family inet;
        family inet6;
        service-domain inside;
    }
    unit 2 {
        family inet;
        family inet6;
    }
}

```

```

        service-domain inside;
    }
}
[edit]
user@host# show security pki ca-profile Root
ca-identity Root;
enrollment {
    url http://10.1.1.1:8080/scep/Root/;
}
revocation-check {
    ocsf {
        url http://10.157.88.56:8210/Root/;
        disable-responder-revocation-check;
        connection-failure fallback-crl;
    }
    use-ocsf;
}
[edit]
user@host# show services ipsec-vpn ike
proposal ike_proposal_ms_2_2_0 {
    authentication-method rsa-signatures;
    dh-group group2;
    lifetime-seconds 3000;
}
policy ike_policy_ms_2_2_0 {
    mode main;
    version 1;
    proposals ike_proposal_ms_2_2_0;
    local-id fqdn company.net;
    local-certificate local7_neg;
    remote-id fqdn company.net;
}
[edit]
user@host# show services ipsec-vpn ipsec
proposal ipsec_proposal_ms_2_2_0 {
    protocol esp;
    authentication-algorithm hmac-sha1-96;
    encryption-algorithm 3des-cbc;
    lifetime-seconds 2000;
}
policy ipsec_policy_ms_2_2_0 {

```

```

    proposals ipsec_proposal_ms_2_2_0;
}

```

If you are done configuring the device, enter `commit` from configuration mode.

Configuring Peer B

CLI Quick Configuration

To quickly configure VPN peer B to use OCSP, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the `[edit]` hierarchy level, and then enter **commit** from configuration mode.

```

set interfaces ge-1/3/0 unit 0 family inet address 192.0.2.0/24
set interfaces ms-2/0/0 unit 0 family inet
set interfaces ms-2/0/0 unit 1 family inet
set interfaces ms-2/0/0 unit 1 family inet6
set interfaces ms-2/0/0 unit 1 service-domain inside
set interfaces ms-2/0/0 unit 2 family inet
set interfaces ms-2/0/0 unit 2 family inet6
set interfaces ms-2/0/0 unit 2 service-domain outside
set security pki ca-profile Root ca-identity Root
set security pki ca-profile Root enrollment url http://10.1.1.1:8080/scep/Root/
set security pki ca-profile Root revocation-check ocsp url http://10.157.88.56:8210/Root/
set security pki ca-profile Root revocation-check use-ocsp
set security pki ca-profile Root revocation-check ocsp disable-responder-revocation-check
set security pki ca-profile Root revocation-check ocsp connection-failure fallback-crl
set services service-set ips_ssl next-hop-service inside-service-interface ms-2/0/0.1
set services service-set ips_ssl next-hop-service outside-service-interface ms-2/0/0.2
set services service-set ips_ssl ipsec-vpn-options local-gateway 192.0.2.0
set services service-set ips_ssl ipsec-vpn-rules vpn_rule_ms_2_0_01
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 from source-address 203.0.113.0/24
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 from destination-address
198.51.100.0/24
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 then remote-gateway 10.0.1.2
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 then dynamic ike-policy
ike_policy_ms_2_0_0
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 then dynamic ipsec-policy
ipsec_policy_ms_2_0_0
set services ipsec-vpn rule vpn_rule_ms_2_0_01 match-direction input
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 protocol esp

```



```

set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 authentication-algorithm hmac-sha1-96
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 encryption-algorithm 3des-cbc
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 lifetime-seconds 2000
set services ipsec-vpn ipsec policy ipsec_policy_ms_2_0_0 proposals ipsec_proposal_ms_2_0_0
set services ipsec-vpn ike proposal ike_proposal_ms_2_0_0 authentication-method rsa-signatures
set services ipsec-vpn ike proposal ike_proposal_ms_2_0_0 dh-group group2
set services ipsec-vpn ike proposal ike_proposal_ms_2_0_0 lifetime-seconds 3000
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 mode main
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 version 1
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 proposals ike_proposal_ms_2_0_0
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 local-id fqdn company.net
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 local-certificate local7_moji
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 remote-id fqdn company.net
set services ipsec-vpn traceoptions level all
set services ipsec-vpn traceoptions flag all

```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For instructions on how to do that, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure VPN peer B to use OCSP:

1. Configure interfaces.

```

[edit interfaces]
set interfaces ge-1/3/0 unit 0 family inet address 192.0.2.0/24
set interfaces ms-2/0/0 unit 0 family inet
set interfaces ms-2/0/0 unit 1 family inet
set interfaces ms-2/0/0 unit 1 family inet6
set interfaces ms-2/0/0 unit 1 service-domain inside
set interfaces ms-2/0/0 unit 2 family inet
set interfaces ms-2/0/0 unit 2 family inet6
set interfaces ms-2/0/0 unit 2 service-domain outside

```

2. Configure the CA profile.

```

[edit security pki ca-profile Root]
set security pki ca-profile Root ca-identity Root
set security pki ca-profile Root enrollment url http://10.1.1.1:8080/scep/Root/

```

```

set security pki ca-profile Root revocation-check ocsf url http://10.157.88.56:8210/Root/
set security pki ca-profile Root revocation-check use-ocsp
set security pki ca-profile Root revocation-check ocsf disable-responder-revocation-check
set security pki ca-profile Root revocation-check ocsf connection-failure fallback-crl

```

3. Configure Phase 1 options.

```

[edit services ipsec-vpn ike proposal ike_proposal_ms_2_0_0]
set services ipsec-vpn ike proposal ike_proposal_ms_2_0_0 authentication-method rsa-signatures
set services ipsec-vpn ike proposal ike_proposal_ms_2_0_0 dh-group group2
set services ipsec-vpn ike proposal ike_proposal_ms_2_0_0 lifetime-seconds 3000

[edit services ipsec-vpn ike policy ike_policy_ms_2_0_0]
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 mode main
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 version 1
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 proposals ike_proposal_ms_2_0_0
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 local-id fqdn company.net
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 local-certificate local7_moji
set services ipsec-vpn ike policy ike_policy_ms_2_0_0 remote-id fqdn company.net

```

4. Configure Phase 2 options.

```

[edit services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0]
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 protocol esp
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 authentication-algorithm hmac-sha1-96
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 encryption-algorithm 3des-cbc
set services ipsec-vpn ipsec proposal ipsec_proposal_ms_2_0_0 lifetime-seconds 2000

[edit services ipsec-vpn ipsec policy ipsec_policy_ms_2_0_0]
set services ipsec-vpn ipsec policy ipsec_policy_ms_2_0_0 proposals ipsec_proposal_ms_2_0_0

[edit services service-set ips_ss1]
set services service-set ips_ss1 next-hop-service inside-service-interface ms-2/0/0.1
set services service-set ips_ss1 next-hop-service outside-service-interface ms-2/0/0.2
set services service-set ips_ss1 ipsec-vpn-options local-gateway 192.0.2.0
set services service-set ips_ss1 ipsec-vpn-rules vpn_rule_ms_2_0_01

[edit services ipsec-vpn rule vpn_rule_ms_2_0_01]
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 from source-address 203.0.113.0/24
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 from destination-address

```

```

198.51.100.0/24
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 then remote-gateway 10.0.1.2
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 then dynamic ike-policy
ike_policy_ms_2_0_0
set services ipsec-vpn rule vpn_rule_ms_2_0_01 term term11 then dynamic ipsec-policy
ipsec_policy_ms_2_0_0
set services ipsec-vpn rule vpn_rule_ms_2_0_01 match-direction input

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show security pki ca-profile Root`, `show services ipsec-vpn ike`, and `show services ipsec-vpn ipsec` commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```

[edit]
user@host# show interfaces
ge-1/3/0 {
    unit 0 {
        family inet {
            address 192.0.2.0/24;
        }
    }
}
ms-2/0/0 {
    unit 0 {
        family inet;
    }
    unit 1 {
        family inet;
        family inet6;
        service-domain inside;
    }
    unit 2 {
        family inet;
        family inet6;
        service-domain inside;
    }
}
[edit]
user@host# show security pki ca-profile Root
ca-identity Root;

```

```

enrollment {
    url http://10.1.1.1:8080/scep/Root/;
}
revocation-check {
    ocsf {
        url http://10.157.88.56:8210/Root/;
        disable-responder-revocation-check;
        connection-failure fallback-crl;
    }
    use-ocsf;
}
[edit]
user@host# show services ipsec-vpn ike
proposal ike_proposal_ms_2_0_0 {
    authentication-method rsa-signatures;
    dh-group group2;
    lifetime-seconds 3000;
}
policy ike_policy_ms_2_0_0 {
    mode main;
    version 1;
    proposals ike_proposal_ms_2_0_0;
    local-id fqdn company.net;
    local-certificate local7_moji;
    remote-id fqdn company.net;
}
[edit]
user@host# show services ipsec-vpn ipsec
proposal ipsec_proposal_ms_2_0_0 {
    protocol esp;
    authentication-algorithm hmac-sha1-96;
    encryption-algorithm 3des-cbc;
    lifetime-seconds 2000;
}
policy ipsec_policy_ms_2_0_0 {
    proposals ipsec_proposal_ms_2_0_0;
}

```

If you are done configuring the device, enter `commit` from configuration mode.

Verification

IN THIS SECTION

- [Verifying CA Certificates | 346](#)
- [Verifying Local Certificates | 348](#)
- [Verifying IKE Phase 1 Status | 349](#)
- [Verifying IPsec Phase 2 Status | 351](#)

Confirm that the configuration is working properly.

Verifying CA Certificates

Purpose

Verify the validity of a CA certificate on each peer device.

Action

From operational mode, enter the `show security pki ca-certificate ca-profile Root` or `show security pki ca-certificate ca-profile Root detail` command.

```
user@host> show security pki ca-certificate ca-profile Root
Certificate identifier: Root
  Issued to: Root, Issued by: C = US, O = Juniper, CN = Root
  Validity:
    Not before: 07- 3-2015 10:54 UTC
    Not after: 07- 1-2020 10:54 UTC
  Public key algorithm: rsaEncryption(2048 bits)

user@host> show security pki ca-certificate ca-profile Root detail
Certificate identifier: Root
  Certificate version: 3
  Serial number: 0000a17f
  Issuer:
    Organization: Juniper, Country: US, Common name: Root
  Subject:
    Organization: Juniper, Country: US, Common name: Root
```

```

Subject string:
  C=US, O=Juniper, CN=Root
Validity:
  Not before: 07- 3-2015 10:54 UTC
  Not after: 07- 1-2020 10:54 UTC
Public key algorithm: rsaEncryption(2048 bits)
  30:82:01:0a:02:82:01:01:00:c6:38:e9:03:69:5e:45:d8:a3:ea:3d
  2e:e3:b8:3f:f0:5b:39:f0:b7:35:64:ed:60:a0:ba:89:28:63:29:e7
  27:82:47:c4:f6:41:53:c8:97:d7:1e:3c:ca:f0:a0:b9:09:0e:3d:f8
  76:5b:10:6f:b5:f8:ef:c5:e8:48:b9:fe:46:a3:c6:ba:b5:05:de:2d
  91:ce:20:12:8f:55:3c:a6:a4:99:bb:91:cf:05:5c:89:d3:a7:dc:a4
  d1:46:f2:dc:36:f3:f0:b5:fd:1d:18:f2:e6:33:d3:38:bb:44:8a:19
  ad:e0:b1:1a:15:c3:56:07:f9:2d:f6:19:f7:cd:80:cf:61:de:58:b8
  a3:f5:e0:d1:a3:3a:19:99:80:b0:63:03:1f:25:05:cc:b2:0c:cd:18
  ef:37:37:46:91:20:04:bc:a3:4a:44:a9:85:3b:50:33:76:45:d9:ba
  26:3a:3b:0d:ff:82:40:36:64:4e:ea:6a:d8:9b:06:ff:3f:e2:c4:a6
  76:ee:8b:58:56:a6:09:d3:4e:08:b0:64:60:75:f3:e2:06:91:64:73
  d2:78:e9:7a:cb:8c:57:0e:d1:9a:6d:3a:4a:9e:5b:d9:e4:a2:ef:31
  5d:2b:2b:53:ab:a1:ad:45:49:fd:a5:e0:8b:4e:0b:71:52:ca:6b:fa
  8b:0e:2c:7c:7b:02:03:01:00:01
Signature algorithm: sha1WithRSAEncryption
Distribution CRL:
  http://10.1.1.1:8080/crl-as-der/currentcrl-45.crl?id=45
Authority Information Access OCSP:
  http://10.1.1.1:8090/Root/
Use for key: CRL signing, Certificate signing, Key encipherment, Digital signature
Fingerprint:
  ed:ce:ec:13:1a:d2:ab:0a:76:e5:26:6d:2c:29:5d:49:90:57:f9:41 (sha1)
  af:87:07:69:f0:3e:f7:c6:b8:2c:f8:df:0b:ae:b0:28 (md5)

```

NOTE: In this example, IP addresses are used in the URLs in the CA profile configuration. If IP addresses are not used with CA-issued certificates or CA certificates, DNS must be configured in the device's configuration. DNS must be able to resolve the host in the distribution CRL and in the CA URL in the CA profile configuration. Additionally, you must have network reachability to the same host to receive revocation checks.

Meaning

The output shows the details and validity of CA certificate on each peer as follows:

- C—Country.

- 0—Organization.
- CN—Common name.
- Not before—Begin date of validity.
- Not after—End date of validity.

Verifying Local Certificates

Purpose

Verify the validity of a local certificate on each peer device.

Action

From operational mode, enter the `show security pki local-certificate certificate-id localcert1 detail` command.

```
user@host> show security pki local-certificate certificate-id local7_neg detail

Certificate identifier: local7_neg
Certificate version: 3
Serial number: 0007d964
Issuer:
  Organization: juniper, Country: us, Common name: Subca2
Subject:
  Organization: juniper, Organizational unit: marketing, State: california, Locality:
sunnyvale, Common name: local, Domain component: juniper
Subject string:
  DC=juniper, CN=local, OU=marketing, O=juniper, L=sunnyvale, ST=california, C=us
Alternate subject: "test@company.net", company.net, 10.0.0.2
Validity:
  Not before: 04- 5-2016 03:30 UTC
  Not after: 07- 1-2020 10:54 UTC
Public key algorithm: rsaEncryption(1024 bits)
30:81:89:02:81:81:00:b9:44:42:0e:26:5a:46:8e:a7:9c:b9:15:a5
f1:38:e4:59:59:9d:84:75:ee:7a:64:ca:0a:a7:68:3b:2b:0c:dc:a8
de:60:df:07:80:23:58:7d:56:dd:4f:50:de:a4:57:f1:a0:df:a9:7a
6c:3d:e0:6d:7a:cf:ef:af:95:1b:12:7a:c4:54:61:12:db:65:0c:f9
25:40:2d:01:71:21:8a:fc:fc:f6:9d:db:5a:63:ca:1a:92:2b:a3:98
f6:6b:e4:23:67:53:92:6a:5e:ad:ae:d7:82:ab:32:c1:60:6f:01:14
```

```

    fd:46:bd:3f:b3:6b:fd:e6:41:de:6d:94:0d:6f:ad:02:03:01:00:01
Signature algorithm: sha256WithRSAEncryption
Distribution CRL:
    http://10.1.1.1:8080/crl-as-der/currentcrl-1925.crl?id=1925
Authority Information Access OCSP:
    http://10.204.128.120:8090/Subca2/
Fingerprint:
    69:00:fe:e1:81:37:ab:54:27:81:ce:57:11:a1:f2:d8:00:e7:e6:c7 (sha1)
    1e:27:93:a1:96:eb:28:0c:dc:f3:50:20:bb:eb:ed:57 (md5)
Auto-re-enrollment:
    Status: Disabled
    Next trigger time: Timer not started

```

Meaning

The output shows the details and validity of a local certificate on each peer as follows:

- DC—Domain component.
- CN—Common name.
- OU—Organizational unit.
- O—Organization.
- L—Locality
- ST—State.
- C—Country.
- Not before—Begin date of validity.
- Not after—End date of validity.

Verifying IKE Phase 1 Status

Purpose

Verify the IKE Phase 1 status on each peer device.

Action

From operational mode, enter the `show services ipsec-vpn ike security-associations` command.

```
user@host> show services ipsec-vpn ike security-associations
```

Remote Address	State	Initiator cookie	Responder cookie	Exchange type
192.0.2.0	Matured	63b3445edda507fb	2715ee5895ed244d	Main

From operational mode, enter the `show services ipsec-vpn ike security-associations detail` command.

```
user@host> show services ipsec-vpn ike security-associations detail
```

```
IKE peer 192.0.2.0
  Role: Initiator, State: Matured
  Initiator cookie: 63b3445edda507fb, Responder cookie: 2715ee5895ed244d
  Exchange type: Main, Authentication method: RSA-signatures
  Local: 10.0.1.2, Remote: 192.0.2.0
  Lifetime: Expires in 788 seconds
  Algorithms:
    Authentication      : hmac-sha1-96
    Encryption          : 3des-cbc
    Pseudo random function: hmac-sha1
    Diffie-Hellman group : 2
  Traffic statistics:
    Input bytes  :          3100
    Output bytes :          4196
    Input packets:           7
    Output packets:          9
  Flags: IKE SA created
  IPSec security associations: 4 created, 4 deleted
```

Meaning

The `flags` field in the output shows that, IKE security association is created.

Verifying IPsec Phase 2 Status

Purpose

Verify the IPsec Phase 2 status on each peer device.

Action

From operational mode, enter the `show services ipsec-vpn ipsec security-associations` command.

```
user@host> show services ipsec-vpn ipsec security-associations
```

```
Service set: ips_ssl, IKE Routing-instance: default
```

```
Rule: vpn_rule_ms_2_2_01, Term: term11, Tunnel index: 1
```

```
Local gateway: 10.0.1.2, Remote gateway: 192.0.2.0
```

```
IPSec inside interface: ms-2/2/0.1, Tunnel MTU: 1500
```

```
UDP encapsulate: Disabled, UDP Destination port: 0
```

Direction	SPI	AUX-SPI	Mode	Type	Protocol
inbound	2151932129	0	tunnel	dynamic	ESP
outbound	4169263669	0	tunnel	dynamic	ESP

From operational mode, enter the `show services ipsec-vpn ipsec security-associations detail` command.

```
user@host> show services ipsec-vpn ipsec security-associations detail
```

```
Service set: ips_ssl, IKE Routing-instance: default
```

```
Rule: vpn_rule_ms_2_2_01, Term: term11, Tunnel index: 1
```

```
Local gateway: 10.0.1.2, Remote gateway: 192.0.2.0
```

```
IPSec inside interface: ms-2/2/0.1, Tunnel MTU: 1500
```

```
UDP encapsulate: Disabled, UDP Destination port: 0
```

```
Local identity: ipv4_subnet(any:0,[0..7]=80.0.0.0/16)
```

```
Remote identity: ipv4_subnet(any:0,[0..7]=30.0.0.0/16)
```

```
Direction: inbound, SPI: 3029124496, AUX-SPI: 0
```

```
Mode: tunnel, Type: dynamic, State: Installed
```

```
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
```

```
Soft lifetime: Expires in 840 seconds
```

```
Hard lifetime: Expires in 1273 seconds
```

```
Anti-replay service: Enabled, Replay window size: 4096
```

```
Copy ToS: Disabled, ToS value: 0
Copy TTL: Disabled, TTL value: 64

Direction: outbound, SPI: 4046774180, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 840 seconds
Hard lifetime: Expires in 1273 seconds
Anti-replay service: Enabled, Replay window size: 4096
Copy ToS: Disabled, ToS value: 0
Copy TTL: Disabled, TTL value: 64
```

Meaning

The output shows the ipsec security associations details.

RELATED DOCUMENTATION

| [Understanding Online Certificate Status Protocol and Certificate Revocation Lists](#) | 329

5

PART

Configuring Layer 2 Circuits

[Overview | 354](#)

[Layer 2 Circuits Configuration Overview | 356](#)

[Configuring Class of Service with Layer 2 Circuits | 378](#)

[Configuring Pseudowire Redundancy for Layer 2 Circuits | 385](#)

[Configuring Load Balancing for Layer 2 Circuits | 426](#)

[Configuring Protection Features for Layer 2 Circuits | 431](#)

[Monitoring Layer 2 Circuits with BFD | 481](#)

[Troubleshooting Layer 2 Circuits | 496](#)

Overview

IN THIS CHAPTER


- [Layer 2 Circuit Overview](#) | 354

Layer 2 Circuit Overview

A Layer 2 circuit is a point-to-point Layer 2 connection transported using Multiprotocol Label Switching (MPLS) or other tunneling technology on the service provider's network. A Layer 2 circuit is similar to a circuit cross-connect (CCC), except that multiple virtual circuits (VCs) are transported over a single shared label-switched path (LSP) tunnel between two provider edge (PE) routers. In contrast, each CCC requires a separate dedicated LSP.

The Junos OS implementation of Layer 2 circuits supports only the remote form of a Layer 2 circuit; that is, a connection from a local customer edge (CE) router to a remote CE router. [Figure 27 on page 354](#) illustrates the components of a Layer 2 circuit.

Figure 27: Components of a Layer 2 Circuit



To establish a Layer 2 circuit, the Label Distribution Protocol (LDP) is used as the signaling protocol to advertise the ingress label to the remote PE routers. For this purpose, a targeted remote LDP neighbor session is established using the extended discovery mechanism described in LDP, and the session is brought up to the remote PE loopback IP address. Because LDP looks at the Layer 2 circuit configuration and initiates extended neighbor discovery for all the Layer 2 circuit neighbors (the remote PEs), no new configuration is necessary in LDP. Each Layer 2 circuit is represented by the logical interface connecting the local PE router to the local customer edge (CE) router. Note that LDP must be enabled on the lo0.0 interface for extended neighbor discovery to function correctly.

Packets are sent to remote CE routers over an egress VPN label advertised by the remote PE router, using a targeted LDP session. The VPN label is sent over an LDP LSP to the remote PE router connected to the remote CE router. Return traffic from the remote CE router destined to the local CE router is sent using an ingress VPN label advertised by the local PE router, which is also sent over the LDP LSP to the local PE router from the remote PE router.

RELATED DOCUMENTATION

Understanding Layer 3 VPNs

[Layer 2 VPN Applications | 145](#)

[Applications for Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | 1323](#)

Applications for Interconnecting a Layer 2 Circuit with a Layer 3 VPN

[Example: Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | 1336](#)

Example: Interconnecting a Layer 2 Circuit with a Layer 3 VPN

[Example: Interconnecting a Layer 2 Circuit with a Layer 2 VPN | 1323](#)

Layer 2 Circuits Configuration Overview

IN THIS CHAPTER

- [Configuring Static Layer 2 Circuits | 356](#)
- [Configuring Local Interface Switching in Layer 2 Circuits | 357](#)
- [Configuring Interfaces for Layer 2 Circuits | 360](#)
- [Example: Configuring the Pseudowire Status TLV | 370](#)
- [Configuring Policies for Layer 2 Circuits | 373](#)
- [Configuring LDP for Layer 2 Circuits | 377](#)

Configuring Static Layer 2 Circuits

You can configure static Layer 2 circuit pseudowires. Static pseudowires are designed for networks that do not support LDP or do not have LDP enabled. You configure a static pseudowire by configuring static values for the in and out labels needed to enable a pseudowire connection. The `ignore-mtu-mismatch`, `ignore-vlan-id`, and `ignore-encapsulation-mismatch` statements are not relevant for static pseudowire configurations since the peer router cannot forward this information.

When you configure static pseudowires, you need to manually compare the encapsulation, TDM bit rate, and control word of the router with the remote peer router and ensure that they match, otherwise the static pseudowire might not work.

To configure static Layer 2 circuit pseudowires, include the `static` statement:

```
static {  
    incoming-label label;  
    outgoing-label label;  
    send-oam;  
}
```

For a list of hierarchy levels at which you can configure this statement, see the statement summary section for this statement.

You can configure a static pseudowire as a standalone Layer 2 circuit or in conjunction with a redundant pseudowire. You configure the static pseudowire statement at the [edit protocols l2circuit neighbor *address* interface *interface-name*] hierarchy level. You configure the redundant pseudowire at the [edit protocols l2circuit neighbor *address* interface *interface-name* backup-neighbor *neighbor*] hierarchy level. If you configure a static pseudowire to a neighbor and also configure a redundant pseudowire, the redundant pseudowire must also be static.

You can enable the ability to ping a static pseudowire by configuring the `send-oam` statement. This functionality applies to the backup neighbor as well. Once you have configured this statement, you can ping the static pseudowire by issuing the `ping mpls l2circuit` command.

For information about how to configure redundant pseudowires, see ["Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS" on page 226](#).

RELATED DOCUMENTATION

[Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS | 226](#)

`ping mpls l2circuit`

Configuring Local Interface Switching in Layer 2 Circuits

IN THIS SECTION

- [Configuring the Interfaces for the Local Interface Switch | 358](#)
- [Enabling Local Interface Switching When the MTU Does Not Match | 359](#)

You can configure a virtual circuit entirely on the local router, terminating the circuit on a local interface. Possible uses for this feature include being able to enable switching between Frame Relay DLCIs.

To configure a virtual circuit to terminate locally, include the `local-switching` statement:

```
local-switching {
  interface interface-name {
    description text;
    end-interface {
      interface interface-name;
```



```

        no-revert;
        protect-interface interface-name;
    }
    ignore-mtu-mismatch;
    no-revert;
    protect-interface interface-name;
}
}

```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit]
- [edit logical-systems *logical-system-name* protocols l2circuit]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy level.

The following sections describe how to configure local interface switching:

Configuring the Interfaces for the Local Interface Switch

Local interface switching requires you to configure at least two interfaces:

- **Starting interface**—Include the `interface` statement at the [edit protocols l2circuit local-switching] hierarchy level.
- **Ending interface**—Include the `end-interface` statement at the [edit protocols l2circuit local-switching interface *interface-name*] hierarchy level.

You can also configure virtual circuit interface protection for each local interface:

- **Protect interface for the starting interface**—Include the `protect-interface` statement at the [edit protocols l2circuit local-switching interface *interface-name*] hierarchy level.
- **Protect interface for the ending interface**—Include the `protect-interface` statement at the [edit protocols l2circuit local-switching interface *interface-name* end-interface] hierarchy level.

For more information about how to configure protect interfaces, see ["Configuring the Protect Interface" on page 365](#).

Typically, when the primary interface goes down, the pseudowire starts using the protect interface. By default, when the primary interface comes back online, the interface is switched-over back from the protect interface to the primary interface. To prevent the switchover back to the primary interface,

unless the primary interface goes down, include the `no-revert` statement. This prevents loss of traffic during the switchover.

NOTE: If the protect interface fails, the interface is switched-over back to the primary interface, irrespective of whether or not the `no-revert` statement is included in the configuration.

You can configure the `no-revert` statement both for the starting interface and the ending interface.

```
[edit protocols l2circuit local-switching interface interface-name]
no-revert;
end-interface {
    interface interface-name;
    no-revert;
}
```

NOTE: The protect interface must be configured prior to configuring the `no-revert` statement.

Enabling Local Interface Switching When the MTU Does Not Match

You can configure a local switching interface to ignore the MTU configuration set for the associated physical interface. This enables you to bring up a circuit between two logical interfaces that are defined on physical interfaces with different MTU values.

To configure the local switching interface to ignore the MTU configured for the physical interface, include the `ignore-mtu-mismatch` statement:

```
ignore-mtu-mismatch;
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit local-switching interface *interface-name*]
- [edit logical-systems *logical-system-name* protocols l2circuit local-switching interface *interface-name*]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy level.

Configuring Interfaces for Layer 2 Circuits

IN THIS SECTION

- [Configuring the Address for the Neighbor of the Layer 2 Circuit | 360](#)
- [Configuring the Neighbor Interface for the Layer 2 Circuit | 361](#)
- [Configuring the Interface Encapsulation Type for Layer 2 Circuits | 369](#)
- [Configuring ATM2 IQ Interfaces for Layer 2 Circuits | 369](#)

The following sections describe how to configure interfaces for Layer 2 circuits:

NOTE: Not all subtasks are supported on all platforms; check the CLI on your device.

Configuring the Address for the Neighbor of the Layer 2 Circuit

All the Layer 2 circuits using a particular remote PE router designated for remote CE routers are listed under the `neighbor` statement (“neighbor” designates the PE router). Each neighbor is identified by its IP address and is usually the end-point destination for the label-switched path (LSP) tunnel transporting the Layer 2 circuit.

To configure a PE router as a neighbor for a Layer 2 circuit, specify the neighbor address using the `neighbor` statement:

```
neighbor address {  
    ...  
}
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit]
- [edit logical-systems *logical-system-name* protocols l2circuit]

Configuring the Neighbor Interface for the Layer 2 Circuit

Each Layer 2 circuit is represented by the logical interface *encapsulation* connecting the local provider edge (PE) router to the local customer edge (CE) router. This interface is tied to the Layer 2 circuit neighbor configured in ["Configuring the Address for the Neighbor of the Layer 2 Circuit" on page 360](#).

To configure the interface for a Layer 2 circuit neighbor, include the interface statement:

NOTE: The commit operation fails, if the same logical interface is configured for both Layer 2 circuit and ccc connection.

NOTE: On the EX9200 switches, replace *encapsulation-type* with the *encapsulation* statement.

```
interface interface-name {
    bandwidth (bandwidth | ctnumber bandwidth);
    community community-name;
    (control-word | no-control-word);
    description text;
    encapsulation-type type;
    ignore-encapsulation-mismatch;
    ignore-mtu-mismatch;
    mtu mtu-number;
    no-revert;
    protect-interface interface-name;
    pseudowire-status-tlv;
    psn-tunnel-endpoint address;
    virtual-circuit-id identifier;
}
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit neighbor *address*]
- [edit logical-systems *logical-system-name* protocols l2circuit neighbor *address*]

The following sections describe how to configure the interface for the Layer 2 circuit neighbor:

Configuring a Community for the Layer 2 Circuit

To configure a community for a Layer 2 circuit, include the `community` statement:

```
community community-name;
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit neighbor *address* interface *interface-name*]
- [edit logical-systems *logical-system-name* protocols l2circuit neighbor *address* interface *interface-name*]

For information about how to configure a routing policy for a Layer 2 circuit, see ["Configuring Policies for Layer 2 Circuits" on page 373](#).

Configuring the Control Word for Layer 2 Circuits

To emulate the virtual circuit (VC) encapsulation for Layer 2 circuits, a 4-byte control word is added between the Layer 2 protocol data unit (PDU) being transported and the VC label that is used for demultiplexing. For most protocols, a null control word consisting of all zeroes is sent between Layer 2 circuit neighbors.

However, individual bits are available in a control word that can carry Layer 2 protocol control information. The control information is mapped into the control word, which allows the header of a Layer 2 protocol to be stripped from the frame. The remaining data and control word can be sent over the Layer 2 circuit, and the frame can be reassembled with the proper control information at the egress point of the circuit.

The following Layer 2 protocols map Layer 2 control information into special bit fields in the control word:

- Frame Relay—The control word supports the transport of discard eligible (DE), forward explicit congestion notification (FECN), and backward explicit congestion notification (BECN) information. For configuration information, see ["Configuring the Control Word for Frame Relay Interfaces" on page 363](#).

NOTE: Frame Relay is not supported on the ACX Series routers.

- ATM AAL5 mode—The control word supports the transport of sequence number processing, ATM cell loss priority (CLP), and explicit forward congestion indication (EFCI) information. When you configure an AAL5 mode Layer 2 circuit, the control information is carried by default and no additional configuration is needed.

- ATM cell-relay mode—The control word supports sequence number processing only. When you configure a cell-relay mode Layer 2 circuit, the sequence number information is carried by default and no additional configuration is needed.

The Junos OS implementation of sequence number processing for ATM cell-relay mode and AAL5 mode is not the same as that described in Sec. 3.1.2 of the IETF draft *Encapsulation Methods for Transport of Layer 2 Frames Over IP and MPLS Networks*. The differences are as follows:

- A packet with a sequence number of 0 is considered as out of sequence.
- A packet that does not have the next incremental sequence number is considered out of sequence.
- When out-of-sequence packets arrive, the sequence number in the Layer 2 circuit control word increments by one and becomes the expected sequence number for the neighbor.

The following sections discuss how to configure the control word for Layer 2 circuits:

Configuring the Control Word for Frame Relay Interfaces

On interfaces with Frame Relay CCC encapsulation, you can configure Frame Relay control bit translation to support Frame Relay services over IP and MPLS backbones by using CCC, Layer 2 VPNs, and Layer 2 circuits. When you configure translation of Frame Relay control bits, the bits are mapped into the Layer 2 circuit control word and preserved across the IP or MPLS backbone.

For information about how to configure the control bits, see the [Configuring Frame Relay Control Bit Translation](#).

Disabling the Control Word for Layer 2 Circuits

The Junos OS can typically determine whether a neighboring router supports the control word. However, if you want to explicitly disable its use on a specific interface, include the `no-control-word` statement:

```
no-control-word;
```

For a list of hierarchy levels at which you can configure this statement, see the statement summary section for this statement.

Configuring the Encapsulation Type for the Layer 2 Circuit Neighbor Interface

You can specify the Layer 2 circuit encapsulation type for the interface receiving traffic from a Layer 2 circuit neighbor. The encapsulation type is carried in the LDP-signaling messages exchanged between Layer 2 circuit neighbors when pseudowires are created. The encapsulation type you configure for each Layer 2 circuit neighbor varies depending on the type of networking equipment or the type of Layer 2

protocol you have deployed in your network. If you do not specify an encapsulation type for the Layer 2 circuit, the encapsulation of the CE device interface is used by default.

Specify the encapsulation type for the Layer 2 circuit neighbor interface by including the `encapsulation-type` statement:

```
encapsulation-type (atm-aal5 | atm-cell | atm-cell-port-mode | atm-cell-vc-mode | atm-cell-vp-mode
| cesop | cisco-hdlc | ethernet | ethernet-vlan | frame-relay | frame-relay-port-mode |
interworking | ppp | satop-e1 | satop-e3 | satop-t1 | satop-t3);
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit neighbor *address* interface *interface-name*]
- [edit logical-systems *logical-system-name* protocols l2circuit neighbor *address* interface *interface-name*]

Enabling the Layer 2 Circuit When the Encapsulation Does Not Match

You can configure the Junos OS to allow a Layer 2 circuit to be established even though the encapsulation configured on the CE device interface does not match the encapsulation configured on the Layer 2 circuit interface by including the `ignore-encapsulation-mismatch` statement. You can configure the `ignore-encapsulation-mismatch` statement for the connection to the remote connection by including the statement at the [edit protocols l2circuit neighbor *address* interface *interface-name*] hierarchy level or for the local connection by including this statement at the [edit protocols l2circuit local-switching interface *interface-name*] hierarchy level.

```
ignore-encapsulation-mismatch;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

Configuring the MTU Advertised for a Layer 2 Circuit

By default, the MTU used to advertise a Layer 2 circuit is determined by taking the interface MTU for the associated physical interface and subtracting the encapsulation overhead for sending IP packets based on the encapsulation.

However, encapsulations that support multiple logical interfaces (and multiple Layer 2 circuits) rely on the same interface MTU (since they are all associated with the same physical interface). This can prove to be a limitation for VLAN Layer 2 circuits using the same Ethernet interface or for Layer 2 circuit DLCIs using the same Frame Relay interface.

This can also affect multivendor environments. For example, if you have three PE devices supplied by different vendors and one of the devices only supports an MTU of 1500, even if the other devices support larger MTUs you must to configure the MTU as 1500 (the smallest MTU of the three PE devices).

You can explicitly configure which MTU is advertised for a Layer 2 circuit, even if the Layer 2 circuit is sharing a physical interface with other Layer 2 circuits. When you explicitly configure an MTU for a Layer 2 circuit, be aware of the following:

- An explicitly configured MTU is signaled to the remote PE device. The configured MTU is also compared to the MTU received from the remote PE device. If there is a conflict, the Layer 2 circuit is taken down.
- If you configure an MTU for an ATM cell relay interface on an ATM II PIC, the configured MTU is used to compute the cell bundle size advertised for that Layer 2 circuit, instead of the default interface MTU.
- A configured MTU is used only in the control plane. It is not enforced in the data plane. You need to ensure that the CE device for a given Layer 2 circuit uses the correct MTU for data transmission.

To configure the MTU for a Layer 2 circuit, include the `mtu` statement at the `[edit protocols l2circuit neighbor address interface interface-name]` hierarchy level.

```
mtu mtu-number;
```

Enabling the Layer 2 Circuit When the MTU Does Not Match

You can configure the Junos OS to allow a Layer 2 circuit to be established even though the MTU configured on the PE router does not match the MTU configured on the remote PE router by including the `ignore-mtu-mismatch` statement at the `[edit protocols l2circuit neighbor address interface interface-name]` hierarchy level.

Configuring the Protect Interface

You can configure a protect interface for the logical interface linking a virtual circuit to its destination, whether the destination is remote or local. A protect interface provides a backup for the protected interface in case of failure. Network traffic uses the primary interface only so long as the primary interface functions. If the primary interface fails, traffic is switched to the protect interface. The protect interface is optional.

To configure the protect interface, include the `protect-interface` statement:

```
protect-interface interface-name;
```

NOTE: The protect interface must be configured prior to configuring the `no-revert` statement.

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

For an example of how to configure a protect interface for a Layer 2 circuit, see ["Example: Configuring Layer 2 Circuit Protect Interfaces" on page 454](#).

Configuring the Protect Interface From Switching Over to the Primary Interface

Typically, when the primary interface goes down, the pseudowire starts using the protect interface. By default, when the primary interface comes back online, the interface is switched-over back from the protect interface to the primary interface. To prevent the switchover back to the primary interface, unless the protect interface goes down, include the `no-revert` statement. This prevents loss of traffic during the switchover.

NOTE: If the protect interface fails, the interface is switched-over back to the primary interface, irrespective of whether or not the `no-revert` statement is included in the configuration.

You can configure the `no-revert` statement at the `[edit protocols l2circuit neighbor address interface interface-name]` hierarchy level:

```
[edit protocols l2circuit neighbor address interface interface-name]
no-revert;
```

Configuring the Pseudowire Status TLV

The pseudowire status type length variable (TLV) is used to communicate the status of a pseudowire back and forth between two PE routers. For Layer 2 circuit configurations, you can configure the PE router to negotiate the pseudowire with its neighbor using the pseudowire status TLV. This same functionality is also available for LDP VPLS neighbor configurations. The pseudowire status TLV is configurable for each pseudowire connection and is disabled by default. The pseudowire status

negotiation process assures that a PE router reverts back to the label withdraw method for pseudowire status if its remote PE router neighbor does not support the pseudowire status TLV.

Unlike the control word, a PE router's ability to support the pseudowire status TLV is communicated when the initial label mapping message is sent to its remote PE router. Once the PE router transmits its support for the pseudowire status TLV to its remote PE router, it includes the pseudowire status TLV in every label mapping message sent to the remote PE router. If you disable support for the pseudowire status TLV on the PE router, a label withdraw message is sent to the remote PE router and then a new label mapping message without the pseudowire status TLV follows.

To configure the pseudowire status TLV for the pseudowire to the neighbor PE router, include the `pseudowire-status-tlv` statement:

```
pseudowire-status-tlv;
```

For a list of the hierarchy levels at which you can include this statement, see the statement summary section for this statement.

Configuring Layer 2 Circuits over Both RSVP and LDP LSPs

You can configure two Layer 2 circuits between the same two routers, and have one Layer 2 circuit traverse an RSVP LSP and the other traverse an LDP LSP. To accomplish this, you need to configure two loopback addresses on the local router. You configure one of the loopback address for the Layer 2 circuit traversing the RSVP LSP. You configure the other loopback address to handle the Layer 2 circuit traversing the LDP LSP. For information about how to configure multiple loop back interfaces, see *Configuring Logical Units on the Loopback Interface for Routing Instances in Layer 3 VPNs*.

You also need to configure a packet switched network (PSN) tunnel endpoint for one of the Layer 2 circuits. It can be either the Layer 2 circuit traversing the RSVP LSP or the one traversing the LDP LSP. The PSN tunnel endpoint address is the destination address for the LSP on the remote router.

To configure the address for the PSN tunnel endpoint, include the `psn-tunnel-endpoint` statement:

```
psn-tunnel-endpoint address;
```

You can include this statement at the following hierarchy levels:

- [edit logical-systems *logical-system-name* protocols l2circuit neighbor *address* interface *interface-name*]
- [edit protocols l2circuit neighbor *address* interface *interface-name*]

By default, the PSN tunnel endpoint for a Layer 2 circuit is identical to the neighbor address, which is also the same as the LDP neighbor address.

The tunnel endpoints on the remote router do not need to be loopback addresses.

Example: PSN Tunnel Endpoint

The following example illustrates how you might configure a PSN tunnel endpoint:

```
[edit protocols l2circuit]
neighbor 10.255.0.6 {
  interface t1-0/2/2.0 {
    psn-tunnel-endpoint 192.0.2.0;
    virtual-circuit-id 1;
  }
  interface t1-0/2/1.0 {
    virtual-circuit-id 10;
  }
}
```

The Layer 2 circuit configured for the t1-0/2/2.0 interface resolves in the inet3 routing table to 192.0.2.0. This could be either an RSVP route or a static route with an LSP next hop.

Configuring the Virtual Circuit ID

You configure a virtual circuit ID on each interface. Each virtual circuit ID uniquely identifies the Layer 2 circuit among all the Layer 2 circuits to a specific neighbor. The key to identifying a particular Layer 2 circuit on a PE router is the neighbor address and the virtual circuit ID. An LDP-FEC-to-label binding is associated with a Layer 2 circuit based on the virtual circuit ID in the FEC and the neighbor that sent this binding. The LDP-FEC-to-label binding enables the dissemination of the VPN label used for sending traffic on that Layer 2 circuit to the remote CE device.

You also configure a virtual circuit ID for each redundant pseudowire. A redundant pseudowire is identified by the backup neighbor address and the virtual circuit ID. For more information, see ["Configuring Pseudowire Redundancy on the PE Router" on page 226](#).

To configure the virtual circuit ID, include the `virtual-circuit-id` statement:

```
virtual-circuit-id identifier;
```

For a list of hierarchy levels at which you can include this statement, see the statement summary section for this statement.

Configuring the Interface Encapsulation Type for Layer 2 Circuits

The Layer 2 encapsulation type is carried in the LDP forwarding equivalence class (FEC). You can configure either circuit cross-connect (CCC) or translational cross-connect (TCC) encapsulation types for Layer 2 circuits. For more information, see the [MPLS Applications User Guide](#) and [Junos OS Network Interfaces Library for Routing Devices](#).

NOTE: Some platform and FPC combinations can not pass TCC encapsulated ISO traffic. See [Platforms/FPCs That Cannot Forward TCC Encapsulated ISO Traffic](#) for details.

To configure the interface encapsulation for a Layer 2 circuit, include the encapsulation statement:

```
encapsulation encapsulation;
```

You can include this statement at the following hierarchy levels:

- [edit interfaces *interface-name*]
- [edit logical-systems *logical-system-name* interfaces *interface-name*]

Configuring ATM2 IQ Interfaces for Layer 2 Circuits

You can configure Asynchronous Transfer Mode 2 (ATM2) intelligent queuing (IQ) interfaces for Layer 2 circuits by using Layer 2 circuit ATM Adaptation Layer 5 (AAL5) transport mode, Layer 2 circuit ATM cell relay mode, and the Layer 2 circuit ATM trunk mode.

The configuration statements are as follows:

- atm-l2circuit-mode aal5
- atm-l2circuit-mode cell
- atm-l2circuit-mode trunk

For more information about these statements, see the [Junos OS Administration Library](#). For more information about how to configure ATM2 IQ interfaces, see the [Junos OS Network Interfaces Library for Routing Devices](#).

The Junos OS implementation of sequence number processing for Layer 2 circuit ATM cell relay mode and Layer 2 circuit AAL5 mode differs from that described in the Internet draft draft-martini-l2circuit-encap-mpls-11.txt, *Encapsulation Methods for Transport of Layer 2 Frames over MPLS Networks* (expires August 2006).

The Junos OS implementation has the following differences:

1. A packet with a sequence number of 0 is treated as out of sequence.
2. A packet that does not have the next incremental sequence number is considered out of sequence.

When out-of-sequence packets arrive, the expected sequence number for the neighbor is set to the sequence number in the Layer 2 circuit control word.

Example: Configuring the Pseudowire Status TLV

IN THIS SECTION

- [Requirements | 370](#)
- [Overview | 370](#)
- [Configuration | 370](#)

Requirements

The following is a list of the hardware and software requirements for this configuration.

- One ACX Series Universal Metro router
- Junos OS Release 12.2 or later

Overview

The configuration shown here is the base configuration of a pseudowire with pseudowire-status-tlv enabled. The pseudowire-status-tlv is used to communicate the status of a pseudowire between PE routers.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 371](#)
- [Configuring the Pseudowire Status TLV | 371](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them in a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level:

```
edit protocols l2circuit
set neighbor 10.255.64.26
set neighbor 10.255.64.26 interface xe-0/0/0
set neighbor 10.255.64.26 interface xe-0/0/0 pseudowire-status-tlv
set neighbor 10.255.64.26 interface xe-0/0/0 virtual-circuit-id 1024
```

Configuring the Pseudowire Status TLV

Step-by-Step Procedure

1. Navigate to the [edit protocols l2circuit] hierarchy level to configure Layer 2 circuits over MPLS.

```
[edit]
user@host# edit protocols l2circuit
```

2. Set the address for the neighbor provider edge router; this example uses a fictitious address, **10.255.64.26**.

```
[edit protocols l2circuit]
user@host# set neighbor 10.255.64.26
```

3. Specify the name of the interface forming the Layer 2 circuit; this example uses **xe-0/0/0**.

```
[edit protocols l2circuit]
user@host# set neighbor 10.255.64.26 interface xe-0/0/0
```

4. Enter the **pseudowire-status-tlv** statement.

```
[edit protocols l2circuit]
user@host# set neighbor 10.255.64.26 interface xe-0/0/0 pseudowire-status-tlv
```

NOTE: You need to configure the **virtual-circuit-id** statement in order for **pseudowire-status-tlv** to work.

5. Set the **virtual-circuit-id** statement to identify the pseudowire as regular or redundant. The identifier value can range from 1 through 4,294,967,295.

```
[edit protocols l2circuit]
user@host# set neighbor 10.255.64.26 interface xe-0/0/0 virtual-circuit-id 1024
```

6. Check your configuration by entering the **show** command.

Results

```
[edit protocols l2circuit]
user@host# show
neighbor 10.255.64.26 {
  interface xe-0-0-0 {
    virtual-circuit-id 1024;
    pseudowire-status-tlv;
  }
}
```

RELATED DOCUMENTATION

[Pseudowire Overview for ACX Series Universal Metro Routers](#)
[Configuring the Pseudowire Status TLV](#)

Configuring Policies for Layer 2 Circuits

IN THIS SECTION

- [Configuring the Layer 2 Circuit Community | 373](#)
- [Configuring the Policy Statement for the Layer 2 Circuit Community | 374](#)
- [Verifying the Layer 2 Circuit Policy Configuration | 376](#)

You can configure Junos routing policies to control the flow of packets over Layer 2 circuits. This capability allows you to provide different level of service over a set of equal-cost Layer 2 circuits. For example, you can configure a circuit for high-priority traffic, a circuit for average-priority traffic, and a circuit for low-priority traffic. By configuring Layer 2 circuit policies, you can ensure that higher-value traffic has a greater likelihood of reaching its destination.

The following sections explain how to configure Layer 2 circuit policies:

Configuring the Layer 2 Circuit Community

To configure a community for Layer 2 circuits, include the `community` statement.

```
community community-name {
    members [ community-ids ];
}
```

You can include this statement at the following hierarchy levels:

- [edit policy-options]
- [edit logical-systems *logical-system-name* policy-options]

name identifies the community or communities.

community-ids identifies the type of community or extended community:

- A normal community uses the following community ID format:

as-number.community-value

as-number is the autonomous system (AS) number of the community member.

community-value is the identifier of the community member. It can be a number from 0 through 65,535.

- An extended community uses the following community ID format:

type.administrator.assigned-number

type is the type of target community. The target community identifies the route's destination.

administrator is either an AS number or an IP version 4 (IPv4) address prefix, depending on the type of community.

assigned-number identifies the local provider.

You also need to configure the community for the Layer 2 circuit interface; see ["Configuring a Community for the Layer 2 Circuit" on page 362](#).

Configuring the Policy Statement for the Layer 2 Circuit Community

To configure a policy to send community traffic over a specific LSP, include the `policy-statement` statement:

```
policy-statement policy-name {
  term term-name {
    from community community-name;
    then {
      install-nexthop (except | lsp lsp-name | lsp-regex lsp-regular-expression);
      accept;
    }
  }
}
```

You can include this statement at the following hierarchy levels:

- [edit `policy-options`]
- [edit `logical-systems logical-system-name policy-options`]

To prevent the installation of any matching next hops, include the `install-nexthop` statement with the `except` option:

```
install-nexthop except;
```

You can include this statement at the following hierarchy levels:

- [edit `policy-options policy-statement policy-name term term-name then`]

- [edit logical-systems *logical-system-name* policy-options policy-statement *policy-name* term *term-name* then]

To assign traffic from a community to a specific LSP, include the `install-nexthop` statement with the `lsp` *lsp-name* option and the `accept` statement:

```
install-nexthop lsp lsp-name;
accept;
```

You can include these statements at the following hierarchy levels:

- [edit policy-options policy-statement *policy-name* term *term-name* then]
- [edit logical-systems *logical-system-name* policy-options policy-statement *policy-name* term *term-name* then]

You can also use a regular expression to select an LSP from a set of similarly named LSPs for the `install-nexthop` statement. To configure a regular expression, include the `install-nexthop` statement with the `lsp-regex` option and the `accept` statement:

```
install-nexthop lsp-regex lsp-regular-expression;
accept;
```

You can include these statements at the following hierarchy levels:

- [edit policy-options policy-statement *policy-name* term *term-name* then]
- [edit logical-systems *logical-system-name* policy-options policy-statement *policy-name* term *term-name* then]

Example: Configuring a Policy for a Layer 2 Circuit Community

The following example illustrates how you might configure a regular expression in a Layer 2 circuit policy. You create three LSPs to handle gold-tier traffic from a Layer 2 circuit. The LSPs are named `alpha-gold`, `beta-gold`, and `delta-gold`. You then include the `install-nexthop` statement with the `lsp-regex` option with the LSP regular expression `.*-gold` at the [edit policy-options policy-statement *policy-name* term *term-name* then] hierarchy level:

```
[edit policy-options]
policy-statement gold-traffic {
  term to-gold-LSPs {
    from community gold;
    then {
      install-nexthop lsp-regex .*-gold;
      accept;
```

```

    }
  }
}

```

The community gold Layer 2 circuits can now use any of the -gold LSPs. Given equal utilization across the three -gold LSPs, LSP selection is made at random.

You need to apply the policy to the forwarding table. To apply a policy to the forwarding table, configure the export statement at the [edit routing-options forwarding-table] hierarchy level:

```

[edit routing-options forwarding-table]
export policy-name;

```

Verifying the Layer 2 Circuit Policy Configuration

To verify that you have configured a policy for the Layer 2 circuit, issue the `show route table mpls detail` command. It should display the community for ingress routes that corresponds to the Layer 2 circuits, as shown by the following example:

```

user@host> show route table mpls detail
so-1/0/1.0 (1 entry, 1 announced)
*L2VPN Preference: 7
Next hop: via so-1/0/0.0 weight 1, selected
Label-switched-path to-community-gold
Label operation: Push 100000 Offset: -4
Next hop: via so-1/0/0.0 weight 1
Label-switched-path to-community-silver
Label operation: Push 100000 Offset: -4
Protocol next hop: 10.255.245.45
Push 100000 Offset: -4
Indirect next hop: 85333f0 314
State: <Active Int>
Local AS: 100
Age: 22
Task: Common L2 VC
Announcement bits (2): 0-KRT 1-Common L2 VC
AS path: I
Communities: 100:1

```

For more information about how to configure routing policies, see [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

Configuring LDP for Layer 2 Circuits

Use LDP as the signaling protocol to advertise ingress labels to the remote PE routers. When configured, LDP examines the Layer 2 circuit configuration and initiates extended neighbor discovery for all the Layer 2 circuit neighbors (for example, remote PEs). This process is similar to how LDP works when tunneled over RSVP. You must run LDP on the `lo0.0` interface for extended neighbor discovery to function correctly.

For detailed information about how to configure LDP, see the [MPLS Applications User Guide](#).

Configuring Class of Service with Layer 2 Circuits

IN THIS CHAPTER


- [Configuring ATM Trunking on Layer 2 Circuits | 378](#)
- [Layer 2 Circuit Bandwidth Accounting and Call Admission Control | 380](#)
- [Configuring Bandwidth Allocation and Call Admission Control in Layer 2 Circuits | 383](#)

Configuring ATM Trunking on Layer 2 Circuits

You can configure Layer 2 circuits to transport ATM traffic from directly connected ATM switches across an MPLS core network. Traffic from an ATM switch is received on the local PE router. The ATM cells are given an MPLS label and then sent across the MPLS network to the remote PE router. The receiving router removes the MPLS label from the ATM cell and then forwards the cell the receiving ATM switch.

NOTE: ATM trunking on Layer 2 circuits is supported only on T Series and M320 routers and ATM2 IQ PICs.

Figure 28: ATM Trunking on Layer 2 Circuits



[Figure 28 on page 378](#) illustrates how ATM switches could be linked together by a Layer 2 circuit. The PE1 Router is configured to receive ATM trunk traffic from ATM Switch 1. As each ATM cell is received on the PE1 Router, it is classified by means of the class-of-service (CoS) information in the cell header and then encapsulated as a labeled packet. The CoS information and cell loss priority (CLP) of the ATM cell are copied into the experimental (EXP) bits of the MPLS label. The labeled packet is then transported across the service provider network to the PE2 Router by means of a Layer 2 circuit.

On the PE2 Router, the label is removed and the plain ATM cell is forwarded to ATM Switch 2. The CoS and CLP are extracted from the EXP bits and are then used to select the correct output queue and determine whether the ATM cell should be dropped.

The ATM physical port on the router can support 32 logical trunks when network-to-network interface (NNI) is used and 8 logical trunks when user-to-network interface (UNI) is used. A trunk can carry traffic on 32 virtual path identifiers (VPIs), numbered 0 through 31. Each ATM trunk is associated with an MPLS label and a logical interface. On the ingress router, one or more of these trunks are mapped to a Layer 2 circuit.

The configuration for the Layer 2 circuit between PE routers is conventional. Follow the procedures outlined in this chapter for configuring the circuit. However, there is some specific configuration you need to complete for the Layer 2 circuit to carry traffic from an ATM trunk.

First, enable ATM trunking for Layer 2 circuits. To enable ATM trunking for Layer 2 circuits, specify the trunk option for the `atm-l2circuit-mode` statement at the `[edit chassis fpc number pic number]` hierarchy level:

```
[edit chassis fpc number pic number]  
atm-l2circuit-mode trunk (uni | nni);
```

Specify the `uni` option for UNI trunks and the `nni` option for NNI trunks. The default option is `uni`.

You also need to configure each ATM trunk for a specific logical interface. Each ATM trunk has a trunk identifier in the range from 0 to 31. This configuration step is in addition to the typical configuration steps you follow related to configuring interfaces for Layer 2 circuits, as described in ["Configuring Interfaces for Layer 2 Circuits" on page 360](#).

To associate a specific trunk identifier with a logical interface, include the `trunk-id` statement:

```
trunk-id number;
```

You can include this statement at the following hierarchy levels:

- `[edit interfaces interface-name unit number]`
- `[edit logical-systems logical-system-name interfaces interface-name unit number]`

Since ATM trunking is supported on ATM2 IQ PICs only, the only value you can configure for the `pic-type` statement is `atm2`. If you do not configure the `pic-type` statement but you do configure the `trunk` option for the `atm-l2circuit-mode` statement (at the `[chassis fpc number pic number]` hierarchy level), the `pic-type` statement defaults to `atm2`.

Layer 2 Circuit Bandwidth Accounting and Call Admission Control

IN THIS SECTION

- [Bandwidth Accounting and Call Admission Control Overview | 380](#)
- [Selecting an LSP Based on the Bandwidth Constraint | 381](#)
- [LSP Path Protection and CAC | 381](#)
- [Layer 2 Circuits Trunk Mode | 383](#)

The sections that follow discuss Layer 2 circuit bandwidth accounting and call admission control (CAC):

Bandwidth Accounting and Call Admission Control Overview

Some network environments require that a certain level of service be guaranteed across the entire length of a path transiting a service provider's network. For Layer 2 circuits transiting an MPLS core network, a customer requirement might be to assure that guarantees for bandwidth and *class of service* (CoS) be maintained across the core network. For example, an Asynchronous Transfer Mode (ATM) circuit can provide service guarantees for each traffic class. A Layer 2 circuit configured to transport that ATM circuit across the network could be expected to provide the same service guarantees.

Providing this type of service guarantee requires the following:

- The LSPs in the MPLS core network must be able to provide service guarantees for bandwidth, rerouting, and route failures. You accomplish these guarantees by configuring multiclass LSPs. For more information about multiclass LSPs, see [Configuring Multiclass LSPs](#).
- The service guarantee must be maintained across the entire length of the link as it transits the service provider's network. Different Layer 2 circuits could have different bandwidth requirements. However, many Layer 2 circuits could be transported over the same E-LSP in the MPLS core network.

- CAC ensures that the LSP has sufficient bandwidth to accommodate the Layer 2 circuit. If there is not enough bandwidth over a particular LSP, the Layer 2 circuit is prevented from using that LSP.

Selecting an LSP Based on the Bandwidth Constraint

CAC of Layer 2 circuits is based on the bandwidth constraint. You must configure this constraint for each Layer 2 circuit interface. If there is a bandwidth constraint configured for a Layer 2 circuit, CAC bases the final selection of which LSP-forwarding next hop to use on the following:

- If multiple LSPs meet the bandwidth requirements, the first LSP found that can satisfy the bandwidth requirements for the Layer 2 circuit is selected.
- If there is more than one next hop mapped to the same LSP, then all the next hops that map to that LSP and pass CAC constraints are installed. This allows the Layer 2 circuit routes to restore themselves quickly in case of failure.
- The available bandwidth on the selected LSP is decremented by the bandwidth required for each Layer 2 circuit. Similarly, when the Layer 2 circuit route is changed or deleted (for example, when the route is disassociated from that particular LSP), the bandwidth on the corresponding LSP is incremented.
- There are no priorities among different Layer 2 circuits competing for the same LSP next hop in the core network.
- When an LSP's bandwidth changes, the Layer 2 circuits using that LSP repeat the CAC process again.

If the LSP bandwidth increases, some Layer 2 circuits that were not established might now successfully resolve over the LSP. Similarly, if the bandwidth of the LSP decreases, some Layer 2 circuits that were previously up might now be declared down because of insufficient bandwidth on the LSP.

- When no LSP is found to meet the bandwidth requirements of the Layer 2 circuit, it is considered to be a CAC failure, and an error is reported.

LSP Path Protection and CAC

CAC can take into account LSPs that have been configured with an MPLS path protection feature, such as secondary paths, fast reroute, or node and link protection. CAC can consider the bandwidth available on these auxiliary links and can accept the backup connection as valid if the main connection fails. However, there are limitations on how the path protection feature must be configured to prevent CAC from taking down the Layer 2 circuit when the LSP it is using is switched to a backup route.

For more information about MPLS path protection features, see the [MPLS and Traffic Protection](#).

The sections that follow discuss the path protection features that can be used in conjunction with CAC and how they must be configured:

Secondary Paths and CAC

The following describes the ways in which secondary paths would interact with Layer 2 circuit CAC:

- If an LSP is configured with both primary and secondary paths, if the paths have the same bandwidth, and if this bandwidth is enough to accommodate the Layer 2 circuit, the Layer 2 circuit route installs both next hops in the forwarding table.

CAC allows the Layer 2 circuit to be switched to the secondary path if the primary path fails.

- If the LSP has primary and secondary paths configured with different bandwidths, each path must run through CAC independently. If the active path for that LSP passes CAC constraints successfully, then that next hop is installed and the corresponding LSP is selected to transport the Layer 2 circuit traffic. The LSP's secondary paths are then checked for CAC, and installed if there is sufficient bandwidth.

However, if the active path for the LSP fails to meet the CAC constraints, then that LSP is not selected and the system looks for a different LSP to transport the Layer 2 circuit.

For example, an LSP has an active primary path with 30 megabits of bandwidth and a secondary path with 10 megabits of bandwidth. The Layer 2 circuit requires 15 megabits of bandwidth. The secondary path fails CAC, and only the next hop corresponding to the primary path is installed for the Layer 2 circuit route. The path protection originally provided by the secondary path is no longer available.

Fast Reroute and CAC

No CAC is done for fast reroute detours. However, as long as the protected path satisfies the CAC bandwidth constraints, the detour next hop is also selected and installed.

Link and Node Protection and CAC

You can configure CAC on Layer 2 circuit-based LSPs with bandwidth constraints and also enable link and node protection. However, if the primary LSP fails, CAC might not be applied to the bypass LSP, meaning the bypass LSP might not meet the bandwidth constraint for the Layer 2 circuit. To minimize the risk of losing traffic, the Layer 2 circuit continues to use the non-CAC bypass LSP while an attempt is made to establish a new Layer 2 circuit route over an LSP that does support CAC.

Layer 2 Circuits Trunk Mode

Using Layer 2 circuit trunk mode, you can configure Layer 2 circuits to carry ATM trunks, providing a way to link ATM switches over an MPLS core network.

Layer 2 circuit trunk mode allows you to configure the following CoS features:

- CoS queues in Layer 2 circuit trunk mode—For ATM2 IQ interfaces, you can configure ATM CoS queues for Layer 2 circuit trunk mode.
- Layer 2 circuit trunk mode scheduling—For ATM2 IQ interfaces configured to use Layer 2 circuit trunk mode, you can share a scheduler among 32 trunks on an ATM port.
- Two early packet discard (EPD) thresholds per queue—For ATM2 IQ interfaces configured to use Layer 2 circuit trunk mode, you can set two EPD thresholds that depend on the packet-loss priorities (PLPs) of the packets.

For a detailed overview and configuration documentation, see the [ATM Interfaces User Guide for Routing Devices](#) and [Class of Service User Guide \(Routers and EX9200 Switches\)](#).

RELATED DOCUMENTATION

| [MPLS and Traffic Protection](#)

Configuring Bandwidth Allocation and Call Admission Control in Layer 2 Circuits

You can configure bandwidth allocation and call admission control (CAC) on Layer 2 circuits. This feature is available for RSVP-signaled LSPs traversing an MPLS network.

When you enable bandwidth allocation on a Layer 2 circuit, attempts to establish an RSVP-signaled LSP are preceded by a check of the available bandwidth on the network. This check is the CAC. The available bandwidth is compared to the bandwidth requested by the LSP. If there is insufficient bandwidth, the Layer 2 circuit is not established and an error message is generated. To apply CAC to a Layer 2 circuit, a bandwidth constraint must be configured.

You can specify the bandwidth for a Layer 2 circuit without configuring a bandwidth for each class type (queue). To specify the bandwidth allocation for a Layer 2 circuit, include the `bandwidth` statement:

```
bandwidth bandwidth;
```

Specify the bandwidth in bits per second.

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit neighbor *address* interface *interface-name*]
- [edit logical-systems *logical-system-name* protocols l2circuit neighbor *address* interface *interface-name*]

Alternatively, you can configure the bandwidth for each class type on a Layer 2 circuit. If you use this type of configuration, you cannot simultaneously configure the nonclass type of bandwidth configuration for the Layer 2 circuit (the commit operation fails).

To configure the bandwidth for each class type on an Layer 2 circuit, include the bandwidth statement:

```
bandwidth {  
    ct0 bandwidth;  
    ct1 bandwidth;  
    ct2 bandwidth;  
    ct3 bandwidth;  
}
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit neighbor *address* interface *interface-name*]
- [edit logical-systems *logical-system-name* protocols l2circuit neighbor *address* interface *interface-name*]

Specify the bandwidth for each class type in bits per second. It is not necessary to specify a bandwidth for all four class types.

Configuring Pseudowire Redundancy for Layer 2 Circuits

IN THIS CHAPTER

- [Understanding Pseudowire Redundancy Mobile Backhaul Scenarios | 385](#)
- [Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario | 391](#)
- [Extension of Pseudowire Redundancy Condition Logic to Pseudowire Service Logical Interface Overview | 421](#)

Understanding Pseudowire Redundancy Mobile Backhaul Scenarios

IN THIS SECTION

- [Sample Topology | 386](#)
- [Benefits of Pseudowire Redundancy Mobile Backhaul | 386](#)
- [Layer 2 Virtual Circuit Status TLV Extension | 387](#)
- [How It Works | 388](#)

With the rising demand for mobile broadband services, telecommunication providers are seeing a sharp increase in bandwidth requirements. To keep pace with demand, operators are deploying packet-based backhaul networks that offer increased capacity at a lower cost, while providing the necessary service reliability and quality of experience that users expect.


Most of the legacy backhaul infrastructure has been traditionally built over PDH microwave, TDM T1/E1, or ATM-over-DSL links. Service providers have traditionally added subsequent TDM links to their base stations when needed to deal with bandwidth constraint scenarios. This expansion model has proven to be inefficient for the unprecedented traffic demands required by 3G and Long Term Evolution (LTE) services. As a direct consequence, operators are gradually migrating to an Ethernet-based higher

capacity infrastructure in the backhaul portion of 3G and LTE topologies. Modern base stations now provide Ethernet backhaul connectivity, allowing pseudowire technologies to transport end-user content to the desired destination. As part of this Ethernet transition, service providers are increasingly demanding better resiliency mechanisms to cover the existence gap with those features provided by previous legacy technologies. With that goal in mind, Junos OS provides efficient pseudowire redundancy capabilities to those topologies where Layer 2 and Layer 3 segments are interconnected.

Sample Topology

Figure 29 on page 386 shows a sample topology.

Figure 29: Pseudowire Redundancy Mobile Backhaul Sample Topology



Benefits of Pseudowire Redundancy Mobile Backhaul

Junos OS pseudowire redundancy capabilities are as follows:

- Redundant loop-free paths to interconnect Layer 2 and Layer 3 domains.
- Layer 2 and Layer 3 domains are synchronized with regard to the elected data path.
- Traffic disruption is minimal for the following possible scenarios:
 - Access link failures
 - Node failures
 - Control-plane failures

- Traffic interruption is minimal after the failure's restoration is completed.

Layer 2 Virtual Circuit Status TLV Extension

The pseudowire status TLV is used to communicate the status of a pseudowire between provider edge (PE) routers. To avoid potential primary-path discrepancies, there must be a mechanism that allows all network elements to be synchronized with respect to the primary path over which traffic needs to be sent. With this goal in mind, the status TLV is extended to address this requirement.

NOTE: The pseudowire status TLV is not supported by ACX5000 line of routers.

By having the active and standby states being defined by the access routers, Junos OS mitigates potential primary path collisions, as there is a unique network element dictating the preferable forwarding path to be elected. As an added value, this allows network operators to switch forwarding paths on demand, which is quite useful for troubleshooting and network maintenance purposes.

The active and standby states are communicated to the aggregation routers by making use of an additional pseudowire state flag.

[Table 9 on page 387](#) includes a list of the pseudowire state flags.

Table 9: Pseudowire Status Code for the Pseudowire Status TLV

Flag	Code
L2CKT_PW_STATUS_PW_FWD	0x00000000
L2CKT_PW_STATUS_PW_NOT_FWD	0x00000001
L2CKT_PW_STATUS_AC_RX_FAULT	0x00000002
L2CKT_PW_STATUS_AC_TX_FAULT	0x00000004
L2CKT_PW_STATUS_PSN_RX_FAULT	0x00000008
L2CKT_PW_STATUS_PSN_TX_FAULT	0x00000010

Table 9: Pseudowire Status Code for the Pseudowire Status TLV (Continued)

Flag	Code
L2CKT_PW_STATUS_PW_FWD_STDBY	0x00000020 Indicates the standby state.
L2CKT_PW_STATUS_SWITCH_OVER	0x00000040


In multichassis LAG (MC-LAG)-based scenarios, this same PW_FWD_STDBY flag is used to advertise to remote PE devices which attachment circuit (AC) is being used as the active one. Upon arrival of this flag, the receiving PE device drops any pseudowire built toward the router originating this state. As we can see, this behavior denotes a slightly different semantic for the PW_FWD_STDBY flag. As a consequence, you can configure the `hot-standby-vc-on` statement to control whether the pseudowire must be constructed upon arrival of the PW_FWD_STDBY flag (in the hot-standby pseudowire scenario), or simply destroy it (in the MC-LAG scenario).

How It Works

The solution uses logical tunnel (It-) paired interfaces for stitching the Layer 2 and Layer 3 domains.

Figure 30 on page 389 shows a diagram depicting how pseudowire redundancy in a mobile backhaul scenario works.

Figure 30: Pseudowire Redundancy Mobile Backhaul Solution



A Layer 2 pseudowire terminates on one of the logical tunnel interfaces (x), defined with the circuit cross-connect (CCC) address family configured. A Layer 3 VPN (RFC 2547) terminates the second logical tunnel interface (y), defined with the IPv4 (inet) address family. Logical tunnel interface (x) and (y) are paired. Layer 2 pseudowires established between each access router and its corresponding aggregation PE devices terminate on the logical tunnel interface defined within each PE device. This logical tunnel interface is used to establish a Layer 2 virtual circuit (VC) toward the remote end. In consequence, the CCC address family needs to be configured on it. The same applies to the remote end, where an equivalent interface needs to be defined with CCC capabilities.

This CCC logical tunnel interface created in the aggregation PE devices is paired with a second logical tunnel interface on which the INET address family is enabled. This second logical tunnel interface is configured within the context of an RFC 2547 Layer 3 VPN.

Within the scope of this document, we refer to the CCC and INET logical tunnel interfaces as LT(x) and LT(y), respectively.

The Junos OS routing protocol process (rpd) enables the stitching required to interconnect the Layer 2 VC ending in LT(x) and the associated LT(y).

In the aggregation PE routers, the routing process builds a pseudowire toward access routers, and this happens regardless of the active or standby state of the pseudowire. The same occurs in access routers,

where the control and forwarding state is preestablished in both the Routing Engine and the Packet Forwarding Engine to mitigate traffic disruption during convergence periods.

An attachment circuit (AC) is a physical or virtual circuit (VC) that attaches a CE device to a PE device. Local preference is used to provide better information than the multiple exit discriminator (MED) value provides for a packet's path selection. You can configure the local preference attribute so that it has a higher value for prefixes received from a router that provides a desired path than prefixes received from a router that provides a less desirable path. The higher the value, the more preferred the route. The local preference attribute is the metric most often used in practice to express preferences for one set of paths over another.

If the Layer 2 circuit is primary, the corresponding PE device advertises the AC's subnet with the higher local preference. All aggregation PE devices initially advertise the AC's subnet with the same local preference. You can configure a routing policy to allow a higher local preference value to be advertised if the Layer 2 VC is active.

If a pseudowire is down, LT(x) is tagged with the CCC_Down flag. When this happens, the corresponding PE device withdraws the AC subnet that was initially advertised. The LT(y) address is shared between the aggregation PE devices as a virtual instance port (VIP). No VRRP hello messages are exchanged. Both PE devices assume the primary role.

Both primary and standby Layer 2 VCs are kept open to reduce traffic disruption in backup-to-primary transitions. The `hot-standby-vc-on` *configuration statement* allows manual activation.

Resiliency in the Layer 2 domain is provided through plain pseudowire redundancy for back-to-back connections. For other topologies, pseudowire virtual circuit connectivity verification (VCCV) is used.

Resiliency in the Layer 3 domain is provided by MPLS fast reroute and end-to-end service restoration. A restoration timer prevents having VCs in the secondary path from being switched back to the primary path immediately after the primary PE device is restored.

Access routers can indicate to the aggregation routers which Layer 2 VC is considered to be active. Upon arrival at LT(x) of a status TLV message communicating a standby state, the routing process decreases the BGP's local preference value of the direct subnet represented by the LT(y) IPv4 address. At this point, BGP proceeds to advertise this local preference change to the rest of the members within the Layer 3 domain, which will then reelect the designated forwarder PE device by relying on BGP's path selection mechanisms.

A similar behavior occurs upon arrival of a status TLV message indicating a Layer 2 VC active state. In this case, the receiving PE device changes the local preference corresponding to the LT(y)'s subnet. The value to be used to either decrease or increase the subnet's local preference value is manually configured using a policy.

RELATED DOCUMENTATION

[Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario](#) | 391

Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario

IN THIS SECTION

- [Requirements](#) | 391
- [Overview](#) | 392
- [Configuration](#) | 392
- [Verification](#) | 416

This example shows how to configure pseudowire redundancy where Layer 2 and Layer 3 segments are interconnected in a mobile backhaul scenario.

Requirements

This example can be configured using the following hardware and software components:

- Junos OS Release 13.2 or later
- ACX5000 line of routers as the access (A) routers
- MX Series 5G Universal Routing Platforms or M Series Multiservice Edge Routers for the Provider Edge (PE) Routers
- PTX Series Packet Transport Routers acting as transit label-switched routers
- T Series Core Routers for the Core Routers

NOTE: The PE routers could also be T Series Core Routers but that is not typical. Depending on your scaling requirements, the core routers could also be MX Series 5G Universal Routing Platforms or M Series Multiservice Edge Routers. The Customer Edge (CE) devices could be other routers or switches from Juniper Networks or another vendor.

No special configuration beyond device initialization is required before configuring this example.


Overview

Device CE1 is a simple edge router with an IPv4 interface and a static route pointing to the PE devices. Device A1 establishes two virtual circuits (VCs) toward Device PE1 and Device PE2 by making use of the hot-standby statement. Device PE1 and Device PE2 terminate these VCs and enforce a policy condition over the logical tunnel IPv4 subnet. Device PE3 performs as a Layer 3 VPN provider edge device by having an IPv4 interface in a Layer 3 VPN shared with Device PE1 and Device PE2.

"CLI Quick Configuration" on page 393 shows the configuration for all of the devices in Figure 31 on page 392.

The section "Step-by-Step Procedure" on page 400 describes the steps on Device A1 and Device PE1.

Figure 31: Pseudowire Redundancy in a Mobile Backhaul Example Topology



Configuration

IN THIS SECTION

- Procedure | 393

Procedure

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device CE1

```
set interfaces ge-1/3/3 vlan-tagging
set interfaces ge-1/3/3 unit 600 vlan-id 600
set interfaces ge-1/3/3 unit 600 family inet address 10.41.0.104/24
set interfaces lo0 unit 0 family inet address 192.168.0.104/32 primary
set protocols ospf area 0.0.0.0 interface ge-1/3/3.600
set protocols ospf area 0.0.0.0 interface lo0.0
set routing-options static route 192.168.0.0/8 next-hop 10.41.0.1
set routing-options static route 10.53.0.0/16 next-hop 10.41.0.1
set routing-options router-id 192.168.0.104
```

Device A1

```
set interfaces ge-1/3/0 unit 0 family inet address 10.20.0.100/24
set interfaces ge-1/3/0 unit 0 family iso
set interfaces ge-1/3/0 unit 0 family mpls
set interfaces ge-1/3/1 unit 0 family inet address 10.10.0.100/24
set interfaces ge-1/3/1 unit 0 family iso
set interfaces ge-1/3/1 unit 0 family mpls
set interfaces ge-1/3/2 vlan-tagging
set interfaces ge-1/3/2 encapsulation vlan-ccc
set interfaces ge-1/3/2 unit 600 encapsulation vlan-ccc
set interfaces ge-1/3/2 unit 600 vlan-id 600
set interfaces ge-1/3/2 unit 600 family ccc
set interfaces lo0 unit 0 family inet address 192.168.0.100/32 primary
set interfaces lo0 unit 0 family iso address 49.0002.0192.0168.0100.00
set routing-options router-id 192.168.0.100
set routing-options autonomous-system 64510
set routing-options forwarding-table export pplb
set protocols rsvp interface ge-1/3/0.0
set protocols rsvp interface ge-1/3/1.0
set protocols rsvp interface lo0.0
set protocols mpls interface ge-1/3/0.0
```

```

set protocols mpls interface ge-1/3/1.0
set protocols isis interface ge-1/3/0.0
set protocols isis interface ge-1/3/1.0
set protocols isis interface lo0.0
set protocols ldp interface ge-1/3/0.0
set protocols ldp interface ge-1/3/1.0
set protocols ldp interface lo0.0
set protocols l2circuit neighbor 192.168.0.101 interface ge-1/3/2.600 virtual-circuit-id 1
set protocols l2circuit neighbor 192.168.0.101 interface ge-1/3/2.600 pseudowire-status-tlv
set protocols l2circuit neighbor 192.168.0.101 interface ge-1/3/2.600 revert-time 10 maximum 60
set protocols l2circuit neighbor 192.168.0.101 interface ge-1/3/2.600 backup-neighbor
192.168.0.102 virtual-circuit-id 2
set protocols l2circuit neighbor 192.168.0.101 interface ge-1/3/2.600 backup-neighbor
192.168.0.102 hot-standby
set policy-options policy-statement pplb then load-balance per-packet

```

Device PE1

```

set interfaces ge-0/1/1 unit 0 family inet address 10.21.0.101/24
set interfaces ge-0/1/1 unit 0 family iso
set interfaces ge-0/1/1 unit 0 family mpls
set interfaces ge-0/1/2 unit 0 family inet address 10.31.0.101/24
set interfaces ge-0/1/2 unit 0 family iso
set interfaces ge-0/1/2 unit 0 family mpls
set interfaces ge-0/1/3 unit 0 family inet address 10.10.0.101/24
set interfaces ge-0/1/3 unit 0 family iso
set interfaces ge-0/1/3 unit 0 family mpls
set interfaces lt-1/2/0 unit 600 encapsulation vlan-ccc
set interfaces lt-1/2/0 unit 600 vlan-id 600
set interfaces lt-1/2/0 unit 600 peer-unit 601
set interfaces lt-1/2/0 unit 601 encapsulation vlan
set interfaces lt-1/2/0 unit 601 vlan-id 600
set interfaces lt-1/2/0 unit 601 peer-unit 600
set interfaces lt-1/2/0 unit 601 family inet filter input icmp_inet
set interfaces lt-1/2/0 unit 601 family inet filter output icmp_inet
set interfaces lt-1/2/0 unit 601 family inet address 10.41.0.101/24 vrrp-group 0 virtual-address
10.41.0.1
set interfaces lt-1/2/0 unit 601 family inet address 10.41.0.101/24 vrrp-group 0 accept-data
set interfaces lo0 unit 0 family inet address 192.168.0.101/32 primary
set interfaces lo0 unit 0 family iso address 49.0002.0192.0168.0003.00
set interfaces lo0 unit 1 family inet address 192.168.1.101/32
set routing-options router-id 192.168.0.101

```

```

set routing-options autonomous-system 64511
set protocols rsvp interface ge-0/1/1.0
set protocols rsvp interface ge-0/1/2.0
set protocols rsvp interface ge-0/1/3.0
set protocols rsvp interface lo0.0
set protocols mpls label-switched-path to_PE3 to 192.168.0.103
set protocols mpls label-switched-path to_PE2 to 192.168.0.102
set protocols mpls interface ge-0/1/1.0
set protocols mpls interface ge-0/1/2.0
set protocols mpls interface ge-0/1/3.0
set protocols bgp local-address 192.168.0.101
set protocols bgp group ibgp family inet-vpn any
set protocols bgp group ibgp peer-as 64511
set protocols bgp group ibgp neighbor 192.168.0.102
set protocols bgp group ibgp neighbor 192.168.0.103
set protocols isis interface ge-0/1/1.0
set protocols isis interface ge-0/1/2.0
set protocols isis interface ge-0/1/3.0
set protocols isis interface lo0.0
set protocols ldp interface ge-0/1/1.0
set protocols ldp interface ge-0/1/2.0
set protocols ldp interface ge-0/1/3.0
set protocols ldp interface lo0.0
set protocols l2circuit neighbor 192.168.0.100 interface lt-1/2/0.600 virtual-circuit-id 1
set protocols l2circuit neighbor 192.168.0.100 interface lt-1/2/0.600 pseudowire-status-tlv hot-standby-vc-on

set policy-options policy-statement l3vpn_export term primary from condition primary
set policy-options policy-statement l3vpn_export term primary then local-preference add 300
set policy-options policy-statement l3vpn_export term primary then community set l3vpn
set policy-options policy-statement l3vpn_export term primary then accept
set policy-options policy-statement l3vpn_export term standby from condition standby
set policy-options policy-statement l3vpn_export term standby then local-preference add 30
set policy-options policy-statement l3vpn_export term standby then community set l3vpn
set policy-options policy-statement l3vpn_export term standby then accept
set policy-options policy-statement l3vpn_export term default then community set l3vpn
set policy-options policy-statement l3vpn_export term default then accept
set policy-options policy-statement l3vpn_import term 1 from community l3vpn
set policy-options policy-statement l3vpn_import term 1 then accept
set policy-options policy-statement l3vpn_import term default then reject
set policy-options policy-statement ospf_export term 0 from community l3vpn
set policy-options policy-statement ospf_export term 0 then accept
set policy-options community l3vpn members target:64511:600
set policy-options condition primary if-route-exists address-family ccc lt-1/2/0.600

```

```

set policy-options condition primary if-route-exists address-family ccc table mpls.0
set policy-options condition primary if-route-exists address-family ccc peer-unit 601
set policy-options condition standby if-route-exists address-family ccc lt-1/2/0.600
set policy-options condition standby if-route-exists address-family ccc table mpls.0
set policy-options condition standby if-route-exists address-family ccc standby
set policy-options condition standby if-route-exists address-family ccc peer-unit 601
set firewall family inet filter icmp_inet interface-specific
set firewall family inet filter icmp_inet term 0 from source-address 10.41.0.101/32 except
set firewall family inet filter icmp_inet term 0 from source-address 10.0.0.0/8
set firewall family inet filter icmp_inet term 0 from protocol icmp
set firewall family inet filter icmp_inet term 0 then count icmp_inet
set firewall family inet filter icmp_inet term 0 then log
set firewall family inet filter icmp_inet term 0 then accept
set firewall family inet filter icmp_inet term 1 then accept
set routing-instances l3vpn instance-type vrf
set routing-instances l3vpn interface lt-1/2/0.601
set routing-instances l3vpn interface lo0.1
set routing-instances l3vpn route-distinguisher 192.168.1.101:64511
set routing-instances l3vpn vrf-import l3vpn_import
set routing-instances l3vpn vrf-export l3vpn_export
set routing-instances l3vpn vrf-table-label
set routing-instances l3vpn protocols ospf export ospf_export
set routing-instances l3vpn protocols ospf area 0.0.0.0 lt-1/2/0.601
set routing-instances l3vpn protocols ospf area 0.0.0.0 lo0.1

```

Device PE2

```

set interfaces ge-0/3/0 unit 0 family inet address 10.20.0.102/24
set interfaces ge-0/3/0 unit 0 family iso
set interfaces ge-0/3/0 unit 0 family mpls
set interfaces ge-0/3/1 unit 0 family inet address 10.21.0.102/24
set interfaces ge-0/3/1 unit 0 family iso
set interfaces ge-0/3/1 unit 0 family mpls
set interfaces ge-0/3/3 unit 0 family inet address 10.32.0.102/24
set interfaces ge-0/3/3 unit 0 family iso
set interfaces ge-0/3/3 unit 0 family mpls
set interfaces lt-1/2/0 unit 600 encapsulation vlan-ccc
set interfaces lt-1/2/0 unit 600 vlan-id 600
set interfaces lt-1/2/0 unit 600 peer-unit 601
set interfaces lt-1/2/0 unit 601 encapsulation vlan
set interfaces lt-1/2/0 unit 601 vlan-id 600
set interfaces lt-1/2/0 unit 601 peer-unit 600

```

```

set interfaces lt-1/2/0 unit 601 family inet filter input icmp_inet
set interfaces lt-1/2/0 unit 601 family inet filter output icmp_inet
set interfaces lt-1/2/0 unit 601 family inet address 10.41.0.102/24 vrrp-group 0 virtual-address
10.41.0.1
set interfaces lt-1/2/0 unit 601 family inet address 10.41.0.102/24 vrrp-group 0 accept-data
set interfaces lo0 unit 0 family inet address 192.168.0.102/32 primary
set interfaces lo0 unit 0 family iso address 49.0002.0192.0168.0102.00
set interfaces lo0 unit 1 family inet address 192.168.1.102/32
set routing-options router-id 192.168.0.102
set routing-options autonomous-system 64511
set protocols rsvp interface ge-0/3/0.0
set protocols rsvp interface ge-0/3/1.0
set protocols rsvp interface ge-0/3/3.0
set protocols rsvp interface lo0.0
set protocols mpls label-switched-path to_PE1 to 192.168.0.101
set protocols mpls label-switched-path to_PE3 to 192.168.0.103
set protocols mpls interface ge-0/3/0.0
set protocols mpls interface ge-0/3/1.0
set protocols mpls interface ge-0/3/3.0
set protocols bgp local-address 192.168.0.102
set protocols bgp group ibgp family inet-vpn any
set protocols bgp group ibgp peer-as 64511
set protocols bgp group ibgp neighbor 192.168.0.101
set protocols bgp group ibgp neighbor 192.168.0.103
set protocols isis interface ge-0/3/0.0
set protocols isis interface ge-0/3/1.0
set protocols isis interface ge-0/3/3.0
set protocols isis interface lo0.0
set protocols ldp interface ge-0/3/0.0
set protocols ldp interface ge-0/3/1.0
set protocols ldp interface ge-0/3/3.0
set protocols ldp interface lo0.0
set protocols l2circuit neighbor 192.168.0.100 interface lt-1/2/0.600 virtual-circuit-id 2
set protocols l2circuit neighbor 192.168.0.100 interface lt-1/2/0.600 pseudowire-status-tlv hot-
standby-vc-on
set policy-options policy-statement l3vpn_export term primary from condition primary
set policy-options policy-statement l3vpn_export term primary then local-preference add 300
set policy-options policy-statement l3vpn_export term primary then community set l3vpn
set policy-options policy-statement l3vpn_export term primary then accept
set policy-options policy-statement l3vpn_export term standby from condition standby
set policy-options policy-statement l3vpn_export term standby then local-preference add 30
set policy-options policy-statement l3vpn_export term standby then community set l3vpn
set policy-options policy-statement l3vpn_export term standby then accept

```



```

set policy-options policy-statement l3vpn_export term default then community set l3vpn
set policy-options policy-statement l3vpn_export term default then accept
set policy-options policy-statement l3vpn_import term 1 from community l3vpn
set policy-options policy-statement l3vpn_import term 1 then accept
set policy-options policy-statement l3vpn_import term default then reject
set policy-options policy-statement ospf_export term 0 from community l3vpn
set policy-options policy-statement ospf_export term 0 then accept
set policy-options community l3vpn members target:64511:600
set policy-options condition primary if-route-exists address-family ccc lt-1/2/0.600
set policy-options condition primary if-route-exists address-family ccc table mpls.0
set policy-options condition primary if-route-exists address-family ccc peer-unit 601
set policy-options condition standby if-route-exists address-family ccc lt-1/2/0.600
set policy-options condition standby if-route-exists address-family ccc table mpls.0
set policy-options condition standby if-route-exists address-family ccc standby
set policy-options condition standby if-route-exists address-family ccc peer-unit 601
set firewall family inet filter icmp_inet interface-specific
set firewall family inet filter icmp_inet term 0 from source-address 10.41.0.102/32 except
set firewall family inet filter icmp_inet term 0 from source-address 10.0.0.0/8
set firewall family inet filter icmp_inet term 0 from protocol icmp
set firewall family inet filter icmp_inet term 0 then count icmp_inet
set firewall family inet filter icmp_inet term 0 then log
set firewall family inet filter icmp_inet term 0 then accept
set firewall family inet filter icmp_inet term 1 then accept
set routing-instances l3vpn instance-type vrf
set routing-instances l3vpn interface lt-1/2/0.601
set routing-instances l3vpn interface lo0.1
set routing-instances l3vpn route-distinguisher 192.168.1.102:64511
set routing-instances l3vpn vrf-import l3vpn_import
set routing-instances l3vpn vrf-export l3vpn_export
set routing-instances l3vpn vrf-table-label
set routing-instances l3vpn protocols ospf export ospf_export
set routing-instances l3vpn protocols ospf area 0.0.0.0 interface lt-1/2/0.601
set routing-instances l3vpn protocols ospf area 0.0.0.0 interface lo0.1

```

Device PE3

```

set interfaces ge-2/0/3 unit 0 family inet address 10.32.0.103/24
set interfaces ge-2/0/3 unit 0 family iso
set interfaces ge-2/0/3 unit 0 family mpls
set interfaces ge-2/0/5 unit 0 family inet address 10.53.0.103/24
set interfaces ge-2/0/5 unit 0 family mpls
set interfaces ge-2/1/8 unit 0 family inet address 10.31.0.103/24

```

```

set interfaces ge-2/1/8 unit 0 family iso
set interfaces ge-2/1/8 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.168.0.103/32 primary
set interfaces lo0 unit 0 family iso address 49.0002.0192.0168.0103.00
set interfaces lo0 unit 1 family inet address 192.168.1.103/32
set routing-options router-id 192.168.0.103
set routing-options autonomous-system 64511
set protocols rsvp interface ge-2/0/3.0
set protocols rsvp interface ge-2/1/8.0
set protocols rsvp interface lo0.0
set protocols mpls label-switched-path to_PE1 to 192.168.0.101
set protocols mpls label-switched-path to_PE2 to 192.168.0.102
set protocols mpls interface ge-2/0/3.0
set protocols mpls interface ge-2/1/8.0
set protocols bgp local-address 192.168.0.103
set protocols bgp group ibgp family inet-vpn any
set protocols bgp group ibgp peer-as 64511
set protocols bgp group ibgp neighbor 192.168.0.101
set protocols bgp group ibgp neighbor 192.168.0.102
set protocols isis interface ge-2/0/3.0
set protocols isis interface ge-2/1/8.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/3.0
set protocols ldp interface ge-2/1/8.0
set protocols ldp interface lo0.0
set policy-options policy-statement l3vpn_ospf_export term 0 from protocol direct
set policy-options policy-statement l3vpn_ospf_export term 0 then accept
set policy-options policy-statement l3vpn_ospf_import term 0 from protocol bgp
set policy-options policy-statement l3vpn_ospf_import term 0 from community l3vpn
set policy-options policy-statement l3vpn_ospf_import term 0 then accept
set policy-options policy-statement ospf_export term 0 from community l3vpn
set policy-options policy-statement ospf_export term 0 then accept
set policy-options community l3vpn members target:64511:600
set routing-instances l3vpn instance-type vrf
set routing-instances l3vpn interface ge-2/0/5.0
set routing-instances l3vpn interface lo0.1
set routing-instances l3vpn route-distinguisher 192.168.0.103:64511
set routing-instances l3vpn vrf-target target:64511:600
set routing-instances l3vpn vrf-table-label
set routing-instances l3vpn protocols ospf export ospf_export
set routing-instances l3vpn protocols ospf area 0.0.0.0 interface ge-2/0/5.0
set routing-instances l3vpn protocols ospf area 0.0.0.0 interface lo0.1

```

Device CE2

```
set interfaces ge-2/0/8 unit 0 family inet address 10.53.0.105/24
set interfaces lo0 unit 0 family inet address 192.168.0.105/32 primary
set protocols ospf area 0.0.0.0 interface ge-2/0/8.0
set protocols ospf area 0.0.0.0 interface lo0.0
set routing-options router-id 192.168.0.105
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure Device A1:

1. Configure the interfaces.

Enable MPLS on the core-facing interfaces. The ISO address family is also enabled, because IS-IS is used as the interior gateway protocol (IGP) in the provider network.

On the customer-facing interface, you do not need to enable MPLS. On this interface, enable CCC encapsulation and address family CCC.

```
[edit interfaces]
user@A1# set ge-1/3/0 unit 0 family inet address 10.20.0.100/24
user@A1# set ge-1/3/0 unit 0 family iso
user@A1# set ge-1/3/0 unit 0 family mpls
user@A1# set ge-1/3/1 unit 0 family inet address 10.10.0.100/24
user@A1# set ge-1/3/1 unit 0 family iso
user@A1# set ge-1/3/1 unit 0 family mpls
user@A1# set ge-1/3/2 vlan-tagging
user@A1# set ge-1/3/2 encapsulation vlan-ccc
user@A1# set ge-1/3/2 unit 600 encapsulation vlan-ccc
user@A1# set ge-1/3/2 unit 600 vlan-id 600
user@A1# set ge-1/3/2 unit 600 family ccc
user@A1# set lo0 unit 0 family inet address 192.168.0.100/32 primary
user@A1# set lo0 unit 0 family iso address 49.0002.0192.0168.0100.00
```

2. Configure the RSVP on the core-facing interfaces and on the loopback interface.

RSVP is used in the Layer 3 domain.

```
[edit protocols rsvp]
user@A1# set interface ge-1/3/0.0
user@A1# set interface ge-1/3/1.0
user@A1# set interface lo0.0
```

3. Configure LDP on the core-facing interfaces and on the loopback interface.

LDP is used in Layer 2 domain.

```
[edit protocols ldp]
user@A1# set interface ge-1/3/0.0
user@A1# set interface ge-1/3/1.0
user@A1# set interface lo0.0
```

4. Configure MPLS on the core-facing interfaces.

```
[edit protocols mpls]
user@A1# set interface ge-1/3/0.0
user@A1# set interface ge-1/3/1.0
```

5. Configure an interior gateway protocol, such as IS-IS or OSPF, on the core-facing interfaces and on the loopback interface.

```
[edit protocols isis]
user@A1# set interface ge-1/3/0.0
user@A1# set interface ge-1/3/1.0
user@A1# set interface lo0.0
```

6. On the interface that faces the customer edge, configure the Layer 2 circuit.

Configure the `hot-standby` statement on those routers with both active and standby virtual circuits (VCs) (Device A1 in our topology). You must include the `pseudowire-status-tlv` statement on access routers. Without the status TLV signaling, the standby flag cannot be advertised to remote provider edge (PE) devices.

The `revert-time` statement and the `maximum` option should also be configured on access routers. Without the `revert-time` statement, traffic of all the VCs will not be transitioned to the primary path upon completion of the restoration. If a `revert-time` delay is defined but a `maximum` delay is not, then VCs are

restored immediately upon the revert timer's expiration. The maximum option allows the VCs to be restored in a scattered fashion rather than all at once.

```
[edit protocols l2circuit neighbor 192.168.0.101 interface ge-1/3/2.600]
user@A1# set virtual-circuit-id 1
user@A1# set pseudowire-status-tlv
user@A1# set revert-time 10 maximum 60
user@A1# set backup-neighbor 192.168.0.102 virtual-circuit-id 2
user@A1# set backup-neighbor 192.168.0.102 hot-standby
```

7. To have the unilist next hop get pushed to other access routers, configure per-packet load balancing.

```
[edit policy-options policy-statement pplb]
user@A1# set then load-balance per-packet
```

8. Apply the per-packet load balancing policy.

```
[edit routing-options forwarding-table]
user@A1# set export pplb
```

9. Configure the autonomous system (AS) ID and the router ID.

```
[edit routing-options]
user@A1# set router-id 192.168.0.100
user@A1# set autonomous-system 64510
```

Similarly, configure any other access devices.

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure Device PE1:

1. Configure the interfaces.

Enable MPLS on the core-facing interfaces.

```
[edit interfaces]
user@PE1# set ge-0/1/1 unit 0 family inet address 10.21.0.101/24
user@PE1# set ge-0/1/1 unit 0 family iso
user@PE1# set ge-0/1/1 unit 0 family mpls
user@PE1# set ge-0/1/2 unit 0 family inet address 10.31.0.101/24
user@PE1# set ge-0/1/2 unit 0 family iso
user@PE1# set ge-0/1/2 unit 0 family mpls
user@PE1# set ge-0/1/3 unit 0 family inet address 10.10.0.101/24
user@PE1# set ge-0/1/3 unit 0 family iso
user@PE1# set ge-0/1/3 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 192.168.0.101/32 primary
user@PE1# set lo0 unit 0 family iso address 49.0002.0192.0168.0003.00
user@PE1# set lo0 unit 1 family inet address 192.168.1.101/32
```

2. On Device PE1 and Device PE2, which are aggregation routers, configure a pair of logical tunnel interfaces to represent LT(x) and LT(y).

The solution uses logical tunnel (lt-) paired interfaces for stitching the Layer 2 and Layer 3 domains.

A Layer 2 pseudowire terminates on one of the logical tunnel interfaces, LT(x), defined with the circuit cross-connect (CCC) address family. A Layer 3 VPN terminates the second logical tunnel interface, LT(y), defined with the IPv4 (inet) address family. LT(x) and LT(y) are paired.

```
[edit interfaces]
user@PE1# set lt-1/2/0 unit 600 encapsulation vlan-ccc
user@PE1# set lt-1/2/0 unit 600 vlan-id 600
user@PE1# set lt-1/2/0 unit 600 peer-unit 601
user@PE1# set lt-1/2/0 unit 601 encapsulation vlan
user@PE1# set lt-1/2/0 unit 601 vlan-id 600
user@PE1# set lt-1/2/0 unit 601 peer-unit 600
user@PE1# set lt-1/2/0 unit 601 family inet filter input icmp_inet
user@PE1# set lt-1/2/0 unit 601 family inet filter output icmp_inet
```

3. (Optional) Associate a unique VRRP address with both Device PE1 and Device PE2.

In this case, both Device PE1 and Device PE2 assume the primary state for the defined VIP IPv4 address, so no VRRP hello message are exchanged between the routers.

```
[edit interfaces lt-1/2/0 unit 601 family inet address 10.41.0.101/24]
user@PE1# set vrrp-group 0 virtual-address 10.41.0.1
user@PE1# set vrrp-group 0 accept-data
```

4. Configure IS-IS or another IGP.

```
[edit protocols isis]
user@PE1# set interface ge-0/1/1.0
user@PE1# set interface ge-0/1/2.0
user@PE1# set interface ge-0/1/3.0
user@PE1# set interface lo0.0
```

5. Configure the MPLS on the core-facing interfaces.

```
[edit protocols mpls]
user@PE1# set interface ge-0/1/1.0
user@PE1# set interface ge-0/1/2.0
user@PE1# set interface ge-0/1/3.0
```

6. Configure label-switched paths to the other PE devices.

BGP is a policy-driven protocol, so also configure and apply any needed routing policies. For example, you might want to export static routes into BGP.

```
[edit protocols mpls]
user@PE1# set label-switched-path to_PE3 to 192.168.0.103
user@PE1# set label-switched-path to_PE2 to 192.168.0.102
```

7. Configure LDP on the core-facing interfaces and on the loopback interface.

```
[edit protocols ldp]
user@PE1# set interface ge-0/1/1.0
user@PE1# set interface ge-0/1/2.0
user@PE1# set interface ge-0/1/3.0
user@PE1# set interface lo0.0
```

8. Configure RSVP on the core-facing interfaces and on the loopback interface.

```
[edit protocols rsvp]
user@PE1# set interface ge-0/1/1.0
user@PE1# set interface ge-0/1/2.0
user@PE1# set interface ge-0/1/3.0
user@PE1# set interface lo0.0
```

9. Configure internal BGP (IBGP).

```
[edit protocols bgp]
user@PE1# set local-address 192.168.0.101
user@PE1# set group ibgp family inet-vpn any
user@PE1# set group ibgp peer-as 64511
user@PE1# set group ibgp neighbor 192.168.0.102
user@PE1# set group ibgp neighbor 192.168.0.103
```

10. Configure the Layer 2 circuit on the logical tunnel interface.

Configure the `hot-standby-vc-on` statement if you want a hot standby pseudowire to be established upon arrival of `PW_FWD_STDBY` status TLV.

```
[edit protocols l2circuit neighbor 192.168.0.100 interface lt-1/2/0.600]
user@PE1# set virtual-circuit-id 1
user@PE1# set pseudowire-status-tlv hot-standby-vc-on
```

11. Define a pair of conditions to be applied to the egress policy defined within the Layer 3 VPN instance.

In both condition `primary` and condition `standby`, the matching route corresponds to the interface `lt-1/2/0.600 (y)`, as this is the format in which egress routes appear in routing table `mpls.0` to represent any given pseudowire.

The difference between these conditions is in the `standby` attribute. Upon arrival of the `PW_FWD_STDBY` status TLV to Device PE1 or Device PE2, Junos OS matches condition `standby`, and in consequence, only term `standby` within the `l3vpn` policy will be executed. On the other hand, if the `PW_FWD_STDBY` status TLV is not present, the policy only matches condition `primary`, which then executes term `primary` in the `l3vpn` policy. Also, for logical tunnel-based CCC services, you must specify the logical tunnel interface, `LT(y)`, that is associated with the logical tunnel CCC interface, `LT(x)`. (See ["Understanding Pseudowire Redundancy Mobile Backhaul Scenarios"](#) on page 385.)

Finally, for CCC-based conditions, Junos OS only allows mpls.0 as the matching routing table. For the address attribute, Junos OS only allows strings with a logical interface unit format (for example, lt-0/0/0.0).

```
[edit policy-options condition primary if-route-exists address-family ccc]
user@PE1# set lt-1/2/0.600
user@PE1# set table mpls.0
user@PE1# set peer-unit 601
[edit policy-options condition standby if-route-exists address-family ccc]
user@PE1# set lt-1/2/0.600
user@PE1# set table mpls.0
user@PE1# set standby
user@PE1# set peer-unit 601
```

12. Configure the Layer 3 VPN export policy.

If the Layer 2 virtual circuit (VC) is primary, the corresponding provider edge (PE) routing device advertises the attachment circuit's (AC's) subnet with the higher local preference. All aggregation PE devices initially advertise the AC's subnet with the same local preference.

This routing policy allows a higher local preference value to be advertised if the Layer 2 VC is active.

```
[edit policy-options policy-statement l3vpn_export]
user@PE1# set term primary from condition primary
user@PE1# set term primary then local-preference add 300
user@PE1# set term primary then community set l3vpn
user@PE1# set term primary then accept
user@PE1# set term standby from condition standby
user@PE1# set term standby then local-preference add 30
user@PE1# set term standby then community set l3vpn
user@PE1# set term standby then accept
user@PE1# set term default then community set l3vpn
user@PE1# set term default then accept
```

13. Configure the Layer 3 VPN community members.

```
[edit policy-options community l3vpn]
user@PE1# set members target:64511:600
```

14. Configure the Layer 3 VPN import policy, based on the Layer 3 VPN community.

```
[edit policy-options policy-statement l3vpn_import]
user@PE1# set term 1 from community l3vpn
user@PE1# set term 1 then accept
user@PE1# set term default then reject
```

15. Configure OSPF export policy, based on the Layer 3 VPN community.

```
[edit policy-options policy-statement ospf_export term 0]
user@PE1# set from community l3vpn
user@PE1# set then accept
```

16. (Optional) Configure a firewall filter to check the path taken by traffic.

```
[edit firewall family inet filter icmp_inet]
user@PE1# set interface-specific
user@PE1# set term 0 from source-address 10.41.0.101/32 except
user@PE1# set term 0 from source-address 10.0.0.0/8
user@PE1# set term 0 from protocol icmp
user@PE1# set term 0 then count icmp_inet
user@PE1# set term 0 then log
user@PE1# set term 0 then accept
user@PE1# set term 1 then accept
```

17. Configure the routing instance.

This routing instance is in the Layer 2 domain where Device PE1 and Device PE2 are interconnected to the metro ring over multiaccess media (Ethernet). You must include the `vrf-table-label` statement on Device PE1 and Device PE2 to enable advertisement of the direct subnet prefix corresponding to the logical tunnel (lt-) interface toward the Layer 3 domain.

Device PE1 and Device PE2 use OSPF for Layer 3 VPN communication with Device CE1.

```
[edit routing-instances l3vpn]
user@PE1# set instance-type vrf
user@PE1# set interface lt-1/2/0.601
user@PE1# set interface lo0.1
user@PE1# set route-distinguisher 192.168.1.101:64511
user@PE1# set vrf-import l3vpn_import
```

```

user@PE1# set vrf-export l3vpn_export
user@PE1# set vrf-table-label
user@PE1# set protocols ospf export ospf_export
user@PE1# set protocols ospf area 0.0.0.0 interface lt-1/2/0.601
user@PE1# set protocols ospf area 0.0.0.0 interface lo0.1

```

18. Configure the autonomous system (AS) ID and router ID.

```

[edit routing-options]
user@PE1# set router-id 192.168.0.101
user@PE1# set autonomous-system 64511

```

Similarly, configure Device PE2.

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show firewall`, `show protocols`, `show policy-options`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

Device A1

```

user@A1# show interfaces
ge-1/3/0 {
  unit 0 {
    family inet {
      address 10.20.0.100/24;
    }
    family iso;
    family mpls;
  }
}
ge-1/3/1 {
  unit 0 {
    family inet {
      address 10.10.0.100/24;
    }
    family iso;
    family mpls;
  }
}

```

```

}
ge-1/3/2 {
    vlan-tagging;
    encapsulation vlan-ccc;
    unit 600 {
        encapsulation vlan-ccc;
        vlan-id 600;
        family ccc;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.168.0.100/32 {
                primary;
            }
        }
        family iso {
            address 49.0002.0192.0168.0100.00;
        }
    }
}
}

```

```
user@A1# show protocols
```

```

rsvp {
    interface ge-1/3/0.0;
    interface ge-1/3/1.0;
    interface lo0.0;
}
mpls {
    interface ge-1/3/0.0;
    interface ge-1/3/1.0;
}
isis {
    interface ge-1/3/0.0;
    interface ge-1/3/1.0;
    interface lo0.0;
}
ldp {
    interface ge-1/3/0.0;
    interface ge-1/3/1.0;
}

```

```

    interface lo0.0;
}
l2circuit {
    neighbor 192.168.0.101 {
        interface ge-1/3/2.600 {
            virtual-circuit-id 1;
            pseudowire-status-tlv;
            backup-neighbor 192.168.0.102 {
                virtual-circuit-id 2;
                hot-standby;
            }
        }
    }
}
}

```

```

user@A1# show policy-options
policy-statement pplb {
    then {
        load-balance per-packet;
    }
}

```

```

user@A1# show routing-options
autonomous-system 64510;
router-id 192.168.0.100;
forwarding-table {
    export pplb;
}

```

Device PE1

```

user@PE1# show interfaces
ge-0/1/1 {
    unit 0 {
        family inet {
            address 10.21.0.101/24;
        }
        family iso;
        family mpls;
    }
}

```

```

    }
}
ge-0/1/2 {
    unit 0 {
        family inet {
            address 10.31.0.101/24;
        }
        family iso;
        family mpls;
    }
}
ge-0/1/3 {
    unit 0 {
        family inet {
            address 10.10.0.101/24;
        }
        family iso;
        family mpls;
    }
}
lt-1/2/0 {
    unit 600 {
        encapsulation vlan-ccc;
        vlan-id 600;
        peer-unit 601;
    }
    unit 601 {
        encapsulation vlan;
        vlan-id 600;
        peer-unit 600;
        family inet {
            filter {
                input icmp_inet;
                output icmp_inet;
            }
            address 10.41.0.101/24 {
                vrrp-group 0 {
                    virtual-address 10.41.0.1;
                    accept-data;
                }
            }
        }
    }
}

```

```

}
lo0 {
    unit 0 {
        family inet {
            address 192.168.0.101/32 {
                primary;
            }
        }
        family iso {
            address 49.0002.0192.0168.0003.00;
        }
    }
    unit 1 {
        family inet {
            address 192.168.1.101/32;
        }
    }
}

```

```

user@PE1# show firewall
family inet {
    filter icmp_inet {
        interface-specific;
        term 0 {
            from {
                source-address {
                    10.41.0.101/32 except;
                    10.0.0.0/8;
                }
                protocol icmp;
            }
            then {
                count icmp_inet;
                log;
                accept;
            }
        }
        term 1 {
            then accept;
        }
    }
}

```

```

    }
}

```

```

user@PE1# show protocols
rsvp {
    interface ge-0/1/1.0;
    interface ge-0/1/2.0;
    interface ge-0/1/3.0;
    interface lo0.0;
}
mpls {
    label-switched-path to_PE3 {
        to 192.168.0.103;
    }
    label-switched-path to_PE2 {
        to 192.168.0.102;
    }
    interface ge-0/1/1.0;
    interface ge-0/1/2.0;
    interface ge-0/1/3.0;
}
bgp {
    local-address 192.168.0.101;
    group ibgp {
        family inet-vpn {
            any;
        }
        peer-as 64511;
        neighbor 192.168.0.102;
        neighbor 192.168.0.103;
    }
}
isis {
    interface ge-0/1/1.0;
    interface ge-0/1/2.0;
    interface ge-0/1/3.0;
    interface lo0.0;
}
ldp {
    interface ge-0/1/1.0;
    interface ge-0/1/2.0;

```



```

interface ge-0/1/3.0;
interface lo0.0;
}
l2circuit {
  neighbor 192.168.0.100 {
    interface lt-1/2/0.600 {
      virtual-circuit-id 1;
      pseudowire-status-tlv hot-standby-vc-on;
    }
  }
}
}

```

```

user@PE1# show policy-options
policy-statement l3vpn_export {
  term primary {
    from condition primary;
    then {
      local-preference add 300;
      community set l3vpn;
      accept;
    }
  }
  term standby {
    from condition standby;
    then {
      local-preference add 30;
      community set l3vpn;
      accept;
    }
  }
  term default {
    then {
      community set l3vpn;
      accept;
    }
  }
}
policy-statement l3vpn_import {
  term 1 {
    from community l3vpn;
    then accept;
  }
}

```

```

    }
    term default {
        then reject;
    }
}
policy-statement ospf_export {
    term 0 {
        from community l3vpn;
        then accept;
    }
}
community l3vpn members target:64511:600;
condition primary {
    if-route-exists {
        address-family {
            ccc {
                lt-1/2/0.600;
                table mpls.0;
                peer-unit 601;
            }
        }
    }
}
condition standby {
    if-route-exists {
        address-family {
            ccc {
                lt-1/2/0.600;
                table mpls.0;
                standby;
                peer-unit 601;
            }
        }
    }
}

```

```

    }
}

```

```

user@PE1# show routing-options
router-id 192.168.0.101;
autonomous-system 64511;

```

```

user@PE1# show routing-instances
l3vpn {
    instance-type vrf;
    interface lt-1/2/0.601;
    interface lo0.1;
    route-distinguisher 192.168.1.101:64511;
    vrf-import l3vpn_import;
    vrf-export l3vpn_export;
    vrf-table-label;
    protocols {
        ospf {
            export ospf_export;
            area 0.0.0.0 {
                interface lt-1/2/0.601;
                interface lo0.1;
            }
        }
    }
}

```

If you are done configuring the devices, enter `commit` from configuration mode.

Verification

IN THIS SECTION

- [Checking Layer 2 Circuits | 417](#)
- [Checking the Policy Conditions | 420](#)

Confirm that the configuration is working properly.

Checking Layer 2 Circuits

Purpose

Upon Layer 2 virtual circuit (VC) establishment, the output of the `show l2circuit connections` command shows the active and the hot-standby VC. In addition, control-plane details are shown for the hot-standby VC.

Action

From operational mode, enter the `show l2circuit connections extensive` command.

```
user@A1> show l2circuit connections extensive
```

Layer-2 Circuit Connections:

Legend for connection status (St)

EI -- encapsulation invalid	NP -- interface h/w not present
MM -- mtu mismatch	Dn -- down
EM -- encapsulation mismatch	VC-Dn -- Virtual circuit Down
CM -- control-word mismatch	Up -- operational
VM -- vlan id mismatch	CF -- Call admission control failure
OL -- no outgoing label	IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC	TM -- TDM misconfiguration
BK -- Backup Connection	ST -- Standby Connection
CB -- rcvd cell-bundle size bad	SP -- Static Pseudowire
LD -- local site signaled down	RS -- remote site standby
RD -- remote site signaled down	HS -- Hot-standby Connection
XX -- unknown	

Legend for interface status

Up -- operational

Dn -- down

Neighbor: 192.168.0.101

Interface	Type	St	Time last up	# Up trans
ge-1/3/2.600(vc 1)	rmt	Up	Jan 24 11:00:26 2013	1

Remote PE: 192.168.0.101, Negotiated control-word: Yes (Null)

Incoming label: 299776, Outgoing label: 299776

Negotiated PW status TLV: Yes

local PW status code: 0x00000000, Neighbor PW status code: 0x00000000

Local interface: ge-1/3/2.600, Status: Up, Encapsulation: VLAN

Connection History:

```

Jan 24 11:00:26 2013 status update timer
Jan 24 11:00:26 2013 PE route changed
Jan 24 11:00:26 2013 Out lbl Update                299776
Jan 24 11:00:26 2013 In lbl Update                299776
Jan 24 11:00:26 2013 loc intf up                  ge-1/3/2.600
Neighbor: 192.168.0.102
Interface                Type  St    Time last up        # Up trans
ge-1/3/2.600(vc 2)      rmt   HS    -----             ----
Remote PE: 192.168.0.102, Negotiated control-word: Yes (Null)
Incoming label: 299792, Outgoing label: 299776
Negotiated PW status TLV: Yes
local PW status code: 0x00000020, Neighbor PW status code: 0x00000000
Local interface: ge-1/3/2.600, Status: Up, Encapsulation: VLAN
user@PE1> show l2circuit connections extensive

```

Layer-2 Circuit Connections:

Legend for connection status (St)

```

EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch     Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad SP -- Static Pseudowire
LD -- local site signaled down  RS -- remote site standby
RD -- remote site signaled down HS -- Hot-standby Connection
XX -- unknown

```

Legend for interface status

```

Up -- operational
Dn -- down

```

Neighbor: 192.168.0.100

```

Interface                Type  St    Time last up        # Up trans
lt-1/2/0.600(vc 1)      rmt   Up    Jan 24 11:06:36 2013      1
Remote PE: 192.168.0.100, Negotiated control-word: Yes (Null)
Incoming label: 299776, Outgoing label: 299776
Negotiated PW status TLV: Yes
local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
Local interface: lt-1/2/0.600, Status: Up, Encapsulation: VLAN

```

Connection History:

```

Jan 24 11:06:36 2013 status update timer
Jan 24 11:06:36 2013 PE route changed
Jan 24 11:06:36 2013 Out lbl Update                299776
Jan 24 11:06:36 2013 In lbl Update                  299776
Jan 24 11:06:36 2013 loc intf up                    lt-1/2/0.600

```

user@PE2> **show l2circuit connections extensive**

Layer-2 Circuit Connections:

Legend for connection status (St)

```

EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch               Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch      Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad SP -- Static Pseudowire
LD -- local site signaled down  RS -- remote site standby
RD -- remote site signaled down HS -- Hot-standby Connection
XX -- unknown

```

Legend for interface status

Up -- operational

Dn -- down

Neighbor: 192.168.0.100

Interface	Type	St	Time last up	# Up trans
lt-1/2/0.600(vc 2)	rmt	Up	Jan 24 10:55:31 2013	1

Remote PE: 192.168.0.100, Negotiated control-word: Yes (Null)

Incoming label: 299776, Outgoing label: 299792

Negotiated PW status TLV: Yes

local PW status code: 0x00000000, Neighbor PW status code: 0x00000020

Local interface: lt-1/2/0.600, Status: Up, Encapsulation: VLAN

Connection History:

```

Jan 24 10:55:31 2013 status update timer
Jan 24 10:55:31 2013 PE route changed
Jan 24 10:55:31 2013 Out lbl Update                299792
Jan 24 10:55:31 2013 In lbl Update                  299776
Jan 24 10:55:31 2013 loc intf up                    lt-1/2/0.600

```

Meaning

From the perspective of Device PE1 and Device PE2, a single Layer 2 circuit is established toward access routers, so there is no standby device information in the CLI output of the `show l2circuit connections` command. Note that no timing and flapping information is provided for the VC acting as the hot-standby. Junos OS only allows these counters to be tracked for the active VC.

Checking the Policy Conditions

Purpose

On the PE devices, verify the state of the different conditions defined as part of the Layer3 VPN's egress policy, where 10.41.0.0/24 corresponds to the logical tunnel (y) subnet.

Action

From operational mode, enter the `show policy conditions detail` command.

```
user@PE1> show policy conditions detail
Configured conditions:
Condition primary (static), event: Existence of a route in a specific routing table
Dependent routes:
  10.41.0.0/24, generation 8
  192.168.0.104/32, generation 8

Condition standby (static), event: Existence of a route in a specific routing table
Dependent routes:
None

Condition tables:
Table mpls.0, generation 0, dependencies 0, If-route-exists conditions: primary (static) standby (static)
Table l3vpn.inet.0, generation 12, dependencies 2
```

```
user@PE2> show policy conditions detail
Configured conditions:
Condition primary (static), event: Existence of a route in a specific routing table
Dependent routes:
  10.41.0.0/24, generation 18
```

Condition standby (static), event: Existence of a route in a specific routing table

Dependent routes:

10.41.0.0/24, generation 18

Condition tables:

Table mpls.0, generation 0, dependencies 0, If-route-exists conditions: primary (static) standby (static)

Table l3vpn.inet.0, generation 367, dependencies 2

RELATED DOCUMENTATION

[Understanding Pseudowire Redundancy Mobile Backhaul Scenarios](#) | 385

Extension of Pseudowire Redundancy Condition Logic to Pseudowire Service Logical Interface Overview

IN THIS SECTION

- [Sample Topology](#) | 422
- [Functionality](#) | 422
- [Policy Condition for Pseudowire Service Logical Interfaces](#) | 423

The pseudowire redundancy feature for mobile backhaul scenarios uses logical tunnel (lt-) paired interfaces as the stitching between Layer 2 and Layer 3 domains. This feature now includes the MPLS pseudowire service logical interface to terminate subscriber interfaces using the ps0.0 interface as the stitching between Layer 2 and Layer 3 domains. This topic describes the functional details of the pseudowire redundancy feature using the ps0.0 interface, which extends the policy logic used in the logical tunnel interfaces.


A pseudowire logical device and its related pseudowire logical interfaces are dependent on the state of the underlying logical transport interface device, which is either the Layer 2 VPN or Layer 2 circuit.

NOTE: We recommend that you use unit 0 to represent the transport logical interface for the pseudowire device. Non-zero unit numbers represent *service* logical interfaces used for pseudowire subscriber interfaces.

Sample Topology

Figure 32 on page 422 on page 1 shows the stitching of Layer 2 and Layer 3 domains between the MPLS access node and the MPLS core. The primary or backup pseudowire on the MPLS access side is terminated at the provider edge devices (PE1 and PE2) at the pseudowire logical transport interface (ps0.0). The corresponding pseudowire logical service interfaces (ps0.1 to ps0.n) at the core MPLS cloud are connected to the Layer 3 domain, and these pseudowire logical service interfaces are configured in Layer 3 VPN routing instances.

Figure 32: Sample Topology for Pseudowire Redundancy



This topology results in a Layer 2 circuit across the MPLS access node and provider edge routers, with the pseudowire logical transport interface (ps0.0) acting as the local interface of the Layer 2 circuit terminating at the PE routers.

Functionality

Figure 32 on page 422 on page 1 shows the functional details of pseudowire redundancy with events between the devices. A1 is the MPLS access node that initiates the primary and backup Layer 2 circuits to the provider edge devices (PE1 and PE2). The Layer 2 circuit is terminated on provider edge devices and then stitched to the Layer 3 VPN.

The functional flow is as follows:

- Create the primary and backup Layer 2 circuit at access node A1.

- Detect both the primary and backup path, advertise the local preference, and stitch the Layer 2 circuit and Layer 3 VPN at the provider edge devices (PE1 and PE2).


The following pseudowire code is used to notify the standby status from the access node to provider edge devices:

- L2CKT_PW_STATUS_PW_FWD_STDBY flag with 0x00000020.

Policy Condition for Pseudowire Service Logical Interfaces

The policy condition uses pseudowire service logical interfaces to stitch the Layer 2 and Layer 3 domains. Provider edge devices (PE1 and PE2) detect both primary and standby virtual circuits on the metro MPLS side. The primary virtual circuit is stitched to Layer 3 domain at the services side PE1 and PE2 towards the MPLS core. See [Figure 33 on page 423](#) on page 2.

Figure 33: Pseudowire Service Logical Interface for Pseudowire Redundancy Solution



A primary Layer 2 circuit exists between access node A1 and provider edge device PE1, and a standby Layer 2 circuit exists between the same access node A1 and provider edge device PE2. The pseudowire service on the transport logical interface (ps0.0) is the local interface for the Layer 2 circuit at PE1 and PE2. At PE1 and PE2, there are multiple Layer 3 VPN instances; for example vrf-x and vrf-y.

The pseudowire service on service logical interfaces ps0.x and ps0.y are configured for the vrf-x and vrf-y routing instances respectively. For example, when the traffic with VLAN ID x originates from the access node to PE1 or PE2 on the Layer 2 circuit, it exits through the pseudowire service on the transport logical interface (ps0.0). Then the pseudowire service on service logical interface ps0.x is selected and sent through the vrf-x instance.

When the pseudowire state is active, the aggregation provider edge device (PE1 or PE2) advertises the subnet of the attachment circuit with the higher local preference value, which is indicated by the user through a manually configured policy.

NOTE: When remote provider edge devices receive two inet-vpn prefixes corresponding to the subnet of the attachment circuit, the highest local preference prefix received determines the primary datapath to be elected.

See the following output:

```
[edit policy-options]
  condition primary {
    if-route-exists {
      address-family {
        ccc {
          ps0.0;
          table mpls.0;
        }
      }
    }
  }
}
policy-statement l3vpn_export {
  term primary {
    from condition primary;
    then {
      local-preference add 300;
      community set l3vpn;
      accept;
    }
  }
}
```

NOTE: In policy-statement *name*, under *condition primary*, there is no need to configure the *peer unit*, as it is valid only for the logical tunnel interface. For the pseudowire service logical interface, one-to-many mapping is used.

RELATED DOCUMENTATION

[Understanding Pseudowire Redundancy Mobile Backhaul Scenarios | 385](#)

[Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario | 391](#)

[Pseudowire Subscriber Logical Interfaces Overview](#)

[Configuring a Pseudowire Subscriber Logical Interface](#)

[Configuring the Transport Logical Interface for a Pseudowire Subscriber Logical Interface](#)

Configuring Load Balancing for Layer 2 Circuits

IN THIS CHAPTER

- [Reducing APS Switchover Time in Layer 2 Circuits | 426](#)

Reducing APS Switchover Time in Layer 2 Circuits

IN THIS SECTION

- [Configuring Per-Packet Load Balancing | 427](#)
- [Configuring Fast APS Switchover | 428](#)

On M320 routers with Channelized OC3/STM1 Circuit Emulation PIC with SFP, you can configure the `fast-aps-switch` statement at the `[edit interfaces interface-name sonet-options aps]` hierarchy level to reduce the Automatic Protection Switching (APS) switchover time in Layer 2 circuits. Configuring this statement reduces the APS switchover time only when the Layer 2 circuit encapsulation type for the interface receiving traffic from a Layer 2 circuit neighbor is Structure Agnostic time-division multiplexing (TDM) over Packet (SAToP).

The `fast-aps-switch` statement must be configured on both working and protect circuits. Additionally, to achieve reduction in APS switchover time:

- Per-packet load balancing must be configured.
- Bidirectional switching mode must be configured.
- If the `fast-aps-switch` statement is configured in revertive APS mode, configure an appropriate value for revert time. We recommend that you configure a revert time of 600 seconds for 672 through 1344 Layer 2 circuits.
- To prevent the logical interfaces in the data path from being shut down, configure appropriate hold-time values on all the interfaces in the data path that support TDM.

NOTE:

- The `fast-aps-switch` statement cannot be configured when the `APS annex-b` option is configured.
- The interfaces that have the `fast-aps-switch` statement configured cannot be used in virtual private LAN service (VPLS) environments.

The following tasks illustrate how to configure Junos OS to reduce APS switchover time.

NOTE: Per-packet load balancing can be configured for a limited set of routes or for all routes. To simplify the steps involved in configuring per-packet load balancing, steps for configuring per-packet load balancing for all routes is covered in this procedure.

Configuring Per-Packet Load Balancing

To configure per-packet load balancing for all routes:

1. Configure the per-packet option for the load-balance statement at the `[edit policy-options policy-statement policy-name then]` hierarchy level.

```
[edit policy-options policy-statement policy-name then]
user@host# set load-balance per-packet
```

For example:

```
[edit policy-options policy-statement load-balancing-policy then]
user@host# set load-balance per-packet
```

2. Configure the policy name in the export statement at the `[edit routing-options forwarding-table]` hierarchy level.

```
[edit routing-options forwarding-table]
user@host# set export policy-name
```

For example:

```
[edit routing-options forwarding-table]
user@host# set export load-balancing-policy
```

SEE ALSO

[Configuring Per-Packet Load Balancing](#)

[Understanding Per-Packet Load Balancing](#)

Configuring Fast APS Switchover

To configure fast APS switchover:

1. On both the working and protect circuits, configure the `fast-aps-switch` statement at the `[edit interfaces interface-name sonet-options aps]` hierarchy level.

```
[edit interfaces interface-name sonet-options aps]
user@host# set fast-aps-switch
```

For example:

```
[edit interfaces cstm1-0/0/0 sonet-options aps]
user@host# set fast-aps-switch
```

```
[edit interfaces cstm1-0/1/0 sonet-options aps]
user@host# set fast-aps-switch
```

2. Configure bidirectional switching mode on both the working and protect circuits. To do this, configure the `switching-mode bidirectional` statement at the `[edit interfaces interface-name sonet-options aps]` hierarchy level on both the working and protect circuits.

```
[edit interfaces interface-name sonet-options aps]
user@host# set switching-mode bidirectional
```

For example:

```
[edit interfaces cstm1-0/0/0 sonet-options aps]
user@host# set switching-mode bidirectional
```

```
[edit interfaces cstm1-0/1/0 sonet-options aps]
user@host# set switching-mode bidirectional
```

3. If APS is configured in revertive mode, configure an appropriate value for revert time on both the working and protect circuits. To do this, configure the revert-time statement at the [edit interfaces *interface-name* sonet-options aps] hierarchy level on both the working and protect circuits.

```
[edit interfaces interface-name sonet-options aps]
user@host# set revert-time seconds
```

For example:

```
[edit interfaces cstm1-0/0/0 sonet-options aps]
user@host# set revert-time 600
```

```
[edit interfaces cstm1-0/1/0 sonet-options aps]
user@host# set revert-time 600
```

4. To prevent the logical interfaces in the data path from being shut down, configure appropriate hold-time values on *all* interfaces in the data path that support TDM.

```
[edit interfaces interface-name hold-time]
user@host# set up seconds down seconds
```

For example:

```
[edit interfaces cstm1-0/0/0 hold-time]
user@host# set up 1 down 400
```


SEE ALSO

| [fast-aps-switch](#) | 1502

Configuring Protection Features for Layer 2 Circuits


IN THIS CHAPTER

- Egress Protection LSPs for Layer 2 Circuits | 432
- Configuring Egress Protection Service Mirroring for BGP Signaled Layer 2 Services | 433
- Example: Configuring an Egress Protection LSP for a Layer 2 Circuit | 438
- Example: Configuring Layer 2 Circuit Protect Interfaces | 454
- Example: Configuring Layer 2 Circuit Switching Protection | 461

Egress Protection LSPs for Layer 2 Circuits

An egress protection LSP provides link protection for link between PE routers and CE devices as illustrated in [Figure 34 on page 432](#).

Figure 34: Egress Protection LSP



Device CE1 is multihomed to router PE1 and router PE2. Device CE2 is multihomed to router PE3 and router PE4. There are two paths connecting devices CE1 and CE2. The working path is CE2-PE3-P1-PE1-CE1, using pseudowire PW1. The protecting path is CE2-PE4-P2-PE2-CE1, using pseudowire PW2. Normally, traffic flows through the working path. When the end-to-end OAM between devices CE1 and

CE2 detects a failure on the working path, traffic will be switched from the working path to the protecting path.

In the topology shown in [Figure 34 on page 432](#), if there was a link or node failure in the core network (for example, a link failure from router P1 to PE1, from router PE3 to P1, or a node failure of router P1), MPLS fast reroute can be triggered on the transport LSPs between router PE3 and router PE1 to repair the connection within tens of milliseconds. Egress protection LSPs address the problem of when a link failure occurs at the edge of the network (for example, a link failure on router PE1 to device CE1).


An egress protection LSP has been configured from router PE1 to router PE2. In the event of a link failure between router PE1 and device CE1, traffic can be switched to the egress protection LSP. Traffic from device CE2 can now be routed through path PE3-P1-PE1-PE2 to reach device CE1.

Configuring Egress Protection Service Mirroring for BGP Signaled Layer 2 Services

Starting in Junos OS Release 14.2, Junos OS supports the restoration of egress traffic when there is a link or node failure in the egress PE node. If there is a link or node failure in the core network, a protection mechanism such as MPLS fast reroute can be triggered on the transport LSPs between the PE routers to repair the connection within tens of milliseconds. An egress protection LSP addresses the problem of a node-link failure at the edge of the network (for example, a failure of a PE router).

Figure 1 shows a simplified topology of the use case that explains this feature.

Figure 35: Egress Protection LSP Configured from Router PE1 to Router PE2



8042264

CE1 is multihomed to PE1 and PE2. There are two paths connecting CE1 and CE2. The working path is CE2-PE3-P-PE1-CE1, via pseudowire PW21. The protecting path is CE2-PE3-P-PE2-CE1, via pseudowire PW22. Traffic is flowing through the working path under normal circumstances. When the end-to-end OAM between CE1 and CE2 detects failure on the working path, traffic will be switched from the working path to the protecting path. The end-to-end failure detection and recovery relies on control plane hence should be relatively slow. To achieve faster protection, local repair mechanisms similar to those used by MPLS fast reroute should be used. In Figure 1 above, if link or node failed in the core network (like link failure on P-PE1, P-PE3, or node failure on P), the MPLS fast reroute will happen on the transport LSPs between PE1 and PE3. The failure could be locally repaired within tens of milliseconds. However, if link or node failure happens at the edge (like link failure on PE3-CE2 or node failure on PE3), there is no local repair currently so we have to rely on the CE1-CE2 end-to-end protection to repair the failure.

- Device CE2—Traffic origin
- Router PE3—Ingress PE router
- Router PE1— (Primary) Egress PE router
- Router PE2—Protector PE router
- Device CE1—Traffic destination

When the link between CE1- PE1 goes down, PE1 will briefly redirect that traffic towards CE1, to PE2. PE2 forwards it to CE1 until ingress router PE3 recalculates to forward the traffic to PE2.

Initially the traffic direction was; CE2 - PE3 - P - PE1 - CE1.

When the link between CE1- PE1 goes down, the traffic will be; CE2 - PE3 - P - PE1 - PE2 -CE1. PE3 then recalculates the path; CE2 - PE3 - P - PE2 - CE1.

1. Configure RSVP on PE1, PE2, and PE3.

```
[edit protocols]
user@PE1# set interface all
user@PE2# set interface all
user@PE3# set interface all
```

2. Configure MPLS.

```
[edit protocols mpls]
user@PE1# set interface all
user@PE2# set interface all
user@PE3# set interface all
```

3. Set PE1 as primary and PE2 as protector nodes.

```
[edit protocols mpls]
user@PE1# set egress-protection context-identifier address primary
user@PE2# set egress-protection context-identifier address protector
```

4. Enable egress-protection on PE1 and PE2.

```
[edit protocols bgp]
user@PE1# set group ibgp family l2vpn egress-protection
user@PE2# set group ibgp family l2vpn egress-protection
```

5. Configure LDP and ISIS on PE1, PE2, and PE3.

```
[edit protocols ldp]
user@PE1# set interface all
user@PE2# set interface all
user@PE3# set interface all
```

```
[edit protocols isis]
user@PE1# set interface all point-to-point
user@PE2# set interface all point-to-point
user@PE3# set interface all point-to-point
```

6. Configure a load balancing policy at PE1, PE2, and PE3.

```
[edit]
user@PE1# set policy-options policy-statement lb then load-balance per-packet
user@PE2# set policy-options policy-statement lb then load-balance per-packet
user@PE3# set policy-options policy-statement lb then load-balance per-packet
```

7. Configure the routing options at PE1, PE2, and PE3, to export routes based on the load balancing policy.

```
[edit]
user@PE1# set routing-options traceoptions file ro.log
user@PE1# set routing-options traceoptions flag normal
user@PE1# set routing-options traceoptions flag route
```

```
user@PE1# set routing-options autonomous-system 100
user@PE1# set routing-options forwarding-table export lb
```

```
[edit]
user@PE2# set routing-options traceoptions file ro.log
user@PE2# set routing-options traceoptions flag normal
user@PE2# set routing-options traceoptions flag route
user@PE2# set routing-options autonomous-system 100
user@PE2# set routing-options forwarding-table export lb
```

```
[edit]
user@PE3# set routing-options traceoptions file ro.log
user@PE3# set routing-options traceoptions flag normal
user@PE3# set routing-options traceoptions flag route
user@PE3# set routing-options autonomous-system 100
user@PE3# set routing-options forwarding-table export lb
```

8. Configure BGP at PE1 to advertise nrli from the routing instance with context-ID as next-hop.

```
[edit]
user@PE1# set routing-instances foo egress-protection context-identifier context-identifier
```

9. Configure l2vpn at PE1, PE2, and PE3

At PE1:

```
[edit routing-instances]
foo {
  instance-type l2vpn;
  egress-protection {
    context-identifier {
      198.51.100.0;
    }
  }
  interface ge-2/0/2.0;
  route-distinguisher 10.255.183.58:1;
  vrf-target target:9000:1;
  protocols {
    l2vpn {
      encapsulation-type ethernet-vlan;
    }
  }
}
```

```

        site foo {
            site-identifier 1;
            multi-homing;
            site-preference primary;
            interface ge-2/0/2.0 {
                remote-site-id 2;
            }
        }
    }
}

```

At PE2:

```

[edit routing-instances]
foo {
    instance-type l2vpn;
    egress-protection {
        protector;
    }
    interface ge-2/0/2.0;
    route-distinguisher 10.255.183.57:1;
    vrf-target target:9000:1;
    protocols {
        l2vpn {
            encapsulation-type ethernet-vlan;
            site foo{
                site-identifier 1;
                multi-homing;
                site-preference backup;
                interface ge-2/0/2.0 {
                    remote-site-id 2;
                }
            }
        }
    }
}

```


At PE3:

```
[edit routing-instances]
foo {
  instance-type l2vpn;
  interface ge-2/1/2.0;
  route-distinguisher 10.255.183.61:1;
  vrf-target target:9000:1;
  protocols {
    l2vpn {
      encapsulation-type ethernet-vlan;
      site foo {
        site-identifier 2;
        interface ge-2/1/2.0;
      }
    }
  }
}
```

Release History Table

Release	Description
14.2	Starting in Junos OS Release 14.2, Junos OS supports the restoration of egress traffic when there is a link or node failure in the egress PE node.

Example: Configuring an Egress Protection LSP for a Layer 2 Circuit

IN THIS SECTION

- [Requirements | 439](#)
- [Egress Protection LSP Overview | 439](#)
- [Egress Protection LSP Configuration | 441](#)

This example shows how to configure an egress protection LSP.

Requirements

Egress protection LSPs are supported on Juniper Networks MX Series routers only. This requirement applies to the PE routers facilitating the egress protection LSP.

Egress Protection LSP Overview

IN THIS SECTION

- [Topology | 440](#)

If there is a link or node failure in the core network, a protection mechanism such as MPLS fast reroute can be triggered on the transport LSPs between the PE routers to repair the connection within tens of milliseconds. An egress protection LSP addresses the problem of when a link failure occurs at the edge of the network (for example, a link failure between a PE router and a CE device). Egress protection LSPs do not address the problem of a node failure at the edge of the network (for example, a failure of a PE router). An egress protection LSP is an RSVP-signaled ultimate hop popping LSP.


This example includes the following configuration concepts and statements that are unique to the configuration of an egress protection LSP:

- **context-identifier**—Specifies an IPv4 address used to define the pair of PE routers participating in the egress protection LSP. The context identifier is used to assign an identifier to the protector PE router. The identifier is propagated to the other PE routers participating in the network, making it possible for the protected egress PE router to signal the egress protection LSP to the protector PE router.
- **egress-protection**—Configures the protector information for the protected Layer 2 circuit and configures the protector Layer 2 circuit at the `[edit protocols l2circuit]` hierarchy level. Configures an LSP as an egress protection LSP at the `[edit protocols mpls label-switched-path lsp-name]` hierarchy level. It also configures the context identifier at the `[edit protocols mpls]` hierarchy level.
- **protected-l2circuit**—Specifies which Layer 2 circuit is to be protected by the egress protect LSP. This statement includes the following sub-statements: `ingress-pe`, `egress-pe`, and `virtual-circuit-id`. These sub-statements specify the address of the PE router at the ingress of the Layer 2 circuit, the address of the PE router at the egress of the Layer 2 circuit, and the Layer 2 circuit's identifier respectively.
- **protector-interface**—Specify the interface used by the egress protection LSP. In the event of a local link failure to a CE device, the egress protect LSP uses the interface specified to communicate with the protector PE router.
- **protector-pe**—Specify the IPv4 address of the protector PE router. The protector PE router must have a connection to the same CE device as the protected PE router for the egress protect LSP to

function. This statement includes the following sub-statements: context-identifier and lsp. The lsp statement specifies the LSP to be used as the actual egress protection LSP.

Topology

Figure 36: Egress Protection LSP Configured from Router PE2 to Router PE3



Pseudowires are configured along two paths, one from router PE1 to router PE2 (pseudowire 12) and one from router PE1 to router PE3 (pseudowire 13). In the event of a failure on the link between router PE2 and device CE2, traffic is switched to the egress protection LSP configured between router PE2 and router PE3 (the protector PE router):

- Device CE1—Traffic origin
- Router PE1—Ingress PE router
- Router PE2—Egress PE router
- Router PE3—Protector PE router
- Device CE2—Traffic destination

This example shows how to configure routers PE1, PE2, and PE3.

Egress Protection LSP Configuration

IN THIS SECTION

- [CLI Quick Configuration | 441](#)
- [Step-by-Step Procedure | 443](#)
- [Results | 449](#)

CLI Quick Configuration

To quickly configure an egress protection LSP, copy the following commands into a text file, modify the interface configurations to match your equipment, remove any line breaks, and then paste the commands into the CLI. This group of set commands is for router PE1.

```
set protocols rsvp interface ge-3/1/0.1
set protocols rsvp interface ge-3/1/3.2
set protocols mpls interface ge-3/1/0.1
set protocols mpls interface ge-3/1/3.2
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-3/1/0.1
set protocols ospf area 0.0.0.0 interface ge-3/1/3.2
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface ge-3/1/0.1
set protocols ldp interface ge-3/1/3.2
set protocols ldp interface lo0.0
set protocols l2circuit neighbor 192.0.2.3 interface fe-3/3/0.1 virtual-circuit-id 32
set protocols l2circuit neighbor 192.0.2.3 interface fe-3/3/0.1 egress-protection protector-
interface ge-3/1/2.2
set protocols l2circuit neighbor 192.0.2.4 interface ge-3/1/2.2 virtual-circuit-id 33
set policy-options policy-statement load-balance-example then load-balance per-packet
set routing-options router-id 192.0.2.2
set routing-options forwarding-table export load-balance-example
```

To quickly configure an egress protection LSP, copy the following commands into a text file, modify the interface configurations to match your equipment, remove any line breaks, and then paste the commands into the CLI. This group of set commands is for router PE2.

```
[edit]
set protocols rsvp tunnel-services
set protocols rsvp interface ge-2/3/0.3
set protocols rsvp interface ge-2/3/1.4 link-protection
set protocols ldp interface ge-2/3/0.3
set protocols ldp interface ge-2/3/1.4
set protocols ldp interface lo0.0
set protocols ldp upstream-label-assignment
set protocols mpls label-switched-path protected-lsp to 192.0.2.5
set protocols mpls label-switched-path protected-lsp egress-protection
set protocols mpls interface ge-2/3/0.3
set protocols mpls interface ge-2/3/1.4
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-2/3/0.3
set protocols ospf area 0.0.0.0 interface ge-2/3/1.4
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/2.5 virtual-circuit-id 23
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/2.5 egress-protection protector-pe
192.0.2.4
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/2.5 egress-protection protector-pe
context-identifier 192.0.2.5
set policy-options policy-statement load-balance-example then load-balance per-packet
set routing-options router-id 192.0.2.3
set routing-options forwarding-table export load-balance-example
```

To quickly configure an egress protection LSP, copy the following commands into a text file, modify the interface configurations to match your equipment, remove any line breaks, and then paste the commands into the CLI. This group of set commands is for router PE3.

```
set protocols rsvp tunnel-services
set protocols rsvp interface ge-2/0/0.6
set protocols rsvp interface ge-2/0/1.7
set protocols mpls interface ge-2/0/0.6
set protocols mpls interface ge-2/0/1.7
set protocols mpls egress-protection context-identifier 192.0.2.5 protector
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-2/0/0.6
```

```

set protocols ospf area 0.0.0.0 interface ge-2/0/1.7
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface ge-2/0/0.6
set protocols ldp interface ge-2/0/1.7
set protocols ldp interface lo0.0
set protocols ldp upstream-label-assignment
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/3.21 virtual-circuit-id 42
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/3.21 egress-protection protected-
l2circuit PW1
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/3.21 egress-protection protected-
l2circuit ingress-pe 192.0.2.2
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/3.21 egress-protection protected-
l2circuit egress-pe 192.0.2.3
set protocols l2circuit neighbor 192.0.2.2 interface ge-2/0/3.21 egress-protection protected-
l2circuit virtual-circuit-id 31

```

Step-by-Step Procedure

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure an egress protection LSP, complete the following steps for router PE1:

1. Configure RSVP. Include the interface linked to router PE2 and the interface linked to router PE3.

```

[edit]
user@PE1# edit protocols rsvp
[edit protocols rsvp]
user@PE1# set interface ge-3/1/0.1
[edit protocols rsvp]
user@PE1# set interface ge-3/1/3.2

```

2. Configure LDP. Include the interface linked to router PE2, the interface linked to router PE3, and the loopback interface.

```

[edit]
user@PE1# edit protocols ldp
[edit protocols ldp]
user@PE1# set interface ge-3/1/0.1

```

```
[edit protocols ldp]
user@PE1# set interface ge-3/1/3.2
[edit protocols ldp]
user@PE1# set interface lo0.0
```

3. Configure MPLS. Include the interface linked to router PE2 and the interface linked to router PE3.

```
[edit]
user@PE1# edit protocols mpls
[edit protocols mpls]
user@PE1# set interface ge-3/1/0.1
[edit protocols mpls]
user@PE1# set interface ge-3/1/3.2
```

4. Configure OSPF. Include the interface linked to router PE2, the interface linked to router PE3, and the loopback interface in the configuration for the OSPF area.

```
[edit]
user@PE1# edit protocols ospf
[edit protocols ospf]
user@PE1# set interface traffic-engineering
[edit protocols ospf]
user@PE1# set area 0.0.0.0 interface ge-3/1/0.1
[edit protocols ospf]
user@PE1# set area 0.0.0.0 interface ge-3/1/3.2
[edit protocols ospf]
user@PE1# set area 0.0.0.0 interface lo0.0 passive
```

5. Configure Layer 2 circuits to use the egress protection LSP to protect against a link failure to device CE1.

```
[edit]
user@PE1# edit protocols l2circuit
[edit protocols l2circuit]
user@PE1# set neighbor 192.0.2.3 interface fe-3/3/0.1 virtual-circuit-id 32
[edit protocols l2circuit]
user@PE1# edit neighbor 192.0.2.3
[edit protocols l2circuit neighbor 192.0.2.3]
user@PE1# set interface fe-3/3/0.1 egress-protection protector-interface ge-3/1/2.2
```

```
[edit protocols l2circuit]
user@PE1# set neighbor 192.0.2.4 interface ge-3/1/2.2 virtual-circuit-id 33
```

6. Configure a load balancing policy.

```
[edit]
user@PE1# set policy-options policy-statement load-balance-example then load-balance per-
packet
```

7. Configure the routing options to export routes based on the load balancing policy.

```
[edit]
user@PE1# set routing-options router-id 192.0.2.2
[edit]
user@PE1# set routing-options forwarding-table export load-balance-example
```

8. If you are done configuring the device, commit the configuration.

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure an egress protection LSP, complete the following steps for router PE2:

1. Configure RSVP. Include the interface linked to the ingress PE router and the interface linked to the CE device.

```
[edit]
user@PE2# edit protocols rsvp
[edit protocols rsvp]
user@PE2# set tunnel-services
[edit protocols rsvp]
user@PE2# set interface ge-2/3/0.3
[edit protocols rsvp]
user@PE2# set interface ge-2/3/1.4 link-protection
```


2. Configure LDP. Include the interface linked to the ingress PE router and the interface linked to the CE device.

```
[edit]
user@PE2# edit protocols ldp
[edit protocols ldp]
user@PE2# set interface ge-2/3/0.3
[edit protocols ldp]
user@PE2# set interface ge-2/3/1.4
[edit protocols ldp]
user@PE2# set interface lo0.0
[edit protocols ldp]
user@PE2# set upstream-label-assignment
```

3. Configure MPLS and the LSP which acts as the egress protection LSP.

```
[edit]
user@PE2# edit protocols mpls
[edit protocols mpls]
user@PE2# set interface ge-2/3/0.3
[edit protocols mpls]
user@PE2# set interface ge-2/3/1.4
[edit protocols mpls]
user@PE2# set label-switched-path protected-lsp to 192.0.2.5
[edit protocols mpls]
user@PE2# set label-switched-path protected-lsp egress-protection
```

4. Configure OSPF.

```
[edit]
user@PE2# edit protocols ospf
[edit protocols ospf]
user@PE2# set interface traffic-engineering
[edit protocols ospf]
user@PE2# set interface area 0.0.0.0 interface ge-2/3/0.3
[edit protocols ospf]
user@PE2# set interface area 0.0.0.0 interface ge-2/3/1.4
[edit protocols ospf]
user@PE2# set interface area 0.0.0.0 interface lo0.0 passive
```

5. Configure the Layer 2 circuit to use the egress protection LSP.

```
[edit]
user@PE2# edit protocols l2circuit
[edit protocols l2circuit]
user@PE2# set neighbor 192.0.2.2 interface ge-2/0/2.5 virtual-circuit-id 23
[edit protocols l2circuit]
user@PE2# edit neighbor 192.0.2.2
[edit protocols l2circuit neighbor 192.0.2.2]
user@PE2# set interface ge-2/0/2.5 egress-protectionprotector-pe 192.0.2.4
[edit protocols l2circuit neighbor 192.0.2.2]
user@PE2# set interface ge-2/0/2.5 egress-protection protector-pe context-identifier 192.0.2.5
```

6. Configure a load balancing policy.

```
[edit]
user@PE1# set policy-options policy-statement load-balance-example then load-balance per-
packet
```

7. Configure the routing options to export routes based on the load balancing policy.

```
[edit]
user@PE2# set routing-options router-id 192.0.2.3
[edit]
user@PE2# set routing-options forwarding-table export load-balance-example
```

8. If you are done configuring the device, commit the configuration.

Step-by-Step Procedure

To configure an egress protection LSP, complete the following steps for router PE3:

1. Configure RSVP. Include the interface linked to the ingress PE router and the interface linked to the CE device.

```
[edit]
user@PE3# edit protocols rsvp
[edit protocols rsvp]
user@PE3# set tunnel-services
```

```
[edit protocols rsvp]
user@PE3# set interface ge-2/0/0.6
[edit protocols rsvp]
user@PE3# set interface ge-2/0/1.7
```

2. Configure LDP. Include the interface linked to the ingress PE router and the interface linked to the CE device.

```
[edit]
user@PE3# edit protocols ldp
[edit protocols ldp]
user@PE3# set interface ge-2/0/0.6
[edit protocols ldp]
user@PE3# set interface ge-2/0/1.7
[edit protocols ldp]
user@PE3# set interface lo0.0
[edit protocols ldp]
user@PE3# set upstream-label-assignment
```

3. Configure MPLS and the LSP which acts as the egress protection LSP.

```
[edit]
user@PE3# edit protocols mpls
[edit protocols mpls]
user@PE3# set interface ge-2/0/0.6
[edit protocols mpls]
user@PE3# set interface ge-2/0/1.7
[edit protocols mpls]
user@PE3# set egress-protection context-identifier 192.0.2.5 protector
```

4. Configure OSPF.

```
[edit]
user@PE3# edit protocols ospf
[edit protocols ospf]
user@PE3# set interface traffic-engineering
[edit protocols ospf]
user@PE3# set area 0.0.0.0 interface ge-2/0/0.6
[edit protocols ospf]
user@PE3# set area 0.0.0.0 interface ge-2/0/1.7
```

```
[edit protocols ospf]
user@PE3# set area 0.0.0.0 interface lo0.0 passive
```

5. Configure the Layer 2 circuit to use the egress protection LSP.

```
[edit]
user@PE3# edit protocols l2circuit
[edit protocols l2circuit]
user@PE3# set neighbor 192.0.2.2 interface ge-2/0/3.21 virtual-circuit-id 42
[edit protocols l2circuit]
user@PE3# edit neighbor 192.0.2.2
[edit protocols l2circuit neighbor 192.0.2.2]
user@PE3# set interface ge-2/0/3.21 egress-protection protected-l2circuit ingress-pe 192.0.2.2
[edit protocols l2circuit neighbor 192.0.2.2]
user@PE3# set interface ge-2/0/3.21 egress-protection protected-l2circuit egress-pe 192.0.2.3
[edit protocols l2circuit neighbor 192.0.2.2]
user@PE3# set interface ge-2/0/3.21 egress-protection protected-l2circuitvirtual-circuit-id 31
```

6. If you are done configuring the device, commit the configuration.

Results

From configuration mode, confirm your configuration on router PE1 by entering the **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
[edit]
user@PE1# show protocols
rsvp {
    interface ge-3/1/0.1;
    interface ge-3/1/3.2;
}
mpls {
    interface ge-3/1/0.1;
    interface ge-3/1/3.2;
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface ge-3/1/0.1;
        interface ge-3/1/3.2;
```

```

        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-3/1/0.1;
    interface ge-3/1/3.2;
    interface lo0.0;
}
l2circuit {
    neighbor 192.0.2.3 {
        interface fe-3/3/0.1 {
            virtual-circuit-id 32;
            egress-protection {
                protector-interface ge-3/1/2.2;
            }
        }
    }
    neighbor 192.0.2.4 {
        interface ge-3/1/2.2 {
            virtual-circuit-id 33;
        }
    }
}
[edit]
user@PE1# show policy-options
policy-statement load-balance-example {
    then {
        load-balance per-packet;
    }
}
[edit]
user@PE1# show routing-options
router-id 192.0.2.2;
forwarding-table {
    export load-balance-example;
}

```

From configuration mode, confirm your configuration on router PE2 by entering the **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
[edit]
user@PE2# show protocols
rsvp {
    tunnel-services;
    interface ge-2/3/0.3;
    interface ge-2/3/1.4 {
        link-protection;
    }
}
mpls {
    label-switched-path protected-lsp {
        to 192.0.2.5;
        egress-protection;
    }
    interface ge-2/3/0.3;
    interface ge-2/3/1.4;
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface ge-2/3/0.3;
        interface ge-2/3/1.4;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-2/3/0.3;
    interface ge-2/3/1.4;
    interface lo0.0;
    upstream-label-assignment;
}
l2circuit {
    neighbor 192.0.2.2 {
        interface ge-2/0/2.5 {
            virtual-circuit-id 23;
            egress-protection {
```

```

        protector-pe 192.0.2.4 context-identifier 192.0.2.5;
    }
}
}
}

```

```

[edit]
user@PE2# show policy-options
policy-options {
    policy-statement load-balance-example {
        then {
            load-balance per-packet;
        }
    }
}

```

```

[edit]
user@PE2# show routing-options
routing-options {
    router-id 192.0.2.3;
    forwarding-table {
        export load-balance-example;
    }
}

```

From configuration mode, confirm your configuration on router PE3 by entering the **show protocols** command. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```

[edit]
user@PE3# show protocols
rsvp {
    tunnel-services;
    interface ge-2/0/0.6;
    interface ge-2/0/1.7;
}
mpls {
    interface ge-2/0/0.6;
    interface ge-2/0/1.7;
}

```

```

    egress-protection {
        context-identifier 192.0.2.5 {
            protector;
        }
    }
}

ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface ge-2/0/0.6;
        interface ge-2/0/1.7;
        interface lo0.0 {
            passive;
        }
    }
}

ldp {
    interface ge-2/0/0.6;
    interface ge-2/0/1.7;
    interface lo0.0;
    upstream-label-assignment;
}

l2circuit {
    neighbor 192.0.2.2 {
        interface ge-2/0/3.21 {
            virtual-circuit-id 42;
            egress-protection {
                protected-l2circuit PW1 ingress-pe 192.0.2.2 egress-pe 192.0.2.3 virtual-circuit-
id 31;
            }
        }
    }
}
}

```


Example: Configuring Layer 2 Circuit Protect Interfaces


IN THIS SECTION

- Configuring Router PE1 | 455
- Configuring Router PE2 | 457
- Configuring Router CE1 | 459
- Configuring Router CE2 | 460

This example illustrates how you might configure a Layer 2 circuit with protect interfaces. Protect interfaces act as backups for their associated interfaces. The primary interface has priority over the protect interface and carries network traffic as long as it is functional. If the primary interface fails, the protect interface is activated. These interfaces can also share the same virtual path identifier (VPI) or virtual circuit identifier (VCI).

Figure 37 on page 454 shows the network topology used in this example.

Figure 37: Layer 2 Circuits Using Protect Interfaces



The following sections describe how to configure a Layer 2 circuit to use a protect interface:

Configuring Router PE1

Configure an interface for traffic to Router CE1 from Router PE1 at the [edit interfaces] hierarchy level:

```
[edit interfaces]
so-0/2/2 {
  description "Router CE1 so-0/2/2";
  no-keepalives;
  encapsulation frame-relay-ccc;
  unit 1 {
    encapsulation frame-relay-ccc;
    point-to-point;
    dlci 600;
  }
  unit 2 {
    encapsulation frame-relay-ccc;
    point-to-point;
    dlci 602;
  }
}
```

Configure an interface for traffic to Router CE1 from Router PE1 at the [edit interfaces] hierarchy level. Logical interface so-0/2/0.2 acts as the protect interface for so-0/2/2.2, and logical interface so-0/2/0.1 acts as the protect interface for so-0/2/2.1:

```
[edit interfaces]
so-0/2/0 {
  description "to Router CE1 so-0/3/0";
  no-keepalives;
  encapsulation frame-relay-ccc;
  unit 1 {
    encapsulation frame-relay-ccc;
    dlci 600;
  }
  unit 2 {
    encapsulation frame-relay-ccc;
    dlci 602;
  }
}
```

Configure an interface for traffic to Router PE2 from Router PE1 at the [edit interfaces] hierarchy level:

```
[edit interfaces]
so-0/2/1 {
  description "to Router PE2 so-1/0/1";
  unit 0 {
    family inet {
      address 192.0.2.0/24 {
        destination 192.0.2.4;
      }
    }
    family iso;
    family mpls;
  }
}
```

Configure an interface for traffic to Router PE2 from Router PE1 at the [edit interfaces] hierarchy level:

```
[edit interfaces]
so-0/2/3 {
  description "Router PE2 so-1/0/3";
  unit 0 {
    family inet;
    family iso;
    family mpls;
  }
  lo0 {
    unit 0 {
      family inet {
        address 198.51.100.0/24;
        address 10.100.40.200/32;
      }
      family iso {
        address 47.0005.80ff.f800.0000.0108.0001.1921.6800.4213.00;
      }
    }
  }
}
```

Configure the Layer 2 circuit by including the `l2circuit` statement at the `[edit protocols]` hierarchy level. The logical interfaces for the Layer 2 circuits and their corresponding protect interfaces are included here:

```
[edit protocols]
l2circuit {
  neighbor 10.100.40.210 {
    interface so-0/2/2.2 {
      protect-interface so-0/2/0.2;
      virtual-circuit-id 2;
      no-control-word;
    }
    interface so-0/2/2.1 {
      protect-interface so-0/2/0.1;
      virtual-circuit-id 1;
      no-control-word;
    }
  }
}
```

Configuring Router PE2

Configure an interface for traffic to Router CE2 from Router PE2:

```
[edit interfaces]
so-1/0/0 {
  description "to Router CE2 so-0/2/0";
  no-keepalives;
  encapsulation frame-relay-ccc;
  unit 1 {
    encapsulation frame-relay-ccc;
    point-to-point;
    dlci 700;
  }
  unit 2 {
    encapsulation frame-relay-ccc;
    point-to-point;
    dlci 702;
  }
}
```

Configure an interface for traffic to Router PE1 from Router PE2:

```
[edit interfaces]
so-1/0/1 {
  description "to Router PE1 so-0/2/1";
  unit 0 {
    family inet {
      address 192.0.2.4/32 {
        destination 192.0.2.22;
      }
    }
    family iso;
    family mpls;
  }
}
```

Configure an interface for traffic to Router PE1 from Router PE2:

```
[edit interfaces]
so-1/0/3 {
  description "to Router PE1 so-0/2/3";
  unit 0 {
    family inet;
    family iso;
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 198.51.100.0/24;
      address 10.100.40.210/32;
    }
    family iso {
      address 47.0005.80ff.f800.0000.0108.0001.1921.6800.4216.00;
    }
  }
}
```

Configure the Layer 2 circuit at the [edit protocols] hierarchy level:

```
[edit protocols]
l2circuit {
  neighbor 10.100.40.200 {
    interface so-1/0/0.1 {
      virtual-circuit-id 1;
      no-control-word;
    }
    interface so-1/0/0.2 {
      virtual-circuit-id 2;
      no-control-word;
    }
  }
}
```

Configuring Router CE1

Configure an interface for traffic to Router PE1 from Router CE1:

```
[edit interfaces]
so-0/3/0 {
  description "to Router PE1 so-0/2/0";
  no-keepalives;
  encapsulation frame-relay;
  unit 1 {
    dlci 601;
    family inet {
      address 203.0.113.1;
    }
  }
}
```

Configure an interface for traffic to Router PE1 from Router CE1:

```
[edit interfaces]
so-0/3/1 {
  description "Router PE1 so-0/2/2";
  no-keepalives;
  encapsulation frame-relay;
```

```

unit 0 {
    dlci 600;
    family inet {
        address 10.10.10.1/24;
        address 203.0.113.2/24;
    }
    family iso;
    family mpls;
}
unit 2 {
    dlci 602;
    family inet {
        address 203.0.113.3/24;
    }
}
}

```

Configuring Router CE2

Configure an interface for traffic to Router PE2 from Router CE2:

```

[edit interfaces]
so-0/2/0 {
    description "to Router PE2 so-1/0/0";
    no-keepalives;
    encapsulation frame-relay;
    unit 1 {
        dlci 700;
        family inet {
            address 10.10.10.2/24;
            address 203.0.113.5/24;
            address 203.0.113.6/24;
        }
    }
    unit 2 {
        dlci 702;
        family inet {
            address 203.0.113.7/24;
        }
    }
}

```

```
}
}
```

Example: Configuring Layer 2 Circuit Switching Protection

IN THIS SECTION

- [Requirements | 461](#)
- [Overview | 462](#)
- [Configuration | 463](#)

Unlike Layer 2 circuit protect interfaces (see ["Example: Configuring Layer 2 Circuit Protect Interfaces" on page 454](#)), which provide traffic protection for paths configured between the PE routers and CE routers, Layer 2 circuit switching protection provides traffic protection for the paths configured between the PE routers. In the event the path used by a Layer 2 circuit fails, traffic can be switched to an alternate path (or protection path). Switching protection is supported for locally switched Layer 2 circuits and provides 1 to 1 protection for each Layer 2 circuit interface.

When you enable Layer 2 circuit switching protection, each Layer 2 circuit interface requires the following paths:

- Working path—Used by the Layer 2 circuit when working normally.
- Protection path—Used by the Layer 2 circuit when the working path fails.

Requirements

This example uses the following hardware and software components:

- MX Series 5G Universal Routing Platforms
- Junos OS Release 12.3

Overview

IN THIS SECTION

- Topology | 462


Each working path can be configured to have either a protection path routed directly to the neighboring PE router (as shown in [Figure 38 on page 462](#)) or indirectly using a pseudowire configured through an intermediate PE router (as shown in [Figure 39 on page 463](#) and [Figure 40 on page 463](#)). The protection path provides failure protection for the traffic flowing between the PE routers. Ethernet OAM monitors the status of these paths. When OAM detects a failure, it reroutes the traffic from the failed working path to the protection path. You can configure OAM to revert the traffic automatically to the working path when it is restored. You can also manually switch traffic between the working path, the protection path, and back.

NOTE: Non-stop routing (*NSR*) and graceful routing engine switchover (*GRES*) do not support Layer 2 circuit switching protection.

Topology

[Figure 38 on page 462](#) illustrates Layer 2 circuit local switching. There are two OAM sessions running between Router PE1 and Router PE2. One OAM session is configured over the working path and the other is configured over the protection path.


Figure 38: Connection Protection Enabled Between Router PE1 and Router PE2



In [Figure 39 on page 463](#) and [Figure 40 on page 463](#), there are two OAM sessions running between Router PE1 and Router PE2. For Figure 2, one OAM session is configured over the working path


between Router PE1 and Router PE2. The other OAM session is configured over the protection path between Router PE1 and Router PE3 to Router PE2.

Figure 39: Connection Protection Using a Pseudowire Configured through Router PE3 as the Protection Path



For [Figure 40 on page 463](#), one OAM session is configured over the working path, the pseudowire between Router PE1 and Router PE3, then to Router PE2. The other OAM session is configured on the protect path between Router PE1 and Router PE2.

Figure 40: Connection Protection Using a Pseudowire Configured through Router PE3 as the Working Path



Configuration

IN THIS SECTION

- [Configuring Connection Protection Between Two PE Routers | 464](#)
- [Verifying that OAM CFM Connections are Active | 468](#)
- [Configuring Connection Protection Using Another PE Router for the Protection Path | 469](#)
- [Verifying that OAM CFM Connections are Active | 474](#)

- [Configuring Connection Protection Using an Another PE Router for the Working Path | 475](#)
- [Verifying that OAM CFM Connections are Active | 479](#)

The following sections describe how to configure each of the variations of Layer 2 circuit connection protection:

Configuring Connection Protection Between Two PE Routers

Step-by-Step Procedure

To configure Layer 2 Circuit switching protection as shown in [Figure 38 on page 462](#) on Router PE1:

1. Configure the Layer 2 circuit on Router PE1.

```
[edit protocols l2circuit]
user@PE1# set local-switching interface ge-2/0/2.0 connection-protection
user@PE1# set local-switching interface ge-2/0/2.0 end-interface interface ge-2/0/1.0
user@PE1# set local-switching interface ge-2/0/2.0 end-interface backup-interface ge-2/0/1.1
```

2. Configure the routing policy on Router PE1.

```
[edit policy-options]
user@PE1# set policy-statement protection-policy then load-balance per-packet
```

3. Enable the routing policy on Router PE1.

```
[edit routing-options]
user@PE1# set forwarding-table export protection-policy
```

4. Configure OAM on Router PE1. OAM is used to monitor the working path between Router PE1 and Router PE2. In the event of a failure on the working path, traffic is switched automatically to the

protection path. A connectivity fault management (CFM) session is configured on the working path and on the protection path. Begin by configuring the OAM maintenance domain.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md level 5
```

5. Configure OAM on Router PE1 for the working path.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working continuity-check interval 100ms
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 interface ge-2/0/1.0
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 interface working
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 direction down
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 remote-mep 103
```

6. Configure OAM on Router PE1 for the protection path.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection continuity-check interval 100ms
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 interface ge-2/0/1.1
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 interface protect
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 direction down
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 remote-mep 104
```

7. Configure the OAM maintenance domain on Router PE2.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md level 5
```

8. Configure OAM on Router PE2 for the working path.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working continuity-check interval 100ms
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 interface ge-2/0/1.0
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 interface working
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 direction down
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 remote-mep 1000
```

9. Configure OAM on Router PE2 for the protection path.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection continuity-check interval 100ms
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 interface ge-2/0/1.1
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 interface protect
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 direction down
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 remote-mep 1001
```

Results

From configuration mode on Router PE1, confirm your configuration by entering the **show protocols l2circuit**, **show policy-options**, **show routing-options**, and **show protocols oam ethernet** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
user@host> show protocols l2circuit
local-switching {
  interface ge-2/0/2.0 {
    connection-protection;
  end-interface {
```

```

        interface ge-2/0/1.0;
        backup-interface ge-2/0/1.1;
    }
}
}

```

```

user@host> show policy-options
policy-statement protection-policy {
    then {
        load-balance per-packet;
    }
}

```

```

user@host> show routing-options
forwarding-table {
    export protection-policy;
}

```

```

user@host> show protocols oam ethernet
connectivity-fault-management {
    maintenance-domain l2circuit-example-md {
        level 5;
        maintenance-association working {
            continuity-check {
                interval 100ms;
            }
            mep 1000 {
                interface ge-2/0/1.0 working;
                direction down;
                remote-mep 103;
            }
        }
        maintenance-association protection {
            continuity-check {
                interval 100ms;
            }
            mep 1001 {
                interface ge-2/0/1.1 protect;
                direction down;
            }
        }
    }
}

```

```

        remote-mep 104;
    }
}
}
}

```

From configuration mode on Router PE2, confirm your configuration by entering the **show protocols oam ethernet** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```

connectivity-fault-management {
  maintenance-domain l2circuit-example-md {
    level 5;
    maintenance-association working {
      continuity-check {
        interval 100ms;
      }
      mep 103 {
        interface ge-2/0/1.0 working;
        direction down;
        remote-mep 1000;
      }
    }
    maintenance-association protection {
      continuity-check {
        interval 100ms;
      }
      mep 104 {
        interface ge-2/0/1.1 protect;
        direction down;
        remote-mep 1001;
      }
    }
  }
}
}
}

```

Verifying that OAM CFM Connections are Active

Purpose

Verify that the CFM connections are active on each of the PE routers.

Action

Execute the following command on each of the PE routers.

1. Verify that the CFM working connection on Router PE1 is active.

```
user@ PE1> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association working
Interface status: Active, Link status: Up
```

2. Verify that the CFM protect connection on Router PE1 is active

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association protection
Interface status: Active, Link status: Up
```

3. Verify that the CFM working connection on Router PE2 is active.

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association working
Interface status: Active, Link status: Up
```

4. Verify that the CFM protect connection on Router PE2 is active.

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association protection
Interface status: Active, Link status: Up
```

Configuring Connection Protection Using Another PE Router for the Protection Path

Step-by-Step Procedure

To configure Layer 2 Circuit switching protection as shown in [Figure 39 on page 463](#) on Router PE1:

1. Configure the Layer 2 circuit on Router PE1.

```
[edit protocols l2circuit]
user@PE1# set local-switching interface ge-2/0/2.0 connection-protection
```



```

user@PE1# set local-switching interface ge-2/0/2.0 backup-neighbor 192.0.2.2 virtual-
circuit-id 2
user@PE1# set local-switching interface ge-2/0/2.0 backup-neighbor 192.0.2.2 community
example
user@PE1# set local-switching interface ge-2/0/2.0 end-interface interface ge-2/0/1.0

```

2. Configure the routing policy on Router PE1.

```

[edit policy-options]
user@PE1# set policy-statement load-balance then load-balance per-packet
user@PE1# set policy-statement protection-policy term protect from community example
user@PE1# set policy-statement protection-policy term protect then install-nexthop lsp-
regex lsp-protect-*

```

3. Configure the community.

```

[edit policy-options]
user@PE1# set community example members 65100:10

```

4. Configure the routing options on Router PE1.

```

[edit routing-options]
user@PE1# set forwarding-table export load-balance

```

5. Configure OAM on Router PE1 to setup the maintenance domain. OAM is used to monitor the working path between Router PE1 and Router PE2. In the event of a failure on the working path, traffic is switched automatically to the protection path.

```

[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md level 5

```

6. Configure OAM on Router PE1 for the working path.

```

[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 interface ge-2/0/1.0
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 direction down

```

```
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 remote-mep 103
```

7. Configure OAM on Router PE1 for the protection path.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 interface ge-2/0/0.0
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 direction down
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 remote-mep 104
```

8. Configure OAM on Router PE2 to setup the maintenance domain.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md level 5
```

9. Configure OAM on Router PE2 for the working path.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 interface ge-2/0/1.0
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 direction down
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 remote-mep 1000
```

10. Configure OAM on Router PE2 for the protection path.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 interface ge-2/0/0.0
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 direction down
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 remote-mep 1001
```

Results

From configuration mode on Router PE1, confirm your configuration by entering the **show protocols l2circuit**, **show policy-options**, **show routing-options**, and **show protocols oam ethernet** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
user@host> show protocols l2circuit
local-switching {
  interface ge-2/0/2.0 {
    connection-protection;
    backup-neighbor 192.0.2.2 {
      virtual-circuit-id 2;
      community example;
    }
  }
  end-interface {
    interface ge-2/0/1.0;
  }
}
```

```
user@host> show policy-options
community example members 65100:10;
policy-statement load-balance {
  then {
    load-balance per-packet;
  }
}
policy-statement protection-policy {
  term protect {
    from community example;
    then {
      install-nexthop lsp-regex lsp-protect-*;
    }
  }
}
```

```
user@host> show routing-options
forwarding-table {
```

```
export load-balance;
}
```

```
user@host> show protocols oam ethernet
connectivity-fault-management {
  maintenance-domain l2circuit-example-md {
    level 5;
    maintenance-association working {
      mep 1000 {
        interface ge-2/0/1.0;
        direction down;
        remote-mep 103;
      }
    }
    maintenance-association protection {
      mep 1001 {
        interface ge-2/0/0.0;
        direction down;
        remote-mep 104;
      }
    }
  }
}
```

From configuration mode on Router PE2, confirm your configuration by entering the **show protocols oam ethernet** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
connectivity-fault-management {
  maintenance-domain l2circuit-example-md {
    level 5;
    maintenance-association working {
      mep 103 {
        interface ge-2/0/1.0;
        direction down;
        remote-mep 1000;
      }
    }
    maintenance-association protection {
      mep 104 {
        interface ge-2/0/0.0;
```

```

        direction down;
        remote-mep 1001;
    }
}
}
}
}

```

Verifying that OAM CFM Connections are Active

Purpose

Verify that the CFM connections are active on each of the PE routers.

Action

Execute the following command on each of the PE routers.

1. Verify that the CFM working connection on Router PE1 is active.

```

user@ PE1> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association working
Interface status: Active, Link status: Up

```

2. Verify that the CFM protect connection on Router PE1 is active

```

user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association protection
Interface status: Active, Link status: Up

```

3. Verify that the CFM working connection on Router PE2 is active.

```

user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association working
Interface status: Active, Link status: Up

```

4. Verify that the CFM protect connection on Router PE2 is active.

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain
l2circuit-example-md maintenance-association protection
Interface status: Active, Link status: Up
```

Configuring Connection Protection Using an Another PE Router for the Working Path

Step-by-Step Procedure

To configure Layer 2 Circuit switching protection as shown in [Figure 40 on page 463](#) on Router PE1:

1. Configure the Layer 2 circuit on Router PE1.

```
[edit protocols l2circuit]
user@PE1# set neighbor 192.0.2.2 interface ge-2/0/2.0 virtual-circuit-id 2
user@PE1# set neighbor 192.0.2.2 interface ge-2/0/2.0 community example
user@PE1# set neighbor 192.0.2.2 interface ge-2/0/2.0 connection-protection
user@PE1# set neighbor 192.0.2.2 interface ge-2/0/2.0 backup-neighbor 192.0.2.3 virtual-
circuit-id 3
user@PE1# set neighbor 192.0.2.2 interface ge-2/0/2.0 backup-neighbor 192.0.2.3 standby
```

2. Configure the policies on Router PE1.

```
[edit policy-options]
user@PE1# set policy-statement load-balance then load-balance per-packet
user@PE1# set policy-statement protection-policy term protect from community example
user@PE1# set policy-statement protection-policy term protect then install-nexthop lsp-
regex lsp-primary
```

3. Configure the community.

```
[edit policy-options]
user@PE1# set community example members 65100:10
```

4. Configure the routing options on Router PE1.

```
[edit routing-options]
user@PE1# set forwarding-table export load-balance
```

5. Configure OAM on Router PE1 to setup the maintenance domain. OAM is used to monitor the working path between Router PE1 and Router PE2. In the event of a failure on the working path, traffic is switched automatically to the protection path.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md level 5
```

6. Configure OAM on Router PE1 for the working path.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 interface ge-2/0/0.0
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 direction down
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 1000 remote-mep 103
```

7. Configure OAM on Router PE1 for the protection path.

```
[edit protocols oam ethernet]
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 interface ge-2/0/1.0
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 direction down
user@PE1# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 1001 remote-mep 104
```

8. Configure OAM on Router PE2 to setup the maintenance domain.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md level 5
```

9. Configure OAM on Router PE2 for the working path.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 interface ge-2/0/0.0
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 direction down
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association working mep 103 remote-mep 1000
```

10. Configure OAM on Router PE2 for the protection path.

```
[edit protocols oam ethernet]
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 interface ge-2/0/1.0
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 direction down
user@PE2# set connectivity-fault-management maintenance-domain l2circuit-example-md
maintenance-association protection mep 104 remote-mep 1001
```

Results

From configuration mode on Router PE1, confirm your configuration by entering the **show protocols l2circuit**, **show policy-options**, **show routing-options**, and **show protocols oam ethernet** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```
user@host> show protocols l2circuit
neighbor 192.0.2.2 {
  interface ge-2/0/2.0 {
    virtual-circuit-id 2;
    community example;
    connection-protection;
    backup-neighbor 192.0.2.3 {
      virtual-circuit-id 3;
      standby;
    }
  }
}
```



```

    }
}

```

```

user@host> show policy-options
community example members 65100:10;
policy-statement load-balance {
    then {
        load-balance per-packet;
    }
}
policy-statement protection-policy {
    term protect {
        from community example;
        then {
            install-nexthop lsp-regex lsp-primary;
        }
    }
}

```

```

user@host> show routing-options
forwarding-table {
    export load-balance;
}

```

```

user@host> show protocols oam ethernet
connectivity-fault-management {
    maintenance-domain l2circuit-example-md {
        level 5;
        maintenance-association working {
            mep 1000 {
                interface ge-2/0/0.0;
                direction down;
                remote-mep 103;
            }
        }
        maintenance-association protection {
            mep 1001 {
                interface ge-2/0/1.0;
                direction down;
            }
        }
    }
}

```

```

        remote-mep 104;
    }
}
}
}

```

From configuration mode on Router PE2, confirm your configuration by entering the **show protocols oam ethernet** commands. If the output does not display the intended configuration, repeat the configuration instructions in this example to correct it.

```

connectivity-fault-management {
  maintenance-domain l2circuit-example-md {
    level 5;
    maintenance-association working {
      mep 103 {
        interface ge-2/0/0.0;
        direction down;
        remote-mep 1000;
      }
    }
    maintenance-association protection {
      mep 104 {
        interface ge-2/0/1.0;
        direction down;
        remote-mep 1001;
      }
    }
  }
}
}
}

```

Verifying that OAM CFM Connections are Active

Purpose

Verify that the CFM connections are active on each of the PE routers.

Action

Execute the following command on each of the PE routers.

1. Verify that the CFM working connection on Router PE1 is active.

```
user@ PE1> show oam ethernet connectivity-fault-management mep-database maintenance-domain  
l2circuit-example-md maintenance-association working  
Interface status: Active, Link status: Up
```

2. Verify that the CFM protect connection on Router PE1 is active

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain  
l2circuit-example-md maintenance-association protection  
Interface status: Active, Link status: Up
```

3. Verify that the CFM working connection on Router PE2 is active.

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain  
l2circuit-example-md maintenance-association working  
Interface status: Active, Link status: Up
```

4. Verify that the CFM protect connection on Router PE2 is active.

```
user@ PE2> show oam ethernet connectivity-fault-management mep-database maintenance-domain  
l2circuit-example-md maintenance-association protection  
Interface status: Active, Link status: Up
```

RELATED DOCUMENTATION

| [Example: Configuring Layer 2 Circuit Protect Interfaces](#) | 454

Monitoring Layer 2 Circuits with BFD

IN THIS CHAPTER

- [Configuring BFD for VCCV for Layer 2 Circuits | 481](#)
- [Example: Configuring BFD for VCCV for Layer 2 Circuits | 484](#)

Configuring BFD for VCCV for Layer 2 Circuits

Bidirectional Forwarding Detection (BFD) support for virtual circuit connection verification (VCCV) allows you to configure a control channel for a pseudowire, in addition to the corresponding operations and management functions to be used over that control channel. BFD provides a low resource mechanism for the continuous monitoring of the pseudowire data path and for detecting data plane failures. This feature provides support for asynchronous mode BFD for VCCV as described in RFC 5885, *Bidirectional Forwarding Detection (BFD) for the Pseudowire Virtual Circuit Connectivity Verification (VCCV)*. You can also use a ping to detect pseudowire failures. However, the processing resources required for a ping are greater than what is needed for BFD. In addition, BFD is capable of detecting data plane failure faster than VCCV ping. BFD for pseudowires is supported for Layer 2 circuits (LDP-based).

Before you begin:

- Configure the device interfaces.

To configure BFD for VCCV:

1. Specify the threshold for the adaptation of the BFD session detection time.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-  
detection]  
user@host# set detection-time threshold milliseconds
```

For example, to set a detection time threshold of 40 milliseconds for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection]
user@host# set detection-time threshold 40
```

2. Configure the virtual circuit ID for the Layer 2 circuit protocol.

```
[edit protocols l2circuit neighbor IP-address interface interface-name]
user@host# set virtual-circuit-id virtual-circuit-id
```

For example, to set the virtual circuit ID as 1 for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection]
user@host# set virtual-circuit-id 1
```

3. Configure the minimum interval after which the local routing device transmits hello packets and then expects to receive a reply from a neighbor with which it has established a BFD session for the Layer 2 circuit.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-
detection]
user@host# set minimum-interval milliseconds
```

For example, to set a minimum interval of 300 milliseconds for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection]
user@host# set minimum-interval 300
```

4. Configure the minimum interval after which the local routing device must receive a reply from a neighbor with which it has established a BFD session for the Layer 2 circuit protocol.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-
detection]
user@host# set minimum-receive-interval milliseconds
```

For example, to set a minimum receive interval of 10 milliseconds for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection]
user@host# set minimum-receive-interval 10
```

5. Configure the number of hello packets not received by a neighbor that causes the originating interface to be declared down for the Layer 2 circuit protocol.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-
detection]
user@host# set multiplier number
```

For example, to set the multiplier as 3 for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection]
user@host# set multiplier 3
```

6. Configure to disable adaptation.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-
detection]
user@host# set no-adaptation
```

7. Configure the minimum interval at which the local routing device transmits hello packets to a neighbor with which it has established a BFD session.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-
detection transmit-interval]
user@host# set minimum-interval milliseconds
```

For example, to set a minimum transmit interval of 5 milliseconds for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection
transmit-interval]
user@host# set minimum-interval 5
```

8. Specify the threshold for the adaptation of the BFD session transmit interval.

```
[edit protocols l2circuit neighbor IP-address interface interface-name oam bfd-liveness-
detection transmit-interval]
user@host# set threshold milliseconds
```

For example, to set a transmit interval threshold of 30 milliseconds for OAM BFD liveness detection:

```
[edit protocols l2circuit neighbor 192.0.2.1 interface ge-1/1/9.0 oam bfd-liveness-detection
transmit-interval]
user@host# set threshold 30
```

RELATED DOCUMENTATION

[Example: Configuring BFD for VCCV for Layer 2 Circuits](#) | 484

Example: Configuring BFD for VCCV for Layer 2 Circuits

IN THIS SECTION

- [Requirements](#) | 484
- [Overview](#) | 485
- [Configuration](#) | 486
- [Verification](#) | 492

This example shows how to configure BFD for VCCV for Layer 2 circuits which enables faster detection of failure in the data path.

Requirements

This example uses the following hardware and software components:

- Two MX Series 5G Universal Routing Platforms
- Junos OS Release 12.1 or later running on all devices

Overview

IN THIS SECTION


- [Topology | 485](#)

Starting with Junos OS Release 12.1, Bidirectional Forwarding Detection (BFD) support for virtual circuit connection verification (VCCV) allows you to configure a control channel for a pseudowire, in addition to the corresponding operations and management functions to be used over that control channel. BFD provides a low resource mechanism for the continuous monitoring of the pseudowire data path and for detecting data plane failures. This feature provides support for asynchronous mode BFD for VCCV as described in RFC 5885, *Bidirectional Forwarding Detection (BFD) for the Pseudowire Virtual Circuit Connectivity Verification (VCCV)*. You can also use a ping to detect pseudowire failures. However, the processing resources required for a ping are greater than what is needed for BFD. In addition, BFD is capable of detecting data plane failure faster than VCCV ping. BFD for pseudowires is supported for Layer 2 circuits (LDP-based).

To configure BFD for VCCV for Layer 2 circuits, configure the `oam` configuration statement at the `[edit protocols l2circuit neighbor address interface interface-name]` hierarchy level. The `control-channel` configuration statement at the `[edit routing-instances routing-instance-name protocols l2vpn oam]` hierarchy level does not apply to Layer 2 circuit configurations.

Topology

In the topology, BFD for VCCV for Layer 2 circuits is configured on Device R0.



Configuration

IN THIS SECTION

- [CLI Quick Configuration | 486](#)
- [Configuring Device R0 | 488](#)
- [Results | 490](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, copy and paste the commands into the CLI at the [edit] hierarchy level, and then enter `commit` from configuration mode.

R0

```
set chassis redundancy graceful-switchover
set interfaces ge-1/1/9 vlan-tagging
set interfaces ge-1/1/9 encapsulation vlan-ccc
set interfaces ge-1/1/9 unit 0 encapsulation vlan-ccc
set interfaces ge-1/1/9 unit 0 vlan-id 512
set interfaces ge-2/0/0 unit 0 family inet address 192.0.2.1/24
set interfaces ge-2/0/0 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 198.51.100.0/24
set routing-options nonstop-routing
set routing-options static route 203.0.113.0/24 next-hop 192.0.2.2
set routing-options router-id 198.51.100.0
set protocols rsvp interface ge-2/0/0.0
set protocols mpls label-switched-path lsp1 to 203.0.113.0
set protocols mpls interface ge-2/0/0.0
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-2/0/0.0
set protocols ldp interface all
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 virtual-circuit-id 1
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection
minimum-interval 300
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection
minimum-receive-interval 10
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection
```

```

multiplier 3
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection
transmit-interval minimum-interval 5
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection
transmit-interval threshold 30
set protocols l2circuit neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection
detection-time threshold 40

```

R1

```

set interfaces ge-1/1/9 vlan-tagging
set interfaces ge-1/1/9 encapsulation vlan-ccc
set interfaces ge-1/1/9 unit 0 encapsulation vlan-ccc
set interfaces ge-1/1/9 unit 0 vlan-id 512
set interfaces ge-2/0/1 unit 0 family inet address 192.0.2.2/24
set interfaces ge-2/0/1 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 203.0.113.0/24
set routing-options static route 198.51.100.0/24 next-hop 192.0.2.1
set routing-options router-id 203.0.113.0
set protocols rsvp interface ge-2/0/1.0
set protocols mpls label-switched-path lsp2 to 198.51.100.0
set protocols mpls interface ge-2/0/1.0
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-2/0/1.0
set protocols ldp interface all
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 virtual-circuit-id 1
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 oam bfd-liveness-detection
minimum-interval 300
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 oam bfd-liveness-detection
minimum-receive-interval 10
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 oam bfd-liveness-detection
multiplier 3
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 oam bfd-liveness-detection
transmit-interval minimum-interval 5
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 oam bfd-liveness-detection
transmit-interval threshold 30
set protocols l2circuit neighbor 198.51.100.0 interface ge-1/1/9.0 oam bfd-liveness-detection
detection-time threshold 40

```

Configuring Device R0

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure Device R0:

NOTE: Repeat this procedure for Device R1 after modifying the appropriate interface names, addresses, and any other parameters for the device.

1. Configure graceful switchover redundancy.

```
[edit chassis]
user@R0# set redundancy graceful-switchover
```

2. Configure the interfaces.

```
[edit interfaces]
user@R0# set ge-1/1/9 vlan-tagging
user@R0# set ge-1/1/9 encapsulation vlan-ccc
user@R0# set ge-1/1/9 unit 0 encapsulation vlan-ccc
user@R0# set ge-1/1/9 unit 0 vlan-id 512
user@R0# set ge-2/0/0 unit 0 family inet address 192.0.2.1/24
user@R0# set ge-2/0/0 unit 0 family mpls
user@R0# set lo0 unit 0 family inet address 198.51.100.0/24
```

3. Configure the nonstop routing option, the static route, and the router ID routing options.

```
[edit routing-options]
user@R0# set nonstop-routing
user@R0# set static route 203.0.113.0/24 next-hop 192.0.2.2
user@R0# set router-id 198.51.100.0
```

4. Configure the RSVP protocol.

```
[edit protocols rsvp]
user@R0# set interface ge-2/0/0.0
```

5. Configure the MPLS protocol.

```
[edit protocols mpls]
user@R0# set label-switched-path lsp1 to 203.0.113.0
user@R0# set interface ge-2/0/0.0
```

6. Configure the OSPF protocol.

```
[edit protocols ospf]
user@R0# set traffic-engineering
user@R0# set area 0.0.0.0 interface ge-2/0/0.0
```

7. Configure the LDP protocol.

```
[edit protocols ldp]
user@R0# set interface all
```

8. Configure the virtual circuit ID for the neighbor of Layer 2 circuit protocols.

```
[edit protocols l2circuit]
user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 virtual-circuit-id 1
```

9. Configure the oam attributes of the Layer 2 circuit protocol.

```
[edit protocols l2circuit]
user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection minimum-
interval 300
user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection minimum-
receive-interval 10
user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection multiplier 3
user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection transmit-
interval minimum-interval 5
```

```

user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection transmit-
interval threshold 30
user@R0# set neighbor 203.0.113.0 interface ge-1/1/9.0 oam bfd-liveness-detection detection-
time threshold 40

```

Results

From configuration mode, confirm your configuration by entering the `show chassis`, `show interfaces`, `show protocols`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@R0# show chassis
redundancy {
    graceful-switchover;
}

```

```

user@R0# show interfaces
ge-1/1/9 {
    vlan-tagging;
    encapsulation vlan-ccc;
    unit 0 {
        encapsulation vlan-ccc;
        vlan-id 512;
    }
}
ge-2/0/0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 198.51.100.0/24;
        }
    }
}

```

```

    }
}

```

```

user@R0# show protocols
rsvp {
    interface ge-2/0/0.0;
}
mpls {
    label-switched-path lsp1 {
        to 203.0.113.0;
    }
    interface ge-2/0/0.0;
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface ge-2/0/0.0;
    }
}
ldp {
    interface all;
}
l2circuit {
    neighbor 203.0.113.0 {
        interface ge-1/1/9.0 {
            virtual-circuit-id 1;
            oam {
                bfd-liveness-detection {
                    minimum-interval 300;
                    minimum-receive-interval 10;
                    multiplier 3;
                    transmit-interval {
                        minimum-interval 5;
                        threshold 30;
                    }
                    detection-time {
                        threshold 40;
                    }
                }
            }
        }
    }
}

```

```

    }
}

```

```

user@R0# show routing-options
nonstop-routing;
static {
    route 203.0.113.0/24 next-hop 192.0.2.2;
}
router-id 198.51.100.0;

```

If you are done configuring the device, enter **commit** from configuration mode.

Verification

IN THIS SECTION

- [Verifying the Layer 2 Circuit Connections | 492](#)
- [Verifying the BFD Session | 493](#)
- [Verifying Detailed BFD Session Information | 494](#)

Verify that the configuration is working properly.

Verifying the Layer 2 Circuit Connections

Purpose

Verify the connections in a Layer 2 Circuit.

Action

From operational mode, run the `show l2circuit connections` command for Device R0.

```

user@R0> show l2circuit connections

Layer-2 Circuit Connections:

Legend for connection status (St)

```

```

EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch      Up -- operational
VM -- vlan id mismatch           CF -- Call admission control failure
OL -- no outgoing label          IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC    TM -- TDM misconfiguration
BK -- Backup Connection          ST -- Standby Connection
CB -- rcvd cell-bundle size bad  SP -- Static Pseudowire
LD -- local site signaled down   RS -- remote site standby
RD -- remote site signaled down  HS -- Hot-standby Connection
XX -- unknown

```

Legend for interface status

Up -- operational

Dn -- down

Neighbor: 203.0.113.0

Interface	Type	St	Time last up	# Up trans
ge-1/1/9.0(vc 1)	rmt	Up	Jun 2 03:19:44 2014	1

Remote PE: 203.0.113.0, Negotiated control-word: Yes (Null)
Incoming label: 299792, Outgoing label: 299792
Negotiated PW status TLV: No
Local interface: ge-1/1/9.0, Status: Up, Encapsulation: VLAN
Flow Label Transmit: No, Flow Label Receive: No
Flow Label Transmit: No, Flow Label Receive: No

Meaning

The output shows the Layer 2 virtual circuit information from Device R0 to its neighbor.

Verifying the BFD Session

Purpose

Verify the BFD session.

Action

From operational mode, run the `show bfd session` command for Device R0.

```
user@R0> show bfd session
```

Address	State	Interface	Detect Time	Transmit Interval	Multiplier
203.0.113.7	Up	ge-2/0/0.0	0.030	0.010	3

1 sessions, 1 clients
Cumulative transmit rate 100.0 pps, cumulative receive rate 100.0 pps

Meaning

The output shows the address, and the interface on which the BFD session is active. The state *Up* indicates that the BFD session is up. The BFD session has a time interval of 30 milliseconds to detect BFD control packets , the transmitting system has a time interval of 10 milliseconds to send BFD control packets, and the transmitting system determines the detection time by multiplying 3 with the time interval. Total number of active BFD sessions and total number of clients that are hosting active BFD sessions. Cumulative transmit rate indicates the total number of BFD control packets transmitted, per second, on all active sessions and cumulative receive rate indicates the total number of BFD control packets received, per second, on all active sessions.

Verifying Detailed BFD Session Information

Purpose

Verify detailed BFD session information.

Action

From operational mode, run the `show bfd session extensive` command for Device R0.

```
user@R0> show bfd session extensive
```

	Detect	Transmit
--	--------	----------

Address	State	Interface	Time	Interval	Multiplier
203.0.113.7	Up	ge-2/0/0.0	0.030	0.010	3
Client L2CKT-OAM, TX interval 0.005, RX interval 0.010					
Session up time 03:47:14					
Local diagnostic None, remote diagnostic None					
Remote state Up, version 1					
Replicated					
Session type: VCCV BFD					
Min async interval 0.005, min slow interval 1.000					
Adaptive async TX interval 0.005, RX interval 0.010					
Local min TX interval 0.005, minimum RX interval 0.010, multiplier 3					
Remote min TX interval 0.005, min RX interval 0.010, multiplier 3					
Threshold transmission interval 0.030, Threshold for detection time 0.040					
Local discriminator 20, remote discriminator 13004					
Echo mode disabled/inactive					
Remote is control-plane independent					
Neighbor address 203.0.113.0, Virtual circuit id 1					
Session ID: 0x0					
1 sessions, 1 clients					
Cumulative transmit rate 100.0 pps, cumulative receive rate 100.0 pps					

Meaning

The output shows detailed information for the BFD session.

RELATED DOCUMENTATION

| [Configuring BFD for VCCV for Layer 2 Circuits](#) | 481

Troubleshooting Layer 2 Circuits

IN THIS CHAPTER

- [Tracing Layer 2 Circuit Operations | 496](#)

Tracing Layer 2 Circuit Operations

To trace the creation of and changes to Layer 2 circuits, include the `traceoptions` statement:

```
traceoptions {  
    file filename <files number> <size size> <world-readable | no-world-readable>;  
    flag flag <flag-modifier> <disable>;  
}
```

You can include this statement at the following hierarchy levels:

- [edit protocols l2circuit]
- [edit logical-systems *logical-system-name* protocols l2circuit]

Specify the following flags to trace the indicated operations on Layer 2 circuits:

- connections—Layer 2 circuit connections (events and state changes)
- error—Error conditions
- FEC—Layer 2 circuit advertisements received or sent using LDP
- topology—Layer 2 circuit topology changes caused by reconfiguration or advertisements received from other PE routers

6

PART

Configuring VPWS VPNs

[Overview | 498](#)

[Configuring VPWS VPNs | 505](#)

Overview

IN THIS CHAPTER

- [Understanding VPWS | 498](#)
- [Supported VPWS Standards | 502](#)
- [FAT Flow Labels Overview | 503](#)

Understanding VPWS

IN THIS SECTION

- [Supported and Unsupported Features | 501](#)

Virtual private wire service (VPWS) Layer 2 VPNs employ Layer 2 services over MPLS to build a topology of point-to-point connections that connect end customer sites in a VPN. These Layer 2 VPNs provide an alternative to private networks that have been provisioned by means of dedicated leased lines or by means of Layer 2 virtual circuits that employ ATM or Frame Relay. The service provisioned with these Layer 2 VPNs is known as VPWS. You configure a VPWS *instance* on each associated edge device for each VPWS Layer 2 VPN.

Traditional VPNs over Layer 2 circuits require the provisioning and maintenance of separate networks for IP and for VPN services. In contrast, *VPWS* enables the sharing of a provider's core network infrastructure between IP and Layer 2 VPN services, reducing the cost of providing those services.

Junos OS supports two types of VPWS Layer 2 VPNs:

- Kompella Layer 2 VPNs, which use BGP for autodiscovery and signaling.
- FEC 129 BGP autodiscovery for VPWS, which uses BGP for autodiscovery and LDP as the signaling protocol.


FEC 129 BGP autodiscovery for VPWS requires the `l2vpn-id`, `source-attachment-identifier`, and `target-attachment-identifier` statements. Kompella Layer 2 VPNs require the `site-identifier` and `remote-site-id` statements.

NOTE: VPWS creates pseudowires that emulate Layer 2 circuits. A virtual private LAN service (VPLS) network is similar to VPWS, but provides point-to-multipoint traffic forwarding in contrast to the VPWS Layer 2 VPN's point-to-point traffic forwarding. If you need point-to-multipoint service instead of point-to-point service, consider using VPLS instead of VPWS.

A VPWS Layer 2 VPN can have either a full-mesh or a hub-and-spoke topology. The tunneling mechanism in the core network typically is MPLS. However, VPWS can also use other tunneling protocols, such as GRE. VPWS is similar to Martini Layer 2 services over MPLS, and employs a similar encapsulation scheme for forwarding traffic.

Figure 41 on page 500 illustrates an example of a simple VPWS Layer 2 VPN topology.

Figure 41: VPWS Sample Topology



In this example, the service provider offers VPWS services to Customer A and Customer B. Customer A wants to create a full mesh of point-to-point links between Westford and Bangalore. Customer B needs only a single point-to-point link between Westford and Sunnyvale. The service provider uses BGP and MPLS signaling in the core, and creates a set of unidirectional pseudowires at each provider edge (PE) device to separately cross-connect each customer's Layer 2 circuits.

In order to provision this service, the provider configures two VPWS Layer 2 VPNs, Layer 2 VPN A and Layer 2 VPN B. The circuit cross-connect (CCC) encapsulation type (ethernet-ccc or vlan-ccc) is configured for each VPWS Layer 2 VPN. All interfaces in a given VPWS Layer 2 VPN must be configured with the VPWS Layer 2 VPN's encapsulation type.

Local and remote site information for the interfaces identifies the cross-connect. Local cross-connects are supported when the interfaces that are connected belong to two different sites configured in the same VPWS instance and on the same PE device.

BGP advertises reachability for the VPNs. The BGP configuration is similar to that used for other VPN services, such as Layer 3 VPNs and VPLS. MPLS is configured to set up base LSPs to the remote PE devices similarly to the other VPN services.

Junos OS provides VPWS support the following configuration methods:

- Pseudowires are manually configured using Forwarding Equivalence Class (FEC) 128.
- Pseudowires are signaled by LDP using FEC 129. This arrangement reduces the configuration burden that is associated with statically configured Layer 2 circuits while still using LDP as the underlying signaling protocol.

Supported and Unsupported Features

Junos OS supports the following features with VPWS :

- Intra-AS VPWS functionality using BGP for autodiscovery and FEC 129 LDP for pseudowire signaling.
- *Graceful Routing Engine switchover.*
- Operation, administration, and maintenance (OAM) mechanisms, including Bidirectional Forwarding Detection and MPLS ping.
- FEC 128 LDP signaling with static configuration (in Junos OS this is configured within protocols l2circuit). With this option, there is no BGP autodiscovery.

Junos OS does not support the following VPWS functionality:

- Multihoming of customer sites to multiple PE devices using the BGP site model of multihoming.
- Terminating FEC 129 VPWS into a mesh group of an FEC 129 VPLS instance.
- Intra-AS VPWS functionality using BGP for autodiscovery and FEC 128 LDP for pseudowire signaling.
- FEC 129 VPWS without BGP autodiscovery.
- Static configuration of VPWS with FEC 129 signaling.
- *Nonstop active routing.*
- Multi-segment pseudowires.

- Interworking of FEC 128 and FEC 129 VPWS.
- Statically configured Layer 2 circuit-style pseudowire redundancy.
- Inter-AS deployments.

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

Supported VPWS Standards

Junos OS substantially supports the following RFCs, which define standards for VPWS and Layer 2 circuits.

- RFC 4447, *Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)*
Junos OS does not support Section 5.3, “The Generalized PWid FEC Element.”
- RFC 4448, *Encapsulation Methods for Transport of Ethernet over MPLS Networks*
- RFC 6074, *Provisioning, Auto-Discovery, and Signaling in Layer 2 Virtual Private Networks (L2VPNs)*
- RFC 6391, *Flow-Aware Transport of Pseudowires over an MPLS Packet Switched Network*
- RFC 6790, *The Use of Entropy Labels in MPLS Forwarding*

The following Internet drafts do not define standards, but provide information about Layer 2 technologies. The IETF classifies them as “Historic.”

- Internet draft draft-martini-l2circuit-encap-mpls-11.txt, *Encapsulation Methods for Transport of Layer 2 Frames Over IP and MPLS Networks*

Junos OS differs from the Internet draft in the following ways:

- A packet with a sequence number of 0 (zero) is treated as out of sequence.
- Any packet that does not have the next incremental sequence number is considered out of sequence.
- When out-of-sequence packets arrive, the expected sequence number for the neighbor is set to the sequence number in the Layer 2 circuit control word.
- Internet draft draft-martini-l2circuit-trans-mpls-19.txt, *Transport of Layer 2 Frames Over MPLS*

RELATED DOCUMENTATION

Supported Carrier-of-Carriers and Interprovider VPN Standards

[Supported Layer 2 VPN Standards | 145](#)

Supported Layer 3 VPN Standards

Supported Multicast VPN Standards

[Supported VPLS Standards | 614](#)

[Accessing Standards Documents on the Internet](#)

FAT Flow Labels Overview

A pseudowire is a Layer 2 circuit or service that emulates the essential attributes of a telecommunications service, such as a T1 line, over an MPLS packet-switched network (PSN). The pseudowire is intended to provide only the minimum necessary functionality to emulate the wire with the required resiliency requirements for the given service definition.

In an MPLS network, the flow-aware transport of pseudowires (FAT) flow label, as described in RFC 6391, *Flow-Aware Transport of Pseudowires over an MPLS Packet Switched Network*, is used for load-balancing traffic across LDP-signaled pseudowires for virtual private LAN service (VPLS) and virtual private wire service (VPWS).

When the pseudowire is configured to use the FAT flow labels for load balancing, packets arriving at the ingress router are processed in the following sequence across the path of the pseudowire:

- The ingress router uses the contents of the inbound packet in the hash-key algorithm to calculate the flow-label value.
- The ingress router pushes the flow label to the label stack of the packet.
- The transit routers perform load balancing based only on the label stack.
- The egress router pops the flow label and forwards the packet to its destination.

For load balancing to work based on a flow-label configuration, a version of LDP that supports signaling extensions to use the flow label with pseudowires must be enabled on all routers. The LDP-signaling configuration is identical for VPLS and VPWS pseudowires.

FAT flow labels are supported on the following LDP-signaled forwarding-equivalence classes (FECs) for VPWS and VPLS pseudowires:

- FEC 128 for VPWS—LDP-signaled VPWS with neighbors that are statically configured (BGP autodiscovery is not supported).

- FEC 128 for VPLS—LDP-signaled VPLS with neighbors that are statically configured (BGP autodiscovery is not supported).
- FEC 129 for VPWS—LDP-signaled VPWS with BGP autodiscovery of neighbors.
- FEC 129 for VPLS—LDP-signaled VPLS with BGP autodiscovery of neighbors.

NOTE: Flow-aware transport of pseudowires (FAT) flow labels are not supported with Enhanced Dense Port Concentrators (DPCs), and flow labels should not be configured in a system with DPCs. Entropy labels are supported with DPCs with the following restrictions: entropy labels are stripped by DPCs, but entropy labels are not pushed by DPCs.

The interface parameter (Sub-TLV) is used both for FEC 128 and FEC 129 pseudowires. The sub-TLV defined for LDP contains the transmit (T) and receive (R) bits. The T bit advertises the ability to push the flow label. The R bit advertises the ability to pop the flow labels. By default, the signaling behavior of the provider edge (PE) router for any of these pseudowires is to advertise the T and R bits in the label set to 0.

The `flow-label-transmit` and `flow-label-receive` configuration statements provide the ability to set the T bit and R bit advertisement to 1 in the Sub-TLV field, which is part of the interface parameters of the FEC for the LDP label-mapping message. You can use these statements to control the pushing of the load-balancing label and the advertisement of the label to the routing peers in the control plane.

Alternatively, for FEC 128 VPWS pseudowires only, you can configure the following statements to statically configure flow label push and pop operations:

- `flow-label-receive-static` to statically pop the flow label on the pseudowire packets received from the remote PE router.
- `flow-label-transmit-static` to statically push the flow label on the pseudowire packets sent to the remote PE router.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

[Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)

[Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

[Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)

Configuring VPWS VPNs

IN THIS CHAPTER

- [Understanding FEC 129 BGP Autodiscovery for VPWS | 505](#)
- [Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 508](#)
- [Example: Configuring MPLS Egress Protection Service Mirroring for BGP Signaled Layer 2 Services | 526](#)
- [Understanding Multisegment Pseudowire for FEC 129 | 550](#)
- [Example: Configuring a Multisegment Pseudowire | 556](#)
- [Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)
- [Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

Understanding FEC 129 BGP Autodiscovery for VPWS

IN THIS SECTION

- [Supported Standards in FEC 129 BGP Autodiscovery for VPWS | 506](#)
- [Routes and Routing Table Interaction in FEC 129 BGP Autodiscovery for VPWS | 506](#)
- [Layer 2 VPN Behavior in FEC 129 BGP Autodiscovery for VPWS | 507](#)
- [BGP Autodiscovery Behavior in FEC 129 BGP Autodiscovery for VPWS | 507](#)
- [LDP Signaling Behavior in VPWS in FEC 129 BGP Autodiscovery for VPWS | 508](#)

The major functional components in a *VPWS* with FEC 129 are BGP, LDP, and the Layer 2 VPN module of Junos OS. BGP is responsible for distributing the local autodiscovery routes created on each PE device to all other PE devices. LDP is responsible for using the autodiscovery information provided by BGP to set up targeted LDP sessions over which to signal the pseudowires. The Layer 2 VPN is the glue that binds the BGP and LDP functionalities together.

Supported Standards in FEC 129 BGP Autodiscovery for VPWS

The relevant RFCs for this feature are as follows:

- RFC 4447, *Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)*
- RFC 6074, *Provisioning, Auto-Discovery, and Signaling in Layer 2 Virtual Private Networks (L2VPNs)*

Routes and Routing Table Interaction in FEC 129 BGP Autodiscovery for VPWS

BGP, LDP, and Layer 2 VPNs interact through different types of routes installed in the *instance.l2vpn.0* table. The routes that are present in the table are autodiscovery routes and pseudowire routes.

- Autodiscovery routes are used by BGP to allow autodiscovery of remote source access individual identifiers (SAIs) (the sources of the point-to-point pseudowires) and PE device addresses. Autodiscovery routes are advertised when you configure the `l2vpn auto-discovery-only` address family.

The format of the autodiscovery routes is a combination of the route distinguisher and the SAI. For example: 10.255.0.1:100:0.0.0.1/96 AD.

[Table 10 on page 506](#) lists the route elements and the number of associated bytes allocated to each element.

Table 10: Autodiscovery Route Format

Route Element	Bytes
RD	8 bytes
SAI	4 bytes

The `l2vpn-id` of the FEC 129 VPWS instance is attached to the route in a BGP extended community. One autodiscovery route is advertised for each source attachment identifier (SAI) in the instance.

- Pseudowire routes are installed by the Layer 2 VPN (local) and LDP (remote) to represent the bidirectional components of the pseudowire. For example: NoCtrlWord:5:100:200:2:0.0.0.1/176. The format of the routes is described in [Table 11 on page 507](#).

Table 11: Pseudowire Route Format

Field Name	Field Description
Pseudowire type + control word bit	2 bytes
Remote PE address	4 bytes
Attachment group identifier (AGI) The AGI field of the pseudowire route is always set to the l2vpn-id of the instance.	8 bytes
SAll	4 bytes
Target attachment individual identifier (TAII)	4 bytes

Layer 2 VPN Behavior in FEC 129 BGP Autodiscovery for VPWS

A Layer 2 VPN installs a locally generated autodiscovery route into the instance.l2vpn.0 table for every SAll configured in an FEC 129 VPWS instance. The extended community containing the l2vpn-id is attached when the route is added to the instance.l2vpn.0 table.

For each autodiscovered SAll from a remote neighbor where the l2vpn-id matches the local l2vpn-id and the received SAll matches a locally configured TAll, the Layer 2 VPN obtains an MPLS label and generates a pseudowire route and adds it to the instance.l2vpn.0 table. The remote PE address is copied from the BGP protocol next hop for the autodiscovery route.

The Layer 2 VPN module of Junos OS is responsible for installing the forwarding routes into the mpls.0 table as usual.

BGP Autodiscovery Behavior in FEC 129 BGP Autodiscovery for VPWS

Local autodiscovery routes installed by the Layer 2 VPN in the instance.l2vpn.0 table are advertised by BGP to remote PE devices s12vpn auto-discovery-only address family according to the instance and BGP export policies.

On the receiving side, BGP accepts autodiscovery routes from remote peers and installs them in the local bgp.l2vpn.0 table, if they are allowed by inbound policy. The route is installed, and a secondary

route is imported into the instance.l2vpn.0 table when an import route target match between the route and instance is found.

LDP Signaling Behavior in VPWS in FEC 129 BGP Autodiscovery for VPWS

In the Junos OS implementation of LDP, the router monitors for routes from instance.l2vpn.0 for any instance configured for FEC 129 VPWS. These routes are identified by the `instance-type l2vpn` statement in the routing instance and the presence of the `l2vpn-id` statement.

When a BGP autodiscovery route is installed, LDP sets up a targeted session with the remote peer, where the peer address is identified as the protocol next hop of the BGP autodiscovery route.

When a pseudowire route is installed in the instance.l2vpn.0 table, LDP uses the parameters associated with the route to signal the creation of the pseudowire using FEC 129. Upon receiving an FEC 129 label mapping message from a remote peer, LDP installs the pseudowire route in the `ldp.l2vpn.0` table.

Upon a successful `l2vpn-id` match with a configured FEC 129 VPWS instance, a secondary pseudowire route is imported to the instance.l2vpn.0 table. If an outgoing pseudowire has not already been set up when the incoming pseudowire signaling is received, LDP initiates the outgoing pseudowire creation as well.

RELATED DOCUMENTATION

[Understanding VPWS | 498](#)

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 508](#)

Example: Configuring FEC 129 BGP Autodiscovery for VPWS

IN THIS SECTION

- [Requirements | 509](#)
- [Overview | 509](#)
- [Configuration | 514](#)
- [Verification | 520](#)

This example shows how to configure the virtual private wire service (VPWS), where remote provider edge (PE) devices are automatically discovered dynamically by BGP, and pseudowires are signaled by LDP using FEC 129. This arrangement reduces the configuration burden that is associated with statically configured Layer 2 circuits while still using LDP as the underlying signaling protocol.

Requirements

This example requires Junos OS Release 13.2 or later on the PE devices.

Overview

IN THIS SECTION

- [Topology Diagram | 513](#)

Because VPWS is a point-to-point service, FEC 129 VPWS routing instances are configured as `instance-type l2vpn`. As with FEC 129 VPLS, FEC 129 VPWS uses the `l2vpn-id` statement to define the Layer 2 VPN of which the routing instance is a member. The presence of the `l2vpn-id` statement designates that FEC 129 LDP signaling is used for the routing instance. The absence of `l2vpn-id` indicates that BGP signaling is used instead.

The point-to-point nature of VPWS requires that you specify the source access individual identifier (SAIL) and the target access individual identifier (TAIL). This SAIL-TAIL pair defines a unique pseudowire between two PE devices.

The SAIL is specified with the `source-attachment-identifier` statement within the FEC 129 VPWS routing instance. You configure the source attachment identifier and the interfaces to associate with that source attachment identifier. Under each interface, you can configure the TAIL with the `target-attachment-identifier` statement. If the configured target identifier matches a source identifier advertised by a remote PE device by way of a BGP autodiscovery message, the pseudowire between that source-target pair is signaled. If there is no match between an advertised source identifier and the configured target identifier, the pseudowire is not established.

Sample: VPWS Configuration with Multiple Interfaces and Sites

```
routing-instances {
  FEC129-VPWS {
    instance-type l2vpn;
    interface ge-0/0/1.0;
    interface ge-0/0/2.0;
    interface ge-0/0/3.0;
```



```

route-distinguisher 10.255.0.1:200;
l2vpn-id l2vpn-id:100:200;
vrf-target target:100:200;
protocols l2vpn {
    site CUSTOMER-1 {
        source-attachment-identifier 1;
        interface ge-0/0/1.0 {
            target-attachment-identifier 2;
        }
        interface ge-0/0/2.0 {
            target-attachment-identifier 3;
        }
    }
}
}
}

```

You can configure multiple interfaces within a site, because each SAIL-TAIL pair defines a unique pseudowire, as shown with pseudowires 1-2 and 1-3 in the sample configuration. Both the source and target access identifiers are 4-byte numbers and can only be configured in FEC 129 VPWS instances where the `instance-type` is `l2vpn` and the `l2vpn-id` configuration statement is present.

You can specify the source and target identifiers as plain unsigned integers in the range 1 through 4,292,967,295.

The Layer 2 circuit and Layer 2 VPN services allow many optional parameters to be included on a per-pseudowire basis. FEC 129 VPWS allows such parameters as MTU settings, community tagging, and inclusion of a control word, as shown in this sample configuration:

Sample: VPWS Configuration with Optional Configuration Parameters

```

routing-instances {
    FEC129-VPWS {
        instance-type l2vpn;
        interface ge-0/0/1.0;
        interface ge-0/0/2.0;
        interface ge-0/0/3.0;
        route-distinguisher 10.255.0.1:200;
        l2vpn-id l2vpn-id:100:200;
        vrf-target target:100:200;
        protocols l2vpn {
            site CUSTOMER-1 {
                source-attachment-identifier 1;
            }
        }
    }
}

```

```

community COMM;
control-word ;
encapsulation-type ethernet;
ignore-encapsulation-mismatch;
ignore-mtu-mismatch;
mtu 1500;
no-control-word;
interface ge-0/0/1.0 {
    target-attachment-identifier 2;
}
interface ge-0/0/2.0 {
    target-attachment-identifier 3;
    community COMM;
    control-word;
    encapsulation-type ethernet;
    ignore-encapsulation-mismatch;
    ignore-mtu-mismatch;
    mtu 1500;
    no-control-word;
}
}
}
}
}
}

```

When configured within the site, the defined parameters affect any pseudowire originating from that site. When configured under an interface, the defined parameters affect that single specific pseudowire. This allows you to manipulate the parameters across all pseudowires associated with a particular local site in one place in the configuration.

Like other point-to-point services, the interfaces configured as members of the FEC 129 VPWS instance must be configured for CCC encapsulation and the CCC address family, as shown here:

```

interfaces {
    ge-0/0/1 {
        encapsulation ethernet-ccc;
        unit 0 {
            family ccc;
        }
    }
    ge-0/0/2 {
        encapsulation ethernet-ccc;
    }
}

```

```

        unit 0 {
            family ccc;
        }
    }
    ge-0/0/3 {
        encapsulation ethernet-ccc;
        unit 0 {
            family ccc;
        }
    }
}

```

You can use `vlan-ccc` instead of `ethernet-ccc`.

To support the basic FEC 129 VPWS functionality, the BGP sessions on the PE devices also need to be configured with the BGP `auto-discovery-only` address family to allow exchange of the autodiscovery routes. If traditional BGP VPLS or Layer 2 VPN service is also provisioned on the PE devices, the address family `l2vpn` signaling is also required, as shown here:

```

bgp {
    group pe {
        type internal;
        local-address 10.255.0.1;
        family l2vpn {
            auto-discovery-only;
            signaling;
        }
        neighbor 10.255.0.2;
        neighbor 10.255.0.3;
    }
}

```

The following configuration sample shows an FEC 129 VPWS routing instance with the operation, administration, and maintenance (OAM) (ping and BFD) configuration options:

Sample: VPWS Configuration with OAM

```

routing-instances {
    FEC129-VPWS {
        instance-type l2vpn;
        interface ge-0/0/1.0;
        route-distinguisher 10.255.0.1:200;
    }
}

```

```

l2vpn-id l2vpn-id:100:200;
vrf-target target:100:200;
protocols l2vpn {
    oam {
        ping-interval 600;
        bfd-liveness-detection {
            minimum-interval 200;
        }
    }
}
site CUSTOMER {
    source-attachment-identifier 1;
    oam {
        ping-interval 600;
        bfd-liveness-detection {
            minimum-interval 200;
        }
    }
    interface ge-0/0/1.0 {
        oam {
            ping-interval 600;
            bfd-liveness-detection {
                minimum-interval 200;
            }
        }
        target-attachment-identifier 2;
    }
}
}
}
}
}

```


OAM options configured under `protocols l2vpn` apply to all sites and pseudowires in the routing instance. OAM options configured under a particular site apply to the pseudowires configured under that site. OAM options configured under a particular interface apply to the pseudowire configured under that interface.

Topology Diagram

[Figure 42 on page 514](#) shows the topology used in this example.

This example uses a simple topology with two PE devices and two customer edge (CE) devices.

Figure 42: Simple VPWS Topology



"CLI Quick Configuration" on page 514 shows the configuration for all of the devices in Figure 42 on page 514. The section "Step-by-Step Procedure" on page 516 describes the steps on Device PE1 and Device PE2.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 514](#)
- [Procedure | 516](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device CE1

```
set interfaces ge-2/0/8 unit 0 description CE1_to_PE1
set interfaces ge-2/0/8 unit 0 family inet address 172.16.0.1/24
set interfaces lo0 unit 0 family inet address 192.0.2.5/24
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/8.0
```

Device CE2

```
set interfaces ge-2/1/6 unit 0 description CE2_to_PE2
set interfaces ge-2/1/6 unit 0 family inet address 172.16.0.4/24
set interfaces lo0 unit 0 family inet address 192.0.2.6/24
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/6.0
```

Device PE1

```
set interfaces ge-2/0/5 encapsulation ethernet-ccc
set interfaces ge-2/0/5 unit 0 description PE1_to_CE1
set interfaces ge-2/0/5 unit 0 family ccc
set interfaces fe-2/0/10 unit 0 description to_PE2
set interfaces fe-2/0/10 unit 0 family inet address 10.0.0.1/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.1/24
set protocols mpls interface fe-2/0/10.0
set protocols bgp local-address 192.0.2.1
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances FEC129-VPWS instance-type l2vpn
set routing-instances FEC129-VPWS interface ge-2/0/5.0
set routing-instances FEC129-VPWS route-distinguisher 192.0.2.1:100
set routing-instances FEC129-VPWS l2vpn-id l2vpn-id:100:100
set routing-instances FEC129-VPWS vrf-target target:100:100
set routing-instances FEC129-VPWS protocols l2vpn site ONE source-attachment-identifier 1
set routing-instances FEC129-VPWS protocols l2vpn site ONE interface ge-2/0/5.0 target-attachment-identifier 2
set routing-options autonomous-system 64510
```

Device PE2

```

set interfaces ge-2/1/7 encapsulation ethernet-ccc
set interfaces ge-2/1/7 unit 0 description PE2_to_CE2
set interfaces ge-2/1/7 unit 0 family ccc
set interfaces fe-2/0/10 unit 0 description to_PE1
set interfaces fe-2/0/10 unit 0 family inet address 10.0.0.2/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.2/24
set protocols mpls interface fe-2/0/10.0
set protocols bgp local-address 192.0.2.2
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.1
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances FEC129-VPWS instance-type l2vpn
set routing-instances FEC129-VPWS interface ge-2/1/7.0
set routing-instances FEC129-VPWS route-distinguisher 192.0.2.2:100
set routing-instances FEC129-VPWS l2vpn-id l2vpn-id:100:100
set routing-instances FEC129-VPWS vrf-target target:100:100
set routing-instances FEC129-VPWS protocols l2vpn site TWO source-attachment-identifier 2
set routing-instances FEC129-VPWS protocols l2vpn site TWO interface ge-2/1/7.0 target-
attachment-identifier 1
set routing-options autonomous-system 64510

```

Procedure

Step-by-Step Procedure

To configure a FEC 129 VPWS:

1. Configure the interfaces.

```

[edit interfaces]
user@PE1# set ge-2/0/5 encapsulation ethernet-ccc
user@PE1# set ge-2/0/5 unit 0 description PE1_to_CE1

```

```

user@PE1# set ge-2/0/5 unit 0 family ccc
user@PE1# set fe-2/0/10 unit 0 description to_PE2
user@PE1# set fe-2/0/10 unit 0 family inet address 10.0.0.1/30
user@PE1# set fe-2/0/10 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 192.0.2.1/24

```

2. Configure MPLS on the core-facing interface.

```

[edit protocols mpls]
user@PE1# set interface fe-2/0/10.0

```

3. Configure BGP.

```

[edit protocols bgp]
user@PE1# set local-address 192.0.2.1
user@PE1# set group pe-pe type internal
user@PE1# set group pe-pe family l2vpn auto-discovery-only
user@PE1# set group pe-pe family l2vpn signaling
user@PE1# set group pe-pe neighbor 192.0.2.2

```

4. Configure an interior gateway protocol, such as IS-IS or OSPF.

If you use OSPF, enable traffic engineering. Traffic engineering is supported by IS-IS by default.

```

[edit protocols ospf]
user@PE1# set traffic-engineering
user@PE1# set area 0.0.0.0 interface lo0.0 passive
user@PE1# set area 0.0.0.0 interface fe-2/0/10.0

```

5. Configure LDP on the core-facing interface and on the loopback interface.

```

[edit protocols ldp]
user@PE1# set interface fe-2/0/10.0
user@PE1# set interface lo0.0

```

6. Configure the VPWS routing instance.

LDP listens for routes from instance.l2vpn.0 for any instance configured for FEC 129 VPWS. These routes are identified by the instance-type l2vpn statement in the routing instance and the presence of the l2vpn-id statement.

Make sure that the target-attachment-identifier matches the source-attachment-identifier in the remote PE device's corresponding site. In this example, the pseudowire is established between Device PE1 and Device PE2. Device PE1 uses SAI 1 and TAI 2, while Device PE2 uses the opposite, SAI 2 and TAI 1.

```
[edit routing-instances FEC129-VPWS]
user@PE1# set instance-type l2vpn
user@PE1# set interface ge-2/0/5.0
user@PE1# set route-distinguisher 192.0.2.1:100
user@PE1# set l2vpn-id l2vpn-id:100:100
user@PE1# set vrf-target target:100:100
user@PE1# set protocols l2vpn site ONE source-attachment-identifier 1
user@PE1# set protocols l2vpn site ONE interface ge-2/0/5.0 target-attachment-identifier 2
```

7. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@PE1# set autonomous-system 64510
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@PE1# commit
```

Results

From configuration mode, confirm your configuration by entering the show interfaces, show protocols, show routing-instances, and show routing-options command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show interfaces
ge-2/0/5 {
  encapsulation ethernet-ccc;
  unit 0 {
    description PE1_to_CE1;
```

```

        family ccc;
    }
}
fe-2/0/10 {
    unit 1 {
        description to_PE2;
        family inet {
            address 10.0.0.1/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}
}

```

```

user@PE1# show protocols
mpls {
    interface fe-2/0/10.0;
}
bgp {
    local-address 192.0.2.1;
    group pe-pe {
        type internal;
        family l2vpn {
            auto-discovery-only;
            inactive: signaling;
        }
        neighbor 192.0.2.2;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
    }
}

```

```

        interface fe-2/0/10.0;
    }
}
ldp {
    interface fe-2/0/10.0;
    interface lo0.0;
}

```

```

user@PE1# show routing-instances
FEC129-VPWS {
    instance-type l2vpn;
    interface ge-2/0/5.0;
    route-distinguisher 192.0.2.1:100;
    l2vpn-id l2vpn-id:100:100;
    vrf-target target:100:100;
    protocols {
        l2vpn {
            site ONE {
                source-attachment-identifier 1;
                interface ge-2/0/5.0 {
                    target-attachment-identifier 2;
                }
            }
        }
    }
}

```

```

user@PE1# show routing-options
autonomous-system 64510;

```

Verification

IN THIS SECTION

- [Verifying the Routes | 521](#)
- [Checking Connectivity Between the CE Devices | 523](#)
- [Checking the VPWS Connections | 523](#)

● Checking Connectivity Between the PE Devices | 525

Confirm that the configuration is working properly.

Verifying the Routes

Purpose

Verify that the expected routes are learned.

Action

From operational mode, enter the `show route` command.

```
user@PE1> show route
inet.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.1/24      *[Direct/0] 6d 21:16:32
                  > via lo0.0
192.0.2.2/24      *[OSPF/10] 6d 21:15:31, metric 1
                  > to 10.0.0.2 via fe-2/0/10.0
10.0.0.0/30       *[Direct/0] 6d 21:16:31
                  > via fe-2/0/10.0
10.0.0.1/32       *[Local/0] 6d 21:16:32
                  Local via fe-2/0/10.0
203.0.113.0/24    *[OSPF/10] 6d 21:16:34, metric 1
                  MultiRecv

inet.3: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2/24      *[LDP/9] 5d 22:25:19, metric 1
                  > to 10.0.0.2 via fe-2/0/10.0

mpls.0: 8 destinations, 8 routes (8 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both
```

```

0          *[MPLS/0] 6d 21:16:33, metric 1
          Receive
1          *[MPLS/0] 6d 21:16:33, metric 1
          Receive
2          *[MPLS/0] 6d 21:16:33, metric 1
          Receive
13         *[MPLS/0] 6d 21:16:33, metric 1
          Receive
299808     *[LDP/9] 5d 22:25:19, metric 1
          > to 10.0.0.2 via fe-2/0/10.0, Pop
299808(S=0) *[LDP/9] 5d 22:25:19, metric 1
          > to 10.0.0.2 via fe-2/0/10.0, Pop
299824     *[L2VPN/7] 5d 22:25:18
          > via ge-2/0/5.0, Pop
ge-2/0/5.0 *[L2VPN/7] 5d 22:13:02, metric2 1
          > to 10.0.0.2 via fe-2/0/10.0, Push 299872

bgp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2:100:0.0.0.2/96 AD
          *[BGP/170] 6d 20:51:23, localpref 100, from 192.0.2.2
          AS path: I, validation-state: unverified
          > to 10.0.0.2 via fe-2/0/10.0

ldp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2:NoCtrlWord:5:100:100:0.0.0.2:0.0.0.1/176
          *[LDP/9] 5d 22:13:02
          Discard

FEC129-VPWS.l2vpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.1:100:0.0.0.1/96 AD
          *[L2VPN/170] 6d 20:53:26, metric2 1
          Indirect
192.0.2.2:100:0.0.0.2/96 AD
          *[BGP/170] 6d 20:51:23, localpref 100, from 192.0.2.2
          AS path: I, validation-state: unverified
          > to 10.0.0.2 via fe-2/0/10.0
192.0.2.2:NoCtrlWord:5:100:100:0.0.0.1:0.0.0.2/176

```

```

*[L2VPN/7] 6d 20:51:23, metric2 1
> to 10.0.0.2 via fe-2/0/10.0
192.0.2.2:NoCtrlWord:5:100:100:0.0.0.2:0.0.0.1/176
*[LDP/9] 5d 22:13:02
Discard

```

Meaning

The output shows all the learned routes, including the autodiscovery (AD) routes.

Checking Connectivity Between the CE Devices

Purpose

Verify that Device CE1 can ping Device CE2.

Action

```

user@CE1> ping 192.0.2.6
PING 192.0.2.6 (192.0.2.6): 56 data bytes
64 bytes from 192.0.2.6: icmp_seq=0 ttl=64 time=0.679 ms
64 bytes from 192.0.2.6: icmp_seq=1 ttl=64 time=0.524 ms
^C
--- 192.0.2.6 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.524/0.602/0.679/0.078 ms

```

Meaning

The output shows that the VPWS is operational.

Checking the VPWS Connections

Purpose

Make sure that all of the FEC 129 VPWS connections come up correctly.

Action

```

user@PE1> show l2vpn connections
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status
Up -- operational
Dn -- down

Instance: FEC129-VPWS
L2vpn-id: 100:100
Local source-attachment-id: 1 (ONE)
  Target-attachment-id  Type  St    Time last up      # Up trans
  2                    rmt   Up    Nov 28 16:16:14 2012      1
  Remote PE: 192.0.2.2, Negotiated control-word: No
  Incoming label: 299792, Outgoing label: 299792
  Local interface: ge-2/0/5.0, Status: Up, Encapsulation: ETHERNET

```

Meaning

As expected, the connection is up. The output includes the source attachment ID and the target attachment ID.

Checking Connectivity Between the PE Devices

Purpose

Verify that Device PE1 can ping Device PE2. The `ping mpls l2vpn fec129` command accepts SAs and TAs as integers or IP addresses and also allows you to use the CE-facing interface instead of the other parameters (instance, local-id, remote-id, remote-pe-address).

Action

```
user@PE1> ping mpls l2vpn fec129 instance FEC129-VPWS remote-id 2 remote-pe-address 192.0.2.2
local-id 1
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

```
user@PE1> ping mpls l2vpn fec129 interface ge-2/0/5.0
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Meaning

The output shows that the VPWS is operational.

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

Example: Configuring MPLS Egress Protection Service Mirroring for BGP Signaled Layer 2 Services

IN THIS SECTION

- [Requirements | 526](#)
- [Overview | 526](#)
- [Configuration | 528](#)
- [Verification | 545](#)

Starting in Junos OS Release 14.2, Junos OS supports the restoration of egress traffic when there is a link or node failure in the egress PE node. If there is a link or node failure in the core network, a protection mechanism such as MPLS fast reroute can be triggered on the transport LSPs between the PE routers to repair the connection within tens of milliseconds. An egress protection LSP addresses the problem of a node-link failure at the edge of the network (for example, a failure of a PE router).

This example shows how to configure link protection for BGP signaled Layer 2 services.

Requirements

MX Series Routers running Junos OS Release 14.2 or later.

Overview

IN THIS SECTION

- [Topology | 527](#)


If there is a link or node failure in the core network, a protection mechanism such as MPLS fast reroute can be triggered on the transport LSPs between the PE routers to repair the connection within tens of milliseconds. An egress protection LSP addresses the problem of a node-link failure at the edge of the network (for example, a failure of a PE router).

This example includes the following configuration concepts and statements that are unique to the configuration of an egress protection LSP:

- **context-identifier**—Specifies an IPv4 or IPv6 address used to define the pair of PE routers participating in the egress protection LSP. It is assigned to each ordered pair of primary PE and the protector to facilitate protection establishment. This address is globally unique, or unique in the address space of the network where the primary PE and the protector reside.
- **egress-protection**—Configures the protector information for the protected Layer 2 circuit and configures the protector Layer 2 circuit at the [edit protocols mpls] hierarchy level. Configures an LSP as an egress protection LSP at the [edit protocols mpls] hierarchy level.
- **protector**—Configures the creation of standby pseudowires on the backup PE for link or node protection for the instance.

Topology

Figure 43: Egress Protection LSP Configured from Router PE1 to Router PE2



In the event of a failure of the egress PE Router PE1, traffic is switched to the egress protection LSP configured between Router PE1 and Router PE2 (the protector PE router):

- Device CE2—Traffic origin
- Router PE3—Ingress PE router
- Router PE1— (Primary) Egress PE router
- Router PE2—Protector PE router
- Device CE1—Traffic destination

When the link between CE1– PE1 goes down, PE1 will briefly redirect that traffic toward CE1, to PE2. PE2 forwards it to CE1 until ingress router PE3 recalculates to forward the traffic to PE2.

Initially the traffic direction was: CE2 – PE3 – P – PE1 – CE1.

When the link between CE1– PE1 goes down, the traffic will be: CE2 – PE3 – P – PE1 – PE2 – CE1. PE3 then recalculates the path: CE2 – PE3 – P – PE2 – CE1.

This example shows how to configure routers PE1, PE2, and PE3.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 528](#)
- [Step-by-Step Procedure | 531](#)
- [Results | 538](#)

CLI Quick Configuration

To quickly configure an egress protection LSP, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configurations, copy and then paste the commands into the CLI and enter `commit` from configuration mode.

PE1

```
set protocols rsvp interface all
set protocols rsvp interface fxp0.0 disable
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols mpls egress-protection context-identifier 198.51.100.3 primary
set protocols mpls egress-protection context-identifier 198.51.100.3 advertise-mode stub-alias
set protocols mpls egress-protection traceoptions file ep size 100m
set protocols mpls egress-protection traceoptions flag all
set protocols bgp traceoptions file bgp.log world-readable
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 10.255.183.58
set protocols bgp group ibgp family inet unicast
set protocols bgp group ibgp family l2vpn signaling egress-protection
set protocols bgp group ibgp neighbor 192.0.2.3
```

```

set protocols bgp group ibgp neighbor 192.0.2.4
set protocols isis traceoptions file isis-edge size 10m world-readable
set protocols isis traceoptions flag error
set protocols isis level 1 disable
set protocols isis level 2 wide-metrics-only
set protocols isis interface all point-to-point
set protocols isis interface all level 2 metric 10
set protocols isis interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set policy-options policy-statement lb then load-balance per-packet
set routing-options traceoptions file ro.log
set routing-options traceoptions flag all
set routing-options traceoptions flag route
set routing-options autonomous-system 100
set routing-options forwarding-table export lb
set routing-instances foo instance-type l2vpn
set routing-instances foo egress-protection context-identifier 198.51.100.3
set routing-instances foo interface ge-2/0/2.0
set routing-instances foo route-distinguisher 10.255.183.58:1
set routing-instances foo vrf-target target:9000:1
set routing-instances foo protocols l2vpn encapsulation-type ethernet-vlan
set routing-instances foo protocols l2vpn site foo site-identifier 1
set routing-instances foo protocols l2vpn site foo site-preference primary
set routing-instances foo protocols l2vpn site foo interface ge-2/0/2.0 remote-site-id 2

```

PE2

```

set protocols rsvp interface all
set protocols rsvp interface fxp0.0 disable
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols mpls egress-protection context-identifier 198.51.100.3 protector
set protocols mpls egress-protection context-identifier 198.51.100.3 advertise-mode stub-alias
set protocols mpls egress-protection traceoptions file ep size 100m
set protocols mpls egress-protection traceoptions flag all
set protocols bgp traceoptions file bgp.log world-readable
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 10.255.183.57
set protocols bgp group ibgp family inet unicast
set protocols bgp group ibgp family l2vpn signaling egress-protection
set protocols bgp group ibgp neighbor 192.0.2.3

```

```

set protocols bgp group ibgp neighbor 192.0.2.4
set protocols isis traceoptions file isis-edge size 10m world-readable
set protocols isis traceoptions flag error
set protocols isis level 1 disable
set protocols isis level 2 wide-metrics-only
set protocols isis interface all point-to-point
set protocols isis interface all level 2 metric 10
set protocols isis interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set policy-options policy-statement lb then load-balance per-packet
set routing-options traceoptions file ro.log
set routing-options traceoptions flag normal
set routing-options traceoptions flag route
set routing-options autonomous-system 100
set routing-options forwarding-table export lb
set routing-instances foo instance-type l2vpn
set routing-instances foo egress-protection protector
set routing-instances foo interface ge-2/0/2.0
set routing-instances foo route-distinguisher 10.255.183.57:1
set routing-instances foo vrf-target target:9000:1
set routing-instances foo protocols l2vpn encapsulation-type ethernet-vlan
set routing-instances foo protocols l2vpn site foo hot-standby
set routing-instances foo protocols l2vpn site foo site-identifier 1
set routing-instances foo protocols l2vpn site foo site-preference backup
set routing-instances foo protocols l2vpn site foo interface ge-2/0/2.0 remote-site-id 2

```

PE3

```

set protocols rsvp interface all
set protocols rsvp interface fxp0.0 disable
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp traceoptions file bgp.log world-readable
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 10.255.183.61
set protocols bgp group ibgp family inet unicast
set protocols bgp group ibgp family l2vpn signaling
set protocols bgp group ibgp neighbor 192.0.2.3
set protocols bgp group ibgp neighbor 192.0.2.4
set protocols isis traceoptions file isis-edge size 10m world-readable
set protocols isis traceoptions flag error

```

```

set protocols isis level 1 disable
set protocols isis level 2 wide-metrics-only
set protocols isis interface all point-to-point
set protocols isis interface all level 2 metric 10
set protocols isis interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set policy-options policy-statement lb then load-balance per-packet
set routing-options traceoptions file ro.log
set routing-options traceoptions flag normal
set routing-options traceoptions flag route
set routing-options autonomous-system 100
set routing-options forwarding-table export lb
set routing-instances foo instance-type l2vpn
set routing-instances foo interface ge-2/1/2.0
set routing-instances foo route-distinguisher 10.255.183.61:1
set routing-instances foo vrf-target target:9000:1
set routing-instances foo protocols l2vpn encapsulation-type ethernet-vlan
set routing-instances foo protocols l2vpn site foo site-identifier 2
set routing-instances foo protocols l2vpn site foo interface ge-2/1/2.0 remote-site-id 1

```

Step-by-Step Procedure

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure an egress protection LSP for router PE1:

1. Configure RSVP.

```

[edit protocols rsvp]
user@PE1# set interface all
user@PE1# set interface fxp0.0 disable

```

2. Configure MPLS to use the egress protection LSP to protect against a link failure to Device CE1.

```

[edit protocols mpls]
user@PE1# set interface all
user@PE1# set interface fxp0.0 disable

```

```

user@PE1# set egress-protection context-identifier 198.51.100.3 primary
user@PE1# set egress-protection context-identifier 198.51.100.3 advertise-mode stub-alias
user@PE1# set egress-protection traceoptions file ep size 100m
user@PE1# set egress-protection traceoptions flag all

```

3. Configure BGP.

```

[edit protocols bgp]
user@PE1# set traceoptions file bgp.log world-readable
user@PE1# set group ibgp type internal
user@PE1# set group ibgp local-address 10.255.183.58
user@PE1# set group ibgp family inet unicast
user@PE1# set group ibgp family l2vpn signaling egress-protection
user@PE1# set group ibgp neighbor 192.0.2.3
user@PE1# set group ibgp neighbor 192.0.2.4

```

4. Configure IS-IS.

```

[edit protocols isis]
user@PE1# set traceoptions file isis-edge size 10m world-readable
user@PE1# set traceoptions flag error
user@PE1# set level 1 disable
user@PE1# set level 2 wide-metrics-only
user@PE1# set interface all point-to-point
user@PE1# set interface all level 2 metric 10
user@PE1# set interface fxp0.0 disable

```

5. Configure LDP.

```

[edit protocols ldp]
user@PE1# set interface all
user@PE1# set interface fxp0.0 disable

```

6. Configure a load-balancing policy.

```

[edit]
user@PE1# set policy-options policy-statement lb then load-balance per-packet

```

7. Configure the routing options to export routes based on the load-balancing policy.

```
[edit routing-options]
user@PE1# set traceoptions file ro.log
user@PE1# set traceoptions flag all
user@PE1# set autonomous-system 100
user@PE1# set forwarding-table export lb
```

8. Configure BGP to advertise nrli from the routing instance with context-ID as next-hop.

```
[edit routing-instances]
user@PE1# set foo instance-type l2vpn
user@PE1# set foo egress-protection context-identifier 198.51.100.3
user@PE1# set foo interface ge-2/0/2.0
user@PE1# set foo route-distinguisher 10.255.183.58:1
user@PE1# set foo vrf-target target:9000:1
```

9. Configure l2vpn instance to use the egress LSP configured.

```
[edit routing-instances]
user@PE1# set foo protocols l2vpn encapsulation-type ethernet-vlan
user@PE1# set foo protocols l2vpn site foo site-identifier 1
user@PE1# set foo protocols l2vpn site foo site-preference primary
user@PE1# set foo protocols l2vpn site foo interface ge-2/0/2.0 remote-site-id 2
```

10. If you are done configuring the device, enter `commit` from configuration mode.

Step-by-Step Procedure

To configure an egress protection LSP for Router PE2:

1. Configure RSVP.

```
[edit protocols rsvp]
user@PE2# set interface all
user@PE2# set interface fxp0.0 disable
```


2. Configure MPLS and the LSP that acts as the egress protection LSP.

```
[edit protocols mpls]
user@PE2# set interface all
user@PE2# set interface fxp0.0 disable
user@PE2# set egress-protection context-identifier 198.51.100.3 protector
user@PE2# set egress-protection context-identifier 198.51.100.3 advertise-mode stub-alias
user@PE2# set egress-protection traceoptions file ep size 100m
user@PE2# set egress-protection traceoptions flag all
```

3. Configure BGP.

```
[edit protocols bgp]
user@PE2# set traceoptions file bgp.log world-readable
user@PE2# set group ibgp type internal
user@PE2# set group ibgp local-address 10.255.183.57
user@PE2# set group ibgp family inet unicast
user@PE2# set group ibgp family l2vpn signaling
user@PE2# set group ibgp family l2vpn egress-protection
user@PE2# set group ibgp neighbor 192.0.2.3
user@PE2# set group ibgp neighbor 192.0.2.4
```

4. Configure IS-IS.

```
[edit protocols isis]
user@PE2# set traceoptions file isis-edge size 10m world-readable
user@PE2# set traceoptions flag error
user@PE2# set level 1 disable
user@PE2# set level 2 wide-metrics-only
user@PE2# set interface all point-to-point
user@PE2# set interface all level 2 metric 10
user@PE2# set interface fxp0.0 disable
```

5. Configure LDP.

```
[edit protocols ldp]
user@PE2# set interface all
user@PE2# set interface fxp0.0 disable
```

6. Configure a load-balancing policy.

```
[edit]
user@PE2# set policy-options policy-statement lb then load-balance per-packet
```

7. Configure the routing options to export routes based on the load-balancing policy.

```
[edit routing-options]
user@PE2# set traceoptions file ro.log
user@PE2# set traceoptions flag all
user@PE2# set autonomous-system 100
user@PE2# set forwarding-table export lb
```

8. Configure BGP to advertise nrli from the routing instance with context-ID as next-hop.

```
[edit routing-instances]
user@PE2# set foo instance-type l2vpn
user@PE2# set foo egress-protection protector
user@PE2# set foo interface ge-2/0/2.0
user@PE2# set foo route-distinguisher 10.255.183.57:1
user@PE2# set foo vrf-target target:9000:1
```

9. Configure l2vpn instance to use the egress LSP configured.

```
[edit routing-instances]
user@PE2# set foo protocols l2vpn encapsulation-type ethernet-vlan
user@PE2# set foo protocols l2vpn site foo hot-standby
user@PE2# set foo protocols l2vpn site foo site-identifier 1
user@PE2# set foo protocols l2vpn site foo site-preference backup
user@PE2# set foo protocols l2vpn site foo interface ge-2/0/2.0 remote-site-id 2
```

10. If you are done configuring the device, enter `commit` from configuration mode.

Step-by-Step Procedure

To configure an egress protection LSP for Router PE3:

1. Configure RSVP.

```
[edit protocols rsvp]
user@PE3# set interface all
user@PE3# set interface fxp0.0 disable
```

2. Configure MPLS.

```
[edit protocols mpls]
user@PE3# set interface all
user@PE3# set interface fxp0.0 disable
```

3. Configure BGP.

```
[edit protocols bgp]
user@PE3# set traceoptions file bgp.log world-readable
user@PE3# set group ibgp type internal
user@PE3# set group ibgp local-address 10.255.183.61
user@PE3# set group ibgp family inet unicast
user@PE3# set group ibgp family l2vpn signaling
user@PE3# set group ibgp neighbor 192.0.2.3
user@PE3# set group ibgp neighbor 192.0.2.4
```

4. Configure IS-IS.

```
[edit protocols isis]
user@PE3# set traceoptions file isis-edge size 10m world-readable
user@PE3# set traceoptions flag error
user@PE3# set level 1 disable
user@PE3# set level 2 wide-metrics-only
user@PE3# set protocols isis interface all point-to-point
[edit protocols isis]
user@PE3# set protocols isis interface all level 2 metric 10
[edit protocols isis]
user@PE3# set protocols isis interface fxp0.0 disable
```

5. Configure LDP.

```
[edit protocols ldp]
user@PE3# set interface all
user@PE3# set interface fxp0.0 disable
```

6. Configure a load-balancing policy.

```
[edit]
user@PE3# set policy-options policy-statement lb then load-balance per-packet
```

7. Configure the routing options to export routes based on the load-balancing policy.

```
[edit routing-options]
user@PE3# set traceoptions file ro.log
user@PE3# set traceoptions flag normal
user@PE3# set traceoptions flag route
user@PE3# set autonomous-system 100
user@PE3# set forwarding-table export lb
```

8. Configure BGP to advertise nlri from the routing instance with context-ID as next-hop.

```
[edit]
user@PE3# set routing-instances foo instance-type l2vpn
user@PE3# set routing-instances foo interface ge-2/1/2.0
user@PE3# set routing-instances foo route-distinguisher 10.255.183.61:1
user@PE3# set routing-instances foo vrf-target target:9000:1
```

9. Configure l2vpn to specify the interface that connects to the site and the remote interface to which you want the specified interface to connect.

```
[edit routing-instances]
user@PE3# set foo protocols l2vpn encapsulation-type ethernet-vlan
user@PE3# set foo protocols l2vpn site foo site-identifier 2
user@PE3# set foo protocols l2vpn site foo interface ge-2/1/2.0 remote-site-id 1
```

10. If you are done configuring the device, enter `commit` from configuration.

Results

From configuration mode, confirm your configuration on Router PE1 by entering the **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
[edit]
user@PE1# show protocols
rsvp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }
    egress-protection {
        context-identifier 198.51.100.3 {
            primary;
            advertise-mode stub-alias;
        }
        traceoptions {
            file ep size 100m;
            flag all;
        }
    }
}
bgp {
    traceoptions {
        file bgp.log world-readable;
    }
    group ibgp {
        type internal;
        local-address 10.255.183.58;
        family inet {
            unicast;
        }
        family l2vpn {
            signaling {
```

```

        egress-protection;
    }
}
neighbor 192.0.2.3;
neighbor 192.0.2.4;
}
}
isis {
    traceoptions {
        file isis-edge size 10m world-readable;
        flag error;
    }
    level 1 disable;
    level 2 wide-metrics-only;
    interface all {
        point-to-point;
        level 2 metric 10;
    }
    interface fxp0.0 {
        disable;
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}

```

[edit]

user@PE1# **show policy-options**

```

policy-statement lb {
    then {
        load-balance per-packet;
    }
}

```

[edit]

user@PE1# **show routing-options**

```

traceoptions {
    file ro.log;
    flag all;
}
autonomous-system 100;

```

```

forwarding-table {
    export lb;
}

[edit]
user@PE1# show routing-instances
foo {
    instance-type l2vpn;
    egress-protection {
        context-identifier {
            198.51.100.3;
        }
    }
    interface ge-2/0/2.0;
    route-distinguisher 10.255.183.58:1;
    vrf-target target:9000:1;
    protocols {
        l2vpn {
            encapsulation-type ethernet-vlan;
            site foo {
                site-identifier 1;
                site-preference primary;
                interface ge-2/0/2.0 {
                    remote-site-id 2;
                }
            }
        }
    }
}

```

From configuration mode, confirm your configuration on Router PE2 by entering the **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@PE2# show protocols
rsvp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

```

```

mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }

    egress-protection {
        context-identifier 198.51.100.3 {
            protector;
            advertise-mode stub-alias;
        }
        traceoptions {
            file ep size 100m;
            flag all;
        }
    }
}
bgp {
    traceoptions {
        file bgp.log world-readable;
    }
    group ibgp {
        type internal;
        local-address 10.255.183.57;
        family inet {
            unicast;
        }
        family l2vpn {
            signaling {
                egress-protection;
            }
        }
        neighbor 192.0.2.3;
        neighbor 192.0.2.4;
    }
}
isis {
    traceoptions {
        file isis-edge size 10m world-readable;
        flag error;
    }
    level 1 disable;
    level 2 wide-metrics-only;
}

```



```

    interface all {
        point-to-point;
        level 2 metric 10;
    }
    interface fxp0.0 {
        disable;
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

[edit]
user@PE2# show policy-options
policy-statement lb {
    then {
        load-balance per-packet;
    }
}

[edit]
user@PE2# show routing-options
traceoptions {
    file ro.log;
    flag normal;
    flag route;
}
autonomous-system 100;
forwarding-table {
    export lb;
}

[edit]
user@PE2# show routing-instances
foo {
    instance-type l2vpn;
    egress-protection {
        protector;
    }
    interface ge-2/0/2.0;

```

```

route-distinguisher 10.255.183.57:1;
vrf-target target:9000:1;
protocols {
    l2vpn {
        encapsulation-type ethernet-vlan;
        site foo {
            hot-standby;
            site-identifier 1;
            site-preference backup;
            interface ge-2/0/2.0 {
                remote-site-id 2;
            }
        }
    }
}

```

From configuration mode, confirm your configuration on Router PE3 by entering the **show protocols**, **show policy-options**, and **show routing-options** commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

[edit]
user@PE3# show protocols
rsvp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    traceoptions {
        file bgp.log world-readable;
    }
    group ibgp {
        type internal;
        local-address 10.255.183.61;
    }
}

```

```

        family inet {
            unicast;
        }
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.3;
        neighbor 192.0.2.4;
    }
}
isis {
    traceoptions {
        file isis-edge size 10m world-readable;
        flag error;
    }
    level 1 disable;
    level 2 wide-metrics-only;
    interface all {
        point-to-point;
        level 2 metric 10;
    }
    interface fxp0.0 {
        disable;
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

```

[edit]

user@PE3# **show policy-options**

```

policy-statement lb {
    then {
        load-balance per-packet;
    }
}

```

[edit]

user@PE3# **show routing-options**

```

traceoptions {

```

```

    file ro.log;
    flag normal;
    flag route;
}
autonomous-system 100;
forwarding-table {
    export lb;
}

[edit]
user@PE3# show routing-instances
foo {
    instance-type l2vpn;
    interface ge-2/1/2.0;
    route-distinguisher 10.255.183.61:1;
    vrf-target target:9000:1;
    protocols {
        l2vpn {
            encapsulation-type ethernet-vlan;
            site foo {
                site-identifier 2;
                interface ge-2/1/2.0 {
                    remote-site-id 1;
                }
            }
        }
    }
}

```

Verification

IN THIS SECTION

- [Verifying the L2VPN Configuration | 546](#)
- [Verifying the Routing Instance Details | 547](#)
- [Verifying the IS-IS Configuration | 548](#)
- [Verifying the MPLS Configuration | 548](#)

Confirm that the configuration is working properly.

Verifying the L2VPN Configuration

Purpose

Verify that LSP is protected by the connection protection logic.

Action

From operational mode, run the `show l2vpn connections extensive` command.

```
user@PE2> show l2vpn connections extensive
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

Legend for interface status

Up -- operational

Dn -- down

Instance: foo

Local site: foo (1)

```

connection-site      Type St  Time last up      # Up trans
2                    rmt  Up  Aug 3 00:08:14 2001      1
  Local circuit: ge-2/0/2.0, Status: Up
  Remote PE: 192.0.2.3
  Incoming label: 32769, Outgoing label: 32768
  Egress Protection: Yes
    Time          Event          Interface/Lbl/PE
    Aug 3 00:08:14 2001  PE route up
    Aug 3 00:08:14 2001  Out lbl Update          32768
    Aug 3 00:08:14 2001  In lbl Update           32769
    Aug 3 00:08:14 2001  ckt0 up                 fe-0/0/0.0

```

Meaning

The Egress Protection: Yes output shows that the given PVC is protected by connection protection logic.

Verifying the Routing Instance Details

Purpose

Verify the routing instance information and the context identifier configured on the primary, which is used as the next-hop address in case of node-link failure.

Action

From operational mode, run the `show route foo detail` command.

```
user@PE2> show route foo detail
```

```

foo:
  Router ID: 0.0.0.0
  Type: l2vpn non-forwarding State: Active
  Interfaces:
    lt-1/2/0.56
  Route-distinguisher: 10.255.255.11:1
  Vrf-import: [ __vrf-import-foo-internal__ ]
  Vrf-export: [ __vrf-export-foo-internal__ ]
  Vrf-import-target: [ target:100:200 ]
  Vrf-export-target: [ target:100:200 ]

```

```
Fast-reroute-priority: low
Vrf-edge-protection-id: 198.51.100.3
Tables:
  foo.l2vpn.0      : 5 routes (3 active, 0 holddown, 0 hidden)
  foo.l2id.0       : 6 routes (2 active, 0 holddown, 0 hidden)
```

Meaning

The context-id is set to 198.51.100.3 and the Vrf-import: [__vrf-import-foo-internal__] in the output mentions the policy used for rewriting the next-hop address.

Verifying the IS-IS Configuration

Purpose

Verify the IS-IS context identifier information.

Action

From operational mode, run the `show isis context-identifier detail` command.

```
user@PE2> show isis context-identifier detail
```

```
IS-IS context database:
Context          L Owner   Role      Primary    Metric
198.51.100.3      2 MPLS    Protector pro17-b-lr-R1 0
  Advertiser pro17-b, Router ID 10.255.107.49, Level 2, tlv protector
  Advertiser pro17-b-lr-R1, Router ID 10.255.255.11, Metric 1, Level 2, tlv prefix
```

Meaning

Router PE2 is the protector and the configured context identifier is in use for the MPLS protocol.

Verifying the MPLS Configuration

Purpose

Verify the context identifier details on the primary and protector PEs.

Action

From operational mode, run the `show mpls context-identifier detail` command.

```
user@PE1> show mpls context-identifier detail
```

```
ID: 198.51.100.3
  Type: primary, Metric: 1, Mode: alias

Total 1, Primary 1, Protector 0
```

```
user@PE2> show mpls context-identifier detail
```

```
ID: 198.51.100.3
  Type: protector, Metric: 16777215, Mode: alias
  Context table: __198.51.100.3__.mpls.0, Label out: 299968
```

```
user@PE2> show mpls egress-protection detail
```

```
Instance          Type      Protection-Type
foo                local-l2vpn Protector
  Route Target 100:200
```

Meaning

Context-id is 198.51.100.3, advertise-mode is alias, the MPLS table created for egress protection is __198.51.100.3__.mpls.0, and the egress instance name is foo, which is of type local-l2vpn.

Release History Table

Release	Description
14.2	Starting in Junos OS Release 14.2, Junos OS supports the restoration of egress traffic when there is a link or node failure in the egress PE node.

Understanding Multisegment Pseudowire for FEC 129

IN THIS SECTION

- [Understanding Multisegment Pseudowire | 550](#)
- [Using FEC 129 for Multisegment Pseudowire | 552](#)
- [Establishing a Multisegment Pseudowire Overview | 553](#)
- [Pseudowire Status Support for Multisegment Pseudowire | 553](#)
- [Pseudowire TLV Support for MS-PW | 554](#)
- [Supported and Unsupported Features | 555](#)


Understanding Multisegment Pseudowire

A pseudowire is a Layer 2 circuit or service that emulates the essential attributes of a telecommunications service, such as a T1 line, over an MPLS packet-switched network (PSN). The pseudowire is intended to provide only the minimum necessary functionality to emulate the wire with the required resiliency requirements for the given service definition.

When a pseudowire originates and terminates on the edge of the same PSN, the pseudowire label is unchanged between the originating and terminating provider edge (T-PE) devices. This is called a single-segment pseudowire (SS-PW). [Figure 44 on page 551](#) illustrates an SS-PW established between two

PE routers. The pseudowires between the PE1 and PE2 routers are located within the same autonomous system (AS).

Figure 44: L2VPN Pseudowire




In cases where it is impossible to establish a single pseudowire from a local to a remote PE, either because it is unfeasible or undesirable to establish a single control plane between the two PEs, a multisegment pseudowire (MS-PW) is used.

An MS-PW is a set of two or more contiguous SS-PWs that are made to function as a single point-to-point pseudowire. It is also known as switched pseudowire. MS-PWs can go across different regions or network domains. A region can be considered as an interior gateway protocol (IGP) area or a BGP autonomous system that belongs to the same or different administrative domain. An MS-PW spans multiple cores or ASs of the same or different carrier networks. A Layer 2 VPN MS-PW can include up to 254 pseudowire segments.

[Figure 45 on page 552](#) illustrates a set of two or more pseudowire segments that function as a single pseudowire. The end routers are called terminating PE (T-PE) routers, and the switching routers are called switching PE (S-PE) routers. The S-PE router terminates the tunnels of the preceding and succeeding pseudowire segments in an MS-PW. The S-PE router can switch the control and data planes

of the preceding and succeeding pseudowire segments of the MS-PW. An MS-PW is declared to be up when all the single-segment pseudowires are up.

Figure 45: Multisegment Pseudowire



Using FEC 129 for Multisegment Pseudowire

Currently, there are two types of attachment circuit identifiers (AIs) defined under FEC 129:

- Type 1 AI
- Type 2 AI

The support of an MS-PW for FEC 129 uses type 2 AI. A type 2 AI is globally unique by definition of RFC 5003.

Single-segment pseudowires (SS-PWs) using FEC 129 on an MPLS PSN can use both type 1 and type 2 AI. For an MS-PW using FEC 129, a pseudowire itself is identified as a pair of endpoints. This requires that the pseudowire endpoints be uniquely identified.

In the case of a dynamically placed MS-PW, there is a requirement for the identifiers of attachment circuits to be globally unique, for the purposes of reachability and manageability of the pseudowire. Thus, individual globally unique addresses are allocated to all the attachment circuits and S-PEs that make up an MS-PW.

Type 2 AI is composed of three fields:

- Global_ID—Global identification, which is usually the AS number.
- Prefix—IPv4 address, which is usually the router ID.

- AC_ID—Local attachment circuit, which is a user-configurable value.

Since type 2 All already contains the T-PE's IP address and it is globally unique, from the FEC 129 pseudowire signaling point of view, the combination (AGI, SAll, TAll) uniquely identifies an MS-PW across all interconnected pseudowire domains.

Establishing a Multisegment Pseudowire Overview

An MS-PW is established by dynamically and automatically selecting the predefined S-PEs and placing the MS-PW between two T-PE devices.

When S-PEs are dynamically selected, each S-PE is automatically discovered and selected using the BGP autodiscovery feature, without the requirement of provisioning the FEC 129 pseudowire-related information on all the S-PEs. BGP is used to propagate pseudowire address information throughout the PSN.

Since there is no manual provisioning of FEC 129 pseudowire information on the S-PEs, the Attachment Group Identifier (AGI) and Attachment Individual Identifier (All) are reused automatically, and choosing the same set of S-PEs for the pseudowire in both the forwarding and reverse direction is achieved through the active and passive role of each T-PE device.

- Active—The T-PE initiates an LDP label mapping message.
- Passive—The T-PE does not initiate an LDP label mapping message until it receives a label mapping message initiated by the active T-PE. The passive T-PE sends its label mapping message to the same S-PE from where it received the label mapping message originated from its active T-PE. This ensures that the same set of S-PEs are used in the reverse direction.

Pseudowire Status Support for Multisegment Pseudowire

Pseudowire Status Behavior on T-PE

The following pseudowire status messages are relevant on the T-PE:

- 0x00000010—Local PSN-facing pseudowire (egress) transmit fault.
- 0x00000001—Generic nonforwarding fault code. This is set as the local fault code. The local fault code is set at the local T-PE, and LDP sends a pseudowire status TLV message with the same fault code to the remote T-PE.
- Fault codes are bit-wise OR'ed and stored as remote pseudowire status codes.

Pseudowire Status Behavior on S-PE

The S-PE initiates the pseudowire status messages that indicate the pseudowire faults. The SP-PE in the pseudowire notification message hints where the fault was originated.

- When a local fault is detected by the S-PE, a pseudowire status message is sent in both directions along the pseudowire. Since there are no attachment circuits on an S-PE, only the following status messages are relevant:
 - 0x00000008—Local PSN-facing pseudowire (ingress) receive fault.
 - 0x00000010—Local PSN-facing pseudowire (egress) transmit fault.
- To indicate which SS-PW is at fault, an LDP SP-PE TLV is attached with the pseudowire status code in the LDP notification message. The pseudowire status is passed along from one pseudowire to another unchanged by the control plane switching function.
- If an S-PE initiates a pseudowire status notification message with one particular pseudowire status bit, then for the pseudowire status code an S-PE receives, the same bit is processed locally and not forwarded until the S-PE's original status error is cleared.
- An S-PE keeps only two pseudowire status codes for each SS-PW it is involved in – local pseudowire status code and remote pseudowire status code. The value of the remote pseudowire status code is the result of logic or operation of the pseudowire status codes in the chain of SS-PWs preceding this segment. This status code is incrementally updated by each S-PE upon receipt and communicated to the next S-PE. The local pseudowire status is generated locally based on its local pseudowire status.
- Only transmit fault is detected at the SP-PE. When there is no MPLS LSP to reach the next segment, a local transmit fault is detected. The transmit fault is sent to the next downstream segment, and the receive fault is sent to the upstream segment.
- Remote failures received on an S-PE are just passed along the MS-PW unchanged. Local failures are sent to both segments of the pseudowire that the S-PE is involved in.

Pseudowire TLV Support for MS-PW

MS-PW provides the following support for the LDP SP-PE TLV [RFC 6073]:

- The LDP SP-PE TLVs for an MS-PW include:
 - Local IP address
 - Remote IP address
- An SP-PE adds the LDP SP-PE TLV to the label mapping message. Each SP-PE appends the local LDP SP-PE TLV to the SP-PE list it received from the other segment.

- The pseudowire status notification message includes the LDP SP-PE TLV when the notification is generated at the SP-PE.

Supported and Unsupported Features

Junos OS supports the following features with MS-PW:

- MPLS PSN for each SS-PW that builds up the MS-PW.
- The same pseudowire encapsulation for each SS-PW in an MS-PW – Ethernet or VLAN-CCC.
- The generalized PWid FEC with T-LDP as an end-to-end pseudowire signaling protocol to set up each SS-PW.
- MP-BGP to autodiscover the two endpoint PEs for each SS-PW associated with the MS-PW.
- Standard MPLS operation to stitch two side-by-side SS-PWs to form an MS-PW.
- Automatic discovery of S-PE so that the MS-PW can be dynamically placed.
- Minimum provisioning of S-PE.
- Operation, administration, and maintenance (OAM) mechanisms, including end-to-end MPLS ping or end-to-any-S-PE MPLS ping, MPLS path trace, end-to-end VCCV, and Bidirectional Forwarding Detection (BFD).
- Pseudowire swithing point (SP) PE TLV for the MS-PW.
- Composite next hop on MS-PW.
- Pseudowire status TLV for MS-PW.

Junos OS does not support the following MS-PW functionality:

- Mix of LDP FEC 128 and LDP FEC 129.
- Static pseudowire where each label is provisioned statically.
- Graceful Routing Engine switchover.
- Nonstop active routing.
- Multihoming.
- Partial connectivity verification (originating from an S-PE) in OAM.

Example: Configuring a Multisegment Pseudowire

IN THIS SECTION

- [Requirements | 556](#)
- [Overview | 557](#)
- [Configuration | 563](#)
- [Verification | 591](#)
- [Troubleshooting | 602](#)

This example shows how to configure a dynamic multisegment pseudowire (MS-PW), where the stitching provider edge (S-PE) devices are automatically and dynamically discovered by BGP, and pseudowires are signaled by LDP using FEC 129. This arrangement requires minimum provisioning on the S-PEs, thereby reducing the configuration burden that is associated with statically configured Layer 2 circuits while still using LDP as the underlying signaling protocol.

Requirements

This example uses the following hardware and software components:

- Six routers that can be a combination of M Series Multiservice Edge Routers, MX Series 5G Universal Routing Platforms, T Series Core Routers, or PTX Series Packet Transport Routers.
 - Two remote PE devices configured as terminating PEs (T-PEs).
 - Two S-PEs configured as:
 - Route reflectors, in the case of interarea configuration.
 - AS boundary routers or route reflectors, in the case of inter-AS configuration.
- Junos OS Release 13.3 or later running on all the devices.

Before you begin:

1. Configure the device interfaces.
2. Configure OSPF or any other IGP protocol.
3. Configure BGP.
4. Configure LDP.

5. Configure MPLS.

Overview

Starting with Junos OS Release 13.3, you can configure an MS-PW using FEC 129 with LDP signaling and BGP autodiscovery in an MPLS packet-switched network (PSN). The MS-PW feature also provides operation, administration, and management (OAM) capabilities, such as ping, traceroute, and BFD, from the T-PE devices.

To enable autodiscovery of S-PEs in an MS-PW, include the `auto-discovery-mspw` statement at the `[edit protocols bgp group group-name family l2vpn]` hierarchy level.

```
family l2vpn {
    auto-discovery-mspw;
}
```

The automatic selection of S-PE and dynamic setting up of an MS-PW rely heavily on BGP. BGP network layer reachability information (NLRI) constructed for the FEC 129 pseudowire to autodiscover the S-PE is called an MS-PW NLRI [draft-ietf-pwe3-dynamic-ms-pw-15.txt]. The MS-PW NLRI is essentially a prefix consisting of a route distinguisher (RD) and FEC 129 source attachment identifier (SAII). It is referred to as a BGP autodiscovery (BGP-AD) route and is encoded as RD:SAII.

Only T-PEs that are provisioned with type 2 AIs initiate their own MS-PW NLRI respectively. Since a type 2 AI is globally unique, an MS-PW NLRI is used to identify a PE device to which the type 2 AI is provisioned. The difference between a type 1 AI and a type 2 AI requires that a new address family indicator (AFI) and subsequent address family identifier (SAFI) be defined in BGP to support an MS-PW. The proposed AFI and SAFI value pair used to identify the MS-PW NLRI is 25 and 6, respectively (pending IANA allocation).

The AFI and SAFI values support autodiscovery of S-PEs and should be configured on both T-PEs that originate the routes, and the S-PEs that participate in the signaling.

[Figure 46 on page 558](#) illustrates an inter-area MS-PW setup between two remote PE routers—T-PE1 and T-PE2. The Provider (P) routers are P1 and P2, and the S-PE routers are S-PE1 and S-PE2. The MS-PW is established between T-PE1 and T-PE2, and all the devices belong to the same AS—AS 100. Since S-PE1 and S-PE2 belong to the same AS, they act as route reflectors and are also known as RR 1 and RR 2, respectively.

[Figure 47 on page 558](#) illustrates an inter-AS MS-PW setup. The MS-PW is established between T-PE1 and T-PE2, where T-PE1, P1, and S-PE1 belong to AS 1, and S-PE2, P2, and T-PE2 belong to AS 2. Since

S-PE1 and S-PE2 belong to different ASs, they are configured as ASBR routers and are also known as ASBR 1 and ASBR 2, respectively.

Figure 46: Interarea Multisegment Pseudowire





Figure 47: Inter-AS Multisegment Pseudowire



The following sections provide information about how an MS-PW is established in an interarea and inter-AS scenario.

Minimum Configuration Requirements on S-PE

In order to dynamically discover both ends of an SS-PW and set up a T-LDP session dynamically, the following is required:

- For interarea MS-PW, each S-PE plays both an ABR and BGP route reflector role.

In the interarea case, as seen in [Figure 46 on page 558](#), the S-PE plays a BGP route reflector role and reflects the BGP-AD route to its client. A BGP-AD route advertised by one T-PE eventually reaches its remote T-PE. Because of the next-hop-self set by each S-PE, the S-PE or T-PE that receives a BGP-AD route can always discover the S-PE that advertises the BGP-AD in its local AS or local area through the BGP next hop.

- For inter-AS MS-PW, each S-PE plays either an ASBR or a BGP route reflector role.

In an MS-PW, the two T-PEs initiate a BGP-AD route respectively. When the S-PE receives the BGP-AD route through either the IBGP session with the T-PE or through a regular BGP-RR, it sets the next-hop-self before re-advertising the BGP-AD route to one or more of its EBGP peers in the inter-AS case, as seen in [Figure 47 on page 558](#).

- Each S-PE must set next-hop-self when re-advertising or reflecting a BGP-AD route for the MS-PW.

Active and Passive Role of T-PE

To ensure that the same set of S-PEs are being used for a MS-PW in both directions, the two T-PEs play different roles in terms of FEC 129 signaling. This is to avoid different paths being chosen by T-PE1 and T-PE2 when each S-PE is dynamically selected for an MS-PW.

When an MS-PW is signaled using FEC 129, each T-PE might independently start signaling the MS-PW. The signaling procedure can result in an attempt to set up each direction of the MS-PW through different S-PEs.

To avoid this situation, one of the T-PEs must start the pseudowire signaling (active role), while the other waits to receive the LDP label mapping before sending the respective pseudowire LDP label mapping message (passive role). When the MS-PW path is dynamically placed, the active T-PE (the Source T-PE) and the passive T-PE (the Target T-PE) must be identified before signaling is initiated for a given MS-PW. The determination of which T-PE assumes the active role is done based on the SAll value, where the T-PE that has a larger SAll value plays the active role.

In this example, the SAll values of T-PE1 and T-PE 2 are 800:800:800 and 700:700:700, respectively. Since T-PE1 has a higher SAll value, it assumes the active role and T-PE2 assumes the passive role.

Directions for Establishing an MS-PW

The directions used by the S-PE for setting up the MS-PW are:

- Forwarding direction—From an active T-PE to a passive T-PE.

In this direction, the S-PEs perform a BGP-AD route lookup to determine the next-hop S-PE to send the label mapping message.

- Reverse direction—From a passive T-PE to an active T-PE.

In this direction, the S-PEs do not perform a BGP-AD route lookup, because the label mapping messages are received from the T-PEs, and the stitching routes are installed in the S-PEs.

In this example, the MS-PW is established in the forwarding direction from T-PE1 to T-PE2. When the MS-PW is placed from T-PE2 to T-PE1, the MS-PW is established in the reverse direction.

Autodiscovery and Dynamic Selection of S-PE

A new AFI and SAFI value is defined in BGP to support the MS-PWs based on type 2 AII. This new address family supports autodiscovery of S-PEs. This address family must be configured on both the T-PEs and S-PEs.

It is the responsibility of the Layer 2 VPN component to dynamically select the next S-PE to use along the MS-PW in the forwarding direction.

- In the forwarding direction, the selection of the next S-PE is based on the BGP-AD route advertised by the BGP and pseudowire FEC information sent by the LDP. The BGP-AD route is initiated by the passive T-PE (T-PE2) in the reverse direction while the pseudowire FEC information is sent by LDP from the active T-PE (T-PE1) in the forwarding direction.
- In the reverse direction, the next S-PE (S-PE2) or the active T-PE (T-PE1) is obtained by looking up the S-PE (S-PE1) that it used to set up the pseudowire in the forwarding direction.

Provisioning a T-PE

To support FEC 129 type 2 AII, the T-PE needs to configure its remote T-PE's IP address, a global ID, and an attachment circuit ID. Explicit paths where a set of S-PEs to use is explicitly specified on a T-PE is not supported. This eliminates the need to provision each S-PE with a type 2 AII.

Stitching an MS-PW

An S-PE performs the following MPLS label operations before forwarding the received label mapping message to the next S-PE:

1. Pops the MPLS tunnel label.
2. Pops the VC label.
3. Pushes a new VC label.
4. Pushes an MPLS tunnel label used for the next segment.

Establishing an MS-PW

After completing the necessary configuration, an MS-PW is established in the following manner:

1. The SAll values are exchanged between T-PE1 and T-PE2 using BGP.

T-PE1 assumes the active T-PE role, because it is configured with a higher SAll value. T-PE2 becomes the passive T-PE.

2. T-PE1 receives the BGP-AD route originated by T-PE2. It compares the All values obtained from T-PE2 in the received BGP-AD route against the All values provisioned locally.

3. If the All values match, T-PE1 performs a BGP-AD route lookup to elect the first S-PE (S-PE1).

4. T-PE1 sends an LDP label mapping message to S-PE1.

5. Using the BGP-AD route originated from T-PE2, and the LDP label mapping message received from T-PE1, S-PE1 selects the next S-PE (S-PE2) in the forwarding direction.

To do this, S-PE1 compares SAll obtained from the BGP-AD route against the TAI from the LDP label mapping message.

6. If the All values match, S-PE1 finds S-PE2 through the BGP next hop associated with the BGP-AD route.

7. The process of selecting S-PE goes on until the last S-PE establishes a T-LDP session with T-PE2. When T-PE2 receives the LDP label mapping message from the last S-PE (S-PE2), it initiates its own label mapping message and sends it back to S-PE2.

8. When all the label mapping messages are received on S-PE1 and S-PE2, the S-PEs install the stitching routes. Thus, when the MS-PW is established in the reverse direction, the S-PEs need not perform BGP-AD route lookup to determine its next hop as it did in the forwarding direction.

OAM Support for an MS-PW

After the MS-PW is established, the following OAM capabilities can be executed from the T-PE devices:

- Ping
- End-to-End Connectivity Verification Between T-PEs

If T-PE1, S-PEs, and T-PE2 support Control Word (CW), the pseudowire control plane automatically negotiates the use of the CW. Virtual Circuit Connectivity Verification (VCCV) Control Channel (CC) Type 3 will function correctly whether or not the CW is enabled on the pseudowire. However, VCCV Type 1, which is used for end-to-end verification only, is only supported if the CW is enabled.

The following is a sample:

Ping from T-P1 to T-PE2

```
user@T-PE1> ping mpls l2vpn fec129 instance instance-name local-id SAII of T-PE1 remote-pe-  
address address of T-PE2 remote-id TAII of T-PE2
```

or

```
user@T-PE1> ping mpls l2vpn fec129 interface CE1-facing interface
```

- Partial Connectivity Verification from T-PE to Any S-PE

To trace part of an MS-PW, the TTL of the pseudowire label can be used to force the VCCV message to pop out at an intermediate node. When the TTL expires, the S-PE can determine that the packet is a VCCV packet either by checking the CW or by checking for a valid IP header with UDP destination port 3502 (if the CW is not in use). The packet should then be diverted to VCCV processing.

If T-PE1 sends a VCCV message with the TTL of the pseudowire label equal to 1, the TTL expires at the S-PE. T-PE1 can thus verify the first segment of the pseudowire.

The VCCV packet is built according to RFC 4379. All the information necessary to build the VCCV LSP ping packet is collected by inspecting the S-PE TLVs. This use of the TTL is subject to the caution expressed in RFC 5085. If a penultimate LSR between S-PEs or between an S-PE and a T-PE manipulates the pseudowire label TTL, the VCCV message might not emerge from the MS-PW at the correct S-PE.

The following is a sample:

Ping from T-PE1 to S-PE

```
user@T-PE1> ping mpls l2vpn fec129 interface CE1-facing interface bottom-label-ttl segment
```

The bottom-label-ttl value is 1 for S-PE1 and 2 for S-PE2.

The bottom-label-ttl statement sets the correct VC label TTL, so the packets are popped to the correct SS-PW for VCCV processing.

NOTE: Junos OS supports VCCV Type 1 and Type 3 for the MS-PW OAM capability. VCCV Type 2 is not supported.

- Traceroute

Traceroute tests each S-PE along the path of the MS-PW in a single operation similar to LSP trace. This operation is able to determine the actual data path of the MS-PW, and is used for dynamically signaled MS-PWs.

```
user@T-PE1> traceroute mpls l2vpn fec129 interface CE1-facing interface
```

- Bidirectional Forwarding Detection

Bidirectional Forwarding Detection (BFD) is a detection protocol designed to provide fast forwarding path failure detection times for all media types, encapsulations, topologies, and routing protocols. In addition to fast forwarding path failure detection, BFD provides a consistent failure detection method for network administrators. The router or switch can be configured to log a system log (syslog) message when BFD goes down.

```
user@T-PE1> show bfd session extensive
```

Configuration

IN THIS SECTION

- [Configuring an Interarea MS-PW | 563](#)
- [Configuring an Inter-AS MS-PW | 577](#)

Configuring an Interarea MS-PW

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

T-PE1

```
set interfaces ge-3/1/0 unit 0 family inet address 192.0.2.1/24
set interfaces ge-3/1/0 unit 0 family mpls
set interfaces ge-3/1/2 encapsulation ethernet-ccc
set interfaces ge-3/1/2 unit 0
```

```

set interfaces lo0 unit 0 family inet address 10.255.10.1/32 primary
set routing-options autonomous-system 100
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group mspw type internal
set protocols bgp group mspw local-address 10.255.10.1
set protocols bgp group mspw neighbor 10.255.2.1
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances ms-pw instance-type l2vpn
set routing-instances ms-pw interface ge-3/1/2.0
set routing-instances ms-pw route-distinguisher 10.10.10.10:15
set routing-instances ms-pw l2vpn-id l2vpn-id:100:15
set routing-instances ms-pw vrf-target target:100:115
set routing-instances ms-pw protocols l2vpn site CE1 source-attachment-identifier 800:800:800
set routing-instances ms-pw protocols l2vpn site CE1 interface ge-3/1/2.0 target-attachment-
identifier 700:700:700
set routing-instances ms-pw protocols l2vpn pseudowire-status-tlv
set routing-instances ms-pw protocols l2vpn oam bfd-liveness-detection minimum-interval 300

```

P1

```

set interfaces ge-2/0/0 unit 0 family inet address 192.0.2.2/24
set interfaces ge-2/0/0 unit 0 family mpls
set interfaces ge-2/0/2 unit 0 family inet address 192.0.2.13/24
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.13.1/32 primary
set routing-options autonomous-system 100
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0

```

S-PE1 (RR 1)

```

set interfaces ge-1/3/1 unit 0 family inet address 192.0.2.9/24
set interfaces ge-1/3/1 unit 0 family mpls
set interfaces ge-1/3/2 unit 0 family inet address 192.0.2.22/24
set interfaces ge-1/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.2.1/32 primary
set routing-options autonomous-system 100
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group mspw type internal
set protocols bgp group mspw local-address 10.255.2.1
set protocols bgp group mspw export next-hop-self
set protocols bgp group mspw cluster 203.0.113.0
set protocols bgp group mspw neighbor 10.255.10.1
set protocols bgp group mspw neighbor 10.255.3.1
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set policy-options policy-statement next-hop-self then next-hop self
set policy-options policy-statement send-inet0 from protocol bgp
set policy-options policy-statement send-inet0 then accept

```

S-PE2 (RR 2)

```

set interfaces ge-0/3/1 unit 0 family inet address 192.0.2.10/24
set interfaces ge-0/3/1 unit 0 family mpls
set interfaces ge-0/3/2 unit 0 family inet address 192.0.2.14/24
set interfaces ge-0/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.3.1/32 primary
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group mspw type internal
set protocols bgp group mspw local-address 10.255.3.1
set protocols bgp group mspw export next-hop-self
set protocols bgp group mspw cluster 198.51.100.0

```



```

set protocols bgp group mspw neighbor 10.255.2.1
set protocols bgp group mspw neighbor 10.255.14.1
set protocols bgp group int type internal
set protocols bgp group int local-address 10.255.3.1
set protocols bgp group int neighbor 10.255.2.1
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set policy-options policy-statement next-hop-self then next-hop self
set policy-options policy-statement send-inet0 from protocol bgp
set policy-options policy-statement send-inet0 then accept

```

P2

```

set interfaces ge-1/3/1 unit 0 family inet address 192.0.2.5/24
set interfaces ge-1/3/1 unit 0 family mpls
set interfaces ge-1/3/2 unit 0 family inet address 192.0.2.4/24
set interfaces ge-1/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.4.1/32 primary
set routing-options autonomous-system 100
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0

```

T-PE2

```

set interfaces ge-2/0/0 encapsulation ethernet-ccc
set interfaces ge-2/0/0 unit 0
set interfaces ge-2/0/2 unit 0 family inet address 192.0.2.15/24
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.1/32 primary
set routing-options autonomous-system 100
set protocols mpls interface all

```

```

set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group mspw type internal
set protocols bgp group mspw local-address 10.255.14.1
set protocols bgp group mspw neighbor 10.255.3.1
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances ms-pw instance-type l2vpn
set routing-instances ms-pw interface ge-2/0/0.0
set routing-instances ms-pw route-distinguisher 10.10.10.10:15
set routing-instances ms-pw l2vpn-id l2vpn-id:100:15
set routing-instances ms-pw vrf-target target:100:115
set routing-instances ms-pw protocols l2vpn site CE2 source-attachment-identifier 700:700:700
set routing-instances ms-pw protocols l2vpn site CE2 interface ge-2/0/0.0 target-attachment-
identifier 800:800:800
set routing-instances ms-pw protocols l2vpn pseudowire-status-tlv
set routing-instances ms-pw protocols l2vpn oam bfd-liveness-detection minimum-interval 300

```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure T-PE1 in the interarea scenario:

NOTE: Repeat this procedure for the T-PE2 device in the MPLS domain, after modifying the appropriate interface names, addresses, and other parameters.

1. Configure the T-PE1 interfaces.

```

[edit interfaces]
user@T-PE1# set ge-3/1/0 unit 0 family inet address 192.0.2.1/24
user@T-PE1# set ge-3/1/0 unit 0 family mpls
user@T-PE1# set ge-3/1/2 encapsulation ethernet-ccc
user@T-PE1# set ge-3/1/2 unit 0
user@T-PE1# set lo0 unit 0 family inet address 10.255.10.1/32 primary

```

2. Set the autonomous system number.

```
[edit routing-options]
user@T-PE1# set autonomous-system 100
```

3. Enable MPLS on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@T-PE1# set mpls interface all
user@T-PE1# set mpls interface fxp0.0 disable
```

4. Enable autodiscovery of intermediate S-PEs that make up the MS-PW using BGP.

```
[edit protocols]
user@T-PE1# set bgp family l2vpn auto-discovery-mspw
```

5. Configure the BGP group for T-PE1.

```
[edit protocols]
user@T-PE1# set bgp group mspw type internal
```

6. Assign local and neighbor addresses to the mspw group for T-PE1 to peer with S-PE1.

```
[edit protocols]
user@T-PE1# set bgp group mspw local-address 10.255.10.1
user@T-PE1# set bgp group mspw neighbor 10.255.2.1
```

7. Configure OSPF on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@T-PE1# set ospf area 0.0.0.0 interface lo0.0
user@T-PE1# set ospf area 0.0.0.0 interface all
user@T-PE1# set ospf area 0.0.0.0 interface fxp0.0 disable
```

8. Configure LDP on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@T-PE1# set ldp interface all
user@T-PE1# set ldp interface fxp0.0 disable
user@T-PE1# set ldp interface lo0.0
```

9. Configure the Layer 2 VPN routing instance on T-PE1.

```
[edit routing-instances]
user@T-PE1# set ms-pw instance-type l2vpn
```

10. Assign the interface name for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw interface ge-3/1/2.0
```

11. Configure the route distinguisher for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw route-distinguisher 10.10.10.10:15
```

12. Configure the Layer 2 VPN ID community for FEC 129 MS-PW.

```
[edit routing-instances]
user@T-PE1# set ms-pw l2vpn-id l2vpn-id:100:15
```

13. Configure a VPN routing and forwarding (VRF) target for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw vrf-target target:100:115
```

14. Configure the source attachment identifier (SAI) value using Layer 2 VPN as the routing protocol for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn site CE1 source-attachment-identifier 800:800:800
```

15. Assign the interface name that connects the CE1 site to the VPN, and configure the target attachment identifier (TAI) value using Layer 2 VPN as the routing protocol for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn site CE1 interface ge-3/1/2.0 target-attachment-identifier 700:700:700
```

16. (Optional) Configure T-PE1 to send MS-PW status TLVs.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn pseudowire-status-tlv
```

17. (Optional) Configure OAM capabilities for the VPN.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn oam bfd-liveness-detection minimum-interval 300
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure S-PE1 (RR 1) in the interarea scenario:

NOTE: Repeat this procedure for the S-PE2 (RR 2) device in the MPLS domain, after modifying the appropriate interface names, addresses, and other parameters.

1. Configure the S-PE1 interfaces.

```
[edit interfaces]
user@S-PE1# set ge-1/3/1 unit 0 family inet address 192.0.2.9/24
user@S-PE1# set ge-1/3/1 unit 0 family mpls
user@S-PE1# set ge-1/3/2 unit 0 family inet address 192.0.2.22/24
user@S-PE1# set ge-1/3/2 unit 0 family mpls
user@S-PE1# set lo0 unit 0 family inet address 10.255.2.1/32 primary
```

2. Set the autonomous system number.

```
[edit routing-options]
user@S-PE1# set autonomous-system 100
```

3. Enable MPLS on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@S-PE1# set mpls interface all
user@S-PE1# set mpls interface fxp0.0 disable
```

4. Enable autodiscovery of S-PE using BGP.

```
[edit protocols]
user@S-PE1# set bgp family l2vpn auto-discovery-mspw
```

5. Configure the BGP group for S-PE1.

```
[edit protocols]
user@S-PE1# set bgp group mspw type internal
```

6. Configure S-PE1 to act as a route reflector.

```
[edit protocols]
user@S-PE1# set bgp group mspw export next-hop-self
user@S-PE1# set bgp group mspw cluster 203.0.113.0
```

7. Assign local and neighbor addresses to the mspw group for S-PE1 to peer with T-PE1 and S-PE2.

```
[edit protocols]
user@S-PE1# set bgp group mspw local-address 10.255.2.1
user@S-PE1# set bgp group mspw neighbor 10.255.10.1 (to T-PE1)
user@S-PE1# set bgp group mspw neighbor 10.255.3.1 (to S-PE2)
```

8. Configure OSPF on all the interfaces of S-PE1, excluding the management interface.

```
[edit protocols]
user@S-PE1# set ospf area 0.0.0.0 interface all
user@S-PE1# set ospf area 0.0.0.0 interface fxp0.0 disable
user@S-PE1# set ospf area 0.0.0.0 interface lo0.0
```

9. Configure LDP on all the interfaces of S-PE1, excluding the management interface.

```
[edit protocols]
user@S-PE1# set ldp interface all
user@S-PE1# set ldp interface fxp0.0 disable
user@S-PE1# set ldp interface lo0.0
```

10. Define the policy for enabling next-hop-self and accepting BGP traffic on S-PE1.

```
[edit policy-options]
user@S-PE1# set policy-statement next-hop-self then next-hop self
user@S-PE1# set policy-statement send-inet0 from protocol bgp
user@S-PE1# set policy-statement send-inet0 then accept
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, `show routing-options`, and `show policy-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

T-PE1

```
user@T-PE1# show interfaces
ge-3/1/0 {
```

```

    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
        family mpls;
    }
}
ge-3/1/2 {
    encapsulation ethernet-ccc;
    unit 0;
}
lo0 {
    unit 0 {
        family inet {
            address 10.255.10.1/32 {
                primary;
            }
        }
    }
}
}

```

```

user@T-PE1# show routing-options
autonomous-system 100;

```

```

user@T-PE1# show protocols
mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    family l2vpn {
        auto-discovery-mspw;
    }
    group mspw {
        type internal;
        local-address 10.255.10.1;
        neighbor 10.255.2.1;
    }
}

```



```

}
ospf {
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
        interface lo0.0;
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}

```

```

user@T-PE1# show routing-instances
ms-pw {
    instance-type l2vpn;
    interface ge-3/1/2.0;
    route-distinguisher 10.10.10.10:15;
    l2vpn-id l2vpn-id:100:15;
    vrf-target target:100:115;
    protocols {
        l2vpn {
            site CE1 {
                source-attachment-identifier 800:800:800;
                interface ge-3/1/2.0 {
                    target-attachment-identifier 700:700:700;
                }
            }
            pseudowire-status-tlv;
            oam {
                bfd-liveness-detection {
                    minimum-interval 300;
                }
            }
        }
    }
}

```

```

    }
}

```

S-PE1 (RR 1)

```

user@S-PE1# show interfaces
ge-1/3/1 {
  unit 0 {
    family inet {
      address 192.0.2.9/24;
    }
    family mpls;
  }
}
ge-1/3/2 {
  unit 0 {
    family inet {
      address 192.0.2.22/24;
    }
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.255.2.1/32 {
        primary;
      }
    }
  }
}
}

```

```

user@S-PE1# show routing-options
autonomous-system 100;

```

```

user@S-PE1# show protocols
mpls {
  interface all;
  interface fxp0.0 {

```

```

        disable;
    }
}
bgp {
    family l2vpn {
        auto-discovery-mspw;
    }
    group mspw {
        type internal;
        local-address 10.255.2.1;
        export next-hop-self;
        cluster 203.0.113.0;
        neighbor 10.255.10.1;
        neighbor 10.255.3.1;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.0;
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}

```

```

user@S-PE1# show policy-options
policy-statement next-hop-self {
    then {
        next-hop self;
    }
}
policy-statement send-inet0 {
    from protocol bgp;
}

```

```

    then accept;
}

```

If you are done configuring the device, enter `commit` from configuration mode.

Configuring an Inter-AS MS-PW

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

T-PE1

```

set interfaces ge-3/1/0 unit 0 family inet address 192.0.2.1/24
set interfaces ge-3/1/0 unit 0 family mpls
set interfaces ge-3/1/2 encapsulation ethernet-ccc
set interfaces ge-3/1/2 unit 0
set interfaces lo0 unit 0 family inet address 10.255.10.1/32 primary
set routing-options autonomous-system 1
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group mspw type internal
set protocols bgp group mspw local-address 10.255.10.1
set protocols bgp group mspw neighbor 10.255.2.1
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances ms-pw instance-type l2vpn
set routing-instances ms-pw interface ge-3/1/2.0
set routing-instances ms-pw route-distinguisher 10.10.10.10:15
set routing-instances ms-pw l2vpn-id l2vpn-id:100:15
set routing-instances ms-pw vrf-target target:100:115
set routing-instances ms-pw protocols l2vpn site CE1 source-attachment-identifier 800:800:800
set routing-instances ms-pw protocols l2vpn site CE1 interface ge-3/1/2.0 target-attachment-
identifier 700:700:700

```

```
set routing-instances ms-pw protocols l2vpn pseudowire-status-tlv
set routing-instances ms-pw protocols l2vpn oam bfd-liveness-detection minimum-interval 300
```

P1

```
set interfaces ge-2/0/0 unit 0 family inet address 192.0.2.2/24
set interfaces ge-2/0/0 unit 0 family mpls
set interfaces ge-2/0/2 unit 0 family inet address 192.0.2.13/24
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.13.1/32 primary
set routing-options autonomous-system 1
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
```

S-PE1 (ASBR 1)

```
set interfaces ge-1/3/1 unit 0 family inet address 192.0.2.9/24
set interfaces ge-1/3/1 unit 0 family mpls
set interfaces ge-1/3/2 unit 0 family inet address 192.0.2.22/24
set interfaces ge-1/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.2.1/32 primary
set routing-options autonomous-system 1
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group to_T-PE1 type internal
set protocols bgp group to_T-PE1 local-address 10.255.2.1
set protocols bgp group to_T-PE1 export next-hop-self
set protocols bgp group to_T-PE1 neighbor 10.255.10.1
set protocols bgp group to_S-PE2 type external
set protocols bgp group to_S-PE2 local-address 10.255.2.1
set protocols bgp group to_S-PE2 peer-as 2
set protocols bgp group to_S-PE2 neighbor 10.255.3.1 multihop ttl 1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface all
```

```

set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set policy-options policy-statement next-hop-self then next-hop self

```

S-PE2 (ASBR 2)

```

set interfaces ge-0/3/1 unit 0 family inet address 192.0.2.10/24
set interfaces ge-0/3/1 unit 0 family mpls
set interfaces ge-0/3/2 unit 0 family inet address 192.0.2.14/24
set interfaces ge-0/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.3.1/32 primary
set routing-options autonomous-system 2
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group to_T-PE2 type internal
set protocols bgp group to_T-PE2 local-address 10.255.3.1
set protocols bgp group to_T-PE2 export next-hop-self
set protocols bgp group to_T-PE2 neighbor 10.255.14.1
set protocols bgp group to_S-PE1 type external
set protocols bgp group to_S-PE1 local-address 10.255.3.1
set protocols bgp group to_S-PE1 peer-as 1
set protocols bgp group to_S-PE1 neighbor 10.255.2.1 multihop ttl 1
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set policy-options policy-statement next-hop-self then next-hop self

```

P2

```

set interfaces ge-1/3/1 unit 0 family inet address 192.0.2.5/24
set interfaces ge-1/3/1 unit 0 family mpls
set interfaces ge-1/3/2 unit 0 family inet address 192.0.2.4/24
set interfaces ge-1/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.4.1/32 primary
set routing-options autonomous-system 2

```

```

set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0

```

T-PE2

```

set interfaces ge-2/0/0 encapsulation ethernet-ccc
set interfaces ge-2/0/0 unit 0
set interfaces ge-2/0/2 unit 0 family inet address 192.0.2.15/24
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.1/32 primary
set routing-options autonomous-system 2
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp family l2vpn auto-discovery-mspw
set protocols bgp group mspw type internal
set protocols bgp group mspw local-address 10.255.14.1
set protocols bgp group mspw neighbor 10.255.3.1
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances ms-pw instance-type l2vpn
set routing-instances ms-pw interface ge-2/0/0.0
set routing-instances ms-pw route-distinguisher 10.10.10.10:15
set routing-instances ms-pw l2vpn-id l2vpn-id:100:15
set routing-instances ms-pw vrf-target target:100:115
set routing-instances ms-pw protocols l2vpn site CE2 source-attachment-identifier 700:700:700
set routing-instances ms-pw protocols l2vpn site CE2 interface ge-2/0/0.0 target-attachment-
identifier 800:800:800
set routing-instances ms-pw protocols l2vpn pseudowire-status-tlv
set routing-instances ms-pw protocols l2vpn oam bfd-liveness-detection minimum-interval 300

```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure the T-PE1 router in the inter-AS scenario:

NOTE: Repeat this procedure for the T-PE2 device in the MPLS domain, after modifying the appropriate interface names, addresses, and other parameters.

1. Configure the T-PE1 interfaces.

```
[edit interfaces]
user@T-PE1# set ge-3/1/0 unit 0 family inet address 192.0.2.1/24
user@T-PE1# set ge-3/1/0 unit 0 family mpls
user@T-PE1# set ge-3/1/2 encapsulation ethernet-ccc
user@T-PE1# set ge-3/1/2 unit 0
user@T-PE1# set lo0 unit 0 family inet address 10.255.10.1/32 primary
```

2. Set the autonomous system number.

```
[edit routing-options]
user@T-PE1# set autonomous-system 1
```

3. Enable MPLS on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@T-PE1# set mpls interface all
user@T-PE1# set mpls interface fxp0.0 disable
```

4. Enable autodiscovery of intermediate S-PEs that make up the MS-PW using BGP.

```
[edit protocols]
user@T-PE1# set bgp family l2vpn auto-discovery-mspw
```


5. Configure the BGP group for T-PE1.

```
[edit protocols]
user@T-PE1# set bgp group mspw type internal
```

6. Assign local and neighbor addresses to the mspw group for T-PE1 to peer with S-PE1.

```
[edit protocols]
user@T-PE1# set bgp group mspw local-address 10.255.10.1
user@T-PE1# set bgp group mspw neighbor 10.255.2.1
```

7. Configure OSPF on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@T-PE1# set ospf area 0.0.0.0 interface lo0.0
user@T-PE1# set ospf area 0.0.0.0 interface all
user@T-PE1# set ospf area 0.0.0.0 interface fxp0.0 disable
```

8. Configure LDP on all the interfaces of T-PE1, excluding the management interface.

```
[edit protocols]
user@T-PE1# set ldp interface all
user@T-PE1# set ldp interface fxp0.0 disable
user@T-PE1# set ldp interface lo0.0
```

9. Configure the Layer 2 VPN routing instance on T-PE1.

```
[edit routing-instances]
user@T-PE1# set ms-pw instance-type l2vpn
```

10. Assign the interface name for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw interface ge-3/1/2.0
```

11. Configure the route distinguisher for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw route-distinguisher 10.10.10.10:15
```

12. Configure the Layer 2 VPN ID community for FEC 129 MS-PW.

```
[edit routing-instances]
user@T-PE1# set ms-pw l2vpn-id l2vpn-id:100:15
```

13. Configure a VPN routing and forwarding (VRF) target for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw vrf-target target:100:115
```

14. Configure the source attachment identifier (SAI) value using Layer 2 VPN as the routing protocol for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn site CE1 source-attachment-identifier 800:800:800
```

15. Assign the interface name that connects the CE1 site to the VPN, and configure the target attachment identifier (TAI) value using Layer 2 VPN as the routing protocol for the mspw routing instance.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn site CE1 interface ge-3/1/2.0 target-attachment-
identifier 700:700:700
```

16. (Optional) Configure T-PE1 to send MS-PW status TLVs.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn pseudowire-status-tlv
```

17. (Optional) Configure OAM capabilities for the VPN.

```
[edit routing-instances]
user@T-PE1# set ms-pw protocols l2vpn oam bfd-liveness-detection minimum-interval 300
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure S-PE1 (ASBR 1) in the inter-AS scenario:

NOTE: Repeat this procedure for the S-PE2 (ASBR 2) device in the MPLS domain, after modifying the appropriate interface names, addresses, and other parameters.

1. Configure S-PE1 (ASBR 1) interfaces.

```
[edit interfaces]
user@S-PE1# set ge-1/3/1 unit 0 family inet address 192.0.2.9/24
user@S-PE1# set ge-1/3/1 unit 0 family mpls
user@S-PE1# set ge-1/3/2 unit 0 family inet address 192.0.2.22/24
user@S-PE1# set ge-1/3/2 unit 0 family mpls
user@S-PE1# set lo0 unit 0 family inet address 10.255.2.1/32 primary
```

2. Set the autonomous system number.

```
[edit routing-options]
user@S-PE1# set autonomous-system 1
```

3. Enable MPLS on all the interfaces of S-PE1 (ASBR 1), excluding the management interface.

```
[edit protocols]
user@S-PE1# set mpls interface all
user@S-PE1# set mpls interface fxp0.0 disable
```

4. Enable autodiscovery of S-PE using BGP.

```
[edit protocols]
user@S-PE1# set bgp family l2vpn auto-discovery-mspw
```

5. Configure the IBGP group for S-PE1 (ASBR 1) to peer with T-PE1.

```
[edit protocols]
user@S-PE1# set bgp group to_T-PE1 type internal
```

6. Configure the IBGP group parameters.

```
[edit protocols]
user@S-PE1# set bgp group to_T-PE1 local-address 10.255.2.1
user@S-PE1# set bgp group to_T-PE1 export next-hop-self
user@S-PE1# set bgp group to_T-PE1 neighbor 10.255.10.1
```

7. Configure the EBGP group for S-PE1 (ASBR 1) to peer with S-PE2 (ASBR 2).

```
[edit protocols]
user@S-PE1# set bgp group to_S-PE2 type external
```

8. Configure the EBGP group parameters.

```
[edit protocols]
user@S-PE1# set bgp group to_S-PE2 local-address 10.255.2.1
user@S-PE1# set bgp group to_S-PE2 peer-as 2
user@S-PE1# set bgp group to_S-PE2 neighbor 10.255.3.1 multihop ttl 1
```

9. Configure OSPF on all the interfaces of S-PE1 (ASBR 1), excluding the management interface.

```
[edit protocols]
user@S-PE1# set ospf area 0.0.0.0 interface all
user@S-PE1# set ospf area 0.0.0.0 interface fxp0.0 disable
user@S-PE1# set ospf area 0.0.0.0 interface lo0.0 passive
```

10. Configure LDP on all the interfaces of S-PE1 (ASBR 1), excluding the management interface.

```
[edit protocols]
user@S-PE1# set ldp interface all
user@S-PE1# set ldp interface fxp0.0 disable
user@S-PE1# set ldp interface lo0.0
```

11. Define the policy for enabling next-hop-self on S-PE1 (ASBR 1).

```
[edit policy-options]
user@S-PE1# set policy-statement next-hop-self then next-hop self
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, `show routing-options`, and `show policy-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

T-PE1

```
user@T-PE1# show interfaces
ge-3/1/0 {
  unit 0 {
    family inet {
      address 192.0.2.1/24;
    }
    family mpls;
  }
}
ge-3/1/2 {
  encapsulation ethernet-ccc;
  unit 0;
}
lo0 {
  unit 0 {
    family inet {
      address 10.255.10.1/32 {
        primary;
      }
    }
  }
}
```

```

    }
}

```

```

user@T-PE1# show routing-options
autonomous-system 1;

```

```

user@T-PE1# show protocols
mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    family l2vpn {
        auto-discovery-mspw;
    }
    group mspw {
        type internal;
        local-address 10.255.10.1;
        neighbor 10.255.2.1;
    }
}
ospf {
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
        interface lo0.0;
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

```

```

    interface lo0.0;
}

```

```

user@T-PE1# show routing-instances
ms-pw {
    instance-type l2vpn;
    interface ge-3/1/2.0;
    route-distinguisher 10.10.10.10:15;
    l2vpn-id l2vpn-id:100:15;
    vrf-target target:100:115;
    protocols {
        l2vpn {
            site CE1 {
                source-attachment-identifier 800:800:800;
                interface ge-3/1/2.0 {
                    target-attachment-identifier 700:700:700;
                }
            }
        }
        pseudowire-status-tlv;
        oam {
            bfd-liveness-detection {
                minimum-interval 300;
            }
        }
    }
}

```

S-PE1 (RR 1)

```

user@S-PE1# show interfaces
ge-1/3/1 {
    unit 0 {
        family inet {
            address 192.0.2.9/24;
        }
        family mpls;
    }
}
ge-1/3/2 {
    unit 0 {

```

```

        family inet {
            address 192.0.2.22/24;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.255.2.1/32 {
                primary;
            }
        }
    }
}
}

```

```

user@T-PE1# show routing-options
autonomous-system 1;

```

```

user@S-PE1# show protocols
mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    family l2vpn {
        auto-discovery-mspw;
    }
    group to_T-PE1 {
        type internal;
        local-address 10.255.2.1;
        export next-hop-self;
        neighbor 10.255.10.1;
    }
    group to_S-PE2 {
        type external;
        local-address 10.255.2.1;
        peer-as 2;
    }
}

```



```

        neighbor 10.255.3.1 {
            multihop {
                ttl 1;
            }
        }
    }
}

ospf {
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}

```

```

user@T-PE1# show policy-options
policy-statement next-hop-self {
    then {
        next-hop self;
    }
}

```

If you are done configuring the device, enter **commit** from configuration mode.

Verification

IN THIS SECTION

- Verifying the Routes | 591
- Verifying the LDP Database | 594
- Checking the MS-PW Connections on T-PE1 | 595
- Checking the MS-PW Connections on S-PE1 | 597
- Checking the MS-PW Connections on S-PE2 | 599
- Checking the MS-PW Connections on T-PE2 | 600

Confirm that the configuration is working properly.

Verifying the Routes

Purpose

Verify that the expected routes are learned.

Action

From operational mode, run the `show route` command for the `bgp.l2vpn.1`, `ldp.l2vpn.1`, `mpls.0`, and `ms-pw.l2vpn.1` routing tables.

From operational mode, run the `show route table bgp.l2vpn.1` command.

```
user@T-PE1> show route table bgp.l2vpn.1
bgp.l2vpn.1: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.10:15:700:0.0.2.188:700/160 AD2
      *[BGP/170] 16:13:11, localpref 100, from 10.255.2.1
      AS path: 2 I, validation-state: unverified
      > to 203.0.113.2 via ge-3/1/0.0, Push 300016
```

From operational mode, run the `show route table ldp.l2vpn.1` command.

```
user@T-PE1> show route table ldp.l2vpn.1
ldp.l2vpn.1: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.255.2.1:CtrlWord:5:100:15:700:0.0.2.188:700:800:0.0.3.32:800/304 PW2
      *[LDP/9] 16:21:27
      Discard
```

From operational mode, run the `show route table mpls.0` command.

```
user@T-PE1> show route table mpls.0
mpls.0: 12 destinations, 12 routes (12 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w6d 00:28:26, metric 1
           Receive
1          *[MPLS/0] 1w6d 00:28:26, metric 1
           Receive
2          *[MPLS/0] 1w6d 00:28:26, metric 1
           Receive
13         *[MPLS/0] 1w6d 00:28:26, metric 1
           Receive
299920     *[LDP/9] 1w5d 01:26:08, metric 1
           > to 203.0.113.2 via ge-3/1/0.0, Pop
299920(S=0) *[LDP/9] 1w5d 01:26:08, metric 1
           > to 203.0.113.2 via ge-3/1/0.0, Pop
299936     *[LDP/9] 1w5d 01:26:08, metric 1
           > to 203.0.113.2 via ge-3/1/0.0, Swap 300016
300096     *[LDP/9] 16:22:35, metric 1
           > to 203.0.113.2 via ge-3/1/0.0, Swap 300128
300112     *[LDP/9] 16:22:35, metric 1
           > to 203.0.113.2 via ge-3/1/0.0, Swap 300144
300128     *[LDP/9] 16:22:35, metric 1
           > to 203.0.113.2 via ge-3/1/0.0, Swap 300160
300144     *[L2VPN/7] 16:22:33
           > via ge-3/1/2.0, Pop          Offset: 4
ge-3/1/2.0 *[L2VPN/7] 16:22:33, metric2 1
           > to 203.0.113.2 via ge-3/1/0.0, Push 300176, Push 300016(top) Offset: 252
```

From operational mode, run the `show route table ms-pw.l2vpn.1` command.

```
user@T-PE1> show route table ms-pw.l2vpn.1
ms-pw.l2vpn.1: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.10.10.10:15:700:0.0.2.188:700/160 AD2
    *[BGP/170] 16:23:27, localpref 100, from 10.255.2.1
    AS path: 2 I, validation-state: unverified
    > to 203.0.113.2 via ge-3/1/0.0, Push 300016
10.10.10.10:15:800:0.0.3.32:800/160 AD2
    *[L2VPN/170] 1w5d 23:25:19, metric2 1
    Indirect
10.255.2.1:CtrlWord:5:100:15:700:0.0.2.188:700:800:0.0.3.32:800/304 PW2
    *[LDP/9] 16:23:25
    Discard
10.255.2.1:CtrlWord:5:100:15:800:0.0.3.32:800:700:0.0.2.188:700/304 PW2
    *[L2VPN/7] 16:23:27, metric2 1
    > to 203.0.113.2 via ge-3/1/0.0, Push 300016
```

Meaning

The output shows all the learned routes, including the autodiscovery (AD) routes.

The AD2 prefix format is RD:SAII-type2, where:

- RD is the route distinguisher value.
- SAII-type2 is the type 2 source attachment identifier value.

The PW2 prefix format is Neighbor_Addr:C:PWtype:l2vpn-id:SAII-type2:TAII-type2, where:

- Neighbor_Addr is the loopback address of neighboring S-PE device.
- C indicates if Control Word (CW) is enabled or not.
 - C is CtrlWord if CW is set.
 - C is NoCtrlWord if CW is not set.
- PWtype indicates the type of the pseudowire.
 - PWtype is 4 if it is in Ethernet tagged mode.
 - PWtype is 5 if it is Ethernet only.

- l2vpn-id is the Layer 2 VPN ID for the MS-PW routing instance.
- SAII-type2 is the type 2 source attachment identifier value.
- TAII-type2 is the type 2 target attachment identifier value.

Verifying the LDP Database

Purpose

Verify the MS-PW labels received by T-PE1 from S-PE1 and sent from T-PE1 to S-PE1.

Action

From operational mode, run the `show ldp database` command.

```
user@T-PE1> show ldp database
Input label database, 10.255.10.1:0--10.255.2.1:0
  Label    Prefix
    3      10.255.2.1/32
  300112    10.255.3.1/32
  300128    10.255.4.1/32
  299968    10.255.10.1/32
  299904    10.255.13.1/32
  300144    10.255.14.1/32
  300176    FEC129 CtrlWord ETHERNET 000a0064:0000000f 000002bc:000002bc:000002bc
00000320:00000320:00000320

Output label database, 10.255.10.1:0--10.255.2.1:0
  Label    Prefix
  299936    10.255.2.1/32
  300096    10.255.3.1/32
  300112    10.255.4.1/32
    3      10.255.10.1/32
  299920    10.255.13.1/32
  300128    10.255.14.1/32
  300144    FEC129 CtrlWord ETHERNET 000a0064:0000000f 00000320:00000320:00000320
000002bc:000002bc:000002bc

Input label database, 10.255.10.1:0--10.255.13.1:0
  Label    Prefix
  300016    10.255.2.1/32
```

```

300128      10.255.3.1/32
300144      10.255.4.1/32
300080      10.255.10.1/32
      3      10.255.13.1/32
300160      10.255.14.1/32

```

Output label database, 10.255.10.1:0--10.255.13.1:0

```

Label      Prefix
299936     10.255.2.1/32
300096     10.255.3.1/32
300112     10.255.4.1/32
      3     10.255.10.1/32
299920     10.255.13.1/32
300128     10.255.14.1/32

```

Meaning

The labels with FEC129 prefix are related to the MS-PW.

Checking the MS-PW Connections on T-PE1

Purpose

Make sure that all of the FEC 129 MS-PW connections come up correctly.

Action

From operational mode, run the `show l2vpn connections extensive` command.

```
user@T-PE1> show l2vpn connections extensive
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure

```

RD -- remote site signaled down  SC -- local and remote site ID collision
LN -- local site not designated  LM -- local site ID not minimum designated
RN -- remote site not designated  RM -- remote site ID not minimum designated
XX -- unknown connection status  IL -- no incoming label
MM -- MTU mismatch                MI -- Mesh-Group ID not available
BK -- Backup connection           ST -- Standby connection
PF -- Profile parse failure        PB -- Profile busy
RS -- remote site standby         SN -- Static Neighbor
LB -- Local site not best-site    RB -- Remote site not best-site
VM -- VLAN ID mismatch

```

Legend for interface status

Up -- operational

Dn -- down

Instance: ms-pw

L2vpn-id: 100:15

Number of local interfaces: 1

Number of local interfaces up: 1

ge-3/1/2.0

Local source-attachment-id: 800:0.0.3.32:800 (CE1)

Target-attachment-id	Type	St	Time last up	# Up trans
700:0.0.2.188:700	rmt	Up	Sep 18 01:10:55 2013	1

Remote PE: 10.255.2.1, Negotiated control-word: Yes (Null)

Incoming label: 300048, Outgoing label: 300016

Negotiated PW status TLV: Yes

local PW status code: 0x00000000, Neighbor PW status code: 0x00000000

Local interface: ge-3/1/2.0, Status: Up, Encapsulation: ETHERNET

Pseudowire Switching Points :

Local address	Remote address	Status
10.255.2.1	10.255.3.1	forwarding
10.255.3.1	10.255.14.1	forwarding

Connection History:

Sep 18 01:10:55 2013	status update timer	
Sep 18 01:10:55 2013	PE route changed	
Sep 18 01:10:55 2013	Out lbl Update	300016
Sep 18 01:10:55 2013	In lbl Update	300048
Sep 18 01:10:55 2013	loc intf up	ge-3/1/2.0

Check the following fields in the output to verify that MS-PW is established between the T-PE devices:

- **Target-attachment-id**—Check if the TAI value is the SAI value of T-PE2.

- **Remote PE**—Check if the T-PE2 loopback address is listed.
- **Negotiated PW status TLV**—Ensure that the value is Yes.
- **Pseudowire Switching Points**—Check if the switching points are listed from S-PE1 to S-PE2 and from S-PE2 to T-PE2.

Meaning

MS-PW is established between T-PE1 and T-PE2 in the forwarding direction.

Checking the MS-PW Connections on S-PE1

Purpose

Make sure that all of the FEC 129 MS-PW connections come up correctly for the mspw routing instance.

Action

From operational mode, run the `show l2vpn connections instance __MSPW__ extensive` command.

```
user@S-PE1> show l2vpn connections instance __MSPW__ extensive
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned    <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure      PB -- Profile busy
RS -- remote site standby        SN -- Static Neighbor
```



```

LB -- Local site not best-site   RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status
Up -- operational
Dn -- down

Instance: __MSPW__
L2vpn-id: 100:15
Local source-attachment-id: 700:0.0.2.188:700
  Target-attachment-id   Type  St    Time last up        # Up trans
  800:0.0.3.32:800       rmt   Up    Sep 18 01:17:38 2013      1
  Remote PE: 10.255.10.1, Negotiated control-word: Yes (Null), Encapsulation: ETHERNET
  Incoming label: 300016, Outgoing label: 300048
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
Local source-attachment-id: 800:0.0.3.32:800
  Target-attachment-id   Type  St    Time last up        # Up trans
  700:0.0.2.188:700       rmt   Up    Sep 18 01:17:38 2013      1
  Remote PE: 10.255.3.1, Negotiated control-word: Yes (Null), Encapsulation: ETHERNET
  Incoming label: 300000, Outgoing label: 300064
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
Pseudowire Switching Points :
  Local address          Remote address         Status
  10.255.3.1             10.255.14.1           forwarding

```

Check the following fields in the output to verify that MS-PW is established between the T-PE devices:

- **Target-attachment-id**—Check if the TAI value is the SAI value of T-PE2.
- **Remote PE**—Check if the T-PE1 and S-PE2 loopback addresses are listed.
- **Negotiated PW status TLV**—Ensure that the value is Yes.
- **Pseudowire Switching Points**—Check if the switching points are listed from S-PE2 to T-PE2.

Meaning

MS-PW is established between T-PE1 and T-PE2 in the forwarding direction.

Checking the MS-PW Connections on S-PE2

Purpose

Make sure that all of the FEC 129 MS-PW connections come up correctly for the mspw routing instance.

Action

From operational mode, run the `show l2vpn connections instance __MSPW__ extensive` command.

```
user@S-PE2> show l2vpn connections instance __MSPW__ extensive
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned    <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status
Up -- operational
Dn -- down

Instance: __MSPW__
L2vpn-id: 100:15
Local source-attachment-id: 700:0.0.2.188:700
Target-attachment-id   Type  St   Time last up      # Up trans
```

```

800:0.0.3.32:800      rmt  Up    Sep 18 00:58:55 2013      1
  Remote PE: 10.255.2.1, Negotiated control-word: Yes (Null), Encapsulation: ETHERNET
  Incoming label: 300064, Outgoing label: 300000
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
  Pseudowire Switching Points :
    Local address      Remote address      Status
    10.255.2.1         10.255.10.1         forwarding
Local source-attachment-id: 800:0.0.3.32:800
Target-attachment-id   Type  St    Time last up          # Up trans
700:0.0.2.188:700     rmt   Up    Sep 18 00:58:55 2013      1
  Remote PE: 10.255.14.1, Negotiated control-word: Yes (Null), Encapsulation: ETHERNET
  Incoming label: 300048, Outgoing label: 300112
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000

```

Check the following fields in the output to verify that MS-PW is established between the T-PE devices:

- **Target-attachment-id**—Check if the TAI value is the SAI value of T-PE1.
- **Remote PE**—Check if the S-PE1 and T-PE2 loopback addresses are listed.
- **Negotiated PW status TLV**—Ensure that the value is Yes.
- **Pseudowire Switching Points**—Check if the switching points are listed from S-PE1 to T-PE1.

Meaning

MS-PW is established between T-PE1 and T-PE2 in the reverse direction.

Checking the MS-PW Connections on T-PE2

Purpose

Make sure that all of the FEC 129 MS-PW connections come up correctly.

Action

From operational mode, run the `show l2vpn connections extensive` command.

```

user@T-PE2> show l2vpn connections extensive
Layer-2 VPN connections:

```

Legend for connection status (St)

EI -- encapsulation invalid NC -- interface encapsulation not CCC/TCC/VPLS
 EM -- encapsulation mismatch WE -- interface and instance encaps not same
 VC-Dn -- Virtual circuit down NP -- interface hardware not present
 CM -- control-word mismatch -> -- only outbound connection is up
 CN -- circuit not provisioned <- -- only inbound connection is up
 OR -- out of range Up -- operational
 OL -- no outgoing label Dn -- down
 LD -- local site signaled down CF -- call admission control failure
 RD -- remote site signaled down SC -- local and remote site ID collision
 LN -- local site not designated LM -- local site ID not minimum designated
 RN -- remote site not designated RM -- remote site ID not minimum designated
 XX -- unknown connection status IL -- no incoming label
 MM -- MTU mismatch MI -- Mesh-Group ID not available
 BK -- Backup connection ST -- Standby connection
 PF -- Profile parse failure PB -- Profile busy
 RS -- remote site standby SN -- Static Neighbor
 LB -- Local site not best-site RB -- Remote site not best-site
 VM -- VLAN ID mismatch

Legend for interface status

Up -- operational
 Dn -- down

Instance: ms-pw

L2vpn-id: 100:15

Number of local interfaces: 1

Number of local interfaces up: 1

ge-2/0/0.0

Local source-attachment-id: 700:0.0.2.188:700 (CE2)

Target-attachment-id	Type	St	Time last up	# Up trans
800:0.0.3.32:800	rmt	Up	Sep 18 01:35:21 2013	1

Remote PE: 10.255.3.1, Negotiated control-word: Yes (Null)

Incoming label: 300112, Outgoing label: 300048

Negotiated PW status TLV: Yes

local PW status code: 0x00000000, Neighbor PW status code: 0x00000000

Local interface: ge-2/0/0.0, Status: Up, Encapsulation: ETHERNET

Pseudowire Switching Points :

Local address	Remote address	Status
10.255.3.1	10.255.2.1	forwarding
10.255.2.1	10.255.10.1	forwarding

Connection History:

Sep 18 01:35:21 2013 status update timer

```

Sep 18 01:35:21 2013 PE route changed
Sep 18 01:35:21 2013 Out lbl Update          300048
Sep 18 01:35:21 2013 In lbl Update          300112
Sep 18 01:35:21 2013 loc intf up           ge-2/0/0.0

```

Check the following fields in the output to verify that MS-PW is established between the T-PE devices:

- **Target-attachment-id**—Check if the TAI value is the SAI value of T-PE1.
- **Remote PE**—Check if the T-PE1 loopback address is listed.
- **Negotiated PW status TLV**—Ensure that the value is Yes.
- **Pseudowire Switching Points**—Check if the switching points are listed from S-PE2 to S-PE1 and from S-PE1 to T-PE1.

Meaning

MS-PW is established between T-PE1 and T-PE2 in the reverse direction.

Troubleshooting

IN THIS SECTION

- [Ping | 602](#)
- [Bidirectional Forwarding Detection | 603](#)
- [Traceroute | 604](#)

To troubleshoot the MS-PW connection, see:

Ping

Problem

How to check the connectivity between the T-PE devices and between a T-PE device and an intermediary device.

Solution

Verify that T-PE1 can ping T-PE2. The `ping mpls l2vpn fec129` command accepts SAs and TAs as integers or IP addresses and also allows you to use the CE-facing interface instead of the other parameters (instance, local-id, remote-id, remote-pe-address).

Checking Connectivity Between T-PE1 and T-PE2

```
user@T-PE1> ping mpls l2vpn fec129 instance FEC129-VPWS local-id 800:800:800 remote-pe-address
10.255.14.1 remote-id 700:700:700
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
user@T-PE1> ping mpls l2vpn fec129 interface ge-3/1/2
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Checking Connectivity Between T-PE1 and S-PE2

```
user@T-PE1> ping mpls l2vpn fec129 interface ge-3/1/2 bottom-label-ttl 2
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Bidirectional Forwarding Detection

Problem

How to use BFD to troubleshoot the MS-PW connection from the T-PE device.

Solution

From operational mode, verify the `show bfd session extensive` command output.

```
user@T-PE1> show bfd session extensive
```

Address	State	Interface	Detect Time	Transmit Interval	Multiplier
198.51.100.7	Up	ge-3/1/0.0	0.900	0.300	3

```

Client FEC129-OAM, TX interval 0.300, RX interval 0.300
Session up time 03:12:42
Local diagnostic None, remote diagnostic None
Remote state Up, version 1
Replicated
Session type: VCCV BFD
Min async interval 0.300, min slow interval 1.000
Adaptive async TX interval 0.300, RX interval 0.300
Local min TX interval 0.300, minimum RX interval 0.300, multiplier 3
Remote min TX interval 0.300, min RX interval 0.300, multiplier 3
Local discriminator 19, remote discriminator 19
Echo mode disabled/inactive
Remote is control-plane independent
L2vpn-id 100:15, Local-id 800:0.0.3.32:800, Remote-id 700:0.0.2.188:700
Session ID: 0x103

1 sessions, 1 clients
Cumulative transmit rate 3.3 pps, cumulative receive rate 3.3 pps

```

Traceroute

Problem

How to verify that MS-PW was established.

Solution

From operational mode, verify traceroute output.

```

user@T-PE1> traceroute mpls l2vpn fec129 interface interface
Probe options: ttl 64, retries 3, exp 7

```

ttl	Label	Protocol	Address	Previous Hop	Probe Status
1		FEC129	10.255.10.1	(null)	Success
2		FEC129	10.255.2.1	10.255.10.1	Success
3		FEC129	10.255.3.1	10.255.2.1	Success
4		FEC129	10.255.14.1	10.255.2.1	Egress

Path 1 via ge-3/1/2 destination 198.51.100.0

Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic

This topic shows how to configure flow-aware transport of pseudowires (FAT) flow labels for forwarding equivalence class (FEC) 128 virtual private wire service (VPWS) pseudowires for load-balancing MPLS traffic.

Before you begin:

1. Configure the device interfaces and enable MPLS on all the interfaces.
2. Configure MPLS and an LSP to the remote PE router.
3. Configure OSPF and IS-IS.
4. Configure LDP on the loopback interface and the PE interface connecting to the P (transit) router.

FAT flow labels enable load-balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. FAT flow labels can be used for LDP-signaled FEC 128 and FEC 129 pseudowires for virtual private LAN service (VPLS) and VPWS networks.

You can configure FAT flow labels to be signaled by LDP on FEC 128 VPWS pseudowires by including the `flow-label-transmit` and `flow-label-receive` configuration statements at the `[edit protocols l2circuit neighbor neighbor-id interface interface-name]` hierarchy level. This configuration sets the T bit and R bit advertisement to 1 (the default being 0) in the Sub-TLV field, which is one of the interface parameters of the FEC for the LDP label-mapping message header. These statements signal the pushing and popping of the load-balancing label to the routing peers in the control plane.

Alternatively, you can configure the following statements at the `[edit protocols l2circuit neighbor neighbor-id interface interface-name]` hierarchy level:

- `flow-label-transmit-static` to statically push the flow label on the pseudowire packets sent to the remote provider edge (PE) router.
- `flow-label-receive-static` to statically pop the flow label on the pseudowire packets received from the remote PE router.

To configure the FAT flow label for an FEC 128-signaled VPLS pseudowire, on the ingress PE router:

1. Configure the neighbors for the Layer 2 circuit.

```
[edit protocols l2circuit]
user@PE1# set neighbor neighbor-id
```

All the Layer 2 circuits using a particular remote PE router designated for remote CE routers are listed under the `neighbor` statement. Each neighbor is identified by its IP address and is usually the end-point destination for the label-switched path (LSP) tunnel transporting the Layer 2 circuit.

2. Configure the interface for the Layer 2 circuit neighbor and a unique identifier for the Layer 2 circuit.

```
[edit protocols l2circuit neighbor neighbor-id]
user@PE1# set interface interface-name virtual-circuit-id unique-l2ckt-identifier
```

- 3.

NOTE: You can only configure one of the following pairs of statements:

- `flow-label-transmit` and `flow-label-receive` **or**,
- `flow-label-transmit-static` and `flow-label-receive-static`

Configure the router to signal the capability to push the flow label in the transmit direction to the remote PE router.

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name]
user@PE1# set flow-label-transmit
```

4. Alternatively, configure the `flow-label-transmit-static` statement to statically push the flow label on the pseudowire packets sent to the remote PE router.

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name]
user@PE1# set flow-label-transmit-static
```

If the incoming pseudowire packet is not marked with the flow label, the packet is dropped by the egress PE router.

5. Configure the router to signal the capability to pop the flow label in the receive direction to the remote egress PE router.

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name]
user@PE1# set flow-label-receive
```

6. Alternatively, configure the `flow-label-receive-static` statement to pop the flow label on the pseudowire packets received from the remote PE router.

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name]
user@PE1# set flow-label-receive-static
```

The ingress PE router inserts the flow label in the pseudowire packet, irrespective of the information exchanged in the signaling plane. If the egress PE router cannot handle the pseudowire packet marked with the flow label, the packet is dropped.

7. Verify and commit the configuration.

For example:

```
[edit protocols l2circuit]
user@PE1# show
neighbor 10.255.104.135 {
  interface ge-1/0/8.0 {
    virtual-circuit-id 1;
    flow-label-transmit;
    flow-label-receive;
  }
}
```

OR:

```
[edit protocols l2circuit]
user@PE1# show
neighbor 10.255.104.135 {
  interface ge-1/0/8.0 {
    virtual-circuit-id 1;
    flow-label-transmit-static;
    flow-label-receive-static;
  }
}
```

8. Repeat the configuration on the remote egress PE router.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)

[Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

[Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)

[FAT Flow Labels Overview | 503](#)

Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic

This topic shows how to configure flow-aware transport of pseudowires (FAT) flow labels for forwarding equivalence class (FEC) 129 virtual private wire service (VPWS) pseudowires.

Before you begin:

1. Configure the device interfaces and enable MPLS on all core-facing interfaces.
2. Configure CCC encapsulation and the CCC address family for interfaces configured as members of the FEC 129 VPWS instance.
3. Configure MPLS and an LSP to the remote provider edge (PE) router.
4. Configure the BGP sessions on the PE devices with the BGP autodiscovery-only address family to allow exchange of the autodiscovery routes.
5. Configure an IGP such as IS-IS or OSPF.
6. Configure LDP on the loopback interface and the core-facing interface.
7. Configure the autonomous system (AS) number.

FAT flow labels enable load-balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. FAT flow labels can be used for LDP-signaled FEC 128 and FEC 129 pseudowires for virtual private LAN service (VPLS) and VPWS networks.

You can configure FAT flow labels to be signaled by LDP on FEC 129 VPWS pseudowires (Layer 2 circuits) by including the `flow-label-transmit` and `flow-label-receive` configuration statements at the `[edit routing-instances instance-name protocols l2vpn site name]` or the `[edit routing-instances instance-name protocols l2vpn site name interface interface-name]` hierarchy level. This configuration sets the T bit and R bit advertisement to 1 (the default being 0) in the Sub-TLV field, which is one of the interface parameters of the FEC for the LDP label-mapping message header. These statements signal the pushing and popping of the load-balancing label to the routing peers in the control plane.

To configure the FAT flow label for an FEC 129 VPWS pseudowire, on the ingress PE router:

1. Configure the VPWS routing instance.

LDP listens for routes from `instance.l2vpn.0` for any instance configured for FEC 129 VPWS. These routes are identified by the `instance-type l2vpn` statement in the routing instance and the presence of the `l2vpn-id` statement.

```
[edit ]
user@PE1# set routing-instances instance-name instance-type l2vpn
user@PE1# set routing-instances instance-name interface interface-name
user@PE1# set routing-instances instance-name route-distinguisher (as-number:x:y | ip-address:id)
user@PE1# set routing-instances instance-name l2vpn-id (as-number:x:y | ip-address:id)
user@PE1# set routing-instances instance-name vrf-target community
user@PE1# set routing-instances instance-name protocols l2vpn site site-name source-attachment-identifier identifier
user@PE1# set routing-instances instance-name protocols l2vpn site site-name interface interface-name target-attachment-identifier identifier
```

Because VPWS is a point-to-point service, FEC 129 VPWS routing instances are configured as `instance-type l2vpn`. As with FEC 129 VPLS, FEC 129 VPWS uses the `l2vpn-id` statement to define the Layer 2 VPN of which the routing instance is a member. The presence of the `l2vpn-id` statement designates that FEC 129 LDP-signaling is used for the routing instance.

2. Configure the device to signal the capability to push the flow label in the transmit direction to the remote PE router.

```
[edit routing-instances instance-name protocols l2vpn site name interface interface-name]
user@PE1# set flow-label-transmit
```

3. Configure the device to signal the capability to pop the flow label in the receive direction to the remote PE router.

```
[edit routing-instances instance-name protocols l2vpn site name interface interface-name]
user@PE1# set flow-label-receive
```

4. Alternatively, configure the flow-label-transmit and flow-label-receive statements directly within the site. When configured within the site, the defined parameters affect any pseudowire originating from that site. When configured under an interface within the site, the defined parameters affect that single specific pseudowire. This enables you to manipulate the parameters across all pseudowires associated with a particular local site in one place in the configuration.

```
[edit routing-instances instance-name protocols l2vpn site name ]
user@PE1# set flow-label-receive
user@PE1# set flow-label-transmit
```

5. Verify and commit the configuration.

For example:

```
[edit routing-instances FEC129-VPWS]
user@PE1# show
instance-type l2vpn;
interface ge-0/0/1.600;
route-distinguisher 10.255.255.1:100;
l2vpn-id l2vpn-id:100:100;
vrf-target target:100:100;
protocols {

    l2vpn {
        site ONE {
            source-attachment-identifier 1;
            interface ge-0/0/1.600 {
                target-attachment-identifier 2;
                flow-label-transmit; <<< Applicable only to the pseudowire specific to the
interface >>>
                flow-label-receive;
            }
        }
        site TWO {
            source-attachment-identifier 3;
            flow-label-transmit; <<< Applicable to all pseudowires within the site >>>

```

```
        flow-label-receive;
        interface ge-0/0/2.600 {
            target-attachment-identifier 1;
        }
        interface ge-0/0/2.601 {
            target-attachment-identifier 4;
        }
    }
}
```

6. Repeat the configuration on the remote egress PE router.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

[Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)

[Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)

[FAT Flow Labels Overview | 503](#)

7

PART

Configuring VPLS

[Overview | 613](#)

[VPLS Configuration Overview | 616](#)

[Configuring Signaling Protocols for VPLS | 619](#)

[Assigning Routing Instances to VPLS | 674](#)

[Associating Interfaces with VPLS | 733](#)

[Configuring Pseudowires | 751](#)

[Configuring Multihoming | 881](#)

[Configuring Point-to-Multipoint LSPs | 1024](#)

[Configuring Inter-AS VPLS and IRB VPLS | 1098](#)

[Configuring Load Balancing and Performance | 1140](#)

[Configuring Class of Service and Firewall Filters in VPLS | 1232](#)

[Monitoring and Tracing VPLS | 1259](#)

Overview

IN THIS CHAPTER

- Introduction to VPLS | 613
- Supported VPLS Standards | 614
- Supported Platforms and PICs | 614

Introduction to VPLS

VPLS is an Ethernet-based point-to-multipoint Layer 2 VPN. It allows you to connect geographically dispersed Ethernet local area networks (LAN) sites to each other across an MPLS backbone. For customers who implement VPLS, all sites appear to be in the same Ethernet LAN even though traffic travels across the service provider's network.

VPLS, in its implementation and configuration, has much in common with a Layer 2 VPN. In VPLS, a packet originating within a service provider customer's network is sent first to a customer edge (CE) device (for example, a router or Ethernet switch). It is then sent to a provider edge (PE) router within the service provider's network. The packet traverses the service provider's network over a MPLS label-switched path (LSP). It arrives at the egress PE router, which then forwards the traffic to the CE device at the destination customer site.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The difference is that for VPLS, packets can traverse the service provider's network in point-to-multipoint fashion, meaning that a packet originating from a CE device can be broadcast to all the PE routers participating in a VPLS routing instance. In contrast, a Layer 2 VPN forwards packets in point-to-point fashion only.

The paths carrying VPLS traffic between each PE router participating in a routing instance are called pseudowires. The pseudowires are signaled using either BGP or LDP.

Supported VPLS Standards

Junos OS substantially supports the following Internet RFCs and draft, which define standards for virtual private LAN service (VPLS).

- RFC 4761, *Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling*
- RFC 4762, *Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling*
FEC 128, FEC 129, control bit 0, the Ethernet pseudowire type 0x0005, and the Ethernet tagged mode pseudowire type 0x0004 are supported.
- RFC 6391, *Flow-Aware Transport of Pseudowires over an MPLS Packet Switched Network*
- RFC 6790, *The Use of Entropy Labels in MPLS Forwarding*
- Internet draft draft-kompella-l2vpn-vpls-multihoming, *Multi-homing in BGP-based Virtual Private LAN Service*

RELATED DOCUMENTATION

Supported Carrier-of-Carriers and Interprovider VPN Standards

[Supported VPWS Standards | 502](#)

[Supported Layer 2 VPN Standards | 145](#)

Supported Layer 3 VPN Standards

Supported Multicast VPN Standards

[Accessing Standards Documents on the Internet](#)

Supported Platforms and PICs

Virtual private LAN service (VPLS) is supported on all M Series routers except the M160.

VPLS is supported on all MX Series and T Series routers.

VPLS is supported on the following SRX Services Gateways for the branch:

- SRX100
- SRX210
- SRX240

- SRX650

VPLS is supported on the following PICs:

- All ATM2 IQ PICs
- 4-port Fast Ethernet PIC with 10/100 Base-TX interfaces PIC
- 1-port, 2-port, and 10-port Gigabit Ethernet PICs
- 1-port, 2-port, and 4-port Gigabit Ethernet PICs with SFP
- 1-port 10-Gigabit Ethernet PIC
- 1-port and 2-port Gigabit Ethernet Intelligent Queuing (IQ) PICs
- 4-port and 8-port Gigabit Ethernet IQ2 PICs with SFP
- 1-port 10-Gigabit Ethernet IQ2 PIC with XFP
- 4-port, quad-wide Gigabit Ethernet PIC
- 10-port 10-Gigabit OSE PIC

VPLS Configuration Overview

IN THIS CHAPTER

- Introduction to Configuring VPLS | 616
- Configuring an Ethernet Switch as the CE Device for VPLS | 618

Introduction to Configuring VPLS

Virtual private LAN service (VPLS) allows you to provide a point-to-multipoint LAN between a set of sites in a virtual private network (VPN).

To configure VPLS functionality, you must enable VPLS support on the provider edge (PE) router. You must also configure PE routers to distribute routing information to the other PE routers in the VPLS. In addition, you must also configure the circuits between the PE routers and the customer edge (CE) routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

You can support VPLS traffic by configuring a **vpls** routing instance on Junos OS or a **virtual-switch** routing instance on Junos Evolve OS. . The routing instance carries Ethernet traffic transparently across the service provider's network. As with other routing instances, all logical interfaces belonging to a VPLS routing instance are listed under that instance.

NOTE:

virtual-switch vlan-id noneservice-type single[edit routing-instances *routing-instance* protocol vpls]

In addition to VPLS routing instance configuration, you must configure MPLS label-switched paths (LSPs) between the PE routers, IBGP sessions between the PE routers, and an interior gateway protocol (IGP) on the PE and provider (P) routers.

Many configuration procedures for VPLS are identical to the procedures for Layer 2 VPNs and Layer 3 VPNs.

Understanding VPLS Interfaces

Interface names:

For each VPLS routing instance on a PE router, you specify which interfaces are to be used to carry VPLS traffic between the PE and CE devices.

Specify both the physical and logical portions of the interface name, in the following format: `physical.logical`. For example, in `ge-1/0/1.2`, `ge-1/0/1` is the physical portion of the interface name and `2` is the logical portion. If you do not specify the logical portion of the interface name, `0` is set by default.

A logical interface can be associated with only one routing instance.

Encapsulation Type:

The link-layer encapsulation type for a VPLS interface can be one of the following:

- **ethernet-vpls:** Use Ethernet VPLS encapsulation on Ethernet interfaces that have VPLS enabled and that must accept packets carrying standard Tag Protocol Identifier (TPID) values.

extended-vlan-vpls: Use extended virtual LAN (VLAN) VPLS encapsulation on Ethernet interfaces that have VLAN 802.1Q tagging and VPLS enabled and that must accept packets carrying TPIDs `0x8100`, `0x9100`, and `0x9901`. All VLAN IDs from 1 through 1023 are valid for VPLS VLANs on Fast Ethernet interfaces, and all VLAN IDs from 1 through 4094 are valid for VPLS VLANs on Gigabit Ethernet interfaces.

vlan-vpls: Use VLAN VPLS encapsulation on Ethernet interfaces with VLAN tagging and VPLS enabled. Interfaces with VLAN VPLS encapsulation accept packets carrying standard TPID values only. You must configure this encapsulation type on both the physical interface and the logical interface. VLAN IDs 1 through 511 are reserved for normal Ethernet VLANs, IDs 512 through 1023 are reserved for VPLS VLANs on Fast Ethernet interfaces, and IDs 512 through 4094 are reserved for VPLS VLANs on Gigabit Ethernet interfaces.
- **flexible-ethernet-services:** Use flexible Ethernet services encapsulation when you want to configure multiple per-unit Ethernet encapsulations. This encapsulation type allows you to configure any combination of route, TCC, CCC, and VPLS encapsulations on a single physical port. Aggregated Ethernet bundles cannot use this encapsulation type.

For flexible Ethernet services encapsulation, VLAN IDs from 1 through 511 are no longer reserved for normal VLANs.

Configuring VPLS on Junos OS Evolved

When you configure VPLS on switches running on Junos OS Evolved, like the ACX 7100 series switches, be aware of the following differences in configuration between switches running on Junos OS and switches running Junos OS Evolve.

Table 12: Differences between Junos OS and Junos OS Evolve

Junos OS	Junos OS Evolve
Supports vpls routing instance.	Supports virtual-switch routing instance. Supports one vlan per routing instance. When you configure a vlan with no vlan IDs or with the vlan-id none or vlan-id all option, you must also include the <code>service-type single</code> statement at the <code>[edit routing-instances routing-instance protocol vpls]</code> hierarchy.
Supports family vpls on interfaces.	Does not support family vpls on interfaces.

Configuring an Ethernet Switch as the CE Device for VPLS

For VPLS configurations, the CE device does not necessarily need to be a router. You can link the PE routers directly to Ethernet switches. However, there are a few configuration issues to be aware of:

- When you configure VPLS routing instances and establish two or more connections between a CE Ethernet switch and a PE router, you must enable the Spanning Tree Protocol (STP) on the switch to prevent loops.
- The Junos OS allows standard Bridge Protocol Data Unit (BPDU) frames to pass through emulated Layer 2 connections, such as those configured with Layer 2 VPNs, Layer 2 circuits, and VPLS instances. However, CE Ethernet switches that generate proprietary BPDU frames might not be able to run STP across Juniper Networks routing platforms configured for these emulated Layer 2 connections.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Configuring Signaling Protocols for VPLS

IN THIS CHAPTER

- VPLS Routing and Virtual Ports | 619
- BGP Signaling for VPLS PE Routers Overview | 621
- Control Word for BGP VPLS Overview | 622
- Configuring a Control Word for BGP VPLS | 623
- BGP Route Reflectors for VPLS | 625
- Interoperability Between BGP Signaling and LDP Signaling in VPLS | 626
- Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS | 629
- Example: VPLS Configuration (BGP Signaling) | 636
- Example: VPLS Configuration (BGP and LDP Interworking) | 653

VPLS Routing and Virtual Ports

Because VPLS carries Ethernet traffic across a service provider network, it must mimic an Ethernet network in some ways. When a PE router configured with a VPLS routing instance receives a packet from a CE device, it first determines whether it has the destination of the VPLS packet in the appropriate routing table. If it does, it forwards the packet to the appropriate PE router or CE device. If it does not, it broadcasts the packet to all other PE routers and CE devices that are members of that VPLS routing instance. In both cases, the CE device receiving the packet must be different from the one sending the packet.

NOTE: In the VPLS documentation, the term *router* is used to refer to any device that provides routing functions.


When a PE router receives a packet from another PE router, it first determines whether it has the destination of the VPLS packet in the appropriate routing table. If it does, the PE router either forwards the packet or drops it depending on whether the destination is a local or remote CE device:

- If the destination is a local CE device, the PE router forwards the packet to it.
- If the destination is a remote CE device (connected to another PE router), the PE router discards the packet.

If the PE router cannot determine the destination of the VPLS packet, it floods the packet to all attached CE devices.

This process is illustrated in [Figure 48 on page 620](#).

Figure 48: Flooding a Packet with an Unknown Destination to All PE Routers in the VPLS Instance



VPLS can be directly connected to an Ethernet switch. Layer 2 information gathered by an Ethernet switch (for example, media access control [MAC] addresses and interface ports) is included in the VPLS routing instance table. However, instead of all VPLS interfaces being physical switch ports, the router allows remote traffic for a VPLS instance to be delivered across an MPLS LSP and arrive on a virtual port. The virtual port emulates a local, physical port. Traffic can be learned, forwarded, or flooded to the virtual port in almost the same way as traffic is sent to a local port.

The VPLS routing table learns MAC address and interface information for both physical and virtual ports. The main difference between a physical port and a virtual port is that the router captures additional information from the virtual port, an outgoing MPLS label used to reach the remote site and an incoming MPLS label for VPLS traffic received from the remote site. The virtual port is generated dynamically on a Tunnel Services *Physical Interface Card* (PIC) when you configure VPLS on the router.

You can also configure VPLS without a Tunnel Services PIC. To do so, you use a label-switched interface (LSI) to provide VPLS functionality. An LSI MPLS label is used as the inner label for VPLS. This label maps to a VPLS routing instance. On the PE router, the LSI label is stripped and then mapped to a logical LSI interface. The Layer 2 Ethernet frame is then forwarded using the LSI interface to the correct VPLS routing instance.

One restriction on flooding behavior in VPLS is that traffic received from remote PE routers is never forwarded to other PE routers. This restriction helps prevent loops in the core network. However, if a CE Ethernet switch has two or more connections to the same PE router, you must enable the Spanning Tree Protocol (STP) on the CE switch to prevent loops. STP is supported on MX Series routers and EX Series switches only.

The Junos OS allows standard Bridge Protocol Data Unit (BPDU) frames to pass through emulated Layer 2 connections, such as those configured with Layer 2 VPNs, Layer 2 circuits, and VPLS routing instances. However, CE Ethernet switches that generate proprietary BPDU frames might not be able to run STP across Juniper Networks routing platforms configured for these emulated Layer 2 connections.

NOTE: Under certain circumstances, VPLS provider routers might duplicate an Internet Control Message Protocol (ICMP) reply from a CE router when a PE router has to flood an ICMP request because the destination MAC address has not yet been learned. The duplicate ICMP reply can be triggered when a CE router with promiscuous mode enabled is connected to a PE router. The PE router automatically floods the promiscuous mode-enabled CE router, which then returns the ICMP request to the VPLS provider routers. The VPLS provider routers consider the ICMP request to be new and flood the request again, creating a duplicate ping reply.

BGP Signaling for VPLS PE Routers Overview

BGP can autonomously signal pseudowires between the PE routers participating in the same virtual private LAN service (VPLS) network. As PE routers are added to and removed from the VPLS network, BGP can signal pseudowires to new PE routers and tear down old pseudowires to old PE routers. Each PE router only needs to be configured with the identity of the VPLS routing instance. Each PE router does not need to be configured with the identities of all of the PE routers that are or might become a part of the VPLS network.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

When you configure BGP for signaling in a VPLS network, customer sites can be either single-homed to a single PE router or multihomed to two or more PE routers. Multihoming provides redundancy for the connection between the customer site and the service provider's network.

You can either configure all of the PE routers in the VPLS network as a full mesh or you can use BGP route reflectors. For full mesh configurations, each PE router needs to be able to create a bidirectional pseudowire to each of the other PE routers participating in the VPLS network.

RELATED DOCUMENTATION

[VPLS Multihoming Overview | 881](#)

[VPLS Path Selection Process for PE Routers | 753](#)

Control Word for BGP VPLS Overview

In a BGP VPLS network, transit routers must determine the payload for hash calculations for load balancing. While parsing an MPLS encapsulated packet for hashing, a transit router can incorrectly calculate an Ethernet payload as an IPv4 or IPv6 payload if the first nibble of the destination address MAC is 0x4 or 0x6, respectively. This false positive can cause out-of-order packet delivery over a pseudowire. This issue can be avoided by configuring a BGP VPLS edge (VE) router to request that other BGP VE routers insert a control word between the label stack and the MPLS payload.

By inserting a control word between the label stack and the Layer 2 header of a packet traversing a VPLS, the first nibble of the destination address MAC can be ensured to be 0, thus preventing the packet from being identified as an IPv4 or IPv6 packet. All VE routers should want incoming packets to contain control words.

BGP is used to negotiate the support for control words between VE routers. You configure a VE router with the `control-word` parameter to indicate the preference to receive packets with the control word. By setting the control word, the VE router expects that all frames marked with a label from the VPLS contain the control word. When remote VE routers advertise their NLRI, if the control word is set on them as well, both ends of the pseudowire have control-word support and the control word is expected in packets arriving at the VE routers in both directions.

If a VE router doesn't have the control word set, a VE router that does have a control word set will act as if the VE router without the control word can neither send nor accept BGP VPLS packets with a control word included.

RELATED DOCUMENTATION

[Configuring a Control Word for BGP VPLS | 623](#)

[control-word | 1458](#)

Configuring a Control Word for BGP VPLS

In a BGP VPLS network, transit routers must determine the payload for hash calculations for load balancing. While parsing an MPLS encapsulated packet for hashing, a transit router can incorrectly calculate an Ethernet payload as an IPv4 or IPv6 payload if the first nibble of the destination address MAC is 0x4 or 0x6, respectively. This false positive can cause out-of-order packet delivery over a pseudowire. This issue can be avoided by configuring a BGP VPLS PE router to request that other BGP VPLS edge (VE) routers insert a control word between the label stack and the MPLS payload.



WARNING: If you attempt to set a control word in a VPLS network that contains a VE router that does not support a control word, the pseudowire will not come up. To ensure that the pseudowire comes up, be sure that all VE routers in the VPLS network support the presence of a control word.

Before configuring support for a control word in a BGP VPLS network, ensure that the router meets the following requirements:

- MX Series router running Junos OS Release 14.1 or later and containing one of the following Flexible PIC Concentrators: ADPC, NPC, or I-Chip

OR

- M320 router running Junos OS Release 14.1 or later and containing either the I-Chip or the Trio

To configure a VE router to expect a control word between the label stack and the MPLS payload:

1. At the [edit routing-instances] hierarchy level in configuration mode, set `control-word` for the VPLS protocol for the specified routing instance.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls control-word
```

For example:

```
[edit routing-instances]
user@host# set vpls1 protocols vpls control-word
```

2. If you are setting control-word on a Trio-based MPC on an MX Series router, set no-ether-pseudowire to omit the IP payload over the Ethernet pseudowire from the hash key.

```
[edit forwarding-options]
user@host# set enhanced-hash-key family mpls no-ether-pseudowire
```

3. Verify the configuration.

```
[edit routing-instances]
user@host# show
vpls1 {
  protocols {
    vpls {
      control-word;
    }
  }
}
```

```
[edit forwarding-options]
user@host# show
enhanced-hash-key {
  family mpls {
    no-ether-pseudowire;
  }
}
```

4. Repeat the configuration on each VE router in the BGP VPLS network.
5. Run `show vpls connections instance routing-instance-name extensive` to verify the presence of a control word for the pseudowire.

For example:

```
user@host# show vpls connections instance vpls1 extensive
Layer-2 VPN connections:
```

```

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
...
PF -- Profile parse failure      PB -- Profile busy

Legend for interface status
Up -- operational
Dn -- down

Instance: vpls1
...
  connection-site      Type  St      Time last up      # Up trans
  1                   rmt   Up      May 21 10:08:34 2013      2
Remote PE: 192.0.2.0, Negotiated control-word: Yes

```

RELATED DOCUMENTATION

[Control Word for BGP VPLS Overview | 622](#)

[control-word | 1458](#)

[no-control-word | 1594](#)

BGP Route Reflectors for VPLS

In large networks, it might be necessary to configure BGP route reflectors to reduce the control plane workload for the routers participating in the VPLS network. BGP route reflectors can help to reduce the workload of the network control plane in the following ways.

- Making it unnecessary to configure all of the VPLS PE routers in a full mesh.
- Limiting the total volume of BGP VPLS messages exchanged within the network by transmitting messages to interested routers only (instead of all of the BGP routers in the network)
- Reducing the network signaling load whenever another BGP router is added to or removed from the network

The basic solution to these problems is to deploy a small group of BGP route reflectors that are in a full mesh with one another. Each of the VPLS PE routers is configured to have a BGP session with one or more of the route reflectors, making it unnecessary to maintain a full mesh of BGP sessions between all of the PE routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

This type of configuration only affects the control plane of the VPLS network (how routers signal and tear down pseudowires to one another in the network). The actual data plane state and forwarding paths for the VPLS traffic are not modified by the route reflectors. Effectively, the VPLS pseudowires should take the same paths across the network whether or not you have configured route reflectors. For a description of how VPLS selects the best path to a PE router, see "[VPLS Path Selection Process for PE Routers](#)" on page 753.

The MAC addresses themselves are not exchanged or processed in any way by BGP. Each VPLS PE router performs all MAC address learning and aging individually. BGP's only function relative to VPLS is to exchange messages related to automatic discovery of PE routers being added to and removed from the VPLS network and the MPLS label exchange needed to signal a pseudowire from one PE router to another.

RELATED DOCUMENTATION

[VPLS Path Selection Process for PE Routers | 753](#)

[Example: Configuring a Route Reflector](#)

[Example: NG-VPLS Using Point-to-Multipoint LSPs | 1030](#)

[Example: Next-Generation VPLS for Multicast with Multihoming | 997](#)

Interoperability Between BGP Signaling and LDP Signaling in VPLS

IN THIS SECTION

- [LDP-Signaled and BGP-Signaled PE Router Topology | 627](#)
- [Flooding Unknown Packets Across Mesh Groups | 629](#)
- [Unicast Packet Forwarding | 629](#)

You can configure a VPLS routing instance where some of the PE routers use BGP for signaling and some use LDP for signaling.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The following concepts form the basis of the configuration needed to include both BGP-signaled and LDP-signaled PE routers in a VPLS routing instance:

- **PE router mesh group**—Consists of a set of routers participating in a VPLS routing instance that share the same signaling protocol, either BGP or LDP, and are also fully meshed. Each VPLS routing instance can have just one BGP mesh group. However, you can configure multiple LDP mesh groups for each routing instance.
- **Border router**—A PE router that must be reachable by all of the other PE routers participating in a VPLS routing instance, whether they are LDP-signaled or BGP-signaled. Bidirectional pseudowires are created between the border router and all of these PE routers. The border router is aware of the composition of each PE mesh group configured as a part of the VPLS routing instance. It can also have direct connections to local CE routers, allowing it to act as a typical PE router in a VPLS routing instance.


The following sections describe how the LDP-signaled and BGP-signaled PE routers function when configured to interoperate within a VPLS routing instance:

LDP-Signaled and BGP-Signaled PE Router Topology

Figure 49 on page 628 illustrates a topology for a VPLS routing instance configured to support both BGP and LDP signaling. Router B is the border router. Routers PE1 and PE2 are in the LDP-signaled mesh group LDP-1. Routers PE3, PE4, and PE5 are in the LDP-signaled mesh group LDP-2. Routers PE6, PE7, PE8, and router B (the border router) are in the BGP-signaled mesh group. The border router also

acts as a standard VPLS PE router (having local connections to CE routers). All of the PE routers shown are within the same VPLS routing instance.

Figure 49: BGP and LDP Signaling for a VPLS Routing Instance



Two-way pseudowires are established between the PE routers in each mesh group and between each PE router in the VPLS routing instance and the border router. In [Figure 49 on page 628](#), two-way pseudowires are established between routers PE1 and PE2 in mesh group LDP-1, routers PE3, PE4, and PE5 in mesh group LDP-2, and routers PE6, PE7, and PE8 in the BGP mesh group. Routers PE1 through PE8 also all have two-way pseudowires to the Border router. Based on this topology, the LDP-signaled routers are able to interoperate with the BGP-signaled routers. Both the LDP-signaled and BGP-signaled PE routers can logically function within a single VPLS routing instance.

NOTE: The following features are not supported for VPLS routing instances configured with both BGP and LDP signaling:

- Point-to-multipoint LSPs

- Integrated routing and bridging
- IGMP snooping

Flooding Unknown Packets Across Mesh Groups

Broadcast, multicast, and unicast packets of unknown origin received from a PE router are flooded to all local CE routers. They are also flooded to all of the PE routers in the VPLS routing instance except the PE routers that are a part of the originating PE router mesh group.

For example, if a multicast packet is received by the border router in [Figure 49 on page 628](#), it is flooded to the two local CE routers. It is also flooded to routers PE1 and PE2 in the LDP-1 mesh group and to routers PE3, PE4, and PE5 in the LDP-2 mesh group. However, the packet is not flooded to routers PE6, PE7, and PE8 in the BGP mesh group.

Unicast Packet Forwarding

The PE border router is made aware of the composition of each PE router mesh group. From the data plane, each PE router mesh group is viewed as a virtual pseudowire LAN. The border router is configured to interconnect all of the PE router mesh groups belonging to a single VPLS routing instance. To interconnect the mesh groups, a common MAC table is created on the border router.

Unicast packets originating within a mesh group are dropped if the destination is another PE router within the same mesh group. However, if the destination MAC address of the unicast packet is a PE router located in a different mesh group, the packet is forwarded to that PE router.

Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS

IN THIS SECTION

- [LDP BGP Interworking Platform Support | 630](#)
- [Configuring FEC 128 VPLS Mesh Groups for LDP BGP Interworking | 631](#)
- [Configuring FEC 129 VPLS Mesh Groups for LDP BGP Interworking | 631](#)
- [Configuring Switching Between Pseudowires Using VPLS Mesh Groups | 632](#)
- [Configuring Integrated Routing and Bridging Support for LDP BGP Interworking with VPLS | 633](#)

A single VPLS routing instance can encompass one set of PE routers that use BGP for signaling and another set of PE routers that use LDP for signaling. Within each set, all of the PE routers are fully meshed in both the control and data planes and have a bidirectional pseudowire to each of the other routers in the set. However, the BGP-signaled routers cannot be directly connected to the LDP-signaled routers. To be able to manage the two separate sets of PE routers in a single VPLS routing instance, a border PE router must be configured to interconnect the two sets of routers.

The VPLS RFCs and Internet drafts require that all of the PE routers participating in a single VPLS routing instance must be fully meshed in the data plane. In the control plane, each fully meshed set of PE routers in a VPLS routing instance is called a PE router mesh group. The border PE router must be reachable by and have bidirectional pseudowires to all of the PE routers that are a part of the VPLS routing instance, both the LDP-signaled and BGP-signaled routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

For LDP BGP interworking to function, LDP-signaled routers can be configured with forwarding equivalence class (FEC) 128 or FEC 129.

The following sections describe how to configure BGP LDP interworking for VPLS:

LDP BGP Interworking Platform Support

LDP BGP interworking is supported on the following Juniper Networks routers and routing platforms:

- ACX5048
- ACX5096
- M7i
- M10i
- M40e
- M120
- M320

- MX Series routers
- T Series routers
- TX Matrix routers
- EX Series switches

Configuring FEC 128 VPLS Mesh Groups for LDP BGP Interworking

To configure FEC 128 LDP BGP interworking for VPLS, include the `mesh-group` statement in the VPLS routing instance configuration of the PE border router:

```
mesh-group mesh-group-name {
    local-switching;
    mac-flush [ explicit-mac-flush-message-options ];
    neighbor address;
    peer-as all;
    vpls-id number;
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

Using the `neighbor` statement, configure each PE router that is a part of the mesh group. You must separate the LDP-signaled routers and the BGP-signaled routers into their own respective mesh groups. The LDP-signaled routers can be divided into multiple mesh groups. The BGP-signaled routers must be configured within a single mesh group for each routing instance.

Configuring FEC 129 VPLS Mesh Groups for LDP BGP Interworking

Configuration for a mesh group for FEC 129 is very similar to the configuration for FEC 128.

Note the following differences for FEC 129:

- Each user-defined mesh group must have a unique route distinguisher. Do not use the route distinguisher that is defined for the default mesh group at the [edit routing-instances] hierarchy level.
- Each user-defined mesh group must have its own import and export route target.

- Each user-defined mesh group can have a unique Layer 2 VPN ID. By default, all the mesh groups that are configured for the a VPLS routing-instance use the same Layer 2 VPN ID, the one that you configure at the [edit routing-instances] hierarchy level.

Configuring Switching Between Pseudowires Using VPLS Mesh Groups

To configure switching between Layer 2 circuit pseudowires using VPLS mesh groups, you can do either of the following:

- Configure a mesh group for each Layer 2 circuit pseudowire terminating at a VPLS routing instance. The Junos OS can support up to 16 mesh groups on MX Series routers and up to 128 on M Series and T Series routers. However, two mesh groups are created by default, one for the CE routers and one for the PE routers. Therefore, the maximum number of user-defined mesh groups is 14 for MX Series routers and 126 for M Series and T Series routers.
- Configure a single mesh group, terminate all the Layer 2 circuit pseudowires into it, and enable local switching between the pseudowires by including the `local-switching` statement at the [edit routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name*] hierarchy level. By default, you cannot configure local switching for mesh groups (except for the CE mesh group) because all of the VPLS PE routers must be configured in a full mesh. However, local switching is useful if you are terminating Layer 2 circuit pseudowires in a mesh group configured for an LDP signaled VPLS routing instance.

NOTE: Do not include the `local-switching` statement on PE routers configured in a full mesh VPLS network.

To terminate multiple pseudowires at a single VPLS mesh group, include the `local-switching` statement:

```
local-switching;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name*]

Configuring Integrated Routing and Bridging Support for LDP BGP Interworking with VPLS

Beginning with Junos OS Release 9.4, you can configure an integrated routing and bridging (IRB) interface on a router that functions as an autonomous system border router (ASBR) in an inter-AS VPLS environment between BGP-signaled VPLS and LDP-signaled VPLS. Previously, IRB interfaces were supported only on Provider Edge (PE) routers.

NOTE: ACX Series routers do not support configuring IRB for LDP BGP Interworking with VPLS.

To configure a IRB support for LDP BGP Interworking with VPLS, include the `routing-interface interface-name` statement.

You can include this statement at the following hierarchy levels:

- `[edit routing-instances routing-instance-name]`
- `[edit logical-routers logical-router-name routing-instances routing-instance-name]`

Configuring Inter-AS VPLS with MAC Processing at the ASBR

Inter-AS VPLS with MAC processing at the ASBR enables you to interconnect customer sites that are located in different ASs. In addition, you can configure the ASs with different signaling protocols. You can configure one of the ASs with BGP-signaled VPLS and the other with LDP-signaled VPLS. For more information about how to configure LDP-signaled and BGP signaled VPLS, see ["Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS" on page 629](#).

For inter-AS VPLS to function properly, you need to configure IBGP peering between the PE routers, including the ASBRs in each AS, just as you do for a typical VPLS configuration. You also need to configure EBGP peering between the ASBRs in the separate ASs. The EBGP peering is needed between the ASBRs only. The link between the ASBR routers does not have to be Ethernet. You can also connect a CE router directly to one of the ASBRs, meaning you do not have to have a PE router between the ASBR and the CE router.

The configuration for the connection between the ASBRs makes inter-AS VPLS with MAC operations unique. The other elements of the configuration are described in other sections of this manual.

The following sections describe how to configure inter-AS VPLS with MAC operations:

Inter-AS VPLS with MAC Operations Configuration Summary

This section provides a summary of all of the elements which must be configured to enable inter-AS VPLS with MAC operations. These procedures are described in detail later in this chapter and in other parts of the [Junos OS VPNs Library for Routing Devices](#).

The following lists all of major elements of an inter-AS VPLS with MAC operations configuration:

- Configure IBGP between all of the routers within each AS, including the ASBRs.
- Configure EBGP between the ASBRs in the separated ASs. The EBGP configuration includes the configuration that interconnects the ASs.
- Configure a full mesh of LSPs between the ASBRs.
- Configure a VPLS routing instance encompassing the ASBR routers. The ASBRs are VPLS peers and are linked by a single pseudowire. Multihoming between ASs is not supported. A full mesh of pseudowires is needed between the ASBR routers in all of the interconnected ASs.
- Configure the VPLS routing instances using either BGP signaling or LDP signaling. LDP BGP interworking is supported for inter-AS VPLS with MAC operations, so it is possible to interconnect the BGP-signaled VPLS routing instances with the LDP-signaled VPLS routing instances.
- Configure a single VPLS mesh group for all of the ASBRs interconnected using inter-AS VPLS.

Configuring the ASBRs for Inter-AS VPLS

This section describes the configuration on the ASBRs needed to enable inter-AS VPLS with MAC operations.

On each ASBR, you need to configure a VPLS mesh group within the VPLS routing instance which needs to include all of the PE routers within the AS, in addition to the ASBR. You need to configure the same mesh group for each of the ASs you want to interconnect using inter-AS VPLS. The mesh group name should be identical on each AS. You also must include the `peer-as all` statement. This statement enables the router to establish a single pseudowire to each of the other ASBRs.

To configure the mesh group on each ASBR, include the `mesh-group` and `peer-as all` statements:

```
mesh-group mesh-group-name {
    peer-as all;
}
```

You can include these statements at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]

- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)


[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

Example: VPLS Configuration (BGP Signaling)

IN THIS SECTION

- [Verifying Your Work | 646](#)

Figure 50: VPLS Topology Diagram



g017142

In [Figure 50 on page 637](#), a simple VPLS topology is enabled between routers PE1 and PE2. CE routers CE1 and CE2 use Ethernet-based interfaces to connect VLAN 600 to their local PE router. The PE routers PE1 and PE2 are connected to one another by LSPs enabled across a service provider backbone running MPLS, BGP, RSVP, and OSPF.

In a VPLS routing instance named *green*, PE1 has a local interface *fe-0/1/0* and a virtual port of *vt-0/3/0.32770* (the virtual port is created dynamically on the Tunnel Services PIC when VPLS is configured). PE2 has a local interface *fe-0/1/0* and a virtual port of *vt-0/3/0.32771* in the same *green* instance. As a result, routers CE1 and CE2 send Ethernet traffic to one another as if they were physically connected to each other on a LAN.

On Router CE1, the only item you need to configure is the Fast Ethernet interface that connects to PE1. Be sure to write down the VLAN identifier and IP address, so you can match them later on CE2.

Router CE1

```
[edit]
interfaces {
  fe-0/1/0 {
    vlan-tagging; # Configure VLAN tagging for VLAN VPLS or extended VLAN VPLS.
    unit 0 {
      vlan-id 600; # The Ethernet interface on CE2 must use the same VLAN ID.
      family inet {
        address 10.11.3.1/24; # The interface on CE2 must use the same prefix.
      }
    }
  }
}
```

If Router PE1 is an MX Series device, you need to configure a tunnel service interface.

To create tunnel interfaces on an MX Series router, include the *tunnel-services* statement at the *[edit chassis fpc slot-number pic number]* hierarchy level. To configure the bandwidth for a tunnel interface, include the *bandwidth* statement at the *[edit chassis fpc slot-number pic number tunnel services]* hierarchy level.

The following example shows a tunnel interface with 1 Gbps of bandwidth configured on PFE 3 of the DPC installed in slot 0 of an MX Series router:

```
[edit chassis]
fpc 0 {
  pic 3 {
    tunnel services {
```

```

        bandwidth 1g;
    }
}
}

```

On Router PE1, prepare the router for VPLS by configuring BGP, MPLS, OSPF, and RSVP. (These protocols are the basis for most Layer 2 VPN-related applications, including VPLS.) Include the signaling statement at the [edit protocols bgp group *group-name* family l2vpn] hierarchy level, because VPLS uses the same infrastructure for internal BGP as Layer 2 VPNs.

NOTE: In Junos OS Release 7.3 and later, the signaling statement replaces the unicast statement at the [edit protocols bgp group *group-name* family l2vpn] hierarchy level. You must use the signaling statement if you wish to configure VPLS domains and Layer 2 VPNs simultaneously.

Next, configure VLAN tagging on the Fast Ethernet interface connected to Router CE1. Include VLAN VPLS encapsulation at both the physical and logical interface levels. Be sure to use the same VLAN ID for all Ethernet interfaces that are part of a single VPLS instance. Finally, add the Fast Ethernet interface into a VPLS routing instance and specify the site range, site ID number, and site name.

Router PE1

```

[edit]
interfaces {
    fe-0/1/0 {
        vlan-tagging; # Configure VLAN tagging for VLAN VPLS or extended VLAN
        VPLS.
        encapsulation vlan-vpls; # Configure VPLS encapsulation on both the
        unit 0 { # physical interface and the logical interface.
            encapsulation vlan-vpls;
            vlan-id 600; # The VLAN ID is the same one used by the CE routers.
        }
    }
    so-1/1/0 {
        unit 0 {
            family inet {
                address 10.11.1.5/30;
            }
            family mpls;
        }
    }
    lo0 {

```

```

        unit 0 {
            family inet {
                address 10.245.14.218/32;
            }
        }
    }
}
routing-options {
    autonomous-system 69;
    forwarding-table {
        export exp-to-fwd; # Apply a policy that selects an LSP for the VPLS instance.
    }
}
protocols {
    rsvp {
        interface all {
            aggregate;
        }
    }

    mpls {
        label-switched-path pe1-to-pe2 { # Configure an LSP to reach other
VPLS PEs.
        to 10.245.14.219;
    }
    interface all;
}
bgp {
    group vpls-pe {
        type internal;
        local-address 10.245.14.218;
        family l2vpn { # VPLS uses the same infrastructure as Layer 2 VPNs
            signaling; # for internal BGP.
        }
        neighbor 10.245.14.217;
        neighbor 10.245.14.219;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface so-1/1/0.0 {
            metric 11;
        }
    }
}

```

```

        interface lo0.0 {
            passive;
        }
    }
}

policy-options {
    policy-statement exp-to-fwd {
        term a {
            from community grn-com; # Matches the community in the VPLS instance.
            then {
                install-nexthop lsp pe1-to-pe2; # If there are multiple LSPs that exist
                accept; # between VPLS PE routers, this statement sends VPLS traffic
            } # over a specific LSP.
        }
    }

    community grn-com members target:11111:1; # Adds the instance to a BGP
} # community.

routing-instances {
    green {
        instance-type vpls; # Configure a VPLS routing instance.
        interface fe-0/1/0.0;
        route-distinguisher 10.245.14.218:1;
        vrf-target target:11111:1; # This value is important to the BGP community.
        protocols {
            vpls { # Configure a VPLS site range, site name, and site identifier.
                site-range 10;
                site greenPE1 {
                    site-identifier 1;
                }
            }
        }
    }
}
}

```

On Router P0, configure BGP, MPLS, OSPF, and RSVP to interconnect PE1 and PE2.

Router P0

```

[edit]
interfaces {
    so-0/0/0 {

```

```

    unit 0 {
        family inet {
            address 10.11.2.6/30;
        }
        family mpls;
    }
}

    so-1/1/0 {
    unit 0 {
        family inet {
            address 10.11.1.6/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.245.14.217/32;
        }
    }
}
}
routing-options {
    autonomous-system 69;
}
protocols {
    rsvp {
        interface all {
            aggregate;
        }
    }

    mpls {
        interface all;
    }
    bgp {
        group vpls-pe {
            type internal;
            local-address 10.245.14.217;
            family l2vpn { # VPLS uses the same infrastructure as Layer 2 VPNs
                signaling; # for internal BGP.
            }
            neighbor 10.245.14.218;

```

```

        neighbor 10.245.14.219;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface so-1/1/0.0 {
            metric 11;
        }
        interface so-0/0/0.0 {
            metric 15;
        }
        interface lo0.0 {
            passive;
        }
    }
}
}

```

If Router PE2 is an MX Series device, you need to configure a tunnel service interfaces.

To create tunnel interfaces on an MX Series router, include the `tunnel-services` statement at the `[edit chassis fpc slot-number pic number]` hierarchy level. To configure the bandwidth for a tunnel interface, include the `bandwidth` statement at the `[edit chassis fpc slot-number pic number]` hierarchy level.

The following example shows a tunnel interface with 1 Gbps of bandwidth configured on PFE 3 of the DPC installed in slot 0 of an MX Series router:

```

[edit chassis]
fpc 0 {
    pic 3 {
        tunnel services {
            bandwidth 1g;
        }
    }
}

```

On Router PE2, configure BGP, MPLS, OSPF, and RSVP to complement the configuration on PE1. Next, configure VLAN tagging on the Fast Ethernet interface connected to Router CE2. Include VLAN VPLS encapsulation at both the physical and logical interface levels. Be sure to use the same VLAN ID for all Ethernet interfaces that are part of a single VPLS instance. Finally, add the Fast Ethernet interface into a VPLS routing instance and specify the site range, site ID number, and site name.

Router PE2

```
[edit]
interfaces {
    fe-0/1/0 {
        vlan-tagging; # Configure VLAN tagging for VLAN VPLS or extended VLAN VPLS.
        encapsulation vlan-vpls; # Configure VPLS encapsulation on both the
        unit 0 { # physical interface and logical interface.
            encapsulation vlan-vpls;
            vlan-id 600;# The VLAN ID is the same one used by the CE routers.
        }
    }
    so-0/0/0 {
        unit 0 {
            family inet {
                address 10.11.2.5/30;
            }
            family mpls;
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 10.245.14.219/32;
            }
        }
    }
}
routing-options {
    autonomous-system 69;
    forwarding-table {
        export exp-to-fwd; # Apply a policy that selects an LSP for the VPLS instance.
    }
}
protocols {
    rsvp {
        interface all {
            aggregate;
        }
    }
    mpls {
        label-switched-path pe2-to-pe1 { # Configure an LSP to other VPLS PE routers.
```

```

        to 10.245.14.218;
    }
    interface all;
}
bgp {
    group vpls-pe {
        type internal;
        local-address 10.245.14.219;
        family l2vpn { # VPLS uses the same infrastructure as Layer 2 VPNs
            signaling; # for internal BGP.
        }
        neighbor 10.245.14.217;
        neighbor 10.245.14.218;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface so-0/0/0.0 {
            metric 15;
        }
        interface lo0.0 {
            passive;
        }
    }
}
}
policy-options {
    policy-statement exp-to-fwd {
        term a {
            from community grn-com; # Matches the community with the VPLS instance.
            then {
                install-nexthop lsp pe2-to-pe1; # If there are multiple LSPs that exist
                accept; # between VPLS PE routers, this statement sends VPLS traffic
            } # over a specific LSP.
        }
    }
    community grn-com members target:11111:1; # This adds the instance into a BGP community.
}
routing-instances {
    green {
        instance-type vpls; # Configure a VPLS routing instance.
        interface fe-0/1/0.0;
    }
}

```



```

route-distinguisher 10.245.14.219:1;
vrf-target target:11111:1; # This value is important for the BGP community.
protocols {
    vpls { # Configure a VPLS site range, site name, and site identifier.
        site-range 10;
        site greenPE2 {
            site-identifier 2;
        }
    }
}
}
}
}

```

On Router CE2, complete your VPLS network by configuring the Fast Ethernet interface that connects to PE2. Use the same VLAN identifier and IP address prefix used on Router CE1.

Router CE2

```

[edit]
interfaces {
    fe-0/1/0 {
        vlan-tagging; # Configure VLAN tagging for VLAN VPLS or extended VLAN VPLS.
        unit 0 {
            vlan-id 600; # The Ethernet interface on CE1 must use the same VLAN ID.
            family inet {
                address 10.11.3.2/24; # The interface on CE1 must use the same prefix.
            }
        }
    }
}
}

```

Verifying Your Work

To verify proper operation of VPLS, use the following commands:

- `clear vpls mac-address instance instance-name`
- `show interfaces terse`
- `show route forwarding-table family mpls`
- `show route forwarding-table family vpls (destination | extensive | matching | table)`


```

                                     feee::10:245:14:218
lsi                                up    up
mtun                              up    up
pimd                             up    up
pime                             up    up
tap                              up    up

user@PE1> show system statistics vpls
vpls:
    0 total packets received
    0 with size smaller than minimum
    0 with incorrect version number
    0 packets for this host
    0 packets with no logical interface
    0 packets with no family
    0 packets with no route table
    0 packets with no auxiliary table
    0 packets with no corefacing entry
    0 packets with no CE-facing entry
    6 mac route learning requests # This indicates that VPLS is working.
    6 mac routes learnt
    0 mac routes aged
    0 mac routes moved

```

To display VPLS source and destination MAC address accounting information, use the destination, extensive, matching, or table option with the `show route forwarding-table family vpls` command. When you analyze the display output, keep in mind the following:

- VPLS MAC address accounting is handled on a per-MAC address basis for each VPLS instance. All information is retrieved from MAC address entries in the MAC address table. VPLS MAC address accounting is performed only on local CE routers.
- The VPLS counters for source and destination MAC addresses increment continuously until the oldest MAC address entries are removed from the memory buffer, either when the entries time out or if the VPLS instance is restarted.

```

user@PE1> show route forwarding-table family vpls extensive
Routing table: green.vpls [Index 2]
VPLS:

Destination: default
Route type: dynamic          Route reference: 0

```

```

Flags: sent to PFE
Next-hop type: flood           Index: 353       Reference: 1

Destination: default
Route type: permanent         Route reference: 0
Flags: none
Next-hop type: discard        Index: 298       Reference: 1

Destination: fe-0/1/0.0
Route type: dynamic           Route reference: 0
Flags: sent to PFE
Next-hop type: flood          Index: 355       Reference: 1

Destination: bb:bb:bb:bb:bb:bb/48 # This MAC address belongs to remote CE2.
Route type: dynamic           Route reference: 0
Flags: sent to PFE, prefix load balance
Next-hop type: indirect       Index: 351       Reference: 4
Next-hop type: Push 800000, Push 100002(top)
Next-hop interface: so-1/1/0.0

Destination: aa:aa:aa:aa:aa:aa/48 # This MAC address belongs to local CE1.
Route type: dynamic           Route reference: 0
Flags: sent to PFE, prefix load balance
Next-hop type: unicast        Index: 354       Reference: 2
Next-hop interface: fe-0/1/0.0

user@PE1> show route forwarding-table family vpls
Routing table: green.vpls
VPLS:
Destination      Type RtRef Next hop      Type Index NhRef Netif
default          dynm   0          flood  353    1
default          perm   0          dscd   298    1
fe-0/1/0.0       dynm   0          flood  355    1
bb:bb:bb:bb:bb:bb/48 # This MAC address belongs to remote CE2.
                  dynm   0          indr   351    4
                  Push 800000, Push 100002(top)
so-1/1/0.0
aa:aa:aa:aa:aa:aa/48 # This MAC address belongs to local CE1.
                  dynm   0          ucst   354    2 fe-0/1/0.0

user@PE1> show route forwarding-table family mpls
Routing table: mpls

```

MPLS:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		dscd	19	1	
0	user	0		recv	18	3	
1	user	0		recv	18	3	
2	user	0		recv	18	3	
100000	user	0	10.11.1.6	swap	100001		so-1/1/0.0
800002	user	0		Pop			vt-0/3/0.32770
vt-0/3/0.32770 (VPLS)							
	user	0		indr	351	4	
Push 800000, Push 100002(top) so-1/1/0.0							

```
user@PE1> show route instance green detail
```

```
green:
```

```
Router ID: 0.0.0.0
```

```
Type: vpls State: Active
```

```
Interfaces:
```

```
fe-0/1/0.0 # This is the local Fast Ethernet interface.
```

```
vt-0/3/0.32770 # This is the dynamically generated VPLS virtual port.
```

```
Route-distinguisher: 10.245.14.218:1
```

```
Vrf-import: [ __vrf-import-green-internal__ ]
```

```
Vrf-export: [ __vrf-export-green-internal__ ]
```

```
Vrf-import-target: [ target:11111:1 ]
```

```
Vrf-export-target: [ target:11111:1 ]
```

```
Tables:
```

```
green.l2vpn.0 : 2 routes (2 active, 0 holddown, 0 hidden)
```

```
user@PE1> show vpls connections
```

```
L2VPN Connections:
```

```
Legend for connection status (St)
```

```
OR -- out of range WE -- intf encaps != instance encaps
```

```
EI -- encapsulation invalid Dn -- down
```

```
EM -- encapsulation mismatch VC-Dn -- Virtual circuit down
```

```
CM -- control-word mismatch -> -- only outbound conn is up
```

```
CN -- circuit not present <- -- only inbound conn is up
```

```
OL -- no outgoing label Up -- operational
```

```
NC -- intf encaps not CCC/TCC XX -- unknown
```

```
NP -- interface not present
```

```
Legend for interface status
```

```
Up -- operational
```

```
Dn -- down
```

Instance: green

Local site: greenPE1 (1)

connection-site	Type	St	Time last up	# Up trans
2	rmt	Up	Jan 24 06:26:49 2003	1

Local interface: vt-0/3/0.32770, Status: Up, Encapsulation: VPLS

Remote PE: 10.245.14.219, Negotiated control-word: No

Incoming label: 800002, Outgoing label: 800000

user@PE1> **show system statistics vpls**

vpls:

- 0 total packets received
- 0 with size smaller than minimum
- 0 with incorrect version number
- 0 packets for this host
- 0 packets with no logical interface
- 0 packets with no family
- 0 packets with no route table
- 0 packets with no auxiliary table
- 0 packets with no corefacing entry
- 0 packets with no CE-facing entry
- 7 mac route learning requests
- 7 mac routes learnt
- 0 mac routes aged
- 0 mac routes moved

user@PE1> **show route instance green detail**

green:

Router ID: 0.0.0.0

Type: vpls State: Active

Interfaces:

fe-0/1/0.0

vt-0/3/0.32770

Route-distinguisher: 10.245.14.218:1

Vrf-import: [__vrf-import-green-internal__]

Vrf-export: [__vrf-export-green-internal__]

Vrf-import-target: [target:11111:1]

Vrf-export-target: [target:11111:1]

Tables:

green.l2vpn.0 : 2 routes (2 active, 0 holddown, 0 hidden)

user@PE1> **show vpls statistics**

Layer-2 VPN Statistics:

Instance: green

Local interface: fe-0/1/0.0, Index: 351

Remote provider edge router: 10.245.14.219

Multicast packets: 363

Multicast bytes : 30956

Flood packets : 0

Flood bytes : 0

Local interface: vt-0/3/0.32770, Index: 354

Remote provider edge router: 10.245.14.219

Multicast packets: 135

Multicast bytes : 12014

Flood packets : 135

Flood bytes : 12014

To clear all MAC address entries for a VPLS instance from the VPLS table, issue the `clear vpls mac-address instance instance-name` command. Add the `logical-system logical-system-name` option to clear entries in a VPLS instance within a logical system. Use the `mac-address` option to remove individual MAC addresses.

RELATED DOCUMENTATION

[Virtual Private LAN Services](#)

Example: VPLS Configuration (BGP and LDP Interworking)

IN THIS SECTION

- [Verifying Your Work | 667](#)

Figure 51: Topology for VPLS Configuration Example




Figure 51 on page 653, shows two VPLS mesh groups: LDP-1 and the default BGP mesh group. The VPLS instance is named v1 in the configuration. Table 13 on page 654 shows the addresses for the router interfaces in the example topology.

Table 13: Router Interface Addresses for VPLS Configuration Example

Router	Interface	Address
CE1	fe-0/0/3 (link to Router PE1)	10.12.31.1
	loopback	10.12.53.1
CE2	fe-0/0/1 (link to Router PE2)	10.12.31.2
	loopback	10.12.53.2
PE1	t1-1/1/1 (link to Router PE2)	10.12.100.17
	t1-0/1/0 (link to Router B)	10.12.100.2
	loopback	10.255.170.106
PE2	t1-0/1/1 (link to Router PE1)	10.12.100.18
	t1-0/1/3 (link to Router B)	10.12.100.6
	loopback	10.255.170.104
B	t1-0/1/2 (link to Router PE1)	10.12.100.1
	t1-0/1/3 (link to Router PE2)	10.12.100.5
	so-0/2/2 (link to Router PE3)	10.12.100.9
	fe-0/0/3 (link to Router PE4)	10.12.100.13
	loopback	10.255.170.98

Table 13: Router Interface Addresses for VPLS Configuration Example (Continued)

Router	Interface	Address
PE3	s0-0/2/1 (link to Router B)	10.12.100.10
	so-0/2/2 (link to Router P0)	10.12.100.21
	loopback	10.255.170.96
P0	so-0/2/1 (link to Router PE3)	10.12.100.22
	t1-0/1/3 (link to Router PE4)	10.12.100.25
	loopback	10.255.170.100
PE4	fe-0/0/3 (link to Router B)	10.12.100.14
	t1-0/1/3 (link to Router P0)	10.12.100.26
	loopback	10.255.170.102
CE3	ge-1/2/1 (link to PE3)	10.12.31.3
	loopback	10.12.53.3
CE4	fe-0/0/2 (link to PE4)	10.12.31.4
	loopback	10.12.53.4

On Router CE3, the only item you need to configure is the Gigabit Ethernet interface that connects to PE3.

Router CE3

```
[edit]
interfaces {
  ge-1/2/1 {
    unit 0 {
      family inet {
        address 10.12.31.1/24;
      }
    }
  }
}
```

On Router PE3, prepare the router for VPLS by configuring BGP, MPLS, OSPF, and LDP. (These protocols are the basis for most Layer 2 VPN-related applications, including VPLS.) Include the `signaling` statement at the `[edit protocols bgp group group-name family l2vpn]` hierarchy level, because VPLS uses the same infrastructure for internal BGP as Layer 2 VPNs.

NOTE: In Junos OS Release 7.3 and later, the `signaling` statement replaces the `unicast` statement at the `[edit protocols bgp group group-name family l2vpn]` hierarchy level. You must use the `signaling` statement if you wish to configure VPLS domains and Layer 2 VPNs simultaneously.

Next, configure VLAN tagging on the Gigabit Ethernet interface connected to Router CE3. Finally, add the Gigabit Ethernet interface into a VPLS routing instance and specify the site range, site ID number, and site name.

Router PE3

```
[edit]
interfaces {
  so-0/2/1 {
    unit 0 {
      family inet {
        address 10.12.100.10/30;
      }
      family mpls;
    }
  }
  so-0/2/2 {
    unit 0 {
      family inet {
```

```

        address 10.12.100.21/30;
    }
    family mpls;
}
}
ge-1/3/1 {
    encapsulation ethernet-vpls;
    unit 0 {
        family vpls;
    }
}
}
}
protocols {
    mpls {
        interface all;
    }
    bgp {
        log-updown;
        group int {
            type internal;
            local-address 10.255.170.96;
            family l2vpn {
                signaling;
            }
            neighbor 10.255.170.98;
            neighbor 10.255.170.102;
        }
    }
    ospf {
        area 0.0.0.0 {
            interface so-0/2/1.0;
            interface so-0/2/2.0;
            interface lo0.0 {
                passive;
            }
        }
    }
    ldp {
        interface so-0/2/1.0;
        interface so-0/2/2.0;
    }
}
}

```

```

routing-instances {
  v1 {
    instance-type vpls;
    interface ge-1/3/1.0;
    route-distinguisher 10.255.170.96:1;
    vrf-target target:1:2;
    protocols {
      vpls {
        site-range 10;
        site 1 {
          site-identifier 3;
        }
      }
    }
  }
}

```

On Router P0, configure MPLS, OSPF, and LDP to interconnect PE3 and PE4.

Router P0

```

[edit]
interfaces {
  t1-0/1/3 {
    unit 0 {
      family inet {
        address 10.12.100.25/30;
      }
      family mpls;
    }
  }
  so-0/2/1 {
    unit 0 {
      family inet {
        address 10.12.100.22/30;
      }
      family mpls;
    }
  }
}
protocols {
  mpls {
    interface all;
  }
}

```

```

ospf {
    area 0.0.0.0 {
        interface so-0/2/1.0;
        interface t1-0/1/3.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface t1-0/1/3.0;
    interface so-0/2/1.0;
}
}

```

On Router PE4, configure BGP, MPLS, OSPF, and LDP to complement the configuration on PE3. Next, configure VLAN tagging on the Fast Ethernet interface connected to Router CE4. Include VLAN VPLS encapsulation at both the physical and logical interface levels. Finally, add the Fast Ethernet interface into a VPLS routing instance and specify the site range, site ID number, and site name.

Router PE4

```

[edit]
interfaces {
    fe-0/0/2 {
        encapsulation ethernet-vpls;
        unit 0 {
            family vpls;
        }
    }
    fe-0/0/3 {
        unit 0 {
            family inet {
                address 10.12.100.14/30;
            }
            family mpls;
        }
    }
}
t1-0/1/3 {
    unit 0 {
        family inet {
            address 10.12.100.26/30;
        }
    }
}

```

```

        family mpls;
    }
}
protocols {
    mpls {
        interface all;
    }
    bgp {
        log-updown;
        group int {
            type internal;
            local-address 10.255.170.102;
            family l2vpn {
                signaling;
            }
            neighbor 10.255.170.96;
            neighbor 10.255.170.98;
        }
    }
}
ospf {
    area 0.0.0.0 {
        interface fe-0/0/3.0;
        interface t1-0/1/3.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface fe-0/0/3.0;
    interface t1-0/1/3.0;
    interface lo0.0;
}
}
routing-instances {
    v1 {
        instance-type vpls;
        interface fe-0/0/2.0;
        route-distinguisher 10.255.170.102:1;
        vrf-target target:1:2;
        protocols {

```

```

    vpls {
        site-range 10;
        site 1 {
            site-identifier 4;
        }
    }
}

```

On Router CE4, configure the Fast Ethernet interface that connects to PE4.

Router CE4

```

[edit]
interfaces {
    fe-0/0/2 {
        unit 0 {
            family inet {
                address 10.12.31.4/24;
            }
        }
    }
}

```

On Router B, the area border router, configure the interfaces. Next, configure BGP, MPLS, OSPF, and LDP. Be sure to include the loopback interface in the LDP configuration by including the `interface lo0.0` statement at the `[edit protocols ldp]` hierarchy level. For BGP, include the signaling statement at the `[edit bgp group group-name family l2vpn]` hierarchy level. Last, configure the VPLS instance with both BGP and LDP signaling. Configure the LDP-1 mesh group by including the `mesh-group ldp1` statement at the `[edit routing-instances v1 protocols vpls]` hierarchy level.

Router B

```

[edit]
interfaces {
    fe-0/0/3 {
        unit 0 {
            family inet {
                address 10.12.100.13/30;
            }
            family mpls;
        }
    }
}

```



```

}
t1-0/1/2 {
    unit 0 {
        family inet {
            address 10.12.100.1/30;
        }
        family mpls;
    }
}
t1-0/1/3 {
    unit 0 {
        family inet {
            address 10.12.100.5/30;
        }
        family mpls;
    }
}
so-0/2/2 {
    unit 0 {
        family inet {
            address 10.12.100.9/30;
        }
        family mpls;
    }
}
}
protocols {
    mpls {
        interface all;
    }
    bgp {
        log-updown;
        group int {
            type internal;
            local-address 10.255.170.98;
            family l2vpn {
                signaling;
            }
            neighbor 10.255.170.96;
            neighbor 10.255.170.102;
        }
    }
}
ospf {

```

```

    area 0.0.0.0 {
        interface t1-0/1/2.0;
        interface t1-0/1/3.0;
        interface so-0/2/2.0;
        interface fe-0/0/3.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface fe-0/0/3.0;
    interface t1-0/1/2.0;
    interface t1-0/1/3.0;
    interface so-0/2/2.0;
    interface lo0.0;
}
}
routing-instances {
    v1 {
        instance-type vpls;
        route-distinguisher 10.255.170.98:1;
        vrf-target target:1:2;
        protocols {
            vpls {
                site-range 10;
                site 1 {
                    site-identifier 1;
                }
                vpls-id 101;
                mesh-group ldp-1 {
                    neighbor 10.255.170.106;
                    neighbor 10.255.170.104;
                }
            }
        }
    }
}
}

```

Finally, configure the LDP PE routers. On Router PE1, prepare the router for VPLS by configuring LDP, MPLS, and OSPF. Next, configure VPLS encapsulation on the Fast Ethernet interface connected to CE1. Finally, add the Fast Ethernet interface to the routing instance, specifying the VPLS ID and the neighboring routers' loopback addresses.

Router PE1

```
[edit]
interfaces {
  fe-0/0/3 {
    encapsulation ethernet-vpls;
    unit 0 {
      family vpls;
    }
  }
  t1-0/1/0 {
    unit 0 {
      family inet {
        address 10.12.100.2/30;
      }
      family mpls;
    }
  }
  t1-1/1/1 {
    unit 0 {
      family inet {
        address 10.12.100.17/30;
      }
      family mpls;
    }
  }
}
protocols {
  mpls {
    interface all;
  }
  ospf {
    area 0.0.0.0 {
      interface t1-0/1/0.0;
      interface t1-1/1/1.0;
      interface lo0.0 {
        passive;
      }
    }
  }
  ldp {
    interface t1-0/1/0.0;
```

```

        interface t1-1/1/1.0;
        interface lo0.0;
    }
}
routing-instances {
    v1 {
        instance-type vpls;
        interface fe-0/0/3.0;
        protocols {
            vpls {
                vpls-id 101;
                neighbor 10.255.170.98;
                neighbor 10.255.170.104;
            }
        }
    }
}
}

```

Next, configure the Fast Ethernet interface on Router CE1 that connects to Router PE1.

Router CE1

```

[edit]
interfaces {
    fe-0/0/3 {
        unit 0 {
            family inet {
                address 10.12.31.1/24;
            }
        }
    }
}

```

On Router PE2, prepare the router for VPLS by configuring LDP, MPLS, and OSPF. Next, configure VPLS encapsulation on the Fast Ethernet interface connected to Router CE1. Finally, add the Fast Ethernet interface to the routing instance, specifying the VPLS ID and the neighboring routers' loopback addresses.

Router PE2

```

[edit]
interfaces {

```

```

t1-0/1/1 {
    unit 0 {
        family inet {
            address 10.12.100.18/30;
        }
        family mpls;
    }
t1-0/1/3 {
    unit 0 {
        family inet {
            address 10.12.100.6/30;
        }
        family mpls;
    }
}
fe-1/0/2 {
    encapsulation ethernet-vpls;
    unit 0 {
        family vpls;
    }
}
}
protocols {
    mpls {
        interface all;
    }
    ospf {
        area 0.0.0.0 {
            interface t1-0/1/3.0;
            interface t1-0/1/1.0;
            interface lo0.0 {
                passive;
            }
        }
    }
}
ldp {
    interface t1-0/1/1.0;
    interface t1-0/1/3.0;
    interface lo0.0;
}
}
routing-instances {
    v1 {

```

```

instance-type vpls;
interface fe-1/0/2.0;
protocols {
    vpls {
        vpls-id 101;
        neighbor 10.255.170.98;
        neighbor 10.255.170.106;
    }
}
}
}

```

Finally, on Router CE2 configure the Fast Ethernet interface connected to PE2:

Router CE2

```

[edit]
interfaces {
    fe-0/0/1 {
        unit 0 {
            family inet {
                address 10.12.31.2/24;
            }
        }
    }
}
}

```

Verifying Your Work

To verify proper operation of VPLS, use the following commands:

- `show bgp summary`
- `show ldp neighbor`
- `show vpls connections`
- `show route forwarding-table family vpls (destination | extensive | matching | table)`
- `show interfaces vt* terse`
- `show vpls flood extensive`
- `show vpls statistics`

The following section shows the output of some of these commands on Router B as a result of the configuration example.

Use the `show bgp summary` command to verify BGP signaling for VPLS is up.

```
user@B> show bgp summary
Groups: 1 Peers: 2 Down peers: 0
Table          Tot Paths  Act Paths Suppressed    History Damp State   Pending
bgp.l2vpn.0      2          2          0          0          0          0
Peer           AS      InPkt   OutPkt   OutQ   Flaps  Last Up/Dwn
State|#Active/Received/Damped...
10.255.170.96  65000      124     125      0       0      54:26 Establ
  bgp.l2vpn.0: 1/1/0
  v1.l2vpn.0: 1/1/0
10.255.170.102 65000      122     124      0       0      54:18 Establ
  bgp.l2vpn.0: 1/1/0
  v1.l2vpn.0: 1/1/0
```

Use the `show ldp neighbors` command to verify that LDP signaling for VPLS is up.

```
user@B> show ldp neighbors
Address          Interface      Label space ID      Hold time
10.255.170.104   lo0.0         10.255.170.104:0    41
10.255.170.106   lo0.0         10.255.170.106:0    38
10.12.100.14     fe-0/0/3.0    10.255.170.102:0    12
10.12.100.10     so-0/2/2.0    10.255.170.96:0     14
10.12.100.2      t1-0/1/2.0    10.255.170.106:0    14
10.12.100.6      t1-0/1/3.0    10.255.170.104:0    13
```

To verify that the VPLS connections are up, use the `show vpls connections` command.

```
user@B>show vpls connections
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned    <- -- only inbound connection is up
OR -- out of range              Up -- operational
```

OL -- no outgoing label Dn -- down
 LD -- local site signaled down CF -- call admission control failure
 RD -- remote site signaled down SC -- local and remote site ID collision LN -- local site not
 designated LM -- local site ID not minimum designated RN -- remote site not designated RM --
 remote site ID not minimum designated XX -- unknown connection status IL -- no incoming label
 MM -- MTU mismatch MI -- Mesh-Group ID not available

Legend for interface status

Up -- operational

Dn -- down

Instance: v1

BGP-VPLS State

Local site: 1 (1)

connection-site	Type	St	Time last up	# Up trans
3	rmt	Up	Jan 22 16:38:47 2008	1

Local interface: vt-0/3/0.1048834, Status: Up, Encapsulation: VPLS

Description: Intf - vpls v1 local site 1 remote site 3

Remote PE: 10.255.170.96, Negotiated control-word: No

Incoming label: 800258, Outgoing label: 800000

4	rmt	Up	Jan 22 16:38:54 2008	1
---	-----	----	----------------------	---

Local interface: vt-0/3/0.1048835, Status: Up, Encapsulation: VPLS

Description: Intf - vpls v1 local site 1 remote site 4

Remote PE: 10.255.170.102, Negotiated control-word: No

Incoming label: 800259, Outgoing label: 800000 LDP-VPLS State

VPLS-id: 101

Mesh-group connections: m1

Neighbor	Type	St	Time last up	# Up trans
10.255.170.104(vpls-id 101)	rmt	Up	Jan 22 16:38:40 2008	1

Local interface: vt-0/3/0.1048833, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls v1 neighbor 10.255.170.104 vpls-id 101

Remote PE: 10.255.170.104, Negotiated control-word: No

Incoming label: 800001, Outgoing label: 800000

10.255.170.106(vpls-id 101)	rmt	Up	Jan 22 16:38:39 2008	1
-----------------------------	-----	----	----------------------	---

Local interface: vt-0/3/0.1048832, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls v1 neighbor 10.255.170.106 vpls-id 101

Remote PE: 10.255.170.106, Negotiated control-word: No

Incoming label: 800000, Outgoing label: 800000

To display VPLS routes (MAC addresses) in the vpls forwarding table, use the `show route forwarding-table family vpls` command.

```
user@B> show route forwarding-table family vpls
Routing table: v1.vpls
VPLS:
Destination      Type RtRef Next hop      Type Index NhRef Netif
default          perm   0                rjct  540   1
vt-0/3/0.1048832 user    0                comp  587   3
vt-0/3/0.1048833 user    0                comp  587   3
vt-0/3/0.1048834 user    0                comp  589   3
vt-0/3/0.1048835 user    0                comp  589   3
00:17:cb:c2:10:01/48
                  dynm   0                indr 262143  4
                  Push 800000  580   2
t1-0/1/3.0
00:17:cb:c2:10:02/48
                  dynm   0                indr 262145  4
                  10.12.100.14 Push 800000  594   2
fe-0/0/3.0
00:17:cb:c2:10:03/48
                  dynm   0                indr 262142  4
                  Push 800000  576   2
t1-0/1/2.0
00:17:cb:c2:10:bd/48
                  dynm   0                indr 262144  4
                  Push 800000  585   2
so-0/2/2.0
```

To display VPLS source and destination MAC address accounting information, use the `destination`, `extensive`, `matching`, or `table` option with the `show route forwarding-table family vpls` command. When you analyze the display output, keep in mind the following:

- VPLS MAC address accounting is handled on a per-MAC address basis for each VPLS instance. All information is retrieved from MAC address entries in the MAC address table. VPLS MAC address accounting is performed only on local CE routers.
- The VPLS counters for source and destination MAC addresses increment continuously until the oldest MAC address entries are removed from the memory buffer, either when the entries time out or if the VPLS instance is restarted.

To display status information about Virtual Loopback Tunnel interfaces in the VPLS instance, use the `show interfaces vt* terse` command.

```
user@B> show interfaces vt* terse
```

Interface	Admin	Link	Proto	Local	Remote
vt-0/3/0	up	up			
vt-0/3/0.1048832	up	up	vpls		
vt-0/3/0.1048833	up	up	vpls		
vt-0/3/0.1048834	up	up	vpls		
vt-0/3/0.1048835	up	up	vpls		

To display VPLS route information related to the flood process, use the `show vpls flood extensive` command.

```
user@B> show vpls flood extensive
```

Name: v1
CEs: 0
VEs: 4

Flood route prefix: 0x4a/32
Flood route type: IFF_FLOOD
Flood route owner: vt-0/3/0.1048834
Flood group name: __ves__
Flood group index: 0
Nextthop type: comp
Nextthop index: 589

Flooding to:

Name	Type	NhType	Index
m1	Group	comp	588

Composition: flood-to-all

Flooding to:

Name	Type	NhType	Index
vt-0/3/0.1048832 VE		indr	262142
vt-0/3/0.1048833 VE		indr	262143

Flood route prefix: 0x4b/32
Flood route type: IFF_FLOOD
Flood route owner: vt-0/3/0.1048835
Flood group name: __ves__
Flood group index: 0
Nextthop type: comp
Nextthop index: 589

Flooding to:

Name	Type	NhType	Index
m1	Group	comp	588
Composition: flood-to-all			
Flooding to:			
Name	Type	NhType	Index
vt-0/3/0.1048832 VE		indr	262142
vt-0/3/0.1048833 VE		indr	262143

Flood route prefix: 0x48/32

Flood route type: IFF_FLOOD

Flood route owner: vt-0/3/0.1048832

Flood group name: m1

Flood group index: 2

Nexthop type: comp

Nexthop index: 587

Flooding to:

Name	Type	NhType	Index
__ves__	Group	comp	586
Composition: flood-to-all			
Flooding to:			
Name	Type	NhType	Index
vt-0/3/0.1048834 VE		indr	262144
vt-0/3/0.1048835 VE		indr	262145

Flood route prefix: 0x49/32

Flood route type: IFF_FLOOD

Flood route owner: vt-0/3/0.1048833

Flood group name: m1

Flood group index: 2

Nexthop type: comp

Nexthop index: 587

Flooding to:

Name	Type	NhType	Index
__ves__	Group	comp	586
Composition: flood-to-all			
Flooding to:			
Name	Type	NhType	Index
vt-0/3/0.1048834 VE		indr	262144
vt-0/3/0.1048835 VE		indr	262145

To view packet flow statistics for the VPLS instance, use the `show vpls statistics` command:

```
user@B> show vpls statistics
Instance: v1
  Local interface: vt-0/3/0.1048832, Index: 72
  Remote PE: 10.255.170.106
    Multicast packets:           6
    Multicast bytes   :          360
    Flooded packets   :          16
    Flooded bytes     :         1188
    Current MAC count:           1
  Local interface: vt-0/3/0.1048833, Index: 73
  Remote PE: 10.255.170.104
    Multicast packets:           4
    Multicast bytes   :          240
    Flooded packets   :           6
    Flooded bytes     :          398
    Current MAC count:           1
  Local interface: vt-0/3/0.1048834, Index: 74
  Remote PE: 10.255.170.96
    Multicast packets:           2
    Multicast bytes   :          120
    Flooded packets   :           4
    Flooded bytes     :          278
    Current MAC count:           1
  Local interface: vt-0/3/0.1048835, Index: 75
  Remote PE: 10.255.170.102
    Multicast packets:           1
    Multicast bytes   :           60
    Flooded packets   :           2
    Flooded bytes     :          158
    Current MAC count:           1
```

RELATED DOCUMENTATION

[Virtual Private LAN Services](#)

Assigning Routing Instances to VPLS

IN THIS CHAPTER

- [Configuring VPLS Routing Instances | 674](#)
- [Configuring a VPLS Routing Instance | 692](#)
- [Support of Inner VLAN List and Inner VLAN Range for Qualified BUM Pruning on a Dual-Tagged Interface for a VPLS Routing Instance Overview | 693](#)
- [Configuring Qualified BUM Pruning for a Dual-Tagged Interface with Inner VLAN list and InnerVLAN range for a VPLS Routing Instance | 695](#)
- [Configuring a Layer 2 Control Protocol Routing Instance | 697](#)
- [PE Router Mesh Groups for VPLS Routing Instances | 698](#)
- [Configuring VPLS Fast Reroute Priority | 699](#)
- [Specifying the VT Interfaces Used by VPLS Routing Instances | 701](#)
- [Understanding PIM Snooping for VPLS | 702](#)
- [Example: Configuring PIM Snooping for VPLS | 703](#)
- [VPLS Label Blocks Operation | 718](#)
- [Configuring the Label Block Size for VPLS | 723](#)
- [Example: Building a VPLS From Router 1 to Router 3 to Validate Label Blocks | 725](#)

Configuring VPLS Routing Instances

IN THIS SECTION

- [Configuring BGP Signaling for VPLS | 676](#)
- [Configuring LDP Signaling for VPLS | 682](#)
- [Configuring VPLS Routing Instance and VPLS Interface Connectivity | 685](#)
- [Configuring the VPLS Encapsulation Type | 686](#)

- [Configuring the MPLS Routing Table to Leak Routes a Nondefault Routing Instance | 687](#)
- [Configuring the VPLS MAC Table Timeout Interval | 688](#)
- [Configuring the Size of the VPLS MAC Address Table | 688](#)
- [Limiting the Number of MAC Addresses Learned from an Interface | 689](#)
- [Removing Addresses from the MAC Address Database | 691](#)

To configure a VPLS routing instance, include the `vpls` statement:

```
vpls {
  active-interface {
    any;
    primary interface-name;
  }
  connectivity-type (ce | irb | permanent);
  control-word;
  encapsulation-type encapsulation-type;
  interface-mac-limit limit;
  import-labeled-routes [ routing-instance-name ];
  label-block-size size;
  mac-table-aging-time time;
  mac-table-size size;
  neighbor neighbor-id;
  no-control-word;
  no-tunnel-services;
  site site-name {
    active-interface {
      any;
      primary interface-name;
    }
    interface interface-name {
      interface-mac-limit limit;
    }
    mesh-group mesh-group-name;
    multi-homing;
    site-identifier identifier;
    site-preference preference-value {
      backup;
      primary;
    }
  }
}
```

```

    }
}
site-range number;
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
tunnel-services {
    devices device-names;
    primary primary-device-name;
}
vpls-id vpls-id;
}

```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

NOTE: You cannot configure a routing protocol (OSPF, RIP, IS-IS or BGP) inside a VPLS routing instance (instance-type vpls). The Junos CLI disallows this configuration.

NOTE: Starting in Junos OS Release 16.1, you can use the `import-labeled-routes` statement to specify one or more nondefault routing instances where you want MPLS pseudowire labeled routes to be leaked from the mpls.0 path routing table in the primary routing instance.

The configuration for the VPLS routing instance statements is explained in the following sections:

Configuring BGP Signaling for VPLS

You can configure BGP signaling for the VPLS routing instance. BGP is used to signal the pseudowires linking each of the PE routers participating in the VPLS routing instance. The pseudowires carry VPLS traffic across the service provider's network between the VPLS sites.

NOTE: You cannot configure both BGP signaling and LDP signaling for the same VPLS routing instance. If you attempt to configure the statements that enable BGP signaling for the VPLS routing instance (the `site`, `site-identifier`, and `site-range` statements) and the statements that enable LDP signaling for the same instance (the `neighbor` and `vpls-id` statements), the commit operation fails.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Configure BGP signaling for the VPLS routing instance by completing the steps in the following sections:

Configuring the VPLS Site Name and Site Identifier

When you configure BGP signaling for the VPLS routing instance, on each PE router you must configure each VPLS site that has a connection to the PE router. All the Layer 2 circuits provisioned for a VPLS site are listed as the set of logical interfaces (using the `interface` statement) within the `site` statement.

You must configure a site name and site identifier for each VPLS site.

To configure the site name and the site identifier, include the `site` and the `site-identifier` statements:

```
site site-name {
  interface interface-name {
    interface-mac-limit limit;
  }
  site-identifier identifier;
}
```

The numerical identifier can be any number from 1 through 65,534 that uniquely identifies the local VPLS site.

You can include these statements at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

Configuring Automatic Site Identifiers for VPLS

When you enable automatic site identifiers, the Junos OS automatically assigns site identifiers to VPLS sites. Only one site is allowed per routing instances when using the `automatic-site-id` function. To configure automatic site identifiers for a VPLS routing instance, include the `automatic-site-id` statement:

```
automatic-site-id {
    collision-detect-time seconds;
    new-site-wait-time seconds;
    reclaim-wait-time minimum seconds maximum seconds;
    startup-wait-time seconds;
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls site *site-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls site *site-name*]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

The `automatic-site-id` statement includes a number of options that control different delays in network layer reachability information (NLRI) advertisements. All of these options are configured with default values. See the statement summary for the `automatic-site-id` statement for more information.

The `automatic-site-id` statement includes the following options:

- `collision-detect-time`—The time in seconds to wait after a claim advertisement is sent to the other routers in a VPLS instance before a PE router can begin using a site identifier. If the PE router receives a competing claim advertisement for the same site identifier during this time period, it initiates the collision resolution procedure for site identifiers.
- `new-site-wait-time`—The time in seconds to wait to receive VPLS information for a newly configured routing instance or a new site. This time interval is also applied whenever the automatic site identifier feature is activated on a VPLS routing instance other than at startup. Effectively, this timer indicates how long to wait before an attempt is made to allocate a site identifier. This timer is also triggered whenever a VPLS routing instance is enabled.
- `reclaim-wait-time`—The time to wait before attempting to claim a site identifier after a collision. A collision occurs whenever an attempt is made to claim a site identifier by two separate VPLS sites.

- `startup-wait-time`—The time in seconds to wait at startup to receive all the VPLS information for the route targets configured on the other PE routers included in the VPLS routing instance.

Configuring the Site Range

When you enable BGP signaling for each VPLS routing instance, you can optionally configure the site range. The site range specifies an upper limit on the maximum site identifier that can be accepted to allow a pseudowire to be brought up. You must specify a value from 1 through 65,534. The default value is 65,534. We recommend using the default. Pseudowires cannot be established to sites with site identifiers greater than the configured site range. If you issue the `show vpls connections` command, such sites are displayed as OR (out of range).

To configure the site range, include the `site-range` statement:

```
site-range number;
```

You can include this statement at the following hierarchy levels:

- `[edit routing-instances routing-instance-name protocols vpls]`
- `[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls]`

NOTE: ACX Series routers do not support the `[edit logical-systems]` hierarchy.

There are networks that require that the site range be configured using a value smaller than the local site identifier, for example, a hub-and-spoke VPLS with multihomed sites. For this type of network, you need to allow pseudowires to be established between the spoke routers and the hub router. However, you also need to prevent pseudowires from being established between spoke routers directly. Due to the multihoming requirement of spoke sites, Layer 2 VPN NRLIs need to be accepted from other spoke routers (at least from spokes with the same site identifier as the locally configured sites) to determine the status of local spoke routers (active or not active) based on the local preference included in the NRLIs received from the other spoke routers.

This type of VPLS network can be implemented by, for example, numbering hub sites with identifiers 1 through 8 and spoke sites with identifiers 9 and larger. You can then configure a site range of 8 on each of the spoke sites. Although the spoke sites accept NRLIs and install them in the Layer 2 VPN routing tables (allowing the multihomed sites to determine the status of the local site), the spoke sites cannot establish pseudowires directly to the other spoke sites due to the configured site range.

The following configurations illustrate this concept. The configurations are for the VPLS routing instances on three routers, two spoke routers and one hub router:

Router 1—spoke:

```

routing-instance hub-and-spoke {
  no-local-switching;
  protocols {
    vpls {
      site-range 8;
      no-tunnel-services;
      site spoke-9 {
        site-identifier 9 {
          multi-homing;
          site-preference primary;
        }
      }
      site spoke-10 {
        site-identifier 10 {
          multi-homing;
          site-preference backup;
        }
      }
    }
  }
}

```

Router 2—spoke:

```

routing-instance hub-and-spoke {
  no-local-switching;
  protocols {
    vpls {
      site-range 8;
      no-tunnel-services;
      site spoke-9 {
        site-identifier 9 {
          multi-homing;
          site-preference backup;
        }
      }
      site spoke-10 {
        site-identifier 10 {
          multi-homing;

```

```

        site-preference primary;
    }
}
}
}
}

```

Hub—router 3:

```

routing-instance hub-and-spoke {
    no-local-switching;
    protocols {
        vpls {
            no-tunnel-services;
            site hub {
                site-identifier 1;
            }
        }
    }
}

```

Configuring the VPLS Site Interfaces

You must configure an interface for each of the pseudowires you specify for the VPLS site.

To configure an interface for the VPLS site, include the interface statement:

```

interface interface-name {
    interface-mac-limit limit;
}

```

You can include these statements at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls site *site-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

You can also configure a limit on the number of MAC addresses that can be learned from the specified interface. For more information, see ["Limiting the Number of MAC Addresses Learned from an Interface" on page 689](#).

Configuring the VPLS Site Preference

You can specify the local preference value advertised for a particular VPLS site. The site preference value is specified using the `site-preference` statement configured at the `[edit routing-instances routing-instance-name protocols vpls site site-name]` hierarchy level. By configuring the `site-preference` statement, a value configured for the `local-preference` statement at the `[edit protocols bgp]` hierarchy level is ignored by the VPLS routing instance. However, you can change the site preference value for VPLS routes exported to other routers by configuring an export policy. When a PE router receives multiple advertisements with the same VPLS edge (VE) device identifier, the advertisement with the highest local preference value is preferred.

To configure the VPLS site preference, include the `site-preference` statement:

```
site-preference preference-value {
    backup;
    primary;
}
```

You can also specify either the `backup` option or the `primary` option for the `site-preference` statement. The `backup` option specifies the preference value as 1, the lowest possible value, ensuring that the VPLS site is the least likely to be selected. The `primary` option specifies the preference value as 65,535, the highest possible value, ensuring that the VPLS site is the most likely to be selected.

For a list of hierarchy levels at which you can include the `site-preference` statement, see the statement summary section for this statement.

Configuring LDP Signaling for VPLS

You can configure LDP as the signaling protocol for a VPLS routing instance. This functionality is described in RFC 4762, *Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling*.

The Junos OS software does not support all of RFC 4762. When enabling LDP signaling for a VPLS routing instance, network engineers should be aware that only the following values are supported:

- FEC—128 or 129
- Control bit—0
- Ethernet pseudowire type—0x0005
- Ethernet tagged mode pseudowire type—0x0004

LDP signaled VPLS supports the Virtual Circuit Connectivity Verification (VCCV) Type Length Value (TLV) for pseudowire label mapping, label database display, and LDP trace. When you enable LDP signaling for a pseudowire, LDP advertises the VCCV capabilities to the neighboring routers. VCCV provides a control channel for a pseudowire and includes both operations and management functions (for example, connectivity verification). This control channel is established between the pseudowire's ingress and egress devices. Once established, connectivity verification messages can be sent over the VCCV control channel.

The Junos OS software supports the following VCCV capabilities for LDP signaled VPLS (defined in RFC 5085 Section 8.1):

- VCCV connectivity check types:
 - Router Alert Label
 - MPLS pseudowire label with TTL=1
- VCCV connectivity verification type:
 - LSP ping

If the peer device also advertises VCCV parameters during pseudowire setup, the Junos OS software selects the set of common advertised parameters to use as the method for performing VCCV OAM on the pseudowire.

The locally advertised and peer advertised VCCV parameters can be viewed using the [show ldp database](#) command as show here:

```
user@host> show ldp database l2circuit extensive
Input label database, 10.255.245.198:0--10.255.245.194:0
  Label      Prefix
  299872     L2CKT CtrlWord PPP VC 100
             MTU: 4470
             VCCV Control Channel types:
               MPLS router alert label
               MPLS PW label with TTL=1
             VCCV Control Verification types:
               LSP ping
  Label      Prefix
             State: Active
             Age: 19:23:08
```

Be aware of the following behavior with regard to TLVs when configuring LDP-signaled VPLS in a network with equipment from other vendors:

- When a Juniper Network's device receives a TLV with an empty address, LDP accepts the TLV.
- When a MAC address is withdrawn, LDP specifies a zero address (0.0.0.0) for the AddressList.

To enable LDP signaling for the set of PE routers participating in the same VPLS routing instance, you need to use the `vpls-id` statement configured at the `[edit routing-instances routing-instance-name protocols vpls]` hierarchy level to configure the same VPLS identifier on each of the PE routers. The VPLS identifier must be globally unique. When each VPLS routing instance (domain) has a unique VPLS identifier, it is possible to configure multiple VPLS routing instances between a given pair of PE routers.

LDP signaling requires that you configure a full-mesh LDP session between the PE routers in the same VPLS routing instance. Neighboring PE routers are statically configured. Tunnels are created between the neighboring PE routers to aggregate traffic from one PE router to another. Pseudowires are then signaled to demultiplex traffic between VPLS routing instances. These PE routers exchange the pseudowire label, the MPLS label that acts as the VPLS pseudowire demultiplexer field, by using LDP forwarding equivalence classes (FECs). Tunnels based on both MPLS and generic routing encapsulation (GRE) are supported.

NOTE: You cannot configure both BGP signaling and LDP signaling for the same VPLS routing instance. If you attempt to configure the statements that enable BGP signaling for the VPLS routing instance (the `site`, `site-identifier`, and `site-range` statements), and the statements that enable LDP signaling for the same instance, `neighbor` and `vpls-id`, the commit operation fails.

To enable LDP signaling for the VPLS routing instance, complete the steps in the following sections:

Configuring LDP Signaling for the VPLS Routing Instance

To configure the VPLS routing instance to use LDP signaling, you must configure the same VPLS identifier on each PE router participating in the instance. Specify the VPLS identifier with the `vpls-id` statement:

```
vpls-id vpls-id;
```

You can include this statement at the following hierarchy levels:

- `[edit routing-instances routing-instance-name protocols vpls]`
- `[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls]`

NOTE: ACX Series routers do not support the `[edit logical-systems]` hierarchy.

To configure the VPLS routing instance to use LDP signaling, you also must include the `neighbor` statement to specify each of the neighboring PE routers that are a part of this VPLS domain:

```
neighbor neighbor-id;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

Configuring LDP Signaling on the Router

To enable LDP signaling, you need to configure LDP on each PE router participating in the VPLS routing instance. A minimal configuration is to enable LDP on the loopback interface, which includes the router identifier (*router-id*), on the PE router using the `interface` statement:

```
interface interface-name;
```

You can include this statement at the following hierarchy levels:

- [edit protocols ldp]
- [edit logical-systems *logical-system-name* protocols ldp]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

You can enable LDP on all the interfaces on the router using the `all` option for the `interfaces` statement. For more information about how to configure LDP, see the [MPLS Applications User Guide](#).

Configuring VPLS Routing Instance and VPLS Interface Connectivity

You can configure the VPLS routing instance to take down or maintain its VPLS connections depending on the status of the interfaces configured for the VPLS routing instance. By default, the VPLS connection is taken down whenever a customer-facing interface configured for the VPLS routing

instance fails. This behavior can be explicitly configured by specifying the `ce` option for the `connectivity-type` statement:

```
connectivity-type ce;
```

You can alternatively specify that the VPLS connection remain up so long as an Integrated Routing and Bridging (IRB) interface is configured for the VPLS routing instance by specifying the `irb` option for the `connectivity-type` statement:

```
connectivity-type irb;
```

To ensure that the VPLS connection remain up until explicitly taken down, specify the `permanent` option for the `connectivity-type` statement:

```
connectivity-type permanent;
```

This option is reserved for use in configuring Layer 2 Wholesale subscriber networks. See the *Broadband Subscriber Management Solutions Guide* for details about configuring a Layer 2 Wholesale network.

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

ACX Series routers do not support `irb` interface in VPLS instance, therefore `connectivity-type irb` for VPLS is not supported.

Configuring the VPLS Encapsulation Type

You can specify a VPLS encapsulation type for the pseudowires established between VPLS neighbors. The encapsulation type is carried in the LDP-signaling messages exchanged between VPLS neighbors when pseudowires are created. You might need to alter the encapsulation type depending on what other vendors' equipment is deployed within your network.

VPLS effectively provides a bridge between Ethernet networks. As a consequence, only two encapsulation types are available:

- ethernet—Ethernet
- ethernet-vlan—Ethernet virtual LAN (VLAN)

If you do not specify an encapsulation type for the VPLS routing instance or the VPLS neighbor, ethernet is used.

To specify an encapsulation type for the VPLS routing instance, include the `encapsulation-type` statement:

```
encapsulation-type (ethernet | ethernet-vlan);
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

You can also specify an encapsulation type for a specific VPLS neighbor by including the `encapsulation-type` statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls neighbor *address*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls neighbor *address*]

Configuring the MPLS Routing Table to Leak Routes a Nondefault Routing Instance

Starting in Junos OS Release 16.1, you can specify one or more nondefault routing instances where you want MPLS routes to be leaked from the `mpls.0` path routing table in the primary routing instance. This capability is useful in an L2VPN/VPLS configuration when the remote PE router is learned from the IGP in a nondefault routing instance, because L2VPN/VPLS installs ingress-labeled routes only in the primary `mpls.0` table.

By default, routes in the `mpls.0` routing table in the primary routing instance are not leaked to the corresponding routing tables in nondefault routing instances. When L2VPN/VPLS traffic is received on the core-facing interface in a nondefault routing instance, the router performs a lookup in the table that corresponds to that interface, *routing-instance-name.mpls.0*. Because the routes are not leaked by default, then no routes are found in the *routing-instance-name.mpls.0* routing table and all the incoming traffic is dropped.

To leak MPLS routes to a nondefault routing instance, include the `import-labeled-routes` statement and specify one or more routing instances where the routes need to be leaked:

```
import-labeled-routes [ routing-instance-name ];
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

Configuring the VPLS MAC Table Timeout Interval

You can modify the timeout interval for the VPLS table. We recommend you that configure longer values for small, stable VPLS networks and shorter values for large, dynamic VPLS networks. If the VPLS table does not receive any updates during the timeout interval, the router waits one additional interval before automatically clearing the MAC address entries from the VPLS table.

To modify the timeout interval for the VPLS table, include the `mac-table-aging-time` statement:

```
mac-table-aging-time seconds;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

NOTE: The `mac-table-aging-time` statement is not available on ACX Series and MX Series routers.

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

Configuring the Size of the VPLS MAC Address Table

You can modify the size of the VPLS media access control (MAC) address table. The default table size is 512 MAC addresses, the minimum is 16 addresses, and the maximum is 65,536 addresses.

NOTE: T4000 routers with Type 5 FPCs support up to 262,143 MAC addresses per VPLS routing instance. To enable the improved VPLS MAC address learning limit (that is, 262,143 MAC addresses), you must include the `enhanced-mode` statement at the [edit chassis network-services] hierarchy level, reboot the router, and then modify the size of the VPLS MAC address table.

If the MAC table limit is reached, new MAC addresses can no longer be added to the table. Eventually the oldest MAC addresses are removed from the MAC address table automatically. This frees space in the table, allowing new entries to be added. However, as long as the table is full, new MAC addresses are dropped.

To change the VPLS MAC table size for each VPLS or VPN routing instance, include the `mac-table-size` statement:

```
mac-table-size size;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

When you include the `mac-table-size` statement, the affected interfaces include all interfaces within the VPLS routing instance, including the local interfaces, the LSI interfaces, and the VT interfaces.

NOTE: ACX Series routers do not support `mac-table-size` statement for VPLS.

Limiting the Number of MAC Addresses Learned from an Interface

You can configure a limit on the number of MAC addresses learned by a VPLS routing instance using the `mac-table-size` statement. If the MAC table limit is reached, new MAC addresses can no longer be added to the table. Eventually the oldest MAC addresses are removed from the MAC address table automatically. This frees space in the table, allowing new entries to be added. However, as long as the table is full, new MAC addresses are dropped.

Because this limit applies to each VPLS routing instance, the MAC addresses of a single interface can consume all the available space in the table, preventing the routing instance from acquiring addresses from other interfaces.

You can limit the number of MAC addresses learned from each interface configured for a VPLS routing instance. To do so, include the `interface-mac-limit` statement:

```
interface-mac-limit limit;
```

NOTE: ACX Series routers do not support *interface-mac-limit limit* for VPLS.

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]

The *interface-mac-limit* statement affects the local interfaces only (the interfaces facing CE devices).

Configuring the *interface-mac-limit* statement at the [edit routing-instances *routing-instance-name* protocols vpls] hierarchy level causes the same limit to be applied to all of the interfaces configured for that specific routing instance.

NOTE: Starting in Junos OS Release 12.3R4, if you do not configure the parameter to limit the number of MAC addresses to be learned by a VPLS instance, the default value is not effective. Instead, if you do not include the *interface-mac-limit* option at the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls site *site-name* interfaces *interface-name*], hierarchy level, this setting is not present in the configuration with the default value of 1024 addresses. If you upgrade a router running a Junos OS release earlier than Release 12.3R4 to Release 12.3R4 or later, you must configure the *interface-mac-limit* option with a valid value for it to be saved in the configuration.

You can also limit the number of MAC addresses learned by a specific interface configured for a VPLS routing instance. This gives you the ability to limit particular interfaces that you expect might generate a lot of MAC addresses.

To limit the number of MAC addresses learned by a specific interface, include the *interface-mac-limit* statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls site *site-name* interfaces *interface-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls site *site-name* interfaces *interface-name*]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

The MAC limit configured for an individual interface at this hierarchy level overrides any value configured at the [edit routing-instances *routing-instance-name* protocols vpls] hierarchy level. Also, the MAC

limit configured using the `mac-table-size` statement can override the limit configured using the `interface-mac-limit` statement.

The MAC address limit applies to customer-facing interfaces only.

Removing Addresses from the MAC Address Database

You can enable MAC flush processing for the VPLS routing instance or for the mesh group under a VPLS routing instance. MAC flush processing removes MAC addresses from the MAC address database that have been learned dynamically. With the dynamically learned MAC addresses removed, MAC address convergence requires less time to complete.

You can clear dynamically learned MAC addresses from the MAC address database by including the `mac-flush` statement:

```
mac-flush [ explicit-mac-flush-message-options ];
```

To clear dynamically learned MAC addresses globally across all devices participating in the routing instance, you can include the statement at the following hierarchy levels:

- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]
- [edit routing-instances *routing-instance-name* protocols vpls]

To clear the MAC addresses on the routers in a specific mesh group, you can include the statement at the following hierarchy levels:

- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name*]
- [edit routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name*]

NOTE: On ACX Series routers, the `mesh-group` statement is supported only on ACX5000 line of routers. ACX5000 line of routers can support up to 8 user-defined mesh groups per VPLS routing instance.

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

For certain cases where MAC flush processing is not initiated by default, you can also specify *explicit-mac-flush-message-options* to additionally configure the router to send explicit MAC flush messages under

specific conditions. For a list of the explicit MAC flush message options you can include with this statement, see the summary section for this statement.

Release History Table

Release	Description
16.1	Starting in Junos OS Release 16.1, you can specify one or more nondefault routing instances where you want MPLS routes to be leaked from the mpls.0 path routing table in the primary routing instance.
12.3R4	Starting in Junos OS Release 12.3R4, if you do not configure the parameter to limit the number of MAC addresses to be learned by a VPLS instance, the default value is not effective.

RELATED DOCUMENTATION

[Configuring Improved VPLS MAC Address Learning on T4000 Routers with Type 5 FPCs | 1220](#)
[enhanced-mode](#)
[show ldp database](#)

Configuring a VPLS Routing Instance

Use the **vpls** routing instance type for point-to-multipoint LAN implementations between a set of sites in a VPN.

To create a routing instance for VPLS, include at least the following statements in the configuration:

```
routing-instances {
  routing-instance-name {
    instance-type vpls;
    interface interface-name;
    route-distinguisher (as-number:number | ip-address:number);
    vrf-import [ policy-names ];
    vrf-export [ policy-names ];
    protocols {
      vpls {
        ... vpls configuration ...
      }
    }
  }
}
```

```
}
}
```

You can include these statements at the following hierarchy levels:

- [edit]
- [edit logical-systems *logical-system-name*]

For more information about configuring VPLS, see the [Junos OS VPNs Library for Routing Devices](#).

RELATED DOCUMENTATION

[Layer 2 Routing Instance Types](#)

[Configuring a Virtual Switch Routing Instance on MX Series Routers](#)

[Configuring a Layer 2 Control Protocol Routing Instance](#) | 697

Support of Inner VLAN List and Inner VLAN Range for Qualified BUM Pruning on a Dual-Tagged Interface for a VPLS Routing Instance Overview

Junos OS provides the `qualified-bum-pruning-mode` statement, which supports constraining of broadcast, multicast, and unknown (BUM) traffic in a VPLS instance to a specific subscriber VLAN stack. This cuts down unnecessary consumption of bandwidth and thereby, improves network performance.

All subscriber VLANs that need to be backhauled to their respective retail-ISPs are also created in the same VPLS instance as the retail-ISP. Each retail-ISP is allocated a VPLS instance. Any traffic on subscriber VLANs is hauled over the VPLS tunnel to the retail-ISP. Similarly, any traffic from a retail-ISP on a VPLS tunnel is forwarded to all the subscriber VLANs in that VPLS instance. For multicast traffic (which includes broadcast, unknown DMAC, and layer 2 and layer 3 multicast), the standard Layer-2 VPLS instance-forwarding creates a BUM packet, which comes from a retail-ISP over a VPLS tunnel, to be flooded to all subscriber VLANs in the VPLS instance. This causes the individual subscribers who might have subscribed to specific multicast traffic channels to receive all the traffic instead of the multicast traffic that the subscriber has signed up for.

To overcome this, BUM traffic needs to be forwarded only to subscribers who are the intended recipients, by mapping the VLAN-tags present in the BUM packet to these subscribers. A subscriber is assigned a stacked VLAN-tag and BUM packets are sent only to a subscriber whose stacked VLAN-tags match the VLAN-tags present in the BUM packet. This ensures that subscribers receive only the BUM traffic that is specifically intended for them, which prevents the normal flooding of BUM traffic. This is

called *BUM-pruning*. Hitherto, Junos OS supported only single VLAN tagged and dual VLAN tagged subscriber interfaces. This implies that for each subscriber, a different interface must be configured. Such a BUM-pruning solution does not scale well. To address this issue, Junos OS now supports configuring VLAN ranges on the subscriber interfaces. This enables better management of subscriber services.

BUM-pruning on Junos OS allows subscriber interfaces to be configured with inner-vlan-lists. Each inner VLAN list includes all the subscriber VLANs that must be grouped on a particular subscriber interface mapped to a VPLS instance. You can configure BUM-pruning on each VPLS instance allocated to a retail-ISP by using the `set routing-instances routing-instance-name qualified-bum-pruning-mode` command.

For normal VPLS flooding, BUM traffic is received over the VPLS tunnel and flooded to all the subscriber interfaces mapped to the vpls-instance. These interfaces might be or might not be mapped to the same subscriber VLAN as the packet received over the VPLS tunnel. By enabling the qualified BUM pruning mode in a VPLS instance, VPLS flooding is restricted to a combination of service-provider VLAN and subscriber VLAN. The `qualified-bum-pruning` statement implements BUM-pruning on the Packet Forwarding Engine in the egress list of each subscriber interface mapped to the VPLS instance. On the Packet Forwarding Engine, BUM-pruning is implemented as a `vlan-check` nexthop installed in the egress list of the subscriber interface. The `vlan-check` nexthop checks whether the BUM packet exiting the ifl has the same combination of service-provider VLAN and subscriber VLAN as that configured on the interface. If the VLAN check matches, the packet is forwarded or else it is discarded. This ensures that only the subscriber that is the intended recipient of the BUM traffic receives the packet. This feature is supported for both single-tagged and dual-tagged subscriber interfaces as well as for subscriber interfaces configured with `vlan-map` operations. If `vlan-map` operations are configured on the interfaces, then the normalized VLAN on the interface is considered for the `vlan-check` nexthop. This feature is supported for both default and logical systems.

Currently, dual-tagged subscriber interfaces can support a single pair of service-provider VLAN and subscriber VLAN. With the support for BUM-pruning of VPLS traffic on dual-tagged interfaces, you can configure a single service provider VLAN(S) on the subscriber interface and map it to multiple customer VLANs using a single inner VLAN list or inner VLAN range. The inner VLAN list on a subscriber interface can have multiple elements. Each element of the inner VLAN list can be as follows:

- A single VLAN tag
- A range of VLANs

The BUM traffic flow through dual-tagged interfaces is supported on both aggregated and non-aggregated subscriber interfaces. When BUM traffic exits a subscriber interface configured with inner VLAN list or inner VLAN range, the service provider VLAN (S) and the subscriber VLAN (C) in the packet are checked against all combinations of (S,C) of the S and C VLANs possible on the interface. If the packet matches any of the combination, it is forwarded on the subscriber interface. If the packet does not match any combination, it is discarded. If the subscriber has `vlan-map` configured, then the S and C VLANs to be checked are modified based on the VLAN normalization on the interface.

RELATED DOCUMENTATION

[qualified-bum-pruning-mode](#) | 1646

[vlan-tags \(Stacked VLAN Tags\)](#) | 1713

Configuring Qualified BUM Pruning for a Dual-Tagged Interface with Inner VLAN list and InnerVLAN range for a VPLS Routing Instance

Currently, dual-tagged subscriber interfaces can support a single pair of service-provider VLAN and subscriber VLAN. With the support for broadcast, unknown unicast, multicast (BUM) pruning of VPLS traffic on dual-tagged interfaces, you can configure a single service provider VLAN— referred to as VLAN(S) in this topic —on the subscriber interface and map it to multiple customer VLANs by using a single inner VLAN list or inner VLAN range. The inner VLAN list on a subscriber interface can have multiple elements. Each element of the inner VLAN list can be a single VLAN tag or a range of VLANs. The BUM traffic flow through dual-tagged interfaces is supported on both aggregated and nonaggregated subscriber interfaces. When BUM traffic exits a subscriber interface that has an inner VLAN list or range configured, the VLAN(S) and the subscriber VLAN— referred to as VLAN(C)— in the packet are checked against all combinations of VLAN(S) and VLAN(C) possible on the interface. If the packet contents match any of the combinations, then the packet is forwarded on the subscriber interface. If the contents do not match any combination, then the packet is discarded. If the subscriber has a VLAN map configured, then the VLAN(S) and VLAN(C) to be checked are modified based on the VLAN normalization on the interface.

Before you configure qualified BUM pruning for a dual-tagged interface including inner VLAN list and inner VLAN range for a VPLS routing instance, you must do the following:

1. Configure the device interfaces.
2. Configure the VPLS routing instance.

To configure qualified-bum-pruning for dual tagged interface including inner VLAN list and inner VLAN range for a VPLS routing instance:

1. Configure a member interface with a service provider VLAN for the VPLS routing instance. You can configure service provider VLAN with an inner VLAN list or inner VLAN range for the VPLS routing instance.

```
[edit interfaces interface-name unit unit-number vlan-tags]
user@host# set outer vlan-id
```

For example, to configure member interface with the service provider VLAN ID 200 for a VPLS routing instance:

```
[edit interfaces ae0 unit 100 vlan-tags]
user@host# set outer 200
```

2. Configure the `inner-list` of the member interface with a single customer VLAN ID or a range of customer VLAN IDs or both for a VPLS routing instance.

```
[edit interfaces interface-name unit unit-number vlan-tags]
user@host# set inner-list [vlan-id]
```

For example, to configure the member interface with a single customer VLAN ID and a range of customer VLAN IDs for a VPLS routing instance:

```
[edit interfaces ae0 unit 100 vlan-tags]
user@host# set inner-list [210 -215 216]
```

3. Configure the member interface with inner VLAN ID range.

```
[edit interfaces interface-name unit unit-number vlan-tags]
user@host# set inner-range vlan-range
```

For example, to configure the member interface with an inner range of 300-310 for VPLS routing instance:

```
[edit interfaces ae6 unit 500 vlan-tags]
user@host# set inner-range 300-310
```

4. Configure BUM pruning for VPLS traffic on dual-tagged interfaces to forward the BUM traffic only to the intended member interfaces.

```
[edit routing-instance VPLS routing-instance]
user@host# set qualified-bum-pruning-mode
```

For example, to configure qualified BUM pruning for routing instance r1:

```
[edit routing-instance r1]
user@host# set qualified-bum-pruning-mode
```

RELATED DOCUMENTATION

[Support of Inner VLAN List and Inner VLAN Range for Qualified BUM Pruning on a Dual-Tagged Interface for a VPLS Routing Instance Overview | 693](#)

[qualified-bum-pruning-mode | 1646](#)

[vlan-tags \(Stacked VLAN Tags\) | 1713](#)

Configuring a Layer 2 Control Protocol Routing Instance

On MX Series routers only, use the **layer2-control** routing instance type for Rapid Spanning-Tree Protocol (RSTP) or Multiple Spanning-Tree Protocol (MSTP) in customer edge interfaces of a VPLS routing instance. Layer 2 control protocols enable features such as Layer 2 protocol tunneling or nonstop bridging. This instance type cannot be used if the customer edge interface is multihomed to two provider edge interfaces. If the customer edge interface is multihomed to two provider edge interfaces, use the default bridge protocol data unit (BPDU) tunneling.

To create a routing instance for Layer 2 control protocols, include at least the following statements in the configuration:

```
routing-instances {
  routing-instance-name {
    instance-type layer2-control;
    interface interface-name;
    route-distinguisher (as-number:number | ip-address:number);
    vrf-import [ policy-names ];
    vrf-export [ policy-names ];
    protocols {
      mstp {
        ... interface options ...
        msti msti-id {
          ... MSTP MSTI configuration ...
        }
      }
    }
  }
}
```

```

    }
  }
}

```

You can include these statements at the following hierarchy levels:

- [edit]
- [edit logical-systems *logical-system-name*]

RELATED DOCUMENTATION

[Layer 2 Routing Instance Types](#)

[Configuring a VPLS Routing Instance | 692](#)

[Configuring a Virtual Switch Routing Instance on MX Series Routers](#)

PE Router Mesh Groups for VPLS Routing Instances

A PE router mesh group consists of a set of routers participating in a VPLS routing instance that share the same signaling protocol, either BGP or LDP. Each VPLS routing instance can have just one BGP mesh group. However, you can configure multiple LDP mesh groups for each routing instance.

The Junos OS can support up to 16 mesh groups on MX Series routers and up to 128 on M Series and T Series routers. However, two mesh groups are created by default, one for the CE routers and one for the PE routers. Therefore, the maximum number of user-defined mesh groups is 14 for MX Series routers and 126 for M Series and T Series routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The Junos OS supports both forwarding equivalency class (FEC) 128 and FEC 129. FEC 129 uses VPLS autodiscovery to convey endpoint information. FEC 128 requires manually configured pseudowires.

The following describes the behavior of mesh groups in regards to BGP-signaled PE routers and LDP-signaled PE routers:

- BGP-signaled PE routers—Automatically discovered PE routers that use BGP for signaling are associated with the default VE mesh group. You cannot configure the Junos OS to associate these routers with a user-defined VE mesh group.

- LDP-signaled PE routers (FEC 128)—PE routers statically configured using FEC-128 LDP signaling are placed in a default mesh group. However, you can configure a VE mesh group and associate each LDP FEC-128 neighbor with it. Each configured VE mesh group contains a set of VEs that are in the same interior gateway protocol (IGP) routing instance and are fully meshed with each other in the control and data planes.
- LDP-signaled PE routers (FEC 129)—Configuration for a mesh group for FEC 129 is very similar to the configuration for FEC 128.

Note the following differences for FEC 129:

- Each user-defined mesh group must have a unique route distinguisher. Do not use the route distinguisher that is defined for the default mesh group at the [edit routing-instances] hierarchy level.
- Each user-defined mesh group must have its own import and export route target.
- Each user-defined mesh group can have a unique Layer 2 VPN ID. By default, all the mesh groups that are configured for the a VPLS routing-instance use the same Layer 2 VPN ID, the one that you configure at the [edit routing-instances] hierarchy level.

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS](#) | 909

Configuring VPLS Fast Reroute Priority

When a path is rerouted after a link failure by using the MPLS fast reroute feature, the router repairs the affected next hops by switching them from the active label switched path (LSP) to the standby LSP. To specify the order in which the router repairs next hops and restores traffic convergence for VPLS routing instances after a fast reroute event, you can use the `fast-reroute-priority` statement to configure `high`, `medium`, or `low` fast reroute priority for a VPLS routing instance. By default, the fast reroute priority for a VPLS routing instance is `low`.

The router repairs next hops and restores known unicast, unknown unicast, broadcast, and multicast traffic for VPLS routing instances in the following order, based on the fast reroute priority configuration:

1. The router repairs next hops for high-priority VPLS routing instances.
2. The router repairs next hops for medium-priority VPLS routing instances.
3. The router repairs next hops for low-priority VPLS routing instances.

Because the router repairs next hops for VPLS routing instances configured with high fast reroute priority first, the traffic traversing high-priority VPLS instances is restored faster than the traffic for VPLS instances configured with medium or low fast reroute priority. The ability to prioritize specific VPLS routing instances for faster convergence and traffic restoration enables service providers to offer differentiated service levels to their customers.

Within a particular fast reroute priority level (high, medium, or low), the router follows no particular order for traffic restoration of VPLS routing instances.

NOTE: VPLS fast reroute priority is not supported on EX Series switches.

To configure high, medium, or low fast reroute priority for a VPLS routing instance, include the `fast-reroute-priority` statement:

```
fast-reroute-priority (high | medium | low);
```

You can include this statement at the following hierarchy levels:

- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options]
- [edit routing-instances *routing-instance-name* forwarding-options]

You can configure fast reroute priority only for routing instances with the `instance-type` set to `vpls`. If you attempt to configure fast reroute priority for a routing instance with an `instance-type` other than `vpls`, the router displays a warning message and the configuration fails.

The following example snippet shows configuration of high fast reroute priority for a VPLS routing instance named `test-vpls`:

```
test-vpls {
  instance-type vpls;
  forwarding-options {
    fast-reroute-priority high;
  }
}
```

To display the fast reroute priority setting configured for a VPLS routing instance, use the `show route instance detail operational` command. For information about using this command, see the [CLI Explorer](#).

Specifying the VT Interfaces Used by VPLS Routing Instances

By default, the Junos OS automatically selects one of the virtual tunnel (VT) interfaces available to the router for de-encapsulating traffic from a remote site. The Junos OS cycles through the currently available VT interfaces, regularly updating the list of available VT interfaces as new remote sites are discovered and new connections are brought up. However, you can also explicitly configure which VT interfaces will receive the VPLS traffic.

By including the `tunnel-services` statement at the `[edit routing-instances routing-instance-name protocols vpls]` hierarchy level, you can specify that traffic for particular VPLS routing instances be forwarded to specific VT interfaces. Doing so allows you to load-balance VPLS traffic among all the available VT interfaces on the router.

The `tunnel-services` statement includes the following options:

- `devices`—Specifies the VT interfaces acceptable for use by the VPLS routing instance. If you do not configure this option, all VT interfaces available to the router can be used for de-encapsulating traffic for this instance.
- `primary`—Specifies the primary VT interface to be used by the VPLS routing instance. The VT interface specified is used to de-encapsulate all VPLS traffic from the MPLS core network for this routing instance. If the VT interface specified is unavailable, then one of the other acceptable VT interfaces (specified in the `devices` option) is used for handling the VPLS traffic. If you do not configure this option, any acceptable VT interface can be used to de-encapsulate VPLS traffic from the core.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

To specify that traffic for a particular VPLS routing instance be forwarded to specific VT interfaces, include the `tunnel-services` statement:

```
tunnel-services {
    devices device-names;
    primary primary-device-name;
}
```

These statements can be configured at the following hierarchy levels:

- `[edit routing-instances routing-instance-name protocols vpls]`
- `[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls]`

Understanding PIM Snooping for VPLS

There are two ways to direct PIM control packets:

- By the use of PIM snooping
- By the use of PIM proxying

PIM snooping configures a device to examine and operate only on PIM hello and join/prune packets. A PIM snooping device snoops PIM hello and join/prune packets on each interface to find interested multicast receivers and populates the multicast forwarding tree with this information. PIM snooping differs from PIM proxying in that both PIM hello and join/prune packets are transparently flooded in the VPLS as opposed to the flooding of only hello packets in the case of PIM proxying. PIM snooping is configured on PE routers connected through pseudowires. PIM snooping ensures that no new PIM packets are generated in the VPLS, with the exception of PIM messages sent through LDP on pseudowires.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

A device that supports PIM snooping snoops hello packets received on attachment circuits. It does not introduce latency in the VPLS core when it forwards PIM join/prune packets.

To configure PIM snooping on a PE router, use the `pim-snooping` statement at the `[edit routing-instances instance-name protocols]` hierarchy level:

```
routing-instances {
  customer {
    instance-type vpls;
    ...
    protocols {
      pim-snooping{
        traceoptions {
          file pim.log size 10m;
          flag all;
          flag timer disable;
        }
      }
    }
  }
}
```

Example: Configuring PIM Snooping for VPLS explains the PIM snooping method. The use of the PIM proxying method is not discussed here and is outside the scope of this document. For more information about PIM proxying, see [PIM Snooping over VPLS](#).

Example: Configuring PIM Snooping for VPLS

IN THIS SECTION

- [Requirements | 703](#)
- [Overview | 703](#)
- [Configuration | 705](#)
- [Verification | 714](#)

This example shows how to configure PIM snooping in a virtual private LAN service (VPLS) to restrict multicast traffic to interested devices.

Requirements

This example uses the following hardware and software components:

- M Series Multiservice Edge Routers (M7i and M10i with Enhanced CFEB, M120, and M320 with E3 FPCs) or MX Series 5G Universal Routing Platforms (MX80, MX240, MX480, and MX960)
- Junos OS Release 13.2 or later

Overview

IN THIS SECTION

- [Topology | 704](#)

The following example shows how to configure PIM snooping to restrict multicast traffic to interested devices in a VPLS.

NOTE: This example demonstrates PIM snooping by the use of a PIM snooping device to restrict multicast traffic. The use of the PIM proxying method to achieve PIM snooping is out of the scope of this document and is yet to be implemented in Junos OS.


Topology

In this example, two PE routers are connected to each other through a pseudowire connection. Router PE1 is connected to Routers CE1 and CE2. A multicast receiver is attached to Router CE2. Router PE2 is connected to Routers CE3 and CE4. A multicast source is connected to Router CE3, and a second multicast receiver is attached to Router CE4.

PIM snooping is configured on Routers PE1 and PE2. Hence, data sent from the multicast source is received only by members of the multicast group.

Figure 52 on page 704 shows the topology used in this example.

Figure 52: PIM Snooping for VPLS



Configuration

IN THIS SECTION

- [CLI Quick Configuration | 705](#)
- [Configuring PIM Snooping for VPLS | 708](#)
- [Results | 711](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Router PE1

```
set multicast-snooping-options traceoptions file snoop.log size 10m
set interfaces ge-2/0/0 encapsulation ethernet-vpls
set interfaces ge-2/0/0 unit 0 description toCE1
set interfaces ge-2/0/1 encapsulation ethernet-vpls
set interfaces ge-2/0/1 unit 0 description toCE2
set interfaces ge-2/0/2 unit 0 description toPE2
set interfaces ge-2/0/2 unit 0 family inet address 10.0.0.1/30
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.1.1/32
set routing-options router-id 10.255.1.1
set protocols mpls interface ge-2/0/1.0
set protocols bgp group toPE2 type internal
set protocols bgp group toPE2 local-address 10.255.1.1
set protocols bgp group toPE2 family l2vpn signaling
set protocols bgp group toPE2 neighbor 10.255.7.7
set protocols ospf area 0.0.0.0 interface ge-2/0/2.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface ge-2/0/2.0
set protocols ldp interface lo0.0
set routing-instances titanium instance-type vpls
set routing-instances titanium vlan-id none
set routing-instances titanium interface ge-2/0/0.0
set routing-instances titanium interface ge-2/0/1.0
```

```

set routing-instances titanium route-distinguisher 101:101
set routing-instances titanium vrf-target target:201:201
set routing-instances titanium protocols vpls vpls-id 15
set routing-instances titanium protocols vpls site pe1 site-identifier 1
set routing-instances titanium protocols pim-snooping

```

Router CE1

```

set interfaces ge-2/0/0 unit 0 description toPE1
set interfaces ge-2/0/0 unit 0 family inet address 10.0.0.10/30
set interfaces lo0 unit 0 family inet address 10.255.2.2/32
set routing-options router-id 10.255.2.2
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols pim rp static address 10.255.3.3
set protocols pim interface all

```

Router CE2

```

set interfaces ge-2/0/0 unit 0 description toPE1
set interfaces ge-2/0/0 unit 0 family inet address 10.0.0.6/30
set interfaces ge-2/0/1 unit 0 description toReceiver1
set interfaces ge-2/0/1 unit 0 family inet address 10.0.0.13/30
set interfaces lo0 unit 0 family inet address 10.255.2.2
set routing-options router-id 10.255.2.2
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols pim rp static address 10.255.3.3
set protocols pim interface all

```

Router PE2

```

set multicast-snooping-options traceoptions file snoop.log size 10m
set interfaces ge-2/0/0 encapsulation ethernet-vpls
set interfaces ge-2/0/0 unit 0 description toCE3
set interfaces ge-2/0/1 encapsulation ethernet-vpls
set interfaces ge-2/0/1 unit 0 description toCE4
set interfaces ge-2/0/2 unit 0 description toPE1
set interfaces ge-2/0/2 unit 0 family inet address 10.0.0.2/30
set interfaces ge-2/0/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.7.7/32

```

```

set routing-options router-id 10.255.7.7
set protocols mpls interface ge-2/0/2.0
set protocols bgp group toPE1 type internal
set protocols bgp group toPE1 local-address 10.255.7.7
set protocols bgp group toPE1 family l2vpn signaling
set protocols bgp group toPE1 neighbor 10.255.1.1
set protocols ospf area 0.0.0.0 interface ge-2/0/2.0
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ldp interface ge-2/0/2.0
set protocols ldp interface lo0.0
set routing-instances titanium instance-type vpls
set routing-instances titanium vlan-id none
set routing-instances titanium interface ge-2/0/0.0
set routing-instances titanium interface ge-2/0/1.0
set routing-instances titanium route-distinguisher 101:101
set routing-instances titanium vrf-target target:201:201
set routing-instances titanium protocols vpls vpls-id 15
set routing-instances titanium protocols vpls site pe2 site-identifier 2
set routing-instances titanium protocols pim-snooping

```

Router CE3 (RP)

```

set interfaces ge-2/0/0 unit 0 description toPE2
set interfaces ge-2/0/0 unit 0 family inet address 10.0.0.18/30
set interfaces ge-2/0/1 unit 0 description toSource
set interfaces ge-2/0/1 unit 0 family inet address 10.0.0.29/30
set interfaces lo0 unit 0 family inet address 10.255.3.3/32
set routing-options router-id 10.255.3.3
set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols pim rp local address 10.255.3.3
set protocols pim interface all

```

Router CE4

```

set interfaces ge-2/0/0 unit 0 description toPE2
set interfaces ge-2/0/0 unit 0 family inet address 10.0.0.22/30
set interfaces ge-2/0/1 unit 0 description toReceiver2
set interfaces ge-2/0/1 unit 0 family inet address 10.0.0.25/30
set interfaces lo0 unit 0 family inet address 10.255.4.4/32
set routing-options router-id 10.255.4.4

```

```

set protocols ospf area 0.0.0.0 interface all
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols pim rp static address 10.255.3.3
set protocols pim interface all

```

Configuring PIM Snooping for VPLS

Step-by-Step Procedure

The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

NOTE: This section includes a step-by-step configuration procedure for one or more routers in the topology. For comprehensive configurations for all routers, see "[CLI Quick Configuration](#)" on [page 705](#).

To configure PIM snooping for VPLS:

1. Configure the router interfaces forming the links between the routers.

Router PE2

```

[edit interfaces]
user@PE2# set ge-2/0/0 encapsulation ethernet-vpls
user@PE2# set ge-2/0/0 unit 0 description toCE3
user@PE2# set ge-2/0/1 encapsulation ethernet-vpls
user@PE2# set ge-2/0/1 unit 0 description toCE4
user@PE2# set ge-2/0/2 unit 0 description toPE1
user@PE2# set ge-2/0/2 unit 0 family mpls
user@PE2# set ge-2/0/2 unit 0 family inet address 10.0.0.2/30
user@PE2# set lo0 unit 0 family inet address 10.255.7.7/32

```

NOTE: ge-2/0/0.0 and ge-2/0/1.0 are configured as VPLS interfaces and connect to Routers CE3 and CE4. See *Virtual Private LAN Service User Guide* for more details.

Router CE3

```

[edit interfaces]

```

```

user@CE3# set ge-2/0/0 unit 0 description toPE2
user@CE3# set ge-2/0/0 unit 0 family inet address 10.0.0.18/30
user@CE3# set ge-2/0/1 unit 0 description toSource
user@CE3# set ge-2/0/1 unit 0 family inet address 10.0.0.29/30
user@CE3# set lo0 unit 0 family inet address 10.255.3.3/32

```

NOTE: The ge-2/0/1.0 interface on Router CE3 connects to the multicast source.

Router CE4

```

[edit interfaces]
user@CE4# set ge-2/0/0 unit 0 description toPE2
user@CE4# set ge-2/0/0 unit 0 family inet address 10.0.0.22/30
user@CE4# set ge-2/0/1 unit 0 description toReceiver2
user@CE4# set ge-2/0/1 unit 0 family inet address 10.0.0.25/30
user@CE4# set lo0 unit 0 family inet address 10.255.4.4/32

```

NOTE: The ge-2/0/1.0 interface on Router CE4 connects to a multicast receiver.

Similarly, configure Routers PE1, CE1, and CE2.

2. Configure the router IDs of all routers.

Router PE2

```

[edit routing-options]
user@PE2# set router-id 10.255.7.7

```

Similarly, configure other routers.

3. Configure an IGP on interfaces of all routers.

Router PE2

```

[edit protocols ospf area 0.0.0.0]
user@PE2# set interface ge-2/0/2.0
user@PE2# set interface lo0.0

```

Similarly, configure other routers.

4. Configure the LDP, MPLS, and BGP protocols on the PE routers.

```

Router PE2
[edit protocols]
user@PE2# set ldp interface lo0.0
user@PE2# set mpls interface ge-2/0/2.0
user@PE2# set bgp group toPE1 type internal
user@PE2# set bgp group toPE1 local-address 10.255.7.7
user@PE2# set bgp group toPE1 family l2vpn signaling
user@PE2# set bgp group toPE1 neighbor 10.255.1.1
user@PE2# set ldp interface ge-2/0/2.0

```

The BGP group is required for interfacing with the other PE router. Similarly, configure Router PE1.

5. Configure PIM on all CE routers.

Ensure that Router CE3 is configured as the rendezvous point (RP) and that the RP address is configured on other CE routers.

```

Router CE3
[edit protocols pim]
user@CE3# set rp local address 10.255.3.3
user@CE3# set interface all

```

```

Router CE4
[edit protocols pim]
user@CE4# set rp static address 10.255.3.3
user@CE4# set interface all

```

Similarly, configure Routers CE1 and CE2.

6. Configure multicast snooping options on the PE routers.

```

Router PE2
[edit multicast-snooping-options traceoptions]
user@PE2# set file snoop.log size 10m

```

Similarly, configure Router PE1.

7. Create a routing instance (titanium), and configure the VPLS on the PE routers.

```

Router PE2
[edit routing-instances titanium]
user@PE2# set instance-type vpls
user@PE2# set vlan-id none
user@PE2# set interface ge-2/0/0.0
user@PE2# set interface ge-2/0/1.0
user@PE2# set route-distinguisher 101:101
user@PE2# set vrf-target target:201:201
user@PE2# set protocols vpls vpls-id 15
user@PE2# set protocols vpls site pe2 site-identifier 2

```

Similarly, configure Router PE1.

8. Configure PIM snooping on the PE routers.

```

Router PE2
[edit routing-instances titanium]
user@PE2# set protocols pim-snooping

```

Similarly, configure Router PE1.

Results

From configuration mode, confirm your configuration by entering the **show interfaces**, **show routing-options**, **show protocols**, **show multicast-snooping-options**, and **show routing-instances** commands.

If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE2# show interfaces
ge-2/0/2 {
  unit 0 {
    description toPE1
    family inet {
      address 10.0.0.2/30;
    }
    family mpls;
  }
}

```

```

ge-2/0/0 {
    encapsulation ethernet-vpls;
    unit 0 {
        description toCE3;
    }
}
ge-2/0/1 {
    encapsulation ethernet-vpls;
    unit 0 {
        description toCE4;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.255.7.7/32;
        }
    }
}

```

```

user@PE2# show routing-options
router-id 10.255.7.7;

```

```

user@PE2# show protocols
mpls {
    interface ge-2/0/2.0;
}
ospf {
    area 0.0.0.0 {
        interface ge-2/0/2.0;
        interface lo0.0;
    }
}
ldp {
    interface ge-2/0/2.0;
    interface lo0.0;
}
bgp {
    group toPE1 {
        type internal;
    }
}

```

```

    local-address 10.255.7.7;
    family l2vpn {
        signaling;
    }
    neighbor 10.255.1.1;
}

```

```

user@PE2# show multicast-snooping-options
traceoptions {
    file snoop.log size 10m;
}

```

```

user@PE2# show routing-instances
titanium {
    instance-type vpls;
    vlan-id none;
    interface ge-2/0/0.0;
    interface ge-2/0/1.0;
    route-distinguisher 101:101;
    vrf-target target:201:201;
    protocols {
        vpls {
            site pe2 {
                site-identifier 2;
            }
            vpls-id 15;
        }
        pim-snooping;
    }
}

```

Similarly, confirm the configuration on all other routers. If you are done configuring the routers, enter `commit` from configuration mode.

NOTE: Use the `show protocols` command on the CE routers to verify the configuration for the PIM RP .

Verification

IN THIS SECTION

- [Verifying PIM Snooping for VPLS | 714](#)

Confirm that the configuration is working properly.

Verifying PIM Snooping for VPLS

Purpose

Verify that PIM Snooping is operational in the network.

Action

To verify that PIM snooping is working as desired, use the following commands:

- `show pim snooping interfaces`
- `show pim snooping neighbors detail`
- `show pim snooping statistics`
- `show pim snooping join`
- `show pim snooping join extensive`
- `show multicast snooping route extensive instance <instance-name> group <group-name>`

1. From operational mode on Router PE2, run the `show pim snooping interfaces` command.

```
user@PE2> show pim snooping interfaces
Instance: titanium

Learning-Domain: default

Name                State IP NbrCnt
ge-2/0/0.0          Up   4     1
ge-2/0/1.0          Up   4     1
```

```
DR address: 10.0.0.22
DR flooding is ON
```

The output verifies that PIM snooping is configured on the two interfaces connecting Router PE2 to Routers CE3 and CE4.

Similarly, check the PIM snooping interfaces on Router PE1.

2. From operational mode on Router PE2, run the **show pim snooping neighbors detail** command.

```
user@PE2> show pim snooping neighbors detail
Instance: titanium
Learning-Domain: default

Interface: ge-2/0/0.0

  Address: 10.0.0.18
    Uptime: 00:17:06
    Hello Option Holdtime: 105 seconds 99 remaining
    Hello Option DR Priority: 1
    Hello Option Generation ID: 552495559
    Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
                                Tracking is supported

Interface: ge-2/0/1.0

  Address: 10.0.0.22
    Uptime: 00:15:16
    Hello Option Holdtime: 105 seconds 103 remaining
    Hello Option DR Priority: 1
    Hello Option Generation ID: 1131703485
    Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
                                Tracking is supported
```

The output verifies that Router PE2 can detect the IP addresses of its PIM snooping neighbors (10.0.0.18 on CE3 and 10.0.0.22 on CE4).

Similarly, check the PIM snooping neighbors on Router PE1.

3. From operational mode on Router PE2, run the **show pim snooping statistics** command.

```
user@PE2> show pim snooping statistics
Instance: titanium
```

```

Learning-Domain: default

Tx J/P messages                0
RX J/P messages                246
Rx J/P messages -- seen        0
Rx J/P messages -- received    246
Rx Hello messages              1036
Rx Version Unknown             0
Rx Neighbor Unknown            0
Rx Upstream Neighbor Unknown   0
Rx J/P Busy Drop               0
Rx J/P Group Aggregate          0
Rx Malformed Packet            0

Rx No PIM Interface            0
Rx Bad Length                  0
Rx Unknown Hello Option        0
Rx Unknown Packet Type         0
Rx Bad TTL                     0
Rx Bad Destination Address      0
Rx Bad Checksum                 0
Rx Unknown Version             0

```

The output shows the number of hello and join/prune messages received by Router PE2. This verifies that PIM sparse mode is operational in the network.

4. Send multicast traffic from the source terminal attached to Router CE3, for the multicast group 203.0.113.1.
5. From operational mode on Router PE2, run the **show pim snooping join**, **show pim snooping join extensive**, and **show multicast snooping route extensive instance <instance-name> group <group-name>** commands to verify PIM snooping.

```

user@PE2> show pim snooping join
Instance: titanium
Learning-Domain: default

Group: 203.0.113.1
  Source: *
  Flags: sparse,rptree,wildcard
  Upstream neighbor: 10.0.0.18, Port: ge-2/0/0.0

```

```

Group: 203.0.113.1
  Source: 10.0.0.30
  Flags: sparse
  Upstream neighbor: 10.0.0.18, Port: ge-2/0/0.0

```

```

user@PE2> show pim snooping join extensive

```

```

Instance: titanium
Learning-Domain: default

```

```

Group: 203.0.113.1
  Source: *
  Flags: sparse,rptree,wildcard
  Upstream neighbor: 10.0.0.18, Port: ge-2/0/0.0
    Downstream port: ge-2/0/1.0
      Downstream neighbors:
        10.0.0.22 State: Join Flags: SRW Timeout: 180

```

```

Group: 203.0.113.1
  Source: 10.0.0.30
  Flags: sparse
  Upstream neighbor: 10.0.0.18, Port: ge-2/0/0.0
    Downstream port: ge-2/0/1.0
      Downstream neighbors:
        10.0.0.22 State: Join Flags: S Timeout: 180

```

The outputs show that multicast traffic sent for the group 203.0.113.1 is sent to Receiver 2 through Router CE4 and also display the upstream and downstream neighbor details.

```

user@PE2> show multicast snooping route extensive instance titanium group 203.0.113.1

```

```

Nexthop Bulking: OFF

```

```

    Family: INET

```

```

Group: 203.0.113.1/24
  Bridge-domain: titanium
  Mesh-group: __all_ces__
  Downstream interface list:
    ge-2/0/1.0 -(1072)
  Statistics: 0 kbps, 0 pps, 0 packets
  Next-hop ID: 1048577
  Route state: Active

```



```

Forwarding state: Forwarding

Group: 203.0.113.1/24
Source: 10.0.0.8
Bridge-domain: titanium
Mesh-group: __all_ces__
Downstream interface list:
    ge-2/0/1.0 -(1072)
Statistics: 0 kbps, 0 pps, 0 packets
Next-hop ID: 1048577
Route state: Active
Forwarding state: Forwarding

```

Meaning

PIM snooping is operational in the network.

VPLS Label Blocks Operation

IN THIS SECTION

- [Elements of Network Layer Reachability Information | 719](#)
- [Requirements for NLRI Elements | 720](#)
- [How Labels are Used in Label Blocks | 720](#)
- [Label Block Composition | 720](#)
- [Label Blocks in Junos OS | 721](#)
- [VPLS Label Block Structure | 721](#)

A virtual private LAN service (VPLS) is a Layer 2 (L2) service that emulates a local area network (LAN) across a wide area network (WAN). VPLS labels are defined and exchanged in the Border Gateway Protocol (BGP) control plane. In the Junos OS implementation, label blocks are allocated and used in the VPLS control plane for two primary functions: autodiscovery and signaling.

- Autodiscovery—A method for automatically recognizing each provider edge (PE) router in a particular VPLS domain, using BGP update messages.

- **Signaling**—Each pair of PE routers in a VPLS domain sends and withdraws VPN labels to each other. The labels are used to establish and dismantle pseudowires between the routers. Signaling is also used to transmit certain characteristics of a pseudowire.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The PE router uses BGP extended communities to identify the members of its VPLS. Once the PE router discovers its members, it is able to establish and tear down pseudowires between members by exchanging and withdrawing labels and transmitting certain characteristics of the pseudowires.

The PE router sends common update messages to all remote PE routers, using a distinct BGP update message, thereby reducing the control plane load. This is achieved by using VPLS label blocks.

Elements of Network Layer Reachability Information

VPLS BGP network layer reachability information (NLRI) is used to exchange VPLS membership and parameters. The elements of a VPLS BGP NLRI are defined in [Table 14 on page 719](#).

Table 14: NLRI Elements

Element	Acronym	Description	Default Size (Octets)
Length		Total length of the NLRI size represented in bytes.	2
Route Distinguisher	RD	Unique identifier for each routing instance configured on a PE.	8
VPLS Edge ID	VE ID	Unique number to identify the edge site.	2
VE Block Offset	VBO	Value used to identify a label block from which a label value is selected to set up pseudowires for a remote site.	2
VE Block Size	VBS	Indicates the number of pseudowires that peers can have in a single block.	2

Table 14: NLRI Elements (Continued)

Element	Acronym	Description	Default Size (Octets)
Label Base	LB	Starting value of the label in the advertised label block.	3

Requirements for NLRI Elements

Junos OS requires a unique route distinguisher (RD) for each routing instance configured on a PE router. A PE router might use the same RD across a VPLS (or VPN) domain or it might use different RDs. Using different RDs helps identify the originator of the VPLS NLRI.

The VPLS edge (VE) ID can be a unique VE ID, site ID, or customer edge (CE) ID. The VE ID is used by a VPLS PE router to index into label blocks used to derive the transmit and receive VPN labels needed for transport of VPLS traffic. The VE ID identifies a particular site, so it needs to be unique within the VPLS domain, except for some scenarios such as multihoming.

All PE routers have full mesh connectivity with each other to exchange labels and set up pseudowires. The VE block size (VBS) is a configurable value that represents the number of label blocks required to cover all the pseudowires for the remote peer.

A single label block contains 8 labels (1 octet) by default. The default VBS in Junos OS is 2 blocks (2 octets) for a total of 16 labels.

How Labels are Used in Label Blocks

Each PE router creates a mapping of the labels in the label block to the sites in a VPLS domain. A PE router advertising a label block with a block offset indicates which sites can use the labels to reach it. When a PE router is ready to advertise its membership to a VPLS domain, it allocates a label block and advertises the VPLS NLRI. In this way, other PE routers in the same VPLS domain can learn of the existence of the VPLS and set up pseudowires to it if needed. The VPLS NLRI advertised for this purpose is referred to as the *default VPLS NLRI*. The label block in the default VPLS NLRI is referred to as the *default label block*.

Label Block Composition

A label block (set of labels) is used to reach a given site ID. A single label block contains 8 labels (1 octet) by default. The VBS is 2 octets by default in Junos OS.

The label block advertised is defined as a label base (LB) and a VE block size (VBS). It is a contiguous set of labels (LB, LB+1,...LB+VBS-1). For example, when Router PE-A sends a VPLS update, it sends the

same label block information to all other PE routers. Each PE router that receives the LB advertisement infers the label intended for Router PE-A by adding its own site ID to the label base.

In this manner, each receiving PE gets a unique label for PE-A for that VPLS. This simple method is enhanced by using a VE block offset (VBO).

A label block is defined as: <Label Base (LB), VE block offset (VBO), VE block size (VBS)> is the set {LB + VBO, LB + VBO + 1, ..., LB + VBO + VBS - 1}.

Label Blocks in Junos OS

Instead of a single large label block to cover all VE IDs in a VPLS, the Junos OS implementation contains several label blocks, each with a different label base. This makes label block management easier, and also allows Router PE-A to seamlessly integrate a PE router joining a VPLS with a site ID not covered by the set of label blocks that Router PE-A has already advertised.

VPLS Label Block Structure

This section illustrates how a label block is uniquely identified.


A VPLS BGP NLRI with site ID V, VE block offset VBO, VE block size VBS, and label base LB communicates the following to its peers:

- Label block for V: Labels from LB to (LB + VBS - 1).
- Remote VE set for V: from VBO to (VBO + VBS - 1).

The label block advertised is a set of labels used to reach a given site ID. If there are several label blocks, the remote VE set helps to identify which label block to use. The example in [Figure 53 on page 722](#)

illustrates label blocks. There are two blocks and each block has eight labels. In this example, the label values are 64 to 71 and 80 to 87.

Figure 53: VPLS Label Block Structure



To create a one-to-one mapping of these 16 labels to 16 sites, assume the site IDs are the numbers 1 to 16, as shown in the illustration. The site block indicates which site ID can use which label in the label block. So, in the first block, site ID 1 uses 64, site ID 2 uses 65, and so forth. Finally, site ID 8 uses 71. The 9th site ID will use the second block instead of the first block.

The labels are calculated by comparing the values of $VBO \leq \text{Local site ID} < (VBO + VBS)$. Consequently, site ID 9 uses 80, site ID 10 uses 81, and so on.


To further illustrate the one-to-one mapping of labels to sites, assume a label block with site offset of 1 and a label base of 10. The combination of label base and block offset contained in the VPLS NLRI provides the mapping of labels to site IDs. The block offset is the starting site ID that can use the label block as advertised in the VPLS NLRI.

To advertise the default VPLS NLRI, a PE router picks a starting block offset that fits its own site ID and is such that the end block offset is a multiple of a single label block. In Junos OS a single label block is eight labels by default.

The end block offset is the last site ID that maps to the last label in the label block. The end offset for the first block is 8 which maps to label 17 and the second block is 16. For example, a site with ID 3 picks a block offset of 1 and advertises a label block of size 8 to cover sites with IDs 1 to 8. A site with ID 10 picks a block offset of 9 to cover sites with IDs 9 to 16.

The VPLS NLRI shown in [Figure 54 on page 723](#) is for site ID 18. The label base contains value 262145. The block offset contains value 17. The illustration shows which site IDs correspond to which labels.

Figure 54: Label Mapping Example



If a PE router configured with site ID 17 is in the same VPLS domain as a PE router configured with site ID 18, it receives the VPLS NLRI as shown in Figure 2. So it uses label 262145 to send traffic to site 18. Similarly, a PE router configured with site ID 19 uses label 262147 to send traffic to a PE router configured with site ID 18. However, only PE routers configured with site IDs 17 to 24 can use the label block shown to set up pseudowires.

RELATED DOCUMENTATION

[Example: Building a VPLS From Router 1 to Router 3 to Validate Label Blocks](#) | 725

Configuring the Label Block Size for VPLS

VPLS MPLS packets have a two-label stack. The outer label is used for normal MPLS forwarding in the service provider's network. If BGP is used to establish VPLS, the inner label is allocated by a PE router as part of a label block. One inner label is needed for each remote VPLS site. Four sizes are supported. We recommend using the default size of 8, unless the network design requires a different size for optimal label usage, to allow the router to support a larger number of VPLS instances.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

If you allocate a large number of small label blocks to increase efficiency, you also increase the number of routes in the VPLS domain. This has an impact on the control plane overhead.

Changing the configured label block size causes all existing pseudowires to be deleted. For example, if you configure the label block size to be 4 and then change the size to 8, all existing label blocks of size 4 are deleted, which means that all existing pseudowires are deleted. The new label block of size 8 is created, and new pseudowires are established.

Four label block sizes are supported: 2, 4, 8, and 16. Consider the following scenarios:

- 2—Allocate the label blocks in increments of 2. For a VPLS domain that has only two sites with no future expansion plans.
- 4—Allocate the label blocks in increments of 4.
- 8 (default)—Allocate the label blocks in increments of 8.
- 16—Allocate the label blocks in increments of 16. A label block size of 16 enables you to minimize the number of routes in the VPLS domain. Use this setting only if the number of routes is the most important concern.

Configure the label block size:

```
[edit routing-instances instance-name protocols vpls]
user@router# set label-block-size 2
```

RELATED DOCUMENTATION

| [Configuring VPLS Routing Instances](#) | 674

Example: Building a VPLS From Router 1 to Router 3 to Validate Label Blocks

IN THIS SECTION

- Requirements | 725
- Overview and Topology | 725
- Configuration | 727

This example illustrates how VPLS label blocks are allocated for a specific configuration. It is organized in the following sections:


Requirements

This configuration example requires three Juniper Networks routers.

Overview and Topology

In the network shown in [Figure 55 on page 725](#) Router 1 is establishing a pseudowire to Router 3

Figure 55: Router 1 to Router 3 Topology



Each PE filters the VPLS NLRI contained in the BGP update messages based on route target communities. Those VPLS NLRI instances that match the route target (in this case 8717:2000:2:1) are imported for further processing. The NLRI for Router 1 and Router 3 is shown in [Table 15 on page 726](#).

Table 15: NLRI Exchange Between for Router 1 and Router 3

Router 1 NLRI Advertisement to Router 3	Router 3 NLRI Advertisement to Router 1
RD - 8717:1000	RD - 8717:1000
VE ID - 1	VE ID - 2
VE Block Offset - 1	VE Block Offset - 1
VE Block Size - 8	VE Block Size - 8
Label Base - 262161	Label Base - 262153

To set up a pseudowire to Router 3, Router 1 must select a label to use to send traffic to Router 3 and also select a label that it expects Router 3 to use to send traffic to itself. The site ID contained in the VPLS NLRI from Router 3 is 2.

Router 1 learns of the existence of site ID 2 in the same VPLS domain. Using the equation $VBO \leq \text{Local Site ID} < (VBO + VBS)$, Router 1 checks if the route advertised by site ID 2 fits in the label block and block offset that it previously advertised to Router 3. In this example it does fit, so the site ID 2 is mapped by the VPLS NLRI advertised by Router 1, and Router 1 is ready to set up a pseudowire to Router 3.

To select the label to reach Router 3, Router 1 looks at the label block advertised by Router 3 and performs a calculation. The calculation a PE router uses to check if its site ID is mapped in the label block from the remote peer is $VBO \leq \text{Local Site ID} < (VBO + VBS)$. So, Router 1 selects label $(262153 + (1 - 1)) = 262153$ to send traffic to Router 3. Using the same equation, Router 1 looks at its own label block that it advertised and selects label $(262161 + (2 - 1)) = 262162$ to receive traffic from Router 3. Router 1 programs its forwarding state such that any traffic destined to Router 3 carries the pseudowire label 262153 and any traffic coming from Router 3 is expected to have the pseudowire label 262162. This completes the operations on the VPLS NLRI received from Router 3. Router 1 now has a pseudowire set up to Router 3.

Router 3 operation is very similar to the Router 1 operation. Since the Router 3 site ID of 2 fits in the label block and block offset advertised by Router 1, Router 3 selects label $(262161 + (2 - 1)) = 262162$ to send traffic to Router 1. Router 3 looks at its own label block that it advertised and selects label $(262153 + (1 - 1)) = 262153$ to receive traffic from Router 1. This completes the creation of a pseudowire to Router 1.

By default, for VPLS operation Junos OS uses a virtual tunnel (VT) loopback interface to represent a pseudowire. This example uses a label-switched interface (LSI) instead of a VT interface because there is

no change in the VPLS control plane operation. Thus, for an MX platform, if there is a tunnel physical interface card (PIC) configured, it is mandatory to include the `no-tunnel-services` statement at the `[edit routing-instances routing-instance-name protocols vpls]` hierarchy level.

Configuration

IN THIS SECTION

- [Configuring Router 1 | 727](#)
- [Configuring Router 3 | 728](#)
- [Verifying the VPLS Label Allocations | 728](#)

The following sections present the steps to configure and verify the example in [Figure 55 on page 725](#).

Configuring Router 1

Step-by-Step Procedure

1. Configure Router 1. Create the `edut` routing instance. Specify the `vpls` instance type. Configure the route distinguisher and specify the value `8717:1000`. Configure the route target and specify the value `8717:100`. Configure the VPLS protocol. Specify `10` as the site range. Specify `1` as the site ID. Include the `no-tunnel-services` statement.

```
[edit routing-instances]
edut {
  instance-type vpls;
  interface ge-5/0/2.0;
  route-distinguisher 8717:1000;
  vrf-target target:8717:100;
  protocols {
    vpls {
      site-range 10;
      no-tunnel-services;
      site router-1 {
        site-identifier 1;
      }
    }
  }
}
```

```

    }
}

```

Configuring Router 3

Step-by-Step Procedure

1. Configure Router 3. Create the `edut` routing instance. Specify the `vpls` instance type. Configure the route distinguisher and specify the value `8717:2000`. Configure the route target and specify the value `8717:200`. Configure the VPLS protocol. Specify `10` as the site range. Specify `2` as the site ID. Include the `no-tunnel-services` statement.

```

[edit routing-instances]
edut {
    instance-type vpls;
    interface ge-4/0/2.0;
    route-distinguisher 8717:2000;
    vrf-target target:8717:100;
    protocols {
        vpls {
            site-range 10;
            no-tunnel-services;
            site router-3 {
                site-identifier 2;
            }
        }
    }
}

```

Verifying the VPLS Label Allocations

Step-by-Step Procedure

1. As shown in the figure and the configuration, Site A is attached to Router 1. Site A is assigned a site ID of 1. Before Router 1 can announce its membership to VPLS `edut` using a BGP update message, Router 1 needs to allocate a default label block. In this example, the label base of the label block allocated by Router 1 is 262161. Since Router 1's site ID is 1, Router 1 associates the assigned label

block with block offset of 1. The following messages are sent from Router 1 to Router 3 and displayed using the `monitor traffic interface interface-name` command:

```
user@Router1> monitor traffic interface ge-5/3/2
Jun 14 12:26:31.280818 BGP SEND 10.10.10.1+179 -> 10.10.10.3+53950
Jun 14 12:26:31.280824 BGP SEND message type 2 (Update) length 88
Jun 14 12:26:31.280828 BGP SEND flags 0x40 code Origin(1): IGP
Jun 14 12:26:31.280833 BGP SEND flags 0x40 code ASPath(2) length 0: <null>
Jun 14 12:26:31.280837 BGP SEND flags 0x40 code LocalPref(5): 100
Jun 14 12:26:31.280844 BGP SEND flags 0xc0 code Extended Communities(16): 2:8717:100
800a:19:0:0
Jun 14 12:26:31.280848 BGP SEND flags 0x90 code MP_reach(14): AFI/SAFI 25/65
Jun 14 12:26:31.280853 BGP SEND          nhop 10.10.10.1 len 4
Jun 14 12:26:31.280862 BGP SEND          8717:1000:1:1 (label base : 262161 range : 8, ce id:
1, offset: 1)
Jun 14 12:26:31.405067 BGP RECV 10.10.10.3+53950 -> 10.10.10.1+179
Jun 14 12:26:31.405074 BGP RECV message type 2 (Update) length 88
Jun 14 12:26:31.405080 BGP RECV flags 0x40 code Origin(1): IGP
Jun 14 12:26:31.405085 BGP RECV flags 0x40 code ASPath(2) length 0: <null>
Jun 14 12:26:31.405089 BGP RECV flags 0x40 code LocalPref(5): 100
Jun 14 12:26:31.405096 BGP RECV flags 0xc0 code Extended Communities(16): 2:8717:100
800a:19:0:0
Jun 14 12:26:31.405101 BGP RECV flags 0x90 code MP_reach(14): AFI/SAFI 25/65
Jun 14 12:26:31.405106 BGP RECV          nhop 10.10.10.3 len 4
Jun 14 12:26:31.405116 BGP RECV          8717:2000:2:1 (label base : 262153 range : 8, ce id:
2, offset: 1)
```

2. As shown in the figure and the configuration, Site B is attached to Router 3. Site B is assigned a site ID of 2. Before Router 3 can announce its membership to VPLS `edut` using a BGP update message, Router 3 assigns a default label block with the label base of 262153. The block offset for this label block is 1 because its own site ID of 2 fits in the block being advertised. The following messages are sent from Router 3 to Router 1 and displayed using the `monitor traffic interface interface-name` command:

```
user@Router3> monitor traffic interface ge-2/0/1
Jun 14 12:26:31.282008 BGP SEND 10.10.10.3+53950 -> 10.10.10.1+179
Jun 14 12:26:31.282018 BGP SEND message type 2 (Update) length 88
Jun 14 12:26:31.282026 BGP SEND flags 0x40 code Origin(1): IGP
Jun 14 12:26:31.282034 BGP SEND flags 0x40 code ASPath(2) length 0: <null>
Jun 14 12:26:31.282041 BGP SEND flags 0x40 code LocalPref(5): 100
Jun 14 12:26:31.282052 BGP SEND flags 0xc0 code Extended Communities(16): 2:8717:100
```

```

800a:19:0:0
Jun 14 12:26:31.282078 BGP SEND flags 0x90 code MP_reach(14): AFI/SAFI 25/65
Jun 14 12:26:31.282088 BGP SEND          nhop 10.10.10.3 len 4
Jun 14 12:26:31.282102 BGP SEND          8717:2000:2:1 (label base : 262153 range : 8, ce id:
2, offset: 1)

Jun 14 12:26:31.283395 BGP RECV 10.10.10.1+179 -> 10.10.10.3+53950
Jun 14 12:26:31.283405 BGP RECV message type 2 (Update) length 88
Jun 14 12:26:31.283412 BGP RECV flags 0x40 code Origin(1): IGP
Jun 14 12:26:31.283419 BGP RECV flags 0x40 code ASPath(2) length 0: <null>
Jun 14 12:26:31.283426 BGP RECV flags 0x40 code LocalPref(5): 100
Jun 14 12:26:31.283435 BGP RECV flags 0xc0 code Extended Communities(16): 2:8717:100
800a:19:0:0
Jun 14 12:26:31.283443 BGP RECV flags 0x90 code MP_reach(14): AFI/SAFI 25/65
Jun 14 12:26:31.283471 BGP RECV          nhop 10.10.10.1 len 4
Jun 14 12:26:31.283486 BGP RECV          8717:1000:1:1 (label base : 262161 range : 8, ce id:
1, offset: 1)

```

3. Verify the connection status messages for Router 1 using the `show vpls connections` command. Notice the base label is 262161, the incoming label from Router 3 is 262162, and the outgoing label to Router 3 is 262153.

```

user@Router1> show vpls connections instance edut extensive
Instance: edut
Local site: router-1 (1)
Number of local interfaces: 1
Number of local interfaces up: 1
IRB interface present: no
ge-5/0/2.0
lsi.1049600      2      Intf - vpls edut local site 1 remote site 2
Label-base      Offset   Range   Preference
262161         1       8       100
connection-site      Type   St      Time last up      # Up trans
2                    rmt    Up      Jun 14 12:26:31 2009      1
Remote PE: 10.10.10.3, Negotiated control-word: No
Incoming label: 262162, Outgoing label: 262153
Local interface: lsi.1049600, Status: Up, Encapsulation: VPLS
Description: Intf - vpls edut local site 1 remote site 2
Connection History:
Jun 14 12:26:31 2009  status update timer
Jun 14 12:26:31 2009  loc intf up                      lsi.1049600
Jun 14 12:26:31 2009  PE route changed

```

```

Jun 14 12:26:31 2009 Out lbl Update      262153
Jun 14 12:26:31 2009 In lbl Update      262162
Jun 14 12:26:31 2009 loc intf down

```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	<- -- only outbound connection is up
CN -- circuit not provisioned	>- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy

Legend for interface status

Up -- operational
Dn -- down

4. Verify the connection status messages for Router 3 using the `show vpls connections` command. Notice the base label is 262153, the incoming label from Router 1 is 262153, and the outgoing label to Router 1 is 262162.

```

user@Router3> show vpls connections instance edut extensive
Instance: edut
  Local site: router-3 (2)
    Number of local interfaces: 1
    Number of local interfaces up: 1
    IRB interface present: no
    ge-4/0/2.0
    lsi.1050368      1      Intf - vpls edut local site 2 remote site 1
    Label-base      Offset  Range   Preference
    262153          1      8       100
    connection-site      Type  St      Time last up      # Up trans

```

```

1                               rmt   Up      Jun 14 12:26:31 2009      1
Remote PE: 10.10.10.1, Negotiated control-word: No
Incoming label: 262153, Outgoing label: 262162
Local interface: lsi.1050368, Status: Up, Encapsulation: VPLS
Description: Intf - vpls edut local site 2 remote site 1
Connection History:
Jun 14 12:26:31 2009  status update timer
Jun 14 12:26:31 2009  loc intf up                lsi.1050368
Jun 14 12:26:31 2009  PE route changed
Jun 14 12:26:31 2009  Out lbl Update                262162
Jun 14 12:26:31 2009  In lbl Update                262153
Jun 14 12:26:31 2009  loc intf down

```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-< -- only outbound connection is up
CN -- circuit not provisioned	>- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not availble
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy

Legend for interface status

Up -- operational
Dn -- down

RELATED DOCUMENTATION

VPLS Label Blocks Operation | 718

Associating Interfaces with VPLS

IN THIS CHAPTER

- [Configuring Interfaces for VPLS Routing | 733](#)
- [VPLS and Aggregated Ethernet Interfaces | 743](#)
- [Configuring VLAN Identifiers for VLANs and VPLS Routing Instances | 744](#)
- [Enabling VLAN Tagging | 748](#)
- [Configuring VPLS Without a Tunnel Services PIC | 749](#)

Configuring Interfaces for VPLS Routing

IN THIS SECTION

- [Configuring the VPLS Interface Name | 734](#)
- [Configuring VPLS Interface Encapsulation | 735](#)
- [Enabling VLAN Tagging | 737](#)
- [Configuring VLAN IDs for Logical Interfaces | 738](#)
- [Enabling VLANs for Hub and Spoke VPLS Networks | 739](#)
- [Sample Scenario of Hierarchical Virtual Private LAN Service on Logical Tunnel Interface | 739](#)
- [Configuring Aggregated Ethernet Interfaces for VPLS | 741](#)

On each PE router and for each VPLS routing instance, specify which interfaces are intended for the VPLS traffic traveling between PE and CE routers. To specify the interface for VPLS traffic, include the interface statement in the routing instance configuration:

```
interface interface-name;
```


You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*]

You must also define each interface by including the following statements:

```
vlan-tagging vlan-tagging;
encapsulation encapsulation-type;
unit logical-unit-number {
    family vpls;
    vlan-id vlan-id-number;
}
```

You can include these statements at the following hierarchy levels:

- [edit interfaces *interface-name*]
- [edit logical-systems *logical-system-name* interfaces *interface-name*]

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The following sections provide enough information to enable you to configure interfaces for VPLS routing.

Configuring the VPLS Interface Name

Specify both the physical and logical portions of the interface name, in the following format:

```
physical.logical
```

For example, in ge-1/2/1.2, ge-1/2/1 is the physical portion of the interface name and 2 is the logical portion. If you do not specify the logical portion of the interface name, 0 is set by default.

A logical interface can be associated with only one routing instance.

If you enable a routing protocol on all instances by specifying `interfaces all` when configuring the master instance of the protocol at the [edit protocols] hierarchy level, and you configure a specific interface for VPLS routing at the [edit routing-instances *routing-instance-name*] hierarchy level, the latter interface statement takes precedence and the interface is used exclusively for VPLS.

If you explicitly configure the same interface name at both the [edit protocols] and [edit routing-instances *routing-instance-name*] hierarchy levels and then attempt to commit the configuration, the commit operation fails.

Configuring VPLS Interface Encapsulation

You need to specify an encapsulation type for each PE-router-to-CE-router interface configured for VPLS. This section describes the encapsulation statement configuration options available for VPLS.

To configure the encapsulation type on the physical interface, include the encapsulation statement:

```
encapsulation (ethernet-vpls | ether-vpls-over-atm-llc | extended-vlan-vpls | vlan-vpls);
```

NOTE: ACX Series routers do not support the *ether-vpls-over-atm-llc* and *extended-vlan-vpls* options for encapsulation.

You can include the encapsulation statement for physical interfaces at the following hierarchy levels:

- [edit interfaces *interface-name*]
- [edit logical-systems *logical-system-name* interfaces *interface-name*]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

You can configure the following physical interface encapsulations for VPLS routing instances:

- *ethernet-vpls*—Use Ethernet VPLS encapsulation on Ethernet interfaces that have VLAN 802.1Q tagging and VPLS enabled. The PE router expects to receive Ethernet frames with VLAN tags that are not service-delimiting. The Ethernet frames are not meaningful to the PE router and cannot be used by the service provider to separate customer traffic.

On M Series routers (except the M320 router), the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.

- *ether-vpls-over-atm-llc*—For ATM intelligent queuing (IQ) interfaces only, use the Ethernet virtual private LAN service (VPLS) over ATM LLC encapsulation to bridge Ethernet interfaces and ATM interfaces over a VPLS routing instance (as described in RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*). Packets from the ATM interfaces are converted to standard ENET2/802.3 encapsulated Ethernet frames with the frame check sequence (FCS) field removed.

- `extended-vlan-vpls`—Use extended virtual LAN (VLAN) VPLS encapsulation on Ethernet interfaces that have VLAN 802.1Q tagging and VPLS enabled and that must accept packets carrying TPIDs 0x8100, 0x9100, and 0x9901. On M Series routers (except the M320 router), the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.

NOTE: The built-in Gigabit Ethernet PIC on an M7i router does not support extended VLAN VPLS encapsulation.

- `vlan-vpls`—Use VLAN VPLS encapsulation on Ethernet interfaces with VLAN 802.1Q tagging and VPLS enabled. The PE router expects to receive Ethernet frames with VLAN tags that are service-delimiting. These VLAN tags can be used by the service provider to separate customer traffic. For example, LAN traffic from different customers can flow through the same service provider switch, which can then apply VLAN tags to distinguish one customer's traffic from the others. The traffic can then be forwarded to the PE router.

Interfaces with VLAN VPLS encapsulation accept packets carrying standard TPID values only. On M Series routers (except the M320 router), the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.

To configure the encapsulation type for logical interfaces, include the encapsulation statement:

```
encapsulation (ether-vpls-over-atm-llc | vlan-vpls);
```

You can include the encapsulation statement for logical interfaces at the following hierarchy levels:

- [edit interfaces *interface-name* unit *number*]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *number*]

You can configure the following logical interface encapsulations for VPLS routing instances:

- `ether-vpls-over-atm-llc`—Use Ethernet VPLS over Asynchronous Transfer Mode (ATM) logical link control (LLC) encapsulation to bridge Ethernet interfaces and ATM interfaces over a VPLS routing instance (as described in RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*). Packets from the ATM interfaces are converted to standard ENET2/802.3-encapsulated Ethernet frames with the frame check sequence (FCS) field removed. This encapsulation type is supported on ATM intelligent queuing (IQ) interfaces only.
- `vlan-vpls`—Use VLAN VPLS encapsulation on Ethernet interfaces with VLAN 802.1Q tagging and VPLS enabled. The PE router expects to receive Ethernet frames with VLAN tags that are service-delimiting. These VLAN tags can be used by the service provider to separate customer traffic. For example, LAN traffic from different customers can flow through the same service provider switch,

which can then apply VLAN tags to distinguish one customer's traffic from the others. The traffic can then be forwarded to the PE router.

Interfaces with VLAN VPLS encapsulation accept packets carrying standard TPID values only. On M Series routers (except the M320 router), the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.

NOTE: Label-switched interfaces (LSIs) do not support VLAN VPLS encapsulation. Therefore, you can only use VLAN VPLS encapsulation on a PE-router-to-CE-router interface and not a core-facing interface.

When you configure the physical interface encapsulation as `vlan-vpls`, you also need to configure the same interface encapsulation for the logical interface. You need to configure the `vlan-vpls` encapsulation on the logical interface because the `vlan-vpls` encapsulation allows you to configure a mixed mode, where some of the logical interfaces use regular Ethernet encapsulation (the default for logical interfaces) and some use `vlan-vpls`.

NOTE: Starting with Junos OS release 13.3, a commit error occurs when you configure `vlan-vpls` encapsulation on a physical interface and configure `family inet` on one of the logical units. Previously, it was possible to commit this invalid configuration.

SEE ALSO

[Configuring VLAN and Extended VLAN Encapsulation](#)

Enabling VLAN Tagging

Junos OS supports receiving and forwarding routed Ethernet frames with 802.1Q virtual local area network (VLAN) tags and running the Virtual Router Redundancy Protocol (VRRP) over 802.1Q-tagged interfaces. For VPLS to function properly, configure the router to receive and forward frames with 802.1Q VLAN tags by including the `vlan-tagging` statement at the `[edit interfaces interface-name]` hierarchy level:

```
[edit interfaces interface-name]  
vlan-tagging;
```

Gigabit Ethernet interfaces can be partitioned. You can assign up to 4095 different logical interfaces, one for each VLAN, but you are limited to a maximum of 1024 VLANs on any single Gigabit Ethernet or 10-Gigabit Ethernet port. Fast Ethernet interfaces can also be partitioned, with a maximum of:

- 1024 logical interfaces for the 4-port FE PIC
- 1024 logical interfaces for the 2-port Fixed Interface Card (FIC) on an M7i router
- 16 logical interfaces for the M40e router

Table 16 on page 738 lists VLAN ID ranges by interface type.

Table 16: VLAN ID Range by Interface Type

Interface Type	VLAN ID Range
Fast Ethernet	512 through 1023
Gigabit Ethernet	512 through 4094

Configuring VLAN IDs for Logical Interfaces

You can bind a VLAN identifier to a logical interface by including the `vlan-id` statement:

```
vlan-id number;
```

You can include this statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number*]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number*]

You can also configure a logical interface to forward packets and learn MAC addresses within each VPLS routing instance configured with a VLAN ID that matches a VLAN ID specified in a list using the `vlan-id-list` statement. VLAN IDs can be entered individually using a space to separate each ID, entered as an inclusive list separating the starting VLAN ID and ending VLAN ID with a hyphen, or a combination of both.

For example, to configure the VLAN IDs 20 and 45 and the range of VLAN IDs between 30 and 40, issue the following command from the CLI:

```
set interfaces ge-1/0/1 unit 1 vlan-id-list [20 30-40 45];
```

To configure a list of VLAN IDs for a logical interface, include the `vlan-id-list` statement:

```
vlan-id-list list-of-vlan-ids;
```

You can include this statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *logical-unit-number*]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number*]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

For more information about how to configure VLANs, see the [Junos OS Network Interfaces Library for Routing Devices](#). For detailed information about how VLAN identifiers in a VPLS routing instance are processed and translated, see the *MX Series Layer 2 Configuration Guide*.

SEE ALSO

| [Junos OS Layer 2 Switching and Bridging Library](#)

Enabling VLANs for Hub and Spoke VPLS Networks

For hub and spoke VPLS networks, you need to configure the swap option for the output-vlan-map statement on the hub facing interface of each spoke PE router. The output-vlan-map statement ensures that the vlan ID of the spoke PE router matches the VLAN ID of the hub PE router in the VPLS network. The following configuration example illustrates an interface configuration with the output-vlan-map statement included:

```
[edit interfaces xe-4/0/0]
vlan-tagging;
encapsulation flexible-ethernet-services;
unit 610 {
    encapsulation vlan-ccc;
    vlan-id 610;
    output-vlan-map swap;
}
```

Sample Scenario of Hierarchical Virtual Private LAN Service on Logical Tunnel Interface

This section describes how to configure the hierarchical virtual private LAN service (H-VPLS) on ACX5048 and ACX5096 routers. Junos OS for ACX5048 and ACX5096 routers supports configuring H-VPLS using the logical tunnel interface encapsulation.

For example, you have three provider edge devices (PE1, PE2 and PE3). PE2 device connects both PE1 and PE3 devices. The pseudowire connecting PE1 and PE2 devices are encapsulated with circuit cross-connect (CCC). In this case, PE1 device acts as a spoke and PE2 as a hub. The pseudowire connecting PE2 and PE3 devices are encapsulated with VPLS. You need to encapsulate CCC and VPLS pseudowires using the logical tunnel interface on the PE2 device.

The following steps describe how to encapsulate CCC and VPLS pseudowires using the logical tunnel interface on the PE2 device:

1. Create a logical tunnel interface on the PE2 device by using the `set chassis fpc fpc-slot pic pic-slot tunnel-services port port-number` CLI command. The *port-number* can be any port on the chassis which is not used for regular traffic forwarding. For example,

```
[edit]
user@host# set chassis fpc 0 pic 0 tunnel-services port 65
```

2. Encapsulate the CCC and VPLS pseudowires using the logical tunnel interface (lt-0/0/65) created on the PE2 device. Use the Ethernet CCC (ethernet-ccc) and Ethernet VPLS (ethernet-vpls) encapsulation types at the [edit interfaces interface-name unit logical-unit-number] hierarchy level as shown in the example:

Device PE2

```
[edit]
user@host# set interfaces lt-0/0/65 unit 0 encapsulation ethernet-ccc;
user@host# set interfaces lt-0/0/65 unit 0 encapsulation peer-unit 1;
user@host# set interfaces lt-0/0/65 unit 1 encapsulation ethernet-vpls;
user@host# set interfaces lt-0/0/65 unit 1 encapsulation peer-unit 0;
```

3. Verify the configuration by entering the show command at the logical tunnel interface level. The output should display as follows:

```
[edit interfaces lt-0/0/65]
user@host# show
unit 0 {
    encapsulation ethernet-ccc;
    peer-unit 1;
}
unit 1 {
    encapsulation ethernet-vpls;
    peer-unit 0;
}
```

Based on this configuration, you can see that:

- The CCC pseudowire on PE2 device originates from It-0/0/65.0
- The VPLS pseudowire on PE2 device originates from It-0/0/65.1
- The CCC pseudowire on PE1 device originates from a regular interface
- The VPLS pseudowire on PE3 device originates from a regular interface

Configuring Aggregated Ethernet Interfaces for VPLS

You can configure aggregated Ethernet interfaces between CE devices and PE routers for VPLS routing instances. Traffic is load-balanced across all of the links in the aggregated interface. If one or more links in the aggregated interface fails, the traffic is switched to the remaining links.

For more information about how aggregated Ethernet interfaces function in the context of VPLS, see ["VPLS and Aggregated Ethernet Interfaces" on page 743](#).

To configure aggregated Ethernet interfaces for VPLS, configure the interface for the VPLS routing instance as follows:

```
interfaces aex {
    vlan-tagging;
    encapsulation encapsulation-type;
    unit logical-unit-number {
        vlan-id number;
    }
}
```

You can configure the following physical link-layer encapsulation types for the VPLS aggregated Ethernet interface:

- ethernet-vpls
- extended-vlan-vpls
- flexible-ethernet-services
- vlan-vpls

NOTE: ACX Series routers do not support the **extended-vlan-vpls** and **vlan-vpls** encapsulation types.

For the **interface** configuration statement, in **ae***x*, the *x* represents the interface instance number to complete the link association; *x* can be from 0 through 127, for a total of 128 aggregated interfaces.

For more information about how to configure aggregated Ethernet interfaces, see the [Ethernet Interfaces User Guide for Routing Devices](#).

The aggregated Ethernet interface must also be configured for the VPLS routing instance as shown in the following example:

```
[edit]
routing-instances {
  green {
    instance-type vpls;
    interface ae0.0;
    route-distinguisher 10.255.234.34:1;
    vrf-target target:11111:1;
    protocols {
      vpls {
        site-range 10;
        site green3 {
          site-identifier 3;
        }
      }
    }
  }
}
```

Interface **ae0.0** represents the aggregated Ethernet interface in the routing instance configuration. The VPLS routing instance configuration is otherwise standard.

SEE ALSO

[VPLS and Aggregated Ethernet Interfaces | 743](#)

[Ethernet Interfaces User Guide for Routing Devices](#)

VPLS and Aggregated Ethernet Interfaces

You can configure aggregated Ethernet interfaces between CE devices and PE routers for VPLS routing instances. Traffic is load-balanced across all of the links in the aggregated interface. If one or more links in the aggregated interface fails, the traffic is switched to the remaining links.

Forwarding is based on a lookup of the DA MAC address. For the remote site, if a packet needs to be forwarded over an LSP, the packet is encapsulated and forwarded through the LSP. If the packet destination is a local site, it is forwarded over appropriate local site interface. For an aggregated Ethernet interface on the local site, packets are sent out of the load-balanced child interface. The Packet Forwarding Engine acquires the child link to transmit the data.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

When a received packet does not have a match to a MAC address in the forwarding database, the packet is forwarded over a set of interfaces determined from a lookup in the flooding database based on the incoming interface. This is denoted by a flood next hop. The flood next hop can include the aggregated Ethernet interface as the set of interfaces to flood the packet.

Each VPLS routing instance configured on a PE router has its own forwarding database entries that associate all of the MAC addresses the VPLS routing instance acquires with each corresponding port. A route is added to the kernel with a MAC address as the prefix and the next hop used to reach the destination. The route is an interface if the destination is local. For a remote destination, the route is a next hop for the remote site.

For local aggregated Ethernet interfaces on M Series and T Series routers, learning is based on the parent aggregated Ethernet *logical interface*. To age out MAC addresses for aggregated Ethernet interfaces, each Packet Forwarding Engine is queried to determine where the individual child interfaces are located. MAC addresses are aged out based on the age of the original interface.

For MX Series routers and EX Series switches, when a Dense Port Concentrator (DPC) learns a MAC address it causes the Routing Engine to age out the entry. This behavior applies to all logical interfaces. For an aggregated Ethernet logical interface, once all the member DPCs have aged out the entry, the entry is deleted from the Routing Engine.

RELATED DOCUMENTATION

[Configuring Interfaces for VPLS Routing | 733](#)

[Configuring Interfaces for VPLS Routing | 733](#)

Configuring VLAN Identifiers for VLANs and VPLS Routing Instances

You can configure VLAN identifiers for a VLAN or a VPLS routing instance in the following ways:

- By using either the `vlan-id` statement or the `vlan-tags` statement to configure a normalizing VLAN identifier. This topic describes how normalizing VLAN identifiers are processed and translated in a VLAN or a VPLS routing instance.
- By using the **input-vlan-map** and the `output-vlan-map` statements at the `[edit interfaces interface-name unit logic-unit-number]` or `[edit logical-systems logical-system-name interfaces interface-name unit logic-unit-number]` hierarchy level to configure VLAN mapping.

NOTE: In ACX5048 and ACX5096 routers, VLAN map operation is supported only if the `connectivity-type` is *ce* mode and not with *permanent* mode.

The **vlan-id** and `vlan-tags` statements are used to specify the normalizing VLAN identifier under the VLAN or VPLS routing instance. The normalizing VLAN identifier can translate or normalize the VLAN tags of packets received into a learn VLAN identifier.

NOTE: You cannot configure VLAN mapping using the **input-vlan-map** and `output-vlan-map` statements if you configure a normalizing VLAN identifier for a VLAN or VPLS routing instance using the **vlan-id** or `vlan-tags` statements.

To configure a VLAN identifier for a VLAN, include either the **vlan-id** or the `vlan-tags` statement at the `[edit interfaces interface-name unit logic-unit-number]` or `[edit logical-systems logical-system-name interfaces interface-name unit logic-unit-number]` hierarchy level, and then include that logical interface in the VLAN configuration.

For a VPLS routing instance, include either the **vlan-id** or `vlan-tags` statement at the `[edit interfaces interface-name unit logic-unit-number]` or `[edit logical-systems logical-system-name interfaces interface-name unit logic-unit-number]` hierarchy level, and then include that logical interface in the VPLS routing instance configuration.

NOTE: ACX Series routers do not support the `[edit logical-systems]` hierarchy.

NOTE: For a single VLAN or VPLS routing instance, you can include either the **vlan-id** or the **vlan-tags** statement, but not both. If you do not configure a **vlan-id** or **vlan-tags** for the VLAN or the VPLS routing instance, the Layer 2 packets received are forwarded to the outbound Layer 2 interface without having the VLAN tag modified unless an **output-vlan-map** is configured on the Layer 2 interface. This results in a frame being forwarded to a Layer 2 interface with a VLAN tag that is different from what is configured for the Layer 2 interface. Note that a frame received from the Layer 2 interface is still required to match the VLAN tag(s) specified in the interface configuration. The invalid configuration may cause a Layer 2 loop to occur. In ACX5048 and ACX5096 routers, if the interface VLAN is configured as **vlan-id-list**, it is mandatory to normalize the VPLS routing instance. **vlan-id all** is not supported in ACX5048 and ACX5096 routers.

The VLAN tags associated with the inbound logical interface are compared with the normalizing VLAN identifier. If the tags are different, they are rewritten as described in [Table 18 on page 747](#). The source MAC address of a received packet is learned based on the normalizing VLAN identifier.

If the VLAN tags associated with the outbound logical interface and the normalizing VLAN identifier are different, the normalizing VLAN identifier is rewritten to match the VLAN tags of the outbound logical interface, as described in [Table 19 on page 748](#).

The following steps outline the process for bridging a packet received over a Layer 2 logical interface when you specify a normalizing VLAN identifier using either the **vlan-id number** or **vlan-tags** statement for a VLAN or a VPLS routing instance:

1. When a packet is received on a physical port, it is accepted only if the VLAN identifier of the packet matches the VLAN identifier of one of the logical interfaces configured on that port.
2. The VLAN tags of the received packet are then compared with the normalizing VLAN identifier. If the VLAN tags of the packet are different from the normalizing VLAN identifier, the VLAN tags are rewritten as described in [Table 18 on page 747](#).
3. If the source MAC address of the received packet is not present in the source MAC table, it is learned based on the normalizing VLAN identifier.
4. The packet is then forwarded toward one or more outbound Layer 2 logical interfaces based on the destination MAC address. A packet with a known unicast destination MAC address is forwarded only to one outbound logical interface. For each outbound Layer 2 logical interface, the normalizing VLAN identifier configured for the VLAN or VPLS routing instance is compared with the VLAN tags configured on that logical interface. If the VLAN tags associated with an outbound logical interface do not match the normalizing VLAN identifier configured for the VLAN or VPLS routing instance, the VLAN tags are rewritten as described in [Table 19 on page 748](#).

The tables below show how VLAN tags are applied for traffic sent to and from the VLAN, depending on how the **vlan-id** and **vlan-tags** statements are configured for the VLAN and on how identifiers are

configured for the logical interfaces in a VLAN or VPLS routing instance. Depending on your configuration, the following rewrite operations are performed on VLAN tags:

- **pop**—Remove a VLAN tag from the top of the VLAN tag stack.
- **pop-pop**—Remove both the outer and inner VLAN tags of the frame.
- **pop-swap**—Remove the outer VLAN tag of the frame and replace the inner VLAN tag of the frame.
- **swap**—Replace the VLAN tag of the frame.
- **push**—Add a new VLAN tag to the top of the VLAN stack.
- **push-push**—Push two VLAN tags in front of the frame.
- **swap-push**—Replace the VLAN tag of the frame and add a new VLAN tag to the top of the VLAN stack.
- **swap-swap**—Replace both the outer and inner VLAN tags of the frame.

Table 17 on page 746 shows the supported input and output VLAN map configurations.

Table 17: Supported Input and Output VLAN Map Configurations

Interface Type	Input-map		Output-map	
	Configuration	Parameters	Configuration	Parameters
Untagged	push	tpid.outer-vlan	pop	None
	push-push	tpid.outer-vlan/ inner-vlan	pop-pop	None
Single tagged	swap	tpid.outer-vlan	swap	tpid.outer-vlan
	push	tpid.outer-vlan	pop	None
	swap-push	tpid.outer-vlan/ inner-vlan	pop-swap	None
Dual tagged	swap	tpid.outer-vlan	swap	tpid.outer-vlan
	pop	None	push	tpid.outer-vlan

Table 17: Supported Input and Output VLAN Map Configurations (Continued)

Interface Type	Input-map		Output-map	
	Configuration	Parameters	Configuration	Parameters
	swap-swap	tpid.outer-vlan/inner-vlan	swap-swap	tpid.outer-vlan

Table 18 on page 747 shows specific examples of how the VLAN tags for packets sent to the VLAN are processed and translated, depending on your configuration. “–” means that the statement is not supported for the specified logical interface VLAN identifier. “No operation” means that the VLAN tags of the received packet are not translated for the specified input logical interface.

Table 18: Statement Usage and Input Rewrite Operations for VLAN Identifiers for a VLAN

VLAN Identifier of Logical Interface	VLAN Configurations for a VLAN		
	vlan-id none	vlan-id 200	vlan tags outer 100 inner 300
none	No operation	push 200	push 100, push 300
200	pop 200	No operation	swap 200 to 300, push 100
1000	pop 1000	swap 1000 to 200	swap 1000 to 300, push 100
vlan-tags outer 2000 inner 300	pop 2000, pop 300	pop 2000, swap 300 to 200	swap 2000 to 100
vlan-tags outer 100 inner 400	pop 100, pop 400	pop 100, swap 400 to 200	swap 400 to 300

Table 19 on page 748 shows specific examples of how the VLAN tags for packets sent from the VLAN are processed and translated, depending on your configuration. “–” means that the statement is not supported for the specified logical interface VLAN identifier. “No operation” means that the VLAN tags of the outbound packet are not translated for the specified output logical interface.

Table 19: Statement Usage and Output Rewrite Operations for VLAN Identifiers for a VLAN

VLAN Identifier of Logical Interface	VLAN Configurations for a VLAN		
	vlan-id none	vlan-id 200	vlan tags outer 100 inner 300
none	no operation	pop 200	pop 100, pop 300
200	push 200	No operation	pop 100, swap 300 to 200
1000	push 1000	swap 200 to 1000	pop 100, swap 300 to 1000
vlan-tags outer 2000 inner 300	push 2000, push 300	swap 200 to 300, push 2000	swap 100 to 2000
vlan-tags outer 100 inner 400	push 100, push 400	swap 200 to 400, push 100	swap 300 to 400

Enabling VLAN Tagging

Junos OS supports receiving and forwarding routed Ethernet frames with 802.1Q virtual local area network (VLAN) tags and running the Virtual Router Redundancy Protocol (VRRP) over 802.1Q-tagged interfaces. For VPLS to function properly, configure the router to receive and forward frames with 802.1Q VLAN tags by including the `vlan-tagging` statement at the `[edit interfaces interface-name]` hierarchy level:

```
[edit interfaces interface-name]
vlan-tagging;
```

Gigabit Ethernet interfaces can be partitioned. You can assign up to 4095 different logical interfaces, one for each VLAN, but you are limited to a maximum of 1024 VLANs on any single Gigabit Ethernet or 10-Gigabit Ethernet port. Fast Ethernet interfaces can also be partitioned, with a maximum of:

- 1024 logical interfaces for the 4-port FE PIC

- 1024 logical interfaces for the 2-port Fixed Interface Card (FIC) on an M7i router
- 16 logical interfaces for the M40e router

Table 20 on page 749 lists VLAN ID ranges by interface type.

Table 20: VLAN ID Range by Interface Type

Interface Type	VLAN ID Range
Fast Ethernet	512 through 1023
Gigabit Ethernet	512 through 4094

Configuring VPLS Without a Tunnel Services PIC

VPLS normally uses a dynamic virtual tunnel logical interface on a Tunnel Services PIC to model traffic from a remote site (a site on a remote PE router that is in a VPLS domain). All traffic coming from a remote site is treated as coming in over the virtual port representing this remote site, for the purposes of Ethernet flooding, forwarding, and learning. An MPLS lookup based on the inner VPN label is done on a PE router. The label is stripped and the Layer 2 Ethernet frame contained within is forwarded to a Tunnel Services PIC. The PIC loops back the packet and then a lookup based on Ethernet MAC addresses is completed. This approach requires that the router have a Tunnel Services PIC and that the PE router complete two protocol lookups.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

You can configure VPLS without a Tunnel Services PIC by configuring the `no-tunnel-services` statement. This statement creates a label-switched interface (LSI) to provide VPLS functionality. An LSI MPLS label is used as the inner label for VPLS. This label maps to a VPLS routing instance. On the PE router, the LSI label is stripped and then mapped to a logical LSI interface. The Layer 2 Ethernet frame is then forwarded using the LSI interface to the correct VPLS routing instance.

By default, VPLS requires a Tunnel Services PIC. To configure VPLS on a router without a Tunnel Services PIC and create an LSI, include the `no-tunnel-services` statement:

```
no-tunnel-services;
```

For a list of the hierarchy levels at which you can include this statement, see the summary section for this statement.

To configure a VPLS routing instance on a router without a tunnel services PIC, include the `no-tunnel-services` statement at the `[edit routing-instances routing-instance-name protocols vpls]` hierarchy level. To configure static VPLS on a router without a tunnel services PIC, include the `no-tunnel-services` statement at the `[edit protocols vpls static-vpls]` hierarchy level.

When you configure VPLS without a Tunnel Services PIC by including the `no-tunnel-services` statement, the following limitations apply:

- An Enhanced FPC is required.
- ATM1 interfaces are not supported.
- Aggregated SONET/SDH interfaces are not supported as core-facing interfaces.
- Channelized interfaces are not supported as core-facing interfaces.
- GRE-encapsulated interfaces are not supported as core-facing interfaces.

RELATED DOCUMENTATION

| [Configuring Static Pseudowires for VPLS | 751](#)

Configuring Pseudowires

IN THIS CHAPTER

- [Configuring Static Pseudowires for VPLS | 751](#)
- [VPLS Path Selection Process for PE Routers | 753](#)
- [BGP and VPLS Path Selection for Multihomed PE Routers | 755](#)
- [Dynamic Profiles for VPLS Pseudowires | 757](#)
- [Use Cases for Dynamic Profiles for VPLS Pseudowires | 758](#)
- [Example: Configuring VPLS Pseudowires with Dynamic Profiles—Basic Solutions | 759](#)
- [Example: Configuring VPLS Pseudowires with Dynamic Profiles—Complex Solutions | 765](#)
- [Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)
- [Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)
- [Example: Configuring H-VPLS BGP-Based and LDP-Based VPLS Interoperation | 775](#)
- [Example: Configuring BGP-Based H-VPLS Using Different Mesh Groups for Each Spoke Router | 805](#)
- [Example: Configuring LDP-Based H-VPLS Using a Single Mesh Group to Terminate the Layer 2 Circuits | 834](#)
- [Example: Configuring H-VPLS With VLANs | 843](#)
- [Example: Configuring H-VPLS Without VLANs | 861](#)
- [Sample Scenario of H-VPLS on ACX Series Routers for IPTV Services | 877](#)

Configuring Static Pseudowires for VPLS

You can configure a VPLS domain using static pseudowires. A VPLS domain consists of a set of PE routers that act as a single virtual Ethernet bridge for the customer sites connected to these routers. By configuring static pseudowires for the VPLS domain, you do not need to configure the LDP or BGP protocols that would normally be used for signaling. However, if you configure static pseudowires, any changes to the VPLS network topology have to be managed manually.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Static pseudowires require that you configure a set of in and out labels for each pseudowire configured for the VPLS domain. You still need to configure a VPLS identifier and neighbor identifiers for a static VPLS domain. You can configure both static and dynamic neighbors within the same VPLS routing instance.

To configure a static pseudowire for a VPLS neighbor, include the static statement:

```
static (Protocols VPLS) {
    incoming-label label;
    outgoing-label label;
}
```

You must configure an incoming and outgoing label for the static pseudowire using the `incoming-label` and `outgoing-label` statements. These statements identify the static pseudowire's incoming traffic and destination.

To configure a static pseudowire for a VPLS neighbor, include the static statement at the [edit routing-instances *routing-instance-name* protocols vpls neighbor *address*] hierarchy level.

You can also configure the static statement for a backup neighbor (if you configure the neighbor as static the backup must also be static) by including it at the [edit routing-instances *routing-instance-name* protocols vpls neighbor *address* backup-neighbor *address*] hierarchy level and for a mesh group by including it at the [edit routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name* neighbor *address*] hierarchy level.

For a list of hierarchy levels at which you can include the static statement, see the statement summary section for this statement.

To enable static VPLS on a router, you need to either configure a virtual tunnel interface (requires the router to have a tunnel services PIC) or you can configure a label switching interface (LSI). To configure an LSI, include the `no-tunnel-services` statement at the [edit protocols vpls static-vpls] hierarchy level. For more information, see ["Configuring VPLS Without a Tunnel Services PIC" on page 749](#).

NOTE: Static pseudowires for VPLS using an LSI is supported on MX series routers and EX Series switches only. For M series and T series routers, a tunnel services PIC is required.

If you issue a `show vpls connections` command, static neighbors are displayed with "SN" next to their addresses in the command output.

RELATED DOCUMENTATION

[Configuring VPLS Without a Tunnel Services PIC | 749](#)

VPLS Path Selection Process for PE Routers

The VPLS path selection process is used to select the best path between a remote PE router and a local PE router in a VPLS network. This path selection process is applied to routes received from both single-homed and multi-homed PE routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

When the VPLS path selection process is complete, a PE router is made the designated VPLS edge (VE) device. The designated VE device effectively acts as the endpoint for the VPLS pseudowire that is signaled from the remote PE router. Once a PE router is made the designated VE device, a pseudowire can be signaled between the remote PE router and the local PE router and then VPLS packets can begin to flow between the PE routers.

Routes from multihomed PE routers connected to the same customer site share the same site ID, but can have different route distinguishers and block offsets. You can alter the configurations of the route distinguishers and block offsets to make a router more likely or less likely to be selected as the designated VE device.

On each PE router in the VPLS network, the best path to the CE device is determined by completing the following VPLS path selection process on each route advertisement received:

1. If the advertisement has the down bit set to 0, the advertisement is discarded.
2. Select the path with a higher preference. The preference attribute is obtained from the site-preference configured using the `site-preference` statement at the `[edit routing-instances routing-instance-name protocols vpls site site-name]` hierarchy level. When the site is down, the preference attribute is obtained from the local preference.
3. If the preference values are the same, select the path with the lower router ID.

4. If the router IDs are the same, the routes are from the same PE router and the advertisement is considered to be an update. The router ID corresponds to the value of the originator ID for the BGP attribute (if present). Otherwise, the IP address for the remote BGP peer is used.
5. If the block offset values are the same, the advertisement is considered to be an update.

Once the VPLS path selection process has been completed and the designated VE device has been selected, a pseudowire is signaled between the remote PE router and the local PE router.

NOTE: The VPLS path selection process works the same whether or not the route has been received from another PE router, a route reflector, or an autonomous system border router (*ASBR*).

When the remote PE router establishes or refreshes a pseudowire to the local PE router, it verifies that the prefix is in the range required for the site ID based on the block offset and label range advertised by the designated VE device. If the prefix is out of range, the pseudowire status is set to out of range.

The following cases outline the potential decisions that could be made when a PE router completes the VPLS path selection process for a Layer 2 advertisement in the VPLS network:

- The PE router originated one of the advertisements and selected its own advertisement as the best path.

This PE router has been selected as the designated VE device. Selection as the designated VE device triggers the creation of pseudowires to and from the other PE routers in the VPLS network. If the remote customer site is multihomed, the designated VE device triggers the creation of pseudowires to and from only the designated VE device for the remote site.

- The PE router originated one of the advertisements but did not select its own advertisement as the best path.

This PE router is a redundant PE router for a multihomed site, but it was not selected as the designated VE device. However, if this PE router has just transitioned from being the designated VE device (meaning it was receiving traffic from the remote PE routers addressed to the multihomed customer site), the PE router tears down all the pseudowires that it had to and from the other PE routers in the VPLS network.

- The PE router received the route advertisements and selected a best path. It did not originate any of these advertisements because it was not connected to the customer site.

If the best path to the customer site (the designated VE device) has not changed, nothing happens. If the best path has changed, this PE router brings up pseudowires to and from the newly designated VE device and tears down the pseudowires to and from the previously designated VE device.

If this PE router does not select a best path after running the VPLS path selection process, then the local PE router does not consider the remote site to exist.

When a VE device receives an advertisement for a Layer 2 NLRI that matches its own site ID but the site is not multihomed, the pseudowire between the VE device and the transmitting PE router transitions to a site collision state and is not considered to be up.

RELATED DOCUMENTATION

[BGP Route Reflectors for VPLS](#) | 625

BGP and VPLS Path Selection for Multihomed PE Routers

The BGP and VPLS path selection procedures are used to select the best path between the remote PE router and one of the multihomed PE routers. As part of these path selection procedures, one of the multihomed PE routers is made the designated VE device. The designated VE device effectively acts as the endpoint for the VPLS pseudowire from the remote PE router. Once a multihomed PE router is made the designated VE device, a pseudowire can be created between the remote PE router and the multihomed PE router.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Routes from multihomed PE routers connected to the same customer site share the same site ID, but can have different route distinguishers and block offsets. On each PE router in the VPLS network, the best path to the multihomed PE router is determined by completing the following VE device-selection procedures on each route advertisement received from a multihomed PE router:

1. BGP designated VE device-selection procedure—Runs before the VPLS designated VE device-selection procedure. However, the BGP designated VE device-selection procedure is used only when the route distinguishers for the multihomed PE routers are identical. If the route distinguishers are unique, only the VPLS designated VE device-selection procedure is run.
2. VPLS designated VE device-selection procedure—Runs after the BGP designated VE device-selection procedure. However, if the route distinguishers for each multihomed PE router are unique, the advertisements are not considered relevant to the BGP designated VE device-selection procedure. As a consequence, only the VPLS designated VE device-selection procedure is used.

The BGP designated VE device-selection procedure is as follows:

1. If the advertisement has the down bit set to 0, the advertisement is discarded.
2. Select the path with a higher preference. The preference attribute is obtained from the site-preference configured using the `site-preference` statement at the [edit routing-instances *routing-instance-name* protocols vpls site *site-name*] hierarchy level. If the site-preference is 0, the preference attribute is obtained from the local-preference.
3. If the preference values are the same, select the path with the lower router-id.
4. If the router-ids are the same, the routes are from the same PE router and the advertisement is considered to be an update.

Once the BGP designated VE device-selection procedure is complete, the VPLS designated VE device-selection procedure begins. This procedure is carried out regardless of the outcome of the BGP designated VE device-selection procedure:

1. If the advertisement has the down bit set to 0, the advertisement is discarded.
2. Select the path with a higher preference. The preference attribute is obtained from the site-preference configured using the `site-preference` statement at the [edit routing-instances *routing-instance-name* protocols vpls site *site-name*] hierarchy level. If the site-preference is 0, the preference attribute is obtained from the local-preference.
3. If the preference values are the same, select the path with the lower router-id.
4. If the router-ids are the same, select the path with a lower route distinguisher.
5. If the route distinguishers are the same, select the path with the lower block offset value.
6. If the block offset values are the same, the advertisement is considered to be an update.

Once the BGP and VPLS path selection procedures have been completed and the designated VE devices have been selected, a pseudowire can be created between the remote PE router and the multihomed PE router.

When the remote PE router establishes or refreshes a pseudowire to the local PE router, it verifies that the prefix is in the range required for the site ID based on the block offset and label range advertised by the designated VE device. If the prefix is out of range, the pseudowire status is set to out of range.

The following cases outline the potential decisions that could be made when a PE router completes the BGP and VPLS path selection procedures for a Layer 2 advertisement in the VPLS network:

- The PE router originated one of the multihomed advertisements and selected its own advertisement as the best path.

This PE router has been selected as the designated VE device. Selection as the designated VE device triggers the creation of pseudowires to and from the other PE routers in the VPLS network. When

the remote customer site is also multihomed, the designated VE device triggers the creation of pseudowires to and from only the designated VE device for the remote site.

- The PE router originated one of the multihomed advertisements but did not select its own advertisement as the best path.

This PE router is one of the redundant PE routers for the multihomed site; it was not selected as the designated VE device. However, if this PE router has just transitioned from being the designated VE device (meaning it was receiving traffic from the remote PE routers addressed to the multihomed customer site), the PE router tears down all the pseudowires that it had to and from the other PE routers in the VPLS network.

- The PE router receives the multihomed advertisements and selects a best path; it does not originate any of these advertisements because it is not connected to the multihomed customer site.

If the preferred path to the customer site (the designated VE device) has not changed, nothing happens. If the preferred path has changed, this PE router brings up pseudowires to and from the newly designated VE device and tears down the pseudowires to and from the previously designated VE device.

If this PE router does not select a best path after running the BGP and VPLS path selection process, the local PE router does not consider the remote site to exist.

When a VE device receives an advertisement for a Layer 2 NLRI which matches its own site ID but the site is not multihomed, the pseudowire between it and the transmitting PE router transitions to a site collision state and is not considered to be up.

Dynamic Profiles for VPLS Pseudowires

A router often has two types of interfaces:

- Static interfaces, which are configured before the router is booted
- Dynamic interfaces, which are created after the router is booted and while it is running

A virtual private LAN service (VPLS) pseudowire interface (such as `lsi.1048576`) is dynamically created by the system. Therefore, the *logical interface* unit number for the VPLS pseudowire is not available in advance to configure characteristics such as virtual local area network (VLAN) identifiers and other parameters. As a result, certain VLAN manipulation features that are easily applied to static interfaces (such as `xe-`, `ge-`, and so on) are either not supported on dynamic interfaces or supported in a nonstandard method.

However, on MX Series routers, there is another configuration method that dynamic interfaces can use to determine their VLAN parameters when they are created by a running router: *dynamic profiles*. A

dynamic profile is a conceptual container that includes parameters associated with a dynamic entity, parameters whose values are not known at the time the entity is configured.

A dynamic profile acts as a kind of template that enables you to create, update, or remove a configuration that includes client access (for example, interface or protocol) or service (for example, CoS) attributes. Using these profiles you can consolidate all of the common attributes of a client (and eventually a group of clients) and apply the attributes simultaneously. The router contains several predefined variables that enable dynamic association of interfaces and logical units to incoming subscriber requests. While configuring a dynamic profile, use the `$junos-interface-ifd-name` variable for a dynamic physical interface and the `$junos-underlying-unit-number` variable for a dynamic logical interface (unit). When a client accesses the router, the dynamic profile configuration replaces the predefined variable with the actual interface name or unit value for the interface the client is accessing.

Dynamic profiles for VPLS are supported only on MX Series routers. For more information about dynamic profiles, see [Junos OS Broadband Subscriber Management and Services Library](#).

RELATED DOCUMENTATION

[Ethernet Networking User Guide for MX Series Routers](#)

[Dynamic Profiles Overview](#)

[Use Cases for Dynamic Profiles for VPLS Pseudowires | 758](#)

[Example: Configuring VPLS Pseudowires with Dynamic Profiles—Basic Solutions | 759](#)

[Example: Configuring VPLS Pseudowires with Dynamic Profiles—Complex Solutions | 765](#)

Use Cases for Dynamic Profiles for VPLS Pseudowires

A dynamic profile is a set of characteristics, defined in a type of template, that you can use to provide dynamic subscriber access and services for broadband applications. These services are assigned dynamically to interfaces. You can use dynamic profiles to configure the VLAN parameters of the dynamic interfaces on MX Series routers.

Two use cases for configuring VPLS pseudowires with dynamic profiles are:

- **Configuring an extra VLAN tag onto pseudowire traffic** — This is a common scenario where all the traffic received from a customer edge (CE) interface needs an additional VLAN tag toward the core. In such cases, you can use dynamic profiles at ingress and egress to control the pseudowire behavior. You can apply dynamic profiles to receive the desired frames, set the additional VLAN tag for these frames, and send these tagged frames with the desired VLAN identifier.

- **Configuring a VPLS pseudowire as a trunk interface** — This is another common scenario where the requirement is to accept traffic from a particular source and to route the traffic based on specific criteria. Dynamic profiles can be used to create multiple pseudowire trunk interfaces to accept the traffic based on specific VLAN identifiers, and to route the accepted traffic to the desired destination.

RELATED DOCUMENTATION

[Dynamic Profiles Overview](#)

[Dynamic Profiles for VPLS Pseudowires](#) | 757

Example: Configuring VPLS Pseudowires with Dynamic Profiles—Basic Solutions

IN THIS SECTION

- [VPLS Pseudowire Interfaces Without Dynamic Profiles](#) | 760
- [VPLS Pseudowire Interfaces and Dynamic Profiles](#) | 761
- [CE Routers Without Dynamic Profiles](#) | 762
- [CE Routers and Dynamic Profiles](#) | 763

The following limitations apply to dynamic profiles for VPLS on MX Series routers:

- The `native-vlan-id` statement is not supported.
- The `native-inner-vlan-id` statement is not supported.
- The `interface-mode access` statement option is not supported.
- The `vlan-id-range` statement is not supported.

In many cases, a configuration using dynamic profiles is more efficient than a static configuration, as shown by the examples in this topic.

VPLS Pseudowire Interfaces Without Dynamic Profiles

Consider the following configuration, which does not use dynamic profiles to manipulate VLAN identifiers:

```
[edit routing-instances]
green {
  instance-type vpls;
  interface ge-0/0/1.1;
  interface ge-0/0/2.1;
  interface ge-0/0/3.1;
  vlan-tags outer 200 inner 100;
  protocols vpls {
    vpls-id 10;
    neighbor 10.1.1.20;
  }
  {...more...}
}

[edit interfaces]
ge-0/0/1 {
  unit 0 {
    vlan-id 10;
  }
}
ge-0/0/2 {
  unit 0 {
    vlan-id 20;
  }
}
ge-0/0/3 {
  unit 0 {
    vlan-id 30;
  }
}
```

NOTE: This is not a complete router configuration.

With this configuration, broadcast packets inside frames arriving with VLAN identifier 10 on **ge-0/0/1** are normalized to a dual-tagged frame with an outer VLAN value of 200 and an inner VLAN value of

100. The broadcast packet and frames exiting **ge-0/0/2** or **ge-0/0/3** have the outer VLAN value stripped and the inner VLAN value swapped to 20 and 30 respectively, according to the interface configuration. However, this stripping of the outer VLAN tag and the swapping is extra work, because the frames will still egress the VPLS pseudowire in routing instance **green** with an outer VLAN tag value of 200 and an inner VLAN tag value of 100, also according to the configuration.

The same configuration can be accomplished more effectively using dynamic profiles.

VPLS Pseudowire Interfaces and Dynamic Profiles

Consider the following configuration, which uses dynamic profiles to manipulate VLAN identifiers:

```
[edit routing-instances]
green {
  instance-type vpls;
  interface ge-0/0/1.1;
  interface ge-0/0/2.1;
  interface ge-0/0/3.1;
  vlan-id 100; # Desired inner VLAN tag on the VPLS pseudowire
  protocols vpls {
    vpls-id 10;
    neighbor 10.1.1.20 {
      associate-profile green_vpls_pw_1; # The profile
    }
  }
  {...more...}
}

[edit interfaces]
ge-0/0/1 {
  unit 0 {
    vlan-id 10;
  }
}
ge-0/0/2 {
  unit 0 {
    vlan-id 20;
  }
}
ge-0/0/3 {
  unit 0 {
    vlan-id 30;
```

```

    }
}

[edit dynamic-profiles]
green_vpls_pw_1 interfaces $junos-interface-ifd-name {
    unit $junos-underlying-unit-number {
        vlan-tags outer 200 inner 100;
    }
}

```

NOTE: This is not a complete router configuration.

With this configuration, broadcast packets inside frames arriving with VLAN identifier 10 on **ge-0/0/1** normalized to a frame with VLAN identifier 100. The broadcast packet and frames exiting **ge-0/0/2** or **ge-0/0/3** have this VLAN value swapped to 20 and 30 respectively, according to the interface configuration. Frames egress the VPLS pseudowire in routing instance **green** with an outer VLAN tag value of 200 pushed on top of the normalized value.

CE Routers Without Dynamic Profiles

You can apply a dynamic profile to an entire VPLS configuration, not just a neighbor.

Consider the following configuration, which does not use dynamic profiles to manipulate VLAN identifiers on a customer edge (CE) router with VLAN identifier 100:

```

[edit routing-instances]
green {
    instance-type vpls;
    interface ge-0/0/1.1;
    interface ge-0/0/2.1;
    interface ge-0/0/3.1;
    vlan-tags outer 200 inner 100;
    protocols vpls {
        vpls-id 10;
        neighbor 10.1.1.20;
    }
    {...more...}
}

[edit interfaces]

```

```

ge-0/0/1 {
    unit 0 {
        vlan-id 100;
    }
}
ge-0/0/2 {
    unit 0 {
        vlan-id 100;
    }
}
ge-0/0/3 {
    unit 0 {
        vlan-id 100;
    }
}

```

NOTE: This is not a complete router configuration.

With this configuration, broadcast packets inside frames arriving on **ge-0/0/1** are normalized to a dual-tagged frame with an outer VLAN value of 200 and an inner VLAN value of 100. The same configuration can be accomplished using dynamic profiles.

CE Routers and Dynamic Profiles

Consider the following configuration, which uses dynamic profiles at the **protocols** level:

```

[edit routing-instances]
green {
    instance-type vpls;
    interface ge-0/0/1.1;
    interface ge-0/0/2.1;
    interface ge-0/0/3.1;
    vlan-id 100; # Desired inner VLAN tag on the VPLS pseudowire
    protocols vpls {
        associate-profile green_vpls_pw_2; # The profile
        vpls-id 10;
        neighbor 10.1.1.20;
    }
    {...more...}
}

```

```

[edit interfaces]
ge-0/0/1 {
    unit 0 {
        vlan-id 100;
    }
}
ge-0/0/2 {
    unit 0 {
        vlan-id 100;
    }
}
ge-0/0/3 {
    unit 0 {
        vlan-id 100;
    }
}

[edit dynamic-profiles]
green_vpls_pw_2 interfaces $junos-interface-ifd-name {
    unit $junos-underlying-unit-number {
        vlan-tags outer 200 inner 100;
    }
}

```

NOTE: This is not a complete router configuration.

With this configuration, broadcast packets inside frames arriving with VLAN identifier 100 on **ge-0/0/1** are normalized to a frame with VLAN identifier 100 (in this case, they are unchanged). The broadcast packet and frames exiting **ge-0/0/2** or **ge-0/0/3** are unchanged as well, according to the interface configuration. Frames egress the VPLS pseudowire in routing instance **green** with an outer VLAN tag value of 200 pushed on top of the normalized value.

RELATED DOCUMENTATION

https://www.juniper.net/documentation/en_US/junos/information-products/pathway-pages/config-guide-vpns/config-guide-vpns-layer-2.html

Example: Configuring VPLS Pseudowires with Dynamic Profiles—Complex Solutions | 765

Example: Configuring VPLS Pseudowires with Dynamic Profiles—Complex Solutions

IN THIS SECTION

- [Configuration of Routing Instance and Interfaces Without Dynamic Profiles | 765](#)
- [Configuration of Routing Instance and Interfaces Using Dynamic Profiles | 766](#)
- [Configuration of Tag Translation Using Dynamic Profiles | 769](#)

Dynamic profiles for VPLS pseudowires can be helpful in a variety of VLAN configurations. This section explores some of these situations through examples.

NOTE: These examples are not complete router configurations.

All of the examples in this section address the same basic topology. A routing instance **blue** uses a trunk bridge to connect different departments in an organization, each with their own VLANs, at two different sites. The organization uses a BGP-based VPLS with a virtual switch to accomplish this.

Configuration of Routing Instance and Interfaces Without Dynamic Profiles

The basic configuration of routing instance and interfaces without dynamic profiles follows:

```
[edit routing-instance blue]
instance-type virtual-switch;
route-distinguisher 10.1.1.10:1;
vrf-target target:1000:1;
interface ge-3/0/0; # The trunk interface
bridge-domains {
  sales {
    vlan-id 10;
    interface ge-0/0/0.1;
    ... # Other interfaces and statements for Sales
  }
  engineering {
    vlan-id 20;
```



```

        interface ge-1/0/2.0;
        ... # Other interfaces and statements for Engineering
    }
    accounting {
        vlan-id 30;
        interface ge-2/0/3.0;
        ... # Other interfaces and statements for Accounting
    }
    others {
        vlan-id-list [ 40 50 ]; # Other departments
    }
}

protocols vpls {
    site-range 10;
    site sample-site-1 {
        site-identifier 1;
    }
}

... # Other statements for instance Blue

[edit interfaces]
ge-0/0/1 {
    unit 0 {
        vlan-id 100;
    }
}

ge-3/0/0 {
    unit 0 {
        family bridge {
            interface-mode trunk; # This is the trunk
            vlan-id-list [ 10 20 30 40 50 ];
        }
    }
}

... # More interface statements

```

This configuration switches the departmental VLAN traffic (sales, engineering, etc.) bridge domains over the VPLS pseudowire trunk connecting to the other site.

Configuration of Routing Instance and Interfaces Using Dynamic Profiles

Here is how dynamic profiles can be applied to this basic configuration.

First, consider the requirement to push an outer VLAN tag value of 200 onto the VPLS pseudowire frames on egress. Dynamic profiles easily satisfy this requirement.

```
[edit routing-instance green]
instance-type virtual-switch;
... # Other routing instance statements
protocols vpls {
    site-range 10;
    site sample-site-1 {
        site-identifier 1;
    }
    associate-profile green_vpls_pw_1; # Apply profile here
}
... # Other routing instance statements

[edit dynamic-profiles]
green_vpls_pw_1 interfaces $junos-interface-ifd-name {
    unit $junos-underlying-unit-number {
        vlan-id 200; # This is the outer tag
        family bridge {
            interface-mode trunk;
            inner-vlan-id-list [ 10 20 30 40 50 ];
        }
    }
}
}
```

NOTE: This is not a complete router configuration.

With the dynamic profile, a packet in a frame arriving on an interface is classified as belonging to one of the bridge domains (VLANs 10–50). At the egress of the trunk VPLS pseudowire, the outer VLAN tag 200 is pushed onto the frame. At the ingress of the pseudowire at the remote location, the outer VLAN tag 200 is removed and the frame is delivered to the appropriate bridge domain.

But what if the packets associated with the Accounting VLAN are not to be forwarding to the remote site? Dynamic profiles are useful here as well.

This configuration keeps the Accounting frames from reaching the remote site.

```
[edit routing-instances green]
instance-type virtual-switch;
```

```

... # Other routing instance statements
protocols vpls {
    site-range 10;
    site sample-site-1 {
        site-identifier 1;
    }
    associate-profile green_vpls_pw_2; # Apply profile here
}
... # Other routing instance statements

[edit dynamic-profiles]
green_vpls_pw_2 interfaces $junos-interface-ifd-name {
    unit $junos-underlying-unit-number {
        family bridge {
            interface-mode trunk;
            inner-vlan-id-list [ 10 20 40 50 ]; # Removed Accounting VLAN 30
        }
    }
}
}

```

NOTE: This is not a complete router configuration.

In this case, frames arriving on the interfaces are classified according to their bridge domains and switched, if necessary, to the VPLS pseudowire trunk, except for Engineering frames. Engineering frames (VLAN 30) are only switched within the interfaces listed within bridge domain **accounting** and any statically configured trunk interfaces and are prevented from crossing the VPLS pseudowire due to the absence of VLAN 30 on the trunk.

We can combine the two examples and use dynamic profiles to forward the frames (other than **accounting** frames) to the remote site with an out tag of 200.

This configuration keeps the Accounting frames from reaching the remote site and pushes an outer tag of 200 on VPLS pseudowire traffic.

```

[edit routing-instances green]
instance-type virtual-switch;
... # Other routing instance statements
protocols vpls {
    site-range 10;
    site sample-site-1 {
        site-identifier 1;
    }
}

```

```

    }
    associate-profile green_vpls_pw_3; # Apply profile here
}
... # Other routing instance statements

[edit dynamic-profiles]
green_vpls_pw_3 interfaces $junos-interface-ifd-name {
    unit $junos-underlying-unit-number {
        vlan-id 200; # This is the outer tag
        family bridge {
            interface-mode trunk;
            inner-vlan-id-list [ 10 20 40 50 ]; # Removed Accounting VLAN 30
        }
    }
}
}

```

NOTE: This is not a complete router configuration.

In this case, frames arriving on the interfaces are classified according to their bridge domains and switched, if necessary, to the VPLS pseudowire trunk with an outer VLAN tag of 200, except for Engineering frames. Engineering frames (VLAN 30) are only switched within the interfaces listed within bridge domain **accounting** and any statically configured trunk interfaces and are prevented from crossing the VPLS pseudowire due to the absence of VLAN 30 on the trunk.

Configuration of Tag Translation Using Dynamic Profiles

Consider a final case where the bridge domain VLANs need translation at the VPLS pseudowire trunk interface. In this case, **sales** (VLAN 10) is mapped to VLAN 110 and **engineering** (VLAN 20) is mapped to VLAN 120.

This configuration adds tag translation to the VPLS pseudowire traffic.

```

[edit routing-instances green]
instance-type virtual-switch;
... # Other routing instance statements
protocols vpls {
    site-range 10;
    site sample-site-1 {
        site-identifier 1;
    }
}

```

```

    associate-profile green_vpls_pw_4; # Apply profile here
}
... # Other routing instance statements

[edit dynamic-profiles]
green_vpls_pw_4 interfaces $junos-interface-ifd-name {
    unit $junos-underlying-unit-number {
        family bridge {
            interface-mode trunk;
            vlan-id-list [ 10 20 30 40 50 ]; # All VLANs
            vlan-rewrite translate 110 10; # Sales VLAN
            vlan-rewrite translate 120 20; # Engineering VLAN
        }
    }
}

```

NOTE: This is not a complete router configuration.

This translates the **sales** and **engineering** VLAN tags exiting the VPLS pseudowire accordingly. At the ingress of the VPLS pseudowire, VLANs 110 and 120 are translated back to 10 and 20, respectively.

RELATED DOCUMENTATION

https://www.juniper.net/documentation/en_US/junos/information-products/pathway-pages/config-guide-vpns/config-guide-vpns-layer-2.html

Example: Configuring VPLS Pseudowires with Dynamic Profiles—Basic Solutions | 759

Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic

This topic shows how to configure flow-aware transport of pseudowires (FAT) flow labels for forwarding equivalence class (FEC) 128 virtual private LAN service (VPLS) pseudowires for load-balancing MPLS traffic.

Before you begin:

1. Configure the device interfaces and enable MPLS on all the interfaces on the provider edge (PE) router.

2. Configure MPLS and an LSP from the ingress PE router to the remote egress PE router.
3. Configure an interior gateway protocol (IGP) on the PE router and provider (P) routers.
4. Configure the circuits between the PE routers and the customer edge (CE) routers.
5. Configure LDP on all the interfaces.

FAT flow labels enable load-balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. FAT flow labels can be used for LDP-signaled FEC 128 and FEC 129 pseudowires for VPLS and virtual private wire service (VPWS) networks.

You can configure FAT flow labels to be signaled by LDP on FEC 128 VPLS pseudowires by including the `flow-label-transmit` and `flow-label-receive` configuration statements at the `[edit routing-instances instance-name protocols vpls]` hierarchy level. This configuration sets the T bit and R bit advertisement to 1 (the default being 0) in the Sub-TLV field, which is one of the interface parameters of the FEC for the LDP label-mapping message header. This configuration is applicable for all the pseudowires providing full mesh connectivity from the VPLS routing instance to all its neighbors.

To configure the FAT flow label for an FEC 128 VPLS pseudowire, on the ingress PE router:

1. Configure the FEC 128 VPLS routing instance.

```
[edit]
user@PE1# set routing-instances instance-name instance-type vpls
user@PE1# set routing-instances instance-name interface interface-name
user@PE1# set routing-instances instance-name protocols vpls vpls-id vpls-id
user@PE1# set routing-instances instance-name protocols vpls neighbor neighbor-id
user@PE1# set routing-instances instance-name protocols vpls neighbor neighbor-id
```

2. Configure the routing instance to signal the capability to push the flow label in the transmit direction to the remote PE router.

```
[edit routing-instances instance-name protocols vpls]
user@PE1# set flow-label-transmit
```

3. Configure the routing instance to signal the capability to pop the flow label in the receive direction to the remote PE router.

```
[edit routing-instances instance-name protocols vpls]
user@PE1# set flow-label-receive
```

4. Verify and commit the configuration.

For example:

```
[edit routing-instances]
user@PE1# show
ldp-fec128-signaled-vpls {
    instance-type vpls;
    interface ge-0/0/1.0;
    protocols {
        vpls {
            vpls-id 100;
            flow-label-transmit;
            flow-label-receive;
        }
    }
}
```

5. Repeat the configuration on the remote egress PE router.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

[Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

[Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)

[FAT Flow Labels Overview | 503](#)

Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic

This topic shows how to configure flow-aware transport of pseudowires (FAT) flow labels for forwarding equivalence class (FEC) 129 virtual private LAN service (VPLS) pseudowires for load-balancing MPLS traffic.

Before you begin:

1. Configure the device interfaces and enable MPLS on all the interfaces.
2. Configure MPLS and an LSP from the ingress provider edge (PE) router to the remote PE router.

3. Configure IBGP sessions between the PE routers.
4. Configure an interior gateway protocol (IGP) on the PE router and provider (P) routers.
5. Configure the circuits between the PE routers and the customer edge (CE) routers.
6. Configure LDP on all the interfaces.

FAT flow labels enable load-balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. FAT flow labels can be used for LDP-signaled FEC 128 and FEC 129 pseudowires for VPLS and virtual private wire service (VPWS) networks.

You can configure FAT flow labels to be signaled by LDP on FEC 129 VPLS pseudowires by including the `flow-label-transmit` and `flow-label-receive` configuration statements at the `[edit routing-instances instance-name protocols vpls]` hierarchy level. This configuration sets the T bit and R bit advertisement to 1 (the default being 0) in the Sub-TLV field, which is part one of the interface parameters of the FEC for the LDP label-mapping message header. This configuration is applicable for all the pseudowires providing full mesh connectivity from the VPLS routing instance to all its neighbors.

To configure the FAT flow label for an FEC 129 VPLS pseudowire, on the ingress PE router:

1. Configure the FEC 129 VPLS routing instance.

```
[edit]
user@PE1# set routing-instances instance-name instance-type vpls
user@PE1# set routing-instances instance-name interface interface-name
user@PE1# set routing-instances instance-name route-distinguisher (as-number:id | ip-address:id)
user@PE1# set routing-instances instance-name l2vpn-id (as-number:x:y | ip-address:id)
user@PE1# set routing-instances instance-name vrf-target target:x:y
```

2. Configure the routing instance to signal the capability to push the flow label in the transmit direction to the remote PE router.

```
[edit routing-instances instance-name protocols vpls]
user@PE1# set flow-label-transmit
```

3. Configure the routing instance to signal the capability to pop the flow label in the receive direction to the remote PE router.

```
[edit routing-instances instance-name protocols vpls]
user@PE1# set flow-label-receive
```


4. Verify and commit the configuration.

For example:

```
[edit routing-instances]
user@PE1# show
ldp-fec129-signaled-vpls {
    instance-type vpls;
    interface fe-0/0/0.0;
    route-distinguisher 10.255.245.45:100;
    l2vpn-id l2vpn-id:100:100;
    vrf-target target:100:100;
    protocols {
        vpls {
            flow-label-transmit;
            flow-label-receive;
        }
    }
}
```

5. Repeat the configuration on the remote egress PE router.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

[Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)

[Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

[FAT Flow Labels Overview | 503](#)

Example: Configuring H-VPLS BGP-Based and LDP-Based VPLS Interoperation

IN THIS SECTION

- [Requirements | 775](#)
- [Overview | 775](#)
- [Configuration | 776](#)
- [Verification | 793](#)

This example shows how to configure the hierarchical virtual private LAN service (H-VPLS) in a scenario that uses both LDP-based VPLS and BGP-based VPLS interoperating in a multihoming deployment. This scenario is useful when a customer deployment has the two different types of VPLS in use, and you need to integrate them. Another example is when ISP-A is running BGP-based VPLS and ISP-B is running the LDP-based VPLS, and the two ISPs are merging their networks.

Requirements

No special configuration beyond device initialization is required before configuring this example.

Overview


In this example, Device PE2 and Device PE3 are acting as internetworking provider edge (PE) routers with BGP-based as well as LDP-based VPLS termination.

The devices in this example have the following roles:

- BGP VPLS only PE—Device PE1
- LDP VPLS only PE—Device PE4
- BGP-LDP VPLS PE—Device PE2 and Device PE3

Figure 56 on page 776 shows the topology used in this example.

Figure 56: H-VPLS with LDP-Based and BGP-Based VPLS Interoperation



From Device PE4, the pseudowire to Device PE3 is the primary or working path. The pseudowire Device PE2 is the backup path.

"CLI Quick Configuration" on page 776 shows the configuration for all of the devices in Figure 56 on page 776. The section "Step-by-Step Procedure" on page 781 describes the steps on Device PE1, Device PE2, and Device PE4.

Configuration

IN THIS SECTION

- Procedure | 776

Procedure

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device PE1

```

set interfaces ge-2/0/5 encapsulation ethernet-vpls
set interfaces ge-2/0/5 unit 0 description to_CE1
set interfaces ge-2/0/5 unit 0 family vpls
set interfaces fe-2/0/9 unit 0 description to_PE2
set interfaces fe-2/0/9 unit 0 family inet address 10.10.3.1/30
set interfaces fe-2/0/9 unit 0 family mpls
set interfaces fe-2/0/10 unit 0 description to_PE3
set interfaces fe-2/0/10 unit 0 family inet address 10.10.1.1/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.1/24
set protocols mpls interface fe-2/0/10.0
set protocols mpls interface fe-2/0/9.0
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface fe-2/0/9.0
set protocols ldp interface lo0.0
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.0.2.1
set protocols bgp group internal-peers family l2vpn signaling
set protocols bgp group internal-peers neighbor 192.0.2.2
set protocols bgp group internal-peers neighbor 192.0.2.3
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ospf area 0.0.0.0 interface fe-2/0/9.0
set routing-instances h-vpls-PE1 instance-type vpls
set routing-instances h-vpls-PE1 interface ge-2/0/5.0
set routing-instances h-vpls-PE1 route-distinguisher 1:1
set routing-instances h-vpls-PE1 vrf-target target:1:1
set routing-instances h-vpls-PE1 protocols vpls interface ge-2/0/5.0
set routing-instances h-vpls-PE1 protocols vpls site PE1-vpls site-identifier 2
set routing-options autonomous-system 64510

```

Device PE2

```

set interfaces ge-2/0/6 encapsulation ethernet-vpls
set interfaces ge-2/0/6 unit 0 description to_CE2
set interfaces ge-2/0/6 unit 0 family vpls
set interfaces fe-2/0/8 unit 0 description to_PE3
set interfaces fe-2/0/8 unit 0 family inet address 10.10.4.2/30
set interfaces fe-2/0/8 unit 0 family mpls

```

```

set interfaces fe-2/0/9 unit 0 description to_PE4
set interfaces fe-2/0/9 unit 0 family inet address 10.10.5.1/30
set interfaces fe-2/0/9 unit 0 family mpls
set interfaces fe-2/0/10 unit 0 description to_PE1
set interfaces fe-2/0/10 unit 0 family inet address 10.10.3.2/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.2/24
set protocols mpls interface fe-2/0/10.0
set protocols mpls interface fe-2/0/9.0
set protocols mpls interface fe-2/0/8.0
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface fe-2/0/9.0
set protocols ldp interface fe-2/0/8.0
set protocols ldp interface lo0.0
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 192.0.2.2
set protocols bgp group ibgp family l2vpn signaling
set protocols bgp group ibgp neighbor 192.0.2.3
set protocols bgp group ibgp neighbor 192.0.2.1
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ospf area 0.0.0.0 interface fe-2/0/9.0
set protocols ospf area 0.0.0.0 interface fe-2/0/8.0
set routing-instances h-vpls-PE2 instance-type vpls
set routing-instances h-vpls-PE2 interface ge-2/0/6.0
set routing-instances h-vpls-PE2 route-distinguisher 1:2
set routing-instances h-vpls-PE2 vrf-target target:1:1
set routing-instances h-vpls-PE2 protocols vpls interface ge-2/0/6.0
set routing-instances h-vpls-PE2 protocols vpls site PE2-vpls site-identifier 1
set routing-instances h-vpls-PE2 protocols vpls site PE2-vpls multi-homing
set routing-instances h-vpls-PE2 protocols vpls site PE2-vpls mesh-group h-vpls-PE2
set routing-instances h-vpls-PE2 protocols vpls vpls-id 100
set routing-instances h-vpls-PE2 protocols vpls mesh-group h-vpls-PE2 vpls-id 100
set routing-instances h-vpls-PE2 protocols vpls mesh-group h-vpls-PE2 local-switching
set routing-instances h-vpls-PE2 protocols vpls mesh-group h-vpls-PE2 neighbor 192.0.2.4
set routing-options autonomous-system 64510

```

Device PE3

```

set interfaces fe-2/0/8 unit 0 description to_PE2
set interfaces fe-2/0/8 unit 0 family inet address 10.10.4.1/30
set interfaces fe-2/0/8 unit 0 family mpls

```

```

set interfaces fe-2/0/9 unit 0 description to_PE4
set interfaces fe-2/0/9 unit 0 family inet address 10.10.6.1/30
set interfaces fe-2/0/9 unit 0 family mpls
set interfaces fe-2/0/10 unit 0 description to_PE1
set interfaces fe-2/0/10 unit 0 family inet address 10.10.1.2/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces ge-2/1/3 encapsulation ethernet-vpls
set interfaces ge-2/1/3 unit 0 description to_CE3
set interfaces ge-2/1/3 unit 0 family vpls
set interfaces lo0 unit 0 family inet address 192.0.2.3/24
set protocols mpls interface fe-2/0/10.0
set protocols mpls interface fe-2/0/8.0
set protocols mpls interface fe-2/0/9.0
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface fe-2/0/9.0
set protocols ldp interface fe-2/0/8.0
set protocols ldp interface lo0.0
set protocols bgp group internal-peers type internal
set protocols bgp group internal-peers local-address 192.0.2.3
set protocols bgp group internal-peers family l2vpn signaling
set protocols bgp group internal-peers neighbor 192.0.2.2
set protocols bgp group internal-peers neighbor 192.0.2.1
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ospf area 0.0.0.0 interface fe-2/0/8.0
set protocols ospf area 0.0.0.0 interface fe-2/0/9.0
set routing-instances h-vpls-PE3 instance-type vpls
set routing-instances h-vpls-PE3 interface ge-2/1/3.0
set routing-instances h-vpls-PE3 route-distinguisher 1:3
set routing-instances h-vpls-PE3 vrf-target target:1:1
set routing-instances h-vpls-PE3 protocols vpls interface ge-2/1/3.0
set routing-instances h-vpls-PE3 protocols vpls site PE3-vpls site-identifier 1
set routing-instances h-vpls-PE3 protocols vpls site PE3-vpls multi-homing
set routing-instances h-vpls-PE3 protocols vpls site PE3-vpls mesh-group h-vpls-PE3
set routing-instances h-vpls-PE3 protocols vpls vpls-id 100
set routing-instances h-vpls-PE3 protocols vpls mesh-group h-vpls-PE3 vpls-id 100
set routing-instances h-vpls-PE3 protocols vpls mesh-group h-vpls-PE3 local-switching
set routing-instances h-vpls-PE3 protocols vpls mesh-group h-vpls-PE3 neighbor 192.0.2.4
set routing-options autonomous-system 64510

```

Device PE4

```

set interfaces fe-2/0/9 unit 0 description to_PE3
set interfaces fe-2/0/9 unit 0 family inet address 10.10.6.2/30
set interfaces fe-2/0/9 unit 0 family mpls
set interfaces fe-2/0/10 unit 0 description to_PE2
set interfaces fe-2/0/10 unit 0 family inet address 10.10.5.2/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces ge-2/1/7 encapsulation ethernet-vpls
set interfaces ge-2/1/7 unit 0 description to_CE4
set interfaces ge-2/1/7 unit 0 family vpls
set interfaces lo0 unit 0 family inet address 192.0.2.4/24
set protocols mpls interface fe-2/0/10.0
set protocols mpls interface fe-2/0/9.0
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface fe-2/0/9.0
set protocols ldp interface lo0.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ospf area 0.0.0.0 interface fe-2/0/9.0
set routing-instances ldp-vpls instance-type vpls
set routing-instances ldp-vpls interface ge-2/1/7.0
set routing-instances ldp-vpls protocols vpls vpls-id 100
set routing-instances ldp-vpls protocols vpls neighbor 192.0.2.3
set routing-instances ldp-vpls protocols vpls neighbor 192.0.2.2

```

Device CE1

```

set interfaces ge-2/0/8 unit 0 description to_PE1
set interfaces ge-2/0/8 unit 0 family inet address 172.16.0.1/24
set interfaces lo0 unit 0 family inet address 10.255.14.214/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/8.0

```

Device CE2

```

set interfaces ge-2/1/5 unit 0 description to_PE2
set interfaces ge-2/1/5 unit 0 family inet address 172.16.0.2/24
set interfaces lo0 unit 0 family inet address 10.255.14.215/32

```

```
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/5.0
```

Device CE3

```
set interfaces ge-2/0/9 unit 0 description to_PE3
set interfaces ge-2/0/9 unit 0 family inet address 172.16.0.3/24
set interfaces lo0 unit 0 family inet address 10.255.14.218/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/9.0
```

Device CE4

```
set interfaces ge-2/1/6 unit 0 description to_PE4
set interfaces ge-2/1/6 unit 0 family inet address 172.16.0.4/24
set interfaces lo0 unit 0 family inet address 10.255.14.219/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/6.0
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure the BGP-based VPLS PE device:

1. Configure the interfaces.

On the device interface that connects to the customer edge, enable VPLS encapsulation and the VPLS address family.

On the core-facing interfaces, enable MPLS labels.

```
[edit interfaces]
user@PE1# set ge-2/0/5 encapsulation ethernet-vpls
user@PE1# set ge-2/0/5 unit 0 description to_CE1
user@PE1# set ge-2/0/5 unit 0 family vpls
user@PE1# set fe-2/0/10 unit 0 description to_PE3
user@PE1# set fe-2/0/10 unit 0 family inet address 10.10.1.1/30
user@PE1# set fe-2/0/10 unit 0 family mpls
```



```

user@PE1# set fe-2/0/9 unit 0 description to_PE2
user@PE1# set fe-2/0/9 unit 0 family inet address 10.10.3.1/30
user@PE1# set fe-2/0/9 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 192.0.2.1/24

```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```

[edit protocols mpls]
user@PE1# set interface fe-2/0/10.0
user@PE1# set interface fe-2/0/9.0
[edit protocols ldp ]
user@PE1# set interface fe-2/0/10.0
user@PE1# set interface fe-2/0/9.0
user@PE1# set interface lo0.0

```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```

[edit protocols ospf area 0.0.0.0]
user@PE1# set interface lo0.0 passive
user@PE1# set interface fe-2/0/10.0
user@PE1# set interface fe-2/0/9.0

```

4. Configure BGP with Layer 2 VPN signaling.

The `l2vpn signaling` statement enables support for both VPLS and Layer 2 VPN advertisement under the same network layer reachability information (NLRI).

The internal IBGP (IBGP) full mesh includes Device PE1, Device PE2, and Device PE3. Device PE4 is not included.

```

[edit protocols bgp group internal-peers]
user@PE1# set type internal
user@PE1# set local-address 192.0.2.1
user@PE1# set family l2vpn signaling
user@PE1# set neighbor 192.0.2.2
user@PE1# set neighbor 192.0.2.3

```

5. Configure the VPLS routing instance.

Because this is BGP-based VPLS, include a route distinguisher, a VRF target, and a site name and ID.

```
[edit routing-instances h-vpls-PE1]
user@PE1# set instance-type vpls
user@PE1# set interface ge-2/0/5.0
user@PE1# set route-distinguisher 1:1
user@PE1# set vrf-target target:1:1
[edit routing-instances h-vpls-PE1 protocols vpls]
user@PE1# set interface ge-2/0/5.0
user@PE1# set site PE1-vpls site-identifier 2
```

6. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@PE1# set autonomous-system 64510
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure the BGP-LDP-based VPLS PE device:

1. Configure the interfaces.

On the PE-r device interface that connects to the customer edge, configure one of the VPLS encapsulation types and the VPLS address family. This enables VPLS.

On the core-facing interfaces, enable MPLS labels.

```
[edit interfaces]
user@PE2# set ge-2/0/6 encapsulation ethernet-vpls
user@PE2# set ge-2/0/6 unit 0 description to_CE2
user@PE2# set ge-2/0/6 unit 0 family vpls
user@PE2# set fe-2/0/10 unit 0 description to_PE1
user@PE2# set fe-2/0/10 unit 0 family inet address 10.10.3.2/30
user@PE2# set fe-2/0/10 unit 0 family mpls
user@PE2# set fe-2/0/9 unit 0 description to_PE4
user@PE2# set fe-2/0/9 unit 0 family inet address 10.10.5.1/30
```

```

user@PE2# set fe-2/0/9 unit 0 family mpls
user@PE2# set fe-2/0/8 unit 0 description to_PE3
user@PE2# set fe-2/0/8 unit 0 family inet address 10.10.4.2/30
user@PE2# set fe-2/0/8 unit 0 family mpls
user@PE2# set lo0 unit 0 family inet address 192.0.2.2/24

```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```

[edit protocols mpls]
user@PE2# set interface fe-2/0/10.0
user@PE2# set interface fe-2/0/9.0
user@PE2# set interface fe-2/0/8.0
[edit protocols ldp]
user@PE2# set interface fe-2/0/10.0
user@PE2# set interface fe-2/0/9.0
user@PE2# set interface fe-2/0/8.0
user@PE2# set interface lo0.0

```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```

[edit protocols ospf area 0.0.0.0]
user@PE2# set interface lo0.0 passive
user@PE2# set interface fe-2/0/10.0
user@PE2# set interface fe-2/0/9.0
user@PE2# set interface fe-2/0/8.0

```

4.

```

[edit protocols bgp group ibgp]
user@PE2# set type internal
user@PE2# set local-address 192.0.2.2
user@PE2# set family l2vpn signaling
user@PE2# set neighbor 192.0.2.3
user@PE2# set neighbor 192.0.2.1

```

5. Configure VPLS.

The `vpls-id` statement enables LDP signaling for the VPLS instance.

```
[edit routing-instances h-vpls-PE2]
user@PE2# set instance-type vpls
user@PE2# set interface ge-2/0/6.0
user@PE2# set route-distinguisher 1:2
user@PE2# set vrf-target target:1:1
[edit routing-instances h-vpls-PE2 protocols vpls]
user@PE2# set interface ge-2/0/6.0
user@PE2# set site PE2-vpls site-identifier 1
user@PE2# set site PE2-vpls multi-homing
user@PE2# set site PE2-vpls mesh-group h-vpls-PE2
user@PE2# set vpls-id 100
user@PE2# set mesh-group h-vpls-PE2 vpls-id 100
user@PE2# set mesh-group h-vpls-PE2 local-switching
user@PE2# set mesh-group h-vpls-PE2 neighbor 192.0.2.4
```

6.

```
[edit routing-options]
user@PE2# set autonomous-system 64510
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure LDP-based VPLS PE device:

1. Configure the interfaces.

On the PE-r device interface that connects to the customer edge, configure one of the VPLS encapsulation types and the VPLS address family. This enables VPLS.

On the core-facing interfaces, enable MPLS labels.

```
[edit interfaces]
user@PE4# set fe-2/0/10 unit 0 description to_PE2
user@PE4# set fe-2/0/10 unit 0 family inet address 10.10.5.2/30
user@PE4# set fe-2/0/10 unit 0 family mpls
user@PE4# set fe-2/0/9 unit 0 description to_PE3
```

```

user@PE4# set fe-2/0/9 unit 0 family inet address 10.10.6.2/30
user@PE4# set fe-2/0/9 unit 0 family mpls
user@PE4# set ge-2/1/7 encapsulation ethernet-vpls
user@PE4# set ge-2/1/7 unit 0 description to_CE4
user@PE4# set ge-2/1/7 unit 0 family vpls
user@PE4# set lo0 unit 0 family inet address 192.0.2.4/24

```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```

[edit protocols mpls]
user@PE4# set interface fe-2/0/10.0
user@PE4# set interface fe-2/0/9.0
[edit protocols ldp]
user@PE4# set interface fe-2/0/10.0
user@PE4# set interface fe-2/0/9.0
user@PE4# set interface lo0.0

```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```

[edit protocols ospf area 0.0.0.0]
user@PE4# set interface lo0.0 passive
user@PE4# set interface fe-2/0/10.0
user@PE4# set interface fe-2/0/9.0

```

4. Configure VPLS.

The vpls-id statement enables LDP signaling for the VPLS instance.

```

[edit routing-instances ldp-vpls]
user@PE4# set instance-type vpls
user@PE4# set interface ge-2/1/7.0
user@PE4# set protocols vpls vpls-id 100
[edit routing-instances ldp-vpls protocols vpls]
user@PE4# set neighbor 192.0.2.3
user@PE4# set neighbor 192.0.2.2

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

Device PE1

```
user@PE1# show interfaces
ge-2/0/5 {
  encapsulation ethernet-vpls;
  unit 0 {
    description to_CE1;
    family vpls;
  }
}
fe-2/0/9 {
}
  unit 0 {
    description to_PE2;
    family inet {
      address 10.10.3.1/30;
    }
    family mpls;
  }
}
fe-2/0/10 {
  unit 0 {
    description to_PE3;
    family inet {
      address 10.10.1.1/30;
    }
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.1/24;
    }
  }
}
```

```

    }
}

```

```

user@PE1# show protocols
mpls {
    interface fe-2/0/10.0;
    interface fe-2/0/9.0;
}
bgp {
    group internal-peers {
        type internal;
        local-address 192.0.2.1;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.2;
        neighbor 192.0.2.3;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
        interface fe-2/0/10.0;
        interface fe-2/0/9.0;
    }
}
ldp {
    interface fe-2/0/10.0;
    interface fe-2/0/9.0;
    interface lo0.0;
}

```

```

user@PE1# show routing-instances
h-vpls-PE1 {
    instance-type vpls;
    interface ge-2/0/5.0;
    route-distinguisher 1:1;
    vrf-target target:1:1;
}

```

```

protocols {
    vpls {
        interface ge-2/0/5.0;
        site PE1-vpls {
            site-identifier 2;
        }
    }
}

```

```

user@PE1# show routing-options
autonomous-system 64510;

```

Device PE2

```

user@PE2# show interfaces
ge-2/0/6 {
    encapsulation ethernet-vpls;
    unit 0 {
        description to_CE2;
        family vpls;
    }
}
fe-2/0/8 {
    unit 0 {
        description to_PE3;
        family inet {
            address 10.10.4.2/30;
        }
        family mpls;
    }
}
fe-2/0/9 {
    unit 0 {
        description to_PE4;
        family inet {
            address 10.10.5.1/30;
        }
        family mpls;
    }
}

```



```

fe-2/0/10 {
    unit 0 {
        description to_PE1;
        family inet {
            address 10.10.3.2/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}

```

```

user@PE2# show protocols
mpls {
    interface fe-2/0/10.0;
    interface fe-2/0/9.0;
    interface fe-2/0/8.0;
}
bgp {
    group ibgp {
        type internal;
        local-address 192.0.2.2;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.3;
        neighbor 192.0.2.1;
    }
}
ospf {
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
        interface fe-2/0/10.0;
        interface fe-2/0/9.0;

```

```

        interface fe-2/0/8.0;
    }
}
ldp {
    interface fe-2/0/10.0;
    interface fe-2/0/9.0;
    interface fe-2/0/8.0;
    interface lo0.0;
}

```

```

user@PE2# show routing-instances
h-vpls-PE2 {
    instance-type vpls;
    interface ge-2/0/6.0;
    route-distinguisher 1:2;
    vrf-target target:1:1;
    protocols {
        vpls {
            interface ge-2/0/6.0;
            site PE2-vpls {
                site-identifier 1;
                multi-homing;
                mesh-group h-vpls-PE2;
            }
            vpls-id 100;
            mesh-group h-vpls-PE2 {
                vpls-id 100;
                local-switching;
                neighbor 192.0.2.4;
            }
        }
    }
}

```

```

user@PE2# show routing-options
autonomous-system 64510;

```

Device PE4

```
user@PE4# show interfaces
ge-2/1/7 {
  encapsulation ethernet-vpls;
  unit 0 {
    description to_CE4;
    family vpls;
  }
}
fe-2/0/9 {
  unit 0 {
    description to_PE3;
    family inet {
      address 10.10.6.2/30;
    }
    family mpls;
  }
}
fe-2/0/10 {
  unit 0 {
    description to_PE2;
    family inet {
      address 10.10.5.2/30;
    }
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.4/24;
    }
  }
}
```

```
user@PE4# show protocols
mpls {
  interface fe-2/0/9.0;
  interface fe-2/0/10.0;
}
```

```
ospf {
  area 0.0.0.0 {
    interface lo0.0 {
      passive;
    }
    interface fe-2/0/9.0;
    interface fe-2/0/10.0;
  }
}
ldp {
  interface fe-2/0/10.0;
  interface fe-2/0/9.0;
  interface lo0.0;
}
```

```
user@PE4# show routing-instances
ldp-vpls {
  instance-type vpls;
  interface ge-2/1/7.0;
  protocols {
    vpls {
      vpls-id 100;
      neighbor 192.0.2.3;
      neighbor 192.0.2.2;
    }
  }
}
```

If you are done configuring the devices, enter **commit** from configuration mode.

Verification

IN THIS SECTION

- [Verifying the VPLS Connections | 794](#)
- [Manually Triggering a Switch from the Active Pseudowire to the Backup Pseudowire | 798](#)
- [Checking Connectivity | 803](#)
- [Checking the BGP Layer 2 VPN Routing Tables | 804](#)

● [Checking the Layer 2 Circuit Routing Tables](#) | 804

Confirm that the configuration is working properly. In a multihoming scenario with BGP-LDP VPLS, the LDP pseudowires are in the down state for the backup PE (Device PE2). Whereas on the LDP-only VPLS PE (Device PE4), the pseudowires to the primary and backup BGP-LDP PE devices are in the up state.

Verifying the VPLS Connections

Purpose

Verify that the VPLS connections are working as expected.

Action

From operational mode, enter the `show vpls connections` command.

```
user@PE1> show vpls connections
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch
```

Legend for interface status

Up -- operational

Dn -- down

Instance: h-vpls-PE1

Local site: PE1-vpls (2)

connection-site	Type	St	Time last up	# Up trans
1	rmt	Up	Oct 16 16:52:27 2012	1

Remote PE: 192.0.2.2, Negotiated control-word: No

Incoming label: 800016, Outgoing label: 800009

Local interface: vt-2/0/10.51380738, Status: Up, Encapsulation: VPLS

Description: Intf - vpls h-vpls-PE1 local site 2 remote site 1

user@PE2> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid NC -- interface encapsulation not CCC/TCC/VPLS

EM -- encapsulation mismatch WE -- interface and instance encaps not same

VC-Dn -- Virtual circuit down NP -- interface hardware not present

CM -- control-word mismatch -> -- only outbound connection is up

CN -- circuit not provisioned <- -- only inbound connection is up

OR -- out of range Up -- operational

OL -- no outgoing label Dn -- down

LD -- local site signaled down CF -- call admission control failure

RD -- remote site signaled down SC -- local and remote site ID collision

LN -- local site not designated LM -- local site ID not minimum designated

RN -- remote site not designated RM -- remote site ID not minimum designated

XX -- unknown connection status IL -- no incoming label

MM -- MTU mismatch MI -- Mesh-Group ID not available

BK -- Backup connection ST -- Standby connection

PF -- Profile parse failure PB -- Profile busy

RS -- remote site standby SN -- Static Neighbor

LB -- Local site not best-site RB -- Remote site not best-site

VM -- VLAN ID mismatch

Legend for interface status

Up -- operational

Dn -- down

Instance: h-vpls-PE2

BGP-VPLS State

Local site: PE2-vpls (1)

connection-site	Type	St	Time last up	# Up trans
1	rmt	RN		
2	rmt	Up	Oct 16 17:12:31 2012	1

Remote PE: 192.0.2.1, Negotiated control-word: No

Incoming label: 800257, Outgoing label: 800000

Local interface: vt-2/0/10.118489089, Status: Up, Encapsulation: VPLS

Description: Intf - vpls h-vpls-PE2 local site 1 remote site 2

LDP-VPLS State

VPLS-id: 100

Mesh-group connections: h-vpls-PE2

Neighbor	Type	St	Time last up	# Up trans
192.0.2.4(vpls-id 100)	rmt	Up	Oct 16 17:12:30 2012	1

Remote PE: 192.0.2.4, Negotiated control-word: No

Incoming label: 800000, Outgoing label: 800001

Negotiated PW status TLV: No

Local interface: vt-2/0/10.118489088, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls h-vpls-PE2 neighbor 192.0.2.4 vpls-id 100

user@PE3> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor

LB -- Local site not best-site RB -- Remote site not best-site
 VM -- VLAN ID mismatch

Legend for interface status

Up -- operational

Dn -- down

Instance: h-vpls-PE3

BGP-VPLS State

Local site: PE3-vpls (1)

connection-site	Type	St	Time last up	# Up trans
1	rmt	LN		
2	rmt	LN		

LDP-VPLS State

VPLS-id: 100

Mesh-group connections: h-vpls-PE3

Neighbor	Type	St	Time last up	# Up trans
192.0.2.4(vpls-id 100)	rmt	LN		

user@PE4> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

Legend for interface status

Up -- operational

Dn -- down

Instance: ldp-vpls

VPLS-id: 100

Neighbor	Type	St	Time last up	# Up trans
192.0.2.2(vpls-id 100)	rmt	Up	Oct 16 17:12:23 2012	1
Remote PE: 192.0.2.2, Negotiated control-word: No				
Incoming label: 800001, Outgoing label: 800000				
Negotiated PW status TLV: No				
Local interface: vt-2/0/10.17825793, Status: Up, Encapsulation: ETHERNET				
Description: Intf - vpls ldp-vpls neighbor 192.0.2.2 vpls-id 100				
192.0.2.3(vpls-id 100)	rmt	Up	Oct 16 17:12:20 2012	1
Remote PE: 192.0.2.3, Negotiated control-word: No				
Incoming label: 800000, Outgoing label: 800000				
Negotiated PW status TLV: No				
Local interface: vt-2/0/10.17825792, Status: Up, Encapsulation: ETHERNET				
Description: Intf - vpls ldp-vpls neighbor 192.0.2.3 vpls-id 100				

Meaning

On Device PE1, the BGP-VPLS connection to Device PE2 is up. In a steady-state condition, Device PE2 is the primary router and has all pseudowires terminating on it. Traffic flows from CE1 to PE1 to PE2 to PE4 to CE4.

On Device PE2, the BGP-VPLS connection to Device PE1 is up. The connection to Device PE3 is in the RN state. The LDP-VPLS connection to Device PE4 is up.

On Device PE3, all VPLS connections are in the LN state. This is expected because Device PE3 is the backup.

On Device PE4, the LDP-only VPLS router, the primary pseudowire to Device PE2 and the backup pseudowire to Device PE3 are in the up state.

Manually Triggering a Switch from the Active Pseudowire to the Backup Pseudowire

Purpose

Verify that when Device PE2 becomes unavailable, the traffic flow shifts to Device PE3.

Action

1. On Device PE2, deactivate the interfaces.

```
user@PE2# deactivate interfaces
user@PE2# commit
```

2. Rerun the show vpls connections command on all of the PE devices.

```
user@PE1> show vpls connections
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status
Up -- operational
Dn -- down

Instance: h-vpls-PE1
Local site: PE1-vpls (2)
  connection-site      Type  St      Time last up      # Up trans
  1                   rmt   Up      Oct 17 12:24:01 2012      2
  Remote PE: 192.0.2.3, Negotiated control-word: No
```

```
Incoming label: 800000, Outgoing label: 800257
Local interface: vt-2/0/10.84934656, Status: Up, Encapsulation: VPLS
Description: Intf - vpls h-vpls-PE1 local site 2 remote site 1
```

```
user@PE2> show vpls connections
```

```
Layer-2 VPN connections:
```

```
Legend for connection status (St)
```

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

```
Legend for interface status
```

```
Up -- operational
```

```
Dn -- down
```

```
Instance: h-vpls-PE2
```

```
BGP-VPLS State
```

```
Local site: PE2-vpls (1)
```

```
LDP-VPLS State
```

```
VPLS-id: 100
```

```
Mesh-group connections: h-vpls-PE2
```

Neighbor	Type	St	Time last up	# Up trans
192.0.2.4(vpls-id 100)	rmt	OL		

```
user@PE3> show vpls connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

Legend for interface status

Up -- operational

Dn -- down

Instance: h-vpls-PE3

BGP-VPLS State

Local site: PE3-vpls (1)

connection-site	Type	St	Time last up	# Up trans
2	rmt	Up	Oct 17 12:24:01 2012	1

Remote PE: 192.0.2.1, Negotiated control-word: No

Incoming label: 800257, Outgoing label: 800000

Local interface: vt-2/0/10.135266304, Status: Up, Encapsulation: VPLS

Description: Intf - vpls h-vpls-PE3 local site 1 remote site 2

LDP-VPLS State

VPLS-id: 100

Mesh-group connections: h-vpls-PE3

Neighbor	Type	St	Time last up	# Up trans
192.0.2.4(vpls-id 100)	rmt	Up	Oct 17 12:24:02 2012	1

Remote PE: 192.0.2.4, Negotiated control-word: No
Incoming label: 800000, Outgoing label: 800000
Negotiated PW status TLV: No
Local interface: vt-2/0/10.135266305, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls h-vpls-PE3 neighbor 192.0.2.4 vpls-id 100

user@PE4> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

Legend for interface status

Up -- operational
Dn -- down

Instance: ldp-vpls

VPLS-id: 100

Neighbor	Type	St	Time last up	# Up trans
192.0.2.2(vpls-id 100)	rmt	OL		
192.0.2.3(vpls-id 100)	rmt	Up	Oct 16 17:12:20 2012	1

```

Remote PE: 192.0.2.3, Negotiated control-word: No
Incoming label: 800000, Outgoing label: 800000
Negotiated PW status TLV: No
Local interface: vt-2/0/10.17825792, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls ldp-vpls neighbor 192.0.2.3 vpls-id 100

```

Meaning

On Device PE1, the BGP-VPLS connection to Device PE3 is up. Traffic flows from CE1 to PE1 to PE3 to PE4 to CE4.

On Device PE2, the BGP-VPLS connection to Device PE1 is in the OL state.

On Device PE3, all VPLS connections are up.

On Device PE4, the VPLS connection to Device PE2 is in the OL state. The VPLS connection to Device PE3 is up.

If you reactivate the interfaces on Device PE2, the connections revert to their previous state and traffic flow.

Checking Connectivity

Purpose

Verify that Device CE1 can ping Device CE4.

Action

```

user@CE1> ping 10.255.14.219

PING 10.255.14.219 (10.255.14.219): 56 data bytes
64 bytes from 10.255.14.219: icmp_seq=0 ttl=64 time=1.149 ms
64 bytes from 10.255.14.219: icmp_seq=1 ttl=64 time=0.779 ms
^C
--- 10.255.14.219 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.779/0.964/1.149/0.185 ms

```

Meaning

The output shows that VPLS is operational.

Checking the BGP Layer 2 VPN Routing Tables

Purpose

Verify that the VPLS routes are learned from BGP.

Action

```
user@PE1> show route table bgp.l2vpn.0
bgp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1:3:1:1/96
    *[BGP/170] 20:00:11, localpref 100, from 192.0.2.3
    AS path: I, validation-state: unverified
    > to 10.10.1.2 via fe-2/0/10.0

user@PE3> show route table bgp.l2vpn.0
bgp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1:1:2:1/96
    *[BGP/170] 20:00:11, localpref 100, from 192.0.2.1
    AS path: I, validation-state: unverified
    > to 10.10.1.1 via fe-2/0/10.0
```

Checking the Layer 2 Circuit Routing Tables

Purpose

Verify that the VPLS routes are learned from LDP.

Action

```
user@PE3> show route table l2circuit.0
l2circuit.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
```

```

+ = Active Route, - = Last Active, * = Both

192.0.2.4:NoCtrlWord:5:100:Local/96
    *[VPLS/7] 01:30:11, metric2 1
    > to 10.10.6.2 via fe-2/0/9.0
192.0.2.4:NoCtrlWord:5:100:Remote/96
    *[LDP/9] 20:41:57
    Discard
user@PE4> show route table bgp.l2vpn.0
l2circuit.0: 3 destinations, 3 routes (2 active, 0 holddown, 1 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3:NoCtrlWord:5:100:Local/96
    *[VPLS/7] 20:42:51, metric2 1
    > to 10.10.6.1 via fe-2/0/9.0
192.0.2.3:NoCtrlWord:5:100:Remote/96
    *[LDP/9] 20:41:57
    Discard

```

RELATED DOCUMENTATION

[Application Note: Demystifying H-VPLS](#)

[Example: Configuring H-VPLS Without VLANs | 861](#)

[Example: Configuring H-VPLS With VLANs | 843](#)

[Redundant Pseudowires for Layer 2 Circuits and VPLS | 223](#)

[Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS | 226](#)

Example: Configuring BGP-Based H-VPLS Using Different Mesh Groups for Each Spoke Router

IN THIS SECTION

- [Requirements | 806](#)
- [Overview and Topology | 807](#)
- [Configuration | 809](#)

This example shows how to configure the hierarchical virtual private LAN service (H-VPLS) using different mesh groups to provide H-VPLS functionality and provides steps for verifying the configuration. This is one type of H-VPLS configuration possible in the Juniper Networks implementation. For information about the alternate type of configuration see ["Example: Configuring LDP-Based H-VPLS Using a Single Mesh Group to Terminate the Layer 2 Circuits" on page 834.](#)

Using mesh groups improves LDP-based VPLS control plane scalability and avoids the requirement for a full mesh of LDP sessions. This example uses BGP-based VPLS.

This example is organized into the following sections:

Requirements


This example uses the following hardware components:

- Four MX Series 5G Universal Routing Platforms for Router PE1, Router PE2, Router PE3, and Router PE4
- One M Series Multiservice Edge Router for Router CE4
- Two EX Series Ethernet Switches for Device CE1 and Device CE2
- One J Series Services Router for Router CE3

Overview and Topology

Figure 57 on page 807 shows the physical topology used in this example.

Figure 57: Physical Topology of H-VPLS




The following describes the base configuration used in this example:

- Router PE1 and Router PE2 are configured as MTU devices.
- Router PE3 and Router PE4 are configured as PE-r routers, each using an LDP-based VPLS routing instance.
- The LDP and OSPF protocols are configured on all of the MTU devices and PE-r routers.
- Core-facing interfaces are enabled with the MPLS address family.
- Optionally, the VPLS routing instances can be configured on PE-r routers with the `no-tunnel-interface` statement. This allows the routers to use a label-switched interface (LSI), which is useful if your routers do not have Tunnel Services PICs or built-in support for tunnel services.
- All of the routers are configured with loopback IP addresses.

- BGP is configured on the PE-r routers. Optionally, you can configure route reflection. This is useful for scaling internal BGP (IBGP). The BGP configuration includes the signaling statement at the [edit protocols bgp group *group-name* family l2vpn] hierarchy level to support Layer 2 VPN signaling using BGP.

Figure 58 on page 808 shows the logical topology used in this example.

Figure 58: Logical Topology of H-VPLS



In Figure 58 on page 808:

- The MTU devices (Router PE1 and Router PE2) have Layer 2 circuit connections to the PE-r routers (Router PE3 and Router PE4). For redundancy, a backup neighbor is configured for the Layer 2 circuit connections to the PE-r routers.
- The l2circuit statement in the [edit protocols] hierarchy is included on the MTU devices.
- A VPLS routing instance is configured on the PE-r routers.
- In the VPLS routing instance on the PE-r routers, mesh groups are created to terminate the Layer 2 circuit pseudowires that originate at the MTU devices.
- Each MTU device is configured with a different virtual circuit ID.
- Each PE-r router's mesh groups configuration includes VPLS ID values that match the virtual circuit IDs used on the MTU devices.

Configuration

IN THIS SECTION

- [Configuring the Spoke MTU PE Routers | 809](#)
- [Configuring the Hub PE \(PE-r\) | 811](#)
- [Verifying the H-VPLS Operation | 814](#)

To configure H-VPLS with different mesh groups for each spoke PE-r router using BGP-based VPLS, perform the following tasks:

Configuring the Spoke MTU PE Routers

Step-by-Step Procedure

1. On Router PE1, configure the Gigabit Ethernet interface connected to Router CE1. Include the encapsulation statement and specify the `ethernet-ccc` option. Also configure the logical interface by including the `family` statement and specifying the `ccc` option.

```
[edit interfaces]
ge-2/0/5 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}
```

2. On Router PE1, configure the Layer 2 circuit by including the `neighbor` statement and specifying the IP address of Router PE3 as the neighbor. Configure the Gigabit Ethernet logical interface by including the `virtual-circuit-id` statement and specifying 100 as the ID. Also configure a backup neighbor for the Layer 2 circuit by including the `backup-neighbor` statement, specifying the loopback interface IP address of Router PE4 as the backup neighbor, and including the `standby` statement.

```
[edit protocols]
l2circuit {
    neighbor 192.0.2.3 {
        interface ge-2/0/5.0 {
```

```

        virtual-circuit-id 100;
        backup-neighbor 192.0.2.4 {           # Backup H-VPLS PE router
            standby;
        }
    }
}

```

3. On Router PE2, configure the Gigabit Ethernet interface connected to Router CE2. Include the encapsulation statement and specify the `ethernet-ccc` option. Also configure the logical interface by including the `family` statement and specifying the `ccc` option.

```

[edit interfaces]
ge-2/0/6 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}

```

4. On Router PE2, configure the Layer 2 circuit by including the `neighbor` statement and specifying the IP address of Router PE3 as the neighbor. Configure the Gigabit Ethernet logical interface by including the `virtual-circuit-id` statement and specifying 200 as the ID. Configure the encapsulation by including the `encapsulation-type` statement and specifying the `ethernet` option. Also configure a backup neighbor for the Layer 2 circuit by including the `backup-neighbor` statement, specifying the loopback interface IP address of Router PE4 as the backup neighbor, and including the `standby` statement.

```

[edit protocols]
l2circuit {
    neighbor 192.0.2.3 {
        interface ge-1/0/2.0 {
            virtual-circuit-id 200;           # different VC-ID
            encapsulation-type ethernet;      # default encapsulation
            backup-neighbor 192.0.2.4 {
                standby;
            }
        }
    }
}

```

Configuring the Hub PE (PE-r)

Step-by-Step Procedure

1. On Router PE3 (the primary hub), configure the Gigabit Ethernet interface connected to Router CE3. Include the `encapsulation ethernet-vpls` option. Also configure the logical interface by including the `family vpls` statement.

```
[edit interfaces]
ge-2/0/0 {
    encapsulation ethernet-vpls;
    unit 0 {
        family vpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}
```

2. On Router PE4 (the backup hub), configure the Gigabit Ethernet interface connected to Router CE4. Include the `encapsulation ethernet-vpls` option. Also configure the logical interface by including the `family vpls` statement.

```
[edit interfaces]
ge-2/1/7 {
    encapsulation ethernet-vpls;
    unit 0 {
        description to_CE4;
        family vpls;
    }
}
```

```
lo0 {
    unit 0 {
        family inet {
```

```

        address 192.0.2.4/24;
    }
}
}

```

3. On PE-r Router PE3, configure the BGP-based VPLS routing instance by including the `instance-type` statement at the `[edit routing-instances H-VPLS]` hierarchy level and specifying the `vpls` option. Include the `interface` statement and specify the Gigabit Ethernet interface connected to Router CE3. Configure a route distinguisher to ensure that the route advertisement is unique by including the `route-distinguisher` statement and specifying `192.0.2.3:33` as the value. Also configure the VPN routing and forwarding (VRF) route target to be included in the route advertisements to the other routers participating in the VPLS. To configure the VRF route target, include the `vrf-target` statement and specify `target:64510:2` as the value. Optionally, include the `no-tunnel-services` statement to enable the use of LSI interfaces, which is useful if the device does not have tunnel services. The `no-tunnel-services` statement is omitted in this example. Optionally, you can include the `site-range` statement to specify an upper limit on the maximum site identifier that can be accepted to allow a pseudowire to be brought up. The `site-range` statement is omitted in this example. We recommend using the default of `65,534`.

Configure the VPLS protocol and the mesh groups for each MTU PE device.

To configure the VPLS protocol, include the `vpls` statement at the `[edit routing-instances H-VPLS protocols]` hierarchy level. Include the `site` statement and specify a name for the site. Include the `interface` statement and specify the Gigabit Ethernet interface connected to Device CE3.

Configuring mesh groups under the VPLS instance terminates the Layer 2 circuit into the VPLS instance. To configure each mesh group, include the `mesh-group` statement and specify the mesh group name. In this example, the mesh group name is the name of the MTU device associated with each mesh group. Include the `vpls-id` statement and specify the ID that matches the virtual circuit ID configured in ["Configuring the Spoke MTU PE Routers" on page 809](#). Also include the `neighbor` statement and specify the IP address of the spoke PE router associated with each mesh group. Optionally, include the `local-switching` statement if you are not using a full mesh of VPLS connections. The `local-switching` statement is useful if you are configuring a single mesh group and terminating multiple Layer 2 circuit pseudowires into it. The `local-switching` statement is omitted in this example.

```

routing-instances {
  H-VPLS {
    instance-type vpls;
    interface ge-2/1/3.0;
    route-distinguisher 192.0.2.3:33;
    vrf-target target:64510:2;
    protocols {
      vpls {

```

```

        site pe3 {
            site-identifier 3;
            interface ge-2/1/3.0;
        }
        mesh-group pe1 {
            vpls-id 100;
            neighbor 192.0.2.1;
        }
        mesh-group pe2 {
            vpls-id 200;
            neighbor 192.0.2.2;
        }
    }
}
}
}

```

4. On PE-r Router PE4, configure a routing instance like the one on Router PE3.

```

routing-instances {
    H-VPLS {
        instance-type vpls;
        interface ge-2/1/7.0;
        route-distinguisher 192.0.2.4:44;
        vrf-target target:64510:2;
        protocols {
            vpls {
                site pe4 {
                    site-identifier 4;
                    interface ge-2/1/7.0;
                }
                mesh-group pe1 {
                    vpls-id 100;
                    neighbor 192.0.2.1;
                }
                mesh-group pe2 {
                    vpls-id 200;
                    neighbor 192.0.2.2;
                }
            }
        }
    }
}

```



```

    }
}

```

Verifying the H-VPLS Operation

Step-by-Step Procedure

This section describes the operational commands that you can use to validate that the H-VPLS is working as expected.

1. On Router PE1 and Router PE2, use the `show l2circuit connections` command to verify that the Layer 2 circuit to Router PE3 is Up and the Layer 2 circuit to Router PE4 is in standby mode.

The output also shows the assigned label, virtual circuit ID, and the ETHERNET encapsulation type.

```

user@PE1> show l2circuit connections
Layer-2 Circuit Connections:

Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch    VC-Dn -- Virtual circuit Down
CM -- control-word mismatch     Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad SP -- Static Pseudowire
LD -- local site signaled down  RS -- remote site standby
RD -- remote site signaled down XX -- unknown

Legend for interface status
Up -- operational
Dn -- down

Neighbor: 192.0.2.3
  Interface          Type  St    Time last up      # Up trans
  ge-2/0/5.0(vc 100)  rmt   Up    Oct 18 15:55:07 2012      1
    Remote PE: 192.0.2.3, Negotiated control-word: No
    Incoming label: 299840, Outgoing label: 800001
    Negotiated PW status TLV: No
    Local interface: ge-2/0/5.0, Status: Up, Encapsulation: ETHERNET
Neighbor: 192.0.2.4

```

Interface	Type	St	Time last up	# Up trans
ge-2/0/5.0(vc 100)	rmt	ST		

```
user@PE2> show l2circuit connections
```

Layer-2 Circuit Connections:

Legend for connection status (St)

EI -- encapsulation invalid	NP -- interface h/w not present
MM -- mtu mismatch	Dn -- down
EM -- encapsulation mismatch	VC-Dn -- Virtual circuit Down
CM -- control-word mismatch	Up -- operational
VM -- vlan id mismatch	CF -- Call admission control failure
OL -- no outgoing label	IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC	TM -- TDM misconfiguration
BK -- Backup Connection	ST -- Standby Connection
CB -- rcvd cell-bundle size bad	SP -- Static Pseudowire
LD -- local site signaled down	RS -- remote site standby
RD -- remote site signaled down	XX -- unknown

Legend for interface status

Up -- operational

Dn -- down

Neighbor: 192.0.2.3

Interface	Type	St	Time last up	# Up trans
ge-2/0/6.0(vc 200)	rmt	Up	Oct 18 15:55:07 2012	1

Remote PE: 192.0.2.3, Negotiated control-word: No

Incoming label: 299872, Outgoing label: 800002

Negotiated PW status TLV: No

Local interface: ge-2/0/6.0, Status: Up, Encapsulation: **ETHERNET**

Neighbor: 192.0.2.4

Interface	Type	St	Time last up	# Up trans
ge-2/0/6.0(vc 200)	rmt	ST		

- On Router PE1 and Router PE2, use the `show ldp neighbor` command to verify that the targeted LDP sessions have been created between the loopback interface to the primary and backup H-VPLS hub neighbors.

```
user@PE1> show ldp neighbor
```

Address	Interface	Label space ID	Hold time
10.10.3.2	ge-2/0/9.0	192.0.2.2:0	13

10.10.1.2	ge-2/0/10.0	192.0.2.3:0	10
192.0.2.3	lo0.0	192.0.2.3:0	36
192.0.2.4	lo0.0	192.0.2.4:0	39
10.10.9.2	ge-2/0/8.0	192.0.2.4:0	14

```
user@PE2> show ldp neighbor
```

Address	Interface	Label space ID	Hold time
10.10.3.1	ge-2/0/10.0	192.0.2.1:0	12
10.10.5.2	ge-2/0/9.0	192.0.2.4:0	11
10.10.4.1	ge-2/0/8.0	192.0.2.3:0	11
192.0.2.3	lo0.0	192.0.2.3:0	39
192.0.2.4	lo0.0	192.0.2.4:0	38

- On Router PE3 and Router PE4, use the `show vpls connections` command to verify that the VPLS connection status is Up for both the LDP-based VPLS and the BGP-based VPLS Layer 2 circuits that are terminated.

```
user@PE3> show vpls connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

Legend for interface status

Up -- operational

Dn -- down

Instance: H-VPLS

BGP-VPLS State

Local site: pe3 (3)

connection-site	Type	St	Time last up	# Up trans
4	rmt	Up	Oct 18 15:58:39 2012	1

Remote PE: 192.0.2.4, Negotiated control-word: No

Incoming label: 800267, Outgoing label: 800266

Local interface: vt-2/0/9.135266562, Status: Up, Encapsulation: VPLS

Description: Intf - vpls H-VPLS local site 3 remote site 4

LDP-VPLS State

Mesh-group connections: pe1

Neighbor	Type	St	Time last up	# Up trans
192.0.2.1(vpls-id 100)	rmt	Up	Oct 18 15:55:07 2012	1

Remote PE: 192.0.2.1, Negotiated control-word: No

Incoming label: 800001, Outgoing label: 299840

Negotiated PW status TLV: No

Local interface: vt-2/0/10.135266560, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls H-VPLS neighbor 192.0.2.1 vpls-id 100

Mesh-group connections: pe2

Neighbor	Type	St	Time last up	# Up trans
192.0.2.2(vpls-id 200)	rmt	Up	Oct 18 15:55:07 2012	1

Remote PE: 192.0.2.2, Negotiated control-word: No

Incoming label: 800002, Outgoing label: 299872

Negotiated PW status TLV: No

Local interface: vt-2/0/8.135266561, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls H-VPLS neighbor 192.0.2.2 vpls-id 200

user@PE4> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down

LD -- local site signaled down CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch MI -- Mesh-Group ID not available
BK -- Backup connection ST -- Standby connection
PF -- Profile parse failure PB -- Profile busy
RS -- remote site standby SN -- Static Neighbor
LB -- Local site not best-site RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status

Up -- operational

Dn -- down

Instance: H-VPLS

BGP-VPLS State

Local site: pe4 (4)

connection-site	Type	St	Time last up	# Up trans
3	rmt	Up	Oct 18 15:58:39 2012	1

Remote PE: 192.0.2.3, Negotiated control-word: No

Incoming label: 800266, Outgoing label: 800267

Local interface: vt-2/0/8.17826050, Status: Up, Encapsulation: VPLS

Description: Intf - vpls H-VPLS local site 4 remote site 3

LDP-VPLS State

Mesh-group connections: pe1

Neighbor	Type	St	Time last up	# Up trans
192.0.2.1(vpls-id 100)	rmt	Up	Oct 18 15:58:39 2012	1

Remote PE: 192.0.2.1, Negotiated control-word: No

Incoming label: 800002, Outgoing label: 299856

Negotiated PW status TLV: No

Local interface: vt-2/0/9.17826048, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls H-VPLS neighbor 192.0.2.1 vpls-id 100

Mesh-group connections: pe2

Neighbor	Type	St	Time last up	# Up trans
192.0.2.2(vpls-id 200)	rmt	Up	Oct 18 15:58:39 2012	1

Remote PE: 192.0.2.2, Negotiated control-word: No

Incoming label: 800003, Outgoing label: 299888

Negotiated PW status TLV: No

Local interface: vt-2/0/10.17826049, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls H-VPLS neighbor 192.0.2.2 vpls-id 200

4. On Router PE3 and Router PE4, use the `show vpls flood` command to verify that the H-VPLS PE router created a flood group for each spoke PE site.

```
user@PE3> show vpls flood
Name: H-VPLS
CEs: 1
VEs: 3
Flood Routes:
  Prefix      Type      Owner      NhType      NhIndex
  0x300cc/51  FLOOD_GRP_COMP_NH __ves__     comp        1376
  0x300cf/51  FLOOD_GRP_COMP_NH __all_ces__ comp        744
  0x300d5/51  FLOOD_GRP_COMP_NH pe1         comp        1702
  0x300d3/51  FLOOD_GRP_COMP_NH pe2         comp        1544
  0x30001/51  FLOOD_GRP_COMP_NH __re_flood__ comp        740
```

```
user@PE4> show vpls flood
Name: H-VPLS
CEs: 1
VEs: 3
Flood Routes:
  Prefix      Type      Owner      NhType      NhIndex
  0x300d1/51  FLOOD_GRP_COMP_NH __ves__     comp        1534
  0x300d0/51  FLOOD_GRP_COMP_NH __all_ces__ comp        753
  0x300d6/51  FLOOD_GRP_COMP_NH pe1         comp        1378
  0x300d4/51  FLOOD_GRP_COMP_NH pe2         comp        1695
  0x30002/51  FLOOD_GRP_COMP_NH __re_flood__ comp        750
```

5. On Router PE3 and Router PE4, use the `show vpls mac-table` command to verify that MAC addresses of the CE devices have been learned.

```
user@PE3> show vpls mac-table
MAC flags (S -static MAC, D -dynamic MAC, L -locally learned, C -Control MAC
          SE -Statistics enabled, NM -Non configured MAC, R -Remote PE MAC)

Routing instance : H-VPLS
Bridging domain : __H-VPLS__, VLAN : NA
  MAC      MAC      Logical      NH      RTR
  address   flags   interface   Index   ID
  00:21:59:0f:35:32  D      vt-2/0/8.135266560
  00:21:59:0f:35:33  D      ge-2/1/3.0
```

```
00:21:59:0f:35:d4  D      vt-2/0/9.135266561
00:21:59:0f:35:d5  D      vt-2/0/10.135266562
```

```
user@PE4> show vpls mac-table
```

```
MAC flags (S -static MAC, D -dynamic MAC, L -locally learned, C -Control MAC
          SE -Statistics enabled, NM -Non configured MAC, R -Remote PE MAC)
```

```
Logical system   : PE4
```

```
Routing instance : H-VPLS
```

```
Bridging domain : __H-VPLS__, VLAN : NA
```

MAC address	MAC flags	Logical interface	NH Index	RTR ID
00:21:59:0f:35:32	D	vt-2/0/8.17826050		
00:21:59:0f:35:33	D	vt-2/0/9.17826050		
00:21:59:0f:35:d4	D	vt-2/0/10.17826050		
00:21:59:0f:35:d5	D	ge-2/1/7.0		

6. Make sure that the CE devices can ping each other.

```
user@CE1> ping 10.255.14.219 # ping sent from CE1 CE4
PING 10.255.14.219 (10.255.14.219): 56 data bytes
64 bytes from 10.255.14.219: icmp_seq=0 ttl=64 time=10.617 ms
64 bytes from 10.255.14.219: icmp_seq=1 ttl=64 time=9.224 ms
^C
--- 10.255.14.219 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 9.224/9.921/10.617/0.697 ms
```

```
user@CE2> ping 10.255.14.218 # ping sent from CE2 to CE3

PING 10.255.14.218 (10.255.14.218): 56 data bytes
64 bytes from 10.255.14.218: icmp_seq=0 ttl=64 time=1.151 ms
64 bytes from 10.255.14.218: icmp_seq=1 ttl=64 time=0.674 ms
^C
--- 10.255.14.218 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.674/0.913/1.151/0.238 ms
```

7. Check the relevant routing tables.

```

user@PE1> show route table l2circuit.0
l2circuit.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3:NoCtrlWord:5:100:Local/96
    *[L2CKT/7] 00:12:16, metric2 1
    > to 10.10.1.2 via ge-2/0/10.0
192.0.2.3:NoCtrlWord:5:100:Remote/96
    *[LDP/9] 00:12:16
    Discard
192.0.2.4:NoCtrlWord:5:100:Local/96
    *[L2CKT/7] 00:12:10, metric2 1
    > to 10.10.9.2 via ge-2/0/8.0
192.0.2.4:NoCtrlWord:5:100:Remote/96
    *[LDP/9] 00:12:15
    Discard

```

```

user@PE2> show route table l2circuit.0
l2circuit.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3:NoCtrlWord:5:200:Local/96
    *[L2CKT/7] 00:13:13, metric2 1
    > to 10.10.4.1 via ge-2/0/8.0
192.0.2.3:NoCtrlWord:5:200:Remote/96
    *[LDP/9] 00:13:13
    Discard
192.0.2.4:NoCtrlWord:5:200:Local/96
    *[L2CKT/7] 00:13:13, metric2 1
    > to 10.10.5.2 via ge-2/0/9.0
192.0.2.4:NoCtrlWord:5:200:Remote/96
    *[LDP/9] 00:13:13
    Discard
user@PE3> show route table H-VPLS.12vpn.0

H-VPLS.12vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3:33:3:1/96

```



```

          *[L2VPN/170/-101] 03:19:26, metric2 1
          Indirect
192.0.2.4:44:4:1/96
          *[BGP/170] 03:15:45, localpref 100, from 192.0.2.4
          AS path: I, validation-state: unverified
          > to 10.10.6.2 via ge-2/0/9.0
user@PE4> show route table H-VPLS.l2vpn.0

H-VPLS.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3:33:3:1/96
          *[BGP/170] 03:21:17, localpref 100, from 192.0.2.3
          AS path: I, validation-state: unverified
          > to 10.10.6.1 via ge-2/0/9.0
192.0.2.4:44:4:1/96
          *[L2VPN/170/-101] 03:17:47, metric2 1
          Indirect

```

Results

The configuration and verification parts of this example have been completed. The following section is for your reference.

The relevant sample configuration for Router PE1 follows.

Router PE1

```

interfaces {
  ge-2/0/5 {
    encapsulation ethernet-ccc;
    unit 0 {
      description to_CE1;
      family ccc;
    }
  }
  ge-2/0/8 {
    unit 0 {
      description to_PE4;
      family inet {
        address 10.10.9.1/30;
      }
    }
  }
}

```

```

        family mpls;
    }
}
ge-2/0/9 {
    unit 0 {
        description to_PE2;
        family inet {
            address 10.10.3.1/30;
        }
        family mpls;
    }
}
ge-2/0/10 {
    unit 0 {
        description to_PE3;
        family inet {
            address 10.10.1.1/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}
}
protocols {
    mpls {
        interface ge-2/0/8.0;
        interface ge-2/0/9.0;
        interface ge-2/0/10.0;
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface lo0.0 {
                passive;
            }
            interface ge-2/0/8.0;
            interface ge-2/0/9.0;

```

```

        interface ge-2/0/10.0;
    }
}
ldp {
    interface ge-2/0/8.0;
    interface ge-2/0/9.0;
    interface ge-2/0/10.0;
    interface lo0.0;
}
l2circuit {
    neighbor 192.0.2.3 {
        interface ge-2/0/5.0 {
            virtual-circuit-id 100;
            backup-neighbor 192.0.2.4 {
                standby;
            }
        }
    }
}
}
}
}

```

The relevant sample configuration for Router PE2 follows.

Router PE2

```

interfaces {
    ge-2/0/6 {
        encapsulation ethernet-ccc;
        unit 0 {
            description to_CE2;
            family ccc;
        }
    }
    ge-2/0/8 {
        unit 0 {
            description to_PE3;
            family inet {
                address 10.10.4.2/30;
            }
            family mpls;
        }
    }
}

```

```

ge-2/0/9 {
    unit 0 {
        description to_PE4;
        family inet {
            address 10.10.5.1/30;
        }
        family mpls;
    }
}
ge-2/0/10 {
    unit 0 {
        description to_PE1;
        family inet {
            address 10.10.3.2/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}
}
protocols {
    mpls {
        interface ge-2/0/8.0;
        interface ge-2/0/9.0;
        interface ge-2/0/10.0;
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface lo0.0 {
                passive;
            }
            interface ge-2/0/8.0;
            interface ge-2/0/9.0;
            interface ge-2/0/10.0;
        }
    }
}

```

```

ldp {
    interface ge-2/0/8.0;
    interface ge-2/0/9.0;
    interface ge-2/0/10.0;
    interface lo0.0;
}
l2circuit {
    neighbor 192.0.2.3 {
        interface ge-2/0/6.0 {
            virtual-circuit-id 200;
            backup-neighbor 192.0.2.4 {
                standby;
            }
        }
    }
}
}

```

The relevant sample configuration for Router PE3 follows.

Router PE3

```

interfaces {
    ge-2/0/8 {
        unit 0 {
            description to_PE2;
            family inet {
                address 10.10.4.1/30;
            }
            family mpls;
        }
    }
    ge-2/0/9 {
        unit 0 {
            description to_PE4;
            family inet {
                address 10.10.6.1/30;
            }
            family mpls;
        }
    }
    ge-2/0/10 {

```

```

    unit 0 {
        description to_PE1;
        family inet {
            address 10.10.1.2/30;
        }
        family mpls;
    }
}
ge-2/1/3 {
    encapsulation ethernet-vpls;
    unit 0 {
        description to_CE3;
        family vpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}
}
protocols {
    mpls {
        interface ge-2/0/8.0;
        interface ge-2/0/9.0;
        interface ge-2/0/10.0;
    }
    bgp {
        group internal-peers {
            type internal;
            local-address 192.0.2.3;
            family l2vpn {
                signaling;
            }
            neighbor 192.0.2.4;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface lo0.0 {

```

```

        passive;
    }
    interface ge-2/0/8.0;
    interface ge-2/0/9.0;
    interface ge-2/0/10.0;
}
}
ldp {
    interface ge-2/0/8.0;
    interface ge-2/0/9.0;
    interface ge-2/0/10.0;
    interface lo0.0;
}
}
routing-instances {
    H-VPLS {
        instance-type vpls;
        interface ge-2/1/3.0;
        route-distinguisher 192.0.2.3:33;
        vrf-target target:64510:2;
        protocols {
            vpls {
                site pe3 {
                    site-identifier 3;
                    interface ge-2/1/3.0;
                }
                mesh-group pe1 {
                    vpls-id 100;
                    neighbor 192.0.2.1;
                }
                mesh-group pe2 {
                    vpls-id 200;
                    neighbor 192.0.2.2;
                }
            }
        }
    }
}
}
routing-options {
    autonomous-system 64510;
}

```

The relevant sample configuration for Router PE4 follows.

Router PE4

```
interfaces {
  ge-2/0/8 {
    unit 0 {
      description to_PE3;
      family inet {
        address 10.10.6.2/30;
      }
      family mpls;
    }
  }
  ge-2/0/9 {
    unit 0 {
      description to_PE1;
      family inet {
        address 10.10.9.2/30;
      }
      family mpls;
    }
  }
  ge-2/0/10 {
    unit 0 {
      description to_PE2;
      family inet {
        address 10.10.5.2/30;
      }
      family mpls;
    }
  }
  ge-2/1/7 {
    encapsulation ethernet-vpls;
    unit 0 {
      description to_CE4;
      family vpls;
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 192.0.2.4/24;
      }
    }
  }
}
```



```

    }
  }
}
protocols {
  mpls {
    interface ge-2/0/8.0;
    interface ge-2/0/9.0;
    interface ge-2/0/10.0;
  }
  bgp {
    group internal-peers {
      type internal;
      local-address 192.0.2.4;
      family l2vpn {
        signaling;
      }
      neighbor 192.0.2.3;
    }
  }
  ospf {
    traffic-engineering;
    area 0.0.0.0 {
      interface lo0.0 {
        passive;
      }
      interface ge-2/0/8.0;
      interface ge-2/0/9.0;
      interface ge-2/0/10.0;
    }
  }
  ldp {
    interface ge-2/0/8.0;
    interface ge-2/0/9.0;
    interface ge-2/0/10.0;
    interface lo0.0;
  }
}
routing-instances {
  H-VPLS {
    instance-type vpls;
    interface ge-2/1/7.0;
    route-distinguisher 192.0.2.4:44;
    vrf-target target:64510:2;
  }
}

```

```

    protocols {
        vpls {
            site pe4 {
                site-identifier 4;
                interface ge-2/1/7.0;
            }
            mesh-group pe1 {
                vpls-id 100;
                neighbor 192.0.2.1;
            }
            mesh-group pe2 {
                vpls-id 200;
                neighbor 192.0.2.2;
            }
        }
    }
}
routing-options {
    autonomous-system 64510;
}

```

The relevant sample configuration for Device CE1 follows.

Router CE1

```

interfaces {
    ge-2/0/8 {
        unit 0 {
            description to_PE1;
            family inet {
                address 172.16.0.1/24;
            }
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 10.255.14.214/32;
            }
        }
    }
}

```

```

}
protocols {
  ospf {
    area 0.0.0.0 {
      interface lo0.0 {
        passive;
      }
      interface ge-2/0/8.0;
    }
  }
}

```

The relevant sample configuration for Device CE2 follows.

Router CE2

```

interfaces {
  ge-2/1/5 {
    unit 0 {
      description to_PE2;
      family inet {
        address 172.16.0.2/24;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.255.14.215/32;
      }
    }
  }
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface lo0.0 {
        passive;
      }
      interface ge-2/1/5.0;
    }
  }
}

```

```

    }
}

```

The relevant sample configuration for Device CE3 follows.

Router CE3

```

interfaces {
    ge-2/0/9 {
        unit 0 {
            description to_PE3;
            family inet {
                address 172.16.0.3/24;
            }
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 10.255.14.218/32;
            }
        }
    }
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface lo0.0 {
                passive;
            }
            interface ge-2/0/9.0;
        }
    }
}

```

The relevant sample configuration for Device CE4 follows.

Router CE4

```

interfaces {
    ge-2/1/6 {
        unit 0 {

```

```

        description to_PE4;
        family inet {
            address 172.16.0.4/24;
        }
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.255.14.219/32;
        }
    }
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface lo0.0 {
                passive;
            }
            interface ge-2/1/6.0;
        }
    }
}
}

```

RELATED DOCUMENTATION

[Example: Configuring LDP-Based H-VPLS Using a Single Mesh Group to Terminate the Layer 2 Circuits](#) | 834

Example: Configuring LDP-Based H-VPLS Using a Single Mesh Group to Terminate the Layer 2 Circuits

IN THIS SECTION

● [Requirements](#) | 835

- Overview and Topology | 836
- Configuration | 837

This example shows how to configure a single mesh group to terminate the Layer 2 circuits into an LDP-based VPLS. This is one type of hierarchical virtual private LAN service (H-VPLS) configuration possible in the Juniper Networks implementation. For information about the alternate type of configuration see ["Example: Configuring BGP-Based H-VPLS Using Different Mesh Groups for Each Spoke Router" on page 805](#).

This example provides step-by-step configuration instructions and also provides steps for verifying and troubleshooting the configuration.

This example is organized into the following sections:

Requirements


This example uses the following hardware components:

- Four MX Series 5G Universal Routing Platforms for Routers PE1, PE2, PE3, and PE4
- Two M Series Multiservice Edge Routers for Routers CE4 and PE5
- Two EX Series Ethernet Switches for Devices CE1 and CE2
- Two T Series Core Routers for Routers P1 and the route reflector

Overview and Topology

Figure 59 on page 836 shows the physical topology used in this example.

Figure 59: Physical Topology of H-VPLS using a Single Mesh Group



In Figure 59 on page 836:

- Local switching is used to switch traffic between Layer 2 circuit pseudowires from the different spoke PE routers.
- The spoke PE routers are configured with the same virtual circuit ID and VPLS ID pair in a mesh group.
- The spoke PE routers are configured in an LDP-signaled VPLS routing instance.
- The layer 2 circuits are terminated into the LDP-based VPLS.

Configuration

IN THIS SECTION

- [Configuring the Spoke PE Routers | 837](#)
- [Configuring the Hub PE Router | 839](#)
- [Verification | 841](#)

To configure a single mesh group to terminate the Layer 2 circuits into an LDP-based VPLS, perform the following tasks:

Configuring the Spoke PE Routers

Step-by-Step Procedure

Configure a single mesh group to terminate all the Layer 2 circuit pseudowires and enable local switching between the pseudowires.

1. On Router PE1, configure the Layer 2 circuit by including the `l2circuit` statement at the `[edit protocols]` hierarchy level. Include the `neighbor` statement and specify the IPv4 address of the hub PE router. Also configure the logical interface by including the `interface` statement and specify the interface connected to Router CE1.

Configure the virtual circuit ID by including the `virtual-circuit-id` statement and specifying 100 as the ID value at the `[edit protocols l2circuit neighbor 192.0.2.5 interface ge-1/0/0.0]` hierarchy level.

Configure the backup neighbor by including the `backup-neighbor` statement and specifying the IPv4 address of the backup hub PE router. Router PE3 is the backup neighbor in this example. Also include the `standby` statement at the `[edit protocols l2circuit neighbor 192.0.2.5 interface ge-1/0/0.0 backup-neighbor 192.0.2.3]` hierarchy level.

```
[edit protocols]
l2circuit {
  neighbor 192.0.2.5 {
    interface ge-1/0/0.0 {
      virtual-circuit-id 100;
      backup-neighbor 192.0.2.3 {
        standby;
      }
    }
  }
}
```



```

    }
  }
}

```

2. On Router PE2, configure the Layer 2 circuit by including the `l2circuit` statement at the `[edit protocols]` hierarchy level. Include the `neighbor` statement and specify the IPv4 address of the hub PE router. Configure the logical interface by including the `interface` statement and specifying the interface connected to Router CE2.

Configure the virtual circuit ID by including the `virtual-circuit-id` statement and specifying 100 as the ID value at the `[edit protocols l2circuit neighbor 192.0.2.5 interface ge-1/0/2.0]` hierarchy level. Include the `encapsulation` statement and specify `ethernet` as the `type`.

Configure the backup neighbor by including the `backup-neighbor` statement and specifying the IPv4 address of the backup hub PE router. Router PE3 is the backup neighbor in this example. Also include the `standby` statement at the `[edit protocols l2circuit neighbor 192.0.2.5 interface ge-1/0/0.0 backup-neighbor 192.0.2.3]` hierarchy level.

```

[edit protocols]
l2circuit {
  neighbor 192.0.2.5 {
    interface ge-1/0/2.0 {
      virtual-circuit-id 100;
      encapsulation-type ethernet;
      backup-neighbor 192.0.2.3 {
        standby;
      }
    }
  }
}

```

3. On Router PE4, configure the Layer 2 circuit by including the `l2circuit` statement at the `[edit protocols]` hierarchy level. Include the `neighbor` statement and specify the IPv4 address of the hub PE router. Configure the logical interface by including the `interface` statement and specify the interface connected to Router CE4.

Configure the virtual circuit ID by including the `virtual-circuit-id` statement and specifying 100 as the ID value at the `[edit protocols l2circuit neighbor 192.0.2.5 interface ge-1/2/0.0]` hierarchy level.

Configure the backup neighbor by including the `backup-neighbor` statement and specifying the IPv4 address of the backup hub PE router. Router PE3 is the backup neighbor in this example. Also include

the standby statement at the [edit protocols l2circuit neighbor 192.0.2.5 interface ge-1/2/0.0 backup-neighbor 192.0.2.3] hierarchy level.

```
[edit protocols]
l2circuit {
  neighbor 192.0.2.5 {
    interface ge-1/2/0.0 {
      virtual-circuit-id 100;
      backup-neighbor 192.0.2.3 {
        standby;
      }
    }
  }
}
```

Configuring the Hub PE Router

Step-by-Step Procedure

Configure a single mesh group to terminate all the Layer 2 circuit pseudowires and enable local switching between the pseudowires.

1. On Router PE3, configure the Gigabit Ethernet interface connected to Router CE3 by including the encapsulation statement and specifying the ethernet-vpls option. Also configure the logical interface by including the family statement and specifying the vpls option.

```
[edit interfaces]
ge-1/0/1 {
  encapsulation ethernet-vpls;
  unit 0 {
    family vpls;
  }
}
```

2. On Router PE3, configure the logical loopback interface by including the family statement and specifying the inet option. Include the address statement and specify the IPv4 address for the interface.

```
[edit interfaces]
lo0 {
```

```

    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}

```

3. On Router PE3, configure the LDP-based VPLS routing instance by including the `instance-type` statement at the `[edit routing-instances H-VPLS]` hierarchy level and specifying the `vpls` option. Include the interface statement and specify the Gigabit Ethernet interface connected to Router CE3.

Configure the VPLS protocol by including the `vpls` statement at the `[edit routing-instances H-VPLS protocols]` hierarchy level. Include the `no-tunnel-services` statement to enable the router to use an LSI interface.

```

[edit routing-instances]
H-VPLS {
    instance-type vpls;
    interface ge-1/0/1.0;
    protocols {
        vpls {
            no-tunnel-services;
        }
    }
}

```

4. On Router PE3, configure the mesh group by including the `mesh-group` statement at the `[edit routing-instances H-VPLS protocols vpls]` hierarchy level and specifying `L2-Circuits` as the name of the group. Include the `vpls-id` statement and specify `100` as the ID value. Include the `local-switching` statement to enable the router to switch traffic between the pseudowires.

For each neighbor in the mesh group, include the `neighbor` statement and specify the IPv4 address of the spoke PE router.

```

[edit routing-instances H-VPLS protocols vpls]
mesh-group L2-Circuits {
    vpls-id 100;    <<< Same VPLS ID on all MTUs
    local-switching; << Local-switching enabled
    neighbor 192.0.2.1; <<MTU IP addresses
    neighbor 192.0.2.2;
}

```

```
neighbor 192.0.2.4;
}
```

Verification

Step-by-Step Procedure

1. On Router PE5, use the `show ldp neighbor` command to verify that LDP sessions have been created to each of the spoke PE routers.

```
user@PE5# show ldp neighbor
```

Address	Interface	Label space ID	Hold time
192.0.2.1	lo0.0	192.0.2.1:0	33
192.0.2.2	lo0.0	192.0.2.2:0	37
192.0.2.4	lo0.0	192.0.2.4:0	39

2. On Router PE5, use the `show vpls connections extensive` command to verify that the mesh group neighbor session is Up, that inbound and outbound labels have been assigned, that the VPLS ID is correct, and that the virtual tunnel interface is being used.

```
user@PE5# show vpls connections extensive
...
Instance: H-VPLS
  Number of local interfaces: 1
  Number of local interfaces up: 1
  Number of VE mesh-groups: 2
  Number of VE mesh-groups up: 1
  ge-2/0/0.0
  Mesh-group interfaces: L2-Circuits
    State: Up      ID: 2
    vt-2/1/0.1048848  Intf - vpls H-VPLS neighbor 192.0.2.4 vpls-id 100
    vt-2/1/0.1048849  Intf - vpls H-VPLS neighbor 192.0.2.2 vpls-id 100
    vt-2/1/0.1048850  Intf - vpls H-VPLS neighbor 192.0.2.1 vpls-id 100
  Mesh-group interfaces: __ves__
    State: Dn      ID: 0
  Mesh-group connections: L2-Circuits
    Neighbor          Type  St   Time last up          # Up trans
    192.0.2.4(vpls-id 100)  rmt  Up   Jan 3 16:46:26 2010      1
    Remote PE: 192.0.2.4, Negotiated control-word: No
    Incoming label: 800011, Outgoing label: 301088
```

```

Local interface: vt-2/1/0.1048848, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls H-VPLS neighbor 192.0.2.4 vpls-id 100
Connection History:
  Jan  3 16:46:26 2010  status update timer
  Jan  3 16:46:26 2010  PE route changed
  Jan  3 16:46:26 2010  In lbl Update                      800011
  Jan  3 16:46:26 2010  Out lbl Update                     301088
  Jan  3 16:46:26 2010  In lbl Update                      800011
  Jan  3 16:46:26 2010  loc intf up                        vt-2/1/0.1048848
192.0.2.2(vpls-id 100)    rmt  Up    Jan  3 16:46:26 2010          1
Remote PE: 192.0.2.2, Negotiated control-word: No
Incoming label: 800010, Outgoing label: 301488
Local interface: vt-2/1/0.1048849, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls H-VPLS neighbor 192.0.2.2 vpls-id 100
Connection History:
  Jan  3 16:46:26 2010  status update timer
  Jan  3 16:46:26 2010  PE route changed
  Jan  3 16:46:26 2010  In lbl Update                      800010
  Jan  3 16:46:26 2010  Out lbl Update                     301488
  Jan  3 16:46:26 2010  In lbl Update                      800010
  Jan  3 16:46:26 2010  loc intf up                        vt-2/1/0.1048849
192.0.2.1(vpls-id 100)    rmt  Up    Jan  3 16:46:26 2010          1
Remote PE: 192.0.2.1, Negotiated control-word: No
Incoming label: 800009, Outgoing label: 301296
Local interface: vt-2/1/0.1048850, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls H-VPLS neighbor 192.0.2.1 vpls-id 100
Connection History:
  Jan  3 16:46:26 2010  status update timer
  Jan  3 16:46:26 2010  PE route changed
  Jan  3 16:46:26 2010  In lbl Update                      800009
  Jan  3 16:46:26 2010  Out lbl Update                     301296
  Jan  3 16:46:26 2010  In lbl Update                      800009
  Jan  3 16:46:26 2010  loc intf up                        vt-2/1/0.1048850

```

RELATED DOCUMENTATION

[Example: Configuring BGP-Based H-VPLS Using Different Mesh Groups for Each Spoke Router](#) | 805

Example: Configuring H-VPLS With VLANs

IN THIS SECTION

- Requirements | 843
- Overview | 843
- Configuration | 845
- Verification | 856

This example shows how to configure the hierarchical virtual private LAN service (H-VPLS). VLANs are configured in this example.

Requirements

No special configuration beyond device initialization is required before configuring this example.

Overview

H-VPLS uses LDP-based VPLS to signal and establish pseudowires. LDP-based VPLS is defined in RFC 4762, *Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling*. RFC 4762 also defines a hierarchical mode of operation for LDP VPLS called H-VPLS.

VPLS and H-VPLS are different with respect to scaling. VPLS requires a full mesh of tunnel label-switched paths (LSPs) among all of the provider edge (PE) routers that participate in the VPLS service. For each VPLS service, $n*(n-1)/2$ pseudowires must be set up between the PE routers. In contrast, H-VPLS partitions the network into several edge domains that are interconnected using an MPLS core. Each edge device only needs to learn of one local PE device and therefore needs less routing table support. This has the potential to allow service providers to use relatively less costly devices (such as EX Series switches) at the customer edge.

NOTE: As alternatives to H-VPLS, Juniper Networks offers other ways to address VPLS scalability. For more information, see [Application Note: Demystifying H-VPLS](#).


H-VPLS defines two roles or functionalities:

- PE-r—PE device that runs VPLS with other PE-r devices, but which also has pseudowires (it can be based on QinQ access) with another device called a multi-tenant unit (MTU), which provides the access layer.

- MTU—PE device that represents the access layer on the H-VPLS architecture and establishes pseudowires to one or more PE-r devices through which VPLS traffic is forwarded.

Figure 60 on page 844 shows the topology used in this example.

Figure 60: Basic H-VPLS With One MTU and Two PE-r Devices



The example shows one MTU (Device PE1) connected to two PE-r devices (Device PE2 and Device PE3).

The pseudowire between Device PE1 and Device PE3 is the primary or working path. The pseudowire between Device PE1 and Device PE2 is the backup path.

To support VLANs with H-VPLS, you must include the `output-vlan-map swap` statement in the configuration of the MTU device as a workaround to prevent a VLAN ID mismatch. Otherwise, the PE-r devices report a VLAN ID mismatch, as shown here:

```
user@PE2> show vpls connections
```

```
Layer-2 VPN connections:
```

```
Legend for connection status (St)
```

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure

```
RD -- remote site signaled down  SC -- local and remote site ID collision
LN -- local site not designated  LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status  IL -- no incoming label
MM -- MTU mismatch               MI -- Mesh-Group ID not available
BK -- Backup connection          ST -- Standby connection
PF -- Profile parse failure       PB -- Profile busy
RS -- remote site standby        SN -- Static Neighbor
LB -- Local site not best-site    RB -- Remote site not best-site
VM -- VLAN ID mismatch
```

Legend for interface status

Up -- operational

Dn -- down

Instance: customer

VPLS-id: 601

Neighbor	Type	St	Time last up	# Up trans
10.255.14.217(vpls-id 601) rmt		VM		

"CLI Quick Configuration" on page 845 shows the configuration for all of the devices in Figure 60 on page 844. The section "Step-by-Step Procedure" on page 848 describes the steps on Device PE1 and Device PE2.

Configuration

IN THIS SECTION

- Procedure | 845

Procedure

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device PE1

```

set interfaces ge-2/0/5 vlan-tagging
set interfaces ge-2/0/5 encapsulation vlan-ccc
set interfaces ge-2/0/5 unit 601 encapsulation vlan-ccc
set interfaces ge-2/0/5 unit 601 vlan-id 601
set interfaces ge-2/0/5 unit 601 output-vlan-map swap
set interfaces ge-2/0/5 unit 601 family ccc
set interfaces ge-2/0/10 unit 0 family inet address 192.0.2.2/24
set interfaces ge-2/0/10 unit 0 family iso
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces ge-2/0/11 unit 0 family inet address 192.0.2.3/24
set interfaces ge-2/0/11 unit 0 family iso
set interfaces ge-2/0/11 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.217/32
set interfaces lo0 unit 0 family iso address 49.0001.0102.5501.4217.00
set protocols mpls interface ge-2/0/10.0
set protocols mpls interface ge-2/0/11.0
set protocols isis level 1 disable
set protocols isis interface ge-2/0/10.0
set protocols isis interface ge-2/0/11.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface ge-2/0/11.0
set protocols ldp interface lo0.0
set protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.601 virtual-circuit-id 601
set protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.601 encapsulation-type
ethernet-vlan
set protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.601 backup-neighbor
10.255.14.216 standby
set routing-options router-id 10.255.14.217

```

Device PE2

```

set interfaces ge-2/0/6 vlan-tagging
set interfaces ge-2/0/6 encapsulation vlan-vpls
set interfaces ge-2/0/6 unit 601 encapsulation vlan-vpls
set interfaces ge-2/0/6 unit 601 vlan-id 601
set interfaces ge-2/0/6 unit 601 family vpls
set interfaces ge-2/0/10 unit 0 family inet address 192.0.2.4/24
set interfaces ge-2/0/10 unit 0 family iso

```

```

set interfaces ge-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.216/32
set interfaces lo0 unit 0 family iso address 49.0001.0102.5501.4216.00
set protocols mpls interface ge-2/0/10.0
set protocols isis level 1 disable
set protocols isis interface ge-2/0/10.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances customer instance-type vpls
set routing-instances customer interface ge-2/0/6.601
set routing-instances customer protocols vpls vpls-id 601
set routing-instances customer protocols vpls neighbor 10.255.14.217 encapsulation-type ethernet-
vlan
set routing-options router-id 10.255.14.216

```

Device PE3

```

set interfaces ge-2/0/10 unit 0 family inet address 192.0.2.5/24
set interfaces ge-2/0/10 unit 0 family iso
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces ge-2/1/3 vlan-tagging
set interfaces ge-2/1/3 encapsulation vlan-vpls
set interfaces ge-2/1/3 unit 601 encapsulation vlan-vpls
set interfaces ge-2/1/3 unit 601 vlan-id 601
set interfaces ge-2/1/3 unit 601 family vpls
set interfaces lo0 unit 0 family inet address 10.255.14.225/32
set interfaces lo0 unit 0 family iso address 49.0001.0102.5501.4225.00
set protocols mpls interface ge-2/0/10.0
set protocols isis level 1 disable
set protocols isis interface ge-2/0/10.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances customer instance-type vpls
set routing-instances customer interface ge-2/1/3.601
set routing-instances customer protocols vpls vpls-id 601
set routing-instances customer protocols vpls neighbor 10.255.14.217 encapsulation-type ethernet-
vlan
set routing-options router-id 10.255.14.225

```

Device CE1

```
set interfaces ge-2/0/8 vlan-tagging
set interfaces ge-2/0/8 unit 601 vlan-id 601
set interfaces ge-2/0/8 unit 601 family inet address 172.16.0.3/24
set interfaces lo0 unit 0 family inet address 10.255.14.214/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/8.601
```

Device CE2

```
set interfaces ge-2/1/5 vlan-tagging
set interfaces ge-2/1/5 unit 601 vlan-id 601
set interfaces ge-2/1/5 unit 601 family inet address 172.16.0.4/24
set interfaces lo0 unit 0 family inet address 10.255.14.215/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/5.601
```

Device CE3

```
set interfaces ge-2/0/9 vlan-tagging
set interfaces ge-2/0/9 unit 601 vlan-id 601
set interfaces ge-2/0/9 unit 601 family inet address 172.16.0.5/24
set interfaces lo0 unit 0 family inet address 10.255.14.218/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/9.601
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure H-VPLS on the MTU device:

1. Configure the interfaces.

On the MTU device interface that connects to the customer edge, configure one of the circuit cross-connect (CCC) encapsulation types and the CCC address family. This enables Layer 2 circuits.

On the core-facing interfaces, enable MPLS labels. The ISO address is needed as well on the core-facing interfaces because IS-IS is used in the core.

```
[edit interfaces]
user@PE1# set ge-2/0/5 vlan-tagging
user@PE1# set ge-2/0/5 encapsulation vlan-ccc
user@PE1# set ge-2/0/5 unit 601 family ccc
user@PE1# set ge-2/0/5 unit 601 encapsulation vlan-ccc
user@PE1# set ge-2/0/5 unit 601 vlan-id 601
user@PE1# set ge-2/0/5 unit 601 output-vlan-map swap
user@PE1# set ge-2/0/10 unit 0 family inet address 192.0.2.2/24
user@PE1# set ge-2/0/10 unit 0 family iso
user@PE1# set ge-2/0/10 unit 0 family mpls
user@PE1# set ge-2/0/11 unit 0 family inet address 192.0.2.3/24
user@PE1# set ge-2/0/11 unit 0 family iso
user@PE1# set ge-2/0/11 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 10.255.14.217/32
user@PE1# set lo0 unit 0 family iso address 49.0001.0102.5501.4217.00
```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```
[edit protocols mpls]
user@PE1# set interface ge-2/0/10.0
user@PE1# set interface ge-2/0/11.0
[edit protocols ldp ]
user@PE1# set interface ge-2/0/10.0
user@PE1# set interface ge-2/0/11.0
user@PE1# set interface lo0.0
```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```
[edit protocols isis]
user@PE1# set level 1 disable
user@PE1# set interface ge-2/0/10.0
```

```
user@PE1# set interface ge-2/0/11.0
user@PE1# set interface lo0.0
```

4. Configure the Layer 2 circuit.

The neighbor 10.255.14.225 is Device PE3's loopback interface address. This sets up the working path.

The neighbor 10.255.14.216 is Device PE2's loopback interface address. This sets up the backup path.

The virtual circuit ID must match the VPLS ID that is configured on Device PE2 and Device PE3.

```
[edit protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.601]
user@PE1# set virtual-circuit-id 601
user@PE1# set encapsulation-type ethernet-vlan
user@PE1# set backup-neighbor 10.255.14.216 standby
```

5. Configure the router ID.

```
[edit routing-options]
user@PE1# set router-id 10.255.14.217
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure H-VPLS on the MTU device:

1. Configure the interfaces.

On the PE-r device interface that connects to the customer edge, configure one of the VPLS encapsulation types and the VPLS address family. This enables VPLS.

On the core-facing interfaces, enable MPLS labels. The ISO address is needed as well on the core-facing interfaces because IS-IS is used in the core.

```
[edit interfaces]
user@PE2# set ge-2/0/6 vlan-tagging
user@PE2# set ge-2/0/6 encapsulation vlan-vpls
```

```

user@PE2# set ge-2/0/6 unit 601 encapsulation vlan-vpls
user@PE2# set ge-2/0/6 unit 601 vlan-id 601
user@PE2# set ge-2/0/6 unit 601 family vpls
user@PE2# set ge-2/0/10 unit 0 family inet address 192.0.2.4/24
user@PE2# set ge-2/0/10 unit 0 family iso
user@PE2# set ge-2/0/10 unit 0 family mpls
user@PE2# set lo0 unit 0 family inet address 10.255.14.216/32
user@PE2# set lo0 unit 0 family iso address 49.0001.0102.5501.4216.00

```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```

[edit protocols mpls]
user@PE2# set interface ge-2/0/10.0
[edit protocols ldp ]
user@PE2# set interface ge-2/0/10.0
user@PE2# set interface lo0.0

```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```

[edit protocols isis]
user@PE2# set level 1 disable
user@PE2# set interface ge-2/0/10.0
user@PE2# set interface lo0.0

```

4. Configure VPLS.

The neighbor 10.255.14.217 statement points to Device PE1's loopback interface address.

The VPLS ID must match the virtual circuit ID that is configured on the MTU (Device PE1).

```

[edit routing-instances customer]
user@PE2# set instance-type vpls
user@PE2# set interface ge-2/0/6.601
user@PE2# set protocols vpls vpls-id 601
user@PE2# set protocols vpls neighbor 10.255.14.217 encapsulation-type ethernet-vlan

```

5. Configure the router ID.

```
[edit routing-options]
user@PE2# set router-id 10.255.14.216
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

Device PE1

```
user@PE1# show interfaces
ge-2/0/5 {
  vlan-tagging;
  encapsulation vlan-ccc;
  unit 601 {
    encapsulation vlan-ccc;
    vlan-id 601;
    output-vlan-map swap;
    family ccc;
  }
}
ge-2/0/10 {
  unit 0 {
    family inet {
      address 192.0.2.2/24;
    }
    family iso;
    family mpls;
  }
}
ge-2/0/11 {
  unit 0 {
    family inet {
      address 192.0.2.3/24;
    }
    family iso;
    family mpls;
  }
}
```

```

}
lo0 {
    unit 0 {
        family inet {
            address 10.255.14.217/32;
        }
        family iso {
            address 49.0001.0102.5501.4217.00;
        }
    }
}
}

```

```

user@PE1# show protocols
mpls {
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
}
isis {
    level 1 disable;
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
    interface lo0.0;
}
ldp {
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
    interface lo0.0;
}
l2circuit {
    neighbor 10.255.14.225 {
        interface ge-2/0/5.601 {
            virtual-circuit-id 601;
            encapsulation-type ethernet-vlan;
            backup-neighbor 10.255.14.216 {
                standby;
            }
        }
    }
}

```



```

    }
}

```

```

user@PE1# show routing-options
router-id 10.255.14.217;

```

Device PE2

```

user@PE2# show interfaces
ge-2/0/6 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 601 {
        encapsulation vlan-vpls;
        vlan-id 601;
        family vpls;
    }
}
ge-2/0/10 {
    unit 0 {
        family inet {
            address 192.0.2.4/24;
        }
        family iso;
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.255.14.216/32;
        }
        family iso {
            address 49.0001.0102.5501.4216.00;
        }
    }
}

```

```
    }
}
```

```
user@PE2# show protocols
mpls {
    interface ge-2/0/10.0;
}
isis {
    level 1 disable;
    interface ge-2/0/10.0;
    interface lo0.0;
}
ldp {
    interface ge-2/0/10.0;
    interface lo0.0;
}
```

```
user@PE2# show routing-instances
customer {
    instance-type vpls;
    interface ge-2/0/6.601;
    protocols {
        vpls {
            vpls-id 601;
            neighbor 10.255.14.217 {
                encapsulation-type ethernet-vlan;
            }
        }
    }
}
```

```
user@PE2# show routing-options
router-id 10.255.14.216;
```

If you are done configuring the devices, enter **commit** from configuration mode.

Verification

IN THIS SECTION

- [Verifying the Layer 2 Circuit | 856](#)
- [Checking the VPLS Connections | 857](#)
- [Checking Connectivity | 859](#)
- [Manually Triggering a Switch from the Active Pseudowire to the Redundant Pseudowire | 860](#)

Confirm that the configuration is working properly.

Verifying the Layer 2 Circuit

Purpose

Verify that Layer 2 circuit is operational on the MTU device.

Action

From operational mode, enter the `show l2circuit connections` command.

```
user@PE1> show l2circuit connections
```

Layer-2 Circuit Connections:

Legend for connection status (St)

EI -- encapsulation invalid	NP -- interface h/w not present
MM -- mtu mismatch	Dn -- down
EM -- encapsulation mismatch	VC-Dn -- Virtual circuit Down
CM -- control-word mismatch	Up -- operational
VM -- vlan id mismatch	CF -- Call admission control failure
OL -- no outgoing label	IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC	TM -- TDM misconfiguration
BK -- Backup Connection	ST -- Standby Connection
CB -- rcvd cell-bundle size bad	SP -- Static Pseudowire
LD -- local site signaled down	RS -- remote site standby
RD -- remote site signaled down	XX -- unknown

Legend for interface status

```

Up -- operational
Dn -- down
Neighbor: 10.255.14.216
  Interface          Type  St    Time last up          # Up trans
ge-2/0/5.601(vc 601)  rmt   Up    Oct  9 16:28:58 2012      1
  Remote PE: 10.255.14.216, Negotiated control-word: No
  Incoming label: 299904, Outgoing label: 800001
  Negotiated PW status TLV: No
  Local interface: ge-2/0/5.601, Status: Up, Encapsulation: VLAN
Neighbor: 10.255.14.225
  Interface          Type  St    Time last up          # Up trans
ge-2/0/5.601(vc 601)  rmt   ST

```

Meaning

As expected, the Layer 2 circuit connection to Device PE3 is operational, and the connection to Device PE2 is in standby mode.

Checking the VPLS Connections

Purpose

Verify that the VPLS connections are operational on the PE-r devices.

Action

From operational mode, enter the `show vpls connections` command.

```
user@PE2> show vpls connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down

LD -- local site signaled down CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch MI -- Mesh-Group ID not available
BK -- Backup connection ST -- Standby connection
PF -- Profile parse failure PB -- Profile busy
RS -- remote site standby SN -- Static Neighbor
LB -- Local site not best-site RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status

Up -- operational

Dn -- down

Instance: customer

VPLS-id: 601

Neighbor	Type	St	Time last up	# Up trans
10.255.14.217(vpls-id 601)	rmt	Up	Oct 9 16:29:02 2012	1

Remote PE: 10.255.14.217, Negotiated control-word: No

Incoming label: 800001, Outgoing label: 299904

Negotiated PW status TLV: No

Local interface: vt-2/0/10.84934914, Status: Up, Encapsulation: VLAN

Description: Intf - vpls customer neighbor 10.255.14.217 vpls-id 601

user@PE3> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down NP -- interface hardware not present
CM -- control-word mismatch -> -- only outbound connection is up
CN -- circuit not provisioned <- -- only inbound connection is up
OR -- out of range Up -- operational
OL -- no outgoing label Dn -- down
LD -- local site signaled down CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated

```

XX -- unknown connection status  IL -- no incoming label
MM -- MTU mismatch                MI -- Mesh-Group ID not available
BK -- Backup connection           ST -- Standby connection
PF -- Profile parse failure        PB -- Profile busy
RS -- remote site standby          SN -- Static Neighbor
LB -- Local site not best-site     RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status
Up -- operational
Dn -- down

Instance: customer
VPLS-id: 601
Neighbor                Type  St    Time last up          # Up trans
10.255.14.217(vpls-id 601) rmt  Up    Oct  9 16:29:02 2012      1
Remote PE: 10.255.14.217, Negotiated control-word: No
Incoming label: 800001, Outgoing label: 299920
Negotiated PW status TLV: No
Local interface: vt-2/0/10.68157698, Status: Up, Encapsulation: VLAN
Description: Intf - vpls customer neighbor 10.255.14.217 vpls-id 601

```

Meaning

As expected, the VPLS connections are operational on both PE-r devices.

Checking Connectivity

Purpose

Verify that Device CE1 can ping Device CE3.

Action

```

user@CE1> ping 10.255.14.218
PING 10.255.14.218 (10.255.14.218): 56 data bytes
64 bytes from 10.255.14.218: icmp_seq=0 ttl=64 time=0.858 ms
64 bytes from 10.255.14.218: icmp_seq=1 ttl=64 time=0.527 ms
64 bytes from 10.255.14.218: icmp_seq=2 ttl=64 time=0.670 ms
^C
--- 10.255.14.218 ping statistics ---

```

```
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.527/0.685/0.858/0.136 ms
```

Meaning

The output shows that H-VPLS is operational.

Manually Triggering a Switch from the Active Pseudowire to the Redundant Pseudowire

Purpose

Make sure that the pseudowire between Device PE1 and Device PE2 becomes operational.

Action

```
user@CE1> request l2circuit-switchover virtual-circuit-id 601 neighbor 10.255.14.225
user@CE1> ping 10.255.14.215
PING 10.255.14.215 (10.255.14.215): 56 data bytes
64 bytes from 10.255.14.215: icmp_seq=0 ttl=64 time=0.738 ms
64 bytes from 10.255.14.215: icmp_seq=1 ttl=64 time=0.627 ms
64 bytes from 10.255.14.215: icmp_seq=2 ttl=64 time=0.629 ms
^C
--- 10.255.14.215 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.627/0.665/0.738/0.052 ms
```

Meaning

The successful ping from Device CE1 to Device CE2 shows that the pseudowire between Device PE1 and PE2 is operational. Now, if you ping Device CE3 from Device CE1, the ping should fail.

RELATED DOCUMENTATION

[Application Note: Demystifying H-VPLS](#)

[Example: Configuring H-VPLS Without VLANs | 861](#)

[Redundant Pseudowires for Layer 2 Circuits and VPLS | 223](#)

[Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS | 226](#)

Example: Configuring H-VPLS Without VLANs

IN THIS SECTION

- Requirements | 861
- Overview | 861
- Configuration | 862
- Verification | 872

This example shows how to configure the hierarchical virtual private LAN service (H-VPLS). No VLANs are configured in this example.

Requirements

No special configuration beyond device initialization is required before configuring this example.

Overview

H-VPLS uses LDP-based VPLS to signal and establish pseudowires. LDP-based VPLS is defined in RFC 4762, *Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling*. RFC 4762 also defines a hierarchical mode of operation for LDP VPLS called H-VPLS.

VPLS and H-VPLS are different with respect to scaling. VPLS requires a full mesh of tunnel label-switched paths (LSPs) among all of the provider edge (PE) routers that participate in the VPLS service. For each VPLS service, $n*(n-1)/2$ pseudowires must be set up between the PE routers. In contrast, H-VPLS partitions the network into several edge domains that are interconnected using an MPLS core. Each edge device only needs to learn of one local PE device and therefore needs less routing table support. This has the potential to allow service providers to use relatively less costly devices (such as EX Series switches) at the customer edge.

NOTE: As alternatives to H-VPLS, Juniper Networks offers other ways to address VPLS scalability. For more information, see [Application Note: Demystifying H-VPLS](#).


H-VPLS defines two roles or functionalities:

- PE-r—PE device that runs VPLS with other PE-r devices, but which also has pseudowires (it can be based on QinQ access) with another device called a multi-tenant unit (MTU), which provides the access layer.

- MTU—PE device that represents the access layer on the H-VPLS architecture and establishes pseudowires to one or more PE-r devices through which VPLS traffic is forwarded.

Figure 61 on page 862 shows the topology used in this example.

Figure 61: Basic H-VPLS With One MTU and Two PE-r Devices



The example shows one MTU (Device PE1) connected to two PE-r devices (Device PE2 and Device PE3).

The pseudowire between Device PE1 and Device PE3 is the primary or working path. The pseudowire between Device PE1 and Device PE2 is the backup path.

"CLI Quick Configuration" on page 863 shows the configuration for all of the devices in Figure 61 on page 862. The section "Step-by-Step Procedure" on page 865 describes the steps on Device PE1 and Device PE2.

Configuration

IN THIS SECTION

- Procedure | 863

Procedure

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device PE1

```
set interfaces ge-2/0/5 encapsulation ethernet-ccc
set interfaces ge-2/0/5 unit 0 family ccc
set interfaces ge-2/0/10 unit 0 family inet address 192.0.2.2/24
set interfaces ge-2/0/10 unit 0 family iso
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces ge-2/0/11 unit 0 family inet address 192.0.2.3/24
set interfaces ge-2/0/11 unit 0 family iso
set interfaces ge-2/0/11 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.217/32
set interfaces lo0 unit 0 family iso address 49.0001.0102.5501.4217.00
set protocols mpls interface ge-2/0/10.0
set protocols mpls interface ge-2/0/11.0
set protocols isis level 1 disable
set protocols isis interface ge-2/0/10.0
set protocols isis interface ge-2/0/11.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface ge-2/0/11.0
set protocols ldp interface lo0.0
set protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.0 virtual-circuit-id 601
set protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.0 backup-neighbor
10.255.14.216 standby
set routing-options router-id 10.255.14.217
```

Device PE2

```
set interfaces ge-2/0/6 encapsulation ethernet-vpls
set interfaces ge-2/0/6 unit 0 family vpls
set interfaces ge-2/0/10 unit 0 family inet address 192.0.2.4/24
set interfaces ge-2/0/10 unit 0 family iso
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.216/32
```

```

set interfaces lo0 unit 0 family iso address 49.0001.0102.5501.4216.00
set protocols mpls interface ge-2/0/10.0
set protocols isis level 1 disable
set protocols isis interface ge-2/0/10.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances customer instance-type vpls
set routing-instances customer interface ge-2/0/6.0
set routing-instances customer protocols vpls vpls-id 601
set routing-instances customer protocols vpls neighbor 10.255.14.217
set routing-options router-id 10.255.14.216

```

Device PE3

```

set interfaces ge-2/1/3 encapsulation ethernet-vpls
set interfaces ge-2/1/3 unit 0 family vpls
set interfaces ge-2/0/10 unit 0 family inet address 192.0.2.5/24
set interfaces ge-2/0/10 unit 0 family iso
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 10.255.14.225/32
set interfaces lo0 unit 0 family iso address 49.0001.0102.5501.4225.00
set protocols mpls interface ge-2/0/10.0
set protocols isis level 1 disable
set protocols isis interface ge-2/0/10.0
set protocols isis interface lo0.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances customer instance-type vpls
set routing-instances customer interface ge-2/1/3.0
set routing-instances customer protocols vpls vpls-id 601
set routing-instances customer protocols vpls neighbor 10.255.14.217
set routing-options router-id 10.255.14.225

```

Device CE1

```

set interfaces ge-2/0/8 unit 0 family inet address 172.16.0.3/24
set interfaces lo0 unit 0 family inet address 10.255.14.214/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/8.0

```

Device CE2

```
set interfaces ge-2/1/5 unit 0 family inet address 172.16.0.4/24
set interfaces lo0 unit 0 family inet address 10.255.14.215/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/5.0
```

Device CE3

```
set interfaces ge-2/0/9 unit 0 family inet address 172.16.0.5/24
set interfaces lo0 unit 0 family inet address 10.255.14.218/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/9.0
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure H-VPLS on the MTU device:

1. Configure the interfaces.

On the MTU device interface that connects to the customer edge, configure one of the circuit cross-connect (CCC) encapsulation types and the CCC address family. This enables Layer 2 circuits.

On the core-facing interfaces, enable MPLS labels. The ISO address is needed as well on the core-facing interfaces because IS-IS is used in the core.

```
[edit interfaces]
user@PE1# set ge-2/0/5 encapsulation ethernet-ccc
user@PE1# set ge-2/0/5 unit 0 family ccc
user@PE1# set ge-2/0/10 unit 0 family inet address 192.0.2.2/24
user@PE1# set ge-2/0/10 unit 0 family iso
user@PE1# set ge-2/0/10 unit 0 family mpls
user@PE1# set ge-2/0/11 unit 0 family inet address 192.0.2.3/24
user@PE1# set ge-2/0/11 unit 0 family iso
user@PE1# set ge-2/0/11 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 10.255.14.217/32
user@PE1# set lo0 unit 0 family iso address 49.0001.0102.5501.4217.00
```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```
[edit protocols mpls]
user@PE1# set interface ge-2/0/10.0
user@PE1# set interface ge-2/0/11.0
[edit protocols ldp ]
user@PE1# set interface ge-2/0/10.0
user@PE1# set interface ge-2/0/11.0
user@PE1# set interface lo0.0
```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```
[edit protocols isis]
user@PE1# set level 1 disable
user@PE1# set interface ge-2/0/10.0
user@PE1# set interface ge-2/0/11.0
user@PE1# set interface lo0.0
```

4. Configure the Layer 2 circuit.

The neighbor 10.255.14.225 is Device PE3's loopback interface address. This sets up the working path.

The neighbor 10.255.14.216 is Device PE2's loopback interface address. This sets up the backup path.

The virtual circuit ID must match the VPLS ID that is configured on Device PE2 and Device PE3.

```
[edit protocols l2circuit neighbor 10.255.14.225 interface ge-2/0/5.0]
user@PE1# set virtual-circuit-id 601
user@PE1# set backup-neighbor 10.255.14.216 standby
```

5. Configure the router ID.

```
[edit routing-options]
user@PE1# set router-id 10.255.14.217
```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure H-VPLS on the MTU device:

1. Configure the interfaces.

On the PE-r device interface that connects to the customer edge, configure one of the VPLS encapsulation types and the VPLS address family. This enables VPLS.

On the core-facing interfaces, enable MPLS labels. The ISO address is needed as well on the core-facing interfaces because IS-IS is used in the core.

```
[edit interfaces]
user@PE2# set ge-2/0/6 encapsulation ethernet-vpls
user@PE2# set ge-2/0/6 unit 0 family vpls
user@PE2# set ge-2/0/10 unit 0 family inet address 192.0.2.4/24
user@PE2# set ge-2/0/10 unit 0 family iso
user@PE2# set ge-2/0/10 unit 0 family mpls
user@PE2# set lo0 unit 0 family inet address 10.255.14.216/32
user@PE2# set lo0 unit 0 family iso address 49.0001.0102.5501.4216.00
```

2. Enable MPLS and LDP on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure MPLS and LDP.

```
[edit protocols mpls]
user@PE2# set interface ge-2/0/10.0
[edit protocols ldp ]
user@PE2# set interface ge-2/0/10.0
user@PE2# set interface lo0.0
```

3. Enable routing on the interfaces.

On the MTU device interfaces that connect to other PE devices, configure an interior gateway protocol (IGP), such as OSPF or IS-IS.

```
[edit protocols isis]
user@PE2# set level 1 disable
user@PE2# set interface ge-2/0/10.0
user@PE2# set interface lo0.0
```

4. Configure VPLS.

The neighbor 10.255.14.217 statement points to Device PE1's loopback interface address.

The VPLS ID must match the virtual circuit ID that is configured on the MTU (Device PE1).

```
[edit routing-instances customer]
user@PE2# set instance-type vpls
user@PE2# set interface ge-2/0/6.0
user@PE2# set protocols vpls vpls-id 601
user@PE2# set protocols vpls neighbor 10.255.14.217
```

5. Configure the router ID.

```
[edit routing-options]
user@PE2# set router-id 10.255.14.216
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

Device PE1

```
user@PE1# show interfaces
ge-2/0/5 {
  encapsulation ethernet-ccc;
  unit 0 {
    family ccc;
  }
}
```

```

ge-2/0/10 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
        family iso;
        family mpls;
    }
}
ge-2/0/11 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
        family iso;
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.255.14.217/32;
        }
        family iso {
            address 49.0001.0102.5501.4217.00;
        }
    }
}

```

```

user@PE1# show protocols
mpls {
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
}
isis {
    level 1 disable;
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
    interface lo0.0;
}
ldp {

```



```

interface ge-2/0/10.0;
interface ge-2/0/11.0;
interface lo0.0;
}
l2circuit {
  neighbor 10.255.14.225 {
    interface ge-2/0/5.0 {
      virtual-circuit-id 601;
      backup-neighbor 10.255.14.216 {
        standby;
      }
    }
  }
}
}

```

```

user@PE1# show routing-options
router-id 10.255.14.217;

```

Device PE2

```

user@PE2# show interfaces
ge-2/0/6 {
  encapsulation ethernet-vpls;
  unit 0 {
    family vpls;
  }
}
ge-2/0/10 {
  unit 0 {
    family inet {
      address 192.0.2.4/24;
    }
    family iso;
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.255.14.216/32;
    }
  }
}

```

```

        family iso {
            address 49.0001.0102.5501.4216.00;
        }
    }
}

```

```

user@PE2# show protocols
mpls {
    interface ge-2/0/10.0;
}
isis {
    level 1 disable;
    interface ge-2/0/10.0;
    interface lo0.0;
}
ldp {
    interface ge-2/0/10.0;
    interface lo0.0;
}

```

```

user@PE2# show routing-instances
customer {
    instance-type vpls;
    interface ge-2/0/6.0;
    protocols {
        vpls {
            vpls-id 601;
            neighbor 10.255.14.217;
        }
    }
}

```

```

user@PE2# show routing-options
router-id 10.255.14.216;

```

If you are done configuring the devices, enter **commit** from configuration mode.

Verification

IN THIS SECTION

- [Verifying the Layer 2 Circuit | 872](#)
- [Checking the VPLS Connections | 873](#)
- [Checking Connectivity | 875](#)
- [Manually Triggering a Switch from the Active Pseudowire to the Redundant Pseudowire | 876](#)

Confirm that the configuration is working properly.

Verifying the Layer 2 Circuit

Purpose

Verify that the Layer 2 circuit is operational on the MTU device.

Action

From operational mode, enter the `show l2circuit connections` command.

```
user@PE1> show l2circuit connections
```

Layer-2 Circuit Connections:

Legend for connection status (St)

EI -- encapsulation invalid	NP -- interface h/w not present
MM -- mtu mismatch	Dn -- down
EM -- encapsulation mismatch	VC-Dn -- Virtual circuit Down
CM -- control-word mismatch	Up -- operational
VM -- vlan id mismatch	CF -- Call admission control failure
OL -- no outgoing label	IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC	TM -- TDM misconfiguration
BK -- Backup Connection	ST -- Standby Connection
CB -- rcvd cell-bundle size bad	SP -- Static Pseudowire
LD -- local site signaled down	RS -- remote site standby
RD -- remote site signaled down	XX -- unknown

Legend for interface status

```

Up -- operational
Dn -- down
Neighbor: 10.255.14.216
  Interface          Type  St    Time last up      # Up trans
  ge-2/0/5.0(vc 601)  rmt   ST
Neighbor: 10.255.14.225
  Interface          Type  St    Time last up      # Up trans
  ge-2/0/5.0(vc 601)  rmt   Up    Oct  5 19:38:15 2012      1
  Remote PE: 10.255.14.225, Negotiated control-word: No
  Incoming label: 299872, Outgoing label: 800001
  Negotiated PW status TLV: No
  Local interface: ge-2/0/5.0, Status: Up, Encapsulation: ETHERNET

```

Meaning

As expected, the Layer 2 circuit connection to Device PE3 is operational, and the connection to Device PE2 is in standby mode.

Checking the VPLS Connections

Purpose

Verify that the VPLS connections are operational on the PE-r devices.

Action

From operational mode, enter the `show vpls connections` command.

```
user@PE2> show vpls connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down

LD -- local site signaled down CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch MI -- Mesh-Group ID not available
BK -- Backup connection ST -- Standby connection
PF -- Profile parse failure PB -- Profile busy
RS -- remote site standby SN -- Static Neighbor
LB -- Local site not best-site RB -- Remote site not best-site
VM -- VLAN ID mismatch

Legend for interface status

Up -- operational

Dn -- down

Instance: customer

VPLS-id: 601

Neighbor	Type	St	Time last up	# Up trans
10.255.14.217(vpls-id 601)	rmt	Up	Oct 8 14:46:54 2012	1
Remote PE: 10.255.14.217, Negotiated control-word: No				
Incoming label: 800001, Outgoing label: 299856				
Negotiated PW status TLV: No				
Local interface: vt-2/0/10.84934913, Status: Up, Encapsulation: ETHERNET				
Description: Intf - vpls customer neighbor 10.255.14.217 vpls-id 601				

user@PE3> **show vpls connections**

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down NP -- interface hardware not present
CM -- control-word mismatch -> -- only outbound connection is up
CN -- circuit not provisioned <- -- only inbound connection is up
OR -- out of range Up -- operational
OL -- no outgoing label Dn -- down
LD -- local site signaled down CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated

```

XX -- unknown connection status  IL -- no incoming label
MM -- MTU mismatch                MI -- Mesh-Group ID not available
BK -- Backup connection           ST -- Standby connection
PF -- Profile parse failure        PB -- Profile busy
RS -- remote site standby          SN -- Static Neighbor
LB -- Local site not best-site     RB -- Remote site not best-site
VM -- VLAN ID mismatch

```

Legend for interface status

Up -- operational

Dn -- down

Instance: customer

VPLS-id: 601

Neighbor	Type	St	Time last up	# Up trans
10.255.14.217(vpls-id 601)	rmt	Up	Oct 8 14:46:54 2012	1

Remote PE: 10.255.14.217, Negotiated control-word: No
Incoming label: 800001, Outgoing label: 299872
Negotiated PW status TLV: No
Local interface: vt-2/0/10.68157697, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls customer neighbor 10.255.14.217 vpls-id 601

Meaning

As expected, the VPLS connections are operational on both PE-r devices.

Checking Connectivity

Purpose

Verify that Device CE1 can ping Device CE3.

Action

```

user@CE1> ping 10.255.14.218
PING 10.255.14.218 (10.255.14.218): 56 data bytes
64 bytes from 10.255.14.218: icmp_seq=0 ttl=64 time=0.858 ms
64 bytes from 10.255.14.218: icmp_seq=1 ttl=64 time=0.527 ms
64 bytes from 10.255.14.218: icmp_seq=2 ttl=64 time=0.670 ms
^C
--- 10.255.14.218 ping statistics ---

```

```
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.527/0.685/0.858/0.136 ms
```

Meaning

The output shows that H-VPLS is operational.

Manually Triggering a Switch from the Active Pseudowire to the Redundant Pseudowire

Purpose

Make sure that the pseudowire between Device PE1 and Device PE2 becomes operational.

Action

```
user@CE1> request l2circuit-switchover virtual-circuit-id 601 neighbor 10.255.14.225
user@CE1> ping 10.255.14.215
PING 10.255.14.215 (10.255.14.215): 56 data bytes
64 bytes from 10.255.14.215: icmp_seq=0 ttl=64 time=0.738 ms
64 bytes from 10.255.14.215: icmp_seq=1 ttl=64 time=0.627 ms
64 bytes from 10.255.14.215: icmp_seq=2 ttl=64 time=0.629 ms
^C
--- 10.255.14.215 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.627/0.665/0.738/0.052 ms
```

Meaning

The successful ping from Device CE1 to Device CE2 shows that the pseudowire between Device PE1 and PE2 is operational. Now, if you ping Device CE3 from Device CE1, the ping should fail.

RELATED DOCUMENTATION

[Application Note: Demystifying H-VPLS](#)

[Example: Configuring H-VPLS With VLANs | 843](#)

[Redundant Pseudowires for Layer 2 Circuits and VPLS | 223](#)

[Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS | 226](#)

Sample Scenario of H-VPLS on ACX Series Routers for IPTV Services

IN THIS SECTION

- [Sample Configuration Scenario of H-VPLS for IPTV Services | 877](#)
- [Guidelines for H-VPLS on ACX Routers | 879](#)

Hierarchical LDP-based VPLS requires a full mesh of tunnel LSPs between all the PE routers that participate in the VPLS service. For each VPLS service, $n*(n-1)/2$ pseudowires must be set up between the PE routers. Although the full mesh requirement creates signaling overhead, the larger negative impact to large-scale deployment is the packet replication requirements for each provisioned pseudowire on a PE router. Using hierarchical connectivity reduces signaling and replication overhead to facilitate large-scale deployments. .

In a typical IPTV solution, IPTV sources are in the public domain and the subscribers are in the private VPN domain. The objective is to deliver the multicast streams originated from the IPTV source to the set-top boxes or subscribers in the private domain. Generally, for an efficient delivery of multicast data from the IP Sources to the access devices (ACX in this case), P2MP LSPs and mVPN is used. The subscriber devices could then be connected to a VPLS or a Layer 3 VPN domain in Access router and they could be configured to import the multicast routes from an MVPN instance. Because VPLS and MVPN are not supported on ACX routers, an alternative approach can be used to achieve H-VPLS capabilities. The support for PIM snooping in Layer 3 interfaces, IGMP snooping in Layer 2 networks, IRB interfaces, and logical tunnel interfaces enables HVLS support.

An ACX router receives the multicast data on the default VRP context and the data gets forwarded on to the BD through IRB and gets replicated on the BD ports based on the membership detected through IGMP snooping. Unicast control traffic between Subscriber devices and the IPTV subscriber management server goes through the private VPN domain. Aggregation routers have VPLS full-mesh connectivity between each other and ACX works as H-VPLS MTU. There is a PW setup between ACX and the aggregation router. LT interface does the stitching of the Bridge domain with the PW

Sample Configuration Scenario of H-VPLS for IPTV Services

Consider a scenario in which set-top boxes (STBs) or customer premises equipment (CPE) devices are connected to two ACX routers, ACX1 and ACX2. On the ACX routers, a global virtual routing and forwarding (VRF) context, bridge domains, pseudowires, and IRB settings are defined. ACX1 is connected to two MX Series routers, MX2 and MX3. Connection to ACX1 to MX2 is through an active pseudowire with PIM deployed. PIM is used as the transport protocol in communication between ACX and MX routers. Unicast transmission is also configured. Connection of ACX1 to MX3 is through a

backup pseudowire. ACX2 is connected to two MX Series routers, MX2 and MX3. Connection to ACX2 to MX2 is through an active pseudowire. ACX2 is linked to MX3 using a standby pseudowire. MX2 and MX3 are connected to MX1, which is the root of the LSP. MX1 is linked to an IPTV source.

Point-to-multipoint (P2MP) traffic engineering (TE) LSP is setup from the MX router (MX-1 is connected to the IPTV source) to the aggregation MX routers (MX-2 & MX-3). MX-1 is the root of the LSP. MX-2 and MX-3 are the leaves. Leaves cannot be configured statically or dynamically.

- PIM can be enabled between MX-1 and IPTV Source and MX-1 is the DR for the Multicast source.
- mVPN is configured on the default VRF routing instance. Selective tree can be used for optimal routing.
- PIM-SM is running in the Access network between access routers (ACX-1 and ACX-2) and aggregation routers (MX-1 and MX-2).

MX-1 and MX-2 are the RPs for the PIM-SM.

- RPF check is disabled for the multicast groups in aggregation routers for it to accept the data from remote source.
- Rendezvous point (RP) redundancy is achieved by configuring auto-RP in ACXs and configuring multiple aggregation routers as RP for every access ring (PIM island).

ACX has a bridge-domain and subscriber devices are connected to the BD ports. This enables the subscribers to be on the same IP subnet. (This method of configuration suits a topology in which you want all the subscribers connected to the ACXs in a single access ring to be on the same subnet. This makes the DHCP server pool allocation policy easier). No local switching is enabled on the bridge domain, to ensure that subscriber to subscriber communication does not occur locally through the bridge domain.

- Bridge domain has the IRB configuration providing connectivity to the default VRF router instance. IGMP is enabled on the IRB interface. This enables the IGMP join messages send by the subscriber devices to be processed by the routing module and in turn triggers a PIM join towards RP in the default routing instance.
- IGMP snooping is enabled on the bridge domain for an optimal forwarding of multicast data at the BD level.
- ACX router receives the multicast data on the default VRP context and the data gets forwarded on to the BD through IRB and gets replicated on the BD ports based on the membership detected through IGMP snooping.
- Unicast control traffic between Subscriber devices and the IPTV subscriber management server goes through the private VPN domain.

- Aggregation routers have VPLS full-mesh connectivity between each other and ACX works as H-VPLS MTU.
- There is a PW set up between ACX and the aggregation router. LT interface does the stitching of the Bridge domain with the PW.
- An active and a standby pseudowire are set up between ACX and aggregation routers to support redundancy for the control traffic.
- PW terminates into the VPLS instance in the aggregation router. PWs from multiple ACX routers are terminated to the same VPLS instance as all the subscribers across all ACX boxes connected to a same aggregation router are in the same subnet.
- VPLS instance in the aggregation router is connected to the L3VPN instance through IRB interface which has IP address from the same subnet as the subscribers. Subscriber management station that is controlling the subscribers belong to a particular customer is connected to this Layer 3 VPN domain.

Guidelines for H-VPLS on ACX Routers

Keep the following points in mind while configuring H-VPLS on ACX routers:

- Control traffic is limited to 1G or 10G bandwidth based on the logical tunnel (lt-) interface limitation.
- Multicast data delivery is based on PIM on the access network. Therefore, the convergence time is directly related to the convergence time of the IGP protocol configured on the access network.
- Two versions of multicast solutions must be implemented in the provider network for the end-to-end solution to work. Also, you must set up PIM- based solution on the access network and MVPN-based solution on the aggregation or core network. This topology is considered a configuration overhead.
- IPv6 multicast and active-active redundancy models are not supported.
- You can implement an IPTV framework without the MVPN and VPLS support on ACX routers.
- Multicast support using PIM-SM and IGMP is supported,
- Unicast control traffic is restricted to the customer VPN domain.
- Support for multiple subscribers to be on the same IP subnet is provided. Direct communication between the subscribers at the ACX level is disabled.
- IGMP snooping is supported to ensure that the multicast data is not forwarded to the subscribers that are not registered for that data.
- An IRB interface is used for only multicast data delivery from the default VRF context.

RELATED DOCUMENTATION

[PIM Overview](#)

[Understanding IGMP](#)

[Layer 2 Bridge Domains on ACX Series Overview](#)

Configuring Multihoming

IN THIS CHAPTER

- [VPLS Multihoming Overview | 881](#)
- [Advantages of Using Autodiscovery for VPLS Multihoming | 884](#)
- [Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 885](#)
- [Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)
- [Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)
- [VPLS Multihoming Reactions to Network Failures | 949](#)
- [Configuring VPLS Multihoming | 950](#)
- [Example: VPLS Multihoming, Improved Convergence Time | 953](#)
- [Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)
- [Next-Generation VPLS for Multicast with Multihoming Overview | 991](#)
- [Example: Next-Generation VPLS for Multicast with Multihoming | 997](#)


VPLS Multihoming Overview

Virtual private LAN service (VPLS) multihoming enables you to connect a customer site to two or more PE routers to provide redundant connectivity. A redundant PE router can provide network service to the customer site as soon as a failure is detected. VPLS multihoming helps to maintain VPLS service and traffic forwarding to and from the multihomed site in the event of the following types of network failures:

- PE router to CE device link failure
- PE router failure

- MPLS-reachability failure between the local PE router and a remote PE router

Figure 62: CE Device Multihomed to Two PE Routers



NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Figure 62 on page 882 illustrates how a CE device could be multihomed to two PE routers. Device CE1 is multihomed to Routers PE1 and PE2. Device CE2 has two potential paths to reach Device CE1, but only one path is active at any one time. If Router PE1 were the designated VPLS edge (VE) device (also called a designated forwarder), BGP would signal a pseudowire from Router PE3 to Router PE1. If a failure occurred over this path, Router PE2 would be made the designated VE device, and BGP would re-signal the pseudowire from Router PE3 to Router PE2.

Multihomed PE routers advertise network layer reachability information (NLRI) for the multihomed site to the other PE routers in the VPLS network. The NLRI includes the site ID for the multihomed PE routers. For all of the PE routers multihomed to the same CE device, you need to configure the same site ID. The remote VPLS PE routers use the site ID to determine where to forward traffic addressed to the customer site. To avoid route collisions, the site ID shared by the multihomed PE routers must be different than the site IDs configured on the remote PE routers in the VPLS network.

Although you configure the same site ID for each of the PE routers multihomed to the same CE device, you can configure unique values for other parameters, such as the route distinguisher. These values help to determine which multihomed PE router is selected as the designated VE device to be used to reach the customer site.

BEST PRACTICE: We recommend that you configure unique route distinguishers for each multihomed PE router. Configuring unique route distinguishers helps with faster convergence when the connection to a primary multihomed PE router goes down. If you configure unique route distinguishers, the other PE routers in the VPLS network must maintain additional state for the multihomed PE routers.

Remote PE routers in the VPLS network need to determine which of the multihomed PE routers should forward traffic to reach the CE device. To make this determination, remote PE routers use the VPLS path-selection process to select one of the multihomed PE routers based on its NLRI advertisement. Because remote PE routers pick only one of the NLRI advertisements, it establishes a pseudowire to only one of the multihomed PE routers, the PE router that originated the winning advertisement. This prevents multiple paths from being created between sites in the network, preventing the formation of Layer 2 loops. If the selected PE router fails, all PE routers in the network automatically switch to the backup PE router and establish new pseudowires to it.

BEST PRACTICE: To prevent the formation of Layer 2 loops between the CE devices and the multihomed PE routers, we recommend that you employ the Spanning Tree Protocol (STP) on your CE devices. Layer 2 loops can form due to incorrect configuration. Temporary Layer 2 loops can also form during convergence after a change in the network topology.

The PE routers run the BGP path selection procedure on locally originated and received Layer 2 route advertisements to establish that the routes are suitable for advertisement to other peers, such as BGP route reflectors. If a PE router in a VPLS network is also a route reflector, the path selection process for the multihomed site has no effect on the path selection process performed by this PE router for the purpose of reflecting Layer 2 routes. Layer 2 prefixes that have different route distinguishers are considered to have different NLRIs for route reflection. The VPLS path selection process enables the route reflector to reflect all routes that have different route distinguishers to the route reflector clients, even though only one of these routes is used to create the VPLS pseudowire to the multihomed site.

Junos OS supports VPLS multihoming for both BGP VPLS and FEC129 VPLS. Support for FEC 129 is added in Junos OS Release 12.3.

RELATED DOCUMENTATION

[Configuring VPLS Multihoming | 950](#)

[Advantages of Using Autodiscovery for VPLS Multihoming | 884](#)

[Example: Configuring VPLS Multihoming \(FEC 129\) | 973](#)

[Example: VPLS Multihoming, Improved Convergence Time | 953](#)

Advantages of Using Autodiscovery for VPLS Multihoming

Virtual private LAN service (VPLS) provides a multipoint-to-multipoint Ethernet service that can span one or more metropolitan areas and provides connectivity between multiple sites as if these sites were attached to the same Ethernet LAN.

VPLS uses an IP and MPLS service provider infrastructure. From a service provider's point of view, use of IP and MPLS routing protocols and procedures instead of the Spanning Tree Protocol (STP), and MPLS labels instead of VLAN IDs, significantly improves the scalability of the VPLS service.

It is frequently a requirement for a service provider to supply its customers with redundant connectivity to one or more sites. This capability is called multihoming.

VPLS multihoming enables you to connect a customer site to two or more PE routers to provide redundant connectivity. A redundant PE router can provide network service to the customer site as soon as a failure is detected. VPLS multihoming helps to maintain VPLS service and traffic forwarding to and from the multihomed site in the event of the following types of network failures:

- PE router to CE device link failure
- PE router failure
- MPLS-reachability failure between the local PE router and a remote PE router

The Junos® operating system (Junos OS) supports both forwarding equivalency class (FEC) 128 and FEC 129. FEC 128 requires manually configured pseudowires. FEC 129 uses VPLS autodiscovery to convey endpoint information. After PE routers are autodiscovered, pseudowires are created automatically.

VPLS multihoming with support for FEC 129 enables you to interoperate with other vendor's auto-discovery for LDP-signaled VPLS. This interoperability allows you to select the vendor that offers the best value.

RELATED DOCUMENTATION

[VPLS Multihoming Overview | 881](#)

[Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

Example: Configuring FEC 129 BGP Autodiscovery for VPWS

IN THIS SECTION

- [Understanding VPWS | 885](#)
- [Understanding FEC 129 BGP Autodiscovery for VPWS | 888](#)
- [Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 891](#)

Understanding VPWS

IN THIS SECTION

- [Supported and Unsupported Features | 887](#)

Virtual private wire service (VPWS) Layer 2 VPNs employ Layer 2 services over MPLS to build a topology of point-to-point connections that connect end customer sites in a VPN. These Layer 2 VPNs provide an alternative to private networks that have been provisioned by means of dedicated leased lines or by means of Layer 2 virtual circuits that employ ATM or Frame Relay. The service provisioned with these Layer 2 VPNs is known as VPWS. You configure a VPWS *instance* on each associated edge device for each VPWS Layer 2 VPN.

Traditional VPNs over Layer 2 circuits require the provisioning and maintenance of separate networks for IP and for VPN services. In contrast, *VPWS* enables the sharing of a provider's core network infrastructure between IP and Layer 2 VPN services, reducing the cost of providing those services.

Junos OS supports two types of VPWS Layer 2 VPNs:

- Kompella Layer 2 VPNs, which use BGP for autodiscovery and signaling.
- FEC 129 BGP autodiscovery for VPWS, which uses BGP for autodiscovery and LDP as the signaling protocol.


FEC 129 BGP autodiscovery for VPWS requires the `l2vpn-id`, `source-attachment-identifier`, and `target-attachment-identifier` statements. Kompella Layer 2 VPNs require the `site-identifier` and `remote-site-id` statements.

NOTE: VPWS creates pseudowires that emulate Layer 2 circuits. A virtual private LAN service (VPLS) network is similar to VPWS, but provides point-to-multipoint traffic forwarding in contrast to the VPWS Layer 2 VPN's point-to-point traffic forwarding. If you need point-to-multipoint service instead of point-to-point service, consider using VPLS instead of VPWS.

A VPWS Layer 2 VPN can have either a full-mesh or a hub-and-spoke topology. The tunneling mechanism in the core network typically is MPLS. However, VPWS can also use other tunneling protocols, such as GRE. VPWS is similar to Martini Layer 2 services over MPLS, and employs a similar encapsulation scheme for forwarding traffic.

Figure 63 on page 886 illustrates an example of a simple VPWS Layer 2 VPN topology.

Figure 63: VPWS Sample Topology



In this example, the service provider offers VPWS services to Customer A and Customer B. Customer A wants to create a full mesh of point-to-point links between Westford and Bangalore. Customer B needs only a single point-to-point link between Westford and Sunnyvale. The service provider uses BGP and MPLS signaling in the core, and creates a set of unidirectional pseudowires at each provider edge (PE) device to separately cross-connect each customer's Layer 2 circuits.

In order to provision this service, the provider configures two VPWS Layer 2 VPNs, Layer 2 VPN A and Layer 2 VPN B. The circuit cross-connect (CCC) encapsulation type (`ethernet-ccc` or `vlan-ccc`) is configured for each VPWS Layer 2 VPN. All interfaces in a given VPWS Layer 2 VPN must be configured with the VPWS Layer 2 VPN's encapsulation type.

Local and remote site information for the interfaces identifies the cross-connect. Local cross-connects are supported when the interfaces that are connected belong to two different sites configured in the same VPWS instance and on the same PE device.

BGP advertises reachability for the VPNs. The BGP configuration is similar to that used for other VPN services, such as Layer 3 VPNs and VPLS. MPLS is configured to set up base LSPs to the remote PE devices similarly to the other VPN services.

Junos OS provides VPWS support the following configuration methods:

- Pseudowires are manually configured using Forwarding Equivalence Class (FEC) 128.
- Pseudowires are signaled by LDP using FEC 129. This arrangement reduces the configuration burden that is associated with statically configured Layer 2 circuits while still using LDP as the underlying signaling protocol.

Supported and Unsupported Features

Junos OS supports the following features with VPWS :

- Intra-AS VPWS functionality using BGP for autodiscovery and FEC 129 LDP for pseudowire signaling.
- *Graceful Routing Engine switchover.*
- Operation, administration, and maintenance (OAM) mechanisms, including Bidirectional Forwarding Detection and MPLS ping.
- FEC 128 LDP signaling with static configuration (in Junos OS this is configured within protocols 12circuit). With this option, there is no BGP autodiscovery.

Junos OS does not support the following VPWS functionality:

- Multihoming of customer sites to multiple PE devices using the BGP site model of multihoming.
- Terminating FEC 129 VPWS into a mesh group of an FEC 129 VPLS instance.

- Intra-AS VPWS functionality using BGP for autodiscovery and FEC 128 LDP for pseudowire signaling.
- FEC 129 VPWS without BGP autodiscovery.
- Static configuration of VPWS with FEC 129 signaling.
- *Nonstop active routing*.
- Multi-segment pseudowires.
- Interworking of FEC 128 and FEC 129 VPWS.
- Statically configured Layer 2 circuit-style pseudowire redundancy.
- Inter-AS deployments.

SEE ALSO

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

Understanding FEC 129 BGP Autodiscovery for VPWS

IN THIS SECTION

- Supported Standards in FEC 129 BGP Autodiscovery for VPWS | 889
- Routes and Routing Table Interaction in FEC 129 BGP Autodiscovery for VPWS | 889
- Layer 2 VPN Behavior in FEC 129 BGP Autodiscovery for VPWS | 890
- BGP Autodiscovery Behavior in FEC 129 BGP Autodiscovery for VPWS | 890
- LDP Signaling Behavior in VPWS in FEC 129 BGP Autodiscovery for VPWS | 891

The major functional components in a *VPWS* with FEC 129 are BGP, LDP, and the Layer 2 VPN module of Junos OS. BGP is responsible for distributing the local autodiscovery routes created on each PE device to all other PE devices. LDP is responsible for using the autodiscovery information provided by BGP to set up targeted LDP sessions over which to signal the pseudowires. The Layer 2 VPN is the glue that binds the BGP and LDP functionalities together.

Supported Standards in FEC 129 BGP Autodiscovery for VPWS

The relevant RFCs for this feature are as follows:

- RFC 4447, *Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)*
- RFC 6074, *Provisioning, Auto-Discovery, and Signaling in Layer 2 Virtual Private Networks (L2VPNs)*

Routes and Routing Table Interaction in FEC 129 BGP Autodiscovery for VPWS

BGP, LDP, and Layer 2 VPNs interact through different types of routes installed in the *instance.l2vpn.0* table. The routes that are present in the table are autodiscovery routes and pseudowire routes.

- Autodiscovery routes are used by BGP to allow autodiscovery of remote source access individual identifiers (SAIs) (the sources of the point-to-point pseudowires) and PE device addresses. Autodiscovery routes are advertised when you configure the `l2vpn auto-discovery-only` address family.

The format of the autodiscovery routes is a combination of the route distinguisher and the SAI. For example: 10.255.0.1:100:0.0.0.1/96 AD.

[Table 21 on page 889](#) lists the route elements and the number of associated bytes allocated to each element.

Table 21: Autodiscovery Route Format

Route Element	Bytes
RD	8 bytes
SAI	4 bytes

The `l2vpn-id` of the FEC 129 VPWS instance is attached to the route in a BGP extended community. One autodiscovery route is advertised for each source attachment identifier (SAI) in the instance.

- Pseudowire routes are installed by the Layer 2 VPN (local) and LDP (remote) to represent the bidirectional components of the pseudowire. For example: NoCtrlWord:5:100:200:2:0.0.0.1/176. The format of the routes is described in [Table 22 on page 890](#).

Table 22: Pseudowire Route Format

Field Name	Field Description
Pseudowire type + control word bit	2 bytes
Remote PE address	4 bytes
Attachment group identifier (AGI) The AGI field of the pseudowire route is always set to the l2vpn-id of the instance.	8 bytes
SAll	4 bytes
Target attachment individual identifier (TAII)	4 bytes

Layer 2 VPN Behavior in FEC 129 BGP Autodiscovery for VPWS

A Layer 2 VPN installs a locally generated autodiscovery route into the instance.l2vpn.0 table for every SAll configured in an FEC 129 VPWS instance. The extended community containing the l2vpn-id is attached when the route is added to the instance.l2vpn.0 table.

For each autodiscovered SAll from a remote neighbor where the l2vpn-id matches the local l2vpn-id and the received SAll matches a locally configured TAll, the Layer 2 VPN obtains an MPLS label and generates a pseudowire route and adds it to the instance.l2vpn.0 table. The remote PE address is copied from the BGP protocol next hop for the autodiscovery route.

The Layer 2 VPN module of Junos OS is responsible for installing the forwarding routes into the mpls.0 table as usual.

BGP Autodiscovery Behavior in FEC 129 BGP Autodiscovery for VPWS

Local autodiscovery routes installed by the Layer 2 VPN in the instance.l2vpn.0 table are advertised by BGP to remote PE devices s12vpn auto-discovery-only address family according to the instance and BGP export policies.

On the receiving side, BGP accepts autodiscovery routes from remote peers and installs them in the local bgp.l2vpn.0 table, if they are allowed by inbound policy. The route is installed, and a secondary route is imported into the instance.l2vpn.0 table when an import route target match between the route and instance is found.

LDP Signaling Behavior in VPWS in FEC 129 BGP Autodiscovery for VPWS

In the Junos OS implementation of LDP, the router monitors for routes from instance.l2vpn.0 for any instance configured for FEC 129 VPWS. These routes are identified by the instance-type l2vpn statement in the routing instance and the presence of the l2vpn-id statement.

When a BGP autodiscovery route is installed, LDP sets up a targeted session with the remote peer, where the peer address is identified as the protocol next hop of the BGP autodiscovery route.

When a pseudowire route is installed in the instance.l2vpn.0 table, LDP uses the parameters associated with the route to signal the creation of the pseudowire using FEC 129. Upon receiving an FEC 129 label mapping message from a remote peer, LDP installs the pseudowire route in the ldp.l2vpn.0 table.

Upon a successful l2vpn-id match with a configured FEC 129 VPWS instance, a secondary pseudowire route is imported to the instance.l2vpn.0 table. If an outgoing pseudowire has not already been set up when the incoming pseudowire signaling is received, LDP initiates the outgoing pseudowire creation as well.

SEE ALSO

[Understanding VPWS | 498](#)

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 508](#)

Example: Configuring FEC 129 BGP Autodiscovery for VPWS

IN THIS SECTION

- [Requirements | 892](#)
- [Overview | 892](#)
- [Configuration | 897](#)
- [Verification | 903](#)

This example shows how to configure the virtual private wire service (VPWS), where remote provider edge (PE) devices are automatically discovered dynamically by BGP, and pseudowires are signaled by LDP using FEC 129. This arrangement reduces the configuration burden that is associated with statically configured Layer 2 circuits while still using LDP as the underlying signaling protocol.

Requirements

This example requires Junos OS Release 13.2 or later on the PE devices.

Overview

IN THIS SECTION

- [Topology Diagram | 896](#)

Because VPWS is a point-to-point service, FEC 129 VPWS routing instances are configured as instance-type `l2vpn`. As with FEC 129 VPLS, FEC 129 VPWS uses the `l2vpn-id` statement to define the Layer 2 VPN of which the routing instance is a member. The presence of the `l2vpn-id` statement designates that FEC 129 LDP signaling is used for the routing instance. The absence of `l2vpn-id` indicates that BGP signaling is used instead.

The point-to-point nature of VPWS requires that you specify the source access individual identifier (SAIL) and the target access individual identifier (TAIL). This SAIL-TAIL pair defines a unique pseudowire between two PE devices.

The SAIL is specified with the `source-attachment-identifier` statement within the FEC 129 VPWS routing instance. You configure the source attachment identifier and the interfaces to associate with that source attachment identifier. Under each interface, you can configure the TAIL with the `target-attachment-identifier` statement. If the configured target identifier matches a source identifier advertised by a remote PE device by way of a BGP autodiscovery message, the pseudowire between that source-target pair is signaled. If there is no match between an advertised source identifier and the configured target identifier, the pseudowire is not established.

Sample: VPWS Configuration with Multiple Interfaces and Sites

```
routing-instances {
  FEC129-VPWS {
    instance-type l2vpn;
    interface ge-0/0/1.0;
    interface ge-0/0/2.0;
    interface ge-0/0/3.0;
    route-distinguisher 10.255.0.1:200;
    l2vpn-id l2vpn-id:100:200;
    vrf-target target:100:200;
    protocols l2vpn {
```

```

    site CUSTOMER-1 {
        source-attachment-identifier 1;
        interface ge-0/0/1.0 {
            target-attachment-identifier 2;
        }
        interface ge-0/0/2.0 {
            target-attachment-identifier 3;
        }
    }
}

```

You can configure multiple interfaces within a site, because each SAIL-TAIL pair defines a unique pseudowire, as shown with pseudowires 1-2 and 1-3 in the sample configuration. Both the source and target access identifiers are 4-byte numbers and can only be configured in FEC 129 VPWS instances where the `instance-type` is `l2vpn` and the `l2vpn-id` configuration statement is present.

You can specify the source and target identifiers as plain unsigned integers in the range 1 through 4,292,967,295.

The Layer 2 circuit and Layer 2 VPN services allow many optional parameters to be included on a per-pseudowire basis. FEC 129 VPWS allows such parameters as MTU settings, community tagging, and inclusion of a control word, as shown in this sample configuration:

Sample: VPWS Configuration with Optional Configuration Parameters

```

routing-instances {
    FEC129-VPWS {
        instance-type l2vpn;
        interface ge-0/0/1.0;
        interface ge-0/0/2.0;
        interface ge-0/0/3.0;
        route-distinguisher 10.255.0.1:200;
        l2vpn-id l2vpn-id:100:200;
        vrf-target target:100:200;
        protocols l2vpn {
            site CUSTOMER-1 {
                source-attachment-identifier 1;
                community COMM;
                control-word ;
                encapsulation-type ethernet;
                ignore-encapsulation-mismatch;
            }
        }
    }
}

```



```

        ignore-mtu-mismatch;
        mtu 1500;
        no-control-word;
    interface ge-0/0/1.0 {
        target-attachment-identifier 2;
    }
    interface ge-0/0/2.0 {
        target-attachment-identifier 3;
        community COMM;
        control-word;
        encapsulation-type ethernet;
        ignore-encapsulation-mismatch;
        ignore-mtu-mismatch;
        mtu 1500;
        no-control-word;
    }
}
}
}
}
}

```

When configured within the site, the defined parameters affect any pseudowire originating from that site. When configured under an interface, the defined parameters affect that single specific pseudowire. This allows you to manipulate the parameters across all pseudowires associated with a particular local site in one place in the configuration.

Like other point-to-point services, the interfaces configured as members of the FEC 129 VPWS instance must be configured for CCC encapsulation and the CCC address family, as shown here:

```

interfaces {
    ge-0/0/1 {
        encapsulation ethernet-ccc;
        unit 0 {
            family ccc;
        }
    }
    ge-0/0/2 {
        encapsulation ethernet-ccc;
        unit 0 {
            family ccc;
        }
    }
}

```

```

ge-0/0/3 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}

```

You can use `vlan-ccc` instead of `ethernet-ccc`.

To support the basic FEC 129 VPWS functionality, the BGP sessions on the PE devices also need to be configured with the BGP `auto-discovery-only` address family to allow exchange of the autodiscovery routes. If traditional BGP VPLS or Layer 2 VPN service is also provisioned on the PE devices, the address family `l2vpn` signaling is also required, as shown here:

```

bgp {
    group pe {
        type internal;
        local-address 10.255.0.1;
        family l2vpn {
            auto-discovery-only;
            signaling;
        }
        neighbor 10.255.0.2;
        neighbor 10.255.0.3;
    }
}

```

The following configuration sample shows an FEC 129 VPWS routing instance with the operation, administration, and maintenance (OAM) (ping and BFD) configuration options:

Sample: VPWS Configuration with OAM

```

routing-instances {
    FEC129-VPWS {
        instance-type l2vpn;
        interface ge-0/0/1.0;
        route-distinguisher 10.255.0.1:200;
        l2vpn-id l2vpn-id:100:200;
        vrf-target target:100:200;
        protocols l2vpn {
            oam {

```

```

        ping-interval 600;
        bfd-liveness-detection {
            minimum-interval 200;
        }
    }
    site CUSTOMER {
        source-attachment-identifier 1;
        oam {
            ping-interval 600;
            bfd-liveness-detection {
                minimum-interval 200;
            }
        }
        interface ge-0/0/1.0 {
            oam {
                ping-interval 600;
                bfd-liveness-detection {
                    minimum-interval 200;
                }
            }
            target-attachment-identifier 2;
        }
    }
}
}
}
}
}

```


OAM options configured under protocols `l2vpn` apply to all sites and pseudowires in the routing instance. OAM options configured under a particular site apply to the pseudowires configured under that site. OAM options configured under a particular interface apply to the pseudowire configured under that interface.

Topology Diagram

[Figure 64 on page 897](#) shows the topology used in this example.

This example uses a simple topology with two PE devices and two customer edge (CE) devices.

Figure 64: Simple VPWS Topology



"CLI Quick Configuration" on page 897 shows the configuration for all of the devices in Figure 64 on page 897. The section "Step-by-Step Procedure" on page 899 describes the steps on Device PE1 and Device PE2.

Configuration

IN THIS SECTION

- CLI Quick Configuration | 897
- Procedure | 899

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device CE1

```
set interfaces ge-2/0/8 unit 0 description CE1_to_PE1
set interfaces ge-2/0/8 unit 0 family inet address 172.16.0.1/24
set interfaces lo0 unit 0 family inet address 192.0.2.5/24
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/8.0
```

Device CE2

```
set interfaces ge-2/1/6 unit 0 description CE2_to_PE2
set interfaces ge-2/1/6 unit 0 family inet address 172.16.0.4/24
set interfaces lo0 unit 0 family inet address 192.0.2.6/24
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/6.0
```

Device PE1

```
set interfaces ge-2/0/5 encapsulation ethernet-ccc
set interfaces ge-2/0/5 unit 0 description PE1_to_CE1
set interfaces ge-2/0/5 unit 0 family ccc
set interfaces fe-2/0/10 unit 0 description to_PE2
set interfaces fe-2/0/10 unit 0 family inet address 10.0.0.1/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.1/24
set protocols mpls interface fe-2/0/10.0
set protocols bgp local-address 192.0.2.1
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances FEC129-VPWS instance-type l2vpn
set routing-instances FEC129-VPWS interface ge-2/0/5.0
set routing-instances FEC129-VPWS route-distinguisher 192.0.2.1:100
set routing-instances FEC129-VPWS l2vpn-id l2vpn-id:100:100
set routing-instances FEC129-VPWS vrf-target target:100:100
set routing-instances FEC129-VPWS protocols l2vpn site ONE source-attachment-identifier 1
set routing-instances FEC129-VPWS protocols l2vpn site ONE interface ge-2/0/5.0 target-attachment-identifier 2
set routing-options autonomous-system 64510
```

Device PE2

```

set interfaces ge-2/1/7 encapsulation ethernet-ccc
set interfaces ge-2/1/7 unit 0 description PE2_to_CE2
set interfaces ge-2/1/7 unit 0 family ccc
set interfaces fe-2/0/10 unit 0 description to_PE1
set interfaces fe-2/0/10 unit 0 family inet address 10.0.0.2/30
set interfaces fe-2/0/10 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.2/24
set protocols mpls interface fe-2/0/10.0
set protocols bgp local-address 192.0.2.2
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.1
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface fe-2/0/10.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface fe-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances FEC129-VPWS instance-type l2vpn
set routing-instances FEC129-VPWS interface ge-2/1/7.0
set routing-instances FEC129-VPWS route-distinguisher 192.0.2.2:100
set routing-instances FEC129-VPWS l2vpn-id l2vpn-id:100:100
set routing-instances FEC129-VPWS vrf-target target:100:100
set routing-instances FEC129-VPWS protocols l2vpn site TWO source-attachment-identifier 2
set routing-instances FEC129-VPWS protocols l2vpn site TWO interface ge-2/1/7.0 target-
attachment-identifier 1
set routing-options autonomous-system 64510

```

Procedure

Step-by-Step Procedure

To configure a FEC 129 VPWS:

1. Configure the interfaces.

```

[edit interfaces]
user@PE1# set ge-2/0/5 encapsulation ethernet-ccc
user@PE1# set ge-2/0/5 unit 0 description PE1_to_CE1

```

```

user@PE1# set ge-2/0/5 unit 0 family ccc
user@PE1# set fe-2/0/10 unit 0 description to_PE2
user@PE1# set fe-2/0/10 unit 0 family inet address 10.0.0.1/30
user@PE1# set fe-2/0/10 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 192.0.2.1/24

```

2. Configure MPLS on the core-facing interface.

```

[edit protocols mpls]
user@PE1# set interface fe-2/0/10.0

```

3. Configure BGP.

```

[edit protocols bgp]
user@PE1# set local-address 192.0.2.1
user@PE1# set group pe-pe type internal
user@PE1# set group pe-pe family l2vpn auto-discovery-only
user@PE1# set group pe-pe family l2vpn signaling
user@PE1# set group pe-pe neighbor 192.0.2.2

```

4. Configure an interior gateway protocol, such as IS-IS or OSPF.

If you use OSPF, enable traffic engineering. Traffic engineering is supported by IS-IS by default.

```

[edit protocols ospf]
user@PE1# set traffic-engineering
user@PE1# set area 0.0.0.0 interface lo0.0 passive
user@PE1# set area 0.0.0.0 interface fe-2/0/10.0

```

5. Configure LDP on the core-facing interface and on the loopback interface.

```

[edit protocols ldp]
user@PE1# set interface fe-2/0/10.0
user@PE1# set interface lo0.0

```

6. Configure the VPWS routing instance.

LDP listens for routes from instance.l2vpn.0 for any instance configured for FEC 129 VPWS. These routes are identified by the `instance-type l2vpn` statement in the routing instance and the presence of the `l2vpn-id` statement.

Make sure that the `target-attachment-identifier` matches the `source-attachment-identifier` in the remote PE device's corresponding site. In this example, the pseudowire is established between Device PE1 and Device PE2. Device PE1 uses SAI 1 and TAI 2, while Device PE2 uses the opposite, SAI 2 and TAI 1.

```
[edit routing-instances FEC129-VPWS]
user@PE1# set instance-type l2vpn
user@PE1# set interface ge-2/0/5.0
user@PE1# set route-distinguisher 192.0.2.1:100
user@PE1# set l2vpn-id l2vpn-id:100:100
user@PE1# set vrf-target target:100:100
user@PE1# set protocols l2vpn site ONE source-attachment-identifier 1
user@PE1# set protocols l2vpn site ONE interface ge-2/0/5.0 target-attachment-identifier 2
```

7. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@PE1# set autonomous-system 64510
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@PE1# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show interfaces
ge-2/0/5 {
    encapsulation ethernet-ccc;
    unit 0 {
        description PE1_to_CE1;
```



```

        family ccc;
    }
}
fe-2/0/10 {
    unit 1 {
        description to_PE2;
        family inet {
            address 10.0.0.1/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}
}

```

```

user@PE1# show protocols
mpls {
    interface fe-2/0/10.0;
}
bgp {
    local-address 192.0.2.1;
    group pe-pe {
        type internal;
        family l2vpn {
            auto-discovery-only;
            inactive: signaling;
        }
        neighbor 192.0.2.2;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
    }
}

```

```

        interface fe-2/0/10.0;
    }
}
ldp {
    interface fe-2/0/10.0;
    interface lo0.0;
}

```

```

user@PE1# show routing-instances
FEC129-VPWS {
    instance-type l2vpn;
    interface ge-2/0/5.0;
    route-distinguisher 192.0.2.1:100;
    l2vpn-id l2vpn-id:100:100;
    vrf-target target:100:100;
    protocols {
        l2vpn {
            site ONE {
                source-attachment-identifier 1;
                interface ge-2/0/5.0 {
                    target-attachment-identifier 2;
                }
            }
        }
    }
}

```

```

user@PE1# show routing-options
autonomous-system 64510;

```

Verification

IN THIS SECTION

- [Verifying the Routes | 904](#)
- [Checking Connectivity Between the CE Devices | 906](#)
- [Checking the VPWS Connections | 906](#)

● Checking Connectivity Between the PE Devices | 908

Confirm that the configuration is working properly.

Verifying the Routes

Purpose

Verify that the expected routes are learned.

Action

From operational mode, enter the `show route` command.

```
user@PE1> show route
inet.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.1/24      *[Direct/0] 6d 21:16:32
                  > via lo0.0
192.0.2.2/24      *[OSPF/10] 6d 21:15:31, metric 1
                  > to 10.0.0.2 via fe-2/0/10.0
10.0.0.0/30       *[Direct/0] 6d 21:16:31
                  > via fe-2/0/10.0
10.0.0.1/32       *[Local/0] 6d 21:16:32
                  Local via fe-2/0/10.0
203.0.113.0/24    *[OSPF/10] 6d 21:16:34, metric 1
                  MultiRecv

inet.3: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2/24      *[LDP/9] 5d 22:25:19, metric 1
                  > to 10.0.0.2 via fe-2/0/10.0

mpls.0: 8 destinations, 8 routes (8 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both
```

```

0          *[MPLS/0] 6d 21:16:33, metric 1
          Receive
1          *[MPLS/0] 6d 21:16:33, metric 1
          Receive
2          *[MPLS/0] 6d 21:16:33, metric 1
          Receive
13         *[MPLS/0] 6d 21:16:33, metric 1
          Receive
299808     *[LDP/9] 5d 22:25:19, metric 1
          > to 10.0.0.2 via fe-2/0/10.0, Pop
299808(S=0) *[LDP/9] 5d 22:25:19, metric 1
          > to 10.0.0.2 via fe-2/0/10.0, Pop
299824     *[L2VPN/7] 5d 22:25:18
          > via ge-2/0/5.0, Pop
ge-2/0/5.0 *[L2VPN/7] 5d 22:13:02, metric2 1
          > to 10.0.0.2 via fe-2/0/10.0, Push 299872

bgp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2:100:0.0.0.2/96 AD
          *[BGP/170] 6d 20:51:23, localpref 100, from 192.0.2.2
          AS path: I, validation-state: unverified
          > to 10.0.0.2 via fe-2/0/10.0

ldp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2:NoCtrlWord:5:100:100:0.0.0.2:0.0.0.1/176
          *[LDP/9] 5d 22:13:02
          Discard

FEC129-VPWS.l2vpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.1:100:0.0.0.1/96 AD
          *[L2VPN/170] 6d 20:53:26, metric2 1
          Indirect
192.0.2.2:100:0.0.0.2/96 AD
          *[BGP/170] 6d 20:51:23, localpref 100, from 192.0.2.2
          AS path: I, validation-state: unverified
          > to 10.0.0.2 via fe-2/0/10.0
192.0.2.2:NoCtrlWord:5:100:100:0.0.0.1:0.0.0.2/176

```

```

          *[L2VPN/7] 6d 20:51:23, metric2 1
          > to 10.0.0.2 via fe-2/0/10.0
192.0.2.2:NoCtrlWord:5:100:100:0.0.0.2:0.0.0.1/176
          *[LDP/9] 5d 22:13:02
          Discard

```

Meaning

The output shows all the learned routes, including the autodiscovery (AD) routes.

Checking Connectivity Between the CE Devices

Purpose

Verify that Device CE1 can ping Device CE2.

Action

```

user@CE1> ping 192.0.2.6
PING 192.0.2.6 (192.0.2.6): 56 data bytes
64 bytes from 192.0.2.6: icmp_seq=0 ttl=64 time=0.679 ms
64 bytes from 192.0.2.6: icmp_seq=1 ttl=64 time=0.524 ms
^C
--- 192.0.2.6 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.524/0.602/0.679/0.078 ms

```

Meaning

The output shows that the VPWS is operational.

Checking the VPWS Connections

Purpose

Make sure that all of the FEC 129 VPWS connections come up correctly.

Action

```
user@PE1> show l2vpn connections
```

```
Layer-2 VPN connections:
```

```
Legend for connection status (St)
```

```
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch             MI -- Mesh-Group ID not available
BK -- Backup connection        ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch
```

```
Legend for interface status
```

```
Up -- operational
```

```
Dn -- down
```

```
Instance: FEC129-VPWS
```

```
L2vpn-id: 100:100
```

```
Local source-attachment-id: 1 (ONE)
```

Target-attachment-id	Type	St	Time last up	# Up trans
2	rmt	Up	Nov 28 16:16:14 2012	1

```
Remote PE: 192.0.2.2, Negotiated control-word: No
```

```
Incoming label: 299792, Outgoing label: 299792
```

```
Local interface: ge-2/0/5.0, Status: Up, Encapsulation: ETHERNET
```

Meaning

As expected, the connection is up. The output includes the source attachment ID and the target attachment ID.

Checking Connectivity Between the PE Devices

Purpose

Verify that Device PE1 can ping Device PE2. The `ping mpls l2vpn fec129` command accepts SAs and TAs as integers or IP addresses and also allows you to use the CE-facing interface instead of the other parameters (instance, local-id, remote-id, remote-pe-address).

Action

```
user@PE1> ping mpls l2vpn fec129 instance FEC129-VPWS remote-id 2 remote-pe-address 192.0.2.2
local-id 1
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

```
user@PE1> ping mpls l2vpn fec129 interface ge-2/0/5.0
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Meaning

The output shows that the VPWS is operational.

SEE ALSO

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

[Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

[Configuring the Local Site on PE Routers in Layer 2 VPNs | 149](#)

Example: Configuring BGP Autodiscovery for LDP VPLS

IN THIS SECTION

- [Requirements | 909](#)
- [Overview | 910](#)
- [Configuration | 912](#)
- [Verification | 933](#)

This example describes how to configure BGP autodiscovery for LDP VPLS, as specified in forwarding equivalency class (FEC) 129. FEC 129 uses BGP autodiscovery to convey endpoint information, so you do not need to manually configure pseudowires.

Requirements

This example uses the following hardware and software components:

- Four MX Series 5G Universal Routing Platforms
- Junos OS Release 10.4R2 or later

If you are using M Series or T Series routers, the PE routers must have either virtual loopback tunnel (vt) interfaces or label-switched interfaces (LSIs). On M Series and T Series routers, VPLS uses tunnel-based PICs to create virtual ports on vt interfaces. If you do not have a tunnel-based PIC installed on your M Series or T Series router, you can still configure VPLS by using LSIs to support the virtual ports. Use of LSIs requires Ethernet-based PICs installed in an Enhanced Flexible PIC Concentrator (FPC).

You do not need to use routers for the CE devices. For example, the CE devices can be EX Series Ethernet Switches.

Overview

IN THIS SECTION

- [Topology Diagram | 912](#)

All PE routers in a VPLS network operate like a large, distributed Ethernet switch to provide Layer 2 services to attached devices. This example shows a minimum configuration for PE routers and CE devices to create an autodiscovered VPLS network. The topology consists of five routers: two PE routers, two CE routers, and an optional route reflector (RR). The PE routers use BGP to autodiscover two different VPLS instances that are configured on both PE routers. Then the PE routers use LDP to automatically signal two pseudowires between the discovered end points. Finally, the PE routers bring up both VPLS instances for forwarding traffic. Each CE device is configured with two VLANs, with each VLAN belonging to different VPLS instances in the PE routers.

This example includes the following settings:

- **auto-discovery-only**—Allows the router to process only the autodiscovery network layer reachability information (NLRI) update messages for LDP-based Layer 2 VPN and VPLS update messages (BGP_L2VPN_AD_NLRI) (FEC 129). Specifically, the `auto-discovery-only` statement notifies the routing process (rpd) to expect autodiscovery-related NLRI messages so that information can be deciphered and used by LDP and VPLS. You can configure this statement at the global, group, and neighbor levels for BGP. The `auto-discovery-only` statement must be configured on all PE routers in the VPLS. If you configure route reflection, the `auto-discovery-only` statement is also required on P routers that act as the route reflector in supporting FEC 129-related updates.

The `signaling` statement is not included in this example but is discussed here for completeness. The `signaling` statement allows the router to process only the BGP_L2VPN_NLRIs used for BGP-based Layer 2 VPNs (FEC 128).

For interoperation scenarios in which a PE router must support both types of NLRI (FEC 128 and FEC 129), you can configure both the `signaling` statement and the `auto-discovery-only` statement. For example, a single PE router might need to process a combination of BGP-signaled virtual private wire service (VPWS) and LDP-signaled VPLS assisted by BGP autodiscovery. Configuring both the `signaling` statement and the `auto-discovery-only` statement together allows both types of signaling to run independently. The `signaling` statement is supported at the same hierarchy levels as the `auto-discovery-only` statement.

- **cluster**—Configuring a route reflector is optional for FEC 129 autodiscovered PE routers. In this example, the `cluster` statement configures Router RR to be a route reflector in the IBGP group. For

inbound updates, BGP autodiscovery NLRI messages are accepted if the router is configured to be a route reflector or if the `keep all` statement is configured in the IBGP group.

- `l2vpn-id`—Specifies a globally unique Layer 2 VPN community identifier for the instance. This statement is configurable for routing instances of type `vpls`.

You can configure the following formats for the community identifier:

- Autonomous system (AS) number format—`l2vpn-id: as-number: 2-byte-number`. For example: `l2vpn-id: 100:200`. The AS number can be in the range from 1 through 65,535.
- IPv4 format—`l2vpn-id: ip-address: 2-byte-number`. For example: `l2vpn-id: 10.1.1.1:2`.
- `vrf-target`—Defines the import and export route targets for the NLRI. You must either configure the `vrf-target` statement or the `vrf-import` and `vrf-export` statements to define the instance import and export policy or the import and export route targets for the NLRI. This example uses the `vrf-target` statement.
- `route-distinguisher`—Forms part of the BGP autodiscovery NLRI and distinguishes to which VPN or VPLS routing instance each route belongs. Each route distinguisher is a 6-byte value. You must configure a unique route distinguisher for each routing instance.

You can configure the following formats for the route distinguisher:

- AS number format—`as-number: 2-byte-number`
- IPv4 format—`ip-address: 2-byte-number`

Two notable statements are included in this example. These statements are important for interoperability with other vendors' equipment. The interoperability statements are not necessary for the topology that is used in this example, but they are included for completeness.


The interoperability statements are as follows:

- `input-vlan-map pop`—Removes an outer VLAN tag from the top of the VLAN tag stack.
- `output-vlan-map push`—Adds an outer VLAN tag in front of the existing VLAN tag.

Topology Diagram

Figure 65 on page 912 shows the topology used in this example.

Figure 65: BGP Autodiscovery for LDP VPLS



Configuration

IN THIS SECTION

- CLI Quick Configuration | 912
- Router PE1 | 916
- Device CE1 | 921
- Router PE2 | 923
- Device CE2 | 928
- Router RR | 930

CLI Quick Configuration

To quickly configure BGP autodiscovery for LDP VPLS, copy the following commands, remove any line breaks, and then paste the commands into the CLI of each device.

On Router PE1:

```
[edit]
set interfaces ge-0/1/0 vlan-tagging
set interfaces ge-0/1/0 encapsulation flexible-ethernet-services
set interfaces ge-0/1/0 unit 100 encapsulation vlan-vpls
set interfaces ge-0/1/0 unit 100 vlan-id 100
set interfaces ge-0/1/0 unit 100 input-vlan-map pop
set interfaces ge-0/1/0 unit 100 output-vlan-map push
set interfaces ge-0/1/0 unit 100 family vpls
set interfaces ge-0/1/0 unit 200 encapsulation vlan-vpls
set interfaces ge-0/1/0 unit 200 vlan-id 200
set interfaces ge-0/1/0 unit 200 family vpls
set interfaces ge-0/1/1 unit 0 description "PE1 to PE2"
set interfaces ge-0/1/1 unit 0 family inet address 192.0.2.4/24
set interfaces ge-0/1/1 unit 0 family iso
set interfaces ge-0/1/1 unit 0 family mpls
set interfaces ge-0/3/0 unit 0 description "PE1 to RR"
set interfaces ge-0/3/0 unit 0 family inet address 192.0.2.7/24
set interfaces ge-0/3/0 unit 0 family iso
set interfaces ge-0/3/0 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.8/24
set routing-options router-id 192.0.2.8
set routing-options autonomous-system 100
set protocols mpls interface lo0.0
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp group int type internal
set protocols bgp group int local-address 192.0.2.8
set protocols bgp group int family l2vpn auto-discovery-only
set protocols bgp group int neighbor 192.0.2.9
set protocols isis level 1 disable
set protocols isis interface all
set protocols isis interface fxp0.0 disable
set protocols isis interface lo0.0
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances vpls100 instance-type vpls
set routing-instances vpls100 interface ge-0/1/0.100
set routing-instances vpls100 route-distinguisher 192.0.2.8:100
set routing-instances vpls100 l2vpn-id l2vpn-id:100:100
```

```

set routing-instances vpls100 vrf-target target:100:100
set routing-instances vpls100 protocols vpls no-tunnel-services
set routing-instances vpls200 instance-type vpls
set routing-instances vpls200 interface ge-0/1/0.200
set routing-instances vpls200 route-distinguisher 192.0.2.8:200
set routing-instances vpls200 l2vpn-id l2vpn-id:100:200
set routing-instances vpls200 vrf-target target:100:208
set routing-instances vpls200 protocols vpls no-tunnel-services

```

On Device CE1:

```

[edit]
set interfaces ge-1/2/1 vlan-tagging
set interfaces ge-1/2/1 mtu 1400
set interfaces ge-1/2/1 unit 100 vlan-id 100
set interfaces ge-1/2/1 unit 100 family inet address 203.0.113.3/24
set interfaces ge-1/2/1 unit 200 vlan-id 200
set interfaces ge-1/2/1 unit 200 family inet address 203.0.113.2/24
set protocols ospf area 0.0.0.0 interface ge-1/2/1.100
set protocols ospf area 0.0.0.0 interface ge-1/2/1.200

```

On Router PE2:

```

[edit]
set interfaces ge-1/1/0 vlan-tagging
set interfaces ge-1/1/0 encapsulation flexible-ethernet-services
set interfaces ge-1/1/0 unit 100 encapsulation vlan-vpls
set interfaces ge-1/1/0 unit 100 vlan-id 100
set interfaces ge-1/1/0 unit 100 input-vlan-map pop
set interfaces ge-1/1/0 unit 100 output-vlan-map push
set interfaces ge-1/1/0 unit 100 family vpls
set interfaces ge-1/1/0 unit 200 encapsulation vlan-vpls
set interfaces ge-1/1/0 unit 200 vlan-id 200
set interfaces ge-1/1/0 unit 200 family vpls
set interfaces ge-1/2/1 unit 0 description "PE2 to PE1"
set interfaces ge-1/2/1 unit 0 family inet address 192.0.2.14/24
set interfaces ge-1/2/1 unit 0 family iso
set interfaces ge-1/2/1 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.10/24
set routing-options router-id 192.0.2.10
set routing-options autonomous-system 100

```

```

set protocols mpls interface lo0.0
set protocols mpls interface all
set protocols mpls interface fxp0.0 disable
set protocols bgp group int type internal
set protocols bgp group int local-address 192.0.2.10
set protocols bgp group int family l2vpn auto-discovery-only
set protocols bgp group int neighbor 192.0.2.9
set protocols isis level 1 disable
set protocols isis interface ge-1/2/1.0
set protocols isis interface lo0.0
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances vpls100 instance-type vpls
set routing-instances vpls100 interface ge-1/1/0.100
set routing-instances vpls100 route-distinguisher 192.0.2.10:100
set routing-instances vpls100 l2vpn-id l2vpn-id:100:100
set routing-instances vpls100 vrf-target target:100:100
set routing-instances vpls100 protocols vpls no-tunnel-services
set routing-instances vpls200 instance-type vpls
set routing-instances vpls200 interface ge-1/1/0.200
set routing-instances vpls200 route-distinguisher 192.0.2.10:200
set routing-instances vpls200 l2vpn-id l2vpn-id:100:200
set routing-instances vpls200 vrf-target target:100:208
set routing-instances vpls200 protocols vpls no-tunnel-services

```

On Device CE2:

```

[edit]
set interfaces ge-1/1/0 vlan-tagging
set interfaces ge-1/1/0 mtu 1400
set interfaces ge-1/1/0 unit 100 vlan-id 100
set interfaces ge-1/1/0 unit 100 family inet address 203.0.113.15/24
set interfaces ge-1/1/0 unit 200 vlan-id 200
set interfaces ge-1/1/0 unit 200 family inet address 203.0.113.16/24
set protocols ospf area 0.0.0.0 interface ge-1/1/0.100
set protocols ospf area 0.0.0.0 interface ge-1/1/0.200

```

On Router RR:

```
[edit]
set interfaces ge-1/3/2 unit 0 description "RR to PE1"
set interfaces ge-1/3/2 unit 0 family inet address 192.0.2.17/24
set interfaces ge-1/3/2 unit 0 family iso
set interfaces ge-1/3/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.9/24
set routing-options router-id 192.0.2.9
set routing-options autonomous-system 100
set protocols bgp group int type internal
set protocols bgp group int local-address 192.0.2.9
set protocols bgp group int family l2vpn auto-discovery-only
set protocols bgp group int cluster 198.51.100.0
set protocols bgp group int neighbor 192.0.2.8
set protocols bgp group int neighbor 192.0.2.10
set protocols isis level 1 disable
set protocols isis interface all
set protocols isis interface fxp0.0 disable
set protocols isis interface lo0.0
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
```

Router PE1

Step-by-Step Procedure

To configure Router PE1:

1. Configure the interfaces, the interface encapsulation, and the protocol families.

```
[edit]
user@PE1# edit interfaces
[edit interfaces]
user@PE1# set ge-0/1/0 encapsulation flexible-ethernet-services
user@PE1# set ge-0/1/0 unit 100 encapsulation vlan-vpls
user@PE1# set ge-0/1/0 unit 100 family vpls
user@PE1# set ge-0/1/0 unit 200 encapsulation vlan-vpls
user@PE1# set ge-0/1/0 unit 200 family vpls
user@PE1# set ge-0/1/1 unit 0 description "PE1 to PE2"
```

```

user@PE1# set ge-0/1/1 unit 0 family inet address 192.0.2.4/24
user@PE1# set ge-0/1/1 unit 0 family iso
user@PE1# set ge-0/1/1 unit 0 family mpls
user@PE1# set ge-0/3/0 unit 0 description "PE1 to RR"
user@PE1# set ge-0/3/0 unit 0 family inet address 192.0.2.7/24
user@PE1# set ge-0/3/0 unit 0 family iso
user@PE1# set ge-0/3/0 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 192.0.2.8/24

```

2. Configure the VLANs.

```

[edit interfaces]
user@PE1# set ge-0/1/0 vlan-tagging
user@PE1# set ge-0/1/0 unit 100 vlan-id 100
user@PE1# set ge-0/1/0 unit 100 input-vlan-map pop
user@PE1# set ge-0/1/0 unit 100 output-vlan-map push
user@PE1# set ge-0/1/0 unit 200 vlan-id 200
user@PE1# exit

```

3. Configure the protocol-independent properties.

We recommend that the router ID be the same as the local address. (See the `local-address` statement in Step "4" on page 917.)

```

[edit]
user@PE1# edit routing-options
[edit routing-options]
user@PE1# set router-id 192.0.2.8
user@PE1# set autonomous-system 100
user@PE1# exit

```

4. Configure IBGP, including the auto-discovery-only statement.

```

[edit]
user@PE1# edit protocols
[edit protocols]
user@PE1# set bgp group int type internal
user@PE1# set bgp group int local-address 192.0.2.8

```



```

user@PE1# set bgp group int family l2vpn auto-discovery-only
user@PE1# set bgp group int neighbor 192.0.2.9

```

5. Configure MPLS, LDP, and an IGP.

```

[edit protocols]
user@PE1# set mpls interface lo0.0
user@PE1# set mpls interface all
user@PE1# set mpls interface fxp0.0 disable
user@PE1# set isis level 1 disable
user@PE1# set isis interface all
user@PE1# set isis interface fxp0.0 disable
user@PE1# set isis interface lo0.0
user@PE1# set ldp interface all
user@PE1# set ldp interface fxp0.0 disable
user@PE1# set ldp interface lo0.0
user@PE1# exit

```

6. Configure the routing instances.

The `no-tunnel-services` statement is required if you are using LSI interfaces for VPLS instead of vt interfaces.

```

[edit]
user@PE1# edit routing-instances
[edit routing-instances]
user@PE1# set vpls100 instance-type vpls
user@PE1# set vpls100 interface ge-0/1/0.100
user@PE1# set vpls100 route-distinguisher 192.0.2.8:100
user@PE1# set vpls100 l2vpn-id l2vpn-id:100:100
user@PE1# set vpls100 vrf-target target:100:100
user@PE1# set vpls100 protocols vpls no-tunnel-services
user@PE1# set vpls200 instance-type vpls
user@PE1# set vpls200 interface ge-0/1/0.200
user@PE1# set vpls200 route-distinguisher 192.0.2.8:200
user@PE1# set vpls200 l2vpn-id l2vpn-id:100:200
user@PE1# set vpls200 vrf-target target:100:208
user@PE1# set vpls200 protocols vpls no-tunnel-services

```

7. If you are done configuring the device, commit the configuration.

```
[edit]
user@PE1# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show interfaces
ge-0/1/0 {
  vlan-tagging;
  encapsulation flexible-ethernet-services;
  unit 100 {
    encapsulation vlan-vpls;
    vlan-id 100;
    input-vlan-map pop;
    output-vlan-map push;
    family vpls;
  }
  unit 200 {
    encapsulation vlan-vpls;
    vlan-id 200;
    family vpls;
  }
}
ge-0/1/1 {
  unit 0 {
    description "PE1 to PE2";
    family inet {
      address 192.0.2.4/24;
    }
    family iso;
    family mpls;
  }
}
ge-0/3/0 {
  unit 0 {
```

```

        description "PE1 to RR";
        family inet {
            address 192.0.2.7/24;
        }
        family iso;
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.8/24;
        }
    }
}
}

```

```

user@PE1# show protocols
mpls {
    interface lo0.0;
    interface all;
    interface fxp0 disable;
}
bgp {
    group int {
        type internal;
        local-address 192.0.2.8;
        family l2vpn {
            auto-discovery-only;
        }
        neighbor 192.0.2.9;
    }
}
isis {
    level 1 disable;
    interface all;
    interface lo0.0;
    interface fxp0 disable;
}
ldp {
    interface lo0.0;
    interface all;
}

```

```

    interface fxp0 disable;
}

```

```

user@PE1# show routing-options
router-id 192.0.2.8;
autonomous-system 100;

```

```

user@PE1# show routing-instances
vpls100 {
    instance-type vpls;
    interface ge-0/1/0.100;
    route-distinguisher 192.0.2.8:100;
    l2vpn-id l2vpn-id:100:100;
    vrf-target target:100:100;
    protocols {
        vpls {
            no-tunnel-services;
        }
    }
}
vpls200 {
    instance-type vpls;
    interface ge-0/1/0.200;
    route-distinguisher 192.0.2.8:200;
    l2vpn-id l2vpn-id:100:200;
    vrf-target target:100:208;
    protocols {
        vpls {
            no-tunnel-services;
        }
    }
}

```

Device CE1

Step-by-Step Procedure

To configure Device CE1:

1. Configure interface addresses and the interface maximum transmission unit (MTU).

```
[edit]
user@CE1# edit interfaces
[edit interfaces]
user@CE1# set ge-1/2/1 mtu 1400
user@CE1# set ge-1/2/1 unit 100 family inet address 203.0.113.3/24
user@CE1# set ge-1/2/1 unit 200 family inet address 203.0.113.2/24
```

2. Configure VLANs.

```
[edit interfaces]
user@CE1# set ge-1/2/1 vlan-tagging
user@CE1# set ge-1/2/1 unit 100 vlan-id 100
user@CE1# set ge-1/2/1 unit 200 vlan-id 200
user@CE1# exit
```

3. Configure an IGP.

```
user@CE1# edit protocols
[edit protocols]
user@CE1# set ospf area 0.0.0.0 interface ge-1/2/1.100
user@CE1# set ospf area 0.0.0.0 interface ge-1/2/1.200
user@CE1# exit
```

4. If you are done configuring the device, commit the configuration.

```
[edit]
user@CE1# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces` and `show protocols` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@CE1# show interfaces
ge-1/2/1 {
```

```

vlan-tagging;
mtu 1400;
unit 100 {
    vlan-id 100;
    family inet {
        address 203.0.113.3/24;
    }
}
unit 200 {
    vlan-id 200;
    family inet {
        address 203.0.113.2/24;
    }
}
}

```

```

user@CE1# show protocols
ospf {
    area 0.0.0.0 {
        interface ge-1/2/1.100;
        interface ge-1/2/1.200;
    }
}

```

Router PE2

Step-by-Step Procedure

To configure Router PE2:

1. Configure the interfaces, the interface encapsulation, and the protocol families.

```

[edit]
user@PE2# edit interfaces
[edit interfaces]
user@PE2# set ge-1/1/0 encapsulation flexible-ethernet-services
user@PE2# set ge-1/1/0 unit 100 encapsulation vlan-vpls
user@PE2# set ge-1/1/0 unit 100 family vpls
user@PE2# set ge-1/1/0 unit 200 encapsulation vlan-vpls
user@PE2# set ge-1/1/0 unit 200 family vpls

```

```

user@PE2# set ge-1/2/1 unit 0 description "PE2 to PE1"
user@PE2# set ge-1/2/1 unit 0 family inet address 192.0.2.14/24
user@PE2# set ge-1/2/1 unit 0 family iso
user@PE2# set ge-1/2/1 unit 0 family mpls
user@PE2# set lo0 unit 0 family inet address 192.0.2.10/24

```

2. Configure the VLANs.

```

[edit interfaces]
user@PE2# set ge-1/1/0 vlan-tagging
user@PE2# set ge-1/1/0 unit 100 vlan-id 100
user@PE2# set ge-1/1/0 unit 100 input-vlan-map pop
user@PE2# set ge-1/1/0 unit 100 output-vlan-map push
user@PE2# set ge-1/1/0 unit 200 vlan-id 200
user@PE2# exit

```

3. Configure the protocols-independent properties.

We recommend that the router ID be the same as the local address. (See the `local-address` statement in Step "4" on page 924.)

```

[edit]
user@PE2# edit routing-options
[edit routing-options]
user@PE2# set router-id 192.0.2.10
user@PE2# set autonomous-system 100

```

4. Configure IBGP, including the auto-discovery-only statement.

```

[edit]
user@PE2# edit protocols
[edit protocols]
user@PE2# set bgp group int type internal
user@PE2# set bgp group int local-address 192.0.2.10
user@PE2# set bgp group int family l2vpn auto-discovery-only
user@PE2# set bgp group int neighbor 192.0.2.9

```

5. Configure MPLS, LDP, and an IGP.

```
[edit protocols]
user@PE2# set mpls interface lo0.0
user@PE2# set mpls interface all
user@PE2# set mpls interface fxp0.0 disable
user@PE2# set isis level 1 disable
user@PE2# set isis interface ge-1/2/1.0
user@PE2# set isis interface lo0.0
user@PE2# set ldp interface all
user@PE2# set ldp interface fxp0.0 disable
user@PE2# set ldp interface lo0.0
user@PE2# exit
```

6. Configure the routing instances.

The `no-tunnel-services` statement is required if you are using LSI interfaces for VPLS instead of vt interfaces.

```
[edit]
user@PE2# edit routing-instances
[edit routing-instances]
user@PE2# set vpls100 instance-type vpls
user@PE2# set vpls100 interface ge-1/1/0.100
user@PE2# set vpls100 route-distinguisher 192.0.2.10:100
user@PE2# set vpls100 l2vpn-id l2vpn-id:100:100
user@PE2# set vpls100 vrf-target target:100:100
user@PE2# set vpls100 protocols vpls no-tunnel-services
user@PE2# set vpls200 instance-type vpls
user@PE2# set vpls200 interface ge-1/1/0.200
user@PE2# set vpls200 route-distinguisher 192.0.2.10:200
user@PE2# set vpls200 l2vpn-id l2vpn-id:100:200
user@PE2# set vpls200 vrf-target target:100:200
user@PE2# set vpls200 protocols vpls no-tunnel-services
```

7. If you are done configuring the device, commit the configuration.

```
[edit]
user@PE2# commit
```


Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE2# show interfaces
ge-1/1/0 {
  vlan-tagging;
  encapsulation flexible-ethernet-services;
  unit 100 {
    encapsulation vlan-vpls;
    vlan-id 100;
    input-vlan-map pop;
    output-vlan-map push;
    family vpls;
  }
  unit 200 {
    encapsulation vlan-vpls;
    vlan-id 200;
    family vpls;
  }
}
ge-1/2/1 {
  unit 0 {
    description "PE2 to PE1";
    family inet {
      address 192.0.2.14/24;
    }
    family iso;
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.10/24;
    }
  }
}
```

```

    }
}

```

```

user@PE2# show protocols
mpls {
    interface lo0.0;
    interface all;
    interface fxp0 disable;
}
bgp {
    group int {
        type internal;
        local-address 192.0.2.10;
        family l2vpn {
            auto-discovery-only;
        }
        neighbor 192.0.2.9;
    }
}
isis {
    level 1 disable;
    interface ge-1/2/1.0;
    interface lo0.0;
}
ldp {
    interface lo0.0;
    interface all;
    interface fxp0 disable;
}

```

```

user@PE2# show routing-options
router-id 192.0.2.10;
autonomous-system 100;

```

```

user@PE2# show routing-instances
vpls100 {
    instance-type vpls;
    interface ge-1/1/0.100;
    route-distinguisher 192.0.2.10:100;
}

```

```

l2vpn-id l2vpn-id:100:100;
vrf-target target:100:100;
protocols {
    vpls {
        no-tunnel-services;
    }
}
}
vpls200 {
    instance-type vpls;
    interface ge-1/1/0.200;
    route-distinguisher 192.0.2.10:200;
    l2vpn-id l2vpn-id:100:200;
    vrf-target target:100:200;
    protocols {
        vpls {
            no-tunnel-services;
        }
    }
}
}

```

Device CE2

Step-by-Step Procedure

To configure Device CE2:

1. Configure VLAN interfaces.

```

[edit]
user@CE2# edit interfaces ge-1/1/0
[edit interfaces ge-1/1/0]
user@CE2# set vlan-tagging
user@CE2# set mtu 1400
user@CE2# set unit 100 vlan-id 100
user@CE2# set unit 100 family inet address 203.0.113.15/24
user@CE2# set unit 200 vlan-id 200
user@CE2# set unit 200 family inet address 203.0.113.16/24
user@CE2# exit

```

2. Configure OSPF on the interfaces.

```
[edit]
user@CE2# edit protocols ospf area 0.0.0.0
[edit protocols ospf area 0.0.0.0]
user@CE2# set interface ge-1/1/0.100
user@CE2# set interface ge-1/1/0.200
user@CE2# exit
```

3. If you are done configuring the device, commit the configuration.

```
[edit]
user@CE2# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces` and `show protocols` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@CE2# show interfaces
ge-1/1/0 {
  vlan-tagging;
  mtu 1400;
  unit 100 {
    vlan-id 100;
    family inet {
      address 203.0.113.15/24;
    }
  }
  unit 200 {
    vlan-id 200;
    family inet {
      address 203.0.113.16/24;
    }
  }
}
```

```

    }
}

```

```

user@CE2# show protocols
ospf {
  area 0.0.0.0 {
    interface ge-1/1/0.100;
    interface ge-1/1/0.200;
  }
}

```

Router RR

Step-by-Step Procedure

To configure Router RR:

1. Configure interface addresses and the protocol families.

```

[edit]
user@RR# edit interfaces
[edit interfaces]
user@RR# set ge-1/3/2 unit 0 description "RR to PE1"
user@RR# set ge-1/3/2 unit 0 family inet address 192.0.2.17/24
user@RR# set ge-1/3/2 unit 0 family iso
user@RR# set ge-1/3/2 unit 0 family mpls
user@RR# set lo0 unit 0 family inet address 192.0.2.9/24
user@RR# exit

```

2. Configure the autonomous systems and the router ID.

```

[edit]
user@RR# edit routing-options
[edit routing-options]
user@RR# set autonomous-system 100
user@RR# set router-id 192.0.2.9
user@RR# exit

```

3. Configure BGP and set this router to be the route reflector. Route reflection is optional for FEC 129.

```
[edit]
user@RR# edit protocols bgp group int
[edit protocols bgp group int]
user@RR# set type internal
user@RR# set local-address 192.0.2.9
user@RR# set family l2vpn auto-discovery-only
user@RR# set cluster 198.51.100.0
user@RR# set neighbor 192.0.2.8
user@RR# set neighbor 192.0.2.10
user@RR# exit
```

4. Configure IS-IS for the IGP.

```
[edit]
user@RR# edit protocols isis
[edit protocols isis]
user@RR# set level 1 disable
user@RR# set interface all
user@RR# set interface fxp0.0 disable
user@RR# set interface lo0.0
user@RR# exit
```

5. Configure LDP for the MPLS signaling protocol.

```
[edit]
user@RR# edit protocols ldp
[edit protocols ldp]
user@RR# set interface all
user@RR# set interface fxp0.0 disable
user@RR# set interface lo0.0
user@RR# exit
```

6. If you are done configuring the device, commit the configuration.

```
[edit]
user@RR# commit
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@RR# show interfaces
ge-1/3/2 {
  unit 0 {
    description "RR to PE1";
    family inet {
      address 192.0.2.17/24;
    }
    family iso;
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.9/24;;
    }
  }
}
```

```
user@RR# show protocols
bgp {
  group int {
    type internal;
    local-address 192.0.2.9;
    family l2vpn {
      auto-discovery-only;
    }
    cluster 198.51.100.0;
    neighbor 192.0.2.8;
    neighbor 192.0.2.10;
  }
}
isis {
  level 1 disable;
  interface lo0.0;
```

```

    interface all;
    interface fxp0 disable;
}
ldp {
    interface lo0.0;
    interface all;
    interface fxp0 disable;
}

```

```

user@RR# show routing-options
router-id 192.0.2.9;
autonomous-system 100;

```

Verification

To verify the operation, use the following commands:

- `show route extensive`
- `show route advertising-protocol bgp neighbor`
- `show route receive-protocol bgp neighbor`
- `show route table bgp.l2vpn.0`
- `show route table vpls100.l2vpn.0`
- `show route table vpls200.l2vpn.0`
- `show vpls connections extensive`
- `show vpls mac-table detail`
- `show vpls statistics`

AD in the routing table output indicates autodiscovery NLRI.

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)
[Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS | 629](#)

Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups

IN THIS SECTION

- Requirements | 934
- Overview | 934
- Configuration | 935
- Verification | 943

This example describes how to configure user-defined mesh groups for BGP autodiscovery for LDP VPLS, as specified in forwarding equivalency class (FEC) 129. FEC 129 uses BGP autodiscovery to convey endpoint information, so you do not need to manually configure pseudowires. You configure mesh groups on the border router to group the sets of PE routers that are automatically fully meshed and that share the same signaling protocol, either BGP or LDP. You can configure multiple mesh groups to map each fully meshed LDP-signaled or BGP-signaled VPLS domain to a mesh group.

Requirements

Before you begin, configure BGP autodiscovery for LDP VPLS. See ["Example: Configuring BGP Autodiscovery for LDP VPLS" on page 909](#).

The hardware and software requirements for this example are the same as the requirements for the *Example: Configuring BGP Autodiscovery for LDP VPLS*. You will need to adapt the example configuration to the topology used in this example.

Overview

IN THIS SECTION

- Topology Diagram | 935

Configuration for a mesh group for FEC 129 is very similar to the mesh-group configuration for FEC 128.


Note the following differences for FEC 129:

- Each user-defined mesh group must have a unique route distinguisher. Do not use the route distinguisher that is defined for the default mesh group at the [edit routing-instances] hierarchy level.
- Each user-defined mesh group must have its own import and export route target.
- Each user-defined mesh group can have a unique Layer 2 VPN ID. By default, all the mesh groups that are configured for a VPLS routing instance use the same Layer 2 VPN ID as the one that you configure at the [edit routing-instances] hierarchy level.

Topology Diagram

Figure 66 on page 935 shows a topology that includes a user-defined mesh group.

Figure 66: BGP Autodiscovery for LDP VPLS with a User-Defined Mesh Group



Configuration

IN THIS SECTION

- [CLI Quick Configuration | 935](#)
- [Procedure | 938](#)

CLI Quick Configuration

To quickly configure a mesh group, copy the following commands, remove any line breaks, and then paste the commands into the CLI of each device.

Device CE1

```
set interfaces ge-2/0/8 unit 0 family inet address 172.16.0.1/24
set interfaces lo0 unit 0 family inet address 10.255.14.214/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/8.0
```

Device CE3

```
set interfaces ge-2/0/9 unit 0 family inet address 172.16.0.3/24
set interfaces lo0 unit 0 family inet address 10.255.14.218/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/9.0
```

Device CE4

```
set interfaces ge-2/1/6 unit 0 family inet address 172.16.0.4/24
set interfaces lo0 unit 0 family inet address 10.255.14.219/32
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/1/6.0
```

Device R2

```
set interfaces ge-2/0/5 encapsulation ethernet-vpls
set interfaces ge-2/0/5 unit 0 description to_CE1
set interfaces ge-2/0/5 unit 0 family vpls
set interfaces ge-2/0/10 unit 0 description to_R3
set interfaces ge-2/0/10 unit 0 family inet address 10.10.4.2/30
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces ge-2/0/11 unit 0 description to_R4
set interfaces ge-2/0/11 unit 0 family inet address 10.10.5.1/30
set interfaces ge-2/0/11 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.2/24
set protocols mpls interface ge-2/0/10.0
set protocols mpls interface ge-2/0/11.0
set protocols bgp local-address 192.0.2.2
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe connect-retry-interval 1
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
```

```

set protocols bgp group pe-pe neighbor 192.0.2.3
set protocols bgp group pe-pe neighbor 192.0.2.4
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface ge-2/0/10.0
set protocols ospf area 0.0.0.0 interface ge-2/0/11.0
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface ge-2/0/11.0
set protocols ldp interface lo0.0
set routing-instances inst512 instance-type vpls
set routing-instances inst512 interface ge-2/0/5.0
set routing-instances inst512 route-distinguisher 100:100
set routing-instances inst512 l2vpn-id l2vpn-id:1:2
set routing-instances inst512 vrf-target target:1:1
set routing-instances inst512 protocols vpls mesh-group metro1 vrf-target target:2:1
set routing-instances inst512 protocols vpls mesh-group metro1 route-distinguisher 100:200
set routing-options autonomous-system 64510

```

Device R3

```

set interfaces ge-2/0/10 unit 0 description to_R2
set interfaces ge-2/0/10 unit 0 family inet address 10.10.4.1/30
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces ge-2/1/3 encapsulation ethernet-vpls
set interfaces ge-2/1/3 unit 0 description to_CE2
set interfaces ge-2/1/3 unit 0 family vpls
set interfaces lo0 unit 0 family inet address 192.0.2.3/24
set protocols mpls interface ge-2/0/10.0
set protocols bgp local-address 192.0.2.3
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe connect-retry-interval 1
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols bgp group pe-pe neighbor 192.0.2.4
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-2/0/10.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances inst512 instance-type vpls
set routing-instances inst512 interface ge-2/1/3.0

```

```

set routing-instances inst512 route-distinguisher 100:100
set routing-instances inst512 l2vpn-id l2vpn-id:1:2
set routing-instances inst512 vrf-target target:1:1
set routing-instances inst512 protocols vpls
set routing-options autonomous-system 64510

```

Device R4

```

set interfaces ge-2/0/10 unit 0 description to_R2
set interfaces ge-2/0/10 unit 0 family inet address 10.10.5.2/30
set interfaces ge-2/0/10 unit 0 family mpls
set interfaces ge-2/1/7 encapsulation ethernet-vpls
set interfaces ge-2/1/7 unit 0 description to_CE3
set interfaces ge-2/1/7 unit 0 family vpls
set interfaces lo0 unit 0 family inet address 192.0.2.4/24
set protocols mpls interface ge-2/0/10.0
set protocols bgp local-address 192.0.2.4
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe connect-retry-interval 1
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols bgp group pe-pe neighbor 192.0.2.3
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-2/0/10.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ldp interface ge-2/0/10.0
set protocols ldp interface lo0.0
set routing-instances inst512 instance-type vpls
set routing-instances inst512 interface ge-2/1/7.0
set routing-instances inst512 route-distinguisher 100:100
set routing-instances inst512 l2vpn-id l2vpn-id:1:2
set routing-instances inst512 vrf-target target:1:1
set routing-instances inst512 protocols vpls
set routing-options autonomous-system 64510

```

Procedure

Step-by-Step Procedure

To configure a mesh group:

1. Configure the interfaces.

```
[edit interfaces]
user@R2# set ge-2/0/5 encapsulation ethernet-vpls
user@R2# set ge-2/0/5 unit 0 description to_CE1
user@R2# set ge-2/0/5 unit 0 family vpls
user@R2# set ge-2/0/10 unit 0 description to_R3
user@R2# set ge-2/0/10 unit 0 family inet address 10.10.4.2/30
user@R2# set ge-2/0/10 unit 0 family mpls
user@R2# set ge-2/0/11 unit 0 description to_R4
user@R2# set ge-2/0/11 unit 0 family inet address 10.10.5.1/30
user@R2# set ge-2/0/11 unit 0 family mpls
user@R2# set lo0 unit 0 family inet address 192.0.2.2/24
```

2. Configure MPLS on the interfaces.

```
[edit protocols mpls]
user@R2# set interface ge-2/0/10.0
user@R2# set interface ge-2/0/11.0
```

3. Configure BGP.

```
[edit protocols bgp]
user@R2# set local-address 192.0.2.2
[edit protocols bgp group pe-pe]
user@R2# set type internal
user@R2# set connect-retry-interval 1
user@R2# set family l2vpn auto-discovery-only
user@R2# set family l2vpn signaling
user@R2# set neighbor 192.0.2.3
user@R2# set neighbor 192.0.2.4
```

4. Set the import and export route target for the default mesh group.

```
[edit protocols ospf]
user@R2# set traffic-engineering
user@R2# set area 0.0.0.0 interface lo0.0 passive
```

```
user@R2# set area 0.0.0.0 interface ge-2/0/10.0
user@R2# set area 0.0.0.0 interface ge-2/0/11.0
```

5. Configure LDP on the core-facing interfaces and on the loopback interface.

```
[edit protocols ldp]
user@R2# set interface ge-2/0/10.0
user@R2# set interface ge-2/0/11.0
user@R2# set interface lo0.0
```

6. Configure the VPLS routing instance.

Make sure that the route distinguisher in the mesh group is unique.

```
[edit routing-instances inst512]
user@R2# set instance-type vpls
user@R2# set interface ge-2/0/5.0
user@R2# set route-distinguisher 100:100
user@R2# set l2vpn-id l2vpn-id:1:2
user@R2# set vrf-target target:1:1
user@R2# set protocols vpls mesh-group metro1 vrf-target target:2:1
user@R2# set protocols vpls mesh-group metro1 route-distinguisher 100:200
```

7. Configure the autonomous system (AS) number.

```
[edit routing-options]
user@R2# set autonomous-system 64510
```

8. If you are done configuring the device, commit the configuration.

```
[edit]
user@R2# commit
```

Results

From configuration mode, confirm your configuration by entering the `show routing-instances` command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@R2# show interfaces
ge-2/0/5 {
  encapsulation ethernet-vpls;
  unit 0 {
    description PE1_to_CE1;
    family vpls;
  }
}
ge-2/0/10 {
  unit 0 {
    description to_R3;
    family inet {
      address 10.10.4.2/30;
    }
    family mpls;
  }
}
ge-2/0/11 {
  unit 0 {
    description to_R4;
    family inet {
      address 10.10.5.1/30;
    }
    family mpls;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.2/24;
    }
  }
}
```



```

    }
}

```

```

user@R2# show protocols
mpls {
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
}
bgp {
    local-address 192.0.2.2;
    group pe-pe {
        type internal;
        connect-retry-interval 1;
        family l2vpn {
            auto-discovery-only;
            signaling;
        }
        neighbor 192.0.2.3;
        neighbor 192.0.2.4;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
        interface ge-2/0/10.0;
        interface ge-2/0/11.0;
    }
}
ldp {
    interface ge-2/0/10.0;
    interface ge-2/0/11.0;
    interface lo0.0;
}

```

```

user@R2# show routing-instances
inst512 {
    instance-type vpls;
}

```

```
interface ge-2/0/5.0;
route-distinguisher 100:100;
l2vpn-id l2vpn-id:1:2;
vrf-target target:1:1;
protocols {
  vpls {
    mesh-group metro1 {
      vrf-target target:2:1;
      route-distinguisher 100:200;
    }
  }
}
```

```
user@R2# show routing-options
autonomous-system 64510;
```

Verification

IN THIS SECTION

- [Verifying the Routes | 943](#)
- [Checking Connectivity | 946](#)
- [Checking the VPLS Connections | 947](#)
- [Display Learned VPLS MAC Address Information | 948](#)

Confirm that the configuration is working properly.

Verifying the Routes

Purpose

Verify that the expected routes are learned.

Action

From operational mode, enter the `show route` command.

```

user@R2> show route
inet.0: 9 destinations, 9 routes (9 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2/24      *[Direct/0] 4d 02:42:47
                  > via lo0.0
192.0.2.3/24      *[OSPF/10] 4d 02:41:56, metric 1
                  > to 10.10.4.1 via ge-2/0/10.0
192.0.2.4/24      *[OSPF/10] 4d 02:42:01, metric 1
                  > to 10.10.5.2 via ge-2/0/11.0
10.10.3.2/24      *[Local/0] 4d 02:42:47
                  Reject
10.10.4.0/30      *[Direct/0] 4d 02:42:46
                  > via ge-2/0/10.0
10.10.4.2/32      *[Local/0] 4d 02:42:47
                  Local via ge-2/0/10.0
10.10.5.0/30      *[Direct/0] 4d 02:42:46
                  > via ge-2/0/11.0
10.10.5.1/32      *[Local/0] 4d 02:42:47
                  Local via ge-2/0/11.0
203.0.113.0/24    *[OSPF/10] 4d 02:42:49, metric 1
                  MultiRecv

inet.3: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3/24      *[LDP/9] 4d 02:01:06, metric 1
                  > to 10.10.4.1 via ge-2/0/10.0
192.0.2.4/24      *[LDP/9] 4d 02:01:06, metric 1
                  > to 10.10.5.2 via ge-2/0/11.0

mpls.0: 12 destinations, 12 routes (12 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0                *[MPLS/0] 4d 02:42:49, metric 1
                  Receive
1                *[MPLS/0] 4d 02:42:49, metric 1
                  Receive

```

```

2          *[MPLS/0] 4d 02:42:49, metric 1
          Receive
13         *[MPLS/0] 4d 02:42:49, metric 1
          Receive
299776     *[LDP/9] 4d 02:01:06, metric 1
          > to 10.10.5.2 via ge-2/0/11.0, Pop
299776(S=0) *[LDP/9] 4d 02:01:06, metric 1
          > to 10.10.5.2 via ge-2/0/11.0, Pop
299792     *[LDP/9] 4d 02:01:06, metric 1
          > to 10.10.4.1 via ge-2/0/10.0, Pop
299792(S=0) *[LDP/9] 4d 02:01:06, metric 1
          > to 10.10.4.1 via ge-2/0/10.0, Pop
800000     *[VPLS/7] 4d 02:01:05
          > via vt-2/0/10.185597952, Pop
800001     *[VPLS/7] 4d 02:01:05
          > via vt-2/0/10.185597953, Pop
vt-2/0/10.185597953*[VPLS/7] 4d 02:01:05, metric2 1
          > to 10.10.5.2 via ge-2/0/11.0, Push 800001
vt-2/0/10.185597952*[VPLS/7] 4d 02:01:05, metric2 1
          > to 10.10.4.1 via ge-2/0/10.0, Push 800001

```

bgp.12vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)

+ = Active Route, - = Last Active, * = Both

100:100:192.0.2.3/96 **AD**

```

*[BGP/170] 4d 02:32:41, localpref 100, from 192.0.2.3
  AS path: I, validation-state: unverified
  > to 10.10.4.1 via ge-2/0/10.0

```

100:100:192.0.2.4/96 **AD**

```

*[BGP/170] 4d 02:32:41, localpref 100, from 192.0.2.4
  AS path: I, validation-state: unverified
  > to 10.10.5.2 via ge-2/0/11.0

```

inst512.12vpn.0: 8 destinations, 8 routes (8 active, 0 holddown, 0 hidden)

+ = Active Route, - = Last Active, * = Both

100:100:192.0.2.2/96 **AD**

```

*[VPLS/170] 4d 02:01:05, metric2 1
  Indirect

```

100:100:192.0.2.3/96 **AD**

```

*[BGP/170] 4d 02:32:41, localpref 100, from 192.0.2.3
  AS path: I, validation-state: unverified
  > to 10.10.4.1 via ge-2/0/10.0

```

```

100:100:192.0.2.4/96 AD
    *[BGP/170] 4d 02:32:41, localpref 100, from 192.0.2.4
    AS path: I, validation-state: unverified
    > to 10.10.5.2 via ge-2/0/11.0
100:200:192.0.2.2/96 AD
    *[VPLS/170] 4d 02:01:05, metric2 1
    Indirect
192.0.2.3:NoCtrlWord:5:1:2:192.0.2.2:192.0.2.3/176
    *[VPLS/7] 4d 02:01:05, metric2 1
    > to 10.10.4.1 via ge-2/0/10.0
192.0.2.3:NoCtrlWord:5:1:2:192.0.2.3:192.0.2.2/176
    *[LDP/9] 4d 02:01:05
    Discard
192.0.2.4:NoCtrlWord:5:1:2:192.0.2.2:192.0.2.4/176
    *[VPLS/7] 4d 02:01:05, metric2 1
    > to 10.10.5.2 via ge-2/0/11.0
192.0.2.4:NoCtrlWord:5:1:2:192.0.2.4:192.0.2.2/176
    *[LDP/9] 4d 02:01:05
    Discard

ldp.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.3:NoCtrlWord:5:1:2:192.0.2.3:192.0.2.2/176
    *[LDP/9] 4d 02:01:05
    Discard
192.0.2.4:NoCtrlWord:5:1:2:192.0.2.4:192.0.2.2/176
    *[LDP/9] 4d 02:01:05
    Discard

```

Meaning

The output shows all the learned routes, including the autodiscovered (AD) routes.

Checking Connectivity

Purpose

Verify that Device CE1 can ping Device CE2 and Device CE3.

Action

```
user@CE1> ping 10.255.14.218
PING 10.255.14.218 (10.255.14.218): 56 data bytes
64 bytes from 10.255.14.218: icmp_seq=0 ttl=64 time=0.787 ms
64 bytes from 10.255.14.218: icmp_seq=1 ttl=64 time=0.651 ms
^C
--- 10.255.14.218 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.651/0.719/0.787/0.068 ms
```

```
user@CE1> ping 10.255.14.219
PING 10.255.14.219 (10.255.14.219): 56 data bytes
64 bytes from 10.255.14.219: icmp_seq=0 ttl=64 time=1.054 ms
64 bytes from 10.255.14.219: icmp_seq=1 ttl=64 time=0.669 ms
^C
--- 10.255.14.219 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.669/0.862/1.054/0.193 ms
```

Meaning

The output shows that VPLS is operational.

Checking the VPLS Connections

Purpose

Make sure that all of the FEC 129 VPLS connections come up correctly.

Action

```
user@R2> show vpls connections
Instance: inst512
  L2vpn-id: 1:2
  Local-id: 192.0.2.2
  Mesh-group connections: __ves__
    Remote-id      Type  St    Time last up      # Up trans
    192.0.2.4      rmt  Up    Oct 26 15:11:56 2012      1
```

```

Remote PE: 192.0.2.4, Negotiated control-word: No
Incoming label: 800001, Outgoing label: 800001
Local interface: vt-2/0/10.185597953, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls inst512 local-id 192.0.2.2 remote-id 192.0.2.4 neighbor
192.0.2.4
192.0.2.3          rmt   Up    Oct 26 15:11:56 2012      1
Remote PE: 192.0.2.3, Negotiated control-word: No
Incoming label: 800000, Outgoing label: 800001
Local interface: vt-2/0/10.185597952, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls inst512 local-id 192.0.2.2 remote-id 192.0.2.3 neighbor
192.0.2.3

```

Meaning

As expected, the connections are up.

Display Learned VPLS MAC Address Information

Purpose

Verify that all CE devices' MAC addresses are learned and installed.

Action

```
user@R2> show vpls mac-table
```

MAC flags (S -static MAC, D -dynamic MAC, L -locally learned, C -Control MAC
SE -Statistics enabled, NM -Non configured MAC, R -Remote PE MAC)

Logical system : R2

Routing instance : inst512

Bridging domain : __inst512__, VLAN : NA

MAC address	MAC flags	Logical interface	NH Index	RTR ID
00:21:59:0f:35:32	D	ge-2/0/5.0		
00:21:59:0f:35:33	D	vt-2/0/10.185597952		
00:21:59:0f:35:d5	D	vt-2/0/10.185597953		

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS | 629](#)

VPLS Multihoming Reactions to Network Failures

VPLS multihoming is designed to protect customer sites from a loss of network connectivity in the event of the following types of network failures:

- Link failure between the CE device and the PE router—BGP on the PE router is notified when the link goes down. BGP sets the circuit status vector bit in the MP_REACH_NLRI to indicate that the circuit is down.

If all of the VPLS local attachment circuits are down, then BGP modifies the down bit in the VPLS advertisement Layer2-Extended-Community to indicate that the customer site is down. When the bit is modified, BGP advertises the route to all of the remote PE routers to notify them that the circuit (and site) is down. Each of the remote PE routers run the BGP and VPLS path selection procedures again and reroute the VPLS pseudowires as needed.

- MPLS connectivity failure to the remote PE router—On the multihomed PE router, BGP discovers that MPLS cannot connect to the BGP next hop in the service provider's network. BGP modifies the circuit status vector bit in the MP_REACH_NLRI to indicate that the LSP is down. Once the bit is modified, BGP readvertises the route to all of the remote PE routers to notify them that connectivity from the local site to the remote site is down.

The remote PE routers each run the BGP and VPLS path selection procedures again. With the LSP to the original multihomed PE router down, the remote PE routers designate the backup multihomed PE router as the VE device for the multihomed customer site. The pseudowires to and from the remote PE routers are then rerouted to the backup multihomed PE router.

- PE router failure—When either the multihomed PE router or the BGP process running on it fails, the remote PE routers detect the expiration of the holdtimer, bring down their peering sessions, and delete the Layer 2 advertisements from that multihomed PE router. The remote PE routers each run the BGP and VPLS path selection procedures again and reroute their pseudowires to the backup multihomed PE router.

Alternatively, the remote PE routers could discover that the BGP next hop, represented by the failed multihomed PE router, is unreachable. For this case, the remote PE routers mark the Layer 2 routes advertised by the multihomed PE router as unreachable. The remote PE routers each run the BGP and VPLS path selection procedures again and reroute their pseudowires to the backup multihomed PE router.

The remote PE routers behave in the same manner if you reconfigure the local preference attribute of the primary multihomed PE router (effectively performing an administrative failover to the backup multihomed PE router). On the primary multihomed PE router, BGP advertises a Layer 2 update with the new local preference attribute to all of the remote PE routers. The remote PE routers each run the BGP and VPLS path selection procedures again and reroute their pseudowires to the backup multihomed PE router.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Configuring VPLS Multihoming

IN THIS SECTION

- [VPLS Multihomed Site Configuration | 951](#)
- [VPLS Single-Homed Site Configuration | 953](#)

VPLS multihoming allows you to connect a customer site to multiple PE routers to provide redundant connectivity while preventing the formation of Layer 2 loops in the service provider's network. A VPLS site multihomed to two or more PE routers provides redundant connectivity in the event of a PE router-to-CE device link failure or the failure of a PE router. For more information about VPLS multihoming, see "[VPLS Multihoming Overview](#)" on page 881.

NOTE: If you want to enable multihoming for a VPLS routing instance, you cannot also enable LDP signaling. You can only enable BGP signaling.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The following sections describe how to configure VPLS multihoming. Some information is also provided on single-homed site configuration versus multihomed site configuration.

VPLS Multihomed Site Configuration

The following describes the requirements for a VPLS multihomed site configuration:

- Assign the same site ID on all PE routers connected to the same CE devices.

When two PE routers use the same site ID, VPLS assumes multihoming behavior by default. The site preference value is used to signal the primary and backup PE router. In such cases, when multihoming is explicitly configured using the `multi-homing` statement, it is only used for tracking the BGP peer status, such as to prevent isolation of the PE router from the core or split brain. There are scenarios, however that require preventing of BGP peer tracking, such as in a two-PE-router topology. In such cases, multihoming should not be explicitly configured as it can break node redundancy.

When identical site IDs are used without configuring multihoming, a collision log message is generated at each signaling: `RPD_L2VPN_SITE_COLLISION: Same site ID 2 configured on remote PE (RD 8.8.8.1:1013:) and local PE in VPN 1013 (non-multihomed site 2).` This is expected behavior.

- Assign unique route distinguishers for each multihomed PE router.
- Reference all interfaces assigned to the multihomed VPLS site on each PE router. Only one of these interfaces is used to send and receive traffic for this site at a time.
- Either designate a primary interface or allow the router to select the interface to be used as the primary interface.

If the router selects the interface, the interface used to connect the PE router to the site depends on the order in which interfaces are listed in the PE router's configuration. The first operational interface in the set of configured interfaces is chosen to be the designated interface. If this interface fails, the next interface in the list is selected to send and receive traffic for the site.

The following configuration shows the statements you need to configure to enable VPLS multihoming:

```
[edit routing-instances routing-instance-name]
instance-type vpls;
interface interface-name;
interface interface-name;
protocols vpls {
  site site-name {
    active-interface {
      any;
      primary interface-name;
    }
    interface interface-name;
    interface interface-name;
```

```

    multi-homing;
    site-identifier number;
  }
}
route-distinguisher (as-number:id | ip-address:id);

```

NOTE: If you add a direct connection between CE devices that are multihomed to the same VPLS site on different PE routers, the traffic can loop and a loss of connectivity might occur. We do not recommend this topology.

Most of these statements are explained in more detail in the rest of this chapter. The following sections explain how to configure the statements that are specific to VPLS multihoming:

Specifying an Interface as the Active Interface

You need to specify one of the interfaces for the multihomed site as the primary interface. If there are multiple interfaces, the remaining interfaces are activated only when the primary interface goes down. If no active interfaces are configured at the site level, all traffic for a VPLS site travels through a single, non-multihomed PE router.

You must configure one of the following options for the active-interface statement:

- **any**—One configured interface is randomly designated as the active interface for the VPLS site.
- **primary**—Specify the name of the multihomed interface to be used as the primary interface by the VPLS site.

To specify a multihomed interface as the primary interface for the VPLS site, include the active-interface statement:

```

active-interface {
    any;
    primary interface-name;
}

```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* protocols vpls site *site-name*]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls site *site-name*]

Configuring Multihoming on the PE Router

When a CE device is connected to the same VPLS site on more than one PE router, including the `multi-homing` statement on all associated PE routers results in tracking of BGP peers. If no BGP peer is available, VPLS deactivates all active interfaces for a site. When two PE routers use the same site ID, VPLS assumes multihoming behavior by default. The site preference value is used to signal the primary and backup PE router. In such cases, when multihoming is explicitly configured using the `multi-homing` statement, it is only used for tracking the BGP peer status, such as to prevent isolation of the PE router from the core or split brain.

NOTE: When identical site IDs are used without configuring multihoming, a collision log message is generated at each signaling: `RPD_L2VPN_SITE_COLLISION: Same site ID 2 configured on remote PE (RD 8.8.8.1:1013:) and local PE in VPN 1013 (non-multihomed site 2).` This is expected behavior.

VPLS Single-Homed Site Configuration

All VPLS single-homed sites are connected to the same default VE device. All interfaces in a VPLS routing instance that are not configured as part of a multihomed site are assumed to be single-homed to the default VE device.

RELATED DOCUMENTATION

[VPLS Multihoming Overview | 881](#)

[Example: VPLS Multihoming, Improved Convergence Time | 953](#)

[active-interface \(VPLS Multihoming\) | 1435](#)

[multi-homing \(VPLS Multihoming for BGP VPLS\) | 1584](#)

Example: VPLS Multihoming, Improved Convergence Time

IN THIS SECTION

- [Requirements | 954](#)
- [Overview | 954](#)
- [Configuration | 956](#)

This example shows how to configure a virtual private LAN service (VPLS) employing multihoming to a customer site. This particular VPLS multihoming example shows how to configure a feature that improves the network convergence time in the event a multihomed site needs to switch traffic to its alternate PE router.

Requirements

This example uses the following hardware and software components:

- Three M Series, MX Series, or T Series routers
- Junos OS Release 12.2 or later

If you are using M Series or T Series routers, the PE routers must have either virtual loopback tunnel (vt) interfaces or label-switched interfaces (LSIs). On M Series and T Series routers, VPLS uses tunnel-based PICs to create virtual ports on vt interfaces. If you do not have a tunnel-based PIC installed on your M Series or T Series router, you can still configure VPLS by using LSIs to support the virtual ports. Use of LSIs requires Ethernet-based PICs installed in an Enhanced Flexible PIC Concentrator (FPC).

You do not need to use routers for the CE devices. For example, the CE devices can be EX Series Ethernet Switches.

Overview

IN THIS SECTION

- [Topology | 956](#)

All PE routers in a VPLS network operate like a large, distributed Ethernet switch to provide Layer 2 services to attached devices. This example illustrates a network of PE routers and CE devices configured to use VPLS multihoming. The topology consists of six routers: four PE routers and two CE devices. Device CE1 is multihomed to Routers PE1 and PE2. The PE routers are configured with the `best-site` and `mac-flush` statements to improve the convergence time in the event the connection between Device CE1 and one of its multihomed PE routers fails.

This example includes the following settings:

- `best-site`—Uses the B-bit of the control flags bit vector (the third bit counting from the most significant bit) within the Layer 2 information extended community to indicate that the site is preferred. Each VPLS site configured with the `best-site` statement signals to the other PE routers that it is the preferred site. The Layer 2 information extended community includes the following information:

- Extended community type (2 octets)
- Encapsulation type (1 octet)
- Control flags (1 octet)
- Layer 2 MTU (2 octets)
- Reserved (2 octets)


When a neighboring PE router within the VPLS routing instance receives the label block advertisement, it knows that the corresponding PE router is the most preferable router of those remote PE routers multihomed to that site. If a neighboring PE router does not support the best site feature, the standard local site selection process is used. For example, if Router PE1 does not receive a B-bit from any of the label blocks advertisements received from Router PE3, Router PE1 proceeds to assume that Router PE3 does not support the best site feature. It creates a virtual circuit based on its minimum-designated site. For the other PE routers that do support the best site feature, Router PE1 builds virtual circuits using the locally tagged best site.

- `mac-flush`—Enables media access control (MAC) flush processing for the VPLS routing instance or for the mesh group under a VPLS routing instance. MAC flush processing removes MAC addresses from the MAC address database that have been learned dynamically. With the dynamically learned MAC addresses removed, MAC address convergence requires less time to complete.

Topology

Figure 67 on page 956 shows the topology used in this example. Router PE2 is configured with the best-site statement and acts as the preferred gateway for traffic from Device CE1.

Figure 67: VPLS Multihoming Topology with Router PE2 Configured as the Best Site



Configuration

IN THIS SECTION

- CLI Quick Configuration | 956
- Router PE1 | 959
- Router PE2 | 963
- Router PE3 | 967

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Router PE1:

```

set interfaces fe-0/1/0 encapsulation ethernet-vpls
set interfaces fe-0/1/0 unit 0 family vpls
set interfaces fe-0/1/2 unit 0 family inet address 10.0.59.14/32
set interfaces fe-0/1/2 unit 0 family iso
set interfaces fe-0/1/2 unit 0 family mpls
set interfaces fe-0/1/3 unit 0 family inet address 10.0.89.14/30
set interfaces fe-0/1/3 unit 0 family iso
set interfaces fe-0/1/3 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.168.9.1/32
set interfaces lo0 unit 0 family iso address 47.0005.8083.0000.1921.6800.5003.00
set routing-options router-id 192.168.9.1
set protocols mpls interface all
set protocols bgp group int type internal
set protocols bgp group int local-address 192.0.2.1
set protocols bgp group int family l2vpn signaling
set protocols isis level 1 disable
set protocols isis interface fe-0/1/2.0
set protocols isis interface fe-0/1/3.0
set protocols isis interface lo0.0
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface fe-0/1/0.0
set routing-instances vpls_1 route-distinguisher 10.255.107.74:1
set routing-instances vpls_1 vrf-target target:65056:1
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls site site_3 site-identifier 3
set routing-instances vpls_1 protocols vpls site site_3 multi-homing
set routing-instances vpls_1 protocols vpls site site_3 site-preference primary
set routing-instances vpls_1 protocols vpls site site_3 interface fe-0/1/0.0
set routing-instances vpls_1 protocols vpls site site_994 site-identifier 994
set routing-instances vpls_1 protocols vpls mac-flush

```

Router PE2:

```

set interfaces fe-0/1/1 encapsulation ethernet-vpls
set interfaces fe-0/1/1 unit 0 family vpls
set interfaces fe-0/1/2 unit 0 family inet address 10.0.59.13/32

```



```

set interfaces fe-0/1/2 unit 0 family iso
set interfaces fe-0/1/2 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.168.5.1/32
set interfaces lo0 unit 0 family iso address 47.0005.8083.0000.1921.6800.5005.00
set routing-options router-id 192.168.5.1
set protocols mpls interface all
set protocols isis level 1 disable
set protocols isis interface fe-0/1/2.0
set protocols isis interface lo0.0
set protocols ldp interface all
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface fe-0/1/1.0
set routing-instances vpls_1 route-distinguisher 10.255.107.76:1
set routing-instances vpls_1 vrf-target target:65056:1
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls site site_3 site-identifier 3
set routing-instances vpls_1 protocols vpls site site_3 multi-homing
set routing-instances vpls_1 protocols vpls site site_3 site-preference backup
set routing-instances vpls_1 protocols vpls site site_3 interface fe-0/1/1.0
set routing-instances vpls_1 protocols vpls site site_995 site-identifier 995
set routing-instances vpls_1 protocols vpls site site_995 best-site
set routing-instances vpls_1 protocols vpls mac-flush

```

Router PE3:

```

set interfaces fe-1/3/0 unit 0 description "PE3 to PE1"
set interfaces fe-1/3/0 unit 0 family inet address 10.0.89.13/30
set interfaces fe-1/3/0 unit 0 family iso
set interfaces fe-1/3/0 unit 0 family mpls
set interfaces fe-1/3/1 encapsulation ethernet-vpls
set interfaces fe-1/3/1 unit 0 family vpls
set interfaces lo0 unit 0 family inet address 192.168.8.1/32
set interfaces lo0 unit 0 family iso address 47.0005.8083.0000.1921.6800.5002.00
set routing-options router-id 192.168.8.1
set protocols isis level 1 disable
set protocols isis interface fe-1/3/0.0
set protocols isis interface lo0.0
set protocols ldp interface all

```

```

set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set protocols mpls interface all
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface fe-1/3/1.0
set routing-instances vpls_1 route-distinguisher 10.255.107.72:1
set routing-instances vpls_1 vrf-target target:65056:1
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls site site_2 site-identifier 2
set routing-instances vpls_1 protocols vpls site site_2 interface fe-0/1/0.100
set routing-instances vpls_1 protocols vpls site site_993 site-identifier 993
set routing-instances vpls_1 protocols vpls mac-flush

```

Router PE1

Step-by-Step Procedure

To configure Router PE1:

1. Configure the interfaces, interface encapsulation, and the protocol families.

```

[edit interfaces]
user@PE1# set fe-0/1/0 encapsulation ethernet-vpls
user@PE1# set fe-0/1/0 unit 0 family vpls
user@PE1# set fe-0/1/2 unit 0 family inet address 10.0.59.14/32
user@PE1# set fe-0/1/2 unit 0 family iso
user@PE1# set fe-0/1/2 unit 0 family mpls
user@PE1# set fe-0/1/3 unit 0 family inet address 10.0.89.14/30
user@PE1# set fe-0/1/3 unit 0 family iso
user@PE1# set interfaces fe-0/1/3 unit 0 family mpls
user@PE1# set lo0 unit 0 family inet address 192.168.9.1/32
user@PE1# set lo0 unit 0 family iso address 47.0005.8083.0000.1921.6800.5003.00

```

2. Configure the protocol-independent properties.

```

[edit routing-options]
user@PE1# set router-id 192.168.9.1

```

3. Configure MPLS on the router's interfaces.

```
[edit protocols mpls]
user@PE1# set interface all
```

4. Configure BGP.

```
[edit protocols bgp]
user@PE1# set group int type internal
user@PE1# set group int local-address 192.0.2.1
user@PE1# set group int family l2vpn signaling
```

5. Configure IS-IS as the IGP between the PE routers.

```
[edit protocols isis]
user@PE1# set level 1 disable
user@PE1# set interface fe-0/1/3.0
user@PE1# set interface lo0.0
```

6. Configure LDP as the signaling protocol for MPLS.

```
[edit protocols ldp]
user@PE1# set interface all
user@PE1# set interface fxp0.0 disable
user@PE1# set interface lo0.0
```

7. Configure the VPLS routing instance.

Include the `mac-flush` statement to ensure that stale routes are removed from Router PE1 promptly.

```
[edit routing-instances vpls_1]
user@PE1# set instance-type vpls
user@PE1# set interface fe-0/1/0.0
user@PE1# set route-distinguisher 10.255.107.74:1
user@PE1# set vrf-target target:65056:1
user@PE1# set protocols vpls no-tunnel-services
user@PE1# set protocols vpls site site_3 site-identifier 3
user@PE1# set protocols vpls site site_3 multi-homing
```

```

user@PE1# set protocols vpls site site_3 site-preference primary
user@PE1# set protocols vpls site site_3 interface fe-0/1/0.0
user@PE1# set protocols vpls site site_994 site-identifier 994
user@PE1# set protocols vpls mac-flush

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE1# show interfaces
fe-0/1/0 {
    encapsulation ethernet-vpls;
    unit 0 {
        family vpls;
    }
}
fe-0/1/2 {
    unit 0 {
        family inet {
            address 10.0.59.14/32;
        }
        family iso;
        family mpls;
    }
}
fe-0/1/3 {
    unit 0 {
        family inet {
            address 10.0.89.14/30;
        }
        family iso;
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.168.9.1/32;
        }
    }
}

```

```

        family iso {
            address 47.0005.8083.0000.1921.6800.5003.00;
        }
    }
}

```

```

user@PE1# show protocols
mpls {
    interface all;
}
bgp {
    group int {
        type internal;
        local-address 192.0.2.1;
        family l2vpn {
            signaling;
        }
    }
}
isis {
    level 1 disable;
    interface fe-0/1/2.0;
    interface fe-0/1/3.0;
    interface lo0.0;
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}

```

```

user@PE1# show routing-instances
vpls_1 {
    instance-type vpls;
    interface fe-0/1/0.0;
    route-distinguisher 10.255.107.74:1;
    vrf-target target:65056:1;
    protocols {

```

```

    vpls {
        no-tunnel-services;
        site site_3 {
            site-identifier 3;
            multi-homing;
            site-preference primary;
            interface fe-0/1/0.0;
        }
        site site_994 {
            site-identifier 994;
        }
        mac-flush;
    }
}
}

```

```

user@PE1# show routing-options
router-id 192.168.9.1;

```

Router PE2

Step-by-Step Procedure

To configure Router PE2:

1. Configure the interfaces, interface encapsulation, and the protocol families.

```

[edit interfaces]
user@PE2# set fe-0/1/1 encapsulation ethernet-vpls
user@PE2# set fe-0/1/1 unit 0 family vpls
user@PE2# set fe-0/1/2 unit 0 family inet address 10.0.59.13/32
user@PE2# set fe-0/1/2 unit 0 family iso
user@PE2# set fe-0/1/2 unit 0 family mpls
user@PE2# set lo0 unit 0 family inet address 192.168.5.1/32
user@PE2# set lo0 unit 0 family iso address 47.0005.8083.0000.1921.6800.5005.00

```

2. Configure the protocol-independent properties.

```
[edit routing-options]
user@PE2# set router-id 192.168.5.1
```

3. Configure MPLS on the Router PE2 interfaces.

```
[edit protocols]
user@PE2# set mpls interface all
```

4. Configure the LDP as the signaling protocol for MPLS on the PE router facing interface.

```
[edit protocols ldp]
user@PE2# set interface all
user@PE2# set interface fxp0.0 disable
user@PE2# set interface lo0.0
```

5. Configure IS-IS as the IGP between the PE routers.

```
[edit protocols isis]
user@PE2# set level 1 disable
user@PE2# set interface fe-0/1/2.0
user@PE2# set interface lo0.0
```

6. Configure the VPLS routing instance vpls_1.

Include the `best-site` statement to ensure that Router PE2 acts as the preferred path for the CE router. Include the `mac-flush` statement to ensure that stale routes are removed from Router PE2 promptly.

```
[edit routing-instances vpls_1]
user@PE2# set instance-type vpls
user@PE2# set interface fe-0/1/1.0
user@PE2# set route-distinguisher 10.255.107.76:1
user@PE2# set vrf-target target:65056:1
user@PE2# set protocols vpls no-tunnel-services
user@PE2# set protocols vpls site site_3 site-identifier 3
user@PE2# set protocols vpls site site_3 multi-homing
```

```

user@PE2# set protocols vpls site site_3 site-preference backup
user@PE2# set protocols vpls site site_3 interface fe-0/1/1.0
user@PE2# set protocols vpls site site_995 site-identifier 995
user@PE2# set protocols vpls site site_995 best-site
user@PE2# set protocols vpls mac-flush

```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```

user@PE2# show interfaces
fe-0/1/1 {
    encapsulation ethernet-vpls;
    unit 0 {
        family vpls;
    }
}
fe-0/1/2 {
    unit 0 {
        family inet {
            address 10.0.59.13/32;
        }
        family iso;
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.168.5.1/32;
        }
        family iso {
            address 47.0005.8083.0000.1921.6800.5005.00;
        }
    }
}

```



```

    }
}

```

```
user@PE2# show protocols
```

```

mpls {
    interface all;
}
isis {
    level 1 disable;
    interface fe-0/1/2.0;
    interface lo0.0;
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}

```

```
user@PE2# show routing-instances
```

```

vpls_1 {
    instance-type vpls;
    interface fe-0/1/1.0;
    route-distinguisher 10.255.107.76:1;
    vrf-target target:65056:1;
    protocols {
        vpls {
            no-tunnel-services;
            site site_3 {
                site-identifier 3;
                multi-homing;
                site-preference backup;
                interface fe-0/1/1.0;
            }
            site site_995 {
                site-identifier 995;
                best-site;
            }
        }
        mac-flush;
    }
}

```

```

    }
  }
}

```

```

user@pe2# show routing-options
router-id 192.168.5.1;

```

Router PE3

Step-by-Step Procedure

To configure Router PE3:

1. Configure the interfaces, interface encapsulation, and the protocol families.

```

[edit interfaces]
user@PE3# set fe-1/3/0 unit 0 description "PE3 to PE1"
user@PE3# set fe-1/3/0 unit 0 family inet address 10.0.89.13/30
user@PE3# set fe-1/3/0 unit 0 family iso
user@PE3# set fe-1/3/0 unit 0 family mpls
user@PE3# set fe-1/3/1 encapsulation ethernet-vpls
user@PE3# set fe-1/3/1 unit 0 family vpls
user@PE3# set lo0 unit 0 family inet address 192.168.8.1/32
user@PE3# set lo0 unit 0 family iso address 47.0005.8083.0000.1921.6800.5002.00

```

2. Configure the protocol-independent properties.

```

[edit routing-options]
user@PE3# set router-id 192.168.8.1

```

3. Configure IS-IS as the IGP between the PE routers.

```

[edit protocols isis]
user@PE3# set level 1 disable
user@PE3# set interface fe-0/1/3.0
user@PE3# set interface lo0.0

```

4. Configure LDP as the signaling protocol for MPLS.

```
[edit protocols ldp]
user@PE3# set interface all
user@PE3# set interface fxp0.0 disable
user@PE3# set interface lo0.0
```

5. Configure the VPLS routing instance.

Include the `mac-flush` statement here to ensure that stale routes are removed from Router PE1 promptly.

```
[edit routing-instances vpls_1]
user@PE3# set instance-type vpls
user@PE3# set interface fe-1/3/1.0
user@PE3# set route-distinguisher 10.255.107.72:1
user@PE3# set vrf-target target:65056:1
user@PE3# set protocols vpls no-tunnel-services
user@PE3# set protocols vpls site site_2 site-identifier 2
user@PE3# set protocols vpls site site_2 interface fe-0/1/0.100
user@PE3# set protocols vpls site site_993 site-identifier 993
user@PE3# set protocols vpls mac-flush
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE3# show interfaces
fe-1/3/0 {
  unit 0 {
    description "PE3 to PE1";
    family inet {
      address 10.0.89.13/30;
    }
    family iso;
    family mpls;
  }
}
```

```

fe-1/3/1 {
    encapsulation ethernet-vpls;
    unit 0 {
        family vpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.168.8.1/32;
        }
        family iso {
            address 47.0005.8083.0000.1921.6800.5002.00;
        }
    }
}

```

```

user@PE3# show protocols
mpls {
    interface all;
}
bgp {
    group int {
        type internal;
        local-address 192.0.2.2;
        family l2vpn {
            signaling;
        }
    }
}
isis {
    level 1 disable;
    interface fe-1/3/0.0;
    interface lo0.0;
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

```

```

interface lo0.0;
}

```

```

user@PE3# show routing-instances
vpls_1 {
    instance-type vpls;
    interface fe-0/1/0.100; ## 'fe-0/1/0.100' is not defined
    route-distinguisher 10.255.107.72:1;
    vrf-target target:65056:1;
    protocols {
        vpls {
            no-tunnel-services;
            site site_2 {
                site-identifier 2;
                interface fe-1/3/1.0;
            }
            site site_993 {
                site-identifier 993;
            }
            mac-flush;
        }
    }
}

```

```

user@pe3# show routing-options
router-id 192.168.8.1;

```

RELATED DOCUMENTATION

[Configuring VPLS Multihoming | 950](#)

[Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

[best-site | 1444](#)

[multi-homing \(VPLS Multihoming for BGP VPLS\) | 1584](#)

Example: Configuring VPLS Multihoming (FEC 129)

IN THIS SECTION


- [VPLS Multihoming Overview | 971](#)
- [Example: Configuring VPLS Multihoming \(FEC 129\) | 973](#)

VPLS Multihoming Overview

Virtual private LAN service (VPLS) multihoming enables you to connect a customer site to two or more PE routers to provide redundant connectivity. A redundant PE router can provide network service to the customer site as soon as a failure is detected. VPLS multihoming helps to maintain VPLS service and traffic forwarding to and from the multihomed site in the event of the following types of network failures:

- PE router to CE device link failure
- PE router failure
- MPLS-reachability failure between the local PE router and a remote PE router

Figure 68: CE Device Multihomed to Two PE Routers



NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Figure 68 on page 971 illustrates how a CE device could be multihomed to two PE routers. Device CE1 is multihomed to Routers PE1 and PE2. Device CE2 has two potential paths to reach Device CE1, but only one path is active at any one time. If Router PE1 were the designated VPLS edge (VE) device (also called a designated forwarder), BGP would signal a pseudowire from Router PE3 to Router PE1. If a failure occurred over this path, Router PE2 would be made the designated VE device, and BGP would re-signal the pseudowire from Router PE3 to Router PE2.

Multihomed PE routers advertise network layer reachability information (NLRI) for the multihomed site to the other PE routers in the VPLS network. The NLRI includes the site ID for the multihomed PE routers. For all of the PE routers multihomed to the same CE device, you need to configure the same site ID. The remote VPLS PE routers use the site ID to determine where to forward traffic addressed to the customer site. To avoid route collisions, the site ID shared by the multihomed PE routers must be different than the site IDs configured on the remote PE routers in the VPLS network.

Although you configure the same site ID for each of the PE routers multihomed to the same CE device, you can configure unique values for other parameters, such as the route distinguisher. These values help to determine which multihomed PE router is selected as the designated VE device to be used to reach the customer site.

BEST PRACTICE: We recommend that you configure unique route distinguishers for each multihomed PE router. Configuring unique route distinguishers helps with faster convergence when the connection to a primary multihomed PE router goes down. If you configure unique route distinguishers, the other PE routers in the VPLS network must maintain additional state for the multihomed PE routers.

Remote PE routers in the VPLS network need to determine which of the multihomed PE routers should forward traffic to reach the CE device. To make this determination, remote PE routers use the VPLS path-selection process to select one of the multihomed PE routers based on its NLRI advertisement. Because remote PE routers pick only one of the NLRI advertisements, it establishes a pseudowire to only one of the multihomed PE routers, the PE router that originated the winning advertisement. This prevents multiple paths from being created between sites in the network, preventing the formation of Layer 2 loops. If the selected PE router fails, all PE routers in the network automatically switch to the backup PE router and establish new pseudowires to it.

BEST PRACTICE: To prevent the formation of Layer 2 loops between the CE devices and the multihomed PE routers, we recommend that you employ the Spanning Tree Protocol (STP) on your CE devices. Layer 2 loops can form due to incorrect configuration. Temporary Layer 2 loops can also form during convergence after a change in the network topology.

The PE routers run the BGP path selection procedure on locally originated and received Layer 2 route advertisements to establish that the routes are suitable for advertisement to other peers, such as BGP route reflectors. If a PE router in a VPLS network is also a route reflector, the path selection process for the multihomed site has no effect on the path selection process performed by this PE router for the purpose of reflecting Layer 2 routes. Layer 2 prefixes that have different route distinguishers are considered to have different NLRIs for route reflection. The VPLS path selection process enables the route reflector to reflect all routes that have different route distinguishers to the route reflector clients, even though only one of these routes is used to create the VPLS pseudowire to the multihomed site.

Junos OS supports VPLS multihoming for both BGP VPLS and FEC129 VPLS. Support for FEC 129 is added in Junos OS Release 12.3.

SEE ALSO

[Configuring VPLS Multihoming | 950](#)

[Advantages of Using Autodiscovery for VPLS Multihoming | 884](#)

[Example: Configuring VPLS Multihoming \(FEC 129\) | 973](#)

[Example: VPLS Multihoming, Improved Convergence Time | 953](#)

Example: Configuring VPLS Multihoming (FEC 129)

IN THIS SECTION

- [Requirements | 974](#)
- [Overview | 974](#)
- [Configuration | 976](#)
- [Verification | 986](#)

This example shows how to configure virtual private LAN service (VPLS) multihoming. Multihoming allows a customer site to connect to multiple provider edge (PE) routers. A VPLS site multihomed to two

or more PE routers provides redundant connectivity in the event of a PE router-to-CE device link failure or the failure of a PE router. The example demonstrates BGP-based multihoming support for FEC 129 VPLS (also known as LDP VPLS with BGP-based autodiscovery).

Requirements

This example has the following hardware and software requirements:

- One or more CE devices to represent a VPLS site.
- Two or more PE devices.
- Junos OS Release 12.3 or later running on the PE devices that are connected to the multihomed VPLS site.

Overview

BGP-based VPLS autodiscovery (FEC 129) enables each VPLS PE router to discover the other PE routers that are in the same VPLS domain. VPLS autodiscovery also automatically detects when PE routers are added or removed from the VPLS domain. You do not need to manually configure the VPLS and maintain the configuration when a PE router is added or deleted. VPLS autodiscovery uses BGP to discover the VPLS members and to set up and tear down pseudowires in the VPLS.

BGP multihoming enables you to connect a customer site to two or more PE routers to provide redundant connectivity while preventing the formation of Layer 2 loops in the service provider's network. The redundant connectivity maintains the VPLS service and traffic forwarding to and from the multihomed site in the event of a PE router-to-CE device link failure, the failure of a PE router, or an MPLS reachability failure between the local PE router and a remote PE router. A redundant PE router can begin providing service to the customer site as soon as the failure is detected.

When a CE device connects to multiple PE routers, each of these routers advertises reachability for the multihomed site—routes that have the same site ID in the Layer 2 network layer reachability information (NLRI). The other PE routers in the network use a BGP path selection process to select only one of the advertising routers to which they send traffic destined for the CE device. This path selection process eliminates Layer 2 loops in the VPLS network.

Autodiscovery is not specifically related to multihoming. Autodiscovery is not required for multihoming to work. They are two separate features. That said, the meaning of FEC 129 is that VPLS does autodiscovery. So when you configure multihoming for FEC 129, you must also, by definition, configure autodiscovery (with the `auto-discovery-only` statement).

There are two places in the configuration where you can configure VPLS multihoming. One is for FEC 128, and the other is for FEC 129:

- For FEC 128—routing-instances *instance-name* protocols vpls site *site-name* multi-homing

- For FEC 129—routing-instances *instance-name* protocols vpls multi-homing


The following statements are used for configuring multihoming for FEC 129:

```
[edit routing-instances instance-name protocols vpls]
multi-homing {
  peer-active;
  site site-name {
    active-interface interface-name {
      any;
      primary interface-name;
    }
    identifier identifier;
    interface interface-name {
      preference preference-value;
    }
    peer-active;
    preference (preference-value | backup | primary);
  }
}
```

This example shows Device CE1 multihomed to Router PE1 and Router PE2. In addition, Device CE2 is single-homed to Router PE1. Device PE3 is the remote PE router, connected to Device CE3. Multihoming is not enabled on Device PE3. ["CLI Quick Configuration" on page 976](#) shows the

configuration for all of the devices in [Figure 69 on page 976](#). The section "[Configuring Device PE1](#)" on [page 981](#) has step-by-step instructions for configuring Device PE1.

Figure 69: Topology for FEC 129 Multihoming



Configuration

IN THIS SECTION

- [CLI Quick Configuration | 976](#)
- [Configuring Device PE1 | 981](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Device PE1

```
set interfaces ge-0/3/3 encapsulation ethernet-vpls
set interfaces ge-0/3/3 unit 0 description PE1-to-CE2
set interfaces ge-0/3/3 unit 0 family vpls
set interfaces ge-0/3/1 encapsulation ethernet-vpls
```

```

set interfaces ge-0/3/1 unit 0 description PE1-to-CE1
set interfaces ge-0/3/1 unit 0 family vpls
set interfaces ge-1/2/0 unit 0 description PE1-to-P
set interfaces ge-1/2/0 unit 0 family inet address 10.1.1.1/30
set interfaces ge-1/2/0 unit 0 family mpls
set interfaces ge-1/2/1 unit 0 description PE1-to-PE2
set interfaces ge-1/2/1 unit 0 family inet address 10.1.1.5/30
set interfaces ge-1/2/1 unit 0 family mpls
set interfaces lo0 unit 2 family inet address 192.0.2.2/24
set protocols mpls interface ge-1/2/0.0
set protocols mpls interface ge-1/2/1.0
set protocols bgp local-address 192.0.2.2
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.3
set protocols bgp group pe-pe neighbor 192.0.2.4
set protocols bgp group pe-pe neighbor 192.0.2.5
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-1/2/0.0
set protocols ospf area 0.0.0.0 interface ge-1/2/1.0
set protocols ospf area 0.0.0.0 interface lo0.2 passive
set protocols ldp interface ge-1/2/0.0
set protocols ldp interface ge-1/2/1.0
set protocols ldp interface lo0.2
set routing-instances green instance-type vpls
set routing-instances green interface ge-0/3/1.0
set routing-instances green interface ge-0/3/3.0
set routing-instances green route-distinguisher 192.0.2.2:1
set routing-instances green l2vpn-id l2vpn-id:100:100
set routing-instances green vrf-target target:100:100
set routing-instances green protocols vpls no-tunnel-services
set routing-instances green protocols vpls oam ping-interval 600
set routing-instances green protocols vpls oam bfd-liveness-detection minimum-interval 200
set routing-instances green protocols vpls multi-homing site test identifier 1
set routing-instances green protocols vpls multi-homing site test interface ge-0/3/1.0
set routing-options router-id 192.0.2.2
set routing-options autonomous-system 100

```

Device PE2

```

set interfaces fe-0/1/3 encapsulation ethernet-vpls
set interfaces fe-0/1/3 unit 0 description PE2-to-CE1
set interfaces fe-0/1/3 unit 0 family vpls
set interfaces ge-1/2/0 unit 0 description PE2-to-PE1
set interfaces ge-1/2/0 unit 0 family inet address 10.1.1.6/30
set interfaces ge-1/2/0 unit 0 family mpls
set interfaces ge-1/2/2 unit 0 description PE2-to-P
set interfaces ge-1/2/2 unit 0 family inet address 10.1.1.10/30
set interfaces ge-1/2/2 unit 0 family mpls
set interfaces lo0 unit 4 family inet address 192.0.2.4/32
set protocols mpls interface ge-1/2/0.0
set protocols mpls interface ge-1/2/2.0
set protocols bgp local-address 192.0.2.4
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols bgp group pe-pe neighbor 192.0.2.3
set protocols bgp group pe-pe neighbor 192.0.2.5
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-1/2/0.0
set protocols ospf area 0.0.0.0 interface ge-1/2/2.0
set protocols ospf area 0.0.0.0 interface lo0.4 passive
set protocols ldp interface ge-1/2/0.0
set protocols ldp interface ge-1/2/2.0
set protocols ldp interface lo0.4
set routing-instances green instance-type vpls
set routing-instances green interface fe-0/1/3.0
set routing-instances green route-distinguisher 192.0.2.4:1
set routing-instances green l2vpn-id l2vpn-id:100:100
set routing-instances green vrf-target target:100:100
set routing-instances green protocols vpls no-tunnel-services
set routing-instances green protocols vpls oam ping-interval 600
set routing-instances green protocols vpls oam bfd-liveness-detection minimum-interval 200
set routing-instances green protocols vpls multi-homing site test identifier 1
set routing-instances green protocols vpls multi-homing site test interface fe-0/1/3.0
set routing-options router-id 192.0.2.4
set routing-options autonomous-system 100

```

Device PE3

```

set interfaces ge-0/3/3 unit 0 encapsulation ethernet-vpls
set interfaces ge-0/3/3 unit 0 description PE3-to-CE3
set interfaces ge-0/3/3 unit 0 family vpls
set interfaces ge-1/2/0 unit 0 description PE3-to-P
set interfaces ge-1/2/0 unit 0 family inet address 10.1.1.14/30
set interfaces ge-1/2/0 unit 0 family mpls
set interfaces lo0 unit 5 family inet address 192.0.2.5/24
set protocols rsdp interface ge-1/2/0.0
set protocols mpls interface ge-1/2/0.0
set protocols bgp local-address 192.0.2.5
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn auto-discovery-only
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols bgp group pe-pe neighbor 192.0.2.3
set protocols bgp group pe-pe neighbor 192.0.2.4
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-1/2/0.0
set protocols ospf area 0.0.0.0 interface lo0.5 passive
set protocols ldp interface ge-1/2/0.0
set protocols ldp interface lo0.5
set routing-instances green instance-type vpls
set routing-instances green interface ge-0/3/3.0
set routing-instances green route-distinguisher 192.0.2.5:100
set routing-instances green l2vpn-id l2vpn-id:100:100
set routing-instances green vrf-target target:100:100
set routing-instances green protocols vpls no-tunnel-services
set routing-instances green protocols vpls oam ping-interval 600
set routing-instances green protocols vpls oam bfd-liveness-detection minimum-interval 200
set routing-instances green protocols vpls oam ping-interval 600
set routing-instances green protocols vpls oam bfd-liveness-detection minimum-interval 200
set routing-options router-id 192.0.2.5
set routing-options autonomous-system 100

```

Device CE1

```

set interfaces ge-0/3/0 unit 0 description CE1-to-PE1
set interfaces ge-0/3/0 unit 0 family inet address 192.0.2.15/24

```

```
set interfaces fe-0/1/2 unit 0 description CE1-to-PE2
set interfaces fe-0/1/2 unit 0 family inet address 192.0.2.11/24
```

Device CE2

```
set interfaces ge-0/3/2 unit 0 description CE2-to-PE1
set interfaces ge-0/3/2 unit 0 family inet address 192.0.2.16/24
```

Device CE3

```
set interfaces ge-0/3/2 unit 0 description CE3-to-PE3
set interfaces ge-0/3/2 unit 0 family inet address 192.0.2.17/24
```

Device P

```
set interfaces ge-1/2/0 unit 0 description P-to-PE1
set interfaces ge-1/2/0 unit 0 family inet address 10.1.1.2/30
set interfaces ge-1/2/0 unit 0 family mpls
set interfaces ge-3/2/0 unit 0 description P-to-PE2
set interfaces ge-3/2/0 unit 0 family inet address 10.1.1.9/30
set interfaces ge-3/2/0 unit 0 family mpls
set interfaces ge-4/2/0 unit 0 description P-to-PE3
set interfaces ge-4/2/0 unit 0 encapsulation ethernet
set interfaces ge-4/2/0 unit 0 family inet address 10.1.1.13/30
set interfaces ge-4/2/0 unit 0 family mpls
set interfaces lo0 unit 3 family inet address 192.0.2.3/32
set protocols mpls interface ge-1/2/0.0
set protocols mpls interface ge-3/2/0.0
set protocols mpls interface ge-4/2/0.0
set protocols bgp local-address 192.0.2.3
set protocols bgp group pe-pe type internal
set protocols bgp group pe-pe family l2vpn signaling
set protocols bgp group pe-pe neighbor 192.0.2.2
set protocols bgp group pe-pe neighbor 192.0.2.4
set protocols bgp group pe-pe neighbor 192.0.2.5
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface ge-1/2/0.0
set protocols ospf area 0.0.0.0 interface ge-3/2/0.0
set protocols ospf area 0.0.0.0 interface ge-4/2/0.0
set protocols ospf area 0.0.0.0 interface lo0.3 passive
set protocols ldp interface ge-1/2/0.0
```

```

set protocols ldp interface ge-3/2/0.0
set protocols ldp interface ge-4/2/0.0
set protocols ldp interface lo0.3
set routing-options router-id 192.0.2.3
set routing-options autonomous-system 100

```

Configuring Device PE1

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure Device PE1:

1. Configure the interfaces.

Configure family `mpls` on the provider-facing interfaces. Configure family `vpls` on the customer-facing interfaces.

```

[edit interfaces]
user@PE1# set ge-0/3/3 encapsulation ethernet-vpls
user@PE1# set ge-0/3/3 unit 0 description PE1-to-CE2
user@PE1# set ge-0/3/3 unit 0 family vpls
user@PE1# set ge-0/3/1 encapsulation ethernet-vpls
user@PE1# set ge-0/3/1 unit 0 description PE1-to-CE1
user@PE1# set ge-0/3/1 unit 0 family vpls
user@PE1# set ge-1/2/0 unit 0 description PE1-to-P
user@PE1# set ge-1/2/0 unit 0 family inet address 10.1.1.1/30
user@PE1# set ge-1/2/0 unit 0 family mpls
user@PE1# set ge-1/2/1 unit 0 description PE1-to-PE2
user@PE1# set ge-1/2/1 unit 0 family inet address 10.1.1.5/30
user@PE1# set ge-1/2/1 unit 0 family mpls
user@PE1# set lo0 unit 2 family inet address 192.0.2.2/24

```

2. Configure the interior gateway protocol (IGP) and signaling protocols on the provider-facing interfaces.

The traffic-engineering statement enables OSPF to advertise the label-switched path (LSP) metric in summary link-state advertisements (LSAs).

```
[edit protocols]
user@PE1# set ldp interface ge-1/2/0.0
user@PE1# set ldp interface ge-1/2/1.0
user@PE1# set ldp interface lo0.2
user@PE1# set mpls interface ge-1/2/0.0
user@PE1# set mpls interface ge-1/2/1.0
user@PE1# set ospf traffic-engineering
user@PE1# set ospf area 0.0.0.0 interface ge-1/2/0.0
user@PE1# set ospf area 0.0.0.0 interface ge-1/2/1.0
user@PE1# set ospf area 0.0.0.0 interface lo0.2 passive
```

3. Configure BGP.

The auto-discovery-only statement notifies the routing process (rpd) to expect autodiscovery-related NLRI messages so that information can be deciphered and used by LDP and VPLS. The auto-discovery-only statement must be configured on all PE routers in a VPLS. If you configure route reflection, the auto-discovery-only statement is also required on provider (P) routers that act as the route reflector in supporting FEC 129-related updates.

For interoperation scenarios in which a PE router must support both types of NLRI (FEC 128 and FEC 129), this example also includes the signaling statement.

```
[edit protocols bgp]
user@PE1# set local-address 192.0.2.2
user@PE1# set group pe-pe type internal
user@PE1# set group pe-pe family l2vpn auto-discovery-only
user@PE1# set group pe-pe family l2vpn signaling
user@PE1# set group pe-pe neighbor 192.0.2.3
user@PE1# set group pe-pe neighbor 192.0.2.4
user@PE1# set group pe-pe neighbor 192.0.2.5
```

4. Configure the routing instance.

Both CE-facing interfaces are included in the routing instance. Only the multihomed interface is included in the multihoming site.

As a convention, the route distinguisher is composed of Device PE1's loopback interface address and the multihoming site identifier.

```
[edit routing-instances green]
user@PE1# set instance-type vpls
user@PE1# set interface ge-0/3/1.0
user@PE1# set interface ge-0/3/3.0
user@PE1# set route-distinguisher 192.0.2.2:1
user@PE1# set l2vpn-id l2vpn-id:100:100
user@PE1# set vrf-target target:100:100
user@PE1# set protocols vpls no-tunnel-services
user@PE1# set protocols vpls multi-homing site test identifier 1
user@PE1# set protocols vpls multi-homing site test interface ge-0/3/1.0
```

5. (Optional) Configure bidirectional forwarding detection (BFD) for FEC 129 VPLS.

```
[edit routing-instances green]
user@PE1# set protocols vpls oam ping-interval 600
user@PE1# set protocols vpls oam bfd-liveness-detection minimum-interval 200
```

6. Configure the autonomous system (AS) number and router ID.

```
[edit routing-options]
user@PE1# set router-id 192.0.2.2
user@PE1# set autonomous-system 100
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-instances`, and `show routing-options` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show interfaces
ge-0/3/1 {
  encapsulation ethernet-vpls;
  unit 0 {
    description PE1-to-CE1;
    family vpls;
```

```

    }
}
ge-0/3/3 {
    encapsulation ethernet-vpls;
    unit 0 {
        description PE1-to-CE2;
        family vpls;
    }
}
ge-1/2/0 {
    unit 0 {
        description PE1-to-P;
        family inet {
            address 10.1.1.1/30;
        }
        family mpls;
    }
}
ge-1/2/1 {
    unit 0 {
        description PE1-to-PE2;
        family inet {
            address 10.1.1.5/30;
        }
        family mpls;
    }
}
lo0 {
    unit 2 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}
}

```

```

user@PE1# show protocols
mpls {
    interface ge-1/2/0.0;
    interface ge-1/2/1.0;
}
bgp {

```

```

local-address 192.0.2.2;
group pe-pe {
    type internal;
    family l2vpn {
        auto-discovery-only;
        signaling;
    }
    neighbor 192.0.2.3;
    neighbor 192.0.2.4;
    neighbor 192.0.2.5;
}
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface ge-1/2/0.0;
        interface ge-1/2/1.0;
        interface lo0.2 {
            passive;
        }
    }
}
}
ldp {
    interface ge-1/2/0.0;
    interface ge-1/2/1.0;
    interface lo0.2;
}
}

```

```

user@PE1# show routing-instances
green {
    instance-type vpls;
    interface ge-0/3/1.0;
    interface ge-0/3/3.0;
    route-distinguisher 192.0.2.2:100;
    l2vpn-id l2vpn-id:100:100;
    vrf-target target:100:100;
    protocols {
        vpls {
            no-tunnel-services;
            oam {
                ping-interval 600;
            }
        }
    }
}

```

```

        bfd-liveness-detection {
            minimum-interval 200;
        }
    }
    multi-homing {
        site test {
            identifier 1;
            interface ge-0/3/1.0;
        }
    }
}

```

```

user@PE1# show routing-options
router-id 192.0.2.2;
autonomous-system 100;

```

If you are done configuring the device, enter `commit` from configuration mode.

Verification

IN THIS SECTION

- [Verifying That Multihoming Is Operational | 986](#)
- [Checking the Multihoming Routes | 988](#)
- [Checking the BFD Sessions | 989](#)
- [Pinging the Remote PE Router in the VPLS Domain | 990](#)

Confirm that the configuration is working properly.

Verifying That Multihoming Is Operational

Purpose

Verify that multihoming is operational.

Action

From operational mode, enter the `show vpls connections extensive` command.

```
user@PE1> show vpls connections extensive
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy
RS -- remote site standby	SN -- Static Neighbor
LB -- Local site not best-site	RB -- Remote site not best-site
VM -- VLAN ID mismatch	

Legend for interface status

Up -- operational
Dn -- down

Instance: green

L2vpn-id: 100:100

Local-id: 192.0.2.2

Number of local interfaces: 2

Number of local interfaces up: 2

ge-0/3/1.0

ge-0/3/3.0

lsi.101711873

Intf - vpls green local-id 192.0.2.2 remote-id 192.0.2.4

neighbor 192.0.2.4

Remote-id	Type	St	Time last up	# Up trans
192.0.2.4	rmt	Up	Jan 31 13:49:52 2012	1

```

Remote PE: 192.0.2.4, Negotiated control-word: No
Incoming label: 262146, Outgoing label: 262146
Local interface: lsi.101711873, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls green local-id 192.0.2.2 remote-id 192.0.2.4 neighbor 192.0.2.4
Connection History:
  Jan 31 13:49:52 2012  status update timer
  Jan 31 13:49:52 2012  PE route changed
  Jan 31 13:49:52 2012  Out lbl Update                262146
  Jan 31 13:49:52 2012  In lbl Update                 262146
  Jan 31 13:49:52 2012  loc intf up                   lsi.101711873
Multi-home:
Local-site      Id    Pref  State
test            1    100   Up
Number of interfaces: 1
Number of interfaces up: 1
  ge-0/3/1.0
Received multi-homing advertisements:
Remote-PE      Pref  flag  Description
192.0.2.4      100   0x0

```

Meaning

The output shows the status of multihoming for routing instance green.

Checking the Multihoming Routes

Purpose

Verify that the expected routes are identified as multihoming.

Action

From operational mode, enter the `show route table bgp.l2vpn.0` and `show route table green.l2vpn.0` commands.

```

user@PE1> show route table bgp.l2vpn.0
bgp.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.4:100:192.0.2.4/96 AD
      *[BGP/170] 1d 03:10:45, localpref 100, from 192.0.2.4
      AS path: I, validation-state: unverified

```

```

> via ge-1/2/1.5
192.0.2.4:100:1:0/96 MH
*[BGP/170] 1d 03:10:45, localpref 100, from 192.0.2.4
AS path: I, validation-state: unverified
> via ge-1/2/1.5

```

```

user@PE1> show route table green.l2vpn.0
green.l2vpn.0: 6 destinations, 6 routes (6 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.2:100:192.0.2.2/96 AD
*[VPLS/170] 1d 03:11:03, metric2 1
Indirect
192.0.2.4:100:192.0.2.4/96 AD
*[BGP/170] 1d 03:11:02, localpref 100, from 192.0.2.4
AS path: I, validation-state: unverified
> via ge-1/2/1.5
192.0.2.2:100:1:0/96 MH
*[VPLS/170] 1d 03:11:03, metric2 1
Indirect
192.0.2.4:100:1:0/96 MH
*[BGP/170] 1d 03:11:02, localpref 100, from 192.0.2.4
AS path: I, validation-state: unverified
> via ge-1/2/1.5
192.0.2.4:NoCtrlWord:5:100:100:192.0.2.2:192.0.2.4/176
*[VPLS/7] 1d 03:11:02, metric2 1
> via ge-1/2/1.5
192.0.2.4:NoCtrlWord:5:100:100:192.0.2.4:192.0.2.2/176
*[LDP/9] 1d 03:11:02
Discard

```

Meaning

MH in the output indicates a multihoming route. AD indicates autodiscovery.

Checking the BFD Sessions

Purpose

Verify that the BFD session status is operational.

Action

From operational mode, enter the `show bfd session` command.

```
user@PE1> show bfd session
```

Address	State	Interface	Detect Time	Transmit Interval	Multiplier
198.51.100.1	Up	ge-1/2/1.0	0.600	0.200	3
198.51.100.1	Up	ge-1/2/0.0	0.600	0.200	3

2 sessions, 2 clients
Cumulative transmit rate 10.0 pps, cumulative receive rate 10.0 pps

Meaning

Up in the State field indicates that BFD is working.

Pinging the Remote PE Router in the VPLS Domain

Purpose

Check the operability of the MPLS Layer 2 virtual private network (VPN) connection.

Action

From operational mode, enter the `ping mpls l2vpn fec129` command with the `fec129` option.

```
user@PE1> ping mpls l2vpn fec129 instance green remote-id 192.0.2.5 remote-pe-address 192.0.2.5
!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Meaning

The output shows that the ping operation is successful, meaning that the LSP for a FEC 129 Layer 2 VPN connection is reachable.

SEE ALSO

[VPLS Multihoming Overview | 881](#)

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

Next-Generation VPLS for Multicast with Multihoming Overview

IN THIS SECTION

- [Operation of Next-Generation VPLS for Multicast with Multihoming Using BGP | 992](#)
- [Implementation of Redundancy Using VPLS Multihomed Links Between PE and CE Devices | 996](#)

VPLS emulates the broadcast domain of a LAN across an MPLS network cloud. Traditional MPLS implementations of VPLS require that all participating ingress PE routers make separate copies of each broadcast or multicast packet to send to all other PE routers that are part of the VPLS site for the same extended LAN. In a large virtual private network (VPN), replication overhead can be significant for each ingress router and its attached core-facing links.

Junos OS offers the following VPLS enhancements which provide redundancy for VPLS between PE and CE routers:

- Redundancy using BGP for multihomed links between PE and CE devices— Juniper Networks integrates the local preference and path selection capability of BGP with VPLS to allow a CE Ethernet switch to have a backup path across the network.
- Redundancy using the Spanning Tree Protocol (STP) for multihomed links between PE and CE devices — Various versions of STP can be used in the CE network to avoid loops in a multihoming environment. The provider does not have any control over this customer network configuration. The provider can also implement BGP-based loop avoidance as an additional measure to avoid loops.

The following standardized VPLS implementations are supported by the Internet Engineering Task Force (IETF):

- RFC 4761, *Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling*

- RFC 4762, *Virtual Private LAN Service (VPLS) Using LDP Signaling*

For more information about the basic configuration of next-generation VPLS, see the Technology Overview *Next-Generation VPLS Using Point-to-Multipoint LSPs for Unicast and Multicast Forwarding*.

For a detailed technology overview of VPLS, you can refer to *LDP-BGP VPLS Interworking* at the following location: <https://www.juniper.net/us/en/local/pdf/whitepapers/2000282-en.pdf> .

Redundancy Using BGP for Multihomed Links between PE and CE Routers

Juniper Networks implements a BGP-based multihoming solution to provide redundancy for VPLS between PE and CE routers.

In this implementation:

- VPLS-enabled PE routers (also called VPLS PE routers) collectively elect one of the VPLS PE routers, to which a site is multihomed, as the designated forwarder of traffic between this site and all other sites.
- All the other VPLS PE routers, to which the same site is connected, do not forward traffic to or from the site.
- Essentially all VPLS PE routers behave as if the site is singlehomed to the VPLS PE router that is the designated forwarder.
- Service providers are able to prevent well-known Layer 2 loops without relying on the customer's STP configuration.
- Customers can still run STP as a fallback strategy to prevent loops that are formed without the service provider's knowledge.

The benefits of multihoming include:

- Redundancy of the link connecting the PE router and the CE device.
- Redundancy of the directly connected PE routers.
- Faster convergence when there is a link failure between a PE router and CE device.
- The same BGP attributes are used to configure primary and backup links.

Operation of Next-Generation VPLS for Multicast with Multihoming Using BGP

VPLS provides a multipoint-to-multipoint Ethernet service that can span one or more metro areas and multiple sites. VPLS provides connectivity as if these sites are attached to the same Ethernet LAN.

VPLS uses an IP and MPLS service provider infrastructure. From the service provider's point of view, using IP and MPLS routing protocols and procedures instead of STP, and using MPLS labels instead of VLAN identifiers (IDs), significantly improves the scalability of the VPLS service.

Single CE Site Connected to Multiple VPLS PE Routers

This section describes the process used to elect a single designated forwarder for a multihomed site.

For a multihomed site, all the PE routers in the VPLS instance elect the same designated forwarder PE router using the BGP VPLS multihoming procedure. Only elected designated forwarders forward traffic to and receive traffic from the multihomed site. All other PE routers where this multihomed site is present do not participate in forwarding for that site.

All remote PE routers are aware of the designated forwarder PE router for each multihomed site and do not create a pseudowire to the PE routers that are not the designated forwarder for the multihomed site.

In [Figure 70 on page 994](#):


- The same site ID (sometimes known as a VPLS edge identifier or VE ID) is configured on all VPLS PE routers to which a site is multihomed.
- All PE routers are aware of which sites are multihomed since they see multiple advertisements with the same site ID.
- One of the VPLS PE routers is selected as the designated forwarder for this site by all PE routers based on a deterministic algorithm.
- The algorithm selects the VPLS PE router that originates the best advertisement with a particular site ID as the designated forwarder. There are two possible selection methods:
 - BGP path selection on the route reflector and the PE routers
 - VPLS site selection on the PE router only
- If multiple network layer reachability information (NLRI) advertisements have the same route distinguisher and site ID, the router uses BGP path selection rules to select the best path. The BGP rules are:
 - Always prefer advertisements that do not have the down bit set over ones that do have this bit set.
 - Prefer the advertisement with the higher local preference.
 - Use the configurable per-site site preference to set the BGP local preference in the advertisement and influence the choice of the designated forwarder.
 - Ignore the interior gateway protocol (IGP) metric while doing path selection because the choice of designated forwarder must be the same on all PE routers.

- Among advertisements with the same route distinguisher, apply VPLS site selection rules (a subset of BGP path selection rules) to pick the select advertisement.

Figure 70 on page 994 illustrates the following four-step process to select the designated forwarder and create the pseudowire:

1. Router PE1 and Router PE2 both have the same site ID (Site 1) for Router CE1.
Router PE1 has a better local preference of 65535 and is configured as the primary router.
2. Router PE3 receives the BGP NLRI advertisement from Router PE1 and Router PE2 with the local preferences of 65535 and 1, respectively.
3. Router PE3 runs the BGP path selection algorithm and selects Router PE1 as the designated forwarder VPLS edge PE router for Site 1.
4. Router PE3 creates the pseudowire only to Router PE1, which helps to save bandwidth in the network core.

Figure 70: Single CE Site Multihomed with Two PE Routers



The resulting VPLS PE router roles for Site 1 are:

- Router PE1 is the designated forwarder VPLS edge PE router.
- Router PE2 is the non-designated forwarder VPLS edge PE router.
- Router PE3 is the remote VPLS edge PE router.

All the interfaces linking the CE and PE devices that are connected to the designated forwarder VPLS PE router, are marked Up and forwarding in show command output.

All the interfaces linking the CE and PE devices on the non-designated forwarder VPLS PE router, are marked `vc-down` in `show` command output. The router does not send traffic or forward received traffic on these interfaces.

Remote VPLS PE routers establish pseudowires only to the designated PE router, and tear down any pseudowires to the non-designated PE router.


Multiple CE Sites Connected to a Single VPLS PE Router for Link Redundancy

This section describe some of the operational details of multiple CE sites connected to a single VPLS PE router.

In [Figure 71 on page 995](#):

- Router CE2 is multihomed to Router PE1 and Router PE2.
- Router CE1 is singlehomed to Router PE1.

Figure 71: Two CE Sites Multihomed to a Single PE Router on Different Line Cards



The scenario shown in Figure 2 is common. Your network might have a single PE router in a remote area, but you would like to multihome a Layer 2 network to different Flexible PIC Concentrators (FPCs) on the same PE router. This configuration provides link redundancy on the CE devices and link redundancy on the links between the CE and PE devices, but limited link redundancy on PE devices. In this case, you need the ability to configure a site to use a single active interface for forwarding.

In this scenario:

- Path selection is done per site to determine if a PE router is the designated forwarder for that site or not.

- Only a single pseudowire is established between any two PE routers, even if one or both of them have multiple designated PE routers.

NOTE: A pseudowire between two PE routers is always established between the designated sites with the minimum site IDs on the two PE routers.

- Establishing a single pseudowire avoids the need to maintain multiple flooding and media access control (MAC) address tables per instance (one per site) on each PE router.
- The local interfaces are marked `vc-down` in the `show` command output where a site is connected to the non-designated forwarder router.
- When a designated site on a PE router fails, all MAC addresses from this remote PE router have to be learned again, since the router does not know the exact site where the MAC addresses were originally learned from.

Implementation of Redundancy Using VPLS Multihomed Links Between PE and CE Devices

You might need to multihome a CE device to multiple PE routers without causing a Layer 2 forwarding loop. This is not a problem if the CE device is a router, since no Layer 2 loops can form when using a router. However, if the CE device is a Layer 2 device, like a hub or switch, multihoming it to two PE routers can cause a Layer 2 loop.

You can use one of the following methods to prevent the Layer 2 loop:

- BGP-based primary and backup link selection.
- Spanning tree protocol (STP) to prune links to the CE router. However, this method requires the service provider to trust its customer to not cause any Layer 2 loops by misconfiguration.
- Active and standby up link functionality, such as the redundant trunk groups that are supported on Juniper Networks EX Series Ethernet Switches.

The limitations of using STP on the CE site are:

- Backbone and access network bandwidth is not used efficiently.
- PE routers using STP to prevent loops with dual-homed sites receive broadcast traffic unnecessarily because the pseudowire to the standby PE router still exists.
- When the direct link between the CE and PE router fails, multihoming works fine. When a link connected downstream from the CE router fails, multihoming does not work.

The benefits and properties of the BGP-based solution are:

- BGP path selection does not have the limitations of STP.
- A CE device that is multihomed to multiple PE routers is given the same site ID on all the PE routers it is multihomed to.
- The BGP path selection algorithm selects the router that originates the best advertisement as the VPLS PE designated forwarder.
- If desired, you can set the local preference on the PE routers to control BGP path selection.
- BGP path selection occurs on the route reflector and the PE router.
- An IGP metric is not part of the selection process.
- If the route distinguisher is the same on both PE routers, the route reflector selects one PE router as the designated forwarder. If the route distinguishers are different on the PE routers, the route reflector forwards both copies of the route to the remote PE routers.

RELATED DOCUMENTATION

[Example: Next-Generation VPLS for Multicast with Multihoming | 997](#)

[Example: NG-VPLS Using Point-to-Multipoint LSPs | 1030](#)

[Next-Generation VPLS Point-to-Multipoint Forwarding Overview | 1024](#)

Example: Next-Generation VPLS for Multicast with Multihoming

IN THIS SECTION

- [Requirements | 997](#)
- [Overview and Topology | 999](#)
- [Configuration | 1001](#)

This example shows how to configure next-generation VPLS for multicast with multihoming. It is organized in the following sections:

Requirements

The following table lists the hardware and software requirements for this configuration.

Table 23: Hardware and Software Used

Equipment	Components	Software
Four MX Series 5G Universal Routing Platforms	DPC40X-1GE -X, DPC 4X-10GE-X, DPC40x-1GE-R, DPC 4X-10GE-R	Junos OS Release 9.3 or later
Two M320 Multiservice Edge Routers and T Series Core Routers	FPC 3, 10GE Xenpak	Junos OS Release 9.3 or later
Five EX Series Ethernet Switches	EX4200, EX3200	Junos OS Release 9.4 or later

Overview and Topology

Figure 72 on page 999 shows the physical topology used in this next-generation VPLS multihoming example.

Figure 72: Physical Topology of Next-Generation VPLS for Multicast with Multihoming





Figure 73 on page 1000 show the logical topology of the next-generation VPLS multihoming example.

Figure 73: Logical Topology of Next-Generation VPLS for Multicast with Multihoming



The network state and configuration before the implementation is as follows:

- Five PE routers participating in the next-generation VPLS domain named GOLD.
- OSPF, BGP, and RSVP are configured on the MPLS core interfaces.
- The `no-tunnel-services` statement is included in the VPLS routing instance. This statement supports the use of label-switched interface (LSI) tunnel interfaces for VPLS.
- Router PE1 and Router PE2 are configured with a dynamic point-to-multipoint LSP using the `vpls-GOLD-p2mp-template` template.
- Router PE3 and Router PE4 are configured to use static point-to-multipoint LSPs.

NOTE: Single-hop point-to-multipoint LSPs are not supported, so single-hop point-to-multipoint LSPs are down.

- Router CE1 is multihomed to Router PE1 and Router PE2 through an EX4200 Layer 2 switch.
- Router CE3 is multihomed to Router PE3 and Router PE4 through an EX4200 Layer 2 switch.

- Router CE5 is singlehomed to Router PE5.
- The off-path route reflector is configured for BGP. The `family l2vpn` statement is included in the route reflector configuration.
- Router CE3 is connected to test equipment through port 203/2. The test equipment generates multicast traffic to groups 203.0.113.1 through 203.0.113.10 at the rate of 10,000 pps.
- Router CE1 and Router CE5 are configured with static Internet Group Management Protocol (IGMP) joins so they can receive the multicast traffic from Router CE3.
- The Layer 2 switches are configured with trunk ports to the PE routers and access ports to the test equipment.

Here is a summary of the steps necessary to complete the configuration successfully:

1. Configure a unique route distinguisher for the VPLS routing instance named GOLD on Router PE1, Router PE2, Router PE3, and Router PE4.
2. Configure the same site ID for the multihomed PE routers. Configure both Router PE1 and Router PE2 with a site ID value of 1. Configure both Router PE3 and Router PE4 with a site ID value of 3.
3. Configure multihoming under the CE1 site configuration.
4. Configure the site-preference Primary on Router PE1 and configure the site-preference Backup on Router PE2. In this case, Router PE1 has the primary link to Router CE1 and Router PE2 has the backup link to Router CE1.
5. Configure the site preference on Router PE3 and Router PE4. Configure Router PE3 as the primary and Router PE4 as the backup.

Configuration

IN THIS SECTION

- [Configuring Next-Generation VPLS Multihoming | 1002](#)
- [Validating the VPLS Control Plane | 1003](#)
- [Verifying the VPLS Data Plane | 1011](#)
- [Results | 1016](#)

This section provides a step-by-step procedure to configure next-generation VPLS for multicast with multihoming.

NOTE: In any configuration session, it is good practice to verify periodically that the configuration can be committed using the `commit check` command.

This example is organized in the following sections:

Configuring Next-Generation VPLS Multihoming

Step-by-Step Procedure

1. In BGP-based VPLS multihoming, it is recommended that you configure distinct route distinguishers for each multihomed router. Configuring distinct route distinguishers helps with faster convergence when the connection to a primary router goes down. It also requires the other backup PE routers to maintain additional state information for faster convergence.

There are two levels of path selection:

- The first is BGP: BGP uses a combination of route distinguisher, site ID, and VE block offset for BGP path selection.
- The second is in VPLS: VPLS uses the site ID for VPLS path selection.

By configuring unique route distinguishers, the prefixes for BGP path selection are all unique. Therefore, BGP path selection is skipped and VPLS path selection is used, which only looks at the site ID.

On Router PE1, Router PE2, Router PE3, and Router PE4 configure a unique router distinguisher for the GOLD routing instance.

```
user@PE1# set routing-instance GOLD route-distinguisher 192.0.2.1:1
user@PE2# set routing-instance GOLD route-distinguisher 192.0.2.2:10
user@PE3# set routing-instance GOLD route-distinguisher 192.0.2.3:1
user@PE4# set routing-instance GOLD route-distinguisher 192.0.2.4:10
```

2. Configure site ID 1 on Routers PE1 and PE2 for Router CE1. Configure site ID 3 on Routers PE3 and PE4 for Router CE3.

```
user@PE1# set routing-instance GOLD protocols vpls site CE1 site-identifier 1
user@PE2# set routing-instance GOLD protocols vpls site CE1 site-identifier 1
```

```
user@PE3# set routing-instance GOLD protocols vpls site CE3 site-identifier 3
user@PE4# set routing-instance GOLD protocols vpls site CE3 site-identifier 3
```

3. Enable multihoming by including the `multi-homing` statement under the multihomed site configuration on Router PE1, Router PE2, Router PE3, and Router PE4.

```
user@PE1# set routing-instance GOLD protocols vpls site CE1 multi-homing
user@PE2# set routing-instance GOLD protocols vpls site CE1 multi-homing
user@PE3# set routing-instance GOLD protocols vpls site CE3 multi-homing
user@PE4# set routing-instance GOLD protocols vpls site CE3 multi-homing
```

4. Include the `site-preference primary` statement on Router PE1 and Router PE3, and include the `site-preference backup` statement on Router PE2 and Router PE4. The `site-preference primary` statement sets the local preference to the highest value (65535) and the `site-preference backup` statement sets the BGP local preference to 1. Since the site ID is the same, the routers select the highest local preference value as the designated forwarder.

```
user@PE1# set routing-instance GOLD protocols vpls site CE1 site-preference primary
user@PE2# set routing-instance GOLD protocols vpls site CE1 site-preference backup
user@PE3# set routing-instance GOLD protocols vpls site CE3 site-preference primary
user@PE4# set routing-instance GOLD protocols vpls site CE3 site-preference backup
```

Validating the VPLS Control Plane

Step-by-Step Procedure

This section presents show commands that you can use to verify the operation of the example configuration.

In this example the traffic patterns are:

- The source is connected to Router CE3 and sends 10,000 pps for the groups 203.0.113.1 to 203.0.113.10. Router CE3 is configured as a rendezvous point.
- Multicast receivers are connected to both Router CE1 and Router CE5. Protocol Independent Multicast (PIM) join messages are generated by the test equipment.
- The link between Router PE3 and Router CE3 and the link between Router PE1 and Router CE1 are configured as primaries for VPLS multihoming.
- All PE routers have a BGP session with the route reflector.

- All PE routers have a label-switched path (LSP) that is created to the route reflector so that the PE routers have a route to the route reflector in the `inet.3` table for route resolution.
1. On Router PE1, use the `show vpls connections` command to verify that the VPLS connections are Up between Router PE1 and Router PE3 and between Router PE1 and PE5. Router PE1 is the primary link selected by the VPLS multihoming configuration.

```
user@PE1# show vpls connections
```

```
Layer-2 VPN connections:
```

```
Legend for connection status (St)
```

```

EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch    WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down  NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range             Up -- operational
OL -- no outgoing label        Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch            MI -- Mesh-Group ID not availble
BK -- Backup connection        ST -- Standby connection

```

```
Legend for interface status
```

```
Up -- operational
```

```
Dn -- down
```

```
Instance: GOLD
```

```
Local site: CE1 (1)
```

connection-site	Type	St	Time last up	# Up trans
1	rmt	RN		
3	rmt	Up	Nov 16 11:22:44 2009	1
Remote PE: 192.0.2.3, Negotiated control-word: No				
Incoming label: 262147, Outgoing label: 262145				
Local interface: lsi.1048835, Status: Up, Encapsulation: VPLS				
Description: Intf - vpls GOLD local site 1 remote site 3				
5	rmt	Up	Nov 16 11:22:46 2009	1
Remote PE: 192.0.2.5, Negotiated control-word: No				
Incoming label: 262149, Outgoing label: 262161				

```
Local interface: lsi.1048836, Status: Up, Encapsulation: VPLS
Description: Intf - vpls GOLD local site 1 remote site 5
```

2. On Router PE2, use the `show vpls connections` command to verify that the VPLS connections to Router PE3 and Router PE5 are in the LN state, meaning the local router is not the designated forwarder. Router PE2 is configured to be the backup link for Router CE1.

```
user@PE2# show vpls connections
...

Instance: GOLD
Local site: CE1 (1)
  connection-site      Type  St    Time last up      # Up trans
  1                    rmt   LN
  3                    rmt   LN
  5                    rmt   LN
```

3. On Router PE3, use the `show vpls connections` command to verify that the VPLS connections to Router PE1 and Router PE5 are Up. Router PE3 is configured to be the primary link for Router CE3.

```
user@PE3# show vpls connections
...

Instance: GOLD
Local site: CE3 (3)
  connection-site      Type  St    Time last up      # Up trans
  1                    rmt   Up    Nov 16 11:22:01 2009      1
    Remote PE: 192.0.2.1, Negotiated control-word: No
    Incoming label: 262145, Outgoing label: 262147
    Local interface: lsi.1048832, Status: Up, Encapsulation: VPLS
    Description: Intf - vpls GOLD local site 3 remote site 1
  3                    rmt   RN
  5                    rmt   Up    Nov 16 11:22:56 2009      1
    Remote PE: 192.0.2.5, Negotiated control-word: No
    Incoming label: 262149, Outgoing label: 262163
    Local interface: lsi.1048834, Status: Up, Encapsulation: VPLS
    Description: Intf - vpls GOLD local site 3 remote site 5
```


4. On Router PE4, use the `show vpls connections` command to verify that the VPLS connections are in the LN state, meaning the local site is not designated. Router PE4 is configured to be the backup link for Router CE3.

```
user@PE4# show vpls connections
...

Instance: GOLD
  Local site: CE3 (3)
    connection-site      Type  St      Time last up      # Up trans
    1                    rmt   LN
    3                    rmt   SC
    5                    rmt   LN
```

5. On Router PE1, use the `show route advertising-protocol` command to verify that Router PE1 (the multihoming primary router) is sending the BGP Layer 2 VPN route advertisement to the route reflector with the local preference value of 65535. The local preference is used by Router PE3 to select Router PE1 as the designated forwarder, rather than selecting Router PE2 that has a local preference of 1.

```
user@PE1# show route advertising-protocol bgp 192.0.2.7 extensive
GOLD.l2vpn.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
* 192.0.2.1:1:1:1/96 (1 entry, 1 announced)
  BGP group to-RR type Internal
    Route Distinguisher: 192.0.2.1:1
    Label-base: 262145, range: 8
    Nexthop: Self
    Flags: Nexthop Change
    Localpref: 65535
    AS path: [65000] I
    Communities: target:65000:1 Layer2-info: encaps:VPLS, control flags:, mtu: 0, site
    preference: 65535
    PMSI: Flags 0:RSVP-TE:label[0:0:0]:Session_13[192.0.2.1:0:9519:192.0.2.1]
```

6. On Router PE2, use the `show route advertising-protocol` command to verify that Router PE2 is configured as the multihoming backup with a local preference of 1.

```
user@PE2# show route advertising-protocol bgp 192.0.2.7 extensive
GOLD.l2vpn.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
* 192.0.2.2:10:1:1/96 (1 entry, 1 announced)
```

```

BGP group to-RR type Internal
  Route Distinguisher: 192.0.2.2:10
  Label-base: 262145, range: 8
  Nexthop: Self
  Flags: Nexthop Change
Localpref: 1
  AS path: [65000] I
  Communities: target:65000:1 Layer2-info: encaps:VPLS, control flags:, mtu: 0, site
  preference: 1

```

7. On Router PE3, use the `show route receive-protocol` command to verify that Router PE3 receives the Layer 2 VPN route from the route reflector for Router PE1 and Router PE2 with different local preference values.

BGP route selection is based on the received l2vpn routes for the VPLS site connected to multihomed PE routers. Since the route distinguishers are different on Router PE1 and Router PE2, Router PE3 and Router PE4 consider the received routes from Router PE1 and Router PE2 as different routes. Router PE3 and Router PE4 run the BGP path selection algorithm and select Router PE1, the router advertising the route with the higher local preference value, as the designated forwarder.

```

user@PE3# show route receive-protocol bgp 192.0.2.7
bgp.l2vpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED    Lclpref    AS path
  192.0.2.1:1:1:1/96
*                   192.0.2.1                65535      I
  192.0.2.2:10:1:1/96
*                   192.0.2.2                1          I
  192.0.2.4:10:3:1/96
*                   192.0.2.4                1          I
  192.0.2.5:10:5:1/96
*                   192.0.2.5                100        I

GOLD.l2vpn.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
  Prefix                Nexthop          MED    Lclpref    AS path
  192.0.2.1:1:1:1/96
*                   192.0.2.1                65535      I
  192.0.2.2:10:1:1/96
*                   192.0.2.2                1          I
  192.0.2.4:10:3:1/96
*                   192.0.2.4                1          I

```

```

192.0.2.5:10:5:1/96
*                192.0.2.5                100        I

```

8. On Router PE3, use the `show route table` command to verify that Router PE3 has selected the static point-to-multipoint LSP from Router PE3 to Router PE1 for forwarding.

Notice that Router PE2 does not have any provider multicast service interface (PMSI) flags because PMSI attributes are not attached.

```

user@PE3# show route table GOLD.l2vpn.0 extensive
GOLD.l2vpn.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
192.0.2.1:1:1:1/96 (1 entry, 1 announced)
    *BGP      Preference: 170/-65536
              Route Distinguisher: 192.0.2.1:1
              PMSI: Flags 0:RSVP-TE:label[0:0:0]:Session_13[192.0.2.1:0:9519:192.0.2.1]
              Next hop type: Indirect
              Next-hop reference count: 4
              Source: 192.0.2.7
              Protocol next hop: 192.0.2.1
              Indirect next hop: 2 no-forward
              State: <Secondary Active Int Ext>
              Local AS: 65000 Peer AS: 65000
              Age: 2:30:44    Metric2: 1
              Task: BGP_65000.192.0.2.7+179
              Announcement bits (1): 0-GOLD-l2vpn
              AS path: I (Originator) Cluster list: 192.0.2.7
              AS path: Originator ID: 192.0.2.1
              Communities: target:65000:1 Layer2-info: encaps:VPLS, control flags:, mtu: 0,
site preference: 65535
              Import Accepted
              Label-base: 262145, range: 8
              Localpref: 65535
              Router ID: 192.0.2.7
              Primary Routing Table bgp.l2vpn.0
              Indirect next hops: 1
                  Protocol next hop: 192.0.2.1 Metric: 3
                  Indirect next hop: 2 no-forward
                  Indirect path forwarding next hops: 1
                      Next hop type: Router
                      Next hop: 10.10.8.2 via xe-0/1/0.0 weight 0x1
                  192.0.2.1/32 Originating RIB: inet.3
                      Metric: 3                      Node path count: 1

```

```

Forwarding nexthops: 1
Nexthop: 10.10.8.2 via xe-0/1/0.0

192.0.2.2:10:1:1/96 (1 entry, 1 announced)
  *BGP   Preference: 170/-2
        Route Distinguisher: 192.0.2.2:10
        Next hop type: Indirect
        Next-hop reference count: 3
        Source: 192.0.2.7
        Protocol next hop: 192.0.2.2
        Indirect next hop: 2 no-forward
        State: <Secondary Active Int Ext>
        Local AS: 65000 Peer AS: 65000
        Age: 2:30:44   Metric2: 1
        Task: BGP_65000.192.0.2.7+179
        Announcement bits (1): 0-GOLD-l2vpn
        AS path: I (Originator) Cluster list: 192.0.2.7
        AS path: Originator ID: 192.0.2.2
        Communities: target:65000:1 Layer2-info: encaps:VPLS, control flags:, mtu: 0,
site preference: 1
        Import Accepted
        Label-base: 262145, range: 8
        Localpref: 1
        Router ID: 192.0.2.7
        Primary Routing Table bgp.l2vpn.0
        Indirect next hops: 1
          Protocol next hop: 192.0.2.2 Metric: 3
          Indirect next hop: 2 no-forward
          Indirect path forwarding next hops: 1
            Next hop type: Router
            Next hop: 10.10.8.2 via xe-0/1/0.0 weight 0x1
          192.0.2.2/32 Originating RIB: inet.3
            Metric: 3                               Node path count: 1
            Forwarding nexthops: 1
              Nexthop: 10.10.8.2 via xe-0/1/0.0

```

9. On Router PE3, use the `show vpls connections` command to verify that the VPLS connection is in the Up state.

Notice the display also shows the local interface and the incoming and outgoing label values used.

```

user@PE3# show vpls connections extensive
...

Instance: GOLD
  Local site: CE3 (3)
    Number of local interfaces: 1
    Number of local interfaces up: 1
    IRB interface present: no
    ge-1/0/0.1
    lsi.1048832      1      Intf - vpls GOLD local site 3 remote site 1
    lsi.1048833      2      Intf - vpls GOLD local site 3 remote site 2
      Interface flags: VC-Down
    lsi.1048834      5      Intf - vpls GOLD local site 3 remote site 5
      Interface flags: VC-Down
    Label-base      Offset      Range      Preference
    262145           1          8          65535
    connection-site      Type      St      Time last up      # Up trans
    1                    rmt      Up      Nov 16 11:22:01 2009      1
      Remote PE: 192.0.2.1, Negotiated control-word: No
      Incoming label: 262145, Outgoing label: 262147
      Local interface: lsi.1048832, Status: Up, Encapsulation: VPLS
      Description: Intf - vpls GOLD local site 3 remote site 1
      RSVP-TE P2MP lsp:
        Egress branch LSP: 192.0.2.3:192.0.2.1:1:vpls:GOLD, State: Up
      Connection History:
        Nov 16 11:22:54 2009 PE route changed
        Nov 16 11:22:01 2009 status update timer
        Nov 16 11:22:01 2009 PE route changed
        Nov 16 11:22:01 2009 Out lbl Update      262147
        Nov 16 11:22:01 2009 In lbl Update      262145
        Nov 16 11:22:01 2009 loc intf up      lsi.1048832
        3                    rmt      RN
        5                    rmt      RD
      Ingress RSVP-TE P2MP LSP: vpls-GOLD, Flood next-hop ID: 616

```

Verifying the VPLS Data Plane

Step-by-Step Procedure

After the control plane is verified using the previous steps, you can verify the data plane. The data plane operation in the VPLS multihoming scenario is the same as the regular next-generation VPLS operation. This section describes the `show` command outputs that you can use to validate the data plane.

1. On Router PE3, use the `show mpls lsp` command to verify the state of the static LSPs and sub-LSPs.

Router PE2 is configured with static point-to-multipoint LSPs and sub-LSPs with link protection. Point to multipoint LSPs are not supported for single-hop LSPs. In the following output notice that the single-hop point-to-multipoint LSP from Router PE3 to Router PE4 is down.

```
user@PE3# show mpls lsp p2mp ingress
Ingress LSP: 1 sessions
P2MP name: vpls-GOLD, P2MP branch count: 4
To          From          State Rt P    ActivePath    LSPname
192.0.2.5   192.0.2.3   Up    0  *           to-pe5
192.0.2.1   192.0.2.3   Up    0  *           to-pe1
192.0.2.4   192.0.2.3   Dn    0  *           to-pe4
192.0.2.2   192.0.2.3   Up    0  *           to-pe2
Total 4 displayed, Up 3, Down 1
```

2. On Router PE1, use the `show mpls lsp` command to verify the state of the dynamic LSPs.

Router PE1 is using a dynamic point-to-multipoint LSP template configured with link protection. Notice that the LSP state is Up and that link protection is desired.

```
user@PE1# show mpls lsp p2mp ingress extensive
Ingress LSP: 1 sessions
P2MP name: 192.0.2.1:1:vpls:GOLD, P2MP branch count: 1

192.0.2.3
  From: 192.0.2.1, State: Up, ActiveRoute: 0, LSPname: 192.0.2.3:192.0.2.1:1:vpls:GOLD
  ActivePath: (primary)
  P2MP name: 192.0.2.1:1:vpls:GOLD
  Link protection desired
  LoadBalance: Random
  Encoding type: Packet, Switching type: Packet, GPID: IPv4
  *Primary          State: Up
  Priorities: 7 0
```

```

OptimizeTimer: 50
SmartOptimizeTimer: 180
Reoptimization in 45 second(s).
Computed ERO (S [L] denotes strict [loose] hops): (CSPF metric: 3)
10.10.3.2 S 10.10.9.2 S 10.10.8.1 S
  Received RRO (ProtectionFlag 1=Available 2=InUse 4=B/W 8=Node 10=SoftPreempt):
    10.10.3.2(Label=488645) 192.0.2.4(flag=0x21) 10.10.9.2(flag=1 Label=299936)
10.10.8.1(Label=262145)
  12 Nov 16 15:38:08.116 CSPF: computation result ignored[314 times]
  11 Nov 16 11:23:44.856 Link-protection Up
  10 Nov 16 11:23:32.696 CSPF: computation result ignored[3 times]
  9 Nov 16 11:22:47.859 Record Route: 10.10.3.2(Label=488645) 192.0.2.4(flag=0x21)
10.10.9.2(flag=1 Label=299936) 10.10.8.1(Label=262145)
  8 Nov 16 11:22:44.910 Record Route: 10.10.3.2(Label=488645) 192.0.2.4(flag=0x20)
10.10.9.2(Label=299936) 10.10.8.1(Label=262145)
  7 Nov 16 11:22:44.910 Up
  6 Nov 16 11:22:44.910 10.10.3.1: Down
  5 Nov 16 11:22:44.866 Selected as active path
  4 Nov 16 11:22:44.864 Record Route: 10.10.3.2(Label=488629) 192.0.2.4(flag=0x20)
10.10.9.2(Label=299920) 10.10.8.1(Label=3)
  3 Nov 16 11:22:44.864 Up
  2 Nov 16 11:22:44.852 Originate Call
  1 Nov 16 11:22:44.852 CSPF: computation result accepted 10.10.3.2 10.10.9.2 10.10.8.1
Created: Mon Nov 16 11:22:45 2009
Total 1 displayed, Up 1, Down 0

```

3. On Router PE3, use the `monitor interface traffic` command to verify the multicast replication behavior for the point-to-multipoint LSP on the designated forwarder Router PE3.

The output shows that 10,000 pps are received on interface `ge-1/0/0` from Router CE3. The traffic has been forwarded to the provider (P) Router P2 and Router PE4 through `xe-0/0/0` and `xe-0/1/0`, respectively. Based on the output, you can determine that a single copy of the packet is being sent to Router P2 and Router PE4.

```

user@PE3> monitor interface traffic
PE3                               Seconds: 8                               Time: 11:58:40

```

Interface	Link	Input packets	(pps)	Output packets	(pps)
lc-0/0/0	Up	0		0	
xe-0/0/0	Up	13570505	(0)	4507338866	(10000)
lc-0/1/0	Up	0		0	

xe-0/1/0	Up	292843	(1)	628972219	(10000)
lc-0/2/0	Up	0		0	
xe-0/2/0	Up	343292	(0)	206808	(1)
lc-0/3/0	Up	0		0	
xe-0/3/0	Down	0	(0)	0	(0)
ge-1/0/0	Up	2703709733	(9999)	13203544	(1)
lc-1/0/0	Up	0		0	
ge-1/0/1	Down	50380341937	(0)	60024542111	(0)
ge-1/0/2	Down	60652323068	(0)	84480825838	(0)
ge-1/0/3	Down	81219536264	(0)	84614255165	(0)
ge-1/0/4	Down	54379241112	(0)	83656815208	(0)

4. On Router P2, use the `monitor interface traffic` command to verify that the multicast packet replication happens close to the PE routers connected to the receivers.

Router PE1 and Router PE5 are connected to receivers that have joined this multicast group. Notice that incoming multicast packets from Router PE3 on the `ge-0/1/0` interface are replicated twice and sent out on the `ge-1/1/0` interface.

```
user@P2> monitor interface traffic
```

P2	Seconds: 6	Time: 12:07:58
----	------------	----------------

Interface	Link	Input packets	(pps)	Output packets	(pps)
ge-0/1/0	Up	661459806	(10000)	116236	(0)
ge-1/1/0	Up	115956	(0)	1322690473	(20000)
gr-2/1/0	Up	0	(0)	0	(0)
ip-2/1/0	Up	0	(0)	0	(0)

5. On Router PE3, use the `show vpls flood` command to verify information about the flood next-hop route.

Junos OS Release 9.0 and later identifies the flood next-hop route as a composite next hop. Notice that the interface is `ge-1/0/0.1`, the next-hop type is `composite`, and that the flood composition is `flood-to-all`. This means the traffic is flooded to all the PE routers.

```
user@PE3# show vpls flood extensive
```

Name: GOLD
CEs: 1
VEs: 1
Flood route prefix: 0x30002/51
Flood route type: FLOOD_GRP_COMP_NH

Flood route owner: __ves__

Flood group name: __ves__

Flood group index: 0

Nexthop type: comp

Nexthop index: 606

Flooding to:

Name	Type	NhType	Index
__all_ces__	Group	comp	603
Composition: split-horizon			
Flooding to:			
Name	Type	NhType	Index
ge-1/0/0.1	CE	ucst	578

Flood route prefix: 0x30003/51

Flood route type: FLOOD_GRP_COMP_NH

Flood route owner: __all_ces__

Flood group name: __all_ces__

Flood group index: 1

Nexthop type: comp

Nexthop index: 611

Flooding to:

Name	Type	NhType	Index
__ves__	Group	comp	594
Composition: flood-to-all			

Component p2mp NH (for all core facing interfaces):

Index

616

Flooding to:

Name	Type	NhType	Index
__all_ces__	Group	comp	603
Composition: split-horizon			
Flooding to:			
Name	Type	NhType	Index
ge-1/0/0.1	CE	ucst	578

Flood route prefix: 0x30001/51

Flood route type: FLOOD_GRP_COMP_NH

Flood route owner: __re_flood__

Flood group name: __re_flood__

Flood group index: 65534

Nexthop type: comp

Nexthop index: 598

Flooding to:

```

Name          Type          NhType      Index
__ves__       Group          comp        594
  Composition: flood-to-all
Component p2mp NH (for all core facing interfaces):
Index
616
Flooding to:
Name          Type          NhType      Index
__all_ces__   Group          comp        603
  Composition: split-horizon
  Flooding to:
    Name          Type          NhType      Index
    ge-1/0/0.1    CE            ucst        578
Name: __juniper_private1__
CEs: 0
VEs: 0

```

6. On Router PE3, use the `show vpls mac-table` command to verify that the MAC address of the PE router at the remote end of the VPLS has been learned and added to the MAC address table.

Notice that the MAC address is learned on the `ge-1/0/0.1` interface.

```

user@PE3# show vpls mac-table
MAC flags (S -static MAC, D -dynamic MAC,
          SE -Statistics enabled, NM -Non configured MAC)

Routing instance : GOLD
Bridging domain : __GOLD__, VLAN : NA
  MAC          MAC      Logical
  address      flags    interface
  00:14:f6:75:78:00  D      ge-1/0/0.1

```

7. On Router PE3, use the `show route forwarding-table family vpls vpn GOLD` command to verify that the forwarding table has the required entries with two labels: one for the VPLS service and the other for the next-hop interface.

```

user@PE3> show route forwarding-table family vpls vpn GOLD
Routing table: GOLD.vpls
VPLS:
Destination      Type RtRef Next hop          Type Index NhRef Netif
default          perm    0          dscd      574    1

```

lsi.1048832	intf	0	indr 1048575	4		
		10.10.7.1	Push 262147, Push 309680(top)	596	2	
xe-0/0/0.0						
lsi.1048836	intf	0	indr 1048574	4		
		10.10.7.1	Push 262179, Push 299856(top)	589	2	
xe-0/0/0.0						
00:10:db:e9:4e:b6/48						
	user	0	indr 1048574	4		
		10.10.7.1	Push 262179 , Push 299856 (top)	589	2	
xe-0/0/0.0						
00:12:1e:c6:98:00/48						
	user	0	indr 1048575	4		
		10.10.7.1	Push 262147, Push 309680(top)	596	2	
xe-0/0/0.0						
00:14:f6:75:78:00/48						
	user	0	ucst	578	4	ge-1/0/0.1
0x30002/51	user	0	comp	606	2	
ge-1/0/0.1	intf	0	ucst	578	4	ge-1/0/0.1
0x30003/51	user	0	comp	611	2	
0x30001/51	user	0	comp	598	2	

Results

The configuration and verification parts of this example have been completed. The following section is for your reference.

The relevant sample configuration for Router PE1 follows:

Router PE1

```
chassis {
  dump-on-panic;
  fpc 1 {
    pic 3 {
      tunnel-services {
        bandwidth 1g;
      }
    }
  }
  network-services ethernet;
}
interfaces {
```

```

xe-0/1/0 {
    unit 0 {
        family inet {
            address 10.10.2.1/30;
        }
        family mpls;
    }
}
xe-0/2/0 {
    unit 0 {
        family inet {
            address 10.10.3.1/30;
        }
        family mpls;
    }
}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.1/30;
        }
        family mpls;
    }
}
ge-1/0/0 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 1 {
        encapsulation vlan-vpls;
        vlan-id 1000;
        family vpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/32;
        }
    }
}
}
routing-options {
    static {

```

```

        route 172.0.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    rsvp {
        interface all;
        interface fxp0.0 {
            disable;
        }
        interface xe-0/3/0.0 {
            link-protection;
        }
        interface xe-0/2/0.0 {
            link-protection;
        }
        interface xe-0/1/0.0 {
            link-protection;
        }
    }
}
mpls {
    label-switched-path to-RR {
        to 192.0.2.7;
    }
    label-switched-path vpls-GOLD-p2mp-template {
        template;
        optimize-timer 50;
        link-protection;
        p2mp;
    }
    label-switched-path to-PE2 {
        to 192.0.2.2;
    }
    label-switched-path to-PE3 {
        to 192.0.2.3;
    }
    label-switched-path to-PE4 {
        to 192.0.2.4;
    }
    label-switched-path to-PE5 {
        to 192.0.2.5;
    }
    interface all;

```

```

        interface fxp0.0 {
            disable;
        }
    }
    bgp {
        group to-RR {
            type internal;
            local-address 192.0.2.1;
            family l2vpn {
                signaling;
            }
            neighbor 192.0.2.7;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface all;
            interface fxp0.0 {
                disable;
            }
        }
    }
}

routing-instances {
    GOLD {
        instance-type vpls;
        interface ge-1/0/0.1;
        route-distinguisher 192.0.2.1:1;
        provider-tunnel {
            rsvp-te {
                label-switched-path-template {
                    vpls-GOLD-p2mp-template;
                }
            }
        }
        vrf-target target:65000:1;
        protocols {
            vpls {
                site-range 8;
                no-tunnel-services;
                site CE1 {
                    site-identifier 1;

```

```

        multi-homing;
        site-preference primary;
        interface ge-1/0/0.1;
    }
}
}
}
}
}
}
}

```

The relevant sample configuration for Router PE2 follows.

PE2 Router

```

chassis {
    dump-on-panic;
    fpc 1 {
        pic 3 {
            tunnel-services {
                bandwidth 1g;
            }
        }
    }
    network-services ethernet;
}
interfaces {
    xe-0/1/0 {
        unit 0 {
            family inet {
                address 10.10.2.2/30;
            }
            family mpls;
        }
    }
    xe-0/2/0 {
        unit 0 {
            family inet {
                address 10.10.5.1/30;
            }
            family mpls;
        }
    }
    xe-0/3/0 {

```

```

    unit 0 {
        family inet {
            address 10.10.4.1/30;
        }
        family mpls;
    }
}
ge-1/0/3 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 1 {
        encapsulation vlan-vpls;
        vlan-id 1000;
        family vpls;
    }
}
fxp0 {
    apply-groups [ re0 re1 ];
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/32;
        }
    }
}
}
routing-options {
    static {
        route 172.0.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    rsvp {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    mpls {
        label-switched-path to-RR {
            to 192.0.2.7;

```



```

    }
    label-switched-path vpls-GOLD-p2mp-template {
        template;
        optimize-timer 50;
        link-protection;
        p2mp;
    }
    label-switched-path to-PE1 {
        to 192.0.2.1;
    }
    label-switched-path to-PE3 {
        to 192.0.2.3;
    }
    label-switched-path to-PE4 {
        to 192.0.2.4;
    }
    label-switched-path to-PE5 {
        to 192.0.2.5;
    }
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    group to-RR {
        type internal;
        local-address 192.0.2.2;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
}

```

```

}
routing-instances {
  GOLD {
    instance-type vpls;
    interface ge-1/0/3.1;
    route-distinguisher 192.0.2.2:10;
    provider-tunnel {
      rsvp-te {
        label-switched-path-template {
          vpls-GOLD-p2mp-template;
        }
      }
    }
  }
  vrf-target target:65000:1;
  protocols {
    vpls {
      site-range 8;
      no-tunnel-services;
      site CE1 {
        site-identifier 1;
        multi-homing;
        site-preference backup;
        interface ge-1/0/3.1;
      }
    }
  }
}

```

RELATED DOCUMENTATION

[Example: NG-VPLS Using Point-to-Multipoint LSPs | 1030](#)

[Next-Generation VPLS Point-to-Multipoint Forwarding Overview | 1024](#)

[Next-Generation VPLS for Multicast with Multihoming Overview | 991](#)

Configuring Point-to-Multipoint LSPs

IN THIS CHAPTER

- [Next-Generation VPLS Point-to-Multipoint Forwarding Overview | 1024](#)
- [Example: NG-VPLS Using Point-to-Multipoint LSPs | 1030](#)
- [Flooding Unknown Traffic Using Point-to-Multipoint LSPs in VPLS | 1073](#)
- [Example: Configuring Ingress Replication for IP Multicast Using MBGP MVPNs | 1078](#)
- [Mapping VPLS Traffic to Specific LSPs | 1096](#)

Next-Generation VPLS Point-to-Multipoint Forwarding Overview

IN THIS SECTION

- [Next-Generation VPLS Point-to-Multipoint Forwarding Applications | 1025](#)
- [Implementation | 1029](#)

VPLS is a Layer 2 solution for efficiently sending multicast traffic over a multiprotocol label switching (MPLS) core.

VPLS emulates the broadcast domain of a LAN across an MPLS network cloud. Traditional MPLS implementations of VPLS require that all participating ingress provider edge (PE) routers make separate copies of each broadcast or multicast packet to send to all other PE routers that are part of the VPLS site for the same extended LAN. In a large virtual private network (VPN), replication overhead can be significant for each ingress router and its attached core-facing links.

Juniper Networks has several important VPLS enhancements that provide a solution for the replication overhead issue:

- Point-to-multipoint LSP support provides efficient distribution of multicast traffic such as IP-based television (IPTV).

- Multihoming support integrates the path selection capability of BGP with VPLS to allow a customer edge (CE) Ethernet switch to have a backup path across the network.

This document explains the use of point-to-multipoint LSPs in the MPLS core as an alternative to ingress replication. Point-to-multipoint LSPs enable ingress routers to send only one copy of each packet into the MPLS cloud. Each PE router maintains a point-to-multipoint tree so traffic can be efficiently sent to all VPN sites. This process requires the fewest possible replications of the packets and does the replication at the most optimal points in the network.

The benefits of this approach are:

- Conservation of bandwidth
- Increased PE router efficiency
- Improved traffic engineering for flows of flooded traffic
- Manual control or several levels of automatic operation
- Simplified multicast optimization, which is ideal for IPTV or network access wholesale

The Internet Engineering Task Force (IETF) supports two standardized VPLS implementations: *RFC 4761: Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling* and *RFC 4762: Virtual Private LAN Service (VPLS) Using LDP Signaling*.

Juniper Networks has implemented VPLS solutions based on both RFCs. BGP-based VPLS is the superior solution, but LDP-based VPLS is supported for those service providers that have already deployed this alternative.

For a detailed technology overview of LDP-BGP VPLS interworking see *LDP-BGP VPLS Interworking at* <https://www.juniper.net/us/en/local/pdf/whitepapers/2000282-en.pdf>.

Next-Generation VPLS Point-to-Multipoint Forwarding Applications

VPLS provides a multipoint-to-multipoint Ethernet service that can span one or more metro areas and provides connectivity between multiple sites as if these sites were attached to the same Ethernet LAN.

VPLS uses an IP and MPLS service provider infrastructure. From a service provider's point of view, use of IP and MPLS routing protocols and procedures instead of the Spanning Tree Protocol (STP), and MPLS labels instead of VLAN IDs, significantly improves the scalability of the VPLS service.

VPLS Protocol Operation

VPLS carries Ethernet traffic across a service provider network, so it must mimic an Ethernet network in some ways. When a PE router configured with a VPLS routing instance receives a packet from a CE device, it first determines whether it knows the destination of the VPLS packet. If it does, it forwards the packet to the appropriate PE router or CE device. If it does not, it broadcasts the packet to all the other

PE routers and CE devices that are members of that VPLS routing instance. In both cases, the CE device receiving the packet must be different from the one sending the packet.

When a PE router receives a packet from another PE router, it first determines whether it knows the destination of the VPLS packet. If the destination is known, the PE router either forwards the packet or drops it, depending on whether the destination is a local or remote CE device. The PE router has three options (scenarios):

- If the destination is a local CE device, the PE router forwards the packet to it.
- If the destination is a remote CE device (connected to another PE router), it discards the packet.
- If it cannot determine the destination of the VPLS packet, the PE router floods it to its attached CE devices.

A VPLS can be directly connected to an Ethernet switch. Layer 2 information gathered by an Ethernet switch, such as media access control (MAC) addresses and interface ports, is included in the VPLS routing instance table. However, instead of all VPLS interfaces being physical switch ports, the router allows remote traffic for a VPLS instance to be delivered across an MPLS LSP and arrive on a virtual port. The virtual port emulates a local, physical port. Traffic can be learned, forwarded, or flooded to the virtual port in almost the same way as traffic sent to a local port.

The VPLS routing table is populated with MAC addresses and interface information for both physical and virtual ports. One difference between a physical port and a virtual port is that on a virtual port, the router captures the outgoing MPLS label used to reach the remote site and an incoming MPLS label for VPLS traffic received from the remote site. The virtual port is generated dynamically on a Tunnel Services PIC when you configure VPLS on a Juniper Networks M Series Multiservice Edge Router or T Series Core Router. A Tunnel Services PIC is required on each M Series or T Series VPLS router.

If your router has an Enhanced FPC installed, you can configure VPLS without a Tunnel Services PIC. To do so, you use a label-switched interface (LSI) to provide VPLS functionality. An LSI MPLS label is used as the inner label for VPLS. This label maps to a VPLS routing instance. On the PE router, the LSI label is stripped and then mapped to a logical LSI interface. The Layer 2 Ethernet frame is then forwarded using the LSI interface to the correct VPLS routing instance. To configure VPLS on a router without a Tunnel Services PIC, include the `no-tunnel-services` statement.

One restriction on flooding behavior in VPLS is that traffic received from remote PE routers is never forwarded to other PE routers. This restriction helps prevent loops in the core network. This also means that the core network of PE routers must be fully meshed. Additionally, if a CE Ethernet switch has two or more connections to the same PE router, you must enable the Spanning Tree Protocol (STP) on the CE switch to prevent loops.

Point-to-Multipoint Implementation

In next-generation VPLS, point-to-multipoint LSPs are used to flood broadcast, multicast, and unknown unicast traffic across a VPLS core network to all the PE routers. This is more efficient in terms of bandwidth utilization between the PE router and provider (P) router.

If point-to-multipoint LSPs are not being used, the PE router needs to forward multiple copies of broadcast, multicast, and unknown unicast packets to all PE routers. If point-to-multipoint LSPs are used, the PE router floods one copy of each packet to the P router, where it is replicated close to the egress router.

NOTE: For next-generation VPLS, both point-to-point LSPs and point-to-multipoint LSPs are needed between the PE routers.

In VPLS, point-to-multipoint LSPs are only used to transport broadcast frames, multicast frames, and unicast frames with an unknown destination MAC address. All other frames are still transported using point-to-point LSPs. This structure is much more efficient for bandwidth use, particularly near the source of the broadcast, multicast, and unknown frames. However, it also results in more state in the network because each PE router is the ingress of one point-to-multipoint LSP that touches all other PE routers and one point-to-point LSP going to each of the other PE routers.

Enabling point-to-multipoint LSPs for any VPLS instance starts the flooding of unknown-unicast, broadcast, and multicast traffic using point-to-multipoint LSPs.

For each VPLS instance, a PE router creates a dedicated point-to-multipoint LSP. Whenever VPLS discovers a new neighbor through BGP, a source-to-leaf sub-LSP is added for this neighbor in the point-to-multipoint LSP instance.

If there are n PE routers in the VPLS instance, then the discovery of a new neighbor through BGP creates n point-to-multipoint LSPs in the network, where each PE router is the root of the tree and the rest of the $n-1$ PE routers are leaf nodes (or source-to-leaf sub-LSPs).

Each point-to-multipoint LSP created by PE routers can be identified using an RSVP-traffic engineering point-to-multipoint session object, which is passed as a provider multicast service interface (PMSI) tunnel attribute by BGP while advertising VPLS routes. Using this tunnel attribute, incoming source-to-leaf sub-LSP add request messages (RSVP-path message) can be associated with the right VPLS instance and originator PE router. As a result, label allocation is done in such a way that when traffic arrives on the LSP, it is not only terminated on the right VPLS instance, but the originator PE router is also identified so that source MAC addresses can be learned.

Point-to-multipoint LSPs can be enabled incrementally on any PE router that is part of a specific VPLS instance. This means a PE router that has this feature uses point-to-multipoint LSPs to flood traffic, whereas other PE routers in the same VPLS instance can use ingress replication to flood the traffic. However, when point-to-multipoint LSPs are enabled on any PE router, make sure that all the PE routers that are part of the same VPLS instance also support this feature.

NOTE: Penultimate-hop popping (PHP) is disabled for point-to-multipoint LSPs terminating in a VPLS instance.

Limitations of Point-to-Multipoint LSPs

When implementing point-to-multipoint LSPs remember the following limitations:

- There is no mechanism to allow only multicast traffic to go over the point-to-multipoint LSP.
- Point-to-multipoint LSPs do not support inter-AS traffic. Only intra-AS traffic is supported.
- Point-to-multipoint LSPs do not support graceful restart for ingress LSPs. This also affects VPLS when flooding is done using point-to-multipoint LSPs.
- The same point-to-multipoint LSP cannot be shared across multiple VPLS instances.
- When this feature is enabled, ingress PE routers use only point-to-multipoint LSPs for flooding. The router initiates the creation of source-to-leaf sub-LSPs for each PE router that is part of the same VPLS instance. Any PE router for which this source-to-leaf sub-LSP fails to come up does not receive any flooded traffic from the ingress PE router.
- It is possible that flooding of unknown unicast traffic over point-to-multipoint LSPs may lead to packet reordering, because as soon as learning is done, unicast traffic is sent out using point-to-point pseudowire LSPs.
- Static LSPs and LSPs configured using the `label-switched-path-template` statement cannot be configured at the same time.
- When an LSP is configured using the `static-lsp` statement, a point-to-multipoint LSP is created statically to include all neighbors in the VPLS instance.

Before enabling the point-to-multipoint LSP feature on any PE router, make sure that all the other PE routers that are part of the same VPLS instance are upgraded to a Junos OS Release that supports it. If a router in the VPLS instance does not support point-to-multipoint LSPs, it may lose all the traffic sent on the point-to-multipoint LSP. Therefore, do not enable this feature if there is a single router in a VPLS instance that is not capable of supporting this feature, either because it is not running the appropriate Junos OS Release or because it is a router from a vendor that does not support this feature.

Simultaneous Transit and Egress Router Operation

A PE router that plays the role of both an MPLS transit router and an MPLS egress router can do so by receiving either one or two copies of a packet to fulfill each of its roles.

To fulfill both roles while using only a single copy of a packet, Juniper Networks M Series and T Series routers require a Tunnel Services PIC configured with virtual tunnel (vt) interfaces and ultimate-hop

popping must be enabled. With a virtual tunnel interface and ultimate-hop popping, a single copy of the received packet is forwarded beyond the PE router to fulfill the transit router role and is also consumed internally by the virtual tunnel interface to fulfill the egress router role.


If a label-switched interface (LSI) *logical interface* is used, then two copies of each packet must be received on the point-to-multipoint LSP, one to fulfill the transit router role and one to fulfill the egress router role.

Implementation

Some implementations of VPLS use ingress replication. Ingress replication is simple but inefficient. It sends multiple copies of the same packet on a link, especially the PE-P link. This causes wasted bandwidth when there is a heavy broadcast and multicast traffic.

As shown in the sample network in [Figure 74 on page 1029](#) the ingress PE router makes three copies of every broadcast, multicast, and flooded packet for each VPLS instance.

Figure 74: Ingress Replication




[Figure 75 on page 1030](#) shows how a point-to-multipoint LSP works for multicast.

In a VPLS using point-to-multipoint LSPs, the ingress PE router sends a single copy of the multicast packet to Router P1. Router P1 makes two copies for this point-to-multipoint LSP. Each of the other P

routers also makes multiple copies of the packet. This moves replication closer to the endpoints and results in significant improvements in the network bandwidth utilization.

Figure 75: Point-to-Multipoint Replication



RELATED DOCUMENTATION

[Example: NG-VPLS Using Point-to-Multipoint LSPs | 1030](#)

Example: NG-VPLS Using Point-to-Multipoint LSPs

IN THIS SECTION

- [Requirements | 1031](#)
- [Overview and Topology | 1032](#)
- [Configuration | 1034](#)

This example shows how to configure next-generation VPLS (NG_VPLS) using point-to-multipoint LSPs. The topology is shown in [Figure 76 on page 1032](#) and [Figure 77 on page 1033](#). This example is organized in the following sections:

Requirements

[Table 24 on page 1031](#) lists the hardware that is used and the software that is required for this example:


Table 24: Hardware and Software Used

Equipment	Components	Software
Six MX Series 5G Universal Routing Platforms	DPC-4 10GE-X, DPC-40 1GE-X	Junos OS Release 9.3R4 or later
One T Series Core Router	FPC3, 10GE-Xenpak	Junos OS Release 9.3R4 or later
Eight EX4200 Ethernet Switches	EX4200 virtual switches	Junos OS Release 9.3R4 or later
One M7i Multiservice Edge Router	Gigabit Ethernet interfaces	Junos OS Release 9.3R4 or later

Overview and Topology

The logical topology of the NG-VPLS example is shown in [Figure 76 on page 1032](#).

Figure 76: Logical Topology of NG-VPLS Using Point-to-Multipoint LSPs




The routers in this example are preconfigured with the following:

- OSPF area 0 is configured on all the PE routers and P routers with traffic engineering enabled.
- All of the core-facing interfaces are configured with the `mpls` protocol address family.
- The RSVP and MPLS protocols are enabled for all the core-facing interfaces.
- All the MX Series routers have their network services mode set to Ethernet. The network services mode is configured by including the `network-services` statement and specifying the `ethernet` option.
- All the PE routers are configured for autonomous system 65000.

The physical topology of the NG-VPLS example is shown in [Figure 77 on page 1033](#). The topology consists of six MX Series routers connected with redundant links in the core. Four MX Series routers are acting as PE routers and two are core routers.

Figure 77: Physical Topology of NG-VPLS Using Point-to-Multipoint LSPs



Note the following topology details:

- A route reflector is configured in the topology to reflect the family 12-vpn routes to all the PE routers for BPG-VPLS.
- The GOLD VPLS routing instance is configured with two sites in each of the PE routers.
- One GOLD site is connected to the CE router and the other one is directly connected to the test equipment on each PE router.

- The `no-tunnel-services` statement is included in the GOLD VPLS instance to enable the use of LSI interfaces for VPLS tunnel services.
- Router CE1 and Router CE2 are EX Series Virtual Chassis switches acting as CE routers.
- Router CE3 is an M7i router acting as a CE router.
- Two multicast sources are configured. One is connected to Router CE1 (Site 1) and the other to Router PE2 (Site 4) to simulate different scenarios.
- Router CE1 is configured as the rendezvous point (RP).
- Unicast traffic is enabled on all the test equipment ports and is sent to all the sites in the GOLD VPLS instance.

Configuration

IN THIS SECTION

- [Configuring the PE Router Interfaces | 1035](#)
- [Configuring a Route Reflector for all PE Routers for BGP-Based VPLS | 1037](#)
- [Establishing BGP-Based VPLS with a Route Reflector | 1038](#)
- [Configuring Point-to-Point LSPs Between PE Routers | 1039](#)
- [Configuring Dynamic and Static Point-to-Multipoint LSPs Between PE Routers | 1040](#)
- [Configuring Point-to-Multipoint Link Protection | 1042](#)
- [Configuring a BGP-Based VPLS Routing Instance for NG-VPLS | 1043](#)
- [Configuring Tunnel Services for VPLS | 1046](#)
- [Verifying the Control Plane | 1048](#)
- [Verifying the Data Plane | 1058](#)
- [Results | 1065](#)

This example shows how to configure next-generation VPLS using point-to-multipoint LSPs. It is organized in the following sections:

Configuring the PE Router Interfaces

Step-by-Step Procedure

On the customer-facing PE interfaces, enable VLAN tagging, configure the encapsulation type, and enable the VPLS address family. There are four possible interface encapsulations for VPLS routing instances that you can choose depending on your needs.

1. If your network requires that each logical interface on the PE router-to-CE router link be configured to only accept packets with VLAN ID 1000, include the `vlan-tagging` statement, include the `encapsulation` statement, and specify `vlan-vpls` as the encapsulation type. Also include the `vlan-id` statement and specify 1000 as the VLAN ID.

```
[edit interfaces]
ge-1/1/0 {
  vlan-tagging;
  encapsulation vlan-vpls;
  unit 1 {
    encapsulation vlan-vpls;
    vlan-id 1000;
    family vpls;
  }
}
```

With this configuration, you can configure multiple logical interfaces with different VLAN IDs and associate each logical interface with a different routing instance.

2. If your network requires each physical interface on the PE router to CE router link to be configured to use the entire Ethernet port as part of a single VPLS instance, include the `encapsulation` statement, and specify `ethernet-vpls` as the encapsulation type.

```
[edit interfaces]
ge-1/2/0 {
  encapsulation ethernet-vpls;
  unit 0 {
    family vpls;
  }
}
```

With this encapsulation mode, you cannot create multiple logical units (VLANs).

3. If your network requires that each logical interface of the single physical interface on the PE router to CE router link be configured to use a mix of different encapsulations, include the encapsulation statement, and specify flexible-ethernet-services as the encapsulation type at the [edit interfaces *interface-name*] hierarchy level. Also include the encapsulation statement, and specify vlan-vpls or vlan-ccc as the encapsulation type at the [edit interfaces *interface-name* unit *logical-unit-number*] hierarchy level.

```
[edit interfaces]
ge-1/2/0 {
  vlan-tagging;
  encapsulation flexible-ethernet-services;
  unit 1 {
    encapsulation vlan-vpls;
  }
  unit 2 {
    encapsulation vlan-ccc;
  }
}
```

4. If your network requires support for using a mix of single and dual tagged VLANs configured in different logical interfaces on a single physical interface, include the encapsulation statement, and specify flexible-vlan-tagging as the encapsulation type.
5. Configure the core-facing CE router interfaces. The CE router and PE router logical interface configuration must match encapsulation types and VLAN IDs. Typically the IP address is configured on the core-facing CE router interfaces if the CE device is a router and terminates the Layer 2 domain into the Layer 3 network. In this example, the interface is configured for single tagging with a VLAN ID of 1000.

```
[edit interfaces]
ge-1/1/0 {
  vlan-tagging;
  unit 1 {
    vlan-id 1000;
    family inet {
      address 198.51.100.4/24;
    }
  }
}
```

Configuring a Route Reflector for all PE Routers for BGP-Based VPLS

Step-by-Step Procedure

Configuring a route reflector is the preferred method to enable any BGP-based service offerings. Configuring a route reflector avoids the requirement for a full mesh of BGP peer sessions, and it scales well. BGP redundancy can be achieved using multiple route reflectors in a single cluster.

1. To enable BGP to carry Layer 2 VPN and VPLS NLRI messages, create a peer group, include the `family` statement, specify the `l2vpn` option, and include the `signaling` statement. To configure the route reflector cluster and complete the BGP peer sessions, include the `cluster` statement and specify the IP address for the cluster ID. Then include the `neighbor` statement and specify the IP address of the PE routers that are BGP client peers in the cluster.

```
[edit protocols]
bgp {
  group RR {
    type internal;
    local-address 192.0.2.7;
    family l2vpn {
      signaling;
    }
    cluster 192.0.2.7;
    neighbor 192.0.2.1; # To PE1
    neighbor 192.0.2.2; # To PE2
    neighbor 192.0.2.3; # To PE3
    neighbor 192.0.2.4; # To PE4
  }
}
```

2. Configure OSPF and enable traffic engineering on the route reflector to create the Constrained Shortest Path First (CSPF) database for the egress LSPs terminating from the PE routers.

```
[edit protocols]
ospf {
  traffic-engineering;
  area 0.0.0.0 {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
}
```



```

    }
}

```

3. Enable the MPLS and RSVP protocols on all interfaces connected to the MPLS core. This terminates the RSVP egress LSPs from the PE routers.

```

[edit protocols]
rsvp {
  interface all;
  interface fxp0.0 {
    disable;
  }
}
mpls {
  interface all;
  interface fxp0.0 {
    disable;
  }
}

```

Establishing BGP-Based VPLS with a Route Reflector

Step-by-Step Procedure

For BGP-based VPLS, all PE routers need to have a full mesh of BGP peer sessions with each other or have a single peer with the route reflector. The route reflector reflects the routes received from the other PE routers. In this example, the PE router is configured to establish a peer relationship with the route reflector.

1. To have all the PE routers establish a BGP client peer session with the route reflector, create an internal peer group, include the `local-address` statement, and specify the IP address of the PE router. Also include the `neighbor` statement, and specify the IP address of the route reflector. To enable BGP to carry Layer 2 VPN and VPLS NLRI messages, include the `family` statement, specify the `l2vpn` option, and include the `signaling` statement.

```

[edit protocols]
bgp {
  group to-RR {
    type internal;
    local-address 192.0.2.1;

```

```

        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7; # To the route reflector
    }
}

```

2. Configure a point-to-point RSVP LSP from the PE routers to the route reflector. To create the LSP, include the `label-switched-path` statement, give the LSP a meaningful name, include the `to` statement and specify the IP address of the route reflector as the LSP end point. This LSP is needed to resolve the BGP next hops in the `inet.3` routing table for the routes received from the route-reflector.

```

[edit protocols]
mpls {
    label-switched-path to-RR {
        to 192.0.2.7;
    }
    interface all;
    interface fxp0.0 {
        disable;
    }
}

```

Configuring Point-to-Point LSPs Between PE Routers

Step-by-Step Procedure

In next-generation VPLS, point-to-multipoint LSPs are only used to transport broadcast, multicast, and unknown unicast frames. All other frames are still transported using point-to-point RSVP LSPs. This is a more efficient use of bandwidth, particularly near the source of the unknown, broadcast, and multicast frames. The trade-off is more state in the network, because each PE router is the ingress of one point-to-multipoint LSP that touches all other PE routers, and n point-to-point LSPs are needed, one going to each of the other PE routers.

1. To create a point-to-point LSP, include the `label-switched-path` statement, give the LSP a meaningful name, include the `to` statement, and specify the IP address of the other PE router as the LSP

endpoint. The example shows the configuration of LSPs from Router PE1 to Routers PE2, PE3, and PE4.

```
[edit protocols]
mpls {
  label-switched-path to-PE2 {
    to 192.0.2.2;
  }
  label-switched-path to-PE3 {
    to 192.0.2.3;
  }
  label-switched-path to-PE4 {
    to 192.0.2.4;
  }
}
```

Configuring Dynamic and Static Point-to-Multipoint LSPs Between PE Routers

Step-by-Step Procedure

This procedure describes how to enable the creation of dynamic point-to-multipoint LSPs and how to configure static point-to-multipoint LSPs. On a router configured with static point-to-multipoint LSPs, the LSPs come up immediately. On a router configured with dynamic point-to-multipoint LSPs, the LSP comes up only after receiving BGP neighbor information from the route reflector or from the other PE routers participating in the VPLS domain.

For each VPLS instance, a PE router with dynamic point-to-multipoint LSPs enabled creates a dedicated point-to-multipoint LSP based on the point-to-multipoint template. Whenever VPLS discovers a new neighbor through BGP, a sub-LSP for this neighbor is added to the point-to-multipoint LSP.

If there are n PE routers in the VPLS instance then the router creates n point-to-multipoint LSPs in the network where each PE router is the root of the tree and includes the rest of the $n-1$ PE routers as leaf nodes connected through a source-to-leaf sub-LSP.

1. In this step, you configure Router PE1 and Router PE2 to use a dynamic point-to-multipoint LSP template for LSP creation. When these routers receive a new BGP route advertised from the route reflector for a new neighbor, they create a point-to-multipoint sub-LSP to that neighbor. To create the dynamic point-to-multipoint LSP template, include the `label-switched-path` statement, give the LSP

template a meaningful name, include the `template` statement and include the `p2mp` statement. Also enable link protection and configure the optimize timer to periodically reoptimize the LSP path.

```
[edit protocols]
mpls {
  label-switched-path vpls-GOLD-p2mp-template {
    template; # identify as a template
    optimize-timer 50;
    link-protection; # link protection is enabled on point-to-multipoint LSPs
    p2mp;
  }
}
```

2. In this step, you configure static point-to-multipoint LSPs. Creating static point-to-multipoint LSPs is similar to creating point-to-point LSPs, except you can also configure other RSVP parameters under each point-to-multipoint LSP.

To create static point-to-multipoint LSPs, include the `label-switched-path` statement, give the LSP a meaningful name, include the `to` statement, and specify the IP address of the PE router that is the endpoint of the LSP. Also include the `p2mp` statement and specify a pathname.

```
[edit protocols]
mpls {
  label-switched-path to-pe2 {
    to 192.0.2.2;
    p2mp vpls-GOLD;
  }
  label-switched-path to-pe3 {
    to 192.0.2.3;
    p2mp vpls-GOLD;
  }
  label-switched-path to-pe1 {
    to 192.0.2.1;
    p2mp vpls-GOLD;
  }
}
```

Configuring Point-to-Multipoint Link Protection

Step-by-Step Procedure

Point-to-multipoint LSPs only support RSVP link protection for traffic engineering. Node protection is not supported. Link protection is optional, but it is the recommended configuration for most networks.

1. To enable link protection on the core-facing interfaces, include the `link-protection` statement at the `[edit protocols rsvp interface interface-name]` hierarchy level.

```
[edit protocols]
rsvp {
  interface all;
  interface fxp0.0 {
    disable;
  }
  interface xe-0/3/0.0 {
    link-protection;
  }
  interface xe-0/2/0.0 {
    link-protection;
  }
  interface xe-0/1/0.0 {
    link-protection;
  }
}
```

2. Enable the point-to-multipoint LSP to use the RSVP link protection feature. Link-protection can be configured for both static point-to-multipoint and dynamic point-to-multipoint LSPs that use a template.

For static point-to-multipoint LSPs, configure each branch sub-LSP. To enable link protection, include the `link-protection` statement at the `[edit protocols mpls label-switched-path label-switched-path-name]` hierarchy level.

```
[edit protocols mpls label-switched-path]
label-switched-path to-pe2 {
  to 192.0.2.2;
  link-protection;
  p2mp vpls-GOLD;
}
label-switched-path to-pe3 {
```

```

        to 192.0.2.3;
        link-protection;
        p2mp vpls-GOLD;
    }
    label-switched-path to-pe1 {
        to 192.0.2.1;
        link-protection;
        p2mp vpls-GOLD;
    }

```

3. For dynamic point-to-multipoint LSPs using a template, only the template needs to have link protection configured. All the point-to-multipoint branch LSPs that use the template inherit this configuration.

To enable link protection for dynamic point-to-multipoint LSPs, include the `link-protection` statement at the `[edit protocols mpls label-switched-path label-switched-path-name]` hierarchy level.

```

[edit protocols mpls label-switched-path]
label-switched-path vpls-GOLD-p2mp-template {
    template;
    optimize-timer 50;
    link-protection;
    p2mp;
}

```

Configuring a BGP-Based VPLS Routing Instance for NG-VPLS

Step-by-Step Procedure

For NG-VPLS, the routing-instance configuration is similar to that for a regular VPLS routing instance. The routing instance defines the VPLS site and creates the VPLS connection. The following parameters are configured.

- Instance Type – VPLS.
- Interface – The interface connecting to the CE router.
- Route Distinguisher – Each routing instance you configure on a PE router must have a unique route distinguisher. The route distinguisher is used by BGP to distinguish between potentially identical network reachability information (NLRI) messages received from different VPNs. We recommend that you use a unique route distinguisher for each routing instance on each PE so that you can determine which PE originated the route.

- VRF Target – Configuring a VRF target community using the `vrf-target` statement causes default VRF import and export policies to be generated that accept imported routes and tag exported routes with the specified target community.
 - Protocols – Configure the VPLS protocol as described in the following procedure.
1. To configure the NG-VPLS routing instance, include the `routing-instances` statement and specify the instance name. Also include the `instance-type` statement and specify `vpls` as the type. Include the `route-distinguisher` statement and specify a route distinguisher that is unique throughout all VPNs configured on the router. Configure a VRF route target by including the `vrf-target` statement and specify the route target. The route target exported by one router must match the route target imported by another router for the same VPLS.

```
[edit]
routing-instances {
  GOLD {
    instance-type vpls;
    interface ge-1/0/0.1;
    interface ge-1/1/0.1;
    route-distinguisher 192.0.2.1:1;
    vrf-target target:65000:1;
  }
}
```

2. To use a point-to-multipoint LSP for VPLS flooding, configure an LSP under the VPLS routing instance.

To configure the point-to-multipoint LSP for VPLS flooding, include the `label-switched-path-template` statement and specify the name of the LSP template at the `[edit routing-instances routing-instances-name provider-tunnel rsvp-te]` hierarchy level.

```
[edit]
routing-instances {
  GOLD {
    instance-type vpls;
    interface ge-1/0/0.1;
    interface ge-1/1/0.1;
    route-distinguisher 192.0.2.1:1;
    provider-tunnel {
      rsvp-te {
        label-switched-path-template {
          vpls-GOLD-p2mp-template;
        }
      }
    }
  }
}
```

```

    }
  }
}
vrf-target target:65000:1;
}
}

```

3. Configuring the VPLS protocol enables the VPLS between different sites in the VPLS domain.

Multiple sites can be configured under a single VPLS routing instance, but note that the lowest site ID is used to build the VPLS pseudowire to the other PE routers, and the label block associated with the lowest site ID is advertised. The following parameters are configured for the VPLS protocol:

- Site – Name of the VPLS site.
- Site Range – Maximum site ID allowed in the VPLS. The site range specifies the highest-value site ID allowed within the VPLS, not the number of sites in the VPLS.
- Site Identifier – Any number between 1 and 65,534 that uniquely identifies the VPLS site. This is also referred as the VE-ID in the relevant RFC.
- PE-CE Interface – The interface participating in this site.
- Tunnel services for VPLS – If you do not configure any tunnel interface at the [edit protocol vpls tunnel-services] hierarchy, the router uses any tunnel interface available on the router for VPLS.
- No-tunnel-services – If you include the no-tunnel-services statement, the router uses a label-switched interface (LSI) for the tunnel services for that VPLS instance.
- Mac Table Size – The size of the VPLS media access control (MAC) address table. The default is 512 addresses and the maximum is 65,536. When the table is full, new MAC addresses are no longer added to the table.

To configure the VPLS protocol, include the `vpls` statement at the [edit routing-instances *routing-instance-name* protocols] hierarchy level. To configure the site range, include the `site-range` statement and specify the highest-value site ID allowed within the VPLS. To cause the router to use an LSI interface, include the `no-tunnel-services` statement. To create a VPLS site, include the `site` statement and specify a site name. Also include the `site-identifier` statement and specify the site ID. Then include the `interface` statement and specify the interface name for the interface connected to the CE device.

```

[edit]
routing-instances {
  GOLD {
    instance-type vpls;

```



```

interface ge-1/0/0.1;
interface ge-1/1/0.1;
route-distinguisher 192.0.2.1:1;
provider-tunnel {
    rsvp-te {
        label-switched-path-template {
            vpls-GOLD-p2mp-template;
        }
    }
}
vrf-target target:65000:1;
protocols {
    vpls {
        site-range 8;
        no-tunnel-services;
        site CE1 {
            site-identifier 1;
            interface ge-1/0/0.1;
        }
        site Direct {
            site-identifier 2;
            interface ge-1/1/0.1;
        }
    }
}
}
}

```

Configuring Tunnel Services for VPLS

Step-by-Step Procedure

A tunnel interface is needed for VPLS configuration to encapsulate the originating traffic, and to de-encapsulate the traffic coming from a remote site. If the tunnel interface is not configured, the router selects one of the available tunnel interfaces on the router by default. There are three methods available in Junos OS to configure this tunnel interface.

- To specify a virtual tunnel interface to be used as the primary device for tunneling, include the primary statement, and specify the virtual tunnel interface to be used at the [edit routing-instances *routing-instance-name* protocols vpls tunnel-services] hierarchy level.

```
[edit routing-instances routing-instance-name]
protocols {
  vpls {
    site-range 8;
    tunnel-services {
      primary vt-1/2/10;
    }
  }
}
```

- To configure the router to use an LSI interface for tunnel services rather than a virtual tunnel interface, include the no-tunnel-services statement at the [edit routing-instances *routing-instance-name* protocols vpls] hierarchy level.

```
[edit routing-instances routing-instance-name]
protocols {
  vpls {
    site-range 8;
    no-tunnel-services;
  }
}
```

- In an MX Series router you must create the tunnel services interface to be used for tunnel services. To create the tunnel service interface, include the bandwidth statement and specify the amount of bandwidth to reserve for tunnel services in gigabits per second at the [edit chassis fpc *slot-number* pic *slot-number* tunnel-services] hierarchy level.

```
[edit chassis]
fpc 1 {
  pic 3 {
    tunnel-services {
      bandwidth 1g;
    }
  }
}
```

Verifying the Control Plane

Step-by-Step Procedure

This section describes `show` command outputs you can use to validate the control plane. It also provides methodologies for troubleshooting. Note the following:

- In this example there are six sites. Router PE1 and Router PE2 have two sites each. Router PE3 and Router PE4 have one site each. All sites are in the GOLD VPLS instance.
- In VPLS if you have multiple sites configured under a single VPLS routing instance, the label block from the site with the lowest site ID is used to establish pseudowires between remote PEs. Note that the data traffic is still sent to those PE router interfaces connected to CE devices that are in one of the following states:
 - LM – Local site ID is not the minimum designated. The local site ID is not the lowest. Therefore the local site ID is not being used to establish pseudowires or distribute VPLS label blocks.
 - RM – Remote site ID is not the minimum designated. The remote site ID is not the lowest. Therefore, the remote site ID is not being used to establish pseudowires or distribute VPLS label blocks.
- For more information about how VPLS label blocks are allocated and used, see *Understanding VPLS Label Blocks Operation*.

1. After the entire configuration is done, you can verify the VPLS connections state.

In the following output, the VPLS connections show the Up state for certain sites, and the remaining sites show either the RM or LM state. This is the expected state in a VPLS implementation on multihoming sites.

In this example, Router PE1 has site CE1 configured with site ID 1 and site Direct configured with site ID 2. The label block for site CE1 is advertised to the remote PE routers and used for receiving the data packets from the remote PE routers. In the `show` command output, notice the following:

- Router PE1 uses its lowest site ID, which is site ID 1. Site ID 1 is used for Device CE1.
- Router PE2 uses its lowest site ID, which is site ID 3. Site ID 3 is used for Device CE2.
- Router PE3 and Router PE4 each have a single site configured.

For site CE1, connection site 3 is in the Up state and connection site 4 is in the RM state.

- For site Direct, all the connections are in the LM state.
- Site Direct has a higher site ID than site 1 on this router.

On Router PE1, use the `show vpls connections` command to verify the VPLS connections state .

```
user@PE1> show vpls connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection

Legend for interface status

Up -- operational
Dn -- down

Instance: GOLD

Local site: CE1 (1)

connection-site	Type	St	Time last up	# Up trans
3	rmt	Up	Oct 6 16:27:23 2009	1
Remote PE: 192.0.2.2, Negotiated control-word: No				
Incoming label: 262171, Outgoing label: 262145				
Local interface: lsi.1049353, Status: Up, Encapsulation: VPLS				
Description: Intf - vpls GOLD local site 1 remote site 3				
4	rmt	RM		
5	rmt	Up	Oct 6 16:27:27 2009	1
Remote PE: 192.0.2.3, Negotiated control-word: No				
Incoming label: 262173, Outgoing label: 262145				
Local interface: lsi.1049354, Status: Up, Encapsulation: VPLS				
Description: Intf - vpls GOLD local site 1 remote site 5				
6	rmt	Up	Oct 6 16:27:31 2009	1
Remote PE: 192.0.2.4, Negotiated control-word: No				
Incoming label: 262174, Outgoing label: 800000				

```

Local interface: lsi.1049355, Status: Up, Encapsulation: VPLS
Description: Intf - vpls GOLD local site 1 remote site 6
Local site: Direct (2)

```

connection-site	Type	St	Time last up	# Up trans
3	rmt	LM		
4	rmt	LM		
5	rmt	LM		
6	rmt	LM		

2. On Router PE4, use the `show vpls connections` command to verify the VPLS connections state.

Verify that site 2 and site 4 are in the RM state. This state tells you that the sites are configured with the highest site ID on Router PE1 and Router PE2. Because Router PE4 has only one site configured, it does not have any sites in the LM states.

```

user@PE4> show vpls connections
...
Instance: GOLD
Local site: Direct (6)

```

connection-site	Type	St	Time last up	# Up trans
1	rmt	Up	Oct 6 16:28:35 2009	1
Remote PE: 192.0.2.1, Negotiated control-word: No				
Incoming label: 800000, Outgoing label: 262174				
Local interface: vt-1/2/10.1048576, Status: Up, Encapsulation: VPLS				
Description: Intf - vpls GOLD local site 6 remote site 1				
2	rmt	RM		
3	rmt	Up	Oct 6 16:28:35 2009	1
Remote PE: 192.0.2.2, Negotiated control-word: No				
Incoming label: 800002, Outgoing label: 262150				
Local interface: vt-1/2/10.1048577, Status: Up, Encapsulation: VPLS				
Description: Intf - vpls GOLD local site 6 remote site 3				
4	rmt	RM		
5	rmt	Up	Oct 6 16:28:35 2009	1
Remote PE: 192.0.2.3, Negotiated control-word: No				
Incoming label: 800004, Outgoing label: 262150				
Local interface: vt-1/2/10.1048578, Status: Up, Encapsulation: VPLS				
Description: Intf - vpls GOLD local site 6 remote site 5				

3. On each PE router, use the `show bgp summary` command to verify that the IBGP sessions between the PE routers or between the PE router and the route reflector have been established. The sessions must be operational before the PE routers can exchange any Layer 2 VPN routes. In the example

below, also notice that the output from Router PE1 shows that the `bgp.12vpn.0` and `GOLD.12vpn.0` routing tables have been created.

```
user@PE1> show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Table    Tot Paths  Act Paths Suppressed    History Damp State    Pending
bgp.12vpn.0      4         4         0         0         0         0
Peer          AS      InPkt    OutPkt    OutQ   Flaps Last Up/Dwn State
192.0.2.7     65000      40       39        0       1    15:45 Establ
  bgp.12vpn.0: 4/4/4/0
  GOLD.12vpn.0: 4/4/4/0

admin@PE2# run show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Table    Tot Paths  Act Paths Suppressed    History Damp State    Pending
bgp.12vpn.0      4         4         0         0         0         0
inet6.0          0         0         0         0         0         0
inet.0           0         0         0         0         0         0
Peer          AS      InPkt    OutPkt    OutQ   Flaps Last Up/Dwn State
192.0.2.7     65000      43       42        0        0    17:25 Establ
  bgp.12vpn.0: 4/4/4/0
  GOLD.12vpn.0: 4/4/4/0
```

4. On Router PE4, use the `show route table` command to verify that there is one Layer 2 VPN route to each of the other PE routers. Router PE3 should have a similar `show` command output.

```
user@PE4> show route table bgp.12vpn.0
bgp.12vpn.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.0.2.1:1:1:1/96
    *[BGP/170] 00:23:18, localpref 100, from 192.0.2.7
        AS path: I
        > to 10.10.9.1 via xe-0/0/0.0, label-switched-path to-PE1
192.0.2.1:1:2:1/96
    *[BGP/170] 00:23:18, localpref 100, from 192.0.2.7
        AS path: I
        > to 10.10.9.1 via xe-0/0/0.0, label-switched-path to-PE1
192.0.2.2:10:3:1/96
    *[BGP/170] 00:23:18, localpref 100, from 192.0.2.7
        AS path: I
```

```

> to 10.10.9.1 via xe-0/0/0.0, label-switched-path to-PE2
192.0.2.2:10:4:1/96
*[BGP/170] 00:23:18, localpref 100, from 192.0.2.7
AS path: I
> to 10.10.9.1 via xe-0/0/0.0, label-switched-path to-PE2
192.0.2.3:10:5:1/96
*[BGP/170] 00:23:18, localpref 100, from 192.0.2.7
AS path: I
> to 10.10.8.1 via xe-0/1/0.0, label-switched-path to-PE3

```

5. On the route reflector, use the `show bgp summary` command to verify that the router has an IBGP peer session with each of the PE routers.

```

user@RR> show bgp summary
Groups: 2 Peers: 5 Down peers: 1
Table    Tot Paths  Act Paths Suppressed  History Damp State  Pending
bgp.l2vpn.0      6         6         0           0         0         0
inet.0           0         0         0           0         0         0
Peer        AS      InPkt    OutPkt  OutQ   Flaps Last Up/Dwn State
192.0.2.1    65000      44      46     0      0      18:27 Establ
  bgp.l2vpn.0: 2/2/2/0
192.0.2.2    65000      43      45     0      0      18:22 Establ
  bgp.l2vpn.0: 2/2/2/0
192.0.2.3    65000      42      45     0      0      18:19 Establ
  bgp.l2vpn.0: 1/1/1/0
192.0.2.4    65000      43      45     0      0      18:15 Establ
  bgp.l2vpn.0: 1/1/1/0

```

6. In NG-VPLS, point-to-multipoint LSPs carry only unknown unicast, broadcast, and multicast packets. A full mesh of point-to-point LSPs is needed between the PE routers for NG-VPLS. The point-to-point LSPs create routes in the `inet.3` routing table. These entries are used to resolve the Layer 2 VPN routes received from the BGP peers. All other data traffic is sent over point-to-point LSPs.

A point-to-point LSP is also created for the route reflector. This LSP creates a route in the `inet.3` routing table for BGP next-hop resolution.

On Router PE1, use the `show mpls lsp` command to verify that the to-PE2, to-PE3, to-PE4, and to-RR LSPs are in the Up state.

```
user@PE1> show mpls lsp ingress unidirectional
Ingress LSP: 7 sessions
To          From          State Rt P    ActivePath    LSPname
192.0.2.2    192.0.2.1      Up    0 *          to-PE2
192.0.2.3    192.0.2.1      Up    0 *          to-PE3
192.0.2.4    192.0.2.1      Up    0 *          to-PE4
192.0.2.7    192.0.2.1      Up    0 *          to-RR
Total 4 displayed, Up 4, Down 0
admin@PE2# run show mpls lsp ingress unidirectional
Ingress LSP: 7 sessions
To          From          State Rt P    ActivePath    LSPname
192.0.2.1    192.0.2.2      Up    0 *          to-PE1
192.0.2.3    192.0.2.2      Up    0 *          to-PE3
192.0.2.4    192.0.2.2      Up    0 *          to-PE4
192.0.2.7    192.0.2.2      Up    0 *          to-RR
Total 4 displayed, Up 4, Down 0
admin@PE3# run show mpls lsp ingress unidirectional
Ingress LSP: 7 sessions
To          From          State Rt P    ActivePath    LSPname
192.0.2.1    192.0.2.3      Up    0 *          to-PE1
192.0.2.2    192.0.2.3      Up    0 *          to-PE2
192.0.2.4    192.0.2.3      Up    0 *          to-PE4
192.0.2.7    192.0.2.3      Up    0 *          to-RR
Total 4 displayed, Up 4, Down 0
admin@PE4# run show mpls lsp ingress unidirectional
Ingress LSP: 7 sessions
To          From          State Rt P    ActivePath    LSPname
192.0.2.1    192.0.2.4      Up    0 *          to-PE1
192.0.2.2    192.0.2.4      Up    0 *          to-PE2
192.0.2.3    192.0.2.4      Up    0 *          to-PE3
192.0.2.7    192.0.2.4      Up    0 *          to-RR
Total 4 displayed, Up 4, Down 0
```

7. For each VPLS instance, a PE router creates a dedicated point-to-multipoint LSP. In this example, Router PE1 and Router PE2 are configured to use a point-to-multipoint dynamic template.

For dynamic point-to-multipoint LSPs, whenever VPLS discovers a new Layer 2 VPN neighbor through BGP, a source-to-leaf sub-LSP is added in the VPLS instance for this neighbor PE router.

On Router PE1, use the `show mpls lsp` command to verify that three source-to-leaf sub-LSPs are created.

```
user@PE1> show mpls lsp ingress p2mp
Ingress LSP: 1 sessions
P2MP name: 192.0.2.1:1:vppls:GOLD, P2MP branch count: 3
To          From          State Rt P    ActivePath      LSPname
192.0.2.4    192.0.2.1      Up    0 *      192.0.2.4:192.0.2.1:1:vppls:GOLD
192.0.2.3    192.0.2.1      Up    0 *      192.0.2.3:192.0.2.1:1:vppls:GOLD
192.0.2.2    192.0.2.1      Up    0 *      192.0.2.2:192.0.2.1:1:vppls:GOLD
Total 3 displayed, Up 3, Down 0
```

8. On Router PE2, use the `show mpls lsp` command to verify that three source-to-leaf sub-LSPs are created.

```
user@PE2> show mpls lsp p2mp ingress
Ingress LSP: 1 sessions
P2MP name: 192.0.2.2:10:vppls:GOLD, P2MP branch count: 3
To          From          State Rt P    ActivePath      LSPname
192.0.2.4    192.0.2.2      Up    0 *      192.0.2.4:192.0.2.2:10:vppls:GOLD
192.0.2.3    192.0.2.2      Up    0 *      192.0.2.3:192.0.2.2:10:vppls:GOLD
192.0.2.1    192.0.2.2      Up    0 *      192.0.2.1:192.0.2.2:10:vppls:GOLD
Total 3 displayed, Up 3, Down 0
```

9. In this step, Router PE3 and Router PE4 are using static point-to-multipoint LSPs. For static point-to-multipoint LSPs, the source-to-leaf sub-LSPs to all the PE routers are manually configured.

On Router PE3, use the `show mpls lsp` command to verify that three source-to-leaf sub-LSPs have been configured.

```
user@PE3> show mpls lsp p2mp ingress
Ingress LSP: 1 sessions
P2MP name: vppls-GOLD, P2MP branch count: 3
To          From          State Rt P    ActivePath      LSPname
192.0.2.1    192.0.2.3      Up    0 *                        to-pe1
192.0.2.4    192.0.2.3      Up    0 *                        to-pe4
192.0.2.2    192.0.2.3      Up    0 *                        to-pe2
Total 3 displayed, Up 3, Down 0
```

10. On Router PE4, use the `show mpls lsp ingress p2mp` command to verify that three source-to-leaf sub-LSPs are configured.

```
user@PE4> show mpls lsp ingress p2mp
Ingress LSP: 1 sessions
P2MP name: vpls-GOLD, P2MP branch count: 3
To          From          State Rt P    ActivePath    LSPname
192.0.2.1   192.0.2.4   Up    0 *          to-pe1
192.0.2.3   192.0.2.4   Up    0 *          to-pe3
192.0.2.2   192.0.2.4   Up    0 *          to-pe2
Total 3 displayed, Up 3, Down 0
```

11. Each point-to-multipoint LSP created by the PE router can be identified using an RSVP-TE point-to-multipoint session object. The session object is passed as a PMSI tunnel attribute by BGP when it advertises VPLS routes. Using this tunnel attribute, an incoming source-to-leaf sub LSP add request (RSVP-Path message) supports label allocation in such a way that when traffic arrives on this source-to-leaf sub-LSP the router terminates the message in the right VPLS instance and also identifies the originating PE. This supports source MAC address learning.

On Router PE1, use the `show rsvp session` command to verify that the RSVP session for the dynamic point-to-multipoint LSP is Up and that link protection is configured as desired. Notice that the point-to-multipoint session object to be sent in BGP is 54337.

```
user@PE1> show rsvp session detail p2mp ingress
Ingress RSVP: 7 sessions
P2MP name: 192.0.2.1:1:vpls:GOLD, P2MP branch count: 3

192.0.2.2
  From: 192.0.2.1, LSPstate: Up, ActiveRoute: 0
  LSPname: 192.0.2.2:192.0.2.1:1:vpls:GOLD, LSPpath: Primary
  P2MP LSPname: 192.0.2.1:1:vpls:GOLD
  Suggested label received: -, Suggested label sent: -
  Recovery label received: -, Recovery label sent: 262145
  Resv style: 1 SE, Label in: -, Label out: 262145
  Time left: -, Since: Tue Oct 6 16:27:23 2009
  Tspec: rate 0bps size 0bps peak Infbps m 20 M 1500
  Port number: sender 2 receiver 54337 protocol 0
  Link protection desired
  Type: Protection down
  PATH rcvfrom: localclient
  Adspeg: sent MTU 1500
```

```

Path MTU: received 1500
PATH sentto: 10.10.2.2 (xe-0/1/0.0) 371 pkts
RESV rcvfrom: 10.10.2.2 (xe-0/1/0.0) 370 pkts
Explct route: 10.10.2.2
Record route: <self> 10.10.2.2

```

12. Router PE4 is configured for static point-to-multipoint LSPs. Link protection is not configured for these LSPs. Use the `show rsvp session` command to verify that the point-to-multipoint session object to be sent in BGP is 42873.

```

user@PE4> show rsvp session detail p2mp ingress
Ingress RSVP: 7 sessions
P2MP name: vpls-GOLD, P2MP branch count: 3

192.0.2.1
  From: 192.0.2.4, LSPstate: Up, ActiveRoute: 0
  LSPname: to-pe1, LSPpath: Primary
  P2MP LSPname: vpls-GOLD
  Suggested label received: -, Suggested label sent: -
  Recovery label received: -, Recovery label sent: 390416
  Resv style: 1 SE, Label in: -, Label out: 390416
  Time left: -, Since: Tue Oct 6 15:28:33 2009
  Tspec: rate 0bps size 0bps peak Infbps m 20 M 1500
  Port number: sender 10 receiver 42873 protocol 0
  PATH rcvfrom: localclient
  Adspec: sent MTU 1500
  Path MTU: received 1500
  PATH sentto: 10.10.9.1 (xe-0/0/0.0) 524 pkts
  RESV rcvfrom: 10.10.9.1 (xe-0/0/0.0) 447 pkts
  Explct route: 10.10.9.1 10.10.3.1
  Record route: <self> 10.10.9.1 10.10.3.1

```

13. On Router PE1, use the `show route table` command to verify that Router PE1 received a Layer 2 VPN route to Router PE2 from the router reflector and the route includes a PMSI object that contains the point-to-multipoint tunnel identifier of 20361.

```

user@PE1> show route table GOLD.l2vpn.0 detail
GOLD.l2vpn.0: 6 destinations, 6 routes (6 active, 0 holddown, 0 hidden)
!
!
192.0.2.2:10:3:1/96 (1 entry, 1 announced)

```

```

*BGP      Preference: 170/-101
          Route Distinguisher: 192.0.2.2:10
          PMSI: Flags 0:RSVP-TE:label[0:0:0]:Session_13[192.0.2.2:0:20361:192.0.2.2]
          Next hop type: Indirect
          Next-hop reference count: 7
          Source: 192.0.2.7
          Protocol next hop: 192.0.2.2
          Indirect next hop: 2 no-forward
          State: <Secondary Active Int Ext>
          Local AS: 65000 Peer AS: 65000
          Age: 4:25:25    Metric2: 1
          Task: BGP_65000.192.0.2.7+63544
          Announcement bits (1): 0-GOLD-l2vpn
          AS path: I (Originator) Cluster list: 192.0.2.7
          AS path: Originator ID: 192.0.2.2
          Communities: target:65000:1 Layer2-info: encaps:VPLS, control flags:, mtu:
0, site preference: 100
          Import Accepted
          Label-base: 262145, range: 8
          Localpref: 100
          Router ID: 192.0.2.7
          Primary Routing Table bgp.l2vpn.0
PMSI: Flags 0:RSVP-TE:label[0:0:0]:Session_13[192.0.2.2:0:20361:192.0.2.2]

```

14. On Router PE2, use the `show rsvp session` command to verify that the PMSI tunnel identifier object of 20361 matches the PMSI tunnel identifier object displayed on Router PE1.

```

user@PE2> show rsvp session p2mp detail
Ingress RSVP: 7 sessions
P2MP name: 192.0.2.2:10:vpls:GOLD, P2MP branch count: 3

192.0.2.1
  From: 192.0.2.2, LSPstate: Up, ActiveRoute: 0
  LSPname: 192.0.2.1:192.0.2.2:10:vpls:GOLD, LSPpath: Primary
  P2MP LSPname: 192.0.2.2:10:vpls:GOLD
  Suggested label received: -, Suggested label sent: -
  Recovery label received: -, Recovery label sent: 262171
  Resv style: 1 SE, Label in: -, Label out: 262171
  Time left: -, Since: Tue Oct 6 16:31:47 2009
  Tspec: rate 0bps size 0bps peak Infbps m 20 M 1500
  Port number: sender 1 receiver 20361 protocol 0
  Link protection desired

```

```

Type: Protection down
PATH rcvfrom: localclient
Adspec: sent MTU 1500
Path MTU: received 1500
PATH sentto: 10.10.2.1 (xe-0/1/0.0) 379 pkts
RESV rcvfrom: 10.10.2.1 (xe-0/1/0.0) 379 pkts
Explct route: 10.10.2.1
Record route: <self> 10.10.2.1

```

Verifying the Data Plane

Step-by-Step Procedure

After the control plane is verified using the previous steps, you can verify the data plane. This section describes `show` command outputs you can use to validate the data plane.

1. On Router PE1, use the `show vpls connections extensive | match Flood` command to verify the point-to-multipoint LSP name and status of all the sites. Notice the flood next-hop identifier of 600 for the 192.0.2.1:1:vpls:GOLD LSP.

```

user@PE1> show vpls connections extensive | match Flood
Ingress RSVP-TE P2MP LSP: 192.0.2.1:1:vpls:GOLD, Flood next-hop ID: 600

```

2. On Router PE1, use the `show vpls connections extensive` command to verify the point-to-multipoint LSP name and status of all the sites.

```

user@PE1> show vpls connections extensive
Instance: GOLD
  Local site: CE1 (1)
    Number of local interfaces: 1
    Number of local interfaces up: 1
    IRB interface present: no
    ge-1/0/0.1
    lsi.1049353      3      Intf - vpls GOLD local site 1 remote site 3
    lsi.1049346      4      Intf - vpls GOLD local site 1 remote site 4
      Interface flags: VC-Down
    lsi.1049354      5      Intf - vpls GOLD local site 1 remote site 5
    lsi.1049355      6      Intf - vpls GOLD local site 1 remote site 6
    Label-base      Offset      Range      Preference
    262169           1          8          100

```

```

connection-site      Type St    Time last up    # Up trans
3                    rmt  Up    Oct  6 16:27:23 2009      1
  Remote PE: 192.0.2.2, Negotiated control-word: No
  Incoming label: 262171, Outgoing label: 262145
  Local interface: lsi.1049353, Status: Up, Encapsulation: VPLS
  Description: Intf - vpls GOLD local site 1 remote site 3
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.2:192.0.2.1:1:vpls:GOLD, State: Up
    Egress branch LSP: 192.0.2.1:192.0.2.2:10:vpls:GOLD, State: Up
  Connection History:
    Oct  6 16:27:23 2009  status update timer
    Oct  6 16:27:23 2009  PE route changed
    Oct  6 16:27:23 2009  Out lbl Update                      262145
    Oct  6 16:27:23 2009  In lbl Update                      262171
    Oct  6 16:27:23 2009  loc intf up                          lsi.1049353
4                    rmt  RM
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.2:192.0.2.1:1:vpls:GOLD, State: Up
5                    rmt  Up    Oct  6 16:27:27 2009      1
  Remote PE: 192.0.2.3, Negotiated control-word: No
  Incoming label: 262173, Outgoing label: 262145
  Local interface: lsi.1049354, Status: Up, Encapsulation: VPLS
  Description: Intf - vpls GOLD local site 1 remote site 5
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.3:192.0.2.1:1:vpls:GOLD, State: Up
    Egress branch LSP: to-pe1, State: Up
  Connection History:
    Oct  6 16:27:27 2009  status update timer
    Oct  6 16:27:27 2009  PE route changed
    Oct  6 16:27:27 2009  Out lbl Update                      262145
    Oct  6 16:27:27 2009  In lbl Update                      262173
    Oct  6 16:27:27 2009  loc intf up                          lsi.1049354
6                    rmt  Up    Oct  6 16:27:31 2009      1
  Remote PE: 192.0.2.4, Negotiated control-word: No
  Incoming label: 262174, Outgoing label: 800000
  Local interface: lsi.1049355, Status: Up, Encapsulation: VPLS
  Description: Intf - vpls GOLD local site 1 remote site 6
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.4:192.0.2.1:1:vpls:GOLD, State: Up
    Egress branch LSP: to-pe1, State: Up
  Connection History:
    Oct  6 16:27:31 2009  status update timer
    Oct  6 16:27:31 2009  PE route changed

```

```

Oct  6 16:27:31 2009  Out lbl Update          800000
Oct  6 16:27:31 2009  In lbl Update           262174
Oct  6 16:27:31 2009  loc intf up             lsi.1049355
Local site: Direct (2)
Number of local interfaces: 1
Number of local interfaces up: 1
IRB interface present: no
Interface name Remote site ID Description
ge-1/1/0.1
lsi.1049347     3      Intf - vpls GOLD local site 2 remote site 3
Interface flags: VC-Down
lsi.1049348     4      Intf - vpls GOLD local site 2 remote site 4
Interface flags: VC-Down
lsi.1049350     5      Intf - vpls GOLD local site 2 remote site 5
Interface flags: VC-Down
lsi.1049352     6      Intf - vpls GOLD local site 2 remote site 6
Interface flags: VC-Down
Label-base      Offset      Range      Preference
262177          1          8          100
connection-site      Type St      Time last up
3                  rmt  LM
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.2:192.0.2.1:1:vpls:GOLD, State: Up
4                  rmt  LM
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.2:192.0.2.1:1:vpls:GOLD, State: Up
5                  rmt  LM
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.3:192.0.2.1:1:vpls:GOLD, State: Up
6                  rmt  LM
  RSVP-TE P2MP lsp:
    Ingress branch LSP: 192.0.2.4:192.0.2.1:1:vpls:GOLD, State: Up
Ingress RSVP-TE P2MP LSP: 192.0.2.1:1:vpls:GOLD, Flood next-hop ID: 600

```

3. Junos OS Release 9.0 and later identifies the flood next-hop route as a composite next hop. On Router PE1, use the `show route forwarding-table family vpls vpn GOLD detail` command to verify that three composite flood next-hop routes are installed in the Packet Forwarding Engine.

```

user@PE1> show route forwarding-table family vpls vpn GOLD detail
Routing table: GOLD.vpls
VPLS:
Destination      Type RtRef Next hop      Type Index NhRef Netif

```

default	perm	0	dscd	518	1	
00:00:28:28:28:02/48						
	user	0	ucst	617	4	ge-1/1/0.1
00:00:28:28:28:06/48						
	user	0	indr	1048576	4	
		10.10.3.2	Push	800000, Push	390384(top)	621 2
xe-0/2/0.0						
lsi.1049353	intf	0	indr	1048574	3	
		10.10.2.2	Push	262145	598 2	xe-0/1/0.0
lsi.1049354	intf	0	indr	1048575	4	
		10.10.1.2	Push	262145, Push	302272(top)	602 2
xe-0/3/0.0						
lsi.1049355	intf	0	indr	1048576	4	
		10.10.3.2	Push	800000, Push	390384(top)	621 2
xe-0/2/0.0						
00:14:f6:75:78:00/48						
	user	0	indr	1048575	4	
		10.10.1.2	Push	262145, Push	302272(top)	602 2
xe-0/3/0.0						
00:19:e2:57:e7:c0/48						
	user	0	ucst	604	4	ge-1/0/0.1
0x30003/51	user	0	comp	613	2	
0x30002/51	user	0	comp	615	2	
0x30001/51	user	0	comp	582	2	
ge-1/0/0.1	intf	0	ucst	604	4	ge-1/0/0.1
ge-1/1/0.1	intf	0	ucst	617	4	ge-1/1/0.1

You can also use the use the show route forwarding-table family vpls extensive command to match the flood identifier and note the flood label. To match the label out corresponding to the point-to-multipoint LSP, use the show rsvp session ingress p2mp command.

4. On Router PE1, use the show route forwarding-table family vpls vpn GOLD extensive | find 0x30003/51 command to get more details about the composite next-hop route and the associated point-to-multipoint LSP labels.

```

user@PE1> show route forwarding-table family vpls vpn GOLD extensive | find 0x30003/51
Destination: 0x30003/51
Route type: user
Route reference: 0
Route interface-index: 0
Flags: sent to PFE
Nexthop:
Next-hop type: composite
Index: 613
Reference: 2

```



```

Nexthop:
Next-hop type: composite      Index: 556      Reference: 4
Next-hop type: unicast       Index: 604      Reference: 4
Next-hop interface: ge-1/0/0.1
Next-hop type: unicast       Index: 617      Reference: 4
Next-hop interface: ge-1/1/0.1

```

Destination: 0x30002/51

```

Route type: user
Route reference: 0            Route interface-index: 0
Flags: sent to PFE
Nexthop:
Next-hop type: composite      Index: 615      Reference: 2
Nexthop:
Next-hop type: composite      Index: 556      Reference: 4
Next-hop type: unicast       Index: 604      Reference: 4
Next-hop interface: ge-1/0/0.1
Next-hop type: unicast       Index: 617      Reference: 4
Next-hop interface: ge-1/1/0.1
Nexthop:
Next-hop type: composite      Index: 603      Reference: 3
Next-hop type: flood         Index: 600      Reference: 2
Nexthop: 10.10.2.2
Next-hop type: Push 262145   Index: 599      Reference: 1
Next-hop interface: xe-0/1/0.0
Nexthop: 10.10.3.2
Next-hop type: Push 390496    Index: 622      Reference: 1
Next-hop interface: xe-0/2/0.0
Nexthop: 10.10.1.2
Next-hop type: Push 302416    Index: 618      Reference: 1
Next-hop interface: xe-0/3/0.0

```

Destination: 0x30001/51

```

Route type: user
Route reference: 0            Route interface-index: 0
Flags: sent to PFE
Nexthop:
Next-hop type: composite      Index: 582      Reference: 2
Nexthop:
Next-hop type: composite      Index: 556      Reference: 4
Next-hop type: unicast       Index: 604      Reference: 4
Next-hop interface: ge-1/0/0.1
Next-hop type: unicast       Index: 617      Reference: 4

```

```

Next-hop interface: ge-1/1/0.1
Nexthop:
Next-hop type: composite          Index: 603      Reference: 3
Next-hop type: flood             Index: 600      Reference: 2
Nexthop: 10.10.2.2
Next-hop type: Push 262145        Index: 599      Reference: 1
Next-hop interface: xe-0/1/0.0
Nexthop: 10.10.3.2
Next-hop type: Push 390496        Index: 622      Reference: 1
Next-hop interface: xe-0/2/0.0
Nexthop: 10.10.1.2
Next-hop type: Push 302416        Index: 618      Reference: 1
Next-hop interface: xe-0/3/0.0

Destination: ge-1/0/0.1
Route type: interface
Route reference: 0                Route interface-index: 84
Flags: sent to PFE
Next-hop type: unicast            Index: 604      Reference: 4
Next-hop interface: ge-1/0/0.1

Destination: ge-1/1/0.1
Route type: interface
Route reference: 0                Route interface-index: 86
Flags: sent to PFE
Next-hop type: unicast            Index: 617      Reference: 4
Next-hop interface: ge-1/1/0.1

```

5. On Router PE1, use the `show vpls mac-table instance GOLD` command to verify the learned MAC addresses of CE routers connected to the VPLS domain.

```

user@PE1> show vpls mac-table instance GOLD
MAC flags (S -static MAC, D -dynamic MAC,
          SE -Statistics enabled, NM -Non configured MAC)

Routing instance : GOLD
Bridging domain : __GOLD__, VLAN : NA
  MAC          MAC      Logical
  address      flags    interface
  00:00:28:28:28:02 D      ge-1/1/0.1
  00:00:28:28:28:04 D      lsi.1049353
  00:14:f6:75:78:00 D      lsi.1049354

```

```
00:19:e2:51:7f:c0 D lsi.1049353
00:19:e2:57:e7:c0 D ge-1/0/0.1
```

6. On Router PE1, use the `show vpls statistics` command to verify the broadcast, multicast, and unicast traffic flow using the packet statistics for the VPLS instance.

```
user@PE1> show vpls statistics
VPLS statistics:

Instance: GOLD
  Local interface: lsi.1049347, Index: 72
    Current MAC count: 0
  Local interface: lsi.1049348, Index: 73
    Current MAC count: 0
  Local interface: lsi.1049346, Index: 82
    Current MAC count: 0
  Local interface: lsi.1049353, Index: 83
  Remote PE: 192.0.2.2
    Current MAC count: 2
  Local interface: ge-1/0/0.1, Index: 84
    Broadcast packets: 421
    Broadcast bytes : 26944
    Multicast packets: 3520
    Multicast bytes : 261906
    Flooded packets : 509043345
    Flooded bytes : 130315095486
    Unicast packets : 393836428
    Unicast bytes : 100822118854
    Current MAC count: 1 (Limit 1024)
  Local interface: ge-1/1/0.1, Index: 86
    Broadcast packets: 0
    Broadcast bytes : 0
    Multicast packets: 0
    Multicast bytes : 0
    Flooded packets : 22889544
    Flooded bytes : 5859702144
    Unicast packets : 472
    Unicast bytes : 30838
    Current MAC count: 1 (Limit 1024)
  Local interface: lsi.1049354, Index: 88
  Remote PE: 192.0.2.3
    Current MAC count: 1
```

```

Local interface: lsi.1049350, Index: 89
  Current MAC count:                0
Local interface: lsi.1049355, Index: 90
Remote PE: 192.0.2.4
  Current MAC count:                0
Local interface: lsi.1049352, Index: 91
  Current MAC count:                0

```

Results

The configuration, verification, and testing part of this example has been completed. The following section is for your reference.

The relevant sample configuration for Router PE1 follows.

PE1 Configuration

```

chassis {
  dump-on-panic;
  fpc 1 {
    pic 3 {
      tunnel-services {
        bandwidth 1g;
      }
    }
  }
  network-services ethernet;
}
interfaces {
  xe-0/1/0 {
    unit 0 {
      family inet {
        address 10.10.2.1/30;
      }
      family mpls;
    }
  }
  xe-0/2/0 {
    unit 0 {
      family inet {
        address 10.10.3.1/30;
      }
    }
  }
}

```

```

        family mpls;
    }
}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.1/30;
        }
        family mpls;
    }
}
ge-1/0/0 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 1 {
        encapsulation vlan-vpls;
        vlan-id 1000;
        family vpls;
    }
}
ge-1/1/0 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 1 {
        encapsulation vlan-vpls;
        vlan-id 1000;
        family vpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}
routing-options {
    autonomous-system 65000;
}
protocols {
    rsvp {
        interface all;
    }
}

```

```

        interface fxp0.0 {
            disable;
        }
    }
    mpls {
        label-switched-path to-RR {
            to 192.0.2.7;
        }
        label-switched-path vpls-GOLD-p2mp-template {
            template;
            optimize-timer 50;
            link-protection;
            p2mp;
        }
        label-switched-path to-PE2 {
            to 192.0.2.2;
        }
        label-switched-path to-PE3 {
            to 192.0.2.3;
        }
        label-switched-path to-PE4 {
            to 192.0.2.4;
        }
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    bgp {
        group to-RR {
            type internal;
            local-address 192.0.2.1;
            family l2vpn {
                signaling;
            }
            neighbor 192.0.2.7;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface all;
            interface fxp0.0 {

```

```

        disable;
    }
}
}
}
routing-instances {
    GOLD {
        instance-type vpls;
        interface ge-1/0/0.1;
        interface ge-1/1/0.1;
        route-distinguisher 192.0.2.1:1;
        provider-tunnel {
            rsvp-te {
                label-switched-path-template {
                    vpls-GOLD-p2mp-template;
                }
            }
        }
        vrf-target target:65000:1;
        protocols {
            vpls {
                site-range 8;
                no-tunnel-services;
                site CE1 {
                    site-identifier 1;
                    interface ge-1/0/0.1;
                }
                site Direct {
                    site-identifier 2;
                    interface ge-1/1/0.1;
                }
            }
        }
    }
}
}
}

```

The relevant sample configuration for Router PE2 follows.

PE2 Configuration

```

chassis {
    dump-on-panic;
}

```

```

aggregated-devices {
    ethernet {
        device-count 1;
    }
}
fpc 1 {
    pic 3 {
        tunnel-services {
            bandwidth 1g;
        }
    }
}
}
interfaces {
    xe-0/1/0 {
        unit 0 {
            family inet {
                address 10.10.2.2/30;
            }
            family mpls;
        }
    }
    xe-0/2/0 {
        unit 0 {
            family inet {
                address 10.10.5.1/30;
            }
            family mpls;
        }
    }
    xe-0/3/0 {
        unit 0 {
            family inet {
                address 10.10.4.1/30;
            }
            family mpls;
        }
    }
    ge-1/0/1 {
        gigether-options {
            802.3ad ae0;
        }
    }
}

```



```

ge-1/0/2 {
    gigether-options {
        802.3ad ae0;
    }
}
ge-1/1/0 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 1 {
        encapsulation vlan-vpls;
        vlan-id 1000;
        family vpls;
    }
}
ae0 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 1 {
        encapsulation vlan-vpls;
        vlan-id 1000;
        family vpls;
    }
}
fxp0 {
    apply-groups [ re0 re1 ];
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}
}
routing-options {
    autonomous-system 65000;
}
protocols {
    rsvp {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

```

```

}
mpls {
    label-switched-path to-RR {
        to 192.0.2.7;
    }
    label-switched-path vpls-GOLD-p2mp-template {
        template;
        optimize-timer 50;
        link-protection;
        p2mp;
    }
    label-switched-path to-PE1 {
        to 192.0.2.1;
    }
    label-switched-path to-PE3 {
        to 192.0.2.3;
    }
    label-switched-path to-PE4 {
        to 192.0.2.4;
    }
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    group to-RR {
        type internal;
        local-address 192.0.2.2;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

```

```

    }
}
routing-instances {
    GOLD {
        instance-type vpls;
        interface ge-1/1/0.1;
        interface ae0.1;
        route-distinguisher 192.0.2.2:10;
        provider-tunnel {
            rsvp-te {
                label-switched-path-template {
                    vpls-GOLD-p2mp-template;
                }
            }
        }
        vrf-target target:65000:1;
        protocols {
            vpls {
                site-range 8;
                site CE1 {
                    site-identifier 3;
                    interface ae0.1;
                }
                site Direct {
                    site-identifier 4;
                    interface ge-1/1/0.1;
                }
            }
        }
    }
}
}

```

RELATED DOCUMENTATION

| [Next-Generation VPLS Point-to-Multipoint Forwarding Overview](#) | 1024

Flooding Unknown Traffic Using Point-to-Multipoint LSPs in VPLS

IN THIS SECTION

- [Configuring Static Point-to-Multipoint Flooding LSPs | 1075](#)
- [Configuring Dynamic Point-to-Multipoint Flooding LSPs | 1076](#)

For a VPLS routing instance, you can flood unknown unicast, broadcast, and multicast traffic using point-to-multipoint (also called *P2MP*) LSPs. By default, VPLS relies upon ingress replication to flood unknown traffic to the members of a VPLS routing instance. This can cause replication of data at routing nodes shared by multiple VPLS members, as shown in [Figure 78 on page 1074](#). The flood data is tripled between PE router PE1 and provider router P1 and doubled between provider routers P1 and P2. By

configuring point-to-multipoint LSPs to handle flood traffic, the VPLS routing instance can avoid this type of traffic replication in the network, as shown in [Figure 79 on page 1074](#).

Figure 78: Flooding Unknown VPLS Traffic Using Ingress Replication





Figure 79: Flooding Unknown VPLS Traffic Using a Point-to-Multipoint LSP



NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The point-to-multipoint LSP used for VPLS flooding can be either static or dynamic. In either case, for each VPLS routing instance, the PE router creates a dedicated point-to-multipoint LSP. All of the neighbors of the VPLS routing instance are added to the point-to-multipoint LSP when the feature is enabled. If there are n PE routers in the VPLS routing instance, n point-to-multipoint LSPs are created in the network where each PE router is the root of the point-to-multipoint tree and includes the rest of the $n - 1$ PE routers as leaf nodes. If you configured static point-to-multipoint LSPs for flooding, any

additional VPLS neighbors added to the routing instance later are not automatically added to the point-to-multipoint LSP. You will need to manually add the new VPLS neighbors to the static point-to-multipoint flooding LSP. If you configure dynamic point-to-multipoint LSPs, whenever VPLS discovers a new neighbor through BGP, a sub-LSP for this neighbor is added to the point-to-multipoint LSP for the routing instance.

This feature can be enabled incrementally on any PE router that is part of a specific VPLS routing instance. The PE routers can then use point-to-multipoint LSPs to flood traffic, whereas other PE routers in the same VPLS routing instance can still use ingress replication to flood traffic. However, when this feature is enabled on any PE router, you must ensure that all PE routers in the VPLS routing instance that participate in the flooding of traffic over point-to-multipoint LSPs are upgraded to Junos OS Release 8.3 or later to support this feature.

To flood unknown unicast, broadcast, and multicast traffic using point-to-multipoint LSPs, configure the `rsvp-te` statement as follows:

```
rsvp-te {
  label-switched-path-template (Multicast) {
    (default-template | lsp-template-name);
  }
  static-lsp lsp-name;
}
```

You can include this statement at the following hierarchy levels:

- [edit routing-instance *routing-instance-name* provider-tunnel]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* provider-tunnel]

You can configure either a static point-to-multipoint LSP for VPLS flooding or a dynamic point-to-multipoint LSP.

NOTE: You cannot specify both the static and label-switched-path-template statements at the same time.

The following sections describe how to configure static and dynamic point-to-multipoint LSPs for flooding unknown traffic in a VPLS routing instance:

Configuring Static Point-to-Multipoint Flooding LSPs

The `static-lsp` option creates a static flooding point-to-multipoint LSP that includes all of the neighbors in the VPLS routing instance. Flood traffic is sent to all of the VPLS neighbors using the generated point-

to-multipoint LSP. VPLS neighbors added to the routing instance later are not automatically added to the point-to-multipoint LSP. You will need to manually add the new VPLS neighbors to the static point-to-multipoint flooding LSP. By configuring static point-to-multipoint LSPs for flooding, you have more control over which path each sub-LSP follows.

To configure a static flooding point-to-multipoint LSP, specify the name of the static flooding point-to-multipoint LSP by including the `static-lsp` statement:

```
static-lsp lsp-name;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* provider-tunnel rsvp-te]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* provider-tunnel rsvp-te]

Configuring Dynamic Point-to-Multipoint Flooding LSPs

To configure a dynamic point-to-multipoint flooding LSP, include the `label-switched-path-template` statement option at the [edit routing-instances *routing-instance-name* provider-tunnel rsvp-te] hierarchy level:

```
[edit routing-instances routing-instance-name provider-tunnel rsvp-te]
label-switched-path-template (Multicast) {
  (default-template | lsp-template-name);
}
```

You can automatically generate the point-to-multipoint LSP to be used for flooding unknown traffic or you can manually configure the point-to-multipoint LSP:

Configuring Dynamic Point-to-Multipoint Flooding LSPs with the Default Template

The `default-template` option, specified at the [edit routing-instances *routing-instance-name* provider-tunnel rsvp-te label-switched-path-template] hierarchy level, causes the point-to-multipoint LSPs to be created with default parameters. The default parameters are for a minimally configured point-to-multipoint LSP. The name of this point-to-multipoint LSP is also generated automatically and is based on the following model:

```
id:vpls:router-id:routing-instance-name
```

The following show command output for `show mpls lsp p2mp` illustrates how a point-to-multipoint flood LSP name could appear if you configure the `label-switched-path-template` statement with the `default-template` option:

```
user@host> show mpls lsp p2mp ingress
Ingress LSP: 2 sessions P2MP name: static, P2MP branch count: 3
To          From          State Rt ActivePath      P      LSPname
10.255.14.181 10.255.14.172 Up    0          *      vpn02-vpn11
10.255.14.177 10.255.14.172 Up    0 path2      *      vpn02-vpn07
10.255.14.174 10.255.14.172 Up    0 path3      *      vpn02-vpn04
P2MP name: 9:vp1s:10.255.14.172:green, P2MP branch count: 2
To          From          State Rt ActivePath      P      LSPname
10.255.14.177 10.255.14.172 Up    0          *      11:vp1s:10.255.14.172:green
10.255.14.174 10.255.14.172 Up    0          *      10:vp1s:10.255.14.172:green
Total 5 displayed, Up 5, Down 0
```

The dynamically generated point-to-multipoint LSP name is `9:vp1s:10.255.14.172:green`.

Configuring Dynamic Point-to-Multipoint Flooding LSPs with a Preconfigured Template

You can configure a point-to-multipoint flooding LSP template for the VPLS routing instance. The template allows you to specify the properties of the dynamic point-to-multipoint LSPs that are used to flood traffic for the VPLS routing instance. You can specify all of the standard options available for a point-to-multipoint LSP within this template. These properties are inherited by the dynamic point-to-multipoint flood LSPs.

To configure a point-to-multipoint LSP template for flooding VPLS traffic, specify all of the properties you want to include in a point-to-multipoint LSP configuration. To specify this LSP as a point-to-multipoint flooding template, include the `p2mp` and `template` statements:

```
p2mp;
template;
```

You can include these statements at the following hierarchy levels:

- [edit protocols mpls label-switched-path *p2mp-lsp-template-name*]
- [edit logical-systems *logical-system-name* protocols mpls label-switched-path *p2mp-lsp-template-name*]

For more information about how to configure the `p2mp` statement and point-to-multipoint LSPs, see the [MPLS Applications User Guide](#).

Once you have configured the point-to-multipoint LSP template, specify the name of the point-to-multipoint LSP template with the `label-switched-path-template` statement:

```
label-switched-path-template (Multicast) p2mp-lsp-template-name;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* provider-tunnel rsvp-te]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* provider-tunnel rsvp-te]

Example: Configuring Ingress Replication for IP Multicast Using MBGP MVPNs

IN THIS SECTION

- [Requirements | 1078](#)
- [Overview | 1079](#)
- [Configuration | 1081](#)
- [Verification | 1086](#)

Requirements

The routers used in this example are Juniper Networks M Series Multiservice Edge Routers, T Series Core Routers, or MX Series 5G Universal Routing Platforms. When using ingress replication for IP multicast, each participating router must be configured with BGP for control plane procedures and with ingress replication for the data provider tunnel, which forms a full mesh of MPLS point-to-point LSPs. The ingress replication tunnel can be selective or inclusive, depending on the configuration of the provider tunnel in the routing instance.

Overview

IN THIS SECTION

- [Topology | 1079](#)

The `ingress-replication` provider tunnel type uses unicast tunnels between routers to create a multicast distribution tree.

The `mpls-internet-multicast` routing instance type uses ingress replication provider tunnels to carry IP multicast data between routers through an MPLS cloud, using MBGP (or Next Gen) MVPN. Ingress replication can also be configured when using MVPN to carry multicast data between PE routers.

The `mpls-internet-multicast` routing instance is a non-forwarding instance used only for control plane procedures. It does not support any interface configurations. Only one `mpls-internet-multicast` routing instance can be defined for a logical system. All multicast and unicast routes used for IP multicast are associated only with the default routing instance (`inet.0`), not with a configured routing instance. The `mpls-internet-multicast` routing instance type is configured for the default master instance on each router, and is also included at the `[edit protocols pim]` hierarchy level in the default instance.

For each `mpls-internet-multicast` routing instance, the `ingress-replication` statement is required under the `provider-tunnel` statement and also under the `[edit routing-instances routing-instance-name provider-tunnel selective group source]` hierarchy level.


When a new destination needs to be added to the ingress replication provider tunnel, the resulting behavior differs depending on how the ingress replication provider tunnel is configured:

- `create-new-ucast-tunnel`—When this statement is configured, a new unicast tunnel to the destination is created, and is deleted when the destination is no longer needed. Use this mode for RSVP LSPs using ingress replication.
- `label-switched-path-template (Multicast)`—When this statement is configured, an LSP template is used for the for the point-to-multipoint LSP for ingress replication.

Topology

The IP topology consists of routers on the edge of the IP multicast domain. Each router has a set of IP interfaces configured toward the MPLS cloud and a set of interfaces configured toward the IP routers. See [Figure 80 on page 1080](#). Internet multicast traffic is carried between the IP routers, through the MPLS cloud, using ingress replication tunnels for the data plane and a full-mesh IBGP session for the control plane.

Figure 80: Internet Multicast Topology



Configuration

IN THIS SECTION

- [Procedure](#) | [1081](#)

Procedure

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

Border Router C

```
set protocols mpls ipv6-tunneling
set protocols mpls interface all
set protocols bgp group ibgp type internal
set protocols bgp group ibgp local-address 10.255.10.61
set protocols bgp group ibgp family inet unicast
set protocols bgp group ibgp family inet-vpn any
set protocols bgp group ibgp family inet6 unicast
set protocols bgp group ibgp family inet6-vpn any
set protocols bgp group ibgp family inet-mvpn signaling
set protocols bgp group ibgp family inet6-mvpn signaling
set protocols bgp group ibgp export to-bgp
set protocols bgp group ibgp neighbor 10.255.10.97
set protocols bgp group ibgp neighbor 10.255.10.55
set protocols bgp group ibgp neighbor 10.255.10.57
set protocols bgp group ibgp neighbor 10.255.10.59
set protocols ospf traffic-engineering
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface lo0.0
set protocols ospf area 0.0.0.0 interface so-1/3/1.0
set protocols ospf area 0.0.0.0 interface so-0/3/0.0
set protocols ospf3 area 0.0.0.0 interface lo0.0
set protocols ospf3 area 0.0.0.0 interface so-1/3/1.0
set protocols ospf3 area 0.0.0.0 interface so-0/3/0.0
```

```

set protocols ldp interface all
set protocols pim rp static address 192.0.2.2
set protocols pim rp static address 2::192.0.2.2
set protocols pim interface fe-0/1/0.0
set protocols pim mpls-internet-multicast
set routing-instances test instance-type mpls-internet-multicast
set routing-instances test provider-tunnel ingress-replication label-switched-path
set routing-instances test protocols mvpn

```

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

The following example shows how to configure ingress replication on an IP multicast instance with the routing instance type `mpls-internet-multicast`. Additionally, this example shows how to configure a selective provider tunnel that selects a new unicast tunnel each time a new destination needs to be added to the multicast distribution tree.

This example shows the configuration of the link between Border Router C and edge IP Router C, from which Border Router C receives PIM join messages.

1. Enable MPLS.

```

[edit protocols mpls]
user@Border_Router_C# set ipv6-tunneling
user@Border_Router_C# set interface all

```

2. Configure a signaling protocol, such as RSVP or LDP.

```

[edit protocols ldp]
user@Border_Router_C# set interface all

```

3. Configure a full-mesh of IBGP peering sessions.

```

[edit protocols bgp group ibgp]
user@Border_Router_C# set type internal
user@Border_Router_C# set local-address 10.255.10.61
user@Border_Router_C# set neighbor 10.255.10.97

```

```

user@Border_Router_C# set neighbor 10.255.10.55
user@Border_Router_C# set neighbor 10.255.10.57
user@Border_Router_C# set neighbor 10.255.10.59
user@Border_Router_C# set export to-bgp

```

4. Configure the multiprotocol BGP-related settings so that the BGP sessions carry the necessary NLRI.

```

[edit protocols bgp group ibgp]
user@Border_Router_C# set family inet unicast
user@Border_Router_C# set family inet-vpn any
user@Border_Router_C# set family inet6 unicast
user@Border_Router_C# set family inet6-vpn any
user@Border_Router_C# set family inet-mvpn signaling
user@Border_Router_C# set family inet6-mvpn signaling

```

5. Configure an interior gateway protocol (IGP).

This example shows a dual stacking configuration with OSPF and OSPF version 3 configured on the interfaces.

```

[edit protocols ospf3]
user@Border_Router_C# set area 0.0.0.0 interface lo0.0
user@Border_Router_C# set area 0.0.0.0 interface so-1/3/1.0
user@Border_Router_C# set area 0.0.0.0 interface so-0/3/0.0
[edit protocols ospf]
user@Border_Router_C# set traffic-engineering
user@Border_Router_C# set area 0.0.0.0 interface fxp0.0 disable
user@Border_Router_C# set area 0.0.0.0 interface lo0.0
user@Border_Router_C# set area 0.0.0.0 interface so-1/3/1.0
user@Border_Router_C# set area 0.0.0.0 interface so-0/3/0.0

```

6. Configure a global PIM instance on the interface facing the edge device.

PIM is not configured in the core.

```

[edit protocols pim]
user@Border_Router_C# set rp static address 192.0.2.2
user@Border_Router_C# set rp static address 2::192.0.2.2
user@Border_Router_C# set interface fe-0/1/0.0
user@Border_Router_C# set mpls-internet-multicast

```

7. Configure the ingress replication provider tunnel to create a new unicast tunnel each time a destination needs to be added to the multicast distribution tree.

```
[edit routing-instances test]
user@Border_Router_C# set instance-type mpls-internet-multicast
user@Border_Router_C# set provider-tunnel ingress-replication label-switched-path
user@Border_Router_C# set protocols mvpn
```

NOTE: Alternatively, use the **label-switched-path-template** statement to configure a point-to-point LSP for the ingress tunnel.

Configure the point-to-point LSP to use the default template settings (this is needed only when using RSVP tunnels). For example:

```
[edit routing-instances test provider-tunnel]
user@Border_Router_C# set ingress-replication label-switched-path label-switched-path-
template default-template
user@Border_Router_C# set selective group 203.0.113.0/24 source 192.168.195.145/32 ingress-
replication label-switched-path
```

8. Commit the configuration.

```
user@Border_Router_C# commit
```

Results

From configuration mode, confirm your configuration by issuing the `show protocols` and `show routing-instances` command. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@Border_Router_C# show protocols
mpls {
    ipv6-tunneling;
    interface all;
}
bgp {
```

```

group ibgp {
    type internal;
    local-address 10.255.10.61;
    family inet {
        unicast;
    }
    family inet-vpn {
        any;
    }
    family inet6 {
        unicast;
    }
    family inet6-vpn {
        any;
    }
    family inet-mvpn {
        signaling;
    }
    family inet6-mvpn {
        signaling;
    }
    export to-bgp; ## 'to-bgp' is not defined
    neighbor 10.255.10.97;
    neighbor 10.255.10.55;
    neighbor 10.255.10.57;
    neighbor 10.255.10.59;
}
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface fxp0.0 {
            disable;
        }
        interface lo0.0;
        interface so-1/3/1.0;
        interface so-0/3/0.0;
    }
}
ospf3 {
    area 0.0.0.0 {
        interface lo0.0;
        interface so-1/3/1.0;
    }
}

```



```

        interface so-0/3/0.0;
    }
}
ldp {
    interface all;
}
pim {
    rp {
        static {
            address 192.0.2.2;
            address 2::192.0.2.2;
        }
    }
    interface fe-0/1/0.0;
    mpls-internet-multicast;
}

```

```

user@Border_Router_C# show routing-instances
test {
    instance-type mpls-internet-multicast;
    provider-tunnel {
        ingress-replication {
            label-switched-path;
        }
    }
    protocols {
        mvpn;
    }
}

```

Verification

IN THIS SECTION

- [Checking the Ingress Replication Status on Border Router C | 1087](#)
- [Checking the Routing Table for the MVPN Routing Instance on Border Router C | 1087](#)
- [Checking the MVPN Neighbors on Border Router C | 1089](#)
- [Checking the PIM Join Status on Border Router C | 1090](#)

- [Checking the Multicast Route Status on Border Router C | 1091](#)
- [Checking the Ingress Replication Status on Border Router B | 1091](#)
- [Checking the Routing Table for the MVPN Routing Instance on Border Router B | 1092](#)
- [Checking the MVPN Neighbors on Border Router B | 1093](#)
- [Checking the PIM Join Status on Border Router B | 1094](#)
- [Checking the Multicast Route Status on Border Router B | 1095](#)

Confirm that the configuration is working properly. The following operational output is for LDP ingress replication SPT-only mode. The multicast source behind IP Router B. The multicast receiver is behind IP Router C.

Checking the Ingress Replication Status on Border Router C

Purpose

Use the `show ingress-replication mvpn` command to check the ingress replication status.

Action

```
user@Border_Router_C> show ingress-replication mvpn

Ingress Tunnel: mvpn:1
Application: MVPN
Unicast tunnels
  Leaf Address      Tunnel-type  Mode      State
  10.255.10.61      P2P LSP     Existing   Up
```

Meaning

The ingress replication is using a point-to-point LSP, and is in the Up state.

Checking the Routing Table for the MVPN Routing Instance on Border Router C

Purpose

Use the `show route table` command to check the route status.

Action

```

user@Border_Router_C> show route table test.mvpn

test.mvpn.0: 5 destinations, 7 routes (5 active, 1 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1:0:0:10.255.10.61/240
    *[BGP/170] 00:45:55, localpref 100, from 10.255.10.61
    AS path: I, validation-state: unverified
    > via so-2/0/1.0
1:0:0:10.255.10.97/240
    *[MVPN/70] 00:47:19, metric2 1
    Indirect
5:0:0:32:192.168.195.106:32:198.51.100.1/240
    *[PIM/105] 00:06:35
    Multicast (IPv4) Composite
    [BGP/170] 00:06:35, localpref 100, from 10.255.10.61
    AS path: I, validation-state: unverified
    > via so-2/0/1.0
6:0:0:1000:32:192.0.2.2:32:198.51.100.1/240
    *[PIM/105] 00:07:03
    Multicast (IPv4) Composite
7:0:0:1000:32:192.168.195.106:32:198.51.100.1/240
    *[MVPN/70] 00:06:35, metric2 1
    Multicast (IPv4) Composite
    [PIM/105] 00:05:35
    Multicast (IPv4) Composite

test.mvpn-inet6.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1:0:0:10.255.10.61/432
    *[BGP/170] 00:45:55, localpref 100, from 10.255.10.61
    AS path: I, validation-state: unverified
    > via so-2/0/1.0
1:0:0:10.255.10.97/432
    *[MVPN/70] 00:47:19, metric2 1
    Indirect

```

Meaning

The expected routes are populating the test.mvpn routing table.

Checking the MVPN Neighbors on Border Router C

Purpose

Use the `show mvpn neighbor` command to check the neighbor status.

Action

```
user@Border_Router_C> show mvpn neighbor
```

```
MVPN instance:
```

```
Legend for provider tunnel
```

```
S-    Selective provider tunnel
```

```
Legend for c-multicast routes properties (Pr)
```

```
DS -- derived from (*, c-g)          RM -- remote VPN route
```

```
Family : INET
```

```
Instance : test
```

```
  MVPN Mode : SPT-ONLY
```

```
  Neighbor
```

```
  10.255.10.61
```

```
    Inclusive Provider Tunnel
```

```
    INGRESS-REPLICATION:MPLS Label 16:10.255.10.61
```

```
MVPN instance:
```

```
Legend for provider tunnel
```

```
S-    Selective provider tunnel
```

```
Legend for c-multicast routes properties (Pr)
```

```
DS -- derived from (*, c-g)          RM -- remote VPN route
```

```
Family : INET6
```

```
Instance : test
```

```
  MVPN Mode : SPT-ONLY
```

```
  Neighbor
```

```
  10.255.10.61
```

```
    Inclusive Provider Tunnel
```

```
    INGRESS-REPLICATION:MPLS Label 16:10.255.10.61
```

Checking the PIM Join Status on Border Router C

Purpose

Use the `show pim join extensive` command to check the PIM join status.

Action

```

user@Border_Router_C> show pim join extensive
Instance: PIM.master Family: INET
R = Rendezvous Point Tree, S = Sparse, W = Wildcard

Group: 198.51.100.1
  Source: *
  RP: 192.0.2.2
  Flags: sparse,rptree,wildcard
  Upstream interface: Local
  Upstream neighbor: Local
  Upstream state: Local RP
  Uptime: 00:07:49
  Downstream neighbors:
    Interface: ge-3/0/6.0
      192.0.2.2 State: Join Flags: SRW Timeout: Infinity
      Uptime: 00:07:49 Time since last Join: 00:07:49
  Number of downstream interfaces: 1

Group: 198.51.100.1
  Source: 192.168.195.106
  Flags: sparse
  Upstream protocol: BGP
  Upstream interface: Through BGP
  Upstream neighbor: Through MVPN
  Upstream state: Local RP, Join to Source, No Prune to RP
  Keepalive timeout: 69
  Uptime: 00:06:21
  Number of downstream interfaces: 0

Instance: PIM.master Family: INET6
R = Rendezvous Point Tree, S = Sparse, W = Wildcard

```

Checking the Multicast Route Status on Border Router C

Purpose

Use the `show multicast route extensive` command to check the multicast route status.

Action

```
user@Border_Router_C> show multicast route extensive
Instance: master Family: INET

Group: 198.51.100.1
  Source: 192.168.195.106/32
  Upstream interface: lsi.0
  Downstream interface list:
    ge-3/0/6.0
  Number of outgoing interfaces: 1
  Session description: NOB Cross media facilities
  Statistics: 18 kbps, 200 pps, 88907 packets
  Next-hop ID: 1048577
  Upstream protocol: MVPN
  Route state: Active
  Forwarding state: Forwarding
  Cache lifetime/timeout: forever
  Wrong incoming interface notifications: 0
  Uptime: 00:07:25

Instance: master Family: INET6
```

Checking the Ingress Replication Status on Border Router B

Purpose

Use the `show ingress-replication mvpn` command to check the ingress replication status.

Action

```
user@Border_Router_B> show ingress-replication mvpn
```

```
Ingress Tunnel: mvpn:1
Application: MVPN
Unicast tunnels
  Leaf Address      Tunnel-type  Mode      State
  10.255.10.97      P2P LSP     Existing   Up
```

Meaning

The ingress replication is using a point-to-point LSP, and is in the Up state.

Checking the Routing Table for the MVPN Routing Instance on Border Router B

Purpose

Use the `show route table` command to check the route status.

Action

```
user@Border_Router_B> show route table test.mvpn

test.mvpn.0: 5 destinations, 7 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1:0:0:10.255.10.61/240
    *[MVPN/70] 00:49:26, metric2 1
    Indirect
1:0:0:10.255.10.97/240
    *[BGP/170] 00:48:22, localpref 100, from 10.255.10.97
    AS path: I, validation-state: unverified
    > via so-1/3/1.0
5:0:0:32:192.168.195.106:32:198.51.100.1/240
    *[PIM/105] 00:09:02
    Multicast (IPv4) Composite
    [BGP/170] 00:09:02, localpref 100, from 10.255.10.97
    AS path: I, validation-state: unverified
    > via so-1/3/1.0
7:0:0:1000:32:192.168.195.106:32:198.51.100.1/240
    *[PIM/105] 00:09:02
    Multicast (IPv4) Composite
    [BGP/170] 00:09:02, localpref 100, from 10.255.10.97
    AS path: I, validation-state: unverified
```

```

> via so-1/3/1.0

test.mvpn-inet6.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1:0:0:10.255.10.61/432
    *[MVPN/70] 00:49:26, metric2 1
    Indirect
1:0:0:10.255.10.97/432
    *[BGP/170] 00:48:22, localpref 100, from 10.255.10.97
    AS path: I, validation-state: unverified
    > via so-1/3/1.0

```

Meaning

The expected routes are populating the test.mvpn routing table.

Checking the MVPN Neighbors on Border Router B

Purpose

Use the `show mvpn neighbor` command to check the neighbor status.

Action

```

user@Border_Router_B> show mvpn neighbor

MVPN instance:
Legend for provider tunnel
S-   Selective provider tunnel

Legend for c-multicast routes properties (Pr)
DS -- derived from (*, c-g)      RM -- remote VPN route
Family : INET

Instance : test
MVPN Mode : SPT-ONLY
Neighbor                               Inclusive Provider Tunnel
10.255.10.97                           INGRESS-REPLICATION:MPLS Label 16:10.255.10.97

MVPN instance:

```


Legend for provider tunnel

S- Selective provider tunnel

Legend for c-multicast routes properties (Pr)

DS -- derived from (*, c-g) RM -- remote VPN route

Family : INET6

Instance : test

MVPN Mode : SPT-ONLY

Neighbor

10.255.10.97

Inclusive Provider Tunnel

INGRESS-REPLICATION:MPLS Label 16:10.255.10.97

Checking the PIM Join Status on Border Router B

Purpose

Use the `show pim join extensive` command to check the PIM join status.

Action

```
user@Border_Router_B> show pim join extensive
```

```
Instance: PIM.master Family: INET
```

```
R = Rendezvous Point Tree, S = Sparse, W = Wildcard
```

```
Group: 198.51.100.1
```

```
Source: 192.168.195.106
```

```
Flags: sparse,spt
```

```
Upstream interface: fe-0/1/0.0
```

```
Upstream neighbor: Direct
```

```
Upstream state: Local Source
```

```
Keepalive timeout: 0
```

```
Uptime: 00:09:39
```

```
Downstream neighbors:
```

```
Interface: Pseudo-MVPN
```

```
Uptime: 00:09:39 Time since last Join: 00:09:39
```

```
Number of downstream interfaces: 1
```

```
Instance: PIM.master Family: INET6
```

```
R = Rendezvous Point Tree, S = Sparse, W = Wildcard
```

Checking the Multicast Route Status on Border Router B

Purpose

Use the `show multicast route extensive` command to check the multicast route status.

Action

```
user@Border_Router_B> show multicast route extensive
Instance: master Family: INET

Group: 198.51.100.1
  Source: 192.168.195.106/32
  Upstream interface: fe-0/1/0.0
  Downstream interface list:
    so-1/3/1.0
  Number of outgoing interfaces: 1
  Session description: NOB Cross media facilities
  Statistics: 18 kbps, 200 pps, 116531 packets
  Next-hop ID: 1048580
  Upstream protocol: MVPN
  Route state: Active
  Forwarding state: Forwarding
  Cache lifetime/timeout: forever
  Wrong incoming interface notifications: 0
  Uptime: 00:09:43
```

RELATED DOCUMENTATION

Configuring Routing Instances for an MBGP MVPN

mpls-internet-multicast

ingress-replication

create-new-ucast-tunnel

label-switched-path-template (Multicast)

show ingress-replication mvpn

Mapping VPLS Traffic to Specific LSPs

You can map VPLS traffic to specific LSPs by configuring forwarding table policies. This procedure is optional but can be useful. The following example illustrates how you can map lower priority VPLS routing instances to slower LSPs while mapping other higher priority VPLS routing instances to faster LSPs. In this example configuration, **a-to-b1** and **a-to-c1** are high-priority LSPs between the PE routers, while **a-to-b2** and **a-to-c2** are low-priority LSPs between the PE routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

To map VPLS traffic, include the policy-statement `vpls-priority` statement:

```
policy-statement vpls-priority {
  term a {
    from {
      rib mpls.0;
      community company-1;
    }
    then {
      install-nexthop lsp [ a-to-b1 a-to-c1 ];
      accept;
    }
  }
  term b {
    from {
      rib mpls.0;
      community company-2;
    }
    then {
      install-nexthop lsp-regex [ "^a-to-b2$" "^a-to-c2$" ];
      accept;
    }
  }
}
community company-1 members target:11111:1;
community company-2 members target:11111:2;
```

You can include the policy-statement `vpls-priority` statement at the following hierarchy levels:

- [edit policy-options]
- [edit logical-systems *logical-system-name* policy-options]

Include the export statement to apply the vpls-priority policy to the forwarding table:

```
export vpls-priority;
```

You can include this statement at the following hierarchy levels:

- [edit routing-options forwarding-table]
- [edit logical-systems *logical-system-name* routing-options forwarding-table]

For more information about how to configure routing policies, see the [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

Configuring Inter-AS VPLS and IRB VPLS

IN THIS CHAPTER

- [Example: Configuring Inter-AS VPLS with MAC Processing at the ASBR | 1098](#)
- [Configuring VPLS and Integrated Routing and Bridging | 1134](#)
- [Configuring Integrated Routing and Bridging in a VPLS Instance \(MX Series Routers Only\) | 1137](#)
- [Configuring L2PT for VPLS | 1137](#)

Example: Configuring Inter-AS VPLS with MAC Processing at the ASBR

IN THIS SECTION

- [Requirements | 1098](#)
- [Overview and Topology | 1099](#)
- [Configuration | 1100](#)

This example describes how to configure inter-AS Virtual Private LAN Service (VPLS) with MAC processing between BGP-signaled VPLS and LDP-signaled VPLS. This feature is described in RFC 4761 as multi-AS VPLS option E or method E.

This example is organized in the following sections:

Requirements

To support inter-AS VPLS between BGP-signaled VPLS and LDP-signaled VPLS, your network must meet the following hardware and software requirements:

- MX Series or M320 routers for the ASBRs.
- Junos OS Release 9.3 or higher.

- Gigabit Ethernet or 10-Gigabit Ethernet interfaces.

Overview and Topology

IN THIS SECTION

- [Topology | 1100](#)

VPLS is a key enabler for delivering multipoint Ethernet service. Major service providers have implemented IP and MPLS backbones and offer VPLS services to large enterprises. Growing demand requires the VPLS network to scale to support many VPLS customers with multiple sites spread across geographically dispersed regions. BGP-signaled VPLS signaling offers scaling advantages over LDP-signaled VPLS. In some environments there is a need for BGP-signaled VPLS to interoperate with existing LDP-signaled VPLS.

This example shows one way to configure BGP-signaled VPLS interworking with an existing LDP-signaled VPLS network.

The advantages of the configuration are:

- You can interconnect customer sites that are spread across different autonomous systems (ASs).
- LDP-signaled VPLS and BGP-signaled VPLS interworking is supported.
- Because the ASBR supports MAC operations, customer sites can be connected directly to the ASBR.
- The inter-AS link is not restricted to Ethernet interfaces.
- Additional configuration for multihoming is relatively straightforward.

Traffic from the interworking virtual private LAN services is switched at the ASBR. The ASBR does all the data plane operations: flooding, MAC learning, aging, and MAC forwarding for each AS to switch traffic among any customer facing interfaces and between the fully meshed pseudowires in the AS. A single pseudowire is created between the ASBRs across the inter-AS link and the ASBRs forward traffic from the pseudowires in each AS to the peer ASBR.

Each ASBR performs VPLS operations within its own AS and performs VPLS operations with the ASBR in the other AS. The ASBR treats the other AS as a BGP-signaled VPLS site. To establish VPLS pseudowires, VPLS NLRI messages are exchanged across the EBGp sessions on the inter-AS links between the ASBRs.

The sample metro network is configured for LDP-signaled VPLS. The core network is configured for BGP-signaled VPLS.


The first part of the example shows the basic configuration steps to configure the logical interfaces, OSPF, internal BGP, LDP, and MPLS. This part of the configuration is the same as other VPLS configurations for LDP-signaled VPLS and BGP-signaled VPLS.

The unique part of the example is configured in the VPLS routing instances, external BGP, and the policy that populates the BGP route table with routes learned from direct routes and OSPF routes. Additional details about the configuration statements are included in the step-by-step procedure.

[Figure 81 on page 1100](#) shows the topology used in this example.

Topology

Figure 81: Inter-AS VPLS with MAC Operations Example Topology



Configuration

IN THIS SECTION

- [Configuring Interfaces | 1101](#)
- [Configuring OSPF | 1104](#)
- [Configuring the Internal BGP Peer Group | 1106](#)
- [Configuring LDP | 1108](#)
- [Configuring MPLS | 1109](#)
- [Configuring the External BGP Peer Group Between the Loopback Interfaces | 1110](#)

- [Configuring the External BGP Peer Group Between the Inter-AS Link Interfaces | 1111](#)
- [Configuring the VPLS Routing Instances | 1117](#)
- [Results | 1121](#)

To configure inter-AS VPLS between BGP-signaled VPLS and LDP-signaled VPLS, perform these tasks.

NOTE: In any configuration session it is a good practice to periodically use the `commit check` command to verify that the configuration can be committed.

Configuring Interfaces

Step-by-Step Procedure

To configure interfaces:

1. On each router, configure an IP address on the loopback logical interface 0 (lo0.0):

```
user@CE1# set interfaces lo0 unit 0 family inet address 192.168.1.1/32 primary
user@PE1# set interfaces lo0 unit 0 family inet address 192.168.2.1/32 primary
user@ASBR1# set interfaces lo0 unit 0 family inet address 192.168.3.1/32 primary
user@ASBR2# set interfaces lo0 unit 0 family inet address 192.168.10.1/32 primary
user@PE2# set interfaces lo0 unit 0 family inet address 192.168.11.1/32 primary
user@CE2# set interfaces lo0 unit 0 family inet address 192.168.12.1/32 primary
```


2. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

3. On each router, display the interface information for lo0 and verify that the correct IP address is configured:

```
user@host> show interfaces lo0
```

```
Physical interface: lo0, Enabled, Physical link is Up
```

```
Interface index: 6, SNMP ifIndex: 6
```

```
Type: Loopback, MTU: Unlimited
```

```
Device flags   : Present Running Loopback
```

```
Interface flags: SNMP-Traps
```

```
Link flags     : None
```

```
Last flapped   : Never
```

```
Input packets  : 0
```

```
Output packets: 0
```

```
Logical interface lo0.0 (Index 75) (SNMP ifIndex 16)
```

```
Flags: SNMP-Traps Encapsulation: Unspecified
```

```
Input packets : 0
```

```
Output packets: 0
```

```
Protocol inet, MTU: Unlimited
```

```
Flags: None
```

```
Addresses
```

```
Local: 127.0.0.1
```

```
Addresses, Flags: Primary Is-Default Is-Primary
```

```
Local: 192.168.3.1
```

```
Logical interface lo0.16384 (Index 64) (SNMP ifIndex 21)
```

```
Flags: SNMP-Traps Encapsulation: Unspecified
```

```

Input packets : 0
Output packets: 0
Protocol inet, MTU: Unlimited
  Flags: None
  Addresses
    Local: 127.0.0.1

Logical interface lo0.16385 (Index 65) (SNMP ifIndex 22)
  Flags: SNMP-Traps Encapsulation: Unspecified
Input packets : 0
Output packets: 0
Protocol inet, MTU: Unlimited
  Flags: None

```

In the example above notice that the primary lo0 local address for the inet protocol family on Router ASBR1 is 192.168.3.1.

4. On each router, configure an IP address and protocol family on the Gigabit Ethernet interfaces. Specify the inet protocol family.

```

user@CE1# set interfaces ge-0/3/0 unit 0 family inet address 10.10.11.1/24
user@PE1# set interfaces ge-1/3/1 unit 0 family inet address 10.0.23.9/30
user@ASBR1# set interfaces ge-0/3/1 unit 0 family inet address 10.0.23.10/30
user@ASBR1# set interfaces ge-0/3/0 unit 0 family inet address 10.0.78.1/30
user@ASBR2# set interfaces ge-3/1/0 unit 0 family inet address 10.0.78.2/30
user@ASBR2# set interfaces ge-3/1/1 unit 0 family inet address 10.0.90.13/30
user@PE2# set interfaces ge-0/1/0 unit 0 family inet address 10.0.90.14/30
user@CE2# set interfaces ge-0/1/1 unit 0 family inet address 10.10.11.2/24

```

5. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

6. Display information for Gigabit Ethernet interfaces and verify that the IP address and protocol family are configured correctly.

```
user@ASBR2> show interfaces ge-* terse
```

Interface	Admin	Link	Proto	Local	Remote
ge-3/1/0	up	up			
ge-3/1/0.0	up	up	inet	10.0.78.2/30	
			multiservice		
ge-3/1/1	up	up			
ge-3/1/1.0	up	up	inet	10.0.90.13/30	
			multiservice		
ge-3/1/2	up	down			
ge-3/1/3	up	down			

Configuring OSPF

Step-by-Step Procedure

To configure OSPF:

1. On the PE and ASBR routers, configure the provider instance of OSPF. Configure OSPF traffic engineering support. Specify area 0.0.0.1 in the LDP-signaled VPLS network and area 0.0.0.0 in the

BGP-signaled network. Specify the Gigabit Ethernet logical interfaces between the PE and ASBR routers. Specify `lo0.0` as a passive interface.

```

user@PE1# set protocols ospf traffic-engineering
user@PE1# set protocols ospf area 0.0.0.1 interface ge-1/3/1.0
user@PE1# set protocols ospf area 0.0.0.1 interface lo0.0 passive
user@ASBR1# set protocols ospf traffic-engineering
user@ASBR1# set protocols ospf area 0.0.0.1 interface ge-0/3/1.0
user@ASBR1# set protocols ospf area 0.0.0.1 interface lo0.0 passive
user@ASBR2# set protocols ospf traffic-engineering
user@ASBR2# set protocols ospf area 0.0.0.0 interface ge-3/1/1.0
user@ASBR2# set protocols ospf area 0.0.0.0 interface lo0.0 passive
user@PE2# set protocols ospf traffic-engineering
user@PE2# set protocols ospf area 0.0.0.0 interface ge-0/1/0.0
user@PE2# set protocols ospf area 0.0.0.0 interface lo0.0 passive

```

2. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

3. Display OSPF neighbor information and verify that the PE routers form adjacencies with the ASBR router in the same area. Verify that the neighbor state is Full.

```

user@host> show ospf neighbor

```

Address	Interface	State	ID	Pri	Dead
10.0.23.10	ge-1/3/1.0	Full	192.168.3.1	128	31

Configuring the Internal BGP Peer Group

Step-by-Step Procedure

The purpose of configuring an internal BGP peer group is to create a full mesh of BGP LSPs among the PE routers in the BGP-signaled AS, including the ASBR routers.

To configure the internal BGP peer group:

1. The purpose of this step is to create a full mesh of IBGP peers between the PE routers, including the ASBR routers, within the BGP-signaled AS.

On Router ASBR2, configure internal BGP. Specify the BGP type as `internal`. Specify the local address as the local `100` IP address.

Specify the `inet` protocol family. Specify the `labeled-unicast` statement and the `resolve-vpn` option. The `labeled-unicast` statement causes the router to advertise labeled routes out of the IPv4 `inet.0` route table and places labeled routes into the `inet.0` route table. The `resolve-vpn` option puts labeled routes in the MPLS `inet.3` route table. The `inet.3` route table is used to resolve routes for the PE router located in the other AS.

Specify the `l2vpn` family to indicate to the router that this is a VPLS. Specify the `signaling` option to configure BGP as the signaling protocol. This enables BGP to carry Layer 2 VPLS NLRI messages for this peer group.

Specify the `100` interface IP address of the PE as the neighbor. Configure an autonomous system identifier.

```
user@ASBR2# set protocols bgp group core-ibgp type internal
user@ASBR2# set protocols bgp group core-ibgp local-address 192.168.10.1
user@ASBR2# set protocols bgp group core-ibgp family inet labeled-unicast resolve-vpn
user@ASBR2# set protocols bgp group core-ibgp family l2vpn signaling
user@ASBR2# set protocols bgp group core-ibgp neighbor 192.168.11.1
user@ASBR2# set routing-options autonomous-system 0.65020
```

2. On Router PE2, configure internal BGP. Specify the BGP type as `internal`. Specify the local address as the local `100` IP address.

Specify the `l2vpn` family to indicate this is a VPLS. Specify the `signaling` option to configure BGP as the signaling protocol. This enables BGP to carry Layer 2 VPLS NLRI messages.

Specify the lo0 interface IP address of Router ASBR2 as the neighbor. Configure an autonomous system identifier.

```
user@PE2# set protocols bgp group core-ibgp type internal
user@PE2# set protocols bgp group core-ibgp local-address 192.168.11.1
user@PE2# set protocols bgp group core-ibgp family l2vpn signaling
user@PE2# set protocols bgp group core-ibgp neighbor 192.168.10.1
user@PE2# set routing-options autonomous-system 0.65020
```

3. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

4. On Router PE2 and Router ASBR2, display BGP neighbor information and verify that the peer connection state is Established.

```
user@ASBR2> show bgp neighbor
Peer: 192.168.11.1+49443 AS 65020 Local: 192.168.10.1+179 AS 65020
  Type: Internal    State: Established    Flags: ImportEval Sync
  Last State: OpenConfirm  Last Event: RecvKeepAlive
  Last Error: None
  Options: Preference LocalAddress AddressFamily Rib-group Refresh
  Address families configured: l2vpn-signaling inet-labeled-unicast
  Local Address: 192.168.10.1 Holdtime: 90 Preference: 170
  Number of flaps: 0
  Peer ID: 192.168.11.1      Local ID: 192.168.10.1      Active Holdtime: 90
  Keepalive Interval: 30      Peer index: 0
...

```

Configuring LDP

Step-by-Step Procedure

To configure LDP:

1. On the PE and ASBR routers, configure LDP with the Gigabit Ethernet interfaces between the PE and ASBR routers, and between the two ASBR routers. To support LDP-signaled VPLS, additionally configure LDP with the `lo0.0` interface on Router PE1 and Router ASBR1:

```
user@PE1# set protocols ldp interface ge-1/3/1.0
user@PE1# set protocols ldp interface lo0.0
user@ASBR1# set protocols ldp interface ge-0/3/1.0
user@ASBR1# set protocols ldp interface ge-0/3/0.0
user@ASBR1# set protocols ldp interface lo0.0
user@ASBR2# set protocols ldp interface ge-3/1/0.0
user@ASBR2# set protocols ldp interface ge-3/1/1.0
user@PE2# set protocols ldp interface ge-0/1/0.0
```

NOTE: The configuration of LDP signaling between the ASBR routers is not required for Inter-AS VPLS. It is included here for reference only and might be used in LDP environments.

2. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

3. Display LDP configuration information and verify that the correct interfaces are configured. LDP operation can be verified after MPLS is configured.

```
user@ASBR1> show configuration protocols ldp
interface ge-0/3/0.0;
interface ge-0/3/1.0;
interface lo0.0;
```

The preceding example is from ASBR1.

Configuring MPLS

Step-by-Step Procedure

To configure MPLS:

1. On the PE and ASBR routers, configure MPLS. Enable MPLS on the logical interfaces. Add the Gigabit Ethernet interfaces to the MPLS protocol. This adds entries to the MPLS forwarding table.

```
user@PE1# set protocols mpls interface ge-1/3/1.0
user@PE1# set interfaces ge-1/3/1 unit 0 family mpls
user@ASBR1# set protocols mpls interface ge-0/3/1.0
user@ASBR1# set protocols mpls interface ge-0/3/0.0
user@ASBR1# set interfaces ge-0/3/1 unit 0 family mpls
user@ASBR1# set interfaces ge-0/3/0 unit 0 family mpls
user@ASBR2# set protocols mpls interface ge-3/1/0.0
user@ASBR2# set protocols mpls interface ge-3/1/1.0
user@ASBR2# set interfaces ge-3/1/0 unit 0 family mpls
user@ASBR2# set interfaces ge-3/1/1 unit 0 family mpls
user@PE2# set protocols mpls interface ge-0/1/0.0
user@PE2# set interfaces ge-0/1/0 unit 0 family mpls
```


2. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

3. On the PE and ASBR routers, display LDP neighbor information and verify that the directly connected LDP neighbors are listed:

```
user@ASBR1> show ldp neighbor
```

Address	Interface	Label space ID	Hold time
192.168.2.1	lo0.0	192.168.2.1:0	44
10.0.78.2	ge-0/3/0.0	192.168.10.1:0	13
10.0.23.9	ge-0/3/1.0	192.168.2.1:0	11

The preceding example is from ASBR1.

Configuring the External BGP Peer Group Between the Loopback Interfaces

Step-by-Step Procedure

To configure the external BGP (EBGP) peer group between the loopback interfaces:

1. On Router ASBR1 and Router PE1, configure an autonomous system identifier:

```
user@PE1# set routing-options autonomous-system 0.65010
user@ASBR1# set routing-options autonomous-system 0.65010
```

2. On Router ASBR1, configure an external BGP peer group for the loopback interfaces. Specify the external BGP group type. Include the `multihop` statement. Specify the local address as the local lo0 IP

address. Configure the `l2vpn` family for BGP signaling. Configure the peer AS as the core AS number. Specify the `100` IP address of Router ASBR2 as the neighbor.

```
user@ASBR1# set protocols bgp group vpls-core type external
user@ASBR1# set protocols bgp group vpls-core multihop
user@ASBR1# set protocols bgp group vpls-core local-address 192.168.3.1
user@ASBR1# set protocols bgp group vpls-core family l2vpn signaling
user@ASBR1# set protocols bgp group vpls-core peer-as 65020
user@ASBR1# set protocols bgp group vpls-core neighbor 192.168.10.1
```

3. On Router ASBR2, configure an external BGP peer group for the loopback interfaces. Specify the external BGP group type. Include the `multihop` statement. The `multihop` statement is needed because the EBGP neighbors are in different ASs. Specify the local address as the local `100` IP address. Configure the `l2vpn` family for BGP signaling. Configure the peer AS as the metro AS number. Specify the `100` IP address of Router ASBR1 as the neighbor.

```
user@ASBR2# set protocols bgp group vpls-metro type external
user@ASBR2# set protocols bgp group vpls-metro multihop
user@ASBR2# set protocols bgp group vpls-metro local-address 192.168.10.1
user@ASBR2# set protocols bgp group vpls-metro family l2vpn signaling
user@ASBR2# set protocols bgp group vpls-metro peer-as 65010
user@ASBR2# set protocols bgp group vpls-metro neighbor 192.168.3.1
```

4. On each router, commit the configuration:

```
user@host> commit
```

Configuring the External BGP Peer Group Between the Inter-AS Link Interfaces

Step-by-Step Procedure

The purpose of configuring external BGP peer groups between the inter-AS link interfaces is to create a full mesh of BGP LSPs among the ASBR routers. To configure the external BGP peer group between the inter-AS link interfaces:

1. On Router ASBR1, configure a policy to export OSPF and direct routes, including the 100 address of the PE routers, into BGP for the establishment of label-switched paths (LSPs):

```

user@ASBR1# set policy-options policy-statement loopback term term1 from protocol ospf
user@ASBR1# set policy-options policy-statement loopback term term1 from protocol direct
user@ASBR1# set policy-options policy-statement loopback term term1 from route-filter
192.168.0.0/16 longer
user@ASBR1# set policy-options policy-statement loopback term term1 then accept

```

2. On Router ASBR1, configure an external BGP peer group for the inter-AS link. Specify the external BGP group type. Specify the local inter-AS link IP address as the local address. Configure the inet family and include the labeled-unicast and resolve-vpn statements. The labeled-unicast statement advertises labeled routes out of the IPv4 inet.0 route table and places labeled routes into the inet.0 route table. The resolve-vpn option stores labeled routes in the MPLS inet.3 route table.

Include the export statement and specify the policy you created. Configure the peer AS as the core AS number. Specify the inter-AS link IP address of Router ASBR2 as the neighbor.

```

user@ASBR1# set protocols bgp group metro-core type external
user@ASBR1# set protocols bgp group metro-core local-address 10.0.78.1
user@ASBR1# set protocols bgp group metro-core family inet labeled-unicast resolve-vpn
user@ASBR1# set protocols bgp group metro-core export loopback
user@ASBR1# set protocols bgp group metro-core peer-as 65020
user@ASBR1# set protocols bgp group metro-core neighbor 10.0.78.2

```

3. On Router ASBR2, configure a policy to export OSPF and direct routes, including the 100 address, into BGP for the establishment of LSPs:

```

user@ASBR2# set policy-options policy-statement loopback term term1 from protocol ospf
user@ASBR2# set policy-options policy-statement loopback term term1 from protocol direct
user@ASBR2# set policy-options policy-statement loopback term term1 from route-filter
192.168.0.0/16 longer
user@ASBR2# set policy-options policy-statement loopback term term1 then accept

```

4. On Router ASBR2, configure an external BGP peer group for the inter-AS link. Specify the external BGP group type. Specify the local inter-AS link IP address as the local address. Configure the inet family and include the labeled-unicast and resolve-vpn statements. Include the export statement and

specify the policy you created. Configure the peer AS as the core AS number. Specify the inter-AS link IP address of Router ASBR1 as the neighbor.

```
user@ASBR2# set protocols bgp group core-metro type external
user@ASBR2# set protocols bgp group core-metro local-address 10.0.78.2
user@ASBR2# set protocols bgp group core-metro family inet labeled-unicast resolve-vpn
user@ASBR2# set protocols bgp group core-metro export loopback
user@ASBR2# set protocols bgp group core-metro peer-as 65010
user@ASBR2# set protocols bgp group core-metro neighbor 10.0.78.1
```

5. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

6. On Router ASBR1, display the BGP neighbors. Verify that the first peer is the IP address of the Gigabit Ethernet interface of Router ASBR2. Verify that the second peer is the IP address of the lo0 interface of Router ASBR2. Also verify that the state of each peer is Established. Notice that on Router ASBR1 the NLRI advertised by Router ASBR2 the inter-AS link peer is inet-labeled-unicast and the NLRI advertised by Router ASBR2 the loopback interface peer is l2vpn-signaling.

```
user@ASBR1> show bgp neighbor
Peer: 10.0.78.2+65473 AS 65020 Local: 10.0.78.1+179 AS 65010
  Type: External    State: Established    Flags: Sync
  Last State: OpenConfirm  Last Event: RecvKeepAlive
  Last Error: Cease
  Export: [ loopback ]
  Options: Preference LocalAddress AddressFamily PeerAS Rib-group Refresh
  Address families configured: inet-labeled-unicast
  Local Address: 10.0.78.1 Holdtime: 90 Preference: 170
  Number of flaps: 3
```

```

Last flap event: Stop
Error: 'Cease' Sent: 1 Recv: 2
Peer ID: 192.168.10.1      Local ID: 192.168.3.1      Active Holdtime: 90
Keepalive Interval: 30      Peer index: 0
BFD: disabled, down
Local Interface: ge-0/3/0.0
NLRI for restart configured on peer: inet-labeled-unicast
NLRI advertised by peer: inet-labeled-unicast
NLRI for this session: inet-labeled-unicast
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: inet-labeled-unicast
NLRI that restart is negotiated for: inet-labeled-unicast
NLRI of received end-of-rib markers: inet-labeled-unicast
NLRI of all end-of-rib markers sent: inet-labeled-unicast
Peer supports 4 byte AS extension (peer-as 65020)
Table inet.0 Bit: 10000
  RIB State: BGP restart is complete
  Send state: in sync
  Active prefixes:          2
  Received prefixes:        3
  Accepted prefixes:        3
  Suppressed due to damping: 0
  Advertised prefixes:      3
Last traffic (seconds): Received 8    Sent 3    Checked 60
Input messages:  Total 8713    Updates 3      Refreshes 0      Octets 165688
Output messages: Total 8745    Updates 2      Refreshes 0      Octets 166315
Output Queue[0]: 0

Peer: 192.168.10.1+51234 AS 65020 Local: 192.168.3.1+179 AS 65010
Type: External    State: Established    Flags: Sync
Last State: OpenConfirm    Last Event: RecvKeepAlive
Last Error: Cease
Options: Multihop Preference LocalAddress AddressFamily PeerAS Rib-group Refresh
Address families configured: l2vpn-signaling
Local Address: 192.168.3.1 Holdtime: 90 Preference: 170
Number of flaps: 3
Last flap event: Stop
Error: 'Cease' Sent: 1 Recv: 2
Peer ID: 192.168.10.1      Local ID: 192.168.3.1      Active Holdtime: 90
Keepalive Interval: 30      Peer index: 0

```

```

BFD: disabled, down
NLRI for restart configured on peer: l2vpn-signaling
NLRI advertised by peer: l2vpn-signaling
NLRI for this session: l2vpn-signaling
Peer supports Refresh capability (2)
Restart time configured on the peer: 120
Stale routes from peer are kept for: 300
Restart time requested by this peer: 120
NLRI that peer supports restart for: l2vpn-signaling
NLRI that restart is negotiated for: l2vpn-signaling
NLRI of received end-of-rib markers: l2vpn-signaling
NLRI of all end-of-rib markers sent: l2vpn-signaling
Peer supports 4 byte AS extension (peer-as 65020)
Table bgp.l2vpn.0 Bit: 20000
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: in sync
  Active prefixes:          1
  Received prefixes:        1
  Accepted prefixes:        1
  Suppressed due to damping: 0
  Advertised prefixes:      1
Table inter-as.l2vpn.0
  RIB State: BGP restart is complete
  RIB State: VPN restart is complete
  Send state: not advertising
  Active prefixes:          1
  Received prefixes:        1
  Accepted prefixes:        1
  Suppressed due to damping: 0
Last traffic (seconds): Received 19   Sent 18   Checked 42
Input messages:  Total 8712   Updates 3     Refreshes 0     Octets 165715
Output messages: Total 8744   Updates 2     Refreshes 0     Octets 166342
Output Queue[1]: 0
Output Queue[2]: 0

```

7. On Router ASBR2, display the BGP summary. Notice that the first peer is the IP address of the Gigabit Ethernet interface of Router ASBR1, the second peer is the IP address of the 100 interface of

Router ASBR1, and the third peer is the 100 interface of Router PE2. Verify that the state of each peer is Established.

```

user@ASBR2> show bgp summary
Groups: 3 Peers: 3 Down peers: 0
Table          Tot Paths  Act Paths Suppressed  History Damp State  Pending
inet.0          3          2          0          0          0          0
bgp.l2vpn.0      2          2          0          0          0          0
Peer            AS      InPkt    OutPkt    OutQ    Flaps Last Up/Dwn State|#Active/
Received/Accepted/Damped...
10.0.78.1        65010    8781     8748      0        2 2d 17:54:56 Establ
  inet.0: 2/3/3/0
192.168.3.1      65010    8780     8747      0        2 2d 17:54:54 Establ
  bgp.l2vpn.0: 1/1/1/0
  inter-as.l2vpn.0: 1/1/1/0
192.168.11.1     65020    8809     8763      0        1 2d 17:59:22 Establ
  bgp.l2vpn.0: 1/1/1/0
  inter-as.l2vpn.0: 1/1/1/0

```

8. On Router PE2, display the BGP group. Verify that the peer is the IP address of the 100 interface of Router ASBR2. Verify that the number of established peer sessions is 1.

```

user@PE1> show bgp group
Group Type: Internal  AS: 65020          Local AS: 65020
Name: core-ibgp      Index: 1           Flags: Export Eval
Holdtime: 0
Total peers: 1       Established: 1
192.168.10.1+179
bgp.l2vpn.0: 1/1/1/0
inter-as.l2vpn.0: 1/1/1/0

Groups: 1 Peers: 1 External: 0 Internal: 1 Down peers: 0 Flaps: 7
Table          Tot Paths  Act Paths Suppressed  History Damp State  Pending
bgp.l2vpn.0      1          1          0          0          0          0
inte.l2vpn.0     1          1          0          0          0          0

```

Configuring the VPLS Routing Instances

Step-by-Step Procedure

To configure the VPLS routing instances:

1. On Router PE1, configure the VPLS routing instance. To enable a VPLS instance, specify the `vpls` instance type. Configure VPLS on the CE-facing Gigabit Ethernet interface. Configure the CE-facing interface to use `ethernet-vpls` encapsulation.

```
user@PE1# set routing-instances metro instance-type vpls
user@PE1# set routing-instances metro interface ge-1/3/0.0
```

2. On Router PE1, configure the VPLS protocol within the routing instance. To uniquely identify the virtual circuit, configure the VPLS identifier. The VPLS identifier uniquely identifies each VPLS in the router. Configure the same VPLS ID on all the routers for a given VPLS.

Specify the IP address of the `lo0` interface on Router ASBR2 as the neighbor.

Configure the CE-facing interface to use `ethernet-vpls` encapsulation and the `vpls` protocol family.

```
user@PE1# set routing-instances metro protocols vpls vpls-id 101
user@PE1# set routing-instances metro protocols vpls neighbor 192.168.3.1
user@PE1# set interfaces ge-1/3/0 encapsulation ethernet-vpls
user@PE1# set interfaces ge-1/3/0 unit 0 family vpls
```

3. On Router ASBR1, configure the VPLS routing instance. To enable a VPLS instance, specify the `vpls` instance type. Configure a route distinguisher and a VRF target. The `vrf-target` statement causes default VRF import and export policies to be generated that accept and tag routes with the specified target community.

NOTE: A route distinguisher allows the router to distinguish between two identical IP prefixes used as VPN routes. Configure a different route distinguisher on each ASBR router.

NOTE: You must configure the same VRF target on both ASBR routers.

```
user@ASBR1# set routing-instances inter-as instance-type vpls
user@ASBR1# set routing-instances inter-as route-distinguisher 65010:1
user@ASBR1# set routing-instances inter-as vrf-target target:2:1
```

4. On Router ASBR1, configure the VPLS protocol within the routing instance.

Configure the VPLS identifier. Specify the IP address of the 100 interface on Router PE1 as the neighbor.

```
user@ASBR1# set routing-instances inter-as protocols vpls vpls-id 101
user@ASBR1# set routing-instances inter-as protocols vpls neighbor 192.168.2.1
```

NOTE: The VPLS identifier uniquely identifies each LDP-signaled VPLS in the router. Configure the same VPLS ID on Router PE1 and Router ASBR1.

5. On Router ASBR1, configure the VPLS site within the routing instance. Configure the site identifier as required by the protocol to establish the EBGp pseudowire. As a best practice for more complex topologies involving multihoming, configure a site preference.

```
user@ASBR1# set routing-instances inter-as protocols vpls site ASBR-metro site-identifier 1
user@ASBR1# set routing-instances inter-as protocols vpls site ASBR-metro site-preference
10000
```

6. On Router ASBR1, configure the VPLS mesh group peer-as statement within the routing instance to specify which ASs belong to this AS mesh group. Configure the peer AS for the mesh group as all.

This statement enables the router to establish a single pseudowire between the ASBR routers. VPLS NLRI messages are exchanged across the EBGp sessions on the inter-AS links between the ASBR routers. All autonomous systems are in one mesh group.

```
user@ASBR1# set routing-instances inter-as protocols vpls mesh-group metro peer-as all
```

7. On ASBR2, configure the VPLS routing instance. To enable a VPLS instance, specify the vpls instance type. Configure a route distinguisher and a VRF target. The vrf-target statement causes

default VRF import and export policies to be generated that accept and tag routes with the specified target community.

NOTE: A route distinguisher allows the router to distinguish between two identical IP prefixes used as VPN routes. Configure a different route distinguisher on each ASBR router.

NOTE: You must configure the same VRF target community on both ASBR routers.

```
user@ASBR2# set routing-instances inter-as instance-type vpls
user@ASBR2# set routing-instances inter-as route-distinguisher 65020:1
user@ASBR2# set routing-instances inter-as vrf-target target:2:1
```

8. On Router ASBR2, configure the VPLS site within the routing instance. Configure the site identifier as required by the protocol.

```
user@ASBR2# set routing-instances inter-as protocols vpls site ASBR-core site-identifier 2
```

9. On Router ASBR2, configure the VPLS mesh group within the routing instance to specify which VPLS PEs belong to this AS mesh group. Configure the peer AS for the mesh group as all.

This statement enables the router to establish a single pseudowire between the ASBR routers. VPLS NLRI messages are exchanged across the EBGp sessions on the inter-AS links between the ASBR routers. All autonomous systems are in one mesh group.

```
user@ASBR1# set routing-instances inter-as protocols vpls mesh-group core peer-as all
```

10. On Router PE2, configure the VPLS routing instance. To enable a VPLS instance, specify the vpls instance type. Configure VPLS on the CE-facing Gigabit Ethernet interface. Configure a route distinguisher and a VRF target.

```
user@PE2# set routing-instances inter-as instance-type vpls
user@PE2# set routing-instances inter-as interface ge-0/1/1.0
user@PE2# set routing-instances inter-as route-distinguisher 65020:1
user@PE2# set routing-instances inter-as vrf-target target:2:1
```

11. On Router PE2, configure the VPLS site within the routing instance. Configure the site identifier as required by the protocol.

Configure the CE-facing interface to use ethernet-vpls encapsulation and the vpls protocol family.

```
user@PE2# set routing-instances inter-as protocols vpls site PE2 site-identifier 3
user@PE2# set interfaces ge-0/1/1 encapsulation ethernet-vpls
user@PE2# set interfaces ge-0/1/1 unit 0 family vpls
```

12. On each router, commit the configuration:

```
user@host> commit check
```

```
configuration check succeeds
```

```
user@host> commit
```

```
commit complete
```

13. On the PE routers, display the CE-facing Gigabit Ethernet interface information and verify that the encapsulation is configured correctly:

```
user@host> show interfaces ge-1/3/0
```

Address	Interface	Label space ID	Hold time
10.0.23.10	ge-1/3/1.0	192.168.3.1:0	11

Physical interface: ge-1/3/0, Enabled, Physical link is Up

Interface index: 147, SNMP ifIndex: 145

Link-level type: Ethernet, MTU: 1514, Speed: 1000mbps, MAC-REWRITE Error: None,

Loopback: Disabled, Source filtering: Disabled, Flow control: Enabled,

Auto-negotiation: Enabled, Remote fault: Online

Device flags : Present Running

Interface flags: SNMP-Traps Internal: 0x4000

Link flags : None

CoS queues : 4 supported, 4 maximum usable queues

Schedulers : 256

```

Current address: 00:12:1e:ee:34:db, Hardware address: 00:12:1e:ee:34:db
Last flapped   : 2008-08-27 19:02:52 PDT (5d 22:32 ago)
Input rate     : 0 bps (0 pps)
Output rate    : 0 bps (0 pps)
Ingress rate at Packet Forwarding Engine      : 0 bps (0 pps)
Ingress drop rate at Packet Forwarding Engine : 0 bps (0 pps)
Active alarms  : None
Active defects : None

Logical interface ge-1/3/0.0 (Index 84) (SNMP ifIndex 146)
  Flags: SNMP-Traps Encapsulation: ENET2
  Input packets : 0
  Output packets: 1
  Protocol inet, MTU: 1500
  Flags: None
  Addresses, Flags: Is-Preferred Is-Primary
    Destination: 10.10.11/24, Local: 10.10.11.11, Broadcast: 10.10.11.255

```

Results

This section describes commands you can use to test the operation of the VPLS.

1. To verify the VPLS connections have been established, enter the `show vpls connections` command on Router PE 1.

```

user@PE1> show vpls connections
Layer-2 VPN connections:

Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available

```

```

BK -- Backup connection      ST -- Standby connection

Legend for interface status
Up -- operational
Dn -- down

Instance: metro
VPLS-id: 101
  Neighbor                Type  St    Time last up        # Up trans
  192.168.3.1(vpls-id 101) rmt   Up    Sep  9 14:05:18 2008      1
  Remote PE: 192.168.3.1, Negotiated control-word: No
  Incoming label: 800001, Outgoing label: 800000
  Local interface: vt-1/2/0.1048576, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls metro neighbor 192.168.3.1 vpls-id 101

```

In the display from Router PE1, verify that the neighbor is the 100 address of Router ASBR1 and that the status is Up.

2. To verify the VPLS connections have been established, enter the `show vpls connections` command on Router ASBR 1.

```

user@ASBR1> show vpls connections
...
Instance: inter-as
BGP-VPLS State
Mesh-group connections: metro
  Neighbor      Local-site  Remote-site  St    Time last up
  192.168.10.1   1           2           Up    Sep  8 20:16:28 2008
  Incoming label: 800257, Outgoing label: 800000
  Local interface: vt-1/2/0.1049088, Status: Up, Encapsulation: VPLS
LDP-VPLS State
VPLS-id: 101
Mesh-group connections: __ves__
  Neighbor                Type  St    Time last up        # Up trans
  192.168.2.1(vpls-id 101) rmt   Up    Sep  9 14:05:22 2008      1
  Remote PE: 192.168.2.1, Negotiated control-word: No
  Incoming label: 800000, Outgoing label: 800001
  Local interface: vt-0/1/0.1049089, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls inter-as neighbor 192.168.2.1 vpls-id 101

```

In the display from Router ASBR1, verify that the neighbor is the 100 address of Router PE1 and that the status is Up.

3. To verify the VPLS connections have been established, enter the `show vpls connections` command on Router ASBR2.

```

user@ASBR2> show vpls connections
...
Instance: inter-as
BGP-VPLS State
Mesh-group connections: __ves__
  Neighbor      Local-site  Remote-site  St      Time last up
  192.168.11.1   2           3            Up      Sep 11 15:18:23 2008
    Incoming label: 800002, Outgoing label: 800001
    Local interface: vt-4/0/0.1048839, Status: Up, Encapsulation: VPLS
Mesh-group connections: core
  Neighbor      Local-site  Remote-site  St      Time last up
  192.168.3.1    2           1            Up      Sep 8 20:16:28 2008
    Incoming label: 800000, Outgoing label: 800257
    Local interface: vt-4/0/0.1048834, Status: Up, Encapsulation: VPLS

```

In the display from Router ASBR2, verify that the neighbor is the `100` address of Router PE2 and that the status is Up.

4. To verify the VPLS connections have been established, enter the `show vpls connections` command on Router PE2.

```

user@PE2> show vpls connections
...
Instance: inter-as
Local site: PE2 (3)
  connection-site      Type  St      Time last up      # Up trans
  2                     rmt   Up      Sep 8 20:16:28 2008      1
    Remote PE: 192.168.10.1, Negotiated control-word: No
    Incoming label: 800001, Outgoing label: 800002
    Local interface: vt-0/3/0.1048832, Status: Up, Encapsulation: VPLS
    Description: Intf - vpls inter-as local site 3 remote site 2

```

In the display from Router PE2, verify that the remote PE is the `100` address of Router ASBR2 and that the status is Up.

5. To verify that the CE routers can send and receive traffic across the VPLS, use the ping command.

```
user@CE1> ping 10.10.11.2
PING 10.10.11.2 (10.10.11.2): 56 data bytes
64 bytes from 10.10.11.2: icmp_seq=0 ttl=64 time=1.369 ms
64 bytes from 10.10.11.2: icmp_seq=1 ttl=64 time=1.360 ms
64 bytes from 10.10.11.2: icmp_seq=2 ttl=64 time=1.333 ms
^C
```

```
user@CE2> ping 10.10.11.1
PING 10.10.11.1 (10.10.11.1): 56 data bytes
64 bytes from 10.10.11.1: icmp_seq=0 ttl=64 time=6.209 ms
64 bytes from 10.10.11.1: icmp_seq=1 ttl=64 time=1.347 ms
64 bytes from 10.10.11.1: icmp_seq=2 ttl=64 time=1.324 ms
^C
```

If Router CE1 can send traffic to and receive traffic from Router CE2 and Router CE2 can send traffic to and receive traffic from Router CE1, the VPLS is performing correctly.

6. To display the configuration for Router CE1, use the show configuration command.

For your reference, the relevant sample configuration for Router CE1 follows.

```
interfaces {
    lo0 {
        unit 0 {
            family inet {
                address 192.168.1.1/32 {
                    primary;
                }
                address 127.0.0.1/32;
            }
        }
    }
    ge-0/3/0 {
        unit 0 {
            family inet {
                address 10.10.11.1/24;
            }
        }
    }
}
```

```

    }
}

```

7. To display the configuration for Router PE1, use the `show configuration` command.

For your reference, the relevant sample configuration for Router PE1 follows.

```

interfaces {
    lo0 {
        unit 0 {
            family inet {
                address 192.168.2.1/32 {
                    primary;
                }
                address 127.0.0.1/32;
            }
        }
    }
    ge-1/3/0 {
        encapsulation ethernet-vpls;
        unit 0 {
            family vpls;
        }
    }
    ge-1/3/1 {
        unit 0 {
            family inet {
                address 10.0.23.9/30;
            }
            family mpls;
        }
    }
}
routing-options {
    autonomous-system 0.65010;
}
protocols {
    mpls {
        interface ge-1/3/1.0;
    }
    ospf {
        traffic-engineering;
    }
}

```



```

        area 0.0.0.1 {
            interface ge-1/3/1.0;
            interface lo0.0 {
                passive;
            }
        }
    }
    ldp {
        interface ge-1/3/1.0;
        interface lo0.0;
    }
}
routing-instances {
    metro {
        instance-type vpls;
        interface ge-1/3/0.0;
        protocols {
            vpls {
                vpls-id 101;
                neighbor 192.168.3.1;
            }
        }
    }
}
}

```

8. To display the configuration for Router ASBR1, use the `show configuration` command.

For your reference, the relevant sample configuration for Router ASBR1 follows.

```

interfaces {
    lo0 {
        unit 0 {
            family inet {
                address 192.168.3.1/32 {
                    primary;
                }
                address 127.0.0.1/32;
            }
        }
    }
    ge-0/3/0 {
        unit 0 {

```

```

        family inet {
            address 10.0.78.1/30;
        }
        family mpls;
    }
}
ge-0/3/1 {
    unit 0 {
        family inet {
            address 10.0.23.10/30;
        }
        family mpls;
    }
}
}
routing-options {
    autonomous-system 0.65010;
}
protocols {
    mpls {
        interface ge-0/3/1.0;
        interface ge-0/3/0.0;
    }
    bgp {
        group vpls-core {
            type external;
            multihop;
            local-address 192.168.3.1;
            family l2vpn {
                signaling;
            }
            peer-as 65020;
            neighbor 192.168.10.1;
        }
        group metro-core {
            type external;
            local-address 10.0.78.1;
            family inet {
                labeled-unicast {
                    resolve-vpn;
                }
            }
        }
        export loopback;
    }
}

```

```

        peer-as 65020;
        neighbor 10.0.78.2;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.1 {
        interface ge-0/3/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-0/3/0.0;
    interface ge-0/3/1.0;
    interface lo0.0;
}
}
policy-options {
    policy-statement loopback {
        term term1 {
            from {
                protocol [ ospf direct ];
                route-filter 192.168.0.0/16 longer;
            }
            then accept;
        }
    }
}
routing-instances {
    inter-as {
        instance-type vpls;
        route-distinguisher 65010:1;
        vrf-target target:2:1;
        protocols {
            vpls {
                site ASBR-metro {
                    site-identifier 1;
                    site-preference 10000;
                }
                vpls-id 101;
                neighbor 192.168.2.1;
            }
        }
    }
}

```

```

        mesh-group metro {
            peer-as {
                all;
            }
        }
    }
}
}
}
}

```

9. To display the configuration for Router ASBR2, use the `show configuration` command.

For your reference, the relevant sample configuration for Router ASBR2 follows.

```

interfaces {
    lo0 {
        unit 0 {
            family inet {
                address 192.168.10.1/32 {
                    primary;
                }
                address 127.0.0.1/32;
            }
        }
    }
    ge-3/1/0 {
        unit 0 {
            family inet {
                address 10.0.78.2/30;
            }
            family mpls;
        }
    }
    ge-3/1/1 {
        unit 0 {
            family inet {
                address 10.0.90.13/30;
            }
            family mpls;
        }
    }
}
}

```

```
routing-options {
    autonomous-system 0.65020;
}
protocols {
    mpls {
        interface ge-3/1/0.0;
        interface ge-3/1/1.0;
    }
    bgp {
        group core-ibgp {
            type internal;
            local-address 192.168.10.1;
            family inet {
                labeled-unicast {
                    resolve-vpn;
                }
            }
            family l2vpn {
                signaling;
            }
            neighbor 192.168.11.1;
        }
        group vpls-metro {
            type external;
            multihop;
            local-address 192.168.10.1;
            family l2vpn {
                signaling;
            }
            peer-as 65010;
            neighbor 192.168.3.1;
        }
        group core-metro {
            type external;
            local-address 10.0.78.2;
            family inet {
                labeled-unicast {
                    resolve-vpn;
                }
            }
            export loopback;
            peer-as 65010;
            neighbor 10.0.78.1;
        }
    }
}
```

```

    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface ge-3/1/1.0;
        interface lo0.0 {
            passive;
        }
    }
}
ldp {
    interface ge-3/1/0.0;
    interface ge-3/1/1.0;
}
}
policy-options {
    policy-statement loopback {
        term term1 {
            from {
                protocol [ ospf direct ];
                route-filter 192.168.0.0/16 longer;
            }
            then accept;
        }
    }
}
routing-instances {
    inter-as {
        instance-type vpls;
        route-distinguisher 65020:1;
        vrf-target target:2:1;
        protocols {
            vpls {
                site ASBR-core {
                    site-identifier 2;
                }
                mesh-group core {
                    peer-as {
                        all;
                    }
                }
            }
        }
    }
}

```

```

    }
  }
}

```

10. To display the configuration for Router PE2, use the `show configuration` command.

For your reference, the relevant sample configuration for Router PE2 follows.

```

interfaces {
  lo0 {
    unit 0 {
      family inet {
        address 192.168.11.1/32 {
          primary;
        }
        address 127.0.0.1/32;
      }
    }
  }
  ge-0/1/0 {
    unit 0 {
      family inet {
        address 10.0.90.14/30;
      }
      family mpls;
    }
  }
  ge-0/1/1 {
    encapsulation ethernet-vpls;
    unit 0 {
      family vpls;
    }
  }
}
routing-options {
  autonomous-system 0.65020;
}
protocols {
  mpls {
    interface ge-0/1/0.0;
  }
  bgp {

```

```

        group core-ibgp {
            type internal;
            local-address 192.168.11.1;
            family l2vpn {
                signaling;
            }
            neighbor 192.168.10.1;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface ge-0/1/0.0;
            interface lo0.0 {
                passive;
            }
        }
    }
    ldp {
        interface ge-0/1/0.0;
    }
}
routing-instances {
    inter-as {
        instance-type vpls;
        interface ge-0/1/1.0;
        route-distinguisher 65020:1;
        vrf-target target:2:1;
        protocols {
            vpls {
                site PE2 {
                    site-identifier 3;
                }
            }
        }
    }
}
}

```

11. To display the configuration for Router CE2, use the `show configuration` command.

For your reference, the relevant sample configuration for Router CE2 follows.

```
interfaces {  
  lo0 {  
    unit 0 {  
      family inet {  
        address 192.168.12.1/32 {  
          primary;  
        }  
        address 127.0.0.1/32;  
      }  
    }  
  }  
  ge-0/1/1 {  
    unit 0 {  
      family inet {  
        address 10.10.11.2/24;  
      }  
    }  
  }  
}
```

Configuring VPLS and Integrated Routing and Bridging

IN THIS SECTION

- [Configuring MAC Address Flooding and Learning for VPLS | 1135](#)
- [Configuring MSTP for VPLS | 1136](#)

Traditional Layer 2 switching environments consist of Layer 2 devices (such as switches) that partition data into broadcast domains. The broadcast domains can be created through physical topologies or logically through virtual local area networks (VLANs). For MX Series routers, you can logically configure broadcast domains within virtual switch routing instances, VPLS routing instances, or bridging domains. The individual routing instances or bridging domains are differentiated through VLAN identifiers and these instances or domains function much like traditional VLANs.

To configure a VLAN with IRB support, include the following statements:

```
[edit]
routing-instances {
  instance-name {
    instance-type vpls;
    vlan-id id;
    route-distinguisher distinguisher;
    vrf-target target;
    interface interface-name;
    interface interface-name;
    routing-interface interface-name;
  }
}
```

In multihomed VPLS configurations, you can configure VPLS to keep a VPLS connection up if only an IRB interface is available by configuring the `irb` option for the `connectivity-type` statement at the `[edit routing-instances routing-instance-name protocols vpls]` hierarchy level. The `connectivity-type` statement has the `ce` and `irb` options. The `ce` option is the default and specifies that a CE interface is required to maintain the VPLS connection. By default, if only an IRB interface is available, the VPLS connection is brought down.

NOTE: A maximum of 4096 active logical interfaces are supported for a VLAN or on each mesh group in a VPLS routing instance configured for Layer 2 bridging.

For detailed information and configuration instructions on bridging domains and spanning tree protocol, see [Junos OS Network Interfaces Library for Routing Devices](#) and [Junos OS Routing Protocols Library](#).

The following sections provide configuration information specific to VPLS in regards to integrated routing and bridging:

Configuring MAC Address Flooding and Learning for VPLS

In a VPLS routing instance or bridge domain, when a frame is received from a CE interface, it is flooded to the other CE interfaces and all of the VE interfaces if the destination MAC address is not learned or if the frame is either broadcast or multicast. If the destination MAC address is learned on another CE device, such a frame is unicasted to the CE interface on which the MAC address is learned. This might not be desirable if the service provider does not want CE devices to communicate with each other directly.

To prevent CE devices from communicating directly include the `no-local-switching` statement at the `[edit bridge-domains bridge-domain-name]` hierarchy level:

```
[edit bridge-domains bridge-domain-name]  
no-local-switching;
```

The `no-local-switching` statement is available only on MX Series routers. If you include it, frames arriving on a CE interface are sent to VE or core-facing interfaces only.

NOTE: (MX80, MX104, and the 16x10GE MPC, MPC1, or MPC2 on MX240, MX480, MX960, MX2010, and MX2020 only) If you configure the `no-local-switching` command at the `[edit bridge-domains bridge-domain-name]` hierarchy level, it might not prevent multicast traffic from being forwarded between the CE-facing interfaces of the bridge domain. Broadcast, unknown unicast, and known multicast traffic does not exhibit this behavior.

Configuring MSTP for VPLS

When you configure integrated routing and bridging, you might also need to configure the Multiple Spanning Tree Protocol (MSTP). When you configure MSTP on a provider edge (PE) router running VPLS, you must also configure `ethernet-vpls` encapsulation on the customer-facing interfaces. VLAN-based VPLS interface encapsulations are not supported with MSTP.

RELATED DOCUMENTATION

[Configuring Integrated Routing and Bridging for VLANs](#)

[Configuring Integrated Routing and Bridging in a VPLS Instance \(MX Series Routers Only\) | 1137](#)

[Example: Configuring Inter-AS VPLS with MAC Processing at the ASBR | 1098](#)

[Example: VPLS Configuration \(BGP and LDP Interworking\) | 653](#)

[Example: VPLS Configuration \(BGP Signaling\) | 636](#)

Configuring Integrated Routing and Bridging in a VPLS Instance (MX Series Routers Only)

Integrated routing and bridging (IRB) over VPLS cannot be used in conjunction with the `vlan-id all` statement. One or more Layer 2 logical interfaces must be configured inside the instance in order for IRB to function properly.

To configure IRB within a VPLS instance, include the `routing-interface irb-interface-name` statement at the `[edit routing-instances routing-instance-name instance-type vpls]` hierarchy level:

```
[edit]
routing-instances {
  marketing {
    instance-type vpls;
    vlan-id 123;
    route-distinguisher 11.11.11.11:10;
    vrf-target target:100:100;
    interface ae0.100;
    interface ae0.200;
    routing-interface irb.1234;
  }
}
```

RELATED DOCUMENTATION

[Configuring Integrated Routing and Bridging for VLANs](#)

[Configuring VPLS and Integrated Routing and Bridging | 1134](#)

[Example: Configuring Inter-AS VPLS with MAC Processing at the ASBR | 1098](#)

[Example: VPLS Configuration \(BGP and LDP Interworking\) | 653](#)

[Example: VPLS Configuration \(BGP Signaling\) | 636](#)

Configuring L2PT for VPLS

You can use Layer 2 Protocol Tunneling (L2PT) to transparently send packets across a VPLS network. The customer edge (CE) device sends and receives packets over VPLS pseudowires to and from the provider edge (PE) device. L2PT doesn't interfere with protocol instances in the network. L2PT supports

802.1x, 802.3ah, CDP, E-LMI, MVRP, LACP, STP/RSTP/MSTP, LLDP, MMRP, and VTP Layer 2 control protocols.

Here is how to configure L2PT for VPLS on the PE device.

1. The packets leave the CE from an untagged or single-tagged port called interface *CE-interface-name*. Configure VPLS VLAN encapsulation for packets that arrive from this port.

- a. Enable flexible VLAN tagging and flexible Ethernet services so you can configure more than one instance of VPLS encapsulation on the port.

```
[edit interfaces CE-interface-name]
set flexible-vlan-tagging
set encapsulation flexible-ethernet-services
```

- b. Since the L2CP frames from the CE device are untagged, configure the native VLAN ID to support untagged VLAN packets.

```
[edit interfaces CE-interface-name]
set native-vlan-id vlan-id-number
```

- c. Configure VPLS VLAN encapsulation.

```
[edit interfaces CE-interface-name unit unit-number]
set encapsulation vlan-vpls
set vlan-id vlan-id-number
```

2. Configure the routing instance.

- a. Configure VPLS as the routing instance protocol.

```
[edit routing-instances routing-instance-name]
set protocols vpls
```

- b. (Optional) If your router doesn't have a Tunnel Services PIC, you will need to configure the `no-tunnel-services` statement at the `[edit routing-instances routing-instance-name protocols vpls]` hierarchy level.

- c. Configure the instance type and identify the CE port. Use the VLAN ID from Step 1.

```
[edit routing-instances routing-instance-name]  
set instance-type vpls  
set vlan-id vlan-id-number  
set interface CE-interface-name
```

3. Configure the L2PT protocol. The protocol can be any of the following: (stp | vtp | cdp | ieee8021x | ieee8023ah | elmi | lacp | lldp | mmrp | mvrp).

```
[edit protocols layer2-control mac-rewrite interface interface-name]  
set protocol protocol-name
```

You have configured L2PT for VPLS on your network.

RELATED DOCUMENTATION

| [Layer 2 Protocol Tunneling](#)

Configuring Load Balancing and Performance

IN THIS CHAPTER

- [Configuring VPLS Load Balancing | 1141](#)
- [Configuring VPLS Load Balancing Based on IP and MPLS Information | 1143](#)
- [Configuring VPLS Load Balancing on MX Series 5G Universal Routing Platforms | 1145](#)
- [Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves | 1147](#)
- [Understanding MAC Pinning | 1169](#)
- [Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171](#)
- [Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172](#)
- [Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)
- [Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176](#)
- [Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance \(LDP and BGP\) | 1178](#)
- [Configuring MAC Pinning on VPLS CE Interface | 1180](#)
- [Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance | 1182](#)
- [Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance | 1184](#)
- [Configuring MAC Pinning on Access Interfaces for Logical Systems | 1186](#)
- [Configuring MAC Pinning on Trunk Interfaces for Logical Systems | 1188](#)
- [Configuring MAC Pinning on Access Interfaces in Virtual Switches for Logical Systems | 1190](#)
- [Configuring MAC Pinning on Trunk Interfaces in Virtual Switches for Logical Systems | 1193](#)
- [Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance \(LDP and BGP\) for Logical Systems | 1195](#)
- [Configuring MAC Pinning on VPLS CE Interface for Logical Systems | 1198](#)
- [Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance for Logical Systems | 1200](#)
- [Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance for Logical Systems | 1202](#)
- [Example: Prevention of Loops in Bridge Domains by Enabling the MAC Pinning Feature on Access Interfaces | 1204](#)

- [Example: Prevention of Loops in Bridge Domains by Enabling the MAC Pinning Feature on Trunk Interfaces | 1210](#)
- [Configuring Improved VPLS MAC Address Learning on T4000 Routers with Type 5 FPCs | 1220](#)
- [Understanding Qualified MAC Learning | 1222](#)
- [Qualified Learning VPLS Routing Instance Behavior | 1223](#)
- [Configuring Qualified MAC Learning | 1230](#)

Configuring VPLS Load Balancing

By default, when there are multiple equal-cost paths to the same destination for the active route, the Junos OS uses a hash algorithm to select one of the next-hop addresses to install in the forwarding table. Whenever the set of next hops for a destination changes, the next-hop address is reselected using the hash algorithm.

You can configure the Junos OS so that, for the active route, all next-hop addresses for a destination are installed in the forwarding table. This feature is called per-packet load balancing. You can use load balancing to spread traffic across multiple paths between routers. You can also configure per-packet load balancing to optimize VPLS traffic flows across multiple paths.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

You can load-balance VPLS traffic based on Layer 2 media access control (MAC) information, IP information and MPLS labels, or MPLS labels only.

NOTE: For platform support information, see "[family multiservice](#)" on page 1499.

To optimize VPLS traffic flows across multiple paths, include the `family multiservice` statement at the `[edit forwarding-options hash-key]` hierarchy level:

```
family multiservice {
  destination-mac;
  label-1;
  label-2;
```



```

payload {
  ip {
    layer-3 {
      (destination-ip-only | source-ip-only);
    }
    layer-3-only;
    layer-4;
  }
}
source-mac;
symetric-hash {
  complement;
}
}

```

You can configure one or more of the following options to load-balance using the specified packet information:

- **destination-mac**—Include the destination-address MAC information in the hash key for Layer 2 load balancing.
- **source-mac**—Include the source-address MAC information in the hash key.
- **label-1**—Include the first MPLS label in the hash key. Used for including a one-label packet for per-flow load balancing of IPv4 VPLS traffic based on IP information and MPLS labels.
- **label-2** —Include the second MPLS label in the hash key. If both **label-1** and **label-2** are specified, the entire first label and the first 16 bits of the second label are hashed.
- **payload**—Include the packet's IP payload in the hash key.
- **ip**—Include the IP address of the IPv4 or IPv6 payload in the hash key.
- **layer-3-only**—Include only the Layer 3 information from the packet's IP payload in the hash key.
- **layer-3**—Include Layer 3 information from the packet's IP payload in the hash key.
- **destination-address-only**—Include only the destination IP address in the payload in the hash key.

NOTE: You can include either the **source-address-only** or the **destination-address-only** statement, not both. They are mutually exclusive.

- **source-address-only**—Include only the source IP address in the payload in the hash key.

NOTE: You can include either the source-address-only or the destination-address-only statement, not both. They are mutually exclusive.

- layer-4—Include Layer 4 information from the packet's IP payload in the hash key.
- symmetric-hash—Configure the symmetric hash or symmetric hash complement for configuring symmetrical load balancing on an 802.3ad Link Aggregation Group.
- complement—Include the complement of the symmetric hash in the hash key.

For more information about how to configure per-packet load balancing, see the [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

RELATED DOCUMENTATION

[Configuring VPLS Load Balancing Based on IP and MPLS Information | 1143](#)

[Configuring VPLS Load Balancing on MX Series 5G Universal Routing Platforms | 1145](#)

Configuring VPLS Load Balancing Based on IP and MPLS Information

In Junos OS Release 9.4 and later, you can configure load balancing for VPLS traffic to have the hash key include IP information and MPLS labels on the M120 and M320 routers only. In earlier Junos OS Releases, you can configure load balancing based only on Layer 2 information. In Junos OS Release 9.5 and later, you can configure load balancing for VPLS traffic based on Layer 3 IP and Layer 4 information on MX Series routers only. For more information, see "[Configuring VPLS Load Balancing on MX Series 5G Universal Routing Platforms](#)" on page 1145.

For IPv4 traffic, only the IP source and destination addresses are included in the hash key. For MPLS and IPv4 traffic, one or two MPLS labels and IPv4 source and destination addresses are included. For MPLS Ethernet pseudowires, only one or two MPLS labels are included in the hash key.

NOTE: VPLS load balancing based on MPLS labels and IP information is supported only on the M120 and M320 routers. In Junos OS Release 9.5 and later, on MX Series routers only, you can configure VPLS load balancing based on IP and Layer 4 information.

To optimize VPLS flows across multiple paths based on IP and MPLS information, include the `family multiservice` statement at the `[edit forwarding-options hash-key]` hierarchy level:

```
[edit forwarding-options hash-key]
family multiservice {
  label-1;
  label-2;
  payload {
    ip {
      layer-3-only;
    }
  }
}
```

To use the first MPLS label in the hash key, include the `label-1` statement:

```
[edit forwarding-options hash-key family multiservice]
label-1;
```

To use the second MPLS label, include both the `label-1` and `label-2` statements:

```
[edit forwarding-options hash-key family multiservice]
label-1;
label-2;
```

To use the packet's IPv4 payload in the hash key, include the `payload` and `ip` statements:

```
[edit forwarding-options hash-key family multiservice]
payload {
  ip;
}
```

NOTE: Only IPv4 is supported.

To include only Layer 3 information from the IPv4 payload, specify the `layer-3-only` option to the `payload ip` statement:

```
[edit forwarding-options hash-key family multiservice]
payload {
  ip {
    layer-3-only;
  }
}
```

To use the first and second MPLS labels and the packet's IP payload in the hash key, include the `label-1`, `label-2`, and `payload ip` statements:

```
[edit forwarding-options hash-key family multiservice]
label-1;
label-2;
payload {
  ip;
}
```

Configuring VPLS Load Balancing on MX Series 5G Universal Routing Platforms

In Junos OS Release 9.5 and later, on MX Series routers, you can configure the load balancing hash key for Layer 2 traffic to use fields in the Layer 3 and Layer 4 headers inside the frame payload. You can also configure VPLS load balancing based on IP and MPLS information on M120 and M320 routers only. For more information, see ["Configuring VPLS Load Balancing Based on IP and MPLS Information" on page 1143](#).

You can configure load balancing on MX Series routers based on Layer 3 or Layer 4 information or both.

To configure VPLS load balancing on the MX Series router to include either Layer 3 IP information or Layer 4 headers or both:

1. Include the `payload` statement at the `[edit forwarding-options hash-key family multiservice]` hierarchy level.
2. Include the `ip` statement at the `[edit forwarding-options hash-key family multiservice payload]` hierarchy level.

To configure VPLS load balancing to include the Layer 3 information:

1. Include the `layer-3` statement at the `[edit forwarding-options hash-key family multiservice payload ip]` hierarchy level.
2. Include the `source-ip-only` statement at the `[edit forwarding-options hash-key family multiservice payload ip layer-3]` hierarchy level to include information about the IP source address only in the hash key.
3. Include `destination-ip-only` statement at the `[edit forwarding-options hash-key family multiservice payload ip layer-3]` hierarchy level to include information about the IP destination address only in the hash key.

NOTE: You can configure either the `source-ip-only` or the `destination-ip-only` statements at a time, not both. They are mutually exclusive.

To configure VPLS load balancing to include Layer 4 information:

- Include the `layer-4` statement at the `[edit forwarding-options hash-key family multiservice payload ip]` hierarchy level.

The following example shows load balancing configured to use the source Layer 3 IP address option and Layer 4 header fields as well as the source and destination MAC addresses:

```
[edit forwarding-options hash-key]
family multiservice {
  source-mac;
  destination-mac;
  payload {
    ip {
      layer-3 {
        source-ip-only;
      }
      layer-4;
    }
  }
}
```

RELATED DOCUMENTATION

[family multiservice](#) | 1499

[hash-key](#)

Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves

IN THIS SECTION

- [MAC Moves Loop Prevention in VPLS Network Overview | 1147](#)
- [Configuring VPLS Loop Prevention Due to MAC Moves | 1149](#)
- [Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves | 1151](#)

MAC Moves Loop Prevention in VPLS Network Overview

Starting in Junos OS 14.2, you can configure the router to prevent a loop in a VPLS network. In a virtual private LAN service (VPLS) deployment, when a previously learned media access control (MAC) address appears on a different physical interface, for example, local interfaces (Gigabit Ethernet interfaces) or label switched Interfaces (LSIs), or within a different unit of the same physical interface and if this behavior occurs frequently, then it is considered a MAC move.

You can configure the router to report a MAC address move based on the following parameters:

- Number of times a MAC address move occurs
- Specified period of time over which the MAC address move occurs

Configuration errors at the network can force traffic into never ending circular paths or loops. These loops in the VPLS network cause frequent MAC moves between different interfaces which can be used to rectify the problem by disabling such an interface in the network. The following two approaches can be used to disable the interface causing the loop:

- Base learning interface (base IFL) approach algorithm- This is the primary approach used to disable the looped interface. Base interface information is maintained for every MAC in the routing instance. If the MAC stays at the interface it was first learned for 300 seconds, then the interface-MAC association is considered to be stable and this interface is considered as the base interface of the MAC. If the MAC move happens frequently between the local interface and the LSI interface while the base interface of the MAC is an LSI, then the local interface is considered to be looped and has to be disabled.
- Statistical approach algorithm- This is the secondary approach used to disable the looped interface. If the MAC has not been learned for over 300 seconds at an interface, then it does not have a base interface and hence the statistical approach is used.

If the MAC that has no base interface information(Base Learning interface is null) starts moving, then the statistics of such MAC moves between different interfaces is learned. If the statistics show MAC moves from LSI to local interface or from local interface to local interface, then the local interface is considered to be looped and is disabled.

There are certain MACs that can move between different interfaces, for example, primary role change in the Virtual Router Redundancy Protocol (VRRP). The base interface of such MAC moves cannot be maintained as this leads to the assumption of a loop creation. Hence, such MACs should be configured as virtual MACs. Example of virtual MACs are 00:00:5e:00:01:xx for VRRP, 00:00:0c:07:ac:xx for hot standby router protocol (HSRP) , 00:07:b4:00:01:xx for global server load balancing (GSLB), and 02:bf:xx:xx:xx:xx for VMotion.

Starting with Junos OS Release 17.4R1, the `global-mac-move` statement replaces the `vpls-mac-move` statement. The following timers under the `global-mac-move` statement help in monitoring the disabled interfaces:

- **Cooloff time** — The cooloff time starts when the interface gets disabled. During this time any MAC move happening in the routing instance is ignored. This ensures that only one interface is blocked at a given time on a routing instance, and blocking of another interface happens only after the expiration of the cooloff timer provided the given MAC moves are still observed. By default, the cooloff time is 30 seconds.
- **Interface recovery time** — When an interface gets disabled , it is disabled permanently. Configuring the interface recovery time ensures that the interface gets enabled on completion of the interface recovery time duration. We recommend that you configure an interface recovery time of more than 300 seconds.
- **Statistical approach wait time** — The time when the statistics are collected after MAC moves are observed to determine the existence of a loop when there is no base IFL for the MAC address. . By default, the statistical approach wait timer is 30 seconds.

Before the base learning interface of a MAC address is established, the statistical approach algorithm is used in MAC move loop prevention. When a statistical approach algorithm is used, the offending MAC address is shown with a MAC address of 00:00:00:00:00:00. Until the base learning interface of MAC addresses are established, this may cause interfaces with routing loops to be misidentified.

SEE ALSO

[virtual-mac](#) | 1703

[global-mac-move](#) | 1515

Configuring VPLS Loop Prevention Due to MAC Moves

In a virtual private LAN service (VPLS) deployment, when a previously learned media access control (MAC) address appears on a different physical interface, for example, local interfaces (Gigabit Ethernet interfaces) or label switched Interfaces (LSIs), or within a different unit of the same physical interface and if this behavior occurs frequently, then it is considered a MAC move. The router reports a MAC address move based on the number of times a MAC address move occurs and the specified period of time over which the MAC address move occurs. Configuration errors at the VPLS network can lead to loops that cause frequent MAC moves between different interfaces. These moves can be used to rectify the problem by disabling such interface in the network. The following two approaches can be used to disable the interface:

- Base learning interface (base IFL) approach algorithm — This is the primary approach used to disable the looped local interface.
- Statistical approach algorithm — This is the secondary approach used to disable the looped local interface.

Some virtual MACs can genuinely move between different interfaces and such MACs can be configured to ignore the moves. The cooloff time and the statistical approach wait time are used internally to find out the looped interface. The interface recovery time can be configured to auto-enable the interface that gets disabled due to a loop in the network.

Before you begin to configure loop prevention in a VPLS network:

1. Configure the VPLS topology.
2. Configure the VPLS routing instances.
3. Enable VPLS MAC move action on a VPLS instance.
4. Configure the routing and signaling protocols.

The following uses the `global-mac-move` command, which replaced the `vpls-mac-move` command starting with Junos OS Release 17.4R1.

To configure loop prevention in a VPLS network:

1. Configure the threshold time and the threshold count to detect MAC moves.

```
[edit protocols l2-learning global-mac-move]
user@host# set threshold-time seconds
user@host# set threshold-count seconds
```


For example, configure the threshold time as 30 and the threshold count as 4 to detect MAC moves.

```
[edit protocols l2-learning global-mac-move]
user@host# set threshold-time 30
user@host# set threshold-count 4
```

NOTE: If the threshold time and threshold count are not configured, then the default values are used. The default value of threshold time is 1 second, and default value of threshold count is 50.

2. (Optional) Configure a cooloff time to ensure that no other interface gets disabled once an interface, for a routing instance, is disabled during this time period.

```
[edit protocols l2-learning global-mac-move]
user@host# set cooloff-time seconds
```

3. (Optional) Configure the statistical approach wait time to determine the existence of a loop based on the statistics collected after MAC moves are observed when there is no base IFL for the MAC address.

```
[edit protocols l2-learning global-mac-move]
user@host# set statistical-approach-wait-time seconds
```

4. (Optional) Configure the interface recovery time to ensure that the disabled interface gets enabled on completion of the interface recovery time duration.

```
[edit protocols l2-learning global-mac-move]
user@host# set interface-recovery-time seconds
```

5. (Optional) Configure the virtual MAC address to ignore the MAC moves as this leads to the assumption of loop creation.

```
[edit protocols l2-learning global-mac-move]
user@host# set virtual-mac mac-address
```

6. Configure the VPLS routing instance of an interface.

```
[edit routing-instances instance-name]
user@host# set instance-type vpls
user@host# set interface interface
```

7. Enable MAC move action on the interface for the VPLS instance, and configure the VPLS neighbor.

```
[edit routing-instances instance-name]
user@host# set protocols vpls enable-mac-move-action
user@host# set protocols vpls no-tunnel-services
user@host# set protocols vpls vpls-id vpls-id
user@host# set protocols vpls neighbor IP-address
```

SEE ALSO

[Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves](#) | 1147

Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves

IN THIS SECTION

- [Requirements](#) | 1151
- [Overview](#) | 1152
- [Configuration](#) | 1154
- [Verification](#) | 1164

This example shows how to prevent a loop in the VPLS network due to MAC moves between different physical interfaces.

When a MAC move is detected in the VPLS network, Junos OS allows the prevention of the loop in the network by disabling the interface using a base IFL or statistical approach algorithm.

Requirements

This example uses the following hardware and software components:

- Four MX Series 5G Universal Routing Platforms
- Junos OS Release 14.2 or later running on all devices

Before you begin:

1. Configure the VPLS topology.
2. Configure the VPLS routing instances.
3. Enable VPLS MAC move action on a VPLS instance.
4. Configure the routing and signaling protocols.

Overview

IN THIS SECTION

- [Topology | 1153](#)

Starting with Junos OS Release 14.2, the loop creation in the VPLS network due to frequent MAC moves between different physical interfaces can be prevented by identifying and disabling such interfaces using the base IFL approach or statistical approach algorithm.


The *base IFL approach* algorithm is the primary approach. Base interface information is maintained for every MAC in the routing instance. If the MAC stays at the interface it was first learned for 300 seconds, then the interface-MAC association is considered to be stable, and this interface is considered as the base interface of the MAC. If the MAC move happens frequently between the local interface and the LSI interface while the base interface of the MAC is an LSI, then the local interface is considered to be looped and has to be disabled.

The *statistical approach* algorithm is the secondary approach used to disable the looped interface. If the MAC has not been learned for over 300 seconds at an interface, then it does not have a base interface and hence the statistical approach is used. If the MAC that has no base interface information(Base Learning interface is null) starts moving then the statistics of such MAC moves between different interfaces is learned. If the statistics show MAC moves from LSI to local interface or from local interface to local interface then the local interface is considered to be looped and is disabled.

Topology

In the topology shown in [Figure 82 on page 1153](#), a loop was detected on Device PE1 in the VPLS network.

Figure 82: Example Loop Prevention Due to MAC Move in VPLS Network



8042468

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 1154](#)
- [Configuring Device PE1 | 1159](#)
- [Results | 1161](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

This example uses the `global-mac-move` command, which replaced the `vppls-mac-move` command starting with Junos OS Release 17.4R1.

PE0

```
set interfaces xe-0/0/0 unit 0 family inet address 198.51.100.8/24
set interfaces xe-0/0/0 unit 0 family mpls
set interfaces xe-0/2/0 unit 0 family inet address 198.51.100.6/24
set interfaces xe-0/2/0 unit 0 family mpls
set interfaces xe-0/3/0 vlan-tagging
set interfaces xe-0/3/0 encapsulation vlan-vpls
set interfaces xe-0/3/0 unit 600 encapsulation vlan-vpls
set interfaces xe-0/3/0 unit 600 vlan-id 600
set interfaces ge-2/0/3 unit 0 family inet address 198.51.100.1/24
set interfaces ge-2/0/3 unit 0 family mpls
set interfaces lo0 unit 0 family inet address 192.0.2.1/24
set routing-options router-id 192.0.2.1
set routing-options autonomous-system 701
set protocols mpls interface fxp0.0 disable
set protocols mpls interface ge-2/0/3.0
set protocols mpls interface xe-0/2/0.0
set protocols mpls interface xe-0/0/0.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface ge-2/0/3.0 interface-type p2p
```

```

set protocols ospf area 0.0.0.0 interface ge-2/0/3.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-0/2/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-0/2/0.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-0/0/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-0/0/0.0 metric 10
set protocols ldp interface xe-0/0/0.0
set protocols ldp interface xe-0/2/0.0
set protocols ldp interface ge-2/0/3.0
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set protocols l2-learning global-mac-move threshold-time 30
set protocols l2-learning global-mac-move threshold-count 4
set protocols l2-learning global-mac-move cooloff-time 10
set protocols l2-learning global-mac-move statistical-approach-wait-time 10
set protocols l2-learning global-mac-move interface-recovery-time 5
set protocols l2-learning global-mac-move virtual-mac 00:00:5e:00:01:00/40
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface xe-0/3/0.600
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls vpls-id 100
set routing-instances vpls_1 protocols vpls neighbor 192.0.2.2
set routing-instances vpls_1 protocols vpls neighbor 192.0.2.3
set routing-instances vpls_1 protocols vpls neighbor 192.0.2.4

```

PE1

```

set interfaces ge-0/0/3 unit 0 family inet address 198.51.100.2/24
set interfaces ge-0/0/3 unit 0 family mpls
set interfaces xe-1/2/0 unit 0 family inet address 198.51.100.5/24
set interfaces xe-1/2/0 unit 0 family mpls
set interfaces xe-1/2/1 unit 0 family inet address 198.51.100.3/24
set interfaces xe-1/2/1 unit 0 family mpls
set interfaces xe-1/3/1 vlan-tagging
set interfaces xe-1/3/1 encapsulation vlan-vpls
set interfaces xe-1/3/1 unit 600 encapsulation vlan-vpls
set interfaces xe-1/3/1 unit 600 vlan-id 600
set interfaces lo0 unit 0 family inet address 192.0.2.2/24
set routing-options router-id 192.0.2.2
set routing-options autonomous-system 701
set protocols mpls interface fxp0.0 disable
set protocols mpls interface ge-0/0/3.0
set protocols mpls interface xe-1/2/1.0

```

```

set protocols mpls interface xe-1/2/0.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface ge-0/0/3.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface ge-0/0/3.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-1/2/1.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-1/2/1.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-1/2/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-1/2/0.0 metric 10
set protocols ldp interface ge-0/0/3.0
set protocols ldp interface xe-1/2/0.0
set protocols ldp interface xe-1/2/1.0
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set protocols l2-learning global-mac-move threshold-time 30
set protocols l2-learning global-mac-move threshold-count 4
set protocols l2-learning global-mac-move cooloff-time 10
set protocols l2-learning global-mac-move statistical-approach-wait-time 10
set protocols l2-learning global-mac-move interface-recovery-time 10
set protocols l2-learning global-mac-move virtual-mac 00:00:5e:00:01:00/40
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface xe-1/3/1.600
set routing-instances vpls_1 protocols vpls enable-mac-move-action
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls vpls-id 100
set routing-instances vpls_1 protocols vpls neighbor 192.0.2.1

```

PE2

```

set interfaces xe-4/0/0 unit 0 family inet address 198.51.100.10/24
set interfaces xe-4/0/0 unit 0 family mpls
set interfaces xe-4/1/0 unit 0 family inet address 198.51.100.4/24
set interfaces xe-4/1/0 unit 0 family mpls
set interfaces xe-4/2/0 unit 0 family inet address 198.51.100.7/24
set interfaces xe-4/2/0 unit 0 family mpls
set interfaces xe-4/3/0 vlan-tagging
set interfaces xe-4/3/0 encapsulation vlan-vpls
set interfaces xe-4/3/0 unit 600 encapsulation vlan-vpls
set interfaces xe-4/3/0 unit 600 vlan-id 600
set interfaces lo0 unit 0 family inet address 192.0.2.3/24
set routing-options router-id 192.0.2.3
set routing-options autonomous-system 701

```

```

set protocols mpls interface fxp0.0 disable
set protocols mpls interface xe-4/2/0.0
set protocols mpls interface xe-4/1/0.0
set protocols mpls interface xe-4/0/0.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface xe-4/2/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-4/2/0.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-4/1/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-4/1/0.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-4/0/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-4/0/0.0 metric 10
set protocols ldp interface xe-4/0/0.0
set protocols ldp interface xe-4/1/0.0
set protocols ldp interface xe-4/2/0.0
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set protocols l2-learning global-mac-move threshold-time 30
set protocols l2-learning global-mac-move threshold-count 4
set protocols l2-learning global-mac-move threshold-count 5
set protocols l2-learning global-mac-move cooloff-time 10
set protocols l2-learning global-mac-move statistical-approach-wait-time 10
set protocols l2-learning global-mac-move interface-recovery-time 10
set protocols l2-learning global-mac-move virtual-mac 00:00:5e:00:01:00/40
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface xe-4/3/0.600
set routing-instances vpls_1 protocols vpls enable-mac-move-action
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls vpls-id 100
set routing-instances vpls_1 protocols vpls neighbor 192.0.2.1

```

PE3

```

set interfaces xe-1/0/0 unit 0 family inet address 198.51.100.9/24
set interfaces xe-1/0/0 unit 0 family mpls
set interfaces xe-1/1/0 unit 0 family inet address 198.51.100.12/24
set interfaces xe-1/1/0 unit 0 family mpls
set interfaces xe-1/2/0 unit 0 family inet address 198.51.100.11/24
set interfaces xe-1/2/0 unit 0 family mpls
set interfaces xe-1/3/0 vlan-tagging
set interfaces xe-1/3/0 encapsulation vlan-vpls
set interfaces xe-1/3/0 unit 600 encapsulation vlan-vpls

```



```

set interfaces xe-1/3/0 unit 600 vlan-id 600
set interfaces xe-2/3/0 vlan-tagging
set interfaces xe-2/3/0 encapsulation vlan-vpls
set interfaces xe-2/3/0 unit 600 encapsulation vlan-vpls
set interfaces xe-2/3/0 unit 600 vlan-id 600
set interfaces lo0 unit 0 family inet address 192.0.2.4/24
set routing-options router-id 192.0.2.4
set routing-options autonomous-system 701
set protocols mpls interface fxp0.0 disable
set protocols mpls interface xe-1/2/0.0
set protocols mpls interface xe-1/0/0.0
set protocols mpls interface xe-1/1/0.0
set protocols ospf area 0.0.0.0 interface lo0.0 passive
set protocols ospf area 0.0.0.0 interface fxp0.0 disable
set protocols ospf area 0.0.0.0 interface xe-1/2/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-1/2/0.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-1/0/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-1/0/0.0 metric 10
set protocols ospf area 0.0.0.0 interface xe-1/1/0.0 interface-type p2p
set protocols ospf area 0.0.0.0 interface xe-1/1/0.0 metric 10
set protocols ldp interface xe-1/0/0.0
set protocols ldp interface xe-1/1/0.0
set protocols ldp interface xe-1/2/0.0
set protocols ldp interface fxp0.0 disable
set protocols ldp interface lo0.0
set protocols l2-learning global-mac-move threshold-time 30
set protocols l2-learning global-mac-move threshold-count 4
set protocols l2-learning global-mac-move cooloff-time 10
set protocols l2-learning global-mac-move statistical-approach-wait-time 10
set protocols l2-learning global-mac-move interface-recovery-time 10
set protocols l2-learning global-mac-move virtual-mac 00:00:52:00:01:00/40
set policy-options policy-statement pplb then load-balance per-packet
set routing-instances vpls_1 instance-type vpls
set routing-instances vpls_1 interface xe-1/3/0.600
set routing-instances vpls_1 interface xe-2/3/0.600
set routing-instances vpls_1 protocols vpls no-tunnel-services
set routing-instances vpls_1 protocols vpls vpls-id 100
set routing-instances vpls_1 protocols vpls neighbor 192.0.2.1

```

Configuring Device PE1

Step-by-Step Procedure

The following example requires that you navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode* in the [CLI User Guide](#).

To configure Device PE1:

NOTE: Repeat this procedure for Routers PE0, PE2, and PE3 after modifying the appropriate interface names, addresses, and any other parameters for the router.

1. Configure the interfaces.

```
[edit interfaces]
user@PE1# set ge-0/0/3 unit 0 family inet address 198.51.100.2/24
user@PE1# set ge-0/0/3 unit 0 family mpls
user@PE1# set xe-1/2/0 unit 0 family inet address 198.51.100.5/24
user@PE1# set xe-1/2/0 unit 0 family mpls
user@PE1# set xe-1/2/1 unit 0 family inet address 198.51.100.3/24
user@PE1# set xe-1/2/1 unit 0 family mpls
user@PE1# set xe-1/3/1 vlan-tagging
user@PE1# set xe-1/3/1 encapsulation vlan-vpls
user@PE1# set xe-1/3/1 unit 600 encapsulation vlan-vpls
user@PE1# set xe-1/3/1 unit 600 vlan-id 600
user@PE1# set lo0 unit 0 family inet address 192.0.2.2/24
```

2. Configure the routing options.

```
[edit routing-options]
user@PE1# set router-id 192.0.2.2
user@PE1# set autonomous-system 701
```

3. Configure the MPLS protocol on the interface.

```
[edit protocols mpls]
user@PE1# set interface fxp0.0 disable
user@PE1# set interface ge-0/0/3.0
```

```

user@PE1# set interface xe-1/2/1.0
user@PE1# set interface xe-1/2/0.0

```

4. Configure the OSPF protocol.

```

[edit protocols ospf]
user@PE1# set area 0.0.0.0 interface lo0.0 passive
user@PE1# set area 0.0.0.0 interface fxp0.0 disable
user@PE1# set area 0.0.0.0 interface ge-0/0/3.0 interface-type p2p
user@PE1# set area 0.0.0.0 interface ge-0/0/3.0 metric 10
user@PE1# set area 0.0.0.0 interface xe-1/2/1.0 interface-type p2p
user@PE1# set area 0.0.0.0 interface xe-1/2/1.0 metric 10
user@PE1# set area 0.0.0.0 interface xe-1/2/0.0 interface-type p2p
user@PE1# set area 0.0.0.0 interface xe-1/2/0.0 metric 10

```

5. Configure the LDP protocols on the interfaces.

```

[edit protocols ldp]
user@PE1# set interface ge-0/0/3.0
user@PE1# set interface xe-1/2/0.0
user@PE1# set interface xe-1/2/1.0
user@PE1# set interface fxp0.0 disable
user@PE1# set interface lo0.0

```

6. Configure the threshold time and the threshold count to detect MAC moves.

```

[edit protocols l2-learning global-mac-move]
user@PE1# set threshold-time 30
user@PE1# set threshold-count 4

```

7. Configure VPLS MAC move parameters like cooloff time, statistical approach wait time, interface recovery time, and virtual MAC.

```

[edit protocols l2-learning global-mac-move]
user@PE1# set cooloff-time 10
user@PE1# set statistical-approach-wait-time 10
user@PE1# set interface-recovery-time 10
user@PE1# set virtual-mac 00:00:5e:00:01:00/40

```

8. Enable MAC move action on the interface for the VPLS instance vpls_1.

```
[edit routing-instances vpls_1]
user@PE1# set instance-type vpls
user@PE1# set interface xe-1/3/1.600
user@PE1# set protocols vpls enable-mac-move-action
user@PE1# set protocols vpls no-tunnel-services
user@PE1# set protocols vpls vpls-id 100
user@PE1# set protocols vpls neighbor 192.0.2.1
```

Results

From configuration mode, confirm your configuration by entering the `show interfaces`, `show protocols`, `show routing-options`, and `show routing-instances` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@PE1# show interfaces
ge-0/0/3 {
  unit 0 {
    family inet {
      address 198.51.100.2/24;
    }
    family mpls;
  }
}
xe-1/2/0 {
  unit 0 {
    family inet {
      address 198.51.100.5/24;
    }
    family mpls;
  }
}
xe-1/2/1 {
  unit 0 {
    family inet {
      address 198.51.100.3/24;
    }
    family mpls;
  }
}
```

```

xe-1/3/1 {
    vlan-tagging;
    encapsulation vlan-vpls;
    unit 600 {
        encapsulation vlan-vpls;
        vlan-id 600;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}

```

```

user@PE1# show protocols
mpls {
    interface fxp0.0 {
        disable;
    }
    interface ge-0/0/3.0;
    interface xe-1/2/1.0;
    interface xe-1/2/0.0;
}
ospf {
    area 0.0.0.0 {
        interface lo0.0 {
            passive;
        }
        interface fxp0.0 {
            disable;
        }
        interface ge-0/0/3.0 {
            interface-type p2p;
            metric 10;
        }
        interface xe-1/2/1.0 {
            interface-type p2p;
            metric 10;
        }
    }
}

```

```

        interface xe-1/2/0.0 {
            interface-type p2p;
            metric 10;
        }
    }
}
ldp {
    interface ge-0/0/3.0;
    interface xe-1/2/0.0;
    interface xe-1/2/1.0;
    interface fxp0.0 {
        disable;
    }
    interface lo0.0;
}
l2-learning {
    global-mac-move {
        threshold-time 30;
        threshold-count 4;
    }
    global-mac-move {
        cooloff-time 10;
        statistical-approach-wait-time 10;
        interface-recovery-time 10;
        virtual-mac 00:00:5e:00:01:00/40;
    }
}
}

```

```

user@PE1# show routing-instances
vpls_1 {
    instance-type vpls;
    interface xe-1/3/1.600;
    protocols {
        vpls {
            enable-mac-move-action;
            no-tunnel-services;
            vpls-id 100;
            neighbor 192.0.2.1;
        }
    }
}
}

```

If you are done configuring the device, enter `commit` from configuration mode.

Verification

IN THIS SECTION

- [Verifying the MAC Move in a VPLS Network | 1164](#)
- [Verifying the MAC Move in a VPLS Instance | 1165](#)
- [Verifying the MAC Move Buffer in a VPLS Network | 1165](#)
- [Verifying the VPLS MAC Table for the Base IFL Approach Algorithm | 1166](#)
- [Verifying That the Interface Is Disabled | 1167](#)
- [Verifying the VPLS MAC Table for the Statistical Approach Algorithm | 1168](#)

Verify that the configuration is working properly.

Verifying the MAC Move in a VPLS Network

Purpose

Verify that the MAC move is observed in a VPLS network.

Action

From operational mode, run the `show vpls mac-move-action` command for Device PE1.

```
user@PE1> show vpls mac-move-action
Instance: vpls_1
  Local interface: xe-1/3/1.600, Index: 341
    Algorithm used : Base IFL
    Time rec       : 02:30:35
    Recovery timer : Yes
```

Meaning

The output shows Instance name, Local interface and Algorithm used indicating that VPLS MAC Move is observed in a VPLS network.

Verifying the MAC Move in a VPLS Instance

Purpose

Verify that the MAC move is observed in a VPLS instance.

Action

From operational mode, run the `show vpls mac-move-action instance instance-name` command for Device PE1.

```
user@PE1> show vpls mac-move-action instance vpls_1

Instance: vpls_1
Local interface: xe-1/3/1.600, Index: 341
Algorithm used : Base IFL
Time rec       : 02:29:35
Recovery timer : Yes
```

Meaning

The output shows Local interface, and Algorithm used indicating that VPLS MAC move has been observed in a VPLS instance.

Verifying the MAC Move Buffer in a VPLS Network

Purpose

Verify the MAC move buffer to monitor the MAC moves that are occurring in the VPLS network.

Action

From operational mode, run the `show l2-learning mac-move-buffer` command for Device PE1.

```
user@PE1> show l2-learning mac-move-buffer

MAC                Time                Bridge
Address            Rec.                Domain
00:10:00:01:00:09  03:26:00           __vpls_1__
00:10:00:01:00:05  03:26:00           __vpls_1__
00:10:00:01:00:03  03:26:00           __vpls_1__
```



```

00:10:00:01:00:05    03:26:00    __vpls_1__
00:10:00:01:00:08    03:26:00    __vpls_1__
00:10:00:01:00:01    03:26:00    __vpls_1__
00:10:00:01:00:03    03:26:00    __vpls_1__
00:10:00:01:00:01    03:26:00    __vpls_1__
00:10:00:01:00:00    03:26:00    __vpls_1__
00:10:00:01:00:01    03:26:01    __vpls_1__
00:10:00:01:00:06    03:26:01    __vpls_1__
00:10:00:01:00:02    03:26:01    __vpls_1__
00:10:00:01:00:08    03:26:01    __vpls_1__
00:10:00:01:00:00    03:26:01    __vpls_1__
00:10:00:01:00:01    03:26:01    __vpls_1__
00:10:00:01:00:09    03:26:01    __vpls_1__

```

Verifying the VPLS MAC Table for the Base IFL Approach Algorithm

Purpose

Verify the base learning interfaces for the MAC addresses. .

Action

From operational mode, run the `show vpls mac-table extensive` command to obtain extensive information of VPLS MAC table.

```

user@PE1> show vpls mac-table extensive

MAC address: 00:10:00:01:00:00
Routing instance: vpls_1
Bridging domain: __vpls_1__, VLAN : NA
Learning interface: lsi.1049165
Base learning interface: lsi.1049165
Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
Epoch: 0                      Sequence number: 1
Learning mask: 0x00000001

MAC address: 00:10:00:01:00:01
Routing instance: vpls_1
Bridging domain: __vpls_1__, VLAN : NA
Learning interface: lsi.1049165
Base learning interface: lsi.1049165

```

```

Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
Epoch: 0                      Sequence number: 1
Learning mask: 0x00000001

MAC address: 00:10:00:01:00:02
Routing instance: vpls_1
Bridging domain: __vpls_1__, VLAN : NA
Learning interface: lsi.1049165
Base learning interface: lsi.1049165
Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
Epoch: 0                      Sequence number: 1
Learning mask: 0x00000001

MAC address: 00:10:00:01:00:03
Routing instance: vpls_1
Bridging domain: __vpls_1__, VLAN : NA
Learning interface: lsi.1049165
Base learning interface: lsi.1049165
Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
Epoch: 0                      Sequence number: 1
Learning mask: 0x00000001

```

Meaning

The output of the command `show vpls mac-table extensive` shows the base learning interface of the MAC address.

Verifying That the Interface Is Disabled

Purpose

Verify that the base learning interface of the MAC address is disabled.

Action

From operational mode, run the `show interfaces interface-name` command for Device PE1.

```

user@PE1> show interfaces xe-1/3/1.600

Logical interface xe-1/3/1.600 (Index 341) (SNMP ifIndex 2864)
Flags: Up Link-Layer-Down SNMP-Traps 0x4000 VLAN-Tag [ 0x8100.600 ] Encapsulation: VLAN-VPLS

```

```

Input packets : 2234018970
Output packets: 2234728895
Protocol vpls, MTU: 1518
Flags: Is-Primary

```

Meaning

The flag link-layer-down in the output indicates that the interface is disabled.

Verifying the VPLS MAC Table for the Statistical Approach Algorithm

Purpose

Verify the VPLS MAC table for the statistical approach algorithm.

Action

From operational mode, run the `show vpls mac-table extensive` command for Device PE1.

```

user@PE1> show vpls mac-table extensive

MAC address: 00:10:00:01:00:00
  Routing instance: vpls_1
    Bridging domain: __vpls_1__, VLAN : NA
    Learning interface: xe-1/3/1.600
    Base learning interface: NULL
    Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
    Epoch: 3                               Sequence number: 442
    Learning mask: 0x00000002

MAC address: 00:10:00:01:00:01
  Routing instance: vpls_1
    Bridging domain: __vpls_1__, VLAN : NA
    Learning interface: xe-1/3/1.600
    Base learning interface: NULL
    Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
    Epoch: 3                               Sequence number: 442
    Learning mask: 0x00000003

MAC address: 00:10:00:01:00:02
  Routing instance: vpls_1

```

```

Bridging domain: __vpls_1__, VLAN : NA
Learning interface: xe-1/3/1.600
Base learning interface: NULL
Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
Epoch: 3                      Sequence number: 442
Learning mask: 0x00000002

MAC address: 00:10:00:01:00:03
Routing instance: vpls_1
Bridging domain: __vpls_1__, VLAN : NA
Learning interface: xe-1/3/1.600
Base learning interface: NULL
Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd
Epoch: 3                      Sequence number: 442
Learning mask: 0x00000002

```

Meaning

The Base learning interface is null which indicates that the statistical approach is in use.

SEE ALSO

[virtual-mac](#) | [1703](#)

[global-mac-move](#) | [1515](#)

Release History Table

Release	Description
14.2	Starting in Junos OS 14.2, you can configure the router to prevent a loop in a VPLS network.

Understanding MAC Pinning

Starting in Junos OS Release 16.1, Junos OS supports MAC pinning to prevent loops on the MX series routers. A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops in Layer 2 bridges and in virtual private LAN service (VPLS) networks. To avoid loops, you can enable the MAC pinning feature on an interface. The MAC pinning feature is applicable only when dynamic learning of MAC addresses over interfaces is enabled.

When you enable MAC pinning on an interface in a bridge domain or VPLS domain, MAC addresses learned over that interface cannot be relearned on any other interface in the same bridge domain or VPLS domain until the MAC address either ages out on the first interface or is cleared from the MAC table. If a packet with the same MAC address arrives at any other interface in the same bridge domain, it is discarded. This, effectively, controls MAC address moves and prevents the creation of loops in Layer 2 bridges and VPLS domains.

NOTE: If the timeout interval for the MAC addresses is not specified by setting the `mac-table-aging-time` statement, the MAC addresses learned over the MAC pinning interface are pinned to the interface until the default timeout period.

You can configure MAC pinning in a bridging environment and in VPLS routing instances. In a bridging environment, you can enable MAC pinning on an access interface and a trunk interface. You can also enable MAC pinning on an access interface or trunk interface of a virtual switch. To avoid loops in the bridging environment, you can use any of the configurations mentioned previously in this topic. To avoid MAC moves and loops, you can use any one of the 16 different MAC pinning configurations.

Starting in Junos OS Release 17.2, the MAC pinning feature is enabled on provider backbone bridging (PBB) and Ethernet VPN (EVPN) integration, including customer edge (CE) interfaces and EVPN over PBB core in both all-active or single-active mode.

To configure MAC pinning for PBB-EVPN, include the `mac-pinning` statement at the `[edit routing-instances pbbn protocols evpn]`, where `pbbn` is the PBB routing instance over backbone port (B-component). With this configuration, the dynamically learned MAC addresses in the PBB I-component (customer routing instance) bridge domain over CE interfaces, as well as PBB-MPLS core interfaces are pinned. This prevents MAC move on duplicate MAC detection, avoiding loop creation in a network.

Release History Table

Release	Description
17.2R1	Starting in Junos OS Release 17.2, the MAC pinning feature is enabled on provider backbone bridging (PBB) and Ethernet VPN (EVPN) integration, including customer edge (CE) interfaces and EVPN over PBB core in both all-active or single-active mode.
16.1	Starting in Junos OS Release 16.1, Junos OS supports MAC pinning to prevent loops on the MX series routers.

RELATED DOCUMENTATION

[Configuring MAC Pinning on Access Interfaces for Bridge Domains](#) | 1171

Configuring MAC Pinning on Trunk Interfaces for Bridge Domains	1172
Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch	1174
Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch	1176
Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance (LDP and BGP) for Logical Systems	1195
Configuring MAC Pinning on VPLS CE Interface for Logical Systems	1198
Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance for Logical Systems	1200
Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance for Logical Systems	1202

Configuring MAC Pinning on Access Interfaces for Bridge Domains

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in bridge domains, you can configure MAC pinning.

This topic describes how to configure MAC pinning on an access interface in a bridge domain. A logical interface configured to accept untagged packets is called an *access interface* or *access port*. When an access interface receives a tagged or an untagged packet, the interface's VLAN ID is added to the packet. The packet is then forwarded within the bridge domain that is configured with the matching VLAN ID.

To configure MAC pinning on access interfaces in bridge domains:

1. Configure the interface as an access interface and specify the VLAN ID at the [edit interfaces] hierarchy level.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port encapsulation ethernet-bridge
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode access
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id vlan-id
```

2. Configure MAC pinning on the interface by including the `mac-pinning` statement at the [edit bridge-domains] hierarchy level.

```
[edit bridge-domains]
user@host# set bridge-domain-name bridge-options interface interfacetype-fpc/pic/port mac-pinning
```

3. In configuration mode, verify the configuration.

```

user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    encapsulation ethernet-bridge;
    unit logical-unit-number {
      family bridge {
        interfaces-mode access;
        vlan-id vlan-id;
      }
    }
  }
}

user@host# show bridge-domains
bridge-domains {
  bridge-domain-name {
    bridge-options {
      interfacetype-fpc/pic/port {
        mac-pinning;
      }
    }
  }
}

```

RELATED DOCUMENTATION

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on Trunk Interfaces for Bridge Domains

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid MAC moves across interfaces in bridge domains, you can configure MAC pinning.

In this topic, we are configuring MAC pinning on a trunk interface in a bridge domain. A logical interface configured to accept any packet tagged with a VLAN ID that matches a VLAN ID specified in the domain is called a *trunk interface* or *trunk port*. When a trunk interface receives a packet tagged with a VLAN ID that matches the list of VLAN IDs specified within the bridge domain, the packet is then forwarded within the bridge domain that is configured with the matching VLAN ID.

To configure MAC pinning on trunk interfaces in bridge domains:

1. Configure the interface as a trunk interface and specify the list of VLAN IDs.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id-list vlan-id-numbers
```

2. Configure the bridge domain by specifying the name of the bridge and the VLAN ID.

```
[edit bridge-domains]
user@host# set bridge-domain-name vlan-id all
```

3. Configure MAC pinning on the interface by including the `mac-pinning` statement at the `[edit switch-options]` hierarchy level.

```
[edit switch-options]
user@host# set interface interfacetype-fpc/pic/port mac-pinning
```

4. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit logical-unit-number {
      family bridge {
        interfaces-mode trunk ;
        vlan-id-list vlan-id-numbers;
      }
    }
  }
}
```



```

    }
  }
  user@host# show bridge-domains
  bridge-domains {
    bridge-domain-name {
      vlan-id all;
    }
  }
  user@host# show switch-options
  switch-options {
    interface interfacetype-fpc/pic/port {
      mac-pinning;
    }
  }

```

RELATED DOCUMENTATION

[Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual switches, you can configure MAC pinning.

This topic describes how to configure MAC pinning on an access interface for a bridge domain in a virtual switch. A virtual switch represents a Layer 2 network as it filters and forwards traffic only at the data link layer. Each bridge domain in a virtual switch participates in Layer 2 Learning and Forwarding. When an access interface for a bridge domain receives a tagged or untagged packet, the interface's VLAN ID is added to the packet. The packet is then forwarded within the bridge domain that is configured with the matching VLAN ID.

To configure MAC pinning on access interfaces for bridge domains in a virtual switch:

1. Configure the interface as an access interface and specify the VLAN ID.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port encapsulation ethernet-bridge
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode access
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id vlan-id
```

2. Configure the routing instance as a virtual switch and specify the access interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type virtual-switch
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

3. Configure the bridge domain and specify the list of VLAN IDs.

```
[edit routing-instances]
user@host# set routing-instance-name bridge-domains bridge-domain-name vlan-id-list vlan-id-numbers
```

4. Configure MAC pinning on the interface.

```
[edit routing-instances]
user@host# set routing-instance-name bridge-domains bridge-domain-name bridge-options interface
interfacetype-fpc/pic/port mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    encapsulation ethernet-bridge;
    unit logical-unit-number {
      family bridge {
        interface-mode access;
        vlan-id vlan-id;
      }
    }
  }
}
user@host# show routing-instances
routing-instances{
```

```

    routing-instance-name {
    instance-type virtual-switch;
        interface interfacetype-fpc/pic/port;
    }
}
user@host# show bridge-domains
bridge-domains {
    bridge-domain-name {
        vlan-id -list vlan-id-numbers;
        bridge-options {
            interface interfacetype-fpc/pic/port {
                mac-pinning;
            }
        }
    }
}

```

RELATED DOCUMENTATION

[Configuring MAC Pinning on Access Interfaces for Bridge Domains](#) | 1171

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch](#) | 1176

[mac-pinning](#) | 1562

Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual switches, you can configure MAC pinning.

This topic describes how to configure MAC pinning on a trunk interface for a bridge domain in a virtual switch. A virtual switch represents a Layer 2 network as it filters and forwards traffic only at the data link layer. Each bridge domain in a virtual switch participates in Layer 2 Learning and Forwarding. When a trunk interface for a bridge domain receives a packet tagged with a VLAN ID that matches the list of VLAN IDs specified with the bridge domain, the packet is then forwarded within the bridge domain that is configured with the matching VLAN ID.

To configure MAC pinning on trunk interfaces for bridge domains in a virtual switch:

1. Configure the interface as a trunk interface and specify the list of VLAN IDs.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id-list vlan-id-numbers
```

2. Configure the routing instance as virtual switch and specify the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type virtual-switch;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

3. Configure the bridge domain and specify the list of VLAN IDs.

```
[edit routing-instances]
user@host# set routing-instance-name bridge-domains bridge-domain-name vlan-id-list vlan-id-numbers
```

4. Configure MAC pinning on the interface by including the mac-pinning statement at the [edit switch-options] hierarchy level.

```
[edit switch-options]
user@host# set interface interfacetype-fpc/pic/port mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit logical-unit-number {
      family bridge {
        interface-mode trunk ;
        vlan-id-list vlan-id-numbers;
      }
    }
  }
}
```

```

    }
user@host# show routing-instances
  routing-instances{
    routing-instance-name{
      instance-type virtual-switch;
      interface interfacetype-fpc/pic/port;
    }
  }
user@host# show bridge-domains
  bridge-domains {
    bridge-domain-name{
      vlan-id -list vlan-id-numbers;
    }
  }
}
user@host# show switch-options
switch-options {
  interface interfacetype-fpc/pic/port {
    mac-pinning;
  }
}

```

RELATED DOCUMENTATION

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance (LDP and BGP)

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning on a trunk interface for all pseudowires of the VPLS routing instance.

To configure MAC pinning for the VPLS routing instance:

1. Configure the interface as a trunk interface and specify the list of VLAN IDs.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
user@host# set interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls;
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id-list vlan-id-numbers
```

2. Configure the routing instance as VPLS and specify the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

3. Configure MAC pinning after specifying the routing protocol configuration.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls mac-pinning
```

4. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
    interfacetype-fpc/pic/port {
        flexible-vlan-tagging;
        encapsulation flexible-ethernet-services;
        unit logical-unit-number {
            encapsulation vlan-vpls;
        }
        family bridge {
            interface-mode trunk ;
            vlan-id-list vlan-id-numbers;
        }
    }
}
user@host# show routing-instances
routing-instances{
```

```

    routing-instance-name {
        instance-type vpls;
        interface interfacetype-fpc/pic/port;
    protocols{
        vpls {
            mac-pinning;
        }
    }
}
}

```

RELATED DOCUMENTATION

[Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on VPLS CE Interface

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning on a VPLS customer edge (CE) trunk interface.

To configure MAC pinning on a VPLS CE interface:

1. Configure the trunk interface and specify the list of VLAN IDs.

```

[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
user@host# set interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls;
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id-list vlan-id-numbers

```

2. Configure the VPLS routing instance and specify the CE interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

3. Configure MAC pinning on the VPLS CE interface.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls interfacetype-fpc/pic/port mac-pinning
```

4. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit logical-unit-number {
      encapsulation vlan-vpls;
    }
    family bridge {
      interface-mode trunk ;
      vlan-id-list vlan-id-numbers;
    }
  }
}
user@host# show routing-instances
routing-instances{
  routing-instance-name{
    instance-type vpls;
    interface interfacetype-fpc/pic/port;
    protocols{
      vpls {
        interface interfacetype-fpc/pic/port {
          mac-pinning;
        }
      }
    }
  }
}
```



```
}
}
```

RELATED DOCUMENTATION

[Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance \(LDP and BGP\) | 1178](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning for all pseudowires of the VPLS site in a BGP-based VPLS routing instance.

To configure MAC pinning for all pseudowires in a BGP-based VPLS Routing instance:

1. Configure the interface as a trunk interface and specify the list of VLAN IDs.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
user@host# set interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls;
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id-list vlan-id-numbers
```

2. Configure the VPLS routing instance and specify the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

3. Configure MAC pinning after specifying the routing protocol and the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls interface interfacetype-fpc/pic/port
user@host# set routing-instance-name protocols vpls site site-name mac-pinning
```

4. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
    interfacetype-fpc/pic/port {
        flexible-vlan-tagging;
        encapsulation flexible-ethernet-services;
        unit logical-unit-number {
            encapsulation vlan-vpls;
            family bridge {
                interface-mode trunk ;
                vlan-id-list vlan-id-numbers;
            }
        }
    }
}
user@host# show routing-instances
routing-instances{
    routing-instance-name {
        instance-type vpls;
        interface interfacetype-fpc/pic/port;
    protocols{
        vpls {
            interface interfacetype-fpc/pic/port;
            site site-name {
                mac-pinning;
            }
        }
    }
}
}
```

RELATED DOCUMENTATION

[Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance \(LDP and BGP\) | 1178](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning on all pseudowires of a specific neighbor of an LDP-based VPLS routing instance.

To configure MAC pinning on all pseudowires of a specific neighbor in a VPLS routing instance with LDP signaling:

1. Configure the interfaces as trunk interfaces and specify the list of VLAN IDs.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
user@host# set interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls;
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk
user@host# set interfacetype-fpc/pic/port unit logical-unit-number family bridge vlan-id-list vlan-id-numbers
```

2. Configure the VPLS routing instance and specify the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port;
```

3. Configure the routing protocol and specify the trunk interface and the VPLS identifier.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls interface interfacetype-fpc/pic/port
user@host# set routing-instance-name protocols vpls vpls-id vpls-id
```

4. Configure MAC pinning after specifying the neighbor ID.

```
user@host# set routing-instance-name protocols vpls neighbor neighbor-id mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
  interfaces {
    interfacetype-fpc/pic/port {
      flexible-vlan-tagging;
      encapsulation flexible-ethernet-services;
      unit logical-unit-number {
        encapsulation vlan-vpls;
        family bridge {
          interface-mode trunk ;
          vlan-id-list vlan-id-numbers;
        }
      }
    }
  }
user@host# show routing-instances
  routing-instances{
    routing-instance-name {
      instance-type vpls;
      interface interfacetype-fpc/pic/port;
    protocols{
      vpls {
        interface interfacetype-fpc/pic/port;
        vpls-id vpls-id;
        neighbor neighbor-id {
          mac-pinning;
        }
      }
    }
  }
```

```
}
}
```

RELATED DOCUMENTATION

[Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance | 1182](#)

[Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance \(LDP and BGP\) | 1178](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on Access Interfaces for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in logical systems, you can configure MAC pinning. A set of logical systems within a single router can handle the functions previously handled by several small routers.

This topic describes how to configure MAC pinning on access interfaces of a logical system.

To configure MAC pinning on access interfaces in logical systems:

1. Configure the access interface.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port encapsulation ethernet-vpls
```

2. Create the logical system by specifying the name of the logical system, and specify the access interface and list of VLAN IDs associated with the interface.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode access vlan-id vlan-id
```

3. Configure MAC pinning on the access interface by including the `[mac-pinning]` statement in the `[edit bridge-domains]` hierarchy.

```
[edit bridge-domains]
user@host# set bridge-domain-name bridge-options interface interfacetype-fpc/pic/port mac-pinning
```

4. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    encapsulation ethernet-vpls;
  }
}
```

```
user@host# show logical-systems
logical-systems {
  logical-system-name {
    interfaces {
      interfacetype-fpc/pic/port {
        unit logical-unit-number {
          family bridge {
            interface-mode access;
            vlan-id vlan-id;
          }
        }
      }
    }
  }
}
```

```
user@host# show bridge-domains
bridge-domains {
  bridge-domain-name {
    bridge-options {
      interface interfacetype-fpc/pic/port {
        mac-pinning;
      }
    }
  }
}
```

```
}
}
```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on Trunk Interfaces for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in logical systems, you can configure MAC pinning. A set of logical systems within a single router can handle the functions previously handled by several small routers.

This topic describes how to configure MAC pinning on trunk interfaces of a logical system.

To configure MAC pinning on trunk interfaces in logical systems:

1. Configure the interface and specify the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
```

2. Create the logical system by specifying the name of the logical system, and specify the trunk interface and list of VLAN IDs associated with the interface.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls family bridge interface-mode trunk vlan-id-list vlan-id-numbers
```

3. Configure the bridge domain by specifying the VLAN ID parameter.

```
[edit bridge-domains]
user@host# set bridge-domain-name vlan-id all
```

4. Configure MAC pinning on the trunk interface by including the `[mac-pinning]` statement at the `[edit switch-options]` hierarchy level.

```
[edit switch-options]
user@host# set interface interfacetype-fpc/pic/port mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
  }
}
```

```
user@host# show logical-systems
logical-systems {
  logical-system-name {
    interfaces {
      interfacetype-fpc/pic/port
    {
      unit 0 {
        encapsulation vlan-vpls;
        family bridge {
          interface-mode trunk;
          vlan-id-list vlan-id-numbers;
        }
      }
    }
  }
}
```



```
    }
}
```

```
user@host# show bridge-domains
bridge-domains {
    bridge-domain-name {
        vlan-id all;
    }
}
```

```
user@host# show switch-options
switch-options {
    interface interfacetype-fpc/pic/port {
        mac-pinning;
    }
}
}
```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176](#)

[Configuring MAC Pinning on Access Interfaces for Logical Systems | 1186](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on Access Interfaces in Virtual Switches for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual switches in logical systems, you can configure MAC pinning. A set of logical systems within a single router can handle the functions previously handled by several small routers.

This topic describes how to configure MAC pinning on access interfaces in virtual switch routing instance of a logical system.

To configure MAC pinning on access interfaces in virtual switches for logical systems:

1. Configure the interface and specify the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port encapsulation ethernet-vpls
```

2. Create the logical system by specifying the name of the logical system, and specify the access interface.

```
[edit ]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode access vlan-id vlan-id
```

3. Configure the routing instance as virtual switch and specify the access interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type virtual-switch;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

4. Configure the bridge domain and specify the list of VLAN IDs.

```
[edit routing-instances]
user@host# set routing-instance-name bridge-domains bridge-domain-name vlan-id-list vlan-id-numbers
user@host# set routing-instance-name bridge-domains bridge-domain-name bridge-options interface interfacetype-fpc/pic/port mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
    interfacetype-fpc/pic/port {
        encapsulation ethernet-vpls;
```

```

    }
}

```

```

user@host# show logical-systems
logical-systems {
    logical-system-name {
        interfaces {
            interfacetype-fpc/pic/port {
                unit logical-unit-number {
                    family bridge {
                        interface-mode access;
                        vlan-id vlan-id;
                    }
                }
            }
        }
    }
}

```

```

user@host# show routing-instances
routing-instances {
    routing-instance-name {
        instance-type virtual-switch;
        interface interfacetype-fpc/pic/port;
        bridge-domains {
            bridge-domain-name {
                vlan-id-list vlan-id-numbers;
                bridge-options {
                    interface interfacetype-fpc/pic/port {
                        mac-pinning;
                    }
                }
            }
        }
    }
}
}
}
}
}
}
}
}
}
}

```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on Trunk Interfaces in Virtual Switches for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual switches in logical systems, you can configure MAC pinning. A set of logical systems within a single router can handle the functions previously handled by several small routers.

This topic describes how to configure MAC pinning on trunk interfaces in virtual switch routing instance of a logical system.

To configure MAC pinning on trunk interfaces in virtual switches for logical systems:

1. Configure the interface and specify the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
```

2. Create the logical system by specifying the name of the logical system and specify the trunk interface.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number family bridge interface-mode trunk vlan-id-list vlan-id-numbers
```

3. Configure the routing instance as a virtual switch and specify the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type virtual-switch;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

4. Configure the bridge domain and specify the list of VLAN IDs.

```
[edit routing-instances]
user@host# set routing-instance-name bridge-domains bridge-domain-name vlan-id-list vlan-id-numbers
```

5. Configure MAC pinning on the trunk interface at the [edit switch-options] hierarchy level.

```
[edit switch-options]
user@host# set interface interfacetype-fpc/pic/port mac-pinning
```

6. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
    interfacetype-fpc/pic/port {
        flexible-vlan-tagging;
        encapsulation flexible-ethernet-services;
    }
}
```

```
user@host# show logical-systems
logical-systems {
    logical-system-name {
        interfaces {
            interfacetype-fpc/pic/port {
                unit logical-unit-number {
                    encapsulation vlan-vpls;
                    family bridge {
                        interface-mode trunk;
                        vlan-id-list vlan-id-numbers;
                    }
                }
            }
        }
    }
}
```

```
user@host# show routing-instances
routing-instances {
    routing-instance-name {
```

```
user@host# show switch-options
switch-options {
    interface interfacetype-fpc/pic/port {
        mac-pinning;
    }
}
}
```

Understanding MAC Pinning | 1169

Configuring MAC Pinning on Access Interfaces in Virtual Switches for Logical Systems | 1190

Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176

mac-pinning | 1562

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across

interfaces in virtual switches in logical systems, you can configure MAC pinning. A set of logical systems within a single router can handle the functions previously handled by several small routers.

This topic describes how to configure MAC pinning for all pseudowires of the VPLS routing instance for logical systems.

To configure MAC pinning for all pseudowires of the VPLS routing instance for logical systems:

1. Configure the interface by specifying the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
```

2. Create the logical system by specifying the name and the trunk interface on the logical unit.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls family bridge interface-mode trunk vlan-id-list vlan-id-numbers
```

3. Configure the VPLS routing instance.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
user@host# set routing-instance-name protocols vpls mac-pinning
```

4. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
    interfacetype-fpc/pic/port {
        flexible-vlan-tagging;
        encapsulation flexible-ethernet-services;
    }
}
```

```
user@host# show logical-systems
logical-systems {
    logical-system-name {
```

```

interfaces {
    interfacetype-fpc/pic/port {
        unit logical-unit-number {
            encapsulation vlan-vpls;
            family bridge {
                interface-mode trunk;
                vlan-id-list vlan-id-numbers;
            }
        }
    }
}

```

```

user@host# show routing-instances
routing-instances {
    routing-instance-name {
        instance-type vpls;
        interface interfacetype-fpc/pic/port;
        protocols {
            vpls {
                mac-pinning;
            }
        }
    }
}

```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning for All Pseudowires of the VPLS Routing Instance \(LDP and BGP\) | 1178](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on VPLS CE Interface for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning on a VPLS customer edge (CE) trunk interface in a logical system.

To configure MAC pinning for VPLS customer edge interface for logical systems:

1. Configure the interfaces by specifying the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
```

2. Create the logical system by specifying the name and the trunk interface on the logical unit.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls family bridge interface-mode trunk vlan-id-list vlan-id-numbers
```

3. Configure the VPLS CE interface and VPLS routing instance.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

4. Configure MAC pinning on the VPLS CE interface.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls interfacetype-fpc/pic/port mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
```

```

    }
}

```

```

user@host# show logical-systems
logical-systems {
  logical-system-name {
    interfaces {
      interfacetype-fpc/pic/port {
        unit logical-unit-number {
          encapsulation vlan-vpls;
          family bridge {
            interface-mode trunk;
            vlan-id-list vlan-id-numbers;
          }
        }
      }
    }
  }
}

```

```

user@host# show routing-instances
routing-instances{
  routing-instance-name {
    instance-type vpls;
    interface interfacetype-fpc/pic/port;
  protocols{
    vpls {
      interface interfacetype-fpc/pic/port {
        mac-pinning;
      }
    }
  }
}

```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on VPLS CE Interface | 1180](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning for all pseudowires of the VPLS site in a BGP-based VPLS routing instance for a logical system.

To configure MAC pinning for all pseudowires in a BGP-based VPLS Routing instance for a logical system:

1. Configure the interface by specifying the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
```

2. Create the logical system and specify the trunk interface and list of VLAN IDs on the logical unit.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls family bridge interface-mode trunk vlan-id-list vlan-id-numbers
```

3. Configure the VPLS routing instance and specify the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls;
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

4. Configure MAC pinning after specifying the routing protocol and the trunk interface.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls interface interfacetype-fpc/pic/port
user@host# set routing-instance-name protocols vpls site site-name mac-pinning
```

5. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
    interfacetype-fpc/pic/port {
        flexible-vlan-tagging;
        encapsulation flexible-ethernet-services;
    }
}
```

```
user@host# show logical-systems
logical-systems {
    logical-system-name {
        interfaces {
            interfacetype-fpc/pic/port {
                unit logical-unit-number {
                    encapsulation vlan-vpls;
                    family bridge {
                        interface-mode trunk;
                        vlan-id-list vlan-id-numbers;
                    }
                }
            }
        }
    }
}
```

```
routing-instances{
    routing-instance-name {
        instance-type vpls;
        interface interfacetype-fpc/pic/port;
    protocols{
        vpls {
            interface interfacetype-fpc/pic/port;
            site site-name {
                mac-pinning;
            }
        }
    }
}
```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning for All Pseudowires of the VPLS Site in a BGP-Based VPLS Routing Instance | 1182](#)

[mac-pinning | 1562](#)

Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance for Logical Systems

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. To avoid loops across interfaces in virtual private LAN services (VPLS), you can configure MAC pinning.

This topic describes how to configure MAC pinning on all pseudowires of a specific neighbor of an LDP-based VPLS routing instance for logical systems.

To configure MAC pinning on all pseudowires of a specific neighbor in a VPLS routing instance with LDP signaling for logical systems:

1. Configure the interfaces by specifying the encapsulation.

```
[edit interfaces]
user@host# set interfacetype-fpc/pic/port flexible-vlan-tagging
user@host# set interfacetype-fpc/pic/port encapsulation flexible-ethernet-services
```

2. Create the logical system interface by specifying the name of the logical system and specifying the trunk interface on the logical unit.

```
[edit]
user@host# set logical-systems logical-system-name interfaces interfacetype-fpc/pic/port unit logical-unit-number encapsulation vlan-vpls family bridge interface-mode trunk vlan-id-list vlan-id-numbers
```

3. Configure the VPLS routing instance and specify the interface.

```
[edit routing-instances]
user@host# set routing-instance-name instance-type vpls
user@host# set routing-instance-name interface interfacetype-fpc/pic/port
```

4. Configure the routing protocol and specify the trunk interface and the VPLS identifier.

```
[edit routing-instances]
user@host# set routing-instance-name protocols vpls interface interfacetype-fpc/pic/port
user@host# set routing-instance-name protocols vpls vpls-id vpls-id
```

5. Configure MAC pinning after specifying the neighbor ID.

```
user@host# set routing-instance-name protocols vpls neighbor neighbor-id mac-pinning
```

6. In configuration mode, verify the configuration.

```
user@host# show interfaces
interfaces {
  interfacetype-fpc/pic/port {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
  }
}
```

```
user@host# show logical-systems
logical-systems {
  logical-system-name {
    interfaces {
      interfacetype-fpc/pic/port {
        unit logical-unit-number {
          encapsulation vlan-vpls;
          family bridge {
            interface-mode trunk;
            vlan-id-list vlan-id-numbers;
          }
        }
      }
    }
  }
}
```

```
user@host# show routing-instance
routing-instances{
  routing-instance-name {
```

```

instance-type vpls;
interface interfacetype-fpc/pic/port;
protocols{
  vpls {
    interface interfacetype-fpc/pic/port;
    vpls-id vpls-id;
    neighbor neighbor-id {
      mac-pinning;
    }
  }
}

```

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on All Pseudowires of a Specific Neighbor of LDP-Based VPLS Routing Instance | 1184](#)

[mac-pinning | 1562](#)

Example: Prevention of Loops in Bridge Domains by Enabling the MAC Pinning Feature on Access Interfaces

IN THIS SECTION

- [Requirements | 1205](#)
- [Overview | 1205](#)
- [Configuration | 1206](#)
- [Verification | 1209](#)

This example shows how to avoid loops in bridge domains by enabling the MAC pinning feature on access interfaces.

Requirements

This example uses the following hardware and software components:

- MX Series 5G Universal Routing Platforms
- Junos OS Release 16.1 running on the routers

Overview

IN THIS SECTION

- [Topology](#) | [1205](#)

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. Loops can occur in Layer 2 bridges and in VPLS networks. To avoid loops, you can enable the MAC pinning feature on the interfaces. The MAC pinning feature is applicable only when dynamic learning of MAC addresses over interfaces is enabled.

This example shows how to enable MAC pinning on two access interfaces in a bridge domain.

Topology

In this example, you configure the interfaces `ge-4/0/6` and `xe-4/2/0` on the MX Series router as access interfaces. Access interfaces accept both untagged and tagged packets and forward the packets within a specified bridge domain, `bd1`. Specify **1** as the VLAN ID for the interfaces and the bridge domain. When an untagged or a tagged packet is received on any of the access interfaces, the packet is accepted, the VLAN ID is added to the packet, and the packet is forwarded within the bridge domain that is configured with the matching ID.

In the bridge domain, after specifying the VLAN ID, specify **131071** as the maximum number of MAC addresses that can be learned on the access interfaces and specify **1048575** as the size of the MAC address table for the bridge domain or VLAN.

In this topology, frequent MAC moves can occur, which can result in loops. To prevent these loops, you can configure MAC pinning. When you configure MAC pinning on an interface, the MAC address learned on the interface cannot be learned on another interface in the same bridge domain. For example, configure MAC pinning on the access interface `ge-4/0/6`. When a packet is received on this interface, the packet is accepted, the VLAN ID is added and the packet is forwarded within the bridge domain with the matching ID. However, if a packet with the same MAC address is received on any other access interface, say `xe-4/2/0`, the packet is discarded or dropped as that MAC address is pinned to the

access interface `ge-4/0/6` . This behavior is common to all access interfaces configured on the router, regardless of whether access pinning is enabled on the access interface or not.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 1206](#)
- [Procedure | 1206](#)
- [Results | 1208](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the `[edit]` hierarchy level.

```
set interfaces ge-4/0/6 encapsulation ethernet-bridge
set interfaces ge-4/0/6 unit 0 family bridge interface-mode access
set interfaces ge-4/0/6 unit 0 family bridge vlan-id 1
set interfaces xe-4/2/0 encapsulation ethernet-bridge
set interfaces xe-4/2/0 unit 0 family bridge interface-mode access
set interfaces xe-4/2/0 unit 0 family bridge vlan-id 1
set bridge-domains bd1 vlan-id 1
set bridge-domains bd1 bridge-options mac-table-size 1048575
set bridge-domains bd1 bridge-options interface ge-4/0/6.0 interface-mac-limit 131071
set bridge-domains bd1 bridge-options interface ge-4/0/6.0 mac-pinning
set bridge-domains bd1 bridge-options interface xe-4/2/0.0 interface-mac-limit 131071
set bridge-domains bd1 bridge-options interface xe-4/2/0.0 mac-pinning
```

Procedure

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure MAC pinning on access interfaces in bridge domains:

1. Configure both the interfaces as access interfaces and specify the VLAN ID.

```
[edit interfaces]
user@host# set interfaces ge-4/0/6 encapsulation ethernet-bridge
user@host# set interfaces ge-4/0/6 unit 0 family bridge interface-mode access
user@host# set interfaces ge-4/0/6 unit 0 family bridge vlan-id 1
user@host# set interfaces xe-4/2/0 encapsulation ethernet-bridge
user@host# set interfaces xe-4/2/0 unit 0 family bridge interface-mode access
user@host# set interfaces xe-4/2/0 unit 0 family bridge vlan-id 1
```

2. Specify the name of the bridge domain.

```
[edit bridge-domains]
user@host# set bridge-domains bd1 vlan-id 1
```

3. Specify the size of the MAC address table for the bridge domain.

```
[edit bridge-domains]
user@host# set bridge-domains bd1 bridge-options mac-table-size 1048575
```

4. Specify the maximum number of MAC addresses that can be learned on both the access interfaces.

```
[edit bridge-domains]
user@host# set bridge-domains bd1 bridge-options interface ge-4/0/6.0 interface-mac-limit 131071
user@host# set bridge-domains bd1 bridge-options interface xe-4/2/0.0 interface-mac-limit 131071
```

5. Configure MAC pinning on both the access interfaces.

```
[edit bridge-domains]
user@host# set bridge-domains bd1 bridge-options interface ge-4/0/6.0 mac-pinning
user@host# set bridge-domains bd1 bridge-options interface xe-4/2/0.0 mac-pinning
```

Results

From configuration mode, confirm your configuration by entering `show interfaces` and `show bridge-domains` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show interfaces
ge-4/0/6 {
encapsulation ethernet-bridge;
  unit 0 {
    family bridge {
      interface-mode access;
      vlan-id 1;
    }
  }
}
xe-4/2/0 {
encapsulation ethernet-bridge;
  unit 0 {
    family bridge {
      interface-mode access;
      vlan-id 1;
    }
  }
}

user@host# show bridge-domains
bridge-domains {
  bd1 {
    vlan-id 1;
    bridge-options {
      mac-table-size {
        1048575;
      }
      interface ge-4/0/6.0 {
        interface-mac-limit {
          131071;
        }
        mac-pinning;
      }
      interface xe-4/2/0.0 {
        interface-mac-limit {
```

Verification

● Verifying That MAC Pinning Is Configured Correctly | 1209

Purpose

Action

```

user@host> show l2-learning interface
Routing Instance Name : default-switch
Logical Interface flags (DL -disable learning, AD -packet action drop,
                        LH - MAC limit hit, DN - Interface Down, MP - MAC Pinning)
Logical      BD      MAC      STP      Logical
Interface    Name     Limit   State   Interface flags
xe-4/0/6.0
              BD_True  131000  Forwarding
              BD_True  131000  Forwarding
              BD_True  131000  Forwarding
              BD_True  131000  Forwarding
              BD_True  131000  Forwarding
Routing Instance Name : default-switch

```

Logical Interface flags (DL -disable learning, AD -packet action drop,
LH - MAC limit hit, DN - Interface Down, MP - MAC Pinning)

Logical Interface	BD Name	MAC Limit	STP State	Logical Interface flags
xe-4/2/0.0		131000		MP
	BD_Tru..	131000	Forwarding	
	BD_Tru..	131000	Forwarding	
	BD_Tru..	131000	Forwarding	
	BD_Tru..	131000	Forwarding	
	BD_Tru..	131000	Forwarding	

Meaning

The Interface flags field indicates the interfaces that have MAC pinning enabled.

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains | 1171](#)

[Configuring MAC Pinning on Access Interfaces for Bridge Domains in a Virtual Switch | 1174](#)

[mac-pinning | 1562](#)

Example: Prevention of Loops in Bridge Domains by Enabling the MAC Pinnning Feature on Trunk Interfaces

IN THIS SECTION

- [Requirements | 1211](#)
- [Overview | 1211](#)
- [Configuration | 1212](#)
- [Verification | 1218](#)

This example shows how to avoid loops in bridge domains by enabling the MAC pinning feature on trunk interfaces.

Requirements

This example uses the following hardware and software components:

- MX Series 5G Universal Routing Platforms
- Junos OS Release 16.1 running on the routers

Overview

IN THIS SECTION

- [Topology](#) | [1211](#)

A MAC move occurs when a MAC address frequently appears on a different physical interface than the one it was learned on. Frequent MAC moves indicate the presence of loops. Loops can occur in Layer 2 bridges and in VPLS networks. To avoid loops, you can enable the MAC pinning feature on the interfaces. The MAC pinning feature is applicable only when dynamic learning of MAC addresses over interfaces is enabled.

This example shows how to enable MAC pinning on three aggregated trunk interfaces in a bridge domain.

Topology

In this example, you configure the interfaces `xe-0/1/1` and `xe-0/3/1` on the MX Series router as an aggregated Ethernet interface, `ae1`. You can configure the other four interfaces, `ge-4/0/6`, `ge-4/1/6`, `xe-4/2/0`, and `xe-4/3/0`, as aggregated Ethernet interfaces, `ae2` and `ae3`. Each of these aggregated Ethernet interfaces are configured as trunk interfaces. Trunk interfaces accept only tagged packets and forward the packets within a specified bridge domain, `BD_Trunk_all`. Specify the list of VLAN IDs for the interfaces and the bridge domain. When a tagged packet is received on any of the aggregated trunk interfaces, the packet is accepted, and the packet is forwarded within the bridge domain that is configured with the matching ID.

In the bridge domain, after specifying the VLAN ID, specify **131000** as the maximum number of MAC addresses that can be learned on each of the aggregated Ethernet trunk interfaces and specify **1048575** as the size of the MAC address table for the bridge domain or VLAN.

In this topology, frequent MAC moves can occur, which can result in loops. To prevent these loops, you can configure MAC pinning. When you configure MAC pinning on an interface, the MAC address learned on the interface cannot be learned on another interface in the same bridge domain. For example, configure MAC pinning on the aggregated Ethernet interface ae1. When a packet is received on this interface, the packet is accepted, and the packet is forwarded within the bridge domain with the matching ID. However, if a packet with the same MAC address is received on any other trunk interface, say ae2, the packet is discarded or dropped as that MAC address is pinned to the trunk interface ae1. This behavior is common to all trunk interfaces configured on the router, regardless of whether access pinning is enabled on the trunk interface or not.

Configuration

IN THIS SECTION

- [CLI Quick Configuration | 1212](#)
- [Procedure | 1213](#)
- [Results | 1215](#)

CLI Quick Configuration

To quickly configure this example, copy the following commands, paste them into a text file, remove any line breaks, change any details necessary to match your network configuration, and then copy and paste the commands into the CLI at the [edit] hierarchy level.

```
set interfaces xe-0/1/1 gigether-options 802.3ad ae1
set interfaces xe-0/3/1 gigether-options 802.3ad ae1
set interfaces ge-4/0/6 gigether-options 802.3ad ae3
set interfaces ge-4/1/6 gigether-options 802.3ad ae3
set interfaces xe-4/2/0 gigether-options 802.3ad ae2
set interfaces xe-4/3/0 gigether-options 802.3ad ae2
set interfaces ae1 flexible-vlan-tagging
set interfaces ae1 encapsulation flexible-ethernet-services
set interfaces ae1 unit 0 family bridge interface-mode trunk
set interfaces ae1 unit 0 family bridge vlan-id-list 1-5
set interfaces ae2 flexible-vlan-tagging
set interfaces ae2 encapsulation flexible-ethernet-services
set interfaces ae2 unit 0 family bridge interface-mode trunk
set interfaces ae2 unit 0 family bridge vlan-id-list 1-5
set interfaces ae3 flexible-vlan-tagging
```

```

set interfaces ae3 encapsulation flexible-ethernet-services
set interfaces ae3 unit 0 family bridge interface-mode trunk
set interfaces ae3 unit 0 family bridge vlan-id-list 1-5
set bridge-domains BD_Trunk_all vlan-id-list 1-5
set bridge-domains BD_Trunk_all bridge-options mac-table-size 1048575
set bridge-domains BD_Trunk_all bridge-options interface ae1.0 interface-mac-limit 131000
set bridge-domains BD_Trunk_all bridge-options interface ae2.0 interface-mac-limit 131000
set bridge-domains BD_Trunk_all bridge-options interface ae3.0 interface-mac-limit 131000
set switch-options interface ae1.0 interface-mac-limit 131000
set switch-options interface ae1.0 mac-pinning
set switch-options interface ae2.0 interface-mac-limit 131000
set switch-options interface ae2.0 mac-pinning
set switch-options interface ae3.0 interface-mac-limit 131000
set switch-options interface ae3.0 mac-pinning

```

Procedure

Step-by-Step Procedure

The following example requires you to navigate various levels in the configuration hierarchy. For information about navigating the CLI, see *Using the CLI Editor in Configuration Mode*.

To configure MAC pinning on trunk interfaces in bridge domains:

1. Configure the interfaces as member aggregated Ethernet interfaces.

```

[edit interfaces]
user@host# set interfaces xe-0/1/1 gigether-options 802.3ad ae1
user@host# set interfaces xe-0/3/1 gigether-options 802.3ad ae1
user@host# set interfaces ge-4/0/6 gigether-options 802.3ad ae3
user@host# set interfaces ge-4/1/6 gigether-options 802.3ad ae3
user@host# set interfaces xe-4/2/0 gigether-options 802.3ad ae2
user@host# set interfaces xe-4/3/0 gigether-options 802.3ad ae2

```

2. Configure the aggregated Ethernet interfaces as trunk interfaces and specify the list of VLAN IDs.

```

user@host# set interfaces ae1 flexible-vlan-tagging
user@host# set interfaces ae1 encapsulation flexible-ethernet-services
user@host# set interfaces ae1 unit 0 family bridge interface-mode trunk
user@host# set interfaces ae1 unit 0 family bridge vlan-id-list 1-5
user@host# set interfaces ae2 flexible-vlan-tagging

```



```

user@host# set interfaces ae2 encapsulation flexible-ethernet-services
user@host# set interfaces ae2 unit 0 family bridge interface-mode trunk
user@host# set interfaces ae2 unit 0 family bridge vlan-id-list 1-5
user@host# set interfaces ae3 flexible-vlan-tagging
user@host# set interfaces ae3 encapsulation flexible-ethernet-services
user@host# set interfaces ae3 unit 0 family bridge interface-mode trunk
user@host# set interfaces ae3 unit 0 family bridge vlan-id-list 1-5

```

3. Specify the name of the bridge domain.

```

[edit bridge-domains]
user@host# set bridge-domains BD_Trunk_all vlan-id-list 1-5

```

4. Specify the size of the MAC address table for the bridge domain.

```

user@host# set bridge-domains BD_Trunk_all bridge-options mac-table-size 1048575

```

5. Specify the maximum number of MAC addresses that can be learned on all three trunk interfaces.

```

user@host# set bridge-domains BD_Trunk_all bridge-options interface ae1.0 interface-mac-limit 131000
user@host# set bridge-domains BD_Trunk_all bridge-options interface ae2.0 interface-mac-limit 131000
user@host# set bridge-domains BD_Trunk_all bridge-options interface ae3.0 interface-mac-limit 131000

```

6. Configure MAC pinning on each of the aggregated Ethernet interfaces at the [edit switch-options] hierarchy level.

```

[edit switch-options]
user@host# set switch-options interface ae1.0 interface-mac-limit 131000
user@host# set switch-options interface ae1.0 mac-pinning
user@host# set switch-options interface ae2.0 interface-mac-limit 131000
user@host# set switch-options interface ae2.0 mac-pinning
user@host# set switch-options interface ae3.0 interface-mac-limit 131000
user@host# set switch-options interface ae3.0 mac-pinning

```

Results

From configuration mode, confirm your configuration by entering `show interfaces` and `show bridge-domains` commands. If the output does not display the intended configuration, repeat the instructions in this example to correct the configuration.

```
user@host# show interfaces
interfaces {
  xe-0/0/0 {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit 0 {
      family bridge {
        interface-mode trunk;
        vlan-id-list 1-5;
      }
    }
  }
  xe-0/1/1 {
    gigether-options {
      802.3ad ae1;
    }
  }
  xe-0/3/1 {
    gigether-options {
      802.3ad ae1;
    }
  }
  ge-4/0/6 {
    gigether-options {
      802.3ad ae3;
    }
  }
  ge-4/1/6 {
    gigether-options {
      802.3ad ae3;
    }
  }
  xe-4/2/0 {
    gigether-options {
      802.3ad ae2;
    }
  }
}
```

```

}
xe-4/3/0 {
    gigether-options {
        802.3ad ae2;
    }
}
ae1 {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit 0 {
        family bridge {
            interface-mode trunk;
            vlan-id-list 1-5;
        }
    }
}
ae2 {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit 0 {
        family bridge {
            interface-mode trunk;
            vlan-id-list 1-5;
        }
    }
}
ae3 {
    flexible-vlan-tagging;
    encapsulation flexible-ethernet-services;
    unit 0 {
        family bridge {
            interface-mode trunk;
            vlan-id-list 1-5;
        }
    }
}
}

user@host# show bridge-domains
bridge-domains {
    BD_Trunk_all {
        vlan-id-list 1-5;
        bridge-options {

```

```

        mac-table-size {
            1048575;
        }
        interface ae1.0 {
            interface-mac-limit {
                131000;
            }
        }
        interface ae2.0 {
            interface-mac-limit {
                131000;
            }
        }
        interface ae3.0 {
            interface-mac-limit {
                131000;
            }
        }
    }
}

```

user@host# show switch-options

```

switch-options {
    interface ae1.0 {
        interface-mac-limit {
            131000;
        }
        mac-pinning;
    }
    interface ae2.0 {
        interface-mac-limit {
            131000;
        }
        mac-pinning;
    }
    interface ae3.0 {
        interface-mac-limit {
            131000;
        }
        mac-pinning;
    }
}

```

```
}  
}
```

If you have completed configuring the device, enter `commit` from the configuration mode.

Verification

IN THIS SECTION

Verifying that MAC Pinning Is Configured Correctly | 1218

Verifying that MAC Pinning Is Configured Correctly

Purpose

Ensure that MAC pinning is enabled on the trunk interfaces.

Action

From operational mode, enter the `show l2-learning interface` command.

```
user@host> show l2-learning interface  
Routing Instance Name : default-switch  
Logical Interface flags (DL -disable learning, AD -packet action drop,  
                        LH - MAC limit hit, DN - Interface Down, MP - MAC Pinning)  
Logical      BD      MAC      STP      Logical  
Interface    Name    Limit   State   Interface flags  
xe-0/0/0.0           8192  
              BD_Tru.. 1024    Forwarding  
              BD_Tru.. 1024    Forwarding  
              BD_Tru.. 1024    Forwarding  
              BD_Tru.. 1024    Forwarding  
              BD_Tru.. 1024    Forwarding  
Routing Instance Name : default-switch  
Logical Interface flags (DL -disable learning, AD -packet action drop,  
                        LH - MAC limit hit, DN - Interface Down, MP - MAC Pinning)  
Logical      BD      MAC      STP      Logical  
Interface    Name    Limit   State   Interface flags  
ae1.0           131000  
                        MP
```

```

BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
Routing Instance Name : default-switch
Logical Interface flags (DL -disable learning, AD -packet action drop,
                        LH - MAC limit hit, DN - Interface Down, MP - MAC Pinning)
Logical      BD      MAC      STP      Logical
Interface    Name    Limit   State   Interface flags
ae2.0                131000                MP
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
Routing Instance Name : default-switch
Logical Interface flags (DL -disable learning, AD -packet action drop,
                        LH - MAC limit hit, DN - Interface Down, MP - MAC Pinning)
Logical      BD      MAC      STP      Logical
Interface    Name    Limit   State   Interface flags
ae3.0                131000                MP
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding
BD_Tr.. 131000 Forwarding

```

Meaning

The Interface flags field indicates the interfaces that have MAC pinning enabled.

RELATED DOCUMENTATION

[Understanding MAC Pinning | 1169](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains | 1172](#)

[Configuring MAC Pinning on Trunk Interfaces for Bridge Domains in a Virtual Switch | 1176](#)

[mac-pinning | 1562](#)

Configuring Improved VPLS MAC Address Learning on T4000 Routers with Type 5 FPCs

Junos OS Release 12.3 enables improved virtual private LAN service (VPLS) MAC address learning on T4000 routers with Type 5 FPCs by supporting up to 262,143 MAC addresses per VPLS routing instance. In Junos OS releases before Release 12.3, T4000 routers with Type 5 FPCs support only 65,535 MAC addresses per VPLS routing instance.

Before you begin, configure VPLS. See ["Configuring VPLS Routing Instances" on page 674](#).

To enable improved VPLS MAC address learning on T4000 routers with Type 5 FPCs:

1. Enable the network services mode by including the `enhanced-mode` statement at the `[edit chassis network-services]` hierarchy level.

```
[edit chassis network-services]
user@host# set enhanced-mode
```

NOTE: After you configure the `enhanced-mode` statement and commit your configuration, a warning message prompts you to reboot the router.

2. Perform a system reboot in operational mode.

```
user@host> request system-reboot
```

After the router reboots, only the T4000 Type 5 FPCs are online while the remaining FPCs are offline. You can verify the status of the FPCs by using the `show chassis fpc operational mode` command.

3. Modify the size of the VPLS MAC address table at the `[edit routing-instance instance-name protocols vpls]` hierarchy level.

```
[edit routing-instance instance-name protocols vpls]
user@host# set mac-table-size size
```

For example, to set the MAC address learning limit to 262,143 addresses for each vpls routing instance:

```
[edit routing-instance vpls protocols vpls]
user@host# set mac-table-size 262143
```

NOTE: The `enhanced-mode` statement supports up to 262,143 MAC addresses per VPLS routing instance. However, the MAC address learning limit for each interface remains the same (that is, 65,535 MAC addresses).

4. In configuration mode, verify the configuration.

```
user@host# show routing-instances instance-name
vpls {
  instance-type vpls;
  protocols {
    vpls {
      mac-table-size {
        262143;
      }
    }
  }
}
```

To disable the improved VPLS MAC address learning feature on T4000 routers with Type 5 FPCs, include the `delete chassis network-services enhanced-mode` statement at the `[edit]` hierarchy level.

NOTE: After you disable network services mode and commit your configuration, a warning message prompts you to reboot the router. You must reboot the router. Continuing without a reboot might result in unexpected system behavior.

RELATED DOCUMENTATION

[enhanced-mode](#)

[Network Services Mode Overview](#)

[Configuring VPLS Routing Instances](#) | 674

| [show chassis fpc](#)

Understanding Qualified MAC Learning

IN THIS SECTION

- [Qualified MAC Learning on the First, Second, and Third VLAN Tags | 1222](#)

MAC learning is the process by which a device learns the MAC addresses of all the nodes on a network.

When a node is first connected to an Ethernet LAN or VLAN, it has no information about the other nodes on the network. As data is sent through the network, data packets include a data frame listing their source and destination MAC addresses. The data frame is forwarded to a target port, which is connected to the second device. The MAC address is learned locally at the target port, which facilitates communications for frames that later enter the target port and contain addresses previously learned from a received frame.

During MAC learning, on a ingress packet, the outer tag is implicitly removed (using the pop operation) and the learning happens on the inner tag. MAC learning is preceded by VLAN manipulation. VLAN used for learning can be changed by VLAN push/pop/swap operations.

Qualified MAC learning enables a device to learn the MAC addresses of network nodes by determining the innermost VLAN tag of single-tagged, 2-tagged, or 3-tagged ingress packets without deleting the outer tag (using the pop operation). If the ingress packet has one tag, learning happens on VLAN 4096, and no tags are implicitly removed. If the ingress packet has two tags, MAC learning happens on the second VLAN and no tags are implicitly removed. If the ingress packet has more than three tags, all tags beyond the third tag are treated as part of data and are not considered for MAC learning.

Qualified MAC Learning on the First, Second, and Third VLAN Tags

For a single-tagged ingress packet, qualified MAC learning happens on VLAN 4096, which is the default VLAN.

In the case of a 2-tagged ingress packet, you enable qualified MAC learning on the second (inner) tag by using the `vlan-id inner-all` configuration statement on the VPLS routing instance. Learning on the second tag happens without the implicit removal of the first (outer) tag. If the ingress packet has more than two tags, all tags beyond the second tag are treated as part of data and are not considered for learning.

Similarly, for an 3-tagged ingress packet, you enable qualified MAC learning on the third (innermost) tag by configuring the `deep-vlan-qualified-learning vlan_tag_number` statement on the logical interface along with the `vlan-id inner-all` statement on the routing instance. Qualified MAC learning happens on the third tag, and no VLAN manipulation happens on the outer tags. However, if `deep-vlan-qualified-learning vlan_tag_number` is enabled to learn on the third VLAN and the ingress packet has only two VLANs, the qualified MAC learning happens on the default VLAN 4096.

Note the following points while configuring qualified MAC learning:

- A logical interface contained in a VPLS routing instance configured with `vlan-id inner-all` might or might not have `deep-vlan-qualified-learning vlan_tag_number` configured.
- A logical interface configured with `deep-vlan-qualified-learning vlan_tag_number`, must belong to a VPLS routing instance that also has `vlan-id inner-all` configured.
- A logical interface configured with `deep-vlan-qualified-learning vlan_tag_number`, must also be configured with one outer and one inner tag.

RELATED DOCUMENTATION

deep-vlan-qualified-learning 1460
vlan-id inner-all 1708

Qualified Learning VPLS Routing Instance Behavior

The following tables summarize the VPLS routing instance behavior regarding qualified MAC learning.

[Table 25 on page 1224](#) summarizes the scenario when `vlan-id all` is not configured on a routing instance. All VLAN identifiers specified on the logical interfaces are included in the routing instance.

Table 25: VPLS Routing Instance Behavior When vlan-id all Is Not Configured *(Continued)*

Configured tags on Logical Interface							
Incoming tags	Outer tag only	Outer tag range only	Outer and inner tags with VLAN-map (no VLAN-id on the routing-instance)	Outer and inner tag only	Outer tag and inner range tag with VLAN-map	Outer tag and inner range	LSI
2 tags	OK	OK	OK (swap/pop-swap: MAC learned on vpls db but no VLAN-id)	OK (MAC learned on VPLS database if no VLAN-id on routing instance; MAC learning on routing instance VLAN-id otherwise)	OK (MAC learning on outer VLAN after VLAN map)	OK (MAC learning on outer VLAN)	Learning on outer tag
2 tags mismatch	Drop	Drop	Drop	Drop	Drop	Drop	Learning on outer tag
> 2 tags	OK	OK	Same as with 2 tags	Same as with 2 tags	Same as with 2 tags	Same as with 2 tags	Learning on outer tag

Table 26 on page 1226 summarizes the scenario when `vlan-id all` is configured on a routing instance. All VLAN identifiers specified on the logical interfaces are included in the routing instance.

Table 26: VPLS Routing Instance Behavior when `vlan-id all` is configured

Configured tags on Logical Interface							
Incoming tags	Outer tag only	Outer tag range only	Outer and inner tags with VLAN-map	Outer and inner tag	Outer tag and inner range tag with VLAN-map	Outer tag and inner range	LSI
No tag	Drop	Drop	Invalid configuration	Drop	Invalid configuration	Drop	Learning on VLAN 4096
1 tag	OK, learning on the tag	OK, learning on the tag	Invalid configuration	Drop	Invalid configuration	Drop	Learning on the tag
1 tag mismatch	Drop	Drop	Invalid configuration	Drop	Invalid configuration	Drop	Learning on the tag
2 tags	OK, learning on the tag	OK, learning on the tag	Invalid configuration	Pop outer tag, MAC learning on inner tag	Invalid configuration	Pop, MAC learning on inner tag	Learning on the outer tag
2 tags mismatch	Drop	Drop	Invalid configuration	Drop	Invalid configuration	Drop	Learning on the outer tag

Table 26: VPLS Routing Instance Behavior when vlan-id all is configured (*Continued*)

Configured tags on Logical Interface							
Incoming tags	Outer tag only	Outer tag range only	Outer and inner tags with VLAN-map	Outer and inner tag	Outer tag and inner range tag with VLAN-map	Outer tag and inner range	LSI
> 2 tags	OK, learning on the tag	OK, learning on the tag	Invalid configuration	Pop outer tag, learning on the second tag	Invalid configuration	Pop, learning on the second tag	Learning on the outer tag

Table 27 on page 1227 summarizes the scenario when `vlan-id inner-all` is configured on a routing instance, but `deep-vlan-qualified-learning vlan_tag_number` is not configured on the logical interface .

Table 27: VPLS Routing Instance and Logical Interface Behavior When `vlan-id inner-all` Is Configured

Configured tags on Logical Interface							
Incoming tags	Outer tag only	Outer tag range only	Outer and inner tags with VLAN-map	Outer and inner tags only	Outer tag and inner range tag with VLAN-map	Outer tag and inner tag range	LSI
No tag	Drop (OK with native VLAN-id)	Drop	Drop	Drop	Drop	Drop	Learning on VLAN 4096
1 tag	OK (MAC learning on VLAN 4096)	OK (MAC learning on VLAN 4096)	Drop	Drop	Drop	Drop	Learning on VLAN 4096

Table 27: VPLS Routing Instance and Logical Interface Behavior When vlan-id inner-all Is Configured (Continued)

Configured tags on Logical Interface							
Incoming tags	Outer tag only	Outer tag range only	Outer and inner tags with VLAN-map	Outer and inner tags only	Outer tag and inner range tag with VLAN-map	Outer tag and inner tag range	LSI
1 tag mismatch	Drop	Drop	Drop	Drop	Drop	Drop	Learning on VLAN 4096
2 tags	OK (MAC learning on the inner VLAN)	OK (MAC learning on the inner VLAN)	OK (MAC learning on inner VLAN after VLAN-map operation	OK (MAC learning on the inner VLAN). No implicit popping of outer tag.	OK (MAC learning on the inner VLAN after VLAN-map operation).	OK (MAC learning on inner VLAN). No implicit popping of outer tag.	Learning on the inner tag
2 tags mismatch	Drop	Drop	Drop	Drop	Drop	Drop	Learning on the inner tag
> 2 tags	OK (MAC learning on the 2nd VLAN tag)	OK (MAC learning on the 2nd VLAN tag)	OK (MAC learning on the 2nd VLAN after VLAN-map operation)	OK (MAC learning on the 2nd incoming VLAN). No popping of outer tag.	OK (MAC learning on the 2nd VLAN after VLAN-map operation)	OK (MAC learning on the 2nd incoming VLAN). No popping of outer tag.	Learning on the 2nd tag

Table 28 on page 1229 summarizes the scenario when vlan-id inner-all is configured on a routing instance and deep-vlan-qualified-learning is configured on the logical interface .

Table 28: VPLS Routing Instance and Logical Interface Behavior When vlan-id inner-all and deep-vlan-qualified-learning Is Configured

Configured tags on Logical Interface						
Incoming tags	Outer tag only	Outer tag range only	Outer and inner tags with VLAN-map	Outer and inner tags only	Outer tag and inner range tag with VLAN-map	Outer tag and inner tag range
No tag	Invalid configuration	Invalid configuration	Drop	Invalid configuration	Invalid configuration	Invalid configuration
1 tag	Invalid configuration	Invalid configuration	Drop	Invalid configuration	Invalid configuration	Invalid configuration
1 tag mismatch	Invalid configuration	Invalid configuration	Drop	Invalid configuration	Invalid configuration	Invalid configuration
2 tags	Invalid configuration	Invalid configuration	OK (learning on VLAN 4096)	OK (learning on VLAN 4096)	Invalid configuration	Invalid configuration
2 tags mismatch	Invalid configuration	Invalid configuration	Drop	Invalid configuration	Invalid configuration	Invalid configuration
3 tags	Invalid configuration	Invalid configuration	OK (MAC learning on innermost VLAN)	OK (MAC learning on innermost VLAN)	Invalid configuration	Invalid configuration

RELATED DOCUMENTATION

[Understanding Qualified MAC Learning](#) | 1222

Configuring Qualified MAC Learning

Qualified MAC learning enables a device to learn the MAC addresses of network nodes by learning the innermost VLAN tag of single vlan-tagged, 2-tagged, or 3-tagged ingress packets without deleting the outer tag (using the pop operation).

To enable qualified MAC learning on the innermost VLAN tag for 2 or 3 tagged packets:

1. In configuration mode, go to the [edit routing-instances] hierarchy level.

```
[edit]
user@host# edit routing-instances instance-name
```

2. Include the `vlan-id inner-all` statement.

```
[edit interfaces instance-name]
user@host# set vlan vlan-id inner-all
```

For enabling qualified MAC learning on the third VLAN tag (innermost) of a 3-tagged packet, along with `vlan-id inner-all`, configure the `deep-vlan-qualified-learning vlan_tag_number` statement.

1. In configuration mode, go to the edit interfaces `interface-name` unit `logical_unit_number` hierarchy level.

```
[edit]
user@host# edit interfaces interface-name unit logical_unit_number
```

2. Include the `deep-vlan-qualified-learning vlan_tag_number` statement.

For bidirectional traffic flow, include the statement `input-vlan-map pop`.

```
[edit interfaces interface-name unit logical_unit_number]
user@host# set deep-vlan-qualified-learning 3
user@host# set input-vlan-map pop
```

3. Verify learned MAC address information..

```
user@host# show vpls mac-table
```

RELATED DOCUMENTATION

[Understanding Qualified MAC Learning | 1222](#)

[deep-vlan-qualified-learning | 1460](#)

[vlan-id inner-all | 1708](#)

Configuring Class of Service and Firewall Filters in VPLS

IN THIS CHAPTER

- [Configuring EXP-Based Traffic Classification for VPLS | 1232](#)
- [Configuring Firewall Filters and Policers for VPLS | 1233](#)
- [Firewall Filter Match Conditions for VPLS Traffic | 1239](#)

Configuring EXP-Based Traffic Classification for VPLS

You can enable EXP classification on traffic entering core facing VPLS LSI interfaces on a VPLS routing instance by configuring either a logical tunnel interface (lt-) or the `no-tunnel-services` statement. By configuring either of these, a default EXP classifier is enabled on every core facing interface that includes **family mpls** in its configuration. This feature works on MX Series routers and EX Series switches only. You can configure an EXP classifier explicitly at the `[edit class-of-service]` hierarchy level. For more information about EXP classifiers, see the [Class of Service User Guide \(Routers and EX9200 Switches\)](#).

To enable EXP classification on traffic entering core facing VPLS LSI interfaces on a VPLS routing instance, include the `no-tunnel-services` statement:

```
no-tunnel-services;
```

You can include this statement at the following hierarchy levels:

- `[edit routing-instances routing-instance-name protocols vpls]`
- `[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls]`

RELATED DOCUMENTATION

[Configuring Firewall Filters and Policers for VPLS | 1233](#)

Configuring Firewall Filters and Policers for VPLS

IN THIS SECTION

- [Configuring a VPLS Filter | 1234](#)
- [Configuring a VPLS Policer | 1237](#)

You can configure both firewall filters and policers for VPLS. Firewall filters allow you to filter packets based on their components and to perform an action on packets that match the filter. Policers allow you to limit the amount of traffic that passes into or out of an interface.

VPLS filters and policers act on a Layer 2 frame that includes the media access control (MAC) header (after any VLAN rewrite or other rules are applied), but does not include the cyclical redundancy check (CRC) field.

You can apply VPLS filters and policers on the PE router to customer-facing interfaces only.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

NOTE: The behavior of firewall filters processing with MAC addresses differs between DPCs and MPCs. On MPCs, interface filters are always applied before MAC learning occurs. The input forwarding table filter is applied after MAC learning is completed. However, on DPCs, MAC learning occurs independently of the application of filters. If the CE-facing interface of the PE where the firewall filter is applied is an MPC, then the MAC entry times out and is never learned again. However, if the CE-facing interface of the PE where the firewall filter is applied is an DP, then the MAC entry is not timed out and if the MAC address entry is manually cleared, it is relearned.

The following sections explain how to configure filters and policers for VPLS:

Configuring a VPLS Filter

To configure a filter for VPLS, include the filter statement at the [edit firewall family vpls] hierarchy level:

```
[edit firewall family vpls]
filter filter-name {
  interface-specific;
  term term-name {
    from {
      match-conditions;
    }
    then {
      actions;
    }
  }
}
```

For more information about how to configure firewall filters, see the [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#). For information on how to configure a VPLS filter match condition, see ["Firewall Filter Match Conditions for VPLS Traffic" on page 1239](#).

To configure a filter for VPLS traffic, complete the following tasks:

Configuring an Interface-Specific Counter for VPLS

When you configure a firewall filter for VPLS and apply it to multiple interfaces, you can specify individual counters specific to each interface. This allows you to collect separate statistics on the traffic transiting each interface.

To generate an interface-specific counter for VPLS, you configure the `interface-specific` statement. A separate instantiation of the filter is generated. This filter instance has a different name (based on the interface name) and collects statistics on the interface specified only.

To configure interface-specific counters, include the `interface-specific` statement at the [edit firewall family vpls filter *filter-name*] hierarchy level:

```
[edit firewall family vpls filter filter-name]
interface-specific;
```

NOTE: The counter name is restricted to 24 bytes. If the renamed counter exceeds this maximum length, it might be rejected.

Configuring an Action for the VPLS Filter

You can configure the following actions for a VPLS filter at the [edit firewall family vpls filter *filter-name* term *term-name* then] hierarchy level: accept, count, discard, forwarding-class, loss-priority, next, policer.

Configuring VPLS FTFs

Forwarding table filters (FTFs) are filters configured for forwarding tables. For VPLS, they are attached to the destination MAC (DMAC) forwarding table of the VPLS routing instance. You define VPLS FTFs in the same manner as any other type of FTF. You can only apply a VPLS FTF as an input filter.

To specify a VPLS FTF, include the filter input statement at the [edit routing-instance *routing-instance-name* forwarding-options family vpls] hierarchy level:

```
[edit routing-instance routing-instance-name forwarding-options family vpls]
filter input filter-name;
```

Changing Precedence for Spanning-Tree BPDU Packets

Spanning tree BPDU packets are automatically set to a high precedence. The queue number on these packets is set to 3. On M Series routers (except the M320 router) by default, a queue value of 3 indicates high precedence. To enable this higher precedence on BPDU packets, an instance-specific BPDU precedence filter named `default_bpdu_filter` is automatically attached to the VPLS DMAC table. This filter places a high precedence on all packets sent to `01:80:c2:00:00:00/24`.

You can overwrite this filter by configuring a VPLS FTF filter and applying it to the VPLS routing instance. For more information, see ["Configuring VPLS FTFs" on page 1235](#) and ["Applying a VPLS Filter to a VPLS Routing Instance" on page 1236](#).

Applying a VPLS Filter to an Interface

To apply a VPLS filter to an interface, include the filter statement:

```
filter {
  group index;
```

```

input input-filter-name;
output output-filter-name;
}

```

You can include this statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *number* family vpls]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *number* family vpls]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

In the input statement, list the name of the VPLS filter to be evaluated when packets are received on the interface. In the output statement, list the name of the VPLS filter to be evaluated when packets are transmitted on the interface.

NOTE: For output interface filters, MAC addresses are learned after the filter action is completed. When an output interface filter's action is discard, the packet is dropped before the MAC address is learned. However, an input interface filter learns the MAC address before discarding the packet.

Applying a VPLS Filter to a VPLS Routing Instance

You can apply a VPLS filter to a VPLS routing instance. The filter checks traffic passing through the specified routing instance.

Input routing instance filters learn the MAC address before the filter action is completed, so if the filter action is discard, the MAC address is learned before the packet is dropped.

To apply a VPLS filter to packets arriving at a VPLS routing instance and specify the filter, include the filter input statement at the [edit routing-instances *routing-instance-name* forwarding-options family vpls] hierarchy level:

```

[edit routing-instances routing-instance-name forwarding-options family vpls]
filter input input-filter-name;

```

Configuring a Filter for Flooded Traffic

You can configure a VPLS filter to filter flooded packets. CE routers typically flood the following types of packets to PE routers in VPLS routing instances:

- Layer 2 broadcast packets
- Layer 2 multicast packets
- Layer 2 unicast packets with an unknown destination MAC address
- Layer 2 packets with a MAC entry in the DMAC routing table

You can configure filters to manage how these flooded packets are distributed to the other PE routers in the VPLS routing instance.

To apply a flooding filter to packets arriving at the PE router in the VPLS routing instance, and specify the filter, include the `flood input` statement:

```
flood input filter-name;
```

You can include this statement at the following hierarchy levels:

- [edit routing-instances *routing-instance-name* forwarding-options family vpls]
- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options family vpls]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

Configuring a VPLS Policer

You can configure a policer for VPLS traffic. The VPLS policer configuration is similar to the configuration of any other type of policer.

VPLS policers have the following characteristics:

- You cannot police the default VPLS routes stored in the flood table from PE router-sourced flood traffic.
- When specifying policing bandwidth, the VPLS policer considers all Layer 2 bytes in a packet to determine the packet length.

To configure a VPLS policer, include the policer statement at the [edit firewall] hierarchy level:

```
[edit firewall]
policer policer-name {
    bandwidth-limit limit;
    burst-size-limit limit;
    then action;
}
```

To apply a VPLS policer to an interface, include the policer statement:

```
policer {
    input input-policer-name;
    output output-policer-name;
}
```

You can include this statement at the following hierarchy levels:

- [edit interfaces *interface-name* unit *number* family vpls]
- [edit logical-systems *logical-system-name* interfaces *interface-name* unit *number* family vpls]

NOTE: ACX Series routers do not support the [edit logical-systems] hierarchy.

In the input statement, list the name of the VPLS policer to be evaluated when packets are received on the interface. In the output statement, list the name of the VPLS policer to be evaluated when packets are transmitted on the interface. This type of VPLS policer can only apply to unicast packets. For information about how to filter flood packets, see ["Configuring a Filter for Flooded Traffic" on page 1237](#).

RELATED DOCUMENTATION

[Routing Policies, Firewall Filters, and Traffic Policers User Guide](#)

[Firewall Filter Match Conditions for VPLS Traffic | 1239](#)

Firewall Filter Match Conditions for VPLS Traffic

In the `from` statement in the VPLS filter term, you specify conditions that the packet must match for the action in the `then` statement to be taken. All conditions in the `from` statement must match for the action to be taken. The order in which you specify match conditions is not important, because a packet must match all the conditions in a term for a match to occur.

If you specify no match conditions in a term, that term matches all packets.

An individual condition in a `from` statement can contain a list of values. For example, you can specify numeric ranges. You can also specify multiple source addresses or destination addresses. When a condition defines a list of values, a match occurs if one of the values in the list matches the packet.

Individual conditions in a `from` statement can be negated. When you negate a condition, you are defining an explicit mismatch. For example, the negated match condition for `forwarding-class` is `forwarding-class-except`. If a packet matches a negated condition, it is immediately considered not to match the `from` statement, and the next term in the filter is evaluated, if there is one. If there are no more terms, the packet is discarded.

You can configure a firewall filter with match conditions for Virtual Private LAN Service (VPLS) traffic (family `vpls`). [Table 29 on page 1239](#) describes the *match-conditions* you can configure at the `[edit firewall family vpls filter filter-name term term-name from]` hierarchy level.

NOTE: Not all match conditions for VPLS traffic are supported on all routing platforms or switching platforms. A number of match conditions for VPLS traffic are supported only on MX Series 5G Universal Routing Platforms.

In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Table 29: Firewall Filter Match Conditions for VPLS Traffic

Match Condition	Description
<code>destination-mac-address</code> <i>address</i>	Match the destination media access control (MAC) address of a VPLS packet.

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
destination-port <i>number</i>	<p>(MX Series routers and EX Series switches only) Match the UDP or TCP destination port field.</p> <p>You cannot specify both the port and destination-port match conditions in the same term.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the port numbers are also listed): afs (1483), bgp (179), biff (512), bootpc (68), bootps (67), cmd (514), cvspserver (2401), dhcp (67), domain (53), eklogin (2105), ekshell (2106), exec (512), finger (79), ftp (21), ftp-data (20), http (80), https (443), ident (113), imap (143), kerberos-sec (88), klogin (543), kpasswd (761), krb-prop (754), krbupdate (760), kshell (544), ldap (389), ldp (646), login (513), mobileip-agent (434), mobilip-mn (435), msdp (639), netbios-dgm (138), netbios-ns (137), netbios-ssn (139), nfsd (2049), nntp (119), ntalk (518), ntp (123), pop3 (110), pptp (1723), printer (515), radacct (1813), radius (1812), rip (520), rkinit (2108), smtp (25), snmp (161), snmptrap (162), snpp (444), socks (1080), ssh (22), sunrpc (111), syslog (514), tacacs (49), tacacs-ds (65), talk (517), telnet (23), tftp (69), timed (525), who (513), or xdmcp (177).</p>
destination-port-except <i>number</i>	<p>(MX Series routers and EX Series switches only) Do not match on the TCP or UDP destination port field. You cannot specify both the port and destination-port match conditions in the same term.</p>
destination-prefix-list <i>name</i>	<p>(ACX Series routers, MX Series routers, and EX Series switches only) Match destination prefixes in the specified list. Specify the name of a prefix list defined at the [edit policy-options prefix-list <i>prefix-list-name</i>] hierarchy level.</p> <p>NOTE: VPLS prefix lists support only IPv4 addresses. IPv6 addresses included in a VPLS prefix list will be discarded.</p>
destination-prefix-list <i>name</i> except	<p>(MX Series routers and EX Series switches only) Do not match destination prefixes in the specified list. For more information, see the destination-prefix-list match condition.</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
<code>dscp number</code>	<p>(MX Series routers and EX Series switches only) Match the Differentiated Services code point (DSCP). The DiffServ protocol uses the type-of-service (ToS) byte in the IP header. The most significant 6 bits of this byte form the DSCP. For more information, see the Understanding How Behavior Aggregate Classifiers Prioritize Trusted Traffic.</p> <p>You can specify a numeric value from 0 through 63. To specify the value in hexadecimal form, include 0x as a prefix. To specify the value in binary form, include b as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> • RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: ef (46). • RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points: <p>af11 (10), af12 (12), af13 (14),</p> <p>af21 (18), af22 (20), af23 (22),</p> <p>af31 (26), af32 (28), af33 (30),</p> <p>af41 (34), af42 (36), af43 (38)</p>
<code>dscp-except number</code>	<p>(MX Series routers and EX Series switches only) Do not match on the DSCP. For details, see the dscp match condition.</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description	
ether-type <i>values</i>	<p>Match the 2-octet IEEE 802.3 Length/EtherType field to the specified value or list of values.</p> <p>You can specify decimal or hexadecimal values from 0 through 65535 (0xFFFF). A value from 0 through 1500 (0x05DC) specifies the length of an Ethernet Version 1 frame. A value from 1536 (0x0600) through 65535 specifies the EtherType (nature of the MAC client protocol) of an Ethernet Version 2 frame.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the hexadecimal values are also listed): aarp (0x80F3), appletalk (0x809B), arp (0x0806), ipv4 (0x0800), ipv6 (0x86DD), mpls-multicast (0x8848), mpls-unicast (0x8847), oam (0x8902), ppp (0x880B), pppoe-discovery (0x8863), pppoe-session (0x8864), or sna (0x80D5).</p>	
ether-type-except <i>values</i>	<p>Do not match the 2-octet Length/EtherType field to the specified value or list of values.</p> <p>For details about specifying the <i>values</i>, see the ether-type match condition.</p>	
flexible-match-mask <i>value</i>	bit-length	<p>Starting in Junos OS 14.2, flexible offset filters are supported in firewall hierarchy configurations.</p> <p>Length of the data to be matched in bits, not needed for string input (0..128)</p>
	bit-offset	Bit offset after the (match-start + byte) offset (0..7)
	byte-offset	Byte offset after the match start point
	flexible-mask-name	Select a flexible match from predefined template field
	mask-in-hex	Mask out bits in the packet data to be matched

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description	
	match-start	Start point to match in packet
	prefix	Value data/string to be matched
flexible-match-range <i>value</i>	bit-length	Length of the data to be matched in bits (0..32)
	bit-offset	Bit offset after the (match-start + byte) offset (0..7)
	byte-offset	Byte offset after the match start point
	flexible-range-name	Select a flexible match from predefined template field
	match-start	Start point to match in packet
	range	Range of values to be matched
	range-except	Do not match this range of values
forwarding-class <i>class</i>	Match the forwarding class. Specify assured-forwarding, best-effort, expedited-forwarding, or network-control.	
forwarding-class-except <i>class</i>	Do not match the forwarding class. For details, see the forwarding-class match condition.	

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
icmp-code <i>message-code</i>	<p>Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the next-header icmp or next-header icmp6 match condition in the same term.</p> <p>If you configure this match condition, you must also configure the icmp-type <i>message-type</i> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> parameter-problem: ip6-header-bad (0), unrecognized-next-header (1), unrecognized-option (2) time-exceeded: ttl-eq-zero-during-reassembly (1), ttl-eq-zero-during-transit (0) destination-unreachable: address-unreachable (3), administratively-prohibited (1), no-route-to-destination (0), port-unreachable (4)
icmp-code-except <i>message-code</i>	Do not match the ICMP message code field. For details, see the icmp-code match condition.

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
<code>icmp-code <i>number</i></code>	<p>(MX Series routers and EX Series switches only) Match the ICMP message code field.</p> <p>If you configure this match condition, we recommend that you also configure the <code>ip-protocol icmp</code> or <code>ip-protocol icmp6</code> match condition in the same term.</p> <p>If you configure this match condition, you must also configure the <code>icmp-type <i>message-type</i></code> match condition in the same term. An ICMP message code provides more specific information than an ICMP message type, but the meaning of an ICMP message code is dependent on the associated ICMP message type.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed). The keywords are grouped by the ICMP type with which they are associated:</p> <ul style="list-style-type: none"> parameter-problem: <code>ip6-header-bad</code> (0), <code>unrecognized-next-header</code> (1), <code>unrecognized-option</code> (2) time-exceeded: <code>ttl-eq-zero-during-reassembly</code> (1), <code>ttl-eq-zero-during-transit</code> (0) destination-unreachable: <code>address-unreachable</code> (3), <code>administratively-prohibited</code> (1), <code>no-route-to-destination</code> (0), <code>port-unreachable</code> (4)
<code>icmp-code-except <i>number</i></code>	<p>(MX Series routers and EX Series switches only) Do not match on the ICMP code field. For details, see the <code>icmp-code</code> match condition.</p>
<code>interface <i>interface-name</i></code>	<p>Interface on which the packet was received. You can configure a match condition that matches packets based on the interface on which they were received.</p> <p>NOTE: If you configure this match condition with an interface that does not exist, the term does not match any packet.</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
interface-group <i>group-number</i>	<p>Match the logical interface on which the packet was received to the specified interface group or set of interface groups. For <i>group-number</i>, specify a single value or a range of values from 0 through 255.</p> <p>To assign a logical interface to an interface group <i>group-number</i>, specify the <i>group-number</i> at the [interfaces <i>interface-name</i> unit <i>number</i> family <i>family</i> filter group] hierarchy level.</p> <p>For more information, see Filtering Packets Received on a Set of Interface Groups Overview.</p> <p>NOTE: This match condition is not supported on T4000 Type 5 FPCs.</p>
interface-group-except <i>group-name</i>	<p>Do not match the logical interface on which the packet was received to the specified interface group or set of interface groups. For details, see the interface-group match condition.</p> <p>NOTE: This match condition is not supported on T4000 Type 5 FPCs.</p>
interface-set <i>interface-set-name</i>	<p>Match the interface on which the packet was received to the specified interface set.</p> <p>To define an interface set, include the interface-set statement at the [edit firewall] hierarchy level. For more information, see Filtering Packets Received on an Interface Set Overview.</p>
ip-address <i>address</i>	<p>(MX Series routers and EX Series switches only) 32-bit address that supports the standard syntax for IPv4 addresses.</p> <p>Note that when using this term, the match condition ether-type IPv4 must be defined on the same term.</p>
ip-destination-address <i>address</i>	<p>(MX Series routers and EX Series switches only) 32-bit address that is the final destination node address for the packet.</p> <p>Note that when using this term, the match condition ether-type IPv4 must be defined on the same term.</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
ip-precedence <i>ip-precedence-field</i>	(MX Series routers and EX Series switches only) IP precedence field. In place of the numeric field value, you can specify one of the following text synonyms (the field values are also listed): critical-ecp (0xa0), flash (0x60), flash-override (0x80), immediate (0x40), internet-control (0xc0), net-control (0xe0), priority (0x20), or routine (0x00).
ip-precedence-except <i>ip-precedence-field</i>	(MX Series routers and EX Series switches only) Do not match on the IP precedence field.
ip-protocol <i>number</i>	(MX Series routers and EX Series switches only) IP protocol field.
ip-protocol-except <i>number</i>	(MX Series routers and EX Series switches only) Do not match on the IP protocol field.
ip-source-address <i>address</i>	<p>(MX Series routers and EX Series switches only) IP address of the source node sending the packet.</p> <p>Note that when using this term, the match condition ether-type IPv4 must also be defined on the same term.</p>
ipv6-source-prefix-list <i>named-list</i>	(MX Series only) Match the IPv6 source address in a <i>named-list</i> .
ipv6-address <i>address</i>	(MX Series and EX9200 only) 128-bit address that supports the standard syntax for IPv6 addresses. Starting in Junos OS 14.2, firewall family bridge IPv6 match criteria is supported on MX Series and EX9200 switches.
ipv6-destination-address <i>address</i>	((MX Series and EX9200 only) 128-bit address that is the final destination node address for this packet. Note that when using this term, the match condition ether-type IPv6 must be defined on the same term.

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
ipv6-destination-prefix-list <i>named-list</i>	(MX Series only) Match the IPv6 destination addresses in a <i>named-list</i> .

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
ipv6-next-header <i>protocol</i>	<p>(MX Series only) Match IPv6 next header protocol type.</p> <p>The following list shows the supported values for <i>protocol</i>:</p> <ul style="list-style-type: none"> • ah—IP Security authentication header • dstopts—IPv6 destination options • egp—Exterior gateway protocol • esp—IPSec Encapsulating Security Payload • fragment—IPv6 fragment header • gre—Generic routing encapsulation • hop-by-hop—IPv6 hop by hop options • icmp—Internet Control Message Protocol • icmp6—Internet Control Message Protocol Version 6 • igmp—Internet Group Management Protocol • ipip—IP in IP • ipv6—IPv6 in IP • no-next-header—IPv6 no next header • ospf—Open Shortest Path First • pim—Protocol Independent Multicast • routing—IPv6 routing header • rsvp—Resource Reservation Protocol • sctp—Stream Control Transmission Protocol • tcp—Transmission Control Protocol • udp—User Datagram Protocol

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
	<ul style="list-style-type: none">• vrrp—Virtual Router Redundancy Protocol
ipv6-next-header-except <i>protocol</i>	(MX Series only) Do not match the IPv6 next header protocol type.

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
ipv6-payload-protocol <i>protocol</i>	<p>(MX Series only) Match IPv6 payload protocol type.</p> <p>The following list shows the supported values for <i>protocol</i>:</p> <ul style="list-style-type: none"> • ah—IP Security authentication header • dstopts—IPv6 destination options • egp—Exterior gateway protocol • esp—IPSec Encapsulating Security Payload • fragment—IPv6 fragment header • gre—Generic routing encapsulation • hop-by-hop—IPv6 hop by hop options • icmp—Internet Control Message Protocol • icmp6—Internet Control Message Protocol Version 6 • igmp—Internet Group Management Protocol • ipip—IP in IP • ipv6—IPv6 in IP • no-next-header—IPv6 no next header • ospf—Open Shortest Path First • pim—Protocol Independent Multicast • routing—IPv6 routing header • rsvp—Resource Reservation Protocol • sctp—Stream Control Transmission Protocol • tcp—Transmission Control Protocol • udp—User Datagram Protocol

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
	<ul style="list-style-type: none"> • vrrp—Virtual Router Redundancy Protocol
ipv6-payload-protocol-except <i>protocol</i>	(MX Series only) Do not match the IPv6 payload protocol.
ipv6-prefix-list <i>named-list</i>	(MX Series only) Match the IPv6 address in a <i>named-list</i> .
ipv6-source-address <i>address</i>	(MX Series only) 128-bit address that is the originating source node address for this packet.
ipv6-traffic-class <i>number</i>	<p>(MX Series only) Differentiated Services code point (DSCP). The DiffServ protocol uses the type-of-service (ToS) byte in the IP header. The most significant 6 bits of this byte form the DSCP. For more information, see Understanding How Behavior Aggregate Classifiers Prioritize Trusted Traffic.</p> <p>You can specify a numeric value from 0 through 63. To specify the value in hexadecimal form, include 0x as a prefix. To specify the value in binary form, include b as a prefix.</p> <p>In place of the numeric value, you can specify one of the following text synonyms (the field values are also listed):</p> <ul style="list-style-type: none"> • RFC 3246, <i>An Expedited Forwarding PHB (Per-Hop Behavior)</i>, defines one code point: ef (46). • RFC 2597, <i>Assured Forwarding PHB Group</i>, defines 4 classes, with 3 drop precedences in each class, for a total of 12 code points: <p>af11 (10), af12 (12), af13 (14),</p> <p>af21 (18), af22 (20), af23 (22),</p> <p>af31 (26), af32 (28), af33 (30),</p> <p>af41 (34), af42 (36), af43 (38)</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
ipv6-traffic-class-except <i>number</i>	Do not match the DSCP number.
learn-vlan-1p-priority <i>number</i>	<p>(MX Series routers, M320 router, and EX Series switches only) Match on the IEEE 802.1p learned VLAN priority bits in the provider VLAN tag (the only tag in a single-tag frame with 802.1Q VLAN tags or the outer tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the user-vlan-1p-priority match condition.</p> <p>NOTE: This match condition supports the presence of a control word for MX Series routers and the M320 router.</p>
learn-vlan-1p-priority-except <i>number</i>	<p>(MX Series routers, M320 router, and EX Series switches only) Do not match on the IEEE 802.1p learned VLAN priority bits. For details, see the learn-vlan-1p-priority match condition.</p> <p>NOTE: This match condition supports the presence of a control word for MX Series routers and the M320 router.</p>
learn-vlan-dei	(MX Series routers and EX Series switches only) Match the user VLAN ID drop eligibility indicator (DEI) bit.
learn-vlan-dei-except	(MX Series routers and EX Series switches only) Do not match the user VLAN ID DEI bit.
learn-vlan-id <i>number</i>	(MX Series routers and EX Series switches only) VLAN identifier used for MAC learning.
learn-vlan-id-except <i>number</i>	(MX Series routers and EX Series switches only) Do not match on the VLAN identifier used for MAC learning.

Table 29: Firewall Filter Match Conditions for VPLS Traffic *(Continued)*

Match Condition	Description
<code>loss-priority <i>level</i></code>	<p>Packet loss priority (PLP) level. Specify a single level or multiple levels: low, medium-low, medium-high, or high.</p> <p>Supported on M120 and M320 routers; M7i and M10i routers with the Enhanced CFEB (CFEB-E); and MX Series routers.</p> <p>For IP traffic on M320, MX Series, and T Series routers with Enhanced II Flexible PIC Concentrators (FPCs) and EX Series switches, you must include the tri-color statement at the [edit class-of-service] hierarchy level to commit a PLP configuration with any of the four levels specified. If the tri-color statement is not enabled, you can only configure the high and low levels. This applies to all protocol families.</p> <p>For information about the tri-color statement and about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see Understanding How Forwarding Classes Assign Classes to Output Queues.</p>
<code>loss-priority-except <i>level</i></code>	<p>Do not match on the packet loss priority level. Specify a single level or multiple levels: low, medium-low, medium-high, or high.</p> <p>For information about using behavior aggregate (BA) classifiers to set the PLP level of incoming packets, see Understanding How Behavior Aggregate Classifiers Prioritize Trusted Traffic.</p>
<code>port <i>number</i></code>	<p>(MX Series routers and EX Series switches only) TCP or UDP source or destination port. You cannot specify both the port match condition and either the destination-port or source-port match condition in the same term.</p>
<code>port-except <i>number</i></code>	<p>(MX Series routers and EX Series switches only) Do not match on the TCP or UDP source or destination port. You cannot specify both the port match condition and either the destination-port or source-port match condition in the same term.</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
prefix-list <i>name</i>	<p>(MX Series routers and EX Series switches only) Match the destination or source prefixes in the specified list. Specify the name of a prefix list defined at the [edit policy-options prefix-list <i>prefix-list-name</i>] hierarchy level.</p> <p>NOTE: VPLS prefix lists support only IPV4 addresses. IPV6 addresses included in a VPLS prefix list will be discarded.</p>
prefix-list <i>name</i> except	<p>(MX Series routers and EX Series switches only) Do not match the destination or source prefixes in the specified list. For more information, see the destination-prefix-list match condition.</p>
source-mac-address <i>address</i>	Source MAC address of a VPLS packet.
source-port <i>number</i>	<p>(MX Series routers and EX Series switches only) TCP or UDP source port field. You cannot specify the port and source-port match conditions in the same term.</p>
source-port-except <i>number</i>	<p>(MX Series routers and EX Series switches only) Do not match on the TCP or UDP source port field. You cannot specify the port and source-port match conditions in the same term.</p>
source-prefix-list <i>name</i>	<p>(ACX Series routers, MX Series routers, and EX Series switches only) Match the source prefixes in the specified prefix list. Specify a prefix list name defined at the [edit policy-options prefix-list <i>prefix-list-name</i>] hierarchy level.</p> <p>NOTE: VPLS prefix lists support only IPV4 addresses. IPV6 addresses included in a VPLS prefix list will be discarded.</p>
source-prefix-list <i>name</i> except	<p>(MX Series routers and EX Series switches only) Do not match the source prefixes in the specified prefix list. For more information, see the source-prefix-list match condition.</p>

Table 29: Firewall Filter Match Conditions for VPLS Traffic (*Continued*)

Match Condition	Description
tcp-flags <i>flags</i>	<p>Match one or more of the low-order 6 bits in the 8-bit TCP flags field in the TCP header.</p> <p>To specify individual bit fields, you can specify the following text synonyms or hexadecimal values:</p> <ul style="list-style-type: none"> • fin (0x01) • syn (0x02) • rst (0x04) • push (0x08) • ack (0x10) • urgent (0x20) <p>In a TCP session, the SYN flag is set only in the initial packet sent, while the ACK flag is set in all packets sent after the initial packet.</p> <p>You can string together multiple flags using the bit-field logical operators.</p> <p>If you configure this match condition for IPv6 traffic, we recommend that you also configure the next-header tcp match condition in the same term to specify that the TCP protocol is being used on the port.</p>
traffic-type <i>type-name</i>	(MX Series routers and EX Series switches only) Traffic type. Specify broadcast, multicast, unknown-unicast, or known-unicast.
traffic-type-except <i>type-name</i>	(MX Series routers and EX Series switches only) Do not match on the traffic type. Specify broadcast, multicast, unknown-unicast, or known-unicast.

Table 29: Firewall Filter Match Conditions for VPLS Traffic (Continued)

Match Condition	Description
<code>user-vlan-1p-priority <i>number</i></code>	<p>(MX Series routers, M320 router, and EX Series switches only) Match on the IEEE 802.1p user priority bits in the customer VLAN tag (the inner tag in a dual-tag frame with 802.1Q VLAN tags). Specify a single value or multiple values from 0 through 7.</p> <p>Compare with the <code>learn-vlan-1p-priority</code> match condition.</p> <p>NOTE: This match condition supports the presence of a control word for MX Series routers and the M320 router.</p>
<code>user-vlan-1p-priority-except <i>number</i></code>	<p>(MX Series routers, M320 router, and EX Series switches only) Do not match on the IEEE 802.1p user priority bits. For details, see the <code>user-vlan-1p-priority</code> match condition.</p> <p>NOTE: This match condition supports the presence of a control word for MX Series routers and the M320 router.</p>
<code>user-vlan-id <i>number</i></code>	<p>(MX Series routers and EX Series switches only) Match the first VLAN identifier that is part of the payload.</p>
<code>user-vlan-id-except <i>number</i></code>	<p>(MX Series routers and EX Series switches only) Do not match on the first VLAN identifier that is part of the payload.</p>
<code>vlan-ether-type <i>value</i></code>	<p>VLAN Ethernet type field of a VPLS packet.</p>
<code>vlan-ether-type-except <i>value</i></code>	<p>Do not match on the VLAN Ethernet type field of a VPLS packet.</p>

Release History Table

Release	Description
14.2	Starting in Junos OS 14.2, flexible offset filters are supported in firewall hierarchy configurations.

14.2	Starting in Junos OS 14.2, firewall family bridge IPv6 match criteria is supported on MX Series and EX9200 switches.
------	--

RELATED DOCUMENTATION

Guidelines for Configuring Firewall Filters

Firewall Filter Terminating Actions

Firewall Filter Nonterminating Actions
--

Monitoring and Tracing VPLS

IN THIS CHAPTER

- [Configuring Port Mirroring for VPLS Traffic | 1259](#)
- [Configuring Y.1731 Functionality for VPLS to Support Delay and Delay Variation | 1259](#)
- [Tracing VPLS Traffic and Operations | 1261](#)

Configuring Port Mirroring for VPLS Traffic

You can configure port mirroring for VPLS traffic on the M7, M10i, M120, M320, and the MX Series routers. VPLS port mirroring is supported only M7i and M0i routers with the Enhanced Compact Forwarding Engine Board (CFEB-E). In addition, on M320 routers, VPLS port mirroring is supported only on Enhanced III Flexible PIC Concentrators (FPCs).

To configure port mirroring for VPLS include the `port-mirroring` statement at the `[edit forwarding-options]` hierarchy level. For more information about configuring port mirroring for VPLS for all platforms supported, see [Routing Policies, Firewall Filters, and Traffic Policers User Guide](#).

Configuring Y.1731 Functionality for VPLS to Support Delay and Delay Variation

For VPLS, you can configure the Ethernet frame delay measurement (ETH-DM) functionality to trigger two-way ETH-DM and allow concurrent ETH-DM CLI sessions from the same local maintenance association end point (MEP). The feature also provides the option to perform ETH-DM for a given 802.1q priority, to set the size of the data type, length, and value (TLV), to disable the `session-id-tlv` option, and to generate XML output.

This feature complements the ITU-T Y.1731 Ethernet service OAM feature. On-demand delay measurement for VPLS is supported on MX Series routers installed with Rev-B DPCs. Only the two-way delay measurement feature is supported for VPLS connections.

MX Series routers with modular port concentrators (MPCs) and 10-Gigabit Ethernet MPCs with SFP+ support ITU-T Y.1731 functionality on VPLS for frame-delay and delay-variation.

This feature is currently supported only for up MEPs. Set the MEP direction to up by configuring the up option for the direction statement at the [edit protocols oam ethernet connectivity-fault-management maintenance-domain *md-name* maintenance-association *ma-name* mep *mep-id*] hierarchy level.

This feature also provides support for an optional configuration where you can delegate the server-side processing (for two-way delay measurement) to the Packet Forwarding Engine (PFE) to prevent overloading on the Routing Engine. To enable this feature, include the delegate-server-processing statement at the [edit protocols oam ethernet connectivity-fault-management performance-monitoring] hierarchy level. By default, the server-side processing is done by the Routing Engine.

The following commands enable you to monitor and maintain the Y.1731 feature for VPLS:

- To display the delay measurement values across a VPLS connection, use the `monitor ethernet delay-measurement two-way (remote-mac-address | mep mep-id) maintenance-domain name maintenance-association name count count wait time priority 802.1p-value size no-session-id-tlv xml` command.
- The feature also provides support for enhanced continuity measurement by using an existing continuity check protocol. The continuity for every remote MEP is measured as the percentage of time that a remote MEP was operationally up over the total administratively enabled time.

To display the continuity measurement information, use the `show oam ethernet connectivity-fault-management mep-database maintenance-domain name maintenance-association name local-mep identifier remote-mep identifier` command.

- You can restart the continuity measurement by clearing the currently measured operational uptime and administrative enabled time. To clear the existing continuity measurement and restart counting the operational uptime, use the `clear oam ethernet connectivity-fault-management continuity-measurement maintenance-domain name maintenance-association name local-mep identifier remote-mep identifier` command.
- To clear the delay statistics, issue a `clear oam ethernet connectivity-fault-management statistics` command or a `clear oam ethernet connectivity-fault-management delay-statistics two-way maintenance-domain md-name maintenance-association ma-name` command.

RELATED DOCUMENTATION

[Ethernet Interfaces User Guide for Routing Devices](#)

[Configuring MEP Interfaces to Support Ethernet Frame Delay Measurements](#)

[Example: Configuring Two-Way Ethernet Frame Delay Measurements with Single-Tagged Interfaces](#)

Tracing VPLS Traffic and Operations

To trace VPLS traffic, include the `traceoptions` statement:

```
traceoptions {  
    file filename <files number> <size size> <world-readable | no-world-readable>;  
    flag flag <flag-modifier> <disable>;  
}
```

You can include this statement at the following hierarchy levels:

- [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls]
- [edit routing-instances *routing-instance-name* protocols vpls]

The following trace flags display the operations associated with VPLS:

- all—All VPLS tracing options
- connections—VPLS connections (events and state changes)
- error—Error conditions
- nlri—VPLS advertisements received or sent using BGP
- route—Trace-routing information
- topology—VPLS topology changes caused by reconsideration or advertisements received from other PE routers using BGP

8

PART

Connecting Layer 2 VPNs and Circuits to Other VPNs

[Connecting Layer 2 VPNs to Other VPNs | 1263](#)

[Connecting Layer 2 Circuits to Other VPNs | 1321](#)

Connecting Layer 2 VPNs to Other VPNs

IN THIS CHAPTER

- [Layer 2 VPN to Layer 2 VPN Connections | 1263](#)
- [Using the Layer 2 Interworking Interface to Interconnect a Layer 2 VPN to a Layer 2 VPN | 1264](#)
- [Example: Interconnecting a Layer 2 VPN with a Layer 2 VPN | 1266](#)
- [Interconnecting Layer 2 VPNs with Layer 3 VPNs Overview | 1288](#)
- [Example: Interconnecting a Layer 2 VPN with a Layer 3 VPN | 1290](#)

Layer 2 VPN to Layer 2 VPN Connections

As the need to link different Layer 2 services to one another for expanded service offerings grows, Layer 2 MPLS VPN services are increasingly in demand. Junos OS enables you to terminate Layer 2 VPN into Layer 2 VPN (also known as Layer 2 VPN stitching) using the Layer 2 interworking (iw0) interface.

Another way to do this is to use a Tunnel Services PIC to loop packets out and back from the Packet Forwarding Engine (PFE), to link together Layer 2 networks. The Layer 2 interworking software interface avoids the need for the Tunnel Services PIC and overcomes the limitation of bandwidth constraints imposed by the Tunnel Services PIC.

RELATED DOCUMENTATION

| [Example: Interconnecting a Layer 2 VPN with a Layer 2 VPN | 1266](#)

Using the Layer 2 Interworking Interface to Interconnect a Layer 2 VPN to a Layer 2 VPN

Instead of using a physical Tunnel PIC for looping the packet received from the Layer 2 VPN to another Layer 2 VPN, the Layer 2 Interworking interface uses Junos OS to stitch together both Layer 2 VPN routes.

To configure the interworking interface, include the `iw0` statement. The `iw0` statement is configured at the `[edit interfaces]` hierarchy level.

```
[edit interfaces]
iw0 {
  unit 0 {
    peer 1;
  }
  unit 1 {
    peer 0;
  }
}
```

NOTE: You must always create and delete (or deactivate) interworking (iw) interfaces in pairs, such as:

```
set interfaces iw0 unit 0 peer-unit 1
set interfaces iw0 unit 1 peer-unit 0
```

An error message displays if you delete or deactivate only one of the interworking interfaces. To successfully deactivate the interfaces and avoid any configuration errors, you must deactivate both.

The configuration of an interworking (iw) interface is similar to the configuration of a logical tunnel (lt) interface. In this example, the logical interfaces must be associated with the endpoints of both Layer 2 VPN connections terminating on this router. To make the association, include the `interfaces` statement and specify `iw0` as the interface name. Include the statement at the `[edit routing-instances routing-instances-name protocols l2vpn site site-name]` hierarchy level for each routing instance. The `routing-instances` statement is configured at the `[edit routing-instances]` hierarchy level.

```
[edit routing-instances]
L2VPN-PE1 {
```

```

instance-type l2vpn;
interface iw0.0;
route-distinguisher 65000:3;
vrf-target target:65000:2;
protocols {
    l2vpn {
        encapsulation-type ethernet;
        site CE3 {
            site-identifier 3;
            interface iw0.0 {
                remote-site-id 1;
            }
        }
    }
}
L2VPN-PE5 {
    instance-type l2vpn;
    interface iw0.1;
    route-distinguisher 65000:33;
    vrf-target target:65000:2;
    protocols {
        l2vpn {
            encapsulation-type ethernet;
            site CE3 {
                site-identifier 3;
                interface iw0.1 {
                    remote-site-id 5;
                }
            }
        }
    }
}

```

In addition to the `iw0` interface configuration, Layer 2 interworking `l2iw` protocols need to be configured. Without the `l2iw` configuration, the `l2iw` routes will not be formed, regardless of whether any `iw` interfaces are present. Only standard trace options can be configured within the `l2iw` protocol. The minimum configuration necessary for the feature to work is shown below:

```

[edit]
protocols {

```

```
l2iw;  
}
```

RELATED DOCUMENTATION

[Layer 2 VPN Applications | 145](#)

[Example: Interconnecting a Layer 2 VPN with a Layer 2 VPN | 1266](#)

Example: Interconnecting a Layer 2 VPN with a Layer 2 VPN

IN THIS SECTION

- [Requirements | 1266](#)
- [Overview and Topology | 1267](#)
- [Configuration | 1268](#)

This example provides a step-by-step procedure for interconnecting and verifying a Layer 2 VPN with a Layer 2 VPN. It contains the following sections:

Requirements

This example uses the following hardware and software components:

- Junos OS Release 9.3 or later
- 2 MX Series 5G Universal Routing Platforms
- 2 M Series Multiservice Edge Routers
- 1 T Series Core Routers
- 1 EX Series Ethernet Switches

Overview and Topology


IN THIS SECTION

Topology | 1267

Topology

The physical topology of the Layer 2 VPN to Layer 2 VPN connection example is shown in [Figure 83 on page 1267](#).


Figure 83: Physical Topology of a Layer 2 VPN to Layer 2 VPN Connection



g040540

The logical topology of a Layer 2 VPN to Layer 2 VPN connection is shown in [Figure 84 on page 1268](#).

Figure 84: Logical Topology of a Layer 2 VPN to Layer 2 VPN Connection



Configuration

IN THIS SECTION

- [Configuring Protocols on the PE and P Routers | 1269](#)
- [Verifying the Layer 2 VPN to Layer 2 VPN Connection on Router PE3 | 1275](#)
- [Verifying the Layer 2 VPN to Layer 2 VPN Connection on Router PE3 | 1279](#)
- [Results | 1282](#)

NOTE: In any configuration session, it is good practice to verify periodically that the configuration can be committed using the `commit check` command.

In this example, the router being configured is identified using the following command prompts:

- CE1 identifies the customer edge 1 (CE1) router
- PE1 identifies the provider edge 1 (PE1) router
- CE3 identifies the customer edge 3 (CE3) router
- PE3 identifies the provider edge 3 (PE3) router
- CE5 identifies the customer edge 5 (CE5) router
- PE5 identifies the provider edge 5 (PE5) router

This example is organized in the following sections:

Configuring Protocols on the PE and P Routers

Step-by-Step Procedure

All of the PE routers and P routers are configured with OSPF as the IGP protocol. The MPLS, LDP, and BGP protocols are enabled on all of the interfaces except `fxp0.0`. Core-facing interfaces are enabled with the MPLS address and inet address.

1. Configure all the PE and P routers with OSPF as the IGP. Enable the MPLS, LDP, and BGP protocols on all interfaces except `fxp0.0`. The following configuration snippet shows the protocol configuration for Router PE1:

```
[edit]
protocols {
  mpls {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  bgp {
    group RR {
      type internal;
      local-address 192.0.2.1;
      family l2vpn {
        signaling;
      }
      neighbor 192.0.2.7;
    }
  }
}
```



```

ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}

```

2. Configure the PE and P routers with OSPF as the IGP. Enable the MPLS, LDP, and BGP protocols on all interfaces except fxp0. The following configuration snippet shows the protocol configuration for Router PE3:

```

[edit]
protocols {
    mpls {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    bgp {
        group RR {
            type internal;
            local-address 192.0.2.3;
            family l2vpn {
                signaling;
            }
            neighbor 192.0.2.7;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {

```

```

        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}

```

Step-by-Step Procedure

Configuring the Layer 2 VPN Protocol and Interfaces

1. On Router PE1, configure the ge-1/0/0 interface encapsulation. To configure the interface encapsulation, include the encapsulation statement and specify the ethernet-ccc option (vlan-ccc encapsulation is also supported). Configure the ge-1/0/0.0 logical interface family for circuit cross-connect functionality. To configure the logical interface family, include the family statement and specify the ccc option. The encapsulation should be configured the same way for all routers in the Layer 2 VPN domain.

```

[edit interfaces]
ge-1/0/0 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}

lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}

```

2. On Router PE1, configure the Layer 2 VPN protocols. Configure the remote site ID as 3. Site ID 3 represents Router PE3 (Hub-PE). To configure the Layer 2 VPN protocols, include the `l2vpn` statement at the `[edit routing-instances routing-instances-name protocols]` hierarchy level. Layer 2 VPNs use BGP as the signaling protocol.

```
[edit routing-instances]
L2VPN {
  instance-type l2vpn;
  interface ge-1/0/0.0;
  route-distinguisher 65000:1;
  vrf-target target:65000:2;
  protocols {
    l2vpn {
      encapsulation-type ethernet;
      site CE1 {
        site-identifier 1;
        interface ge-1/0/0.0 {
          remote-site-id 3;
        }
      }
    }
  }
}
```

3. On Router PE5, configure the `ge-2/0/0` interface encapsulation by including the `encapsulation` statement and specify the `ethernet-ccc` option. Configure the `ge-1/0/0.0` logical interface family for circuit cross-connect functionality by including the `family` statement and specifying the `ccc` option.

```
[edit interfaces]
ge-2/0/0 {
  encapsulation ethernet-ccc;
  unit 0 {
    family ccc;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.5/24;
    }
  }
}
```

```

    }
}

```

4. On Router PE5, configure the Layer 2 VPN protocols by including the `l2vpn` statement at the `[edit routing-instances routing-instances-name protocols]` hierarchy level. Configure the remote site ID as 3.

```

[edit routing-instances]
L2VPN {
    instance-type l2vpn;
    interface ge-2/0/0.0;
    route-distinguisher 65000:5;
    vrf-target target:65000:2;
    protocols {
        l2vpn {
            encapsulation-type ethernet;
            site CE5 {
                site-identifier 5;
                interface ge-2/0/0.0 {
                    remote-site-id 3;
                }
            }
        }
    }
}

```

5. On Router PE3, configure the `iw0` interface with two logical interfaces. To configure the `iw0` interface, include the `interfaces` statement and specify `iw0` as the interface name. For the unit 0 logical interface, include the `peer-unit` statement and specify the logical interface unit 1 as the peer interface. For the unit 1 logical interface, include the `peer-unit` statement and specify the logical interface unit 0 as the peer interface.

```

[edit interfaces]
iw0 {
    unit 0 {
        encapsulation ethernet-ccc;
        peer-unit 1;
    }
    unit 1 {
        encapsulation ethernet-ccc;
        peer-unit 0;
    }
}

```

```

    }
}

```

6. On Router PE3, configure the edge-facing ge-1/0/1 interface encapsulation by including the encapsulation statement and specifying the ethernet-ccc option.

```

[edit interfaces]
ge-1/0/1 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}

```

7. On Router PE3, configure the logical loopback interface. The loopback interface is used to establish the targeted LDP sessions to Routers PE1 and Router PE5.

```

[edit interfaces]
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}

```

8. On Router PE3, enable the Layer 2 interworking protocol. To enable the Layer 2 interworking protocol, include the l2iw statement at the [edit protocols] hierarchy level.

```

[edit protocols]
l2iw;

```

9. On Router PE3, configure two Layer 2 VPN routing instances to terminate the Layer 2 VPN virtual circuits from Router PE1 and Router PE5, as shown.

```

[edit routing-instances]
L2VPN-PE1 {
    instance-type l2vpn;
    interface iw0.0;
}

```

```

route-distinguisher 65000:3;
vrf-target target:65000:2;
protocols {
    l2vpn {
        encapsulation-type ethernet;
        site CE3 {
            site-identifier 3;
            interface iw0.0 {
                remote-site-id 1;
            }
        }
    }
}
L2VPN-PE5 {
    instance-type l2vpn;
    interface iw0.1;
    route-distinguisher 65000:33;
    vrf-target target:65000:2;
    protocols {
        l2vpn {
            encapsulation-type ethernet;
            site CE3 {
                site-identifier 3;
                interface iw0.1 {
                    remote-site-id 5;
                }
            }
        }
    }
}

```

Verifying the Layer 2 VPN to Layer 2 VPN Connection on Router PE3

Step-by-Step Procedure

1. BGP is used for control plane signaling in a Layer 2 VPN. On Router PE1, use the `show bgp` command to verify that the BGP control plane for the Layer 2 VPN, has established a neighbor relationship with the route reflector that has IP address 192.0.2.7.

Three Layer 2 VPN routes are received from the route reflector for each PE router in the topology.

```

user@PE1> show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Table          Tot Paths  Act Paths Suppressed  History Damp State  Pending
bgp.l2vpn.0      3          3          0          0          0          0
Peer            AS      InPkt    OutPkt    OutQ    Flaps Last Up/Dwn State|#Active/
Received/Accepted/Damped...
192.0.2.7        65000      190      192        0        0      1:24:40 Establ
  bgp.l2vpn.0: 3/3/3/0
  L2VPN.l2vpn.0: 3/3/3/0

```

2. On Router PE1, use the `show route` command to verify that the BGP Layer 2 VPN routes are stored in the `L2VPN.l2vpn.0` routing table for each PE router.

```

user@PE1> show route table L2VPN.l2vpn.0
L2VPN.l2vpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both
65000:1:1:3/96
      *[L2VPN/170/-101] 01:31:53, metric2 1
      Indirect
65000:3:3:1/96
      *[BGP/170] 01:24:58, localpref 100, from 192.0.2.7
      AS path: I
      > to 10.10.1.2 via xe-0/3/0.0
65000:5:5:3/96
      *[BGP/170] 01:24:58, localpref 100, from 192.0.2.7
      AS path: I
      > to 10.10.3.2 via xe-0/2/0.0
65000:33:3:5/96
      *[BGP/170] 01:24:58, localpref 100, from 192.0.2.7
      AS path: I
      > to 10.10.1.2 via xe-0/3/0.0

```

3. On Router PE1, use the `show ldp session` command to verify that targeted LDP sessions are established to the PE routers in the network and that the state is `Operational`.

```

user@PE1> show ldp session
Address          State          Connection      Hold time

```

192.0.2.2	Operational	Open	24
192.0.2.3	Operational	Open	22
192.0.2.5	Operational	Open	28

4. On Router PE1, use the `show l2vpn connections` command to verify that the Layer 2 VPN to site 3 on Router PE3 (Hub-PE) is Up.

```
user@PE1> show l2vpn connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure
RD -- remote site signaled down	SC -- local and remote site ID collision
LN -- local site not designated	LM -- local site ID not minimum designated
RN -- remote site not designated	RM -- remote site ID not minimum designated
XX -- unknown connection status	IL -- no incoming label
MM -- MTU mismatch	MI -- Mesh-Group ID not available
BK -- Backup connection	ST -- Standby connection
PF -- Profile parse failure	PB -- Profile busy

Legend for interface status

Up -- operational
Dn -- down

Instance: L2VPN

Local site: CE1 (1)

connection-site	Type	St	Time last up	# Up trans
3	rmt	Up	Jan 5 18:08:25 2010	1
Remote PE: 192.0.2.3, Negotiated control-word: Yes (Null)				
Incoming label: 800000, Outgoing label: 800000				
Local interface: ge-1/0/0.0, Status: Up, Encapsulation: ETHERNET				
5	rmt	OR		

5. On Router PE1, use the `show route` command to verify that the `mpls.0` routing table is populated with the Layer 2 VPN routes used to forward the traffic using an LDP label. Notice that in this example, the router is pushing label `8000000`.

```

user@PE1> show route table mpls.0
[edit]
mpls.0: 13 destinations, 13 routes (13 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0                *[MPLS/0] 1w1d 11:36:44, metric 1
                  Receive
1                *[MPLS/0] 1w1d 11:36:44, metric 1
                  Receive
2                *[MPLS/0] 1w1d 11:36:44, metric 1
                  Receive
300432            *[LDP/9] 3d 04:25:02, metric 1
                  > to 10.10.2.2 via xe-0/1/0.0, Pop
300432(S=0)       *[LDP/9] 3d 04:25:02, metric 1
                  > to 10.10.2.2 via xe-0/1/0.0, Pop
300768            *[LDP/9] 3d 04:25:02, metric 1
                  > to 10.10.3.2 via xe-0/2/0.0, Pop
300768(S=0)       *[LDP/9] 3d 04:25:02, metric 1
                  > to 10.10.3.2 via xe-0/2/0.0, Pop
300912            *[LDP/9] 3d 04:25:02, metric 1
                  > to 10.10.3.2 via xe-0/2/0.0, Swap 299856
301264            *[LDP/9] 3d 04:24:58, metric 1
                  > to 10.10.1.2 via xe-0/3/0.0, Swap 308224
301312            *[LDP/9] 3d 04:25:01, metric 1
                  > to 10.10.1.2 via xe-0/3/0.0, Pop
301312(S=0)       *[LDP/9] 3d 04:25:01, metric 1
                  > to 10.10.1.2 via xe-0/3/0.0, Pop
800000            *[L2VPN/7] 01:25:28
                  > via ge-1/0/0.0, Pop      Offset: 4
ge-1/0/0.0        *[L2VPN/7] 01:25:28, metric2 1
                  > to 10.10.1.2 via xe-0/3/0.0, Push 800000 Offset: -4

```

Verifying the Layer 2 VPN to Layer 2 VPN Connection on Router PE3

Step-by-Step Procedure

1. On Router PE3, use the `show l2vpn connections` command to verify that the Layer 2 VPN connections from Router PE1 and Router PE5 are Up and are using the `iw0` interface.

```
user@PE3> show l2vpn connections
Instance: L2VPN-PE1
  Local site: CE3 (3)
    connection-site      Type  St    Time last up      # Up trans
    1                    rmt   Up    Jan  5 18:08:22 2010      1
      Remote PE: 192.0.2.1, Negotiated control-word: Yes (Null)
      Incoming label: 800000, Outgoing label: 800000
      Local interface: iw0.0, Status: Up, Encapsulation: ETHERNET
    5                    rmt   OR
      Remote PE: 192.0.2.1, Negotiated control-word: Yes (Null)
      Incoming label: 800000, Outgoing label: 800000
      Local interface: iw0.0, Status: Up, Encapsulation: ETHERNET

Instance: L2VPN-PE5
  Local site: CE3 (3)
    connection-site      Type  St    Time last up      # Up trans
    1                    rmt   CN
    5                    rmt   Up    Jan  5 18:08:22 2010      1
      Remote PE: 192.0.2.5, Negotiated control-word: Yes (Null)
      Incoming label: 800002, Outgoing label: 800000
      Local interface: iw0.1, Status: Up, Encapsulation: ETHERNET
```

2. On Router PE3, use the `show ldp neighbor` command to verify that the targeted LDP session neighbor IP addresses are shown.

```
user@PE3> show ldp neighbor
Address      Interface      Label space ID      Hold time
192.0.2.1    lo0.0          192.0.2.1:0         44
192.0.2.2    lo0.0          192.0.2.2:0         42
192.0.2.4    lo0.0          192.0.2.4:0         31
192.0.2.5    lo0.0          192.0.2.5:0         44
```

3. On Router PE3, use the `show bgp summary` command to verify that the BGP control plane for the Layer 2 VPN, has established a neighbor relationship with the route reflector that has IP address 192.0.2.7.

```
user@PE3> show bgp summary
Groups: 1 Peers: 1 Down peers: 0
Table          Tot Paths  Act Paths Suppressed    History Damp State   Pending
bgp.l2vpn.0      2          2          0          0          0          0
Peer            AS        InPkt    OutPkt    OutQ    Flaps Last Up/Dwn State|#Active/
Received/Accepted/Damped...
192.0.2.7        65000     10092    10195      0        0 3d 4:23:27 Establ
  bgp.l2vpn.0: 2/2/2/0
  L2VPN-PE1.l2vpn.0: 2/2/2/0
  L2VPN-PE5.l2vpn.0: 2/2/2/0
```

4. On Router PE3, use the `show ldp session` command to verify that targeted LDP sessions are established to all of the PE routers in the network and that the state is Operational.

```
user@PE3> show ldp session
Address          State          Connection      Hold time
192.0.2.1        Operational    Open            24
192.0.2.2        Operational    Open            22
192.0.2.4        Operational    Open            20
192.0.2.5        Operational    Open            24
```

5. On Router PE3, use the `show route table mpls.0` command to verify that the `mpls.0` routing table is populated with the Layer 2 VPN routes used to forward the traffic using an LDP label. Notice that in this example, the router is swapping label 800000. Also notice the two `iw0` interfaces that are used for the Layer 2 interworking routes.

```
user@PE3>show route table mpls.0
mpls.0: 16 destinations, 18 routes (16 active, 2 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w1d 11:50:14, metric 1
           Receive
1          *[MPLS/0] 1w1d 11:50:14, metric 1
           Receive
2          *[MPLS/0] 1w1d 11:50:14, metric 1
           Receive
308160     *[LDP/9] 3d 04:38:45, metric 1
```

```

> to 10.10.1.1 via xe-0/3/0.0, Pop
308160(S=0) * [LDP/9] 3d 04:38:45, metric 1
> to 10.10.1.1 via xe-0/3/0.0, Pop
308176 * [LDP/9] 3d 04:38:44, metric 1
> to 10.10.6.2 via xe-0/1/0.0, Pop
308176(S=0) * [LDP/9] 3d 04:38:44, metric 1
> to 10.10.6.2 via xe-0/1/0.0, Pop
308192 * [LDP/9] 00:07:18, metric 1
> to 10.10.20.1 via xe-0/0/0.0, Swap 601649
to 10.10.6.2 via xe-0/1/0.0, Swap 299856
308208 * [LDP/9] 3d 04:38:44, metric 1
> to 10.10.5.1 via xe-0/2/0.0, Pop
308208(S=0) * [LDP/9] 3d 04:38:44, metric 1
> to 10.10.5.1 via xe-0/2/0.0, Pop
308224 * [LDP/9] 3d 04:38:42, metric 1
> to 10.10.20.1 via xe-0/0/0.0, Pop
308224(S=0) * [LDP/9] 3d 04:38:42, metric 1
> to 10.10.20.1 via xe-0/0/0.0, Pop
800000 * [L2IW/6] 01:39:13, metric2 1
> to 10.10.6.2 via xe-0/1/0.0, Swap 800000
[L2VPN/7] 01:39:13
> via iw0.0, Pop Offset: 4
800002 * [L2IW/6] 01:39:13, metric2 1
> to 10.10.1.1 via xe-0/3/0.0, Swap 800000
[L2VPN/7] 01:39:13
> via iw0.1, Pop Offset: 4
iw0.0 * [L2VPN/7] 01:39:13, metric2 1
> to 10.10.1.1 via xe-0/3/0.0, Push 800000 Offset: -4
iw0.1 * [L2VPN/7] 01:39:13, metric2 1
> to 10.10.6.2 via xe-0/1/0.0, Push 800000 Offset: -4

```

Step-by-Step Procedure

Testing Layer 2 VPN to Layer 2 VPN Connectivity (CE1 to CE5)

1. On Router CE1, use the ping command to test connectivity to Router CE5. Notice that the response time is in milliseconds, confirming that the ping response is returned.

```

user@CE1>ping 198.51.100.11
PING 198.51.100.11 (198.51.100.11): 56 data bytes
64 bytes from 198.51.100.11: icmp_seq=1 ttl=64 time=22.425 ms
64 bytes from 198.51.100.11: icmp_seq=2 ttl=64 time=1.299 ms

```

```
64 bytes from 198.51.100.11: icmp_seq=3 ttl=64 time=1.032 ms
64 bytes from 198.51.100.11: icmp_seq=4 ttl=64 time=1.029 ms
```

2. On Router CE5, use the ping command to test connectivity to Router CE1. Notice that the response time is in milliseconds, confirming that the ping response is returned.

```
user@CE5>ping 198.51.100.1
PING 198.51.100.1 (198.51.100.1): 56 data bytes
64 bytes from 198.51.100.1: icmp_seq=0 ttl=64 time=1.077 ms
64 bytes from 198.51.100.1: icmp_seq=1 ttl=64 time=0.957 ms
64 bytes from 198.51.100.1: icmp_seq=2 ttl=64 time=1.057 ms 1.017 ms
```

Results

The configuration and verification of this example have been completed. The following section is for your reference.

The relevant sample configuration for Router PE1 follows.

Router PE1

```
chassis {
  dump-on-panic;
  fpc 1 {
    pic 3 {
      tunnel-services {
        bandwidth 1g;
      }
    }
  }
  network-services ethernet;
}

interfaces {
  xe-0/1/0 {
    unit 0 {
      family inet {
        address 10.10.2.1/30;
      }
      family mpls;
    }
  }
}
```

```

xe-0/2/0 {
    unit 0 {
        family inet {
            address 10.10.3.1/30;
        }
        family mpls;
    }
}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.1/30;
        }
        family mpls;
    }
}
ge-1/0/0 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}
}
routing-options {
    static {
        route 172.16.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    mpls {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

```

```

bgp {
    group RR {
        type internal;
        local-address 192.0.2.1;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}

ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

}

routing-instances {
    L2VPN {
        instance-type l2vpn;
        interface ge-1/0/0.0;
        route-distinguisher 65000:1;
        vrf-target target:65000:2;
        protocols {
            l2vpn {
                encapsulation-type ethernet;
                site CE1 {
                    site-identifier 1;
                    interface ge-1/0/0.0 {
                        remote-site-id 3;
                    }
                }
            }
        }
    }
}

```

```

    }
}

```

The relevant sample configuration for Router PE3 follows.

Router PE3

```

chassis {
    dump-on-panic;
    fpc 1 {
        pic 3 {
            tunnel-services {
                bandwidth 1g;
            }
        }
    }
    network-services ethernet;
}
interfaces {
    xe-0/0/0 {
        unit 0 {
            family inet {
                address 10.10.20.2/30;
            }
            family mpls;
        }
    }
    xe-0/1/0 {
        unit 0 {
            family inet {
                address 10.10.6.1/30;
            }
            family mpls;
        }
    }
    xe-0/2/0 {
        unit 0 {
            family inet {
                address 10.10.5.2/30;
            }
            family mpls;
        }
    }
}

```



```

}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.2/30;
        }
        family mpls;
    }
}
ge-1/0/1 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}
iw0 {
    unit 0 {
        encapsulation ethernet-ccc;
        peer-unit 1;
    }
    unit 1 {
        encapsulation ethernet-ccc;
        peer-unit 0;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}
}
routing-options {
    static {
        route 172.16.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    l2iw;
    mpls {
        interface all;
    }
}

```

```

        interface fxp0.0 {
            disable;
        }
    }
    bgp {
        group RR {
            type internal;
            local-address 192.0.2.3;
            family l2vpn {
                signaling;
            }
            neighbor 192.0.2.7;
        }
    }
    ospf {
        area 0.0.0.0 {
            interface all;
            interface fxp0.0 {
                disable;
            }
        }
    }
    ldp {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

routing-instances {
    L2VPN-PE1 {
        instance-type l2vpn;
        interface iw0.0;
        route-distinguisher 65000:3;
        vrf-target target:65000:2;
        protocols {
            l2vpn {
                encapsulation-type ethernet;
                site CE3 {
                    site-identifier 3;
                    interface iw0.0 {
                        remote-site-id 1;
                    }
                }
            }
        }
    }
}

```

```

    }
  }
}
L2VPN-PE5 {
  instance-type l2vpn;
  interface iw0.1;
  route-distinguisher 65000:33;
  vrf-target target:65000:2;
  protocols {
    l2vpn {
      encapsulation-type ethernet;
      site CE3 {
        site-identifier 3;
        interface iw0.1 {
          remote-site-id 5;
        }
      }
    }
  }
}
}

```

RELATED DOCUMENTATION

[Understanding Layer 2 VPNs | 143](#)

[Layer 2 VPN Applications | 145](#)

[Using the Layer 2 Interworking Interface to Interconnect a Layer 2 VPN to a Layer 2 VPN | 1264](#)

Interconnecting Layer 2 VPNs with Layer 3 VPNs Overview

IN THIS SECTION

- [Interconnecting Layer 2 VPNs with Layer 3 VPNs Applications | 1289](#)

As MPLS-based Layer 2 services grow in demand, new challenges arise for service providers to be able to interoperate with Layer 2 and Layer 3 services and give their customers value-added services. Junos OS has various features to address the needs of service providers. One of these features is the use of a logical tunnel interface. This Junos OS functionality makes use of a tunnel PIC to loop packets out and back from the Packet Forwarding Engine to link the Layer 2 network with the Layer 3 network. The solution is limited by the logical tunnel bandwidth constraints imposed by the tunnel PIC.

Interconnecting Layer 2 VPNs with Layer 3 VPNs Applications

Interconnecting a Layer 2 VPN with a Layer 3 VPN provides the following benefits:

- A single access line to provide multiple services—Traditional VPNs over Layer 2 circuits require the provisioning and maintenance of separate networks for IP and for VPN services. In contrast, Layer 2 VPNs enable the sharing of a provider's core network infrastructure between IP and Layer 2 VPN services, thereby reducing the cost of providing those services.
- Flexibility—Many different types of networks can be accommodated by the service provider. If all sites in a VPN are owned by the same enterprise, this is an intranet. If various sites are owned by different enterprises, the VPN is an extranet. A site can be located in more than one VPN.
- Wide range of possible policies—You can give every site in a VPN a different route to every other site, or you can force traffic between certain pairs of sites routed via a third site and so pass certain traffic through a firewall.
- Scalable network—This design enhances the scalability because it eliminates the need for provider edge (PE) routers to maintain all of the service provider's VPN routes. Each PE router maintains a VRF table for each of its directly connected sites. Each customer connection (such as a Frame Relay PVC, an ATM PVC, or a VLAN) is mapped to a specific VRF table. Thus, it is a port on the PE router and not a site that is associated with a VRF table. Multiple ports on a PE router can be associated with a single VRF table. It is the ability of PE routers to maintain multiple forwarding tables that supports the per-VPN segregation of routing information.
- Use of route reflectors—Provider edge routers can maintain IBGP sessions to route reflectors as an alternative to a full mesh of IBGP sessions. Deploying multiple route reflectors enhances the scalability of the RFC 2547bis model because it eliminates the need for any single network component to maintain all VPN routes.
- Multiple VPNs are kept separate and distinct from each other—The customer edge routers do not peer with each other. Two sites have IP connectivity over the common backbone only, and only if there is a VPN which contains both sites. This feature keeps the VPNs separate and distinct from each other, even if two VPNs have an overlapping address space.
- Simple for customers to use—Customers can obtain IP backbone services from a service provider, and they do not need to maintain their own backbones.

Example: Interconnecting a Layer 2 VPN with a Layer 3 VPN

IN THIS SECTION

- [Requirements | 1290](#)
- [Overview and Topology | 1290](#)
- [Configuration | 1294](#)
- [Verification | 1314](#)

This example provides a step-by-step procedure and commands for interconnecting and verifying a Layer 2 VPN with a Layer 3 VPN. It contains the following sections:

Requirements

This example uses the following hardware and software components:

- Junos OS Release 9.3 or later
- Five MX Series routers
- Three M Series routers
- Two T Series routers

Overview and Topology

IN THIS SECTION

- [Topology | 1292](#)

A Layer 2 VPN is a type of virtual private network (VPN) that uses MPLS labels to transport data. The communication occurs between the provider edge (PE) routers.

Layer 2 VPNs use BGP as the signaling protocol and, consequently, have a simpler design and require less provisioning overhead than traditional VPNs over Layer 2 circuits. BGP signaling also enables autodiscovery of Layer 2 VPN peers. Layer 2 VPNs can have either a full-mesh or a hub-and-spoke

topology. The tunneling mechanism in the core network is, typically, MPLS. However, Layer 2 VPNs can also use other tunneling protocols, such as GRE.

Layer 3 VPNs are based on RFC 2547bis, *BGP/MPLS IP VPNs*. RFC 2547bis defines a mechanism by which service providers can use their IP backbones to provide VPN services to their customers. A Layer 3 VPN is a set of sites that share common routing information and whose connectivity is controlled by a collection of policies. The sites that make up a Layer 3 VPN are connected over a provider's existing public Internet backbone. RFC 2547bis VPNs are also known as BGP/MPLS VPNs because BGP is used to distribute VPN routing information across the provider's backbone, and MPLS is used to forward VPN traffic across the backbone to remote VPN sites.

Customer networks, because they are private, can use either public addresses or private addresses, as defined in RFC 1918, *Address Allocation for Private Internets*. When customer networks that use private addresses connect to the public Internet infrastructure, the private addresses might overlap with the same private addresses used by other network users. MPLS/BGP VPNs solve this problem by adding a *route distinguisher*. A route distinguisher is a VPN identifier prefix that is added to each address from a particular VPN site, thereby creating an address that is unique both within the VPN and within the Internet.

In addition, each VPN has its own VPN-specific routing table that contains the routing information for that VPN only. To separate a VPN's routes from routes in the public Internet or those in other VPNs, the PE router creates a separate routing table for each VPN called a VPN routing and forwarding (VRF) table. The PE router creates one VRF table for each VPN that has a connection to a customer edge (CE) router. Any customer or site that belongs to the VPN can access only the routes in the VRF tables for that VPN. Every VRF table has one or more extended community attributes associated with it that identify the route as belonging to a specific collection of routers. One of these, the *route target* attribute, identifies a collection of sites (VRF tables) to which a PE router distributes routes. The PE router uses the route target to constrain the import of remote routes into its VRF tables.

When an ingress PE router receives routes advertised from a directly connected CE router, it checks the received route against the VRF export policy for that VPN.

- If it matches, the route is converted to VPN-IPv4 format—that is, the route distinguisher is added to the route. The PE router then announces the route in VPN-IPv4 format to the remote PE routers. It also attaches a route target to each route learned from the directly connected sites. The route target attached to the route is based on the value of the VRF table's configured export target policy. The routes are then distributed using IBGP sessions, which are configured in the provider's core network.
- If the route from the CE router does not match, it is not exported to other PE routers, but it can still be used locally for routing, for example, if two CE routers in the same VPN are directly connected to the same PE router.


When an egress PE router receives a route, it checks it against the import policy on the IBGP session between the PE routers. If it is accepted, the router places the route into its `bgp.l3vpn.0` table. At the same time, the router checks the route against the VRF import policy for the VPN. If it matches, the

route distinguisher is removed from the route and the route is placed into the VRF table (the *routing-instance-name.inet.0* table) in IPv4 format.

Topology


Figure 85 on page 1292 shows the physical topology of a Layer 2 VPN-to-Layer 3 VPN interconnection.

Figure 85: Physical Topology of a Layer 2 VPN Terminating into a Layer 3 VPN



The logical topology of a Layer 2 VPN-to-Layer 3 VPN interconnection is shown in [Figure 86 on page 1293](#).

Figure 86: Logical Topology of a Layer 2 VPN Terminating into a Layer 3 VPN



The following definitions describe the meaning of the device abbreviations used in [Figure 85 on page 1292](#) and [Figure 86 on page 1293](#).

- Customer edge (CE) device—A device at the customer premises that provides access to the service provider's VPN over a data link to one or more provider edge (PE) routers.

Typically the CE device is an IP router that establishes an adjacency with its directly connected PE routers. After the adjacency is established, the CE router advertises the site's local VPN routes to the PE router and learns remote VPN routes from the PE router.

- Provider edge (PE) device—A device, or set of devices, at the edge of the provider network that presents the provider's view of the customer site.

PE routers exchange routing information with CE routers. PE routers are aware of the VPNs that connect through them, and PE routers maintain VPN state. A PE router is only required to maintain VPN routes for those VPNs to which it is directly attached. After learning local VPN routes from CE routers, a PE router exchanges VPN routing information with other PE routers using IBGP. Finally, when using MPLS to forward VPN data traffic across the provider's backbone, the ingress PE router

functions as the ingress label-switching router (LSR) and the egress PE router functions as the egress LSR.

- **Provider (P) device**—A device that operates inside the provider's core network and does not directly interface to any CE.

Although the P device is a key part of implementing VPNs for the service provider's customers and may provide routing for many provider-operated tunnels that belong to different VPNs, it is not itself VPN-aware and does not maintain VPN state. Its principal role is allowing the service provider to scale its VPN offerings, for example, by acting as an aggregation point for multiple PE routers.

P routers function as MPLS transit LSRs when forwarding VPN data traffic between PE routers. P routers are required only to maintain routes to the provider's PE routers; they are not required to maintain specific VPN routing information for each customer site.

Configuration

IN THIS SECTION

- [Configuring the Base Protocols and Interfaces | 1294](#)
- [Configuring the VPN Interfaces | 1298](#)

To interconnect a Layer 2 VPN with a Layer 3 VPN, perform these tasks:

Configuring the Base Protocols and Interfaces

Step-by-Step Procedure

1. On each PE and P router, configure OSPF with traffic engineering extensions on all interfaces. Disable OSPF on the fxp0.0 interface.

```
[edit protocols]
ospf {
  traffic-engineering;
  area 0.0.0.0 {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
}
```

```
    }
}
```

2. On all the core routers, enable MPLS on all interfaces. Disable MPLS on the fxp0.0 interface.

```
[edit protocols]
mpls {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
```

3. On all the core routers, create an internal BGP peer group and specify the route reflector address (192.0.2.7) as the neighbor. Also enable BGP to carry Layer 2 VPLS network layer reachability information (NLRI) messages for this peer group by including the `signaling` statement at the `[edit protocols bgp group group-name family l2vpn]` hierarchy level.

```
[edit protocols]
bgp {
    group RR {
        type internal;
        local-address 192.0.2.2;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}
```

4. On Router PE3, create an internal BGP peer group and specify the route reflector IP address (192.0.2.7) as the neighbor. Enable BGP to carry Layer 2 VPLS NLRI messages for this peer group and enable the processing of VPN-IPv4 addresses by including the `unicast` statement at the `[edit protocols bgp group group-name family inet-vpn]` hierarchy level.

```
[edit protocols]
bgp {
    group RR {
        type internal;
        local-address 192.0.2.3;
```

```

        family inet-vpn {
            unicast;
        }
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}

```

5. For the Layer 3 VPN domain on Router PE3 and Router PE5, enable RSVP on all interfaces. Disable RSVP on the fxp0.0 interface.

```

[edit protocols]
rsvp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

```

6. On Router PE3 and Router PE5, create label-switched paths (LSPs) to the route reflector and the other PE routers. The following example shows the configuration on Router PE5.

```

[edit protocols]
mpls {
    label-switched-path to-RR {
        to 192.0.2.7;
    }
    label-switched-path to-PE2 {
        to 192.0.2.2;
    }
    label-switched-path to-PE3 {
        to 192.0.2.3;
    }
    label-switched-path to-PE4 {
        to 192.0.2.4;
    }
    label-switched-path to-PE1 {
        to 192.0.2.1;
    }
}

```

```

    }
}

```

7. On Routers PE1, PE2, PE3, and PE5, configure the core interfaces with an IPv4 address and enable the MPLS address family. The following example shows the configuration of the xe-0/1/0 interface on Router PE2.

```

[edit]
interfaces {
  xe-0/1/0 {
    unit 0 {
      family inet {
        address 10.10.2.2/30;
      }
      family mpls;
    }
  }
}

```

8. On Router PE2 and Router PE3, configure LDP for the Layer 2 VPN MPLS signaling protocol for all interfaces. Disable LDP on the fxp0.0 interface. (RSVP can also be used.)

```

[edit protocols]
ldp {
  interface all;
  interface fxp0.0 {
    disable;
  }
}

```

9. On the route reflector, create an internal BGP peer group and specify the PE routers IP addresses as the neighbors.

```

[edit]
protocols {
  bgp {
    group RR {
      type internal;
      local-address 192.0.2.7;
      family inet {

```

```

        unicast;
    }
    family inet-vpn {
        unicast;
    }
    family l2vpn {
        signaling;
    }
    cluster 192.0.2.7;
    neighbor 192.0.2.1;
    neighbor 192.0.2.2;
    neighbor 192.0.2.4;
    neighbor 192.0.2.5;
    neighbor 192.0.2.3;
}
}
}

```

10. On the route reflector, configure MPLS LSPs towards Routers PE3 and PE5 to resolve the BGP next hops from inet.3 routing table.

```

[edit]
protocols {
    mpls {
        label-switched-path to-pe3 {
            to 192.0.2.3;
        }

        label-switched-path to-pe5 {
            to 192.0.2.5;
        }
        interface all;
    }
}

```

Configuring the VPN Interfaces

Step-by-Step Procedure

Router PE2 is one end of the Layer 2 VPN. Router PE3 is performing the Layer 2 VPN stitching between the Layer 2 VPN and the Layer 3 VPN. Router PE3 uses the logical tunnel interface (lt interface)

configured with different logical interface units applied under two different Layer 2 VPN instances. The packet is looped though the It interface configured on Router PE3. The configuration of Router PE5 contains the PE-CE interface.

1. On Router PE2, configure the ge-1/0/2 interface encapsulation. Include the encapsulation statement and specify the ethernet-ccc option (vlan-ccc encapsulation is also supported) at the [edit interfaces ge-1/0/2] hierarchy level. The encapsulation should be the same in a whole Layer 2 VPN domain (Routers PE2 and PE3). Also, configure interface lo0.

```
[edit]
interfaces {
  ge-1/0/2 {
    encapsulation ethernet-ccc;
    unit 0;
  }
  lo0 {
    unit 0 {
      family inet {
        address 192.0.2.2/24;
      }
    }
  }
}
```

2. On Router PE2, configure the routing instance at the [edit routing-instances] hierarchy level. Also, configure the Layer 2 VPN protocol at the [edit routing-instances *routing-instances-name* protocols] hierarchy level. Configure the remote site ID as 3. Site ID 3 represents Router PE3 (Hub-PE). The Layer 2 VPN is using LDP as the signaling protocol. Be aware that in the following example, both the routing instance and the protocol are named l2vpn.

```
[edit]
routing-instances {
  l2vpn { # routing instance
    instance-type l2vpn;
    interface ge-1/0/2.0;
    route-distinguisher 65000:2;
    vrf-target target:65000:2;
    protocols {
      l2vpn { # protocol
        encapsulation-type ethernet;
        site CE2 {
```

```

        site-identifier 2;
        interface ge-1/0/2.0 {
            remote-site-id 3;
        }
    }
}
}
}
}
}

```

3. On Router PE5, configure the Gigabit Ethernet interface for the PE-CE link ge-2/0/0 and configure the lo0 interface.

```

[edit interfaces]
ge-2/0/0 {
    unit 0 {
        family inet {
            address 198.51.100.8/24;
        }
    }
}
lo0 {
    unit 0 {
    }
}
}

```

4. On Router PE5, configure the Layer 3 VPN routing instance (L3VPN) at the [edit routing-instances] hierarchy level. Also configure BGP at the [edit routing-instances L3VPN protocols] hierarchy level.

```

[edit]
routing-instances {
    L3VPN {
        instance-type vrf;
        interface ge-2/0/0.0;
        route-distinguisher 65000:5;
        vrf-target target:65000:2;
        vrf-table-label;
        protocols {
            bgp {
                group ce5 {
                    neighbor 198.51.100.2 {

```

```

    peer-as 200;
  }
}
}
}
}
}
}
}

```

5. In an MX Series router, such as Router PE3, you must create the tunnel services interface to be used for tunnel services. To create the tunnel service interface, include the `bandwidth` statement and specify the amount of bandwidth to reserve for tunnel services in gigabits per second at the `[edit chassis fpc slot-number pic slot-number tunnel-services]` hierarchy level.

```

[edit]
chassis {
  dump-on-panic;
  fpc 1 {
    pic 1 {
      tunnel-services {
        bandwidth 1g;
      }
    }
  }
}

```

6. On Router PE3, configure the Gigabit Ethernet interface.

Include the `address` statement at the `[edit interfaces ge-1/0/1.0 family inet]` hierarchy level and specify 198.51.100.9/24 as the IP address.

```

[edit]
interfaces {
  ge-1/0/1 {
    unit 0 {
      family inet {
        address 198.51.100.9/24;
      }
    }
  }
}

```


7. On Router PE3, configure the lt-1/1/10.0 logical tunnel interface at the [edit interfaces lt-1/1/10 unit 0] hierarchy level. Router PE3 is the router that is *stitching* the Layer 2 VPN to the Layer 3 VPN using the logical tunnel interface. The configuration of the peer unit interfaces is what makes the interconnection.

To configure the interface, include the `encapsulation ethernet-ccc` option. Include the `peer-unit` statement and specify the logical interface unit 1 as the peer tunnel interface. Include the `family` statement and specify the `ccc` option.

```
[edit]
interfaces {
  lt-1/1/10 {
    unit 0 {
      encapsulation ethernet-ccc;
      peer-unit 1;
      family ccc;
    }
  }
}
```

8. On Router PE3, configure the lt-1/1/10.1 logical tunnel interface at the [edit interfaces lt-1/1/10 unit 1] hierarchy level.

To configure the interface, include the `encapsulation ethernet` option. Include the `peer-unit` statement and specify the logical interface unit 0 as the peer tunnel interface. Include the `family` statement and specify the `inet` option. Include the `address` statement at the [edit interfaces lt-1/1/10 unit 0] hierarchy level and specify 198.51.100.7/24 as the IPv4 address.

```
[edit]
interfaces {
  lt-1/1/10 {
    unit 1 {
      encapsulation ethernet;
      peer-unit 0;
      family inet {
        address 198.51.100.7/24;
      }
    }
  }
}
```

9. On Router PE3, add the lt interface unit 1 to the routing instance at the [edit routing-instances L3VPN] hierarchy level. Configure the instance type as vrf with lt peer-unit 1 as a PE-CE interface to terminate the Layer 2 VPN on Router PE2 into the Layer 3 VPN on Router PE3.

```
[edit]
routing-instances {
  L3VPN {
    instance-type vrf;
    interface ge-1/0/1.0;
    interface lt-1/1/10.1;
    route-distinguisher 65000:33;
    vrf-target target:65000:2;
    vrf-table-label;
    protocols {
      bgp {
        export direct;
        group ce3 {
          neighbor 198.51.100.10 {
            peer-as 100;
          }
        }
      }
    }
  }
}
```

10. On Router PE3, add the lt interface unit 0 to the routing instance at the [edit routing-instances protocols l2vpn] hierarchy level. Also configure the same vrf target for the Layer 2 VPN and Layer 3 VPN routing instances, so that the routes can be leaked between the instances. The example configuration in the previous step shows the vrf target for the L3VPN routing instance. The following example shows the vrf target for the l2vpn routing instance.

```
[edit]
routing-instances {
  l2vpn {
    instance-type l2vpn;
    interface lt-1/1/10.0;
    route-distinguisher 65000:3;
    vrf-target target:65000:2;
    protocols {
      l2vpn {
```

```

        encapsulation-type ethernet;
        site CE3 {
            site-identifier 3;
            interface lt-1/1/10.0 {
                remote-site-id 2;
            }
        }
    }
}

```

11. On Router PE3, configure the policy-statement statement to export the routes learned from the directly connected lt interface unit 1 to all the CE routers for connectivity, if needed.

```

[edit]
policy-options {
    policy-statement direct {
        term 1 {
            from protocol direct;
            then accept;
        }
    }
}

```

Results

The following output shows the full configuration of Router PE2:

Router PE2

```

interfaces {
    xe-0/1/0 {
        unit 0 {
            family inet {
                address 10.10.2.2/30;
            }
            family mpls;
        }
    }
    xe-0/2/0 {

```

```

    unit 0 {
        family inet {
            address 10.10.5.1/30;
        }
        family mpls;
    }
}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.4.1/30;
        }
        family mpls;
    }
}
ge-1/0/2 {
    encapsulation ethernet-ccc;
    unit 0;
}
fxp0 {
    apply-groups [ re0 re1 ];
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}
}
routing-options {
    static {
        route 172.0.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    mpls {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

```

```

bgp {
    group RR {
        type internal;
        local-address 192.0.2.2;
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}

ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}

}

routing-instances {
    l2vpn {
        instance-type l2vpn;
        interface ge-1/0/2.0;
        route-distinguisher 65000:2;
        vrf-target target:65000:2;
        protocols {
            l2vpn {
                encapsulation-type ethernet;
                site CE2 {
                    site-identifier 2;
                    interface ge-1/0/2.0 {
                        remote-site-id 3;
                    }
                }
            }
        }
    }
}

```

```

    }
}

```

The following output shows the final configuration of Router PE5:

Router PE5

```

interfaces {
  ge-0/0/0 {
    unit 0 {
      family inet {
        address 10.10.4.2/30;
      }
      family mpls;
    }
  }
  xe-0/1/0 {
    unit 0 {
      family inet {
        address 10.10.6.2/30;
      }
      family mpls;
    }
  }
  ge-1/0/0 {
    unit 0 {
      family inet {
        address 10.10.9.1/30;
      }
      family mpls;
    }
  }
  xe-1/1/0 {
    unit 0 {
      family inet {
        address 10.10.3.2/30;
      }
      family mpls;
    }
  }
  ge-2/0/0 {
    unit 0 {

```

```

        family inet {
            address 198.51.100.8/24;
        }
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.5/24;
        }
    }
}
}
routing-options {
    static {
        route 172.0.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    rsvp {
        interface all {
            link-protection;
        }
        interface fxp0.0 {
            disable;
        }
    }
    mpls {
        label-switched-path to-RR {
            to 192.0.2.7;
        }
        label-switched-path to-PE2 {
            to 192.0.2.2;
        }
        label-switched-path to-PE3 {
            to 192.0.2.3;
        }
        label-switched-path to-PE4 {
            to 192.0.2.4;
        }
        label-switched-path to-PE1 {
            to 192.0.2.1;
        }
    }
}

```

```

    }
    interface all;
    interface fxp0.0 {
        disable;
    }
}
bgp {
    group to-rr {
        type internal;
        local-address 192.0.2.5;
        family inet-vpn {
            unicast;
        }
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}
routing-instances {
    L3VPN {
        instance-type vrf;
        interface ge-2/0/0.0;
        route-distinguisher 65000:5;
        vrf-target target:65000:2;
        vrf-table-label;
    }
}

```



```

    protocols {
        bgp {
            group ce5 {
                neighbor 198.51.100.2 {
                    peer-as 200;
                }
            }
        }
    }
}

```

The following output shows the final configuration of Router PE3:

Router PE3

```

chassis {
    dump-on-panic;
    fpc 1 {
        pic 1 {
            tunnel-services {
                bandwidth 1g;
            }
        }
    }
    network-services ip;
}
interfaces {
    ge-1/0/1 {
        unit 0 {
            family inet {
                address 198.51.100.9/24;
            }
        }
    }
    lt-1/1/10 {
        unit 0 {
            encapsulation ethernet-ccc;
            peer-unit 1;
            family ccc;
        }
        unit 1 {

```

```
        encapsulation ethernet;
        peer-unit 0;
        family inet {
            address 198.51.100.7/24;
        }
    }
}
xe-2/0/0 {
    unit 0 {
        family inet {
            address 10.10.20.2/30;
        }
        family mpls;
    }
}
xe-2/1/0 {
    unit 0 {
        family inet {
            address 10.10.6.1/30;
        }
        family mpls;
    }
}
xe-2/2/0 {
    unit 0 {
        family inet {
            address 10.10.5.2/30;
        }
        family mpls;
    }
}
xe-2/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.2/30;
        }
        family mpls;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
```

```

    }
  }
}
routing-options {
  static {
    route 172.0.0.0/8 next-hop 172.19.59.1;
  }
  autonomous-system 65000;
}
protocols {
  rsvp {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  mpls {
    label-switched-path to-RR {
      to 192.0.2.7;
    }
    label-switched-path to-PE2 {
      to 192.0.2.2;
    }
    label-switched-path to-PE5 {
      to 192.0.2.5;
    }
    label-switched-path to-PE4 {
      to 192.0.2.4;
    }
    label-switched-path to-PE1 {
      to 192.0.2.1;
    }
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  bgp {
    group RR {
      type internal;
      local-address 192.0.2.3;
      family inet-vpn {

```

```

        unicast;
    }
    family l2vpn {
        signaling;
    }
    neighbor 192.0.2.7;
}
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}
policy-options {
    policy-statement direct {
        term 1 {
            from protocol direct;
            then accept;
        }
    }
}
routing-instances {
    L3VPN {
        instance-type vrf;
        interface ge-1/0/1.0;
        interface lt-1/1/10.1;
        route-distinguisher 65000:33;
        vrf-target target:65000:2;
        vrf-table-label;
        protocols {
            bgp {
                export direct;
            }
        }
    }
}

```

```

        group ce3 {
            neighbor 198.51.100.10 {
                peer-as 100;
            }
        }
    }
}

l2vpn {
    instance-type l2vpn;
    interface lt-1/1/10.0;
    route-distinguisher 65000:3;
    vrf-target target:65000:2;
    protocols {
        l2vpn {
            encapsulation-type ethernet;
            site CE3 {
                site-identifier 3;
                interface lt-1/1/10.0 {
                    remote-site-id 2;
                }
            }
        }
    }
}
}

```

Verification

IN THIS SECTION

- [Verifying Router PE2 VPN Interface | 1315](#)
- [Verifying Router PE3 VPN Interface | 1317](#)
- [Verifying End-to-End connectivity from Router CE2 to Router CE5 and Router CE3 | 1320](#)

Verify the Layer 2 VPN-to-Layer 3 VPN interconnection:

Verifying Router PE2 VPN Interface

Purpose

Check that the Layer 2 VPN is up and working at the Router PE2 interface and that all the routes are there.

Action

1. Use the `show l2vpn connections` command to verify that the connection site ID is 3 for Router PE3 and that the status is Up.

```

user@PE2> show l2vpn connections
Layer-2 VPN connections:
Legend for connection status (St)
EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned    <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down   CF -- call admission control failure
RD -- remote site signaled down  SC -- local and remote site ID collision
LN -- local site not designated  LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby

Legend for interface status
Up -- operational
Dn -- down

Instance: l2vpn
Local site: CE2 (2)
  connection-site  Type  St    Time last up      # Up trans
  3                rmt   Up    Jan 7 14:14:37 2010      1
Remote PE: 192.0.2.3, Negotiated control-word: Yes (Null)

```

```
Incoming label: 800000, Outgoing label: 800001
Local interface: ge-1/0/2.0, Status: Up, Encapsulation: ETHERNET
```

2. Use the `show route table` command to verify that the Layer 2 VPN route is present and that there is a next hop of 10.10.5.2 through the xe-0/2/0.0 interface. The following output verifies that the Layer 2 VPN routes are present in the l2vpn.l2vpn.0 table. Similar output should be displayed for Router PE3.

```
user@PE2> show route table l2vpn.l2vpn.0
l2vpn.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

65000:2:2:3/96
    *[L2VPN/170/-101] 02:40:35, metric2 1
        Indirect
65000:3:3:1/96
    *[BGP/170] 02:40:35, localpref 100, from 192.0.2.7
        AS path: I
        > to 10.10.5.2 via xe-0/2/0.0
```

3. Verify that Router PE2 has a Layer 2 VPN MPLS label pointing to the LDP label to Router PE3 in both directions (PUSH and POP).

```
user@PE2> show route table mpls.0
mpls.0: 13 destinations, 13 routes (13 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w3d 08:57:41, metric 1
            Receive
1          *[MPLS/0] 1w3d 08:57:41, metric 1
            Receive
2          *[MPLS/0] 1w3d 08:57:41, metric 1
            Receive
300560     *[LDP/9] 19:45:53, metric 1
            > to 10.10.2.1 via xe-0/1/0.0, Pop
300560(S=0) *[LDP/9] 19:45:53, metric 1
            > to 10.10.2.1 via xe-0/1/0.0, Pop
301008     *[LDP/9] 19:45:53, metric 1
            > to 10.10.4.2 via xe-0/3/0.0, Swap 299856
301536     *[LDP/9] 19:45:53, metric 1
            > to 10.10.4.2 via xe-0/3/0.0, Pop
301536(S=0) *[LDP/9] 19:45:53, metric 1
```

```

> to 10.10.4.2 via xe-0/3/0.0, Pop
301712      *[LDP/9] 16:14:52, metric 1
> to 10.10.5.2 via xe-0/2/0.0, Swap 315184
301728      *[LDP/9] 16:14:52, metric 1
> to 10.10.5.2 via xe-0/2/0.0, Pop
301728(S=0) *[LDP/9] 16:14:52, metric 1
> to 10.10.5.2 via xe-0/2/0.0, Pop
800000      *[L2VPN/7] 02:40:35
> via ge-1/0/2.0, Pop      Offset: 4
ge-1/0/2.0  *[L2VPN/7] 02:40:35, metric2 1
> to 10.10.5.2 via xe-0/2/0.0, Push 800001 Offset: -4

```

Meaning

The l2vpn routing instance is up at interface ge-1/0/2 and the Layer 2 VPN route is shown in table l2vpn.l2vpn.0. Table mpls.0 shows the Layer 2 VPN routes used to forward the traffic using an LDP label.

Verifying Router PE3 VPN Interface

Purpose

Check that the Layer 2 VPN connection from Router PE2 and Router PE3 is Up and working.

Action

1. Verify that the BGP session with the route reflector for the family l2vpn-signaling and the family inet-vpn is established.

```

user@PE3> show bgp summary
Groups: 2 Peers: 2 Down peers: 0
Table      Tot Paths  Act Paths Suppressed  History Damp State   Pending
bgp.l2vpn.0      1         1         0           0         0         0
bgp.L3VPN.0      1         1         0           0         0         0
Peer        AS   InPkt   OutPkt   OutQ   Flaps  Last Up/Dwn   State|#Active /Received/
Accepted/Damped...
192.0.2.7  65000   2063    2084     0       1   15:35:16  Establ
  bgp.l2vpn.0: 1/1/1/0
  bgp.L3VPN.0: 1/1/1/0
  L3VPN.inet.0: 1/1/1/0
  l2vpn.l2vpn.0: 1/1/1/0

```


2. The following output verifies the Layer 2 VPN route and the label associated with it.

```

user@PE3> show route table l2vpn.l2vpn.0 detail
l2vpn.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
65000:2:2:3/96 (1 entry, 1 announced)
    *BGP    Preference: 170/-101
            Route Distinguisher: 65000:2
            Next hop type: Indirect
            Next-hop reference count: 4
            Source: 192.0.2.7
            Protocol next hop: 192.0.2.2
            Indirect next hop: 2 no-forward
            State: <Secondary Active Int Ext>
            Local AS: 65000 Peer AS: 65000
            Age: 2:45:52    Metric2: 1
            Task: BGP_65000.192.0.2.7+60585
            Announcement bits (1): 0-l2vpn-l2vpn
            AS path: I (Originator) Cluster list: 192.0.2.7
            AS path: Originator ID: 192.0.2.2
            Communities: target:65000:2 Layer2-info: encaps:ETHERNET, control
flags:Control-Word, mtu: 0, site preference: 100 Accepted
            Label-base: 800000, range: 2, status-vector: 0x0
            Localpref: 100
            Router ID: 192.0.2.7
            Primary Routing Table bgp.l2vpn.0

```

3. The following output show the L2VPN MPLS.0 route in the mpls.0 route table.

```

user@PE3> show route table mpls.0
mpls.0: 21 destinations, 21 routes (21 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w3d 09:05:41, metric 1
           Receive
1          *[MPLS/0] 1w3d 09:05:41, metric 1
           Receive
2          *[MPLS/0] 1w3d 09:05:41, metric 1
           Receive
16         *[VPN/0] 15:59:24
           to table L3VPN.inet.0, Pop
315184     *[LDP/9] 16:21:53, metric 1

```

```

> to 10.10.20.1 via xe-2/0/0.0, Pop
315184(S=0)  *[LDP/9] 16:21:53, metric 1
> to 10.10.20.1 via xe-2/0/0.0, Pop
315200      *[LDP/9] 01:13:44, metric 1
            to 10.10.20.1 via xe-2/0/0.0, Swap 625297
> to 10.10.6.2 via xe-2/1/0.0, Swap 299856
315216      *[LDP/9] 16:21:53, metric 1
> to 10.10.6.2 via xe-2/1/0.0, Pop
315216(S=0)  *[LDP/9] 16:21:53, metric 1
> to 10.10.6.2 via xe-2/1/0.0, Pop
315232      *[LDP/9] 16:21:45, metric 1
> to 10.10.1.1 via xe-2/3/0.0, Pop
315232(S=0)  *[LDP/9] 16:21:45, metric 1
> to 10.10.1.1 via xe-2/3/0.0, Pop
315248      *[LDP/9] 16:21:53, metric 1
> to 10.10.5.1 via xe-2/2/0.0, Pop
315248(S=0)  *[LDP/9] 16:21:53, metric 1
> to 10.10.5.1 via xe-2/2/0.0, Pop
315312      *[RSVP/7] 15:02:40, metric 1
> to 10.10.6.2 via xe-2/1/0.0, label-switched-path to-pe5
315312(S=0)  *[RSVP/7] 15:02:40, metric 1
> to 10.10.6.2 via xe-2/1/0.0, label-switched-path to-pe5
315328      *[RSVP/7] 15:02:40, metric 1
> to 10.10.20.1 via xe-2/0/0.0, label-switched-path to-RR
315360      *[RSVP/7] 15:02:40, metric 1
> to 10.10.20.1 via xe-2/0/0.0, label-switched-path to-RR
316272      *[RSVP/7] 01:13:27, metric 1
> to 10.10.6.2 via xe-2/1/0.0, label-switched-path Bypass->10.10.9.1
316272(S=0)  *[RSVP/7] 01:13:27, metric 1
> to 10.10.6.2 via xe-2/1/0.0, label-switched-path Bypass->10.10.9.1
800001      *[L2VPN/7] 02:47:33
            > via lt-1/1/10.0, Pop      Offset: 4
lt-1/1/10.0  *[L2VPN/7] 02:47:33, metric2 1
            > to 10.10.5.1 via xe-2/2/0.0, Push 800000 Offset: -4

```

4. Use the `show route table mpls.0` command with the `detail` option to see the BGP attributes of the route such as next-hop type and label operations.

```

user@PE5> show route table mpls.0 detail
lt-1/1/10.0 (1 entry, 1 announced)
    *L2VPN Preference: 7
    Next hop type: Indirect

```

```

Next-hop reference count: 2
Next hop type: Router, Next hop index: 607
Next hop: 10.10.5.1 via xe-2/2/0.0, selected
Label operation: Push 800000 Offset: -4
Protocol next hop: 192.0.2.2
Push 800000 Offset: -4
Indirect next hop: 8cae0a0 1048574
State: <Active Int>
Age: 2:46:34    Metric2: 1
Task: Common L2 VC
Announcement bits (2): 0-KRT 2-Common L2 VC
AS path: I
Communities: target:65000:2 Layer2-info: encaps:ETHERNET, control
flags:Control-Word, mtu: 0, site preference: 100

```

Verifying End-to-End connectivity from Router CE2 to Router CE5 and Router CE3

Purpose

Check the connectivity between Routers CE2, CE3, and CE5.

Action

1. Ping the Router CE3 IP address from Router CE2.

```

user@CE2> ping 198.51.100.10 # CE3 IP address
PING 198.51.100.10 (198.51.100.10): 56 data bytes
64 bytes from 198.51.100.10: icmp_seq=0 ttl=63 time=0.708 ms
64 bytes from 198.51.100.10: icmp_seq=1 ttl=63 time=0.610 ms

```

2. Ping the Router CE5 IP address from Router CE2.

```

user@CE2> ping 198.51.100.2 # CE5 IP address
PING 198.51.100.2 (198.51.100.2): 56 data bytes
64 bytes from 198.51.100.2: icmp_seq=0 ttl=62 time=0.995 ms
64 bytes from 198.51.100.2: icmp_seq=1 ttl=62 time=1.005 ms

```

Connecting Layer 2 Circuits to Other VPNs

IN THIS CHAPTER

- Using the Layer 2 Interworking Interface to Interconnect a Layer 2 Circuit to a Layer 2 VPN | 1321
- Applications for Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | 1323
- Example: Interconnecting a Layer 2 Circuit with a Layer 2 VPN | 1323
- Example: Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | 1336
- Applications for Interconnecting a Layer 2 Circuit with a Layer 3 VPN | 1357
- Example: Interconnecting a Layer 2 Circuit with a Layer 3 VPN | 1358

Using the Layer 2 Interworking Interface to Interconnect a Layer 2 Circuit to a Layer 2 VPN

Instead of using a physical Tunnel PIC for looping the packet received from the Layer 2 circuit, the Layer 2 interworking interface uses Junos OS to stitch together both Layer 2 VPN routes.

To configure the interworking interface, include the **iw0** statement. The **iw0** statement is configured at the **[edit interfaces]** hierarchy level. This specifies the peering between two logical interfaces. This configuration is similar to the configuration for a logical tunnel interface. The logical Interfaces must be associated with the endpoints of a Layer 2 circuit and Layer 2 VPN connections.

```
[edit interfaces]
iw0 {
  unit 0 {
    peer-unit 1;
  }
  unit 1 {
    peer-unit 0;
  }
}
```

Configure the Layer 2 circuit protocol by including the `l2circuit` statement at the `[edit protocols]` hierarchy level and specifying the `neighbor` and `iw0` interface.

```
[edit protocols]
l2circuit {
  neighbor 192.0.2.0 {
    interface iw0.0;
  }
}
```

Configure the Layer 2 VPN connection, by including the `routing-instance-name` statement at the `[edit routing-instances]` hierarchy level and specifying the `instance-type l2vpn` option.

```
[edit routing-instances]
routing-instance-name {
  instance-type l2vpn;
  interface iw0.1;
  ...
  protocols {
    l2vpn {
      <l2vpn configuration>;
    }
  }
}
```

In addition to the `iw0` interface configuration, Layer 2 interworking `l2iw` protocols must be enabled. Without the `l2iw` configuration, the `l2iw` routes will not be formed, regardless of whether any `iw` interfaces are present. Within the `l2iw` protocols, only trace options can be configured in the standard fashion. The minimum configuration necessary for the feature to work is shown below:

```
[edit]
protocols {
  l2iw;
}
```

RELATED DOCUMENTATION

[Layer 2 Circuit Overview | 354](#)

[Example: Interconnecting a Layer 2 Circuit with a Layer 2 VPN | 1323](#)

Applications for Interconnecting a Layer 2 Circuit with a Layer 2 Circuit

MPLS-based Layer 2 services are growing in demand among enterprise and service providers. This creates new challenges for service providers who want to provide end-to-end value-added services. There are various reasons to stitch different Layer 2 services to one another and to Layer 3 services, for example, to expand the service offerings and to expand geographically. Junos OS has various features to address the needs of the service provider.

In Layer 2 circuits with structure-aware TDM Circuit Emulation Service over Packet-Switched Network (CESoPSN) encapsulation, you can configure the payload size for virtual circuits that terminate on Layer 2 interworking (iw) logical interfaces. The payload size must be specified to enable stitching of LDP-signaled TDM pseudowires in environments where an interconnection between two Layer 2 circuits is required. You can include the `payload-size bytes` statement at the `[edit interfaces interface-name cesopsn-options]` hierarchy level, to define the size in bytes (from 32 through 1024 bytes).

Interconnecting a Layer 2 circuit with a Layer 2 circuit includes the following benefits:

- Interconnecting a Layer 2 circuit with a Layer 2 circuit enables the sharing of a service provider's core network infrastructure between Layer 2 circuit services, reducing the cost of providing those services. A Layer 2 MPLS circuit enables service providers to create a Layer 2 circuit service over an existing IP and MPLS backbone.
- Service providers do not have to invest in separate Layer 2 equipment to provide Layer 2 circuit service. A service provider can configure a provider edge router to run any Layer 2 protocol. Customers who prefer to maintain control over most of the administration of their own networks want Layer 2 circuit connections with their service provider instead of a Layer 3 VPN connection.

RELATED DOCUMENTATION

[Example: Interconnecting a Layer 2 Circuit with a Layer 2 Circuit](#) | 1336

Example: Interconnecting a Layer 2 Circuit with a Layer 2 VPN

IN THIS SECTION

- [Requirements](#) | 1324
- [Overview and Topology](#) | 1324
- [Configuration](#) | 1326

This example provides a step-by-step procedure and commands for configuring and verifying a Layer 2 circuit to a Layer 2 VPN. It contains the following sections:

Requirements

This example uses the following hardware and software components:

- Junos OS Release 9.3 or later
- 2 MX Series 5G Universal Routing Platforms
- 2 M Series Multiservice Edge Router
- 1 T Series Core Router
- 1 EX Series Ethernet Switch

Overview and Topology


IN THIS SECTION

- [Topology | 1325](#)

Topology


The physical topology of a Layer 2 circuit to a Layer 2 VPN connection is shown in [Figure 87 on page 1325](#).

Figure 87: Physical Topology of a Layer 2 Circuit to a Layer 2 VPN Connection



The logical topology of a Layer 2 circuit to a Layer 2 VPN connection is shown in [Figure 88 on page 1326](#).

Figure 88: Logical Topology of a Layer 2 Circuit to a Layer 2 VPN Connection



Configuration

IN THIS SECTION

- [Configuring Protocols on the PE and P Routers | 1327](#)
- [Verification | 1333](#)

NOTE: In any configuration session, it is good practice to verify periodically that the configuration can be committed using the `commit check` command.

In this example, the router being configured is identified using the following command prompts:

- CE1 identifies the customer edge 1 (CE1) router
- PE1 identifies the provider edge 1 (PE1) router
- CE3 identifies the customer edge 3 (CE3) router
- PE3 identifies the provider edge 3 (PE3) router
- CE5 identifies the customer edge 5 (CE5) router
- PE5 identifies the provider edge 5 (PE5) router

This example is organized in the following sections:

Configuring Protocols on the PE and P Routers

Step-by-Step Procedure

In this example, all of the PE routers and P routers are configured with OSPF as the IGP protocol. The MPLS, LDP, and BGP protocols are enabled on all of the interfaces except `fxp0.0`. Core-facing interfaces are enabled with the MPLS address and inet address.

1. Configure all the PE and P routers with OSPF as the IGP. Enable the MPLS, LDP, and BGP protocols on all interfaces except `fxp0.0`. LDP is used as the signaling protocol on Router PE1 for the Layer 2 circuit. The following configuration snippet shows the protocol configuration for Router PE1:

```
[edit]
protocols {
  mpls {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  bgp {
    group RR {
      type internal;
      local-address 192.0.2.1;
      family l2vpn {
        signaling;
      }
      neighbor 192.0.2.7;
    }
  }
}
```

```

ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}

```

2. Configure the PE and P routers with OSPF as the IGP. Enable the MPLS, LDP, and BGP protocols on all interfaces except fxp0. BGP is used as the signaling protocol on Router PE3 for the Layer 2 VPN. The following configuration snippet shows the protocol configuration for Router PE3:

```

[edit]
protocols {
    mpls {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    bgp {
        group RR {
            type internal;
            local-address 192.0.2.3;
            family l2vpn {
                signaling;
            }
            neighbor 192.0.2.7;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {

```

```

        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}

ldp {
    interface all;
    interface fxp0.0 {
        disable;
    }
}
}

```

Step-by-Step Procedure

Configuring Interfaces

1. On Router PE1, configure the `ge-1/0/0` interface encapsulation. To configure the interface encapsulation, include the encapsulation statement and specify the `ethernet-ccc` option (vlan-ccc encapsulation is also supported). Configure the `ge-1/0/0.0` logical interface family for circuit cross-connect functionality. To configure the logical interface family, include the `family` statement and specify the `ccc` option. The encapsulation should be configured the same way for all routers in the Layer 2 circuit domain.

```

[edit interfaces]
ge-1/0/0 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}

lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}

```

2. Router PE5 is the router that is *stitching* the Layer 2 circuit to the Layer 2 VPN using the interworking interface. The configuration of the peer unit interfaces is what makes the interconnection.

On Router PE5, configure the `iw0` interface with two logical interfaces. To configure the `iw0` interface, include the `interfaces` statement and specify `iw0` as the interface name. For the unit 0 logical interface, include the `peer-unit` statement and specify the logical interface `unit 1` as the peer interface. For the unit 1 logical interface, include the `peer-unit` statement and specify the logical interface `unit 0` as the peer interface.

```
[edit interfaces]
iw0 {
  unit 0 {
    encapsulation ethernet-ccc;
    peer-unit 1;
  }
  unit 1 {
    encapsulation ethernet-ccc;
    peer-unit 0;
  }
}
```

3. On Router PE5, configure the logical loopback interface. The loopback interface is used to establish the targeted LDP sessions to Routers PE1 and PE5.

```
[edit interfaces]
lo0 {
  unit 0 {
    family inet {
      address 192.0.2.5/24;
    }
  }
}
```

Step-by-Step Procedure

Configuring the Layer 2 circuit protocol

1. On Router PE1, configure the IP address of the remote PE router with the `neighbor` statement. The loopback address and router ID of the PE neighbor is commonly the neighbor's IP address. To allow a Layer 2 circuit to be established even though the maximum transmission unit (MTU) configured on

the PE router does not match the MTU configured on the remote PE router, include the `ignore-mtu-mismatch` statement.

```
[edit]
protocols {
  l2circuit {
    neighbor 192.0.2.5 {
      interface ge-1/0/0.0 {
        virtual-circuit-id 100;
        no-control-word;
        ignore-mtu-mismatch;
      }
    }
  }
}
```

2. On Router PE5, configure the IP address of the remote PE router. To configure the IP address of the remote PE router, include the `neighbor` statement and specify the IP address of the loopback interface on Router PE1. Configure the virtual circuit ID to be the same as the virtual circuit ID on the neighbor router. To allow a Layer 2 circuit to be established even though the MTU configured on the local PE router does not match the MTU configured on the remote PE router, include the `ignore-mtu-mismatch` statement. Also disable the use of the control word for demultiplexing by including the `no-control-word` statement.

```
[edit protocols]
l2circuit {
  neighbor 192.0.2.1 {
    interface iw0.0 {
      virtual-circuit-id 100;
      no-control-word;
      ignore-mtu-mismatch;
    }
  }
}
```

3. On Router PE5, configure the Layer 2 VPN protocols by including the `l2vpn` statement at the `[edit routing-instances routing-instances-name protocols]` hierarchy level. To configure the `iw0` interface, include the `interfaces` statement and specify `iw0` as the interface name. The `iw0` interface is configured under the Layer 2 VPN protocols to receive the looped packet from the `iw0.1` logical interface. The `l2vpn` protocol is configured on Router PE5 with site CE5, which is configured in the BGP L2VPN routing

instance. Router CE1 has communication to Router CE5, through the Layer 2 interworking configuration on Router PE5.

```
[edit]
routing-instances {
  L2VPN {
    instance-type l2vpn;
    interface ge-2/0/0.0;
    interface iw0.1;
    route-distinguisher 65000:5;
    vrf-target target:65000:2;
    protocols {
      l2vpn {
        no-control-word;
        encapsulation-type ethernet;
        site CE5 {
          site-identifier 5;
          interface ge-2/0/0.0 {
            remote-site-id 3;
          }
        }
        site l2-circuit {
          site-identifier 6;
          interface iw0.1 {
            remote-site-id 3;
          }
        }
      }
    }
  }
}
```

4. In addition to the `iw0` interface configuration, the Layer 2 interworking `l2iw` protocol must be configured. Without the `l2iw` protocol configuration, the Layer 2 interworking routes are not formed, regardless of whether any `iw` interfaces are present.

On Router PE5, configure the `l2iw` protocol. To configure the protocol, include the `l2iw` statement at the `[edit protocols]` hierarchy level.

```
[edit]
protocols {
```

```
l2iw;
}
```

Verification

Step-by-Step Procedure

Verifying the Layer 2 Circuit Connection on Router PE1.

1. On Router PE1, use the `show l2circuit connections` command to verify that the Layer 2 Circuit from Router PE1 to Router PE5 is Up.

```
user@PE1> show l2circuit connections
Layer-2 Circuit Connections:
Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch     Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad XX -- unknown
SP -- Static Pseudowire

Legend for interface status
Up -- operational
Dn -- down
Neighbor: 192.0.2.5
  Interface          Type  St    Time last up  # Up trans
  ge-1/0/0.0(vc 100)  rmt   Up    Jan  3 22:00:49 2010    1
  Remote PE: 192.0.2.5, Negotiated control-word: No
  Incoming label: 301328, Outgoing label: 300192
  Local interface: ge-1/0/0.0, Status: Up, Encapsulation: ETHERNET
```


2. On Router PE5, use the `show l2vpn connections` command to verify that the Layer 2 VPN connection is Up using the `iw0` peer interface of the Layer 2 circuit.

```

user@PE5> show l2vpn connections
Instance: L2VPN
Local site: CE5 (5)
  connection-site      Type  St    Time last up    # Up trans
  l2-circuit (6)       loc   OR
  3                    rmt   Up
  Jan  3 22:51:12 2010      1
  Remote PE: 192.0.2.3, Negotiated control-word: No
  Incoming label: 800258, Outgoing label: 800000
  Local interface: ge-2/0/0.0, Status: Up, Encapsulation: ETHERNET
Local site: l2-circuit (6)
  connection-site      Type  St    Time last up    # Up trans
  CE5 (5)              loc   OR
  3                    rmt   Up    Jan  3 22:56:38 2010    1
  Remote PE: 192.0.2.3, Negotiated control-word: No
  Incoming label: 800262, Outgoing label: 800001
  Local interface: iw0.1, Status: Up, Encapsulation: ETHERNET

```

Step-by-Step Procedure

Verifying that the Layer 2 Circuit is terminating into the Layer 2 VPN connection.

1. On Router PE5, use the `show l2circuit connections` command to verify that the Layer 2 circuit is Up using the `iw0` interface. This will be looped through the `iw0.1` interface to the Layer 2 VPN.

```

user@PE5> show l2circuit connections

Layer-2 Circuit Connections:
Neighbor: 192.0.2.1
  Interface      Type  St    Time last up    # Up trans
  iw0.0(vc 100)  rmt   Up    Jan  3 21:59:07 2010    1
  Remote PE: 192.0.2.1, Negotiated control-word: No
  Incoming label: 300192, Outgoing label: 301328

```

2. On Router PE 5, use the `show route table mpls.0` command to verify the Layer 2 circuit and Layer 2 VPN routes. In the example below, the Layer 2 circuit is associated with LDP label 301328 and the Layer 2

VPN is associated with LDP label 800001. Notice the two `iw0` interfaces that are used for the Layer 2 interworking route.

```

user@PE5>show route table mpls.0

mpls.0: 18 destinations, 20 routes (18 active, 2 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 5d 20:07:31, metric 1
            Receive
1          *[MPLS/0] 5d 20:07:31, metric 1
            Receive
2          *[MPLS/0] 5d 20:07:31, metric 1
            Receive
299776     *[LDP/9] 2d 03:00:51, metric 1
300048     *[LDP/9] 2d 03:00:49, metric 1
            > to 10.10.6.1 via xe-0/1/0.0, Pop
300048(S=0) *[LDP/9] 2d 03:00:49, metric 1
            > to 10.10.6.1 via xe-0/1/0.0, Pop
300192     *[L2IW/6] 19:11:05, metric2 1
            > to 10.10.6.1 via xe-0/1/0.0, Swap 800001
            [L2CKT/7] 20:08:36
            > via iw0.0, Pop
800258     *[L2VPN/7] 19:16:31
            > via ge-2/0/0.0, Pop          Offset: 4
800262     *[L2IW/6] 19:11:05, metric2 1          > to 10.10.3.1 via xe-1/1/0.0,
Swap 301328          [L2VPN/7] 19:11:05          > via iw0.1, Pop          Offset:
4ge-2/0/0.0     *[L2VPN/7] 19:16:31, metric2 1
            > to 10.10.6.1 via xe-0/1/0.0, Push 800000 Offset: -4
iw0.0         *[L2CKT/7] 20:08:36, metric2 1
            > to 10.10.3.1 via xe-1/1/0.0, Push 301328
iw0.1         *[L2VPN/7] 19:11:05, metric2 1
            > to 10.10.6.1 via xe-0/1/0.0, Push 800001 Offset: -4

```

RELATED DOCUMENTATION

Applications for Interconnecting a Layer 2 Circuit with a Layer 2 Circuit | 1323

Example: Interconnecting a Layer 2 Circuit with a Layer 2 Circuit

IN THIS SECTION

- [Requirements | 1336](#)
- [Overview and Topology | 1336](#)
- [Configuration | 1338](#)

This example provides a step-by-step procedure and commands for configuring and verifying a Layer 2 circuit to a Layer 2 circuit interconnection. It contains the following sections:

Requirements

This example uses the following hardware and software components:

- Junos OS Release 9.3 or later
- 2 MX Series routers
- 2 M Series routers
- 1 T Series router
- 1 EX Series router


Overview and Topology

IN THIS SECTION

- [Topology | 1338](#)


The physical topology of a Layer 2 circuit to Layer 2 circuit interconnection is shown in [Figure 89 on page 1337](#)

Figure 89: Physical Topology of a Layer 2 Circuit Terminating into a Layer 2 Circuit



The logical topology of a Layer 2 circuit to Layer 2 circuit interconnection is shown in [Figure 90 on page 1338](#)

Figure 90: Logical Topology of a Layer 2 Circuit Terminating into a Layer 2 Circuit



80-40579

Topology

Configuration

IN THIS SECTION

- [Configuring PE Router Customer-facing and Loopback Interfaces | 1339](#)
- [Configuring Core-facing Interfaces | 1341](#)
- [Configuring Protocols | 1343](#)
- [Configuring the Layer 2 Circuits | 1344](#)
- [Interconnecting the Layer 2 Circuits | 1346](#)
- [Verifying the Layer 2 Circuit to Layer 2 Circuit Interconnection | 1347](#)

NOTE: In any configuration session, it is good practice to verify periodically that the configuration can be committed using the `commit check` command.

In this example, the router being configured is identified using the following command prompts:

- CE2 identifies the customer edge 2 (CE2) router
- PE1 identifies the provider edge 1 (PE1) router
- CE3 identifies the customer edge 3 (CE3) router
- PE3 identifies the provider edge 3 (PE3) router
- CE5 identifies the customer edge 5 (CE5) router
- PE5 identifies the provider edge 5 (PE5) router

This example contains the following procedures:

Configuring PE Router Customer-facing and Loopback Interfaces

Step-by-Step Procedure

To begin building the interconnection, configure the interfaces on the PE routers. If your network contains provider (P) routers, configure the interfaces on the P routers also. This example shows the configuration for Router PE1 and Router PE5.

1. On Router PE1, configure the `ge-1/0/0` interface encapsulation. To configure the interface encapsulation, include the `encapsulation` statement and specify the `ethernet-ccc` option (vlan-ccc encapsulation is also supported). Configure the `ge-1/0/0.0` logical interface family for circuit cross-connect functionality. To configure the logical interface family, include the `family` statement and specify the `ccc` option.

```
[edit interfaces]
ge-1/0/0 {
  encapsulation ethernet-ccc;
  unit 0 {
```

```

        family ccc;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}

```

2. On Router PE5, configure the ge-2/0/0 interface encapsulation. To configure the interface encapsulation, include the encapsulation statement and specify the ethernet-ccc option. Configure the ge-2/0/0.0 logical interface family for circuit cross-connect functionality. To configure the logical interface family, include the family statement and specify the ccc option

```

[edit interfaces]
ge-2/0/0 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.5/24;
        }
    }
}

```

3. On Router PE3, configure the logical loopback interface. The loopback interface is used to establish the targeted LDP sessions to Routers PE1 and PE5.

```

[edit interfaces]
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}

```

```

    }
}

```

Configuring Core-facing Interfaces

Step-by-Step Procedure

This procedure describes how to configure the core-facing interfaces on the PE routers. This example does not include all the core-facing interfaces shown in the physical topology illustration. Enable the `mpls` and `inet` address families on the core-facing interfaces.

1. On Router PE1, configure the `xe-0/3/0` interface. Include the `family` statement and specify the `inet` address family. Include the `address` statement and specify `10.10.1.1/30` as the interface address. Include the `family` statement and specify the `mpls` address family.

```

[edit interfaces]
xe-0/3/0 {
  unit 0 {
    family inet {
      address 10.10.1.1/30;
    }
    family mpls;
  }
}

```

2. On Router PE3, configure the core-facing interfaces. Include the `family` statement and specify the `inet` address family. Include the `address` statement and specify the IPv4 addresses shown in the example as the interface addresses. Include the `family` statement and specify the `mpls` address family. In the example, the `xe-0/0/0` interface is connected to the route reflector, the `xe-0/1/0` interface is connected to Router PE5, the `xe-0/2/0` interface is connected to Router PE2, and the `xe-0/3/0` interface is connected to Router PE1.

```

[edit interfaces]
xe-0/0/0 {
  unit 0 {
    family inet {
      address 10.10.20.2/30;
    }
    family mpls;
  }
}

```



```

}
xe-0/1/0 {
    unit 0 {
        family inet {
            address 10.10.6.1/30;
        }
        family mpls;
    }
}
xe-0/2/0 {
    unit 0 {
        family inet {
            address 10.10.5.2/30;
        }
        family mpls;
    }
}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.2/30;
        }
        family mpls;
    }
}

```

3. On Router PE5, configure the xe-0/1/0 interface. Include the family statement and specify the inet address family. Include the address statement and specify 10.10.6.2/30 as the interface address. Include the family statement and specify the mpls address family.

```

[edit interfaces]
xe-0/1/0 {
    unit 0 {
        family inet {
            address 10.10.6.2/30;
        }
        family mpls;
    }
}

```

Configuring Protocols

Step-by-Step Procedure

This procedure describes how to configure the protocols used in this example. If your network contains P routers, configure the protocols on the P routers also.

Configure all of the PE routers and P routers with OSPF as the IGP protocol. Enable MPLS and LDP protocols on all of the interfaces except `fxp0.0`.

1. On Router PE1, enable OSPF as the IGP. Enable the MPLS and LDP protocols on all interfaces except `fxp0.0`. LDP is used as the signaling protocol on Router PE1 for the Layer 2 circuit. The following configuration snippet shows the protocol configuration for Router PE1:

```
[edit]
protocols {
  mpls {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  ospf {
    traffic-engineering;
    area 0.0.0.0 {
      interface all;
      interface fxp0.0 {
        disable;
      }
    }
  }
  ldp {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
}
```

2. Configure the PE and P routers with OSPF as the IGP. Enable the MPLS and LDP protocols on all interfaces except fxp0.0. The following configuration snippet shows the protocol configuration for Router PE3:

```
[edit]
protocols {
  mpls {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  ospf {
    traffic-engineering;
    area 0.0.0.0 {
      interface all;
      interface fxp0.0 {
        disable;
      }
    }
  }
  ldp {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
}
```

Configuring the Layer 2 Circuits

Step-by-Step Procedure

This procedure describes how to configure the Layer 2 circuits.

NOTE: In this example the `ignore-mtu-mismatch` statement is required for the circuit to come up.

1. On Router PE1, configure the Layer 2 circuit. Include the `l2circuit` statement. Include the `neighbor` statement and specify the loopback IPv4 address of Router PE3 as the neighbor. Include the `interface` statement and specify `ge-1/0/0.0` as the logical interface that is participating in the Layer 2 circuit. Include the `virtual-circuit-id` statement and specify `100` as the identifier. Include the `ignore-mtu-mismatch` statement to allow a Layer 2 circuit to be established even though the maximum transmission unit (MTU) configured on the local PE router does not match the MTU configured on the remote PE router.

```
[edit]
protocols {
  l2circuit {
    neighbor 192.0.2.3 {
      interface ge-1/0/0.0 {
        virtual-circuit-id 100;
        ignore-mtu-mismatch;
      }
    }
  }
}
```

2. On Router PE5, configure the Layer 2 circuit. Include the `l2circuit` statement. Include the `neighbor` statement and specify the loopback IPv4 address of Router PE3 as the neighbor. Include the `interface` statement and specify `ge-2/0/0.0` as the logical interface that is participating in the Layer 2 circuit. Include the `virtual-circuit-id` statement and specify `200` as the identifier. Include the `ignore-mtu-mismatch` statement to allow a Layer 2 circuit to be established even though the MTU configured on the local PE router does not match the MTU configured on the remote PE router.

```
[edit]
protocols {
  l2circuit {
    neighbor 192.0.2.3 {
      interface ge-2/0/0.0 {
        virtual-circuit-id 200;
        ignore-mtu-mismatch;
      }
    }
  }
}
```

3. On Router PE3, configure the Layer 2 circuit to Router PE1. Include the `l2circuit` statement. Include the `neighbor` statement and specify the loopback IPv4 address of Router PE1 as the neighbor. Include

the interface statement and specify `iw0.0` as the logical interworking interface that is participating in the Layer 2 circuit. Include the `virtual-circuit-id` statement and specify `100` as the identifier. Include the `ignore-mtu-mismatch` statement to allow a Layer 2 circuit to be established even though the MTU configured on the local PE router does not match the MTU configured on the remote PE router.

On Router PE3, configure the Layer 2 circuit to Router PE5. Include the `l2circuit` statement. Include the `neighbor` statement and specify the loopback IPv4 address of Router PE5 as the neighbor. Include the interface statement and specify `iw0.1` as the logical interworking interface that is participating in the Layer 2 circuit. Include the `virtual-circuit-id` statement and specify `200` as the identifier. Include the `ignore-mtu-mismatch` statement.

```
[edit protocols]
l2circuit {
  neighbor 192.0.2.1 {
    interface iw0.0 {
      virtual-circuit-id 100;
      ignore-mtu-mismatch;
    }
  }
  neighbor 192.0.2.5 {
    interface iw0.1 {
      virtual-circuit-id 200;
      ignore-mtu-mismatch;
    }
  }
}
```

Interconnecting the Layer 2 Circuits

Step-by-Step Procedure

Router PE3 is the router that is *stitching* the Layer 2 circuits together using the interworking interface. The configuration of the peer unit interfaces is what makes the interconnection.

1. On Router PE3, configure the `iw0.0` interface. Include the `encapsulation` statement and specify the `ethernet-ccc` option. Include the `peer-unit` statement and specify the logical interface unit 1 as the peer tunnel interface.

On Router PE3, configure the `iw0.1` interface. Include the `encapsulation ethernet-ccc` option. Include the `peer-unit` statement and specify the logical interface unit 0 as the peer tunnel interface.

```
[edit interfaces]
iw0 {
  unit 0 {
    encapsulation ethernet-ccc;
    peer-unit 1;
  }
  unit 1 {
    encapsulation ethernet-ccc;
    peer-unit 0;
  }
}
```

2. On Router PE3, configure the Layer 2 interworking `l2iw` protocol. To configure the Layer 2 interworking protocol, include the `l2iw` statement at the `[edit protocols]` hierarchy level.

```
[edit]
protocols {
  l2iw;
}
```

3. On each router, commit the configuration.

```
user@host> commit check
configuration check succeeds
user@host> commit
```

Verifying the Layer 2 Circuit to Layer 2 Circuit Interconnection

Step-by-Step Procedure

Verify that the Layer 2 circuit connection on Router PE1 is up, the LDP neighbors are correct, and the MPLS label operations are correct.

1. On Router PE1, use the `show l2circuit connections` command to verify that the Layer 2 circuit from Router PE1 to Router PE3 is Up.

```

user@PE1> show l2circuit connections
Layer-2 Circuit Connections:
Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch     Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad XX -- unknown
SP -- Static Pseudowire

Legend for interface status
Up -- operational
Dn -- down
Neighbor: 192.0.2.3
  Interface          Type St   Time last up   # Up trans
  ge-1/0/0.0(vc 100) rmt  Up    Jan  5 22:00:49 2010    1
  Remote PE: 192.0.2.3, Negotiated control-word: Yes (Null)
  Incoming label: 301328, Outgoing label: 314736
  Local interface: ge-1/0/0.0, Status: Up, Encapsulation: ETHERNET

```

2. On Router PE1, use the `show ldp neighbor` command to verify that the IPv4 address of Router PE3 is shown as the LDP neighbor.

```

user@PE1> show ldp neighbor

Address          Interface      Label space ID      Hold time
192.0.2.3        lo0.0         192.0.2.3:0        41

```

3. On Router PE 1, use the `show route table mpls.0` command to verify the Layer 2 circuit is using the LDP label to Router PE3 in both directions (Push and Pop). In the example below, the Layer 2 circuit is associated with LDP label 301328.

```

user@PE1> show route table mpls.0

mpls.0: 13 destinations, 13 routes (13 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w1d 08:25:39, metric 1
           Receive
1          *[MPLS/0] 1w1d 08:25:39, metric 1
           Receive
2          *[MPLS/0] 1w1d 08:25:39, metric 1
           Receive
300432     *[LDP/9] 3d 01:13:57, metric 1
           > to 10.10.2.2 via xe-0/1/0.0, Pop
300432(S=0) *[LDP/9] 3d 01:13:57, metric 1
           > to 10.10.2.2 via xe-0/1/0.0, Pop
300768     *[LDP/9] 3d 01:13:57, metric 1
           > to 10.10.3.2 via xe-0/2/0.0, Pop
300768(S=0) *[LDP/9] 3d 01:13:57, metric 1
           > to 10.10.3.2 via xe-0/2/0.0, Pop
300912     *[LDP/9] 3d 01:13:57, metric 1
           > to 10.10.3.2 via xe-0/2/0.0, Swap 299856
301264     *[LDP/9] 3d 01:13:53, metric 1
           > to 10.10.1.2 via xe-0/3/0.0, Swap 308224
301312     *[LDP/9] 3d 01:13:56, metric 1
           > to 10.10.1.2 via xe-0/3/0.0, Pop
301312(S=0) *[LDP/9] 3d 01:13:56, metric 1
           > to 10.10.1.2 via xe-0/3/0.0, Pop
301328     *[L2CKT/7] 02:33:26                > via ge-1/0/0.0, Pop      Offset: 4
ge-1/0/0.0  *[L2CKT/7] 02:33:26, metric2 1    > to 10.10.1.2 via xe-0/3/0.0, Push
314736 Offset: -4

```

4. On Router PE3, use the `show l2circuit connections` command to verify that the Layer 2 circuit from Router PE3 to Router PE5 is Up, that the Layer 2 circuit from Router PE3 to Router PE1 is Up, that the

connections to Router PE1 and Router PE5 use the iw0 interface, and that the status for both local iw0 interfaces is Up.

```

user@PE3> show l2circuit connections
Layer-2 Circuit Connections:
Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch      Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad XX -- unknown
SP -- Static Pseudowire

Legend for interface status
Up -- operational
Dn -- down
Neighbor: 192.0.2.1
  Interface          Type  St    Time last up      # Up trans
  iw0.0(vc 100)      rmt   Up    Jan  5 13:50:14 2010      1
  Remote PE: 192.0.2.1, Negotiated control-word: Yes (Null)
  Incoming label: 314736, Outgoing label: 301328
  Local interface: iw0.0, Status: Up, Encapsulation: ETHERNET
Neighbor: 192.0.2.5
  Interface          Type  St    Time last up      # Up trans
  iw0.1(vc 200)      rmt   Up    Jan  5 13:49:58 2010      1
  Remote PE: 192.0.2.5, Negotiated control-word: Yes (Null)
  Incoming label: 314752, Outgoing label: 300208
  Local interface: iw0.1, Status: Up, Encapsulation: ETHERNET

```

5. On Router PE3, use the `show ldp neighbor` command to verify that the correct IPv4 addresses are shown as the LDP neighbor.

```

user@PE3> show ldp neighbor
Address      Interface      Label space ID      Hold time
192.0.2.1    lo0.0          192.0.2.1:0         44
192.0.2.2    lo0.0          192.0.2.2:0         42

```

192.0.2.4	lo0.0	192.0.2.4:0	31
192.0.2.5	lo0.0	192.0.2.5:0	44

6. On Router PE3, use the `show route table mpls.0` command to verify that the `mpls.0` routing table is populated with the Layer 2 interworking routes. Notice that in this example, the router is swapping label 314736 received from Router PE1 on the `iw0.0` to label 301328.

```

user@PE3> show route table mpls.0
mpls.0: 16 destinations, 18 routes (16 active, 2 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w1d 08:28:24, metric 1
            Receive
1          *[MPLS/0] 1w1d 08:28:24, metric 1
            Receive
2          *[MPLS/0] 1w1d 08:28:24, metric 1
            Receive
308160     *[LDP/9] 3d 01:16:55, metric 1
            > to 10.10.1.1 via xe-0/3/0.0, Pop
308160(S=0) *[LDP/9] 3d 01:16:55, metric 1
            > to 10.10.1.1 via xe-0/3/0.0, Pop
308176     *[LDP/9] 3d 01:16:54, metric 1
            > to 10.10.6.2 via xe-0/1/0.0, Pop
308176(S=0) *[LDP/9] 3d 01:16:54, metric 1
            > to 10.10.6.2 via xe-0/1/0.0, Pop
308192     *[LDP/9] 00:21:40, metric 1
            > to 10.10.20.1 via xe-0/0/0.0, Swap 601649
            to 10.10.6.2 via xe-0/1/0.0, Swap 299856
308208     *[LDP/9] 3d 01:16:54, metric 1
            > to 10.10.5.1 via xe-0/2/0.0, Pop
308208(S=0) *[LDP/9] 3d 01:16:54, metric 1
            > to 10.10.5.1 via xe-0/2/0.0, Pop
308224     *[LDP/9] 3d 01:16:52, metric 1
            > to 10.10.20.1 via xe-0/0/0.0, Pop
308224(S=0) *[LDP/9] 3d 01:16:52, metric 1
            > to 10.10.20.1 via xe-0/0/0.0, Pop
314736     *[L2IW/6] 02:35:31, metric2 1
            > to 10.10.6.2 via xe-0/1/0.0, Swap 300208
            [L2CKT/7] 02:35:31
            > via iw0.0, Pop      Offset: 4
314752     *[L2IW/6] 02:35:31, metric2 1
            > to 10.10.1.1 via xe-0/3/0.0, Swap 301328

```

```

                                [L2CKT/7] 02:35:47
                                > via iw0.1, Pop      Offset: 4
iw0.0                          *[L2CKT/7] 02:35:31, metric2 1
                                > to 10.10.1.1 via xe-0/3/0.0, Push 301328 Offset: -4
iw0.1                          *[L2CKT/7] 02:35:47, metric2 1
                                > to 10.10.6.2 via xe-0/1/0.0, Push 300208 Offset: -4

```

7. Verify that Router CE1 can send traffic to and receive traffic from Router CE5 across the interconnection, using the ping command.

```

user@CE1>ping 198.51.100.11
PING 198.51.100.11 (198.51.100.11): 56 data bytes
64 bytes from 198.51.100.11: icmp_seq=1 ttl=64 time=22.425 ms
64 bytes from 198.51.100.11: icmp_seq=2 ttl=64 time=1.299 ms
64 bytes from 198.51.100.11: icmp_seq=3 ttl=64 time=1.032 ms
64 bytes from 198.51.100.11: icmp_seq=4 ttl=64 time=1.029 ms

```

8. Verify that Router CE5 can send traffic to and receive traffic from Router CE1 across the interconnection, using the ping command.

```

user@CE5>ping 198.51.100.1
PING 198.51.100.1 (198.51.100.1): 56 data bytes
64 bytes from 198.51.100.1: icmp_seq=0 ttl=64 time=1.077 ms
64 bytes from 198.51.100.1: icmp_seq=1 ttl=64 time=0.957 ms
64 bytes from 198.51.100.1: icmp_seq=2 ttl=64 time=1.057 ms 1.017 ms

```

Results

The configuration and verification of this example has been completed. The following section is for your reference.

The relevant sample configuration for Router PE1 follows.

Router PE1

```

[edit]
interfaces {
  xe-0/1/0 {
    unit 0 {

```

```

        family inet {
            address 10.10.2.1/30;
        }
        family mpls;
    }
}
xe-0/2/0 {
    unit 0 {
        family inet {
            address 10.10.3..1/30;
        }
        family mpls;
    }
}
xe-0/3/0 {
    unit 0 {
        family inet {
            address 10.10.1.1/30;
        }
        family mpls;
    }
}
ge-1/0/0 {
    encapsulation ethernet-ccc;
    unit 0 {
        family ccc;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.1/24;
        }
    }
}
}
forwarding-options {
    hash-key {
        family inet {
            layer-3;
            layer-4;
        }
        family mpls {

```

```

        label-1;
        label-2;
    }
}
}
routing-options {
    static {
        route 172.16.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    mpls {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    ospf {
        traffic-engineering;
        area 0.0.0.0 {
            interface all;
            interface fxp0.0 {
                disable;
            }
        }
    }
    ldp {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    l2circuit {
        neighbor 192.0.2.3 {
            interface ge-1/0/0.0 {
                virtual-circuit-id 100;
                ignore-mtu-mismatch;
            }
        }
    }
}
}

```

The relevant sample configuration for Router PE3 follows.

Router PE3

```
[edit]
interfaces {
  xe-0/0/0 {
    unit 0 {
      family inet {
        address 10.10.20.2/30;
      }
      family mpls;
    }
  }
  xe-0/1/0 {
    unit 0 {
      family inet {
        address 10.10.6.1/30;
      }
      family mpls;
    }
  }
  xe-0/2/0 {
    unit 0 {
      family inet {
        address 10.10.5.2/30;
      }
      family mpls;
    }
  }
  xe-0/3/0 {
    unit 0 {
      family inet {
        address 10.10.1.2/30;
      }
      family mpls;
    }
  }
  ge-1/0/1 {
    encapsulation ethernet-ccc;
    unit 0 {
      family ccc;
    }
  }
}
```

```

    }
}
iw0 {
    unit 0 {
        encapsulation ethernet-ccc;
        peer-unit 1;
    }
    unit 1 {
        encapsulation ethernet-ccc;
        peer-unit 0;
    }
}
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}
}
routing-options {
    static {
        route 172.16.0.0/8 next-hop 172.19.59.1;
    }
    autonomous-system 65000;
}
protocols {
    l2iw;
    mpls {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    ospf {
        area 0.0.0.0 {
            interface all;
            interface fxp0.0 {
                disable;
            }
        }
    }
}
ldp {

```

```

interface all;
interface fxp0.0 {
    disable;
}
}
l2circuit {
    neighbor 192.0.2.1 {
        interface iw0.0 {
            virtual-circuit-id 100;
            ignore-mtu-mismatch;
        }
    }
    neighbor 192.0.2.5 {
        interface iw0.1 {
            virtual-circuit-id 200;
            ignore-mtu-mismatch;
        }
    }
}
}
}

```

RELATED DOCUMENTATION

| [Applications for Interconnecting a Layer 2 Circuit with a Layer 2 Circuit](#) | 1323

Applications for Interconnecting a Layer 2 Circuit with a Layer 3 VPN

MPLS-based Layer 2 services are growing in demand among enterprise and service providers. This creates new challenges related to interoperability between Layer 2 and Layer 3 services for service providers who want to provide end-to-end value-added services. There are various reasons to stitch different Layer 2 services to one another and to Layer 3 services. For example, to expand the service offerings and to expand geographically. The Junos OS has various features to address the needs of the service provider.

You can enable pseudowire services and configure a pseudowire service interface as an access point for interconnecting layer 2 circuits to layer 3 VPNs. For more information, see [Pseudowire Subscriber Logical Interfaces Overview](#).

Interconnecting a Layer 2 Circuit with a Layer 3 VPN provides the following benefits:

- Interconnecting a Layer 2 Circuit with a Layer 3 VPN enables the sharing of a service provider's core network infrastructure between IP and Layer 2 circuit services, reducing the cost of providing those services. A Layer 2 MPLS circuit allows service providers to create a Layer 2 circuit service over an existing IP and MPLS backbone.
- Service providers do not have to invest in separate Layer 2 equipment to provide Layer 2 circuit service. A service provider can configure a provider edge router to run any Layer 3 protocol in addition to the Layer 2 protocols. Customers who prefer to maintain control over most of the administration of their own networks want Layer 2 circuit connections with their service provider instead of a Layer 3 VPN connection.

Example: Interconnecting a Layer 2 Circuit with a Layer 3 VPN

IN THIS SECTION

- [Requirements | 1358](#)
- [Overview and Topology | 1359](#)
- [Configuration | 1360](#)
- [Verifying the Layer 2 Circuit to Layer 3 VPN Interconnection | 1375](#)

This example provides a step-by-step procedure and commands for configuring and verifying a Layer 2 circuit to Layer 3 VPN interconnection. It contains the following sections:

Requirements

This example uses the following hardware and software components:

- Junos OS Release 9.3 or later
- 3 MX Series 5G Universal Routing Platforms
- 1 M Series Multiservice Edge Router
- 1 T Series Core Router
- 1 EX Series Ethernet Switch


Overview and Topology

IN THIS SECTION

Topology | 1360

The physical topology of a Layer 2 circuit to Layer 3 VPN interconnection is shown in [Figure 91 on page 1359](#).


Figure 91: Physical Topology of a Layer 2 Circuit to Layer 3 VPN Interconnection



g040540

The logical topology of a Layer 2 circuit to Layer 3 VPN interconnection is shown in [Figure 92 on page 1360](#).

Figure 92: Logical Topology of a Layer 2 Circuit to Layer 3 VPN Interconnection



8040544

Topology

Configuration

IN THIS SECTION

- [Configuring PE Router Customer-facing and Loopback Interfaces | 1361](#)
- [Configuring Core-facing Interfaces | 1363](#)
- [Configuring Protocols | 1365](#)
- [Configuring Routing Instances and Layer 2 Circuits | 1369](#)
- [Configuring the Route Reflector | 1371](#)
- [Interconnecting the Layer 2 Circuit with the Layer 3 VPN | 1373](#)

NOTE: In any configuration session, it is good practice to verify periodically that the configuration can be committed using the `commit check` command.

In this example, the router being configured is identified using the following command prompts:

- CE2 identifies the customer edge 2 (CE2) router
- PE1 identifies the provider edge 1 (PE1) router
- CE3 identifies the customer edge 3 (CE3) router
- PE3 identifies the provider edge 3 (PE3) router
- CE5 identifies the customer edge 5 (CE5) router
- PE5 identifies the provider edge 5 (PE5) router

This example contains the following procedures:

Configuring PE Router Customer-facing and Loopback Interfaces

Step-by-Step Procedure

To begin building the interconnection, configure the interfaces on the PE routers. If your network contains provider (P) routers, configure the interfaces on the P routers also. This example shows the configuration for Router PE2, Router PE3, and Router PE5.

1. On Router PE2, configure the `ge-1/0/2` interface encapsulation. To configure the interface encapsulation, include the `encapsulation` statement and specify the `ethernet-ccc` option (`vlan-ccc` encapsulation is also supported). Configure the `ge-1/0/2.0` logical interface family for circuit cross-connect functionality. To configure the logical interface family, include the `family` statement and specify the `ccc` option. The encapsulation should be configured the same way for all routers in the Layer 2 circuit domain.

```
[edit interfaces]
ge-1/0/2 {
  encapsulation ethernet-ccc;
  unit 0 {
    family ccc;
```

```

    }
}

```

2. On Router PE2, configure the `lo0.0` interface. Include the `family` statement and specify the `inet` option. Include the address statement and specify `192.0.2.2/24` as the loopback IPv4 address.

```

[edit interfaces]
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.2/24;
        }
    }
}

```

3. On Router PE3, configure the `ge-1/0/1` interface. Include the `family` statement and specify the `inet` option. Include the address statement and specify `198.51.100.1/24` as the interface address for this device.

```

[edit interfaces]
ge-1/0/1 {
    unit 0 {
        family inet {
            address 198.51.100.1/24;
        }
    }
}

```

4. On Router PE3, configure the `lo0.0` loopback interface. Include the `family` statement and specify the `inet` option. Include the address statement and specify `192.0.2.3/24` as the loopback IPv4 address for this router.

```

[edit interfaces]
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.3/24;
        }
    }
}

```

```

    }
}

```

5. On Router PE5, configure the ge-2/0/0 interface. Include the family statement and specify the inet option. Include the address statement and specify 198.51.100.8/24 as the interface address.

```

[edit interfaces]
ge-2/0/0 {
    unit 0 {
        family inet {
            address 198.51.100.8/24;
        }
    }
}

```

6. On Router PE5, configure the lo0.0 interface. Include the family statement and specify the inet option. Include the address statement and specify 192.0.2.5/24 as the loopback IPv4 address for this router.

```

[edit interfaces]
lo0 {
    unit 0 {
        family inet {
            address 192.0.2.5/24;
        }
    }
}

```

Configuring Core-facing Interfaces

Step-by-Step Procedure

This procedure describes how to configure the core-facing interfaces on the PE routers. This example does not include all the core-facing interfaces shown in the physical topology illustration. Enable the `mpls` and `inet` address families on the core-facing interfaces.

1. On Router PE2, configure the xe-0/2/0 interface. Include the family statement and specify the inet address family. Include the address statement and specify 10.10.5.1/30 as the interface address. Include the family statement and specify the mpls address family.

```
[edit interfaces]
xe-0/2/0 {
  unit 0 {
    family inet {
      address 10.10.5.1/30;
    }
    family mpls;
  }
}
```

2. On Router PE3, configure the core-facing interfaces. Include the family statement and specify the inet address family. Include the address statement and specify the IPv4 addresses shown in the example as the interface addresses. Include the family statement and specify the mpls address family. In the example, the xe-2/1/0 interface is connected to Router PE5, and the xe-2/2/0 interface is connected to Router PE2.

```
[edit interfaces]
xe-2/0/0 {
  unit 0 {
    family inet {
      address 10.10.20.2/30;
    }
    family mpls;
  }
}
xe-2/1/0 {
  unit 0 {
    family inet {
      address 10.10.6.1/30;
    }
    family mpls;
  }
}
xe-2/2/0 {
  unit 0 {
    family inet {
      address 10.10.5.2/30;
```

```

    }
    family mpls;
  }
}
xe-2/3/0 {
  unit 0 {
    family inet {
      address 10.10.1.2/30;
    }
    family mpls;
  }
}

```

3. On Router PE5, configure the `xe-0/1/0` interface. Include the `family` statement and specify the `inet` address family. Include the address statement and specify `10.10.6.2/30` as the interface address. Include the `family` statement and specify the `mpls` address family.

```

[edit interfaces]
xe-0/1/0 {
  unit 0 {
    family inet {
      address 10.10.6.2/30;
    }
    family mpls;
  }
}

```

Configuring Protocols

Step-by-Step Procedure

This procedure describes how to configure the protocols used in this example. If your network contains P routers, configure the interfaces on the P routers also.

1. On Router PE3, enable OSPF as the IGP. Enable the MPLS, LDP, and BGP protocols on all interfaces except fxp0.0. LDP is used as the signaling protocol for the Layer 2 circuit to Router PE2 . The following configuration snippet shows the protocol configuration for Router PE3:

```
[edit]
protocols {
  rsvp {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  mpls {
    label-switched-path to-RR {
      to 192.0.2.7;
    }
    label-switched-path to-PE2 {
      to 192.0.2.2;
    }
    label-switched-path to-PE5 {
      to 192.0.2.5;
    }
    label-switched-path to-PE4 {
      to 192.0.2.4;
    }
    label-switched-path to-PE1 {
      to 192.0.2.1;
    }
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  bgp {
    group RR {
      type internal;
      local-address 192.0.2.3;
      family inet-vpn {
        unicast;
      }
      family l2vpn {
        signaling;
      }
    }
  }
}
```

```

    }
    neighbor 192.0.2.7;
  }
}
ospf {
  traffic-engineering;
  area 0.0.0.0 {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
}
ldp {
  interface all;
  interface fxp0.0 {
    disable;
  }
}
}

```

2. On Router PE2, configure the MPLS, OSPF, and LDP protocols.

```

[edit ]
protocols {
  mpls {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  ospf {
    traffic-engineering;
    area 0.0.0.0 {
      interface all;
      interface fxp0.0 {
        disable;
      }
    }
  }
}
ldp {
  interface all;

```

```

        interface fxp0.0 {
            disable;
        }
    }
}

```

3. On Router PE5, enable OSPF as the IGP. Enable the MPLS, RSVP, and BGP protocols on all interfaces except `fxp0.0`. Enable core-facing interfaces with the `mpls` and `inet` address families.

```

[edit]
protocols {
    rsvp {
        interface all {
            link-protection;
        }
        interface fxp0.0 {
            disable;
        }
    }
    mpls {
        label-switched-path to-RR {
            to 192.0.2.7;
        }
        label-switched-path to-PE2 {
            to 192.0.2.2;
        }
        label-switched-path to-PE3 {
            to 192.0.2.3;
        }
        label-switched-path to-PE4 {
            to 192.0.2.4;
        }
        label-switched-path to-PE1 {
            to 192.0.2.1;
        }
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
    bgp {
        group to-rr {

```

```

        type internal;
        local-address 192.0.2.5;
        family inet-vpn {
            unicast;
        }
        family l2vpn {
            signaling;
        }
        neighbor 192.0.2.7;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
}

```

Configuring Routing Instances and Layer 2 Circuits

Step-by-Step Procedure

This procedure describes how to configure the Layer 2 circuit and the Layer 3 VPN.

1. On Router PE2, configure the Layer 2 circuit. Include the `l2circuit` statement. Include the `neighbor` statement and specify the loopback IPv4 address of Router PE3 as the neighbor. Include the `interface` statement and specify `ge-1/0/2.0` as the logical interface that is participating in the Layer 2 circuit. Include the `virtual-circuit-id` statement and specify `100` as the identifier. Include the `no-control-word` statement for equipment that does not support the control word.

```

[edit ]
protocols {
    l2circuit {
        neighbor 192.0.2.3 {
            interface ge-1/0/2.0 {
                virtual-circuit-id 100;
                no-control-word;
            }
        }
    }
}

```

```

    }
  }
}

```

2. On Router PE3, configure the Layer 2 circuit to Router PE2. Include the `l2circuit` statement. Include the `neighbor` statement and specify the loopback IPv4 address of Router PE2 as the neighbor. Include the `interface` statement and specify `lt-1/1/10.0` as the logical tunnel interface that is participating in the Layer 2 circuit. Include the `virtual-circuit-id` statement and specify `100` as the identifier. Include the `no-control-word` statement.

```

[edit ]
protocols {
  l2circuit {
    neighbor 192.0.2.2 {
      interface lt-1/1/10.0 {
        virtual-circuit-id 100;
        no-control-word;
      }
    }
  }
}

```

3. On Router PE3, configure the Layer 3 VPN (L3VPN) routing instance to Router PE5 at the `[edit routing-instances]` hierarchy level. Also configure the BGP peer group at the `[edit routing-instances L3VPN protocols]` hierarchy level.

```

[edit ]
routing-instances {
  L3VPN {
    instance-type vrf;
    interface ge-1/0/1.0;
    interface lt-1/1/10.1;
    route-distinguisher 65000:33;
    vrf-target target:65000:2;
    vrf-table-label;
    protocols {
      bgp {
        export direct;
        group ce3 {
          neighbor 198.51.100.6{

```

```

    peer-as 100;
  }
}
}
}
}
}
}

```

4. On Router PE5, configure the Layer 3 VPN routing instance (L3VPN) at the [edit routing-instances] hierarchy level. Also configure the BGP peer group at the [edit routing-instances L3VPN protocols] hierarchy level.

```

[edit ]
routing-instances {
  L3VPN {
    instance-type vrf;
    interface ge-2/0/0.0;
    route-distinguisher 65000:5;
    vrf-target target:65000:2;
    vrf-table-label;
    protocols {
      bgp {
        group ce5 {
          neighbor 198.51.100.10 {
            peer-as 200;
          }
        }
      }
    }
  }
}
}

```

Configuring the Route Reflector

Step-by-Step Procedure

Although a route reflector is not required to interconnect a Layer 2 circuit with a Layer 3 VPN, this example uses a route reflector. This procedure shows the relevant portion of the route reflector configuration.

1. Configure the route reflector with RSVP, MPLS, BGP and OSPF. The route reflector is a BGP peer with the PE routers. Notice that the BGP peer group configuration includes the `family` statement and specifies the `inet-vpn` option. The `inet-vpn` option enables BGP to advertise network layer reachability information (NLRI) for the Layer 3 VPN routes. The configuration also includes the `family` statement and specifies the `l2vpn` option. The `l2vpn` option enables BGP to advertise NLRI for the Layer 2 circuit. Layer 2 circuits use the same internal BGP infrastructure as Layer 2 VPNs.

```
[edit ]
protocols {
  rsvp {
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  mpls {
    label-switched-path to-pe3 {
      to 192.0.2.3;
    }
    label-switched-path to-pe5 {
      to 192.0.2.5;
    }
    interface all;
    interface fxp0.0 {
      disable;
    }
  }
  bgp {
    group RR {
      type internal;
      local-address 192.0.2.7;
      family inet {
        unicast;
      }
      family inet-vpn {
        unicast;
      }
      family l2vpn {
        signaling;
      }
      cluster 192.0.2.7;
      neighbor 192.0.2.1;
```

```

        neighbor 192.0.2.2;
        neighbor 192.0.2.4;
        neighbor 192.0.2.5;
        neighbor 192.0.2.3;
    }
}
ospf {
    traffic-engineering;
    area 0.0.0.0 {
        interface all;
        interface fxp0.0 {
            disable;
        }
    }
}
}
}

```

Interconnecting the Layer 2 Circuit with the Layer 3 VPN

Step-by-Step Procedure

Before you can configure the logical tunnel interface in an MX Series router, you must create the tunnel services interface to be used for tunnel services.

1. Create the tunnel service interface on Router PE3. Include the bandwidth statement at the [edit chassis fpc *slot-number* pic *slot-number* tunnel-services] hierarchy level and specify the amount of bandwidth to reserve for tunnel services in gigabits per second.

```

[edit chassis]
fpc 1 {
    pic 1 {
        tunnel-services {
            bandwidth 1g;
        }
    }
}
}

```

2. On Router PE3, configure the lt-1/1/10 logical tunnel interface unit 0.

Router PE3 is the router that is *stitching* the Layer 2 circuit to the Layer 3 VPN using the logical tunnel interface. The configuration of the peer unit interfaces is what makes the interconnection.

Include the encapsulation statement and specify the ethernet-ccc option. Include the peer-unit statement and specify the logical interface unit 1 as the peer tunnel interface. Include the family statement and specify the ccc option.

Configure the lt-1/1/10 logical interface unit 1 with ethernet encapsulation. Include the peer-unit statement and specify the logical interface unit 0 as the peer tunnel interface. Include the family statement and specify the inet option. Also include the address statement and specify 198.51.100.11/24 as the IPv4 address of the interface.

NOTE: The peering logical interfaces must belong to the same logical tunnel interface derived from the Tunnel Services PIC.

```
[edit interfaces]
lt-1/1/10 {
  unit 0 {
    encapsulation ethernet-ccc;
    peer-unit 1;
    family ccc;
  }
  unit 1 {
    encapsulation ethernet;
    peer-unit 0;
    family inet {
      address 198.51.100.11/24;
    }
  }
}
```

3. On each router, commit the configuration.

```
user@host> commit check
configuration check succeeds
user@host> commit
```

Verifying the Layer 2 Circuit to Layer 3 VPN Interconnection

IN THIS SECTION

- [Verifying That the Layer 2 Circuit Connection to Router PE3 is Up | 1375](#)
- [Verifying LDP Neighbors and Targeted LDP LSPs on Router PE2 | 1376](#)
- [Verifying the Layer 2 Circuit Routes on Router PE2 | 1377](#)
- [Verifying That the Layer 2 Circuit Connection to Router PE2 is Up | 1378](#)
- [Verifying LDP Neighbors and Targeted LDP LSPs on Router PE3 | 1379](#)
- [Verifying a BGP Peer Session with the Route Reflector on Router PE3 | 1380](#)
- [Verifying the Layer 3 VPN Routes on Router PE3 | 1380](#)
- [Verifying the Layer 2 Circuit Routes on Router PE3 | 1381](#)
- [Verifying the MPLS Routes on Router PE3 | 1382](#)
- [Verifying Traffic Flow Between Router CE2 and Router CE3 | 1384](#)
- [Verifying Traffic Flow Between Router CE2 and Router CE5 | 1385](#)

To verify that the interconnection is working properly, perform these tasks:

Verifying That the Layer 2 Circuit Connection to Router PE3 is Up

Purpose

To verify that the Layer 2 circuit connection from Router PE2 to Router PE3 is up. To also document the incoming and outgoing LDP labels and the circuit ID used by this Layer 2 circuit connection.

Action

Verify that the Layer 2 circuit connection is up, using the `show l2circuit connections` command.

```
user@PE2> show l2circuit connections
Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch      Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
```

```

OL -- no outgoing label      IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC  TM -- TDM misconfiguration
BK -- Backup Connection      ST -- Standby Connection
CB -- rcvd cell-bundle size bad SP -- Static Pseudowire
LD -- local site signaled down RS -- remote site standby
RD -- remote site signaled down XX -- unknown

```

Legend for interface status

Up -- operational

Dn -- down

Neighbor: 192.0.2.3

Interface	Type	St	Time last up	# Up trans
ge-1/0/2.0(vc 100)	rmt	Up	Jan 7 02:14:13 2010	1

Remote PE: 192.0.2.3, Negotiated control-word: No

Incoming label: 301488, Outgoing label: 315264

Negotiated PW status TLV: No

Local interface: ge-1/0/2.0, Status: Up, Encapsulation: ETHERNET

Meaning

The output shows that the Layer 2 circuit connection from Router PE2 to Router PE3 is Up and the connection is using the ge-1/0/2.0 interface. Note that the outgoing label is 315264 and the incoming label is 301488, the virtual circuit (VC) identifier is 100 and the encapsulation is ETHERNET.

Verifying LDP Neighbors and Targeted LDP LSPs on Router PE2

Purpose

To verify that Router PE2 has a targeted LDP LSP to Router PE3 and that Router PE2 and Router PE3 are LDP neighbors.

Action

Verify that Router PE2 has a targeted LDP LSP to Router PE3 and that Router PE2 and Router PE3 are LDP neighbors, using the show ldp neighbor command.

```
user@PE2> show ldp neighbor
```

Address	Interface	Label space ID	Hold time
192.0.2.3	lo0.0	192.0.2.3:0	38

Meaning

The output shows that Router PE2 has an LDP neighbor with the IPv4 address of 192.0.2.3. Address 192.0.2.3 is the lo0.0 interface address of Router PE3. Notice that Router PE2 uses the local lo0.0 interface for the LSP.

Verifying that the routers are LDP neighbors also verifies that the targeted LSP is established.

Verifying the Layer 2 Circuit Routes on Router PE2

Purpose

To verify that Router PE2 has a route for the Layer 2 circuit and that the route uses the LDP MPLS label to Router PE3.

Action

Verify that Router PE2 has a route for the Layer 2 circuit and that the route uses the LDP MPLS label to Router PE3, using the `show route table mpls.0` command.

```
user@PE2> show route table mpls.0
mpls.0: 13 destinations, 13 routes (13 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w3d 05:24:11, metric 1
            Receive
1          *[MPLS/0] 1w3d 05:24:11, metric 1
            Receive
2          *[MPLS/0] 1w3d 05:24:11, metric 1
            Receive
300560     *[LDP/9] 16:12:23, metric 1
            > to 10.10.2.1 via xe-0/1/0.0, Pop
300560(S=0) *[LDP/9] 16:12:23, metric 1
            > to 10.10.2.1 via xe-0/1/0.0, Pop
301008     *[LDP/9] 16:12:23, metric 1
            > to 10.10.4.2 via xe-0/3/0.0, Swap 299856
301488     *[L2CKT/7] 11:07:28
            > via ge-1/0/2.0, Pop
301536     *[LDP/9] 16:12:23, metric 1
            > to 10.10.4.2 via xe-0/3/0.0, Pop
301536(S=0) *[LDP/9] 16:12:23, metric 1
            > to 10.10.4.2 via xe-0/3/0.0, Pop
```

```

301712          *[LDP/9] 12:41:22, metric 1
                > to 10.10.5.2 via xe-0/2/0.0, Swap 315184
301728          *[LDP/9] 12:41:22, metric 1
                > to 10.10.5.2 via xe-0/2/0.0, Pop
301728(S=0)     *[LDP/9] 12:41:22, metric 1
                > to 10.10.5.2 via xe-0/2/0.0, Pop
ge-1/0/2.0      *[L2CKT/7] 11:07:28, metric2 1
                > to 10.10.5.2 via xe-0/2/0.0, Push 315264

```

Meaning

The output shows that Router PE2 pushes the 315264 outgoing label on the L2CKT route going out interface ge-1/0/2.0. The output also shows that Router PE2 pops the 301488 incoming label on the L2CKT coming from interface ge-1/0/2.0

Verifying That the Layer 2 Circuit Connection to Router PE2 is Up

Purpose

To verify that the Layer 2 circuit connection from Router PE3 to Router PE2 is Up, To also document the incoming and outgoing LDP labels and the circuit ID used by this Layer 2 circuit connection.

Action

Verify that the Layer 2 circuit connection is up, using the `show l2circuit connections` command.

```

user@PE3> show l2circuit connections
Layer-2 Circuit Connections:
Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch     Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad XX -- unknown

Legend for interface status
Up -- operational

```

```

Dn -- down
Neighbor: 192.0.2.2
  Interface          Type  St    Time last up      # Up trans
  lt-1/1/10.0(vc 100)  rmt   Up    Jan  7 02:15:03 2010      1
  Remote PE: 192.0.2.2, Negotiated control-word: No
  Incoming label: 315264, Outgoing label: 301488
  Local interface: lt-1/1/10.0, Status: Up, Encapsulation: ETHERNET

```

Meaning

The output shows that the Layer 2 circuit connection from Router PE3 to Router PE2 is Up and the connection is using the logical tunnel (lt) interface. Note that the incoming label is 315264 and the outgoing label is 301488, the virtual circuit (VC) identifier is 100, and that the encapsulation is ETHERNET.

Verifying LDP Neighbors and Targeted LDP LSPs on Router PE3

Purpose

To verify that Router PE3 has a targeted LDP LSP to Router PE2 and that Router PE3 and Router PE2 are LDP neighbors.

Action

Verify that Router PE2 has a targeted LDP LSP to Router PE3 and that Router PE2 and Router PE3 are LDP neighbors, using the `show ldp neighbor` command.

```

user@PE2> show ldp neighbor
Address      Interface      Label space ID      Hold time
192.0.2.2    lo0.0          192.0.2.2:0         43
192.0.2.4    lo0.0          192.0.2.4:0         33

```

Meaning

The output shows that Router PE3 has an LDP neighbor with the IPv4 address of 192.0.2.2. Address 192.0.2.2 is the lo0.0 interface address of Router PE2. The output also shows that the interface used on Router PE3 for the LSP is lo0.0. Verifying that the routers are LDP neighbors also verifies that the targeted LSP is established.

Verifying a BGP Peer Session with the Route Reflector on Router PE3

Purpose

To verify that Router PE3 has a peer session established with the route reflector.

Action

Verify that Router PE3 has a peer session established with the route reflector, using the `show bgp summary` command.

```
user@PE2> show bgp summary
Groups: 2 Peers: 2 Down peers: 0
Table          Tot Paths  Act Paths Suppressed    History  Damp State   Pending
bgp.l3vpn.0          1          1          0          0          0          0
Peer              AS      InPkt    OutPkt    OutQ   Flaps Last Up/Dwn State|#Active/
Received/Accepted/Damped...
192.0.2.7          65000      1597      1612        0        1   12:03:21 Establ
  bgp.l2vpn.0: 0/0/0/0
  bgp.l3vpn.0: 1/1/1/0
  L3VPN.inet.0: 1/1/1/0
```

Meaning

The output shows that Router PE3 has a peer session with the router with the IPv4 address of 192.0.2.7. Address 192.0.2.7 is the lo0.0 interface address of the route reflector. The output also shows that the peer session state is Establ, meaning that the session is established.

Verifying the Layer 3 VPN Routes on Router PE3

Purpose

To verify that Router PE3 has Layer 3 VPN routes to Router CE2, Router CE3, and Router CE5.

Action

Verify that Router PE3 has routes to Router CE2, Router CE3, and Router CE5 in the Layer 3 VPN route table, using the `show route table L3VPN.inet.0` command. In this example, L3VPN is the name configured for the routing instance.

```
user@PE3> show route table L3VPN.inet.0
L3VPN.inet.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

198.51.100.10/24    *[Direct/0] 11:13:59
                  > via lt-1/1/10.1
198.51.100.11/24    *[Local/0] 11:13:59
                  Local via lt-1/1/10.1
198.51.100.12/24    *[BGP/170] 11:00:41, localpref 100, from 192.0.2.7
                  AS path: I
                  > to 10.10.6.2 via xe-2/1/0.0, Push 16
198.51.100.13/24    *[Direct/0] 11:54:41
                  > via ge-1/0/1.0
198.51.100.1/24     *[Local/0] 11:54:41
                  Local via ge-1/0/1.0
```

Meaning

The output shows that Router PE3 has a route to the IPv4 subnetwork address of 198.51.100.10. Address 198.51.100.15 is the interface address of Router CE2. The output shows that Router PE3 has a route to the IPv4 subnetwork address of 198.51.100.12. Address 198.51.100.10 is the interface address of Router CE5. The output shows that Router PE3 has a route to the IPv4 subnetwork address of 198.51.100.13. Address 198.51.100.6 is the interface address of Router CE3.

Verifying the Layer 2 Circuit Routes on Router PE3

Purpose

To verify that Router PE3 has a route to Router PE2 in the Layer 2 circuit route table.

Action

Verify that Router PE3 has a route to Router PE2 in the Layer 2 circuit route table, using the `show route table l2circuit.0` command.

```
user@PE3> show route table l2circuit.0
192.0.2.2:NoCtrlWord:5:100:Local/96 (1 entry, 1 announced)
  *L2CKT Preference: 7
    Next hop type: Indirect
    Next-hop reference count: 1
    Next hop type: Router
    Next hop: 10.10.5.1 via xe-2/2/0.0, selected
    Protocol next hop: 192.0.2.2
    Indirect next hop: 8cae0a0 -
    State: <Active Int>
    Local AS: 65000
    Age: 11:16:50 Metric2: 1
    Task: l2 circuit
    Announcement bits (1): 0-LDP
    AS path: I
    VC Label 315264, MTU 1500
```

Meaning

The output shows that Router PE3 has a route to the IPv4 address of 192.0.2.2. Address 192.0.2.2 is the lo0.0 interface address of Router PE2. Note that the VC label is 315264. This label is the same as the incoming MPLS label displayed using the `show l2circuit connections` command.

Verifying the MPLS Routes on Router PE3

Purpose

To verify that Router PE3 has a route to Router PE2 in the MPLS route table.

Action

Verify Router PE3 has a route to Router PE2 in the MPLS route table, using the `show route table mpls.0` command.

```
user@PE3> show route table mpls.0
mpls.0: 21 destinations, 21 routes (21 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

0          *[MPLS/0] 1w3d 05:29:02, metric 1
           Receive
1          *[MPLS/0] 1w3d 05:29:02, metric 1
           Receive
2          *[MPLS/0] 1w3d 05:29:02, metric 1
           Receive
16         *[VPN/0] 12:22:45
           to table L3VPN.inet.0, Pop
315184     *[LDP/9] 12:45:14, metric 1
           > to 10.10.20.1 via xe-2/0/0.0, Pop
315184(S=0) *[LDP/9] 12:45:14, metric 1
           > to 10.10.20.1 via xe-2/0/0.0, Pop
315200     *[LDP/9] 00:03:53, metric 1
           > to 10.10.20.1 via xe-2/0/0.0, Swap 625297
           to 10.10.6.2 via xe-2/1/0.0, Swap 299856
315216     *[LDP/9] 12:45:14, metric 1
           > to 10.10.6.2 via xe-2/1/0.0, Pop
315216(S=0) *[LDP/9] 12:45:14, metric 1
           > to 10.10.6.2 via xe-2/1/0.0, Pop
315232     *[LDP/9] 12:45:06, metric 1
           > to 10.10.1.1 via xe-2/3/0.0, Pop
315232(S=0) *[LDP/9] 12:45:06, metric 1
           > to 10.10.1.1 via xe-2/3/0.0, Pop
315248     *[LDP/9] 12:45:14, metric 1
           > to 10.10.5.1 via xe-2/2/0.0, Pop
315248(S=0) *[LDP/9] 12:45:14, metric 1
           > to 10.10.5.1 via xe-2/2/0.0, Pop
315264     *[L2CKT/7] 11:11:20
           > via lt-1/1/10.0, Pop
315312     *[RSVP/7] 11:26:01, metric 1
           > to 10.10.6.2 via xe-2/1/0.0, label-switched-path to-pe5
315312(S=0) *[RSVP/7] 11:26:01, metric 1
           > to 10.10.6.2 via xe-2/1/0.0, label-switched-path to-pe5
```

```

315328      *[RSVP/7] 11:26:01, metric 1
             > to 10.10.20.1 via xe-2/0/0.0, label-switched-path to-RR
315360      *[RSVP/7] 11:26:01, metric 1
             > to 10.10.20.1 via xe-2/0/0.0, label-switched-path to-RR
316208      *[RSVP/7] 00:03:32, metric 1
             > to 10.10.6.2 via xe-2/1/0.0, label-switched-path Bypass->10.10.9.1
316208(S=0) *[RSVP/7] 00:03:32, metric 1
             > to 10.10.6.2 via xe-2/1/0.0, label-switched-path Bypass->10.10.9.1
1t-1/1/10.0 *[L2CKT/7] 11:11:20, metric2 1
             > to 10.10.5.1 via xe-2/2/0.0, Push 301488

```

Meaning

The output shows that Router PE3 has a route for the Layer 2 circuit and that the route uses the LDP MPLS label to Router PE2. Notice that the 301488 label is the same as the outgoing label displayed on Router PE2 using the `show l2circuit connections` command.

Verifying Traffic Flow Between Router CE2 and Router CE3

Purpose

To verify that the CE routers can send and receive traffic across the interconnection.

Action

Verify that Router CE2 can send traffic to and receive traffic from Router CE3 across the interconnection, using the `ping` command.

```

user@CE2>ping 198.51.100.6
PING 198.51.100.6 (198.51.100.6): 56 data bytes
64 bytes from 198.51.100.6: icmp_seq=0 ttl=63 time=0.708 ms
64 bytes from 198.51.100.6: icmp_seq=1 ttl=63 time=0.610 ms

```

Meaning

The output shows that Router CE2 can send an ICMP request to and receive a response from Router CE3 across the interconnection.

Verifying Traffic Flow Between Router CE2 and Router CE5

Purpose

To verify that the CE routers can send and receive traffic across the interconnection.

Action

Verify that Router CE2 can send traffic to and receive traffic from Router CE5 across the interconnection, using the ping command.

```
user@CE2>ping 198.51.100.10
PING 198.51.100.10 (198.51.100.10): 56 data bytes
64 bytes from 198.51.100.10: icmp_seq=0 ttl=62 time=0.995 ms
64 bytes from 198.51.100.10: icmp_seq=1 ttl=62 time=1.005 ms
```

Meaning

The output shows that Router CE2 can send an ICMP request to and receive a response from Router CE5 across the interconnection.

9

PART

Configuration Statements and Operational Commands

[Configuration Statements \(All VPNs\) | 1387](#)

[Configuration Statements \(Layer 2 VPNs and VPLS\) | 1428](#)

[Operational Commands | 1728](#)

Configuration Statements (All VPNs)

IN THIS CHAPTER

- `aggregate-label` | 1388
- `backup-neighbor` | 1389
- `description` (Routing Instances) | 1391
- `family route-target` | 1392
- `graceful-restart` (Enabling Globally) | 1394
- `instance-type` | 1397
- `interface` (Routing Instances) | 1400
- `no-forwarding` | 1402
- `forward-policy-mismatch` (Security Group VPN Member) | 1403
- `proxy-generate` | 1404
- `revert-time` (Protocols Layer 2 Circuits) | 1406
- `route-distinguisher` | 1409
- `route-distinguisher-id` | 1412
- `route-target-filter` | 1414
- `switchover-delay` | 1416
- `unicast-reverse-path` | 1417
- `vpn-apply-export` | 1419
- `vrf-export` | 1420
- `vrf-import` | 1422
- `vrf-mtu-check` | 1424
- `vrf-target` | 1425

aggregate-label

IN THIS SECTION

- [Syntax | 1388](#)
- [Hierarchy Level | 1388](#)
- [Description | 1388](#)
- [Options | 1389](#)
- [Required Privilege Level | 1389](#)
- [Release Information | 1389](#)

Syntax

```
aggregate-label {  
    community community-name;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols bgp family inet labeled-unicast],  
[edit logical-systems logical-system-name protocols bgp family inet6 labeled-unicast],  
[edit logical-systems logical-system-name protocols bgp family inet-vpn unicast],  
[edit logical-systems logical-system-name protocols bgp family inet-vpn6 unicast],  
[edit protocols bgp family inet labeled-unicast],  
[edit protocols bgp family inet6 labeled-unicast],  
[edit protocols bgp family inet-vpn unicast],  
[edit protocols bgp family inet6-vpn unicast]
```

Description

Specify matching criteria (in the form of a community) such that all routes which match are assigned the same VPN label, selected from one of the several routes in the set defined by this criteria. This reduces the number of VPN labels that the router must consider, and aggregates the received labels.

Options

`community community-name`—Specify the name of the community to which to apply the aggregate label.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| *Configuring Aggregate Labels for VPNs*

backup-neighbor

IN THIS SECTION

- [Syntax | 1389](#)
- [Hierarchy Level | 1390](#)
- [Description | 1390](#)
- [Options | 1390](#)
- [Required Privilege Level | 1391](#)
- [Release Information | 1391](#)

Syntax

```
backup-neighbor address {
  community name;
  mtu number;
```



```

hot-standby;
psn-tunnel-endpoint address;
standby;
static;
virtual-circuit-id number;
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address],
[edit protocols l2circuit local-switching interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name],
[edit routing-instances routing-instance-name protocols vpls neighbor address]

```

Description

Configure pseudowire redundancy for Layer 2 circuits and VPLS. A redundant pseudowire can act as a backup connection and can be configured between a PE router and a CE device or between PE routers, maintaining Layer 2 circuit and VPLS services after certain types of failures. This feature can help improve the reliability of certain types of networks where a single point of failure could interrupt service for customers.

NOTE: VPLS is not supported on ACX Series routers. The `psn-tunnel-endpoint` statement is not supported at the `[edit protocols l2circuit local-switching interface interface-name end-interface interface interface-name]` hierarchy level.

Options

address—Specifies the address for the backup neighbor.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.2.

RELATED DOCUMENTATION

Configuring Pseudowire Redundancy on the PE Router 226
Example: Configuring Layer 2 Circuit Switching Protection 461
community (Protocols Layer 2 Circuit) 1448
psn-tunnel-endpoint 1645
virtual-circuit-id 1700

description (Routing Instances)

IN THIS SECTION

- [Syntax | 1391](#)
- [Hierarchy Level | 1392](#)
- [Description | 1392](#)
- [Required Privilege Level | 1392](#)
- [Release Information | 1392](#)

Syntax

```
description text;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],  
[edit routing-instances routing-instance-name]
```

Description

Provide a text description for the routing instance. If the text includes one or more spaces, enclose it in quotation marks (" "). Any descriptive text you include is displayed in the output of the `show route instance detail` command and has no effect on the operation of the routing instance.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

family route-target

IN THIS SECTION

- [Syntax | 1393](#)
- [Hierarchy Level | 1393](#)
- [Description | 1393](#)
- [Options | 1393](#)
- [Required Privilege Level | 1394](#)
- [Release Information | 1394](#)

Syntax

```
family route-target {
    advertise-default;
    external-paths number;
    prefix-limit number;
    proxy-generate <route-target-policy route-target-policy-name>;
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols bgp group group-name],
[edit logical-systems logical-system-name protocols bgp group group-name neighbor address],
[edit protocols bgp group group-name],
[edit protocols bgp group group-name neighbor address]
```

Description

Enable BGP route target filtering on the VPN.

The family `route-target` statement is useful for filtering VPN routes before they are sent. Provider edge (PE) routers inform the route reflector (RR) which routes to send, using family `route-target` to provide the route-target-interest information. The RR then sends to the PE router only the advertisements containing the specified route target.

Options

`advertise-default`—Cause the router to advertise the default route target route (0:0:0/0) and suppress all routes that are more specific. This can be used by a route reflector on BGP groups consisting of neighbors that act as provider edge (PE) routers only. PE routers often need to advertise all routes to the route reflector. Suppressing all route target advertisements other than the default route reduces the amount of information exchanged between the route reflector and the PE routers. The Junos OS further helps to reduce route target advertisement overhead by not maintaining dependency information unless a nondefault route is received.

`external-paths number`—Cause the router to advertise the VPN routes that reference a given route target. The number you specify with the `external-paths` statement determines the number of external peer routers (currently advertising that route target) that receive the VPN routes. The default value is 1.

`prefix-limit number`—The number of prefixes that can be received from a peer router.

The remaining statement is described separately.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Configuring BGP Route Target Filtering for VPNs

Understanding Proxy BGP Route Target Filtering for VPNs

Example: Configuring an Export Policy for BGP Route Target Filtering for VPNs

graceful-restart (Enabling Globally)

IN THIS SECTION

- [Syntax | 1395](#)
- [Hierarchy Level | 1395](#)
- [Description | 1395](#)
- [Default | 1396](#)
- [Options | 1396](#)
- [Required Privilege Level | 1396](#)
- [Release Information | 1396](#)

Syntax

```
graceful-restart {  
    disable;  
    helper-disable;  
    maximum-helper-recovery-time seconds;  
    maximum-helper-restart-time seconds;  
    notify-duration seconds;  
    recovery-time seconds;  
    restart-duration seconds;  
    stale-routes-time seconds;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options],  
[edit logical-systems logical-system-name routing-instances routing-instance-name routing-  
options],  
[edit routing-options],  
[edit routing-instances routing-instance-name routing-options]
```

Description

You configure the graceful restart routing option globally to enable the feature, but not to enable graceful restart for all routing protocols in a routing instance. To enable graceful restart globally, include the graceful-restart statement under the [edit routing options] hierarchy level. This enables graceful restart globally for all routing protocols. You can, optionally, modify the global settings at the individual protocol level.

NOTE:

- For VPNs, the graceful-restart statement allows a router whose VPN control plane is undergoing a restart to continue to forward traffic while recovering its state from neighboring routers.
- For BGP, if you configure graceful restart after a BGP session has been established, the BGP session restarts and the peers negotiate graceful restart capabilities.

- LDP sessions flap when graceful-restart configurations change.

Default

Graceful restart is disabled by default.

Options

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Enabling Graceful Restart](#)

[Configuring Routing Protocols Graceful Restart](#)

[Configuring Graceful Restart for MPLS-Related Protocols](#)

[Configuring VPN Graceful Restart](#)

[Configuring Logical System Graceful Restart](#)

[Configuring Graceful Restart for QFabric Systems](#)

instance-type

IN THIS SECTION

- [Syntax | 1397](#)
- [Hierarchy Level | 1397](#)
- [Description | 1397](#)
- [Options | 1398](#)
- [Required Privilege Level | 1399](#)
- [Release Information | 1399](#)

Syntax

```
instance-type type;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],  
[edit routing-instances routing-instance-name]
```

Description

Define the type of routing instance.



CAUTION: We strongly recommend that if you change an instance-type referenced under a firewall filter, for example, from virtual-router to forwarding, make the change during a maintenance window, as follows:

1. Deactivate the routing instance.
2. Change the instance-type.

3. Activate the routing instance.

This is not required if you are configuring the `instance-type` for the first time.

Options

NOTE: On ACX Series routers, you can configure only the forwarding, virtual router, and VRF routing instances.

type—Can be one of the following:

- `evpn`—Enable an Ethernet VPN (EVPN) on the routing instance.
- `evpn-vpws`—Enable an Ethernet VPN (EVPN) Virtual Private Wire Service (VPWS) on the routing instance.
- `forwarding`—Provide support for filter-based forwarding, where interfaces are not associated with instances. All interfaces belong to the default instance. Other instances are used for populating RPD learned routes. For this instance type, there is no one-to-one mapping between an interface and a routing instance. All interfaces belong to the default instance `inet.0`.
- `l2backhaul-vpn`—Provide support for Layer 2 wholesale VLAN packets with no existing corresponding logical interface. When using this instance, the router learns both the outer tag and inner tag of the incoming packets, when the `instance-role` statement is defined as `access`, or the outer VLAN tag only, when the `instance-role` statement is defined as `nni`.
- `l2vpn`—Enable a Layer 2 VPN on the routing instance. You must configure the `interface`, `route-distinguisher`, `vrf-import`, and `vrf-export` statements for this type of routing instance.
- `layer2-control`—(MX Series routers only) Provide support for RSTP or MSTP in customer edge interfaces of a VPLS routing instance. This instance type cannot be used if the customer edge interface is multihomed to two provider edge interfaces. If the customer edge interface is multihomed to two provider edge interfaces, use the default BPDU tunneling.
- `mac-vrf`—Enable configuring multiple customer-specific EVPN instances (EVIs) of this type, each of which can support a different EVPN service type. You can have customer-specific virtual routing and forwarding (VRF) tables with MAC addresses on each Juniper Networks device that serves as a virtual tunnel endpoint (VTEP) in the EVPN-VXLAN network. This type of routing instance is for EVPN unicast routes only. See `mac-vrf` for more on this type of EVPN instance.
- `mpls-forwarding`—(MX Series routers only) Allow filtering and translation of route distinguisher (RD) values in IPv4 and IPv6 VPN address families on both routes received and routes sent for selected

BGP sessions. In particular, for Inter-AS VPN Option-B networks, this option can prevent the malicious injection of VPN labels from one peer AS boundary router to another.

- `mpls-internet-multicast`—(EX Series, M Series, MX Series, and T Series routers only) Provide support for ingress replication provider tunnels to carry IP multicast data between routers through an MPLS cloud, using MBGP or next-generation MVPN.
- `no-forwarding`—This is the default routing instance. Do not create a corresponding forwarding instance. Use this routing instance type when a separation of routing table information is required. There is no corresponding forwarding table. All routes are installed into the default forwarding table. IS-IS instances are strictly nonforwarding instance types.
- `virtual-router`—Enable a virtual router routing instance. This instance type is similar to a VPN routing and forwarding instance type, but used for non-VPN-related applications. You must configure the `interface` statement for this type of routing instance. You do not need to configure the `route-distinguisher`, `vrf-import`, and `vrf-export` statements.
- `virtual-switch`—(MX Series routers, EX9200 switches, and QFX switches only) Provide support for Layer 2 bridging. Use this routing instance type to isolate a LAN segment with its Spanning Tree Protocol (STP) instance and to separate its VLAN identifier space.
- `vpls`—Enable VPLS on the routing instance. Use this routing instance type for point-to-multipoint LAN implementations between a set of sites in a VPN. You must configure the `interface`, `route-distinguisher`, `vrf-import`, and `vrf-export` statements for this type of routing instance.
- `vrf`—VPN routing and forwarding (VRF) instance. Provides support for Layer 3 VPNs, where interface routes for each instance go into the corresponding forwarding table only. Required to create a Layer 3 VPN. Create a VRF table (*instance-name.inet.0*) that contains the routes originating from and destined for a particular Layer 3 VPN. For this instance type, there is a one-to-one mapping between an interface and a routing instance. Each VRF instance corresponds with a forwarding table. Routes on an interface go into the corresponding forwarding table. You must configure the `interface`, `route-distinguisher`, `vrf-import`, and `vrf-export` statements for this type of routing instance.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

`virtual-switch` and `layer2-control` options introduced in Junos OS Release 8.4.

`mpls-internet-multicast` option introduced in Junos OS Release 11.1 for the EX Series, M Series, MX Series, and T Series.

`evpn` option introduced in Junos OS Release 13.2 for MX 3D Series routers.

`evpn` option introduced in Junos OS Release 17.3 for the QFX Series.

`forwarding` option introduced in Junos OS Release 14.2 for the PTX Series.

`mpls-forwarding` option introduced in Junos OS Release 16.1 for the MX Series.

`evpn-vpws` option introduced in Junos OS Release 17.1 for MX Series routers.

`mac-vrf` option introduced in Junos OS Release 20.4 for MX Series and vMX routers; QFX5100, QFX5110, QFX5120, QFX5200, QFX10002 (including QFX10002-60C), QFX10008, QFX10016, and EX9200 Series switches. Also introduced in Junos OS Evolved Release 21.2R1 on QFX5130-32CD switches.

Support for logical systems on MX Series routers added in Junos OS Release 17.4R1.

`evpn-vpws` option introduced in cRPD Release 20.3R1.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

[Configuring Virtual Router Routing Instances](#)

[Example: Configuring Filter-Based Forwarding on the Source Address](#)

[Example: Configuring Filter-Based Forwarding on Logical Systems](#)

interface (Routing Instances)

IN THIS SECTION

- [Syntax | 1401](#)
- [Hierarchy Level | 1401](#)
- [Description | 1401](#)
- [Options | 1401](#)

- Required Privilege Level | 1401
- Release Information | 1401

Syntax

```
interface interface-name {  
    description text;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],  
[edit routing-instances routing-instance-name]
```

Description

Specify the interface over which the VPN traffic travels between the PE device and CE device. You configure the interface on the PE device. If the value `vrf` is specified for the `instance-type` statement included in the routing instance configuration, this statement is required.

Options

interface-name—Name of the interface.

The remaining statement is explained separately. Search for a statement in [CLI Explorer](#) or click a linked statement in the Syntax section for details.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

[interface \(VPLS Routing Instances\)](#) | 1535

no-forwarding

IN THIS SECTION

- [Syntax](#) | 1402
- [Hierarchy Level](#) | 1402
- [Description](#) | 1402
- [Default](#) | 1403
- [Required Privilege Level](#) | 1403
- [Release Information](#) | 1403

Syntax

```
no-forwarding;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols ldp],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols ldp],  
[edit protocols ldp],  
[edit routing-instances routing-instance-name protocols ldp]
```

Description

Do not add ingress routes to the inet.0 routing table even if [traffic-engineering](#) bgp-igp (configured at the [edit protocols mpls] hierarchy level) is enabled.

Default

The no-forwarding statement is disabled. Ingress routes are added to the inet.0 routing table instead of the inet.3 routing table when `traffic-engineering` `bgp-igp` is enabled.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Preventing Addition of Ingress Routes to the inet.0 Routing Table](#)

Configuring Virtual-Router Routing Instances in VPNs

forward-policy-mismatch (Security Group VPN Member)

IN THIS SECTION

- [Syntax | 1403](#)
- [Hierarchy Level | 1404](#)
- [Description | 1404](#)
- [Required Privilege Level | 1404](#)
- [Release Information | 1404](#)

Syntax

```
vpn vpn-name {
    ike-gateway gateway-number;
```

```

group group-number;
match-direction (input);
tunnel mtu mtu-size;
}

```

Hierarchy Level

```
[edit security group-vpn member ipsec]
```

Description

Configure the forward policy mismatch for group VPN member.

Required Privilege Level

security—To view this statement in the configuration.

security-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 18.2R1.

RELATED DOCUMENTATION

[Group VPNv2 Overview](#)

proxy-generate

IN THIS SECTION

- [Syntax | 1405](#)
- [Hierarchy Level | 1405](#)
- [Description | 1405](#)

- Options | 1405
- Required Privilege Level | 1405
- Release Information | 1406

Syntax

```
proxy-generate <route-target-policy route-target-policy-name>;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols bgp group group-name family route-target],
[edit logical-systems logical-system-name protocols bgp group group-name neighbor address family
route-target],
[edit protocols bgp group group-name family route-target],
[edit protocols bgp group group-name neighbor address family route-target]
```

Description

Enable proxy BGP route target filtering (also known as proxy route target constrain, or proxy RTC). This feature is useful if you have a network environment where route target filtering is not widely deployed or fully supported. When configured for proxy BGP route target filtering, the device creates route target membership (RT membership) on behalf of its peers that do not have the route target filtering functionality. The device then distributes the RT membership advertisements from incoming BGP VPN routes to other devices in the network that need them.

Options

route-target-policy <i>route-target-policy-name</i>	(Optional) Apply a routing policy that defines a subset of VPN routes to be used in your proxy BGP route target filter. The subset of VPN routes control which proxy BGP route targets are used to create the proxy BGP route target routes.
--	--

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.2.

RELATED DOCUMENTATION

Example: Configuring Proxy BGP Route Target Filtering for VPNs

Example: Configuring an Export Policy for BGP Route Target Filtering for VPNs

Configuring BGP Route Target Filtering for VPNs

[family route-target | 1392](#)

[rtf-prefix-list](#)

revert-time (Protocols Layer 2 Circuits)

IN THIS SECTION

- [Syntax | 1406](#)
- [Hierarchy Level | 1407](#)
- [Description | 1407](#)
- [Default | 1408](#)
- [Options | 1408](#)
- [Required Privilege Level | 1408](#)
- [Release Information | 1408](#)

Syntax

```
revert-time seconds maximum seconds;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address],
[edit protocols l2circuit neighbor address interface interface-name],
[edit routing-instances routing-instance-name protocols vpls neighbor address]
```

Description

Specify a revert time for redundant Layer 2 circuits and VPLS pseudowires. When you have configured redundant pseudowires for Layer 2 circuits or VPLS, traffic is switched to the backup connection in the event that the primary connection fails. If you configure a revert time, when the configured time expires traffic is reverted to the primary path, assuming the primary path has been restored.

With the `maximum` option, specify a maximum reversion interval to add after the `revert-time` delay. If a `revert-time` delay is defined but a maximum timer is not defined, VCs are restored upon the revert-timer's expiration.

To reduce as much as possible the amount of traffic discarded, and potential data-path asymmetries observed during primary-to-backup transition periods, you can use this restoration timer. This restoration timer is activated when the backup path is performing as active, and then the primary path is restored. The goal is to avoid moving traffic back to the primary path right away, to make sure that the control plane's related tasks (such as IGP, LDP, RSVP, and internal BGP) have enough time to complete their updating cycle.

By enabling a gradual return of traffic to the primary path, you can ensure that the relatively-slow control-plane processing and updating does not have a negative impact on the restoration process.

The `maximum` option extends the revert timer's functionality to provide a jittered interval over which a certain number of circuits can be transitioned back to the primary path. By making use of this maximum value, you can define a time interval during which circuits are expected to switch over. As a consequence, circuits' effective transitions are scattered during restoration periods.

When making use of `revert-time x maximum y` statement, you can ensure that the corresponding circuit that is active is moved to the primary path within a time-slot (t_1) such as that: $x \leq t_1 \leq y$. In other words, by activating this statement, you can ensure the following:

- VCs stay in the backup path for at least x seconds after the primary path comes back up.
- VCs are moved back to the primary path before y seconds have elapsed.
- y maximum value = x maximum value * 2 = 1200 seconds.

The ideal values for *x* and *y* will be conditioned to internal aspects of your network. For this reason, there are no default values for these settings. If no *revert-time* is set, the default behavior is non-revertive. That is, circuits are not returned to the primary path upon restoration. They are kept on the backup path.

Default

Without the *revert-time* statement, virtual circuit (VC) traffic is not transitioned to the primary path upon restoration of the primary path.

Options

seconds—Revert time in seconds.

- **Range:** 0 through 600 seconds

maximum seconds—Number of seconds to delay path restoration after the *revert-time* delay.

- **Range:** 0 through 1200 seconds

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.2.

maximum option introduced in Junos OS Release 13.2.

RELATED DOCUMENTATION

| [Configuring Redundant Pseudowires for Layer 2 Circuits and VPLS](#) | 226

route-distinguisher

IN THIS SECTION

- [Syntax | 1409](#)
- [Hierarchy Level | 1409](#)
- [Description | 1409](#)
- [Options | 1410](#)
- [Required Privilege Level | 1411](#)
- [Release Information | 1411](#)

Syntax

```
route-distinguisher (as-number:id | ip-address:id);
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn mesh-group mesh-group-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
mesh-group mesh-group-name],
[edit protocols evpn interconnect]
[edit routing-instances routing-instance-name],
[edit routing-instances routing-instance-name protocols evpn interconnect]
[edit routing-instances routing-instance-name protocols l2vpn mesh-group mesh-group-name],
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
```

Description

Specify an identifier attached to a route, enabling you to distinguish to which VPN or virtual private LAN service (VPLS) the route belongs. Each routing instance must have a unique route distinguisher (RD) associated with it. The RD is used to place bounds around a VPN so that the same IP address prefixes

can be used in different VPNs without having them overlap. If the instance type is `vrf`, the `route-distinguisher` statement is required.

For Layer 2 VPNs and VPLS, if you configure the `l2vpn-use-bgp-rules` statement, you must configure a unique RD for each PE router participating in the routing instance.

For Ethernet VPN (EVPN), you must configure a unique RD for each PE router participating in the routing instance to ensure that the prefixes generated by different PEs are unique.

For other types of VPNs, we recommend that you use a unique RD for each provider edge (PE) router participating in specific routing instance. Although you can use the same RD on all PE routers for the same VPN routing instance, if you use a unique RD, you can determine the customer edge (CE) router from which a route originated within the VPN.

For Layer 2 VPNs and VPLSs, if you configure mesh groups, the RD in each mesh group must be unique.



CAUTION: We strongly recommend that if you change an RD that has already been configured, or change the routing-instance type from `virtual-router` to `vrf`, make the change during a maintenance window, as follows:

1. Deactivate the routing instance.
2. Change the RD.
3. Activate the routing instance.

This is not required if you are configuring the RD for the first time.

Options

as-number: number—*as-number* is an assigned AS number, and *number* is any 2-byte or 4-byte value. The AS number can be from 1 through 4,294,967,295. If the AS number is a 2-byte value, the administrative number is a 4-byte value. If the AS number is 4-byte value, the administrative number is a 2-byte value. An RD consisting of a 4-byte AS number and a 2-byte administrative number is defined as a type 2 RD in RFC 4364 *BGP/MPLS IP VPNs*.

NOTE: In Junos OS Release 9.1 and later, the numeric range for AS numbers is extended to provide BGP support for 4-byte AS numbers, as defined in RFC 4893, *BGP Support for Four-octet AS Number Space*. All releases of Junos OS support 2-byte AS numbers. To configure an RD that includes a 4-byte AS number, append the letter “L” to the end of the AS number. For example, an RD with the 4-byte AS number 7,765,000 and an administrative number of 1,000 is represented as `77765000L:1000`.

In Junos OS Release 9.2 and later, you can also configure a 4-byte AS number using the AS dot notation format of two integer values joined by a period: *<16-bit high-order value in decimal>.<16-bit low-order value in decimal>*. For example, the 4-byte AS number of 65,546 in the plain-number format is represented as 1.10 in AS dot notation format.

number:id—Number and identifier expressed in one of these formats: *16-bit number.32-bit identifier* or *32-bit number.16-bit identifier*.

ip-address:id—IP address (*ip-address* is a 4-byte value) within your assigned prefix range and a 2-byte value for the *id*. The IP address can be any globally unique unicast address.

- **Range:** 0 through 4,294,967,295 ($2^{32} - 1$). If the router you are configuring is a BGP peer of a router that does not support 4-byte AS numbers, you need to configure a local AS number. For more information, see *Using 4-Byte Autonomous System Numbers in BGP Networks Technology Overview*.

NOTE: For Ethernet VPN (EVPN), an RD that includes zero as the *id* value is reserved for the default EVPN routing instance by default. Because the same RD cannot be assigned for two routing instances, using a *ip-address.id* RD for another routing instance (default-switch), where the *id* value is zero, throws a commit error.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support at [edit routing-instances *routing-instance-name* protocols vpls mesh-group *mesh-group-name*] hierarchy level introduced in Junos OS Release 11.2.

Support at [edit routing-instances *routing-instance-name* protocols l2vpn mesh-group *mesh-group-name*] hierarchy level introduced in Junos OS Release 13.2.

Support at the following hierarchy levels introduced in Junos OS Release 20.3R1 on QFX Series switches: [edit protocols evpn interconnect] and [edit routing-instances *routing-instance-name* protocols evpn interconnect].

RELATED DOCUMENTATION

Example: Configuring BGP Route Target Filtering for VPNs

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 885](#)

Configuring EVPN Routing Instances

Configuring Routing Instances on PE Routers in VPNs

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

[Configuring an MPLS-Based Layer 3 VPN \(CLI Procedure\)](#)

path-selection

route-distinguisher-id

IN THIS SECTION

- [Syntax | 1412](#)
- [Hierarchy Level | 1412](#)
- [Description | 1413](#)
- [Options | 1413](#)
- [Required Privilege Level | 1413](#)
- [Release Information | 1413](#)

Syntax

```
route-distinguisher-id ip-address;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options],
[edit routing-options]
```

Description

Automatically assign a route distinguisher to the routing instance.

If you configure the `route-distinguisher` statement in addition to the `route-distinguisher-id` statement, the value configured for `route-distinguisher` supersedes the value generated from `route-distinguisher-id`.

NOTE: To avoid a conflict in the two route distinguisher values, you must ensure that the first half of the route distinguisher obtained by configuring the `route-distinguisher` statement is different from the first half of the route distinguisher obtained by configuring the `route-distinguisher-id` statement.

Options

ip-address—Address for routing instance.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Example: Configuring BGP Route Target Filtering for VPNs

Configuring Routing Instances on PE Routers in VPNs

route-target-filter

IN THIS SECTION

- [Syntax | 1414](#)
- [Hierarchy Level | 1414](#)
- [Description | 1414](#)
- [Options | 1415](#)
- [Required Privilege Level | 1415](#)
- [Release Information | 1415](#)

Syntax

```
route-target-filter destination {  
    group group-name;  
    local;  
    neighbor address;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options rib bgp.rtarget.0 static],  
[edit routing-options rib bgp.rtarget.0 static]
```

Description

Statically configure route target filtering. Route target filtering allows you to distribute VPN routes to only the routers that need them. In VPN networks without route target filtering configured, BGP distributes all static VPN routes to all of the VPN peer routers. You can add static routes to the bgp.rtarget.0 routing table with specific NLRI-imposed constraints.

Options

<i>destination</i>	Allows you to specify the static route destination. This value must be in the format x:y/len. The x value is either an IP address or an AS number followed by an optional L to indicate a 4 byte AS number, and y is a number (for example, 123456L:100/64).
<i>group group-name(s)</i>	Installs an RT-Constrain filter for the destination for all peers in the specified BGP group. The route and corresponding BGP group are displayed in the output of the show bgp group rtf detail command.
<i>local</i>	Causes the router to originate the route target constrain NLRI, but does not install any filtering state for the prefix. This behavior can be useful when the router should always receive VPN routes with this route-target regardless of the state of a given BGP peering session or group status. The route is not displayed in the output of the show bgp group rtf detail command unless it is also included in either the BGP neighbor or BGP group configuration.
<i>neighbor address</i>	Installs an RT-Constrain filter for the destination for this BGP neighbor. The route is displayed in the output of the show bgp group rtf detail command. Specify the BGP neighbor using the router's IP address.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.2.

RELATED DOCUMENTATION

Configuring Static Route Target Filtering for VPNs

Reducing Network Resource Use with Static Route Target Filtering for VPNs

switchover-delay

IN THIS SECTION

- [Syntax | 1416](#)
- [Hierarchy Level | 1416](#)
- [Description | 1416](#)
- [Options | 1416](#)
- [Required Privilege Level | 1417](#)
- [Release Information | 1417](#)

Syntax

```
switchover-delay milliseconds;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
neighbor address],  
[edit protocols l2circuit neighbor address interface interface-name],  
[edit routing-instances routing-instance-name protocols vpls neighbor address]
```

Description

After the primary pseudowire goes down, specifies the delay (in milliseconds) to wait before the backup pseudowire takes over. You configure this statement for each backup neighbor configuration to adjust the switchover time after a failure is detected.

Options

milliseconds—Specify the time to wait before switching to the backup pseudowire after the primary pseudowire fails.

- **Default:** 10,000 milliseconds
- **Range:** 0 through 180,000 milliseconds

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.2.

RELATED DOCUMENTATION

| [Configuring the Switchover Delay for the Pseudowires](#) | 227

unicast-reverse-path

IN THIS SECTION

- [Syntax](#) | 1417
- [Hierarchy Level](#) | 1418
- [Description](#) | 1418
- [Options](#) | 1418
- [Required Privilege Level](#) | 1418
- [Release Information](#) | 1418

Syntax

```
unicast-reverse-path (active-paths | feasible-paths);
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options forwarding-table],
[edit routing-instances routing-instance-name instance-type name routing-options forwarding-
table],
[edit routing-options forwarding-table]
```

Description

Control the operation of unicast reverse-path-forwarding check. This statement enables the RPF check to be used when routing is asymmetrical.

Options

active-paths—Consider only active paths during the unicast reverse-path check.

feasible-paths—Consider all feasible paths during the unicast reverse-path check.

- **Default:** If you omit the unicast-reverse-path statement, only the active paths to a particular destination are considered.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support for routing instances added in Junos OS Release 8.3.

NOTE: This feature is not supported on the EX4300 switch, even though it is available on the device.

RELATED DOCUMENTATION

Example: Configuring Unicast RPF (On a Router)

vpn-apply-export

IN THIS SECTION

- [Syntax | 1419](#)
- [Hierarchy Level | 1419](#)
- [Description | 1419](#)
- [Required Privilege Level | 1420](#)
- [Release Information | 1420](#)

Syntax

```
vpn-apply-export;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols bgp],  
[edit logical-systems logical-system-name protocols bgp group group-name],  
[edit logical-systems logical-system-name protocols bgp group group-name neighbor neighbor],  
[edit protocols bgp],  
[edit protocols bgp group group-name],  
[edit protocols bgp group group-name neighbor neighbor]
```

Description

Apply both the VRF export and BGP group or neighbor export policies (VRF first, then BGP) before routes from the vrf or l2vpn routing tables are advertised to other PE routers.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Configuring Policies for the VRF Table on PE Routers in VPNs

vrf-export

IN THIS SECTION

- [Syntax | 1420](#)
- [Hierarchy Level | 1421](#)
- [Description | 1421](#)
- [Default | 1421](#)
- [Options | 1421](#)
- [Required Privilege Level | 1421](#)
- [Release Information | 1421](#)

Syntax

```
vrf-export [ policy-names ];
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name
protocols
                                vpls mesh-group mesh-group-name]
[edit protocols evpn interconnect]
[edit routing-instances routing-instance-name]
[edit routing-instances routing-instance-name protocols evpn interconnect]
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
[edit switch-options]
```

Description

Specify how routes are exported from the local device's routing table (*routing-instance-name*.inet.0) to the remote device. If the value *vrf* is specified for the *instance-type* statement included in the routing instance configuration, this statement is required.

You can configure multiple export policies on the router or switch.

Default

If the *instance-type* is *vrf*, *vrf-export* is a required statement. The default action is to reject.

Options

policy-names—Names for the export policies.

Required Privilege Level

routing— To view this statement in the configuration.

routing-control— To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support at the following hierarchy levels introduced in Junos OS Release 20.3R1 on QFX Series switches: [edit protocols evpn interconnect] and [edit routing-instances *routing-instance-name* protocols evpn interconnect].

RELATED DOCUMENTATION

Implementing EVPN-VXLAN for Data Centers

instance-type

Configuring Policies for the VRF Table on PE Routers in VPNs

vrf-import

IN THIS SECTION

- [Syntax | 1422](#)
- [Hierarchy Level | 1422](#)
- [Description | 1423](#)
- [Options | 1423](#)
- [Required Privilege Level | 1423](#)
- [Release Information | 1423](#)

Syntax

```
vrf-import [ policy-names ];
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name
protocols                                vpls mesh-group mesh-group-name]
[edit protocols evpn interconnect]
[edit routing-instances routing-instance-name]
[edit routing-instances routing-instance-name protocols evpn interconnect]
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
[edit switch-options]
```

Description

Specify how routes are imported into the routing table (*routing-instance-name*.inet.0) of the local device from the remote device.

You can configure multiple import policies on the device.

One of the following statements are required for importing routes:

- **vrf-target** - When you configure only the `vrf-target` statement without the `vrf-import` statement, by default all routes matching the specified target community are accepted.
- **vrf-import** - When you configure only the `vrf-import` statement, there is no default action. Only routes accepted in the configured `vrf-import` policy statement are imported.

Options

policy-names—Names for the import policies.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support at the following hierarchy levels introduced in Junos OS Release 20.3R1 on QFX Series switches: [edit protocols evpn interconnect] and [edit routing-instances *routing-instance-name* protocols evpn interconnect].

RELATED DOCUMENTATION

Implementing EVPN-VXLAN for Data Centers

instance-type

Configuring Policies for the VRF Table on PE Routers in VPNs

vrf-mtu-check

IN THIS SECTION

- [Syntax | 1424](#)
- [Hierarchy Level | 1424](#)
- [Description | 1424](#)
- [Default | 1424](#)
- [Required Privilege Level | 1424](#)
- [Release Information | 1425](#)

Syntax

```
vrf-mtu-check;
```

Hierarchy Level

```
[edit chassis]
```

Description

On M Series routers (except the M120 and M320 router) and on EX Series 8200 switches, configure path maximum transmission unit (MTU) checks on the outgoing interface for unicast traffic routed on a virtual private network (VPN) routing and forwarding (VRF) instance.

Default

Disabled.

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Configuring Path MTU Checks for VPN Routing Instances

Configure Path MTU Discovery

vrf-target

IN THIS SECTION

- [Syntax | 1425](#)
- [Hierarchy Level | 1426](#)
- [Description | 1426](#)
- [Options | 1426](#)
- [Required Privilege Level | 1427](#)
- [Release Information | 1427](#)

Syntax

```
vrf-target {  
    community;  
    auto  
    import community-name;  
    export community-name;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn mesh-group mesh-group-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
mesh-group mesh-group-name],
[edit protocols evpn interconnect],
[edit routing-instances routing-instance-name protocols evpn interconnect],
[edit routing-instances routing-instance-name protocols evpn vni-options],
[edit routing-instances routing-instance-name protocols l2vpn mesh-group mesh-group-name],
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name],
[edit switch-options]
```

Description

Specify a virtual routing and forwarding (VRF) target community. If you configure the *community* option only, default VRF import and export policies are generated that accept and tag routes with the specified target community. The purpose of the *vrf-target* statement is to simplify the configuration by allowing you to configure most statements at the [edit routing-instances] hierarchy level. In effect, this statement configures a single policy for import and a single policy for export to replace the per-VRF policies for every community.

You can still create more complex policies by explicitly configuring VRF import and export policies using the *import* and *export* options.

Options

community—Community name.

auto—Automatically derives the route target (RT). The auto-derived route targets have higher precedence over manually configured RT in *vrf-target*, *vrf-export* policies, and *vrf-import* policies.

NOTE: Auto-derived route targets are supported only in virtual switch and EVPN routing instances.

import community-name—Allowed communities accepted from neighbors.

export community-name—Allowed communities sent to neighbors.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

auto option added in Junos OS Release 19.1R1 for MX series.

Support at the following hierarchy levels introduced in Junos OS Release 20.3R1 on QFX Series switches: [edit protocols evpn interconnect] and [edit routing-instances *routing-instance-name* protocols evpn interconnect].

RELATED DOCUMENTATION

Configuring Policies for the VRF Table on PE Routers in VPNs

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 885](#)

Configuration Statements (Layer 2 VPNs and VPLS)

IN THIS CHAPTER

- action-priority | 1433
- active-interface (VPLS Multihoming) | 1435
- any (VPLS Multihoming) | 1436
- auto-discovery-only | 1438
- automatic-site-id | 1440
- backup-interface (Layer 2 Circuits) | 1442
- bandwidth (Protocols Layer 2 Circuit) | 1443
- best-site | 1444
- bfd-liveness-detection (Layer 2 VPN and VPLS) | 1446
- community (Protocols Layer 2 Circuit) | 1448
- connection-protection | 1450
- connectivity-type | 1451
- control-channel (Protocols OAM) | 1453
- control-word (Protocols Layer 2 Circuit Neighbor) | 1454
- control-word (Protocols Layer 2 VPN) | 1456
- control-word | 1458
- deep-vlan-qualified-learning | 1460
- default-isid | 1461
- description (Protocols Layer 2 Circuit Neighbor) | 1463
- description (Protocols Layer 2 VPN) | 1464
- detection-time (BFD Liveness Detection) | 1465
- egress-protection (Layer 2 circuit) | 1469
- egress-protection (MPLS) | 1470
- encapsulation (Logical Interface) | 1472
- encapsulation | 1477
- encapsulation-type (Layer 2 Circuits) | 1484

- [encapsulation-type \(Layer 2 VPNs\) | 1486](#)
- [end-interface | 1489](#)
- [exclusive-mac | 1490](#)
- [extended-vlan-list | 1492](#)
- [family \(Protocols BGP\) | 1494](#)
- [family multiservice | 1499](#)
- [fast-aps-switch | 1502](#)
- [fast-reroute-priority | 1504](#)
- [flow-label | 1506](#)
- [flow-label-receive | 1507](#)
- [flow-label-receive-static | 1509](#)
- [flow-label-static | 1510](#)
- [flow-label-transmit | 1512](#)
- [flow-label-transmit-static | 1514](#)
- [global-mac-move | 1515](#)
- [hot-standby | 1517](#)
- [hot-standby \(Protocols Layer 2 Circuit\) | 1518](#)
- [hot-standby-vc-on \(Protocols Layer 2 Circuit\) | 1520](#)
- [identifier \(VPLS Multihoming for FEC 129\) | 1522](#)
- [ignore-encapsulation-mismatch | 1524](#)
- [ignore-mtu-mismatch | 1525](#)
- [import-labeled-routes \(Routing Instances VPLS\) | 1527](#)
- [interface \(Protocols Layer 2 Circuit\) | 1528](#)
- [interface \(Protocols Layer 2 VPN\) | 1531](#)
- [interface \(VPLS Mesh-Group\) | 1533](#)
- [interface \(VPLS Multihoming for FEC 129\) | 1534](#)
- [interface \(VPLS Routing Instances\) | 1535](#)
- [interface-mac-limit \(VPLS\) | 1537](#)
- [install-nexthop | 1539](#)
- [l2circuit | 1540](#)
- [l2ckt | 1543](#)
- [l2-learning | 1544](#)

- [l2vpn | 1546](#)
- [l2vpn \(routing-options\) | 1549](#)
- [l2vpn-id | 1551](#)
- [label-allocation | 1552](#)
- [label-block-size | 1553](#)
- [label-switched-path-template \(Multicast\) | 1555](#)
- [local-switching \(Layer 2 Circuits\) | 1557](#)
- [local-switching \(VPLS\) | 1559](#)
- [mac-flush | 1560](#)
- [mac-pinning | 1562](#)
- [mac-statistics | 1564](#)
- [mac-table-size | 1567](#)
- [map-dest-bmac-to-dest-cmac | 1569](#)
- [mesh-group \(Protocols VPLS\) | 1570](#)
- [minimum-interval \(BFD Liveness Detection\) | 1572](#)
- [minimum-receive-interval \(BFD Liveness Detection\) | 1574](#)
- [mtu | 1576](#)
- [multicast-mode \(EVPN\) | 1580](#)
- [multiplier \(BFD Liveness Detection\) | 1582](#)
- [multi-homing \(VPLS Multihoming for BGP VPLS\) | 1584](#)
- [multi-homing \(VPLS Multihoming for FEC 129\) | 1585](#)
- [neighbor \(Protocols Layer 2 Circuit\) | 1587](#)
- [neighbor \(Protocols VPLS\) | 1590](#)
- [no-adaptation \(BFD Liveness Detection\) | 1592](#)
- [no-control-word | 1594](#)
- [no-control-word \(Protocols Layer 2 VPN\) | 1596](#)
- [no-l2ckt | 1597](#)
- [no-l2vpn | 1599](#)
- [no-local-switching \(VPLS\) | 1600](#)
- [no-mac-learning | 1601](#)
- [no-normalization | 1605](#)
- [no-revert \(Local Switching\) | 1607](#)

- [no-revert \(Neighbor Interface\) | 1608](#)
- [no-tunnel-services | 1610](#)
- [oam | 1612](#)
- [packet-action | 1613](#)
- [path-selection | 1617](#)
- [pbb-service-options | 1621](#)
- [peer-active \(VPLS Multihoming for FEC 129\) | 1622](#)
- [peer-as \(VPLS\) | 1625](#)
- [ping-interval | 1626](#)
- [policer \(Layer 2 VPN\) | 1628](#)
- [policy-oids | 1630](#)
- [preference \(Interface-Level Preference for VPLS Multihoming for FEC 129\) | 1631](#)
- [preference \(Site-Level Preference for VPLS Multihoming for FEC 129\) | 1633](#)
- [primary \(VPLS Multihoming\) | 1634](#)
- [protect-interface | 1636](#)
- [protected-l2circuit | 1638](#)
- [protector-interface | 1639](#)
- [protector-pe | 1641](#)
- [proxy \(Interfaces\) | 1642](#)
- [pseudowire-status-tlv | 1644](#)
- [psn-tunnel-endpoint | 1645](#)
- [qualified-bum-pruning-mode | 1646](#)
- [remote | 1648](#)
- [remote-site-id | 1649](#)
- [routing-instances | 1651](#)
- [rsvp-te \(Routing Instances Provider Tunnel\) | 1652](#)
- [send-oam | 1654](#)
- [service-groups | 1655](#)
- [service-type | 1656](#)
- [site \(Layer 2 Circuits\) | 1658](#)
- [site \(VPLS Multihoming for FEC 128\) | 1660](#)
- [site \(VPLS Multihoming for FEC 129\) | 1661](#)

- [site-identifier \(Layer 2 Circuits\) | 1663](#)
- [site-identifier \(VPLS\) | 1664](#)
- [site-preference | 1666](#)
- [site-range | 1668](#)
- [source-attachment-identifier \(Protocols VPWS\) | 1669](#)
- [source-bmac | 1671](#)
- [standby \(Protocols Layer 2 Circuit\) | 1673](#)
- [static \(Protocols Layer 2 Circuit\) | 1674](#)
- [static \(Protocols VPLS\) | 1676](#)
- [static-mac | 1678](#)
- [target-attachment-identifier \(Protocols VPWS\) | 1680](#)
- [template | 1682](#)
- [traceoptions \(Egress Protection\) | 1683](#)
- [traceoptions \(Protocols Layer 2 Circuit\) | 1685](#)
- [traceoptions \(Protocols Layer 2 VPN\) | 1687](#)
- [traceoptions \(Protocols VPLS\) | 1690](#)
- [transmit-interval \(BFD Liveness Detection\) | 1693](#)
- [tunnel-services \(Routing Instances VPLS\) | 1696](#)
- [version \(BFD Liveness Detection\) | 1698](#)
- [virtual-circuit-id | 1700](#)
- [virtual-gateway-address | 1702](#)
- [virtual-mac | 1703](#)
- [vlan-id | 1705](#)
- [vlan-id \(routing instance\) | 1706](#)
- [vlan-id inner-all | 1708](#)
- [vlan-id-list \(Interface in VPLS\) | 1709](#)
- [vlan-tagging | 1710](#)
- [vlan-tags \(Stacked VLAN Tags\) | 1713](#)
- [vpls \(Interfaces\) | 1716](#)
- [vpls \(Routing Instance\) | 1717](#)
- [vpls-id | 1721](#)
- [vpls-id-list \(protocols vpls mesh-group\) | 1722](#)

- [vpls-mac-move | 1724](#)
- [vpws-service-id | 1725](#)

action-priority

IN THIS SECTION

- [Syntax | 1433](#)
- [Hierarchy Level | 1433](#)
- [Description | 1433](#)
- [Options | 1434](#)
- [Required Privilege Level | 1434](#)
- [Release Information | 1434](#)

Syntax

```
action-priority value;
```

Hierarchy Level

```
[edit routing-instances routing-instance-name protocols protocol-name interface interface-name]
```

Description

Configure the priority for an interface on which the MAC move is applied. When a MAC move is configured with a corresponding action, and that limit is exceeded, the action is applied to one of the interfaces associated with that MAC address having the highest action priority. If the action configured for the MAC move is shutdown, you can use the action priority to determine which interface is disabled. If an interface is trusted, assign a low action priority to decrease the likelihood that the interface shuts down if the configured action is shutdown or `vlan-member-shutdown`.

If no action priority is configured, or if the interfaces have the same action priority, then the action is applied to the interface to which the MAC address moved last.

Options

value Value assigned to an interface associated with a MAC address move. The value determines the priority with which an action is applied to the interface if the MAC address move limit is reached. The interface with the highest priority is the interface with the lowest value configured for action-priority.

A higher value means lower priority. For example, if a MAC address move occurs between two interfaces with the action priority value set to 5 and 6, the interface with value 5 as the action priority value is blocked.

If a VPLS instance has MAC move action enabled, set the action-priority to 8 for the router to detect an interface as a core interface by the VPLS customer edge loop prevention feature. By default, the loop prevention feature supports lsi and vt-type interfaces as core interfaces; however, you can use this special action-priority value to designate any interface as a core interface.

- **Default:** 4
- **Range:** 0 through 8

Required Privilege Level

system—To view this statement in the configuration.

system-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.2.

RELATED DOCUMENTATION

| [Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves](#) | 1147

active-interface (VPLS Multihoming)

IN THIS SECTION

- [Syntax | 1435](#)
- [Hierarchy Level | 1435](#)
- [Description | 1435](#)
- [Required Privilege Level | 1436](#)
- [Release Information | 1436](#)

Syntax

```
active-interface {  
    any;  
    primary interface-name;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing],  
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing site site-name],  
[edit routing-instances instance-name protocols vpls multi-homing],  
[edit routing-instances instance-name protocols vpls multi-homing site site-name]
```

Description

Specify a multihomed interface as the primary interface for the VPLS site. If there are multiple interfaces, the remaining interfaces are activated only when the primary interface goes down. If no active interfaces are configured at the site level, it is assumed that all traffic for a VPLS site travels through a single, nonmultihomed PE router.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The remaining statements are explained separately. See [CLI Explorer](#).

For FEC 128, use the [edit routing-instances *instance-name* protocols vpls multi-homing] hierarchy level.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 7.5.

RELATED DOCUMENTATION

| [Specifying an Interface as the Active Interface](#) | 952

any (VPLS Multihoming)

IN THIS SECTION

- [Syntax](#) | 1437
- [Hierarchy Level](#) | 1437
- [Description](#) | 1437
- [Default](#) | 1437
- [Required Privilege Level](#) | 1437
- [Release Information](#) | 1438

Syntax

```
any;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-
homing active-interface],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-
homing site site-name active-interface],
[edit routing-instances instance-name protocols vpls multi-homing active-interface],
[edit routing-instances instance-name protocols vpls multi-homing site site-name active-
interface]
```

Description

Specify that any multihomed interface can be used as the primary interface by the VPLS site. Depending on the order in which interfaces are listed in the PE router's configuration, the first operational interface in the set of configured interfaces is chosen to be the primary interface.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

For FEC 128, use the [edit routing-instances *instance-name* protocols vpls multi-homing active-interface] hierarchy level.

Default

This is the default behavior.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 7.5.

RELATED DOCUMENTATION

[Specifying an Interface as the Active Interface | 952](#)

[primary \(VPLS Multihoming\) | 1634](#)

auto-discovery-only

IN THIS SECTION

- [Syntax | 1438](#)
- [Hierarchy Level | 1438](#)
- [Description | 1439](#)
- [Required Privilege Level | 1439](#)
- [Release Information | 1439](#)

Syntax

```
auto-discovery-only;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols bgp family l2vpn],
[edit logical-systems logical-system-name protocols bgp group group-name family l2vpn],
[edit logical-systems logical-system-name protocols bgp group group-name neighbor address family
l2vpn],
[edit logical-systems logical-system-name routing-instances instance-name protocols bgp family
l2vpn],
[edit logical-systems logical-system-name routing-instances instance-name protocols bgp group
```

```

group-name family l2vpn],
[edit logical-systems logical-system-name routing-instances instance-name protocols bgp group
group-name neighbor address family l2vpn],
[edit protocols bgp family l2vpn],
[edit protocols bgp group group-name family l2vpn],
[edit protocols bgp group group-name neighbor address family l2vpn],
[edit routing-instances instance-name protocols bgp family l2vpn],
[edit routing-instances instance-name protocols bgp group group-name family l2vpn],
[edit routing-instances instance-name protocols bgp group group-name neighbor address family
l2vpn]

```

Description

Enable the router to process only the autodiscovery network layer reachability information (NLRI) update messages for VPWS and LDP-based Layer 2 VPN and VPLS update messages (BGP_L2VPN_AD_NLRI) (FEC 129).

Specifically, the auto-discovery-only statement notifies the routing process (rpd) to expect autodiscovery-related NLRI messages so that information can be deciphered and used by LDP, VPLS, and VPWS.

The auto-discovery-only statement must be configured on all provider edge (PE) routers in a VPLS or in a VPWS. If you configure route reflection, the auto-discovery-only statement is also required on provider (P) routers that act as the route reflector in supporting FEC 129-related updates.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.4R2.

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 885](#)

automatic-site-id

IN THIS SECTION

- [Syntax | 1440](#)
- [Hierarchy Level | 1440](#)
- [Description | 1440](#)
- [Options | 1441](#)
- [Required Privilege Level | 1441](#)
- [Release Information | 1441](#)

Syntax

```
automatic-site-id {  
    collision-detect-time seconds;  
    new-site-wait-time seconds;  
    reclaim-wait-time minimum seconds maximum seconds;  
    startup-wait-time seconds;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
site site-name],  
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Enable automatic site identifiers for VPLS routing instances.

When you configure `automatic-site-id` for the first time, you must deactivate and then activate protocol `vpls`. However, if you already have `automatic-site-id` configured, you do not need to deactivate and then activate protocol `vpls`.

Options

collision-detect-time—The time in seconds to wait after a claim advertisement is sent to the other routers in a VPLS instance before a PE router can begin using a site identifier. If the PE router receives a competing claim advertisement for the same site identifier during this time period, it initiates the collision resolution procedure for site identifiers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

new-site-wait-time—The time in seconds to wait to receive VPLS information for a newly configured routing instance or a new site. This time interval is also applied whenever the automatic site identifier feature is activated on a VPLS routing instance other than at startup. Effectively, this timer indicates how long to wait before an attempt is made to allocate a site identifier. This timer is also triggered whenever a VPLS routing instance is enabled.

reclaim-wait-time—The time in seconds to wait to receive VPLS information for a newly configured routing instance or a new site. This time interval is also applied whenever the automatic site identifier feature is activated on a VPLS routing instance other than at startup. Effectively, this timer indicates how long to wait before an attempt is made to allocate a site identifier. This timer is also triggered whenever a VPLS routing instance is enabled. You can configure two values for this option: the **minimum** wait time and the **maximum** wait time.

startup-wait-time—The time in seconds to wait at startup to receive all the VPLS information for the route targets configured on the other PE routers included in the VPLS routing instance.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.1.

RELATED DOCUMENTATION

[Configuring Automatic Site Identifiers for VPLS](#) | 678

backup-interface (Layer 2 Circuits)

IN THIS SECTION

- [Syntax | 1442](#)
- [Hierarchy Level | 1442](#)
- [Description | 1442](#)
- [Required Privilege Level | 1442](#)
- [Release Information | 1443](#)

Syntax

```
backup-interface interface-name;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface  
interface-name end-interface interface interface-name],  
[edit protocols l2circuit local-switching interface interface-name end-interface interface  
interface-name]
```

Description

Specify the interface to be used by the protection psduowire in connection protection configurations for Layer 2 circuits.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

| [Example: Configuring Layer 2 Circuit Switching Protection](#) | [461](#)

bandwidth (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax](#) | [1443](#)
- [Hierarchy Level](#) | [1443](#)
- [Description](#) | [1444](#)
- [Options](#) | [1444](#)
- [Required Privilege Level](#) | [1444](#)
- [Release Information](#) | [1444](#)

Syntax

```
bandwidth (bandwidth | ctnumber bandwidth);
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name],  
[edit protocols l2circuit neighbor address interface interface-name]
```

Description

Specify bandwidth allocation for a Layer 2 circuit or for the class types of a Layer 2 circuit.

Options

bandwidth—Configure the bandwidth in bits per second for the Layer 2 circuit. You cannot configure the bandwidth for the Layer 2 circuit and for the class types at the same time.

ctnumber bandwidth—Configure the bandwidth in bits per second for a class type on the Layer 2 circuit. You can configure bandwidth for up to four class types (ct0, ct1, ct2, ct3) per Layer 2 circuit. If you configure the class types, you must configure them in order, starting with class type ct0.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring Bandwidth Allocation and Call Admission Control in Layer 2 Circuits](#) | 383

best-site

IN THIS SECTION

- [Syntax](#) | 1445
- [Hierarchy Level](#) | 1445
- [Description](#) | 1445
- [Required Privilege Level](#) | 1445
- [Release Information](#) | 1445

Syntax

```
best-site;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
site site-name],  
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Enables the VPLS multihoming best site functionality, allowing the site on which it has been enabled to be the preferred site for this PE router. This statement must be configured on all PE routers within the optimized VPLS routing instance.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.2.

RELATED DOCUMENTATION

| [Example: VPLS Multihoming, Improved Convergence Time](#) | 953

bfd-liveness-detection (Layer 2 VPN and VPLS)

IN THIS SECTION

- [Syntax | 1446](#)
- [Hierarchy Level | 1446](#)
- [Description | 1447](#)
- [Required Privilege Level | 1447](#)
- [Release Information | 1447](#)

Syntax

```
bfd-liveness-detection {  
    detection-time {  
        threshold milliseconds;  
    }  
    minimum-interval milliseconds;  
    minimum-receive-interval milliseconds;  
    multiplier number;  
    no-adaptation;  
    transmit-interval {  
        minimum-interval milliseconds;  
        threshold milliseconds;  
    }  
    version (1 | automatic);  
}
```

Hierarchy Level

```
[edit logical-system logical-system-name routing-instances routing-instance-name protocols  
l2vpn oam],  
[edit logical-system logical-system-name routing-instances routing-instance-name protocols vpls  
neighbor neighbor-id oam],  
[edit logical-system logical-system-name routing-instances routing-instance-name protocols vpls  
mesh-group mesh-group-name neighbor neighbor-id oam],
```

```
[edit logical-system logical-system-name routing-instances routing-instance-name protocols vpls
oam],
[edit routing-instances routing-instance-name protocols l2vpn oam],
[edit routing-instances routing-instance-name protocols vpls neighbor neighbor-id oam],
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor
neighbor-id oam],
[edit routing-instances routing-instance-name protocols vpls oam]
```

Description

Configure bidirectional failure detection timers.

The BFD failure detection timers are adaptive and can be adjusted to be more or less aggressive. For example, the timers can adapt to a higher value if the adjacency fails, or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds. A back-off algorithm increases the receive (Rx) interval by two if the local BFD instance is the reason for the session flap. The transmission (Tx) interval is increased by two if the remote BFD instance is the reason for the session flap. You can use the `clear bfd adaptation` command to return BFD interval timers to their configured values. The `clear bfd adaptation` command is hitless, meaning that the command does not affect traffic flow on the routing device.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

Statement introduced in Junos OS Release 13.2 for Layer 2 VPNs and VPLS.

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

community (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1448](#)
- [Hierarchy Level | 1448](#)
- [Description | 1449](#)
- [Options | 1449](#)
- [Required Privilege Level | 1449](#)
- [Release Information | 1449](#)

Syntax

```
community community-name {  
    invert-match;  
    members community-members;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name policy-options],  
[edit logical-systems logical-system-name protocols l2circuit local-switching interface  
interface-name backup-neighbor address],  
[edit logical-systems logical-system-name protocols l2circuit neighbor address  
interface interface-name],  
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name backup-neighbor address],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
neighbor address backup-neighbor address],  
[edit policy-options],  
[edit protocols l2circuit local-switching interface interface-name backup-neighbor address],  
[edit protocols l2circuit neighbor address interface interface-name],  
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor address],
```

```
[edit routing-instances routing-instance-name protocols vpls neighbor address backup-neighbor
address]
```

Description

Specify the community for the Layer 2 circuit.

Options

community-name—Name of the Layer 2 circuit community.

invert-match—Invert the results of the community expression match.

members community-members—Specify the members of the community.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Hierarchy levels associated with the *backup-neighbor* statement (pseudowire redundancy) added in Junos OS Release 9.2.

RELATED DOCUMENTATION

[Configuring the Layer 2 Circuit Community | 373](#)

[Configuring Pseudowire Redundancy on the PE Router | 226](#)

[Example: Configuring Layer 2 Circuit Switching Protection | 461](#)

connection-protection

IN THIS SECTION

- [Syntax | 1450](#)
- [Hierarchy Level | 1450](#)
- [Description | 1450](#)
- [Required Privilege Level | 1450](#)
- [Release Information | 1451](#)

Syntax

```
connection-protection;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface  
interface-name],  
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface],  
[edit protocols l2circuit local-switching interface interface-name],  
[edit protocols l2circuit neighbor address interface interface-name]
```

Description

Enable connection protection on the Layer 2 circuit. Connection protection enables you to configure a redundant pseudowire to act as a backup connection and can be configured between PE routers, maintaining Layer 2 circuit and VPLS services after certain types of failures. This feature helps to improve the reliability of networks where a single point of failure could interrupt service for customers.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

| [Example: Configuring Layer 2 Circuit Switching Protection](#) | 461

connectivity-type

IN THIS SECTION

- [Syntax](#) | 1451
- [Hierarchy Level](#) | 1451
- [Description](#) | 1452
- [Default](#) | 1452
- [Options](#) | 1452
- [Required Privilege Level](#) | 1452
- [Release Information](#) | 1452

Syntax

```
connectivity-type (ce | irb | permanent);
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Specify when a VPLS connection is taken down depending on whether or not the interface for the VPLS routing instance is customer-facing or integrated routing and bridging (IRB).

NOTE: The `connectivity-type` statement is not supported for FEC 129 VPLS (also known as LDP VPLS with BGP-based autodiscovery).

Default

`ce`

Options

`ce`—Require that for the VPLS connection to be up, the customer-facing interface for the VPLS routing instance must also be up. If the customer-facing interface fails, the VPLS connection is taken down.

`irb`—Allow a VPLS connection to remain up so long as an IRB interface is configured for the VPLS routing instance.

`permanent`—Allow a VPLS connection to remain up until specifically taken down. This option is reserved for use in configuring Layer 2 Wholesale subscriber networks. See the *Broadband Subscriber Management Solutions Guide* for details about configuring a Layer 2 Wholesale network.

NOTE: To specifically take down a VPLS routing instance that is using the `permanent` option, all associated static logical interfaces must also be down.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.1.

`irb` option introduced in Junos OS Release 9.3.

`permanent` option introduced in Junos OS Release 10.4.

RELATED DOCUMENTATION

[Configuring VPLS Routing Instance and VPLS Interface Connectivity | 685](#)

[Configuring Separate NNI Routing Instances for Layer 2 Wholesale Service Retailers](#)

control-channel (Protocols OAM)

IN THIS SECTION

- [Syntax | 1453](#)
- [Hierarchy Level | 1453](#)
- [Description | 1454](#)
- [Options | 1454](#)
- [Required Privilege Level | 1454](#)
- [Release Information | 1454](#)

Syntax

```
control-channel {  
    pwe3-control-word;  
    pw-label-ttl-1;  
    router-alert-label;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn oam],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
oam],  
[edit routing-instances routing-instance-name protocols l2vpn oam],  
[edit routing-instances routing-instance-name protocols vpls oam]
```


Description

Configure the Virtual Circuit Connection Verification (VCCV) BFD control channel. VCCV provides a control channel associated with a pseudowire. You can configure a number of different CV types for this control channel, based on the configuration of the pseudowire.

Options

`pwe3-control-word`—For BGP-based pseudowires that send OAM packets with a control word that has 0001b as the first nibble.

`pw-label-ttl-1`—For BGP-based pseudowires that send OAM packets with the MPLS pseudowire label and time-to-live (TTL) set to 1.

`router-alert-label`—For BGP-based pseudowires that send OAM packets with router alert label.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

RELATED DOCUMENTATION

[Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS](#) | 234

control-word (Protocols Layer 2 Circuit Neighbor)

IN THIS SECTION

- [Syntax](#) | 1455
- [Hierarchy Level](#) | 1455
- [Description](#) | 1455

- Options | 1455
- Required Privilege Level | 1455
- Release Information | 1456

Syntax

```
(control-word | no-control-word);
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address  
interface interface-name],  
[edit protocols l2circuit neighbor address interface interface-name]
```

Description

Specify the control word. The control word is four bytes long and is inserted between the Layer 2 protocol data unit (PDU) being transported and the virtual circuit (VC) label that is used for demultiplexing.

Options

`control-word`—Enable the use of the control word.

- **Default:** A null control word is enabled by default. You can also configure the control word explicitly using the `control-word` statement.

`no-control-word`—Disable the use of the control word.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring the Control Word for Frame Relay Interfaces](#) | 363

control-word (Protocols Layer 2 VPN)

IN THIS SECTION

- [Syntax](#) | 1456
- [Hierarchy Level](#) | 1456
- [Description](#) | 1457
- [Default](#) | 1457
- [Required Privilege Level](#) | 1457
- [Release Information](#) | 1457

Syntax

```
control-word;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn],  
[edit routing-instances routing-instance-name protocols l2vpn]
```

Description

Specify the control word. The control word is 4 bytes long and is inserted between the Layer 2 protocol data unit (PDU) being transported and the virtual connection (VC) label that is used for demultiplexing.

NOTE: The following configuration statements are ignored for time-division multiplexing pseudowires at the [edit protocols l2vpn] hierarchy level:

- control-word
- no-control-word

Default

The control word is enabled by default. You can also configure the control word explicitly using the control-word statement.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Disabling the Control Word for Layer 2 VPNs | 214](#)

[no-control-word \(Protocols Layer 2 VPN\) | 1596](#)

control-word

IN THIS SECTION

- [Syntax | 1458](#)
- [Hierarchy Level | 1458](#)
- [Description | 1458](#)
- [Required Privilege Level | 1459](#)
- [Release Information | 1459](#)

Syntax

```
control-word;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
mesh-group mesh-group-name neighbor address static],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
neighbor address static],  
[edit routing-instances routing-instance-name protocols vpls],  
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor  
address static],  
[edit routing-instances routing-instance-name protocols vpls neighbor address static]
```

Description

Set control-word to request that other routers insert a control word between the label stack and the MPLS payload.

By default control-word is enabled or disabled for static pseudowires in instance and in mesh-group is based on what is configured for VPLS instance. [Table 30 on page 1459](#) summarizes how the control-word

is enabled or disabled based on control-word configuration at VPLS instance and at static pseudowires in mesh-group.

Table 30: Status of control-word for static pseudowire with respect to control-word at VPLS instance

Control-word Configuration at VPLS Instance	Control-word Configuration at Static Pseudowire in Mesh-group	Control-word Enabled or Disabled for Static Pseudowire
default	default	disabled
default	control-word	enabled
default	no-control-word	disabled
control-word	default	enabled
control-word	control-word	enabled
control-word	no-control-word	disabled
no-control-word	default	disabled
no-control-word	control-word	enabled
no-control-word	no-control-word	disabled

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

Statement introduced for static pseudowires in mesh-group and in VPLS instance in Junos OS Release 20.3R1.

RELATED DOCUMENTATION

[Control Word for BGP VPLS Overview | 622](#)

[Configuring a Control Word for BGP VPLS | 623](#)

[no-control-word | 1594](#)

deep-vlan-qualified-learning

IN THIS SECTION

- [Syntax | 1460](#)
- [Hierarchy Level | 1460](#)
- [Description | 1460](#)
- [Required Privilege Level | 1461](#)
- [Release Information | 1461](#)

Syntax

```
deep-vlan-qualified-learning vlan_tag_number;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical_unit_number]
```

Description

Enable qualified MAC learning on the third VLAN tag (innermost) of an ingress 3-tagged packet, without any kind of implicit VLAN manipulation. If the packet has 2 tags, MAC learning happens on the second

VLAN. If the ingress packet has more than 3 tags, all tags beyond the third tag are treated as part of data and not considered for learning. For bidirectional traffic flow `input-vlan-map pop` must be configured.

NOTE: In Junos OS Release 17.4R1 the `vlan_tag_number` is 3 only.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Command introduced in Junos OS Release 17.4R1.

RELATED DOCUMENTATION

[vlan-id inner-all](#) | 1708

[Understanding Qualified MAC Learning](#) | 1222

default-isid

IN THIS SECTION

- [Syntax](#) | 1462
- [Hierarchy Level](#) | 1462
- [Description](#) | 1462
- [Options](#) | 1462
- [Required Privilege Level](#) | 1462
- [Release Information](#) | 1462

Syntax

```
default-isid isid-number;
```

Hierarchy Level

```
[edit routing-instances routing-instance-name service-groups service-group-name pbb-service-options]
```

Description

For IEEE 802.1ah provider backbone bridge (PBB) configurations, configure the default service identifier (I-SID) for all unmapped service VLANs (S-VLANs) for the customer routing instance (I-component) service group.

Options

~~*default-isid*~~—Default service identifier. Enter an I-SID in the range from **256** through **16777214**.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in JUNOS Release 10.0.

RELATED DOCUMENTATION

| [Example: Configuring E-LINE and E-LAN Services for a PBB Network on MX Series Routers](#)

description (Protocols Layer 2 Circuit Neighbor)

IN THIS SECTION

- [Syntax | 1463](#)
- [Hierarchy Level | 1463](#)
- [Description | 1463](#)
- [Required Privilege Level | 1463](#)
- [Release Information | 1463](#)

Syntax

```
description text;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name],  
[edit protocols l2circuit neighbor address interface interface-name]
```

Description

Provide a text description for the Layer 2 circuit. If the text includes one or more spaces, enclose the entire text string in quotation marks (" ").

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| *Configuring Routing Instances on PE Routers in VPNs*

description (Protocols Layer 2 VPN)

IN THIS SECTION

- [Syntax | 1464](#)
- [Hierarchy Level | 1464](#)
- [Description | 1464](#)
- [Options | 1465](#)
- [Required Privilege Level | 1465](#)
- [Release Information | 1465](#)

Syntax

```
description text;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn site site-name interface interface-name],  
[edit routing-instances routing-instance-name protocols l2vpn site site-name interface interface-  
name]
```

Description

Describe the VPN or virtual private LAN service (VPLS) routing instance.

Options

text—Provide a text description. If the text includes one or more spaces, enclose it in quotation marks (" "). Any descriptive text you include is displayed in the output of the `show route instance detail` command and has no effect on operation.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring the Site | 150](#)

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

detection-time (BFD Liveness Detection)

IN THIS SECTION

- [Syntax | 1466](#)
- [BGP | 1466](#)
- [EVPN, L2VPN, VPLS | 1466](#)
- [Description | 1467](#)
- [Options | 1468](#)
- [Required Privilege Level | 1468](#)
- [Release Information | 1468](#)

Syntax

```
detection-time {
    threshold milliseconds;
}
```

BGP

```
[edit logical-systems name protocols                bgp                bfd-liveness-detection],
[edit logical-systems name protocols                bgpgroup            bfd-liveness-detection],
[edit logical-systems name protocols                bgp group name      neighbor address bfd-liveness-
detection],
[edit logical-systems name                routing-instances            name
protocols                bgp                bfd-liveness-detection],
[edit logical-systems name                routing-instances            name
protocols                bgpgroup            bfd-liveness-detection],
[edit logical-systems name                routing-instances            name
protocols                bgpgroup neighbor address bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols
bgp                bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols
bgpgroup            bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols                bgpgroup
neighbor address bfd-liveness-detection],
[edit protocols bgp    bfd-liveness-detection],
[edit protocols bgp group    bfd-liveness-detection],
[edit protocols bgp group neighbor address bfd-liveness-detection],
[edit routing-instances name protocols                bgp                bfd-liveness-detection],
[edit routing-instances name protocols                bgp group            bfd-liveness-detection],
[edit routing-instances name protocols                bgp group neighbor address bfd-liveness-
detection],
[edit tenants name routing-instances name protocols bgp                bfd-liveness-detection]
[edit tenants name routing-instances name protocols bgp group            bfd-liveness-detection]
[edit tenants name routing-instances name protocols bgp groupneighbor address bfd-liveness-detection]
```

EVPN, L2VPN, VPLS

```
[edit logical-systems name                routing-instances            name protocols (evpn |
l2vpn | vpls) oam                bfd-liveness-detection],
```

```

[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls)mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls)neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls)mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-
detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls)mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],

```

Description

Enable BFD failure detection. The BFD failure detection timers are adaptive and can be adjusted to be faster or slower. The lower the BFD failure detection timer value, the faster the failure detection and vice versa. For example, the timers can adapt to a higher value if the adjacency fails (that is, the timer detects failures more slowly). Or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds. A back-off algorithm increases the receive (Rx) interval by two if the local BFD instance is the reason for the session flap. The transmission (Tx) interval is increased by two if the remote BFD instance is the reason for the session flap. You can use the `clear bfd adaptation` command to return BFD interval timers to their configured values. The `clear bfd adaptation` command is hitless, meaning that the command does not affect traffic flow on the routing device.

Starting in Junos OS Release 20.3R1, we support distributed mode for BFD failure detection on the SRX5000 line of devices with SPC3 card. The distributed mode provides faster BFD failure detection of 300 (3 x 100) ms. You can enable distributed mode when you configure the BFD failure detection timer value less than 500 ms.

Starting in Junos OS Release 21.1R1, we support distributed mode for BFD on SRX1500, SRX4100, SRX4200, and SRX4600. This mode provides a faster BFD failure detection time of 3 x 300 ms.

For optimization and performance enhancement, you must configure the BFD failure detection timer value in multiples of 50 ms.

Options

threshold milliseconds

Specify the threshold for the adaptation of the BFD session detection time. When the detection time adapts to a value equal to or greater than the threshold, a single trap and a single system log message are sent.

NOTE: The threshold value must be equal to or greater than the transmit interval.

The threshold time must be equal to or greater than the value specified in the `minimum-interval` or the `minimum-receive-interval` statement.

- **Range:** 1 through 255,000 milliseconds

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.2.

Support for BFD authentication introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

Understanding How BFD Detects Network Failures

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD for BGP](#)

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

[bfd-liveness-detection](#)

egress-protection (Layer 2 circuit)

IN THIS SECTION

- [Syntax | 1469](#)
- [Hierarchy Level | 1469](#)
- [Description | 1470](#)
- [Options | 1470](#)
- [Required Privilege Level | 1470](#)
- [Release Information | 1470](#)

Syntax

```
egress-protection {  
    protected-l2circuit {  
        egress-pe address;  
        ingress-pe address;  
        virtual-circuit-id identifier;  
    }  
    protector-interface interface-name;  
    protector-pe address {  
        context-identifier identifier;  
        lsp lsp-name;  
    }  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name],  
[edit protocols l2circuit neighbor address interface interface-name]
```


Description

Configures an egress protection virtual circuit (EPVC).

Options

The other statements are explained separately.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS release 10.4.

RELATED DOCUMENTATION

| [Example: Configuring an Egress Protection LSP for a Layer 2 Circuit](#) | 438

egress-protection (MPLS)

IN THIS SECTION

- [Syntax](#) | 1471
- [Hierarchy Level](#) | 1471
- [Description](#) | 1471
- [Options](#) | 1471
- [Required Privilege Level](#) | 1471
- [Release Information](#) | 1472

Syntax

```
egress-protection {
  context-identifier context-id {
    primary | protector;
    metric igp-metric-value;
    advertise-mode (stub-alias | stub-proxy);
  }
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols mpls],
[edit logical-systems logical-system-name protocols mpls label-switched-path lsp-name],
[edit protocols mpls],
[edit protocols mpls label-switched-path lsp-name]
```

Description

Enables an Edge Protection Virtual Circuit (EPVC) for the MPLS protocol.

Options

context-identifier *context-id-ip-address* (Optional) The context identifier IPv4 address.

metric *igp-metric-value* (Optional) The IGP metric value ranging from 2 through 16777215.

(primary | protector) On the primary PE router, configure as type primary. On the protector PE router, configure as type protector.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.4.

Options `primary`, `protector`, and `metric` introduced in Junos OS Release 11.4R3.

Option `advertise-mode` introduced in Junos OS Release 13.3.

RELATED DOCUMENTATION

Example: Configuring Egress Protection for Layer 3 VPN Services

Example: Configuring Layer 3 VPN Egress Protection with RSVP and LDP

encapsulation (Logical Interface)

IN THIS SECTION

- [Syntax | 1472](#)
- [Hierarchy Level | 1473](#)
- [Description | 1473](#)
- [Options | 1473](#)
- [Required Privilege Level | 1476](#)
- [Release Information | 1476](#)

Syntax

```
encapsulation (atm-ccc-cell-relay | atm-ccc-vc-mux | atm-cisco-nlpid | atm-mlppp-llc | atm-nlpid
| atm-ppp-llc | atm-ppp-vc-mux | atm-snap | atm-tcc-snap | atm-tcc-vc-mux | atm-vc-mux | ether-
over-atm-llc | ether-vpls-over-atm-llc | ether-vpls-over-fr | ether-vpls-over-ppp | ethernet |
ethernet-ccc | ethernet-vpls | ethernet-vpls-fr | frame-relay-ccc | frame-relay-ether-type |
frame-relay-ether-type-tcc | frame-relay-ppp | frame-relay-tcc | gre-fragmentation | multilink-
frame-relay-end-to-end | multilink-ppp | ppp-over-ether | ppp-over-ether-over-atm-llc | vlan-
bridge | vlan-ccc | vlan-vci-ccc | vlan-tcc | vlan-vpls | vxlan);
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number],
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number],
[edit interfaces rlsq number unit logical-unit-number]
[edit protocols evpn]
```

Description

Configure a logical link-layer encapsulation type. Not all encapsulation types are supported on the switches. See the switch CLI.

Starting in Junos OS Release 20.1R1, aggregated ethernet interfaces supports VLAN TCC (Translational cross-connect) encapsulation on MX series platforms. See [Configuring VLAN TCC Encapsulation](#) for more details. Non-ethernet media types, SONET and ATM interfaces are only supported. It is expected that the user will have the member links of aggregated ethernet with supported hardware for configuring VLAN TCC encapsulation and no commit check is performed externally for the aggregated ethernet (AE) interfaces.

Options

`atm-ccc-cell-relay`—Use ATM cell-relay encapsulation.

`atm-ccc-vc-mux`—Use ATM virtual circuit (VC) multiplex encapsulation on CCC circuits. When you use this encapsulation type, you can configure the ccc family only.

`atm-cisco-nlpid`—Use Cisco ATM network layer protocol identifier (NLPID) encapsulation. When you use this encapsulation type, you can configure the inet family only.

`atm-mlppp-llc`—For ATM2 IQ interfaces only, use Multilink Point-to-Point (MLPPP) over AAL5 LLC. For this encapsulation type, your router must be equipped with a Link Services or Voice Services PIC. MLPPP over ATM encapsulation is not supported on ATM2 IQ OC48 interfaces.

`atm-nlpid`—Use ATM NLPID encapsulation. When you use this encapsulation type, you can configure the inet family only.

`atm-ppp-llc`—(ATM2 IQ interfaces and MX Series routers with MPC/MIC interfaces using the ATM MIC with SFP only) Use PPP over AAL5 LLC encapsulation.

`atm-ppp-vc-mux`—(ATM2 IQ interfaces and MX Series routers with MPC/MIC interfaces using the ATM MIC with SFP only) Use PPP over ATM AAL5 multiplex encapsulation.

`atm-snap`—(All interfaces including MX Series routers with MPC/MIC interfaces using the ATM MIC with SFP) Use ATM subnetwork attachment point (SNAP) encapsulation.

`atm-tcc-snap`—Use ATM SNAP encapsulation on translational cross-connect (TCC) circuits.

`atm-tcc-vc-mux`—Use ATM VC multiplex encapsulation on TCC circuits. When you use this encapsulation type, you can configure the `tcc` family only.

`atm-vc-mux`—(All interfaces including MX Series routers with MPC/MIC interfaces using the ATM MIC with SFP) Use ATM VC multiplex encapsulation. When you use this encapsulation type, you can configure the `inet` family only.

`ether-over-atm-llc`—(All IP interfaces including MX Series routers with MPC/MIC interfaces using the ATM MIC with SFP) For interfaces that carry IP traffic, use Ethernet over ATM LLC encapsulation. When you use this encapsulation type, you cannot configure multipoint interfaces.

`ether-vpls-over-atm-llc`—For ATM2 IQ interfaces only, use the Ethernet virtual private LAN service (VPLS) over ATM LLC encapsulation to bridge Ethernet interfaces and ATM interfaces over a VPLS routing instance (as described in RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*). Packets from the ATM interfaces are converted to standard ENET2/802.3 encapsulated Ethernet frames with the frame check sequence (FCS) field removed.

`ether-vpls-over-fr`—For E1, T1, E3, T3, and SONET interfaces only, use the Ethernet virtual private LAN service (VPLS) over Frame Relay encapsulation to support Bridged Ethernet over Frame Relay encapsulated TDM interfaces for VPLS applications, per RFC 2427, *Multiprotocol Interconnect over Frame Relay*.

NOTE: The SONET/SDH OC3/STM1 (Multi-Rate) MIC with SFP, the Channelized SONET/SDH OC3/STM1 (Multi-Rate) MIC with SFP, and the DS3/E3 MIC do not support Ethernet over Frame Relay encapsulation.

`ether-vpls-over-ppp`—For E1, T1, E3, T3, and SONET interfaces only, use the Ethernet virtual private LAN service (VPLS) over Point-to-Point Protocol (PPP) encapsulation to support Bridged Ethernet over PPP-encapsulated TDM interfaces for VPLS applications.

`ethernet`—Use Ethernet II encapsulation (as described in RFC 894, *A Standard for the Transmission of IP Datagrams over Ethernet Networks*).

`ethernet-ccc`—Use Ethernet CCC encapsulation on Ethernet interfaces.

`ethernet-vpls`—Use Ethernet VPLS encapsulation on Ethernet interfaces that have VPLS enabled and that must accept packets carrying standard Tag Protocol ID (TPID) values.

NOTE: The built-in Gigabit Ethernet PIC on an M7i router does not support extended VLAN VPLS encapsulation.

`ethernet-vpls-fr`—Use in a VPLS setup when a CE device is connected to a PE router over a time-division multiplexing (TDM) link. This encapsulation type enables the PE router to terminate the outer layer 2 Frame Relay connection, use the *802.1p* bits inside the inner Ethernet header to classify the packets, look at the MAC address from the Ethernet header, and use the MAC address to forward the packet into a given VPLS instance.

`frame-relay-ccc`—Use Frame Relay encapsulation on CCC circuits. When you use this encapsulation type, you can configure the `ccc` family only.

`frame-relay-ether-type`—Use Frame Relay ether type encapsulation for compatibility with Cisco Frame Relay. The physical interface must be configured with flexible-frame-relay encapsulation.

`frame-relay-ether-type-tcc`—Use Frame Relay ether type TCC for Cisco-compatible Frame Relay on TCC circuits to connect different media. The physical interface must be configured with flexible-frame-relay encapsulation.

`frame-relay-ppp`—Use PPP over Frame Relay circuits. When you use this encapsulation type, you can configure the `ppp` family only.

`frame-relay-tcc`—Use Frame Relay encapsulation on TCC circuits for connecting different media. When you use this encapsulation type, you can configure the `tcc` family only.

`gre-fragmentation`—For adaptive services interfaces only, use GRE fragmentation encapsulation to enable fragmentation of IPv4 packets in GRE tunnels. This encapsulation clears the do not fragment (DF) bit in the packet header. If the packet's size exceeds the tunnel's maximum transmission unit (MTU) value, the packet is fragmented before encapsulation.

`multilink-frame-relay-end-to-end`—Use MLFR FRF.15 encapsulation. This encapsulation is used only on multilink, link services, and voice services interfaces and their constituent T1 or E1 interfaces, and is supported on LSQ and redundant LSQ interfaces.

`multilink-ppp`—Use MLPPP encapsulation. This encapsulation is used only on multilink, link services, and voice services interfaces and their constituent T1 or E1 interfaces.

`ppp-over-ether`—Use PPP over Ethernet encapsulation to configure an underlying Ethernet interface for a dynamic PPPoE logical interface on M120 and M320 routers with Intelligent Queuing 2 (IQ2) PICs, and on MX Series routers with MPCs.

`ppp-over-ether-over-atm-llc`—(MX Series routers with MPCs using the ATM MIC with SFP only) For underlying ATM interfaces, use PPP over Ethernet over ATM LLC encapsulation. When you use this encapsulation type, you cannot configure the interface address. Instead, configure the interface address on the PPP interface.

`vlan-bridge`—Use Ethernet VLAN bridge encapsulation on Ethernet interfaces that have IEEE *802.1Q* tagging, flexible-ethernet-services, and bridging enabled and that must accept packets carrying TPID 0x8100 or a user-defined TPID.

`vlan-ccc`—Use Ethernet virtual LAN (VLAN) encapsulation on CCC circuits. When you use this encapsulation type, you can configure the `ccc` family only.

`vlan-vci-ccc`—Use ATM-to-Ethernet interworking encapsulation on CCC circuits. When you use this encapsulation type, you can configure the `ccc` family only.

`vlan-tcc`—Use Ethernet VLAN encapsulation on TCC circuits. When you use this encapsulation type, you can configure the `tcc` family only.

`vlan-vpls`—Use Ethernet VLAN encapsulation on VPLS circuits.

`vxlan`—Use VXLAN data plane encapsulation for EVPN.

Required Privilege Level

`interface`—To view this statement in the configuration.

`interface-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Release History Table

Release	Description
20.1R1	Starting in Junos OS Release 20.1R1, aggregated ethernet interfaces supports VLAN TCC (Translational cross-connect) encapsulation on MX series platforms.

RELATED DOCUMENTATION

[Configuring Layer 2 Switching Cross-Connects Using CCC](#)

[Configuring the Encapsulation for Layer 2 Switching TCCs](#)

[Configuring Interface Encapsulation on Logical Interfaces](#)

[Configuring the CCC Encapsulation for LSP Tunnel Cross-Connects](#)

[Circuit and Translational Cross-Connects Overview](#)

[Identifying the Access Concentrator](#)

[Configuring ATM Interface Encapsulation](#)

[Configuring VLAN and Extended VLAN Encapsulation](#)

[Configuring ATM-to-Ethernet Interworking](#)

[Configuring Interface Encapsulation on PTX Series Packet Transport Routers](#)

[Configuring CCC Encapsulation for Layer 2 VPNs | 209](#)

[Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits | 210](#)

[Configuring ATM for Subscriber Access](#)

[Understanding CoS on ATM IMA Pseudowire Interfaces Overview](#)

[Configuring Policing on an ATM IMA Pseudowire](#)

encapsulation

IN THIS SECTION

- [Syntax | 1477](#)
- [Syntax \(SRX Series Physical Interfaces\) | 1478](#)
- [Syntax \(SRX Series Logical Interfaces\) | 1478](#)
- [Hierarchy Level \(Physical Interfaces\) | 1478](#)
- [Hierarchy Level \(Logical Interfaces\) | 1478](#)
- [Description | 1478](#)
- [Default | 1478](#)
- [Physical Interface Options and Logical Interface Options | 1479](#)
- [Required Privilege Level | 1483](#)
- [Release Information | 1483](#)

Syntax

```
encapsulation (atm-ccc-cell-relay | atm-pvc | cisco-hdlc | cisco-hdlc-ccc | cisco-hdlc-tcc |
ethernet-bridge | ethernet-ccc | ethernet-over-atm | ethernet-tcc | ethernet-vpls | ethernet-
vpls-fr | ether-vpls-over-atm-llc | ethernet-vpls-ppp | extended-frame-relay-ccc | extended-
frame-relay-ether-type-tcc | extended-frame-relay-tcc | extended-vlan-bridge | extended-vlan-ccc
| extended-vlan-tcc | extended-vlan-vpls | flexible-ethernet-services | flexible-frame-relay |
frame-relay | frame-relay-ccc | frame-relay-ether-type | frame-relay-ether-type-tcc | frame-
relay-port-ccc | frame-relay-tcc | generic-services | multilink-frame-relay-uni-nni | ppp | ppp-
ccc | ppp-tcc | vlan-ccc | vlan-vci-ccc | vlan-vpls);
```


Syntax (SRX Series Physical Interfaces)

```
encapsulation (ether-vpls-ppp | ethernet-bridge | ethernet-ccc | ethernet-tcc | ethernet-vpls |
extended-frame-relay-ccc | extended-frame-relay-tcc | extended-vlan-bridge | extended-vlan-ccc |
extended-vlan-tcc | extended-vlan-vpls | flexible-ethernet-services | frame-relay-port-ccc |
vlan-ccc | vlan-vpls);
```

Syntax (SRX Series Logical Interfaces)

```
encapsulation ( dix | ether-vpls-fr | frame-relay-ppp | ppp-over-ether | vlan-bridge | vlan-ccc
| vlan-tcc | vlan-vpls );
```

Hierarchy Level (Physical Interfaces)

```
[edit interfaces interface-name]
[edit interfaces rlsq number:number]
```

Hierarchy Level (Logical Interfaces)

```
[edit interfaces interface-name unit logical-unit-number]
```

Description

Specify the physical link layer encapsulation type. For some devices, you may also specify the logical link layer encapsulation type. See [Feature Explorer](#) for more information.

NOTE: Not all encapsulation types are supported on all switches. See the switch CLI.

Default

ppp—Use serial PPP encapsulation.

Physical Interface Options and Logical Interface Options

For physical interfaces:

NOTE: EX Series switches do not support Frame Relay, ATM, PPP, SONET, or SATSOP encapsulation.

ACX Series routers do not support CISCO HDLC encapsulation.

- `atm-ccc-cell-relay`—Use ATM cell-relay encapsulation.
- `atm-pvc`—Defined in RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*. When you configure physical ATM interfaces with ATM PVC encapsulation, an RFC 2684-compliant ATM Adaptation Layer 5 (AAL5) tunnel is set up to route the ATM cells over a Multiprotocol Label Switching (MPLS) path that is typically established between two MPLS-capable routers using the Label Distribution Protocol (LDP).
- `cisco-hdlc`—Use Cisco-compatible High-Level Data Link Control (HDLC) framing. E1, E3, SONET/SDH, T1, and T3 interfaces can use Cisco HDLC encapsulation. Two related versions are supported:
 - CCC version (`cisco-hdlc-ccc`)—The logical interface does not require an encapsulation statement. When you use this encapsulation type, you can configure the `ccc` family only.
 - TCC version (`cisco-hdlc-tcc`)—Similar to CCC and has the same configuration restrictions, but used for circuits with different media on either side of the connection.
- `cisco-hdlc-ccc`—Use Cisco-compatible HDLC framing on CCC circuits.
- `cisco-hdlc-tcc`—Use Cisco-compatible HDLC framing on TCC circuits for connecting different media.
- `ethernet-bridge`—Use Ethernet bridge encapsulation on Ethernet interfaces that have bridging enabled and that must accept all packets.
- `ethernet-over-atm`—For interfaces that carry IPv4 traffic, use Ethernet over ATM encapsulation. When you use this encapsulation type, you cannot configure multipoint interfaces. As defined in RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*, this encapsulation type allows ATM interfaces to connect to devices that support only bridge protocol data units (BPDUs). Junos OS does not completely support bridging, but accepts BPDUs as a default gateway. If you use the router as an edge device, then the router acts as a default gateway. It accepts Ethernet LLC/SNAP frames with IP or ARP in the payload, and drops the rest. For packets destined to the Ethernet LAN, a route lookup is done using the destination IP address. If the route lookup yields a full address match, the packet is encapsulated with an LLC/SNAP and MAC header, and the packet is forwarded to the ATM interface.

- `ethernet-tcc`—For interfaces that carry IPv4 traffic, use Ethernet TCC encapsulation on interfaces that must accept packets carrying standard TPID values. For 8-port, 12-port, and 48-port Fast Ethernet PICs, TCC is not supported.
- `ethernet-vpls`—Use Ethernet VPLS encapsulation on Ethernet interfaces that have VPLS enabled and that must accept packets carrying standard TPID values. On M Series routers, except the M320 router, the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.
- `ethernet-vpls-fr`—Use in a VPLS setup when a CE device is connected to a PE device over a time division multiplexing (TDM) link. This encapsulation type enables the PE device to terminate the outer Layer 2 Frame Relay connection, use the *802.1p* bits inside the inner Ethernet header to classify the packets, look at the MAC address from the Ethernet header, and use the MAC address to forward the packet into a given VPLS instance.
- `ethernet-vpls-ppp`—Use in a VPLS setup when a CE device is connected to a PE device over a time division multiplexing (TDM) link. This encapsulation type enables the PE device to terminate the outer Layer 2 PPP connection, use the *802.1p* bits inside the inner Ethernet header to classify the packets, look at the MAC address from the Ethernet header, and use it to forward the packet into a given VPLS instance.
- `ether-vpls-over-atm-llc`—For ATM intelligent queuing (IQ) interfaces only, use the Ethernet virtual private LAN service (VPLS) over ATM LLC encapsulation to bridge Ethernet interfaces and ATM interfaces over a VPLS routing instance (as described in RFC 2684, *Multiprotocol Encapsulation over ATM Adaptation Layer 5*). Packets from the ATM interfaces are converted to standard ENET2/802.3 encapsulated Ethernet frames with the frame check sequence (FCS) field removed.
- `extended-frame-relay-ccc`—Use Frame Relay encapsulation on CCC circuits. This encapsulation type allows you to dedicate DLCIs 1 through 1022 to CCC. When you use this encapsulation type, you can configure the `ccc` family only.
- `extended-frame-relay-ether-type-tcc`—Use extended Frame Relay ether type TCC for Cisco-compatible Frame Relay for DLCIs 1 through 1022. This encapsulation type is used for circuits with different media on either side of the connection.
- `extended-frame-relay-tcc`—Use Frame Relay encapsulation on TCC circuits to connect different media. This encapsulation type allows you to dedicate DLCIs 1 through 1022 to TCC.
- `extended-vlan-bridge`—Use extended VLAN bridge encapsulation on Ethernet interfaces that have IEEE *802.1Q* VLAN tagging and bridging enabled and that must accept packets carrying TPID 0x8100 or a user-defined TPID.
- `extended-vlan-ccc`—Use extended VLAN encapsulation on CCC circuits with Gigabit Ethernet and 4-port Fast Ethernet interfaces that must accept packets carrying 802.1Q values. Extended VLAN CCC encapsulation supports TPIDs 0x8100, 0x9100, and 0x9901. When you use this encapsulation type,

you can configure the ccc family only. For 8-port, 12-port, and 48-port Fast Ethernet PICs, extended VLAN CCC is not supported. For 4-port Gigabit Ethernet PICs, extended VLAN CCC is not supported.

- `extended-vlan-tcc`—For interfaces that carry IPv4 traffic, use extended VLAN encapsulation on TCC circuits with Gigabit Ethernet interfaces on which you want to use 802.1Q tagging. For 4-port Gigabit Ethernet PICs, extended VLAN TCC is not supported.
- `extended-vlan-vpls`—Use extended VLAN VPLS encapsulation on Ethernet interfaces that have VLAN 802.1Q tagging and VPLS enabled and that must accept packets carrying TPIDs 0x8100, 0x9100, and 0x9901. On M Series routers, except the M320 router, the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.

NOTE: The built-in Gigabit Ethernet PIC on an M7i router does not support extended VLAN VPLS encapsulation.

- `flexible-ethernet-services`—For Gigabit Ethernet IQ interfaces and Gigabit Ethernet PICs with small form-factor pluggable transceivers (SFPs) (except the 10-port Gigabit Ethernet PIC and the built-in Gigabit Ethernet port on the M7i router), and for Gigabit Ethernet interfaces, use flexible Ethernet services encapsulation when you want to configure multiple per-unit Ethernet encapsulations. Aggregated Ethernet bundles can use this encapsulation type. This encapsulation type allows you to configure any combination of route, TCC, CCC, Layer 2 virtual private networks (VPNs), and VPLS encapsulations on a single physical port. If you configure flexible Ethernet services encapsulation on the physical interface, VLAN IDs from 1 through 511 are no longer reserved for normal VLANs.
- `flexible-frame-relay`—For IQ interfaces only, use flexible Frame Relay encapsulation when you want to configure multiple per-unit Frame Relay encapsulations. This encapsulation type allows you to configure any combination of TCC, CCC, and standard Frame Relay encapsulations on a single physical port. Also, each logical interface can have any DLCI value from 1 through 1022.
- `frame-relay`—Use Frame Relay encapsulation is defined in RFC 1490, *Multiprotocol Interconnect over Frame Relay*. E1, E3, link services, SONET/SDH, T1, T3, and voice services interfaces can use Frame Relay encapsulation.
- `frame-relay-ccc`—Use Frame Relay encapsulation on CCC circuits. This encapsulation is same as standard Frame Relay for DLCIs 0 through 511. DLCIs 512 through 1022 are dedicated to CCC. The logical interface must also have `frame-relay-ccc` encapsulation. When you use this encapsulation type, you can configure the ccc family only.
- `frame-relay-ether-type`—Use Frame Relay ether type encapsulation for compatibility with the Cisco Frame Relay. IETF frame relay encapsulation identifies the payload format using NLPID and SNAP

formats. Cisco-compatible Frame Relay encapsulation uses the Ethernet type to identify the type of payload.

NOTE: When the encapsulation type is set to Cisco-compatible Frame Relay encapsulation, ensure that the LMI type is set to ANSI or Q933-A.

- `frame-relay-ether-type-tcc`—Use Frame Relay ether type TCC for Cisco-compatible Frame Relay on TCC circuits to connect different media. This encapsulation is Cisco-compatible Frame Relay for DLCIs 0 through 511. DLCIs 512 through 1022 are dedicated to TCC.
- `frame-relay-port-ccc`—Use Frame Relay port CCC encapsulation to transparently carry all the DLCIs between two customer edge (CE) routers without explicitly configuring each DLCI on the two provider edge (PE) routers with Frame Relay transport. The connection between the two CE routers can be either user-to-network interface (UNI) or network-to-network interface (NNI); this is completely transparent to the PE routers. When you use this encapsulation type, you can configure the `ccc` family only.
- `frame-relay-tcc`—This encapsulation is similar to Frame Relay CCC and has the same configuration restrictions, but used for circuits with different media on either side of the connection.
- `generic-services`—Use generic services encapsulation for services with a hierarchical scheduler.
- `multilink-frame-relay-uni-nni`—Use MLFR UNI NNI encapsulation. This encapsulation is used on link services, voice services interfaces functioning as FRF.16 bundles, and their constituent T1 or E1 interfaces, and is supported on LSQ and redundant LSQ interfaces.
-
- `ppp`—Use serial PPP encapsulation. This encapsulation is defined in RFC 1661, *The Point-to-Point Protocol (PPP) for the Transmission of Multiprotocol Datagrams over Point-to-Point Links*. PPP is the default encapsulation type for physical interfaces. E1, E3, SONET/SDH, T1, and T3 interfaces can use PPP encapsulation.
- `ppp-ccc`—Use serial PPP encapsulation on CCC circuits. When you use this encapsulation type, you can configure the `ccc` family only.
- `ppp-tcc`—Use serial PPP encapsulation on TCC circuits for connecting different media. When you use this encapsulation type, you can configure the `tcc` family only.
- `vlan-ccc`—Use Ethernet VLAN encapsulation on CCC circuits. VLAN CCC encapsulation supports TPID 0x8100 only. When you use this encapsulation type, you can configure the `ccc` family only.

- `vlan-vci-ccc`—Use ATM-to-Ethernet interworking encapsulation on CCC circuits. When you use this encapsulation type, you can configure the `ccc` family only. All logical interfaces configured on the Ethernet interface must also have the encapsulation type set to `vlan-vci-ccc`.
- `vlan-vpls`—Use VLAN VPLS encapsulation on Ethernet interfaces with VLAN tagging and VPLS enabled. Interfaces with VLAN VPLS encapsulation accept packets carrying standard TPID values only. On M Series routers, except the M320 router, the 4-port Fast Ethernet TX PIC and the 1-port, 2-port, and 4-port, 4-slot Gigabit Ethernet PICs can use the Ethernet VPLS encapsulation type.

NOTE:

- Label-switched interfaces (LSIs) do not support VLAN VPLS encapsulation. Therefore, you can only use VLAN VPLS encapsulation on a PE-router-to-CE-router interface and not a core-facing interface.
- Starting with Junos OS release 13.3, a commit error occurs when you configure `vlan-vpls` encapsulation on a physical interface and configure family `inet` on one of the logical units. Previously, it was possible to commit this invalid configuration.

For logical interfaces:

- `frame-relay`—Configure a Frame Relay encapsulation when the physical interface has multiple logical units, and the units are either point to point or multipoint.
- `multilink-frame-relay-uni-nni`—Link services interfaces functioning as FRF.16 bundles can use Multilink Frame Relay UNI NNI encapsulation.
- `ppp`—For normal mode (when the device is using only one ISDN B-channel per call). Point-to-Point Protocol is for communication between two computers using a serial interface.
- `ppp-over-ether`—This encapsulation is used for underlying interfaces of `pp0` interfaces.

Required Privilege Level

`interface`—To view this statement in the configuration.

`interface-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Statement introduced in Junos OS Release 9.5.

RELATED DOCUMENTATION

Understanding Physical Encapsulation on an Interface
Configuring Interface Encapsulation on Physical Interfaces
Configuring CCC Encapsulation for Layer 2 VPNs 209
Configuring Layer 2 Switching Cross-Connects Using CCC
Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits 210
Configuring ATM Interface Encapsulation
Configuring ATM-to-Ethernet Interworking
Configuring VLAN and Extended VLAN Encapsulation
Configuring VLAN and Extended VLAN Encapsulation
Configuring Encapsulation for Layer 2 Wholesale VLAN Interfaces
Configuring Interfaces for Layer 2 Circuits 360
Configuring Interface Encapsulation on PTX Series Packet Transport Routers
Configuring MPLS LSP Tunnel Cross-Connects Using CCC
Configuring TCC
Configuring VPLS Interface Encapsulation 735
Configuring Interfaces for VPLS Routing 733
Defining the Encapsulation for Switching Cross-Connects
Configuring an MPLS-Based Layer 2 VPN (CLI Procedure)

encapsulation-type (Layer 2 Circuits)

IN THIS SECTION

- [Syntax | 1485](#)
- [Hierarchy Level | 1485](#)
- [Description | 1485](#)
- [Options | 1485](#)
- [Required Privilege Level | 1486](#)
- [Release Information | 1486](#)

Syntax

```
encapsulation-type (atm-aal5 | atm-cell | atm-cell-port-mode | atm-cell-vc-mode | atm-cell-vp-
mode | cesop | cisco-hdlc | ethernet | ethernet-vlan | frame-relay | frame-relay-port-mode |
interworking | ppp | satop-e1 | satop-e3 | satop-t1 | satop-t3);
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name],
[edit protocols l2circuit local-switching interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name]
```

Description

Specify the type of Layer 2 traffic transiting the Layer 2 circuit.

Options

atm-aal5—ATM Adaptation Layer (AAL/5)

atm-cell—ATM cell relay

atm-cell-port-mode—ATM cell relay port promiscuous mode

atm-cell-vc-mode—ATM VC cell relay nonpromiscuous mode

atm-cell-vp-mode—ATM virtual path (VP) cell relay promiscuous mode

cesop—CESOP-based Layer 2 circuit

cisco-hdlc—Cisco Systems-compatible HDLC

ethernet—Ethernet

ethernet-vlan—Ethernet VLAN

frame-relay—Frame Relay

frame-relay-port-mode—Frame Relay port mode

interworking—Layer 2.5 interworking

ppp—PPP

satsop-e1—SATSOP-E1-based Layer 2 circuit

satsop-e3—SATSOP-E3-based Layer 2 circuit

satsop-t1—SATSOP-T1-based Layer 2 circuit

satsop-t3—SATSOP-T3-based Layer 2 circuit

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.2.

RELATED DOCUMENTATION

| [Configuring the Encapsulation Type for the Layer 2 Circuit Neighbor Interface](#) | 363

encapsulation-type (Layer 2 VPNs)

IN THIS SECTION

- [Syntax](#) | 1487
- [Hierarchy Level](#) | 1487
- [Description](#) | 1487
- [Options](#) | 1487
- [Required Privilege Level](#) | 1488
- [Release Information](#) | 1488

Syntax

```
encapsulation-type (atm-aal5 | atm-cell | atm-cell-port-mode | atm-cell-vc-mode | atm-cell-vp-
mode | cesop | cisco-hdlc | ethernet | ethernet-vlan | frame-relay | frame-relay-port-mode |
interworking | ppp | satop-e1 | satop-e3 | satop-t1 | satop-t3);
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit protocols l2circuit neighbor address interface interface-name],
[edit routing-instances routing-instance-name protocols l2vpn],
[edit routing-instances routing-instance-name protocols l2vpn neighbor address],
[edit routing-instances routing-instance-name protocols vpls],
[edit routing-instances routing-instance-name protocols vpls neighbor address]
```

Description

Specify the type of Layer 2 traffic originating from the CE device. Only the ethernet and ethernet-vlan encapsulation types are supported for VPLS. Not all encapsulation types are supported on the switches. See the switch CLI.

Options

atm-aal5—ATM Adaptation Layer (AAL/5)

atm-cell—ATM cell relay

atm-cell-port-mode—ATM cell relay port promiscuous mode

atm-cell-vc-mode—ATM VC cell relay nonpromiscuous mode

atm-cell-vp-mode—ATM virtual path (VP) cell relay promiscuous mode

cesop—CESOP-based Layer 2 VPN

cisco-hdlc—Cisco Systems-compatible HDLC

ethernet—Ethernet

ethernet-vlan—Ethernet VLAN

frame-relay—Frame Relay

frame-relay-port-mode—Frame Relay port mode

interworking—Layer 2.5 interworking VPN

ppp—PPP

satsop-e1—SATSOP-E1-based Layer 2 VPN

satsop-e3—SATSOP-E3-based Layer 2 VPN

satsop-t1—SATSOP-T1-based Layer 2 VPN

satsop-t3—SATSOP-T3-based Layer 2 VPN

- **Default:** For VPLS networks, the default encapsulation type is ethernet.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.2.

RELATED DOCUMENTATION

[Configuring the Encapsulation Type | 153](#)

[Configuring VPLS Routing Instances | 674](#)

[Configuring the Encapsulation Type for the Layer 2 Circuit Neighbor Interface | 363](#)

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

end-interface

IN THIS SECTION

- [Syntax | 1489](#)
- [Hierarchy Level | 1489](#)
- [Description | 1489](#)
- [Required Privilege Level | 1490](#)
- [Release Information | 1490](#)

Syntax

```
end-interface {  
    interface interface-name;  
    no-revert;  
    protect-interface interface-name;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface  
  interface-name],  
[edit protocols l2circuit local-switching interface interface-name]
```

Description

Specify the end interface for a local interface switch.

NOTE: The protect interface must be configured prior to configuring the no-revert statement.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring Local Interface Switching in Layer 2 Circuits](#) | 357

exclusive-mac

IN THIS SECTION

- [Syntax](#) | 1490
- [Hierarchy Level](#) | 1490
- [Description](#) | 1491
- [Options](#) | 1491
- [Required Privilege Level](#) | 1491
- [Release Information](#) | 1492

Syntax

```
exclusive-mac virtual-mac-mac-address/mask;
```

Hierarchy Level

```
[edit protocols l2-learning global-mac-move]
```

Description

Exclude MAC addresses from the MAC move limit algorithm.

The global MAC move feature is used to track MAC addresses when they appear on a different physical interface or within a different unit of the same physical interface. When you configure the `exclusive-mac virtual-mac-mac-address/mask` parameter at the `[edit protocols l2-learning global-mac-move]` hierarchy level, specified MAC addresses are excluded and will not be tracked. In addition, excluded MAC addresses cannot be pinned when `mac-pinning` is set on an interface.

This feature can be useful in OVSDB-managed topologies with VRRP servers deployed in a redundancy configuration (primary/member), and when MAC move limit is configured. Both servers could negotiate primary role, and the same MAC address could be learned under the global MAC move feature while negotiation is occurring. In such cases, excluding the MAC address of the VRRP servers by using the `exclusive-mac` statement prevents this “false” move from being tracked.

The following example excludes VRRP V2 virtual router MAC addresses, as defined in RFC 3768:

```
[edit]
set protocols l2-learning global-mac-move exclusive-mac 00:00:5e:00:01:00/40
```

The following example excludes VRRP V3 virtual router MAC addresses, as defined in RFC 5798:

```
[edit]
set protocols l2-learning global-mac-move exclusive-mac 00:00:5e:00:02:00/40
```

Options

<i>virtual-mac-mac-address/mask</i>	Specify a MAC address and a mask. If the mask is 48, only the exact MAC address is excluded. If the mask is 40, all the MAC addresses that have the same first 5 bytes are excluded.
-------------------------------------	--

Required Privilege Level

view-level—To view this statement in the configuration.

control-level—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1X53-D45.

RELATED DOCUMENTATION

| [Configuring MAC Move Parameters](#)

extended-vlan-list

IN THIS SECTION

- [Syntax | 1492](#)
- [Hierarchy Level | 1492](#)
- [Description | 1493](#)
- [Options | 1493](#)
- [Required Privilege Level | 1493](#)
- [Release Information | 1493](#)

Syntax

```
extended-vlan-list vlan-id | [vlan-id set];
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols]  
[edit routing-instances routing-instance-name instance-type virtual-switch protocols evpn]
```

Description

Specify the VLAN or range of VLANs that are extended over the WAN, wherein all the single VLAN bridge domains corresponding to these VLANs are stretched.

NOTE: The `extended-vni-list` statement is an exclusive command. You cannot configure the `extended-vni-list` statement with either the `extended-vlan-list` or `extended-vni-all` statements.

Options

- | | |
|--------------------|--|
| <i>vlan-id</i> | VLAN ID to be EVPN extended. |
| <i>vlan-id set</i> | List of VLAN IDs to be EVPN extended. <ul style="list-style-type: none"> • Range: 1 through 4094 VLANs |

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

Support for logical systems on MX Series routers added in Junos OS Release 17.4R1.

RELATED DOCUMENTATION

| *evpn*

family (Protocols BGP)

IN THIS SECTION

- [Syntax | 1494](#)
- [Hierarchy Level | 1497](#)
- [Description | 1497](#)
- [Options | 1497](#)
- [Required Privilege Level | 1498](#)
- [Release Information | 1498](#)

Syntax

```
family {
  (inet | inet6 | inet-vpn | inet6-vpn | iso-vpn) {
    (any | flow | labeled-unicast | multicast | unicast | segment-routing-te) {
      accepted-prefix-limit {
        maximum number;
        teardown <percentage-threshold> idle-timeout (forever | minutes);
        drop-excess <percentage>;
        hide-excess <percentage>;
      }

      add-path {
        receive;
        send {
          include-backup-path backup_path_number;
          multipath;
          path-count number;
          path-selection-mode {
            (all-paths | equal-cost-paths);
          }
          prefix-policy [ policy-names ];
        }
      }

      aigp [disable];
      loops number;
      prefix-limit {
```

```

        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
        drop-excess <percentage>;
        hide-excess <percentage>;
    }

    protection;
    rib-group group-name;
    topology name {
        community {
            target identifier;
        }
    }
    flow {
        no-install;
        no-validate policy-name;
    }
    labeled-unicast {
        accepted-prefix-limit {
            maximum number;
            teardown <percentage> <idle-timeout (forever | minutes)>;
            drop-excess <percentage>;
            hide-excess <percentage>;
        }

        aggregate-label {
            community community-name;
        }
        explicit-null {
            connected-only;
        }
        prefix-limit {
            maximum number;
            teardown <percentage> <idle-timeout (forever | minutes)>;
            drop-excess <percentage>;
            hide-excess <percentage>;
        }
    }

    resolve-vpn;
    rib (inet.3 | inet6.3);
    rib-group group-name;
    traffic-statistics {
        file filename <world-readable | no-world-readable>;
        interval seconds;
    }
}

```

```

}
route-target {
    accepted-prefix-limit {
        maximum number;
        proxy-generate <route-target-policy route-target-policy-name>;
        teardown <percentage> <idle-timeout (forever | minutes)>;
        drop-excess <percentage>;
        hide-excess <percentage>;
    }
    advertise-default;
    external-paths number;
    prefix-limit {
        maximum number;
        teardown <percentage> <idle-timeout (forever | minutes)>;
        drop-excess <percentage>;
        hide-excess <percentage>;
    }
}
}
(evpn | inet-mdt | inet-mvpn | inet6-mvpn | l2vpn) {
    signaling {
        accepted-prefix-limit {
            maximum number;
            teardown <percentage-threshold> idle-timeout (forever | minutes);
            drop-excess <percentage>;
            hide-excess <percentage>;
        }
    }
    add-path {
        receive;
        send {
            include-backup-path backup_path_number;
            multipath;
            path-count number;
            path-selection-mode {
                (all-paths | equal-cost-paths);
            }
            prefix-policy [ policy-names ];
        }
    }
    aigp [disable];
    damping;
    loops number;
    prefix-limit {
        maximum number;
    }
}

```

```

        teardown <percentage> <idle-timeout (forever | minutes)>;
        drop-excess <percentage>;
        hide-excess <percentage>;
    }
    rib-group group-name;
}
}
traffic-engineering;
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name protocols bgp],
[edit logical-systems logical-system-name protocols bgp group group-name],
[edit logical-systems logical-system-name protocols bgp group group-name neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols bgp],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols bgp
group group-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols bgp
group group-name neighbor address],
[edit protocols bgp],
[edit protocols bgp group group-name],
[edit protocols bgp family prefix-limit (inet | inet6)(any | flow | labeled-unicast | multicast |
unicast)],
[edit protocols bgp group group-name neighbor address],
[edit routing-instances routing-instance-name protocols bgp],
[edit routing-instances routing-instance-name protocols bgp group group-name],
[edit routing-instances routing-instance-name protocols bgp group group-name neighbor address]

```

Description

Enable multiprotocol BGP (MP-BGP) by configuring BGP to carry network layer reachability information (NLRI) for address families other than unicast IPv4, to specify MP-BGP to carry NLRI for the IPv6 address family, or to carry NLRI for VPNs.

Options

any—Configure the family type to be both unicast and multicast.

evpn—Configure NLRI parameters for Ethernet VPNs (EVPNs).

`inet`—Configure NLRI parameters for IPv4.

`inet6`—Configure NLRI parameters for IPv6.

`inet-mdt`—Configure NLRI parameters for the multicast distribution tree (MDT) subaddress family identifier (SAFI) for IPv4 traffic in Layer 3 VPNs.

`inet-mvpn`—Configure NLRI parameters for IPv4 for multicast VPNs.

`inet6-mvpn`—Configure NLRI parameters for IPv6 for multicast VPNs.

`inet-vpn`—Configure NLRI parameters for IPv4 for Layer 3 VPNs.

`inet6-vpn`—Configure NLRI parameters for IPv6 for Layer 3 VPNs.

`inet6-vpn`—Configure NLRI parameters for IPv6 for Layer 3 VPNs.

`iso-vpn`—Configure NLRI parameters for IS-IS for Layer 3 VPNs.

`l2vpn`—Configure NLRI parameters for IPv4 for MPLS-based Layer 2 VPNs and VPLS.

`labeled-unicast`—Configure the family type to be labeled-unicast. This means that the BGP peers are being used only to carry the unicast routes that are being used by labeled-unicast for resolving the labeled-unicast routes. This statement is supported only with `inet` and `inet6`.

`multicast`—Configure the family type to be multicast. This means that the BGP peers are being used only to carry the unicast routes that are being used by multicast for resolving the multicast routes.

`unicast`—Configure the family type to be unicast. This means that the BGP peers only carry the unicast routes that are being used for unicast forwarding purposes. The default family type is unicast.

`segment-routing-te`—Configure the family type to be segment routing traffic engineering. This means that BGP peers only carry segment routing policies for traffic steering.

The remaining statements are explained separately. Search for a statement in [CLI Explorer](#) or click a linked statement in the Syntax section for details.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

`inet-mvpn` and `inet6-mvpn` statements introduced in Junos OS Release 8.4.

inet-mdt statement introduced in Junos OS Release 9.4.

Support for the loops statement introduced in Junos OS Release 9.6.

evpn statement introduced in Junos OS Release 13.2.

traffic-engineering statement introduced in Junos OS Release 14.2.

segment-routing-te option introduced in Junos OS Release 17.4R1 for QFX Series, MX Series, and PTX Series with FPC-PTX-P1-A.

RELATED DOCUMENTATION

Configuring IBGP Sessions Between PE Routers in VPNs

[Understanding Multiprotocol BGP](#)

[autonomous-system](#)

[local-as](#)

family multiservice

IN THIS SECTION

- [Syntax | 1499](#)
- [Hierarchy Level | 1500](#)
- [Description | 1500](#)
- [Options | 1500](#)
- [Required Privilege Level | 1501](#)
- [Release Information | 1502](#)

Syntax

```
family multiservice {
  destination-mac;
  label-1;
  label-2;
```

```

payload {
  ip {
    layer-3 {
      (source-ip-only | destination-ip-only);
    }
    layer-3-only;
    layer-4;
  }
}
source-mac;
symmetric-hash {
  complement;
}
}

```

Hierarchy Level

[edit [forwarding-options](#) [hash-key](#)]

Description

Configure load balancing based on Layer 2 media access control information. On MX Series routers, configure VPLS load balancing. On M120 and M320 routers only, configure VPLS load balancing based on MPLS labels and IP information. For IPv4 traffic, only the IP source and destination addresses are included in the hash key. For MPLS and IPv4 traffic, one or two MPLS labels and IPv4 source and destination addresses are included. For MPLS Ethernet pseudowires, only one or two MPLS labels are included in the hash key.

Options

You can configure one or more options to load-balance using the packet information that you specify.

destination-mac—Include the destination-address MAC information in the hash key for Layer 2 load balancing.

label-1 (M120 and M320 routers only)—Include the first MPLS label in the hash key. Used for including a one-label packet for per-flow load balancing of IPv4 VPLS traffic based on IP information and MPLS labels.

label-2 (M120 and M320 routers only)—Include the second MPLS label in the hash key. If both **label-1** and **label-2** are specified, the entire first label and the first 16 bits of the second label are hashed.

payload (MX Series, M120, and M320 routers only)—Include the packet's IP payload in the hash key.

- ip (MX Series, M120, and M320 routers only)—Include the IP address of the IPv4 or IPv6 payload in the hash key.
- layer-3 (MX Series routers only)—Use this to include Layer 3 information from the packet's payload in the hash key.
 - destination-ip-only (MX Series routers only)—Use this to include only the destination IP address in the payload in the hash key.
 - source-ip-only (MX Series routers only)—Use this to include only the source IP address in the payload in the hash key.

NOTE: You can include either the source-ip-only or the destination-ip-only statement, not both. They are mutually exclusive.

- layer-3-only (M120, and M320 routers only)—Include only the Layer 3 information from the packet's IP payload in the hash key.
- layer-4 (MX Series routers only)—Include Layer 4 information from the packet's IP payload in the hash key.

NOTE: On MX Series routers only, you can configure either Layer 3 or Layer 4 load balancing, or both at the same time.

NOTE: On I chip platforms, an unknown Layer 4 header is excluded from load-balance hashing to avoid undesired packet reordering.

source-mac—Include the source-address MAC information in the hash key.

symmetric-hash (MX Series routers only)—Configure the symmetric hash or symmetric hash complement for configuring symmetrical load balancing on an 802.3ad Link Aggregation Group.

- complement —Include the complement of the symmetric hash in the hash key.

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.0.

ip, label-1, label-2, layer-3-only, and payload options introduced in Junos OS Release 9.4.

layer-3, layer-. source-ip-only, and destination-ip-only options introduced in Junos OS Release 9.5.

symmetric-hash and complement options introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

[Configuring Load Balancing Based on MAC Addresses](#)

[Configuring VPLS Load Balancing Based on IP and MPLS Information | 1143](#)

[Configuring VPLS Load Balancing on MX Series 5G Universal Routing Platforms | 1145](#)

[Configuring VPLS Load Balancing | 1141](#)

fast-aps-switch

IN THIS SECTION

- [Syntax | 1502](#)
- [Hierarchy Level | 1503](#)
- [Description | 1503](#)
- [Required Privilege Level | 1503](#)
- [Release Information | 1503](#)

Syntax

```
fast-aps-switch;
```

Hierarchy Level

```
[edit interfaces interface-name sonet-options aps]
```

Description

(M320 routers with Channelized OC3/STM1 Circuit Emulation PIC with SFP only, EX Series switches, and MX series routers with Channelized OC3/STM1 Circuit Emulation PIC with SFP only using container interfaces) Reduce the Automatic Protection Switching (APS) switchover time in Layer 2 circuits.

NOTE:

- The fast APS switching feature is supported only within a single chassis on a MX series router using a container interface.
- Configuring this statement reduces the APS switchover time only when the Layer 2 circuit encapsulation type for the interface receiving traffic from a Layer 2 circuit neighbor is SAToP.
- When the `fast-aps-switch` statement is configured in revertive APS mode, you must configure an appropriate value for revert time to achieve reduction in APS switchover time.
- To prevent the logical interfaces in the data path from being shut down, configure appropriate hold-time values on all the interfaces in the data path that support TDM.
- The `fast-aps-switch` statement cannot be configured when the `APS annex-b` option is configured.
- The interfaces that have the `fast-aps-switch` statement configured cannot be used in virtual private LAN service (VPLS) environments.

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.1.

RELATED DOCUMENTATION

[Reducing APS Switchover Time in Layer 2 Circuits | 426](#)

fast-reroute-priority

IN THIS SECTION

- [Syntax | 1504](#)
- [Hierarchy Level | 1504](#)
- [Description | 1504](#)
- [Default | 1505](#)
- [Options | 1505](#)
- [Required Privilege Level | 1505](#)
- [Release Information | 1505](#)

Syntax

```
fast-reroute-priority (high | low | medium);
```

Hierarchy Level

```
[edit forwarding-options]  
[edit logical-systems logical-system-name routing-instances routing-instance-name forwarding-  
options],  
[edit routing-instances routing-instance-name forwarding-options]
```

Description

Specify the fast reroute priority for a VPLS routing instance. You can configure high, medium, or low fast reroute priority to prioritize specific VPLS routing instances for faster convergence and traffic restoration. Because the router repairs next hops for high-priority VPLS routing instances first, the

traffic traversing a VPLS routing instance configured with `high` fast reroute priority is restored faster than the traffic for VPLS routing instances configured with `medium` or `low` fast reroute priority.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Default

`low`

Options

`high`—Set the fast reroute priority for a VPLS routing instance to high. During a fast reroute event, the router repairs next hops for high-priority VPLS routing instances first.

`low`—Set the fast reroute priority for a VPLS routing instance to low, which is the default. During a fast reroute event, the router repairs next hops for low-priority VPLS routing instances last.

`medium`—Set the fast reroute priority for a VPLS routing instance to medium. During a fast reroute event, the router repairs next hops for medium-priority VPLS instances after high-priority VPLS routing instances but before low-priority VPLS routing instances.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.5.

RELATED DOCUMENTATION

| [Configuring VPLS Fast Reroute Priority](#) | 699

flow-label

IN THIS SECTION

- [Syntax | 1506](#)
- [Hierarchy Level | 1506](#)
- [Description | 1506](#)
- [Required Privilege Level | 1506](#)
- [Release Information | 1507](#)

Syntax

```
flow-label;
```

Hierarchy Level

```
[edit routing-instances name protocols evpn]
```

Description

Advertise that the device is able to support flow-aware transport (FAT) labels for EVPN-MPLS E- LAN services. With FAT flow labels, you can load balance MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. RFC 6391 describes FAT flow labels and how they are used.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Evolved Release 22.2R1.

flow-label-receive

IN THIS SECTION

- [Syntax | 1507](#)
- [Hierarchy Level | 1507](#)
- [Description | 1507](#)
- [Required Privilege Level | 1508](#)
- [Release Information | 1508](#)

Syntax

```
flow-label-receive;
```

Hierarchy Level

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name],  
[edit routing-instances routing-instance-name protocols l2vpn site name],  
[edit routing-instances routing-instance-name protocols l2vpn site name interface interface-name],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Configure the router to signal the capability to pop the flow label in the receive direction to the remote provider edge (PE) router.

The flow-aware transport of pseudowires (FAT) flow labels enable load-balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep

packet inspection of the payload. FAT flow labels can be used for LDP-signaled forwarding equivalence class (FEC 128 and FEC 129) pseudowires for virtual private LAN service (VPLS) and virtual private wire service (VPWS) networks.

NOTE:

- Starting with Junos OS Release 16.1, `flow-label-receive` statement is supported for BGP L2VPN and BGP VPLS.
- The `flow-label-receive` statement is not supported in OAM CFM session over Layer 2 circuit.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

[Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)

[Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

[Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)

flow-label-receive-static

IN THIS SECTION

- [Syntax | 1509](#)
- [Hierarchy Level | 1509](#)
- [Description | 1509](#)
- [Required Privilege Level | 1510](#)
- [Release Information | 1510](#)

Syntax

```
flow-label-receive-static;
```

Hierarchy Level

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name]  
[edit routing-instances instance-name protocols evpn],  
[edit routing-instances instance-name protocols evpn interface interface-name]
```

Description

Configure the router to pop the flow label on pseudowire packets received from a remote provider edge (PE) router. The ingress PE router inserts the flow label in the pseudowire packet regardless of the information exchanged in the signaling plane. If the egress PE router cannot handle the pseudowire packet with the flow label, it drops the packet.

Flow-aware transport of pseudowires (FAT) flow labels enable load balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. You can use this statement to enable devices to pop FAT flow labels for:

- Forwarding equivalence class (FEC) 128 pseudowires in:
 - Virtual private LAN service (VPLS) networks.
 - Virtual private wire service (VPWS) networks.

In these cases, configure this statement in the [edit protocols l2circuit neighbor *neighbor-id* interface *interface-name*] hierarchy.

- Pseudowires in Ethernet VPN (EVPN)-MPLS networks with VPWS (EVPN-VPWS):

- Globally in an EVPN-VPWS routing instance.

In this case, configure this statement in the [edit routing-instances *instance-name* protocols evpn] hierarchy.

- For specific interfaces in an EVPN-VPWS routing instance.

In this case, configure this statement in the [edit routing-instances *instance-name* protocols evpn interface *interface-name*] hierarchy.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

Support in a EVPN-VPWS routing instance added in Junos OS Release 21.1R1.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

FAT Flow Labels in EVPN-VPWS Routing Instances

flow-label-static

IN THIS SECTION

- [Syntax | 1511](#)
- [Hierarchy Level | 1511](#)

- [Description | 1511](#)
- [Required Privilege Level | 1512](#)
- [Release Information | 1512](#)

Syntax

```
flow-label-static;
```

Hierarchy Level

```
[edit routing-instances name protocols evpn]
```

Description

For EVPN-MPLS E-LAN services, configure the router to signal the ability to push the flow-aware transport (FAT) flow label on pseudowire packets received from a provider edge (PE) router or to pop the FAT flow label on pseudowire packets transmitted to a PE router. The ingress PE router inserts the flow label in the pseudowire packet regardless of the information exchanged in the signaling plane. If the egress PE router cannot handle the pseudowire packet with the flow label, it drops the packet. A change in FAT flow label configuration is a catastrophic event, causing traffic loss. RFC 6391 describes FAT flow labels and how they are used.

With FAT flow labels, you can load balance known unicast MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. You can use this statement to enable devices to pop or push FAT flow labels for these EVPN service types:

- `vlan-based`
- `vlan-bundle`
- `vlan-aware`

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Evolved Release 22.2R1.

flow-label-transmit

IN THIS SECTION

- [Syntax | 1512](#)
- [Hierarchy Level | 1512](#)
- [Description | 1513](#)
- [Required Privilege Level | 1513](#)
- [Release Information | 1513](#)

Syntax

```
flow-label-transmit;
```

Hierarchy Level

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name],  
[edit routing-instances routing-instance-name protocols l2vpn site name],  
[edit routing-instances routing-instance-name protocols l2vpn site name interface interface-name],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Configure the router to signal the capability to push the flow label in the transmit direction to the provider edge (PE) router.

The flow-aware transport of pseudowires (FAT) flow labels enable load-balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. FAT flow labels can be used for LDP-signaled forwarding equivalence class (FEC 128 and FEC 129) pseudowires for virtual private LAN service (VPLS) and virtual private wire service (VPWS) networks.

NOTE:

- Starting with Junos OS Release 16.1, flow-label-transmit statement is supported for BGP L2VPN and BGP VPLS.
- The flow-label-transmit statement is not supported in OAM CFM session over L2Circuit.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

[Configuring the FAT Flow Label for FEC 128 VPLS Pseudowires for Load-Balancing MPLS Traffic | 770](#)

[Configuring the FAT Flow Label for FEC 129 VPWS Pseudowires for Load-Balancing MPLS Traffic | 608](#)

[Configuring the FAT Flow Label for FEC 129 VPLS Pseudowires for Load-Balancing MPLS Traffic | 772](#)

flow-label-transmit-static

IN THIS SECTION

- [Syntax | 1514](#)
- [Hierarchy Level | 1514](#)
- [Description | 1514](#)
- [Required Privilege Level | 1515](#)
- [Release Information | 1515](#)

Syntax

```
flow-label-transmit-static;
```

Hierarchy Level

```
[edit protocols l2circuit neighbor neighbor-id interface interface-name],  
[edit routing-instances instance-name protocols evpn],  
[edit routing-instances instance-name protocols evpn interface interface-name]
```

Description

Configure the router to push the flow label on pseudowire packets it sends to a remote provider edge (PE) router. The ingress PE router inserts the flow label in the pseudowire packet regardless of the information exchanged in the signaling plane. If the egress PE router can't handle a pseudowire packet that contains the flow label, it drops the packet.

Flow-aware transport of pseudowires (FAT) flow labels enable load balancing of MPLS packets across equal-cost multipath (ECMP) paths or link aggregation groups (LAGs) without the need for deep packet inspection of the payload. You can use this statement to enable devices to push FAT flow labels for:

- Forwarding equivalence class (FEC) 128 pseudowires in:
 - Virtual private LAN service (VPLS) networks.
 - Virtual private wire service (VPWS) networks.

In these cases, configure this statement in the [edit protocols l2circuit neighbor *neighbor-id* interface *interface-name*] hierarchy.

- Pseudowires in Ethernet VPN (EVPN)-MPLS networks with VPWS (EVPN-VPWS):

- Globally in an EVPN-VPWS routing instance.

In this case, configure this statement in the [edit routing-instances *instance-name* protocols evpn] hierarchy.

- For specific interfaces in an EVPN-VPWS routing instance.

In this case, configure this statement in the [edit routing-instances *instance-name* protocols evpn interface *interface-name*] hierarchy.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

Support in a EVPN-VPWS routing instance added in Junos OS Release 21.1R1.

RELATED DOCUMENTATION

[Configuring the FAT Flow Label for FEC 128 VPWS Pseudowires for Load-Balancing MPLS Traffic | 605](#)

FAT Flow Labels in EVPN-VPWS Routing Instances

global-mac-move

IN THIS SECTION

- [Syntax | 1516](#)
- [Hierarchy Level | 1516](#)

- [Description | 1516](#)
- [Default | 1516](#)
- [Required Privilege Level | 1517](#)
- [Release Information | 1517](#)

Syntax

```
global-mac-move {  
    cooloff-time seconds;  
    disable-action;  
    exclusive-mac virtual-mac-mac-address/mask;  
    interface-recovery-time seconds;  
    notification-time seconds;  
    reopen-time seconds;  
    statistical-approach-wait-time seconds;  
    threshold-count count;  
    threshold-time seconds;  
    virtual-mac mac-address /mask;  
}
```

Hierarchy Level

```
[edit protocols l2-learning]
```

Description

Set parameters for media access control (MAC) address move reporting.

Default

By default, MAC moves notify every second, with a threshold time of 1 second and a threshold count of 50.

Required Privilege Level

view-level—To view this statement in the configuration.

control-level—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.4.

Support for logical systems added in Junos OS Release 9.6.

Support for disable-action and reopen-time added in Junos OS Release 13.2.

Support for exclusive-mac added in Junos OS Release 14.1X53-D45.

Statements cooloff-time, interface-recovery-time, statistical-approach-wait-time, and virtual-mac moved from vpls-mac-move to global-mac-move hierarchy level in Junos OS Release 17.4.

RELATED DOCUMENTATION

[Configuring MAC Move Parameters](#)

[MAC Moves Loop Prevention in VPLS Network Overview | 1147](#)

[Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves | 1151](#)

[virtual-mac | 1703](#)

hot-standby

IN THIS SECTION

- [Syntax | 1518](#)
- [Hierarchy Level | 1518](#)
- [Description | 1518](#)
- [Required Privilege Level | 1518](#)
- [Release Information | 1518](#)

Syntax

```
hot-standby;
```

Hierarchy Level

```
[edit routing-instances routing-instance-name protocols l2vpn site site-name]
```

Description

Turn on the protector behavior for the site. This keeps backup pseudowire in continuous standby mode and ready for traffic forwarding.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.2.

RELATED DOCUMENTATION

| *Example: Configuring MPLS Egress Protection Service Mirroring for BGP Signaled Layer 2 Services*

hot-standby (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1519](#)
- [Hierarchy Level | 1519](#)

- [Description | 1519](#)
- [Required Privilege Level | 1519](#)
- [Release Information | 1520](#)

Syntax

```
hot-standby;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name end-interface interface interface-name backup-neighbor address],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name backup-neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address backup-neighbor address],
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor address],
[edit routing-instances routing-instance-name protocols vpls neighbor address backup-neighbor
address]
```

Description

Configure the pseudowire to the specified backup neighbor as the hot-standby. When you configure this statement, traffic flows over both the active and hot-standby pseudowires to the backup device (either a CE device or PE router). The backup device drops the traffic from the hot-standby pseudowire, unless the active pseudowire fails. If the active pseudowire fails, the backup device automatically switches to the hot-standby pseudowire.

Configure the hot-standby statement on routers that have both active and standby virtual circuits. Generally, these are access routers. On provider edge routers, configure the hot-standby-vc-on' statement to indicate that a hot-standby pseudowire is desired upon arrival of a PW_FWD_STDBY status-TLV.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Hierarchy levels associated with the backup-neighbor statement added in Junos OS Release 9.2.

RELATED DOCUMENTATION

[Configuring Layer 2 Circuits over Both RSVP and LDP LSPs | 367](#)

[Configuring Pseudowire Redundancy on the PE Router | 226](#)

[Example: Configuring Layer 2 Circuit Switching Protection | 461](#)

hot-standby-vc-on (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1520](#)
- [Hierarchy Level | 1520](#)
- [Description | 1521](#)
- [Required Privilege Level | 1521](#)
- [Release Information | 1521](#)

Syntax

```
hot-standby-vc-on;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name pseudowire-status-tlv],
```

```
[edit logical systems logical-system-name routing-instances routing-instance-name protocols vpls
mesh-group mesh-group-name neighbor address pseudowire-status-tlv],
[edit protocols l2circuit neighbor address interface interface-name pseudowire-status-tlv],
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor
address pseudowire-status-tlv]
```

Description

On provider edge (PE) aggregation routers, configure the `hot-standby-vc-on` statement to indicate that a hot-standby pseudowire is desired upon arrival of a PW_FWD_STDBY status-tlv. This flag indicates the standby state. Configure in conjunction with the `hot-standby` statement on routers that have both active and standby virtual circuits. Generally, these are access routers.

The goal of the `hot-standby` statement is to reduce the amount of traffic being discarded during primary-to-backup transition periods. This statement enables the possibility of keeping both the active and standby paths open within the Layer 2 domain. By having both the active and standby VCs able to send and receive traffic, traffic loops could potentially occur within the Layer 2 domain. In consequence, Layer 2 VCs are kept open only in the PE-to-access direction. In other words, aggregation PE devices can send traffic toward access devices, but access devices send traffic exclusively through the active VC.

In this regard, the `hot-standby` statement is quite similar to the `standby` statement. The `hot-standby` statement allows for a faster forwarding-path switchover during transition periods, as compared to what is allowed by the `standby` statement.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.2.

Support for VPLS routing instances added in Junos OS Release 15.1R2.

RELATED DOCUMENTATION

[Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario](#) | 391

identifier (VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax | 1522](#)
- [Hierarchy Level | 1522](#)
- [Description | 1522](#)
- [Options | 1523](#)
- [Required Privilege Level | 1523](#)
- [Release Information | 1523](#)

Syntax

```
identifier identifier;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing site site-name],  
[edit routing-instances instance-name protocols vpls multi-homing site site-name]
```

Description

Configure a Layer 2 VPN or VPLS multihoming identifier (MHID). An identifier needs to be configured for each multihomed site. Multihoming site identifiers are specific to a VPLS domain. They need not be unique on a provider edge (PE) router when multiple VPLS instances are present. The network layer reachability information (NLRI) advertisements sent to a CE device are identified as candidates for designated forwarder selection because the advertisements have the same multihoming identifier. Thus, you should assign the same identifier on all VPLS PE routers that are multihomed to the same customer site.

NOTE: The route distinguisher must be unique among PE routers participating in a multihomed site, so that the RD:MHID combination is unique across multiple VPLS domains. For example, one PE router might have a route distinguisher of 192.0.2.4:1, and another PE router in the same site might have a route distinguisher of 192.0.2.:1. The first number can be, for example, the loopback interface address that identifies the PE router. The second number is the multihoming identifier.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

identifier Number that identifies the multihomed site.

- **Range:** 1 through 65535

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

| [Example: Configuring VPLS Multihoming \(FEC 129\)](#) | 971

ignore-encapsulation-mismatch

IN THIS SECTION

- [Syntax | 1524](#)
- [Hierarchy Level | 1524](#)
- [Description | 1525](#)
- [Required Privilege Level | 1525](#)
- [Release Information | 1525](#)

Syntax

```
ignore-encapsulation-mismatch;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface interface-name],  
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface interface-name],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor neighbor-id],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls neighbor neighbor-id],  
[edit protocols l2circuit local-switching interface interface-name],  
[edit protocols l2circuit neighbor address interface interface-name],  
[edit routing-instances routing-instance-name protocols evpn interface interface-name],  
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor neighbor-id],  
[edit routing-instances routing-instance-name protocols vpls neighbor neighbor-id]
```

Description

Allow a Layer 2 circuit, VPLS, or EVPN to be established even though the encapsulation configured on the CE device interface does not match the encapsulation configured on the Layer 2 circuit, VPLS, or EVPN interface.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration

Release Information

Statement introduced in Junos OS Release 9.2.

Statement extended to support local switching in Junos OS Release 10.4.

Statement introduced for EVPNs in Junos OS Release 13.2 for MX 3D Series.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

[Enabling the Layer 2 Circuit When the Encapsulation Does Not Match | 364](#)

ignore-mtu-mismatch

IN THIS SECTION

- [Syntax | 1526](#)
- [Hierarchy Level | 1526](#)
- [Description | 1526](#)
- [Required Privilege Level | 1526](#)
- [Release Information | 1526](#)

Syntax

```
ignore-mtu-mismatch;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn interface interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit protocols l2circuit local-switching interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name],
[edit routing-instances routing-instance-name protocols l2vpn interface interface-name],
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Ignore the MTU configuration set for the physical interface associated with the local switching interface or with the remote PE router. This allows a pseudowire to be brought up between two logical interfaces that are defined on physical interfaces with different MTU values.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration

Release Information

Statement introduced in Junos OS Release 8.5.

Support for remote PE routers added in Junos OS Release 9.2.

Support for Layer 2 VPNs and VPLS added in Junos OS Release 10.4.

RELATED DOCUMENTATION

[Enabling Local Interface Switching When the MTU Does Not Match | 359](#)

[Configuring the MTU for Layer 2 Interfaces | 212](#)

import-labeled-routes (Routing Instances VPLS)

IN THIS SECTION

- [Syntax | 1527](#)
- [Hierarchy Level | 1527](#)
- [Description | 1527](#)
- [Options | 1528](#)
- [Required Privilege Level | 1528](#)
- [Release Information | 1528](#)

Syntax

```
import-labeled-routes [ routing-instance-name ]
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit routing-instances routing-instance-name protocols vpls ]
```

Description

(MX Series routers with MPCs and MIC interfaces only) Specify one or more routing instances where MPLS paths (pseudowire labeled routes) are leaked from the mpls.0 routing table in the primary routing instance to the local *routing-instance-name*.mpls.0 routing table.

This capability is useful in an L2VPN/VPLS configuration when the remote PE router is learned from the IGP in a nondefault routing instance, because L2VPN/VPLS installs ingress-labeled routes only in the primary mpls.0 table.

When L2VPN/VPLS traffic is received on the core-facing interface in a nondefault routing instance, the router performs a lookup in the table that corresponds to that interface, *routing-instance-name.mpls.0*. Because the routes are not leaked by default, no routes are found in the *routing-instance-name.mpls.0* routing table and all the incoming traffic is dropped.

Options

routing-instance-name Name of a nondefault routing instance where you want routes leaked from the primary MPLS routing table.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 16.1.

RELATED DOCUMENTATION

| [Configuring VPLS Routing Instances](#) | 674

interface (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax](#) | 1529
- [Hierarchy Level](#) | 1529
- [Description](#) | 1530
- [Options](#) | 1530

- Required Privilege Level | 1530
- Release Information | 1531

Syntax

```
interface interface-name {
    backup-neighbor address;
    bandwidth (bandwidth | ctnumber bandwidth);
    community community-name;
    connection-protection;
    (control-word | no-control-word);
    description text;
    egress-protection;
    encapsulation-type type;
    flow-label-receive;
    flow-label-receive-static;
    flow-label-transmit;
    flow-label-transmit-static;
    ignore-encapsulation-mismatch;
    ignore-mtu-mismatch;
    mtu mtu-number;
    no-revert;
    oam;
    protect-interface interface-name;
    pseudowire-status-tlv hot-standby-vc-on;
    psn-tunnel-endpoint address;
    revert-time seconds;
    send-ip-addr-list-tlv;
    static {
        switchover-delay milliseconds;
        virtual-circuit-id identifier;
    }
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching],
[edit logical-systems logical-system-name protocols l2circuit neighbor address],
```

```
[edit protocols l2circuit local-switching],
[edit protocols l2circuit neighbor address]
```

Description

Interface over which Layer 2 circuit traffic travels.

Options

interface-name Name of the interface to configure.

NOTE: The commit operation fails, if the same logical interface is configured for both layer 2 circuit and ccc connection.

connection-protection Enable end-to-end protection through OAM failure detection.

flow-label-receive Advertise capability to pop flow label in receive direction to the remote provider edge (PE) device.

flow-label-receive-static Pop flow label on the pseudowire packets received from the remote PE device. The ingress PE inserts the flow label in the pseudowire packet, irrespective of the information exchanged in the signaling plane. If the egress PE cannot handle the pseudowire packet marked with the flow label, the packet is dropped.

flow-label-transmit Advertise capability to push flow label in transmit direction to the remote PE device.

flow-label-transmit-static Push flow label on the pseudowire packets sent to the remote PE device. If the incoming pseudowire packet is not marked with the flow label, the packet is dropped by the egress PE.

send-ip-addr-list-tlv On a PS service logical interface, signal that the IP address TLV is sent, allowing the access PE router to send the local CE router's address to the service PE router.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

flow-label-receive-static and flow-label-transmit-static options introduced in Junos OS Release 14.1.

RELATED DOCUMENTATION

| [Configuring the Neighbor Interface for the Layer 2 Circuit](#) | [361](#)

interface (Protocols Layer 2 VPN)

IN THIS SECTION

- [Syntax](#) | [1531](#)
- [Hierarchy Level](#) | [1532](#)
- [Description](#) | [1532](#)
- [Options](#) | [1532](#)
- [Required Privilege Level](#) | [1532](#)
- [Release Information](#) | [1532](#)

Syntax

```
interface interface-name {  
    description text;  
    remote-site-id    remote-site-id;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn],  
[edit routing-instances routing-instance-name protocols l2vpn]
```

Description

Configure an interface to handle traffic for a circuit configured for the Layer 2 VPN.

Options

interface-name—Name of the interface used for the Layer 2 VPN.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring the Site | 150](#)

[Configuring the Remote Site ID | 151](#)

interface (VPLS Mesh-Group)

IN THIS SECTION

- [Syntax | 1533](#)
- [Hierarchy Level | 1533](#)
- [Description | 1533](#)
- [Required Privilege Level | 1533](#)
- [Release Information | 1533](#)

Syntax

```
interface interface-name;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
mesh-group mesh-group-name],  
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
```

Description

Specify one or more interfaces belonging to the virtual private LAN service (VPLS) flood mesh-group.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 15.2.

RELATED DOCUMENTATION

[Configuring VPLS Routing Instances | 674](#)

[mesh-group \(Protocols VPLS\) | 1570](#)

interface (VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax | 1534](#)
- [Hierarchy Level | 1534](#)
- [Description | 1534](#)
- [Options | 1535](#)
- [Required Privilege Level | 1535](#)
- [Release Information | 1535](#)

Syntax

```
interface interface-name {  
    preference preference-value;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-  
homing site site-name],  
[edit routing-instances instance-name protocols vpls multi-homing site site-name]
```

Description

Configure the interface that connects this site to the VPN.

The remaining statement is explained separately. See [CLI Explorer](#).

Options

interface-name—Name of the interface (for example, ge-0/1/0.1).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[Example: Configuring VPLS Multihoming \(FEC 129\)](#) | [971](#)

interface (VPLS Routing Instances)

IN THIS SECTION

- [Syntax](#) | [1535](#)
- [Hierarchy Level](#) | [1536](#)
- [Description](#) | [1536](#)
- [Options](#) | [1536](#)
- [Required Privilege Level](#) | [1536](#)
- [Release Information](#) | [1536](#)

Syntax

```
interface interface-name {  
    mac-pinning;
```

```
interface-mac-limit limit;
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
site site-name],
[edit routing-instances routing-instance-name protocols vpls],
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Configure the interface for a pseudowire to the VPLS customer site. To complete the configuration of interfaces for a VPLS routing instance, you must also configure the interfaces specified for a VPLS site at the `[edit routing-instances routing-instance-name]` hierarchy level as described in *Configuring Routing Instances on PE Routers in VPNs*.

Options

interface-name—Specify the name of the interface used by the VPLS site.

The remaining statement is explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring the VPLS Site Interfaces](#) | 681

Configuring Routing Instances on PE Routers in VPNs

interface-mac-limit (VPLS)

IN THIS SECTION

- [Syntax](#) | 1537
- [Hierarchy Level](#) | 1537
- [Description](#) | 1538
- [Options](#) | 1538
- [Required Privilege Level](#) | 1538
- [Release Information](#) | 1538

Syntax

```
interface-mac-limit limit {  
    packet-action drop;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
site site-name interfaces interface-name],  
[edit routing-instances routing-instance-name protocols evpn],  
[edit routing-instances routing-instance-name protocols evpn interface interface-name],  
[edit routing-instances routing-instance-name protocols vpls site site-name interfaces interface-  
name]
```

Description

Specify the maximum number of media access control (MAC) addresses that can be learned by the EVPN or VPLS routing instance. You can configure the same limit for all interfaces configured for a routing instance. You can also configure a limit for a specific interface.

Starting with Junos OS Release 12.3R4, if you do not configure the parameter to limit the number of MAC addresses to be learned by a VPLS instance, the default value is not effective. Instead, if you do not include the `interface-mac-limit` option at the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls site *site-name* interfaces *interface-name*], hierarchy level, this setting is not present in the configuration with the default value of 1024 addresses. If you upgrade a router running a Junos OS release earlier than Release 12.3R4 to Release 12.3R4 or later, you must configure the `interface-mac-limit` option with a valid value for it to be saved in the configuration.

Options

limit—Number of MAC addresses that can be learned from each interface.

- **Range:** 1 through 131,071 MAC addresses

NOTE: For M120 devices only, the range is 16 through 65,536 MAC addresses.

- **Default:** 1024 addresses

The remaining statement is explained separately. Search for a statement in [CLI Explorer](#) or click a linked statement in the Syntax section for details.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support for EVPNs introduced in Junos OS Release 13.2 on MX 3D Series routers.

Support for EVPNs introduced in Junos OS Release 14.2 on EX Series switches.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

[Limiting the Number of MAC Addresses Learned from an Interface | 689](#)

interface

[mac-table-size | 1567](#)

install-nexthop

IN THIS SECTION

- [Syntax | 1539](#)
- [Hierarchy Level | 1539](#)
- [Description | 1540](#)
- [Options | 1540](#)
- [Required Privilege Level | 1540](#)
- [Release Information | 1540](#)

Syntax

```
install-nexthop (except | lsp lsp-name | lsp-regex lsp-regular-expression);
```

Hierarchy Level

```
[edit logical-systems logical-system-name policy-options policy-statement policy-name term term-name then],  
[edit policy-options policy-statement policy-name term term-name then]
```

Description

Select a specific label-switched path (LSP), or select an LSP from a set of similarly named LSPs as the traffic destination for the configured community. Also can prevent the installation of any matching next hops.

Options

`except`—Prevent the installation of any matching next hops.

`lsp lsp-name`—Configure a specific LSP.

`lsp-regex lsp-regular-expression`—Configure a range of similarly named LSPs. You can use the following wildcard characters when configuring an LSP regular expression:

- Asterisk (*)—Match any characters.
- Period (.)—Match any single digit.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring the Policy Statement for the Layer 2 Circuit Community](#) | 374

I2circuit

IN THIS SECTION

● [Syntax](#) | 1541

- Hierarchy Level | 1542
- Description | 1542
- Required Privilege Level | 1542
- Release Information | 1542

Syntax

```
l2circuit {
    auto-sensing{
        password password;
    }
    local-switching {
        interface interface-name {
            description text;
            end-interface {
                interface interface-name;
                protect-interface interface-name;
            }
            ignore-mtu-mismatch;
            protect-interface interface-name;
        }
    }
    neighbor address {
        interface interface-name {
            backup-neighbor address;
            bandwidth (bandwidth | ctnumber bandwidth);
            community community-name;
            connection-protection;
            (control-word | no-control-word);
            description text;
            egress-protection;
            encapsulation-type type;
            ignore-encapsulation-mismatch;
            ignore-mtu-mismatch;
            mtu mtu-number;
            protect-interface interface-name;
            pseudowire-status-tlv hot-standby-vc-on;
            psn-tunnel-endpoint address;
        }
    }
}
```



```

        virtual-circuit-id identifier;
    }
}
resolution {
    preserve-nexthop-heirarchy;
}
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name protocols],
[edit protocols]

```

Description

Enables a Layer 2 circuit.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring ATM Trunking on Layer 2 Circuits | 378](#)

[Configuring Bandwidth Allocation and Call Admission Control in Layer 2 Circuits | 383](#)

[Configuring Interfaces for Layer 2 Circuits | 360](#)

[Configuring LDP for Layer 2 Circuits | 377](#)

[Configuring Policies for Layer 2 Circuits | 373](#)[Configuring Static Layer 2 Circuits | 356](#)[Tracing Layer 2 Circuit Operations | 496](#)

I2ckt

IN THIS SECTION

- [Syntax | 1543](#)
- [Hierarchy Level | 1543](#)
- [Description | 1543](#)
- [Required Privilege Level | 1544](#)
- [Release Information | 1544](#)

Syntax

```
l2ckt {  
    l2vpn;  
    l3vpn;  
    labeled-bgp;  
    no-l2vpn;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options forwarding-table chained-composite-  
next-hop ingress],  
[edit routing-options forwarding-table chained-composite-next-hop ingress]
```

Description

Enable composite chained next hop for ingress Layer 2 circuit label-switched paths (LSPs).

The remaining statements are explained separately.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.3.

I2-learning

IN THIS SECTION

- [Syntax \(MX Series, QFX Series, EX Series\) | 1544](#)
- [Syntax \(SRX Series\) | 1545](#)
- [Hierarchy Level | 1545](#)
- [Description | 1545](#)
- [Options | 1545](#)
- [Required Privilege Level | 1545](#)
- [Release Information | 1546](#)

Syntax (MX Series, QFX Series, EX Series)

```
l2-learning {  
    global-le-bridge-domain-aging-time;  
    global-mac-ip-limit number;  
    global-mac-ip-table-aging-time seconds;  
    global-mac-limit limit;  
    global-mac-statistics;  
    global-mac-table-aging-time seconds;  
    global-no-mac-learning;
```

```
global-mac-move;
}
```

Syntax (SRX Series)

```
l2-learning {
    global-mac-limit limit {
        packet-action-drop
    }
    global-mac-table-aging-time seconds;
    global-mode (switching | transparent-bridge) ;
    global-no-mac-learning;
}
```

Hierarchy Level

```
[edit protocols]
```

Description

Configure Layer 2 address learning and forwarding properties globally.

The remaining statements are explained separately. See [CLI Explorer](#).

Options

global-le-bridge-domain-aging-time Specify the aging time of LE bridge-domain. The MAC address is learnt after next hop(NH) and bridge-domain(BD), also called NHBD. This aging time delays the deletion of NHBD. Configuring lesser time, in seconds, results in faster deletion of NHBD.

- **Range:** 120 to 1000000 seconds

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

Statement modified in Junos OS Release 9.5. Support for global mode added in Junos OS Release 15.1X49-D40.

global-le-bridge-domain-aging-time option introduced in Junos OS Release 14.2R5 for the MX Series.

global-mac-ip-limit and global-mac-ip-table-aging-time options introduced in Junos OS Release 17.4R1 for MX Series routers and EX9200 switches.

RELATED DOCUMENTATION

[Understanding Layer 2 Learning and Forwarding](#)

[global-mac-table-aging-time](#)

[global-mac-limit \(Protocols\)](#)

[global-no-mac-learning](#)

[global-mode \(Protocols\)](#)

I2vpn

IN THIS SECTION

- [Syntax | 1546](#)
- [Hierarchy Level | 1549](#)
- [Description | 1549](#)
- [Required Privilege Level | 1549](#)
- [Release Information | 1549](#)

Syntax

```
l2vpn {
  (control-word | no-control-word);
```

```

encapsulation-type type;
oam {
    bfd-liveness-detection {
        detection-time {
            threshold milliseconds;
        }
        minimum-interval milliseconds;
        minimum-receive-interval milliseconds;
        multiplier number;
        no-adaptation;
        transmit-interval {
            threshold milliseconds;
            minimum-interval milliseconds;
        }
        version (1 | automatic);
    }
    ping-interval seconds;
}
site site-name {
    community COMM;
    control-word ;
    encapsulation-type ethernet;
    ignore-encapsulation-mismatch;
    ignore-mtu-mismatch;
    interface interface-name {
        description text;
        community COMM;
        control-word ;
        encapsulation-type ethernet;
        ignore-encapsulation-mismatch;
        ignore-mtu-mismatch;
        mtu 1500;
        no-control-word;
        oam {
            bfd-liveness-detection {
                detection-time {
                    threshold milliseconds;
                }
                minimum-interval milliseconds;
                minimum-receive-interval milliseconds;
                multiplier number;
                no-adaptation;
                transmit-interval {

```

```

        threshold milliseconds;
        minimum-interval milliseconds;
    }
    version (1 | automatic);
}
ping-interval seconds; seconds;
}
remote-site-id remote-site-id;
target-attachment-identifier identifier;
}
mtu 1500;
no-control-word;
oam {
    bfd-liveness-detection {
        detection-time {
            threshold milliseconds;
        }
        minimum-interval milliseconds;
        minimum-receive-interval milliseconds;
        multiplier number;
        no-adaptation;
        transmit-interval {
            threshold milliseconds;
            minimum-interval milliseconds;
        }
        version (1 | automatic);
    }
    ping-interval seconds; seconds;
}
site-identifier identifier;
site-preference preference-value {
    backup;
    primary;
}
source-attachment-identifier identifier;
}
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
}

```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols],
[edit routing-instances routing-instance-name protocols]
```

Description

Enable a Layer 2 VPN routing instance on a PE router or switch.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring a Layer 2 VPN Routing Instance | 149](#)

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

I2vpn (routing-options)

IN THIS SECTION

- [Syntax | 1550](#)
- [Hierarchy Level | 1550](#)
- [Description | 1550](#)
- [Required Privilege Level | 1550](#)

Syntax

```
l2vpn {  
    l2ckt;  
    l3vpn;  
    labeled-bgp;  
    no-l2ckt;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options forwarding-table chained-composite-  
next-hop ingress],  
[edit routing-options forwarding-table chained-composite-next-hop ingress]
```

Description

Enable composite chained next hop for ingress Layer 2 virtual private network (VPN) label-switched paths (LSPs).

The remaining statements are explained separately.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.3.

l2vpn-id

IN THIS SECTION

- [Syntax | 1551](#)
- [Hierarchy Level | 1551](#)
- [Description | 1551](#)
- [Options | 1551](#)
- [Required Privilege Level | 1552](#)
- [Release Information | 1552](#)

Syntax

```
l2vpn-id (as-number:id | ip-address:id);
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name],  
[edit routing-instances instance-name]
```

Description

Specify a globally unique Layer 2 VPN community identifier for the instance.

Options

as-number:id—Autonomous system number (*l2vpn-id:as-number:2-byte-number*. For example: *l2vpn-id l2vpn-id:100:200*. The AS number can be in the range from 1 through 65,535.

ip-address:id—IP address (*l2vpn-id:ip-address:2-byte-number*. For example: *l2vpn-id l2vpn-id:10.1.1.1:2*. The IP address can be any globally unique unicast address.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.4R2.

RELATED DOCUMENTATION

[Example: Configuring BGP Autodiscovery for LDP VPLS | 909](#)

[Example: Configuring BGP Autodiscovery for LDP VPLS with User-Defined Mesh Groups | 934](#)

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 885](#)

label-allocation

IN THIS SECTION

- [Syntax | 1552](#)
- [Hierarchy Level | 1553](#)
- [Description | 1553](#)
- [Options | 1553](#)
- [Required Privilege Level | 1553](#)
- [Release Information | 1553](#)

Syntax

```
label-allocation per-instance | per-bridge-domain;
```

Hierarchy Level

```
[edit routing-instances routing-instance-name protocols evpn]
```

Description

Specifies the MPLS label allocation setting for the EVPN routing instance.

Options

`per-instance`—Allocates a single MPLS label for the EVPN routing instance.

`per-bridge-domain`—Allocates a single MPLS label for each bridge domain. By default, `per-bridge-domain` is enabled on the PTX10008 Packet Transport Routers.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.2.

RELATED DOCUMENTATION

| *Configuring EVPN Routing Instances*

label-block-size

IN THIS SECTION

- [Syntax | 1554](#)
- [Hierarchy Level | 1554](#)

- [Description | 1554](#)
- [Default | 1554](#)
- [Options | 1554](#)
- [Required Privilege Level | 1555](#)
- [Release Information | 1555](#)

Syntax

```
label-block-size size;
```

Hierarchy Level

```
[edit logical-systems profile-name routing-instances instance-name protocols vpls],  
[edit routing-instances instance-name protocols vpls]
```

Description

Configure the label block size for VPLS labels.

Default

8

Options

- 2—Allocate the label blocks in increments of 2. For a VPLS domain that has only two sites with no future expansion plans.
- 4—Allocate the label blocks in increments of 4.
- 8 (default)—Allocate the label blocks in increments of 8.
- 16—Allocate the label blocks in increments of 16. A label block size of 16 enables you to minimize the number of routes in the VPLS domain. Use this setting only if the number of routes is the most important concern.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

RELATED DOCUMENTATION

| [Configuring the Label Block Size for VPLS](#) | 723

label-switched-path-template (Multicast)

IN THIS SECTION

- [Syntax](#) | 1555
- [Hierarchy Level](#) | 1556
- [Description](#) | 1556
- [Options](#) | 1556
- [Required Privilege Level](#) | 1557
- [Release Information](#) | 1557

Syntax

```
label-switched-path-template {  
    (default-template | lsp-template-name);  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name provider-
tunnel rsvp-te],
[edit logical-systems logical-system-name routing-instances routing-instance-name provider-
tunnel ingress-replication label-switched-path],
[edit logical-systems logical-system-name routing-instances routing-instance-name provider-
tunnel selective group address source source-address rsvp-te],
[edit logical-systems logical-system-name routing-options dynamic-tunnels tunnel-name rsvp-te
entry-name],
[edit protocols mvpn inter-region-segmented template template-name region region-name ingress-
replication label-switched-path],
[edit protocols mvpn inter-region-segmented template template-name region region-name rsvpe-te],
[edit protocols mvpn inter-region-template template template-name all-regions ingress-
replication label-switched-path],
[edit protocols mvpn inter-region-template template template-name all-regions rsvp-te],
[edit routing-instances routing-instance-name provider-tunnel ingress-replication label-switched-
path],
[edit routing-instances routing-instance-name provider-tunnel rsvp-te],
[edit routing-instances routing-instance-name provider-tunnel selective group address source
source-address rsvp-te],
[edit routing-options dynamic-tunnels tunnel-name rsvp-te entry-name]
[edit routing-instances instance-name provider-tunnel]
```

Description

Specify the LSP template. An LSP template is used as the basis for other dynamically generated LSPs. This feature can be used for a number of applications, including point-to-multipoint LSPs, flooding VPLS traffic, configuring ingress replication for IP multicast using MBGP MVPNs, and to enable RSVP automatic mesh. There is no default setting for the label-switched-path-template statement, so you must configure either the default-template using the default-template option, or you must specify the name of your preconfigured LSP template.

Options

default-template—Specify that the default LSP template be used for the dynamically generated LSPs.

lsp-template-name—Specify the name of an LSP to be used as a template for the dynamically generated LSPs.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.5.

RELATED DOCUMENTATION

[Example: Configuring Ingress Replication for IP Multicast Using MBGP MVPNs | 1078](#)

Configuring Point-to-Multipoint LSPs for an MBGP MVPN

[Configuring Dynamic Point-to-Multipoint Flooding LSPs | 1076](#)

[Configuring RSVP Automatic Mesh](#)

local-switching (Layer 2 Circuits)

IN THIS SECTION

- [Syntax | 1557](#)
- [Hierarchy Level | 1558](#)
- [Description | 1558](#)
- [Required Privilege Level | 1558](#)
- [Release Information | 1558](#)

Syntax

```
local-switching {  
  interface interface-name {  
    description text;  
    encapsulation-type;
```



```

end-interface {
    interface interface-name;
    no-revert;
    protect-interface interface-name;
}
ignore-encapsulation-mismatch;
ignore-mtu-mismatch;
no-revert;
protect-interface interface-name;
}
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name protocols l2circuit],
[edit protocols l2circuit]

```

Description

Configure a local switching interface. A local switching interface allows you to terminate a virtual circuit on the local router.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring Local Interface Switching in Layer 2 Circuits](#) | 357

local-switching (VPLS)

IN THIS SECTION

- [Syntax | 1559](#)
- [Hierarchy Level | 1559](#)
- [Description | 1559](#)
- [Required Privilege Level | 1559](#)
- [Release Information | 1560](#)

Syntax

```
local-switching;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
mesh-group mesh-group-name],  
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
```

Description

Allows you to terminate multiple Layer 2 circuit pseudowires at a single VPLS mesh group. Note that when using [vpls-id-list](#), you can enable local-switching to allow local switching of traffic (including BUM traffic) between multiple pseudo wires. Enabling local-switching also eliminates the need to have a dedicated mesh-group for each LDP spoke pseudo wire (which has a limit of 14).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.3.

RELATED DOCUMENTATION

[Configuring Switching Between Pseudowires Using VPLS Mesh Groups](#) | 632

mac-flush

IN THIS SECTION

- [Syntax](#) | 1560
- [Hierarchy Level](#) | 1560
- [Description](#) | 1561
- [Options](#) | 1561
- [Required Privilege Level](#) | 1562
- [Release Information](#) | 1562

Syntax

```
mac-flush [ explicit-mac-flush-message-options ];
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
mesh-group mesh-group-name],  
[edit routing-instances routing-instance-name protocols vpls],  
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
```

Description

Enable media access control (MAC) flush processing for the virtual private LAN service (VPLS) routing instance or for the mesh group under a VPLS routing instance. MAC flush processing removes MAC addresses from the MAC address database that have been learned dynamically. With the dynamically learned MAC addresses removed, MAC address convergence requires less time to complete.

For certain cases where MAC flush processing is not initiated by default, you can also specify *explicit-mac-flush-message-options* that additionally configure the router to send explicit MAC flush messages. To configure the router to send explicit MAC flush messages under specific conditions, include *explicit-mac-flush-message-options* with the statement.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

In certain cases, BGP updates sent by the provider edge (PE) device are delayed for 1 to 5 seconds.

This happens when all of the following conditions are true:

- BGP-based VPLS multihoming sites are configured.
- The `mac-flush` statement is included in the configuration.
- a non-minimum designated-forwarder site (site-x, for example) transitions to non-designated-forwarder status

The BGP update being delayed corresponds to the explicit-MAC flush notification message sent by site-x's PE device (PE2, for example). This BGP update message is not deferred if the designated-forwarder status is lost due to a locally-triggered event (for example, a local attachment-circuit interface going down). In other words, BGP update messages are deferred (in Device PE2) only when the designated-forwarder state is lost due to external events taking place in remote PE devices that also hold site-x (for example, in PE1). Suppose, for example, that Device PE1 is the default designated-forwarder with site-x's local interface in the DOWN state. Device PE2 defers BGP update message after Device PE1's local interface comes back to the UP state.

Options

explicit-mac-flush-message-options—(Optional) You can specify one or more of the following explicit MAC flush message options:

- *any-interface*—(Optional) Send a MAC flush message when any customer-facing attachment circuit interface goes down.

- **any-spoke**—(Optional) Send a MAC FLUSH-FROM-ME flush message to all provider edge (PE) routers in the core when one of the spoke pseudowires between the multitenant unit switch and the other network-facing provider edge (NPE) router goes down, causing the multitenant unit switch to switch to this NPE router.

NOTE: This option has a similar effect in a VPLS multihoming environment with multiple multitenant unit switches connected to NPE routers, where both multitenant unit switches have pseudowires that terminate in a mesh group with local-switching configured. If the any-spoke option is enabled, then both PE routers send MAC FLUSH-FROM-ME flush messages to all PEs in the core.

- **propagate**—(Optional) Propagate MAC flush to the core.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

RELATED DOCUMENTATION

[Configuring VPLS Routing Instances | 674](#)

[Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS | 629](#)

mac-pinning

IN THIS SECTION

- [Syntax | 1563](#)
- [Hierarchy Level | 1563](#)
- [Description | 1563](#)

- [Default | 1564](#)
- [Required Privilege Level | 1564](#)
- [Release Information | 1564](#)

Syntax

```
mac-pinning;
```

Hierarchy Level

```
[edit bridge-domains bridge-domain-name bridge-options interface interface-name],
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options
interface interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains
bridge-domain-name bridge-options interface interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name switch-options
interface interface-name],
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options
interface interface-name],
[edit routing-instances routing-instance-name protocols evpn],
[edit routing-instances routing-instance-name switch-options interface interface-name],
[edit switch-options interface interface-name],
[edit switch-options interface interface-name interface-mac-limit limit]
```

Description

Enable MAC pinning on an interface. When you enable MAC pinning on an interface in a bridge domain or VPLS domain, MAC addresses learned over that interface cannot be relearned on any other interface in the same bridge domain or VPLS domain until the MAC address is cleared from the MAC table. If the same MAC address is learned over any other interface in the same bridge domain, it is discarded. This, effectively, controls MAC address moves and prevents creation of loops in Layer 2 bridges.

NOTE: If the timeout interval for the MAC addresses is not specified by setting the `mac-table-aging-time` statement, the MAC addresses learned over the MAC pinning interface are pinned to the interface until the default timeout period.

Default

MAC pinning is not enabled.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 16.1.

Support at `[edit routing-instances routing-instance-name protocols evpn]` hierarchy introduced in Junos OS Release 17.2R1 on MX Series Routers with MPC and MIC interfaces.

RELATED DOCUMENTATION

[Understanding Layer 2 Learning and Forwarding for Bridge Domains](#)

[Understanding Layer 2 Learning and Forwarding for Bridge Domains Functioning as Switches with Layer 2 Trunk Ports](#)

[Understanding MAC Pinning | 1169](#)

mac-statistics

IN THIS SECTION

- [Syntax | 1565](#)
- [Hierarchy Level | 1565](#)

- [Description | 1565](#)
- [Default | 1565](#)
- [Required Privilege Level | 1566](#)
- [Release Information | 1566](#)

Syntax

```
mac-statistics;
```

Hierarchy Level

```
[edit bridge-domains bridge-domain-name bridge-options],
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options],
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains
bridge-domain-name bridge-options],
[edit logical-systems logical-system-name routing-instances routing-instance-name switch-options],
[edit logical-systems logical-system-name switch-options],
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options],
[edit routing-instances routing-instance-name switch-options],
[edit routing-instances routing-instance-name protocols evpn],
[edit switch-options],
[edit switch-options],
[edit vlans vlan-name switch-options]
```

Description

(MX Series routers, EX Series switches, and QFX Series only) For bridge domains or VLANs, enable MAC accounting either for a specific bridge domain or VLAN, or for a set of bridge domains or VLANs associated with a Layer 2 trunk port.

Default

disabled

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

Support for the `switch-options` statement added in Junos OS Release 9.2.

Support for top-level configuration for the `virtual-switch` type of routing instance added in Junos OS Release 9.2. In Junos OS Release 9.1 and earlier, the routing instances hierarchy supported this statement only for a VPLS instance or a bridge domain configured within a virtual switch.

Support for logical systems added in Junos OS Release 9.6.

[`edit switch-options`] and [`edit vlans vlan-name switch-options`] hierarchy levels introduced in Junos OS Release 12.3R2 for EX Series switches.

Support for EVPNs added in Junos OS Release 13.2 for MX 3D Series routers.

[`edit switch-options`] and [`edit vlans vlan-name switch-options`] hierarchy levels introduced in Junos OS Release 13.2 for the QFX Series.

RELATED DOCUMENTATION

[Understanding Layer 2 Learning and Forwarding for Bridge Domains](#)

[Layer 2 Learning and Forwarding for VLANs Overview](#)

[Understanding Layer 2 Learning and Forwarding for Bridge Domains Functioning as Switches with Layer 2 Trunk Ports](#)

[Layer 2 Learning and Forwarding for VLANs Acting as a Switch for a Layer 2 Trunk Port](#)

[*Configuring EVPN Routing Instances*](#)

[*Configuring EVPN Routing Instances on EX9200 Switches*](#)

mac-table-size

IN THIS SECTION

- [Syntax | 1567](#)
- [Hierarchy Level | 1567](#)
- [Description | 1567](#)
- [Options | 1567](#)
- [Required Privilege Level | 1568](#)
- [Release Information | 1568](#)

Syntax

```
mac-table-size size {  
    packet-action drop;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit routing-instances routing-instance-name protocols evpn],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Specify the size of the MAC address table.

Options

size—Size of the MAC address table.

Range:

- (M Series and T Series routers only) 16 through 65,536 MAC addresses
- (MX Series routers only) 16 through 1,048,575 MAC addresses
- (T4000 routers with Type 5 FPCs only) 16 through 262,143 MAC addresses

NOTE: Before modifying the size of the MAC address table (to 262,143 addresses), you must enable network services mode by including the `enhanced-mode` statement at the `[edit chassis network-services]` hierarchy level and then reboot the router.

- **Default:** 5120 MAC addresses

The remaining statement is explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

[Configuring the Size of the VPLS MAC Address Table | 688](#)

[Configuring Improved VPLS MAC Address Learning on T4000 Routers with Type 5 FPCs | 1220](#)

[enhanced-mode](#)

evpn

map-dest-bmac-to-dest-cmac

IN THIS SECTION

- [Syntax | 1569](#)
- [Hierarchy Level | 1569](#)
- [Description | 1569](#)
- [Required Privilege Level | 1569](#)
- [Release Information | 1569](#)

Syntax

```
map-dest-bmac-to-dest-cmac <b-mac-address> <c-mac-address>;
```

Hierarchy Level

```
[edit routing-instances routing-instance-name service-groups service-group-name]
```

Description

Specify the destination customer MAC (C-MAC) address to Provider Backbone Bridging (PBB) MAC (B-MAC) address mapping. The address mapping prevents unnecessary flooding of packets towards the core.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 16.1.

RELATED DOCUMENTATION

| *routing-instances (Multiple Routing Entities)*

mesh-group (Protocols VPLS)

IN THIS SECTION

- [Syntax | 1570](#)
- [Hierarchy Level | 1571](#)
- [Description | 1571](#)
- [Options | 1571](#)
- [Required Privilege Level | 1571](#)
- [Release Information | 1571](#)

Syntax

```
mesh-group mesh-group-name {  
    interface interface-name;  
    l2vpn-id (as-number:id | ip-address:id);  
    local-switching;  
    mac-flush [ explicit-mac-flush-message-options ];  
    neighbor address {...};  
    peer-as all;  
    pseudowire-status-tlv hot-standby-vc-on;  
    route-distinguisher (as-number:id | ip-address:id);  
    vpls-id number;  
    vrf-export [ policy-names ];  
    vrf-import [ policy-names ];  
    vrf-target {  
        community;  
        import community-name;  
        export community-name;  
    }  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
site site-name],
[edit routing-instances routing-instance-name protocols vpls],
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Specify the virtual private LAN service (VPLS) mesh group. The statement options allow you to specify each provider edge (PE) router that is a member of the mesh group. This statement is also used in the configuration of inter-autonomous system (AS) VPLS with media access control (MAC) operations.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

mesh-group-name—Name of the VPLS mesh group.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.0.

local-switching, mac-tlv-receive, mac-tlv-send, and peer-as options introduced in Junos OS Release 9.3.

pseudowire-status-tlv and mac-flush options introduced in Junos OS Release 10.0.

route-distinguisher, vrf-export, vrf-import, and vrf-target options introduced in Junos OS Release 11.2.

hot-standby-vc-on and interface *interface-name* options introduced in Junos OS Release 15.1R2.

RELATED DOCUMENTATION

[Configuring VPLS Routing Instances | 674](#)

[Configuring Interoperability Between BGP Signaling and LDP Signaling in VPLS | 629](#)

minimum-interval (BFD Liveness Detection)

IN THIS SECTION

- [Syntax | 1572](#)
- [Hierarchy Level | 1572](#)
- [Description | 1573](#)
- [Options | 1573](#)
- [Required Privilege Level | 1573](#)
- [Release Information | 1573](#)

Syntax

```
minimum-interval milliseconds;
```

Hierarchy Level

```
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
```

```

[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-
detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) oam
bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],

```

Description

Configure the minimum interval after which the local routing device transmits hello packets and then expects to receive a reply from a neighbor with which it has established a BFD session. Optionally, instead of using this statement, you can specify the minimum transmit and receive intervals separately using the `minimum-interval` (specified under the `transmit-interval` statement) and `minimum-receive-interval` statements.

Options

milliseconds—Specify the minimum interval value for BFD liveliness detection.

- **Range:** 1 through 255,000

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.5.

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS](#) | 231

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

[bfd-liveness-detection \(Layer 2 VPN and VPLS\) | 1446](#)

[minimum-receive-interval \(BFD Liveness Detection\) | 1574](#)

transmit-interval

minimum-receive-interval (BFD Liveness Detection)

IN THIS SECTION

- [Syntax | 1574](#)
- [Hierarchy Level | 1574](#)
- [Description | 1575](#)
- [Options | 1575](#)
- [Required Privilege Level | 1575](#)
- [Release Information | 1575](#)

Syntax

```
minimum-receive-interval milliseconds;
```

Hierarchy Level

```
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) neighbor neighbor-id oam bfd-liveness-detection],
```

```
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls)mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-
detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls)mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],
```

Description

Configure the minimum interval after which the local routing device must receive a reply from a neighbor with which it has established a BFD session. Optionally, instead of using this statement, you can configure the minimum receive interval using the `minimum-interval` statement.

Options

milliseconds—Specify the minimum receive interval value.

- **Range:** 1 through 255,000

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.5.

Support for BFD authentication introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

[bfd-liveness-detection \(Layer 2 VPN and VPLS\) | 1446](#)

[minimum-interval \(BFD Liveness Detection\) | 1572](#)

transmit-interval

mtu

IN THIS SECTION

- [Syntax | 1576](#)
- [Hierarchy Level | 1576](#)
- [Description | 1577](#)
- [Options | 1579](#)
- [Required Privilege Level | 1580](#)
- [Release Information | 1580](#)

Syntax

```
mtu bytes;
```

Hierarchy Level

```
[edit interfaces interface-name],
[edit interfaces interface-name unit logical-unit-number family family],
[edit interfaces interface-range name],
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number
family family],
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name backup-neighbor address],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
```

```

interface-name],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name backup-neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn interface interface-name],
[edit protocols l2circuit local-switching interface interface-name backup-neighbor address],
[edit protocols l2circuit neighbor address interface interface-name]
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor address],
[edit routing-instances routing-instance-name protocols l2vpn interface interface-name],
[edit logical-systems name protocols ospf area name interface ],
[edit logical-systems name routing-instances name protocols
ospf area name interface],
[edit protocols ospf area name interface ],
[edit routing-instances name protocols ospf area name interface]

```

Description

Specify the maximum transmission unit (MTU) size for the media or protocol. The default MTU size depends on the device type. Changing the media MTU or protocol MTU causes an interface to be deleted and added again.

To route jumbo data packets on an integrated routing and bridging (IRB) interface or routed VLAN interface (RVI) on EX Series switches, you must configure the jumbo MTU size on the member physical interfaces of the VLAN that you have associated with the IRB interface or RVI, as well as on the IRB interface or RVI itself (the interface named *irb* or *vlan*, respectively).



CAUTION: For EX Series switches, setting or deleting the jumbo MTU size on an IRB interface or RVI while the switch is transmitting packets might cause packets to be dropped.

NOTE: The MTU for an IRB interface is calculated by removing the Ethernet header overhead [6(DMAC)+6(SMAC)+2(EtherType)]. Because, the MTU is the lower value of the MTU configured on the IRB interface and the MTU configured on the IRB's associated bridge domain IFDs or IFLs, the IRB MTU is calculated as follows:

- In case of Layer 2 IFL configured with the `flexible-vlan-tagging` statement, the IRB MTU is calculated by including 8 bytes overhead (SVLAN+CVLAN).

- In case of Layer 2 IFL configured with the `vlan-tagging` statement, the IRB MTU is calculated by including a single VLAN 4 bytes overhead.

NOTE:

- If a packet whose size is larger than the configured MTU size is received on the receiving interface, the packet is eventually dropped. The value considered for MRU (maximum receive unit) size is also the same as the MTU size configured on that interface.
- Not all devices allow you to set an MTU value, and some devices have restrictions on the range of allowable MTU values. You cannot configure an MTU for management Ethernet interfaces (fxp0, em0, or me0) or for loopback, multilink, and multicast tunnel devices.
- On ACX Series routers, you can configure the protocol MTU by including the `mtu` statement at the `[edit interfaces interface-name unit logical-unit-number family inet]` or `[edit interfaces interface-name unit logical-unit-number family inet6]` hierarchy level.
 - If you configure the protocol MTU at any of these hierarchy levels, the configured value is applied to all families that are configured on the logical interface.
 - If you are configuring the protocol MTU for both `inet` and `inet6` families on the same logical interface, you must configure the same value for both the families. It is not recommended to configure different MTU size values for `inet` and `inet6` families that are configured on the same logical interface.
- Starting in Release 14.2, MTU for IRB interfaces is calculated by removing the Ethernet header overhead ($6(\text{DMAC}) + 6(\text{SMAC}) + 2(\text{EtherType})$), and the MTU is a minimum of the two values:
 - Configured MTU
 - Associated bridge domain's physical or logical interface MTU
 - For Layer 2 logical interfaces configured with `flexible-vlan-tagging`, IRB MTU is calculated by including 8 bytes overhead ($\text{SVLAN} + \text{CVLAN}$).
 - For Layer 2 logical interfaces configured with `vlan-tagging`, IRB MTU is calculated by including single VLAN 4 bytes overhead.

NOTE: Changing the Layer 2 logical interface option from `vlan-tagging` to `flexible-vlan-tagging` or vice versa adjusts the logical interface MTU by 4 bytes with the existing MTU size. As a result, the Layer 2 logical interface is deleted and re-added, and the IRB MTU is re-computed appropriately.

For more information about configuring MTU for specific interfaces and router or switch combinations, see [Configuring the Media MTU](#).

Options

bytes—MTU size.

- **Range:** 256 through 9192 bytes, 256 through 9216 (EX Series switch interfaces), 256 through 9500 bytes (Junos OS 12.1X48R2 for PTX Series routers), 256 through 9500 bytes (Junos OS 16.1R1 for MX Series routers)

Starting in Junos OS Evolved Release 21.2R1, MTU 16KB is only for transiting traffic of WAN interfaces on the PTX10001-36MR, PTX10008 and PTX10004 routers. MTU is 9500B for protocols and 16KB for transit traffic.

NOTE: Starting in Junos OS Release 16.1R1, the MTU size for a media or protocol is increased from 9192 to 9500 for Ethernet interfaces on the following MX Series MPCs:

- MPC1
 - MPC2
 - MPC2E
 - MPC3E
 - MPC4E
 - MPC5E
 - MPC6E
- **Default:** 1500 bytes (INET, INET6, and ISO families), 1448 bytes (MPLS), 1514 bytes (EX Series switch interfaces)

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support for Layer 2 VPNs introduced in Junos OS Release 10.4.

Statement introduced in Junos OS Release 12.2 for ACX Series Universal Metro Routers.

Support at the[set interfaces interface-name unit logical-unit-number family ccc] hierarchy level introduced in Junos OS Release 12.3R3 for MX Series routers.

RELATED DOCUMENTATION

[Configuring the Media MTU](#)

[Configuring the MTU for Layer 2 Interfaces | 212](#)

[Setting the Protocol MTU](#)

multicast-mode (EVPN)

IN THIS SECTION

- [Syntax | 1581](#)
- [Hierarchy Level | 1581](#)
- [Description | 1581](#)
- [Options | 1581](#)
- [Required Privilege Level | 1581](#)
- [Release Information | 1582](#)

Syntax

```
multicast-mode client | ingress-replication;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols],
[edit protocols evpn],
[edit routing-instances routing-instance-name protocols evpn]
```

Description

Configure the multicast server mode for delivering traffic and packets for Ethernet VPN (EVPN). This statement is required for a VXLAN EVPN instance.

NOTE: If you configure the `multicast-mode` statement, then you must also configure the `encapsulation vxlan` statement.

Options

client	Use the client as the multicast mode for delivering traffic and multicast packets across routers and switches.
ingress-replication	Use ingress replication as the multicast mode for delivering broadcast, unknown unicast, and multicast (BUM) traffic and multicast packets across routers and switches.

- **Default:** ingress-replication

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1X53-D30.

Support for logical systems on MX Series routers added in Junos OS Release 17.4R1.

RELATED DOCUMENTATION

Understanding EVPN with VXLAN Data Plane Encapsulation

EVPN Over VXLAN Encapsulation Configuration Overview for QFX Series and EX4600 Switches

Using a Default Layer 3 Gateway to Route Traffic in an EVPN-VXLAN Overlay Network

Example: Configuring an EVPN Control Plane and VXLAN Data Plane

multiplier (BFD Liveness Detection)

IN THIS SECTION

- [Syntax | 1582](#)
- [Hierarchy Level | 1582](#)
- [Description | 1583](#)
- [Options | 1583](#)
- [Required Privilege Level | 1583](#)
- [Release Information | 1584](#)

Syntax

```
multiplier number;
```

Hierarchy Level

```
[edit logical-systems name
  routing-instances
    name protocols (evpn |
  l2vpn | vpls) oam
    bfd-liveness-detection],
```

```

[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-
detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],

```

Description

Configure the number of hello packets not received by a neighbor that causes the originating interface to be declared down.

Options

number—Number of hello packets.

- **Range:** 1 through 255
- **Default:** 3

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.5.

Support for BFD authentication introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

[bfd-liveness-detection \(Layer 2 VPN and VPLS\) | 1446](#)

multi-homing (VPLS Multihoming for BGP VPLS)

IN THIS SECTION

- [Syntax | 1584](#)
- [Hierarchy Level | 1584](#)
- [Description | 1585](#)
- [Required Privilege Level | 1585](#)
- [Release Information | 1585](#)

Syntax

```
multi-homing;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
site site-name],
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Configuration of this statement tracks BGP peers, such as to prevent isolation of the PE router from the core or split brain.. If no BGP peer is available, all active interfaces for a site are deactivated.

When identical site IDs are used without configuring multihoming, a collision log message is generated at each signaling: RPD_L2VPN_SITE_COLLISION: Same site ID 2 configured on remote PE (RD 8.8.8.1:1013:) and local PE in VPN 1013 (non-multihomed site 2). This is expected behavior.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 7.5.

RELATED DOCUMENTATION

[Configuring Multihoming on the PE Router](#) | 953

multi-homing (VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax](#) | 1586
- [Hierarchy Level](#) | 1586
- [Description](#) | 1586
- [Required Privilege Level](#) | 1587
- [Release Information](#) | 1587

Syntax

```
multi-homing {
  peer-active;
  site site-name {
    active-interface interface-name {
      any;
      primary interface-name;
    }
    identifier identifier;
    interface interface-name {
      preference preference-value;
    }
    peer-active;
    preference (preference-value | backup | primary);
  }
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls],
[edit routing-instances instance-name protocols vpls]
```

Description

For VPLS autodiscovery (FEC 129), specify the parameters for multihoming to two or more provider edge (PE) routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

neighbor (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1587](#)
- [Hierarchy Level | 1589](#)
- [Description | 1589](#)
- [Options | 1589](#)
- [Required Privilege Level | 1589](#)
- [Release Information | 1589](#)

Syntax

```
neighbor address {  
  interface interface-name {  
    backup-neighbor address {  
      community name;  
      hot-standby;  
      psn-tunnel-endpoint address;  
      standby;  
    }  
  }  
}
```

```

        virtual-circuit-id number;
    }
    bandwidth (bandwidth | ctnumber bandwidth);
    community community-name;
    (control-word | no-control-word);
    description text;
    egress-protection {
        protected-l2circuit {
            egress-pe address;
            ingress-pe address;
            virtual-circuit-id identifier;
        }
        protector-interface interface-name;
        protector-pe address {
            context-identifier identifier;
            lsp lsp-name;
        }
    }
}
encapsulation-type type;
ignore-encapsulation-mismatch;
ignore-mtu-mismatch;
mtu mtu-number;
no-revert;
protect-interface interface-name;
pseudowire-status-tlv hot-standby-vc-on;
psn-tunnel-endpoint address;
revert-time seconds;
static {
    incoming-label label;
    outgoing-label label;
    send-oam;
}
switchover-delay milliseconds;
virtual-circuit-id identifier;
}
}

```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit],  
[edit protocols l2circuit]
```

Description

Each Layer 2 circuit is represented by the logical interface connecting the local provider edge (PE) router or switch to the local customer edge (CE) router or switch. All the Layer 2 circuits using a particular remote PE router or switch designated for remote CE routers or switches are listed under the `neighbor` statement (`neighbor` designates the PE router or switch). Each neighbor is identified by its IP address and is usually the end-point destination for the LSP tunnel (transporting the Layer 2 circuit).

Options

address—IP address of a neighboring router or switch.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring the Neighbor Interface for the Layer 2 Circuit](#) | 361

neighbor (Protocols VPLS)

IN THIS SECTION

- [Syntax | 1590](#)
- [Hierarchy Level | 1591](#)
- [Description | 1591](#)
- [Options | 1591](#)
- [Required Privilege Level | 1592](#)
- [Release Information | 1592](#)

Syntax

```
neighbor neighbor-id {  
    mac-pinning;  
    associate-profile {  
        dynamic-profile-name;  
        profile-variable-set profile-variable-set-name;  
    }  
    backup-neighbor {...}  
    community community-name;  
    connection-protection;  
    encapsulation-type type;  
    ignore-encapsulation-mismatch;  
    oam {  
        bfd-liveness-detection {  
            detection-time {  
                threshold milliseconds;  
            }  
            minimum-interval milliseconds;  
            minimum-receive-interval milliseconds;  
            multiplier number;  
            no-adaptation;  
            transmit-interval {  
                minimum-interval milliseconds;  
                threshold milliseconds;  
            }  
        }  
    }  
}
```

```

        version (1 | automatic);
    }
    ping-interval;
}
pseudowire-status-tlv;
psn-tunnel-endpoint address;
revert-time seconds;

static {
    incoming-label label;
    outgoing-label label;
    control-word;
    no-control-word;
}
switchover-delay milliseconds;
vpls-id-list vc-id-numbers;
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls mesh-
group mesh-group-name],
[edit routing-instances routing-instance-name protocols vpls],
[edit routing-instances instance-name protocols vpls mesh-group mesh-group-name]

```

Description

Specify each of the PE routers participating in the VPLS domain. Configuring this statement enables LDP for signaling VPLS.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

neighbor-id—Specify the neighbor identifier for each PE router participating in the VPLS domain.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

The pseudowire-status-tlv option was added in Junos OS Release 10.0.

The vpls-id-list option was added in Junos OS Release 14.2 for MX Series routers to provide support for multiple pseudowires between the same pair of PEs in LDP-VPLS.

RELATED DOCUMENTATION

| [Configuring LDP Signaling for VPLS](#) | 682

no-adaptation (BFD Liveness Detection)

IN THIS SECTION

- [Syntax](#) | 1592
- [Hierarchy Level](#) | 1593
- [Description](#) | 1593
- [Required Privilege Level](#) | 1594
- [Release Information](#) | 1594

Syntax

```
no-adaptation;
```

Hierarchy Level

```
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-
detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],
```

Description

Configure BFD sessions not to adapt to changing network conditions. We recommend that you *do not* disable BFD adaptation unless it is preferable to have BFD adaptation disabled in your network.

The BFD failure detection timers are adaptive and can be adjusted to be faster or slower. The lower the BFD failure detection timer value, the faster the failure detection and vice versa. For example, the timers can adapt to a higher value if the adjacency fails (that is, the timer detects failures more slowly). Or a neighbor can negotiate a higher value for a timer than the configured value. The timers adapt to a higher value when a BFD session flap occurs more than three times in a span of 15 seconds. A back-off algorithm increases the receive (Rx) interval by two if the local BFD instance is the reason for the session flap. The transmission (Tx) interval is increased by two if the remote BFD instance is the reason for the session flap. However, include the `no-adaptation` statement in the configuration if you do not want BFD sessions to adapt to changing network conditions.

You can use the `clear bfd adaptation` command to return BFD interval timers to their configured values. The `clear bfd adaptation` command does not affect traffic flow on the routing device.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.0

Support for BFD authentication introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

[bfd-liveness-detection \(Layer 2 VPN and VPLS\) | 1446](#)

no-control-word

IN THIS SECTION

- [Syntax | 1595](#)
- [Hierarchy Level | 1595](#)
- [Description | 1595](#)
- [Required Privilege Level | 1595](#)
- [Release Information | 1595](#)

Syntax

```
no-control-word;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
mesh-group mesh-group-name neighbor address static],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address static],
[edit routing-instances routing-instance-name protocols vpls],
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor
address static],
[edit routing-instances routing-instance-name protocols vpls neighbor address static]
```

Description

Set `no-control-word` to request that other routers *not* insert a control word between the label stack and the MPLS payload. This is the default setting for BGP VPLS.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.1.

Statement introduced for static pseudowires in mesh-group and in VPLS instance in Junos OS Release 20.3R1.

RELATED DOCUMENTATION

[Control Word for BGP VPLS Overview](#) | 622

[Configuring a Control Word for BGP VPLS | 623](#)

[control-word | 1458](#)

no-control-word (Protocols Layer 2 VPN)

IN THIS SECTION

- [Syntax | 1596](#)
- [Hierarchy Level | 1596](#)
- [Description | 1596](#)
- [Default | 1597](#)
- [Required Privilege Level | 1597](#)
- [Release Information | 1597](#)

Syntax

```
no-control-word;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
  l2vpn],  
[edit routing-instances routing-instance-name protocols l2vpn]
```

Description

Disable the control word. This might be necessary on networks with equipment that does not support the control word.

NOTE: The following configuration statements are ignored for time-division multiplexing pseudowires at the [edit protocols l2vpn] hierarchy level:

- control-word
- no-control-word

Default

The control word is enabled by default. Use the `no-control-word` statement to disable the control word.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Disabling the Control Word for Layer 2 VPNs | 214](#)

[control-word \(Protocols Layer 2 VPN\) | 1456](#)

no-l2ckt

IN THIS SECTION

- [Syntax | 1598](#)
- [Hierarchy Level | 1598](#)
- [Description | 1598](#)
- [Required Privilege Level | 1598](#)

Syntax

```
no-l2ckt;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options forwarding-table chained-composite-  
next-hop ingress],  
[edit routing-options forwarding-table chained-composite-next-hop ingress]
```

Description

Disable composite chained next hop for ingress Layer 2 circuit label-switched paths (LSPs).

The remaining statements are explained separately.

NOTE: For PTX Series routers, it is recommended that you do not use this command and disable composite chained next hop for ingress LSPs.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.3.

no-l2vpn

IN THIS SECTION

- [Syntax | 1599](#)
- [Hierarchy Level | 1599](#)
- [Description | 1599](#)
- [Required Privilege Level | 1600](#)
- [Release Information | 1600](#)

Syntax

```
no-l2vpn {  
    l2ckt;  
    l3vpn;  
    labeled-bgp;  
    no-l2ckt;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-options forwarding-table chained-composite-  
next-hop ingress],  
[edit routing-options forwarding-table chained-composite-next-hop ingress]
```

Description

Disable composite chained next hop for ingress Layer 2 virtual private networkk (VPN) label-switched paths (LSPs).

The remaining statements are explained separately.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.3.

no-local-switching (VPLS)

IN THIS SECTION

- [Syntax | 1600](#)
- [Hierarchy Level | 1600](#)
- [Description | 1600](#)
- [Required Privilege Level | 1601](#)
- [Release Information | 1601](#)

Syntax

```
no-local-switching;
```

Hierarchy Level

```
[edit bridge-domains bridge-domain-name]
```

Description

Prevent CE devices from communicating directly with each other. If the `no-local-switching` statement is configured, frames arriving on a CE interface are sent to a VPLS edge (VE) device or core-facing interfaces only.

NOTE: (MX80, MX104, and the 16x10GE MPC, MPC1, or MPC2 on MX240, MX480, MX960, MX2010, and MX2020 only) If you configure the `no-local-switching` command at the `[edit bridge-domains bridge-domain-name]` hierarchy level, it might not prevent multicast traffic from being forwarded between the CE-facing interfaces of the bridge domain. Broadcast, unknown unicast, and known multicast traffic does not exhibit this behavior.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.5.

RELATED DOCUMENTATION

[Configuring VPLS and Integrated Routing and Bridging](#) | 1134

no-mac-learning

IN THIS SECTION

- [Syntax](#) | 1602
- [QFX Series and EX4600](#) | 1602
- [QFX Series per VLAN](#) | 1602
- [EX Series Q-in-Q Interfaces](#) | 1602
- [EX Series and SRX Series Q-inQ Vlans](#) | 1603
- [ACX Series, MX Series, EX Series with ELS support, M Series, T Series](#) | 1603
- [Description](#) | 1603
- [Default](#) | 1604

- Required Privilege Level | 1604
- Release Information | 1604

Syntax

```
no-mac-learning;
```

QFX Series and EX4600

For QFX Series and EX4600 platforms without ELS:

```
[edit ethernet-switching-options interfaces interface-name]
```

For QFX Series and EX4600 platforms with ELS:

```
[edit vlans vlan-name switch-options]
```

QFX Series per VLAN

```
[edit vlans vlan-name]
```

```
[edit vlans vlan-name switch-options]
```

EX Series Q-in-Q Interfaces

```
[edit ethernet-switching-options interfaces interface-name]
```

EX Series and SRX Series Q-inQ Vlans

```
[edit vlans vlan-name]
```

ACX Series, MX Series, EX Series with ELS support, M Series, T Series

```
[edit bridge-domains bridge-domain-name bridge-options],
[edit bridge-domains bridge-domain-name bridge-options interface interface-name],
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options],
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options
interface interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains
bridge-domain-name bridge-options],
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains
bridge-domain-name bridge-options interface interface-name],
[edit logical-systems logical-system-name routing-instances routing-instance-name switch-options],
[edit logical-systems logical-system-name switch-options],
[edit bridge-domains bridge-domain-name bridge-options interface interface-name],
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options],
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options
interface interface-name],
[edit routing-instances routing-instance-name protocols evpn],
[edit routing-instances routing-instance-name protocols evpn interface interface-name],
[edit routing-instances routing-instance-name switch-options],
[edit switch-options],
[edit switch-options],
[edit switch-options interface interface-name],
[set vlans vlan-name switch-options]
```

Description

For QFX Series, EX Series switches and SRX Series devices, disables MAC address learning for the specified VLAN.

For QFX Series and EX4600, disable MAC address learning for the specified interface. Disabling MAC address learning on an interface disables learning for all the VLANs of which that interface is a member.

For EX Series switches' Q-in-Q interfaces, disables MAC address learning for the specified interface. Disabling MAC address learning on an interface disables learning for all the VLANs of which that interface is a member.

For MX Series routers and EX Series switches with ELS support, disables MAC learning for a virtual switch, for a bridge domain or VLAN, for a specific logical interface in a bridge domain or VLAN, or for a set of bridge domains or VLANs associated with a Layer 2 trunk port. On platforms that support EVPNs, you can disable MAC learning on an EVPN.

NOTE: When MAC learning is disabled for a VPLS routing instance, traffic is not load-balanced and only one of the equal-cost next hops is used.

Default

MAC learning is enabled.

Required Privilege Level

system—To view this statement in the configuration.

system-control—To add this statement to the configuration.

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

Support for the `switch-options` statement added in Junos OS Release 9.2.

Support for top-level configuration for the `virtual-switch type` of routing instance added in Junos OS Release 9.2. In Junos OS Release 9.1 and earlier, the routing instances hierarchy supported this statement only for a VPLS instance or bridge domain configured within a virtual switch.

Support for logical systems added in Junos OS Release 9.6.

[edit switch-options], [edit switch-options interface *interface-name*], [edit vlans *vlan-name* switch-options], and [edit vlans *vlan-name* switch-options interface *interface-name*] hierarchy levels introduced in Junos OS Release 12.3 R2 for EX Series switches.

Support for EVPNs added in Junos OS Release 13.2 for MX 3D Series routers.

Hierarchy levels [edit switch-options interface *interface-name*] and [edit vlans *vlan-name* switch-options] introduced in Junos OS Release 13.2X50-D10 for EX Series switches.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

[Understanding Layer 2 Learning and Forwarding for Bridge Domains](#)

[Layer 2 Learning and Forwarding for VLANs Overview](#)

[Understanding Layer 2 Learning and Forwarding for Bridge Domains Functioning as Switches with Layer 2 Trunk Ports](#)

[Understanding Bridging and VLANs on Switches](#)

[Understanding Q-in-Q Tunneling and VLAN Translation](#)

[Understanding Q-in-Q Tunneling and VLAN Translation](#)

[Configuring Q-in-Q Tunneling on EX Series Switches](#)

no-normalization

IN THIS SECTION

- [Syntax | 1605](#)
- [Hierarchy Level | 1605](#)
- [Description | 1606](#)
- [Required Privilege Level | 1606](#)
- [Release Information | 1606](#)

Syntax

```
no-normalization;
```

Hierarchy Level

```
[edit logical-systems name routing-instances name],
[edit logical-systems name routing-instances name bridge-domains name bridge-options],
```



```
[edit routing-instances name ],
[edit routing-instances name bridge-domains name bridge-options]
```

Description

The `no-normalization` statement disables VLAN ID (VID) normalization for interfaces. This allows the configuration of VLAN-based service for EVPN with VID translation. This means the customer can have a different VID per Ethernet segment per PE with a strict compliance of RFC 7432. Use of this statement sets the Ethernet tag ID to zero.

Configuration of `vlan-id none` and `no-normalization` statements together enable transportation of dual-tagged frames across the EVPN core network in a virtual switch instance type.

Following are examples of the prerequisites for and use of the `no-normalization` statement on routing instance `r1`:

- `no-normalization` statement can be configured Only for EVPN instances:

```
set routing-instances r1 instance-type evpn
set routing-instances r1 no-normalization
```

- `no-normalization` of VLAN can be configured Only when `instance-type virtual-switch` along with protocols `evpn` is preconfigured:

```
set routing-instances r1 instance-type virtual-switch
set routing-instances r1 protocols evpn
set routing-instances r1 bridge-domains xyz bridge-options no-normalization
```

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 17.3R1.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

[routing-instances](#) | [1651](#)

[instance-type](#) | [1397](#)

VLAN-Based Service for EVPN

Virtual Switch Support for EVPN Overview

no-revert (Local Switching)

IN THIS SECTION

- [Syntax](#) | [1607](#)
- [Hierarchy Level](#) | [1607](#)
- [Description](#) | [1607](#)
- [Required Privilege Level](#) | [1608](#)
- [Release Information](#) | [1608](#)

Syntax

```
no-revert;
```

Hierarchy Level

```
[edit protocols l2circuit local-switching interfaces interface-name]
```

```
[edit protocols l2circuit local-switching interfaces interface-name end-interface interface-name]
```

Description

(Optional) Prevent the local switching interface from reverting to the primary interface.

NOTE: The protect interface must be configured prior to configuring the `no-revert` statement.

Typically, when the primary interface goes down, the pseudowire starts using the protect interface. By default, when the primary interface comes back online, the interface is switched-over back from the protect interface to the primary interface. To prevent the switchover back to the primary interface, unless the primary interface goes down, include the `no-revert` statement. This prevents loss of traffic during the switchover.

NOTE: If the protect interface fails, the interface is switched-over back to the primary interface, irrespective of whether or not the `no-revert` statement is included in the configuration.

This statement can be configured both for the starting interface and the ending interface.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 11.4.

RELATED DOCUMENTATION

[Configuring Local Interface Switching in Layer 2 Circuits](#) | 357

no-revert (Neighbor Interface)

IN THIS SECTION

- [Syntax](#) | 1609
- [Hierarchy Level](#) | 1609

- [Description | 1609](#)
- [Required Privilege Level | 1609](#)
- [Release Information | 1610](#)

Syntax

```
no-revert;
```

Hierarchy Level

```
[edit protocols l2circuit neighbor address interfaces interface-name],  
[edit logical-systems logical-system-name protocols l2circuit neighbor address interfaces  
interface-name]
```

Description

(Optional) Prevent the protect interface from reverting to the primary interface.

NOTE: The protect interface must be configured prior to configuring the `no-revert` statement.

Typically, when the primary interface goes down, the pseudowire starts using the protect interface. By default, when the primary interface comes back online, the interface is switched-over back from the protect interface to the primary interface. To prevent the switchover back to the primary interface, unless the protect interface goes down, include the `no-revert` statement. This prevents loss of traffic during the switchover.

NOTE: If the protect interface fails, the interface is switched-over back to the primary interface, irrespective of whether or not the `no-revert` statement is included in the configuration.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 11.3.

RELATED DOCUMENTATION

| [Configuring Interfaces for Layer 2 Circuits](#) | 360

no-tunnel-services

IN THIS SECTION

- [Syntax](#) | 1610
- [Hierarchy Level](#) | 1610
- [Description](#) | 1611
- [Required Privilege Level](#) | 1611
- [Release Information](#) | 1611

Syntax

```
no-tunnel-services;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols vpls static-vpls],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit protocols vpls static-vpls],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Configure VPLS on a router without a Tunnel Services PIC. Configuring the `no-tunnel-services` statement creates a label-switched interface (LSI) to provide VPLS functionality. An LSI MPLS label is used as the inner label for VPLS. This label maps to a VPLS routing instance. On the PE router, the LSI label is stripped and then mapped to a logical LSI interface. The Layer 2 Ethernet frame is then forwarded using the LSI interface to the correct VPLS routing instance.

NOTE: In VPLS documentation, the word *Router* in terms such as *PR Router* is used to refer to any device that provides routing functions.

NOTE:

On MX Series routers, label-switched interfaces configured with the `no-tunnel-services` statement are not supported with GRE tunnels when the GRE interface resides on a DPC.

NOTE: Although visible in the CLI, the `no-tunnel-services` statement is not supported on DPC cards at the [edit logical-systems *logical-system-name* protocols vpls static-vpls] and the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls] hierarchy levels.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 7.6.

Support for static VPLS added in Junos OS Release 10.2.

RELATED DOCUMENTATION

[Configuring VPLS Without a Tunnel Services PIC | 749](#)

[Configuring Static Pseudowires for VPLS | 751](#)

[Configuring EXP-Based Traffic Classification for VPLS | 1232](#)

oam

IN THIS SECTION

- [Syntax | 1612](#)
- [Hierarchy Level | 1612](#)
- [Description | 1612](#)
- [Options | 1613](#)
- [Required Privilege Level | 1613](#)
- [Release Information | 1613](#)

Syntax

```
oam {  
    bfd-liveness-detection;  
    ping-interval;  
    ping-multiplier ping-count;  
}
```

Hierarchy Level

```
[edit routing-instances routing-instance-name protocols l2vpn],  
[edit routing-instances routing-instance-name protocols vpls],  
[edit routing-instances routing-instance-name protocols vpls neighbor address],  
[edit protocols l2circuit neighbor address interface interface-name]
```

Description

Allows you to configure bidirectional forwarding detection (BFD) and a control channel for a pseudowire, in addition to the corresponding operations and management functions to be used over that control channel. BFD provides a low resource fault detection mechanism for the continuous monitoring of the pseudowire data path and for detecting data plane failures. The `control-channel` statement is not applicable to Layer 2 circuit pseudowires.

Options

bfd-liveness-detection	The <code>bfd-liveness-detection</code> statement and substatements are described in the Junos OS Routing Protocols Library .
ping-multiplier <i>ping-count</i>	Specify the number of LSP ping packets to delay the virtual circuit connectivity verification (VCCV) Bidirectional Forwarding Detection (BFD) session from going down. The VCCV BFD session is signaled down only after the specified number of LSP ping packets are lost. This feature is supported for Layer 2 Circuit, Layer 2 VPN, and VPLS technologies.

The other statements are explained separately.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

Support for VPLS FEC 129 introduced in Junos OS Release 12.2.

`ping-multiplier` statement introduced in Junos OS Release 16.1.

RELATED DOCUMENTATION

[Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 234](#)

packet-action

IN THIS SECTION

- [Syntax | 1614](#)
- [Hierarchy Level | 1614](#)

- [Description | 1615](#)
- [Default | 1615](#)
- [Options | 1616](#)
- [Required Privilege Level | 1616](#)
- [Release Information | 1616](#)

Syntax

```
packet-action action;
```

Hierarchy Level

```
[edit bridge-domains bridge-domain-name bridge-options interface interface-name interface-mac-limit
limit],
[edit bridge-domains bridge-domain-name bridge-options interface-mac-limit limit],
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options
interface interface-name interface-mac-limit limit],
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options interface-
mac-limit limit],
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains
bridge-domain-name bridge-options interface interface-name interface-mac-limit limit],
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains
bridge-domain-name bridge-options interface-mac-limit limit],
[edit logical-systems logical-system-name routing-instances routing-instance-name switch-options
interface interface-name interface-mac-limit limit],
[edit logical-systems logical-system-name routing-instances routing-instance-name switch-options
interface-mac-limit limit],
[edit logical-systems logical-system-name switch-options interface-mac-limit limit],
[edit protocols l2-learning global-mac-limit limit],
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options
interface interface-name interface-mac-limit limit],
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options
interface-mac-limit limit],
[edit routing-instances routing-instance-name protocols evpn interface-mac-limit (VPLS)],
[edit routing-instances routing-instance-name protocols evpn interface interface-name interface-
mac-limit (VPLS)],
```

```
[edit routing-instances routing-instance-name protocols evpn mac-table-size limit],
[edit routing-instances routing-instance-name switch-options interface interface-name interface-mac-limit limit],
[edit routing-instances routing-instance-name switch-options interface-mac-limit limit],
[edit switch-options interface-mac-limit limit],
[edit switch-options interface interface-name interface-mac-limit limit],
[edit switch-options interface-mac-limit limit],
[edit switch-options interface interface-name interface-mac-limit limit],
[edit switch-options interface-mac-limit limit],
[edit switch-options mac-table-size limit],
[edit switch-options interface interface-name interface-mac-limit limit],
[edit vlans vlan-name switch-options interface interface-name interface-mac-limit limit],
[edit vlans vlan-name switch-options interface-mac-limit limit],
[edit vlans vlan-name switch-options mac-table-size limit]
[edit vlans vlan-name switch-options interface-mac-limit limit],
[edit vlans vlan-name switch-options interface interface-name interface-mac-limit limit],
[edit vlans vlan-name switch-options mac-table-size limit]
```

Description

Specify the action taken when packets with new source MAC addresses are received after the MAC address limit is reached. If this statement is not configured, packets with new source MAC addresses are forwarded by default.

NOTE: The packet-action statement is not supported on the QFX10002-60C switch.

Default

NOTE: On a QFX Series Virtual Chassis, if you include the shutdown option at the [edit vlans *vlan-name* switch-options interface *interface-name* interface-mac-limit packet-action] hierarchy level and issue the commit operation, the system generates a commit error. The system does not generate an error if you include the shutdown option at the [edit switch-options interface *interface-name* interface-mac-limit packet-action] hierarchy level.

Disabled. The default is for packets for new source MAC addresses to be forwarded after the MAC address limit is reached.

Options

drop Drop packets with new source MAC addresses, and do not learn the new source MAC addresses.

NOTE: On QFX10000 switches, if you include the drop option, you cannot configure unicast reverse-path forwarding (URFP) on integrated routing and bridging (IRB) and MAC limiting on the same interface. If you have an MC-LAG configuration, you cannot configure MAC limiting on the interchassis link (ICL) interface.

drop-and-log (EX Series switches and QFX Series only) Drop packets with new source MAC addresses, and generate an alarm, an SNMP trap, or a system log entry.

log (EX Series switches and QFX Series only) Hold packets with new source MAC addresses, and generate an alarm, an SNMP trap, or a system log entry.

none (EX Series switches and QFX Series only) Forward packets with new source MAC addresses, and learn the new source MAC address.

shutdown (EX Series switches and QFX Series only) Disable the specified interface, and generate an alarm, an SNMP trap, or a system log entry.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

Support for the `switch-options` statement added in Junos OS Release 9.2.

Support for top-level configuration for the `virtual-switch` type of routing instance added in Junos OS Release 9.2. In Junos OS Release 9.1 and earlier, the routing instances hierarchy supported this statement only for a VPLS instance or a bridge domain configured within a virtual switch.

Support for logical systems added in Junos OS Release 9.6.

[edit switch-options interface *interface-name* interface-mac-limit *limit*], [edit switch-options interface-mac-limit *limit*], [edit switch-options mac-table-size *limit*], [edit vlans *vlan-name* switch-options interface *interface-name* interface-mac-limit *limit*], [edit vlans *vlan-name* switch-options interface-mac-limit *limit*], and [edit vlans *vlan-name* switch-options mac-table-size *limit*] hierarchy levels introduced in Junos OS Release 12.3R2 for EX Series switches.

Support for EVPNs introduced in Junos OS Release 13.2 on MX Series 5G Universal Routing Platforms.

Support at the [edit switch-options interface *interface-name* interface-mac-limit *limit*] hierarchy level and hierarchy levels under [edit vlans *vlan-name*] introduced in Junos OS Release 13.2X50-D10 for EX Series switches and Junos OS Release 13.2 for the QFX Series.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

[Configuring MAC Limiting \(ELS\)](#)

[Configuring Persistent MAC Learning \(ELS\)](#)

[Understanding Layer 2 Learning and Forwarding for Bridge Domains](#)

[Layer 2 Learning and Forwarding for VLANs Overview](#)

[Understanding Layer 2 Learning and Forwarding for Bridge Domains Functioning as Switches with Layer 2 Trunk Ports](#)

[Layer 2 Learning and Forwarding for VLANs Overview](#)

[Layer 2 Learning and Forwarding for VLANs Acting as a Switch for a Layer 2 Trunk Port](#)

path-selection

IN THIS SECTION

- [Syntax | 1618](#)
- [Hierarchy Level | 1618](#)
- [Description | 1618](#)
- [Default | 1618](#)
- [Options | 1618](#)
- [Required Privilege Level | 1620](#)

Syntax

```
path-selection {  
    (always-compare-med | cisco-non-deterministic | external-router-id);  
    as-path-ignore;  
    l2vpn-use-bgp-rules;  
    med-plus-igp {  
        igp-multiplier number;  
        med-multiplier number;  
    }  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols bgp],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols bgp],  
[edit protocols bgp],  
[edit routing-instances routing-instance-name protocols bgp]
```

Description

Configure BGP path selection.

Default

If the path-selection statement is not included in the configuration, only the multiple exit discriminators (MEDs) of routes that have the same peer ASs are compared.

Options

<code>always-compare-med</code>	Always compare MEDs whether or not the peer ASs of the compared routes are the same.
---------------------------------	--

NOTE: We recommend that you configure the `always-compare-med` option.

as-path-ignore In the best-path algorithm, skip the step that compares the autonomous system (AS) path lengths. By default, the best-path algorithm evaluates the length of the AS paths and prefers the route with the shortest AS path length.

NOTE: Starting with Junos OS Release 14.1R8, 14.2R7, 15.1R4, 15.1F6, and 16.1R1, the **as-path-ignore** option is supported for routing instances.

cisco-non-deterministic Emulate the Cisco IOS default behavior. This mode evaluates routes in the order that they are received and does not group them according to their neighboring AS. With `cisco-non-deterministic` mode, the active path is always first. All inactive, but eligible, paths follow the active path and are maintained in the order in which they were received, with the most recent path first. Ineligible paths remain at the end of the list.

As an example, suppose you have three path advertisements for the 192.168.1.0 /24 route:

- Path 1—learned through EBGP; AS Path of 65010; MED of 200
- Path 2—learned through IBGP; AS Path of 65020; MED of 150; IGP cost of 5
- Path 3—learned through IBGP; AS Path of 65010; MED of 100; IGP cost of 10

These advertisements are received in quick succession, within a second, in the order listed. Path 3 is received most recently, so the routing device compares it against path 2, the next most recent advertisement. The cost to the IBGP peer is better for path 2, so the routing device eliminates path 3 from contention. When comparing paths 1 and 2, the routing device prefers path 1 because it is received from an EBGP peer. This allows the routing device to install path 1 as the active path for the route.

NOTE: We do not recommend using this configuration option in your network. It is provided solely for interoperability to allow all routing devices in the network to make consistent route selections.

external-router-id Compare the router ID between external BGP paths to determine the active path.

igp-multiplier <i>number</i>	<p>The multiplier value for the IGP cost to a next-hop address. This option is useful for making the MED and IGP cost comparable.</p> <ul style="list-style-type: none"> • Range: 1 through 1000 • Default: 1
l2vpn-use-bgp-rules	<p>Enable routers to use both the BGP path selection algorithm and the designated forwarder path selection algorithm when selecting the preferred path to each destination in a Layer 2 VPN or VPLS routing instance. The BGP path selection algorithm is used by all of the Provider routers participating in the routing instance. The designated forwarder path selection algorithm is used by the PE router participating in the routing instance.</p> <ul style="list-style-type: none"> • Default: By default, the designated forwarder path selection algorithm is used to select the best path to reach each destination within Layer 2 VPN and VPLS routing instances.
med-multiplier <i>number</i>	<p>The multiplier value for the MED calculation. This option is useful for making the MED and IGP cost comparable.</p> <ul style="list-style-type: none"> • Range: 1 through 1000 • Default: 1
med-plus-igp	<p>Add the IGP cost to the indirect next-hop destination to the MED before comparing MED values for path selection. This statement only affects best-path selection. It does not affect the advertised MED.</p>

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

med-plus-igp option introduced in Junos OS Release 8.1.

as-path-ignore and l2vpn-use-bgp-rules options introduced in Junos OS Release 10.2.

RELATED DOCUMENTATION

Understanding BGP Path Selection

[Enabling BGP Path Selection for Layer 2 VPNs and VPLS | 220](#)

route-distinguisher

[Example: Ignoring the AS Path Attribute When Selecting the Best Path](#)

pbb-service-options

IN THIS SECTION

- [Syntax | 1621](#)
- [Hierarchy Level | 1621](#)
- [Description | 1622](#)
- [Options | 1622](#)
- [Required Privilege Level | 1622](#)
- [Release Information | 1622](#)

Syntax

```
pbb-service-options {
    default-isid isid-number;
    isid isid-number vlan-id-list [ vlan-ids ];
    mac-address mac-address;
    source-bmac <mac-address>
}
```

Hierarchy Level

```
[edit routing-instances routing-instance-name service-groups service-group-name]
```


Description

For IEEE 802.1ah provider backbone bridge (PBB) configurations, configure PBB service options for the customer routing instance (I-component) service group.

NOTE: The `mac-address` statement is not supported for PBB-EVPN.

The remaining statements are explained separately. See [CLI Explorer](#).

Options

service-group-name—Name of a service group.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in JUNOS Release 10.0.

RELATED DOCUMENTATION

[Example: Configuring E-LINE and E-LAN Services for a PBB Network on MX Series Routers](#)

peer-active (VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax | 1623](#)
- [Hierarchy Level | 1623](#)
- [Description | 1623](#)
- [Default | 1624](#)

- Required Privilege Level | 1624
- Release Information | 1624

Syntax

```
peer-active;
```

Hierarchy Level


```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing],  
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing site site-name],  
[edit routing-instances instance-name protocols vpls multi-homing],  
[edit routing-instances instance-name protocols vpls multi-homing site site-name]
```

Description

Keep customer edge (CE) interfaces in the up state when all BGP peers go down.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Consider a scenario in which two provider edge (PE) routers are sharing two multihomed sites under one routing instance, with two CE devices, CE1 and CE2.



If the BGP peering session drops between Router PE1 and Router PE2, each one would consider itself to be the designated forwarder (DF) for Device CE1 and Device CE2. This creates a loop through the two CE devices, in which traffic loops from one CE device to the other then back to the first.

Junos OS overcomes this scenario by dropping all multihomed CE interface traffic on all multihoming PE routers when the BGP session drops between the PE routers. This functionality is enabled by default for all sites in a routing instance.

The `peer-active` statement disables the default functionality, so that PE routers keep their multihomed CE interfaces in the up state, even though the BGP peering session is down.

If you configure this statement in the `multi-homing` hierarchy, the default functionality is disabled for all sites. If you configure this statement for a site, the default functionality is disabled only for that particular site.

Default

If you omit this statement, Junos OS drops all multihomed CE interface traffic on all multihoming PE routers when the BGP session drops between the PE routers.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

peer-as (VPLS)

IN THIS SECTION

- [Syntax | 1625](#)
- [Hierarchy Level | 1625](#)
- [Description | 1625](#)
- [Options | 1626](#)
- [Required Privilege Level | 1626](#)
- [Release Information | 1626](#)

Syntax

```
peer-as {  
    all;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
mesh-group mesh-group-name],  
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name]
```

Description

Enable the autonomous system border router (ASBR) to establish a single pseudowire to each of the other ASBRs interconnected using inter-AS VPLS with MAC processing at the ASBR.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

all—This option is required. All peer routers, the ASBRs, are placed within the same VPLS mesh group.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.3.

RELATED DOCUMENTATION

| [Configuring Inter-AS VPLS with MAC Processing at the ASBR](#) | 633

ping-interval

IN THIS SECTION

- [Syntax](#) | 1627
- [Hierarchy Level](#) | 1627
- [Description](#) | 1627
- [Options](#) | 1627
- [Required Privilege Level](#) | 1627
- [Release Information](#) | 1628

Syntax

```
ping-interval seconds;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name oam],
[edit logical-systems logical-system-name routing-instances instance-name protocols l2vpn oam],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls
neighbor address oam],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls mesh-
group mesh-group-name neighbor address oam],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls oam],
[edit protocols l2circuit neighbor address interface interface-name oam],
[edit routing-instances instance-name protocols l2vpn oam],
[edit routing-instances instance-name protocols vpls neighbor address oam],
[edit routing-instances instance-name protocols vpls mesh-group mesh-group-name neighbor address
oam],
[edit routing-instances instance-name protocols vpls oam]
```

Description

Configure the time interval between ping messages for bidirectional forwarding detection (BFD) sessions enabled over pseudowires inside a VPN.

Options

seconds—Time interval between ping messages.

- **Range:** 30 through 3600

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

Support for FEC 129 VPLS added in Junos OS Release 12.2.

RELATED DOCUMENTATION

[Configuring BFD for VCCV for Layer 2 VPNs, Layer 2 Circuits, and VPLS | 234](#)

[Junos OS VPNs Library for Routing Devices](#)

policer (Layer 2 VPN)

IN THIS SECTION

- [Syntax | 1628](#)
- [Hierarchy Level | 1629](#)
- [Description | 1629](#)
- [Options | 1629](#)
- [Required Privilege Level | 1629](#)
- [Release Information | 1629](#)

Syntax

```
policer {  
    input policer-template-name;  
    output policer-template-name;  
}
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number family (ccc | inet | tcc)],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number  
family (ccc | inet | tcc)]
```

Description

Use policing to control the amount of traffic flowing over the interfaces servicing a Layer 2 VPN.

Options

input *policer-template-name*—Name of one policer to evaluate when packets are received on the interface.

output *policer-template-name*—Name of one policer to evaluate when packets are transmitted on the interface.

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring Traffic Policing in Layer 2 VPNs | 229](#)

[Routing Policies, Firewall Filters, and Traffic Policers User Guide](#)

[Junos OS Network Interfaces Library for Routing Devices](#)

policy-oids

IN THIS SECTION

- [Syntax | 1630](#)
- [Hierarchy Level | 1630](#)
- [Description | 1630](#)
- [Options | 1630](#)
- [Required Privilege Level | 1631](#)
- [Release Information | 1631](#)

Syntax

```
policy-oids [ oid ];
```

Hierarchy Level

```
[edit services ipsec-vpn ike policy policy-name certificate]
```

Description

Configure policy object identifiers (OIDs). This configuration is optional.

Options

oid Policy OID contained in a peer's certificate or certificate chain. Up to five policy OIDs can be configured. Each OID can be up to 63 bytes long.

NOTE: You must ensure that at least one of the configured policy OIDs is included in a peer's certificate or certificate chain. Note that the **policy-oids** field in a peer's certificate is

optional. If you configure policy OIDs in an IKE policy and the peer's certificate chain does not contain any policy OIDs, certificate validation for the peer fails.

Required Privilege Level

view-level—To view this statement in the configuration.

control-level—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 16.1.

RELATED DOCUMENTATION

[Understanding Digital Certificate Validation | 300](#)

[Example: Improving Digital Certificate Validation by Configuring Policy OIDs on an MX Series Device | 307](#)

preference (Interface-Level Preference for VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax | 1632](#)
- [Hierarchy Level | 1632](#)
- [Description | 1632](#)
- [Options | 1632](#)
- [Required Privilege Level | 1632](#)
- [Release Information | 1632](#)

Syntax

```
preference preference-value;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-  
homing site site-name interface interface-name],  
[edit routing-instances instance-name protocols vpls multi-homing site site-name interface  
interface-name]
```

Description

Specify a preference for the interface to become the designated forwarder (DF) for a multihomed VPLS site. This preference statement can be useful when you want the interface preference for a site to change dynamically so that the DF election can be influenced depending on the interface state. Among the list of interface preferences, Junos OS advertises the best preference as the VPLS site's preference value. For example, if the site has three interfaces configured with preference values 12, 10, and 9, respectively, 12 is advertised as the site preference. If that interface goes down, 10 is advertised as the site preference.

If you configure interface-level preference, you cannot configure site-level preference.

Options

- | | |
|--------------------------------|---|
| <i>preference-value</i> | Preference value for the interface. |
| | <ul style="list-style-type: none"> • Range: 1 through 65535 |

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

| [Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

preference (Site-Level Preference for VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax | 1633](#)
- [Hierarchy Level | 1633](#)
- [Description | 1633](#)
- [Default | 1634](#)
- [Options | 1634](#)
- [Required Privilege Level | 1634](#)
- [Release Information | 1634](#)

Syntax

```
preference (preference-value | backup | primary);
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing site site-name],  
[edit routing-instances instance-name protocols vpls multi-homing site site-name]
```

Description

Influence the designated forwarder (DF) selection for a multihomed VPLS site. Configure the preference in terms of keywords `primary` and `backup`, or configure the preference value explicitly.

Default

If this statement is omitted, the default preference value for the site is 100.

Options

<i>preference-value</i>	Preference value for the DF. <ul style="list-style-type: none"> • Range: 1 through 65535
backup	Less likely to become the DF.
primary	Most likely to become the DF.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

| [Example: Configuring VPLS Multihoming \(FEC 129\)](#) | [971](#)

primary (VPLS Multihoming)

IN THIS SECTION

- [Syntax](#) | [1635](#)
- [Hierarchy Level](#) | [1635](#)
- [Description](#) | [1635](#)
- [Default](#) | [1635](#)

- Options | 1636
- Required Privilege Level | 1636
- Release Information | 1636

Syntax

```
primary interface-name;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing active-interface],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing site site-name active-interface],
[edit routing-instances instance-name protocols vpls multi-homing active-interface],
[edit routing-instances instance-name protocols vpls multi-homing site site-name active-interface]
```

Description

Specify the name of the multihomed interface to be used as the primary interface by the VPLS site.

For FEC 128, use the [edit routing-instances *instance-name* protocols vpls multi-homing active-interface] hierarchy level.

Default

If you omit this statement, depending on the order in which interfaces are listed in the PE router's configuration, the first operational interface in the set of configured interfaces is chosen to be the primary interface.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

interface-name—Name of the interface (for example, ge-0/1/0.1).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 7.5.

RELATED DOCUMENTATION

[Specifying an Interface as the Active Interface | 952](#)

[any \(VPLS Multihoming\) | 1436](#)

protect-interface

IN THIS SECTION

- [Syntax | 1636](#)
- [Hierarchy Level | 1637](#)
- [Description | 1637](#)
- [Options | 1637](#)
- [Required Privilege Level | 1637](#)
- [Release Information | 1637](#)

Syntax

```
protect-interface interface-name;
```

Hierarchy Level

```
[edit bridge-domains bridge-domain-name interface],
[edit logical-systems logical-systems--name bridge-domains bridge-domains interface],
[edit logical-systems logical-system-name protocols l2circuit neighbor address
interface interface-name],
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name],
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name end-interface],
[edit logical-systems logical-systems-name routing-instances name interface ],
[edit protocols l2circuit local-switching interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name],
[edit protocols l2circuit local-switching interface interface-name end-interface]
[edit routing-instances routing-instances-name interface ]
```

Description

Provide a backup for the protected interface in case of failure. Network traffic uses the primary interface only, as long as the primary interface functions.

Options

interface-name—Name of the protect interface to configure.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Support at the following hierarchy levels introduced in Junos OS Release 17.4: [edit bridge domains], [edit logical-systems], and [edit routing-instances].

RELATED DOCUMENTATION

[Configuring the Protect Interface | 365](#)

Configuring EVPN Active-Standby Multihoming to a Single PE Device

protected-l2circuit

IN THIS SECTION

- [Syntax | 1638](#)
- [Hierarchy Level | 1638](#)
- [Description | 1638](#)
- [Options | 1639](#)
- [Required Privilege Level | 1639](#)
- [Release Information | 1639](#)

Syntax

```
protected-l2circuit {  
    egress-pe address;  
    ingress-pe address;  
    virtual-circuit-id identifier;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name egress-protection],  
[edit protocols l2circuit neighbor address interface interface-name egress-protection]
```

Description

Configures the protected Layer 2 circuit as part of an egress protection virtual circuit (EPVC).

Options

egress-pe <i>address</i>	Specify the address of the egress PE router for the protected Layer 2 circuit.
ingress-pe <i>address</i>	Specify the address of the ingress PE router for the protected Layer 2 circuit.
virtual-circuit-id <i>identifier</i>	Specify the virtual circuit identifier for the protected Layer 2 circuit.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS release 10.4.

RELATED DOCUMENTATION

[Example: Configuring an Egress Protection LSP for a Layer 2 Circuit](#) | 438

protector-interface

IN THIS SECTION

- [Syntax](#) | 1640
- [Hierarchy Level](#) | 1640
- [Description](#) | 1640
- [Options](#) | 1640
- [Required Privilege Level](#) | 1640
- [Release Information](#) | 1640

Syntax

```
protector-interface interface-name;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name egress-protection],  
[edit protocols l2circuit neighbor address interface interface-name egress-protection]
```

Description

Configures the protector interface for an egress protection LSP.

Options

interface-name —Name of the interface used to protect traffic for an egress protection LSP.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS release 10.4.

RELATED DOCUMENTATION

| [Example: Configuring an Egress Protection LSP for a Layer 2 Circuit](#) | 438

protector-pe

IN THIS SECTION

- [Syntax | 1641](#)
- [Hierarchy Level | 1641](#)
- [Description | 1641](#)
- [Options | 1641](#)
- [Required Privilege Level | 1642](#)
- [Release Information | 1642](#)

Syntax

```
protector-pe address {
    context-identifier identifier;
    lsp lsp-name;
}
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name egress-protection],
[edit protocols l2circuit neighbor address interface interface-name egress-protection]
```

Description

Configures the protector PE router for an egress protection LSP. Test.

Options

address —IPv4 address for the protector PE router.

- context-identifier** *identifier* —Identifies the context for the egress protection LSP.
- lsp** *lsp-name* —Specifies the LSP for the egress protection LSP.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS release 10.4.

RELATED DOCUMENTATION

[Example: Configuring an Egress Protection LSP for a Layer 2 Circuit](#) | 438

proxy (Interfaces)

IN THIS SECTION

- [Syntax](#) | 1642
- [Hierarchy Level](#) | 1643
- [Description](#) | 1643
- [Options](#) | 1643
- [Required Privilege Level](#) | 1643
- [Release Information](#) | 1643

Syntax

```
proxy inet-address address;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number family tcc],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number  
family tcc]
```

Description

For Layer 2.5 VPNs using an Ethernet interface as the TCC router, configure the IP address for which the TCC router is proxying. Ethernet TCC is supported on interfaces that carry IPv4 traffic only. Ethernet TCC encapsulation is supported on 1-port Gigabit Ethernet, 2-port Gigabit Ethernet, 4-port Gigabit Ethernet, and 4-port Fast Ethernet PICs only. Ethernet TCC is not supported on the T640 routing node.

Options

`inet-address address`—IP address for which the TCC router is acting as a proxy.

Required Privilege Level

`interface`—To view this statement in the configuration.

`interface-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits](#) | 210

pseudowire-status-tlv

IN THIS SECTION

- Syntax | 1644
- Hierarchy Level | 1644
- Description | 1644
- Required Privilege Level | 1644
- Release Information | 1645

Syntax

```
pseudowire-status-tlv hot-standby-vc-on;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name],  
[edit protocols l2circuit neighbor address interface interface-name],
```

Description

Enables the pseudowire type length variable (TLV). The pseudowire status TLV is used to communicate the status of a pseudowire back and forth between two PE routers. The pseudowire status TLV is configurable for each pseudowire connection and is disabled by default.

The remaining statement is explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.0.

RELATED DOCUMENTATION

[Configuring the Pseudowire Status TLV | 366](#)

[Example: Configuring Pseudowire Redundancy in a Mobile Backhaul Scenario | 391](#)

psn-tunnel-endpoint

IN THIS SECTION

- [Syntax | 1645](#)
- [Hierarchy Level | 1645](#)
- [Description | 1646](#)
- [Options | 1646](#)
- [Required Privilege Level | 1646](#)
- [Release Information | 1646](#)

Syntax

```
psn-tunnel-endpoint address;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit neighbor address
interface interface-name],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name backup-neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address backup-neighbor address],
```



```
[edit protocols l2circuit neighbor address interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor address],
[edit routing-instances routing-instance-name protocols vpls neighbor address backup-neighbor
address]
```

Description

Specify the endpoint of the packet switched network (PSN) tunnel on the remote PE router.

Options

address—Address for the tunnel endpoint.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Hierarchy levels associated with the `backup-neighbor` statement added in Junos OS Release 9.2.

RELATED DOCUMENTATION

[Configuring Layer 2 Circuits over Both RSVP and LDP LSPs | 367](#)

[Configuring Pseudowire Redundancy on the PE Router | 226](#)

qualified-bum-pruning-mode

IN THIS SECTION

- [Syntax | 1647](#)
- [Hierarchy Level | 1647](#)

- [Description | 1647](#)
- [Required Privilege Level | 1647](#)
- [Release Information | 1647](#)

Syntax

```
qualified-bum-pruning-mode;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],  
[edit routing-instances routing-instance-name]
```

Description

For Junos OS Layer 2 Wholesale configurations, prune (constrain) distribution of broadcast, unicast, and multicast (BUM) packets of unknown origin to only those interfaces that match the traffic from a specific VLAN pair.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.4.

RELATED DOCUMENTATION

[Configuring Separate NNI Routing Instances for Layer 2 Wholesale Service Retailers](#)

[Layer 2 and Layer 3 Wholesale Overview](#)

Support of Inner VLAN List and Inner VLAN Range for Qualified BUM Pruning on a Dual-Tagged Interface for a VPLS Routing Instance Overview | 693

remote

IN THIS SECTION

- [Syntax | 1648](#)
- [Hierarchy Level | 1648](#)
- [Description | 1648](#)
- [Options | 1649](#)
- [Required Privilege Level | 1649](#)
- [Release Information | 1649](#)

Syntax

```
remote (inet-address | mac-address) address;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number family tcc],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number  
family tcc]
```

Description

For Layer 2.5 VPNs employing an Ethernet interface as the TCC router, configure the location of the remote router. Ethernet TCC is supported on interfaces that carry IPv4 traffic only. Ethernet TCC encapsulation is supported on 1-port Gigabit Ethernet, 2-port Gigabit Ethernet, 4-port Gigabit Ethernet, and 4-port Fast Ethernet PICs only.

Options

`inet-address`*address*—The IP address of the remote site.

`mac-address` *address*—The MAC address of the remote site.

Required Privilege Level

`interface`—To view this statement in the configuration.

`interface-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring TCC Encapsulation for Layer 2 VPNs and Layer 2 Circuits](#) | 210

remote-site-id

IN THIS SECTION

- [Syntax](#) | 1650
- [Hierarchy Level](#) | 1650
- [Description](#) | 1650
- [Options](#) | 1650
- [Required Privilege Level](#) | 1650
- [Release Information](#) | 1650

Syntax

```
remote-site-id remote-site-ID;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn site site-name interface interface-name],  
[edit routing-instances routing-instance-name protocols l2vpn site site-name interface interface-  
name]
```

Description

Control the remote interface to which the interface should connect. If you do not explicitly configure the remote site ID, the order of the interfaces configured for the site determines the default value. This statement is optional.

Options

remote-site-ID—Identifier specifying the interface on the remote PE router the Layer 2 VPN routing instance connects to.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring the Remote Site ID | 151](#)

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

routing-instances

IN THIS SECTION

- [Syntax | 1651](#)
- [Hierarchy Level | 1651](#)
- [Description | 1651](#)
- [Default | 1651](#)
- [Options | 1652](#)
- [Required Privilege Level | 1652](#)
- [Release Information | 1652](#)

Syntax

```
routing-instances routing-instance-name { ... }
```

Hierarchy Level

```
[edit],  
[edit logical-systems logical-system-name]
```

Description

Configure an additional routing entity for a router or switch. You can create multiple instances of BGP, IS-IS, OSPF, OSPF version 3 (OSPFv3), and RIP for a router or switch.

Default

Routing instances are disabled for the router or switch.

Options

routing-instance-name—Name of the routing instance, a maximum of 31 characters. The remaining statements are explained separately.

non-forwarding-vrf—Enable this option to not create a routing and forwarding (VRF) table for local or transit routes belonging to the given VPN.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring Routing Instances on PE Routers in VPNs

rsvp-te (Routing Instances Provider Tunnel)

IN THIS SECTION

- [Syntax | 1652](#)
- [Hierarchy Level | 1653](#)
- [Release Information | 1653](#)

Syntax

```
rsvp-te {
  label-switched-path-template {
```

```

        (default-template | lsp-template-name);
    }
    static-lsp lsp-name;
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name routing-instances routing-instance-name provider-
tunnel],
[edit routing-instances routing-instance-name provider-tunnel]
[edit routing-instances instance-name provider-tunnel]

```

Release Information

Statement introduced in Junos OS Release 8.3.

Options

`static-lsp lsp-name`—Create a static point-to-multipoint LSP and automatically include all of the neighbors in the VPLS routing instance.

The remaining option is explained separately.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

RELATED DOCUMENTATION

| [Flooding Unknown Traffic Using Point-to-Multipoint LSPs in VPLS](#) | 1073

send-oam

IN THIS SECTION

- [Syntax | 1654](#)
- [Hierarchy Level | 1654](#)
- [Description | 1654](#)
- [Required Privilege Level | 1654](#)
- [Release Information | 1654](#)

Syntax

```
send-oam;
```

Hierarchy Level

```
[edit protocols l2circuit neighbor address interface interface-name static]
```

Description

Enable the ability to ping a static pseudowire. If you configure the `send-oam` statement, it applies to the backup neighbor as well. Once you have configured this statement, you can ping the static pseudowire by issuing the `ping mpls l2circuit` command.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.5.

RELATED DOCUMENTATION

[Configuring Static Layer 2 Circuits | 356](#)

ping mpls l2circuit

service-groups

IN THIS SECTION

- [Syntax | 1655](#)
- [Hierarchy Level | 1655](#)
- [Description | 1656](#)
- [Options | 1656](#)
- [Required Privilege Level | 1656](#)
- [Release Information | 1656](#)

Syntax

```
service-groups {
  service-group-name {
    pbb-service-options {
      default-isid isid-number;
      isid isid-number vlan-id-list [ vlan-ids ];
      mac-address mac-address;
    }
    service-type (elan | eline);
    source-bmac <mac-address> <length>
  }
}
```

Hierarchy Level

```
[edit routing-instances (Multiple Routing Entities) routing-instance-name]
```

Description

For IEEE 802.1ah provider backbone bridge (PBB) configurations, configure the service groups to be supported in the customer routing instance (I-component).

NOTE: The `mac-address` statement under `pbb-service-options` is not supported for PBB-EVPN.

NOTE: The `eline` option for the `service-type` statement is not supported for PBB-EVPN.

The remaining statements are explained separately. See [CLI Explorer](#).

Options

service-group-name—Name of a service group.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in JUNOS Release 10.0.

service-type

IN THIS SECTION

- [Syntax | 1657](#)
- [Hierarchy Level | 1657](#)
- [Description | 1657](#)
- [Options | 1657](#)
- [Required Privilege Level | 1657](#)

Syntax

```
service-type (elan | eline);
```

Hierarchy Level

```
[edit routing-instances (Multiple Routing Entities) routing-instance-name service-groups]
```

Description

For IEEE 802.1ah provider backbone bridge (PBB) configurations, configure the service type for the service group in the customer routing instance (I-component).

Options

elan—Connects a set of customer endpoints (like a bridged Ethernet network). E-LAN service is also known as point-to-multipoint service.

eline—Connects two customer Ethernet ports over a WAN. E-LINE service is also known as point-to-point service.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in JUNOS Release 10.0.

site (Layer 2 Circuits)

IN THIS SECTION

- [Syntax | 1658](#)
- [Hierarchy Level | 1658](#)
- [Description | 1659](#)
- [Options | 1659](#)
- [Required Privilege Level | 1659](#)
- [Release Information | 1659](#)

Syntax

```
site site-name {  
    hot-standby;  
    site-identifier identifier;  
    site-preference preference-value {  
        backup;  
        primary;  
    }  
    interface interface-name {  
        description text;  
        remote-site-id remote-site-ID;  
    }  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn],  
[edit routing-instances routing-instance-name protocols l2vpn]
```

Description

Specify the site name, site identifier, and interfaces connecting to the site. Allows you to configure a remote site ID for remote sites.

Options

`hot-standby`—Turn on the protector behavior for the site. This keeps backup pseudowire in continuous standby mode and ready for traffic forwarding.

`site-identifier` *identifier*—Numerical identifier for the site used as a default reference for the remote site ID.

`site-name`—Name of the site.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

`hot-standby` option introduced in Junos OS Release 14.2 for MX Series routers.

RELATED DOCUMENTATION

[Configuring the Site | 150](#)

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

site (VPLS Multihoming for FEC 128)

IN THIS SECTION

- [Syntax | 1660](#)
- [Hierarchy Level | 1660](#)
- [Description | 1661](#)
- [Options | 1661](#)
- [Required Privilege Level | 1661](#)
- [Release Information | 1661](#)

Syntax

```
site site-name {  
    mac-pinning;  
    active-interface (any | primary interface-name);  
    best-site;  
    interface interface-name {  
        interface-mac-limit limit;  
    }  
    mesh-group mesh-group-name;  
    multi-homing;  
    site-identifier identifier;  
    site-preference preference-value;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Specify the site name and site identifier for a site. Allows you to configure a remote site ID for remote sites.

Options

site-name—Name of the site.

The remaining statements are explained separately. Search for a statement in [CLI Explorer](#) or click a linked statement in the Syntax section for details.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

site (VPLS Multihoming for FEC 129)

IN THIS SECTION

- [Syntax | 1662](#)
- [Hierarchy Level | 1662](#)
- [Description | 1662](#)
- [Options | 1662](#)
- [Required Privilege Level | 1663](#)
- [Release Information | 1663](#)

Syntax

```

site site-name {
    active-interface interface-name {
        any;
        primary interface-name;
    }
    identifier identifier;
    interface interface-name {
        preference preference-value;
    }
    peer-active;
    preference (preference-value | backup | primary);
}

```

Hierarchy Level

```

[edit logical-systems logical-system-name routing-instances instance-name protocols vpls multi-homing],
[edit routing-instances instance-name protocols vpls multi-homing]

```

Description

For VPLS autodiscovery (FEC 129), specify the parameters for a VPLS site that is multihomed to two or more provider edge (PE) routers.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

site-name—Name of the site.

The remaining statements are explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[Example: Configuring VPLS Multihoming \(FEC 129\) | 971](#)

site-identifier (Layer 2 Circuits)

IN THIS SECTION

- [Syntax | 1663](#)
- [Hierarchy Level | 1664](#)
- [Description | 1664](#)
- [Options | 1664](#)
- [Required Privilege Level | 1664](#)
- [Release Information | 1664](#)

Syntax

```
site-identifier identifier;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn site site-name],
[edit routing-instances routing-instance-name protocols l2vpn site site-name]
```

Description

Specify the numerical identifier for the local Layer 2 VPN site.

Options

identifier—The numerical identifier for the Layer 2 VPN site, which can be any number from 1 through 65,534.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring the Site | 150](#)

[Configuring an MPLS-Based Layer 2 VPN \(CLI Procedure\)](#)

site-identifier (VPLS)

IN THIS SECTION

● [Syntax | 1665](#)

- Hierarchy Level | 1665
- Description | 1665
- Options | 1665
- Required Privilege Level | 1665
- Release Information | 1665

Syntax

```
site-identifier identifier;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
site site-name],  
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Specify the numerical identifier for the local VPLS site.

Options

identifier—Specify the numerical identifier for the local VPLS site. The identifier must be an unsigned 16-bit number greater than zero.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring the VPLS Site Name and Site Identifier](#) | 677

site-preference

IN THIS SECTION

- [Syntax](#) | 1666
- [Hierarchy Level](#) | 1666
- [Description](#) | 1667
- [Options](#) | 1667
- [Required Privilege Level](#) | 1667
- [Release Information](#) | 1667

Syntax

```
site-preference preference-value {  
    backup;  
    primary;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
l2vpn site site-name],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
site site-name],  
[edit routing-instances routing-instance-name protocols l2vpn site site-name],  
[edit routing-instances routing-instance-name protocols vpls site site-name]
```

Description

Specify the preference value advertised for a particular Layer 2 VPN or VPLS site. The site preference value is encoded in the BGP local preference attribute. When a PE router receives multiple advertisements with the same VE identifier, the advertisement with the highest local preference value is preferred. You can use this statement to enable multihoming for Layer 2 VPNs and VPLS.

Options

preference-value—Specify the preference value advertised for a Layer 2 VPN or VPLS site.

- **Range:** 1 through 65,535

backup—Set the preference value to 1.

primary—Set the preference value to 65,535.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Statement introduced for Layer 2 VPNs in Junos OS Release 9.1.

RELATED DOCUMENTATION

[Configuring a Site Preference and Layer 2 VPN Multihoming](#) | 154

[Configuring the VPLS Site Preference](#) | 682

site-range

IN THIS SECTION

- [Syntax | 1668](#)
- [Hierarchy Level | 1668](#)
- [Description | 1668](#)
- [Options | 1668](#)
- [Required Privilege Level | 1669](#)
- [Release Information | 1669](#)

Syntax

```
site-range number;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Specify an upper limit on the maximum site identifier that can be accepted to allow a pseudowire to be brought up. Pseudowires cannot be established to sites with site identifiers greater than the configured site range. If you issue the `show vpls connections` command, such sites are displayed as OR (out of range).

Options

number Maximum number of site identifiers. We recommend using the default value.

- **Range:** 1 through 65,534
- **Default:** 65,534

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Configuring the Site Range](#) | [679](#)

source-attachment-identifier (Protocols VPWS)

IN THIS SECTION

- [Syntax](#) | [1669](#)
- [Hierarchy Level](#) | [1670](#)
- [Description](#) | [1670](#)
- [Options](#) | [1670](#)
- [Required Privilege Level](#) | [1670](#)
- [Release Information](#) | [1670](#)

Syntax

```
source-attachment-identifier identifier;
```


Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn site site-name],
[edit routing-instances routing-instance-name protocols l2vpn site site-name]
```

Description

For FEC 129, specify the VPWS source attachment identifier. The point-to-point nature of VPWS requires that you specify the source access individual identifier (SAII) and the target access individual identifier (TAII). This SAII-TAII pair defines a unique pseudowire between two PE devices.

Auto-discovery routes are used by BGP to allow auto-discovery of remote source access individual identifiers (SAIIs) (the sources of the point-to-point pseudowires). One auto-discovery route is advertised for each source attachment identifier (SAI) in the instance or mesh group.

The SAII is specified with the `source-attachment-identifier` statement within the FEC 129 VPWS routing instance. You configure the source attachment identifier and the interfaces to associate with that source attachment identifier. Under each interface, you can configure the TAII with the `target-attachment-identifier` statement. If the configured target identifier matches a source identifier advertised by a remote PE device by way of a BGP auto-discovery message, the pseudowire between that source-target pair is signaled. If there is no match between an advertised source identifier and the configured target identifier, the pseudowire is not established.

Options

identifier—The numerical identifier for the Layer 2 VPN site.

- **Range:** 1 through 4,292,967,295

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.2.

RELATED DOCUMENTATION

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS | 885](#)

[target-attachment-identifier \(Protocols VPWS\) | 1680](#)

source-bmac

IN THIS SECTION

- [Syntax | 1671](#)
- [Hierarchy Level | 1671](#)
- [Description | 1671](#)
- [Options | 1672](#)
- [Required Privilege Level | 1672](#)
- [Release Information | 1672](#)

Syntax

```
source-bmac <mac-address> <length> [auto];
```

Hierarchy Level

```
[edit interfaces interface-name unit unit esi],
[edit routing-instances routing-instance-name pbb-options],
[edit routing-instances routing-instance-name pbb-options service-groups service-group-name],
[edit routing-instances routing-instance-name pbb-options service-groups service-group-name isid
isid-name]
```

Description

Set a shared source Provider Backbone Bridging (PBB) MAC (B-MAC) address for all service identifiers (ISIDs) under a specified routing instance. If a source B-MAC address is derived automatically from the aggregated Ethernet system ID, you must specify the `auto` keyword.

For PBB-Ethernet VPN (EVPN) functionality, one service group (a group of ISIDs) can correspond to a single-homed, single-Active, or Active-Active scenario. You cannot mix and match service groups. For a shared B-MAC model, you configure one source B-MAC per service group using the routing-instances *routing-instance-name* pbb-options service-groups *service-group-name* hierarchy.

To specify a source B-MAC per ISID, use the routing-instances *routing-instance-name* pbb-options service-groups *service-group-name* isid *isid-name* hierarchy. If you do not specify the source B-MAC per ISID, then the B-MAC inherits from the B-MAC configuration located under the pbb-options setting.

The support of the source-bmac statement at the [edit interfaces *interface-name* unit *unit* esi] hierarchy level allows configuring of the Ethernet Segment Identifier (ESI) and source B-MAC address per logical interface, in addition to the existing support for physical devices.

Options

Length Length of the B-MAC address.

- **Default:** 48B

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 16.1.

Support at the [edit interfaces *interface-name* unit *unit* esi] hierarchy level introduced in Junos OS Release 18.1R1.

RELATED DOCUMENTATION

| *routing-instances (Multiple Routing Entities)*

standby (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1673](#)
- [Hierarchy Level | 1673](#)
- [Description | 1673](#)
- [Required Privilege Level | 1674](#)
- [Release Information | 1674](#)

Syntax

```
standby;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface  
interface-name end-interface interface interface-name backup-neighbor address],  
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface  
interface-name backup-neighbor address],  
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls  
neighbor address backup-neighbor address],  
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor address],  
[edit routing-instances routing-instance-name protocols vpls neighbor address backup-neighbor  
address]
```

Description

Configure the pseudowire to the specified backup neighbor as the standby. When you configure this statement, traffic flows over both the active and standby pseudowires to the backup device (either a CE device or PE router). The backup device drops the traffic from the standby pseudowire, unless the active pseudowire fails. If the active pseudowire fails, the backup device automatically switches to the standby pseudowire.

The standby statement is quite similar to the [hot-standby](#) statement introduced in Junos OS Release 12.3. The hot-standby statement allows for a faster forwarding-path switchover during transition periods, as compared to what is allowed by the standby statement.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Hierarchy levels associated with the backup-neighbor statement added in Junos OS Release 9.2.

RELATED DOCUMENTATION

[Configuring Layer 2 Circuits over Both RSVP and LDP LSPs | 367](#)

[Configuring Pseudowire Redundancy on the PE Router | 226](#)

[Example: Configuring Layer 2 Circuit Switching Protection | 461](#)

static (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1675](#)
- [Hierarchy Level | 1675](#)
- [Description | 1675](#)
- [Options | 1675](#)
- [Required Privilege Level | 1675](#)
- [Release Information | 1676](#)

Syntax

```
static {
    incoming-label label;
    outgoing-label label;
    send-oam;
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name l2circuit neighbor address interface interface-name],
[edit logical-systems logical-system-name l2circuit neighbor address interface interface-name
backup-neighbor neighbor],
[edit protocols l2circuit neighbor address interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor neighbor]
```

Description

Configures static Layer 2 circuit pseudowires. Static pseudowires are designed for networks that do not support LDP or do not have LDP enabled. You configure a static pseudowire by configuring static values for the in and out labels needed to enable a pseudowire connection.

Options

incoming-label (Optional for PTX Series Packet Transport Routers only) Configure the Layer 2 circuit incoming static pseudowire label.

- **Range:** 1000000 through 1048575

outgoing-label (Optional for PTX Series Packet Transport Routers only) Configure the Layer 2 circuit outgoing static pseudowire label.

- **Range:** 16 through 1048575

The remaining statement is explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 9.5.

RELATED DOCUMENTATION

| [Configuring Static Layer 2 Circuits](#) | 356

static (Protocols VPLS)

IN THIS SECTION

- [Syntax](#) | 1676
- [Hierarchy Level](#) | 1677
- [Description](#) | 1677
- [Options](#) | 1677
- [Required Privilege Level](#) | 1677
- [Release Information](#) | 1678

Syntax

```
static {  
    incoming-label label;  
    outgoing-label label;  
    control-word;  
    no-control-word;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
mesh-group mesh-group-name neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address],
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols vpls
neighbor address backup-neighbor address],
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor
address],
[edit routing-instances routing-instance-name protocols vpls neighbor address],
[edit routing-instances routing-instance-name protocols vpls neighbor address backup-neighbor
address]
```

Description

Specifies a static pseudowire for a VPLS domain. By configuring static pseudowires for the VPLS domain, you do not need to configure the LDP or BGP protocols that would normally be used for signaling. Static pseudowires require that you configure a set of in and out labels for each pseudowire configured for the VPLS domain. You can configure both static and dynamic neighbors within the same VPLS routing instance. You can also configure a static pseudowire for a backup neighbor (if you configure the neighbor as static the backup must also be static) and for a mesh group.

Options

`incoming-label label`—You must configure an incoming label for the static pseudowire.

- **Range:** 29,696 through 41,983 and 1,000,000 through 1,048,575

`outgoing-label label`—You must configure an outgoing label for the static pseudowire.

- **Range:** 16 through 1,048,575

`control-word`—Set `control-word` to request that other routers insert a control word between the label stack and the MPLS payload.

`no-control-word`—Set `no-control-word` to request that other routers not insert a control word between the label stack and the MPLS payload. This is the default setting for BGP VPLS.

Required Privilege Level

`routing`—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 10.2.

Options control-word and no-control-word are introduced in Junos OS Release 20.3R1.

NOTE: Options control-word and no-control-word are not introduced at the [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols vpls neighbor *address* backup-neighbor *address*] and [edit routing-instances *routing-instance-name* protocols vpls neighbor *address* backup-neighbor *address*] hierarchy level.

RELATED DOCUMENTATION

[Configuring Static Pseudowires for VPLS | 751](#)

[control-word | 1458](#)

[no-control-word | 1594](#)

static-mac

IN THIS SECTION

- [Syntax | 1679](#)
- [Hierarchy Level | 1679](#)
- [Description | 1679](#)
- [Options | 1679](#)
- [Required Privilege Level | 1680](#)
- [Release Information | 1680](#)

Syntax

```
static-mac mac-address;
```

```
static-mac mac-address {  
    vlan-id number;  
}
```

Hierarchy Level

```
[edit vlans vlan-name switch-options interface interface-name]
```

```
[edit bridge-domains bridge-domain-name bridge-options interface interface-name],
```

```
[edit logical-systems logical-system-name bridge-domains bridge-domain-name bridge-options  
interface interface-name],  
[edit logical-systems logical-system-name routing-instances routing-instance-name bridge-domains  
bridge-domain-name bridge-options interface interface-name],
```

```
[edit routing-instances routing-instance-name bridge-domains bridge-domain-name bridge-options  
interface interface-name],  
[edit routing-instances routing-instance-name protocols evpn interface interface-name]
```

Description

Configure a static MAC address for a logical interface in a bridge domain or VLAN.

The *vlan-id* option can be specified for static-macs only if *vlan-id all* is configured for the bridging domain or VLAN.

Options

mac-address—MAC address

`vlan-id number`—(Optional) VLAN identifier to associate with static MAC address.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

Statement modified in Junos OS Release 9.5.

Support for logical systems added in Junos OS Release 9.6.

[`edit vlans vlan-name switch-options interface interface name`] hierarchy level introduced in Junos OS Release 12.3R2 for EX Series switches.

Support for EVPNs added in Junos OS Release 13.2 for MX 3D Series routers. The `vlan-id` option is not available for EVPNs.

[`edit vlans vlan-name switch-options interface interface name`] hierarchy level introduced in Junos OS Release 13.2 for the QFX Series.

RELATED DOCUMENTATION

[*Configuring EVPN Routing Instances*](#)

[Understanding Layer 2 Learning and Forwarding for Bridge Domains](#)

[Layer 2 Learning and Forwarding for VLANs Overview](#)

[Adding a Static MAC Address Entry to the Ethernet Switching Table on a Switch with ELS Support](#)

target-attachment-identifier (Protocols VPWS)

IN THIS SECTION

● [Syntax | 1681](#)

● [Hierarchy Level | 1681](#)

- [Description | 1681](#)
- [Options | 1681](#)
- [Required Privilege Level | 1682](#)
- [Release Information | 1682](#)

Syntax

```
target-attachment-identifier identifier;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols l2vpn site
site-name interface interface-name],
[edit routing-instances instance-name protocols l2vpn site site-name interface interface-name]
```

Description

For FEC 129, specify the VPWS target attachment identifier. The point-to-point nature of VPWS requires that you specify the source access individual identifier (SAII) and the target access individual identifier (TAII). This SAII-TAII pair defines a unique pseudowire between two PE devices.

Auto-discovery routes are used by BGP to allow auto-discovery of SAIIs (the sources of the point-to-point pseudowires). One auto-discovery route is advertised for each source attachment identifier (SAI) in the instance or mesh group.

The SAII is specified with the `source-attachment-identifier` statement within the FEC 129 VPWS routing instance. You configure the source attachment identifier and the interfaces to associate with that source attachment identifier. Under each interface, you can configure the TAII with the `target-attachment-identifier` statement. If the configured target identifier matches a source identifier advertised by a remote PE device by way of a BGP auto-discovery message, the pseudowire between that source-target pair is signaled. If there is no match between an advertised source identifier and the configured target identifier, the pseudowire is not established.

Options

identifier—The numerical identifier for the Layer 2 VPN site.

- **Range:** 1 through 4,292,967,295

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.2.

RELATED DOCUMENTATION

[Example: Configuring FEC 129 BGP Autodiscovery for VPWS](#) | 885

[source-attachment-identifier \(Protocols VPWS\)](#) | 1669

template

IN THIS SECTION

- [Syntax](#) | 1682
- [Hierarchy Level](#) | 1683
- [Description](#) | 1683
- [Required Privilege Level](#) | 1683
- [Release Information](#) | 1683

Syntax

```
template;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols mpls label-switched-path p2mp-lsp-template-name],  
[edit protocols mpls label-switched-path p2mp-lsp-template-name]
```

Description

Specify a template for the dynamically generated point-to-multipoint LSPs used for VPLS flooding.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.3.

RELATED DOCUMENTATION

| [Configuring Dynamic Point-to-Multipoint Flooding LSPs with a Preconfigured Template](#) | 1077

traceoptions (Egress Protection)

IN THIS SECTION

- [Syntax](#) | 1684
- [Hierarchy Level](#) | 1684
- [Description](#) | 1684
- [Options](#) | 1684
- [Required Privilege Level](#) | 1685
- [Release Information](#) | 1685

Syntax

```
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag;
}
```

Hierarchy Level

```
[edit protocols mpls egress-protection],
```

Description

Configure tracing operations for egress protection.

Options

- | | |
|--------------------------------|--|
| <i>filename</i> | Name of the file to receive the output of the tracing operation. |
| <i>files
number</i> | <p>(Optional) Maximum number of trace files. If you specify a maximum number of files, you must also include the size statement to specify the maximum file size. When a trace file named <i>trace-file</i> reaches its maximum size, it is renamed <i>trace-file.0</i>, then <i>trace-file.1</i>, and so on, until the maximum number of trace files is reached. Then the oldest trace file is overwritten.</p> <ul style="list-style-type: none"> • Range: 2 through 1000 • Default: 2 files |
| <i>flag</i> | <p>Tracing operation to perform. To specify more than one tracing operation, include multiple flag statements.</p> <ul style="list-style-type: none"> • all—Trace all operations • error—Trace error conditions • route—Trace route transitions • state—Trace state transitions |

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 11.4R3.

RELATED DOCUMENTATION

[Example: Configuring MPLS Egress Protection for Layer 3 VPN Services](#)

traceoptions (Protocols Layer 2 Circuit)

IN THIS SECTION

- [Syntax | 1685](#)
- [Hierarchy Level | 1686](#)
- [Description | 1686](#)
- [Options | 1686](#)
- [Required Privilege Level | 1687](#)
- [Release Information | 1687](#)

Syntax

```
traceoptions {  
  file filename <files number> <size size> <world-readable | no-world-readable>;  
  flag flag <flag-modifier> <disable>;  
}
```


Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit],
[edit protocols l2circuit]
```

Description

Trace traffic flowing through a Layer 2 circuit.

Options

disable—(Optional) Disable the tracing operation. You can use this option to disable a single operation when you have defined a broad group of tracing operations, such as `all`.

file *filename*—Name of the file to receive the output of the tracing operation. Enclose the name in quotation marks (" ").

files *number*—(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed *trace-file.0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the `size` option.

- **Range:** 2 through 1000 files
- **Default:** 2 files

flag *flag*—Tracing operation to perform. To specify more than one tracing operation, include multiple `flag` statements.

- `connections`—Layer 2 circuit connections (events and state changes)
- `error`—Error conditions
- `fec`—Layer 2 circuit advertisements received or sent by means of LDP
- `topology`—Layer 2 circuit topology changes caused by reconfiguration or advertisements received from other PE routers

flag-modifier—(Optional) Modifier for the tracing flag. You can specify the `detail` modifier if you want to provide detailed trace information.

no-world-readable—(Optional) Do not allow any user to read the log file.

`size size`—(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file.0*. When the *trace-file* again reaches its maximum size, *trace-file.0* is renamed *trace-file.1* and *trace-file* is renamed *trace-file.0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the `files` option.

- **Syntax:** `yk` to specify kilobytes, `ym` to specify megabytes, or `yg` to specify gigabytes
- **Range:** 10 KB through the maximum file size supported on your system
- **Default:** 1 MB

`world-readable`—(Optional) Allow any user to read the log file.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Tracing Layer 2 Circuit Operations](#) | 496

traceoptions (Protocols Layer 2 VPN)

IN THIS SECTION

- [Syntax](#) | 1688
- [Hierarchy Level](#) | 1688
- [Description](#) | 1688

- Options | 1688
- Required Privilege Level | 1690
- Release Information | 1690

Syntax

```
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
l2vpn],
[edit routing-instances routing-instance-name protocols l2vpn]
```

Description

Trace traffic flowing through a Layer 2 VPN.

Options

disable—(Optional) Disable the tracing operation. You can use this option to disable a single operation when you have defined a broad group of tracing operations, such as `all`.

file *filename*—Name of the file to receive the output of the tracing operation. Enclose the name in quotation marks (" ").

files *number*—(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed *trace-file.0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the `size` option.

- **Range:** 2 through 1000 files

- **Default:** 2 files

flag flag—Tracing operation to perform. To specify more than one tracing operation, include multiple *flag* statements.

- *all*—All Layer 2 VPN tracing options
- *connections*—Layer 2 connections (events and state changes)
- *error*—Error conditions
- *general*—General events
- *nlri*—Layer 2 advertisements received or sent by means of the BGP
- *normal*—Normal events
- *policy*—Policy processing
- *route*—Routing information
- *state*—State transitions
- *task*—Routing protocol task processing
- *timer*—Routing protocol timer processing
- *topology*—Layer 2 VPN topology changes caused by reconfiguration or advertisements received from other PE routers using BGP

flag-modifier—(Optional) Modifier for the tracing flag. You can specify the following modifier:

- *detail*—Provide detailed trace information
- *receive*—Trace received packets
- *send*—Trace transmitted packets

no-world-readable—(Optional) Prevents any user from reading the trace file.

size size—(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file.0*. When *trace-file* again reaches its maximum size, *trace-file.0* is renamed *trace-file.1* and *trace-file* is renamed *trace-file.0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the *files* option.

- **Syntax:** *k* to specify kilobytes, *m* to specify megabytes, or *g* to specify gigabytes

- **Range:** 10 KB through the maximum file size supported on your system
- **Default:** 1 MB

world-readable—(Optional) Allow any user to read the trace file.

- **Default:** The default is no-world-readable.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Tracing Layer 2 VPN Traffic and Operations](#) | 155

traceoptions (Protocols VPLS)

IN THIS SECTION

- [Syntax](#) | 1691
- [Hierarchy Level](#) | 1691
- [Description](#) | 1691
- [Options](#) | 1691
- [Required Privilege Level](#) | 1692
- [Release Information](#) | 1693

Syntax

```
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols
vpls],
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Trace traffic flowing through a VPLS routing instance.

Options

disable—(Optional) Disable the tracing operation. You can use this option to disable a single operation when you have defined a broad group of tracing operations, such as `all`.

file *filename*—Name of the file to receive the output of the tracing operation. Enclose the name in quotation marks (" ").

files *number*—(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches this size, it is renamed *trace-file.0*. When *trace-file* again reaches its maximum size, *trace-file.0* is renamed *trace-file.1* and *trace-file* is renamed *trace-file.0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the `size` option.

- **Range:** 2 through 1000 files
- **Default:** 2 files

flag *flag*—Tracing operation to perform. To specify more than one tracing operation, include multiple `flag` statements. You can specify the following tracing flags:

- **all**—All VPLS tracing options

- `connections`—VPLS connections (events and state changes)
- `error`—Error conditions
- `nlri`—VPLS advertisements received or sent by means of the BGP
- `route`—Routing information
- `topology`—VPLS topology changes caused by reconfiguration or advertisements received from other provider edge (PE) routers using BGP

flag-modifier—(Optional) Modifier for the tracing flag. You can specify the following modifiers:

- `detail`—Provide detailed trace information.
- `disable`—Disable the tracing flag.
- `receive`—Trace received packets.
- `send`—Trace sent packets.

`no-world-readable`—Do not allow any user to read the log file.

`size size`—(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file.0*. When *trace-file* again reaches its maximum size, *trace-file.0* is renamed *trace-file.1* and *trace-file* is renamed *trace-file.0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the `files` option.

- **Syntax:** *kk* to specify kilobytes, *mm* to specify megabytes, or *gg* to specify gigabytes
- **Range:** 10 KB through the maximum file size supported on your system
- **Default:** 1 MB

`world-readable`—Allow any user to read the log file.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Tracing VPLS Traffic and Operations](#) | [1261](#)

transmit-interval (BFD Liveness Detection)

IN THIS SECTION

- [Syntax](#) | [1693](#)
- [BGP](#) | [1693](#)
- [EVPN, L2VPN, VPLS](#) | [1694](#)
- [Description](#) | [1695](#)
- [Options](#) | [1695](#)
- [Required Privilege Level](#) | [1696](#)
- [Release Information](#) | [1696](#)

Syntax

```
transmit-interval {
    minimum-interval milliseconds;
    threshold milliseconds;
}
```

BGP

```
[edit logical-systems name protocols                bgp                bfd-liveness-detection],
[edit logical-systems name protocols                bgpgroup          bfd-liveness-detection],
[edit logical-systems name protocols                bgp group name    neighbor address bfd-liveness-
```



```

detection],
[edit logical-systems name routing-instances name
protocols bgp bfd-liveness-detection],
[edit logical-systems name routing-instances name
protocols bgpgroup bfd-liveness-detection],
[edit logical-systems name routing-instances name
protocols bgpgroup neighbor address bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols
bgp bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols
bgpgroup bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols
bgpgroup neighbor address bfd-liveness-detection],
[edit protocols bgp bfd-liveness-detection],
[edit protocols bgp group bfd-liveness-detection],
[edit protocols bgp group neighbor address bfd-liveness-detection],
[edit routing-instances name protocols bgp bfd-liveness-detection],
[edit routing-instances name protocols bgp group bfd-liveness-detection],
[edit routing-instances name protocols bgp group neighbor address bfd-liveness-
detection],
[edit tenants name routing-instances name protocols bgp bfd-liveness-detection]
[edit tenants name routing-instances name protocols bgp group bfd-liveness-detection]
[edit tenants name routing-instances name protocols bgp group neighbor address bfd-liveness-detection]

```

EVPN, L2VPN, VPLS

```

[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-

```

```

detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls)mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)
oam          bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam          bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],

```

Description

Specify the transmit interval for the `bfd-liveness-detection` statement. The negotiated transmit interval for a peer is the interval between the sending of BFD packets to peers. The receive interval for a peer is the minimum time that it requires between packets sent from its peer; the receive interval is not negotiated between peers. To determine the transmit interval, each peer compares its configured minimum transmit interval with its peer's minimum receive interval. The larger of the two numbers is accepted as the transmit interval for that peer.

Options

minimum-interval *milliseconds*

Configure the minimum interval at which the local routing device transmits hello packets to a neighbor with which it has established a BFD session. Optionally, instead of using this statement at this hierarchy level, you can configure the minimum transmit interval using the `minimum-interval` statement at the `bfd-liveness-detection` hierarchy level.

NOTE: The threshold value specified in the `threshold` statement must be greater than the value specified in the `minimum-interval` statement for the `transmit-interval` statement.

- **Range:** 1 through 255,000 milliseconds

threshold *milliseconds*

Specify the threshold for the adaptation of the BFD session transmit interval. When the transmit interval adapts to a value greater than the threshold, a single trap and a single system message are sent.

- **Range:** 0 through 4,294,967,295 ($2^{32} - 1$)

NOTE: The threshold value specified in the threshold statement must be greater than the value specified in the minimum-interval statement for the transmit-interval statement.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.2.

Support for BFD authentication introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD for Static Routes for Faster Network Failure Detection](#)

[bfd-liveness-detection \(BGP\)](#)

[bfd-liveness-detection \(Layer 2 VPN and VPLS\) | 1446](#)

tunnel-services (Routing Instances VPLS)

IN THIS SECTION

- [Syntax | 1697](#)
- [Hierarchy Level | 1697](#)
- [Description | 1697](#)
- [Options | 1697](#)
- [Required Privilege Level | 1698](#)

Syntax

```
tunnel-services {  
    devices device-names;  
    primary primary-device-name;  
}
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols  
vpls],  
[edit routing-instances routing-instance-name protocols vpls]
```

Description

Specify that traffic for particular VPLS routing instances be forwarded to specific virtual tunnel (VT) interfaces, allowing you to load-balance VPLS traffic among all the available VT interfaces on the router.

NOTE: In the VPLS documentation, the word *router* in terms such as *PE router* is used to refer to any device that provides routing functions.

Options

devices *device-names*—Specify the VT interfaces acceptable for use by the VPLS routing instance. If you do not configure this option, all VT interfaces available to the router can be used for de-encapsulating traffic for this instance.

primary *primary-device-name*—Specify the primary VT interface to be used by the VPLS routing instance. The VT interface specified is used to de-encapsulate all VPLS traffic from the MPLS core network for this routing instance. If the VT interface specified is unavailable, then one of the other acceptable VT interfaces is used for handling the VPLS traffic. If you do not configure this option, any acceptable VT interface can be used to de-encapsulate VPLS traffic from the core.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

| [Specifying the VT Interfaces Used by VPLS Routing Instances](#) | 701

version (BFD Liveness Detection)

IN THIS SECTION

- [Syntax](#) | 1698
- [Hierarchy Level](#) | 1699
- [Description](#) | 1699
- [Options](#) | 1699
- [Required Privilege Level](#) | 1700
- [Release Information](#) | 1700

Syntax

```
version (1 | automatic);
```

Hierarchy Level

```
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name routing-instances name protocols (evpn |
l2vpn | vpls) mesh-group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn |
vpls) neighbor neighbor-id oam bfd-liveness-detection],
[edit logical-systems name tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-
group mesh-group-name neighbor neighbor-id oam bfd-liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) oam bfd-
liveness-detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id oam bfd-liveness-
detection],
[edit routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-name neighbor
neighbor-id oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls)
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) neighbor neighbor-id
oam bfd-liveness-detection],
[edit tenants name routing-instances name protocols (evpn | l2vpn | vpls) mesh-group mesh-group-
name neighbor neighbor-id oam bfd-liveness-detection],
```

Description

Specify the BFD version for detection. You can explicitly configure BFD version 1 or the routing device can automatically detect the BFD version. By default, the routing device automatically detects the BFD version.

Options

Configure the BFD version to detect: 1 (BFD version 1) or automatic (autodetect the BFD version).

- **Default:** The routing device automatically detects the BFD version.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.1

RELATED DOCUMENTATION

[Configuring BFD for Layer 2 VPN and VPLS | 231](#)

[Example: Configuring BFD Authentication for BGP](#)

[Example: Configuring BFD on Internal BGP Peer Sessions](#)

[Understanding BFD Authentication for BGP](#)

virtual-circuit-id

IN THIS SECTION

- [Syntax | 1700](#)
- [Hierarchy Level | 1701](#)
- [Description | 1701](#)
- [Options | 1701](#)
- [Required Privilege Level | 1701](#)
- [Release Information | 1701](#)

Syntax

```
virtual-circuit-id identifier;
```

Hierarchy Level

```
[edit logical-systems logical-system-name protocols l2circuit local-switching interface
interface-name backup-neighbor address],
[edit logical-systems logical-system-name protocols l2circuit neighbor address
interface interface-name],
[edit logical-systems logical-system-name protocols l2circuit neighbor address interface
interface-name backup-neighbor address],
[edit protocols l2circuit local-switching interface interface-name backup-neighbor address],
[edit protocols l2circuit neighbor address interface interface-name],
[edit protocols l2circuit neighbor address interface interface-name backup-neighbor address]
```

Description

Uniquely identify a Layer 2 circuit for either a standard pseudowire or a redundant pseudowire.

Options

identifier—1 through 4,294,967,295

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Hierarchy levels for backup-neighbor (pseudowire redundancy) added in Junos OS Release 9.2.

RELATED DOCUMENTATION

[Configuring the Virtual Circuit ID | 368](#)

[Configuring Pseudowire Redundancy on the PE Router | 226](#)

[Example: Configuring Layer 2 Circuit Switching Protection | 461](#)

virtual-gateway-address

IN THIS SECTION

- [Syntax | 1702](#)
- [Hierarchy Level | 1702](#)
- [Description | 1702](#)
- [Options | 1703](#)
- [Required Privilege Level | 1703](#)
- [Release Information | 1703](#)

Syntax

```
virtual-gateway-address address;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number family family address address]
```

Description

Set the default IPv4 or IPv6 address for the gateway for end hosts. You eliminate the need to proxy for remote gateway IP addresses because you must configure the virtual gateway address using the same IP address as on all of the provider edge (PE) devices. This configuration internally generates the same Virtual Router Redundancy Protocol (VRRP) MAC. You can set a corresponding virtual gateway address for each logical integrated routing and bridging (IRB) interface. A maximum of 64 PEs can have the same virtual gateway address.

To support pinging on the virtual gateway IP address, you must include both the `virtual-gateway-accept-data` statement and the `preferred` statement at the `[edit interfaces irb unit]` hierarchy of the preferred virtual gateway.

Options

address—virtual gateway address. You can't specify the addresses 0.0.0.0 (default route address) or 255.255.255.255 (broadcast IP address).

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 16.1.

RELATED DOCUMENTATION

EVPN with IRB Solution Overview

Example: Configuring EVPN with IRB Solution

[Configuring the Interface Address](#)

virtual-mac

IN THIS SECTION

- [Syntax | 1704](#)
- [Hierarchy Level | 1704](#)
- [Description | 1704](#)
- [Options | 1704](#)
- [Required Privilege Level | 1704](#)
- [Release Information | 1704](#)

Syntax

```
virtual-mac mac-address/mask;
```

Hierarchy Level

```
[edit protocols l2-learning global-mac-move]
```

Description

Configure MAC addresses that are not to be considered in the VPLS loop prevention algorithm.

NOTE: Starting in Junos OS Release 17.4R1, this statement has been replaced with the [exclusive-mac](#) statement.

Options

mac-address/mask MAC address

- **Values:** 00:00:5e:00:01:00/8, 00:00:0c:07:ac:00/8, and 02:bf:00:00:00:00/32

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.2.

RELATED DOCUMENTATION

[Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves](#) | 1147

[global-mac-move](#) | 1515

vlan-id

IN THIS SECTION

- [Syntax | 1705](#)
- [Hierarchy Level | 1705](#)
- [Description | 1705](#)
- [Options | 1705](#)
- [Required Privilege Level | 1706](#)
- [Release Information | 1706](#)

Syntax

```
vlan-id number;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number]
```

Description

For Fast Ethernet and Gigabit Ethernet interfaces only, bind an 802.1Q VLAN tag ID to a logical interface.

Options

number—A valid VLAN identifier.

- **Range:** For 4-port Fast Ethernet PICs configured to handle VPLS traffic, 512 through 1023. For 1-port and 10-port Gigabit Ethernet PICs configured to handle VPLS traffic, 512 through 4094.

NOTE: On Junos OS Evolved, `vlan-id 0` is not supported.

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring Interfaces for VPLS Routing](#) | 733

vlan-id (routing instance)

IN THIS SECTION

- [Syntax](#) | 1706
- [Hierarchy Level](#) | 1707
- [Description](#) | 1707
- [Options](#) | 1707
- [Required Privilege Level](#) | 1707
- [Release Information](#) | 1707

Syntax

```
vlan-id (vlan-id | all | none);
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name],
[edit routing-instances routing-instance-name]
[edit routing-instances routing-instance-name instance-type]
```

Description

Specify 802.1Q VLAN tag IDs to a routing instance.

Options

vlan-id—A valid VLAN identifier.

- **Range:** For 4-port Fast Ethernet PICs, 512 through 1023. For 1-port and 10-port Gigabit Ethernet PICs configured to handle VPLS traffic, 512 through 4094.

all—Include all VLAN identifiers specified on the logical interfaces included in the routing instance.

none—Include no VLAN identifiers for the routing instance.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 13.2.

RELATED DOCUMENTATION

Configuring EVPN Routing Instances

Configuring EVPN Routing Instances on EX9200 Switches

vlan-id inner-all

IN THIS SECTION

- [Syntax | 1708](#)
- [Hierarchy Level | 1708](#)
- [Description | 1708](#)
- [Required Privilege Level | 1708](#)
- [Release Information | 1708](#)

Syntax

```
vlan-id inner-all;
```

Hierarchy Level

```
[edit routing instances instance_name]
```

Description

Enable qualified MAC learning on the second (inner) VLAN tag of an ingress 2-tagged packet, without removing the first (outer) tag implicitly. For a single vlan-tagged packet, qualified MAC learning happens on VLAN 4096. If the ingress packet has more than two tags, all tags beyond the second tag are treated as part of data.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Command introduced in Junos OS Release 17.4R1.

RELATED DOCUMENTATION

[Understanding Qualified MAC Learning | 1222](#)

[deep-vlan-qualified-learning | 1460](#)

vlan-id-list (Interface in VPLS)

IN THIS SECTION

- [Syntax | 1709](#)
- [Hierarchy Level | 1709](#)
- [Description | 1709](#)
- [Options | 1710](#)
- [Required Privilege Level | 1710](#)
- [Release Information | 1710](#)

Syntax

```
vlan-id-list [ numbers number-number ];
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number]
```

Description

Configure a logical interface to forward packets and learn MAC addresses within each VPLS routing instance configured with a VLAN ID that matches a VLAN ID specified in the list. VLAN IDs can be entered individually using a space to separate each ID, entered as an inclusive list separating the starting VLAN ID and ending VLAN ID with a hyphen, or a combination of both.

Options

number number—Individual VLAN IDs separated by a space.

number-number—Starting VLAN ID and ending VLAN ID in an inclusive range.

- **Range:** 1 through 4095

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced for VPLS in Junos OS Release 10.2.

RELATED DOCUMENTATION

[Configuring Interfaces for VPLS Routing | 733](#)

[Configuring Interfaces for VPLS Routing | 733](#)

vlan-tagging

IN THIS SECTION

- [Syntax | 1711](#)
- [Syntax \(QFX Series, NFX Series, and EX4600\) | 1711](#)
- [Syntax \(SRX Series Interfaces\) | 1711](#)
- [Hierarchy Level | 1711](#)
- [QFX Series, NFX Series, and EX4600 Interfaces | 1711](#)
- [SRX Series Interfaces | 1711](#)
- [Description | 1712](#)
- [Default | 1712](#)

- Options | 1712
- Required Privilege Level | 1712
- Release Information | 1712

Syntax

```
vlan-tagging;
```

Syntax (QFX Series, NFX Series, and EX4600)

```
vlan-tagging;
```

Syntax (SRX Series Interfaces)

```
vlan-tagging native-vlan-id vlan-id;
```

Hierarchy Level

```
[edit interfaces interface-name],  
[edit logical-systems logical-system-name interfaces interface-name]
```

QFX Series, NFX Series, and EX4600 Interfaces

```
[edit interfaces \(QFX Series\) interface-name ]  
[edit interfaces \(QFX Series\) interface-range interface-range-name ]
```

SRX Series Interfaces

```
[edit interfaces interface ]
```

Description

For Fast Ethernet and Gigabit Ethernet interfaces, aggregated Ethernet interfaces configured for VPLS, and pseudowire subscriber interfaces, enable the reception and transmission of 802.1Q VLAN-tagged frames on the interface.

NOTE: For QFX Series configure VLAN identifier for untagged packets received on the physical interface of a trunk mode interface. Enable VLAN tagging. The platform receives and forwards single-tag frames with 802.1Q VLAN tags.

On EX Series switches except for EX4300 and EX9200 switches, the `vlan-tagging` and `family ethernet-switching` statements cannot be configured on the same interface. Interfaces on EX2200, EX3200, EX3300, EX4200, and EX4500 switches are set to `family ethernet-switching` by the default factory configuration. EX6200 and EX8200 switch interfaces do not have a default `family` setting.

Default

VLAN tagging is disabled by default.

Options

`native-vlan-id`—(SRX Series) Configures a VLAN identifier for untagged packets. Enter a number from 0 through 4094.

NOTE: The `native-vlan-id` can be configured only when either `flexible-vlan-tagging mode` or `interface-mode trunk` is configured.

Required Privilege Level

`interface`—To view this statement in the configuration.

`interface-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

Statement introduced in Junos OS Release 12.2 for ACX Series Universal Metro Routers.

RELATED DOCUMENTATION

[802.1Q VLANs Overview](#)

[Configuring a Layer 3 Subinterface \(CLI Procedure\)](#)

[Configuring Tagged Aggregated Ethernet Interfaces](#)

[Example: Configuring Layer 3 Subinterfaces for a Distribution Switch and an Access Switch](#)

[vlan-id](#)

[Configuring a Layer 3 Logical Interface](#)

[Configuring VLAN Tagging](#)

vlan-tags (Stacked VLAN Tags)

IN THIS SECTION

- [Syntax | 1713](#)
- [Hierarchy Level | 1713](#)
- [Description | 1714](#)
- [Options | 1714](#)
- [Required Privilege Level | 1716](#)
- [Release Information | 1716](#)

Syntax

```
vlan-tags inner tpid.vlan-id inner-list value inner-range vid1-vid2 outer tpid.vlan-id;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number]
```

Description

Bind TPIDs and 802.1Q VLAN tag IDs to a logical interface. TPID fields are used to identify the frame as an IEEE 802.1Q-tagged frame.

Options

inner
tpid. vlan-id A TPID and a valid VLAN identifier. TPID is a 16-bit field set to a value of 0x8100 in order to identify the frame as an IEEE 802.1Q-tagged frame.

- **Range:** (most routers) For VLAN ID, 1 through 4094. VLAN ID 0 is reserved for tagging the priority of frames. For PTX Series, VLAN ID 0 is not supported.

inner-list
value List or a set of VLAN identifiers.

NOTE: This is supported on MX Series routers with Trio-based FPCs.

inner-range
tpid. vid1-vid2 Specify a TPID and a range of VLAN IDs where vid1 is the start of the range and vid2 is the end of the range.

NOTE: On the network-to-network (NNI) or egress interfaces of provider edge (PE) routers, you cannot configure the *inner-range tpid. vid1-vid2* option with the *vlan-tags* statement for ISP-facing interfaces.

- **Range:** For VLAN ID, 1 through 4094. VLAN ID 0 is reserved for tagging the priority of frames.

outer
tpid. vlan-id A TPID and a valid VLAN identifier.

- **Range:** (most routers) For VLAN ID, 1 through 511 for normal interfaces, and 512 through 4094 for VLAN CCC interfaces. VLAN ID 0 is reserved for tagging the priority of frames. For PTX Series, VLAN ID 0 is not supported.

NOTE: Configuring *inner-range* with the entire *vlan-id* range consumes system resources and is not a best practice. The *inner-range* must be used only when a subset of VLAN IDs of inner tag (not the entire range) needs to be associated with a logical interface. If you specify the entire range (1 through 4094), it has the same

result as not specifying a range; however, it consumes Packet Forwarding Engine resources such as VLAN lookup table entries, and so on.

The following examples illustrate this further:

1. Inefficient

```
[edit interfaces interface-name]stacked-vlan-tagging;
unit number {
    vlan-tags outer vid inner-range 1-4094;
}
```

2. Best Practice

```
[edit interfaces interface-name]
vlan-tagging;
unit number {
    vlan-id vid;
}
```

NOTE: Configuring `inner-range` with the entire `vlan-id` range consumes system resources and is not a best practice. The `inner-range` must be used only when a subset of VLAN IDs of inner tag (not the entire range) needs to be associated with a logical interface. If you specify the entire range (1 through 4094), it has the same result as not specifying a range; however, it consumes Packet Forwarding Engine resources such as VLAN lookup table entries, and so on.

The following examples illustrate this further:

1. Inefficient

```
[edit interfaces interface-name]
stacked-vlan-tagging;
unit number {
    vlan-tags outer vid inner-range 1-4094;
}
```

2. Best Practice

```
[edit interfaces interface-name]
vlan-tagging;
unit number {
    vlan-id vid;
}
```

Required Privilege Level

interface—To view this statement in the configuration.

interface-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring Dual VLAN Tags](#)

[Configuring Flexible VLAN Tagging on PTX Series Packet Transport Routers](#)

[stacked-vlan-tagging](#)

vpls (Interfaces)

IN THIS SECTION

- [Syntax | 1717](#)
- [Hierarchy Level | 1717](#)
- [Description | 1717](#)
- [Required Privilege Level | 1717](#)
- [Release Information | 1717](#)

Syntax

```
vpls;
```

Hierarchy Level

```
[edit interfaces interface-name unit logical-unit-number family],  
[edit logical-systems logical-system-name interfaces interface-name unit logical-unit-number  
family]
```

Description

Specify the VPLS protocol family information for the logical interface.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

RELATED DOCUMENTATION

[Configuring Interfaces for VPLS Routing | 733](#)

vpls (Routing Instance)

IN THIS SECTION

● [Syntax | 1718](#)

- Hierarchy Level | 1720
- Description | 1720
- Options | 1720
- Required Privilege Level | 1720
- Release Information | 1720

Syntax

```
vpls {
    mac-pinning;
    active-interface {
        any;
        primary interface-name;
    }
    community COMM;
    connectivity-type (ce | irb);
    control-word;
    encapsulation-type ethernet;
    ignore-encapsulation-mismatch;
    ignore-mtu-mismatch;
    import-labeled-routes [ routing-instance-name ];
    interface interface-name;
    interface-mac-limit limit;
    label-block-size size;
    mac-flush [ explicit-mac-flush-message-options ];
    mac-table-aging-time time;
    mac-table-size size;
    mesh-group mesh-group-name {
        interface interface-name;
        l2vpn-id (as-number:id | ip-address:id);
        local-switching;
        mac-flush [ explicit-mac-flush-message-options ];
        neighbor address {...};
        peer-as all;
        pseudowire-status-tlv hot-standby-vc-on;
        route-distinguisher (as-number:id | ip-address:id);
        vpls-id number;
        vrf-export [ policy-names ];
    }
}
```

```

    vrf-import [ policy-names ];
    vrf-target {
        community;
        import community-name;
        export community-name;
    }
}
mtu mtu;
no-control-word;
no-tunnel-services;
service-type single;
site site-name {
    active-interface interface-name {
        any;
        primary preference-value;
    }
    best-site;
    interface interface-name {
        interface-mac-limit limit;
    }
    mesh-group mesh-group-name;
    multi-homing;
    site-identifier identifier;
    site-preference preference-value {
        backup;
        primary;
    }
}
site-range number;
traceoptions {
    file filename <files number> <size size> <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
tunnel-services {
    devices device-names;
    primary primary-device-name;
}
}

```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances routing-instance-name protocols],  
[edit routing-instances routing-instance-name protocols]
```

Description

Configure a virtual private LAN service (VPLS) routing instance.

The remaining statements are explained separately. Search for a statement in [CLI Explorer](#) or click a linked statement in the Syntax section for details.

Options

`service-type single`—Allows one vlan per routing instance.

Required Privilege Level

`routing`—To view this statement in the configuration.

`routing-control`—To add this statement to the configuration.

Release Information

Statement introduced before Junos OS Release 7.4.

`mac-flush` option introduced in Junos OS Release 10.0.

`hot-standby-vc-on`, `import-labeled-routes [routing-instance-name]`, and interface `interface` options introduced in Junos OS Release 15.1R2.

RELATED DOCUMENTATION

| [Configuring VPLS Routing Instances](#) | 674

vpls-id

IN THIS SECTION

- [Syntax | 1721](#)
- [Hierarchy Level | 1721](#)
- [Description | 1721](#)
- [Options | 1722](#)
- [Required Privilege Level | 1722](#)
- [Release Information | 1722](#)

Syntax

```
vpls-id vpls-id;
```

Hierarchy Level

```
[edit logical-systems logical-system-name routing-instances instance-name protocols l2vpn],
[edit logical-systems logical-system-name routing-instances instance-name protocols l2vpn mesh-
group mesh-group-name],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls],
[edit logical-systems logical-system-name routing-instances instance-name protocols vpls mesh-
group mesh-group-name],
[edit routing-instances instance-name protocols l2vpn],
[edit routing-instances instance-name protocols l2vpn mesh-group mesh-group-name],
[edit routing-instances instance-name protocols vpls],
[edit routing-instances instance-name protocols vpls mesh-group mesh-group-name]
```

Description

Identify the virtual circuit identifier used for the VPLS routing instance or mesh group. This statement is a part of the configuration to enable LDP signaling for VPLS.

Options

vpls-id—Specify a valid identifier for the VPLS routing instance.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 8.4.

RELATED DOCUMENTATION

| [Configuring LDP Signaling for VPLS | 682](#)

vpls-id-list (protocols vpls mesh-group)

IN THIS SECTION

- [Syntax | 1722](#)
- [Hierarchy Level | 1723](#)
- [Description | 1723](#)
- [Options | 1723](#)
- [Required Privilege Level | 1723](#)
- [Release Information | 1723](#)

Syntax

```
vpls-id-list vc-id-numbers;
```

Hierarchy Level

```
[edit routing-instances routing-instance-name protocols vpls mesh-group mesh-group-name neighbor
address]
```

Description

The `vpls-id-list` option allows you to configure multiple pseudowires under LDP-VPLS neighbor by creating one pseudowire per virtual circuit id. This combination of neighbor and virtual circuit ID must be unique across the I2circuit and all local LDP-VPLS instances. The pseudowire will terminate in the specified mesh-group.

As with other pseudowires, the pseudowires created here will signal the remote PE via LDP label mapping message. For each pseudowire created under a neighbor, VPLS will create a VT/LSI interface and add both it and the and label route to the mpls.0 table. Note that you can create multiple pseudowires between the same pair of PEs in LDP-VPLS for a single routing instances only.

Enable `local-switching` along with `vpls-id-list` to allow local switching of traffic (including BUM traffic) between multiple pseudo wires. This can also eliminate the need to have a dedicated mesh-group for each LDP spoke pseudo wire (which has a limit of 14), and provide support for H-VPLS in EVP-LAN and EP-LAN topologies.

Options

vc-id-numbers—The virtual circuit ID for the PE pair. This ID can be any number in the range of 1 to 4294967295.

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.2 .

RELATED DOCUMENTATION

[show vpls connections](#) | [1874](#)

[neighbor \(Protocols VPLS\) | 1590](#)

vpls-mac-move

IN THIS SECTION

- [Syntax | 1724](#)
- [Hierarchy Level | 1724](#)
- [Description | 1724](#)
- [Options | 1725](#)
- [Required Privilege Level | 1725](#)
- [Release Information | 1725](#)

Syntax

```
vpls-mac-move{  
    cooloff-time seconds;  
    interface-recovery-time seconds;  
    statistical-approach-wait-time seconds;  
    virtual-mac mac-address /mask;  
}
```

Hierarchy Level

```
[edit protocols l2-learning]
```

Description

Configure VPLS MAC move parameters to prevent loop creation in the network.

Options

cooloff-time <i>seconds</i>	Time interval, in seconds, during which no additional interface is disabled by the PE after a MAC move is detected. By default, it is 30 seconds.
interface-recovery-time <i>seconds</i>	Time interval, in seconds, after which the interface is enabled after a VPLS MAC move is detected. By default, the timer is disabled.
statistical-approach-wait-time <i>seconds</i>	Time interval, in seconds, during which the MAC moves are monitored to collect the statistics. By default, it is 30 seconds.

The remaining statement is explained separately. See [CLI Explorer](#).

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 14.2.

Statement changed to `global-mac-move` in Junos OS Release 17.4R1

RELATED DOCUMENTATION

[MAC Moves Loop Prevention in VPLS Network Overview](#) | 1147

[Example: Configuring Loop Prevention in VPLS Network Due to MAC Moves](#) | 1147

[virtual-mac](#) | 1703

vpws-service-id

IN THIS SECTION

● [Syntax](#) | 1726

● [Hierarchy Level](#) | 1726

- [Description | 1726](#)
- [Options | 1726](#)
- [Required Privilege Level | 1727](#)
- [Release Information | 1727](#)

Syntax

```
vpws-service-id {
    local service-id;
    remote service-id;
}
```

Hierarchy Level

```
[edit routing-instance instance-type protocols evpn interface interface-name]
```

Description

Specify the local and remote Ethernet VPN (EVPN)-Virtual Private Wire Service (VPWS) service identifiers. These service identifiers are unique to an EVPN and are used to identify the endpoints of the EVPN-VPWS network. These endpoints are autodiscovered by BGP and are used to exchange the service labels (learned from the respective provider edge (PE) routers) that are used by autodiscovered routes per EVI route type. Depending on the mode of operation of the PE routers in the EVPN-VPWS network, these two endpoints of the can be colocated on the same PE router or on different PE routers.

Options

local Unique local VPWS service identifier of the EVPN-VPWS network. This identifies the logical interface of the PE router forwarding traffic to the PE router with a remote VPWS service identifier in the EVPN-VPWS network.

- **Range:** 1 through 16,777,215

remote Unique remote VPWS service identifier of the EVPN-VPWS network. This identifies the logical interface of the PE router receiving the traffic from the PE router with a local VPWS service identifier in the EVPN-VPWS network.

- **Range:** 1 through 16,777,215

Required Privilege Level

routing—To view this statement in the configuration.

routing-control—To add this statement to the configuration.

Release Information

Statement introduced in Junos OS Release 17.1.

RELATED DOCUMENTATION

Overview of VPWS with EVPN Signaling Mechanisms

EVPN Multihoming Overview

Configuring VPWS with EVPN Signaling Mechanisms

Example: Configuring VPWS with EVPN Signaling Mechanisms

show evpn vpws-instance

Operational Commands

IN THIS CHAPTER

- [clear bridge statistics | 1729](#)
- [clear pim snooping join | 1731](#)
- [clear pim snooping statistics | 1734](#)
- [clear security group-vpn member group | 1736](#)
- [clear security group-vpn member ike security-associations | 1738](#)
- [clear security group-vpn member kek security-associations | 1739](#)
- [clear vpls mac-address | 1740](#)
- [clear vpls mac-move-action | 1742](#)
- [clear vpls mac-table | 1744](#)
- [ping mpls l2circuit | 1745](#)
- [ping mpls l2vpn | 1749](#)
- [ping vpls instance | 1753](#)
- [request l2circuit-switchover | 1756](#)
- [show interfaces lsi \(Label-Switched Interface\) | 1757](#)
- [show l2circuit connections | 1762](#)
- [show l2vpn connections | 1773](#)
- [show pim snooping interfaces | 1783](#)
- [show pim snooping join | 1787](#)
- [show pim snooping neighbors | 1793](#)
- [show pim snooping statistics | 1800](#)
- [show route | 1807](#)
- [show route table | 1820](#)
- [show route forwarding-table | 1849](#)
- [show security group-vpn member ike security-associations | 1863](#)
- [show security pki ca-certificate \(View\) | 1869](#)
- [show vpls connections | 1874](#)

- [show vpls flood event-queue | 1890](#)
- [show vpls flood instance | 1892](#)
- [show vpls flood route | 1896](#)
- [show vpls mac-move-action | 1899](#)
- [show vpls mac-table | 1901](#)
- [show vpls statistics | 1909](#)

clear bridge statistics

IN THIS SECTION

- [Syntax | 1729](#)
- [Description | 1730](#)
- [Options | 1730](#)
- [Required Privilege Level | 1730](#)
- [Output Fields | 1730](#)
- [Sample Output | 1730](#)
- [Sample Output | 1730](#)
- [Sample Output | 1731](#)
- [Release Information | 1731](#)

Syntax

```
clear bridge statistics
<bridge-domain bridge-domain>
<instance instance-name bridge-domain bridge-domain>
<logical-system logical-system-name instance instance-name bridge-domain bridge-domain>
```

Description

Clear bridge statistics of all interfaces in a routing instance.

Options

bridge-domain <i>bridge-domain</i>	(Optional) Clear bridge statistics of all interfaces for the specified bridge domain in the default routing instance in the global logical system.
instance <i>instance-name</i> bridge-domain <i>bridge-domain</i>	(Optional) Clear bridge statistics of all interfaces for the specified bridge domain in the specified routing instance in the global logical system.
logical-system <i>logical-system-name</i> instance <i>instance-name</i> bridge-domain <i>bridge-domain</i>	(Optional) Clear bridge statistics of all interfaces for the specified bridge domain, routing instance, and logical system name.

Required Privilege Level

maintenance

Output Fields

These commands produces no output.

Sample Output

clear bridge statistics

```
user@host> clear bridge statistics bridge-domain bridge-domain-name
```

Sample Output

clear bridge statistics

```
user@host> clear bridge statistics instance instance-name bridge-domain bridge-domain-name
```

Sample Output

clear bridge statistics

```
user@host> clear bridge statistics logical-system logical-system-name instance instance-name  
bridge-domain bridge-domain-name
```

Release Information

Command introduced in Junos OS Release 17.2.

RELATED DOCUMENTATION

| [clear evpn statistics](#)

clear pim snooping join

IN THIS SECTION

- [Syntax | 1731](#)
- [Description | 1732](#)
- [Options | 1732](#)
- [Required Privilege Level | 1732](#)
- [Output Fields | 1732](#)
- [Sample Output | 1732](#)
- [Release Information | 1733](#)

Syntax

```
clear pim snooping join  
<instance instance-name>
```

```
<logical-system logical-system-name>
<vlan-id vlan-id>
```

Description

Clear information about Protocol Independent Multicast (PIM) snooping joins.

Options

none	Display detailed information.
instance <i>instance-name</i>	(Optional) Clear PIM snooping join information for the specified routing instance.
logical-system <i>logical-system-name</i>	(Optional) Delete the IGMP snooping statistics for a given logical system or for all logical systems.
vlan-id <i>vlan-identifier</i>	(Optional) Clear PIM snooping join information for the specified VLAN.

Required Privilege Level

view

Output Fields

See ["show pim snooping join" on page 1787](#) for an explanation of the output fields.

Sample Output

clear pim snooping join

The following sample output displays information about PIM snooping joins before and after the clear pim snooping join command is entered:

```
user@host> show pim snooping join extensive
Instance: vpls1
Learning-Domain: vlan-id 10
Learning-Domain: vlan-id 20

Group: 198.51.100.2
```

```

Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 192.0.2.5, port: ge-1/3/7.20
Downstream port: ge-1/3/1.20
Downstream neighbors:
192.0.2.2 State: Join Flags: SRW Timeout: 185

Group: 198.51.100.3
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 192.0.2.4, port: ge-1/3/5.20
Downstream port: ge-1/3/3.20
Downstream neighbors:
192.0.2.3 State: Join Flags: SRW Timeout: 175
user@host> clear pim snooping join
Clearing the Join/Prune state for 203.0.113.0/24
Clearing the Join/Prune state for 203.0.113.0/24
user@host> show pim snooping join extensive
Instance: vpls1
Learning-Domain: vlan-id 10
Learning-Domain: vlan-id 20

```

Release Information

Command introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[PIM Snooping for VPLS](#)

clear pim snooping statistics

IN THIS SECTION

- [Syntax | 1734](#)
- [Description | 1734](#)
- [Options | 1734](#)
- [Required Privilege Level | 1735](#)
- [Output Fields | 1735](#)
- [Sample Output | 1735](#)
- [Release Information | 1736](#)

Syntax

```
clear pim snooping statistics  
<instance instance-name>  
<interface interface-name>  
<logical-system logical-system-name>  
<vlan-id vlan-id>
```

Description

Clear Protocol Independent Multicast (PIM) snooping statistics.

Options

none	Clear PIM snooping statistics for all family addresses, instances, and interfaces.
instance <i>instance-name</i>	(Optional) Clear statistics for a specific PIM-snooping-enabled routing instance.
interface <i>interface-name</i>	(Optional) Clear PIM snooping statistics for a specific interface.

logical-system <i>logical-system-name</i>	(Optional) Delete the IGMP snooping statistics for a given logical system or for all logical systems.
vlan-id <i>vlan-identifier</i>	(Optional) Clear PIM snooping statistics information for the specified VLAN.

Required Privilege Level

clear

Output Fields

See ["show pim snooping statistics" on page 1800](#) for an explanation of the output fields.

Sample Output

clear pim snooping statistics

The following sample output displays PIM snooping statistics before and after the `clear pim snooping statistics` command is entered:

```

user@host> show pim snooping statistics
Instance: vpls1
Learning-Domain: vlan-id 10

Tx J/P messages 0
RX J/P messages 660
Rx J/P messages -- seen 0
Rx J/P messages -- received 660
Rx Hello messages 1396
Rx Version Unknown 0
Rx Neighbor Unknown 0
Rx Upstream Neighbor Unknown 0
Rx Bad Length 0
Rx J/P Busy Drop 0
Rx J/P Group Aggregate 0
Rx Malformed Packet 0

Learning-Domain: vlan-id 20
user@host> clear pim snooping statistics

```

```

user@host> show pim snooping statistics
Instance: vpls1
Learning-Domain: vlan-id 10

Tx J/P messages 0
RX J/P messages 0
Rx J/P messages -- seen 0
Rx J/P messages -- received 0
Rx Hello messages 0
Rx Version Unknown 0
Rx Neighbor Unknown 0
Rx Upstream Neighbor Unknown 0
Rx Bad Length 0
Rx J/P Busy Drop 0
Rx J/P Group Aggregate 0
Rx Malformed Packet 0

Learning-Domain: vlan-id 20

```

Release Information

Command introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[PIM Snooping for VPLS](#)

clear security group-vpn member group

IN THIS SECTION

- [Syntax | 1737](#)
- [Description | 1737](#)
- [Options | 1737](#)
- [Required Privilege Level | 1737](#)

- [Output Fields | 1737](#)
- [Release Information | 1737](#)

Syntax

```
clear security group-vpn member group <vpn vpn-name> <group-id group-id>
```

Description

Clear all current information for IKE, TEK, and KEK SAs. Group VPNv2 is supported on MX Series routers, SRX300, SRX320, SRX340, SRX345, SRX550HM, SRX1500, SRX4100, SRX4200, and SRX4600 devices and vSRX instances.

Options

none	Clear SA information for all groups.
vpn <i>vpn-name</i>	(Optional) Clear SA information for the specified VPN name.
group-id <i>group-id</i>	(Optional) Clear SA information for the specified group identifier.

Required Privilege Level

clear

Output Fields

This command produces no output.

Release Information

Command introduced in Junos OS Release 15.1X49-D30.

RELATED DOCUMENTATION

| [Group VPNv2 Overview](#)

clear security group-vpn member ike security-associations

IN THIS SECTION

- [Syntax | 1738](#)
- [Description | 1738](#)
- [Options | 1738](#)
- [Required Privilege Level | 1739](#)
- [Output Fields | 1739](#)
- [Release Information | 1739](#)

Syntax

```
clear security group-vpn member ike security-associations [index SA-index] [peer-ipaddress]
```

Description

Clear IKE security association (SA) for a group member. Group VPNv2 is supported on SRX300, SRX320, SRX340, SRX345, SRX550HM, SRX1500, SRX4100, SRX4200, and SRX4600 devices and vSRX instances.

Options

- **none**—Clear all IKE SAs for the group member.
- **index**—(Optional) Clear the IKE SA with this index number.
- **peer-ipaddress**—(Optional) Clear the IKE SA with this peer.

Required Privilege Level

clear

Output Fields

This command produces no output.

Release Information

Command introduced in Junos OS Release 10.2.

RELATED DOCUMENTATION

show security group-vpn member ike security-associations

[Group VPNv2 Overview](#)

clear security group-vpn member kek security-associations

IN THIS SECTION

- [Syntax | 1739](#)
- [Description | 1740](#)
- [Options | 1740](#)
- [Required Privilege Level | 1740](#)
- [Output Fields | 1740](#)
- [Release Information | 1740](#)

Syntax

```
clear security group-vpn member kek security-associations [index SA-index]
```

Description

Clear key encryption key (KEK) SAs for a group member.

Options

- `none`—Clear all KEK SAs for the group member.
- `index`—(Optional) Clear the KEK SA with this index number.

Required Privilege Level

clear

Output Fields

This command produces no output.

Release Information

Command introduced in Junos OS Release 10.2.

RELATED DOCUMENTATION

[show security group-vpn member kek security-associations](#)

[Group VPNv2 Overview](#)

clear vpls mac-address

IN THIS SECTION

- [Syntax | 1741](#)
- [Description | 1741](#)
- [Options | 1741](#)
- [Required Privilege Level | 1741](#)

- [Output Fields | 1742](#)
- [Sample Output | 1742](#)
- [Release Information | 1742](#)

Syntax

```
clear vpls mac-address
<instance instance-name>
<logical-system (all | logical-system-name)>
<mac-address>
```

Description

(T Series and M Series routers, except for the M160 router) Clear media access control (MAC) address entries from the virtual private LAN service (VPLS) table.

Options

none	Clear all MAC address entries from the VPLS table for all routing instances.
instance <i>instance-name</i>	(Optional) Clear all MAC address entries for a VPLS instance from the VPLS table.
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.
<i>mac-address</i>	(Optional) Clear a specific MAC address in a VPLS instance from the VPLS table.

Required Privilege Level

maintenance

Output Fields

When you enter this command, you are provided feedback on the status of your request.

Sample Output

clear vpls mac-address

```
user@host> clear vpls mac-address
```

Release Information

Command introduced before Junos OS Release 7.4.

clear vpls mac-move-action

IN THIS SECTION

- [Syntax | 1742](#)
- [Description | 1743](#)
- [Options | 1743](#)
- [Required Privilege Level | 1743](#)
- [Output Fields | 1743](#)
- [Sample Output | 1743](#)
- [Release Information | 1743](#)

Syntax

```
clear vpls mac-move-action  
<interface ifl-name.unit>
```

Description

Clear the learning interfaces (IFLs) disabled due to a MAC move.

Options

none Clear all the IFLs disabled due to a MAC move.

interface *ifl-name.unit* (Optional) Clear the VPLS interface disabled due to a MAC move.

Required Privilege Level

clear

Output Fields

When you enter this command, you are provided feedback on the status of your request.

Sample Output

clear vpls mac-move-action (MX Series)

```
user@host> clear vpls mac-move-action
```

clear vpls mac-move-action interface ifl-name.unit (MX Series)

```
user@host> clear vpls mac-move-action interface xe-1/0/0.1
```

Release Information

Command introduced in Junos OS Release 14.2.

clear vpls mac-table

IN THIS SECTION

- [Syntax | 1744](#)
- [Description | 1744](#)
- [Options | 1744](#)
- [Required Privilege Level | 1745](#)
- [Output Fields | 1745](#)
- [Sample Output | 1745](#)
- [Release Information | 1745](#)

Syntax

```
clear vpls mac-table  
<instance instance-name>  
<interface interface-name>  
<logical-system (all | logical-system-name)>  
<mac-address>  
<vlan-id>
```

Description

(MX Series routers) Clear media access control (MAC) addresses from the virtual private LAN service (VPLS) MAC table.

Options

none	Clear all MAC addresses from the VPLS table for all routing instances.
instance <i>instance-name</i>	(Optional) Clear all MAC addresses for a VPLS instance from the VPLS table.
interface <i>interface-name</i>	(Optional) Clear all MAC addresses for a VPLS interface from the VPLS table.

logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.
mac-address	(Optional) Clear a specific MAC address in a VPLS instance from the VPLS table.
vlan-id	(Optional) Clear MAC addresses on a specified VLAN (0 through 4095).

Required Privilege Level

maintenance

Output Fields

When you enter this command, you are provided feedback on the status of your request.

Sample Output

clear vpls mac-table

```
user@host> clear vpls mac-table
```

Release Information

Command introduced before Junos OS Release 9.5.

ping mpls l2circuit

IN THIS SECTION

- [Syntax | 1746](#)
- [Description | 1746](#)
- [Options | 1746](#)
- [Additional Information | 1748](#)

- [Required Privilege Level | 1748](#)
- [Output Fields | 1748](#)
- [Sample Output | 1748](#)
- [Release Information | 1749](#)

Syntax

```
ping mpls l2circuit (interface interface-name | virtual-circuit virtual-circuit-id
neighbor address)
<count count>
<destination address>
<detail>
<exp forwarding-class>
<logical-system (all | logical-system-name)>
reply-mode (application-level-control-channel | ip-udp | no-reply)
<size bytes>
<source source-address>
<sweep>
<v1>
```

Description

Check the operability of the MPLS Layer 2 circuit connections. Type Ctrl+c to interrupt a ping mpls l2circuit command.

NOTE: This command is not supported on EX4500 and EX4550 switches.

Options

count *count* (Optional) Number of ping requests to send. If *count* is not specified, five ping requests are sent. The range of values is 1 through 1,000,000. The default value is 5.

destination <i>address</i>	(Optional) Specify an address other than the default (127.0.0.1/32) for the ping echo requests. The address can be anything within the 127/8 subnet.						
detail	(Optional) Display detailed information about the echo requests sent and received.						
exp <i>forwarding-class</i>	(Optional) Value of the forwarding class for the MPLS ping packets.						
interface <i>interface-name</i>	Ping an interface configured for the Layer 2 circuit on the egress provider edge (PE) router.						
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on the specified logical system.						
reply-mode	(Optional) Reply mode for the ping request. This option has the following suboptions: <table> <tr> <td>application-level-control-channel</td><td>Reply using an application level control channel.</td></tr> <tr> <td>ip-udp</td><td>Reply using an IPv4 or IPv6 UDP packet.</td></tr> <tr> <td>no-reply</td><td>Do not reply to the ping request.</td></tr> </table>	application-level-control-channel	Reply using an application level control channel.	ip-udp	Reply using an IPv4 or IPv6 UDP packet.	no-reply	Do not reply to the ping request.
application-level-control-channel	Reply using an application level control channel.						
ip-udp	Reply using an IPv4 or IPv6 UDP packet.						
no-reply	Do not reply to the ping request.						
<div> <p>NOTE: The reply-mode option and its suboptions application-level-control-channel, ip-udp, and no-reply are also available in Junos OS Release 10.2R4 and 10.3R2.</p> </div>							
size <i>bytes</i>	(Optional) Size of the label-switched path (LSP) ping request packet (96 through 65468 bytes). Packets are 4-byte aligned. For example, If you enter a size of 97, 98, 99, or 100, the router or switch uses a size value of 100 bytes. If you enter a packet size that is smaller than the minimum size, an error message is displayed reminding you of the 96-byte minimum.						
source <i>source-address</i>	(Optional) IP address of the outgoing interface. This address is sent in the IP source address field of the ping request. If this option is not specified, the default address is usually the loopback interface (10.0).						
sweep	(Optional) Automatically determine the size of the maximum transmission unit (MTU).						
v1	(Optional) Use the type 9 Layer 2 circuit type, length, and value (TLV).						

virtual-circuit *virtual-circuit-id* neighbor address

Ping the virtual circuit identifier on the egress PE router or switch and the specified neighbor, testing the integrity of the Layer 2 circuit between the ingress and egress PE routers or switches.

Additional Information

You must configure MPLS at the [edit protocols mpls] hierarchy level on the egress PE router or switch (the router or switch receiving the MPLS echo packets) to ping a Layer 2 circuit.

In asymmetric MTU scenarios, the echo response might be dropped. For example, if the MTU from System A to System B is 1000 bytes, the MTU from System B to System A is 500 bytes, and the ping request packet size is 1000 bytes, the echo response is dropped because the PAD TLV is included in the echo response, making it too large.

Required Privilege Level

network

Output Fields

When you enter this command, you are provided feedback on the status of your request. An exclamation point (!) indicates that an echo reply was received. A period (.) indicates that an echo reply was not received within the timeout period. An x indicates that an echo reply was received with an error code. Packets with an error code are not counted in the received packets count. They are accounted for separately.

Sample Output

ping mpls l2circuit interface

```
user@host> ping mpls l2circuit interface so-1/0/0.1
Request for seq 1, to interface 69, labels <100000, 100208>, packet size 100
Reply for seq 1, return code: Egress-ok, time: 0.439 ms
```

ping mpls l2circuit virtual-circuit detail

```
user@host> ping mpls l2circuit virtual-circuit 200 neighbor 10.255.245.122/32 detail
Request for seq 1, to interface 68, labels <100048, 100128>, packet size 100
```

```
Reply for seq 1, return code: Egress-ok time: 0.539 ms
```

ping mpls l2circuit interface <interface-name> reply-mode

```
user@host> ping mpls l2circuit interface lt-1/2/0.21 reply-mode application-level-control-channel
!!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Release Information

Command introduced before Junos OS Release 7.4.

The size and sweep options were introduced in Junos OS Release 9.6.

The reply-mode option and its suboptions are introduced in Junos OS Release 10.4R1.

ping mpls l2vpn

IN THIS SECTION

- [Syntax | 1750](#)
- [Description | 1750](#)
- [Options | 1750](#)
- [Additional Information | 1751](#)
- [Required Privilege Level | 1752](#)
- [Output Fields | 1752](#)
- [Sample Output | 1752](#)
- [Release Information | 1753](#)

Syntax

```
ping mpls l2vpn (instance instance-name local-site-id local-site-id-number remote-site-id
remote-site-id-number | interface interface-name)
<bottom-label-ttl>
<count count>
<destination address>
<detail>
<exp forwarding-class>
<logical-system (all | logical-system-name)>
reply-mode (application-level-control-channel | ip-udp | no-reply)
<size bytes>
<source source-address>
<sweep>
```

Description

Check the operability of MPLS Layer 2 virtual private network (VPN) connections. Type Ctrl+c to interrupt a ping mpls l2vpn command.

Options

bottom-label-ttl	(Optional) Display the time-to-live value for the bottom label in the label stack.
count <i>count</i>	(Optional) Number of ping requests to send. If <i>count</i> is not specified, five ping requests are sent. The range of values is 1 through 1,000,000. The default value is 5.
destination <i>address</i>	(Optional) Specify an address other than the default (127.0.0.1/32) for the ping echo requests. The address can be anything within the 127/8 subnet.
detail	(Optional) Display detailed information about the echo requests sent and received.
exp <i>forwarding-class</i>	(Optional) Value of the forwarding class for the MPLS ping packets.
instance <i>instance-name</i> local-site-id <i>local-site-id-number</i> remote-site-id <i>remote-site-id-number</i>	Ping a combination of the Layer 2 VPN routing instance name, the local site identifier, and the remote site identifier, testing the integrity of the Layer 2 VPN circuit (specified by the identifiers) between the ingress and egress provider edge (PE) routers or switches.

interface <i>interface-name</i>	Ping an interface configured for the Layer 2 VPN on the egress PE router or switch.						
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on the specified logical system.						
reply-mode	(Optional) Reply mode for the ping request. This option has the following suboptions: <table data-bbox="534 531 1442 720"> <tr> <td>application-level-control-channel</td><td>Reply using an application level control channel.</td></tr> <tr> <td>ip-udp</td><td>Reply using an IPv4 or IPv6 UDP packet.</td></tr> <tr> <td>no-reply</td><td>Do not reply to the ping request.</td></tr> </table> <p>The reply-mode option and its suboptions application-level-control-channel, ip-udp, and no-reply are also available in Junos OS Release 10.2R4 and 10.3R2.</p>	application-level-control-channel	Reply using an application level control channel.	ip-udp	Reply using an IPv4 or IPv6 UDP packet.	no-reply	Do not reply to the ping request.
application-level-control-channel	Reply using an application level control channel.						
ip-udp	Reply using an IPv4 or IPv6 UDP packet.						
no-reply	Do not reply to the ping request.						
size <i>bytes</i>	(Optional) Size of the label-switched path (LSP) ping request packet (96 through 65468 bytes). Packets are 4-byte aligned. For example, If you enter a size of 97, 98, 99, or 100, the router or switch uses a size value of 100 bytes. If you enter a packet size that is smaller than the minimum size, an error message is displayed reminding you of the 96-byte minimum.						
source <i>source-address</i>	(Optional) IP address of the outgoing interface. This address is sent in the IP source address field of the ping request. If this option is not specified, the default address is usually the loopback interface (10.0).						
sweep	(Optional) Automatically determine the size of the maximum transmission unit (MTU).						

Additional Information

You must configure MPLS at the [edit protocols mpls] hierarchy level on the egress PE router or switch (the router or switch receiving the MPLS echo packets) to ping a Layer 2 circuit.

In asymmetric MTU scenarios, the echo response might be dropped. For example, if the MTU from System A to System B is 1000 bytes, the MTU from System B to System A is 500 bytes, and the ping request packet size is 1000 bytes, the echo response is dropped because the PAD TLV is included in the echo response, making it too large.

Required Privilege Level

network

Output Fields

When you enter this command, you are provided feedback on the status of your request. An exclamation point (!) indicates that an echo reply was received. A period (.) indicates that an echo reply was not received within the timeout period. An x indicates that an echo reply was received with an error code these packets are not counted in the received packets count. They are accounted for separately.

Sample Output

ping mpls l2vpn instance

```
user@host> ping mpls l2vpn instance vpn1 remote-site-id 1 local-site-id 2
!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

ping mpls l2vpn instance detail

```
user@host> ping mpls l2vpn instance vpn1 remote-site-id 1 local-site-id 2 detail
Request for seq 1, to interface 68, labels <800001, 100176>
Reply for seq 1, return code: Egress-ok
Request for seq 2, to interface 68, labels <800001, 100176>
Reply for seq 2, return code: Egress-ok
Request for seq 3, to interface 68, labels <800001, 100176>
Reply for seq 3, return code: Egress-ok
Request for seq 4, to interface 68, labels <800001, 100176>
Reply for seq 4, return code: Egress-ok
Request for seq 5, to interface 68, labels <800001, 100176>
Reply for seq 5, return code: Egress-ok

--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

ping mpls l2vpn interface <interface-name> reply-mode

```
user@host> ping mpls l2vpn interface lt-1/2/0.21 reply-mode ip-udp
!!!!
--- lsping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Release Information

Command introduced before Junos OS Release 7.4.

The size and sweep options were introduced in Junos OS Release 9.6.

The reply-mode option and its suboptions are introduced in Junos OS Release 10.4R1.

ping vpls instance

IN THIS SECTION

- [Syntax | 1753](#)
- [Description | 1754](#)
- [Options | 1754](#)
- [Additional Information | 1755](#)
- [Required Privilege Level | 1755](#)
- [Output Fields | 1755](#)
- [Sample Output | 1755](#)
- [Release Information | 1755](#)

Syntax

```
ping vpls instance instance-name destination-mac address source-ip address
<bd-name name>
<control-plane-response>
```

```

<count number>
<detail>
<learning-vlan-id number>
<logical-system logical-system-name>

```

Description

Check the operability of virtual private LAN service (VPLS) connections. Type Ctrl+c to interrupt a ping vpls instance command.

When you issue a ping vpls instance command, a chassis MAC address is drawn from the ingress PE router's pool of MAC addresses and used to create the VPLS ping packet. The ping packet is then forwarded to the egress PE router. When the egress PE router receives the ping packet, it learns the MAC address from the VPLS ping packet. The MAC address is added to the egress PE router's MAC table.

The ping vpls instance command relies on the LSP ping and trace infrastructure defined in RFC 4379, *Detecting Multi-Protocol Label Switched (MPLS) Data Plane Failures* and further enhancements defined in Internet draft draft-stokes-vkompella-ppvpn-hvpls-oam-02, *Testing Hierarchical Virtual Private LAN Services*.

Options

instance <i>instance-name</i>	Specify the name of the VPLS routing instance.
destination-mac <i>address</i>	Specify a destination MAC address for the ping echo requests.
source ip <i>address</i>	IP address of the outgoing interface.
bd-name <i>name</i>	(Optional) Name of the bridge domain.
control-plane-response	(Optional) Request VPLS OAM responses using the control plane.
count <i>number</i>	(Optional) Number of ping requests to send. If count is not specified, five ping requests are sent. The range of values is 1 through 1,000,000 . The default value is 5 .
detail	(Optional) Display detailed information about the echo requests sent and received.
learning-vlan-id <i>number</i>	(Optional) Specify a learning VLAN identifier for the ping echo requests. The range of values is 0 through 4094 .

logical-system *logical-system-name* (Optional) Specify a logical system name for the ping echo requests.

Additional Information

This statement is only supported on the MX Series routers, the M120 and M320 routers, and the T1600 router.

Required Privilege Level

network

Output Fields

When you enter this command, you are provided feedback on the status of your request. An exclamation point (!) indicates that an echo reply was received. A period (.) indicates that an echo reply was not received within the timeout period. An **x** indicates that an echo reply was received with an error code. Packets with an error code are not counted in the received packets count. They are accounted for separately.

Sample Output

ping vpls instance

```
user@host> ping vpls instance red destination-mac 00:89:67:1a:23:6f source-ip 10.255.17.138
! -> sample-router:red:ge-4/1/1.0
! -> sample-router:red:ge-4/1/1.0
! -> sample-router:red:ge-4/1/1.0
! -> sample-router:red:ge-4/1/1.0
! -> sample-router:red:ge-4/1/1.0

--- vpls ping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
```

Release Information

Command introduced in Junos OS Release 9.1.

request l2circuit-switchover

IN THIS SECTION

- [Syntax | 1756](#)
- [Description | 1756](#)
- [Options | 1756](#)
- [Required Privilege Level | 1757](#)
- [Output Fields | 1757](#)
- [Sample Output | 1757](#)
- [Release Information | 1757](#)

Syntax

```
request l2circuit-switchover
<logical-system (all | logical-system-name)>
<neighbor address>
<virtual-circuit-id identifier>
```

Description

Manually trigger a switch from the active pseudowire to the redundant pseudowire. This command can be useful when performing network maintenance.

Options

logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.
neighbor <i>address</i>	(Optional) Trigger a switch of all of the active pseudowire connections with the specified neighbor to their respective redundant pseudowires.
virtual-circuit-id <i>identifier</i>	(Optional) Trigger a switch from the active pseudowire connection of the specified Layer 2 circuit to its redundant pseudowire.

Required Privilege Level

maintenance

Output Fields

When you enter this command, you are provided feedback on the status of your request.

Sample Output

request l2circuit-switchover virtual-circuit-id

```
user@host>request l2circuit-switchover virtual-circuit-id 12
```

Release Information

Command introduced in Junos OS Release 9.2.

RELATED DOCUMENTATION

| [MPLS Feature Support on QFX Series and EX4600 Switches](#)

show interfaces lsi (Label-Switched Interface)

IN THIS SECTION

- [Syntax | 1758](#)
- [Description | 1758](#)
- [Options | 1758](#)
- [Required Privilege Level | 1758](#)
- [Output Fields | 1758](#)
- [Sample Output | 1761](#)
- [Release Information | 1762](#)

Syntax

```
show interfaces interface-type
<brief | detail | extensive | terse>
<descriptions>
<media>
<routing-instance instance-name>
<snmp-index snmp-index>
<statistics>
```

Description

Display status information about the specified label-switched interface (LSI).

Options

<i>interface-type</i>	On most routers, the interface type is <i>lt-fpc/pic/port</i> .
brief detail extensive terse	(Optional) Display the specified level of output.
descriptions	(Optional) Display interface description strings.
media	(Optional) Display media-specific information about network interfaces.
routing-instance <i>instance-name</i>	(Optional) Display information for the specified routing instance.
snmp-index <i>snmp-index</i>	(Optional) Display information for the specified SNMP index of the interface.
statistics	(Optional) Display static interface statistics.

Required Privilege Level

view

Output Fields

[Table 31 on page 1759](#) lists the output fields for the `show interfaces (logical tunnel)` command. Output fields are listed in the approximate order in which they appear.

Table 31: Logical Tunnel show interfaces Output Fields

Field Name	Field Description	Level of Output
Physical Interface		
Physical interface	Name of the physical interface.	All levels
Logical Interface		
Logical interface	Name of the logical interface.	All levels
Index	Logical interface index number, which reflects its initialization sequence.	detail extensive none
SNMP ifIndex	SNMP interface index number.	detail extensive none
Generation	Unique number for use by Juniper Networks technical support only.	detail extensive
Flags	Information about the logical interface. Possible values are described in the “Logical Interface Flags” section under Common Output Fields Description .	All levels
Encapsulation	Encapsulation on the logical interface.	All levels

Table 31: Logical Tunnel show interfaces Output Fields (Continued)

Field Name	Field Description	Level of Output
Traffic statistics	<p>Total number of bytes and packets received and transmitted on the logical interface. These statistics are the sum of the local and transit statistics. When a burst of traffic is received, the value in the output packet rate field might briefly exceed the peak cell rate. It takes awhile (generally, less than 1 second) for this counter to stabilize.</p> <ul style="list-style-type: none"> • Input bytes—Rate of bytes received on the interface. • Output bytes—Rate of bytes transmitted on the interface. • Input packets—Rate of packets received on the interface. • Output packets—Rate of packets transmitted on the interface. 	detail extensive
Local statistics	<p>Statistics for traffic received from and transmitted to the Routing Engine. When a burst of traffic is received, the value in the output packet rate field might briefly exceed the peak cell rate. It takes awhile (generally, less than 1 second) for this counter to stabilize.</p>	detail extensive
Transit statistics	<p>Statistics for traffic transiting the router. When a burst of traffic is received, the value in the output packet rate field might briefly exceed the peak cell rate. It takes awhile (generally, less than 1 second) for this counter to stabilize.</p>	detail extensive
Protocol	<p>Protocol family configured on the logical interface, such as iso, inet6, mpls.</p>	detail extensive none
MTU	<p>MTU size on the logical interface.</p>	detail extensive none
Generation	<p>Unique number for use by Juniper Networks technical support only.</p>	detail extensive
Flags	<p>Information about the protocol family flags. Possible values are described in the “Family Flags” section under Common Output Fields Description.</p>	detail extensive none

Sample Output

show interfaces lsi extensive

```
user@host> show interfaces lsi extensive
```

```
Physical interface: lsi
```

```
Logical interface lsi.84934656 (Index 363) (SNMP ifIndex 586) (Generation 194)
```

```
Flags: Up Point-To-Point SNMP-Traps 0x4000000 Encapsulation: LSI-NULL
```

```
Traffic statistics:
```

```
Input bytes : 0
```

```
Output bytes : 0
```

```
Input packets: 0
```

```
Output packets: 0
```

```
Local statistics:
```

```
Input bytes : 0
```

```
Output bytes : 0
```

```
Input packets: 0
```

```
Output packets: 0
```

```
Transit statistics:
```

```
Input bytes : 0 0 bps
```

```
Output bytes : 0 0 bps
```

```
Input packets: 0 0 pps
```

```
Output packets: 0 0 pps
```

```
Protocol vpls, MTU: Unlimited, Generation: 279, Route table: 10
```

```
Logical interface lsi.84934657 (Index 366) (SNMP ifIndex 589) (Generation 197)
```

```
Flags: Up Point-To-Point SNMP-Traps 0x4000000 Encapsulation: LSI-NULL
```

```
Traffic statistics:
```

```
Input bytes : 0
```

```
Output bytes : 0
```

```
Input packets: 0
```

```
Output packets: 0
```

```
Local statistics:
```

```
Input bytes : 0
```

```
Output bytes : 0
```

```
Input packets: 0
```

```
Output packets: 0
```

```
Transit statistics:
```

```
Input bytes : 0 0 bps
```

```
Output bytes : 0 0 bps
```

```
Input packets: 0 0 pps
```

```
Output packets:          0          0 pps
Protocol vpls, MTU: Unlimited, Generation: 282, Route table: 10
```

Release Information

Command introduced before Junos OS Release 7.4.

show l2circuit connections

IN THIS SECTION

- [Syntax | 1762](#)
- [Description | 1763](#)
- [Options | 1763](#)
- [Required Privilege Level | 1763](#)
- [Output Fields | 1763](#)
- [Sample Output | 1769](#)
- [Sample Output | 1769](#)
- [Sample Output | 1770](#)
- [Sample Output | 1771](#)
- [Release Information | 1772](#)

Syntax

```
show l2circuit connections
<brief | extensive | summary>
<down | up | up-down>
<history>
<interface interface-name>
<logical-system (all | logical-system-name)>
<neighbor neighbor>
<status>
```

Description

Display status information about Layer 2 virtual circuits from the local provider edge (PE) router to its neighbors.

Options

none	Display standard information about Layer 2 virtual circuits on all interfaces for all neighbors.
brief extensive summary	(Optional) Display the specified level of output. Use history to display information about connection history. Use status to display information about the connection and interface status.
down up up-down	(Optional) Display nonoperational, operational, or both kinds of connections.
history	(Optional) Display information about connection history.
interface <i>interface-name</i>	(Optional) Show all Layer 2 virtual circuits on an interface.
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system. This option is only supported on Junos OS.
neighbor <i>neighbor</i>	(Optional) IP address of a specific neighbor.
status	(Optional) Display information about the connection and interface status.

Required Privilege Level

view

Output Fields

[Table 32 on page 1764](#) lists the output fields for the `show l2circuit connections` command. Output fields are listed in the approximate order in which they appear.

Table 32: show l2circuit connections Output Fields

Field Name	Field Description
Layer-2 Circuit Connections	Displays the legends for connection and interface status.
Neighbor	Remote PE neighbor.
Interface	Logical PE-to-CE interface on which the virtual circuit is configured.
Type	VC type: rmt (remote) or loc (local).

Table 32: show l2circuit connections Output Fields (*Continued*)

Field Name	Field Description
Legend for connection status (St)	<p>Status of the virtual circuit connection:</p> <ul style="list-style-type: none"> • EI—The local virtual circuit interface is configured with an encapsulation that is not supported. • MM—The two routers do not agree on an MTU value, which causes an MTU mismatch. • EM—The encapsulation type received on this virtual circuit from the neighbor does not match the local virtual circuit interface encapsulation type. • CM—The two routers do not agree on a control word, which causes a control word mismatch. • VM—The remote and local VLAN IDs do not match across the Layer 2 circuit. • OL—No advertisement has been received for this virtual circuit from the neighbor. There is no outgoing label available for use by this virtual circuit. • NC—The interface is not configured as a CCC or TCC interface. • BK—The virtual circuit has switched to a backup connection. • CB—The remote PE router is advertising a different cell bundle from that configured on the local PE router. • LD—The connection to the local site is signaled down, because the CE-facing interface to the local site is down. • RD—The remote neighbor is down. It has signaled a problem using the pseudowire status code. • NP—The router detects that interface hardware is not present. The hardware may be offline, a PIC may not be of the desired type, or the interface may be configured in a different routing instance. • Dn—The virtual circuit is down. • VC-Dn—The virtual circuit is down because there is no tunnel LSP from the local PE router to the neighbor. • UP—The virtual circuit is operational.

Table 32: show l2circuit connections Output Fields (*Continued*)

Field Name	Field Description
	<ul style="list-style-type: none"> • CF—The router cannot find enough bandwidth to the remote router to satisfy the Layer 2 circuit bandwidth requirement. • IB—The bit rate is incompatible for Time Division Multiplexing (TDM). • TDM—TDM is not configured correctly. • ST—The virtual circuit has been switched to a standby connection. • SP—The virtual circuit connection is using a static pseudowire. • RS—The remote site is in a standby state. • XX—The virtual circuit is down for an unknown reason. This is a programming error.
Time last up	Date and time the virtual circuit was last operational.
# Up trans	Number of times the virtual circuit came up.
<i>local-interface-name</i>	Name of the local PE-to-CE interface.
Status	Status of the local interface.
Up	Interface is operational.
Dn	Interface is not operational.
NP	Not present. Interface does not exist.
DS	Disabled. Interface has been administratively disabled.
WE	Wrong encapsulation. The interface is not configured as CCC.
UN	Interface status is initialized.

Table 32: show l2circuit connections Output Fields (Continued)

Field Name	Field Description
Encapsulation	Encapsulation of the local interface.
Flow Label Transmit	Flow label transmit status.
Flow Label Receive	Flow label receive status.
Remote PE	Prefix of the remote PE router.
Negotiated control-word	Whether the use of the control word has been negotiated for this virtual circuit: Yes (Null) or No.
Incoming label	Label used by the remote side of the virtual circuit to send packets destined to the local side. This label is routed to the local virtual circuit interface.
Outgoing label	Label used by the local side of the virtual circuit to send packets to the remote side of the virtual circuit. Packets originated on the local virtual circuit interface are encapsulated with this label before being placed on the tunnel LSP to the neighbor for this virtual circuit. This label is allocated by the neighbor and is used in demultiplexing incoming packets destined for this virtual circuit.
Negotiated PW status TLV	Displays the pseudowire status type, length, and value (TLV). TLVs are a method of encoding variable-length or optional information. If the pseudowire status TLV is used, the corresponding local or neighbor PE router status code is also displayed.
local PW status code	If the pseudowire status TLV is used, displays the local PE router status code.
Neighbor PW status code	If the pseudowire status TLV is used, displays the neighbor PE router status code.
Local interface	Name of the local interface used for the Layer 2 circuit connection.
Status	Status of the local interface (Up or Down).

Table 32: show l2circuit connections Output Fields (Continued)

Field Name	Field Description
Encapsulation	Encapsulation configured for the local interface.
APS-active	Indicates that the interface belongs to the working circuit.
APS-inactive	Indicates that the interface belongs to the protect circuit.
Connection protection	Whether or not connection protection is configured for the Layer 2 circuit to the neighbor: Yes or No.
VC bandwidth	Bandwidth requirement of the Layer 2 circuit.
Time	Time at which the event occurred.
Connection History	<p>Event types logged in history.</p> <ul style="list-style-type: none"> • loc intf up—Local virtual circuit interface went up. • loc intf down—Local virtual circuit interface went down. • In lbl Update—Incoming label has been updated. • Out lbl Update—Outgoing label has been updated. • PE route changed—Route to PE router has been updated. • PE route down—Route to PE router is down. • rmt side marked—Remote side is marked. • VC Dn—Remote side indicated that its end of the virtual circuit is down (if the tunnel LSP from the remote side to the local side is down). • status update timer—Status update timer processing. It computes the state of the virtual circuit, and determines whether it should be advertised to or withdrawn from the remote side.

Sample Output

show l2circuit connections

```

user@host> show l2circuit connections
Layer-2 Circuit Connections:

Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch     Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC   TM -- TDM misconfiguration
BK -- Backup Connection         ST -- Standby Connection
CB -- rcvd cell-bundle size bad SP -- Static Pseudowire
LD -- local site signaled down  RS -- remote site standby
RD -- remote site signaled down HS -- hot standby
XX -- unknown

Legend for interface status
Up -- operational
Dn -- down
Neighbor: 10.255.245.51

```

Interface	Type	St	Time last up	# Up trans
ge-2/0/2.600(vc 5)	rmt	Up	Dec 7 18:11:18 2009	1

```

Remote PE: 10.255.245.51, Negotiated control-word: No
Incoming label: 299856, Outgoing label: 299808
Negotiated PW status TLV: No
Local interface: ge-2/0/2.600, Status: Up, Encapsulation: VLAN
Flow Label Transmit: No, Flow Label Receive: No
Auto-sensed or Programmed by XYZ

```

Sample Output

show l2circuit connections interface

```

user@host> show l2circuit connections interface t1-2/0/0:1:1.0
Layer-2 Circuit Connections:

```

Legend for connection status (St)

EI -- encapsulation invalid	NP -- interface h/w not present
MM -- mtu mismatch	Dn -- down
EM -- encapsulation mismatch	VC-Dn -- Virtual circuit Down
CM -- control-word mismatch	Up -- operational
VM -- vlan id mismatch	CF -- Call admission control failure
OL -- no outgoing label	IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC	TM -- TDM misconfiguration
BK -- Backup Connection	ST -- Standby Connection
CB -- rcvd cell-bundle size bad	SP -- Static Pseudowire
LD -- local site signaled down	RS -- remote site standby
RD -- remote site signaled down	HS -- hot standby
XX -- unknown	

Legend for interface status

Up -- operational

Dn -- down

Neighbor: 10.1.1.1

Interface	Type	St	Time last up	# Up trans
t1-2/0/0:1:1.0(vc 1)(SP)	rmt	Up	Apr 27 04:21:02 2011	1

Remote PE: 10.1.1.1, Negotiated control-word: Yes (Non-null)

Incoming label: 1010001, Outgoing label: 1000001

Negotiated PW status TLV: No

Local interface: t1-1/0/0:1:1.0, Status: Up, Encapsulation: SATOP-T1, APS-active

Local interface: t1-2/0/0:1:1.0, Status: Up, Encapsulation: SATOP-T1, APS-inactive

Sample Output

show l2circuit connections extensive

user@host>show l2circuit connections extensive

Layer-2 Circuit Connections:

Legend for connection status (St)

EI -- encapsulation invalid	NP -- interface h/w not present
MM -- mtu mismatch	Dn -- down
EM -- encapsulation mismatch	VC-Dn -- Virtual circuit Down
CM -- control-word mismatch	Up -- operational
VM -- vlan id mismatch	CF -- Call admission control failure
OL -- no outgoing label	IB -- TDM incompatible bitrate

```

NC -- intf encaps not CCC/TCC    TM -- TDM misconfiguration
BK -- Backup Connection          ST -- Standby Connection
CB -- rcvd cell-bundle size bad  SP -- Static Pseudowire
LD -- local site signaled down   RS -- remote site standby
RD -- remote site signaled down  HS -- hot standby
XX -- unknown

Legend for interface status
Up -- operational
Dn -- down
Neighbor: 10.255.49.149

```

Interface	Type	St	Time last up	# Up trans
ae0.0(vc 100)	rmt	Up	Aug 31 09:36:12 2009	1

```

Remote PE: 10.255.49.149, Negotiated control-word: Yes (Null)
Incoming label: 299824, Outgoing label: 299776
Negotiated PW status TLV: Yes
local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
Local interface: ae0.0, Status: Up, Encapsulation: ETHERNET
Connection protection: Yes
Connection History:
Aug 31 09:36:12 2009 status update timer
Aug 31 09:36:12 2009 PE route changed
Aug 31 09:36:12 2009 Out lbl Update                299776
Aug 31 09:36:12 2009 In lbl Update                 299824
Aug 31 09:36:12 2009 loc intf up                   ae0.0

```

Sample Output

show l2circuit connections extensive (Pseudowire Redundancy with Hot Standby)

```

user@host>show l2circuit connections extensive
Layer-2 Circuit Connections:

Legend for connection status (St)
EI -- encapsulation invalid      NP -- interface h/w not present
MM -- mtu mismatch              Dn -- down
EM -- encapsulation mismatch     VC-Dn -- Virtual circuit Down
CM -- control-word mismatch      Up -- operational
VM -- vlan id mismatch          CF -- Call admission control failure
OL -- no outgoing label         IB -- TDM incompatible bitrate
NC -- intf encaps not CCC/TCC    TM -- TDM misconfiguration

```

```

BK -- Backup Connection          ST -- Standby Connection
CB -- rcvd cell-bundle size bad  SP -- Static Pseudowire
LD -- local site signaled down   RS -- remote site standby
RD -- remote site signaled down  HS -- Hot-standby Connection
XX -- unknown

Legend for interface status
Up -- operational
Dn -- down
Neighbor: 192.0.2.101
  Interface          Type  St    Time last up          # Up trans
  ge-1/3/2.600(vc 1)  rmt   Up    Jan 24 11:00:26 2013      1
  Remote PE: 192.0.2.101, Negotiated control-word: Yes (Null)
  Incoming label: 299776, Outgoing label: 299776
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
  Local interface: ge-1/3/2.600, Status: Up, Encapsulation: VLAN
  Connection History:
    Jan 24 11:00:26 2013  status update timer
    Jan 24 11:00:26 2013  PE route changed
    Jan 24 11:00:26 2013  Out lbl Update                299776
    Jan 24 11:00:26 2013  In lbl Update                299776
    Jan 24 11:00:26 2013  loc intf up                  ge-1/3/2.600
Neighbor: 192.0.2.102
  Interface          Type  St    Time last up          # Up trans
  ge-1/3/2.600(vc 2)  rmt   HS    -----              ----
  Remote PE: 192.0.2.102, Negotiated control-word: Yes (Null)
  Incoming label: 299792, Outgoing label: 299776
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000020, Neighbor PW status code: 0x00000000
  Local interface: ge-1/3/2.600, Status: Up, Encapsulation: VLAN

```

Release Information

Command introduced before Junos OS Release 7.4.

Display enhancements in Junos OS Release 9.6.

Display enhancements in Junos OS Release 10.2.

Display enhancements in Junos OS Release 12.1.

Display enhancements in Junos OS Release 13.2.

show l2vpn connections

IN THIS SECTION

- [Syntax | 1773](#)
- [Description | 1773](#)
- [Options | 1773](#)
- [Required Privilege Level | 1774](#)
- [Output Fields | 1774](#)
- [Sample Output | 1779](#)
- [Release Information | 1783](#)

Syntax

```
show l2vpn connections
<brief | extensive>
<down | up | up-down>
<history>
<instance instance>
<instance-history>
<local-site local-site>
<logical-system (all | logical-system-name)>
<remote-site remote-site>
<status>
<summary>
```

Description

Display Layer 2 virtual private network (VPN) connections.

Options

none	Display all Layer 2 VPN connections for all routing instances.
-------------	--

brief extensive	(Optional) Display the specified level of output.
down up up-down	(Optional) Display nonoperational, operational, or both kinds of connections.
history	(Optional) Display information about connection history.
instance <i>instance</i>	(Optional) Display connections for the specified routing instance only.
instance-history	(Optional) Display information about connection history for a particular instance.
local-site <i>local-site</i>	(Optional) Display connections for the specified Layer 2 VPN local site name or ID only.
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.
remote-site <i>remote-site</i>	(Optional) Display connection for the specified Layer 2 VPN remote site ID only.
status	(Optional) Display information about the connection and interface status.
summary	(Optional) Display summary of all Layer 2 VPN connections information.

Required Privilege Level

view

Output Fields

[Table 33 on page 1774](#) lists the output fields for the `show l2vpn connections` command. Output fields are listed in the approximate order in which they appear.

Table 33: show l2vpn connections Output Fields

Field Name	Field Description
Instance	Name of Layer 2 VPN instance.

Table 33: show l2vpn connections Output Fields (Continued)

Field Name	Field Description
L2vpn-id	For BGP autodiscovery, a globally unique Layer 2 VPN community identifier for the instance.
Local-ID	BGP local-address assigned to the local routing device.
Local site	Name of local site.
Local source-attachment-id	For FEC 129, the VPWS source attachment identifier. The point-to-point nature of VPWS requires that you specify the source access individual identifier (SAII) and the target access individual identifier (TAII). This SAII-TAII pair defines a unique pseudowire between two PE devices.
Target-attachment-id	For FEC 129, the VPWS target attachment identifier. If the configured target identifier matches a source identifier advertised by a remote PE device by way of a BGP auto-discovery message, the pseudowire between that source-target pair is signaled. If there is no match between an advertised source identifier and the configured target identifier, the pseudowire is not established.
Interface name	Name of interface.
Remote Site ID	Remote site ID.
Label Offset	Numbers within the label block that are skipped to find the next label base.
Label-base	Advertises the first label in a block of labels. A remote PE router uses this first label when sending traffic toward the advertising PE router.
Range	Advertises the label block size.
status-vector	Bit vector advertising the state of local PE-CE circuits to remote PE routers. A bit value of 0 indicates that the local circuit and LSP tunnel to the remote PE router are up, whereas a value of 1 indicates either one or both are down.

Table 33: show l2vpn connections Output Fields (Continued)

Field Name	Field Description
connection-site	Name of the connection site.
Type	Type of connection: loc (local) or rmt (remote).
St	Status of the connection. (For a list of possible values, see the Legend for connection status (St) field.)
Time last up	Time that the connection was last in the Up condition.
# Up trans	Number of transitions from Down to Up condition.
Local circuit	Address and status of local circuit.
Remote circuit	Address and status of remote circuit.

Table 33: show l2vpn connections Output Fields (Continued)

Field Name	Field Description
St	<p>Status of the Layer 2 VPN connection (corresponds with Legend for Connection Status):</p> <ul style="list-style-type: none"> • EI—The local Layer 2 VPN interface is configured with an encapsulation that is not supported. • EM—The encapsulation type received on this Layer 2 VPN connection from the neighbor does not match the local Layer 2 VPN connection interface encapsulation type. • VC-Dn—The virtual circuit is currently down. • CM—The two routers do not agree on a control word, which causes a control word mismatch. • CN—The virtual circuit is not provisioned properly. • OR—The label associated with the virtual circuit is out of range. • OL—No advertisement has been received for this virtual circuit from the neighbor. There is no outgoing label available for use by this virtual circuit. • LD—All of the CE-facing interfaces to the local site are down. Therefore, the connection to the local site is signaled as down to the other PE routers. No pseudowires can be established. • RD—All the interfaces to the remote neighbor are down. Therefore, the remote site has been signaled as down to the other PE routers. No pseudowires can be established. • LN—The local site has lost path selection to the remote site and therefore no pseudowires can be established from this local site. • RN—The remote site has lost path selection to a local site or other remote site and therefore no pseudowires are established to this remote site. • XX—The Layer 2 VPN connection is down for an unknown reason. This is a programming error. • NC—The interface encapsulation is not configured as an appropriate CCC, TCC, or Layer 2 VPN encapsulation. • WE—The encapsulation configured for the interface does not match the encapsulation configured for the associated connection within the Layer 2 VPN routing instance.

Table 33: show l2vpn connections Output Fields (Continued)

Field Name	Field Description
	<ul style="list-style-type: none"> • NP—The router detects that interface hardware is not present. The hardware might be offline, a PIC might not be of the desired type, or the interface might be configured in a different routing instance. • ->—Only the outbound connection is up. • <-—Only the inbound connection is up. • Up—The Layer 2 VPN connection is operational. • Dn—The Layer 2 VPN connection is down. • CF—The router cannot find enough bandwidth to the remote router to satisfy the Layer 2 VPN connection bandwidth requirement. • SC—The local site identifier matches the remote site identifier. No pseudowire can be established between these two sites. You should configure different values for the local and remote site identifiers. • LM—The local site identifier is not the minimum designated, meaning it is not the lowest. There is another local site with a lower site identifier. Pseudowires are not being established to this local site, and the associated local site identifier is not being used to distribute Layer 2 VPN label blocks. However, this is not an error state. Traffic continues to be forwarded to the PE router interfaces connected to the local sites when the local sites are in this state. • RM—The remote site identifier is not the minimum designated, meaning it is not the lowest. There is another remote site connected to the same PE router which has lower site identifier. The PE router cannot establish a pseudowire to this remote site and the associated remote site identifier cannot be used to distribute VPLS label blocks. However, this is not an error state. Traffic can continue to be forwarded to the PE router interface connected to this remote site when the remote site is in this state. • IL—The incoming packets for the Layer 2 VPN connection have no MPLS label.
Remote PE	Address of the remote provider edge router.
Incoming label	Name of the incoming label.

Table 33: show l2vpn connections Output Fields (Continued)

Field Name	Field Description
Outgoing label	Name of the outgoing label.
Egress Protection	Whether the given PVC is protected by connection protection logic using egress protection for BGP signaled layer 2 services.
Flow Label Receive	Capability to pop the flow label in the receive direction to the remote provider edge (PE) router
Flow Label Transmit	Capability to push the flow label in the transmit direction to the provider edge (PE) router
Time	Date and time of Layer 2 VPN connection event.
Event	Type of event.
Interface/Lbl/PE	Interface, label, or PE router.

Sample Output

show l2vpn connections

```

user@host> show l2vpn connections
L2VPN Connections :
Instance : vpna
Edge protection: Not-Primary
Local site: 2 (ce-2)
offset: 1, range: 3, label-base: 32768
  connection-site      Type St  Time last up      # Up trans
  3 (3)                loc  Up   Jul 18 20:45:46 2001      1
    Local circuit: fe-0/0/0.1, Status: Up
    Remote circuit: fe-0/0/3.0, Status: Up
  1                    rmt  Up   Jul 18 21:47:25 2001      1
    Local circuit: fe-0/0/0.0, Status: Up

```

```

Remote PE: 192.0.2.1
Incoming label: 32768, Outgoing label: 32769
Local site: 3 (ce-3)
offset: 1, range: 2, label-base: 33792
  connection-site      Type  St  Time last up      # Up trans
  2 (ce-b)             loc   Up   Jul 18 20:45:46 2001      1
    Local circuit: fe-0/0/0.1, Status: Up
    Remote circuit: fe-0/0/3.0, Status: Up
  1                     rmt   Up   Jul 18 21:47:25 2001      1
    Local circuit: fe-0/0/3.1, Status: Up
    Remote PE: 192.0.2.1
    Incoming label: 33792, Outgoing label: 32770

```

show l2vpn connections

```
user@host> show l2vpn connections
```

Layer-2 VPN connections:

Legend for connection status (St)

```

EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned    <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch             MI -- Mesh-Group ID not available
BK -- Backup connection        ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch

```

Legend for interface status

```
Up -- operational
```

Dn -- down

Instance: l2vpn-inst

Edge protection: Not-Primary

Local site: pe2 (2)

connection-site	Type	St	Time last up	# Up trans
1	rmt	Up	Jun 22 14:46:50 2015	1

Remote PE: 10.255.255.1, Negotiated control-word: Yes (Null)

Incoming label: 800002, Outgoing label: 800003

Local interface: ge-0/0/1.300, Status: Up, Encapsulation: VLAN

Flow Label Transmit: Yes, Flow Label Receive: Yes

show l2vpn connections extensive

```
user@host> show l2vpn connections extensive
```

L2VPN Connections:

Instance: vpn-a

Edge protection: Not-Primary

Local site: ce-a (1)

Interface name	Remote Site ID
fe-0/0/0.0	2

Label Offset	Offset	Range
32768	1	2

connection-site	Type	St	Time last up	# Up trans
2	rmt	Up	Aug 3 00:08:14 2001	1

Local circuit: fe-0/0/0.0, Status: Up

Remote PE: 192.168.24.1

Incoming label: 32769, Outgoing label: 32768

Egress Protection: Yes

Time	Event	Interface/Lbl/PE
Aug 3 00:08:14 2001	PE route up	
Aug 3 00:08:14 2001	Out lbl Update	32768
Aug 3 00:08:14 2001	In lbl Update	32769
Aug 3 00:08:14 2001	ckt0 up	fe-0/0/0.0

show l2vpn connections extensive (VPWS)

```
user@host> show l2vpn connections
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid NC -- interface encapsulation not CCC/TCC/VPLS
 EM -- encapsulation mismatch WE -- interface and instance encaps not same
 VC-Dn -- Virtual circuit down NP -- interface hardware not present
 CM -- control-word mismatch -> -- only outbound connection is up
 CN -- circuit not provisioned <- -- only inbound connection is up
 OR -- out of range Up -- operational
 OL -- no outgoing label Dn -- down
 LD -- local site signaled down CF -- call admission control failure
 RD -- remote site signaled down SC -- local and remote site ID collision
 LN -- local site not designated LM -- local site ID not minimum designated
 RN -- remote site not designated RM -- remote site ID not minimum designated
 XX -- unknown connection status IL -- no incoming label
 MM -- MTU mismatch MI -- Mesh-Group ID not available
 BK -- Backup connection ST -- Standby connection
 PF -- Profile parse failure PB -- Profile busy
 RS -- remote site standby SN -- Static Neighbor
 LB -- Local site not best-site RB -- Remote site not best-site
 VM -- VLAN ID mismatch

Legend for interface status

Up -- operational
 Dn -- down

Instance: FEC129-VPWS

L2vpn-id: 100:100

Number of local interfaces: 1

Number of local interfaces up: 1

ge-2/0/5.0

Local source-attachment-id: 1 (ONE)

Target-attachment-id	Type	St	Time last up	# Up trans
2	rmt	Up	Nov 28 16:16:14 2012	1

Remote PE: 198.51.100.2, Negotiated control-word: No

Incoming label: 299792, Outgoing label: 299792

Local interface: ge-2/0/5.0, Status: Up, Encapsulation: ETHERNET

Connection History:

Nov 28 16:16:14 2012	status update timer
Nov 28 16:16:14 2012	PE route changed
Nov 28 16:16:14 2012	Out lbl Update 299792
Nov 28 16:16:14 2012	In lbl Update 299792
Nov 28 16:16:14 2012	loc intf up ge-2/0/5.0

Release Information

Command introduced before Junos OS Release 7.4.

instance-history option introduced in Junos OS Release 12.3R2.

show pim snooping interfaces

IN THIS SECTION

- [Syntax | 1783](#)
- [Description | 1783](#)
- [Options | 1784](#)
- [Required Privilege Level | 1784](#)
- [Output Fields | 1784](#)
- [Sample Output | 1785](#)
- [Release Information | 1787](#)

Syntax

```
show pim snooping interfaces
<brief | detail>
<instance instance-name>
<interface interface-name>
<logical-system logical-system-name>
<vlan-id vlan-identifier>
```

Description

Display information about PIM snooping interfaces.

Options

none	Display detailed information.
brief detail	(Optional) Display the specified level of output.
instance <i><instance-name></i>	(Optional) Display PIM snooping interface information for the specified routing instance.
interface <i><interface-name></i>	(Optional) Display PIM snooping information for the specified interface only.
logical-system <i>logical-system-name</i>	(Optional) Display information about a particular logical system, or type 'all'.
vlan-id <i><vlan-identifier></i>	(Optional) Display PIM snooping interface information for the specified VLAN.

Required Privilege Level

view

Output Fields

[Table 34 on page 1784](#) lists the output fields for the `show pim snooping interface` command. Output fields are listed in the approximate order in which they appear.

Table 34: show pim snooping interface Output Fields

Field Name	Field Description	Level of Output
Instance	Routing instance for PIM snooping.	All levels
Learning-Domain	Learning domain for snooping.	All levels
Name	Router interfaces that are part of this learning domain.	All levels
State	State of the interface: Up, or Down.	All levels

Table 34: show pim snooping interface Output Fields (Continued)

Field Name	Field Description	Level of Output
IP-Version	Version of IP used: 4 for IPv4, or 6 for IPv6.	All levels
NbrCnt	Number of neighboring routers connected through the specified interface.	All levels
DR address	IP address of the designated router.	All levels

Sample Output

show pim snooping interfaces

```
user@host> show pim snooping interfaces
```

```
Instance: vpls1
```

```
Learning-Domain: vlan-id 10
```

```
Name State IP-Version NbrCnt
```

```
ge-1/3/1.10 Up 4 1
```

```
ge-1/3/3.10 Up 4 1
```

```
ge-1/3/5.10 Up 4 1
```

```
ge-1/3/7.10 Up 4 1
```

```
DR address: 192.0.2.5
```

```
DR flooding is ON
```

```
Learning-Domain: vlan-id 20
```

```
Name State IP-Version NbrCnt
```

```
ge-1/3/1.20 Up 4 1
```

```
ge-1/3/3.20 Up 4 1
```

```
ge-1/3/5.20 Up 4 1
```

```
ge-1/3/7.20 Up 4 1
```

```
DR address: 192.0.2.6
```

```
DR flooding is ON
```

show pim snooping interfaces instance vpls1

```
user@host> show pim snooping interfaces instance vpls1
```

```
Instance: vpls1
```

```
Learning-Domain: vlan-id 10
```

```
Name State IP-Version NbrCnt
```

```
ge-1/3/1.10 Up 4 1
```

```
ge-1/3/3.10 Up 4 1
```

```
ge-1/3/5.10 Up 4 1
```

```
ge-1/3/7.10 Up 4 1
```

```
DR address: 192.0.2.5
```

```
DR flooding is ON
```

```
Learning-Domain: vlan-id 20
```

```
Name State IP-Version NbrCnt
```

```
ge-1/3/1.20 Up 4 1
```

```
ge-1/3/3.20 Up 4 1
```

```
ge-1/3/5.20 Up 4 1
```

```
ge-1/3/7.20 Up 4 1
```

```
DR address: 192.0.2.6
```

```
DR flooding is ON
```

show pim snooping interfaces interface <interface-name>

```
user@host> show pim snooping interfaces interface ge-1/3/1.10
```

```
Instance: vpls1
```

```
Learning-Domain: vlan-id 10
```

```
Name State IP-Version NbrCnt
```

```
ge-1/3/1.10 Up 4 1
```

```
DR address: 192.0.2.5
```

```
DR flooding is ON
```

```
Learning-Domain: vlan-id 20
```

```
DR address: 192.0.2.6
```

```
DR flooding is ON
```

show pim snooping interfaces vlan-id <vlan-id>

```
user@host> show pim snooping interfaces vlan-id 10
Instance: vpls1
Learning-Domain: vlan-id 10

Name State IP-Version NbrCnt
ge-1/3/1.10 Up 4 1
ge-1/3/3.10 Up 4 1
ge-1/3/5.10 Up 4 1
ge-1/3/7.10 Up 4 1
DR address: 192.0.2.5
DR flooding is ON
```

Release Information

Command introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[PIM Snooping for VPLS](#)

show pim snooping join

IN THIS SECTION

- [Syntax | 1788](#)
- [Description | 1788](#)
- [Options | 1788](#)
- [Required Privilege Level | 1788](#)
- [Output Fields | 1788](#)
- [Sample Output | 1791](#)
- [Release Information | 1793](#)

Syntax

```
show pim snooping join
<brief | detail | extensive>
<instance instance-name>
<logical-system logical-system-name>
<vlan-id vlan-id>
```

Description

Display information about Protocol Independent Multicast (PIM) snooping joins.

Options

none	Display detailed information.
brief detail extensive	(Optional) Display the specified level of output.
instance <i>instance-name</i>	(Optional) Display PIM snooping join information for the specified routing instance.
logical-system <i>logical-system-name</i>	(Optional) Display information about a particular logical system, or type 'all'.
vlan-id <i>vlan-identifier</i>	(Optional) Display PIM snooping join information for the specified VLAN.

Required Privilege Level

view

Output Fields

[Table 35 on page 1789](#) lists the output fields for the show pim snooping join command. Output fields are listed in the approximate order in which they appear.

Table 35: show pim snooping join Output Fields

Field Name	Field Description	Level of Output
Instance	Routing instance for PIM snooping.	All levels
Learning-Domain	Learning domain for PIM snooping.	All levels
Group	Multicast group address.	All levels
Source	Multicast source address: <ul style="list-style-type: none"> • * (wildcard value) • <ipv4-address> • <ipv6-address> 	All levels
Flags	PIM flags: <ul style="list-style-type: none"> • bidirectional—Bidirectional mode entry. • dense—Dense mode entry. • rptree—Entry is on the rendezvous point tree. • sparse—Sparse mode entry. • spt—Entry is on the shortest-path tree for the source. • wildcard—Entry is on the shared tree. 	All levels

Table 35: show pim snooping join Output Fields (Continued)

Field Name	Field Description	Level of Output
Upstream state	<p>Information about the upstream interface:</p> <ul style="list-style-type: none"> Join to RP—Sending a join to the rendezvous point. Join to Source—Sending a join to the source. Local RP—Sending neither join messages nor prune messages toward the RP, because this router is the rendezvous point. Local Source—Sending neither join messages nor prune messages toward the source, because the source is locally attached to this routing device. Prune to RP—Sending a prune to the rendezvous point. Prune to Source—Sending a prune to the source. <p>NOTE: RP group range entries have None in the Upstream state field because RP group ranges do not trigger actual PIM join messages between routers.</p>	All levels
Upstream neighbor	<p>Information about the upstream neighbor: Direct, Local, Unknown, or a specific IP address.</p> <p>For bidirectional PIM, Direct means that the interface is directly connected to a subnet that contains a phantom RP address.</p>	All levels
Upstream port	<p>RPF interface toward the source address for the source-specific state (S,G) or toward the rendezvous point (RP) address for the non-source-specific state (*,G).</p> <p>For bidirectional PIM, RP Link means that the interface is directly connected to a subnet that contains a phantom RP address.</p>	All levels
Downstream port	Information about downstream interfaces.	extensive
Downstream neighbors	Address of the downstream neighbor.	extensive
Timeout	Time remaining until the downstream join state is updated (in seconds).	extensive

Sample Output

show pim snooping join

```
user@host> show pim snooping join
Instance: vpls1

Learning-Domain: vlan-id 10
Group: 198.51.100.2
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 192.0.2.4, port: ge-1/3/5.10

Learning-Domain: vlan-id 20
Group: 198.51.100.3
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 203.0.113.4, port: ge-1/3/5.20
```

show pim snooping join extensive

```
user@host> show pim snooping join extensive
Instance: vpls1
Learning-Domain: vlan-id 10

Group: 198.51.100.2
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 192.0.2.4, port: ge-1/3/5.10
Downstream port: ge-1/3/1.10
Downstream neighbors:
192.0.2.2 State: Join Flags: SRW Timeout: 166

Learning-Domain: vlan-id 20
Group: 198.51.100.3
Source: *
```

```

Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 203.0.113.4, port: ge-1/3/5.20
Downstream port: ge-1/3/3.20
Downstream neighbors:
203.0.113.3 State: Join Flags: SRW Timeout: 168

```

show pim snooping join instance

```

user@host> show pim snooping join instance vpls1
Instance: vpls1

Learning-Domain: vlan-id 10
Group: 198.51.100.2
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 192.0.2.4, port: ge-1/3/5.10

Learning-Domain: vlan-id 20
Group: 198.51.100.3
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 203.0.113.4, port: ge-1/3/5.20

```

show pim snooping join vlan-id

```

user@host> show pim snooping join vlan-id 10
Instance: vpls1
Learning-Domain: vlan-id 10
Group: 198.51.100.2
Source: *
Flags: sparse,rptree,wildcard
Upstream state: None
Upstream neighbor: 192.0.2.4, port: ge-1/3/5.10

```

Release Information

Command introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

| [PIM Snooping for VPLS](#)

show pim snooping neighbors

IN THIS SECTION

- [Syntax | 1793](#)
- [Description | 1793](#)
- [Options | 1794](#)
- [Required Privilege Level | 1794](#)
- [Output Fields | 1794](#)
- [Sample Output | 1796](#)
- [Release Information | 1799](#)

Syntax

```
show pim snooping neighbors  
<brief | detail>  
<instance instance-name>  
<interface interface-name>  
<logical-system logical-system-name>  
<vlan-id vlan-identifier>
```

Description

Display information about Protocol Independent Multicast (PIM) snooping neighbors.

Options

none	Display detailed information.
brief detail	(Optional) Display the specified level of output.
instance <i>instance-name</i>	(Optional) Display PIM snooping neighbor information for the specified routing instance.
interface <i>interface-name</i>	(Optional) Display information for the specified PIM snooping neighbor interface.
logical-system <i>logical-system-name</i>	(Optional) Display information about a particular logical system, or type 'all'.
vlan-id <i>vlan-identifier</i>	(Optional) Display PIM snooping neighbor information for the specified VLAN.

Required Privilege Level

view

Output Fields

[Table 36 on page 1794](#) lists the output fields for the `show pim snooping neighbors` command. Output fields are listed in the approximate order in which they appear.

Table 36: show pim snooping neighbors Output Fields

Field Name	Field Description	Level of Output
Instance	Routing instance for PIM snooping.	All levels
Learning-Domain	Learning domain for PIM snooping.	All levels
Interface	Router interface for which PIM snooping neighbor details are displayed.	All levels

Table 36: show pim snooping neighbors Output Fields (Continued)

Field Name	Field Description	Level of Output
Option	PIM snooping options available on the specified interface: <ul style="list-style-type: none"> • H = Hello Option Holdtime • P = Hello Option DR Priority • L = Hello Option LAN Prune Delay • G = Generation Identifier • T = Tracking Bit 	All levels
Uptime	Time the neighbor has been operational since the PIM process was last initialized, in the format <i>dd:hh:mm:ss</i> ago for less than a week and <i>nwnd:hh:mm:ss</i> ago for more than a week.	All levels
Neighbor addr	IP address of the PIM snooping neighbor connected through the specified interface.	All levels
Address	IP address of the specified router interface.	All levels
Hello Option Holdtime	Time for which the neighbor is available, in seconds. The range of values is 0 through 65,535.	detail
Hello Option DR Priority	Designated router election priority. The range of values is 0 through 4294967295. NOTE: By default, every PIM interface has an equal probability (priority 1) of being selected as the DR.	detail
Hello Option Generation ID	9-digit or 10-digit number used to tag hello messages.	detail
Hello Option LAN Prune Delay	Time to wait before the neighbor receives prune messages, in the format delay <i>nnn</i> ms override <i>nnnn</i> ms.	detail

Sample Output

show pim snooping neighbors

```

user@host> show pim snooping neighbors
B = Bidirectional Capable, G = Generation Identifier,
H = Hello Option Holdtime, L = Hello Option LAN Prune Delay,
P = Hello Option DR Priority, T = Tracking Bit

Instance: vpls1
Learning-Domain: vlan-id 10

Interface Option Uptime Neighbor addr
ge-1/3/1.10 HPLGT 00:43:33 192.0.2.2
ge-1/3/3.10 HPLGT 00:43:33 192.0.2.3
ge-1/3/5.10 HPLGT 00:43:33 192.0.2.4
ge-1/3/7.10 HPLGT 00:43:33 192.0.2.5

Learning-Domain: vlan-id 20

Interface Option Uptime Neighbor addr
ge-1/3/1.20 HPLGT 00:43:33 192.0.2.12
ge-1/3/3.20 HPLGT 00:43:33 192.0.2.13
ge-1/3/5.20 HPLGT 00:43:33 192.0.2.14
ge-1/3/7.20 HPLGT 00:43:33 192.0.2.15

```

show pim snooping neighbors detail

```

user@host> show pim snooping neighbors detail
Instance: vpls1
Learning-Domain: vlan-id 10

Interface: ge-1/3/1.10
Address: 192.0.2.2
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 83 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 830908833
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

```

Interface: ge-1/3/3.10
Address: 192.0.2.3
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 97 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 2056520742
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

Interface: ge-1/3/5.10
Address: 192.0.2.4
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 81 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 1152066227
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

Interface: ge-1/3/7.10
Address: 192.0.2.5
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 96 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 1113200338
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported
Learning-Domain: vlan-id 20

Interface: ge-1/3/1.20
Address: 192.0.2.12
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 81 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 963205167
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

Interface: ge-1/3/3.20
Address: 192.0.2.13
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 104 remaining
Hello Option DR Priority: 1


```

Hello Option Generation ID: 166921538
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

```

```

Interface: ge-1/3/5.20
Address: 192.0.2.14
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 88 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 789422835
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

```

```

Interface: ge-1/3/7.20
Address: 192.0.2.15
Uptime: 00:44:51
Hello Option Holdtime: 105 seconds 88 remaining
Hello Option DR Priority: 1
Hello Option Generation ID: 1563649680
Hello Option LAN Prune Delay: delay 500 ms override 2000 ms
Tracking is supported

```

show pim snooping neighbors instance

```

user@host> show pim snooping neighbors instance vpls1
B = Bidirectional Capable, G = Generation Identifier,
H = Hello Option Holdtime, L = Hello Option LAN Prune Delay,
P = Hello Option DR Priority, T = Tracking Bit

```

```

Instance: vpls1
Learning-Domain: vlan-id 10

```

```

Interface Option Uptime Neighbor addr
ge-1/3/1.10 HPLGT 00:46:03 192.0.2.2
ge-1/3/3.10 HPLGT 00:46:03 192.0.2.3
ge-1/3/5.10 HPLGT 00:46:03 192.0.2.4
ge-1/3/7.10 HPLGT 00:46:03 192.0.2.5

```

```

Learning-Domain: vlan-id 20

```

```
Interface Option Uptime Neighbor addr
ge-1/3/1.20 HPLGT 00:46:03 192.0.2.12
ge-1/3/3.20 HPLGT 00:46:03 192.0.2.13
ge-1/3/5.20 HPLGT 00:46:03 192.0.2.14
ge-1/3/7.20 HPLGT 00:46:03 192.0.2.15
```

show pim snooping neighbors interface

```
user@host> show pim snooping neighbors interface ge-1/3/1.20
B = Bidirectional Capable, G = Generation Identifier,
H = Hello Option Holdtime, L = Hello Option LAN Prune Delay,
P = Hello Option DR Priority, T = Tracking Bit

Instance: vpls1
Learning-Domain: vlan-id 10
Learning-Domain: vlan-id 20

Interface Option Uptime Neighbor addr
ge-1/3/1.20 HPLGT 00:48:04 192.0.2.12
```

show pim snooping neighbors vlan-id

```
user@host> show pim snooping neighbors vlan-id 10
B = Bidirectional Capable, G = Generation Identifier,
H = Hello Option Holdtime, L = Hello Option LAN Prune Delay,
P = Hello Option DR Priority, T = Tracking Bit

Instance: vpls1
Learning-Domain: vlan-id 10

Interface Option Uptime Neighbor addr
ge-1/3/1.10 HPLGT 00:49:12 192.0.2.2
ge-1/3/3.10 HPLGT 00:49:12 192.0.2.3
ge-1/3/5.10 HPLGT 00:49:12 192.0.2.4
ge-1/3/7.10 HPLGT 00:49:12 192.0.2.5
```

Release Information

Command introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[Configuring Interface Priority for PIM Designated Router Selection](#)[Modifying the PIM Hello Interval](#)[PIM Snooping for VPLS](#)[show pim neighbors](#)

show pim snooping statistics

IN THIS SECTION

- [Syntax | 1800](#)
- [Description | 1800](#)
- [Options | 1801](#)
- [Required Privilege Level | 1801](#)
- [Output Fields | 1801](#)
- [Sample Output | 1803](#)
- [Release Information | 1806](#)

Syntax

```
show pim snooping statistics  
<instance instance-name>  
<interface interface-name>  
<logical-system logical-system-name>  
<vlan-id vlan-id>
```

Description

Display Protocol Independent Multicast (PIM) snooping statistics.

Options

none	Display PIM statistics.
instance <i>instance-name</i>	(Optional) Display statistics for a specific routing instance enabled by Protocol Independent Multicast (PIM) snooping.
interface <i>interface-name</i>	(Optional) Display statistics about the specified interface for PIM snooping.
logical-system <i>logical-system-name</i>	(Optional) Display information about a particular logical system, or type 'all'.
vlan-id <i>vlan-identifier</i>	(Optional) Display PIM snooping statistics information for the specified VLAN.

Required Privilege Level

view

Output Fields

[Table 37 on page 1801](#) lists the output fields for the `show pim snooping statistics` command. Output fields are listed in the approximate order in which they appear.

Table 37: show pim snooping statistics Output Fields

Field Name	Field Description	Level of Output
Instance	Routing instance for PIM snooping.	All levels
Learning-Domain	Learning domain for PIM snooping.	All levels
Tx J/P messages	Total number of transmitted join/prune packets.	All levels
RX J/P messages	Total number of received join/prune packets.	All levels

Table 37: show pim snooping statistics Output Fields (Continued)

Field Name	Field Description	Level of Output
Rx J/P messages -- seen	Number of join/prune packets seen but not received on the upstream interface.	All levels
Rx J/P messages -- received	Number of join/prune packets received on the downstream interface.	All levels
Rx Hello messages	Total number of received hello packets.	All levels
Rx Version Unknown	Number of packets received with an unknown version number.	All levels
Rx Neighbor Unknown	Number of packets received from an unknown neighbor.	All levels
Rx Upstream Neighbor Unknown	Number of packets received with unknown upstream neighbor information.	All levels
Rx Bad Length	Number of packets received containing incorrect length information.	All levels
Rx J/P Busy Drop	Number of join/prune packets dropped while the router is busy.	All levels
Rx J/P Group Aggregate 0	Number of join/prune packets received containing the aggregate group information.	All levels
Rx Malformed Packet	Number of malformed packets received.	All levels
Rx No PIM Interface	Number of packets received without the interface information.	All levels
Rx No Upstream Neighbor	Number of packets received without upstream neighbor information.	All levels

Table 37: show pim snooping statistics Output Fields (Continued)

Field Name	Field Description	Level of Output
Rx Unknown Hello Option	Number of hello packets received with unknown options.	All levels

Sample Output

show pim snooping statistics

```
user@host> show pim snooping statistics
```

```
Instance: vpls1
```

```
Learning-Domain: vlan-id 10
```

```
Tx J/P messages 0
```

```
RX J/P messages 8
```

```
Rx J/P messages -- seen 0
```

```
Rx J/P messages -- received 8
```

```
Rx Hello messages 37
```

```
Rx Version Unknown 0
```

```
Rx Neighbor Unknown 0
```

```
Rx Upstream Neighbor Unknown 0
```

```
Rx Bad Length 0
```

```
Rx J/P Busy Drop 0
```

```
Rx J/P Group Aggregate 0
```

```
Rx Malformed Packet 0
```

```
Rx No PIM Interface 0
```

```
Rx No Upstream Neighbor 0
```

```
Rx Bad Length 0
```

```
Rx Neighbor Unknown 0
```

```
Rx Unknown Hello Option 0
```

```
Rx Malformed Packet 0
```

```
Learning-Domain: vlan-id 20
```

```
Tx J/P messages 0
```

```
RX J/P messages 2
```

```
Rx J/P messages -- seen 0
```

```

Rx J/P messages -- received 2
Rx Hello messages 39
Rx Version Unknown 0
Rx Neighbor Unknown 0
Rx Upstream Neighbor Unknown 0
Rx Bad Length 0
Rx J/P Busy Drop 0
Rx J/P Group Aggregate 0
Rx Malformed Packet 0
Rx No PIM Interface 0
Rx No Upstream Neighbor 0
Rx Bad Length 0
Rx Neighbor Unknown 0
Rx Unknown Hello Option 0
Rx Malformed Packet 0

```

show pim snooping statistics instance

```

user@host> show pim snooping statistics instance vpls1
Instance: vpls1
Learning-Domain: vlan-id 10

Tx J/P messages 0
RX J/P messages 9
Rx J/P messages -- seen 0
Rx J/P messages -- received 9
Rx Hello messages 45
Rx Version Unknown 0
Rx Neighbor Unknown 0
Rx Upstream Neighbor Unknown 0
Rx Bad Length 0
Rx J/P Busy Drop 0
Rx J/P Group Aggregate 0
Rx Malformed Packet 0
Rx No PIM Interface 0
Rx No Upstream Neighbor 0
Rx Bad Length 0
Rx Neighbor Unknown 0
Rx Unknown Hello Option 0
Rx Malformed Packet 0

```

```
Learning-Domain: vlan-id 20
```

```
Tx J/P messages 0
RX J/P messages 3
Rx J/P messages -- seen 0
Rx J/P messages -- received 3
Rx Hello messages 47
Rx Version Unknown 0
Rx Neighbor Unknown 0
Rx Upstream Neighbor Unknown 0
Rx Bad Length 0
Rx J/P Busy Drop 0
Rx J/P Group Aggregate 0
Rx Malformed Packet 0
Rx No PIM Interface 0
Rx No Upstream Neighbor 0
Rx Bad Length 0
Rx Neighbor Unknown 0
Rx Unknown Hello Option 0
Rx Malformed Packet 0
```

show pim snooping statistics interface

```
user@host> show pim snooping statistics interface ge-1/3/1.20
```

```
Instance: vpls1
```

```
Learning-Domain: vlan-id 10
```

```
Learning-Domain: vlan-id 20
```

```
PIM Interface statistics for ge-1/3/1.20
```

```
Tx J/P messages 0
RX J/P messages 0
Rx J/P messages -- seen 0
Rx J/P messages -- received 0
Rx Hello messages 13
Rx Version Unknown 0
Rx Neighbor Unknown 0
Rx Upstream Neighbor Unknown 0
Rx Bad Length 0
Rx J/P Busy Drop 0
```



```
Rx J/P Group Aggregate 0  
Rx Malformed Packet 0
```

show pim snooping statistics vlan-id

```
user@host> show pim snooping statistics vlan-id 10  
Instance: vpls1  
Learning-Domain: vlan-id 10  
  
Tx J/P messages 0  
RX J/P messages 11  
Rx J/P messages -- seen 0  
Rx J/P messages -- received 11  
Rx Hello messages 64  
Rx Version Unknown 0  
Rx Neighbor Unknown 0  
Rx Upstream Neighbor Unknown 0  
Rx Bad Length 0  
Rx J/P Busy Drop 0  
Rx J/P Group Aggregate 0  
Rx Malformed Packet 0  
Rx No PIM Interface 0  
Rx No Upstream Neighbor 0  
Rx Bad Length 0  
Rx Neighbor Unknown 0
```

Release Information

Command introduced in Junos OS Release 12.3.

RELATED DOCUMENTATION

[PIM Snooping for VPLS](#)

[clear pim snooping statistics](#) | 1734

show route

IN THIS SECTION

- [Syntax | 1807](#)
- [Syntax \(EX Series Switches\) | 1807](#)
- [Description | 1808](#)
- [Options | 1808](#)
- [Required Privilege Level | 1809](#)
- [Output Fields | 1809](#)
- [Sample Output | 1813](#)
- [Release Information | 1819](#)

Syntax

```
show route
<all>
<destination-prefix>
<logical-system (all | logical-system-name)>
<private>
<te-ipv4-prefix-ip te-ipv4-prefix-ip>
<te-ipv4-prefix-node-ip te-ipv4-prefix-node-ip>
<te-ipv4-prefix-node-iso te-ipv4-prefix-node-iso>
< te-ipv6-prefix-ipv6-addr te-ipv6-prefix-ipv6-addr>
< te-ipv6-prefix-node-iso te-ipv6-prefix-node-iso>

<rib-sharding (main | rib-shard-name)>
```

Syntax (EX Series Switches)

```
show route
<all>
<destination-prefix>
<private>
```

Description

Display the active entries in the routing tables.

Options

none	Display brief information about all active entries in the routing tables.
all	(Optional) Display information about all routing tables, including private, or internal, routing tables.
<i>destination-prefix</i>	(Optional) Display active entries for the specified address or range of addresses.
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.
private	(Optional) Display information only about all private, or internal, routing tables.
programmed detail	(Optional) Display API-programmed routes.
display-client-data	(Optional) Display client id and cookie information for routes installed by the routing protocol process client applications.
te-ipv4-prefix-ip <i>te-ipv4-prefix-ip</i>	(Optional) Display IPv4 address of the traffic-engineering prefix, without the mask length if present in the routing table.
te-ipv4-prefix-node-ip <i>te-ipv4-prefix-node-ip</i>	(Optional) Display all prefixes that have originated from the traffic-engineering node. You can filter IPv4 node addresses from the traffic-engineered routes in the <code>lsdist.0</code> table.
te-ipv4-prefix-node-iso <i>te-ipv4-prefix-node-iso</i>	(Optional) Display all prefixes that have originated from the traffic-engineering node. You can filter IPv4 routes with the specified ISO circuit ID from the <code>lsdist.0</code> table.
te-ipv6-prefix-ipv6-addr <i>te-ipv6-prefix-ipv6-addr</i>	(Optional) Filter IPv6 node addresses from the traffic-engineering IPv6 prefix.
te-ipv6-prefix-node-iso <i>te-ipv6-prefix-node-iso</i>	(Optional) Filter IPv6 routes with the specified ISO circuit ID in the traffic-engineering IPv6 prefix.
rib-sharding (main <i>rib-shard-name</i>)	(Optional) Display the rib shard name.

Required Privilege Level

view

Output Fields

Table 38 on page 1809 describes the output fields for the `show route` command. Output fields are listed in the approximate order in which they appear.

Table 38: show route Output Fields

Field Name	Field Description
<i>routing-table-name</i>	Name of the routing table (for example, inet.0).
<i>number destinations</i>	Number of destinations for which there are routes in the routing table.
<i>number routes</i>	<p>Number of routes in the routing table and total number of routes in the following states:</p> <ul style="list-style-type: none"> • active (routes that are active). • holddown (routes that are in the pending state before being declared inactive). A holddown route was once the active route and is no longer the active route. The route is in the holddown state because a protocol still has interest in the route, meaning that the interest bit is set. A protocol might have its interest bit set on the previously active route because the protocol is still advertising the route. The route will be deleted after all protocols withdraw their advertisement of the route and remove their interest bit. A persistent holddown state often means that the interested protocol is not releasing its interest bit properly. <p>However, if you have configured advertisement of multiple routes (with the <code>add-path</code> or <code>advertise-inactive</code> statement), the holddown bit is most likely set because BGP is advertising the route as an active route. In this case, you can ignore the holddown state because nothing is wrong.</p> <p>If you have configured <code>uRPF-loose</code> mode, the holddown bit is most likely set because Kernel Routing Table (KRT) is using inactive route to build valid incoming interfaces. In this case, you can ignore the holddown state because nothing is wrong.</p> <ul style="list-style-type: none"> • hidden (routes that are not used because of a routing policy).

Table 38: show route Output Fields (*Continued*)

Field Name	Field Description
<i>destination-prefix</i>	<p>Route destination (for example:10.0.0.1/24). Sometimes the route information is presented in another format, such as:</p> <ul style="list-style-type: none"> • <i>MPLS-label</i>(for example, 80001). • <i>interface-name</i> (for example, ge-1/0/2). • <i>neighbor-address.control-word-status.encapsulation type.vc-id.source</i> (Layer 2 circuit only. For example, 10.1.1.195:NoCtrlWord:1:1:Local/96): <ul style="list-style-type: none"> • <i>neighbor-address</i>—Address of the neighbor. • <i>control-word-status</i>—Whether the use of the control word has been negotiated for this virtual circuit: NoCtrlWord or CtrlWord. • <i>encapsulation type</i>—Type of encapsulation, represented by a number: (1) Frame Relay DLCI, (2) ATM AAL5 VCC transport, (3) ATM transparent cell transport, (4) Ethernet, (5) VLAN Ethernet, (6) HDLC, (7) PPP, (8) ATM VCC cell transport, (10) ATM VPC cell transport. • <i>vc-id</i>—Virtual circuit identifier. • <i>source</i>—Source of the advertisement: Local or Remote.
[<i>protocol</i> , <i>preference</i>]	<p>Protocol from which the route was learned and the preference value for the route.</p> <ul style="list-style-type: none"> • +—A plus sign indicates the active route, which is the route installed from the routing table into the forwarding table. • - —A hyphen indicates the last active route. • *—An asterisk indicates that the route is both the active and the last active route. An asterisk before a to line indicates the best subpath to the route. <p>In every routing metric except for the BGP LocalPref attribute, a lesser value is preferred. In order to use common comparison routines, Junos OS stores the 1's complement of the LocalPref value in the Preference2 field. For example, if the LocalPref value for Route 1 is 100, the Preference2 value is -101. If the LocalPref value for Route 2 is 155, the Preference2 value is -156. Route 2 is preferred because it has a higher LocalPref value and a lower Preference2 value.</p>

Table 38: show route Output Fields (*Continued*)

Field Name	Field Description
<i>weeks:days</i> <i>hours.minutes.seconds</i>	How long the route been known (for example, 2w4d 13:11:14, or 2 weeks, 4 days, 13 hours, 11 minutes, and 14 seconds).
metric	Cost value of the indicated route. For routes within an AS, the cost is determined by the IGP and the individual protocol metrics. For external routes, destinations, or routing domains, the cost is determined by a preference value.
localpref	Local preference value included in the route.
from	Interface from which the route was received.
AS path	<p>AS path through which the route was learned. The letters at the end of the AS path indicate the path origin, providing an indication of the state of the route at the point at which the AS path originated:</p> <ul style="list-style-type: none"> • I—IGP. • E—EGP. • ?—Incomplete; typically, the AS path was aggregated. <p>When AS path numbers are included in the route, the format is as follows:</p> <ul style="list-style-type: none"> • []—Brackets enclose the local AS number associated with the AS path if more than one AS number is configured on the routing device, or if AS path prepending is configured. • { }—Braces enclose AS sets, which are groups of AS numbers in which the order does not matter. A set commonly results from route aggregation. The numbers in each AS set are displayed in ascending order. • ()—Parentheses enclose a confederation. • ([])—Parentheses and brackets enclose a confederation set. <p>NOTE: In Junos OS Release 10.3 and later, the AS path field displays an unrecognized attribute and associated hexadecimal value if BGP receives attribute 128 (attribute set) and you have not configured an independent domain in any routing instance.</p>

Table 38: show route Output Fields *(Continued)*

Field Name	Field Description
encapsulated	Extended next-hop encoding capability enabled for the specified BGP community for routing IPv4 traffic over IPv6 tunnels. When BGP receives routes without the tunnel community, IPv4-Over IPv6 tunnels are not created and BGP routes are resolved without encapsulation.
Route Labels	Stack of labels carried in the BGP route update.
validation-state	<p>(BGP-learned routes) Validation status of the route:</p> <ul style="list-style-type: none"> • Invalid—Indicates that the prefix is found, but either the corresponding AS received from the EBGp peer is not the AS that appears in the database, or the prefix length in the BGP update message is longer than the maximum length permitted in the database. • Unknown—Indicates that the prefix is not among the prefixes or prefix ranges in the database. • Unverified—Indicates that the origin of the prefix is not verified against the database. This is because the database got populated and the validation is not called for in the BGP import policy, although origin validation is enabled, or the origin validation is not enabled for the BGP peers. • Valid—Indicates that the prefix and autonomous system pair are found in the database.
to	<p>Next hop to the destination. An angle bracket (>) indicates that the route is the selected route.</p> <p>If the destination is Discard, traffic is dropped.</p>

Table 38: show route Output Fields (Continued)

Field Name	Field Description
via	<p>Interface used to reach the next hop. If there is more than one interface available to the next hop, the interface that is actually used is followed by the word Selected. This field can also contain the following information:</p> <ul style="list-style-type: none"> • Weight—Value used to distinguish primary, secondary, and fast reroute backup routes. Weight information is available when MPLS label-switched path (LSP) link protection, node-link protection, or fast reroute is enabled, or when the standby state is enabled for secondary paths. A lower weight value is preferred. Among routes with the same weight value, load balancing is possible. • Balance—Balance coefficient indicating how traffic of unequal cost is distributed among next hops when a routing device is performing unequal-cost load balancing. This information is available when you enable BGP multipath load balancing. • lsp-path-name—Name of the LSP used to reach the next hop. • label-action—MPLS label and operation occurring at the next hop. The operation can be pop (where a label is removed from the top of the stack), push (where another label is added to the label stack), or swap (where a label is replaced by another label). For VPNs, expect to see multiple push operations, corresponding to the inner and outer labels required for VPN routes (in the case of a direct PE-to-PE connection, the VPN route would have the inner label push only).
Private unicast	(Enhanced subscriber management for MX Series routers) Indicates that an access-internal route is managed by enhanced subscriber management. By contrast, access-internal routes not managed by enhanced subscriber management are displayed with associated next-hop and media access control (MAC) address information.
balance	Distribution of the load based on the underlying operational interface bandwidth for equal-cost multipaths (ECMP) across the nexthop gateways in percentages.

Sample Output

show route

```

user@host> show route
inet.0: 11 destinations, 12 routes (11 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

```



```

1:65500:1:10.0.0.20/240
    *[MVPN/70] 19:53:41, metric2 1
    Indirect
1:65500:1:10.0.0.40/240
    *[BGP/170] 19:53:29, localpref 100, from 10.0.0.30
    AS path: I
    > to 10.0.24.4 via lt-0/3/0.24, label-switched-path toD
    [BGP/170] 19:53:26, localpref 100, from 10.0.0.33
    AS path: I
    > to 10.0.24.4 via lt-0/3/0.24, label-switched-path toD
1:65500:1:10.0.0.60/240
    *[BGP/170] 19:53:29, localpref 100, from 10.0.0.30
    AS path: I
    > to 10.0.28.8 via lt-0/3/0.28, label-switched-path toF
    [BGP/170] 19:53:25, localpref 100, from 10.0.0.33
    AS path: I
    > to 10.0.28.8 via lt-0/3/0.28, label-switched-path toF

```

show route

The following sample output shows route hierarchy for translation route.

```

user@host> show route 10.1.1.1

C1.inet.0: 44 destinations, 44 routes (44 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.1.1.1/32      *[PRPD/10] 00:16:50, metric 2
                  > to 192.0.2.2 via ge-0/0/1.0

```

show route forwarding-table matching 10.1.1.1

```

user@host> show route forwarding-table matching 10.1.1.1
Routing table: C1.inet
Internet:

```

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
10.1.1.1/32	user	0		indr	1048574	4	

comp	624	2
------	-----	---

show route 10.1.1.1 extensive expanded-nh

```

user@host> show route 10.1.1.1 extensive expanded-nh
C1.inet
C1.inet.0: 44 destinations, 44 routes (44 active, 0 holddown, 0 hidden)
10.1.1.1/32 (1 entry, 1 announced)
Installed-nexthop:
Indr (0xc5c207c) ::44.0.0.1
  Krt_inh (0xc6fd004) Index:1048574 PNH: ::44.0.0.1
    Translate-comp (0xc5c2144) Index:624 v4tov6 src ::22.0.0.1 dest ::44.0.0.1

```

show route te-ipv6-prefix-ipv6-addr

```

user@host> show route te-ipv6-prefix-ipv6-addr 10::10

inet.0: 14 destinations, 14 routes (14 active, 0 holddown, 0 hidden)

inet.3: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

iso.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

mpls.0: 14 destinations, 14 routes (14 active, 0 holddown, 0 hidden)

inet6.0: 10 destinations, 11 routes (10 active, 0 holddown, 0 hidden)

inet6.3: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

lsdist.0: 18 destinations, 18 routes (18 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

IPV6 PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv6:10::10/128 } ISIS-L1:0 }/1216
      *[IS-IS/15] 00:07:58
      Fictitious

```

show route te-ipv6-prefix-node-iso

```

user@host> show route te-ipv6-prefix-node-iso 0100.0100.0100.00

inet.0: 14 destinations, 14 routes (14 active, 0 holddown, 0 hidden)

inet.3: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

iso.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

mpls.0: 14 destinations, 14 routes (14 active, 0 holddown, 0 hidden)

inet6.0: 10 destinations, 11 routes (10 active, 0 holddown, 0 hidden)

inet6.3: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)

lsdist.0: 18 destinations, 18 routes (18 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

IPV6 PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv6:10::10/128 } ISIS-L1:0 }/
1216
          *[IS-IS/15] 00:08:46
          Fictitious
IPV6 PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv6:21:0:1::1/128 } ISIS-L1:0 }/
1216
          *[IS-IS/15] 00:08:46
          Fictitious
IPV6 PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv6:abcd::128:207:200:16/128 } ISIS-
L1:0 }/1216
          *[IS-IS/15] 00:08:46
          Fictitious

```

show route (VPN)

The following sample output shows a VPN route with composite next hops enabled. The first Push operation corresponds to the outer label. The second Push operation corresponds to the inner label.

```

user@host> show route 192.0.2.0

13979:665001.inet.0: 871 destinations, 3556 routes (871 active, 0 holddown, 0 hidden)

```

+ = Active Route, - = Last Active, * = Both

```
192.0.2.0/24      [BGP/170] 00:28:32, localpref 100, from 10.9.9.160
                  AS path: 13980 ?, validation-state: unverified
                  > to 10.100.0.42 via ae2.0, Push 16, Push 300368(top)
                  [BGP/170] 00:28:28, localpref 100, from 10.9.9.169
                  AS path: 13980 ?, validation-state: unverified
                  > to 10.100.0.42 via ae2.0, Push 126016, Push 300368(top)
#[Multipath/255] 00:28:28, metric2 102
                  > to 10.100.0.42 via ae2.0, Push 16, Push 300368(top)
                  to 10.100.0.42 via ae2.0, Push 16, Push 300368(top)
```

show route (with Destination Prefix)

```
user@host> show route 192.168.0.0/12
```

inet.0: 10 destinations, 10 routes (9 active, 0 holddown, 1 hidden)

+ = Active Route, - = Last Active, * = Both

```
192.168.0.0/12    *[Static/5] 2w4d 12:54:27
                  > to 192.168.167.254 via fxp0.0
```

show route destination-prefix detail

```
user@host> show route 198.51.100.0 detail
```

inet.0: 15 destinations, 20 routes (15 active, 0 holddown, 0 hidden)

198.51.100.0/24 (2 entries, 2 announced)

*BGP Preference: 170/-101

...

BGP-Static Preference: 4294967292

Next hop type: Discard

Address: 0x9041ae4

Next-hop reference count: 2

State: <NoReadvrt Int Ext AlwaysFlash>

Inactive reason: Route Preference

Local AS: 200

Age: 4d 1:40:40

Validation State: unverified

Task: RT

```
Announcement bits (1): 2-BGP_RT_Background
AS path: 4 5 6 I
```

show route extensive

```
user@host> show route extensive
v1.mvpn.0: 5 destinations, 8 routes (5 active, 1 holddown, 0 hidden)
1:65500:1:10.0.0.40/240 (1 entry, 1 announced)
  *BGP   Preference: 170/-101
        PMSI: Flags 0x0: Label[0:0:0]: PIM-SM: Sender 10.0.0.40 Group 203.0.113.1
        Next hop type: Indirect
        Address: 0x92455b8
        Next-hop reference count: 2
        Source: 10.0.0.30
        Protocol next hop: 10.0.0.40
        Indirect next hop: 2 no-forward
        State: <Active Int Ext>
        Local AS: 64510 Peer AS: 64511
        Age: 3 Metric2: 1
        Validation State: unverified
        Task: BGP_64510.10.0.0.30+179
        Announcement bits (2): 0-PIM.v1 1-mvpn global task
        AS path: I (Originator) Cluster list: 10.0.0.30
        AS path: Originator ID: 10.0.0.40
        Communities: target:64502:100 encapsulation:0L:14
        Import Accepted
        Localpref: 100
        Router ID: 10.0.0.30
        Primary Routing Table bgp.mvpn.0
        Indirect next hops: 1
          Protocol next hop: 10.0.0.40 Metric: 1
          Indirect next hop: 2 no-forward
          Indirect path forwarding next hops: 1
            Next hop type: Router
            Next hop: 10.0.24.4 via lt-0/3/0.24 weight 0x1
          10.0.0.40/32 Originating RIB: inet.3
            Metric: 1 Node path count: 1
            Forwarding nexthops: 1
              Nexthop: 10.0.24.4 via lt-0/3/0.24
```

show route programmed detail

```

user@host> show route programmed detail
inet.0: 36 destinations, 37 routes (36 active, 0 holddown, 0 hidden)
100.75.1.0/27 (2 entries, 1 announced)
    *Static Preference: 5/100
        Next hop type: Router, Next hop index: 0
        Address: 0xcc38a10
        Next-hop reference count: 1
        Next hop: 100.30.1.2 via ge-0/0/2.0 weight 0x1, selected
        Session Id: 0x0
        Next hop: via fti0.1001 weight 0x8001
        Session Id: 0x0
        State: <Active Int NSR-incapable Programmed>
        Age: 37
        Validation State: unverified
        Announcement bits (1): 0-KRT
        AS path: I

```

Release Information

Command introduced before Junos OS Release 7.4.

Option private introduced in Junos OS Release 9.5.

Option private introduced in Junos OS Release 9.5 for EX Series switches.

Option display-client-data introduced in Junos OS Release 16.2R1 on MX80, MX104, MX240, MX480, MX960, MX2010, MX2020, vMX Series routers.

Options te-ipv4-prefix-ip, te-ipv4-prefix-node-ip, and te-ipv4-prefix-node-iso introduced in Junos OS Release 17.2R1 on MX Series and PTX Series.

rib-sharding option introduced in cRPD Release 20.1R1.

RELATED DOCUMENTATION

[Understanding IS-IS Configuration](#)

[Verifying and Managing Junos OS Enhanced Subscriber Management](#)

show route table

IN THIS SECTION

- [Syntax | 1820](#)
- [Syntax \(EX Series Switches, QFX Series Switches\) | 1820](#)
- [Description | 1820](#)
- [Options | 1820](#)
- [Required Privilege Level | 1821](#)
- [Output Fields | 1821](#)
- [Sample Output | 1837](#)
- [Release Information | 1849](#)

Syntax

```
show route table routing-table-name  
<brief | detail | extensive | terse>  
<logical-system (all | logical-system-name)>
```

Syntax (EX Series Switches, QFX Series Switches)

```
show route table routing-table-name  
<brief | detail | extensive | terse>
```

Description

Display the route entries in a particular routing table.

Options

brief | detail | extensive | terse (Optional) Display the specified level of output.

logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system. This option is only supported on Junos OS.
<i>routing-table-name</i>	Display route entries for all routing tables whose names begin with this string (for example, inet.0 and inet6.0 are both displayed when you run the <code>show route table inet</code> command).

Required Privilege Level

view

Output Fields

[Table 39 on page 1821](#) describes the output fields for the `show route table` command. Output fields are listed in the approximate order in which they appear.

Table 39: show route table Output Fields

Field Name	Field Description
<i>routing-table-name</i>	Name of the routing table (for example, inet.0).

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
Restart complete	<p>All protocols have restarted for this routing table.</p> <p>Restart state:</p> <ul style="list-style-type: none"> • Pending:<i>protocol-name</i>—List of protocols that have not yet completed graceful restart for this routing table. • Complete—All protocols have restarted for this routing table. <p>For example, if the output shows-</p> <ul style="list-style-type: none"> • LDP.inet.0 : 5 routes (4 active, 1 holddown, 0 hidden) Restart Pending: OSPF LDP VPN <p>This indicates that OSPF, LDP, and VPN protocols did not restart for the LDP.inet.0 routing table.</p> <ul style="list-style-type: none"> • vpls_1.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden) Restart Complete <p>This indicates that all protocols have restarted for the vpls_1.l2vpn.0 routing table.</p>
<i>number</i> destinations	Number of destinations for which there are routes in the routing table.
<i>number</i> routes	<p>Number of routes in the routing table and total number of routes in the following states:</p> <ul style="list-style-type: none"> • active (routes that are active) • holddown (routes that are in the pending state before being declared inactive) • hidden (routes that are not used because of a routing policy)

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
<i>route-destination</i> (entry, announced)	<p>Route destination (for example:10.0.0.1/24). The entry value is the number of routes for this destination, and the announced value is the number of routes being announced for this destination. Sometimes the route destination is presented in another format, such as:</p> <ul style="list-style-type: none"> • <i>MPLS-label</i>(for example, 80001). • <i>interface-name</i> (for example, ge-1/0/2). • <i>neighbor-address:control-word-status:encapsulation type:vc-id:source</i> (Layer 2 circuit only; for example, 10.1.1.195:NoCtrlWord:1:1:Local/96). • <i>neighbor-address</i>—Address of the neighbor. • <i>control-word-status</i>—Whether the use of the control word has been negotiated for this virtual circuit: NoCtrlWord or CtrlWord. • <i>encapsulation type</i>—Type of encapsulation, represented by a number: (1) Frame Relay DLCI, (2) ATM AAL5 VCC transport, (3) ATM transparent cell transport, (4) Ethernet, (5) VLAN Ethernet, (6) HDLC, (7) PPP, (8) ATM VCC cell transport, (10) ATM VPC cell transport. • <i>vc-id</i>—Virtual circuit identifier. • <i>source</i>—Source of the advertisement: Local or Remote. • <i>inclusive multicast Ethernet tag route</i>—Type of route destination represented by (for example, 3:100.100.100.10:100::0::10::100.100.100.10/384): <ul style="list-style-type: none"> • <i>route distinguisher</i>—(8 octets) Route distinguisher (RD) must be the RD of the EVPN instance (EVI) that is advertising the NLRI. • <i>Ethernet tag ID</i>—(4 octets) Identifier of the Ethernet tag. Can set to 0 or to a valid Ethernet tag value. • <i>IP address length</i>—(1 octet) Length of IP address in bits. • <i>originating router's IP address</i>—(4 or 16 octets) Must set to the provider edge (PE) device's IP address. This address should be common for all EVIs on the PE device, and may be the PE device's loopback address.

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
label stacking	<p>(Next-to-the-last-hop routing device for MPLS only) Depth of the MPLS label stack, where the label-popping operation is needed to remove one or more labels from the top of the stack. A pair of routes is displayed, because the pop operation is performed only when the stack depth is two or more labels.</p> <ul style="list-style-type: none"> • S=0 route indicates that a packet with an incoming label stack depth of 2 or more exits this routing device with one fewer label (the label-popping operation is performed). • If there is no S= information, the route is a normal MPLS route, which has a stack depth of 1 (the label-popping operation is not performed).
[protocol, preference]	<p>Protocol from which the route was learned and the preference value for the route.</p> <ul style="list-style-type: none"> • +-A plus sign indicates the active route, which is the route installed from the routing table into the forwarding table. • --A hyphen indicates the last active route. • *-An asterisk indicates that the route is both the active and the last active route. An asterisk before a to line indicates the best subpath to the route. <p>In every routing metric except for the BGP LocalPref attribute, a lesser value is preferred. In order to use common comparison routines, Junos OS stores the 1's complement of the LocalPref value in the Preference2 field. For example, if the LocalPref value for Route 1 is 100, the Preference2 value is -101. If the LocalPref value for Route 2 is 155, the Preference2 value is -156. Route 2 is preferred because it has a higher LocalPref value and a lower Preference2 value.</p>
Level	<p>(IS-IS only). In IS-IS, a single AS can be divided into smaller groups called areas. Routing between areas is organized hierarchically, allowing a domain to be administratively divided into smaller areas. This organization is accomplished by configuring Level 1 and Level 2 intermediate systems. Level 1 systems route within an area. When the destination is outside an area, they route toward a Level 2 system. Level 2 intermediate systems route between areas and toward other ASs.</p>
Route Distinguisher	IP subnet augmented with a 64-bit prefix.
PMSI	Provider multicast service interface (MVPN routing table).

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
Next-hop type	Type of next hop. For a description of possible values for this field, see Table 40 on page 1830 .
Next-hop reference count	Number of references made to the next hop.
Flood nexthop branches exceed maximum message	Indicates that the number of flood next-hop branches exceeded the system limit of 32 branches, and only a subset of the flood next-hop branches were installed in the kernel.
Source	IP address of the route source.
Next hop	Network layer address of the directly reachable neighboring system.
via	<p>Interface used to reach the next hop. If there is more than one interface available to the next hop, the name of the interface that is actually used is followed by the word Selected. This field can also contain the following information:</p> <ul style="list-style-type: none"> • Weight—Value used to distinguish primary, secondary, and fast reroute backup routes. Weight information is available when MPLS label-switched path (LSP) link protection, node-link protection, or fast reroute is enabled, or when the standby state is enabled for secondary paths. A lower weight value is preferred. Among routes with the same weight value, load balancing is possible. • Balance—Balance coefficient indicating how traffic of unequal cost is distributed among next hops when a routing device is performing unequal-cost load balancing. This information is available when you enable BGP multipath load balancing.
Label-switched-path <i>lsp-path-name</i>	Name of the LSP used to reach the next hop.
Label operation	MPLS label and operation occurring at this routing device. The operation can be pop (where a label is removed from the top of the stack), push (where another label is added to the label stack), or swap (where a label is replaced by another label).

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
Interface	(Local only) Local interface name.
Protocol next hop	Network layer address of the remote routing device that advertised the prefix. This address is used to derive a forwarding next hop.
Indirect next hop	Index designation used to specify the mapping between protocol next hops, tags, kernel export policy, and the forwarding next hops.
State	State of the route (a route can be in more than one state). See Table 41 on page 1832 .
Local AS	AS number of the local routing devices.
Age	How long the route has been known.
AIGP	Accumulated interior gateway protocol (AIGP) BGP attribute.
Metric n	Cost value of the indicated route. For routes within an AS, the cost is determined by IGP and the individual protocol metrics. For external routes, destinations, or routing domains, the cost is determined by a preference value.
MED-plus-IGP	Metric value for BGP path selection to which the IGP cost to the next-hop destination has been added.
TTL-Action	For MPLS LSPs, state of the TTL propagation attribute. Can be enabled or disabled for all RSVP-signaled and LDP-signaled LSPs or for specific VRF routing instances.
Task	Name of the protocol that has added the route.

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
Announcement bits	<p>The number of BGP peers or protocols to which Junos OS has announced this route, followed by the list of the recipients of the announcement. Junos OS can also announce the route to the kernel routing table (KRT) for installing the route into the Packet Forwarding Engine, to a resolve tree, a Layer 2 VC, or even a VPN. For example, <i>n-Resolve inet</i> indicates that the specified route is used for route resolution for next hops found in the routing table.</p> <ul style="list-style-type: none"> <i>n</i>—An index used by Juniper Networks customer support only.
AS path	<p>AS path through which the route was learned. The letters at the end of the AS path indicate the path origin, providing an indication of the state of the route at the point at which the AS path originated:</p> <ul style="list-style-type: none"> I—IGP. E—EGP. Recorded—The AS path is recorded by the sample process (sampled). ?—Incomplete; typically, the AS path was aggregated. <p>When AS path numbers are included in the route, the format is as follows:</p> <ul style="list-style-type: none"> []—Brackets enclose the number that precedes the AS path. This number represents the number of ASs present in the AS path, when calculated as defined in RFC 4271. This value is used in the AS-path merge process, as defined in RFC 4893. []—If more than one AS number is configured on the routing device, or if AS path prepending is configured, brackets enclose the local AS number associated with the AS path. { }—Braces enclose AS sets, which are groups of AS numbers in which the order does not matter. A set commonly results from route aggregation. The numbers in each AS set are displayed in ascending order. ()—Parentheses enclose a confederation. ([])—Parentheses and brackets enclose a confederation set. <p>NOTE: In Junos OS Release 10.3 and later, the AS path field displays an unrecognized attribute and associated hexadecimal value if BGP receives attribute 128 (attribute set) and you have not configured an independent domain in any routing instance.</p>

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
validation-state	<p>(BGP-learned routes) Validation status of the route:</p> <ul style="list-style-type: none"> • Invalid—Indicates that the prefix is found, but either the corresponding AS received from the EBGp peer is not the AS that appears in the database, or the prefix length in the BGP update message is longer than the maximum length permitted in the database. • Unknown—Indicates that the prefix is not among the prefixes or prefix ranges in the database. • Unverified—Indicates that the origin of the prefix is not verified against the database. This is because the database got populated and the validation is not called for in the BGP import policy, although origin validation is enabled, or the origin validation is not enabled for the BGP peers. • Valid—Indicates that the prefix and autonomous system pair are found in the database.
FECs bound to route	Indicates point-to-multipoint root address, multicast source address, and multicast group address when multipoint LDP (M-LDP) inband signaling is configured.
Primary Upstream	When multipoint LDP with multicast-only fast reroute (MoFRR) is configured, indicates the primary upstream path. MoFRR transmits a multicast join message from a receiver toward a source on a primary path, while also transmitting a secondary multicast join message from the receiver toward the source on a backup path.
RPF Nexthops	When multipoint LDP with MoFRR is configured, indicates the reverse-path forwarding (RPF) next-hop information. Data packets are received from both the primary path and the secondary paths. The redundant packets are discarded at topology merge points due to the RPF checks.
Label	Multiple MPLS labels are used to control MoFRR stream selection. Each label represents a separate route, but each references the same interface list check. Only the primary label is forwarded while all others are dropped. Multiple interfaces can receive packets using the same label.
weight	Value used to distinguish MoFRR primary and backup routes. A lower weight value is preferred. Among routes with the same weight value, load balancing is possible.

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
VC Label	MPLS label assigned to the Layer 2 circuit virtual connection.
MTU	Maximum transmission unit (MTU) of the Layer 2 circuit.
VLAN ID	VLAN identifier of the Layer 2 circuit.
Prefixes bound to route	Forwarding equivalent class (FEC) bound to this route. Applicable only to routes installed by LDP.
Communities	Community path attribute for the route. See Table 42 on page 1836 for all possible values for this field.
Layer2-info: encaps	Layer 2 encapsulation (for example, VPLS).
control flags	Control flags: none or Site Down.
mtu	Maximum transmission unit (MTU) information.
Label-Base, range	First label in a block of labels and label block size. A remote PE routing device uses this first label when sending traffic toward the advertising PE routing device.
status vector	Layer 2 VPN and VPLS network layer reachability information (NLRI).
Accepted Multipath	Current active path when BGP multipath is configured.
Accepted LongLivedStale	The LongLivedStale flag indicates that the route was marked LLGR-stale by this router, as part of the operation of LLGR receiver mode. Either this flag or the LongLivedStaleImport flag might be displayed for a route. Neither of these flags is displayed at the same time as the Stale (ordinary GR stale) flag.

Table 39: show route table Output Fields (Continued)

Field Name	Field Description
Accepted LongLivedStaleImport	<p>The LongLivedStaleImport flag indicates that the route was marked LLGR-stale when it was received from a peer, or by import policy. Either this flag or the LongLivedStale flag might be displayed for a route. Neither of these flags is displayed at the same time as the Stale (ordinary GR stale) flag.</p> <p>Accept all received BGP long-lived graceful restart (LLGR) and LLGR stale routes learned from configured neighbors and import into the inet.0 routing table</p>
ImportAccepted LongLivedStaleImport	<p>Accept all received BGP long-lived graceful restart (LLGR) and LLGR stale routes learned from configured neighbors and imported into the inet.0 routing table</p> <p>The LongLivedStaleImport flag indicates that the route was marked LLGR-stale when it was received from a peer, or by import policy.</p>
Accepted MultipathContrib	Path currently contributing to BGP multipath.
Localpref	Local preference value included in the route.
Router ID	BGP router ID as advertised by the neighbor in the open message.
Primary Routing Table	In a routing table group, the name of the primary routing table in which the route resides.
Secondary Tables	In a routing table group, the name of one or more secondary tables in which the route resides.

[Table 40 on page 1830](#) describes all possible values for the Next-hop Types output field.

Table 40: Next-hop Types Output Field Values

Next-Hop Type	Description
Broadcast (bcast)	Broadcast next hop.

Table 40: Next-hop Types Output Field Values *(Continued)*

Next-Hop Type	Description
Deny	Deny next hop.
Discard	Discard next hop.
Flood	Flood next hop. Consists of components called branches, up to a maximum of 32 branches. Each flood next-hop branch sends a copy of the traffic to the forwarding interface. Used by point-to-multipoint RSVP, point-to-multipoint LDP, point-to-multipoint CCC, and multicast.
Hold	Next hop is waiting to be resolved into a unicast or multicast type.
Indexed (idxd)	Indexed next hop.
Indirect (indr)	Used with applications that have a protocol next hop address that is remote. You are likely to see this next-hop type for internal BGP (IBGP) routes when the BGP next hop is a BGP neighbor that is not directly connected.
Interface	Used for a network address assigned to an interface. Unlike the router next hop, the interface next hop does not reference any specific node on the network.
Local (locl)	Local address on an interface. This next-hop type causes packets with this destination address to be received locally.
Multicast (mcst)	Wire multicast next hop (limited to the LAN).
Multicast discard (mdsc)	Multicast discard.
Multicast group (mgrp)	Multicast group member.
Receive (rcv)	Receive.

Table 40: Next-hop Types Output Field Values *(Continued)*

Next-Hop Type	Description
Reject (rjct)	Discard. An ICMP unreachable message was sent.
Resolve (rslv)	Resolving next hop.
Routed multicast (mcrt)	Regular multicast next hop.
Router	<p>A specific node or set of nodes to which the routing device forwards packets that match the route prefix.</p> <p>To qualify as a next-hop type router, the route must meet the following criteria:</p> <ul style="list-style-type: none"> • Must not be a direct or local subnet for the routing device. • Must have a next hop that is directly connected to the routing device.
Table	Routing table next hop.
Unicast (ucst)	Unicast.
Unilist (ulst)	List of unicast next hops. A packet sent to this next hop goes to any next hop in the list.

[Table 41 on page 1832](#) describes all possible values for the State output field. A route can be in more than one state (for example, <Active NoReadvrt Int Ext>).

Table 41: State Output Field Values

Value	Description
Accounting	Route needs accounting.
Active	Route is active.

Table 41: State Output Field Values *(Continued)*

Value	Description
Always Compare MED	Path with a lower multiple exit discriminator (MED) is available.
AS path	Shorter AS path is available.
Cisco Non-deterministic MED selection	Cisco nondeterministic MED is enabled, and a path with a lower MED is available.
Clone	Route is a clone.
Cluster list length	Length of cluster list sent by the route reflector.
Delete	Route has been deleted.
Ex	Exterior route.
Ext	BGP route received from an external BGP neighbor.
FlashAll	Forces all protocols to be notified of a change to any route, active or inactive, for a prefix. When not set, protocols are informed of a prefix only when the active route changes.
Hidden	Route not used because of routing policy.
IfCheck	Route needs forwarding RPF check.
IGP metric	Path through next hop with lower IGP metric is available.
Inactive reason	Flags for this route, which was not selected as best for a particular destination.
Initial	Route being added.

Table 41: State Output Field Values *(Continued)*

Value	Description
Int	Interior route.
Int Ext	BGP route received from an internal BGP peer or a BGP confederation peer.
Interior > Exterior > Exterior via Interior	Direct, static, IGP, or EBGP path is available.
Local Preference	Path with a higher local preference value is available.
Martian	Route is a martian (ignored because it is obviously invalid).
MartianOK	Route exempt from martian filtering.
Next hop address	Path with lower metric next hop is available.
No difference	Path from neighbor with lower IP address is available.
NoReadvrt	Route not to be advertised.
NotBest	Route not chosen because it does not have the lowest MED.
Not Best in its group	Incoming BGP AS is not the best of a group (only one AS can be the best).
NotInstall	Route not to be installed in the forwarding table.
Number of gateways	Path with a greater number of next hops is available.
Origin	Path with a lower origin code is available.

Table 41: State Output Field Values (Continued)

Value	Description
Pending	Route pending because of a hold-down configured on another route.
Release	Route scheduled for release.
RIB preference	Route from a higher-numbered routing table is available.
Route Distinguisher	64-bit prefix added to IP subnets to make them unique.
Route Metric or MED comparison	Route with a lower metric or MED is available.
Route Preference	Route with lower preference value is available.
Router ID	Path through a neighbor with lower ID is available.
Secondary	Route not a primary route.
Unusable path	Path is not usable because of one of the following conditions: <ul style="list-style-type: none"> • The route is damped. • The route is rejected by an import policy. • The route is unresolved.
Update source	Last tiebreaker is the lowest IP address value.
VxlanLocalRT	Route is an EVPN Type 5 route (IP prefix route).

[Table 42 on page 1836](#) describes the possible values for the Communities output field.

Table 42: Communities Output Field Values

Value	Description
<i>area-number</i>	4 bytes, encoding a 32-bit area number. For AS-external routes, the value is 0. A nonzero value identifies the route as internal to the OSPF domain, and as within the identified area. Area numbers are relative to a particular OSPF domain.
<i>bandwidth: local AS number:link-bandwidth-number</i>	Link-bandwidth community value used for unequal-cost load balancing. When BGP has several candidate paths available for multipath purposes, it does not perform unequal-cost load balancing according to the link-bandwidth community unless all candidate paths have this attribute.
<i>domain-id</i>	Unique configurable number that identifies the OSPF domain.
<i>domain-id-vendor</i>	Unique configurable number that further identifies the OSPF domain.
<i>link-bandwidth-number</i>	Link-bandwidth number: from 0 through 4,294,967,295 (bytes per second).
<i>local AS number</i>	Local AS number: from 1 through 65,535.
<i>options</i>	1 byte. Currently this is only used if the route type is 5 or 7. Setting the least significant bit in the field indicates that the route carries a type 2 metric.
<i>origin</i>	(Used with VPNs) Identifies where the route came from.
<i>ospf-route-type</i>	1 byte, encoded as 1 or 2 for intra-area routes (depending on whether the route came from a type 1 or a type 2 LSA); 3 for summary routes; 5 for external routes (area number must be 0); 7 for NSSA routes; or 129 for sham link endpoint addresses.
<i>route-type-vendor</i>	Displays the area number, OSPF route type, and option of the route. This is configured using the BGP extended community attribute 0x8000. The format is <i>area-number:ospf-route-type:options</i> .
<i>rte-type</i>	Displays the area number, OSPF route type, and option of the route. This is configured using the BGP extended community attribute 0x0306. The format is <i>area-number:ospf-route-type:options</i> .

Table 42: Communities Output Field Values (Continued)

Value	Description
target	Defines which VPN the route participates in; target has the format <i>32-bit IP address:16-bit number</i> . For example, 10.19.0.0:100.
unknown IANA	Incoming IANA codes with a value between 0x1 and 0x7fff. This code of the BGP extended community attribute is accepted, but it is not recognized.
unknown OSPF vendor community	Incoming IANA codes with a value above 0x8000. This code of the BGP extended community attribute is accepted, but it is not recognized.
evpn-mcast-flags	Identifies the value in the multicast flags extended community and whether snooping is enabled. A value of 0x1 indicates that the route supports IGMP proxy.
evpn-l2-info	<p>Identifies whether Multihomed Proxy MAC and IP Address Route Advertisement is enabled. A value of 0x20 indicates that the proxy bit is set. .</p> <p>Use the <code>show bridge mac-ip-table extensive</code> statement to determine whether the MAC and IP address route was learned locally or from a PE device.</p>

Sample Output

show route table bgp.l2vpn.0

```

user@host> show route table bgp.l2vpn.0
bgp.l2vpn.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

192.168.24.1:1:4:1/96
    *[BGP/170] 01:08:58, localpref 100, from 192.168.24.1
    AS path: I
    > to 10.0.16.2 via fe-0/0/1.0, label-switched-path am

```


show route table bgpmcast.0 extensive

```

user@host> show route table bgpmcast.0 extensive
bgpmcast.0: 1 destinations, 1 routes (1 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

4:3:0:0:32:10.2.20.20:32:225.1.1.1:10.4.4.4:10.20.20.20/240 (1 entry, 1 announced)
    *BGP      Preference: 170/-101
                Tunnel type: AnyEncap, RPF tunnel:, Remote end point: 10.1.4.4
                Tunnel type: AnyEncap, Remote end point: 10.2.4.4
                Tunnel type: AnyEncap, Remote end point: 10.3.4.4
                Tunnel type: AnyEncap, Remote end point: 10.4.6.4
                Next hop type: Indirect, Next hop index: 0
                Address: 0xc54639c
                Next-hop reference count: 1
                Source: 10.1.1.1
                Protocol next hop: 10.20.20.20
                Indirect next hop: 0x2 no-forward INH Session ID: 0x0
                State: <Active Int Ext>
                Local AS: 65100 Peer AS: 65100
                Age: 30 Metric2: 0
                Validation State: unverified
                Task: BGP_100.1.1.1.1
                Announcement bits (1): 0-bgpmcast global task
                AS path: I
                Communities: target:10.4.4.4:0
                Accepted
                Localpref: 100
                Router ID: 10.1.1.1
                Indirect next hops: 1
                    Protocol next hop: 10.20.20.20
                    Indirect next hop: 0x2 no-forward INH Session ID: 0x0
                    Indirect path forwarding next hops: 1
                        Next hop type: Router
                        Next hop: 10.4.20.20 via ge-0/0/5.0
                        Session Id: 0x140
                        10.20.20.20/32 Originating RIB: inet.0
                        Node path count: 1
                        Forwarding nexthops: 1
                            Next hop type: Router

```

Next hop: 10.4.20.20 via ge-0/0/5.0
Session Id: 0x140

show route table inet.0

```
user@host> show route table inet.0
inet.0: 12 destinations, 12 routes (11 active, 0 holddown, 1 hidden)
+ = Active Route, - = Last Active, * = Both

0.0.0.0/0      *[Static/5] 00:51:57
                > to 172.16.5.254 via fxp0.0
10.0.0.1/32    *[Direct/0] 00:51:58
                > via at-5/3/0.0
10.0.0.2/32    *[Local/0] 00:51:58
                Local
10.12.12.21/32 *[Local/0] 00:51:57
                Reject
10.13.13.13/32 *[Direct/0] 00:51:58
                > via t3-5/2/1.0
10.13.13.14/32 *[Local/0] 00:51:58
                Local
10.13.13.21/32 *[Local/0] 00:51:58
                Local
10.13.13.22/32 *[Direct/0] 00:33:59
                > via t3-5/2/0.0
127.0.0.1/32   [Direct/0] 00:51:58
                > via lo0.0
10.222.5.0/24  *[Direct/0] 00:51:58
                > via fxp0.0
10.222.5.81/32 *[Local/0] 00:51:58
                Local
```

show route table inet.3

```
user@host> show route table inet.3
inet.3: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.0.0.5/32    *[LDP/9] 00:25:43, metric 10, tag 200
```

```

    to 10.2.94.2 via lt-1/2/0.49
> to 10.2.3.2 via lt-1/2/0.23

```

show route table inet.3 protocol ospf

```

user@host> show route table inet.3 protocol ospf
inet.3: 9 destinations, 18 routes (9 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

1.1.1.20/32      [L-OSPF/10] 1d 00:00:56, metric 2
> to 10.0.10.70 via lt-1/2/0.14, Push 800020
  to 10.0.6.60 via lt-1/2/0.12, Push 800020, Push 800030(top)
1.1.1.30/32      [L-OSPF/10] 1d 00:01:01, metric 3
> to 10.0.10.70 via lt-1/2/0.14, Push 800030
  to 10.0.6.60 via lt-1/2/0.12, Push 800030
1.1.1.40/32      [L-OSPF/10] 1d 00:01:01, metric 4
> to 10.0.10.70 via lt-1/2/0.14, Push 800040
  to 10.0.6.60 via lt-1/2/0.12, Push 800040
1.1.1.50/32      [L-OSPF/10] 1d 00:01:01, metric 5
> to 10.0.10.70 via lt-1/2/0.14, Push 800050
  to 10.0.6.60 via lt-1/2/0.12, Push 800050
1.1.1.60/32      [L-OSPF/10] 1d 00:01:01, metric 6
> to 10.0.10.70 via lt-1/2/0.14, Push 800060
  to 10.0.6.60 via lt-1/2/0.12, Pop

```

show route table inet6.0

```

user@host> show route table inet6.0
inet6.0: 3 destinations, 3 routes (3 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Route, * = Both

fec0:0:0:3::/64 *[Direct/0] 00:01:34
>via fe-0/1/0.0

fec0:0:0:3::/128 *[Local/0] 00:01:34
>Local

fec0:0:0:4::/64 *[Static/5] 00:01:34
>to fec0:0:0:3::ffff via fe-0/1/0.0

```

show route table inet6.3

```

user@router> show route table inet6.3
inet6.3: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

::10.255.245.195/128
    *[LDP/9] 00:00:22, metric 1
    > via so-1/0/0.0
::10.255.245.196/128
    *[LDP/9] 00:00:08, metric 1
    > via so-1/0/0.0, Push 100008

```

show route table l2circuit.0

```

user@host> show route table l2circuit.0
l2circuit.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.1.1.195:NoCtrlWord:1:1:Local/96
    *[L2CKT/7] 00:50:47
    > via so-0/1/2.0, Push 100049
    via so-0/1/3.0, Push 100049
10.1.1.195:NoCtrlWord:1:1:Remote/96
    *[LDP/9] 00:50:14
    Discard
10.1.1.195:CtrlWord:1:2:Local/96
    *[L2CKT/7] 00:50:47
    > via so-0/1/2.0, Push 100049
    via so-0/1/3.0, Push 100049
10.1.1.195:CtrlWord:1:2:Remote/96
    *[LDP/9] 00:50:14
    Discard

```

show route table lsdist.0

```

user@host> show route table lsdist.0

lsdist.0: 21 destinations, 21 routes (21 active, 0 holddown, 0 hidden)

```

+ = Active Route, - = Last Active, * = Both

NODE { AS:100 ISO:0003.0003.0303.00 ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:16

Fictitious

NODE { AS:100 ISO:1282.0404.9202.00 ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:07

Fictitious

NODE { AS:100 ISO:1282.0404.9202.02 ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:07

Fictitious

LINK { Local { AS:100 ISO:0003.0003.0303.00 }.{ IPv4:23.0.0.2 IPv6:23::2 } Remote { AS:100 ISO:1282.0404.9202.02 }.{ } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:07

Fictitious

LINK { Local { AS:100 ISO:1282.0404.9202.00 }.{ IPv4:23.0.0.1 IPv6:23::1 } Remote { AS:100 ISO:1282.0404.9202.02 }.{ } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:07

Fictitious

LINK { Local { AS:100 ISO:1282.0404.9202.02 }.{ } Remote { AS:100 ISO:0003.0003.0303.00 }.{ } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:07

Fictitious

LINK { Local { AS:100 ISO:1282.0404.9202.02 }.{ } Remote { AS:100 ISO:1282.0404.9202.00 }.{ } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:07

Fictitious

PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv4:3.3.3.3/32 } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:16

Fictitious

PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv4:32.32.32.32/32 } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:16

Fictitious

PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv4:33.33.33.33/32 } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:16

Fictitious

PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv4:100.100.100.0/32 } ISIS-L2:0 }/1216

*[IS-IS/18] 10:19:16

Fictitious

PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv4:128.204.49.193/32 } ISIS-L2:0 }/

```

1216
    *[IS-IS/18] 10:19:16
        Fictitious
PREFIX { Node { AS:100 ISO:1282.0404.9202.00 } { IPv4:2.2.2.2/32 } ISIS-L2:0 }/1216
    *[IS-IS/18] 10:19:07
        Fictitious
PREFIX { Node { AS:100 ISO:1282.0404.9202.00 } { IPv4:128.204.49.202/32 } ISIS-L2:0 }/
1216
    *[IS-IS/18] 10:19:07
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv6:3::3/128 } ISIS-L2:0 }/
1216
    *[IS-IS/18] 10:19:16
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv6:23::/64 } ISIS-L2:0 }/
1216
    *[IS-IS/18] 10:19:16
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv6:100:100:100::100/128 } ISIS-L2:0 }/
1216
    *[IS-IS/18] 10:19:16
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:0003.0003.0303.00 } { IPv6:abcd::128:204:49:193/128 } ISIS-
L2:0 }/1216
    *[IS-IS/18] 10:19:16
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:1282.0404.9202.00 } { IPv6:2::2/128 } ISIS-L2:0 }/
1216
    *[IS-IS/18] 10:19:07
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:1282.0404.9202.00 } { IPv6:23::/64 } ISIS-L2:0 }/
1216
    *[IS-IS/18] 10:19:07
        Fictitious
IPV6 PREFIX { Node { AS:100 ISO:1282.0404.9202.00 } { IPv6:abcd::128:204:49:202/128 } ISIS-
L2:0 }/1216
    *[IS-IS/18] 10:19:07
        Fictitious

```

show route table lsdist.0 detail

```

user@host> show route table lsdist.0 detail
lsdist.0: 14 destinations, 14 routes (14 active, 0 holddown, 0 hidden)
NODE { AS:200 ISO:1282.2113.1154.00 ISIS-L1:0 }/1216 (1 entry, 1 announced)
*IS-IS Preference: 15
Level: 1
Next hop type: Fictitious, Next hop index: 0
Address: 0xc5b3054
Next-hop reference count: 14
.....
.....
.....
Area membership:
47 00 05 80 ff f8 00 00 00 01 08 00 01
SPRING-Capabilities:
- SRGB block [Start: 800000, Range: 4096, Flags: 0xc0]
SPRING-Algorithms:
- Algo: 0
SPRING Flex-Algorithms Definition:
- Flex-Algo: 129
Metric: 0, Calc: 0, priority: 129
- Flags: 0x02, - Inc Any: 0x00040000, - Exclude: 0x00008000, - Inc All: 0x00004000
.....
.....
.....
PREFIX { Node { AS:200 ISO:1282.2113.3158.00 } { IPv4:128.220.13.196/32 } ISIS-L1:0 }/1216 (1
entry, 1 announced)
*IS-IS Preference: 15
Level: 1
Next hop type: Fictitious, Next hop index: 0
Address: 0xc5b3054
Next-hop reference count: 14
Next hop:
State: <Active NotInstall>
Local AS: 200
Age: 16:16:25
.....
.....
Prefix SID: 10, Flags: 0xe0, Algo: 0
Prefix SID: 780, Flags: 0xe0, Algo: 129

```

```

Flex Algo: 129, Flex Algo Metric: 10
*****
*****
IPV6 PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv6:4000::/64 } ISIS-L1:0 }/1216 (1
entry, 1 announced)
    *BGP    Preference: 170/-101
            Next hop type: Router, Next hop index: 588
            Address: 0x7660f64
            Next-hop reference count: 12, key opaque handle: 0x0, non-key opaque handle: 0x0
            Source: 21.0.2.1
            Next hop: 21.0.2.1 via ge-0/0/0.0, selected
            Session Id: 320
            State: <Active Ext>
            Local AS:    200 Peer AS:    100
            Age: 1d 10:20:38
            Validation State: unverified
            Task: BGP_100.21.0.2.1
            Announcement bits (1): 0-TED Export
            AS path: 100 I
            Accepted
            SRV6 Locator Flags: 0, Algo: 0, Metric: 0
            Localpref: 100
            Router ID: 100.100.100.0
            Thread: junos-main

```

show route table lsdist.0 extensive

The output of the `show route table lsdist.0 extensive` command to include IPv6 Prefix attributes.

```

user@host> show route table lsdist.0 extensive
lsdist.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
NODE { AS:100 ISO:0100.0100.0100.00 ISIS-L1:0 }/1216 (1 entry, 1 announced)
TSI:
LINK-STATE attribute handle 0x75ace70
    *BGP    Preference: 170/-101
            Next hop type: Router, Next hop index: 0
            Address: 0x7661124
            Next-hop reference count: 5, key opaque handle: 0x0, non-key opaque handle: 0x0
            Source: 21.0.2.1
            Next hop: 21.0.2.1 via ge-0/0/0.0, selected

```



```

Session Id: 0
State: <Active Ext>
Local AS: 200 Peer AS: 100
Age: 17
Validation State: unverified
Task: BGP_100.21.0.2.1
Announcement bits (1): 0-TED Export
AS path: 100 I
Accepted
IPv4 Router-ids:
    100.100.100.0
Area border router: No
External router: No
Attached: No
Overload: No
Hostname: R0
Area membership:
    49 00 05
SPRING-Algorithms:
    - Algo: 0
    - Algo: 1
SRV6 Capable: - Flags: 0
SRV6 Node MSD:
    - Type: 41, Value: 6
    - Type: 42, Value: 7
    - Type: 43, Value: 5
    - Type: 44, Value: 6
    - Type: 45, Value: 6
Localpref: 100
Router ID: 100.100.100.0
Thread: junos-main

```

```

PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv4:100.100.100.0/32 } ISIS-L1:0 }/1216 (1
entry, 1 announced)

```

```

TSI:

```

```

LINK-STATE attribute handle 0x0

```

```

    *BGP    Preference: 170/-101
           Next hop type: Router, Next hop index: 0
           Address: 0x7661124
           Next-hop reference count: 5, key opaque handle: 0x0, non-key opaque handle: 0x0
           Source: 21.0.2.1
           Next hop: 21.0.2.1 via ge-0/0/0.0, selected
           Session Id: 0

```

```

State: <Active Ext>
Local AS: 200 Peer AS: 100
Age: 28
Validation State: unverified
Task: BGP_100.21.0.2.1
Announcement bits (1): 0-TED Export
AS path: 100 I
Accepted
Localpref: 100
Router ID: 100.100.100.0
Thread: junos-main

```

```

IPV6 PREFIX { Node { AS:100 ISO:0100.0100.0100.00 } { IPv6:10::10/128 } ISIS-L1:0 }/1216 (1
entry, 1 announced)

```

```

TSI:

```

```

LINK-STATE attribute handle 0x0

```

```

*BGP Preference: 170/-101
Next hop type: Router, Next hop index: 0
Address: 0x7661124
Next-hop reference count: 5, key opaque handle: 0x0, non-key opaque handle: 0x0
Source: 21.0.2.1
Next hop: 21.0.2.1 via ge-0/0/0.0, selected
Session Id: 0
State: <Active Ext>
Local AS: 200 Peer AS: 100
Age: 28
Validation State: unverified
Task: BGP_100.21.0.2.1
Announcement bits (1): 0-TED Export
AS path: 100 I
Accepted
Localpref: 100
Router ID: 100.100.100.0
Thread: junos-main

```

show route table mpls

```

user@host> show route table mpls
mpls.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

```

```

0          *[MPLS/0] 00:13:55, metric 1
          Receive
1          *[MPLS/0] 00:13:55, metric 1
          Receive
2          *[MPLS/0] 00:13:55, metric 1
          Receive
1024       *[VPN/0] 00:04:18
          to table red.inet.0, Pop

```

show route table mpls.0 protocol ospf

```

user@host> show route table mpls.0 protocol ospf
mpls.0: 29 destinations, 29 routes (29 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

299952     *[L-OSPF/10] 23:59:42, metric 0
          > to 10.0.10.70 via lt-1/2/0.14, Pop
          to 10.0.6.60 via lt-1/2/0.12, Swap 800070, Push 800030(top)
299952(S=0) *[L-OSPF/10] 23:59:42, metric 0
          > to 10.0.10.70 via lt-1/2/0.14, Pop
          to 10.0.6.60 via lt-1/2/0.12, Swap 800070, Push 800030(top)
299968     *[L-OSPF/10] 23:59:48, metric 0
          > to 10.0.6.60 via lt-1/2/0.12, Pop

```

show route table VPN-AB.inet.0

```

user@host> show route table VPN-AB.inet.0
VPN-AB.inet.0: 8 destinations, 8 routes (8 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.39.1.0/30    *[OSPF/10] 00:07:24, metric 1
              > via so-7/3/1.0
10.39.1.4/30    *[Direct/0] 00:08:42
              > via so-5/1/0.0
10.39.1.6/32    *[Local/0] 00:08:46
              Local
10.255.71.16/32 *[Static/5] 00:07:24
              > via so-2/0/0.0
10.255.71.17/32 *[BGP/170] 00:07:24, MED 1, localpref 100, from
10.255.71.15

```

```

AS path: I
> via so-2/1/0.0, Push 100020, Push 100011(top)
10.255.71.18/32 *[BGP/170] 00:07:24, MED 1, localpref 100, from
10.255.71.15
AS path: I
> via so-2/1/0.0, Push 100021, Push 100011(top)
10.255.245.245/32 *[BGP/170] 00:08:35, localpref 100
AS path: 2 I
> to 10.39.1.5 via so-5/1/0.0
10.255.245.246/32 *[OSPF/10] 00:07:24, metric 1
> via so-7/3/1.0

```

Release Information

Command introduced before Junos OS Release 7.4.

Show route table evpn statement introduced in Junos OS Release 15.1X53-D30 for QFX Series switches.

RELATED DOCUMENTATION

[show route summary](#)

show route forwarding-table

IN THIS SECTION

- [Syntax](#) | **1850**
- [Syntax \(MX Series Routers\)](#) | **1850**
- [Syntax \(TX Matrix and TX Matrix Plus Routers\)](#) | **1851**
- [Description](#) | **1851**
- [Options](#) | **1851**
- [Required Privilege Level](#) | **1853**
- [Output Fields](#) | **1853**
- [Sample Output](#) | **1859**

Syntax

```
show route forwarding-table
<detail | extensive | summary>
<all>
<ccc interface-name>
<destination destination-prefix>
<family family | matching matching>
<interface-name interface-name>
<label name>
<matching matching>
<multicast>
<table (default | logical-system-name/routing-instance-name | routing-instance-name)>
<vlan (all | vlan-name)>
<vpn vpn>
```

Syntax (MX Series Routers)


```
show route forwarding-table
<detail | extensive | summary>
<all>
<bridge-domain (all | domain-name)>
<ccc interface-name>
<destination destination-prefix>
<family family | matching matching>
<interface-name interface-name>
<label name>
<learning-vlan-id learning-vlan-id>
<matching matching>
<multicast>
<table (default | logical-system-name/routing-instance-name | routing-instance-name)>
<vlan (all | vlan-name)>
<vpn vpn>
```

Syntax (TX Matrix and TX Matrix Plus Routers)

```
show route forwarding-table
<detail | extensive | summary>
<all>
<ccc interface-name>
<destination destination-prefix>
<family family | matching matching>
<interface-name interface-name>
<matching matching>
<label name>
<lcc number>
<multicast>
<table routing-instance-name>
<vpn vpn>
```

Description

Display the Routing Engine's forwarding table, including the network-layer prefixes and their next hops. This command is used to help verify that the routing protocol process has relayed the correction information to the forwarding table. The Routing Engine constructs and maintains one or more routing tables. From the routing tables, the Routing Engine derives a table of active routes, called the forwarding table.

**NOTE:** The Routing Engine copies the forwarding table to the Packet Forwarding Engine, the part of the router that is responsible for forwarding packets. To display the entries in the Packet Forwarding Engine's forwarding table, use the `show pfe route` command.

Options

- | | |
|-------------------------------------|---|
| none | Display the routes in the forwarding tables. By default, the <code>show route forwarding-table</code> command does not display information about private, or internal, forwarding tables. |
| detail extensive summary | (Optional) Display the specified level of output. |
| all | (Optional) Display routing table entries for all forwarding tables, including private, or internal, tables. |

bridge-domain (all <i>bridge-domain-name</i>)	(MX Series routers only) (Optional) Display route entries for all bridge domains or the specified bridge domain.
ccc <i>interface-name</i>	(Optional) Display route entries for the specified circuit cross-connect interface.
destination <i>destination-prefix</i>	(Optional) Destination prefix.
family <i>family</i>	(Optional) Display routing table entries for the specified family: bridge (ccc destination detail extensive interface-name label learning-vlan-id matching multicast summary table vlan vpn), ethernet-switching, evpn, fibre-channel, fmembers, inet, inet6, iso, mcsnoop-inet, mcsnoop-inet6, mpls, satellite-inet, satellite-inet6, satellite-vpls, tnp, unix, vpls, or vlan-classification.
interface-name <i>interface-name</i>	(Optional) Display routing table entries for the specified interface.
label <i>name</i>	(Optional) Display route entries for the specified label.
lcc <i>number</i>	<p>(TX Matrix and TX matrix Plus routers only) (Optional) On a routing matrix composed of a TX Matrix router and T640 routers, display information for the specified T640 router (or line-card chassis) connected to the TX Matrix router. On a routing matrix composed of the TX Matrix Plus router and T1600 or T4000 routers, display information for the specified router (line-card chassis) connected to the TX Matrix Plus router.</p> <p>Replace <i>number</i> with the following values depending on the LCC configuration:</p> <ul style="list-style-type: none"> • 0 through 3, when T640 routers are connected to a TX Matrix router in a routing matrix. • 0 through 3, when T1600 routers are connected to a TX Matrix Plus router in a routing matrix. • 0 through 7, when T1600 routers are connected to a TX Matrix Plus router with 3D SIBs in a routing matrix. • 0, 2, 4, or 6, when T4000 routers are connected to a TX Matrix Plus router with 3D SIBs in a routing matrix.
learning-vlan-id <i>learning-vlan-id</i>	(MX Series routers only) (Optional) Display learned information for all VLANs or for the specified VLAN.
matching <i>matching</i>	(Optional) Display routing table entries matching the specified prefix or prefix length.
multicast	(Optional) Display routing table entries for multicast routes.

- table** (Optional) Display route entries for all the routing tables in the main routing instance or for the specified routing instance. If your device supports logical systems, you can also display route entries for the specified logical system and routing instance. To view the routing instances on your device, use the `show route instance` command.
- vlan (all | *vlan-name*)** (Optional) Display information for all VLANs or for the specified VLAN.
- vpn *vpn*** (Optional) Display routing table entries for a specified VPN.

Required Privilege Level

view

Output Fields

[Table 43 on page 1853](#) lists the output fields for the `show route forwarding-table` command. Output fields are listed in the approximate order in which they appear. Field names might be abbreviated (as shown in parentheses) when no level of output is specified, or when the `detail` keyword is used instead of the `extensive` keyword.

Table 43: show route forwarding-table Output Fields

Field Name	Field Description	Level of Output
Logical system	Name of the logical system. This field is displayed if you specify the <code>table <i>logical-system-name/routing-instance-name</i></code> option on a device that is configured for and supports logical systems.	All levels
Routing table	Name of the routing table (for example, <code>inet</code> , <code>inet6</code> , <code>mpls</code>).	All levels

Table 43: show route forwarding-table Output Fields (*Continued*)

Field Name	Field Description	Level of Output
Enabled protocols	<p>The features and protocols that have been enabled for a given routing table. This field can contain the following values:</p> <ul style="list-style-type: none"> • BUM hashing—BUM hashing is enabled. • MAC Stats—Mac Statistics is enabled. • Bridging—Routing instance is a normal layer 2 bridge. • No VLAN—No VLANs are associated with the bridge domain. • All VLANs—The <code>vlan-id all</code> statement has been enabled for this bridge domain. • Single VLAN—Single VLAN ID is associated with the bridge domain. • MAC action drop—New MACs will be dropped when the MAC address limit is reached. • Dual VLAN—Dual VLAN tags are associated with the bridge domain • No local switching—No local switching is enabled for this routing instance.. • Learning disabled—Layer 2 learning is disabled for this routing instance. • MAC limit reached—The maximum number of MAC addresses that was configured for this routing instance has been reached. • VPLS—The VPLS protocol is enabled. • No IRB I2-copy—The <code>no-irb-layer-2-copy</code> feature is enabled for this routing instance. • ACKed by all peers—All peers have acknowledged this routing instance. • BUM Pruning—BUM pruning is enabled on the VPLS instance. • Def BD VXLAN—VXLAN is enabled for the default bridge domain. • EVPN—EVPN protocol is enabled for this routing instance. 	All levels

Table 43: show route forwarding-table Output Fields (*Continued*)

Field Name	Field Description	Level of Output
	<ul style="list-style-type: none"> • Def BD OVSDDB—Open vSwitch Database (OVSDDB) is enabled on the default bridge domain. • Def BD Ingress replication—VXLAN ingress node replication is enabled on the default bridge domain. • L2 backhaul—Layer 2 backhaul is enabled. • FRR optimize—Fast reroute optimization • MAC pinning—MAC pinning is enabled for this bridge domain. • MAC Aging Timer—The MAC table aging time is set per routing instance. • EVPN VXLAN—This routing instance supports EVPN with VXLAN encapsulation. • PBBN—This routing instance is configured as a provider backbone bridged network. • PBN—This routing instance is configured as a provider bridge network. • ETREE—The ETREE protocol is enabled on this EVPN routing instance. • ARP/NDP suppression—EVPN ARP NDP suppression is enabled in this routing instance. • Def BD EVPN VXLAN—EVPN VXLAN is enabled for the default bridge domain. • MPLS control word—Control word is enabled for this MPLS routing instance. 	
Address family	Address family (for example, IP, IPv6, ISO, MPLS, and VPLS).	All levels
Destination	Destination of the route.	detail extensive

Table 43: show route forwarding-table Output Fields (*Continued*)

Field Name	Field Description	Level of Output
Route Type (Type)	<p>How the route was placed into the forwarding table. When the detail keyword is used, the route type might be abbreviated (as shown in parentheses):</p> <ul style="list-style-type: none"> • cloned (clon)—(TCP or multicast only) Cloned route. • destination (dest)—Remote addresses directly reachable through an interface. • destination down (iddn)—Destination route for which the interface is unreachable. • interface cloned (ifcl)—Cloned route for which the interface is unreachable. • route down (ifdn)—Interface route for which the interface is unreachable. • ignore (ignr)—Ignore this route. • interface (intf)—Installed as a result of configuring an interface. • permanent (perm)—Routes installed by the kernel when the routing table is initialized. • user—Routes installed by the routing protocol process or as a result of the configuration. 	All levels
Route Reference (RtRef)	Number of routes to reference.	detail extensive

Table 43: show route forwarding-table Output Fields (*Continued*)

Field Name	Field Description	Level of Output
Flags	<p>Route type flags:</p> <ul style="list-style-type: none"> • none—No flags are enabled. • accounting—Route has accounting enabled. • cached—Cache route. • incoming-iface <i>interface-number</i>—Check against incoming interface. • prefix load balance—Load balancing is enabled for this prefix. • rt nh decoupled—Route has been decoupled from the next hop to the destination. • sent to PFE—Route has been sent to the Packet Forwarding Engine. • static—Static route. 	extensive
Next hop	<p>IP address of the next hop to the destination.</p> <p>NOTE: For static routes that use point-to-point (P2P) outgoing interfaces, the next-hop address is not displayed in the output.</p>	detail extensive

Table 43: show route forwarding-table Output Fields (*Continued*)

Field Name	Field Description	Level of Output
Next hop Type (Type)	<p>Next-hop type. When the detail keyword is used, the next-hop type might be abbreviated (as indicated in parentheses):</p> <ul style="list-style-type: none"> • broadcast (bcst)—Broadcast. • deny—Deny. • discard (dscd) —Discard. • hold—Next hop is waiting to be resolved into a unicast or multicast type. • indexed (idxd)—Indexed next hop. • indirect (indr)—Indirect next hop. • local (locl)—Local address on an interface. • routed multicast (mcrt)—Regular multicast next hop. • multicast (mcst)—Wire multicast next hop (limited to the LAN). • multicast discard (mdsc)—Multicast discard. • multicast group (mgrp)—Multicast group member. • receive (recv)—Receive. • reject (rjct)—Discard. An ICMP unreachable message was sent. • resolve (rslv)—Resolving the next hop. • unicast (ucst)—Unicast. • unilist (ulst)—List of unicast next hops. A packet sent to this next hop goes to any next hop in the list. • VxLAN Local—EVPN Type 5 route in kernel. 	detail extensive
Index	Software index of the next hop that is used to route the traffic for a given prefix.	detail extensive none

Table 43: show route forwarding-table Output Fields (*Continued*)

Field Name	Field Description	Level of Output
Route interface-index	Logical interface index from which the route is learned. For example, for interface routes, this is the logical interface index of the route itself. For static routes, this field is zero. For routes learned through routing protocols, this is the logical interface index from which the route is learned.	extensive
Reference (NhRef)	Number of routes that refer to this next hop.	detail extensive none
Next-hop interface (Netif)	Interface used to reach the next hop.	detail extensive none
Weight	Value used to distinguish primary, secondary, and fast reroute backup routes. Weight information is available when MPLS label-switched path (LSP) link protection, node-link protection, or fast reroute is enabled, or when the standby state is enabled for secondary paths. A lower weight value is preferred. Among routes with the same weight value, load balancing is possible (see the Balance field description).	extensive
Balance	Balance coefficient indicating how traffic of unequal cost is distributed among next hops when a router is performing unequal-cost load balancing. This information is available when you enable BGP multipath load balancing.	extensive
RPF interface	List of interfaces from which the prefix can be accepted. Reverse path forwarding (RPF) information is displayed only when rpf-check is configured on the interface.	extensive

Sample Output

show route forwarding-table

```

user@host> show route forwarding-table
Routing table: default.inet
Internet:

```

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	46	4	
0.0.0.0/32	perm	0		dscd	44	1	
172.16.1.0/24	ifdn	0		rslv	608	1	ge-2/0/1.0
172.16.1.0/32	iddn	0	172.16.1.0	recv	606	1	ge-2/0/1.0
172.16.1.1/32	user	0		rjct	46	4	
172.16.1.1/32	intf	0	172.16.1.1	loc1	607	2	
172.16.1.1/32	iddn	0	172.16.1.1	loc1	607	2	
172.16.1.255/32	iddn	0	ff:ff:ff:ff:ff:ff	bcst	605	1	ge-2/0/1.0
10.0.0.0/24	intf	0		rslv	616	1	ge-2/0/0.0
10.0.0.0/32	dest	0	10.0.0.0	recv	614	1	ge-2/0/0.0
10.0.0.1/32	intf	0	10.0.0.1	loc1	615	2	
10.0.0.1/32	dest	0	10.0.0.1	loc1	615	2	
10.0.0.255/32	dest	0	10.0.0.255	bcst	613	1	ge-2/0/0.0
10.1.1.0/24	ifdn	0		rslv	612	1	ge-2/0/1.0
10.1.1.0/32	iddn	0	10.1.1.0	recv	610	1	ge-2/0/1.0
10.1.1.1/32	user	0		rjct	46	4	
10.1.1.1/32	intf	0	10.1.1.1	loc1	611	2	
10.1.1.1/32	iddn	0	10.1.1.1	loc1	611	2	
10.1.1.255/32	iddn	0	ff:ff:ff:ff:ff:ff	bcst	609	1	ge-2/0/1.0
10.209.0.0/16	user	0	10.209.63.254	ucst	419	20	fxp0.0
10.209.0.0/16	user	1	0:12:1e:ca:98:0	ucst	419	20	fxp0.0
10.209.0.0/18	intf	0		rslv	418	1	fxp0.0
10.209.0.0/32	dest	0	10.209.0.0	recv	416	1	fxp0.0
10.209.2.131/32	intf	0	10.209.2.131	loc1	417	2	
10.209.2.131/32	dest	0	10.209.2.131	loc1	417	2	
10.209.17.55/32	dest	0	0:30:48:5b:78:d2	ucst	435	1	fxp0.0
10.209.63.42/32	dest	0	0:23:7d:58:92:ca	ucst	434	1	fxp0.0
10.209.63.254/32	dest	0	0:12:1e:ca:98:0	ucst	419	20	fxp0.0
10.209.63.255/32	dest	0	10.209.63.255	bcst	415	1	fxp0.0
10.227.0.0/16	user	0	10.209.63.254	ucst	419	20	fxp0.0

...

Routing table: iso

ISO:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	27	1	
47.0005.80ff.f800.0000.0108.0003.0102.5524.5220.00							
intf 0			loc1 28				1

Routing table: inet6

Internet6:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	6	1	
ff00::/8	perm	0		mdsc	4	1	
ff02::1/128	perm	0	ff02::1	mcst	3	1	

Routing table: ccc

MPLS:

Interface.Label	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	16	1	
100004(top)fe-0/0/1.0							

show route forwarding-table detail

```
user@host> show route forwarding-table detail
```

Routing table: inet

Internet:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	user	2	0:90:69:8e:b1:1b	ucst	132	4	fxp0.0
default	perm	0		rjct	14	1	
10.1.1.0/24	intf	0	ff.3.0.21	ucst	322	1	so-5/3/0.0
10.1.1.0/32	dest	0	10.1.1.0	recv	324	1	so-5/3/0.0
10.1.1.1/32	intf	0	10.1.1.1	loc1	321	1	
10.1.1.255/32	dest	0	10.1.1.255	bcst	323	1	so-5/3/0.0
10.21.21.0/24	intf	0	ff.3.0.21	ucst	326	1	so-5/3/0.0
10.21.21.0/32	dest	0	10.21.21.0	recv	328	1	so-5/3/0.0
10.21.21.1/32	intf	0	10.21.21.1	loc1	325	1	
10.21.21.255/32	dest	0	10.21.21.255	bcst	327	1	so-5/3/0.0
127.0.0.1/32	intf	0	127.0.0.1	loc1	320	1	
172.17.28.19/32	clon	1	192.168.4.254	ucst	132	4	fxp0.0
172.17.28.44/32	clon	1	192.168.4.254	ucst	132	4	fxp0.0

...

Routing table: private1__inet

Internet:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	46	1	
10.0.0.0/8	intf	0		rslv	136	1	fxp1.0
10.0.0.0/32	dest	0	10.0.0.0	recv	134	1	fxp1.0
10.0.0.4/32	intf	0	10.0.0.4	loc1	135	2	
10.0.0.4/32	dest	0	10.0.0.4	loc1	135	2	

...

Routing table: iso

ISO:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	38	1	

Routing table: inet6

Internet6:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	22	1	
ff00::/8	perm	0		mdsc	21	1	
ff02::1/128	perm	0	ff02::1	mcst	17	1	

...

Routing table: mpls

MPLS:

Destination	Type	RtRef	Next hop	Type	Index	NhRef	Netif
default	perm	0		rjct	28	1	

show route forwarding-table destination extensive (EVPN Type 5 route with Type 2 and Type 5 route coexistence)

user@device> show route forwarding-table destination 10.1.1.20 table vrf1 extensive

Routing table: vrf1.inet [Index 9]

Internet:

Destination: 10.1.1.20/32

Route type: user

Route reference: 0

Route interface-index: 0

Multicast RPF nh index: 0

P2mpidx: 0

Flags: sent to PFE, VxLAN Local

Nexthop:

Next-hop type: composite Index: 2694 Reference: 7

Next-hop type: indirect Index: 524326 Reference: 2

Next-hop type: unilist Index: 524288 Reference: 5

Nexthop: 10.1.1.1

Next-hop type: unicast Index: 1724 Reference: 15

Next-hop interface: xe-0/0/1.0 Weight: 0x0

Next-hop: 10.1.1.4 Next-hop type: unicast Index: 1725 Reference: 15
 Next-hop interface: xe-0/0/4.0 Weight: 0x0

show route forwarding-table extensive (RPF)

The next example is based on the following configuration, which enables an RPF check on all routes that are learned from this interface, including the interface route:

```
so-1/1/0 {
  unit 0 {
    family inet {
      rpf-check;
      address 192.0.2.2/30;
    }
  }
}
```

Release Information

Command introduced before Junos OS Release 7.4.

Option bridge-domain introduced in Junos OS Release 7.5

Option learning-vlan-id introduced in Junos OS Release 8.4

Options all and vlan introduced in Junos OS Release 9.6.

RELATED DOCUMENTATION

| *show route instance*

show security group-vpn member ike security-associations

IN THIS SECTION

● Syntax | 1864

- [Description | 1864](#)
- [Options | 1864](#)
- [Required Privilege Level | 1864](#)
- [Output Fields | 1865](#)
- [Sample Output | 1867](#)
- [Sample Output | 1868](#)
- [Release Information | 1868](#)

Syntax

```
show security group-vpn member ike security-associations [brief | detail] [index sa-index] [peer-ipaddress]
```

Description

Display IKE security associations (SAs) for group members. Group VPNv2 is supported on SRX300, SRX320, SRX340, SRX345, SRX550HM, SRX1500, SRX4100, SRX4200, and SRX4600 devices and vSRX instances.

Options

- **none**—Display summary information about all IKE SAs for the group members.
- **brief**—(Optional) Display summary output.
- **detail**—(Optional) Display detailed output.
- **index***sa-index*—(Optional) Display detailed information about the specified SA identified by index number. To obtain a list of all SAs that includes their index numbers, use the command with no options.
- **peer***ipaddress*—(Optional) Display information about the SA with the specified peer.

Required Privilege Level

view

Output Fields

Table 44 on page 1865 lists the output fields for the `show security group-vpn member ike security-associations` command. Output fields are listed in the approximate order in which they appear.

Table 44: show security group-vpn member ike security-associations Output Fields

Field Name	Field Description
Index	Index number of an SA. This number is an internally generated number you can use to display information about a single SA.
State	State of the IKE security associations: <ul style="list-style-type: none"> DOWN—SA has not been negotiated with the peer. UP—SA has been negotiated with the peer.
Initiator cookie	Random number, called a cookie, which is sent to the remote node when the IKE negotiation is triggered.
Responder cookie	Random number generated by the remote node and sent back to the initiator as a verification that the packets were received. A cookie is aimed at protecting the computing resources from attack without spending excessive CPU resources to determine the cookie's authenticity.
Mode	Negotiation method agreed on by the two IPsec endpoints, or peers, used to exchange information between themselves. Each exchange type determines the number of messages and the payload types that are contained in each message. The modes, or exchange types, are <ul style="list-style-type: none"> main—The exchange is done with six messages. This mode or exchange type encrypts the payload, protecting the identity of the neighbor. The authentication method used is displayed: preshared keys or certificate. aggressive—The exchange is done with three messages. This mode or exchange type does not encrypt the payload, leaving the identity of the neighbor unprotected.
Remote Address	IP address of the destination peer with which the local peer communicates.

Table 44: show security group-vpn member ike security-associations Output Fields (Continued)

Field Name	Field Description
IKE Peer	IP address of the destination peer with which the local peer communicates.
Exchange type	<p>Negotiation method agreed on by the two IPsec endpoints, or peers, used to exchange information between themselves. Each exchange type determines the number of messages and the payload types that are contained in each message. The modes, or exchange types, are</p> <ul style="list-style-type: none"> • main—The exchange is done with six messages. This mode or exchange type encrypts the payload, protecting the identity of the neighbor. The authentication method used is displayed: preshared keys or certificate. • aggressive—The exchange is done with three messages. This mode or exchange type does not encrypt the payload, leaving the identity of the neighbor unprotected.
Authentication method	<p>Method the server uses to authenticate the source of IKE messages:</p> <ul style="list-style-type: none"> • pre-shared-keys—Preshared key for encryption and decryption that both participants must have before beginning tunnel negotiations.
Local	Address of the local peer.
Lifetime	Number of seconds remaining until the IKE SA expires.

Table 44: show security group-vpn member ike security-associations Output Fields (Continued)

Field Name	Field Description
Algorithms	<p>Internet Key Exchange (IKE) algorithms used to encrypt and secure exchanges between the peers during the IPsec Phase 2 process:</p> <ul style="list-style-type: none"> • Authentication—Type of authentication algorithm used. <ul style="list-style-type: none"> • sha-256—Secure Hash Algorithm 256 authentication. • sha-384—Secure Hash Algorithm 384 authentication. • Encryption—Type of encryption algorithm used. <ul style="list-style-type: none"> • aes-256-cbc—Advanced Encryption Standard (AES) 256-bit encryption. • aes-192-cbc— AES192-bit encryption • aes-128-cbc—AES 128-bit encryption.
Traffic statistics	<ul style="list-style-type: none"> • Input bytes—Number of bytes received. • Output bytes—Number of bytes transmitted. • Input packets—Number of packets received. • Output packets—Number of packets transmitted.

Sample Output

show security group-vpn member ike security-associations

```

user@host> show security group-vpn member ike security-associations
Index   State Initiator cookie Responder cookie Mode      Remote Address
4736345 UP      70611c65603d53da 6e0888777ad10f8d Main      192.0.2.3

```

Sample Output

show security group-vpn member ike security-associations detail

```

user@host> show security group-vpn member ike security-associations detail
IKE peer 192.0.2.5, Index 5824842, Gateway Name: group1_2
  Role: Initiator, State: UP
  Initiator cookie: fc866556b8afe4cd, Responder cookie: 1238de6b8a89de44
  Exchange type: Main, Authentication method: Pre-shared-keys
  Local: 192.0.2.7:848, Remote: 192.0.2.5:848
  Lifetime: Expires in 2 seconds
  Peer ike-id: 192.0.2.5
  Xauth user-name: not available
  Xauth assigned IP: 0.0.0.0
  Algorithms:
    Authentication      : hmac-sha1-96
    Encryption          : 3des-cbc
    Pseudo random function: hmac-sha1
    Diffie-Hellman group : DH-group-2
  Traffic statistics:
    Input  bytes :          2044
    Output bytes :          900
    Input  packets:           7
    Output packets:           7
  Flags: IKE SA is created

```

Release Information

Command introduced in Junos OS Release 10.2.

RELATED DOCUMENTATION

clear security group-vpn member ike security-associations

[Group VPNv2 Overview](#)

show security pki ca-certificate (View)

IN THIS SECTION

- [Syntax | 1869](#)
- [Description | 1869](#)
- [Options | 1869](#)
- [Required Privilege Level | 1870](#)
- [Output Fields | 1870](#)
- [Sample Output | 1872](#)
- [Release Information | 1874](#)

Syntax

```
show security pki ca-certificate  
<brief | detail>  
<ca-profile ca-profile-name>
```

Description

Display information about the certificate authority (CA) public key infrastructure (PKI) digital certificates configured on the device.

The FIPS image does not permit the use of MD5 fingerprints. Therefore, MD5 fingerprints are not included when a certificate is displayed using this command. The SHA-1 fingerprint that is currently displayed is retained in the FIPS image. The Simple Certificate Enrollment Protocol (SCEP) is disabled in the FIPS image.

Options

- none—Display basic information about all configured CA certificates.
- brief | detail—(Optional) Display the specified level of output.
- ca-profile *ca-profile-name*— (Optional) Display information about only the specified CA certificate.

Required Privilege Level

view

Output Fields

Table 45 on page 1870 lists the output fields for the `show security pki ca-certificate` command. Output fields are listed in the approximate order in which they appear.

Table 45: show security pki ca-certificate Output Fields

Field Name	Field Description
CA profile	<p>Name of the CA profile in the CA certificate.</p> <p>Starting in Junos OS Release 21.4R1, you can view this information by executing the <code>show security pki ca-certificate <brief detail></code> command.</p>
Certificate identifier	<p>Name of the digital certificate.</p>
Certificate version	<p>Revision number of the digital certificate.</p>
Serial number	<p>Unique serial number of the digital certificate.</p>
Issuer	<p>Authority that issued the digital certificate, including details of the authority organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none">• Organization—Organization of origin.• Organizational unit—Department within an organization.• Country—Country of origin.• Locality—Locality of origin.• Common name—Name of the authority.

Table 45: show security pki ca-certificate Output Fields (Continued)

Field Name	Field Description
Subject	<p>Details of the digital certificate holder organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> • Organization—Organization of origin. • Organizational unit—Department within an organization. • Country—Country of origin. • Locality—Locality of origin. • Common name—Name of the authority. <p>If the certificate contains multiple subfield entries, all entries are displayed.</p>
Subject string	Subject field as it appears in the certificate.
Validity	<p>Time period when the digital certificate is valid. Values are:</p> <ul style="list-style-type: none"> • Not before—Start time when the digital certificate becomes valid. • Not after—End time when the digital certificate becomes invalid.
Public key algorithm	Encryption algorithm used with the private key, such as rsaEncryption(1024 bits).
Signature algorithm	Encryption algorithm that the CA used to sign the digital certificate, such as sha1WithRSAEncryption.
Certificate Policy	Policy Identifier—One or more policy object identifiers (OIDs).
Use for key	Use of the public key, such as Certificate signing, CRL signing, Digital signature, or Data encipherment.

Table 45: show security pki ca-certificate Output Fields (Continued)

Field Name	Field Description
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate. Starting in Junos OS Release 21.4R1, you can also view the SHA256 fingerprint for a local certificate along with SHA1 and MD5 fingerprints.
Distribution CRL	Distinguished name information and the URL for the certificate revocation list (CRL) server.

Sample Output

show security pki ca-certificate (MX240, MX480, MX960, SRX Series Devices and vSRX)

Starting in Junos OS Release 21.4R1, execute the `show security pki ca-certificate <ca-profile ca-profile-name>` command to view the CA profile name printed in the CA. The CA profile field in the output represents the CA profile name printed in the CA. In this sample, the CA profile name printed in the CA certificate is a Root-CA.

```

user@host> show security pki ca-certificate ca-profile Root-CA
LSYS: root-logical-system
  CA profile: Root-CA
Certificate identifier: Root-CA
  Issued to: Root-CA, Issued by: C = us, O = juniper, CN = Root-CA
Validity:
  Not before: 05-19-2021 08:05 UTC
  Not after: 05-17-2031 08:05 UTC
Public key algorithm: rsaEncryption(2048 bits)
Keypair Location: Keypair generated locally

```

show security pki ca-certificate ca-profile detail (MX240, MX480, MX960, SRX Series Devices and vSRX)

Starting in Junos OS Release 21.4R1, execute the `show security pki ca-certificate <ca-profile ca-profile-name> detail` command to view:

- the CA profile name printed in the CA. The CA profile field in the output represents the CA profile name printed in the CA. In this sample, the CA profile name printed in the CA certificate is Root-CA.
- the SHA256 fingerprint for a CA certificate.

```
user@host> show security pki ca-certificate ca-profile Root-CA detail
```

```
LSYS: root-logical-system
```

```
CA profile: Root-CA
```

```
Certificate identifier: Root-CA
```

```
Certificate version: 3
```

```
Serial number:
```

```
hexadecimal: 0x00000d87
```

```
decimal: 3463
```

```
Issuer:
```

```
Organization: juniper, Country: us, Common name: Root-CA
```

```
Subject:
```

```
Organization: juniper, Country: us, Common name: Root-CA
```

```
Subject string:
```

```
C=us, O=juniper, CN=Root-CA
```

```
Validity:
```

```
Not before: 05-19-2021 08:05 UTC
```

```
Not after: 05-17-2031 08:05 UTC
```

```
Public key algorithm: rsaEncryption(2048 bits)
```

```
30:82:01:0a:02:82:01:01:00:cf:28:0c:04:ae:f0:89:f1:0a:cc:b3
```

```
5a:0a:d9:c7:0a:f3:90:2e:7d:06:73:a4:65:94:3d:53:d4:25:2e:40
```

```
11:98:4e:2f:52:53:1e:b3:69:2b:80:89:2e:b0:17:3a:3d:96:b3:70
```

```
26:f7:da:ae:4e:ba:15:50:db:42:bd:bc:8c:0c:fd:5b:8e:f5:fb:74
```

```
3c:48:8f:ec:c0:6a:5f:46:b3:1f:19:10:10:c4:e2:7e:e7:c5:ed:e1
```

```
ff:64:01:01:f5:69:82:47:7a:2f:4c:6f:52:df:a4:06:fb:f8:ac:04
```

```
3c:46:51:08:b4:5d:71:f3:69:a1:22:cb:53:18:74:bc:bf:4d:6b:4a
```

```
b0:cd:4c:60:38:5f:ec:a8:6d:6c:77:dd:ed:14:a1:5f:c7:84:a7:74
```

```
7a:6c:45:fa:4e:8a:db:8d:6c:ec:6a:25:fa:38:54:97:ac:0e:d0:12
```

```
48:e5:0f:10:b2:3d:b0:de:95:53:d3:c8:a5:dc:6f:ed:f5:7d:49:e3
```

```
b5:68:98:24:a7:8b:5d:a7:e5:98:de:51:b5:20:68:15:22:64:f1:c3
```

```
cc:c4:1a:1a:be:bf:cb:fb:a7:79:92:a8:45:a3:ef:0d:2e:0f:21:f4
```

```
5e:9d:77:1f:32:68:45:e1:93:ab:27:88:a6:c6:b2:81:55:a1:6d:c6
```

```
81:85:1b:7f:61:02:03:01:00:01
```

```
Signature algorithm: sha256WithRSAEncryption
```

```
Distribution CRL:
```

```
http://10.48.148.132:8080/crl-as-der/currentcrl-11.crl?id=11
```

Authority Information Access OCSP:

<http://10.48.148.132:8090/Root-CA/>

Use for key: CRL signing, Certificate signing, Key encipherment, Digital signature

Fingerprint:

b4:65:6b:a2:28:01:b1:76:26:8b:8f:4f:53:b9:50:a6:eb:df:39:3a (sha1)

14:c9:4f:da:96:15:94:6f:fa:5e:fd:60:ce:47:90:97 (md5)

49:ee:63:56:72:0b:f4:87:08:75:c9:1a:fa:6c:4d:c7:7c:2f:a2:21:31:68:30:67:87:37:cd:c0:86:34:1c:76
(sha256)

Release Information

Command modified in Junos OS Release 8.5.

Subject string output field added in Junos OS Release 12.1X44-D10. Policy identifier output field added in Junos OS Release 12.3X48-D10.

CA profile and (sha256) for Fingerprint output field added in Junos OS Release 21.4R1.

RELATED DOCUMENTATION

[ca-profile \(Security PKI\)](#)

[request security pki ca-certificate verify \(Security\)](#)

show vpls connections

IN THIS SECTION

- [Syntax | 1875](#)
- [Description | 1875](#)
- [Options | 1875](#)
- [Required Privilege Level | 1876](#)
- [Output Fields | 1876](#)
- [Sample Output | 1883](#)
- [Release Information | 1890](#)

Syntax

```
show vpls connections
<brief | extensive>
<down | up | up-down>
<history>
<instance instance-name local-site local-site-name remote-site remote-site-name>
<instance-history>
<logical-system (all | logical-system-name)>
<status>
<summary>
```

Description

(T Series and M Series routers, except for the M160 router) Display virtual private LAN service (VPLS) connection information.

Options

none	Display information about all VPLS connections for all routing instances.
brief extensive	(Optional) Display the specified level of output.
down up up-down	(Optional) Display nonoperational, operational, or both types of connections.
history	(Optional) Display information about connection history.
instance <i>instance-name</i>	(Optional) Display the VPLS connections for the specified routing instance only.
instance-history	(Optional) Display information about connection history for a particular instance.
local-site <i>local-site-name</i>	(Optional) Display the VPLS connections for the specified local site name or ID only.
remote-site <i>remote-site-name</i>	(Optional) Display the VPLS connections for the specified remote site name or ID only. Label block size information is always shown as 0 when using this option.

logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.
status	(Optional) Display information about the connection and interface status.
summary	(Optional) Display summary of all VPLS connections information.

Required Privilege Level

view

Output Fields

[Table 46 on page 1876](#) lists the output fields for the `show vpls connections` command. Output fields are listed in the approximate order in which they appear.

Table 46: show vpls connections Output Fields

Field Name	Field Description
Instance	Name of the VPLS instance.
Local site	Name of the local site.
VPLS-id	Identifier for the VPLS site.
Number of local interfaces	Number of interfaces configured for the local site.
Number of local interfaces up	Number of interfaces configured for the local site that are currently up.
IRB interface present	Indicates whether or not an integrated routing and bridging (IRB) interface is present (yes or no).

Table 46: show vpls connections Output Fields (*Continued*)

Field Name	Field Description
Intf	<p>List of all of the interfaces configured for the local site. The types of interfaces can include VPLS virtual loopback tunnel interfaces and label-switched interfaces. Any interface that supports VPLS could be listed here.</p> <p>Virtual loopback tunnel interfaces are displayed using the <code>vt-fpc/pic/port.nnnnn</code> format. Label-switched interfaces are displayed using the <code>lsi.nnnnn</code> format. In both cases, <code>nnnnn</code> is a dynamically generated virtual port used to transport and receive packets from other provider edge (PE) routers in the VPLS domain.</p> <p>Each interface might include the following information:</p> <ul style="list-style-type: none"> • Identification as a VPLS interface • Name of the associated VPLS routing instance • Local site number • Remote site number • VPLS neighbor address • VPLS identifier
Interface flags	<p>Flag associated with the interface. Can include the following:</p> <ul style="list-style-type: none"> • VC-Down—The virtual circuit associated with this interface is down.
Label-base	First label in a block of labels. A remote PE router uses this first label when sending traffic toward the advertising PE router.
Offset	Displays the VPLS Edge (VE) block offset in the Layer 2 VPN NLRI. The VE block offset is used to identify a label block from which a particular label value is selected to setup a pseudowire for a remote site. The block offset value itself indicates the starting VE ID that maps to the label base contained in the VPLS NLRI advertisement.
Size	Label block size. A configurable value that represents the number of label blocks required to cover all the pseudowires for the remote peer. Acceptable configuration values are: 2, 4, 8 and 16. The default value is 2. A value of 0 will be displayed when using the remote-site option.

Table 46: show vpls connections Output Fields (Continued)

Field Name	Field Description
Range	Label block range. A value that keeps track of the numbers of remote sites discovered within each label block.
Preference	Preference value advertised for a VPLS site. When multiple PE routers are assigned the same VE ID for multihoming, you might need to specify that a particular PE router acts as the designated forwarder by configuring the site preference value. The site preference indicates the degree of preference for a particular customer site. The site preference is one of the tie-breaking criteria used in a designated forwarder election.
status-vector	Bit vector advertising the state of local PE-CE circuits to remote PE routers. A bit value of 0 indicates that the local circuit and LSP tunnel to the remote PE router are up, whereas a value of 1 indicates either one or both are down.
connection-site	Name of the connection site.
Neighbor	IP address and VPLS identifier for the VPLS neighbor. If multiple pseudowires have been configured, the IP address will also show the PW-specific "vpls-id-list" on page 1722, for example, 203.0.113.144 (vpls-id 200).
Type	Type of connection: loc (local) or rmt (remote).

Table 46: show vpls connections Output Fields (*Continued*)

Field Name	Field Description
St	<p>Status of the VPLS connection (corresponds with Legend for Connection Status):</p> <ul style="list-style-type: none"> • EI—The local VPLS interface is configured with an encapsulation that is not supported. • EM—The encapsulation type received on this VPLS connection from the neighbor does not match the local VPLS connection interface encapsulation type. • VC-Dn—The virtual circuit is currently down. • CM—The two routers do not agree on a control word, which causes a control word mismatch. • CN—The virtual circuit is not provisioned properly. • OR—The label associated with the virtual circuit is out of range. • OL—No advertisement has been received for this virtual circuit from the neighbor. There is no outgoing label available for use by this virtual circuit. • LD—All of the CE-facing interfaces to the local site are down. Therefore, the connection to the local site is signaled as down to the other PE routers. No pseudowires can be established. • RD—All the interfaces to the remote neighbor are down. Therefore, the remote site has been signaled as down to the other PE routers. No pseudowires can be established. • LN—The local site has lost path selection to the remote site and therefore no pseudowires can be established from this local site. • RN—The remote site has lost path selection to a local site or other remote site and therefore no pseudowires are established to this remote site. <p>In a multihoming configuration, one multihomed PE site displays the state LN, and the other multihomed PE site displays the state RN in the following circumstances:</p> <ul style="list-style-type: none"> • The multihomed links are both configured to be the backup site. • The two multihomed PE routers have the same site ID, but have a peering relationship with a route reflector (RR) that has a different site ID. <ul style="list-style-type: none"> • XX—The VPLS connection is down for an unknown reason. This is a programming error.

Table 46: show vpls connections Output Fields (*Continued*)

Field Name	Field Description
	<ul style="list-style-type: none"> • MM—The MTU for the local site and the remote site do not match. • BK—The router is using a backup connection. • PF—Profile parse failure. • RS—The remote site is in a standby state. • NC—The interface encapsulation is not configured as an appropriate CCC, TCC, or VPLS encapsulation. • WE—The encapsulation configured for the interface does not match the encapsulation configured for the associated connection within the VPLS routing instance. • NP—The router detects that interface hardware is not present. The hardware might be offline, a PIC might not be of the desired type, or the interface might be configured in a different routing instance. • -->—Only the outbound connection is up. • <—Only the inbound connection is up. • Up—The VPLS connection is operational. • Dn—The VPLS connection is down. • CF—The router cannot find enough bandwidth to the remote router to satisfy the VPLS connection bandwidth requirement. • SC—The local site identifier matches the remote site identifier. No pseudowire can be established between these two sites. You should configure different values for the local and remote site identifiers. • LM—The local site identifier is not the minimum designated, meaning it is not the lowest. There is another local site with a lower site identifier. Pseudowires are not being established to this local site, and the associated local site identifier is not being used to distribute VPLS label blocks. However, this is not an error state. Traffic continues to be forwarded to the PE router interfaces connected to the local sites when the local sites are in this state. • RM—The remote site identifier is not the minimum designated, meaning it is not the lowest. There is another remote site connected to the same PE router which has

Table 46: show vpls connections Output Fields (*Continued*)

Field Name	Field Description
	<p>lower site identifier. The PE router cannot established a pseudowire to this remote site and the associated remote site identifier cannot be used to distribute VPLS label blocks. However, this is not an error state. Traffic can continue to be forwarded to the PE router interface connected to this remote site when the remote site is in this state.</p> <ul style="list-style-type: none"> • IL—The incoming packets for the VPLS connection have no MPLS label. • MI—The configured mesh group identifier is in use by another system in the network. • ST—The router has switched to a standby connection. • PB—Profile busy. • SN—The VPLS neighbor is static.
Time last up	Time connection was last in the Up condition.
# Up trans	Number of transitions from Down to Up condition.
Status	<p>Status of the (local or remote circuit) local interface:</p> <ul style="list-style-type: none"> • Up—Operational • Dn—Down • NP—Not present • DS—Disabled • WE—Wrong encapsulation • UN—Uninitialized
Encapsulation	Type of encapsulation: VPLS.
Remote PE	Address of the remote provider edge router.

Table 46: show vpls connections Output Fields (Continued)

Field Name	Field Description
Negotiated control-word	Whether a control word has been negotiated: Yes or No.
Incoming label	Name of the incoming label.
Outgoing label	Name of the outgoing label.
Negotiated PW status TLV	Indicates whether or not the pseudowire status TLV has been negotiated for the VPLS connection.
Local interface	<p>Provides the following information about the local interface configured for the VPLS neighbor:</p> <ul style="list-style-type: none"> • Name of the local interface • Status—Interface status (Up or Down) • Encapsulation—Interface encapsulation (for example, ETHERNET) • Description—Includes the VPLS instance name, the VPLS neighbor address, and the VPLS identifier
Time	Date and time of VPLS connection event.
Event	Type of event.
Interface/Lbl/PE	Interface, label, or PE router.
Connection History	Each entry can include the date, time, year, and the connection event. Connection events include any of a variety of events related to VPLS connections, such as route changes, label updates, and interfaces going down or coming up.

Sample Output

show vpls connections

```
user@host> show vpls connections
```

```
Layer-2 VPN connections:
```

```
Legend for connection status (St)
```

```

EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -< -- only outbound connection is up
CN -- circuit not provisioned   >- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unn connection status    IL -- no incoming label
MM -- MTU mismatch             MI -- Mesh-Group ID not available
BK -- Backup connection        ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy

```

```
Legend for interface status
```

```
Up -- operational
```

```
Dn -- down
```

```
Instance: vpls-1
```

```
Local site: 1 (11)
```

```
Number of local interfaces: 1
```

```
Number of local interfaces up: 1
```

```
IRB interface present: no
```

```
lt-1/3/0.10496
```

```

vt-1/3/0.1048588  1      Intf - vpls vpls-1 local site 11 remote site 1
vt-1/2/0.1048591  2      Intf - vpls vpls-1 local site 11 remote site 2
vt-1/2/0.1048585  3      Intf - vpls vpls-1 local site 11 remote site 3
vt-1/2/0.1048587  4      Intf - vpls vpls-1 local site 11 remote site 4
vt-1/2/0.1048589  5      Intf - vpls vpls-1 local site 11 remote site 5
vt-1/3/0.1048586  6      Intf - vpls vpls-1 local site 11 remote site 6
vt-1/3/0.1048590  7      Intf - vpls vpls-1 local site 11 remote site 7
vt-1/3/0.1048584  8      Intf - vpls vpls-1 local site 11 remote site 8

```

```

Label-base      Offset      Size  Range      Preference
800256          1          16    16          100

Timer Values:
  Startup wait time: 120 seconds
  New site wait-time: 20 seconds
  Collision detect time: 30 seconds
  Reclaim wait time: 748 milliseconds

connection-site      Type  St      Time last up      # Up trans
1                    rmt   Up      Apr 28 13:28:24 2009      2
  Remote PE: 192.0.2.1, Negotiated control-word: No
  Incoming label: 800256, Outgoing label: 800026
  Local interface: vt-1/3/0.1048588, Status: Up, Encapsulation: VPLS
  Description: Intf - vpls vpls-1 local site 11 remote site 1

Connection History:
  Apr 28 13:28:24 2009  status update timer
  Apr 28 13:28:24 2009  PE route down
  Apr 28 13:24:27 2009  status update timer
  Apr 28 13:24:27 2009  loc intf up          vt-1/3/0.1048588
  Apr 28 13:24:27 2009  PE route changed
  Apr 28 13:24:27 2009  Out lbl Update          800026
  Apr 28 13:24:27 2009  In lbl Update           800256
  Apr 28 13:24:27 2009  loc intf down

2                    rmt   Up      Apr 28 13:28:24 2009      2
  Remote PE: 192.0.2.71, Negotiated control-word: No
  Incoming label: 800257, Outgoing label: 800034
  Local interface: vt-1/2/0.1048591, Status: Up, Encapsulation: VPLS
  Description: Intf - vpls vpls-1 local site 11 remote site 2

Connection History:
  Apr 28 13:28:24 2009  status update timer
  Apr 28 13:28:24 2009  PE route down
  Apr 28 13:24:28 2009  status update timer
  Apr 28 13:24:28 2009  loc intf up          vt-1/2/0.1048591
  Apr 28 13:24:28 2009  PE route changed
  Apr 28 13:24:28 2009  Out lbl Update          800034
  Apr 28 13:24:28 2009  In lbl Update           800257
  Apr 28 13:24:28 2009  loc intf down

```

show vpls connections (with FEC128 and FEC129 in the same routing-instance)

```

user@host> show vpls connections
Instance: fec129

```

```

L2vpn-id: 1:1
Local-id: 203.0.113.0
FEC129-VPLS State:
Mesh-group connections: __ves__

```

Remote-id	Type	St	Time last up	# Up trans
203.0.3.3	rmt	Up	Sep 19 09:59:56 2017	1

```

Remote PE: 203.0.3.3, Negotiated control-word: No
Incoming label: 262155, Outgoing label: 262164
Negotiated PW status TLV: No
Local interface: lsi.1048844, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls fec129 local-id 10.4.4.4 remote-id 203.0.3.3 neighbor 203.0.3.3
Flow Label Transmit: No, Flow Label Receive: No

```

Remote-id	Type	St	Time last up	# Up trans
203.0.2.2	rmt	Up	Sep 19 09:59:52 2017	1

```

Remote PE: 203.0.2.2, Negotiated control-word: No
Incoming label: 262154, Outgoing label: 262157
Negotiated PW status TLV: No
Local interface: lsi.1048846, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls fec129 local-id 10.4.4.4 remote-id 203.0.2.2 neighbor 203.0.2.2
Flow Label Transmit: No, Flow Label Receive: No

```

Remote-id	Type	St	Time last up	# Up trans
203.0.1.1	rmt	Up	Sep 19 09:59:48 2017	1

```

Remote PE: 203.0.1.1, Negotiated control-word: No
Incoming label: 262156, Outgoing label: 262157
Negotiated PW status TLV: No
Local interface: lsi.1048845, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls fec129 local-id 10.4.4.4 remote-id 203.0.1.1 neighbor 203.0.1.1
Flow Label Transmit: No, Flow Label Receive: No

```

LDP-VPLS State

```

Mesh-group connections: MG1

```

Neighbor	Type	St	Time last up	# Up trans
203.0.6.6(vpls-id 1)	rmt	Up	Sep 17 19:17:11 2017	1

```

Remote PE: 203.0.6.6, Negotiated control-word: No
Incoming label: 262423, Outgoing label: 262145
Negotiated PW status TLV: No
Local interface: lsi.1049859, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls bgp-vpls neighbor 203.0.6.6 vpls-id 1
Flow Label Transmit: No, Flow Label Receive: No

```

Neighbor	Type	St	Time last up	# Up trans
203.0.7.7(vpls-id 1)	rmt	Up	Sep 17 19:17:04 2017	1

```

Remote PE: 203.0.7.7, Negotiated control-word: No
Incoming label: 262424, Outgoing label: 262145
Negotiated PW status TLV: No
Local interface: lsi.1049857, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls bgp-vpls neighbor 203.0.7.7 vpls-id 1

```



```

Flow Label Transmit: No, Flow Label Receive: No
Mesh-group connections: MG2
Neighbor                Type  St    Time last up        # Up trans
203.0.5.5(vpls-id 1)    rmt  Up    Sep 17 19:17:00 2017      1
Remote PE: 203.0.5.5, Negotiated control-word: No
Incoming label: 262425, Outgoing label: 299872
Negotiated PW status TLV: No
Local interface: lsi.1049856, Status: Up, Encapsulation: ETHERNET
Description: Intf - vpls bgp-vpls neighbor 203.0.5.5 vpls-id 1
Flow Label Transmit: No, Flow Label Receive: No

```

show vpls connections (with multiple pseudowires)

```
user@host> show vpls connections
```

Layer-2 VPN connections:

Legend for connection status (St)

```

EI -- encapsulation invalid      NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch     WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down   NP -- interface hardware not present
CM -- control-word mismatch     -> -- only outbound connection is up
CN -- circuit not provisioned   <- -- only inbound connection is up
OR -- out of range              Up -- operational
OL -- no outgoing label         Dn -- down
LD -- local site signaled down  CF -- call admission control failure
RD -- remote site signaled down SC -- local and remote site ID collision
LN -- local site not designated LM -- local site ID not minimum designated
RN -- remote site not designated RM -- remote site ID not minimum designated
XX -- unknown connection status IL -- no incoming label
MM -- MTU mismatch              MI -- Mesh-Group ID not available
BK -- Backup connection         ST -- Standby connection
PF -- Profile parse failure     PB -- Profile busy
RS -- remote site standby       SN -- Static Neighbor
LB -- Local site not best-site  RB -- Remote site not best-site
VM -- VLAN ID mismatch

```

Legend for interface status

```

Up -- operational
Dn -- down

```

Instance: vpls

```

VPLS-id: 100
Mesh-group connections: __ves__
  Neighbor           Type St   Time last up      # Up trans
10.255.114.3 (vpls-id 100) rmt  Up    Apr 11 23:38:38 2013      1
  Remote PE: 10.255.114.3, Negotiated control-word: No
  Incoming label: 262145, Outgoing label: 262145
  Negotiated PW status TLV: No
  Local interface: lsi.1049090, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls h-vpls neighbor 10.255.114.3 vpls-id 100

Mesh-group connections: spokes
  Neighbor           Type St   Time last up      # Up trans
10.255.114.4 (vpls-id 200) rmt  Up    Apr 11 23:39:25 2013      1
  Remote PE: 10.255.114.4, Negotiated control-word: No
  Incoming label: 262148, Outgoing label: 304224
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
  Local interface: lsi.1049091, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls h-vpls neighbor 10.255.114.4 vpls-id 200
10.255.114.4 (vpls-id 201) rmt  Up    Apr 11 23:39:25 2013      1
  Remote PE: 10.255.114.4, Negotiated control-word: No
  Incoming label: 262149, Outgoing label: 304225
  Negotiated PW status TLV: Yes
  local PW status code: 0x00000000, Neighbor PW status code: 0x00000000
  Local interface: lsi.1049096, Status: Up, Encapsulation: ETHERNET
  Description: Intf - vpls h-vpls neighbor 10.255.114.4 vpls-id 201

```

show vpls connections extensive (Static VPLS Neighbors)

```
user@host> show vpls connections extensive instance red
```

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid	NC -- interface encapsulation not CCC/TCC/VPLS
EM -- encapsulation mismatch	WE -- interface and instance encaps not same
VC-Dn -- Virtual circuit down	NP -- interface hardware not present
CM -- control-word mismatch	-> -- only outbound connection is up
CN -- circuit not provisioned	<- -- only inbound connection is up
OR -- out of range	Up -- operational
OL -- no outgoing label	Dn -- down
LD -- local site signaled down	CF -- call admission control failure

RD -- remote site signaled down SC -- local and remote site ID collision
 LN -- local site not designated LM -- local site ID not minimum designated
 RN -- remote site not designated RM -- remote site ID not minimum designated
 XX -- unn connection status IL -- no incoming label
 MM -- MTU mismatch MI -- Mesh-Group ID not available
 BK -- Backup connection ST -- Standby connection
 PF -- Profile parse failure PB -- Profile busy
 RS -- remote site standby SN -- Static Neighbor

Legend for interface status

Up -- operational
 Dn -- down

Instance: static

VPLS-id: 1

Number of local interfaces: 1

Number of local interfaces up: 1

ge-0/0/5.0

lsi.1049344 Intf - vpls static neighbor 10.255.114.3 vpls-id 1

Neighbor	Type	St	Time last up	# Up trans
----------	------	----	--------------	------------

10.255.114.3(vpls-id 1)(SN)	rmt	Up	Mar 4 08:48:41 2010	1
-----------------------------	-----	----	---------------------	---

Remote PE: 10.255.114.3, Negotiated control-word: No

Incoming label: 29696, Outgoing label: 29697

Negotiated PW status TLV: No

Local interface: lsi.1049344, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls static neighbor 10.255.114.3 vpls-id 1

Connection History:

Mar 4 08:48:41 2010 status update timer

Mar 4 08:48:41 2010 PE route changed

Mar 4 08:48:41 2010 Out lbl Update 29697

Mar 4 08:48:41 2010 In lbl Update 29696

Mar 4 08:48:41 2010 loc intf up lsi.1049344

command-name

user@PE1> **show vpls connections extensive** (Multihoming with FEC 129)

Layer-2 VPN connections:

Legend for connection status (St)

EI -- encapsulation invalid NC -- interface encapsulation not CCC/TCC/VPLS
 EM -- encapsulation mismatch WE -- interface and instance encaps not same

VC-Dn -- Virtual circuit down NP -- interface hardware not present
 CM -- control-word mismatch -> -- only outbound connection is up
 CN -- circuit not provisioned <- -- only inbound connection is up
 OR -- out of range Up -- operational
 OL -- no outgoing label Dn -- down
 LD -- local site signaled down CF -- call admission control failure
 RD -- remote site signaled down SC -- local and remote site ID collision
 LN -- local site not designated LM -- local site ID not minimum designated
 RN -- remote site not designated RM -- remote site ID not minimum designated
 XX -- unknown connection status IL -- no incoming label
 MM -- MTU mismatch MI -- Mesh-Group ID not available
 BK -- Backup connection ST -- Standby connection
 PF -- Profile parse failure PB -- Profile busy
 RS -- remote site standby SN -- Static Neighbor
 LB -- Local site not best-site RB -- Remote site not best-site
 VM -- VLAN ID mismatch

Legend for interface status

Up -- operational

Dn -- down

Instance: green

L2vpn-id: 100:100

Local-id: 192.0.2.2

Number of local interfaces: 2

Number of local interfaces up: 2

ge-0/3/1.0

ge-0/3/3.0

lsi.101711873

Intf - vpls green local-id 192.0.2.2 remote-id 192.0.2.4

neighbor 192.0.2.4

Remote-id	Type	St	Time last up	# Up trans
192.0.2.4	rmt	Up	Jan 31 13:49:52 2012	1

Remote PE: 192.0.2.4, Negotiated control-word: No

Incoming label: 262146, Outgoing label: 262146

Local interface: lsi.101711873, Status: Up, Encapsulation: ETHERNET

Description: Intf - vpls green local-id 192.0.2.2 remote-id 192.0.2.4 neighbor 192.0.2.4

Connection History:

Jan 31 13:49:52 2012 status update timer

Jan 31 13:49:52 2012 PE route changed

Jan 31 13:49:52 2012 Out lbl Update 262146

Jan 31 13:49:52 2012 In lbl Update 262146

Jan 31 13:49:52 2012 loc intf up lsi.101711873

Multi-home:

```

Local-site      Id    Pref  State
test            1     100   Up
Number of interfaces: 1
Number of interfaces up: 1
ge-0/3/1.0
Received multi-homing advertisements:
Remote-PE      Pref  flag  Description
192.0.2.4      100   0x0

```

Release Information

Command introduced before Junos OS Release 7.4.

instance-history option introduced in Junos OS Release 12.3R2.

show vpls flood event-queue

IN THIS SECTION

- [Syntax | 1890](#)
- [Description | 1891](#)
- [Options | 1891](#)
- [Required Privilege Level | 1891](#)
- [Output Fields | 1891](#)
- [Sample Output | 1892](#)
- [Release Information | 1892](#)

Syntax

```
show vpls flood event-queue
```

Description

Display the pending events in the VPLS flood queue.

Options

This command has no options.

Required Privilege Level

view

Output Fields

Table 47 on page 1891 lists the output fields for the show vpls flood event-queue command. Output fields are listed in the approximate order in which they appear.

Table 47: show vpls flood event-queue Output Fields

Field Name	Field Description
Current Pending Event	Provides information on the current event in the VPLS flood event queue.
Name	Name of the event.
Owner Name	Name of the interface associated with the flood event.
Pending Op	Pending operation for the event.
Last Error	Name of the last error encountered.
Number of Retries	Number of attempts made to update the event queue.
Pending Event List	List of the events awaiting processing.
Event Name	Name of the event.

Table 47: show vpls flood event-queue Output Fields *(Continued)*

Field Name	Field Description
Pending Op	Pending operation for the event.
Event Identifier	Name of the interface associated with the flood event.

Sample Output

show vpls flood event-queue

```

user@host> show vpls flood event-queue
Current Pending Event
  Name:          Flood Nexthop
  Owner Name:ge-4/3/0.0
  Pending Op: ADD
  Last Error:ENOMEM
  Number of Retries:3
  Pending Event List:
  Event Name      Pending Op      Event Identifier
  Flood Nexthop   ADD                ge-4/3/0.0
  Flood Route     ADD                ge-4/3/0.0

```

Release Information

Command introduced in Junos OS Release 8.0.

show vpls flood instance

IN THIS SECTION

- [Syntax | 1893](#)
- [Description | 1893](#)

- [Options | 1893](#)
- [Required Privilege Level | 1893](#)
- [Output Fields | 1894](#)
- [Sample Output | 1894](#)
- [Release Information | 1895](#)

Syntax

```
show vpls flood instance
<brief | detail | extensive>
  <instance-name>
<logical-system logical-system-name>
```

Description

Display VPLS information related to the flood process.

Options

none	Display VPLS information related to the flood process for all routing instances.
brief detail extensive	(Optional) Display the specified level of output.
<i>instance-name</i>	(Optional) Display VPLS information related to the flood process for the specified routing instance.
logical-system <i>logical-system-name</i>	(Optional) Display VPLS information related to the flood process for the specified logical system.

Required Privilege Level

view

Output Fields

Table 48 on page 1894 lists the output fields for the `show vpls flood instance` command. Output fields are listed in the approximate order in which they appear.

Table 48: show vpls flood instance Output Fields

Field Name	Field Description
Logical system	Name of the logical system.
Name	Name of the VPLS routing instance.
CEs	Number of CE routers connected to the VPLS instance.
VEs	Number of VE routers connected to the VPLS instance.
Flood routes	List of all flood routes associated with the VPLS instance.
Prefix	Prefix for the route.
Type	Type of route.
Owner	VPLS routing instance or interface associated with the route.
Nhype	Next-hop type. For example, flood for a flood route.
Nhindex	Next-hop index number for the route.

Sample Output

show vpls flood instance

```

user@host> show vpls flood instance

Logical system: __example_ls1__

```

```
Name: green
CEs: 1
VEs: 1
Flood Routes:
  Prefix    Type          Owner          NhType    NhIndex
  default   ALL_CE_FLOOD green          flood     383
  0x47/16   CE_FLOOD      fe-1/2/1.0    flood     388
```

show vpls flood instance logical-system-name

```
user@host:__example_ls1__> show vpls flood instance example_ls1
```

```
Logical system: __example_ls1__
Name: green
CEs: 1
VEs: 1
Flood Routes:
  Prefix    Type          Owner          NhType    NhIndex
  default   ALL_CE_FLOOD green          flood     383
  0x47/16   CE_FLOOD      fe-1/2/1.0    flood     388
```

show vpls flood instance detail

```
user@host:__example_ls1__> show vpls flood instance detail
```

```
Logical system: __example_ls1__
Name: green
CEs: 1
VEs: 1
Flood Routes:
  Prefix    Type          Owner          NhType    NhIndex
  default   ALL_CE_FLOOD green          flood     383
  0x47/16   CE_FLOOD      fe-1/2/1.0    flood     388
```

Release Information

Command introduced in Junos OS Release 8.0.

show vpls flood route

IN THIS SECTION

- [Syntax | 1896](#)
- [Description | 1896](#)
- [Options | 1896](#)
- [Required Privilege Level | 1897](#)
- [Output Fields | 1897](#)
- [Sample Output | 1898](#)
- [Release Information | 1899](#)

Syntax

```
show vpls flood route
(all-ce-flood instance-name instance-name <logical-system-name logical-system-name> |
ce-flood interface interface-name)
```

Description

Display VPLS route information related to the flood process for either the specified routing instance or the specified interface.

Options

all-ce-flood	Display the flood next-hop route for all customer edge routers for traffic coming from the core of the network.
ce-flood interface <i>interface-name</i>	Display the flood next-hop route for traffic coming from the specified customer edge interface.
instance-name <i>instance-name</i>	Display the flood routes for the specified instance.

logical-system-name (Optional) Specify the logical system whose flood routes you want to display.
logical-system-name You can only specify the default logical system name for VPLS. The default logical system name is **__example_ls1__** \ (the name must be entered in the command with the underscore characters).

Required Privilege Level

view

Output Fields

[Table 49 on page 1897](#) lists the output for the `show vpls flood route` command. Output fields are listed in the approximate order in which they appear.

Table 49: show vpls flood route Output Fields

Field Name	Field Description
Flood route prefix	Prefix for the flood route.
Flood route type	Type of flood route (either CE_FLOOD or ALL_CE_FLOOD).
Flood route owner	VPLS routing instance or interface associated with the flood route.
Nexthop type	Next-hop type. For example, flood for a flood route.
Nexthop index	Next-hop index number for the route.
Interfaces flooding to	Interfaces to which VPLS routes are being flooded.
Name	Name of the interface.
Type	Type of VPLS router (CE or VE).
Nh type	Next-hop type.

Table 49: show vpls flood route Output Fields (Continued)

Field Name	Field Description
Index	Index number for the flood route.

Sample Output

show vpls flood route all-ce-flood

```
user@host:__example_ls1__> show vpls flood route all-ce-flood logical-system-name
__example_ls1__instance-name green
```

Flood route prefix: default

Flood route type: ALL_CE_FLOOD

Flood route owner: green

Nexthop type: flood

Nexthop index: 383

Interfaces Flooding to:

Name	Type	NhType	Index
fe-1/2/1.0	CE		

show vpls flood route ce-flood

```
user@host:__example_ls1__> show vpls flood route ce-flood interface fe-1/2/1.0
```

Flood route prefix: 0x47/16

Flood route type: CE_FLOOD

Flood route owner: fe-1/2/1.0

Nexthop type: flood

Nexthop index: 388

Interfaces Flooding to:

Name	Type	NhType	Index
lsi.49152	VE	indr	262142

Release Information

Command introduced in Junos OS Release 8.0.

show vpls mac-move-action

IN THIS SECTION

- [Syntax | 1899](#)
- [Description | 1899](#)
- [Options | 1899](#)
- [Required Privilege Level | 1900](#)
- [Output Fields | 1900](#)
- [Sample Output | 1900](#)
- [Release Information | 1901](#)

Syntax

```
show vpls mac-move-action instance  
<instance instance-name>
```

Description

Display the learning interfaces (IFLs) disabled due to a MAC move in a VPLS instance.

Options

none Display all the IFLs disabled due to MAC moves.

instance *instance-name* (Optional) Display the IFLs disabled due to a MAC move in a VPLS instance.

Required Privilege Level

view

Output Fields

Table 50 on page 1900 describes the output fields for the **show vpls mac-move-action** command. Output fields are listed in the approximate order in which they appear.

Table 50: show vpls mac-move-action Output Fields

Field Name	Field Description
Instance	Instance name
Local Interface	Local interface disabled due to MAC move.
Index	Index number.
Algorithm Used	<p>The following algorithm can be in use:</p> <ul style="list-style-type: none"> • Base IFL — Primary approach • Statistical — Secondary approach
Time rec	Time recorded in hh:mm:sec.
Recovery Timer	Enable the interface after a set time.

Sample Output

show vpls mac-move-action (MX Series)

```

user@host> show vpls mac-move-action

Instance: vpls_1
Local interface: xe-1/3/1.600, Index: 341
Algorithm used : Statistical

```

```
Time rec      : 02:30:35  
Recovery timer : Yes
```

show vpls mac-move-action instance instance-name

```
user@host> show vpls mac-move-action instance vpls_1
```

```
Instance: vpls_1  
Local interface: xe-1/3/1.600, Index: 341  
Algorithm used : Base IFL  
Time rec      : 02:29:35  
Recovery timer : Yes
```

Release Information

Command introduced in Junos OS Release 14.2.

show vpls mac-table

IN THIS SECTION

- [Syntax | 1902](#)
- [Description | 1902](#)
- [Options | 1902](#)
- [Required Privilege Level | 1903](#)
- [Output Fields | 1903](#)
- [Sample Output | 1904](#)
- [Release Information | 1909](#)

Syntax

```
show vpls mac-table
<age>
<brief | detail | extensive | summary>
<bridge-domain bridge-domain-name>
<instance instance-name>
<interface interface-name>
<logical-system (all | logical-system-name)>
<mac-address>
<vlan-id vlan-id-number>
```

Description

Display learned virtual private LAN service (VPLS) media access control (MAC) address information.

Options

none	Display all learned VPLS MAC address information.
age	(Optional) Display age of a single mac-address.
brief detail extensive summary	(Optional) Display the specified level of output.
bridge-domain <i>bridge-domain-name</i>	(Optional) Display learned VPLS MAC addresses for the specified bridge domain.
instance <i>instance-name</i>	(Optional) Display learned VPLS MAC addresses for the specified instance.
interface <i>interface-name</i>	(Optional) Display learned VPLS MAC addresses for the specified instance.
logical-system (all <i>logical-system-name</i>)	(Optional) Display learned VPLS MAC addresses for all logical systems or for the specified logical system.
<i>mac-address</i>	(Optional) Display the specified learned VPLS MAC address information..
vlan-id <i>vlan-id-number</i>	(Optional) Display learned VPLS MAC addresses for the specified VLAN.

Required Privilege Level

view

Output Fields

Table 51 on page 1903 describes the output fields for the `show vpls mac-table` command. Output fields are listed in the approximate order in which they appear.

Table 51: show vpls mac-table Output fields

Field Name	Field Description
Age	Age of a single mac-address.
Routing instance	Name of the routing instance.
Bridging domain	Name of the bridging domain.
MAC address	MAC address or addresses learned on a logical interface.
MAC flags	Status of MAC address learning properties for each interface: <ul style="list-style-type: none"> • S—Static MAC address configured. • D—Dynamic MAC address learned. • SE—MAC accounting is enabled. • NM—Nonconfigured MAC.
Logical interface	Name of the logical interface.
MAC count	Number of MAC addresses learned on a specific routing instance or interface.
Learning interface	Logical interface or logical Label Switched Interface (LSI) the address is learned on.
Base learning interface	Base learning interface of the MAC address. This field is introduced in Junos OS Release 14.2.

Table 51: show vpls mac-table Output fields (Continued)

Field Name	Field Description
Learn VLAN ID/ VLAN	VLAN ID of the routing instance or bridge domain in which the MAC address was learned.
VXLAN ID/VXLAN	VXLAN Network Identifier (VNI)
Layer 2 flags	Debugging flags signifying that the MAC address is present in various lists.
Epoch	Spanning Tree Protocol epoch number identifying when the MAC address was learned. Used for debugging.
Sequence number	Sequence number assigned to this MAC address. Used for debugging.
Learning mask	Mask of Packet Forwarding Engines where this MAC address was learned. Used for debugging.
IPC generation	Creation time of the logical interface when this MAC address was learned. Used for debugging.

Sample Output

show vpls mac-table

```

user@host> show vpls mac-table
MAC flags (S -static MAC, D -dynamic MAC,
          SE -Statistics enabled, NM -Non configured MAC)

Routing instance : vpls_ldp1
VLAN : 223
  MAC          MAC      Logical
  address      flags    interface
  00:00:5e:00:53:5d  D      ge-0/2/5.400

MAC flags (S -static MAC, D -dynamic MAC,
          SE -Statistics enabled, NM -Non configured MAC)

```

```

Routing instance : vpls_red
VLAN : 401
  MAC          MAC      Logical
  address      flags    interface
00:00:5e:00:53:12 D      lsi.1051138
00:00:5e:00:53:f0 D      lsi.1051138

```

show vpls mac-table (with Layer 2 Services over GRE Interfaces)

```

user@host> show vpls mac-table
MAC flags (S -static MAC, D -dynamic MAC, L -locally learned
          SE -Statistics enabled, NM -Non configured MAC, R -Remote PE MAC)

Routing instance : vpls_4site:1000
Bridging domain : __vpls_4site:1000__, MAC          MAC      Logical
  address      flags    interface
00:00:5e:00:53:f4 D,SE    ge-4/2/0.1000
00:00:5e:00:53:33 D,SE    lsi.1052004
00:00:5e:00:53:32 D,SE    lsi.1048840
00:00:5e:00:53:14 D,SE    lsi.1052005
00:00:5e:00:53:f7 D,SE    gr-1/2/10.10

```

show vpls mac-table (with VXLAN enabled)

```

user@host> show vpls mac-table
MAC flags (S -static MAC, D -dynamic MAC, L -locally learned
          SE -Statistics enabled, NM -Non configured MAC, R -Remote PE MAC)

Routing instance : vpls_4site:1000
Bridging domain : __vpls_4site:1000__, VLAN : 4094,4093
VXLAN: Id : 300, Multicast group: 233.252.0.1
  MAC          MAC      Logical
  address      flags    interface
00:00:5e:00:53:f4 D,SE    ge-4/2/0.1000
00:00:5e:00:53:33 D,SE    lsi.1052004
00:00:5e:00:53:32 D,SE    lsi.1048840
00:00:5e:00:53:14 D,SE    lsi.1052005

```

```
00:00:5e:00:53:f7  D,SE    vtep.1052010
00:00:5e:00:53:3f  D,SE    vtep.1052011
```

show vpls mac-table age (for GE interface)

```
user@host> show vpls mac-table age 00:00:5e:00:53:1a instance vpls_instance_1
MAC Entry Age information
Current Age: 4 seconds
```

show vpls mac-table age (for AE interface)

```
user@host> show vpls mac-table age 00:00:5e:00:53:1a instance vpls_instance_1
MAC Entry Age information
Current Age on FPC1: 102 seconds
Current Age on FPC2: 94 seconds
```

show vpls mac-table count

```
user@host> show vpls mac-table count
0 MAC address learned in routing instance __example_private1__

MAC address count per interface within routing instance:
Logical interface      MAC count
lc-0/0/0.32769         0
lc-0/1/0.32769         0
lc-0/2/0.32769         0
lc-2/0/0.32769         0
lc-0/3/0.32769         0
lc-2/1/0.32769         0
lc-9/0/0.32769         0
lc-11/0/0.32769        0
lc-2/2/0.32769         0
lc-9/1/0.32769         0
lc-11/1/0.32769        0
lc-2/3/0.32769         0
lc-9/2/0.32769         0
lc-11/2/0.32769        0
lc-11/3/0.32769        0
```

```
lc-9/3/0.32769          0
```

MAC address count per learn VLAN within routing instance:

Learn VLAN ID	MAC count
0	0

1 MAC address learned in routing instance vpls_ldp1

MAC address count per interface within routing instance:

Logical interface	MAC count
lsi.1051137	0
ge-0/2/5.400	1

MAC address count per learn VLAN within routing instance:

Learn VLAN ID	MAC count
0	1

1 MAC address learned in routing instance vpls_red

MAC address count per interface within routing instance:

Logical interface	MAC count
ge-0/2/5.300	1

MAC address count per learn VLAN within routing instance:

Learn VLAN ID	MAC count
0	1

show vpls mac-table detail

```
user@host> show vpls mac-table detail
```

MAC address: 00:00:5e:00:53:5d

Routing instance: vpls_ldp1

Learning interface: ge-0/2/5.400

Layer 2 flags: in_ifd, in_ifl, in_vlan, kernel

Epoch: 0 Sequence number: 1

Learning mask: 0x1 IPC generation: 0

MAC address: 00:00:5e:00:53:5d

Routing instance: vpls_red

Learning interface: ge-0/2/5.300

Layer 2 flags: in_ifd, in_ifl, in_vlan, kernel

Epoch: 0	Sequence number: 1
Learning mask: 0x1	IPC generation: 0

show vpls mac-table extensive

```
user@host> show vpls mac-table extensive
```

MAC address: 00:00:5e:00:53:00

Routing instance: vpls_1

Bridging domain: __vpls_1__, VLAN : NA

Learning interface: lsi.1049165

Base learning interface: lsi.1049165

Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd

Epoch: 0 Sequence number: 1

Learning mask: 0x00000001

MAC address: 00:00:5e:00:53:01

Routing instance: vpls_1

Bridging domain: __vpls_1__, VLAN : NA

Learning interface: lsi.1049165

Base learning interface: lsi.1049165

Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd

Epoch: 0 Sequence number: 1

Learning mask: 0x00000001

MAC address: 00:00:5e:00:53:02

Routing instance: vpls_1

Bridging domain: __vpls_1__, VLAN : NA

Learning interface: lsi.1049165

Base learning interface: lsi.1049165

Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd

Epoch: 0 Sequence number: 1

Learning mask: 0x00000001

MAC address: 00:00:5e:00:53:03

Routing instance: vpls_1

Bridging domain: __vpls_1__, VLAN : NA

Learning interface: lsi.1049165

Base learning interface: lsi.1049165

Layer 2 flags: in_hash,in_ifd,in_ifl,in_vlan,in_rtt,kernel,in_ifbd

Epoch: 0 Sequence number: 1
Learning mask: 0x00000001

Release Information

Command introduced in Junos OS Release 8.5.

show vpls statistics

IN THIS SECTION

- [Syntax | 1909](#)
- [Description | 1909](#)
- [Options | 1910](#)
- [Required Privilege Level | 1910](#)
- [Output Fields | 1910](#)
- [Sample Output | 1911](#)
- [Release Information | 1912](#)

Syntax

```
show vpls statistics  
<instance instance-name>  
<logical-system (all | logical-system-name)>
```

Description

(T Series and M Series routers, except for the M160 router) Display virtual private LAN service (VPLS) statistics.

Options

none	Display VPLS statistics for all routing instances.
instance <i>instance-name</i>	(Optional) Display VPLS statistics for a specific VPLS routing instance only.
logical-system (all <i>logical-system-name</i>)	(Optional) Perform this operation on all logical systems or on a particular logical system.

Required Privilege Level

view

Output Fields

[Table 52 on page 1910](#) lists the output fields for the `show vpls statistics` command. Output fields are listed in the approximate order in which they appear.

Table 52: show vpls statistics Output Fields

Field Name	Field Description
Instance	Name of the VPLS instance.
Local interface	Name of the local VPLS virtual loopback tunnel interface, vt-fpc/pic/port.nnnnn , where nnnnn is a dynamically generated virtual port used to transport and receive packets from other provider edge (PE) routers in the VPLS domain.
Index	Number associated with the next hop.
Remote provider edge router	Address of the remote provider edge router.
Multicast packets	Number of multicast packets received.
Multicast bytes	Number of multicast bytes received.

Table 52: show vpls statistics Output Fields (Continued)

Field Name	Field Description
Flood packets	Number of VPLS flood packets received.
Flood bytes	Number of VPLS flood bytes received.
Current MAC count	Number of MAC addresses learned by the interface and the configured maximum limit on the number of MAC addresses that can be learned.

Sample Output

show vpls statistics

```
user@host> show vpls statistics
```

```
VPLS statistics:
```

```
Instance: green
```

```
Local interface: fe-2/2/1.0, Index: 69
```

```

Multicast packets:          1
Multicast bytes   :          60
Flooded packets   :          18
Flooded bytes    :        2556
Current MAC count:          1

```

```
Local interface: lt-0/3/0.2, Index: 72
```

```

Multicast packets:          3
Multicast bytes   :        153
Flooded packets   :          1
Flooded bytes    :          51
Current MAC count:          1

```

```
Local interface: lsi.32769, Index: 75
```

```
Current MAC count:          0
```

```
Local interface: lsi.32771, Index: 77
```

```

Remote PE: 10.255.14.222
Current MAC count:          2

```

Instance: red

```

Local interface: vt-0/3/0.32768, Index: 74
Multicast packets:          0
Multicast bytes   :          0
Flooded packets   :          0
Flooded bytes    :          0
Current MAC count:          0

```

```

Local interface: vt-0/3/0.32770, Index: 76
Multicast packets:          0
Multicast bytes   :          0
Flooded packets   :          0
Flooded bytes    :          0
Current MAC count:          0

```

show vpls statistics instance

```
user@host> show vpls statistics instance red
```

Layer-2 VPN Statistics:

Instance: red

```

Local interface: vt-3/2/0.32768, Index: 73
Remote provider edge router: 10.255.17.35
Multicast packets:          0
Multicast bytes   :          0
Flood packets    :          0
Flood bytes      :          0
Current MAC count:          1 (Limit 20)

```

Release Information

Command introduced before Junos OS Release 7.4.