



**JUNOS® Software**

# **CLI Reference for J-series Services Routers and SRX-series Services Gateways**

*Release 9.3*

**Juniper Networks, Inc.**  
1194 North Mathilda Avenue  
Sunnyvale, California 94089  
USA  
408-745-2000  
**[www.juniper.net](http://www.juniper.net)**

Part Number: 530-025832-01, Revision 1

This product includes the Envoy SNMP Engine, developed by Epilogue Technology, an Integrated Systems Company. Copyright © 1986-1997, Epilogue Technology Corporation. All rights reserved. This program and its documentation were developed at private expense, and no part of them is in the public domain.

This product includes memory allocation software developed by Mark Moraes, copyright © 1988, 1989, 1993, University of Toronto.

This product includes FreeBSD software developed by the University of California, Berkeley, and its contributors. All of the documentation and software included in the 4.4BSD and 4.4BSD-Lite Releases is copyrighted by the Regents of the University of California. Copyright © 1979, 1980, 1983, 1986, 1988, 1989, 1991, 1992, 1993, 1994. The Regents of the University of California. All rights reserved.

GateD software copyright © 1995, the Regents of the University. All rights reserved. Gate Daemon was originated and developed through release 3.0 by Cornell University and its collaborators. Gated is based on Kirton's EGP, UC Berkeley's routing daemon (routed), and DCN's HELLO routing protocol. Development of Gated has been supported in part by the National Science Foundation. Portions of the GateD software copyright © 1988, Regents of the University of California. All rights reserved. Portions of the GateD software copyright © 1991, D. L. S. Associates.

This product includes software developed by Maker Communications, Inc., copyright © 1996, 1997, Maker Communications, Inc.

Juniper Networks, the Juniper Networks logo, JUNOS, NetScreen, ScreenOS, and Steel-Belted Radius are registered trademarks of Juniper Networks, Inc. in the United States and other countries. JUNOSe is a trademark of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Products made or sold by Juniper Networks or components thereof might be covered by one or more of the following patents that are owned by or licensed to Juniper Networks: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

#### *JUNOS® Software CLI Reference*

Release 9.3

Copyright © 2008, Juniper Networks, Inc.

All rights reserved. Printed in USA.

#### Revision History

October 2008—Revision 1

The information in this document is current as of the date listed in the revision history.

#### YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. The JUNOS software has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

#### SOFTWARE LICENSE

The terms and conditions for using this software are described in the software license contained in the acknowledgment to your purchase order or, to the extent applicable, to any reseller agreement or end-user purchase agreement executed between you and Juniper Networks. By using this software, you indicate that you understand and agree to be bound by those terms and conditions. Generally speaking, the software license restricts the manner in which you are permitted to use the software and may contain prohibitions against certain uses. The software license may state conditions under which the license is automatically terminated. You should consult the license for further details. For complete product documentation, please see the Juniper Networks Web site at [www.juniper.net/techpubs](http://www.juniper.net/techpubs).

## END USER LICENSE AGREEMENT

**READ THIS END USER LICENSE AGREEMENT ("AGREEMENT") BEFORE DOWNLOADING, INSTALLING, OR USING THE SOFTWARE.** BY DOWNLOADING, INSTALLING, OR USING THE SOFTWARE OR OTHERWISE EXPRESSING YOUR AGREEMENT TO THE TERMS CONTAINED HEREIN, YOU (AS CUSTOMER OR IF YOU ARE NOT THE CUSTOMER, AS A REPRESENTATIVE/AGENT AUTHORIZED TO BIND THE CUSTOMER) CONSENT TO BE BOUND BY THIS AGREEMENT. IF YOU DO NOT OR CANNOT AGREE TO THE TERMS CONTAINED HEREIN, THEN (A) DO NOT DOWNLOAD, INSTALL, OR USE THE SOFTWARE, AND (B) YOU MAY CONTACT JUNIPER NETWORKS REGARDING LICENSE TERMS.

1. **The Parties.** The parties to this Agreement are (i) Juniper Networks, Inc. (if the Customer's principal office is located in the Americas) or Juniper Networks (Cayman) Limited (if the Customer's principal office is located outside the Americas) (such applicable entity being referred to herein as "Juniper"), and (ii) the person or organization that originally purchased from Juniper or an authorized Juniper reseller the applicable license(s) for use of the Software ("Customer") (collectively, the "Parties").

2. **The Software.** In this Agreement, "Software" means the program modules and features of the Juniper or Juniper-supplied software, for which Customer has paid the applicable license or support fees to Juniper or an authorized Juniper reseller, or which was embedded by Juniper in equipment which Customer purchased from Juniper or an authorized Juniper reseller. "Software" also includes updates, upgrades and new releases of such software. "Embedded Software" means Software which Juniper has embedded in or loaded onto the Juniper equipment and any updates, upgrades, additions or replacements which are subsequently embedded in or loaded onto the equipment.

3. **License Grant.** Subject to payment of the applicable fees and the limitations and restrictions set forth herein, Juniper grants to Customer a non-exclusive and non-transferable license, without right to sublicense, to use the Software, in executable form only, subject to the following use restrictions:

a. Customer shall use Embedded Software solely as embedded in, and for execution on, Juniper equipment originally purchased by Customer from Juniper or an authorized Juniper reseller.

b. Customer shall use the Software on a single hardware chassis having a single processing unit, or as many chassis or processing units for which Customer has paid the applicable license fees; provided, however, with respect to the Steel-Belted Radius or Odyssey Access Client software only, Customer shall use such Software on a single computer containing a single physical random access memory space and containing any number of processors. Use of the Steel-Belted Radius or IMS AAA software on multiple computers or virtual machines (e.g., Solaris zones) requires multiple licenses, regardless of whether such computers or virtualizations are physically contained on a single chassis.

c. Product purchase documents, paper or electronic user documentation, and/or the particular licenses purchased by Customer may specify limits to Customer's use of the Software. Such limits may restrict use to a maximum number of seats, registered endpoints, concurrent users, sessions, calls, connections, subscribers, clusters, nodes, realms, devices, links, ports or transactions, or require the purchase of separate licenses to use particular features, functionalities, services, applications, operations, or capabilities, or provide throughput, performance, configuration, bandwidth, interface, processing, temporal, or geographical limits. In addition, such limits may restrict the use of the Software to managing certain kinds of networks or require the Software to be used only in conjunction with other specific Software. Customer's use of the Software shall be subject to all such limitations and purchase of all applicable licenses.

d. For any trial copy of the Software, Customer's right to use the Software expires 30 days after download, installation or use of the Software. Customer may operate the Software after the 30-day trial period only if Customer pays for a license to do so. Customer may not extend or create an additional trial period by re-installing the Software after the 30-day trial period.

e. The Global Enterprise Edition of the Steel-Belted Radius software may be used by Customer only to manage access to Customer's enterprise network. Specifically, service provider customers are expressly prohibited from using the Global Enterprise Edition of the Steel-Belted Radius software to support any commercial network access services.

The foregoing license is not transferable or assignable by Customer. No license is granted herein to any user who did not originally purchase the applicable license(s) for the Software from Juniper or an authorized Juniper reseller.

4. **Use Prohibitions.** Notwithstanding the foregoing, the license provided herein does not permit the Customer to, and Customer agrees not to and shall not: (a) modify, unbundle, reverse engineer, or create derivative works based on the Software; (b) make unauthorized copies of the Software (except as necessary for backup purposes); (c) rent, sell, transfer, or grant any rights in and to any copy of the Software, in any form, to any third party; (d) remove any proprietary notices, labels, or marks on or in any copy of the Software or any product in which the Software is embedded; (e) distribute any copy of the Software to any third party, including as may be embedded in Juniper equipment sold in the secondhand market; (f) use any 'locked' or key-restricted feature, function, service, application, operation, or capability without first purchasing the applicable license(s) and obtaining a valid key from Juniper, even if such feature, function, service, application, operation, or capability is enabled without a key; (g) distribute any key for the Software provided by Juniper to any third party; (h) use the Software in any manner that extends or is broader than the uses purchased by Customer from Juniper or an authorized Juniper reseller; (i) use Embedded Software on non-Juniper equipment; (j) use Embedded Software (or make it available for use) on Juniper equipment that the Customer did not originally purchase from Juniper or an authorized Juniper reseller; (k) disclose the results of testing or benchmarking of the Software to any third party without the prior written consent of Juniper; or (l) use the Software in any manner other than as expressly provided herein.

5. **Audit.** Customer shall maintain accurate records as necessary to verify compliance with this Agreement. Upon request by Juniper, Customer shall furnish such records to Juniper and certify its compliance with this Agreement.

6. **Confidentiality.** The Parties agree that aspects of the Software and associated documentation are the confidential property of Juniper. As such, Customer shall exercise all reasonable commercial efforts to maintain the Software and associated documentation in confidence, which at a minimum includes restricting access to the Software to Customer employees and contractors having a need to use the Software for Customer's internal business purposes.

7. **Ownership.** Juniper and Juniper's licensors, respectively, retain ownership of all right, title, and interest (including copyright) in and to the Software, associated documentation, and all copies of the Software. Nothing in this Agreement constitutes a transfer or conveyance of any right, title, or interest in the Software or associated documentation, or a sale of the Software, associated documentation, or copies of the Software.

8. **Warranty, Limitation of Liability, Disclaimer of Warranty.** The warranty applicable to the Software shall be as set forth in the warranty statement that accompanies the Software (the "Warranty Statement"). Nothing in this Agreement shall give rise to any obligation to support the Software. Support services may be purchased separately. Any such support shall be governed by a separate, written support services agreement. TO THE MAXIMUM EXTENT PERMITTED BY LAW, JUNIPER SHALL NOT BE LIABLE FOR ANY LOST PROFITS, LOSS OF DATA, OR COSTS OR PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, OR FOR ANY SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THIS AGREEMENT, THE SOFTWARE, OR ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. IN NO EVENT SHALL JUNIPER BE LIABLE FOR DAMAGES ARISING FROM UNAUTHORIZED OR IMPROPER USE OF ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE, EXCEPT AS EXPRESSLY PROVIDED IN THE WARRANTY STATEMENT TO THE EXTENT PERMITTED BY LAW, JUNIPER DISCLAIMS ANY AND ALL WARRANTIES IN AND TO THE SOFTWARE (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT DOES JUNIPER WARRANT THAT THE SOFTWARE, OR ANY EQUIPMENT OR NETWORK RUNNING THE SOFTWARE, WILL OPERATE WITHOUT ERROR OR INTERRUPTION, OR WILL BE FREE OF VULNERABILITY TO INTRUSION OR ATTACK. In no event shall Juniper's or its suppliers' or licensors' liability to Customer, whether in contract, tort (including negligence), breach of warranty, or otherwise, exceed the price paid by Customer for the Software that gave rise to the claim, or if the Software is embedded in another Juniper product, the price paid by Customer for such other product. Customer acknowledges and agrees that Juniper has set its prices and entered into this Agreement in reliance upon the disclaimers of warranty and the limitations of liability set forth herein, that the same reflect an allocation of risk between the Parties (including the risk that a contract remedy may fail of its essential purpose and cause consequential loss), and that the same form an essential basis of the bargain between the Parties.

9. **Termination.** Any breach of this Agreement or failure by Customer to pay any applicable fees due shall result in automatic termination of the license granted herein. Upon such termination, Customer shall destroy or return to Juniper all copies of the Software and related documentation in Customer's possession or control.

10. **Taxes.** All license fees payable under this agreement are exclusive of tax. Customer shall be responsible for paying Taxes arising from the purchase of the license, or importation or use of the Software. If applicable, valid exemption documentation for each taxing jurisdiction shall be provided to Juniper prior to invoicing, and Customer shall promptly notify Juniper if their exemption is revoked or modified. All payments made by Customer shall be net of any applicable withholding tax. Customer will provide reasonable assistance to Juniper in connection with such withholding taxes by promptly: providing Juniper with valid tax receipts and other required documentation showing Customer's payment of any withholding taxes; completing appropriate applications that would reduce the amount of withholding tax to be paid; and notifying and assisting Juniper in any audit or tax proceeding related to transactions hereunder. Customer shall comply with all applicable tax laws and regulations, and Customer will promptly pay or reimburse Juniper for all costs and damages related to any liability incurred by Juniper as a result of Customer's non-compliance or delay with its responsibilities herein. Customer's obligations under this Section shall survive termination or expiration of this Agreement.

11. **Export.** Customer agrees to comply with all applicable export laws and restrictions and regulations of any United States and any applicable foreign agency or authority, and not to export or re-export the Software or any direct product thereof in violation of any such restrictions, laws or regulations, or without all necessary approvals. Customer shall be liable for any such violations. The version of the Software supplied to Customer may contain encryption or other capabilities restricting Customer's ability to export the Software without an export license.

12. **Commercial Computer Software.** The Software is "commercial computer software" and is provided with restricted rights. Use, duplication, or disclosure by the United States government is subject to restrictions set forth in this Agreement and as provided in DFARS 227.7201 through 227.7202-4, FAR 12.212, FAR 27.405(b)(2), FAR 52.227-19, or FAR 52.227-14(ALT III) as applicable.

13. **Interface Information.** To the extent required by applicable law, and at Customer's written request, Juniper shall provide Customer with the interface information needed to achieve interoperability between the Software and another independently created program, on payment of applicable fee, if any. Customer shall observe strict obligations of confidentiality with respect to such information and shall use such information in compliance with any applicable terms and conditions upon which Juniper makes such information available.

14. **Third Party Software.** Any licensor of Juniper whose software is embedded in the Software and any supplier of Juniper whose products or technology are embedded in (or services are accessed by) the Software shall be a third party beneficiary with respect to this Agreement, and such licensor or vendor shall have the right to enforce this Agreement in its own name as if it were Juniper. In addition, certain third party software may be provided with the Software and is subject to the accompanying license(s), if any, of its respective owner(s). To the extent portions of the Software are distributed under and subject to open source licenses obligating Juniper to make the source code for such portions publicly available (such as the GNU General Public License ("GPL") or the GNU Library General Public License ("LGPL")), Juniper will make such source code portions (including Juniper modifications, as appropriate) available upon request for a period of up to three years from the date of distribution. Such request can be made in writing to Juniper Networks, Inc., 1194 N. Mathilda Ave., Sunnyvale, CA 94089, ATTN: General Counsel. You may obtain a copy of the GPL at <http://www.gnu.org/licenses/gpl.html>, and a copy of the LGPL at <http://www.gnu.org/licenses/lgpl.html>.

15. **Miscellaneous.** This Agreement shall be governed by the laws of the State of California without reference to its conflicts of laws principles. The provisions of the U.N. Convention for the International Sale of Goods shall not apply to this Agreement. For any disputes arising under this Agreement, the Parties hereby consent to the personal and exclusive jurisdiction of, and venue in, the state and federal courts within Santa Clara County, California. This Agreement constitutes the entire and sole agreement between Juniper and the Customer with respect to the Software, and supersedes all prior and contemporaneous

agreements relating to the Software, whether oral or written (including any inconsistent terms contained in a purchase order), except that the terms of a separate written agreement executed by an authorized Juniper representative and Customer shall govern to the extent such terms are inconsistent or conflict with terms contained herein. No modification to this Agreement nor any waiver of any rights hereunder shall be effective unless expressly assented to in writing by the party to be charged. If any portion of this Agreement is held invalid, the Parties agree that such invalidity shall not affect the validity of the remainder of this Agreement. This Agreement and associated documentation has been written in the English language, and the Parties agree that the English version will govern. (For Canada: Les parties aux présentes confirment leur volonté que cette convention de même que tous les documents y compris tout avis qui s'y rattache, soient rédigés en langue anglaise. (Translation: The parties confirm that this Agreement and all related documentation is and will be in the English language)).



# Table of Contents

---

## About This Guide xxvii

---

Objectives .....	xxvii
Audience .....	xxviii
Supported Routing Platforms .....	xxviii
How to Use This Manual .....	xxviii
Document Conventions .....	xxx
List of Technical Publications .....	xxxii
Documentation Feedback .....	xxxiii
Requesting Technical Support .....	xxxiv

## Part 1

---

## Configuration Statements

---

### Chapter 1

---

### Access Hierarchy and Statements 3

---

Access Configuration Statement Hierarchy .....	3
admin-search .....	6
assemble .....	7
authentication-order .....	8
banner .....	9
banner (FTP, HTTP, Telnet) .....	9
banner (Web Authentication) .....	10
base-distinguished-name .....	11
client-group .....	12
client-idle-timeout .....	12
client-name-filter .....	13
client-session-timeout .....	13
configuration-file .....	14
count .....	14
default-profile .....	15
distinguished-name .....	15
domain-name .....	16
fail .....	16
firewall-authentication .....	17
firewall-user .....	18
ftp .....	18
http .....	19
ldap-options .....	20
ldap-server .....	21
login .....	22

pass-through .....	23
password .....	24
port .....	25
port (LDAP) .....	25
port (RADIUS) .....	25
radius-options .....	26
radius-server .....	27
retry .....	28
retry (LDAP) .....	28
retry (RADIUS) .....	29
revert-interval .....	30
revert-interval (LDAP) .....	30
revert-interval (RADIUS) .....	31
routing-instance .....	32
routing-instance (LDAP) .....	32
routing-instance (RADIUS) .....	33
search .....	33
search-filter .....	34
secret .....	34
securid-server .....	35
separator .....	36
session-options .....	37
source-address .....	38
source-address (LDAP) .....	38
source-address (RADIUS) .....	38
success .....	39
telnet .....	40
timeout .....	41
timeout (LDAP Server) .....	41
timeout (RADIUS Server) .....	42
traceoptions .....	43
web-authentication .....	44

<b>Chapter 2</b>	<b>Accounting-Options Hierarchy</b>	<b>45</b>
------------------	-------------------------------------	-----------

Accounting-Options Configuration Statement Hierarchy .....	45
--	----

<b>Chapter 3</b>	<b>Applications Hierarchy and Statements</b>	<b>47</b>
------------------	--	-----------

Applications Configuration Statement Hierarchy .....	47
alg .....	49
application-protocol .....	50
destination-port .....	51
icmp-code .....	54
icmp-type .....	55
inactivity-timeout .....	55
protocol .....	56
rpc-program-number .....	57
source-port .....	57



	term .....	58
	uuid .....	59
<b>Chapter 4</b>	<b>Chassis Hierarchy and Statements</b>	<b>61</b>
	Chassis Configuration Statement Hierarchy .....	61
	cluster .....	65
	control-ports .....	66
	gratuitous-arp-count .....	67
	heartbeat-interval .....	67
	heartbeat-threshold .....	68
	interface-monitor .....	68
	node .....	69
	node (Cluster) .....	69
	node (Redundancy-Group) .....	70
	pic-mode .....	71
	preempt .....	72
	priority .....	72
	redundancy-group .....	73
	reth-count .....	74
	traceoptions .....	75
	tunnel-queuing .....	76
	weight .....	77
<b>Chapter 5</b>	<b>Class-of-Service Hierarchy</b>	<b>79</b>
	Class-of-Service Configuration Statement Hierarchy .....	79
<b>Chapter 6</b>	<b>Event-Options Hierarchy</b>	<b>83</b>
	Event-Options Configuration Statement Hierarchy .....	83
<b>Chapter 7</b>	<b>Firewall Hierarchy</b>	<b>85</b>
	Firewall Configuration Statement Hierarchy .....	85
<b>Chapter 8</b>	<b>Forwarding-Options Hierarchy and Statements</b>	<b>89</b>
	Forwarding-Options Configuration Statement Hierarchy .....	89
	vpn .....	93
<b>Chapter 9</b>	<b>Groups Hierarchy</b>	<b>95</b>
	Groups Configuration Statement Hierarchy .....	95

<b>Chapter 10</b>	<b>Interfaces Hierarchy and Statements</b>	<b>97</b>
	Interfaces Configuration Statement Hierarchy .....	97
	client-identifier .....	109
	dhcp .....	109
	fabric-options .....	110
	flow-control .....	110
	lease-time .....	111
	link-speed .....	111
	loopback .....	112
	member-interfaces .....	112
	next-hop-tunnel .....	113
	no-flow-control .....	113
	no-loopback .....	113
	no-source-filtering .....	113
	redundancy-group .....	114
	redundant-ether-options .....	114
	redundant-parent .....	115
	redundant-parent (Fast Ethernet Options) .....	115
	redundant-parent (Gigabit Ethernet Options) .....	115
	retransmission-attempt .....	116
	retransmission-interval .....	116
	server-address .....	117
	source-address-filter .....	117
	source-filtering .....	118
	update-server .....	118
	vendor-id .....	119
	web-authentication .....	119
<b>Chapter 11</b>	<b>Policy-Options Hierarchy and Statements</b>	<b>121</b>
	Policy-Options Configuration Statement Hierarchy .....	121
	condition .....	122
	route-active-on .....	123
<b>Chapter 12</b>	<b>Protocols Hierarchy</b>	<b>125</b>
	Protocols Configuration Statement Hierarchy .....	125
<b>Chapter 13</b>	<b>Routing-Instances Hierarchy</b>	<b>149</b>
	Routing-Instances Configuration Statement Hierarchy .....	149
<b>Chapter 14</b>	<b>Routing-Options Hierarchy</b>	<b>161</b>
	Routing-Options Configuration Statement Hierarchy .....	161

## **Chapter 15                      Schedulers Hierarchy and Statements                      169**

Schedulers Configuration Statement Hierarchy .....	169
all-day .....	170
daily .....	171
exclude .....	172
friday .....	173
monday .....	174
saturday .....	175
scheduler .....	176
schedulers .....	177
start-date .....	177
start-time .....	178
stop-date .....	179
stop-time .....	180
sunday .....	181
thursday .....	182
tuesday .....	183
wednesday .....	184

## **Chapter 16                      Security Hierarchy and Statements                      185**

Security Configuration Statement Hierarchy .....	185
access-profile .....	207
ack-number .....	207
action .....	208
active-policy .....	209
address .....	210
address (ARP Proxy Services Gateway) .....	210
address (Destination NAT Services Gateway) .....	211
address (Destination NAT Services Router) .....	211
address (IKE Gateway) .....	212
address (Source NAT) .....	212
address (Zone Address Book) .....	213
address (Zone Address Set) .....	213
address-book .....	214
address-persistent .....	214
address-range .....	215
address-range (Destination NAT) .....	215
address-range (Source NAT) .....	215
address-set .....	216
administrator .....	216
aging .....	217
alarm-threshold .....	218
alarm-without-drop .....	218
alert .....	219
alg .....	220
algorithm .....	224
all-tcp .....	225
allow-dns-reply .....	225

allow-icmp-without-flow .....	226
allow-incoming .....	226
always-send .....	227
anomaly .....	227
application .....	228
application (Protocol Binding Custom Attack) .....	228
application (Security Policies) .....	228
application-identification .....	229
application-screen .....	230
application-screen (H323) .....	230
application-screen (MGCP) .....	231
application-screen (SCCP) .....	231
application-screen (SIP) .....	232
application-services .....	233
application-system-cache .....	233
application-system-cache-timeout .....	234
attack-threshold .....	235
attacks .....	236
attacks (Exempt Rulebase) .....	236
attacks (IPS Rulebase) .....	237
attack-type .....	238
attack-type (Anomaly) .....	238
attack-type (Chain) .....	239
attack-type (Signature) .....	240
authentication .....	243
authentication-algorithm .....	244
authentication-method .....	245
auto-re-enrollment .....	246
automatic .....	247
bind-interface .....	247
c-timeout .....	248
ca-identity .....	248
ca-profile .....	249
ca-profile-name .....	250
cache-size .....	250
call-flood .....	251
category .....	251
certificate .....	252
certificate-id .....	252
chain .....	253
challenge-password .....	254
check-first-session .....	254
clear-threshold .....	255
code .....	255
connection-flood .....	256
connections-limit .....	256
container .....	257
context .....	257
count .....	258
count (Custom Attack) .....	258
count (Security Policies) .....	259

crl .....	260
custom-attack .....	261
custom-attack-group .....	265
custom-attacks .....	265
data-length .....	266
dead-peer-detection .....	267
default-policy .....	268
deny .....	269
deny (Policy) .....	269
deny (SIP) .....	270
description .....	271
description (IDP Policy) .....	271
description (Security Policies) .....	271
destination .....	272
destination (Destination NAT Services Gateway) .....	273
destination (IP Headers in Signature Attack) .....	274
destination-address .....	275
destination-address (Destination NAT Services Gateway) .....	275
destination-address (IDP Policy) .....	276
destination-address (Security Policies) .....	276
destination-address (Source NAT Services Gateway) .....	277
destination-address (Static NAT Services Gateway) .....	277
destination-address (Traffic Policy Services Gateway) .....	278
destination-except .....	278
destination-ip .....	279
destination-ip-based .....	279
destination-nat .....	280
destination-nat (Destination NAT Services Gateway) .....	280
destination-nat (Destination NAT Services Router) .....	281
destination-nat (Security Policies) .....	282
destination-port .....	283
destination-port (Destination NAT Services Gateway) .....	283
destination-port (Signature Attack) .....	284
destination-threshold .....	285
detect-shellcode .....	285
detector .....	286
df-bit .....	286
dh-group .....	287
direction .....	288
direction (Custom Attack) .....	288
direction (Dynamic Attack Group) .....	289
disable-call-id-hiding .....	289
distinguished-name .....	290
dns .....	291
dynamic .....	292
dynamic-attack-group .....	293
early-ageout .....	294
enable-all-qmodules .....	294
enable-packet-pool .....	295
encryption .....	296
encryption-algorithm .....	297

endpoint-registration-timeout .....	297
enrollment .....	298
establish-tunnels .....	299
expression .....	300
external-interface .....	301
external-interface (IKE Gateway) .....	301
external-interface (Manual Security Association) .....	301
false-positives .....	302
family .....	303
filters .....	304
fin-no-ack .....	305
firewall-authentication .....	306
firewall-authentication (Policies) .....	306
firewall-authentication (Security) .....	307
flood .....	308
flood (ICMP) .....	308
flood (UDP) .....	309
flow .....	310
flow (IDP) .....	310
flow (Security Flow) .....	311
forwarding-options .....	312
fragment .....	313
from .....	313
from-zone .....	314
from-zone (IDP Policy) .....	314
from-zone (Security Policies) .....	315
ftp .....	317
functional-zone .....	318
gatekeeper .....	319
gateway .....	320
gateway (IKE) .....	321
gateway (IPsec) .....	322
gateway (Manual Security Association) .....	322
global .....	323
gre-in .....	324
gre-out .....	325
group-members .....	326
h323 .....	327
header-length .....	328
high-watermark .....	328
host-address-base .....	329
host-address-low .....	329
host-inbound-traffic .....	330
hostname .....	331
icmp .....	332
icmp (Protocol Binding Custom Attack) .....	332
icmp (Security Screen) .....	333
icmp (Signature Attack) .....	334
identification .....	335
identification (ICMP Headers in Signature Attack) .....	335
identification (IP Headers in Signature Attack) .....	336

idle-time .....	336
idp .....	337
idp-policy .....	344
ids-option .....	346
ignore-mem-overflow .....	347
ignore-regular-expression .....	348
ike .....	349
ike (IPsec VPN) .....	349
ike (Security) .....	350
ike-policy .....	351
ike-user-type .....	352
inactive-media-timeout .....	353
inactive-media-timeout (MGCP) .....	353
inactive-media-timeout (SCCP) .....	354
inactive-media-timeout (SIP) .....	354
include-destination-address .....	355
inet .....	355
inet6 .....	356
install-interval .....	356
interface .....	357
interface (ARP Proxy Services Gateway) .....	357
interface (NAT Services Router) .....	358
interfaces .....	359
interval .....	360
interval (IDP) .....	360
interval (IKE) .....	360
ip .....	361
ip (Protocol Binding Custom Attack) .....	361
ip (Security Screen) .....	362
ip (Signature Attack) .....	364
ip-action .....	365
ip-block .....	365
ip-close .....	366
ip-flags .....	366
ip-notify .....	367
ips .....	367
ipsec-policy .....	368
ipsec-vpn .....	369
ipsec-vpn (Flow) .....	369
ipsec-vpn (Policies) .....	370
ip-sweep .....	370
iso .....	371
land .....	371
large .....	372
lifetime-kilobytes .....	372
limit-session .....	373
local .....	373
local-certificate .....	374
local-identity .....	375

log .....	376
log (IDP) .....	376
log (IDP Policy) .....	377
log (Security Policies) .....	377
log-attacks .....	378
log-errors .....	378
log-supercede-min .....	379
low-watermark .....	379
management .....	380
manual .....	381
match .....	382
match (Destination NAT Services Gateway) .....	382
match (IDP Policy) .....	383
match (Security Policies) .....	384
match (Source NAT Services Gateway) .....	384
match (Static NAT Services Gateway) .....	385
max-flow-mem .....	385
max-logs-operate .....	386
max-packet-mem .....	386
max-packet-memory .....	387
max-sessions .....	387
max-tcp-session-packet-memory .....	388
max-time-report .....	388
max-timers-poll-ticks .....	389
max-udp-session-packet-memory .....	389
maximum-call-duration .....	390
media-source-port-any .....	390
member .....	391
message-flood .....	392
message-flood (H323) .....	392
message-flood (MGCP) .....	393
mgcp .....	394
mode .....	395
mode (Forwarding-Options) .....	395
mode (Policy) .....	396
mpls .....	396
msrpc .....	397
mss .....	398
nat .....	399
nat (Services Gateway Configuration) .....	400
nat (Services Router Configuration) .....	402
nat-keepalive .....	403
negate .....	404
no-allow-icmp-without-flow .....	404
no-anti-replay .....	404
no-enable-all-qmodules .....	404
no-enable-packet-pool .....	405
no-log-errors .....	405
no-nat-traversal .....	405
no-policy-lookup-cache .....	405



no-port-translation .....	406
no-reset-on-policy .....	406
no-sequence-check .....	406
no-syn-check .....	407
no-syn-check-in-tunnel .....	407
notification .....	408
optimized .....	408
option .....	409
order .....	409
overflow-pool .....	410
overflow-pool (Source NAT Services Gateway) .....	410
overflow-pool (Source NAT Services Router) .....	411
pair-policy .....	412
pass-through .....	413
pattern .....	414
peer-certificate-type .....	414
perfect-forward-secrecy .....	415
performance .....	416
permit .....	417
ping-death .....	418
pki .....	419
policies .....	421
policy .....	423
policy (IKE) .....	423
policy (IPsec) .....	424
policy (Security) .....	425
policy-lookup-cache .....	426
policy-rematch .....	427
pool .....	428
pool (Destination NAT Services Gateway) .....	428
pool (Pool Set) .....	429
pool (Source NAT) .....	429
pool (Source NAT Services Gateway) .....	430
pool-set .....	430
pool-utilization-alarm .....	431
port .....	432
port-scan .....	433
pptp .....	434
pre-filter-shellcode .....	435
predefined-attack-groups .....	435
predefined-attacks .....	436
pre-shared-key .....	436
process-ignore-s2c .....	437
process-override .....	437
process-port .....	438
products .....	438
proposal .....	439
proposal-set .....	440
proposal-set (IKE) .....	441
proposal-set (IPsec) .....	442
protect .....	443

protocol .....	444
protocol (IPsec) .....	444
protocol (Manual Security Association) .....	445
protocol (IP Headers in Signature Attack) .....	445
protocol (Signature Attack) .....	446
protocol-binding .....	449
protocol-name .....	450
protocols .....	451
protocols (Interface Host-Inbound Traffic) .....	452
protocols (Zone Host-Inbound Traffic) .....	454
proxy-arp .....	456
proxy-arp (Services Gateway Configuration) .....	456
proxy-arp (Services Router Configuration) .....	457
proxy-identity .....	457
raise-threshold .....	458
real .....	459
re-assembler .....	460
re-enroll-trigger-time-percentage .....	460
recommended .....	461
recommended-action .....	462
regexp .....	463
reject .....	463
reject-timeout .....	464
remote .....	464
reset .....	465
reset-on-policy .....	465
respond-bad-spi .....	466
retain-hold-resource .....	466
revocation-check .....	467
route-change-timeout .....	468
routing-instance .....	469
routing-instance (Destination NAT Services Gateway) .....	469
routing-instance (Source NAT Services Gateway) .....	469
rpc .....	470
rsh .....	471
rst-invalidate-session .....	472
rst-sequence-check .....	472
rtsp .....	473
rule .....	474
rule (Destination NAT) .....	474
rule (Exempt Rulebase) .....	475
rule (IPS Rulebase) .....	476
rule (Source NAT) .....	477
rule (Static NAT) .....	478
rule-set .....	479
rule-set (Destination NAT Services Gateway) .....	479
rule-set (Source NAT Services Gateway) .....	480
rule-set (Static NAT Services Gateway) .....	481
rulebase-exempt .....	482
rulebase-ips .....	483
sccp .....	484

scheduler-name .....	485
scope .....	486
scope (Chain Attack) .....	486
scope (Custom Attack) .....	487
screen .....	488
screen (Security) .....	489
screen (Zones) .....	490
security-package .....	491
security-zone .....	492
sensor-configuration .....	494
session-close .....	495
session-init .....	496
sequence-number .....	497
sequence-number (ICMP Headers in Signature Attack) .....	497
sequence-number (TCP Headers in Signature Attack) .....	498
service .....	499
service (Anomaly Attack) .....	499
service (Dynamic Attack Group) .....	499
service (Security IPsec) .....	500
severity .....	501
severity (Custom Attack) .....	501
severity (Dynamic Attack Group) .....	502
severity (IPS Rulebase) .....	503
shellcode .....	504
signature .....	505
sip .....	509
source .....	510
source (IP Headers in Signature Attack) .....	510
source (Source NAT Services Gateway) .....	511
source-address .....	513
source-address (Destination NAT Services Gateway) .....	513
source-address (IDP Policy) .....	514
source-address (Security Policies) .....	514
source-address (Source NAT Services Gateway) .....	515
source-except .....	515
source-interface .....	516
source-ip-based .....	516
source-nat .....	517
source-nat (NAT) .....	517
source-nat (NAT Interface) .....	518
source-nat (Security Policies) .....	519
source-nat (Source NAT Services Gateway) .....	519
source-port .....	520
source-threshold .....	521
spi .....	522
sql .....	523
ssh-known-hosts .....	524
start-log .....	525
start-time .....	525
static .....	526

static-nat .....	527
static-nat (Static NAT Services Router) .....	527
static-nat (Static NAT Services Gateway) .....	528
sunrpc .....	529
suppression .....	530
syn-ack-ack-proxy .....	531
syn-fin .....	531
syn-flood .....	532
syn-flood-protection-mode .....	533
syn-frag .....	534
system-services .....	535
system-services (Interface Host-Inbound Traffic) .....	536
system-services (Zone Host-Inbound Traffic) .....	538
t1-interval .....	539
t4-interval .....	540
talk .....	541
target .....	542
tcp .....	543
tcp (Protocol Binding Custom Attack) .....	543
tcp (Security Screen) .....	544
tcp (Signature Attack) .....	545
tcp-flags .....	547
tcp-initial-timeout .....	548
tcp-mss .....	549
tcp-no-flag .....	550
tcp-rst .....	550
tcp-session .....	551
terminal .....	552
test .....	552
tftp .....	553
then .....	554
then (Destination NAT Services Gateway) .....	554
then (IDP Policy) .....	555
then (Security Policies) .....	556
then (Source NAT Services Gateway) .....	557
then (Static NAT Services Gateway) .....	557
threshold .....	558
time-binding .....	558
timeout .....	559
timeout (IDP Policy) .....	559
timeout (Security Screen) .....	560
to .....	560
to-zone .....	561
tos .....	562
total-length .....	563
traceoptions .....	564
traceoptions (firewall-authentication) .....	565
traceoptions (H.323 ALG) .....	566
traceoptions (Flow) .....	567
traceoptions (IDP) .....	569
traceoptions (IKE) .....	571

traceoptions (IPsec) .....	572
traceoptions (MGCP ALG) .....	573
traceoptions (NAT Services Gateway) .....	574
traceoptions (NAT Services Router) .....	576
traceoptions (PKI) .....	578
traceoptions (Policies) .....	580
traceoptions (SCCP ALG) .....	582
traceoptions (Screen) .....	583
traceoptions (Security) .....	585
traceoptions (SIP ALG) .....	587
transaction-timeout .....	588
trusted-ca .....	588
ttl .....	589
tunable-name .....	590
tunable-value .....	590
tunnel .....	591
type .....	592
type (ICMP Headers in Signature Attack) .....	592
type (Dynamic Attack Group) .....	593
udp .....	594
udp (Protocol Binding Custom Attack) .....	594
udp (Security Screen) .....	595
udp (Signature Attack) .....	596
unknown-message .....	597
unknown-message (H.323 ALG) .....	597
unknown-message (MGCP ALG) .....	598
unknown-message (SCCP ALG) .....	599
unknown-message (SIP ALG) .....	600
urgent-pointer .....	601
url .....	601
user-at-hostname .....	602
vpn .....	603
vpn-monitor .....	604
vpn-monitor-options .....	605
web-authentication .....	606
web-redirect .....	607
wildcard .....	608
window-scale .....	608
window-size .....	609
winnuke .....	609
xauth .....	610
zones .....	611

**Chapter 17****Services Hierarchy****613**

Services Configuration Statement Hierarchy .....	613
--	-----

<b>Chapter 18</b>	<b>SNMP Hierarchy and Statements</b>	<b>615</b>
	SNMP Configuration Statement Hierarchy .....	615
	authorization .....	620
	client-list-name .....	620
<b>Chapter 19</b>	<b>System Hierarchy and Statements</b>	<b>621</b>
	System Configuration Statement Hierarchy .....	621
	cache .....	631
	client .....	632
	dns-proxy .....	633
	domain-name .....	634
	dynamic-dns .....	634
	firewall-authentication-service .....	635
	general-authentication-service .....	636
	interface .....	637
	name-server .....	637
	network-security .....	638
	pki-local-certificate .....	638
	propagate-settings .....	639
	server-select .....	639
	system-generated-certificate .....	640
	traceoptions .....	641
	traceoptions (DNS Proxy) .....	642
	traceoptions (General Authentication Service) .....	644
	traceoptions (WAN Acceleration) .....	646
	wan-acceleration .....	647
<b>Part 2</b>	<b>Operational Commands</b>	
<b>Chapter 20</b>	<b>Clear Commands</b>	<b>651</b>
	clear chassis cluster control-plane statistics .....	652
	clear chassis cluster data-plane statistics .....	653
	clear chassis cluster failover-count .....	654
	clear chassis cluster statistics .....	655
	clear network-access requests pending .....	656
	clear network-access requests statistics .....	657
	clear network-access securid-node-secret-file .....	658
	clear security alg h323 counters .....	659
	clear security alg mgcp calls .....	660
	clear security alg mgcp counters .....	661
	clear security alg msrpc portmap .....	662
	clear security alg sccp calls .....	663
	clear security alg sccp counters .....	664
	clear security alg sip calls .....	665
	clear security alg sip counters .....	666

clear security alg sunrpc portmap .....	667
clear security firewall-authentication history .....	668
clear security firewall-authentication history address .....	669
clear security firewall-authentication history identifier .....	670
clear security firewall-authentication users .....	671
clear security firewall-authentication users address .....	672
clear security firewall-authentication users identifier .....	673
clear security flow session all .....	674
clear security flow session application .....	675
clear security flow session destination-port .....	677
clear security flow session destination-prefix .....	678
clear security flow session interface .....	679
clear security flow session protocol .....	680
clear security flow session resource-manager .....	682
clear security flow session session-identifier .....	683
clear security flow session source-port .....	684
clear security flow session source-prefix .....	685
clear security idp application-identification application-system-cache .....	686
clear security idp attack table .....	687
clear security idp counters application-identification .....	688
clear security idp counters dfa .....	689
clear security idp counters flow .....	690
clear security idp counters ips .....	691
clear security idp counters log .....	692
clear security idp counters packet .....	693
clear security idp counters policy-manager .....	694
clear security idp counters tcp-reassembler .....	695
clear security ike respond-bad-spi-count .....	696
clear security ike security-associations .....	697
clear security ipsec security-associations .....	699
clear security ipsec statistics .....	700
clear security nat incoming-table .....	701
clear security pki key-pair .....	702
clear security pki local-certificate .....	703
clear security policies statistics .....	704
clear security screen statistics .....	705
clear security screen statistics interface .....	706
clear security screen statistics zone .....	707
clear system services dns-proxy cache .....	708
clear system services dns-proxy statistics .....	709

## Chapter 21

### Request Commands

**711**

request chassis cluster failover node .....	712
request chassis cluster failover reset .....	713
request security idp security-package download .....	714
request security idp security-package install .....	716
request security pki ca-certificate verify .....	717
request security pki local-certificate generate-self-signed .....	718
request security pki local-certificate verify .....	720

request system partition compact-flash .....	721
request system services dhcp .....	722
request wan-acceleration login .....	723

**Chapter 22****Restart Commands****725**

restart wan-acceleration .....	726
--------------------------------	-----

**Chapter 23****Show Commands****727**

show bgp neighbor .....	728
show chassis cluster control-plane statistics .....	732
show chassis cluster data-plane statistics .....	733
show chassis cluster interfaces .....	735
show chassis cluster statistics .....	736
show chassis cluster status .....	739
show chassis fpc .....	741
show chassis hardware .....	744
show interfaces .....	749
show interfaces flow-statistics .....	754
show network-access requests pending .....	757
show network-access requests statistics .....	759
show network-access securid-node-secret-file .....	760
show schedulers .....	761
show security alg h323 counters .....	763
show security alg mgcp calls .....	765
show security alg mgcp counters .....	767
show security alg mgcp endpoints .....	769
show security alg msrpc .....	771
show security alg sctp calls .....	773
show security alg sctp counters .....	775
show security alg sip calls .....	777
show security alg sip counters .....	780
show security alg sip rate .....	784
show security alg sip transactions .....	786
show security alg sunrpc portmap .....	787
show security firewall-authentication history .....	788
show security firewall-authentication history address .....	790
show security firewall-authentication history identifier .....	793
show security firewall-authentication users .....	796
show security firewall-authentication users address .....	798
show security firewall-authentication users identifier .....	800
show security flow gate .....	802
show security flow session .....	805
show security flow session application .....	807
show security flow session destination-port .....	809
show security flow session destination-prefix .....	811
show security flow session interface .....	813
show security flow session protocol .....	815
show security flow session resource-manager .....	818



show security flow session session-identifier .....	820
show security flow session source-port .....	824
show security flow session source-prefix .....	826
show security flow session summary .....	828
show security flow session tunnel .....	830
show security idp active-policy .....	832
show security idp application-identification application-system-cache .....	833
show security idp attack table .....	834
show security idp counters application-identification .....	835
show security idp counters dfa .....	837
show security idp counters flow .....	838
show security idp counters ips .....	841
show security idp counters log .....	843
show security idp counters packet .....	846
show security idp counters policy-manager .....	849
show security idp counters tcp-reassembler .....	850
show security idp memory .....	853
show security idp security-package-version .....	854
show security idp status .....	855
show security ike pre-shared-key .....	856
show security ike security-associations .....	857
show security ipsec next-hop-tunnels .....	862
show security ipsec security-associations .....	863
show security ipsec statistics .....	869
show security monitoring fpc fpc-number .....	872
show security nat destination pool .....	874
show security nat destination rule .....	876
show security nat destination summary .....	879
show security nat destination-nat summary .....	881
show security nat incoming-table .....	882
show security nat interface-nat-ports .....	884
show security nat source pool .....	886
show security nat source rule .....	888
show security nat source summary .....	891
show security nat source-nat pool .....	893
show security nat source-nat summary .....	895
show security nat static rule .....	896
show security nat static-nat summary .....	898
show security pki ca-certificate .....	900
show security pki certificate-request .....	904
show security pki crl .....	906
show security pki local-certificate .....	908
show security policies .....	912
show security resource-manager group active .....	915
show security resource-manager resource active .....	917
show security resource-manager settings .....	919
show security screen ids-option .....	921
show security screen statistics .....	923
show security zones .....	928
show security zones type .....	930
show system services dhcp client .....	932

show system services dhcp relay-statistics .....935

show system services dns-proxy .....937

show system services dynamic-dns client .....939

show wan-acceleration status .....941

**Part 3**

**Index**

---

Index .....945

# About This Guide

This preface provides the following guidelines for using the *JUNOS® Software CLI Reference*:

- Objectives on page xxvii
- Audience on page xxviii
- Supported Routing Platforms on page xxviii
- How to Use This Manual on page xxviii
- Document Conventions on page xxx
- List of Technical Publications on page xxxii
- Documentation Feedback on page xxxiii
- Requesting Technical Support on page xxxiv

## Objectives

---

This reference documents command-line interface (CLI) statements and commands for J-series Services Routers running JUNOS software with enhanced services and SRX-series services gateways running JUNOS software. This reference provides the following information:

- Configuration hierarchies—Complete hierarchies of the configuration statements that you use to configure J-series Services Routers and SRX-series services gateways. Hierarchies include all configuration statements—including the statements shared with the JUNOS software—and highlight statements specific to the J-series and SRX-series devices in bold type.
- Configuration statements—Descriptions of the configuration statements that are unique to the J-series and SRX-series devices.
- Commands—Descriptions of the operational mode commands that you use to monitor and troubleshoot J-series and SRX-series operations.



**NOTE:** This manual documents Release 9.3 of JUNOS software. For additional information—either corrections to or information that might have been omitted from this manual—see the *JUNOS Software with Enhanced Services Release Notes* or *JUNOS Software for SRX-series Services Gateways Release Notes* at <http://www.juniper.net>.

---

## Audience

This manual is designed for anyone who installs, sets up, configures, monitors, or administers a J-series Services Router running JUNOS software with enhanced services or an SRX-series services gateway running JUNOS software. The manual is intended for the following audiences:

- Customers with technical knowledge of and experience with networks and network security, the Internet, and Internet routing protocols
- Network administrators who install, configure, and manage Internet routers

Personnel operating the equipment must be trained and competent; must not conduct themselves in a careless, willfully negligent, or hostile manner; and must abide by the instructions provided by the documentation.

## Supported Routing Platforms

This manual describes features supported on J-series Services Routers running JUNOS software with enhanced services and SRX-series services gateways running JUNOS software.

## How to Use This Manual

This manual and the other manuals in this set explain how to install, configure, and manage:

- JUNOS software with enhanced services for J-series Services Routers
- JUNOS software for SRX-series services gateways

Table 1 on page xxviii identifies the tasks required to configure and manage these devices and shows where to find task information and instructions.

For an annotated list of the documentation referred to in Table 1 on page xxviii, see “List of Technical Publications” on page xxxii. All documents are available at <http://www.juniper.net/techpubs/>.

**Table 1: Tasks and Related Documentation**

Task	Related Documentation
<b>Basic Device Installation and Setup</b>	
■ Reviewing safety warnings and compliance statements	J-series Services Routers:
■ Installing hardware and establishing basic connectivity	■ <i>JUNOS Software with Enhanced Services Quick Start</i>
■ Initially setting up a device	■ <i>JUNOS Software with Enhanced Services Hardware Guide</i>
	■ <i>JUNOS Software with Enhanced Services Release Notes</i>
	SRX-series services gateways: the appropriate <i>Services Gateway Getting Started Guide</i>

**Table 1: Tasks and Related Documentation** *(continued)*

Task	Related Documentation
<b>Migration from ScreenOS or JUNOS Software to JUNOS Software with Enhanced Services (if necessary)</b>	
<ul style="list-style-type: none"><li>■ Migrating from JUNOS Release 8.3 or later to JUNOS software with enhanced services</li><li>■ Migrating from ScreenOS Release 5.4 or later JUNOS software with enhanced services</li></ul>	<i>JUNOS Software with Enhanced Services Migration Guide</i> (J-series Services Routers only)
<b>Context—Changing to Secure Context or Router Context</b>	
Changing the device from one context to another and understanding the factory default settings	<i>JUNOS Software Administration Guide</i>
<b>Interface Configuration</b>	
Configuring device interfaces	<ul style="list-style-type: none"><li>■ <i>JUNOS Software Interfaces and Routing Configuration Guide</i></li><li>■ <i>JUNOS Software CLI Reference</i></li></ul>
<b>Deployment Planning and Configuration</b>	
<ul style="list-style-type: none"><li>■ Understanding and gathering information required to design network firewalls and IPsec VPNs</li><li>■ Implementing a JUNOS software with enhanced services firewall from a sample scenario</li><li>■ Implementing a policy-based IPsec VPN from a sample scenario</li></ul>	<i>JUNOS Software with Enhanced Services Design and Implementation Guide</i> (J-series Services Routers only)
<b>Security Configuration</b>	
Configuring and managing the following security services: <ul style="list-style-type: none"><li>■ Stateful firewall policies</li><li>■ Zones and their interfaces and address books</li><li>■ IPsec VPNs</li><li>■ Firewall screens</li><li>■ Interface modes: Network Address Translation (NAT) mode and Router mode</li><li>■ Public Key Cryptography (PKI)</li><li>■ Application Layer Gateways (ALGs)</li><li>■ Chassis clusters</li><li>■ Intrusion Detection and Prevention (IDP)</li></ul>	<ul style="list-style-type: none"><li>■ <i>JUNOS Software Security Configuration Guide</i></li><li>■ <i>JUNOS Software CLI Reference</i></li></ul>
<b>Routing Protocols and Services Configuration</b>	
<ul style="list-style-type: none"><li>■ Configuring routing protocols, including static routes and the dynamic routing protocols RIP, OSPF, BGP, and IS-IS</li><li>■ Configuring class-of-service (CoS) features, including traffic shaping and policing</li><li>■ Configuring packet-based stateless firewall filters (access control lists) to control access and limit traffic rates</li><li>■ Configuring MPLS to control network traffic patterns</li></ul>	<ul style="list-style-type: none"><li>■ <i>JUNOS Software Interfaces and Routing Configuration Guide</i></li><li>■ <i>JUNOS Software CLI Reference</i></li></ul>
<b>WAN Acceleration Module Installation (Optional)</b>	

**Table 1: Tasks and Related Documentation** *(continued)*

Task	Related Documentation
Installing and initially configuring a WXC Integrated Services Module (ISM 200)	<i>WXC Integrated Services Module Installation and Configuration Guide</i> (J-series Services Routers only)
<b>User and System Administration</b>	
<ul style="list-style-type: none"> <li>■ Administering user authentication and access</li> <li>■ Monitoring the device, routing protocols, and routing operations</li> <li>■ Configuring and monitoring system alarms and events, real-time performance (RPM) probes, and performance</li> <li>■ Monitoring the firewall and other security-related services</li> <li>■ Managing system log files</li> <li>■ Upgrading software</li> <li>■ Diagnosing common problems</li> </ul>	<i>JUNOS Software Administration Guide</i>
<b>User Interfaces</b>	
<ul style="list-style-type: none"> <li>■ Understanding and using the J-Web interface</li> <li>■ Understanding and using the CLI configuration editor</li> </ul>	<ul style="list-style-type: none"> <li>■ <i>JUNOS Software with Enhanced Services Quick Start</i> (J-series Services Routers only)</li> <li>■ <i>JUNOS Software Administration Guide</i></li> </ul>

## Document Conventions

Table 2 on page xxx defines the notice icons used in this guide.

**Table 2: Notice Icons**





Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.

Table 3 on page xxxi defines the text and syntax conventions used in this guide.

**Table 3: Text and Syntax Conventions**

Convention	Description	Examples
Bold text like this	Represents text that you type.	To enter configuration mode, type the <b>configure</b> command:  user@host> <b>configure</b>
Fixed-width text like this	Represents output that appears on the terminal screen.	user@host> <b>show chassis alarms</b> No alarms currently active
<i>Italic text like this</i>	<ul style="list-style-type: none"> <li>Introduces important new terms.</li> <li>Identifies book names.</li> <li>Identifies RFC and Internet draft titles.</li> </ul>	<ul style="list-style-type: none"> <li>A policy <i>term</i> is a named structure that defines match conditions and actions.</li> <li><i>JUNOS System Basics Configuration Guide</i></li> <li>RFC 1997, <i>BGP Communities Attribute</i></li> </ul>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name:  [edit] root@# <b>set system domain-name</b> <i>domain-name</i>
Plain text like this	Represents names of configuration statements, commands, files, and directories; IP addresses; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none"> <li>To configure a stub area, include the <b>stub</b> statement at the [edit <b>protocols ospf area area-id</b>] hierarchy level.</li> <li>The console port is labeled <b>CONSOLE</b>.</li> </ul>
< > (angle brackets)	Enclose optional keywords or variables.	stub <default-metric <i>metric</i> >;
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	broadcast   multicast  ( <i>string1</i>   <i>string2</i>   <i>string3</i> )
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	rsvp { # Required for dynamic MPLS only
[ ] (square brackets)	Enclose a variable for which you can substitute one or more values.	community name members [ <i>community-ids</i> ]
Indentation and braces ( { } )	Identify a level in the configuration hierarchy.	[edit] routing-options { static { route default { nexthop <i>address</i> ; retain; } } }
; (semicolon)	Identifies a leaf statement at a configuration hierarchy level.	

**Table 3: Text and Syntax Conventions** (*continued*)

Convention	Description	Examples
<b>J-Web GUI Conventions</b>		
<b>Bold text like this</b>	Represents J-Web graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none"> <li>■ In the Logical Interfaces box, select <b>All Interfaces</b>.</li> <li>■ To cancel the configuration, click <b>Cancel</b>.</li> </ul>
<b>&gt;</b> (bold right angle bracket)	Separates levels in a hierarchy of J-Web selections.	In the configuration editor hierarchy, select <b>Protocols &gt; Ospf</b> .

## List of Technical Publications

The following sections list hardware and software guides and release notes for SRX-series services gateways and J-series Services Routers running JUNOS software.

All documents are available at <http://www.juniper.net/techpubs/>.

- Hardware Guides**
- *SRX 5600 Services Gateway Hardware Guide*—Describes hardware components, installation, basic configuration, and basic troubleshooting procedures for the SRX 5600 services gateway. This guide explains how to prepare a site, unpack and install the device, replace device hardware, establish basic connectivity, and perform routine maintenance.
  - *SRX 5800 Services Gateway Hardware Guide*—Describes hardware components, installation, basic configuration, and basic troubleshooting procedures for the SRX 5800 services gateway. This guide explains how to prepare a site, unpack and install the device, replace device hardware, establish basic connectivity, and perform routine maintenance.
  - *JUNOS Software with Enhanced Services Quick Start*—Explains how to quickly set up a J-series Services Router. This document contains router declarations of conformity.
  - *JUNOS Software with Enhanced Services Hardware Guide*—Provides an overview, basic instructions, and specifications for J-series Services Routers. This guide explains how to prepare a site, unpack and install the router, replace router hardware, and establish basic router connectivity. This guide contains hardware descriptions and specifications.
- Software Guides**
- *JUNOS Software Interfaces and Routing Configuration Guide*—Explains how to configure SRX-series and J-series interfaces for basic IP routing with standard routing protocols, ISDN service, firewall filters (access control lists), and class-of-service (CoS) traffic classification.
  - *JUNOS Software Security Configuration Guide*—Explains how to configure and manage SRX-series and J-series security services such as stateful firewall policies, IPsec VPNs, firewall screens, Network Address Translation (NAT), Public Key Cryptography, chassis clusters, Application Layer Gateways (ALGs), and Intrusion Detection and Prevention (IDP).



- *JUNOS Software Administration Guide*—Shows how to monitor SRX-series and J-series devices and routing operations, firewall and security services, system alarms and events, and network performance. This guide also shows how to administer user authentication and access, upgrade software, and diagnose common problems.
  - *JUNOS Software CLI Reference*—Provides the complete configuration hierarchy available on SRX-series and J-series devices. This guide also describes the configuration statements and operational mode commands unique to these devices.
  - *JUNOS Network Management Configuration Guide*—Describes enterprise-specific MIBs for JUNOS software. The information in this guide is applicable to M-series, T-series, EX-series, SRX-series, and J-series devices.
  - *JUNOS System Log Messages Reference*—Describes how to access and interpret system log messages generated by JUNOS software modules and provides a reference page for each message. The information in this guide is applicable to M-series, T-series, EX-series, SRX-series, and J-series devices.
  - *JUNOS Software with Enhanced Services Design and Implementation Guide*—Provides guidelines and examples for designing and implementing IPsec VPNs, firewalls, and routing on J-series Services Routers running JUNOS software with enhanced services.
  - *JUNOS Software with Enhanced Services Migration Guide*—Provides instructions for migrating an SSG device running ScreenOS software or a J-series Services Router running the JUNOS software to JUNOS software with enhanced services.
  - *WXC Integrated Services Module Installation and Configuration Guide*—Explains how to install and initially configure a WXC Integrated Services Module in a J-series Services Router for application acceleration.
- Release Notes**
- *JUNOS Software for SRX-series Services Gateways Release Notes*—Summarizes new features and known problems for SRX-series services gateways and the JUNOS software running on those devices. The release notes also contain corrections and updates to the manuals and software upgrade and downgrade instructions.
  - *JUNOS Software with Enhanced Services Release Notes*—Summarizes new features and known problems for J-series Services Routers and the JUNOS software running on those routers. The release notes also contain corrections and updates to the manuals and software upgrade and downgrade instructions.

## Documentation Feedback

---

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation. You can send your comments to [techpubs-comments@juniper.net](mailto:techpubs-comments@juniper.net), or fill out the documentation feedback form at <https://www.juniper.net/cgi-bin/docbugreport/>. If you are using e-mail, be sure to include the following information with your comments:

- Document name
- Document part number

- Page number
- Software release version (not required for *Network Operations Guides [NOGs]*)

## Requesting Technical Support

---

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or JNASC support contract, or are covered under warranty, and need postsales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the JTAC User Guide located at <http://www.juniper.net/customers/support/downloads/710059.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC Hours of Operation —The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

### Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Search for known bugs: <http://www2.juniper.net/kb/>
- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>
- Download the latest versions of software and review release notes: <http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <https://www.juniper.net/alerts/>
- Join and participate in the Juniper Networks Community Forum: <http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool located at <https://tools.juniper.net/SerialNumberEntitlementSearch/>.

### Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/> .
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, visit us at <http://www.juniper.net/support/requesting-support.html>.



## **Part 1**

# **Configuration Statements**

- Access Hierarchy and Statements on page 3
- Accounting-Options Hierarchy on page 45
- Applications Hierarchy and Statements on page 47
- Chassis Hierarchy and Statements on page 61
- Class-of-Service Hierarchy on page 79
- Event-Options Hierarchy on page 83
- Firewall Hierarchy on page 85
- Forwarding-Options Hierarchy and Statements on page 89
- Groups Hierarchy on page 95
- Interfaces Hierarchy and Statements on page 97
- Policy-Options Hierarchy and Statements on page 121
- Protocols Hierarchy on page 125
- Routing-Instances Hierarchy on page 149
- Routing-Options Hierarchy on page 161
- Schedulers Hierarchy and Statements on page 169
- Security Hierarchy and Statements on page 185
- Services Hierarchy on page 613
- SNMP Hierarchy and Statements on page 615
- System Hierarchy and Statements on page 621



## Chapter 1

# Access Hierarchy and Statements

This chapter presents the complete **access** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **access** configuration hierarchy to configure access to the device and user authentication methods. For configuration instructions, see the *JUNOS Software Security Configuration Guide*.

For information about **access** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS System Basics Configuration Guide*.

- Access Configuration Statement Hierarchy on page 3

## Access Configuration Statement Hierarchy

---

To configure device access and user authentication, use the following statements at the [edit **access**] hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **access** hierarchy are shown in normal font and are documented in the *JUNOS System Basics Configuration Guide*.

```
access {  
  firewall-authentication {  
    pass-through {  
      default-profile profile-name;  
      (ftp | http | telnet) {  
        banner {  
          fail string;  
          login string;  
          success string;  
        }  
      }  
    }  
  }  
  traceoptions {  
    file filename <files number> <match regular-expression>  
    <size maximum-file-size> <world-readable | no-world-readable>  
    flag flag;  
  }  
}
```

```

    }
    web-authentication {
        banner {
            success string;
        }
        default-profile profile-name;
    }
}
ldap-options {
    assemble {
        common-name common-name;
    }
    base-distinguished-name base-distinguished-name;
    revert-interval seconds;
    search {
        admin-search {
            distinguished-name distinguished-name;
            password password;
        }
        search-filter filter-name;
    }
}
ldap-server server-address {
    port port-number;
    retry attempts;
    routing-instance routing-instance-name;
    source-address source-address;
    timeout seconds;
}
profile profile-name {
    accounting-order [ accounting-methods ];
    authentication-order ( ldap | password | radius | securid );
    client client-name {
        chap-secret chap-secret;
        client-group [ group-names ];
        firewall-user {
            password password;
        }
        pap-password pap-password;
    }
    client-name-filter client-name {
        count number;
        domain-name domain-name;
        separator special-character;
    }
    ldap-options {
        assemble {
            common-name common-name;
        }
        base-distinguished-name base-distinguished-name;
        revert-interval seconds;
        search {
            admin-search {
                distinguished-name distinguished-name;
                password password;
            }
        }
    }
}

```



```

    }
    search-filter filter-name;
  }
}
ldap-server server-address {
  port port-number;
  retry attempts;
  routing-instance routing-instance-name;
  source-address source-address;
  timeout seconds;
}
radius-options {
  revert-interval seconds;
}
radius-server server-address {
  port port-number;
  retry attempts;
  routing-instance routing-instance-name;
  secret password;
  source-address source-address;
  timeout seconds;
}
session-options {
  client-group [group-names];
  client-idle-timeout minutes;
  client-session-timeout minutes;
}
}
radius-options {
  revert-interval seconds;
}
radius-server server-address {
  port port-number;
  retry attempts;
  routing-instance routing-instance-name;
  secret password;
  source-address source-address;
  timeout seconds;
}
securid-server {
  server-name configuration-file filepath;
}
}

```

## admin-search

---

<b>Syntax</b>	admin-search { distinguished-name <i>distinguished-name</i> ; password <i>password</i> ; }
<b>Hierarchy Level</b>	[edit access ldap-options search], [edit access profile <i>profile-name</i> ldap-options search]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that a Lightweight Directory Access Protocol (LDAP) administrator search is performed. By default, the search is an anonymous search. To perform an administrator search, you must specify administrator credentials, which are used in the bind as part of performing the search.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## assemble

---

<b>Syntax</b>	assemble { common-name <i>common-name</i> ; }
<b>Hierarchy Level</b>	[edit access ldap-options], [edit access profile <i>profile-name</i> ldap-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that a user's LDAP distinguished name (DN) is assembled through the use of a common name identifier, the username, and base distinguished name.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	common-name <i>common-name</i> —Common name identifier used as a prefix for the username during the assembly of the user's distinguished name. For example, uid specifies “ user id,” and cn specifies “common name.”
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## authentication-order

---

<b>Syntax</b>	authentication-order (ldap   password   radius   securid);
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> ]
<b>Release Information</b>	Statement modified in Release 9.1 of JUNOS software.
<b>Description</b>	<p>Set the order in which the JUNOS software tries different authentication methods when verifying that a client can access the devices. For each login attempt, the software tries the authentication methods in order, from first to last.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>■ ldap—Verify the client using LDAP.</li> <li>■ password—Verify the client using the information configured at the [edit access profile <i>profile-name</i> client <i>client-name</i>] hierarchy level.</li> <li>■ radius—Verify the client using RADIUS authentication services.</li> <li>■ securid—Verify the client using SecurID authentication services.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>access—To view this statement in the configuration.</p> <p>access-control—To add this statement to the configuration.</p>

## banner

---

See the following sections:

- banner (FTP, HTTP, Telnet) on page 9
- banner (Web Authentication) on page 10

### ***banner (FTP, HTTP, Telnet)***

**Syntax**    banner {  
               fail *string* ;  
               login *string* ;  
               success *string* ;  
               }

**Hierarchy Level**    [edit access firewall-authentication pass-through (ftp | http | telnet)]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure the banners that appear to users during the FTP, HTTP, and Telnet firewall authentication process. The banners appear during login, after successful authentication, and after failed authentication.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    access—To view this statement in the configuration.  
                                       access-control—To add this statement to the configuration.

**banner (Web Authentication)**

**Syntax**    banner {  
                  success *string* ;  
                  }

**Hierarchy Level**    [edit access firewall-authentication web-authentication]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure the banners that appear to users during the Web Authentication process. The banners appear during login, after successful authentication, and after failed authentication.

                  This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statement is explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    access—To view this statement in the configuration.  
                                  access-control—To add this statement to the configuration.

## base-distinguished-name

---

<b>Syntax</b>	base-distinguished-name <i>base-distinguished-name</i> ;
<b>Hierarchy Level</b>	[edit access ldap-options], [edit access profile <i>profile-name</i> ldap-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the base distinguished name (DN), which can be used in one of the following ways:</p> <ul style="list-style-type: none"> <li>■ If you are using the <b>assemble</b> statement so that the user's distinguished name is being assembled, the base distinguished name is appended to a username to generate the user's distinguished name. The resulting distinguished name is used in the LDAP bind call.</li> <li>■ If you are using the <b>search</b> statement so that the user's distinguished name is found by a search, the search is restricted to the subtree of the base distinguished name.</li> </ul> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>base-distinguished-name</i> —Series of basic properties that define the user. For example in the base distinguished name <b>o=juniper, c=us</b> , where <b>c</b> stands for country, and <b>o</b> for organization.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## client-group

---

<b>Syntax</b>	client-group [ <i>group-names</i> ];
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> client <i>client-name</i> ] [edit access profile <i>profile-name</i> session-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a list of client groups that the client belongs to. If the group list is not defined as part of the client profile, the client group configured at the [edit access profile session-options] hierarchy level is used.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>group-names</i> —Names of one or more groups the client belongs to, separated by spaces—for example <b>g1, g2, g3</b> . The total length of the group name string cannot exceed 256 characters.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## client-idle-timeout

---

<b>Syntax</b>	client-idle-timeout <i>minutes</i> ;
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> session-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specifies the grace period that begins after an authenticated user terminates all sessions and connections. Authentication is not required if a new connection is initiated during the grace period by the same user.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>minutes</i> —Number of minutes of idle time that elapse before the session is terminated. <b>Range:</b> 10 through 255 minutes <b>Default:</b> 10 minutes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.



## client-name-filter

---

<b>Syntax</b>	client-name-filter <i>client-name</i> { count <i>number</i> ; domain-name <i>domain-name</i> ; separator <i>special-character</i> ; }
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Define client-name-related restrictions. Clients whose names follow these restrictions are authenticated on the server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>client-name</i> —Name of the client.  The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## client-session-timeout

---

<b>Syntax</b>	client-session-timeout <i>minutes</i> ;
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> session-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the amount of time after which user sessions are terminated, regardless of user activity (also known as a forced or hard authentication timeout).  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>minutes</i> —Number of minutes after which user sessions are terminated. <b>Range:</b> 1 through 10000 minutes <b>Default:</b> Off
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## configuration-file

---

<b>Syntax</b>	<code>server-name configuration-file <i>filepath</i>;</code>
<b>Hierarchy Level</b>	[edit access securid-server]
<b>Release Information</b>	Statement introduced in Release 9.1 of JUNOS software.
<b>Description</b>	Specify the path of the SecurID server configuration file. The file is copied on the devices in some directory location—for example, <code>/var/db/securid/sdconf.rec</code> .  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>server-name</i> —Name of the SecurID authentication server.  <i>filepath</i> —Path of the SecurID server configuration file.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## count

---

<b>Syntax</b>	<code>count <i>number</i>;</code>
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> client-name-filter <i>client-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the number of characters to be stripped from a client name, from right to left, until the specified number of characters are deleted. The resulting name is sent to the authentication server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Number of characters to be stripped in a client name.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## default-profile

---

<b>Syntax</b>	default-profile <i>profile-name</i> ;
<b>Hierarchy Level</b>	[edit access firewall-authentication pass-through]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the authentication profile to use if no profile is specified in a policy.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>profile-name</i> —Name of the profile.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## distinguished-name

---

<b>Syntax</b>	distinguished-name <i>distinguished-name</i> ;
<b>Hierarchy Level</b>	[edit access ldap-options search admin-search], [edit access profile <i>profile-name</i> ldap-options search admin-search]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the distinguished name of an administrative user. The distinguished name is used in the bind for performing the LDAP search.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>distinguished-name</i> —Set of properties that define the user. For example, cn = admin, ou = eng, o = juniper, dc = net.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## domain-name

---

<b>Syntax</b>	<code>domain-name <i>domain-name</i>;</code>
<b>Hierarchy Level</b>	<code>[edit access profile <i>profile-name</i> client-name-filter <i>client-name</i>]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a domain name that must be in a client's name during the authentication process.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>domain-name</i> —Domain name that must be in a client name. The name must not exceed 128 characters.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## fail

---

<b>Syntax</b>	<code>fail <i>string</i>;</code>
<b>Hierarchy Level</b>	<code>[edit access firewall-authentication pass-through default-profile <i>profile-name</i> (ftp   http   telnet) banner]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the banner that a client sees if the authentication process fails.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>string</i> —Banner text. Maximum length of the message text is 250 characters. Enclose the banner text within spaces or special characters—for example, quotation marks (" ").
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## firewall-authentication

---

**Syntax**

```

firewall-authentication {
    pass-through {
        default-profile profile-name;
        (ftp | http | telnet) {
            banner {
                fail string;
                login string;
                success string;
            }
        }
    }
    traceoptions {
        file filename <files number> <match regular-expression>
        <size maximum-file-size> <world-readable | no-world-readable>
        flag flag;
    }
    web-authentication {
        banner {
            success string;
        }
        default-profile profile-name;
    }
}

```

**Hierarchy Level** [edit access]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure default firewall authentication settings used by firewall authentication policies that restrict and permit access for firewall users to protected resources behind a firewall.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** access—To view this statement in the configuration.  
 access-control—To add this statement to the configuration.

## firewall-user

---

<b>Syntax</b>	<pre> firewall-user {     password <i>password</i>; } </pre>
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> client <i>client-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a client as a firewall user and the associated password (encrypted).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>password <i>password</i>—Password used by the firewall user during local authentication.</p> <p><b>Range:</b> 1 through 128 characters</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>secret—To view this statement in the configuration.</p> <p>secret-control—To add this statement to the configuration.</p>

## ftp

---

<b>Syntax</b>	<pre> ftp {     banner {         fail <i>string</i>;         login <i>string</i>;         success <i>string</i>;     } } </pre>
<b>Hierarchy Level</b>	[edit access firewall-authentication pass-through]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure banners for the FTP login prompt, successful authentication, and failed authentication.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>access—To view this statement in the configuration.</p> <p>access-control—To add this statement to the configuration.</p>

**http**

---

<b>Syntax</b>	<pre>http {   banner {     fail <i>string</i>;     login <i>string</i>;     success <i>string</i>;   } }</pre>
<b>Hierarchy Level</b>	[edit access firewall-authentication pass-through]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure banners for the HTTP login prompt, successful authentication, and failed authentication.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## Idap-options

---

<b>Syntax</b>	<pre> Idap-options {   assemble {     common-name <i>common-name</i>;   }   base-distinguished-name <i>base-distinguished-name</i>;   revert-interval <i>seconds</i>;   search {     admin-search {       distinguished-name <i>distinguished-name</i>;       password <i>password</i>;     }     search-filter <i>filter-name</i>;   } } </pre>
<b>Hierarchy Level</b>	[edit access], [edit access profile <i>profile-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure LDAP authentication options.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining options are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.



## ldap-server

---

**Syntax** ldap-server *server-address* {  
     port *port-number*;  
     retry *attempts*;  
     routing-instance *routing-instance-name*;  
     source-address *source-address*;  
     timeout *seconds*;  
 }

**Hierarchy Level** [edit access],  
 [edit access profile *profile-name*]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify that the device use an LDAP server for authentication.

This statement is supported on J-series and SRX-series devices.

**Options** *server-address*—Address of the LDAP authentication server.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** access—To view this statement in the configuration.  
 access-control—To add this statement to the configuration.

## login

---

<b>Syntax</b>	login <i>string</i> ;
<b>Hierarchy Level</b>	[edit access firewall-authentication pass-through default-profile <i>profile-name</i> (ftp   http   telnet) banner]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the login banner for users using FTP, HTTP, and Telnet during the authentication process.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>string</i> —Banner text. Maximum length of the message text is 250 characters. Enclose the banner text within spaces or special characters—for example quotation marks (" ").
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## pass-through

---

**Syntax**

```
pass-through {
  default-profile profile-name;
  (ftp | http | telnet) {
    banner {
      fail string;
      login string;
      success string;
    }
  }
}
```

**Hierarchy Level** [edit access firewall-authentication]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure pass-through firewall user authentication, when a host or user from one zone needs to access a protected resource in another zone. A user must use an FTP, Telnet, or HTTP client to access the IP address of the protected resource and get authenticated by the firewall. The device uses FTP, Telnet, and HTTP to collect username and password information. Subsequent traffic from the user or host is allowed or denied based on the result of this authentication. After the user is authenticated, the firewall proxies the connection.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** access—To view this statement in the configuration.  
access-control—To add this statement to the configuration.

## password

---

<b>Syntax</b>	<code>password password;</code>
<b>Hierarchy Level</b>	[edit access ldap-options search admin-search], [edit access profile <i>profile-name</i> ldap-options search admin-search]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the plain-text password for the administrative user. This password is used in the bind for performing the LDAP search.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>password</i> —Administrative user password.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## port

---

See the following sections:

- port (LDAP) on page 25
- port (RADIUS) on page 25

### port (LDAP)

<b>Syntax</b>	port <i>port-number</i> ;
<b>Hierarchy Level</b>	[edit access ldap-server <i>server-address</i> ], [edit access profile <i>profile-name</i> ldap-server <i>server-address</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the port number on which to contact the LDAP server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>port-number</i> —Port number on which to contact the LDAP server. <b>Default:</b> 389
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

### port (RADIUS)

<b>Syntax</b>	port <i>port-number</i> ;
<b>Hierarchy Level</b>	[edit access radius-server <i>server-address</i> ], [edit access profile <i>profile-name</i> radius-server <i>server-address</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the port number on which to contact the RADIUS server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>port-number</i> —Port number on which to contact the RADIUS server. <b>Default:</b> 1812 (as specified in RFC 2865)
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## radius-options

---

<b>Syntax</b>	radius-options { revert-interval <i>seconds</i> ; }
<b>Hierarchy Level</b>	[edit access], [edit access profile <i>profile-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure RADIUS options.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statement is explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## radius-server

---

<b>Syntax</b>	<pre>radius-server server-address {     port port-number;     retry attempts;     routing-instance routing-instance-name;     secret password;     source-address source-address;     timeout seconds; }</pre>
<b>Hierarchy Level</b>	[edit access], [edit access profile <i>profile-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure RADIUS for Layer 2 Tunneling Protocol (L2TP) or Point-to-Point Protocol (PPP) authentication.</p> <p>To configure multiple RADIUS servers, include multiple <b>radius-server</b> statements. The servers are tried in order and in a round-robin fashion until a valid response is received from one of the servers or until all the configured retry limits are reached.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>server-address</b>—Address of the RADIUS authentication server.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>access—To view this statement in the configuration.</p> <p>access-control—To add this statement to the configuration.</p>

## retry

---

See the following sections:

- `retry` (LDAP) on page 28
- `retry` (RADIUS) on page 29

### ***retry (LDAP)***

<b>Syntax</b>	<code>retry attempts;</code>
<b>Hierarchy Level</b>	[edit access ldap-server <i>server-address</i> ], [edit access profile <i>profile-name</i> ldap-server <i>server-address</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the number of retries that a device can attempt to contact an LDAP server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>attempts</i> —Number of retries that the device is allowed to attempt to contact an LDAP server. <b>Range:</b> 1 through 10 <b>Default:</b> 3
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.



**retry (RADIUS)**

<b>Syntax</b>	<code>retry attempts;</code>
<b>Hierarchy Level</b>	[edit access radius-server <i>server-address</i> ], [edit access profile <i>profile-name</i> radius-server <i>server-address</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the number of retries that a device can attempt to contact a RADIUS authentication server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>attempts</i> —Number of retries that the device is allowed to attempt to contact a RADIUS server. <b>Range:</b> 1 through 10 <b>Default:</b> 3
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> . See also <b>timeout</b> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## revert-interval

---

See the following sections:

- `revert-interval (LDAP)` on page 30
- `revert-interval (RADIUS)` on page 31

### ***revert-interval (LDAP)***

**Syntax** `revert-interval seconds;`

**Hierarchy Level** `[edit access ldap-options],`  
`[edit access profile profile-name ldap-options]`

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the amount of time that elapses before the primary server is contacted if backup server is being used.

This statement is supported on J-series and SRX-series devices.

**Options** *seconds*—Number of seconds that elapse before the primary server is contacted.  
**Range:** 60 through 4294967295 seconds  
**Default:** 600 seconds

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `access`—To view this statement in the configuration.  
`access-control`—To add this statement to the configuration.

**revert-interval (RADIUS)**

<b>Syntax</b>	revert-interval <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit access radius-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the amount of time that elapses before the primary server is contacted if backup server is being used.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>seconds</i> —Number of seconds that elapse before the primary server is contacted. <b>Range:</b> 60 through 4294967295 seconds <b>Default:</b> 600 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## routing-instance

---

See the following sections:

- routing-instance (LDAP) on page 32
- routing-instance (RADIUS) on page 33

### ***routing-instance (LDAP)***

**Syntax** `routing-instance routing-instance-name;`

**Hierarchy Level** [edit access ldap-server *server-address*],  
[edit access profile *profile-name* ldap-server *server-address*]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure the routing instance used to send LDAP packets to the LDAP server. A routing instance is a collection of routing tables, the interfaces contained in the routing tables, and the routing protocol parameters that control the information in the routing tables.

This statement is supported on J-series and SRX-series devices.

**Options** *routing-instance-name*—Name of the routing instance.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** access—To view this statement in the configuration.  
access-control—To add this statement to the configuration.

**routing-instance (RADIUS)**

<b>Syntax</b>	<code>routing-instance routing-instance-name;</code>
<b>Hierarchy Level</b>	[edit access radius-server <i>server-address</i> ], [edit access profile <i>profile-name</i> radius-server <i>server-address</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the routing instance used to send RADIUS packets to the RADIUS server. A routing instance is a collection of routing tables, the interfaces contained in the routing tables, and the routing protocol parameters that control the information in the routing tables.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>routing-instance-name</i> —Name of the routing instance.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

**search**

---

<b>Syntax</b>	<pre>search {   admin-search {     distinguished-name <i>distinguished-name</i>;     password <i>password</i>;   }   search-filter <i>filter-name</i>; }</pre>
<b>Hierarchy Level</b>	[edit access ldap-options], [edit access profile <i>profile-name</i> ldap-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that a search is used to get a user's LDAP distinguished name (DN). The search is performed based on the search filter and the part typed in by the user during authentication.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## search-filter

---

<b>Syntax</b>	search-filter <i>filter-name</i> ;
<b>Hierarchy Level</b>	[edit access ldap-options search], [edit access profile <i>profile-name</i> ldap-options search]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that a search filter is used to find the user's LDAP distinguished name (DN). For example, a filter of <i>cn</i> specifies that the search matches a user whose common name is the username.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>filter-name</i> —Name of the filter used to find the user's distinguished name.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## secret

---

<b>Syntax</b>	secret <i>password</i> ;
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> radius-server <i>server-address</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the RADIUS secret password, which is shared between the router and the RADIUS server. The device uses this secret to encrypt the user's password that is sent to the RADIUS server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>password</i> —RADIUS secret. Maximum length is 256 characters.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## securid-server

---

**Syntax** securid-server {  
     server-name configuration-file *filepath*;  
 }

**Hierarchy Level** [edit access]

**Release Information** Statement introduced in Release 9.1 of JUNOS software.

**Description** Configure SecurID server for SecurID authentication type.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statement is explained separately.



**NOTE:** You can configure only one SecurID server. SecurID challenges are not supported for this release.

---

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** access—To view this statement in the configuration.  
 access-control—To add this statement to the configuration.

## separator

---

<b>Syntax</b>	<code>separator <i>special-character</i>;</code>
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> client-name-filter <i>client-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a character to identify where stripping of characters occurs in a client name. Stripping removes characters to the right of each instance of the specified character, plus the character itself. The stripping begins with the rightmost separator character.</p> <p>Use the <b>separator</b> statement with the <b>count</b> statement to determine which characters in a client name are stripped. If the specified number of separator characters (count) exceeds the actual number of separator characters in the client name, stripping stops at the last available separator character.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>special-character</i> —Character used to identify where to start the stripping of characters in a client name.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.



## session-options

---

<b>Syntax</b>	<pre>session-options {   client-group [group-names];   client-idle-timeout minutes;   client-session-timeout minutes; }</pre>
<b>Hierarchy Level</b>	[edit access profile <i>profile-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define options that control a user's session after successful authentication.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>access—To view this statement in the configuration.</p> <p>access-control—To add this statement to the configuration.</p>

## source-address

---

See the following sections:

- source-address (LDAP) on page 38
- source-address (RADIUS) on page 38

### source-address (LDAP)

<b>Syntax</b>	source-address <i>source-address</i> ;
<b>Hierarchy Level</b>	[edit access ldap-server <i>server-address</i> ], [edit access profile <i>profile-name</i> ldap-server <i>server-address</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure a source address for each configured LDAP server. Each LDAP request sent to a LDAP server uses the specified source address.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>source-address</i> —Valid IPv4 address configured on one of the device interfaces.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

### source-address (RADIUS)

<b>Syntax</b>	source-address <i>source-address</i> ;
<b>Hierarchy Level</b>	[edit access radius-server <i>server-address</i> ], [edit access profile <i>profile-name</i> radius-server <i>server-address</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Configure a source address for each configured RADIUS server. Each RADIUS request sent to a RADIUS server uses the specified source address.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>source-address</i> —Valid IPv4 address configured on one of the device interfaces.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## success

---

<b>Syntax</b>	<code>success <i>string</i>;</code>
<b>Hierarchy Level</b>	[edit access firewall-authentication pass-through default-profile <i>name</i> (ftp   http   telnet) banner], [edit access firewall-authentication web-authentication]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the banner (message) that users see when trying to connect using FTP, HTTP, or Telnet after successful authentication.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>string</i> —Banner text. Maximum length of the message text is 250 characters. Enclose the banner text within spaces or special characters—for example, quotation marks (" ").
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

## telnet

---

**Syntax**   telnet {  
              banner {  
                fail *string*;  
                login *string*;  
                success *string*;  
              }  
            }

**Hierarchy Level**   [edit access firewall-authentication pass-through]

**Release Information**   Statement introduced in Release 8.5 of JUNOS software.

**Description**   Configure banners for Telnet login prompt, successful authentication, and failed authentication.

This statement is supported on J-series and SRX-series devices.

**Options**   The remaining statements are explained separately.

**Usage Guidelines**   For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**   access—To view this statement in the configuration.  
                              access-control—To add this statement to the configuration.

**timeout**

---

See the following sections:

- timeout (LDAP Server) on page 41
- timeout (RADIUS Server) on page 42

***timeout (LDAP Server)***

<b>Syntax</b>	timeout <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit access ldap-server <i>server-address</i> ] [edit access profile <i>profile-name</i> ldap-server <i>server-address</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the amount of time that the local device waits to receive a response from an LDAP server.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>seconds</i> —Amount of time to wait. <b>Range:</b> 1 through 90 seconds <b>Default:</b> 3 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	access—To view this statement in the configuration. access-control—To add this statement to the configuration.

**timeout (RADIUS Server)**

<b>Syntax</b>	timeout <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit access radius-server <i>server-address</i> ] [edit access profile <i>profile-name</i> radius-server <i>server-address</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the amount of time that the local device waits to receive a response from a RADIUS server.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>seconds</i>—Amount of time to wait.</p> <p><b>Range:</b> 1 through 90 seconds</p> <p><b>Default:</b> 3 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	secret—To view this statement in the configuration. secret-control—To add this statement to the configuration.

## traceoptions

---

**Syntax** traceoptions {  
     file *filename* {  
         files *number*;  
         match *regular-expression*;  
         size *maximum-file-size*;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag*;  
 }

**Hierarchy Level** [edit access firewall-authentication]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Define Routing Engine firewall authentication tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename*—Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory */var/log*.

files *number*—(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file.0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression*—(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size*—(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file.0*. When the *trace-file* again reaches its maximum size, *trace-file.0* is renamed *trace-file.1* and *trace-file* is renamed *trace-file.0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option

enables any user to read the file. To explicitly set the default behavior, use the `no-world-readable` option.

**flag *flag***—Tracing operation to perform. To specify more than one tracing operation, include multiple flag statements. You can include the following flags.

- **all**—All tracing operations
- **authentication**—Trace authentication events
- **configuration**—Trace configuration events
- **setup**—Trace setup of firewall authentication service

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `trace`—To view this statement in the configuration.  
`trace-control`—To add this statement to the configuration.

## web-authentication

---

**Syntax** `web-authentication {  
     banner {  
         success string;  
     }  
     default-profile default-profile;  
 }`

**Hierarchy Level** [edit access firewall-authentication]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify that users go through the Web authentication process. Users use HTTP to access an IP address on the **device** that is enabled for Web authentication. Users do not use HTTP to access the IP address of the protected resource in this case. Users are prompted for their username and password, which are verified by the device. Subsequent traffic from the user/host to the protected resource is allowed or denied based on the result of this authentication. This method of authentication differs from pass-through authentication in that users need to access the protected resource directly after accessing the Web authentication IP address and being authenticated.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `access`—To view this statement in the configuration.  
`access-control`—To add this statement to the configuration.



## Chapter 2

# Accounting-Options Hierarchy

This chapter presents the complete **accounting-options** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **accounting-options** configuration hierarchy to collect and log data about basic system operations and services on the device. For configuration instructions, see the *JUNOS Software Administration Guide*.

For information about these **accounting-options** statements that are shared across Juniper Networks devices, see the *JUNOS Network Management Configuration Guide*.

This chapter contains the following sections:

- Accounting-Options Configuration Statement Hierarchy on page 45

## Accounting-Options Configuration Statement Hierarchy

---

To configure accounting options, use the following statements at the [edit **accounting-options**] hierarchy level.

Shared JUNOS statements in the **accounting-options** hierarchy are shown in normal font and are documented in the *JUNOS Network Management Configuration Guide*.

```
accounting-options {
  class-usage-profile profile-name {
    destination-classes {
      destination-class-name ;
    }
    file filename ;
    interval minutes ;
    source-classes {
      source-class-name ;
    }
  }
  file filename {
    archive-sites {
      site-name ;
    }
    files file-number ;
    nonpersistent;
    size bytes ;
    start-time time ;
    transfer-interval minutes ;
  }
}
```

```

}
filter-profile profile-name {
    counters {
        counter name ;
    }
    file filename ;
    interval minutes ;
}
interface-profile profile-name {
    fields {
        field-name ;
    }
    file filename ;
    interval minutes ;
}
mib-profile profile-name {
    file filename ;
    interval minutes ;
    object-names {
        mib-object-name ;
    }
    operation operation-name ;
}
routing-engine-profile profile-name {
    fields {
        field-name ;
    }
    file filename ;
    interval minutes ;
}
}

```

## Chapter 3

# Applications Hierarchy and Statements

This chapter presents the complete **applications** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **applications** configuration hierarchy to configure applications functions of J-series and SRX-series devices and their properties on the device. For configuration instructions, see the *JUNOS Software Security Configuration Guide*.

For information about **applications** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS Services Interfaces Configuration Guide*.

This chapter contains the following sections:

- Applications Configuration Statement Hierarchy on page 47

## Applications Configuration Statement Hierarchy

---

To configure applications properties and to group application objects, use the following statements at the [edit **applications**] hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **applications** hierarchy are shown in normal font and are documented in the *JUNOS Services Interfaces Configuration Guide*.

```
applications {  
  application application-name {  
    application-protocol protocol-name;  
    destination-port port-number;  
    icmp-code value ;  
    icmp-type value ;  
    inactivity-timeout seconds ;  
    protocol type;  
    rpc-program-number number ;  
    source-port port-number;  
    term term-name {  
      alg application;  
      destination-port port-number;
```

```
    icmp-code value;  
    icmp-type value;  
    inactivity-timeout seconds;  
    protocol type;  
    rpc-program-number number;  
    source-port port-number;  
    uuid hex-value;  
  }  
  uuid hex-value;  
}  
application-set application-set-name {  
  [application application-name ];  
}  
}
```

**alg**


---

<b>Syntax</b>	<code>alg application ;</code>
<b>Hierarchy Level</b>	[edit applications application <i>application-name</i> term <i>term-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define individual Application Layer Gateway (ALG).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>application</i> —Name of the application. The following protocols are supported:</p> <ul style="list-style-type: none"> <li>■ <code>dns</code>—Domain Name Service</li> <li>■ <code>ftp</code>—File Transfer Protocol</li> <li>■ <code>ignore</code>—Ignore application type</li> <li>■ <code>mgcp-ca</code>—Media Gateway Control Protocol with Call Agent</li> <li>■ <code>mgcp-ua</code>—MGCP with User Agent</li> <li>■ <code>ms-rpc</code>—Microsoft RPC</li> <li>■ <code>pptp</code>—Point-to-Point Tunneling Protocol</li> <li>■ <code>q931</code>—ISDN connection control protocol (Q.931)</li> <li>■ <code>ras</code>—Remote Access Service</li> <li>■ <code>realaudio</code>—RealAudio</li> <li>■ <code>rsh</code>—UNIX remote shell services</li> <li>■ <code>rtsp</code>—Real-Time Streaming Protocol</li> <li>■ <code>sccp</code>—Skinny Client Control Protocol</li> <li>■ <code>sip</code>—Session Initiation Protocol</li> <li>■ <code>sqlnet-v2</code>—Oracle SQLNET v2</li> <li>■ <code>sun-rpc</code>—Sun Microsystems RPC</li> <li>■ <code>talk</code>—TALK program</li> <li>■ <code>tftp</code>—Trivial File Transfer Protocol</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>

## application-protocol

---

<b>Syntax</b>	<code>application-protocol protocol-name ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application application-name ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Identify the application protocol name.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>protocol-name</i> —Name of the protocol. The following protocols are supported:</p> <ul style="list-style-type: none"> <li>■ <code>dns</code>—Domain Name Service</li> <li>■ <code>ftp</code>—File Transfer Protocol</li> <li>■ <code>ignore</code>—Ignore application type</li> <li>■ <code>mgcp-ca</code>—Media Gateway Control Protocol with Call Agent</li> <li>■ <code>mgcp-ua</code>—MGCP with User Agent</li> <li>■ <code>ms-rpc</code>—Microsoft RPC</li> <li>■ <code>pptp</code>—Point-to-Point Tunneling Protocol</li> <li>■ <code>q931</code>—ISDN connection control protocol (Q.931)</li> <li>■ <code>ras</code>—Remote Access Service</li> <li>■ <code>realaudio</code>—RealAudio</li> <li>■ <code>rsh</code>—UNIX remote shell services</li> <li>■ <code>rtsp</code>—Real-Time Streaming Protocol</li> <li>■ <code>sccp</code>—Skinny Client Control Protocol</li> <li>■ <code>sip</code>—Session Initiation Protocol</li> <li>■ <code>sqlnet-v2</code>—Oracle SQLNET v2</li> <li>■ <code>sun-rpc</code>—Sun Microsystems RPC</li> <li>■ <code>talk</code>—TALK program</li> <li>■ <code>tftp</code>—Trivial File Transfer Protocol</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>

## destination-port

---

<b>Syntax</b>	<code>destination-port <i>port-number</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application <i>application-name</i> ],</code> <code>[edit applications application <i>application-name</i> term <i>term-name</i> ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) destination port number.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>port-number</i> —Range of ports. You can use a numeric value or one of the text synonyms listed in Table 4 on page 52.

**Table 4: Port Names Supported by Services Interfaces**

Port Name	Corresponding Port Number
afs	1483
bgp	179
biff	512
bootpc	68
bootps	67
cmd	514
cvspserver	2401
dhcp	67
domain	53
eklogin	2105
ekshell	2106
excc	512
finger	79
ftp	21
ftp-data	20
http	80
https	443
ident	113
imap	143
kerberos-sec	88
klogin	543
kpasswd	761
krb-prop	754
krbupdate	760
kshell	544
ldap	389
ldp	646



**Table 4: Port Names Supported by Services Interfaces** *(continued)*

Port Name	Corresponding Port Number
login	513
mobileip-agent	434
mobileip-mn	435
msdp	639
netbios-dgm	138
netbios-ns	137
netbios-ssn	139
nfsd	2049
nntp	119
ntalk	518
ntp	123
pop3	110
pptp	1723
printer	515
radacct	1813
radius	1812
rip	520
rkinit	2108
smtp	25
snmp	161
snmp-trap	162
snpp	444
socks	1080
ssh	22
sunrpc	111
syslog	514
tacacs	49

**Table 4: Port Names Supported by Services Interfaces** *(continued)*

Port Name	Corresponding Port Number
tacacs-ds	65
talk	517
telnet	23
tftp	69
timed	525
who	513
xmcp	177

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** system—To view this statement in the configuration.  
system-control—To add this statement to the configuration.

## icmp-code

**Syntax** `icmp-code value ;`

**Hierarchy Level** [edit applications application *application-name* term *term-name* ]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Specify the Internet Control Message Protocol (ICMP) code value.

This statement is supported on J-series and SRX-series devices.

**Options** *value* —ICMP code value, such as `host-unreachable` or `host-unreachable-for-tos`.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** system—To view this statement in the configuration.  
system-control—To add this statement to the configuration.

## icmp-type

---

<b>Syntax</b>	<code>icmp-type value ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application <i>application-name</i> term <i>term-name</i> ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the ICMP packet type value.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>value</i> —ICMP type value, such as <code>echo</code> or <code>echo-reply</code> .
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## inactivity-timeout

---

<b>Syntax</b>	<code>inactivity-timeout seconds ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application <i>application-name</i> term <i>term-name</i> ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Inactivity timeout period, in seconds.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>seconds</i> —Length of time the application is inactive before it times out. <b>Default:</b> 60 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## protocol

---

**Syntax**    protocol type ;

**Hierarchy Level**    [edit applications application *application-name* ],  
[edit applications application *application-name* term *term-name* ]

**Release Information**    Statement modified in Release 8.5 of JUNOS software.

**Description**    Specify the networking protocol name or number.

This statement is supported on J-series and SRX-series devices.

**Options**    *protocol-name* —Networking protocol name. The following text values are supported. For a complete list of possible numeric values, see RFC 1700, *Assigned Numbers (for the Internet Protocol Suite)*.

- ah—IP Security Authentication Header
- egp—Exterior gateway protocol
- esp—IPsec Encapsulating Security Payload
- gre—Generic routing encapsulation
- icmp—Internet Control Message Protocol
- igmp—Internet Group Management Protocol
- ipip—IP over IP
- node—Clear each session that uses the specified IP protocol on a specific node.
- ospf—Open Shortest Path First
- pim—Protocol Independent Multicast
- rsvp—Resource Reservation Protocol
- sctp—Stream Control Transmission Protocol
- tcp—Transmission Control Protocol
- udp—User Datagram Protocol



**NOTE:** Internet Protocol version 6 (IPv6) is not supported as a network protocol in application definitions

---

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    system—To view this statement in the configuration.  
system-control—To add this statement to the configuration.

## rpc-program-number

---

<b>Syntax</b>	<code>rpc-program-number number ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application application-name term term-name ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the remote procedure call (RPC) or Distributed Computing Environment (DCE) value.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —RPC or DCE program value. <b>Range:</b> 0 through 65535
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## source-port

---

<b>Syntax</b>	<code>source-port port-number ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application application-name ],</code> <code>[edit applications application application-name term term-name ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the source port identifier.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>port-number</i> —Identifier for the port. You can use a numeric value or one of the text synonyms listed in Table 4 on page 52.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## term

---

**Syntax**    `term term-name {  
               alg application ;  
               destination-port port-number ;  
               icmp-code value ;  
               icmp-type value ;  
               inactivity-timeout seconds ;  
               protocol type ;  
               rpc-program-number number ;  
               source-port port-number ;  
               uuid hex-value ;  
               }`

**Hierarchy Level**    [edit applications application *application-name* ]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Define individual application protocols.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    system—To view this statement in the configuration.  
                                   system-control—To add this statement to the configuration.

**uuid**

---

<b>Syntax</b>	<code>uuid <i>hex-value</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit applications application <i>application-name</i> term <i>term-name</i> ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the Universal Unique Identifier (UUID) for objects. DCE RPC services are mainly used by Microsoft applications. The ALG uses well-known TCP port 135 for port mapping services and uses the Universal Unique Identifier (UUID) instead of the program number to identify protocols. The main application-based DCE RPC is the Microsoft Exchange Protocol.</p> <p>Support for stateful firewall and NAT services requires that you configure the DCE RPC portmap ALG on TCP port 135. The DCE RPC ALG uses the TCP protocol with application-specific UUIDs.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>hex-value</i> —Hexadecimal value.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>





## Chapter 4

# Chassis Hierarchy and Statements

This chapter presents the complete **chassis** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **chassis** configuration hierarchy to configure alarms and other chassis properties and to configure chassis clusters. For configuration instructions, see the *JUNOS Software with Enhanced Services Hardware Guide* and the *JUNOS Software Administration Guide*. To configure chassis clusters, see the *JUNOS Software Security Configuration Guide*.

For information about chassis statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS System Basics Configuration Guide*.

This chapter contains the following sections:

- Chassis Configuration Statement Hierarchy on page 61

## Chassis Configuration Statement Hierarchy

---

To configure chassis properties, use the following statements at the **[edit chassis]** hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **chassis** hierarchy are shown in normal font and are documented in the *JUNOS System Basics Configuration Guide*.

```
chassis {  
  alarm {  
    ds1 {  
      ais (ignore | red | yellow);  
      ylw (ignore | red | yellow);  
    }  
    ethernet {  
      link-down (ignore | red | yellow);  
    }  
    integrated-services {  
      failure (ignore | red | yellow);  
    }  
    management-ethernet {
```

```

    link-down (ignore | red | yellow);
}
serial {
    cts-absent (ignore | red | yellow);
    dcd-absent (ignore | red | yellow);
    dsr-absent (ignore | red | yellow);
    loss-of-rx-clock (ignore | red | yellow);
    loss-of-tx-clock (ignore | red | yellow);
}
services {
    hw-down (ignore | red | yellow);
    linkdown (ignore | red | yellow);
    pic-hold-reset (ignore | red | yellow);
    pic-reset (ignore | red | yellow);
    rx-errors (ignore | red | yellow);
    sw-down (ignore | red | yellow);
    tx-errors (ignore | red | yellow);
}
sonet {
    alarm-name (ignore | red | yellow);
}
t3 {
    ais (ignore | red | yellow);
    exz (ignore | red | yellow);
    ferf (ignore | red | yellow);
    idle (ignore | red | yellow);
    lcv (ignore | red | yellow);
    lof (ignore | red | yellow);
    los (ignore | red | yellow);
    pll (ignore | red | yellow);
    ylw (ignore | red | yellow);
}
}
cluster {
    control-ports {
        fpc slot-numberport port-number;
    }
    heartbeat-interval milliseconds;
    heartbeat-threshold number;
    node node-number;
    redundancy-group group-number {
        gratuitous-arp-count number;
        interface-monitor interface-name {
            weight number;
        }
        node node-number {
            priority priority-number;
        }
    }
    preempt;
}
reth-count number;
traceoptions {
    file filename {
        <files number>;
        <match regular-expression>;
        <size maximum-file-size>;
    }
}

```

```

    <world-readable | no-world-readable>;
  }
  flag {
    all;
    configuration;
    routing-socket;
  }
}
config-button {
  no-clear;
  no-rescue;
}
container-devices {
  device-count container-devices-number ;
}
craft-lockout;
disable-power-management;
fpc slot-number {
  offline;
  pic pic-number {
    aggregate-ports;
    atm-cell-relay-accumulation;
    atm-l2circuit-mode (cell | aal5 | trunk trunk );
    ce1 {
      e1 port-number {
        channel-group group-number timeslots slot-number ;
      }
    }
    ct3 {
      port port-number {
        t1 link-number {
          channel-group group-number timeslots slot-number ;
        }
      }
    }
  }
  ethernet {
    pic-mode (enhanced-switching | routing | switching);
  }
  framing (sdh | sonet);
  idle-cell-format {
    itu-t;
    payload-pattern payload-pattern-byte ;
  }
  max-queues-per-interface (4 | 8);
  mlfr-uni-nni-bundles number ;
  no-concatenate;
  q-pic-large-buffer <(large-scale | small-scale)>;
  red-buffer-occupancy {
    weighted-averaged [ instant-usage-weight-exponent weight-value ];
  }
  shdsl {
    pic-mode (1-port-atm | 2-port-atm);
  }
  sparse-dlcis;
  traffic-manager {

```

```

        egress-shaping-overhead number ;
        ingress-shaping-overhead number ;
        mode ( egress-only | ingress-and-egress );
    }
    tunnel-queuing;
    tunnel-services {
        bandwidth (1g | 10g);
    }
    vtmapping (itu-t | klm);
}
power (off | on);
}
pem {
    minimum number ;
}
redundancy {
    failover {
        on-disk-failure;
        on-loss-of-keepalives;
    }
    graceful-switchover;
    keepalive-time seconds ;
    routing-engine slot-number (backup | disabled | master);
}
routing-engine {
    on-disk-failure disk-failure-action (halt | reboot);
}
}

```

## cluster

---

```

Syntax cluster {
    control-ports {
        fpc slot-number port port-number ;
    }
    heartbeat-interval milliseconds ;
    heartbeat-threshold number ;
    node node-number ;
    redundancy-group group-number {
        gratuitous-arp-count number ;
        interface-monitor interface-name {
            weight number ;
        }
        node node-number {
            priority priority-number ;
        }
    }
    preempt;
}
reth-count number ;
traceoptions {
    file filename {
        <files number >;
        <match regular-expression> ;
        <size maximum-file-size >;
        <world-readable | no-world-readable>;
    }
    flag {
        all;
        configuration;
        routing-socket;
    }
}
}

```

**Hierarchy Level** [edit chassis]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Configure a chassis cluster.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** interface—To view this statement in the configuration.  
 interface-control—To add this statement to the configuration.

## control-ports

---

**Syntax**     control-ports {  
                   fpc *slot-number* port *port-number* ;  
                   }

**Hierarchy Level**     [edit chassis cluster]

**Release Information**     Statement introduced in Release 9.2 of JUNOS software.

**Description**     Specific to SRX-series services gateway. Enable the specific control port of the Services Processing Card (SPC) for use as a control link for the chassis cluster. By default, all control ports are disabled. User needs to configure a minimum of one control port per chassis of the cluster.

This statement is supported on SRX-series devices.

**Options**     fpc *slot-number* —Flexible PIC Concentrator (FPC) slot number



**NOTE:** FPC slot range depends on platform. The maximum range of 0 through 23 applies to SRX 5800 services gateway; for SRX 5600 services gateway, the only applicable range is 0 through 11.

---

port *port-number* —Port number on which to configure the control port.

**Usage Guidelines**     For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**     interface—To view this statement in the configuration.  
    interface-control—To add this statement to the configuration.

## gratuitous-arp-count

---

<b>Syntax</b>	gratuitous-arp-count number;
<b>Hierarchy Level</b>	[edit chassis cluster redundancy-group group-number]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Specify the number of gratuitous Address Resolution Protocol (ARP) requests to send on an active interface after failover.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Number of gratuitous ARP requests that a newly elected primary device in a chassis cluster sends out to announce its presence to the other network devices. <b>Range:</b> 1 through 16 <b>Default:</b> 4
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## heartbeat-interval

---

<b>Syntax</b>	heartbeat-interval <i>milliseconds</i> ;
<b>Hierarchy Level</b>	[edit chassis cluster]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Set the interval between the periodic signals broadcast to the devices in a chassis cluster to indicate that the active node is operational.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>milliseconds</i> —Time interval between any two heartbeat messages. <b>Range:</b> 1000 through 2000 milliseconds <b>Default:</b> 1000 milliseconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## heartbeat-threshold

---

<b>Syntax</b>	heartbeat-threshold <i>number</i> ;
<b>Hierarchy Level</b>	[edit chassis cluster]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Set the number of consecutive missed heartbeat signals that a device in a chassis cluster must exceed to trigger failover of the active node.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>number</i> —Number of consecutive missed heartbeats.</p> <p><b>Range:</b> 3 through 8</p> <p><b>Default:</b> 3</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>

## interface-monitor

---

<b>Syntax</b>	<pre>interface-monitor interface-name {     weight number ; }</pre>
<b>Hierarchy Level</b>	[edit chassis cluster redundancy-group <i>group-number</i> ]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Specify a redundancy group interface to be monitored for failover and the relative weight of the interface.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>interface-name</i> —Name of the physical interface to monitor.</p> <p>The remaining statement is explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>



## node

---

See the following sections:

- `node (Cluster)` on page 69
- `node (Redundancy-Group)` on page 70

### ***node (Cluster)***

**Syntax** `node node-number ;`

**Hierarchy Level** [edit chassis cluster]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Identify the device in a chassis cluster. The node 0 device in the cluster has the chassis ID 1, and the node 1 device in the cluster has the chassis ID 2.

This statement is supported on J-series and SRX-series devices.

**Options** `node-number` —Cluster node number.

**Range:** 0 through 1

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**node (Redundancy-Group)**

**Syntax**    node *node-number* {  
                       priority *priority-number* ;  
                       }

**Hierarchy Level**    [edit chassis cluster redundancy-group *group-number* ]

**Release Information**    Statement introduced in Release 9.0 of JUNOS software.

**Description**    Identify each cluster node in a redundancy group and set its relative priority for mastership.

This statement is supported on J-series and SRX-series devices.

**Options**    *node-number* —Cluster node number, set with the chassis cluster node *node-number* statement.

The remaining statement is explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    interface—To view this statement in the configuration.  
                                   interface-control—To add this statement to the configuration.

## pic-mode

---

**Syntax** `pic-mode (enhanced-switching | routing | switching);`

**Hierarchy Level** `[edit chassis fpc slot-number pic pic-number ethernet]`

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Set the mode to configure the uPIMs.

This statement is supported on J-series devices.

**Options** `enhanced-switching`—Enhanced switching mode of operation. Each port of the uPIMs can be configured for switching or routing mode.



**NOTE:** Only one `enhanced-switching` mode uPIM per chassis is supported currently.

---

`routing`—Routing mode of operation. All ports of the uPIMs are in routing mode. Routing mode is the default setting.

`switching`—Switching mode of operation. All ports of the uPIMs are in switching mode.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

**Required Privilege Level** `interface`—To view this statement in the configuration.  
`interface-control`—To add this statement to the configuration.

## preempt

---

<b>Syntax</b>	<code>preempt;</code>
<b>Hierarchy Level</b>	<code>[edit chassis cluster redundancy-group <i>group-number</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Enable chassis cluster node preemption within a redundancy group. If <b>preempt</b> is added to a redundancy group configuration, the device with the higher priority in the group can initiate a failover to become master. By default, preemption is disabled.</p> <p>Initiating a failover with the <code>request chassis cluster failover node</code> or <code>request chassis cluster failover redundancy-group</code> command overrides the priority settings and preemption.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>

## priority

---

<b>Syntax</b>	<code>priority <i>priority-number</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit chassis cluster redundancy-group <i>group-number</i> node <i>node-number</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Define the priority of a node (device) in a redundancy group. Initiating a failover with the <code>request chassis cluster failover node</code> or <code>request chassis cluster failover redundancy-group</code> command overrides the priority settings.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>priority-number</i> —Priority value of the node. The eligible node with the highest priority is elected master.</p> <p><b>Range:</b> 1 through 254</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>

## redundancy-group

---

**Syntax** `redundancy-group group-number {  
     gratuitous-arp-count number ;  
     interface-monitor interface {  
         weight number ;  
     }  
     node node-number {  
         priority priority-number ;  
     }  
     preempt;  
}`

**Hierarchy Level** [edit chassis cluster]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Define a redundancy group. Except for redundancy group 0, a redundancy group is a logical interface consisting of two physical Ethernet interfaces, one on each chassis. One interface is active, and the other is on standby. When the active interface fails, the standby interface becomes active. The logical interface is called a redundant Ethernet (reth) interface.

Redundancy group 0 consists of the two Routing Engines in the chassis cluster and controls Routing Engine primaryship. You must define redundancy group 0 in the chassis cluster configuration.

This statement is supported on J-series and SRX-series devices.

**Options** `group-number` —Redundancy group identification number.  
**Range:** 0 through 255

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** interface—To view this statement in the configuration.  
 interface-control—To add this statement to the configuration.

## reth-count

---

<b>Syntax</b>	<code>reth-count <i>number</i> ;</code>
<b>Hierarchy Level</b>	[edit chassis cluster]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Specify the number of redundant Ethernet (<b>reth</b>) interfaces allowed in the chassis cluster.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>number</i> —Number of redundant Ethernet interfaces allowed.</p> <p><b>Range:</b> 1 through 128</p> <p><b>Default:</b> 0</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## traceoptions

---

**Syntax**

```

traceoptions {
  file filename {
    <files number >;
    <match regular-expression >;
    <size maximum-file-size >;
    <world-readable | no-world-readable>;
  }
  flag {
    all;
    configuration;
    routing-socket;
  }
}

```

**Hierarchy Level** [edit chassis cluster]

**Release Information** Statement modified in Release 9.0 of JUNOS software.

**Description** Define chassis cluster redundancy process tracing operations.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename* —Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory */var/log*.

files *number* —(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 0 KB through 1 GB

**Default:** 128 KB

**world-readable | no-world-readable**—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The **world-readable** option enables any user to read the file. To explicitly set the default behavior, use the **no-world-readable** option.

**flag**—Trace operation or operations to perform on chassis cluster redundancy processes. To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace all the events
  - **configuration**—Trace configuration events
  - **routing-socket**—Trace logging of rtsock activity

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **trace**—To view this statement in the configuration.  
**trace-control**—To add this statement to the configuration.

## tunnel-queuing

---

**Syntax** tunnel-queuing;

**Hierarchy Level** [edit chassis fpc *slot-number* pic *pic-number* ]

**Release Information** Statement modified in Release 9.0 of JUNOS software.

**Description** Enable class-of-service (CoS) queuing for generic routing encapsulation (GRE) and IP-IP tunnels.

This statement is supported on J-series devices.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

**Required Privilege Level** **interface**—To view this statement in the configuration.  
**interface-control**—To add this statement to the configuration.



## weight

---

<b>Syntax</b>	<code>weight number ;</code>
<b>Hierarchy Level</b>	<code>[edit chassis cluster redundancy-group group-number interface-monitor interface ]</code>
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Specify the relative importance of the interface to the operation of the redundancy group. The failure of an interface with a greater weight brings the group closer to failover. Every monitored interface is assigned a weight. If an interface fails, the weight of the interface is deducted from the threshold of its redundancy group. Every redundancy group has a threshold of 255. If the threshold reaches 0, a failover is triggered. Failover is triggered even if the redundancy group is in manual failover mode and preemption is not enabled.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>number</i> —Weight assigned to the interface. A higher weight value indicates a greater importance.</p> <p><b>Range:</b> 0 through 255</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>



## Chapter 5

# Class-of-Service Hierarchy

This chapter presents the complete **class-of-service** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **class-of-service** configuration hierarchy to configure class-of-services (CoS) features. For configuration instructions, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

For information about these **class-of-service** statements that are shared across Juniper Networks devices, see the *JUNOS Class of Service Configuration Guide*.

This chapter contains the following sections:

- Class-of-Service Configuration Statement Hierarchy on page 79

## Class-of-Service Configuration Statement Hierarchy

---

To configure CoS, use the following statements at the [edit **class-of-service**] hierarchy level.

Shared JUNOS statements in the **class-of-service** hierarchy are shown in normal font and are documented in the *JUNOS Class of Service Configuration Guide*.

```
class-of-service {
  adaptive-shapers {
    adaptive-shaper-name {
      trigger type shaping-rate (percent percent | rate );
    }
  }
  classifiers {
    type classifier-name {
      forwarding-class class-name {
        loss-priority (low | high) code-points [ alias | bits ];
      }
      import ( classifier-name | default);
    }
  }
  code-point-aliases {
    (dscp | dscp-ipv6 | exp | ieee-802.1 | inet-precedence) {
      alias-name bits ;
    }
  }
  drop-profiles {
```

```

    profile-name {
        fill-level percentage drop-probability percentage ;
        interpolate {
            drop-probability value ;
            fill-level value ;
        }
    }
}
forwarding-classes {
    queue queue-number class-name priority (low | high);
}
forwarding-policy {
    class class-name {
        classification-override {
            forwarding-class class-name ;
        }
    }
    next-hop-map map-name {
        forwarding-class class-name {
            lsp-next-hop [ lsp-regular-expression ];
            next-hop [ next-hop-name ];
            non-lsp-next-hop [ lsp-regular-expression ];
        }
    }
}
fragmentation-maps {
    map-name {
        forwarding-class class-name {
            drop-timeout milliseconds ;
            fragment-threshold bytes ;
            multilink-class number ;
            no-fragmentation;
        }
    }
}
host-outbound-traffic {
    dscp-code-point value ;
    forwarding-class class-name ;
}
interfaces {
    interface-name {
        input-scheduler-map map-name ;
        input-shaping-rate rate ;
        scheduler-map map-name ;
        scheduler-map-chassis map-name ;
        shaping-rate rate ;
        unit logical-unit-number {
            adaptive-shaper adaptive-shaper-name ;
            classifiers {
                (dscp | dscp-ipv6 | exp | ieee-802.1 | inet-precedence)
                ( classifier-name | default);
            }
            forwarding-class class-name ;
            fragmentation-map map-name ;
            input-scheduler-map map-name ;
            input-shaping-rate (percent percentage | rate );
        }
    }
}

```

```

input-traffic-control-profile profiler-name shared-instance instance-name
;
loss-priority-maps {
    default;
    map-name ;
}
output-traffic-control-profile profile-name shared-instance instance-name
;
rewrite-rules {
    dscp ( rewrite-name | default);
    dscp-ipv6 ( rewrite-name | default);
    exp ( rewrite-name | default) protocol protocol-types ;
    frame-relay-de ( rewrite-name | default);
    ieee-802.1 ( rewrite-name | default) vlan-tag (outer | outer-and-inner);
    ieee-802.1ad ( rewrite-name | default) vlan-tag (outer | outer-and-inner);
    inet-precedence ( rewrite-name | default);
}
scheduler-map map-name ;
shaping-rate rate ;
virtual-channel-group group-name ;
}
}
}
loss-priority-maps {
    frame-relay-de ( map-name | default) {
        loss-priority level code-points [ values ];
    }
}
rewrite-rules {
    type rewrite-name {
        forwarding-class class-name {
            loss-priority level code-point [ aliases ] [ 6-bit-patterns ];
        }
        import ( rewrite-name | default);
    }
}
scheduler-maps {
    map-name {
        forwarding-class class-name scheduler scheduler-name ;
    }
}
schedulers {
    scheduler-name {
        buffer-size (percent percentage | remainder | temporal microseconds );
        drop-profile-map {
            loss-priority (any | high | low | medium-high | medium-low);
            protocol (any | non-tcp | tcp);
        }
        priority (high | low | medium-high | medium-low | strict-high);
        shaping-rate (percent percentage | rate );
        transmit-rate (percent percentage | rate | remainder) <exact | rate-limit>;
    }
}
traceoptions {
    flag flag {
        all;
    }
}

```

```

    asynch;
    hardware-database;
    init;
    parse;
    process;
    restart;
    route-socket;
    show;
    snmp;
    util;
  }
}
traffic-control-profiles profile-name {
  delay-buffer-rate (percent percent | rate );
  guaranteed-rate (percent percent | rate );
  scheduler-map map-name ;
  shaping-rate (percent percent | rate );
}
virtual-channel-groups {
  virtual-channel-group-name {
    virtual-channel-name {
      default;
      scheduler-map map-name ;
      shaping-rate (percent percent | rate );
    }
  }
}
virtual-channels {
  virtual-channel-name ;
}
}

```

## Chapter 6

# Event-Options Hierarchy

This chapter presents the complete **event-options** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **event-options** configuration hierarchy to configure diagnostic event policies and actions associated with each policy. For configuration instructions, see the *JUNOS Software Administration Guide*.

For information about these **event-options** statements that are shared across Juniper Networks devices, see the *JUNOS Configuration and Diagnostic Automation Guide*.

This chapter contains the following sections:

- Event-Options Configuration Statement Hierarchy on page 83

## Event-Options Configuration Statement Hierarchy

---

To configure event policies, use the following statements at the [edit event-options] hierarchy level.

Shared JUNOS statements in the **event-options** hierarchy are shown in normal font and are documented in the *JUNOS Configuration and Diagnostic Automation Guide*.

```
event-options {
  destinations {
    destination-name {
      archive-sites {
        url password password ;
      }
      transfer-delay seconds ;
    }
  }
  event-script {
    file script-name ;
    traceoptions {
      file filename <files number> <size maximum-file-size>
        <world-readable | no-world-readable>;
      flag flag ;
    }
  }
  generate-event event-name {
    time-interval seconds ;
    time-of-day hh : mm : ss ;
  }
}
```

```

}
policy policy-name {
  attributes-match {
    event1 . attribute-name equals event2 . attribute-name ;
    event . attribute-name matches regular-expression ;
    event1 . attribute-name starts-with event2 . attribute-name ;
  }
  events [ events ];
  then {
    event-script script-name .xml {
      arguments {
        name value ;
      }
      destination destination-name {
        retry-count number {
          retry-interval seconds ;
        }
        transfer-delay seconds ;
      }
      output-filename filename ;
      output-format (text | xml);
      user-name user-name ;
    }
    execute-commands {
      commands {
        "command";
      }
      destination destination-name {
        retry-count number {
          retry-interval seconds ;
        }
        transfer-delay seconds ;
      }
      output-file-name filename ;
      output-format (text | xml);
      user-name user-name ;
    }
    ignore;
    raise-trap;
    upload filename committed destination destination-name ;
    upload filename filename destination destination-name ;
  }
  within seconds not events [ events ];
}
traceoptions {
  file filename <files number > <size maximum-file-size >
  <world-readable | no-world-readable>;
  flag flag ;
}
}

```



## Chapter 7

# Firewall Hierarchy

This chapter presents the complete **firewall** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **firewall** configuration hierarchy to configure stateless firewall filters—also known as access control lists (ACLs)—on the device. Stateless firewall filters allow you to filter packets based on their components and to perform an action on packets that match the filter. For configuration instructions, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

For information about these **firewall** statements that are shared across Juniper Networks devices—see the *JUNOS Policy Framework Configuration Guide*.

This chapter contains the following sections:

- Firewall Configuration Statement Hierarchy on page 85

## Firewall Configuration Statement Hierarchy

---

To configure stateless firewall filters, use the following statements at the [edit **firewall**] hierarchy level.

Shared JUNOS statements in the **firewall** hierarchy are shown in normal font and are documented in the *JUNOS Policy Framework Configuration Guide*.

```
firewall {
  family family-name {
    dialer-filter filter-name {
      accounting-profile [ profile - name s];
      term term-name {
        from {
          match-conditions ;
        }
        then {
          action
          action-modifiers ;
          policer policer-name ;
          port-mirror;
          virtual-channel virtual-channel-name ;
        }
      }
    }
  }
  filter filter-name {
```

```

    accounting-profile [ profile - name s];
    interface-specific;
    term term-name {
        filter filter-name ;
        from {
            match-conditions ;
        }
        then {
            action ;
            action-modifiers ;
            policer policer-name ;
            port-mirror;
            virtual-channel virtual-channel-name ;
        }
    }
}
service-filter filter-name {
    term term-name {
        from {
            match-conditions ;
        }
        then {
            action ;
            action-modifiers ;
        }
    }
}
simple-filter filter-name {
    interface-specific;
    term term-name {
        from {
            match-conditions ;
        }
        then {
            action ;
            action-modifiers ;
        }
    }
}
}
filter filter-name {
    accounting-profile [ profile-names ];
    interface-specific;
    term term-name {
        filter filter-name ;
        from {
            match-conditions ;
        }
        then {
            action ;
            action-modifiers ;
            virtual-channel virtual-channel-name ;
        }
    }
}
}
interface-set interface-set-name {

```

```

    [ interface-names ];
}
policer policer-name {
    filter-specific;
    if-exceeding {
        bandwidth-limit bps ;
        bandwidth-percent number ;
        burst-size-limit bytes ;
    }
    logical-bandwidth-policer;
    logical-interface-policer;
    then {
        policer-action ;
    }
}
three-color-policer policer-name {
    action {
        loss-priority high {
            then {
                discard;
            }
        }
    }
    logical-interface-policer;
    single-rate {
        (color-aware | color-blind);
        committed-burst-size bytes ;
        committed-information-rate bps ;
        excess-burst-size bytes ;
    }
    two-rate {
        (color-aware | color-blind);
        committed-information-rate bps ;
        committed-burst-size bytes ;
        peak-information-rate bps ;
        peak-burst-size bytes ;
    }
}
}

```



## Chapter 8

# Forwarding-Options Hierarchy and Statements

This chapter presents the complete **forwarding-options** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **forwarding-options** configuration hierarchy to configure forwarding options protocols, including flow monitoring, accounting properties, and packet capture. For configuration instructions, see the *JUNOS Software Administration Guide*.

For information about these **forwarding-options** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS Policy Options Configuration Guide* and the *JUNOS Services Interfaces Configuration Guide*.

This chapter contains the following sections:

- Forwarding-Options Configuration Statement Hierarchy on page 89

## Forwarding-Options Configuration Statement Hierarchy

---

To configure forwarding options, use the following statements at the **[edit forwarding-options]** hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **forwarding-options** hierarchy are shown in normal font and are documented in the *JUNOS Policy Options Configuration Guide* and the *JUNOS Services Interfaces Configuration Guide*.

```
forwarding-options {  
  accounting group-name {  
    output {  
      aggregate-export-interval value ;  
      cflowd [ hostnames ] {  
        aggregation {  
          autonomous-system;  
          destination-prefix;        }  
      }  
    }  
  }}
```

```

        protocol-port;
        source-destination-prefix {
            caida-compliant;
        }
        source-prefix;
    }
    autonomous-system-type;
    port;
    version;
}
flow-active-timeout;
flow-inactive-timeout;
interface interface-name {
    engine-id number ;
    engine-type number ;
    source-address address ;
}
}
family family-name {
    inet {
        filter (input | output);
    }
    inet6 {
        filter (input | output);
    }
    mpls {
        filter (input | output);
    }
}
hash-key {
    family {
        inet {
            layer-3;
            layer-4;
        }
        mpls {
            label-1;
            label-2;
            label-3;
            no-labels;
            payload {
                ip {
                    layer-3-only;
                    port-data {
                        destination-lsb;
                        destination-msb;
                        source-lsb;
                        source-msb;
                    }
                }
            }
        }
    }
}
helpers {
```

```

bootp {
  client-response-ttl value ;
  description text ;
  interface interface-name {
    broadcast;
    client-response-ttl number ;
    description description ;
    maximum-hop-count number ;
    minimum-wait-time seconds ;
    no-listen;
    server address ;
    vpn;
  }
  maximum-hop-count number ;
  minimum-wait-time seconds ;
  relay-agent-option;
  server address {
    routing-instance [ value ];
  }
  vpn;
}
domain {
  description text ;
  interface interface-name;
  server {
    address address ;
    routing-instance [ value ];
  }
}
port value {
  description text ;
  interface interface-name;
  server {
    address address ;
    routing-instance [ value ];
  }
}
tftp {
  description text ;
  interface interface-name;
  server {
    address address ;
    routing-instance [ value ];
  }
}
traceoptions {
  file filename {
    files number ;
    match regular-expression ;
    size maximum-file-size ;
    <world-readable | no-world-readable>;
  }
  flag {
    address;
    all;
    bootp;

```

```

        config;
        domain;
        ifdb;
        io;
        main;
        port;
        rtsock;
        tftp;
        trace;
        ui;
        util;
    }
    level level ;
}
}
packet-capture {
    disable;
    file filename {
        <files number >;
        <size maximum-file-size >;
        <world-readable | no-world-readable>;
    }
    maximum-capture-size [ value ];
}
port-mirroring {
    family {
        inet {
            input {
                rate number ;
                run-length number ;
            }
            output {
                interface interface-name {
                    next-hop {
                        address ;
                    }
                }
                no-filter-check;
            }
        }
    }
}
traceoptions {
    file filename <files number > <size maximum-file-size >
    <world-readable | no-world-readable>;
}
}
sampling {
    disable;
    input {
        family {
            inet {
                max-packets-per-second number ;
                rate number ;
                run-length number ;
            }
        }
    }
}

```



```

    }
    output {
      cflowd hostname {
        aggregation {
          autonomous-system;
          destination-prefix;
          protocol-port;
          source-destination-prefix {
            caida-compliant;
          }
          source-prefix;
        }
        autonomous-system-type (origin | peer);
        (local-dump | no-local-dump);
        port port-number ;
        source-address address ;
        version format ;
      }
      file {
        disable;
        file filename;
        files number ;
        size bytes ;
        (stamp | no-stamp);
        (world-readable | no-world-readable);
      }
      flow-active-timeout seconds ;
      flow-inactive-timeout seconds ;
      interface interface-name ;
    }
  }
}

```

## vpn

<b>Syntax</b>	vpn;
<b>Hierarchy Level</b>	[edit forwarding-options helpers bootp]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>For Dynamic Host Configuration Protocol (DHCP) or BOOTP client request forwarding, enable virtual private network (VPN) encryption for a client request to pass through a VPN tunnel.</p> <p>This statement is supported on J-series devices.</p>
<b>Usage Guidelines</b>	To configure DHCP, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>



## Chapter 9

# Groups Hierarchy

This chapter presents the complete **groups** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Use the statements in the groups configuration hierarchy to configure information that can be dynamically updated in different parts of the device configuration.

For information about these **groups** statements that are shared across Juniper Networks devices, see the *JUNOS CLI User Guide*.

This chapter contains the following sections:

- Groups Configuration Statement Hierarchy on page 95

### Groups Configuration Statement Hierarchy

---

To configure groups, use the following statements at the [edit groups] hierarchy level.

Shared JUNOS statements in the **groups** hierarchy are shown in normal font and are documented in the *JUNOS CLI User Guide*.

```
groups {  
  group-name {  
    configuration-data ;  
  }  
}
```



## Chapter 10

# Interfaces Hierarchy and Statements

This chapter presents the complete **interfaces** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **interfaces** configuration hierarchy to configure interfaces on the device. For configuration instructions, see the *JUNOS Software Interfaces and Routing Configuration Guide* and the *JUNOS Software Administration Guide*.

For information about **interfaces** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS Network Interfaces Configuration Guide* and the *JUNOS Services Interfaces Configuration Guide*.

This chapter contains the following sections:

- Interfaces Configuration Statement Hierarchy on page 97

## Interfaces Configuration Statement Hierarchy

---

To configure interfaces, use the following statements at the **[edit Interfaces]** hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **interfaces** hierarchy are shown in normal font and are documented in the *JUNOS Network Interfaces Configuration Guide* and the *JUNOS Services Interfaces Configuration Guide*.

```
interfaces {
  interface-name {
    accounting-profile name ;
    atm-options {
      cell-bundle-size cells ;
      ilmi;
      linear-red-profiles profile-name {
        high-plp-max-threshold percent ;
        low-plp-max-threshold percent ;
        queue-depth cells high-plp-threshold percent low-plp-threshold percent ;
      }
    }
    mpls {
      pop-all-labels {
        required-depth number ;
      }
    }
  }
}
```

```

    }
  }
  pic-type (atm1 | atm2);
  plp-to-clp;
  promiscuous-mode {
    vpi vpi-identifier ;
  }
  scheduler-maps map-name {
    forwarding-class class-name {
      epd-threshold cells plp1 cells ;
      linear-red-profile profile-name ;
      priority (low | high);
      transmit-weight (cells number | percent number );
    }
    vc-cos-mode (alternate | strict);
  }
  vpi vpi-identifier {
    maximum-vcs maximum-vcs ;
    oam-liveness {
      down-count cells;
      up-count cells;
    }
    oam-period (disable | seconds);
    shaping {
      (cbr rate | rtvbr peak rate sustained rate burst length |
      vbr peak rate sustained rate burst length );
      queue-length number ;
    }
  }
}
}
clocking (external | internal);
dce;
description text ;
dialer-options {
  pool pool-identifier ;
  priority priority-number ;
}
disable;
dsl-options {
  loopback local;
  operating-mode mode ;
}
ds0-options {
  bert-algorithm algorithm ;
  bert-error-rate rate ;
  bert-period seconds ;
  byte-encoding (nx56 | nx64);
  fcs (16 | 32);
  idle-cycle-flag (flags | ones);
  invert data;
  loopback (payload | remote);
  start-end-flag (shared | filler);
}
e1-options {
  bert-algorithm algorithm ;
  bert-error-rate rate ;

```

```

    bert-period seconds ;
    fcs (16 | 32);
    framing (g704 | g704-no-crc4 | unframed);
    idle-cycle-flag (flags | ones);
    invert data;
    loopback (local | remote);
    start-end-flag (shared | filler);
    timeslots time-slot-range;
}
e3-options {
    atm-encapsulation (direct | PLCP);
    bert-algorithm algorithm ;
    bert-error-rate rate ;
    bert-period seconds ;
    buildout feet;
    compatibility-mode (digital-link | kentrox | larscom) <subrate value >;
    fcs (16 | 32);
    framing (g.751 | g.832);
    idle-cycle-flag value ;
    loopback (local | remote);
    (payload-scrambler | no-payload-scrambler);
    start-end-flag value ;
    (unframed | no-unframed);
}
encapsulation type ;
ether-vpls-over-atm-llc;
es-options {
    backup-interface es- pim /0/ port ;
}
fabric-options {
    member-interfaces member-interface-name;
}
failure-options {
    [trigger-link-failure interface-name ];
}
fastether-options {
    (flow-control | no-flow-control);
    ingress-rate-limit rate ;
    (loopback | no-loopback);
    mpls {
        pop-all-labels {
            required-depth [ number ];
        }
    }
    redundant-parent interface-name;
    source-address-filter {
        mac-address ;
    }
    (source-filtering | no-source-filtering);
}
flexible-vlan-tagging;
framing (lan-phy | sdh | sonet | wan-phy);
gigether-options {
    (auto-negotiation <remote-fault
    (local-interface-online | local-interface-offline)> | no-auto-negotiation);
    (flow-control | no-flow-control);

```

```

ignore-l3-incompletes;
(loopback | no-loopback);
mpls {
    pop-all-labels {
        required-depth [ number ];
    }
}
redundant-parent interface-name;
source-address-filter {
    mac-address ;
}
(source-filtering | no-source-filtering);
ethernet-switch-profile {
    ethernet-policer-profile {
        input-priority-map {
            ieee802.1p premium [ values ];
        }
        output-priority-map {
            classifier {
                premium {
                    forward-class class-name {
                        loss-priority (high | low);
                    }
                }
            }
        }
        policer cos-policer-name {
            aggregate {
                bandwidth-limit bps ;
                burst-size-limit bytes ;
            }
            premium {
                bandwidth-limit bps ;
                burst-size-limit bytes ;
            }
        }
    }
}
(mac-learn-enable | no-mac-learn-enable);
tag-protocol-id [ tpids ];
}
}
(gratuitous-arp-reply | no-gratuitous-arp-reply);
hold-time up milliseconds down milliseconds ;
isdn-options {
    calling-number number ;
    incoming-called-number number <reject>;
    pool pool-name <priority priority> ;
    spid1 spid-string ;
    spid2 spid-string ;
    static-tei-val value ;
    switch-type (att5e | etsi | ni1 | ntdms100 | ntt);
    t310 seconds ;
    tei-option (first-call | power-up);
}
keepalives <down-count number > <interval seconds > <up-count number >;
lmi {

```



```

lmi-type (ansi | itu);
n391dte number ;
n392dce number ;
n392dte number ;
n393dce number ;
n393dte number ;
t391dte seconds ;
t392dce seconds ;
}
mac mac-address ;
mlfr-uni-nni-bundle-options {
    acknowledge-retries number ;
    acknowledge-timer milliseconds ;
    action-red-differential-delay (disable-tx | remove-link);
    drop-timeout milliseconds ;
    fragment-threshold bytes ;
    hello-timer milliseconds ;
    link-layer-overhead percent ;
    lmi-type (ansi | itu);
    minimum-links number ;
    mrru bytes ;
    n391 number ;
    n392 number ;
    n393 number ;
    red-differential-delay milliseconds ;
    t391 seconds ;
    t392 seconds ;
    yellow-differential-delay milliseconds ;
}
modem-options {
    dialin (console | routable);
    init-command-string initialization-command-string ;
}
mtu bytes ;
multiservice-options {
    boot-command filename;
    (core-dump | no-core-dump);
    (syslog | no-syslog);
}
no-gratuitous-arp-request;
no-keepalives;
no-partition {
    interface-type type ;
}
partition partition-number {
    interface-type type ;
    oc-slice oc-slice-range ;
    timeslots time-slot-range ;
}
passive-monitor-mode;
per-unit-scheduler;
ppp-options {
    chap {
        access-profile name;
        default-chap-secret name ;
        local-name name;
    }
}

```

```

        passive;
    }
    compression {
        acfc;
        pfc;
    }
    no-termination-request;
    lcp-restart-timer milliseconds ;
    ncp-restart-timer milliseconds ;
}
redundant-ether-options {
  (flow-control | no-flow-control);
  link-speed speed;
  (loopback | no-loopback);
  redundancy-group number;
  source-address-filter mac-address;
  (source-filtering | no-source-filtering);
}
serial-options {
    clock-rate rate ;
    clocking-mode (dce | internal | loop);
    control-leads {
        control-signal (assert | de-assert | normal);
        cts (ignore | normal | require);
        dcd (ignore | normal | require);
        dsr (ignore | normal | require);
        dtr signal-handling-option ;
        ignore-all;
        indication (ignore | normal | require);
        rts (assert | de-assert | normal);
        tm (ignore | normal | require);
    }
    control-polarity (positive | negative);
    cts-polarity (positive | negative);
    dcd-polarity (positive | negative);
    dsr-polarity (positive | negative);
    dtr-circuit (balanced | unbalanced);
    dtr-polarity (positive | negative);
    encoding (nrz | nrzi);
    indication-polarity (positive | negative);
    line-protocol protocol ;
    loopback mode;
    rts-polarity (positive | negative);
    tm-polarity (positive | negative);
    transmit-clock invert;
}
services-options {
    inactivity-timeout seconds ;
    open-timeout seconds ;
    syslog {
        host hostname {
            facility-override facility-name ;
            log-prefix prefix-number ;
            services priority-level ;
        }
    }
}

```

```

}
shdsl-options {
    annex (annex-a | annex-b);
    line-rate line-rate ;
    loopback (local | remote | payload);
    snr-margin {
        current margin ;
        snext margin ;
    }
}
t1-options {
    bert-algorithm algorithm ;
    bert-error-rate rate ;
    bert-period seconds ;
    buildout value ;
    byte-encoding (nx64 | nx56);
    fcs (16 | 32);
    framing (esf | sf);
    idle-cycle-flags (flags | ones);
    invert-data;
    line-encoding (ami | b8zs);
    loopback (local | payload | remote);
    remote-loopback-respond;
    start-end-flag (filler | shared);
    timeslots time-slot-range ;
}
t3-options {
    atm-encapsulation (direct | PLCP);
    bert-algorithm algorithm ;
    bert-error-rate rate ;
    bert-period seconds ;
    buildout feet;
    (cbit-parity | no-cbit-parity);
    compatibility-mode (adtran | digital-link | kentrox | larscom | verilink)
    <subrate value >;
    fcs (16 | 32);
    (feac-loop-respond | no-feac-loop-respond);
    idle-cycle-flag value ;
    (long-buildout | no-long-buildout);
    (loop-timing | no-loop-timing);
    loopback (local | payload | remote);
    (payload-scrambler | no-payload-scrambler);
    start-end-flag value ;
}
threshold bytes ;
traceoptions {
    flag flag < flag-modifier > <disable>;
}
(traps | no-traps);
vlan-tagging;
unit logical-unit-number {
    accept-source-mac {
        mac-address mac-address ;
        policer {
            input policer-name ;
            output policer-name ;
        }
    }
}

```

```

    }
  }
  accounting-profile name ;
  allow-any-vci;
  atm-scheduler-map (default | map-name );
  backup-options {
    interface interface-name ;
  }
  bandwidth rate ;
  cell-bundle-size cells ;
  clear-dont-fragment-bit;
  compression {
    rtp {
      f-max-period number ;
      maximum-contexts number ;
      port {
        maximum port-number ;
        minimum port-number ;
      }
      queues [ queue-numbers ];
    }
  }
  compression-device interface-name ;
  copy-tos-to-outer-ip-header;
  description text ;
  dialer-options {
    activation-delay seconds ;
    callback;
    callback-wait-period seconds ;
    deactivation-delay seconds ;
    dial-string [ dial-string-numbers ];
    idle-timeout seconds ;
    incoming-map (accept-all | caller caller-number );
    initial-route-check seconds ;
    load-interval seconds ;
    load-threshold percent ;
    pool pool-name ;
    redial-delay time ;
    watch-list {
      [ routes ];
    }
  }
  disable;
  disable-mlppp-inner-ppp-pfc;
  dlci dlci-identifier ;
  drop-timeout milliseconds ;
  dynamic-call-admission-control {
    activation-priority number ;
    bearer-bandwidth-limit threshold ;
  }
  encapsulation type ;
  epd-threshold cells plp1 cells ;
  f-max-period number ;
  fragment-threshold bytes ;
  input-vlan-map {
    (pop | pop-pop | pop-swap | push | push-push | swap |

```

```

        swap-push | swap-swap);
        inner-tag-protocol-id tpid;
        inner-vlan-id number ;
        tag-protocol-id tpid;
        vlan-id number ;
    }
    interleave-fragments;
    inverse-arp;
    (keepalives | no-keepalives);
    link-layer-overhead percent ;
    minimum-links number ;
    mrru bytes ;
    multicast-dlci dlci-identifier ;
    multicast-vci vpi-identifier.vci-identifier ;
    multilink-max-classes number ;
    multipoint number ;
    multipoint;
    oam-liveness {
        up-count cells ;
        down-count cells ;
    }
    oam-period (disable | seconds );
    output-vlan-map {
        (pop | pop-pop | pop-swap | push | push-push | swap |
        swap-push | swap-swap);
        inner-tag-protocol-id tpid;
        inner-vlan-id number ;
        tag-protocol-id tpid;
        vlan-id number ;
    }
    passive-monitor-mode;
    peer-unit unit-number ;
    plp-to-clp;
    point-to-point;
    ppp-options {
        chap {
            access-profile name ;
            default-chap-secret name ;
            local-name name ;
            passive;
        }
        compression {
            acfc;
            pfc;
        }
        lcp-restart-timer milliseconds ;
        loopback-clear-timer seconds ;
        ncp-restart-timer milliseconds ;
        no-termination-request;
        pap;
        access-profile name ;
        default-password password ;
        local-name name ;
        local-password password ;
        passive;
    }
}

```

```

}
pppoe-options {
    access-concentrator name ;
    auto-reconnect seconds ;
    service-name name ;
    underlying-interface interface-name ;
}
proxy-arp;
service-domain (inside | outside);
shaping{
    (cbr rate | rtvbr peak rate sustained rate burst length |
    vbr peak rate sustained rate burst length );
    queue-length number ;
}
short-sequence;
three-color-policer {
    input policer-name ;
    output policer-name ;
}
transmit-weight number ;
(traps | no-traps);
trunk-bandwidth rate ;
trunk-id number ;
tunnel {
    backup-destination address ;
    destination address ;
    key number ;
    routing-instance {
        destination routing-instance-name;
    }
    source source-address ;
    ttl number ;
}
vci vpi-identifier.vci-identifier ;
vpi vpi-identifier ;
vlan-id number ;
vlan-tags inner tpid.vlan-id outer tpid.vlan-id ;
family family {
    accounting {
        destination-class-usage;
        source-class-usage {
            direction ;
        }
    }
}
address address {
    arp ip-address (mac | multicast-mac) mac-address <publish>;
    broadcast address ;
    destination address ;
    destination-profile name ;
    eui-64;
    multipoint-destination address dlci dlci-identifier ;
    multipoint-destination address {
        epd-threshold cells ;
        inverse-arp;
        oam-liveness {
            up-count cells ;
        }
    }
}

```

```

        down-count cells ;
    }
    oam-period ( disable | seconds );
    shaping{
        (cbr rate | rtvbr peak rate sustained rate burst length |
        vbr peak rate sustained rate burst length );
        queue-length number ;
    }
    vci vpi-identifier.vci-identifier ;
}
preferred;
primary;
vrp-group group-number {
    (accept-data | no-accept-data):
    advertise-interval seconds ;
    authentication-type authentication ;
    authentication-key key ;
    fast-interval milliseconds;
    (preempt | no-preempt) {
        hold-time seconds ;
    }
    priority number ;
    track {
        interface interface-name {
            priority-cost priority ;
            bandwidth-threshold bits-per-second {
                priority-cost priority ;
            }
        }
        priority-hold-time seconds ;
    }
    virtual-address [ addresses ];
}
web-authentication {
    http;
}
}
bundle interface-name ;
dhcp {
    client-identifier (ascii ascii | hexadecimal hexadecimal);
    lease-time seconds;
    retransmission-attempt number;
    retransmission-interval seconds;
    server-address ip-address;
    update-server;
    vendor-id vendor-id;
}
dialer filter-name;
filter {
    group filter-group-number;
    input filter-name;
    input-list {
        [filter-names];
    }
    output filter-name ;
    output-list {

```

```

        [filter-names];
    }
}
keep-address-and-control;
mtu bytes ;
multicast-only;
next-hop-tunnel gateway-address ipsec-vpn vpn-name;
no-redirects;
policer {
    arp policer-template-name;
    input policer-template-name;
    output policer-template-name;
}
primary;
proxy inet-address address ;
receive-options-packets;
receive-ttl-exceeded;
remote (inet-address address | mac-address address);
rpf-check <fail-filter filter-name> {
    <mode loose>;
}
sampling {
    direction ;
}
service {
    input {
        service-set service-set-name <service-filter filter-name >;
        post-service-filter filter-name ;
    }
    output {
        service-set service-set-name <service-filter filter-name >;
    }
}
simple-filter {
    input filter-name ;
}
(translate-discard-eligible | no-translate-discard-eligible);
(translate-ecn-and-becn | no-translate-ecn-and-becn);
unnumbered-address {
    interface-name ;
    destination destination-address ;
    destination-profile profile-name ;
    preferred-source-address interface-name ;
}
}
}
traceoptions {
    flag flag <disable>;
}
}
traceoptions {
    file filename <files number > <match regular-expression >
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag <disable>;
}

```



## client-identifier

---

<b>Syntax</b>	<code>client-identifier (ascii <i>ascii</i>   hexadecimal <i>hexadecimal</i> );</code>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet dhcp]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify an ASCII or hexadecimal identifier for the Dynamic Host Configuration Protocol (DHCP) client. The DHCP server identifies a client by a client-identifier value.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<code>ascii <i>ascii</i></code> —Identifier consisting of ASCII characters.  <code>hexadecimal <i>hexadecimal</i></code> —Identifier consisting of hexadecimal characters.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## dhcp

---

<b>Syntax</b>	<pre>dhcp {   client-identifier (ascii <i>ascii</i>   hexadecimal <i>hexadecimal</i> );   lease-time <i>seconds</i> ;   retransmission-attempt <i>number</i> ;   retransmission-interval <i>seconds</i> ;   server-address <i>ip-address</i> ;   update-server;   vendor-id <i>vendor-id</i> ; }</pre>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family <i>family</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the Dynamic Host Configuration Protocol (DHCP) client.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## fabric-options

---

<b>Syntax</b>	fabric-options { member-interfaces <i>member-interface-name</i> ; }
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure fabric interface properties.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statement is explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## flow-control

---

<b>Syntax</b>	(flow-control   no-flow-control);
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> fastether-options], [edit interfaces <i>interface-name</i> gigeether-options], [edit interfaces <i>interface-name</i> redundant-ether-options]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	For Fast Ethernet, Gigabit Ethernet, and redundant Ethernet interfaces only, explicitly enable flow control, which regulates the flow of packets from the device to the remote side of the connection. Enabling flow control is useful when the device is a Gigabit Ethernet switch. Flow control is not supported on the 4-port Fast Ethernet ePIM.  This statement is supported on J-series and SRX-series devices.
<b>Default</b>	Flow control is the default behavior.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## lease-time

---

<b>Syntax</b>	<code>lease-time seconds ;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet dhcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the time to negotiate and exchange Dynamic Host Configuration Protocol (DHCP) information.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>seconds</i> —Request time to negotiate and exchange information. <b>Range:</b> 60 through 2147483647 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## link-speed

---

<b>Syntax</b>	<code>link-speed speed ;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> redundant-ether-options]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	For redundant Ethernet interfaces (reth0) in a chassis cluster only, set the required link speed.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>speed</i> —For redundant Ethernet links, you can specify <i>speed</i> in bits per second either as a complete decimal number or as a decimal number followed by the abbreviation k (1000), m (1,000,000), or g(1,000,000,000).
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## loopback

---

<b>Syntax</b>	(loopback   no-loopback);
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> redundant-ether-options]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	For Fast Ethernet, Gigabit Ethernet, and redundant Ethernet interfaces, enable or disable loopback mode.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## member-interfaces

---

<b>Syntax</b>	member-interfaces <i>member-interface-name</i> ;
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> fabric-options]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the member interface name. Member interfaces that connect to each other must be of the same type.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>member-interface-name</i> —Member interface name.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## next-hop-tunnel

---

<b>Syntax</b>	<code>next-hop-tunnel <i>gateway-address</i> ipsec-vpn <i>vpn-name</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>For the secure tunnel (st) interface, create entries in the Next-Hop Tunnel Binding (NHTB) table, which is used to map the next-hop gateway IP address to a particular IP Security (IPsec) Virtual Private Network (VPN) tunnel. NHTB allows the binding of multiple IPsec VPN tunnels to a single IPsec tunnel interface.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><code><i>gateway-address</i></code> —Next-hop gateway IP address.</p> <p><code>ipsec-vpn <i>vpn-name</i></code> —VPN to which the next-hop gateway IP address is mapped.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>

## no-flow-control

---

**See** `flow-control`

## no-loopback

---

**See** `loopback`

## no-source-filtering

---

**See** `source-filtering`

## redundancy-group

---

<b>Syntax</b>	<code>redundancy-group <i>number</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> redundant-ether-options]</code>
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Specify the redundancy group that a redundant Ethernet interface belongs to.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Number of the redundancy group that the redundant interface belongs to. Failover properties of the interface are inherited from the redundancy group. <b>Range:</b> 1 through 255
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> . See also .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## redundant-ether-options

---

<b>Syntax</b>	<code>redundant-ether-options {     (flow-control   no-flow-control);     link-speed <i>speed</i> ;     (loopback   no-loopback);     redundancy-group <i>number</i> ;     source-address-filter <i>mac-address</i> ;     (source-filtering   no-source-filtering); }</code>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Configure Ethernet redundancy options for a chassis cluster.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## redundant-parent

---

See the following sections:

- [redundant-parent \(Fast Ethernet Options\)](#) on page 115
- [redundant-parent \(Gigabit Ethernet Options\)](#) on page 115

### ***redundant-parent (Fast Ethernet Options)***

**Syntax** `redundant-parent interface-name ;`

**Hierarchy Level** [edit interfaces *interface-name* fastether-options]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Configure Fast Ethernet-specific interface properties for Ethernet redundancy in a chassis cluster.

This statement is supported on J-series and SRX-series devices.

**Options** *interface* —Parent redundant interface of the Fast Ethernet interface.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

### ***redundant-parent (Gigabit Ethernet Options)***

**Syntax** `redundant-parent interface-name ;`

**Hierarchy Level** [edit interfaces *interface-name* ggether-options]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Configure Gigabit Ethernet-specific interface properties for Ethernet redundancy in a chassis cluster.

This statement is supported on J-series and SRX-series devices.

**Options** *interface* —Parent redundant interface of the Gigabit Ethernet interface.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

## retransmission-attempt

---

<b>Syntax</b>	<code>retransmission-attempt <i>number</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet dhcp]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the number of times the device attempts to retransmit a Dynamic Host Control Protocol (DHCP) packet fallback.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Number of attempts to retransmit the packet. <b>Range:</b> 0 through 6 <b>Default:</b> 4
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## retransmission-interval

---

<b>Syntax</b>	<code>retransmission-interval <i>seconds</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet dhcp]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the time between successive retransmission attempts.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>seconds</i> —Number of seconds between successive retransmission. <b>Range:</b> 4 through 64 seconds <b>Default:</b> 4 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.



## server-address

---

<b>Syntax</b>	<code>server-address ip-address ;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet dhcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the preferred DHCP server address that is sent to DHCP clients.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ip-address</i> —DHCP server address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## source-address-filter

---

<b>Syntax</b>	<code>source-address-filter mac-address ;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> redundant-ether-options]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	For redundant Ethernet interfaces, specify the MAC addresses from which the interface can receive packets. For this statement to have any effect, you must include the <code>source-filtering</code> statement in the configuration to enable source address filtering.  Be sure to update the MAC address if the remote Ethernet card is replaced. Replacing the interface card changes the MAC address. Otherwise, the interface cannot receive packets from the new card.  This statement is supported on J-series devices.
<b>Options</b>	<i>mac-address</i> —MAC address filter. You can specify the MAC address as six hexadecimal bytes in one of the following formats: <i>nn:nn:nn:nn:nn:nn</i> (for example, 00:11:22:33:44:55) or <i>nnnn:nnnn:nnnn</i> (for example, 0011.2233.4455). You can configure up to 64 source addresses. To specify more than one address, include multiple <i>mac-address</i> options in the <code>source-address-filter</code> statement.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> . See also <code>source-filtering</code> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## source-filtering

---

<b>Syntax</b>	(source-filtering   no-source-filtering);
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> redundant-ether-options]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	<p>For redundant Ethernet interfaces, enable the filtering of MAC source addresses, which blocks all incoming packets to that interface. To allow the interface to receive packets from specific MAC addresses, include the <b>source-address-filter</b> statement.</p> <p>If the remote Ethernet card is changed, the interface cannot receive packets from the new card because it has a different MAC address.</p> <p>By default, source address filtering is disabled.</p> <p>This statement is supported on J-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> . See also <b>source-address-filter</b> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## update-server

---

<b>Syntax</b>	update-server;
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet dhcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Propagate DHCP options to a local DHCP server.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## vendor-id

---

<b>Syntax</b>	<code>vendor-id vendor-id ;</code>
<b>Hierarchy Level</b>	<code>[edit interfaces interface-name unit logical-unit-number family inet dhcp]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure a vendor class ID for the Dynamic Host Configuration Protocol (DHCP) client.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<code>vendor-id</code> —vendor class ID.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>

## web-authentication

---

<b>Syntax</b>	<pre>web-authentication {   http; }</pre>
<b>Hierarchy Level</b>	<code>[edit interfaces interface-name unit logical-unit-number family inet address address ]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the Web authentication process for firewall user authentication.</p> <p><code>http</code>—Enable HTTP service.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>



## Chapter 11

# Policy-Options Hierarchy and Statements

This chapter presents the complete **policy-options** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **policy-options** configuration hierarchy to configure routing policies that control the information from routing protocols that the device imports into its routing table and exports to its neighbors. For configuration instructions, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

For information about **policy-options** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS Policy Framework Configuration Guide*.

This chapter contains the following sections:

- Policy-Options Configuration Statement Hierarchy on page 121

## Policy-Options Configuration Statement Hierarchy

---

To configure policy options, use the following statements at the [edit **policy-options**] hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **policy-options** hierarchy are shown in normal font and are documented in the *JUNOS Policy Framework Configuration Guide*.

```
policy-options {
  as-path name regular-expression ;
  as-path-group group-name;
  community name {
    invert-match;
    members [ community-ids];
  }
  condition condition-name {
    if-route-exists address table table-name;
    route-active-on (node0 | node1);
  }
  damping name{
    disable;
    half-life minutes;
```

```

    max-suppress minutes;
    reuse number;
    suppress number;
}
policy-statement policy-name {
  term term-name {
    default-action (accept | reject);
    from {
      family family-name;
      match-conditions;
      policy subroutine-policy-name;
      prefix-list name;
      route-filter destination-prefix match-type <actions>;
      source-address-filter destination-prefix match-type <actions>;
    }
    to {
      match-conditions;
      policy subroutine-policy-name;
    }
    then actions;
  }
}
prefix-list name {
  ip-addresses;
}
}

```

## condition

---

**Syntax** `condition condition-name {  
     if-route-exists address table table-name ;  
     route-active-on (node0 | node1);  
}`

**Hierarchy Level** [edit policy-options]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** For chassis cluster configurations, specify the match condition for use in routing to a redundant Ethernet (reth) interface.

This statement is supported on J-series and SRX-series devices.

**Options** *condition-name* —Name of the routing policy match condition.

The remaining statement is explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** routing—To view this statement in the configuration.  
 routing-control—To add this statement to the configuration.

## route-active-on

---

<b>Syntax</b>	route-active-on (node0   node1);
<b>Hierarchy Level</b>	[edit policy-options condition <i>condition-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>For chassis cluster configurations, identify the device (node) on which a route is active.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	node0   node1—Node in a chassis cluster.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	routing—To view this statement in the configuration. routing-control—To add this statement to the configuration.





## Chapter 12

# Protocols Hierarchy

This chapter presents the complete **protocols** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **protocols** configuration hierarchy to configure routing protocols, including Intermediate System-to-Intermediate System (IS-IS), Open Shortest Path First (OSPF), Routing Information Protocol (RIP), Routing Information Protocol Next Generation (RIPng), and Border Gateway Protocol (BGP). For configuration instructions, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

For information about these **protocols** statements that are shared across Juniper Networks devices, see the *JUNOS Routing Protocols Configuration Guide* and the *JUNOS Services Interfaces Configuration Guide*.

This chapter contains the following sections:

- Protocols Configuration Statement Hierarchy on page 125

## Protocols Configuration Statement Hierarchy

---

To configure protocols, use the following statements at the [edit protocols] hierarchy level.

Shared JUNOS statements in the **protocols** hierarchy are shown in normal font and are documented in the *JUNOS Routing Protocols Configuration Guide*, the *JUNOS MPLS Applications Configuration Guide*, the *JUNOS Multicast Protocols Configuration Guide*, and the *JUNOS Services Interfaces Configuration Guide*.

```
protocols {
  bfd {
    traceoptions {
      file filename <files number > <match regular-expression >
      <size maximum-file-size > <world-readable | no-world-readable>;
      flag flag ;
    }
  }
  bgp {
    accept-remote-nexthop;
    advertise-inactive;
    advertise-peer-as;
    authentication-algorithm algorithm ;
    authentication-key key ;
    authentication-key-chain key-chain ;
```

```

bfd-liveness-detection {
  detection-time {
    threshold milliseconds ;
  }
  holddown-interval milliseconds;
  local-address ip-address ;
  minimum-interval milliseconds ;
  minimum-receive-interval milliseconds ;
  minimum-receive-ttl milliseconds ;
  multiplier number ;
  neighbor address ;
  transmit-interval {
    minimum-interval milliseconds ;
    threshold milliseconds ;
  }
  version (0 | 1);
}
cluster cluster-identifier;
damping;
description text-description ;
disable;
export [ policy-name ];
family {
  (inet | inet-mvpn | inet-vpn | inet6 | inet6-mvpn | inet6-vpn | iso-vpn | l2-vpn) {
    (any | flow | multicast | unicast | signaling) {
      prefix-limit {
        maximum number ;
        teardown < percentage > <idle-timeout (forever | minutes )>;
      }
      rib-group group-name ;
    }
    labeled-unicast {
      aggregate-label {
        community community-name :
      }
      explicit-null {
        connected-only;
      }
      per-group-label;
      prefix-limit {
        maximum number ;
        teardown < percentage > <idle-timeout (forever | minutes )>;
      }
      resolve-vpn;
      rib inet.3;
      rib-group group-name ;
      traffic-statistics {
        file filename <files number > <match regular-expression >
          <size maximum-file-size > <world-readable | no-world-readable>;
        interval seconds ;
      }
    }
  }
}
route-target {
  advertise-default;
  external-paths number ;
}

```

```

        prefix-limit {
            maximum number ;
            teardown < percentage > <idle-timeout (forever | minutes) >;
        }
    }
}
graceful-restart {
    disable;
    restart-time seconds ;
    stale-routes-time seconds ;
}
group group-name {
    bgp-options ;
    peer-as autonomous-system ;
    type type ;
    neighbor address ;
}
hold-time seconds ;
import [ policy-name ];
include-mp-next-hop;
keep (all | none);
local-address address ;
local-as autonomous-system <private> <loops loops >;
local-preference local-preference ;
log-updown;
metric-out ( metric | minimum-igp < offset > | igp < offset >);
multihop < ttl-value >;
no-advertise-peer-as;
no-aggregator-id;
no-client-reflect;
out-delay seconds ;
passive;
path-selection {
    (always-compare-med | cisco-non-deterministic | external-router-id);
    med-plus-igp {
        igp-multiplier number ;
        med-multiplier number ;
    }
}
peer-as autonomous-system ;
preference preference ;
remove-private;
tcp-mss segment-size ;
traceoptions {
    file filename <files number > <no-stamp> <replace>
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
vpn-apply-export;
}
connections {
    interface-switch interface-switch-name {
        interface interface-name ;
    }
    lsp-switch lsp-switch-name {
        receive-lsp path-name ;
    }
}

```

```

        transmit-lsp path-name ;
    }
    remote-interface-switch {
        interface interface-name ;
        receive-lsp path-name ;
        transmit-lsp path-name ;
    }
}
dot1x {
    authenticator {
        authentication-profile-name profile-name ;
        interface interface-name {
            disable;
            guest-vlan vlan-name ;
            maximum-requests request-number ;
            quiet-period seconds ;
            (reauthentication seconds | no-reauthentication);
            retries number ;
            server-timeout seconds ;
            suppliant (multiple | single | single-secure);
            suppliant-timeout seconds ;
            transmit-period seconds ;
        }
        static mac-address {
            interface interface-name ;
            vlan-assignment address ;
        }
    }
    traceoptions {
        file filename <files number > <no-stamp> <replace>
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag <disable>;
    }
}
dvmrp {
    disable;
    export [ policy-name ];
    import [ policy-name ];
    interface interface-name {
        disable;
        hold-time seconds ;
        metric value ;
        mode (forwarding | unicast-routing);
    }
    rib-group group-name ;
    traceoptions {
        file filename <files number > <no-stamp> <replace>
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag <flag-modifier > <disable>;
    }
}
esis {
    disable;
    graceful-restart {
        disable;
        restart-duration seconds ;
    }
}

```

```

}
interface ( interface-name | all) {
    disable;
    end-system-configuration-timer seconds ;
    hold-time seconds ;
}
preference preference ;
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
}
gvrp {
    disable;
    interface interface-name {
        disable;
    }
    join-timer milliseconds ;
    leave-timer milliseconds ;
    leaveall-timer milliseconds ;
}
igmp {
    accounting;
    interface interface-name {
        (accounting | no-accounting);
        disable;
        immediate-leave;
        promiscuous-mode;
        ssm-map ssm-map ;
        static {
            group group-address {
                source source-address ;
            }
        }
        version number ;
    }
    query-interval seconds ;
    query-last-member-interval seconds ;
    query-response-interval seconds ;
    robust-count robust-count ;
    traceoptions {
        file filename <files number > <no-stamp> <replace> <size maximum-file-size
        >
        <world-readable | no-world-readable>;
        flag flag < flag-modifier > <disable>;
    }
}
igmp-snooping {
    traceoptions {
        file filename <files number > <no-stamp> <replace> <size maximum-file-size
        >
        <world-readable | no-world-readable> <match regex>;
        flag flag ;
    }
}

```

```

vlan ( vlan-id | vlan-number {
    disable;
    immediate-leave;
    interface interface-name {
        multicast-router-interface;
        static {
            group ip-address ;
        }
    }
    query-interval seconds ;
    query-last-member-interval seconds ;
    query-response-interval seconds ;
    robust-count number ;
}
}
isis {
    clns-routing;
    disable;
    export [ policy-names ];
    graceful-restart {
        disable;
        helper-disable;
        restart-duration seconds ;
    }
    ignore-attached-bit;
    interface (all | interface-name ) {
        bfd-liveness-detection {
            detection-time {
                threshold milliseconds ;
            }
            minimum-interval milliseconds ;
            minimum-receive-interval milliseconds ;
            transmit-interval {
                minimum-interval milliseconds ;
                threshold milliseconds ;
            }
            multiplier number ;
            version (1 | automatic);
        }
        checksum;
        csnp-interval ( seconds | disable);
        disable;
        hello-padding (adaptive | loose | strict);
        ldp-synchronization {
            disable;
            hold-time seconds ;
        }
        level level-number {
            disable;
            hello-authentication-key key;
            hello-authentication-type authentication ;
            hello-interval seconds ;
            hold-time seconds ;
            ipv4-multicast-metric number ;
            ipv6-multicast-metric number ;
            ipv6-unicast-metric number ;
        }
    }
}

```

```

    metric metric ;
    passive;
    priority number ;
    te-metric metric ;
}
lsp-interval milliseconds ;
mesh-group ( value | blocked);
no-adjacency-down-notification;
no-ipv4-multicast;
no-ipv6-multicast;
no-ipv6-unicast;
no-unicast-topology;
passive;
point-to-point;
}
label-switched-path name level level metric metric ;
level level-number {
    authentication-key key ;
    authentication-type authentication ;
    disable;
    external-preference preference ;
    no-csnp-authentication;
    no-hello-authentication;
    no-psnp-authentication;
    preference preference ;
    prefix-export-limit number ;
    wide-metrics-only;
}
loose-authentication-check;
lsp-lifetime seconds ;
no-adjacency-holddown;
no-authentication-check;
no-ipv4-routing;
no-ipv6-routing;
overload {
    advertise-high-metrics;
    timeout seconds ;
}
reference-bandwidth reference-bandwidth ;
rib-group {
    inet group-name ;
    inet6 group-name ;
}
spf-options {
    delay milliseconds ;
    holddown milliseconds ;
    rapid-runs number ;
}
topologies {
    ipv4-multicast;
    ipv6-unicast;
}
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size >
    <world-readable | no-world-readable>;

```

```

        flag flag < flag-modifier > <disable>;
    }
    traffic-engineering {
        disable;
        ipv4-multicast-rpf-routes;
        shortcuts <ignore-lsp-metrics>;
    }
}
l2circuit {
    local-switching {
        interface interface-name {
            description text-description ;
            end-interface {
                interface interface-name ;
                protect-interface interface-name ;
            }
            ignore-mtu-mismatch;
            protect-interface interface-name ;
        }
    }
}
neighbor address {
    interface interface-name {
        bandwidth (ct0 class0 | ct1 class1 | ct2 class2 | ct3 class3 );
        community community ;
        (control-word | no-control-word);
        description text-description ;
        ignore-encapsulation-mismatch;
        mtu mtu ;
        protect-interface interface-name ;
        psn-tunnel-endpoint psn-tunnel-endpoint ;
        virtual-circuit-id circuit-id ;
    }
}
}
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
}
lacp {
    traceoptions {
        file filename <files number > <match regular-expression >
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag ;
    }
}
layer2-control {
    mac-rewrite {
        interface interface-name {
            protocol protocol-name ;
        }
    }
}
nonstop-bridging {
    mac-rewrite {
        interface interface-name {
            protocol protocol-name ;
        }
    }
}

```



```

    }
  }
  traceoptions {
    file filename <files number > <no-stamp> <replace>
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag ;
  }
}
traceoptions {
  file filename <files number > <no-stamp> <replace>
  <size maximum-file-size > <world-readable | no-world-readable>;
  flag flag ;
}
}
ldp {
  (deaggregate | no-deaggregate);
  egress-policy [ policy-name ];
  explicit-null;
  export [ policy-name ];
  graceful-restart {
    disable;
    helper-disable;
    maximum-recovery-time seconds ;
    recovery-time seconds ;
  }
  import [ policy-name ];
  interface interface-name {
    disable;
    hello-interval seconds ;
    hold-time seconds ;
    transport-address (interface | router-id);
  }
  keepalive-interval seconds ;
  keepalive-timeout seconds ;
  l2-smart-policy;
  log-updown {
    trap {
      disable;
    }
  }
  next-hop {
    merged {
      policy [ policy-name ];
    }
  }
}
no-forwarding;
oam {
  bfd-liveness-detection {
    detection-time {
      threshold milliseconds ;
    }
  }
  minimum-interval milliseconds ;
  minimum-receive-interval milliseconds ;
  multiplier number ;
  transmit-interval {
    minimum-interval milliseconds ;
  }
}

```

```

        threshold milliseconds ;
    }
    version (0 | 1 | automatic);
}
fec class-address {
    (bfd-liveness-detection | no-bfd-liveness-detection);
    periodic-traceroute flags ;
}
}
policing {
    fec class-address {
        ingress-traffic filter-name ;
        transit-traffic filter-name ;
    }
}
preference preference ;
session session-address {
    authentication-algorithm algorithm ;
    authentication-key key ;
    authentication-key-chain key-chain ;
}
strict-targeted-hellos;
traceoptions {
    file filename <files number> <no-stamp> <replace> <size maximum-file-size>
    <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
track-igp-metric;
traffic-statistics {
    file filename <files number> <match regular-expression>
    <size maximum-file-size> <world-readable | no-world-readable>;
    interval seconds ;
    no-penultimate-hop;
}
transport-address (interface | router-id);
}
link-management {
    peer peer-name {
        address address ;
        control-channel [ control-channel-interfaces ];
        lmp-control-channel interface-name {
            remote-address address ;
        }
        lmp-protocol {
            hello-dead-interval milliseconds ;
            hello-interval milliseconds ;
            passive;
            retransmission-interval milliseconds ;
            retry-limit number ;
        }
        te-link [ te-link-names ];
    }
}
te-link te-link-name {
    disable;
    interface interface-name {

```

```

        disable;
        local-address address ;
        remote-address address ;
        remote-id id-number ;
    }
    local-address address ;
    remote-address address ;
    remote-id id-number ;
    te-metric te-metric ;
}
traceoptions {
    file filename <files number> <no-stamp> <replace> <size maximum-file-size>
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
}
mld {
    interface interface-name {
        disable;
        immediate-leave;
        ssm-map ssm-map ;
        static {
            group group-address {
                source source-address ;
            }
        }
        version number ;
    }
    query-interval seconds ;
    query-last-member-interval seconds ;
    query-response-interval seconds ;
    robust-count robust-count ;
    traceoptions {
        file filename <files number > <no-stamp> <replace>
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag < flag-modifier > <disable>;
    }
}
mpls {
    disable;
    admin-down;
    admin-group {
        exclude [ group-names ];
        include-all [ group-names ];
        include-any [ group-names ];
    }
    admin-groups {
        group-name group-value ;
    }
    advertise-hold-time seconds ;
    auto-policing {
        class all policer-action;
        class ctnumber (drop | loss-priority-high | loss-priority-low);
    }
    bandwidth bps ;
    class-of-service cos-value ;
}

```

```

diffserv-te {
    bandwidth-model {
        extended-mam;
        mam;
        rdm;
    }
    te-class-matrix {
        tenumber {
            priority priority ;
            traffic-class {
                ctnumber priority priority ;
            }
        }
    }
}
expand-loose-hop;
explicit-null;
hop-limit number ;
icmp-tunneling;
interface ( interface-name | all ) {
    disable;
    admin-group {
        group-name ;
    }
    label-map ( in-label | default-route ) {
        class-of-service value ;
        (discard | next-hop ( address | hostname | interface-name ) | reject);
        (pop | swap out-label );
        preference preference ;
        swap-push swap-label push-label ;
    }
}
ipv6-tunneling;
label-switched-path lsp-name {
    disable;
    adaptive;
    admin-down;
    admin-group {
        exclude [ group-names ];
        include-all [ group-names ];
        include-any [ group-names ];
    }
    associate-backup-pe-groups;
    auto-bandwidth {
        adjust-interval seconds ;
        adjust-threshold percent ;
        adjust-threshold-overflow-limit number ;
        maximum-bandwidth bps ;
        minimum-bandwidth bps ;
        monitor-bandwidth;
    }
    bandwidth bps ;
    class-of-service cos-value ;
    description;
    fast-reroute {
        bandwidth bps ;

```

```

bandwidth-percent percent ;
(exclude group-names | no-exclude);
hop-limit number ;
(include-all group-names | no-include-all);
(include-any group-names | no-include-any);
}
from address ;
hop-limit number ;
install {
    destination-prefix / prefix-length <active>;
}
ldp-tunneling;
link-protection;
metric number ;
no-cspf;
no-decrement-ttl;
no-install-to-address;
node-link-protection;
oam {
    bfd-liveness-detection {
        detection-time threshold milliseconds ;
        failure-action teardown;
        minimum-interval milliseconds ;
        minimum-receive-interval milliseconds ;
        multiplier detection-time-multiplier ;
        no-adaptation;
        transmit-interval {
            minimum-interval milliseconds ;
            threshold milliseconds ;
        }
        version bfd-version ;
    }
    traceoptions {
        file filename <files number > <match regular-expression >
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag ;
    }
}
optimize-timer seconds ;
p2mp {
    path-name ;
}
policing {
    filter filter-name ;
    no-auto-policing;
}
preference preference ;
primary path-name {
    adaptive;
    admin-down;
    admin-group {
        exclude [ group-names ];
        include-all [ group-names ];
        include-any [ group-names ];
    }
    bandwidth bps ;
}

```

```

class-of-service cos-value ;
hop-limit number ;
no-cspf;
no-decrement-ttl;
oam {
    bfd-liveness-detection {
        detection-time threshold milliseconds ;
        failure-action teardown;
        minimum-interval milliseconds ;
        minimum-receive-interval milliseconds ;
        multiplier detection-time-multiplier ;
        no-adaptation;
        transmit-interval {
            minimum-interval milliseconds ;
            threshold milliseconds ;
        }
        version bfd-version ;
    }
    traceoptions {
        file filename <files number > <match regular-expression >
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag ;
    }
}
optimize-timer seconds ;
preference preference ;
priority setup-priority hold-priority ;
(record | no-record);
select {
    manual;
    unconditional;
}
standby;
}
priority setup-priority hold-priority ;
(random | least-fill | most-fill);
(record | no-record);
retry-limit number ;
retry-timer seconds ;
revert-timer seconds ;
secondary path-name {
    adaptive;
    admin-down;
    admin-group {
        exclude [ group-names ];
        include-all [ group-names ];
        include-any [ group-names ];
    }
    bandwidth bps ;
    class-of-service cos-value ;
    hop-limit number ;
    no-cspf;
    no-decrement-ttl;
    oam {
        bfd-liveness-detection {
            detection-time threshold milliseconds ;

```

```

        failure-action teardown;
        minimum-interval milliseconds ;
        minimum-receive-interval milliseconds ;
        multiplier detection-time-multiplier ;
        no-adaptation;
        transmit-interval {
            minimum-interval milliseconds ;
            threshold milliseconds ;
        }
        version bfd-version ;
    }
    traceoptions {
        file filename <files number > <match regular-expression >
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag ;
    }
}
optimize-timer seconds ;
preference preference ;
priority setup-priority hold-priority ;
(record | no-record);
select {
    manual;
    unconditional;
}
standby;
}
soft-preemption;
standby;
template;
to address ;
traceoptions {
    file filename <files number > <no-stamp> <replace>
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag ;
}
}
log-updown {
    (syslog | no-syslog);
    (trap | no-trap (mpls-lsp-traps | rfc3812-traps) );
    trap-path-down;
    trap-path-up;
}
no-cspf;
no-decrement-ttl;
no-propagate-ttl;
oam {
    bfd-liveness-detection {
        detection-time threshold milliseconds ;
        failure-action teardown;
        minimum-interval milliseconds ;
        minimum-receive-interval milliseconds ;
        multiplier detection-time-multiplier ;
        no-adaptation;
        transmit-interval {
            minimum-interval milliseconds ;

```

```

        threshold milliseconds ;
    }
    version bfd-version ;
}
traceoptions {
    file filename <files number > <match regular-expression >
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag ;
}
}
optimize-aggressive;
optimize-timer;
path path-name {
    address <loose | strict>;
}
path-mtu {
    allow-fragmentation;
    rsvp {
        mtu-signaling;
    }
}
preference preference ;
priority setup-priority hold-priority ;
(record | no-record);
revert-timer seconds ;
rsvp-error-hold-time seconds ;
smart-optimize-timer seconds ;
standby;
static-path inet {
    prefix {
        class-of-service value ;
        double-push bottom-value top-value ;
        next-hop ( address | interface-name );
        preference preference ;
        push out-label ;
        triple-push bottom-value middle-value top-value ;
    }
}
statistics {
    auto-bandwidth;
    file filename <files number> <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    interval seconds ;
}
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag ;
}
traffic-engineering (bgp | bgp-igp | bgp-igp-both-ribs | mpls-forwarding);
}
msdp {
    msdp-options ;
}

```



```

mstp {
  bpdu-block-on-edge;
  bridge-priority priority ;
  configuration-name name ;
  disable;
  forward-delay seconds ;
  hello-time seconds ;
  interface interface-name {
    bpdu-timeout-action {
      alarm;
      block;
    }
    cost interface-cost ;
    disable;
    edge;
    mode (point-to-point | shared);
    no-root-port;
    priority interface-priority ;
  }
  max-age seconds ;
  max-hops number ;
  msti msti-id {
    bridge-priority priority ;
    interface interface-name {
      cost interface-cost ;
      disable;
      priority interface-priority ;
    }
    vlan [vlan-id];
  }
  revision-level number ;
  traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
  }
}

oam {
  ethernet {
    connectivity-fault-management {
      action-profile profile-name {
        default-actions {
          interface-down;
        }
      }
    }
    linktrace {
      age (10s | 30s | 1m | 10m | 30m);
      path-database-size number ;
    }
    maintenance-domain domain-name {
      level number;
      name-format (character-string | dns | mac+2oct | none);
      maintenance-association association-name {
        continuity-check {
          hold-interval minutes ;
        }
      }
    }
  }
}

```

```

        interval (10m | 10s | 1m | 1s| 100ms);
        loss-threshold number ;
    }
    mep mep-id {
        auto-discovery;
        direction (up | down);
        interface interface-name ;
        priority number ;
        remote-mep mep-id {
            action-profile profile-name ;
        }
    }
    short-name-format (2octet | character-string | rfc-2685-vpn-id | vlan);
}
}
traceoptions {
    file filename <files number > <match regular-expression >
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag ;
}
}
link-fault-management {
    action-profile profile-name {
        action {
            link-down;
            send-critical-event;
            syslog;
        }
        event {
            link-adjacency-loss;
            link-event-rate {
                frame-error count ;
                frame-period count ;
                frame-period-summary count ;
                symbol-period count ;
            }
            protocol-down;
        }
    }
}
interface interface-name {
    apply-action-profile profile-name ;
    event-thresholds {
        frame-error count ;
        frame-period count ;
        frame-period-summary count ;
        symbol-period count ;
    }
    link-discovery (active | passive);
    negotiation-options {
        allow-remote-loopback;
        no-allow-link-events;
    }
    pdu-interval interval ;
    pdu-threshold threshold-value ;
}
traceoptions {

```

```

        file filename <files number> <match regular-expression>
        <size maximum-file-size> <world-readable | no-world-readable>;
        flag flag ;
    }
}
}
ospf {
    ospf-options ;
}
ospf3 {
    area area-id {
        area-range network/mask-length <restrict> <exact> <override-metric metric>;
    }
    interface interface-name {
        disable;
        dead-interval seconds ;
        hello-interval seconds ;
        metric metric ;
        neighbor address <eligible>;
        passive;
        priority number ;
        retransmit-interval seconds ;
        transit-delay seconds ;
    }
    nssa {
        area-range network/mask-length <restrict> <exact>
        <override-metric metric>;
        default-lsa {
            default-metric metric ;
            metric-type type ;
            type-7;
        }
        (no-summaries | summaries);
    }
    stub <default-metric metric> <(no-summaries | summaries)>;
}
disable;
export [ policy-names ];
external-preference preference ;
import [ policy-names ];
overload {
    <timeout seconds>;
}
preference preference ;
prefix-export-limit number ;
reference-bandwidth reference-bandwidth ;
rib-group group-name ;
spf-options {
    delay milliseconds ;
    holddown milliseconds ;
    rapid-runs number ;
}
traceoptions {
    file filename <files number> <no-stamp> <replace> <size maximum-file-size>
    >

```

```

        <world-readable | no-world-readable>;
        flag flag < flag-modifier > <disable>;
    }
}
pgm {
    pgm-options ;
}
pim {
    pim-options ;
}
ppp {
    ppp-options ;
}
rip {
    authentication-key password ;
    authentication-type type ;
    (check-zero | no-check-zero);
    graceful-restart {
        disable;
        restart-time seconds ;
    }
    group group-name {
        bfd-liveness-detection {
            detection-time {
                threshold milliseconds ;
            }
            minimum-interval milliseconds ;
            minimum-receive-interval milliseconds ;
            transmit-interval {
                minimum-interval milliseconds ;
                threshold milliseconds ;
            }
            multiplier number ;
            version (0 | 1 | automatic);
        }
        export [ policy-names ];
        metric-out metric ;
        preference preference ;
        route-timeout seconds ;
        update-interval seconds ;
        neighbor neighbor-name {
            authentication-key password ;
            authentication-type type ;
            bfd-liveness-detection {
                detection-time {
                    threshold milliseconds ;
                }
                minimum-interval milliseconds ;
                minimum-receive-interval milliseconds ;
                transmit-interval {
                    minimum-interval milliseconds ;
                    threshold milliseconds ;
                }
                multiplier number ;
                version (0 | 1 | automatic);
            }
        }
    }
}

```

```

        (check-zero | no-check-zero);
        import [ policy-names ];
        message-size number ;
        metric-in metric ;
        receive receive-options ;
        route-timeout seconds ;
        send send-options ;
        update-interval seconds ;
    }
}
holddown seconds ;
import [ policy-names ];
message-size number ;
metric-in metric ;
receive receive-options ;
rib-group group-name ;
route-timeout seconds ;
send send-options ;
update-interval seconds ;
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
}
ripng {
    ripng-options ;
}
router-advertisement {
    router-advertisement-configuration ;
}
router-discovery {
    address address {
        (advertise | ignore);
        (broadcast | multicast);
        (priority number | ineligible);
    }
    disable;
    interface interface-name {
        lifetime seconds ;
        max-advertisement-interval seconds ;
        min-advertisement-interval seconds ;
    }
    traceoptions {
        file filename <files number > <no-stamp> <replace> <size maximum-file-size
        >
        <world-readable | no-world-readable>;
        flag flag < flag-modifier > <disable>;
    }
}
}
rstp {
    bpdu-block-on-edge;
    bridge-priority priority ;
    disable;
    forward-delay seconds ;

```

```

hello-time seconds ;
interface interface-name {
    bpdu-timeout-action {
        alarm;
        block;
    }
    cost interface-cost ;
    disable;
    edge;
    mode (point-to-point | shared);
    no-root-port;
    priority interface-priority ;
}
max-age seconds ;
traceoptions {
    file filename <files number> <no-stamp> <replace> <size maximum-file-size>
    <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
}
rsvp {
    rsvp-options ;
}
sap {
    sap-options ;
}
stp {
    bpdu-block-on-edge;
    bridge-priority priority ;
    disable;
    forward-delay seconds ;
    hello-time seconds ;
    interface interface-name {
        bpdu-timeout-action {
            alarm;
            block;
        }
        cost interface-cost ;
        disable;
        edge;
        mode (point-to-point | shared);
        no-root-port;
        priority interface-priority ;
    }
    max-age seconds ;
    traceoptions {
        file filename <files number> <no-stamp> <replace> <size maximum-file-size>
        <world-readable | no-world-readable>;
        flag flag <flag-modifier> <disable>;
    }
}
}
vrrp {
    vrrp-options ;
}

```

```

vstp {
  disable;
  force-version stp;
  interface interface-name {
    bpdu-timeout-action {
      alarm;
      block;
    }
    cost cost ;
    edge;
    mode (p2p | shared);
    no-root-port;
    priority interface-priority ;
  }
  vlan vlan-id {
    bridge-priority priority ;
    forward-delay seconds ;
    hello-time seconds ;
    interface interface-name {
      bpdu-timeout-action {
        alarm;
        block;
      }
      cost cost ;
      edge;
      mode (p2p | shared);
      no-root-port;
      priority interface-priority ;
    }
    max-age seconds ;
    traceoptions {
      file filename <files number > <no-stamp> <replace>
        <size maximum-file-size > <(world-readable | no-world-readable)>;
      flag flag <flag-modifier > <disable>;
    }
  }
}
}
}
}

```





## Chapter 13

# Routing-Instances Hierarchy

This chapter presents the complete **routing-instances** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **routing-instances** configuration hierarchy to configure routing instances. For configuration instructions, see the *JUNOS Software with Enhanced Services Design and Implementation Guide*.

For information about these **routing-instances** statements that are shared across Juniper Networks devices, see the *JUNOS Routing Protocols Configuration Guide*, the *JUNOS Services Interfaces Configuration Guide*, the *JUNOS Multicast Protocols Configuration Guide*, and the *JUNOS Network Interfaces Configuration Guide*.

This chapter contains the following sections:

- Routing-Instances Configuration Statement Hierarchy on page 149

## Routing-Instances Configuration Statement Hierarchy

---

To configure routing instances, use the following statements at the [edit **routing-instances**] hierarchy level.

Shared JUNOS statements in the **routing-instances** hierarchy are shown in normal font and are documented in the *JUNOS Routing Protocols Configuration Guide*, the *JUNOS Services Interfaces Configuration Guide*, the *JUNOS Multicast Protocols Configuration Guide*, and the *JUNOS Network Interfaces Configuration Guide*.

```
routing-instances {
  routing-instance-name {
    description text ;
    forwarding-options{
      accounting group-name {
        output {
          aggregate-export-interval seconds ;
          cflowd hostname {
            aggregation {
              autonomous-system;
              destination-prefix;
              protocol-port;
              source-destination-prefix {
                caida-compliant;
              }
            }
            source-prefix;
          }
        }
      }
    }
  }
}
```

```

    }
    autonomous-system-type (origin | peer);
    port port-number ;
    version number ;
  }
  flow-active-timeout seconds ;
  flow-inactive-timeout seconds ;
  interface interface-name {
    engine-id number ;
    engine-type number ;
    source-address address ;
  }
}
family {
  inet {
    filter (input input-filter-name | output output-filter-name );
  }
  inet6 {
    filter (input input-filter-name | output output-filter-name );
  }
  mpls {
    filter (input input-filter-name | output output-filter-name );
  }
}
helpers {
  bootp {
    client-response-ttl value ;
    description text ;
    interface interface-name {
      client-response-ttl value ;
      description text ;
      maximum-hop-count number ;
      minimum-wait-time seconds ;
      no-listen;
      server address {
        routing-instance [ value ];
      }
      vpn;
    }
    maximum-hop-count number ;
    minimum-wait-time seconds ;
    relay-agent-option;
    server address {
      routing-instance [ value ];
    }
    vpn;
  }
  domain {
    description text ;
    interface interface-name {
      description text ;
      no-listen;
      server address {
        routing-instance [ value ];
      }
    }
  }
}

```

```

    }
    server address {
        routing-instance [ value ];
    }
}
port port-number {
    description text ;
    interface interface-name {
        description text ;
        no-listen;
        server address {
            routing-instance [ value ];
        }
    }
    server address {
        routing-instance [ value ];
    }
}
tftp {
    description text ;
    interface interface-name {
        description text ;
        no-listen;
        server address {
            routing-instance [ value ];
        }
    }
    server address {
        routing-instance [ value ];
    }
}
traceoptions {
    file filename <files number > <match regular-expression >
    <size maximum-file-size >
    <world-readable | no-world-readable>;
    flag {
        address;
        all;
        bootp;
        config;
        domain;
        ifdb;
        io;
        main;
        port;
        rtsock;
        tftp;
        trace;
        ui;
        util;
    }
    level match-level ;
}
}
packet-capture {
    disable;
}

```

```

file filename <files number> <size maximum-file-size>
<world-readable | no-world-readable>;
maximum-capture-size size ;
}
sampling {
  disable;
  input {
    family {
      inet {
        max-packets-per-second seconds ;
        rate rate ;
        run-length number ;
      }
    }
  }
  output {
    cflowd hostname {
      aggregation;
      autonomous-system-type (origin | peer);
      (local-dump | no-local-dump);
      port port-number ;
      source-address address ;
      version number ;
    }
    file filename <disable> <files number> <size maximum-file-size>
    <stamp | no-stamp>
    <world-readable | no-world-readable>;
    flow-active-timeout seconds ;
    flow-inactive-timeout seconds ;
    interface interface-name {
      engine-id number ;
      engine-type number ;
      source-address address ;
    }
  }
  traceoptions {
    file filename <files number> <size maximum-file-size>
    <world-readable | no-world-readable>;
  }
}
}
instance-type (forwarding | l2vpn | no-forwarding | virtual-router | vpls | vrf);
interface interface-name ;
multicast-snooping-options {
  flood-groups [ value ];
  forwarding-cache {
    threshold (suppress | reuse) value value ;
    timeout minutes ;
  }
  options {
    syslog {
      level level | upto level ;
      mark seconds;
    }
  }
}
}
no-local-switching;

```

```

no-vrf-advertise;
protocols {
  bgp {
    bgp-configuration ;
  }
  esis {
    esis-configuration ;
  }
  isis {
    isis-configuration ;
  }
  l2vpn {
    l2vpn-configuration ;
  }
  ldp {
    ldp-configuration ;
  }
  msdp {
    msdp-configuration;
  }
  ospf {
    domain-id domain-id ;
    domain-vpn-tag number ;
    route-type-community (vendor | iana);
    ospf-configuration ;
  }
  ospf3 {
    domain-id domain-id ;
    domain-vpn-tag number ;
    route-type-community (vendor | iana);
    ospf3-configuration ;
  }
  pim {
    mdt {
      group-range multicast-prefix ;
      threshold {
        group group-address {
          source source-address {
            rate threshold-rate ;
          }
        }
      }
      tunnel-limit limit ;
    }
    pim-configuration ;
  }
  rip {
    rip-configuration ;
  }
  router-discovery {
    router-discovery-configuration ;
  }
}
provider-tunnel {
  pim-asm {
    group-address group-address ;
  }
}

```

```

}
rsvp-te {
    label-switched-path-template (default | lsp-template-name );
    static-lsp p2mp-lsp-name ;
}
selective {
    group group-prefix ;
    tunnel-limit number ;
}
}
route-distinguisher ( as-number : number | ip-address : number );
routing-options {
    aggregate {
        defaults {
            aggregate-options ;
        }
        route destination-prefix {
            aggregate-options ;
            policy policy-name ;
        }
    }
}
auto-export {
    (disable | enable);
    family {
        inet {
            disable;
            flow {
                (disable | enable);
                rib-group rib-group ;
            }
            multicast {
                (disable | enable);
                rib-group rib-group ;
            }
            unicast {
                (disable | enable);
                rib-group rib-group ;
            }
        }
        inet6 {
            disable;
            multicast {
                (disable | enable);
                rib-group rib-group ;
            }
            unicast {
                (disable | enable);
                rib-group rib-group ;
            }
        }
    }
}
iso {
    disable;
    unicast {
        (disable | enable);
        rib-group rib-group ;
    }
}

```

```

    }
  }
  traceoptions {
    file filename <files number > <no-stamp> <replace>
    <size maximum-file-size >
    <world-readable | no-world-readable>;
    flag flag <flag-modifier > <disable>;
  }
}
autonomous-system autonomous-system <loops number > {
  independent-domain;
}
fate-sharing {
  group group-name {
    cost value ;
    from address {
      to address ;
    }
  }
}
}
flow {
  route name {
    match {
      match-conditions ;
    }
    then {
      actions ;
    }
  }
  validation {
    traceoptions {
      file filename <files number > <no-stamp> <replace>
      <size maximum-file-size >
      <world-readable | no-world-readable>;
      flag flag <flag-modifier > <disable>;
    }
  }
}
forwarding-table {
  unicast-reverse-paths (active-paths | feasible-paths);
}
generate {
  defaults {
    generate-options ;
  }
  route destination-prefix {
    generate-options ;
    policy policy-name ;
  }
}
graceful-restart {
  disable;
  restart-duration duration ;
}
instance-export [ policy-names ];
instance-import [ policy-names ];

```

```

interface-routes {
  family (inet | inet6) {
    import [ import-policies ];
    export {
      lan;
      point-to-point;
    }
  }
  rib-group {
    inet group-name ;
    inet6 group-name ;
  }
}
martians {
  destination-prefix match-type <allow>;
}
maximum-paths path-limit <log-only | threshold value log-interval seconds
>;
maximum-prefixes prefix-limit <log-only | threshold value log-interval
seconds >;
multicast {
  flow-map map-name {
    bandwidth value {
      adaptive;
    }
  }
  forwarding-cache {
    timeout minutes {
      never;
    }
  }
  policy [ policy-name ];
  redundant-sources [ source-address ];
}
forwarding-cache {
  threshold (suppress | reuse) value value ;
  timeout minutes ;
}
interface interface-name {
  maximum-bandwidth limit ;
}
rpf-check-policy [ value ];
scope scope-name {
  interface [ interface-name ];
  prefix destination-prefix ;
}
scope-policy [ policy-name ];
ssm-groups [ addresses ];
ssm-map map-name {
  policy [ policy-name ];
  source [ source-address ];
}
}
multipath {
  vpn-unequal-cost {
    equal-external-internal;
  }
}

```



```

}
options {
    mark seconds ;
    syslog (level level | upto level );
}
resolution {
    rib routing-table-name {
        import [ policy-names ];
        resolution-ribs [ routing-table-names ];
    }
}
rib routing-table-name {
    aggregate {
        defaults {
            aggregate-options ;
        }
        route destination-prefix {
            aggregate-options ;
            policy policy-name ;
        }
    }
    generate {
        defaults {
            generate-options ;
        }
        route destination-prefix {
            generate-options ;
            policy policy-name ;
        }
    }
    martians {
        destination-prefix match-type <allow>;
    }
    maximum-paths path-limit <log-only | threshold value log-interval seconds
>;
    maximum-prefixes prefix-limit <log-only | threshold value log-interval
seconds >;
    multipath {
        vpn-unequal-cost {
            equal-external-internal;
        }
    }
    static {
        defaults {
            static-options ;
        }
        rib-group group-name ;
        route destination-prefix {
            bfd-liveness-detection {
                detection-time {
                    threshold milliseconds ;
                }
            }
            holddown-interval milliseconds;
            local-address ip-address ;
            minimum-interval milliseconds ;
            minimum-receive-interval milliseconds ;
        }
    }
}

```

```

        minimum-receive-ttl milliseconds ;
        multiplier number ;
        neighbor address ;
        transmit-interval {
            minimum-interval milliseconds ;
            threshold milliseconds ;
        }
        version (0 | 1);
    }
    lsp-next-hop nexthop {
        metric metric ;
        preference preference ;
    }
    next-hop [ nexthop ];
    qualified-next-hop ( address | interface-name ) {
        interface interface-name ;
        metric metric ;
        preference preference ;
    }
    static-options ;
}
}
}
router-id address ;
static {
    defaults {
        static-options ;
    }
    rib-group group-name ;
    route destination-prefix {
        bfd-liveness-detection {
            detection-time {
                threshold milliseconds ;
            }
            holddown-interval milliseconds;
            local-address ip-address ;
            minimum-interval milliseconds ;
            minimum-receive-interval milliseconds ;
            minimum-receive-ttl milliseconds ;
            multiplier number ;
            neighbor address ;
            transmit-interval {
                minimum-interval milliseconds ;
                threshold milliseconds ;
            }
            version (0 | 1);
        }
        lsp-next-hop nexthop {
            metric metric ;
            preference preference ;
        }
        next-hop [ nexthop ];
        qualified-next-hop ( address | interface-name ) {
            interface interface-name ;
            metric metric ;

```

```

        preference preference ;
    }
    static-options ;
}
}
}
vlan-id (all | none | vlan-id );
vlan-tags {
    inner vlan-id ;
    outer vlan-id ;
}
vrf-export [ policy-names ];
vrf-import [ policy-names ];
vrf-table-label;
vrf-target {
    export community-name ;
    import community-name ;
}
}
}
}
}

```



## Chapter 14

# Routing-Options Hierarchy

This chapter presents the complete **routing-options** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **routing-options** configuration hierarchy to configure protocol-independent routing properties. For configuration instructions, see the *JUNOS Software with Enhanced Services Design and Implementation Guide* and the *JUNOS Software Interfaces and Routing Configuration Guide*.

For information about these **routing-options** statements that are shared across Juniper Networks devices, see the *JUNOS Routing Protocols Configuration Guide*, the *JUNOS Services Interfaces Configuration Guide*, and the *JUNOS Multicast Protocols Configuration Guide*.

This chapter contains the following sections:

- Routing-Options Configuration Statement Hierarchy on page 161

## Routing-Options Configuration Statement Hierarchy

---

To configure routing options, use the following statements at the [edit **routing-options**] hierarchy level.

Shared JUNOS statements in the **routing-options** hierarchy are shown in normal font and are documented in the *JUNOS Routing Protocols Configuration Guide*, the *JUNOS Services Interfaces Configuration Guide*, and the *JUNOS Multicast Protocols Configuration Guide*.

```
routing-options {
  aggregate {
    defaults {
      aggregate-options ;
    }
    route destination-prefix {
      policy policy-name ;
      aggregate-options ;
    }
  }
  auto-export {
    (disable | enable);
    family {
      inet {
        disable;
```

```

    flow {
        (disable | enable);
        rib-group rib-group ;
    }
    multicast {
        (disable | enable);
        rib-group rib-group ;
    }
    unicast {
        (disable | enable);
        rib-group rib-group ;
    }
}
inet6 {
    disable;
    multicast {
        (disable | enable);
        rib-group rib-group ;
    }
    unicast {
        (disable | enable);
        rib-group rib-group ;
    }
}
iso {
    disable;
    unicast {
        (disable | enable);
        rib-group rib-group ;
    }
}
}
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
}
autonomous-system autonomous-system <loops number >;
bgp-orf-cisco-mode;
confederation confederation-autonomous-systems {
    members [ autonomous-system ];
}
dynamic-tunnels {
    tunnel-name {
        destination-networks prefix ;
        source-address address ;
        tunnel-type type-of-tunnel ;
    }
}
traceoptions {
    file filename <files number > <no-stamp> <replace> <size maximum-file-size
    >
    <world-readable | no-world-readable>;
    flag flag < flag-modifier > <disable>;
}
}

```

```

}
fate-sharing {
  group group-name {
    cost value ;
    from address {
      to address ;
    }
  }
}
flow {
  route name {
    match {
      match-conditions ;
    }
    then {
      actions ;
    }
  }
}
validation {
  traceoptions {
    file filename <files number > <no-stamp> <replace>
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag <flag-modifier > <disable>;
  }
}
forwarding-table {
  export [ policy-names ];
  (indirect-next-hop | no-indirect-next-hop);
  unicast-reverse-paths (active-paths | feasible-paths);
}
generate {
  defaults {
    generate-options ;
  }
  route destination-prefix {
    policy policy-name ;
    generate-options ;
  }
}
graceful-restart {
  disable;
  restart-duration duration ;
}
instance-export [ policy-names ];
instance-import [ policy-names ];
interface-routes {
  family (inet | inet6) {
    import [ import-policies ];
    export {
      lan;
      point-to-point;
    }
  }
}
rib-group {
  inet group-name ;
}

```

```

        inet6 group-name ;
    }
}
martians {
    destination-prefix match-type <allow>;
}
maximum-paths path-limit <log-only | threshold value log-interval seconds >;
maximum-prefixes prefix-limit <log-only | threshold value log-interval seconds >;
multicast {
    flow-map map-name {
        bandwidth value {
            adaptive;
        }
        forwarding-cache {
            timeout minutes {
                never;
            }
        }
        policy [ policy-name ];
        redundant-sources [ source-address ];
    }
    forwarding-cache {
        threshold (suppress | reuse) value value ;
        timeout minutes ;
    }
    interface interface-name {
        maximum-bandwidth limit ;
    }
    rpf-check-policy [ value ];
    scope scope-name {
        interface [ interface-name ];
        prefix destination-prefix ;
    }
    scope-policy [ policy-name ];
    ssm-groups [ addresses ];
    ssm-map map-name {
        policy [ policy-name ];
        source [ source-address ];
    }
    traceoptions {
        file filename <files number > <no-stamp> <replace> <size maximum-file-size
        >
        <world-readable | no-world-readable>;
        flag flag <flag-modifier > <disable>;
    }
}
options {
    mark seconds ;
    syslog (level level | upto level );
}
resolution {
    rib routing-table-name {
        import [ policy-names ];
        resolution-ribs [ routing-table-names ];
    }
    tracefilter [ policy-name ];
}

```



```

traceoptions {
    file filename <files number> <no-stamp> <replace> <size maximum-file-size>
    >
    <world-readable | no-world-readable>;
    flag flag <flag-modifier> <disable>;
}
}
rib routing-table-name {
    aggregate {
        defaults {
            aggregate-options ;
        }
        route destination-prefix {
            policy policy-name ;
            aggregate-options ;
        }
    }
}
generate {
    defaults {
        generate-options ;
    }
    route destination-prefix {
        policy policy-name ;
        generate-options ;
    }
}
martians {
    destination-prefix match-type <allow>;
}
maximum-paths path-limit <log-only | threshold value log-interval seconds>;
maximum-prefixes prefix-limit <log-only | threshold value log-interval
seconds>;
static {
    defaults {
        static-options ;
    }
    rib-group group-name ;
    route destination-prefix {
        bfd-liveness-detection {
            detection-time {
                threshold milliseconds ;
            }
            holddown-interval milliseconds;
            local-address ip-address ;
            minimum-interval milliseconds ;
            minimum-receive-interval milliseconds ;
            minimum-receive-ttl milliseconds ;
            multiplier number ;
            neighbor address ;
            transmit-interval {
                minimum-interval milliseconds ;
                threshold milliseconds ;
            }
        }
        version (0 | 1);
    }
}
lsp-next-hop nexthop '{

```

```

        metric metric ;
        preference preference ;
    }
    next-hop [ next-hop ];
    qualified-next-hop ( address | interface-name ) {
        interface interface-name ;
        metric metric ;
        preference preference ;
    }
    static-options ;
}
}
}
rib-groups {
    group-name {
        export-rib [ group-names ];
        import-policy [ policy-names ];
        import-rib [ group-names ];
    }
}
route-distinguished-id address ;
route-record;
router-id address ;
source-routing (ip | ipv6);
static {
    defaults {
        static-options ;
    }
    rib-group group-name ;
    route destination-prefix {
        bfd-liveness-detection {
            detection-time {
                threshold milliseconds ;
            }
            holddown-interval milliseconds;
            local-address ip-address ;
            minimum-interval milliseconds ;
            minimum-receive-interval milliseconds ;
            minimum-receive-ttl milliseconds ;
            multiplier number ;
            neighbor address ;
            transmit-interval {
                minimum-interval milliseconds ;
                threshold milliseconds ;
            }
            version (0 | 1);
        }
        lsp-next-hop nexthop '{
            metric metric ;
            preference preference ;
        }
        next-hop [ next-hop ];
        qualified-next-hop ( address | interface-name ) {
            interface interface-name ;
            metric metric ;

```

```

        preference preference ;
    }
    static-options ;
}
}
topologies {
    family (inet | inet6) {
        topology topology-name;
    }
}
traceoptions {
    file name <files number > <no-stamp> <replace> <size maximum-file-size >
    <world-readable | no-world-readable>;
    flag flag <flag-modifier > <disable>;
}
}

```



## Chapter 15

# Schedulers Hierarchy and Statements

This chapter presents the complete **schedulers** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. The chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **schedulers** configuration hierarchy to determine the day and time when security policies are in effect. For configuration instructions, see the *JUNOS Software Security Configuration Guide*.

This chapter contains the following sections:

- Schedulers Configuration Statement Hierarchy on page 169

### Schedulers Configuration Statement Hierarchy

---

To configure security policy schedulers, use the following statements at the [edit **schedulers**] hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

```
schedulers {
  scheduler scheduler-name {
    daily (all-day | exclude | start-time time stop-time time);
    friday {
      (all-day | exclude | start-time time stop-time time);
    }
    monday {
      (all-day | exclude | start-time time stop-time time);
    }
    saturday {
      (all-day | exclude | start-time time stop-time time);
    }
    start-date date-time stop-date date-time;
    sunday {
      (all-day | exclude | start-time time stop-time time);
    }
    thursday {
      (all-day | exclude | start-time time stop-time time);
    }
    tuesday {
      (all-day | exclude | start-time time stop-time time);
    }
  }
}
```

```

        wednesday {
            (all-day | exclude | start-time time stop-time time);
        }
    }
}

```

## all-day

---

**Syntax** all-day;

**Hierarchy Level** [edit schedulers scheduler *scheduler-name* daily],  
 [edit schedulers scheduler *scheduler-name* friday],  
 [edit schedulers scheduler *scheduler-name* monday],  
 [edit schedulers scheduler *scheduler-name* saturday],  
 [edit schedulers scheduler *scheduler-name* sunday],  
 [edit schedulers scheduler *scheduler-name* tuesday],  
 [edit schedulers scheduler *scheduler-name* thursday],  
 [edit schedulers scheduler *scheduler-name* wednesday]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Schedule the security policy to be in effect for an entire day.

This statement is supported on J-series and SRX-series devices.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.



**NOTE:** A schedule set for a specific time overrides a schedule set with the **all-day** statement. Use the **all-day** statement to specify that a security policy be in effect for the whole day

---

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**daily**

---

**Syntax**    `daily {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Schedule the security policy to be in effect every day of the week.

If you create a daily schedule with the **daily** statement and also use the **friday**, **monday**, **saturday**, **sunday**, **tuesday**, **thursday**, and **wednesday** statement in the schedule, the parameters specified for a specific day (for example, Friday using the **friday** statement) override the schedule set with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## exclude

---

**Syntax**    exclude;

**Hierarchy Level**    [edit schedulers scheduler *scheduler-name* daily],  
                           [edit schedulers scheduler *scheduler-name* friday],  
                           [edit schedulers scheduler *scheduler-name* monday],  
                           [edit schedulers scheduler *scheduler-name* saturday],  
                           [edit schedulers scheduler *scheduler-name* sunday],  
                           [edit schedulers scheduler *scheduler-name* tuesday],  
                           [edit schedulers scheduler *scheduler-name* thursday],  
                           [edit schedulers scheduler *scheduler-name* wednesday]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Exclude a specified day from the schedule.

Use the **exclude** statement to exclude a day from a daily schedule created with the **daily** statement. You cannot use the **exclude** statement for a particular day unless it is in conjunction with the **daily** statement in a schedule.

This statement is supported on J-series and SRX-series devices.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                       security-control—To add this statement to the configuration.



## friday

---

**Syntax**    `friday {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify a schedule for every Friday.

If you use the **friday** statement in conjunction with the **daily** statement for a schedule, the parameters set for the **friday** statement override the parameters set for the **daily** statement.

Use the **exclude** option to exclude Friday from a daily schedule configured with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## monday

---

**Syntax**    `monday {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify a schedule for every Monday.

If you use the **monday** statement in conjunction with the **daily** statement for a schedule, the parameters set for the **monday** statement override the parameters set for the **daily** statement.

Use the **exclude** option to exclude Monday from a daily schedule configured with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## saturday

---

**Syntax**    `saturday {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify a schedule for every Saturday.

If you use the **saturday** statement in conjunction with the **daily** statement for a schedule, the parameters set for the **saturday** statement override the parameters set for the **daily** statement.

Use the **exclude** option to exclude Saturday from a daily schedule configured with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## scheduler

---

**Syntax** scheduler *scheduler-name* {  
     daily (all-day | exclude | start-time *time* stop-time *time* );  
     friday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
     monday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
     saturday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
     start-date *date-time* stop-date *date-time* ;  
     sunday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
     thursday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
     tuesday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
     wednesday {  
         (all-day | exclude | start-time *time* stop-time *time* );  
     }  
 }

**Hierarchy Level** [edit schedulers]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Create or modify a schedule that defines when security policies are in effect.

You configure a schedule to start at a specific date and time or start on a recurrent basis.

This statement is supported on J-series and SRX-series devices.

**Options** *scheduler-name* —Name of the schedule. The schedule name must consist of 1 to 63 characters that can be letters, numbers, dashes, and underscores and can begin with a number or letter.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## schedulers

---

<b>Syntax</b>	<code>schedulers { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure schedules for security policies that allow you to control network traffic flow and enforce network security.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## start-date

---

<b>Syntax</b>	<code>start-date <i>date-time</i> ;</code>
<b>Hierarchy Level</b>	<p>[edit schedulers],</p> <p>[edit schedulers scheduler <i>scheduler-name</i> ]</p>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the time, day, month, and year that the schedule starts.</p> <p>Specifying the year is optional. If no year is specified, the schedule applies to the current year and all subsequent years. If the year is specified in either the <b>start-date</b> or <b>stop-date</b> statement, that year is used for both statements.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>date-time</i> —Use the format [ <i>yyyy -</i> ] <i>mm - dd . hh . mm</i> to specify the year, month, day, hour, and minutes.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## start-time

---

**Syntax**    `start-time time ;`

**Hierarchy Level**    [edit schedulers scheduler *scheduler-name* daily],  
                           [edit schedulers scheduler *scheduler-name* friday],  
                           [edit schedulers scheduler *scheduler-name* monday],  
                           [edit schedulers scheduler *scheduler-name* saturday],  
                           [edit schedulers scheduler *scheduler-name* sunday],  
                           [edit schedulers scheduler *scheduler-name* tuesday],  
                           [edit schedulers scheduler *scheduler-name* thursday],  
                           [edit schedulers scheduler *scheduler-name* wednesday]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the time that a schedule starts for a specified day.

If you specify a starting time for a daily schedule with the **daily** statement and also include the the **friday**, **monday**, **saturday**, **sunday**, **tuesday**, **thursday**, and **wednesday** statements in the schedule, the starting time specified for a specific day (for example, Friday using the **friday** statement) overrides the starting time set with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    *time* —Use the 24-hour format ( *hh* : *mm* : *ss* ) to specify the hours, minutes, and seconds.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                       security-control—To add this statement to the configuration.

## stop-date

---

<b>Syntax</b>	<code>stop-date <i>date-time</i> ;</code>
<b>Hierarchy Level</b>	[edit schedulers], [edit schedulers scheduler <i>scheduler-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the time, day, month, and year that the schedule ends.</p> <p>Specifying the year is optional. If no year is specified, the schedule applies to the current year and all subsequent years. If the year is specified in either the <b>start-date</b> or <b>stop-date</b> statement, that year is used for both statements.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>date-time</i> —Use the format [ <i>yyyy</i> -] <i>mm</i> - <i>dd</i> . <i>hh</i> . <i>mm</i> to specify the year, month, day, hour, and minutes.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## stop-time

---

**Syntax** `stop-time time ;`

**Hierarchy Level** [edit schedulers scheduler *scheduler-name* daily],  
 [edit schedulers scheduler *scheduler-name* friday],  
 [edit schedulers scheduler *scheduler-name* monday],  
 [edit schedulers scheduler *scheduler-name* saturday],  
 [edit schedulers scheduler *scheduler-name* sunday],  
 [edit schedulers scheduler *scheduler-name* tuesday],  
 [edit schedulers scheduler *scheduler-name* thursday],  
 [edit schedulers scheduler *scheduler-name* wednesday]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the time that a schedule stops for a specified day.

If you specify a stop time for a daily schedule with the **daily** statement and also include the the **friday**, **monday**, **saturday**, **sunday**, **tuesday**, **thursday**, and **wednesday** statements in the schedule, the stop time specified for a specific day (for example, Friday using the **friday** statement) overrides the stop time set with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options** *time* —Use the 24-hour format ( *hh* : *mm* : *ss* ) to specify the hours, minutes, and seconds.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.



## sunday

---

<b>Syntax</b>	sunday (all-day   exclude   start-time <i>time</i> stop-time <i>time</i> );
<b>Hierarchy Level</b>	[edit schedulers scheduler <i>scheduler-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a schedule for every Sunday.</p> <p>If you use the <b>sunday</b> statement in conjunction with the <b>daily</b> statement for a schedule, the parameters set for the <b>sunday</b> statement override the parameters set for the <b>daily</b> statement.</p> <p>Use the <b>exclude</b> option to exclude Sunday from a daily schedule configured with the <b>daily</b> statement.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## thursday

---

**Syntax**    `thursday {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify a schedule for every Thursday.

If you use the **thursday** statement in conjunction with the **daily** statement for a schedule, the parameters set for the **thursday** statement override the parameters set for the **daily** statement.

Use the **exclude** option to exclude Thursday from a daily schedule configured with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## tuesday

---

**Syntax**    `tuesday {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify a schedule for every Tuesday.

If you use the **tuesday** statement in conjunction with the **daily** statement for a schedule, the parameters set for the **tuesday** statement override the parameters set for the **daily** statement.

Use the **exclude** option to exclude Tuesday from a daily schedule configured with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## wednesday

---

**Syntax**    `wednesday {  
                  (all-day | exclude | start-time time stop-time time );  
                  }`

**Hierarchy Level**    `[edit schedulers scheduler scheduler-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify a schedule for every Wednesday.

If you use the **wednesday** statement in conjunction with the **daily** statement for a schedule, the parameters set for the **wednesday** statement override the parameters set for the **daily** statement.

Use the **exclude** option to exclude Wednesday from a daily schedule configured with the **daily** statement.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## Chapter 16

# Security Hierarchy and Statements

This chapter presents the complete **security** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **security** configuration hierarchy to configure the rules for the transit traffic and the actions that need to take place on the traffic as it passes through the firewall and to monitor the traffic attempting to cross from one security zone to another. For configuration instructions, see the *JUNOS Software Security Configuration Guide*.

For information about the following **security** statements that are shared across Juniper Networks devices—see the *JUNOS System Basics Configuration Guide*.

This chapter contains the following sections:

- Security Configuration Statement Hierarchy on page 185
- no-allow-icmp-without-flow on page 404
- no-enable-all-qmodules on page 404
- no-enable-packet-pool on page 405
- no-log-errors on page 405
- no-policy-lookup-cache on page 405
- no-reset-on-policy on page 406

## Security Configuration Statement Hierarchy

---

To configure security rules, actions, and zones, use the following statements at the **[edit security]** hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **security** hierarchy are shown in normal font and are documented in the *JUNOS System Basics Configuration Guide*.

```
security {  
  alg {  
    dns {
```

```

    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}
ftp {
    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}
h323 {
    application-screen {
        message-flood {
            gatekeeper threshold rate;
        }
        unknown-message {
            permit-nat-applied;
            permit-routed;
        }
    }
    disable;
    endpoint-registration-timeout seconds;
    media-source-port-any;
    traceoptions {
        flag {
            all <detail | extensive | terse>;
            cc <detail | extensive | terse>;
            h225-asn1 <detail | extensive | terse>;
            h245 <detail | extensive | terse>;
            h245-asn1 <detail | extensive | terse>;
            q931 <detail | extensive | terse>;
            ras <detail | extensive | terse>;
            ras-asn1 <detail | extensive | terse>;
        }
    }
}
mgcp {
    application-screen {
        connection-flood threshold rate;
        message-flood threshold rate;
        unknown-message {
            permit-nat-applied;
            permit-routed;
        }
    }
    disable;
    inactive-media-timeout seconds;
    maximum-call-duration minutes;
    traceoptions {
        flag {
            all <extensive>;
            call <extensive>;
        }
    }
}

```

```

        cc <extensive>;
        decode <extensive>;
        error <extensive>;
        nat <extensive>;
        packet <extensive>;
        rm <extensive>;
    }
}
transaction-timeout seconds;
}
msrpc {
    disable;
    traceoptions {
        flag {
            all <extensive>
        }
    }
}
pptp {
    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}
real {
    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}
rsh {
    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}
rtsp {
    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}
sccp {
    application-screen {
        call-flood threshold rate;
        unknown-message {
            permit-nat-applied;
            permit-routed;
        }
    }
}

```

```

    }
  }
  disable;
  inactive-media-timeout seconds;
  traceoptions {
    flag {
      all <extensive>;
      call <extensive>;
      cc <extensive>;
      cli <extensive>;
      decode <extensive>;
      error <extensive>;
      init <extensive>;
      nat <extensive>;
      rm <extensive>;
    }
  }
}
sip {
  application-screen {
    protect {
      deny {
        all | destination-ip address;
        timeout seconds;
      }
    }
    unknown-message {
      permit-nat-applied;
      permit-routed;
    }
  }
  c-timeout minutes;
  disable;
  disable-call-id-hiding;
  inactive-media-timeout seconds;
  maximum-call-duration minutes;
  retain-hold-resource;
  t1-interval milliseconds;
  t4-interval seconds;
  traceoptions {
    flag {
      all <detail | extensive | terse>;
      call <detail | extensive | terse>;
      cc <detail | extensive | terse>;
      nat <detail | extensive | terse>;
      parser <detail | extensive | terse>;
      rm <detail | extensive | terse>;
    }
  }
}
sql {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}

```



```

    }
  }
  sunrpc {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
  talk {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
  tftp {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
}
authentication-key-chains {
  key-chain key-chain-name {
    description text ;
    tolerance seconds ;
  }
}
firewall-authentication {
  traceoptions {
    flag {
      all <detail | extensive | terse>;
      authentication <detail | extensive | terse>;
      proxy <detail | extensive | terse>;
    }
  }
}
flow {
  aging {
    early-ageout seconds;
    high-watermark percent;
    low-watermark percent;
  }
  allow-dns-reply;
  route-change-timeout seconds;
  syn-flood-protection-mode (syn-cookie | syn-proxy);
  tcp-mss {
    all-tcp {
      mss value;
    }
  }
  gre-in {

```

```

        mss value;
    }
    gre-out {
        mss value;
    }
    ipsec-vpn {
        mss value;
    }
}
tcp-session {
    no-sequence-check;
    no-syn-check;
    no-syn-check-in-tunnel;
    rst-invalidate-session;
    rst-sequence-check;
    tcp-initial-timeout seconds;
}
traceoptions {
    file filename <files number > <match regular-expression>
    <size maximum-file-size> <world-readable | no-world-readable>;
    flag flag;
}
}
forwarding-options {
    family {
        inet6 {
            mode packet-based;
        }
        iso {
            mode packet-based;
        }
        mpls {
            mode packet-based;
        }
    }
}
}
idp {
    active-policy policy-name;
    custom-attack attack-name {
        attack-type {
            anomaly {
                direction (any | client-to-server | server-to-client);
                service service-name;
                shellcode (all | intel | no-shellcode | sparc);
                test test-condition;
            }
            chain {
                expression boolean-expression;
                member member-name {
                    attack-type {
                        (anomaly | signature);
                    }
                }
            }
            order;
            protocol-binding {
                application application-name;
            }
        }
    }
}

```

```

icmp;
ip {
    protocol-number transport-layer-protocol-number;
}
rpc {
    program-number rpc-program-number;
}
tcp {
    minimum-port port-number maximum-port port-number;
}
udp {
    minimum-port port-number maximum-port port-number;
}
}
reset;
scope (session | transaction);
}
signature {
    context context-name;
    direction (any | client-to-server | server-to-client);
    negate;
    pattern signature-pattern;
    protocol {
        icmp {
            code {
                match (equal | greater-than | less-than | not-equal);
                value code-value;
            }
            data-length {
                match (equal | greater-than | less-than | not-equal);
                value data-length;
            }
            identification {
                match (equal | greater-than | less-than | not-equal);
                value identification-value;
            }
            sequence-number {
                match (equal | greater-than | less-than | not-equal);
                value sequence-number;
            }
            type {
                match (equal | greater-than | less-than | not-equal);
                value type-value;
            }
        }
    }
}
ip {
    destination {
        match (equal | greater-than | less-than | not-equal);
        value hostname;
    }
    identification {
        match (equal | greater-than | less-than | not-equal);
        value identification-value;
    }
    ip-flags {

```

```

    (df | no-df);
    (mf | no-mf);
    (rb | no-rb);
}
protocol {
    match (equal | greater-than | less-than | not-equal);
    value transport-layer-protocol-id;
}
source {
    match (equal | greater-than | less-than | not-equal);
    value hostname;
}
tos {
    match (equal | greater-than | less-than | not-equal);
    value type-of-service-in-decimal;
}
total-length {
    match (equal | greater-than | less-than | not-equal);
    value total-length-of-ip-datagram;
}
ttl {
    match (equal | greater-than | less-than | not-equal);
    value time-to-live;
}
}
tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value tcp-data-length;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port;
    }
    header-length {
        match (equal | greater-than | less-than | not-equal);
        value header-length;
    }
    mss {
        match (equal | greater-than | less-than | not-equal);
        value maximum-segment-size;
    }
    option {
        match (equal | greater-than | less-than | not-equal);
        value tcp-option;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number;
    }
    source-port {

```

```

        match (equal | greater-than | less-than | not-equal);
        value source-port;
    }
    tcp-flags {
        (ack | no-ack);
        (fin | no-fin);
        (psh | no-psh);
        (r1 | no-r1);
        (r2 | no-r2);
        (rst | no-rst);
        (syn | no-syn);
        (urg | no-urg);
    }
    urgent-pointer {
        match (equal | greater-than | less-than | not-equal);
        value urgent-pointer;
    }
    window-scale {
        match (equal | greater-than | less-than | not-equal);
        value window-scale-factor;
    }
    window-size {
        match (equal | greater-than | less-than | not-equal);
        value window-size;
    }
}
udp {
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value data-length;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port;
    }
}
}
protocol-binding {
    application application-name;
    icmp;
    ip {
        protocol-number transport-layer-protocol-number;
    }
    rpc {
        program-number rpc-program-number;
    }
    tcp {
        minimum-port port-number maximum-port port-number;
    }
    udp {
        minimum-port port-number maximum-port port-number;
    }
}

```

```

    }
  }
  regexp regular-expression;
  shellcode (all | intel | no-shellcode | sparc);
}
}
recommended-action (close | close-client | close-server | drop | drop-packet
| ignore | none);
severity (critical | info | major | minor | warning);
time-binding {
  count count-value;
  scope (destination | peer | source);
}
}
custom-attack-group custom-attack-group-name {
  group-members [attack-group-name | attack-name];
}
dynamic-attack-group dynamic-attack-group-name {
  filters {
    category {
      values [list-of-values];
    }
    direction {
      values [any | client-to-server | exclude-any | exclude-client-to-server |
exclude-server-to-client | server-to-client];
    }
    false-positives {
      values [frequently | occasionally | rarely | unknown];
    }
    performance {
      values [fast | normal | slow | unknown];
    }
    products {
      values [list-of-values];
    }
    recommended;
    service {
      values [list-of-values];
    }
    severity {
      values [critical | info | major | minor | warning];
    }
    type {
      values [anomaly | signature];
    }
  }
}
idp-policy policy-name {
  rulebase-exempt {
    rule rule-name {
      description text;
      match {
        attacks {
          custom-attacks [attack-name];
          predefined-attack-groups [attack-name];
          predefined-attacks [attack-name];
        }
      }
    }
  }
}

```

```

    }
    destination-address [address-name];
    destination-except [address-name];
    from-zone zone-name;
    source-address [address-name];
    source-except [address-name];
    to-zone zone-name;
  }
}
}
rulebase-ips {
  rule rule-name {
    description text;
    match {
      attacks {
        custom-attacks [ attack-name ];
        predefined-attack-groups [ attack-name ];
        predefined-attacks [ attack-name ];
      }
      destination-address [ address-name ];
      destination-except [ address-name ];
      from-zone zone-name;
      source-address [ address-name ];
      source-except [ address-name ];
      to-zone zone-name;
    }
    terminal;
    then {
      action {
        (close-client | close-client-and-server | close-server |
        drop-connection | drop-packet | ignore-connection |
        mark-diffserv value | no-action | recommended);
      }
      ip-action {
        (ip-block | ip-close | ip-notify);
        log;
        target (destination-address | service | source-address |
        source-zone | zone-service);
        timeout seconds;
      }
      notification {
        log-attacks {
          alert (yes | no);
        }
      }
      severity (critical | info | major | minor | warning);
    }
  }
}
}
security-package {
  automatic {
    enable;
    interval hours;
    start-time start-time;
  }
}

```

```

    url url-name;
}
sensor-configuration {
    application-identification {
        application-system-cache;
        application-system-cache-timeout value;
        check-first-session;
        disable;
        max-packet-memory value;
        max-sessions value;
        max-tcp-session-packet-memory value;
        max-udp-session-packet-memory value;
    }
    detector {
        protocol-name protocol-name {
            tunable-name tunable-name {
                tunable-value protocol-value;
            }
        }
    }
}
flow {
    (allow-icmp-without-flow | no-allow-icmp-without-flow);
    (log-errors | no-log-errors);
    max-timers-poll-ticks value;
    reject-timeout value;
    (reset-on-policy | no-reset-on-policy);
}
global {
    (enable-all-qmodules | no-enable-all-qmodules);
    (enable-packet-pool | no-enable-packet-pool);
    (policy-lookup-cache | no-policy-lookup-cache);
}
ips {
    detect-shellcode;
    ignore-regular-expression;
    log-supercede-min minimum-value;
    pre-filter-shellcode;
    process-ignore-s2c;
    process-override;
    process-port port-number;
}
log {
    cache-size size;
    suppression {
        disable;
        include-destination-address;
        max-logs-operate value;
        max-time-report value;
        start-log value;
    }
}
re-assembler {
    ignore-mem-overflow;
    max-flow-mem value;
    max-packet-mem value;
}

```



```

    }
  }
  traceoptions {
    file filename {
      <files number>;
      <match regular-expression>;
      <size maximum-file-size>;
      <world-readable | no-world-readable>;
    }
    flag all;
    level (all | error | info | notice | verbose | warning);
    no-remote-trace;
  }
}
ike {
  gateway gateway-name {
    address [(ip-address | hostname)] |
    dead-peer-detection {
      always-send;
      interval seconds;
      threshold number;
    }
    dynamic {
      connections-limit number;
      distinguished-name {
        container container-string;
        wildcard wildcard-string;
      }
      hostname domain-name;
      ike-user-type (group-ike-id | shared-ike-id);
      inet ip-address;
      user-at-hostname user-at-hostname;
    }
    external-interface external-interface-name;
    ike-policy policy-name;
    local-identity (distinguished-name string | hostname hostname
    | inet ipv4-ip-address | user-at-hostname e-mail-address);
    nat-keepalive seconds;
    no-nat-traversal;
    xauth {
      access-profile profile-name;
    }
  }
}
policy policy-name {
  certificate {
    local-certificate certificate-id;
    peer-certificate-type (pkcs7 | x509-signature);
    trusted-ca (ca-index | use-all);
  }
  description description;
  mode (aggressive | main);
  pre-shared-key (ascii-text | hexadecimal);
  proposal-set <basic | compatible | standard>;
}
proposal proposal-name {

```

```

    authentication-algorithm (md5 | sha1 | sha-256);
    authentication-method (dsa-signatures | pre-shared-keys | rsa-signatures);
    description description;
    dh-group (group1 | group2 | group5);
    encryption-algorithm (des-cbc | 3des-cbc | aes-128-cbc | aes-192-cbc
    | aes-256-cbc);
  }
  respond-bad-spi number;
  traceoptions {
    file filename {
      <files number>;
      <match regular-expression>;
      <size maximum-file-size>;
    }
    flag {
      all;
      certificates;
      database;
      general;
      ike;
      parse;
      policy-manager;
      routing-socket;
      timer;
      snmp;
    }
  }
}
ipsec {
  policy policy-name {
    description description;
    perfect-forward-secrecy keys (group1 | group2 | group5);
    proposal-set (basic | compatible | standard);
  }
  proposal proposal-name {
    description description;
    encryption-algorithm (des-cbc | 3des-cbc | aes-128-cbc | aes-192-cbc
    | aes-256-cbc);
    lifetime-kilobytes kilobytes;
    lifetime-seconds seconds;
    protocol (ah | esp);
  }
  vpn vpn-name {
    bind-interface interface-name;
    df-bit (clear | copy | set);
    establish-tunnels (immediately | on-traffic);
    ike {
      gateway gateway-name;
      idle-time seconds;
      install-interval seconds;
      ipsec-policy ipsec-policy-name;
      no-anti-replay;
      proxy-identity {
        local ipv4-prefix;
        remote ipv4-prefix;
      }
    }
  }
}

```

```

        service service-name;
    }
}
manual {
    authentication {
        algorithm (hmac-md5-96 | hmac-sha1-96);
        key (ascii-text key | hexadecimal key);
    }
    encryption {
        algorithm (3des-cbc | aes-128-cbc | aes-192-cbc
        | aes-256-cbc | des-cbc);
        key (ascii-text key | hexadecimal key);
    }
    external-interface external-interface-name;
    gateway ip-address;
    protocol (ah | esp);
    spi spi value;
}
vpn-monitor {
    destination-ip ip-address;
    optimized;
    source-interface interface-name;
}
}
vpn-monitor-options {
    interval seconds;
    threshold number;
}
traceoptions {
    flag {
        all;
        next-hop-tunnel-binding;
        packet-drops;
        packet-processing;
        security-associations;
    }
}
}
nat {
    destination {
        pool pool-name {
            address <ip-address> (to ip-address | port port-number):
            routing-instance routing-instance-name;
        }
        rule-set rule-set-name {
            from interface [interface-name] |
            routing-instance [routing-instance-name] | zone [zone-name];
            rule rule-name {
                match {
                    destination-address destination-address;
                    destination-port port-number;
                    source-address [source-address];
                }
                then {
                    destination-nat (off | pool pool-name);
                }
            }
        }
    }
}

```

```

    }
  }
}
proxy-arp {
  interface interface-name {
    address ip-address to ip-address;
  }
}
source {
  address-persistent;
  pool pool-name {
    address ip-address to ip-address;
    host-address-base ip-address;
    overflow-pool (interface | pool-name);
    port no-translation | range high ip-address low ip-address;
    routing-instance routing-instance-name;
  }
  pool-utilization-alarm {
    clear-threshold threshold-value;
    raise-threshold threshold-value;
  }
  rule-set rule-set-name {
    from interface [interface-name] |
    routing-instance [routing-instance-name] | zone [zone-name];
    rule rule-name {
      match {
        destination-address [destination-address];
        source-address [source-address];
      }
      then {
        source-nat (off | interface | pool pool-name);
      }
    }
    to interface [interface-name] |
    routing-instance [routing-instance-name] | zone [zone-name];
  }
}
static {
  rule-set rule-set-name {
    from interface [interface-name] |
    routing-instance [routing-instance-name] | zone [zone-name];
    rule rule-name {
      match {
        destination-address [destination-address];
      }
      then {
        static-nat prefix <addr-prefix>
        <routing-instance routing-instance-name>;
      }
    }
  }
}
traceoptions {
  file filename {

```

```

    <files number>;
    <match regular-expression>;
    <size maximum-file-size>;
    <world-readable | no-world-readable>;
}
flag {
    all;
    destination-nat-pfe;
    destination-nat-re;
    destination-nat-rt;
    source-nat-pfe;
    source-nat-re;
    source-nat-rt;
    static-nat-pfe;
    static-nat-re;
    static-nat-rt;
}
no-remote-trace;
}
}
nat {
    destination-nat destination-nat-name {
        address prefix <port port-number>;
        address-range high ip-address low ip-address;
    }
    interface interface-name {
        allow-incoming;
        proxy-arp {
            address prefix;
            address-range high ip-address low ip-address;
        }
        source-nat {
            pool pool-name {
                address prefix;
                address-range high ip-address low ip-address;
                allow-incoming;
                host-address-low ip-address;
                no-port-translation;
                overflow-pool (interface | pool-name );
            }
        }
        static-nat ip-prefix {
            host ip-prefix;
            virtual-router vr-name;
        }
    }
}
source-nat {
    address-persistent;
    pool-set pool-set-name {
        pool pool-name;
    }
    pool-utilization-alarm {
        clear-threshold clear-threshold;
        raise-threshold raise-threshold;
    }
}

```

```

    }
    traceoptions {
        file filename {
            <files number>;
            <match regular-expression>;
            <size maximum-file-size>;
            <world-readable | no-world-readable>;
        }
        flag {
            all;
            configuration;
            flow;
            routing-protocol;
            routing-socket;
        }
    }
}
pki {
    auto-re-enrollment {
        certificate-id certificate-id-name {
            ca-profile-name ca-profile-name;
            challenge-password password;
            re-enroll-trigger-time-percentage percentage;
            re-generate-keypair;
        }
    }
    ca-profile ca-profile-name {
        administrator {
            e-mail-address e-mail-address;
        }
        ca-identity ca-identity;
        enrollment {
            retry number;
            retry-interval seconds ;
            url url-name;
        }
        revocation-check {
            crl {
                disable {
                    on-download-failure;
                }
                refresh-interval hours;
                url url-name;
            }
            disable;
        }
    }
    traceoptions {
        file filename <files number> <match regular-expression>
        <size maximum-file-size> <world-readable | no-world-readable>;
        flag flag;
    }
}
policies {
    default-policy {

```

```

    (deny-all | permit-all);
}
from-zone zone-name to-zone zone-name {
  policy policy-name {
    match {
      application [application-name-or-set];
      destination-address {
        address-name;
      }
      source-address {
        address-name;
      }
    }
    scheduler-name scheduler-name;
    then {
      count {
        alarm {
          per-minute-threshold number;
          per-second-threshold number;
        }
      }
      (deny | reject);
      permit {
        application-services (wx-redirect | wx-reverse-redirect);
        destination-address {
          drop-translated;
          drop-untranslated;
        }
        destination-nat destination-name;
        firewall-authentication {
          pass-through {
            access-profile profile-name>;
            client-match match-name>;
            web-redirect;
          }
          web-authentication {
            client-match user-or-group;
          }
        }
        source-nat (pool pool-name | pool-set pool-set-name | interface);
        tunnel {
          ipsec-vpn vpn-name;
          pair-policy pair-policy;
        }
      }
      log {
        session-close;
        session-init;
      }
    }
  }
}
policy-rematch;
traceoptions {
  file filename <files number> <match regular-express>

```

```

        <size maximum-file-size> <world-readable | no-world-readable>;
        flag flag;
    }
}
screen {
    ids-option {
        screen-name {
            alarm-without-drop;
            icmp {
                flood {
                    threshold number;
                }
                fragment;
                ip-sweep {
                    threshold number;
                }
                large;
                ping-death;
            }
        }
        ip {
            bad-option;
            block-frag;
            loose-source-route-option;
            record-route-option;
            security-option;
            source-route-option;
            spoofing;
            stream-option;
            strict-source-route-option;
            tear-drop;
            timestamp-option;
            unknown-protocol;
        }
        limit-session {
            destination-ip-based number;
            source-ip-based number;
        }
        tcp {
            fin-no-ack;
            land;
            port-scan {
                threshold number;
            }
            syn-ack-ack-proxy {
                threshold number;
            }
            syn-fin;
            syn-flood {
                alarm-threshold number;
                attack-threshold number;
                destination-threshold number;
                source-threshold number;
                timeout seconds;
            }
            syn-frag;
            tcp-no-flag;
        }
    }
}

```



```

        winnuke;
    }
    udp {
        flood {
            threshold number;
        }
    }
}
traceoptions {
    file filename <files number> <match regular-expression>
    <size maximum-file-size> <world-readable | no-world-readable>;
    flag flag;
}
}
ssh-known-hosts {
    fetch-from-server fetch-from-server;
    host hostname {
        dsa-key base64-encoded-dsa-key;
        rsa-key base64-encoded-dsa-key;
        rsa1-key base64-encoded-dsa-key;
    }
    load-key-file key-file;
}
traceoptions {
    file filename {
        <files number>;
        <match regular-expression>;
        <size maximum-file-size>;
        <world-readable | no-world-readable>;
    }
    flag flag;
    no-remote-trace;
    rate-limit rate;
}
zones {
    functional-zone {
        management {
            host-inbound-traffic {
                protocols {
                    protocol-name;
                    protocol-name <except>;
                }
                system-services {
                    service-name;
                    service-name <except>;
                }
            }
        }
        interfaces interface-name {
            host-inbound-traffic {
                protocols {
                    protocol-name;
                    protocol-name <except>;
                }
                system-services {
                    service-name;

```

```

        service-name <except>;
    }
}
screen screen-name;
}
security-zone zone-name {
    address-book {
        address address-name (ip-prefix | dns-name dns-address-name);
        address-set address-set-name {
            address address-name;
        }
    }
    host-inbound-traffic {
        protocols {
            protocol-name;
            protocol-name <except>;
        }
        system-services {
            service-name;
            service-name <except>;
        }
    }
    interfaces interface-name {
        host-inbound-traffic {
            protocols {
                protocol-name;
                protocol-name <except>;
            }
            system-services {
                service-name;
                service-name <except>;
            }
        }
    }
    screen screen-name;
    tcp-rst;
}
}
}
}
}
```

## access-profile

---

<b>Syntax</b>	<code>access-profile <i>profile-name</i> ;</code>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> xauth]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the access profile to use for extended authentication for remote users trying to access a Virtual Private Network (VPN) tunnel.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>profile-name</i> —Name of the access profile.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ack-number

---

<b>Syntax</b>	<code>ack-number {     match (equal   greater-than   less-than   not-equal);     value <i>acknowledgement-number</i> ; }</code>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the ACK number of the packet. This number identifies the next sequence number; the ACK flag must be set to activate this field.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>acknowledgement-number</i> —Match the ACK number of the packet. <b>Range:</b> 0 through 4294967295
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## action

---

**Syntax**    action {  
               (close-client | close-client-and-server | close-server |  
               drop-connection | drop-packet | ignore-connection |  
               mark-diffserv *value* | no-action | recommended);  
               }

**Hierarchy Level**    [edit security idp idp-policy *policy-name* rulebase-ips rule *rule-name* then]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Specify the actions you want IDP to take when the monitored traffic matches the attack objects specified in the rules.

This statement is supported on SRX-series devices.

- Options**
- **close-client**—Closes the connection and sends an RST packet to the client but not to the server.
  - **close-client-and-server**—Closes the connection and sends an RST packet to both the client and the server.
  - **close-server**—Closes the connection and sends an RST packet to the server but not to the client.
  - **drop-connection**—Drops all packets associated with the connection, preventing traffic for the connection from reaching its destination. Use this action to drop connections for traffic that is not prone to spoofing.
  - **drop-packet**—Drops a matching packet before it can reach its destination but does not close the connection. Use this action to drop packets for attacks in traffic that is prone to spoofing, such as UDP traffic. Dropping a connection for such traffic could result in a denial of service that prevents you from receiving traffic from a legitimate source-IP address.
  - **ignore-connection**—Stops scanning traffic for the rest of the connection if an attack match is found. IDP disables the rulebase for the specific connection.
  - **mark-diffserv *value*** —Assigns the indicated service-differentiation value to the packet in an attack, then passes them on normally.
  - **no-action**—No action is taken. Use this action when you want to only generate logs for some traffic.
  - **recommended**—All predefined attack objects have a default action associated with them. This is the action that Juniper Networks recommends when that attack is detected.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

## active-policy

---

**Syntax** `active-policy policy-name ;`

**Hierarchy Level** [edit security idp]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify which policy among the configured policies to activate.

This statement is supported on SRX-series devices.

**Options** *policy-name* —Name of the active policy.



**NOTE:** You need to make sure the active policy is enforced in the data plane.

---

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## address

---

See the following sections:

- address (ARP Proxy Services Gateway) on page 210
- address (Destination NAT Services Gateway) on page 211
- address (Destination NAT Services Router) on page 211
- address (IKE Gateway) on page 212
- address (Source NAT) on page 212
- address (Zone Address Book) on page 213
- address (Zone Address Set) on page 213

### **address (ARP Proxy Services Gateway)**

**Syntax** address *ip-address* to *ip-address* ;

**Hierarchy Level** [edit security nat proxy-arp interface *interface-name*],  
[edit security nat source pool *pool-name*]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify a single address or an address range of ARP proxy.

This statement is supported on SRX-series devices.

**Options** to—Specify the upper limit of the address range.

*ip-address* —IP address of an ARP proxy.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**address (Destination NAT Services Gateway)**

<b>Syntax</b>	address < <i>ip-address</i> > (to <i>ip-address</i>   port <i>port-number</i> );
<b>Hierarchy Level</b>	[edit security nat destination pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a single address or an address range of the destination NAT pool.  This statement is supported on SRX-series devices.
<b>Options</b>	to—Specify the upper limit of the address range.  <i>ip-address</i> —IP address of a pool.  port <i>port-number</i> —Specify the port number.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**address (Destination NAT Services Router)**

<b>Syntax</b>	address <i>prefix</i> <port <i>port-number</i> >;
<b>Hierarchy Level</b>	[edit security nat destination-nat <i>destination-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify an IP address to which destination IP addresses are translated, when all conditions specified in the security profile are met.  This statement is supported on J-series devices.
<b>Options</b>	<i>prefix</i> —IP address to which destination IP addresses are translated.  port <i>port-number</i> —(Optional) Port number.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**address (IKE Gateway)**

<b>Syntax</b>	address [( <i>ip-address</i>   <i>hostname</i> )];
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the IP address or the hostname of the primary Internet Key Exchange (IKE) gateway and up to four backup gateways.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ip-address</i>   <i>hostname</i> —IP address or hostname of an IKE gateway.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**address (Source NAT)**

<b>Syntax</b>	address <i>prefix</i> ;
<b>Hierarchy Level</b>	[edit security nat interface <i>interface-name</i> proxy-arp], [edit security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify an IP address to which source IP addresses and port numbers of packets are translated.  This statement is supported on J-series devices.
<b>Options</b>	<i>prefix</i> —IP address to add to the source pool.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



**address (Zone Address Book)**

<b>Syntax</b>	<code>address address-name (ip-prefix   dns-name dns-address-name) ;</code>
<b>Hierarchy Level</b>	<code>[edit security zones security-zone zone-name address-book]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Add an entry containing an IP address or Domain Name System (DNS) hostname to the address book for a security zone. A zone's address book contains entries for addressable entities in policy definitions.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>address-name</i>— Name of the address entry.</p> <p><i>ip-prefix</i>— IPv4 address with prefix.</p> <p><i>dns-name dns-address-name</i> —DNS address name.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**address (Zone Address Set)**

<b>Syntax</b>	<code>address address-name ;</code>
<b>Hierarchy Level</b>	<code>[edit security zones security-zone zone-name address-book address-set address-set-name]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Add an address entry to a set of IP addresses for a security zone.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>address-name</i> —Address entry name, as defined with the <b>address (Zone Address Book)</b> statement.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## address-book

---

<b>Syntax</b>	<pre>address-book {     address address-name (ip-prefix   dns-name dns-address-name) ;     address-set address-set-name {         address address-name ;     } }</pre>
<b>Hierarchy Level</b>	[edit security zones security-zone zone-name]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define entries in the address book of a security zone. An address book is a list containing all addresses and address groups, and domain names defined for a security zone. You use address-book entries to identify addressable entities in policy definitions.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## address-persistent

---

<b>Syntax</b>	address-persistent;
<b>Hierarchy Level</b>	[edit security nat source-nat], [edit security nat source]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Enable the device to assign the same IP address from a source pool to a host for multiple concurrent sessions that require the same source IP address for each session.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## address-range

---

See the following sections:

- address-range (Destination NAT) on page 215
- address-range (Source NAT) on page 215

### **address-range (Destination NAT)**

<b>Syntax</b>	address-range high <i>ip-address</i> low <i>ip-address</i> ;
<b>Hierarchy Level</b>	[edit security nat destination-nat <i>destination-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a range of IP addresses for destination address translation.  This statement is supported on J-series devices.
<b>Options</b>	high <i>ip-address</i> —Upper limit of the address range.  low <i>ip-address</i> —Lower limit of the address range.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

### **address-range (Source NAT)**

<b>Syntax</b>	address-range high <i>ip-address</i> low <i>ip-address</i> ;
<b>Hierarchy Level</b>	[edit security nat interface <i>interface-name</i> proxy-arp], [edit security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a range of IP addresses for a source pool.  This statement is supported on J-series devices.
<b>Options</b>	high <i>ip-address</i> —Upper limit of the address range.  low <i>ip-address</i> —Lower limit of the address range.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## address-set

---

<b>Syntax</b>	address-set <i>address-set-name</i> { address <i>address-name</i> ; }
<b>Hierarchy Level</b>	[edit security zones security-zone <i>zone-name</i> address-book]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Identify a collection of addresses, as defined with the <b>address</b> (Zone Address Book) statement.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>address-set-name</i> —Name of the address set.  The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## administrator

---

<b>Syntax</b>	administrator { e-mail-address <i>e-mail-address</i> ; }
<b>Hierarchy Level</b>	[edit security pki ca-profile <i>ca-profile-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify an administrator e-mail address to which the certificate request is sent.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	e-mail-address <i>e-mail-address</i> —E-mail address where the certificate request is sent. By default, there is no preset e-mail address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## aging

---

**Syntax**    aging {  
               early-ageout *seconds* ;  
               high-watermark *percent* ;  
               low-watermark *percent* ;  
               }

**Hierarchy Level**    [edit security flow]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Direct the device to begin aggressively aging out sessions when the percentage of entries in the session table exceeds the high-watermark setting and then stops when the percentage of sessions falls below the low-watermark setting.

This statement is supported on J-series and SRX-series devices.


**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                      security-control—To add this statement to the configuration.

## alarm-threshold

---

<b>Syntax</b>	alarm-threshold <i>number</i> ;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> top syn-flood]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Define the number of half-complete proxy connections per second at which the device makes entries in the event alarm log.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>number</i> —Threshold value.</p> <p><b>Range:</b> 1 through 100000 per second</p> <p><b>Default:</b> 512 per second</p>
<hr/> <div>  <b>NOTE:</b> For SRX-series devices the applicable range is 1 through 1000000 per second.         </div> <hr/>	
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## alarm-without-drop

---

<b>Syntax</b>	alarm-without-drop;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Direct the device to generate an alarm when detecting an attack but not block the attack. Use this statement to allow an attack to enter a segment of your network that you have previously prepared to receive it (for example, a honeynet, which is a decoy network with extensive monitoring capabilities).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## alert

---

<b>Syntax</b>	alert (yes   no);
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then notification log-attacks]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Set an alert flag in the Alert column of the Log Viewer for the matching log record.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**alg**

---

```

Syntax  alg {
            dns {
                disable;
                traceoptions {
                    flag {
                        all <extensive>;
                    }
                }
            }
            ftp {
                disable;
                traceoptions {
                    flag {
                        all <extensive>;
                    }
                }
            }
            h323 {
                application-screen {
                    message-flood {
                        gatekeeper threshold rate ;
                    }
                    unknown-message {
                        permit-nat-applied;
                        permit-routed;
                    }
                }
                disable;
                endpoint-registration-timeout seconds ;
                media-source-port-any;
                traceoptions {
                    flag {
                        all <detail | extensive | terse>;
                        cc <detail | extensive | terse>;
                        h225-asn1 <detail | extensive | terse>;
                        h245 <detail | extensive | terse>;
                        h245-asn1 <detail | extensive | terse>;
                        q931 <detail | extensive | terse>;
                        ras <detail | extensive | terse>;
                        ras-asn1 <detail | extensive | terse>;
                    }
                }
            }
            mgcp {
                application-screen {
                    connection-flood threshold rate ;
                    message-flood threshold rate ;
                    unknown-message {
                        permit-nat-applied;
                        permit-routed;
                    }
                }
            }
        }

```



```

}
disable;
inactive-media-timeout seconds ;
maximum-call-duration minutes ;
traceoptions {
  flag {
    all <extensive>;
    call <extensive>;
    cc <extensive>;
    decode <extensive>;
    error <extensive>;
    nat <extensive>;
    packet <extensive>;
    rm <extensive>;
  }
}
transaction-timeout seconds ;
}
msrpc {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
pptp {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
real {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
rsh {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
rtsp {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}

```

```

    }
  }
  sccp {
    application-screen {
      call-flood threshold rate ;
      unknown-message {
        permit-nat-applied;
        permit-routed;
      }
    }
    disable;
    inactive-media-timeout seconds ;
    traceoptions {
      flag {
        all <extensive>;
        call <extensive>;
        cc <extensive>;
        cli <extensive>;
        decode <extensive>;
        error <extensive>;
        init <extensive>;
        nat <extensive>;
        rm <extensive>;
      }
    }
  }
  sip {
    application-screen {
      protect {
        deny {
          all | destination-ip address ;
          timeout seconds ;
        }
      }
      unknown-message {
        permit-nat-applied;
        permit-routed;
      }
    }
    c-timeout minutes ;
    disable;
    disable-call-id-hiding;
    inactive-media-timeout seconds ;
    maximum-call-duration minutes ;
    retain-hold-resource;
    t1-interval milliseconds ;
    t4-interval seconds ;
    traceoptions {
      flag {
        all <detail | extensive | terse>;
        call <detail | extensive | terse>;
        cc <detail | extensive | terse>;
        nat <detail | extensive | terse>;
        parser <detail | extensive | terse>;
        rm <detail | extensive | terse>;
      }
    }
  }

```

```

    }
  }
  sql {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
  sunrpc {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
  talk {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
  tftp {
    disable;
    traceoptions {
      flag {
        all <extensive>;
      }
    }
  }
}

```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure an Application Layer Gateway (ALG) on the device. An ALG runs as a service and can be associated in policies with specified types of traffic. ALGs are enabled by default.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## algorithm

---

<b>Syntax</b>	algorithm (3des-cbc   aes-128-cbc   aes-192-cbc   aes-256-cbc   des-cbc);
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> manual encryption]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Select the encryption algorithm for the internal Routing-Engine-to-Routing-Engine IPsec security association (SA) configuration.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>3des-cbc—3DES-CBC encryption algorithm.</p> <p>aes-128-cbc—AES-CBC 128-bit encryption algorithm.</p> <p>aes-192-cbc—AES-CBC 192-bit encryption algorithm.</p> <p>aes-256-cbc—AES-CBC 256-bit encryption algorithm.</p> <p>des-cbc—DES-CBC encryption algorithm.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## all-tcp

---

<b>Syntax</b>	all-tcp { mss <i>value</i> ; }
<b>Hierarchy Level</b>	[edit security flow tcp-mss]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Set the TCP maximum segment size (MSS) value for all TCP packets for network traffic.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	mss <i>value</i> —TCP MSS value. <b>Range:</b> 64 through 65535 bytes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## allow-dns-reply

---

<b>Syntax</b>	allow-dns-reply;
<b>Hierarchy Level</b>	[edit security flow]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Allow an incoming Domain Name Service (DNS) reply packet without a matched request. By default, if an incoming UDP first-packet has dst-port 53, the device checks the DNS message packet header to verify that the query bit (QR) is 0, which denotes a query message. If the QR bit is 1, which denotes a response message, the device drops the packet, does not create a session, and increments the illegal packet flow counter for the interface. Using the <b>allow-dns-reply</b> statement directs the device to skip the check.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## allow-icmp-without-flow

---

<b>Syntax</b>	(allow-icmp-without-flow   no-allow-icmp-without-flow);
<b>Hierarchy Level</b>	[edit security idp sensor-configuration flow]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Allow an ICMP packet without matched request. By default the ICMP flow is enabled.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## allow-incoming

---

<b>Syntax</b>	allow-incoming;
<b>Hierarchy Level</b>	<p>[edit security nat interface <i>interface-name</i>],</p> <p>[edit security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i>]</p>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the source IP address pool for the interface to support incoming voice over IP (VoIP) calls.</p> <p>This statement is supported on J-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## always-send

---

<b>Syntax</b>	<code>always-send;</code>
<b>Hierarchy Level</b>	<code>[edit security ike gateway <i>gateway-name</i> dead-peer-detection]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Instructs the device to send dead peer detection (DPD) requests regardless of whether there is outgoing IPsec traffic to the peer.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## anomaly

---

<b>Syntax</b>	<pre>anomaly {     direction (any   client-to-server   server-to-client);     service <i>service-name</i> ;     shellcode (all   intel   no-shellcode   sparc);     test <i>test-condition</i> ; }</pre>
<b>Hierarchy Level</b>	<code>[edit security idp custom-attack <i>attack-name</i> attack-type]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Protocol anomaly attack objects detect abnormal or ambiguous messages within a connection according to the set of rules for the particular protocol being used.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## application

---

See the following sections:

- application (Protocol Binding Custom Attack) on page 228
- application (Security Policies) on page 228

### **application (Protocol Binding Custom Attack)**

<b>Syntax</b>	<code>application application-name ;</code>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain protocol-binding] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol-binding]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Allow IDP to match the attack for a specified application.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>application-name</i> —Name of the application.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

### **application (Security Policies)**

<b>Syntax</b>	<code>application [ <i>application-name-or-set</i> ];</code>
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> match]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the IP or remote procedure call (RPC) application or set of applications to be used as match criteria.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>application-name-or-set</i> —Name of the application or application set used as match criteria.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## application-identification

---

**Syntax**    application-identification {  
               application-system-cache;  
               application-system-cache-timeout *value*;  
               check-first-session;  
               disable;  
               max-packet-memory *value*;  
               max-sessions *value*;  
               max-tcp-session-packet-memory *value*;  
               max-udp-session-packet-memory *value*;  
               }

**Hierarchy Level**    [edit security idp sensor-configuration]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Enable to identify the TCP/UDP application session running on nonstandard ports to match the application properties of transiting network traffic.

This statement is supported on SRX-series devices.

**Options**    disable—Disable the TCP/UDP application identification of nonstandard ports' matching properties.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## application-screen

---

See the following sections:

- application-screen (H323) on page 230
- application-screen (MGCP) on page 231
- application-screen (SCCP) on page 231
- application-screen (SIP) on page 232

### ***application-screen (H323)***

**Syntax**    application-screen {  
                   message-flood {  
                     gatekeeper threshold *rate* ;  
                   }  
                   unknown-message {  
                     permit-nat-applied;  
                     permit-routed;  
                   }  
                 }

**Hierarchy Level**    [edit security alg h323]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure the security screens for the H.323 protocol Application Layer Gateway (ALG).

This statement is supported on J-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                      security-control—To add this statement to the configuration.

**application-screen (MGCP)**

<b>Syntax</b>	<pre> application-screen {     connection-flood threshold <i>rate</i> ;     message-flood threshold <i>rate</i> ;     unknown-message {         permit-nat-applied;         permit-routed;     } } </pre>
<b>Hierarchy Level</b>	[edit security alg mgcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the security screens for the Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**application-screen (SCCP)**

<b>Syntax</b>	<pre> application-screen {     call-flood threshold <i>rate</i> ;     unknown-message {         permit-nat-applied;         permit-routed;     } } </pre>
<b>Hierarchy Level</b>	[edit security alg sccp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the security screens for the Skinny Client Control Protocol (SCCP) Application Layer Gateway (ALG).</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**application-screen (SIP)**

**Syntax**

```

application-screen {
  protect {
    deny {
      all | destination-ip address ;
      timeout seconds ;
    }
  }
  unknown-message {
    permit-nat-applied;
    permit-routed;
  }
}

```

**Hierarchy Level** [edit security alg sip]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure the security screens for the Session Initiation Protocol (SIP) Application Layer Gateway (ALG).

This statement is supported on J-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## application-services

---

<b>Syntax</b>	application-services (wx-redirect   wx-reverse-redirect);
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define the acceleration zone security policy for WX redirection of packets to the WXC Integrated Service Module (ISM 200) for WAN acceleration. During the redirection process, the direction of the WX packet and its type determine further processing of the packet.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>wx-redirect</b>—Specify the WX redirection needed for the packets that arrive from the LAN.</p> <p><b>wx-reverse-redirect</b>—Specify the WX redirection needed for the reverse flow of the packets that arrive from the WAN.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## application-system-cache

---

<b>Syntax</b>	application-system-cache;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>When a session is created, specify an application ID to match the application properties of transiting network traffic. The application port mappings are saved in the application system cache.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## application-system-cache-timeout

---

<b>Syntax</b>	application-system-cache-timeout <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Specify the timeout value in seconds for the application system cache entries. Note the cache is not cleared when IDP policy is loaded. Users need to manually clear or wait for the cache entries to expire.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>value</i> —Timeout value for the application system cache entries.</p> <p><b>Range:</b> 0 through 1 000 000 seconds</p> <p><b>Default:</b> 3600 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## attack-threshold

---

**Syntax** `attack-threshold number ;`

**Hierarchy Level** [edit security screen ids-option *screen-name* tcp syn-flood]

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Define the number of SYN packets per second required to trigger the SYN proxy response.

This statement is supported on J-series and SRX-series devices.

**Options** *number* —Number of SYN packets per second required to trigger the SYN proxy response.

**Range:** 1 through 100000 per second

**Default:** 200 per second



**NOTE:** For SRX-series devices the applicable range is 1 through 1000000 per second.

---

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## attacks

---

See the following sections:

- attacks (Exempt Rulebase) on page 236
- attacks (IPS Rulebase) on page 237

### **attacks (Exempt Rulebase)**

**Syntax** attacks {  
     custom-attacks [attack-name];  
     predefined-attack-groups [attack-name];  
     predefined-attacks [attack-name];  
 }

**Hierarchy Level** [edit security idp idp-policy *policy-name* rulebase-exempt rule *rule-name* match]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the attacks that you do not want the device to match in the monitored network traffic. Each attack is defined as an attack object, which represents a known pattern of attack.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.



**attacks (IPS Rulebase)**

<b>Syntax</b>	attacks { custom-attacks [attack-name]; predefined-attack-groups [attack-name]; predefined-attacks [attack-name]; }
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the attacks you want the device to match in the monitored network traffic. Each attack is defined as an attack object, which represents a known pattern of attack.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## attack-type

---

See the following sections:

- attack-type (Anomaly) on page 238
- attack-type (Chain) on page 239
- attack-type (Signature) on page 240

### attack-type (Anomaly)

**Syntax**    attack-type {  
               anomaly {  
                   direction (any | client-to-server | server-to-client);  
                   service *service-name* ;  
                   shellcode (all | intel | no-shellcode | sparc);  
                   test *test-condition* ;  
               }  
           }

**Hierarchy Level**    [edit security idp custom-attack *attack-name*]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify the type of attack.

This statement is supported on SRX-series devices.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

**attack-type (Chain)**

**Syntax**

```

attack-type {
  chain {
    expression boolean-expression ;
    member member-name {
      attack-type {
        (anomaly | signature);
      }
    }
  }
  order;
  protocol-binding {
    application application-name ;
    icmp;
    ip {
      protocol-number transport-layer-protocol-number ;
    }
    rpc {
      program-number rpc-program-number ;
    }
    tcp {
      minimum-port port-number maximum-port port-number ;
    }
    udp {
      minimum-port port-number maximum-port port-number ;
    }
  }
  reset;
  scope (session | transaction);
}

```

**Hierarchy Level** [edit security idp custom-attack *attack-name*]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Specify the type of attack.

This statement is supported on SRX-series devices.



**NOTE:** In a chain attack, you can configure multiple member attacks.

In an attack, under protocol binding TCP/UDP, you can specify multiple ranges of ports.

---

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**attack-type (Signature)**

```

Syntax  attack-type {
            signature {
                context context-name ;
                direction (any | client-to-server | server-to-client);
                negate;
                pattern signature-pattern ;
                protocol {
                    icmp {
                        code {
                            match (equal | greater-than | less-than | not-equal);
                            value code-value ;
                        }
                        data-length {
                            match (equal | greater-than | less-than | not-equal);
                            value data-length ;
                        }
                        identification {
                            match (equal | greater-than | less-than | not-equal);
                            value identification-value ;
                        }
                        sequence-number {
                            match (equal | greater-than | less-than | not-equal);
                            value sequence-number ;
                        }
                    }
                    type {
                        match (equal | greater-than | less-than | not-equal);
                        value type-value ;
                    }
                }
            }
            ip {
                destination {
                    match (equal | greater-than | less-than | not-equal);
                    value hostname ;
                }
                identification {
                    match (equal | greater-than | less-than | not-equal);
                    value identification-value ;
                }
                ip-flags {
                    (df | no-df);
                    (mf | no-mf);
                    (rb | no-rb);
                }
                protocol {
                    match (equal | greater-than | less-than | not-equal);
                    value transport-layer-protocol-id ;
                }
                source {
                    match (equal | greater-than | less-than | not-equal);
                    value hostname ;
                }
                tos {
                    match (equal | greater-than | less-than | not-equal);
                    value type-of-service-in-decimal ;
                }
            }
        }

```

```

}
total-length {
    match (equal | greater-than | less-than | not-equal);
    value total-length-of-ip-datagram ;
}
ttl {
    match (equal | greater-than | less-than | not-equal);
    value time-to-live ;
}
}
tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number ;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value tcp-data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    header-length {
        match (equal | greater-than | less-than | not-equal);
        value header-length ;
    }
    mss {
        match (equal | greater-than | less-than | not-equal);
        value maximum-segment-size ;
    }
    option {
        match (equal | greater-than | less-than | not-equal);
        value tcp-option ;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
    tcp-flags {
        (ack | no-ack);
        (fin | no-fin);
        (psh | no-psh);
        (r1 | no-r1);
        (r2 | no-r2);
        (rst | no-rst);
        (syn | no-syn);
        (urg | no-urg);
    }
    urgent-pointer {
        match (equal | greater-than | less-than | not-equal);
        value urgent-pointer ;
    }
}

```

```

    }
    window-scale {
        match (equal | greater-than | less-than | not-equal);
        value window-scale-factor ;
    }
    window-size {
        match (equal | greater-than | less-than | not-equal);
        value window-size ;
    }
}
udp {
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
}
}
protocol-binding {
    application application-name ;
    icmp;
    ip {
        protocol-number transport-layer-protocol-number ;
    }
    rpc {
        program-number rpc-program-number ;
    }
    tcp {
        minimum-port port-number maximum-port port-number ;
    }
    udp {
        minimum-port port-number maximum-port port-number ;
    }
}
regexp regular-expression ;
shellcode (all | intel | no-shellcode | sparc);
}

```

**Hierarchy Level** [edit security idp custom-attack *attack-name*]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Specify the type of attack.

This statement is supported on SRX-series devices.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## authentication

---

**Syntax** authentication {  
     algorithm (hmac-md5-96 | hmac-sha1-96);  
     key (ascii-text *key* | hexadecimal *key* );  
 }

**Hierarchy Level** [edit security ipsec vpn *vpn-name* manual]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure IP Security (IPsec) authentication parameters for a manual security association (SA).

This statement is supported on J-series and SRX-series devices.

**Options** algorithm—Hash algorithm that authenticates packet data. It can be one of the following:

- hmac-md5-96—Produces a 128-bit digest.

hmac-sha1-96—Produces a 160-bit digest

key—Type of authentication key. It can be one of the following:

- ascii-text *key*—ASCII text key. For hmac-md5-96, the key is 16 ASCII characters; for hmac-sha1-96, the key is 20 ASCII characters.
- hexadecimal *key*—Hexadecimal key. For hmac-md5-96, the key is 32 hexadecimal characters; for hmac-sha1-96, the key is 40 hexadecimal characters.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## authentication-algorithm

---

<b>Syntax</b>	authentication-algorithm (md5   sha1   sha-256);
<b>Hierarchy Level</b>	[edit security ike proposal <i>proposal-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the Internet Key Exchange (IKE) authentication algorithm.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>authentication-algorithm—Hash algorithm that authenticates packet data. It can be one of three algorithms:</p> <ul style="list-style-type: none"><li>■ md5—Produces a 128-bit digest.</li><li>■ sha1—Produces a 160-bit digest.</li><li>■ sha-256—Produces a 256-bit digest.</li></ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## authentication-method

---

<b>Syntax</b>	authentication-method (dsa-signatures   pre-shared-keys   rsa-signatures);
<b>Hierarchy Level</b>	[edit security ike proposal <i>proposal-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specifies the method the device uses to authenticate the source of Internet Key Exchange (IKE) messages. The <b>pre-shared-keys</b> option refers to a preshared key, which is a key for encryption and decryption that both participants must have before beginning tunnel negotiations. The <b>rsa-signatures</b> and <b>dsa-signatures</b> options refer to two kinds of digital signatures, which are certificates that confirm the identity of the certificate holder. (The default method is a preshared key.)</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>dsa-signatures</b>—Specifies that the Digital Signature Algorithm (DSA) is used.</p> <p><b>pre-shared-keys</b>—Specifies that a preshared key, which is a secret key shared between the two peers, is used during authentication to identify the peers to each other. The same key must be configured for each peer. This is the default method.</p> <p><b>rsa-signatures</b>—Specifies that a public key algorithm, which supports encryption and digital signatures, is used.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## auto-re-enrollment

---

**Syntax** auto-re-enrollment {  
     certificate-id *certificate-id-name* {  
         ca-profile-name *ca-profile-name* ;  
         challenge-password *password* ;  
         re-enroll-trigger-time-percentage *percentage* ;  
         re-generate-keypair;  
     }  
 }

**Hierarchy Level** [edit security pki]

**Release Information** Statement modified in Release 9.0 of JUNOS software.

**Description** Configure the automatic re-enrollment of a certificate authority (CA) certificate.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## automatic

---

<b>Syntax</b>	automatic { enable; interval <i>hours</i> ; start-time <i>start-time</i> ; }
<b>Hierarchy Level</b>	[edit security idp security-package]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Enable the device to automatically download the updated signature database from the specified URL.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## bind-interface

---

<b>Syntax</b>	bind-interface <i>interface-name</i> ;
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the tunnel interface to which the route-based virtual private network (VPN) is bound.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>interface-name</i> —Tunnel interface.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## c-timeout

---

<b>Syntax</b>	c-timeout <i>minutes</i> ;
<b>Hierarchy Level</b>	[edit security alg sip]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the timeout interval for Session Initiation Protocol (SIP) transactions in minutes.  This statement is supported on J-series devices.
<b>Options</b>	<i>minutes</i> —Timeout interval. <b>Range:</b> 3 through 10 minutes <b>Default:</b> 3 minutes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ca-identity

---

<b>Syntax</b>	ca-identity <i>ca-identity</i> ;
<b>Hierarchy Level</b>	[edit security pki ca-profile <i>ca-profile-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the certificate authority (CA) identity to use in requesting digital certificates.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ca-identity</i> —Name of CA identity. This name is typically the domain name of the CA.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ca-profile

---

**Syntax**

```
ca-profile ca-profile-name {
  administrator {
    e-mail-address e-mail-address ;
  }
  ca-identity ca-identity ;
  enrollment {
    retry number;
    retry-interval seconds;
    url url-name;
  }
  revocation-check {
    crl {
      disable {
        on-download-failure;
      }
      refresh-interval hours ;
      url url-name ;
    }
    disable;
  }
}
```

**Hierarchy Level** [edit security pki]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure certificate authority (CA) profile.

This statement is supported on J-series and SRX-series devices.

**Options** *ca-profile-name* —Name of a trusted CA.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## ca-profile-name

---

<b>Syntax</b>	ca-profile-name <i>ca-profile-name</i> ;
<b>Hierarchy Level</b>	[edit security pki auto-re-enrollment certificate-id <i>certificate-id-name</i> ]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	Specify the name of the certificate authority (CA) profile.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ca-profile-name</i> —Name of the specific CA profile.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## cache-size

---

<b>Syntax</b>	cache-size <i>size</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration log]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the size in bytes for each user's log cache.  This statement is supported on SRX-series devices.
<b>Options</b>	size—Cache size. <b>Range:</b> 1 through 65535 bytes <b>Default:</b> 12800 bytes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## call-flood

---

<b>Syntax</b>	call-flood threshold <i>rate</i> ;
<b>Hierarchy Level</b>	[edit security alg sccp application-screen]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Limit the number of calls per second allowed to Skinny Client Control Protocol (SCCP) client. Calls exceeding the threshold are dropped by the SCCP Application Layer Gateway (ALG).</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<p>threshold <i>rate</i> —Number of calls per second per client.</p> <p><b>Range:</b> 2 through 1000</p> <p><b>Default:</b> 20</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## category

---

<b>Syntax</b>	<pre>category {   values [list-of-values]; }</pre>
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify a category filter to add attack objects based on the category.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	values—Name of the category filter.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## certificate

---

<b>Syntax</b>	certificate { local-certificate <i>certificate-id</i> ; peer-certificate-type (pkcs7   x509-signature); trusted-ca ( <i>ca-index</i>   use-all); }
<b>Hierarchy Level</b>	[edit security ike policy <i>policy-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify usage of a digital certificate to authenticate the virtual private network (VPN) initiator and recipient.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## certificate-id

---

<b>Syntax</b>	certificate-id <i>certificate-id-name</i> { ca-profile-name <i>ca-profile-name</i> ; challenge-password <i>password</i> ; re-enroll-trigger-time-percentage <i>percentage</i> ; re-generate-keypair; }
<b>Hierarchy Level</b>	[edit security pki auto-re-enrollment]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	Specify the certificate authority (CA) certificate to use for automatic re-enrollment.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>certificate-id-name</i> —Identifier of the certificate that needs automatic re-enrollment.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



**chain**

```

Syntax  chain {
            expression boolean-expression ;
            member member-name {
                attack-type {
                    (anomaly | signature);
                }
            }
            order;
            protocol-binding {
                application application-name ;
                icmp;
                ip {
                    protocol-number transport-layer-protocol-number ;
                }
                rpc {
                    program-number rpc-program-number ;
                }
                tcp {
                    minimum-port port-number maximum-port port-number ;
                }
                udp {
                    minimum-port port-number maximum-port port-number ;
                }
            }
            reset;
            scope (session | transaction);
        }

```

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Chain attack object combines multiple signatures and/or protocol anomalies into a single object. Traffic must match all of the combined signatures and/or protocol anomalies to match the chain attack object.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## challenge-password

---

<b>Syntax</b>	challenge-password <i>password</i> ;
<b>Hierarchy Level</b>	[edit security pki auto-re-enrollment certificate-id <i>certificate-id-name</i> ]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	Specify the password used by the certificate authority (CA) for enrollment and revocation. If the CA does not provide the challenge password, choose your own password.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## check-first-session

---

<b>Syntax</b>	check-first-session;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify an application ID to the first data packet to match the application properties of transiting network traffic.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## clear-threshold

---

<b>Syntax</b>	<code>clear-threshold <i>clear-threshold</i> ;</code>
<b>Hierarchy Level</b>	[edit security nat source-nat pool-utilization-alarm], [edit security nat source pool-utilization-alarm]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	Configure the lower threshold at which an SNMP trap is triggered when pool utilization for a source pool without Port Address Translation (PAT) falls below the threshold.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>clear-threshold</i> -Threshold at which an SNMP trap is triggered. <b>Range:</b> 40 through 100
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security-To view this statement in the configuration. security-control-To add this statement to the configuration.

## code

---

<b>Syntax</b>	<code>code {     match (equal   greater-than   less-than   not-equal);     value <i>code-value</i> ; }</code>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol icmp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the secondary code that identifies the function of the request/reply within a given type.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>code-value</i> —Match a decimal value. <b>Range:</b> 0 through 255
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## connection-flood

---

<b>Syntax</b>	connection-flood threshold <i>rate</i> ;
<b>Hierarchy Level</b>	[edit security alg mgcp application-screen]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Limit the number of new connection requests allowed per Media Gateway (MG) per second. Messages exceeding the threshold are dropped by the Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>threshold <i>rate</i> —Number of connection requests per second allowed per MG.</p> <p><b>Range:</b> 2 through 10000</p> <p><b>Default:</b> 200</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## connections-limit

---

<b>Syntax</b>	connections-limit <i>number</i> ;
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Limit the number of concurrent connections that the group profile supports. When the maximum number of connections is reached, no more dynamic virtual private network (VPN) endpoints dialup users attempting to access an IPsec VPN are allowed to begin Internet Key Exchange (IKE) negotiations.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>number</i> —Maximum number of concurrent connections allowed.</p> <p><b>Range:</b> 1 through 1000</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## container

---

<b>Syntax</b>	<code>container container-string;</code>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic distinguished-name]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that the value in the identity fields of a dynamic virtual private network (VPN) endpoint user's distinguished name exactly match the values in the group IKE user's distinguished name. The order of the identity fields in the fields of the distinguished name strings must be identical when matching.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>container-string</i> —Distinguished name identity value to be matched.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## context

---

<b>Syntax</b>	<code>context context-name ;</code>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Define the location of the signature where IDP should look for the attack in a specific Application Layer protocol.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>context-name</i> —Name of the context under which the attack has to be matched.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## count

---

See the following sections:

- [count \(Custom Attack\)](#) on page 258
- [count \(Security Policies\)](#) on page 259

### **count (Custom Attack)**

**Syntax**    `count count-value ;`

**Hierarchy Level**    [edit security idp custom-attack *attack-name* time-binding]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify the number of times that IDP detects the attack within the specified scope before triggering an event.

This statement is supported on SRX-series devices.

**Options**    *count-value* —Number of times IDP detects the attack.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**count (Security Policies)**

**Syntax**    `count {  
               alarm {  
                   per-minute-threshold number | per-second-threshold number ;  
               }  
           }`

**Hierarchy Level**    [edit security policies from-zone *zone-name* to-zone *zone-name* policy *policy-name* then]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Enables a count, in bytes or kilobytes, of all network traffic the security policy allows to pass through the device.

This statement is supported on J-series and SRX-series devices.

**Options**    `per-minute-threshold number` —Alarm threshold in kilobytes per minute.

`per-second-threshold number` —Alarm threshold in bytes per second.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                      security-control—To add this statement to the configuration.

**crl**

---

**Syntax**   crl {  
               disable {  
                   on-download-failure;  
               }  
               refresh-interval *hours* ;  
               url *url-name* ;  
           }

**Hierarchy Level**   [edit security pki ca-profile *ca-profile-name* revocation-check]

**Release Information**   Statement introduced in Release 8.5 of JUNOS software.

**Description**   Configure the certificate revocation list (CRL). A CRL is a time-stamped list identifying revoked certificates, which is signed by a CA and made available to the participating IPsec peers on a regular periodic basis.

This statement is supported on J-series and SRX-series devices.

**Options**   disable on-download-failure—(Optional) Override the default behavior and permit certificate verification even if the CRL fails to download.

refresh-interval *hours* —Time interval, in hours, between CRL updates.

url *url-name* —Name of the location from which to retrieve the CRL through HTTP or Lightweight Directory Access Protocol (LDAP). You can specify one URL for each configured CA profile. By default, no location is specified. Use a fully qualified domain name (FQDN) or an IP address and, optionally, a port number. If no port number is specified, port 80 is used for HTTP and port 443 is used for LDAP.

**Usage Guidelines**   For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**   security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.



**custom-attack**

```

Syntax  custom-attack attack-name {
    attack-type {
        anomaly {
            direction (any | client-to-server | server-to-client);
            service service-name ;
            shellcode (all | intel | no-shellcode | sparc);
            test test-condition ;
        }
        chain {
            expression boolean-expression ;
            member member-name {
                attack-type {
                    (anomaly | signature);
                }
            }
            order;
            protocol-binding {
                application application-name ;
                icmp;
                ip {
                    protocol-number transport-layer-protocol-number ;
                }
                rpc {
                    program-number rpc-program-number ;
                }
                tcp {
                    minimum-port port-number maximum-port port-number ;
                }
                udp {
                    minimum-port port-number maximum-port port-number ;
                }
            }
            reset;
            scope (session | transaction);
        }
        signature {
            context context-name ;
            direction (any | client-to-server | server-to-client);
            negate;
            pattern signature-pattern ;
            protocol {
                icmp {
                    code {
                        match (equal | greater-than | less-than | not-equal);
                        value code-value ;
                    }
                    data-length {
                        match (equal | greater-than | less-than | not-equal);
                        value data-length ;
                    }
                }
                identification {

```

```

        match (equal | greater-than | less-than | not-equal);
        value identification-value ;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number ;
    }
    type {
        match (equal | greater-than | less-than | not-equal);
        value type-value ;
    }
}
ip {
    destination {
        match (equal | greater-than | less-than | not-equal);
        value hostname ;
    }
    identification {
        match (equal | greater-than | less-than | not-equal);
        value identification-value ;
    }
    ip-flags {
        (df | no-df);
        (mf | no-mf);
        (rb | no-rb);
    }
    protocol {
        match (equal | greater-than | less-than | not-equal);
        value transport-layer-protocol-id ;
    }
    source {
        match (equal | greater-than | less-than | not-equal);
        value hostname ;
    }
    tos {
        match (equal | greater-than | less-than | not-equal);
        value type-of-service-in-decimal ;
    }
    total-length {
        match (equal | greater-than | less-than | not-equal);
        value total-length-of-ip-datagram ;
    }
    ttl {
        match (equal | greater-than | less-than | not-equal);
        value time-to-live ;
    }
}
tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number ;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value tcp-data-length ;
    }
}

```

```

destination-port {
    match (equal | greater-than | less-than | not-equal);
    value destination-port ;
}
header-length {
    match (equal | greater-than | less-than | not-equal);
    value header-length ;
}
mss {
    match (equal | greater-than | less-than | not-equal);
    value maximum-segment-size ;
}
option {
    match (equal | greater-than | less-than | not-equal);
    value tcp-option ;
}
sequence-number {
    match (equal | greater-than | less-than | not-equal);
    value sequence-number ;
}
source-port {
    match (equal | greater-than | less-than | not-equal);
    value source-port ;
}
tcp-flags {
    (ack | no-ack);
    (fin | no-fin);
    (psh | no-psh);
    (r1 | no-r1);
    (r2 | no-r2);
    (rst | no-rst);
    (syn | no-syn);
    (urg | no-urg);
}
urgent-pointer {
    match (equal | greater-than | less-than | not-equal);
    value urgent-pointer ;
}
window-scale {
    match (equal | greater-than | less-than | not-equal);
    value window-scale-factor ;
}
window-size {
    match (equal | greater-than | less-than | not-equal);
    value window-size ;
}
}
udp {
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
}

```

```

        source-port {
            match (equal | greater-than | less-than | not-equal);
            value source-port ;
        }
    }
}
protocol-binding {
    application application-name ;
    icmp;
    ip {
        protocol-number transport-layer-protocol-number ;
    }
    rpc {
        program-number rpc-program-number ;
    }
    tcp {
        minimum-port port-number maximum-port port-number ;
    }
    udp {
        minimum-port port-number maximum-port port-number ;
    }
}
regexp regular-expression ;
shellcode (all | intel | no-shellcode | sparc);
}
}
recommended-action (close | close-client | close-server | drop |
drop-packet | ignore | none);
severity (critical | info | major | minor | warning);
time-binding {
    count count-value ;
    scope (destination | peer | source);
}
}
}

```

<b>Hierarchy Level</b>	[edit security idp]
<b>Release Information</b>	Statement modified in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Configure custom attack objects to detect a known or unknown attack that can be used to compromise your network.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>attack-name</i> —Name of the custom attack object.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## custom-attack-group

---

<b>Syntax</b>	<code>custom-attack-group <i>custom-attack-group-name</i> {     group-members [<i>attack-group-name</i>   <i>attack-name</i>]; }</code>
<b>Hierarchy Level</b>	[edit security idp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Configure custom attack group. A custom attack group is a list of attacks that would be matched on the traffic if the group is selected in a policy.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>custom-attack-group-name</i> —Name of the custom attack group.  The remaining statement is explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## custom-attacks

---

<b>Syntax</b>	<code>custom-attacks [<i>attack-name</i>];</code>
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match attacks], [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match attacks]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Select custom attacks defined under [edit security idp custom-attack] by specifying their names.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>attack-name</i> —Name of the new custom attack object.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## data-length

---

<b>Syntax</b>	<pre>data-length {     match (equal   greater-than   less-than   not-equal);     value <i>data-length</i> ; }</pre>
<b>Hierarchy Level</b>	<pre>[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol udp] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol icmp] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]</pre>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify the number of bytes in the data payload. In the TCP header, for SYN, ACK, and FIN packets, this field should be empty.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><b>match</b> (equal   greater-than   less-than   not-equal)—Match an operand.</p> <p><b>value</b> <i>data-length</i> —Match the number of bytes in the data payload.</p> <p><b>Range:</b> 0 through 65535</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## dead-peer-detection

---

<b>Syntax</b>	<pre> dead-peer-detection {     always-send;     interval <i>seconds</i> ;     threshold <i>number</i> ; }</pre>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the device to use dead peer detection (DPD). DPD is a method used by devices to verify the current existence and availability of IPsec peer devices. A device performs this verification by sending encrypted IKE Phase 1 notification payloads (R-U-THERE) to peers and waiting for DPD acknowledgements (R-U-THERE-ACK).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## default-policy

---

<b>Syntax</b>	default-policy { (deny-all   permit-all); }
<b>Hierarchy Level</b>	[edit security policies]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the default security policy that defines the actions the device takes on a packet that does not match any user-defined policy.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>deny-all—Deny all traffic. Packets are dropped. This is the default.</p> <p>permit-all—Permit all traffic that does not match a policy.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## deny

---

See the following sections:

- deny (Policy) on page 269
- deny (SIP) on page 270

### **deny (Policy)**

**Syntax** deny;

**Hierarchy Level** [edit security policies from-zone *zone-name* to-zone *zone-name* policy *policy-name* then]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Block the service at the firewall. The device drops the packets.

This statement is supported on J-series and SRX-series devices.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**deny (SIP)**

**Syntax**    deny {  
               all | destination-ip *address* ;  
               timeout *seconds* ;  
               }

**Hierarchy Level**    [edit security alg sip application-screen protect]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Protect servers against INVITE attacks.

This statement is supported on J-series devices.

**Options**    all—Configure the Session Initiation Protocol (SIP) application screen to protect servers at all destination IP addresses against INVITE attacks.

destination-ip *address* —Configure the SIP application screen to protect the server at this destination IP address against INVITE attacks. You can include up to 16 destination IP addresses of servers to be protected. Enabling this option disables the all option.

timeout *seconds* —Amount of time (in *seconds* ) to make an attack table entry for each INVITE, which is listed in the application screen.

**Range:** 1 through 3600 seconds

**Default:** 5 seconds

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## description

---

See the following sections:

- description (IDP Policy) on page 271
- description (Security Policies) on page 271

### **description (IDP Policy)**

<b>Syntax</b>	<code>description text ;</code>
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> ] [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> ]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	Specify descriptive text for an exempt rule, or IPS rule.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>description</i> —Descriptive text about an exempt rule, or IPS rule.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

### **description (Security Policies)**

<b>Syntax</b>	<code>description description ;</code>
<b>Hierarchy Level</b>	[edit security ike policy <i>policy-name</i> ], [edit security ike proposal <i>proposal-name</i> ], [edit security ipsec policy <i>policy-name</i> ], [edit security ipsec proposal <i>proposal-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify descriptive text for an IKE policy, IPsec policy, IKE proposal, or IPsec proposal.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>description</i> —Descriptive text about an IKE policy, IPsec policy, IKE proposal, or IPsec proposal.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## **destination**

---

See the following sections:

- destination (Destination NAT Services Gateway) on page 273
- destination (IP Headers in Signature Attack) on page 274

**destination (Destination NAT Services Gateway)**

**Syntax**

```

destination {
    pool pool-name {
        address < ip-address > (to ip-address | port port-number );
        routing-instance routing-instance-name ;
    }
    rule-set rule-set-name {
        from interface [interface-name] |
        routing-instance [routing-instance-name] | zone [zone-name];
        rule rule-name {
            match {
                destination-address destination-address ;
                destination-port port-number ;
                source-address [source-address];
            }
            then {
                destination-nat (off | pool pool-name );
            }
        }
    }
}

```

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure destination NAT of services gateway, which allows you to configure the following:

- Translate destination IP address or addresses to a specific IP address.
- Translate destination IP address or addresses and port number(s) to a specific IP address and one port number.
- Translate a range of destination IP addresses to another range of IP addresses. This mapping is one-to-one, static, and without PAT.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

***destination (IP Headers in Signature Attack)***

**Syntax**    destination {  
                  match (equal | greater-than | less-than | not-equal);  
                  value *hostname* ;  
                  }

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol ip]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify the IP address of the attack target.

This statement is supported on SRX-series devices.

**Options**    match (equal | greater-than | less-than | not-equal)—Match an operand.

value *host-name* —Match an ip-address or a host name.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

## destination-address

---

See the following sections:

- destination-address (Destination NAT Services Gateway) on page 275
- destination-address (IDP Policy) on page 276
- destination-address (Security Policies) on page 276
- destination-address (Source NAT Services Gateway) on page 277
- destination-address (Static NAT Services Gateway) on page 277
- destination-address (Traffic Policy Services Gateway) on page 278

### ***destination-address* (Destination NAT Services Gateway)**

<b>Syntax</b>	<code>destination-address destination-address ;</code>
<b>Hierarchy Level</b>	[edit security nat destination rule-set <i>rule-set-name</i> rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a destination address to match the rule. You can configure one address or a subnet.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>destination-address</i> —Destination address or a subnet.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**destination-address (IDP Policy)**

<b>Syntax</b>	destination-address [ address-name ];
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match], [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a destination IP address or IP address set object to be used as the match destination address object. The default value is any.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>address-name</i> —IP address, IP address set object.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**destination-address (Security Policies)**

<b>Syntax</b>	destination-address { <i>address-name</i> ; }
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> match]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a destination IP address or IP address set to be used as the match criteria for the security policy.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>address-name</i> —IP address, IP address set, or address book entry.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



***destination-address (Source NAT Services Gateway)***

<b>Syntax</b>	<code>destination-address [destination-address];</code>
<b>Hierarchy Level</b>	[edit security nat source rule-set <i>rule-set-name</i> rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a destination address to match the rule. You can configure multiple addresses or subnets.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>destination-address</i> —Destination address or a subnet.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

***destination-address (Static NAT Services Gateway)***

<b>Syntax</b>	<code>destination-address [destination-address];</code>
<b>Hierarchy Level</b>	[edit security nat static rule-set <i>rule-set-name</i> rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a destination address to match the rule. You can configure one address or a subnet.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>destination-address</i> —Destination address or a subnet.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**destination-address (Traffic Policy Services Gateway)**

<b>Syntax</b>	destination-address { drop-translated; drop-untranslated; }
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Enable the destination address translation to permit the traffic. By default the policy permits both the translated and the untranslated packets.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><b>drop-translated</b>—Drop the packets with translated destination address.</p> <p><b>drop-untranslated</b>—Drop the packets without translated destination address.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**destination-except**

---

<b>Syntax</b>	destination-except [ <i>address-name</i> ];
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match], [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Specify a destination IP address or IP address set object to specify all destination address objects except the specified address objects. The default value is any.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<i>address-name</i> —IP address, IP address set object.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>


## destination-ip

---

<b>Syntax</b>	<code>destination-ip ip-address ;</code>
<b>Hierarchy Level</b>	<code>[edit security ipsec vpn vpn-name vpn-monitor]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the destination of the Internet Control Message Protocol (ICMP) pings. If this statement is used, the device uses the peer's gateway address by default.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<code>ip-address</code> —Destination IP address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## destination-ip-based

---

<b>Syntax</b>	<code>destination-ip-based number ;</code>
<b>Hierarchy Level</b>	<code>[edit security screen ids-option screen-name limit-session]</code>
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	Limit the number of concurrent sessions the device can direct to a single destination IP address.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<code>number</code> —Maximum number of concurrent sessions that can be directed to a destination IP address. <b>Range:</b> 1 through 50000 <b>Default:</b> 128
 <b>NOTE:</b> For SRX-series devices the applicable range is 1 through 8000000.	
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## destination-nat

---

See the following sections:

- destination-nat (Destination NAT Services Gateway) on page 280
- destination-nat (Destination NAT Services Router) on page 281
- destination-nat (Security Policies) on page 282

### ***destination-nat (Destination NAT Services Gateway)***

**Syntax** destination-nat (off | pool *pool-name* );

**Hierarchy Level** [edit security nat destination rule-set *rule-set-name* rule *rule-name* then]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the action of the destination NAT rule.

This statement is supported on SRX-series devices.

**Options** off—Do not perform destination NAT operation.

pool *pool-name* —Use user-defined destination NAT pool to perform destination NAT.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**destination-nat (Destination NAT Services Router)**

**Syntax** `destination-nat destination-nat-name {  
           address prefix <port port-number >;  
           address-range high ip-address low ip-address ;  
           }`

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure policy-based destination Network Address Translation (NAT), which allows you to configure the following:

- Translate destination IP address or addresses to a single IP address.
- Translate destination IP address or addresses and port number(s) to an IP address and one port number.
- Translate a range of destination IP addresses to another range of IP addresses. This mapping is one-to-one and static.

This statement is supported on J-series devices.

**Options** `destination-nat-name` —Name of destination NAT.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

***destination-nat (Security Policies)***

<b>Syntax</b>	<code>destination-nat destination-name ;</code>
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that destination NAT be used in the security policy.  This statement is supported on J-series devices.
<b>Options</b>	<code>pool destination-name</code> —Use the specified destination NAT.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.
<b>Related Topics</b>	destination-nat (Destination NAT Services Router)

## destination-port

---

See the following sections:

- destination-port (Destination NAT Services Gateway) on page 283
- destination-port (Signature Attack) on page 284

### ***destination-port (Destination NAT Services Gateway)***

**Syntax** destination-port *port-number* ;

**Hierarchy Level** [edit security nat destination rule-set *rule-set-name* rule *rule-name* match]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify a destination port to match the rule. You can configure one port.

This statement is supported on SRX-series devices.

**Options** *port-number* —Destination port number.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.


***destination-port (Signature Attack)***

<b>Syntax</b>	<pre>destination-port {     match (equal   greater-than   less-than   not-equal);     value <i>destination-port</i> ; }</pre>
<b>Hierarchy Level</b>	<pre>[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol udp] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]</pre>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify the port number of the attack target.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><b>match</b> (equal   greater-than   less-than   not-equal)—Match an operand.</p> <p><b>value</b> <i>destination-port</i> —Match the port number of the attack target.</p> <p><b>Range:</b> 0 through 65535</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>



## destination-threshold

---

<b>Syntax</b>	destination-threshold <i>number</i> ;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> tcp syn-flood]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the number of SYN segments received per second for a single destination IP address before the device begins dropping connection requests to that destination. If a protected host runs multiple services, you might want to set a threshold based only on the destination IP address, regardless of the destination port number.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Number of SYN segments received per second before the device begins dropping connection requests. <b>Range:</b> 4 through 100000 per second <b>Default:</b> 4000 per second
	<b>NOTE:</b> For SRX-series devices the applicable range is 4 through 1000000 per second.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## detect-shellcode

---

<b>Syntax</b>	detect-shellcode;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Enable to detect the shell code and prevent buffer overflow attacks. By default this setting is enabled.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## detector

---

<b>Syntax</b>	<pre> detector {     protocol-name protocol-name {         tunable-name tunable-name {             tunable-value protocol-value ;         }     } } </pre>
<b>Hierarchy Level</b>	[edit security idp sensor-configuration]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Configure protocol detector engine for a specific service.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## df-bit

---

<b>Syntax</b>	df-bit (clear   copy   set);
<b>Hierarchy Level</b>	[edit security ipsec vpn vpn-name]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify how the router handles the Don't Fragment (DF) bit in the outer header.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>clear—Clear (disable) the DF bit from the outer header. This is the default.</p> <p>copy—Copy the DF bit to the outer header.</p> <p>set—Set (enable) the DF bit in the outer header.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**dh-group**

---

<b>Syntax</b>	dh-group (group1   group2   group5);
<b>Hierarchy Level</b>	[edit security ike proposal <i>proposal-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the IKE Diffie-Hellman group.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	dh-group—Type of Diffie-Hellman prime modulus group for performing a Diffie-Hellman authentication key exchange. <ul style="list-style-type: none"> <li>■ group1—768-bit algorithm.</li> <li>■ group2—1024-bit algorithm.</li> <li>■ group5—1536-bit algorithm.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## direction

---

See the following sections:

- [direction \(Custom Attack\)](#) on page 288
- [direction \(Dynamic Attack Group\)](#) on page 289

### ***direction (Custom Attack)***

**Syntax** direction (any | client-to-server | server-to-client);

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type anomaly]  
[edit security idp custom-attack *attack-name* attack-type signature]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Define the connection direction of the attack.

This statement is supported on SRX-series devices.

**Options** any—Detect the attack in either direction.

client-to-server—Detect the attack only in client-to-server traffic.

server-to-client—Detect the attack only in server-to-client traffic.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**direction (Dynamic Attack Group)**

<b>Syntax</b>	direction { values [any   client-to-server   exclude-any   exclude-client-to-server   exclude-server-to-client   server-to-client]; }
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a direction filter to add predefined attacks to the dynamic group based on the direction specified in the attacks.  This statement is supported on SRX-series devices.
<b>Options</b>	values—Name of the direction filter. You can select from the following directions: <ul style="list-style-type: none"> <li>■ any—Monitors traffic from client to server and server and client.</li> <li>■ client-to-server—Monitors traffic only from client to server (most attacks occur over client-to-server connections).</li> <li>■ exclude-any—Allows traffic from client to server and server and client.</li> <li>■ exclude-client-to-server—Allows traffic only from client to server.</li> <li>■ exclude-server-to-client—Allows traffic only from server-to-client.</li> <li>■ server-to-client—Monitors traffic only from server-to-client.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**disable-call-id-hiding**

<b>Syntax</b>	disable-call-id-hiding;
<b>Hierarchy Level</b>	[edit security alg sip]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Disable translation of the host IP address in call-ID header. Translation is enabled by default.  This statement is supported on J-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## distinguished-name

---

**Syntax** distinguished-name {  
    container *container-string* ;  
    wildcard *wildcard-string* ;  
}

**Hierarchy Level** [edit security ike gateway *gateway-name* dynamic]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify a distinguished name as the identifier for the remote gateway with a dynamic IP address.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**dns**

---

**Syntax**

```

dns {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}

```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the Domain Name Service (DNS) Application Layer Gateway (ALG) on the device.

This statement is supported on J-series devices.

**Options** **disable**—Disable the DNS ALG by default, the DNS ALG is enabled.

**traceoptions**—Configure DNS ALG tracing options.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

**all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## dynamic

---

**Syntax**    dynamic {  
               connections-limit *number*;  
               distinguished-name {  
                   container *container-string*;  
                   wildcard *wildcard-string*;  
               }  
               hostname *domain-name*;  
               ike-user-type (group-ike-id | shared-ike-id);  
               inet *ip-address*;  
               user-at-hostname *user-at-hostname*;

**Hierarchy Level**    [edit security ike gateway *gateway-name*]

**Release Information**    Statement modified in Release 8.5 of JUNOS software.

**Description**    Specify the identifier for the remote gateway with a dynamic IP address. Use this statement to set up a VPN with a gateway that has an unspecified IP address.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the JUNOS Software Security Configuration Guide.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.



## dynamic-attack-group

---

**Syntax** `dynamic-attack-group dynamic-attack-group-name {`  
     `filters {`  
         `category {`  
             `values [list-of-values];`  
         `}`  
         `direction {`  
             `values [any | client-to-server | exclude-any | exclude-client-to-server |`  
             `exclude-server-to-client | server-to-client];`  
         `}`  
         `false-positives {`  
             `values [frequently | occasionally | rarely | unknown];`  
         `}`  
         `performance {`  
             `values [fast | normal | slow | unknown];`  
         `}`  
         `products {`  
             `values [list-of-values];`  
         `}`  
         `recommended;`  
         `service {`  
             `values [list-of-values];`  
         `}`  
         `severity {`  
             `values [critical | info | major | minor | warning];`  
         `}`  
         `type {`  
             `values [anomaly | signature];`  
         `}`  
     `}`  
`}`

**Hierarchy Level** [edit security idp]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Configure dynamic attack group. Dynamic attack groups select its members based on the filters specified in the group. Hence the list of attacks get updated (added or removed) when a new signature database is used.

This statement is supported on SRX-series devices.

**Options** *dynamic-attack-group-name* —Name of the dynamic attack group.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## early-ageout

---

<b>Syntax</b>	early-ageout seconds ;
<b>Hierarchy Level</b>	[edit security flow aging]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define the ageout value before the device aggressively ages out a session from its session table.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<p><b>seconds</b> —Amount of time that elapses before the device aggressively ages out a session.</p> <p><b>Range:</b> 1 through 65535 seconds</p> <p><b>Default:</b> 20 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## enable-all-qmodules

---

<b>Syntax</b>	(enable-all-qmodules   no-enable-all-qmodules);
<b>Hierarchy Level</b>	[edit security idp sensor-configuration global]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Enable all the qmodules of the global rulebase IDP security policy. By default all the qmodules are enabled.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## enable-packet-pool

---

<b>Syntax</b>	(enable-packet-pool   no-enable-packet-pool);
<b>Hierarchy Level</b>	[edit security idp sensor-configuration global]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Enable the packet pool to use when the current pool is exhausted. By default packet pool is enabled.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## encryption

---

**Syntax** encryption {  
     algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);  
     key (ascii-text *key* | hexadecimal *key* );  
 }

**Hierarchy Level** [edit security ipsec vpn *vpn-name* manual]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure an encryption algorithm and key for a manual Security Association (SA).

This statement is supported on J-series and SRX-series devices.

**Options** algorithm—Type of encryption algorithm. It can be one of the following:

- des-cbc—Has a block size of 8 bytes (64 bits); its key size is 48 bits long.
- 3des-cbc—Has block size of 8 bytes (64 bits); its key size is 192 bits long



**NOTE:** For 3des-cbc, we recommend that the first 8 bytes be different from the second 8 bytes, and the second 8 bytes be the same as the third 8 bytes.

- 
- aes-128-cbc—Advanced Encryption Standard (AES) 128-bit encryption algorithm.
  - aes-192-cbc—Advanced Encryption Standard (AES) 192-bit encryption algorithm.
  - aes-256-cbc—Advanced Encryption Standard (AES) 256-bit encryption algorithm.

key—Type of encryption key. It can be one of the following:

- ascii-text *key*—ASCII text key. For the **des-cbc** option, the key contains 8 ASCII characters; for **3des-cbc**, the key contains 24 ASCII characters.
- hexadecimal *key*—Hexadecimal key. For the **des-cbc** option, the key contains 16 hexadecimal characters; for the **3des-cbc** option, the key contains 48 hexadecimal characters.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## encryption-algorithm

---

<b>Syntax</b>	encryption-algorithm (des-cbc   3des-cbc   aes-128-cbc   aes-192-cbc   aes-256-cbc);
<b>Hierarchy Level</b>	[edit security ike proposal <i>proposal-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Configure an IKE encryption algorithm.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	3des-cbc—Has a block size of 24 bytes; the key size is 192 bits long.  des-cbc—Has a block size of 8 bytes; the key size is 48 bits long.  aes-128-cbc—Advanced Encryption Standard (AES) 128-bit encryption algorithm.  aes-192-cbc—Advanced Encryption Standard (AES) 192-bit encryption algorithm.  aes-256-cbc—Advanced Encryption Standard (AES) 256-bit encryption algorithm.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## endpoint-registration-timeout

---

<b>Syntax</b>	endpoint-registration-timeout <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit security alg h323]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the timeout value in seconds for entries in the NAT table.  This statement is supported on J-series devices.
<b>Options</b>	<i>seconds</i> —Timeout value. <b>Range:</b> 10 through 50000 seconds <b>Default:</b> 3600 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## enrollment

---

**Syntax** enrollment {  
     retry *number* ;  
     retry-interval *seconds* ;  
     url *url-name* ;  
 }

**Hierarchy Level** [edit security pki ca-profile *ca-profile-name*]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Specify the enrollment parameters for a certificate authority (CA).

This statement is supported on J-series and SRX-series devices.

**Options** retry *number* —Number of automated attempts for online enrollment to be retried in case enrollment response is pending.

**Range:** 0 through 1080

**Default:** 10

retry-interval *seconds* —Time interval, in seconds, between the enrollment retries.

**Range:** 0 through 3600

**Default:** 900 seconds

url *url-name* —Enrollment URL where the Simple Certificate Enrollment Protocol (SCEP) request is sent to the certification authority (CA) as configured in this profile.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## establish-tunnels

---

<b>Syntax</b>	establish-tunnels (immediately   on-traffic);
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify when IKE is activated: immediately after VPN information is configured and configuration changes are committed, or only when data traffic flows. In the second case, IKE needs to be negotiated with the peer gateway.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>immediately</b>—IKE is activated immediately after VPN configuration and configuration changes are committed.</p> <p><b>on-traffic</b>—IKE is activated only when data traffic flows and must to be negotiated.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## expression

---

<b>Syntax</b>	<code>expression <i>boolean-expression</i>;</code>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Configure Boolean expression. The Boolean expression defines the condition for the individual members of a chain attack that will decide if the chain attack is hit.</p> <p>For standalone IDP devices, expression overrides order function.</p> <p>For SRX-series devices, expression and order cannot be configured together. Only one of them can be specified.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>boolean-expression</i>—Boolean operators:</p> <ul style="list-style-type: none"> <li>■ <b>or</b>—If either of the member name patterns match, the expression matches.</li> <li>■ <b>and</b>—If both of the member name patterns mach, the expression matches. It does not matter which order the members appear in.</li> <li>■ <b>oand</b>—If both of the member name patterns match, and if they appear in the same order as in the Boolean Expression, the expression matches.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>



## external-interface

---

See the following sections:

- external-interface (IKE Gateway) on page 301
- external-interface (Manual Security Association) on page 301

### external-interface (IKE Gateway)

<b>Syntax</b>	<code>external-interface external-interface-name ;</code>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the outgoing interface for IKE SAs. This interface is associated with a zone that acts as its carrier, providing firewall security for it.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>external-interface-name</i> —Name of the interface to be used to send traffic to the IPsec VPN.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

### external-interface (Manual Security Association)

<b>Syntax</b>	<code>external-interface external-interface-name ;</code>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> manual]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the outgoing interface for the manual SA.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>external-interface-name</i> —Name of the outgoing interface.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## false-positives

---

<b>Syntax</b>	false-positives { values [frequently   occasionally   rarely   unknown]; }
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a false-positives filter to add attack objects based on the frequency that the attack produces a false positive on your network.  This statement is supported on SRX-series devices.
<b>Options</b>	<p>values—Name of the false positives filter. You can select from the following false positives frequency:</p> <ul style="list-style-type: none"> <li>■ frequently—Frequently track false positives occurrence.</li> <li>■ occasionally—Occasionally track false positives occurrence.</li> <li>■ rarely—Rarely track false positives occurrence.</li> <li>■ unknown—By default, all compound attack objects are set to Unknown. As you fine-tune IDP to your network traffic, you can change this setting to help you track false positives.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## family

---

**Syntax**

```
family {
  inet6 {
    mode packet-based;
  }
  iso {
    mode packet-based;
  }
  mpls {
    mode packet-based;
  }
}
```

**Hierarchy Level** [edit security forwarding-options]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Determine the protocol family to be used for packet forwarding.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## filters

---

**Syntax**

```
filters {
  category {
    values [list-of-values];
  }
  direction {
    values [any | client-to-server | exclude-any | exclude-client-to-server |
    exclude-server-to-client | server-to-client];
  }
  false-positives {
    values [frequently | occasionally | rarely | unknown];
  }
  performance {
    values [fast | normal | slow | unknown];
  }
  products {
    values [list-of-values];
  }
  recommended;
  service {
    values [list-of-values];
  }
  severity {
    values [critical | info | major | minor | warning];
  }
  type {
    values [anomaly | signature];
  }
}
```

**Hierarchy Level** [edit security idp dynamic-attack-group *dynamic-attack-group-name*]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** To create a dynamic attack group, set the criteria using the different type of filters.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**fin-no-ack**

---

<b>Syntax</b>	fin-no-ack;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> top]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable detection of an illegal combination of flags, and reject packets that have this combination.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## firewall-authentication

---

See the following sections:

- firewall-authentication (Policies) on page 306
- firewall-authentication (Security) on page 307

### ***firewall-authentication (Policies)***

**Syntax** firewall-authentication {  
     pass-through {  
         access-profile *profile-name* ;  
         client-match *match-name* ;  
         web-redirect;  
     }  
     web-authentication {  
         client-match *user-or-group* ;  
     }  
 }

**Hierarchy Level** [edit security policies from-zone *zone-name* to-zone *zone-name* policy *policy-name* then permit]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure firewall authentication methods.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**firewall-authentication (Security)**

**Syntax**

```

firewall-authentication {
  traceoptions {
    flag {
      all <detail | extensive | terse>;
      authentication <detail | extensive | terse>;
      proxy <detail | extensive | terse>;
    }
  }
}

```

**Hierarchy Level** [edit security]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Define data-plane firewall authentication tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** flag—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

- all—Enable all tracing operations.
- authentication—Trace data-plane firewall authentication events.
- proxy—Trace data-plane firewall authentication proxy events.

detail—Display moderate amount of data.

extensive—Display extensive amount of data.

terse—Display minimum amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## flood

---

See the following sections:

- flood (ICMP) on page 308
- flood (UDP) on page 309

### **flood (ICMP)**

**Syntax** flood {  
    threshold *number* ;  
}

**Hierarchy Level** [edit security screen ids-option *screen-name* icmp]

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Configure the device to detect and prevent Internet Control Message Protocol (ICMP) floods. An ICMP flood occurs when ICMP echo requests are broadcast with the purpose of flooding a system with so much data that it first slows down, and then times out and is disconnected. The threshold defines the number of ICMP packets per second allowed to ping the same destination address before the device rejects further ICMP packets.

This statement is supported on J-series and SRX-series devices.

**Options** threshold *number* —Number of ICMP packets per second allowed to ping the same destination address before the device rejects further ICMP packets.

**Range:** 1 through 100000 per second

**Default:** 1000 per second



**NOTE:** For SRX-series devices the applicable range is 1 through 4000000 per second.

---

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



**flood (UDP)**

**Syntax**    flood {  
                  threshold *number* ;  
          }

**Hierarchy Level**    [edit security screen ids-option *screen-name* udp]

**Release Information**    Statement modified in Release 9.2 of JUNOS software.

**Description**    Configure the device to detect and prevent UDP floods. UDP flooding occurs when an attacker sends UDP packets to slow down the system to the point that it can no longer process valid connection requests.

The threshold defines the number of UDP packets per second allowed to ping the same destination IP address/port pair. When the number of packets exceeds this value within any 1-second period, the device generates an alarm and drops subsequent packets for the remainder of that second.

This statement is supported on J-series and SRX-series devices.

**Options**    threshold *number* —Number of UDP packets per second allowed to ping the same destination address before the device rejects further UDP packets.  
                  **Range:** 1 through 100000 per second  
                  **Default:** 1000 per second



**NOTE:** For SRX-series devices the applicable range is 1 through 4000000 per second.

---

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

## flow

---

See the following sections:

- flow (IDP) on page 310
- flow (Security Flow) on page 311

### flow (IDP)

**Syntax** flow {  
     (allow-icmp-without-flow | no-allow-icmp-without-flow);  
     (log-errors | no-log-errors);  
     max-timers-poll-ticks *value* ;  
     reject-timeout *value* ;  
     (reset-on-policy | no-reset-on-policy);  
 }

**Hierarchy Level** [edit security idp sensor-configuration]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure the IDP engine to manage the packet flow.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**flow (Security Flow)**

**Syntax**

```

flow {
    aging {
        early-ageout seconds ;
        high-watermark percent ;
        low-watermark percent ;
    }
    allow-dns-reply;
    route-change-timeout seconds ;
    syn-flood-protection-mode (syn-cookie | syn-proxy);
    tcp-mss {
        all-tcp {
            mss value ;
        }
        gre-in {
            mss value ;
        }
        gre-out {
            mss value ;
        }
        ipsec-vpn {
            mss value ;
        }
    }
    tcp-session {
        no-sequence-check;
        no-syn-check;
        no-syn-check-in-tunnel;
        rst-invalidate-session;
        rst-sequence-check;
        tcp-initial-timeout seconds ;
    }
    traceoptions {
        file filename <files number > <size maximum-file-size >;
        <world-readable | no-world-readable>;
        flag flag;
    }
}

```

**Hierarchy Level** [edit security]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Determine how the device manages packet flow. The device can regulate packet flow in the following ways:

- Enable or disable DNS replies when there is no matching DNS request.
- Set the initial session-timeout values.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## forwarding-options

---

**Syntax**

```
forwarding-options {
  family {
    inet6 {
      mode packet-based;
    }
    iso {
      mode packet-based;
    }
  }
  mpls {
    mode packet-based;
  }
}
```

**Hierarchy Level** [edit security]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Determine how the `inet6`, and `iso` protocol families manage security forwarding options.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## fragment

---

<b>Syntax</b>	fragment;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> icmp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the device to detect and drop any ICMP frame with the More Fragments flag set or with an offset indicated in the <b>offset</b> field.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## from

---

<b>Syntax</b>	from interface [interface-name]   routing-instance [routing-instance-name]   zone [zone-name];
<b>Hierarchy Level</b>	[edit security nat destination rule-set <i>rule-set-name</i> ], [edit security nat source rule-set <i>rule-set-name</i> ], [edit security nat static rule-set <i>rule-set-name</i> ]
<b>Release Information</b>	Statement modified in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the source of the packet among the routing instance, interface, or zone.  This statement is supported on SRX-series devices.
<b>Options</b>	interface <i>interface-name</i> —Name of the interface.  routing-instance <i>routing-instance-name</i> —Name of the routing instance.  zone <i>zone-name</i> —Name of the zone.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## from-zone

---

See the following sections:

- from-zone (IDP Policy) on page 314
- from-zone (Security Policies) on page 315

### **from-zone (IDP Policy)**

**Syntax** from-zone *zone-name* ;

**Hierarchy Level** [edit security idp idp-policy *policy-name* rulebase-exempt rule *rule-name* match],  
[edit security idp idp-policy *policy-name* rulebase-ips rule *rule-name* match]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify a source zone to be associated with the security policy. The default value is any.

This statement is supported on SRX-series devices.

**Options** *zone-name* —Name of the source zone object.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**from-zone (Security Policies)**

```

Syntax  from-zone zone-name to-zone zone-name {
    policy policy-name {
        match {
            application [ application-name-or-set ];
            destination-address {
                address-name ;
            }
            source-address {
                address-name ;
            }
        }
        scheduler-name scheduler-name ;
        then {
            count {
                alarm {
                    per-minute-threshold number;
                    per-second-threshold number ;
                }
            }
            (deny | reject);
            permit {
                application-services (wx-redirect | wx-reverse-redirect);
                destination-address {
                    drop-translated;
                    drop-untranslated;
                }
                destination-nat destination-name ;
                firewall-authentication {
                    pass-through {
                        access-profile profile-name ;
                        client-match match-name ;
                        web-redirect;
                    }
                    web-authentication {
                        client-match user-or-group ;
                    }
                }
            }
            source-nat (pool pool-name | pool-set pool-set-name | interface);
            tunnel {
                ipsec-vpn vpn-name ;
                pair-policy pair-policy ;
            }
        }
        log {
            session-close;
            session-init;
        }
    }
}

```

**Hierarchy Level** [edit security policies]

<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a source zone and destination zone to be associated with the security policy.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>zone-name</i> —Name of the source zone.</p> <p><i>to-zone zone-name</i> —Name of the destination zone.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>



**ftp**

---

**Syntax**

```
ftp {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Specify the FTP ALG on the device.

This statement is supported on J-series and SRX-series devices.

**Options** disable—Disable the FTP ALG. By default, the FTP ALG is enabled.



**NOTE:** By default, FTP ALG is disabled for SRX-series devices.

---

traceoptions—Configure FTP ALG tracing options. To specify more than one trace operation, include multiple flag statements.

flag—Trace operation to perform.

all—Trace all events.

extensive—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## functional-zone

---

**Syntax**

```
functional-zone {
  management {
    host-inbound-traffic {
      protocols {
        protocol-name ;
        protocol-name <except>;
      }
      system-services {
        service-name ;
        service-name <except>;
      }
    }
    interfaces interface-name {
      host-inbound-traffic {
        protocols {
          protocol-name ;
          protocol-name <except>;
        }
        system-services {
          service-name ;
          service-name <except>;
        }
      }
    }
    screen screen-name ;
  }
}
```

**Hierarchy Level** [edit security zones]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure a functional zone.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## gatekeeper

---

<b>Syntax</b>	gatekeeper threshold <i>rate</i> ;
<b>Hierarchy Level</b>	[edit security alg h323 application-screen message-flood]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Limit the rate at which remote access server (RAS) requests to the gatekeeper are processed. Messages exceeding the threshold are dropped.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<p>threshold <i>rate</i> —Threshold measured in messages per second.</p> <p><b>Range:</b> 1 through 50000</p> <p><b>Default:</b> 1000</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## **gateway**

---

See the following sections:

- gateway (IKE) on page 321
- gateway (IPsec) on page 322
- gateway (Manual Security Association) on page 322

**gateway (IKE)**

**Syntax** `gateway gateway-name {`  
     `address [( ip-address | hostname )] |`  
     `dead-peer-detection {`  
         `always-send;`  
         `interval seconds ;`  
         `threshold number ;`  
     `}`  
     `dynamic {`  
         `connections-limit number ;`  
         `distinguished-name {`  
             `container container-string ;`  
             `wildcard wildcard-string ;`  
         `}`  
         `hostname domain-name ;`  
         `ike-user-type (group-ike-id | shared-ike-id);`  
         `inet ip-address ;`  
         `user-at-hostname user-at-hostname ;`  
     `}`  
     `external-interface external-interface-name ;`  
     `ike-policy name ;`  
     `local-identity (hostname hostname | inet ipv4-ip-address |`  
     `user-at-hostname e-mail-address | distinguished-name string );`  
     `nat-keepalive seconds ;`  
     `no-nat-traversal;`  
     `xauth {`  
         `access-profile profile-name ;`  
     `}`  
`}`

**Hierarchy Level** [edit security ike]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure an IKE gateway.

This statement is supported on J-series and SRX-series devices.

**Options** *gateway-name* —Name of the gateway.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**gateway (IPsec)**

<b>Syntax</b>	<code>gateway gateway-name ;</code>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the remote gateway.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>gateway-name</i> —Name of the gateway.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**gateway (Manual Security Association)**

<b>Syntax</b>	<code>gateway ip-address ;</code>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> manual]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	For a manual security association, specify the IP address of the peer.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ip-address</i> —IP address of the peer.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## global

---

**Syntax**    global {  
              (enable-all-qmodules | no-enable-all-qmodules);  
              (enable-packet-pool | no-enable-packet-pool);  
              (policy-lookup-cache | no-policy-lookup-cache);  
              }

**Hierarchy Level**    [edit security idp sensor-configuration]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Configure the global rulebase IDP security policy.

                  This statement is supported on SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

**gre-in**

---

**Syntax**    gre-in {  
              mss *value* ;  
              }

**Hierarchy Level**    [edit security flow tcp-mss]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Enable and specify the TCP maximum segment size (TCP MSS) for Generic Routing Encapsulation (GRE) packets that are coming out from an IPsec VPN tunnel. If the device receives a GRE-encapsulated TCP packet with the SYN bit and TCP MSS option set and the TCP MSS option specified in the packet exceeds the TCP MSS specified by the device, the device modifies the TCP MSS value accordingly. By default, a TCP MSS for GRE packets is not set.

This statement is supported on J-series and SRX-series devices.

**Options**    mss *value* —TCP MSS for GRE packets. Value is optional.  
              **Range:** 64 through 63535 bytes  
              **Default:** 1320 bytes, if no value is specified

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.



**gre-out**

---

**Syntax**   gre-out {  
              mss *value* ;  
          }

**Hierarchy Level**   [edit security flow tcp-mss]

**Release Information**   Statement introduced in Release 8.5 of JUNOS software.

**Description**   Enable and specify the TCP maximum segment size (TCP MSS) for Generic Routing Encapsulation (GRE) packets that are going into an IPsec VPN tunnel. If the device receives a GRE-encapsulated TCP packet with the SYN bit and TCP MSS option set and the TCP MSS option specified in the packet exceeds the TCP MSS specified by the device, the device modifies the TCP MSS value accordingly. By default, a TCP MSS for GRE packets is not set.

This statement is supported on J-series and SRX-series devices.

**Options**   mss *value* —TCP MSS for GRE packets. Value is optional.  
              **Range:** 64 through 65535 bytes  
              **Default:** 1320 bytes

**Usage Guidelines**   For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**   security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## group-members

---

<b>Syntax</b>	group-members [attack-group-name   attack-name];
<b>Hierarchy Level</b>	[edit security idp custom-attack-group <i>custom-attack-group-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify the group members in a custom group. The members can be predefined attacks, predefined attack groups, custom attacks, or custom dynamic groups.</p> <p>Use custom groups for the following tasks:</p> <ul style="list-style-type: none"> <li>■ To define a specific set of attacks to which you know your network is vulnerable.</li> <li>■ To group your custom attack objects.</li> <li>■ To define a specific set of informational attack objects that you use to keep you aware of what is happening on your network.</li> </ul> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>attack-group-name—Name of the group attack object.</p> <p>attack-name—Name of the attack object.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**h323**

```

Syntax  h323 {
            application-screen {
                message-flood {
                    gatekeeper threshold rate ;
                }
                unknown-message {
                    permit-nat-applied;
                    permit-routed;
                }
            }
            disable;
            endpoint-registration-timeout seconds ;
            media-source-port-any;
            traceoptions {
                flag {
                    all <detail | extensive | terse>;
                    cc <detail | extensive | terse>;
                    h225-asn1 <detail | extensive | terse>;
                    h245 <detail | extensive | terse>;
                    h245-asn1 <detail | extensive | terse>;
                    q931 <detail | extensive | terse>;
                    ras <detail | extensive | terse>;
                    ras-asn1 <detail | extensive | terse>;
                }
            }
        }

```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the H.323 Application Layer Gateway (ALG) on the device. H.323 is a control-signaling protocol used to exchange messages between H.323 endpoints.

This statement is supported on J-series devices.

**Options** **disable**—Disable the H.323 ALG. By default, H.323 ALG is enabled.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## header-length

---

<b>Syntax</b>	header-length { match (equal   greater-than   less-than   not-equal); value <i>header-length</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the number of bytes in the TCP header.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>header-length</i> —Match the number of bytes in the TCP header. <b>Range:</b> 0 through 15 bytes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## high-watermark

---

<b>Syntax</b>	high-watermark <i>percent</i> ;
<b>Hierarchy Level</b>	[edit security flow aging]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Sets the point at which the aggressive aging-out process begins.  This statement is supported on J-series devices.
<b>Options</b>	<i>percent</i> —Percentage of session-table capacity at which aggressive aging-out starts. <b>Range:</b> 1 through 100 percent <b>Default:</b> 100 percent
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## host-address-base

---

<b>Syntax</b>	host-address-base <i>ip-address</i> ;
<b>Hierarchy Level</b>	[edit security nat source pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the base address of the original source IP address range. This is used for IP shifting.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>ip-address</i> —IPv4 address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## host-address-low

---

<b>Syntax</b>	host-address-low <i>ip-address</i> ;
<b>Hierarchy Level</b>	[edit security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the starting address in the original source address range of a static Network Address Translation (NAT) source pool.  This statement is supported on J-series devices.
<b>Options</b>	<i>ip-address</i> —IPv4 address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## host-inbound-traffic

---

**Syntax**    host-inbound-traffic {  
               protocols {  
                   protocol-name ;  
                   protocol-name <except>;  
               }  
               system-services {  
                   service-name ;  
                   service-name <except>;  
               }  
              }

**Hierarchy Level**    [edit security zones functional-zone management],  
                          [edit security zones functional-zone management interfaces *interface-name*],  
                          [edit security zones security-zone *zone-name*],  
                          [edit security zones security-zone *zone-name* interfaces *interface-name*]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Control the type of traffic that can reach the device from interfaces bound to the zone.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## hostname

---

<b>Syntax</b>	hostname <i>domain-name</i> ;
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Unique name by which a network-attached device is known on a network.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>domain-name</i> —A fully qualified domain name (FQDN).
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## icmp

---

See the following sections:

- icmp (Protocol Binding Custom Attack) on page 332
- icmp (Security Screen) on page 333
- icmp (Signature Attack) on page 334

### ***icmp (Protocol Binding Custom Attack)***

<b>Syntax</b>	icmp;
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain protocol-binding] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol-binding]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Allow IDP to match the attack for specified ICMP.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



**icmp (Security Screen)**

**Syntax** icmp {  
     flood {  
         threshold *number* ;  
     }  
     fragment;  
     ip-sweep {  
         threshold *number*;  
     }  
     large;  
     ping-death;  
 }

**Hierarchy Level** [edit security screen ids-option *screen-name* ]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure ICMP intrusion detection service (IDS) options.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**icmp (Signature Attack)**

**Syntax** icmp {  
     code {  
         match (equal | greater-than | less-than | not-equal);  
         value *code-value* ;  
     }  
     data-length {  
         match (equal | greater-than | less-than | not-equal);  
         value *data-length* ;  
     }  
     identification {  
         match (equal | greater-than | less-than | not-equal);  
         value *identification-value* ;  
     }  
     sequence-number {  
         match (equal | greater-than | less-than | not-equal);  
         value *sequence-number* ;  
     }  
     type {  
         match (equal | greater-than | less-than | not-equal);  
         value *type-value* ;  
     }  
 }

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type signature protocol]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Allow IDP to match the ICMP header information for the signature attack.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## identification

---

See the following sections:

- identification (ICMP Headers in Signature Attack) on page 335
- identification (IP Headers in Signature Attack) on page 336

### ***identification (ICMP Headers in Signature Attack)***

**Syntax**    identification {  
                   match (equal | greater-than | less-than | not-equal);  
                   value *identification-value*;  
                   }

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol icmp]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify a unique value used by the destination system to associate requests and replies.

This statement is supported on SRX-series devices.

**Options**    match (equal | greater-than | less-than | not-equal)—Match an operand.

value *identification-value* —Match a decimal value.

**Range:** 0 through 65535

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                   security-control—To add this statement to the configuration.

**identification (IP Headers in Signature Attack)**

<b>Syntax</b>	<pre> identification {     match (equal   greater-than   less-than   not-equal);     value <i>identification-value</i>; } </pre>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol ip]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify a unique value used by the destination system to reassemble a fragmented packet.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>match (equal   greater-than   less-than   not-equal)—Match an operand.</p> <p>value <i>identification-value</i> —Match a decimal value.</p> <p><b>Range:</b> 0 through 65535</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**idle-time**

---

<b>Syntax</b>	idle-time <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the maximum amount of idle time to delete a security association (SA).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>seconds</i> —Maximum amount of idle time.</p> <p><b>Range:</b> 60 through 999999 seconds</p> <p><b>Default:</b> To be disabled</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**idp**

```

Syntax  idp {
    active-policy policy-name ;
    custom-attack attack-name {
        attack-type {
            anomaly {
                direction (any | client-to-server | server-to-client);
                service service-name ;
                shellcode (all | intel | no-shellcode | sparc);
                test test-condition ;
            }
            chain {
                expression boolean-expression ;
                member member-name {
                    attack-type {
                        (anomaly | signature);
                    }
                }
            }
            order;
            protocol-binding {
                application application-name ;
                icmp;
                ip {
                    protocol-number transport-layer-protocol-number ;
                }
                rpc {
                    program-number rpc-program-number ;
                }
                tcp {
                    minimum-port port-number maximum-port port-number ;
                }
                udp {
                    minimum-port port-number maximum-port port-number ;
                }
            }
            reset;
            scope (session | transaction);
        }
    }
    signature {
        context context-name ;
        direction (any | client-to-server | server-to-client);
        negate;
        pattern signature-pattern ;
        protocol {
            icmp {
                code {
                    match (equal | greater-than | less-than | not-equal);
                    value code-value ;
                }
                data-length {
                    match (equal | greater-than | less-than | not-equal);
                    value data-length ;
                }
            }
        }
    }
}

```

```

    }
    identification {
        match (equal | greater-than | less-than | not-equal);
        value identification-value ;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number ;
    }
    type {
        match (equal | greater-than | less-than | not-equal);
        value type-value ;
    }
}
ip {
    destination {
        match (equal | greater-than | less-than | not-equal);
        value hostname ;
    }
    identification {
        match (equal | greater-than | less-than | not-equal);
        value identification-value ;
    }
    ip-flags {
        (df | no-df);
        (mf | no-mf);
        (rb | no-rb);
    }
    protocol {
        match (equal | greater-than | less-than | not-equal);
        value transport-layer-protocol-id ;
    }
    source {
        match (equal | greater-than | less-than | not-equal);
        value hostname ;
    }
    tos {
        match (equal | greater-than | less-than | not-equal);
        value type-of-service-in-decimal ;
    }
    total-length {
        match (equal | greater-than | less-than | not-equal);
        value total-length-of-ip-datagram ;
    }
    ttl {
        match (equal | greater-than | less-than | not-equal);
        value time-to-live ;
    }
}
tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number ;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);

```

```

    value tcp-data-length ;
}
destination-port {
    match (equal | greater-than | less-than | not-equal);
    value destination-port ;
}
header-length {
    match (equal | greater-than | less-than | not-equal);
    value header-length ;
}
mss {
    match (equal | greater-than | less-than | not-equal);
    value maximum-segment-size ;
}
option {
    match (equal | greater-than | less-than | not-equal);
    value tcp-option ;
}
sequence-number {
    match (equal | greater-than | less-than | not-equal);
    value sequence-number ;
}
source-port {
    match (equal | greater-than | less-than | not-equal);
    value source-port ;
}
tcp-flags {
    (ack | no-ack);
    (fin | no-fin);
    (psh | no-psh);
    (r1 | no-r1);
    (r2 | no-r2);
    (rst | no-rst);
    (syn | no-syn);
    (urg | no-urg);
}
urgent-pointer {
    match (equal | greater-than | less-than | not-equal);
    value urgent-pointer ;
}
window-scale {
    match (equal | greater-than | less-than | not-equal);
    value window-scale-factor ;
}
window-size {
    match (equal | greater-than | less-than | not-equal);
    value window-size ;
}
}
udp {
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);

```

```

        value destination-port ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
}
protocol-binding {
    application application-name ;
    icmp;
    ip {
        protocol-number transport-layer-protocol-number ;
    }
    rpc {
        program-number rpc-program-number ;
    }
    tcp {
        minimum-port port-number maximum-port port-number ;
    }
    udp {
        minimum-port port-number maximum-port port-number ;
    }
}
regexp regular-expression ;
shellcode (all | intel | no-shellcode | sparc);
}
}
recommended-action (close | close-client | close-server | drop |
drop-packet | ignore | none);
severity (critical | info | major | minor | warning);
time-binding {
    count count-value ;
    scope (destination | peer | source);
}
}
custom-attack-group custom-attack-group-name {
    group-members [attack-group-name | attack-name];
}
dynamic-attack-group dynamic-attack-group-name {
    filters {
        category {
            values [list-of-values];
        }
        direction {
            values [any | client-to-server | exclude-any | exclude-client-to-server |
exclude-server-to-client | server-to-client];
        }
        false-positives {
            values [frequently | occasionally | rarely | unknown];
        }
        performance {
            values [fast | normal | slow | unknown];
        }
        products {
            values [list-of-values];
        }
    }
}

```



```

    }
    recommended;
    service {
        values [list-of-values];
    }
    severity {
        values [critical | info | major | minor | warning];
    }
    type {
        values [anomaly | signature];
    }
}
}
idp-policy policy-name {
    rulebase-exempt {
        rule rule-name {
            description text ;
            match {
                attacks {
                    custom-attacks [ attack-name ];
                    predefined-attack-groups [ attack-name ];
                    predefined-attacks [ attack-name ];
                }
                destination-address [ address-name ];
                destination-except [ address-name ];
                from-zone zone-name ;
                source-address [ address-name ];
                source-except [ address-name ];
                to-zone zone-name ;
            }
        }
    }
}
rulebase-ips {
    rule rule-name {
        description text ;
        match {
            attacks {
                custom-attacks [ attack-name ];
                predefined-attack-groups [ attack-name ];
                predefined-attacks [ attack-name ];
            }
            destination-address [ address-name ];
            destination-except [ address-name ];
            from-zone zone-name ;
            source-address [ address-name ];
            source-except [ address-name ];
            to-zone zone-name ;
        }
    }
    terminal;
    then {
        action {
            (close-client | close-client-and-server | close-server |
             drop-connection | drop-packet | ignore-connection |
             mark-diffserv value | no-action | recommended);
        }
        ip-action {

```

```

        (ip-block | ip-close | ip-notify);
        log;
        target (destination-address | service | source-address |
        source-zone | zone-service);
        timeout seconds;
    }
    notification {
        log-attacks {
            alert (yes | no);
        }
    }
    severity (critical | info | major | minor | warning);
}
}
}
}
security-package {
    automatic {
        enable;
        interval hours ;
        start-time start-time ;
    }
    url url-name ;
}
sensor-configuration {
    application-identification {
        application-system-cache;
        application-system-cache-timeout value ;
        check-first-session;
        disable;
        max-packet-memory value ;
        max-sessions value ;
        max-tcp-session-packet-memory value ;
        max-udp-session-packet-memory value ;
    }
    detector {
        protocol-name protocol-name {
            tunable-name tunable-name {
                tunable-value protocol-value ;
            }
        }
    }
}
flow {
    (allow-icmp-without-flow | no-allow-icmp-without-flow);
    (log-errors | no-log-errors);
    max-timers-poll-ticks value ;
    reject-timeout value ;
    (reset-on-policy | no-reset-on-policy);
}
global {
    (enable-all-qmodules | no-enable-all-qmodules);
    (enable-packet-pool | no-enable-packet-pool);
    (policy-lookup-cache | no-policy-lookup-cache);
}
ips {
    detect-shellcode;

```

```

        ignore-regular-expression;
        log-supercede-min minimum-value ;
        pre-filter-shellcode;
        process-ignore-s2c;
        process-override;
        process-port port-number ;
    }
    log {
        cache-size size ;
        suppression {
            disable;
            include-destination-address;
            max-logs-operate value ;
            max-time-report value ;
            start-log value ;
        }
    }
    re-assembler {
        ignore-mem-overflow;
        max-flow-mem value ;
        max-packet-mem value ;
    }
}
traceoptions {
    file filename {
        <files number >;
        <match regular-expression >;
        <size maximum-file-size >;
        <world-readable | no-world-readable>;
    }
    flag all;
    level (all | error | info | notice | verbose | warning);
    no-remote-trace;
}
}

```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement modified in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Configure Intrusion Detection and Prevention (IDP) to selectively enforce various IDP attack detection and prevention techniques on the network.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## idp-policy

---

```

Syntax idp-policy policy-name {
    rulebase-exempt {
        rule rule-name {
            description text ;
            match {
                attacks {
                    custom-attacks [ attack-name ];
                    predefined-attack-groups [ attack-name ];
                    predefined-attacks [ attack-name ];
                }
                destination-address [ address-name ];
                destination-except [ address-name ];
                from-zone zone-name ;
                source-address [ address-name ];
                source-except [ address-name ];
                to-zone zone-name ;
            }
        }
    }
    rulebase-ips {
        rule rule-name {
            description text ;
            match {
                attacks {
                    custom-attacks [ attack-name ];
                    predefined-attack-groups [ attack-name ];
                    predefined-attacks [ attack-name ];
                }
                destination-address [ address-name ];
                destination-except [ address-name ];
                from-zone zone-name ;
                source-address [ address-name ];
                source-except [ address-name ];
                to-zone zone-name ;
            }
        }
        terminal;
        then {
            action {
                (close-client | close-client-and-server | close-server |
                 drop-connection | drop-packet | ignore-connection |
                 mark-diffserv value | no-action | recommended);
            }
            ip-action {
                (ip-block | ip-close | ip-notify);
                log;
                target (destination-address | service | source-address |
                     source-zone | zone-service);
                timeout seconds;
            }
            notification {
                log-attacks {

```

```
        alert (yes | no);(  
    }  
} severity (critical | info | major | minor | warning);  
}  
}  
}
```

<b>Hierarchy Level</b>	[edit security idp]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Configure a security IDP policy.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>policy-name</i> —Name of the IDP policy.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ids-option

---

**Syntax** `ids-option {`

```

    screen-name {
        alarm-without-drop;
        icmp {
            flood {
                threshold number ;
            }
            fragment;
            ip-sweep {
                threshold number ;
            }
            large;
            ping-death;
        }
        ip {
            bad-option;
            block-frag;
            loose-source-route-option;
            record-route-option;
            security-option;
            source-route-option;
            spoofing;
            stream-option;
            strict-source-route-option;
            tear-drop;
            timestamp-option;
            unknown-protocol;
        }
        limit-session {
            destination-ip-based number ;
            source-ip-based number ;
        }
        tcp {
            fin-no-ack;
            land;
            port-scan {
                threshold number ;
            }
            syn-ack-ack-proxy {
                threshold number ;
            }
            syn-fin;
            syn-flood {
                alarm-threshold number ;
                attack-threshold number ;
                destination-threshold number ;
                source-threshold number ;
                timeout seconds ;
            }
            syn-frag;
            tcp-no-flag;

```

```

        winnuke;
    }
    udp {
        flood {
            threshold number ;
        }
    }
}

```

<b>Hierarchy Level</b>	[edit security screen]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Define screens for intrusion detection and prevention.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ignore-mem-overflow

---

<b>Syntax</b>	ignore-mem-overflow;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration re-assembler]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Enable the TCP reassembler to ignore the memory overflow to prevent the dropping of IDP custom applications. By default this feature is enabled.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ignore-regular-expression

---

<b>Syntax</b>	ignore-regular-expression;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Enable regular expression to detect intrusion attempts. By default this setting is disabled.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## ike

---

See the following sections:

- ike (IPsec VPN) on page 349
- ike (Security) on page 350

### **ike (IPsec VPN)**

**Syntax**    ike {  
               gateway gateway -name ;  
               idle-time seconds ;  
               install-interval seconds ;  
               ipsec-policy ipsec-policy-name ;  
               no-anti-replay;  
               proxy-identity {  
                   local ipv4-prefix ;  
                   remote ipv4-prefix ;  
                   service service-name ;  
               }  
           }

**Hierarchy Level**    [edit security ipsec vpn vpn-name ]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Define an IKE-keyed IPsec VPN.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

**ike (Security)**

```

Syntax   ike {
            gateway gateway-name {
                address [( ip-address | hostname )] |
                dead-peer-detection {
                    always-send;
                    interval seconds ;
                    threshold number ;
                }
                dynamic {
                    connections-limit number ;
                    distinguished-name {
                        container container-string ;
                        wildcard wildcard-string ;
                    }
                    hostname domain-name ;
                    ike-user-type (group-ike-id | shared-ike-id);
                    inet ip-address ;
                    user-at-hostname user-at-hostname ;
                }
                external-interface external-interface-name ;
                ike-policy policy-name ;
                local-identity (hostname hostname | inet ipv4-ip-address |
                user-at-hostname e-mail-address | distinguished-name string );
                nat-keepalive seconds ;
                no-nat-traversal;
                xauth {
                    access-profile profile-name ;
                }
            }
            policy policy-name {
                certificate {
                    local-certificate certificate-id ;
                    peer-certificate-type (pkcs7 | x509-signature);
                    trusted-ca ( ca-index | use-all);
                }
                description description ;
                mode (aggressive | main);
                pre-shared-key (ascii-text | hexadecimal);
                proposal-set <basic | compatible | standard>;
            }
            proposal proposal-name {
                authentication-algorithm (md5 | sha1 | sha-256);
                authentication-method (dsa-signatures | pre-shared-keys | rsa-signatures);
                description description ;
                dh-group (group1 | group2 | group5);
                encryption-algorithm (des-cbc | 3des-cbc | aes-128-cbc | aes-192-cbc
                | aes-256-cbc);
                lifetime-seconds seconds ;
            }
            respond-bad-spi number ;
            traceoptions {
                file {
                    files number ;
                    size maximum-file-size ;
                }
            }
        }

```

```
    }  
    flag {  
        all;  
        certificates;  
        database;  
        general;  
        ike;  
        parse;  
        policy-manager;  
        routing-socket;  
        timer;  
        snmp;  
    }  
}
```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Define Internet Key Exchange (IKE) configuration.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ike-policy

---

<b>Syntax</b>	ike-policy <i>policy-name</i> ;
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the IKE policy to be used for the gateway.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>policy-name</i> —IKE policy name.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ike-user-type

---

<b>Syntax</b>	ike-user-type (group-ike-id   shared-ike-id);
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the type of IKE user for a remote access connection.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>group-ike-id</b>—E-mail address or fully qualified domain name (FQDN) shared for a group of remote access users so that each one does not need a separate IKE profile configured.</p> <p><b>shared-ike-id</b>—E-mail address shared for a large number of remote access users so that each one does not need a separate IKE profile configured.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## inactive-media-timeout

---

See the following sections:

- inactive-media-timeout (MGCP) on page 353
- inactive-media-timeout (SCCP) on page 354
- inactive-media-timeout (SIP) on page 354

### ***inactive-media-timeout (MGCP)***

<b>Syntax</b>	inactive-media-timeout seconds ;
<b>Hierarchy Level</b>	[edit security alg mgcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the maximum amount of time that the temporary openings in the firewall (pinholes) remain open for media if no activity is detected.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	seconds —Maximum amount of time that the pinholes remain open. <b>Range:</b> 10 through 2550 seconds <b>Default:</b> 120 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

***inactive-media-timeout (SCCP)***

<b>Syntax</b>	<code>inactive-media-timeout seconds ;</code>
<b>Hierarchy Level</b>	[edit security alg sccp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the maximum amount of time that the temporary openings in the firewall (pinholes) remain open for media if no activity is detected.  This statement is supported on J-series devices.
<b>Options</b>	<code>seconds</code> —Maximum amount of time that the pinholes remain open. <b>Range:</b> 10 through 600 seconds <b>Default:</b> 120 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

***inactive-media-timeout (SIP)***

<b>Syntax</b>	<code>inactive-media-timeout seconds ;</code>
<b>Hierarchy Level</b>	[edit security alg sip]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the maximum amount of time that the temporary openings in the firewall (pinholes) remain open for media if no activity is detected.  This statement is supported on J-series devices.
<b>Options</b>	<code>seconds</code> —Maximum amount of time that the pinholes remain open. <b>Range:</b> 0 through 2550 seconds <b>Default:</b> 120 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## include-destination-address

---

<b>Syntax</b>	include-destination-address;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration log suppression]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>When log suppression is enabled, multiple occurrences of events with the same source, service, and matching attack object generate a single log record with a count of occurrences. If you enable this option, log suppression will only combine log records for events with a matching source as well. The IDP Sensor does not consider destination when determining matching events for log suppression. By default this setting is disabled.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## inet

---

<b>Syntax</b>	inet <i>ip-address</i> ;
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify IPv4 address to identify the dynamic peer.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>ip-address</i> —IPv4 address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## inet6

---

**Syntax**    `inet6 {  
                  mode packet-based;  
                  }`

**Hierarchy Level**    [edit security forwarding-options family]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Enable the forwarding of IPv6 traffic. By default, the device drops IPv6 traffic.



**NOTE:** JUNOS software security processing is not applied to IPv6 packets forwarded by the device.

---

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## install-interval

---

**Syntax**    `install-interval seconds ;`

**Hierarchy Level**    [edit security ipsec vpn *vpn-name* ike]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the maximum number of seconds to allow for the installation of a rekeyed outbound security association (SA) on the device.

This statement is supported on J-series and SRX-series devices.

**Options**    *seconds* —Maximum amount of idle time.  
                  **Range:** 0 through 10 seconds

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.



## interface

---

See the following sections:

- interface (ARP Proxy Services Gateway) on page 357
- interface (NAT Services Router) on page 358

### ***interface (ARP Proxy Services Gateway)***

**Syntax**    `interface interface-name {  
                  address ip-address to ip-address ;  
                  }`

**Hierarchy Level**    [edit security nat proxy-arp]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Specify the interface on which the ARP proxy is to be configured. It should be a logical interface.

This statement is supported on SRX-series devices.

**Options**    *interface-name* —Name of the logical interface.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

**interface (NAT Services Router)**

**Syntax** interface *interface-name* {  
     allow-incoming;  
     proxy-arp {  
         address *prefix* ;  
         address-range high *ip-address* low *ip-address* ;  
     }  
     source-nat {  
         pool *pool-name* {  
             address *prefix* ;  
             address-range high *ip-address* low *ip-address* ;  
             allow-incoming;  
             host-address-low *ip-address* ;  
             no-port-translation;  
             overflow-pool (interface | *pool-name* );  
         }  
     }  
     static-nat *ip-prefix* {  
         host *ip-prefix* ;  
         virtual-router *vr-name* ;  
     }  
 }

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the interface on which to configure NAT.

This statement is supported on J-series devices.

**Options** *interface-name* —Name of the interface.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## interfaces

---

<b>Syntax</b>	<pre> interfaces <i>interface-name</i> {     host-inbound-traffic {         protocols {             <i>protocol-name</i> ;             <i>protocol-name</i> &lt;except&gt;;         }         system-services {             <i>service-name</i> ;             <i>service-name</i> &lt;except&gt;;         }     } } </pre>
<b>Hierarchy Level</b>	[edit security zones functional-zone management], [edit security zones security-zone <i>zone-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the set of interfaces that are part of the zone.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>interface-name</i> —Name of the interface.  The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## interval

---

See the following sections:

- interval (IDP) on page 360
- interval (IKE) on page 360

### *interval (IDP)*

<b>Syntax</b>	<code>interval hours ;</code>
<b>Hierarchy Level</b>	[edit security idp security-package automatic]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the amount of time that the device waits before updating the signature database. User should insert a default value.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>hours</i> —Number of hours that the device waits. <b>Range:</b> 24 through 336 hours
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

### *interval (IKE)*

<b>Syntax</b>	<code>interval seconds ;</code>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dead-peer-detection]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the amount of time that the peer waits for traffic from its destination peer before sending a dead-peer-detection (DPD) request packet.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>seconds</i> —Number of seconds that the peer waits before sending a DPD request packet. <b>Range:</b> 0 through 60 seconds <b>Default:</b> 10 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**ip**

---

See the following sections:

- [ip \(Protocol Binding Custom Attack\)](#) on page 361
- [ip \(Security Screen\)](#) on page 362
- [ip \(Signature Attack\)](#) on page 364

***ip (Protocol Binding Custom Attack)***

**Syntax**    `ip {  
                  protocol-number transport-layer-protocol-number;  
                  }`

**Hierarchy Level**    `[edit security idp custom-attack attack-name attack-type chain protocol-binding]`  
                          `[edit security idp custom-attack attack-name attack-type signature protocol-binding]`

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Allow IDP to match the attack for a specified IP protocol type.

This statement is supported on SRX-series devices.

**Options**    `protocol-number transport-layer-protocol-number` —Transport Layer protocol number.  
                  **Range:** 0 through 139

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    `security`—To view this statement in the configuration.  
                                  `security-control`—To add this statement to the configuration.

**ip (Security Screen)**

**Syntax**    ip {  
               bad-option;  
               block-frag;  
               loose-source-route-option;  
               record-route-option;  
               security-option;  
               source-route-option;  
               spoofing;  
               stream-option;  
               strict-source-route-option;  
               tear-drop;  
               timestamp-option;  
               unknown-protocol;  
               }

**Hierarchy Level**    [edit security screen ids-option *screen-name* ]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure IP layer IDS options.

This statement is supported on J-series and SRX-series devices.

- Options**    ■ **bad-option**—Detect and drop any packet with an incorrectly formatted IP option in the IP packet header. The device records the event in the SCREEN counters list for the ingress interface.
- **block-frag**—Enable IP packet fragmentation blocking.
- **loose-source-route-option**—Detect packets where the IP option is 3 (Loose Source Routing), and record the event in the SCREEN counters list for the ingress interface. This option specifies a partial route list for a packet to take on its journey from source to destination. The packet must proceed in the order of addresses specified, but it is allowed to pass through other devices in between those specified.
- **record-route-option**—Detect packets where the IP option is 7 (Record Route), and record the event in the SCREEN counters list for the ingress interface.
- **security-option**—Detect packets where the IP option is 2 (security), and record the event in the SCREEN counters list for the ingress interface.
- **source-route-option**—Detect packets, and record the event in the SCREEN counters list for the ingress interface.
- **spoofing**—Prevent spoofing attacks. Spoofing attacks occur when unauthorized agents attempt to bypass firewall security by imitating valid client IP addresses. Using the spoofing option invalidates such false source IP address connections.
- The default behavior is to base spoofing decisions on individual interfaces.
- **stream-option**—Detect packets where the IP option is 8 (Stream ID), and record the event in the SCREEN counters list for the ingress interface.
- **strict-source-route-option**—Detect packets where the IP option is 9 (Strict Source Routing), and record the event in the SCREEN counters list for the ingress

interface. This option specifies the complete route list for a packet to take on its journey from source to destination. The last address in the list replaces the address in the destination field.

- **tear-drop**—Block the Teardrop attack. Teardrop attacks occur when fragmented IP packets overlap and cause the host attempting to reassemble the packets to crash. The tear-drop option directs the device to drop any packets that have such a discrepancy.
- **timestamp-option**—Detect packets where the IP option list includes option 4 (Internet Timestamp), and record the event in the SCREEN counters list for the ingress interface.
- **unknown-protocol**—Discard all received IP frames with protocol numbers greater than 137. Such protocol numbers are undefined or reserved.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**ip (Signature Attack)**

```

Syntax  ip {
            destination {
                match (equal | greater-than | less-than | not-equal);
                value hostname ;
            }
            identification {
                match (equal | greater-than | less-than | not-equal);
                value identification-value ;
            }
            ip-flags {
                (df | no-df);
                (mf | no-mf);
                (rb | no-rb);
            }
            protocol {
                match (equal | greater-than | less-than | not-equal);
                value transport-layer-protocol-id ;
            }
            source {
                match (equal | greater-than | less-than | not-equal);
                value hostname ;
            }
            tos {
                match (equal | greater-than | less-than | not-equal);
                value type-of-service-in-decimal ;
            }
            total-length {
                match (equal | greater-than | less-than | not-equal);
                value total-length-of-ip-datagram ;
            }
            ttl {
                match (equal | greater-than | less-than | not-equal);
                value time-to-live ;
            }
        }

```

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type signature protocol]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Allow IDP to match the IP header information for the signature attack.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



## ip-action

---

<b>Syntax</b>	<pre>ip-action {   (ip-block   ip-close   ip-notify);   log;   target (destination-address   service   source-address     source-zone   zone-service);   timeout seconds; }</pre>
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Specify the actions you want IDP to take against future connections that use the same IP address.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## ip-block

---

<b>Syntax</b>	ip-block;
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then ip-action]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Block future connections of any session that matches the IP action. If there is an IP action match with multiple rules, then the most severe IP action of all the matched rules is applied. The highest IP action priority (that is, the most severe action) is Drop/Block, then Close, then Notify.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## ip-close

---

<b>Syntax</b>	ip-close;
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then ip-action]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Close future connections of any new sessions that match the IP action by sending RST packets to the client and server.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## ip-flags

---

<b>Syntax</b>	<pre>ip-flags {   (df   no-df);   (mf   no-mf);   (rb   no-rb); }</pre>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol ip]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify that IDP looks for a pattern match whether or not the IP flag is set.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><b>df   no-df</b>—When set, the df (Don't Fragment) indicates that the packet cannot be fragmented for transmission. When unset, it indicates that the packet can be fragmented.</p> <p><b>mf   no-mf</b>—When set, the mf (More Fragments) indicates that the packet contains more fragments. When unset, it indicates that no more fragments remain.</p> <p><b>rb   no-rb</b>—When set, the rb (Reserved Bit) indicates that the bit is reserved.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## ip-notify

---

<b>Syntax</b>	ip-notify;
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then ip-action]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Do not take any action against future traffic, but do log the event. This is the default.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ips

---

<b>Syntax</b>	ips { detect-shellcode; ignore-regular-expression; log-supercede-min <i>minimum-value</i> ; pre-filter-shellcode; process-ignore-s2c; process-override; process-port <i>port-number</i> ; }
<b>Hierarchy Level</b>	[edit security idp sensor-configuration]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Configure IPS security policy sensor settings.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## ipsec-policy

---

<b>Syntax</b>	<code>ipsec-policy <i>ipsec-policy-name</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit security ipsec vpn <i>vpn-name</i> ike]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the IPsec policy name.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>ipsec-policy-name</i> —Name of the IPsec policy.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## ipsec-vpn

---

See the following sections:

- ipsec-vpn (Flow) on page 369
- ipsec-vpn (Policies) on page 370

### *ipsec-vpn (Flow)*

**Syntax** ipsec-vpn {  
    mss *value* ;  
}

**Hierarchy Level** [edit security flow tcp-mss]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the TCP maximum segment size (TCP MSS) for the TCP packets that are about to go into an IPsec VPN tunnel. This value overrides the value specified in the all-tcp-mss statement.

This statement is supported on J-series and SRX-series devices.

**Options** mss *value* —TCP MSS value for TCP packets entering an IPsec VPN tunnel. Value is optional.  
**Range:** 64 through 65535 bytes  
**Default:** 1320 bytes

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**ipsec-vpn (Policies)**

<b>Syntax</b>	<code>ipsec-vpn vpn-name ;</code>
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit tunnel]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Define IPsec name for VPN.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>vpn-name</i> —Name of the IPsec.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**ip-sweep**


---


<b>Syntax</b>	<code>ip-sweep {     threshold <i>number</i>; }</code>
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> icmp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure the device to detect and prevent an IP Sweep attack. An IP Sweep attack occurs when an attacker sends ICMP echo requests (pings) to multiple destination addresses. If a target host replies, the reply reveals the target's IP address to the attacker. If the device receives 10 ICMP echo requests within the number of microseconds specified in this statement, it flags this as an IP Sweep attack, and rejects the 11th and all further ICMP packets from that host for the remainder of the second.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>threshold number</i> —Maximum number of microseconds during which up to 10 ICMP echo requests from the same host are allowed into the router. More than 10 requests from a host during this period triggers an IP Sweep attack response on the router during the remainder of the second. <b>Range:</b> 1000 through 1000000 microseconds <b>Default:</b> 5000 microseconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**iso**


---

<b>Syntax</b>	iso { mode packet-based; }
<b>Hierarchy Level</b>	[edit security forwarding-options family]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Enable the forwarding of IS-IS traffic. By default, the device drops IS-IS traffic.

---

	<b>NOTE:</b> JUNOS software security processing is not applied to IS-IS packets forwarded by the device.
---	--

---

This statement is supported on J-series and SRX-series devices.

<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	To configure the IS-IS protocol, see the <i>JUNOS Software Interfaces and Routing Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**land**


---

<b>Syntax</b>	land;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> tcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Enable prevention of Land attacks by combining the SYN flood defense with IP spoofing protection. Land attacks occur when an attacker sends spoofed IP packets with headers containing the target's IP address for the source and destination IP addresses. The attacker sends these packets with the SYN flag set to any available port. The packets induce the target to create empty sessions with itself, filling its session table and overwhelming its resources.

---

This statement is supported on J-series and SRX-series devices.

<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## large

---

<b>Syntax</b>	large;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> icmp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the device to detect and drop any ICMP frame with an IP length greater than 1024 bytes.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## lifetime-kilobytes

---

<b>Syntax</b>	lifetime-kilobytes <i>kilobytes</i> ;
<b>Hierarchy Level</b>	[edit security ipsec proposal <i>proposal-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the lifetime (in kilobytes) of an IPsec security association (SA).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>kilobytes</i> —Lifetime of the IPsec security association (SA).</p> <p><b>Range:</b> 64 through 1048576 kilobytes</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>



## limit-session

---

<b>Syntax</b>	limit-session { destination-ip-based <i>number</i> ; source-ip-based <i>number</i> ; }
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Limit the number of concurrent sessions the device can initiate from a single source IP address or the number of sessions it can direct to a single destination IP address.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## local

---

<b>Syntax</b>	local <i>ipv4-prefix</i> ;
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike proxy-identity]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the local IP address and subnet mask for the proxy identity.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ipv4-prefix</i> —IP address and subnet mask.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## local-certificate

---

<b>Syntax</b>	<code>local-certificate <i>certificate-id</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit security ike policy <i>policy-name</i> certificate]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a particular certificate when the local device has multiple loaded certificates.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>certificate-id</i> —Name of the specific certificate to be used.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## local-identity

---

<b>Syntax</b>	local-identity (distinguished-name <i>string</i>   hostname <i>hostname</i>   inet <i>ipv4-ip-address</i>   user-at-hostname <i>e-mail-address</i> );
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the local IKE identity to send in the exchange with the destination peer so that the destination peer can communicate with the local peer. If you do not configure a local-identity, the device uses the IP address corresponding to the local endpoint by default.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<p>distinguished-name <i>string</i> —Specify identity as the distinguished name (DN) from the certificate. If there is more than one certificate on the device, use the <b>security ike gateway <i>gateway-name</i> policy <i>policy-name</i> certificate local-certificate <i>certificate-id</i></b> statement to specify a certificate.</p> <p>hostname <i>hostname</i> —Specify identity as a fully qualified domain name (FQDN).</p> <p>inet <i>ipv4-ip-address</i> —Specify identity as an IPv4 IP address.</p> <p>user-at-hostname <i>e-mail-address</i> —Specify identity as an e-mail address.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## log

---

See the following sections:

- [log \(IDP\) on page 376](#)
- [log \(IDP Policy\) on page 377](#)
- [log \(Security Policies\) on page 377](#)

### log (IDP)

**Syntax**

```
log {
  cache-size size ;
  suppression {
    disable;
    include-destination-address;
    max-logs-operate value ;
    max-time-report value ;
    start-log value ;
  }
}
```

**Hierarchy Level** [edit security idp sensor-configuration]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure IDP security policy logs.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**log (IDP Policy)**

<b>Syntax</b>	log;
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then ip-action]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Log the information about the IP action against the traffic that matches a rule.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**log (Security Policies)**

<b>Syntax</b>	log { session-close; session-init; }
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Enable traffic to which the policy applies to be logged at the beginning or end of a session.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## log-attacks

---

<b>Syntax</b>	log-attacks { alert (yes   no); }
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then notification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Enable the log attacks to create a log record that appears in the log viewer.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## log-errors

---

<b>Syntax</b>	(log-errors   no-log-errors);
<b>Hierarchy Level</b>	[edit security idp sensor-configuration flow]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Enable the error log to generate the result of success or failure about the flow. A flow-related error is when IDP receives a packet that does not fit into expected flow. By default error log is enabled.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## log-superscede-min

---

<b>Syntax</b>	log-superscede-min <i>minimum-value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the amount of time to supersede the IPS sensor logs.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>minimum-value</i> —Minimum time to supersede the log. <b>Range:</b> 0 through 65535 seconds <b>Default:</b> 1 second
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## low-watermark

---

<b>Syntax</b>	low-watermark <i>percent</i> ;
<b>Hierarchy Level</b>	[edit security flow aging]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Set the point at which the aggressive aging-out process ends.  This statement is supported on J-series devices.
<b>Options</b>	<i>percent</i> —Percentage of session-table capacity at which aggressive aging-out ends. <b>Range:</b> 0 through 100 percent <b>Default:</b> 100 percent
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## management

---

**Syntax**

```
management {
  host-inbound-traffic {
    protocols {
      protocol-name ;
      protocol-name <except>;
    }
    system-services {
      service-name ;
      service-name <except>;
    }
  }
  interfaces interface-name {
    host-inbound-traffic {
      protocols {
        protocol-name ;
        protocol-name <except>;
      }
      system-services {
        service-name ;
        service-name <except>;
      }
    }
  }
  screen screen-name ;
}
```

**Hierarchy Level** [edit security zones]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the host for out-of-band management interfaces. You can set firewall options in this zone to protect the management interface from different types of attacks. Because this zone cannot be specified in policies, traffic entering from this zone can only be traffic originating from the device itself and cannot transit out from any other zone.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



## manual

---

**Syntax**    manual {  
              authentication {  
                  algorithm (hmac-md5-96 | hmac-sha1-96);  
                  key (ascii-text *key* | hexadecimal *key* );  
              }  
              encryption {  
                  algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);  
                  key (ascii-text *key* | hexadecimal *key* );  
              }  
              external-interface *external-interface-name* ;  
              gateway *ip-address* ;  
              protocol (ah | esp);  
              spi *spi-value* ;  
           }

**Hierarchy Level**    [edit security ipsec vpn *vpn-name* ]

**Release Information**    Statement modified in Release 8.5 of JUNOS software.

**Description**    Define a manual IPsec security association (SA).

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

## match

---

See the following sections:

- [match \(Destination NAT Services Gateway\)](#) on page 382
- [match \(IDP Policy\)](#) on page 383
- [match \(Security Policies\)](#) on page 384
- [match \(Source NAT Services Gateway\)](#) on page 384
- [match \(Static NAT Services Gateway\)](#) on page 385

### **match (Destination NAT Services Gateway)**

**Syntax**    match {  
               destination-address *destination-address* ;  
               destination-port *port-number* ;  
               source-address [*source-address*];  
               }

**Hierarchy Level**    [edit security nat destination rule-set *rule-set-name* rule *rule-name* ]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Specify the destination rules to be used as match criteria.

This statement is supported on SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

**match (IDP Policy)**

<b>Syntax</b>	<pre> match {   attacks {     custom-attacks [ attack-name ];     predefined-attack-groups [ attack-name ];     predefined-attacks [ attack-name ];   }   destination-address [ address-name ];   destination-except [ address-name ];   from-zone zone-name ;   source-address [ address-name ];   source-except [ address-name ];   to-zone zone-name ; } </pre>
<b>Hierarchy Level</b>	<pre> [edit security idp idp-policy policy-name rulebase-exempt rule rule-name ], [edit security idp idp-policy policy-name rulebase-ips rule rule-name ] </pre>
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Specify the rules to be used as match criteria.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**match (Security Policies)**

**Syntax** match {  
     application [ *application-name-or-set* ];  
     destination-address {  
         *address-name* ;  
     }  
     source-address {  
         *address-name* ;  
     }  
 }

**Hierarchy Level** [edit security policies from-zone *zone-name* to-zone *zone-name* policy *policy-name*]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure security policy match criteria.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**match (Source NAT Services Gateway)**

**Syntax** match {  
     destination-address [destination-address];  
     source-address [source-address];  
 }

**Hierarchy Level** [edit security nat source rule-set *rule-set-name* rule *rule-name* ]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the source rules to be used as match criteria.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**match (Static NAT Services Gateway)**

<b>Syntax</b>	match { destination-address [destination-address]; }
<b>Hierarchy Level</b>	[edit security nat static rule-set <i>rule-set-name</i> rule <i>rule-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the static rules to be used as match criteria.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statement is explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**max-flow-mem**

---

<b>Syntax</b>	max-flow-mem <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration re-assembler]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Define the maximum TCP flow memory which IDP sensor can handle.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum TCP flow memory in kilobytes. <b>Range:</b> 64 through 4294967295 kilobytes <b>Default:</b> 1024 kilobytes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## max-logs-operate

---

<b>Syntax</b>	max-logs-operate <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration log suppression]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>When log suppression is enabled, IDP must cache log records so that it can identify when multiple occurrences of the same event occur. This setting specifies how many log records are tracked simultaneously by IDP.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>value</i> —Maximum number of log records are tracked by IDP.</p> <p><b>Range:</b> 256 through 65536 records</p> <p><b>Default:</b> 16384 records</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## max-packet-mem

---

<b>Syntax</b>	max-packet-mem <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration re-assembler]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Define the maximum TCP packet memory that the IDP sensor can handle.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>value</i> —Maximum TCP packet memory.</p> <p><b>Range:</b> 64 through 4294967295 kilobytes (KB)</p> <p><b>Default:</b> 262144 KB</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## max-packet-memory

---

<b>Syntax</b>	<code>max-packet-memory value ;</code>
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the maximum memory length of a packet in bytes.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum memory length in bytes. <b>Range:</b> 0 through 200000000 bytes <b>Default:</b> 100000000 bytes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## max-sessions

---

<b>Syntax</b>	<code>max-sessions value ;</code>
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the maximum number of sessions that IDP maintains. If the sensor reaches the maximum, it drops all new sessions.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum number of sessions. <b>Range:</b> 0 through 500000
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## max-tcp-session-packet-memory

---

<b>Syntax</b>	max-tcp-session-packet-memory <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the maximum number of TCP sessions that IDP maintains. If the sensor reaches the maximum, it drops all new TCP sessions.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum number of TCP sessions. <b>Range:</b> 0 through 60000
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## max-time-report

---

<b>Syntax</b>	max-time-report <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration log suppression]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	When log suppression is enabled, IDP maintains a count of multiple occurrences of the same event. After the specified number of seconds has passed, IDP writes a single log entry containing the count of occurrences.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Time after which IDP writes a single log entry containing the count of occurrences. <b>Range:</b> 1 through 60 seconds <b>Default:</b> 10 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## max-timers-poll-ticks

---

<b>Syntax</b>	max-timers-poll-ticks <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration flow]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the time at which timer ticks at regular interval.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum amount of time at which the timer ticks. <b>Range:</b> 0 through 1000 ticks <b>Default:</b> 1000 ticks
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## max-udp-session-packet-memory

---

<b>Syntax</b>	max-udp-session-packet-memory <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration application-identification]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the maximum number of UDP sessions that IDP maintains. If the sensor reaches the maximum, it drops all new UDP sessions.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum number of UDP sessions. <b>Range:</b> 0 through 20000
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## maximum-call-duration

---

<b>Syntax</b>	maximum-call-duration <i>minutes</i> ;
<b>Hierarchy Level</b>	[edit security alg mgcp], [edit security alg sip]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the time at which the SIP call ends. The media session is released after the call has ended.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>minutes</i> —Maximum amount of time at which the call ends and releases the media sessions. <b>Range:</b> 3 through 7200 minutes <b>Default:</b> 720 minutes
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## media-source-port-any

---

<b>Syntax</b>	media-source-port-any;
<b>Hierarchy Level</b>	[edit security alg h323]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Allow media traffic from any port number. By default, this feature is disabled, which allows a temporary opening in the firewall (pinhole) for media traffic to be opened.  This statement is supported on J-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## member

---

**Syntax**    `member member-name {  
                  attack-type {  
                    (anomaly | signature);  
                  }  
                }`

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type chain]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Create the list of member attacks.

This statement is supported on SRX-series devices.

**Options**    *member-name* —Name of the member list.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## message-flood

---

See the following sections:

- message-flood (H323) on page 392
- message-flood (MGCP) on page 393

### message-flood (H323)

**Syntax** message-flood {  
                   gatekeeper threshold *rate* ;  
                   }

**Hierarchy Level** [edit security alg h323 application-screen]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Limit the rate per second at which remote access server (RAS) requests to the gatekeeper are processed. Messages exceeding the threshold are dropped. This feature is disabled by default.

This statement is supported on J-series devices.

**Options** gatekeeper threshold *rate* —Maximum number of RAS connection requests per second allowed per gateway.  
**Range:** 1 through 65535  
**Default:** 1000

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**message-flood (MGCP)**

<b>Syntax</b>	message-flood threshold <i>rate</i> ;
<b>Hierarchy Level</b>	[edit security alg mgcp application-screen]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Limits the rate per second at which message requests to the Media Gateway are processed. Messages exceeding the threshold are dropped by the Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG). This feature is disabled by default.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>threshold <i>rate</i> —Number of connection requests per second allowed per Media Gateway.</p> <p><b>Range:</b> 2 through 50000</p> <p><b>Default:</b> 1000</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**mgcp**

---

**Syntax**

```
mgcp {
  application-screen {
    connection-flood threshold rate ;
    message-flood threshold rate ;
    unknown-message {
      permit-nat-applied;
      permit-routed;
    }
  }
  disable;
  inactive-media-timeout seconds ;
  maximum-call-duration minutes ;
  traceoptions {
    flag {
      all <extensive>;
      call <extensive>;
      cc <extensive>;
      decode <extensive>;
      error <extensive>;
      nat <extensive>;
      packet <extensive>;
      rm <extensive>;
    }
  }
  transaction-timeout seconds ;
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Specify the Media Gateway Control Protocol (MGCP) ALG on the device. MGCP is a text-based Application Layer protocol that can be used for call setup and call control.

This statement is supported on J-series and SRX-series devices.

**Options** **disable**—Disable the MGCP ALG. By default, the MGCP ALG is enabled.



**NOTE:** By default, the MGCP ALG is disabled for SRX-series devices.

---

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## mode

---

See the following sections:

- `mode (Forwarding-Options)` on page 395
- `mode (Policy)` on page 396

### ***mode (Forwarding-Options)***

**Syntax** `mode packet-based;`

**Hierarchy Level** [edit security forwarding-options family]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Enable packet forwarding for the selected protocol family. By default, the device drops traffic for the protocol family.

This statement is supported on J-series and SRX-series devices.

**Options** `packet-based`— Perform simple packet forwarding.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Interfaces and Routing Configuration Guide*.

**Required Privilege Level** `security`—To view this statement in the configuration.  
`security-control`—To add this statement to the configuration.

**mode (Policy)**


<b>Syntax</b>	mode (aggressive   main);
<b>Hierarchy Level</b>	[edit security ike policy <i>policy-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define the mode used for Internet Key Exchange (IKE) Phase 1 negotiations. Use aggressive mode only when you need to initiate an IKE key exchange without ID protection, as when a peer unit has a dynamically assigned IP address.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>■ aggressive—Aggressive mode.</li> <li>■ main—Main mode. Main mode is the recommended key-exchange method because it conceals the identities of the parties during the key exchange.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**mpls**


---

<b>Syntax</b>	mpls { mode packet-based; }
<b>Hierarchy Level</b>	[edit security forwarding-options family]
<b>Release Information</b>	Statement introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Enable the forwarding of MPLS traffic. By default, the device drops MPLS traffic.

---



**CAUTION:** Because MPLS is in operating packet mode, security services are not available.

---

This statement is supported on J-series and SRX-series devices.

<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Interfaces and Routing Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



**msrpc**

---

**Syntax**

```
msrpc {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Specify the Microsoft (MS) remote procedure call (RPC) ALG on the device.

This statement is supported on J-series devices.

**Options** **disable**—Disable the Microsoft RPC ALG. By default, the Microsoft RPC ALG is enabled.

**traceoptions**—Configure the Microsoft RPC ALG tracing options.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

■ **all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

**mss**

---

**Syntax**    mss {  
               match (equal | greater-than | less-than | not-equal);  
               value *maximum-segment-size*;  
               }

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol tcp]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify the maximum segment size (MSS) in the TCP header.

This statement is supported on SRX-series devices.

**Options**    match (equal | greater-than | less-than | not-equal)—Match an operand.

value *maximum-segment-size*—Match the maximum segment size value.

**Range:** 0 through 65535

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## **nat**

---

See the following sections:

- nat (Services Gateway Configuration) on page 400
- nat (Services Router Configuration) on page 402

**nat (Services Gateway Configuration)**

```

Syntax  nat {
    destination {
        pool pool-name {
            address < ip-address > (to ip-address | port port-number );
            routing-instance routing-instance-name ;
        }
        rule-set rule-set-name {
            from interface [interface-name] |
            routing-instance [routing-instance-name] | zone [zone-name];
            rule rule-name {
                match {
                    destination-address destination-address ;
                    destination-port port-number ;
                    source-address [source-address];
                }
                then {
                    destination-nat (off | pool pool-name );
                }
            }
        }
    }
    proxy-arp {
        interface interface-name {
            address ip-address to ip-address ;
        }
    }
    source {
        address-persistent;
        pool pool-name {
            address ip-address to ip-address ;
            host-address-base ip-address ;
            overflow-pool (interface | pool-name );
            port no-translation | range high ip-address low ip-address ;
            routing-instance routing-instance-name ;
        }
        pool-utilization-alarm {
            clear-threshold threshold-value ;
            raise-threshold threshold-value ;
        }
        rule-set rule-set-name {
            from interface [interface-name] |
            routing-instance [routing-instance-name] | zone [zone-name];
            rule rule-name {
                match {
                    destination-address [destination-address];
                    source-address [source-address];
                }
                then {
                    source-nat (off | interface | pool pool-name );
                }
            }
        }
        to interface [interface-name] |
        routing-instance [routing-instance-name] | zone [zone-name];
    }
}

```

```

}
static {
  rule-set rule-set-name {
    from interface [interface-name] |
    routing-instance [routing-instance-name] | zone [zone-name];
    rule rule-name {
      match {
        destination-address [destination-address];
      }
      then {
        static-nat prefix < addr-prefix >
        <routing-instance routing-instance-name >;
      }
    }
  }
}
}
traceoptions {
  file filename {
    <files number >;
    <match regular-expression >;
    <size maximum-file-size >;
    <world-readable | no-world-readable>;
  }
  flag {
    all;
    destination-nat-pfe;
    destination-nat-re;
    destination-nat-rt;
    source-nat-pfe;
    source-nat-re;
    source-nat-rt;
    static-nat-pfe;
    static-nat-re;
    static-nat-rt;
  }
  no-remote-trace;
}
}

```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement modified in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Configure Network Address Translation (NAT) for the services gateway.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**nat (Services Router Configuration)**

```

Syntax  nat {
    destination-nat destination-nat-name {
        address prefix <port port-number >;
        address-range high ip-address low ip-address ;
    }
    interface interface-name {
        allow-incoming;
        proxy-arp {
            address prefix ;
            address-range high ip-address low ip-address ;
        }
        source-nat {
            pool pool-name {
                address prefix ;
                address-range high ip-address low ip-address ;
                allow-incoming;
                host-address-low ip-address ;
                no-port-translation;
                overflow-pool (interface | pool-name );
            }
        }
        static-nat ip-prefix {
            host ip-prefix;
            virtual-router vr-name ;
        }
    }
    source-nat {
        address-persistent;
        pool-set pool-set-name {
            pool pool-name ;
        }
        pool-utilization-alarm {
            clear-threshold clear-threshold ;
            raise-threshold raise-threshold ;
        }
    }
    traceoptions {
        file filename {
            <files number >;
            <match regular-expression >;
            <size maximum-file-size >;
            <world-readable | no-world-readable>;
        }
        flag {
            all;
            configuration;
            flow;
            routing-protocol;
            routing-socket;
        }
    }
}

```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure Network Address Translation (NAT) for the Services Router.  This statement is supported on J-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## nat-keepalive

---

<b>Syntax</b>	nat-keepalive seconds ;
<b>Hierarchy Level</b>	[edit security ike gateway gateway-name ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the interval at which NAT keepalive packets can be sent so that NAT translation continues.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	seconds —Maximum interval in seconds at which NAT keepalive packets can be sent. <b>Range:</b> 1 through 300 seconds <b>Default:</b> 5 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## negate

---

<b>Syntax</b>	negate;
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Select negate to exclude the specified pattern from being matched.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## no-allow-icmp-without-flow

---

**See** allow-icmp-without-flow

## no-anti-replay

---

<b>Syntax</b>	no-anti-replay;
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike gateway gateway <i>-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Disable the antireplay checking feature of IPsec. By default, antireplay checking is enabled.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## no-enable-all-qmodules

---

**See** enable-all-qmodules



**no-enable-packet-pool**

---

**See** enable-packet-pool

**no-log-errors**

---

**See** log-errors

**no-nat-traversal**

---

**Syntax** no-nat-traversal;

**Hierarchy Level** [edit security ike gateway *gateway-name* ]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Disables UDP encapsulation of IPsec Encapsulating Security Payload (ESP) packets, otherwise known as Network Address Translation Traversal (NAT-T). NAT-T is enabled by default.

This statement is supported on J-series and SRX-series devices.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**no-policy-lookup-cache**

---

**See** policy-lookup-cache

## no-port-translation

---

<b>Syntax</b>	no-port-translation;
<b>Hierarchy Level</b>	[edit security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Disable Port Address Translation (PAT) for a source pool.</p> <p>This statement is supported on J-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## no-reset-on-policy

---

**See** reset-on-policy

## no-sequence-check

---

<b>Syntax</b>	no-sequence-check;
<b>Hierarchy Level</b>	[edit security flow tcp-session]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify that the device does not check sequence numbers in TCP segments during stateful inspection. By default, the device monitors the sequence numbers in TCP segments. The device detects the window scale specified by source and destination hosts in a session and adjusts a window for an acceptable range of sequence numbers according to their specified parameters. The device then monitors the sequence numbers in packets sent between these hosts. If the device detects a sequence number outside this range, it drops the packet.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## no-syn-check

---

<b>Syntax</b>	no-syn-check;
<b>Hierarchy Level</b>	[edit security flow tcp-session]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Disable checking of the TCP SYN bit before creating a session. By default, the device checks that the SYN bit is set in the first packet of a session. If the bit is not set, the device drops the packet.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## no-syn-check-in-tunnel

---

<b>Syntax</b>	no-syn-check-in-tunnel;
<b>Hierarchy Level</b>	[edit security flow tcp-session]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Disable checking of the TCP SYN bit before creating a session for tunneled packets. By default, the device checks that the SYN bit is set in the first packet of a VPN session. If the bit is not set, the device drops the packet.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## notification

---

<b>Syntax</b>	notification { log-attacks { alert (yes   no); } }
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Configure the logging options against the action. When attacks are detected, you can choose to log an attack and create log records with attack information and send that information to the log server.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## optimized

---

<b>Syntax</b>	optimized;
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> vpn-monitor]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that the device uses traffic patterns as evidence of peer liveliness. If enabled, ICMP requests are suppressed. This feature is disabled by default.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## option

---

<b>Syntax</b>	option { match (equal   greater-than   less-than   not-equal); value <i>tcp-option</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the TCP option kind in the TCP header.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>tcp-option</i> —Match the option value. <b>Range:</b> 0 through 255
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## order

---

<b>Syntax</b>	order;
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Create a compound attack object that must match each member signature or protocol anomaly in the order you specify. If you do not specify an ordered match, the compound attack object still must match all members, but the attacks or protocol anomalies can appear in random order.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## overflow-pool

---

See the following sections:

- overflow-pool (Source NAT Services Gateway) on page 410
- overflow-pool (Source NAT Services Router) on page 411

### **overflow-pool (Source NAT Services Gateway)**

**Syntax** overflow-pool (interface | pool-name);

**Hierarchy Level** [edit security nat source pool pool-name]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify a source pool to use when the current address pool is exhausted.

This statement is supported on SRX-series devices.

**Options** interface — Interfaces IP address.

pool-name — Defined source pool (created with the security nat source pool pool-name statement). The source pool must have Port Address Translation (PAT) enabled.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security — To view this statement in the configuration.  
security-control — To add this statement to the configuration.

**overflow-pool (Source NAT Services Router)**

<b>Syntax</b>	overflow-pool (interface   <i>pool-name</i> );
<b>Hierarchy Level</b>	[edit security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a source pool to use when the current pool is exhausted.  This statement is supported on J-series devices.
<b>Options</b>	interface—Interface source pool.  <i>pool-name</i> —Defined source pool (created with the security nat interface <i>interface-name</i> source-nat pool <i>pool-name</i> statement). The source pool must have Port Address Translation (PAT) enabled and be defined under the same interface.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## pair-policy

---

<b>Syntax</b>	<code>pair-policy pair-policy ;</code>
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit tunnel]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Link the policy that you are configuring with another policy that references the same VPN tunnel so that both policies share one proxy ID and one security association (SA). Policy pairing is useful when you want to allow bidirectional traffic over a policy-based VPN that is using source or destination address translation with a dynamic IP address pool or destination address translation with a mapped IP (MIP) or dynamic IP (DIP) address pool.</p> <p>Without policy pairing, the device derives a different proxy ID from the outbound and inbound policies. Two proxy IDs causes a problem for the remote peer with a single proxy ID for the VPN tunnel.</p> <p>Pairing two policies solves the proxy ID problem for the remote peer and conserves SA resources. The single proxy ID is derived from the policy you configured last.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## pass-through

---

**Syntax**    `pass-through {  
              access-profile profile-name ;  
              client-match match-name ;  
              web-redirect;  
              }`

**Hierarchy Level**    `[edit security policies from-zone zone-name to-zone zone-name policy policy-name  
                          then permit firewall-authentication]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure pass-through firewall user authentication. The user needs to use an FTP, Telnet, or HTTP client to access the IP address of the protected resource in another zone. Subsequent traffic from the user or host is allowed or denied based on the result of this authentication. Once authenticated, the firewall proxies the connection.

This statement is supported on J-series and SRX-series devices.

- Options**
- `access-profile profile-name` —(Optional) Name of the access profile.
  - `client-match match-name` —(Optional) Specify the name of the users or user groups in a profile who are allowed access by this policy. If you do not specify any users or user groups, any user who is successfully authenticated is allowed access.
  - `web-redirect`—(Optional) Enable redirecting an HTTP request to the device and redirecting the client system to a Web page for authentication. Including this statement allows users an easier authentication process because they need to know only the name or IP address of the resource they are trying to access.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## pattern

---

<b>Syntax</b>	<code>pattern signature-pattern ;</code>
<b>Hierarchy Level</b>	<code>[edit security idp custom-attack attack-name attack-type signature]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the pattern IDP should match. You construct the attack pattern just as you would when creating a new signature attack object.  This statement is supported on SRX-series devices.
<b>Options</b>	<code>signature-pattern</code> —Specify the signature pattern.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## peer-certificate-type

---

<b>Syntax</b>	<code>peer-certificate-type (pkcs7   x509-signature);</code>
<b>Hierarchy Level</b>	<code>[edit security ike policy policy-name certificate]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a preferred type of certificate (PKCS7 or X509).  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<ul style="list-style-type: none"> <li>■ <code>pkcs7</code>—Public-Key Cryptography Standard #7.</li> <li>■ <code>x509-signature</code>—X509 is an ITU-T standard for public key infrastructure.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## perfect-forward-secrecy

---

<b>Syntax</b>	perfect-forward-secrecy keys (group1   group2   group5);
<b>Hierarchy Level</b>	[edit security ipsec policy <i>policy-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify Perfect Forward Secrecy (PFS) as the method that the device uses to generate the encryption key. PFS generates each new encryption key independently from the previous key.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>group1—Diffie-Hellman Group 1.</p> <p>group2—Diffie-Hellman Group 2.</p> <p>group5—Diffie-Hellman Group 5.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## performance

---

<b>Syntax</b>	performance { values [fast   normal   slow   unknown]; }
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a performance filter to add attack objects based on the performance level that is vulnerable to the attack.  This statement is supported on SRX-series devices.
<b>Options</b>	<p>values—Name of the performance filter. You can select from the following performance level:</p> <ul style="list-style-type: none"> <li>■ fast—Fast track performance level.</li> <li>■ normal—Normal track performance level.</li> <li>■ slow—Slow track performance level.</li> <li>■ unknown—By default, all compound attack objects are set to Unknown. As you fine-tune IDP to your network traffic, you can change this setting to help you track performance level.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## permit

---

**Syntax**

```

permit {
  application-services (wx-redirect | wx-reverse-redirect);
  destination-address {
    drop-translated;
    drop-untranslated;
  }
  destination-nat destination-name ;
  firewall-authentication {
    pass-through {
      access-profile profile-name ;
      client-match match-name ;
      web-redirect;
    }
    web-authentication {
      client-match user-or-group ;
    }
  }
  source-nat (pool pool-name | pool-set pool-set-name | interface);
  tunnel {
    ipsec-vpn vpn-name ;
    pair-policy pair-policy ;
  }
}

```

**Hierarchy Level** [edit security policies from-zone *zone-name* to-zone *zone-name* policy *policy-name* then]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the policy action to perform when packets match the defined criteria.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## ping-death

---

<b>Syntax</b>	ping-death;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> icmp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the device to detect and reject oversized and irregular ICMP packets. Although the TCP/IP specification requires a specific packet size, many ping implementations allow larger packet sizes. Larger packets can trigger a range of adverse system reactions, including crashing, freezing, and restarting.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**pki**

```

Syntax  pki {
            auto-re-enrollment {
                certificate-id certificate-id-name {
                    ca-profile-name ca-profile-name ;
                    challenge-password password ;
                    re-enroll-trigger-time-percentage percentage ;
                    re-generate-keypair;
                }
            }
            ca-profile ca-profile-name {
                administrator {
                    e-mail-address e-mail-address ;
                }
                ca-identity ca-identity ;
                enrollment {
                    retry number;
                    retry-interval seconds;
                    url url-name;
                }
                revocation-check {
                    crl {
                        disable {
                            on-download-failure;
                        }
                        refresh-interval hours ;
                        url url-name ;
                    }
                    disable;
                }
            }
            traceoptions {
                file filename <files number > <match regular-expression>
                <size maximum-file-size > <world-readable | no-world-readable>
                flag flag ;
            }
        }

```

**Hierarchy Level** [edit security]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure an IPsec profile to request digital certificates.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**Related Topics** *JUNOS Feature Guide* and the *JUNOS System Basics and Services Command Reference*



## policies

---

```

Syntax  policies {
    default-policy {
        (deny-all | permit-all);
    }
    from-zone zone-name to-zone zone-name {
        policy policy-name {
            match {
                application [ application-name-or-set ];
                destination-address {
                    address-name ;
                }
                source-address {
                    address-name ;
                }
            }
        }
        scheduler-name scheduler-name ;
        then {
            count {
                alarm {
                    per-minute-threshold number;
                    per-second-threshold number ;
                }
            }
            (deny | reject);
            permit {
                application-services (wx-redirect | wx-reverse-redirect);
                destination-address {
                    drop-translated;
                    drop-untranslated;
                }
                destination-nat destination-name ;
                firewall-authentication {
                    pass-through {
                        access-profile profile-name ;
                        client-match match-name ;
                        web-redirect;
                    }
                    web-authentication {
                        client-match user-or-group ;
                    }
                }
            }
            source-nat (pool pool-name | pool-set pool-set-name | interface);
            tunnel {
                ipsec-vpn vpn-name ;
                pair-policy pair-policy ;
            }
        }
        log {
            session-close;
            session-init;
        }
    }
}

```

```

    }
  }
}
policy-match;
traceoptions {
  file filename <files number> <size maximum-file-size>
  <world-readable | no-world-readable>;
  flag flag ;
}
}

```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure network security policies.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## policy

---

See the following sections:

- policy (IKE) on page 423
- policy (IPsec) on page 424
- policy (Security) on page 425

### **policy (IKE)**

**Syntax**    `policy policy-name {`  
                   `certificate {`  
                     `local-certificate certificate-id ;`  
                     `peer-certificate-type (pkcs7 | x509-signature);`  
                     `trusted-ca ( ca-index | use-all);`  
                   `}`  
                   `description description ;`  
                   `mode (aggressive | main);`  
                   `pre-shared-key (ascii-text | hexadecimal);`  
                   `proposal-set <basic | compatible | standard>;`  
                   `}`

**Hierarchy Level**    [edit security ike]

**Release Information**    Statement modified in Release 8.5 of JUNOS software.

**Description**    Configure an IKE policy.

This statement is supported on J-series and SRX-series devices.

**Options**    *policy-name* —Name of the IKE policy. The policy name can be up to 32 alphanumeric characters long.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

**policy (IPsec)**

**Syntax**    `policy policy-name {  
                   description description ;  
                   perfect-forward-secrecy keys (group1 | group2 | group5);  
                   proposal-set (basic | compatible | standard);  
                   }`

**Hierarchy Level**    [edit security ipsec]

**Release Information**    Statement modified in Release 8.5 of JUNOS software.

**Description**    Define an IPsec policy.

This statement is supported on J-series and SRX-series devices.

**Options**    *policy-name* —Name of the IPsec policy.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                      security-control—To add this statement to the configuration.

**policy (Security)**

**Syntax** `policy policy-name {`  
     `match {`  
         `application [ application-name-or-set ];`  
         `destination-address {`  
             `address-name ;`  
         `}`  
         `source-address {`  
             `address-name ;`  
         `}`  
     `}`  
     `scheduler-name scheduler-name ;`  
     `then {`  
         `count {`  
             `alarm {`  
                 `per-minute-threshold number;`  
                 `per-second-threshold number ;`  
             `}`  
         `}`  
         `(deny | reject);`  
         `permit {`  
             `application-services (wx-redirect | wx-reverse-redirect);`  
             `destination-address {`  
                 `drop-translated;`  
                 `drop-untranslated;`  
             `}`  
             `destination-nat destination-name ;`  
             `firewall-authentication {`  
                 `pass-through {`  
                     `access-profile profile-name ;`  
                     `client-match match-name ;`  
                     `web-redirect;`  
                 `}`  
                 `web-authentication {`  
                     `client-match user-or-group ;`  
                 `}`  
             `}`  
             `source-nat (pool pool-name | pool-set pool-set-name | interface);`  
             `tunnel {`  
                 `ipsec-vpn vpn-name ;`  
                 `pair-policy pair-policy ;`  
             `}`  
         `}`  
         `log {`  
             `session-close;`  
             `session-init;`  
         `}`  
     `}`  
`}`

**Hierarchy Level** [edit security policies from-zone *zone-name* to-zone *zone-name* ]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Define a security policy.

This statement is supported on J-series and SRX-series devices.

**Options** *policy-name* —Name of the security policy.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## policy-lookup-cache

---

**Syntax** (policy-lookup-cache | no-policy-lookup-cache);

**Hierarchy Level** [edit security idp sensor-configuration global]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Enable cache to accelerate IDP policy lookup.

This statement is supported on SRX-series devices.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## policy-rematch

---

<b>Syntax</b>	policy-rematch;
<b>Hierarchy Level</b>	[edit security policies]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the device to add a policy that has just been modified to a deferred action list for reevaluation. For every session associated with the policy, the device reevaluates the policy lookup. If the policy is different from the one associated with the session, the device drops the session. If the policy matches, the session continues.</p> <p>The policy rematch feature is disabled by default.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## pool

---

See the following sections:

- pool (Destination NAT Services Gateway) on page 428
- pool (Pool Set) on page 429
- pool (Source NAT) on page 429
- pool (Source NAT Services Gateway) on page 430

### ***pool (Destination NAT Services Gateway)***

**Syntax** pool *pool-name* {  
     address < *ip-address* > (to *ip-address* | port *port-number* );  
     routing-instance *routing-instance-name* ;  
 }

**Hierarchy Level** [edit security nat destination]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Define a destination NAT pool to identify the pool uniquely.

This statement is supported on SRX-series devices.

**Options** *pool-name* —Name of the pool.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.



**pool (Pool Set)**

<b>Syntax</b>	<code>pool pool-name ;</code>
<b>Hierarchy Level</b>	<code>[edit security nat source-nat pool-set pool-set-name ]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Add a pool of Network Address Translation (NAT) source IP addresses for multiple concurrent sessions to a pool set.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<code>pool-name</code> —Name of the source pool.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**pool (Source NAT)**

<b>Syntax</b>	<pre>pool pool-name {     address prefix ;     address-range high ip-address low ip-address ;     allow-incoming;     host-address-low ip-address ;     no-port-translation;     overflow-pool (interface   pool-name ); }</pre>
<b>Hierarchy Level</b>	<code>[edit security nat interface interface-name source-nat]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define a Network Address Translation (NAT) pool of source IP addresses.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<p><code>pool-name</code> —Name of the pool.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**pool (Source NAT Services Gateway)**

<b>Syntax</b>	<pre>pool pool-name {     address ip-address to ip-address ;     host-address-base ip-address ;     overflow-pool (interface   pool-name );     port no-translation   range high ip-address low ip-address ;     routing-instance routing-instance-name ; }</pre>
<b>Hierarchy Level</b>	[edit security nat source]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Define a source NAT pool to identify the pool uniquely.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>pool-name</i> —Name of the pool.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**pool-set**


---

<b>Syntax</b>	<pre>pool-set pool-set-name {     pool pool-name ; }</pre>
<b>Hierarchy Level</b>	[edit security nat source-nat]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define a Network Address Translation (NAT) source IP address pools for multiple concurrent sessions set.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<p><i>pool-set-name</i> —Name of the pool set.</p> <p>The remaining statement is explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## pool-utilization-alarm

---

<b>Syntax</b>	<pre>pool-utilization-alarm {     clear-threshold <i>clear-threshold</i> ;     raise-threshold <i>raise-threshold</i> ; }</pre>
<b>Hierarchy Level</b>	[edit security nat source-nat], [edit security nat source]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Define the pool utilization alarm thresholds for a Network Address Translation (NAT) source IP address pool without Port Address Translation (PAT). When pool utilization exceeds the upper (raise) threshold or falls below the lower (clear) threshold, an SNMP trap is triggered.</p> <p>This statement is supported on J-series and SRX-series devices.</p> <p>The remaining statements are explained separately.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## port

---

<b>Syntax</b>	port no-translation   range high <i>ip-address</i> low <i>ip-address</i> ;
<b>Hierarchy Level</b>	[edit security nat source pool <i>pool-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the Port Address Translation (PAT) for a source pool.  This statement is supported on SRX-series devices.
<b>Options</b>	no-translation—If set, no Port Address Translation is required.  <i>range</i> high <i>ip-address</i> low <i>ip-address</i> —Specify the port number range attached to each address in the pool.  The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## port-scan

---

**Syntax**    port-scan {  
              threshold *number* ;  
              }

**Hierarchy Level**    [edit security screen ids-option *screen-name* tcp]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Prevent port scan attacks. A port scan attack occurs when an attacker sends packets with different port numbers to scan available services. The attack succeeds if a port responds. To prevent this attack, the device internally logs the number of different ports scanned from a single remote source. For example, if a remote host scans 10 ports in 0.005 seconds (equivalent to 5000 microseconds, the default threshold setting), the device flags this behavior as a port scan attack, and rejects further packets from the remote source.

This statement is supported on J-series and SRX-series devices.

**Options**    threshold *number* —Number of microseconds during which the device accepts packets from the same remote source with up to 10 different port numbers. If the number of ports during the threshold period reaches 10 or more, the device rejects additional packets from the source.  
              **Range:** 1000 through 1000000 microseconds  
              **Default:** 5000 microseconds

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                     security-control—To add this statement to the configuration.

**pptp**

---

**Syntax**

```
pptp {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the Point-to-Point Tunneling Protocol (PPTP) ALG on the device.

This statement is supported on J-series devices.

**Options** **disable**—Disable the PPTP ALG. By default, the PPTP ALG is enabled.

**traceoptions**—Configure PPTP ALG tracing options. To specify more than one trace operation, include multiple flag statements.

**flag**—Trace operation to perform.

**all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## pre-filter-shellcode

---

<b>Syntax</b>	pre-filter-shellcode;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Enable to pre-filter the shell code and protects it from buffer overflow attacks. By default this setting is enabled.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## predefined-attack-groups

---

<b>Syntax</b>	predefined-attack-groups [attack-name];
<b>Hierarchy Level</b>	<p>[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match attacks],</p> <p>[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match attacks]</p>
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Specify predefined attack groups that you can use to match the traffic against known attack objects. You can update only the list of attack objects.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<i>attack-name</i> —Name of the predefined attack object group.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## predefined-attacks

---

<b>Syntax</b>	<code>predefined-attacks [ attack-name ];</code>
<b>Hierarchy Level</b>	<code>[edit security idp idp-policy policy-name rulebase-exempt rule rule-name match attacks],</code> <code>[edit security idp idp-policy policy-name rulebase-ips rule rule-name match attacks]</code>
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify predefined attack objects that you can use to match the traffic against known attacks. You can update only the list of attack objects.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>attack-name</i> —Name of the predefined attack objects.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## pre-shared-key

---

<b>Syntax</b>	<code>pre-shared-key (ascii-text   hexadecimal);</code>
<b>Hierarchy Level</b>	<code>[edit security ike policy policy-name ]</code>
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Define a preshared key for an IKE policy.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ascii-text</i> —ASCII text key.  <i>hexadecimal</i> —Hexadecimal key.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## process-ignore-s2c

---

<b>Syntax</b>	process-ignore-s2c;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Set the command to disable the server-to-client inspection.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## process-override

---

<b>Syntax</b>	process-override;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Set the command to forcefully run the IDS inspection module even if there is no policy match.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## process-port

---

<b>Syntax</b>	<code>process-port <i>port-number</i> ;</code>
<b>Hierarchy Level</b>	[edit security idp sensor-configuration ips]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Set the command to a specific port to forcefully run the IDS inspection module on that TCP/UDP port even if there is no policy match.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p><i>port-number</i> —Port Number.</p> <p><b>Range:</b> 0 through 65535</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## products

---

<b>Syntax</b>	<pre>products {   values [list-of-values]; }</pre>
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify a products filter to add attack objects based on the application that is vulnerable to the attack.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<i>values</i> —Name of the products filter.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## proposal

---

**Syntax** `proposal proposal-name {  
     authentication-algorithm (md5 | sha1 | sha-256);  
     authentication-method (dsa-signatures | pre-shared-keys | rsa-signatures);  
     description description ;  
     dh-group (group1 | group2 | group5);  
     encryption-algorithm (des-cbc | 3des-cbc | aes-128-cbc | aes-192-cbc  
     | aes-256-cbc);  
 }`

**Hierarchy Level** [edit security ike]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Define an IKE proposal.

This statement is supported on J-series and SRX-series devices.

**Options** *proposal-name* —Name of the IKE proposal. The proposal name can be up to 32 alphanumeric characters long.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## **proposal-set**

---

See the following sections:

- **proposal-set (IKE)** on page 441
- **proposal-set (IPsec)** on page 442

***proposal-set (IKE)***

<b>Syntax</b>	<code>proposal-set &lt;basic   compatible   standard&gt;;</code>
<b>Hierarchy Level</b>	<code>[edit security ike policy <i>policy-name</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify a set of default Internet Key Exchange (IKE) proposals.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>basic</b>—Basic set of two IKE proposals:</p> <ul style="list-style-type: none"> <li>■ Proposal 1—Preshared key, Data Encryption Standard (DES) encryption, and Diffie-Hellman Group 1 and Secure Hash Algorithm 1 (SHA-1) authentication.</li> <li>■ Proposal 2—Preshared key, DES encryption, and Diffie-Hellman Group 1 and MD5 authentication.</li> </ul> <p><b>compatible</b>—Set of four commonly used IKE proposals:</p> <ul style="list-style-type: none"> <li>■ Proposal 1—Preshared key, triple DES (3DES) encryption, and G2 and SHA-1 authentication.</li> <li>■ Proposal 2—Preshared key, 3DES, and Diffie-Hellman Group 2 and MD5 authentication.</li> <li>■ Proposal 3—Preshared key, DES encryption, and Diffie-Hellman Group 2 and SHA-1 authentication.</li> <li>■ Proposal 4—Preshared key, DES encryption, and Diffie-Hellman Group 2 and MD5 authentication.</li> </ul> <p><b>standard</b>—Standard set of two set of IKE proposals:</p> <ul style="list-style-type: none"> <li>■ Proposal 1—Preshared key, 3DES encryption, and Diffie-Hellman Group 2 and SHA-1 authentication.</li> <li>■ Proposal 2—Preshared key, Advanced Encryption Standard (AES) 128-bit encryption, and Diffie-Hellman Group 2 and SHA-1 authentication.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p><code>security</code>—To view this statement in the configuration.</p> <p><code>security-control</code>—To add this statement to the configuration.</p>

**proposal-set (IPsec)**

<b>Syntax</b>	proposal-set <basic   compatible   standard>;
<b>Hierarchy Level</b>	[edit security ipsec policy <i>policy-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define a set of default IPsec proposals.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>basic</b>—Basic set of two IPsec proposals:</p> <ul style="list-style-type: none"> <li>■ Proposal 1—Encapsulating Security Payload (ESP) with no Perfect Forward Secrecy (PFS) security, triple Data Encryption Standard (3DES) encryption, and secure Hash Algorithm (SHA-1) authentication.</li> <li>■ Proposal 2—ESP with no PFS security, 3DES encryption, and MD5 authentication.</li> </ul> <p><b>compatible</b>—Set of four commonly used IKE proposals:</p> <ul style="list-style-type: none"> <li>■ Proposal 1—Preshared key, triple DES (3DES) encryption, and G2 and SHA-1 authentication.</li> <li>■ Proposal 2—Preshared key, 3DES, and Diffie-Hellman Group 2 and MD5 authentication.</li> <li>■ Proposal 3—Preshared key, DES encryption, and Diffie-Hellman Group 2 and SHA-1 authentication.</li> <li>■ Proposal 4—Preshared key, DES encryption, and Diffie-Hellman Group 2 and MD5 authentication.</li> </ul> <p><b>standard</b>—Standard set of two set of IKE proposals:</p> <ul style="list-style-type: none"> <li>■ Proposal 1—Preshared key, 3DES encryption, and Diffie-Hellman Group 2 and SHA-1 authentication.</li> <li>■ Proposal 2—Preshared key, Advanced Encryption Standard (AES) 128-bit encryption, and Diffie-Hellman Group 2 and SHA-1 authentication.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## protect

---

**Syntax**    protect {  
               deny {  
                   all | destination-ip *address* ;  
                   timeout *seconds* ;  
               }  
           }

**Hierarchy Level**    [edit security alg sip application-screen]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure options to protect servers against INVITE attacks.

This statement is supported on J-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

## protocol

---

See the following sections:

- protocol (IPsec) on page 444
- protocol (Manual Security Association) on page 445
- protocol (IP Headers in Signature Attack) on page 445
- protocol (Signature Attack) on page 446

### **protocol (IPsec)**

**Syntax** protocol (ah | esp);

**Hierarchy Level** [edit security ipsec proposal *proposal-name* ]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Define the IPsec protocol for a manual or dynamic security association (SA).

This statement is supported on J-series and SRX-series devices.

**Options** ah—Authentication Header protocol.

esp—Encapsulating Security Payload (ESP) protocol.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



**protocol (Manual Security Association)**

<b>Syntax</b>	protocol (ah   esp)
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> manual]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Define the IPsec protocol for the manual security association.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	ah—Authentication Header protocol.  esp—ESP protocol (To use the ESP protocol, you must also use the <b>tunnel</b> statement at the [edit security ipsec security-association <i>sa-name</i> mode] hierarchy level.)
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**protocol (IP Headers in Signature Attack)**

<b>Syntax</b>	protocol { match (equal   greater-than   less-than   not-equal); value <i>transport-layer-protocol-id</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol ip]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the Transport Layer protocol number.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>transport-layer-protocol-id</i> —Match the Transport Layer protocol ID.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**protocol (Signature Attack)**

```

Syntax  protocol {
            icmp {
                code {
                    match (equal | greater-than | less-than | not-equal);
                    value code-value ;
                }
                data-length {
                    match (equal | greater-than | less-than | not-equal);
                    value data-length ;
                }
                identification {
                    match (equal | greater-than | less-than | not-equal);
                    value identification-value ;
                }
                sequence-number {
                    match (equal | greater-than | less-than | not-equal);
                    value sequence-number ;
                }
                type {
                    match (equal | greater-than | less-than | not-equal);
                    value type-value ;
                }
            }
            ip {
                destination {
                    match (equal | greater-than | less-than | not-equal);
                    value hostname ;
                }
                identification {
                    match (equal | greater-than | less-than | not-equal);
                    value identification-value ;
                }
                ip-flags {
                    (df | no-df);
                    (mf | no-mf);
                    (rb | no-rb);
                }
                protocol {
                    match (equal | greater-than | less-than | not-equal);
                    value transport-layer-protocol-id ;
                }
                source {
                    match (equal | greater-than | less-than | not-equal);
                    value hostname ;
                }
                tos {
                    match (equal | greater-than | less-than | not-equal);
                    value type-of-service-in-decimal ;
                }
                total-length {
                    match (equal | greater-than | less-than | not-equal);
                    value total-length-of-ip-datagram ;
                }
                ttl {

```

```

        match (equal | greater-than | less-than | not-equal);
        value time-to-live ;
    }
}
tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number ;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value tcp-data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    header-length {
        match (equal | greater-than | less-than | not-equal);
        value header-length ;
    }
    mss {
        match (equal | greater-than | less-than | not-equal);
        value maximum-segment-size ;
    }
    option {
        match (equal | greater-than | less-than | not-equal);
        value tcp-option ;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
    tcp-flags {
        (ack | no-ack);
        (fin | no-fin);
        (psh | no-psh);
        (r1 | no-r1);
        (r2 | no-r2);
        (rst | no-rst);
        (syn | no-syn);
        (urg | no-urg);
    }
    urgent-pointer {
        match (equal | greater-than | less-than | not-equal);
        value urgent-pointer ;
    }
    window-scale {
        match (equal | greater-than | less-than | not-equal);
        value window-scale-factor ;
    }
    window-size {

```

```

        match (equal | greater-than | less-than | not-equal);
        value window-size ;
    }
}
udp {
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
}
}

```

<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a protocol to match the header information for the signature attack.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## protocol-binding

---

**Syntax** protocol-binding {  
     application *application-name* ;  
     icmp;  
     ip {  
         protocol-number *transport-layer-protocol-number* ;  
     }  
     rpc {  
         program-number *rpc-program-number* ;  
     }  
     tcp {  
         minimum-port *port-number* maximum-port *port-number* ;  
     }  
     udp {  
         minimum-port *port-number* maximum-port *port-number* ;  
     }  
 }

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type chain]  
 [edit security idp custom-attack *attack-name* attack-type signature]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Select a protocol that the attack uses to enter your network.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## protocol-name

---

**Syntax**    protocol-name *protocol-name* {  
                   tunable-name *tunable-name* {  
                     tunable-value *protocol-value* ;  
                   }  
                 }

**Hierarchy Level**    [edit security idp sensor-configuration detector]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Specify the name of the protocol to be used to configure each of the protocol detector engines.

This statement is supported on SRX-series devices.

**Options**    *protocol-name* —Name of the specific protocol.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## protocols

---

See the following sections:

- protocols (Interface Host-Inbound Traffic) on page 452
- protocols (Zone Host-Inbound Traffic) on page 454

**protocols (Interface Host-Inbound Traffic)**

<b>Syntax</b>	<pre> protocols {     protocol-name ;     protocol-name &lt;except&gt;; } </pre>
<b>Hierarchy Level</b>	[edit security zones security-zone <i>zone-name</i> interfaces <i>interface-name</i> host-inbound-traffic]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the types of routing protocol traffic that can reach the device on a per-interface basis.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>protocol-name</i> —Protocol for which traffic is allowed. The following protocols are supported:</p> <ul style="list-style-type: none"> <li>■ <b>all</b>—Enable traffic from all possible protocols available.</li> <li>■ <b>bfd</b>—Enable incoming Bidirectional Forwarding Detection (BFD) Protocol traffic.</li> <li>■ <b>bgp</b>—Enable incoming BGP traffic.</li> <li>■ <b>dvmrp</b>—Enable incoming Distance Vector Multicast Routing Protocol (DVMRP) traffic.</li> <li>■ <b>igmp</b>—Enable incoming Internet Group Management Protocol (IGMP) traffic.</li> <li>■ <b>ldp</b>—Enable incoming Label Distribution Protocol (LDP) traffic (UDP and TCP port 646).</li> <li>■ <b>msdp</b>—Enable incoming Multicast Source Discovery Protocol (MSDP) traffic.</li> <li>■ <b>nhrp</b>—Enable incoming Next Hop Resolution Protocol (NHRP) traffic.</li> <li>■ <b>ospf</b>—Enable incoming OSPF traffic.</li> <li>■ <b>pgm</b>—Enable incoming Pragmatic General Multicast (PGM) protocol traffic (IP protocol number 113).</li> <li>■ <b>pim</b>—Enable incoming Protocol Independent Multicast (PIM) traffic.</li> <li>■ <b>rip</b>—Enable incoming RIP traffic.</li> <li>■ <b>router-discovery</b>—Enable incoming router discovery traffic.</li> <li>■ <b>rsvp</b>—Enable incoming Resource Resolution Protocol (RSVP) traffic (IP protocol number 46).</li> <li>■ <b>sap</b>— Enable incoming Session Announcement Protocol (SAP) traffic. SAP always listens on 224.2.127.254:9875.</li> <li>■ <b>vrrp</b>—Enable incoming Virtual Router Redundancy Protocol (VRRP) traffic.</li> </ul> <p><b>except</b>—(Optional) <i>except</i> can only be used if <b>all</b> has been defined.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .



<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.
---------------------------------	---

**protocols (Zone Host-Inbound Traffic)**

**Syntax** protocols {  
     `protocol-name` ;  
     `protocol-name` <except>;  
 }

**Hierarchy Level** [edit security zones security-zone *zone-name* host-inbound-traffic]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the types of traffic that can reach the device for all interfaces in a zone.

This statement is supported on J-series and SRX-series devices.

- Options** *protocol-name* —Protocol for which traffic is allowed. The following protocols are supported:
- **all**—Enable traffic from all possible protocols available.
  - **bfd**—Enable incoming Bidirectional Forwarding Detection (BFD) protocol traffic.
  - **bgp**—Enable incoming BGP traffic.
  - **dvmrp**—Enable incoming Distance Vector Multicast Routing Protocol (DVMRP) traffic.
  - **igmp**—Enable incoming Internet Group Management Protocol (IGMP) traffic.
  - **ldp**—Enable incoming Label Distribution Protocol (LDP) traffic (UDP and TCP port 646).
  - **msdp**—Enable incoming Multicast Source Discovery Protocol (MSDP) traffic.
  - **nhrp**—Enable incoming Next Hop Resolution Protocol (NHRP) traffic.
  - **ospf**—Enable incoming OSPF traffic.
  - **pgm**—Enable incoming Pragmatic General Multicast (PGM) protocol traffic (IP protocol number 113).
  - **pim**—Enable incoming Protocol Independent Multicast (PIM) traffic.
  - **rip**—Enable incoming RIP traffic.
  - **router-discovery**—Enable incoming router discovery traffic.
  - **rsvp**—Enable incoming Resource Reservation Protocol (RSVP) traffic (IP protocol number 46).
  - **sap**— Enable incoming Session Announcement Protocol (SAP) traffic. SAP always listens on 224.2.127.254:9875. New addresses and ports can be added dynamically. This information must be propagated to the Packet Forwarding Engine (PFE).
  - **vrrp**—Enable incoming Virtual Router Redundancy Protocol (VRRP) traffic.

**except**—(Optional) except can only be used if all has been defined.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.
---------------------------------	---

## proxy-arp

---

See the following sections:

- proxy-arp (Services Gateway Configuration) on page 456
- proxy-arp (Services Router Configuration) on page 457

### ***proxy-arp (Services Gateway Configuration)***

**Syntax**    proxy-arp {  
                   interface *interface-name* {  
                     address *ip-address* to *ip-address* ;  
                   }  
                 }

**Hierarchy Level**    [edit security nat]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Configure Address Resolution Protocol (ARP) proxy.

This statement is supported on SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

**proxy-arp (Services Router Configuration)**

<b>Syntax</b>	<pre> proxy-arp {     address <i>prefix</i> ;     address-range high <i>ip-address</i> low <i>ip-address</i> ; } </pre>
<b>Hierarchy Level</b>	[edit security nat interface <i>interface-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure Address Resolution Protocol (ARP) proxy.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

**proxy-identity**

---

<b>Syntax</b>	<pre> proxy-identity {     local <i>ipv4-prefix</i> ;     remote <i>ipv4-prefix</i> ;     service <i>service-name</i> ; } </pre>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Optionally specify the IPsec proxy ID to use in negotiations. The default behavior is to use the identities taken from the firewall policies.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## raise-threshold

---

<b>Syntax</b>	<code>raise-threshold <i>raise-threshold</i> ;</code>
<b>Hierarchy Level</b>	[edit security nat source-nat pool-utilization-alarm] [edit security nat source pool-utilization-alarm]
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	Configure the upper threshold at which an SNMP trap is triggered when pool utilization for a source pool without Port Address Translation (PAT) rises above the threshold. This feature is disabled by default.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>raise-threshold</i> —Threshold at which an SNMP trap is triggered. <b>Range:</b> 50 through 100
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**real**

---

**Syntax**    `real {  
               disable;  
               traceoptions {  
                   flag {  
                       all <extensive>;  
                   }  
               }  
           }`

**Hierarchy Level**    [edit security alg]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the RealAudio and RealVideo ALG on the device.

This statement is supported on J-series devices.

**Options**    `disable`—Disable the RealAudio and RealVideo ALG.

`traceoptions`—Configure RealAudio and RealVideo ALG tracing options. By default, the RealAudio and RealVideo ALG is enabled.

`flag`—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

`all`—Trace all RealAudio and RealVideo ALG events.

`extensive`—(Optional) Display extensive amount of data.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    `security`—To view this statement in the configuration.  
                                   `security-control`—To add this statement to the configuration.

## re-assembler

---

<b>Syntax</b>	re-assembler { ignore-mem-overflow; max-flow-mem <i>value</i> ; max-packet-mem <i>value</i> ; }
<b>Hierarchy Level</b>	[edit security idp sensor-configuration]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Configure TCP reassembler for IDP sensor settings.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## re-enroll-trigger-time-percentage

---

<b>Syntax</b>	re-enroll-trigger-time-percentage <i>percentage</i> ;
<b>Hierarchy Level</b>	[edit security pki auto-re-enrollment certificate-id <i>certificate-id-name</i> ]
<b>Release Information</b>	Statement modified in Release 9.0 of JUNOS software.
<b>Description</b>	Specify the time before expiration as a percentage.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## recommended

---

<b>Syntax</b>	recommended;
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify recommended filter to add predefined attacks recommended by Juniper to the dynamic attack group.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	values—Name of the recommended filter.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## recommended-action

---

<b>Syntax</b>	<code>recommended-action (close   close-client   close-server   drop   drop-packet   ignore   none);</code>
<b>Hierarchy Level</b>	<code>[edit security idp custom-attack <i>attack-name</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>When the security device detects an attack, it performs the specified action.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>The seven actions are as follows, from most to least severe:</p> <p><code>close</code>—Reset the client and the server.</p> <p><code>close-client</code>—Reset the client.</p> <p><code>close-server</code>—Reset the server.</p> <p><code>drop</code>—Drop the particular packet and all subsequent packets of the flow.</p> <p><code>drop-packet</code>—Drop the particular packet of the flow.</p> <p><code>ignore</code>—Do not inspect any further packets.</p> <p><code>none</code>—Do not perform any action.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p><code>security</code>—To view this statement in the configuration.</p> <p><code>security-control</code>—To add this statement to the configuration.</p>

## regex

---

<b>Syntax</b>	<code>regex regular-expression ;</code>
<b>Hierarchy Level</b>	<code>[edit security idp custom-attack <i>attack-name</i> attack-type signature]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a PCRE expression.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## reject

---

<b>Syntax</b>	<code>reject;</code>
<b>Hierarchy Level</b>	<code>[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Block the service at the firewall. The device drops the packet and sends a TCP reset (RST) segment to the source host for TCP traffic and an ICMP “destination unreachable, port unreachable” message (type 3, code 3) for UDP traffic. For types of traffic other than TCP and UDP, the device drops the packet without notifying the source host, which is also what occurs when the action is <code>deny</code> .  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## reject-timeout

---

<b>Syntax</b>	<code>reject-timeout value ;</code>
<b>Hierarchy Level</b>	[edit security idp sensor-configuration flow]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the amount of time in milliseconds within which a response must be received.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Maximum amount of time in milliseconds. <b>Range:</b> 1 through 65535 milliseconds <b>Default:</b> 300 milliseconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## remote

---

<b>Syntax</b>	<code>remote ipv4-prefix ;</code>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike proxy-identity]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the remote IP address and subnet mask for the proxy identity.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ipv4-prefix</i> —IP address and subnet mask.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## reset

---

<b>Syntax</b>	reset;
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Select <b>reset</b> if the compound attack should be matched more than once within a single session or transaction.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## reset-on-policy

---

<b>Syntax</b>	(reset-on-policy   no-reset-on-policy);
<b>Hierarchy Level</b>	[edit security idp sensor-configuration flow]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>IDP keeps track of connections in a table. If enabled, the security module resets the flow table each time a security policy loads or unloads. If this setting is disabled, then the security module continues to retain a previous security policy until all flows referencing that security policy go away. Juniper Networks recommends that you keep this setting enabled to preserve memory.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## respond-bad-spi

---

<b>Syntax</b>	<code>respond-bad-spi <i>number</i> ;</code>
<b>Hierarchy Level</b>	[edit security ike]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable response to invalid IPsec Security Parameter Index (SPI) values. If the security associations (SAs) between two peers of an IPsec VPN become unsynchronized, the device resets the state of a peer so that the two peers are synchronized.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>number</i> —Number of times to respond to invalid SPI values per gateway.</p> <p><b>Range:</b> 1 through 30</p> <p><b>Default:</b> 5</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## retain-hold-resource

---

<b>Syntax</b>	<code>retain-hold-resource;</code>
<b>Hierarchy Level</b>	[edit security alg sip]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the device to not free media resources for a Session Initiation Protocol (SIP) Application Layer Gateway (ALG), even when a media stream is placed on hold. By default, media stream resources are released when the media stream is held.</p> <p>This statement is supported on J-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## revocation-check

---

**Syntax**

```
revocation-check {
  crl {
    disable {
      on-download-failure;
    }
    refresh-interval hours ;
    url url-name ;
  }
  disable;
}
```

**Hierarchy Level** [edit security pki ca-profile *ca-profile-name* ]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Specify the method the device uses to verify the revocation status of digital certificates.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## route-change-timeout

---

<b>Syntax</b>	route-change-timeout <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit security flow]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the session timeout value on a route change to a nonexistent route. By default, this feature is disabled. If the timeout is not defined, sessions discovered to have no route are aged out by means of their current session timeout values.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>seconds</i> —Amount of time before sessions with no route are aged out.</p> <p><b>Range:</b> 6 through 1800 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## routing-instance

---

See the following sections:

- routing-instance (Destination NAT Services Gateway) on page 469
- routing-instance (Source NAT Services Gateway) on page 469

### ***routing-instance (Destination NAT Services Gateway)***

**Syntax** routing-instance *routing-instance-name* ;

**Hierarchy Level** [edit security nat destination pool *pool-name* ]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the routing instance on which to perform the route lookup for the address in the pool. It is not a mandatory flag. If the user does not configure the routing instance, by default the pool belongs to routing-instance *inet.0*.

This statement is supported on SRX-series devices.

**Options** *routing-instance-name* —Name of the routing instance.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

### ***routing-instance (Source NAT Services Gateway)***

**Syntax** routing-instance *routing-instance-name* ;

**Hierarchy Level** [edit security nat source pool *pool-name* ]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the routing instance to which the pool is bound. It is not a mandatory flag. If the user does not configure the routing instance, by default the pool belongs to routing-instance *inet.0*.

This statement is supported on SRX-series devices.

**Options** *routing-instance-name* —Name of the routing instance.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**rpc**

---

**Syntax**    `rpc {  
                  program-number rpc-program-number ;  
                  }`

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type chain protocol-binding]  
                          [edit security idp custom-attack *attack-name* attack-type signature protocol-binding]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Allow IDP to match the attack for a specified remote procedure call (RPC) program number.

This statement is supported on SRX-series devices.

**Options**    `program-number rpc-program-number` —RPC program number.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

**rsh**

---

**Syntax**    rsh {  
               disable;  
               traceoptions {  
                   flag {  
                       all <extensive>;  
                   }  
               }  
           }

**Hierarchy Level**    [edit security alg]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the remote shell (RSH) ALG on the device.

This statement is supported on J-series devices.

**Options**    **disable**—Disable the RSH ALG. By default, the RSH ALG is enabled.

**traceoptions**—Configure RSH ALG tracing options.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

**all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

## rst-invalidate-session

---

<b>Syntax</b>	rst-invalidate-session;
<b>Hierarchy Level</b>	[edit security flow tcp-session]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the device to mark a session for immediate termination when it receives a TCP reset (RST) message. By default, this feature is disabled and the device applies the normal session timeout interval. For TCP, normal session timeout is 30 minutes; for HTTP, it is 5 minutes; and for UDP, it is 1 minute.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## rst-sequence-check

---

<b>Syntax</b>	rst-sequence-check;
<b>Hierarchy Level</b>	[edit security flow tcp-session]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Verify that the TCP sequence number in a TCP segment with the RST bit enabled matches the previous sequence number for a packet in that session or is the next higher number incrementally. If the sequence number does not match either of these expected numbers, the device drops the packet and sends the host a TCP ACK message with the correct sequence number. By default, this check is disabled.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**rtsp**

---

**Syntax**

```
rtsp {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the Real-Time Streaming Protocol (RTSP) ALG on the device.

This statement is supported on J-series devices.

**Options** **disable**—Disable the RTSP ALG. By default, the RTSP ALG is enabled.

**traceoptions**—Configure RTSP ALG tracing options.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

**all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## rule

---

See the following sections:

- rule (Destination NAT) on page 474
- rule (Exempt Rulebase) on page 475
- rule (IPS Rulebase) on page 476
- rule (Source NAT) on page 477
- rule (Static NAT) on page 478

### **rule (Destination NAT)**

**Syntax**     `rule rule-name {  
                  match {  
                    destination-address destination-address ;  
                    destination-port port-number ;  
                    source-address [source-address];  
                  }  
                  then {  
                    destination-nat (off | pool pool-name );  
                  }  
                }`

**Hierarchy Level**     [edit security nat destination rule-set *rule-set-name* ]

**Release Information**     Statement introduced in Release 9.2 of JUNOS software.

**Description**     Define a destination NAT rule.

This statement is supported on SRX-series devices.

**Options**     *rule-name* —Name of the destination NAT rule.

The remaining statements are explained separately.

**Usage Guidelines**     For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**     security—To view this statement in the configuration.  
                                     security-control—To add this statement to the configuration.

**rule (Exempt Rulebase)**

**Syntax**    `rule rule-name {  
                   description text ;  
                   match {  
                     attacks {  
                       custom-attacks [ attack-name ];  
                       predefined-attack-groups [ attack-name ];  
                       predefined-attacks [ attack-name ];  
                     }  
                   destination-address [ address-name ];  
                   destination-except [ address-name ];  
                   from-zone zone-name ;  
                   source-address [ address-name ];  
                   source-except [ address-name ];  
                   to-zone zone-name ;  
                   }  
                   }`

**Hierarchy Level**    [edit security idp idp-policy *policy-name* rulebase-exempt]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Specify exempt rule to create, modify, delete, and reorder the rules in a rulebase.

This statement is supported on SRX-series devices.

**Options**    *rule-name* —Name of the exempt rulebase rule.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

**rule (IPS Rulebase)**

```

Syntax rule rule-name {
    description text ;
    match {
        attacks {
            custom-attacks [ attack-name ];
            predefined-attack-groups [ attack-name ];
            predefined-attacks [ attack-name ];
        }
        destination-address [ address-name ];
        destination-except [ address-name ];
        from-zone zone-name ;
        source-address [ address-name ];
        source-except [ address-name ];
        to-zone zone-name ;
    }
    terminal;
    then {
        action {
            (close-client | close-client-and-server | close-server |
            drop-connection | drop-packet | ignore-connection |
            mark-diffserv value | no-action | recommended);
        }
        ip-action {
            (ip-block | ip-close | ip-notify);
            log;
            target (destination-address | service | source-address |
            source-zone | zone-service);
            timeout seconds ;
        }
        notification {
            log-attacks {
                alert (yes | no);
            }
        }
        severity (critical | info | major | minor | warning);
    }
}

```

**Hierarchy Level** [edit security idp idp-policy *policy-name* rulebase-ips]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify IPS rule to create, modify, delete, and reorder the rules in a rulebase.

This statement is supported on SRX-series devices.

**Options** *rule -name* —Name of the IPS rulebase rule.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.



**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

### ***rule (Source NAT)***

**Syntax**

```
rule rule-name {
    match {
        destination-address [destination-address];
        source-address [source-address];
    }
    then {
        source-nat (off | interface | pool pool-name );
    }
}
```

**Hierarchy Level** [edit security nat source rule-set *rule-set-name* ]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Define a source NAT rule.

This statement is supported on SRX-series devices.

**Options** *rule-name* —Name of the source NAT rule.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**rule (Static NAT)**

**Syntax**    `rule rule-name {  
                   match {  
                     destination-address [destination-address];  
                   }  
                   then {  
                     static-nat prefix < addr-prefix >  
                     <routing-instance routing-instance-name >;  
                   }  
                 }`

**Hierarchy Level**    [edit security nat static rule-set *rule-set-name* ]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Define a static NAT rule.

This statement is supported on SRX-series devices.

**Options**    *rule-name* —Name of the static NAT rule.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

## rule-set

---

See the following sections:

- rule-set (Destination NAT Services Gateway) on page 479
- rule-set (Source NAT Services Gateway) on page 480
- rule-set (Static NAT Services Gateway) on page 481

### **rule-set (Destination NAT Services Gateway)**

**Syntax**

```
rule-set rule-set-name {
  from interface [interface-name] |
  routing-instance [routing-instance-name] | zone [zone-name];
  rule rule-name {
    match {
      destination-address destination-address ;
      destination-port port-number ;
      source-address [source-address];
    }
    then {
      destination-nat (off | pool pool-name );
    }
  }
}
```

**Hierarchy Level** [edit security nat destination]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure the set of rules for destination NAT.

This statement is supported on SRX-series devices.

**Options** *rule-set-name* —Name of the rule set.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**rule-set (Source NAT Services Gateway)**

**Syntax** `rule-set rule-set-name {  
     from interface [interface-name] |  
     routing-instance [routing-instance-name] | zone [zone-name];  
     rule rule-name {  
         match {  
             destination-address [destination-address];  
             source-address [source-address];  
         }  
         then {  
             source-nat (off | interface | pool pool-name );  
         }  
     }  
     to interface [interface-name] |  
     routing-instance [routing-instance-name] | zone [zone-name];  
}`

**Hierarchy Level** [edit security nat source]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure the set of rules for source NAT.

This statement is supported on SRX-series devices.

**Options** *rule-set-name* —Name of the rule set.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**rule-set (Static NAT Services Gateway)**

**Syntax** `rule-set rule-set-name {  
     from interface [interface-name] |  
     routing-instance [routing-instance-name] | zone [zone-name];  
     rule rule-name {  
         match {  
             destination-address [destination-address];  
         }  
         then {  
             static-nat prefix < addr-prefix >  
             <routing-instance routing-instance-name >;  
         }  
     }  
}`

**Hierarchy Level** [edit security nat static]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Configure the set of rules for static NAT.

This statement is supported on SRX-series devices.

**Options** *rule-set-name* —Name of the rule set.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## rulebase-exempt

---

**Syntax**

```
rulebase-exempt {
  rule rule-name {
    description text ;
    match {
      attacks {
        custom-attacks [ attack-name ];
        predefined-attack-groups [ attack-name ];
        predefined-attacks [ attack-name ];
      }
      destination-address [ address-name ];
      destination-except [ address-name ];
      from-zone zone-name ;
      source-address [ address-name ];
      source-except [ address-name ];
      to-zone zone-name ;
    }
  }
}
```

**Hierarchy Level** [edit security idp idp-policy *policy-name* ]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure the exempt rulebase to skip detection of a set of attacks in certain traffic.



**NOTE:** You must configure the IPS rulebase before configuring the exempt rulebase.

---

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## rulebase-ips

---

```

Syntax rulebase-ips {
    rule rule-name {
        description text ;
        match {
            attacks {
                custom-attacks [ attack-name ];
                predefined-attack-groups [ attack-name ];
                predefined-attacks [ attack-name ];
            }
            destination-address [ address-name ];
            destination-except [ address-name ];
            from-zone zone-name ;
            source-address [ address-name ];
            source-except [ address-name ];
            to-zone zone-name ;
        }
        terminal;
        then {
            action {
                (close-client | close-client-and-server | close-server |
                drop-connection | drop-packet | ignore-connection |
                mark-diffserv value | no-action | recommended);
            }
            ip-action {
                (ip-block | ip-close | ip-notify);
                log;
                target (destination-address | service | source-address |
                source-zone | zone-service);
                timeout seconds;
            }
            notification {
                log-attacks {
                    alert (yes | no);
                }
            }
            severity (critical | info | major | minor | warning);
        }
    }
}

```

**Hierarchy Level** [edit security idp idp-policy *policy-name*]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure the IPS rulebase to detect attacks based on stateful signature and protocol anomalies.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## sccp

---

**Syntax**

```
sccp {
  application-screen {
    call-flood threshold rate ;
    unknown-message {
      permit-nat-applied;
      permit-routed;
    }
  }
  disable;
  inactive-media-timeout seconds ;
  traceoptions {
    flag {
      all <extensive>;
      call <extensive>;
      cc <extensive>;
      cli <extensive>;
      decode <extensive>;
      error <extensive>;
      init <extensive>;
      nat <extensive>;
      rm <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the Skinny Client Control Protocol (SCCP) ALG on the device.

This statement is supported on J-series devices.

**Options** disable—Disable the SCCP ALG. By default, the SCCP ALG is enabled.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



## **scheduler-name**

---

<b>Syntax</b>	<code>scheduler-name scheduler-name ;</code>
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the schedule (as defined by the <code>scheduler scheduler-name</code> statement) for which the policy is in effect.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>scheduler-name</i> —Name of the scheduler.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## scope

---

See the following sections:

- `scope` (Chain Attack) on page 486
- `scope` (Custom Attack) on page 487

### **scope (Chain Attack)**

**Syntax** `scope (session | transaction);`

**Hierarchy Level** `[edit security idp custom-attack attack-name attack-type chain]`

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Specify whether the match should occur over a single session or can be made across multiple transactions within a session.

This statement is supported on SRX-series devices.

**Options** `session`—Allow multiple matches for the object within the same session.

`transaction`—Match the object across multiple transactions that occur within the same session.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `security`—To view this statement in the configuration.  
`security-control`—To add this statement to the configuration.

**scope (Custom Attack)**

<b>Syntax</b>	scope (destination   peer   source);
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> time-binding]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify whether the counting of the attack is from the same source IP address, the same destination IP address, or a peer.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>■ <b>destination</b>—IDP detects attacks to a given destination IP address for the specified number of times, regardless of the source IP address.</li> <li>■ <b>peer</b>—IDP detects attacks between source and destination IP addresses of the sessions for the specified number of times.</li> <li>■ <b>source</b>—IDP detects attacks from a given source IP address for the specified number of times, regardless of the destination IP address.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## **screen**

---

See the following sections:

- **screen (Security)** on page 489
- **screen (Zones)** on page 490

**screen (Security)**

```

Syntax  screen {
            ids-option {
                screen-name {
                    alarm-without-drop;
                    icmp {
                        flood {
                            threshold number ;
                        }
                        fragment;
                        ip-sweep {
                            threshold number ;
                        }
                        large;
                        ping-death;
                    }
                    ip {
                        bad-option;
                        block-frag;
                        loose-source-route-option;
                        record-route-option;
                        security-option;
                        source-route-option;
                        spoofing;
                        stream-option;
                        strict-source-route-option;
                        tear-drop;
                        timestamp-option;
                        unknown-protocol;
                    }
                    limit-session {
                        destination-ip-based number ;
                        source-ip-based number ;
                    }
                }
            }
            tcp {
                fin-no-ack;
                land;
                port-scan {
                    threshold number ;
                }
                syn-ack-ack-proxy {
                    threshold number ;
                }
                syn-fin;
                syn-flood {
                    alarm-threshold number ;
                    attack-threshold number ;
                    destination-threshold number ;
                    source-threshold number ;
                    timeout seconds ;
                }
                syn-frag;
                tcp-no-flag;
                winnuke;
            }
        }

```

```

        udp {
            flood {
                threshold number ;
            }
        }
    }
    traceoptions {
        file filename <files number > <match regular-expression >
        <size maximum-file-size > <world-readable | no-world-readable>;
        flag flag ;
    }
}

```

<b>Hierarchy Level</b>	[edit security]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure security screen options.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>screen-name</i> —Name of the screen configured at <b>security screen ids-options</b> level.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## screen (Zones)

<b>Syntax</b>	screen <i>screen-name</i> ;
<b>Hierarchy Level</b>	[edit security zones functional-zone management], [edit security zones security-zone <i>zone-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify a security screen for a security zone.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>screen-name</i> —Name of the screen.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## security-package

---

**Syntax** security-package {  
     automatic {  
         enable;  
         interval *hours* ;  
         start-time *start-time* ;  
     }  
     url *url-name* ;  
 }

**Hierarchy Level** [edit security idp]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure the device to automatically download the updated signature database from the specified URL.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## security-zone

---

**Syntax**

```
security-zone zone-name {
  address-book {
    address address-name (ip-prefix | dns-name dns-address-name);
    address-set address-set-name {
      address address-name ;
    }
  }
  host-inbound-traffic {
    protocols {
      protocol-name ;
      protocol-name <except>;
    }
    system-services {
      service-name ;
      service-name < except >;
    }
  }
  interfaces interface-name {
    host-inbound-traffic {
      protocols {
        protocol-name ;
        protocol-name < except >;
      }
      system-services {
        service-name ;
        service-name < except >;
      }
    }
  }
  screen screen-name ;
  tcp-rst;
}
```

**Hierarchy Level** [edit security zones]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Define a security zone, which allows you to divide the network into different segments and apply different security options to each segment.

This statement is supported on J-series and SRX-series devices.

**Options** *zone-name* —Name of the security zone.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.



security-control—To add this statement to the configuration.

## sensor-configuration

---

```

Syntax  sensor-configuration {
    application-identification {
        application-system-cache;
        application-system-cache-timeout value ;
        check-first-session;
        disable;
        max-packet-memory value ;
        max-sessions value ;
        max-tcp-session-packet-memory value ;
        max-udp-session-packet-memory value ;
    }
    detector {
        protocol-name protocol-name {
            tunable-name tunable-name {
                tunable-value protocol-value ;
            }
        }
    }
    flow {
        (allow-icmp-without-flow | no-allow-icmp-without-flow);
        (log-errors | no-log-errors);
        max-timers-poll-ticks value ;
        reject-timeout value ;
        (reset-on-policy | no-reset-on-policy);
    }
    global {
        (enable-all-qmodules | no-enable-all-qmodules);
        (enable-packet-pool | no-enable-packet-pool);
        (policy-lookup-cache | no-policy-lookup-cache);
    }
    ips {
        detect-shellcode;
        ignore-regular-expression;
        log-supercede-min minimum-value ;
        pre-filter-shellcode;
        process-ignore-s2c;
        process-override;
        process-port port-number ;
    }
    log {
        cache-size size ;
        suppression {
            disable;
            include-destination-address;
            max-logs-operate value ;
            max-time-report value ;
            start-log value ;
        }
    }
    re-assembler {
        ignore-mem-overflow;
    }
}

```

```

        max-flow-mem value ;
        max-packet-mem value ;
    }
}

```

<b>Hierarchy Level</b>	[edit security idp]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Configure various IDP parameters to match the properties of transiting network traffic.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## session-close

---

<b>Syntax</b>	session-close;
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then log]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable traffic to which the policy applies to be logged at the end of a session.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## session-init

---

<b>Syntax</b>	session-init;
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then log]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable traffic to which the policy applies to be logged at the beginning of a session.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## sequence-number

---

See the following sections:

- sequence-number (ICMP Headers in Signature Attack) on page 497
- sequence-number (TCP Headers in Signature Attack) on page 498

### ***sequence-number (ICMP Headers in Signature Attack)***

**Syntax** sequence-number {  
     match (equal | greater-than | less-than | not-equal);  
     value *sequence-number*;  
 }

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type signature protocol icmp]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Specify the sequence number of the packet. This number identifies the location of the request/reply in relation to the entire sequence.

This statement is supported on SRX-series devices.

**Options** match (equal | greater-than | less-than | not-equal)—Match an operand.

value *sequence-number* —Match a decimal value.

**Range:** 0 through 65535

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**sequence-number (TCP Headers in Signature Attack)**

**Syntax** sequence-number {  
     match (equal | greater-than | less-than | not-equal);  
     value *sequence-number*;  
 }

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type signature protocol tcp]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Specify the sequence number of the packet. This number identifies the location of the data in relation to the entire data sequence.

This statement is supported on SRX-series devices.

**Options** match (equal | greater-than | less-than | not-equal)—Match an operand.

value *sequence-number* —Match a decimal value.

**Range:** 0 through 4294967295

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

## service

---

See the following sections:

- service (Anomaly Attack) on page 499
- service (Dynamic Attack Group) on page 499
- service (Security IPsec) on page 500

### service (Anomaly Attack)

<b>Syntax</b>	<code>service service-name ;</code>
<b>Hierarchy Level</b>	<code>[edit security idp custom-attack attack-name attack-type anomaly]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Service is the protocol whose anomaly is defined in the attack. IP, TCP, UDP, ICMP are also valid as services.  This statement is supported on SRX-series devices.
<b>Options</b>	<code>service-name</code> —Name of the protocol.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

### service (Dynamic Attack Group)

<b>Syntax</b>	<code>service {     values [list-of-values]; }</code>
<b>Hierarchy Level</b>	<code>[edit security idp dynamic-attack-group dynamic-attack-group-name filters]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify a service filter to add attack objects based on the attack service, such as FTP, HTTP, NetBios, and so on.  This statement is supported on SRX-series devices.
<b>Options</b>	<code>values</code> —Name of the service filter.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**service (Security IPsec)**

<b>Syntax</b>	<code>service service-name ;</code>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> ike proxy-identity]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the service (port and protocol combination) to protect.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>service-name</i> —Name of the service, as defined with <code>system-services</code> (Interface Host-Inbound Traffic) and <code>system-services</code> (Zone Host-Inbound Traffic).
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.
<b>Related Topics</b>	<code>system-services</code> (Interface Host-Inbound Traffic)  <code>system-services</code> (Zone Host-Inbound Traffic)



## severity

---

See the following sections:

- **severity (Custom Attack)** on page 501
- **severity (Dynamic Attack Group)** on page 502
- **severity (IPS Rulebase)** on page 503

### severity (Custom Attack)

**Syntax** severity (critical | info | major | minor | warning);

**Hierarchy Level** [edit security idp custom-attack *attack-name*]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Select the severity that matches the lethality of the attack object on your network.

This statement is supported on SRX-series devices.

**Options** You can set the severity level to the following levels:

- **critical**—Contains attack objects matching exploits that attempt to evade detection, cause a network device to crash, or gain system-level privileges.
- **info**—Contains attack objects matching normal, harmless traffic containing URLs, DNS lookup failures, SNMP public community strings, and Peer-to-Peer (P2P) parameters. You can use informational attack objects to obtain information about your network.
- **major**—Contains attack objects matching exploits that attempt to disrupt a service, gain user-level access to a network device, or activate a Trojan horse previously loaded on a device.
- **minor**—Contains attack objects matching exploits that detect reconnaissance efforts attempting to access vital information through directory traversal or information leaks.
- **warning**—Contains attack objects matching exploits that attempt to obtain noncritical information or scan a network with a scanning tool.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**severity (Dynamic Attack Group)**

**Syntax**    severity {  
                  values [critical | info | major | minor | warning];  
                  }

**Hierarchy Level**    [edit security idp dynamic-attack-group *dynamic-attack-group-name* filters]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify a severity filter to add attack objects based on the attack severity.

This statement is supported on SRX-series devices.

**Options**    values—Name of the severity filter. You can select from the following severity:

- critical—The attack is a critical one.
- info—Provide information of attack when it matches.
- major—The attack is a major one.
- minor—The attack is a minor one.
- warning—Issue a warning when attack matches.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

**severity (IPS Rulebase)**

<b>Syntax</b>	severity (critical   info   major   minor   warning);
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Set the rule severity levels in logging to support better organization and presentation of log records on the log server. You can use the default severity settings of the selected attack object, or choose a specific severity for your rule. The severity you configure in the rules overrides the inherited attack severity.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>You can set the severity level to the following levels:</p> <ul style="list-style-type: none"> <li>■ critical—2</li> <li>■ info—3</li> <li>■ major—4</li> <li>■ minor—5</li> <li>■ warning—7</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## shellcode

---

<b>Syntax</b>	shellcode (all   intel   no-shellcode   sparc);
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type anomaly] [edit security idp custom-attack <i>attack-name</i> attack-type signature]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Shellcode signifies that the attack is a shellcode attack and is capable of creating its own shell.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>all—All shellcode checks will be performed if this attack matches.</p> <p>intel—Basic shellcode checks and Intel-specific shellcode checks will be performed.</p> <p>no-shellcode—No shellcode checks will be performed.</p> <p>sparc—Basic shellcode checks and Sparc-specific shellcode checks will be performed.</p> <p><b>Default:</b> Basic shellcode checks will be performed when this field is not configured.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## signature

---

**Syntax** signature {  
     context *context-name* ;  
     direction (any | client-to-server | server-to-client);  
     negate;  
     pattern *signature-pattern* ;  
     protocol {  
         icmp {  
             code {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *code-value* ;  
             }  
             data-length {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *data-length* ;  
             }  
             identification {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *identification-value* ;  
             }  
             sequence-number {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *sequence-number* ;  
             }  
             type {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *type-value* ;  
             }  
         }  
         ip {  
             destination {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *hostname* ;  
             }  
             identification {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *identification-value* ;  
             }  
             ip-flags {  
                 (df | no-df);  
                 (mf | no-mf);  
                 (rb | no-rb);  
             }  
             protocol {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *transport-layer-protocol-id* ;  
             }  
             source {  
                 match (equal | greater-than | less-than | not-equal);  
                 value *hostname* ;  
             }  
             tos {

```

        match (equal | greater-than | less-than | not-equal);
        value type-of-service-in-decimal ;
    }
    total-length {
        match (equal | greater-than | less-than | not-equal);
        value total-length-of-ip-datagram ;
    }
    ttl {
        match (equal | greater-than | less-than | not-equal);
        value time-to-live ;
    }
}
tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number ;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value tcp-data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    header-length {
        match (equal | greater-than | less-than | not-equal);
        value header-length ;
    }
    mss {
        match (equal | greater-than | less-than | not-equal);
        value maximum-segment-size ;
    }
    option {
        match (equal | greater-than | less-than | not-equal);
        value tcp-option ;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
    tcp-flags {
        (ack | no-ack);
        (fin | no-fin);
        (psh | no-psh);
        (r1 | no-r1);
        (r2 | no-r2);
        (rst | no-rst);
        (syn | no-syn);
        (urg | no-urg);
    }
    urgent-pointer {

```

```

        match (equal | greater-than | less-than | not-equal);
        value urgent-pointer ;
    }
    window-scale {
        match (equal | greater-than | less-than | not-equal);
        value window-scale-factor ;
    }
    window-size {
        match (equal | greater-than | less-than | not-equal);
        value window-size ;
    }
}
udp {
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
}
}
protocol-binding {
    application application-name ;
    icmp;
    ip {
        protocol-number transport-layer-protocol-number ;
    }
    rpc {
        program-number rpc-program-number ;
    }
    tcp {
        minimum-port port-number maximum-port port-number ;
    }
    udp {
        minimum-port port-number maximum-port port-number ;
    }
}
regexp regular-expression ;
shellcode (all | intel | no-shellcode | sparc);
}

```

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

<b>Description</b>	IDP uses stateful signatures to detect attacks. Stateful signatures are more specific than regular signatures. With stateful signatures, IDP can look for the specific protocol or service used to perpetrate the attack.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



**sip**

```

Syntax  sip {
    application-screen {
        protect {
            deny {
                all | destination-ip address ;
                timeout seconds ;
            }
        }
        unknown-message {
            permit-nat-applied;
            permit-routed;
        }
    }
    c-timeout minutes ;
    disable;
    disable-call-id-hiding;
    inactive-media-timeout seconds ;
    maximum-call-duration minutes ;
    retain-hold-resource;
    t1-interval milliseconds ;
    t4-interval seconds ;
    traceoptions {
        flag {
            all <detail | extensive | terse>;
            call <detail | extensive | terse>;
            cc <detail | extensive | terse>;
            nat <detail | extensive | terse>;
            parser <detail | extensive | terse>;
            rm <detail | extensive | terse>;
        }
    }
}

```

**Hierarchy Level** [edit security alg]

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Specify the Session Initiation Protocol (SIP) ALG on the device.

This statement is supported on J-series devices.

**Options** disable—Disable the SIP ALG. By default, SIP ALG is enabled.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## source

---

See the following sections:

- [source \(IP Headers in Signature Attack\)](#) on page 510
- [source \(Source NAT Services Gateway\)](#) on page 511

### **source (IP Headers in Signature Attack)**

**Syntax**    source {  
                  match (equal | greater-than | less-than | not-equal);  
                  value *hostname* ;  
                  }

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol ip]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify the IP address of the attacking device.

This statement is supported on SRX-series devices.

**Options**    match (equal | greater-than | less-than | not-equal)—Match an operand.

value *host-name* —Match an ip-address or a host name.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

**source (Source NAT Services Gateway)**

**Syntax**

```

source {
    address-persistent;
    pool pool-name {
        address ip-address to ip-address ;
        host-address-base ip-address ;
        overflow-pool (interface | pool-name );
        port no-translation | range high ip-address low ip-address ;
        routing-instance routing-instance-name ;
    }
    pool-utilization-alarm {
        clear-threshold threshold-value ;
        raise-threshold threshold-value ;
    }
    rule-set rule-set-name {
        from interface [interface-name] |
        routing-instance [routing-instance-name] | zone [zone-name];
        rule rule-name {
            match {
                destination-address [destination-address];
                source-address [source-address];
            }
            then {
                source-nat (off | interface | pool pool-name );
            }
        }
        to interface [interface-name] |
        routing-instance [routing-instance-name] | zone [zone-name];
    }
}

```

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure source NAT of services gateway, which allows you to configure the following:

- Translate source IP address or addresses to the egress interface' IP address.
- Translate a range of source IP addresses to another range of IP addresses. This mapping is dynamic and without PAT.
- Translate a range of source IP addresses to another range of IP addresses. This mapping is dynamic and with PAT.
- Translate a range of source IP addresses to another range of IP addresses. This mapping is one-to-one, static, and without PAT.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

## source-address

---

See the following sections:

- source-address (Destination NAT Services Gateway) on page 513
- source-address (IDP Policy) on page 514
- source-address (Security Policies) on page 514
- source-address (Source NAT Services Gateway) on page 515

### source-address (Destination NAT Services Gateway)

**Syntax** source-address [source-address];

**Hierarchy Level** [edit security nat destination rule-set *rule-set-name* rule *rule-name* match]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify source address to match the rule. You can configure multiple addresses or subnets.

This statement is supported on SRX-series devices.

**Options** *source-address* —Source address or a subnet.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**source-address (IDP Policy)**

<b>Syntax</b>	source-address [ address-name ];
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match], [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a source IP address or IP address set object to be used as the match source address object. The default value is any.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>address-name</i> —IP address, IP address set object.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**source-address (Security Policies)**

<b>Syntax</b>	source-address { <i>address-name</i> ; }
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> match]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Define the matching criteria, which can include one or more IP addresses, address sets, or both in the <b>from-zone</b> zone.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>address-name</i> —IP addresses, address sets, or both are used for matching.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**source-address (Source NAT Services Gateway)**

<b>Syntax</b>	source-address [source-address];
<b>Hierarchy Level</b>	[edit security nat source rule-set <i>rule-set-name</i> rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify source address to match the rule. You can configure multiple addresses or subnets.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>source-address</i> —Source address or a subnet.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**source-except**

---

<b>Syntax</b>	source-except [ address-name ];
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match], [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a source IP address or IP address set object to specify all source address objects except the specified address objects. The default value is any.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>address-name</i> —IP address, IP address set object.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## source-interface

---

<b>Syntax</b>	<code>source-interface interface-name ;</code>
<b>Hierarchy Level</b>	<code>[edit security ipsec vpn vpn-name vpn-monitor]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the source interface for ICMP requests (VPN monitoring “hellos” ). If no source interface is specified, the device automatically uses the local tunnel endpoint interface.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>interface-name</i> —Name of the interface for the ICMP requests.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## source-ip-based

---

<b>Syntax</b>	<code>source-ip-based number ;</code>
<b>Hierarchy Level</b>	<code>[edit security screen ids-option screen-name limit-session]</code>
<b>Release Information</b>	Statement modified in Release 9.2 of JUNOS software.
<b>Description</b>	Limit the number of concurrent sessions the device can initiate from a single source IP address.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Maximum number of concurrent sessions that can be initiated from a source IP address. <b>Range:</b> 1 through 50000 <b>Default:</b> 128



**NOTE:** For SRX-series devices the applicable range is 1 through 8000000.

---

<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## source-nat

---

See the following sections:

- source-nat (NAT) on page 517
- source-nat (NAT Interface) on page 518
- source-nat (Security Policies) on page 519
- source-nat (Source NAT Services Gateway) on page 519

### source-nat (NAT)

**Syntax**

```
source-nat {
  address-persistent;
  pool-set pool-set-name {
    pool pool-name ;
  }
  pool-utilization-alarm {
    clear-threshold clear-threshold ;
    raise-threshold raise-threshold ;
  }
}
```

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure source Network Address Translation (NAT).

This statement is supported on J-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**source-nat (NAT Interface)**

**Syntax** pool pool-name {  
     address *prefix*;  
     address-range high ip-address low *ip-address*;  
     allow-incoming;  
     host-address-low *ip-address*;  
     no-port-translation;  
     overflow-pool (interface | *pool-name*);  
     }  
 }

**Hierarchy Level** [edit security nat interface *interface-name*]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure source NAT for an interface.

This statement is supported on J-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security — To view this statement in the configuration.  
 security-control — To add this statement to the configuration.

**source-nat (Security Policies)**

<b>Syntax</b>	source-nat (pool <i>pool-name</i>   pool-set <i>pool-set-name</i>   interface);
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that source NAT be used in the security policy.  This statement is supported on J-series devices.
<b>Options</b>	pool <i>pool-name</i> — Use the specified NAT source address pool.  pool-set <i>pool-set-name</i> — Use the specified NAT source address pool set.  interface — Use the interface's NAT source address pool.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security — To view this statement in the configuration. security-control — To add this statement to the configuration.
<b>Related Topics</b>	source-nat (NAT)  source-nat (NAT Interface)

**source-nat (Source NAT Services Gateway)**

<b>Syntax</b>	source-nat (off   interface   pool <i>pool-name</i> );
<b>Hierarchy Level</b>	[edit security nat source rule-set <i>rule-set-name</i> rule <i>rule-name</i> then]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the action of the source NAT rule.  This statement is supported on SRX-series devices.
<b>Options</b>	off — Do not perform the source NAT operation.  interface — Use egress interface IPv4 address to perform the source NAT.  pool — <i>pool-name</i> Use user-defined source NAT pool to perform the source NAT.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security — To view this statement in the configuration. security-control — To add this statement to the configuration.

## source-port

---

<b>Syntax</b>	source-port { match (equal   greater-than   less-than   not-equal); value <i>source-port</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol udp] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the port number on the attacking device.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>source-port</i> —Port number on the attacking device. <b>Range:</b> 0 through 65535
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## source-threshold

---

**Syntax** `source-threshold number ;`

**Hierarchy Level** `[edit security screen ids-option screen-name tcp syn-flood]`

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Specify the number of SYN segments that the device can receive per second from a single source IP address (regardless of the destination IP address and port number) before the device begins dropping connection requests from that source.

This statement is supported on J-series and SRX-series devices.

**Options** *number* —Number of SYN segments to be received per second before the device starts dropping connection requests.

**Range:** 4 through 100000 per second

**Default:** 4000 per second



**NOTE:** For SRX-series devices the applicable range is 4 through 1000000 per second.

---

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## **spi**

---

<b>Syntax</b>	<code>spi spi-value ;</code>
<b>Hierarchy Level</b>	[edit security ipsec vpn <i>vpn-name</i> manual]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure a security parameter index (SPI) for a security association (SA).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>spi-value</i> —An arbitrary value that uniquely identifies which security association (SA) to use at the receiving host (the destination address in the packet).</p> <p><b>Range:</b> 256 through 16639</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**sql**

---

**Syntax**    sql {  
               disable;  
               traceoptions {  
                   flag {  
                       all <extensive>;  
                   }  
               }  
           }

**Hierarchy Level**    [edit security alg]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the Oracle SQL ALG on the device.

This statement is supported on J-series devices.

**Options**    disable—Disable the SQL ALG. By default, the SQL ALG is enabled.

traceoptions—Configure SQL ALG tracing options.

flag—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

all—Trace all events.

extensive—(Optional) Display extensive amount of data.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

## ssh-known-hosts

---

**Syntax** `ssh-known-hosts {  
     fetch-from-server fetch-from-server ;  
     host hostname {  
         dsa-key base64-encoded-dsa-key ;  
         rsa-key base64-encoded-dsa-key ;  
         rsa1-key base64-encoded-dsa-key ;  
     }  
     load-key-file key-file ;  
}`

**Hierarchy Level** [edit security]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure SSH support for known hosts and for administering SSH host key updates.

This statement is supported on J-series and SRX-series devices.

**Options** `dsa-key`—Digital signature algorithm (DSA) for SSH version 2.

`fetch-from-server`—Retrieve SSH public host key information from a specified server.

`load-key-file`—Import SSH host key information from the `/var/tmp/ssh-known-hosts` file.

`rsa-key`—Public key algorithm that supports encryption and digital signatures for SSH version 1 and SSH version 2.

`rsa1-key`—RSA public key algorithm, which supports encryption and digital signatures for SSH version 1.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `security`—To view this statement in the configuration.  
`security-control`—To add this statement to the configuration.



## start-log

---

<b>Syntax</b>	start-log <i>value</i> ;
<b>Hierarchy Level</b>	[edit security idp sensor-configuration log suppression]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify how many instances of a specific event must occur before log suppression begins.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>value</i> —Log suppression begins after how many occurrences. <b>Range:</b> 1 through 128 <b>Default:</b> 1
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## start-time

---

<b>Syntax</b>	start-time <i>start-time</i> ;
<b>Hierarchy Level</b>	[edit security idp security-package automatic]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the time that the device automatically starts downloading the updated signature database from the specified URL.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>start-time</i> —Time in MM-DD.hh:mm format.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## static

---

**Syntax**

```
static {
  rule-set rule-set-name {
    from interface [interface-name] |
    routing-instance [routing-instance-name] | zone [zone-name];
    rule rule-name {
      match {
        destination-address [destination-address];
      }
      then {
        static-nat prefix < addr-prefix >
        <routing-instance routing-instance-name >;
      }
    }
  }
}
```

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Configure static NAT of services gateway.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## static-nat

---

See the following sections:

- static-nat (Static NAT Services Router) on page 527
- static-nat (Static NAT Services Gateway) on page 528

### ***static-nat (Static NAT Services Router)***

**Syntax**    static-nat *ip-prefix* {  
                   host *ip-prefix*;  
                   virtual-router *vr-name* ;  
                   }

**Hierarchy Level**    [edit security nat interface *interface-name* ]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure static NAT.

This statement is supported on J-series devices.

**Options**    *ip-prefix* —IP address to which another IP address is mapped.

host *ip-prefix* —IP address to be mapped.

virtual-router *vr-name* —Virtual router to perform the route lookup for the host addresses.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                   security-control—To add this statement to the configuration.

**static-nat (Static NAT Services Gateway)**

<b>Syntax</b>	<code>static-nat prefix &lt; <i>addr-prefix</i> &gt; &lt;routing-instance <i>routing-instance-name</i> &gt;;</code>
<b>Hierarchy Level</b>	<code>[edit security nat static rule-set <i>rule-set-name</i> rule <i>rule-name</i> then]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the translated address of the static NAT rule.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>address-prefix</i> —Static IP address prefix.  <i>routing-instance routing-instance-name</i> —Use user-defined static NAT routing-instance to perform static NAT. By default, the <i>routing-instance</i> is the same as the <i>from routing-instance</i> .
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<i>security</i> —To view this statement in the configuration. <i>security-control</i> —To add this statement to the configuration.

**sunrpc**

---

**Syntax**

```

sunrpc {
    disable;
    traceoptions {
        flag {
            all <extensive>;
        }
    }
}

```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 9.0 of JUNOS software.

**Description** Specify the Sun Microsystems remote procedure call (RPC) ALG on the device.

This statement is supported on J-series devices.

**Options** **disable**—Disable the Sun RPC ALG. By default, the Sun RPC ALG is enabled.

**traceoptions**—Configure the Sun RPC ALG tracing options.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

■ **all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## suppression

---

**Syntax**    suppression {  
               disable;  
               include-destination-address;  
               max-logs-operate *value* ;  
               max-time-report *value* ;  
               start-log *value* ;  
               }

**Hierarchy Level**    [edit security idp sensor-configuration log]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Log suppression reduces the number of logs by displaying a single record for multiple occurrences of the same event. Log suppression can negatively impact sensor performance if the reporting interval is set too high. By default this feature is enabled.

This statement is supported on SRX-series devices.

**Options**    disable—Disable log suppression.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## syn-ack-ack-proxy

---

<b>Syntax</b>	syn-ack-ack-proxy; { threshold <i>number</i> , }
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> tcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Prevent the SYN-ACK-ACK attack, which occurs when the attacker establishes multiple Telnet sessions without allowing each session to terminate. This behavior consumes all open slots, generating a denial-of-service (DoS) condition.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	threshold <i>number</i> — Number of connections from any single IP address. <b>Range:</b> 1 through 250000 <b>Default:</b> 512
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## syn-fin

---

<b>Syntax</b>	syn-fin;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> tcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Enables detection of an illegal combination of flags that attackers can use to consume sessions on the target device, thus resulting in a denial-of-service (DoS) condition.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## syn-flood

---

**Syntax**    syn-flood {  
               alarm-threshold *number* ;  
               attack-threshold *number* ;  
               destination-threshold *number* ;  
               source-threshold *number* ;  
               timeout *seconds* ;  
               }

**Hierarchy Level**    [edit security screen ids-option *screen-name* tcp]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure detection and prevention of SYN flood attacks. Such attacks occur when the connecting host continuously sends TCP SYN requests without replying to the corresponding ACK responses.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.



## syn-flood-protection-mode

---

<b>Syntax</b>	syn-flood-protection-mode (syn-cookie   syn-proxy);
<b>Hierarchy Level</b>	[edit security flow]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable SYN-cookie defenses or SYN-proxy defenses against SYN attacks.</p> <p>The SYN flood protection mode is enabled globally on the device and is activated when the configured <b>syn-flood attack-threshold value</b> is exceeded.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>syn-cookie</b>—Uses a cryptographic hash to generate a unique Initial Sequence Number (ISN). This is enabled by default.</p> <p><b>syn-proxy</b>—Uses a proxy to handle the SYN attack.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>
<b>Related Topics</b>	attack-threshold

## syn-frag

---

<b>Syntax</b>	syn-frag;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> top]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enables detection of a SYN fragment attack and drops any packet fragments used for the attack. A SYN fragment attack floods the target host with SYN packet fragments. The host caches these fragments, waiting for the remaining fragments to arrive so it can reassemble them. The flood of connections that cannot be completed eventually fills the host's memory buffer. No further connections are possible, and damage to the host's operating system can occur.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## **system-services**

---

See the following sections:

- `system-services` (Interface Host-Inbound Traffic) on page 536
- `system-services` (Zone Host-Inbound Traffic) on page 538

**system-services (Interface Host-Inbound Traffic)**

**Syntax**    `system-services {  
                  service-name ;  
                  service-name <except>;  
                  }`

**Hierarchy Level**    `[edit security zones security-zone zone-name interfaces interface-name  
                          host-inbound-traffic]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the types of traffic that can reach the device on a particular interface.

This statement is supported on J-series and SRX-series devices.

- Options**    *service-name* —Service for which traffic is allowed. The following services are supported:
- *all*—Enable all possible system services available on the Routing Engine (RE).
  - *any-service*—Enable services on entire port range.
  - *bootp*—Enables traffic destined to BOOTP and DHCP relay agents.
  - *dhcp*—Enable incoming DHCP requests.
  - *dns*—Enable incoming DNS services.
  - *finger*—Enable incoming finger traffic.
  - *ftp*—Enable incoming FTP traffic.
  - *ident-reset*—Enable the access that has been blocked by an unacknowledged identification request.
  - *http*—Enable incoming J-Web or clear-text Web authentication traffic.
  - *https*—Enable incoming J-Web or Web authentication traffic over Secure Sockets Layer (SSL).
  - *ike*—Enable Internet Key Exchange traffic.
  - *netconf SSH*—Enable incoming NetScreen Security Manager (NSM) traffic over SSH.
  - *ping*—Allow the device to respond to ICMP echo requests.
  - *rlogin*—Enable incoming *rlogin* (remote login) traffic.
  - *rpm*—Enable incoming real-time performance monitoring (RPM) traffic.
  - *rsh*—Enable incoming Remote Shell (*rsh*) traffic.
  - *snmp*—Enable incoming SNMP traffic (UDP port 161).
  - *snmp-trap*—Enable incoming SNMP traps (UDP port 162).
  - *ssh*—Enable incoming SSH traffic.
  - *telnet*—Enable incoming Telnet traffic.
  - *tftp*—Enable TFTP services.

- **traceroute**—Enable incoming traceroute traffic (UDP port 33434).
- **xnm-ssl**— Enable incoming JUNOScript-over-SSL traffic for all specified interfaces.
- **xnm-clear-text**—Enable incoming JUNOScript traffic for all specified interfaces.

**except**—(Optional) except can only be used if all has been defined.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**system-services (Zone Host-Inbound Traffic)**

**Syntax**    system-services {  
                   service-name ;  
                   service-name <except>;  
                   }

**Hierarchy Level**    [edit security zones security-zone *zone-name* host-inbound-traffic]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the types of traffic that can reach the device for all interfaces in a zone.

This statement is supported on J-series and SRX-series devices.

- Options**    *service-name* —Service for which traffic is allowed. The following services are supported:
- *all*—Enable all possible system services available on the Routing Engine (RE).
  - *any-service*—Enable services on entire port range.
  - *bootp*—Enables traffic destined to BOOTP and DHCP relay agents.
  - *dhcp*—Enable incoming DHCP requests.
  - *dns*—Enable incoming DNS services.
  - *finger*—Enable incoming finger traffic.
  - *ftp*—Enable incoming FTP traffic.
  - *ident-reset*—Enable the access that has been blocked by an unacknowledged identification request.
  - *http*—Enable incoming J-Web or clear-text Web authentication traffic.
  - *https*—Enable incoming J-Web or Web authentication traffic over Secure Sockets Layer (SSL).
  - *ike*—Enable Internet Key Exchange traffic.
  - *netconf SSH*—Enable incoming NetScreen Security Manager (NSM) traffic over SSH.
  - *ping*—Allow the device to respond to ICMP echo requests.
  - *rlogin*—Enable incoming *rlogin* (remote login) traffic.
  - *rpm*—Enable incoming Real-time performance monitoring (RPM) traffic.
  - *rsh*—Enable incoming Remote Shell (*rsh*) traffic.
  - *snmp*—Enable incoming SNMP traffic (UDP port 161).
  - *snmp-trap*—Enable incoming SNMP traps (UDP port 162).
  - *ssh*—Enable incoming SSH traffic.
  - *telnet*—Enable incoming Telnet traffic.
  - *tftp*—Enable TFTP services.
  - *traceroute*—Enables incoming traceroute traffic (UDP port 33434).

- `xnm-ssl`— Enable incoming JUNOScript-over-SSL traffic for all specified interfaces.
- `xnm-clear-text`—Enable incoming JUNOScript traffic for all specified interfaces.

`except`—(Optional) `except` can only be used if `all` has been defined.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `security`—To view this statement in the configuration.  
`security-control`—To add this statement to the configuration.

## t1-interval

---

**Syntax** `t1-interval milliseconds ;`

**Hierarchy Level** [edit security alg sip]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the maximum round-trip time (RTT) (in milliseconds) allowed for Session Initiation Protocol (SIP) transactions.

This statement is supported on J-series devices.

**Options** `milliseconds` —Maximum round-trip time (RTT) allowed measured in milliseconds.  
**Range:** 500 through 5000 milliseconds  
**Default:** 500 milliseconds

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `security`—To view this statement in the configuration.  
`security-control`—To add this statement to the configuration.

## t4-interval

---

<b>Syntax</b>	t4-interval <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit security alg sip]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the maximum length of time (in seconds) that the network can take to clear messages between client and server Session Initiation Protocol (SIP) transactions.</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<p><i>seconds</i> —Maximum number of seconds that the network can take to clear messages between client and server transactions.</p> <p><b>Range:</b> 5 through 10 seconds</p> <p><b>Default:</b> 5 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



## talk

---

**Syntax**

```
talk {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the TALK program ALG on the device.

This statement is supported on J-series devices.

**Options** **disable**—Disable the TALK program ALG. By default, the TALK program ALG is enabled.

**traceoptions**—Configure TALK program ALG tracing options.

**flag**—Trace operation to perform. To perform more than one trace operation, include multiple flag statements.

**all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## target

---

<b>Syntax</b>	target (destination-address   service   source-address   source-zone   zone-service);
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> then ip-action]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Specify the blocking options that you want to set to block the future connections. Blocking options can be based on the following matches of the attack traffic:</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>■ <b>destination-address</b>—Matches traffic based on the destination address of the attack traffic.</li> <li>■ <b>service</b>—Matches traffic based on the source address, destination address, destination port, and protocol of the attack traffic. This is the default.</li> <li>■ <b>source-address</b>—Matches traffic based on the source address of the attack traffic.</li> <li>■ <b>source-zone</b>—Matches traffic based on the source zone of the attack traffic.</li> <li>■ <b>zone-service</b>—Matches traffic based on the source zone, destination address, destination port, and protocol of the attack traffic.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## tcp

---

See the following sections:

- tcp (Protocol Binding Custom Attack) on page 543
- tcp (Security Screen) on page 544
- tcp (Signature Attack) on page 545

### tcp (Protocol Binding Custom Attack)

<b>Syntax</b>	tcp { minimum-port <i>port-number</i> maximum-port <i>port-number</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain protocol-binding] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol-binding]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Allow IDP to match the attack for specified TCP port(s).  This statement is supported on SRX-series devices.
<b>Options</b>	minimum-port <i>port-number</i> —Minimum port in the port range. <b>Range:</b> 0 through 65535  maximum-port <i>port-number</i> —Maximum port in the port range. <b>Range:</b> 0 through 65535
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**tcp (Security Screen)**

**Syntax**    tcp {  
               fin-no-ack;  
               land;  
               port-scan {  
                   threshold *number* ;  
               }  
               syn-ack-ack-proxy {  
                   threshold *number* ;  
               }  
               syn-fin;  
               syn-flood {  
                   alarm-threshold *number* ;  
                   attack-threshold *number* ;  
                   destination-threshold *number* ;  
                   source-threshold *number* ;  
                   timeout *seconds* ;  
               }  
               syn-frag;  
               tcp-no-flag;  
               winnuke;  
           }

**Hierarchy Level**    [edit security screen ids-option *screen-name* ]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure TCP-layer intrusion detection service (IDS) options.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

**tcp (Signature Attack)**

```

Syntax  tcp {
    ack-number {
        match (equal | greater-than | less-than | not-equal);
        value acknowledgement-number ;
    }
    data-length {
        match (equal | greater-than | less-than | not-equal);
        value tcp-data-length ;
    }
    destination-port {
        match (equal | greater-than | less-than | not-equal);
        value destination-port ;
    }
    header-length {
        match (equal | greater-than | less-than | not-equal);
        value header-length ;
    }
    mss {
        match (equal | greater-than | less-than | not-equal);
        value maximum-segment-size ;
    }
    option {
        match (equal | greater-than | less-than | not-equal);
        value tcp-option ;
    }
    sequence-number {
        match (equal | greater-than | less-than | not-equal);
        value sequence-number ;
    }
    source-port {
        match (equal | greater-than | less-than | not-equal);
        value source-port ;
    }
    tcp-flags {
        (ack | no-ack);
        (fin | no-fin);
        (psh | no-psh);
        (r1 | no-r1);
        (r2 | no-r2);
        (rst | no-rst);
        (syn | no-syn);
        (urg | no-urg);
    }
    urgent-pointer {
        match (equal | greater-than | less-than | not-equal);
        value urgent-pointer ;
    }
    window-scale {
        match (equal | greater-than | less-than | not-equal);
        value window-scale-factor ;
    }
    window-size {
        match (equal | greater-than | less-than | not-equal);
        value window-size ;
    }
}

```

```
}  
}
```

<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Allow IDP to match the TCP header information for the signature attack.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## tcp-flags

---

**Syntax**    tcp-flags {  
               (ack | no-ack);  
               (fin | no-fin);  
               (psh | no-psh);  
               (r1 | no-r1);  
               (r2 | no-r2);  
               (rst | no-rst);  
               (syn | no-syn);  
               (urg | no-urg);  
               }

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol tcp]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify that IDP looks for a pattern match whether or not the TCP flag is set.

This statement is supported on SRX-series devices.

**Options**    **ack | no-ack**—When set, the acknowledgment flag acknowledges receipt of a packet.

**fin | no-fin**—When set, the final flag indicates that the packet transfer is complete and the connection can be closed.

**psh | no-psh**—When set, the push flag indicates that the receiver should push all data in the current sequence to the destination application (identified by the port number) without waiting for the remaining packets in the sequence.

**r1 | no-r1**—When set, indicates that the R1 retransmission threshold has been reached.

**r2 | no-r2**—When set, indicates that the R2 retransmission threshold has been reached.

**rst | no-rst**—When set, the reset flag resets the TCP connection, discarding all packets in an existing sequence.

**syn | no-syn**—When set, indicates that the sending device is asking for a three-way handshake to initialize communications.

**urg | no-urg**—When set, the urgent flag indicates that the packet data is urgent.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

## tcp-initial-timeout

---

<b>Syntax</b>	tcp-initial-timeout <i>seconds</i> ;
<b>Hierarchy Level</b>	[edit security flow tcp-session]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Define the length of time (in seconds) that the device keeps an initial TCP session in the session table before dropping it, or until the device receives a FIN (no more data) or RST (reset) packet.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>seconds</i> —Number of seconds that the device keeps an initial TCP session in the session table before dropping it.</p> <p><b>Range:</b> 20 through 300 seconds</p> <p><b>Default:</b> 20 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.



**tcp-mss**

---

**Syntax**

```

tcp-mss {
  all-tcp {
    mss value ;
  }
  gre-in {
    mss value ;
  }
  gre-out {
    mss value ;
  }
  ipsec-vpn {
    mss value ;
  }
}

```

**Hierarchy Level** [edit security flow]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure TCP maximum segment size (TCP MSS) for the following packet types:

- All TCP packets for network traffic.
- GRE packets entering the IPsec VPN tunnel.
- GRE packets exiting the IPsec VPN tunnel.
- TCP packets entering the IPsec VPN tunnel.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## tcp-no-flag

---

<b>Syntax</b>	tcp-no-flag;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> tcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the device to drop illegal TCP packets with a missing or malformed flag field.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## tcp-rst

---

<b>Syntax</b>	tcp-rst;
<b>Hierarchy Level</b>	[edit security zones security-zone <i>zone-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable the device to send a TCP segment with the RST (reset) flag set to 1 (one) in response to a TCP segment with any flag other than SYN set and that does not belong to an existing session.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## tcp-session

---

**Syntax**    tcp-session {  
               no-sequence-check;  
               no-syn-check;  
               no-syn-check-in-tunnel;  
               rst-invalidate-session;  
               rst-sequence-check;  
               tcp-initial-timeout *seconds* ;  
           }

**Hierarchy Level**    [edit security flow]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure TCP session attributes:

- TCP sequence number checking.
- TCP SYN bit checking.
- Reset (RST) checking.
- Initial TCP session timeout.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                      security-control—To add this statement to the configuration.

## terminal

---

<b>Syntax</b>	terminal;
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Set or unset a terminal rule flag. The device stops matching rules for a session when a terminal rule is matched.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## test

---

<b>Syntax</b>	test <i>test-condition</i> ;}
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type anomaly]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify protocol anomaly condition to be checked.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>test-condition</i> —Name of the anomaly test condition.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**tftp**

---

**Syntax**

```
tftp {
  disable;
  traceoptions {
    flag {
      all <extensive>;
    }
  }
}
```

**Hierarchy Level** [edit security alg]

**Release Information** Statement modified in Release 9.2 of JUNOS software.

**Description** Configure the Trivial File Transfer Protocol (TFTP) ALG on the device.

This statement is supported on J-series and SRX-series devices.

**Options** **disable**—Disable the TFTP ALG. By default, the TFTP ALG is enabled.



**NOTE:** By default, the TFTP ALG is disabled for SRX-series devices.

---

**traceoptions**—Configure TFTP ALG tracing options.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

**all**—Trace all events.

**extensive**—(Optional) Display extensive amount of data.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** **security**—To view this statement in the configuration.  
**security-control**—To add this statement to the configuration.

## then

---

See the following sections:

- then (Destination NAT Services Gateway) on page 554
- then (IDP Policy) on page 555
- then (Security Policies) on page 556
- then (Source NAT Services Gateway) on page 557
- then (Static NAT Services Gateway) on page 557

### **then (Destination NAT Services Gateway)**

**Syntax**    then {  
                   destination-nat (off | pool *pool-name* );  
                   }

**Hierarchy Level**    [edit security nat destination rule-set *rule-set-name* rule *rule-name* ]

**Release Information**    Statement introduced in Release 9.2 of JUNOS software.

**Description**    Specify the action to be performed when traffic matches the destination NAT rule criteria.

This statement is supported on SRX-series devices.

**Options**    The remaining statement is explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                      security-control—To add this statement to the configuration.

**then (IDP Policy)**

**Syntax**

```

then {
  action {
    (close-client | close-client-and-server | close-server |
     drop-connection | drop-packet | ignore-connection |
     mark-diffserv value | no-action | recommended);
  }
  ip-action {
    (ip-block | ip-close | ip-notify);
    log;
    target (destination-address | service | source-address |
            source-zone | zone-service);
    timeout seconds ;
  }
  notification {
    log-attacks {
      alert (yes | no);
    }
  }
  severity (critical | info | major | minor | warning);
}

```

**Hierarchy Level** [edit security idp idp-policy *policy-name* rulebase-ips rule *rule-name* ]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the action to be performed when traffic matches the defined criteria.

This statement is supported on SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**then (Security Policies)**

```

Syntax  then {
            count {
                alarm {
                    per-minute-threshold number;
                    per-second-threshold number ;
                }
            }
            (deny | reject);
            permit {
                application-services (wx-redirect | wx-reverse-redirect);
                destination-address {
                    drop-translated;
                    drop-untranslated;
                }
                destination-nat destination-name ;
                firewall-authentication {
                    pass-through {
                        access-profile profile-name ;
                        client-match match-name ;
                        web-redirect;
                    }
                    web-authentication {
                        client-match user-or-group ;
                    }
                }
                source-nat (pool pool-name | pool-set pool-set-name | interface);
                tunnel {
                    ipsec-vpn vpn-name ;
                    pair-policy pair-policy ;
                }
            }
            log {
                session-close;
                session-init;
            }
        }

```

**Hierarchy Level** [edit security policies from-zone *zone-name* to-zone *zone-name* policy *policy-name* ]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the policy action to be performed when packets match the defined criteria.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



**then (Source NAT Services Gateway)**

<b>Syntax</b>	then { source-nat (off   interface   pool <i>pool-name</i> ); }
<b>Hierarchy Level</b>	[edit security nat source rule-set <i>rule-set-name</i> rule <i>rule-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the action to be performed when traffic matches the source NAT rule criteria.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statement is explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**then (Static NAT Services Gateway)**

<b>Syntax</b>	then { static-nat prefix < <i>addr-prefix</i> > <routing-instance <i>routing-instance-name</i> >; }
<b>Hierarchy Level</b>	[edit security nat static rule-set <i>rule-set-name</i> rule <i>rule-name</i> ]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the action to be performed when traffic matches the static NAT rule criteria.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statement is explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## threshold

---

<b>Syntax</b>	<code>threshold number ;</code>
<b>Hierarchy Level</b>	<code>[edit security ike gateway gateway-name dead-peer-detection]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the maximum number of unsuccessful dead peer detection (DPD) requests to be sent before the peer is considered unavailable.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>number</i> —Maximum number of unsuccessful DPD requests to be sent. <b>Range:</b> 1 through 5  <i>Output:</i> 5
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## time-binding

---

<b>Syntax</b>	<code>time-binding {     count count-value ;     scope (destination   peer   source); }</code>
<b>Hierarchy Level</b>	<code>[edit security idp custom-attack attack-name ]</code>
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Allow IDP to detect a sequence of the same attacks over a period of time.  This statement is supported on SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## timeout

---

See the following sections:

- [timeout \(IDP Policy\)](#) on page 559
- [timeout \(Security Screen\)](#) on page 560

### ***timeout (IDP Policy)***

**Syntax** `timeout seconds ;`

**Hierarchy Level** `[edit security idp idp-policy policy-name rulebase-ips rule rule-name then ip-action]`

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Specify the number of seconds that you want the IP action to remain in effect after a traffic match.

This statement is supported on SRX-series devices.

**Options** `seconds` —Number of seconds the IP action should remain effective.

**Range:** 0 through 65535 seconds

**Default:** 0 second

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** `security`—To view this statement in the configuration.  
`security-control`—To add this statement to the configuration.

**timeout (Security Screen)**

<b>Syntax</b>	<code>timeout seconds ;</code>
<b>Hierarchy Level</b>	<code>[edit security screen ids-option <i>screen-name</i> tcp syn-flood]</code>
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the maximum length of time before a half-completed connection is dropped from the queue. You can decrease the timeout value until you see any connections dropped during normal traffic conditions.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<code>seconds</code> —Time interval before a half-completed connection is dropped from the queue. <b>Range:</b> 1 through 50 seconds <b>Default:</b> 20 seconds
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**to**


---

<b>Syntax</b>	<code>to interface [interface-name]   routing-instance [routing-instance-name]   zone [zone-name];</code>
<b>Hierarchy Level</b>	<code>[edit security nat source rule-set <i>rule-set-name</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the destination of the packet among the routing instance, interface, or zone.  This statement is supported on SRX-series devices.
<b>Options</b>	<code>interface <i>interface-name</i></code> —Name of the interface.  <code>routing-instance <i>routing-instance-name</i></code> —Name of the routing instance.  <code>zone <i>zone-name</i></code> —Name of the zone.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**to-zone**

---

<b>Syntax</b>	<code>to-zone zone-name ;</code>
<b>Hierarchy Level</b>	[edit security idp idp-policy <i>policy-name</i> rulebase-exempt rule <i>rule-name</i> match], [edit security idp idp-policy <i>policy-name</i> rulebase-ips rule <i>rule-name</i> match]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify a destination zone to be associated with the security policy. The default value is any.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>zone-name</i> —Name of the destination zone object.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**tos**

---

**Syntax**    `tos {  
               match (equal | greater-than | less-than | not-equal);  
               value type-of-service-in-decimal ;  
           }`

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol ip]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Specify the type of service.

This statement is supported on SRX-series devices.

**Options**    `match (equal | greater-than | less-than | not-equal)`—Match an operand.  
               `value type-of-service-in-decimal` —The following service types are available:

- 0000—Default
- 0001—Minimize Cost
- 0002—Maximize Reliability
- 0003—Maximize Throughput
- 0004—Minimize Delay
- 0005—Maximize Security

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.

## total-length

---

<b>Syntax</b>	total-length { match (equal   greater-than   less-than   not-equal); value <i>total-length-of-ip-datagram</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol ip]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the number of bytes in the packet, including all header fields and the data payload.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>total-length-of-ip-datagram</i> —Length of the IP datagram. <b>Range:</b> 0 through 65535
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## traceoptions

---

See the following sections:

- [traceoptions \(firewall-authentication\)](#) on page 565
- [traceoptions \(H.323 ALG\)](#) on page 566
- [traceoptions \(Flow\)](#) on page 567
- [traceoptions \(IDP\)](#) on page 569
- [traceoptions \(IKE\)](#) on page 571
- [traceoptions \(IPsec\)](#) on page 572
- [traceoptions \(MGCP ALG\)](#) on page 573
- [traceoptions \(NAT Services Gateway\)](#) on page 574
- [traceoptions \(NAT Services Router\)](#) on page 576
- [traceoptions \(PKI\)](#) on page 578
- [traceoptions \(Policies\)](#) on page 580
- [traceoptions \(SCCP ALG\)](#) on page 582
- [traceoptions \(Screen\)](#) on page 583
- [traceoptions \(Security\)](#) on page 585
- [traceoptions \(SIP ALG\)](#) on page 587



***traceoptions (firewall-authentication)***

**Syntax**    `traceoptions {  
               flag {  
                   all <detail | extensive | terse>;  
                   authentication <detail | extensive | terse>;  
                   proxy <detail | extensive | terse>;  
               }  
           }`

**Hierarchy Level**    [edit security firewall-authentication]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Define data-plane firewall authentication tracing options.

This statement is supported on J-series and SRX-series devices.

**Options**    `flag`—Trace operation to perform. To specify more than one trace operation, include multiple `flag` statements.

- `all`—Enable all tracing operations
- `authentication`—Trace data-plane firewall authentication events
- `proxy`—Trace data-plane firewall authentication proxy events

`detail`—Display moderate amount of data in trace.

`extensive`—Display extensive amount of data in trace.

`terse`—Display minimum amount of data in trace.

**Required Privilege Level**    `trace`—To view this statement in the configuration.  
                                   `trace-control`—To add this statement to the configuration.

**traceoptions (H.323 ALG)**

**Syntax** traceoptions {  
     flag {  
         all <detail | extensive | terse>;  
         cc <detail | extensive | terse>;  
         h225-asn1 <detail | extensive | terse>;  
         h245 <detail | extensive | terse>;  
         h245-asn1 <detail | extensive | terse>;  
         q931 <detail | extensive | terse>;  
         ras <detail | extensive | terse>;  
         ras-asn1 <detail | extensive | terse>;  
     }  
 }

**Hierarchy Level** [edit security alg h323]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure H.323 tracing options.

This statement is supported on J-series devices.

**Options** flag—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- all—Trace with all flags enabled
- cc—Trace chassis cluster functions
- h225-asn1—Trace H.225 ASN.1 processing activity
- h245—Trace H.245 processing activity
- h245-asn1—Trace H.245 ASN.1 processing activity
- q931—Trace Q.931 processing activity
- ras—Trace remote access server (RAS) processing activity
- ras-asn1—Trace RAS ASN.1 processing activity

detail—Display moderate amount of data in trace.

extensive—Display extensive amount of data in trace.

terse—Display minimum amount of data in trace.

**Required Privilege Level** trace—To view this statement in the configuration.  
 trace-control—To add this statement to the configuration.

**traceoptions (Flow)**

**Syntax** traceoptions {  
     file *filename* <files *number* > <match *regular-expression* > <size *maximum-file-size* >  
     <world-readable | no-world-readable>;  
     flag *flag* ;  
 }

**Hierarchy Level** [edit security flow]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure flow tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename* —Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory */var/log*.

files *number* —(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The **world-readable** option enables any user to read the file. To explicitly set the default behavior, use the **no-world-readable** option.

flag—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

- **ager**—Trace session ageout related events
- **all**—Trace with all flags enabled
- **basic-datapath**—Trace basic packet flow activity
- **cli**—Trace CLI configuration activity and command changes
- **errors**—Trace flow errors activity
- **fragmentation**—Trace IP fragmentation and reassembly events
- **chassis-cluster**—Trace chassis cluster information
- **host-traffic**—Trace host traffic information
- **lookup**—Trace lookup events
- **multicast**—Trace multicast flow information
- **packet-drops**—Trace packet drop activity
- **route**—Trace route information
- **session**—Trace session creation and deletion events
- **session-scan**—Trace session scan information
- **tcp-advanced**—Trace advanced TCP packet flow activity
- **tcp-basic**—Trace TCP packet flow activity
- **tunnel**—Trace tunnel information

**Required Privilege Level**    **trace**—To view this statement in the configuration.  
    **trace-control**—To add this statement to the configuration.

**traceoptions (IDP)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number* >;  
         <match *regular-expression* >;  
         <size *maximum-file-size* >;  
         <world-readable | no-world-readable>;  
     }  
     flag all;  
     level (all | error | info | notice | verbose | warning);  
     no-remote-trace;  
 }

**Hierarchy Level** [edit security idp]

**Release Information** Statement introduced in Release 9.2 of JUNOS software.

**Description** Configure IDP tracing options.

This statement is supported on SRX-series devices.

**Options** file *filename* —Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory */var/log*.

files *number* —(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option

enables any user to read the file. To explicitly set the default behavior, use the `no-world-readable` option.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace all iked process modules activity

**level**—Set the level of debugging the output option.

- **all**—Match all levels
- **error**—Match error conditions
- **info**—Match informational messages
- **notice**—Match conditions that should be handled specially
- **verbose**—Match verbose messages
- **warning**—Match warning messages

**no-remote-trace**—Set remote tracing as disabled.

**Required Privilege Level** **trace**—To view this statement in the configuration.  
**trace-control**—To add this statement to the configuration.

**traceoptions (IKE)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number* >;  
         <match *regular-expression* >;  
         <size *maximum-file-size* >;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit security ike]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure IKE tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename* —Name of the file to receive the output of the tracing operation. Enclose the name within quotation marks. All files are placed in the directory */var/log*.

files *number* —(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option enables any user to read the file. To explicitly set the default behavior, use the *no-world-readable* option.

**flag** *flag*—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace all iked process modules activity
- **certificates**—Trace certificate-related activity
- **database**—Trace VPN-related database activity
- **general**—Trace general activity
- **ike**—Trace IKE protocol activity
- **parse**—Trace VPN parsing activity
- **policy-manager**—Trace iked callback activity
- **routing-socket**—Trace routing socket activity
- **timer**—Trace timer activity
- **snmp**—Trace SNMP operations activity

**Required Privilege Level** **trace**—To view this statement in the configuration.  
**trace-control**—To add this statement to the configuration.

### ***traceoptions (IPsec)***

**Syntax**

```
traceoptions {
    flag {
        all;
        next-hop-tunnel-binding;
        packet-drops;
        packet-processing;
        security-associations;
    }
}
```

**Hierarchy Level** [edit security ipsec]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure IPsec tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** **flag**—To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace with all flags enabled
- **next-hop-tunnel-binding**—Trace next-hop tunnel binding events
- **packet-drops**—Trace packet drop activity
- **packet-processing**—Trace data packet processing events
- **security-associations**—Trace security association (SA) management events

**Required Privilege Level** **trace**—To view this statement in the configuration.  
**trace-control**—To add this statement to the configuration.



**traceoptions (MGCP ALG)**

**Syntax**

```

traceoptions {
  flag {
    all <extensive>;
    call <extensive>;
    cc <extensive>;
    decode <extensive>;
    error <extensive>;
    nat <extensive>;
    packet <extensive>;
    rm <extensive>;
  }
}

```

**Hierarchy Level** [edit security alg mgcp]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure Media Gateway Control Protocol (MGCP) tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** flag—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- all—Trace with all flags enabled
- call—Trace call processing activity
- cc—Trace chassis cluster functions
- decode—Trace decoder operations activity
- error—Trace processing errors activity
- nat—Trace Network Address Translation (NAT) processing activity
- packet—Trace MGCP protocol packet processing activity
- rm—Trace MGCP Resource Management (Resmgr) functions activity

**Required Privilege Level** trace—To view this statement in the configuration.  
 trace-control—To add this statement to the configuration.

**traceoptions (NAT Services Gateway)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number* >;  
         <match *regular-expression* >;  
         <size *maximum-file-size* >;  
         <world-readable | no-world-readable>;  
     }  
     flag {  
         all;  
         destination-nat-pfe;  
         destination-nat-re;  
         destination-nat-rt;  
         source-nat-pfe;  
         source-nat-re;  
         source-nat-rt;  
         static-nat-pfe;  
         static-nat-re;  
         static-nat-rt;  
     }  
     no-remote-trace;  
 }

**Hierarchy Level** [edit security nat]

**Release Information** Statement modified in Release 9.3 of JUNOS software.

**Description** Configure NAT tracing options.

This statement is supported on SRX-series devices.

**Options** *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

*files number* —(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

*match regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

*size maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the `files` option and filename.

**Syntax:** `x k` to specify KB, `x m` to specify MB, or `x g` to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

**world-readable | no-world-readable**—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The **world-readable** option enables any user to read the file. To explicitly set the default behavior, use the **no-world-readable** option.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace with all flags enabled
- **destination-nat-pfe**—Trace destination NAT events on PFE-ukernel side
- **destination-nat-re**—Trace destination NAT events on routing engine (RE) side
- **destination-nat-rt**—Trace destination NAT events on packet processing engine real-time (PFE-RT) side
- **source-nat-pfe**—Trace source NAT events on PFE-ukernel side
- **source-nat-re**—Trace source NAT events on RE side
- **source-nat-rt**—Trace source NAT events on PFE-RT side
- **static-nat-pfe**—Trace static NAT events on PFE-ukernel side
- **static-nat-re**—Trace static NAT events on RE side
- **static-nat-rt**—Trace static NAT events on PFE-RT side

**no-remote-trace**—Set remote tracing as disabled.

**Required Privilege Level**

**trace**—To view this statement in the configuration.

**trace-control**—To add this statement to the configuration.

**traceoptions (NAT Services Router)**

**Syntax** traceoptions {  
     file *filename* <files *number* > <match *regular-expression* >  
     <size *maximum-file-size* > <world-readable | no-world-readable>;  
     flag *flag*;  
 }

**Hierarchy Level** [edit security nat]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure NAT tracing options.

This statement is supported on J-series devices.

**Options** *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

files *number* —(Optional) Maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The **world-readable** option enables any user to read the file. To explicitly set the default behavior, use the **no-world-readable** option.

flag—Trace operation to perform. To specify more than one trace operation, include multiple flag statements.

- all—Trace with all flags enabled

- configuration—Trace configuration events
- flow—Trace flow events
- routing-protocol—Trace routing protocol events
- routing-socket—Trace routing socket events

**Required Privilege Level**    trace—To view this statement in the configuration.  
                                      trace-control—To add this statement to the configuration.

**traceoptions (PKI)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number* >;  
         <match *regular-expression* >;  
         <size *maximum-file-size* >;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit security pki]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure public key infrastructure (PKI) tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

*files number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1* , and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

*match regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

*size maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** *x k* to specify KB, *x m* to specify MB, or *x g* to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

*world-readable | no-world-readable*—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option enables any user to read the file. To explicitly set the default behavior, use the *no-world-readable* option.

**flag**—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace with all flags enabled
- **certificate-verification**—Trace PKI certificate verification events
- **online-crl-check**—Trace PKI online certificate revocation list (CRL) events

**Required Privilege Level**

**trace**—To view this statement in the configuration.

**trace-control**—To add this statement to the configuration.

**traceoptions (Policies)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number* >;  
         <match *regular-expression* >;  
         <size *maximum-file-size* >;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit security policies]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure policy tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

*files number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1* , and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

*match regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

*size maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** *x k* to specify KB, *x m* to specify MB, or *x g* to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

*world-readable | no-world-readable*—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option enables any user to read the file. To explicitly set the default behavior, use the *no-world-readable* option.



**flag**—Trace operation to perform. To specify more than one trace operation, include multiple **flag** statements.

- **all**—Trace with all flags enabled
- **configuration**—Trace configuration events
- **compilation**—Trace policy compilation events
- **ipc**—Trace process inter communication events
- **lookup**—Trace policy lookup events
- **routing-socket**—Trace routing socket events
- **rules**—Trace policy rules-related events

**Required Privilege Level**    **trace**—To view this statement in the configuration.  
    **trace-control**—To add this statement to the configuration.

**traceoptions (SCCP ALG)**

**Syntax**    traceoptions {  
               flag {  
                   all <extensive>;  
                   call <extensive>;  
                   cc <extensive>;  
                   cli <extensive>;  
                   decode <extensive>;  
                   error <extensive>;  
                   init <extensive>;  
                   nat <extensive>;  
                   rm <extensive>;  
               }  
           }

**Hierarchy Level**    [edit security alg sccp]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure Skinny Client Control Protocol (SCCP) tracing options.

This statement is supported on J-series devices.

**Options**    *flag* —Trace operation to perform. To specify more than one trace operation, include multiple *flag* statements.

- *all*—Trace with all flags enabled
- *call*—Enable tracing for SCCP call processing
- *cc*—Enable tracing for SCCP chassis cluster functions
- *cli*—Enable tracing for SCCP command-line interface (CLI) client processing
- *decode*—Enable tracing for SCCP decoder operations
- *error*—Enable tracing for SCCP processing errors
- *init*—Enable tracing for SCCP initialization errors
- *nat*—Enable tracing for SCCP NAT processing
- *rm*—Enable tracing for SCCP Resource Management (Resmgr) functions

**Required Privilege Level**    trace—To view this statement in the configuration.  
                                   trace-control—To add this statement to the configuration.

**traceoptions (Screen)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number* >;  
         <match *regular-expression* >;  
         <size *maximum-file-size* >;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit security screen]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure screen tracing options.

To specify more than one tracing option, include multiple **flag** statements.

This statement is supported on J-series and SRX-series devices.

**Options** *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

**files** *number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

**match** *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

**size** *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

**world-readable | no-world-readable**—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The **world-readable** option

enables any user to read the file. To explicitly set the default behavior, use the `no-world-readable` option.

`flag`—Trace operation to perform. To specify more than one trace operation, include multiple `flag` statements.

- `all`—Trace all screen events
- `configuration`—Trace screen configuration events
- `flow`—Trace flow events

**Required Privilege Level** `trace`—To view this statement in the configuration.  
`trace-control`—To add this statement to the configuration.

**traceoptions (Security)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number*> ;  
         <match *regular-expression*> ;  
         <size *maximum-file-size*> ;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
     no-remote-trace;  
     rate-limit *rate* ;  
 }

**Hierarchy Level** [edit security]

**Release Information** Statement modified in Release 8.5 of JUNOS software.

**Description** Configure security tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

*files number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1*, and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

*match regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

*size maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** *x k* to specify KB, *x m* to specify MB, or *x g* to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

*world-readable | no-world-readable*—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option

enables any user to read the file. To explicitly set the default behavior, use the `no-world-readable` option.

`flag`—Trace operation to perform. To specify more than one trace operation, include multiple `flag` statements.

- `all`—Trace all security events
- `configuration`—Trace security configuration events
- `compilation`—Trace security compilation events
- `routing-socket`—Trace routing socket events

`no-remote-trace`—Set remote tracing as disabled.

`rate-limit` *rate* —Number of trace per second. You can configure the incoming rate of trace messages.

**Required Privilege Level** `trace`—To view this statement in the configuration.  
`trace-control`—To add this statement to the configuration.

**traceoptions (SIP ALG)**

**Syntax** traceoptions {  
     flag {  
         all <detail | extensive | terse>;  
         call <detail | extensive | terse>;  
         cc <detail | extensive | terse>;  
         nat <detail | extensive | terse>;  
         parser <detail | extensive | terse>;  
         rm <detail | extensive | terse>;  
     }  
 }

**Hierarchy Level** [edit security alg sip]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure Session Initiation Protocol (SIP) tracing options.

This statement is supported on J-series devices.

**Options** *flag* —Trace operation to perform. To specify more than one trace operation, include multiple *flag* statements.

- *all*—Trace with all flags enabled
- *call*—Enable tracing for SIP call processing
- *cc*—Enable tracing for SIP chassis cluster functions
- *nat*—Enable tracing SIP Network Address Translation (NAT) processing
- *parser*—Enable tracing SIP parser operations
- *rm*—Enable tracing SIP Resource Management (Resmgr) functions

*detail*—Display moderate amount of data in trace.

*extensive*—Display extensive amount of data in trace.

*terse*—Display minimum amount of data in trace.

**Required Privilege Level** *trace*—To view this statement in the configuration.  
*trace-control*—To add this statement to the configuration.

## transaction-timeout

---

<b>Syntax</b>	transaction-timeout seconds ;
<b>Hierarchy Level</b>	[edit security alg mgcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Timeout value for Media Gateway Control Protocol (MGCP) transactions. If the timeout value exceeds transaction will be removed by MGCP transactions ager out processing.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>seconds —Timeout value.</p> <p><b>Range:</b> 3 through 50 seconds</p> <p><b>Default:</b> 30 seconds</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## trusted-ca

---

<b>Syntax</b>	trusted-ca ( ca-index   use-all);
<b>Hierarchy Level</b>	[edit security ike policy policy-name certificate]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the preferred certificate authority (CA) to use when requesting a certificate from the peer. If no value is specified, then no certificate request is sent (although incoming certificates are still accepted).</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>■ ca-index —Preferred certificate authority ID for the device to use.</li> <li>■ use-all—Device uses all configured certificate authorities.</li> </ul>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>



**ttl**

---

<b>Syntax</b>	ttl { match (equal   greater-than   less-than   not-equal); value <i>time-to-live</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol ip]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify the time-to-live (TTL) value of the packet. This value represents the number of routers the packet can pass through. Each router that processes the packet decrements the TTL by 1; when the TTL reaches 0, the packet is discarded.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>match (equal   greater-than   less-than   not-equal)—Match an operand.</p> <p>value<i>time-to-live</i>—The time-to-live value.     <b>Range:</b> 0 through 255</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## tunable-name

---

<b>Syntax</b>	<code>tunable-name <i>tunable-name</i> {     tunable-value <i>protocol-value</i> ; }</code>
<b>Hierarchy Level</b>	<code>[edit security idp sensor-configuration detector protocol-name <i>protocol-name</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the name of the tunable parameter to enable or disable the protocol detector for each of the service. By default, the protocol decoders for all services are enabled.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>tunable-name</i> —Name of the specific tunable parameter.  The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## tunable-value

---

<b>Syntax</b>	<code>tunable-value <i>protocol-value</i> ;</code>
<b>Hierarchy Level</b>	<code>[edit security idp sensor-configuration detector protocol-name <i>protocol-name</i>     tunable-name <i>tunable-name</i> ]</code>
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the value of the tunable parameter to enable or disable the protocol detector for each of the service.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>protocol-value</i> —Protocol number.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## tunnel

---

<b>Syntax</b>	<pre>tunnel {     ipsec-vpn <i>vpn-name</i> ;     pair-policy <i>pair-policy</i> ; }</pre>
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Encapsulate outgoing IP packets and decapsulate incoming IP packets.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## type

---

See the following sections:

- type (ICMP Headers in Signature Attack) on page 592
- type (Dynamic Attack Group) on page 593

### **type (ICMP Headers in Signature Attack)**

**Syntax** type {  
     match (equal | greater-than | less-than | not-equal);  
     value *type-value*;  
 }

**Hierarchy Level** [edit security idp custom-attack *attack-name* attack-type signature protocol icmp]

**Release Information** Statement introduced in Release 9.3 of JUNOS software.

**Description** Specify the primary code that identifies the function of the request/reply.

This statement is supported on SRX-series devices.

**Options** match (equal | greater-than | less-than | not-equal)—Match an operand.

value*type-value*—Match a decimal value.

**Range:** 0 through 255

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
 security-control—To add this statement to the configuration.

**type (Dynamic Attack Group)**

<b>Syntax</b>	<pre> type {     values [anomaly   signature]; } </pre>
<b>Hierarchy Level</b>	[edit security idp dynamic-attack-group <i>dynamic-attack-group-name</i> filters]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify an attack type filter to add attack objects based on the type of attack object (signature or protocol anomaly).</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	values—Name of the attack type filter.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## udp

---

See the following sections:

- udp (Protocol Binding Custom Attack) on page 594
- udp (Security Screen) on page 595
- udp (Signature Attack) on page 596

### udp (Protocol Binding Custom Attack)

<b>Syntax</b>	udp { minimum-port <i>port-number</i> maximum-port <i>port-number</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type chain protocol-binding] [edit security idp custom-attack <i>attack-name</i> attack-type signature protocol-binding]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Allow IDP to match the attack for specified UDP port(s).  This statement is supported on SRX-series devices.
<b>Options</b>	minimum-port <i>port-number</i> —Minimum port in the port range. <b>Range:</b> 0 through 65535  maximum-port <i>port-number</i> —Maximum port in the port range. <b>Range:</b> 0 through 65535
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**udp (Security Screen)**

**Syntax**    `udp {  
               flood {  
                   threshold number ;  
               }  
           }`

**Hierarchy Level**    `[edit security screen ids-option screen-name ]`

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify the number of packets allowed per second to the same destination IP address/port pair. When the number of packets exceeds this value within any 1-second period, the device generates an alarm and drops subsequent packets for the remainder of that second.

This statement is supported on J-series and SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                  security-control—To add this statement to the configuration.

**udp (Signature Attack)**

**Syntax**    `udp {  
               data-length {  
                   match (equal | greater-than | less-than | not-equal);  
                   value data-length ;  
               }  
               destination-port {  
                   match (equal | greater-than | less-than | not-equal);  
                   value destination-port ;  
               }  
               source-port {  
                   match (equal | greater-than | less-than | not-equal);  
                   value source-port ;  
               }  
           }`

**Hierarchy Level**    [edit security idp custom-attack *attack-name* attack-type signature protocol]

**Release Information**    Statement introduced in Release 9.3 of JUNOS software.

**Description**    Allow IDP to match the UDP header information for the signature attack.

This statement is supported on SRX-series devices.

**Options**    The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                                   security-control—To add this statement to the configuration.



## unknown-message

---

See the following sections:

- unknown-message (H.323 ALG) on page 597
- unknown-message (MGCP ALG) on page 598
- unknown-message (SCCP ALG) on page 599
- unknown-message (SIP ALG) on page 600

### unknown-message (H.323 ALG)

**Syntax**    unknown-message {  
                  permit-nat-applied;  
                  permit-routed;  
                  }

**Hierarchy Level**    [edit security alg h323 application-screen]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify how unidentified H.323 messages are handled by the device. The default is to drop unknown (unsupported) messages. Permitting unknown messages can compromise security and is not recommended. However, in a secure test or production environment, this statement can be useful for resolving interoperability issues with disparate vendor equipment. By permitting unknown H.323 (unsupported) messages, you can get your network operational and later analyze your VoIP traffic to determine why some messages were being dropped.

This statement applies only to received packets identified as supported VoIP packets. If a packet cannot be identified, it is always dropped. If a packet is identified as a supported protocol, the message is forwarded without processing.

This statement is supported on J-series devices.

**Options**    **permit-nat-applied**—Specifies that unknown messages be allowed to pass if the session is in NAT mode.

**permit-routed**— Specifies that unknown messages be allowed to pass if the session is in Route mode. (Sessions in Transparent mode are treated as Route mode.)

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
   security-control—To add this statement to the configuration.

**unknown-message (MGCP ALG)**

**Syntax**    unknown-message {  
                  permit-nat-applied;  
                  permit-routed;  
               }

**Hierarchy Level**    [edit security alg mgcp application-screen]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify how unidentified Media Gateway Control Protocol (MGCP) messages are handled by the device. The default is to drop unknown (unsupported) messages. Permitting unknown messages can compromise security and is not recommended. However, in a secure test or production environment, this statement can be useful for resolving interoperability issues with disparate vendor equipment. By permitting unknown MGCP (unsupported) messages, you can get your network operational and later analyze your VoIP traffic to determine why some messages were being dropped.

This statement applies only to received packets identified as supported VoIP packets. If a packet cannot be identified, it is always dropped. If a packet is identified as a supported protocol, the message is forwarded without processing.

This statement is supported on J-series and SRX-series devices.

**Options**    **permit-nat-applied**—Specifies that unknown messages be allowed to pass if the session is in NAT mode.

**permit-routed**— Specifies that unknown messages be allowed to pass if the session is in Route mode. (Sessions in Transparent mode are treated as Route mode.)

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

**unknown-message (SCCP ALG)**

**Syntax**    unknown-message {  
                  permit-nat-applied;  
                  permit-routed;  
          }

**Hierarchy Level**    [edit security alg sccp application-screen]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify how unidentified Skinny Client Control Protocol (SCCP) messages are handled by the device. The default is to drop unknown (unsupported) messages. Permitting unknown messages can compromise security and is not recommended. However, in a secure test or production environment, this statement can be useful for resolving interoperability issues with disparate vendor equipment. By permitting unknown SCCP (unsupported) messages, you can get your network operational and later analyze your VoIP traffic to determine why some messages were being dropped.

This statement applies only to received packets identified as supported VoIP packets. If a packet cannot be identified, it is always dropped. If a packet is identified as a supported protocol, the message is forwarded without processing.

This statement is supported on J-series devices.

**Options**    **permit-nat-applied**—Specifies that unknown messages be allowed to pass if the session is in NAT mode.

**permit-routed**— Specifies that unknown messages be allowed to pass if the session is in Route mode. (Sessions in Transparent mode are treated as Route mode.)

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
          security-control—To add this statement to the configuration.

**unknown-message (SIP ALG)**

**Syntax**    unknown-message {  
                  permit-nat-applied;  
                  permit-routed;  
                  }

**Hierarchy Level**    [edit security alg sip application-screen]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Specify how unidentified Session Initiation Protocol (SIP) messages are handled by the device. The default is to drop unknown (unsupported) messages. Permitting unknown messages can compromise security and is not recommended. However, in a secure test or production environment, this statement can be useful for resolving interoperability issues with disparate vendor equipment. By permitting unknown SIP (unsupported) messages, you can get your network operational and later analyze your VoIP traffic to determine why some messages were being dropped.

This statement applies only to received packets identified as supported VoIP packets. If a packet cannot be identified, it is always dropped. If a packet is identified as a supported protocol, the message is forwarded without processing.

This statement is supported on J-series devices.

**Options**    **permit-nat-applied**—Specifies that unknown messages be allowed to pass if the session is in NAT mode.

**permit-routed**— Specifies that unknown messages be allowed to pass if the session is in Route mode. (Sessions in Transparent mode are treated as Route mode.)

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    security—To view this statement in the configuration.  
                  security-control—To add this statement to the configuration.

## urgent-pointer

---

<b>Syntax</b>	urgent-pointer { match (equal   greater-than   less-than   not-equal); value <i>urgent-pointer</i> ; }
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the data in the packet is urgent; the URG flag must be set to activate this field.  This statement is supported on SRX-series devices.
<b>Options</b>	match (equal   greater-than   less-than   not-equal)—Match an operand.  value <i>urgent-pointer</i> —Match the value of the urgent pointer. <b>Range:</b> 0 through 65535
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## url

---

<b>Syntax</b>	url <i>url-name</i> ;
<b>Hierarchy Level</b>	[edit security idp security-package]
<b>Release Information</b>	Statement introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Specify the URL to automatically download the updated signature database.  This statement is supported on SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## user-at-hostname

---

<b>Syntax</b>	<code>user-at-hostname <i>user-at-hostname</i> ;</code>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure an e-mail address.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>user-at-hostname</i> —Valid e-mail address.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

**vpn**

**Syntax** `vpn vpn-name ;`  
`bind-interface interface-name ;`  
`df-bit (clear | copy | set);`  
`establish-tunnels (immediately | on-traffic);`  
`ike {`  
     `gateway gateway -name ;`  
     `idle-time seconds ;`  
     `install-interval seconds ;`  
     `ipsec-policy ipsec-policy-name ;`  
     `no-anti-replay;`  
     `proxy-identity {`  
         `local ipv4-prefix ;`  
         `remote ipv4-prefix ;`  
         `service service-name ;`  
     `}`  
`}`  
`manual {`  
     `authentication {`  
         `algorithm (hmac-md5-96 | hmac-sha1-96);`  
         `key (ascii-text key | hexadecimal key );`  
     `}`  
     `encryption {`  
         `algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);`  
         `key (ascii-text key | hexadecimal key );`  
     `}`  
     `external-interface external-interface-name ;`  
     `gateway ip-address ;`  
     `protocol (ah | esp);`  
     `spi spi-value ;`  
`}`  
`vpn-monitor {`  
     `destination-ip ip-address ;`  
     `optimized;`  
     `source-interface interface-name ;`  
`}`

**Hierarchy Level** [edit security ipsec]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure an IPsec VPN.

This statement is supported on J-series and SRX-series devices.

**Options** *vpn-name* —Name of the VPN.

The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

## vpn-monitor

---

**Syntax** vpn-monitor {  
    destination-ip *ip-address* ;  
    optimized;  
    source-interface *interface-name* ;  
}

**Hierarchy Level** [edit security ipsec vpn *vpn-name* ]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure settings for VPN monitoring. This feature cannot be configured simultaneously with the **dead-peer-detection** statement.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.

**Related Topics** dead-peer-detection



## vpn-monitor-options

---

<b>Syntax</b>	vpn-monitor-options { interval <i>seconds</i> ; threshold <i>number</i> ; }
<b>Hierarchy Level</b>	[edit security ipsec]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure VPN monitoring options.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	interval <i>seconds</i> —Interval at which to send ICMP requests to the peer. <b>Range:</b> 1 through 3600 seconds <b>Default:</b> 10 seconds  threshold <i>number</i> —number of consecutive unsuccessful pings before the peer is declared unreachable. <b>Range:</b> 1 through 65536 pings <b>Default:</b> 10 pings
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## web-authentication

---

<b>Syntax</b>	web-authentication { client-match <i>user-or-group</i> ; }
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to-zone <i>zone-name</i> policy <i>policy-name</i> then permit firewall-authentication]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that the policy allows access to users who have previously been authenticated by Web authentication. Web authentication must be enabled on one of the addresses on the interface to which the HTTP request is redirected.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	client-match <i>user-or-group</i> —(Optional) Username or user group name.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## web-redirect

---

<b>Syntax</b>	web-redirect;
<b>Hierarchy Level</b>	[edit security policies from-zone <i>zone-name</i> to zone <i>zone-name</i> policy <i>policy-name</i> then permit firewall-authentication pass-through]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Optionally, redirect HTTP requests to the device's internal Web server by sending a redirect HTTP response to the client system to reconnect to the Web server for user authentication. The interface on which the client's request arrived is the interface to which the request is redirected.</p> <p>Using this feature allows for a richer user login experience. For example, instead of a popup prompt asking for username and password, users can get the login page in a browser. Enabling <b>web-redirect</b> has the same effect as users typing the Web authentication IP address in a client browser. Using <b>web-redirect</b> provides a more seamless authentication experience because users do not need to know the Web authentication IP address but only the IP address of the resource they are trying to access. After the user has been authenticated this way, traffic from user's IP address is authenticated to go through the <b>web-redirect</b> method.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## wildcard

---

<b>Syntax</b>	wildcard <i>string</i> ;
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> dynamic distinguished-name]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify that the values of a dynamic virtual private network (VPN) endpoint user's distinguished name's identity fields match the values in the group IKE user's distinguished name's fields. The order of the identity fields in the distinguished name strings does not matter during a match.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>string</i> —Distinguished name identity values to be matched.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## window-scale

---

<b>Syntax</b>	<pre> window-scale {     match (equal   greater-than   less-than   not-equal);     value <i>window-scale-factor</i>; } </pre>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Specify the scale factor that the session of the attack will use. The window scale extension expands the definition of the TCP window to 32 bits and then uses a scale factor to carry this 32-bit value in the 16-bit window field of the TCP header.  This statement is supported on SRX-series devices.
<b>Options</b>	<i>match</i> (equal   greater-than   less-than   not-equal)—Match an operand.  <i>value window-scale-factor</i> —Match the number of bytes. <b>Range:</b> 0 through 255
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.

## window-size

---

<b>Syntax</b>	<pre> window-size {     match (equal   greater-than   less-than   not-equal);     value window-size; } </pre>
<b>Hierarchy Level</b>	[edit security idp custom-attack <i>attack-name</i> attack-type signature protocol tcp]
<b>Release Information</b>	Statement introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Specify the number of bytes in the TCP window size.</p> <p>This statement is supported on SRX-series devices.</p>
<b>Options</b>	<p>match (equal   greater-than   less-than   not-equal)—Match an operand.</p> <p>value <i>window-size</i>—Match the number of bytes.</p> <p><b>Range:</b> 0 through 65535</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## winnuke

---

<b>Syntax</b>	winnuke;
<b>Hierarchy Level</b>	[edit security screen ids-option <i>screen-name</i> tcp]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable detection of attacks on Windows NetBios communications. Packets are modified as necessary and passed on. Each WinNuke attack triggers an attack log entry in the event alarm log.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>security—To view this statement in the configuration.</p> <p>security-control—To add this statement to the configuration.</p>

## xauth

---

<b>Syntax</b>	<pre>xauth {     access-profile <i>profile-name</i> ; }</pre>
<b>Hierarchy Level</b>	[edit security ike gateway <i>gateway-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specifies that extended authentication (XAuth) is performed in addition to IKE authentication for remote users trying to access a VPN tunnel. Include a previously created access profile, created with the <b>edit access profile</b> statement, to specify the access profile to be used for authentication information.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<b>access-profile <i>profile-name</i></b> —Name of previously created access profile to reference for authentication information.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	security—To view this statement in the configuration. security-control—To add this statement to the configuration.
<b>Related Topics</b>	profile statement in the <i>JUNOS Systems Basics Configuration Guide</i> .

**zones**

```

Syntax zones {
    functional-zone {
        management {
            host-inbound-traffic {
                protocols {
                    protocol-name ;
                    protocol-name <except>;
                }
                system-services {
                    service-name ;
                    service-name <except>;
                }
            }
        }
        interfaces interface-name {
            host-inbound-traffic {
                protocols {
                    protocol-name ;
                    protocol-name <except>;
                }
                system-services {
                    service-name ;
                    service-name <except>;
                }
            }
        }
        screen screen-name ;
    }
}

security-zone zone-name {
    address-book {
        address address-name ( ip-prefix | dns-name dns-address-name );
        address-set address-set-name {
            address address-name ;
        }
    }
    host-inbound-traffic {
        protocols {
            protocol-name ;
            protocol-name <except>;
        }
        system-services {
            service-name ;
            service-name <except>;
        }
    }
    interfaces interface-name {
        host-inbound-traffic {
            protocols {
                protocol-name ;
                protocol-name <except>;
            }
        }
    }
}

```

```

        system-services {
            service-name ;
            service-name <except>;
        }
    }
}
screen screen-name ;
tcp-rst;
}
}

```

**Hierarchy Level** [edit security]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** A zone is a collection of interfaces for security purposes. All interfaces in a zone are equivalent from a security point of view. Configure the following zones:

- Functional zone—Special-purpose zone like management zone that can host dedicated management interfaces.
- Security zone—Most common type of zone that is used as a building block in policies.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level** security—To view this statement in the configuration.  
security-control—To add this statement to the configuration.



## Chapter 17

# Services Hierarchy

This chapter presents the complete **services** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software.

Use the statements in the **services** configuration hierarchy to configure real-time performance monitoring (RPM) on the J-series device. For configuration instructions, see the *JUNOS Software Administration Guide*.

For information about these **services** statements that are shared across Juniper Networks devices, see the *JUNOS Services Interfaces Configuration Guide*.

This chapter contains the following sections:

- Services Configuration Statement Hierarchy on page 613

## Services Configuration Statement Hierarchy

---

To configure RPM probes, use the following statements at the [edit **services**] hierarchy level.

Shared JUNOS statements in the **services** hierarchy are shown in normal font and are documented in the *JUNOS Services Interfaces Configuration Guide*.

```
services {
  rpm {
    bgp {
      data-fill;
      data-size;
      destination-port;
      history-size;
      logical-system logical-system-name [routing-instances routing-instance-name
    ];
      probe-count count ;
      probe-interval seconds ;
      probe-type type ;
      routing-instances instance-name ;
      test-interval interval ;
    }
    probe owner {
      test test-name {
        data-fill data ;
        data-size size ;
        destination-interface interface-name ;
      }
    }
  }
}
```

```

        destination-port port ;
        dscp-code-point dscp-bits ;
        hardware-timestamp;
        history-size size ;
        probe-count count ;
        probe-interval seconds ;
        probe-type type ;
        routing-instance instance-name ;
        source-address address ;
        target-url ( url | address );
        test-interval interval ;
        thresholds thresholds ;
        traps traps ;
    }
}
probe-limit;
probe-server {
    icmp {
        destination-interface interface-name ;
    }
    tcp {
        destination-interface interface-name ;
        port port-number ;
    }
    udp {
        destination-interface interface-name ;
        port port-number ;
    }
}
}
}

```

## Chapter 18

# SNMP Hierarchy and Statements

This chapter presents the complete **snmp** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **snmp** configuration hierarchy to configure the Simple Network Management Protocol (SNMP) for monitoring device operation and performance. For configuration instructions, see the *JUNOS Software Administration Guide*.

For information about **snmp** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS Network Management Configuration Guide*.

This chapter contains the following sections:

- SNMP Configuration Statement Hierarchy on page 615

## SNMP Configuration Statement Hierarchy

---

To configure SNMP, use the following statements at the [edit **snmp**] hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **snmp** hierarchy are shown in normal font and are documented in the *JUNOS Network Management Configuration Guide*.

```
snmp {
  client-list list-name;
  community community-name {
    authorization (read-only | read-write);
    client-list-name client-list-name;
    clients {
      address < restrict>;
    }
    routing-instances routing-instances {
      client-list-name client-list-name ;
      clients {
        address < restrict>;
      }
    }
  }
}
```

```

    view view-name ;
}
contact contact-information ;
description description ;
engine-id {
    (local engine-id | use-default-ip-address | use-mac-address);
}
filter-duplicates;
health-monitor {
    falling-threshold percentage ;
    interval seconds;
    rising-threshold percentage ;
}
interface [ interface-names ];
location location ;
logical-system-trap-filter;
name system-name ;
nonvolatile {
    commit-delay seconds ;
}
rmon {
    alarm index {
        description description ;
        falling-event-index index ;
        falling-threshold integer ;
        falling-threshold-interval seconds ;
        interval seconds ;
        request-type (get-next-request | get-request | walk-request);
        rising-event-index index ;
        rising-threshold integer ;
        sample-type (absolute-value | delta-value);
        startup-alarm (falling-alarm | rising-alarm | rising-or-falling-alarm);
        syslog-subtag text-string ;
        variable oid-variable ;
    }
    event index {
        community community-name ;
        description description ;
        type (log | log-and-trap | none | snmptrap);
    }
}
routing-instance access {
    access-list {
        routing-instance-name ;
    }
}
traceoptions {
    file filename <files number > <match regular-expression >
    <size maximum-file-size > <world-readable | no-world-readable>;
    flag flag ;
}
trap-group group-name {
    categories {
        authentication;
        chassis;
        configuration;
    }
}

```

```

    link;
    remote-operations;
    rmon-alarm;
    routing;
    services;
    sonet-alarms {
        alarm-name ;
    }
    startup;
    vrrp-events;
}
destination-port port-number ;
routing-instance instance-name ;
targets {
    address ;
}
version (all | v1 | v2);
}
trap-options {
    agent-address outgoing-interface;
    routing-instances instance-name {
        source-address address ;
    }
    source-address address ;
}
v3 {
    notify notify-name {
        tag tag-name ;
        type (inform | trap);
    }
    notify-filter notify-filter-name {
        oid oid-name <exclude | include>;
    }
    snmp-community community-index {
        community-name community-name ;
        context context ;
        security-name security-name ;
        tag tag-name ;
    }
    target-address target-address-name {
        address address ;
        address-mask address-mask ;
        port port-number ;
        retry-count number ;
        routing-instance instance-name ;
        tag-list tag-list ;
        target-parameters parameter-name ;
        timeout seconds ;
    }
    target-parameters target-parameters-name {
        notify-filter notify-filter-name ;{
            parameters {
                message-processing-model (v1 | v2c | v3);
                security-level (authentication | none | privacy);
                security-model (usm | v1 | v2c);
                security-name security-name ;
            }
        }
    }
}

```

```

    }
  }
  usm {
    local-engine {
      user user-name {
        authentication-md5 {
          authentication-password password ;
        }
        authentication-none;
        authentication-sha {
          authentication-password password ;
        }
        privacy-3des {
          privacy-password password ;
        }
        privacy-aes128 {
          privacy-password password ;
        }
        privacy-des {
          privacy-password password ;
        }
        privacy-none;
      }
    }
    remote-engine {
      user user-name {
        authentication-md5 {
          authentication-password password ;
        }
        authentication-none;
        authentication-sha {
          authentication-password password ;
        }
        privacy-3des {
          privacy-password password ;
        }
        privacy-aes128 {
          privacy-password password ;
        }
        privacy-des {
          privacy-password password ;
        }
        privacy-none;
      }
    }
  }
  vacm {
    access {
      group group-name {
        context-prefix prefix {
          security-model (any | usm | v1 | v2c) {
            security-level (authentication | none | privacy) {
              context-match (exact | prefix);
              notify-view notify-view-name ;
              read-view read-view-name ;
              write-view write-view-name ;
            }
          }
        }
      }
    }
  }
}

```

```

    }
  }
}
default-context-prefix {
  security-model (any | usm | v1 | v2c) {
    security-level (authentication | none | privacy) {
      context-match (exact | prefix);
      notify-view notify-view-name ;
      read-view read-view-name ;
      write-view write-view-name ;
    }
  }
}
}
}
}
security-to-group {
  security-model (usm | v1 | v2c) {
    security-name security-name {
      group group-name ;
    }
  }
}
}
}
}
view view-name {
  oid oid-name {
    <exclude | include>;
  }
}
}
}
}

```

## authorization

---

<b>Syntax</b>	authorization (read-only   read-write);
<b>Hierarchy Level</b>	[edit snmp community <i>community-name</i> ]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Set the access authorization for SNMP Get, GetBulk, GetNext, and Set requests.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>read-write—Enable all requests, including Set requests. You must configure a view to enable Set requests.</p> <p>read-only—Enable Get, GetNext, and GetBulk requests. This is the default option.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	<p>snmp—To view this statement in the configuration.</p> <p>snmp-control—To add this statement to the configuration.</p>

## client-list-name

---

<b>Syntax</b>	client-list-name <i>client-list-name</i> ;
<b>Hierarchy Level</b>	[edit snmp community <i>community-name</i> ]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the name of the list of SNMP network management system (NSM) clients that are authorized to collect information about network operations. You cannot use an SNMP client list and individually configured SNMP clients in the same configuration.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>client-list-name</i> — Name of the client list. Client list is the list of IP address prefixes defined with the <b>prefix-list</b> statement in the policy-options hierarchy.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>snmp—To view this statement in the configuration.</p> <p>snmp-control—To add this statement to the configuration.</p>



## Chapter 19

# System Hierarchy and Statements

This chapter presents the complete **system** configuration hierarchy available on J-series Services Routers and SRX-series services gateways running JUNOS software. Where applicable, the chapter also provides a summary for each statement in the hierarchy that is exclusive to J-series and SRX-series devices. Statement summaries are organized alphabetically.

Use the statements in the **system** configuration hierarchy to configure system management functions, including the device's hostname, address, and domain name; the addresses of the Domain Name System (DNS) servers; user login accounts, including user authentication and the root-level user account; time zones and Network Time Protocol (NTP) properties; and properties of the device's auxiliary and console ports. For configuration instructions, see the *JUNOS Software Security Configuration Guide* and the *JUNOS Software Administration Guide*.

For information about **system** statements that are not explained here—statements that are shared across Juniper Networks devices—see the *JUNOS System Basics Configuration Guide* and the *JUNOS Network Interfaces Configuration Guide*.

This chapter includes the following sections:

- System Configuration Statement Hierarchy on page 621

## System Configuration Statement Hierarchy

---

To configure system properties, use the following statements at the [edit **system**] hierarchy level. Statements exclusively for J-series and SRX-series devices running JUNOS software are shown in bold font and are documented in this chapter.

Shared JUNOS statements in the **system** hierarchy are shown in normal font and are documented in the *JUNOS System Basics Configuration Guide* and the *JUNOS Network Interfaces Configuration Guide*.

```
system {
  accounting {
    destination {
      radius {
        server {
          server-address {
            accounting-port port-number ;
            retry number ;
            secret password ;
          }
        }
      }
    }
  }
}
```

```

        source-address address ;
        timeout seconds ;
    }
}
}
tacplus {
    server server-address {
        port port-number ;
        secret password ;
        single-connection;
        timeout seconds ;
    }
}
}
events [login change-log interactive-commands];
traceoptions {
    file filename <files number > <size maximum-file-size >
    <world-readable | no-world-readable>;
    flag flag ;
}
}
archival {
    configuration {
        archive-sites {
            ftp://< username >:< password >@< host >:< port >/< url-path >;
            scp: // < username >:< password >@< host >:< port >/< url-path >;
        }
        transfer-interval interval ;
        transfer-on-commit;
    }
}
arp {
    aging-timer minutes;
    passive-learning;
}
authentication-order [ authentication-methods ];
autoinstallation {
    configuration-servers url {
        password password ;
    }
    interfaces interface-name {
        bootp;
        rarp;
        slarp;
    }
}
}
backup-router address <destination destination-address>;
building name;
commit synchronize;
(compress-configuration-files | no-compression-configuration-files);
default-address-selection;
diag-port-authentication (encrypted-password "password" | plain-text-password);
domain-name domain-name ;
domain-search [ domain-list ];
dump-device {
    boot-device;
}

```

```

compact-flash;
removable-compact-flash;
usb;
}
encrypt-configuration-files;
host-name hostname;
inet6-backup-router address <destination destination-address >;
internet-options address <destination destination-address >;
internet-options {
    (gre-path-mtu-discovery | no-gre-path-mtu-discovery);
    icmpv4-rate-limit {
        bucket-size seconds ;
        packet-rate packet-rate ;
    }
    icmpv6-rate-limit {
        bucket-size seconds ;
        packet-rate packet-rate ;
    }
    (ipip-path-mtu-discovery | no-ipip-path-mtu-discovery);
    no-tcp-rfc1323;
    no-tcp-rfc1323-paws;
    (path-mtu-discovery | no-path-mtu-discovery);
    source-quench;
    source-port upper-limit < upper-limit >;
    (source-quench | no-source-quench);
    tcp-drop-synfin-set;
}
location {
    altitude feet ;
    building name ;
    country-code code ;
    floor number ;
    hcoord horizontal-coordinate ;
    lata service-area ;
    latitude degrees ;
    longitude degrees ;
    npa-nxx number ;
    postal-code postal-code ;
    rack number ;
    vcoord vertical-coordinate ;
}
login {
    announcement text ;
    class class-name {
        allow-commands " regular-expression ";
        allow-configuration " regular-expression ";
        deny-commands " regular-expression ";
        deny-configuration " regular-expression ";
        idle-timeout minutes ;
        login-alarms;
        login-tip;
        permissions [ permissions ];
    }
    message text ;
    password {
        change-type (set-transitions | character-set);

```

```

        format (md5 | sha1 | des);
        maximum-length length;
        minimum-changes number;
        minimum-length length;
    }
    user username {
        authentication {
            (encrypted-password "password" | plain-text-password);
            ssh-dsa " public-key ";
            ssh-rsa " public-key ";
        }
        class class-name ;
        full-name complete-name ;
        uid uid-value ;
    }
    retry-options {
        backoff-threshold number ;
        backoff-factor seconds ;
        minimum-time seconds ;
        tries-before-disconnect number ;
    }
}
max-configurations-on-flash number ;
mirror-flash-on-disk;
name-server ip-address ;
no-compress-configuration-files;
no-multicast-echo;
no-redirects;
no-saved-core-context;
ntp {
    authentication-key key-number type type value password ;
    boot-server (NTP) address ;
    broadcast < address > <key key-number > <version value > <ttl value >;
    broadcast-client;
    multicast-client < address >;
    peer address <key key-number > <version value > <prefer>;
    server address <key key-number > <version value > <prefer>;
    source-address source-address ;
    trusted-key [ key-numbers ];
}
pic-console-authentication {
    encrypted-password encrypted-password ;
    plain-text-password;
}
ports {
    auxiliary {
        disable;
        insecure;
        type terminal-type ;
    }
    console {
        disable;
        insecure;
        log-out-on-disconnect;
        type terminal-type ;
    }
}

```

```

}
processes {
    audit-process;
    bootp;
    chassis-control (enable | disable) failover failover-option;
    class-of-service (enable | disable) failover failover-option;
    craft-control (enable | disable) failover failover-option;
    dfc-daemon;
    dhcp (enable | disable) failover failover-option;
    dialer-services;
    disk-monitoring (enable | disable) failover failover-option;
    ecc-error-logging (enable | disable) failover failover-option;
    event-processing (enable | disable) failover failover-option;
    firewall (enable | disable) failover failover-option;
    firewall-authentication-service (enable | disable);
    forwarding;
    general-authentication-service {
        (enable | disable);
        traceoptions {
            file filename {
                files number;
                match regular-expression;
                size maximum-file-size;
                <world-readable | no-world-readable>;
            }
            flag flag;
        }
    }
}
ilmi;
inet-process (enable | disable) failover failover-option;
init;
interface-control (enable | disable) failover failover-option;
isdn-signaling;
kernel-replication (enable | disable) failover failover-option;
l2ald-service;
l2tp-service (enable | disable) failover failover-option;
lACP;
link-management (enable | disable) failover failover-option;
logical-system-mux;
mib-process (enable | disable) failover failover-option;
named;
network-security (enable | disable);
ntp (enable | disable) failover failover-option;
periodic-packet-services;
pfe;
pgm (enable | disable) failover failover-option;
pic-services-logging (enable | disable) failover failover-option;
ppp;
pppoe (enable | disable) failover failover-option;
redundancy-device (enable | disable) failover failover-option;
remote-operations (enable | disable) failover failover-option;
routing (enable | disable) failover failover-option;
sampling (enable | disable) failover failover-option;
service-deployment (enable | disable) failover failover-option;
snmp (enable | disable) failover failover-option;
sonet-aps;

```

```

usb-control (enable | disable) failover failover-option;
vrrp;
watchdog (enable | disable) failover failover-option;
wan-acceleration {
  (enable | disable);
  traceoptions {
    file filename {
      files number;
      match regular-expression;
      size maximum-file-size;
      <world-readable | no-world-readable>;
    }
    flag flag;
  }
}
web-management (enable | disable) failover failover-option;
}
radius-options {
  attributes {
    nas-ip-address nas-ip-address ;
  }
}
radius-server server-address {
  accounting-port number ;
  port number ;
  retry number ;
  secret password ;
  source-address source-address ;
  timeout seconds ;
}
root-authentication {
  (encrypted-password " password " | plain-text-password);
  ssh-dsa " public-key ";
  ssh-rsa " public-key ";
}
(saved-core-context | no-saved-core-context);
saved-core-files number;
scripts {
  commit {
    allow-transients;
    file filename .xsl {
      optional;
      refresh;
      refresh-from url ;
      source url ;
    }
    refresh;
    refresh-from url ;
    traceoptions {
      file filename <files number > <size maximum-file-size >
      <world-readable | no-world-readable>;
      flag flag ;
    }
  }
}
load-scripts-from-flash;
op {

```

```

file filename .xsl {
    arguments name {
        description cli-help-text ;
    }
    command filename-alias ;
    description cli-help-text ;
    refresh;
    refresh-from url ;
    source url ;
}
refresh;
refresh-from url ;
traceoptions {
    file filename <files number > <size maximum-file-size >;
    flag flag ;
}
}
}
services {
    dhcp {
        boot-file filename ;
        boot-server ( address | hostname );
        domain-name domain-name ;
        domain-search [ domain-list ];
        default-lease-time seconds;
        maximum-lease-time seconds;
        name-server {
            address ;
        }
        option {
            [ ( id-number option-type option-value ) | ( id-number array option-type
              option-values ) ];
        }
        pool {
            subnet-address ( address/netmask ) {
                address-range {
                    high address;
                    low address;
                }
                exclude-address {
                    address ;
                }
            }
        }
        propagate-settings propagate-settings;
    }
    propagate-settings propagate-settings;
    router {
        address ;
    }
    static-binding MAC-address {
        fixed-address {
            address ;
        }
        host hostname ;
        client-identifier (ascii client-id | hexadecimal client-id);
    }
}

```

```

server-identifier address ;
wins-server {
    address;
}
}
dns-proxy {
    cache hostname inet ip-address;
    interface interface-name;
    server-select name {
        domain-name domain-name;
        name-server ip-address;
    }
    traceoptions {
        file filename {
            <files number>;
            <match regular-expression>;
            <size maximum-file-size>;
            <world-readable | no-world-readable>;
        }
        flag flag;
    }
}
dynamic-dns {
    client hostname {
        agent agent-name;
        interface interface-name;
        password password;
        server (dyndns | ddo);
        username username;
    }
}
finger {
    <connection-limit limit >;
    <rate-limit limit >;
}
ftp {
    <connection-limit limit >;
    <rate-limit limit >;
}
netconf {
    ssh {
        <connection-limit number >;
        <rate-limit number >;
    }
}
outbound-ssh {
    application-id application-id {
        device-id device-id ;
        ip-address {
            port port-number ;
            retry number ;
            timeout value ;
        }
        keep-alive number ;
        reconnect-strategy (in-order | sticky);
    }
}

```



```

        secret secret ;
        services {
            netconf;
        }
    }
    traceoptions {
        file filename {
            <files number> ;
            <match regular-expression>;
            <size maximum-file-size>;
            <world-readable | no-world-readable>;
        }
        flag flag ;
    }
}
service-deployment {
    local-certificate certificate-name ;
    servers server-address {
        port-number port-number ;
    }
    source-address source-address ;
    traceoptions {
        flag flag ;
    }
}
ssh {
    <connection-limit limit>;
    protocol-version [v1 v2];
    <rate-limit limit>;
    root-login (allow | deny | deny-password);
}
telnet {
    <connection-limit limit>;
    <rate-limit limit>;
}
web-management {
    http {
        interface [ interface-name s];
        port port ;
    }
    https {
        interface [ interface-names ];
        local-certificate name ;
        pki-local-certificate name;
        port port ;
        system-generated-certificate;
    }
    session {
        idle-timeout [ minutes ];
        session-limit [ session-limit ];
    }
}
xnm-clear-text {
    connection-limit limit ;
    rate-limit limit ;
}

```

```

    xnm-ssl {
        connection-limit limit ;
        local-certificate name ;
        rate-limit limit ;
    }
}
static-host-mapping hostname {
    alias [ alias ];
    inet [ address ];
    inet6 [ address ];
    sysid system-identifier ;
}
syslog {
    archive {
        archive-sites url;
        <files number >;
        <size maximum-file-size >;
        <world-readable | no-world-readable>;
    }
    console {
        facility severity ;
    }
    file filename {
        facility severity ;
        explicit-priority;
        match " regular-expression ";
        archive {
            files number ;
            size maximum-file-size ;
            start-time;
            transfer-interval;
            <world-readable | no-world-readable>;
        }
    }
}
host ( hostname | other-routing-engine | scc-master) {
    any;
    authorization;
    change-log;
    conflict-log;
    daemon;
    dfc;
    external;
    firewall;
    ftp;
    interactive-commands;
    kernel;
    pfe;
    user;
    explicit-priority;
    facility-override facility ;
    log-prefix string ;
    match " regular-expression ";
}
source-address source-address {
    archive;
    console;
}

```

```
file;
host;
time-format;
user;
}
time-format (year | millisecond | year millisecond);
user ( username | *) {
    match < regular-expression >;
}
}
tacplus-options service-name service-name ;
tacplus-server server-address {
    port port-number;
    secret password ;
    single-connection;
    source-address source-address ;
    timeout seconds ;
}
time-zone (GMT hour-offset | time-zone );
}
```

**cache**

---

<b>Syntax</b>	cache hostname inet ip-address ;
<b>Hierarchy Level</b>	[edit system services dns-proxy]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Specify the hostname and IPV4 address for each resolved Domain Name System (DNS) query.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>hostname — Name of the host for which the IP address is resolved.</p> <p>inet ip-address —IPV4 address of the corresponding host name.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## client

---

**Syntax**    client *hostname* {  
               agent *agent-name* ;  
               interface *interface-name* ;  
               password *password* ;  
               server (dyndns | ddo);  
               username *username* ;  
               }

**Hierarchy Level**    [edit system services dynamic-dns]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Configure the dynamic DNS clients.

This statement is supported on J-series and SRX-series devices.

**Options**    *hostname* —Host name for the DNS query form the client.

*agent agent-name* —String the user decides to name the client being created.

*interface interface-name* —Interface whose IP address is monitored by the Dynamic DNS client.

*password password* —Specify a password for the URL.

*server*—Dynamic DNS server that is servicing this client or URL.

■ *dyndns*—Use the dynamic DNS server <http://www.dyndns.org>.

*username username* —Login details of the user.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Administration Guide*.

**Required Privilege Level**    system—To view this statement in the configuration.  
                                   system-control—To add this statement to the configuration.

**dns-proxy**

---

**Syntax**

```

dns-proxy {
  cache hostname inet ip-address ;
  interface interface-name ;
  server-select name {
    domain-name domain-name ;
    name-server ip-address ;
  }
  traceoptions {
    file {
      <files number >;
      <match regular-expression >;
      <size maximum-file-size >;
      <world-readable | no-world-readable>;
    }
    flag flag ;
  }
}

```

**Hierarchy Level** [edit system services]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Specify the properties of the server for use as Domain Name System (DNS) proxy by DNS clients.

This statement is supported on J-series and SRX-series devices.

**Options** The remaining statements are explained separately.

**Usage Guidelines** For configuration instructions and examples, see the *JUNOS Software Administration Guide*.

**Required Privilege Level** system—To view this statement in the configuration.  
 system-control—To add this statement to the configuration.

## domain-name

---

<b>Syntax</b>	domain-name <i>domain-name</i> ;
<b>Hierarchy Level</b>	[edit system services dns-proxy server-select]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the domain name of associated name servers for the DNS queries.  This statement is supported on J-series and SRX-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## dynamic-dns

---

<b>Syntax</b>	dynamic-dns { client <i>hostname</i> { agent <i>agent-name</i> ; interface <i>interface-name</i> ; password <i>password</i> ; server (dyndns   ddo); username <i>username</i> ; } }
<b>Hierarchy Level</b>	[edit system services]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Configure dynamic Domain Name System (DNS) clients.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	The remaining statements are explained separately.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

**firewall-authentication-service**

---

<b>Syntax</b>	firewall-authentication-service (enable   disable);
<b>Hierarchy Level</b>	[edit system processes]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable or disable the firewall authentication service process.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>enable—Start the firewall authentication service process.</p> <p>disable—Stop the firewall authentication service process.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>

## general-authentication-service

---

**Syntax**    general-authentication-service {  
               (enable | disable);  
               traceoptions {  
                   file *filename* {  
                       <files *number* >;  
                       <match *regular-expression*>;  
                       <size *maximum-file-size*>;  
                       <world-readable | no-world-readable>;  
                   }  
               flag *flag* ;  
               }  
           }

**Hierarchy Level**    [edit system processes]

**Release Information**    Statement introduced in Release 8.5 of JUNOS software.

**Description**    Enable or disable the general authentication process.

This statement is supported on J-series and SRX-series devices.

**Options**    enable—Start the general authentication service process.

disable—Stop the general authentication service process.

The remaining statements are explained separately.

**Usage Guidelines**    For configuration instructions and examples, see the *JUNOS Software Security Configuration Guide*.

**Required Privilege Level**    system—To view this statement in the configuration.  
                                   system-control—To add this statement to the configuration.



## interface

---

<b>Syntax</b>	<code>interface <i>interface-name</i> ;</code>
<b>Hierarchy Level</b>	[edit system services dns-proxy]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the interface on the device to associate with the Domain Name System (DNS), else all the DNS queries received on that interface are dropped.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>interface-name</i> —Name of the interface.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## name-server

---

<b>Syntax</b>	<code>name-server <i>ip-address</i> ;</code>
<b>Hierarchy Level</b>	[edit system services dns-proxy server-select]
<b>Release Information</b>	Statement modified in Release 8.5 of JUNOS software.
<b>Description</b>	Specify the IP address of the servers for resolving a particular domain name.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	<i>ip-address</i> —Specify the IP address of the preferred server.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## network-security

---

<b>Syntax</b>	network-security (enable   disable);
<b>Hierarchy Level</b>	[edit system processes]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable or disable the network security process on the device.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>enable—Start the network security process.</p> <p>disable—Stop the network security process.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>

## pki-local-certificate

---

<b>Syntax</b>	pki-local-certificate <i>name</i> ;
<b>Hierarchy Level</b>	[edit system services web-management https]
<b>Release Information</b>	Statement introduced in Release 9.1 of JUNOS software.
<b>Description</b>	<p>Specify the name of the certificate that is generated by public key infrastructure (PKI) and authenticated by certificate authority (CA).</p> <p>This statement is supported on J-series devices.</p>
<b>Options</b>	<i>name</i> —Name of certificate.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	<p>system—To view this statement in the configuration.</p> <p>system-control—To add this statement to the configuration.</p>

## propagate-settings

---

<b>Syntax</b>	<code>propagate-settings <i>logical-interface-name</i> ;</code>
<b>Hierarchy Level</b>	[edit system services dhcp], [edit system services dhcp pool]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Enable or disable the propagation of TCP/IP settings received on the device acting as Dynamic Host Configuration Protocol (DHCP) client. The settings can be propagated to the server pool running on the device. Use the <b>system services dhcp</b> statement to set this feature globally. Use the <b>system services dhcp pool</b> statement to set the feature for the address pool and override the global setting.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<i>logical-interface-name</i> —Name of the logical interface to receive TCP/IP settings from the external network for propagation to the DHCP pool running on the device.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## server-select

---

<b>Syntax</b>	<pre>server-select <i>name</i> {     domain-name <i>domain-name</i> ;     name-server <i>ip-address</i> ; }</pre>
<b>Hierarchy Level</b>	[edit system services dns-proxy]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Configure the Domain Name System (DNS) proxy server.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>domain-name</b> <i>domain-name</i> —Name of the domain.</p> <p><b>name-server</b> <i>ip-address</i> —DNS server's IPv4 address.</p>
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Administration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## system-generated-certificate

---

<b>Syntax</b>	system-generated-certificate;
<b>Hierarchy Level</b>	[edit system services web-management https]
<b>Description</b>	Automatically generated self-signed certificate  This statement is supported on J-series devices.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>JUNOS Software Security Configuration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.

## **traceoptions**

---

See the following sections:

- `traceoptions` (DNS Proxy) on page 642
- `traceoptions` (General Authentication Service) on page 644
- `traceoptions` (WAN Acceleration) on page 646

**traceoptions (DNS Proxy)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number*> ;  
         <match *regular-expression*> ;  
         <size *maximum-file-size*> ;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit system services dns-proxy]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure DNS proxy tracing options.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

files *number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1* , and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The **world-readable** option enables any user to read the file. To explicitly set the default behavior, use the **no-world-readable** option.

**flag** *flag* —Tracing operation to perform. To specify more than one tracing operation, include multiple **flag** statements. You can include the following flags.

- **all**—Trace everything in DNS
  - **critical**—Trace critical events
  - **error**—Trace errors
  - **events**—Trace events
  - **info**—Trace information
  - **memory**—Trace memory allocation/deallocation
  - **packets**—Trace incoming & outgoing packets
  - **parse**—Trace parse events
  - **route-socket**—Trace routing socket events

**Required Privilege Level** **trace**—To view this statement in the configuration.  
**trace-control**—To add this statement to the configuration.

**traceoptions (General Authentication Service)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number*>;  
         <match *regular-expression*>;  
         <size *maximum-file-size*>;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit system processes general-authentication-service]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure tracing operations for general-authentication-service processes.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

files *number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1* , and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option enables any user to read the file. To explicitly set the default behavior, use the *no-world-readable* option.



**flag** *flag* —Tracing operation to perform. To specify more than one tracing operation, include multiple **flag** statements. You can include the following flags.

- **all** —Trace with all flags enabled
  - **configuration** —Trace configuration events
  - **framework**—Trace authentication framework events
  - **ldap** —Trace ldap authentication events
  - **local-authentication**—Trace local authentication events
  - **radius** —Trace radius authentication events

**Required Privilege Level** **trace**—To view this statement in the configuration.  
**trace-control**—To add this statement to the configuration.

**traceoptions (WAN Acceleration)**

**Syntax** traceoptions {  
     file *filename* {  
         <files *number*> ;  
         <match *regular-expression*>;  
         <size *maximum-file-size*>;  
         <world-readable | no-world-readable>;  
     }  
     flag *flag* ;  
 }

**Hierarchy Level** [edit system processes wan-acceleration]

**Release Information** Statement introduced in Release 8.5 of JUNOS software.

**Description** Configure tracing operations for WXC Integrated Services Module (ISM 200) processes.

This statement is supported on J-series and SRX-series devices.

**Options** file *filename* —By default, the name of the log file that records trace output is the name of the process being traced. Use this option to specify another name.

files *number* —(Optional) Specify the maximum number of trace files. When a trace file named *trace-file* reaches its maximum size, it is renamed to *trace-file .0*, then *trace-file.1* , and so on, until the maximum number of trace files is reached. The oldest archived file is overwritten.

If you specify a maximum number of files, you also must specify a maximum file size with the size option and a filename.

**Range:** 2 through 1000 files

**Default:** 10 files

match *regular-expression* —(Optional) Refine the output to include lines that contain the regular expression.

size *maximum-file-size* —(Optional) Maximum size of each trace file, in kilobytes (KB), megabytes (MB), or gigabytes (GB). When a trace file named *trace-file* reaches this size, it is renamed *trace-file .0*. When the *trace-file* again reaches its maximum size, *trace-file .0* is renamed *trace-file .1* and *trace-file* is renamed *trace-file .0*. This renaming scheme continues until the maximum number of trace files is reached. Then the oldest trace file is overwritten.

If you specify a maximum file size, you also must specify a maximum number of trace files with the files option and filename.

**Syntax:** x k to specify KB, x m to specify MB, or x g to specify GB

**Range:** 10 KB through 1 GB

**Default:** 128 KB

world-readable | no-world-readable—(Optional) By default, log files can be accessed only by the user who configures the tracing operation. The *world-readable* option enables any user to read the file. To explicitly set the default behavior, use the *no-world-readable* option.

**flag** *flag* —Tracing operation to perform. To specify more than one tracing operation, include multiple **flag** statements. You can include the following flags.

- **all**—Trace all options
  - **configuration** — Trace configuration events
  - **fpc-ipc**—Trace FPC interprocess communication messages
  - **fpc-ipc-heart-beat**—Trace FPC interprocess heart beat messages
  - **memory**—Trace memory allocation or deallocation messages
  - **ssam**—Trace state synchronization and management events
  - **wx-login**—Trace WXC ISM200 login events

<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>WXC Integrated Services Module Installation and Configuration Guide</i> .
<b>Required Privilege Level</b>	trace—To view this statement in the configuration. trace-control—To add this statement to the configuration.

wan-acceleration

---

<b>Syntax</b>	wan-acceleration (enable   disable);
<b>Hierarchy Level</b>	[edit system processes]
<b>Release Information</b>	Statement introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Enable or disable the WXC Integrated Services Module (ISM 200) for WAN acceleration.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	enable—Turn on the WXC ISM200.  disable—Turn off the WXC ISM200.
<b>Usage Guidelines</b>	For configuration instructions and examples, see the <i>WXC Integrated Services Module Installation and Configuration Guide</i> .
<b>Required Privilege Level</b>	system—To view this statement in the configuration. system-control—To add this statement to the configuration.



## **Part 2**

# **Operational Commands**

- Clear Commands on page 651
- Request Commands on page 711
- Restart Commands on page 725
- Show Commands on page 727



## Chapter 20

# Clear Commands

This chapter presents the **clear** operational commands available on J-series Services Routers and SRX-series services gateways running JUNOS software. Use the **clear** operational commands to clear software processes on the device. Operational commands are organized alphabetically.

The commands shown in this chapter are exclusive to J-series and SRX-series devices. For information about **clear** commands that are not explained here—commands that are shared across Juniper Networks devices—see the *JUNOS System Basics and Services Command Reference*.

## clear chassis cluster control-plane statistics

---

<b>Syntax</b>	clear chassis cluster control-plane statistics
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Clear the control plane statistics of a chassis cluster.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show chassis cluster control-plane statistics on page 732
<b>List of Sample Output</b>	clear chassis cluster control-plane statistics on page 652
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear chassis cluster control-plane statistics</b>	<pre>user@host&gt; clear chassis cluster control-plane statistics Cleared control-plane statistics</pre>



## clear chassis cluster data-plane statistics

---

<b>Syntax</b>	clear chassis cluster data-plane statistics
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Clear the data plane statistics of a chassis cluster.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show chassis cluster data-plane statistics on page 733
<b>List of Sample Output</b>	clear chassis cluster data-plane statistics on page 653
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear chassis cluster data-plane statistics</b>	<pre>user@host&gt; clear chassis cluster data-plane statistics</pre> <p>Cleared data-plane statistics</p>

## clear chassis cluster failover-count

---

<b>Syntax</b>	clear chassis cluster failover-count
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Clear the failover count of a chassis cluster.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>request chassis cluster failover node on page 712</p> <p>request chassis cluster failover reset on page 713</p> <p>show chassis cluster status on page 739</p>
<b>List of Sample Output</b>	clear chassis cluster failover-count on page 654
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear chassis cluster failover-count</b>	<pre>user@host&gt; clear chassis cluster failover-count Cleared failover-count for all redundancy-groups</pre>

## clear chassis cluster statistics

---

<b>Syntax</b>	clear chassis cluster statistics
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Clear the control plane and data plane statistics of a chassis cluster.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show chassis cluster statistics on page 736
<b>List of Sample Output</b>	clear chassis cluster statistics on page 655
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear chassis cluster statistics</b>	<pre>user@host&gt; clear chassis cluster statistics Cleared control-plane statistics Cleared data-plane statistics</pre>

## clear network-access requests pending

---

<b>Syntax</b>	clear network-access requests pending <index <i>index-number</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Clear or cancel all pending authentication requests.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Clear all network access requests pending.  index <i>index-number</i> —Clear the specified authentication request. To display index numbers, use the <code>show network-access requests pending</code> command.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show network-access requests pending on page 757
<b>List of Sample Output</b>	clear network-access requests pending on page 656
<b>Output Fields</b>	This command produces no output.

The following example displays the network access requests that are pending, clears the requests, and displays the results of the clear operation:

```
clear network-access requests pending
user@host> show network-access requests pending
Information about pending authentication entries
  Total pending authentication requests: 2
Index User                Status
 1    Sun                  Processing
 2    Sam                  Processed
user@host> clear network-access requests pending
user@host> show network-access requests pending
Information about pending authentication entries
  Total pending authentication requests: 2
Index User                Status
 1    Sun                  Cancelled by Admin
 2    Sam                  Cancelled by Admin
```

## clear network-access requests statistics

---

<b>Syntax</b>	clear network-access requests statistics
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Clear general authentication statistics for the configured authentication type.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>authentication-order</p> <p>show network-access requests statistics on page 759</p>
<b>List of Sample Output</b>	clear network-access requests statistics on page 657
<b>Output Fields</b>	This command produces no output.
<b>clear network-access requests statistics</b>	<pre>user@host&gt; clear network-access requests statistics</pre>

## **clear network-access securid-node-secret-file**

---

<b>Syntax</b>	clear network-access securid-node-secret-file
<b>Release Information</b>	Command introduced in Release 9.1 of JUNOS software.
<b>Description</b>	Delete the node secret file for the SecurID authentication type.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	configuration-file  securid-server  show network-access securid-node-secret-file on page 760
<b>List of Sample Output</b>	clear network-access securid-node-secret-file on page 658
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear network-access securid-node-secret-file</b>	user@host> <b>clear network-access securid-node-secret-file</b>

## clear security alg h323 counters

---

<b>Syntax</b>	clear security alg h323 counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear information about H.323 Application Layer Gateway (ALG) counters.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Clear H.323 ALG counters.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear H.323 counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>h323</p> <p>show security alg h323 counters on page 763</p>
<b>List of Sample Output</b>	clear security alg h323 counters on page 659
<b>Output Fields</b>	This command produces no output.
<b>clear security alg h323 counters</b>	user@host> clear security alg h323 counters

## clear security alg mgcp calls

---

<b>Syntax</b>	clear security alg mgcp calls <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear information about Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG) calls.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Clear all MGCP ALG calls.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear MGCP calls on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>mgcp</p> <p>show security alg mgcp calls on page 765</p>
<b>List of Sample Output</b>	clear security alg mgcp calls on page 660
<b>Output Fields</b>	This command produces no output.
<b>clear security alg mgcp calls</b>	user@host> clear security alg mgcp calls



## clear security alg mgcp counters

---

<b>Syntax</b>	clear security alg mgcp counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG) counter information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Clear all MGCP ALG counters.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear MGCP counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>mgcp</p> <p>show security alg mgcp counters on page 767</p>
<b>List of Sample Output</b>	clear security alg mgcp counters on page 661
<b>Output Fields</b>	This command produces no output.
<b>clear security alg mgcp counters</b>	user@host> clear security alg mgcp counters

## clear security alg msrpc portmap

---

<b>Syntax</b>	clear security alg msrpc portmap
<b>Release Information</b>	Command introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Clear information about Microsoft's implementation of the remote procedure call (MSRPC) mapping table.</p> <p>This command is supported on J-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>msrpc</p> <p>show security alg msrpc on page 771</p>
<b>List of Sample Output</b>	clear security alg msrpc portmap on page 662
<b>Output Fields</b>	This command produces no output.
<b>clear security alg msrpc portmap</b>	<pre>user@host&gt; clear security alg msrpc portmap</pre>

## clear security alg sccp calls

---

<b>Syntax</b>	clear security alg sccp calls <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear Skinny Client Protocol (SCCP) Application Layer Gateway (ALG) call information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Clear all SCCP ALG calls.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear SCCP calls on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>sccp</p> <p>show security alg sccp calls on page 773</p>
<b>List of Sample Output</b>	clear security alg sccp calls on page 663
<b>Output Fields</b>	This command produces no output.
<b>clear security alg sccp calls</b>	user@host> clear security alg sccp calls

## clear security alg sccp counters

---

<b>Syntax</b>	clear security alg sccp counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear Skinny Client Control Protocol (SCCP) Application Layer Gateway (ALG) counters.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Clear all SCCP ALG counters.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear SCCP counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>sccp</p> <p>show security alg sccp counters on page 775</p>
<b>List of Sample Output</b>	clear security alg sccp counters on page 664
<b>Output Fields</b>	This command produces no output.
<b>clear security alg sccp counters</b>	user@host> clear security alg sccp counters

## clear security alg sip calls

---

<b>Syntax</b>	clear security alg sip calls <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear Session Initiation Protocol (SIP) Application Layer Gateway (ALG) call information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Clear all SIP ALG calls.</p> <p><b>node</b>—(Optional) For chassis cluster configuration, clear SIP calls on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>sip</p> <p>show security alg sip calls on page 777</p>
<b>List of Sample Output</b>	clear security alg sip calls on page 665
<b>Output Fields</b>	This command produces no output.
<b>clear security alg sip calls</b>	user@host> clear security alg sip calls

## clear security alg sip counters

---

<b>Syntax</b>	clear security alg sip counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear Session Initiation Protocol (SIP) Application Layer Gateway (ALG) counters.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Clear all SIP ALG counters.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear SIP counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>sip</p> <p>show security alg sip counters on page 780</p>
<b>List of Sample Output</b>	clear security alg sip counters on page 666
<b>Output Fields</b>	This command produces no output.
<b>clear security alg sip counters</b>	user@host> clear security alg sip counters

## **clear security alg sunrpc portmap**

---

<b>Syntax</b>	clear security alg sunrpc portmap
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Clear Sun Microsystem remote procedure call (SUNRPC) mapping table information.</p> <p>This command is supported on J-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>sunrpc</p> <p>show security alg sunrpc portmap on page 787</p>
<b>List of Sample Output</b>	clear security alg sunrpc portmap on page 667
<b>Output Fields</b>	This command produces no output.
<b>clear security alg sunrpc portmap</b>	<pre>user@host&gt; clear security alg sunrpc portmap</pre>

## clear security firewall-authentication history

---

<b>Syntax</b>	clear security firewall-authentication history <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear all firewall authentication history information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<b>node</b> —(Optional) For chassis cluster configurations, clear all firewall authentication history on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	firewall-authentication (Security)  show security firewall-authentication history on page 788
<b>List of Sample Output</b>	clear security firewall-authentication history on page 668 clear security firewall-authentication history node 1 on page 668
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security firewall-authentication history</b>	<pre> user@host&gt; clear security firewall-authentication history node0: ----- node1: -----           </pre>
<b>clear security firewall-authentication history node 1</b>	<pre> user@host&gt; clear security firewall-authentication history node 1 node1: -----           </pre>



## clear security firewall-authentication history address

---

<b>Syntax</b>	clear security firewall-authentication history address <i>address</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear firewall authentication history for this source IP address.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><b>address</b> <i>address</i> —Source IP address for which to clear firewall authentication history.</p> <p><b>none</b>—Clear all firewall authentication history for this address.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear firewall authentication history for this address on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>firewall-authentication (Security)</p> <p>show security firewall-authentication history address on page 790</p>
<b>List of Sample Output</b>	<p>clear security firewall-authentication history address 100.0.0.1 on page 669</p> <p>clear security firewall-authentication history address 100.0.0.1 node 1 on page 669</p>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security firewall-authentication history address 100.0.0.1</b>	<pre>user@host&gt; clear security firewall-authentication history address 100.0.0.1 node0: ----- node1: -----</pre>
<b>clear security firewall-authentication history address 100.0.0.1 node 1</b>	<pre>user@host&gt; clear security firewall-authentication history address 100.0.0.1 node 1 node1: -----</pre>

## clear security firewall-authentication history identifier

---

<b>Syntax</b>	clear security firewall-authentication history identifier <i>identifier</i> <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; node options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear firewall authentication history information for the authentication with this identifier.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>identifier <i>identifier</i> —Identification number of the authentication for which to clear authentication history.</p> <p>none—Clear all firewall authentication history information for the authentication with this identifier.</p> <p>node—(Optional) For chassis cluster configurations, clear firewall authentication history on a specific node for the authentication with this identifier.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>firewall-authentication (Security)</p> <p>show security firewall-authentication history identifier on page 793</p>
<b>List of Sample Output</b>	<p>clear security firewall-authentication history identifier 2 on page 670</p> <p>clear security firewall-authentication history identifier 2 node 1 on page 670</p>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security firewall-authentication history identifier 2</b>	<pre> user@host&gt; clear security firewall-authentication history identifier 2 node0: ----- node1: ----- </pre>
<b>clear security firewall-authentication history identifier 2 node 1</b>	<pre> user@host&gt; clear security firewall-authentication history identifier 2 node 1 node1: ----- </pre>

## clear security firewall-authentication users

---

<b>Syntax</b>	clear security firewall-authentication users <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear firewall authentication tables for all users.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<b>node</b> —(Optional) For chassis cluster configurations, clear firewall authentication details for all users on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security firewall-authentication users on page 796
<b>List of Sample Output</b>	clear security firewall-authentication users on page 671 clear security firewall-authentication users node 1 on page 671
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security firewall-authentication users</b>	<pre> user@host&gt; clear security firewall-authentication users node 1 node0: ----- node1: ----- </pre>
<b>clear security firewall-authentication users node 1</b>	<pre> user@host&gt; clear security firewall-authentication users node 1 node1: ----- </pre>

## clear security firewall-authentication users address

---

<b>Syntax</b>	clear security firewall-authentication users address <i>address</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <i>node</i> options added in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Clear information about the users at the specified IP address that are currently authenticated.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>address</b> <i>address</i> —IP address for which to clear user firewall authentication information.</p> <p><b>none</b>—Clear all the firewall authentication information for users at this IP address.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear user firewall authentication entries on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security firewall-authentication users address on page 798
<b>List of Sample Output</b>	<p>clear security firewall-authentication users address 100.0.0.1 on page 672</p> <p>clear security firewall-authentication users address 100.0.0.1 node 1 on page 672</p>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security firewall-authentication users address 100.0.0.1</b>	<pre>user@host&gt; clear security firewall-authentication users address 100.0.0.1 node0: ----- node1: -----</pre>
<b>clear security firewall-authentication users address 100.0.0.1 node 1</b>	<pre>user@host&gt; clear security firewall-authentication users address 100.0.0.1 node 1 node1: -----</pre>

## clear security firewall-authentication users identifier

---

<b>Syntax</b>	clear security firewall-authentication users identifier <i>identifier</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear firewall authentication details about the user with this identification number.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Identification number of the user for which to clear authentication details.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear the firewall authentication details on a specific node (device) in the cluster for the user with this identification number.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security firewall-authentication users identifier on page 800
<b>List of Sample Output</b>	clear security firewall-authentication users identifier 2 on page 673 clear security firewall-authentication users identifier 2 node 1 on page 673
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security firewall-authentication users identifier 2</b>	<pre> user@host&gt; clear security firewall-authentication users identifier 2 node0: ----- node1: ----- </pre>
<b>clear security firewall-authentication users identifier 2 node 1</b>	<pre> user@host&gt; clear security firewall-authentication users identifier 2 node 1 node1: ----- </pre>

## clear security flow session all

---

<b>Syntax</b>	clear security flow session all <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear all currently active security sessions on the device.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<b>node</b> —(Optional) For chassis cluster configurations, clear all security sessions on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session on page 805
<b>List of Sample Output</b>	clear security flow session all on page 674 clear security flow session all node 0 on page 674
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session all</b>	<pre> user@host&gt; clear security flow session all node0: ----- 1 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session all node 0</b>	<pre> user@host&gt; clear security flow session all node 0 node0: ----- 0 active sessions cleared </pre>

## clear security flow session application

---

**Syntax** clear security flow session application  
*application-name*  
 <node ( *node-id* | all | local | primary)>

**Release Information** Command introduced in Release 8.5 of JUNOS software; **node** options added in Release 9.0 of JUNOS software.

**Description** Clear currently active sessions for application types or application sets.

This command is supported on J-series and SRX-series devices.

**Options** *application-name* —Name of the specified application type or application set.

- dns—Domain Name System
- ftp—File Transfer Protocol
- ignore—Ignore application type
- mgcp-ca—Media Gateway Control Protocol with Call Agent
- mgcp-ua—MGCP with User Agent
- ms-rpc—Microsoft RPC
- pptp—Point-to-Point Tunneling Protocol
- q931—ISDN connection control protocol
- ras—RAS
- realaudio—RealAudio
- rsh—UNIX remote shell services
- rtsp—Real-Time Streaming Protocol
- sccp—Skinny Client Control Protocol
- sip—Session Initiation Protocol
- sqlnet-v2—Oracle SQLNET
- sun-rpc—Sun Microsystems RPC
- talk—TALK program
- tftp—Trivial File Transfer Protocol

**node**—(Optional) For chassis cluster configurations, clear sessions for applications on a specific node (device) in the cluster.

- *node-id* —Identification number of the node. It can be 0 or 1.
- all —Clear all nodes.
- local —Clear the local node.
- primary—Clear the primary node.

<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session application on page 807
<b>List of Sample Output</b>	clear security flow session application dns on page 676 clear security flow session application dns node 0 on page 676
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session application dns</b>	<pre>user@host&gt; clear security flow session application dns node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared</pre>
<b>clear security flow session application dns node 0</b>	<pre>user@host&gt; clear security flow session application dns node 0 node0: ----- 0 active sessions cleared</pre>



## clear security flow session destination-port

---

<b>Syntax</b>	clear security flow session destination-port <i>destination-port-number</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear each session that uses the specified destination port  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>destination-port-number</i> —Number of the destination port.  <b>node</b> —(Optional) For chassis cluster configurations, clear security sessions on the port on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session destination-port on page 809
<b>List of Sample Output</b>	clear security flow session destination-port 1 on page 677 clear security flow session destination-port 1 node 0 on page 677
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session destination-port 1</b>	<pre> user@host&gt; clear security flow session destination-port 1 node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session destination-port 1 node 0</b>	<pre> user@host&gt; clear security flow session destination-port 1 node 0 node0: ----- 0 active sessions cleared </pre>

## clear security flow session destination-prefix

---

<b>Syntax</b>	clear security flow session destination-prefix <i>destination-IP-prefix</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear sessions that match this destination IPv4 prefix or address.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>destination-IP-prefix</i> —Destination IPv4 prefix or address.  <b>node</b> —(Optional) For chassis cluster configurations, clear sessions that match the IPv4 prefix or address on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session destination-prefix on page 811
<b>List of Sample Output</b>	clear security flow session destination-prefix 100.0.0.1 on page 678 Clear security flow session destination-prefix 100.0.0.1 node 0 on page 678
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session destination-prefix 100.0.0.1</b>	<pre> user@host&gt; clear security flow session destination-prefix 100.0.0.1 node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>Clear security flow session destination-prefix 100.0.0.1 node 0</b>	<pre> user@host&gt; clear security flow session destination-prefix 100.0.0.1 node 0 node0: ----- 0 active sessions cleared </pre>

## clear security flow session interface

---

<b>Syntax</b>	clear security flow session interface <i>interface-name</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear sessions that use the specified interface.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>interface-name</i> —Name of a specific incoming or outgoing interface.  <b>node</b> —(Optional) For chassis cluster configurations, clear security sessions on the interface on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session interface on page 813
<b>List of Sample Output</b>	clear security flow session interface ge-0/0/0.0 on page 679 clear security flow session interface ge/0/0.0 node 0 on page 679
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session interface ge-0/0/0.0</b>	<pre> user@host&gt; clear security flow session interface ge-0/0/0.0 node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session interface ge/0/0.0 node 0</b>	<pre> user@host&gt; clear security flow session interface ge-0/0/0.0 node 0 node0: ----- 0 active sessions cleared </pre>

## clear security flow session protocol

---

**Syntax** clear security flow session protocol *protocol-name* | *protocol-number*  
<node ( *node-id* | all | local | primary)>

**Release Information** Command introduced in Release 8.5 of JUNOS software; **node** options added in Release 9.0 of JUNOS software.

**Description** Clear each session that uses the specified IP protocol.

This command is supported on J-series and SRX-series devices.

**Options** *protocol-name* — (Optional) Networking protocol name. The following text values are supported.

- ah—IP Security Authentication Header
- egp—Exterior gateway protocol
- esp—IPsec Encapsulating Security Payload
- gre—Generic routing encapsulation
- icmp—Internet Control Message Protocol
- igmp—Internet Group Management Protocol
- ipip—IP over IP
- ospf—Open Shortest Path First
- pim—Protocol Independent Multicast
- rsvp—Resource Reservation Protocol
- sctp—Stream Control Transmission Protocol
- tcp—Transmission Control Protocol
- udp—User Datagram Protocol

*protocol-number* —(Optional) Numeric protocol value. For a complete list of possible numeric values, see RFC 1700, *Assigned Numbers (for the Internet Protocol Suite)*.

**Range:** 0 through 255

**node**—(Optional) For chassis cluster configurations, clear security on a specific node (device) in the cluster for the user with this identification number.

- *node-id* —Identification number of the node. It can be 0 or 1.
- all —Clear all nodes.
- local —Clear the local node.
- primary—Clear the primary node.

**Required Privilege Level** clear

<b>Related Topics</b>	show security flow session protocol on page 815
<b>List of Sample Output</b>	clear security flow session protocol pim on page 681 clear security flow session protocol 0 on page 681
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session protocol pim</b>	<pre> user@host&gt; clear security flow session protocol pim node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session protocol 0</b>	<pre> user@host&gt; clear security flow session protocol 0 node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>

## clear security flow session resource-manager

---

<b>Syntax</b>	clear security flow session resource-manager <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear resource-manager sessions.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<b>node</b> —(Optional) For chassis cluster configurations, clear the resource manager sessions on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session resource-manager on page 818
<b>List of Sample Output</b>	clear security flow session resource-manager on page 682 clear security flow session resource-manager node 0 on page 682
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session resource-manager</b>	<pre> user@host&gt; clear security flow session resource-manager node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session resource-manager node 0</b>	<pre> user@host&gt; clear security flow session resource-manager node 0 node0: ----- 0 active sessions cleared </pre>

## clear security flow session session-identifier

---

<b>Syntax</b>	clear security flow session session-identifier session-identifier <node ( node-id   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; node options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear the session with the specific identifier.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>session-identifier —Number from 1 through 4294967295 that identifies the security session.</p> <p>node—(Optional) For chassis cluster configurations, clear the specified session on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ node-id—Identification number of the node. It can be 0 or 1.</li> <li>■ all—Clear all nodes.</li> <li>■ local—Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session session-identifier on page 820
<b>List of Sample Output</b>	clear security flow session session-identifier 1 on page 683 clear security flow session session-identifier 1 node 0 on page 683
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session session-identifier 1</b>	<pre>user@host&gt; clear security flow session session-identifier 1 0 active sessions cleared</pre>
<b>clear security flow session session-identifier 1 node 0</b>	<pre>user@host&gt; clear security flow session session-identifier 1 node 0 node0: ----- 0 active sessions cleared</pre>

## clear security flow session source-port

---

<b>Syntax</b>	clear security flow session source-port <i>source-port-number</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear each session that uses the specified source port.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>source-port-number</i> —Number that identifies the source port.  <b>Range:</b> 1 through 65535  <i>node</i> —(Optional) For chassis cluster configurations, clear sessions on the specified source port on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session source-port on page 824
<b>List of Sample Output</b>	clear security flow session source-port 1 on page 684 clear security flow session source-port 1 node 0 on page 684
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session source-port 1</b>	<pre> user@host&gt; clear security flow session source-port 1 node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session source-port 1 node 0</b>	<pre> user@host&gt; clear security flow session source-port 1 node 0 node0: ----- 0 active sessions cleared </pre>



## clear security flow session source-prefix

---

<b>Syntax</b>	clear security flow session source-prefix source-prefix-number <node ( node-id   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; node options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear sessions that match the source prefix.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>source-prefix-number —Source IPv4 prefix or address.</p> <p>node—(Optional) For chassis cluster configurations, clear security sessions matching the source prefix on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ node-id —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security flow session source-prefix on page 826
<b>List of Sample Output</b>	clear security flow session source-prefix 100.0.0.1 on page 685 clear security flow session source-prefix 100.0.0.1 node 0 on page 685
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security flow session source-prefix 100.0.0.1</b>	<pre> user@host&gt; clear security flow session source-prefix 100.0.0.1 node0: ----- 0 active sessions cleared node1: ----- 0 active sessions cleared </pre>
<b>clear security flow session source-prefix 100.0.0.1 node 0</b>	<pre> user@host&gt; clear security flow session source-prefix 100.0.0.1 node 0 node0: ----- 0 active sessions cleared </pre>

## **clear security idp application-identification application-system-cache**

---

<b>Syntax</b>	clear security idp application-identification application-system-cache
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Clear IDP application system cache.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>application-system-cache</p> <p>show security idp application-identification application-system-cache on page 833</p>
<b>List of Sample Output</b>	clear security idp application-identification application-system-cache on page 686
<b>Output Fields</b>	This command produces no output.
<b>clear security idp application-identification application-system-cache</b>	<pre>user@host&gt; clear security idp application-identification application-system-cache</pre>

## clear security idp attack table

---

<b>Syntax</b>	clear security idp attack table
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Clear details of the IDP attack table.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>attacks</p> <p>show security idp attack table on page 834</p>
<b>List of Sample Output</b>	clear security idp attack table on page 687
<b>Output Fields</b>	This command produces no output.
<b>clear security idp attack table</b>	user@host> <b>clear security idp attack table</b>

## clear security idp counters application-identification

---

<b>Syntax</b>	clear security idp counters application-identification
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the application identification counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>application-identification</p> <p>show security idp counters application-identification on page 835</p>
<b>List of Sample Output</b>	clear security idp counters application-identification on page 688
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters application-identification</b>	<pre>user@host&gt; clear security idp counters application-identification clear_counter_class: counters cleared, status = 0</pre>

## **clear security idp counters dfa**

---

<b>Syntax</b>	clear security idp counters dfa
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the DFA counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security idp counters dfa on page 837
<b>List of Sample Output</b>	clear security idp counters dfa on page 689
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters dfa</b>	<pre>user@host&gt; clear security idp counters dfa clear_counter_class: counters cleared, status = 0</pre>

## clear security idp counters flow

---

<b>Syntax</b>	clear security idp counters flow
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the IDP flow-related counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>flow (IDP)</p> <p>show security idp counters flow on page 838</p>
<b>List of Sample Output</b>	clear security idp counters flow on page 690
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters flow</b>	<pre>user@host&gt; clear security idp counters dfa clear_counter_class: counters cleared, status = 0</pre>

## clear security idp counters ips

---

<b>Syntax</b>	clear security idp counters ips
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the ips counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>ips</p> <p>show security idp counters ips on page 841</p>
<b>List of Sample Output</b>	clear security idp counters ips on page 691
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters ips</b>	<pre>user@host&gt; clear security idp counters ips clear_counter_class: counters cleared, status = 0</pre>

## clear security idp counters log

---

<b>Syntax</b>	clear security idp counters log
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the IDP log counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	<p>log (IDP)</p> <p>show security idp counters log on page 843</p>
<b>List of Sample Output</b>	clear security idp counters log on page 692
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters log</b>	<pre>user@host&gt; clear security idp counters log clear_counter_class: counters cleared, status = 0</pre>



## clear security idp counters packet

---

<b>Syntax</b>	clear security idp counters packet
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the IDP packet counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security idp counters packet on page 846
<b>List of Sample Output</b>	clear security idp counters packet on page 693
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters packet</b>	<pre>user@host&gt; clear security idp counters packet clear_counter_class: counters cleared, status = 0</pre>

## **clear security idp counters policy-manager**

---

<b>Syntax</b>	clear security idp counters policy-manager
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reset all the IDP policies counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security idp counters policy-manager on page 849
<b>List of Sample Output</b>	clear security idp counters policy-manager on page 694
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters policy-manager</b>	<pre>user@host&gt; clear security idp counters policy-manager clear_counter_class: counters cleared, status = 0</pre>

## clear security idp counters tcp-reassembler

---

<b>Syntax</b>	clear security idp counters tcp-reassembler
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Reset all the TCP reassembler counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	re-assembler  show security idp counters tcp-reassembler on page 850
<b>List of Sample Output</b>	clear security idp counters tcp-reassembler on page 695
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security idp counters tcp-reassembler</b>	<pre> user@host&gt; clear security idp counters tcp-reassembler clear_counter_class: counters cleared, status = 0 </pre>

## clear security ike respond-bad-spi-count

---

<b>Syntax</b>	clear security ike respond-bad-spi-count < <i>gateway-name</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Clear information about invalid Internet Key Exchange (IKE) security parameter index (SPI) counters.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Clear all invalid SPI counters.  <i>gateway-name</i> —(Optional) Clear the invalid SPI counters for the given gateway.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	respond-bad-spi
<b>List of Sample Output</b>	clear security ike respond-bad-spi-count on page 696 clear security ike respond-bad-spi-count gateway-name1 on page 696
<b>Output Fields</b>	This command produces no output.
<b>clear security ike respond-bad-spi-count</b>	user@host> clear security ike respond-bad-spi-count
<b>clear security ike respond-bad-spi-count gateway-name1</b>	user@host> clear security ike respond-bad-spi-count gateway-name1

## clear security ike security-associations

---

<b>Syntax</b>	clear security ike security-associations < <i>peer-address</i> > <fpc <i>slot-number</i> > <indexSA-index-number> <kmd-instance (all   <i>kmd-instance-name</i> )> <picslot-number>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; fpc, pic, and kmd-instance options added in Release 9.3 of JUNOS software.
<b>Description</b>	Clear information about the current Internet Key Exchange (IKE) security associations.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Clear all IKE security associations.  <i>peer-address</i> —(Optional) Clear IKE security associations for the destination peer at this IP address.  <i>fpc slot-number</i> —Specific to SRX-series services gateway. Clear information about existing IKE SAs in this particular Flexible PIC Concentrator (FPC) slot.  <i>index SA-index-number</i> —(Optional) Clear the IKE security association with this index number.  <i>kmd-instance</i> —Specific to SRX-series services gateway. Clear information about existing IKE SAs in the key management process (daemon) (KMD) identified by the FPC <i>slot-number</i> and PIC <i>slot-number</i> . <ul style="list-style-type: none"> <li>■ all—All KMD instances running on the Services Processing Unit (SPU).</li> <li>■ <i>kmd-instance-name</i>—Name of the KMD instance running on the SPU.</li> </ul> <i>pic slot-number</i> —Specific to SRX-series services gateway. Clear information about existing IKE SAs in this particular PIC slot.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security ike security-associations on page 857
<b>List of Sample Output</b>	clear security ike security-associations on page 697 clear security ike security-associations 1.1.1.2 on page 698 clear security ike security-associations index 8 on page 698 clear security ike security-associations fpc 5 pic 0 kmd-instance all (SRX-series devices) on page 698
<b>Output Fields</b>	This command produces no output.
<b>clear security ike security-associations</b>	user@host> clear security ike security-associations

**clear security ike security-associations 1.1.1.2**  
user@host> clear security ike security-associations 1.1.1.2

**clear security ike security-associations index 8**  
user@host> clear security ike security-associations index 8

**clear security ike security-associations fpc 5 pic 0 kmd-instance all**  
user@host> clear security ike security-associations fpc 5 pic 0 kmd-instance all  
**(SRX-series devices)**

## clear security ipsec security-associations

---

<b>Syntax</b>	clear security ipsec security-associations fpc <i>slot-number</i> <index <i>SA-index-number</i> > kmd-instance (all   <i>kmd-instance-name</i> ) pic <i>slot-number</i>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; fpc, pic, and kmd-instance options added in Release 9.3 of JUNOS software.
<b>Description</b>	Clear information about IPsec security associations.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Clear all IPsec security associations.  fpc <i>slot-number</i> —Specific to SRX-series services gateway. Clear information about existing IPsec SAs in this particular Flexible PIC Concentrator (FPC) slot.  index <i>SA-index-number</i> —(Optional) Clear the IPsec security association with this index number.  kmd-instance—Specific to SRX-series services gateway. Clear information about existing IPsec SAs in the key management process (daemon) (KMD) identified by the FPC <i>slot-number</i> and PIC <i>slot-number</i> . <ul style="list-style-type: none"> <li>■ all—All KMD instances running on the Services Processing Unit (SPU).</li> <li>■ <i>kmd-instance-name</i>—Name of the KMD instance running on the SPU.</li> </ul> pic <i>slot-number</i> —Specific to SRX-series services gateway. Clear information about existing IPsec SAs in this particular PIC slot.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security ipsec security-associations on page 863
<b>List of Sample Output</b>	clear security ipsec security-associations on page 699 clear security ipsec security-associations index 8 on page 699
<b>Output Fields</b>	This command produces no output.
<b>clear security ipsec security-associations</b>	user@host> clear security ipsec security-associations
<b>clear security ipsec security-associations index 8</b>	user@host> clear security ipsec security-associations index 8

## clear security ipsec statistics

---

<b>Syntax</b>	clear security ike statistics <fpc slot-number> <index SA-index-number> <pic slot-number>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>fpc</b> and <b>pic</b> options added in Release 9.3 of JUNOS software.
<b>Description</b>	Clear IPsec statistics on the device.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Clear all IPsec statistics.  <b>fpc slot-number</b> —Specific to SRX-series services gateway. Clear statistics about existing IPsec SAs in this particular Flexible PIC Concentrator (FPC) slot.  <b>index SA-index-number</b> —(Optional) Clear the IPsec statistics for the security association with this index number.  <b>pic slot-number</b> —Specific to SRX-series services gateway. Clear statistics about existing IPsec SAs in this particular PIC slot.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security ipsec statistics on page 869
<b>List of Sample Output</b>	clear security ipsec statistics on page 700 clear security ipsec statistics index 1 on page 700 clear security ipsec statistics fpc 5 pic 0 (SRX-series devices) on page 700
<b>Output Fields</b>	This command produces no output.
<b>clear security ipsec statistics</b>	user@host> clear security ipsec statistics
<b>clear security ipsec statistics index 1</b>	user@host> clear security ipsec statistics index 1
<b>clear security ipsec statistics fpc 5 pic 0 (SRX-series devices)</b>	user@host> clear security ipsec statistics fpc 5 pic 0



## clear security nat incoming-table

---


<b>Syntax</b>	clear security nat incoming-table <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear Network Address Translation (NAT) incoming table information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Clear all information NAT incoming table.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear incoming table information on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security nat incoming-table on page 882
<b>List of Sample Output</b>	clear security nat incoming-table on page 701
<b>Output Fields</b>	This command produces no output.
<b>clear security nat incoming-table</b>	user@host> clear security nat incoming-table

## clear security pki key-pair

---

<b>Syntax</b>	clear security pki key-pair (all   certificate-id <i>certificate-id</i> )
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Clear public key infrastructure (PKI) key pair information for local digital certificates on the device.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	all—Clear key pair information for all local certificates.  certificate-id <i>certificate-id</i> —Clear key pair information for the local certificate with this certificate ID.
<b>Required Privilege Level</b>	clear and security
<b>Related Topics</b>	show security pki certificate-request on page 904
<b>List of Sample Output</b>	clear security pki key-pair all on page 702
<b>Output Fields</b>	This command produces no output.
<b>clear security pki key-pair all</b>	user@host> clear security pki key-pair all

## clear security pki local-certificate

<b>Syntax</b>	clear security pki local-certificate (all   certificate-id <i>certificate-id</i>   system-generated)
<b>Release Information</b>	Command modified in Release 9.1 of JUNOS software.
<b>Description</b>	Clear public key infrastructure (PKI) information for local digital certificates on the device.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	all—Clear information for all the local digital certificates on the device.
	<b>NOTE:</b> You cannot clear the automatically generated self-signed certificate using clear security pki local-certificate all command. To clear the self-signed certificate you need to use system-generated as an option.
	certificate-id <i>certificate-id</i> —Clear the specified local digital certificate with this certificate ID.
	system-generated—Clear the existing automatically generated self-signed certificate and generate a new self-signed certificate.
<b>Required Privilege Level</b>	clear and security
<b>Related Topics</b>	show security pki local-certificate on page 908  request security pki local-certificate generate-self-signed on page 718
<b>List of Sample Output</b>	clear security pki local-certificate all on page 703 clear security pki local-certificate system-generated on page 703
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security pki local-certificate all</b>	user@host> clear security pki local-certificate all
<b>clear security pki local-certificate system-generated</b>	user@host> clear security pki local-certificate system-generated

## clear security policies statistics

---

<b>Syntax</b>	clear security policies statistics
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Clear statistics for security policies configured on the device.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security policies on page 912
<b>List of Sample Output</b>	clear security policies statistics on page 704
<b>Output Fields</b>	This command produces no output.
<b>clear security policies statistics</b>	user@host> clear security policies statistics

## clear security screen statistics

---

<b>Syntax</b>	clear security screen statistics <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Clear intrusion detection service (IDS) security screen statistics on the device.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	node—(Optional) For chassis cluster configurations, clear security screen statistics on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security screen statistics on page 923
<b>List of Sample Output</b>	clear security screen statistics node 0 on page 705
<b>Output Fields</b>	This command produces no output.
<b>clear security screen statistics node 0</b>	user@host> <b>clear security screen statistics node 0</b>

## clear security screen statistics interface

---

<b>Syntax</b>	clear security screen statistics interface <i>interface-name</i>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Clear intrusion detection service (IDS) security screen statistics for an interface.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>interface</b> <i>interface-name</i> —Name of the interface on which to clear security screen statistics.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, clear security screen statistics on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b> —Clear all nodes.</li> <li>■ <b>local</b> —Clear the local node.</li> <li>■ <b>primary</b>—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security screen statistics on page 923
<b>List of Sample Output</b>	<p>clear security screen statistics interface fab0 on page 706</p> <p>clear security screen statistics interface fab0 node 0 on page 706</p>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security screen statistics interface fab0</b>	<pre> user@host&gt; clear security screen statistics interface fab0 node0: ----- IDS statistics has been cleared. node1: ----- IDS statistics has been cleared. </pre>
<b>clear security screen statistics interface fab0 node 0</b>	<pre> user@host&gt; clear security screen statistics interface fab0 node 0 node0: ----- IDS statistics has been cleared. </pre>

## clear security screen statistics zone

---

<b>Syntax</b>	clear security screen statistics zone <i>zone-name</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; node options added in Release 9.0 of JUNOS software.
<b>Description</b>	Clear IDS security screen statistics for a security zone.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>zone <i>zone-name</i> —Name of the security zone for which to clear security screen statistics.</p> <p>node—(Optional) For chassis cluster configurations, clear security screen statistics for a security zone on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all —Clear all nodes.</li> <li>■ local —Clear the local node.</li> <li>■ primary—Clear the primary node.</li> </ul>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show security screen statistics on page 923
<b>List of Sample Output</b>	clear security screen statistics zone abc node all on page 707 clear security screen statistics node 0 zone my-zone on page 707
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>clear security screen statistics zone abc node all</b>	<pre> user@host&gt; clear security screen statistics zone abc node all node0: ----- IDS statistics has been cleared. node1: ----- IDS statistics has been cleared.</pre>
<b>clear security screen statistics node 0 zone my-zone</b>	<pre> user@host&gt; clear security screen statistics node 0 zone my-zone node0: ----- IDS statistics has been cleared.</pre>

## clear system services dns-proxy cache

---

<b>Syntax</b>	clear system services dns-proxy cache < <i>hostname</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Clear Domain Name System (DNS) proxy cache information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Clear all DNS proxy cache information.  <i>hostname</i> —(Optional) Clear DNS proxy cache information from the specified host.
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show system services dns-proxy on page 937
<b>List of Sample Output</b>	clear system services dns-proxy cache on page 708
<b>Output Fields</b>	This command produces no output.
<b>clear system services dns-proxy cache</b>	user@host> <b>clear system services dns-proxy cache</b>



## **clear system services dns-proxy statistics**

---

<b>Syntax</b>	clear system services dns-proxy statistics
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Clear DNS proxy statistics.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	clear
<b>Related Topics</b>	show system services dns-proxy on page 937
<b>List of Sample Output</b>	clear system services dns-proxy statistics on page 709
<b>Output Fields</b>	This command produces no output.
<b>clear system services dns-proxy statistics</b>	<pre>user@host&gt; clear system services dns-proxy statistics</pre>



## Chapter 21

# Request Commands

This chapter presents the **request** operational commands available on J-series Services Routers and SRX-series services gateways running JUNOS software. Use the **request** operational commands to stop or reboot device components, switch between primary and backup components, display messages, and display system information. Operational commands are organized alphabetically.

The commands shown in this chapter are exclusive to J-series and SRX-series devices. For information about **request** commands that are not explained here—commands that are shared across Juniper Networks device—see the *JUNOS System Basics and Services Command Reference*.

## request chassis cluster failover node

---

<b>Syntax</b>	<code>request chassis cluster failover node <i>node-number</i> redundancy-group <i>group-number</i></code>
<b>Release Information</b>	Command introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>For chassis cluster configurations, initiate manual failover in a redundancy group from one node to the other, which becomes the primary node, and automatically reset the priority of the group to 255. The failover stays in effect until the new primary node becomes unavailable, the threshold of the redundancy group reaches 0, or you use the <code>request chassis cluster failover reset</code> command.</p> <p>After a manual failover, you must use the <code>request chassis cluster failover reset</code> command before initiating another failover.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><code>node <i>node-number</i></code>—Number of the chassis cluster node to which the redundancy group fails over.</p> <p><b>Range:</b> 0 through 1</p> <p><code>redundancy-group <i>group-number</i></code>—Number of the redundancy group on which to initiate manual failover. Redundancy group 0 is a special group consisting of the two Routing Engines in the chassis cluster.</p> <p><b>Range:</b> 0 through 255</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Topics</b>	<p><code>clear chassis cluster failover-count</code> on page 654</p> <p><code>request chassis cluster failover reset</code> on page 713</p> <p><code>show chassis cluster status</code> on page 739</p>
<b>List of Sample Output</b>	<code>request chassis cluster failover node 0 redundancy-group 1</code> on page 712
<b>Output Fields</b>	This command produces no output.
<b>request chassis cluster failover node 0 redundancy-group 1</b>	<code>user@host&gt; request chassis cluster failover node 0 redundancy-group 1</code>

## request chassis cluster failover reset

---

<b>Syntax</b>	request chassis cluster failover reset redundancy-group <i>group-number</i>
<b>Release Information</b>	Command introduced in Release 9.0 of JUNOS software.
<b>Description</b>	<p>In chassis cluster configurations, undo the previous manual failover and return the redundancy group to its original settings.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>redundancy-group <i>group-number</i> —Number of the redundancy group on which to reset manual failover. Redundancy group 0 is a special group consisting of the two Routing Engines in the chassis cluster.</p> <p><b>Range:</b> 0 through 255</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Topics</b>	<p>clear chassis cluster failover-count on page 654</p> <p>request chassis cluster failover node on page 712</p> <p>show chassis cluster status on page 739</p>
<b>List of Sample Output</b>	request chassis cluster failover reset redundancy-group 0 on page 713
<b>Output Fields</b>	This command produces no output.
<b>request chassis cluster failover reset redundancy-group 0</b>	<pre>user@host&gt; request chassis cluster failover reset redundancy-group 0</pre>

## request security idp security-package download

---

<b>Syntax</b>	request security idp security-package download <check-server> <full-update> <policy-templates> <version <i>version-number</i> >
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Manually download the individual components of the security package from the Juniper Security Engineering portal. The components are downloaded into a staging folder inside the device. By default, this command tries to download the delta set attack signature table.</p> <p>This command is supported on SRX-series devices.</p>
<b>Options</b>	<p><b>check-server</b>—(Optional) Retrieve the version information of the latest security package from the security portal server.</p> <p><b>full-update</b>—(Optional) Download the latest security package with the full set of attack signature tables from the portal.</p> <p><b>policy-templates</b>—(Optional) Download the latest policy templates from the portal.</p> <p><b>version <i>version-number</i></b> —(Optional) Download the security package of a specific version from the portal.</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Topics</b>	<p>show security idp active-policy on page 832</p> <p>show security idp security-package-version on page 854</p>
<b>List of Sample Output</b>	<p>request security idp security-package download on page 714</p> <p>request security idp security-package download policy-templates on page 714</p> <p>request security idp security-package download version 1151 full-update on page 714</p>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>request security idp security-package download</b>	<pre>user@host&gt; request security idp security-package download Successfully downloaded from(https://services.netscreen.com/cgi-bin/index.cgi). Version info:1152(Thu Apr 24 14:37:44 2008, Detector=9.1.140080400)</pre>
<b>request security idp security-package download policy-templates</b>	<pre>user@host&gt; request security idp security-package download policy-templates Successfully downloaded from(https://services.netscreen.com/cgi-bin/index.cgi). Version info:35</pre>
<b>request security idp security-package</b>	<pre>user@host&gt; request security idp security-package download version 1151 full-update</pre>

**download version 1151** Successfully downloaded from(<https://services.netscreen.com/cgi-bin/index.cgi>).  
**full-update** Version info:1151(Wed Apr 23 14:39:15 2008, Detector=9.1.140080400)

## request security idp security-package install

---

<b>Syntax</b>	request security idp security-package install <policy-templates> <status> <update-attack-database-only>
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Update the attack database inside the device with the newly downloaded one from the staging folder, recompiles the existing running policy and pushes the re-compiled policy to the data plane. Also, if there is an existing running policy and the previously installed detector's version is different from the newly downloaded one, the downloaded components are pushed to the data plane.  This command is supported on SRX-series devices.
<b>Options</b>	<p><b>policy-templates</b>—(Optional) Install the policy template file into /var/db/scripts/commit/templates.</p> <p><b>status</b>—(Optional) The command <b>security-package install</b> may take long time depending on the new Security DB size. Hence, <b>security-package install</b> command returns immediately and a background process performs the task. So, user can check the status using <b>security-package install status</b> command.</p> <p><b>update-attack-database-only</b>—(Optional) Loads the security package into IDP database but do not compile/push the active policy or the new detector to the data plane.</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Topics</b>	<p>show security idp active-policy on page 832</p> <p>show security idp security-package-version on page 854</p>
<b>List of Sample Output</b>	<p>request security idp security-package install on page 716</p> <p>request security idp security-package install status on page 716</p>
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>request security idp security-package install</b>	<pre>user@host&gt; request security idp security-package install</pre> <p>Will be processed in async mode. Check the status using the status checking CLI</p>
<b>request security idp security-package install status</b>	<pre>user@host&gt; request security idp security-package install status</pre> <p>Done;Attack DB update : successful - [UpdateNumber=1152,ExportDate=Thu Apr 24 14:37:44 2008]</p> <p>Updating data-plane with new attack or detector : not performed due to no existing active policy found.</p>



## request security pki ca-certificate verify

---

<b>Syntax</b>	request security pki ca-certificate verify ca-profile <i>ca-profile-name</i>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Verify the digital certificate installed for the specified certificate authority (CA).  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	ca-profile <i>ca-profile-name</i> —Display the specified CA profile.
<b>Required Privilege Level</b>	maintenance and security
<b>Related Topics</b>	ca-profile  show security pki ca-certificate on page 900
<b>List of Sample Output</b>	request security pki ca-certificate verify ca-profile ca1 (CRL downloaded) on page 717 request security pki ca-certificate verify ca-profile ca1 (CRL not downloaded) on page 717
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.  This user has downloaded the certificate revocation list (CRL).
<b>request security pki ca-certificate verify ca-profile ca1 (CRL downloaded)</b>	user@host> request security pki ca-certificate verify ca-profile ca1 CA certificate ca1 verified successfully  This user has not downloaded the certificate revocation list (CRL).
<b>request security pki ca-certificate verify ca-profile ca1 (CRL not downloaded)</b>	user@host> request security pki ca-certificate verify ca-profile ca1 CA certificate ca1: CRL verification in progress.Please check the PKId debug logs for completion status

## request security pki local-certificate generate-self-signed

---

<b>Syntax</b>	<pre>request security pki local-certificate generate-self-signed     certificate-id <i>certificate-id-name</i>     domain-name <i>domain-name</i> subject <i>subject-distinguished-name</i>     &lt;email <i>email-address</i>&gt;     &lt;ip-address <i>ip-address</i>&gt;</pre>
<b>Release Information</b>	Command introduced in Release 9.1 of JUNOS software with enhanced services.
<b>Description</b>	<p>Manually generate a self-signed certificate for the given distinguished name.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>certificate-id</b> <i>certificate-id-name</i>—Name of the certificate and the public/private key pair.</p> <p><b>domain-name</b> <i>domain-name</i>—Fully qualified domain name (FQDN). The FQDN provides the identity of the certificate owner for Internet Key Exchange (IKE) negotiations and provides an alternative to the subject name.</p> <p><b>subject</b> <i>subject-distinguished-name</i>—Distinguished name format that contains the common name, department, company name, state, and country in the following format: CN, OU, O, ST, C</p> <ul style="list-style-type: none"> <li>■ CN—Common name</li> <li>■ OU—Organizational unit name</li> <li>■ O—Organization name</li> <li>■ ST—State</li> <li>■ C—Country</li> </ul> <p><b>email</b> <i>email-address</i>—E-mail address of the certificate holder.</p> <p><b>ip-address</b> <i>ip-address</i>—IP address of the routing platform.</p>
<b>Required Privilege Level</b>	maintenance and security
<b>Related Topics</b>	<p>clear security pki local-certificate on page 703</p> <p>show security pki local-certificate on page 908</p>
<b>List of Sample Output</b>	request security pki local-certificate generate-self-signed certificate-id self-cert subject cn=abc domain-name juniper.net email mholmes@juniper.net on page 719
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.

```
request security pki local-certificate generate-self-signed
local-certificate
generate-self-signed
certificate-id self-cert subject cn=abc domain-name juniper.net email
mholmes@juniper.net
Self-signed certificate generated and loaded successfully
subject cn=abc
domain-name juniper.net
email
mholmes@juniper.net
```

## request security pki local-certificate verify

---

<b>Syntax</b>	request security pki local-certificate verify certificate-id <i>certificate-id-name</i>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Verify the validity of the local digital certificate identifier.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	certificate-id <i>certificate-id-name</i> — Name of the local digital certificate identifier.
<b>Required Privilege Level</b>	maintenance and security
<b>List of Sample Output</b>	request security pki local-certificate verify certificate-id bme1 (not downloaded) on page 720 request security pki local-certificate verify certificate bme1 (downloaded) on page 720
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.  You receive the following response before the certificate revocation list (CRL) is downloaded:  <div> <b>request security pki local-certificate verify certificate-id bme1 (not downloaded)</b> <pre> user@host&gt; request security pki local-certificate verify certificate-id bme1 Local certificate bme1: CRL verification in progress.Please check the PKId debug logs for completion status </pre> </div> You receive the following response after the certificate revocation list (CRL) is downloaded:  <div> <b>request security pki local-certificate verify certificate bme1 (downloaded)</b> <pre> user@host&gt; request security pki local-certificate verify certificate-id bme1 Local certificate bme1 verification success </pre> </div>

**request system partition compact-flash**

---

<b>Syntax</b>	request system partition compact-flash
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Reboots the device and repartitions the compact flash. The compact flash is repartitioned only if it is possible to restore all the data on the compact flash. Otherwise, the operation is aborted, and a message is displayed indicating that the current disk usage needs to be reduced.</p> <p>This command is supported on J-series devices.</p>
<b>Required Privilege Level</b>	maintenance
<b>List of Sample Output</b>	request system partition compact-flash (If Yes) on page 721 request system partition compact-flash (If No) on page 721
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>request system partition compact-flash (If Yes)</b>	<pre>user@host&gt; request system partition compact-flash Are you sure you want to reboot and partition the compact-flash ? [yes,no] yes Initiating repartition operation. The operation may take several minutes to complete. System will reboot now... &lt;System reboots&gt; &lt;Repartition operation is performed&gt; &lt;System reboots and starts up normally&gt;</pre>
<b>request system partition compact-flash (If No)</b>	<pre>user@host&gt; request system partition compact-flash Are you sure you want to reboot and partition the compact-flash ? [yes,no] no</pre>

## request system services dhcp

---

<b>Syntax</b>	<code>request system services dhcp (release <i>interface-name</i>   renew <i>interface-name</i>)</code>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Release or renew the acquired IP address for a specific interface.</p> <p>To view the status of the Dynamic Host Configuration Protocol (DHCP) clients on the specified interfaces, enter the <code>show system services dhcp client <i>interface-name</i></code> command.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><code>release <i>interface-name</i></code> —Clears other resources received earlier from the server, and reinitializes the client state to INIT for the particular interface.</p> <p><code>renew <i>interface-name</i></code> —Reacquires an IP address from the server for the interface. When you use this option, the command sends a discover message if the client state is INIT and a renew request message if the client state is BOUND. For all other states it performs no action.</p>
<b>Required Privilege Level</b>	maintenance
<b>Related Topics</b>	<p>dhcp</p> <p>show system services dhcp client on page 932</p>
<b>List of Sample Output</b>	<p>request system services dhcp client release ge-1/0/1 on page 722</p> <p>request system services dhcp client renew ge-1/0/1 on page 722</p>
<b>Output Fields</b>	This command produces no output.
<b>request system services dhcp client release ge-1/0/1</b>	<pre>user@host&gt; request system services dhcp client release ge-1/0/1</pre>
<b>request system services dhcp client renew ge-1/0/1</b>	<pre>user@host&gt; request system services dhcp client renew ge-1/0/1</pre>

## request wan-acceleration login

---

<b>Syntax</b>	<code>request wan-acceleration login fpc slot-number</code>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Log in to the WXC Integrated Services Module (ISM 200) from J-series devices running JUNOS software to access the WXOS CLI.</p> <p>To view the slot number, enter the <code>show chassis fpc pic-status</code> command. You require interface permission for read-only access, and interface-control and configure permission for read-write access.</p> <p>This command is supported on J-series devices.</p>
<b>Options</b>	<code>fpc slot-number</code> —Higher number of the two slots in the device chassis occupied by the WXC ISM 200.
<b>Required Privilege Level</b>	maintenance
<b>Related Topics</b>	<p><code>show chassis fpc</code> on page 741</p> <p><code>restart wan-acceleration</code> on page 726</p> <p><code>show wan-acceleration status</code> on page 941</p>
<b>List of Sample Output</b>	<p><code>request wan-acceleration login fpc 3 (permissions set)</code> on page 723</p> <p><code>request wan-acceleration login fpc 3 (permissions not set)</code> on page 723</p>
<b>Output Fields</b>	<p>When you enter this command, you are provided feedback on the status of your request.</p> <p>This user has a user account with interface-control and configure permissions set for read-write access to WXOS or has interface permissions set for read-only access.</p>
<b>request wan-acceleration login fpc 3 (permissions set)</b>	<pre>user@host&gt; request wan-acceleration login fpc 3 Copyright 2001-2006 Juniper Networks, Inc. All Rights Reserved.</pre> <p>This user has a user account without the correct permissions set and does not gain access to WXOS.</p>
<b>request wan-acceleration login fpc 3 (permissions not set)</b>	<pre>user@host&gt; request wan-acceleration login fpc 3 FPCLOGIN_LOGIN_FAILURE: fpclogin failed: user permissions not set.</pre>





## Chapter 22

# Restart Commands

This chapter presents the **restart** operational commands available on J-series Services Routers and SRX-series services gateways running JUNOS software. Use the **restart** operational commands to restart software processes on the device. Operational commands are organized alphabetically.

The commands shown in this chapter are exclusive to J-series and SRX-series devices. For information about **restart** commands that are not explained here—commands that are shared across Juniper Networks devices—see the *JUNOS System Basics and Services Command Reference*.

## restart wan-acceleration

---

<b>Syntax</b>	restart wan-acceleration
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Restart the WAN acceleration process.</p> <p>If the WXC Integrated Services Module (ISM 200) is not accessible, or is not responding, you can use this command to restart the WAN acceleration process on the device.</p> <p>This command is supported on J-series devices.</p>
<b>Required Privilege Level</b>	reset
<b>Related Topics</b>	<p>request wan-acceleration login on page 723</p> <p>show wan-acceleration status on page 941</p>
<b>List of Sample Output</b>	restart wan-acceleration on page 726
<b>Output Fields</b>	When you enter this command, you are provided feedback on the status of your request.
<b>restart wan-acceleration</b>	<pre>user@host&gt; restart wan-acceleration WAN acceleration process started, pid 5497</pre>

## Chapter 23

# Show Commands

This chapter presents the **show** operational commands available on J-series Services Routers and SRX-series services gateways running JUNOS software. Use the **show** operational commands to review and verify the validity of your configurations and monitor device operation. Operational commands are organized alphabetically.

The commands shown in this chapter are exclusive to J-series and SRX-series devices. For information about **show** commands that are not explained here—commands that are shared across Juniper Networks devices—see the *JUNOS Interfaces Command Reference*, the *JUNOS Routing Protocols and Policies Command Reference*, and the *JUNOS System Basics and Services Command Reference*.

## show bgp neighbor

---

<b>Syntax</b>	show bgp neighbor < <i>neighbor-address</i> > <instance <i>instance</i> >
<b>Release Information</b>	Command modified in Release 8.5 of JUNOS software.
<b>Description</b>	Display the state of the specified Border Gateway Protocol (BGP) neighbor. If a peer is forced to Idle state because of license check failure, the output displays the state and the reason—LicenseCheckFailed.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>instance instance</i> —(Optional) Display peer information for a particular routing instance.  <i>neighbor-address</i> —(Optional) Display information for only the BGP peer at the specified IP address.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<i>JUNOS Routing Protocols and Policies Command Reference</i>
<b>List of Sample Output</b>	show bgp neighbor 5.5.5.2 on page 730 show bgp neighbor instance master on page 731
<b>Output Fields</b>	Table 5 on page 728 lists the output fields for the show bgp neighbor command. Output fields are listed in the approximate order in which they appear.

**Table 5: show bgp neighbor Output Fields**

Field Name	Field Description
Peer	Address of the BGP neighbor. The address is followed by the neighbor's port number.
AS	AS number of the peer.
Local	Address of the local device. The address is followed by the peer's port number.
Type	Type of peer: Internal or External.

**Table 5: show bgp neighbor Output Fields** (continued)

Field Name	Field Description
State	<p>Current state of the BGP session:</p> <ul style="list-style-type: none"> <li>■ <b>Active</b>—BGP is initiating a transport protocol connection in an attempt to connect to a peer. If the connection is successful, BGP sends an open message.</li> <li>■ <b>Connect</b>—BGP is waiting for the transport protocol connection to complete.</li> <li>■ <b>Established</b>—The BGP session has been established, and the peers are exchanging update messages.</li> <li>■ <b>Idle</b>—Either the BGP license check failed, or this is the first stage of a connection and BGP is waiting for a Start event.</li> <li>■ <b>OpenConfirm</b>—BGP has acknowledged receipt of an open message from the peer and is waiting to receive a keepalive or notification message.</li> <li>■ <b>OpenSent</b>—BGP has sent an open message and is waiting to receive an open message from the peer.</li> </ul>
Flags	<p>Internal BGP flags:</p> <ul style="list-style-type: none"> <li>■ <b>Aggregate Label</b>—BGP has aggregated a set of incoming labels (labels received from the peer) into a single forwarding label.</li> <li>■ <b>CleanUp</b>—The peer session is being shut down.</li> <li>■ <b>Delete</b>—This peer has been deleted.</li> <li>■ <b>Idled</b>—This peer has been permanently idled.</li> <li>■ <b>Initializing</b>—The peer session is initializing.</li> <li>■ <b>SendRtn</b>—Messages are being sent to the peer.</li> <li>■ <b>Sync</b>—This peer is synchronized with the rest of the peer group.</li> <li>■ <b>TryConnect</b>—Another attempt is being made to connect to the peer.</li> <li>■ <b>Unconfigured</b>—This peer is not configured.</li> <li>■ <b>WriteFailed</b>—An attempt to write to this peer failed.</li> <li>■ <b>Last State</b>—Previous state of the BGP session.</li> </ul>
Last State	Previous state of the BGP session.
Last Event	<p>Last activity that occurred in the BGP session:</p> <ul style="list-style-type: none"> <li>■ <b>Closed</b>—The BGP session closed.</li> <li>■ <b>ConnectRetry</b>—The transport protocol connection failed, and BGP is trying again to connect.</li> <li>■ <b>HoldTime</b>—The session ended because the hold timer expired.</li> <li>■ <b>KeepAlive</b>—The local device sent a BGP keepalive message to the peer.</li> <li>■ <b>Open</b>—The local device sent a BGP open message to the peer.</li> <li>■ <b>OpenFail</b>—The local device did not receive an acknowledgment of a BGP open message from the peer.</li> <li>■ <b>RecvKeepAlive</b>—The local device received a BGP keepalive message from the peer.</li> <li>■ <b>RecvNotify</b>—The local device received a BGP notification message from the peer.</li> <li>■ <b>RecvOpen</b>—The local device received a BGP open message from the peer.</li> <li>■ <b>RecvUpdate</b>—The local device received a BGP update message from the peer.</li> <li>■ <b>Start</b>—The peering session started.</li> <li>■ <b>Stop</b>—The peering session stopped.</li> <li>■ <b>TransportError</b>—A TCP error occurred.</li> </ul>

**Table 5: show bgp neighbor Output Fields** *(continued)*

Field Name	Field Description
Last Error	<p>Last error that occurred in the BGP session:</p> <ul style="list-style-type: none"> <li>■ <b>Cease</b>—An error occurred, such as a version mismatch, that caused the session to close.</li> <li>■ <b>Finite State Machine Error</b>—In setting up the session, BGP received a message that it did not understand.</li> <li>■ <b>Hold Time Expired</b>—The session's hold time expired.</li> <li>■ <b>Message Header Error</b>—The header of a BGP message was malformed.</li> <li>■ <b>Open Message Error</b>—A BGP open message contained an error.</li> <li>■ <b>None</b>—No errors occurred in the BGP session.</li> <li>■ <b>Update Message Error</b>—A BGP update message contained an error.</li> </ul>
Export	Name of the export policy that is configured on the peer.
Import	Name of the import policy that is configured on the peer.
Options	<p>Configured BGP options:</p> <ul style="list-style-type: none"> <li>■ <b>AddressFamily</b>—Configured address family: inet or inet-vpn.</li> <li>■ <b>GracefulRestart</b>—Graceful restart is configured.</li> <li>■ <b>HoldTime</b>—Hold time configured with the <b>hold-time</b> statement. The hold time is three times the interval at which keepalive messages are sent.</li> <li>■ <b>Local Address</b>—Address configured with the <b>local-address</b> statement.</li> <li>■ <b>NLRI</b>—Configured multicast BGP state for the BGP group: multicast, unicast, or both if you have configured <b>nlri any</b>.</li> <li>■ <b>Peer AS</b>—Configured peer autonomous system (AS).</li> <li>■ <b>Preference</b>—Preference value configured with the <b>preference</b> statement.</li> <li>■ <b>Refresh</b>—Configured to refresh automatically when the policy changes.</li> <li>■ <b>Rib-group</b>—Configured routing table group.</li> </ul>
Address families configured	Names of configured address families for the VPN.
Local Address	Address of the local device.
Holdtime	Hold time configured with the <b>hold-time</b> statement. The hold time is three times the interval at which keepalive messages are sent.
Preference	Preference value configured with the <b>preference</b> statement.
Number of flaps	Number of times the BGP session has gone down and then come back up.
Trace file	Name of the file to receive the output of the tracing operation.

```

show bgp neighbor user@host> show bgp neighbor 5.5.5.2
5.5.5.2      Type: Internal  State: Idle (LicenseCheckFailed)  Flags: <ImportEval Sync>
Peer: 5.5.5.2 AS 200      Local: unspecified AS 200
                Type: Internal  State: Idle (LicenseCheckFailed)      (route reflector
client)Flags: <ImportEval>
                Last State: Idle      Last Event: Start

```

```

Last Error: None
Options: <Preference LogUpDown Cluster AddressFamily PeerAS Rib-group Refresh>

Address families configured: inet-unicast inet-vpn-unicast l2vpn-signaling
Holdtime: 90 Preference: 170
Number of flaps: 0
Trace options: all
Trace file: /var/log/bgp size 131072 files 10

```

```

show bgp neighbor user@host> show bgp neighbor instance master
instance master Peer: 5.5.5.1 AS 200 Local: 5.5.5.2 AS 200
Type: Internal State: Idle (LicenseCheckFailed) Flags: <>
Last State: Idle Last Event: Start
Last Error: Cease
Export: [ static ]
Options: <Preference LocalAddress LogUpDown AddressFamily PeerAS Rib-group
Refresh>
Address families configured: inet-unicast inet-vpn-unicast
Local Address: 5.5.5.2 Holdtime: 90 Preference: 170
Number of flaps: 4
Last flap event: RecvUpdate
Error: 'Update Message Error' Sent: 3 Recv: 0
Error: 'Cease' Sent: 2 Recv: 0
Trace file: /var/log/bgp size 131072 files 10

```

## show chassis cluster control-plane statistics

<b>Syntax</b>	show chassis cluster control-plane statistics
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Display information about chassis cluster control plane statistics.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear chassis cluster control-plane statistics on page 652
<b>List of Sample Output</b>	show chassis cluster control-plane statistics on page 732
<b>Output Fields</b>	Table 6 on page 732 lists the output fields for the show chassis cluster control-plane statistics command. Output fields are listed in the approximate order in which they appear.

**Table 6: show chassis cluster control-plane statistics Output Fields**

Field Name	Field Description
Control link statistics	Statistics of the control link used by chassis cluster traffic.  <ul style="list-style-type: none"> <li>■ Heartbeat packets sent—Number of heartbeat messages sent on the control link.</li> <li>■ Heartbeat packets received—Number of heartbeat messages received on the control link.</li> </ul>
Fabric link statistics	Statistics of the fabric link used by chassis cluster traffic.  <ul style="list-style-type: none"> <li>■ Probes sent—Number of probes sent.</li> <li>■ Probes received—Number of probes received.</li> </ul>

```

show chassis cluster control-plane statistics  user@host> show chassis cluster control-plane statistics
Control link statistics:
  Heartbeat packets sent: 124
  Heartbeat packets received: 125
Fabric link statistics:
  Probes sent: 124
  Probes received: 125

```



## show chassis cluster data-plane statistics

---

<b>Syntax</b>	show chassis cluster data-plane statistics
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Display information about chassis cluster data plane statistics.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear chassis cluster data-plane statistics on page 653
<b>List of Sample Output</b>	show chassis cluster data-plane statistics on page 734
<b>Output Fields</b>	Table 7 on page 734 lists the output fields for the show chassis cluster data-plane statistics command. Output fields are listed in the approximate order in which they appear.

**Table 7: show chassis cluster data-plane statistics Output Fields**

Field Name	Field Description
Services Synchronized	<ul style="list-style-type: none"> <li>■ Service name—Name of the service.</li> <li>■ Rtos sent—Number of real-time objects (RTO) sent.</li> <li>■ Rtos received—Number of RTOs received.</li> <li>■ Translation context—Messages synchronizing Network Address Translation (NAT) translation context.</li> <li>■ Incoming NAT—Messages synchronizing incoming Network Address Translation (NAT) service.</li> <li>■ Resource manager—Messages synchronizing resource manager groups and resources.</li> <li>■ Session create—Messages synchronizing session creation.</li> <li>■ Session close—Messages synchronizing session close.</li> <li>■ Session change—Messages synchronizing session change.</li> <li>■ Gate create—Messages synchronizing creation of pinholes (temporary openings in the firewall).</li> <li>■ Session ageout refresh request—Messages synchronizing request session after ageout.</li> <li>■ Session ageout refresh reply—Messages synchronizing reply session after ageout.</li> <li>■ IPsec VPN—Messages synchronizing VPN session.</li> <li>■ Firewall user authentication—Messages synchronizing firewall user authentication session.</li> <li>■ MGCP ALG—Messages synchronizing MGCP ALG sessions.</li> <li>■ H323 ALG—Messages synchronizing H.323 ALG sessions.</li> <li>■ SIP ALG—Messages synchronizing SIP ALG sessions.</li> <li>■ SCCP ALG—Messages synchronizing SCCP ALG sessions.</li> <li>■ PPTP ALG—Messages synchronizing PPTP ALG sessions.</li> <li>■ RTSP ALG—Messages synchronizing RTSP ALG sessions.</li> </ul>

```

show chassis cluster data-plane statistics user@host> show chassis cluster data-plane statistics
Services Synchronized:
Service name                RTOs sent    RTOs received
Translation context         0            0
Incoming NAT                0            0
Resource manager            0            0
Session create              0            0
Session close               0            0
Session change              0            0
Gate create                 0            0
Session ageout refresh requests 0            0
Session ageout refresh replies 0            0
IPsec VPN                   0            0
Firewall user authentication 0            0
MGCP ALG                    0            0
H323 ALG                    0            0
SIP ALG                     0            0
SCCP ALG                    0            0
PPTP ALG                    0            0
RTSP ALG                    0            0

```

## show chassis cluster interfaces

<b>Syntax</b>	show chassis cluster interfaces
<b>Release Information</b>	Command modified in Release 9.0 of JUNOS software.
<b>Description</b>	Display the status of the control interface in a chassis cluster configuration.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show chassis cluster interfaces on page 735
<b>Output Fields</b>	Table 8 on page 735 lists the output fields for the <b>show chassis cluster interfaces</b> command. Output fields are listed in the approximate order in which they appear.

**Table 8: show chassis cluster interfaces Output Fields**

Field Name	Field Description
Control link namea	Name and status of the chassis cluster control interface.
Redundant-ethernet Information	<ul style="list-style-type: none"> <li>■ Name—Name of the redundant Ethernet interface.</li> <li>■ Status—State of the interface: <b>up</b> or <b>down</b>.</li> <li>■ Redundancy-group—ID number (1-255) of the redundancy group associated with the redundant Ethernet interface.</li> </ul>
Interface Monitoring	<ul style="list-style-type: none"> <li>■ Interface—Name of the interface to be monitored.</li> <li>■ Weight—Relative importance of the interface to redundancy group operation.</li> <li>■ Status—State of the interface: <b>up</b> or <b>down</b>.</li> <li>■ Redundancy-group—Identification number of the redundancy group associated with the interface.</li> </ul>

```

show chassis cluster user@host> show chassis cluster interfaces
interfaces          Control link name: em0.0
                      Redundant-ethernet Information:
                        Name      Status      Redundancy-group
                        reth0     Up         1
                      Interface Monitoring:
                        Interface  Weight    Status    Redundancy-group
                        ge-6/0/0   200      Up        1

```

## show chassis cluster statistics

---

<b>Syntax</b>	show chassis cluster statistics
<b>Release Information</b>	Command modified in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about chassis cluster services and interfaces.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear chassis cluster statistics on page 655
<b>List of Sample Output</b>	show chassis cluster statistics on page 737
<b>Output Fields</b>	Table 9 on page 736 lists the output fields for the show chassis cluster statistics command. Output fields are listed in the approximate order in which they appear.

**Table 9: show chassis cluster statistics Output Fields**

Field Name	Field Description
Control link statistics	Statistics of the control link used by chassis cluster traffic. <ul style="list-style-type: none"><li>■ Heartbeat packets sent—Number of heartbeat messages sent on the control link.</li><li>■ Heartbeat packets received—Number of heartbeat messages received on the control link.</li></ul>
Fabric link statistics	Statistics of the fabric link used by chassis cluster traffic. <ul style="list-style-type: none"><li>■ Probes sent—Number of probes sent.</li><li>■ Probes received—Number of probes received.</li></ul>

**Table 9: show chassis cluster statistics Output Fields (continued)**

Field Name	Field Description
Services Synchronized	<ul style="list-style-type: none"> <li>■ Service name—Name of the service.</li> <li>■ Rtos sent—Number of real-time objects (RTO) sent.</li> <li>■ Rtos received—Number of RTOs received.</li> <li>■ Translation context—Messages synchronizing Network Address Translation (NAT) translation context.</li> <li>■ Incoming NAT—Messages synchronizing incoming Network Address Translation (NAT) service.</li> <li>■ Resource manager—Messages synchronizing resource manager groups and resources.</li> <li>■ Session create—Messages synchronizing session creation.</li> <li>■ Session close—Messages synchronizing session close.</li> <li>■ Session change—Messages synchronizing session change.</li> <li>■ Gate create—Messages synchronizing creation of pinholes (temporary openings in the firewall).</li> <li>■ Session ageout refresh request—Messages synchronizing request session after ageout.</li> <li>■ Session ageout refresh reply—Messages synchronizing reply session after ageout.</li> <li>■ IPsec VPN—Messages synchronizing VPN session.</li> <li>■ Firewall user authentication—Messages synchronizing firewall user authentication session.</li> <li>■ MGCP ALG—Messages synchronizing MGCP ALG sessions.</li> <li>■ H323 ALG—Messages synchronizing H.323 ALG sessions.</li> <li>■ SIP ALG—Messages synchronizing SIP ALG sessions.</li> <li>■ SCCP ALG—Messages synchronizing SCCP ALG sessions.</li> <li>■ PPTP ALG—Messages synchronizing PPTP ALG sessions.</li> <li>■ RTSP ALG—Messages synchronizing RTSP ALG sessions.</li> </ul>

```

show chassis cluster user@host> show chassis cluster statistics
statistics      Control link statistics:
                  Heartbeat packets sent: 798
                  Heartbeat packets received: 784
                  Fabric link statistics:
                  Probes sent: 793
                  Probes received: 0
                  Services Synchronized:
                  Service name           RTOs sent   RTOs received
                  Translation context     0           0
                  Incoming NAT            0           0
                  Resource manager        0           0
                  Session create          0           0
                  Session close           0           0
                  Session change          0           0
                  Gate create              0           0
                  Session ageout refresh requests 0           0
                  Session ageout refresh replies 0           0
                  IPsec VPN               0           0
                  Firewall user authentication 0           0
                  MGCP ALG                0           0

```

H323 ALG	0	0
SIP ALG	0	0
SCCP ALG	0	0
PPTP ALG	0	0
RTSP ALG	0	0

## show chassis cluster status

<b>Syntax</b>	show chassis cluster status <redundancy-group <i>group-number</i> >
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software.
<b>Description</b>	Display the failover status of a chassis cluster.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display the status of all redundancy groups in the chassis cluster.  <i>redundancy-group group-number</i> —(Optional) Display the status of the specified redundancy group.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	redundancy-group  clear chassis cluster failover-count on page 654  request chassis cluster failover node on page 712  request chassis cluster failover reset on page 713
<b>List of Sample Output</b>	show chassis cluster status on page 740 show chassis cluster status redundancy-group 0 on page 740
<b>Output Fields</b>	Table 10 on page 739 lists the output fields for the <b>show chassis cluster status</b> command. Output fields are listed in the approximate order in which they appear.

**Table 10: show chassis cluster status Output Fields**

Field Name	Field Description
Cluster ID	ID number (1-15) of a cluster.
Redundancy-Group	ID number (1-255) of a redundancy group in the chassis cluster.
Node name	Node (device) in the chassis cluster ( <b>node0</b> or <b>node1</b> ).
Priority	Assigned priority for the redundancy group on that node.
Status	State of the redundancy group ( <b>Primary</b> or <b>Secondary</b> ). <ul style="list-style-type: none"> <li>■ <b>Primary</b>—Redundancy group is active and passing traffic.</li> <li>■ <b>Secondary</b>—Redundancy group is passive and not passing traffic.</li> </ul>
Preempt	<ul style="list-style-type: none"> <li>■ <b>Yes:</b> Mastership can be preempted based on priority.</li> <li>■ <b>No:</b> Change in priority will not preempt the mastership.</li> </ul>

**Table 10: show chassis cluster status Output Fields** *(continued)*

Field Name	Field Description
Manual failover	<ul style="list-style-type: none"> <li>■ Yes: If the Mastership is set manually through the CLI with the <code>request chassis cluster failover node</code> or <code>request chassis cluster failover redundancy-group</code> command. This overrides Priority and Preempt.</li> <li>■ No: Mastership is not set manually through the CLI.</li> </ul>

```

show chassis cluster status      user@host> show chassis cluster status
Cluster ID: 3, Redundancy-group: 0
  Node name      Priority    Status    Preempt    Manual failover
  node0          254      Primary   No         No
  node1          2       Secondary No         No
Cluster ID: 3, Redundancy-group: 1
  Node name      Priority    Status    Preempt    Manual failover
  node0          254      Primary   No         No
  node1          1       Secondary No         No

show chassis cluster status redundancy-group 0
user@host> show chassis cluster status redundancy-group 0
Cluster: 1, Redundancy-Group: 0
  Node name      Priority    Status    Preempt    Manual failover
  node0          254      Primary   No         No
  node1          1       Secondary No         No

```



## show chassis fpc

---

<b>Syntax</b>	<pre>show chassis fpc &lt;detail &lt; pim-slot &gt;  &lt;node ( node-id   local   primary)&gt;&gt;   &lt;node ( node-id   local   primary)&gt;   &lt;pic-status &lt; pim-slot &gt;  &lt;node ( node-id   local   primary)&gt;&gt;</pre>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Display status information about the installed Physical Interface Modules (PIMs) and PIM slots in a single device chassis or in a chassis cluster configuration.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>none</b>—Display brief information about the state of the installed PIMs and PIM slots.</p> <p><b>detail</b>—(Optional) Display detailed PIM status information.</p> <p><b>pim-slot</b> —(Optional) Display information about the PIM in this slot.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display status information for all PIMs or for the specified PIM on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <b>node-id</b> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul> <p><b>pic-status</b>—(Optional) Display status information for all PIMs or for the PIM in the specified slot (see <b>pim-slot</b> ). The PIM slot number is reported as an FPC number, and the PIM number (always 0) is reported as a PIC number.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<i>JUNOS System Basics and Services Command Reference</i>
<b>List of Sample Output</b>	<p>show chassis fpc on page 742</p> <p>show chassis fpc (SRX 5600 and SRX 5800 devices) on page 742</p> <p>show chassis fpc detail on page 743</p> <p>show chassis fpc pic-status on page 743</p> <p>show chassis fpc pic-status (SRX 5600 and SRX 5800 devices) on page 743</p>
<b>Output Fields</b>	Table 11 on page 742 lists the output fields for the <b>show chassis fpc</b> command. Output fields are listed in the approximate order in which they appear.

**Table 11: show chassis fpc Output Fields**

Field Name	Field Description
Slot or Slot State	Slot number and state. The state can be one of the following conditions: <ul style="list-style-type: none"> <li>■ Dead—Held in reset because of errors.</li> <li>■ Diag—Slot is being ignored while the device is running diagnostics.</li> <li>■ Dormant—Held in reset.</li> <li>■ Empty—No PIM is present.</li> <li>■ Online—PIM is online and running.</li> <li>■ Present—PIM is detected by the device, but is either not supported by the current version of JUNOS or inserted in the wrong slot. The output also states either <b>Hardware Not Supported</b> or <b>Hardware Not In Right Slot</b>. PIM is coming up but not yet online.</li> <li>■ Probed—Probe is complete; awaiting restart of the Packet Forwarding Engine (PFE).</li> <li>■ Probe-wait—Waiting to be probed.</li> </ul>
Temp (C) or Temperature	Temperature of the air passing by the PIM, in degrees Celsius or in both Celsius and Fahrenheit.
Total CPU Utilization (%)	Total percentage of CPU being used by the PIM's processor.
Interrupt CPU Utilization (%)	Of the total CPU being used by the PIM's processor, the percentage being used for interrupts.
Memory DRAM (MB)	Total DRAM, in megabytes, available to the PIM's processor.
Heap Utilization (%)	Percentage of heap space (dynamic memory) being used by the PIM's processor. If this number exceeds 80 percent, there may be a software problem (memory leak).
Buffer Utilization (%)	Percentage of buffer space being used by the PIM's processor for buffering internal messages.
Start Time	Time when the Routing Engine detected that the PIM was running.
Uptime	How long the Routing Engine has been connected to the PIM and, therefore, how long the PIM has been up and running.
PIC type	(pic-status output only) Type of PIM.

```

show chassis fpc      user@host> show chassis fpc
Temp CPU Utilization (%)  Memory  Utilization (%)
Slot State                (C) Total  Interrupt    DRAM (MB) Heap    Buffer
0 Online                  ----- CPU less FPC -----
1 Online                  ----- Not Usable -----
2 Online                  ----- CPU less FPC -----

```

```

show chassis fpc (SRX 5600 and SRX 5800 devices) user@host> show chassis fpc
Temp CPU Utilization (%)  Memory  Utilization (%)
Slot State                (C) Total  Interrupt    DRAM (MB) Heap    Buffer
0 Empty
1 Empty
2 Empty
3 Online                  37      3        0        1024      7        42

```

```

4 Empty
5 Empty
6 Online          30      8      0      1024      23      30
7 Empty
8 Empty
9 Empty
10 Empty
11 Empty

```

**show chassis fpc detail** user@host> **show chassis fpc detail**

```

Slot 2 information:
State                               Online
Total CPU DRAM                     ---- CPU less FPC ----
Start time                         2002-01-07 17:11:28 PST
Uptime                             2 days, 8 hours, 38 minutes, 5 seconds

```

**show chassis fpc pic-status** user@host> **show chassis fpc pic-status**

```

node0:
-----
Slot 0  Online      FPC
PIC 0   Online      4x GE Base PIC
Slot 3  Online      FPC
PIC 0   Online      4x FE
Slot 6  Online      FPC
PIC 0   Online      8x GE uPIM
node1:
-----
Slot 0  Offline     FPC
Slot 3  Offline     FPC
Slot 6  Offline     FPC

```

**show chassis fpc pic-status (SRX 5600 and SRX 5800 devices)** user@host> **show chassis fpc pic-status**

```

Slot 3  Online      SRX5k SPC
PIC 0   Online      SPU Cp
PIC 1   Online      SPU Flow
Slot 6  Online      SRX5k DPC 4x 10GE
PIC 0   Online      1x 10GE(LAN/WAN) RichQ
PIC 1   Online      1x 10GE(LAN/WAN) RichQ
PIC 2   Online      1x 10GE(LAN/WAN) RichQ
PIC 3   Online      1x 10GE(LAN/WAN) RichQ

```

## show chassis hardware

<b>Syntax</b>	show chassis hardware <clei-models   detail   extensive   models   node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display chassis hardware information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><b>clei-models</b>—(Optional) Display Common Language Equipment Identifier Code (CLEI) barcode and model number for orderable field-replaceable units (FRUs).</p> <p><b>detail   extensive</b>—(Optional) Display the specified level of output.</p> <p><b>models</b>—(Optional) Display model numbers and part numbers for orderable FRUs.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display chassis hardware information on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <b>node-id</b> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<i>JUNOS System Basics and Services Command Reference</i>
<b>List of Sample Output</b>	<p>show chassis hardware on page 746</p> <p>show chassis hardware (SRX 5600 and SRX 5800 devices) on page 746</p> <p>show chassis hardware detail on page 746</p> <p>show chassis hardware detail node 1 on page 746</p> <p>show chassis hardware extensive on page 747</p> <p>show chassis hardware models (SRX 5600 and SRX 5800 devices) on page 748</p> <p>show chassis hardware clei-models (SRX 5600 and SRX 5800 devices) on page 748</p>
<b>Output Fields</b>	Table 12 on page 744 lists the output fields for the <b>show chassis hardware</b> command. Output fields are listed in the approximate order in which they appear.

**Table 12: show chassis hardware Output Fields**

Field Name	Field Description
Item	Chassis component—Information about the backplane; power supplies; fan trays; Routing Engine; each Physical Interface Module (PIM)—reported as FPC and PIC—and each fan, blower, and impeller.
Version	Revision level of the chassis component.

**Table 12: show chassis hardware Output Fields (continued)**

Field Name	Field Description
Part Number	Part number for the chassis component.
Serial Number	Serial number of the chassis component. The serial number of the backplane is also the serial number of the device chassis. Use this serial number when you need to contact Juniper Networks Customer Support about the device chassis.
Assb ID or Assembly ID	Identification number that describes the FRU hardware.
FRU model number	Model number of FRU hardware component.
CLEI code	Common Language Equipment Identifier code. This value is displayed only for hardware components that use ID EEPROM format v2. This value is not displayed for components that use ID EEPROM format v1.
EEPROM Version	ID EEPROM version used by hardware component: 0x01 (version 1) or 0x02 (version 2).
Description	<p>Brief description of the hardware item:</p> <ul style="list-style-type: none"> <li>■ Type of power supply.</li> <li>■ Type of PIM. If the PIM type is not supported on the current software release, the output states <b>Hardware Not Supported</b>.</li> <li>■ Type of FPC: The FPC type corresponds to the PIM. The following shows the PIM abbreviation in the output and the corresponding PIM name: <ul style="list-style-type: none"> <li>■ 2x FE—Dual-Port Fast Ethernet PIM</li> <li>■ 4x FE—4-Port Fast Ethernet ePIM</li> <li>■ 1x GE Copper—Copper Gigabit Ethernet ePIM (one 10-Mbps, 100-Mbps, or 1000-Mbps port)</li> <li>■ 1x GE SFP—SFP Gigabit Ethernet ePIM (one fiber port)</li> <li>■ 1x SFP uPIM—1-Port Gigabit Ethernet uPIM</li> <li>■ 6x GE SFP uPIM—6-Port Gigabit Ethernet uPIM</li> <li>■ 8x GE SFP uPIM—8-Port Gigabit Ethernet uPIM</li> <li>■ 16x GE SFP uPIM—16-Port Gigabit Ethernet uPIM</li> <li>■ 4x GE Base PIC—Four built-in Gigabit Ethernet ports on a chassis (fixed PIM)</li> <li>■ 2x Serial—Dual-Port Serial PIM</li> <li>■ 2x T1—Dual-Port T1 PIM</li> <li>■ 2x E1—Dual-Port E1 PIM</li> <li>■ 2x CT1E1/PRI—Dual-Port Channelized T1/E1/ISDN PRI PIM</li> <li>■ 1x T3—T3 PIM (one port)</li> <li>■ 1x E3—E3 PIM (one port)</li> <li>■ 4x BRI S/T—4-Port ISDN BRI S/T PIM</li> <li>■ 4x BRI U—4-Port ISDN BRI U PIM</li> <li>■ 1x ADSL Annex A—ADSL 2/2 + Annex A PIM (one port, for POTS)</li> <li>■ 1x ADSL Annex B—ADSL 2/2 + Annex B PIM (one port, for ISDN)</li> <li>■ 2x SHDSL (ATM)—G.SHDSL PIM (2-port two-wire mode or 1-port four-wire mode)</li> <li>■ Integrated Services Module—WXC Integrated Services Module (ISM 200)</li> </ul> </li> <li>■ For hosts, the Routing Engine type.</li> </ul>

**show chassis hardware**

```

user@host> show chassis hardware
Hardware inventory:
Item              Version  Part number  Serial number  Description
Chassis                               JN001340AA    JSR2300
Routing Engine    REV 07   750-009992   AA04350184    RE-J.1
FPC 0             REV 04   750-010738   AB04330259    FPC
PIC 0
Power Supply 0
2x FE, 2x T1

```

**show chassis hardware**  
**(SRX 5600 and SRX**  
**5800 devices)**

```

user@host> show chassis hardware
Hardware inventory:
Item              Version  Part number  Serial number  Description
Chassis                               JN10B7005AGA  SRX 5800
Midplane          REV 03   710-013698   TR0779        SRX 5800 Backplane
FPM Board         REV 03   710-014974   KC3406        Front Panel Display
PDM              Rev 03   740-013110   QCS1122504F   Power Distribution Module
PEM 1            Rev 03   740-013683   QCS1134703V   DC Power Entry Module
PEM 2            Rev 03   740-013683   QCS1134700E   DC Power Entry Module
Routing Engine 0 REV 06   740-015113   1000696955    RE-S-1300
CB 0             REV 07   710-013385   JZ3257        SRX5k SCB
FPC 3            BB-P2-39 710-020305   JS4847        SRX5k SPC
CPU              REV 06   710-013713   KC1180        DPC PMB
PIC 0            BUILTIN   BUILTIN       SPU Cp
PIC 1            BUILTIN   BUILTIN       SPU Flow
FPC 6            REV 03   750-020751   JT0109        SRX5k DPC 4x 10GE
CPU              REV 06   710-013713   KC3543        DPC PMB
PIC 0            BUILTIN   BUILTIN       1x 10GE(LAN/WAN) RichQ
Xcvr 0           NON-JNPR  A7C00SY       XFP-10G-SR
PIC 1            BUILTIN   BUILTIN       1x 10GE(LAN/WAN) RichQ
Xcvr 0           REV 01   740-011571   C728XJ01W     XFP-10G-SR
PIC 2            BUILTIN   BUILTIN       1x 10GE(LAN/WAN) RichQ
PIC 3            BUILTIN   BUILTIN       1x 10GE(LAN/WAN) RichQ
Fan Tray 0       REV 04   740-014971   TP1432        Fan Tray
Fan Tray 1       REV 04   740-014971   TP1829        Fan Tray

```

**show chassis hardware**  
**detail**

```

user@host> show chassis hardware detail
Hardware inventory:
Item              Version  Part number  Serial number  Description
Chassis                               JN000968AB    J4300
Midplane          REV 05   710-010001   ad04420077
System IO         REV 07   710-010003   AE04420393    System IO board
Routing Engine    REV 08   750-010005   btrd43500196  RE-J.2
ad0              488 MB  512MB CHH     504754C53A711400 Compact Flash
ad2              488 MB  512MB CHH     504754C43A711400 Removable Compact
Flash
FPC 2            REV 08   750-013493   NB9161        FPC
PIC 0
Module
ANNEX            REV 08   750-013493   NB9161        Integrated Services

```

**show chassis hardware**  
**detail node 1**

```

user@host> show chassis hardware detail node 1
node1:
-----
Hardware inventory:
Item              Version  Part number  Serial number  Description
Chassis                               JN108C688ADB  J6350
Midplane          REV 03   710-014593   NM7516
System IO         REV 01   710-016210   NN9781        JX350 System IO
Crypto Module
Routing Engine    REV 08   710-015273   NM6569        RE-J6350-3400
ad0              991 MB  1GB CKS       20060000000000000800 Compact Flash

```

```

FPC 0
FPC 3          REV 06   750-013492   NM1294          FPC
FPC 6          REV 11   750-015153   NP8750          FPC

```

# show chassis hardware extensive

```

user@host> show chassis hardware extensive
Hardware inventory:
Item          Version  Part number  Serial number  Description
Chassis
Jedec Code:   0x0000          EEPROM Version: 0x00
P/N:          .....          S/N:          JN107a494ADA
Assembly ID:  0x0513          Assembly Version: 00.00
Date:         00-00-0000      Assembly Flags:  0x00
Version:      .....
ID: j4350
...
FPC 5          REV 08   750-013493   NB9161          FPC
Jedec Code:   0x7fb0          EEPROM Version: 0x01
P/N:          750-013493      S/N:          S/N NB9161
Assembly ID:  0x073c          Assembly Version: 01.08
Date:         03-03-2006      Assembly Flags:  0x00
Version:      REV 08
ID: FPC
FRU Model Number: SSG-EPIM-1TX
Board Information Record:
Address 0x00: 34 01 05 05 02 ff ff ff ff ff ff ff ff ff ff
I2C Hex Data:
Address 0x00: 7f b0 01 ff 07 3c 01 08 52 45 56 20 30 38 00 00
Address 0x10: 00 00 00 00 37 35 30 2d 30 31 33 34 39 33 00 00
Address 0x20: 53 2f 4e 20 4e 42 39 31 36 31 00 00 00 03 03 07
Address 0x30: d6 ff ff ff 34 01 05 05 02 ff ff ff ff ff ff ff
Address 0x40: ff ff ff ff 01 00 00 00 00 00 00 00 00 00 00 53
Address 0x50: 53 47 2d 45 50 49 4d 2d 31 54 58 00 00 00 00 00
Address 0x60: 00 00 00 00 00 00 00 00 ff ff ff ff ff ff ff ff
Address 0x70: ff ff ff ff ff ff ff ff ff ff ff ff ff ff ff ff
PIC 0
Integrated Services
Module
Jedec Code:   0x7fb0          EEPROM Version: 0x01
Assembly ID:  0x063c          Assembly Version: 01.08
Date:         03-03-2006      Assembly Flags:  0x00
ID: Integrated Services Module
Board Information Record:
Address 0x00: 34 01 05 05 02 ff ff ff ff ff ff ff ff ff ff
I2C Hex Data:
Address 0x00: 7f b0 01 ff 06 3c 01 08 00 00 00 00 00 00 00 00
Address 0x10: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
Address 0x20: 00 00 00 00 00 00 00 00 00 00 00 00 00 03 03 07
Address 0x30: d6 ff ff ff 34 01 05 05 02 ff ff ff ff ff ff ff
Address 0x40: ff ff ff ff 00 00 00 00 00 00 00 00 00 00 00 53
Address 0x50: 53 47 2d 45 50 49 4d 2d 31 54 58 00 00 00 00 00
Address 0x60: 00 00 00 00 00 00 00 00 ff ff ff ff ff ff ff ff
Address 0x70: ff ff ff ff ff ed c0 0e 0b 00 00 00 00 00 00 00
ANNEX          REV 08   750-013493   NB9161          Integrated Services
Jedec Code:   0x7fb0          EEPROM Version: 0x01
P/N:          750-013493      S/N:          S/N NB9161
Assembly ID:  0x0808          Assembly Version: 01.08
Date:         03-03-2006      Assembly Flags:  0x00
Version:      REV 08
ID: Integrated Services
FRU Model Number: SSG-EPIM-1TX
Board Information Record:
Address 0x00: 34 01 05 05 02 ff ff ff ff ff ff ff ff ff ff
I2C Hex Data:
Address 0x00: 7f b0 01 ff 08 08 01 08 52 45 56 20 30 38 00 00

```

```

Address 0x10: 00 00 00 00 37 35 30 2d 30 31 33 34 39 33 00 00
Address 0x20: 53 2f 4e 20 4e 42 39 31 36 31 00 00 00 03 03 07
Address 0x30: d6 ff ff ff 34 01 05 05 02 ff ff ff ff ff ff ff
Address 0x40: ff ff ff ff 01 00 00 00 00 00 00 00 00 00 00 53
Address 0x50: 53 47 2d 45 50 49 4d 2d 31 54 58 00 00 00 00 00
Address 0x60: 00 00 00 00 00 00 ff ff ff ff ff ff ff ff ff ff
Address 0x70: ff ff ff ff ff ff ff ff ff ff ff ff ff ff ff

```

**show chassis hardware  
models (SRX 5600 and  
SRX 5800 devices)**

```
user@host> show chassis hardware models
```

```
Hardware inventory:
```

Item	Version	Part number	Serial number	FRU model number
Midplane	REV 03	710-013698	TR0779	CHAS-BP-MX960-S
FPM Board	REV 03	710-014974	KC3406	CRAFT-MX960-S
Routing Engine 0	REV 06	740-015113	1000696955	RE-S-1300-2048-S
CB 0	REV 07	710-013385	JZ3257	SCB-MX960-S

**show chassis hardware  
clei-models (SRX 5600  
and SRX 5800 devices)**

```
user@host> show chassis hardware clei-models
```

```
Hardware inventory:
```

Item	Version	Part number	CLEI code	FRU model number
FPM Board	REV 02	710-017254		CRAFT-MX480-S
Routing Engine 0	REV 06	740-015113		RE-S-1300-2048-S
CB 0	REV 07	710-013385		SCB-MX960-S
Fan Tray				SRX5600-FAN



## show interfaces

---

<b>Syntax</b>	show interfaces < interface-name > <extensive   terse>
<b>Release Information</b>	Command modified in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Display status information and statistics about interfaces on J-series and SRX-series devices running JUNOS software.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>interface-name</i> —(Optional) Display standard information about the specified interface. Following is a list of typical interface names. Replace pim with the PIM slot and port with the port number. For a complete list, see the <i>JUNOS Software Interfaces and Routing Configuration Guide</i>.</p> <ul style="list-style-type: none"> <li>■ <i>at-pim/0/port</i>—ATM-over-ADSL or ATM-over-SHDSL interface.</li> <li>■ <i>br-pim/0/port</i>—Basic Rate Interface for establishing ISDN connections.</li> <li>■ <i>ce1-pim/0/ port</i>—Channelized E1 interface.</li> <li>■ <i>ct1-pim/0/port</i>—Channelized T1 interface.</li> <li>■ <i>dl0</i>—Dialer Interface for initiating ISDN and USB modem connections.</li> <li>■ <i>e1-pim/0/port</i>—E1 interface.</li> <li>■ <i>e3-pim/0/port</i>—E3 interface.</li> <li>■ <i>fe-pim/0/port</i>—Fast Ethernet interface.</li> <li>■ <i>ge-pim/0/port</i>—Gigabit Ethernet interface.</li> <li>■ <i>se-pim/0/port</i>—Serial interface.</li> <li>■ <i>t1-pim/0/port</i>—T1 (also called DS1) interface.</li> <li>■ <i>t3-pim/0/port</i>—T3 (also called DS3) interface.</li> <li>■ <i>wx-slot/0/0</i>—WAN acceleration interface, for the WXC Integrated Services Module (ISM 200).</li> </ul> <p><i>extensive   terse</i>—(Optional) Display the specified level of output.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<i>JUNOS Interfaces Command Reference</i>
<b>List of Sample Output</b>	<p>show interfaces Gigabit Ethernet on page 750</p> <p>show interfaces extensive (Gigabit Ethernet) on page 750</p> <p>show interfaces terse on page 751</p> <p>show interfaces extensive (WAN Acceleration) on page 752</p>
<b>Output Fields</b>	Table 13 on page 750 lists the output fields for the <b>show interfaces</b> command. Output fields are listed in the approximate order in which they appear.

**Table 13: show interfaces Output Fields**

Field Name	Field Description
Allowed host inbound traffic	The allowed traffic through the interface.
Traffic statistics	Number of packets and bytes transmitted and received on the physical interface.
Local statistics	Number of packets and bytes transmitted and received on the physical interface.
Transit statistics	Number of packets and bytes transiting the physical interface.
Flow input statistics	Statistics on packets received by flow module.
Flow output statistics	Statistics on packets sent by flow module.
Flow error statistics	Statistics on errors in the flow module.
Admin	The interface is enabled (up) or disabled (down).

```

show interfaces Gigabit Ethernet user@host> show interfaces ge-0/0/1.0
Logical interface ge-0/0/1.0 (Index 67) (SNMP ifIndex 36)
  Flags: Device-Down SNMP-Traps Encapsulation: ENET2
  Protocol inet, MTU: 1500
  Flags: None
  Addresses, Flags: Dest-route-down Is-Preferred Is-Primary
    Destination: 4.4.4/24, Local: 4.4.4.254, Broadcast: 4.4.4.255
  Security: Zone: Untrust, ident-reset: on
  Allowed host-inbound traffic: bfd bgp bootp dhcp dlsw dvmrp finger ftp
                                http https ike ident-reset igmp ldp mld
                                msdp netconf ospf ospf3 pgm pim ping rip
                                ripng rlogin router-discovery rpm rsh
                                rsvp sap snmp snmp-trap ssh telnet
                                traceroute vrrp xnm-clear xnm-sslshow
  interfaces <interface-name> extensive

show interfaces extensive (Gigabit Ethernet) user@host> show interfaces ge-0/0/1.0 extensive
Logical interface ge-0/0/1.0 (Index 67) (SNMP ifIndex 37) (Generation 134)

  Flags: SNMP-Traps VLAN-Tag [ 0x8100.100 ] Encapsulation: ENET2
  Traffic statistics:
    Input bytes : 0
    Output bytes : 0
    Input packets: 0
    Output packets: 0
    Input bytes : IPv6 0
    Output bytes : IPv6 0
    Input packets: IPv6 0
    Output packets: IPv6 0
  Local statistics:
    Input bytes : 0
    Output bytes : 0
    Input packets: 0
    Output packets: 0
    Input bytes : IPv6 0
    Output bytes : IPv6 0
    Input packets: IPv6 0

```

```

        Output packets:                IPv6 0
Transit statistics:
    Input bytes :                      0          0 bps
    Output bytes :                     0          0 bps
    Input packets:                     0          0 pps
    Output packets:                    0          0 pps
    Input bytes :                      IPv6 0
    Output bytes :                     IPv6 0
    Input packets:                     IPv6 0
    Output packets:                     IPv6 0
Flow statistics:
    Flow input statistics:
        Self packets :                  0
        ICMP packets :                 113
        VPN packets :                   0
        Bytes permitted by policy:      0
        Connections established:        11
    Flow output statistics:
        Multicast packets :              0
        Bytes permitted by policy:      0
    Flow error statistics (Packets dropped due to):
        Policy denied:                  0
        No parent for a gate:            0
        Syn-attack protection:           0
        Incoming NAT errors:            0
        No session found:                0
        No more sessions:                0
        Invalid zone received packet:    0
        User authentication errors:      0
        Multiple user authentications:   0
        Multiple Incoming NAT:           0
        Address spoofing:                0
        No zone or NULL zone binding     0
        No NAT gate:                     0
        No minor session:                0
        No session for a gate:           0
        TCP sequence number out of window: 0
        No Route present:                0
        Authentication failed:           0
        Security association not active:  0
        No SA for incoming SPI:          0
        No one interested in self packets: 0
    Protocol inet, MTU: 1500, Generation: 139, Route table: 0
    Flags: None
    Addresses, Flags: None
        Destination: Unspecified, Local: 2.2.2.2, Broadcast: Unspecified,
        Generation: 137
    Addresses, Flags: Primary Is-Primary
        Destination: Unspecified, Local: 3.3.3.3, Broadcast: Unspecified,
        Generation: 139

```

**show interfaces terse**    user@host> **show interfaces terse**

Interface	Admin	Link	Proto	Local	Remote
ge-0/0/0	up	up			
ge-0/0/0.0	up	up	inet	10.209.4.61/18	
gr-0/0/0	up	up			
ip-0/0/0	up	up			
st0	up	up			
st0.1	up	ready	inet		
ls-0/0/0	up	up			
lt-0/0/0	up	up			

```

mt-0/0/0          up    up
pd-0/0/0          up    up
pe-0/0/0          up    up
e3-1/0/0          up    up
t3-2/0/0          up    up
e1-3/0/0          up    up
se-4/0/0          up    down
t1-5/0/0          up    up
br-6/0/0          up    up
dc-6/0/0          up    up
dc-6/0/0.32767    up    up
bc-6/0/0:1        down  up
bc-6/0/0:1.0      up    down
dl0               up    up
dl0.0             up    up    inet
dsc               up    up
gre               up    up
ipip              up    up
lo0               up    up
lo0.16385         up    up    inet    10.0.0.1        --> 0/0
                                           10.0.0.16       --> 0/0

lsi               up    up
mtun              up    up
pimd              up    up
pime              up    up
pp0               up    up

```

**show interfaces  
extensive (WAN  
Acceleration)**

```

user@host> show interfaces wx-6/0/0 extensive
Physical interface: wx-6/0/0, Enabled, Physical link is Up
Interface index: 142, SNMP ifIndex: 41, Generation: 143
Type: PIC-Peer, Link-level type: PIC-Peer, MTU: 1522, Clocking: Unspecified,
Speed: 1000mbps
Device flags : Present Running
Interface flags: Point-To-Point Promiscuous SNMP-Traps Internal: 0x4000
Link type : Full-Duplex
Link flags : None
Physical info : Unspecified
Hold-times : Up 0 ms, Down 0 ms
Current address: Unspecified, Hardware address: Unspecified
Alternate link address: Unspecified
Last flapped : 2007-08-01 05:19:35 UTC (02:12:04 ago)
Statistics last cleared: Never
Traffic statistics:
Input bytes :          58427          0 bps
Output bytes :        115078          0 bps
Input packets:         847          0 pps
Output packets:        972          0 pps
Input errors:
Errors: 0, Drops: 0, Framing errors: 0, Runts: 0, Giants: 0,
Policed discards: 0, Resource errors: 0
Output errors:
Carrier transitions: 0, Errors: 0, Drops: 0, MTU errors: 0,
Resource errors: 0
Logical interface wx-6/0/0.0 (Index 68) (SNMP ifIndex 43) (Generation 135)
Flags: Point-To-Point SNMP-Traps Encapsulation: PIC-Peering
Security: Zone: wx-zone
Allowed host-inbound traffic : any-service bootp bfd bgp dlsd dns dvmp
igmp ldp msdp nhrp ospf pgm pim rip router-discovery rsvp sap vrrp dhcp
finger ftp tftp ident-reset http https ike netconf ping rlogin rpm rsh snmp
snmp-trap ssh telnet traceroute xnm-clear-text xnm-ssl
Flow Statistics :

```

```

Flow Input statistics :
  Self packets :          0
  ICMP packets :          0
  VPN packets :           0
  Bytes permitted by policy : 70137
  Connections established : 4
Flow Output statistics:
  Multicast packets :      0
  Bytes permitted by policy : 2866
Flow error statistics (Packets dropped due to):
  Address spoofing:        0
  Authentication failed:   0
  Incoming NAT errors:     0
  Invalid zone received packet: 0
  Multiple user authentications: 0
  Multiple incoming NAT:   0
  No parent for a gate:    0
  No one interested in self packets: 0
  No minor session:        0
  No more sessions:        0
  No NAT gate:             0
  No route present:        0
  No SA for incoming SPI:  0
  No tunnel found:         0
  No session for a gate:    0
  No zone or NULL zone binding 0
  Policy denied:           0
  Security association not active: 0
  TCP sequence number out of window: 0
  Syn-attack protection:   0
  User authentication errors: 0
Protocol inet, MTU: 1500, Generation: 141, Route table: 0
  Flags: None
  Addresses, Flags: Is-Preferred Is-Primary
    Destination: 10.87.13.2, Local: 3.3.3.3, Broadcast: Unspecified,
    Generation: 142

```

## show interfaces flow-statistics

<b>Syntax</b>	show interfaces flow-statistics <interface-name>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Display interfaces flow statistics.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><i>Interface-name</i> —(Optional) Display flow statistics about the specified interface. Following is a list of typical interface names. Replace pim with the PIM slot and port with the port number. For a complete list, see the <i>JUNOS Software Interfaces and Routing Configuration Guide</i>.</p> <ul style="list-style-type: none"> <li>■ <i>at-pim/0/port</i>—ATM-over-ADSL or ATM-over-SHDSL interface.</li> <li>■ <i>br-pim/0/port</i>—Basic Rate Interface for establishing ISDN connections.</li> <li>■ <i>ce1-pim/0/port</i>—Channelized E1 interface.</li> <li>■ <i>ct1-pim/0/port</i>—Channelized T1 interface.</li> <li>■ <i>dl0</i>—Dialer Interface for initiating ISDN and USB modem connections.</li> <li>■ <i>e1-pim/0/port</i>—E1 interface.</li> <li>■ <i>e3-pim/0/port</i>—E3 interface.</li> <li>■ <i>fe-pim/0/ port</i>—Fast Ethernet interface.</li> <li>■ <i>ge-pim/0/port</i>—Gigabit Ethernet interface.</li> <li>■ <i>se-pim/0/port</i>—Serial interface.</li> <li>■ <i>t1-pim/0/port</i>—T1 (also called DS1) interface.</li> <li>■ <i>t3-pim/0/ port</i>—T3 (also called DS3) interface.</li> <li>■ <i>wx-slot/0/0</i>—WAN acceleration interface, for the WXC Integrated Services Module (ISM 200).</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show interfaces flow-statistics (Gigabit Ethernet) on page 755
<b>Output Fields</b>	Table 14 on page 754 lists the output fields for the <b>show interfaces flow-statistics</b> command. Output fields are listed in the approximate order in which they appear.

**Table 14: show interfaces flow-statistics Output Fields**

Field Name	Field Description
Traffic statistics	Number of packets and bytes transmitted and received on the physical interface.
Local statistics	Number of packets and bytes transmitted and received on the physical interface.
Transit statistics	Number of packets and bytes transiting the physical interface.

**Table 14: show interfaces flow-statistics Output Fields** (continued)

Field Name	Field Description
Flow input statistics	Statistics on packets received by flow module.
Flow output statistics	Statistics on packets sent by flow module.
Flow error statistics	Statistics on errors in the flow module.

```

show interfaces      user@host> show interfaces flow-statistics ge-0/0/1.0
flow-statistics (Gigabit   Logical interface ge-0/0/1.0 (Index 70) (SNMP ifIndex 49)
Ethernet)              Flags: SNMP-Traps Encapsulation: ENET2
                           Input packets : 5161
                           Output packets: 83
                           Security: Zone: zone2
                           Allowed host-inbound traffic : bootp bfd bgp dls w dns dvmrp igmp ldp msdp
nhrp ospf pgm
                           pim rip router-discovery rsvp sap vrrp dhcp finger ftp tftp ident-reset http
                           https ike
                           netconf ping rlogin rpm rsh snmp snmp-trap ssh telnet traceroute xnm-clear-text
xnm-ssl
                           lsping
                           Flow Statistics :
                           Flow Input statistics :
                               Self packets :                0
                               ICMP packets :                0
                               VPN packets :                 2564
                               Bytes permitted by policy :    3478
                               Connections established :      1
                           Flow Output statistics:
                               Multicast packets :            0
                               Bytes permitted by policy :    16994
                           Flow error statistics (Packets dropped due to):
                               Address spoofing:              0
                               Authentication failed:         0
                               Incoming NAT errors:           0
                               Invalid zone received packet:   0
                               Multiple user authentications:  0
                               Multiple incoming NAT:          0
                               No parent for a gate:           0
                               No one interested in self packets: 0
                               No minor session:               0
                               No more sessions:               0
                               No NAT gate:                    0
                               No route present:                0
                               No SA for incoming SPI:         0
                               No tunnel found:                 0
                               No session for a gate:           0
                               No zone or NULL zone binding     0
                               Policy denied:                   0
                               Security association not active: 0
                               TCP sequence number out of window: 0
                               Syn-attack protection:          0
                               User authentication errors:      0
                           Protocol inet, MTU: 1500
                           Flags: None

```

```
Addresses, Flags: Is-Preferred Is-Primary  
Destination: 2.2.2/24, Local: 2.2.2.2, Broadcast: 2.2.2.255
```



## show network-access requests pending

<b>Syntax</b>	show network-access requests pending <detail> <index <i>number</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display the status of pending authentication requests.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Show pending authentication requests.  detail—Display detailed information about all pending requests.  index <i>number</i> —(Optional) Display detailed information about the request specified by this index number. Use the command without options to obtain a list of requests and index numbers.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear network-access requests pending on page 656
<b>List of Sample Output</b>	show network-access requests pending on page 758 show network-access requests pending detail on page 758 show network-access requests pending index 1 on page 758
<b>Output Fields</b>	Table 15 on page 757 lists the output fields for the show network-access requests pending command. Output fields are listed in the approximate order in which they appear.

**Table 15: show network-access requests pending Output Fields**

Field Name	Field Description
Index	Internal number identifying the pending request. Use this number to obtain more information on the record.
User	Originator of authentication request.
Status	<p>The pending requests are requests and responses that are not yet sent back to the respective clients. The pending requests can be in one of the following states:</p> <ul style="list-style-type: none"> <li>■ <b>Processing:</b> This request is being processed by the device. The authentication process has started but is not complete.</li> <li>■ <b>Waiting on Auth Server:</b> The request is sent to an external authentication server, and the device is waiting for the response.</li> <li>■ <b>Processed:</b> This request has completed authentication (success or failure). The results are not yet forwarded back to the client.</li> <li>■ <b>Request cancelled by Admin:</b> This request was cancelled by the Admin. The reply with cancel code is not yet sent back to the client.</li> </ul>

**Table 15: show network-access requests pending Output Fields** (continued)

Field Name	Field Description
Profile	The profile determines how the user is authenticated.  Local clients defined with the statement <code>access profile client</code> are authenticated with the password authentication. Clients configured external to the device, on a RADIUS or LDAP server are authenticated with RADIUS or LDAP authentication.

```

show network-access requests pending      user@host> show network-access requests pending
Information about pending authentication entries
Total pending authentication requests: 2
Index User                               Status
1      Sun                               Processing
2      Sam                               Processed

show network-access requests pending detail user@host> show network-access requests pending detail
Information about pending authentication entries
Total pending authentication requests: 2
Index: 1 User: Sun
Status: Processing
Profile: Sunnyvale-firewall-users
Index: 2 User: Sam
Status: Processed
Profile: Westford-profile

show network-access requests pending index 1 user@host> show network-access requests pending index 1
Index: 1 User: Sun
Status: Processing
Profile: Sunnyvale-firewall-users

```

## show network-access requests statistics

<b>Syntax</b>	show network-access requests statistics
<b>Release Information</b>	Command modified in Release 9.1 of JUNOS software.
<b>Description</b>	Display authentication statistics for the configured authentication type.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	authentication-order  clear network-access requests statistics on page 657
<b>Output Fields</b>	Table 16 on page 759 lists the output fields for the network-access requests statistics command. Output fields are listed in the approximate order in which they appear.

**Table 16: show network-access requests statistics Output Fields**

Field Name	Field Description
Total requests received	Total number of authentication requests that the device received from clients.
Total responses sent	Total number of authentication responses that the device sent to the clients.
Success responses	Total number of clients that authenticated successfully.
Failure responses	Total number of clients that failed to authenticate.

```

show network-access requests statistics  user@host> show network-access requests statistics
General authentication statistics
  Total requests received: 100
  Total responses sent: 70
Radius authentication statistics
  Total requests received: 40
  Success responses: 20
  Failure responses: 20
LDAP authentication statistics
  Total requests received: 30
  Success responses: 15
  Failure responses: 15
Local authentication statistics
  Total requests received: 5
  Success responses: 2
  Failure responses: 3
Securid authentication statistics
  Total requests received: 15
  Success responses: 3
  Failure responses: 12

```

## show network-access securid-node-secret-file

<b>Syntax</b>	show network-access securid-node-secret-file
<b>Release Information</b>	Command introduced in Release 9.1 of JUNOS software.
<b>Description</b>	Display the path to the node secret file for the SecurID authentication type.  This command is supported on J-series and SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	configuration-file  securid-server  clear network-access securid-node-secret-file on page 658
<b>List of Sample Output</b>	show network-access securid-node-secret-file on page 760
<b>Output Fields</b>	Table 17 on page 760 lists the output fields for the network-access securid-node-secret-file command. Output fields are listed in the approximate order in which they appear.

**Table 17: show network-access securid-node-secret-file Output Fields**

Field Name	Field Description
SecurID Server	Name of the SecurID authentication server.
Node Secret File	Path to the node secret file.

```

show network-access user@host> show network-access securid-node-secret-file
securid-node-secret-file SecurID server node secret file:
                        SecurID Server      Node Secret File
                        ace-server1         /var/db/securid/ace-server1/node-secret

```

## show schedulers

<b>Syntax</b>	show schedulers < scheduler-name <i>scheduler-name</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about security policy schedulers configured on the system. If a specific scheduler is identified, detailed information is displayed for that scheduler only.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display information on all configured schedulers.  scheduler-name <i>scheduler-name</i> —(Optional) Display information on a particular scheduler.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	schedulers
<b>List of Sample Output</b>	show schedulers on page 761 show schedulers scheduler-name sch20 on page 762
<b>Output Fields</b>	Table 18 on page 761 lists the output fields for the <b>show schedulers</b> command. Output fields are listed in the approximate order in which they appear.

**Table 18: show schedulers Output Fields**

Field Name	Field Description
Scheduler name	Name of the scheduler.
State	Status of the scheduler: <ul style="list-style-type: none"> <li>■ <b>active</b>—The scheduler is associated with one or more policies. If active: <ul style="list-style-type: none"> <li>■ <b>Next deactivation</b>—Date and time when the policies with which the scheduler is associated are to be deactivated.</li> </ul> </li> <li>■ <b>inactive</b>—The scheduler is associated with one or more policies. If inactive: <ul style="list-style-type: none"> <li>■ <b>Next activation</b>—Date and time when the associated policies are to be activated.</li> </ul> </li> <li>■ <b>unused</b>—The scheduler is not associated with any policy, or it is past the stop date and no future activity is required.</li> </ul>

```

show schedulers  user@host> show schedulers
Scheduler name: s1, State: unused
Scheduler name: sch1, State: inactive
Next activation: Thu Feb 15 00:00:00 2007
Scheduler name: sch10, State: unused

```

```
Scheduler name: sch20, State: active  
Next deactivation: Thu Feb 15 00:00:00 2007
```

```
show schedulers      user@host> show schedulers scheduler-name sch20  
scheduler-name sch20 Scheduler name: sch20, State: active  
                        Next deactivation: Thu Feb 15 00:00:00 2007
```

## show security alg h323 counters

<b>Syntax</b>	show security alg h323 counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display H.323 Application Layer Gateway (ALG) counters information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Display H.323 ALG counters. information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display H.323 counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>h323</p> <p>clear security alg h323 counters on page 659</p>
<b>List of Sample Output</b>	show security alg h323 counters on page 764
<b>Output Fields</b>	Table 19 on page 763 lists the output fields for the <b>show security alg h323 counters</b> command. Output fields are listed in the approximate order in which they appear.

**Table 19: show security alg h323 counters Output Fields**

Field Name	Field Description
Packets received	Number of H.323 ALG packets received.
Packets dropped	Number of H.323 ALG packets dropped.
RAS message received	Number of incoming RAS (Endpoint Registration, Admission, and Status) messages per second per gatekeeper received and processed.
Q.931 message received	Counter for Q.931 message received.
H.245 message received	Counter for H.245 message received.

**Table 19: show security alg h323 counters Output Fields** (continued)

Field Name	Field Description
Number of calls	Total number of H.323 ALG calls.
<b>NOTE:</b>  This counter displays the number of call legs and may not display the exact number of voice calls that are active. For instance, for a single active voice call between two endpoints, this counter might display a value of 2.	
Number of active calls	Number of active H.323 ALG calls.
Decoding errors	Number of decoding errors.
Message flood dropped	Error counter for message flood dropped.
NAT errors	H.323 ALG Network Address Translation (NAT) errors.
Resource manager errors	H.323 ALG resource manager errors.

```

show security alg h323 counters user@host> show security alg h323 counters
counters
H.323 counters summary:
Packets received           :4060
Packets dropped            :24
RAS message received       :3690
Q.931 message received     :202
H.245 message received     :145
Number of calls            :25
Number of active calls     :0
H.323 Error Counters:
Decoding errors            :24
Message flood dropped      :0
NAT errors                 :0
Resource manager errors    :0
H.323 Message Counters:
RRQ      : 431   RCF      : 49 ARQ : 60   ACF      : 33
URQ      : 34   UCF      : 25 DRQ : 55   DCF      : 44
oth RAS  : 2942 Setup    : 28 Alert : 9   Connect : 25
CallPrd  : 18   Info     : 0   RelCmpl : 39 Facility : 14
Progress : 0   Empty     : 65   OLC     : 20   OLC-ACK : 20
oth H245 : 16

```



## show security alg mgcp calls

<b>Syntax</b>	show security alg mgcp calls <endpoint <i>endpoint-name</i>   node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG) calls.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all MGCP ALG calls.</p> <p>endpoint <i>endpoint-name</i> —(Optional) Display information about the endpoints of each MGCP ALG call.</p> <p>node—(Optional) For chassis cluster configurations, display MGCP calls on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>mgcp</p> <p>clear security alg mgcp calls on page 660</p>
<b>List of Sample Output</b>	<p>show security alg mgcp calls on page 766</p> <p>show security alg mgcp calls endpoint on page 766</p>
<b>Output Fields</b>	Table 20 on page 765 lists the output fields for the <b>show security alg mgcp calls</b> command. Output fields are listed in the approximate order in which they appear.

**Table 20: show security alg mgcp calls Output Fields**

Field Name	Field Description
Connection ID	Connection identifier for MGCP ALG calls.
Local SDP	MGCP ALG call local owner IP address as per the Session Description Protocol (SDP).
Remote SDP	MGCP ALG call remote owner IP address as per the Session Description Protocol (SDP).
RM Group	Resource manager group ID.
Notified entity	The certificate authority (CA) currently controlling the gateway.

```

show security alg mgcp calls
user@host> show security alg mgcp calls
Endpoint@GW      Zone      Call ID      RM Group
d001@101.50.10.1  Trust     10d55b81140e0f76  512
Connection Id> 0
Local SDP>  o: 101.50.10.1      x_o: 101.50.10.1
c: 101.50.10.1/32206      x_c: 101.50.10.1/32206
Remote SDP>  c: 3.3.3.5/16928    x_c: 3.3.3.5/16928
Endpoint@GW      Zone      Call ID      RM Group
d001@3.3.3.5     Untrust   3a104e9b41a7c4c9  511
Connection Id> 0
Local SDP>  o: 3.3.3.5      x_o: 3.3.3.5
c: 3.3.3.5/16928      x_c: 3.3.3.5/16928
Remote SDP>  c: 101.50.10.1/32206    x_c: 101.50.10.1/32206

show security alg mgcp calls endpoint
user@host> show security alg mgcp calls endpoint
Gateway: 101.50.10.1      Zone: Trust      IP: 101.50.10.1 -> 101.50.10.1
Endpoint      Trans #  Call #  Notified Entity
d001          1        1      0.0.0.0/0->0.0.0.0/0
Gateway: 3.3.3.5      Zone: Untrust    IP: 3.3.3.5 -> 3.3.3.5
Endpoint      Trans #  Call #  Notified Entity
d001          1        1      0.0.0.0/0->0.0.0.0/0

```

## show security alg mgcp counters

<b>Syntax</b>	show security alg mgcp counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG) counters information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display MGCP ALG counters information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display MGCP counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>mgcp</p> <p>clear security alg mgcp counters on page 661</p>
<b>List of Sample Output</b>	show security alg mgcp counters on page 768
<b>Output Fields</b>	Table 21 on page 767 lists the output fields for the <b>show security alg mgcp counters</b> command. Output fields are listed in the approximate order in which they appear.

**Table 21: show security alg mgcp counters Output Fields**

Field Name	Field Description
Packets received	Number of MGCP ALG packets received.
Packets dropped	Number of MGCP ALG packets dropped.
Message received	Number of MGCP ALG messages received.
Number of connections	Number of MGCP ALG connections.
Number of active connections	Number of active MGCP ALG connections.
Number of calls	Number of MGCP ALG calls.
Number of active calls	Number of MGCP ALG active calls.

**Table 21: show security alg mgcp counters Output Fields** *(continued)*

Field Name	Field Description
Number of active transactions	Number of active transactions.
Number of re-transmission	Number of MGCP ALG retransmissions.
Unknown-method	MGCP ALG unknown method errors.
Decoding error	MGCP ALG decoding errors.
Transaction error	MGCP ALG transaction errors.
Call error	MGCP ALG counter errors.
Connection error	MGCP ALG connection errors.
Connection flood drop	MGCP ALG connection flood drop errors.
Message flood drop	MGCP ALG message flood drop error.
IP resolve error	MGCP ALG IP address resolution errors.
NAT error	MGCP ALG Network Address Translation (NAT) errors.
Resource manager error	MGCP ALG resource manager errors.

```

show security alg mgcp counters user@host> show security alg mgcp counters
counters MGCP counters summary:
Packets received :284
Packets dropped :0
Message received :284
Number of connections :4
Number of active connections :3
Number of calls :4
Number of active calls :3
Number of transactions :121
Number of active transactions:52
Number of re-transmission :68
MGCP Error Counters:
Unknown-method :0
Decoding error :0
Transaction error :0
Call error :0
Connection error :0
Connection flood drop :0
Message flood drop :0
IP resolve error :0
NAT error :0
Resource manager error :0
MGCP Packet Counters:
CRCX :4 MDCX :9 DLCX :2
AUPE :1 AUCX :0 NTFY :43
RSIP :79 EPCF :0 RQNT :51
000-199 :0 200-299 :95 300-999 :0

```

## show security alg mgcp endpoints

<b>Syntax</b>	show security alg mgcp endpoints < endpoint name > <node ( node-id   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Media Gateway Control Protocol (MGCP) Application Layer Gateway (ALG) endpoints.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display MGCP ALG endpoints information.</p> <p><i>endpoint-name</i> —(Optional) Display information about the specified MGCP ALG endpoint.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display MGCP endpoints on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	mgcp
<b>List of Sample Output</b>	<p>show security alg mgcp endpoints on page 770</p> <p>show security alg mgcp endpoints d001@100.100.100.152 on page 770</p>
<b>Output Fields</b>	Table 22 on page 769 lists the output fields for the <b>show security alg mgcp endpoints</b> command. Output fields are listed in the approximate order in which they appear.

**Table 22: show security alg mgcp endpoints Output Fields**

Field Name	Field Description
Gateway	IP address of the gateway.
Zone	Gateway zone ID.
Endpoint	Endpoint name.
Trans #	Transaction ID.
Call #	Call ID.

Table 22: show security alg mgcp endpoints Output Fields (continued)

Field Name	Field Description
Notified entity	The certificate authority (CA) currently controlling the gateway.

show security alg mgcp endpoints

user@host> show security alg mgcp endpoints

Gateway: 100.100.100.152      Zone: z0      IP: 100.100.100.152 -> 100.100.100.152

Endpoint              Trans #      Call #      Notified entity

d001                   3           1           0.0.0.0:0 -> 0.0.0.0:0

show security alg mgcp endpoints d001@100.100.100.152

user@host> show security alg mgcp endpoints d001@100.100.100.152

Gateway: 100.100.100.152      Zone: z0      IP: 100.100.100.152 -> 100.100.100.152

Endpoint              Trans #      Call #      Notified entity

d001                   12          2           0.0.0.0:0 -> 0.0.0.0:0

## show security alg msrpc

<b>Syntax</b>	show security alg msrpc <object-id-map> <portmap>
<b>Release Information</b>	Command introduced in Release 9.0 of JUNOS software with enhanced services.
<b>Description</b>	Display Microsoft (MS) remote procedure call (RPC) Application Layer Gateway (ALG) information.  This command is supported on J-series devices.
<b>Options</b>	object-id-map—(Optional) Display information about MSRPC ID (UUID) to object ID (OID) table.  portmap—(Optional) Display information about Microsoft's implementation of the remote procedure call (MSRPC) mapping table.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	msrpc  Sample Output on page ?
<b>List of Sample Output</b>	show security alg msrpc object-id-map on page 771 show security alg msrpc portmap on page 772
<b>Output Fields</b>	Table 23 on page 771 lists the output fields for the show security alg msrpc command. Output fields are listed in the approximate order in which they appear.

**Table 23: show security alg msrpc Output Fields**

Field Name	Field Description
UUID	MS RPC ID.
OID	MS RPC object ID.
IP	IP address of the server that maps to the MS RPC ID.
Port	Port number of the server that maps to the MS RPC ID.
Protocol	Protocol used to support the process.

```

show security alg msrpc  user@host> show security alg msrpc object-id-map
object-id-map           UUID
                        1be617c0-31a5-11cf-a7d8-00805f48a135  0x80000020
                        e3514235-4b06-11d1-ab04-00c04fc2dcd2  0x80000002
                        67df7c70-0f04-11ce-b13f-00aa003bac6c   0x80000014

```

```
show security alg msrpc user@host> show security alg msrpc portmap
portmap      IP      Port  Protocol  UUID
             172.27.81.162 36100 TCP       1544f5e0-613c-11d1-93df-00c04fd7bd09
             172.27.81.162 516   TCP       f5cc5a18-4264-101a-8c59-08002b2f8426
```



## show security alg sccp calls

<b>Syntax</b>	show security alg sccp calls < brief   detail   node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Skinny Client Control Protocol (SCCP) Application Layer Gateway (ALG) calls.  This command is supported on J-series devices.
<b>Options</b>	none   brief—Display brief call information.  detail—(Optional) Display detailed call information.  node—(Optional) For chassis cluster configurations, display SCCP calls on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	sccp  clear security alg sccp calls on page 663
<b>List of Sample Output</b>	show security alg sccp calls on page 774 show security alg sccp calls detail on page 774
<b>Output Fields</b>	Table 24 on page 773 lists the output fields for the <b>show security alg sccp calls</b> command. Output fields are listed in the approximate order in which they appear.

**Table 24: show security alg sccp calls Output Fields**

Field Name	Field Description
Client IP address	IP address of the client.
Client zone	Client zone ID.
Call manager	IP address of the call manager.
Resource manager group	Resource manager group ID.

```

show security alg sccp user@host> show security alg sccp calls
calls
Client IP      Zone      CallManager      Conference ID  RM group
11.0.102.91    7         13.0.99.226      16789504      2047
12.0.102.96    8         13.0.99.226      16789505      2048

show security alg sccp user@host> show security alg sccp calls detail
calls detail
Client IP address: 11.0.102.91
Client zone: 7
CallManager IP: 13.0.99.226
Conference ID: 16789504
Resource manager group: 2048
SCCP channel information:
  Media transmit channel address (IP address/Port): 0.0.0.0:0
  Media transmit channel translated address (IP address/Port): 0.0.0.0:0
  Media transmit channel pass-through party ID (PPID): 0
  Media transmit channel resource ID: 0
  Media receive channel address (IP address/Port): 11.0.102.91:20060
  Media receive channel translated address (IP address/Port): 25.0.0.1:1032
  Media receive channel pass-through party ID (PPID): 16934451
  Media receive channel resource ID: 8185
  Multimedia transmit channel address (IP address/Port): 0.0.0.0:0
  Multimedia transmit channel translated address (IP address/Port): 0.0.0.0:0
  Multimedia transmit channel pass-through party ID (PPID): 0
  Multimedia transmit channel resource ID: 0
  Multimedia receive channel address (IP address/Port): 0.0.0.0:0
  Multimedia receive channel translated address (IP address/Port): 0.0.0.0:0
  Multimedia receive channel pass-through party ID (PPID): 0
  Multimedia receive channel resource ID: 0
Total number of calls = 1

```

## show security alg sccp counters

<b>Syntax</b>	show security alg sccp counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Skinny Client Control Protocol (SCCP) Application Layer Gateway (ALG) counters.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Display all SCCP ALG counters.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display SCCP counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>sccp</p> <p>clear security alg sccp counters on page 664</p>
<b>List of Sample Output</b>	show security alg sccp counters on page 776
<b>Output Fields</b>	Table 25 on page 775 lists the output fields for the show security alg sccp counters command. Output fields are listed in the approximate order in which they appear.

**Table 25: show security alg sccp counters Output Fields**

Field Name	Field Description
Active client sessions	Number of active SCCP ALG client sessions.
Active calls	Number of active SCCP ALG calls.
Total calls	Total number of SCCP ALG calls.
Packets received	Number of SCCP ALG packets received.
PDU's processed	Number of SCCP ALG protocol data units (PDU) processed.
Current call rate	Number of calls per second.
Packets dropped	Number of packets dropped by the SCCP ALG.

**Table 25: show security alg sccp counters Output Fields** *(continued)*

Field Name	Field Description
Decode errors	Number of decoding errors.
Protocol errors	Number of protocol errors.
Address translation errors	Number of NAT errors.
Policy lookup errors	Number of errors occurring during policy lookups.
Unknown PDUs	Number of unknown protocol data units (PDUs).
Maximum calls exceed	Number of times the maximum number of calls was exceeded.
Maximum call rate exceed	Number of times the maximum call rate was exceeded.
Initialization errors	Number of call initialization errors.
Internal errors	Number of internal errors.
Nonspecific error	Number of nonspecific errors.

```

show security alg sccp counters user@host> show security alg sccp counters
counters                      SCCP call statistics:
    Active client sessions      : 4
    Active calls                : 2
    Total calls                 : 3
    Packets received            : 232
    PDUs processed              : 232
    Current call rate           : 0
Error counters:
    Packets dropped             : 0
    Decode errors               : 0
    Protocol errors             : 0
    Address translation errors  : 0
    Policy lookup errors        : 0
    Unknown PDUs                : 0
    Maximum calls exceeded      : 0
    Maximum call rate exceeded  : 0
    Initialization errors       : 0
    Internal errors             : 0
    Nonspecific error           : 0

```

## show security alg sip calls

<b>Syntax</b>	show security alg sip calls <brief   detail   node ( <i>node-id</i>   all   local   primary) >
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Session Initiation Protocols (SIP) Application Layer Gateway (ALG) calls.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none   brief—Display brief call information.  detail—(Optional) Display detailed information about SIP ALG calls.  node—(Optional) For chassis cluster configurations, display SIP calls on a specific node (device) in the cluster. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	sip  clear security alg sip calls on page 665
<b>List of Sample Output</b>	show security alg sip calls on page 778 show security alg sip calls detail on page 778 show security alg sip calls node all on page 778
<b>Output Fields</b>	Table 26 on page 777 lists the output fields for the <b>show security alg sip calls</b> command. Output fields are listed in the approximate order in which they appear.

**Table 26: show security alg sip calls Output Fields**

Field Name	Field Description
UAS callid	Call Identifier for the SIP ALG user agent server.
Local Tag	Local tag for the SIP ALG user agent server.
Remote Tag	Remote tag for the SIP ALG user agent server.
State	State of the SIP ALG user agent server.

```

show security alg sip user@host> show security alg sip calls
calls Total number of calls: 2 (# of call legs 4)
    Call leg1: zone 3
        UAS callid:000ed748-55330007-04c3379d-0aab7e18@2.2.3.2 (pending tsx 1)
        Local tag
        Remote tag: 000ed748553300e264b0a951-5caa0a95
        State: STATE_DISCONNECTED
    Call leg2: zone 2
        UAC callid:000ed748-55330007-04c3379d-0aab7e18@2.2.3.2 (pending tsx 1)
        Local tag: 000ed748553300e264b0a951-5caa0a95
        Remote tag
        State: STATE_DISCONNECTED
    Call leg1: zone 3
        UAS callid:000ed748-55330007-04c3379d-0aab7e18@2.2.3.2 (pending tsx 1)
        Local tag: 000f90542e7e64cd724880f5-65db2f99
        Remote tag: 000ed748553300e264b0a951-5caa0a95
        State: STATE_ESTABLISHED
    Call leg2: zone 2
        UAC callid:000ed748-55330007-04c3379d-0aab7e18@2.2.3.2 (pending tsx 1)
        Local tag: 000ed748553300e264b0a951-5caa0a95
        Remote tag: 000f90542e7e64cd724880f5-65db2f99
        State: STATE_ESTABLISHED

show security alg sip user@host> show security alg sip calls detail
calls detail Total number of calls: 1
    Call ID : 000ed748-5533005e-11d97de9-77759865@10.10.10.254
    Local tag : 000f90542e7e005c7807c3a0-0647d41e
    Remote tag : 000ed748553300724648b313-2ccd0d9a
    State : STATE_ESTABLISHED
    RM Group:2048
    Local Info Remote Info RM Info
    -----
    Call leg 1: IP Port IP Port RSC id
    Host 10.10.10.10 5060 10.10.10.10 5060
    Contact 10.10.10.100 5060 10.10.10.254 1025 8191
    Contact maddr-
    SDP:c 10.10.10.100 10.10.10.254
    SDP:m 10.10.10.100 18902 10.10.10.254 64518 8192 ,8185
    Call leg 2:
    Host 10.10.10.10 5060 10.10.10.10 5060
    Contact 10.10.10.254 1025 10.10.10.100 5060 8188
    Contact maddr-
    SDP:c 10.10.10.254 10.10.10.100
    SDP:m 10.10.10.254 64518 10.10.10.100 18902 8186 ,8187

show security alg sip user@host> show security alg sip calls node all
calls node all node0:
    -----
    Total number of calls: 1
    Call leg 1 Zone : 6
    UAS call ID: 00078513-12490005-2ca7b914-2b5ea3b3@26.0.29.236 (pending
    transactions 0)
    Local tag : 00036bb9112700267368b9d7-423830f3
    Remote tag : 000785131249002902c91c61-0a9627ad
    State : STATE_ESTABLISHED
    Call leg 2 Zone : 8
    UAC call ID: 00078513-12490005-2ca7b914-2b5ea3b3@11.0.100.196:1050 (pending
    transactions 0)
    Local tag : 000785131249002902c91c61-0a9627ad
    Remote tag : 00036bb9112700267368b9d7-423830f3
    State : STATE_ESTABLISHED

```

node1:

```
-----
Total number of calls: 1
Call leg 1 Zone : 6
  UAS call ID: 00078513-12490005-2ca7b914-2b5ea3b3@26.0.29.236 (pending
transactions 0)
  Local tag : 00036bb9112700267368b9d7-423830f3
  Remote tag : 000785131249002902c91c61-0a9627ad
  State      : STATE_ESTABLISHED
Call leg 2 Zone : 8
  UAC call ID: 00078513-12490005-2ca7b914-2b5ea3b3@11.0.100.196:1050 (pending
transactions 0)
  Local tag : 000785131249002902c91c61-0a9627ad
  Remote tag : 00036bb9112700267368b9d7-423830f3
  State      : STATE_ESTABLISHED
```

## show security alg sip counters

<b>Syntax</b>	show security alg sip counters <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Session Initiation Protocol (SIP) Application Layer Gateway (ALG) counters.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all SIP ALG counters.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display SIP counters on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>sip</p> <p>clear security alg sip counters on page 666</p>
<b>List of Sample Output</b>	show security alg sip counters on page 782
<b>Output Fields</b>	Table 27 on page 780 lists the output fields for the <b>show security alg sip counters</b> command. Output fields are listed in the approximate order in which they appear.

**Table 27: show security alg sip counters Output Fields**

Field Name	Field Description
INVITE	Number of INVITE requests sent. An INVITE request is sent to invite another user to participate in a session.
CANCEL	Number of CANCEL requests sent. A user can send a CANCEL request to cancel a pending INVITE request. A CANCEL request has no effect if the SIP server processing the INVITE had sent a final response for the INVITE before it received the CANCEL
ACK	Number of ACK requests sent. The user from whom the INVITE originated sends an ACK request to confirm reception of the final response to the INVITE request.
BYE	Number of BYE requests sent. A user sends a BYE request to abandon a session. A BYE request from either user automatically terminates the session.
RR header exceeded max	Number of times the SIP ALG RR (Record-Route) headers exceeded the maximum limit.



**Table 27: show security alg sip counters Output Fields (continued)**

Field Name	Field Description
REGISTER	Number of REGISTER requests sent. A user sends a REGISTER request to a SIP registrar server to inform it of the current location of the user. A SIP registrar server records all the information it receives in REGISTER requests and makes this information available to any SIP server attempting to locate a user.
OPTIONS	Number of OPTIONS requests sent. An OPTION request is used by the User Agent (UA) to obtain information about the capabilities of the SIP proxy. A server responds with information about what methods, session description protocols, and message encoding it supports.
INFO	Number of INFO requests sent. AN INFO message is used to communicate mid-session signaling information along the signaling path for the call.
MESSAGE	Number of MESSAGE requests sent. SIP messages consist of requests from a client to a server and responses to the requests from a server to a client with the purpose of establishing a session (or a call).
NOTIFY	Number of NOTIFY requests sent. NOTIFY requests are sent to inform subscribers of changes in state to which the subscriber has a subscription.
PRACK	Number of PRACK requests sent. The PRACK request plays the same role as ACK, but for provisional responses.
PUBLISH	Number of PUBLISH requests sent. The PUBLISH request used for publishing event state. PUBLISH is similar to REGISTER in that it allows a user to create, modify, and remove state in another entity which manages this state on behalf of the user.
REFER	Number of REFER requests sent. A REFER request is used to refer the recipient (identified by the Request-URI) to a third party by the contact information provided in the request.
SUBSCRIBE	Number of SUBSCRIBE requests sent. A SUBSCRIBE request is used to request current state and state updates from a remote node.
UPDATE	Number of UPDATE requests sent. AN UPDATE request is used to create a temporary opening in the firewall (pinhole) for new or updates Session Description Protocol (SDP) information. The following fields are modified: Via, From, To, Call-ID, Contact, Route, and Record-Route.
BENOTIFY	Number of BENOTIFY requests sent. A BENOTIFY request is used to reduce the unnecessary SIP signaling traffic on application servers. Applications that do not need a response for a NOTIFY request can enhance performance by enabling BENOTIFY.
SERVICE	Number of SERVICE requests sent. The SERVICE method used by a SIP client to request a service of a SIP server. It is a standard SIP message and will be forwarded until it reaches the server or end user which is performing the service.
OTHER	Number of OTHER requests sent.
Total Pkt-in	Number of SIP ALG total packets received.
Total Pkt dropped on error	Number of SIP ALG total packets dropped while transmission and retransmission of messages.
Transaction error	Number of SIP ALG transaction errors.

**Table 27: show security alg sip counters Output Fields (continued)**

Field Name	Field Description
Call error	Number of SIP ALG call errors.
IP resolve error	Number of SIP ALG IP address resolution errors.
NAT error	Number of SIP ALG NAT errors.
Resource manager error	Number of SIP ALG resource manager errors.
Contact header exceeded max	Number of times the SIP ALG contact headers exceeded the maximum limit.
Invite Dropped due to call limit	Number of SIP ALG invite dropped due to call limits.
SIP msg not processed by stack	Number of SIP ALG stack errors.
SIP msg not processed by alg	Number of SIP ALG messages not processed by ALGs.
SIP unknown method dropped	Number of SIP ALG unknown method errors.
Decoding error	Number of SIP ALG decoding errors.
Request for disconnected call	Number of SIP ALG calls disconnected.
Request out of state	Number of SIP ALG messages out of state errors.

```

show security alg sip user@host> show security alg sip counters
counters SIP message counters(T:Transmit, RT:Retransmit):
  Method      T    1xx    2xx    3xx    4xx    5xx    6xx
              RT    RT     RT     RT     RT     RT     RT
  INVITE      0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  CANCEL      0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  ACK         0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  BYE         0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  REGISTER    0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  OPTIONS     0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  INFO        0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  MESSAGE     0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  NOTIFY      0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  PRACK       0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  PUBLISH     0    0      0      0      0      0      0
              0    0      0      0      0      0      0
  REFER       0    0      0      0      0      0      0
              0    0      0      0      0      0      0

```

SUBSCRIBE	0	0	0	0	0	0	0
	0	0	0	0	0	0	0
UPDATE	0	0	0	0	0	0	0
	0	0	0	0	0	0	0
BENOTIFY	0	0	0	0	0	0	0
	0	0	0	0	0	0	0
SERVICE	0	0	0	0	0	0	0
	0	0	0	0	0	0	0
OTHER	0	0	0	0	0	0	0
	0	0	0	0	0	0	0

## SIP Error Counters:

Total Pkt-in	:15
Total Pkt dropped on error	:0
Transaction error	:0
Call error	:0
IP resolve error	:0
NAT error	:0
Resource manager error	:0
RR header exceeded max	:0
Contact header exceeded max	:0
Invite Dropped due to call limit	:0
SIP msg not processed by stack	:0
SIP msg not processed by alg	:0
SIP unknown method dropped	:0
Decoding error	:0
Request for disconnected call	:0
Request out of state	:0

## show security alg sip rate

<b>Syntax</b>	show security alg sip rate <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display rate information for Session Initiation Protocol (SIP) Application Layer Protocol (ALG) messages.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all SIP ALG rate information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display SIP rate on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	sip
<b>List of Sample Output</b>	show security alg sip rate on page 784
<b>Output Fields</b>	Table 28 on page 784 lists the output fields for the <b>show security alg sip rate</b> command. Output fields are listed in the approximate order in which they appear.

**Table 28: show security alg sip rate Output Fields**

Field Name	Field Description
CPU ticks	SIP ALG CPU ticks per microsecond.
Time taken	Time, in microseconds, that the last SIP ALG message needed to transit the network.
Total time	Total time, in microseconds, during an interval of less than 10 minutes for the specified number of SIP ALG messages to transit the network.
Rate	Number of SIP ALG messages per second transiting the network.

```

show security alg sip  user@host> show security alg sip rate
rate                  CPU ticks per us is 166
                        Time taken for the last message is 1103 us

```

```
Total time taken for 3124 messages is 6221482 us (in less than 10 minutes)
Rate: 502 messages/second
```

## show security alg sip transactions

<b>Syntax</b>	show security alg sip transactions <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about Session Initiation Protocol (SIP) Application Layer Gateway (ALG) transactions.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all SIP ALG transactions.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display SIP transactions on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	sip
<b>List of Sample Output</b>	show security alg sip transactions on page 786
<b>Output Fields</b>	Table 29 on page 786 lists the output fields for the show security alg sip transaction command. Output fields are listed in the approximate order in which they appear.

**Table 29: show security alg sip transactions Output Fields**

Field Name	Field Description
UAS	SIP ALG User Agent Server transaction name.
UAC	ALG SIP User Agent Client transaction name.

```

show security alg sip transactions  user@host> show security alg sip transactions
Total number of transactions: 1
Transaction Name      Method    CSeq      State      Timeout  VIA RSC ID
UAS:tsx0x4b06ddf4    BYE       101       Proceeding -1        -
UAC:tsx0x4b06f610    BYE       101       Calling    27        8185

```

## show security alg sunrpc portmap

<b>Syntax</b>	show security alg sunrpc portmap
<b>Release Information</b>	Command introduced in Release 9.0 of JUNOS software.
<b>Description</b>	Display Sun Microsystems remote procedure call (RPC) ALG information.  This command is supported on J-series devices.
<b>Options</b>	portmap—Display Sun Microsystem remote procedure call (SUNRPC) mapping table information.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	sunrpc  clear security alg sunrpc portmap on page 667
<b>List of Sample Output</b>	show security alg sunrpc portmap on page 787
<b>Output Fields</b>	Table 30 on page 787 lists the output fields for the show security alg sunrpc portmap command. Output fields are listed in the approximate order in which they appear.

**Table 30: show security alg sunrpc portmap Output Fields**

Field Name	Field Description
IP	IP address of the server that maps to the program.
Port	Port number of the server that maps to the program.
Protocol	Protocol used to support the process.
Program	Program ID number.

```

show security alg sunrpc portmap
user@host> show security alg sunrpc portmap
IP          Port    Protocol Program
10.209.17.127 32835  TCP      100005
10.209.17.127 2049   UDP      100003
10.209.17.127 111    UDP      100000
10.209.17.127 111    TCP      100000

```

## show security firewall-authentication history

<b>Syntax</b>	show security firewall-authentication history <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display security firewall authentication history information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display history of firewall authentication information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display all firewall authentication history on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	firewall-authentication (Security)  clear security firewall-authentication history on page 668
<b>List of Sample Output</b>	show security firewall-authentication history on page 789 show security firewall-authentication history node all on page 789
<b>Output Fields</b>	Table 31 on page 788 lists the output fields for the <b>show security firewall-authentication history</b> command. Output fields are listed in the approximate order in which they appear.

**Table 31: show security firewall-authentication history Output Fields**

Field Name	Field Description
Authentications	Number of authentications.
Id	Identification number.
Source IP	IP address of the authentication source.
Date	Authentication date.
Time	Authentication time.
Duration	Authentication duration.



**Table 31: show security firewall-authentication history Output Fields** (continued)

Field Name	Field Description
Status	Authentication status success or failure.
User	Name of the user.

```

show security      user@host> show security firewall-authentication history
firewall-authentication History of firewall authentication data:
history             Authentications: 1
                        Id Source Ip      Date      Time      Duration  Status  User
                        1 211.0.0.6      2007-04-03 11:43:06 00:00:45  Success hello

show security      user@host> show security firewall-authentication history node all
firewall-authentication node0:
history node all -----
History of firewall authentication data:
Authentications: 2
Id Source Ip      Date      Time      Duration  Status  User
1 100.0.0.1      2008-01-04 12:00:10 0:05:49  Success  local1
2 100.0.0.1      2008-01-04 14:36:52 0:01:03  Success  local1
node1:
-----
History of firewall authentication data:
Authentications: 1
      Id Source Ip      Date      Time      Duration  Status  User
      1 100.0.0.1      2008-01-04 14:59:43 1193046:06: Success local1

```

## show security firewall-authentication history address

<b>Syntax</b>	show security firewall-authentication history address <i>ip-address</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display security firewall authentication history for this source IP address.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>address <i>ip-address</i> —IP address of the authentication source.</p> <p>none—Display all firewall authentication history for this address.</p> <p>node—(Optional) For chassis cluster configurations, display firewall authentication history for this address on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>firewall-authentication (Security)</p> <p>clear security firewall-authentication history address on page 669</p>
<b>List of Sample Output</b>	<p>show security firewall-authentication history address 4.4.4.2 on page 791</p> <p>show security firewall-authentication history address 100.0.0.1 node local on page 791</p>
<b>Output Fields</b>	Table 32 on page 790 lists the output fields for the <b>show security firewall-authentication history address</b> command. Output fields are listed in the approximate order in which they appear.

**Table 32: show security firewall-authentication history address Output Fields**

Field Name	Field Description
Username	User ID.
Source IP	IP address of the authentication source.
Authentication state	Status of authentication (success or failure).
Authentication method	Path chosen for authentication.
Access start date	Date when user authenticated.

**Table 32: show security firewall-authentication history address Output Fields** (continued)

Field Name	Field Description
Access start time	Time when user authenticated.
Duration of user access	Time duration of the accessing firewall.
Policy name	Name of the policy.
Source zone	User traffic received from the zone.
Destination zone	User traffic destined to the zone.
Access profile	Name of profile used for authentication.
Bytes sent by this user	Number of bytes sent by the user.
Bytes received by this user	Number of bytes received by the user.

```

show security      user@host> show security firewall-authentication history address 4.4.4.2
firewall-authentication
history address 4.4.4.2
Username: u1
Source IP: 4.4.4.2
Authentication state: Success
Authentication method: Pass-through using HTTP
Access start date: 2007-09-12
Access start time: 15:33:29
Duration of user access: 0:00:48
Policy name: Z1-Z2
Source zone: Z1
Destination zone: Z2
Access profile: profile-local
Bytes sent by this user: 0
Bytes received by this user: 449

show security      user@host> show security firewall-authentication history address 100.0.0.1 node
firewall-authentication
history address    local
100.0.0.1 node local
node0:
-----
Username: local1
Source IP: 100.0.0.1
Authentication state: Success
Authentication method: Pass-through using Telnet
Access start date: 2008-01-04
Access start time: 12:00:10
Duration of user access: 0:05:49
Policy name: POL1
Source zone: z1
Destination zone: z2
Access profile: p1
Bytes sent by this user: 0
Bytes received by this user: 0
Username: local1
Source IP: 100.0.0.1
Authentication state: Success
Authentication method: Pass-through using Telnet
Access start date: 2008-01-04

```

```
Access start time: 14:36:52
Duration of user access: 0:01:03
Policy name: POL1
Source zone: z1
Destination zone: z2
Access profile: p1
Bytes sent by this user: 2178
Bytes received by this user: 4172
```

## show security firewall-authentication history identifier

<b>Syntax</b>	show security firewall-authentication history identifier <i>identifier</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display security firewall authentication history information for the authentication with this identifier.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><b>identifier</b> <i>identifier</i>—Identifying number of the authentication process.</p> <p><b>none</b>—Display all firewall authentication history information for the authentication with this identifier.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display firewall authentication history on a specific node for the authentication with this identifier.</p> <ul style="list-style-type: none"> <li>■ <b>node-id</b> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>firewall-authentication (Security)</p> <p>clear security firewall-authentication history identifier on page 670</p>
<b>List of Sample Output</b>	<p>show security firewall-authentication history identifier 1 on page 794</p> <p>show security firewall-authentication identifier 1 node primary on page 794</p>
<b>Output Fields</b>	Table 33 on page 793 lists the output fields for the <b>show security firewall-authentication history identifier</b> command. Output fields are listed in the approximate order in which they appear.

**Table 33: show security firewall-authentication history identifier Output Fields**

Field Name	Field Description
Username	User ID.
Source IP	IP address of the authentication source.
Authentication state	Status of authentication (success or failure).
Authentication method	Path chosen for authentication.

**Table 33: show security firewall-authentication history identifier Output Fields** (continued)

Field Name	Field Description
Access start date	Date when user authenticated.
Access start time	Time when user authenticated.
Duration of user access	Time duration of the accessing firewall.
Policy index	Identification number of the policy.
Policy name	Name of the policy.
Source zone	User traffic received from the zone.
Destination zone	User traffic destined to the zone.
Access profile	Name of profile used for authentication.
Bytes sent by this user	Number of bytes sent by the user.
Bytes received by this user	Number of bytes received by the user.
Client-groups	Name of the client group.

**show security  
firewall-authentication  
history identifier 1**

```
user@host> show security firewall-authentication history identifier 1
Username: hello
Source IP: 211.0.0.6
Authentication state: Success
Authentication method: Pass-through using Telnet
Access start date: 2007-04-03
Access start time: 11:43:06
Duration of user access: 00:00:45
Policy index: 4
Source zone: z2
Destination zone: z1
Access profile: profile1
Bytes sent by this user: 0
Bytes received by this user: 1050
Client-groups: Sunnyvale Bangalore
```

**show security  
firewall-authentication  
identifier 1 node primary**

```
user@host> show security firewall-authentication history identifier 1 node primary
node0:
-----
Username: local1
Source IP: 100.0.0.1
Authentication state: Success
Authentication method: Pass-through using Telnet
Access start date: 2008-01-04
Access start time: 12:00:10
Duration of user access: 0:05:49
Policy name: POL1
Source zone: z1
Destination zone: z2
Access profile: p1
```

```
Bytes sent by this user: 0  
Bytes received by this user: 0
```

## show security firewall-authentication users

<b>Syntax</b>	show security firewall-authentication users <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display firewall authentication details about all users.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display details about all firewall authentication users.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display firewall authentication details for all users on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>firewall-authentication (Security)</p> <p>clear security firewall-authentication users on page 671</p>
<b>List of Sample Output</b>	<p>show security firewall-authentication users on page 797</p> <p>show security firewall-authentication users node 0 on page 797</p> <p>show security firewall-authentication users node all on page 797</p>
<b>Output Fields</b>	Table 34 on page 796 lists the output fields for the <b>show security firewall-authentication users</b> command. Output fields are listed in the approximate order in which they appear.

**Table 34: show security firewall-authentication users Output Fields**

Field Name	Field Description
Total users in table	Gives count of how many entries/users the command will display.
Id	Identification number.
Source IP	IP address of the authentication source.
Src zone	User traffic received from the zone.
Dst zone	User traffic destined to the zone.
Profile	Name of profile used for authentication.



**Table 34: show security firewall-authentication users Output Fields** (continued)

Field Name	Field Description
Age	Idle timeout for the user.
Status	Authentication status success or failure.
User	Name of the user.

```

show security      user@host> show security firewall-authentication users
firewall-authentication
users              Firewall authentication data:
                    Total users in table: 1
                    Id Source Ip      Src zone Dst zone Profile   Age Status  User
                    1 10.0.0.1       z1      z2      p1          0 Success local1

```

```

show security      user@host> show security firewall-authentication users node 0
firewall-authentication
users node 0      node0:
                    -----
                    Firewall authentication data:
                    Total users in table: 1
                    Id Source Ip      Src zone Dst zone Profile   Age Status  User
                    3 100.0.0.1       z1      z2      p1          1 Success local1

```

```

show security      user@host> show security firewall-authentication users node all
firewall-authentication
users node all    node0:
                    -----
                    Firewall authentication data:
                    Total users in table: 1
                    Id Source Ip      Src zone Dst zone Profile   Age Status  User
                    3 100.0.0.1       z1      z2      p1          1 Success local1

                    node1:
                    -----
                    Firewall authentication data:
                    Total users in table: 1
                    Id Source Ip      Src zone Dst zone Profile   Age Status  User
                    2 100.0.0.1       z1      z2      p1          1 Success local1

```

## show security firewall-authentication users address

<b>Syntax</b>	show security firewall-authentication users address <i>ip-address</i> <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about the users at the specified IP address that are currently authenticated.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	address <i>ip-address</i> —IP address of the authentication source.  none—Display all the firewall authentication information for users at this IP address.  node—(Optional) For chassis cluster configurations, display user firewall authentication entries on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	firewall-authentication (Security)  clear security firewall-authentication users address on page 672
<b>List of Sample Output</b>	show security firewall-authentication users address 211.0.0.6 on page 799 show security firewall-authentication users address 100.0.0.1 node local on page 799
<b>Output Fields</b>	Table 35 on page 798 lists the output fields for the <b>show security firewall-authentication users address</b> command. Output fields are listed in the approximate order in which they appear.

**Table 35: show security firewall-authentication users address Output Fields**

Field Name	Field Description
Username	User ID.
Source IP	IP address of the authentication source.
Authentication state	Status of authentication (success or failure).
Authentication method	Path chosen for authentication.
Access time remaining	Duration for which the connection exists.

**Table 35: show security firewall-authentication users address Output Fields** *(continued)*

Field Name	Field Description
Source zone	User traffic received from the zone.
Destination zone	User traffic destined to the zone.
Policy index	Identification number of the policy.
Policy name	Name of the policy.
Access profile	Name of profile used for authentication.
Interface Name	Name of the interface.
Bytes sent by this user	Number of bytes sent by the user.
Bytes received by this user	Number of bytes received by the user.
Client-groups	Name of the client group.

```

show security      user@host>show security firewall-authentication users address 211.0.0.6
firewall-authentication
users address 211.0.0.6  Username: hello
                          Source IP: 211.0.0.6
                          Authentication state: Success
                          Authentication method: Pass-through using Telnet
                          Access time remaining: 0
                          Source zone: z2
                          Destination zone: z1
                          Policy index: 5
                          Access profile: profile1
                          Interface Name: ge-0/0/2.0
                          Bytes sent by this user: 0
                          Bytes received by this user: 0
                          Client-groups: Sunnyvale Bangalore

```

```

show security      user@host> show security firewall-authentication users address 100.0.0.1 node
firewall-authentication local
users address 100.0.0.1 node0:
node local          -----
                          Username: local1
                          Source IP: 100.0.0.1
                          Authentication state: Success
                          Authentication method: Pass-through using Telnet
                          Age: 2
                          Access time remaining: 4
                          Source zone: z1
                          Destination zone: z2
                          Policy name: POL1
                          Access profile: p1
                          Interface Name: reth1.0
                          Bytes sent by this user: 614
                          Bytes received by this user: 1880

```

## show security firewall-authentication users identifier

<b>Syntax</b>	show security firewall-authentication users identifier <i>identifier</i> <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display firewall authentication details about the user with this identification number.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><b>identifier</b><i>identifier</i>—Identification number of the user for which to display authentication details.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display the firewall authentication details security firewall authentication entry on a specific node (device) in the cluster for the user with this identification number.</p> <ul style="list-style-type: none"> <li>■ <b>node-id</b> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>firewall-authentication (Security)</p> <p>clear security firewall-authentication users identifier on page 673</p>
<b>List of Sample Output</b>	<p>show security firewall-authentication users identifier 3 on page 801</p> <p>show security firewall-authentication users identifier 3 node primary on page 801</p>
<b>Output Fields</b>	Table 36 on page 800 lists the output fields for the <b>show security firewall-authentication users identifier</b> command. Output fields are listed in the approximate order in which they appear.

**Table 36: show security firewall-authentication users identifier Output Fields**

Field Name	Field Description
Username	User ID.
Source IP	IP address of the authentication source.
Authentication state	Status of authentication (success or failure).
Authentication method	Path chosen for authentication.
Age	Idle timeout for the user.

**Table 36: show security firewall-authentication users identifier Output Fields** (continued)

Field Name	Field Description
Access time remaining	Duration for which the connection exists.
Source zone	User traffic received from the zone.
Destination Zone	User traffic destined to the zone.
Policy Name	Name of the policy.
Access profile	Name of profile used for authentication.
Interface Name	Name of the interface
Bytes sent by this user	Number of bytes sent by the user.
Bytes received by this user	Number of bytes received by the user.

**show security  
firewall-authentication  
users identifier 3**

```
user@host> show security firewall-authentication users identifier 3
Username: u1
Source IP: 4.4.4.2
Authentication state: Success
Authentication method: Pass-through using HTTP
Age: 1
Access time remaining: 254
Source zone: Z1
Destination zone: Z2
Policy name: Z1-Z2
Access profile: profile-local
Interface Name: ge-0/0/1.0
Bytes sent by this user: 0
Bytes received by this user: 449
```

**show security  
firewall-authentication  
users identifier 3 node  
primary**

```
user@host> show security firewall-authentication users identifier 3 node primary
node0:
-----
Username: local1
Source IP: 100.0.0.1
Authentication state: Success
Authentication method: Pass-through using Telnet
Age: 1
Access time remaining: 5
Source zone: z1
Destination zone: z2
Policy name: POL1
Access profile: p1
Interface Name: reth1.0
Bytes sent by this user: 614
Bytes received by this user: 1880
```

## show security flow gate

<b>Syntax</b>	show security flow gate <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	<p>Display information about temporary openings known as pinholes or gates in the security firewall.</p> <p>Pinholes are used by applications that commonly have both control and data sessions and must create openings in the firewall for the data sessions based on information from the parent sessions.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>node</b>—(Optional) For chassis cluster configurations, display gate information on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	flow
<b>List of Sample Output</b>	<p>show security flow gate on page 803</p> <p>show security flow gate node 0 on page 804</p>
<b>Output Fields</b>	Table 37 on page 802 lists the output fields for the <b>show security flow gate</b> command. Output fields are listed in the approximate order in which they appear.

**Table 37: show security flow gate Output Fields**

Field Name	Field Description
Hole	Range of flows permitted by the pinhole.
Translated	<p>Tuples used to create the session if it matches the pinhole.</p> <ul style="list-style-type: none"> <li>■ Source address and port</li> <li>■ Destination address and port</li> </ul>
Protocol	Application protocol, such as UDP or TCP.
Application	Name of the application.
Age	Idle timeout for the pinhole.

**Table 37: show security flow gate Output Fields** *(continued)*

Field Name	Field Description
Flags	Internal debug flags for the pinhole.
Zone	Incoming zone.
Reference count	Number of resource-manager references to the pinhole.
Resource	Resource manager information about the pinhole.

```

user@host> show security flow gate
Hole: 0.0.0.0-0.0.0.0/0-0->40.1.1.252-40.1.1.252/64515-64515
Translated: 0.0.0.0/0->11.0.31.161/25415
Protocol: udp
Application: none/0
Age: 101 seconds
Flags: 0xe001
Zone: untrust
Reference count: 1
Resource: 5-1024-8185
Hole: 0.0.0.0-0.0.0.0/0-0->40.1.1.252-40.1.1.252/1046-1046
Translated: 40.1.1.250/36039->11.0.31.161/5060
Protocol: udp
Application: junos-sip/63
Age: 65535 seconds
Flags: 0xe200
Zone: untrust
Reference count: 1
Resource: 5-1024-8189
Hole: 0.0.0.0-0.0.0.0/0-0->40.1.1.5-40.1.1.5/24101-24101
Translated: 0.0.0.0/0->40.1.1.5/24101
Protocol: udp
Application: none/0
Age: 93 seconds
Flags: 0xe001
Zone: trust
Reference count: 1
Resource: 5-1024-8188
Hole: 0.0.0.0-0.0.0.0/0-0->40.1.1.5-40.1.1.5/24100-24100
Translated: 0.0.0.0/0->40.1.1.5/24100
Protocol: udp
Application: none/0
Age: 93 seconds
Flags: 0xe001
Zone: trust
Reference count: 1
Resource: 5-1024-8191
Hole: 0.0.0.0-0.0.0.0/0-0->40.1.1.250-40.1.1.250/5060-5060
Translated: 0.0.0.0/0->40.1.1.250/5060
Protocol: udp
Application: junos-sip/63
Age: 65535 seconds
Flags: 0xe200
Zone: trust
Reference count: 1
Resource: 5-1024-8190

```

```
show security flow gate node 0
user@host> show security flow gate node 0
node0:
```

```
-----
Hole: 0.0.0.0-0.0.0.0/0-0->11.0.30.21-11.0.30.21/24923-24923
Translated: 0.0.0.0/0->11.0.30.21/24923
Protocol: udp
Application: none/0
Age: 89 seconds
Flags: 0xe001
Zone: trust
Reference count: 1
Resource: 5-1024-8192
Hole: 0.0.0.0-0.0.0.0/0-0->11.0.54.20-11.0.54.20/5060-5060
Translated: 0.0.0.0/0->11.0.54.20/5060
Protocol: udp
Application: junos-sip/63
Age: 65535 seconds
Flags: 0xe200
Zone: trust
Reference count: 1
Resource: 5-1024-8188

Hole: 0.0.0.0-0.0.0.0/0-0->11.0.100.196-11.0.100.196/64511-64511
Translated: 0.0.0.0/0->26.0.29.236/25897
Protocol: udp
Application: none/0
Age: 88 seconds
Flags: 0xe001
Zone: dmz
Reference count: 1
Resource: 5-1024-8187

Hole: 0.0.0.0-0.0.0.0/0-0->11.0.100.196-11.0.100.196/64510-64510
Translated: 0.0.0.0/0->26.0.29.236/25896
Protocol: udp
Application: none/0
Age: 88 seconds
Flags: 0xe001
Zone: dmz
Reference count: 1
Resource: 5-1024-8190

Hole: 0.0.0.0-0.0.0.0/0-0->11.0.100.196-11.0.100.196/1024-1024
Translated: 11.0.54.20/41968->26.0.29.236/5060
Protocol: udp
Application: junos-sip/63
Age: 65535 seconds
Flags: 0xe200
Zone: dmz
Reference count: 1
Resource: 5-1024-8186
```



## show security flow session

<b>Syntax</b>	show security flow session node ( <i>node-id</i>   all   local   primary)
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about all currently active security sessions on the device.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display information about all active sessions.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display all active sessions on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>flow</p> <p>clear security flow session all on page 674</p>
<b>List of Sample Output</b>	<p>show security flow session on page 806</p> <p>show security flow session node all on page 806</p>
<b>Output Fields</b>	Table 38 on page 805 lists the output fields for the <b>show security flow session</b> command. Output fields are listed in the approximate order in which they appear.

**Table 38: show security flow session Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. Use this ID to get more information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```

show security flow session
user@host> show security flow session
Session ID: 2102, Policy name: self-traffic-policy/1, Timeout: 272
  In: 172.24.68.74/3428 --> 10.157.84.52/23;tcp, If: ge-0/0/0.0
  Out: 10.157.84.52/23 --> 172.24.68.74/3428;tcp, If: .local..0
Session ID: 2111, Policy name: self-traffic-policy/1, Timeout: 1800
  In: 172.24.68.97/3175 --> 10.157.84.52/23;tcp, If: ge-0/0/0.0
  Out: 10.157.84.52/23 --> 172.24.68.97/3175;tcp, If: .local..0
Session ID: 2112, Policy name: self-traffic-policy/1, Timeout: 1781
  In: 172.24.68.97/3176 --> 10.157.84.52/23;tcp, If: ge-0/0/0.0
  Out: 10.157.84.52/23 --> 172.24.68.97/3176;tcp, If: .local..0
3 sessions displayed

```

```

show security flow session node all
user@host> show security flow session node all
node0:
-----
Session ID: 1, Policy name: sfw1/4, State: Active, Timeout: 60
  In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1
  Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1
Session ID: 2, Policy name: sfw2/5, State: Active, Timeout: 60
  In: 1.1.2.2/2000 --> 11.11.2.2/40000;udp, If: reth0.2
  Out: 11.11.2.2/40000 --> 1.1.2.2/2000;udp, If: reth1.2
Session ID: 3, Policy name: sfw3/6, State: Active, Timeout: 60
  In: 1.1.3.2/2000 --> 11.11.3.2/40000;udp, If: reth0.3
  Out: 11.11.3.2/40000 --> 1.1.3.2/2000;udp, If: reth1.3
Session ID: 4, Policy name: sfw4/7, State: Active, Timeout: 60
  In: 1.1.4.2/2000 --> 11.11.4.2/40000;udp, If: reth0.4
  Out: 11.11.4.2/40000 --> 1.1.4.2/2000;udp, If: reth1.4
4 sessions displayed
node1:
-----

```

```

Session ID: 1, Policy name: sfw1/4, State: Backup, Timeout: 482
  In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1
  Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1
Session ID: 2, Policy name: sfw2/5, State: Backup, Timeout: 476
  In: 1.1.2.2/2000 --> 11.11.2.2/40000;udp, If: reth0.2
  Out: 11.11.2.2/40000 --> 1.1.2.2/2000;udp, If: reth1.2
Session ID: 3, Policy name: sfw3/6, State: Backup, Timeout: 480
  In: 1.1.3.2/2000 --> 11.11.3.2/40000;udp, If: reth0.3
  Out: 11.11.3.2/40000 --> 1.1.3.2/2000;udp, If: reth1.3
Session ID: 4, Policy name: sfw4/7, State: Backup, Timeout: 482
  In: 1.1.4.2/2000 --> 11.11.4.2/40000;udp, If: reth0.4
  Out: 11.11.4.2/40000 --> 1.1.4.2/2000;udp, If: reth1.4
4 sessions displayed

```

## show security flow session application

---

<b>Syntax</b>	show security flow session application <i>application-name</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about each session of the specified application type.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><i>application-name</i> —Type of application about which to display sessions information. Possible values are</p> <ul style="list-style-type: none"> <li>■ dnsDomain Name System</li> <li>■ ftpFile Transfer Protocol</li> <li>■ ignoreIgnore application type</li> <li>■ mgcp-caMedia Gateway Control Protocol with Call Agent</li> <li>■ mgcp-uaMGCP with User Agent</li> <li>■ pptpPoint-to-Point Tunneling Protocol</li> <li>■ q931ISDN connection control protocol</li> <li>■ rasRAS</li> <li>■ realaudioRealAudio</li> <li>■ rshUNIX remote shell services</li> <li>■ rtspReal-Time Streaming Protocol</li> <li>■ sccpSkinny Client Control Protocol</li> <li>■ sipSession Initiation Protocol</li> <li>■ sqlnet-v2Oracle SQLNET</li> <li>■ talkTALK program</li> <li>■ tftpTrivial File Transfer Protocol</li> </ul> <p><b>node</b>—(Optional) For chassis cluster configurations, display sessions for the specified application type or application set on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>

<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session application on page 675
<b>List of Sample Output</b>	show security flow session application ftp on page 808 show security flow session application sip node primary on page 808
<b>Output Fields</b>	Table 39 on page 808 lists the output fields for the <b>show security flow session application</b> command. Output fields are listed in the approximate order in which they appear.

**Table 39: show security flow session application Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```

show security flow session application ftp
user@host> show security flow session application ftp
Session ID: 33, Policy name: default-policy/2, Timeout: 1492
In: 10.10.10.1/2851 --> 192.168.0.2/21;tcp, If: t1-1/0/0.0
Out: 192.168.0.2/21 --> 10.10.10.1/2851;tcp, If: ge-0/0/1.0

```

```

show security flow session application sip node primary
user@host> show security flow session application sip node primary
node0:
-----
Session ID: 246, Policy name: trust_to_dmz/4, State: Active, Timeout: 6
In: 26.0.29.236/50039 --> 11.0.54.20/5060;udp, If: reth0.0
Out: 11.0.54.20/5060 --> 11.0.100.196/1047;udp, If: reth2.0

Session ID: 253, Policy name: trust_to_dmz/4, State: Active, Timeout: 4
In: 26.0.29.236/50055 --> 11.0.54.20/5060;udp, If: reth0.0
Out: 11.0.54.20/5060 --> 11.0.100.196/1048;udp, If: reth2.0
Session ID: 254, Policy name: trust_to_dmz/4, State: Active, Timeout: 64
Resource information : SIP ALG, 1024, 8186
In: 11.0.54.20/41968 --> 11.0.100.196/1024;udp, If: reth2.0
Out: 26.0.29.236/5060 --> 11.0.54.20/41968;udp, If: reth0.0

3 sessions displayed

```

## show security flow session destination-port

<b>Syntax</b>	show security flow session destination-port <i>destination-port-number</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about each session that uses the specified destination port.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>destination-port-number</i> —Number of the destination port about which to display sessions information.  <b>Range:</b> 1 through 65535  <b>node</b> —(Optional) For chassis cluster configurations, display sessions for the specified destination port on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session destination-port on page 677
<b>List of Sample Output</b>	show security flow session destination-port 21 on page 810 show security flow session destination-port 40000 node local on page 810
<b>Output Fields</b>	Table 40 on page 809 lists the output fields for the <b>show security flow session destination-port</b> command. Output fields are listed in the approximate order in which they appear.

**Table 40: show security flow session destination-port Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```

show security flow      user@host> show security flow session destination-port 21
session destination-port Session ID: 33, Policy name: default-policy/2, Timeout: 1492
21      In: 10.10.10.1/2851 --> 192.168.0.2/21;tcp, If: t1-1/0/0.0
      Out: 192.168.0.2/21 --> 10.10.10.1/2851;tcp, If: ge-0/0/1.0

show security flow      user@host> show security flow session destination-port 40000 node local
session destination-port node0:
40000 node local -----
      Session ID: 1, Policy name: sfw1/4, State: Active, Timeout: 60
      In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1
      Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1
      Session ID: 2, Policy name: sfw2/5, State: Active, Timeout: 60
      In: 1.1.2.2/2000 --> 11.11.2.2/40000;udp, If: reth0.2
      Out: 11.11.2.2/40000 --> 1.1.2.2/2000;udp, If: reth1.2
      Session ID: 3, Policy name: sfw3/6, State: Active, Timeout: 60
      In: 1.1.3.2/2000 --> 11.11.3.2/40000;udp, If: reth0.3
      Out: 11.11.3.2/40000 --> 1.1.3.2/2000;udp, If: reth1.3
      Session ID: 4, Policy name: sfw4/7, State: Active, Timeout: 60
      In: 1.1.4.2/2000 --> 11.11.4.2/40000;udp, If: reth0.4
      Out: 11.11.4.2/40000 --> 1.1.4.2/2000;udp, If: reth1.4
      4 sessions displayed

```

## show security flow session destination-prefix

<b>Syntax</b>	show security flow session destination-prefix <i>destination-IP-prefix</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about each session that matches the specified IPv4 destination prefix.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>destination-IP-prefix</i> —Destination IPv4 prefix or address about which to display session information.  <i>node</i> —(Optional) For chassis cluster configurations, display sessions that match the specified destination prefix on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session destination-prefix on page 678
<b>List of Sample Output</b>	show security flow session destination-prefix 192.168/16 on page 812 show security flow session destination-prefix 11.11.1.2 node primary on page 812
<b>Output Fields</b>	Table 41 on page 811 lists the output fields for the <b>show security flow session destination-prefix</b> command. Output fields are listed in the approximate order in which they appear.

**Table 41: show security flow session destination-prefix Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```

show security flow      user@host> show security flow session destination-prefix 192.168/16
session                Session ID: 33, Policy name: default-policy/2, Timeout: 1492
destination-prefix      In: 10.10.10.1/2851 --> 192.168.0.2/21;tcp, If: t1-1/0/0.0
192.168/16             Out: 192.168.0.2/21 --> 10.10.10.1/2851;tcp, If: ge-0/0/1.0

show security flow      user@host> show security flow session destination-prefix 11.11.1.2 node primary
session                node0:
destination-prefix      -----
11.11.1.2 node primary Session ID: 1, Policy name: sfw1/4, State: Active, Timeout: 60
                        In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1
                        Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1
                        1 sessions displayed

```



## show security flow session interface

<b>Syntax</b>	show security flow session interface <i>interface-name</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about each session that uses the specified interface. The interface name can be a session's incoming or outgoing interface.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>interface-name</i> —Name of the interface on the router for which to display sessions information.  <i>node</i> —(Optional) For chassis cluster configurations, display sessions that use the specified interface on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i>—Identification number of the node. It can be 0 or 1.</li> <li>■ <i>all</i>—Display information about all nodes.</li> <li>■ <i>local</i>—Display information about the local node.</li> <li>■ <i>primary</i>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session interface on page 679
<b>List of Sample Output</b>	show security flow session interface Gigabit Ethernet on page 814 show security flow session interface reth0.1 node local on page 814
<b>Output Fields</b>	Table 42 on page 813 lists the output fields for the <b>show security flow session interface</b> command. Output fields are listed in the approximate order in which they appear.

**Table 42: show security flow session interface Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (source and destination IP address, application protocol, and interface).
Out	Reverse flow (source and destination IP address, application protocol, and interface).

```

show security flow      user@host> show security flow session interface ge-0/0/0.0
session interface GigabitEthernet
                               Session ID: 1658, Policy name: self-traffic-policy/1, Timeout: 1800
                               In: 172.23.9.135/3998 --> 10.157.84.52/23;tcp, If: ge-0/0/0.0
                               Out: 10.157.84.52/23 --> 172.23.9.135/3998;tcp, If: .local..0
                               1 sessions displayed

show security flow      user@host> show security flow session interface reth0.1 node local
session interface      node0:
reth0.1 node local
                               -----
                               Session ID: 1, Policy name: sfw1/4, State: Active, Timeout: 60
                               In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1
                               Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1
                               1 sessions displayed

```

## show security flow session protocol

---

**Syntax** show security flow session protocol ( *protocol-name* | *protocol-number* )  
<node ( *node-id* | all | local | primary )>

**Release Information** Command introduced in Release 8.5 of JUNOS software; **node** options added in Release 9.0 of JUNOS software.

**Description** Display information about each session that uses the specified protocol.

This command is supported on J-series and SRX-series devices.

**Options** *protocol-name* —(Optional) Protocol to use as a sessions filter. Information about sessions that use this protocol is displayed. Possible protocols are

- ah—IP Security Authentication Header
- egp—Exterior gateway protocol
- esp—IPsec Encapsulating Security Payload
- gre—Generic routing encapsulation
- icmp—Internet Control Message Protocol
- igmp—Internet Group Management Protocol
- ipip—IP over IP
- ospf—Open Shortest Path First
- pim—Protocol Independent Multicast
- rsvp—Resource Reservation Protocol
- sctp—Stream Control Transmission Protocol
- tcp—Transmission Control Protocol
- udp—User Datagram Protocol

*protocol-number* —(Optional) Numeric protocol value. For a complete list of possible numeric values, see RFC 1700, *Assigned Numbers (for the Internet Protocol Suite)*.

**Range:** 0 through 255

**node**—(Optional) For chassis cluster configurations, display sessions that use the specified protocol on a specific node.

- *node-id* —Identification number of the node. It can be 0 or 1.
- all—Display information about all nodes.
- local—Display information about the local node.
- primary—Display information about the primary node.

**Required Privilege Level** view

**Related Topics** clear security flow session protocol on page 680

**List of Sample Output** show security flow session protocol udp on page 816  
 show security flow session protocol tcp on page 816  
 show security flow session protocol udp node primary on page 816

**Output Fields** Table 43 on page 816 lists the output fields for the show security flow session protocol command. Output fields are listed in the approximate order in which they appear.

**Table 43: show security flow session protocol Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (Source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (Source and destination IP addresses, application protocol, and interface).

**show security flow session protocol udp** user@host> **show security flow session protocol udp**  
 Session ID: 1, Policy name: self-traffic-policy/1, Timeout: 57  
 In: 0.0.0.0/68 --> 255.255.255.255/67;udp, If: ge-0/0/0.0  
 Out: 255.255.255.255/67 --> 0.0.0.0/68;udp, If: .local..0

**show security flow session protocol tcp** user@host> **show security flow session protocol tcp**  
 Session ID: 4135, Policy name: N/A, Timeout: 1799  
 In: 10.0.0.96/1026 --> 10.0.0.1/5000;tcp, If: pc-5/0/0.16383  
 Out: 10.0.0.1/5000 --> 10.0.0.96/1026;tcp, If: .local..0  
 Session ID: 6301, Policy name: wx2ut, Timeout: 1726  
 In: 2.2.2.1/1865 --> 90.0.0.5/3578;tcp, If: wx-5/0/0.0  
 Out: 90.0.0.5/3578 --> 2.2.2.1/1865;tcp, If: e1-2/0/0.0  
 Session ID: 6307, Policy name: ut2wx, Timeout: 1726  
 In: 90.0.0.5/3331 --> 2.2.2.1/3578;tcp, If: e1-2/0/0.0  
 Out: 2.2.2.1/3578 --> 90.0.0.5/3331;tcp, If: wx-5/0/0.0  
 Session ID: 6329, Policy name: ut2wx, Timeout: 494  
 In: 90.0.0.6/3336 --> 2.2.2.3/3578;tcp, If: e1-2/0/1.0  
 Out: 2.2.2.3/3578 --> 90.0.0.6/3336;tcp, If: wx-5/0/0.0  
 Session ID: 6348, Policy name: ut2t\_red, Timeout: 1605  
 In: 90.0.0.1/3972 --> 20.0.0.1/21;tcp, If: e1-2/0/0.0  
 Out: 20.0.0.1/21 --> 90.0.0.1/3972;tcp, If: ge-0/0/1.0  
 Session ID: 6355, Policy name: t2ut\_red, Timeout: 1726  
 In: 20.0.0.1/1104 --> 90.0.0.1/21;tcp, If: ge-0/0/1.0  
 Out: 90.0.0.1/21 --> 20.0.0.1/1104;tcp, If: e1-2/0/0.0  
 6 sessions displayed

**show security flow session protocol udp node primary** user@host> **show security flow session protocol udp node primary**  
 node0:  
 -----  
 Session ID: 1, Policy name: sfw1/4, State: Active, Timeout: 60  
 In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1  
 Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1

```
Session ID: 2, Policy name: sfw2/5, State: Active, Timeout: 60
  In: 1.1.2.2/2000 --> 11.11.2.2/40000;udp, If: reth0.2
  Out: 11.11.2.2/40000 --> 1.1.2.2/2000;udp, If: reth1.2
Session ID: 3, Policy name: sfw3/6, State: Active, Timeout: 60
  In: 1.1.3.2/2000 --> 11.11.3.2/40000;udp, If: reth0.3
  Out: 11.11.3.2/40000 --> 1.1.3.2/2000;udp, If: reth1.3
Session ID: 4, Policy name: sfw4/7, State: Active, Timeout: 60
  In: 1.1.4.2/2000 --> 11.11.4.2/40000;udp, If: reth0.4
  Out: 11.11.4.2/40000 --> 1.1.4.2/2000;udp, If: reth1.4
4 sessions displayed
```

## show security flow session resource-manager

<b>Syntax</b>	show security flow session resource-manager <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about sessions created by the resource manager.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all resource manager sessions.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display resource manager sessions on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session resource-manager on page 682
<b>List of Sample Output</b>	<p>show security flow session resource-manager on page 819</p> <p>show security flow session resource-manager node 0 on page 819</p> <p>show security flow session resource-manager node 1 on page 819</p>
<b>Output Fields</b>	Table 44 on page 818 lists the output fields for the <b>show security flow session resource-manager</b> command. Output fields are listed in the approximate order in which they appear.

**Table 44: show security flow session resource-manager Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
Resource information	Information about the session particular to the resource manager, including the name of the ALG, the group ID, and the resource ID.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```

show security flow      user@host> show security flow session resource-manager
session                Session ID: 2218, Policy name: foo/4, Timeout: 60
resource-manager      Resource information : MGCP ALG, 2047, 8188
                          In: 12.0.102.26/28072 --> 11.0.101.236/23252;udp, If: ge-0/0/2.0
                          Out: 11.0.101.236/23252 --> 12.0.102.26/28072;udp, If: ge-0/0/1.0

show security flow      user@host> show security flow session resource-manager node 0
session                node0:
resource-manager node  -----
0                        Session ID: 254, Policy name: trust_to_dmz/4, State: Active, Timeout: 36
                          Resource information : SIP ALG, 1024, 8186
                          In: 11.0.54.20/41968 --> 11.0.100.196/1024;udp, If: reth2.0
                          Out: 26.0.29.236/5060 --> 11.0.54.20/41968;udp, If: reth0.0

                          Session ID: 255, Policy name: trust_to_dmz/4, State: Active, Timeout: 120
                          Resource information : SIP ALG, 1024, 8191
                          In: 26.0.29.236/25896 --> 11.0.30.21/24922;udp, If: reth0.0
                          Out: 11.0.30.21/24922 --> 11.0.100.196/64510;udp, If: reth2.0

                          2 sessions displayed

show security flow      user@host> show security flow session resource-manager node 1
session                node1:
resource-manager node  -----
1                        Session ID: 250, Policy name: trust_to_dmz/4, State: Backup, Timeout: 880
                          Resource information : SIP ALG, 1022, 8192
                          In: 11.0.54.20/41968 --> 11.0.100.196/1024;udp, If: reth2.0
                          Out: 26.0.29.236/5060 --> 11.0.54.20/41968;udp, If: reth0.0

                          Session ID: 251, Policy name: trust_to_dmz/4, State: Backup, Timeout: 894
                          Resource information : SIP ALG, 1022, 8180
                          In: 26.0.29.236/25896 --> 11.0.30.21/24922;udp, If: reth0.0
                          Out: 11.0.30.21/24922 --> 11.0.100.196/64510;udp, If: reth2.0

                          2 sessions displayed

```

## show security flow session session-identifier

<b>Syntax</b>	show security flow session session-identifier session-identifier <node ( node-id   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display detailed information about the session with this identifier.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><b>session-identifier</b> —Identifier of the session about which to display information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display session information about the sessions with this identifier on a specific node.</p> <ul style="list-style-type: none"> <li>■ <b>node-id</b> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session session-identifier on page 683
<b>List of Sample Output</b>	<p>show security flow session session-identifier 36 on page 821</p> <p>show security flow session session-identifier 2218 on page 822</p> <p>show security flow session session-identifier 33 on page 822</p> <p>show security flow session session-identifier 1 node primary on page 822</p>
<b>Output Fields</b>	Table 45 on page 820 lists the output fields for the <b>show security flow session session-identifier</b> command. Output fields are listed in the approximate order in which they appear.

**Table 45: show security flow session session-identifier Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Status	Session status.
Flag	Internal flag depicting the state of the session, used for debugging purposes.
Virtual system	Virtual system to which the session belongs.
Policy name	Name and ID of the policy that the first packet of the session matched.



**Table 45: show security flow session session-identifier Output Fields (continued)**

Field Name	Field Description
Maximum timeout	Maximum session timeout.
Current timeout	Remaining time for the session unless traffic exists in the session.
Start time	Time when the session was created, offset from the system start time.
Duration	Length of time for which the session is active.
In	<p>For the input flow:</p> <ul style="list-style-type: none"> <li>■ Source and destination addresses and protocol tuple for the input flow.</li> <li>■ Interface: Input flow interface.</li> <li>■ Session token: Internal token derived from the virtual routing instance.</li> <li>■ Flag: Internal debugging flags.</li> <li>■ Route: Internal next hop of the route to be used by the flow.</li> <li>■ Gateway: Next-hop gateway of the flow.</li> <li>■ Tunnel: If the flow is going into a tunnel, the tunnel ID. Otherwise, 0 (zero).</li> <li>■ Port Sequence, FIN sequence, FIN state, Cookie: Internal TCP state tracking information.</li> </ul>
Out	<p>For the reverse flow:</p> <ul style="list-style-type: none"> <li>■ Source and destination addresses, and protocol tuple for the reverse flow.</li> <li>■ Interface: Reverse flow interface.</li> <li>■ Session token: Internal token derived from the virtual routing instance.</li> <li>■ Flag: Internal debugging flags.</li> <li>■ Route: Internal next hop of the route to be used by the flow.</li> <li>■ Gateway: Next-hop gateway of the flow.</li> <li>■ Tunnel: If the flow is going into a tunnel, the tunnel ID. Otherwise, 0 (zero).</li> <li>■ Port Sequence, FIN sequence, FIN state, Cookie: Internal TCP state tracking information.</li> </ul>

```

show security flow      user@host> show security flow session session-identifier 36
session                Session ID: 36, Status: Normal, Flag: 0x8094540
session-identifier 36 Virtual system: Root VSYS(I), Policy name: foo/4
                        Maximum timeout: 1800, Current timeout: 1646
                        Start time: 61995, Duration: 158
                        In: 10.10.10.1/4923 --> 3.3.3.2/23;tcp,
                           Interface: tl-1/0/0.0,
                           Session token: 0x12, Flag: 0x8094530
                           Route: 0x70010, Gateway: 10.10.10.0, Tunnel: 0
                           Port sequence: 0, FIN sequence: 0,
                           FIN state: 0, Cookie: 0,
                        Out: 3.3.3.2/23 --> 10.10.10.1/4923;tcp,
                           Interface: .local..0,
                           Session token: 0x4, Flag: 0x8094530
                           Route: 0xffffb0006, Gateway: 3.3.3.2, Tunnel: 0
                           Port sequence: 0, FIN sequence: 0,

```

```

    FIN state: 0, Cookie: 0,
1 sessions displayed

```

```

show security flow      user@host> show security flow session session-identifier 2218
session                Session ID: 2218, Status: Normal, Flag: 0x8094660
session-identifier 2218 Virtual system: Root VSYS(I), Policy name: foo/4
                          Maximum timeout: 60, Current timeout: 60
                          Start time: 0, Duration: 0
                          Client: MGCP ALG, Group: 2047, Resource: 8188
                          In: 12.0.102.26/28072 --> 11.0.101.236/23252;udp,
                          Interface: ge-0/0/2.0,
                          Session token: 0xa, Flag: 0x8094740
                          Route: 0xb0010, Gateway: 12.0.102.26, Tunnel: 0
                          Port sequence: 0, FIN sequence: 0,
                          FIN state: 0, Cookie: 0,
                          Out: 11.0.101.236/23252 --> 12.0.102.26/28072;udp,
                          Interface: ge-0/0/1.0,
                          Session token: 0x8, Flag: 0x8094740
                          Route: 0xa0010, Gateway: 11.0.101.236, Tunnel: 0
                          Port sequence: 0, FIN sequence: 0,
                          FIN state: 0, Cookie: 0,
1 sessions displayed

```

```

show security flow      user@host> show security flow session session-identifier 33
session                Session ID: 33, Status: Normal, Flag: 0x80a15f0
session-identifier 33 Virtual system: Root VSYS(I), Policy name: default-policy/2
                          Application: junos-ftp/1
                          Maximum timeout: 1800, Current timeout: 1492
                          Start time: 31128, Duration: 121
                          In: 10.10.10.1/2851 --> 192.168.0.2/21;tcp,
                          Interface: tl-1/0/0.0,
                          Session token: 0x6, Flag: 0x80a15e0
                          Route: 0x60010, Gateway: 10.10.10.0, Tunnel: 0
                          Port sequence: 0, FIN sequence: 0,
                          FIN state: 0, Cookie: 0,
                          Out: 192.168.0.2/21 --> 10.10.10.1/2851;tcp,
                          Interface: ge-0/0/1.0,
                          Session token: 0x6, Flag: 0x80a15e0
                          Route: 0x90010, Gateway: 192.168.0.2, Tunnel: 0
                          Port sequence: 0, FIN sequence: 0,
                          FIN state: 0, Cookie: 0,
1 sessions displayed

```

```

show security flow      user@host> show security flow session session-identifier 1 node primary
session                node0:
session-identifier 1 node
primary                -----
                          Session ID: 1, Status: Normal, State: Active
                          Flag: 0x40
                          Virtual system: root, Policy name: sfw1/4
                          Maximum timeout: 60, Current timeout: 60
                          Start time: 472, Duration: 142
                          In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp,
                          Interface: reth0.1,
                          Session token: 0xa, Flag: 0x1
                          Route: 0x1bfb01, Gateway: 1.1.1.2, Tunnel: 0
                          Port sequence: 0, FIN sequence: 0,
                          FIN state: 0,
                          Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp,
                          Interface: reth1.1,
                          Session token: 0x12, Flag: 0x0
                          Route: 0x1b9b01, Gateway: 11.11.1.2, Tunnel: 0

```

```
Port sequence: 0, FIN sequence: 0,  
FIN state: 0,  
1 sessions displayed
```

## show security flow session source-port

<b>Syntax</b>	show security flow session source-port source-port-number <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about each session that uses the specified source port.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><i>source-port-number</i> —Number of the source port about which to display sessions information.</p> <p><i>node</i>—(Optional) For chassis cluster configurations, display sessions for the specified source port on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <i>all</i>—Display information about all nodes.</li> <li>■ <i>local</i>—Display information about the local node.</li> <li>■ <i>primary</i>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session source-port on page 684
<b>List of Sample Output</b>	show security flow session source-port 2851 on page 825 show security flow session source-port 2000 node 1 on page 825
<b>Output Fields</b>	Table 46 on page 824 lists the output fields for the <b>show security flow session source-port</b> command. Output fields are listed in the approximate order in which they appear.

**Table 46: show security flow session source-port Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
Resource information	Information about the session particular to the resource manager, including the name of the ALG, the group ID, and the resource ID.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```

show security flow      user@host> show security flow session source-port 2851
session source-port    Session ID: 33, Policy name: default-policy/2, Timeout: 1492
2851                   In: 10.10.10.1/2851 --> 192.168.0.2/21;tcp, If: t1-1/0/0.0
                           Out: 192.168.0.2/21 --> 10.10.10.1/2851;tcp, If: ge-0/0/1.0

```

```

show security flow      user@host> show security flow session source-port 2000 node 1
session source-port    node1:
2000 node 1            -----
                           Session ID: 1, Policy name: sfw1/4, State: Backup, Timeout: 322
                           In: 1.1.1.2/2000 --> 11.11.1.2/40000;udp, If: reth0.1
                           Out: 11.11.1.2/40000 --> 1.1.1.2/2000;udp, If: reth1.1
                           Session ID: 2, Policy name: sfw2/5, State: Backup, Timeout: 316
                           In: 1.1.2.2/2000 --> 11.11.2.2/40000;udp, If: reth0.2
                           Out: 11.11.2.2/40000 --> 1.1.2.2/2000;udp, If: reth1.2
                           Session ID: 3, Policy name: sfw3/6, State: Backup, Timeout: 320
                           In: 1.1.3.2/2000 --> 11.11.3.2/40000;udp, If: reth0.3
                           Out: 11.11.3.2/40000 --> 1.1.3.2/2000;udp, If: reth1.3
                           Session ID: 4, Policy name: sfw4/7, State: Backup, Timeout: 322
                           In: 1.1.4.2/2000 --> 11.11.4.2/40000;udp, If: reth0.4
                           Out: 11.11.4.2/40000 --> 1.1.4.2/2000;udp, If: reth1.4
                           4 sessions displayed

```

## show security flow session source-prefix

<b>Syntax</b>	show security flow session source-prefix <i>source-prefix-number</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about each session that uses the specified source prefix.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p><i>source-prefix-number</i> —Source IPv4 prefix or address about which to display sessions information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display sessions for the specified source prefix on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session source-prefix on page 685
<b>List of Sample Output</b>	show security flow session source-prefix 10/8 on page 827
<b>Output Fields</b>	Table 47 on page 826 lists the output fields for the <b>show security flow session source-prefix</b> command. Output fields are listed in the approximate order in which they appear.

**Table 47: show security flow session source-prefix Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic.
Timeout	Idle timeout after which the session expires.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).
Out	Reverse flow (source and destination IP addresses, application protocol, and interface).

```
show security flow session source-prefix 10/8
user@host> show security flow session source-prefix 10/8
Session ID: 36, Policy name: foo/4, Timeout: 1547
  In: 10.10.10.1/4923 --> 3.3.3.2/23;tcp, If: t1-1/0/0.0
  Out: 3.3.3.2/23 --> 10.10.10.1/4923;tcp, If: .local..0
1 sessions displayed
```

## show security flow session summary

<b>Syntax</b>	show security flow session summary <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display summary information about existing sessions, including types of sessions, active and failed sessions, and the maximum allowed number of sessions.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display details summary of all sessions.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display a summary of sessions on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security flow session all on page 674
<b>List of Sample Output</b>	<p>show security flow session summary on page 829</p> <p>show security flow session summary (SRX-series devices) on page 829</p> <p>show security flow session summary node all on page 829</p> <p>show security flow session summary member primary on page 829</p>
<b>Output Fields</b>	Table 48 on page 828 lists the output fields for the show security flow session summary command. Output fields are listed in the approximate order in which they appear.

**Table 48: show security flow session summary Output Fields**

Field Name	Field Description
Unicast-sessions	Total number of active unicast sessions.
Multicast-sessions	Total number of active multicast sessions.
Failed-sessions	Total number of failed sessions.
Active-sessions	Total number of active sessions.
Maximum-sessions	Maximum number of supported sessions.



```

show security flow session summary      user@host> show security flow session summary
Session summary:
  Unicast-sessions: 1
  Multicast-sessions: 0
  Failed-sessions: 0
  Active-sessions: 1
  Maximum-sessions: 256000

show security flow session summary      user@host> show security flow session summary
(SRX-series devices)                  Session summary:
  Unicast-sessions: 0
  Multicast-sessions: 0
  Failed-sessions: 0
  Sessions-in-use: 0
  Maximum-sessions: 131072
  Unicast-sessions: 0
  Multicast-sessions: 0
  Failed-sessions: 0
  Sessions-in-use: 0
  Maximum-sessions: 524288

show security flow session summary node all user@host> show security flow session summary node all
session summary node all              node0:
-----
Session summary:
  Unicast-sessions: 4
  Multicast-sessions: 0
  Failed-sessions: 0
  Sessions-in-use: 4
  Maximum-sessions: 262144
node1:
-----
Session summary:
  Unicast-sessions: 4
  Multicast-sessions: 0
  Failed-sessions: 0
  Sessions-in-use: 4
  Maximum-sessions: 262144

show security flow session summary member primary user@host> show security flow session summary member primary
session summary member primary      Session summary:
  Unicast-sessions: 1
  Multicast-sessions: 0
  Failed-sessions: 0
  Active-sessions: 1
  Maximum-sessions: 10000

```

## show security flow session tunnel

<b>Syntax</b>	show security flow session tunnel <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about all tunnel sessions.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all tunnel sessions.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display tunnel sessions on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>no-syn-check-in-tunnel</p> <p>clear security flow session all on page 674</p>
<b>List of Sample Output</b>	show security flow session tunnel on page 830
<b>Output Fields</b>	Table 49 on page 830 lists the output fields for the <b>show security flow session tunnel</b> command. Output fields are listed in the approximate order in which they appear.

**Table 49: show security flow session tunnel Output Fields**

Field Name	Field Description
Session ID	Number that identifies the session. You can use this ID to get additional information about the session.
Policy name	Policy that permitted the traffic. NA (Not Applicable) for a tunnel session.
Timeout	Idle timeout after which the session expires. NA (Not Applicable) for a tunnel session.
In	Incoming flow (source and destination IP addresses, application protocol, and interface).

```

show security flow session tunnel
user@host> show security flow session tunnel
Session ID: 9003, Policy name: N/A, Timeout: N/A
In: 2.2.2.2/0 --> 2.2.2.1/0;esp, If: fe-4/0/0.0

```

```
Session ID: 9004, Policy name: N/A, Timeout: N/A  
In: 2.2.2.2/48468 --> 2.2.2.1/48442;esp, If: fe-4/0/0.0  
Session ID: 9005, Policy name: N/A, Timeout: N/A  
In: 10.157.89.106/2048 --> 10.157.89.210/2048;gre, If: ge-0/0/1.0
```

## show security idp active-policy

---

<b>Syntax</b>	show security idp active-policy
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Display information about the policy name and running detector version with which the policy is compiled from IDP data plane module.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>request security idp security-package download on page 714</p> <p>request security idp security-package install on page 716</p>
<b>List of Sample Output</b>	show security idp active-policy on page 832
<b>Output Fields</b>	Table 50 on page 832 lists the output fields for the show security idp active-policy command. Output fields are listed in the approximate order in which they appear.

**Table 50: show security idp active-policy Output Fields**

Field Name	Field Description
Policy Name	Name of the running policy.
Running Detector Version	Current version of the running detector.

```

show security idp      user@host> show security idp active-policy
active-policy          Policy Name : viking-policy
                          Running Detector Version : 9.1.140080300

```

## show security idp application-identification application-system-cache

<b>Syntax</b>	show security idp application-identification application-system-cache
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Display application ID from default port/protocol binding or from the application system cache.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>application-system-cache</p> <p>clear security idp application-identification application-system-cache on page 686</p>
<b>List of Sample Output</b>	show security idp application-identification application-system-cache on page 833
<b>Output Fields</b>	Table 51 on page 833 lists the output fields for the show security idp application-identification application-system-cache command. Output fields are listed in the approximate order in which they appear.

**Table 51: show security idp application-identification application-system-cache Output Fields**

Field Name	Field Description
Vsys-ID	Application identification number.
IP address	IPv4 address.
Port	Port number that are is use with the current session.
Protocol	Name of the protocol session.
Expired	Session expired status Yes or No
Service	Name of the service.

```

show security idp      user@host> show security idp application-identification application-system-cache
application-identification IDP Application System Cache statistics:
application-system-cache Vsys-ID      IP address      Port      Protocol  Expired  Service
                           0              5.0.0.1       80       tcp       No       HTTP

```

show security idp attack table

Syntax	show security idp attack table
Release Information	Command introduced in Release 9.2 of JUNOS software.
Description	Display detailed information of IDP attack table.  This command is supported on SRX-series devices.
Required Privilege Level	view
Related Topics	attacks  clear security idp attack table on page 687
List of Sample Output	show security idp attack table on page 834
Output Fields	Table 52 on page 834 lists the output fields for the show security idp attack table command. Output fields are listed in the approximate order in which they appear.

Table 52: show security idp attack table Output Fields

Field Name	Field Description
Attack name	Name of the attack that you want to match in the monitored network traffic.
Hits	Total number of attack matches.

show security idp attack table	user@host> show security idp attack table
	IDP attack statistics:
	Attack name#Hits
	HTTP:OVERFLOW:PI3WEB-SLASH-OF1

## show security idp counters application-identification

<b>Syntax</b>	show security idp counters application-identification
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all IDP application identification (AI) counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	application-identification  clear security idp counters application-identification on page 688
<b>List of Sample Output</b>	show security idp counters application-identification on page 836
<b>Output Fields</b>	Table 53 on page 835 lists the output fields for the show security idp counters application-identification command. Output fields are listed in the approximate order in which they appear.

**Table 53: show security idp counters application-identification Output Fields**

Field Name	Field Description
AI cache hits	Number of sessions found application in AI cache.
AI cache misses	Number of sessions those did not find application from AI cache.
AI matches	Number of sessions matched AI signatures.
AI no-matches	Number of sessions that did not match AI signatures.
AI-enabled sessions	Number of sessions that are AI enabled.
AI-disabled sessions	Number of sessions that are AI disabled.
AI-disabled sessions due to gate match	Number of sessions disabled AI match due to gate match.
AI-disabled sessions due to ssl encapsulated flows	Number of sessions disabled AI match due to ssl encapsulated flows.
AI-disabled sessions due to cache hit	Number of sessions disabled AI match due to AI cache match.
AI-disabled sessions due to configuration	Number of sessions disabled AI match due to AI session limit in the configuration.
AI-disabled sessions due to protocol remapping	Number of sessions disabled AI match due to protocol remapping.
AI-disabled sessions due to RPC match	Number of sessions disabled AI match due to RPC match.

**Table 53: show security idp counters application-identification Output Fields** *(continued)*

Field Name	Field Description
AI-disabled sessions due to Aux/Dynamic/Encap/Mgmt flows  (Unsupported)	Number of sessions disabled AI match due to auxiliary, dynamic, encapsulated, or management flows.
AI-disabled sessions due to non-TCP/UDP flows	Number of sessions disabled AI match due to non-TCP or non-UDP flows.
AI-disabled sessions due to no AI signatures  (Unsupported)	Number of sessions disabled AI match due to absence of AI signature.
AI-disabled sessions due to session limit	Number of sessions disabled AI match after reaching AI max session limit.
AI-disabled sessions due to session packet memory limit	Number of sessions disabled AI match after reaching AI memory usage limit per session.
AI-disabled sessions due to global packet memory limit	Number of sessions disabled AI match after reaching AI global memory usage limit.

```

show security idp counters application-identification
user@host> show security idp counters application-identification
IDP counters:
IDP counter type                                     Value
AI cache hits                                         2682
AI cache misses                                       3804
AI matches                                             74
AI no-matches                                         27
AI-enabled sessions                                   3804
AI-disabled sessions                                  2834
AI-disabled sessions due to gate match                 0
AI-disabled sessions due to ssl encapsulated flows    0
AI-disabled sessions due to cache hit                 2682
AI-disabled sessions due to configuration             0
AI-disabled sessions due to protocol remapping        0
AI-disabled sessions due to RPC match                 0
AI-disabled sessions due to Aux/Dynamic/Encap/Mgmt flows 0
AI-disabled sessions due to non-TCP/UDP flows         118
AI-disabled sessions due to no AI signatures          0
AI-disabled sessions due to session limit             0
AI-disabled sessions due to session packet memory limit 34
AI-disabled sessions due to global packet memory limit 0

```



## show security idp counters dfa

<b>Syntax</b>	show security idp counters dfa
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all DFA counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security idp counters dfa on page 689
<b>List of Sample Output</b>	show security idp counters dfa on page 837
<b>Output Fields</b>	Table 54 on page 837 lists the output fields for the show security idp counters dfa command. Output fields are listed in the approximate order in which they appear.

**Table 54: show security idp counters dfa Output Fields**

Field Name	Field Description
DFA Group Merged Usage	Number of DFA groups merged.
DFA Matches	Number of DFA matches found.

<b>show security idp counters dfa</b>	user@host> show security idp counters dfa	
	IDP counters:	
	IDP counter type	Value
	DFA Group Merged Usage	0
	DFA Matches	1

## show security idp counters flow

<b>Syntax</b>	show security idp counters flow
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all IDP flow counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	flow (IDP)  clear security idp counters flow on page 690
<b>List of Sample Output</b>	show security idp counters flow on page 839
<b>Output Fields</b>	Table 55 on page 838 lists the output fields for the show security idp counters flow command. Output fields are listed in the approximate order in which they appear.

**Table 55: show security idp counters flow Output Fields**

Field Name	Field Description
Fast-path packets	Number of packets that are set through fast path after completing idp policy lookup.
Slow-path packets	Number of packet that are sent through slow path during idp policy lookup.
ICMP-error packets	Number of ICMP error packets.
(Unsupported)	
Session construction failed	Number of times the packet failed to establish the session.
(Unsupported)	
Session limit reached	Number of sessions that reached idp sessions limit.
Not a new session	Number of session that extended from its time limit.
(Unsupported)	
Invalid index at ageout	Invalid session index in session ageout message.
(Unsupported)	
Packet logging	Number of packets saved for packet logging.
Busy packets	Number of packets saved as the one or more packets of this session are handed off for async processing.
(Unsupported)	
Policy cache hits	Number of sessions that matched policy cache.

**Table 55: show security idp counters flow Output Fields** (continued)

Field Name	Field Description
Policy cache misses	Number of sessions that did not match policy cache.
Maximum flow hash collisions	Maximum number of packets of one flow that share the same hash value.
Bad-UDP-checksumpackets	Number of packets that received with bad UDP checksum error.
(Unsupported)	
Gates added	Number of gate entries added for dynamic port identification.
Gate matches	Number of times a gate is matched.
(Unsupported)	
Sessions deleted	Number of sessions deleted.
Sessions aged-out	Number of sessions are aged out if no traffic is received within session timeout value.
(Unsupported)	
Sessions in-use while aged-out	Number of sessions in use during session ageout.
(Unsupported)	
TCP flows marked dead on RST/FIN	Number of session marked dead on TCP RST/FIN.
Sessions constructed	Number of sessions established.
Sessions destructed	Number of sessions destructed.
SM Session Create	Number of SM sessions created.
SM Packet Process	Number of packets processed from SM.
SM Session close	Number of SM sessions closed.

```

show security idp counters flow user@host> show security idp counters flow
IDP counters:
IDP counter type                                Value
Fast-path packets                               0
Slow-path packets                               1
ICMP-error packets                               0
Session construction failed                       0
Session limit reached                             0
Not a new session                                0
Invalide index at ageout                         0
Packet logging                                    0
Busy packets                                     0
Policy cache hits                                 0
Policy cache misses                               1
Maximum flow hash collisions                      0
Flow hash collisions                              0

```

Bad-UDP-checksum packets	0
Gates added	0
Gate matches	0
Sessions deleted	1
Sessions aged-out	0
Sessions in-use while aged-out	0
TCP flows marked dead on RST/FIN	1
Sessions constructed	1
Sessions destructed	1
SM Session Create	1
SM Packet Process	28
SM Session close	1

## show security idp counters ips

<b>Syntax</b>	show security idp counters ips
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Display the status of all IPS counter values.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>ips</p> <p>clear security idp counters ips on page 691</p>
<b>List of Sample Output</b>	show security idp counters ips on page 842
<b>Output Fields</b>	Table 56 on page 841 lists the output fields for the show security idp counters ips command. Output fields are listed in the approximate order in which they appear.

**Table 56: show security idp counters ips Output Fields**

Field Name	Field Description
TCP fast path	Number of TCP packets skipped for IDS processing.
Layer-4 anomalies	Number of Layer-4 protocol error or anomaly.
Anomaly hash misses	Number of times look failed on anomaly hash.
Line context matches	Number of attempts to match line based attacks in traffic stream.
Stream256 context matches	Number of attempts to match stream based attacks in first 256 bytes of traffic stream.
Stream context matches	Number of attempts to match stream based attacks in traffic stream.
Packet context matches	Number of attempts to match packet based attacks in traffic packet.
Packet header matches	Number of attempts to match packet header based attacks in traffic packet.
Context matches	Number of attempts to match protocol context based attacks in traffic stream.
Regular expression matches	Number of attempts to match PCRE expressions in traffic stream.
Tail DFAs	Number of attempts to match an attack on tail DFA group matches.
Exempted attacks	Number of attacks exempted from match as per exempt rulebase.
Out of order chains	Number of times attack is excluded from match due to member attacks in an attack group did not complete chain.
Partial chain matches	Number of attacks in partial chain match with attack scope as transaction.

**Table 56: show security idp counters ips Output Fields** (*continued*)

Field Name	Field Description
IDS device FIFO size	Number of IDS contexts in virtual IDS device.
IDS device FIFO overflows	Number of times an IDS context can not be written as the IDS device is full.
Brute force queue size	Number of entries in the brute force queue.
IDS cache hits	Number of sessions those found attack instance in IDS cache.
(Unsupported)	
IDS cache misses	Number of sessions those did not find attack instance in IDS cache.
(Unsupported)	
Shellcode detection invocations	Number of times shell code match is attempted.
Wrong offsets	Number of times attack's offset is not within the service offset range.
No peer MAC	Number of times flow peer MAC address is not available.
(Unsupported)	

```

show security idp counters ips user@host> show security idp counters ips
IDP counters:
IDP counter type Value
TCP fast path 15
Layer-4 anomalies 0
Anomaly hash misses 3
Line context matches 5
Stream256 context matches 5
Stream context matches 5
Packet context matches 0
Packet header matches 0
Context matches 12
Regular expression matches 0
Tail DFAs 0
Exempted attacks 0
Out of order chains 0
Partial chain matches 0
IDS device FIFO size 0
IDS device FIFO overflows 0
Brute force queue size 0
IDS cache hits 0
IDS cache misses 0
Shellcode detection invocations 0
Wrong offsets 0
No peer MAC 0

```

## show security idp counters log

<b>Syntax</b>	show security idp counters log
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all IDP log counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	log (IDP)  clear security idp counters log on page 692
<b>List of Sample Output</b>	show security idp counters log on page 844
<b>Output Fields</b>	Table 57 on page 843 lists the output fields for the show security idp counters log command. Output fields are listed in the approximate order in which they appear.

**Table 57: show security idp counters log Output Fields**

Field Name	Field Description
Logs dropped	Number of logs that are dropped.
Suppressed log count	Number of logs that are suppressed.
Logs waiting for post-window packets (Unsupported)	Number of logs waiting for post-window packets.
Logs ready to be sent (Unsupported)	Number of logs ready to be sent.
Logs in suppression list (Unsupported)	Number of logs considered for suppression list.
Log timers created	Number of times the log timer is created.
Logs timers expired	Number of times the log timer is expired.
Log timers cancelled	Number of times the log timer is canceled.
Logs ready to be sent high watermark (Unsupported)	Number of packets that are ready to be sent with high degree watermark.
Log receive buffer full (Unsupported)	Number of times the buffer is full.

**Table 57: show security idp counters log Output Fields** *(continued)*

Field Name	Field Description
Packet log too big (Unsupported)	Number of packet logs that exceeded allowed packet log size.
Reads per second (Unsupported)	Number of packets that are read per second.
Logs in read buffer high watermark (Unsupported)	Number of high watermark packets that are in read buffer.
Packets logged	Number of packets that are logged,
Packets lost (Unsupported)	Number of packets that are failed to log.
Packets copied (Unsupported)	Number of packets copied during packet log.
Packets held (Unsupported)	Number of packets held for packet log.
Packets released	Number of packets that are released from hold.
IP Action Messages (Unsupported)	Number of IP action messages.
IP Action Drops (Unsupported)	Number of IP action messages dropped.
IP Action Exists (Unsupported)	Number of exits during IP action creation.
NWaits (Unsupported)	Number of logs waiting for post window packets.
Match vectors	Number of attacks in IDS match vector.
Supercedes	Number of attacks in supercede vector.

```

show security idp counters log user@host> show security idp counters log
IDP counters:
IDP counter type

```

Value



Logs dropped	0
Suppressed log count	0
Logs waiting for post-window packets	0
Logs ready to be sent	0
Logs in suppression list	0
Log timers created	0
Logs timers expired	0
Log timers cancelled	0
Logs ready to be sent high watermark	0
Log receive buffer full	0
Packet log too big	0
Reads per second	1
Logs in read buffer high watermark	0
Log Bytes in read buffer high watermark	0
Packets logged	0
Packets lost	0
Packets copied	0
Packets held	0
Packets released	0
IP Action Messages	0
IP Action Drops	0
IP Action Exists	0
NWaits	0
Match vectors	0
Supercedes	0
Kpacket too big	0

## show security idp counters packet

<b>Syntax</b>	show security idp counters packet
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all IDP packet counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security idp counters packet on page 693
<b>List of Sample Output</b>	show security idp counters packet on page 847
<b>Output Fields</b>	Table 58 on page 846 lists the output fields for the show security idp counters packet command. Output fields are listed in the approximate order in which they appear.

**Table 58: show security idp counters packet Output Fields**

Field Name	Field Description
Processed packets	Number of packets processed by IDP service.
Dropped packets	Number of packets dropped by IDP service.
Dropped sessions	Number of sessions dropped.
(Unsupported)	
Bad IP headers	Number of packets that fail IP header length validity check.
Packets with IP options	Number of packets that contain the optional header fields.
Decapsulated packets	Number of packets that are decapsulated.
GRE decapsulations	Number of packets that are generic routing encapsulation (GRE) decapsulated.
(Unsupported)	
PPP decapsulations	Number of packets that are Point-to-Point Protocol (PPP) decapsulated.
(Unsupported)	
GTP decapsulations	Number of packets that are GPRS tunneling protocol (GTP) decapsulated.
(Unsupported)	
GTP flows	Number of GTP flows.
(Unsupported)	

**Table 58: show security idp counters packet Output Fields** *(continued)*

Field Name	Field Description
TCP decompression uncompressed IP (Unsupported)	Number of uncompressed IP headers that are to be TCP decompressed.
TCP decompression compressed IP (Unsupported)	Number of compressed IP headers that are to be TCP decompressed.
Deferred-send packets (Unsupported)	Number of deferred IP packets that are sent out.
IP-in-IP packets (Unsupported)	Number of packets that are IP-in-IP encapsulated.
TTL errors (Unsupported)	Number of packets with TTL error in the header.
Routing loops (Unsupported)	Number of packets that continue to be routed in an endless circle due to inconsistent routing state.
No-route packets (Unsupported)	Number of packets that could not be routed further.
Flood IP (Unsupported)	Number of packets that are identified as IP flood packets.
Invalid ethernet headers (Unsupported)	Number of packets that are identified with invalid Ethernet header.
Packets attached	Number of packets attached.
Packets cloned	Number of packets that are cloned.
Packets allocated	Number of packets allocated.
Packets destructed	Number of packets destructed.

```

show security idp counters packet
user@host> show security idp counters packet
IDP counters:
IDP counter type      Value
Processed packets    27
Dropped packets      0
Dropped sessions     0
Bad IP headers       0

```

Packets with IP options	0
Decapsulated packets	0
GRE decapsulations	0
PPP decapsulations	0
GTP decapsulations	0
GTP flows	0
TCP decompression uncompressed IP	0
TCP decompression compressed IP	0
Deferred-send packets	0
IP-in-IP packets	0
TTL errors	0
Routing loops	0
STP drops	0
No-route packets	0
Flood IP	0
Invalid ethernet headers	0
Packets attached	28
Packets cloned	28
Packets allocated	0
Packets destructed	55

## show security idp counters policy-manager

<b>Syntax</b>	show security idp counters policy-manager
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all IDP policies counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security idp counters policy-manager on page 694
<b>List of Sample Output</b>	show security idp counters policy-manager on page 849
<b>Output Fields</b>	Table 59 on page 849 lists the output fields for the show security idp counters policy-manager command. Output fields are listed in the approximate order in which they appear.

**Table 59: show security idp counters policy-manager Output Fields**

Field Name	Field Description
Number of policies	Number of policies installed.
Number of aged out policies	Number of IDP policies that are expired.

<b>show security idp counters policy-manager</b>	<pre> user@host&gt; show security idp counters policy-manager IDP counters:   IDP counter type   Number of policies   Number of aged out policies </pre>	<pre> Value   0   0 </pre>
--	--	----------------------------

## show security idp counters tcp-reassembler

<b>Syntax</b>	show security idp counters tcp-reassembler
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all TCP reassembler counter values.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	re-assembler  clear security idp counters tcp-reassembler on page 695
<b>List of Sample Output</b>	show security idp counters tcp-reassembler on page 851
<b>Output Fields</b>	Table 60 on page 850 lists the output fields for the <code>show security idp counters tcp-reassembler</code> command. Output fields are listed in the approximate order in which they appear.

**Table 60: show security idp counters tcp-reassembler Output Fields**

Field Name	Field Description
Bad TCP checksums  (Unsupported)	Number of packets that have incorrect TCP checksums.
Bad TCP headers	Number of bad TCP headers detected.
Slow path segments	Number of segments that are sent through the slow path if the TCP segment does not pass fast-path segment validation.
Fast path segments	Number of segments that are sent through the fast path after passing a predefined TCP validation sequence.
Sequence number wrap around errors	Number of packets that wrap around of the sequence number.
Session reuses	Number of sessions that reused an already established TCP session.
SYN retransmissions	Number of SYN packets that are retransmitted.
Bad three way handshake acknowledgements	Number of packets that have incorrect three-way handshake acknowledgements (ACK packet).
Sequence number out of sync flows	Number of packets that have out-of-sync sequence numbers.
Fast path pattern matches in queued up streams	Number of queued packets that have fast path pattern match.
New segments with no overlaps with old segment	Number of new segments that do not overlap with old segment.

**Table 60: show security idp counters tcp-reassembler Output Fields** (continued)

Field Name	Field Description
New segment overlaps with beginning of old segment	Number of new segments that overlap with beginning of old segment.
New segment overlaps completely with old segment	Number of new segments that overlap completely with old segment.
New segment is contained in old segment	Number of new segments contained in old segment.
New segment overlaps with end of old segment	Number of new segments that overlap with the end of old segment.
New segment begins after end of old segment	Number of new segments that overlap after the end of old segment.
Memory consumed by new segment	Memory that is consumed by the new segment.
Segments in memory	Number of segments that are stored in memory for processing.
Per-flow memory overflows	Number of segments dropped after reaching per flow memory limit.
Global memory overflows	Number of segments dropped after reaching reassembler global memory limit.
Overflow drops	Number of packets that are dropped due to memory overflow.
Copied packets	Number of packets copied in reassembler.
(Unsupported)	
Closed Acks	Number of Ack packets seen without having seen SYN on the same session.

```

show security idp counters tcp-reassembler user@host> show security idp counters tcp-reassembler
IDP counters:
IDP counter type Value
Bad TCP checksums 0
Bad TCP headers 0
Slow path segments 4
Fast path segments 23
Sequence number wrap around errors 0
Session reuses 0
SYN retransmissions 0
Bad three way handshake acknowledgements 0
Sequence number out of sync flows 0
Fast path pattern matches in queued up streams 0
New segments with no overlaps with old segment 0
New segment overlaps with beginning of old segment 0
New segment overlaps completely with old segment 0
New segment is contained in old segment 0
New segment overlaps with end of old segment 0
New segment begins after end of old segment 0
Memory consumed by new segment 0
Segments in memory 0

```

Per-flow memory overflows	0
Global memory overflows	0
Overflow drops	0
Copied packets	0
Closed Acks	0



## show security idp memory

<b>Syntax</b>	show security idp memory
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of all IDP data plane memory.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security idp memory on page 853
<b>Output Fields</b>	Table 61 on page 853 lists the output fields for the show security idp memory command. Output fields are listed in the approximate order in which they appear.

**Table 61: show security idp memory Output Fields**

Field Name	Field Description
PIC	Name of the PIC.
Total IDP data plane memory	Total memory space which is allocated for the IDP data plane.
Used	Used memory space in the data plane.
Available	Available memory space in the data plane.

```

show security idp user@host> show security idp memory
memory          IDP data plane memory statistics:
                   PIC : spu-13
                   Total IDP data plane memory : 307 MB
                   Used : 42 MB ( 43008 KB )
                   Available : 265 MB ( 271360 KB )
                   PIC : spu-12
                   Total IDP data plane memory : 307 MB
                   Used : 42 MB ( 43008 KB )
                   Available : 265 MB ( 271360 KB )

```

## show security idp security-package-version

<b>Syntax</b>	show security idp security-package-version
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Display information of the currently installed security package version and detector version.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>security-package</p> <p>request security idp security-package download on page 714</p> <p>request security idp security-package install on page 716</p>
<b>List of Sample Output</b>	show security idp security-package-version on page 854
<b>Output Fields</b>	Table 62 on page 854 lists the output fields for the <b>show security idp security-package-version</b> command. Output fields are listed in the approximate order in which they appear.

**Table 62: show security idp security-package-version Output Fields**

Field Name	Field Description
Attack database version	Attack database version number that are currently installed on the system.
Detector version	Detector version number that are currently installed on the system.
Policy template version	Policy template version that are currently installed on the system.

```

show security idp security-package-version  user@host> show security idp security-package-version
Attack database version:1154(Mon Apr 28 15:08:42 2008)
Detector version :9.1.140080400
Policy template version :7

```

## show security idp status

<b>Syntax</b>	show security idp status
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display the status of the current IDP policy.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security idp status on page 855
<b>Output Fields</b>	Table 63 on page 855 lists the output fields for the <b>show security idp status</b> command. Output fields are listed in the approximate order in which they appear.

**Table 63: show security idp status Output Fields**

Field Name	Field Description
Status of IDP	Status of current IDP policy.
Packets/second	The aggregated throughput (packets per second) for the system.
KBits/second	The aggregated throughput (kbits per second) for the system.
Latency	<ul style="list-style-type: none"> <li>■ min—Minimum delay for a packet to receive and return by a node in microseconds.</li> <li>■ max—Maximum delay for a packet to receive and return by a node in microseconds.</li> <li>■ ave—Average delay for a packet to receive and return by a node in microseconds.</li> </ul>
Current policy	Name of the current installed policy.

```

show security idp status  user@host> show security idp status
                          Status of IDP: s0,      Up since: 2008-03-31 16:33:22 PDT (12:47:45 ago)
                          Packets/second: 0          Peak: 12 @ 2008-03-31 18:45:39 PDT
                          KBits/second : 0           Peak: 6 @ 2008-03-31 18:45:39 PDT
                          Latency (microseconds): [min: 0] [max: 0] [ave: 0]
                          Current policy: viking-policy v0

```

## show security ike pre-shared-key

---

<b>Syntax</b>	show security ike pre-shared key <master-key <i>master-key</i> > <user-id <i>user-id</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display the Internet Key Exchange (IKE) preshared key used by the Virtual Private network (VPN) gateway to authenticate the remote access user.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	master-key <i>master-key</i> —(Optional) Master preshared key.  user-id <i>user-id</i> —(Optional) IKE user ID value.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	pre-shared-key
<b>List of Sample Output</b>	show security ike pre-shared-key on page 856
<b>show security ike pre-shared-key</b>	user@host> show security ike pre-shared-key user-id a@juniper.net master-key juniper Preshared Key:3b33ec3631a561ec5a710f5d02f208033b108bb4

## show security ike security-associations

---

<b>Syntax</b>	<pre>show security ike security-associations &lt;peer-address&gt; &lt;brief   detail&gt; &lt;fpc slot-number&gt; &lt;index SA-index-number&gt; &lt;kmd-instance (all   kmd-instance-name)&gt; &lt;pic slot-number&gt;</pre>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>fpc</b> , <b>pic</b> , and <b>kmd-instance</b> options added in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Display information about Internet Key Exchange (IKE) security associations (SAs).</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>none</b>—Display standard information about existing IKE SAs, including index numbers.</p> <p><b>peer-address</b>—(Optional) Display details about a particular SA, based on the IP address of the destination peer. This option and <b>index</b> provide the same level of output.</p> <p><b>brief</b>—(Optional) Display standard information about all existing IKE SAs. (Default)</p> <p><b>detail</b>—(Optional) Display detailed information about all existing IKE SAs.</p> <p><b>fpc slot-number</b>—Specific to SRX-series services gateway. Display information about existing IKE SAs in this particular Flexible PIC Concentrator (FPC) slot. This option is used to filter the output.</p> <p><b>index SA-index-number</b>—(Optional) Display information for a particular SA based on the index number of the SA. To obtain the index number for a particular SA, display the list of existing SAs by using the command with no options. This option and <b>peer-address</b> provide the same level of output.</p> <p><b>kmd-instance</b> —Specific to SRX-series services gateway. Display information about existing IKE SAs in the key management process (daemon) (KMD) identified by the FPC slot-number and PIC slot-number. This option is used to filter the output.</p> <ul style="list-style-type: none"> <li>■ <b>all</b>—All KMD instances running on the Services Processing Unit (SPU).</li> <li>■ <b>kmd-instance-name</b>—Name of the KMD instance running on the SPU.</li> </ul> <p><b>pic slot-number</b> —Specific to SRX-series services gateway. Display information about existing IKE SAs in this particular PIC slot. This option is used to filter the output.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security ike security-associations on page 697
<b>List of Sample Output</b>	<p>show security ike security-associations on page 860</p> <p>show security ike security-associations detail on page 860</p>

show security ike security-associations detail (SRX-series devices) on page 861  
 show security ike security-associations index 8 detail on page 861  
 show security ike security-associations 1.1.1.2 on page 861  
 show security ike security-associations fpc 6 pic 1 kmd-instance all (SRX-series devices) on page 861

**Output Fields** Table 64 on page 858 lists the output fields for the `show security ike security-associations` command. Output fields are listed in the approximate order in which they appear.

**Table 64: show security ike security-associations Output Fields**

Field Name	Field Description
IKE Peer or Remote Address	IP address of the destination peer with which the local peer communicates.
Index	Index number of an SA. This number is an internally generated number you can use to display information about a single SA.
Location	<ul style="list-style-type: none"> <li>■ <b>FPC</b>—Flexible PIC Concentrator (FPC) slot number.</li> <li>■ <b>PIC</b>—PIC slot number.</li> <li>■ <b>KMD-Instance</b>—The name of the kmd-instance running on the SPU, identified by the FPC slot-number and PIC slot-number. Currently, 4 kmd-instances running on each SPU and any particular IKE negotiation is carried out by a single kmd-instance.</li> </ul>
Role	Part played in the IKE session. The device triggering the IKE negotiation is the initiator, and the device accepting the first IKE exchange packets is the responder.
State	State of the IKE security associations: <ul style="list-style-type: none"> <li>■ <b>DOWN</b>—SA has not been negotiated with the peer.</li> <li>■ <b>UP</b>—SA has been negotiated with the peer.</li> </ul>
Initiator cookie	Random number, called a cookie, which is sent to the remote node when the IKE negotiation is triggered.
Responder cookie	Random number generated by the remote node and sent back to the initiator as a verification that the packets were received.  A cookie is aimed at protecting the computing resources from attack without spending excessive CPU resources to determine the cookie's authenticity.
Mode or Exchange type	Negotiation method agreed on by the two IPSec endpoints, or peers, used to exchange information between themselves. Each exchange type determines the number of messages and the payload types that are contained in each message. The modes, or exchange types, are <ul style="list-style-type: none"> <li>■ <b>main</b>—The exchange is done with six messages. This mode or exchange type encrypts the payload, protecting the identity of the neighbor. The authentication method used is displayed: preshared keys or certificate.</li> <li>■ <b>aggressive</b>—The exchange is done with three messages. This mode or exchange type does not encrypt the payload, leaving the identity of the neighbor unprotected.</li> </ul>
Local	Address of the local peer.
Remote	Address of the remote peer.
Lifetime	Number of seconds remaining until the IKE SA expires.

**Table 64: show security ike security-associations Output Fields (continued)**

Field Name	Field Description
Algorithms	<p>Internet Key Exchange (IKE) algorithms used to encrypt and secure exchanges between the peers during the IPSec Phase 2 process:</p> <ul style="list-style-type: none"> <li>■ Authentication—Type of authentication algorithm used. <ul style="list-style-type: none"> <li>■ sha1—Secure Hash Algorithm 1 (sha1) authentication.</li> <li>■ md5—MD5 authentication</li> </ul> </li> <li>■ Encryption—Type of encryption algorithm used.. <ul style="list-style-type: none"> <li>■ aes-256-cbc—Advanced Encryption Standard (AES) 256-bit encryption.</li> <li>■ aes-192-cbc— AES 192-bit encryption</li> <li>■ aes-128-cbc—AES 128-bit encryption.</li> <li>■ 3des-cbc—3 Data Encryption Standard (DES) encryption.</li> <li>■ des-cbc—DES encryption.</li> </ul> </li> </ul>
Traffic statistics	<ul style="list-style-type: none"> <li>■ Input bytes—Number of bytes received.</li> <li>■ Output bytes—Number of bytes transmitted.</li> <li>■ Input packets—Number of packets received.</li> <li>■ Output packets—Number of packets transmitted.</li> </ul>
Flags	<p>Notification to the key management process of the status of the IKE negotiation:</p> <ul style="list-style-type: none"> <li>■ caller notification sent—Caller program notified about the completion of the IKE negotiation.</li> <li>■ waiting for done—Negotiation is done. The library is waiting for the remote end retransmission timers to expire.</li> <li>■ waiting for remove—Negotiation has failed. The library is waiting for the remote end retransmission timers to expire before removing this negotiation.</li> <li>■ waiting for policy manager—Negotiation is waiting for a response from the policy manager.</li> </ul>
IPSec security associations	<ul style="list-style-type: none"> <li>■ <i>number created</i>: The number of SAs created.</li> <li>■ <i>number deleted</i>: The number of SAs deleted.</li> </ul>

**Table 64: show security ike security-associations Output Fields (continued)**

Field Name	Field Description
Phase 2 negotiations in progress	<p>Number of phase 2 IKE negotiations in progress and status information:</p> <ul style="list-style-type: none"> <li>■ <b>Negotiation type</b>—Type of phase 2 negotiation. The JUNOS software currently supports quick mode.</li> <li>■ <b>Message ID</b>—Unique identifier for a phase 2 negotiation.</li> <li>■ <b>Local identity</b>—Identity of the local phase 2 negotiation. The format is id-type-name (proto-name:port-number,[0..id-data-len] = iddata-presentation)</li> <li>■ <b>Remote identity</b>—Identity of the remote phase 2 negotiation. The format is id-type-name (proto-name:port-number,[0..id-data-len] = iddata-presentation)</li> <li>■ <b>Flags</b>—Notification to the key management process of the status of the IKE negotiation: <ul style="list-style-type: none"> <li>■ <b>caller notification sent</b>—Caller program notified about the completion of the IKE negotiation.</li> <li>■ <b>waiting for done</b>—Negotiation is done. The library is waiting for the remote end retransmission timers to expire.</li> <li>■ <b>waiting for remove</b>—Negotiation has failed. The library is waiting for the remote end retransmission timers to expire before removing this negotiation.</li> <li>■ <b>waiting for policy manager</b>—Negotiation is waiting for a response from the policy manager.</li> </ul> </li> </ul>

**show security ike  
security-associations**

```
user@host> show security ike security-associations
Index Remote Address   State Initiator cookie   Responder cookie   Mode
8 1.1.1.2    UP 3a895f8a9f620198    9040753e66d700bb   Main
Index Remote Address   State Initiator cookie   Responder cookie   Mode
9 1.2.1.3    UP 5ba96hfa9f65067    1 70890755b65b80b   d Main
```

**show security ike  
security-associations  
detail**

```
user@host> show security ike security-associations detail
IKE peer 1.1.1.2, Index 8,
Role: Responder, State: UP
Initiator cookie: 3a895f8a9f620198, Responder cookie: 9040753e66d700bb
Exchange type: Main, Authentication method: Pre-shared keys
Local: 1.1.1.1: 500, Remote: 1.1.1.2:500
Lifetime: Expired in 381 seconds
Algorithms:
Authentication :      md5
Encryption:         3des-cbc
Pseudo random function      hmac-md5
Traffic statistics:
Input bytes:          11268
Output bytes:          6940
Input packets:         57
Output packets        57
Flags: Caller notification sent
IPsec security associations: 0 created, 0 deleted
Phase 2 negotiations in progress: 1

Negotiation type: Quick mode, Role: Responder, Message ID: 1765792815
Local: 1.1.1.1:500, Remote: 1.1.1.2:500
Local identity: No Id
Remote identity: No Id
Flags: Caller notification sent, Waiting for remove
```



```

show security ike security-associations detail (SRX-series devices)
user@host> show security ike security-associations detail1
IKE peer 30.0.0.2, Index 1,
  Location: FPC 1, PIC 2, KMD-Instance 3
  Role: Initiator, State: UP
  Initiator cookie: 58196469ec2df068, Responder cookie: e4de44f4ef333df9
  Exchange type: Main, Authentication method: Pre-shared-keys
  Local: 20.0.0.4:500, Remote: 30.0.0.2:500
  Lifetime: Expires in 1171 seconds
  Algorithms:
    Authentication      : sha1
    Encryption          : 3des-cbc
    Pseudo random function: hmac-sha1
  Traffic statistics:
    Input bytes  :          604
    Output bytes :          1472
    Input packets:           4
    Output packets:          8
  Flags: Caller notification sent
  IPsec security associations: 1 created, 0 deleted
  Phase 2 negotiations in progress: 0

show security ike security-associations index 8 detail
user@host> show security ike security-associations index 8 detail
IKE peer 1.1.1.2, Index 8
  Role: Responder, State:UP
  Initiator cookie: 3a895f8a9f620198, Responder cookie: 9040753e66d700bb
  Exchange type; main, Authentication method: Pre-shared-keys
  Local: 1.1.1.1:500, Remote: 1.1.1.2:500
  Lifetime: Expired in 381 seconds
  Algorithms:
    Authentication:      md5
    Encryption:          3des-cbc
    Pseudo random function  hmac-md5
  Traffic statistics:
    Input bytes:      11268
    Output bytes:      6940
    Input packets:      57
    Output packets:      57
  Flags: Caller notification sent
  IPsec security associations: 0 created, 0 deleted
  Phase 2 negotiations in progress: 1

  Negotiation type: Quick mode, Role: Responder, Message ID: 1765792815
  Local: 1.1.1.1:500, Remote: 1.1.1.2:500
  Local identity: No Id
  Remote identity: No Id
  Flags: Caller notification sent, Waiting for remove

show security ike security-associations 1.1.1.2
user@host> show security ike security-associations 1.1.1.2
Index  Remote Address  State  Initiator cookie  Responder cookie  Mode
8      1.1.1.2             UP     3a895f8a9f620198  9040753e66d700bb  Main

show security ike security-associations fpc 6 pic 1 kmd-instance all
user@host> show security ike security-associations fpc 6 pic 1 kmd-instance all
Index  Remote Address  State  Initiator cookie  Responder cookie  Mode
1728053250 1.1.1.2      UP     fc959afd1070d10b  bdeb7e8c1ea99483  Main

```

## show security ipsec next-hop-tunnels

<b>Syntax</b>	show security ipsec next-hop-tunnels < interface-name <i>interface-name</i> >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display security information about the secure tunnel interface.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display information about all secure tunnel interface.  interface-name <i>interface-name</i> —(Optional) Name of the secure tunnel logical interface.
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security ipsec next-hop-tunnels on page 862
<b>Output Fields</b>	Table 65 on page 862 lists the output fields for the show security ipsec next-hop-tunnels command. Output fields are listed in the approximate order in which they appear.

**Table 65: show security ipsec next-hop-tunnels Output Fields**

Field Name	Field Description
Next-hop gateway	IP address of the next gateway.
Interface	Name of the secure tunnel logical interface.
IPsec VPN name	Name of the IPsec VPN tunnel.
Flag	<ul style="list-style-type: none"> <li>■ Static—IP address manually configured.</li> <li>■ Auto—IP address obtained from the remote peer automatically.</li> </ul>

```

show security ipsec next-hop-tunnels user@host> show security ipsec next-hop-tunnels
Next-hop gateway interface IPsec VPN name Flag
11.1.1.2          st0.0      autokey      Static
11.1.1.3          st0.0      pbd-4-6     Auto

```

## show security ipsec security-associations

---

<b>Syntax</b>	<pre>show security ipsec security-associations &lt;brief   detail&gt; &lt;fpc slot-number&gt; &lt;index SA-index-number&gt; &lt;kmd-instance (all   kmd-instance-name)&gt; &lt;pic slot-number&gt;</pre>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>fpc</b> , <b>pic</b> , and <b>kmd-instance</b> options added in Release 9.3 of JUNOS software.
<b>Description</b>	<p>Display information about the IPSec security associations (SAs).</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p><b>none</b>—Display information about all SAs.</p> <p><b>brief   detail</b>—(Optional) Display the specified level of output.</p> <p><b>fpc slot-number</b>—Specific to SRX-series services gateway. Display information about existing IPsec SAs in this particular Flexible PIC Concentrator (FPC) slot. This option is used to filter the output.</p> <p><b>index SA-index-number</b>—(Optional) Display detailed information about the specified security association identified by index number. To obtain a list of all SAs that includes their index numbers, use the command with no options.</p> <p><b>kmd-instance</b>—Specific to SRX-series services gateway. Display information about existing IPsec SAs in the key management process (daemon) (KMD) identified by the FPC slot-number and PIC slot-number. This option is used to filter the output.</p> <ul style="list-style-type: none"> <li>■ <b>all</b>—All KMD instances running on the Services Processing Unit (SPU)</li> <li>■ <b>kmd-instance-name</b>—Name of the KMD instance running on the SPU.</li> </ul> <p><b>pic slot-number</b>—Specific to SRX-series services gateway. Display information about existing IPsec SAs in this particular PIC slot. This option is used to filter the output.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security ipsec security-associations on page 699
<b>List of Sample Output</b>	<p>show security ipsec security-associations on page 866</p> <p>show security ipsec security-associations index on page 866</p> <p>show security ipsec security-associations brief on page 867</p> <p>show security ipsec security-associations detail on page 867</p> <p>show security ipsec security-associations detail (SRX-series devices) on page 867</p> <p>show security ipsec security-associations fpc 6 pic 1 kmd-instance all (SRX-series devices) on page 868</p>

**Output Fields** Table 66 on page 864 lists the output fields for the `show security ipsec security-associations` command. Output fields are listed in the approximate order in which they appear.

**Table 66: show security ipsec security-associations Table 52: show security ipsec security-associations Table 52: show security ipsec security-associations**

Field Name	Field Description
Total active tunnels	Total number of active IPsec tunnels.
ID	Index number of the SA. You can use this number to get additional information about the SA.
Gateway	IP address of the remote gateway.
Port	If Network Address Translation (NAT-T) is used, this value is 4500. Otherwise it is the standard IKE port, 500.
Algorithm	<p>Cryptography used to secure exchanges between peers during the IKE Phase 2 negotiations includes</p> <ul style="list-style-type: none"> <li>■ An authentication algorithm used to authenticate exchanges between the peers. Options are <code>hmac-md5-95</code>, <code>hmac-sha1-96</code>, or <code>ESP</code>.</li> <li>■ An encryption algorithm used to encrypt data traffic. Options are <code>3des-cbc</code>, <code>aes-128-cbc</code>, <code>aes-192-cbc</code>, <code>aes-256-cbc</code>, or <code>des-cbc</code>.</li> </ul>
SPI	Security parameter index (SPI) identifier. An SA is uniquely identified by an SPI. Each entry includes the name of the VPN, the remote gateway address, the SPIs for each direction, the encryption and authentication algorithms, and keys. The peer gateways each have two SAs, one resulting from each of the two phases of negotiation: Phase 1 and Phase 2.
Life: sec/kb	The lifetime of the SA, after which it expires, expressed either in seconds or kilobytes.
Sta	<p>State has two options, Installed and Not Installed.</p> <ul style="list-style-type: none"> <li>■ Installed—The security association is installed in the security association database.</li> <li>■ Not Installed—The security association is not installed in the security association database.</li> </ul> <p>For <code>transport</code> mode, the value of State is always Installed.</p>
Mon	The Mon refers to VPN monitoring status. If VPN monitoring is enabled, then this will show U (up) or D (down). A hyphen (-) means VPN monitoring is not enabled for this SA.
vsys or Virtual-system	The root system.
Tunnel index	Numeric identifier of the specific IPSec tunnel for the SA.
Local gateway	Gateway address of the local system.
Remote gateway	Gateway address of the remote system.
Local identity	Identity of the local peer so that its partner destination gateway can communicate with it. The value is specified as an IPv4 address, fully qualified domain name, e-mail address, or distinguished name.

**Table 66: show security ipsec security-associations Table 52: show security ipsec security-associations Table 52: show security ipsec security-associations (continued)**

Field Name	Field Description
Remote identity	IPv4 address of the destination peer gateway.
DF-bit	State of the don't fragment bit: set or cleared.
Policy-name	Name of the applicable policy.
Location	<p>FPC—Flexible PIC Concentrator (FPC) slot number.</p> <p>PIC—PIC slot number.</p> <p>KMD-Instance—The name of the kmd-instance running on the SPU, identified by the FPC slot-number and PIC slot-number. Currently, 4 kmd-instances running on each SPU and any particular IPsec negotiation is carried out by a single kmd-instance.</p>
Direction	Direction of the security association; it can be inbound or outbound.
AUX-SPI	<p>Value of the auxiliary security parameter index.</p> <ul style="list-style-type: none"> <li>■ When the value is AH or ESP, AUX-SPI is always 0.</li> <li>■ When the value is AH+ESP, AUX-SPI is always a positive integer.</li> </ul>
Mode	<p>Mode of the security association:</p> <ul style="list-style-type: none"> <li>■ transport—Protects host-to-host connections.</li> <li>■ tunnel—Protects connections between security gateways.</li> </ul>
Type	<p>Type of the security association:</p> <ul style="list-style-type: none"> <li>■ manual—Security parameters require no negotiation. They are static and are configured by the user.</li> <li>■ dynamic—Security parameters are negotiated by the IKE protocol. Dynamic security associations are not supported in transport mode.</li> </ul>
State	<p>State of the security association:</p> <ul style="list-style-type: none"> <li>■ Installed—The security association is installed in the security association database.</li> <li>■ Not Installed—The security association is not installed in the security association database.</li> </ul> <p>For transport mode, the value of <b>State</b> is always <b>Installed</b>.</p>
Protocol	<p>Protocol supported.</p> <ul style="list-style-type: none"> <li>■ Transport mode supports Encapsulation Security Protocol (ESP) and Authentication Header (AH).</li> <li>■ Tunnel mode supports ESP and AH <ul style="list-style-type: none"> <li>■ Authentication—Type of authentication used.</li> <li>■ Encryption—Type of encryption used.</li> </ul> </li> </ul>

**Table 66: show security ipsec security-associations Table 52: show security ipsec security-associations Table 52: show security ipsec security-associations (continued)**

Field Name	Field Description
Soft lifetime	<p>The soft lifetime informs the IPSec key management system that the SA is about to expire.</p> <p>Each lifetime of a security association has two display options, hard and soft, one of which must be present for a dynamic security association. This allows the key management system to negotiate a new SA before the hard lifetime expires.</p> <ul style="list-style-type: none"> <li>■ Expires in seconds—Number of seconds left until the SA expires.</li> </ul>
Hard lifetime	<p>The hard lifetime specifies the lifetime of the SA.</p> <ul style="list-style-type: none"> <li>■ Expires in seconds—Number of seconds left until the SA expires.</li> </ul>
Lifesize Remaining	<p>The lifesize remaining specifies the usage limits in kilobytes. If there is no lifesize specified, it shows unlimited.</p> <ul style="list-style-type: none"> <li>■ Expires in kilobytes—Number of kilobytes left until the SA expires.</li> </ul>
Anti-replay service	State of the service that prevents packets from being replayed. It can be <b>Enabled</b> or <b>Disabled</b> .
Replay window size	<p>Configured size of the antireplay service window. It can be 32 or 64 packets. If the replay window size is 0, the antireplay service is disabled.</p> <p>The antireplay window size protects the receiver against replay attacks by rejecting old or duplicate packets.</p>

**show security ipsec security-associations**

```
user@host> show security ipsec security-associations
Total active tunnels: 1
ID Gateway  Port  Algorithm  SPI   Life:sec/kb Sta vsys
5 5.5.5.4    500   esp:3des/sha1  ed0cec21  expir unlim I/I      0
5 5.5.5.4    500   esp:3des/sha1
```

**show security ipsec security-associations index**

```
user@host> show security ipsec security-associations index 5
Virtual-system: Root
Local gateway: 1.1.1.1, Remote gateway: 1.1.1.2
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0...7]=0.0.0.0/0)
DF-bit: clear
Policy-name: my-policy

Direction: inbound, SPI: 494001027, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expired
Hard lifetime: Expired in 130 seconds
Lifesize Remaining: Unlimited
Anti-replay service: Enabled, Replay window size: 64

Direction: inbound, SPI: 1498711950, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 40 seconds
```

Hard lifetime: Expires in 175 seconds  
 Lifesize Remaining: Unlimited  
 Anti-replay service: Enabled, Replay window size: 64

Direction: outbound, SPI: 4038397695, AUX-SPI: 0  
 Mode: tunnel, Type: dynamic, State: Installed  
 Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc  
 Soft lifetime: Expires in 40 seconds  
 Hard lifetime: Expires in 175 seconds  
 Lifesize Remaining: Unlimited  
 Anti-replay service: Enabled, Replay window size: 64

**show security ipsec  
 security-associations  
 brief**

user@host> **show security ipsec security-associations brief**  
 Total active tunnels: 2  
 ID Gateway Port Algorithm SPI Life:sec/kb Mon vsys  
 <16384 1.1.1.1 500 ESP:3des/sha1 af88baa 28795/unlim D 0  
 >16384 1.1.1.1 500 ESP:3des/sha1 f4e3e5f4 28795/unlim D 0

**show security ipsec  
 security-associations  
 detail**

user@host> **show security ipsec security-associations detail**  
 Virtual-system: Root  
 Local Gateway: 1.1.1.2, Remote Gateway: 1.1.1.1  
 Local Identity: ipv4\_subnet(any:0,[0..7]=0.0.0.0/0)  
 Remote Identity: ipv4\_subnet(any:0,[0..7]=0.0.0.0/0)  
 DF-bit: clear

Direction: inbound, SPI: 184060842, AUX-SPI: 0  
 Hard lifetime: Expires in 28785 seconds  
 Lifesize Remaining: Unlimited  
 Soft lifetime: Expired  
 Mode: tunnel, Type: dynamic, State: installed, VPN Monitoring: DOWN  
 Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc  
 Anti-replay service: enabled, Replay window size: 32

Direction: outbound, SPI: 4108576244, AUX-SPI: 0  
 Hard lifetime: Expires in 28785 seconds  
 Lifesize Remaining: Unlimited  
 Soft lifetime: Expired  
 Mode: tunnel, Type: dynamic, State: installed, VPN Monitoring: DOWN  
 Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc  
 Anti-replay service: enabled, Replay window size: 32

**show security ipsec  
 security-associations  
 detail (SRX-series  
 devices)**

user@host> **show security ipsec security-associations detail**  
 Virtual-system: Root  
 Local Gateway: 20.0.0.4, Remote Gateway: 30.0.0.2  
 Local Identity: ipv4\_subnet(any:0,[0..7]=0.0.0.0/0)  
 Remote Identity: ipv4(any:0,[0..3]=20.0.0.4)  
 DF-bit: clear  
 Policy-name: p1

Location: FPC 1, PIC 2, KMD-Instance 3  
 Direction: inbound, SPI: 3727011331, AUX-SPI: 0  
 Hard lifetime: Expires in 3570 seconds  
 Lifesize Remaining: Unlimited  
 Soft lifetime: Expires in 3525 seconds  
 Mode: tunnel, Type: dynamic, State: installed, VPN Monitoring: -  
 Protocol: ESP, Authentication: hmac-sha1-96, Encryption: aes-cbc (128 bits)  
 Anti-replay service: enabled, Replay window size: 32

Location: FPC 1, PIC 2, KMD-Instance 3  
 Direction: outbound, SPI: 4212479378, AUX-SPI: 0  
 Hard lifetime: Expires in 3570 seconds

```

Lifesize Remaining: Unlimited
Soft lifetime: Expires in 3525 seconds
Mode: tunnel, Type: dynamic, State: installed, VPN Monitoring: -
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: aes-cbc (128 bits)
Anti-replay service: enabled, Replay window size: 32

```

```

show security ipsec security-associations fpc 6 pic 1 kmd-instance all
(SRX-series devices)
user@host> show security ipsec security-associations fpc 6 pic 1 kmd-instance all
Total active tunnels: 1

```

ID	Gateway	Port	Algorithm	SPI	Life:sec/kb	Mon	vsys
<2	1.1.1.2	500	ESP:3des/sha1	67a7d25d	28280/unlim	-	0
>2	1.1.1.2	500	ESP:3des/sha1	a23cbcdc	28280/unlim	-	0



## show security ipsec statistics

<b>Syntax</b>	show security ipsec statistics fpc <i>slot-number</i> <index <i>SA-index-number</i> > pic <i>slot-number</i>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>fpc</b> and <b>pic</b> options added in Release 9.3 of JUNOS software.
<b>Description</b>	Display standard IPsec statistics.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display statistics about all IPsec security associations (SAs).  <b>fpc <i>slot-number</i></b> —Specific to SRX-series services gateway. Display statistics about existing IPsec SAs in this particular Flexible PIC Concentrator (FPC) slot. This option is used to filter the output.  <b>index <i>SA-index-number</i></b> —(Optional) Display statistics for the SA with this index number.  <b>pic <i>slot-number</i></b> —Specific to SRX-series services gateway. Display statistics about existing IPsec SAs in this particular PIC slot. This option is used to filter the output.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security ipsec statistics on page 700
<b>List of Sample Output</b>	show security ipsec statistics on page 870 show security ipsec statistics index 5 on page 870 show security ipsec statistics fpc 6 pic 1 (SRX-series devices) on page 871
<b>Output Fields</b>	Table 67 on page 869 lists the output fields for the <b>show security ipsec statistics</b> command. Output fields are listed in the approximate order in which they appear.

**Table 67: show security ipsec statistics Output Fields**

Field Name	Field Description
Virtual-system	The root system.
ESP Statistics:	<ul style="list-style-type: none"> <li>■ <b>Encrypted bytes</b>—Total number of bytes encrypted by the local system across the IPsec tunnel.</li> <li>■ <b>Decrypted bytes</b>—Total number of bytes decrypted by the local system across the IPsec tunnel.</li> <li>■ <b>Encrypted packets</b>—Total number of packets encrypted by the local system across the IPsec tunnel.</li> <li>■ <b>Decrypted packets</b>—Total number of packets decrypted by the local system across the IPsec tunnel.</li> </ul>

**Table 67: show security ipsec statistics Output Fields** (continued)

Field Name	Field Description
AH Statistics:	<ul style="list-style-type: none"> <li>■ <b>Input bytes</b>—Total number of bytes received by the local system across the IPsec tunnel.</li> <li>■ <b>Output bytes</b>—Total number of bytes transmitted by the local system across the IPsec tunnel.</li> <li>■ <b>Input packets</b>—Total number of packets received by the local system across the IPsec tunnel.</li> <li>■ <b>Output packets</b>—Total number of packets transmitted by the local system across the IPsec tunnel.</li> </ul>
Errors	<ul style="list-style-type: none"> <li>■ <b>AH authentication failures</b>—Total number of authentication header (AH) failures. An AH failure occurs when there is a mismatch of the authentication header in a packet transmitted across an IPsec tunnel.</li> <li>■ <b>Replay errors</b>—Total number of replay errors. A replay error is generated when a duplicate packet is received within the replay window.</li> <li>■ <b>ESP authentication failures</b>—Total number of Encapsulation Security Payload (ESP) failures. An ESP failure occurs when there is an authentication mismatch in ESP packets.</li> <li>■ <b>ESP decryption failures</b>—total number of ESP decryption errors.</li> <li>■ <b>Bad headers</b>—Total number of invalid headers detected.</li> <li>■ <b>Bad trailers</b>—Total number of invalid trailers detected.</li> </ul>

```

show security ipsec statistics  user@host> show security ipsec statistics
Virtual-system: Root
ESP Statistics:
  Encrypted bytes:          0
  Decrypted bytes:         0
  Encrypted packets:       0
  Decrypted packets:       0
AH Statistics:
  Input bytes:             0
  Output bytes:            0
  Input packets:           0
  Output packets:          0
Errors:
  AH authentication failures: 0, Replay errors: 0
  ESP authentication failures: 0, ESP decryption failures: 0
  Bad headers: 0, Bad trailers: 0

```

```

show security ipsec statistics index 5  user@host> show security ipsec statistics index 5
Virtual-system: Root
SA index: 5
ESP Statistics:
  Encrypted bytes:          0
  Decrypted bytes:         0
  Encrypted packets:       0
  Decrypted packets:       0
AH Statistics:
  Input bytes:             0
  Output bytes:            0
  Input packets:           0
  Output packets:          0

```

Errors:

AH authentication failures: 0, Replay errors: 0

ESP authentication failures: 0, ESP decryption failures: 0

Bad headers: 0, Bad trailers: 0

**show security ipsec  
statistics fpc 6 pic 1  
(SRX-series devices)**

user@host> **show security ipsec statistics fpc 6 pic 1**

ESP Statistics:

Encrypted bytes: 536408

Decrypted bytes: 696696

Encrypted packets: 1246

Decrypted packets: 888

AH Statistics:

Input bytes: 0

Output bytes: 0

Input packets: 0

Output packets: 0

Errors:

AH authentication failures: 0, Replay errors: 0

ESP authentication failures: 0, ESP decryption failures: 0

Bad headers: 0, Bad trailers: 0

## show security monitoring fpc fpc-number

<b>Syntax</b>	show security monitoring fpc <i>fpc-number</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display security monitoring information about the FPC slot.  This command is supported on SRX-series devices.
<b>Options</b>	<p><i>fpc-number</i> —Display security monitoring information for the specified FPC slot. It can be in the range from 0 to 11.</p> <p><i>node</i>—(Optional) For chassis cluster configurations, display security monitoring information for the specified FPC on a specific node (device) in the cluster.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security monitoring fpc 1 on page 872 show security monitoring fpc 8 on page 873
<b>Output Fields</b>	Table 68 on page 872 lists the output fields for the <b>show security monitoring fpc fpc-number</b> command. Output fields are listed in the approximate order in which they appear.

**Table 68: show security monitoring fpc fpc-number Output Fields**

Field Name	Field Description
FPC	Slot number in which the FPC is installed. It can be between 0 to 11.
PIC	Slot number in which the PIC is installed.
CPU Utilization (%)	Total percentage of CPU being used by the PIC's processors.
Memory Utilization (%)	Percentage of heap space (dynamic memory) being used by the PIC's processor. If this number exceeds 80 percent, there may be a software problem (memory leak).

```

show security      user@host> show security monitoring fpc 1
monitoring fpc 1  FPC 1
                    PIC 0
                    CPU utilization   :    0 %
                    Memory Utilization:   67 %

```

```

PIC 1
  CPU utilization   :    0 %
  Memory Utilization:   67 %

show security
monitoring fpc 8
user@host> show security monitoring fpc 8
node0:
-----
FPC 8
  PIC 0
    CPU utilization   :    0 %
    Memory Utilization:   74 %
node1:
-----
FPC 8
  PIC 0
    CPU utilization   :    0 %
    Memory Utilization:   74 %
  PIC 1
    CPU utilization   :    0 %
    Memory Utilization:   43 %

```

## show security nat destination pool

<b>Syntax</b>	show security nat destination pool < <i>pool-name</i> > all
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display information about the specified Network Address Translation (NAT) destination address pool.  This command is supported on SRX-series devices.
<b>Options</b>	<i>pool-name</i> —Name of the destination address pool.  all—Display information about all the destination NAT address pool.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	pool (Destination NAT Services Gateway)
<b>List of Sample Output</b>	show security nat destination pool dst-nat-pool1 on page 874 show security nat destination pool all on page 875
<b>Output Fields</b>	Table 69 on page 874 lists the output fields for the show security nat destination pool command. Output fields are listed in the approximate order in which they appear.

**Table 69: show security nat destination pool Output Fields**

Field Name	Field Description
Pool Name	Name of the destination pool.
Pool id	Pool identification number.
Routing Instance	Name of the routing instance.
Total address	Number of IP addresses that are in use.
Address available	Number of IP addresses that are free for use.
Address range	IP address or IP address range for the pool.
Port	Port number.
Total destination nat pool number	Number of destination NAT pools.

```

show security nat destination pool dst-nat-pool1
user@host> show security nat destination pool dst-nat-pool1
Pool name:      dst-nat-pool1
Pool id:        1
Routing instance: ri-green

```

```

Total address:      1
Address available:  1
Address range              Port
10.1.1.150-10.1.1.150

```

**show security nat destination pool all**     user@host> **show security nat destination pool all**

```

Total destination nat pool number: 3

Pool name:          dst-nat-pool1
Pool id:            1
Routing instance:   ri-green
Total address:      1
Address available:  1
Address range              Port
10.1.1.150-10.1.1.150
Pool name:          dst-nat-pool2
Pool id:            2
Routing instance:   ri-green
Total address:      21
Address available:  10
Address range              Port
10.1.1.160-10.1.1.180
Pool name:          dst-nat-pool3
Pool id:            3
Routing instance:   ri-green
Total address:      1
Address available:  1
Address range              Port
10.1.1.190-10.1.1.190      8080

```

## show security nat destination rule

<b>Syntax</b>	show security nat destination rule <rule-name> all
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display information about the specified destination Network Address Translation (NAT) rule.  This command is supported on SRX-series devices.
<b>Options</b>	<i>rule-name</i> —Name of the rule.  all—Display information about all the destination NAT rule.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	rule (Destination NAT)
<b>List of Sample Output</b>	show security nat destination rule r4 on page 877 show security nat destination rule all on page 877
<b>Output Fields</b>	Table 70 on page 876 lists the output fields for the show security nat destination rule command. Output fields are listed in the approximate order in which they appear. Table 71 lists the output fields for the show security nat destination rule command. Output fields are listed in the approximate order in which they appear.

**Table 70: show security nat destination rule Output Fields**

Field Name	Field Description
Destination nat rule	Name of the destination NAT rule.
State	Status of the IP address: <ul style="list-style-type: none"> <li>■ <b>Active</b>—Denotes that the IP address is in use.</li> <li>■ <b>Free</b>—IP address is available for allocation.</li> </ul>
Index	Rule index number.
From routing instance	Name of the routing instance from which the packet comes.
Source address	Name of the source addresses which match the rule. The default value is any.
Destination address	Name of the destination addresses which match the rule. The default value is any.
Destination ports	Destination ports number which match the rule. The default value is any.



**Table 70: show security nat destination rule Output Fields** *(continued)*

Field Name	Field Description
Action	The action taken in regard to a packet that matches the rule's tuples. Actions include the following: <ul style="list-style-type: none"> <li>■ <b>destination-nat</b>—Use user-defined destination NAT pool to perform destination NAT.</li> <li>■ <b>ui</b>—Do not perform destination NAT.</li> </ul>
Hit times	Number of times a translation in the translation table is used for a destination NAT rule.
Fail times	Number of times a translation in the translation table failed to translate for a destination NAT rule.
Total destination nat rule number	Number of destination NAT rules.
Total hit times	Number of times a translation in the translation table is used for all the destination NAT rules.
Total fail times	Number of times a translation in the translation table failed to translate for all the destination NAT rules.

```

show security nat      user@host>show security nat destination rule r4
destination rule r4  Destination nat rule: r4, State: enabled, Index: 7
                        From routing instance: ri-1
                        Source addresses:
                        any: 0.0.0.0/0
                        Destination addresses:
                        1.1.1.1/32 1.1.1.3/32
                        Destination ports:
                        any: 0
                        Action: destination-nat pool d1

                        Hit times: 30
                        Fail times: 0

```

```

show security nat      user@host> show security nat destination rule all
destination rule all  Total destination nat rule number: 2
                        Total hit times: 45
                        Total fail times: 3

                        Destination nat rule: r4, State: enabled, Index: 7
                        From routing instance: ri-1
                        Source addresses:
                        any: 0.0.0.0/0
                        Destination addresses:
                        1.1.1.1/32 1.1.1.3/32
                        Destination ports:
                        any: 0
                        Action: destination-nat pool d1

                        Hit times: 30
                        Fail times: 0

                        Destination nat rule: r5, State: enabled, Index: 8

```

```
From routing instance: ri-1, interface: fe-0/0/0.0
Source addresses:
  any: 0.0.0.0/0
Destination addresses:
  1.1.1.1/32
Destination ports:
  any: 0
Action: destination-nat pool d3

Hit times: 15
Fail times: 3
```

## show security nat destination summary

<b>Syntax</b>	show security nat destination summary
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	<p>Display a summary of Network Address Translation (NAT) destination pool information.</p> <p>This command is supported on SRX-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>pool (Destination NAT Services Gateway)</p> <p>rule (Destination NAT)</p>
<b>List of Sample Output</b>	show security nat destination summary on page 879
<b>Output Fields</b>	Table 71 on page 879 lists the output fields for the show security nat destination summary command. Output fields are listed in the approximate order in which they appear.

**Table 71: show security nat destination summary Output Fields**

Field Name	Field Description
Total destination nat pool number	Number of destination NAT pools.
Pool name	Name of the destination address pool.
Address range	IP address or IP address range for the pool.
Routing Instance	Name of the routing instance.
Port	Port number.
Total	Number of IP addresses that are in use.
Available	Number of IP addresses that are free for use.
Total destination nat rule number	Number of destination NAT rules.
Total hit times	Number of times a translation in the translation table is used for all the destination NAT rules.
Total fail times	Number of times a translation in the translation table failed to translate for all the destination NAT rules.

**show security nat destination summary**    user@host> **show security nat destination summary**

Total destination nat pool number: 3

Pool name	Address range	Routing instance	Port	Total	Available
dst-nat-pool1	10.1.1.150-10.1.1.150	ri-green		1	1
dst-nat-pool2	10.1.1.160-10.1.1.180	ri-green		21	10
dst-nat-pool3	10.1.1.190-10.1.1.190	ri-green	8080	1	1

Total destination nat rule number: 2

Total hit times: 45

Total fail times: 3

## show security nat destination-nat summary

<b>Syntax</b>	show security nat destination-nat summary <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display a summary of destination Network Address Translation (NAT) information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Display a summary of destination NAT information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display a summary of destination NAT information on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	destination-nat
<b>List of Sample Output</b>	show security nat destination-nat summary on page 881
<b>Output Fields</b>	Table 72 on page 881 lists the output fields for the <b>show security nat destination-nat summary</b> command. Output fields are listed in the approximate order in which they appear.

**Table 72: show security nat destination-nat summary Output Fields**

Field Name	Field Description
Pool name	Name of destination pool.
Address range	IP address or IP address range for the pool.
Port	Port number associated with IP address (if previously configured).

```

show security nat destination-nat summary
user@host> show security nat destination-nat summary
Pool name      Address range      Port
d1             1.1.1.1
d2             1.1.1.2            12345
d3             111.11.111.100 - 111.111.111.200

```

## show security nat incoming-table

<b>Syntax</b>	show security nat incoming-table <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display Network Address Translation (NAT) table information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Display all information NAT incoming table.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display incoming table information on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security nat incoming-table on page 701
<b>List of Sample Output</b>	show security nat incoming-table on page 883
<b>Output Fields</b>	Table 73 on page 882 lists the output fields for the <b>show security nat incoming-table</b> command. Output fields are listed in the approximate order in which they appear.

**Table 73: show security nat incoming-table Output Fields**

Field Name	Field Description
In use	Number of entries in the NAT table.
Maximum	Maximum number of entries possible in the NAT table.
Entry allocation failed	Number of entries failed for allocation.
Destination	Destination IP address and port number.
Host	Host IP address and port number that the destination IP address is mapped.
References	Number of sessions referencing the entry.
Timeout	Timeout, in seconds, of the entry in the NAT table.
Source-pool	Name of source pool where translation is allocated.

```
show security nat incoming-table user@host> show security nat incoming-table
incoming-table In use: 1, Maximum: 1024, Entry allocation failed: 0
Destination      Host              References Timeout Source-pool
10.1.1.26:1028    1.1.1.10:5060    1          3600 p1
```

## show security nat interface-nat-ports

<b>Syntax</b>	show security nat interface-nat-ports <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display port usage for an interface source pool for Network Address Translation (NAT).  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display all port usage information for an interface source pool.</p> <p>node—(Optional) For chassis cluster configurations, display interface NAT ports information on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security nat interface-nat-ports on page 884
<b>Output Fields</b>	Table 74 on page 884 lists the output fields for the show security nat interface-nat-ports command. Output fields are listed in the approximate order in which they appear.

**Table 74: show security nat interface-nat-ports Output Fields**

Field Name	Field Description
Pool Index	Port pool index.
Total Ports	Total number of ports in a port pool. In services gateway, 10 interface NAT ports are supported.
Single Ports Allocated	Number of ports allocated one at a time that are in use.
Single Ports Available	Number of ports allocated one at a time that are free for use.
Twin Ports Allocated	Number of ports allocated two at a time that are in use.
Twin Ports Available	Number of ports allocated two at a time that are free for use.

**show security nat interface-nat-ports**    user@host> show security nat interface-nat-ports



Pool	Total	Single ports	Single ports	Twin ports	Twin ports
index	ports	allocated	available	allocated	available
0	64510	0	63486	0	1024
1	64510	0	63486	0	1024
2	64510	0	63486	0	1024
3	64510	0	63486	0	1024
4	64510	0	63486	0	1024
5	64510	0	63486	0	1024
6	64510	0	63486	0	1024
7	64510	0	63486	0	1024
8	64510	0	63486	0	1024
9	64510	0	63486	0	1024

## show security nat source pool

<b>Syntax</b>	show security nat source pool < <i>pool-name</i> > all
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display information about the specified Network Address Translation (NAT) source address pool.  This command is supported on SRX-series devices.
<b>Options</b>	<i>pool-name</i> —Name of the source pool.  all—Display information about all the source NAT address pool.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	pool (Source NAT Services Gateway)
<b>List of Sample Output</b>	show security nat source pool src-nat-pool1 on page 887 show security nat source pool all on page 887
<b>Output Fields</b>	Table 75 on page 886 lists the output fields for the <b>show security nat source pool</b> command. Output fields are listed in the approximate order in which they appear.

**Table 75: show security nat source pool Output Fields**

Field Name	Field Description
Pool name	Name of the source pool.
Pool id	Pool identification number.
Routing Instance	Name of the routing instance.
Port range	Port number range for the pool.
Total address	Number of IP addresses that are in use.
Address available	Number of IP addresses that are free for use.
Address range	IP address or IP address range for the pool.
Single ports	Number of allocated single ports.
Twin ports	Number of allocated twin ports.

```

show security nat user@host> show security nat source pool src-nat-pool1
source pool      Pool name:      src-nat-pool1
src-nat-pool1    Pool id:       1
                  Routing instance: ri-1
                  Port range:    [2000,63000]
                  Total address:  1
                  Address available: 1
                  Address range   Single ports Twin ports
                  30.30.30.6-30.30.30.6      0          0

```

```

show security nat user@host> show security nat source pool all
source pool all  Total source nat pool number: 2
                  Pool name:      src-nat-pool1
                  Pool id:       1
                  Routing instance: ri-1
                  Port range:    [2000,63000]
                  Total address:  1
                  Address available: 1
                  Address range   Single ports Twin ports
                  30.30.30.6-30.30.30.6      0          0
                  Pool name:      src-nat-pool2
                  Pool id:       2
                  Routing instance: ri-1
                  Port translation: no
                  Total address:  81
                  Address available: 50
                  Address range   Single ports Twin ports
                  10.0.0.20-10.0.0.100      0          0

```

## show security nat source rule

<b>Syntax</b>	show security nat source rule <rule-name> all
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display information about the specified source Network Address Translation (NAT) rule.  This command is supported on SRX-series devices.
<b>Options</b>	<i>rule-name</i> —Name of the rule.  all—Display information about all the source NAT rule.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	rule (Source NAT)
<b>List of Sample Output</b>	show security nat source rule r1 on page 889 show security nat source rule all on page 889
<b>Output Fields</b>	Table 76 on page 888 lists the output fields for the show security nat source rule command. Output fields are listed in the approximate order in which they appear

**Table 76: show security nat source rule Output Fields**

Field Name	Field Description
Source nat rule	Name of the source NAT rule.
State	Status of the IP address: <ul style="list-style-type: none"> <li>■ Active—Denotes that the IP address is in use.</li> <li>■ Free—IP address is available for allocation.</li> </ul>
Index	Rule index number.
From routing instance	Name of the routing instance from which the packet comes.
To routing instance	Name of the routing instance in which packet should reach.
Source address	Name of the source addresses which match the rule. The default value is any.
Destination address	Name of the destination addresses which match the rule. The default value is any.
Destination ports	Destination ports number which match the rule. The default value is any.

**Table 76: show security nat source rule Output Fields** (continued)

Field Name	Field Description
Action	<p>The action taken in regard to a packet that matches the rule's tuples. Actions include the following:</p> <ul style="list-style-type: none"> <li>■ off—Do not perform source NAT.</li> <li>■ source-nat—Use user-defined source NAT pool to perform source NAT</li> <li>■ interface—Use egress interface's IP address to perform source NAT.</li> </ul>
Hit times	Number of times a translation in the translation table is used for a source NAT rule.
Fail times	Number of times a translation in the translation table failed to translate for a source NAT rule.
Total destination nat rule number	Number of destination NAT rules.
Total hit times	Number of times a translation in the translation table is used for all the source NAT rules.
Total fail times	Number of times a translation in the translation table failed to translate for all the source NAT rules.

```

show security nat user@host> show security nat source rule r1
source rule r1      Source nat rule: r1, State: enabled, Index: 4
                      From routing instance: ri-2
                      To routing instance: ri-1
                      Source addresses:
                        any: 0.0.0.0/0
                      Destination addresses:
                        any: 0.0.0.0/0
                      Action: source-nat pool s1

                      Hit times: 22
                      Fail times: 2

```

```

show security nat user@host> show security nat source rule all
source rule all      Total source nat rule number: 2
                      Total hit times: 32
                      Total fail times: 2

                      Source nat rule: r1, State: enabled, Index: 4
                      From routing instance: ri-2
                      To routing instance: ri-1
                      Source addresses:
                        any: 0.0.0.0/0
                      Destination addresses:
                        any: 0.0.0.0/0
                      Action: source-nat pool s1

                      Hit times: 22
                      Fail times: 2

                      Source nat rule: r2, State: enabled, Index: 5
                      From routing instance: ri-2, zone: z3 z4
                      To routing instance: ri-1

```

```
Source addresses:  
  any: 0.0.0.0/0  
Destination addresses:  
  any: 0.0.0.0/0  
Action: source-nat pool s2  
  
Hit times: 10  
Fail times: 0
```

## show security nat source summary

<b>Syntax</b>	show security nat source summary
<b>Release Information</b>	Command introduced in Release 9.2 of JUNOS software.
<b>Description</b>	Display a summary of Network Address Translation (NAT) source pool information.  This command is supported on SRX-series devices.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	pool (Source NAT Services Gateway)  rule (Source NAT)
<b>List of Sample Output</b>	show security nat source summary on page 891
<b>Output Fields</b>	Table 77 on page 891 lists the output fields for the show security nat source summary command. Output fields are listed in the approximate order in which they appear.

**Table 77: show security nat source summary Output Fields**

Field Name	Field Description
Total source nat pool number	Number of source NAT pools.
Pool name	Name of the source address pool.
Address range	IP address or IP address range for the pool.
Routing Instance	Name of the routing instance.
PAT IP	Whether Port Address Translation (PAT) is enabled (yes or no).
total IP	Number of IP addresses that are in use.
available	Number of IP addresses that are free for use.
Total source nat rule number	Number of source NAT rules.
Total hit times	Number of times a translation in the translation table is used for all the source NAT rules.
Total fail times	Number of times a translation in the translation table failed to translate for all the source NAT rules.

```

show security nat source summary user@host> show security nat source summary
Total source nat pool number: 2
Pool name      Address range  Routing instance PAT IP total IP available
src-nat-pool1  30.30.30.6-30.30.30.6  ri-1      yes    1        1
src-nat-pool2  10.0.0.20-10.0.0.100  ri-1      no     81       50

```

```
Total source nat rule number: 1
Total hit times: 22
Total fail times: 2
```



## show security nat source-nat pool

<b>Syntax</b>	show security nat source-nat pool <i>pool-name</i> <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display information about the specified Network Address Translation (NAT) source address pool.  This command is supported on J-series devices.
<b>Options</b>	<i>pool-name</i> —Name of the source pool.  <b>node</b> —(Optional) For chassis cluster configurations, display source NAT information of this pool on specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	source-nat
<b>List of Sample Output</b>	show security nat source-nat pool source-pool-with-pat on page 894
<b>Output Fields</b>	Table 78 on page 893 lists the output fields for the <b>show security nat source-nat pool</b> command. Output fields are listed in the approximate order in which they appear.

**Table 78: show security nat source-nat pool Output Fields**

Field Name	Field Description
Pool Name	Name of the source pool.
Address	IP address in the source pool.
Status	Status of the IP address: <ul style="list-style-type: none"> <li>■ <b>Active</b>—Denotes that the IP address is in use. This status applies only to source NAT without Port Address Translation (PAT).</li> <li>■ <b>Free</b>—IP address is available for allocation.</li> </ul>
Single Ports	Number of allocated single ports.
Twin Ports	Number of allocated twin ports.

**Table 78: show security nat source-nat pool Output Fields** *(continued)*

Field Name	Field Description
PAT	Whether PAT is enabled (Yes or No).

```

show security nat      user@host> show security nat source-nat pool source-pool-with-pat
source-nat pool      Pool Name           Address      Status      Single Ports  Twin Ports  PAT
source-pool-with-pat source-pool-with-pat 10.1.1.200  Free        0             0          Yes

```

## show security nat source-nat summary

<b>Syntax</b>	show security nat source-nat summary <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display a summary of Network Address Translation (NAT) source pool information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Display a summary of NAT source pool information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display source NAT summary information on specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	source-nat (NAT)
<b>List of Sample Output</b>	show security nat source-nat summary on page 895
<b>Output Fields</b>	Table 79 on page 895 lists the output fields for the <b>show security nat source-nat summary</b> command. Output fields are listed in the approximate order in which they appear.

**Table 79: show security nat source-nat summary Output Fields**

Field Name	Field Description
Pool Name	Name of source pool.
Address Low	Starting IP address of one address range in the source pool.
Address High	Ending IP address of one address range in the source pool.
Interface	Name of the interface on which the source pool is defined.
PAT	Whether Port Address Translation (PAT) is enabled (Yes or No).

```

show security nat source-nat summary
user@host> show security nat source-nat summary
Pool Name      Address Low    Address High   Interface      PAT
p1             10.1.1.2      10.1.1.2      ge-0/0/0.0     Yes
p2 10.1.1.2    10.1.1.2      ge-0/0/0.0     Yes

```

## show security nat static rule

<b>Syntax</b>	show security nat static rule <rule-name> all
<b>Release Information</b>	Command introduced in Release 9.3 of JUNOS software.
<b>Description</b>	Display information about the specified static Network Address Translation (NAT) rule.  This command is supported on SRX-series devices.
<b>Options</b>	<i>rule-name</i> —Name of the rule.  all—Display information about all the static NAT rules.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	rule (Static NAT)
<b>List of Sample Output</b>	show security nat static rule rsr11 on page 897 show security nat static rule all on page 897
<b>Output Fields</b>	Table 80 on page 896 lists the output fields for the <b>show security nat static rule</b> command. Output fields are listed in the approximate order in which they appear.

**Table 80: show security nat static rule Output Fields**

Field Name	Field Description
Static nat rule	Name of the static NAT rule.
Rule-set	Name of the rule-set. Currently, you can configure 8 rules within the same rule-set.
Rule-Id	Rule ID number.
Rule-position	Position of the rules indicates the order that they apply to traffic.
From interface	Name of the interface from which the packet comes.
From routing instance	Name of the routing instance from which the packet comes.
Destination address	Name of the destination addresses that match the rule.
Host addresses	Name of the host addresses that match the rule.
Netmask	Subnet IP address.
Translation hits	Number of times a translation in the translation table is used for a static NAT rule.

```

show security nat static rule rsr11 user@host> show security nat static rule rsr11
Static NAT rule: rsr11 Rule-set: rsr1
Rule-Id : 1
Rule position : 4
From routing instance : default
Destination addresses : 40.0.0.0
Host addresses : 31.0.0.0
Netmask : 255.255.255.0
Translation hits : 0

show security nat static rule all user@host> show security nat static rule all
Static NAT rule: rsr3 Rule-set: rsr2
Rule-Id : 3
Rule position : 6
From interface : ge-0/0/1.0
Destination addresses : 60.0.0.0
Host addresses : 100.0.0.0
Netmask : 255.255.255.0
Translation hits : 0
Static NAT rule: rsr11 Rule-set: rsr1
Rule-Id : 1
Rule position : 4
From routing instance : default
Destination addresses : 40.0.0.0
Host addresses : 31.0.0.0
Netmask : 255.255.255.0
Translation hits : 0

```

## show security nat static-nat summary

<b>Syntax</b>	show security nat static-nat summary <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display static Network Address Translation (NAT) summary information.  This command is supported on J-series devices.
<b>Options</b>	<p>none—Display static NAT summary information.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display static NAT summary information on specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security nat static-nat summary on page 898
<b>Output Fields</b>	Table 81 on page 898 lists the output fields for the <b>show security nat static-nat summary</b> command. Output fields are listed in the approximate order in which they appear.

**Table 81: show security nat static-nat summary Output Fields**

Field Name	Field Description
Total static NAT mappings	Number of static NAT entries in the table.
Maximum	Maximum number of static NAT entries possible.
Ingress Interface	Name of the interface on which static NAT is defined.
Destination	Destination IP address and subnet mask.
Host	Host IP address and subnet mask mapped to the destination IP address and subnet mask.
Virtual Router	Name of the virtual device that performs route lookup for the host IP address and subnet mask.

**show security nat static-nat summary**    user@host> **show security nat static-nat summary**

Total static NAT mappings: 3, Maximum: 300

Ingress Interface	Destination	Host	Virtual Router
ge-0/0/0.0	1.1.1.1/32	10.1.1.1/32	trust-vr
ge-0/0/0.0	1.1.3.0/24	10.1.3.0/24	trust-vr
ge-0/0/0.1	2.2.2.1/32	20.1.1.1/32	trust-vr

## show security pki ca-certificate

<b>Syntax</b>	show security pki ca-certificate <brief   detail> <ca-profile <i>ca-profile-name</i> >
<b>Release Information</b>	Command modified in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about the certificate authority (CA) public key infrastructure (PKI) digital certificates configured on the device.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display basic information about all configured CA certificates.  brief   detail—(Optional) Display the specified level of output.  ca-profile <i>ca-profile-name</i> —(Optional) Display information about only the specified CA certificate.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	ca-profile  request security pki ca-certificate verify on page 717  <i>JUNOS System Basics and Services Command Reference</i>
<b>List of Sample Output</b>	show security pki ca-certificate ca-profile juniper brief on page 901 show security pki ca-certificate ca-profile juniper detail on page 902
<b>Output Fields</b>	Table 82 on page 900 lists the output fields for the show security pki ca-certificate command. Output fields are listed in the approximate order in which they appear.

**Table 82: show security pki ca-certificate Output Fields**

Field Name	Field Description
Certificate identifier	Name of the digital certificate.
Certificate version	Revision number of the digital certificate.
Serial number	Unique serial number of the digital certificate.
Issued to	Device that was issued the digital certificate.
Issued by	Authority that issued the digital certificate.



**Table 82: show security pki ca-certificate Output Fields** (continued)

Field Name	Field Description
Issuer	<p>Authority that issued the digital certificate, including details of the authority organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> <li>■ Organization—Organization of origin.</li> <li>■ Organizational unit—Department within an organization.</li> <li>■ Country—Country of origin.</li> <li>■ Locality—Locality of origin.</li> <li>■ Common name—Name of the authority.</li> </ul>
Subject	<p>Details of the digital certificate holder organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> <li>■ Organization—Organization of origin.</li> <li>■ Organizational unit—Department within an organization.</li> <li>■ Country—Country of origin.</li> <li>■ Locality—Locality of origin.</li> <li>■ Common name—Name of the authority.</li> </ul>
Validity	<p>Time period when the digital certificate is valid. Values are:</p> <ul style="list-style-type: none"> <li>■ Not before—Start time when the digital certificate becomes valid.</li> <li>■ Not after—End time when the digital certificate becomes invalid.</li> </ul>
Public key algorithm	Encryption algorithm used with the private key, such as rsaEncryption(1024 bits).
Signature algorithm	Encryption algorithm that the CA used to sign the digital certificate, such as sha1WithRSAEncryption.
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.
Distribution CRL	Distinguished name information and the URL for the certificate revocation list (CRL) server.
Use for key	Use of the public key, such as Certificate signing, CRL signing, Digital signature, or Data encipherment.

**show security pki  
ca-certificate ca-profile  
juniper brief**

```

user@host> show security pki ca-certificate ca-profile juniper brief
Certificate identifier: kpradeep.juniper.net
Issued to: kpradeep.juniper.net, Issued by: kpradeep.juniper.net
Validity:
  Not before: 2005 Jul 8th, 12:44:54 GMT
  Not after: 2010 Jul 8th, 12:46:07 GMT
Public key algorithm: rsaEncryption(1024 bits)
Certificate identifier: kpradeep.juniper.net
Issued to: kpradeep.newra.juniper.net, Issued by: kpradeep.juniper.net
Validity:
  Not before: 2005 Jul 12th, 12:48:32 GMT
  Not after: 2006 Jul 12th, 12:58:32 GMT
Public key algorithm: rsaEncryption(1024 bits)
Certificate identifier: kpradeep.juniper.net

```

Issued to: kpradeep.newra.juniper.net, Issued by: kpradeep.juniper.net  
Validity:

Not before: 2005 Jul 12th, 12:48:32 GMT

Not after: 2006 Jul 12th, 12:58:32 GMT

Public key algorithm: rsaEncryption(1024 bits)

**show security pki  
ca-certificate ca-profile  
juniper detail**

user@host> **show security pki ca-certificate ca-profile juniper detail**

Certificate identifier: kpradeep.juniper.net

Certificate version: 3

Serial number: 1442 8439 1974 7864 6894 2623 4704 6564 1574

Issuer:

Common name: kpradeep.juniper.net

Subject:

Common name: kpradeep.juniper.net

Validity:

Not before: 2005 Jul 8th, 12:44:54 GMT

Not after: 2010 Jul 8th, 12:46:07 GMT

Public key algorithm: rsaEncryption(1024 bits)

e8:ba:49:61:42:c4:3e:81:07:19:8d:cd:38:cc:85:9b:ff:d2:c6:90:04:fa

18:58:8a:03:59:57:3d:b2:f0:06:62:a7:93:db:4e:8c:5d:6d:14:80:4e:38

03:69:64:ac:56:cf:72:d7:49:d1:00:45:c8:02:68:fd:e0:af:98:78:b1:b9

ee:9c:ad:21:f2:9d:7b:06:c4:71:b2:be:f4:e3:58:af:22:3b:ae:dc:1a:5e

f2:35:2c:0b:49:23:ee:2e:ba:e4:9a:24:f3:ff:01:5c:20:92:1d:76:51:fb

6b:bb:45:65:2f:db:2b:d7:e5:7d:03:9b:3e:21:88:75:46:5f

Signature algorithm: sha1WithRSAEncryption

Fingerprint:

00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10 (sha1)

71:6f:6a:76:17:9b:d6:2a:e7:5a:72:97:82:6d:26:86 (md5)

Distribution CRL:

file://\multiplex\CertEnroll\kpradeep.juniper.net.crl

http://multiplex/CertEnroll/kpradeep.juniper.net.crl

Use for key: CRL signing, Certificate signing, Digital signature

Certificate identifier: kpradeep.juniper.net

Certificate version: 3

Serial number: 9998 7697 0440 0585 1234

Issuer:

Common name: kpradeep.juniper.net

Subject:

Organization: Juniper Networks, Organizational unit: Pepsi, Country: IN,

Locality: Bangalore, Common name: kpradeep.newra.juniper.net

Validity:

Not before: 2005 Jul 12th, 12:48:32 GMT

Not after: 2006 Jul 12th, 12:58:32 GMT

Public key algorithm: rsaEncryption(1024 bits)

bd:26:77:95:16:23:b4:82:fc:cd:ea:fe:28:41:d4:d3:fd:df:f7:76:03:a6

23:3a:8a:6e:9e:25:41:e3:96:57:4a:bf:dc:5e:f2:09:a6:07:79:02:f7:40

1b:b9:79:70:79:65:c8:70:d9:6a:bd:a9:9c:cd:b3:39:80:e5:5a:c7:74:66

4a:05:b7:3b:ed:7a:99:e9:4b:58:e6:e7:69:9a:79:d4:c1:a5:26:12:5e:8d

3b:d1:b0:22:df:a9:ba:a2:23:73:21:1b:62:44:72:ad:c0:c3:7c:56:e8:ea

fe:ae:81:2b:44:8b:fe:da:ea:e3:18:85:bf:05:ea:28:8d:4b

Signature algorithm: sha1WithRSAEncryption

Fingerprint:

46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f (sha1)

ee:cc:c7:f4:5d:ac:65:33:0a:55:db:59:72:2c:dd:16 (md5)

Distribution CRL:

file://\multiplex\CertEnroll\kpradeep.juniper.net.crl

http://multiplex/CertEnroll/kpradeep.juniper.net.crl

Use for key: Data encipherment, Key encipherment

Certificate identifier: kpradeep.juniper.net

Certificate version: 3

Serial number: 9998 7666 0817 5841 3062

```

Issuer:
  Common name: kpradeep.juniper.net
Subject:
  Organization: Juniper Netowrks, Organizational unit: Pepsi,
  Country: IN,
  Locality: Bangalore, Common name: kpradeep.newra.juniper.net
Validity:
  Not before: 2005 Jul 12th, 12:48:32 GMT
  Not after: 2006 Jul 12th, 12:58:32 GMT
Public key algorithm: rsaEncryption(1024 bits)
  b6:b8:70:5f:c5:c5:c4:6d:be:a5:1e:19:12:b2:d4:8f:44:01:89:aa:66:98
  2d:21:0c:a2:45:04:ac:09:f6:8f:c7:ae:c3:40:d7:f4:b7:d8:8f:f1:21:d0
  c5:f0:b4:ea:05:c6:92:3a:e6:2e:33:0f:7b:a0:e1:de:16:52:13:09:16:91
  01:4a:bb:1e:f5:8d:98:e1:e4:2a:03:81:46:4f:1a:a3:20:4e:4d:5c:6e:f5
  ab:7e:08:81:b3:c0:78:2d:7b:ae:be:db:56:1e:6d:34:1f:a3:20:6e:7f:59
  a0:f1:d6:52:d9:35:5d:0a:f6:b4:ef:97:47:5b:0e:d3:11:2b
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17 (sha1)
  23:79:40:c9:6d:a6:f0:ca:e0:13:30:d4:29:6f:86:79 (md5)
Distribution CRL:
  file://\multiplex\CertEnroll\kpradeep.juniper.net.crl
  http://multiplex/CertEnroll/kpradeep.juniper.net.crl
Use for key: Non repudiation, Digital signature

```

## show security pki certificate-request

<b>Syntax</b>	show security pki certificate-request <brief   detail> <certificate-id <i>certificate-id-name</i> >
<b>Release Information</b>	Command modified in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about manually generated local digital certificate requests that are stored on the device.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display basic information about all local digital certificate requests.  brief   detail—(Optional) Display the specified level of output.  certificate-id <i>certificate-id-name</i> —(Optional) Display information about only the specified local digital certificate requests.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security pki key-pair on page 702  <i>JUNOS System Basics and Services Command Reference</i>
<b>List of Sample Output</b>	show security pki certificate-request certificate-id hassan brief on page 905 show security pki certificate-request certificate-id hassan detail on page 905
<b>Output Fields</b>	Table 83 on page 904 lists the output fields for the show security pki certificate-request command. Output fields are listed in the approximate order in which they appear.

**Table 83: show security pki certificate-request Output Fields**

Field Name	Field Description
Certificate identifier	Name of the digital certificate.
Certificate version	Revision number of the digital certificate.
Issued to	Device that was issued the digital certificate.
Subject	Details of the digital certificate holder organized using the distinguished name format. Possible subfields are: <ul style="list-style-type: none"> <li>■ Organization—Organization of origin.</li> <li>■ Organizational unit—Department within an organization.</li> <li>■ Country—Country of origin.</li> <li>■ Locality—Locality of origin.</li> <li>■ Common name—Name of the authority.</li> </ul>
Alternate subject	Domain name or IP address of the device related to the digital certificate.

**Table 83: show security pki certificate-request Output Fields** (*continued*)

Field Name	Field Description
Public key algorithm	Encryption algorithm used with the private key, such as rsaEncryption(1024 bits).
Public key verification status	Public key verification status: Failed or Passed. The detail output also provides the verification hash.
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.
Use for key	Use of the public key, such as Certificate signing, CRL signing, Digital signature, or Data encipherment.

**show security pki  
certificate-request  
certificate-id hassan  
brief**

```
user@host> show security pki certificate-request certificate-id hassan brief
Certificate identifier: hassan
Issued to: hassan@juniper.net
Public key algorithm: rsaEncryption(1024 bits)
```

**show security pki  
certificate-request  
certificate-id hassan  
detail**

```
user@host> show security pki certificate-request certificate-id hassan detail
Certificate identifier: hassan
Certificate version: 3
Subject:
  Organization: juniper, Organizational unit: pepsi, Country: IN,
  Common name: hassan
Alternate subject: 102.168.72.124
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed
  c7:a4:fb:e7:8c:4f:31:e7:eb:01:d8:32:65:21:f2:eb:6f:7d:49:1a:c3:9b
  63:47:e2:4f:f6:db:f6:c8:75:dd:e6:ec:0b:35:0a:62:32:45:6b:35:1f:65
  c9:66:b7:40:b2:f9:2a:ab:5b:60:f7:c7:73:36:da:68:25:fc:40:4b:12:3c
  d5:c8:c6:66:f6:10:1e:86:67:a8:95:9b:7f:1c:ae:a7:55:b0:28:95:a7:9a
  a2:24:28:e4:5a:b2:a9:06:7a:69:37:20:15:e1:b6:66:eb:22:b5:b6:77:f6
  65:88:b0:94:2b:91:4b:99:78:4a:e3:56:cc:14:45:d7:97:fd
Fingerprint:
  8f:22:1a:f2:9f:27:b0:21:6c:da:46:64:31:34:1f:68:42:5a:39:e0 (sha1)
  09:15:11:aa:ea:f9:5a:b5:70:d7:0b:8e:be:a6:d3:cb (md5)
Use for key: Digital signature
```

## show security pki crl

<b>Syntax</b>	show security pki crl < brief   detail> <ca-profile <i>ca-profile-name</i> >
<b>Release Information</b>	Command modified in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about the certificate revocation lists (CRLs) configured on the device.  This statement is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display basic information about all CRLs.  brief   detail—(Optional) Display the specified level of output.  ca-profile <i>ca-profile-name</i> —(Optional) Display information about only the specified CA profile.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	crl  <i>JUNOS System Basics and Services Command Reference</i>
<b>List of Sample Output</b>	show security pki crl ca-profile ca2 on page 907 show security pki crl ca-profile ca2 brief on page 907 show security pki crl ca-profile ca2 detail on page 907
<b>Output Fields</b>	Table 84 on page 906 lists the output fields for the <b>show security pki crl</b> command. Output fields are listed in the approximate order in which they appear.

**Table 84: show security pki crl Output Fields**

Field Name	Field Description
CA profile	Name of the configured CA profile.
CRL version	Revision number of the certificate revocation list.
CRL issuer	Authority that issued the digital certificate, including details of the authority organized using the distinguished name format. Possible subfields are: <ul style="list-style-type: none"> <li>■ emailAddress—Mail address of the issuing authority.</li> <li>■ C—Country of origin.</li> <li>■ ST—State of origin.</li> <li>■ L—Locality of origin.</li> <li>■ O—Organization of origin.</li> <li>■ OU—Department within an organization.</li> <li>■ CN—Name of the authority.</li> </ul>

**Table 84: show security pki crl Output Fields (continued)**

Field Name	Field Description
Effective date	Date and time the certificate revocation list becomes valid.
Next update	Date and time the routing platform will download the latest version of the certificate revocation list.
Revocation List	<p>List of digital certificates that have been revoked before their expiration date. Values are:</p> <ul style="list-style-type: none"> <li>■ Serial number—Unique serial number of the digital certificate.</li> <li>■ Revocation date—Date and time that the digital certificate was revoked.</li> </ul>

```

show security pki crl      user@host> show security pki crl ca-profile ca2
ca-profile ca2          CA profile: ca2
                           CRL version: V00000001
                           CRL issuer: emailAddress = asaini@juniper.net, C = US, ST = ca, L = sunnyvale,
                           O = Juniper networks, OU = SPG QA, CN = 2000-spg-juniper-net
                           Effective date: 04-26-2007 18:47
                           Next update: 05- 4-2007 07:07

```

```

show security pki crl      user@host> show security pki crl ca-profile ca2 brief
ca-profile ca2 brief     CA profile: ca2
                           CRL version: V00000001
                           CRL issuer: emailAddress = asaini@juniper.net, C = US, ST = ca, L = sunnyvale,
                           O = Juniper networks, OU = SPG QA, CN = 2000-spg-juniper-net
                           Effective date: 04-26-2007 18:47
                           Next update: 05- 4-2007 07:07

```

```

show security pki crl      user@host> show security pki crl ca-profile ca2 detail
ca-profile ca2 detail    CA profile: ca2
                           CRL version: V00000001
                           CRL issuer: emailAddress = asaini@juniper.net, C = US, ST = ca, L = sunnyvale,
                           O = Juniper networks, OU = SPG QA, CN = 2000-spg-juniper-net
                           Effective date: 04-26-2007 18:47
                           Next update: 05- 4-2007 07:07
                           Revocation List:
                           Serial number      Revocation date
                           174e6399000000000506    03-16-2007 23:09
                           174ef3f30000000000507    03-16-2007 23:09
                           17529cd60000000000508    03-16-2007 23:09
                           1763ac260000000000509    03-16-2007 23:09
                           21904e57000000000050a    03-16-2007 23:09
                           2191cf79000000000050b    03-16-2007 23:09
                           21f10eb6000000000050c    03-16-2007 23:09
                           2253ca2a000000000050f    03-16-2007 23:09
                           2478939b0000000000515    03-16-2007 23:09
                           24f350040000000000516    03-16-2007 23:09
                           277ddfa80000000000517    03-16-2007 23:09
                           277e97bd0000000000518    03-16-2007 23:09
                           27846a760000000000519    03-16-2007 23:09
                           2785176f000000000051a    03-16-2007 23:09

```

## show security pki local-certificate

<b>Syntax</b>	<pre>show security pki local-certificate &lt; brief   detail &gt; &lt; certificate-id <i>certificate-id-name</i> &gt; &lt;system-generated&gt;</pre>
<b>Release Information</b>	Command modified in Release 9.1 of JUNOS software.
<b>Description</b>	<p>Display information about the local digital certificates, corresponding public keys, and the automatically generated self-signed certificate configured on the device.</p> <p>This statement is supported on J-series and SRX-series devices.</p>
<b>Options</b>	<p>none—Display basic information about all configured local digital certificates, corresponding public keys, and the automatically generated self-signed certificate.</p> <p>brief   detail—(Optional) Display the specified level of output.</p> <p>certificate-id <i>certificate-id-name</i> —(Optional) Display information about only the specified local digital certificates and corresponding public keys.</p> <p>system-generated—Display information about the automatically generated self-signed certificate.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>clear security pki local-certificate on page 703</p> <p>request security pki local-certificate generate-self-signed on page 718</p> <p><i>JUNOS System Basics and Services Command Reference</i></p>
<b>List of Sample Output</b>	<p>show security pki local-certificate certificate-id on page 909</p> <p>show security pki local-certificate certificate-id detail on page 910</p> <p>show security pki local-certificate system-generated on page 910</p> <p>show security pki local-certificate system-generated detail on page 910</p>
<b>Output Fields</b>	Table 85 on page 908 lists the output fields for the <b>show security pki local-certificate</b> command. Output fields are listed in the approximate order in which they appear.

**Table 85: show security pki local-certificate Output Fields**

Field Name	Field Description
Certificate identifier	Name of the digital certificate.
Certificate version	Revision number of the digital certificate.
Serial number	Unique serial number of the digital certificate.
Issued to	Device that was issued the digital certificate.



**Table 85: show security pki local-certificate Output Fields (continued)**

Field Name	Field Description
Issued by	Authority that issued the digital certificate.
Issuer	<p>Authority that issued the digital certificate, including details of the authority organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> <li>■ Organization—Organization of origin.</li> <li>■ Organizational unit—Department within an organization.</li> <li>■ Country—Country of origin.</li> <li>■ Locality—Locality of origin.</li> <li>■ Common name—Name of the authority.</li> </ul>
Subject	<p>Details of the digital certificate holder organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> <li>■ Organization—Organization of origin.</li> <li>■ Organizational unit—Department within an organization.</li> <li>■ Country—Country of origin.</li> <li>■ Locality—Locality of origin.</li> <li>■ Common name—Name of the authority.</li> </ul>
Alternate subject	Domain name or IP address of the device related to the digital certificate.
Validity	<p>Time period when the digital certificate is valid. Values are:</p> <ul style="list-style-type: none"> <li>■ Not before—Start time when the digital certificate becomes valid.</li> <li>■ Not after—End time when the digital certificate becomes invalid.</li> </ul>
Public key algorithm	Encryption algorithm used with the private key, such as <code>rsaEncryption(1024 bits)</code> .
Public key verification status	Public key verification status: <b>Failed</b> or <b>Passed</b> . The <b>detail</b> output also provides the verification hash.
Signature algorithm	Encryption algorithm that the CA used to sign the digital certificate, such as <code>sha1WithRSAEncryption</code> .
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.
Distribution CRL	Distinguished name information and URL for the certificate revocation list (CRL) server.
Use for key	Use of the public key, such as <b>Certificate signing</b> , <b>CRL signing</b> , <b>Digital signature</b> , or <b>Data encipherment</b> .

**show security pki  
local-certificate  
certificate-id**

```
user@host> show security pki local-certificate certificate-id hassan
Certificate identifier: hassan
Issued to: hassan, Issued by: kpradeep.juniper.net
Validity:
Not before: 2005 Aug 2nd, 05:23:42 GMT
Not after: 2006 Aug 2nd, 05:33:42 GMT
```

Public key algorithm: rsaEncryption(1024 bits)  
Public key verification status: Passed

**show security pki  
local-certificate  
certificate-id detail**

user@host> **show security pki local-certificate certificate-id hassan detail**

Certificate identifier: hassan  
Certificate version: 3  
Serial number: 3115 8938 6334 6035 7529  
Issuer:  
Common name: kpradeep.juniper.net  
Subject:  
Organization: juniper, Organizational unit: pepsi, Country: IN,  
Common name: hassan  
Alternate subject: hassan.com  
Validity:  
Not before: 2005 Aug 2nd, 05:23:42 GMT  
Not after: 2006 Aug 2nd, 05:33:42 GMT  
Public key algorithm: rsaEncryption(1024 bits)  
Public key verification status: Passed  
c7:a4:fb:e7:8c:4f:31:e7:eb:01:d8:32:65:21:f2:eb:6f:7d:49:1a:c3:9b  
63:47:e2:4f:f6:db:f6:c8:75:dd:e6:ec:0b:35:0a:62:32:45:6b:35:1f:65  
c9:66:b7:40:b2:f9:2a:ab:5b:60:f7:c7:73:36:da:68:25:fc:40:4b:12:3c  
d5:c8:c6:66:f6:10:1e:86:67:a8:95:9b:7f:1c:ae:a7:55:b0:28:95:a7:9a  
a2:24:28:e4:5a:b2:a9:06:7a:69:37:20:15:e1:b6:66:eb:22:b5:b6:77:f6  
65:88:b0:94:2b:91:4b:99:78:4a:e3:56:cc:14:45:d7:97:fd  
Signature algorithm: sha1WithRSAEncryption  
Fingerprint:  
36:ec:35:5a:9a:6d:1c:77:a8:bb:f6:b9:94:57:36:11:c8:88:93:cc (sha1)  
1f:ab:f2:a0:84:5a:9c:e6:0e:92:79:70:cf:2c:1a:73 (md5)  
Distribution CRL:  
file://\multiplex\CertEnroll\kpradeep.juniper.net.crl  
http://multiplex/CertEnroll/kpradeep.juniper.net.crl  
Use for key: Digital signature

**show security pki  
local-certificate  
system-generated**

user@host> **show security pki local-certificate system-generated**

Certificate identifier: system-generated  
Issued to: JN10D3DFCADA, Issued by: CN = JN10D3DFCADA, CN = system generated,  
CN = self-signed  
Validity:  
Not before: 02-21-2008 10:27  
Not after: 02-19-2013 10:27  
Public key algorithm: rsaEncryption(1024 bits)

**show security pki  
local-certificate  
system-generated detail**

user@host> **show security pki local-certificate system-generated detail**

Certificate identifier: system-generated  
Certificate version: 3  
Serial number: a3f42347afe6953f8f3fe4aae70f310f  
Issuer:  
Common name: JN10D3DFCADA  
Subject:  
Common name: JN10D3DFCADA  
Alternate subject: email empty, fqdn empty, ip empty  
Validity:  
Not before: 02-21-2008 10:27  
Not after: 02-19-2013 10:27  
Public key algorithm: rsaEncryption(1024 bits)  
30:81:89:02:81:81:00:c1:50:fa:46:eb:57:6b:7d:11:05:a0:7d:17  
0c:2b:0e:d1:26:4c:ae:4d:75:b2:c9:73:2d:bb:d0:ef:07:f0:24:9e  
23:42:29:79:30:c3:3b:f4:b7:5a:74:3a:9c:d1:66:45:af:e8:41:5d  
52:bf:81:c3:c9:d9:d5:ba:0f:5e:d3:28:d4:44:d2:60:0c:42:76:c5  
ed:93:89:20:13:ee:e6:23:ab:d6:e5:fe:5e:13:a2:94:c0:ae:f9:1e  
cd:fa:ca:9f:59:92:b4:b3:84:e9:61:76:7b:81:f4:5a:48:a6:91:ae

```
39:99:b9:3a:06:ac:d7:b2:15:85:bd:8f:b7:90:e1:02:03:01:00:01
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
42:79:b0:f0:fa:fc:03:33:bd:0d:d4:56:21:f1:d9:28:51:00:3f:b0 (sha1)
f0:77:8e:3e:1d:41:12:a1:bf:3d:cd:19:e5:66:3e:15 (md5)
```

## show security policies

<b>Syntax</b>	show security policies <detail> <policy-name <i>policy-name</i> >
<b>Release Information</b>	Command modified in Release 9.2 of JUNOS software.
<b>Description</b>	Display a summary of all security policies configured on the device. If a particular policy is specified, display information particular to that policy.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display basic information about all configured policies.  detail—(Optional) Display a detailed view of all of the policies configured on the device.  policy-name <i>policy-name</i> —(Optional) Display information about the specified policy.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	clear security policies statistics on page 704
<b>List of Sample Output</b>	show security policies on page 914 ssh security policies policy-name p1 detail on page 914
<b>Output Fields</b>	Table 86 on page 912 lists the output fields for the <b>show security policies</b> command. Output fields are listed in the approximate order in which they appear.

**Table 86: show security policies Output Fields**

Field Name	Field Description
From zone	Name of the source zone.
To zone	Name of the destination zone.
Policy	Name of the applicable Policy.
Sequence number	Number of the policy within a given context. For example, three policies that are applicable in a from-zoneA to-zoneB context might be ordered with sequence numbers 1, 2, and 3. Also, in a from-zoneC to-zoneD context, four policies might have sequence numbers 1, 2, 3, and 4.
State	Status of the policy: <ul style="list-style-type: none"> <li>■ <b>enabled</b>: The policy can be used in the policy lookup process which determines access rights for a packet and the action taken in regard to it.</li> <li>■ <b>disabled</b>: The policy cannot be used in the policy lookup process, and therefore it is not available for access control.</li> </ul>

**Table 86: show security policies Output Fields (continued)**

Field Name	Field Description
Source addresses	<p>For standard display mode, the names of the source addresses for a policy. Address sets are resolved to their individual names. (In this case, only the names are given, not their IP addresses.)</p> <p>For detail display mode, the names and corresponding IP addresses of the source addresses for a policy. Address sets are resolved to their individual address name-IP address pairs.</p>
Destination addresses	Name of the destination address (or address set) as it was entered in the destination zone's address book. A packet's destination address must match this value for the policy to apply to it.
Applications	<p>Name of a preconfigured or custom application whose type the packet matches, as specified at configuration time.</p> <ul style="list-style-type: none"> <li>■ <b>IP protocol:</b> The IP protocol used by the application—for example, TCP, UDP, ICMP.</li> <li>■ <b>ALG:</b> If an ALG is associated with the session, the name of the ALG. Otherwise, 0.</li> <li>■ <b>Inactivity timeout:</b> Elapse time without activity after which the application is terminated.</li> <li>■ <b>Source port range:</b> The low-high source port range for the session application.</li> </ul>
Destination Address Translation	<p>Status of the destination address translation traffic:</p> <ul style="list-style-type: none"> <li>■ <b>drop translated—</b> Drop the packets with translated destination address.</li> <li>■ <b>drop untranslated—</b> Drop the packets without translated destination address.</li> </ul>
Action or Action-type	<ul style="list-style-type: none"> <li>■ The action taken in regard to a packet that matches the policy's tuples. Actions include the following: <ul style="list-style-type: none"> <li>■ <b>permit</b></li> <li>■ <b>firewall-authentication</b></li> <li>■ <b>tunnel ipsec-vpn <i>vpn-name</i></b></li> <li>■ <b>pair-policy <i>pair-policy-name</i></b></li> <li>■ <b>source-nat pool <i>pool-name</i></b></li> <li>■ <b>pool-set <i>pool-set-name</i></b></li> <li>■ <b>interface</b></li> <li>■ <b>destination-nat <i>name</i></b></li> <li>■ <b>deny</b></li> <li>■ <b>reject</b></li> </ul> </li> </ul>
Index	An internal number associated with the policy.
Session log	Session log entry that indicates whether the <b>at-create</b> and <b>at-close</b> flags were set at configuration time to log session information.
Scheduler name	Name of a preconfigured scheduler whose schedule determines when the policy is active (or inactive) to check an incoming packet to determine how to treat the packet.

**Table 86: show security policies Output Fields** (continued)

Field Name	Field Description
Policy statistics	<p>Policy statistics include the following:</p> <ul style="list-style-type: none"> <li>■ Input bytes—The number of bytes presented for processing by the device.</li> <li>■ Output bytes—The number of bytes actually processed by the device.</li> <li>■ Input packets—The number of packets presented for processing by the device.</li> <li>■ Active sessions—The number of sessions currently present because of access control lookups that used this policy.</li> <li>■ Session deletions—The number of sessions deleted since system startup.</li> <li>■ Policy lookups—Number of times the policy was accessed to check for a match.</li> </ul>

**show security policies**

```

user@host> show security policies
From zone: trust, To zone: untrust
Policy: p1, State: enabled, Index: 4, Sequence number: 1
  Source addresses: v-2-2-2-0
  Destination addresses: v-1-1-1-0
  Applications: any
  Action: permit, log, scheduled
Policy: p2, State: enabled, Index: 5, Sequence number: 2
  Source addresses: v-2-2-2-0
  Destination addresses: v-1-1-1-0
  Applications: any
  Action: deny, scheduled

```

**show security policies policy-name p1 detail**

```

user@host> show security policies policy-name p1 detail
Policy: p1, action-type: permit, State: enabled, Index: 4
Sequence number: 1
From zone: trust, To zone: untrust
Source addresses:
  v-2-2-2-0: 2.2.2.0/24
Destination addresses:
  v-1-1-1-0: 1.1.1.0/24
Application: any
IP protocol: 0, ALG: 0, Inactivity timeout: 0
Source port range: [0-0]
Destination port range: [0-0]
Destination Address Translation: drop translated
Session log: at-create, at-close
Scheduler name: sch20
Policy statistics:
  Input bytes      :          50000      100 bps
  Output bytes     :          40000      100 bps
  Input packets    :           200      200 pps
  Output packets   :           100      100 pps
  Session rate     :              2       1 sps
  Active sessions  :             11
  Session deletions:             20
  Policy lookups   :             12

```

## show security resource-manager group active

<b>Syntax</b>	show security resource-manager group active <group-number > <node ( node-id   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display security information about active groups created through the resource manager.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display resource manager group service information for all active groups.</p> <p><i>group-number</i> —(Optional) Display resource manager group service information for a specific group identification number.</p> <p><b>node</b>—(Optional) For chassis cluster configurations, display active resource manager group service information on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <b>all</b>—Display information about all nodes.</li> <li>■ <b>local</b>—Display information about the local node.</li> <li>■ <b>primary</b>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	<p>show security resource-manager group active on page 916</p> <p>show security resource-manager group active 2048 on page 916</p> <p>show security resource-manager group active node primary on page 916</p> <p>show security resource-manager group active node all on page 916</p> <p>show security resource-manager group active 1024 node all on page 916</p>
<b>Output Fields</b>	Table 87 on page 915 lists the output fields for the <b>show security resource-manager group</b> command. Output fields are listed in the approximate order in which they appear.

**Table 87: show security resource-manager group Output Fields**

Field Name	Field Description
Total groups	Total number of groups in the system.
active groups	Number of active groups.
Group ID	Identification number whose group information is displayed.

```

show security      user@host> show security resource-manager group active
resource-manager group Total groups 32, active groups 0
active

show security      user@host> show security resource-manager group active 2048
resource-manager group Total groups 2048, active groups 1
active 2048         Group ID 2048: state - Active
                        : Virtual System      - root
                        : Application         - SIP ALG
                        : Group Timeout       - 65535
                        : Number of resources - 3
                        Resource ID - 8190
                        Resource ID - 8188
                        Resource ID - 8187

show security      user@host> show security resource-manager group active node primary
resource-manager group node0:
active node primary -----
                        Group ID 1024: Application - SIP ALG
                        Total groups 1024, active groups 1

show security      user@host> show security resource-manager group active node all
resource-manager group node0:
active node all      -----
                        Group ID 1024: Application - SIP ALG
                        Total groups 1024, active groups 1
                        node1:
                        -----
                        Group ID 1024: Application - SIP ALG
                        Total groups 1024, active groups 1

show security      user@host> show security resource-manager group active 1024 node all
resource-manager group node0:
active 1024 node all -----
                        Group ID 1024: state - Active
                        : Application         - SIP ALG
                        : Group Timeout       - 65535
                        : Number of resources - 3
                        Resource ID - 8192
                        Resource ID - 8188
                        Resource ID - 8187
                        node1:
                        -----
                        Group ID 1024: state - Active
                        : Application         - SIP ALG
                        : Group Timeout       - 65535
                        : Number of resources - 3
                        Resource ID - 8187
                        Resource ID - 8186
                        Resource ID - 8190

```



## show security resource-manager resource active

<b>Syntax</b>	show security resource-manager resource active <resource-id > <node ( node-id   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display security information about active resources created through the resource manager.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display information for all active resources.</p> <p><i>resource-id</i> —(Optional) Display information for a resource with a specific identification number.</p> <p><i>node</i>—(Optional) For chassis cluster configurations, display active resource manager information on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <i>all</i>—Display information about all nodes.</li> <li>■ <i>local</i>—Display information about the local node.</li> <li>■ <i>primary</i>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security resource-manager resource active on page 918 show security resource-manager resource active 8190 on page 918 show security resource-manager resource active node local on page 918 show security resource-manager resource active node primary on page 918
<b>Output Fields</b>	Table 88 on page 917 lists the output fields for the <b>show security resource-manager resource</b> command. Output fields are listed in the approximate order in which they appear.

**Table 88: show security resource-manager resource Output Fields**

Field Name	Field Description
Total resources	Total number of resources in the system.
active resources	Number of active resources.
Resource ID	Identification number whose resource information is displayed.

```

show security      user@host> show security resource-manager resource active
resource-manager   Total resources 128, active resources 0
resource active

show security      user@host> show security resource-manager resource active 8190
resource-manager   Total resource 8192, active resource 3
resource active 8190 Resource ID 8190: state - Active
                        : Start time           - 0
                        : Resource timeout      - 120
                        : Parent group          - 2048
                        : Number of sessions    - 1
                        :   Session ID         - 8
                        : Number of Holes       - 1
                        1) Source IP Range      - {0.0.0.0, 0.0.0.0}
                        : Source Port Range     - {0, 0}
                        : Destination IP Range  - {20.20.20.31, 20.20.20.31}
                        : Destination Port Range - {50195, 50195}
                        : Protocol              - 17
                        : Reference count       - 1

show security      user@host> show security resource-manager resource active node local
resource-manager   node0:
resource active node
local              -----
                        Resource ID 8192: Group ID - 1024, Application - SIP ALG
                        Resource ID 8188: Group ID - 1024, Application - SIP ALG
                        Resource ID 8187: Group ID - 1024, Application - SIP ALG
                        Total Resources 8192, active resources 3

show security      user@host> show security resource-manager resource active node primary
resource-manager   node0:
resource active node
primary            -----
                        Resource ID 8192: Group ID - 1024, Application - SIP ALG
                        Resource ID 8188: Group ID - 1024, Application - SIP ALG
                        Resource ID 8187: Group ID - 1024, Application - SIP ALG
                        Total Resources 8192, active resources 3

```

## show security resource-manager settings

<b>Syntax</b>	show security resource-manager settings <node ( <i>node-id</i>   all   local   primary )>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display resource manager settings.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	node—(Optional) For chassis cluster configurations, display resource manager settings on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>List of Sample Output</b>	show security resource-manager settings on page 919 show security resource-manager settings node primary on page 920 show security resource-manager settings node all on page 920
<b>Output Fields</b>	Table 89 on page 919 lists the output fields for the <b>show security resource-manager settings</b> command. Output fields are listed in the approximate order in which they appear.

**Table 89: show security resource-manager settings Output Fields**

Field Name	Field Description
Client Heartbeat	Time after which idle an resource manager client is timed out.
Count	Number of active clients.
Pinhole age	Duration for which the temporary opening in the security firewall (pinhole) is open for specified traffic. If the specified traffic does not exist during this time period, the pinhole is timed out.

```

show security      user@host> show security resource-manager settings
resource-manager  Client Heartbeat: timeout 600 seconds, count 5
settings           Pinhole age: 32 seconds

```

```
show security      user@host> show security resource-manager settings node primary  
resource-manager  node0:  
settings node primary -----
```

```
Client heartbeat: timeout 600 seconds, count 5  
Pinhole age: 120 seconds
```

```
show security      user@host> show security resource-manager settings node all  
resource-manager  node0:  
settings node all -----
```

```
Client heartbeat: timeout 600 seconds, count 5  
Pinhole age: 120 seconds  
node1:  
-----
```

```
Client heartbeat: timeout 600 seconds, count 5  
Pinhole age: 120 seconds
```

## show security screen ids-option

<b>Syntax</b>	show security screen ids-option screen-name <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display configuration information about the specified security screen.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<i>screen-name</i> —Name of the screen.  <i>node</i> —(Optional) For chassis cluster configurations, display the configuration status of the security screen on a specific node. <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ <i>all</i>—Display information about all nodes.</li> <li>■ <i>local</i>—Display information about the local node.</li> <li>■ <i>primary</i>—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	ids-option
<b>List of Sample Output</b>	show security screen ids-option jscreen on page 922 show security screen ids-option jscreen1 node all on page 922
<b>Output Fields</b>	Table 90 on page 921 lists the output fields for the <b>show security screen ids-option</b> command. Output fields are listed in the approximate order in which they appear.

**Table 90: show security screen ids-option Output Fields**

Field Name	Field Description
TCP port scan threshold	Number of microseconds during which the device accepts packets from the same remote source with up to 10 different port numbers.
ICMP address sweep threshold	Maximum number of microseconds during which up to 10 ICMP echo requests from the same host are allowed into the device.
UDP flood threshold	Number of UDP packets per second allowed to ping the same destination address before the device rejects further UDP packets.
TCP winnuke	Enable or disable the detection of Transport Control Protocol (TCP) WinNuke attacks.
TCP SYN flood attack threshold	Number of SYN packets per second required to trigger the SYN proxy response.
TCP SYN flood alarm threshold	Number of half-complete proxy connections per second at which the device makes entries in the event alarm log.

**Table 90: show security screen ids-option Output Fields** (continued)

Field Name	Field Description
TCP SYN flood source threshold	Number of SYN segments to be received per second before the device starts dropping connection requests.
TCP SYN flood destination threshold	Number of SYN segments received per second before the device begins dropping connection requests.
TCP SYN flood timeout	Maximum length of time before a half-completed connection is dropped from the queue.
TCP SYN flood queue size	Number of proxy connection requests that can be held in the proxy connection queue before the device starts rejecting new connection requests.
ICMP large packet	Enable or disable the detection of any ICMP frame with an IP length greater than 1024 bytes.

```

show security screen      user@host> show security screen ids-option jscreen
ids-option jscreen      Screen object status:
                           Name                               Value
                           TCP port scan threshold            5000
                           ICMP address sweep threshold        5000

show security screen      user@host> show security screen ids-option jscreen1 node all
ids-option jscreen1 node node0:
all                      -----
                           Screen object status:
                           Name                               Value
                           UDP flood threshold                 1000
                           TCP winnuke                         enabled
                           TCP SYN flood attack threshold       200
                           TCP SYN flood alarm threshold        512
                           TCP SYN flood source threshold       4000
                           TCP SYN flood destination threshold  4000
                           TCP SYN flood timeout                20
                           TCP SYN flood queue size             1024
                           ICMP large packet                   enabled
                           node1:
                           -----
                           Screen object status:
                           Name                               Value
                           UDP flood threshold                 1000
                           TCP winnuke                         enabled
                           TCP SYN flood attack threshold       200
                           TCP SYN flood alarm threshold        512
                           TCP SYN flood source threshold       4000
                           TCP SYN flood destination threshold  4000
                           TCP SYN flood timeout                20
                           TCP SYN flood queue size             1024
                           ICMP large packet                   enabled

```

## show security screen statistics

<b>Syntax</b>	show security screen statistics (zone <i>zone-name</i>   interface <i>interface-name</i> ) <node ( <i>node-id</i>   all   local   primary)>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software; <b>node</b> options added in Release 9.0 of JUNOS software.
<b>Description</b>	Display intrusion detection system (IDS) security screen statistics.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	<p>none—Display IDS security for all zones and interface.</p> <p>zone <i>zone-name</i> —(Optional) Display screen statistics for this security zone.</p> <p>interface <i>interface-name</i>—(Optional) Display screen statistics for this interface.</p> <p>node—(Optional) For chassis cluster configurations, display security screen statistics on a specific node.</p> <ul style="list-style-type: none"> <li>■ <i>node-id</i> —Identification number of the node. It can be 0 or 1.</li> <li>■ all—Display information about all nodes.</li> <li>■ local—Display information about the local node.</li> <li>■ primary—Display information about the primary node.</li> </ul>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>clear security screen statistics on page 705</p> <p>clear security screen statistics interface on page 706</p> <p>clear security screen statistics zone on page 707</p>
<b>List of Sample Output</b>	<p>show security screen statistics zone scrzone on page 925</p> <p>show security screen statistics interface ge-0/0/3 on page 926</p> <p>show security screen statistics interface ge-0/0/1 node primary on page 926</p>
<b>Output Fields</b>	Table 91 on page 923 lists the output fields for the <b>show security screen statistics</b> command. Output fields are listed in the approximate order in which they appear.

**Table 91: show security screen statistics Output Fields**

Field Name	Field Description
ICMP flood	Internet Control Message Protocol (ICMP) flood counter. An ICMP flood typically occurs when ICMP echo requests use all resources in responding, such that valid network traffic can no longer be processed.

**Table 91: show security screen statistics Output Fields** *(continued)*

Field Name	Field Description
UDP flood	User Datagram Protocol (UDP) flood counter. UDP flooding occurs when an attacker sends IP packets containing UDP datagrams with the purpose of slowing down the resources, such that valid connections can no longer be handled.
TCP winnuke	Number of Transport Control Protocol (TCP) WinNuke attacks. WinNuke is a denial-of-service (DoS) attack targeting any computer on the Internet running Windows.
TCP port scan	Number of TCP port scans. The purpose of this attack is to scan the available services in the hopes that at least one port will respond, thus identifying a service to target.
ICMP address sweep	Number of ICMP address sweeps. An IP address sweep can occur with the intent of triggering responses from active hosts
IP tear drop	Number of teardrop attacks. teardrop attacks exploit the reassembly of fragmented IP packets.
TCP SYN flood	Number of TCP SYN attacks.
IP spoofing	Number of IP spoofs. IP spoofing occurs when an invalid source address is inserted in the packet header to make the packet appear to come from a trusted source.
ICMP ping of death	ICMP ping of death counter. Ping of death occurs when IP packets are sent that exceed the maximum legal length (65,535 bytes).
IP source route option	Number of IP source route attacks.
TCP land attack	Number of land attacks. Land attacks occur when an attacker sends spoofed SYN packets containing the IP address of the victim as both the destination and source IP address.
TCP SYN fragment	Number of TCP SYN fragments.
TCP no flag	Number of TCP headers without flags set. A normal TCP segment header has at least one control flag set.
IP unknown protocol	Number of Internet protocols (IP).
IP bad options	Number of invalid options.
IP record route option	Number of packets with the IP record route option enabled. This option records the IP addresses of the network devices along the path that the IP packet travels.
IP timestamp option	Number of IP timestamp option attacks. This option records the time (in Universal Time) when each network device receives the packet during its trip from the point of origin to its destination.
IP security option	Number of IP security option attacks.
IP loose source route option	Number of IP loose source route option attacks. This option specifies a partial route list for a packet to take on its journey from source to destination.
IP strict source route option	Number of IP strict source route option attacks. This option specifies the complete route list for a packet to take on its journey from source to destination.
IP stream option	Number of stream option attacks. This option provides a way for the 16-bit SATNET stream identifier to be carried through networks that do not support streams.



**Table 91: show security screen statistics Output Fields** (continued)

Field Name	Field Description
ICMP fragment	Number of ICMP fragments. Because ICMP packets contain very short messages, there is no legitimate reason for ICMP packets to be fragmented. If an ICMP packet is so large that it must be fragmented, something is amiss.
ICMP large packet	Number of large ICMP packets.
TCP SYN FIN	Number of TCP SYN FIN packets.
TCP FIN no ACK	Number of TCP FIN flags without the acknowledge (ACK) flag.
Source session limit	Number of concurrent sessions that can be initiated from a source IP address.
TCP SYN-ACK-ACK Proxy	Number of TCP flags enabled with SYN-ACK-ACK. To prevent flooding with SYN-ACK-ACK sessions, you can enable the SYN-ACK-ACK proxy protection screen option. After the number of connections from the same IP address reaches the SYN-ACK-ACK proxy threshold, J-series and SRX-series devices running JUNOS software rejects further connection requests from that IP address.
IP Block Fragment	Number of IP block fragments.
Destination session limit	Number of concurrent sessions that can be directed to a single destination IP address.

```

show security screen user@host> show security screen statistics zone scrzone
statistics zone scrzone Screen statistics:
IDS attack type           Statistics
  ICMP flood              0
  UDP flood               0
  TCP winnuke             0
  TCP port scan           91
  ICMP address sweep      0
  IP tear drop            0
  TCP SYN flood           0
  IP spoofing             0
  ICMP ping of death      0
  IP source route option  0
  TCP land attack         0
  TCP SYN fragment        0
  TCP no flag             0
  IP unknown protocol     0
  IP bad options          0
  IP record route option  0
  IP timestamp option     0
  IP security option      0
  IP loose source route option 0
  IP strict source route option 0
  IP stream option        0
  ICMP fragment           0
  ICMP large packet       0
  TCP SYN FIN             0
  TCP FIN no ACK          0
  Source session limit    0
  TCP SYN-ACK-ACK proxy   0

```

```

IP block fragment          0
Destination session limit  0

```

```

show security screen user@host> show security screen statistics interface ge-0/0/3
statistics interface Screen statistics:
ge-0/0/3 IDS attack type Statistics
            ICMP flood      0
            UDP flood       0
            TCP winnuke     0
            TCP port scan   91
            ICMP address sweep
            IP tear drop    0
            TCP SYN flood   0
            IP spoofing     0
            ICMP ping of death
            IP source route option
            TCP land attack 0
            TCP SYN fragment
            TCP no flag     0
            IP unknown protocol
            IP bad options  0
            IP record route option
            IP timestamp option
            IP security option
            IP loose source route option
            IP strict source route option
            IP stream option
            ICMP fragment   0
            ICMP large packet
            TCP SYN FIN     0
            TCP FIN no ACK  0
            Source session limit
            TCP SYN-ACK-ACK proxy
            IP block fragment
            Destination session limit

```

```

show security screen user@host> show security screen statistics interface ge-0/0/1 node primary
statistics interface node0:
ge-0/0/1 node primary -----
Screen statistics:
IDS attack type Statistics
            ICMP flood      1
            UDP flood       1
            TCP winnuke     1
            TCP port scan   1
            ICMP address sweep
            IP tear drop    1
            TCP SYN flood   1
            IP spoofing     1
            ICMP ping of death
            IP source route option
            TCP land attack 1
            TCP SYN fragment
            TCP no flag     1
            IP unknown protocol
            IP bad options  1
            IP record route option
            IP timestamp option
            IP security option
            IP loose source route option
            IP strict source route option

```

IP stream option	1
ICMP fragment	1
ICMP large packet	1
TCP SYN FIN	1
TCP FIN no ACK	1
Source session limit	1
TCP SYN-ACK-ACK proxy	1
IP block fragment	1
Destination session limit	1

## show security zones

<b>Syntax</b>	show security zones <detail   terse> < zone-name >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about security zones.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display information about all zones.  detail   terse—(Optional) Display the specified level of output.  zone-name —(Optional) Display information about the specified zone.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	security-zone
<b>List of Sample Output</b>	show security zones on page 928 show security zones abc on page 929 show security zones abc detail on page 929 show security zones terse on page 929 show security zones my-shared-external on page 929
<b>Output Fields</b>	Table 92 on page 928 lists the output fields for the <b>show security zones</b> command. Output fields are listed in the approximate order in which they appear.

**Table 92: show security zones Output Fields**

Field Name	Field Description
Security zone	Name of the security zone.
Policy configurable	Whether the policy can be configured or not.
Interfaces bound	Number of interfaces in the zone.
Interfaces	List of the interfaces in the zone.
Zone	Name of the zone.
Type	Type of the zone.

```

show security zones  user@host> show security zones
                        Functional zone: management
                        Policy configurable: No
                        Interfaces bound: 1

```

```

    Interfaces:
      ge-0/0/0.0
  Security zone: Host
    Send reset for non-SYN session TCP packets: Off
    Policy configurable: Yes
    Interfaces bound: 1
    Interfaces:
      fxp0.0
  Security zone: abc
    Send reset for non-SYN session TCP packets: Off
    Policy configurable: Yes
    Interfaces bound: 1
    Interfaces:
      ge-0/0/1.0
  Security zone: def
    Send reset for non-SYN session TCP packets: Off
    Policy configurable: Yes
    Interfaces bound: 1
    Interfaces:
      ge-0/0/2.0
  Security zone: junos-global
    Send reset for non-SYN session TCP packets: Off
    Policy configurable: Yes
    Interfaces bound: 0
    Interfaces:

```

```

show security zones abc  user@host> show security zones abc
Security zone: abc
  Send reset for non-SYN session TCP packets: Off
  Policy configurable: Yes
  Interfaces bound: 1
  Interfaces:
    ge-0/0/1.0

```

```

show security zones abc  user@host> show security zones abc detail
detail Security zone: abc
  Send reset for non-SYN session TCP packets: Off
  Policy configurable: Yes
  Interfaces bound: 1
  Interfaces:
    ge-0/0/1.0

```

```

show security zones      user@host> show security zones terse
terse
Zone           Type
my-internal    Security
my-external    Security
dmz            Security
my-shared-external Security

```

```

show security zones      user@host> show security zones my-shared-external
my-shared-external Security zone: my-shared-external, Shared
  send reset for non SYN non session TCP packets : On
  IP/TCP reassembly for ALG on traffic from/to this zone: Yes
  Policy Configurable: Yes
  Interfaces bound:1.
    ge-0/1/1.0
  IP classification: Disabled.

```

## show security zones type

<b>Syntax</b>	show security zones type (functional   security) <detail   terse>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about security zones of the specified type.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	functional—Display functional zones.  security—Display security zones.  detail   terse—(Optional) Display the specified level of output.
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	security-zone
<b>List of Sample Output</b>	show security zones type functional on page 930 show security zones type security on page 931 show security zones type security terse on page 931 show security zones type security detail on page 931
<b>Output Fields</b>	Table 93 on page 930 lists the output fields for the <b>show security zones type</b> command. Output fields are listed in the approximate order in which they appear.

**Table 93: show security zones type Output Fields**

Field Name	Field Description
Security zone	Zone name.
Policy configurable	Whether the policy can be configured or not.
Interfaces	List of the interfaces in the zone.
Interfaces bound	Number of interfaces in the zone.
Zone	Name of the zone.
Type	Type of the zone.

```

show security zones    user@host> show security zones type functional
type functional      Security zone: Host
                        Send reset for non-SYN session TCP packets: Off
                        Policy configurable: Yes
                        Interfaces bound: 1

```

```

Interfaces:
fxp0.0
Security zone: fz
Send reset for non-SYN session TCP packets: Off
Policy configurable: Yes
Interfaces bound: 1
Interfaces:
ge-0/0/1.0

```

```

show security zones      user@host> show security zones type security
type security           Security zone: Host
                          Send reset for non-SYN session TCP packets: Off
                          Policy configurable: Yes
                          Interfaces bound: 1
                          Interfaces:
                          fxp0.0
                          Security zone: fz
                          Send reset for non-SYN session TCP packets: Off
                          Policy configurable: Yes
                          Interfaces bound: 1
                          Interfaces:
                          ge-0/0/1.0

```

```

show security zones      user@host> show security zones type security terse
type security terse
Zone                      Type
my-internal               Security
my-external               Security
dmz                       Security
my-shared-external       Security

```

```

show security zones      user@host> show security zones type security detail
type security detail
Security zone: HOST
  Send reset for non-SYN session TCP packets: Off
  Policy configurable: Yes
  Interfaces bound: all
  Interfaces:
Security zone: junos-global
  Send reset for non-SYN session TCP packets: Off
  Policy configurable: Yes
  Interfaces bound: 0
  Interfaces:

```

## show system services dhcp client

<b>Syntax</b>	show system services dhcp client < <i>interface-name</i> > <statistics>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about DHCP clients.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display DHCP information for all interfaces.  <i>interface-name</i> —(Optional) Display DHCP information for the specified interface.  statistics—(Optional) Display DHCP client statistics.
<b>Required Privilege Level</b>	view and system
<b>Related Topics</b>	dhcp  request system services dhcp on page 722
<b>List of Sample Output</b>	show system services dhcp client on page 933 show system services dhcp client ge-0/0/1.0 on page 933 show system services dhcp client statistics on page 934
<b>Output Fields</b>	Table 94 on page 932 lists the output fields for the <b>show system services dhcp client</b> command. Output fields are listed in the approximate order in which they appear.

**Table 94: show system services dhcp client Output Fields**

Field Name	Field Description
Logical Interface Name	Name of the logical interface.
Client Status	State of the client binding.
Vendor Identifier	Vendor ID.
Server Address	IP address of the DHCP server.
Address obtained	IP address obtained from the DHCP server.
Lease Obtained at	Date and time the lease was obtained.
Lease Expires at	Date and time the lease expires.
DHCP Options	<ul style="list-style-type: none"> <li>■ Name: server-identifier, Value: IP address of the name server.</li> <li>■ Name: device, Value: IP address of the name device.</li> <li>■ Name: domain-name, Value: Name of the domain.</li> </ul>



**Table 94: show system services dhcp client Output Fields (continued)**

Field Name	Field Description
Packets dropped	Total packets dropped.
Messages received	<p>Number of the following DHCP messages received:</p> <ul style="list-style-type: none"> <li>■ DHCPOFFER—First packet received on a logical interface when DHCP is enabled.</li> <li>■ DHCPACK—When received from the server, the client sends an ARP request for that address and adds a (ARP response) timer for 4 seconds and stop the earlier timer added for DHCPACK.</li> <li>■ DHCPNAK—When a DHCPNAK is received instead of DHCPACK, the logical interface sends a DHCPDISCOVER packet.</li> </ul>
Messages sent	<p>Number of the following DHCP messages sent:</p> <ul style="list-style-type: none"> <li>■ DHCPDECLINE—Packet sent when ARP response is received and there is a conflict. The logical interface sends a new DHCPDISCOVER packet.</li> <li>■ DHCPDISCOVER—Packet sent on the interface for which the DHCP client is enabled.</li> <li>■ DHCPREQUEST—Packet sent to the DHCP server after accepting the DHCPOFFER. After sending the DHCPREQUEST, the device adds a retransmission-interval timer.</li> <li>■ DHCPINFORM—Packet sent to the DHCP server for local configuration parameters.</li> <li>■ DHCPRELEASE—Packet sent to the DHCP server to relinquish network address and cancel remaining lease.</li> <li>■ DHCPRENEW—Packet sent to the DHCP server to renew the address. The next message to be sent will be a DHCPREQUEST message, which will be unicast directly to the server.</li> <li>■ DHCPREBIND—Packet sent to any server to renew the address. The next message to be sent will be a DHCPREQUEST message, which will be broadcast.</li> </ul>

**show system services  
dhcp client**

```

user@host> show system services dhcp client
Logical Interface Name      ge-0/0/1.0
Hardware address           00:0a:12:00:12:12
Client Status              bound
Vendor Identifier          ether
Server Address             10.1.1.1
Address obtained           10.1.1.89
update server              enabled
Lease Obtained at          2006-08-24 18:13:04 PST
Lease Expires at           2006-08-25 18:13:04 PST
DHCP Options :
  Name: name-server, Value: [ 10.209.194.131, 2.2.2.2, 3.3.3.3 ]
  Name: server-identifier, Value: 10.1.1.1
  Name: router, Value: [ 10.1.1.80 ]
  Name: domain-name, Value: netscreen-50

```

**show system services  
dhcp client ge-0/0/1.0**

```

user@host> show system services dhcp client ge-0/0/1.0
Logical Interface name      ge-0/0/1.0
Hardware address           00:12:1e:a9:7b:81
Client status              bound
Address obtained           30.1.1.20
Update server              disabled
Lease obtained at          2007-05-10 18:16:18 UTC
Lease expires at           2007-05-11 18:16:18 UTC

```

```

DHCP options:
  Name: server-identifier, Value: 30.1.1.2
  Code: 1, Type: ip-address, Value: 255.255.255.0
  Name: name-server, Value: [ 77.77.77.77, 55.55.55.55 ]
  Name: domain-name, Value: englab.juniper.net

```

```

show system services user@host> show system services dhcp client statistics
dhcp client statistics

```

```

Packets dropped:
  Total                                0
Messages received:
  DHCPPOFFER                          0
  DHCPACK                             8
  DHCPNAK                             0
Messages sent:
  DHCPDECLINE                         0
  DHCPDISCOVER                       0
  DHCPREQUEST                         1
  DHCPINFORM                         0
  DHCPRELEASE                        0
  DHCPRENEW                          7
  DHCPREBIND                         0

```

## show system services dhcp relay-statistics

<b>Syntax</b>	show system services dhcp relay-statistics
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Display information about the DHCP relay.</p> <p>This command is supported on J-series and SRX-series devices.</p>
<b>Required Privilege Level</b>	view and system
<b>Related Topics</b>	dhcp
<b>List of Sample Output</b>	show system services dhcp relay-statistics on page 935
<b>Output Fields</b>	Table 95 on page 935 lists the output fields for the <code>show system services dhcp relay-statistics</code> command. Output fields are listed in the approximate order in which they appear.

**Table 95: show system services dhcp relay-statistics Output Fields**

Field Name	Field Description
Received packets	Total DHCP packets received.
Forwarded packets	Total DHCP packet forwarded.
Dropped packets	<p>Total DHCP packets dropped for the following reasons:</p> <ul style="list-style-type: none"> <li>■ Due to a missing interface in the relay database—Number of packets discarded because they did not belong to a configured interface.</li> <li>■ Due to a missing matching routing instance—Number of packets discarded because they did not belong to a configured routing instance.</li> <li>■ Due to an error during packet read—Number of packets discarded because of a system read error.</li> <li>■ Due to an error during packet send—Number of packets that the DHCP relay application could not send.</li> <li>■ Due to an invalid server address—Number of packets discarded because an invalid server address was specified.</li> <li>■ Due to a missing valid local address—Number of packets discarded because there was no valid local address.</li> <li>■ Due to a missing route to the server or client—Number of packets discarded because there were no addresses available for assignment.</li> </ul>

```

show system services dhcp relay-statistics
user@host> show system services dhcp relay-statistics
Received packets: 4
Forwarded packets: 4
Dropped packets: 4
  Due to missing interface in relay database: 4
  Due to missing matching routing instance: 0

```

```
Due to an error during packet read: 0  
Due to an error during packet send: 0  
Due to invalid server address: 0  
Due to missing valid local address: 0  
Due to missing route to server/client: 0
```

## show system services dns-proxy

<b>Syntax</b>	show system services dns-proxy <cache>
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display Domain Name System (DNS) proxy information.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display DNS proxy statistics information.  cache—(Optional) Display the DNS proxy cache.
<b>Required Privilege Level</b>	view and system
<b>Related Topics</b>	cache  clear system services dns-proxy cache on page 708  clear system services dns-proxy statistics on page 709
<b>List of Sample Output</b>	show system services dns-proxy on page 938 show system services dns-proxy cache on page 938
<b>Output Fields</b>	Table 96 on page 937 lists the output fields for the <b>show system services dns-proxy</b> command. Output fields are listed in the approximate order in which they appear.

**Table 96: show system services dns-proxy Output Fields**

Field Name	Field Description
DNS proxy statistics	Display information about the DNS proxy. <ul style="list-style-type: none"> <li>■ <b>Status:</b> State of the proxy server—Enabled or disabled.</li> <li>■ <b>Queries received</b>—Number of DNS queries received by the DNS proxy.</li> <li>■ <b>Responses sent</b>—Number of DNS responses sent by the DNS proxy.</li> <li>■ <b>Queries forwarded</b>—Number of DNS queries forwarded by the DNS proxy.</li> <li>■ <b>Negative responses</b>—Number of negative responses the DNS proxy sent to the DNS client.</li> <li>■ <b>Retry requests</b>—Number of retries the DNS proxy received from the DNS client.</li> <li>■ <b>Pending requests</b>—Number of pending queries the DNS proxy has yet to send the DNS client a response for.</li> <li>■ <b>Server failures</b>—Number of DNS proxy server failures.</li> </ul>
Hostname	Hostname of the host that has been cached.
IP address	IP address of the host.
Time-to-live	Length of time before an entry is purged from the DNS cache.

**Table 96: show system services dns-proxy Output Fields (continued)**

Field Name	Field Description
Type	Type of DNS Resource Record. For example, A records refer to IPv4 host addresses.
Class	Class of DNS. A parameter used to define a DNS Resource Record. For example, IN class is used for Internet domain names.

```

show system services user@host> show system services dns-proxy
dns-proxy           DNS proxy statistics :

```

```

    Status           : enabled
    Query received    : 215
    Sent response     : 211
    Query forwarded   : 39
    Negative response : 33
    Retry requests    : 0
    Pending requests  : 0
    Server fail       : 128

```

```

show system services user@host> show system services dns-proxy cache
dns-proxy cache

```

Hostname	IP address	Time-to-live	Type	Class
juniper.net	207.17.137.229	2006-08-30 06:50:57 PDT	A	IN
whitestar.juniper.net	172.17.27.50	2006-08-30 06:50:57 PDT	A	IN
scarlet.juniper.net	172.17.28.11	2006-08-30 06:50:57 PDT	A	IN
bng-admin1.juniper.net	10.209.194.131	2006-08-30 06:50:57 PDT	A	IN
wf-nis1.juniper.net	10.10.4.202	2006-08-30 06:50:57 PDT	A	IN
asg-ns1.juniper.net	10.16.0.11	2006-08-30 06:50:57 PDT	A	IN
ruby.juniper.net	172.17.28.100	2006-08-30 06:50:57 PDT	A	IN
a.l.google.com	216.239.53.9	2006-08-29 23:54:42 PDT	A	IN
b.l.google.com	64.233.179.9	2006-08-29 23:54:59 PDT	A	IN
maps.l.google.com	64.233.189.104	2006-08-29 06:56:01 PDT	A	IN
c.l.google.com	64.233.161.9	2006-08-29 23:54:35 PDT	A	IN
d.l.google.com	64.233.183.9	2006-08-29 23:54:46 PDT	A	IN
e.l.google.com	66.102.11.9	2006-08-29 23:54:50 PDT	A	IN
g.l.google.com	64.233.167.9	2006-08-29 23:55:20 PDT	A	IN

## show system services dynamic-dns client

<b>Syntax</b>	show system services dynamic-dns client < brief   detail > < hostname >
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	Display information about dynamic DNS clients.  This command is supported on J-series and SRX-series devices.
<b>Options</b>	none—Display summary about all dynamic DNS clients.  brief   detail—(Optional) Display the specified level of output.  hostname—(Optional) Display information about a specific dynamic DNS client.
<b>Required Privilege Level</b>	view and system
<b>Related Topics</b>	dynamic-dns
<b>List of Sample Output</b>	show system services dynamic-dns client on page 940 show system services dynamic-dns client jnpr.ddo.jp on page 940 show system services dynamic-dns client detail on page 940 show system services dynamic-dns client detail jnpr.ddo.jp on page 940 show system services dynamic-dns client brief on page 940 show system services dynamic-dns client foo.example.com on page 940
<b>Output Fields</b>	Table 97 on page 939 lists the output fields for the show system services dynamic-dns client command. Output fields are listed in the approximate order in which they appear.

**Table 97: show system services dynamic-dns client Output Fields**

Field Name	Field Description
Internal hostname	Name of the internal dynamic-DNS client.
Hostname	Name of the internal dynamic-DNS client.
Server	Name of the dynamic-DNS server.
Agent	Secure device.
Last response	Status of last response.
Last update	Date and time of last update.
Interface	Device interface whose IP address changes.

```

show system services dynamic-dns client
user@host> show system services dynamic-dns client
Internal hostname  Server      Last response
jnpr.ddo.jp       ddo.jp      success
jnr.ddo.jp        ddo.jp      failure
newsam.getmyip.com members.dyndns.org nochg
samks.gotdns.com  members.dyndns.org noch

show system services dynamic-dns client jnpr.ddo.jp
user@host> show system services dynamic-dns client jnpr.ddo.jp
Internal hostname  Server      Last response
jnpr.ddo.jp       ddo.jp      success

show system services dynamic-dns client detail
user@host> show system services dynamic-dns client detail
Hostname      : jnpr.ddo.jp
Server        : ddo.jp
Agent         : voyager-0.1
Last response: success
Last update   : 2006-08-29 04:02:52 PDT
Interface     : ge-0/0/0.0
Hostname      : jnr.ddo.jp
Server        : ddo.jp
Agent         : voyager-0.1
Last response: failure
Last update   : 2006-08-29 04:03:03 PDT
Interface     : ge-0/0/0.0
Hostname      : newsam.getmyip.com
Server        : members.dyndns.org
Agent         : voyager-0.1
Last response: nochg
Last update   : 2006-08-29 04:02:50 PDT
Username      : samks
Interface     : ge-0/0/1.0

show system services dynamic-dns client detail jnpr.ddo.jp
user@host> show system services dynamic-dns client detail jnpr.ddo.jp
Hostname      : jnpr.ddo.jp
Server        : ddo.jp
Agent         : voyager-0.1
Last response: success
Last update   : 2006-08-29 04:02:52 PDT
Interface     : ge-0/0/0.0

show system services dynamic-dns client brief
user@host> show system services dynamic-dns client brief
Internal hostname  Server      Last response
jnpr.ddo.jp       ddo.jp      success
jnr.ddo.jp        ddo.jp      failure
newsam.getmyip.com members.dyndns.org nochg
samks.gotdns.com  members.dyndns.org noch

show system services dynamic-dns client foo.example.com
user@host> show system services dynamic-dns client foo.example.com
Hostname      : foo.example.com
Type          : dyndns
Server        : members.dyndns.org
Username      : samks
Last update   : 2006-06-14 02:25:12 PDT
Last response: not-init
Interface     : ge-0/0/0.0
               ge-0/0/1.0

```



## show wan-acceleration status

<b>Syntax</b>	show wan-acceleration status
<b>Release Information</b>	Command introduced in Release 8.5 of JUNOS software.
<b>Description</b>	<p>Display the redirection status and related information about the WXC Integrated Services Module (ISM 200) for WAN acceleration.</p> <p>This command is supported on J-series devices.</p>
<b>Required Privilege Level</b>	view
<b>Related Topics</b>	<p>request wan-acceleration login on page 723</p> <p>restart wan-acceleration on page 726</p>
<b>List of Sample Output</b>	show wan-acceleration status on page 941
<b>Output Fields</b>	Table 98 on page 941 lists the output fields for the show wan-acceleration status command. Output fields are listed in the approximate order in which they appear.

**Table 98: show wan-acceleration status Output Fields**

Field Name	Field Description
Redirection status	Indicates whether traffic redirection to the WXC ISM 200 is active.
Interface	Name of the WXC ISM 200 interface.
Primary address	Address used to manage the WXC ISM 200, and as the source address of traffic sent across the WAN.
Secondary address	Source address of traffic destined for an alternate WAN path when the Multi-Path feature is configured (optional).
JUNOS version	Installed version of JUNOS software.
WXOS version	Installed version of WXOS.
JUNOS/WXOS protocol	Indicates whether the JUNOS software and WXOS versions are compatible.

```

show wan-acceleration status  user@host> show wan-acceleration status
                                Redirection status: active, Interface: wx-2/0/0
                                Primary address: 10.87.5.2, Secondary address: 0.0.0.0
                                JUNOS version: 9.0R1 Enhanced Services
                                WXOS version: 5.4.6.0j
                                JUNOS/WXOS protocol: Version compatible

```



## **Part 3**

# **Index**

- Index on page 945



# Index

## Symbols

#, comments in configuration statements.....	xxxi
( ), in syntax descriptions.....	xxxi
< >, in syntax descriptions.....	xxxi
[ ], in configuration statements.....	xxxi
{ }, in configuration statements.....	xxxi
(pipe), in syntax descriptions.....	xxxi
.....	211, 212, 213, 440

## A

Access Configuration Statement Hierarchy.....	3
access-profile statement.....	207
Accounting-Options Configuration Statement Hierarchy.....	45
ack-number statement.....	207
action statement.....	208
active-policy statement.....	209
address statement.....	210
(ARP Proxy Services Gateway).....	210
(Destination NAT Services Gateway).....	211
(Destination NAT Services Router).....	211
(IKE Gateway).....	212
(Source NAT).....	212
(Zone Address Book).....	213
(Zone Address Set).....	213
address-book statement.....	214
address-persistent statement.....	214
address-range statement.....	215
(Destination NAT).....	215
(Source NAT).....	215
address-set statement.....	216
admin-search statement.....	6
administrator statement.....	216
aging statement.....	217
alarm-threshold statement.....	218
alarm-without-drop statement.....	218
alert statement.....	219
alg statement.....	49, 220
algorithm statement.....	224
all-day statement.....	170
all-tcp statement.....	225

allow-dns-reply statement.....	225
allow-icmp-without-flow statement.....	226
allow-incoming statement.....	226
always-send statement.....	227
anomaly statement.....	227
application statement.....	228
(Protocol Binding Custom Attack).....	228
(Security Policies).....	228
application-identification statement.....	229
application-protocol statement.....	50
application-screen statement.....	230
(H323).....	230
(MGCP).....	231
(SCCP).....	231
(SIP).....	232
application-services statement.....	233
application-system-cache statement.....	233
application-system-cache-timeout statement.....	234
Applications Configurations Statement Hierarchy.....	47
assemble statement statement.....	7
attack-threshold statement.....	235
attack-type statement.....	238
(Custom Attack).....	238, 239, 240
attacks statement.....	236
(Exempt Rulebase).....	236
(IPS Rulebase).....	237
authentication statement.....	243
authentication-algorithm statement.....	244
authentication-method statement.....	245
authentication-order statement.....	8
authorization statement.....	620
auto-re-enrollment statement.....	246
automatic statement.....	247

## B

banner statement.....	9
(FTP, HTTP, Telnet).....	9
(Web Authentication).....	10
base-distinguished-name statement.....	11
bind-interface statement.....	247
braces, in configuration statements.....	xxxi
brackets	
angle, in syntax descriptions.....	xxxi
square, in configuration statements.....	xxxi

**C**

c-timeout statement.....	248	clear security flow session interface command.....	679
ca-identity statement.....	248	clear security flow session protocol command.....	680
ca-profile statement.....	249	clear security flow session resource-manager command.....	682
ca-profile-name statement.....	250	clear security flow session session-identifier command.....	683
cache statement.....	631	clear security flow session source-port command.....	684
cache-size statement.....	250	clear security flow session source-prefix command.....	685
call-flood statement.....	251	clear security idp application-identification application-system-cache command.....	686
category statement.....	251	clear security idp attack table command.....	687
certificate statement.....	252	clear security idp counters application-identification command.....	688
certificate-id statement.....	252	clear security idp counters dfa command.....	689
chain statement.....	253	clear security idp counters flow command.....	690
challenge-password statement.....	254	clear security idp counters ips command.....	691
Chassis Configuration Statement Hierarchy.....	61	clear security idp counters log command.....	692
check-first-session statement.....	254	clear security idp counters packet command.....	693
Class-of-Service Configuration Statement Hierarchy.....	79	clear security idp counters policy-manager command.....	694
clear chassis cluster control-plane statistics command.....	652	clear security idp counters tcp-reassembler command.....	695
clear chassis cluster data-plane statistics command.....	653	clear security ike respond-bad-spi-count command.....	696
clear chassis cluster failover-count command.....	654	clear security ike security-associations command.....	697
clear chassis cluster statistics command.....	655	clear security ipsec security-associations command.....	699
clear network-access requests pending command.....	656	clear security ipsec statistics command.....	700
clear network-access requests statistics command.....	657	clear security nat incoming-table command.....	701
clear network-access securid-node-secret-file command.....	658	clear security pki key-pair command.....	702
clear security alg h323 counters command.....	659	clear security pki local-certificate command.....	703
clear security alg mgcp calls command.....	660	clear security policies statistics command.....	704
clear security alg mgcp counters command.....	661	clear security screen statistics command.....	705
clear security alg msrpc portmap command.....	662	clear security screen statistics interface command.....	706
clear security alg sccp calls command.....	663	clear security screen statistics zone command.....	707
clear security alg sccp counters command.....	664	clear system services dns-proxy cache command.....	708
clear security alg sip calls command.....	665	clear system services dns-proxy statistics command.....	709
clear security alg sip counters command.....	666	clear-threshold statement.....	255
clear security alg sunrpc portmap command.....	667	client statement.....	632
clear security firewall-authentication history address command.....	669	client-group statement.....	12
clear security firewall-authentication history command.....	668	client-identifier statement.....	109
clear security firewall-authentication history identifier command.....	670	client-idle-timeout statement.....	12
clear security firewall-authentication users address command.....	672	client-list-name statement.....	620
clear security firewall-authentication users command.....	671	client-name-filter statement.....	13
clear security firewall-authentication users identifier command.....	673	client-session-timeout statement.....	13
clear security flow session all command.....	674	cluster statement.....	65
clear security flow session application command.....	675	code statement.....	255
clear security flow session destination-port command.....	677	comments, in configuration statements.....	xxxi
clear security flow session destination-prefix command.....	678	condition statement.....	122
		configuration-file statement.....	14
		connection-flood statement.....	256
		connections-limit statement.....	256

container statement.....257  
 context statement.....257  
 control-ports statement.....66  
 conventions  
   notice icons.....xxx  
   text and syntax.....xxx  
 count statement.....14, 258  
   (Custom Attack).....258  
   (Security Policies).....259  
 crl statement.....260  
 curly braces, in configuration statements.....xxxi  
 custom-attack statement.....261  
 custom-attack-group statement.....265  
 custom-attacks statement.....265  
 customer support.....xxxiv  
   contacting JTAC.....xxxiv

## D

daily statement.....171  
 data-length statement.....266  
 dead-peer-detection statement.....267  
 default-policy statement.....268  
 default-profile statement.....15  
 deny statement.....269  
   (Policy).....269  
   (SIP).....270  
 description statement.....271  
   (IDP Policy).....271  
   (Security Policies).....271  
 destination statement.....272  
   (Destination NAT Services Gateway).....273  
   (IP Headers in Signature Attack).....274  
 destination-address statement.....275  
   (Destination NAT Services Gateway).....275  
   (IDP Policy).....276  
   (Security Policies).....276  
   (Source NAT Services Gateway).....277  
   (Traffic Policy Services Gateway).....278  
 destination-except statement.....278  
 destination-ip statement.....279  
 destination-ip-based statement.....279  
 destination-nat statement.....280  
   (Destination NAT Services Gateway).....280  
   (Destination NAT Services Router).....281  
   (Security Policies).....282  
 destination-port statement.....51, 283  
   (Destination NAT Services Gateway).....283  
   (Signature Attack).....284  
 destination-threshold statement.....285  
 detect-shellcode statement.....285  
 detector statement.....286  
 df-bit statement.....286  
 dh-group statement.....287  
 dhcp statement.....109

direction statement.....288  
   (Custom Attack).....288  
   (Dynamic Attack Group).....289  
 disable-call-id-hiding statement.....289  
 distinguished-name statement.....15, 290  
 dns statement.....291  
 dns-proxy statement.....633  
 documentation set  
   comments on.....xxxiii  
   list of.....xxxii  
 domain-name statement.....16, 634  
 dynamic statement.....292  
 dynamic-attack-group statement.....293  
 dynamic-dns statement.....634

## E

early-ageout statement.....294  
 enable-all-qmodules statement.....294  
 enable-packet-pool statement.....295  
 encryption statement.....296  
 encryption-algorithm statement.....297  
 endpoint-registration-timeout statement.....297  
 enroll statement.....298  
 establish-tunnels statement.....299  
 Event-Options Configuration Statement Hierarchy.....83  
 exclude statement.....172  
 expression statement.....300  
 external-interface statement.....301  
   (IKE Gateway).....301  
   (Manual Security Association).....301

## F

fabric-options statement.....110  
 fail statement.....16  
 false-positives statement.....302  
 family statement.....303  
 filters statement.....304  
 fin-no-ack statement.....305  
 Firewall Configuration Statement Hierarchy.....85  
 firewall filters  
   statistics  
     clearing .....857  
     displaying.....928, 932, 937  
 firewall-authentication statement.....17, 306  
   (Policies).....306  
   (Security).....307  
 firewall-authentication-service statement.....635  
 firewall-user statement.....18  
 flood statement.....308  
   (ICMP).....308  
   (UDP).....309  
 flow statement.....310  
   (IDP).....310  
   (Security Flow).....311

flow-control statement.....	110
font conventions.....	xxx
Forwarding-Options Configuration Statement Hierarchy.....	89
forwarding-options statement.....	312
fragment statement.....	313
friday statement.....	173
from statement.....	313
from-zone statement.....	314
(IDP Policy).....	314
(Security Policies).....	315
ftp statement.....	18, 317
functional-zone statement.....	318

**G**

gatekeeper statement.....	319
gateway statement.....	320
(IKE).....	321
(IPsec).....	322
(Manual Security Association).....	322
general-authentication-service statement.....	636
gratuitous-arp-count statement.....	67
gre-in statement.....	324
gre-out statement.....	325
group-members statement.....	326
Groups Configuration Statement Hierarchy.....	95

**H**

h323 statement.....	327
hardware	
supported platforms.....	xxviii
header-length statement.....	328
heartbeat-interval statement.....	67
heartbeat-threshold statement.....	68
help-text = " Hostname and IPV4 address of DNS query".....	631
high-watermark statement.....	328
host-address-base statement.....	329
host-address-low statement.....	329
host-inbound-traffic statement.....	330
hostname statement.....	331
http statement.....	19

**I**

icmp statement.....	332
(Protocol Binding Custom Attack).....	332
(Security Screen).....	333
(Signature Attack).....	334
icmp-code statement.....	54
icmp-type statement.....	55
identification statement.....	335
(ICMP Headers in Signature Attack).....	335
(IP Headers in Signature Attack).....	336

idle-time statement.....	336
idp statement.....	337
idp-policy statement.....	344
ids-option statement.....	346
ignore-mem-overflow statement.....	347
ignore-regular-expression statement.....	348
ike statement.....	349
(IPsec VPN).....	349
(Security).....	350
ike-policy statement.....	351
ike-user-type statement.....	352
inactive-media-timeout statement.....	353
(MGCP).....	353
(SCCP).....	354
(SIP).....	354
inactivity-timeout statement.....	55
include-destination-address statement.....	355
inet statement.....	355
inet6 statement.....	356
install-interval statement.....	356
interface statement.....	357, 637
(ARP Proxy Services Gateway).....	357
(NAT Services Router).....	358
interface-monitor statement.....	68
Interfaces Configuration Statement Hierarchy.....	97
interfaces statement.....	359
interval statement.....	360
(IDP).....	360
(IKE).....	360
ip statement.....	361
(Protocol Binding Custom Attack).....	361
(Security Screen).....	362
(Signature Attack).....	364
ip-action statement.....	365
ip-block statement.....	365
ip-close statement.....	366
ip-flags statement.....	366
ip-notify statement.....	367
ip-sweep statement.....	370
ips statement.....	367
ipsec-policy statement.....	368
ipsec-vpn statement.....	369
(Flow).....	369
(Policies).....	370
iso statement.....	371

**J**

JUNOS software	
release notes, URL.....	xxvii

**L**

land statement.....	371
large statement.....	372
ldap-options statement.....	20



ldap-server statement.....	21
lease-time statement.....	111
lifetime-kilobytes statement.....	372
limit-session statement.....	373
link-speed statement.....	111
local statement.....	373
local-certificate statement.....	374
local-identity statement.....	375
log statement.....	376
(IDP Policy).....	377
(IDP).....	376
(Security Policies).....	377
log-attacks statement.....	378
log-errors statement.....	378
log-supercede-min statement.....	379
login statement.....	22
loopback statement.....	112
low-watermark statement.....	379

## M

management statement.....	380
manual statement.....	381
manuels	
comments on.....	xxxiii
list of .....	xxxii
match statement.....	382
(Destination NAT Services Gateway).....	382
(IDP Policy).....	383
(Security Policies).....	384
(Source NAT Services Gateway).....	384
max-flow-mem statement.....	385
max-logs-operate statement.....	386
max-packet-mem statement.....	386
max-packet-memory statement.....	387
max-sessions statement.....	387
max-tcp-session-packet-memory statement.....	388
max-time-report statement.....	388
max-timers-poll-ticks statement.....	389
max-udp-session-packet-memory statement.....	389
maximum-call-duration statement.....	390
media-source-port-any statement.....	390
member statement.....	391
member-interfaces statement.....	112
message-flood statement.....	392
(H323).....	392
(MGCP).....	393
mgcp statement.....	394
mode statement.....	395
(Forwarding Options).....	395
(Policy).....	396
monday statement.....	174
mpls statement.....	396
msrpc statement.....	397
mss statement.....	398

## N

name-server statement.....	637
nat statement.....	399
(Services Gateway Configuration).....	400
(Services Router Configuration).....	402
nat-keepalive statement.....	403
negate statement.....	404
network-security statement.....	638
next-hop-tunnel statement.....	113
no-allow-icmp-without-flow statement.....	404
no-anti-replay statement.....	404
no-enable-all-qmodules statement.....	404
no-enable-packet-pool statement.....	405
no-flow-control statement.....	113
no-log-errors statement.....	405
no-loopback statement.....	113
no-nat-traversal statement.....	405
no-policy-lookup-cache statement.....	405
no-port-translation statement.....	406
no-reset-on-policy statement.....	406
no-sequence-check statement.....	406
no-source-filtering statement.....	113
no-syn-check statement.....	407
no-syn-check-in-tunnel statement.....	407
node statement.....	69
(Cluster).....	69
(Redundancy-Group).....	70
notice icons.....	xxx
notification statement.....	408

## O

optimized statement.....	408
option statement.....	409
order statement.....	409
overflow-pool statement.....	410
(Source NAT Services Router).....	411
;(Source NAT Services Gateway).....	410

## P

pair-policy statement.....	412
parentheses, in syntax descriptions.....	xxx
pass-through statement.....	23, 413
password statement.....	24
pattern statement.....	414
peer-certificate-type statement.....	414
perfect-forward-secrecy statement.....	415
performance statement.....	416
permit statement.....	417
pic-mode statement.....	71
ping-death statement.....	418
pki statement.....	419
pki-local-certificate statement.....	638
policers, displaying.....	912
policies statement.....	421

policy statement.....	423	re-assembler statement.....	460
(IKE).....	423	re-enroll-trigger-time-percentage statement.....	460
policy statement: (Security).....	425	real statement.....	459
policy-lookup-cache statement.....	426	recommended statement.....	461
Policy-Options Configuration Statement		recommended-action statement.....	462
Hierarchy.....	121	redundancy-group statement.....	73, 114
policy-rematch statement.....	427	redundant-ether-options statement.....	114
pool statement.....	428	redundant-parent statement.....	115
(Destination NAT Services Gateway).....	428	(Fast Ethernet Options).....	115
(Pool Set).....	429	(Gigabit Ethernet Options).....	115
(Source NAT Services Gateway).....	430	regexp statement.....	463
(Source NAT).....	429	reject statement.....	463
pool-set statement.....	430	reject-timeout statement.....	464
pool-utilization-alarm statement.....	431	release notes, URL.....	xxvii
port statement.....	25, 432	remote statement.....	464
(LDAP).....	25	request chassis cluster failover node command.....	712
(RADIUS).....	25	request chassis cluster failover reset command.....	713
port-scan statement.....	433	request security idp security-package download	
pptp statement.....	434	command.....	714
pre-filter-shellcode statement.....	435	request security idp security-package install	
pre-shared-key statement.....	436	command.....	716
predefined-attack-groups statement.....	435	request security pki ca-certificate verify	
predefined-attacks statement.....	436	command.....	717
preempt statement.....	72	request security pki local-certificate generate-self-signed	
priority statement.....	72	command.....	718
process-ignore-s2c statement.....	437	request security pki local-certificate verify	
process-override statement.....	437	command.....	720
process-port statement.....	438	request system partition compact-flash	
products statement.....	438	command.....	721
propagate-settings statement.....	639	request system services dhcp command.....	722
proposal statement.....	439	request wan-acceleration login command.....	723
proposal-set statement.....	440	reset statement.....	465
(IKE).....	441	reset-on-policy statement.....	465
(IPsec).....	442	respond-bad-spi statement.....	466
protect statement.....	443	restart wan-acceleration command.....	726
protocol statement.....	56, 444	retain-hold-resource statement.....	466
(IP Headers in Signature Attack).....	445	reth-count statement.....	74
(IPsec).....	444	retransmission-attempt statement.....	116
(Manual Security Association).....	445	retransmission-interval statement.....	116
(Signature Attack).....	446	retry statement.....	28
protocol-binding statement.....	449	(LDAP).....	28
protocol-name statement.....	450	(RADIUS).....	29
Protocols Configuration Statement Hierarchy.....	125	revert-interval statement.....	30
protocols statement.....	451	(LDAP).....	30
(Interface Host-Inbound Traffic).....	452	(RADIUS).....	31
(Zone Host-Inbound Traffic).....	454	revocation-check statement.....	467
proxy-arp statement.....	456	route-active-on statement.....	123
(Services Gateway Configuration).....	456	route-change-timeout statement.....	468
(Services Router Configuration).....	457	routing-instance statement.....	469
proxy-identity statement.....	457	(Destination NAT Services Gateway).....	469
		(LDAP).....	32
		(RADIUS).....	33
		(Source NAT Services Gateway).....	469
		Routing-Instances Configuration Statement	
		Hierarchy.....	149

**R**

radius-options statement.....	26
radius-server statement.....	27
raise-threshold statement.....	458

Routing-Options Configuration Statement	
Hierarchy.....	161
rpc statement.....	470
rpc-program-number statement.....	57
rsh statement.....	471
rst-invalidate-session statement.....	472
rst-sequence-check statement.....	472
rtsp statement.....	473
rule statement.....	474
(destination NAT).....	474
(Exempt Rulebase).....	475
(IPS Rulebase).....	476
(Source NAT).....	477
rule-set statement.....	479
(Destination NAT Services Gateway).....	479
(Source NAT Services Gateway).....	480
rulebase-exempt statement.....	482
rulebase-ips statement.....	483
<b>S</b>	
saturday statement.....	175
sccp statement.....	484
scheduler statement.....	176
scheduler-name statement.....	485
Schedulers Configuration Statement Hierarchy.....	169
schedulers statement.....	177
scope statement.....	486
(Chain Attack).....	486
(Custom Attack).....	487
screen statement.....	488
(Security).....	489
(Zones).....	490
search statement.....	33
search-filter statement.....	34
secret statement.....	34
securid-server statement.....	35
Security Configuration Statement Hierarchy.....	185
security-package statement.....	491
security-zone statement.....	492
sensor-configuration statement.....	494
separator statement.....	36
sequence-number statement.....	497
(ICMP Headers in Signature Attack).....	497
(TCP Headers in Signature Attack).....	498
server-address statement.....	117
server-select statement.....	639
service statement.....	499
(Anomaly Attack).....	499
(Dynamic Attack Group).....	499
(Security IPsec).....	500
Services Configuration Statement Hierarchy.....	613
session-close statement.....	495
session-init statement.....	496
session-options statement.....	37
severity statement.....	501
(Custom Attack).....	501
(Dynamic Attack Group).....	502
(IPS Rulebase).....	503
shellcode statement.....	504
show bgp neighbor command.....	728
show chassis cluster control-plane statistics	
command.....	732
show chassis cluster data-plane statistics	
command.....	733
show chassis cluster interfaces command.....	735
show chassis cluster statistics command.....	736
show chassis cluster status command.....	739
show chassis fpc command.....	741
show chassis hardware command.....	744
show interfaces command.....	749
show interfaces flow-statistics command.....	754
show network-access requests pending	
command.....	757
show network-access requests statistics	
command.....	759
show network-access securid-node-secret-file	
command.....	760
show schedulers command.....	761
show security alg h323 counters command.....	763
show security alg mgcp calls command.....	765
show security alg mgcp counters command.....	767
show security alg mgcp endpoints command.....	769
show security alg msrpc command.....	771
show security alg sccp calls command.....	773
show security alg sccp counters command.....	775
show security alg sip calls command.....	777
show security alg sip counters command.....	780
show security alg sip rate command.....	784
show security alg sip transactions command.....	786
show security alg sunrpc portmap command.....	787
show security firewall-authentication history address	
command.....	790
show security firewall-authentication history	
command.....	788
show security firewall-authentication history identifier	
command.....	793
show security firewall-authentication users address	
command.....	798
show security firewall-authentication users	
command.....	796
show security firewall-authentication users identifier	
command.....	800
show security flow gate command.....	802
show security flow session application	
command.....	807
show security flow session command.....	805
show security flow session destination-port	
command.....	809
show security flow session destination-prefix	
command.....	811

show security flow session interface command.....	813	show security pki certificate-request command.....	904
show security flow session protocol command.....	815	show security pki crl command.....	906
show security flow session resource-manager command.....	818	show security pki local-certificate command.....	908
show security flow session session-identifier command.....	820	show security policies command.....	912
show security flow session source-port command.....	824	show security resource-manager group active command.....	915
show security flow session source-prefix command.....	826	show security resource-manager resource active command.....	917
show security flow session summary command.....	828	show security resource-manager settings command.....	919
show security flow session tunnel command.....	830	show security screen ids-option command.....	921
show security idp active-policy command.....	832	show security screen statistics command.....	923
show security idp application-identification application-system-cache command.....	833	show security zones command.....	928
show security idp attack table command.....	834	show security zones type command.....	930
show security idp counters application-identification command.....	835	show system services dhcp client command.....	932
show security idp counters dfa command.....	837	show system services dhcp relay-statistics command.....	935
show security idp counters flow command.....	838	show system services dns-proxy command.....	937
show security idp counters ips command.....	841	show system services dynamic-dns client command.....	939
show security idp counters log command.....	843	show wan-acceleration status command.....	941
show security idp counters packet command.....	846	signature statement.....	505
show security idp counters policy-manager command.....	849	sip statement.....	509
show security idp counters tcp-reassembler command.....	850	SNMP Configuration Statement Hierarchy.....	615
show security idp memory command.....	853	source statement.....	510
show security idp security-package-version command.....	854	(IP Headers in Signature Attack).....	510
show security idp status command.....	855	(Source NAT Services Gateway).....	511
show security ike pre-shared-key command.....	856	source-address statement.....	38, 513
show security ike security-associations command.....	857	(Destination NAT Services Gateway).....	513
show security ipsec next-hop-tunnels command.....	862	(IDP Policy).....	514
show security ipsec security-associations command.....	863	(LDAP).....	38
show security ipsec statistics command.....	869	(RADIUS).....	38
show security monitoring fpc fpc-number command.....	872	(Security Policies).....	514
show security nat destination pool command.....	874	(Source NAT Services Gateway).....	515
show security nat destination rule command.....	876	source-address-filter statement.....	117
show security nat destination summary command.....	879	source-except statement.....	515
show security nat destination-nat summary command.....	881	source-filtering statement.....	118
show security nat incoming-table command.....	882	source-interface statement.....	516
show security nat interface-nat-ports command.....	884	source-ip-based statement.....	516
show security nat source pool command.....	886	source-nat statement.....	517
show security nat source rule command.....	888	(NAT).....	517
show security nat source summary command.....	891	source-nat statement: (NAT Interface).....	518
show security nat source-nat pool command.....	893	source-nat statement: (Security Policies).....	519
show security nat source-nat summary command.....	895	source-nat statement: (Source NAT Services Gateway).....	519
show security nat static-nat summary command.....	898	source-port statement.....	57, 520
show security pki ca-certificate command.....	900	source-threshold statement.....	521
		sql statement.....	522
		ssh-known-hosts statement.....	523
		start-date statement.....	177
		start-log statement.....	525
		start-time statement.....	178, 525
		static statement.....	526
		static-nat statement.....	527
		stop-date statement.....	179

stop-time statement.....	180
success statement.....	39
sunday statement.....	181
sunrpc statement.....	529
support, technical <i>See</i> technical support	
suppression statement.....	530
syn-ack-ack-proxy statement.....	531
syn-fin statement.....	531
syn-flood statement.....	532
syn-flood-protection-mode statement.....	533
syn-frag statement.....	534
syntax conventions.....	xxx
System Configuration Statement Hierarchy.....	621
system-generated-certificate statement.....	640
system-services statement.....	535
(Interface Host-Inbound Traffic).....	536
(Zone Host-Inbound Traffic).....	538

## T

t1-interval statement.....	539
t4-interval statement.....	540
talk statement.....	541
target statement.....	542
tcp statement.....	543
(Protocol Binding Custom Attack).....	543
(Security Screen).....	544
(Signature Attack).....	545
tcp-flags statement.....	547
tcp-initial-timeout statement.....	548
tcp-mss statement.....	549
tcp-no-flag statement.....	550
tcp-rst statement.....	550
tcp-session statement.....	551
technical publications list.....	xxxii
technical support	
contacting JTAC.....	xxxiv
telnet statement.....	40
term statement.....	58
terminal statement.....	552
test statement.....	552
tftp statement.....	553
then statement.....	554
(Destination NAT Services Gateway).....	554
(IDP Policy).....	555
(Security Policies).....	556
(Source NAT Services gateway).....	557
threshold statement.....	558
thursday statement.....	182
time-binding statement.....	558
timeout statement.....	41, 559
(IDP Policy).....	559
(LDAP Server).....	41
(RADIUS Server).....	42
(Security Screen).....	560
to statement.....	560

to-zone statement.....	561
tos statement.....	562
total-length statement.....	563
traceoptions statement.....	43, 75, 564, 641
(DNS Proxy).....	642
(firewall-authentication).....	565
(Flow).....	567
(General Authentication Service).....	644
(H.323 ALG).....	566
(IDP).....	569
(IKE).....	571
(IPsec).....	572
(MGCP ALG).....	573
(NAT Services Gateway).....	574
(NAT Services Router).....	576
(PKI).....	578
(Policies).....	580
(SCCP ALG).....	582
(Screen).....	583
(Security).....	585
(SIP ALG).....	587
(WAN Acceleration).....	646
transaction-timeout statement.....	588
trusted-ca statement.....	588
ttl statement.....	589
tuesday statement.....	183
tunable-name statement.....	590
tunable-value statement.....	590
tunnel statement.....	591
tunnel-queuing statement.....	76
type statement.....	592
(Dynamic Attack Group).....	593
(ICMP Headers in Signature Attack).....	592

## U

udp statement.....	594
(Protocol Binding Custom Attack).....	594
(Security Screen).....	595
(Signature Attack).....	596
unknown-message statement.....	597
(H.323 ALG).....	597
(MGCP ALG).....	598
(SCCP ALG).....	599
(SIP ALG).....	600
update-server statement.....	118
urgent-pointer statement.....	601
url statement.....	601
URLs	
release notes.....	xxvii
user-at-hostname statement.....	602
uuid statement.....	59

## V

vendor-id statement.....	119
--------------------------	-----

vpn statement.....	93, 603
vpn-monitor statement.....	604
vpn-monitor-options statement.....	605

## W

wan-acceleration statement.....	647
web-authentication statement.....	44, 119, 606
web-redirect statement.....	607
wednesday statement.....	184
weight statement.....	77
wildcard statement.....	608
window-scale statement.....	608
window-size statement.....	609
winnuke statement.....	609

## X

xauth statement.....	610
----------------------	-----

## Z

zones statement .....	611
-----------------------	-----