

Chapter 20

DTD for Dialer Response Tags

This chapter contains the Extensible Markup Language (XML) document type definition (DTD) called `junos-dood.dtd`, which lists the JUNOS XML tags that contain Integrated Services Digital Network (ISDN) dialer information. The associated XML namespace is `http://xml.juniper.net/junos/9.3R1/junos-dood`. To review reference pages for the tags, see “Summary of Dialer Response Tags” on page 641.

```
<!-- Copyright (c) 2000-2008, Juniper Networks, Inc. -->
<!-- All rights reserved. -->
<!-- junos-dood.dtd -->
```

```
<!ELEMENT activation-delay (#PCDATA)>
```

```
<!ELEMENT activation-delay-elapsed (#PCDATA)>
```

```
<!ELEMENT backup EMPTY>
```

```
<!ELEMENT call-idle-timeout (#PCDATA)>
```

```
<!ELEMENT callback-wait-period (#PCDATA)>
```

```
<!ELEMENT callback-wait-period-elapsed (#PCDATA)>
```

```
<!ELEMENT deactivation-delay (#PCDATA)>
```

```
<!ELEMENT deactivation-delay-elapsed (#PCDATA)>
```

```
<!ELEMENT default-activation-delay (#PCDATA)>
```

```
<!ELEMENT default-callback-wait-period (#PCDATA)>
```

```
<!ELEMENT default-deactivation-delay (#PCDATA)>
```

```
<!ELEMENT default-idle-timeout (#PCDATA)>
```

```
<!ELEMENT default-initial-route-check (#PCDATA)>
```

```
<!ELEMENT default-load-interval (#PCDATA)>
```

```
<!ELEMENT default-load-threshold (#PCDATA)>
```

```
<!ELEMENT default-pool-priority (#PCDATA)>
```

```
<!ELEMENT default-redial-delay (#PCDATA)>
```

```

<!ELEMENT dial-string (#PCDATA)>

<!ELEMENT dial-string-list (dial-string)*>
<!ATTLIST dial-string-list junos:style CDATA #IMPLIED>

<!ELEMENT dialer-defaults-information (default-idle-timeout | default-activation-delay |
default-deactivation-delay | default-initial-route-check | default-pool-priority |
default-load-threshold | default-load-interval | default-redial-delay |
default-callback-wait-period)*>

<!ELEMENT dialer-info (dialer-interface-name | dialer-interface-state |
dialer-interface-flags)*>

<!ELEMENT dialer-interface (dialer-interface-name | dialer-interface-state |
dialer-interface-flags | pool-id | primary-interface | dial-string-list | sub-interface-list |
watch-list | activation-delay | deactivation-delay | activation-delay-elapsed |
deactivation-delay-elapsed | call-idle-timeout | initial-route-check | redial-delay |
callback-wait-period | callback-wait-period-elapsed | load-threshold | load-interval)*>

<!ELEMENT dialer-interface-flags (backup | multilink | watchlist | interesting-detected)*>

<!ELEMENT dialer-interface-information (dialer-interface)*>
<!ATTLIST dialer-interface-information junos:style CDATA #IMPLIED>

<!ELEMENT dialer-interface-name (#PCDATA)>

<!ELEMENT dialer-interface-state (#PCDATA)>

<!ELEMENT dialer-pool (pool-id | pool-member-list)*>

<!ELEMENT dialer-pool-information (dialer-pool)*>
<!ATTLIST dialer-pool-information junos:style CDATA #IMPLIED>

<!ELEMENT initial-route-check (#PCDATA)>

<!ELEMENT interesting-detected EMPTY>

<!ELEMENT load-interval (#PCDATA)>

<!ELEMENT load-threshold (#PCDATA)>

<!ELEMENT multilink EMPTY>

<!ELEMENT pool-id (#PCDATA)>

<!ELEMENT pool-member-list (dialer-info | sub-info)*>

<!ELEMENT pool-priority (#PCDATA)>

<!ELEMENT primary-interface (#PCDATA)>

<!ELEMENT redial-delay (#PCDATA)>

<!ELEMENT sub-info (sub-interface-name | sub-interface-flags | pool-priority)*>

<!ELEMENT sub-interface-flags (#PCDATA)>

```

```
<!ELEMENT sub-interface-list (sub-interface-name)*>  
<!ATTLIST sub-interface-list junos:style CDATA #IMPLIED>  
  
<!ELEMENT sub-interface-name (#PCDATA)>  
  
<!ELEMENT watch-list (watch-route)*>  
<!ATTLIST watch-list junos:style CDATA #IMPLIED>  
  
<!ELEMENT watch-route (#PCDATA)>  
  
<!ELEMENT watchlist EMPTY>
```

