

Chapter 10

Tag Elements Beginning with J

This chapter lists the configuration tag elements that have names beginning with the letter *j*. The tag names are in alphabetical order. For information about the notation used in this chapter, see Table 2 on page cdxiii.

For information about the tag elements that client applications use to request, change, and commit configuration information, see the *JUNOScript API Guide* and *NETCONF API Guide*.

<jnx-example> (configuration)

| | |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Usage | <pre><configuration> <jnx-example> <traceoptions>...</traceoptions> <jnx-example-data>...</jnx-example-data> </jnx-example> </configuration></pre> |
| Description | Example service configuration. |
| Contents | <p><jnx-example-data>—Example data entries.</p> <p><traceoptions>—Example service trace options.</p> |

<jnx-example-data> (configuration/jnx-example)

Usage <configuration>
 <jnx-example>
 <jnx-example-data>
 <name>*name*</name> <!-- identifier -->
 <description>*description*</description>
 <type>*type-choice*</type>
 <value>*value*</value>
 </jnx-example-data>
 </jnx-example>
 </configuration>

Description Example data entries.

Contents <description>—General description of data.

 <name>—Example data identifier.

 <type>—Example data type.

- fat—Fat data.
- none—No type.
- skinny—Skinny data.

 <value>—Example data value.