

Chapter 63

DTD for Telephony Gateway Module Response Tags

This chapter contains the Extensible Markup Language (XML) document type definition (DTD) called `junos-tmgd.dtd`, which lists the JUNOS XML tags that contain information about the Telephony Gateway Module, a component that supports voice-over-IP services on some models of J-series Services Router. The associated XML namespace is <http://xml.juniper.net/junos/9.4R1/junos-tmgd>. To review reference pages for the tags, see “Summary of Telephony Gateway Module Response Tags” on page 1646.

```
<!-- Copyright (c) 2000-2008, Juniper Networks, Inc. -->
```

```
<!-- All rights reserved. -->
```

```
<!-- junos-tmgd.dtd -->
```

```
<!ELEMENT dsp-capacity (#PCDATA)>
```

```
<!ELEMENT dynamic-cac-activation-priority (#PCDATA)>
```

```
<!ELEMENT dynamic-cac-bbl (#PCDATA)>
```

```
<!ELEMENT dynamic-cac-information (dynamic-cac-interface-name |  
dynamic-cac-interface-state | dynamic-cac-activation-priority | dynamic-cac-bbl)*>
```

```
<!ELEMENT dynamic-cac-interface-name (#PCDATA)>
```

```
<!ELEMENT dynamic-cac-interface-state (#PCDATA)>
```

```
<!ELEMENT media-gateway-controller (#PCDATA)>
```

```
<!ELEMENT media-gateway-controller-configuration (media-gateway-controller)*>
```

```
<!ELEMENT offline-reason (#PCDATA)>
```

```
<!ELEMENT slot (#PCDATA)>
```

```
<!ELEMENT telephony-interface-module-status (slot | tim-state | offline-reason)*>
```

```
<!ELEMENT telephony-interface-module-status-information  
(telephony-interface-module-status)*>
```

```
<!ELEMENT tgm-dsp-capacity-information (dsp-capacity)*>
```

```
<!ELEMENT tgm-dynamic-cac-information (tgm-reported-bearer-bandwidth-limit |  
tgm-dynamic-cac-list)*>
```

```
<!ELEMENT tgm-dynamic-cac-list (dynamic-cac-information)*>
```

```
<!ELEMENT tgm-information (media-gateway-controller-configuration)*>
```

```
<!ELEMENT tgm-reported-bearer-bandwidth-limit (#PCDATA)>
```

```
<!ELEMENT tim-state (#PCDATA)>
```