

Configuring Shadow Nodes

Before you configure shadow nodes:

- Configure the traffic classes.
See Configuring Traffic Classes That Define Service Levels.
- Configure the queuing hierarchy.
See Configuring Queue Profiles to Manage Buffers and Thresholds.
- Configure the scheduler hierarchy and shaping with scheduler profiles.
See Configuring a Scheduler Hierarchy.

To add a shadow node to a QoS profile:

1. Create a QoS profile and enter QoS Profile Configuration mode.

```
host1(config)#qos-profile shadowNode
host1(config-qos-profile)#
```

2. Configure a scheduler node for each interface of the specified type.

```
host1(config-qos-profile)#atm node scheduler-profile default
```

3. Configure a shadow node for each interface of the specified type.

```
host1(config-qos-profile)#atm shadow-node scheduler-profile default
```

4. Configure a queue for interfaces in the specified traffic class.

```
host1(config-qos-profile)#atm queue traffic-class strict-priority scheduler-profile
scheduler1
```

5. (Optional) Configure a traffic-class group and reference a scheduler profile in the QoS profile.

```
host1(config-qos-profile)#atm group default scheduler-profile default
```

The router creates the shadow node when the following conditions are met:

- After all the nodes and group nodes are created.
- If the queues are not at the required scheduler level.
- When a node of the same interface type has existed in the same group of the scheduler hierarchy.

Related Topics

- Shadow Node Overview
- Shadow Nodes and Scheduler Behavior
- Managing System Resources for Shadow Nodes

- Monitoring a Scheduler Hierarchy on an Interface with QoS Profiles
- group
- node
- qos-profile
- queue
- shadow-node

Published: 2010-03-21