



---

# JunosE™ Software for E Series™ Broadband Services Routers

## Command Reference A to M

Release

13.1.x



---

Published: 2012-03-30

Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, California 94089  
USA  
408-745-2000  
[www.juniper.net](http://www.juniper.net)

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Products made or sold by Juniper Networks or components thereof might be covered by one or more of the following patents that are owned by or licensed to Juniper Networks: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

*JunosE™ Software for E Series™ Broadband Services Routers Command Reference Guide A to M*  
Release 13.1.x  
Copyright © 2012, Juniper Networks, Inc.  
All rights reserved.

Revision History  
April 2012—FRS JunosE 13.1.x

The information in this document is current as of the date on the title page.

#### YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

#### END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <http://www.juniper.net/support/eula.html>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

# Abbreviated Table of Contents

	About the Documentation .....	xxxvii
Part 1	Commands, A to M	
Chapter 1	Command Reference Topics .....	3
Chapter 2	A Commands .....	19
Chapter 3	B Commands .....	223
Chapter 4	C Commands .....	361
Chapter 5	D Commands .....	487
Chapter 6	E Commands .....	567
Chapter 7	F Commands .....	637
Chapter 8	G Commands .....	675
Chapter 9	H Commands .....	691
Chapter 10	I Commands .....	707
Chapter 11	K Commands .....	1169
Chapter 12	L Commands .....	1173
Chapter 13	M Commands .....	1285
Part 2	Index	
	Index .....	1469





# Table of Contents

	<b>About the Documentation . . . . .</b>	<b>xxxvii</b>
	E Series and JunosE Documentation and Release Notes . . . . .	xxxvii
	Audience . . . . .	xxxvii
	E Series and JunosE Text and Syntax Conventions . . . . .	xxxvii
	Obtaining Documentation . . . . .	xxxix
	Documentation Feedback . . . . .	xxxix
	Requesting Technical Support . . . . .	xxxix
	Self-Help Online Tools and Resources . . . . .	xl
	Opening a Case with JTAC . . . . .	xl
<b>Part 1</b>	<b>Commands, A to M</b>	
<b>Chapter 1</b>	<b>Command Reference Topics . . . . .</b>	<b>3</b>
	Using the no Version Versus the default Version of Commands . . . . .	3
	Deprecated Commands . . . . .	4
	Filtering show Commands . . . . .	4
	Interface Types and Specifiers . . . . .	5
<b>Chapter 2</b>	<b>A Commands . . . . .</b>	<b>19</b>
	aaa accounting acct-stop on-aaa-failure . . . . .	20
	aaa accounting acct-stop on-access-deny . . . . .	21
	aaa accounting broadcast . . . . .	22
	aaa accounting commands . . . . .	23
	aaa accounting default . . . . .	24
	aaa accounting duplication . . . . .	25
	aaa accounting exec . . . . .	26
	aaa accounting immediate-update . . . . .	27
	aaa accounting interval . . . . .	28
	aaa accounting statistics . . . . .	29
	aaa accounting suppress null-username . . . . .	30
	aaa accounting vr-group . . . . .	31
	aaa authentication default . . . . .	32
	aaa authentication enable default . . . . .	33
	aaa authentication login . . . . .	34
	aaa authorization . . . . .	35
	aaa authorization config-commands . . . . .	36
	aaa delimiter . . . . .	37
	aaa dhcpv6-delegated-prefix delegated-ipv6-prefix . . . . .	38
	aaa dhcpv6-ndra-pool override . . . . .	39
	aaa dns . . . . .	40
	aaa domain-map . . . . .	41

aaa duplicate-address-check	42
aaa duplicate-prefix-check	43
aaa duplicate-prefix-check-extension	44
aaa intf-desc-format include	45
aaa ipv4-addr-saving	46
aaa ipv6-dns	47
aaa ipv6-nd-ra-prefix framed-ipv6-prefix	48
aaa local database	49
aaa local select database	50
aaa local username	51
aaa new-model	52
aaa parse-direction	53
aaa parse-order	54
aaa per-profile-attr-list	55
aaa per-profile-attr-list (For Global Configuration)	56
aaa-perprofilelist-name	57
aaa profile	58
aaa qos downstream-rate	59
aaa route-download	60
aaa route-download ipv6	61
aaa route-download ipv6 now	62
aaa route-download now	63
aaa route-download suspend	64
aaa service accounting interval	65
aaa strip-domain	66
aaa subscriber limit per-port	68
aaa subscriber limit per-vr	69
aaa timeout	70
aaa tunnel assignment-id-format	71
aaa tunnel calling-number-format	72
aaa tunnel calling-number-format-fallback	75
aaa tunnel client-name	77
aaa tunnel-group	78
aaa tunnel ignore	79
aaa tunnel nas-port-method	80
aaa tunnel password	81
aaa tunnel switch-profile	82
aaa tunnel tx-connect-speed-method	83
aaa user accounting interval	84
aaa virtual-router	85
aaa wins	86
access-class in	87
access-list	88
accounting	89
action-type	90
adapter accept	91
adapter disable	92
adapter enable	93
adapter erase	94

address	95
address area	96
address authentication key	97
address authentication-key	98
address authentication message-digest	99
address authentication mode	100
address authentication-none	101
address bfd-liveness-detection	102
address cost	103
address dead-interval	104
address-family	105
address hello-interval	107
address message-digest-key md5	108
address network	109
address passive-interface	110
address-pool-name	111
address priority	112
address receive version	113
address retransmit-interval	114
address send version	115
address transmit-delay	116
adjustment-factor	117
advertise-passive-only	118
agent context-name	119
aggregate-address	120
aggregation-node	121
aggressive-mode	122
allow	123
append-after	124
application	125
aps events	126
aps force	127
aps group	128
aps lockdown	129
aps manual	130
aps protect	131
aps revert	132
aps unidirectional	133
aps working	134
area	135
area-authentication	136
area-authentication-key	137
area default-cost	138
area-message-digest-key	139
area nssa	141
area range	142
area stub	143
area virtual-link	144
area virtual-link authentication-key	145

area virtual-link authentication message-digest	146
area virtual-link authentication-none	147
area virtual-link dead-interval	148
area virtual-link hello-interval	149
area virtual-link message-digest-key md5	150
area virtual-link retransmit-interval	151
area virtual-link transmit-delay	152
arp	153
arp spoof-check	154
arp timeout	155
assured-rate	156
atm	157
atm aal5 description	158
atm aal5 shutdown	159
atm aal5 snmp trap link-status	160
atm atm1483 advisory-rx-speed	161
atm atm1483 auto-configure	162
atm atm1483 description	163
atm atm1483 export-subinterface-description	164
atm atm1483 mtu	165
atm atm1483 profile	166
atm atm1483 shutdown	167
atm atm1483 snmp trap link-status	168
atm atm1483 subscriber	169
atm auto-configuration	170
atm bulk-config	171
atm bulk-config modify	172
atm bulk-config shutdown	173
atm cac	174
atm cell-packing	175
atm-cell-mode	176
atm classifier-list	177
atm class-vc	178
atm clock internal	179
atm description	180
atm dos-protection-group	181
atm framing	182
atm ilmi-enable	183
atm ilmi-keepalive	184
atm lbo	185
atm mcpt-timers	186
atm oam	187
atm oam flush	188
atm oam loopback-location	189
atm policy	190
atm policy-list	191
atm pvc	192
atm shutdown	195
atm snmp trap link-status	196

	atm sonet stm-1 . . . . .	197
	atm uni-version . . . . .	198
	atm vc-per-vp . . . . .	199
	atm vp-description . . . . .	200
	atm-vp qos-parameter . . . . .	201
	atm-vp qos-profile . . . . .	202
	atm vp-tunnel . . . . .	203
	attributes (AAA) . . . . .	204
	attributes (RADIUS) . . . . .	205
	authentication . . . . .	206
	authentication key . . . . .	207
	authentication-key . . . . .	208
	authentication message-digest . . . . .	209
	authentication mode . . . . .	210
	authentication-none . . . . .	211
	authorization . . . . .	212
	authorization change . . . . .	213
	auth-router-name . . . . .	214
	auto-configure . . . . .	215
	auto-configure atm1483 . . . . .	216
	auto-configure vlan . . . . .	217
	auto-cost reference-bandwidth . . . . .	218
	automatic-virtual-link . . . . .	219
	auto-summary . . . . .	220
	average-length-exponent . . . . .	221
	avp . . . . .	222
<b>Chapter 3</b>	<b>B Commands . . . . .</b>	<b>223</b>
	backup-address-pool-name . . . . .	224
	bandwidth . . . . .	225
	bandwidth oversubscription . . . . .	226
	banner . . . . .	227
	baseline aaa . . . . .	228
	baseline aaa route-download . . . . .	229
	baseline atm vp interface . . . . .	230
	baseline bridge . . . . .	231
	baseline bridge interface . . . . .	232
	baseline bridge interface vpls . . . . .	233
	baseline clns . . . . .	234
	baseline cops . . . . .	235
	baseline dhcp . . . . .	236
	baseline frame-relay interface . . . . .	237
	baseline frame-relay multilinkinterface . . . . .	238
	baseline hdlc interface . . . . .	239
	baseline interface . . . . .	240
	baseline ip . . . . .	241
	baseline ip bgp . . . . .	242
	baseline ip dhcp-external . . . . .	243
	baseline ip dhcp-local . . . . .	244

baseline ip dvmrp . . . . .	245
baseline ip http . . . . .	246
baseline ip igmp . . . . .	247
baseline ip igmp-proxy interface . . . . .	248
baseline ip interface . . . . .	249
baseline ip mobile home-agent . . . . .	250
baseline ip nat . . . . .	251
baseline ip ospf . . . . .	252
baseline ip rip . . . . .	253
baseline ip tunnel-reassembly . . . . .	254
baseline ip udp . . . . .	255
baseline ip vrrp . . . . .	256
baseline ipv6 . . . . .	257
baseline ipv6 dhcpv6-local . . . . .	258
baseline ipv6 interface . . . . .	259
baseline ipv6 local ndra-pool . . . . .	260
baseline ipv6 local pool . . . . .	261
baseline ipv6 mld . . . . .	262
baseline ipv6 mld-proxy interface . . . . .	263
baseline ipv6 ospf . . . . .	264
baseline ipv6 tcp . . . . .	265
baseline line interface sonet . . . . .	266
baseline local pool . . . . .	267
baseline log . . . . .	268
baseline mpls interface . . . . .	269
baseline mpls label . . . . .	270
baseline mpls next-hop . . . . .	271
baseline mpls tunnel . . . . .	272
baseline path interface sonet . . . . .	273
baseline ppp interface . . . . .	274
baseline pppoe interface . . . . .	275
baseline radius . . . . .	276
baseline radius dynamic-request . . . . .	277
baseline radius relay . . . . .	278
baseline section interface sonet . . . . .	279
baseline show-delta-counts . . . . .	280
baseline snmp . . . . .	281
baseline ssc . . . . .	282
baseline suspicious-control-flow-detection counts . . . . .	283
baseline tacacs . . . . .	284
baseline tcp . . . . .	285
bert . . . . .	286
bfd adapt . . . . .	287
bgp advertise-best-external-to-internal . . . . .	288
bgp advertise-inactive . . . . .	289
bgp always-compare-med . . . . .	290
bgp bestpath med confed . . . . .	291
bgp bestpath missing-as-worst . . . . .	292
bgp client-to-client reflection . . . . .	293

bgp cluster-id . . . . .	294
bgp confederation identifier . . . . .	295
bgp confederation peers . . . . .	296
bgp dampening . . . . .	297
bgp default ipv4-unicast . . . . .	298
bgp default local-preference . . . . .	299
bgp default route-target filter . . . . .	300
bgp enforce-first-as . . . . .	301
bgp fast-external-fallover . . . . .	302
bgp graceful-restart . . . . .	303
bgp graceful-restart path-selection-defer-time-limit . . . . .	304
bgp graceful-restart restart-time . . . . .	305
bgp graceful-restart stalepaths-time . . . . .	306
bgp log-neighbor-changes . . . . .	307
bgp maxas-limit . . . . .	308
bgp redistribute-internal . . . . .	309
bgp router-id . . . . .	310
bgp shutdown . . . . .	311
bgp wait-on-end-of-rib . . . . .	312
boolean-test . . . . .	313
boot backup . . . . .	314
boot config . . . . .	315
boot force-backup . . . . .	316
boot hotfix . . . . .	317
boot revert-tolerance . . . . .	318
boot revert-tolerance never . . . . .	319
boot subsystem . . . . .	320
boot system . . . . .	321
bridge1483 dos-protection-group . . . . .	322
bridge1483 mtu . . . . .	323
bridge1483 service-profile . . . . .	324
bridge . . . . .	325
bridge acquire . . . . .	326
bridge address . . . . .	327
bridge aging-time . . . . .	329
bridge crb . . . . .	330
bridge-group . . . . .	331
bridge learn . . . . .	332
bridge route . . . . .	333
bridge snmp-trap link-status . . . . .	334
bridge subscriber-policy . . . . .	335
bridge vpls rd . . . . .	336
bridge vpls route-target . . . . .	337
bridge vpls site-name site-id . . . . .	339
bridge vpls site-range . . . . .	340
bridge vpls transport-virtual-router . . . . .	341
broadcast . . . . .	342
buffer-weight . . . . .	343
bulkstats . . . . .	344

**Chapter 4**

bulkstats collector .....	345
bulkstats file-format endOfLine-LF .....	346
bulkstats interfaces description-format common .....	347
bulkstats interfaces rfc1213 .....	348
bulkstats interface-type .....	349
bulkstats receiver remote-name .....	350
bulkstats schema .....	351
bulkstats schema subtree .....	352
bulkstats schema subtree policy .....	353
bulkstats schema subtree qos .....	354
bulkstats traps .....	356
bulkstats virtual-router-group .....	357
bundled-group-id .....	358
bundled-group-id-overrides-mlppp-ed .....	359
<b>C Commands .....</b>	<b>361</b>
cablelength .....	362
cache entries .....	363
cache timeout .....	364
cbr .....	365
channelized .....	366
check-disk .....	367
check-vpn-next-hops .....	368
classifier-group .....	369
class-int .....	370
class-vc .....	371
cleanup-timeout-factor .....	372
clear access-list .....	373
clear arp .....	374
clear bfd adapted-intervals .....	375
clear bfd session .....	376
clear bgp ipv6 .....	377
clear bgp ipv6 dampening .....	378
clear bgp ipv6 dynamic-peers .....	380
clear bgp ipv6 redistribution .....	381
clear bgp ipv6 wait-end-of-rib .....	382
clear bridge .....	383
clear bridge address .....	384
clear bridge interface .....	385
clear bridge interface vpls .....	386
clear egress-queue .....	387
clear fabric-queue .....	388
clear ip bgp .....	389
clear ip bgp dampening .....	391
clear ip bgp dynamic-peers .....	393
clear ip bgp redistribution .....	394
clear ip bgp wait-end-of-rib .....	395
clear ip demux .....	396
clear ip dhcp-local binding .....	397



clear ip dvmrp routes . . . . .	398
clear ip flow stats . . . . .	399
clear ip interface . . . . .	400
clear ip isis redistribution . . . . .	401
clear ip mobile binding . . . . .	402
clear ip mroute . . . . .	403
clear ip nat translation . . . . .	404
clear ip ospf database . . . . .	406
clear ip ospf neighbor . . . . .	407
clear ip ospf redistribution . . . . .	408
clear ip pim auto-rp . . . . .	409
clear ip pim interface count . . . . .	410
clear ip pim remote-neighbor count . . . . .	411
clear ip prefix-list . . . . .	412
clear ip prefix-tree . . . . .	413
clear ip rip dynamic-interfaces . . . . .	414
clear ip rip redistribution . . . . .	415
clear ip routes . . . . .	416
clear ip routes download . . . . .	417
clear ip tunnel-routes . . . . .	418
clear ipv6 access-list . . . . .	419
clear ipv6 bfd session . . . . .	420
clear ipv6 interface . . . . .	421
clear ipv6 mroute . . . . .	422
clear ipv6 neighbors . . . . .	423
clear ipv6 ospf counters . . . . .	424
clear ipv6 ospf process . . . . .	425
clear ipv6 ospf redistribution . . . . .	426
clear ipv6 pim interface . . . . .	427
clear ipv6 pim remote-neighbor . . . . .	428
clear ipv6 prefix-list . . . . .	429
clear ipv6 routes . . . . .	430
clear ipv6 routes download . . . . .	431
clear ipv6 tunnel-routes . . . . .	432
clear isis adjacency . . . . .	433
clear isis database . . . . .	434
clear isis ipv6 redistribution . . . . .	435
clear l2c discovery-table . . . . .	436
clear l2c neighbor . . . . .	437
clear line . . . . .	438
clear mirror log . . . . .	439
clear mpls dynamic-interfaces on-major-interfaces . . . . .	440
clear mpls ldp . . . . .	441
clear redundancy history . . . . .	442
clear rsvp authentication . . . . .	443
clear suspicious-control-flow-detection . . . . .	444
client-name . . . . .	445
clns configuration-time . . . . .	446
clns holding-time . . . . .	447

clns host	448
clock set	449
clock source	450
clock summer-time date	451
clock summer-time recurring	452
clock timezone	453
color	454
color-aware	455
color-mark-profile	456
committed-action	457
committed-burst	458
committed-drop-threshold	459
committed-length	460
committed-rate	461
committed-threshold	462
common-name	463
configure	464
confirmations explicit	465
conformed-action	466
conformed-drop-threshold	467
conformed-fraction	468
conformed-length	469
conformed-threshold	470
control-plane	471
controlled-interface-type	472
controller e3	473
controller sonet	474
controller t3	475
convergence-factor	476
copy	477
copy running-configuration	479
copy running-configuration startup-configuration	480
copy startup-configuration	481
cost	482
country	483
crc	484
crl	485
crypto key dss	486
<b>Chapter 5 D Commands</b>	<b>487</b>
data-character-bits	488
dead-interval	489
deadtime	490
debounce	491
debounce-interval	492
debounce-time	493
debug ip bgp	494
debug ip mbgp	496
debug ip ospf	498

debug ip pim	500
debug ip rip	502
debug ipv6 ospf	503
debug ipv6 pim	505
debug isis	507
default-fields peer	509
default-fields route	511
default-information originate	513
default-metric	515
default-router	516
default-upper-type mlppp	517
delete	518
delta-sampling	519
deny	520
description	521
dhcp delete-binding	522
dhcp-external delete-binding	525
dhcp-external duplicate-mac-address	526
dhcpv6 delete-binding	527
diag	528
diag-level	529
dir	530
disable	531
disable-autosync	532
disable-dynamic-redistribute	533
disable-incremental-external-spf	534
disable proxy lcp	535
disable-switch-on-error	536
disconnect-cause	537
disconnect ssh	538
discovery-mode	539
distance	540
distance bgp	541
distance ip	542
distribute-domain-wide	543
distribute-list	544
dns-domain-search	545
dns-server	546
dns-server (for IPv6)	547
do	548
domain	549
domain-authentication	550
domain-authentication-key	551
domain-id	552
domain-message-digest-key	553
domain-name	555
domain-suffix	556
domain-tag	557
dont-install-routes	558

## Chapter 6

dos-protection-group .....	559
drop-profile .....	560
ds3-scramble .....	561
dsr-detect .....	562
dsu bandwidth .....	563
dsu mode .....	564
duplex .....	565
dvmrp destination profile .....	566
<b>E Commands .....</b>	<b>567</b>
e3-scramble .....	568
enable .....	569
enable-frag-stats .....	570
enabled .....	571
enable ipsec-transport .....	572
enable password .....	573
enable proxy authenticate .....	574
enable secret .....	575
encapsulation .....	576
encapsulation bridge1483 .....	577
encapsulation frame-relay ietf .....	578
encapsulation hdlc .....	579
encapsulation mlframe-relay ietf .....	580
encapsulation mlppp .....	581
encapsulation ppp .....	582
encapsulation pppoe .....	583
encapsulation vlan .....	584
encryption .....	585
end .....	586
enrollment retry-limit .....	587
enrollment retry-period .....	588
enrollment url .....	589
equipment loopback .....	590
erase secrets .....	591
ethernet description .....	592
ethernet dos-protection-group .....	593
ethernet oam lfm .....	594
ethernet oam lfm high-threshold .....	595
ethernet oam lfm link-monitor frame-seconds .....	596
ethernet oam lfm link-monitor frame-seconds-summary .....	598
ethernet oam lfm link-monitor symbol-period .....	600
ethernet oam lfm mode .....	602
ethernet oam lfm pdu-lost-threshold .....	603
ethernet oam lfm pdu-transmit-interval .....	604
ethernet oam lfm remote-failure .....	605
ethernet oam lfm remote-loopback .....	606
ethernet oam lfm remote-loopback supported .....	607
event .....	608
exceeded-action .....	609

exceeded-drop-threshold	610
exceeded-fraction	611
exceeded-length	612
exceeded-threshold	613
exception dump	614
exception gateway	615
exception http-redirect	616
exception monitor	617
exception monitor interval	618
exception protocol ftp	619
exception source	620
excess-burst	621
exclude-ndraprefix	622
exclude-prefix	623
exclude-subsystem	624
exec-banner	625
exec-timeout	626
existence-test	627
exit	628
exit-address-family	629
exit-remote-neighbor	630
exp-mask	631
export destination	632
export map	633
export source	634
extended-authentication	635
external-paths	636
<b>Chapter 7</b>	
<b>F Commands</b>	<b>637</b>
fabric-strict-priority	638
fabric-weight	639
fabric weights	640
failover-resync	641
filter	642
flash-disk compare	643
flash-disk duplicate	644
flash-disk initialize	645
flash-disk scan	646
forward	647
forward interface	648
forward next-hop	649
forwarding-rate-threshold	650
forwarding-table route-holddown	651
frame-relay class	652
frame-relay classifier-list	653
frame-relay description	654
frame-relay dos-protection-group	655
frame-relay fragment	656
frame-relay interface-dlci ietf	657

	frame-relay intf-type . . . . .	658
	frame-relay keepalive . . . . .	659
	frame-relay lmi-n391dte . . . . .	660
	frame-relay lmi-n392dce . . . . .	661
	frame-relay lmi-n392dte . . . . .	662
	frame-relay lmi-n393dce . . . . .	663
	frame-relay lmi-n393dte . . . . .	664
	frame-relay lmi-t391dte . . . . .	665
	frame-relay lmi-t392dce . . . . .	666
	frame-relay lmi-type . . . . .	667
	frame-relay policy . . . . .	668
	frame-relay policy-list . . . . .	669
	framing . . . . .	670
	frequency . . . . .	671
	ftp-server enable . . . . .	672
	ftp-server flush . . . . .	673
	full-spf-always . . . . .	674
<b>Chapter 8</b>	<b>G Commands . . . . .</b>	<b>675</b>
	global export map . . . . .	676
	global import map . . . . .	677
	graceful-restart . . . . .	678
	graceful-restart helper . . . . .	679
	graceful-restart helper-abort-topology-change . . . . .	680
	graceful-restart notify-time . . . . .	681
	graceful-restart restart-time . . . . .	682
	grace-period . . . . .	683
	gre destination profile . . . . .	684
	green-mark . . . . .	685
	gre-tunnel classifier-list . . . . .	686
	gre-tunnel policy . . . . .	687
	gre-tunnel policy-list . . . . .	688
	group . . . . .	689
	gsmp-syn-timeout . . . . .	690
<b>Chapter 9</b>	<b>H Commands . . . . .</b>	<b>691</b>
	halt . . . . .	692
	hash . . . . .	693
	hdlc dos-protection-group . . . . .	694
	hdlc down-when-looped . . . . .	695
	hdlc keepalive . . . . .	696
	hdlc shutdown . . . . .	697
	hello hold-time . . . . .	698
	hello interval . . . . .	699
	hello-interval . . . . .	700
	help . . . . .	701
	hops-of-statistics-kept . . . . .	702
	host . . . . .	703
	hostname . . . . .	704
	hotfix activate . . . . .	705

<b>Chapter 10</b>	<b>I Commands</b>	<b>707</b>
	id	708
	identification	709
	idle-character	710
	igmp disable	711
	igmp promiscuous	712
	ignore-attached-bit	713
	ignore-lsp-errors	714
	ike cri	715
	ike local-identity	716
	ike peer-identity distinguished-name	717
	ike peer-identity domain-name	718
	ike peer-identity ip address	719
	ike peer-identity username	720
	import map	721
	inarp	722
	include circuit-identifier	723
	include dhcp-option 82	724
	include hostname	725
	include ip-address	726
	include mac-address	727
	include virtual-router-name	728
	index	729
	instance-interface-type	730
	interface	731
	interface atm	732
	interface-event-disable	733
	interface fastEthernet	734
	interface gigabitEthernet	735
	interface ip	736
	interface ipv6	737
	interface lag	738
	interface loopback	739
	interface mframe-relay	740
	interface mppp	741
	interface null	742
	interface pos	743
	interface serial	744
	interface tenGigabitEthernet	745
	interface tunnel	746
	invert data	747
	ip	748
	ip access-routes	749
	ip access-route table-map	750
	ip address	751
	ip-address	752
	ip address-pool	753
	ip-address-pool	754
	ip address virtual-router	755

ip alwaysup	756
ip analyzer	757
ip as-path access-list	758
ip atm-vc	760
ip auto-configure append-virtual-router-name	761
ip auto-configure ip-subscriber	762
ip auto-detect ip-subscriber	763
ip bgp-community new-format	764
ip bgp-confed-as-set new-format	765
ip block-multicast-sources	766
ip broadcast-address	767
ip classifier-list	768
ip community-list	771
ip debounce-time	772
ip demux-type da-prefix	773
ip description	774
ip destination-prefix	775
ip dhcp-capture	776
ip dhcp-external auto-configure	777
ip dhcp-external disregard-giaddr-next-hop	778
ip dhcp-external recreate-subscriber-interface	779
ip dhcp-external server-address	780
ip dhcp-external server-sync	781
ip dhcp-local auth domain	782
ip dhcp-local auth include	783
ip dhcp-local auth password	784
ip dhcp-local auth user-prefix	785
ip dhcp-local auto-configure agent-circuit-identifier	786
ip dhcp-local cable-modem	787
ip dhcp-local excluded-address	788
ip dhcp-local limit	789
ip dhcp-local pool	790
ip dhcp-local snmpTraps	791
ip dhcp-local unique-client-ids	792
ip dhcp-server	793
ip directed-broadcast	794
ip disable-forwarding	795
ip domain-lookup	796
ip domain-name	797
ip dos-protection-group	798
ip dvmrp	799
ip dvmrp accept-filter	800
ip dvmrp announce-filter	801
ip dvmrp auto-summary	802
ip dvmrp disable	803
ip dvmrp metric-offset	804
ip dvmrp route-hog-notification	805
ip dvmrp route-limit	806
ip dvmrp summary-address	807



ip dvmrp unicast-routing . . . . .	808
ip dynamic-interface-prefix . . . . .	809
ip explicit-path . . . . .	810
ip extcommunity-list . . . . .	811
ip fallback global . . . . .	812
ip filter-options all . . . . .	813
ip flow-aggregation cache . . . . .	814
ip flow-cache entries . . . . .	815
ip flow-cache timeout . . . . .	816
ip flow-export . . . . .	817
ip flow-sampling-mode packet-interval . . . . .	818
ip flow statistics . . . . .	819
ip ftp source-address . . . . .	820
ip ftp source-interface . . . . .	821
ip gratuitous-arps . . . . .	822
ip-hint . . . . .	823
ip http . . . . .	824
ip http access-class . . . . .	825
ip http max-connection-time . . . . .	826
ip http port . . . . .	827
ip http redirectUrl . . . . .	828
ip http same-host-limit . . . . .	829
ip http server . . . . .	830
ip icmp update-source . . . . .	831
ip igmp . . . . .	832
ip igmp access-group . . . . .	833
ip igmp access-source-group . . . . .	834
ip igmp apply-oif-map . . . . .	835
ip igmp explicit-tracking . . . . .	836
ip igmp group limit . . . . .	837
ip igmp immediate-leave . . . . .	838
ip igmp last-member-query-interval . . . . .	839
ip igmp oif-map . . . . .	840
ip igmp promiscuous . . . . .	841
ip igmp-proxy . . . . .	842
ip igmp-proxy unsolicited-report-interval . . . . .	843
ip igmp-proxy V1-router-present-time . . . . .	844
ip igmp querier . . . . .	845
ip igmp querier-timeout . . . . .	846
ip igmp query-interval . . . . .	847
ip igmp query-max-response-time . . . . .	848
ip igmp robustness . . . . .	849
ip igmp ssm-map enable . . . . .	850
ip igmp ssm-map static . . . . .	851
ip igmp static-exclude . . . . .	852
ip igmp static-group . . . . .	853
ip igmp static-include . . . . .	854
ip igmp version . . . . .	855
ip ignore-df-bit . . . . .	856

ip inactivity-timer . . . . .	857
ip initial-sequence-preference . . . . .	858
ip interface . . . . .	859
ip irdp . . . . .	860
ip local alias . . . . .	861
ip local pool . . . . .	862
ip local pool snmpTrap . . . . .	863
ip local pool warning . . . . .	864
ip local shared-pool . . . . .	865
ip mac-validate . . . . .	866
ip mask-reply . . . . .	867
ip match-policy-list . . . . .	868
ip mirror . . . . .	869
ip mobile home-agent . . . . .	870
ip mobile host . . . . .	871
ip mobile profile . . . . .	872
ip mobile secure foreign-agent . . . . .	873
ip mobile secure host . . . . .	874
ip mpls forwarding-mode label-switched . . . . .	876
ip mtu . . . . .	877
ip multicast admission-bandwidth-limit . . . . .	878
ip multicast ioa-packet-replication . . . . .	879
ip multicast-routing . . . . .	880
ip multicast-routing bandwidth-map . . . . .	881
ip multicast-routing disable-rpf-check . . . . .	882
ip multicast-routing permanent-mroute . . . . .	883
ip multipath round-robin . . . . .	884
ip name-server . . . . .	885
ip nat . . . . .	886
ip nat inside source list . . . . .	887
ip nat inside source static . . . . .	888
ip nat outside source list . . . . .	889
ip nat outside source static . . . . .	890
ip nat pool . . . . .	891
ip nat translation . . . . .	892
ip nat translation max-entries . . . . .	893
ip nfs . . . . .	894
ip nfs host . . . . .	895
ip ospf authentication-key . . . . .	896
ip ospf authentication message-digest . . . . .	897
ip ospf authentication-none . . . . .	898
ip ospf bfd-liveness-detection . . . . .	899
ip ospf cost . . . . .	900
ip ospf dead-interval . . . . .	901
ip ospf hello-interval . . . . .	902
ip ospf message-digest-key md5 . . . . .	903
ip ospf network . . . . .	904
ip ospf priority . . . . .	905
ip ospf retransmit-interval . . . . .	906

ip ospf shutdown . . . . .	907
ip ospf transmit-delay . . . . .	908
ip pim . . . . .	909
ip pim bfd-liveness-detection . . . . .	910
ip pim bsr-candidate . . . . .	911
ip pim data-mdt . . . . .	912
ip pim dr-priority . . . . .	913
ip pim group-address-pool . . . . .	914
ip pim join-filter . . . . .	915
ip pim join-prune-interval . . . . .	916
ip pim query-interval . . . . .	917
ip pim rp-address . . . . .	918
ip pim rp-candidate . . . . .	919
ip pim send-rp-announce . . . . .	920
ip pim send-rp-discovery scope . . . . .	921
ip pim sparse-mode graceful-restart-duration . . . . .	922
ip pim spt-threshold . . . . .	923
ip pim ssm . . . . .	924
ip policy . . . . .	925
ip policy-list . . . . .	927
ip policy-parameter hierarchical . . . . .	928
ip policy-parameter reference-rate . . . . .	929
ip prefix-list . . . . .	930
ip prefix-tree . . . . .	931
ip profile . . . . .	932
ip proxy-arp . . . . .	933
ip re-authenticate-auto-detect ip-subscriber . . . . .	934
ip redirects . . . . .	935
ip refresh-route . . . . .	936
ip rip . . . . .	937
ip rip authentication key . . . . .	938
ip rip authentication mode . . . . .	939
ip rip bfd-liveness-detection . . . . .	940
ip rip copy-to-dynamic . . . . .	941
ip rip receive version . . . . .	942
ip rip send version . . . . .	943
ip route . . . . .	944
ip route-cache flow sampled . . . . .	946
ip route-map ip-subscriber . . . . .	947
ip route-type . . . . .	948
ip router-id . . . . .	949
ip router isis . . . . .	950
ip-router-name . . . . .	951
ip rpf-route . . . . .	952
ip rsvp authentication . . . . .	953
ip rsvp authentication key . . . . .	954
ip rsvp bandwidth . . . . .	955
ip rsvp bfd-liveness-detection . . . . .	956
ip rsvp signalling hello . . . . .	957

ip sa-validate . . . . .	958
ip sa-validate trap-enable . . . . .	959
ip service-profile . . . . .	960
ip share-interface . . . . .	961
ip share-nexthop . . . . .	962
ip shutdown . . . . .	963
ip source-prefix . . . . .	964
ip source-route . . . . .	965
ip speed . . . . .	966
ip split-horizon . . . . .	967
ip ssh authentication-retries . . . . .	968
ip ssh crypto . . . . .	969
ip ssh disable-user-authentication . . . . .	970
ip ssh mac . . . . .	971
ip ssh sleep . . . . .	972
ip ssh timeout . . . . .	973
ip ssh user-authentication-protocol . . . . .	974
ip static-route table-map . . . . .	975
ip summary-address . . . . .	976
ip tcp ack-rst-and-syn . . . . .	977
ip tcp adjust-mss . . . . .	978
ip ttl . . . . .	979
ip tunnel reassembly . . . . .	980
ip unnumbered . . . . .	981
ip unreachable . . . . .	982
ip use-framed-routes ip-subscriber . . . . .	983
ip virtual-router . . . . .	984
ip vrf . . . . .	985
ip vrf forwarding . . . . .	986
ip vrrp . . . . .	987
ip vrrp accept-data . . . . .	988
ip vrrp advertise-interval . . . . .	989
ip vrrp authentication-key . . . . .	990
ip vrrp authentication-type . . . . .	991
ip vrrp enable . . . . .	992
ip vrrp icr-partition . . . . .	993
ip vrrp icr-partition group . . . . .	994
ip vrrp icr-partition svlan-list . . . . .	995
ip vrrp icr-partition svlan-list explicit . . . . .	996
ip vrrp icr-partition svlan-range . . . . .	997
ip vrrp icr-partition vlan-list . . . . .	999
ip vrrp icr-partition vlan-range . . . . .	1000
ip vrrp preempt . . . . .	1002
ip vrrp priority . . . . .	1003
ip vrrp timers-learn . . . . .	1004
ip vrrp track . . . . .	1005
ip vrrp virtual-address . . . . .	1006
ipsec ca authenticate . . . . .	1007
ipsec ca enroll . . . . .	1008

ipsec ca identity . . . . .	1009
ipsec certificate-database refresh . . . . .	1010
ipsec certificate-request generate . . . . .	1011
ipsec clear sa . . . . .	1012
ipsec crt . . . . .	1013
ipsec identity . . . . .	1014
ipsec ike-policy-rule . . . . .	1015
ipsec isakmp-policy-rule . . . . .	1016
ipsec key generate . . . . .	1017
ipsec key manual pre-share . . . . .	1018
ipsec key pubkey-chain rsa . . . . .	1019
ipsec key zeroize . . . . .	1020
ipsec lifetime . . . . .	1021
ipsec local-endpoint . . . . .	1022
ipsec option dpd . . . . .	1023
ipsec option nat-t . . . . .	1024
ipsec option tx-invalid-cookie . . . . .	1025
ipsec transform-set . . . . .	1026
ipsec transport profile . . . . .	1027
ipsec tunnel profile . . . . .	1028
ipv6 . . . . .	1029
ipv6 access-list . . . . .	1030
ipv6 access-route table-map . . . . .	1031
ipv6 address . . . . .	1032
ipv6 address-pool local . . . . .	1033
ipv6 address-pool ndra . . . . .	1034
ipv6 block-multicast-sources . . . . .	1035
ipv6 classifier-list . . . . .	1036
ipv6 description . . . . .	1038
ipv6 dhcpv6-local auth domain . . . . .	1039
ipv6 dhcpv6-local auth include . . . . .	1040
ipv6 dhcpv6-local auth password . . . . .	1041
ipv6 dhcpv6-local auth user-prefix . . . . .	1042
ipv6 dhcpv6-local delegated-prefix . . . . .	1043
ipv6 dhcpv6-local dns-domain-search . . . . .	1044
ipv6 dhcpv6-local dns-server . . . . .	1045
ipv6 dhcpv6-local duid-type . . . . .	1046
ipv6 dhcpv6-local prefix-lifetime . . . . .	1047
ipv6 dos-protection-group . . . . .	1048
ipv6 enable . . . . .	1049
ipv6 hop-limit . . . . .	1050
ipv6 http . . . . .	1051
ipv6 http port . . . . .	1052
ipv6 http redirectUrl . . . . .	1053
ipv6 http server . . . . .	1054
ipv6 initial-sequence-preference . . . . .	1055
ipv6-local-interface . . . . .	1056
ipv6 local ndra-pool . . . . .	1057
ipv6 local pool . . . . .	1058

ipv6 mld	1059
ipv6 mld access-group	1060
ipv6 mld access-source-group	1061
ipv6 mld apply-oif-map	1062
ipv6 mld explicit-tracking	1063
ipv6 mld group limit	1064
ipv6 mld immediate-leave	1065
ipv6 mld last-member-query-interval	1066
ipv6 mld oif-map	1067
ipv6 mld-proxy	1068
ipv6 mld-proxy unsolicited-report-interval	1069
ipv6 mld-proxy version	1070
ipv6 mld querier-timeout	1071
ipv6 mld query-interval	1072
ipv6 mld query-max-response-time	1073
ipv6 mld robustness	1074
ipv6 mld ssm-map enable	1075
ipv6 mld ssm-map static	1076
ipv6 mld static-exclude	1077
ipv6 mld static-group	1078
ipv6 mld static-include	1079
ipv6 mld version	1080
ipv6 mtu	1081
ipv6 multicast admission-bandwidth-limit	1082
ipv6 multicast ioa-packet-replication	1083
ipv6 multicast-routing	1084
ipv6 multicast-routing bandwidth-map	1085
ipv6 multicast-routing disable-rpf-check	1086
ipv6 multicast-routing permanent-mroute	1087
ipv6 nd	1088
ipv6 nd active-solicitations	1089
ipv6 nd dad attempts	1090
ipv6 nd managed-config-flag	1091
ipv6 nd ns-interval	1092
ipv6 nd other-config-flag	1093
ipv6 nd prefix-advertisement	1094
ipv6 nd proxy	1095
ipv6 nd ra-interval	1096
ipv6 nd ra-lifetime	1097
ipv6-ndra-pool-name	1098
ipv6 nd reachable-time	1099
ipv6 nd suppress-ra	1100
ipv6 nd suppress-ra-source-link-layer	1101
ipv6 neighbor	1102
ipv6 ospf area	1103
ipv6 ospf bfd-liveness-detection	1104
ipv6 ospf cost	1105
ipv6 ospf dead-interval	1106
ipv6 ospf hello-interval	1107

ipv6 ospf mtu-ignore .....	1108
ipv6 ospf network .....	1109
ipv6 ospf priority .....	1110
ipv6 ospf retransmit-interval .....	1111
ipv6 ospf shutdown .....	1112
ipv6 ospf transmit-delay .....	1113
ipv6 pim bfd-liveness-detection .....	1114
ipv6 pim bsr-candidate .....	1115
ipv6 pim dr-priority .....	1116
ipv6 pim join-filter .....	1117
ipv6 pim join-prune-interval .....	1118
ipv6 pim query-interval .....	1119
ipv6 pim rp-address .....	1120
ipv6 pim rp-candidate .....	1121
ipv6 pim sparse-mode .....	1122
ipv6 pim sparse-mode graceful-restart-duration .....	1123
ipv6 pim spt-threshold .....	1124
ipv6 pim ssm .....	1125
ipv6 policy .....	1126
ipv6 policy-list .....	1128
ipv6 policy-parameter hierarchical .....	1129
ipv6 policy-parameter reference-rate .....	1130
ipv6 prefix-list .....	1131
ipv6-prefix-pool-name .....	1132
ipv6 route .....	1133
ipv6 router isis .....	1134
ipv6 router mld .....	1135
ipv6-router-name .....	1136
ipv6 router ospf .....	1137
ipv6 router pim .....	1138
ipv6 route-type .....	1139
ipv6 rpf-route .....	1140
ipv6 sa-validate .....	1141
ipv6 share-interface .....	1142
ipv6 static-route table-map .....	1143
ipv6 unnumbered .....	1144
ipv6 virtual-router .....	1145
isis authentication-key .....	1146
isis bfd-liveness-detection .....	1147
isis circuit-type .....	1148
isis csnp-interval .....	1149
isis hello-interval .....	1150
isis hello-multiplier .....	1151
isis hello padding .....	1152
isis lsp-interval .....	1153
isis mesh-group .....	1154
isis message-digest-key .....	1155
isis metric .....	1157
isis network point-to-point .....	1158

	isis priority . . . . .	1159
	isis retransmit-interval . . . . .	1160
	isis retransmit-throttle-interval . . . . .	1161
	isis tag . . . . .	1162
	issuer-identifier . . . . .	1163
	issu initialize . . . . .	1164
	issu start . . . . .	1165
	issu stop . . . . .	1166
	is-type . . . . .	1167
<b>Chapter 11</b>	<b>K Commands . . . . .</b>	<b>1169</b>
	key . . . . .	1170
	key-string . . . . .	1172
<b>Chapter 12</b>	<b>L Commands . . . . .</b>	<b>1173</b>
	l2c . . . . .	1174
	l2c end-user-id . . . . .	1175
	l2c ip listen . . . . .	1176
	l2c ip oif . . . . .	1177
	l2c line-configuration . . . . .	1178
	l2c max-branches . . . . .	1179
	l2c oam . . . . .	1180
	l2c peer-attachment-id . . . . .	1181
	l2tp checksum . . . . .	1182
	l2tp classifier-list . . . . .	1183
	l2tp destination lockout-test . . . . .	1184
	l2tp destination lockout-timeout . . . . .	1185
	l2tp destination profile . . . . .	1186
	l2tp destruct-timeout . . . . .	1187
	l2tp dial-out connecting-timer-value . . . . .	1188
	l2tp dial-out dormant-timer-value . . . . .	1189
	l2tp dial-out max-buffered-triggers . . . . .	1190
	l2tp dial-out session delete . . . . .	1191
	l2tp dial-out session reset . . . . .	1192
	l2tp dial-out target . . . . .	1193
	l2tp disable calling-number-avp . . . . .	1194
	l2tp disable challenge . . . . .	1195
	l2tp disconnect-cause . . . . .	1196
	l2tp drain . . . . .	1197
	l2tp drain destination . . . . .	1198
	l2tp drain tunnel . . . . .	1199
	l2tp failover-resync . . . . .	1200
	l2tp fail-over-within-preference . . . . .	1201
	l2tp ignore-receive-data-sequencing . . . . .	1202
	l2tp ignore-transmit-address-change . . . . .	1203
	l2tp policy . . . . .	1204
	l2tp policy-list . . . . .	1205
	l2tp policy-parameter hierarchical . . . . .	1206
	l2tp policy-parameter reference-rate . . . . .	1207
	l2tp reject-transmit-address-change . . . . .	1208



l2tp retransmission . . . . .	1209
l2tp rx-connect-speed-when-equal . . . . .	1210
l2tp shutdown . . . . .	1211
l2tp shutdown destination . . . . .	1212
l2tp shutdown session . . . . .	1213
l2tp shutdown tunnel . . . . .	1214
l2tp switch-profile . . . . .	1215
l2tp tunnel default-receive-window . . . . .	1216
l2tp tunnel idle-timeout . . . . .	1217
l2tp tunnel short-drain-timeout . . . . .	1218
l2tp tunnel-switching . . . . .	1219
l2tp tunnel test . . . . .	1220
l2tp unlock destination . . . . .	1221
l2tp unlock-test destination . . . . .	1222
l2tp weighted-load-balancing . . . . .	1223
l2vpn control-word . . . . .	1224
l2vpn encapsulation-type . . . . .	1225
l2vpn local-site-id remote-site-id . . . . .	1226
l2vpn rd . . . . .	1227
l2vpn route-target . . . . .	1228
l2vpn sequencing . . . . .	1229
l2vpn site-name site-id . . . . .	1230
l2vpn site-range . . . . .	1231
lACP . . . . .	1232
lACP port-priority . . . . .	1233
lag dos-protection-group . . . . .	1234
lease . . . . .	1235
license bfd . . . . .	1236
license b-ras . . . . .	1237
license ipsec-tunnels . . . . .	1238
license ipv6 . . . . .	1239
license issu . . . . .	1240
license l2tp-session . . . . .	1241
license mobile-ip home-agent . . . . .	1242
license nat . . . . .	1243
license service-management . . . . .	1244
lifetime . . . . .	1245
line . . . . .	1247
line-card switch . . . . .	1248
link . . . . .	1249
link failover arp-flush . . . . .	1250
link failover force . . . . .	1251
link failover timeout . . . . .	1252
link selection . . . . .	1253
list . . . . .	1254
load-interval . . . . .	1255
load-rebalance . . . . .	1256
local host . . . . .	1257
local-interface . . . . .	1258

	local ip address . . . . .	1259
	local ip identity . . . . .	1261
	local ip network . . . . .	1262
	log . . . . .	1263
	log-adjacency-changes . . . . .	1264
	log destination . . . . .	1265
	log destination syslog source . . . . .	1267
	log engineering . . . . .	1268
	log fields . . . . .	1269
	log filters . . . . .	1270
	log here . . . . .	1271
	log severity . . . . .	1272
	log unlimit . . . . .	1274
	log verbosity . . . . .	1275
	login . . . . .	1276
	login authentication . . . . .	1277
	logout subscribers . . . . .	1278
	loopback . . . . .	1279
	lsp-gen-interval . . . . .	1281
	lsp-mtu . . . . .	1282
	lsp-refresh-interval . . . . .	1283
<b>Chapter 13</b>	<b>M Commands . . . . .</b>	<b>1285</b>
	macro . . . . .	1286
	map-class frame-relay . . . . .	1287
	map-group . . . . .	1288
	map-list . . . . .	1289
	mark . . . . .	1290
	mark-clp . . . . .	1292
	mark-de . . . . .	1293
	mark-exp . . . . .	1294
	mark-user-priority . . . . .	1295
	mask destination . . . . .	1296
	masked-key . . . . .	1297
	mask source . . . . .	1298
	mask-val . . . . .	1299
	match as-path . . . . .	1300
	match community . . . . .	1301
	match distance . . . . .	1302
	match extcommunity . . . . .	1303
	match ip address . . . . .	1304
	match ip next-hop . . . . .	1305
	match ipv6 address . . . . .	1306
	match ipv6 next-hop . . . . .	1307
	match ipv6 route-source . . . . .	1308
	match level . . . . .	1309
	match metric . . . . .	1310
	match metric-type . . . . .	1311
	match mpls-label . . . . .	1312

match policy-list	1313
match route-type	1314
match-set summary prefix-tree	1315
match tag	1316
max aci-svs per-pvs	1317
max-branches	1318
max-discovery-table-entries	1319
maximum-paths	1320
maximum routes	1321
maximum-voql	1322
max-interfaces	1323
max-lsp-lifetime	1324
max-response-failure	1325
max-sessions	1326
mdl carrier	1327
mdl string	1328
mdl transmit	1329
mdt-data-delay	1330
mdt-data-holddown	1331
mdt-data-timeout	1332
mdt-interval	1333
medium ipv4	1334
member interface	1335
member-interface	1336
member-interface-type	1337
memory	1338
message-digest-key md5	1339
metric	1340
metric-style narrow	1341
metric-style transition	1342
metric-style wide	1343
minimum-dynamic-rate-percent	1344
minimum-links	1345
mirror	1346
mirror analyzer-ip-address	1348
mirror disable	1349
mirror-enable	1351
mirror trap-enable	1352
mld disable	1353
mode	1354
monitor atm vc	1355
monitor atm vp	1356
monitor vlan interface	1357
more	1358
motd-banner	1359
mount	1360
mpls	1361
mpls atm vci range	1363
mpls atm vpi range	1364

mpls backup-path . . . . .	1365
mpls bandwidth . . . . .	1366
mpls classifier-list . . . . .	1367
mpls copy-upc-to-exp . . . . .	1368
mpls create-dynamic-interfaces . . . . .	1369
mpls diff-serv phb-id traffic-class . . . . .	1370
mpls disable . . . . .	1371
mpls explicit-path . . . . .	1372
mpls ip propagate-ttl . . . . .	1373
mpls l2transport load-balancing-group . . . . .	1374
mpls ldp . . . . .	1376
mpls ldp advertise-labels . . . . .	1377
mpls ldp autoconfig . . . . .	1378
mpls ldp deaggregate . . . . .	1379
mpls ldp disable . . . . .	1380
mpls ldp discovery transport-address . . . . .	1381
mpls ldp egress-label . . . . .	1382
mpls ldp graceful-restart . . . . .	1383
mpls ldp graceful-restart reconnect-time . . . . .	1384
mpls ldp graceful-restart recovery-time . . . . .	1385
mpls ldp graceful-restart timers max-recovery . . . . .	1386
mpls ldp graceful-restart timers neighbor-liveness . . . . .	1387
mpls ldp igp sync holddown . . . . .	1388
mpls ldp independent-control . . . . .	1389
mpls ldp ip-forwarding . . . . .	1390
mpls ldp link-hello disable . . . . .	1391
mpls ldp neighbor password . . . . .	1392
mpls ldp profile . . . . .	1393
mpls ldp redistribute . . . . .	1394
mpls ldp session holdtime . . . . .	1395
mpls ldp session keepalive interval . . . . .	1396
mpls ldp session retries . . . . .	1397
mpls ldp session retry-time . . . . .	1398
mpls ldp strict-security . . . . .	1399
mpls ldp sync . . . . .	1400
mpls ldp targeted-hello holdtime . . . . .	1401
mpls ldp targeted-hello interval . . . . .	1402
mpls ldp targeted-hello receive list . . . . .	1403
mpls ldp targeted-hello send list . . . . .	1404
mpls ldp vpls neighbor . . . . .	1405
mpls ldp vpls vpls-id . . . . .	1406
mpls lsp no-route retries . . . . .	1407
mpls lsp no-route retry-time . . . . .	1408
mpls lsp retries . . . . .	1409
mpls lsp retry-time . . . . .	1410
mpls match exp-bits . . . . .	1411
mpls match traffic-class . . . . .	1412
mpls policy . . . . .	1413
mpls policy-list . . . . .	1414

mpls policy-parameter hierarchical . . . . .	1415
mpls policy-parameter reference-rate . . . . .	1416
mpls policy-statistics . . . . .	1417
mpls preserve-vpn-exp . . . . .	1418
mpls-relay . . . . .	1419
mpls-relay atm cell-packing mcpt-timer . . . . .	1422
mpls-relay atm vpi-range vci-range . . . . .	1423
mpls-relay disable . . . . .	1424
mpls reoptimize . . . . .	1425
mpls reoptimize timers frequency . . . . .	1426
mpls rsvp . . . . .	1427
mpls rsvp authentication . . . . .	1428
mpls rsvp authentication key . . . . .	1429
mpls rsvp bfd-liveness-detection . . . . .	1430
mpls rsvp disable . . . . .	1431
mpls rsvp egress-label . . . . .	1432
mpls rsvp message-bundling . . . . .	1433
mpls rsvp profile . . . . .	1434
mpls rsvp refresh-reduction . . . . .	1435
mpls rsvp signalling hello . . . . .	1436
mpls rsvp signalling hello graceful-restart . . . . .	1437
mpls rsvp signalling hello graceful-restart recovery-time . . . . .	1438
mpls rsvp signalling hello graceful-restart restart-time . . . . .	1439
mpls rsvp signalling node-hello . . . . .	1440
mpls signaling-interface . . . . .	1441
mpls spf-use-any-best-path . . . . .	1442
mpls statistics label . . . . .	1443
mpls statistics next-hop . . . . .	1444
mpls statistics policy . . . . .	1445
mpls topology-driven-lsp . . . . .	1446
mpls topology-driven-lsp ip-interfaces . . . . .	1447
mpls traffic-class . . . . .	1448
mpls traffic-eng . . . . .	1449
mpls traffic-eng administrative-weight . . . . .	1450
mpls traffic-eng area . . . . .	1451
mpls traffic-eng attribute-flags . . . . .	1452
mpls traffic-eng egress-label . . . . .	1453
mpls traffic-eng flood thresholds . . . . .	1454
mpls traffic-eng link-management timers periodic-flooding . . . . .	1455
mpls traffic-eng multicast-intact . . . . .	1456
mpls traffic-eng router-id . . . . .	1457
mpls tunnel-model . . . . .	1458
mpls tunnels profile . . . . .	1459
mroute port admission-bandwidth-limit . . . . .	1460
mroute port limit . . . . .	1461
mru . . . . .	1462
mtrace . . . . .	1463
mtu . . . . .	1464
multicast . . . . .	1465

	multicast group port limit .....	1466
Part 2	Index	
	Index .....	1469

# List of Tables

	<b>About the Documentation . . . . .</b>	<b>xxxvii</b>
	Table 1: Notice Icons . . . . .	xxxviii
	Table 2: Text and Syntax Conventions . . . . .	xxxviii
<b>Part 1</b>	<b>Commands, A to M</b>	
<b>Chapter 1</b>	<b>Command Reference Topics . . . . .</b>	<b>3</b>
	Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router . . . . .	5
	Table 4: Interface Types and Specifiers for E120 Router and E320 Router . . . . .	13





# About the Documentation

- E Series and JunosE Documentation and Release Notes on page xxxvii
- Audience on page xxxvii
- E Series and JunosE Text and Syntax Conventions on page xxxvii
- Obtaining Documentation on page xxxix
- Documentation Feedback on page xxxix
- Requesting Technical Support on page xxxix

## E Series and JunosE Documentation and Release Notes

---

For a list of related JunosE documentation, see  
<http://www.juniper.net/techpubs/software/index.html>.

If the information in the latest release notes differs from the information in the documentation, follow the *JunosE Release Notes*.

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at  
<http://www.juniper.net/techpubs/>.

## Audience

---

This guide is intended for experienced system and network specialists working with Juniper Networks E Series Broadband Services Routers in an Internet access environment.

## E Series and JunosE Text and Syntax Conventions

---

Table 1 on page xxxviii defines notice icons used in this documentation.

Table 1: Notice Icons

Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.

Table 2 on page xxxviii defines text and syntax conventions that we use throughout the E Series and JunosE documentation.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
<b>Bold text like this</b>	Represents commands and keywords in text.	<ul style="list-style-type: none"> <li>Issue the <b>clock source</b> command.</li> <li>Specify the keyword <b>exp-msg</b>.</li> </ul>
<b>Bold text like this</b>	Represents text that the user must type.	<b>host1(config)#traffic class low-loss1</b>
Fixed-width text like this	Represents information as displayed on your terminal's screen.	<b>host1#show ip ospf 2</b>  Routing Process OSPF 2 with Router ID 5.5.0.250  Router is an Area Border Router (ABR)
<i>Italic text like this</i>	<ul style="list-style-type: none"> <li>Emphasizes words.</li> <li>Identifies variables.</li> <li>Identifies chapter, appendix, and book names.</li> </ul>	<ul style="list-style-type: none"> <li>There are two levels of access: <i>user</i> and <i>privileged</i>.</li> <li><i>clusterId</i>, <i>ipAddress</i>.</li> <li><i>Appendix A, System Specifications</i></li> </ul>
Plus sign (+) linking key names	Indicates that you must press two or more keys simultaneously.	Press Ctrl + b.
<b>Syntax Conventions in the Command Reference Guide</b>		
Plain text like this	Represents keywords.	terminal length
<i>Italic text like this</i>	Represents variables.	<i>mask</i> , <i>accessListName</i>

Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
(pipe symbol)	Represents a choice to select one keyword or variable to the left or to the right of this symbol. (The keyword or variable can be either optional or required.)	diagnostic   line
[ ] (brackets)	Represent optional keywords or variables.	[ internal   external ]
[ ]* (brackets and asterisk)	Represent optional keywords or variables that can be entered more than once.	[ level1   level2   l1 ]*
{ } (braces)	Represent required keywords or variables.	{ permit   deny } { in   out }  { clusterId   ipAddress }

## Obtaining Documentation

To obtain the most current version of all Juniper Networks technical documentation, see the Technical Documentation page on the Juniper Networks Web site at <http://www.juniper.net/>.

To download complete sets of technical documentation to create your own documentation CD-ROMs or DVD-ROMs, see the Portable Libraries page at

<http://www.juniper.net/techpubs/resources/index.html>

Copies of the Management Information Bases (MIBs) for a particular software release are available for download in the software image bundle from the Juniper Networks Web site at <http://www.juniper.net/>.

## Documentation Feedback

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation to better meet your needs. Send your comments to [techpubs-comments@juniper.net](mailto:techpubs-comments@juniper.net), or fill out the documentation feedback form at <https://www.juniper.net/cgi-bin/docbugreport/>. If you are using e-mail, be sure to include the following information with your comments:

- Document or topic name
- URL or page number
- Software release version

## Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or JNASC support contract,

or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <http://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf> .
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/> .
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

## Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Search for known bugs: <http://www2.juniper.net/kb/>
- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>
- Download the latest versions of software and review release notes: <http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <https://www.juniper.net/alerts/>
- Join and participate in the Juniper Networks Community Forum: <http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://tools.juniper.net/SerialNumberEntitlementSearch/>

## Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/> .
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <http://www.juniper.net/support/requesting-support.html> .

## PART 1

# Commands, A to M

- [Command Reference Topics on page 3](#)
- [A Commands on page 19](#)
- [B Commands on page 223](#)
- [C Commands on page 361](#)
- [D Commands on page 487](#)
- [E Commands on page 567](#)
- [F Commands on page 637](#)
- [G Commands on page 675](#)
- [H Commands on page 691](#)
- [I Commands on page 707](#)
- [K Commands on page 1169](#)
- [L Commands on page 1173](#)
- [M Commands on page 1285](#)



## CHAPTER 1

# Command Reference Topics

- [Using the no Version Versus the default Version of Commands on page 3](#)
- [Deprecated Commands on page 4](#)
- [Filtering show Commands on page 4](#)
- [Interface Types and Specifiers on page 5](#)

### Using the no Version Versus the default Version of Commands

---

Most router configuration commands have a **no** version, which you can use to negate a command (or a portion of it specified by an optional keyword) or restore its default setting. When you use a command *without* the keyword **no**, you can reenable a disabled feature or override a default setting. You have the option of using the **default** keyword whenever the **no** keyword is also a choice; simply enter the keyword **default** instead of **no**.

In most cases, when you execute the **default** version of a command, it produces the exact results as the **no** version. There are some commands for which the **default** version yields a different result than the **no** version.

Commands for which the **default** behavior differs from the **no** behavior are clearly identified in this guide. Unless otherwise specified, therefore, the **default** command is identical to the **no** command and is neither documented nor discussed.

The syntax for each **no** command is described in this guide. Some commands do not have a **no** version; this is indicated in the individual command descriptions except for the **show** commands, none of which has a **no** version.

The CLI can act on **no** versions of commands when you have entered sufficient information to distinguish the command syntactically, and ignores all subsequent input on that line.

To be compatible with some non-E Series implementations, the **no** versions of commands accept the same options as the affirmative version of the commands. The CLI ignores the optional input if it has no effect on the command behavior. If using the option changes the behavior of the **no** version, the individual command entry in this guide describes the difference in behavior.

## Deprecated Commands

---

A command that has been deprecated in a release or in a particular configuration mode returns a notice when you issue the command manually:

**NOTICE:** This command is obsolete. It may be completely removed from a subsequent software release.

A preferred alternate command is provided in the notice. If you have a script that uses the deprecated command, the deprecated command is automatically mapped to the preferred command when you run the script. If the deprecated command no longer has a function, then that command has no effect when you run a script containing the command.

We recommend that you use the preferred command when writing new scripts.

## Filtering show Commands

---

You have access to a variety of **show** commands that display router and protocol information. You can filter the output of a **show** command by specifying **|** (the UNIX pipe symbol), one of the following keywords, and either a case-sensitive text string or a regular expression.

- **begin**—Displays output beginning with the first line that contains the text string or regular expression
- **include**—Displays output lines that contain the text string or regular expression and excludes lines that do not contain the text string or regular expression
- **exclude**—Displays output lines that do not contain the text string or regular expression and excludes lines that do contain the text string or regular expression

You can press Ctrl+c to interrupt the **show** command output.



**NOTE:** The router does not recognize beginning spaces of the text string. For example, if you enter the **include** option with **IP** as the text string on which to filter, the router ignores the space and displays lines that include words such as **RIP**.

In the following example, the output display consists only of lines that contain the string *ip*. The router omits all other lines of the output from the display because none of them contain the string *ip*.

```
host1#show config include-defaults | include ip
! Configuration script generated on FRI NOV 12 1999 16:56:41 UTC
ip address 192.168.1.229 255.255.255.0
ip rip receive version 2 1
ip rip send version 1
ip rip authentication mode md5 17
ip rip authentication key
ip route 10.6.0.0 255.255.0.0 192.168.1.1
ip route 10.10.0.0 255.255.0.0 192.168.1.1
```




```
ip route 10.10.0.166 255.255.255.255 192.168.1.1
ip debounce-time 0
router rip
```

- Related Documentation
- For a list of regular expressions, see *Using Regular Expressions* in the *JunosE IP Services Configuration Guide*

## Interface Types and Specifiers


Many commands take the variables *interfaceType* and *interfaceSpecifier*. Some commands support all types of interfaces, whereas other commands support only certain types of interfaces. Similarly, some commands support all interface specifier formats for a particular interface type, whereas other commands support only certain interface specifier formats.

Table 3 on page 5 lists the interface specifiers for each type of interface on ERX7xx models, ERX14xx models, and the Juniper Networks ERX310 Broadband Services Router.



**NOTE:** On ERX7xx models, ERX14xx models, and the ERX310 router, you can use the `atm slot/port/vpi/vci` interface specifier format as an alternative to the `atm slot/port.subinterface` format with the specific `show interface` and `show subinterface` commands to monitor all ATM 1483 subinterfaces (except NBMA interfaces) as well as the upper-layer interfaces configured over an ATM 1483 subinterface. You cannot, however, use the `atm slot/port/vpi/vci` format to create or modify an ATM 1483 subinterface.

Table 4 on page 13 lists the interface specifiers for each type of interface on the Juniper Networks E120 and E320 Broadband Services Routers.



**NOTE:** On the E120 router and the E320 router you can use the `atm slot/adapter/port/vpi/vci` interface specifier format as an alternative to the `atm slot/adapter/port.subinterface` format with the specific `show interface` and `show subinterface` commands to monitor all ATM 1483 subinterfaces (except NBMA interfaces) as well as the upper-layer interfaces configured over an ATM 1483 subinterface. You cannot, however, use the `atm slot/adapter/port/vpi/vci` format to create or modify an ATM 1483 subinterface.

Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router

Interface Type	Description	Interface Specifier	Example
atm	ATM interface or ATM 1483 subinterface	Refer to the individual formats listed below.	

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
<ul style="list-style-type: none"> <li>ATM interface or subinterface</li> </ul>	<p>To configure an ATM interface or subinterface:</p> <p><i>slot/port[.subinterface ]</i></p> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	<p>atm 3/2.6</p>	
<ul style="list-style-type: none"> <li>ATM 1483 subinterface</li> </ul>	<p>To display information about an ATM 1483 subinterface by using <b>show</b> commands:</p> <p><i>slot/port/vpi/vci</i></p> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>vpi</i>—Virtual path identifier of the PVC on this ATM 1483 subinterface; allowable numeric range depends on the module capabilities and current configuration</li> <li><i>vci</i>—Virtual circuit identifier of the PVC on this ATM 1483 subinterface; allowable numeric range depends on the module capabilities and current configuration</li> </ul>	<p>atm 3/2/1/2</p>	

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
fastEthernet	IEEE 802.3 Fast Ethernet (FE) interface	<code>slot/port[.subinterface1[.subinterface2 ] ]</code> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module or port 0 for the Fast Ethernet management port on the SRP I/O module</li> </ul> <p>The meaning of the <i>subinterface</i> variables depends on the configuration context. You can configure Fast Ethernet interfaces with or without VLANs.</p> <ul style="list-style-type: none"> <li>VLANs: <ul style="list-style-type: none"> <li><i>subinterface1</i>—Number of the VLAN subinterface in the range 1–2147483647; no more than 4096 VLAN subinterfaces per Fast Ethernet physical port</li> <li><i>subinterface2</i>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 8000 PPPoE subinterfaces per Fast Ethernet line module</li> </ul> </li> <li>No VLANs: <ul style="list-style-type: none"> <li><i>subinterface1</i>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 8000 PPPoE subinterfaces per Fast Ethernet line module</li> <li><i>subinterface2</i>—Not used</li> </ul> </li> </ul>	fastEthernet 3/2.6.20

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
gigabitEthernet	IEEE 802.3 Gigabit Ethernet (GE) interface	<code>slot/port[.subinterface1[.subinterface2 ] ]</code> <ul style="list-style-type: none"> <li><code>slot</code>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><code>port</code>—Port number on the I/O module</li> </ul> <p>The meaning of the <code>subinterface</code> variables depends on the configuration context. You can configure Gigabit Ethernet interfaces with or without VLANs.</p> <ul style="list-style-type: none"> <li>VLANs: <ul style="list-style-type: none"> <li><code>subinterface1</code>—Number of the VLAN subinterface in the range 1–2147483647; no more than 4096 VLAN subinterfaces per Gigabit Ethernet physical port</li> <li><code>subinterface2</code>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 8000 PPPoE subinterfaces per Gigabit Ethernet line module</li> </ul> </li> <li>No VLANs: <ul style="list-style-type: none"> <li><code>subinterface1</code>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 8000 PPPoE subinterfaces per Gigabit Ethernet line module</li> <li><code>subinterface2</code>—Not used</li> </ul> </li> </ul>	gigabitEthernet 3/0.6.20
lag	IEEE 802.3ad link aggregation group (LAG) interface	<code>bundle-name[.subinterface ]</code> <ul style="list-style-type: none"> <li><code>bundle-name</code>—Name of the bundle</li> <li><code>subinterface</code>—Number of the LAG subinterface in the range 1–2147483647</li> </ul>	lag paris.2
loopback	Loopback interface	<code>integer</code> <ul style="list-style-type: none"> <li><code>integer</code>—Integer in the range 1–4294967293</li> </ul>	loopback 20
mlframe-relay	Multilink frame relay interface	<code>bundle-name[.subinterface ]</code> <ul style="list-style-type: none"> <li><code>bundle-name</code>—Name of the bundle</li> <li><code>subinterface</code>—Number of the MLFR subinterface in the range 1–4294967293</li> </ul>	mlframe-relay boston.1
mlppp	Multilink PPP interface	<code>bundle-name</code> <ul style="list-style-type: none"> <li><code>bundle-name</code>—Name of the bundle</li> </ul>	mlppp chicago

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
mplsL2shim	MPLS shim interface	<code>slot/port[.subinterface ]</code> <ul style="list-style-type: none"> <li><code>slot</code>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><code>port</code>—Port number on the I/O module</li> <li><code>subinterface</code>—Number of the subinterface in the range 1–2147483647</li> </ul>	mplsL2shim 3/2.1
mplsMajor	MPLS major interface	<code>slot/port[.subinterface ]</code> <ul style="list-style-type: none"> <li><code>slot</code>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><code>port</code>—Port number on the I/O module</li> <li><code>subinterface</code>—Number of the subinterface in the range 1–2147483647</li> </ul>	mplsMajor 3/2.1
mplsMinor	MPLS minor interface	<code>[ vr:]tunnel-name</code> <ul style="list-style-type: none"> <li><code>vr</code>—Name of a virtual router</li> <li><code>tunnel-name</code>—Name of the tunnel</li> </ul>	mplsMinor lsp-02020202-1-4
null	Null interface, which acts as a data sink and cannot forward or receive traffic. You cannot configure values on the null interface.	0	null 0
pos	Packet over SONET (POS) interface	<code>slot/port[.subinterface ]</code> <ul style="list-style-type: none"> <li><code>slot</code>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><code>port</code>—Port number on the I/O module</li> <li><code>subinterface</code>—Number of the subinterface in the range 1–2147483647</li> </ul>	pos 3/2
serial	CT3, E3 Frame, T3 Frame, or cOCx/STMx interface	Refer to the individual formats listed below.	

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
<ul style="list-style-type: none"> <li>CT3</li> </ul>		<i>slot/port:channel/subchannel[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models) and 0–13 (ERX14xx models)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>channel</i>—Number of a T1 channel on a CT3 module; in the range 1–28</li> <li><i>subchannel</i>—Number of the channel group associated with a range of DS0 timeslots on a CT3 module; in the range 1–28</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	serial 3/2:20/15
<ul style="list-style-type: none"> <li>E3/T3 Frame</li> </ul>		<i>slot/port[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models) and 0–13 (ERX14xx models)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	serial 3/2
<ul style="list-style-type: none"> <li>cOCx/STMx: unframed E1</li> </ul>		<i>slot/port:path-channel/path-payload/tributary-group/tributary-number/channelNumber[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>path-channel</i>—Number of the STS-1or STM-0 line in the range 1–2147483648</li> <li><i>path-payload</i>—Number of the payload within the path</li> <li><i>tributary-group</i>—Number of the tributary group within the path</li> <li><i>tributary-number</i>—Number of the tributary within the group</li> <li><i>channelNumber</i>—1 (the router assigns the number one to an unframed E1 channel)</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	serial 3/0:10/1/2/2/1

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
<ul style="list-style-type: none"> <li>cOCx/STMx: fractional E1/T1</li> </ul>		<i>slot/port/path-channel/path-payload/tributary-group/tributary-number/channel-group[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>path-channel</i>—Number of the STS-1or STM-0 line in the range 1–2147483648</li> <li><i>path-payload</i>—Number of the payload within the path</li> <li><i>tributary-group</i>—Number of the tributary group within the path</li> <li><i>tributary-number</i>—Number of the tributary within the group</li> <li><i>channel-group</i>—Number of a fractional T1 or E1 line</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	serial 3/0:10/1/2/2/1
<ul style="list-style-type: none"> <li>cOCx/STMx: unchannelized DS3</li> </ul>		<i>slot/port/path-channel/ds3-channel-number [.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>path-channel</i>—Number of the STS-1or STM-0 line in the range 1–2147483648</li> <li><i>ds3-channel-number</i>—Number of a T3 channel</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	serial 3/0:1/1

**Table 3: Interface Types and Specifiers for ERX7xx Models, ERX14xx Models, and ERX310 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
<ul style="list-style-type: none"> <li>cOCx/STMx: DS3 channelized to DS0</li> </ul>		<i>slot/port:path-channel/ds3-channel-number/ds1-channel-number/subchannel-number [subinterface]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>path-channel</i>—Number of the STS-1or STM-0 line in the range 1–2147483648</li> <li><i>ds3-channel-number</i>—Number of a T3 channel</li> <li><i>ds1-channel-number</i>—Number of a T1 channel</li> <li><i>subchannel-number</i>—Number of a fractional T1 channel</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	serial 3/0:1/1/10/15
sonet – line layer	Line layer of a SONET/SDH interface	<i>slot/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> </ul>	sonet 3/0
sonet – path layer	Path layer of a SONET/SDH interface	<i>slot/port:path-channel</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> <li><i>path-channel</i>—Number of the STS-1or STM-0 line in the range 1–2147483648</li> </ul>	sonet 3/0:2
sonet – section layer	Section layer of a SONET/SDH interface	<i>slot/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–6 (ERX7xx models), 0–13 (ERX14xx models), and 0–2 (ERX310 router)</li> <li><i>port</i>—Port number on the I/O module</li> </ul>	sonet 3/0
tunnel	Tunnel interface	<i>tunnel-type:tunnel-name[subinterface]</i> <ul style="list-style-type: none"> <li><i>tunnel-type</i>—Type of the tunnel: dvmp, gre, ipsec, l2tp, or mpls</li> <li><i>tunnel-name</i>—Name of the tunnel</li> <li><i>subinterface</i>—For GRE tunnels, number of the subinterface in the range 1–2147483647</li> </ul>	tunnel gre:boston



Table 4: Interface Types and Specifiers for E120 Router and E320 Router

Interface Type	Description	Interface Specifier	Example
atm	ATM interface or ATM 1483 subinterface	Refer to the individual formats listed below.	
<ul style="list-style-type: none"> <li>ATM interface or subinterface</li> </ul>		<p>To configure an ATM interface or subinterface:</p> <p><i>slot/adapter/port[.subinterface]</i></p> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	atm 3/1/7.6
<ul style="list-style-type: none"> <li>ATM 1483 subinterface</li> </ul>		<p>To display information about an ATM 1483 subinterface by using <b>show</b> commands:</p> <p><i>slot/adapter/port/vpi/vci</i></p> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> <li><i>vpi</i>—Virtual path identifier of the PVC on this ATM1483 subinterface; numeric range for the E120 and E320 routers is 0–255</li> <li><i>vci</i>—Virtual circuit identifier of the PVC on this ATM1483 subinterface; numeric range for the E120 and E320 routers is 1–65535</li> </ul>	atm 3/1/7/1/2

Table 4: Interface Types and Specifiers for E120 Router and E320 Router (*continued*)

Interface Type	Description	Interface Specifier	Example
fastEthernet  (for Fast Ethernet management port on SRP IOA)	IEEE 802.3 Fast Ethernet (FE) interface	<i>slot/adapter/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot, either 6 or 7</li> <li><i>adapter</i>—Identifier for the SRP I/O adapter (IOA) within the chassis slot; always 0</li> <li><i>port</i>—Port number on the SRP IOA; always 0</li> </ul>	fastEthernet 6/0/0
gigabitEthernet	IEEE 802.3 Gigabit Ethernet (GE) interface	<i>slot/adapter/port[.subinterface1[.subinterface2 ]]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> </ul> <p>The meaning of the <i>subinterface</i> variables depends on the configuration context. You can configure Gigabit Ethernet interfaces with or without VLANs.</p> <ul style="list-style-type: none"> <li>VLANs: <ul style="list-style-type: none"> <li><i>subinterface1</i>—Number of the VLAN subinterface in the range 1–2147483647; no more than 4096 VLAN subinterfaces per Gigabit Ethernet physical port</li> <li><i>subinterface2</i>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 16,000 PPPoE subinterfaces per Gigabit Ethernet line module</li> </ul> </li> <li>No VLANs: <ul style="list-style-type: none"> <li><i>subinterface1</i>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 16,000 PPPoE subinterfaces per Gigabit Ethernet line module</li> <li><i>subinterface2</i>—Not used</li> </ul> </li> </ul>	gigabitEthernet 4/0/1.20
lag	IEEE 802.3ad link aggregation group (LAG) interface	<i>bundle-name[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>bundle-name</i>—Name of the bundle</li> <li><i>subinterface</i>—Number of the LAG subinterface in the range 1–2147483647</li> </ul>	lag paris.2

**Table 4: Interface Types and Specifiers for E120 Router and E320 Router (continued)**

Interface Type	Description	Interface Specifier	Example
mplsL2shim	MPLS shim interface	<i>slot/adapter/port[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	mplsL2shim 3/0/2.1
mplsMajor	MPLS major interface	<i>slot/adapter/port[.subinterface ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> <li><i>subinterface</i>—Number of the subinterface in the range 1–2147483647</li> </ul>	mplsMajor 3/0/2.1
mplsMinor	MPLS minor interface	[ <i>vr:</i> ] <i>tunnel-name</i> <ul style="list-style-type: none"> <li><i>vr</i>—Name of a virtual router</li> <li><i>tunnel-name</i>—Name of the tunnel</li> </ul>	mplsMinor lsp-02020202-1-4

Table 4: Interface Types and Specifiers for E120 Router and E320 Router (*continued*)

Interface Type	Description	Interface Specifier	Example
pos	Packet over SONET (POS) interface	<i>slot/adapter/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> </ul>	pos 5/0/0
sonet – line layer	Line layer of a SONET/SDH interface	<i>slot/adapter/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> </ul>	sonet 3/0/0
sonet – path layer	Path layer of a SONET/SDH interface	<i>slot/adapter/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> </ul>	sonet 3/0/0

**Table 4: Interface Types and Specifiers for E120 Router and E320 Router (continued)**

Interface Type	Description	Interface Specifier	Example
sonet – section layer	Section layer of a SONET/SDH interface	<i>slot/adapter/port</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot, either 0 or 1, where: <ul style="list-style-type: none"> <li>0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).</li> <li>1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).</li> </ul> </li> <li><i>port</i>—Port number on the IOA</li> </ul>	sonet 3/0/0
tenGigabitEthernet	IEEE 802.3ae 10-Gigabit Ethernet (GE) interface	<i>slot/adapter/port[.subinterface1[.subinterface2 ] ]</i> <ul style="list-style-type: none"> <li><i>slot</i>—Number of the chassis slot in the range 0–5 (E120 router) and 0–5 or 11–16 (E320 router)</li> <li><i>adapter</i>—Identifier for the IOA within the chassis slot. 0 indicates that this a full-height IOA.</li> <li><i>port</i>—Port number on the IOA</li> </ul> <p>The meaning of the <i>subinterface</i> variables depends on the configuration context. You can configure 10-Gigabit Ethernet interfaces with or without VLANs.</p> <ul style="list-style-type: none"> <li>VLANs: <ul style="list-style-type: none"> <li><i>subinterface1</i>—Number of the VLAN subinterface in the range 1–2147483647; no more than 4096 VLAN subinterfaces per 10-Gigabit Ethernet physical port</li> <li><i>subinterface2</i>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 16,000 PPPoE subinterfaces per 10-Gigabit Ethernet line module</li> </ul> </li> <li>No VLANs: <ul style="list-style-type: none"> <li><i>subinterface1</i>—When using PPPoE, the number of the PPPoE subinterface in the range 1–2147483647; no more than 16,000 PPPoE subinterfaces per 10-Gigabit Ethernet line module</li> <li><i>subinterface2</i>—Not used</li> </ul> </li> </ul>	tenGigabitEthernet 4/0/1.20

**Table 4: Interface Types and Specifiers for E120 Router and E320 Router (*continued*)**

Interface Type	Description	Interface Specifier	Example
tunnel	Tunnel interface	<i>tunnel-type:tunnel-name[.subinterface]</i> <ul style="list-style-type: none"><li>• <i>tunnel-type</i>—Type of the tunnel: dvmrp, gre, l2tp, or mpls</li><li>• <i>tunnel-name</i>—Name of the tunnel</li><li>• <i>subinterface</i>—For GRE tunnels, number of the subinterface in the range 1–2147483647</li></ul>	tunnel gre:boston

## CHAPTER 2

# A Commands

## aaa accounting acct-stop on-aaa-failure

---

**Syntax**   aaa accounting acct-stop on-aaa-failure { enable | disable }  
             no aaa accounting acct-stop on-aaa-failure

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Configures AAA to send an Acct-Stop message if a user fails AAA, but RADIUS grants access. The **no** version returns the parameter to the default of enable.

**Options**

- enable—Specifies the feature; this is the default setting
- disable—Disables the feature

**Mode**    Global Configuration



## aaa accounting acct-stop on-access-deny

---

**Syntax**   aaa accounting acct-stop on-access-deny { enable | disable }  
             no aaa accounting acct-stop on-access-deny

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Issues an Acct-Stop message if RADIUS denies access. The **no** version returns the parameter to the default of disable.

**Options**

- enable—Specifies the feature
- disable—Disables the feature; this is the default setting

**Mode**    Global Configuration

## aaa accounting broadcast

---

**Syntax**    `aaa accounting broadcast vrGroupName`  
              `no aaa accounting broadcast`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Broadcasts accounting records for a virtual router to accounting servers of the virtual routers in the specified virtual router group. The **no** version disables the feature.

**Options**    • *vrGroupName*—Name of the virtual router group; a string of up to 32 characters

**Mode**    Global Configuration

## aaa accounting commands

---

**Syntax**    `aaa accounting commands level { default | listName } stop-only tacacs+`  
`no aaa accounting commands level listName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables AAA accounting for TACACS+ to be captured for a specific user privilege level and creates accounting method lists. The **no** version deletes the accounting method list.

- Options**
- *level*—Privilege level of user commands for which accounting information is captured; in the range 0–15
  - *default*—Specifies that the default method list is used to specify how accounting is performed
  - *listName*—Named method list used to specify how accounting is performed
  - *stop-only*—Sends a stop accounting notice at the end of a process

**Mode**    Global Configuration

## aaa accounting default

---

**Syntax**    `aaa accounting { subscriberType } default accountor [ accountor ]*`  
`no aaa accounting { subscriberType } default`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the accounting method used for a particular type of subscriber. The **no** version produces the same result as specifying the **radius** value.

- Options**
- *subscriberType*—Type of subscriber:
    - atm1483—Specifies ATM 1483 subscribers; not supported
    - ip—Specifies IP subscriber management interfaces
    - ipsec—Specifies IPSec subscribers
    - ppp—Specifies PPP subscribers
    - radius-relay—Specifies RADIUS relay server subscribers
    - tunnel—Specifies tunnel subscribers
  - *accountor*—Accounting method:
    - none—Disables accounting
    - radius—Enables RADIUS accounting
    - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## aaa accounting duplication

---

**Syntax**    `aaa accounting duplication routerName`  
              `no aaa accounting duplication`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sends duplicate accounting records to the accounting server of a different virtual router.  
                    The **no** version disables the feature.

**Options**    • *routerName*—Virtual router name

**Mode**    Global Configuration

## aaa accounting exec

---

**Syntax**   aaa accounting exec { default | *listName* } start-stop tacacs+  
no aaa accounting exec *listName*

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Enables AAA accounting for TACACS+ to be captured for User Exec terminal sessions, and creates accounting method lists. The **no** version deletes the accounting method list.

- Options**
- **exec**—Specifies that accounting information is captured for User Exec terminal sessions
  - **default**—Specifies that the default method list is used to specify how accounting is performed
  - ***listName***—Named method list used to specify how accounting is performed
  - **start-stop**—Sends a start accounting notice at the beginning of a process and a stop accounting notice at the end of a successful process

**Mode**   Global Configuration

## aaa accounting immediate-update

---

**Syntax**   aaa accounting immediate-update { enable | disable }  
              no aaa accounting immediate-update

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Configures the router to send an Acct-Update message to the accounting server on receipt of a response (ACK or timeout) for the Acct-Start message. The **no** version restores the default condition, disabling immediate updates.

**Options**

- enable—Specifies the feature
- disable—Disables the feature; this is the default setting

**Mode**   Global Configuration

## aaa accounting interval

---

**Syntax**    `aaa accounting interval period`  
`no aaa accounting interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the default accounting interval used for all users and services. The **no** version sets the value to 0, which turns off interim accounting.



.....  
**NOTE:** This command is deprecated and might be removed completely in a future release. Use the **aaa service accounting interval** and **aaa user accounting interval** commands to configure default accounting intervals for services and users.  
.....

**Options**    • *period*—Accounting interval in minutes in the range 10–1440, which sets the time period between accounting updates

**Mode**    Global Configuration



## aaa accounting statistics

---

**Syntax**   aaa accounting statistics { volume-time | time }  
             no aaa accounting statistics

**Release Information**   Command introduced in JunosE Release 7.2.0.

**Description**   Configures the router to collect either a full set of statistics or only uptime status for the sessions AAA is managing. Collecting only the uptime status is a more efficient use of system resources. The **no** version restores the default setting in which the router collects full statistics.

- Options**
- volume-time—Collects a full complement of statistics from each connection; the default setting
  - time—Collects only uptime status for each connection

**Mode**   Global Configuration

## aaa accounting suppress null-username

---

**Syntax** [ no ] aaa accounting suppress null-username

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that accounting records are not generated for users whose username string is null; accounting records will be generated only for users with explicit usernames. The **no** version enables accounting records to be generated for all users, including those who do not have usernames.

**Mode** Global Configuration

## aaa accounting vr-group

---

**Syntax** [ no ] aaa accounting vr-group *vrGroupName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an accounting virtual router group and enters VR Group Configuration mode. A virtual router group can have up to four virtual routers, whose accounting servers can receive broadcast accounting records. A group must contain at least one virtual router. The **no** version deletes the accounting virtual router group.

**Options** • *vrGroupName*—Name of the virtual router group; a string of up to 32 characters

**Mode** Global Configuration

## aaa authentication default

---

**Syntax**    `aaa authentication subscriberType default authenticator [ authenticator ]*`  
`no aaa authentication subscriberType default`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the authentication method used for a particular type of subscriber. The **no** version produces the same result as specifying the **radius** value.

- Options**
- *subscriberType*—Type of subscriber:
    - atm1483—Specifies ATM 1483 subscribers
    - ip—Specifies IP subscriber management interfaces
    - ipsec—Specifies IPSec subscribers
    - ppp—Specifies PPP subscribers
    - radius-relay—Specifies RADIUS relay server subscribers
    - tunnel—Specifies tunnel subscribers
  - *authenticator*—Authentication method:
    - none—Disables authentication, allowing all users access
    - local—Enables local authentication; supported for PPP subscribers only
    - radius—Enables RADIUS for authentication
    - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## aaa authentication enable default

---

**Syntax**    `aaa authentication enable default authenticator [ authenticator ]*`  
`no aaa authentication enable default`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Allows privilege determination to be authenticated through the authenticator(s) you specify (TACACS+ or RADIUS server). This command specifies a list of authentication methods that are used to determine whether a user is granted access to the privilege command level. This authentication is applied to vty users. Requests sent to a TACACS+ or RADIUS server include the username that is entered for login authentication. If the authentication method list is empty, the local **enable** password is used. To specify that the authentication should succeed even if all methods return an error, specify **none** as the final method in the command line. The **no** version removes the authentication settings.

**Options**    • *authenticator*—Authentication method:

- **enable**—Use the enable password
- **line**—Use the line password
- **none**—Use no authentication
- **radius**—Use RADIUS authentication
- **tacacs+**—Use TACACS+ authentication
- **\***—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## aaa authentication login

---

**Syntax**    `aaa authentication login { default | authListName } authenticator [ authenticator ]*`  
`no aaa authentication login authListName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates an authentication list and the criteria for login. This authentication is applied to vty users. After you have specified **aaa new-model** as the authentication method for vty lines, an authentication list called default is automatically assigned to the vty lines. To allow users to access the vty lines, you must create an authentication list and either:

- Name the list default.
- Assign a different name to the authentication list, and assign the new list to the vty line using the **login authentication** command.

The system traverses the list of authentication methods to determine whether a user is allowed to start a Telnet session. If a specific method is available but the user information is not valid (such as an incorrect password), the system does not continue to traverse the list and denies the user a session. If a specific method is unavailable, the system continues to traverse the list. For example, if **tacacs+** is the first authentication type element on the list and the TACACS+ server is unreachable, the system attempts to authenticate with the next authentication type on the list, such as **radius**. The system assumes an implicit denial of service if it reaches the end of the authentication list without finding an available method. The **no** version disables AAA authentication.

- Options**
- **default**—Specifies the use of the default login for authentication
  - ***authListName***—Existing authentication list name (created using the **login authentication** command); a string of 1–32 characters
  - ***authenticator***—Authentication method:
    - **line**—Use the line password for authentication
    - **none**—Use no authentication
    - **radius**—Use RADIUS authentication
    - **tacacs+**—Use TACACS+ authentication
  - **\***—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## aaa authorization

**Syntax** `aaa authorization { exec | commands level } authorListName authMethod [ authMethod ]*`

`no aaa authorization { exec | commands level } authorListName`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets parameters that restrict a user's access to a network. The **no** version disables authorization for a function.

- Options**
- **exec**—Runs authorization to determine if the user is allowed to run Exec mode commands
  - **level**—Privilege level of commands for which authorization is run; in the range 0–15
  - **authorListName**—Name of the authorization methods list of up to 32 characters
  - **authMethod**—Authorization method lists define the way authorization is performed and the sequence in which the methods are performed. You can designate one or more security protocols in the method list to be used for authorization. If the initial method fails, the next method in the list is used. The process continues until either there is successful communication with a listed authorization method or all methods defined are exhausted:
    - **if-authenticated**—Allows the user to access the requested function if the user is authenticated
    - **none**—NAS does not request authorization information; authorization is not performed over this line
    - **tacacs+**—NAS exchanges authorization information with the TACACS+ security daemon



**NOTE:** For information about TACACS+, see *JunosE Broadband Access Configuration Guide*.

- **\***—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## aaa authorization config-commands

---

**Syntax** [ no ] aaa authorization config-commands

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Reauthorizes the use of Global Configuration commands. This command is enabled by default when the **aaa authorization commands** command is executed. The **no** version disables AAA configuration command authorization.



.....  
**NOTE:** Using the **no** version can potentially reduce the amount of administrative control on configuration commands.  
.....

**Mode** Global Configuration



## aaa delimiter

---

**Syntax**    `aaa delimiter { domainName | realmName } delimiters`  
`no aaa delimiter { domainName | realmName }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies delimiters for the domain and realm names. You can specify up to eight delimiters each for domain and realm names. The **no** version restores the default value.

- Options**
- `domainName`—Allows you to set delimiters for the domain name
  - `realmName`—Allows you to set delimiters for the realm name
  - `delimiters`—Either the domain or realm delimiter(s). You can specify up to eight characters.
    - The default domain name delimiter is @.
    - The default realm name delimiter is NULL (no character). In this case, realm parsing is disabled (having no delimiter disables realm parsing).

**Mode**    Global Configuration

## aaa dhcpv6-delegated-prefix delegated-ipv6-prefix

---

**Syntax** [ no ] aaa dhcpv6-delegated-prefix delegated-ipv6-prefix

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Sets the Delegated-IPv6-Prefix RADIUS attribute to be used for DHCPv6 Prefix Delegation. The **no** version restores the default behavior, which causes the Framed-IPv6-Prefix RADIUS attribute to be used for Prefix Delegation.



.....

**NOTE:** If you configured the Framed-IPv6-Prefix attribute to be used for IPv6 Neighbor Discovery router advertisements by using the **aaa ipv6-nd-ra-prefix framed-ipv6-prefix** command, you must also issue the **aaa dhcpv6-delegated-prefix delegated-ipv6-prefix** command after you issue the **aaa ipv6-nd-ra-prefix framed-ipv6-prefix** command to enable the use of the Delegated-IPv6-Prefix attribute for DHCPv6 Prefix Delegation. Otherwise, the Framed-IPv6-Prefix attribute will be used for both IPv6 Neighbor Discovery router advertisements and DHCPv6 Prefix Delegation.

.....

**Mode** Global Configuration

## aaa dhcpv6-ndra-pool override

---

**Syntax** [ no ] aaa dhcpv6-ndra-pool override

**Release Information** Command introduced in JunosE Release 13.0.0.

**Description** If the authentication server returns the Neighbor Discovery router advertisement prefix pool name in the RADIUS-Accept-Request message, it causes the Framed-Ipv6-Pool attribute to be used for IPv6 Neighbor Discovery router advertisements and the Delegated-Ipv6-Pool attribute to be used for DHCPv6 Prefix Delegation. The **no** version of this command causes the Ipv6-NdRa-Pool attribute to be used for IPv6 Neighbor Discovery router advertisements and the Framed-Ipv6-Pool attribute to be used for DHCPv6 Prefix Delegation. When the Ipv6-NdRa-Pool attribute is used for Neighbor Discovery, the prefix to be allocated to requesting routers or subscribers is obtained from the IPv6 local address pool for Neighbor Discovery. When the Delegated-Ipv6-Pool attribute is used for Prefix Delegation, the prefix to be delegated to the clients is obtained from the IPv6 local address pool for Prefix Delegation.

**Mode** Global Configuration

**Related Documentation**

- [Configuring IPv6 Neighbor Discovery Local Address Pools](#)

## aaa dns

---

**Syntax**    `aaa dns { primary | secondary } ipAddress`  
              `no aaa dns { primary | secondary }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IP address of the primary DNS name server. The **no** version sets the corresponding address to 0.

- Options**
- `primary`—Specifies the primary DNS name server
  - `secondary`—Specifies the secondary DNS name server
  - `ipAddress`—IP address of the name server

**Mode**    Global Configuration

## aaa domain-map

---

**Syntax**    `aaa domain-map domainName`  
              `[ routerName [ loopback interfaceNumber | ipAddress ipMask ] ]`  
  
              `no aaa domain-map domainName`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              *ipAddress* and *ipMask* variables added in JunosE Release 9.0.0.

**Description**    Maps a user domain name to a virtual router. When you specify only the domain name, the command sets the mode to Domain Map Configuration. The **no** version deletes the map entry.

- Options**
- *domainName*—User domain name; specify the domain name *none* to assign users without domains to a specific virtual router.
  - *routerName*—Router name associated with the domain name
  - *loopback*—Specifies the loopback interface
  - *interfaceNumber*—Interface number in the range 0–32000
  - *ipAddress*—IP address of the local interface
  - *ipMask*—IPv4 address mask of the local interface

**Mode**    Global Configuration

## aaa duplicate-address-check

---

**Syntax**   aaa duplicate-address-check { enable | disable }

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Allows you to enable or disable routing table address lookup or duplicate address check. There is no **no** version.



.....  
**NOTE:** To use this command, you must have a B-RAS license. Run the **license b-ras** command and enter your password.  
.....

- Options**
- enable—Specifies the feature; this is the default
  - disable—Disables the feature

**Mode**   Global Configuration

## aaa duplicate-prefix-check

---

**Syntax** [ no | default ] aaa duplicate-prefix-check { enable | disable }

**Release Information** Command introduced in JunosE Release 11.2.0.

**Description** Configures AAA to enable duplicate IPv6 prefix-check in a virtual router context. Duplicate IPv6 prefix checking by AAA is disabled by default . The **default** version restores the default condition. The **no** version disables the duplicate IPv6 prefix-check capability.

**Options**

- enable—Specifies the feature
- disable—Disables the feature; this is the default

**Mode** Global Configuration

## aaa duplicate-prefix-check-extension

---

**Syntax** [ no | default ] aaa duplicate-prefix-check-extension { enable | disable }

**Release Information** Command introduced in JunosE Release 12.2.0.

**Description** Configures AAA to enable the enhanced duplicate IPv6 prefix-check in a virtual router context. Enhanced duplicate IPv6 prefix checking by AAA is disabled by default . The **no** version disables the enhanced duplicate IPv6 prefix-check capability.

- Options**
- **enable**—Specifies the feature
  - **disable**—Disables the feature; this is the default

**Mode** Global Configuration



## aaa intf-desc-format include

**Syntax**    `aaa intf-desc-format include { sub-intf | adapter } { enable | disable }`  
               `no aaa intf-desc-format include { sub-intf | adapter }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies whether the subinterface or adapter is included in or omitted from the interface description that the router passes to RADIUS for inclusion in the NAS-Port-Id attribute. Also affects the Interface field displayed by the **show subscribers** command. The **no** version restores the default, in which the subinterface and adapter are included.



**NOTE:** For subscribers connected over the link aggregation group (LAG) interface in DHCP standalone authenticate mode, RADIUS uses the LAG interface ID for the Nas-Port-Id attribute.

- Options**
- **sub-intf**—Specifies that the subinterface is included in or omitted from the interface description
  - **adapter**—Specifies that the adapter is included in or omitted from the interface description
  - **enable**—Includes the subinterface or adapter in the interface description; this is the default
  - **disable**—Omits the subinterface or adapter from the interface description

**Mode**    Global Configuration

## aaa ipv4-addr-saving

---

**Syntax** [no] aaa ipv4-addr-saving *string*

**Release Information** Command introduced in JunosE Release 13.1.0.

**Description** Enables the PPP application to inform the RADIUS server about released IPv4 addresses for dual-stack subscribers. A string of up to 32 alphanumeric characters, including special printable characters, is included in the VSA. The **no** version restores the default.

**Mode** Global Configuration

**Related Documentation**

- [Configuring IPCP Renegotiations in a Dual-Stack Network for Optimal Utilization of Released IPv4 Addresses](#)
- [Overview of Processing IPCP Negotiations for Dual-Stack Subscribers](#)

## aaa ipv6-dns

---

**Syntax**    `aaa ipv6-dns { primary | secondary } ipv6Address`  
              `no aaa ipv6-dns { primary | secondary }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IPv6 address of the primary DNS name server. The **no** version sets the corresponding address to 0 (or ::).

- Options**
- `primary`—Specifies the primary DNS name server
  - `secondary`—Specifies the secondary DNS name server
  - `ipv6Address`—IPv6 address of the name server

**Mode**    Global Configuration

## aaa ipv6-nd-ra-prefix framed-ipv6-prefix

---

**Syntax** [ no ] aaa ipv6-nd-ra-prefix framed-ipv6-prefix

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Sets the Framed-IPv6-Prefix RADIUS attribute to be used for IPv6 Neighbor Discovery router advertisements. The **no** version restores the default behavior, which causes the IPv6-NdRa-Prefix VSA to be used for router advertisements.



.....

**NOTE:** If you issue this command before issuing the **aaa dhcpv6-delegated-prefix delegated-ipv6-prefix** command, a warning message is displayed prompting you to configure the Delegated-IPv6-Prefix attribute for DHCPv6 Prefix Delegation. The message also states that the Framed-IPv6-Prefix RADIUS attribute will be used for both IPv6 Neighbor Discovery router advertisements and DHCPv6 Prefix Delegation if you do not configure the Delegated-IPv6-Prefix attribute for Prefix Delegation.

This warning message is displayed only if you configured the logging severity level as warning for the aaaServerGeneral logging event category.

.....

**Mode** Global Configuration

## aaa local database

---

**Syntax** [ no ] aaa local database *databaseName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a local user database for use by a local authentication server. The **no** version deletes the local user database and all entries in the database.

**Options**

- *databaseName*—Name of the user database; up to 32 characters; the name **default** is recognized as the default user database

**Mode** Global Configuration

## aaa local select database

---

**Syntax**   aaa local select database *databaseName*  
             no aaa local select

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Assigns the local user database that the virtual router uses for local authentication. The **no** version restores the default setting, which uses the default local user database for local authentication.

**Options**

- *databaseName*—Name of the local user database

**Mode**       Global Configuration

## aaa local username

---

**Syntax** [ no ] aaa local username *userName* database *databaseName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures a user entry in the specified local user database and enters Local User Configuration mode. The **no** version deletes the user entry from the specified local user database.

**Options**

- *userName*—User name of the subscriber
- *databaseName*—Name of the local user database; database name **default** configures the username in the default local user database

**Mode** Global Configuration

## aaa new-model

---

**Syntax** [ no ] aaa new-model

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies AAA authentication for Telnet sessions. It is also used to specify AAA new model as the authentication method for the vty lines on your router. If you specify AAA new model and you do not create an authentication list, users will not be able to access the router through a vty line. The **no** version restores simple authentication (login and password).

**Mode** Global Configuration



## aaa parse-direction

---

**Syntax**    `aaa parse-direction { domainName | realmName } { left-to-right | right-to-left }`  
`no aaa parse-direction { domainName | realmName }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the direction the router uses for domain and realm parsing. The router either searches from right-to-left, or from left-to-right. If searching for the realm, the router uses the realm delimiter valued in its search. If searching for the domain, it uses the domain delimiter values in its search. The **no** version returns the parse direction to the default setting.

- Options**
- **domainName**—Specifies that the domain name is parsed. The router performs domain searches from right-to-left by default.
  - **realmName**—Specifies that the realm name is parsed. The router performs realm searches from left-to-right by default.
  - **left-to-right**—Causes the router to search from the left-most character. When the router reaches a realm delimiter, it uses anything to the left of the delimiter as the domain. When the router reaches a domain delimiter, it uses anything to the right of the delimiter as the domain.
  - **right-to-left**—Causes the router to search from the right-most character. When the router reaches a realm delimiter, it uses anything to the left of the delimiter as the domain. When the router reaches a domain delimiter, it uses anything to the right of the delimiter as the domain.

**Mode**    Global Configuration

## aaa parse-order

---

**Syntax**   aaa parse-order { domain-first | realm-first }  
             no aaa parse-order

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Specifies the order in which the router searches for a domain name. It either searches for realm and then domain, or it searches for domain and then realm. The **no** version returns the parse order to the default of searching for realm first.

- Options**
- domain-first—Causes the router to search for a domain name first. When the router reaches a domain delimiter, it uses anything to the right of the delimiter as the domain name.
  - realm-first—Causes the router to search for a realm name first. When the router reaches a realm delimiter, it uses anything to the left of the delimiter as the domain name.

**Mode**   Global Configuration

## aaa per-profile-attr-list

---

**Syntax** [ no ] aaa per-profile-attr-list *profileName*

**Release Information** Command introduced in JunosE Release 12.1.0.

**Description** Creates a new AAA per-profile attribute list and puts the E Series router into AAA-Per-Profile Configuration mode. The **no** version removes the configured AAA per-profile attribute list. By default, no attribute list is configured.

**Options** • *profileName*—Name of the AAA per-profile; string of up to 32 characters

**Mode** Global Configuration

**Related Documentation** • [Configuring an AAA Per-Profile Attribute List](#)

## aaa per-profile-attr-list (For Global Configuration)

---

<b>Syntax</b>	<code>aaa per-profile-attr-list <i>profileName</i> action-type { enable   disable } attributes [ <i>attributeName</i> ]*</code>  <code>[ no ] aaa per-profile-attr-list <i>profileName</i></code>
<b>Release Information</b>	Command introduced in JunosE Release 12.1.0.
<b>Description</b>	Allows the user to configure an AAA per-profile list with attributes. The <b>no</b> version removes the configured AAA per-profile attribute list. By default, no attribute list is configured.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>profileName</i>—Name of the AAA per-profile; string of up to 32 characters</li><li>• enable—Includes the attribute in the request packets</li><li>• disable—Excludes the attribute in the request packets</li><li>• <i>attributeName</i>—The following AAA attributes can be specified:<ul style="list-style-type: none"><li>• tunnel-ignore-nasport</li><li>• tunnel-ignore-nasport-type</li><li>• *—Indicates that one or more parameters can be repeated multiple times in a list in the command line</li></ul></li></ul>
<b>Mode</b>	Global Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring an AAA Per-Profile Attribute List</li></ul>

## aaa-perprofilelist-name

---

**Syntax** [ no | default ] aaa-perprofilelist-name [ *perProfileName* ]

**Release Information** Command introduced in JunosE Release 12.1.0.

**Description** Allows the user to attach the AAA per-profile name in the AAA profile. The **no** version restores the default value. By default, the profile name is not configured.

**Options** • *perProfileName*—Name of the AAA per-profile; string of up to 32 characters

**Mode** AAA Profile Configuration

## aaa profile

---

**Syntax** [ no ] aaa profile *profileName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a new AAA profile to allow mapping to AAA services. The **no** version removes the profile.

**Options** • *profileName*—Profile name of up to 32 characters

**Mode** AAA Profile Configuration

## aaa qos downstream-rate

---

**Syntax** [ no ] aaa qos downstream-rate

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Enables the QoS downstream rate application to shape VLANs or ATM VCs based on downstream rates obtained from the Actual-Data-Rate-Downstream [26-130] DSL Forum VSA. The **no** version returns the parameter to the default of disabled.

**Mode** Global Configuration

## aaa route-download

---

**Syntax**    `aaa route-download [ downloadInterval ] [ retry-interval retryInterval ]`  
              `[ cost cost ] [ tag tagValue ] [ base-user-name name ] [ password password ]`  
              `[ synchronization time ]`

`no aaa route-download`

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Enables the RADIUS route-download server and configures parameters for the server. The **no** version disables the route-download server.

- Options**
- *downloadInterval*—Interval between download operations, in the range 1–1440 minutes; default is 720 minutes
  - *retryInterval*—Interval between retries after a failed download, in the range 1–60 minutes; default is 10 minutes
  - *cost*—Default cost of a downloaded route, in the range 1–254; default is 2
  - *tagValue*—Default tag of a downloaded route, in the range 1–4294967295; default is 0
  - *name*—Name of router used for route-download requests; default is the router hostname
  - *password*—Password used for route-download requests
  - *time*—Time the download operation is restarted each day, in 24-hour format (hh:mm:ss)

**Mode**    Global Configuration



## aaa route-download ipv6

**Syntax**    `aaa route-download ipv6 [ downloadInterval ] [ retry-interval retryInterval ]`  
               `[ cost cost ] [ tag tagValue ] [ ipv6-base-user-name ipv6BaseUserName ] [ ipv6-password`  
               `ipv6Password ] [ synchronization time ]`

`no aaa route-download ipv6`

**Release Information**    Command introduced in JunosE Release 13.0.0.

**Description**    Enables the RADIUS route-download server to download IPv6 routes and configures parameters for the route downloader. The **no** version disables the route-download server.

- Options**
- *downloadInterval*—Interval between download operations, in the range 1–1440 minutes; default value is 720 minutes
  - *retryInterval*—Interval between retries after a failed download, in the range 1–60 minutes; default value is 10 minutes
  - *cost*—Default cost of a downloaded route, in the range 1–254; default value is 2
  - *tagValue*—Default tag of a downloaded route, in the range 1–4294967295; default is value 0
  - *ipv6BaseUserName* —User name used for route-download requests; default is the router hostname
  - *ipv6Password*—Password used for route-download requests
  - *time*—Time the download operation is restarted each day, in 24-hour format (hh:mm:ss)

**Mode**    Global Configuration

## aaa route-download ipv6 now

---

**Syntax**   aaa route-download ipv6 now [ force ] [ adjust-scheduler ]

**Release Information**   Command introduced in JunosE Release 13.0.0.

**Description**   Specifies that the RADIUS route-download server immediately performs the IPv6 route-download operation. If a download is currently in progress when you issue this command without the **force** keyword, the in-progress download continues until complete and no additional download is started. There is no **no** version.

- Options**
- **force**—Interrupts any in-progress route-download operation and immediately starts a new download
  - **adjust-scheduler**—Resets the download scheduler to use this download as the start time for synchronizing download counts

**Mode**   Privileged Exec

## aaa route-download now

---

**Syntax**   aaa route-download now [ force ] [ adjust-scheduler ]

**Release Information**   Command introduced in JunosE Release 8.1.0.

**Description**   Specifies that the RADIUS route-download server immediately perform the route download operation. If a download is currently in progress when you issue this command without the **force** keyword, the in-progress download continues until complete and no additional download is started. There is no **no** version.

- Options**
- **force**—Interrupts any in-progress route-download operation and immediately starts a new download
  - **adjust-scheduler**—Resets the download scheduler to use this download as the start time for synchronizing download counts

**Mode**   Privileged Exec

## aaa route-download suspend

---

**Syntax** [ no ] aaa route-download suspend [ ipv6 ]

**Release Information** Command introduced in JunosE Release 8.1.0.  
**ipv6** keyword added in JunosE Release 13.0.0.

**Description** Temporarily suspends the RADIUS route-download server operation. The **no** version stops the suspend specification and restores the route-download operation.

**Options** • **ipv6**—Temporarily suspends the IPv6 route-download operation

**Mode** Privileged Exec

---

## aaa service accounting interval

---

**Syntax**    `aaa service accounting interval period`  
`no aaa service accounting interval`

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Specifies the default accounting interval used for services on the virtual router—the Service Manager application uses this setting for RADIUS-initiated services when no value is specified in the Service-Interim-Acct-Interval VSA (Juniper VSA 26-140). The **no** version restores the default setting of 0, which turns off interim accounting for services associated with users attached to this virtual router.



**NOTE:** This command and the `aaa user accounting interval` command replace the deprecated `aaa accounting interval` command, which may be removed completely in a future release.

**Options**    • *period*—Accounting interval in minutes in the range 10–1440, which sets the time period between accounting updates for services associated with users on this virtual router; 0 is the default

**Mode**    Global Configuration

## aaa strip-domain

**Syntax** `aaa strip-domain { delimiter domainName delimiter | disable | enable | parse-direction domainName { left-to-right | right-to-left } }`

`no aaa strip-domain { delimiter domainName | parse-direction domainName }`

**Release Information** Command introduced in JunosE Release 12.0.0.

**Description** Enables domain name stripping configuration per virtual router. By default, domain name stripping per virtual router is disabled. If domain name stripping is enabled, then you can specify the parse-direction and the delimiter value for the domain name.

Based on the parse-direction configured, the router searches from right-to-left, or from left-to-right. While searching for the domain, it uses the domain delimiter values in its search and parses the domain name accordingly.

The **no** version disables the domain name stripping functionality.



**NOTE:** The **aaa strip-domain** command can be configured on a non-default virtual router only.

- Options**
- **delimiter**—Configures the delimiter for the subscriber's domain name per virtual router
  - **domainName**—Configures the domain name characteristics for the broadband remote access subscriber per virtual router
  - ***delimiter***—Delimiter value configured for the domain using the **aaa delimiter** command; default value is @
  - **disable**—Disables the domain name stripping functionality for a virtual router
  - **enable**—Enables domain name stripping functionality for a virtual router
  - **parse-direction**—Configures the parsing direction for the subscriber's domain name per virtual router. The default parsing direction for a domain name is right-to-left
  - **left-to-right**—Causes the router to search from the left-most character. When the router reaches a domain delimiter, it uses anything to the right of the delimiter as the domain
  - **right-to-left**—Causes the router to search from the right-most character. When the router reaches a domain delimiter, it uses anything to the right of the delimiter as the domain

**Mode** Global Configuration

**Related Documentation**

- [aaa domain-map on page 41](#)
- `show aaa strip-domain`

- ppp authentication

## aaa subscriber limit per-port

---

**Syntax**    `aaa subscriber limit per-port interfaceSpecifier limitValue`  
              `no aaa subscriber limit per-port interfaceSpecifier`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum number of active subscribers permitted on the specified port. The **no** version returns the limit to the default, 0 (zero).

- Options**
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *limitValue*—Maximum number of subscribers; default value is 0 (zero), which means there is no limit on the number of subscribers

**Mode**    Global Configuration



## aaa subscriber limit per-vr

---

**Syntax**   aaa subscriber limit per-vr *limitValue*  
              no aaa subscriber limit per-vr

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Sets the maximum number of active subscribers permitted on the virtual router. The **no** version returns the limit to the default, 0 (zero).

**Options**

- *limitValue*—Maximum number of subscribers; default value is 0 (zero), which means there is no limit on the number of subscribers

**Mode**    Global Configuration

## aaa timeout

**Syntax** To set the default idle timeout:

```
aaa timeout idle idleTimeout
```

```
no aaa timeout idle
```

To set the default session timeout:

```
aaa timeout session sessionTimeout
```

```
no aaa timeout session
```

To enable monitoring of only ingress traffic for the configured idle timeout period:

```
aaa timeout idle ingress-only
```

```
no aaa timeout idle [ ingress-only ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**ingress-only** keyword added in JunosE Release 9.3.0.

**Description** Sets the default idle timeout or session timeout for B-RAS PPP users, and optionally enables the PPP application to monitor only ingress traffic for the configured idle timeout period to determine whether to disconnect an inactive PPP session. The **no** version restores the idle timeout or session timeout to its default value, 0 seconds, and disables ingress-only traffic monitoring for idle timeout if configured.



**NOTE:** To enable ingress-only traffic monitoring for the idle timeout period by issuing the **aaa timeout idle ingress-only** command, you must also set the idle timeout value by issuing the **aaa timeout idle** command.

- Options**
- *idleTimeout*—In seconds, 300–86400
  - *sessionTimeout*—Time in the range 60–31622400 seconds (that is, a minimum of 1 minute to a maximum of 366 days); the router terminates the user session once the maximum session timeout is reached, which means that the duration of a PPP or an L2TP user session cannot exceed 366 days
  - **ingress-only**—Enables PPP to monitor only ingress traffic for the configured idle timeout period to determine whether to disconnect an inactive PPP session; if you do not specify the **ingress-only** keyword, PPP monitors both ingress traffic and egress traffic for the idle timeout period to determine inactivity and subsequent disconnection of an inactive PPP session

**Mode** Global Configuration

## aaa tunnel assignment-id-format

---

**Syntax**   aaa tunnel assignment-id-format { assignmentId | client-server-id }  
no aaa tunnel assignment-id-format

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Sets the format for the tunnel assignment ID. The **no** version sets the tunnel assignment ID to the default, assignmentID.

**Options**

- assignmentId—Configures the format to be assignmentId only
- client-server-id—Configures the format to be a combination of clientAuthId + serverAuthId + assignmentId

**Mode**   Global Configuration

## aaa tunnel calling-number-format

---

**Syntax**   aaa tunnel calling-number-format  
              { descriptive [ include-agent-circuit-id ] [ include-agent-remote-id ] |  
              fixed [ stacked ] |  
              fixed-adapter-embedded [ stacked ] |  
              fixed-adapter-new-field [ stacked ] |  
              include-agent-circuit-id [ include-agent-remote-id ] |  
              include-agent-remote-id }  
  
              no aaa tunnel calling-number-format

**Release Information**   Command introduced before JunosE Release 7.1.0.  
                          **include-agent-circuit-id** and **include-agent-remote-id** keywords added in JunosE Release 8.1.0.  
                          **stacked** keyword added in JunosE Release 9.3.0.  
                          **fixed-adapter-embedded** and **fixed-adapter-new-field** keywords added in JunosE Release 10.0.0.

**Description**   Configures the format used by the E Series L2TP access concentrator (LAC) to generate the L2TP Calling Number attribute value pair (AVP) 22 that it passes to the L2TP network server (LNS). Available formats include different fixed formats and several formats that include either or both of the agent-circuit-id (suboption 1) and agent-remote-id (suboption 2) suboptions of the PPPoE intermediate agent tags. The **no** version restores the default calling number format, descriptive.

- Options**
- descriptive—Formats calling number AVP in descriptive format that includes only interface information
  - descriptive include-agent-circuit-id—Formats calling number AVP in descriptive format to include interface information and the agent-circuit-id suboption
  - descriptive include-agent-circuit-id include-agent-remote-id—Formats calling number AVP in descriptive format to include interface information and both the agent-circuit-id and agent-remote-id suboptions
  - descriptive include-agent-remote-id—Formats calling number AVP in descriptive format to include interface information and the agent-remote-id
  - fixed—Formats calling number AVP to use a fixed format of up to 15 characters consisting of all ASCII fields, similar to the fixed format of RADIUS attribute 31 (Calling-Station-Id):
    - Format for ATM interfaces:  
      *systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) *VPI* (3 bytes) *VCI* (5 bytes)
    - Format for Ethernet interfaces:  
      *systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) *VLAN* (8 bytes)
    - Format for serial interfaces:

*systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) 0 (8 bytes)

- In the case of PPP terminated from LNS, the Calling-Station-Id attribute is the value passed as the calling-station AVP.
- fixed-adapter-embedded—Formats calling number AVP to use a fixed format of up to 15 characters consisting of all ASCII fields with a 1-byte *slot* field, 1-byte *adapter* field, and 1-byte *port* field:
  - Format for ATM interfaces:  
*systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte)  
*VPI* (3 bytes) *VCI* (5 bytes)
  - Format for Ethernet interfaces:  
*systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte)  
*VLAN* (8 bytes)
  - Format for serial interfaces:  
*systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte)  
0 (8 bytes)
  - For E120 and E320 routers, *adapter* is the number of the bay in which the I/O adapter (IOA) resides, either 0 (representing the right IOA bay on the E120 router and the upper IOA bay on the E320 router) or 1 (representing the left IOA bay on the E120 router or the lower IOA bay on the E320 router). For ERX7xx models, ERX14xx models, and ERX310 routers, which do not use IOAs, *adapter* is always shown as 0.
  - Slot numbers 0 through 16 are shown as ASCII characters in the 1-byte slot field.
- fixed-adapter-new-field—Formats calling number AVP to use a fixed format of up to 17 characters consisting of all ASCII fields with a 2-byte *slot* field, 1-byte *adapter* field, and 2-byte *port* field:
  - Format for ATM interfaces:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes)  
*VPI* (3 bytes) *VCI* (5 bytes)
  - Format for Ethernet interfaces:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes) *VLAN* (8 bytes)
  - Format for serial interfaces:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes)  
0 (8 bytes)
  - For E120 routers and E320 routers, *adapter* is the number of the bay in which the IOA resides, either 0 or 1. For ERX7xx models, ERX14xx models, and ERX310 routers, which do not use IOAs, *adapter* is always shown as 0.
  - Slot numbers 0 through 16 are shown as integers in the 2-byte *slot* field.
- include-agent-circuit-id—Formats calling number AVP to include only the agent-circuit-id suboption

- **include-agent-circuit-id include-agent-remote-id**—Formats calling number AVP to include both the agent-circuit-id and agent-remote-id suboptions
- **include-agent-remote-id**—Formats calling number AVP to include only the agent-remote-id suboption
- **stacked**—Includes a 4-byte stacked VLAN (S-VLAN) ID in the fixed, fixed-adapter-embedded, and fixed-adapter-new-field calling number AVP formats for Ethernet interfaces; by default, these formats do not include the S-VLAN ID unless you specify the optional **stacked** keyword:
  - Format for Ethernet interfaces that use **fixed**:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) *S-VLAN* (4 bytes) *VLAN* (4 bytes)
  - Format for Ethernet interfaces that use **fixed-adapter-embedded**:  
*systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte) *S-VLAN* (4 bytes) *VLAN* (4 bytes)
  - Format for Ethernet interfaces that use **fixed-adapter-new-field**:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes) *S-VLAN* (4 bytes) *VLAN* (4 bytes)

**Mode**    Global Configuration

## aaa tunnel calling-number-format-fallback

**Syntax**   aaa tunnel calling-number-format-fallback  
               { descriptive |  
               fixed [ stacked ] |  
               fixed-adapter-embedded [ stacked ] |  
               fixed-adapter-new-field [ stacked ] }  
  
               no aaa tunnel calling-number-format-fallback

**Release Information**   Command introduced in JunosE Release 8.1.0.  
**fixed-adapter-embedded**, **fixed-adapter-new-field**, and **stacked** keywords added in JunosE Release 10.0.0.

**Description**   Configures the fallback format for the tunnel calling number to be passed by the E Series L2TP access concentrator (LAC) to the L2TP network server (LNS) in the L2TP Calling Number attribute value pair (AVP) 22 when the PPPoE agent circuit ID is null or unavailable. The fallback format is used only when the configured calling number format includes either or both of the agent-circuit-id and agent-remote-id suboptions. The **no** version restores the default fallback format, descriptive.

- Options**
- **descriptive**—Configures the fallback format in descriptive format that includes only interface information
  - **fixed**—Configures the fallback format in a fixed format of up to 15 characters consisting of all ASCII fields, similar to the fixed format of RADIUS attribute 31 (Calling-Station-Id):
    - Fallback format for ATM interfaces:  
       *systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) *VPI* (3 bytes)  
       *VCI* (5 bytes)
    - Fallback format for Ethernet interfaces:  
       *systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) *VLAN* (8 bytes)
    - Fallback format for serial interfaces:  
       *systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) 0 (8 bytes)
    - In the case of PPP terminated from LNS, the Calling-Station-Id attribute is the value passed as the calling-station AVP.
  - **fixed-adapter-embedded**—Configures the fallback format in a fixed format of up to 15 characters consisting of all ASCII fields with a 1-byte *slot* field, 1-byte *adapter* field, and 1-byte *port* field:
    - Fallback format for ATM interfaces:  
       *systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte)  
       *VPI* (3 bytes) *VCI* (5 bytes)
    - Fallback format for Ethernet interfaces:  
       *systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte)  
       *VLAN* (8 bytes)

- Fallback format for serial interfaces:  
*systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte)  
0 (8 bytes)
- For E120 routers and E320 routers, *adapter* is the number of the bay in which the I/O adapter (IOA) resides, either 0 (representing the right IOA bay on the E120 router and the upper IOA bay on the E320 router) or 1 (representing the left IOA bay on the E120 router or the lower IOA bay on the E320 router). For ERX7xx models, ERX14xx models, and ERX310 routers, which do not use IOAs, *adapter* is always shown as 0.
- Slot numbers 0 through 16 are shown as ASCII characters in the 1-byte slot field.
- **fixed-adapter-new-field**—Configures the fallback format in a fixed format of up to 17 characters consisting of all ASCII fields with a 2-byte *slot* field, 1-byte *adapter* field, and 2-byte *port* field:
  - Fallback format for ATM interfaces:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes)  
*VPI* (3 bytes) *VCI* (5 bytes)
  - Fallback format for Ethernet interfaces:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes) *VLAN* (8 bytes)
  - Fallback format for serial interfaces:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes)  
0 (8 bytes)
  - For E120 routers and E320 routers, *adapter* is the number of the bay in which the IOA resides, either 0 or 1. For ERX7xx models, ERX14xx models, and ERX310 routers, which do not use IOAs, *adapter* is always shown as 0.
  - Slot numbers 0 through 16 are shown as integers in the 2-byte *slot* field.
- **stacked**—Includes a 4-byte stacked VLAN (S-VLAN) ID in the fixed, fixed-adapter-embedded, and fixed-adapter-new-field fallback formats for Ethernet interfaces; by default, these formats do not include the S-VLAN ID unless you specify the optional **stacked** keyword:
  - Fallback format for Ethernet interfaces that use **fixed**:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *port* (1 byte) *S-VLAN* (4 bytes) *VLAN* (4 bytes)
  - Fallback format for Ethernet interfaces that use **fixed-adapter-embedded**:  
*systemName* (up to 4 bytes) *slot* (1 byte) *adapter* (1 byte) *port* (1 byte) *S-VLAN* (4 bytes) *VLAN* (4 bytes)
  - Fallback format for Ethernet interfaces that use **fixed-adapter-new-field**:  
*systemName* (up to 4 bytes) *slot* (2 bytes) *adapter* (1 byte) *port* (2 bytes) *S-VLAN* (4 bytes) *VLAN* (4 bytes)

**Mode**    Global Configuration



## aaa tunnel client-name

---

**Syntax**    `aaa tunnel client-name name`  
              `no aaa tunnel client-name`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the default tunnel client name. If the tunnel client name is not included in the tunnel attributes that are returned from the domain map or authentication server, the router uses the default name. The **no** version deletes the client name.

**Options**    • *name*—Default tunnel client name; a string of up to 32 characters

**Mode**    Global Configuration

## aaa tunnel-group

---

**Syntax** [ no ] aaa tunnel-group *groupName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an AAA tunnel group and changes the mode to Tunnel Group Configuration mode. In Tunnel Group Configuration mode, you can add up to 31 tunnel definitions. The **no** version deletes the AAA group tunnel configuration from the router.

**Options** • *groupName*—String of up to 64 characters (no spaces)

**Mode** Global Configuration

## aaa tunnel ignore

---

**Syntax**    `aaa tunnel ignore { nas-port | nas-port-type } { enable | disable }`  
`no aaa tunnel ignore { nas-port | nas-port-type }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies whether to use the tunnel peer's NAS-Port [5] and NAS-Port-Type [61] attributes. The **no** version negates the command or restores the default of enable.

- Options**
- `nas-port`—Configures the tunnel peer's supplied nas-port value
  - `nas-port-type`—Configures the tunnel peer's supplied nas-port-type value
  - `enable`—Implements the feature; this is the default setting
  - `disable`—Disables the feature

**Mode**    Global Configuration

## aaa tunnel nas-port-method

---

**Syntax**   aaa tunnel nas-port-method cisco-avp  
             no aaa tunnel nas-port-method

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Configures the tunnel's default NAS port type to provide limited support for a Cisco proprietary vendor-specific method when configuring the LAC to LNS NAS port identification transfer mechanism. The **no** version disables the command.



.....  
**NOTE:** Use of this feature is not recommended and continued compatibility cannot be guaranteed.  
.....

**Mode**   Global Configuration

## aaa tunnel password

---

**Syntax**    `aaa tunnel password name`  
              `no aaa tunnel password`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the default tunnel password. If the tunnel password is not included in the tunnel attributes that are returned from the domain map or authentication server, the router uses the default password. The **no** version deletes the password.

**Options**    • *name*—Default tunnel password; a string of up to 32 characters

**Mode**    Global Configuration

## aaa tunnel switch-profile

---

**Syntax**   aaa tunnel switch-profile *profileName*

no aaa tunnel switch-profile

**Release Information**   Command introduced in JunosE Release 7.2.0.

**Description**   Applies a default L2TP tunnel switch profile to a virtual router. The default tunnel switch profile defines the L2TP tunnel switching behavior for the interfaces to which this profile is assigned. The router uses the default tunnel switch profile if the tunnel attributes returned from an AAA domain map or tunnel group or from a RADIUS authentication server do not include a named tunnel switch profile. The **no** version removes the default tunnel switch profile assignment from the virtual router.

**Options**

- *profileName*—Name of the default tunnel switch profile; a string of up to 64 alphanumeric characters

**Mode**   Global Configuration

```
no aaa tunnel tx-connect-speed-method
```

Mode Global Configuration

## aaa user accounting interval

---

**Syntax**    `aaa user accounting interval period`

`no aaa user accounting interval`

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Specifies the default user accounting interval used on the virtual router. This router uses this value for users when no value is specified in the RADIUS Acct-Interim-Interval attribute (RADIUS attribute 85). The **no** version restores the default setting of 0, which turns off interim accounting for users attached to this virtual router.



.....  
**NOTE:** This command and the **aaa service accounting interval** command replace the deprecated **aaa accounting interval** command, which may be removed completely in a future release.  
.....

**Options**    • *period*—Accounting interval in minutes in the range 10–1440, which sets the time period between accounting updates for users on this virtual router; 0 is the default

**Mode**    Global Configuration



## aaa virtual-router

---

**Syntax**    `aaa virtual-router indexInteger vrName`  
              `no aaa virtual-router indexInteger`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    For AAA broadcast accounting, adds a virtual router to a virtual router group. The **no** version with the *indexInteger* parameter removes a specific virtual router from the virtual router group.

- Options**
- *indexInteger*—Number in the range 1–4 that indicates the virtual router's listing in the virtual router group; the *indexInteger* is used in the **no** version of the command to delete a particular virtual router from the group
  - *vrName*—Name of virtual router that can receive AAA broadcast accounting packets.

**Mode**    VR Group Configuration

## aaa wins

---

**Syntax**    `aaa wins { primary | secondary } ipAddress`  
`no aaa wins { primary | secondary }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IP address of the WINS name server. The **no** version sets the corresponding address to 0.

- Options**
- `primary`—Specifies the primary WINS name server
  - `secondary`—Specifies the secondary WINS name server
  - `ipAddress`—IP address of the name server

**Mode**    Global Configuration

## access-class in

---

**Syntax**    `access-class listName in`  
              `no access-class [ listName ] in`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Restricts incoming connections between a particular virtual terminal line and the addresses in an access list. The **no** version removes access restrictions.

**Options**    • *listName*—Name of the access list

**Mode**    Line Configuration

## access-list

---

**Syntax** Standard IP access list:

```
access-list accessListName { permit | deny }  
{ srcIP srcWildcard | [ host ] srcIPHost | any } [ log ]
```

```
no access-list accessListName [ { permit | deny }  
{ srcIP srcWildcard | [ host ] srcIPHost | any } [ log ] ]
```

Extended IP access list:

```
access-list accessListName { permit | deny } ip { srcIP srcWildcard |  
host srcIPHost | any } { dstIP dstWildcard | host dstIPHost | any } [ log ]
```

```
no access-list accessListName [ { permit | deny } ip { srcIP srcWildcard |  
host srcIPHost | any } { dstIP dstWildcard | host dstIPHost | any } [ log ] ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a standard or extended IP access list. The extended access list enables you to specify a destination address or host, precedence, and type of service. This command imposes an implicit last rule of “deny ip any any” to deny all routes that do not match previous rules in the access list. The **no** version removes the IP access list, the specified entry in an access list, or the log for a specified entry.

- Options**
- *accessListName*—String of up to 32 alphanumeric characters
  - permit—Permits access if the conditions are matched
  - deny—Denies access if the conditions are matched
  - *srcIP*—Source IP address from which the packet is being sent
  - *srcWildcard*—Wildcard mask IP address
  - host—Identifies the address as a host
  - *srcIPHost*—Source host IP address; assumes a wildcard mask of 0
  - any—Creates an address of 0.0.0.0 with a wildcard mask of 255.255.255.255
  - *dstIP*—Destination IP address
  - *dstWildcard*—Wildcard mask IP address for destination
  - *dstIPHost*—Destination host IP address to which the packet is being sent
  - log—Logs an Info event into the ipAccessList log whenever the access-list rule is matched

**Mode** Global Configuration

## accounting

---

**Syntax**    `accounting { exec | commands level } listName`

`no accounting { exec | commands level }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables AAA accounting services on a console line, a virtual terminal line, or a group of lines and applies the specified accounting method list. The **no** version restores the default method list.



**NOTE:** To disable accounting for a console line or virtual terminal line, specify a nonexistent accounting method list name (for example, `noAccounting`).

- Options**
- **exec**—Specifies that accounting information is captured for User Exec terminal sessions on the line
  - **level**—Privilege level of User Exec mode commands for which accounting information is captured; in the range 0–15
  - **listName**—Named method list used to specify how accounting is performed

**Mode**    Line Configuration

## action-type

---

**Syntax** [ no | default ] action-type { enable | disable }

**Release Information** Command introduced in JunosE Release 12.1.0.

**Description** Includes or excludes the attributes in the RADIUS request message. The **no** version restores the default setting. By default, the action-type is disabled.

**Options**

- enable—Includes the attribute in the request packets
- disable—Excludes the attribute in the request packets

**Mode** RADIUS Per-Profile List Configuration, AAA Per-Profile List Configuration

## adapter accept

**Syntax** `adapter accept adapterSpecifier`

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Erases from NVS the type and configuration of the previous I/O adapter (IOA) in the specified IOA bay, and allows you to configure a new IOA. Issue this command after you have installed a different type of IOA in an IOA bay. You can use this command only when the state of the IOA is not present or disabled (mismatch). There is no **no** version.



**NOTE:** Issuing this command reboots the line module associated with the IOA, but it does not accept its configuration.

To accept the configuration of the line module and its associated IOAs, issue the `slot accept` command.

- Options**
- *adapterSpecifier*—Particular IOA in the format *slot/adapter*:
    - *slot*—Number of the chassis slot; for E120 routers, in the range 0–5; for E320 routers, in the range 0–5 or 11–16
    - *adapter*—Identifier for the IOA within the chassis slot, either 0 or 1, where:
      - 0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).
      - 1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).

**Mode** Global Configuration

## adapter disable

---

**Syntax**    adapter disable *adapterSpecifier*

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Disables the IOA installed in the specified IOA bay. There is no **no** version.



**NOTE:** For IOAs that support hot-swapping, issuing this command does not reboot the line module. For IOAs that do not support hot-swapping, issuing this command reboots the line module associated with the IOA, but it does not disable it.

To disable the line module and its associated IOAs, issue the slot disable command.

- Options**
- *adapterSpecifier*—Particular IOA in the format *slot/adapter*:
    - *slot*—Number of the chassis slot; for E120 routers, in the range 0–5; for E320 routers, in the range 0–5 or 11–16
    - *adapter*—Identifier for the IOA within the chassis slot, either 0 or 1, where:
      - 0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).
      - 1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).

**Mode**    Global Configuration



## adapter enable

**Syntax** `adapter enable adapterSpecifier`

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables the IOA installed in the specified IOA bay. There is no **no** version.



**NOTE:** For IOAs that support hot-swapping, issuing this command does not reboot the line module. For IOAs that do not support hot-swapping, issuing this command reboots the line module associated with the IOA, but it does not enable it.

To enable the line module and its associated IOAs, issue the `slot enable` command.

- Options**
- *adapterSpecifier*—Particular IOA in the format *slot/adapter*:
    - *slot*—Number of the chassis slot; for E120 routers, in the range 0–5; for E320 routers, in the range 0–5 or 11–16
    - *adapter*—Identifier for the IOA within the chassis slot, either 0 or 1, where:
      - 0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).
      - 1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).

**Mode** Global Configuration

## adapter erase

---

**Syntax**    `adapter erase adapterSpecifier`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Erases from NVS the type and configuration of the previous IOA in the specified IOA bay, and allows you to configure a new IOA. Issue this command before you install a different type of IOA in an IOA bay. There is no **no** version.



.....  
**NOTE:** Issuing this command reboots the line module associated with the IOA, but it does not erase its configuration.

To erase the configuration of the line module and its associated IOAs, issue the `slot erase` command.

.....

- Options**
- *adapterSpecifier*—Particular IOA in the format *slot/adapter*:
    - *slot*—Number of the chassis slot; for E120 routers, in the range 0–5; for E320 routers, in the range 0–5 or 11–16
    - *adapter*—Identifier for the IOA within the chassis slot, either 0 or 1, where:
      - 0 indicates that the IOA is installed in the right IOA bay (E120 router) or the upper IOA bay (E320 router).
      - 1 indicates that the IOA is installed in the left IOA bay (E120 router) or the lower IOA bay (E320 router).

**Mode**    Global Configuration

## address

**Syntax** To set the tunnel endpoint address:

`address serverAddress`

`no address`

To configure RIP:

`[ no ] address { ipAddress | unnumbered interfaceType interfaceSpecifier }`

To configure NAT address pool ranges:

`[ no ] address startIpAddress endIpAddress`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** From Domain Map Tunnel Configuration mode, sets the tunnel endpoint address of an L2TP tunnel. The **no** version removes the address of the tunnel.

From Tunnel Group Tunnel Configuration mode, sets the tunnel endpoint address of an L2TP tunnel. The **no** version removes the address of the tunnel.

From Interface Configuration or Subinterface Configuration mode, configures RIP to run on the interface specified by the IP address or on an unnumbered interface. Uses the default values: send version is RIP version 1, receive version is RIP version 1 and version 2, authentication is not enabled. The **no** version deletes the RIP interface. Use the **address** commands to configure RIP attributes on the network.

From IP NAT Pool Configuration mode, configures NAT IP address pool ranges. The **no** version removes the range from the current NAT address pool.

- Options**
- *serverAddress*—IP address of the LNS endpoint
  - *ipAddress*—Address of IP interface where RIP will be run
  - *unnumbered*—Specifies that RIP will be run on an unnumbered interface
    - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *startIpAddress*—Starting IP address (inclusive) of the NAT pool range you are creating
  - *endIpAddress*—Ending IP address (inclusive) of the NAT pool range you are creating

**Mode** Address Family Configuration (RIP), Domain Map Tunnel Configuration, IP NAT Pool Configuration, Router Configuration (RIP), Tunnel Group Tunnel Configuration

## address area

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
area { *areald* | *arealdInt* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an interface on which OSPF runs in the specified area, on top of the IP interface at the specified IP address. Uses the default values. The **no** version deletes OSPF interfaces. If the OSPF network was previously specified with the **network area** command, the OSPF interface already exists, and you do not need to use this command, unless you want to change the area of the OSPF interface to an area different from the one specified by the **network area** command.



**NOTE:** Before you issue this command, you must first configure an interface with the IP address specified by *ipAddress* or an interface configured as unnumbered.

You must issue this command before issuing any other OSPF address command.

- Options**
- *ipAddress*—IP address of the interface on which OSPF will be run
  - unnumbered—Configures OSPF on an unnumbered interface
    - *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5
  - *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 1–4294967295

**Mode** Router Configuration

## address authentication key

---

**Syntax** address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
 authentication key [ 0 | 8 ] *authkey*

no address [ *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* ]  
 authentication key

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the password for text authentication and the key for MD5 authentication. The **no** version clears the key for the interface. Supported only in RIP version 2. Authentication is disabled by default.

- Options**
- *ipAddress*—Address of IP interface where RIP will be run
  - unnumbered—Specifies that RIP will be run on an unnumbered interface
    - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - 0—Indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authkey*—Password sent with RIP messages or the key used to encrypt/decrypt RIP messages, depending on the authentication mode set for this interface

**Mode** Address Family Configuration, Router Configuration

## address authentication-key

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
authentication-key [ 0 | 8 ] *authKey*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns a password used by neighboring routers that are using OSPF simple password authentication. The **no** version deletes the password.



NOTE: You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - 0—Indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authKey*—Password, string of up to 8 characters

**Mode** Router Configuration

## address authentication message-digest

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* } authentication message-digest

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that MD5 authentication is used for the OSPF interface. The **no** version sets authentication for the interface to none, but leaves any configured MD5 key intact.



**NOTE:** You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Router Configuration

## address authentication mode

---

**Syntax**    address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
             authentication mode { text | md5 *keyID* }

             no address [ *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* ]  
             authentication mode

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the type of authentication used on this interface. The **no** version removes authentication from the interface. Supported only in RIP version 2. Authentication is disabled by default.

- Options**
- *ipAddress*—Address of IP interface where RIP will be run
  - unnumbered—Specifies RIP will be run on an unnumbered interface
    - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - text—Simple text password is sent with each RIP message. If the password is not possessed by neighbors, the message is rejected.
  - md5—MD5 message-digest algorithms are used to encrypt and compress the RIP message.
  - *keyID*—Number identifying the MD5 key. Neighbors must share the MD5 key to decrypt the message and encrypt the response.

**Mode**    Address Family Configuration, Router Configuration



## address authentication-none

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
authentication-none

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that no authentication is to be used for the OSPF interface. The **no** version has no effect.



**NOTE:** You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Router Configuration

## address bfd-liveness-detection

---

**Syntax** address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
bfd-liveness-detection [ minimum-interval *minInterval* |  
[ minimum-receive-interval *minRecInterval* ]  
[ minimum-transmit-interval *minTransInterval* ] ] [ multiplier *multValue* ]  
  
no address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
bfd-liveness-detection

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Enables BFD (bidirectional forwarding detection) on an interface running RIP and defines BFD values to be negotiated between peers for detection of IP data path failures. The **no** version disables BFD on the RIP interface.

- Options**
- *ipAddress*—Address of IP interface where RIP will be run
  - unnumbered—Specifies that RIP will be run on an unnumbered interface
    - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *minInterval* —Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode** Address Family Configuration, Router Configuration

## address cost

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* } cost *intfCost*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a cost metric for an OSPF interface. Used in the calculation of the SPF routing table. The **no** version resets the path cost to the default.



**NOTE:** You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *intfCost*—Link-state metric cost; a number in the range 0–65535; default value is 10

**Mode** Router Configuration

## address dead-interval

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
dead-interval *deadInterval*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the time period that the router's neighbors should wait without seeing hello packets from the router before they declare the router to be down. The **no** version resets the dead interval to its default.



NOTE: You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *deadInterval*—Number in the range 0–2147483647 seconds; default value is 40 seconds

**Mode** Router Configuration

## address-family

**Syntax** For BGP:

```
[ no ] address-family { { ipv4 | ipv6 } [ unicast | multicast
| [ unicast ] vrf vrfName ] |
{ vpv4 | vpv6 } [ unicast ] | l2vpn [ signaling ] | route-target [ signaling ] |
vpls vplsName | vpws vpwsName }
```

For IS-IS:

```
[ no ] address-family ipv6 [ unicast | multicast | unicast multicast ]
```

For RIP:

```
[ no ] address-family ipv4 [ unicast ] vrf vrfName
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**l2vpn** and **signaling** keywords added in JunosE Release 7.1.0.  
**vpls** keyword and *vplsName* variable added in JunosE Release 7.1.0.  
**vpws** keyword and *vpwsName* variable added in JunosE Release 8.1.0.  
**route-target signaling** keywords and IS-IS IPv6 version added in JunosE Release 8.2.0.

**Description** For BGP, configures the router to exchange addresses for the specified address family. This command takes effect immediately.

- For the IPv4 address family, configures the router or a specific VRF to exchange IPv4 addresses in unicast, multicast, or VPN mode.
- For the IPv6 address family, configures the router or a specific VRF to exchange IPv6 addresses in unicast, multicast, or VPN mode.
- For the L2VPN address family, configures a router to exchange layer 2 NLRI for all VPLS instances and all L2VPN (VPWS) instances.
- For the VPLS address family, configures the router to exchange layer 2 NLRI for the VPLS address family for a specified VPLS instance.
- For the VPWS address family, configures the router to exchange layer 2 NLRI for the VPWS address family for a specified L2VPN (VPWS) instance.
- For the route-target address family, configures the router to exchange route-target membership NLRI (RT-MEM-NLRI) that includes information about membership in VPN route-target extended communities.

For IS-IS, configures IS-IS to exchange IPv6 addresses.

For RIP, configures RIP in a specific VRF to exchange IPv4 addresses.

For all routing protocols, the **no** version removes the address family.

- Options**
- **ipv4**—Specifies sessions that carry standard IPv4 address prefixes (default)
  - **ipv6**—Specifies sessions that carry IPv6 address prefixes

- **multicast**—Specifies multicast prefixes
- **unicast**—Specifies unicast prefixes (default)
- **vrfName**—Name of the VRF; string of 1–32 alphanumeric characters
- **vpn4**—Specifies sessions that carry customer VPN-IPv4 prefixes, each of which has been made globally unique by adding an 8-byte route distinguisher
- **vpn6**—Specifies sessions that carry customer VPN-IPv6 prefixes, each of which has been made globally unique by adding an 8-byte route distinguisher
- **l2vpn**—Specifies sessions that carry L2VPN reachability information
- **l2vpn signaling**—Specifies BGP signaling of L2VPN reachability information; currently, you can omit the **signaling** keyword with no adverse effects
- **route-target**—Specifies sessions that carry route-target membership information
- **route-target signaling**—Specifies BGP signaling of route-target membership information; currently, this can be omitted with no adverse effects
- **vplsName**—Name of a VPLS instance for which you are specifying the L2VPN address family; must be issued for each separate VPLS instance
- **vpwsName**—Name of a layer 2 VPN (VPWS) instance for which you are specifying the L2VPN address family; must be issued for each separate L2VPN instance

**Mode** Router Configuration

**Related Documentation**

- [BGP Signaling for L2VPNs Overview](#)
- [BGP Signaling for VPLS Overview](#)

## address hello-interval

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
hello-interval *helloInterval*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the interval between hello packets that the router sends on the interface. The **no** version resets the hello interval to its default.



**NOTE:** You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *helloInterval*—Number in the range 1–65535 seconds; default value is 10 seconds

**Mode** Router Configuration

## address message-digest-key md5

---

**Syntax** address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
message-digest-key *keyID* md5 [ 0 | 8 ] *msgDigestKey*

no address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
message-digest-key *keyID*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables OSPF MD5 authentication and configures the MD5 key. The **no** version deletes an MD5 key.



**NOTE:** If all the MD5 keys have been deleted, the authentication type is still MD5, but you need to configure MD5 keys.

To disable MD5 authentication for the interface, use the [address authentication-none](#) command.

You must issue the [address area](#) command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5
  - *keyID*—Key identifier in the range 1–255
  - md5—Specifies use of the MD5 algorithm
  - 0—Indicates the *msgDigestKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *msgDigestKey* is entered in encrypted form (ciphertext)
  - *msgDigestKey*—OSPF password; string of up to 16 alphanumeric characters

**Mode** Router Configuration



## address network

**Syntax** address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
 network { broadcast | non-broadcast | point-to-point }  
 no address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* } network

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the OSPF network type for the specified interface to something other than the default for the network medium. The **no** version restores the default value for the medium.



**NOTE:** You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5
  - broadcast—Sets network type to broadcast
  - non-broadcast—Sets network type to NBMA
  - point-to-point—Sets network type to point-to-point

**Mode** Router Configuration

## address passive-interface

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
passive-interface

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables the transmission of routing updates on an interface. OSPF routing information is neither sent nor received through the specified router interface. The specified interface address appears as a stub network in the OSPF domain. The **no** version reenables the transmission of routing updates.



NOTE: You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5

**Mode** Router Configuration

## address-pool-name

---

**Syntax** address-pool-name *poolName*

no address-pool-name

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an address pool name to associate with the domain name being configured. The **no** version removes the pool name.

**Options** • *poolName*—Name of the pool to associate with the domain name

**Mode** Domain Map Configuration

## address priority

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
priority *intfPriority*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the router priority. Used in determining the designated router for the particular network. This designation only applies to multi-access networks. Every broadcast and nonbroadcast multiaccess network has a designated router. The **no** version restores the default value.



NOTE: You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5
  - *intfPriority*—Priority value, an 8-bit number in the range 1–255; default value is 1

**Mode** Router Configuration

## address receive version

**Syntax** address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
 receive version { 1 | 2 | 1 2 | 2 1 | off }  
 no address [ *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* ] receive version

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Restricts the RIP version that the router can receive on an interface. The **no** version sets the interface back to the default value, receiving both RIP version 1 and version 2.

- Options**
- *ipAddress*—Address of IP interface where RIP will be run
  - unnumbered—Specifies that RIP will be run on an unnumbered interface
    - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - 1—Specifies RIP version 1 only
  - 2—Specifies RIP version 2 only
  - 1 2—Specifies RIP version 1 and version 2; the default value
  - 2 1—Specifies RIP version 2 and version 1
  - off—Turns reception off

**Mode** Address Family Configuration, Router Configuration

## address retransmit-interval

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
retransmit-interval *retransInterval*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the time between LSA retransmissions for the interface when an acknowledgment for the LSA is not received. The **no** version restores the default value.



.....  
**NOTE:** You must issue the **address area** command before issuing this command.  
.....

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5
  - *retransInterval*—Number in the range 0–3600 seconds; default value is 5 seconds

**Mode** Router Configuration

## address send version

**Syntax** address { *ipAddress* | unnumbered *interfaceType interfaceSpecifier* }  
 send version { 1 | 2 | 1 2 | 2 1 | off }  
 no address [ *ipAddress* | unnumbered *interfaceType interfaceSpecifier* ] send version

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Restricts the RIP version that the router can send on an interface. The **no** version sets the interface back to the default value, sending only RIP version 1.

- Options**
- *ipAddress*—Address of IP interface where RIP will be run
  - unnumbered—Specifies that RIP will be run on an unnumbered interface
    - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - 1—Specifies RIP version 1 only
  - 2—Specifies RIP version 2 only
  - 1 2—Specifies RIP version 1 and version 2
  - 2 1—Specifies RIP version 2 and version 1
  - off—Turns reception off

**Mode** Address Family Configuration, Router Configuration

## address transmit-delay

---

**Syntax** [ no ] address { *ipAddress* | unnumbered *interfaceType* *interfaceSpecifier* }  
transmit-delay *transmDelay*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the estimated time it takes to transmit a link-state update packet on the interface. The **no** version restores the default value.



NOTE: You must issue the **address area** command before issuing this command.

- Options**
- *ipAddress*—OSPF interface address previously specified with the **address** command
  - unnumbered—Indicates that OSPF is running on an unnumbered interface previously specified with the **address** command
    - *interfaceType*—Interface type; see “Interface Types and Specifiers” on page 5
    - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *transmDelay*—Link-state transmit delay, a number in the range 0–3600 seconds; default value is 1 second

**Mode** Router Configuration



## adjustment-factor

---

**Syntax**    adjustment-factor *dslType value*  
              no adjustment-factor *dslType*

**Release Information**    Command introduced in JunosE Release 9.1.0.

**Description**    Configures an adjustment factor that is applied globally to the ANCP-reported downstream and upstream data rate for all subscribers of a particular DSL line type. The adjusted data rate results in an accurate QoS shaping rate. The **no** version restores the default, wherein the rate is not adjusted.

**Options**

- *dslType*—Type of DSL subscriber line for which the data rate is adjusted by the specified QoS adjustment factor: **adsl1**, **adsl2**, **adsl2+**, **vdsl**, **vdsl2**, or **sds**
- *value*—QoS adjustment factor applied to upstream or down stream data rates for the DSL type; a percentage in the range 1–100

**Mode**    L2C Configuration

## advertise-passive-only

---

**Syntax** [no] advertise-passive-only

**Release Information** Command introduced in JunosE Release 12.0.0.

**Description** Configures IS-IS to only advertise IP prefixes that belong to passive interfaces. The **no** version restores the default, in which all entries in the LSP database are advertised.

**Mode** Router Configuration

**Related Documentation**

- *Advertising IP Prefixes of Passive Interfaces* in the *IP, IPv6, and IGP Configuration Guide*

## agent context-name

---

**Syntax**    agent context-name *contextName* [ wildcard ] [ limit *contextNameLimit* ]  
              no agent

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the virtual router SNMP agent on which you want to poll MIB objects. The **no** version returns the context name to the default context (virtual router).

**Options**    • *contextName*—Context name of the agent



.....  
**NOTE:** The *contextName* value is the virtual router number in the order the virtual router was created (for example, router1, router2, and so on). Use the **show snmp agent** command to obtain the context name for the virtual router.  
.....

- wildcard—Specifies that the context name is a wildcard value
- *contextNameLimit*—Maximum number of agents to be polled

**Mode**    SNMP Trigger Configuration

## aggregate-address

---

**Syntax** [ no ] aggregate-address { *address mask* | *ipv6Prefix* }  
[ as-set | summary-only | attribute-map *attributeMapTag* |  
advertise-map *advertiseMapTag* | suppress-map *suppressMapName* ]\*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an aggregate entry in a BGP routing table. The **no** version removes the aggregate.

- Options**
- *address*—Aggregate IPv4 address
  - *mask*—Aggregate IPv4 mask
  - *ipv6Prefix*—Aggregate IPv6 prefix
  - **as-set**—If the **as-set** option is not specified, the path attributes of the aggregate route are set in the same way as locally originated routes, except that the `atomic_aggregate` and `aggregator` attributes are added. If the **as-set** option *is* used, the path attributes of the aggregate route are determined by combining the path attributes of the aggregated routes as described in *RFC 4271—A Border Gateway Protocol 4 (BGP-4)*. If the **as-set** option is used, the path attributes of the aggregate route may change whenever one of the aggregated routes changes, causing the aggregate route to be readvertised.
  - **summary-only**—Filters all more specific routes from updates. **summary-only** not only creates the aggregate route but also suppresses advertisements of more-specific routes to all neighbors. If you only want to suppress advertisements to certain neighbors, you may use the **neighbor distribute-list** command, with caution. If a more-specific route leaks out, all BGP speakers will prefer that route over the less-specific aggregate you are generating (using longest-match routing). Alternatively, you can use the **suppress-map** keyword to suppress specific routes.
  - *attributeMapTag*—String of up to 32 characters that identifies the route map used to set the attributes of the aggregate route
  - *advertiseMapTag*—String of up to 32 characters that identifies the route map used to set the routes to create AS-SET origin communities in the range
  - *suppressMapName*—String of up to 32 characters that identifies a route map that filters routes to be suppressed
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Address Family Configuration, Router Configuration

## aggregation-node

---

<b>Syntax</b>	aggregation-node { <i>nodeValue</i>   atm   atm-vc   atm-vp <i>vpValue</i>   ethernet   fr-vc   forwarding   ppp-interface   svlan <i>svlanValue</i>   vlan }  no aggregation-node
<b>Release Information</b>	Command introduced in JunosE Release 8.0.0. <b>ppp-interface</b> keyword added in JunosE Release 10.3.0.
<b>Description</b>	Configures the aggregation node value. The <b>no</b> version restores the default value, where the forwarding interface becomes the aggregation node.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>nodeValue</i>— Aggregation node number in the range 1–65535</li><li>• <i>vpValue</i>—ATM VPI number in the range 0–255</li><li>• <i>svlanValue</i>—S-VLAN ID number in the range 0–4095</li></ul>
<b>Mode</b>	Policy Parameter Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Creating a Classifier Group for a Policy List</li></ul>

## aggressive-mode

---

**Syntax**    aggressive-mode { accepted | requested | required }  
              no aggressive-mode

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **accepted**, **requested**, and **required** keywords added in JunosE Release 7.3.0.

**Description**    Enables aggressive mode negotiation for the tunnel. The **no** version restores the default, no aggressive mode.

- Options**
- **accepted**—Accepts aggressive mode when proposed by peers
  - **requested**—Requests aggressive mode when negotiating with peers
  - **required**—Only requests and accepts aggressive mode when negotiating with peers

**Mode**    IKE Policy Configuration

## allow

---

**Syntax** [ no ] allow *domainName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the domain names that are to be allowed access to AAA authentication. The **no** version negates the command.

**Options** • *domainName*—Name of the domain; maximum of 64 characters

**Mode** AAA Profile Configuration

## append-after

---

**Syntax**    append-after *indexNumber* next-address *ipAddress* [ [ mask ] *ipMask* ] [ loose ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Adds a next hop after a particular index in the MPLS explicit path. The sequence numbers for existing hops after the index adjust automatically. There is no **no** version.

**Options**

- *indexNumber*—Number of a node in an ordered set of abstract nodes
- *ipAddress*—Address of the next hop
- *ipMask*—[ not currently used ] mask for the next adjacent address
- loose—Indicates the node is not necessarily directly connected (adjacent) to the previous node in the path. If loose is not configured, the configuration defaults to strict. Strict indicates that the node is directly connected to the previous node.

**Mode**    Explicit Path Configuration



## application

---

**Syntax**    `application applicationType1 [ applicationType2 [ applicationType3 ] ]`  
`no application`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the type of application that is secured by connections created with this IPSec transport profile. You can specify multiple application types. The **no** version restores the default application, L2TP.

**Options**    • *applicationType*—One of the following application types:

- *dvmrp*—Secures DVMRP traffic.
- *gre*—Secures GRE traffic.
- *l2tp*—Secures L2TP traffic; this is the default application
- *l2tp-nat-passthrough*—Secures L2TP traffic and also allows clients to connect from behind NAT devices that support IPSec passthrough

**Mode**    IPSec Transport Profile Configuration

## aps events

---

**Syntax**    `aps events list [ list ]*`

`no aps events`

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Enables line modules to deliver APS events to the necessary SNMP traps. You can configure notification for specific events. The **no** version disables the delivery of APS events from line modules to SNMP traps.

- Options**
- *list*—One of the following APS events:
    - *all*—Configures notification of all APS events
    - *channel-mismatch*—Configures notification of APS channel mismatches
    - *feplf*—Configures notification of APS far-end protection line failures
    - *mode-mismatch*—Configures notification of APS mode mismatches
    - *psbf*—Configures notification of APS protection signal byte failures
    - *switchover*—Configures notification of APS switchovers
    - *\**—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## aps force

---

**Syntax**    `aps force channelNumber`  
`no aps force`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Forces the specified interface to be replaced by the inactive interface in an APS/MSP group. The **no** version allows the specified interface to resume operation.

**Options**    • *channelNumber*—One of the following channel numbers:

- 0—Switches from the protect interface back to the working interface
- 1—Switches from the working interface to the protect interface

**Mode**    Controller Configuration

## aps group

---

**Syntax**    `aps group groupName`

`no aps group`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns an interface to an APS/MSP group. The **no** version removes a group of APS/MSP interfaces.

**Options**

- *groupName*—Name of the APS/MSP group to which the active and standby interfaces belong; string of up to 32 characters

**Mode**    Controller Configuration

## aps logout

---

**Syntax**    `aps logout [ 0 ]`

`no aps logout`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Prevents the working interface from switching to the protect interface. The **no** version restores the default situation, in which the working interface can switch to the protect interface.

**Options**

- 0—Specifies the channel number that identifies the protect interface; because the protect interface is always assigned channel number 0, this is the only valid option

**Mode**    Controller Configuration

## aps manual

---

**Syntax**    `aps manual channelNumber`

`no aps manual`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Forces the working interface to switch to the protect interface, unless a request of equal or higher priority exists. The **no** version allows the specified working interface to resume the active role.

- Options**    • *channelNumber*—One of the following channel numbers:
- 0—Switches from the protect interface back to the working interface
  - 1—Switches from the working interface to the protect interface

**Mode**    Controller Configuration

## aps protect

---

**Syntax**    `aps protect [ 0 ]`

`no aps protect`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures an interface as a protect interface. The **no** version removes the relationship between the protect interface and the active interface.

**Options**

- 0—Specifies the channel number that identifies the protect interface; because the protect interface is always assigned channel number 0, this is the only valid option

**Mode**    Controller Configuration

## aps revert

---

**Syntax**    `aps revert minutes`

`no aps revert`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the APS/MSP group to operate in revertive mode. The **no** version restores the default setting, nonrevertive mode.

**Options**

- *minutes*—Number of minutes in the range 5–12 at which the interface resumes the active role after that interface becomes available

**Mode**    Controller Configuration



## aps unidirectional

---

**Syntax** [ no ] aps unidirectional

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the APS/MSP group to operate in unidirectional mode, the default setting. The **no** version configures the APS/MSP group to operate in bidirectional mode.

**Mode** Controller Configuration

## aps working

---

**Syntax**    aps working [ 1 ]

             no aps working

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures an interface as a working interface. The **no** version removes the configuration.

**Options**    • 1—Channel number that identifies the working interface; because the working interface is always assigned channel number 1, this is the only valid option

**Mode**    Controller Configuration

## area

---

**Syntax**    no area { *areald* | *arealdInt* }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    This command has only a **no** version. See the no area command for a complete description.

**Mode**    Router Configuration

## area-authentication

---

**Syntax** [ no ] area-authentication { csnp | psnp }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables or disables (suppresses) simple text authentication or HMAC MD5 authentication of IS-IS level 1 CSNP packets or PSNP packets. The **no** version restores the default behavior, in which authentication of IS-IS level 1 CSNPs and PSNPs is disabled.

**Options**

- **csnp**—Enables authentication of IS-IS level 1 complete sequence number PDUs (CSNPs)
- **psnp**—Enables authentication of IS-IS level 1 partial sequence number PDUs (PSNPs)

**Mode** Router Configuration

---

## area-authentication-key

---

**Syntax**    `area-authentication-key [ 0 | 8 ] authKey`  
              `no area-authentication-key`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a password used by neighboring routers for authentication of IS-IS level 1 LSPs, CSNPs, and PSNPs. The **no** version deletes the password.



.....  
**NOTE:** Issuing this command enables simple authentication of level 1 LSPs only. To enable authentication of level 1 CSNPs or PSNPs, use the [area-authentication](#) command.  
.....

- Options**
- 0—Indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authKey*—Password, string of up to 8 characters

**Mode**    Router Configuration

## area default-cost

---

**Syntax**    `area { areald | arealdInt } default-cost defaultCost`  
`no area { areald | arealdInt } default-cost`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a cost for the default summary route sent into a stub area. A stub area is an OSPF area that carries a default route, intra-area routes, and interarea routes, but does not carry external routes. You cannot configure virtual links across a stub area. Stub areas cannot contain an AS boundary router. The **no** version removes the configured default route cost.

**Options**

- *areald*—OSPF area ID in IP address format
- *arealdInt*—OSPF area ID as a decimal value 0–4294967295
- *defaultCost*—Stub area's advertised external route cost (cost metric); an integer in the range 0–16777215

**Mode**    Router Configuration

## area-message-digest-key

**Syntax** `area-message-digest-key keyId hmac-md5 [ 0 | 8 ] key`  
`[ start-accept startAcceptTime [ { startAcceptMonth startAcceptDay | startAcceptDay startAcceptMonth } startAcceptYear ] ]`  
`[ start-generate startGenTime [ { startGenMonth startGenDay | startGenDay startGenMonth } startGenYear ] ]`  
`[ stop-accept { never | stopAcceptTime [ { stopAcceptMonth stopAcceptDay | stopAcceptDay stopAcceptMonth } stopAcceptYear ] } ]`  
`[ stop-generate { never | stopGenTime [ { stopGenMonth stopGenDay | stopGenDay stopGenMonth } stopGenYear ] } ]`  
`no area-message-digest-key keyId`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an HMAC MD5 key that the router uses to create a secure, encrypted message digest of each IS-IS level 1 packet (LSPs, CSNPs, and PSNPs). The digest is inserted into the packet from which it is created. Using this algorithm for area routers protects against unauthorized routers injecting false routing information into your network.

You can specify when the router will start (default is the current time) and stop (default is never) accepting packets that include a digest made with this key. You can specify when the router will start (default is the current time plus 2 minutes) and stop (default is never) generating packets that include a digest made with this key. The **no** version deletes the key specified by the *keyId*.



**NOTE:** Issuing this command enables MD5 authentication of level 1 LSPs only. To enable authentication of level 1 CSNPs or PSNPs, use the [area-authentication](#) command.

- Options**
- *keyId*—Integer from 1 to 255 that is a unique identifier for the secret key, sent with the message digest in the packet.
  - 0—Indicates the *key* is entered in unencrypted form (plaintext); default option
  - 8—Indicates the *key* is entered in encrypted form (ciphertext)
  - *key*—String of up to 20 alphanumeric characters; secret key used by the HMAC MD5 algorithm to generate the message digest
  - *startAcceptTime*, *startAcceptMonth*, *startAcceptDay*, *startAcceptYear*—Time, month, day, year that the router will start accepting packets created with this password. Use military time format *HH : MM[: SS ]*.
  - *startGenTime*, *startGenMonth*, *startGenDay*, *startGenYear*—Time, month, day, year that the router will start inserting this password into packets. Use military time format *HH : MM[: SS ]*.

- *never*—Indicates the router never stops accepting or generating packets; overrides previously specified stop times and keeps using the authentication key in sending and receiving PDUs with the corresponding authentication indefinitely
- *stopAcceptTime, stopAcceptMonth, stopAcceptDay, stopAcceptYear*—Time, month, day, year that the router will stop accepting packets created with this password. Use military time format *HH : MM[: SS ]*.
- *stopGenTime, stopGenMonth, stopGenDay, stopGenYear*—Time, month, day, year that the router will stop inserting this password into packets. Use military time format *HH : MM[: SS ]*.

**Mode** Router Configuration



## area nssa

**Syntax** [ no ] area { *areald* | *arealdInt* } nssa [ default-information-originate [ always | metric *absoluteValue* | metric-type 1 | metric-type 2 | route-map *mapTag* ]\* ] [ no-summary ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**no-summary** keyword added in JunosE Release 7.2.0.

**Description** Configures an area as an NSSA and controls generation of type 7 default LSAs. NSSAs are similar to stub areas but have the additional capability of importing AS external routes in a limited fashion. The **no** version removes the specified option for default-information-originate, removes default-information-originate, or removes the NSSA designation from the area.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - default-information-originate—Causes the generation of a type 7 default LSA if a default route exists in the routing table.
  - always—Creates the default route if it does not exist
  - *absoluteValue*—Metric applied to the generated type 7 default LSAs; ranges from 0–4294967295
  - metric-type 1—Cost of the external routes is equal to the sum of all internal costs and the external cost
  - metric-type 2—Cost of the external routes is equal to the external cost alone; this is the OSPF default
  - *mapTag*—String of up to 32 alphanumeric characters that specifies a route map applied to the generated type 7 default LSAs
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line
  - no-summary—Restricts T3 summary LSAs from flowing into the NSSA area (T7 external LSAs and T3 default route LSAs are still injected into the area)

**Mode** Router Configuration

## area range

---

**Syntax** For OSPFv2:

```
[ no ] area { areald | arealdInt } range ipAddress mask [ do-not-advertise ]  
[ cost costValue ]
```

For OSPFv3:

```
[ no ] area { areald | arealdInt } range ipv6Prefix/ipv6PrefixLength  
[ do-not-advertise | advertise | cost costValue ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**cost** keyword and *costValue* variable for OSPFv2 added in JunosE Release 8.1.0.

**Description** Aggregates routes at an area boundary. By default, the range of configured networks is advertised in type 3 (summary) LSAs. The **no** version disables this function.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address to match
  - *mask*—IP address mask
  - *ipv6Prefix*—IPv6 network number to match
  - *ipv6PrefixLength*—Length of the IPv6 prefix; a decimal value that indicates how many of the higher-order contiguous bits of the IPv6 address make up the prefix (the network portion of the IPv6 address). A slash (/) must precede this value.
  - do-not-advertise—Specifies that the range of configured networks is not advertised
  - advertise—Specifies that the range of configured networks is advertised (IPv6 only)
  - *costValue*—Cost value for the specified range of networks in the range 0–65535

**Mode** Router Configuration

## area stub

---

**Syntax** [ no ] area { *areald* | *arealdInt* } stub [ no-summary ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**no-summary** keyword for OSPFv2 added in JunosE Release 7.2.0.

**Description** Defines an area as a stub area. A stub area is an OSPF area that carries a default route, intra-area routes, and interarea routes, but does not carry AS external routes. This reduces the size of the area's OSPF database and decreases memory usage for external routers in the stub area. The **no** version disables this function.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - no-summary—Specifies that the summary LSA not be sent into the stub area

**Mode** Router Configuration

## area virtual-link

---

**Syntax** [ no ] area { *areald* | *arealdInt* } virtual-link *ipAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an OSPF virtual link. The **no** version removes the virtual link.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address associated with the virtual link neighbor

**Mode** Router Configuration

## area virtual-link authentication-key

---

**Syntax** [ no ] area { *areaID* | *arealDInt* } virtual-link *ipAddress* authentication-key [ 0 | 8 ] *key*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures simple password (type 1) authentication for OSPF virtual links. The **no** version removes the password.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address of the virtual link neighbor
  - 0—Indicates the *key* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *key* is entered in encrypted form (ciphertext)
  - *key*—Password to be used by neighbors; string of up to 16 alphanumeric characters. All neighboring routers on the same network must have the same password.

**Mode** Router Configuration

## area virtual-link authentication message-digest

---

**Syntax** [ no ] area { *areaID* | *arealInt* } virtual-link *ipAddress* authentication message-digest

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that MD5 authentication is used for the virtual link. The **no** version sets the authentication for the virtual link to none, but leaves any configured MD5 key intact.

**Options**

- *areaID*—OSPF area ID in IP address format
- *arealInt*—OSPF area ID as a decimal value in the range 0–4294967295
- *ipAddress*—IP address of the virtual link neighbor

**Mode** Router Configuration

## area virtual-link authentication-none

---

**Syntax** [ no ] area { *areald* | *arealdInt* } virtual-link *ipAddress* authentication-none

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that no authentication is to be used for the virtual link. The **no** version has no effect.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address of the virtual link neighbor

**Mode** Router Configuration

## area virtual-link dead-interval

---

**Syntax** [ no ] area { *areald* | *arealdInt* } virtual-link *ipAddress* dead-interval *deadInterval*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an OSPF virtual link and the time interval allowed for detecting a dead router. The **no** version removes the virtual link's dead interval.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address of the virtual link neighbor
  - *deadInterval*—Integer in the range 0–2147483647 seconds; default value is 40 seconds

**Mode** Router Configuration



## area virtual-link hello-interval

---

**Syntax** [ no ] area { *areald* | *arealdInt* } virtual-link *ipAddress* hello-interval *helloInterval*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an OSPF virtual link and the time between the hello packets. The hello interval value must be the same for both ends of the virtual link. The **no** version removes the virtual link's hello interval.

- Options**
- *areald*—OSPF area ID in IP address format.
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address associated with the virtual link neighbor
  - *helloInterval*—Integer in the range 1–65535 seconds; default value is 10 seconds

**Mode** Router Configuration

## area virtual-link message-digest-key md5

**Syntax**    `area { areald | arealdInt } virtual-link ipAddress  
                   message-digest-key md5KeyId md5 [ 0 | 8 ] msgDigestKey  
                   no area { areald | arealdInt } virtual-link ipAddress message-digest-key md5KeyId`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables MD5 authentication and configures MD5 keys for virtual links. The **no** version deletes MD5 keys.



**NOTE:** If you delete all the MD5 keys, the authentication type for the virtual link is still MD5, but you need to configure MD5 keys.

To disable MD5 authentication for the virtual link, use the [area virtual-link authentication-none](#) command.

- Options**
- *areald*—OSPF area ID in IP address format
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address of the virtual link neighbor
  - *md5KeyId*—Key identifier in the range 1–255
  - 0—Indicates the *msgDigestKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *msgDigestKey* is entered in encrypted form (ciphertext)
  - *msgDigestKey*—Password to be used by neighbors; string of up to 16 alphanumeric characters. All neighboring routers on the same network must have the same password.

**Mode**    Router Configuration

## area virtual-link retransmit-interval

---

**Syntax** [ no ] area { *areald* | *arealdInt* } virtual-link *ipAddress* retransmit-interval *retransmInterval*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an OSPF virtual link and the time between link-state advertisement retransmissions for the adjacency belonging to the virtual link. The **no** version removes the virtual link's retransmit interval.

- Options**
- *areald*—OSPF area ID in IP address format.
  - *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address of the virtual link neighbor
  - *retransmInterval*—LSA retransmit interval; an integer in the range 0–3600 seconds; default value is 5 seconds

**Mode** Router Configuration

## area virtual-link transmit-delay

---

**Syntax** [ no ] area { *areaId* | *areaIdInt* } virtual-link *ipAddress* transmit-delay *transmDelay*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an OSPF virtual link and the estimated time it takes to transmit a link-state update packet on the virtual link. The **no** version removes the virtual link's transmit delay.

- Options**
- *areaId*—OSPF area ID in IP address format
  - *areaIdInt*—OSPF area ID as a decimal value in the range 0–4294967295
  - *ipAddress*—IP address associated with the virtual link neighbor
  - *transmDelay*—LSA transmit delay; an integer in the range 0–3600 seconds; default value is 1 second

**Mode** Router Configuration

## arp

**Syntax** To add a permanent ARP cache entry in Global Configuration mode:

```
[ no ] arp [ vrf vrfName ] ipAddress interfaceType interfaceSpecifier
[ macAddress [ validate ] ]
```

To modify the subscriber policy for ARP packets in Subscriber Policy Configuration mode:

```
arp { permit | deny }
```

```
no arp
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** In Global Configuration mode, adds a permanent entry in the ARP cache. This command applies only to Fast Ethernet, Gigabit Ethernet, 10-Gigabit Ethernet interfaces, and bridged Ethernet interfaces configured over ATM 1483. The **no** version removes an entry from the ARP cache.

In Subscriber Policy Configuration mode, modifies the subscriber policy for ARP to define whether the subscriber (client) interfaces belonging to a bridge group or VPLS instance forward (permit) or filter (deny) ARP packets. The **no** version restores the default value, permit ARP packets.

In Subscriber Policy Configuration mode, you cannot change the default subscriber policy values for trunk (server) interfaces belonging to a bridge group or VPLS interface. You also cannot change the default subscriber policy values for a VPLS virtual core interface, which acts as a trunk interface. The VPLS virtual core interface represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) device.

- Options**
- *vrfName*—Name of the VRF to which the command applies; string of 1–32 alphanumeric characters
  - *ipAddress*—IP address in 32-bit dotted-decimal format corresponding to the local data link address
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *macAddress*—MAC address of the interface
  - *validate*—Allows the inclusion of MAC validation entries
  - *permit*—Specifies that the subscriber interface associated with the bridge group or VPLS instance forwards ARP packets
  - *deny*—Specifies that the subscriber interface associated with the bridge group or VPLS instance filters ARP packets

**Mode** Global Configuration, Subscriber Policy Configuration

## arp spoof-check

---

**Syntax** [ no ] arp spoof-check

**Release Information** Command introduced in JunosE Release 9.3.0.

**Description** Configures the router to check for spoofed ARP packets received on an IP interface. By default, the router checks all ARP packets received on a major IP interface or a subinterface to identify and discard spoofed ARP packets. The **no** version disables checking for spoofed ARP packets received on the interface.

**Mode** Interface Configuration

## arp timeout

---

**Syntax**    arp timeout *timeoutVal*

no arp timeout

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies how long an entry remains in the ARP cache. You can set the ARP timeout on Fast Ethernet, Gigabit Ethernet, and 10-Gigabit Ethernet interfaces, and bridged Ethernet interfaces configured over ATM 1483. The default value is 21600 seconds (6 hours). Use the **show configuration** command to display the current value. The **no** version restores the default value.

**Options**    • *timeoutVal*—Time in seconds that an entry remains in the ARP cache

**Mode**    Interface Configuration

## assured-rate

---

**Syntax**    `assured-rate { assuredRate | hierarchical | [ operator operandValue ]* }`

`no assured-rate`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
*operator* and *operandValue* variables added in JunosE Release 7.1.0.

**Description**    Sets the assured rate for the scheduler profile. The assured rate overrides the HRR weight of the scheduler node or queue. The **no** version deletes the assured rate.

- Options**
- *assuredRate*—Constant assured rate in bits per second; in the range 25000–10000000000 (25 Kbps to 1 Gbps)
  - *hierarchical*—Specifies that the node use the hierarchical assured rate (HAR) feature, in which the scheduler node's assured rate is dynamically adjusted based on the sum of the assured rates of all its child nodes and queues
  - *operator*—Mathematical function
  - *operandValue*—Input for the operator; can be a QoS parameter definition name or an integer
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Scheduler Profile Configuration

- Related Documentation**
- Configuring an Assured Rate for a Scheduler Node or Queue
  - Configuring a Basic Parameter Definition for QoS Administrators



## atm

---

**Syntax**    atm { ubr | ubr pcr *pcr* | nrtvbr *pcr scr mbs* | rtvbr *pcr scr mbs* | cbr *pcr* }  
              no atm

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures traffic-shaping parameters for PPPoA via domain-based parameters. The **no** version removes the ATM traffic-shaping configuration.

- Options**
- **ubr**—Sets the traffic category to unspecified bit rate
  - **ubr pcr**—Sets the traffic category to unspecified bit rate with peak cell rate
  - **nrtvbr**—Sets the traffic category to non-real time variable bit rate
  - **rtvbr**—Set the traffic category to real time variable bit rate
  - **cbr**—Sets the traffic category to constant bit rate
  - **pcr**—Peak cell rate in the range 0–4294967295 Kbps
  - **scr**—Sustained cell rate in the range 0–4294967295 Kbps
  - **mbs**—Maximum burst size in the range 0–4294967295 Kbps

**Mode**    Domain Map Configuration

## atm aal5 description

---

**Syntax**    atm aal5 description *name*  
              no atm aal5 description

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description or alias to an ATM AAL5 interface. The **no** version removes the text description or alias. Use the show atm aal5 interface command to display the text description.

**Options**    • *name*—Alias for the AAL5 interface; up to 32 characters

**Mode**    Interface Configuration

## atm aal5 shutdown

---

**Syntax** [ no ] atm aal5 shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the administrative state of an ATM AAL5 interface to disabled. The **no** version enables a disabled interface.

**Mode** Interface Configuration

## atm aal5 snmp trap link-status

---

**Syntax** [ no ] atm aal5 snmp trap link-status

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SNMP link status traps on the AAL5 layer on a per-interface basis. The **no** version disables the traps.

**Mode** Interface Configuration

## atm atm1483 advisory-rx-speed

---

**Syntax**    atm atm1483 advisory-rx-speed *speed*  
              no atm atm1483 advisory-rx-speed

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets an advisory receive (RX) speed that the LAC sends in the RX Connect-Speed AVP [38] to the LNS. The **no** version restores the default behavior, in which the RX speed is not sent to the LNS.

**Options**    • *speed*—Speed in the range 0–2147483647 kbps

**Mode**    Profile Configuration, Subinterface Configuration

## atm atm1483 auto-configure

---

**Syntax**    `atm atm1483 auto-configure upperInterfaceType`  
              `[ lockout-time { minValue maxValue | none } ]`  
  
              `no atm atm1483 auto-configure upperInterfaceType [ lockout-time ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies one or more types of dynamic upper interface encapsulations that are accepted or detected by a dynamic ATM 1483 subinterface. Optionally, specifies the lockout time range for the encapsulation type. You can issue this command repeatedly in Profile Configuration mode to include autodetection of multiple upper interface encapsulation types within the base profile for a dynamic ATM 1483 subinterface. The **no** version terminates detection of the specified encapsulation type.



.....  
**NOTE:** Encapsulation type lockout is available for bridged Ethernet, IP, PPP, and PPPoE encapsulation types.  
.....

- Options**
- *upperInterfaceType*—One of the following dynamic encapsulation types:
    - bridgedEthernet
    - ip
    - ppp
    - pppoe
  - *minValue*—Minimum lockout time in the range 1–86400 seconds (24 hours); default value is 1 second
  - *maxValue*—Maximum lockout time in the range 1–86400 seconds (24 hours); default value is 300 seconds (5 minutes)
  - none—Disables lockout for the specified dynamic encapsulation type

**Mode**    Profile Configuration

## atm atm1483 description

---

**Syntax**    atm atm1483 description *name*  
              no atm atm1483 description

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description or alias to an ATM 1483 interface. The **no** version removes the text description or alias. Use the `show atm subinterface` command to display the text description.

**Options**    • *name*—Text string or alias for the ATM 1483 interface; up to 255 characters

**Mode**    Profile Configuration, Subinterface Configuration

## **atm atm1483 export-subinterface-description**

---

**Syntax** [ no ] atm atm1483 export-subinterface-description

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Exports ATM 1483 subinterface descriptions to the line module. The **no** version restores the default behavior, where ATM 1483 subinterface descriptions are not sent to the line module.

**Mode** Global Configuration



## atm atm1483 mtu

---

**Syntax**    atm atm1483 mtu *size*  
              no atm atm1483 mtu

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the MTU size for an ATM 1483 subinterface. The **no** version restores the default MTU size of 9180.

**Options**    • *size*—Maximum number of packet transmissions permitted on an ATM 1483 subinterface; in the range 256–9180; default value is 9180

**Mode**    Subinterface Configuration

## atm atm1483 profile

---

**Syntax**    `atm atm1483 profile upperInterfaceType profileName`  
              `no atm atm1483 profile upperInterfaceType`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Adds a nested profile assignment to a base profile for a dynamic ATM 1483 subinterface. A nested profile assignment references another profile that dynamically configures upper interface encapsulation types over the ATM 1483 subinterface. The **no** version removes the profile assignment for the upper interface type.

**Options**

- *upperInterfaceType*—One of the following dynamic encapsulation types:
  - bridgedEthernet
  - ip
  - ppp
  - pppoe
- *profileName*—Profile name of up to 80 characters

**Mode**    Profile Configuration

## atm atm1483 shutdown

---

**Syntax** [ no ] atm atm1483 shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the administrative state of an ATM 1483 subinterface to disabled. The **no** version enables a disabled subinterface.

**Mode** Subinterface Configuration

## atm atm1483 snmp trap link-status

---

**Syntax** [ no ] atm atm1483 snmp trap link-status

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SNMP link status traps on the ATM1483 layer. The **no** version disables the traps.

**Mode** Subinterface Configuration

## atm atm1483 subscriber

---

**Syntax**    atm atm1483 subscriber *upperInterfaceType* { user | user-prefix } *userName*  
              domain *domainName* [ { password | password-prefix }  
              *password* ] [ no-authenticate ]  
  
              no atm atm1483 subscriber *upperInterfaceType*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a local subscriber (when one cannot be obtained externally, as in PPP) for a dynamic upper interface encapsulation type configured over a dynamic ATM 1483 subinterface. A subscriber supports authentication and configuration from the RADIUS server. The **no** version removes the subscriber.

- Options**
- *upperInterfaceType*—One of the following dynamic encapsulation types:
    - bridgedEthernet
    - ip
  - user—Employs the username as specified
  - user-prefix—Appends the interface physical location to the username
  - *userName*—RADIUS username
  - *domainName*—Domain name
  - password—Employs the password as specified
  - password-prefix—Appends the interface physical location to the password
  - *password*—RADIUS password
  - no-authenticate—Disables authentication

**Mode**    Profile Configuration

## atm auto-configuration

---

**Syntax** [ no ] atm auto-configuration

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables autoconfiguration of ILMI. Autoconfiguration is enabled by default. This command overrides any previous configuration of the [atm uni-version](#) command. The **no** version disables auto configuration and sets the ILMI parameters to the UNI version configured using the [atm uni-version](#) command, which has a default value of UNI 4.0.

**Mode** Interface Configuration

## atm bulk-config

**Syntax**    `atm bulk-config bulkConfigName [ vc-range vpiStart vpiEnd vciStart vciEnd ]*`  
               `no atm bulk-config bulkConfigName [ vc-range vpiStart vpiEnd vciStart vciEnd ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a range of ATM PVCs for use by a dynamic ATM 1483 subinterface, and assigns a name to the virtual circuit (VC) range. Each VC range consists of one or more nonoverlapping VC subranges. A VC subrange is a group of VCs that resides within the specified VPI and VCI ranges. You can configure multiple VC ranges on an ATM AAL5 interface. The **no** version removes the specified VC range (including all subranges in the range) from the ATM AAL5 interface or the specified subrange from the VC range. The **no** version also removes any overriding profile assignments for ATM PVCs within the deleted VC range or VC subrange.



**NOTE:** The total number of VCs configured with the `atm bulk-config` command cannot exceed the maximum ATM VC capacity of the line module you are using. For details about the ATM VC capacity of supported line modules, see *JunosE Release Notes, Appendix A, System Maximums*.

- Options**
- *bulkConfigName*—Name of the VC range; string of up to 80 characters
  - *vpiStart*—Starting virtual path identifier (inclusive) of the VC subrange you are configuring
  - *vpiEnd*—Ending virtual path identifier (inclusive) of the VC subrange you are configuring
  - *vciStart*—Starting virtual circuit identifier (inclusive) of the VC subrange you are configuring
  - *vciEnd*—Ending virtual circuit identifier (inclusive) of the VC subrange you are configuring
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Interface Configuration

## atm bulk-config modify

---

**Syntax** atm bulk-config *bulkConfigName* modify vc-range *vpiStart vpiEnd vciStart vciEnd*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Modifies the VC subrange values for the specified bulk configuration VC range. If the new subrange encompasses previously configured subranges within that range, those subranges are merged into the new one, freeing subrange resources. There is no **no** version.

- Options**
- *bulkConfigName*—Name of the VC range; string of up to 80 characters
  - *vpiStart*—Starting virtual path identifier (inclusive) of the VC subrange you are configuring
  - *vpiEnd*—Ending virtual path identifier (inclusive) of the VC subrange you are configuring
  - *vciStart*—Starting virtual circuit identifier (inclusive) of the VC subrange you are configuring
  - *vciEnd*—Ending virtual circuit identifier (inclusive) of the VC subrange you are configuring

**Mode** Interface Configuration



## atm bulk-config shutdown

---

**Syntax** [ no ] atm bulk-config *bulkConfigName* shutdown  
[ vc-range *vpiStart vpiEnd vciStart vciEnd* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Administratively disables (shuts down) the specified VC range or subrange. The **no** version reenables the specified VC range or the specified subranges; this is the default condition.

- Options**
- *bulkConfigName*—Name of the VC range; string of up to 80 characters
  - *vpiStart*—Starting virtual path identifier (inclusive) of the VC subrange you are configuring
  - *vpiEnd*—Ending virtual path identifier (inclusive) of the VC subrange you are configuring
  - *vciStart*—Starting virtual circuit identifier (inclusive) of the VC subrange you are configuring
  - *vciEnd*—Ending virtual circuit identifier (inclusive) of the VC subrange you are configuring

**Mode** Interface Configuration

## atm cac

---

**Syntax** [ no ] atm cac [ *subscriptionBandwidth* ] [ *ubr ubrWeight* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables CAC on the ATM interface. If the subscription limit or UBR weight parameters are set to zero, the router uses the effective port bandwidth as the subscription bandwidth. The effective bandwidth varies according to line module. The **no** version disables CAC on the interface.



.....  
**NOTE:** If you modify one of these parameters after CAC is enabled, you must modify both parameters. Otherwise, the parameter not specified reverts to its default value.  
.....

- Options**
- *subscriptionBandwidth*—Maximum allowable bandwidth on this port in the range 0–2147482647 Kbps; default value is 0
  - *ubrWeight*—Bandwidth associated with UBR and UBR-PCR connections in the range 0–2147482647 Kbps; default value is 0

**Mode** Interface Configuration

## atm cell-packing

**Syntax**    `atm cell-packing maxCellsPerPacket mcpt-timer timerIdentifier`  
               `no atm cell-packing`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures cell concatenation parameters for an ATM 1483 subinterface that provides ATM layer 2 services over MPLS with virtual channel connection (VCC) cell relay encapsulation. The **no** version restores the default cell concatenation parameters for the subinterface.



**NOTE:** See the [atm mcpt-timers](#) command for information about configuring systemwide values for the three ATM Martini cell packing timers to define the cell collection time threshold.

- Options**
- *maxCellsPerPacket*—Maximum number of ATM cells in the range 1–190 that the router can concatenate in a single VCC cell relay–encapsulated packet and transmit on an MPLS pseudowire connection; default value is 1 cell per packet
  - *timerIdentifier*—Integer in the range 1–3 that identifies which of the three ATM Martini cell packing timers (timer 1, timer 2, or timer 3) you want to use to detect timeout of the cell collection time threshold; default value is 1. When the timer expires, the router forwards the packet even if the number of concatenated ATM cells in the packet is fewer than the specified maximum number of cells per packet.

**Mode**    Subinterface Configuration

**Related Documentation**

- [Configuring an MPLS Pseudowire with VCC Cell Relay Encapsulation](#)

## atm-cell-mode

---

**Syntax** [ no ] atm-cell-mode

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Accounts for the ATM cell tax in rate calculations for interface types that support rate-limiting and are stackable over ATM. The **no** version restores the default, which uses the frame size with the layer 2 header included.

**Mode** Policy List Configuration

**Related Documentation**

- [Enabling ATM Cell Mode](#)

## atm classifier-list

---

**Syntax** atm classifier-list *classifierName* [ traffic-class *trafficClassName* ]  
[ color { green | yellow | red } ] [ user-packet-class *userPacketClassValue* ]  
[ clp *clpValue* ]  
  
no atm classifier-list *classifierName* [ *classifierNumber* ]

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Creates a classifier control list that can only be used in ATM policy lists. The **no** version removes the ATM classifier control list. ATM packets are classified on CLP. The CLP bit is not available on frame-based interfaces on E Series Broadband Services Router line modules.

- Options**
- *classifierName*—Name of the classifier control list entry
  - *trafficClassName*—Name of the traffic class to match
  - green—Matches packet color to green, indicating a low drop preference
  - yellow—Matches packet color to yellow, indicating a medium drop preference
  - red—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—User packet value to match in the range 0–15
  - *clpValue*—Value of the CLP, 0 or 1
  - *classifierNumber*—Index of the classifier control list entry to be deleted

**Mode** Global Configuration

**Related Documentation**

- Creating or Modifying Classifier Control Lists for ATM Policy Lists

## atm class-vc

---

**Syntax**    `atm class-vc vcClassName`

`no atm class-vc [ vcClassName ]`

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Assigns a previously configured VC class to a base profile for a dynamic ATM 1483 subinterface. Issuing this command applies the set of attributes in the specified VC class to all bulk-configured VC ranges that are dynamically created from this profile. The **no** version removes the VC class association with the base profile.

**Options**    • *vcClassName*—Name of the VC class configured with the `vc-class atm` command

**Mode**    Profile Configuration

## atm clock internal

---

**Syntax** [ no ] atm clock internal [ *internalSource* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Causes the ATM interface to generate the transmit clock internally. The **no** version causes ATM interfaces to recover the clock from the received signal. If the internal clock is chosen and no internal source is specified, then the internal clock source is taken from the line module.

**Options**

- *internalSource*—One of the following:
  - *module*—Specifies that the internal clock is from the line module
  - *chassis*—Specifies that the internal clock is from the configured router clock

**Mode** Interface Configuration

## atm description

---

**Syntax**    atm description *name*

             no atm description

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description or alias to the ATM interface. The first 32 characters of the description are pushed out to RADIUS during authentication and accounting. The show atm interface command displays the text description. The **no** version removes the text description or alias.

**Options**    • *name*—Text string or alias of up to 255 characters; can include the # (pound sign) character

**Mode**    Interface Configuration



## atm dos-protection-group

---

**Syntax**    atm dos-protection-group *groupName*  
              no atm dos-protection-group

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches an ATM denial of service (DoS) protection group to an interface. The **no** version removes the DoS protection group.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## atm framing

---

**Syntax**    atm framing *framingType*

             no atm framing

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures T3 or E3 framing on an ATM interface. The **no** version returns framing to the default. For a T3 interface, the default value is cbitplcp. For an E3 interface, the default value is g751plcp.

- Options**    • *framingType*—One of the following:
- cbitadm—c-bit with ATM direct mapping for a DS3 (T3) interface
  - cbitplcp—c-bit with PLCP framing for a DS3 (T3) interface (default for T3)
  - g832adm—G.832 ATM direct mapping for an E3 interface
  - g751adm—G.751 ATM direct mapping for an E3 interface
  - g751plcp—G.751 PLCP mapping for an E3 interface (default for E3)
  - m23adm—M23 ATM direct mapping for a DS3 (T3) interface
  - m23plcp—M23 with PLCP framing for a DS3 (T3)

**Mode**    Interface Configuration

## atm ilmi-enable

---

**Syntax** [ no ] atm ilmi-enable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables ILMI on the interface. The **no** version removes the ILMI PVC.

**Mode** Interface Configuration

## atm ilmi-keepalive

---

**Syntax**    [ no ] atm ilmi-keepalive [ *seconds* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables generation of ILMI keepalive messages on the router, affecting the operational state of the ATM interface. The **no** version disables the generation of keepalive messages.

**Options**    • *seconds*—Number in the range 0–4294967295; the interval in seconds between two consecutive ILMI keepalive requests

**Mode**    Interface Configuration

## atm lbo

---

**Syntax**    atm lbo { long | short }  
              no atm lbo

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the cable length (line build-out) for the ATM T3 or E3 interface. The length of cable determines power requirements. The **no** version restores the default value.

- Options**
- long—Specifies cable length in the range 226–450 feet
  - short—Specifies cable length in the range 0–225 feet (the default)

**Mode**    Interface Configuration

## atm mcpt-timers

---

**Syntax**    `atm mcpt-timers timer1 timer2 timer3`

`no atm mcpt-timers`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures systemwide values for the three ATM Martini cell packing timers. These timers define the time threshold that the router uses to collect and concatenate ATM cells in a single VCC cell relay–encapsulated packet and transmit the packet on an MPLS pseudowire connection. When the timer expires, the router forwards the packet even if the number of concatenated ATM cells in the packet is fewer than the specified maximum number of cells per packet. The **no** version restores the default values for all three timers.



**NOTE:** See the [atm cell-packing](#) command for information about specifying the maximum number of concatenated cells per packet and identifying which of the three ATM Martini cell packing timers you want to use to detect timeout of the cell collection threshold.

- Options**
- *timer1*—Number of microseconds in the range 100–4095; default value is 100
  - *timer2*—Number of microseconds in the range 100–4095; default value is 500
  - *timer3*—Number of microseconds in the range 100–4095; default value is 1000

**Mode**    Global Configuration

**Related Documentation**

- [Configuring an MPLS Pseudowire with VCC Cell Relay Encapsulation](#)

## atm oam

**Syntax** atm oam [ *vpi* ] [ [ seg-loopback | end-loopback [ loopback-timer *time* ] ]  
[ cc { source | sink | both } ] ]  
  
no atm oam [ *vpi* ] [ [ seg-loopback | end-loopback [ loopback-timer *time* ] ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures F4 OAM on an interface or circuit. The **no** version deletes F4 OAM circuits.



**NOTE:** If you do not specify any options, both F4 end-to-end OAM and F4 segment OAM are enabled on all VPIs on the interface.

- Options**
- *vpi*—VPI on which you want to enable F4 OAM. If you do not specify a VPI, F4 OAM flow is enabled on all VPIs on the interface.
  - *seg-loopback*—Enables F4 segment OAM
  - *end-loopback*—Enables F4 end-to-end OAM
  - *loopback-timer*—To generate F4 loopback cells on the VPI, you must configure the loopback timer; you can set the loopback timer only for end-to-end loopback
  - *time*—Time interval in the range 1–600 seconds between transmissions of F4 loopback cells.
  - *cc*—Enables CC cells on the PVC; you can enable CC cells only on data circuits, not on control circuits, such as ILMI or signaling circuits
  - *sink*—Enables this VC as a sink point (cell receiver)
  - *source*—Enables this VC as the source point (cell generator)
  - *both*—Enables this VC as both a sink point and a source point

**Mode** Interface Configuration, Subinterface Configuration

## atm oam flush

---

**Syntax** [ no ] atm oam flush [ alarm-cells ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the router to ignore all OAM cells received on an ATM interface, and to stop sending OAM cells on this interface. OAM performs fault management and performance management functions on an ATM interface. The **no** version disables OAM flush on the interface.

**Options**

- **alarm-cells**—Causes the router to ignore only AIS and RDI cells and to accept all other OAM cells

**Mode** Interface Configuration



## atm oam loopback-location

---

**Syntax** atm oam loopback-location *locationID*

[ no ] atm oam loopback-location

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the location ID of the ATM interface. The **no** version returns the loopback location to the default setting of all 1s (ones).

**Options** • *locationID*—Value of the four-octet long location ID of the ATM interface

**Mode** Interface Configuration

## atm policy

---

**Syntax** atm policy { input | output } *policyName*  
[ statistics { enabled [ preserve | merge ] | disabled [ merge ] } | merge ]  
  
no atm policy { input | output } [ *policyName* ]

**Release Information** Command introduced in JunosE Release 7.1.0.  
**merge** keyword added in JunosE Release 7.2.0.

**Description** Assigns a policy list to the ingress or egress of an ATM interface. If you enter this command when the policy list does not exist, the router creates a policy list with a filter rule as the default. You must specify the **input** or **output** keyword to assign the policy list to the ingress or egress of the interface. The **no** version removes the association between a policy list and an interface.

- Options**
- input—Applies policy to data arriving at this interface
  - output—Applies policy to data leaving this interface
  - *policyName*—Name of the policy; a maximum of 40 characters
  - statistics—Enables or disables collection of policy routing statistics
    - enabled—Enables collection of policy routing statistics
    - preserve—Preserves existing statistics for any classifier-list that is the same for both the new and old policy attachments when you attach a new policy to an interface
    - disabled—Disables collection of policy routing statistics
  - merge—Enables merging of multiple policies to form a single policy

**Mode** Interface Configuration

**Related Documentation**

- Setting a Statistics Baseline for Policies

## atm policy-list

---

**Syntax** [ no ] atm policy-list *policyName*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Creates an ATM policy list and accesses Policy List Configuration mode. If you execute an **atm policy-list** command and type **exit**, the router creates a policy list with a filter rule as the default. Attaching this policy list to an interface filters all packets on that interface. The **no** version removes a policy list.

**Options** • *policyName*—Name of the policy list; a maximum of 40 characters

**Mode** Global Configuration

**Related Documentation** • Creating Policy Lists for ATM

## atm pvc

**Syntax** To create a PVC on an ATM interface when using the **aal5snap**, **aal5autoconfig**, or **aal5mux ip** encapsulation type:

```
atm pvc vcd vpi vci encapsulation [ cbr cbr | peak [ average burst [ rt ] ] ]
[ oam [ seconds | cc [ segment | end-to-end ] { source | sink | both } ] ]
[ inArp [ minutes ] ]

no atm pvc vcd
```

To create a PVC on an ATM interface when using the **aal5all**, **aal0**, or **ilmi** encapsulation type:

```
atm pvc vcd vpi vci encapsulation [ cbr cbr | peak [ average burst [ rt ] ] ]

no atm pvc vcd
```

To use a profile to apply encapsulation and traffic-shaping parameters to a bulk range of PVCs configured for a dynamic ATM 1483 subinterface:

```
atm pvc encapsulation [ cbr cbr | peak [ average burst [ rt ] ] ] [oam seconds ]

no atm pvc
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** From Interface Configuration or Subinterface Configuration mode, creates a PVC on an ATM interface. The **no** version removes the specified PVC.

From Profile Configuration mode, applies encapsulation, traffic-shaping, and OAM parameters to the range of PVCs configured on a static ATM AAL5 interface for use by a dynamic ATM 1483 subinterface. The **no** version restores the default service type, UBR, on the VC range.



**NOTE:** The optional *peak*, *average*, and *burst* parameters configure traffic-shaping parameters for the circuit. The allowable traffic-shaping features and range specifications depend on the line module capabilities.

- Options**
- *vcd*—Virtual circuit descriptor that is an identifier for the VC in other commands; in the range 1–2147483647
  - *vpi*—Virtual path identifier of this PVC. The allowable numeric range depends on the line module capabilities and current configuration. The VPI and VCI cannot both be set to 0; if one is 0, the other cannot be 0.
  - *vci*—Virtual circuit identifier of this PVC. The allowable numeric range depends on the line module capabilities and current configuration. The VPI and VCI cannot both be set to 0; if one is 0, the other cannot be 0.

- *encapsulation*—Available options differ for ATM interfaces and dynamic ATM 1483 subinterfaces, as follows:
  - For PVCs created on ATM interfaces:
    - *aal5all*—Causes the router to pass through all ATM AAL5 traffic without interpreting it; supported for ATM layer 2 services over MPLS
    - *aal0*—Causes the router to receive raw ATM cells on this circuit and forward the cells without performing AAL5 packet reassembly; supported for ATM layer 2 services over MPLS
    - *aal5snap*—LLC encapsulated circuit; LLC/SNAP header precedes the protocol datagram
    - *aal5mux ip*—VC-based multiplexed circuit used for IP only
    - *aal5autoconfig*—Enables autodetection of the 1483 encapsulation (LLC/SNAP or VC multiplexed)
    - *ilmi*—Integrated local management interface encapsulation
  - For PVCs created on dynamic ATM 1483 subinterfaces:
    - *aal5snap*—LLC encapsulated circuit; LLC/SNAP header precedes the protocol datagram
    - *aal5mux ip*—VC-based multiplexed circuit used for IP only
    - *aal5autoconfig*—Enables autodetection of the 1483 encapsulation (LLC/SNAP or VC multiplexed)
- *cbr*—Constant bit rate in Kbps
- *peak*—PCR in Kbps
- *average*—Average rate in Kbps; also referred to as SCR
- *burst*—Length in cells of the burst; also referred to as MBS
- *rt*—Selects VBR-RT as the service type; the default type is VBR-NRT. You can select **rt** only if you set the *peak*, *average*, and *burst* parameters.
- *oam*—Enables generation of OAM F5 loopback cells on this circuit. This option enables VC integrity features that affect the operational state of the ATM PVC. You can use the **oam** keyword only if you specify the **aal5snap**, **aal5autoconfig**, or **aal5mux ip** encapsulation type.
- *seconds*—Time interval in the range 1–600 seconds between transmissions of OAM F5 end-to-end loopback cells for VC connectivity verification.
- *inArp*—Enables Inverse ARP. You can use the **inArp** keyword only if you specify the **aal5snap** encapsulation type.
- *minutes*—Inverse ARP refresh rate in minutes; 15 minutes is the default
- *cc*—Enables CC cells on the PVC; you can enable CC cells only on data circuits, not on control circuits, such as ILMI or signaling circuits

- segment—Opens an OAM CC segment cell flow
- end-to-end—Opens an OAM CC end-to-end cell flow
- sink—Enables this VC as a sink point (cell receiver)
- source—Enables this VC as the source point (cell generator)
- both—Enables this VC as both a sink point and a source point

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

**Related Documentation**

- Configuring an MPLS Pseudowire with VCC Cell Relay Encapsulation
- Configuring Local ATM Cross-Connects with AAL5 Encapsulation
- Configuring MPLS LSPs for VPWS

## atm shutdown

---

**Syntax** [ no ] atm shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Administratively disables an ATM interface. The **no** version enables a disabled interface.

**Mode** Interface Configuration

## atm snmp trap link-status

---

**Syntax** [ no ] atm snmp trap link-status

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SNMP link status traps on the ATM layer on a per-interface basis. The **no** version disables the traps.

**Mode** Interface Configuration



## atm sonet stm-1

---

**Syntax** [ no ] atm sonet stm-1

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the mode of operation on the physical interface to SDH STM-1. The **no** version restores the default value, SONET STS-3c operation.

**Mode** Interface Configuration

## atm uni-version

---

**Syntax**    atm uni-version *versionNumber*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the UNI version the interface should use. There is no **no** version.

**Options**    • *versionNumber*—UNI version number: 3.0, 3.1, or 4.0

**Mode**    Interface Configuration

## atm vc-per-vp

**Syntax** atm vc-per-vp [ *vcCount* ]

no atm vc-per-vp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the number of virtual circuits per virtual path. This command controls the VPI and VCI range on the ATM interface. The allowable configuration range depends on the line module. The router will not execute the command if any virtual circuits are open on the interface. The **no** version restores the default.



**NOTE:** This command is not available for ATM interfaces on the E120 router and the E320 router because they support the entire VPI/VCI range.

The minimum number of VCs per VP is 4096 for OC3-4 modules and 1024 for T3 ATM modules. If you enter a value that is below the minimum, the router uses the minimum value.

VCs and VP tunnels must not exist when you issue this command. If they do, you must delete the VC and VP tunnel configuration before you issue this command.

**Options** • *vcCount*—Number of virtual circuits per virtual path

**Mode** Interface Configuration

## atm vp-description

---

**Syntax**    `atm vp-description vpi description`  
              `no atm vp-description vpi`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description to an individual virtual path (VP) on an ATM interface. Use the `show atm vp-description` command to display the description. The **no** version restores the default value, a null string.

**Options**

- *vpi*—Virtual path identifier number in the range 0–255
- *description*—Text string or alias for the specified VPI; up to 32 characters

**Mode**    Interface Configuration

## atm-vp qos-parameter

---

**Syntax**    `atm-vp vpi qos-parameter qosParameterInstanceName qosParameterInstanceValue`  
              `no atm-vp vpi qos-parameter qosParameterInstanceName`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Attaches a QoS parameter instance to the specified VP on the ATM major interface. The **no** version detaches the parameter instance from the specified VP.

**Options**

- *vpi*—Virtual path identifier of this PVC; number in the range 0–255
- *qosParameterInstanceName*—Name of the parameter instance that you want to attach to the VP
- *qosParameterInstanceValue*—Number of the scheduler rate for the parameter instance; the default value is the minimum value defined in the parameter definition

**Mode**    Interface Configuration

**Related Documentation**

- Creating Parameter Instances

## atm-vp qos-profile

---

**Syntax** [ no ] atm-vp *vpi* qos-profile *qosProfileName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Attaches a QoS profile to the specified VP on the interface. The **no** version detaches the QoS profile from the VP.

- Options**
- *vpi*—Virtual path identifier of this PVC; number in the range 0–255
  - *qosProfileName*—Name of the QoS profile that you want to attach to the VP

**Mode** Interface Configuration

**Related Documentation**

- Attaching a QoS Profile to an Interface

## atm vp-tunnel

---

**Syntax**    `atm vp-tunnel vpi { cbr cbrKbps | kbps }`  
              `no atm vp-tunnel vpi`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines a virtual path tunnel and configures the rate of traffic flow within the tunnel. For QoS configurations, use to configure a shapeless VP tunnel. The **no** version removes the restriction.

- Options**
- *vpi*—Number in the range 0–255; virtual path identifier of this PVC
  - *cbr*—Specifies the service class as constant bit rate
  - *cbrKbps*—Tunnel rate for a virtual path with the CBR service class specified; a value in the range 1–4294967295, when you specify the rate of traffic flow with the CBR service class. Because the CBR service category guarantees a fixed amount of bandwidth to be allotted to the client, an error message is displayed if you configure a value of 0 for the tunnel rate for CBR traffic flows. The aggregate to this traffic from all circuits configured in the tunnel is held to the specified rate. Certain line modules may have minimum rates for VP tunnels.
  - *kbps*—Tunnel rate for a virtual path when you specify the rate of traffic flow without the constant bit rate (CBR) service category, a value in the range 0–4294967295. The aggregate to this traffic from all circuits configured in the tunnel is held to the specified rate. Certain line modules may have minimum rates for VP tunnels. Using a rate of 0 configures a shapeless tunnel (a tunnel with no rate) that is used for VP shaping in the SAR.

**Mode**    Interface Configuration

## attributes (AAA)

---

**Syntax** [ no | default ] attributes [ *attributeName* ]\*

**Release Information** Command introduced in JunosE Release 12.1.0.

**Description** Allows the user to configure an attribute or multiple attributes in the list. The **no** version restores the default setting. By default, the attributes are not configured.



**NOTE:** The attributes must be configured after configuring the **action-type**. You can specify the attributes in any order.

- Options**
- *attributeName*—The following AAA attributes can be specified:
    - tunnel-ignore-nasport
    - tunnel-ignore-nasport-type
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** AAA Per-Profile List Configuration



---

## attributes (RADIUS)

---

**Syntax** [ no | default ] attributes [ *attributeName* ]\*

**Release Information** Command introduced in JunosE Release 12.1.0.

**Description** Allows the user to configure an attribute or multiple attributes in the list. The **no** version restores the default setting. By default, the attributes are not configured.



**NOTE:** The attributes must be configured after configuring the **request-type** and **action-type**. You can specify the attributes in any order.

- Options**
- *attributeName*—The following RADIUS attributes can be specified:
    - calling-station-id
    - override-nas-ip-addr
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** RADIUS Per-Profile List Configuration

## authentication

---

**Syntax**    authentication { rsa-sig | pre-share }  
              no authentication

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the authentication method to use in the IKE policy. The **no** version restores the default, preshared keys.

**Options**    • rsa-sig—Specifies RSA signature as the authentication method  
              • pre-share—Specifies preshared keys as the authentication method

**Mode**    IKE Policy Configuration

## authentication key

---

**Syntax** authentication key [ 0 | 8 ] *authkey*  
no authentication key

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the password for text authentication and the key for MD5 authentication for RIP remote-neighbor interface. The **no** version clears the key for the interface. Supported only in RIP version 2. Authentication is disabled by default.

- Options**
- 0—Indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authkey*—Password sent with RIP messages or the key used to encrypt/decrypt RIP messages, depending on the authentication mode set for this remote-neighbor interface.

**Mode** Remote Neighbor Configuration

## authentication-key

---

**Syntax**    authentication-key [ 0 | 8 ] *authKey*  
              no authentication-key

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables simple password authentication and assigns a password used by OSPF remote neighbors. The **no** version deletes the password.

- Options**
- 0—Indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authKey*—Password; string of up to 8 characters

**Mode**    Remote Neighbor Configuration

## authentication message-digest

---

**Syntax** authentication message-digest

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that MD5 authentication is used for the OSPF remote-neighbor interface. There is no **no** version.

**Mode** Remote Neighbor Configuration

## authentication mode

---

**Syntax** authentication mode { text | md5 *keyID* }

no authentication mode

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the type of authentication used on the RIP remote-neighbor interface. Authentication is disabled by default. The **no** version removes authentication from the interface. Supported only in RIP version 2.

- Options**
- **text**—Sends a simple text password with each RIP message; if the password is not possessed by remote neighbors, the message is rejected
  - **md5**—Encrypts and compresses the RIP message with MD5 message-digest algorithms
  - **keyID**—Number identifying the MD5 key in the range 1–255; remote neighbors must share the MD5 key to decrypt the message and encrypt the response

**Mode** Remote Neighbor Configuration

## authentication-none

---

**Syntax** authentication-none

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that no authentication is to be used for the OSPF remote-neighbor interface. There is no **no** version.

**Mode** Remote Neighbor Configuration

## authorization

---

**Syntax**    `authorization { exec | commands level } authorListName`  
`no authorization {exec | commands level }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables AAA authorization for a specified vty line or group of vty lines. Associates the authorization list with the specified line. If the list does not exist or is empty, authorization always succeeds. For a command to be authorized, its level must match exactly with the level of one of the configured lists. The **no** version disables authorization.



.....  
**NOTE:** After you enable the **aaa authorization** command and define a named authorization method list (or use the default method list) for a particular type of authorization, you must apply the defined list to the appropriate lines for authorization to take place.  
.....

- Options**
- **exec**—Applies this authorization to CLI access in general
  - **commands**—Applies this authorization to user commands of the specified privilege level
  - **level**—Privilege level; a number in the range 0–15
  - **authorListName**—Name of an authorization method list of up to 32 characters; if no methods list is specified, the default is used

**Mode**    Line Configuration



## authorization change

---

**Syntax** [ no ] authorization change

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the router to receive change-of-authorization messages, such as packet mirroring attributes and Service Manager attributes, from the RADIUS server. The **no** version restores the default, in which support for RADIUS-initiated change-of-authorization messages is disabled on the router.

**Mode** RADIUS Configuration

**Related Documentation**

- [Configuring RADIUS-Based Mirroring](#)

## auth-router-name

---

**Syntax** [ no ] auth-router-name [ *routerName* ]

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Assigns an access virtual router. The **no** version restores the default router.



.....  
**NOTE:** This command replaces the deprecated **router-name** command, which may be removed completely in a future release.  
.....

**Options** • *routerName*—Name of the virtual router; string of 1–32 alphanumeric characters

**Mode** Domain Map Configuration

## auto-configure

**Syntax** `auto-configure upperInterfaceType [ lockout-time { minValue maxValue | none } ]`  
`no auto-configure upperInterfaceType [ lockout-time ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the type(s) of dynamic encapsulations that are accepted or detected by the static ATM 1483 interface. Optionally, specifies the lockout time range for the encapsulation type. You can enter this command repeatedly in Subinterface Configuration mode to support multiple dynamic interface types. The **no** version terminates detection of the specified encapsulation type or, if the **lockout-time** keyword is specified, restores the lockout time range to its default values.

Encapsulation type lockout is performed on a per-encapsulation-type basis for each subinterface. An encapsulation type not configured for autodetection with this command is automatically locked out. The lockout temporarily prevents the static ATM 1483 subinterface from detecting, accepting, and creating the encapsulation type until the lockout time expires.



### NOTE:

- Encapsulation type lockout is available for bridged Ethernet, IP, PPP, and PPPoE encapsulation types.
- Disabling lockout can result in undesirable CPU loading; we recommend that you not disable lockout for general use. At a minimum, use the default lockout time.

- Options**
- *upperInterfaceType*—One of the following dynamic encapsulation types:
    - bridgedEthernet
    - ip
    - ppp
    - pppoe
  - *minValue*—Minimum lockout time in the range 1–86400 seconds (24 hours); default value is 1 second
  - *maxValue*—Maximum lockout time in the range 1–86400 seconds (24 hours); default value is 300 seconds (5 minutes)
  - none—Disables lockout for the specified dynamic encapsulation type

**Mode** Interface Configuration, Subinterface Configuration

## auto-configure atm1483

---

**Syntax** [ no ] auto-configure atm1483

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the static ATM AAL5 interface to support autodetection of an ATM 1483 dynamic encapsulation type. The **no** version terminates autodetection of the ATM 1483 encapsulation type.

**Mode** Interface Configuration

## auto-configure vlan

---

**Syntax** [ no ] auto-configure vlan

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Configures the static VLAN major interface to support autodetection of a dynamic VLAN subinterface. The **no** version terminates autodetection of the VLAN subinterface.

**Mode** Interface Configuration

## auto-cost reference-bandwidth

---

**Syntax** [ no ] auto-cost reference-bandwidth *refBw*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls how OSPFv3 calculates default metrics for the interface. The **no** version assigns cost based only on the interface type.

**Options**

- *refBw*—Bandwidth in megabits per second in the range 1–4294967; default value is 100

**Mode** Router Configuration

## automatic-virtual-link

---

**Syntax** [ no ] automatic-virtual-link

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables or disables automatic virtual link configuration. The **no** version disables an automatic virtual link.

**Mode** Router Configuration

## auto-summary

---

**Syntax** [ no ] auto-summary

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Reenables the automatic summarization of routes redistributed into BGP to their natural network masks. Automatic summarization is enabled by default. The **no** version disables automatic summarization.

**Mode** Address Family Configuration, Router Configuration



## average-length-exponent

---

**Syntax**    `average-length-exponent exponent`  
              `no average-length-exponent`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the exponent used to weight the average queue length over time, controlling WRED responsiveness. The **no** version negates the average-length-exponent.

**Options**    • *exponent*—Total average queue length (TAQL) coefficient

**Mode**    Drop Profile Configuration

**Related Documentation**    • Configuring RED  
                                  • Configuring WRED

## avp

---

**Syntax**    *avp avpType action*

*no avp avpType*

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Configures the L2TP tunnel switching behavior for a specified L2TP AVP type. The **no** version restores the default L2TP tunnel switching behavior for AVPs of the specified type.

- Options**
- *avpType*—One of the following L2TP AVPs
    - *bearer-type*—L2TP Bearer Type AVP 18; by default, the router regenerates this AVP at the outbound LAC session, based on the local policy that is in effect
    - *calling-number*—L2TP Calling Number AVP 22; by default, the router regenerates this AVP at the outbound LAC session, based on the local policy that is in effect
    - *cisco-nas-port*—Cisco NAS Port Info AVP 100; by default, the router drops this AVP
  - *action*—One of the following actions that characterize the tunnel switching behavior; currently, only the **relay** action is supported
  - *relay*—Causes the router to preserve the value of an incoming AVP of the specified type when packets are switched between an inbound LNS session and an outbound LAC session

**Mode**    L2TP Tunnel Switch Profile Configuration

## CHAPTER 3

# B Commands

## backup-address-pool-name

---

**Syntax**    backup-address-pool-name *poolName*  
              no address-pool-name

**Release Information**    Command introduced in JunosE Release 10.0.0.

**Description**    Specifies a backup local address pool name to associate with the domain name being configured. This pool is used to assign IP addresses to users, if the primary local pool has been fully allocated. The **no** version removes the backup pool name.



.....  
**NOTE:** You must configure a primary local address pool for the backup local address pool to take effect.  
.....

**Options**    • *poolName*—Name of the backup pool to associate with the domain name; string of up to 16 alphanumeric characters

**Mode**    Domain Map Configuration

**Related Documentation**    • Local Address Servers Configuration Overview

## bandwidth

---

**Syntax**    `bandwidth bandwidth`  
`no bandwidth`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the total bandwidth available on the interface. For total reservable bandwidth, see the [mpls bandwidth](#) command. The **no** version removes the admission control configuration from the interface.

**Options**    • *bandwidth*—Available bandwidth in kilobits per second, a value from 1–10,000,000

**Mode**    Interface Configuration, Subinterface Configuration

**Related Documentation**    • [ospf bandwidth](#)

## bandwidth oversubscription

---

**Syntax** [ no ] bandwidth oversubscription

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Allows the line modules to operate below line rate performance. The **no** version forces the line modules to operate at line rate performance.

**Mode** Privileged Exec

## banner

---

**Syntax**    `banner [ motd | login | exec ] bannerText`  
              `no banner [ motd | login | exec ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures message-of-the-day, login, or exec banners to be displayed by the CLI. If you do not specify an option, the behavior is the same as if you specified the **motd** option. The **no** version deletes the banner.

**Options**

- **motd**—Displays the banner when a console or vty connection is initiated
- **login**—Displays the banner before any user authentication (line or RADIUS authentication); the banner is also displayed if user authentication is not configured
- **exec**—Displays the banner after user authentication (if any) and before the first prompt of a CLI session
- ***bannerText***—Alphanumeric string truncated at 1024 characters; delimited by the first character of the string, which must be repeated at the end of the string and must not occur anywhere else in the string

**Mode**    Global Configuration

## baseline aaa

---

**Syntax**    baseline aaa

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for authentication and authorization statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec



## baseline aaa route-download

---

**Syntax**    baseline aaa route-download [ ipv6 ]

**Release Information**    Command introduced in JunosE Release 8.1.0.  
                              **ipv6** keyword added in JunosE Release 13.0.0.

**Description**    Sets a statistics baseline for route downloads. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**    • **ipv6**—Sets a baseline for IPv6 route downloads

**Mode**    Privileged Exec

## baseline atm vp interface

---

**Syntax**    baseline atm vp interface atm *interfaceSpecifier* *vpi*

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for an ATM virtual path (VP) interface. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**

- *interfaceSpecifier*—ATM interface specifier; see [Interface Types and Specifiers on page 5](#)
- *vpi*—Virtual path identifier of the PVC. The numeric range depends on the line module capabilities and current configuration.

**Mode**    Privileged Exec

## baseline bridge

---

**Syntax**    `baseline bridge { bridgeGroupName | vplsName }`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for a bridge group or VPLS instance. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**

- *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command
- *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command

**Mode**    Privileged Exec

**Related Documentation**

- [Setting the Baseline for VPLS Statistics](#)

## baseline bridge interface

---

**Syntax**    baseline bridge interface *interfaceType interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for a specified network interface belonging to a bridge group or VPLS instance. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.



.....  
**NOTE:** Using the **baseline bridge interface** command for a VPLS instance affects the specified network interface associated with the VPLS instance, but has no effect on the VPLS virtual core interface, which represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices. To set a statistics baseline for the VPLS virtual core interface, use the **baseline bridge interface vpls** command.  
.....

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - atm
    - fastEthernet
    - gigabitEthernet
    - tenGigabitEthernet
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

**Related Documentation**

- [Setting the Baseline for VPLS Statistics](#)

## baseline bridge interface vpls

---

**Syntax**    baseline bridge interface vpls *vplsName*

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for a VPLS instance on the VPLS virtual core interface, which represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.



**NOTE:** Using the **baseline bridge interface vpls** command affects the VPLS virtual core interface, but has no effect on the network interfaces associated with the VPLS instance. To set a statistics baseline for a VPLS network interface, use the **baseline bridge interface** command.

**Options**    • *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command

**Mode**    Privileged Exec

**Related Documentation**    • Setting the Baseline for VPLS Statistics

## baseline clns

---

**Syntax**    `baseline clns [ interfaceType interfaceSpecifier ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for CLNS. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**

- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline cops

---

**Syntax**    baseline cops

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a baseline for the Common Open Policy Service (COPS) statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline dhcp

---

**Syntax**    baseline dhcp { server | relay }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for DHCP relay and DHCP relay proxy statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**

- server—Sets baseline for DHCP proxy server statistics
- relay—Sets baseline for DHCP relay statistics

**Mode**    Privileged Exec

**Related Documentation**

- Setting Baselines for DHCP Statistics



---

## baseline frame-relay interface

---

**Syntax** baseline frame-relay interface *interfaceType interfaceSpecifier* [ *dlci* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets a statistics baseline for Frame Relay and MLFR interfaces, subinterfaces, and circuits. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - mlframe-relay
    - pos
    - serial
    - tunnel
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *dlci*—DLCI number to be used on the specified subinterface to identify a virtual circuit in the range 16–1007

**Mode** Privileged Exec

## baseline frame-relay multilinkinterface

---

**Syntax**    baseline frame-relay multilinkinterface *interfaceType interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for MLFR links. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - serial
    - pos
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline hdlc interface

---

**Syntax** baseline hdlc interface *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets a statistics baseline for Cisco HDLC interfaces. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - pos
    - serial
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Privileged Exec

## baseline interface

---

**Syntax**    `baseline interface interfaceType interfaceSpecifier [ vcd ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for an interface or a specific ATM virtual circuit. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *vcd*—Virtual circuit descriptor; number in the range 1–4294967295; an identifier for the VC in other commands (ATM interfaces only)

**Mode**    Privileged Exec

## baseline ip

---

**Syntax**    `baseline ip [ vrf vrfName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the baseline on general IP traffic statistics as the current value. There is no **no** version.

**Options**    • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters

**Mode**    Privileged Exec

## baseline ip bgp

---

**Syntax**    baseline ip bgp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the baseline on all BGP statistics as the current value. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip dhcp-external

---

<b>Syntax</b>	baseline ip dhcp-external
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Sets a baseline for DHCP external server statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no <b>no</b> version.
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Setting Baselines for DHCP Statistics</a></li></ul>

## baseline ip dhcp-local

---

**Syntax**    baseline ip dhcp-local [ interface *interfaceType* *interfaceSpecifier* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for DHCP local server statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**    • *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)

- atm
- fastEthernet
- gigabitEthernet
- tenGigabitEthernet

• *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec



## baseline ip dvmrp

---

**Syntax**    baseline ip dvmrp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for DVMRP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip http

---

**Syntax**    baseline ip http

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Sets a baseline for HTTP local server statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip igmp

---

**Syntax**    baseline ip igmp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for IGMP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip igmp-proxy interface

---

**Syntax**    baseline ip igmp-proxy interface

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the baseline on all IGMP statistics by setting the counters for the numbers of queries received and reports sent on the upstream interface to zero. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip interface

---

**Syntax**    `baseline ip interface [ vrf vrfName ] interfaceType interfaceSpecifier`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for IP interface statistics. There is no **no** version.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline ip mobile home-agent

---

**Syntax**    baseline ip mobile home-agent

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Sets a statistics baseline for a specified Mobile IP home agent for control traffic. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip nat

---

**Syntax**    baseline ip nat

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for NAT statistics and counters. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip ospf

---

**Syntax**    baseline ip ospf

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for OSPF statistics and counters. There is no **no** version.

**Mode**    Privileged Exec



## baseline ip rip

---

**Syntax**    baseline ip rip

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for RIP interfaces. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip tunnel-reassembly

---

**Syntax**    baseline ip tunnel-reassembly

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Sets a statistics baseline for tunnel reassembly statistics on the current virtual router. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever you retrieve baseline-relative statistics. There is no **no** version.

**Mode**    Privileged Exec

## baseline ip udp

---

**Syntax**    `baseline ip udp [ vrf vrfName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for UDP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**    • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters

**Mode**    Privileged Exec

## baseline ip vrrp

---

**Syntax**    baseline ip vrrp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for VRRP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ipv6

---

**Syntax**    baseline ipv6 [ udp ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the baseline on general IPv6 traffic statistics as the current value. Use the **udp** keyword to set a baseline for UDP statistics. There is no **no** version.

**Options**    • udp—Sets a baseline for UDP statistics

**Mode**    Privileged Exec

## baseline ipv6 dhcpv6-local

---

**Syntax**    baseline ipv6 dhcpv6-local

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for DHCPv6 local server statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

**Related Documentation**

- Setting Baselines for DHCP Statistics

## baseline ipv6 interface

---

**Syntax**    `baseline ipv6 interface interfaceType interfaceSpecifier`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for IPv6 interface statistics. There is no **no** version.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline ipv6 local ndra-pool

---

<b>Syntax</b>	baseline ipv6 local ndra-pool
<b>Release Information</b>	Command introduced in JunosE Release 13.0.0.
<b>Description</b>	Sets a baseline for the IPv6 local Neighbor Discovery router advertisement pool prefix assignment statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no <b>no</b> version.
<b>Mode</b>	Privileged Exec, User Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring IPv6 Neighbor Discovery Local Address Pools</a></li></ul>



## baseline ipv6 local pool

---

**Syntax**    baseline ipv6 local pool

**Release Information**    Command introduced in JunosE Release 10.1.0.

**Description**    Sets a baseline for the IPv6 local pool prefix assignment statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec, User Exec

## baseline ipv6 mld

---

**Syntax**    baseline ipv6 mld

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for MLD statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ipv6 mld-proxy interface

---

**Syntax**    baseline ipv6 mld-proxy interface

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the baseline on all MLD statistics by setting the counters for the numbers of queries received and reports sent on the upstream interface to zero. There is no **no** version.

**Mode**    Privileged Exec

## baseline ipv6 ospf

---

**Syntax**    baseline ipv6 ospf [ *processId* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for OSPFv3 statistics and counters. There is no **no** version.

**Options**    • *processId*—Integer in the range 1–65535

**Mode**    Privileged Exec

## baseline ipv6 tcp

---

**Syntax**    `baseline ipv6 tcp [ vrf vrfName ] [ localAddress localPort remoteAddress remotePort ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              `ip` keyword removed and `ipv6` keyword added in JunosE Release 7.2.0.

**Description**    Sets a statistics baseline for only IPv6 TCP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no `no` version.

**Options**

- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
- *localAddress*—Local IPv6 address on the router
- *localPort*—Local TCP port number on the router
- *remoteAddress*—IPv6 address of remote router
- *remotePort*—TCP port number on remote router

**Mode**    Privileged Exec

## baseline line interface sonet

---

**Syntax**    baseline line interface sonet *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for SONET/SDH statistics at the line layer. The router implements the baseline by reading and storing the MIB statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**    • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline local pool

---

**Syntax**    baseline local pool

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for the router local address pool statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline log

---

**Syntax**    `baseline log [ last-reset | time [ utc ] month day year ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for logging events. To use the current system time, do not enter any options. There is no **no** version.

- Options**
- **last-reset**—Causes the router to display log messages generated since the last time the router was reset
  - **time**—Time and date after which the router displays messages that are timestamped. To set the time, use the following syntax:  
*Hour:Minute[:Second]*—Current time in 24-hour format; seconds are optional
  - **utc**—Indicates that the time entered is UTC (GMT) time; if you do not include this keyword, the router considers the time entered to be local time
  - **month**—Name of the month in English
  - **day**—Number of the day in the range 1–31
  - **year**—Four-digit number of the year

**Mode**    Privileged Exec



## baseline mpls interface

---

<b>Syntax</b>	baseline mpls interface <i>interfaceName</i>
<b>Release Information</b>	Command introduced in JunosE Release 7.1.0.
<b>Description</b>	Sets a statistics baseline for the specified MPLS major interface or MPLS shim interface. By default, the interface counters are baselined at zero. There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>interfaceName</i>—Name of interface; up to 15 alphanumeric characters</li></ul>
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Setting Baselines for Layer 2 Services over MPLS Statistics</li></ul>

## baseline mpls label

---

**Syntax**    baseline mpls label { interface *interfaceName* atm *vpi vci* | *labelValue* }

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for the specified MPLS in label. Statistics for an in label must be enabled with the **mpls statistics label** command before they can be baselined. By default, the in-label counters are baselined at zero. There is no **no** version.

- Options**
- *interfaceName*—Name of interface for label in interface label space on an ATM AAL5 interface; up to 15 alphanumeric characters
  - *vpi*—Virtual path identifier for a label, a value in the range 0–255
  - *vci*—Virtual circuit identifier for a label, a value in the range 33–65535
  - *labelValue*—Integer identifying a label in the platform label space, a value in the range 16–1048575

**Mode**    Privileged Exec

## baseline mpls next-hop

---

**Syntax**    `baseline mpls next-hop nextHopIndex`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for the specified MPLS next hop. Statistics for a next hop must be enabled with the **mpls statistics next-hop** command before they can be baselined. By default, the next-hop counters are baselined at zero. There is no **no** version.

**Options**

- *nextHopIndex*—Number identifying a next hop; displayed by the **show mpls forwarding** command

**Mode**    Privileged Exec

## baseline mpls tunnel

---

**Syntax**    baseline mpls tunnel *tunnelName*

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for the specified MPLS tunnel. Statistics for a tunnel must be enabled with the **mpls statistics policy** command before they can be baselined. By default, the next-hop counters are baselined at zero. There is no **no** version.

**Options**    • *tunnelName*—Name identifying a tunnel; displayed by the **show mpls tunnels** command

**Mode**    Privileged Exec

## baseline path interface sonet

---

**Syntax**    baseline path interface sonet *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for SONET/SDH statistics at the path layer. The router implements the baseline by reading and storing the MIB statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**    • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline ppp interface

---

**Syntax**    baseline ppp interface { atm | fastEthernet | gigabitEthernet | serial | mlppp | pos } *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **fastEthernet** and **gigabitEthernet** keywords added in JunosE Release 11.0.0

**Description**    Sets a statistics baseline for PPP interfaces. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**

- atm—Specifies an ATM interface
- fastEthernet—Specifies a Fast Ethernet interface
- gigabitEthernet—Specifies a Gigabit Ethernet interface
- mlppp—Specifies an MLPPP interface
- pos—Specifies a POS interface
- serial—Specifies a serial interface
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

---

## baseline pppoe interface

---

**Syntax** baseline pppoe interface *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets a statistics baseline for PPPoE interfaces, subinterfaces, and/or circuits. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - atm
    - fastEthernet
    - gigabitEthernet
    - lag
    - serial—PPPoE is not currently supported on serial interfaces
    - tenGigabitEthernet
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Privileged Exec

## baseline radius

---

**Syntax**    baseline radius

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for RADIUS statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec



## baseline radius dynamic-request

---

**Syntax** baseline radius dynamic-request

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets a statistics baseline for RADIUS dynamic-request statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode** Privileged Exec

**Related Documentation**

- [Monitoring Packet Mirroring Overview](#)

## baseline radius relay

---

**Syntax**    baseline radius relay

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for RADIUS relay statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline section interface sonet

---

**Syntax**    baseline section interface sonet *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a statistics baseline for SONET/SDH statistics at the section layer. The router implements the baseline by reading and storing the MIB statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Options**    • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## baseline show-delta-counts

---

**Syntax** [ no ] baseline show-delta-counts

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the router to always display the statistics relative to the most recent appropriate baseline. The **no** version removes the configuration.

**Mode** Global Configuration

## baseline snmp

---

**Syntax**    baseline snmp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for SNMP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline ssc

---

**Syntax**    baseline ssc

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Sets a baseline for the SRC statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec

## baseline suspicious-control-flow-detection counts

---

**Syntax** baseline suspicious-control-flow-detection counts

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Sets a baseline for statistics for suspicious control flow detection. There is no **no** version.

**Mode** Privileged Exec, User Exec

## baseline tacacs

---

**Syntax**    baseline tacacs

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a baseline for TACACS+ statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

**Mode**    Privileged Exec



## baseline tcp

**Syntax** `baseline [ ip | ipv6 ] tcp [ vrf vrfName ] [ localAddress localPort remoteAddress remotePort ]`

**Release Information** Command introduced in JunosE Release 7.2.0.  
**ip** keyword made optional in JunosE Release 7.2.0.  
**ipv6** keyword added in JunosE Release 7.2.0.

**Description** Sets a baseline for all TCP statistics or for only IPv4 or IPv6 TCP statistics. The router implements the baseline by reading and storing the statistics at the time the baseline is set and then subtracting this baseline whenever baseline-relative statistics are retrieved. There is no **no** version.

- Options**
- **ip**—Implements a baseline for only IPv4 statistics
  - **ipv6**—Implement a baseline for only IPv6 statistics
  - **vrfName**—Name of the VRF; string of 1–32 alphanumeric characters
  - **localAddress**—Local IP or IPv6 address on the router
  - **localPort**—Local TCP port number on the router
  - **remoteAddress**—IP or IPv6 address of remote router
  - **remotePort**—TCP port number on remote router

**Mode** Privileged Exec

## bert

**Syntax**    bert pattern *pattern* interval *time* [ unframed ]  
               no bert

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables bit error rate tests using the specified pattern on T3 interfaces on channelized and unchannelized T3 modules. The **no** version stops the test that is running.



**NOTE:** The BERT patterns supported can vary depending on the line module and I/O module assembly you are using.

- Options**
- *pattern*—One of the following test patterns:
    - 0s—Repetitive test pattern of all zeros, 00000...
    - 1s—Repetitive test pattern of all ones, 11111...
    - 2^9—Pseudorandom test pattern, 511 bits in length
    - 2^11—Pseudorandom test pattern, 2047 bits in length
    - 2^15—Pseudorandom test pattern, 32,767 bits in length
    - 2^20-O153—Pseudorandom test pattern, 1,048,575 bits in length
    - 2^20-QRSS—Pseudorandom QRSS test pattern, 1,048,575 bits in length
    - 2^23—Pseudorandom test pattern, 8,388,607 bits in length
    - alt-0-1—Repetitive alternating test pattern of zeros and ones, 01010101...
  - *time*—Duration of the test in the range 1–1440 minutes
  - unframed—(available for E1 and T1 interfaces only) if specified, the test bit pattern occupies all bits on the link, overwriting the framing bits; if not specified, the test bit pattern occupies only the payload bits

**Mode**    Controller Configuration

## bfd adapt

---

**Syntax** [ no ] bfd adapt

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Enables all BFD sessions to adapt timer intervals on all virtual routers on the router. The **no** version disables subsequent BFD sessions from adapting timer intervals without resetting any already adapted intervals.

**Mode** Global Configuration

## bgp advertise-best-external-to-internal

---

**Syntax** [ no ] bgp advertise-best-external-to-internal

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Causes the BGP selection process to select two best routes to every destination. BGP advertises to external peers the best route selected from the complete set of routes known to that destination. BGP advertises to internal peers the best route from the set of routes received from external and confederation peers. The **no** version restores the default condition, wherein BGP selects only one best route for each destination from the complete set of routes; if the best route was received from an internal peer, BGP does not advertise any route to that destination to the internal peers.

**Mode** Router Configuration

## bgp advertise-inactive

---

**Syntax** [ no ] bgp advertise-inactive

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the advertisement of inactive BGP received routes—routes that are considered by BGP to be “best routes” and therefore are present in the IP forwarding table, but that are *not* being used for forwarding. The **no** version restores the default state of normal route advertisement, whereby BGP advertises received routes only if they are in the IP forwarding table and are being used to forward traffic, or if synchronization is enabled.

**Mode** Router Configuration

## bgp always-compare-med

---

**Syntax** [ no ] bgp always-compare-med

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the comparison of the MED for paths from neighbors in different ASs. The **no** version disables the feature.

**Mode** Router Configuration

## bgp bestpath med confed

---

**Syntax** [ no ] bgp bestpath med confed

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that BGP considers the MED when comparing routes originated from different sub-ASs within the confederation to which this BGP speaker belongs. The **no** version restores the default state, where the MED attribute is not considered.

**Mode** Router Configuration

## bgp bestpath missing-as-worst

---

**Syntax** [ no ] bgp bestpath missing-as-worst

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that a route with a MED is always considered to be better than a route without a MED by causing the missing MED attribute to have a value of infinity. The **no** version restores the default state, where the missing MED attribute is considered to have a value of zero.

**Mode** Router Configuration



## bgp client-to-client reflection

---

**Syntax** [ no ] bgp client-to-client reflection

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Restores route reflection from a BGP route reflector to clients. The **no** version disables client-to-client reflection. By default, BGP reflects routes received from any route reflector client to all other route reflector clients. This command can be used to disable or restore this behavior.

**Mode** Router Configuration

## bgp cluster-id

---

**Syntax**    `bgp cluster-id { clusterId | ipAddress }`  
             `no bgp cluster-id [ clusterId | ipAddress ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a cluster ID if the BGP cluster has more than one route reflector. The **no** version causes BGP to use the router ID as the cluster ID.

- Options**
- *clusterId*—Number in the range 0–4294967295; the cluster ID of this router acting as a route reflector
  - *ipAddress*—Cluster ID of this router acting as a route reflector specified as an IP address

**Mode**    Router Configuration

## bgp confederation identifier

---

**Syntax**    `bgp confederation identifier autonomousSystem`  
              `no bgp confederation identifier [ autonomousSystem ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a BGP confederation identifier. The **no** version removes a BGP confederation identifier.

**Options**    • *autonomousSystem*—Number in the range 1–4294967295; the confederation identifier

**Mode**    Router Configuration

## bgp confederation peers

**Syntax** `bgp confederation peers { autonomousSystem [ autonomousSystem ]* | filter-list filterListName }`

```
no bgp confederation peers [ autonomousSystem [ autonomousSystem ]* |  
filter-list filterListName ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.

<b>Description</b>	Specifies the sub-ASs that belong to a confederation by listing individual AS numbers or by reference to an AS-path access list (the filter list). If the remote AS of a peer appears in the list of sub-AS numbers or in the filter list, then the peer is considered to be in the same confederation. The <b>no</b> version removes individually specified sub-ASs, all sub-ASs specified by the filter list, or all sub-ASs from the confederation.
--------------------	--

**Options**

- *autonomousSystem*—AS number in the range 1– 4294967295
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line
- *filterListName*—Name of an AS-path access list; a string of up to 32 characters

Mode Router Configuration

## bgp dampening

**Syntax** [ no ] bgp dampening [ *halfLife* [ *reuse suppress maxSuppressTime*  
[ *halfLifeUnreachable* ] ] ] [ route-map *mapTag* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables BGP route dampening. The router assesses a penalty of 1000 each time a route flaps and adds this to any previously accumulated penalty value. Penalties are cumulative. The **no** version disables route flap dampening.

- Options**
- *halfLife*—Half-life period in minutes in the range 1–45; default value is 15. When a BGP route has been assigned a penalty, the penalty is decreased by half after the half-life period.
  - *reuse*—Reuse limit in the range 1–20000; default value is 750. As the penalty for a flapping route decreases and falls below this reuse limit, the route is unsuppressed. That is, the route is added back to the BGP table and used for forwarding.
  - *suppress*—Suppress limit in the range 1–20000; default value is 2000. A route is suppressed when its penalty exceeds this limit.
  - *maxSuppressTime*—Maximum suppression time in minutes in the range 1–255. This value is the maximum amount of time a route can be suppressed. The default value is four times the half-life value.
  - *halfLifeUnreachable*—Alternate half-life period in minutes for unreachable routes; a number in the range 1–45. If this value is not specified, the same half-life period is used for both reachable and unreachable routes.
  - *route-map*—Specifies that dampening can be applied to routes according to the route map behavior. If the route map *permits* a route, the route is subject to dampening. If the route map *denies* a route, the route is not subject to dampening. The route map can contain a *no dampening* clause that determines dampening characteristics.
  - *mapTag*—Name of the route map; a string of up to 32 alphanumeric characters.

**Mode** Address Family Configuration, Router Configuration

## bgp default ipv4-unicast

---

**Syntax** [ no ] bgp default ipv4-unicast

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Causes all neighbors subsequently created with the neighbor remote-as or neighbor peer-group commands to be automatically activated in the IPv4 unicast address family. The **no** version disables the IPv4 unicast address family on all neighbors.

**Mode** Address Family Configuration, Router Configuration

## bgp default local-preference

---

**Syntax**    `bgp default local-preference value`  
              `no bgp default local-preference [ value ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Changes the default local preference value. Generally, the default value of 100 allows you to easily define a particular path as less preferable than paths with no local preference attribute. The preference is sent to all routers in the local AS. The preferred path is the one with the highest preference value. The **no** version restores the default setting.

**Options**    • *value*—Local preference number in the range 0–4294967295

**Mode**    Router Configuration

## bgp default route-target filter

---

**Syntax** [ no ] bgp default route-target filter

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls whether incoming BGP routes are filtered according to membership in route-target communities. Automatic filtering is enabled by default. The **no** version disables automatic filtering.

**Mode** Router Configuration



## bgp enforce-first-as

---

**Syntax** [ no ] bgp enforce-first-as

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Forces BGP to compare the configured remote AS number of an external peer with the first AS in the AS path of routes received from the peer. If the AS numbers do not match, BGP sends the peer an error message. The **no** version restores the default condition, which does not perform the AS comparison.

**Mode** Router Configuration

## bgp fast-external-fallover

---

**Syntax** [ no ] bgp fast-external-fallover

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Automatically brings down a BGP session to any adjacent external peer immediately after the link fails (as opposed to waiting for the TCP connection to fail or the hold timer to expire). The **no** version disables automatic session termination.

**Mode** Router Configuration

---

## bgp graceful-restart

---

**Syntax** [ no | default ] bgp graceful-restart

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the BGP graceful restart capability globally, which enables BGP to maintain its forwarding state during a peer restart, avoiding network-wide route flaps and interruptions in traffic forwarding. Graceful restart is disabled by default. The **default** version restores the default condition, wherein graceful restart is disabled, and consequently, advertisement of the BGP graceful restart capability is stopped. The **no** version disables the graceful restart capability.



.....  
**NOTE:** The E Series router supports graceful restart, both as a receiving peer and a restarting peer.  
.....

**Mode** Router Configuration

## bgp graceful-restart path-selection-defer-time-limit

---

**Syntax**    `bgp graceful-restart path-selection-defer-time-limit seconds`  
             `no bgp graceful-restart path-selection-defer-time-limit [ seconds ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum time period after a peer session restart during which the best-path selection process is deferred. The period is measured from when the session is detected in a down state. The **no** version restores the default value, 360 seconds.

**Options**    • *seconds*—Integer in the range 1–3600; default value is 600 seconds

**Mode**    Router Configuration

## bgp graceful-restart restart-time

---

**Syntax**    `bgp graceful-restart restart-time seconds`

`no bgp graceful-restart restart-time [ seconds ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time period advertised to all peers during which a restart is expected to be complete on this BGP speaker. If the speaker does not reestablish peering sessions within this period, the peers flush all routes from this speaker that they marked as stale when the speaker restarted and the sessions went down. The **no** version restores the default value, 120 seconds.

**Options**    • *seconds*—Integer in the range 1–3600; default value is 120 seconds

**Mode**    Router Configuration

## bgp graceful-restart stalepaths-time

---

**Syntax**    `bgp graceful-restart stalepaths-time seconds`  
             `no bgp graceful-restart stalepaths-time [ seconds ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time period after a peer session restart for all peers during which BGP waits for an End-of-RIB marker from a peer before flushing all stale routes from that peer. The period is measured from when the session is detected in a down state. The **no** version restores the default value, 360 seconds.

**Options**    • *seconds*—Integer in the range 1–3600; default value is 360 seconds

**Mode**    Router Configuration

## bgp log-neighbor-changes

---

**Syntax** [ no ] bgp log-neighbor-changes

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Causes BGP to log a message of severity notice to the bgpNeighborChanges log whenever a peer enters or leaves the Established state for any reason. No other messages are logged to the bgpNeighborChanges log. The **no** version disables this log.

**Mode** Router Configuration

## bgp maxas-limit

---

**Syntax**    `bgp maxas-limit limit`  
              `no bgp maxas-limit [ limit ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Causes BGP to check the length of AS paths received in update messages and to not forward routes whose AS paths are greater than the specified length. The **no** version halts checking of the AS path length.

**Options**    • *limit*—Maximum acceptable length of a received AS path; number in the range 1–1000

**Mode**    Router Configuration



## bgp redistribute-internal

---

**Syntax** [ no ] bgp redistribute-internal

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Authorizes redistribution of internal BGP routes (in addition to external BGP routes) into protocols that have BGP route redistribution enabled. This command is not required for IBGP routes within a VRF, for which redistribution is always enabled. The **no** version restores the default, redistributing only external BGP routes.

**Mode** Router Configuration

## bgp router-id

---

**Syntax**    `bgp router-id ipAddress`

`no bgp router-id [ ipAddress ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the BGP identifier. The **no** version restores the router ID as the identifier.

**Options**    • *ipAddress*—IP address to be used as the BGP identifier; ignored if present in the **no** version

**Mode**    Router Configuration

## bgp shutdown

---

**Syntax** [ no ] bgp shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Administratively disables BGP. The **no** version reenables BGP.

**Mode** Router Configuration

## bgp wait-on-end-of-rib

---

**Syntax**    `bgp wait-on-end-of-rib seconds`  
              `no bgp wait-on-end-of-rib`

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Specifies how long BGP waits to receive an End-of-RIB marker sent by route-target address family peers to signal the peer has finished advertising route-target membership information. Applies to all peers in the route-target address family. The **no** version restores the default value.

**Options**    • *seconds*—Number of seconds BGP wait for End-of-RIB marker, in the range 1–3600; default is 60 seconds

**Mode**    Address Family Configuration, Router Configuration

## boolean-test

---

**Syntax** `boolean-test { comparison comparisonType | event eventOwner eventName  
| startup |  
value booleanValue }`

`no boolean-test [ comparison | event | startup | value ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines Boolean test values for the trigger that you are configuring, including comparison settings, a Boolean value, a startup condition, and binding an event to the boolean-test trigger. The **no** version deletes the Boolean-test values for this trigger or removes either the startup condition or event binding.

- Options**
- *comparisonType*—One of the following types of Boolean comparison to perform: (equal, greater, greaterOrEqual, less, lessOrEqual, unequal
  - *eventOwner*—Name of event owner that partially specifies event to trigger the Boolean test; string of up to 32 alphanumeric characters
  - *eventName*—Name of event that partially specifies event to trigger the Boolean test; string of up to 32 alphanumeric characters
  - startup—Specifies not to perform the Boolean comparison when this trigger first becomes active
  - *booleanValue*—Value in the range -2147483648–2147483647 to use for the Boolean test

**Mode** SNMP Trigger Configuration

## boot backup

---

**Syntax**    `boot backup relFilename { cnfFilename | scrFilename | factory-defaults }`  
              `no boot backup`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the release and the configuration to be used the next (and every subsequent) time the boot logic chooses backup mode. The **no** version removes the setting.

- Options**
- *relFilename*—System software file
  - *cnfFilename*—Name of an existing configuration file (.cnf)
  - *scrFilename*—Name of an existing script file (.scr)
  - *factory-defaults*—Specifies that the router reverts to factory default configuration when rebooted

**Mode**    Global Configuration

## boot config

**Syntax** `boot config { cnfFilename [ once ] | scrFilename | running-configuration | startup-configuration | factory-defaults }`

`no boot config`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies how the router obtains its startup configuration. The **no** version clears a previous request to reboot in a specified manner; the next reboot uses the configuration saved in nonvolatile storage.



**CAUTION:** All **boot config** commands except for **boot config running-configuration** and **boot config startup-configuration** erase the existing running configuration when you reboot the router. Before executing this command, you might want to save the current configuration to a .cnf file using the **copy running-configuration** command.

- Options**
- *cnfFilename*—Name of an existing startup configuration file (.cnf) to be used on all subsequent reboots
  - *once*—Restores a configuration from the specified configuration file only on the next reboot. Subsequent reboots revert to the running-configuration settings.
  - *scrFilename*—Name of an existing script file (.scr)
  - *running-configuration*—Specifies that the running configuration is to be used for reboot; only available if the router is in Automatic Commit mode
  - *startup-configuration*—Specifies that the running configuration is to be used for reboot; only available if the router is in Manual Commit mode
  - *factory-defaults*—Specifies that the factory default configuration is to be used for the next reboot. Subsequent reboots revert to the running-configuration settings.

**Mode** Global Configuration

## boot force-backup

---

**Syntax** [ no ] boot force-backup

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Forces the router to use the backup software release file or router configuration file on the next boot. The **no** version sets the router to use the default release or configuration file on the next boot.



.....  
**NOTE:** After the router has used the backup settings, the **no boot force-backup** command is the only way to get the router to use the default settings again.  
.....

**Mode** Global Configuration



---

## boot hotfix

---

**Syntax**    `boot hotfix hfixFilename`  
`no boot hotfix { hfixFilename | all-releases }`

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Arms the specified hotfix as a startup hotfix that is automatically activated during system initialization when the SRP module is reloaded. The **no** version disarms the specified armed hotfix or all armed hotfixes.



.....  
**NOTE:** See also the `no boot hotfix all-releases` command.  
.....

- Options**
- *hfixFileName*—Name of a hotfix software file (.hfx) on the local file system
  - all-releases—Disarms all hotfixes currently armed for the armed release

**Mode**    Global Configuration

## boot revert-tolerance

---

**Syntax**    `boot revert-tolerance count time`  
`no boot revert-tolerance`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the reversion tolerances that the boot logic uses to determine whether the router should use the normal or backup settings. Issuing this command when high availability is enabled results in the system cold-restarting the router and using the backup settings if the tolerance settings are met. The **no** version restores the default reversion tolerance settings. The default settings are 3 crashes in 30 minutes.

- Options**
- *count*—Number of times the operational SRP software crashes; in the range 0–4294967295; default value is 3
  - *time*—Time in the range 0–4294967295 seconds in which the set number (count) of crashes occurs; the default setting is 1800

**Mode**    Global Configuration

## boot revert-tolerance never

---

**Syntax**    boot revert-tolerance never

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the boot logic to never revert to the backup release or configuration. There is no **no** version.

**Mode**    Global Configuration

## boot subsystem

---

**Syntax**    `boot [ backup ] subsystem subsysName relFileName`  
`no boot [ backup ] subsystem [ subsysName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the selected subsystem to use the specified release the next time the subsystem is booted. The **no** version disables the subsystem. The **backup** option enables you to specify a backup release for the module in the specified slot in case the module reboots more times than allowed within the period specified by the [boot revert-tolerance](#) command.

**Options**

- **backup**—Configures a backup setting
- *subsysName*—Name of the subsystem to be configured
- *relFileName*—Name of system software file to use

**Mode**    Global Configuration

---

## boot system

---

**Syntax**    `boot system relFileName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the software release (.rel) file to use on reboot. There is no **no** version.



---

**NOTE:** In a dual SRP module configuration, when this information is synchronized to the standby SRP module, the standby SRP module is reloaded to boot the specified release. The high availability feature requires the release to be the same on the active and the standby SRP modules. This means that arming the system to boot with a different release causes the standby module to reload and prevent high availability from becoming active or to disable high availability if it is active or pending.

---

**Options**    • *relFileName*—Name of the software release file (.rel) that contains the software release

**Mode**    Global Configuration

## bridge1483 dos-protection-group

---

**Syntax**    bridge1483 dos-protection-group *groupName*  
              no bridge1483 dos-protection-group

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches a bridge 1483 denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## bridge1483 mtu

---

**Syntax**    `bridge1483 mtu mtuSize`  
              `no bridge1483 mtu`

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Sets the maximum allowable size, in bytes, of the maximum transmission unit (MTU) for bridged Ethernet interfaces. The **no** version restores the default MTU size for bridged Ethernet interfaces, 1518 bytes.

**Options**    • *mtuSize*—Maximum allowable size of the MTU, in the range 64–9180 bytes; default value is 1518

**Mode**    Profile Configuration, Subinterface Configuration

## bridge1483 service-profile

---

**Syntax** [ no ] bridge1483 service-profile *profileName*

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Assigns the specified IP service profile to the interface profile from which a dynamic bridged Ethernet interface is created. The IP service profile must be defined in the default virtual router. The **no** version removes the IP service profile assignment from the interface profile.

**Options** • *profileName*—Name of the IP service profile; maximum of 32 alphanumeric characters

**Mode** Profile Configuration



---

## bridge

---

**Syntax** [ no ] bridge *bridgeGroupName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a bridge group to use for transparent bridging. A bridge group is a named collection of network interfaces (ports) on an E Series router that forms a broadcast domain. Each bridge group has its own set of forwarding tables and filters and, as such, functions as a logical bridging device. The **no** version removes the bridge group configuration from the router.

To configure an existing bridge group as a VPLS instance, you must use the [bridge vpls transport-virtual-router](#) command.



**NOTE:** Do not assign the bridge group the same name as an existing virtual router configured on the router.

**Options**

- *bridgeGroupName*—Name of the bridge group; string of up to 32 alphanumeric characters

**Mode** Global Configuration

## bridge acquire

---

**Syntax** [ no ] bridge { *bridgeGroupName* | *vplsName* } acquire

**Release Information** Command introduced before JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description** Configures a bridge group or VPLS instance to acquire dynamically learned MAC addresses. Issuing this command enables the router to forward any frames it receives for nodes (stations) whose addresses it has learned dynamically. The **no** version prevents the router or VPLS instance from acquiring dynamically learned MAC addresses, and limits forwarding only to those nodes that have a statically configured address entry in the forwarding table.

To configure the maximum number of MAC addresses that the router can learn, use the [bridge learn](#) command (for a bridge group or VPLS instance) or the [bridge-group learn](#) command (for a network interface associated with a bridge group or VPLS instance).

- Options**
- *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command
  - *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command

**Mode** Global Configuration

**Related Documentation**

- [Configuring Optional Attributes for VPLS Instances](#)

## bridge address

**Syntax** `bridge { bridgeGroupName | vplsName } address macAddress`  
`{ forward interfaceType interfaceSpecifier | discard }`  
`no bridge { bridgeGroupName | vplsName } address macAddress`

**Release Information** Command introduced before JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description** Enables a bridge group or VPLS instance to filter (forward or discard) frames based on their MAC address. Use this command to filter frames by a specific MAC address and to add a static (nonlearned) entry to the forwarding table. The **no** version removes the static MAC address entry from the forwarding table.



**NOTE:** For a VPLS instance, you cannot create a static (nonlearned) MAC address entry to forward to the VPLS virtual core interface.

- Options**
- *bridgeGroupName*—Name of a bridge group specified with the **bridge** command
  - *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command
  - *macAddress*—Unique 48-bit (6-byte) number that is programmed into each LAN network interface card (NIC) at the time of manufacture; also known as a hardware address or physical address. The MAC address format is a dotted triple of four-digit hexadecimal numbers; for example, 0090.1a40.4c7c
  - **forward**—Forwards frames destined for the specified MAC address out the specified network interface
  - *interfaceType*—One of the following interface types listed in “Interface Types and Specifiers” on page 5
    - atm
    - fastEthernet
    - gigabitEthernet
    - tenGigabitEthernet
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - **discard**—Discards (drops) frames sent from or destined for the specified MAC address without further processing

**Mode** Global Configuration

**Related Documentation**

- [Configuring Optional Attributes for VPLS Instances](#)

## bridge aging-time

---

**Syntax**    `bridge { bridgeGroupName | vplsName } aging-time seconds`  
               `no bridge { bridgeGroupName | vplsName } aging-time`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                               *vplsName* variable added in JunosE Release 7.1.0.

**Description**    Sets the aging time of a dynamic (learned) entry in the forwarding table of a bridge group or VPLS instance. The aging time is the length of time, in seconds, that an entry can remain in the forwarding table. An entry expires from the forwarding table when it reaches the specified aging time. The **no** version restores the default value, 300 seconds.

**Options**    • *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command  
               • *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command  
               • *seconds*—Aging time in the range 10–1000000 seconds

**Mode**    Global Configuration

**Related Documentation**    • [Configuring Optional Attributes for VPLS Instances](#)

## bridge crb

---

**Syntax** [ no ] bridge crb

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables concurrent routing and bridging (CRB) for all bridge groups configured on the router except those bridge groups configured as VPLS instances. When CRB is enabled, the router can route a protocol among a group of interfaces in one bridge group and concurrently bridge the same protocol among a separate group of interfaces in a different bridge group on the router. The **no** version disables CRB on all bridge groups and restores the default bridging capability.

The command takes effect for all bridge groups on the router not configured as VPLS instances; you cannot enable CRB for some bridge groups but not for others.

**Mode** Global Configuration

## bridge-group

**Syntax** `bridge-group { bridgeGroupName | vplsName }`  
`[ subscriber-trunk | snmp-trap link-status | learn addressCount ]`

`no bridge-group { bridgeGroupName | vplsName } [ subscriber-trunk | snmp-trap link-status | learn ]`

**Release Information** Command introduced before JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description** Assigns a network interface to a bridge group or VPLS instance. You can also use this command to configure the type of interface, enable SNMP link-status processing for the interface, and set the maximum number of dynamic MAC addresses that the interface can learn. The **no** version removes the network interface from the bridge group or VPLS instance and restores the default values for the interface type (subscriber client interface), SNMP link-status processing (disabled), or number of maximum learned MAC addresses (0 addresses).

- Options**
- *bridgeGroupName*—Name of the bridge group to which the interface belongs, as specified with the [bridge](#) command
  - *vplsName*—Name of the VPLS instance to which the interface belongs, as specified with the [bridge vpls transport-virtual-router](#) command
  - `subscriber-trunk`—Creates a trunk (server) interface in the bridge group or VPLS instance; if you omit this keyword, the router creates a subscriber (client) interface by default
  - `snmp-trap link-status`—Enables SNMP link-status processing only for the specified interface in the bridge group or VPLS instance
  - *addressCount*—Maximum number of MAC addresses that the interface in the bridge group or VPLS instance can learn, up to the maximum number that the router supports, in the range 0–64000

**Mode** Interface Configuration, Subinterface Configuration

**Related Documentation**

- [Configuring VPLS Network Interfaces](#)

## bridge learn

---

**Syntax**    `bridge { bridgeGroupName | vplsName } learn addressCount`  
`no bridge { bridgeGroupName | vplsName } learn`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description**    Sets the maximum number of dynamic MAC addresses that a bridge group or VPLS instance can learn. The **no** version restores the default value, 0 (zero) learned addresses. The default value implies that there is no maximum number of learned entries for an individual bridge group or VPLS instance; that is, a bridge group or VPLS instance can learn an unlimited number of MAC addresses, up to the maximum number that the router supports.

To enable or disable the ability of a bridge group or VPLS instance to learn dynamic MAC addresses, use the [bridge acquire](#) command.



.....  
**NOTE:** For information about the maximum number of learned MAC address entries combined for all bridge groups and VPLS instances supported per chassis, see *JunosE Release Notes, Appendix A, System Maximums*.  
.....

- Options**
- *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command
  - *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command
  - *addressCount*—Maximum number of MAC addresses that the bridge group can learn, in the range 0–64000

**Mode**    Global Configuration

**Related Documentation**

- [Configuring Optional Attributes for VPLS Instances](#)



## bridge route

**Syntax** [ no ] bridge *bridgeGroupName* route { ip | mpls | pppoe }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables routing of IP, MPLS, or PPPoE packets in a specified bridge group when concurrent routing and bridging (CRB) is enabled for all bridge groups on the router. The command uses the routing table entries to determine the path on which to send the packet toward its final destination. The **no** version disables routing of the specified protocol in the specified bridge group.

If you issue this command for a protocol that is not currently configured in the interface stack for that bridge group, the bridge group discards (drops) those packets.



**NOTE:** The **bridge route** command is available for a bridge group only after you issue the **bridge crb** command to enable CRB for all bridge groups on the router.

The **bridge route** command is not valid for bridge groups configured as VPLS instances. If you attempt to issue the **bridge route** command for a VPLS instance, the router displays an error message and rejects the command.

- Options**
- *bridgeGroupName*—Name of a bridge group specified with the **bridge** command
  - ip—Specifies that the bridge group routes IP packets
  - mpls—Specifies that the bridge group routes MPLS packets
  - pppoe—Specifies that the bridge group routes PPPoE packets

**Mode** Global Configuration

## bridge snmp-trap link-status

---

**Syntax** [ no ] bridge { *bridgeGroupName* | *vplsName* } snmp-trap link-status

**Release Information** Command introduced before JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description** Enables SNMP link-status processing for all network interfaces associated with a bridge group or VPLS instance. The **no** version disables SNMP link-status processing for all interfaces in the bridge group or VPLS instance.

**Options**

- *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command
- *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command

**Mode** Global Configuration

**Related Documentation**

- [Configuring Optional Attributes for VPLS Instances](#)

## bridge subscriber-policy

**Syntax**    `bridge { bridgeGroupName | vplsName } subscriber-policy subscriberPolicyName`  
               `no bridge { bridgeGroupName | vplsName } subscriber-policy`  
               `[ subscriberPolicyName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                               *vplsName* variable added in JunosE Release 7.1.0.

**Description**    Associates the subscriber (client) interfaces that belong to a bridge group or to a VPLS instance with a nondefault subscriber policy. The **no** version removes the association with the subscriber policy.

You cannot associate a nondefault subscriber policy with trunk (server) interfaces that belong to a bridge group or to a VPLS instance. You also cannot associate a nondefault subscriber policy with the VPLS virtual core interface, which acts as a trunk interface. The VPLS virtual core interface represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices.

- Options**
- *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command
  - *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command
  - *subscriberPolicyName*—Name of the subscriber policy specified with the `subscriber-policy` command

**Mode**    Global Configuration

## bridge vpls rd

**Syntax** `bridge vplsName vpls rd routeDistinguisher`  
`no bridge vplsName vpls rd`

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies the unique two-part route distinguisher for a VPLS instance that uses BGP as the signaling protocol. Because you cannot change or remove the route distinguisher for a VPLS instance after you set it, issuing the **no** version fails, and causes the router to display an error message.

The following rules apply when you configure the route distinguisher for a VPLS instance:

- After you set the route distinguisher for a VPLS instance, you cannot change it for that VPLS instance. To change the route distinguisher, you must either remove the transport virtual router configuration from the VPLS instance or delete the VPLS instance from the router. You can then reconfigure the VPLS instance with a new route distinguisher.
- Multiple VPLS instances that use the same transport virtual router cannot have the same route distinguisher. Conversely, multiple VPLS instances that use different transport virtual routers can have the same route distinguisher.

The **bridge vpls rd** command is not valid for a VPLS instance that uses LDP as the signaling protocol. To configure a VPLS instance with LDP signaling, use the [mpls ldp vpls vpls-id](#) command and the [mpls ldp vpls neighbor](#) command.



**NOTE:** The **bridge vpls rd** command is available for a VPLS instance only after you issue the [bridge vpls transport-virtual-router](#) command, which creates the VPLS instance and configures the transport virtual router.

- Options**
- *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command
  - *routeDistinguisher*—Unique two-part identifier in the format *number1:number2*, where:
    - *number1*—Autonomous system (AS) number or an IP address
    - *number2*—Unique integer; 32 bits if *number1* is an AS number; 16 bits if *number1* is an IP address

**Mode** Global Configuration

**Related Documentation**

- [Configuring VPLS Instances with BGP Signaling](#)

## bridge vpls route-target

**Syntax** [ no ] bridge *vplsName* vpls route-target { import | export | both } *extendedCommunity*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Creates or adds to a list of VPN extended communities that the router uses to determine which routes are imported by a VPLS instance that uses BGP as the signaling protocol. The **no** version removes a route target from the specified list.

A route is imported into the BGP address family for a specified VPLS instance when both of the following conditions are met:

- An update message with a route-target export list advertises a route.
- That list contains at least one route target that matches a route target in the route-target import list associated with a VPLS instance.

The **bridge vpls route-target** command is not valid for a VPLS instance that uses LDP as the signaling protocol. To configure a VPLS instance with LDP signaling, use the **mpls ldp vpls vpls-id** command and the **mpls ldp vpls neighbor** command.



**NOTE:** The **bridge vpls route-target** command is available for a VPLS instance only after you issue the **bridge vpls transport-virtual-router** command, which creates the VPLS instance and configures the transport virtual router.

- Options**
- *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command
  - **import**—Adds the route target to the specified VPLS instance's import list; the VPLS instance accepts only routes that have at least one route target that matches a route target in the import list
  - **export**—Adds the route target to the specified VPLS instance's export list; all routes advertised from this VPLS instance are associated with the export list
  - **both**—Adds the route target to both the import list and export list of the specified VPLS instance. This is the recommended setting for a VPLS instance
  - *extendedCommunity*—Two-part number in the format *number1:number2* that identifies an extended community of VPNs, where:
    - *number1*—Autonomous system (AS) number or an IP address
    - *number2*—Unique integer; 32 bits if *number1* is an AS number; 16 bits if *number1* is an IP address

**Mode** Global Configuration

**Related Documentation**

- [Configuring VPLS Instances with BGP Signaling](#)

## bridge vpls site-name site-id

**Syntax** [ no ] bridge *vplsName* vpls site-name *siteName* site-id *siteId*  
[ multi-homed priority *priority* ]

**Release Information** Command introduced in JunosE Release 7.1.0.  
**multi-homed priority** keywords and *priority* variable added in JunosE Release 9.3.0.

**Description** Configures a customer site name and a unique site identifier that belongs to the specified VPLS instance that uses BGP as the signaling protocol. Optionally configures the site to be multihomed. In a VPLS configuration, each customer site is represented by a customer edge (CE) device located at the edge of the customer's network. The router (VPLS edge device, also known as VE router) communicates with the customer site by means of a bridge network interface connection to the CE device. The **no** version removes the site name and site identifier from the VPLS instance, or removes the multihomed configuration for the customer site and returns it to a single-homed state.

The **bridge vpls site-name site-id** command is not valid for a VPLS instance that uses LDP as the signaling protocol. To configure a VPLS instance with LDP signaling, use the [mpls ldp vpls vpls-id](#) command and the [mpls ldp vpls neighbor](#) command.



**NOTE:** The **bridge vpls site-name site-id** command is available for a VPLS instance only after you issue the [bridge vpls transport-virtual-router](#) command, which creates the VPLS instance and configures the transport virtual router.

- Options**
- *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command
  - *siteName*—Name of the site; string of up to 128 alphanumeric characters
  - *siteId*—Numerical identifier for the site; must be an unsigned 16-bit integer greater than zero that is unique across the VPLS domain associated with the VPLS instance
  - *priority*—Number that sets the priority of this VPLS instance for a multi-homed site, in the range 1–65535; priority is sent in BGP advertisements as the Local-Preference attribute and determines whether the router hosting the VPLS instance becomes the designated VE router for this multihomed site

**Mode** Global Configuration

**Related Documentation**

- [Configuring VPLS Instances with BGP Signaling](#)

## bridge vpls site-range

---

**Syntax**    `bridge vplsName vpls site-range siteRange`  
`no bridge vplsName vpls site-range`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Configures the maximum number of customer sites that can participate in the specified VPLS domain that uses BGP as the signaling protocol. In a VPLS configuration, each customer site is represented by a customer edge (CE) device located at the edge of the customer's network. The router (VPLS edge device) communicates with the customer site by means of a bridge network interface connection to the CE device. The **no** version restores the default site range, 1.

The **bridge vpls site-range** command is not valid for a VPLS instance that uses LDP as the signaling protocol. To configure a VPLS instance with LDP signaling, use the **mpls ldp vpls vpls-id** command and the **mpls ldp vpls neighbor** command.



.....  
**NOTE:** The **bridge vpls site-range** command is available for a VPLS instance only after you issue the **bridge vpls transport-virtual-router** command, which creates the VPLS instance and configures the transport virtual router.  
.....

- Options**
- *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command
  - *siteRange*—Maximum number of sites that can participate in the VPLS domain, in the range 1–65534; default value is 1

**Mode**    Global Configuration

**Related Documentation**

- Configuring VPLS Instances with BGP Signaling



## bridge vpls transport-virtual-router

**Syntax**    `bridge vplsName vpls transport-virtual-router virtualRouterName`  
               `no bridge vplsName vpls transport-virtual-router`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Configures the transport virtual router for a VPLS instance that uses either BGP or LDP as the signaling protocol. Issuing this command creates a new VPLS instance on the router or causes an existing bridge group to become a VPLS instance. The **no** version removes the VPLS instance from the router and clears any attributes configured for the deleted VPLS instance.

A VPLS instance is a single instance of the virtual private LAN service (VPLS). VPLS employs a layer 2 virtual private network (VPN) to connect multiple individual LANs across a service provider's MPLS network. The multiple LANs function as a single virtual LAN.

The transport virtual router specifies the name of the virtual router on which the BGP or LDP instance that signals reachability for this VPLS instance is configured.

To create a new VPLS instance or configure an existing bridge group as a VPLS instance, you must issue the **bridge vpls transport-virtual-router** command before you issue any other commands to configure VPLS attributes; otherwise, the VPLS configuration fails.

- Options**
- *vplsName*—Name of the new VPLS instance, or name of an existing bridge group specified with the **bridge** command that you want to configure as a VPLS instance; string of up to 32 alphanumeric characters
  - *virtualRouterName*—Name of the virtual router on which the BGP or LDP instance that signals reachability for this VPLS instance is configured

**Mode**    Global Configuration

- Related Documentation**
- Configuring VPLS Instances with BGP Signaling
  - Configuring VPLS Instances with LDP Signaling

## broadcast

---

**Syntax** broadcast { permit | deny }

no broadcast

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Modifies the subscriber policy for the broadcast protocol to define whether the subscriber (client) interfaces that belongs to a bridge group or to a VPLS instance forward (permit) or filter (deny) broadcast packets. The **no** version restores the default value, deny broadcast packets.

You cannot change the default subscriber policy values for trunk (server) interfaces that belongs to a bridge group or to a VPLS interface. You also cannot change the default subscriber policy values for a VPLS virtual core interface, which acts as a trunk interface. The VPLS virtual core interface represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) device.

- Options**
- permit—Specifies that the subscriber interface associated with the bridge group or VPLS instance forwards broadcast packets
  - deny—Specifies that the subscriber interface associated with the bridge group or VPLS instance filters broadcast packets

**Mode** Subscriber Policy Configuration

## buffer-weight

---

**Syntax**    `buffer-weight bufferWeight`  
              `no buffer-weight`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the buffer weight of the queue. The **no** version returns the queue to its default buffer weight.

**Options**    • *bufferWeight*—Range 1–63; default value is 8

**Mode**    Queue Profile Configuration

**Related Documentation**    • [Configuring Queue Profiles to Manage Buffers and Thresholds](#)

## bulkstats

---

**Syntax**    no bulkstats

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    This command has only a **no** version. See the no bulkstats command for a complete description.

**Mode**    Router Configuration

## bulkstats collector

**Syntax** bulkstats collector *collectorIndex*  
 [ collect-mode { auto-xfer | on-file-full | manual-xfer } | description *descrip* |  
 interval *intrvl* | max-size *maxSize* | primary-receiver *primRecvIndex* |  
 secondary-receiver *secRecvIndex* | single-interval ]  
  
 no bulkstats collector *collectorIndex* [ collect-mode | description | interval | max-size  
 |primary-receiver | secondary-receiver | single-interval ]\*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates and configures a collector of bulk statistical data to collect MIB-2 ifTable MIB objects. You can configure up to six collectors. The **no** version restores the default value for specified options; if no options are specified, the **no** version deletes the collector.

- Options**
- *collectorIndex*—Number in the range 1–65535 that identifies the particular data collector
  - collect-mode—Specifies one of the following collection modes:
    - auto-xfer—Agent automatically transfers file when interval expires
    - on-file-full—Agent automatically transfers file when it is full
    - manual-xfer—Router or user-initiated transfers; default collection mode
  - *descrip*—Descriptive information to insert into the bulkstats file
  - *intrvl*—Time period in the range 300– 86400 seconds for which the collector transfers data from the router to the receivers; default interval is 360 seconds
  - *maxSize*—Maximum size of the file in the range 10240–20971520 bytes; default file size is 2,621,440 bytes
  - *primRecvIndex*—Number in the range 1–65535 that identifies the primary receiver to which the router transfers the data; by default the primary receiver is cleared
  - *secRecvIndex*—Number in the range 1–65535 that identifies the secondary (backup) receiver to which the router transfers the data; by default the secondary receiver is cleared
  - single-interval—Specifies that the collector retrieves the bulk statistics data only once; by default, the collector receives the data periodically
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## bulkstats file-format endOfLine-LF

---

**Syntax** [ no ] bulkstats file-format endOfLine-LF

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Removes the carriage return (CR) and leaves only a line feed (LF) at the end of each line in the bulkstats file. The **no** version returns the end of line format to the default, CR and LF.

**Mode** Global Configuration

## bulkstats interfaces description-format common

---

**Syntax** [ no ] bulkstats interfaces description-format common

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the conventional industry method of encoding the SNMP ifDescr object that the bulkstats application reports. The **no** version returns the encoding method to a proprietary encoding scheme.

**Mode** Global Configuration

## bulkstats interfaces rfc1213

---

**Syntax** [ no ] bulkstats interfaces rfc1213

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables RFC 1213 interface numbering mode on bulkstats. The **no** version disables RFC 1213 interface numbering mode on bulkstats.

**Mode** Global Configuration



## bulkstats interface-type

---

**Syntax** [ no ] bulkstats interface-type *interfaceType* [ *interfaceSpecifier* ]\*  
[ collector *collectorIndex* ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**mplsL2shim**, **mplsMajor**, and **mplsMinor** keywords added in JunosE Release 8.2.0.

**Description** Configures the interface type on which you want to collect statistics. The **no** version deletes the interface type from bulkstats collection.

- Options**
- *interfaceType*—One of the following interface types for which you can collect statistics: ATM, ATM 1483, Ethernet, Frame Relay, Frame Relay subinterface, Cisco HDLC, IP, MPLS minor, MPLS major, MPLS shim, PPP, VLAN subinterface
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line
  - *collectorIndex*—Number in the range 1–65535 that identifies the particular data collector. Always specify this option if you defined more than one collector.

**Mode** Global Configuration

## bulkstats receiver remote-name

---

**Syntax**    bulkstats receiver *receiverIndex* remote-name *remoteName.sts*  
              [ *receiverAttrib* [ *receiverAttrib* ]\* ]  
  
              no bulkstats receiver *receiverIndex* [ remote-name *remoteName* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the bulk statistics receiver parameters. The **no** version deletes the receiver.

- Options**
- *receiverIndex*—Number in the range 1–65535 that identifies the receiver of the data
  - *remoteName*—Composed of the remote host, path, filename, and formatters; include a .sts filename extension
  - *receiverAttrib*—One of the following dynamic attributes
    - *sysName*—Inserts the router name into the stored remote filename
    - *sysUpTime*—Inserts the router up time into the stored remote filename
    - *collectorSequence*—Inserts a sequence number into the stored remote filename
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## bulkstats schema

---

**Syntax**    `bulkstats schema schemaIndex [ collector collectorIndex ]`  
              `no bulkstats schema schemaIndex`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the schema for collecting bulk statistics. The **no** version removes the schema.

**Options**    • *schemaIndex*—Identifier for the schema in the range 1–65535  
              • *collectorIndex*—Identifier for the collector in the range 1–65535

**Mode**    Global Configuration

## bulkstats schema subtree

---

**Syntax**    bulkstats schema *schemaIndex* subtree  
              { if-stack | if-stats { subtreeelist [ *ifstatsList* [ *ifstatsList* ]\* ] |  
              if-create-delete-time-stats *interfaceType interfaceType* } | igmp | system }  
  
              bulkstats schema *schemaIndex* subtree  
              { if-stack | if-stats | igmp [ subtreeelist *igmpList* [ *igmpList* ]\* ] | system }  
  
              no bulkstats schema *schemaIndex*

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                             **mplsL2shim**, **mplsMajor**, and **mplsMinor** keywords added in JunosE Release 8.2.0.

**Description**            Configures the schema for collecting if-stack, if-stats, or router data. The **no** version removes the schema.

- Options**
- *schemaIndex*—Identifier for the schema in the range 1–65535
  - if-stack—Retrieves ifStackTable
  - if-stats—Retrieves ifTable/ifXTable counters
  - *ifstatsList*—Type of statistics and **time-offset** keyword, which includes the offset from the master interval at which the record was collected in each bulkstats interface record
  - if-create-delete-time-stats—Retrieves interface final statistics (interface statistics that may be lost during higher create or delete frequency)
  - *interfaceType*—One of the following interface types for which you can collect statistics: ATM 1483, IP, MPLS minor, MPLS major, MPLS shim, PPP
  - igmp—Retrieves IGMP statistics
  - *igmpList*—Type of statistics and **time-offset** keyword, which includes the offset from the master interval at which the record was collected in each bulkstats interface record
  - system—Retrieves sysUpTime and nvsUtilPct global statistics; retrieves slotDescr, the cpuUtilPct, and memUtilPct per-slot statistics
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**                    Global Configuration

## bulkstats schema subtree policy

---

**Syntax** bulkstats schema *schemaIndex* subtree policy [ policy-name *policyName* ]  
 [ policy-type *policyType* ] [ policy-subtreelist *policyList* [ *policyList* ]\* ]  
 no bulkstats schema *schemaIndex*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the schema to collect statistics on a specific policy, a type of policy, or based on color-coded tags applied by a policy. The **no** version removes the schema.

- Options**
- *schemaIndex*—Identifier for the schema in the range 1–65535
  - *policyName*—Name of policy for which you want to collect statistics
  - *policyType*—Select one of the following types:
    - input—Collect data on input policies
    - localInput—Collect data on local input policies
    - output—Collect data on output policies
  - *policyList* —Retrieves statistics based on color-coded tags applied by a policy
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## bulkstats schema subtree qos

---

**Syntax**    bulkstats schema *schemaIndex* subtree qos [ subtree-list *qosList* [ *qosList* ]\*]  
             export-summarized-stats ]

no bulkstats schema *schemaIndex*

**Release Information**    Command introduced in JunosE Release 11.1.0.

**Description**    Configures the bulk statistics schema to collect QoS statistics and configuration information on egress queues belonging to different interface types. The **no** version removes the schema.

- Options**
- *schemaIndex*—Identifier for the schema in the range 1–65535
  - *qosList*—Select one of the following queue attributes:
    - aggregate-drop-rate—Configures QoS schema to export the average drop rate within the rate-period specified in the statistics profile of the egress queue
    - all—Configures QoS schema to export all statistics; this is the default option
    - assured-rate—Configures QoS schema to export the assured rate attribute
    - burst—Configures QoS schema to export the burst attribute
    - byte-adjustment-bytes—Configures QoS schema to export the number of bytes configured for the byte-adjustment application, if the byte-adjustment application is enabled on the queue
    - byte-adjustment-type—Configures QoS schema to export the type of byte-adjustment, if byte-adjustment application is enabled on the queue
    - drop-profile—Configures QoS schema to export the drop profile name associated with the queue
    - forwarded-bytes—Configures QoS schema to export the number of bytes forwarded from the queue
    - forwarded-packets—Configures QoS schema to export the number of forwarded packets from the queue
    - forwarded-rate—Configures QoS schema to export the average forwarded rate within the rate period specified on the statistics profile of the queue
    - green-dropped-bytes—Configures QoS schema to export the number of bytes of green traffic that was dropped on this queue
    - green-dropped-packets—Configures QoS schema to export the number of packets of green traffic that was dropped on this queue
    - parent-shaping-rate—Configures QoS schema to export the shaping rate enabled on the parent interface in the scheduling hierarchy

- parent-shared-shaping-rate—Configures QoS schema to export the shared shaping rate enabled on the parent interface in the scheduling hierarchy
- parent-weight—Configures QoS schema to export the aggregate weight of the parent interface
- queue-length—Configures QoS schema to export the queue length attribute
- queue-profile—Configures QoS schema to export the queue profile name
- red-dropped-bytes—Configures QoS schema to export the number of bytes of red traffic that was dropped on the queue
- red-dropped-packets—Configures QoS schema to export the number of red packets that was dropped on the queue
- RED-enabled—Configures QoS schema to verify whether the Random Early Detect (RED) option is enabled on the queue
- scheduler-profile—Configures QoS schema to export the scheduler profile name
- shaping-mode—Configures QoS schema to export the shaping mode attribute
- shaping-rate—Configures QoS schema to export the shaping rate attribute
- shared-shaping-mode—Configures QoS schema to export the shared shaping mode attribute
- shared-shaping-rate—Configures QoS schema to export the shared shaping rate attribute
- statistics-profile—Configures QoS schema to export the statistics profile name
- weight—Configures QoS schema to export the weight assigned to the queue
- yellow-dropped-bytes—Configures QoS schema to export the number of bytes of yellow traffic that was dropped on the queue
- yellow-dropped-packets—Configures QoS schema to export the number of yellow packets that were dropped on the queue
- export-summarized-stats—Exports the summarized QoS rate statistics over each S-VLAN or ATM VP (virtual path)
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

**Related Documentation**

- *Configuring SNMP in JunosE System Basics Configuration Guide*
- QoS Statistics Overview

## bulkstats traps

---

**Syntax**    bulkstats traps { nearly-full [ *threshold* ] | full }  
              no bulkstats traps { nearly-full | full }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the bulkstats traps. The **no** version disables the trap.

- Options**
- nearly-full—Specifies a percentage less than 100 percent
  - *threshold*—Percentage less than 100 percent; if not specified, defaults to 99 percent
  - full—100 percent

**Mode**    Global Configuration



## bulkstats virtual-router-group

---

**Syntax** [ no ] bulkstats virtual-router-group collector *collectorindex* *VRnames*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Configures the bulkstats for virtual router groups. The **no** version prevents bulkstats from being reported for virtual router groups.

- Options**
- **virtual-router-group**—Specifies the name or unique index number that contains from 1 to the maximum number of routers supported in the system
  - **collectorIndex**—Number that identifies the particular data collector, in the range 1–65535
  - **VRnames**—List of virtual router names

**Mode** Global Configuration

## bundled-group-id

---

**Syntax** [ no ] bundled-group-id *bundledGroupID*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns a bundled group identifier when no endpoint discriminator is available for bundled sessions using an L2TP destination host profile. When multiple tunnel-service modules are installed in a router that is deployed as an LNS and the tunnel sessions carry MLPPP, the router can use the bundled group identifier when selecting a tunnel-service module for bundled sessions. The **no** version restores the default value, no assigned bundled group identifier.



**NOTE:** We recommend that you assign a bundled group identifier for bundled sessions only when you are certain that endpoint discriminators are unavailable to identify bundle membership.

**Options** • *bundledGroupID*—Identifier for a bundled group in the range 0–4294967295

**Mode** L2TP Destination Profile Host Configuration

## **bundled-group-id-overrides-mlppp-ed**

---

**Syntax** [ no ] bundled-group-id-overrides-mlppp-ed

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the router uses the bundled group identifier you assigned using the **bundled-group-id** command when selecting a tunnel-service module instead of any endpoint discriminator. The **no** version removes the override.



.....  
**NOTE:** We strongly recommend that you use this command only with the support of JTAC.  
.....

**Mode** L2TP Destination Profile Host Configuration



## CHAPTER 4

# C Commands

## cablelength

---

**Syntax**    `cablelength length`  
              `no cablelength`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the length of the cable, which determines power requirements. The **no** version uses the default value, 0 feet.

**Options**    • *length* —Cable length in the range 0–450 feet

**Mode**    Controller Configuration

## cache entries

---

**Syntax**    cache entries *entryNumber*  
              no cache entries

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Sets the number of entries in the aggregation cache. The **no** version sets the number of entries to the default value.

**Options**    • *entryNumber*—Number of entries in the aggregation cache in the range 1024—524288; default value is 4096

**Mode**    Flow Cache Configuration

## cache timeout

---

**Syntax**    `cache timeout { active activeTimer | inactive inactiveTimer }`  
              `no cache timeout`

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Sets the active and inactive aging timers. The **no** version resets the default values.

**Options**

- *activeTimer*—Active aging timer in the range 1–60
- *inactiveTimer*—Inactive aging timer in the range 10–600

**Mode**    Flow Cache Configuration



---

**cbr**

---

**Syntax**    *cbr pcr*

*no cbr*

**Release Information**    Command introduced in JunosE Release 7.1.0.  
                              ATM VC Class Configuration mode added in JunosE Release 7.3.0.

**Description**    In ATM VC Configuration mode, configures the constant bit rate (CBR) service category on an ATM PVC. You must specify the peak cell rate (PCR) value. The **cbr** command is valid only for data PVCs; you cannot use this command for control (ILMI or signaling) PVCs. The **no** version restores the default service category, unspecified bit rate (UBR) without a PCR.

                      In ATM VC Class Configuration mode, configures the CBR service category as part of a VC class definition that you assign to an ATM data PVC. The **no** version restores the default service category, UBR without a PCR, in the VC class.

**Options**    • *pcr*—Peak cell rate, in Kbps, in the range 1–149760 (for OC3 ATM modules) or 1–599040 (for OC12 ATM modules)

**Mode**    ATM VC Configuration, ATM VC Class Configuration

## channelized

---

**Syntax** [ no ] channelized

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures a port on the CT3/T3-F0 line module and associated I/O module to support channelized T3 operation. The **no** version configures the port for unchannelized operation.

**Mode** Controller Configuration

## check-disk

---

**Syntax**    check-disk [ repair ] [ disk0 | disk1 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **disk0** and **disk1** keywords added in JunosE Release 7.2.0.  
                              Privileged Exec mode added in JunosE Release 8.0.0.

**Description**    Finds and repairs structural inconsistencies and damage in the DOS file system in unmounted flash cards on the primary SRP module. There is no **no** version.

- Options**
- **disk0**—Specifies flash card in slot 0 of the SRP module; default value is **disk0**; available only in Boot mode, because **disk0** cannot be in an unmounted state in a router outside of Boot mode
  - **disk1**—Specifies flash card in slot 1 of the SRP module; supported only on the E120 router and the E320 router

**Mode**    Boot, Privileged Exec

## check-vpn-next-hops

---

**Syntax** [ no ] check-vpn-next-hops

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables a BGP speaker to take the reachability of the next hop on received VPNv4 or VPNv6 routes into account when it determines the best route to a prefix. Checking the reachability is disabled by default. The **no** version explicitly disables reachability checking.

**Mode** Address Family Configuration

## classifier-group

**Syntax** classifier-group { \* | *classifierName* } [ precedence *precValue* ] [ parent-group *parentGroupName* ] [ external parent-group *externalParentGroupName* parameter *parameterName* ]

no classifier-group { \* | *classifierName* }

**Release Information** Command introduced before JunosE Release 7.1.0.  
**parent-group** keyword and *parentGroupName* variable added in JunosE Release 7.2.0.  
**external parent-group** keyword and *externalParentGroupName* variable added in JunosE Release 8.0.0.

**Description** Creates a classifier group for a policy list and assigns precedence to the specific CLACL in the group. This command accesses Classifier Group Configuration mode, in which you create policy rule configurations related to the specified CLACL. If a parent group was not created by the **parent-group** command, the **parent-group** keyword creates a parent group in a rate-limit hierarchy for IP, IPv6, L2TP, and MPLS. All packets matching the classifier are sent to the parent group for further processing, except for packets dropped by the classifier using the filter rule. More than one classifier group can have the same parent group, which enables you to create hierarchies. The **no** version removes the classifier group and its rules from the policy list.

- Options**
- **\***—Specifies that the router selects all packets from the interface associated with the policy list for this classifier group
  - *classifierName*—Name of a specific CLACL used to classify packets in this policy list
  - *precValue*—Precedence value for the CLACL, in the range 0–65535; a value of 100 is assigned if no value is specified
  - *parentGroupName*—Name of the parent group; if the parent group does not exist, naming the parent group creates an empty parent group



**NOTE:** Secure policy lists, which are used for packet mirroring operations, do not support named classifier groups. You must use **classifier-group \***. Also, secure policy lists do not support the **precedence** keyword.

- *externalParentGroupName*—External parent group name
- *parameterName*—Parameter name

**Mode** Policy List Configuration

- Related Documentation**
- Creating a Classifier Group for a Policy List
  - Configuring CLI-Based Mirroring

## class-int

---

**Syntax**    `class-int vcClassName`  
              `no class-int [ vcClassName ]`

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    When issued from Interface Configuration mode, assigns a previously configured VC class to an ATM major interface. When issued from Subinterface Configuration mode, assigns a previously configured VC class to a static ATM 1483 subinterface. Issuing this command applies the set of attributes in the specified VC class to the ATM data PVCs statically or dynamically created on the ATM major interface or ATM 1483 subinterface. The **no** version removes the VC class association with the interface or subinterface, and causes the router to set the PVC attributes to their systemwide default values, or to the values set in the associated VC class with the next highest order of precedence.

**Options**    • *vcClassName*—Name of the VC class configured with the `vc-class atm` command

**Mode**    Interface Configuration, Subinterface Configuration

## class-vc

---

**Syntax**    `class-vc vcClassName`  
              `no class-vc [ vcClassName ]`

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Assigns a previously configured VC class to an individual ATM data PVC. The **class-vc** command is valid only for data PVCs created with the `pvc` command; it has no effect for data PVCs created with the **atm pvc** command, or for control (ILMI or signaling) PVCs. Issuing this command applies the set of attributes in the specified VC class to the ATM data PVC. The **no** version removes the VC class association with the ATM PVC.

**Options**    • *vcClassName*—Name of the VC class configured with the `vc-class atm` command

**Mode**    ATM VC Configuration

## cleanup-timeout-factor

---

**Syntax** cleanup-timeout-factor *lostRefreshes*  
no cleanup-timeout-factor

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the number of refresh messages that can be lost before the PATH or RESV state is ended. The **no** version restores the default value, 3.

**Options** • *lostRefreshes*—Number of lost refresh messages

**Mode** RSVP Profile Configuration



## clear access-list

---

**Syntax** clear access-list [ *accessListName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears counters for entries in IP access lists. There is no **no** version.

**Options** • *accessListName*—Name of the access list; string of 1–32 alphanumeric characters

**Mode** Privileged Exec

## clear arp

---

**Syntax**    `clear [ ip ] arp [ vrf vrfName ] { ipAddress interfaceType interfaceSpecifier | * }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears entries from the ARP cache. There is no **no** version.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *ipAddress*—IP address in 32-bit dotted-decimal format of the entry to be cleared
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - \*—Clears all dynamic ARP entries

**Mode**    Privileged Exec

## clear bfd adapted-intervals

---

**Syntax** clear bfd adapted-intervals

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Resets adapted timer intervals for all BFD sessions on the router. There is no **no** version.

**Mode** Global Configuration

## clear bfd session

---

**Syntax** clear bfd session [ address *ipAddress* | discriminator *discriminatorID* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Restarts all BFD sessions or a specified BFD session. There is no **no** version.

- Options**
- *ipAddress*—IP address of the destination to which the session has been established
  - *discriminatorID*—Unique system-wide identifier for the BFD session; integer in the range 1–4294967295

**Mode** Privileged Exec, User Exec

## clear bgp ipv6

**Syntax** clear bgp ipv6 [ unicast | multicast | vpnv6 | route-target signaling ]  
 [ *ipAddress* | *ipv6Address* | peer-group *peerGroupName* | \* ] [ vrf *vrfName* ]  
 [ soft [ in | out ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
*ipv6Address* variable added in JunosE Release 8.0.0.  
**route-target signaling** keywords added in JunosE Release 8.2.0.

**Description** Resets the IPv6 BGP session. If the **soft** option is not used, brings down the underlying TCP connection and then brings it back up again, causing both peers to resend their complete BGP routing table. If the **soft out** option is used, the BGP speaker reapplies outbound policy and resends all routes to the specified peer(s). If the **soft in** option is used, the BGP speaker reapplies inbound policy to the routes received from the specified peers. This is possible only if soft reconfiguration inbound has been enabled for the peer or the peer supports the route-refresh capability. There is no **no** version.

- Options**
- unicast—Clears the unicast routing table; the default option
  - multicast—Clears the multicast routing table
  - vpnv6—Clears the VPNv6 unicast routing and forwarding table
  - route-target signaling—Clears the route-target membership information
  - *ipAddress*—IP address of identified BGP neighbor to clear
  - *ipv6Address*—IPv6 address of identified BGP neighbor to clear
  - *peerGroupName*—Name of a BGP peer group to clear
  - \*—Clears all connections
  - *vrfName*—Name of a virtual routing and forwarding instance to clear
  - soft—Specifies soft reconfiguration
    - in—Triggers inbound soft reconfiguration
    - out—Triggers outbound soft reconfiguration

**Mode** Privileged Exec

## clear bgp ipv6 dampening

**Syntax** To clear IPv6-specific information for only the route-target address family:

```
clear bgp ipv6 route-target signaling
{ dampening | flap-statistics } [ rtfPrefix | rtfAddress ]
```

To clear IPv6-specific information for any case other than for the route-target address family:

```
clear bgp ipv6 [ vrf vrfName ] [ unicast | multicast | vpnv6 ]
{ dampening | flap-statistics } [ ipv6Prefix ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**route-target signaling** keywords and *rtMemNlri* variable added in JunosE Release 8.2.0.  
*rtMemNlri* variable replaced by two variables, *rtfAddress* and *rtfPrefix*, in JunosE Release 9.1.0.

**Description** Clears IPv6-specific BGP route flap dampening information and reinstates the suppressed routes. If the *ipv6Prefix* option is not used, clears the entire IPv6 BGP routing table. The **dampening** keyword and the **flap-statistics** keyword both have the same effect. There is no **no** version.

- Options**
- route-target signaling—Clears the route-target membership information
  - *rtfPrefix*—Prefix representing the route-target membership NLRI (RT-MEM-NLRI), in the format *asNumber : extendedCommunity / prefixLength* (for example, 320:320:524/36) where:
    - *asNumber*—AS number for origin of route target information, in the range 1–4294967295
    - *extendedCommunity*—Two-part number in the format *number1:number2* that identifies an extended community of VPNs, in the format *number1 : number2*, where:
      - *number1*—Autonomous system (AS) number, in the range 1–4294967295, or an IP address
      - *number2*—Unique integer, in the range 1–4294967295; 32 bits if *number1* is a 16-bit AS number; 16 bits if *number1* is an IP address or a 32-bit AS number
    - *prefixLength*—Number that specifies the length of the route prefix, in the range 32–96
  - *rtfAddress*—*rtfPrefix* with a prefix length of 96; representing the route-target membership NLRI (RT-MEM-NLRI), in the format *asNumber:extendedCommunity* (for example, 320:320:524 or 320:50.2.3.4:524)
  - *vrfName*—Name of a virtual routing and forwarding instance to clear
  - unicast—Clears the unicast routing table; the default option
  - multicast—Clears the multicast routing table

- `vpn6`—Clears the VPNv6 unicast routing and forwarding table
- *ipv6Prefix*—IPv6 network for which to clear dampening information

**Mode** Privileged Exec

## clear bgp ipv6 dynamic-peers

---

**Syntax**    clear bgp ipv6 [ *ipAddress* | *ipv6Address* | peer-group *peerGroupName* | \* ]  
              [ vrf *vrfName* ] dynamic-peers

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              *ipv6Address* variable added in JunosE Release 8.0.0.

**Description**    Removes all IPv6-specific dynamic peers in the specified scope. There is no **no** version.

- Options**
- *ipAddress*—IP address of identified BGP neighbor to clear
  - *ipv6Address*—IPv6 address of identified BGP neighbor to clear
  - *peerGroupName*—Name of a BGP peer group to clear
  - \*—Clears all connections
  - *vrfName*—Name of a virtual routing and forwarding instance to clear

**Mode**    Privileged Exec



## clear bgp ipv6 redistribution

---

**Syntax** clear bgp ipv6 [ unicast | multicast ] redistribution

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all IPv6 routes that have been redistributed into BGP. There is no **no** version.

**Options**

- unicast—Clears the unicast routing table; the default option
- multicast—Clears the multicast routing table

**Mode** Privileged Exec

## clear bgp ipv6 wait-end-of-rib

---

**Syntax** clear bgp ipv6 [ unicast | multicast | vpnv6 | route-target signaling ] [ vrf *vrfName* ]  
[ *ipAddress* | *ipv6Address* | peer-group *peerGroupName* | \* ] wait-end-of-rib

**Release Information** Command introduced before JunosE Release 7.1.0.  
*ipv6Address* variable added in JunosE Release 8.0.0.  
**route-target signaling** keywords added in JunosE Release 8.2.0.

**Description** Resets the IPv6 BGP session and brings down the underlying TCP connection and then brings it back up again, causing both peers to resend their complete BGP routing table. Clears the specified peer from the set of peers for which BGP is waiting to receive an End-of-RIB marker after a peer restart. Hard clearing a peer has the same effect for that peer. There is no **no** version.

- Options**
- unicast—Clears the unicast routing table; the default option
  - multicast—Clears the multicast routing table
  - vpnv6 —Clears the VPNv6 unicast routing and forwarding table
  - route-target signaling—Clears the route-target membership information
  - *vrfName*—Name of a virtual routing and forwarding instance to clear
  - *ipAddress*—IP address of identified BGP neighbor to clear
  - *ipv6Address*—IPv6 address of identified BGP neighbor to clear
  - *peerGroupName*—Name of a BGP peer group to clear
  - \*—Clears all connections

**Mode** Privileged Exec

## clear bridge

---

<b>Syntax</b>	clear bridge { <i>bridgeGroupName</i>   <i>vplsName</i> }
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0. <i>vplsName</i> variable added in JunosE Release 7.1.0.
<b>Description</b>	Removes all dynamic (learned) MAC address entries from the forwarding table for the specified bridge group or VPLS instance . There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>bridgeGroupName</i>—Name of a bridge group specified with the <a href="#">bridge</a> command</li><li>• <i>vplsName</i>—Name of a VPLS instance created with the <a href="#">bridge vpls transport-virtual-router</a> command</li></ul>
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Clearing Dynamic MAC Addresses from the VPLS Forwarding Table</a></li></ul>

## clear bridge address

---

**Syntax**    `clear bridge { bridgeGroupName | vplsName } address macAddress`

**Release Information**    Command introduced in JunosE Release 7.1.0.  
*vplsName* variable added in JunosE Release 7.1.0.

**Description**    Removes a specific dynamic (learned) MAC address entry from the forwarding table for the specified bridge group or VPLS instance. There is no **no** version.

- Options**
- *bridgeGroupName*—Name of a bridge group specified with the [bridge](#) command
  - *vplsName*—Name of a VPLS instance created with the [bridge vpls transport-virtual-router](#) command
  - *macAddress*—Unique 48-bit (6-byte) number that is programmed into each LAN network interface card (NIC) at the time of manufacture; also known as a hardware address or physical address. The MAC address format is a dotted triple of four-digit hexadecimal numbers; for example, 0090.1a40.4c7c

**Mode**    Privileged Exec

**Related Documentation**

- [Clearing Dynamic MAC Addresses from the VPLS Forwarding Table](#)

## clear bridge interface

**Syntax** clear bridge interface *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Removes from the forwarding table all dynamic (learned) MAC address entries for a specified network interface that belongs to a bridge group or to a VPLS instance . There is no **no** version.



**NOTE:** Using the **clear bridge interface** command for a VPLS instance affects the specified network interface associated with the VPLS instance, but has no effect on the VPLS virtual core interface, which represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices. To remove all MAC addresses from the forwarding table for the VPLS virtual core interface, use the **clear bridge interface vpls** command.

- Options**
- *interfaceType*—One of the following interface types listed in “[Interface Types and Specifiers](#)” on page 5
    - atm
    - fastEthernet
    - gigabitEthernet
    - tenGigabitEthernet
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers](#) on page 5

**Mode** Privileged Exec

**Related Documentation**

- Clearing Dynamic MAC Addresses from the VPLS Forwarding Table

## clear bridge interface vpls

---

**Syntax**    clear bridge interface vpls *vplsName*

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Removes from the forwarding table for a VPLS instance all dynamic (learned) MAC address entries on the VPLS virtual core interface, which represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices. There is no **no** version.



.....

**NOTE:** Using the **clear bridge interface vpls** command affects the VPLS virtual core interface, but has no effect on the network interfaces associated with the VPLS instance. To remove all MAC addresses from the forwarding table for a VPLS network interface, use the **clear bridge interface** command.

.....

**Options**    • *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command

**Mode**    Privileged Exec

**Related Documentation**    • Clearing Dynamic MAC Addresses from the VPLS Forwarding Table

## clear egress-queue

---

**Syntax**    `clear egress-queue interfaceType interfaceSpecifier [ explicit ]`  
              `[ traffic-class trafficClassName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears egress queue statistics for the all queues bound to the specified interface for queues stacked at and above the interface, or only for the specified traffic class. There is no **no** version.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - **explicit**—Clears queues only on the specified interface and not queues stacked above the interface
  - *trafficClassName*—Name of a traffic class for which egress queue statistics are cleared

**Mode**    Privileged Exec

## clear fabric-queue

---

**Syntax**    clear fabric-queue [ traffic-class *trafficClassName* ] [ egress-slot *egressSlot* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears statistics for all fabric queues or for the specified traffic-class, egress-slot, or both. There is no **no** version.

- Options**
- *trafficClassName*—Name of a traffic class for which fabric-queue statistics will be cleared
  - *egressSlot*—Number of an egress slot for which fabric-queue statistics will be cleared

**Mode**    Privileged Exec



## clear ip bgp

**Syntax** clear ip bgp [ *ipAddress* | *ipv6Address* | peer-group *peerGroupName* | \* ] [ vrf *vrfName* ]  
[ ipv4 unicast | ipv4 multicast | vpnv4 unicast | l2vpn all | l2vpn vpls *vplsName* | l2vpn vpws *vpwsName* | route-target signaling ] soft [ in [ prefix-filter ] | out ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**l2vpn** keyword added in JunosE Release 7.1.0.  
*ipv6Address* variable added in JunosE Release 8.0.0.  
**route-target signaling** keywords added in JunosE Release 8.2.0.  
**all**, **vpls**, and **vpws** keywords and *vplsName* and *vpwsName* variables added in JunosE Release 9.3.0.

**Description** If the **soft** option is not used, brings down the underlying TCP connection and then brings it back up again, causing both peers to resend their complete BGP routing table. If the **soft out** option is used, the BGP speaker reapplies outbound policy and resends all routes to the specified peers. If the **soft in** option is used, the BGP speaker reapplies inbound policy to the routes received from the specified peers. This is possible only if soft reconfiguration inbound has been enabled for the peer or the peer supports the route-refresh capability. There is no **no** version.

- Options**
- *ipAddress*—IP address of identified BGP neighbor to clear
  - *ipv6Address*—IPv6 address of identified BGP neighbor to clear
  - *peerGroupName*—Name of a BGP peer group to clear
  - \*—Clears all connections
  - *vrfName*—Name of a virtual routing and forwarding instance to clear
  - ipv4 unicast—Clears the IPv4 unicast routing table; the default option
  - ipv4 multicast—Clears the IPv4 multicast routing table
  - vpnv4 unicast—Clears the VPNv4 unicast routing and forwarding table
  - l2vpn all—Clears the L2VPN reachability information for all VPLS and VPWS instances in the L2VPN address family
  - l2vpn vpls *vplsName*—Clears the L2VPN reachability information for the VPLS instance with the name *vplsName*
  - l2vpn vpws *vpwsName*—Clears the L2VPN reachability information for the VPWS instance with the name *vpwsName*
  - route-target signaling—Clears the route-target membership information
  - soft—Specifies soft reconfiguration
    - in—Triggers inbound soft reconfiguration
    - prefix-filter—Pushes out prefix list and Cisco-proprietary prefix list outbound route filters and triggers inbound soft reconfiguration

- out—Triggers outbound soft reconfiguration

**Mode** Privileged Exec

**Related Documentation** • Clearing BGP Attributes for VPLS

## clear ip bgp dampening

**Syntax** To clear IP-specific information for only the route-target address family:

```
clear ip bgp route-target signaling { dampening | flap-statistics } [ rtfPrefix
| rtfAddress ]
```

To clear IP-specific information for any case other than for the route-target address family:

```
clear ip bgp
[ vrf vrfName ] [ ipv4 unicast | ipv4 multicast | vpnv4 unicast |
l2vpn all | l2vpn vpls vplsName | l2vpn vpws vpwsName ]
{ dampening | flap-statistics } [ ipAddress [ addressMask ] ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**l2vpn** keyword added in JunosE Release 7.1.0.  
**vpls** keyword and *vplsName* variable added in JunosE Release 7.1.0.  
**all**, **vpws**, and **route-target signaling** keywords and *rtMemNlri* and *vpwsName* variables added in JunosE Release 8.2.0.  
*rtMemNlri* variable replaced by two variables, *rtfAddress* and *rtfPrefix*, in JunosE Release 9.1.0.

**Description** Clears IP route flap dampening information and reinstates the suppressed routes. The **dampening** keyword and the **flap-statistics** keyword both have the same effect. There is no **no** version.

- Options**
- **route-target signaling**—Clears the route-target membership information
  - ***rtfPrefix***—Prefix representing the route-target membership NLRI (RT-MEM-NLRI), in the format *asNumber* : *extendedCommunity* / *prefixLength* (for example, 320:320:524/36) where:
    - *asNumber*—AS number for origin of route target information, in the range 1–4294967295
    - *extendedCommunity*—Two-part number in the format *number1*:*number2* that identifies an extended community of VPNs, in the format *number1* : *number2*, where:
      - *number1*—Autonomous system (AS) number, in the range 1–4294967295, or an IP address
      - *number2*—Unique integer, in the range 1–4294967295; 32 bits if *number1* is a 16-bit AS number; 16 bits if *number1* is an IP address or a 32-bit AS number
    - *prefixLength*—Number that specifies the length of the route prefix, in the range 32–96
  - ***rtfAddress***—*rtfPrefix* with a prefix length of 96; representing the route-target membership NLRI (RT-MEM-NLRI), in the format *asNumber*:*extendedCommunity* (for example, 320:320:524 or 320:50.2.3.4:524)
  - ***vrfName***—Name of a virtual routing and forwarding instance to clear

- `ipv4 unicast`—Clears the IPv4 unicast routing table; the default option
- `ipv4 multicast`—Clears the IPv4 multicast routing table
- `vpn4 unicast`—Clears the VPNv4 unicast routing and forwarding table
- `l2vpn all`—Clears the L2VPN reachability information for all VPLS and VPWS instances in the L2VPN address family
- `l2vpn vpls vplsName`—Clears the L2VPN reachability information for the VPLS instance with the name *vplsName*
- `l2vpn vpws vpwsName`—Clears the L2VPN reachability information for the VPWS instance with the name *vpwsName*
- `ipAddress`—IP address of the BGP neighbor to clear
- `addressMask`—Address mask to be applied to the network IP address

**Mode** Privileged Exec

**Related Documentation**

- Clearing BGP Attributes for VPLS

## clear ip bgp dynamic-peers

---

**Syntax** clear ip bgp [ *ipAddress* | *ipv6Address* | peer-group *peerGroupName* | \* ] [ vrf *vrfName* ]  
dynamic-peers

**Release Information** Command introduced before JunosE Release 7.1.0.  
*ipv6Address* variable added in JunosE Release 8.0.0.

**Description** Removes all dynamic peers in the specified scope. There is no **no** version.

- Options**
- *ipAddress*—IP address of identified BGP neighbor to clear
  - *ipv6Address*—IPv6 address of identified BGP neighbor to clear
  - *peerGroupName*—Name of a BGP peer group to clear
  - \*—Clears all connections
  - *vrfName*—Name of a virtual routing and forwarding instance to clear

**Mode** Privileged Exec

## clear ip bgp redistribution

---

**Syntax** clear ip bgp [ ipv4 { unicast | multicast } ] redistribution

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Reapplies policy to routes that have been redistributed into BGP. There is no **no** version.

- Options**
- ipv4 unicast—Reapplies policy to redistributed IPv4 unicast routes
  - ipv4 multicast—Reapplies policy to redistributed IPv4 multicast routes

**Mode** Privileged Exec, User Exec

## clear ip bgp wait-end-of-rib

<b>Syntax</b>	clear ip bgp [ <i>ipAddress</i>   <i>ipv6Address</i>   peer-group <i>peerGroupName</i>   * ] [ vrf <i>vrfName</i> ] [ ipv4 unicast   ipv4 multicast   vpnv4 unicast   l2vpn all   l2vpn vpls <i>vplsName</i>   l2vpn vpws <i>vpwsName</i>   route-target signaling ] wait-end-of-rib
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0. <b>l2vpn</b> keyword added in JunosE Release 7.1.0. <i>ipv6Address</i> variable added in JunosE Release 8.0.0. <b>route-target signaling</b> keywords added in JunosE Release 8.2.0. <b>all</b> , <b>vpls</b> , and <b>vpws</b> keywords and <i>vplsName</i> and <i>vpwsName</i> variables added in JunosE Release 9.3.0.
<b>Description</b>	Brings down the underlying TCP connection and then brings it back up again, causing both peers to resend their complete BGP routing table, but clears the specified peer from the set of peers for which BGP is waiting to receive an End-of-RIB marker after a peer restart. Hard clearing a peer has the same effect for that peer. There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"> <li>• <i>ipAddress</i>—IP address of identified BGP neighbor to clear</li> <li>• <i>ipv6Address</i>—IPv6 address of identified BGP neighbor to clear</li> <li>• <i>peerGroupName</i>—Name of a BGP peer group to clear</li> <li>• *—Clears all connections</li> <li>• <i>vrfName</i>—Name of a virtual routing and forwarding instance to clear</li> <li>• ipv4 unicast—Clears the IPv4 unicast routing table; the default option</li> <li>• ipv4 multicast—Clears the IPv4 multicast routing table</li> <li>• vpnv4 unicast—Clears the VPNv4 unicast routing and forwarding table</li> <li>• l2vpn all—Clears the L2VPN reachability information for all VPLS and VPWS instances in the L2VPN address family</li> <li>• l2vpn vpls <i>vplsName</i>—Clears the L2VPN reachability information for the VPLS instance with the name <i>vplsName</i></li> <li>• l2vpn vpws <i>vpwsName</i>—Clears the L2VPN reachability information for the VPWS instance with the name <i>vpwsName</i></li> <li>• route-target signaling—Clears the route-target membership information</li> </ul>
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Clearing BGP Attributes for VPLS</li> </ul>

## clear ip demux

---

**Syntax** clear ip demux

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all dynamically created demultiplexer table entries associated with route-map processing of the **set ip source-prefix** command. There is no **no** version.

**Mode** Interface Configuration



---

## clear ip dhcp-local binding

---

**Syntax** clear ip dhcp-local binding *ipAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the specified IP DHCP address binding. There is no **no** version.



**NOTE:** This command is deprecated and might be removed completely in a future release. The function provided by this command has been replaced by the **dhcp delete-binding** command.

**Options** • *ipAddress*—DHCP IP address binding to clear

**Mode** Privileged Exec

## clear ip dvmrp routes

---

**Syntax** clear ip dvmrp routes [ *ipAddress* [ *addressMask* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears DVMRP routes from the routing table. There is no **no** version.

- Options**
- *ipAddress*—IP address for which longest match is cleared
  - *addressMask*—Address mask to be applied to the IP address

**Mode** Privileged Exec

## clear ip flow stats

---

**Syntax** clear ip flow stats

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all entries from all flow caches on the router. There is no **no** version.



.....  
**CAUTION:** Using this command may temporarily disrupt flow data collection.  
.....

**Mode** Privileged Exec

## clear ip interface

---

**Syntax**    clear ip interface [ *vrf vrfName* ] *interfaceType interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears the counters on the specified IP interface. The default is all interface types and all interfaces. There is no **no** version.

**Options**

- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
- *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec

## clear ip isis redistribution

---

**Syntax** clear ip isis redistribution

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all the routes that have previously been redistributed into IS-IS and redistributes them using the current policy configuration. There is no **no** version.

**Mode** Privileged Exec

## clear ip mobile binding

---

**Syntax** clear ip mobile binding { nai { *user@realm* | *@realm* | *@* } | *ipAddress* | all }

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Clears the binding table in a virtual router or a specified binding determined by the mobile node home address or network access identifier (NAI). There is no **no** version.

- Options**
- *user@realm*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *user@realm*, where *realm* is the domain name
  - *@realm*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *@realm*, where *realm* is the domain name
  - *@*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *@*
  - *ipAddress*—IP address of the home agent
  - **all**—Clears all the bindings in the binding table

**Mode** Privileged Exec

## clear ip mroute

---

**Syntax** clear ip mroute { \* | *grpAddress* [ *sourceAddress* ] }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all or the specified multicast forwarding entries. There is no **no** version.

- Options**
- \*—Clears all IP multicast forwarding entries
  - *grpAddress*—Address of the multicast group for which forwarding entries should be cleared
  - *sourceAddress*—Address of the multicast source for which forwarding entries should be cleared

**Mode** Privileged Exec, User Exec

## clear ip nat translation

---

**Syntax** clear ip nat translation \*

clear ip nat translation inside *insideGlobalIpAddress* *insideLocalIpAddress*

clear ip nat translation outside *outsideLocalIpAddress* *outsideGlobalIpAddress*

clear ip nat translation { icmp | tcp | udp }

inside *insideGlobalIpAddress* *insideGlobalPort* *insideLocalIpAddress* *insideLocalPort*

clear ip nat translation { gre | icmp | tcp | udp }

inside *insideGlobalIpAddress* \* *insideLocalIpAddress* \*

clear ip nat translation { icmp | tcp | udp }

inside *insideGlobalIpAddress* *insideGlobalPort* *insideLocalIpAddress* *insideLocalPort*

outside *outsideLocalIpAddress* *outsideLocalPort* *outsideGlobalIpAddress* *outsideGlobalPort*

**Release Information** Command introduced before JunosE Release 7.1.0.  
**gre** keyword added in JunosE Release 7.3.0.

**Description** Clears all or the specified NAT table entries. There is no **no** version.

- Options**
- \*—Clears all translations when used in the **clear ip nat translation** version of this command
  - \*—Matches any global or local port to remove inside source extended GRE, ICMP, TCP, or UDP translations for the specified global IP address and local IP address when used in the **clear ip nat translation { gre | icmp | tcp | udp } inside** *insideGlobalIpAddress* \* *insideLocalIpAddress* \* version of this command
  - inside—Specifies an inside address
  - *insideGlobalIpAddress*—Inside global IP address
  - *insideLocalIpAddress*—Inside local IP address
  - outside—Specifies an outside address
  - *outsideLocalIpAddress*—Outside local IP address
  - *outsideGlobalIpAddress*—Outside global IP address
  - tcp—Specifies a TCP port translation
  - udp—Specifies a UDP port translation
  - icmp—Specifies an ICMP port translation
  - gre—Specifies a GRE translation
  - *insideGlobalPort*—Inside global port number
  - *insideLocalPort*—Inside local port number



- *outsideGlobalPort*—Outside global port number
- *outsideLocalPort*—Outside local port number

**Mode** Privileged Exec

## clear ip ospf database

---

**Syntax** clear ip ospf database

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Deletes all entries from the OSPF link-state database and resets all adjacencies. There is no **no** version.

**Mode** Privileged Exec

---

## clear ip ospf neighbor

---

**Syntax** clear ip ospf neighbor [ *neighborAddress* ]

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Clears or resets adjacency with a specified neighbor session. There is no **no** version.



**NOTE:** When OSPF is configured and running over an NBMA network, do not issue the **clear ip ospf neighbor** command simultaneously on both ends of the OSPF link. Doing so brings the OSPF link down completely. In this event, you must do one of the following on both sides of the link to bring the link back up:

- Reconfigure the OSPF neighbors on the NBMA interface with the **neighbor** command.
- Issue the **clear ip ospf database** command to clear and reset the OSPF adjacencies.
- Issue the **shutdown** command followed by the **no shutdown** command on the interface.

**Options** • *neighborAddress*—IP address of identified neighbor to clear or reset

**Mode** Privileged Exec

## clear ip ospf redistribution

---

**Syntax** clear ip ospf redistribution

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears and readvertises all of the routes that have been previously redistributed into OSPF. Exercise caution when using this command as it purges all external LSAs and reoriginates. There is no **no** version.

**Mode** Privileged Exec

## clear ip pim auto-rp

---

**Syntax** clear ip pim auto-rp [ *ipAddress* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the group-to-RP router mappings the router learned via autoRP. There is no **no** version.

**Options** • *ipAddress*—IP address of the router designated as an RP router

**Mode** Privileged Exec, User Exec

## clear ip pim interface count

---

**Syntax** clear ip pim interface [ *interfaceType interfaceSpecifier* ] count

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the counters for multicast packet statistics on all interfaces or the specified interface. There is no **no** version.

**Options**

- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Privileged Exec, User Exec

---

## clear ip pim remote-neighbor count

---

**Syntax** clear ip pim remote-neighbor [ *ipAddress* ] count

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the counters for remote neighbor statistics on all interfaces or the specified interface. There is no **no** version.



.....

**NOTE:** This command is typically used when you configure PIM remote neighbors to run multicast services over BGP/MPLS VPNs. That functionality is no longer supported.

.....

**Options** • *ipAddress*—IP address of the interface

**Mode** Privileged Exec, User Exec

## clear ip prefix-list

---

**Syntax** clear ip prefix-list [ *listName* [ *network/length* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all hit counts in the prefix lists, the specified prefix list, or the specified entry from the specified prefix list. There is no **no** version.

- Options**
- *listName*—Name of the prefix list; string of up to 32 characters
  - *network*—Base address of the network route to be filtered; for example, 192.168.32.0 or 10.10.0.0
  - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched

**Mode** Privileged Exec, User Exec



## clear ip prefix-tree

---

**Syntax** clear ip prefix-tree [ *treeName* [ *network/length* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all prefix trees, the specified prefix tree, or the specified entry from the specified prefix tree. There is no **no** version.

- Options**
- *treeName*—Name of the prefix list; string of up to 32 characters
  - *network*—Base address of the network route to be filtered; for example, 192.168.32.0 or 10.10.0.0
  - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched

**Mode** Privileged Exec, User Exec

## clear ip rip dynamic-interfaces

---

**Syntax** clear ip rip dynamic-interfaces

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all existing dynamic, unnumbered interfaces that were created since issuing the **ip rip copy-to-dynamic** command. There is no **no** version.

**Mode** Privileged Exec, User Exec

## clear ip rip redistribution

---

**Syntax** clear ip rip redistribution

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all the routes that have previously been redistributed into RIP. There is no **no** version.

**Mode** Privileged Exec, User Exec

## clear ip routes

---

**Syntax**    `clear ip routes [ vrf vrfName ] { * | ipAddress ipMask }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears a specified route or all dynamic routes from the routing table of a specified VRF or all VRFs. There is no **no** version.

- Options**
- *vrfName*—Name of the VRF context from which routes are to be cleared
  - \*—Clears all dynamic routes
  - *ipAddress*—IP address prefix for routes that are cleared; in 32-bit dotted-decimal format
  - *ipMask*—Mask of the IP address prefix for routes that are cleared; in 32-bit dotted-decimal format

**Mode**    Privileged Exec

## clear ip routes download

**Syntax** For a specific VRF:

```
clear ip routes download [ vrf vrfName ] { ipAddress ipMask | * }
```

For all virtual routers:

```
clear ip routes download { all | reload }
```

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Synchronizes downloaded access routes and the routes installed in the routing table. This command has no effect if a download operation is in progress. There is no **no** version.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters; the current virtual router is used by default
  - *ipAddress*—IP address prefix to clear
  - *ipMask*—Network mask of the IP address prefix to clear
  - \*—Clears all dynamic routes that are installed in the routing table of the current virtual router or specified VRF
  - all—Clears all downloaded routes that are installed in the routing tables of all virtual routers and VRFs
  - reload—Performs a route download operation, then clears all downloaded routes from the routing tables in all virtual routers and VRFs

**Mode** Privileged Exec

## clear ip tunnel-routes

---

**Syntax**    clear ip tunnel-routes [ vrf *vrfName* ] { \* | *ipAddress ipMask* }

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Clears and then refreshes a specified route or all dynamic routes from the tunnel routing table of the virtual router or a specified VRF. There is no **no** version.

**Options**

- *vrfName*—Name of the VRF context from which routes are to be cleared
- \*—Clears all dynamic routes
- *ipAddress*—IP address prefix for routes that are cleared; in 32-bit dotted-decimal format
- *ipMask*—Mask of the IP address prefix for routes that are cleared; in 32-bit dotted-decimal or /N format

**Mode**    Privileged Exec

## clear ipv6 access-list

---

**Syntax** clear ipv6 access-list [ *accessListName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears counters for entries in IP access lists. There is no **no** version.

**Options** • *accessListName*—Name of the access list; a string of up to 32 characters

**Mode** Privileged Exec

## clear ipv6 bfd session

---

**Syntax**    clear ipv6 bfd session [ address *ipv6Address* ]

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Restarts all IPv6 BFD sessions or a specified BFD session. There is no **no** version.

**Options**    • *ipAddress*—IP address of the destination to which the session has been established

**Mode**    Privileged Exec, User Exec



## clear ipv6 interface

---

**Syntax** clear ipv6 interface *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the counters on the specified IPv6 interface. The default is all interface types and all interfaces. There is no **no** version.

**Options**

- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Privileged Exec

## clear ipv6 mroute

---

**Syntax**    clear ipv6 mroute { \* | *grpAddress* [ *sourceAddress* ] }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears all or the specified IPv6 multicast forwarding entries. There is no **no** version.

- Options**
- \*—Clears all IPv6 multicast forwarding entries
  - *grpAddress*—Address of the multicast group for which forwarding entries should be cleared
  - *sourceAddress*—Address of the multicast source for which forwarding entries should be cleared

**Mode**    Privileged Exec, User Exec

## clear ipv6 neighbors

---

**Syntax** clear ipv6 neighbors [ include-statics | statics-only ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all IPv6 dynamic neighbors. The **include-statics** keyword clears both dynamic neighbors and static neighbors. The **statics-only** keyword clears only IPv6 static neighbors. There is no **no** version.

**Options**

- include-statics—Clears both dynamic and static neighbors
- statics-only—Clears only static neighbors

**Mode** Privileged Exec

## clear ipv6 ospf counters

---

**Syntax**    clear ipv6 ospf [ *processId* ] counters

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears all OSPF IPv6 statistical counters for the virtual router. There is no **no** version.

**Options**    • *processId*—Number in the range 1–65535 that identifies the OSPF process

**Mode**    Privileged Exec

## clear ipv6 ospf process

---

**Syntax**    `clear ipv6 ospf [ processId ] process`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears the OSPF IPv6 process on the virtual router. There is no **no** version.

**Options**    • *processId*—Number in the range 1–65535 that identifies the OSPF process

**Mode**    Privileged Exec

## clear ipv6 ospf redistribution

---

**Syntax** clear ipv6 ospf redistribution

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears and readvertise all of the routes that have been previously redistributed into OSPF. Exercise caution when using this command as it purges all external LSAs and reoriginates. There is no **no** version.

**Mode** Privileged Exec

## clear ipv6 pim interface

---

**Syntax** clear ipv6 pim interface [ *interfaceType interfaceSpecifier* ] count

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the counters for multicast packet statistics on all IPv6 interfaces or the specified IPv6 interface. There is no **no** version.

**Options**

- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Privileged Exec, User Exec

## clear ipv6 pim remote-neighbor

---

**Syntax**    clear ipv6 pim remote-neighbor [ *ipv6Address* ] count

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears the counters for remote neighbor statistics on all IPv6 interfaces or the specified IPv6 interface. There is no **no** version.

**Options**    • *ipv6Address*—IPv6 address of the interface

**Mode**    Privileged Exec, User Exec



## clear ipv6 prefix-list

---

**Syntax** clear ipv6 prefix-list [ *listName* [ *network/length* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all hit counts in all IPv6 prefix lists, the specified prefix list, or the specified entry from the specified prefix list. There is no **no** version.

**Options**

- *listName*—Name of the IPv6 prefix list; string of up to 32 characters
- *network*—Base address of the network route to be filtered; for example, ::ffff:a:b:c:d
- *length*—Length of the network prefix; number of bits masking base address to produce address to be matched

**Mode** Privileged Exec, User Exec

## clear ipv6 routes

---

**Syntax**    clear ipv6 routes [ *ipv6Prefix* | \* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears IPv6 routes. To clear the routes for a specific IPv6 network, specify the IPv6 prefix. To clear all dynamic IPv6 routes, use the \* (asterisk) option. There is no **no** version.

- Options**
- *ipv6Prefix*—IPv6 network for which to clear route information
  - \*—Clears all dynamic IPv6 routes

**Mode**    Privileged Exec

## clear ipv6 routes download

**Syntax** For a specific VR or VRF:

```
clear ipv6 routes download [ vrf vrfName ] {ipv6Prefix| * }
```

For all virtual routers:

```
clear ipv6 routes download { all | reload }
```

**Release Information** Command introduced in JunosE Release 13.0.0.

**Description** Synchronizes downloaded IPv6 access routes and the routes installed in the routing table. This command has no effect if a download operation is in progress. There is no **no** version.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters; the current virtual router is used by default
  - *ipv6Prefix*—IPv6 network whose route information needs to be cleared
  - \*—Clears all dynamic IPv6 routes that are installed in the routing table of the current virtual router or specified VRF
  - all—Clears all downloaded IPv6 routes that are installed in the routing tables of all virtual routers and VRFs
  - reload—Performs a route download operation, then clears all downloaded routes from the routing tables in all virtual routers and VRFs

**Mode** Privileged Exec

## clear ipv6 tunnel-routes

---

**Syntax**    clear ipv6 tunnel-routes [ *ipv6Prefix* | \* ]

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Clears and then refreshes IPv6 routes from the tunnel routing table. To clear the routes for a specific IPv6 network, specify the IPv6 prefix. To clear all dynamic IPv6 routes, use the \* (asterisk) option. There is no **no** version.

- Options**
- *ipv6Prefix*—IPv6 network for which to clear route information
  - \*—Clears all dynamic IPv6 routes

**Mode**    Privileged Exec

## clear isis adjacency

---

**Syntax** clear isis adjacency [ *systemId* | *hostname* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all entries from the adjacency database, or clears only adjacencies with a specified neighbor. There is no **no** version.

**Options**

- *systemId*—System ID of an IS-IS neighbor
- *hostname*—Hostname of an IS-IS neighbor

**Mode** Privileged Exec

## clear isis database

---

**Syntax**    clear isis database [ *systemId* | *hostname* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears all entries from the IS-IS link-state database, or clears only entries associated with a specified neighbor. There is no **no** version.

**Options**

- *systemId*—System ID of an IS-IS neighbor
- *hostname*—Hostname of an IS-IS neighbor

**Mode**    Privileged Exec

## clear isis ipv6 redistribution

---

**Syntax** clear isis ipv6 redistribution

**Release Information** Command introduced in JunosE Release 8.2.0.

**Description** Clears all the IPv6 routes that have previously been redistributed into IS-IS and redistributes them using the current policy configuration. There is no **no** version.

**Mode** Privileged Exec

## clear l2c discovery-table

---

**Syntax** clear l2c discovery-table { neighbor *neighborName* | end-user-id *userId* |  
neighbor *neighborName* end-user-id *userId* }

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Clears all entries or a specified entry from the topology discovery table. There is no **no** version.

**Options**

- *neighborName*—Name of the neighbor you want to reset
- *userId*—User ID you want to reset

**Mode** Privileged Exec



## clear l2c neighbor

---

**Syntax** clear l2c neighbor *neighborName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Resets the specified GSMP neighbor session. There is no **no** version.

**Options** • *neighborName*—Name of the neighbor you want to reset

**Mode** Privileged Exec

## clear line

---

**Syntax**    clear line { *absoluteLine* | *cliType* *relativeLine* }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Removes all services on any line on the system and closes any files opened as a result of services on that line. There is no **no** version.

**Options**

- *absoluteLine*—Absolute number of the line to which the user is connected; see the line number field in the **show users** command output
- *cliType*—One of the following types of lines:
  - console
  - vty
- *relativeLine*—Relative number for a line; see the line name field in the **show users** command output

**Mode**    User Exec

## clear mirror log

---

**Syntax** clear mirror log

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears all log entries for packet mirroring operations. By default, you must have CLI user access level 13 or above to use this command; an administrator can modify the user access level requirement. There is no **no** version.

**Mode** Privileged Exec, User Exec

**Related Documentation**

- [Monitoring Packet Mirroring Overview](#)
- [Logging Packet Mirroring Information](#)

## clear mpls dynamic-interfaces on-major-interfaces

---

**Syntax** clear mpls dynamic-interfaces [ ip | ipv6 ] on-major-interfaces  
[ *interfaceType interfaceSpecifier* ]

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Removes and re-creates both dynamic IPv4 interfaces and dynamic IPv6 interfaces that are on top of all MPLS major interfaces or on top of the specified MPLS major interface. There is no **no** version.

- Options**
- ip—Specifies that only IPv4 dynamic interfaces are removed and re-created
  - ipv6—Specifies that only IPv6 dynamic interfaces are removed and re-created
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Privileged Exec

## clear mpls ldp

---

**Syntax** `clear mpls ldp [ prefix destAddr [ maskLen | mask ] | neighbor [ neighborAddress ] ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Removes and reestablishes existing LDP LSPs, thereby forcing the reapplication of policies on the reestablished topology-driven LDP LSPs. You can clear all LDP LSPs or limit the clearance to only LSPs to a specified prefix or neighbor. Affects the data traffic on LSPs that are in use when the command is issued. There is no **no** version.

- Options**
- *destAddr*—IP address of the prefix to be cleared
  - *maskLen*—Length of the prefix to be cleared; number in the range 0–32
  - *mask*—Mask for the prefix to be cleared
  - *neighborAddress*—IP address of a neighbor 32-bit dotted-decimal format of the entry to be cleared

**Mode** Privileged Exec

## clear redundancy history

---

**Syntax**    clear redundancy history

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Clears the high availability switchover history for the router. There is no **no** version.

**Mode**    Privileged Exec

## clear rsvp authentication

---

**Syntax** clear { ip | mpls } rsvp authentication [ *ipAddress* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Clears the security association and resets the sequence number on the receiving peer for the specified sending peer. There is no **no** version.

- Options**
- ip—Specifies keyword for compatibility with non-E Series implementations
  - mpls—Indicates JunosE MPLS implementation
  - *ipAddress*—IP address of sending peer

**Mode** Privileged Exec

## clear suspicious-control-flow-detection

---

**Syntax**    clear suspicious-control-flow-detection  
              [ interface *interfaceSpecifier* protocol *protocolValue* address *ethernetAddress* slot  
              *slotNumber* ]

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Clears one or more suspicious flows. If you do not specify a slot, interface, or IP address, clears all suspicious flows. If you specify a slot, clears all specified suspicious flows on that slot. If you specify an interface and protocol, clears flows that are identified down to the Ethernet mac address level. There is no **no** version.

- Options**
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *protocolValue*—Name of the protocol to be cleared
  - *ethernetAddress*—Ethernet address to be cleared
  - *slotNumber*—Number of the slot to be cleared

**Mode**    Privileged Exec, User Exec



---

## client-name

---

**Syntax**    client-name *clientname*  
              no client-name

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    From Domain Map Tunnel Configuration or Tunnel Group Tunnel Configuration mode, sets a hostname for a tunnel that the LAC uses when communicating with the LNS about the tunnel. The **no** version removes the hostname from the tunnel.



.....  
**NOTE:** In Domain Map Tunnel Configuration mode, this command is replacing the **hostname** command. The **hostname** command may be removed completely from Domain Map Tunnel Configuration mode in a future release.  
.....

**Options**    • *clientname*—String of up to 64 characters (no spaces)

**Mode**    Domain Map Tunnel Configuration, Tunnel Group Tunnel Configuration

## clns configuration-time

---

**Syntax**    clns configuration-time *configTime*  
              no clns configuration-time

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the rate at which ES hellos and IS hellos are sent. The **no** version restores the default value, 10 seconds.

**Options**    • *configTime*—Number in the range 1–65535; rate in seconds at which ES and IS hello packets are sent; default value is 10 seconds

**Mode**    Global Configuration

## clns holding-time

---

**Syntax**    `clns holding-time holdTime`  
              `no clns holding-time`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Allows the sender of an ES hello or IS hello to specify the length of time you consider the information in the hello packets to be valid. The **no** version restores the default value, 30 seconds.

**Options**    • *holdTime*—Number in the range 1–65535; length of time in seconds during which the information in the hello packets is considered valid

**Mode**    Global Configuration

## clns host

---

**Syntax**    `clns host name nsap`  
              `no clns host name`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines a name-to-NSAP mapping that can then be used with commands requiring NSAPs. Enables dynamic resolution of hostnames to system IDs (within the NSAP address). The hostname mapping is sent in the LSPs within the dynamic hostname TLV tuple. Display the TLV by issuing the **show isis database detail** command. Use the **show hosts** command to display the mapping. The **no** version restores the default of no mapping defined.

**Options**

- *name*—Name for the NSAP; first character can be either a letter or a number. If a number is used, the operations you can perform are limited.
- *nsap*—NSAP to which that name maps

**Mode**    Global Configuration

## clock set

---

**Syntax**    `clock set time { month day | day month } year`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Allows you to manually set the system clock. There is no **no** version.

- Options**
- *time*—Current time (in 24-hour format – *HH:MM:SS*)
  - *month*—Name of the month (January, February, ...)
  - *day*—Day of the month (1–31)
  - *year*—Year (2000, 2001, ...)

**Mode**    Privileged Exec

## clock source

---

**Syntax**    clock source { line | internal { module | chassis } }  
              no clock source

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Determines how an interfaces obtains clocking signals. The **no** version restores the default value, **line**.

- Options**
- line—Interface clocks data from a clock recovered from the line's receive data stream; the default.
  - internal—Internal clock source transmits data from its internal clock. You must specify one of the following for internal clocking:
    - module—Internal clock is from the line module itself
    - chassis—Internal clock is from the configured system clock

**Mode**    Controller Configuration, Interface Configuration (POS only)

## clock summer-time date

**Syntax** clock summer-time name date { *startDay startMonth* | *startMonth startDay* }  
*startYear startTime* { *stopDay stopMonth* | *stopMonth stopDay* }  
*stopYear stopTime* [ *dstOffset* ]

no clock summer-time

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the router to automatically switch to summer time (Daylight Saving Time—DST). It should start on the first specific date listed in the command and end on the second specific date in the command. The **no** version configures the software so that it does not automatically switch to summer time.

**Options**

- *name*—Name of the time zone (for example, PDT) to be displayed when daylight saving (summer) time is in effect
- *date*—Indicates that summer time should start on the first specific date listed in the command and end on the second specific date in the command
- *startDay*—DST start day (1–31)
- *startMonth*—DST start month (January, February, ...)
- *startYear*—DST start year (2000, 2001, ...)
- *startTime*—DST start time (24-hour format) in hours and minutes (hh:mm)
- *stopDay*—DST stop day
- *stopMonth*—DST stop month
- *stopYear*—DST stop year
- *stopTime*—DST stop time (24-hour format)
- *dstOffset*—Number of minutes to add during summer time in the range 1–1440; default = 60

**Mode** Global Configuration

## clock summer-time recurring

---

**Syntax** clock summer-time name recurring [ { *startWeekNumber* | *startWeekEnum* }  
*startDay* *startMonth* *startTime* { *stopWeekNumber* | *stopWeekEnum* }  
*stopDay* *stopMonth* *stopTime* [ *dstOffset* ] ]

no clock summer-time

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the router to automatically switch to summer time (Daylight Saving Time) on the specified dates every year. The **no** version configures the software not to automatically switch to summer time.

- Options**
- *name*—Name of the time zone (for example, EDT for Eastern Daylight Savings Time) to be displayed when daylight saving (summer) time is in effect
  - *recurring*—Indicates that summer time should start and end on the specified days every year
  - *startWeekNumber*—DST start week of the month (1–5)
  - *startWeekEnum*—First week in month (first); or last week in month (last)
  - *startDay*—DST start day of the week (Sunday, Monday, ...)
  - *startMonth*—DST start month (January, February, ...)
  - *startTime*—DST start time (24-hour format) in hours and minutes (hh:mm)
  - *stopWeekNumber*—DST stop week of the month (1–5)
  - *stopWeekEnum*—First week in month (first); or last week in month (last)
  - *stopDay*—DST stop day of the week
  - *stopMonth*—DST stop month
  - *stopTime*—DST stop time in hours and minutes (hh:mm)
  - *dstOffset*—Number of minutes to add during summer time in the range 1–1440; default = 60

**Mode** Global Configuration



## clock timezone

---

**Syntax**    clock timezone *name hours* [ *minutes* ]

              no clock timezone

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time zone for display. The **no** version sets the time zone to UTC.

- Options**
- *name*—Name of the time zone to be displayed when Standard time is in effect, such as EST or PST.
  - *hours*—Hours offset from UTC (-23, -22 ... 23)
  - *minutes*—Minutes offset from UTC (0–59)

**Mode**    Global Configuration

## color

---

**Syntax** [ no ] [ suspend ] color { green | yellow | red }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a policy rule that assigns a color to packets defined in the current classifier control list. The **no** version removes the rule from the policy list; the **suspend** version temporarily suspends the policy rule; the **no suspend** version resumes application of a suspended rule.



.....  
**NOTE:** This command replaces the Policy List Configuration mode version of the **color** command, which may be removed completely in a future release.  
.....

- Options**
- green—Assigns green color to packets; highest precedence
  - yellow—Assigns yellow color to packets; intermediate precedence
  - red—Assigns red color to packets; lowest precedence

**Mode** Classifier Group Configuration

- Related Documentation**
- Hierarchical Rate Limits Overview
  - Policy Rule Precedence

## color-aware

---

**Syntax** [ no ] color-aware

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Configures rate-limit profile to operate in color-aware mode. (Supported only on hierarchical rate limits.) Color-aware rate limits can change the algorithm used depending on the color of the incoming packet, which might have been set in the previous rate limit, in a policy action, or in an earlier policy. The **no** version restores the default value, which is not color-aware.

**Mode** Rate Limit Profile Configuration

**Related Documentation**

- [Creating a Two-Rate Rate-Limit Profile](#)

## color-mark-profile

---

**Syntax** [ no ] [ ip | ipv6 | mpls ] color-mark-profile *profileName*

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Translates the packet color (independent of its type) to a type-dependent mark (for ToS or EXP), which is applied to a packet after it has exited a rate-limit hierarchy. If translation is not configured for a color, then packets of that color are not changed. The **no** version deletes the color-mark profile.

**Options**

- *profileName*—Name of the rate-limit profile to be used in a policy (up to 40 alphanumeric characters)

**Mode** Color Mark Profile Configuration, Global Configuration

**Related Documentation**

- Hierarchical Rate Limits Overview
- Policy Rule Precedence

## committed-action

**Syntax** For IP and IPv6 rate-limit profiles:

```
[ no ] committed-action { drop | transmit | mark markVal }
```

For L2TP rate-limit profiles:

```
[ no ] committed-action { drop | transmit }
```

For MPLS rate-limit profiles:

```
[ no ] committed-action { drop | transmit | mark-exp expValue }
```

For hierarchical rate-limit profiles:

```
[ no ] committed-action { drop | transmit [ conditional | unconditional | final ] }
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**conditional**, **unconditional**, and **final** keywords added in JunosE Release 7.2.0.

**Description** Sets the action for packets conforming to the committed rate and committed burst size and conforming to the exceed rate and exceed burst size for a rate-limit profile. The **no** version restores the value to the default value, drop.

- Options**
- **drop**—Drops the packet
  - **transmit**—Transmits the packet; for hierarchical rate limits:
    - **conditional**—Packets must pass the next rate limit
    - **unconditional**—Packets take resources, but are not affected by the rest of the hierarchy
    - **final**—Packets exit the hierarchy at rate limit
  - *markVal*—Value in the range 0–255
  - *expValue*—EXP bit value in the range 0–7

**Mode** Rate Limit Profile Configuration

**Related Documentation**

- Creating a Two-Rate Rate-Limit Profile

## committed-burst

---

**Syntax** committed-burst { *size* | millisecond *milliseconds* }  
no committed-burst

**Release Information** Command introduced before JunosE Release 7.1.0.  
*milliseconds* variable added in JunosE Release 8.1.0.

**Description** Sets the committed burst for a rate limit profile. The **no** version restores the default value, 100 ms; if 100ms is less than 8K, then 8K (8192).

- Options**
- *size*—Size in bytes in the range 1–4294967295
  - *milliseconds*—Milliseconds in the range 1–10000

**Mode** Rate Limit Profile Configuration

**Related Documentation**

- Creating a Two-Rate Rate-Limit Profile

## committed-drop-threshold

---

<b>Syntax</b>	committed-drop-threshold <i>committedDropThreshold</i> no committed-drop-threshold
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Configures the threshold above which committed-drop-events are logged. The <b>no</b> version removes the threshold.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>committedDropThreshold</i>—Bits per second in the range 0–1073741824</li></ul>
<b>Mode</b>	Statistics Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring Event Statistics</li></ul>

## committed-length

---

**Syntax** committed-length *minimumCommittedLength* [ *maximumCommittedLength* ]  
no committed-length

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets minimum and maximum constraints for the queue's committed lengths. The **no** version removes constraints on the queue's committed length.

- Options**
- *minimumCommittedLength*—Range 0–1073741824
  - *maximumCommittedLength*—Range 0–1073741824

**Mode** Queue Profile Configuration

**Related Documentation**

- [Configuring Queue Profiles to Manage Buffers and Thresholds](#)



## committed-rate

---

<b>Syntax</b>	<code>committed-rate { <i>rate</i>   <i>parameterName</i> percentage <i>percentValue</i> }</code> <code>no committed-rate</code>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0. <i>parameterName</i> and <i>percentValue</i> variables added in JunosE Release 8.1.0.
<b>Description</b>	Sets the committed rate for a rate-limit profile as a specified value or as a percentage of a reference rate defined in the specified policy parameter. The <b>no</b> version restores the default value, 0.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>rate</i>—Rate in bits per second in the range 0–4294967295</li><li>• <i>parameterName</i>—Name of policy parameter up to 40 characters</li><li>• <i>percentValue</i>—Percentage in the range 0–100</li></ul>
<b>Mode</b>	Rate Limit Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Creating a Two-Rate Rate-Limit Profile</li><li>• Setting the Committed Rate for a Rate-Limit Profile</li></ul>

## committed-threshold

---

<b>Syntax</b>	<code>committed-threshold { percent <i>MinThresholdPercent</i> <i>MaxThresholdPercent</i>   <i>MinThresholdBytes</i> <i>MaxThresholdBytes</i> } <i>MaxDropProbability</i></code>  <code>no committed-threshold</code>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Specifies the committed queue thresholds and maximum drop probability. The <b>no</b> version removes committed threshold.
<b>Options</b>	<ul style="list-style-type: none"><li>• <b>percent</b>—Specifies committed queue thresholds as percentages</li><li>• <i>MinThresholdPercent</i>—Minimum queue threshold as a percentage of queue length</li><li>• <i>MaxThresholdPercent</i>—Maximum queue threshold as a percentage of queue length</li><li>• <i>MinThresholdBytes</i>—Minimum queue threshold in bytes</li><li>• <i>MaxThresholdBytes</i>—Maximum queue threshold in bytes</li><li>• <i>MaxDropProbability</i>—Maximum drop probability</li></ul>
<b>Mode</b>	Drop Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring RED</li><li>• Configuring WRED</li></ul>

## common-name

---

**Syntax** [ no ] common-name *commonName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a common name used to generate certificate requests. The **no** version removes the common name.

**Options** • *commonName*—Name of up to 60 characters

**Mode** IPSec Identity Configuration

## configure

---

**Syntax**    configure [ terminal | file [ *fileName* ] [ verbose | show-progress [ *dotPeriod* ] ] ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enters Global Configuration mode. There is no **no** version.



**NOTE:** This command is not allowed for a short time after a warm restart (warm switchover) occurs. This behavior allows some applications time to complete their warm-restart initialization. However, if the warm-restart does not complete in 5 minutes, the warm-start is cancelled and configuration access is restored.

- Options**
- terminal—Enables manual configuration from a terminal
  - file—Configures the router from a script file
  - *fileName*—Script file to execute
  - verbose—Echoes each command as the script is executed
  - show-progress—Displays a '.' during script execution
  - *dotPeriod*—Number of commands executed before a '.' is displayed; default value is 100

**Mode**    Privileged Exec

## confirmations explicit

---

**Syntax** [ no ] confirmations explicit

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Requires the user to enter **y**, **ye**, or **yes** to confirm a prompt, and to enter **n** or **no** to deny a prompt. The **no** version restores the default state, which permits pressing <Enter> or <y> to confirm a prompt and entering any other characters to deny a prompt.

**Mode** Global Configuration

## conformed-action

---

**Syntax** For IP and IPv6 rate-limit profiles:

[ no ] conformed-action { drop | transmit | mark *markVal* }

For L2TP rate-limit profiles:

[ no ] conformed-action { drop | transmit }

For MPLS rate-limit profiles:

[ no ] conformed-action { drop | transmit | mark-exp *expValue* }

For hierarchical rate-limit profiles:

[ no ] conformed-action { drop | transmit [ conditional | unconditional | final ] }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the action for packets not conforming to the committed rate and committed burst size, but conforming to the peak rate and peak burst size for a rate-limit profile. The **no** version restores the value to the default value, drop.

- Options**
- drop—Drops the packet
  - transmit—Transmits the packet; for hierarchical rate limits:
    - conditional—Packets must pass the next rate limit
    - unconditional—Packets take resources, but are not affected by the rest of the hierarchy
    - final—Packets exit the hierarchy at rate limit
  - *markVal*—Value in the range 0–255
  - *expValue*—EXP bit value in the range 0–7

**Mode** Rate Limit Profile Configuration

**Related Documentation**

- Creating a Two-Rate Rate-Limit Profile

## conformed-drop-threshold

---

<b>Syntax</b>	<code>conformed-drop-threshold <i>conformedDropThreshold</i></code> <code>no conformed-drop-threshold</code>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0. <b>conditional</b> , <b>unconditional</b> , and <b>final</b> keywords added in JunosE Release 7.2.0.
<b>Description</b>	Configures the threshold above which conformed-drop-events are logged. The <b>no</b> version removes the threshold.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>conformedDropThreshold</i>—Bits per second in the range 0–1073741824</li></ul>
<b>Mode</b>	Statistics Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring Event Statistics</li></ul>

## conformed-fraction

---

**Syntax**    `conformed-fraction conformedFraction`  
              `no conformed-fraction`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the percentage of the total queue that can be occupied before dropping conformed packets. The **no** version returns the conformed fraction to its default setting.

**Options**    • *conformedFraction*—Percentage in the range 0–100; default value is 50

**Mode**    Queue Profile Configuration

**Related Documentation**    • Configuring Queue Profiles to Manage Buffers and Thresholds



## conformed-length

---

**Syntax**    conformed-length *minimumConformedLength* [ *maximumConformedLength* ]  
              no conformed-length

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets minimum and maximum constraints for the queue's conformed lengths. The **no** version removes constraints on the queue's conformed length.

**Options**    • *minimumConformedLength*—Number in the range 0–1073741824  
              • *maximumConformedLength*—Number in the range 0–1073741824

**Mode**    Queue Profile Configuration

**Related Documentation**    • Configuring Queue Profiles to Manage Buffers and Thresholds

## conformed-threshold

---

<b>Syntax</b>	<code>conformed-threshold { percent <i>MinThresholdPercent</i> <i>MaxThresholdPercent</i>   <i>MinThresholdBytes</i> <i>MaxThresholdBytes</i> } <i>MaxDropProbability</i></code>  <code>no conformed-threshold</code>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Specifies the conformed queue thresholds and maximum drop probability. The <b>no</b> version removes conformed threshold.
<b>Options</b>	<ul style="list-style-type: none"><li>• <code>percent</code>—Specifies conformed queue thresholds as percentages</li><li>• <i>MinThresholdPercent</i>—Minimum queue threshold as a percentage of queue length</li><li>• <i>MaxThresholdPercent</i>—Maximum queue threshold as a percentage of queue length</li><li>• <i>MinThresholdBytes</i>—Minimum queue threshold in bytes</li><li>• <i>MaxThresholdBytes</i>—Maximum queue threshold in bytes</li><li>• <i>MaxDropProbability</i>—Maximum drop probability</li></ul>
<b>Mode</b>	Drop Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring RED</li><li>• Configuring WRED</li></ul>

## control-plane

---

**Syntax**    control-plane

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Enters Control Plane Configuration mode. There is no **no** version.

**Mode**    Global Configuration

**Related Documentation**

- Rate-Limiting Traffic Flows

## controlled-interface-type

---

<b>Syntax</b>	<code>controlled-interface-type { <i>controlledInterfaceType</i>   set   superset }</code>  <code>no controlled-interface-type { <i>controlledInterfaceType</i>   all }</code>
<b>Release Information</b>	Command introduced in JunosE Release 7.1.0. <b>set</b> and <b>superset</b> keywords added in JunosE Release 9.2.0.
<b>Description</b>	Assigns controlled-interface types to a QoS parameter definition. Controlled-interface types specify the types of logical interfaces whose queues and nodes can be controlled by instances of the parameter definition. You can specify up to four controlled-interface types for each parameter definition. The <b>no</b> version removes the controlled-interface type from the parameter definition.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>controlledInterfaceType</i>—One of the following controlled-interface types: atm, atm-vc, atm-vp, bridge, ethernet, fr-vc, ip, ip-tunnel, ipv6, l2tp-session, l2tp-tunnel, lsp, serial, svlan, server-port, vlan</li><li>• set—Specifies an interface set as a controlled-interface type</li><li>• superset—Specifies an interface superset as a controlled-interface type</li><li>• all—Removes all controlled-interface types</li></ul>
<b>Mode</b>	QoS Parameter Definition
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring a Basic Parameter Definition for QoS Administrators</a></li><li>• <a href="#">Creating a QoS Parameter on an Interface Superset or Interface Set</a></li></ul>

## controller e3

---

**Syntax**    controller e3 *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Accesses Controller Configuration mode so that you can configure an E3 controller. There is no **no** version.

**Options**    • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Global Configuration

## controller sonet

---

**Syntax**    controller sonet *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Selects an interface on which you want to configure SONET or SDH. There is no **no** version.

**Options**    • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Global Configuration

## controller t3

---

**Syntax**    controller t3 *interfaceSpecifier*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Accesses Controller Configuration mode so that you can configure a T3 controller. There is no **no** version.

**Options**    • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Global Configuration

## convergence-factor

---

**Syntax**    `convergence-factor convergenceFactor`  
              `no convergence-factor`

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Specifies the convergence factor for all simple shared shapers on the router. The convergence factor determines how quickly the dynamic shaping rate converges with the calculated dynamic shaping rate, and is expressed as a percentage of the available bandwidth. The **no** version removes the specified convergence factor from all simple shared shapers on the router.

**Options**    • *convergenceFactor*—Percentage value in the range 0–99; default value is 50

**Mode**    QoS Shared Shaper Control Configuration

**Related Documentation**    • [Configuring Simple Shared Shaper Algorithm Variables](#)



## copy

**Syntax** `copy [ sourcePath ]sourceFilename [ destinationPath ]destinationFilename [ force ]`

**Release Information** Command introduced before JunosE Release 7.1.0.  
*hostName* and *deviceName* variables added in JunosE Release 7.2.0.

**Description** Copies a local or network file. There is no **no** version.



**NOTE:** You cannot change the extension of a file, for example, from .mac to .scr. You can copy software release (.rel) files only *to* the router (download); you cannot copy them *from* the router (upload). See *Copying and Redirecting Files* in the *JunosE System Basics Configuration Guide*, for detailed information on file type usage with the **copy** command.

- Options**
- **sourcePath**—Path to the source in the format:  
*hostName*: | *deviceName*: | /incoming/*subdirectory*/ | /outgoing/*subdirectory*/
  - **hostName**:—Name of the network host
  - **deviceName**:—Name of the device specifying a flash card slot
    - **disk0**—Specifies flash card slot 0 on the primary SRP module; if no device is specified for the primary SRP module, then disk0 is used
    - **disk1**—Specifies flash card slot 1 on the primary SRP module; source and destination file types must be .dmp; supported only on the E120 and E320 routers
    - **standby**—Specifies flash card slot 0 on the standby SRP module for backward compatibility
    - **standby-disk0**—Specifies flash card slot 0 on the standby SRP module
    - **standby-disk1**—Specifies flash card slot 1 on the standby SRP module; source and destination file types must be .dmp; supported only on the E120 and E320 routers
  - **incoming**—Specifies the router's incoming FTP directory
  - **subdirectory**—Name of a subdirectory on the router's FTP server. If the subdirectory does not exist, the router creates it.
  - **outgoing**—Specifies the router's outgoing FTP directory
  - **sourceFilename**—Name of the the source file
  - **destinationPath**—Path to the destination in the format:  
*networkPath* | /incoming/*subdirectory* | /outgoing/*subdirectory*
    - **networkPath**—Path to the network host
    - **incoming**—Specifies the incoming router's FTP directory

- *subdirectory*—Name of a subdirectory on the *ERX* router's FTP server. If the subdirectory does not exist, the router creates it.
- *outgoing*—Specifies the router's outgoing FTP directory
- *destinationFilename*—Name of the destination file
- *force*—Forces a copy, even when the destination file already exists; if a file is marked by the file system as in use because it is required for the current operation or configuration, the **force** keyword cannot force a copy of that file

**Mode** Privileged Exec

## copy running-configuration

**Syntax** `copy running-configuration destination [ force ] [ include-text-config ]`

**Release Information** Command introduced before JunosE Release 7.1.0.  
**include-text-config** keyword added in JunosE Release 9.1.0.

**Description** Saves the configuration currently running on the router to a local or remote (network) router configuration file (.cnf) in compressed format. It also embeds the Cyclic Redundancy Check (CRC) value in the header of the configuration file.

Available only if the router is in Automatic Commit mode. There is no **no** version.

- Options**
- *destination*—Destination filename (\*.cnf)
  - *force*—Creates a copy even when the destination file already exists
  - *include-text-config*—Generates the .cnf file, including the text configuration, in compressed format



**NOTE:** A Perl script is provided in the Tools folder of the compressed software image bundle, which you downloaded from the Juniper Networks website, that enables you to view the text configuration in a configuration file that contains both binary and text configuration. The Perl script supports multiple platforms. The “Usage and Troubleshooting document for desktop tool” file in PDF format provides an explanation of how to extract the system configuration file, using the `extractScrFromCnf.pl` script.

**Mode** Privileged Exec

## **copy running-configuration startup-configuration**

---

**Syntax**    copy running-configuration startup-configuration

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Saves all outstanding (unsaved) configuration changes to nonvolatile storage; an exact alias of the **write memory** command. Available if the router is in either Automatic Commit mode or Manual Commit mode. If you issue this command from Automatic Commit mode, the CLI notifies you that the command is not necessary, but allows you to proceed. This command is prevented during the high availability initialization state. If the command is issued during this state, the CLI notifies you of the state and requests that you try again later. There is no **no** version.

**Mode**    Privileged Exec

## copy startup-configuration

---

**Syntax**    copy startup-configuration *destination* [ force ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Copies the previously saved startup configuration to a local or remote (network) router configuration (\*.cnf) file. Available only if the router is in Manual Commit mode. If you have made but not saved any configuration changes, those changes are not in the startup configuration. There is no **no** version.

- Options**
- *destination*—Destination filename (\*.cnf)
  - *force*—Creates a copy even if the destination file already exists

**Mode**    Privileged Exec

## cost

---

**Syntax**    `cost intfCost`

`no cost`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a cost metric for an OSPF remote-neighbor interface. Used in the calculation of the SPF routing table. The **no** version restores the default value.

**Options**

- *intfCost*—Link-state metric cost; a number in the range 1–65535; default value is 10 if there is no route to the remote neighbor; otherwise, the default is calculated based on the bandwidth of the physical interface used to reach the remote neighbor and the OSPF auto-cost reference bandwidth

**Mode**    Remote Neighbor Configuration

## country

---

**Syntax** [ no ] country *countryCode*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a country name used to generate certificate requests. The **no** version removes the country name.

**Options** • *countryCode*—Two-character country name

**Mode** IPSec Identity Configuration

## crc

---

**Syntax**    `crc { 16 | 32 | none }`

`no crc`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the size of the cyclic redundancy check. CRC is an error-checking technique that uses a calculated numeric value to detect errors in transmitted data. 16 and 32 indicate the number of check digits per frame that are used to calculate the FCS. Both the sender and receiver must use the same setting. The default value is 16. The **no** version restores the value to the default.

- Options**
- 16—Specifies CRC-16, which transmits streams of 8-bit characters and generates 16-bit check bits per frame
  - 32—Specifies CRC-32, which transmits longer streams at faster rates and therefore provides better ongoing error detection
  - none—Disables CRC checking

**Mode**    Interface Configuration



## crl

---

**Syntax**   crl { ignored | optional | required }  
             no crl

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Controls how the router checks certificate revocation lists (CRLs) when determining whether to accept a peer's certificates. The **no** version restores the default setting.

- Options**
- ignored—Specifies that the router will not try to find or use CRLs
  - optional—Specifies that the router will try to find a CRL. If a CRL is found, the peer certificate must not appear in the CRL. If no CRL is found, the peer can still authenticate; this is the default.
  - required—Specifies that the router must find a valid CRL; the CRL must be current, and the peer certificate must not appear in the CRL

**Mode**   IPSec CA Identity Configuration

## crypto key dss

---

**Syntax**    crypto key { generate | zeroize } dss

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Controls SSH server daemon and creation/deletion of SSH server host key. This command is not displayed by the **show config** command. There is no **no** version.

SSH can be enabled or disabled regardless of the state of the Telnet daemon. If SSH is enabled, use access control lists to limit access through Telnet.



**NOTE:** When you perform a stateful SRP switchover operation on a device with a large number of virtual routers (VRs) when SSH is configured on VRs other than the default, SSH can sometimes become disabled. This condition happens if SSH attempts to bind with a VR before the VR becomes reenabled after the restart. In this case, after stateful SRP switchover is completed, if you enter the **crypto key zeroize dss** command to disable the SSH server daemon, a message is displayed stating that the VR instance is not enabled and prompts you to retry after SSH is reenabled on that VR. After the VR instance is reenabled, you must manually reenab SSH either by accessing the console VTY or creating a Telnet session to the router by using the **crypto key generate dss** command.

- Options**
- **generate**—Creates the SSH server host key and enables the daemon
  - **zeroize**—Deletes the SSH server host key and stops the SSH daemon if it is running. Issuing this command terminates any active client sessions. The next time the router boots after this command is issued, the SSH server daemon is not started.

**Mode**    Global Configuration

**Related Documentation**

- Setting Virtual Terminal Access Lists

## CHAPTER 5

# D Commands

## data-character-bits

---

**Syntax** data-character bits { 7 | 8 }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the number of data bits available for characters for all sessions on the specified vty lines. There is no **no** version.

- Options**
- 7—Specifies 7 data bits per character; this setting supports only characters in the standard ASCII set
  - 8—Specifies 8 data bits per character; default setting, supports the full set of 8-bit international characters

**Mode** Line Configuration

## dead-interval

---

**Syntax**    `dead-interval deadInterval`

`no dead-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time period that the OSPF router waits without seeing hello packets from a remote neighbor before declaring the neighbor to be down. The **no** version restores the default value.

**Options**    • *deadInterval*—Number in the range 1–65535 seconds; default value is 40 seconds

**Mode**    Remote Neighbor Configuration

## deadtime

---

**Syntax**    *deadtime recovery*  
*no deadtime*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the amount of time, in minutes, that a server is marked as unavailable if a request times out for the configured retry count. If a server fails to answer a request, it is marked “unavailable” by the router. The router does not send requests to the server for the configured time. The **no** version restores the default value, 0, turning off the deadtime mechanism.

**Options**    • *recovery*—Number of minutes that a server is marked as unavailable, in the range 0–1440; default value is 0

**Mode**    RADIUS Configuration

## debounce

---

**Syntax**    `debounce [ seconds ]`

`no debounce`

**Release Information**    Command introduced in JunosE Release 9.3.0.

**Description**    Enables the debounce timer and sets the time interval that the interface waits before reporting a state change to the upper-layer protocols. The **no** version restores the default behavior, disabling debounce on the interface.

**Options**

- *seconds*—Interval for which an interface must maintain a given state before the interface reports the state change to the upper-layer protocols. Number in the range 1–5 seconds; default value is 1 second.

**Mode**    Interface Configuration

## debounce-interval

---

**Syntax**    `debounce-interval seconds`  
`no debounce-interval`

**Release Information**    Command introduced in JunosE Release 9.3.0.

**Description**    Modifies the minimum time an Ethernet interface must maintain a given state—for example, up or down—before the interface notifies the upper-layer protocols of the state change. The **no** version restores the default value, 1 second.



.....  
**NOTE:** You can configure this command only if you have enabled the  
debounce timer feature using the **debounce** command.  
.....

**Options**

- *seconds*—Interval for which an interface must maintain a given state before the interface reports the state change to the upper-layer protocols. Number in the range 1–5 seconds; default value is 1 second.

**Mode**    Interface Configuration



## debounce-time

---

**Syntax**    `debounce-time interval`

`no debounce-time`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the interval to wait before bringing up a RIP interface that was brought down. The **no** version restores the default value, 10.

**Options**    • *interval*—Seconds in the range 0–60

**Mode**    Address Family Configuration, Router Configuration

## debug ip bgp

---

**Syntax**    debug ip bgp [ in | out ] [ *peerAddress* [ *peerAddressMask* ] ] [ *bgpLog* ]  
             [ router *routerName* ] [ filtering-router *filteringRouterName* ] [ *accessClassName* ]  
             [ route-map *mapName* ] [ severity { *severityValue* | *severityNumber* } ]  
             [ verbosity *verbosityLevel* ] [ secondary ]

no debug ip bgp [ in | out ] [ *peerAddress* [ *peerAddressMask* ] ] [ *bgpLog* ]  
             [ router *routerName* ] [ filtering-router *filteringRouterName* ] [ *accessClassName* ]  
             [ route-map *mapName* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Shows information about the selected variable. The **no** version disables the display.

- Options**
- in—Displays information for inbound events
  - out—Displays information for outbound events
  - *peerAddress*—IP address of BGP peer for which information is displayed
  - *peerAddressMask*—Network mask of BGP peer for which information is displayed
  - *bgpLog*—BGP log of interest; one of the following options:
    - dampening—BGP dampening event; route is suppressed or no longer suppressed by route-flap dampening
    - events—BGP finite state machine events and transitions
    - keepalives—BGP keepalive message events
    - next-hops—BGP next hop events
    - updates—BGP routing table update events
  - *routerName*—Name of the virtual router that owns the BGP router for which information is being displayed
  - *filteringRouterName*—Name of the virtual router that owns the access class and route map parameters
  - *accessClassName*—Name of an access list to filter output
  - *mapName*—Name of a route map to filter output
  - severity—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - emergency or 0—System unusable
    - alert or 1—Immediate action needed
    - critical or 2—Critical condition exists

- *error or 3*—Error condition
- *warning or 4*—Warning condition
- *notice or 5*—Normal but significant condition
- *info or 6*—Informational message
- *debug or 7*—Debug message
- *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
  - *low*—Terse
  - *medium*—Moderate detail
  - *high*—Verbose
- *secondary*—Indicates that the specified filter conditions for the log are imposed in addition to any that were previously specified; if omitted, the specified filter conditions replace any that were previously specified

**Mode** Privileged Exec

## debug ip mbgp

---

**Syntax** debug ip mbgp [ in | out ] [ *peerAddress* [ *peerAddressMask* ] ] [ *bgpLog* ]  
[ *router routerName* ] [ filtering-router *filteringRouterName* ] [ *accessClassName* ]  
[ route-map *mapName* ] [ severity { *severityValue* | *severityNumber* } ]  
[ verbosity *verbosityLevel* ] [ secondary ]

no debug ip mbgp [ in | out ] [ *peerAddress* [ *peerAddressMask* ] ] [ *bgpLog* ]  
[ *router routerName* ] [ filtering-router *filteringRouterName* ] [ *accessClassName* ]  
[ route-map *mapName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Shows information about the selected variable. The **no** version disables the display.

- Options**
- in—Displays information for inbound events
  - out—Displays information for outbound events
  - *peerAddress*—IP address of BGP peer for which information is displayed
  - *peerAddressMask*—Network mask of BGP peer for which information is displayed
  - *bgpLog*—BGP log of interest; one of the following options:
    - dampening—BGP dampening event; route is suppressed or no longer suppressed by route-flap dampening
    - events—BGP finite state machine events and transitions
    - keepalives—BGP keepalive message events
    - next-hops—BGP next hop events
    - updates—BGP routing table update events
  - *routerName*—Name of the virtual router that owns the BGP router for which information is being displayed
  - *filteringRouterName*—Name of the virtual router that owns the access class and route map parameters
  - *accessClassName*—Name of an access list to filter output
  - *mapName* —Name of a route map to filter output
  - severity—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - emergency or 0—System unusable
    - alert or 1—Immediate action needed
    - critical or 2—Critical condition exists

- *error or 3*—Error condition
- *warning or 4*—Warning condition
- *notice or 5*—Normal but significant condition
- *info or 6*—Informational message
- *debug or 7*—Debug message
- *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
  - *low*—Terse
  - *medium*—Moderate detail
  - *high*—Verbose
- *secondary*—Indicates that the specified filter conditions for the log are imposed in addition to any that were previously specified; if omitted, the specified filter conditions replace any that were previously specified

**Mode** Privileged Exec

## debug ip ospf

---

**Syntax**    `debug ip ospf ospfLog [ severity { severityValue | severityNumber } ]`  
              `[ verbosity verbosityLevel ]`  
  
              `no debug ip ospf ospfLog`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Shows information about the selected variable. The **no** version disables the display.

- Options**
- *ospfLog*—OSPF log of interest; one of the following options:
    - *adj*—OSPF adjacency events
    - *elect-dr*—OSPF designated router election
    - *events*—OSPF general events
    - *lsa*—OSPF link-state advertisements events
    - *neighbor*—OSPF neighbor state machine
    - *packets-rcvd*—OSPF packets received
    - *packets-sent*—OSPF packets sent
    - *route*—OSPF route events
    - *spf*—All OSPF shortest path first calculation events
    - *spf-ext*—OSPF shortest path first external route calculation events
    - *spf-inter*—OSPF shortest path first interarea route calculation events
    - *spf-intra*—OSPF shortest path first intra-area route calculation events
  - *severity*—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - *emergency or 0*—System unusable
    - *alert or 1*—Immediate action needed
    - *critical or 2*—Critical condition exists
    - *error or 3*—Error condition
    - *warning or 4*—Warning condition
    - *notice or 5*—Normal but significant condition

- *info or 6*—Informational message
- *debug or 7*—Debug message
- *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
  - *low*—Terse
  - *medium*—Moderate detail
  - *high*—Verbose

**Mode** Privileged Exec

## debug ip pim

---

**Syntax** The syntax differs for PIM Dense Mode and PIM Sparse Mode.

PIM Dense Mode:

```
debug ip pim { pimLog [ severity { severityValue | severityNumber } ]  
[ verbosity verbosityLevel ] | switchState groupAddress sourceAddress |  
dense-mode { on | off } }
```

PIM Sparse Mode:

```
debug ip pim { pimLog [ severity { severityValue | severityNumber } ]  
[ verbosity verbosityLevel ] | switchState groupAddress sourceAddress |  
sparse-mode { on | off | sg-state [ group groupAddress  
[ source sourceAddress ] | rp rpAddress ] [ count ] } }
```

```
no debug ip pim pimLog
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Shows information about the selected variable. The **no** version disables the display.

- Options**
- *pimLog*—PIM log of interest; one of the following options:
    - *autoRp-rcvd*—Auto-RP packets received
    - *autoRP-sent*—Auto-RP packets sent
    - *engineering*—PIM engineering
    - *hellos-rcvd*—PIM hello messages received
    - *hellos-sent*—PIM hello messages sent
    - *packets*—PIM packets received and sent
    - *packets-rcvd*—PIM packets received
    - *packets-sent*—PIM packets sent
  - *severity*—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - *emergency* or 0—System unusable
    - *alert* or 1—Immediate action needed
    - *critical* or 2—Critical condition exists
    - *error* or 3—Error condition



- *warning or 4*—Warning condition
- *notice or 5*—Normal but significant condition
- *info or 6*—Informational message
- *debug or 7*—Debug message
- *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
  - *low*—Terse
  - *medium*—Moderate detail
  - *high*—Verbose
- *switchState*—Switches from one type of tree to another
  - *rpt-switch*—Switch from a shortest-path tree to a shared path tree
  - *spt-switch*—Switch from a shared-path tree to a shortest path tree
- *groupAddress*—IP address of the multicast group
- *sourceAddress*—IP address of the multicast source
- *on*—Turns on the specified PIM mode on all virtual routers
- *off*—Turns off the specified PIM mode on all virtual routers
- *sg-state*—Displays information about the relationship between a source, multicast group, and RP router
- *rp*—Displays information about the relationships between sources, groups, and the specified RP router
- *rpAddress*—Address of the RP router
- *count*—Displays one of the following
  - (with no optional keywords) number of relationships between a source, multicast group, and RP router
  - (with the **group** keyword) number of sources associated with the multicast group for PIM sparse mode
  - (with the **source** and **group** keywords) number of source-group pairs for PIM sparse mode
  - (with the **rp** keyword) number of source-group pairs associated with the RP router for PIM sparse mode

**Mode** Privileged Exec

## debug ip rip

---

**Syntax**    `debug ip rip ripLog [ severity { severityValue | severityNumber } ]`  
              `[ verbosity verbosityLevel ]`  
  
              `no debug ip rip ripLog`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Shows information about the selected variable. The **no** version disables the display.

- Options**
- *ripLog*—RIP log of interest; one of the following options:
    - *events*—General RIP events, such as removing RIP from an interface or creating the RIP process
    - *route*—Events associated with two RIP routers exchanging routes
  - *severity*—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - *emergency or 0*—System unusable
    - *alert or 1*—Immediate action needed
    - *critical or 2*—Critical condition exists
    - *error or 3*—Error condition
    - *warning or 4*—Warning condition
    - *notice or 5*—Normal but significant condition
    - *info or 6*—Informational message
    - *debug or 7*—Debug message
  - *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
    - *low*—Terse
    - *medium*—Moderate detail
    - *high*—Verbose

**Mode**    Privileged Exec

## debug ipv6 ospf

**Syntax**    `debug ipv6 ospf ospfLog [ severity { severityValue | severityNumber } ]`  
                   `[ verbosity verbosityLevel ]`  
                   `no debug ipv6 ospf ospfLog`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Shows information about the selected variable. The **no** version disables the display.

- Options**
- *ospfLog*—OSPF log of interest; one of the following options:
    - *adj*—OSPF adjacency events
    - *elect-dr*—OSPF designated router election
    - *events*—OSPF general events
    - *lsa*—OSPF link-state advertisements events
    - *neighbor*—OSPF neighbor state machine
    - *packets-rcvd*—OSPF packets received
    - *packets-sent*—OSPF packets sent
    - *route*—OSPF route events
    - *spf*—All OSPF shortest path first calculation events
    - *spf-ext*—OSPF shortest path first external route calculation events
    - *spf-inter*—OSPF shortest path first interarea route calculation events
    - *spf-intra*—OSPF shortest path first intra-area route calculation events
  - *severity*—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - *emergency or 0*—System unusable
    - *alert or 1*—Immediate action needed
    - *critical or 2*—Critical condition exists
    - *error or 3*—Error condition
    - *warning or 4*—Warning condition
    - *notice or 5*—Normal but significant condition

- *info or 6*—Informational message
- *debug or 7*—Debug message
- *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
  - *low*—Terse
  - *medium*—Moderate detail
  - *high*—Verbose

**Mode** Privileged Exec

## debug ipv6 pim

**Syntax** debug ipv6 pim  
 { *pimLog* [ *severity* { *severityValue* | *severityNumber* } ] [ *verbosity* *verbosityLevel* ] |  
*switchState* *groupAddress* *sourceAddress* |  
 dense-mode { on | off } |  
 sparse-mode { on | off | sg-state [ *group* *groupAddress*  
 [ *source* *sourceAddress* ] | *rp* *rpAddress* ] [ *count* ] } }  
 no debug ipv6 pim *pimLog*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Shows information about the selected variable. The **no** version disables the display.

- Options**
- *pimLog*—PIM log of interest; one of the following options:
    - autoRp-rcvd—Auto-RP packets received
    - autoRP-sent—Auto-RP packets sent
    - engineering—PIM engineering
    - hellos-rcvd—PIM hello messages received
    - hellos-sent—PIM hello messages sent
    - packets—PIM packets received and sent
    - packets-rcvd—PIM packets received
    - packets-sent—PIM packets sent
  - *severity*—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - emergency or 0—System unusable
    - alert or 1—Immediate action needed
    - critical or 2—Critical condition exists
    - error or 3—Error condition
    - warning or 4—Warning condition
    - notice or 5—Normal but significant condition
    - info or 6—Informational message
    - debug or 7—Debug message

- *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:
  - low—Terse
  - medium—Moderate detail
  - high—Verbose
- *switchState*—Switches from one type of tree to another
  - rpt-switch—Switch from a shortest-path tree to a shared path tree
  - spt-switch—Switch from a shared-path tree to a shortest path tree
- *groupAddress*—IPv6 address of the multicast group
- *sourceAddress*—IPv6 address of the multicast source
- on—Turns on the specified PIM mode on all virtual routers
- off—Turns off the specified PIM mode on all virtual routers
- sg-state—Displays information about the relationship between a source, multicast group, and RP router
- rp—Displays information about the relationships between sources, groups, and the specified RP router
- *rpAddress*—Address of the RP router
- count—Displays one of the following
  - (with no optional keywords) number of relationships between a source, multicast group, and RP router
  - (with the **group** keyword) number of sources associated with the multicast group for PIM sparse mode
  - (with the **source** and **group** keywords) number of source-group pairs for PIM sparse mode
  - (with the **rp** keyword) number of source-group pairs associated with the RP router for PIM sparse mode

**Mode** Privileged Exec

## debug isis

**Syntax**    `debug isis isisLog [ severity { severityValue | severityNumber } ]`  
                   `[ verbosity verbosityLevel ]`  
                   `no debug isis isisLog`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Displays debug-related information about selected IS-IS log parameters. This command manipulates the same log as the Global Configuration **log** commands. The **no** version disables debugging display.

- Options**
- *isisLog*—IS-IS log of interest; one of the following options:
    - *adj-packets*—IS-IS adjacency-related packets, such as hello packets sent and IS-IS received adjacencies going up and down
    - *mpls traffic-eng advertisements*—MPLS traffic-engineering agent advertisements
    - *mpls traffic-eng agents*—MPLS traffic-engineering agents
    - *snp-packets*—IS-IS CSNPs/PSNPs
    - *spf-events*—Shortest path first events
    - *spf-statistics*—SPF timing and statistic data
    - *spf-triggers*—SPF triggering events
    - *update-packets*—Update-related packets
  - *severity*—Specifies the minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7; the lower the number, the higher the priority:
    - *emergency or 0*—System unusable
    - *alert or 1*—Immediate action needed
    - *critical or 2*—Critical condition exists
    - *error or 3*—Error condition
    - *warning or 4*—Warning condition
    - *notice or 5*—Normal but significant condition
    - *info or 6*—Informational message
    - *debug or 7*—Debug message
  - *verbosityLevel*—Verbosity of the log category's messages; can be any of the following:

- low—Terse
- medium—Moderate detail
- high—Verbose

**Mode** Privileged Exec



## default-fields peer

**Syntax** [ no ] default-fields peer *fieldOptions*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the fields that will appear by default in the output of subsequently issued `show ip bgp summary` and `show bgp ipv6 summary` commands. The **no** version removes the fields from the output.

- Options**
- *fieldOptions*—Field(s) to be displayed, in the format  
all | [ dynamic | intro | last-reset-reason | messages-received | messages-sent |  
more-in-queue | peer-type | prefixes-received | remote-as | rib-version |  
send-queue-length | state | times-up | up-down-time | updates-received | updates-sent  
]\*
  - all—All available information; not recommended, because this information for each network does not fit on a single line and is difficult to read
  - dynamic—Nature of peer, dynamic or not
  - intro—Introductory information about the state of various BGP attributes; this information is displayed only if you specify this keyword
  - last-reset-reason —Reason for most recent reset
  - messages-received—Total number of messages received from the peer
  - messages-sent—Total number of messages sent to the peer
  - more-in-queue—Status indicating whether any messages are waiting to be sent to this peer
  - peer-type—Type of BGP peer: internal, external, or confederation
  - prefixes-received—Number of unique prefixes received from the peer
  - remote-as—Remote AS number of the peer
  - rib-version—Last RIB version queued to be sent to this peer
  - send-queue-length—Number of messages queued to be sent to this peer
  - state—State of the BGP session
  - times-up—Number of times the session has been established
  - up-down-time—How long the session has been up or down
  - updates-received—Number of update messages received from the peer

- updates-sent—Number of update messages sent to the peer
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Router Configuration

## default-fields route

**Syntax** [ no ] default-fields route *fieldOptions*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the fields that will appear by default in the output of any subsequently issued **show ip bgp** or **show bgp ipv6** command that displays routes (except for the **show ip bgp summary** or **show bgp ipv6 summary** commands). The **no** version removes the fields from the output.

- Options**
- *fieldOptions*—Field(s) to be displayed, in the format all | [ afi | aggregator | as-path | atomic-aggregate | best | clusters | communities | extended-communities | imported | intro | in-label | loc-pref | med | next-hop | next-hop-cost | origin | originator-id | out-label | peer | peer-type | rd | safi | stale | unknown-types | weight ]\*
    - all—All available information; not recommended, because this information for each network does not fit on a single line and is difficult to read
    - afi—Address family identifier
    - aggregator—AS number and IP address of aggregator
    - as-path—AS path through which this route has been advertised
    - atomic-aggregate—Whether the atomic aggregate attribute is present
    - best—Whether this is the best route for the prefix
    - clusters—List of cluster IDs through which the route has been advertised
    - communities—Community number associated with the route
    - extended-communities—Extended community
    - imported—Whether the route was imported
    - intro—Introductory information about the state of various BGP attributes; this information is displayed only if you specify this keyword
    - in-label—MPLS label for the route; the label received with incoming MPLS frames
    - loc-pref—Local preference for the route
    - med—Multiexit discriminator for the route
    - next-hop—IP address of the next router that is used when forwarding a packet to the destination network
    - next-hop-cost—Whether the indirect next hop of the route is unreachable, if not, displays IGP cost to the indirect next hop

- out-label—MPLS label for the route; the label with outgoing MPLS frames
- peer—IP address of BGP peer from which route was learned
- peer-type—Type of BGP peer: internal, external, or confederation
- origin—Origin of the route
- originator-id—Router ID of the router in the local AS that originated the route
- rd—Route distinguisher
- safi—Subsequent address family identifier
- stale—Route that has gone stale due to peer restart
- unknown-types—Attribute codes for unknown path attributes
- weight—Weight of the route
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Router Configuration

## default-information originate

**Syntax** For BGP:

default-information originate [ route-map *mapTag* ]

no default-information originate [ route-map [ *mapTag* ] ]

For IS-IS:

[ no ] default-information originate [ route-map *mapTag* ]

For RIP:

[ no ] default-information originate [ route-map *mapTag* ]

default-information originate always

For OSPF:

[ no ] default-information originate [ always | metric *metricValue* | metric-type 1 | metric-type 2 | route-map *mapTag* ]\*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables BGP to advertise a default route (0.0.0.0/0) if the default route exists in the IP routing table. If the default route does not exist, you must configure it using the **ip route** command.

When you issue this command in the route-target address family, BGP advertises the Default-RT-MEM-NLRI route (0:0:0/0)

For IS-IS, OSPF, and RIP, configures a default route for the distribution of default information into the respective routing domain. IS-IS creates the default route (0.0.0.0/0) if it does not exist in the IP routing table. OSPF and RIP do not create the default route unless you use the **always** option.

For all protocols, the **no** version disables advertisement of the default route. The syntax varies with the protocol.

- Options**
- *mapTag*—Name of route map used to import the default route; string of up to 32 characters
  - **always**—Creates the default route, so that it is always advertised
  - *metricValue*—Sets the metric for the default route; in the range 0–4294967295
  - **metric-type 1**—Sets the default route's metric type to OSPF external type 1
  - **metric-type 2**—Sets the default route's metric type to OSPF external type 2
  - **\***—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Address Family Configuration, Router Configuration

## default-metric

---

**Syntax** [ no ] default-metric *metricValue* [ *interfaceType* *interfaceSpecifier* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures RIP to use this metric on redistributed routes on all subsequently created interfaces. The **no** version restores the default value, 0.

**Options**

- *metricValue*—Metric to apply to routes; in the range 1–16
- *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Address Family Configuration, Router Configuration

## default-router

---

**Syntax**    `default-router ipAddressPrimary [ ipAddressSecondary ]`  
              `no default-router`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IP address of the router that the subscriber's computer will use for traffic destined for locations beyond the local subnet. The default router must be on the same subnet as the local server pool addresses configured with the **network** command. The **no** version removes the association between the address pool and the router.

- Options**
  - *ipAddressPrimary*—IP address of preferred router
  - *ipAddressSecondary*—IP address of secondary router

**Mode**    DHCP Local Pool Configuration



## default-upper-type mlppp

---

**Syntax**    default-upper-type mlppp  
              no default-upper-type

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies that L2TP creates an MLPPP interface for the current LNS session when full LCP proxy data is not available. The **no** version deletes the MLPPP specification.

**Mode**    L2TP Destination Profile Host Configuration

## delete

---

**Syntax**    delete { *filename* | directory *directoryName*[:*fileName* ] } [ force ]

**Release Information**    Command introduced before JunosE Release 7.1.0.  
*fileName* variable added for **directory** keyword in JunosE Release 9.1.0.

**Description**    Deletes a directory or file in nonvolatile storage. There is no **no** version.



**NOTE:** For detailed information on file type usage with the **delete** command, see *Deleting Files* in the *JunosE System Basics Configuration Guide*.

- Options**
- *fileName*—Name of the local file you are deleting (for example, `system1.cnf`); in User Exec and Privileged Exec mode only, an asterisk (\*) in any position in the filename substitutes for zero or more characters; using an asterisk causes the CLI to prompt you for confirmation before the file or directory is deleted. You cannot delete `reboot.hty` or `system.log` files when you use an asterisk.
  - *directoryName*—Path of a directory. To delete a file in user space, specify the incoming or outgoing directory on the FTP server; you can specify the name of a subdirectory in the incoming or outgoing directory. You cannot use an asterisk in a directory name.
  - **force**—Forces deletion of directory or file even when it is not empty; however, if a file in the specified directory, or a specified file, is marked by the file system as in use because it is required for the current operation or configuration, the **force** keyword cannot force a deletion of the directory.

The **force** keyword is ignored when you attempt to delete any `.dmp` or `.tsa` file (unless the deletion is issued from a `.mac` or `.scr` file); this means that the CLI always prompts for confirmation for these file types.

**Mode**    Boot, Privileged Exec, User Exec

## delta-sampling

---

**Syntax** delta-sampling [ discontinuity-id *mibId*  
| discontinuity-id-type { timeStamp | timeTicks } ]

no delta-sampling [ discontinuity-id ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies delta sampling for the trigger you are configuring. The **no** version returns the trigger to the default sampling method—absolute-value sampling.

- Options**
- discontinuity-id—Specifies a discontinuity MIB ID for the sample. The discontinuity MIB ID monitors the sample for any discontinuity errors during the sample frequency. If a discontinuity error occurs, the router removes the sampling for that interval.
  - *mibId*—Object ID of the discontinuity MIB attribute that you want to use for this trigger
  - discontinuity-id-type—Specifies a discontinuity ID type (either timeStamp or timeTicks). The discontinuity ID type indicates the time value that you expect for a specific sample.

**Mode** SNMP Trigger Configuration

## deny

---

**Syntax** [ no ] deny *domainName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the domain name(s) that are to be denied access to AAA authentication. The **no** version negates the command.

**Options** • *domainName*—Name of the domain; maximum of 64 characters

**Mode** AAA Profile Configuration

## description

**Syntax**    `description name`  
               `no description`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    In Controller Configuration mode, assigns a text description or an alias to a CT3, E3, T3, or SONET/SDH interface. Use the `show controllers e3`, `show controllers sonet`, `show controllers t1`, or `mpls rsvp disable` command to display the description. The **no** version removes the description or alias.

In VRF Configuration mode, assigns a text description or an alias to the VRF. The **no** version removes the description or alias.



**NOTE:** In Interface Configuration mode, this command has been replaced by the `ip description` command for assigning a description to a static IP interface. This command may be removed completely from Interface Configuration mode in a future release.

**Options**    • *name*—Text string or alias of up to 256 characters (in Interface Configuration mode) or up to 80 characters (in Controller Configuration mode and VRF Configuration mode)

**Mode**    Controller Configuration, Interface Configuration, VRF Configuration

## dhcp delete-binding

**Syntax** To delete the DHCP client with the specified binding ID:

```
dhcp delete-binding bindingId
```

To delete all DHCP client bindings or all DHCP client bindings of a particular type on the specified subnet:

```
dhcp delete-binding { all | all-local | all-external | all-relay-proxy } [ subnetAddress ]
```

To delete DHCP client bindings of a particular type on the specified subnet:

```
dhcp delete-binding { local | external | relay-proxy } [ subnetAddress ]
```

To delete DHCP client bindings for the specified IP prefix:

```
dhcp delete-binding [ local | external | relay-proxy ] [ subnetAddress ] ip-prefix ipPrefix
```

To delete DHCP client bindings for the specified interface string:

```
dhcp delete-binding [ local | external | relay-proxy ] [ subnetAddress ] interface string
```

To delete DHCP client bindings without a lower-layer interface:

```
dhcp delete-binding [ local | external | relay-proxy ] [ subnetAddress ] no-interface
```

To delete DHCP client bindings for the specified agent-circuit-id suboption (suboption 1) string of the DHCP relay agent information option (option 82):

```
dhcp delete-binding [ local | external | relay-proxy ] [ subnetAddress ] circuit-id string
```

To delete DHCP client bindings for the specified agent-remote-id suboption (suboption 2) string of the DHCP relay agent information option (option 82):

```
dhcp delete-binding [ local | external | relay-proxy ] [ subnetAddress ] remote-id string
```

**Release Information** Command introduced in JunosE Release 8.1.0.

**local**, **external**, **relay-proxy**, **interface**, **no-interface**, **ip-prefix**, **circuit-id**, and **remote-id** keywords and *subnetAddress*, *ipAddress*, and *string* variables added in JunosE Release 9.3.0.

**Description** Deletes the specified DHCP client bindings. There is no **no** version.



**NOTE:** This command replaces the deprecated **clear ip dhcp-local binding** and **dhcp-external delete-binding** commands, which may be removed completely in a future release.

- Options**
- *bindingId*—DHCP binding ID for a specific client
  - *all*—Specifies all DHCP local server, DHCP external server, and DHCP relay proxy client bindings
  - *all-local*—Specifies all DHCP local server client bindings
  - *all-external*—Specifies all DHCP external server client bindings
  - *all-relay-proxy*—Specifies all DHCP relay proxy client bindings
  - *local*—Specifies DHCP local server client bindings that meet the deletion criteria
  - *external*—Specifies DHCP external server client bindings that meet the deletion criteria
  - *relay-proxy*—Specifies DHCP relay proxy client bindings that meet the deletion criteria
  - *subnetAddress*—IP address of the subnet on which the DHCP clients reside
  - *ipPrefix*—IP prefix (address and subnetwork mask) of the DHCP clients; for example, 10.10.10.0/24
  - *no-interface*—Specifies DHCP clients without a lower-layer interface; use this keyword to delete DHCP client bindings configured over dynamic interfaces for which the lower-layer interface has been shut down
  - *string*—Regular expression string that represents the interface, circuit ID, or remote ID to be matched; you must enclose elements containing a space within double quotes (“*one element*”)

Each element is either a literal string, a metacharacter, or a combination. You can remove the special meaning of a metacharacter by preceding it with a backslash (\). Regular expressions support the following metacharacters:

- *^* Matches the beginning of the input string. Alternatively, when used as the first character within brackets—*[^ ]*—matches any number except the ones specified within the brackets.
- *\$* Matches the end of the input string
- *.* (period) Matches any single character, including white space
- *\** Matches 0 or more sequences of the immediately previous character or pattern.
- *+* Matches 1 or more sequences of the immediately previous character or pattern
- *?* Matches 0 or 1 sequence of the immediately previous character or pattern
- *( )* Specifies patterns for multiple use when followed by one of the multiplier metacharacters: asterisk *\**, plus sign *+*, or question mark *?*
- *[ ]* Matches any enclosed character; specifies a range of single characters
- *–* (hyphen) Used within brackets to specify a range of AS or community numbers

- `_` (underscore) Matches a `^`, a `$`, a comma, a space, a `{`, or a `}`. Placed on either side of a string to specify a literal and disallow substring matching. Numerals enclosed by underscores can be preceded or followed by any of the characters listed above
- `|` Matches characters on either side of the metacharacter; logical OR

You must specify the interface string as a regular expression without spaces; for example, `fastEthernet1.1/100` or `fastEthernet.*100`

The following rules apply for representing nonprintable character sequences in the circuit ID string or the remote ID string:

- To represent the binary sequence `0d 0a` (hex), use the string `'\\r\\n'`. This consists of four ASCII characters: `5c` for `\\`, `72` for `r`, `5c` for `\\`, and `6e` for `n`.

For example, to match the sequence `74 65 73 74 0d 0a 6f 6e 65` (hex), use the string `'test\\r\\n'`. In this string, `74` is represented by `t`, `65` is represented by `e`, `73` is represented by `s`, `74` is represented by `t`, `0d 0a` is represented by `\\r\\n`, `6f` is represented by `o`, `6e` is represented by `n`, and `65` is represented by `e`.

- To represent the binary sequence `0d 00` (hex), use the string `'\\r'`. This consists of two ASCII characters: `5c` for `\\`, and `72` for `r`.
- To represent the binary sequence `0a 00` (hex), use the string `'\\n'`. This consists of two ASCII characters: `5c` for `\\`, and `6e` for `n`.

For example, to match the sequence `74 65 73 74 0a 00 6f 6e 65` (hex), use the string `'test\\n'`. In this string, `74` is represented by `t`, `65` is represented by `e`, `73` is represented by `s`, `74` is represented by `t`, `0a 00` is represented by `\\n`, `0a` is represented by `\\n`, `6f` is represented by `o`, `6e` is represented by `n`, and `65` is represented by `e`.

- To represent all other cases, use the string `'\\xab'`, where `ab` is a hex code of the byte. For example, to represent byte `3A`, use `'\\x3a'`. This consists of four ASCII characters: `5c` for `\\`, `78` for `x`, `33` for `3`, and `61` for `a`.

As another example, to match the sequence `74 65 73 74 f3 6f 6e 65` (hex), use the string `'test\\xf3one'`. In this string, `74` is represented by `t`, `65` is represented by `e`, `73` is represented by `s`, `74` is represented by `t`, byte `F3` is represented by `\\xf3`, `6f` is represented by `o`, `6e` is represented by `n`, and `65` is represented by `e`.

**Mode** Privileged Exec



---

## dhcp-external delete-binding

---

**Syntax** dhcp-external delete-binding [ binding-id *bindingId* | all ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Deletes a specific client binding or all bindings from the virtual router's DHCP binding table. There is no **no** version.



.....

**NOTE:** This command is deprecated and might be removed completely in a future release. The function provided by this command has been replaced by the **dhcp delete-binding** command.

.....

- Options**
- *bindingId*—DHCP binding ID associated with the user.
  - all—Specifies all bindings

**Mode** Privileged Exec

## dhcp-external duplicate-mac-address

---

**Syntax** [ no ] dhcp-external duplicate-mac-address

**Release Information** Command introduced in JunosE Release 9.3.0.

**Description** Configures the DHCP external server application to use a combination of the MAC address and the gateway IP address (giaddr) to uniquely identify DHCP clients attached to the router. This behavior is also referred to as *duplicate MAC mode*. The **no** version restores the default behavior, also known as *unique MAC mode*, which uses only the MAC address to uniquely identify DHCP clients.

**Mode** Global Configuration

**Related Documentation**

- DHCP External Server Identification of Clients with Duplicate MAC Addresses Overview
- Configuring DHCP External Server to Uniquely Identify Clients with Duplicate MAC Addresses

## dhcpv6 delete-binding

---

<b>Syntax</b>	dhcpv6 delete-binding { all   <i>ipv6Prefix</i>   <i>string</i> }
<b>Release Information</b>	Command introduced in JunosE Release 11.0.0.
<b>Description</b>	Deletes the specified DHCPv6 client bindings. There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"><li>• all—Specifies all DHCPv6 client bindings.</li><li>• <i>ipv6Prefix</i>—IPv6 prefix (address and subnetwork mask) of the DHCPv6 clients; for example, 2002:2:4:1::/64</li><li>• <i>string</i>—Local address pool name in the range 1–16 characters; for example, server4pool</li></ul>
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Deleting DHCPv6 Client Bindings</li><li>• Monitoring DHCPv6 Local Server Binding Information</li></ul>

## diag

---

**Syntax** `diag slotNumber [ subsystem ] [ force ]`

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Reboots the SRP module or line module in the specified slot on all E Series routers and performs diagnostic tests. There is no **no** version.

- Options**
- *slotNumber*—Number of the chassis slot that contains the SRP module or line module
  - *subsystem*—Type of subsystem on the E120 router or the E320 router; use when the specified *slotNumber* is a slot that contains an SRP module
    - *srp*—Indicates the system controller (SC) on one or both SRP modules; specify this keyword to restart only the portion of the SC on the individual SRP module
    - *fabric*—Indicates the portion of the switch fabric on the SRP modules; specify this keyword to restart only an individual fabric slice
  - *force*—Specifies that the system manually confirm conflicting conditions when the slot of the active SRP module is specified

**Mode** Privileged Exec

## diag-level

---

**Syntax**    diag-level [ normal ] [ bypass ]

**Release Information**    Command introduced in JunosE Release 9.2.0.

**Description**    Sets the diagnostics level on the active or standby SRP module to reduce boot time during a cold and a warm boot. The default diagnostics level is normal. There is no **no** version.

**Options**    • normal—executes full diagnostics on the boot of the line card  
              bypass—skips diagnostic tests on the boot of the line card

**Mode**    Global Configuration

## dir

---

**Syntax**    dir [ *word* ] [ short ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Displays information about the files in nonvolatile storage, including name, size, date created, and whether they are in use. There is no **no** version.



.....

**NOTE:** When high availability is enabled on the router, it is possible that files or file attributes may appear to be unsynchronized when they are not. When enabled, high availability mirrors configuration changes instantly from the active SRP module to the standby SRP module. However, although these changes are reflected immediately in memory, NVS on the standby SRP module is updated at 5-minute intervals.

.....

- Options**
- *word*—Path to a specific directory, or a filename; an asterisk (\*) in any position in a filename substitutes for zero or more characters; you cannot use a wildcard in a path
  - *short*—Limits display to file name and creation date

**Mode**    Privileged Exec, User Exec

## disable

**Syntax** To return to User Exec mode:

`disable [ level ]`

For DVMRP, RIP:

`[ no ] disable`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** When used from Privileged Exec mode, exits Privileged Exec mode and returns to User Exec mode.

When used from Router Configuration or Interface Configuration mode in the context of a DVMRP configuration, disables DVMRP on the virtual router or interface. The **no** version reenables DVMRP on the virtual router or interface.

When used from Router Configuration mode in the context of a RIP configuration, disables RIP on the virtual router. The **no** version enables RIP processing on the virtual router.

- Options**
- *level*—One of the following privilege levels; default value is 1
    - 0—Allows the user to execute the **help**, **enable**, **disable**, and **exit** commands
    - 1—Allows the user to execute commands in User Exec mode plus commands at level 0
    - 5—Allows the user to execute Privileged Exec show commands plus the commands at levels 1 and 0
    - 10—Allows the user to execute all commands except support commands, which may be provided by Juniper Networks Customer Service
    - 15—Allows the user to execute support commands

**Mode** Address Family Configuration (RIP), Interface Configuration (DVMRP only), Privileged Exec, Router Configuration (DVMRP or RIP)

## disable-autosync

---

**Syntax** [ no ] disable-autosync

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Halts automatic synchronization between the primary and standby SRP modules. When high availability is enabled (that is, the high availability state is initializing, active, or pending) this command affects only changes to nonconfiguration files. With high availability enabled, configuration changes are always mirrored to the standby SRP module. The **no** version restores the default situation, in which automatic synchronization runs as a background process every 5 minutes.

**Mode** Global Configuration



## disable-dynamic-redistribute

---

**Syntax** [ no ] disable-dynamic-redistribute

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Halts the dynamic redistribution of routes that are initiated by changes to a route map. Supported by DVMRP, BGP, IS-IS, OSPF, and RIP. The **no** version reenables dynamic redistribution of routes.

**Mode** Address Family Configuration, Router Configuration

## disable-incremental-external-spf

---

**Syntax** [ no ] disable-incremental-external-spf

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables incremental external SPF on the router; results in a full SPF when an event occurs to trigger an external SPF. The **no** version reenables incremental external SPF.

**Mode** Router Configuration

## disable proxy lcp

---

**Syntax** [ no ] disable proxy lcp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables the proxy LCP parameter for the remote host. The **no** version enables the proxy LCP parameter for the remote host.

**Mode** L2TP Destination Profile Host Configuration

## disable-switch-on-error

---

**Syntax** [ no ] disable-switch-on-error

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents the redundant SRP module from taking over if the primary SRP module experiences a software failure or if you push the reset button on the primary SRP module. Issue the **sync** command immediately before you issue this command. The **no** version restores the default situation, in which the redundant SRP module takes over if the primary SRP module experiences a failure.

**Mode** Global Configuration

## disconnect-cause

---

**Syntax** [ no ] disconnect-cause

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables an E Series LNS to generate, for the L2TP session to which the L2TP host profile applies, a PPP Disconnect Cause Code attribute value pair (AVP) and include it in all L2TP Call-Disconnect-Notify (CDN) messages that it sends to an LAC. This action provides a mechanism for the LAC to obtain information about the cause of a session disconnection. The **no** version disables generation of the PPP Disconnect Cause Code AVP, which is the default setting.

**Mode** L2TP Destination Profile Host Configuration

## disconnect ssh

---

**Syntax**    `disconnect ssh { vty vtyle | sessionId }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Terminates an active SSH session. Use the **show ip ssh** command to determine the session identifier for the session to terminate. There is no **no** version.



.....  
**NOTE:** You can also use the **clear line vty terminal** command to terminate SSH sessions. In that case, use the **show users** command to determine the virtual terminal number to specify with the **clear line vty terminal** command.  
.....

- Options**
- *vtyle*—Virtual terminal identifier for VTY where the SSH session resides; use the **show users** command to determine the identifier
  - *sessionId*—Integer in the range 0–4294967295 that identifies the session to be terminated

**Mode**    Privileged Exec

## discovery-mode

---

**Syntax** [ no ] discovery-mode

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Enables ANCP discovery mode. This mode allows RADIUS software to obtain loop parameter information from a connected access node. If discovery mode is disabled, it does not accept topology discovery messages and stops advertising topology discovery capability. It does not affect any other neighbors. The **no** version disables ANCP discovery mode.

**Mode** L2C Neighbor Configuration

## distance

---

**Syntax** The options available vary depending on your routing protocol context; that is, on whether you are configuring OSPF or RIP.

For OSPF:

```
[ no ] distance { ospfWeight | ospf { external distExt | inter-area disInter | intra-area disIntra } [ external distExt | inter-area distInter | intra-area distIntra ]* }
```

For RIP:

```
[ no ] distance ripWeight
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an administrative distance for RIP or OSPF routes. A distance of 255 prevents the route from being installed in the routing table. The **no** version either negates a command or restores the command's defaults.

- Options**
- **distance**—Weight applied to OSPF routes
  - **ospfWeight**—Value assigned to OSPF routes that are added to the IP routing table; a number in the range 1–255
  - **ospf**—OSPF routes
  - **distExt**—Distance for external type 5 and type 7 routes; a number in the range 1–255
  - **disInter**—Distance for interarea routes; a number in the range 1–255
  - **disIntra**—Distance for intra-area routes; a number in the range 1–255
  - **\***—Indicates that one or more parameters can be repeated multiple times in a list in the command line
  - **ripWeight**—Administrative distance assigned to RIP routes added to the IP routing table in the range 0–255; default value is 120

**Mode** Address Family Configuration (RIP), Router Configuration (OSPF or RIP)



## distance bgp

---

**Syntax**    `distance bgp externalDistance internalDistance localDistance`  
`no distance bgp [ externalDistance [ internalDistance [ localDistance ] ] ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the administrative distances for BGP routes. A distance of 255 prevents the route from being installed in the routing table. The **no** version restores the default values.

- Options**
- *externalDistance*—Administrative distance for routes external to the AS in the range 1–255; default value is 20
  - *internalDistance*—Administrative distance for routes internal to the AS in the range 1–255; default value is 200
  - *localDistance*—Administrative distance for local (redistributed) routes in the range 1–255; default value is 200

**Mode**    Address Family Configuration, Router Configuration

## distance ip

---

**Syntax** [ no ] distance *weight* ip

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the administrative distance for IS-IS routes that are inserted into the IP routing table. A distance of 255 prevents the route from being installed in the routing table. The **no** version restores the default value, 115.

**Options**

- *weight*—Administrative distance assigned to IS-IS routes added to the IP routing table in the range 1–255

**Mode** Router Configuration

## distribute-domain-wide

---

**Syntax** [ no ] distribute-domain-wide

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Increases the granularity of routing information within an IS-IS domain by allowing routes to be distributed from level 2 to level 1. This results in more accurate routing between level 1 areas. The **no** version disables the command.

**Mode** Router Configuration

## distribute-list

---

**Syntax** In Router Configuration mode:

```
[ no ] distribute-list accessListName { in | out } [ interfaceType interfaceSpecifier ]
```

In Remote Neighbor Configuration mode:

```
[ no ] distribute-list accessListName { in | out }
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the distribute list, an access list applied to incoming or outgoing RIP route updates. In Remote Neighbor Configuration mode, applies only to a RIP remote-neighbor interface. The **no** version removes the distribute list. An IP access list acts as a filter; refer to the **access-list** command for details.

- Options**
- *accessListName*—Name of the access list; string of up to 32 alphanumeric characters
  - in—Applies the access list to incoming route updates
  - out—Applies the access list to outgoing route updates
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Address Family Configuration, Remote Neighbor Configuration, Router Configuration

---

## dns-domain-search

---

**Syntax** [ no ] dns-domain-search *domainName*

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Specifies a list of domain names in the IPv6 local address pool to be returned to clients in DHCPv6 responses as part of the Domain Search List option. The **no** version removes the configured domain name.



.....  
**NOTE:** You can configure one domain name per line. Enter the command on separate lines to configure additional domain names.  
.....

**Options**

- *domainName*—Domain name that the DHCPv6 client uses when it resolves hostnames with the DNS server. You can specify a maximum of four DNS domains for the search list of an IPv6 local pool; maximum of 32 characters

**Mode** IPv6 Local Pool Configuration

## dns-server

---

**Syntax**    `dns-server ipAddressPrimary [ ipAddressSecondary ]`

`no dns-server`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a DNS server to an address pool. The **no** version removes the association between the address pool and the DNS server.

- Options**
- *ipAddressPrimary*—IP address of preferred DNS server
  - *ipAddressSecondary*—IP address of secondary DNS server

**Mode**    DHCP Local Pool Configuration

## dns-server (for IPv6)

---

**Syntax**    `dns-server ipv6AddressPrimary [ ipv6AddressSecondary ]`  
`no dns-server`

**Release Information**    Command introduced in JunosE Release 10.1.0.

**Description**    Configures the primary and secondary IPv6 DNS server addresses in the IPv6 local address pool. The DNS server addresses are returned to the client in DHCPv6 responses as part of the DNS Recursive Name Server option. The **no** version removes the configured DNS server addresses.

**Options**

- *ipv6AddressPrimary*—IPv6 address of the primary DNS server.
- *ipv6AddressSecondary*—IPv6 address of the secondary DNS server.

**Mode**    IPv6 Local Pool Configuration

## do

---

**Syntax**    *do execCommand*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Allows you to issue an Exec mode command from any configuration command mode. This command functions the same as the **run** command. There is no **no** version.

**Options**    • *execCommand*—CLI command that you can issue from User Exec or Privileged Exec mode

**Mode**    All configuration command modes



## domain

---

**Syntax**    `domain domainName`

`no domain`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the domain to an automatically generated username in an IP service profile.  
The **no** version removes the domain.

**Options**    • *domainName* —Name of the domain; maximum of 32 characters

**Mode**    IP Service Profile Configuration

## domain-authentication

---

**Syntax** [ no ] domain-authentication { csnp | psnp }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables or disables simple text authentication or HMAC MD5 authentication of IS-IS level 2 CSNP packets or PSNP packets. The **no** version restores the default behavior, in which authentication of IS-IS level 2 CSNPs and PSNPs is disabled.

- Options**
- csnp—Enables authentication of IS-IS level 2 complete sequence number PDUs (CSNPs)
  - psnp—Enables authentication of IS-IS level 2 partial sequence number PDUs (PSNPs)

**Mode** Router Configuration

---

## domain-authentication-key

---

**Syntax**    domain-authentication-key [ 0 | 8 ] *authKey*  
              no domain-authentication-key

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a password for authentication of IS-IS level 2 LSPs, CSNPs, and PSNPs. The **no** version deletes the password.



.....  
**NOTE:** Issuing this command enables simple authentication of level 2 LSPs only. To enable authentication of level 2 CSNPs or PSNPs, use the **domain-authentication** command.  
.....

- Options**
- 0—indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authKey*—password; string of up to 8 characters

**Mode**    Router Configuration

## domain-id

---

**Syntax**    `domain-id domainIdAddress | domainId`  
`no domain-id`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the OSPF domain ID for an OSPF VRF on a PE. The **no** version restores the default value.

- Options**
- *domainIdAddress*—OSPF domain ID in IP address format; default value is the IP address of the OSPF router configured in the VRF
  - *domainId*—OSPF domain ID as an integer value in the range 0–4294967295; default value is 0

When the *domainId* is zero, MP-BGP does not attach an OSPF domain identifier attribute when it converts an OSPF route to an MP-BGP route to cross the BGP/MPLS VPN.

**Mode**    Router Configuration

## domain-message-digest-key

**Syntax** domain-message-digest-key *keyId* hmac-md5 [ 0 | 8 ] *key*  
 [ start-accept *startAcceptTime* [ { *startAcceptMonth* *startAcceptDay* | *startAcceptDay* *startAcceptMonth* } *startAcceptYear* ] ]  
 [ start-generate *startGenTime* [ { *startGenMonth* *startGenDay* | *startGenDay* *startGenMonth* } *startGenYear* ] ]  
 [ stop-accept { never | *stopAcceptTime* [ { *stopAcceptMonth* *stopAcceptDay* | *stopAcceptDay* *stopAcceptMonth* } *stopAcceptYear* ] } ]  
 [ stop-generate { never | *stopGenTime* [ { *stopGenMonth* *stopGenDay* | *stopGenDay* *stopGenMonth* } *stopGenYear* ] } ]  
 no domain-message-digest-key *keyId*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an HMAC MD5 key that the router uses to create a secure, encrypted message digest of each IS-IS level 2 packet (LSPs, CSNPs, and PSNPs). The digest is inserted into the packet from which it is created. Using this algorithm for domain routers protects against unauthorized routers injecting false routing information into your network. You can specify when the router will start (default is the current time) and stop (default is never) accepting packets that include a digest made with this key. You can specify when the router will start (default is the current time plus 2 minutes) and stop (default is never) generating packets that include a digest made with this key. The **no** version deletes the key specified by the *keyId*.



**NOTE:** Issuing this command enables MD5 authentication of level 2 LSPs only. To enable authentication of level 2 CSNPs or PSNPs, use the **domain-authentication** command.

- Options**
- *keyId*—Integer from 1 to 255 that is a unique identifier for the secret key, sent with the message digest in the packet.
  - 0—Indicates the *key* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *key* is entered in encrypted form (ciphertext)
  - *key*—String of up to 20 alphanumeric characters; secret key used by the HMAC MD5 algorithm to generate the message digest.
  - *startAcceptTime*, *startAcceptMonth*, *startAcceptDay*, *startAcceptYear* – time, month, day, year that the router will start accepting packets created with this password. Use military time format *HH : MM [ : SS ]*.
  - *startGenTime*, *startGenMonth*, *startGenDay*, *startGenYear*—Time, month, day, year that the router will start inserting this password into packets. Use military time format *HH : MM [ : SS ]*.

- *never*—Specifies that the router never stops accepting or generating packets; overrides previously specified stop times.
- *stopAcceptTime, stopAcceptMonth, stopAcceptDay, stopAcceptYear*—Time, month, day, year that the router will stop accepting packets created with this password. Use military time format *HH : MM[ : SS ]*.
- *stopGenTime, stopGenMonth, stopGenDay, stopGenYear*—Time, month, day, year that the router will stop inserting this password into packets. Use military time format *HH : MM[ : SS ]*.

**Mode** Router Configuration

---

## domain-name

---

**Syntax** From DHCP Local Pool Configuration mode:

domain-name *domainName*

no domain-name

From IPSec Identity Configuration mode:

[ no ] domain-name *domainName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** From DHCP Local Pool Configuration mode, specifies a domain name that can be returned to the subscriber of an address pool if requested. The **no** version removes the association between the address pool and the domain name.

From IPSec Identity mode, specifies the domain name that the router uses in IKE authentication messages and to generate certificate requests. The **no** version removes the domain name.

**Options**

- *domainName*—Name of the domain
- *domainName*—Name used in certificate requests and in IKE authentication messages; up to 60 characters

**Mode** DHCP Local Pool Configuration, IPSec Identity Configuration

## domain-suffix

---

**Syntax**    domain-suffix *domainSuffix*  
              no domain-suffix

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Appends a domain suffix to user-provided usernames on this profile. The **no** version restores the default value, no domain suffix, and usernames are passed transparently to AAA.

**Options**    • *domainSuffix*—Domain suffix that you want to append to user-provided usernames.

**Mode**    IPSec Tunnel Profile Configuration



## domain-tag

---

**Syntax**    domain-tag *routeTag*  
              no domain-tag

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the VPN route tag for an OSPF VRF on a PE to prevent routing loops back into the VPN. The **no** version restores the default value.

**Options**    • *routeTag*—Number identifying the VPN route tag in the range 0–4294967295  
              The default value is a 32-bit number based on the AS number of the BGP/MPLS VPN backbone, with the first 16 bits set to 1110 0000 0000 0000, followed by the 16 bits representing the AS number.

**Mode**    Router Configuration

## dont-install-routes

---

**Syntax** [ no ] dont-install-routes

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents OSPF routes that point directly to the OSPF remote neighbor from being installed in the IP routing table of the VR or VRF in which OSPF is running. The **no** version restores the default behavior, which installs the routes in the IP routing table.

**Mode** Remote Neighbor Configuration

---

## dos-protection-group

---

**Syntax** [ no ] dos-protection-group *groupName*

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates a denial of service (DoS) protection group and enters DoS Protection Group Configuration mode. The **no** version removes the DoS protection group.



.....  
**NOTE:** A group named default always exists.  
.....

**Options**

- *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode** Global Configuration

## drop-profile

---

**Syntax** [ no ] drop-profile *dropProfileName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a drop profile. The **no** version removes the drop profile.

**Options**

- *dropProfileName*—Name for the drop profile

**Mode** Global Configuration

**Related Documentation**

- Configuring RED
- Configuring WRED

## ds3-scramble

---

**Syntax** [ no ] ds3-scramble

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables scrambling of the ATM cell payload on a T3 interface. DS3 scrambling assists clock recovery on the receiving end of the interface. The **no** version disables cell scrambling.

**Mode** Controller Configuration

## dsr-detect

---

**Syntax** [ no ] dsr-detect

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Requires that a DSR signal be detected on the line for a user to log into the console. DSR is carried on pin 6 of the SRP module's RS-232 (DB-9) connector. The DSR input must be connected to the DSR output of a modem or the DTR output of another DTE device, such as a terminal server, that supports this signal. If a session is in progress and the DSR signal is lost, the user is logged out automatically. The **no** version restores the default of no DSR required.

**Mode** Privileged Exec

## dsu bandwidth

---

**Syntax**    dsu bandwidth *bandwidthValue*  
              no dsu bandwidth

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the speed for the fractional T3 lines. The **no** version clears the bandwidth. If you issue this command, be sure to issue the **dsu mode** and **scramble** commands. Similarly, if you issue the **no** version, be sure to issue the **no** versions of the **dsu mode** and **scramble** commands; otherwise, the interface may drop packets unexpectedly.

**Options**    • *bandwidthValue*—Value of the fractional bandwidth in the range 22–44210 Kbps. The router offers a set of speeds in increments that depend on the DSU mode you specify. The actual speed of the fractional T3 lines will be the value closest to the fractional bandwidth you specify.

**Mode**    Controller Configuration

## dsu mode

---

**Syntax**    dsu mode { 0 | 2 }

no dsu mode

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the DSU mode for the lines. The **no** version clears the dsu mode. If you issue this command, be sure to issue the **dsu bandwidth** and scramble commands. Similarly, if you issue the **no** version, be sure to issue the **no** versions of the **dsu bandwidth** and scramble commands; otherwise, the interface may drop packets unexpectedly.

- Options**
- 0—Sets digital Link mode
  - 2—Sets Larscom mode

**Mode**    Controller Configuration



---

## duplex

---

**Syntax**    `duplex duplexMode`

`no duplex`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the duplex mode for an Ethernet interface. This command works with the **speed** command; if you set or accept the automatically negotiate setting for either duplex mode or speed, the router negotiates both parameters with the remote device. The **no** version specifies the default value, automatically negotiate or full duplex (FE-8 SFP I/O module only). This command is not available for the Ethernet interface on the SRP module.

- Options**    • *duplexMode*—One of the following duplex options
- *automatically negotiate*—Specifies that the router negotiates duplex mode with the remote device; not valid for the FE-8 SFP I/O module
  - *full*—Specifies that the router uses full duplex on a Fast Ethernet or Gigabit Ethernet interface
  - *half*—Specifies that the router uses half duplex on a Fast Ethernet interface; this value is not valid for Gigabit Ethernet interfaces

**Mode**    Interface Configuration

## dvmrp destination profile

---

**Syntax**    `dvmrp destination profile profileName { [ any-virtual-router ] |  
[ virtual-router virtualRouterName ] }`

`no dvmrp destination profile profileName`

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures a destination profile for dynamic DVMRP tunnels and enters IP Tunnel Destination Profile Configuration mode. There is no **no** version.

- Options**
- *profileName*—Name of the destination profile
  - *any-virtual-router*—Specifies a default destination profile for all virtual routers; only one default destination profile can be defined in the system
  - *virtualRouterName*—Name of the transport virtual router

**Mode**    Global Configuration

## CHAPTER 6

# E Commands

## e3-scramble

---

**Syntax** [ no ] e3-scramble

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables scrambling of the ATM cell payload on an E3 interface. E3 scrambling assists clock recovery on the receiving end of the interface. The **no** version disables scrambling.

**Mode** Controller Configuration

## enable

**Syntax** To access Privileged Exec mode:

```
enable [ level ]
```

To enable event or trigger configuration:

```
[ no ] enable
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** From User Exec mode, enters Privileged Exec mode at the specified privilege level. There is no **no** version for this use.

From SNMP Event Configuration or SNMP Trigger Configuration modes, enables the configuration for the event or trigger, respectively. The **no** version disables the event or trigger.

- Options**
- *level*—level at which you want to access the Privilege Exec mode; default value is 10; commands generally fall into one of the following security/privilege levels:
    - 0—allows the user to execute the **help**, **enable**, **disable**, and **exit** commands
    - 1—Allows the user to execute commands in User Exec mode plus commands at level 0
    - 5—Allows the user to execute Privileged Exec **show** commands plus the commands at levels 1 and 0
    - 10—Allows the user to execute all commands except support commands, which may be provided by Juniper Networks Customer Service, or the ability to assign privileges to commands
    - 15—Allows the user to execute support commands and assign privileges to commands

**Mode** SNMP Event Configuration, SNMP Trigger Configuration, User Exec

## enable-frag-stats

---

**Syntax** [ no ] enable-frag-stats

**Release Information** Command introduced in JunosE Release 12.3.0.

**Description** Enables collection and preservation of policy statistics for traffic on tunnel interfaces to which output policies are applied as a measure of the number of fragments. By default, output policy statistics for tunnel interfaces are maintained as a measure of the number of packets. The **no** version restores the default behavior.

**Mode** Global Configuration

**Related Documentation**

- [Statistics Collection for Output Policies on Tunnel Interfaces Overview](#)
- [Configuring Statistics Collection for Output Policies on Tunnel Interfaces](#)
- [Verifying Statistics Collection for Output Policies on Tunnel Interfaces](#)
- [show enable-frag-stats](#)

## enabled

---

**Syntax** [ no ] enabled

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Enables the aggregation cache to start accumulating information from the flow cache.  
The **no** version stops the information flow from the flow cache.

**Mode** Flow Cache Configuration

## enable ipsec-transport

---

**Syntax** [ no ] enable ipsec-transport

**Release Information** Command introduced before JunosE Release 7.1.0.  
IP Tunnel Destination Profile Configuration mode added in JunosE Release 8.2.0.

**Description** In IP Tunnel Destination Profile Configuration mode, specifies that the router accepts only dynamic IP tunnels protected by an IPSec transport connection. The **no** version disables IPSec transport mode.

In L2TP Destination Profile Host Configuration mode, specifies that the router accepts only L2TP tunnels protected by an IPSec transport connection. The **no** version disables IPSec transport mode.

**Mode** IP Tunnel Destination Profile Configuration, L2TP Destination Profile Host Configuration



## enable password

**Syntax**    `enable password [ level securityLevel ] [ passwordType ] passwordText`  
               `no enable password [ level securityLevel ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a password to control access to certain types of commands. The first time you define a password, you must enter it in plain text. To view its encrypted form, use the **show config** display. To redefine the password at a later date, you can enter the password in its encrypted form. The **no** version removes the password requirement.



**NOTE:** On the E Series router, all passwords are stored as encrypted passwords.

- Options**
- *securityLevel*—Security level for which you want to set the password; default value is 5; commands generally fall into one of the following security/privilege levels:
    - 0—Allows the user to execute the **help**, **enable**, **disable**, and **exit** commands
    - 1—Allows the user to execute commands in User Exec mode plus commands at level 0
    - 5—Allows the user to execute Privileged Exec show commands plus the commands at levels 1 and 0; this is the default level
    - 10—Allows the user to execute all commands except support commands, which may be provided by Juniper Networks Customer Service
    - 15—Allows the user to execute privilege setting and support commands
  - *passwordType*:
    - 0—Specifies that an unencrypted password follows; this is the default
    - 7—Specifies that an encrypted password follows
  - *passwordText*—Password, either encrypted or unencrypted, depending on the password type

**Mode**    Global Configuration

## enable proxy authenticate

---

**Syntax** [ no ] enable proxy authenticate

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures proxy authenticate for a remote host. The **no** version removes proxy authenticate configuration from the remote host.

**Mode** L2TP Destination Profile Host Configuration

## enable secret

**Syntax**    `enable secret [ level securityLevel ] [ secretType ] secretText`  
               `no enable secret [ securityLevel ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a secret to control access to certain types of commands. The first time you define a secret, you must enter it in plain text. To view its encrypted form, use the **show config** display. To redefine the secret at a later date, you can enter the secret in its encrypted form. The **no** version removes the secret requirement.



**NOTE:** On the E Series router, all secrets are stored as encrypted secrets.

- Options**
- *securityLevel*—Security level for which you want to set the secret; default value is 5
    - 0—Allows the user to execute the **help**, **enable**, **disable**, and **exit** commands
    - 1—Allows the user to execute commands in User Exec mode plus commands at level 0
    - 5—Allows the user to execute Privileged Exec **show** commands plus the commands at levels 1 and 0; this is the default level
    - 10—Allows the user to execute all commands except support commands, which may be provided by Juniper Networks Customer Service
    - 15—Allows the user to execute support commands
  - *secretType*—One of the following:
    - 0—Indicates that the secret is unencrypted; this is the default
    - 7—Indicates that the secret is encrypted
  - *secretText*—Secret, either encrypted or unencrypted, depending on the secret type

**Mode**    Global Configuration

## encapsulation

---

**Syntax**    encapsulation *encapsulationType*

no encapsulation

**Release Information**    Command introduced in JunosE Release 7.1.0.  
ATM VC Class Configuration mode added in JunosE Release 7.3.0.

**Description**    In ATM VC Configuration mode, configures the encapsulation method on an ATM PVC. The encapsulation method represents the format of the data units that traverse the PVC. The **encapsulation** command is valid only for data PVCs; you cannot use this command for control (ILMI or signaling) PVCs. The **no** version restores the default encapsulation method, **aal5snap**.

In ATM VC Class Configuration mode, configures the encapsulation method as part of a VC class definition that you assign to an ATM data PVC. The **no** version restores the default encapsulation method, **aal5snap**, in the VC class.

- Options**
- *encapsulationType*—One of the following encapsulation methods for data PVCs:
    - aal0—Causes the router to receive raw ATM cells on this PVC and forward the cells without performing AAL5 packet reassembly
    - aal5all—Configures ATM over MPLS passthrough connections; the router passes through all ATM AAL5 traffic without interpreting it
    - aal5autoconfig—Enables autodetection of the 1483 encapsulation (LLC/SNAP or VC multiplexed)
    - aal5mux ip—Configures a VC-based multiplexed circuit used for IP only
    - aal5snap—Configures an LLC encapsulated circuit; an LLC/SNAP header precedes the protocol datagram

**Mode**    ATM VC Configuration, ATM VC Class Configuration

## encapsulation bridge1483

---

**Syntax**    encapsulation bridge1483 [ mac-address *macAddress* ]  
              no encapsulation bridge1483

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures bridged Ethernet as the encapsulation method on an interface and optionally assigns a MAC address to the interface. The **no** version removes bridged Ethernet as the encapsulation method on the interface.

**Options**    • *macAddress*—User-configured MAC address for the interface. The MAC address format is a dotted triple of four-digit hexadecimal numbers; for example, 0090.1a40.4c7c. Multicast MAC address cannot be configured on bridged Ethernet interfaces.

**Mode**    Subinterface Configuration

## encapsulation frame-relay ietf

---

**Syntax**    encapsulation frame-relay ietf  
              no encapsulation frame-relay

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables Frame Relay encapsulation. The **no** version removes Frame Relay configuration from an interface.

**Mode**    Interface Configuration

**Related Documentation**

- Configuring Frame Relay Layer 2 Services

## encapsulation hdlc

---

**Syntax** [ no ] encapsulation hdlc

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables Cisco HDLC encapsulation. The **no** version disables Cisco HDLC on an interface.

**Mode** Interface Configuration, Subinterface Configuration

## encapsulation mlframe-relay ietf

---

**Syntax**    encapsulation mlframe-relay ietf  
              no encapsulation mlframe-relay

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables Multilink Frame Relay encapsulation. The **no** version removes Multilink Frame Relay configuration from an interface.

**Mode**    Interface Configuration



## encapsulation mlppp

---

**Syntax** [ no ] encapsulation mlppp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures MLPPP as the encapsulation method on an individual interface. Creates an MLPPP link interface, which can be configured as a member of an MLPPP bundle. The **no** version disables MLPPP on an interface.

**Mode** Interface Configuration, Subinterface Configuration

## encapsulation ppp

---

**Syntax** [ no ] encapsulation ppp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures PPP as the encapsulation method for the interface. The **no** version disables PPP on an interface.

**Mode** Interface Configuration, Subinterface Configuration

## encapsulation pppoe

---

**Syntax** [ no ] encapsulation pppoe

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures PPPoE as the encapsulation method for the interface. The **no** version removes PPPoE encapsulation from the interface.

**Mode** Interface Configuration, Subinterface Configuration

## encapsulation vlan

---

**Syntax** [ no ] encapsulation vlan

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures VLAN as the encapsulation method for the interface. The **no** version removes VLAN encapsulation from the interface.

**Mode** Interface Configuration, Subinterface Configuration

**Related Documentation**

- [Configuring Ethernet/VLAN Layer 2 Services](#)
- [Configuring S-VLAN Tunnels for Layer 2 Services](#)
- [Configuring Local Cross-Connects Between Ethernet/VLAN Interfaces](#)

## encryption

---

**Syntax**    encryption { des | 3des }  
              no encryption

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the encryption algorithm to use in the IKE policy. The **no** version restores the default, 3DES.

**Options**    • des—Specifies 56-bit DES-CBC as the encryption algorithm  
              • 3des—Specifies 168-bit 3DES-CBC as the encryption algorithm

**Mode**    IKE Policy Configuration

## end

---

**Syntax**    end

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Exits Global Configuration mode or any of the Configuration submodes and returns to the User Exec mode. There is no **no** version.

**Mode**    Global Configuration

## enrollment retry-limit

---

**Syntax**    enrollment retry-limit *minutes*  
              no enrollment retry-limit

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of minutes during which the router continues to send a certificate request to the CA. The **no** version restores the default.

**Options**    • *minutes*—Number of minutes, from 0 (infinite time period) to 480; default value is 60

**Mode**    IPSec CA Identity Configuration

## enrollment retry-period

---

**Syntax**    enrollment retry-period *minutes*  
              no enrollment retry-period

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of minutes that the router waits after receiving no response before resending a certificate request to the CA. The **no** version restores the default.

**Options**    • *minutes*—Number of minutes in the range 0–60 minutes; default value is 1

**Mode**    IPSec CA Identity Configuration



## enrollment url

---

**Syntax**    `enrollment url url`

`no enrollment url`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the URL of the simple certificate enrollment protocol (SCEP) server to which the router sends CA certificate requests (using the **ipsec ca authenticate** command) and public certificate requests (using the **ipsec ca enroll** command). The **no** version deletes the URL specification.

**Options**

- *url*—URL of SCEP server; in the format `http://server_ipaddress`; a maximum of 200 characters

**Mode**    IPSec CA Identity Configuration

## equipment loopback

---

**Syntax**    equipment { customer | network } loopback  
              no equipment

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables or disables the router's ability to be placed in loopback by a remote device connected on a CT3 or T3 interface. The **no** version disables the router's ability to be placed in loopback by the remote device.

- Options**
- customer—Enables the router to enter into loopback when it receives an appropriate signal from the remote interface
  - network—Disables the router's ability to enter into loopback when it receives an appropriate signal from the remote interface

**Mode**    Controller Configuration

---

## erase secrets

---

**Syntax**    `erase secrets seconds`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Removes all CLI passwords or secrets. Execute before pressing the NMI button on the SRP module. There is no **no** version.



.....

**NOTE:** If you enter the **service unattended password-recovery** command, the behavior of the **erase secrets** command changes. The **erase secrets** command will not take any parameters and will not be available through a vty session until you enter **no service unattended password-recovery**.

.....

**Options**    • *seconds*—Number of seconds in the range 1–60 to allow for the operation

**Mode**    User Exec

## ethernet description

---

**Syntax**    ethernet description *name*  
              no ethernet description

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Adds a text description to a non-SRP Fast Ethernet or Gigabit Ethernet interface. The **no** version removes the description from the interface.

**Options**    • *name*—String of up to 64 characters

**Mode**    Interface Configuration

## ethernet dos-protection-group

---

**Syntax**    ethernet dos-protection-group *groupName*  
              no ethernet dos-protection-group

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches an Ethernet denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## ethernet oam lfm

---

**Syntax** [ no ] ethernet oam lfm

**Release Information** Command introduced in JunosE Release 11.1.0.

**Description** Enables 802.3ah Ethernet Operation, Administration, and Maintenance (OAM) link-fault management on an interface. Enabling IEEE 802.3ah OAM functionality on a physical interface automatically triggers the discovery process. The default discovery mode of the OAM entity is active. The **no** version disables OAM link-fault management on the interface.



.....  
**NOTE:** If you enable OAM on an interface without specifying other parameters for the local OAM entity, such as the discovery mode for the OAM entity and the interval at which OAM protocol data units (PDUs) are sent to the remote peer, default values are assigned to all the attributes that are not manually configured.  
.....

**Mode** Interface Configuration

**Related Documentation**

- [ethernet oam lfm mode on page 602](#)
- Guidelines for Configuring 802.3ah OAM Link-Fault Management
- Configuring 802.3ah OAM Link-Fault Management

---

## ethernet oam lfm high-threshold

---

**Syntax** [ no ] ethernet oam lfm high-threshold { disable-interface | failover }

**Release Information** Command introduced in JunosE Release 11.1.0.

**Description** Configures a specific action to occur when a high threshold for an error is exceeded on an Ethernet OAM interface. The **no** version removes the high-threshold action from the interface of the local OAM client and causes no action to be performed when local errors occur on the interface.

- Options**
- **disable-interface**—Sets the OAM functionality to unconditionally attempt to influence the operational state of the interface to down. If the interface is a member link of a LAG bundle and at least one other viable link (redundant member or another active/up link) is present, OAM attempts to influence the operational state of the link to down. Otherwise, no action is taken
  - **failover**—On GE-2 and GE-HDE line modules with GE-2 SFP I/O modules with physical link redundancy, causes the link to transition from active to redundant

**Mode** Interface Configuration

- Related Documentation**
- OAM Link Monitoring Feature
  - Configuring 802.3ah OAM Link-Fault Management
  - Example: Configuring 802.3ah OAM Link-Fault Management and Enabling Remote Failure Monitoring on an Interface

## ethernet oam lfm link-monitor frame-seconds

**Syntax** ethernet oam lfm link-monitor frame-seconds { threshold { high { *highFrames* | none } | low *lowFrames* } | window *period* }

no ethernet oam lfm link-monitor frame-seconds [ threshold { high { *highFrames* | none } | low *lowFrames* } | window *period* ]

**Release Information** Command introduced in JunosE Release 11.1.0.

**Description** Configures a threshold value for sending frame error events that triggers an action or causes an Errored Frame Event TLV to be sent to the OAM entity, or a period of time in which error frames are counted. The **no** version disables monitoring of received frame error events.



**NOTE:** You can configure this command multiple times to configure combinations of high and low threshold values or a window period for frame error events.

- Options**
- **link-monitor**—Configures link monitoring parameters. Link monitoring operations start automatically when Ethernet OAM is enabled on an interface. When link monitoring operations are disabled, the interface does not actively send or receive Event Notification OAM PDUs
  - **frame-seconds**—Configures the threshold value or window for frame error events
  - **threshold**—Configures a period or a value at, above, or below which an action is triggered
  - **highFrames**—Integer in the range 1–65535 that is the high threshold in number of frames, which when exceeded causes an action to be triggered. The action that the local OAM entity performs when the high threshold value is exceeded depends on the value configured using the **ethernet oam lfm high-threshold** command. There is no default value. If you specify a high threshold option for error frames, you must also enter the number of frames, which when exceeded causes the configured action to be taken
  - **none**—Removes the high threshold value for error frames
  - **lowFrames**—Integer in the range 0–65535 that is the low threshold in number of frames; default value is 0 frames. When this value is exceeded, an Errored Frame Event TLV is sent to the peer. If you do not configure a low threshold for frame error events, the Errored Frame Event TLV is not sent to the peer
  - **period**—A window and period of time during which error frames are counted. Integer in the range 10–600 that represents a number of milliseconds in a multiple of 100; default value is 1000 milliseconds, which is denoted by specifying 10 units for the *period* variable in the CLI interface

**Mode** Interface Configuration



- Related Documentation**
- [ethernet oam lfm link-monitor symbol-period on page 600](#)
  - [ethernet oam lfm link-monitor frame-seconds-summary on page 598](#)
  - OAM Link Monitoring Feature
  - Configuring 802.3ah OAM Link-Fault Management
  - Example: Configuring 802.3ah OAM Link-Fault Management and Enabling Remote Failure Monitoring on an Interface

## ethernet oam lfm link-monitor frame-seconds-summary

**Syntax** ethernet oam lfm link-monitor frame-seconds-summary { threshold { high { *highSummary* | none } | low *lowSummary* } | window *period* }

no ethernet oam lfm link-monitor frame-seconds-summary [ threshold { high { *highSummary* | none } | low *lowSummary* } | window *period* ]

**Release Information** Command introduced in JunosE Release 11.1.0.

**Description** Configures a threshold value for frame period summary error events that triggers an action or causes an Errored Frame Seconds Summary Event TLV to be sent to the OAM entity, or a period of time in which frame period summary error events are counted. The **no** version disables monitoring of received frame period summary error events.



**NOTE:** You can configure this command multiple times to configure combinations of high and low threshold values or a window period for frame error events.

- Options**
- **link-monitor**—Configures link monitoring parameters. Link monitoring operations start automatically when Ethernet OAM is enabled on an interface. When link monitoring operations are disabled, the interface does not actively send or receive Event Notification OAM PDUs
  - **frame-seconds-summary**—Configures the threshold value or window for frame period summary error events
  - **threshold**—Configures a period or a value at, above, or below which an action is triggered
  - **highSummary**—Integer in the range 1–65535 that is the high threshold in number of error frame seconds, which when exceeded causes an action to be triggered. The action that the local OAM entity performs when the high threshold value is exceeded depends on the value configured using the **ethernet oam lfm high-threshold** command. There is no default value. If you specify a high threshold option for frame period summary error events, you must also enter the number of frames, which when exceeded causes the configured action to be taken
  - **none**—Removes the high threshold value for frame period summary error events
  - **lowSummary**—Integer in the range 0–65535 that is the low threshold in number of error frame seconds, which when exceeded causes an Errored Frame Seconds Summary Event TLV to be sent to the peer; default value is 0 frames. If you do not configure a low threshold for framed symbol errors, the Link Fault critical event PDU is not sent to the peer
  - **period**—A window and period of time during which framed period summary seconds are counted. Integer in the range 10–900 seconds that is the monitoring period for framed symbol errors; default value is 60 seconds

**Mode**    Interface Configuration

- Related Documentation**
- [ethernet oam lfm link-monitor symbol-period on page 600](#)
  - [ethernet oam lfm link-monitor frame-seconds on page 596](#)
  - OAM Link Monitoring Feature
  - Configuring 802.3ah OAM Link-Fault Management
  - Example: Configuring 802.3ah OAM Link-Fault Management and Enabling Remote Failure Monitoring on an Interface

## ethernet oam lfm link-monitor symbol-period

**Syntax** ethernet oam lfm link-monitor symbol-period { threshold { high { *highFrames* | none } | low *lowFrames* } | window *period* }

no ethernet oam lfm link-monitor symbol-period [ threshold { high { *highFrames* | none } | low *lowFrames* } | window *period* ]

**Release Information** Command introduced in JunosE Release 11.1.0.

**Description** Configures a threshold value for symbol error events that triggers an action or causes an Error Symbol Period TLV to be sent to the OAM entity, or a period of time in which symbol error events are counted. The **no** version disables monitoring of received symbol error events.



**NOTE:** You can configure this command multiple times to configure combinations of high and low threshold values or a window period for frame error events.

- Options**
- **link-monitor**—Configures link monitoring parameters. Link monitoring operations start automatically when Ethernet OAM is enabled on an interface. When link monitoring operations are disabled, the interface does not actively send or receive Event Notification OAM PDUs
  - **symbol-period**—Configures the threshold value or window for symbol error events
  - **threshold**—Configures a period or a value at, above, or below which an action is triggered
  - **highSymbols**—Integer in the range 1–65535 that is the high threshold in number of symbol error seconds, which when exceeded causes an action to be triggered. The action that the local OAM entity performs when the high threshold value is exceeded depends on the value configured using the **ethernet oam lfm high-threshold** command. There is no default value. If you specify a high threshold option for frame period summary error events, you must also enter the number of frames, which when exceeded causes the configured action to be taken
  - **none**—Removes the high threshold value for symbol error events
  - **lowSymbols**—Integer in the range 0–65535 that is the low threshold in number of symbol error seconds, which when exceeded causes an Error Symbol Period TLV to be sent to the peer; default value is 0 symbol error seconds. If you do not configure a low threshold for symbol error events, the Link Fault critical event PDU is not sent to the peer
  - **period**—A window and period of time during which symbol error events are counted. Integer in the range 1–60 seconds that is the monitoring period for symbol errors; there is no default value

**Mode** Interface Configuration

- Related Documentation**
- [ethernet oam lfm link-monitor frame-seconds on page 596](#)
  - OAM Link Monitoring Feature
  - Configuring 802.3ah OAM Link-Fault Management
  - Example: Configuring 802.3ah OAM Link-Fault Management and Enabling Remote Failure Monitoring on an Interface

## ethernet oam lfm mode

---

<b>Syntax</b>	[ no ] ethernet oam lfm mode { active   passive } [ pdu-lost-threshold <i>pduLostPackets</i> ]
<b>Release Information</b>	Command introduced in JunosE Release 11.1.0.
<b>Description</b>	Configures the discovery mode to be used for IEEE 802.3ah OAM link-fault management support on an interface as active or passive. Also, configures the number of OAM packet data units (PDUs) from the remote peer that an interface on the local client can miss before the link between the two entities is considered down. The default mode of the interface on the OAM client is active. The <b>no</b> version disables discovery, deactivating link-fault management functionality on the interface.
<b>Options</b>	<ul style="list-style-type: none"><li>• <b>mode</b>—Configures the OAM client mode for the discovery process</li><li>• <b>active</b>—Sets the discovery mode of the local OAM client as active. In active mode, the interface discovers and monitors the peer on the link if the peer also supports IEEE 802.3ah OAM functionality. This is the default discovery mode of the OAM client</li><li>• <b>passive</b>—Sets the discovery mode of the local OAM client as passive. In passive mode, an OAM entity does not initiate the discovery process. You cannot perform link-fault management if you configure both the local client and the remote peer for passive mode operation</li><li>• <b>pduLostPackets</b>—The window for which the local client waits to receive OAM packets from the remote peer before it generates a link fault event. Number of expected OAM packets from the remote peer that the local OAM client can miss before a link-fault event is triggered; a number in the range 3–10; default value is 5</li></ul>
<b>Mode</b>	Interface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• OAM Discovery Feature</li><li>• Guidelines for Configuring 802.3ah OAM Link-Fault Management</li><li>• Configuring 802.3ah OAM Link-Fault Management</li></ul>

---

## ethernet oam lfm pdu-lost-threshold

---

<b>Syntax</b>	[ no ] ethernet oam lfm pdu-lost-threshold <i>pduLostPackets</i>
<b>Release Information</b>	Command introduced in JunosE Release 11.1.0.
<b>Description</b>	Configures the number of OAM protocol data units (PDUs) that a local OAM client can fail to receive from a remote peer before a link-fault event is triggered. The <b>no</b> version removes the configured threshold for PDUs that can be missed from a remote peer before the generation of a link-fault event.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>pduLostPackets</i>—Number of expected OAM packets from the remote peer that the local OAM client can miss before a link-fault event is triggered; a number in the range 3–10; default value is 5</li></ul>
<b>Mode</b>	Interface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• OAM Discovery Feature</li><li>• Configuring 802.3ah OAM Link-Fault Management</li><li>• <a href="#">ethernet oam lfm mode on page 602</a></li></ul>

## ethernet oam lfm pdu-transmit-interval

---

**Syntax** [ no ] ethernet oam lfm pdu-transmit-interval *period* [ mode { active | passive } | pdu-lost-threshold *pduLostPackets* ]

**Release Information** Command introduced in JunosE Release 11.1.0.

**Description** Configures the minimum rate at which OAM protocol data units (PDUs) are transmitted in milliseconds. Also, specifies the discovery mode of the OAM client and the number of OAM packet data units (PDUs) from the remote peer that an interface on the local client can miss before the link between the two entities is considered down. The **no** version removes the frequency values configured on the interface for transmission of OAM PDUs to the remote peer. The **no** version with the **mode** keyword deactivates link-fault management on the interface.

- Options**
- *period*—Interval at which OAM PDUs are sent from the local OAM entity to the remote peer to maintain the OAM association in an active state. Number in the range 100–1000 milliseconds; default value is 1000 milliseconds
  - *mode*—Configures the OAM client mode for the discovery process
  - *active*—Sets the discovery mode of the local OAM client as active. In active mode, the interface discovers and monitors the peer on the link if the peer also supports IEEE 802.3ah OAM functionality. This is the default discovery mode of the OAM client
  - *passive*—Sets the discovery mode of the local OAM client as passive. In passive mode, an OAM entity does not initiate the discovery process. You cannot perform link-fault management if you configure both the local client and the remote peer for passive mode operation
  - *pduLostPackets*—The window for which the local client waits to receive OAM packets from the remote peer before it generates a link fault event. Number of expected OAM packets from the remote peer that the local OAM client can miss before a link-fault event is triggered; a number in the range 3–10; default value is 5

**Mode** Interface Configuration

- Related Documentation**
- OAM Discovery Feature
  - Configuring 802.3ah OAM Link-Fault Management
  - [ethernet oam lfm mode on page 602](#)



## ethernet oam lfm remote-failure

<b>Syntax</b>	[ no ] ethernet oam lfm remote-failure { critical-event   dying-gasp   link-fault } action { disable-interface   failover }
<b>Release Information</b>	Command introduced in JunosE Release 11.1.0.
<b>Description</b>	Configures the Ethernet OAM link-fault management functionality to detect failure conditions that occurred in the receive path of the link, and to influence the state of the link based on an Event Notification PDU received from the remote peer. Also, specifies the action to be taken by the system when the configured link-fault event occurs, such as disabling the interface or causing a failover to another member link of a LAG bundle. The <b>no</b> version disables detection of remote faults and causes no action to be taken when a link-fault event occurs.
<b>Options</b>	<ul style="list-style-type: none"> <li>remote-failure—Enables detection of faults that occur in the receive path of an OAM link</li> <li>critical-event—Enables detection of unspecified critical event conditions that occurred in the receive path of the link and influences the state of the link based on an Event Notification PDU received from the remote peer. This type of condition is vendor-specific</li> <li>dying-gasp—Enables detection of unrecoverable error conditions that occurred in the receive path of the link and influences the state of the link based on an Event Notification PDU received from the remote peer. This type of condition is vendor-specific</li> <li>link-fault—Enables detection of loss-of-signal conditions that occurred in the receive path of the link and influences the state of the link based on an Event Notification PDU received from the remote peer</li> <li>action—Sets the action to be performed on an interface when an OAM PDU is received from the remote peer by the local OAM entity to signal a fault condition in the receive path of the link</li> <li>disable-interface—Sets the OAM functionality to unconditionally attempt to influence the operational state of the interface to down</li> <li>failover—Causes a failover to another member interface in the LAG bundle when the high threshold for an error is exceeded that trigger the sending of link event TLVs. On GE-2 and GE-HDE line modules that are paired with GE-2 SFP I/O modules with physical link redundancy, causes the link to transition from active to redundant</li> </ul>
<b>Mode</b>	Interface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>OAM Remote Fault Detection Feature</li> <li>Configuring 802.3ah OAM Link-Fault Management</li> <li>Example: Configuring 802.3ah OAM Link-Fault Management and Enabling Remote Failure Monitoring on an Interface</li> </ul>

## ethernet oam lfm remote-loopback

---

<b>Syntax</b>	ethernet oam lfm remote-loopback { start   stop } <i>interfaceType interfaceSpecifier</i>
<b>Release Information</b>	Command introduced in JunosE Release 11.1.0.
<b>Description</b>	<p>Enables or disables remote loopback functionality on the remote OAM entity. Also causes the remote peer to commence or halt sending of all received frames from the local entity to the specified interface, except OAM PDUs, without any changes made to the frames. OAM PDUs continue to be processed. By default, the remote peer does not loop back the non-OAM PDUs that it receives from the local entity. There is no <b>no</b> version.</p> <p>This configuration setting is not preserved across a reboot.</p>
<b>Options</b>	<ul style="list-style-type: none"><li>• <b>start</b>—Commences the remote loopback operation on the remote OAM entity</li><li>• <b>stop</b>—Halts the remote loopback operation on the remote OAM entity; this is the default behavior</li><li>• <i>interfaceType</i>—One of the following interface types listed in <a href="#">“Interface Types and Specifiers” on page 5</a><ul style="list-style-type: none"><li>• fastEthernet</li><li>• gigabitEthernet</li><li>• tenGigabitEthernet</li></ul></li><li>• <i>interfaceSpecifier</i>—Particular interface; format varies according to interface type; see <a href="#">Interface Types and Specifiers on page 5</a></li></ul>
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">ethernet oam lfm remote-loopback supported on page 607</a></li><li>• OAM Remote and Local Loopback Feature</li><li>• Configuring 802.3ah OAM Link-Fault Management</li><li>• Example: Enabling Remote Loopback Support on the Local Interface</li></ul>

---

## ethernet oam lfm remote-loopback supported

---

<b>Syntax</b>	[ no ] ethernet oam lfm remote-loopback supported
<b>Release Information</b>	Command introduced in JunosE Release 11.1.0.
<b>Description</b>	Configures Ethernet OAM remote loopback functionality on an interface and causes the interface to receive and respond to remote loopback requests from peers. The <b>no</b> version disables the remote loopback behavior on the interface, which is the default behavior.
<b>Options</b>	<ul style="list-style-type: none"><li>• remote-loopback—Configures a local interface to be placed into remote loopback mode and enables the local interface to respond to remote loopback requests that it receives from a peer OAM entity</li><li>• supported—Enables the Ethernet OAM configuration on the interface to initiate remote loopback or respond to a remote loopback request it receives from a peer</li></ul>
<b>Mode</b>	Interface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">ethernet oam lfm remote-loopback on page 606</a></li><li>• OAM Remote and Local Loopback Feature</li><li>• Configuring 802.3ah OAM Link-Fault Management</li><li>• Example: Enabling Remote Loopback Support on the Local Interface</li></ul>

## event

---

**Syntax**    [ no ] event *eventOwner eventName*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates an event and launches the event configuration mode in the SNMP server event manager. The **no** version removes the event.

- Options**
- *eventOwner*—Owner associated with this event; string of up to 32 alphanumeric characters
  - *eventName*—Name associated with this event; string of up to 32 alphanumeric characters

**Mode**    SNMP Event Manager Configuration

## exceeded-action

<b>Syntax</b>	<p>For IP and IPv6 rate-limit profiles:</p> <pre>[ no ] exceeded-action { drop   transmit   mark <i>markVal</i> }</pre> <p>For L2TP rate-limit profiles:</p> <pre>[ no ] exceeded-action { drop   transmit }</pre> <p>For MPLS rate-limit profiles:</p> <pre>[ no ] exceeded-action { drop   transmit   mark-exp <i>expValue</i> }</pre> <p>For hierarchical rate-limit profiles:</p> <pre>[ no ] exceeded-action { drop   transmit [ conditional   final ] }</pre>
<b>Release Information</b>	<p>Command introduced before JunosE Release 7.1.0.</p> <p><b>conditional</b> and <b>final</b> keywords added in JunosE Release 7.2.0.</p>
<b>Description</b>	<p>Sets the action for packets not conforming to the committed rate and committed burst size, and not conforming to the peak rate and peak burst size. The <b>no</b> version restores the default, drop.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>• <b>drop</b>—Drops the packet</li> <li>• <b>transmit</b>—Transmits the packet; for hierarchical rate limits:             <ul style="list-style-type: none"> <li>• <b>conditional</b>—Packets must pass the next rate limit</li> <li>• <b>final</b>—Packets exit the hierarchy at rate limit</li> </ul> </li> <li>• <b>markVal</b>—Marks value in the range 0–255; mark actions are not supported on hierarchical rate limits</li> <li>• <b>expValue</b>—EXP bit value in the range 0–7</li> </ul>
<b>Mode</b>	Rate Limit Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Creating a Two-Rate Rate-Limit Profile</li> </ul>

## exceeded-drop-threshold

---

**Syntax**    `exceeded-drop-threshold exceededDropThreshold`  
              `no exceeded-drop-threshold`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the threshold above which exceeded-drop-events are logged. The **no** version removes the threshold.

**Options**    • *exceededDropThreshold*—Bits per second in the range 0–1073741824

**Mode**    Statistics Profile Configuration

**Related Documentation**    • [Configuring Event Statistics](#)

## exceeded-fraction

---

**Syntax**    `exceeded-fraction exceededFraction`  
              `no exceeded-fraction`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the percentage of the total queue length that can be occupied before dropping exceeded packets. The **no** version returns the exceeded fraction to its default setting.

**Options**    • *exceededFraction*—Percentage range 0–100; default value is 25

**Mode**    Queue Profile Configuration

**Related Documentation**    • Configuring Queue Profiles to Manage Buffers and Thresholds

## exceeded-length

---

**Syntax**    `exceeded-length minimumExceededLength [ maximumExceededLength ]`  
              `no exceeded-length`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets minimum and maximum constraints for the queue's exceeded lengths. The **no** version removes constraints on the queue's exceeded length.

**Options**

- *minimumExceededLength*—Range 0–1073741824
- *maximumExceededLength*—Range 0–1073741824

**Mode**    Queue Profile Configuration

**Related Documentation**

- [Configuring Queue Profiles to Manage Buffers and Thresholds](#)



## exceeded-threshold

---

<b>Syntax</b>	<p>exceeded-threshold { percent <i>MinThresholdPercent</i> <i>MaxThresholdPercent</i>   <i>MinThresholdBytes</i> <i>MaxThresholdBytes</i> } <i>MaxDropProbability</i></p> <p>no exceeded-threshold</p>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Specifies the exceeded queue thresholds and maximum drop probability. The <b>no</b> version removes exceeded threshold.
<b>Options</b>	<ul style="list-style-type: none"> <li>• percent—Specifies <i>exceeded</i> queue thresholds as percentages</li> <li>• <i>MinThresholdPercent</i>—Minimum queue threshold as a percentage of queue length</li> <li>• <i>MaxThresholdPercent</i>—Maximum queue threshold as a percentage of queue length</li> <li>• <i>MinThresholdBytes</i>—Minimum queue threshold in bytes</li> <li>• <i>MaxThresholdBytes</i>—Maximum queue threshold in bytes</li> <li>• <i>MaxDropProbability</i>—Maximum drop probability</li> </ul>
<b>Mode</b>	Drop Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Configuring RED</li> <li>• Configuring WRED</li> </ul>

## exception dump

---

**Syntax**    exception dump { except-srp | srp-only } { local | *ipAddress* [ *directoryName* ] }  
              no exception dump

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the location from and to which the router should transfer a core dump file. Core dumps are enabled and stored in local NVS by default. The **no** version disables the command.

**Options**

- except-srp—Generates core dump for all non-SRP modules
- srp-only—Generates core dump for only the SRP modules
- local—Nonvolatile storage memory
- *ipAddress*—IP address of the server to which the router will transfer the core dump file
- *directoryName*—Name of the directory on the server to which the router will transfer the core dump file

**Mode**    Global Configuration

## exception gateway

---

**Syntax**    exception gateway *ipAddress*  
              no exception gateway

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the gateway through which the router sends the core dump file to the remote FTP server. The **no** version returns the value to its default (null).

**Options**    • *ipAddress*—IP address of the gateway

**Mode**    Global Configuration

## exception http-redirect

---

**Syntax** [ no ] exception http-redirect

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Creates the exception rule within an IPv4 or IPv6 policy classifier group so the application can perform an application-dependent action on the content of the packet. HTTP redirect is the only application that is available as a destination of the exception rule. The **no** version removes the exception rule.

This command is not supported for the ES2 10G Uplink LM.

**Mode** Classifier Group Configuration

**Related Documentation**

- Assigning Values to the ATM CLP Bit
- Creating an Exception Rule within a Policy Classifier Group

## exception monitor

---

**Syntax** exception monitor *ipAddress* [ *directoryName* ]

no exception monitor

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the core dump monitor and specifies the location to which the router transfers core dump files. The **no** version disables the core dump monitor.

- Options**
- *ipAddress*—IP address of the server to which you want the router to transfer core dump files
  - *directoryName*—Name of the directory on the server to which you want the router to transfer core dump files

**Mode** Global Configuration

## exception monitor interval

---

**Syntax**    exception monitor interval *interval*  
              no exception monitor interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval at which you want the router to check NVS for core dump files. The **no** version disables the core dump monitor.

**Options**    • *interval*—Number of minutes between NVS checks; in the range 1–1440

**Mode**    Global Configuration

## exception protocol ftp

---

**Syntax**    exception protocol ftp [ [ *algorithmType* ] *userName* [ [ *algorithmType* ] *password* ] ]  
              no exception protocol

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the username and password for FTP access to a host where you transferred a core dump file. The **no** version restores the defaults.

- Options**
- *algorithmType*—Type of user name or password
    - 0—Indicates the *password* is unencrypted; the default
    - 8—Indicates the *password* is encrypted
  - *userName*—Username required to access the FTP server; the default username is anonymous
  - *password*—Password required to access the FTP server; default value is no password

**Mode**    Global Configuration

## exception source

---

**Syntax**    exception source *ipAddress ipAddressMask*

no exception source

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IP address and mask of the router interface over which you want to send the core dump file to the remote FTP server. The **no** version returns the value to its default (null).

- Options**
- *ipAddress*—IP address of the interface
  - *ipAddressMask*—Optionally add the IP address mask of the interface

**Mode**    Global Configuration



## excess-burst

---

**Syntax**    `excess-burst { size | millisecond milliseconds }`  
              `no excess-burst`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets amount of bandwidth allocated to accommodate a packet in progress when the rate is in excess of the burst. The **no** version restores the default value, 0.

**Options**

- *size*—Amount of bandwidth allocated; in the range 0–4294967295
- *milliseconds*—Milliseconds in the range 1–10000

**Mode**    Rate Limit Profile Configuration

**Related Documentation**

- Creating a Two-Rate Rate-Limit Profile

## exclude-ndraprefix

---

**Syntax** [ no ] exclude-ndraprefix *Ipv6Prefix* [ *endIpv6prefix* ]

**Release Information** Command introduced in JunosE Release 13.0.0.

**Description** Specifies the IPv6 prefix or range of prefixes to exclude from being allocated to the requesting router. You can exclude those prefixes that have been assigned to local interfaces from being delegated to the Neighbor Discovery router advertisement clients. The **no** version removes the IPv6 prefix or prefix range from the exclusion set and makes it available again for delegation to clients.



**NOTE:** If you attempt to exclude a prefix range that overlaps with another prefix range that has been already excluded from delegation to clients in the IPv6 local address pool, an error message is displayed and the configuration fails.

- Options**
- *Ipv6Prefix*—IPv6 prefix or the starting IPv6 prefix of the range of prefixes to be excluded from being delegated to the requesting router
  - *endIpv6Prefix*—Ending prefix of the range of IPv6 prefixes to be excluded from being delegated to the requesting router. If you specify this value, all prefixes from the starting IPv6 prefix up to this prefix are excluded from allocation.

**Mode** IPv6 NdRa Pool Configuration

**Related Documentation**

- Configuring IPv6 Neighbor Discovery Local Address Pools

---

## exclude-prefix

---

**Syntax** [ no ] exclude-prefix *IPv6Prefix* [ *endIPv6prefix* ]

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Specifies the IPv6 prefix or range of prefixes to exclude from being allocated to the requesting router. You can exclude those prefixes that have been assigned to local interfaces from being delegated to the DHCPv6 clients. The **no** version removes the IPv6 prefix or prefix range from the exclusion set and makes it available again for delegation to clients.



**NOTE:** If you attempt to exclude a prefix range that overlaps with another prefix range that has been already excluded from delegation to clients in the IPv6 local address pool, an error message is displayed and the configuration fails.

- Options**
- *IPv6Prefix*—IPv6 prefix or the starting IPv6 prefix of the range of prefixes to be excluded from being delegated to the requesting router.
  - *endIPv6Prefix*—Ending prefix of the range of IPv6 prefixes to be excluded from being delegated to the requesting router. If you specify this value, all prefixes from the starting IPv6 prefix up to this prefix are excluded from allocation.

**Mode** IPv6 Local Pool Configuration

## exclude-subsystem

---

**Syntax**    `exclude-subsystem subsystemName`  
              `no exclude-subsystem [ subsystemName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Excludes subsystem files from being copied when you copy a software release to the router. The **no** version removes the exclusion for a specified subsystem file or all subsystem files.

**Options**    • *subsystemName*—Name of the subsystem file to be excluded

**Mode**    Global Configuration

## exec-banner

---

**Syntax** [ no | default ] exec-banner

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls display of an exec banner (configured with the **banner** command) on a particular line after user authentication (if any) and before the first prompt of a CLI session. The **no** version disables the exec banner and the motd banner on the line. The **default** version restores the default setting, in which the banner is enabled on all lines.

**Mode** Line Configuration

## exec-timeout

---

**Syntax**    `exec-timeout minutes [ seconds ]`

`no exec-timeout`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time interval that the console or vty line waits for expected user input. The **no** version restores the default value, which is no time limit.

- Options**
- *minutes*—Number of minutes for the time limit; in the range from 0 to 35791
  - *seconds*—Number of seconds in addition to the minutes for the time limit; in the range from 0 to 2147483

**Mode**    Line Configuration

---

## existence-test

---

**Syntax**    `existence-test { event eventOwner eventName |  
                  startup { absent | present } | test-type { absent | changed | present } }`  
  
              `no existence-test [ event | startup | test-type ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines existence test values for the trigger that you are configuring, including binding an event to the existence-test trigger, specifying a startup condition, and defining an existence-test type. The **no** version deletes the existence-test values for this trigger or removes either the startup condition or event binding.

- Options**
- *eventOwner*—Name of event owner that partially specifies event to trigger the existence test; string of up to 32 alphanumeric characters
  - *eventName*—Name of event that partially specifies event to trigger the existence test; string of up to 32 alphanumeric characters
  - *startup*—Specifies startup existence condition that you predict the sample to follow; absent or present; you can specify both conditions in the same command
  - *test-type*—Specifies type of existence test to perform; absent, changed, or present; you can specify one, two, or all three conditions in the same command

**Mode**    SNMP Trigger Configuration

## exit

---

**Syntax**    exit

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Exits the current command mode. In User Exec and Privileged Exec modes, logs out of the CLI. There is no **no** version.

**Mode**    All modes



## exit-address-family

---

<b>Syntax</b>	exit-address-family
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Exits from Address Family Configuration mode and returns to Router Configuration mode. There is no <b>no</b> version.
<b>Mode</b>	Address Family Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• BGP Signaling for L2VPNs Overview</li><li>• BGP Signaling for VPLS Overview</li></ul>

## exit-remote-neighbor

---

**Syntax**    exit-remote-neighbor

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Exits from Remote Neighbor Configuration mode and returns to Router Configuration mode. There is no **no** version.

**Mode**    Remote Neighbor Configuration

## exp-mask

---

**Syntax** [ no ] exp-mask *maskValue*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the EXP mask to be applied with the mark values. The **no** version restores the default mask of 7.

**Options**

- *maskValue*—EXP mask value in the range 0–7

**Mode** Rate Limit Profile Configuration

**Related Documentation**

- Creating a Two-Rate Rate-Limit Profile

## export destination

---

**Syntax** [ no ] export destination { *hostName* | *ipAddress* } udp-port

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Configures an export destination for the aggregation cache. The **no** version removes the destination.

- Options**
- *hostName*—Name of the destination host
  - *ipAddress*—Address of IP interface
  - udp-port—Specifies UDP port as the destination

**Mode** Flow Cache Configuration

## export map

---

**Syntax**    export map [ ipv4 | ipv6 ] *routeMap* [ filter ]  
              no export map [ ipv4 | ipv6 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Associates a route map with a VRF to modify or filter routes exported by the VRF to the global BGP VPN RIB in the parent VR. Both IPv4 and IPv6 routes are exported unless you issue the appropriate keyword to restrict exportation. The **no** version restores the default behavior, which is to export all routes without applying a route map.

**Options**

- *ipv4*—Specifies that only IPv4 routes are exported to the global BGP VPN RIB
- *ipv6*—Specifies that only IPv6 routes are exported to the global BGP VPN RIB
- *routeMap*—Name of a route map; string of up to 32 alphanumeric characters
- *filter*—Prevents routes that do not match the route map from being exported; if absent, such routes are exported but their attributes are not modified by the route map

**Mode**    VRF Configuration

## export source

---

**Syntax** [ no ] export source interface *interface*

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Sets the source IP address for datagrams containing information from the cache. The **no** version removes the setting of the IP address.

**Options** • *interface*—Name of the interface

**Mode** Flow Cache Configuration

---

## extended-authentication

---

**Syntax**    `extended-authentication { none | pap | chap } [ re-authenticate ]`  
              `[ skip-peer-config ]`  
  
              `no extended-authentication`

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Specifies the extended user authentication protocol for use during the extended user authentication protocol exchange. The **no** version restores the default protocol, `pap`.

- Options**
- `none`—Specifies that no extended authentication is performed
  - `pap`—Specifies the use of PAP protocol for extended authentication
  - `chap`—Specifies the use of CHAP protocol for extended authentication
  - `re-authenticate`—Enables reauthentication when IKE SA rekeying occurs. When this option is enabled, rekeying of IKE SAs uses the initial authentication protocol to reauthenticate the user. When this option is disabled, authentication is only performed at the first IKE SA establishment. Subsequent IKE SAs rekey operations inherit the initial authentication and do not reauthenticate users. For maximum security, enable reauthentication.
  - `skip-peer-config`—Disables configuration of peer IP characteristics

**Mode**    IPSec Tunnel Profile Configuration

## external-paths

---

**Syntax**    external-paths *limit*

             no external-paths

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures the maximum number of received external BGP best paths allowed for route-target signaling. The **no** version restores the default value, 1.

**Options**    • *limit*—Number of paths, in the range 1–255

**Mode**    Address Family Configuration, Router Configuration



## CHAPTER 7

# F Commands

## **fabric-strict-priority**

---

**Syntax** [ no ] fabric-strict-priority

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies strict priority scheduling for queues in the traffic class in the fabric. The **no** version deletes the strict priority setting.

**Mode** Traffic Class Configuration

## **fabric-weight**

---

**Syntax**    `fabric-weight weight`  
              `no fabric-weight`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the relative weight for queues in the traffic class in the fabric. The **no** version sets the fabric weight to the default value.

**Options**    • *weight*—Range 1–63; default value is 8

**Mode**    Traffic Class Configuration

## fabric weights

---

**Syntax**    fabric weights multicast *multicastValue* unicast *unicastValue*  
              no fabric weights

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Defines the multicast-to-unicast traffic ratio for the ERX1440, ERX310, E120, or E320 router switch fabric. The **no** version returns the switch fabric to its default multicast:unicast ratio (15:2).

- Options**
- *multicastValue*—Ratio value of multicast bandwidth in the range 1–15
  - *unicastValue*—Ratio value of unicast bandwidth in the range 1–15

**Mode**    Global Configuration

---

## failover-resync

---

**Syntax** failover-resync { failover-protocol | failover-protocol-fallback-to-silent-failover | silent-failover | disable | not-configured }

no failover-resync

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Configures the L2TP peer resynchronization method that an L2TP failed endpoint uses to resynchronize with its peer non-failed endpoint. This command configures peer resynchronization for a host profile or a domain map tunnel, and overrides a global peer resynchronization method that is specified in Global Configuration mode. The **no** version restores the default setting, not-configured.

- Options**
- failover-protocol—Specifies the L2TP failover protocol method
  - failover-protocol-fallback-to-silent-failover—Specifies the L2TP failover protocol method; however, if the peer does not support this method, the silent failover method is used
  - silent-failover—Specifies the silent failover method
  - disable—Disables peer resynchronization
  - not-configured—Specifies that peer resynchronization is not configured for L2TP host profiles and AAA domain map tunnels. L2TP uses the global failover method; the default setting

**Mode** Domain Map Tunnel Configuration, L2TP Destination Profile Host Configuration

## filter

---

**Syntax**    [ no ] [ suspend ] filter

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines a policy rule that drops all packets conforming to the current classifier control list and can be used while the policy list is referenced by interfaces. The **no** version removes the filter rule from the policy list; the **suspend** version temporarily suspends the policy rule; the **no suspend** version resumes application of a suspended rule.



.....  
**NOTE:** This command replaces the Policy List Configuration version of the **filter** command, which may be removed completely in a future release.  
.....

**Mode**    Classifier Group Configuration

**Related Documentation**    • Policy Rule Precedence

## flash-disk compare

---

**Syntax** flash-disk compare { all | configuration }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Performs a checksum validation that compares the contents of the NVS file system on the primary SRP module with the contents of the NVS file system on the redundant SRP module, and detects any differences. The command validates only those files that are synchronized between the primary and redundant SRP modules; it does not validate log files, core dump files, and other files that are excluded from the system synchronization process. There is no **no** version.

- Options**
- all—Compares all files in NVS; this option can take several minutes to complete
  - configuration—Compares only configuration files; this option takes less time to complete because it compares only a subset of the files in the NVS file system

**Mode** Privileged Exec

## flash-disk duplicate

---

**Syntax**    flash-disk duplicate

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Copies the contents of NVS on the primary SRP module to another NVS card. There is no **no** version.

**Mode**    Boot



## flash-disk initialize

---

**Syntax** flash-disk initialize [ no-format ] [ disk0 | disk1 ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**disk0** and **disk1** keywords added in JunosE Release 7.2.0.  
Privileged Exec mode added in JunosE Release 8.0.0.

**Description** Performs a low-level format of unmounted flash cards. There is no **no** version.

- Options**
- no-format—Erases all files but does not format the flash card
  - disk0—Specifies flash card in slot 0 of the SRP module; default value is disk0; available only in Boot mode, because disk0 cannot be in an unmounted state in a router outside of Boot mode
  - disk1—Specifies flash card in slot 1 of the SRP module; supported only on the E120 router and the E320 router

**Mode** Boot, Privileged Exec

## flash-disk scan

---

**Syntax** flash-disk scan [ repair ] [ disk0 | disk1 ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**disk0** and **disk1** keywords added in JunosE Release 7.2.0.  
Privileged Exec mode added in JunosE Release 8.0.0.

**Description** Scans the flash card on the primary SRP module to detect corrupt sectors, deletes files and directories that contain corrupt sectors, and fixes nonfatal errors. There is no **no** version.

- Options**
- **repair**—Repairs nonfatal errors detected on flash disk
  - **disk0**—Specifies flash card in slot 0 of the SRP module; default value is disk0; available only in Boot mode, because disk0 cannot be in an unmounted state in a router outside of Boot mode
  - **disk1**—Specifies flash card in slot 1 of the SRP module; supported only on the E120 router and the E320 router

**Mode** Boot, Privileged Exec

## forward

**Syntax** [ no ] [ suspend ] forward  
 [ interface *interfaceType* *interfaceSpecifier* [ next-hop *nextHop*  
 [ ignore-default-route ] ]  
 [ order *orderValue* ] ] [ next-hop *nextHop* [ virtual-router *vrName* ]  
 [ ignore-default-route ] [ order *orderValue* ] ] |  
 [ order *orderValue* ] | classifier-group *clacName* ] [ precedence *precValue* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a rule to forward all packets that match the specified classifier control list. If you do not specify a classifier control list using the **classifier-group** keyword, the router will select all packets from the interface in the direction of the attached policy list. The **no** version removes the rule from the policy list; the **suspend** version temporarily suspends the forward rule; the **no suspend** version resumes application of a suspended rule.

See the [forward interface](#) and [forward next-hop](#) commands for descriptions of the Classifier Group Configuration mode versions of this command.

- Options**
- *interfaceType*—Interface type; see “[Interface Types and Specifiers](#)” on page 5 (IP policy lists only)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see “[Interface Types and Specifiers](#)” on page 5 (IP policy lists only)
  - *nextHop*—Next-hop IP address (IP policy lists only)
  - ignore-default-route—Ignores the default route as a consideration for the next hop (IP policy lists only)
  - *vrName*—Name of the virtual router (IP policy lists only)
  - *orderValue*—Order of this forward rule within the single classifier; in the range 1–32767; default value is 100 (IP policy lists only)
  - *clacName*—Classifier control list used to classify packets for this policy
  - *precValue*—Precedence of this rule in relation to other rules within this set: in the range 0–32768; default value is 100

**Mode** Policy List Configuration

**Related Documentation**

- Assigning Values to the ATM CLP Bit

## forward interface

---

**Syntax** [ no ] [ suspend ] forward [ interface *interfaceType* *interfaceSpecifier*  
[ next-hop *nextHop* [ ignore-default-route ] ] [ order *orderValue* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a rule to forward all packets that match the current classifier control list. The **no** version removes the rule from the policy list; the **suspend** version temporarily suspends the forward rule; the **no suspend** version resumes application of a suspended rule.



.....  
**NOTE:** The **forward interface** command replaces the **next-interface** command, which may be removed completely in a future release.  
.....

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *nextHop*—Next-hop IP address
  - ignore-default-route—Ignores the default route as a consideration for the next hop
  - *orderValue*—Order of this forward rule within the single classifier; in the range 1–32767; default value is 100

**Mode** Classifier Group Configuration

**Related Documentation**

- [Assigning Values to the ATM CLP Bit](#)

## forward next-hop

**Syntax** [ no ] [ suspend ] forward next-hop *nextHop* [ virtual-router *vrName* ]  
[ ignore-default-route ] [ order *orderValue* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a rule to forward all packets that match the current classifier control list. The **no** version removes the rule from the policy list; the **suspend** version temporarily suspends the forward rule; the **no suspend** version resumes application of a suspended rule.



**NOTE:** The **forward next-hop** command replaces the **next-hop** command, which may be removed completely in a future release.

- Options**
- *nextHop*—Next-hop IP address
  - *vrName*—Name of the virtual router
  - ignore-default-route—Ignores the default route as a consideration for the next hop
  - *orderValue*—Order of this forward rule within the single classifier; in the range 1–32767; default value is 100

**Mode** Classifier Group Configuration

**Related Documentation**

- Assigning Values to the ATM CLP Bit

## forwarding-rate-threshold

---

**Syntax** forwarding-rate-threshold *forwardingRateThreshold*  
no forwarding-rate-threshold

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the threshold above which forwarded-rate-exceeded events are logged. The **no** version removes the threshold.

**Options** • *forwardingRateThreshold*—Bits per second in the range 0–1073741824

**Mode** Statistics Profile Configuration

**Related Documentation** • [Configuring Event Statistics](#)

## forwarding-table route-holddown

---

**Syntax** forwarding-table route-holddown *timerValue*  
no forwarding-table route-holddown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the number of seconds allowed after a routing table change for the accumulation of additional updates and subsequent distribution of the set of routing table changes to the line modules. The **no** version sets the hold-down time to the default value (3 seconds).

**Options**

- *timerValue*—Number of seconds allowed for the accumulation and subsequent distribution of routing table updates to the line modules; a range of 0-30 seconds, where 0 specifies an update following each routing table change

**Mode** Global Configuration

## frame-relay class

---

**Syntax** [ no ] frame-relay class *mapName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Associates a map class with a subinterface. The **no** version removes the association between the map class and the subinterface.

**Options** • *mapName*—Name of the map class; use up to 64 characters

**Mode** Subinterface Configuration



## frame-relay classifier-list

---

**Syntax** frame-relay classifier-list *classifierName* [ traffic-class *trafficClassName* ]  
 [ color { green | yellow | red } ] [ user-packet-class *userPacketClassValue* ]  
 [ de-bit *deValue* ]

no frame-relay classifier-list *classifierName* [ *classifierNumber* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies a Frame Relay classifier control list. The **no** version removes the classifier control list.

- Options**
- *classifierName*—Name of the classifier control list entry
  - *trafficClassName*—Name of the traffic class to match
  - green—Matches packet color to green, indicating a low drop preference
  - yellow—Matches packet color to yellow, indicating a medium drop preference
  - red—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—User packet value to match in the range 0–15
  - *deValue*—Value of the DE bit to match; 0 or 1

**Mode** Global Configuration

**Related Documentation**

- Creating or Modifying Classifier Control Lists for Frame-Relay Policy Lists

## frame-relay description

---

**Syntax**    frame-relay description *name*  
              no frame-relay description

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description or an alias to a Frame Relay interface or subinterface. Use the show frame-relay interface or show frame-relay subinterface command to display the text description. The **no** version removes the description or alias.

**Options**    • *name*—Text string or alias of up to 80 characters for the Frame Relay interface or subinterface

**Mode**    Interface Configuration, Subinterface Configuration

## frame-relay dos-protection-group

---

**Syntax**    frame-relay dos-protection-group *groupName*  
              no frame-relay dos-protection-group

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches a Frame Relay denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## frame-relay fragment

---

**Syntax**    frame-relay fragment [ [ *fragmentSize* ] [ fragmentation-only ] | reassembly-only ]  
             no frame-relay fragment

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures fragmentation and reassembly for the map class created with the **map-class frame-relay** command. The **no** version stops fragmentation and/or reassembly on the subinterface.

- Options**
- *fragmentSize*—Maximum payload size of a fragment in bytes; a number in the range 16–8188; default value is 52
  - fragmentation-only—Specifies fragmentation only
  - reassembly-only—Specifies reassembly only

**Mode**    Map Class Configuration

## frame-relay interface-dlci ietf

---

**Syntax**    frame-relay interface-dlci *dlci* ietf  
              no frame-relay interface-dlci *dlci*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a data-link connection identifier to a specified Frame Relay subinterface on the router or access server. The DLCI number identifies a virtual circuit. The **no** version removes this assignment.

**Options**    • *dlci*—DLCI number to be used on the specified subinterface to identify a virtual circuit in the range 16–1007

**Mode**    Subinterface Configuration

**Related Documentation**    • Configuring Frame Relay Layer 2 Services

## frame-relay intf-type

---

**Syntax**    frame-relay intf-type *type*  
              no frame-relay intf-type

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a Frame Relay interface type. The **no** version restores the default value, DTE.

- Options**    • *type*—One of the following interface types:
- dce—Router is connected to user DTE equipment
  - dte—Router is connected to a Frame Relay network; the default
  - nni—Router connects two Frame Relay networks

**Mode**    Interface Configuration

**Related Documentation**    • Configuring Frame Relay Layer 2 Services

## frame-relay keepalive

---

**Syntax**    frame-relay keepalive [ *seconds* ]  
              no frame-relay keepalive

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables the LMI mechanism for serial lines using Frame Relay encapsulation. The **no** version disables this capability. The keepalive command is similar to the **frame-relay lmi-t391dte** command.

**Options**    • *seconds*—Number in the range 5–30; default value is 10 seconds; defines the keepalive interval; the interval must be set, and the value on the DTE should be less than the value set on the DCE

**Mode**    Interface Configuration

## frame-relay lmi-n391dte

---

**Syntax**    frame-relay lmi-n391dte *keepExchanges*  
              no frame-relay lmi-n391dte

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the full-status polling counter (N391) on a DTE interface. The **no** version restores the default value, assuming an LMI has been configured.

**Options**    • *keepExchanges*—Number in the range 1– 255; default value is 6; number of keep exchanges to be done before requesting a full-status message. If you specify a value of 1, you receive full-status messages only.

**Mode**    Interface Configuration



## frame-relay lmi-n392dce

---

**Syntax**    frame-relay lmi-n392dce *threshold*  
              no frame-relay lmi-n392dce

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the error threshold counter (N392) on a DCE interface. The **no** version removes current setting and sets the default.

**Options**    • *threshold*—Positive number in the range 1– 10; number of errors that will place the interface in an operationally down state; default value is 2 errors

**Mode**    Interface Configuration

## frame-relay lmi-n392dte

---

**Syntax**    frame-relay lmi-n392dte *threshold*  
              no frame-relay lmi-n392dte

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the error threshold counter (N392) on a DTE interface. The **no** version removes current setting and sets the default.

**Options**    • *threshold*—Positive number in the range 1–10; number of errors that will place the interface in an operationally down state; default value is 3 errors

**Mode**    Interface Configuration

## frame-relay lmi-n393dce

---

**Syntax**    frame-relay lmi-n393dce *events*  
              no frame-relay lmi-n393dce

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the monitored events count (N393) on a DCE interface. The **no** version removes current setting and sets the default.

**Options**    • *events*—Number in the range 1–10 events; specifies the diagnostic window used to verify link integrity; default value is 2 events (The detection of N392 errors within the window of N393 samples places the interface in an operationally down state.)

**Mode**    Interface Configuration

## frame-relay lmi-n393dte

---

**Syntax**    frame-relay lmi-n393dte *events*  
              no frame-relay lmi-n393dte

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the monitored event count (N393) on a DTE interface. The **no** version removes current setting and sets the default.

**Options**    • *events*—Number in the range 1–10 events; default value is 4 events; specifies the diagnostic window used to verify link integrity (the detection of N392 errors within the window of N393 samples places the interface in an operationally down state)

**Mode**    Interface Configuration

## frame-relay lmi-t391dte

---

**Syntax**    frame-relay lmi-t391dte *seconds*  
              no frame-relay lmi-t391dte

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the link integrity verification polling timer (T391) on a DTE interface. The **no** version removes the current setting and sets the default.

**Options**    • *seconds*—Number in the range 5–30 seconds; specifies the interval in seconds between status inquiries issued by the DTE; default value is 10 seconds

**Mode**    Interface Configuration

## frame-relay lmi-t392dce

---

**Syntax**    frame-relay lmi-t392dce *seconds*  
              no frame-relay lmi-t392dce

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the polling verification timer (T392) on a DCE interface. The **no** version removes current setting and sets the default.

**Options**    • *seconds*—Number in the range 5–30 seconds; specifies the expected interval in seconds between status inquiries issued by the DTE equipment; default value is 15 seconds

**Mode**    Interface Configuration

## frame-relay lmi-type

---

**Syntax**    frame-relay lmi-type *type*  
              no frame-relay lmi-type

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Selects the LMI type. The **no** version restores the default value.

- Options**
- *type*—One of the following types:
    - *ansi*—ANSI T1.617 Annex D
    - *cisco*—Original Group of Four specification developed by DEC, Northern Telecom, Stratacom, and Cisco
    - *q933a*—ITU-T Q.933 Annex A
    - *none*—No management interface is used

**Mode**    Interface Configuration

**Related Documentation**

- [Configuring Frame Relay Layer 2 Services](#)

## frame-relay policy

---

**Syntax**    frame-relay policy { input | output } *policyName*  
              [ statistics { enabled [ baseline { enabled | disabled } ] [ preserve | merge ] |  
              disabled [ merge ] } ] merge ]  
  
              no frame-relay policy { input | output } [ *policyName* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **merge** keyword added in JunosE Release 7.2.0.

**Description**    Assigns a policy list to the ingress or egress of a Frame Relay interface. If you enter this command when the policy list does not exist, the router will create a policy list with a filter rule as the default. You must specify the **input** or **output** keyword to assign the policy list to the ingress or egress of the interface. The **no** version removes the association between a policy list and an interface.

- Options**
- input—Applies policy to data arriving at this interface
  - output—Applies policy to data leaving this interface
  - *policyName*—Name of the policy; a maximum of 40 characters
  - statistics—Enables or disable collection of policy routing statistics
    - enabled—Enables collection of policy routing statistics
    - baseline enabled—Enables baselining of policy routing statistics
    - baseline disabled—Disables baselining of policy routing statistics
    - preserve—Preserves existing statistics for any classifier-list that is the same for both the new and old policy attachments when you attach a new policy to an interface
    - disabled—Disables collection of policy routing statistics
  - merge—Enables merging of multiple policies to form a single policy

**Mode**    Interface Configuration

**Related Documentation**

- Setting a Statistics Baseline for Policies



## frame-relay policy-list

---

**Syntax** [ no ] frame-relay policy-list *policyName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies a Frame Relay policy list and accesses Policy List Configuration mode. If you execute a **frame-relay policy-list** command and type **exit**, the router creates a policy list with a filter rule as the default. Attaching this policy list to an interface filters all packets on that interface. The **no** version removes a policy list.

**Options** • *policyName*—Name of the policy list

**Mode** Global Configuration

**Related Documentation** • [Creating Policy Lists for Frame Relay](#)

## framing

---

**Syntax**    `framing framingType`  
`no framing`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the framing mode used by E3 or T3 interfaces. Available modes vary by the type of interface. The **no** version restores the default for that interface.

- Options**    • *framingType*—One of the following framing types:
- E3 Frame
    - g751—Default; G.751 compliant frame
    - g832—G.832 compliant frame
  - T3
    - c-bit—Default; specifies c-bit parity framing
    - m23—Specifies M23 multiplexer framing

**Mode**    Controller Configuration

## frequency

---

**Syntax**    `frequency frequencyValue`

`no frequency`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    In RTR Configuration mode, sets the time interval between RTR operations. In SNMP Event Manager Configuration mode, sets the frequency (in seconds) at which you want MIB sampling to occur. The **no** version restores the default value.

**Options**    • *frequencyValue*—Number of seconds between RTR operations or MIB sampling operations, depending on the configuration mode; with RTR operations, for both types (echo and pathEcho), the default value is 60 seconds; with MIB sampling, the default value is 600 seconds.

**Mode**    RTR Configuration, SNMP Event Manager Configuration

## ftp-server enable

---

**Syntax** [ no ] ftp-server enable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the FTP server and monitors the FTP port for attempts to connect to the FTP server. The **no** version terminates the current FTP sessions and disables the FTP server.

**Mode** Global Configuration

## ftp-server flush

---

<b>Syntax</b>	ftp-server flush
<b>Release Information</b>	Command introduced in JunosE Release 10.0.0.
<b>Description</b>	Forcibly terminates existing file transfer sessions to enable unified ISSU to proceed successfully. There is no <b>no</b> version.
<b>Mode</b>	Privileged Exec
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>FTP Server File Transfers Behaviors</i> in the <i>JunosE System Basics Configuration Guide</i></li></ul>

## full-spf-always

---

**Syntax** [ no ] full-spf-always

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables full SPF calculations for ISIS network changes. The **no** version restores partial route calculation (PRC) mode for SPF calculations.

**Mode** Router Configuration

## CHAPTER 8

# G Commands

## global export map

---

**Syntax**    global export map [ ipv4 | ipv6 ] *routeMap*  
              no global export map [ ipv4 | ipv6 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Associates a route map with a VRF to modify and filter routes exported by the VRF to the global BGP non-VPN RIB in the parent VR. Both IPv4 and IPv6 routes are exported unless you issue the appropriate keyword to restrict exportation. The **no** version disables the exporting of routes to the global BGP non-VPN RIB.

- Options**
- **ipv4**—Specifies that only IPv4 routes are exported to the global BGP non-VPN RIB
  - **ipv6**—Specifies that only IPv6 routes are exported to the global BGP non-VPN RIB
  - **routeMap**—Name of a route map; string of up to 32 alphanumeric characters

**Mode**    VRF Configuration



## global import map

---

**Syntax**    `global import map [ ipv4 | ipv6 ] routeMap max-routes maxNumber`  
              `no global import map [ ipv4 | ipv6 ]`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Associates a route map with a VRF to modify and filter routes imported by the VRF from the global BGP non-VPN RIB in the parent VR. Both IPv4 and IPv6 routes are imported unless you issue the appropriate keyword to restrict importation. The **no** version disables the importing of routes from the global BGP non-VPN RIB to the VRF RIB.

- Options**
- `ipv4`—Specifies that only IPv4 routes are imported from the global BGP non-VPN RIB
  - `ipv6`—Specifies that only IPv6 routes are imported from the global BGP non-VPN RIB
  - `routeMap`—Name of a route map; string of up to 32 alphanumeric characters
  - `maxNumber`—Maximum number of routes that can be imported; integer in the range 1–4294967295

**Mode**    VRF Configuration

## graceful-restart

---

**Syntax** [ no ] graceful-restart

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures hitless restart capability for OSPFv2. If high availability is active, the OSPF instance can perform a hitless restart when switching or failing over to the secondary SRP module. The **no** version disables OSPF graceful restart capability on the router.

**Mode** Router Configuration

## graceful-restart helper

---

**Syntax** [ no ] graceful-restart helper

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the router to function as an OSPFv2 or OSPFv3 graceful restart helper router. The **no** version disables OSPF graceful restart helper mode capability on the router.

**Mode** Router Configuration

## **graceful-restart helper-abort-topology-change**

---

**Syntax**   graceful-restart helper-abort-topology-change { any | non-externals }  
              no graceful-restart helper-abort-topology-change

**Release Information**   Command introduced before JunosE Release 7.1.0.

**Description**   Configures the OSPFv2 or OSPFv3 helper router to cease help to a restarting router under the specified conditions. However, the router continues to act as helper for subsequent graceful restart requests. The **no** version turns off the graceful restart helper capability.

**Options**   • any—Abandons the helper role when any LSA changes during the restart  
              • non-externals—Abandons the helper role only when any nonexternal LSA changes during the restart

**Mode**   Router Configuration

## graceful-restart notify-time

---

**Syntax** [ no ] graceful-restart notify-time *notifyTime*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the estimated time for the OSPFv2 router to send purged grace LSAs over all interfaces. The **no** version returns the notify duration timer to its default value, 15 seconds.

**Options**

- *notifyTime*—Number of seconds during which the router can send purged grace LSAs over all interfaces; in the range 1–1800

**Mode** Router Configuration

## graceful-restart restart-time

---

**Syntax** [ no ] graceful-restart restart-time *restartTime*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the estimated time for the restarting OSPFv2 router to reacquire OSPF neighbors that were fully functional prior to the restart. When this timer expires, the restarting router exits the restart procedure, originates any LSAs that were suppressed during the restart, removes any self-originated LSAs that it received from helping neighbors, runs SPF, and updates any routes in the routing table. The **no** version returns the restart duration timer to its default value, 180 seconds.

**Options**

- *restartTime*—Number of seconds during which the restarting router can reacquire OSPF neighbors that were fully functional prior to the restart; in the range 1–1800

**Mode** Router Configuration

## grace-period

---

**Syntax**    `grace-period days [ hours [ minutes [ seconds ] ] ]`  
`no grace-period`

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Configures the grace period for address leases allocated from the current DHCP local address pool. When the address lease expires, the address enters the grace period, when the address continues to be unavailable to other clients and can only be reassigned to the original client. This command applies only to expired releases—to optionally apply the grace period to addresses that are *explicitly released* by a client, you must enable the **use-release-grace-period** command. The **no** version restores the default, in which no grace period is associated with the local address pool.

- Options**
- *days*—Number of days in the grace period; in the range 0–32767
  - *hours*—Number of hours in the grace period; in the range 0–23
  - *minutes*—Number of minutes in the grace period; in the range 0–59
  - *seconds*—Number of seconds in the grace period; in the range 0–59

**Mode**    DHCP Local Pool Configuration

## gre destination profile

**Syntax**    gre destination profile *profileName* [ [ any-virtual-router ] |  
               [ virtual-router *virtualRouterName* ] }  
  
             no gre destination profile *profileName*

**Release Information** Command introduced in JunosE Release 8.2.0.

<b>Description</b>	Configures a destination profile for dynamic GRE tunnels and enters IP Tunnel Destination Profile Configuration mode. The <b>no</b> version deletes the destination profile.
--------------------	--

**Options**

- *profileName*—Name of the destination profile
- *any-virtual-router*—Specifies a default destination profile for all virtual routers; only one default destination profile can be defined in the system
- *virtualRouterName*—Name of the transport virtual router

Mode Global Configuration



## green-mark

---

**Syntax** [ no ] green-mark colorMarkValue

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Applies ToS mark value to green packets, which can be from policy actions, earlier policies, or rate-limit hierarchies. The **no** version deletes the ToS mark value.

**Options**

- colorMarkValue—Value of the ToS mark to be applied: in the range 0–255

**Mode** Color Mark Profile Configuration

**Related Documentation**

- Hierarchical Rate Limits Overview
- Policy Rule Precedence

## gre-tunnel classifier-list

---

**Syntax**    `gre-tunnel classifier-list classifierName`  
              `[ traffic-class className ] [ color { green | yellow | red } ]`  
              `[ user-packet-class userPacketClassValue ]`  
              `[ precedence precNum | dsfield dsfieldNum | tos tosNum ]`  
  
              `no gre-tunnel classifier-list classifierName [ classifierNumber ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates or modifies a GRE tunnel classifier control list. The **no** version deletes the classifier control list.

- Options**
- *classifierName*—Name of a classifier list entry
  - *className*—Name of a traffic class; the router supports up to eight traffic classes
  - *green*—Matches packet color to green, indicating a low drop preference
  - *yellow*—Matches packet color to yellow, indicating a medium drop preference
  - *red*—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—Value of the user packet class in the range 0–15
  - *precNum*—Upper three bits of the ToS byte; in the range 0–7
  - *dsfieldNum*—Upper six bits of the ToS byte; in the range 0–63
  - *tosNum*—Whole eight bits of the ToS byte; in the range 0–255
  - *classifierNumber*—Index of the classifier control list entry to be deleted; an integer in the range 1–10000

**Mode**    Global Configuration

**Related Documentation**

- Creating or Modifying Classifier Control Lists for GRE Tunnel Policy Lists

## gre-tunnel policy

<b>Syntax</b>	<pre>gre-tunnel policy { input   output } <i>policyName</i> [ statistics { enabled   disabled   preserve }   merge ]  no gre-tunnel policy { input   output } [ <i>policyName</i> ]</pre>
<b>Release Information</b>	<p>Command introduced before JunosE Release 7.1.0.</p> <p><b>merge</b> keyword added in JunosE Release 7.2.0.</p>
<b>Description</b>	<p>Assigns a GRE tunnel policy list to an interface. If you enter the <b>gre-tunnel policy</b> command and the policy list does not exist, the router creates a policy list with no rules, the default. Attaching this policy list to an interface filters all packets on that interface. You must specify the <b>input</b> or <b>output</b> keyword to assign the policy list to the ingress or egress of the interface. The <b>no</b> version removes the association between a policy list and an interface.</p>
<b>Options</b>	<ul style="list-style-type: none"> <li>• <b>input</b>—Applies policy to data arriving at this interface</li> <li>• <b>output</b>—Applies policy to data leaving this interface</li> <li>• <b><i>policyName</i></b>—Name of the policy; a maximum of 40 characters</li> <li>• <b>statistics</b>—Enables or disables collection of policy routing statistics <ul style="list-style-type: none"> <li>• <b>enabled</b>—Enables collection of policy routing statistics</li> <li>• <b>disabled</b>—Disables collection of policy routing statistics</li> <li>• <b>preserve</b>—Preserves existing statistics for any classifier-list that is the same for both the new and old policy attachments when you attach a new policy to an interface</li> </ul> </li> <li>• <b>merge</b>—Enables merging of multiple policies to form a single policy</li> </ul>
<b>Mode</b>	Interface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Setting a Statistics Baseline for Policies</li> </ul>

## gre-tunnel policy-list

---

**Syntax** [ no ] gre-tunnel policy-list *policyName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates the specified policy list and accesses Policy List Configuration mode. If you enter the **gre-tunnel policy-list** command and the policy list does not exist, the router creates a policy list with no rules, the default. Attaching this policy list to an interface filters all packets on that interface. The **no** version deletes the policy list.

**Options** • *policyName*—Name of a policy list; string of up to 40 alphanumeric characters

**Mode** Global Configuration

**Related Documentation** • [Creating Policy Lists for GRE Tunnels](#)

## group

**Syntax** To specify a group scheduler node for QoS:

```
[ no ] typeOfInterface group groupName scheduler-profile schedulerProfileName
```

To specify a Diffie-Hellman group:

```
group { 1 | 2 | 5 }
```

```
no group
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** From QoS Profile Configuration mode, specifies that a group scheduler node be configured for each interface of the given interface type. The **no** version removes this rule from the QoS profile.

From IKE Policy Configuration mode, assigns a Diffie-Hellman group to the IKE policy. The **no** version restores the default, 1024-bit Diffie-Hellman group.

- Options**
- *typeOfInterface*—Interface types for group scheduler nodes to be configured: atm, ethernet, serial, server-port
  - *groupName*—Name of the traffic class group
  - *schedulerProfileName*—Name of the scheduler profile
  - 1—Specifies the 768-bit group
  - 2—Specifies the 1024-bit group
  - 5—Specifies the 1536-bit group

**Mode** IKE Policy Configuration, QoS Profile Configuration

- Related Documentation**
- Configuring a QoS Profile
  - Configuring Shadow Nodes
  - Configuring QoS for an L2TP Session
  - Configuring QoS for Tunnel-Server Ports for L2TP LNS Sessions

## gsmp-syn-timeout

---

**Syntax** [ no ] gsmp-syn-timeout *timeOutValue*

**Release Information** Command introduced in JunosE Release 11.0.0.

**Description** Defines the ANCP neighbor session connection timeout value (in seconds). The neighbor session connection is established on the TCP session.

The **no** version reverts the session timeout to its default setting (60 seconds).

**Options**

- *timeOutValue*— Session timeout in seconds. The timer value cannot be more than the ANCP session timeout value. The default value for the ANCP session timeout is 75 seconds.

**Mode** L2C Configuration

## CHAPTER 9

# H Commands

## halt

---

**Syntax** The syntax of the command depends on whether you enter it from Boot mode or Privileged Exec mode.

From Boot mode:

halt

From Privileged Exec mode:

halt [ force | primary-srp [ force ] | standby-srp [ force ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Stops operation on both SRP modules or on the specified SRP module. When the high availability state is active or pending, this command ensures that the router configuration, up to when you issued the **halt** command, is mirrored to the standby SRP module. There is no **no** version.



**CAUTION:** To prevent corruption of NVS, issue this command before you remove or power down an SRP module.

- Options**
- **force**—Prompts the user to confirm that the router should stop operation if the SRP modules are in certain states, such as writing configuration data to NVS, that could lead to loss of configuration data or corruption of NVS.



**CAUTION:** When the high availability state is active or pending, issuing the **force** keyword does not guarantee that the configuration has been mirrored; recent configuration changes may be lost if you issue the **force** keyword.

- **primary-srp**—Stops operation on primary SRP module only
- **standby-srp**—Stops operation on standby SRP module only

**Mode** Boot, Privileged Exec



## hash

---

**Syntax**    hash { sha | md5 }  
             no hash

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the hash algorithm in an IKE policy. The **no** version restores the default, SHA-1.

- Options**
- sha—Specifies SHA-1 (HMAC variant) as the hash algorithm
  - md5—Specifies MD5 (HMAC variant) as the hash algorithm

**Mode**    IKE Policy Configuration

## hdlc dos-protection-group

---

**Syntax**    `hdlc dos-protection-group groupName`  
              `no hdlc dos-protection-group`

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches an HDLC denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## hdlc down-when-looped

---

**Syntax** [ no ] hdlc down-when-looped

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables loopback detection on a Cisco HDLC interface. Loopback detection is disabled by default. The **no** version disables loopback detection.

**Mode** Interface Configuration, Subinterface Configuration

## hdlc keepalive

---

**Syntax**    hdlc keepalive [ *seconds* ]  
              no hdlc keepalive

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a keepalive value. The keepalive mechanism tracks the health of the connection. The **no** version turns off the keepalive feature.

**Options**    • *seconds*—Keepalive timeout period in the range 0–6553 seconds; default value is 10.  
              A value of zero (0) turns off the keepalive feature.

**Mode**    Interface Configuration, Subinterface Configuration

## hdlc shutdown

---

**Syntax** [ no ] hdlc shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Stops or restarts a Cisco HDLC session. The **no** version restarts a Cisco HDLC session.

**Mode** Interface Configuration, Subinterface Configuration

## hello hold-time

---

**Syntax**    `hello hold-time seconds`  
              `no hello hold-time`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the MPLS hold time, the period that a sending LSR maintains a record of link hello messages from the receiving LSR without receipt of another link hello from that LSR. Each LSR peer sends the hold time in its link hello messages; peers negotiate to use the minimum of the hold times proposed by all LSRs on the same subnet. The hold timer is restarted whenever the LSR receives a link hello from the adjacent peer. The timer expires if no link hello is received from the adjacent peer within the hold time. The LSR deletes the link hello adjacency when the timer expires. If all link hello adjacencies are deleted for an LDP session, then the LSR terminates the LDP session. The **no** version restores the default value, 15 seconds.

**Options**    • *seconds*—Number of seconds, in the range 1–65535

**Mode**    LDP Profile Configuration

## hello interval

---

**Syntax**    `hello interval seconds`  
              `no hello interval`

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Specifies the interval between link-hello packets sent by LDP. The **no** version restores the default interval, 5 seconds.

**Options**    • *seconds*—Number of seconds, in the range 1–65535

**Mode**    LDP Profile Configuration

## hello-interval

---

**Syntax**    hello-interval *helloInterval*

             no hello-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval between hello packets that the router sends on the OSPF remote-neighbor interface. The **no** version restores the default value.

**Options**    • *helloInterval*—Number in the range 1–65535 seconds; default value is 10 seconds

**Mode**    Remote Neighbor Configuration



## help

---

**Syntax**    help

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Displays basic information about the Help system. There is no **no** version.

**Mode**    All modes

## hops-of-statistics-kept

---

**Syntax** hops-of-statistics-kept [ *hopsKeptValue* ]  
no hops-of-statistics-kept

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the number of hops to keep statistics for an entry. The **no** version restores the default value.

**Options**

- *hopsKeptValue*—Number of hops for which statistics are collected for a particular *pathEcho* type; default value is 16 for a *pathEcho* entry and 1 for an *echo* entry; if you omit this option, all hops found are recorded



.....  
**NOTE:** The E Series router supports only the *pathEcho* and *echo* types.  
.....

**Mode** RTR Configuration

## host

**Syntax** `host hostname ipAddress [ ftp [ [ userAlgorithmType ] userName [ [ passwordAlgorithmType ] password ] ] ] [ tftp ]`  
`no host hostname`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Adds or modifies an entry to the host table. The **no** version removes the specified host.

- Options**
- *hostname*—Hostname to add or modify; up to 20 characters
  - *ipAddress*—IPv4 or IPv6 address of the host
  - *ftp*—Specifies that the host is an FTP server; the default protocol if neither *ftp* nor *tftp* is specified
  - *userAlgorithmType*—Type of username
    - 0—Indicates that the *userName* is unencrypted; the default
    - 8—Indicates that the *userName* is an encrypted password
  - *userName*—Username used to access an FTP server (but not an NFS server); defaults to **anonymous**
  - *passwordAlgorithmType*—Type of password
    - 0—Indicates that the *password* is unencrypted; the default
    - 8—Indicates that the *password* is an encrypted password
  - *password*—Password used to access an FTP server (but not an NFS server); defaults to **null**
  - *tftp*—Specifies that the host is a TFTP server

**Mode** Global Configuration

## hostname

---

**Syntax**    `hostname hostname`  
`no hostname`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the name for the router; this hostname subsequently appears in the router CLI prompt. The **no** version removes the hostname from the router.



.....  
**NOTE:** In Domain Map Tunnel Configuration mode, this command has been replaced by the [clear suspicious-control-flow-detection](#) command and may be removed completely from Domain Map Tunnel Configuration mode in a future release.  
.....

**Options**    • *hostname*—String of up to 63 characters (no spaces)

**Mode**    Global Configuration

## hotfix activate

---

**Syntax**    `hotfix activate hfixFilename`  
`no hotfix activate { hfixFilename | all }`

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Activates the specified hotfix present on the local flash card. The **no** version deactivates the specified hotfix or all currently active hotfixes. Deactivating a hotfix restores the router to the state that existed before the hotfix was activated.

**Options**

- *hfixFileName*—Name of a hotfix software file (.hfx) on the local file system
- all—Specifies that all currently active hotfixes are deactivated

**Mode**    Privileged Exec



## CHAPTER 10

# I Commands

## id

---

**Syntax**    [ no ] *id neighborid*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the ANCP neighbor ID in the L2C Neighbor (config-l2c-neighbor) Configuration mode. The **no** version removes the neighbor ID.

**Options**    • *neighborid*—ANCP neighbor ID (MAC address) in the form XXXX.XXXX.XXXX

**Mode**    L2C Neighbor Configuration



## identification

---

**Syntax**    `identification serverId`

`no identification`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    From Domain Map Tunnel Configuration or Tunnel Group Tunnel mode, specifies the assignment ID of an L2TP tunnel. The **no** version removes the assignment ID from the tunnel.

**Options**    • *serverId*—L2TP tunnel assignment ID up to 32 characters

**Mode**    Domain Map Tunnel Configuration, Tunnel Group Tunnel

## idle-character

---

**Syntax**    idle-character { flags | marks }  
             no idle-character

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the HDLC idle character that is transmitted between HDLC packets. The **no** version restores the default value.

- Options**
- flags—Sets the idle character to 0x7E; the default value
  - marks—Sets the idle character to 0xFF

**Mode**    Interface Configuration

## igmp disable

---

**Syntax** [ no ] igmp disable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables IGMP on a virtual router. The **no** version reenables IGMP on a virtual router.

**Mode** Router Configuration

## igmp promiscuous

---

**Syntax** [ no ] igmp promiscuous

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Allows all IGMP interfaces on the router to accept IGMP reports from hosts on any subnet. The **no** version allows IGMP interfaces on the router to accept IGMP reports only from hosts on their associated subnets.

**Mode** Router Configuration

## ignore-attached-bit

---

**Syntax** [ no ] ignore-attached-bit

**Release Information** Command introduced in JunosE Release 12.0.0.

**Description** Allows the router to disregard the attach bit (ATT) in a level 1 router LSP. The **no** version restores the default, in which the attach bit is taken into account.

**Mode** Router Configuration

**Related Documentation**

- *Disregarding the Attach Bit in Level 1 LSPs* in the *IP, IPv6, and IGP Configuration Guide*

## ignore-lsp-errors

---

**Syntax** [ no ] ignore-lsp-errors

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Allows the router to ignore IS-IS link-state packets that are received with internal checksum errors rather than purging the link-state packets. The **no** version disables this function.

**Mode** Router Configuration

## ike crl

---

**Syntax**    ike crl { ignored | optional | required }  
              no ike crl

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Controls how the router handles certificate revocation lists (CRLs) during negotiation of IKE phase 1 signature authentication. The **no** version returns the CRL setting to the default, optional.



.....  
**NOTE:** This command has been replaced by the [ipsec crl](#) command and may be removed completely in a future release.  
.....

- Options**
- **ignored**—Allows negotiations to succeed even if a CRL is invalid or the peer's certificate appears in the CRL; this is the most lenient setting
  - **optional**—If the router finds a valid CRL, it uses it; this is the default
  - **required**—Requires a valid CRL; either the certificates belonging to the E Series router or the peer must not appear in the CRL; this is the strictest setting

**Mode**    Global Configuration

## ike local-identity

---

**Syntax**    ike local-identity { ip address *ipAddress* | username *userName* | domain-name *domainName* }

no ike local-identity

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Sets the local IKE identity used for IKE security association (SA) negotiations. The **no** version removes the local IKE identity.

- Options**
- *ipAddress*—IP address in 32-bit dotted decimal format (for example, 192.56.32.2)
  - *userName*—Username used as the IKE local identity for IKE SA negotiations
  - *domainName*—Domain name used as the IKE local identity for IKE SA negotiations (string of 1–32 characters)

**Mode**    IPSec Tunnel Profile Configuration



## ike peer-identity distinguished-name

---

**Syntax**   ike peer-identity distinguished-name *dnString*  
             no ike peer-identity ip address distinguished-name

**Release Information**   Command introduced in JunosE Release 7.3.0.

**Description**   Enables this profile to accept logins from users that present an ASN.1-encoded distinguished name as an IKE identity type and the user-provided IKE identity matches each distinguished name field in this profile. The **no** version removes the peer IKE identity.

**Options**

- *dnString*—String of 1–32 characters used as the distinguished name

**Mode**       IPSec Tunnel Profile Configuration

## ike peer-identity domain-name

---

**Syntax**    ike peer-identity domain-name *domainName*  
              no ike peer-identity ip address domain-name

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Enables this profile to accept logins from users that present a userFQDN or FQDN as an IKE identity type and the domain name portion of the IKE identity matches the domain name setting for this profile. An empty string (default) means that IKE identity types of userFQDN and FQDN are not allowed for logins on this profile. The IKE identity type of userFQDN also carries a domain name. Users presenting this identity must also pass any restrictions set for the peer domain name for this profile before they are able to log in. The **no** version removes the peer IKE identity.

**Options**    • *domainName*—String of 1–32 characters used as the domain name

**Mode**    IPSec Tunnel Profile Configuration

## ike peer-identity ip address

---

**Syntax**    ike peer-identity ip address *ipAddress* [ *ipMask* ]

              no ike peer-identity ip address *ipAddress*

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Enables this profile to accept logins from users that present an IP address as an IKE identity type and the IP address resides within the specified network. The default of 0.0.0.0/0 allows any peer IP address to this profile. The **no** version removes the peer IKE identity.

- Options**
- *ipAddress*—IP address in 32-bit dotted decimal format (for example, 192.56.32.2)
  - *ipMask*—Mask for associated IP subnet in dotted decimal or prefix length notation

**Mode**    IPSec Tunnel Profile Configuration

## ike peer-identity username

---

**Syntax**   ike peer-identity username *userName*  
             no ike peer-identity ip address username

**Release Information**   Command introduced in JunosE Release 7.3.0.

**Description**   Enables this profile to accept logins from users that present a userFQDN as an IKE identity type and the username portion of the IKE identity matches the username setting for this profile. An empty string (default) means that an IKE identity type of userFQDN is not allowed for logins on this profile. The **no** version removes the peer IKE identity.

**Options**

- *userName*—String of 1–32 characters used as the user name

**Mode**       IPSec Tunnel Profile Configuration

## import map

---

**Syntax**    `import map [ ipv4 | ipv6 ] routeMap`  
`no import map [ ipv4 | ipv6 ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Associates a route map with a VRF to modify and filter routes imported by the VRF from the global BGP VPN RIB. Both IPv4 and IPv6 routes are imported unless you issue the appropriate keyword to restrict importation. The **no** version enables all routes whose route targets match the import route targets of the VRF to be imported without applying a route map.

- Options**
- `ipv4`—Specifies that only IPv4 routes are imported from the global BGP VPN RIB
  - `ipv6`—Specifies that only IPv6 routes are imported from the global BGP VPN RIB
  - `routeMap`—Name of a route map; string of up to 32 alphanumeric characters

**Mode**    VRF Configuration

## inarp

---

**Syntax**    inarp [ *frequency* ]

             no inarp

**Release Information**    Command introduced in JunosE Release 7.1.0.  
                             ATM VC Class Configuration mode added in JunosE Release 7.3.0.

**Description**    In ATM VC Configuration mode, enables Inverse ARP (InARP) on an ATM PVC that resides on an ATM 1483 NBMA subinterface. Optionally, you can specify the InARP refresh rate. The **inarp** command is valid only for data PVCs configured with **aal5snap** encapsulation; you cannot use this command for data PVCs with other encapsulation types or for control (ILMI or signaling) PVCs. The **no** version restores the default behavior, which disables InARP.

                     In ATM VC Class Configuration mode, enables InARP as part of a VC class definition that you assign to an ATM data PVC. The **no** version restores the default behavior, which disables InARP, in the VC class.

**Options**    • *frequency*—InARP refresh rate in minutes, in the range 1–60; default value is 15

**Mode**    ATM VC Configuration, ATM VC Class Configuration

## include circuit-identifier

---

**Syntax**    include circuit-identifier *circuitType* [ prepend-circuit-type ]  
              no include circuit-identifier

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies that the circuit identifier is included when the router automatically generates a username for an IP service profile. The **no** version disables inclusion of the circuit identifier.

**Options**    • *circuitType*—Type of circuit; atm or vlan  
              • prepend-circuit-type—Specifies that the circuit type is included in the username

**Mode**    IP Service Profile Configuration

## include dhcp-option 82

---

**Syntax** [ no ] include dhcp-option 82 { agent-circuit-id | agent-remote-id }

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Specifies that the agent-circuit-id suboption or the agent-remote-id suboption of the DHCP relay agent information option (option 82) is included when the router automatically generates a username for an IP service profile. The **no** version disables inclusion of the suboption.

**Mode** IP Service Profile Configuration



## include hostname

---

**Syntax** [ no ] include hostname

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Specifies that the router's hostname is included when the router automatically generates a username for an IP service profile. The **no** version disables inclusion of the hostname.

**Mode** IP Service Profile Configuration

## include ip-address

---

**Syntax** [ no ] include ip-address

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the IP address is included when the router automatically generates a username for an IP service profile. The **no** version disables inclusion of the IP address.

**Mode** IP Service Profile Configuration

## include mac-address

---

**Syntax** [ no ] include mac-address

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the MAC address is included when the router automatically generates a username for an IP service profile. The **no** version disables inclusion of the MAC address.

**Mode** IP Service Profile Configuration

## include virtual-router-name

---

**Syntax** [ no ] include virtual-router-name

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the virtual router name is included when the router automatically generates a username for an IP service profile. The **no** version disables inclusion of the virtual router name.

**Mode** IP Service Profile Configuration

## index

---

**Syntax**    `index indexNumber next-address ipAddress [ [ mask ] ipMask ] [ loose ]`  
              `no index indexNumber`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a next hop at a particular index in the MPLS explicit path. The **no** version removes the next hop from the index.

- Options**
- *indexNumber*—Number of a node in an ordered set of abstract nodes; in the range 1–255
  - *ipAddress*—Address of the next hop
  - *ipMask*—[ not currently used] mask for the next adjacent address
  - *loose*—Node is not necessarily directly connected (adjacent) to the previous node in the path. If *loose* is not configured, the configuration defaults to *strict*. *Strict* indicates that the node is directly connected to the previous node.

**Mode**    Explicit Path Configuration

## instance-interface-type

---

<b>Syntax</b>	<code>instance-interface-type {<i>instanceInterfaceType</i>   set   superset }</code>  <code>no instance-interface-type { <i>instanceInterfaceType</i>   all }</code>
<b>Release Information</b>	Command introduced in JunosE Release 7.1.0. <b>lag</b> keyword added in JunosE Release 8.1.0. <b>set</b> and <b>superset</b> keywords added in JunosE Release 9.2.0.
<b>Description</b>	Assigns an instance-interface type to a QoS parameter definition. Instance-interface types indicate the interfaces for which QoS clients can assign QoS parameter instances. You can specify up to eight instance-interface types for each parameter definition. The <b>no</b> version removes the specified instance-interface type from the parameter definition.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>instanceInterfaceType</i>—One of the following instance-interface types: atm, atm-vc, atm-vp, bridge, ethernet, fr-vc, ip, ip-tunnel, ipv6, lag, l2tp-session, l2tp-tunnel, lsp, pppoe, serial, server-port, svlan, vlan</li><li>• set—Specifies an interface set as an instance-interface type</li><li>• superset—Specifies an interface superset as an instance-interface type</li><li>• all—Removes all instance-interface types</li></ul>
<b>Mode</b>	QoS Parameter Definition
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring a Basic Parameter Definition for QoS Administrators</a></li><li>• <a href="#">Creating a QoS Parameter on an Interface Superset or Interface Set</a></li></ul>

## interface

---

**Syntax** [ no ] interface *interfaceType* *interfaceSpecifier* [ *extension* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures an interface. The **no** version removes the subinterface or the logical interface.



**NOTE:** See the individual **interface** command entries for the syntax for each type of interface.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *extension*—Option that depends on the type of interface

**Mode** Global Configuration

## interface atm

---

**Syntax** [ no ] interface atm *interfaceSpecifier* [ multipoint | point-to-point ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures an ATM interface or subinterface type. The **no** version removes the interface or subinterface.



**NOTE:** On the OC3-2 GE APS I/O module, you can configure only OC3/STM1 ATM interfaces in ports 0 and 1. Port 2 is reserved for a Gigabit Ethernet interface.

- Options**
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - multipoint—Specifies an NBMA subinterface
  - point-to-point—Specifies an ATM interface or subinterface; default

**Mode** Global Configuration, Interface Configuration

- Related Documentation**
- Configuring an MPLS Pseudowire with VCC Cell Relay Encapsulation
  - Configuring Local ATM Cross-Connects with AAL5 Encapsulation
  - Configuring MPLS LSPs for VPWS



## interface-event-disable

---

**Syntax** [ no ] interface-event-disable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that RIP does not purge the routing table on a RIP interface that has been brought down. The **no** version restores the default condition, wherein RIP does purge the routing table on an interface after a down event.

**Mode** Address Family Configuration, Router Configuration

## interface fastEthernet

---

<b>Syntax</b>	[ no ] interface fastEthernet <i>interfaceSpecifier</i>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Specifies a Fast Ethernet interface or subinterface or creates a subinterface over a Fast Ethernet interface. The <b>no</b> version removes the interface or subinterface. You must issue the <b>no</b> version from the highest level down; you cannot remove an interface or subinterface if the one above it still exists.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>interfaceSpecifier</i>—Particular interface; format varies according to interface type; see <a href="#">Interface Types and Specifiers on page 5</a></li></ul>
<b>Mode</b>	Global Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring Customer-Facing Interfaces in the VPWS Instance</li><li>• Configuring Ethernet/VLAN Layer 2 Services</li><li>• Configuring Local Cross-Connects Between Ethernet/VLAN Interfaces</li><li>• Configuring S-VLAN Tunnels for Layer 2 Services</li></ul>

## interface gigabitEthernet

**Syntax** [ no ] interface gigabitEthernet *interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies or creates a Gigabit Ethernet interface or a subinterface over a Gigabit Ethernet interface. The **no** version removes the interface or subinterface. You must issue the **no** version from the highest level down; you cannot remove an interface or subinterface if the one above it still exists.



**NOTE:** On the GE I/O module, you can configure only the primary port, 0. The router automatically uses the redundant port, 0R, if the primary port fails.

On the GE-2 APS I/O module, you can configure only the primary ports, 0 and 1. The router automatically uses the corresponding redundant port, 0R or 1R, if the primary port fails.

On the OC3-2 GE APS I/O module, you can configure only a Gigabit Ethernet interface in port 2. Ports 0 and 1 are reserved for OC3/STM1 ATM interfaces.

On the ES-2 GE-4 IOA, you can configure all four ports.

**Options** • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration

**Related Documentation**

- Configuring the QoS Shaping Mode for Ethernet Interfaces
- Creating a QoS Interface Hierarchy for Bulk-Configured VLAN Subinterfaces with RADIUS
- Configuring a Parameter Definition to Shape Ethernet Traffic Using Cell Mode

## interface ip

---

**Syntax** [ no ] interface ip *interfaceName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a shared IP interface. You can use the specified name to refer to the shared IP interface; you cannot use the layer 2 interface to refer to the shared IP interface, because the shared interface can be moved. The **no** version removes the IP interface.

**Options** • *interfaceName*—String of up to 15 characters

**Mode** Global Configuration

## interface ipv6

---

**Syntax** [ no ] interface ipv6 *interfaceName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a shared IPv6 interface. The **no** version removes the IPv6 interface.

**Options** • *interfaceName*—String of up to 15 characters

**Mode** Global Configuration

## interface lag

---

**Syntax** [ no ] interface lag *interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an IEEE 802.3ad link aggregation group (LAG) interface, also known as a LAG bundle, or a subinterface in a LAG bundle. Link aggregation enables you to group multiple Ethernet physical interfaces configured on the same module and with the same characteristics into a single logical interface. The individual Ethernet interfaces are referred to as member links of the LAG bundle. The **no** version removes the LAG bundle or subinterface.

**Options**

- *interfaceSpecifier*—LAG interface specifier; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration

**Related Documentation**

- Configuring the Scheduler Hierarchy for Hashed Load Balancing in 802.3ad Link Aggregation Groups
- Configuring the Scheduler Hierarchy for Subscriber Load Balancing in 802.3ad Link Aggregation Groups
- Configuring Load Rebalancing for 802.3ad Link Aggregation Groups

## interface loopback

**Syntax** [ no ] interface loopback *interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a loopback interface, which provides a stable address for protocols (for example, BGP, Telnet, or LDP) to use so that they can avoid any impact if a physical interface goes down. The loopback interface sends packets back to the router or access server for local processing. Any packets routed from the loopback interface, but not destined to the loopback interface, are dropped. The **no** version deletes the loopback interface.



**NOTE:** Do not confuse loopback with the null 0 interface. Traffic routed to null 0 is discarded on the line module.

You cannot shut down a loopback interface.



**BEST PRACTICE:** We recommend that you configure a 32-bit subnet mask for the loopback interface. For example, if you configure a loopback interface with the IP address and mask as 1.1.1.1/16, the 1.1.0.0/16 route entry is entered on the line module and if no specific or longer route entry is found, all traffic destined to the 1.1.0.0/16 subnet is forwarded to the SRP module by the line module. Although the SRP module responds only to traffic destined to the 1.1.1.1 subnet and discards traffic to all other host IP addresses within that subnet (1.1.1.1/16), if the SRP module receives too much traffic from subnets other than 1.1.1.1, the CPU utilization on the SRP module reaches the saturation level.

**Options**

- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration

**Related Documentation**

- Configuring an MPLS Pseudowire with VCC Cell Relay Encapsulation
- Configuring Local ATM Cross-Connects with AAL5 Encapsulation
- Configuring Local Cross-Connects Between Ethernet/VLAN Interfaces
- Configuring the Loopback Interface and Router ID for BGP for VPWS
- Configuring the Loopback Interface and Router ID for VPLS

## interface mlframe-relay

---

**Syntax** [ no ] interface mlframe-relay *interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an MLFR bundle or a subinterface in a bundle. The **no** version removes the bundle or subinterface.

**Options** • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration



## interface mlppp

---

**Syntax** [ no ] interface mlppp *interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an MLPPP network interface, also known as the MLPPP bundle. The **no** version deletes the MLPPP bundle.

**Options** • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Interface Configuration, Subinterface Configuration

## interface null

---

**Syntax**    interface null 0

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Selects the null interface, which does not forward traffic. The null interface acts as a data sink. Though you can access the null interface, you cannot configure any values for it or delete it. There is no **no** version.

**Mode**    Global Configuration

## interface pos

---

**Syntax** [ no ] interface pos *interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures a Packet over SONET interface. The **no** version removes the interface.

**Options**

- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration

**Related Documentation**

- Configuring HDLC Layer 2 Services

## interface serial

---

<b>Syntax</b>	[ no ] interface serial <i>interfaceSpecifier</i>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Specifies the location of the serial interface on CT3 and COCX-F3 modules. The <b>no</b> version disables the interface.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>interfaceSpecifier</i>—Particular interface; format varies according to interface type; see <a href="#">Interface Types and Specifiers on page 5</a></li></ul>
<b>Mode</b>	Global Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring Frame Relay Layer 2 Services</li><li>• Configuring HDLC Layer 2 Services</li></ul>

## interface tenGigabitEthernet

---

**Syntax** [ no ] interface tenGigabitEthernet *interfaceSpecifier*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies or creates a 10-Gigabit Ethernet interface or a subinterface over a 10-Gigabit Ethernet interface. The **no** version removes the interface or subinterface. You must issue the **no** version from the highest level down; you cannot remove an interface or subinterface if the one above it still exists.

**Options** • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration

## interface tunnel

---

**Syntax** [ no ] interface tunnel *interfaceSpecifier* [ transport-virtual-router *vrName* ]  
[ ipsec-transport ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a tunnel interface for use by DVMRP, GRE, IPSec, or MPLS. You can specify that the tunnel be established in the routing space of a virtual router other than the current VR. If you specify another VR, all tunnel commands apply to the tunnel in that VR. If you do not specify another VR, tunnel commands apply to the current VR. For DVMRP and GRE tunnels, you can specify that the tunnel be protected with IPSec in transport mode. The **no** version removes the tunnel interface.

- Options**
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *vrName*—Name of virtual router (other than the current VR) in which the tunnel will be established
  - ipsec-transport—Indicates that the tunnel is protected with IPSec in transport mode; used for GRE or DVMRP tunnels only

**Mode** Global Configuration

## invert data

---

**Syntax** [ no ] invert data

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables data stream inversion. Data stream inversion must be turned on by network personnel at the other end of the line. The **no** version disables data stream inversion.

**Mode** Interface Configuration

## ip

---

**Syntax**    ip { permit | deny }

no ip

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Modifies the subscriber policy for IP to define whether the subscriber (client) interfaces that belong to a bridge group or to a VPLS instance forward (permit) or filter (deny) IP packets. The **no** version restores the default value, permit IP packets.

You cannot change the default subscriber policy values for trunk (server) interfaces that belong to a bridge group or to a VPLS instance. You also cannot change the default subscriber policy values for a VPLS virtual core interface, which acts as a trunk interface. The VPLS virtual core interface represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices.

- Options**
- permit—Specifies that the subscriber interface associated with the bridge group or VPLS instance forwards IP packets
  - deny—Specifies that the subscriber interface associated with the bridge group or VPLS instance filters IP packets

**Mode**    Subscriber Policy Configuration



## ip access-routes

---

**Syntax** [ no ] ip access-routes

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the ability to create host access routes on a PPP interface, which is useful for the B-RAS application. It also enables an access route in a profile. The **no** version disables the feature.

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

## ip access-route table-map

---

**Syntax** [ no ] ip access-route table-map *mapName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Filters access routes before an access list adds them to the routing table. The **no** version deletes the table map.

**Options** • *mapName*—Name of the table map that you want the router to use

**Mode** Global Configuration

---

## ip address

---

**Syntax**    `ip address ipAddress ipMask [ secondary ]`  
`no ip address [ ipAddress ipMask [ secondary ] ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a primary or secondary IP address for an interface or subinterface. The **no** version removes an IP address or disables IP processing. You must specify the layer 2 encapsulation before you can set the IP address.

**Options**

- *ipAddress*—IP address in 32-bit dotted decimal format (for example, 192.56.32.2)
- *ipMask*—mask for associated IP subnet in dotted decimal or prefix length notation
- *secondary*—Specifies that the configured address is a secondary IP address; if omitted, the configured address is the primary IP address

**Mode**    Interface Configuration, Profile Configuration, Subinterface Configuration

**Related Documentation**

- Configuring Local ATM Cross-Connects with AAL5 Encapsulation
- Configuring Local Cross-Connects Between Ethernet/VLAN Interfaces
- Configuring the Loopback Interface and Router ID for BGP for VPWS
- Configuring the Loopback Interface and Router ID for VPLS
- Configuring MPLS LSPs for VPWS

## ip-address

---

**Syntax**    `ip-address ipAddress`

`[ no ] ip-address`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IP address parameter for a user entry in the local user database. The **no** version deletes the IP address parameter from the user entry.

**Options**    • *ipAddress*—IP address in 32-bit dotted decimal format (for example, 192.56.32.2)

**Mode**    Local User Configuration

## ip address-pool

---

**Syntax** ip address-pool { dhcp | local | none }  
no ip address-pool

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies to the router where to get an IP address for the remote user. The **no** version uses the default value, **local**.

- Options**
- dhcp—Enables the use of a DHCP server for address allocations
  - local—Enables the use of local address pool for address allocations
  - none—Does not enable an IP address pool

**Mode** Global Configuration

## ip-address-pool

---

**Syntax**    `ip-address-pool poolName`  
              `no ip-address-pool`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IP address pool parameter for a user entry in the local user database. The address pool is used to assign an IP address to the subscriber. The **no** version deletes the IP address pool parameter from the user entry in the local user database.

**Options**    • *poolName*—Name of IP address pool

**Mode**    Local User Configuration

## ip address virtual-router

---

**Syntax** [ no ] ip address *ipAddress* virtual-router *vrName*  
no ip address

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Limits the scope of the IKE policy rule to the specified local IP address on the specified virtual router. This limitation ensures that this policy rule is evaluated for IKE source address evaluations for only the specified IP address and virtual router. The **no** version removes IP address and virtual router limitation.

- Options**
- *ipAddress*—IP address in 32-bit dotted decimal format (for example, 192.56.32.2) to which you want to limit this policy rule
  - *vrName*—Name of virtual router to which you want to limit this policy rule

**Mode** IKE Policy Configuration

## ip alwaysup

---

**Syntax** [ no ] ip alwaysup

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Forces the interface to appear as if it is up, regardless of the state of the lower layers. Use this command to reduce routing protocol topology changes on the router when the network attached to this link is single-homed. This command may be useful when the router is running routing protocols with very large routing tables that may take a long time to converge. The **no** version makes the interface appear in its current state.

**Mode** Interface Configuration, Subinterface Configuration



## ip analyzer

---

**Syntax**    ip analyzer [ default ]

no ip analyzer

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures an interface as an analyzer interface, for use in an interface mirroring configuration. The **no** version removes the analyzer interface configuration from the interface.

**Options**    • default—Specifies that this interface is the default analyzer interface for the virtual router

**Mode**    Interface Configuration

**Related Documentation**    • Configuring CLI-Based Mirroring  
• Configuring RADIUS-Based Mirroring

## ip as-path access-list

---

**Syntax**    `ip as-path access-list accessListName { permit | deny } pathExpression`  
`no ip as-path access-list accessListName [ { permit | deny } pathExpression ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines a BGP-related access list. You can specify an access list filter on both inbound and outbound BGP routes. Each filter is an access list based on regular expressions. If the regular expression matches the representation of the AS path of the route as an ASCII string, then the permit or deny condition applies. The AS path does not contain the local AS number. The **no** version removes a single access list entry if **permit** or **deny** and a *pathExpression* are specified. Otherwise, the entire access list is removed.

- Options**
- *accessListName*—Name of the access list; a string of up to 32 characters
  - **permit**—Permits access for matching conditions
  - **deny**—Denies access to matching conditions
  - *pathExpression*—Regular expression describing the AS paths to be matched

Use a sequence of one or more elements, each of which is either an AS number or one of the following punctuation characters:

    ^ start of the path

    \$ end of the path

    { start of an AS\_SET

    } end of an AS\_SET

    ( start of an AS\_CONFED\_SET or AS\_CONFED\_SEQ

    ) end of an AS\_CONFED\_SET or AS\_CONFED\_SEQ

Use the following regular expression metacharacters to match individual elements:

    . matches any single element

    \* matches zero or more occurrences of any element

    + matches one or more occurrences of any element

    [ ] matches any elements enclosed between brackets ( [ ] )

    - hyphen; used within brackets to specify a range of AS numbers

^ matches any AS number except the ones specified when used as a first item within brackets

\_ underscore; used in implementations on routers from other vendors on either side of a path to specify a literal and disallow substring matching. Allowed but not required in our CLI.

**Mode**    Global Configuration

## ip atm-vc

---

**Syntax**    ip *ipAddress* atm-vc *vcd* broadcast  
              no ip *ipAddress* atm-vc *vcd*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Associates a protocol and address to a specific virtual circuit. The **no** version removes the association.

- Options**
- *ipAddress*—IP address to be associated with the virtual circuit
  - *vcd*—Number in the range 1–2147483647; virtual circuit descriptor; an identifier for the VC in other commands
  - broadcast—Specifies that the circuit should participate in broadcast operations

**Mode**    Map List Configuration

## ip auto-configure append-virtual-router-name

---

**Syntax** [ no ] ip auto-configure append-virtual-router-name

**Release Information** Command introduced in JunosE Release 12.1.0.

**Description** Appends the virtual router name to the subscriber interface name in the dynamic subscriber interface (DSI) configuration. This feature is enabled by default in a non-DSI configuration with the DHCP local server. The **no** version restores the default behavior where subscribers with the same IP address are disallowed in the DSI configuration.

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

## ip auto-configure ip-subscriber

---

**Syntax** [ no ] ip auto-configure ip-subscriber [ include-primary | exclude-primary ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**include-primary** and **exclude-primary** keywords added in JunosE Release 7.1.0.

**Description** Configures a primary IP interface to support creation of dynamic subscriber interfaces. The **include-primary** and **exclude-primary** keywords specify whether the primary interface can be assigned to a subscriber. The primary interface is not assigned to a subscriber by default.

The router creates the required dynamic subscriber interfaces when the IP address is assigned to the associated subscriber. The address might be assigned by an external DHCP server, the DHCP local server, or the packet detect feature. The primary interface is not assigned to a subscriber by default.

The **no** version disables creation of dynamic subscriber interfaces on this primary IP interface. Use the **no** version with the **include-primary** keyword to specify that the primary interface is not assigned to a subscriber.

- Options**
- **include-primary**—Specifies that the primary interface can be assigned to a subscriber; the **no** version disables the assignment of the primary interface
  - **exclude-primary**—Specifies that the primary interface cannot be assigned to a subscriber; the **no** version enables the assignment of the primary interface

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

## ip auto-detect ip-subscriber

---

**Syntax** [ no ] ip auto-detect ip-subscriber

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the router's packet detect feature, specifying that IP automatically detect packets that do not match any entries in the demultiplexer table. When an unmatched packet is detected, an event is generated that determines whether to create a dynamic subscriber interface or to configure an existing interface. The **no** version disables autodetection.

**Mode** Interface Configuration, Profile Configuration

## ip bgp-community new-format

---

**Syntax** [ no ] ip bgp-community new-format

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that communities must be displayed in *AA:NN* format, where *AA* is a number that identifies the autonomous system and *NN* is a number that identifies the community within the autonomous system. The **no** version restores the default display.

**Mode** Global Configuration



## ip bgp-confed-as-set new-format

---

**Syntax** [ no ] ip bgp-confed-as-set new-format

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that AS-confed-sets must be displayed within square brackets, [ ], with the ASs delimited by commas. The **no** version restores the default, displaying AS-confed-sets within parentheses, ( ), with the ASs delimited by spaces.

**Mode** Global Configuration

## ip block-multicast-sources

---

**Syntax** [ no ] ip block-multicast-sources

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 8.1.0.

**Description** Prevents mroute creation by blocking multicast traffic that has a scope larger than link-local (for example, global). In Profile Configuration mode, blocks multicast sources per user on dynamic IP interfaces. The **no** version restores the default behavior of creating mroutes upon receiving multicast packets.

**Mode** Interface Configuration, Profile Configuration

## ip broadcast-address

---

**Syntax** [ no ] ip broadcast-address [ *ipAddress* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a broadcast address for an interface. The **no** version restores the default IP broadcast address.

**Options** • *ipAddress*—Broadcast IP address

**Mode** Interface Configuration, Subinterface Configuration

## ip classifier-list

---

**Syntax** ip classifier-list *classifierName* [ traffic-class *trafficClassName* ]  
[ color { green | yellow | red } ] [ user-packet-class *userPacketClassValue* ]  
[ source-route-class *routeClassValue* ] [ destination-route-class *routeClassValue* ]  
[ local { true | false } ] [ not ] { *protocol* }  
[ not ] { *sourceAddress* *sourceMask* | host *sourceHostAddress* | any }  
[ *sourceQualifier* ]  
[ not ] { *destinationAddress* *destinationMask* | host *destinationHostAddress* | any }  
[ *destinationQualifier* ] [ *tcpQualifier* ] [ ip-flags *ipFlags* ]  
[ ip-frag-offset { eq 0 | eq 1 | gt 1 } ]  
[ precedence *precNum* | dsField *dsFieldNum* | tos *tosNum* ]  
  
no ip classifier-list *classifierName* [ *classifierNumber* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies a classifier control list. Use the **not** keyword to deny traffic for a specific protocol, source address, or destination address. Use the **any** keyword to allow traffic to any source or destination address. The **no** version removes the classifier control list.

- Options**
- *classifierName*—Name of the classifier control list entry
  - *trafficClassName*—Name of the traffic class to match
  - green—Matches packet color to green, indicating a low drop preference
  - yellow—Matches packet color to yellow, indicating a medium drop preference
  - red—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—User packet value to match; in the range 0–15
  - *routeClassValue*—Value of the route-class; in the range 0–255
  - local—Specifies traffic destined for this interface
    - true—Matches packets that are locally destined
    - false—Matches packets that are not locally destined
  - not—Matches any except the immediately following protocol or address
  - *protocol*—Protocol name (IGMP, IP, TCP, or UDP) or number (in the range 0–255) to match
  - *sourceAddress*—Source address to match
  - *sourceMask*—Wild-card mask to apply to the source address
  - host—Matches source or destination address as a host
  - *sourceHostAddress*—Source host address to match
  - any—Matches any source or destination address

- *sourceQualifier*—For UDP or TCP protocols, one of the following protocol-specific classifier parameters. See Creating or Modifying Classifier Control Lists for IP Policy Lists for details.
  - *portOperator*—One of the following Boolean operator keywords: **lt** (less than), **gt** (greater than), **eq** (equal to), **ne** (not equal), or **range** (range of port numbers)
  - *range*—Single port number or a range of port numbers
- *destinationAddress*—Destination address to match
- *destinationMask*—Wild-card mask to apply to the destination address
- *destinationHostAddress*—Destination host address to match
- *destinationQualifier*—One of the following protocol-specific classifier parameters for destination TCP or UDP ports, ICMP code and type, or IGMP type. The *portOperator* and *port range* are used with TCP and UDP. The *icmpType*, *icmpCode*, and *igmpType* parameters are used with ICMP and IGMP.
  - *portOperator*—one of the following Boolean operator keywords: **lt** (less than), **gt** (greater than), **eq** (equal to), or **ne** (not equal), or **range** (range of port numbers) (TCP and UDP only)
  - *range*—Single port number or a range of port numbers
  - *icmpType*—ICMP message type (ICMP only)
  - *icmpCode*—ICMP message code (ICMP only)
  - *igmpType*—IGMP message type (IGMP only)
- *tcpQualifier*—TCP flags classification parameters
- *tcpFlag*—For TCP only; a logic equation that specifies flag bit values; ! means logical NOT and & means logical AND; use any of the following flag names:
  - *ack*—0x10
  - *fin*—0x01
  - *push*—0x08
  - *rst*—0x04
  - *syn*—0x02
  - *urgent*—0x20
- *ipFlags*—Logic equation that specifies flag bit values; ! means logical NOT and & means logical AND; use any of the following flag names:
  - *dont-fragment*—0x02
  - *more-fragments*—0x01
  - *reserved*—0x04

- **ip-frag-offset**—Matches the specified IP fragmentation offset; use any of the following:
  - **eq 0**—Equals 0
  - **eq 1**—Equals 1
  - **gt 1**—Greater than 1
- **precNum**—Upper three bits of the ToS byte; in the range 0–7
- **dsFieldNum**—Upper six bits of the ToS byte; in the range 0–63
- **tosNum**—Whole eight bits of the ToS byte; in the range 0–255
- **classifierNumber**—Index of the classifier control list entry to be deleted

**Mode** Global Configuration

**Related Documentation** • [Creating or Modifying Classifier Control Lists for IP Policy Lists](#)

## ip community-list

**Syntax** Using a regular expression to specify the community:

```
[ no ] ip community-list communityLisName { permit | deny } communityExpression
```

Using some other method to specify the community:

```
ip community-list communityLisName { permit | deny }
{ communityNumber | asCommunityNumber | no-export | no-advertise | local-as |
internet } [ communityNumber | asCommunityNumber | no-export | no-advertise |
local-as | internet ]*

no ip community-list communityLisName [ { permit | deny }
[ { communityNumber | asCommunityNumber | no-export | no-advertise | local-as | internet
} ] [ communityNumber | asCommunityNumber | no-export | no-advertise | local-as |
internet ]* ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a community list for BGP and controls access to it. The **no** version removes the community list, including all list entries.

- Options**
- *communityLisName*—Name of a community list; a string of up to 32 characters; identifies one or more permit or deny groups of communities; used for standard community lists
  - permit—Permits access for a matching condition
  - deny—Denies access for a matching condition
  - *communityExpression*—Regular expression that matches the community
  - *communityNumber*—Community number in the range 1–4294967295
  - *asCommunityNumber*—Community number in the format *AA:NN*, where *AA* is a number that identifies the autonomous system and *NN* is a number that identifies the community within the autonomous system.
  - no-export—Specifies that BGP does not advertise this route outside a BGP confederation boundary
  - no-advertise—Specifies that BGP does not advertise this route to any peer (internal or external)
  - local-as—Specifies that BGP does not advertise this route to external peers; sometimes known as the no-export-subconfed community
  - internet—Specifies the Internet community
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## ip debounce-time

---

**Syntax**    `ip debounce-time [ vrf vrfName ] period`  
              `no ip debounce-time [ vrf vrfName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines the minimum time an IP interface must be in a given state—for example, up or down—before being reported. The **no** version removes the debounce time.

**Options**

- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
- *period*—Interval in the range 0–60000 milliseconds

**Mode**    Global Configuration, Interface Configuration



## ip demux-type da-prefix

---

**Syntax** [ no ] ip demux-type da-prefix

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that a subscriber interface will demultiplex traffic using destination addresses. The **no** version restores the default situation, in which the subscriber interface demultiplexes traffic using source addresses.

**Mode** Interface Configuration

## ip description

---

**Syntax**    ip description *name*  
              no ip description

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description or an alias to a static IP interface or subinterface. If no IP interface currently exists, then a static IP interface is automatically created on the current layer 2 interface and the description is applied to that static IP interface. You cannot assign a profile to a layer 2 interface that has a static interface configured above it. Use the show ip interface command to display the text description. The **no** version removes the description or alias.



.....  
**NOTE:** This command is replacing the **description** command to assign a description to a static IP interface. The **description** command may be removed completely from Interface Configuration mode in a future release.  
.....

**Options**    • *name*—Name for the static IP interface; string of up to 256 characters

**Mode**    Interface Configuration, Subinterface Configuration

---

## ip destination-prefix

---

**Syntax** [ no ] ip destination-prefix *ipAddress* *ipAddressMask* deny

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures a subscriber interface or a primary IP interface that is enabled for dynamic creation of subscriber interfaces to demultiplex traffic with the specified destination address. On the ERX1440 Broadband Services Router or the E320 router, you can configure up to 1024 subnets for static subscriber interfaces per primary IP interface when each subnet has a variable network mask that is less than /32. The number of subnets identifying a single route (/32) is still limited by the global maximum of 16,000 hosts per line module. The **no** version removes the association between the interface and the specified destination address.

- Options**
- *ipAddress*—Destination IP address that the router uses to identify packets for this interface
  - *ipAddressMask*—Network mask for associated IP subnet
  - deny—Filters packets matching this command

**Mode** Interface Configuration, Subinterface Configuration

## ip dhcp-capture

---

**Syntax**    ip dhcp-capture { all | receive | transmit } [ priority { low | high } ]  
              no ip dhcp-capture { all | receive | transmit }

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Configures the E Series router to capture and log DHCP packet information for an interface. By default, DHCP packet information is not captured. The **no** version restores the default behavior.

- Options**
- all—Captures received and transmitted packets
  - receive—Captures received packets
  - transmit—Captures transmitted packets
  - low—Captured packets arrive with low priority; the default priority
  - high—Captured packets arrive with high priority

**Mode**    Interface Configuration

## ip dhcp-external auto-configure

---

**Syntax** [ no ] ip dhcp-external auto-configure [ agent-circuit-identifier ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**agent-circuit-identifier** keyword added in JunosE Release 7.3.0.

**Description** Configures the E Series router to automatically create the user's DSI. This command is specific to a virtual router. The **no** version disables the autoconfigure feature.

**Options**

- **agent-circuit-identifier**—Creates dynamic subscriber interfaces built over dynamic VLANs that are based on the agent-circuit-id option (suboption 1) of the option 82 field in DHCP messages.

**Mode** Global Configuration

## ip dhcp-external disregard-giaddr-next-hop

---

**Syntax** [ no ] ip dhcp-external disregard-giaddr-next-hop

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the DHCP external application to disregard the giaddr in packets destined for the DHCP server when the next hop for a subscriber's access route is determined. The **no** version returns to the default, in which DHCP external uses the giaddr to determine the next hop.

**Mode** Global Configuration

## ip dhcp-external recreate-subscriber-interface

---

**Syntax** [ no ] ip dhcp-external recreate-subscriber-interface

**Release Information** Command introduced in JunosE Release 9.2.0.

**Description** Configures the DHCP external server application to delete and re-create the existing dynamic subscriber interface after a bound DHCP client extends its IP address lease by restarting the DHCP discovery process on its primary IP interface instead of by initiating the DHCP renewal process on its dynamic subscriber interface. This command is specific to a virtual router. The **no** version restores the default behavior, which preserves the dynamic subscriber interface after a bound client restarts the discovery process on its primary IP interface.

**Mode** Global Configuration

**Related Documentation**

- Preservation of Dynamic Subscriber Interfaces with DHCP External Server Overview
- Configuring DHCP External Server to Control Preservation of Dynamic Subscriber Interfaces

## ip dhcp-external server-address

---

**Syntax** [ no ] ip dhcp-external server-address *ipAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures a DHCP server that is used to determine which DHCP packets are monitored. The **no** version removes the DHCP server.

**Options**

- *ipAddress*—IP address of the external DHCP server; you can specify a maximum of four servers

**Mode** Global Configuration



## ip dhcp-external server-sync

---

**Syntax** [ no ] ip dhcp-external server-sync

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates subscriber state information based on lease renewals when the external DHCP server is unsynchronized with the E Series router. The **no** version disables this feature.

**Mode** Global Configuration

## ip dhcp-local auth domain

---

**Syntax** [ no ] ip dhcp-local auth domain *domainName*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies a domain name for a username that is locally configured for a DHCP standalone mode client. In standalone mode, the locally configured username is presented to AAA in an authentication request. The **no** version removes the domain name.

**Options** • *domainName*—String of 1–32 characters used as the domain name

**Mode** Global Configuration

## ip dhcp-local auth include

---

**Syntax** [ no ] ip dhcp-local auth include { circuit-identifier | circuit-type | mac-address | option82 | virtual-router-name | radius-dhcp-options }

**Release Information** Command introduced in JunosE Release 7.1.0.  
**radius-dhcp-options** keyword added in JunosE Release 11.3.0.

**Description** Includes optional information as part of the locally configured username for a DHCP standalone mode client. In standalone mode, the username is presented to AAA in an authentication request. The **no** version removes the specified optional information.

- Options**
- circuit-identifier—Specifies the circuit identifier of the interface on which the DHCP client's request was received
  - circuit-type—Specifies the circuit type of the interface on which the DHCP client's request was received
  - mac-address—Specifies the DHCP client's MAC address
  - option82—Specifies the DHCP client's Option 82 value
  - virtual-router-name—Specifies the DHCP local server's virtual router name
  - radius-dhcp-options—Specifies the DHCP options returned from the RADIUS server

**Mode** Global Configuration

## ip dhcp-local auth password

---

**Syntax** [ no ] ip dhcp-local auth password *password*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Assigns a password used to authenticate a locally configured DHCP standalone mode client. In DHCP standalone mode, the password is presented to AAA in an authentication request. The **no** version removes the password.

**Options** • *password*—String of 1–32 characters used as the password

**Mode** Global Configuration

## ip dhcp-local auth user-prefix

---

**Syntax** [ no ] ip dhcp-local auth user-prefix *userNamePrefix*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies a user prefix for a username that is locally configured for a DHCP standalone mode client. In DHCP standalone mode, the username is presented to AAA in an authentication request. The **no** version removes the user prefix.

**Options**

- *userNamePrefix*—String of 1–32 characters used as the prefix for a locally configured username

**Mode** Global Configuration

## ip dhcp-local auto-configure agent-circuit-identifier

---

**Syntax** [ no ] ip dhcp-local auto-configure agent-circuit-identifier

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Configures the DHCP local server to support the creation of dynamic subscriber interfaces built over dynamic VLANs that are based on the agent-circuit-id option (suboption 1) of the option 82 field in DHCP messages. This command is specific to a virtual router. The **no** version disables the autoconfigure feature.

**Mode** Global Configuration

## ip dhcp-local cable-modem

---

**Syntax** [ no ] ip dhcp-local cable-modem dhcp-server *ipAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the IP address of the external DHCP server to which the DHCP local server will relay DHCP messages from cable modems. The **no** version removes the cable modem configuration.



**NOTE:** This command is deprecated and might be removed completely in a future release. Use the **set dhcp vendor-option** command to configure the vendor class identifier option to match the string used by cable modems to replace the function of this command.

**Options** • *ipAddress*—IP address of the cable modem DHCP server

**Mode** Global Configuration

## ip dhcp-local excluded-address

---

**Syntax** [ no ] ip dhcp-local excluded-address *ipAddressStart* *ipAddressStop*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies IP addresses that the DHCP local server should not supply from the default address pool because those addresses are already used by devices on the subnet. The **no** version allows the DHCP local server to supply the specified IP address.

- Options**
- *ipAddressStart*—Single IP address or start of the range of IP addresses that the DHCP local server should not supply
  - *ipAddressStop*—End of the range of IP addresses that the DHCP local server should not supply

**Mode** Global Configuration



## ip dhcp-local limit

**Syntax** ip dhcp-local limit  
 { atm | ethernet | pos | vlan | interface *InterfaceType* *InterfaceSpecifier* } *value*  
 no ip dhcp-local limit [ atm | ethernet | pos | vlan  
 | interface *InterfaceType* *InterfaceSpecifier* ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**interface** keyword and *interfaceType* and *interfaceSpecifier* variables added in JunosE Release 7.1.0.  
**pos** keyword added in JunosE Release 10.0.0.

**Description** Specifies the maximum number of IP addresses that the DHCP local server can supply to each VPI/VCI, VLAN, Ethernet subnetwork, or POS access interface, or to a particular interface or subinterface. The **no** version restores the default address limit value, 48000.

- Options**
- atm—Specifies the limit for VPIs and VCIs
  - ethernet—Specifies the limit for Ethernet subnets
  - pos—Specifies the limit for POS access interfaces
  - vlan—Specifies the limit for VLANs
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *value*—Maximum number of leases, in the range 0–96000; default is 48000

**Mode** Global Configuration

## ip dhcp-local pool

---

**Syntax** [ no ] ip dhcp-local pool { *poolName* | default }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Accesses DHCP Local Pool Configuration mode. The DHCP local server uses pool names other than default to maintain configuration information for subscribers to a particular domain. The **no** version prevents the DHCP local server from supplying IP addresses from the specified pool.

- Options**
- *poolName*—Name of the address pool
  - default—Specifies the default address pool

**Mode** Global Configuration

## ip dhcp-local snmpTraps

---

**Syntax** [ no ] ip dhcp-local snmpTraps

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables DHCP local server SNMP traps. The **no** version disables DHCP local server SNMP traps.

**Mode** Global Configuration

## ip dhcp-local unique-client-ids

---

**Syntax** [ no ] ip dhcp-local unique-client-ids

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Configures the method that DHCP local server uses when it receives a DHCP DISCOVER or REQUEST packet from a client ID or hardware address that matches the client ID or hardware address of a currently bound client on another subnet or subinterface.

Use this command to specify that DHCP local server uses a method that considers a request from a client with a duplicate client ID or hardware address to be from a roaming client—the server then terminates the currently bound client's existing lease and assigns a new address to the requesting client.

The **no** version restores the default behavior, in which DHCP local server uses the DHCP client's subnet or subinterface to differentiate between two clients that use the same client ID or hardware address—the DHCP server processes requests in the normal manner.



.....  
**NOTE:** This command replaces the **ip dhcp-local inhibit-roaming** command, which has been removed from the CLI.  
.....

**Mode** Global Configuration

## ip dhcp-server

---

**Syntax**    `ip dhcp-server dhcpServerAddress [ adminStatus ]`  
`no ip dhcp-server [ dhcpServerAddress [ adminStatus ] ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Adds the IP address of a single DHCP server to the list of DHCP servers from which the router can request addresses to allocate to remote users. A maximum of five DHCP servers can be specified. The **no** version removes the specified DHCP server or removes all DHCP servers from the list.

- Options**
- *dhcpServerAddress*—IP address of the DHCP server that will allocate addresses for remote users
  - *adminStatus*—One of the following options:
    - *disable*—Disables the DHCP server
    - *drain*—Drains the DHCP server

**Mode**    Global Configuration

## ip directed-broadcast

---

**Syntax** [ no ] ip directed-broadcast

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables translation of directed broadcast to physical broadcasts. The **no** version disables the function.

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

## ip disable-forwarding

---

**Syntax** [ no ] ip disable-forwarding

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables forwarding of packets on the SRP Ethernet interface to maintain router performance. The **no** version enables forwarding of packets on the SRP Ethernet interface. You see an error message if you try to set this command for interfaces other than the SRP Ethernet interface.

**Mode** Interface Configuration, Subinterface Configuration

## ip domain-lookup

---

**Syntax** [ no ] ip domain-lookup [ transit-virtual-router *vrName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Without the **transit-virtual-router** option, enables the router to query the configured DNS name servers when it needs an IP hostname-to-IP address translation. With the **transit-virtual-router** option, configures a virtual router to use the name servers you configured for another virtual router. The **no** version without the **transit-virtual-router** option restores the default situation, in which the router does not query the DNS server. The **no** version with the **transit-virtual-router** option stops a virtual router from using the same name servers you configured for another virtual router.

**Options**

- *vrName*—Name of the virtual router that has the DNS configuration you want to use for a second virtual router

**Mode** Global Configuration



## ip domain-name

---

**Syntax** [ no ] ip domain-name *domainName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a default domain name for the clients that a name resolver serves. The **no** version deletes the domain name; that is, the domain name will no longer be appended to hostnames in the static host table.

**Options** • *domainName*—Default domain name for your hosts

**Mode** Global Configuration

## ip dos-protection-group

---

**Syntax**    ip dos-protection-group *groupName*  
              no ip dos-protection-group

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches an IP denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## ip dvmrp

---

**Syntax** [ no ] ip dvmrp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Activates DVMRP on an interface. The **no** version removes DVMRP from an interface.

**Mode** Interface Configuration

## ip dvmrp accept-filter

---

**Syntax** [ no ] ip dvmrp accept-filter *listName1* [ *distance* ] neighbor-list *listName2*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Filters incoming DVMRP reports in accordance with a standard IP access list. The **no** version disables the filter.

- Options**
- *listName1*—Name of the IP access list. If the name is 0, the interface accepts all destinations. You can specify a simple or extended access list; with an extended access list you can specify an address and a subnet mask.
  - *distance*—Number in the range 0–255; default value is 0; the distance associated with the DVMRP route when the router determines the RPF interface for the source of a multicast packet
  - *listName2*—Name of an access list containing the neighbors from which the router will accept reports. If the name is 0, the interface accepts destinations from all its neighbors.

**Mode** Interface Configuration

## ip dvmrp announce-filter

---

**Syntax**    ip dvmrp announce-filter *listName*  
              no ip dvmrp announce-filter

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a list of DVMRP routes that the router will advertise on an interface. The **no** version restores the default situation, in which the router advertises all known routes on the interface.

**Options**    • *listName*—Name of the IP access list that specifies the DVMRP routes that the router will advertise on the interface. You can specify a simple or extended access list; with an extended access list you can specify an address and a subnet mask.

**Mode**    Interface Configuration

## ip dvmrp auto-summary

---

**Syntax**    [ no ] ip dvmrp auto-summary

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Summarizes routes automatically on an interface. By default, automatic summarization is enabled. The **no** version disables automatic summarization.

**Mode**    Interface Configuration

## ip dvmrp disable

---

**Syntax** [ no ] ip dvmrp disable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables DVMRP on an interface without removing the DVMRP configuration. The **no** version reenables the DVMRP configuration on a disabled interface.

**Mode** Interface Configuration

## ip dvmrp metric-offset

---

**Syntax** [ no ] ip dvmrp metric-offset { in | out } [ *increment* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Adjusts the number of hops associated with routes passing through an interface. This action indicates that the route is more efficient or less efficient than an alternative route. The **no** version restores the default values.

- Options**
- **in**—Increments the number of hops for a DVMRP route advertised in incoming DVMRP reports. If you do not specify a key word, this option is the default.
  - **out**—Increments the number of hops for a DVMRP route advertised in outgoing DVMRP reports
  - ***increment***—Number of hops associated with this interface; default value is 1 for incoming reports and 0 for outgoing reports.

**Mode** Interface Configuration



## ip dvmrp route-hog-notification

---

**Syntax** [ no ] ip dvmrp route-hog-notification [ *limit* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the number of DVMRP routes that the router can record before it generates a system log warning message. The **no** version restores the default setting, 10,000 routes.

**Options** • *limit*—Number in the range 0–2147483647

**Mode** Global Configuration

## ip dvmrp route-limit

---

**Syntax** [ no ] ip dvmrp route-limit [ *limit* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Limits the number of routes that the router can advertise on each interface. The default value is 7000. The **no** version removes the limit for the number of routes that the router can advertise on each interface.

**Options** • *limit*—Number of routes that the router can advertise

**Mode** Global Configuration

## ip dvmrp summary-address

---

**Syntax** [ no ] ip dvmrp summary-address *ipAddress* *mask* [ metric *cost* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Advertises a DVMRP summary address on the interface. The **no** version stops the advertising of a summary address on an interface.

- Options**
- *ipAddress*—Summary address
  - *mask*—Subnet mask
  - *cost*—Cost associated with this summary address

**Mode** Interface Configuration

## ip dvmrp unicast-routing

---

**Syntax** [ no ] ip dvmrp unicast-routing

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the exchange of DVMRP unicast routes on an interface not owned by DVMRP. The **no** version disables the exchange of DVMRP unicast routes on an interface not owned by DVMRP.

**Mode** Interface Configuration

## ip dynamic-interface-prefix

---

**Syntax**    ip dynamic-interface-prefix [ vrf *vrfName* ] *prefix*  
              no ip dynamic-interface-prefix [ vrf *vrfName* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the prefix for the names of dynamic shared IP interfaces created for overlapping BGP/MPLS VPNs. The **no** version restores the default prefix, **dyn**.

- Options**
- *vrfName*—Name of the VRF in which the shared interface is created; a string of 1–32 alphanumeric characters
  - *prefix*—String of 1–10 alphanumeric characters

**Mode**    Global Configuration

## ip explicit-path

---

**Syntax** { ip | mpls } explicit-path { name *name* | identifier *number* } [ enable | disable ]  
no { ip | mpls } explicit-path { name *name* | identifier *number* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an explicit path by name or ID number and also enables or disables the explicit path. The **no** version deletes the explicit path.

- Options**
- ip—Specifies alternative keyword for compatibility with non-E Series implementations
  - mpls—Specifies JunosE MPLS implementation
  - *name*—Name for the explicit path; string of up to 20 characters
  - *number*—Number identifying the explicit path in the range 1–65535
  - enable—Reenables the explicit path that was previously disabled on the virtual router; to prevent a partially configured explicit path from being used, do not enable it until you have finished configuring or modifying the path
  - disable—Disables the explicit path that was previously enabled on the virtual router

**Mode** Global Configuration

## ip extcommunity-list

**Syntax** ip extcommunity-list *listName* { permit | deny } *extendedCommunity*  
 [ *extendedCommunity* ]\*

no ip extcommunity-list *listName* [ { permit | deny } *extendedCommunity*  
 [ *extendedCommunity* ]\* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an extended-community (extcommunity) list to be referenced in a route map. The **no** version deletes the extcommunity.

- Options**
- *listName*—Name of the extended-community list
  - permit—Permits membership in the extended community for matching conditions
  - deny—Denies membership in the extended community for matching conditions
  - *extendedCommunity*—Extended community specified in the format:  
 {rt | soo } { *ASN:nn* | *ipAddress:nn* }
    - rt—Specifies a route-target community; consists of one or more routers that can receive a set of routes advertised by BGP that carry the extended-community attribute
    - soo—Specifies a Site-of-Origin community; consists of one or more routers that injects a set of routes into BGP that carry the extended-community attribute
    - *ASN:nn*—Identifies the extended community by a 16-bit autonomous system number followed by a 32-bit integer
    - *ipAddress:nn*—Identifies the extended community identified by an IP address followed by a 16-bit integer
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## ip fallback global

---

**Syntax** [ no ] ip fallback global

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables secondary routing table lookup for an interface in a virtual router forwarding table of the parent (global) virtual router if the initial route lookup on a VRF is unsuccessful. The **no** version discontinues secondary routing table lookup.

**Mode** VRF Configuration



## ip filter-options all

---

**Syntax** [ no ] ip filter-options all

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables filtering of packets with IP options on an interface. IP options filtering is disabled by default. The **no** version disables filtering of packets with IP options.

**Mode** Interface Configuration, Profile Configuration

**Related Documentation**

- Enabling IP Options Filtering

## ip flow-aggregation cache

---

**Syntax** [ no ] ip flow-aggregation cache [ as | destination-prefix | prefix | protocol-port | source-prefix ]

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates an aggregation cache and accesses Flow Cache Configuration mode. The **no** version removes the aggregation cache and its configuration.

- Options**
- **as**—Specifies autonomous system aggregation
  - **destination-prefix**—Specifies destination prefix aggregation
  - **prefix**—Specifies prefix aggregation
  - **protocol-port**—Specifies protocol port aggregation
  - **source-prefix**—Specifies source prefix aggregation

**Mode** Flow Cache Configuration, Global Configuration

## ip flow-cache entries

---

**Syntax** ip flow-cache entries *cacheEntries*  
no ip flow-cache entries

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Limits the number of entries in the flow cache (for all line modules in the router). The **no** version sets the number of entries back to its default value.

**Options**

- *cacheEntries*—Number of cache entries allowed for all line modules in the router in the range 1024–524288; default value is 65536

**Mode** Global Configuration

## ip flow-cache timeout

---

**Syntax** ip flow-cache timeout { active *activeTimer* | inactive *inactiveTimer* }  
no ip flow-cache timeout { active | inactive }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines the J-Flow activity or inactivity timers. The **no** version restores the default value of each timer.

- Options**
- *activeTimer*—Value of activity timer in the range 0–60 minutes; default value is 30
  - *inactiveTimer*—Value of inactivity timer in the range 10–600 seconds; default value is 15

**Mode** Global Configuration

## ip flow-export

**Syntax** [ no ] ip flow-export { *hostName* | *ipAddress* } *udpPort* version 5  
[ peer-as | origin-as ]

[ no ] ip flow-export destination { *hostName* | *ipAddress* } *udpPort*

[ no ] ip flow-export source *interfaceType* *interfaceSpecifier*

[ no ] ip flow-export version 5 [ peer-as | origin-as ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines J-Flow export values for the IP flow. The **no** version removes the export setting.

- Options**
- *hostName*—Name of the remote host for outgoing export datagrams
  - *ipAddress*—IP address of the export destination host
  - *udpPort*—UDP port number
  - version 5—Specifies version 5 of the J-Flow statistical information
  - peer-as—Exports peer-as information
  - origin-as—Exports origin-as information
  - destination—Specifies destination for outgoing export datagrams
  - source—Specifies source interface for outgoing export datagrams
  - *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Global Configuration

## ip flow-sampling-mode packet-interval

---

**Syntax**    ip flow-sampling-mode packet-interval *intervalValue*  
              no ip flow-sampling-mode packet-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines the sampling interval for an interface that is running J-Flow. Even though each flow is sampled, the flow sample is not necessarily cached because of system constraints. The **no** version returns the sampling interval to the default value.



.....  
**NOTE:** For interfaces on the ES2 10G LM with either the ES2-S1 GE-8 IOA or the ES2-S2 10GE PR IOA on E120 routers and E320 routers, J-Flow adjusts the maximum sampling interval to 8,388,608 (decimal equivalent of 0x800000) and changes the sampling interval to the closest integer that is a power of two and that is less than or equal to the configured value.  
.....

**Options**    • *intervalValue*—Sampling interval, in the range 1–4000000000 packets; default value is 4000000000

**Mode**    Global Configuration

## ip flow statistics

---

**Syntax** [ no ] ip flow statistics

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables J-Flow statistics. The **no** version disables J-Flow statistics.

**Mode** Global Configuration

## ip ftp source-address

---

**Syntax**    ip ftp source-address *sourceAddress*  
              no ip ftp source-address [ *sourceAddress* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies an operational interface by IP address as the source interface in FTP packets sent via the router's FTP client. The **no** version restores the source address in the FTP packets to that on which the FTP connection is made.

**Options**    • *sourceAddress*—Source IP address

**Mode**    Global Configuration



## ip ftp source-interface

---

**Syntax**    ip ftp source-interface *interfaceType interfaceSpecifier*  
              no ip ftp source-interface [ *interfaceType interfaceSpecifier* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Identifies an interface by type and location as the source interface in FTP packets sent via the router's FTP client. The **no** version restores the source address in the FTP packets to that on which the FTP connection is made.

**Options**    • *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)  
              • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Global Configuration

## ip gratuitous-arps

---

**Syntax** ip gratuitous-arps [ *numberOfMessages* ]

no ip gratuitous-arps

**Release Information** Command introduced in JunosE Release 12.3.0.

**Description** Enables the transmission of Gratuitous Address Resolution Protocol (GARP) messages and specifies the number of GARP packets to be transmitted at intervals of 10 seconds. By default, three GARP packets are transmitted when you create an IP interface or the interface state changes from the down state to the up state. Regardless of whether transmission of GARP packets is disabled or the number of packets to be sent is modified using this command, one GARP is always sent for each virtual address of a VRRP interface and three GARPs are always sent when a failover occurs to the secondary link of the redundant port on GE-2 and GE-HDE line modules that are paired with GE-2 SFP I/O modules, 2xGE APS I/O SFP modules, and GE-2 APS I/O SFP modules, with physical link redundancy. The **no** version disables the transmission of GARP messages.

**Options**

- *numberOfMessages*—Number of GARP packets that are transmitted at an interval of 10 seconds in the range 1-3; default value is 3

**Mode** Interface Configuration

**Related Documentation**

- Configuring the Transmission of GARP Packets
- Transmission of GARP Packets Overview

## ip-hint

---

**Syntax** ip-hint { enable | disable }  
no ip-hint

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** When enabled, the E Series router preallocates an IP address for the remote (B-RAS) user before calling authentication. The address is then passed as a hint in the authentication request to the RADIUS server. The **no** version disables the feature.

**Options**

- enable—Specifies the feature
- disable—Disables the feature; this is the default setting

**Mode** Domain Map Configuration

## ip http

---

**Syntax** [ no ] ip http

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Creates the HTTP local server. The **no** version deletes the HTTP local server.

**Mode** Global Configuration

## ip http access-class

---

**Syntax**    ip http access-class *listName*  
              no ip http access-class

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Specifies the standard IP access list that identifies the subscribers who are authorized to connect to the HTTP local server. The **no** version removes the association between the access list and the HTTP local server.

**Options**    • *listName*—Name of the access list

**Mode**    Global Configuration

## ip http max-connection-time

---

**Syntax** ip http max-connection-time *seconds*

no ip http max-connection-time

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Specifies the maximum time that the HTTP local server maintains an inactive connection. The **no** version restores the default time.

**Options**

- *seconds*—Either 0 (unlimited) or the number of seconds in the range 3–7200; default value is 30 seconds

**Mode** Global Configuration

## ip http port

---

**Syntax**    ip http port *portNumber*

no ip http port

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Specifies the port on which the HTTP local server receives connection attempts. The **no** version restores the default port number.

**Options**    • *portNumber*—Number of the port, in the range 0–65535; the default is port 80

**Mode**    Global Configuration

## ip http redirectUrl

---

**Syntax** ip http redirectUrl *url* [ preserveOriginalUrl ]

no ip http redirectUrl

**Release Information** Command introduced in JunosE Release 7.2.0.  
**preserveOriginalUrl** keyword added in JunosE Release 12.3.0.

**Description** Specifies the URL to which a subscriber's initial Web browser session is redirected, enabling initial provisioning and service selection for the subscriber. The **no** version removes the redirection action.

- Options**
- *url*—Name of the URL; 230 characters maximum
  - preserveOriginalUrl —Enables the preservation of the subscriber's originally requested URL

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

**Related Documentation**

- Configuring the Preservation of the Original URL During Redirection of Subscriber Sessions



## ip http same-host-limit

---

**Syntax**    ip http same-host-limit *maxConnections*  
              no ip http same-host-limit

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Specifies the maximum number of connections that can exist between one IP address and the HTTP local server. The **no** version restores the default number of allowed connections.

**Options**    • *maxConnections*—Maximum number of connections allowed, in the range 0–1000; the default is 3

**Mode**    Global Configuration

## ip http server

---

**Syntax** [ no ] ip http server

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Enables the HTTP local server. The **no** version disables the HTTP local server.

**Mode** Global Configuration

Mode Global Configuration

## ip igmp

---

**Syntax**    [ no ] ip igmp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables IGMP on an interface, and sets the IGMP version to IGMPv2. The **no** version disables IGMP on an interface.

**Mode**    Interface Configuration, Profile Configuration

## ip igmp access-group

---

**Syntax**    ip igmp access-group *accessListName*

             no ip igmp access-group

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Restricts hosts on this subnet to joining multicast groups on the specified IP access list. The **no** version removes the association with the specified access list and allows hosts on the subnet to join any multicast group.

**Options**    • *accessListName*—Name of the access list; a string of up to 32 characters

**Mode**    Interface Configuration, Profile Configuration

## ip igmp access-source-group

---

**Syntax**    ip igmp access-source-group *accessListName*  
              no ip igmp access-source-group

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Restricts hosts on this subnet to membership in those source-groups (also known as “channels” ) permitted by the specified IP access list. The **no** version removes any access list restriction.

**Options**    • *accessListName*—Name of the access list; a string of up to 32 characters

**Mode**    Interface Configuration, Profile Configuration

## ip igmp apply-oif-map

---

**Syntax**    ip igmp apply-oif-map *mapName*  
              no ip igmp apply-oif-map

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Applies the specified outgoing interface (OIF) map to the current interface. The **no** version removes the outgoing interface map association from the interface.

**Options**    • *mapName*—Name of the OIF map

**Mode**    Interface Configuration, Profile Configuration

## ip igmp explicit-tracking

---

**Syntax** [ no ] ip igmp explicit-tracking [ disable-if-igmp-v2-detected ]

**Release Information** Command introduced in JunosE Release 8.2.0.

**Description** Enables explicit host tracking for IGMP interfaces. The **no** version disables explicit host tracking on the interface or with the **disable-if-igmp-v2-detected** keyword reverts to the default explicit host tracking.

**Options**

- **disable-if-igmp-v2-detected**—Disables explicit host tracking if IGMP V2 hosts detected on IGMP V3 interfaces

**Mode** Interface Configuration, Profile Configuration



## ip igmp group limit

---

**Syntax**    ip igmp group limit *groupLimit*  
              no ip igmp group limit

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Limits the number of IGMP groups that an interface can accept. The **no** version restores the default situation, in which there is no limit to the number of IGMP groups that the interface accepts.

**Options**    • *groupLimit*—Maximum number of IGMP groups that an interface can accept in the range 0–64,000

**Mode**    Interface Configuration, Profile Configuration

## ip igmp immediate-leave

---

**Syntax** [ no ] ip igmp immediate-leave

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Removes an interface immediately when the router receives an leave group membership message from the host associated with this interface. The **no** version restores the default situation, in which the router issues query messages to multicast groups and removes an interface if the associated host does not return a group membership report within a certain length of time.



.....  
**CAUTION:** Issue this command only on IGMPv2 interfaces to which one IGMP client is connected. Do not issue this command to interfaces to which more than one IGMP client is connected.  
.....

**Mode** Interface Configuration, Profile Configuration

## ip igmp last-member-query-interval

---

**Syntax** ip igmp last-member-query-interval *tenthsOfaSecond*

no ip igmp last-member-query-interval

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies in tenths of a second the maximum time the router waits for a response after sending a last member query. The router sends a last member query when it receives an IGMPv2 leave message or an IGMPv3 state change report. The **no** version restores the default value, 10 tenths of a second (1 second).

**Options**

- *tenthsOfaSecond*—Time interval between receipt of an IGMP leave message and sending out of a query in the range 1–254 tenths of a second. Using a lower value allows members to leave groups more quickly.

**Mode** Interface Configuration, Profile Configuration

## ip igmp oif-map

---

**Syntax** [ no ] ip igmp oif-map *mapName* { *interfaceType* *interfaceSpecifier* | self }  
[ *groupPrefix* [ *sourcePrefix* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an outgoing interface (OIF) map. The **no** version removes an outgoing interface map attribute or the entire outgoing interface map.

- Options**
- *mapName*—Name of the OIF map
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - self—Specifies that the multicast outgoing interface is the same as IGMP join interface
  - *groupPrefix*—Group prefix in the form *ipAddress/maskLength*
  - *sourcePrefix*—Source prefix in the form *ipAddress/maskLength*

**Mode** Global Configuration

## ip igmp promiscuous

---

**Syntax** ip igmp promiscuous { on | off }

no ip igmp promiscuous

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the specified interface to accept IGMP reports from hosts on any subnet. The **no** version specifies that an IGMP interface should use the Router Configuration mode setting (see the [igmp promiscuous](#) command) to determine from which subnets it can accept IGMP reports.

**Options**

- on—Enables the interface to accept IGMP reports from hosts on any subnet
- off—Allows the interface to accept IGMP reports only from hosts on subnets associated with this interface

**Mode** Interface Configuration, Profile Configuration

## ip igmp-proxy

---

**Syntax** [ no ] ip igmp-proxy [ version { 2 | 3 } ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IGMP proxy on an interface and specifies the version. Version 2 is enabled by default. The **no** version disables IGMP proxy for an interface.

- Options**
- 2—Specifies IGMP proxy version 2
  - 3—Specifies IGMP proxy version 3

**Mode** Interface Configuration

---

## ip igmp-proxy unsolicited-report-interval

---

**Syntax** ip igmp-proxy unsolicited-report-interval *tenths-of-a-second*  
no ip igmp-proxy unsolicited-report-interval

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies how often the upstream interface should transmit unsolicited reports. This command has no effect on interfaces other than the upstream value. The **no** version transmits unsolicited reports using the default value, 400 tenths of a second.



.....  
**NOTE:** Issue this command only on the upstream interface. Otherwise, this command will have no effect.  
.....

**Options** • *tenths-of-a-second*—Time interval at which the interface transmits unsolicited reports

**Mode** Interface Configuration

## ip igmp-proxy V1-router-present-time

---

**Syntax**    ip igmp-proxy V1-router-present-time *seconds*  
              no ip igmp-proxy V1-router-present-time

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies how long the router assumes that there is an IGMPv1 querier router on the subnet after the router receives an IGMP V1 query on this interface. The **no** version restores the default value, 10 seconds.

**Options**    • *seconds*—Time for which the router assumes that there is an IGMPv1 querier router on the subnet after the router receives an IGMP V1 query on this interface

**Mode**    Interface Configuration



---

## ip igmp querier

---

**Syntax** [ no ] ip igmp querier

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the interface will act as a querier when you configure IGMPv1 on an interface; this is the default behavior. The **no** version specifies that this interface will not issue query packets.



.....  
**NOTE:** This command is valid only for interfaces on configured with IGMPv1.  
.....

**Mode** Interface Configuration, Profile Configuration

## ip igmp querier-timeout

---

**Syntax**    ip igmp querier-timeout *seconds*  
              no ip igmp querier-timeout

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time that the interface waits before declaring itself as the querier. The **no** version restores the default value, twice the query interval.

**Options**    • *seconds*—Time interval between the last query from the previous router and the first query from this interface

**Mode**    Interface Configuration, Profile Configuration

## ip igmp query-interval

---

**Syntax**    ip igmp query-interval *seconds*  
              no ip igmp query-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets how often the router sends IGMP host-query packets from this interface. The **no** version restores the default value, 125 seconds.

**Options**    • *seconds*—Polling interval in the range 0–65535 seconds

**Mode**    Interface Configuration, Profile Configuration

## ip igmp query-max-response-time

---

**Syntax** ip igmp query-max-response-time *tenthsOfaSecond*

no ip igmp query-max-response-time

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the period in tenths of a second during which the host is expected to respond to an IGMP query. IGMP version 2 includes this value in IGMP query messages sent out on the interface. You cannot set this value on interfaces running IGMP version 1. The **no** version restores the default value, 100 tenths of a second (10 seconds).

**Options**

- *tenthsOfaSecond*—Time interval between receipt of an IGMP query and the response; in the range 1–254 tenths of a second.

**Mode** Interface Configuration, Profile Configuration

## ip igmp robustness

---

**Syntax**    ip igmp robustness *numberOfMessages*  
              no ip igmp robustness

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of times that the router sends IGMP group-specific queries before declaring a group to no longer have any members on an interface. The **no** version restores the default value, 3.

**Options**    • *numberOfMessages*—Number of times that the router sends IGMP group-specific queries in the range 1–4

**Mode**    Interface Configuration, Profile Configuration

## ip igmp ssm-map enable

---

**Syntax** [ no ] ip igmp ssm-map enable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SSM mapping on the router. SSM mapping statically assigns sources to IGMPv1 and IGMPv2 groups. You must use SSM mapping for IGMPv1 and IGMPv2 hosts to interoperate with PIM SSM. SSM mapping allows the router to use a statically configured list to translate (\*G) memberships to (S,G) memberships. The **no** version disables the SSM map.

**Mode** Privileged Exec, User Exec

## ip igmp ssm-map static

---

**Syntax** [ no ] ip igmp ssm-map static *accessListName* *sourceAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an access list and source address for use in SSM mapping. SSM mapping statically assigns sources to IGMPv1 and IGMPv2 groups. You must use SSM mapping for IGMPv1 and IGMPv2 hosts to interoperate with PIM SSM. SSM mapping allows the router to use a statically configured list to translate (\*,G) memberships to (S,G) memberships. The **no** version removes the SSM map association.

**Options**

- *accessListName*—Name of the access control list
- *sourceAddress*—Address of the source

**Mode** Privileged Exec, User Exec

## ip igmp static-exclude

---

**Syntax** [ no ] ip igmp static-exclude *sourceAddress groupAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that an interface not handle multicast traffic for one or more (S,G) combinations. The **no** version removes the (S,G) exclusion from the interface.

**Options**

- *sourceAddress*—Address of the source
- *groupAddress*—Address of the group

**Mode** Interface Configuration, Profile Configuration



## ip igmp static-group

---

**Syntax** [ no ] ip igmp static-group *groupAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns an interface to handle all multicast traffic for a group. The interface sets no timers for this group. The **no** version removes the group from the interface.

**Options** • *groupAddress*—Address of the group

**Mode** Interface Configuration, Profile Configuration

## ip igmp static-include

---

**Syntax** [ no ] ip igmp static-include *sourceAddress* *groupAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns an interface to handle multicast traffic for one or more (S,G) combinations. The **no** version removes the (S,G) association from the interface.

**Options**

- *sourceAddress*—Address of the source
- *groupAddress*—Address of the group

**Mode** Interface Configuration, Profile Configuration

## ip igmp version

---

**Syntax**    ip igmp version { 3 | 2 | 1 | passive }  
              no ip igmp version

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the IGMP version for the interface. The **no** version restores the default value, IGMPv2.

- Options**
- 3—Specifies IGMP version 3
  - 2—Specifies IGMP version 2
  - 1—Specifies IGMP version 1
  - passive—Configures a mapped OIF as a passive interface with only multicast-data-forwarding capability

**Mode**    Interface Configuration, Profile Configuration

## ip ignore-df-bit

---

**Syntax** [ no ] ip ignore-df-bit

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the router ignores the don't-fragment bit (DF) if present in the IP header of packets crossing the configured interface; the router then fragments packets even if the bit is present. The **no** version restores the default behavior, which is to consider the DF bit before fragmenting.



.....  
**NOTE:** You can also use RADIUS VSA [26-70] to configure the router's DF bit support. The action configured by the RADIUS VSA takes precedence over the action configured by this command. For more information, see *JunosE Broadband Access Configuration Guide*.  
.....

**Mode** Interface Configuration, Profile Configuration

## ip inactivity-timer

---

**Syntax** [ no ] ip inactivity-timer *inactiveTime*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures an inactivity timer. IP polls the dynamic interface at the configured interval to determine whether the interface was active during the interval. Inactive interfaces are deleted only when the period of inactivity is equal to or greater than the configured value. The **no** version disables the timer.

**Options** • *inactiveTime*—Length of time in the range 0–63335 minutes; a value of 0 specifies that dynamically created subscriber interfaces are not deleted

**Mode** Interface Configuration, Profile Configuration

## ip initial-sequence-preference

---

**Syntax**    ip initial-sequence-preference *preference*  
              no ip initial-sequence-preference

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Configures the warm restart replay preference for an IP interface after a high availability switchover. The **no** version restores the default value.

**Options**    • *preference*—Preference value, 0 or 1; 1 indicates highest preference; default value is 0

**Mode**    Subinterface Configuration

## ip interface

---

**Syntax**    no ip interface

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    This command has only a **no** version. See the no ip interface command for a complete description.

**Mode**    Interface Configuration, Subinterface Configuration

## ip irdp

---

**Syntax** [ no ] ip irdp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables ICMP Router Discovery Protocol processing on an interface. The **no** version disables IRDP routing.

**Mode** Interface Configuration, Subinterface Configuration



## ip local alias

---

**Syntax** ip local alias aliasName pool-name *poolName*

[ no ] ip local alias aliasName

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an alias for a local address pool. The **no** version deletes the alias name.

- Options**
- *aliasName*—Text string in the range 1–16 characters that defines an alias name for the local address pool
  - *poolName*—Text string in the range 1–16 characters that is the name of the local address pool

**Mode** Global Configuration

## ip local pool

---

**Syntax** [ no ] ip local pool *name* [ *startIpAddress* [ *endIpAddress* ] ]  
[ warning *highUtilization* *abatedUtilization* ] [ snmpTrap ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the pool name, the starting address, the ending address, group name, the utilization threshold, and the SNMP trap flag. The **no** version deletes a local pool.

- Options**
- *name*—Text string in the range 1–16 characters that defines the name of the local address *pool*
  - *startIpAddress*—Starting IP address in the local address pool
  - *endIpAddress*—Ending IP address in the local address pool
  - warning—Specifies one of the following utilization warnings:
    - *highUtilization*—High utilization value; a number in the range 1–100; default value is 85
    - *abatedUtilization*—Abated utilization value; a number in the range 1–100; default value is 75
  - snmpTrap—Enables SNMP pool utilization traps

**Mode** Global Configuration

## ip local pool snmpTrap

---

**Syntax** [ no ] ip local pool *name* snmpTrap

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SNMP pool utilization traps. The **no** version disables SNMP pool utilization traps.

**Options**

- *name*—Text string in the range 1–16 characters that defines the name of the local address *pool*

**Mode** Global Configuration

## ip local pool warning

---

**Syntax**    ip local pool *name* warning *highUtilization* *abatedUtilization* [ snmpTrap ]  
              no ip local pool *name* warning [ *highUtilization* *abatedUtilization* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Identifies the warning threshold values. The **no** version resets the thresholds to their default values.

- Options**
- *name*—Text string in the range 1–16 characters that defines the name of the local address *pool*
  - *highUtilization*—High utilization value; a number in the range 1–100; default value is 85
  - *abatedUtilization*—Abated utilization value; a number in the range 1–100; default value is 75
  - snmpTrap—Enables snmp pool utilization traps

**Mode**    Global Configuration

## ip local shared-pool

---

**Syntax**    `ip local shared-pool localPoolName dhcpPoolName`  
              `no ip local shared-pool localPoolName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a shared local address pool that shares addresses from the specified DHCP local server address pool in the same virtual router. The **no** version deletes the shared local address pool.

- Options**
- *localPoolName*—Text string in the range 1–16 characters that defines the name of the shared local address pool that obtains addresses from a DHCP local server address pool.
  - *dhcpPoolName*—Text string in the range 1–64 characters that defines the name of the DHCP local address pool that provides addresses to the shared local address pool.

**Mode**    Global Configuration

## ip mac-validate

---

**Syntax** ip mac-validate [ strict | loose ]

no ip mac-validate

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables MAC address validation on a per interface basis. When MAC address validation is enabled, the router checks the entry in the MAC validation table that corresponds to the IP source address of an incoming packet. The MAC source address of the packet must match the MAC source address of the table entry for the router to forward the packet. The **no** version disables the feature.

**Options**

- **strict**—Prevents transmission of IP packets that do not reside in the validation table
- **loose**—Allows IP packets to pass through even though the packets do not have entries in the validation table; only packets that have matching IP–MAC pair entries in the table are validated; this is the default setting

**Mode** Interface Configuration

## ip mask-reply

---

**Syntax** [ no ] ip mask-reply

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables ICMP netmask reply. The **no** version disables the feature.

**Mode** Interface Configuration, Subinterface Configuration

## ip match-policy-list

---

**Syntax** [ no ] ip match-policy-list *policyList* { permit | deny }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an IP policy list and launches the policy list configuration mode. The **no** version deletes the policy list.

- Options**
- *policyList*—Name of the policy list
  - permit—Defines the policy list as a permit
  - deny—Defines the policy list as a deny

**Mode** Global Configuration



## ip mirror

**Syntax** `ip mirror mirrorInterfaceType mirrorInterfaceSpecifier`  
`[ analyzerInterfaceType analyzerInterfaceSpecifier [ next-hop nextHop ] ]`

`no ip mirror mirrorInterfaceType mirrorInterfaceSpecifier`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the specified interface to mirror all IP ingress and egress traffic, and directs the mirrored traffic to an analyzer interface. The **no** version disables mirroring on the interface.



**NOTE:** This command is deprecated and might be removed completely in a future release. The function provided by this command has been replaced by the updated packet mirroring feature and the **ip policy** command used with the **secure-input** and **secure-output** keywords.

- Options**
- *mirrorInterfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *mirrorInterfaceSpecifier*—Particular interface that performs the interface mirroring function; see [Interface Types and Specifiers on page 5](#)
  - *analyzerInterfaceType*—Interface type
  - *analyzerInterfaceSpecifier*—Particular interface used as the analyzer interface; if omitted, the virtual router's default analyzer interface is used
  - *nextHop*—Next-hop IP address to the remote analyzer host; required if the analyzer interface is a shared medium, such as Ethernet

**Mode** Global Configuration

**Related Documentation**

- [Configuring CLI-Based Mirroring](#)

## ip mobile home-agent

---

**Syntax** ip mobile home-agent [ care-of-access *acl* ] [ lifetime *lifetimeSeconds* ]  
[ replay *replaySeconds* ] [ reverse-tunnel-off ]  
  
no ip mobile home-agent

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Configures the Mobile IP home agent on a virtual router. Issuing this command does not affect existing parameters such as lifetime, replay value, or care-of-access ACL for any mobile node's existing binding. The new parameters take effect only upon each re-registration or new registration. For example, configuring a shorter lifetime does not cause an existing binding to be removed prematurely, but the new lifetime value is used only upon re-registration by a mobile node so that both the mobile node and the home agent are informed of the newly negotiated value. The **no** version disables the home agent service on the virtual router.



**NOTE:** The values for lifetime, replay, and care-of access configured per mobile host by using the **ip mobile host** command override the values configured by using the **ip mobile home-agent** command.

- Options**
- *acl*—Name of the access control list applied to the care-of-access, which restricts access for foreign agents or networks. You can override this care-of-access ACL with other ACLs for specific host mobile nodes. By default, the router does not apply a care-of-access ACL
  - *lifetimeSeconds*—Maximum number of seconds, in the range 5–65535, during which registration requests are established; default value is 36,000 seconds. The maximum lifetime configured for specific mobile nodes can override this lifetime value
  - *replaySeconds*—Number of seconds, in the range 1–255, by which a registration request can exceed the home agent configured time value; default value is 7 seconds
  - reverse-tunnel-off—Disables reverse tunneling support by the home agent, which denies T bit registration requests. By default, reverse tunneling is enabled on the router. When you modify support for reverse tunnels, the modification takes effect only for subsequently accepted registration requests

**Mode** Global Configuration

## ip mobile host

**Syntax** `ip mobile host { nai { user@realm | @realm | @ } | ipAddress } [aaa] [care-of-access acl] [lifetime lifetimeSeconds]`

`no ip mobile host { nai { user@realm | @realm | @ } | ipAddress }`

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Configures the mobile node on a virtual router with an optional host network access identifier (NAI) address or the home address (IP address of the home agent). You can specify either the **nai** keyword or a non-zero home address (IP address of the mobile node). If the AAA server does not provide all configuration information, a local lookup retrieves the configuration information by either matching the NAI registration request or the home address registration request. The **no** version deletes the configuration of the mobile node on the virtual router.

- Options**
- *user@realm*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *user@realm*, where *realm* is the domain name
  - *@realm*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *@realm*, where *realm* is the domain name
  - *@*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *@*
  - *ipAddress*—IP address of the home agent
  - *aaa*—Causes the router to use the AAA server to validate registration requests and to obtain configuration and security association information
  - *acl*—Name of the access control list applied to the care-of-access, which restricts access for foreign agents or networks. You can override this care-of-access ACL with other ACLs for specific host mobile nodes. By default, the router does not apply a care-of-access ACL
  - *lifetimeSeconds*—Maximum number of seconds during which the registration requests are established; default value is 36,000 seconds. The maximum lifetime configured for specific mobile nodes can override this lifetime value

**Mode** Global Configuration

## ip mobile profile

---

**Syntax** [ no ] ip mobile profile *profileName*

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Configures or associates a preconfigured interface profile with the home agent in a virtual router. You must configure a mobile profile for every virtual router in which the home agent exists. The profile parameters determine the interface characteristics for Mobile IP signaling. The **no** version removes the profile configuration from the virtual router.

**Options**

- *profileName*—Name of the profile associated with the home agent for Mobile IP signaling in a virtual router

**Mode** Global Configuration

## ip mobile secure foreign-agent

**Syntax** ip mobile secure foreign-agent *ipAddress* spi *spi* key { hex *hexKeyVal* | ascii *asciiKeyVal* }  
[ replay timestamp within *seconds* ] [ algorithm { hmac-md5 | keyed-md5 } ]

no ip mobile secure foreign-agent *ipAddress* spi *spi* key { hex *hexKeyVal* |  
ascii *asciiKeyVal* }

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Configures the security associations for a foreign agent by specifying a security parameter index (SPI) value and an authentication key. You can specify the interval within which a registration request can exceed the home agent configured time value by specifying the **replay timestamp within** keyword. The **no** version deletes the security associations for the specified foreign agent on the virtual router.

- Options**
- *ipAddress*—IP address of the foreign agent
  - *spi*—Security parameter index (SPI) value, a specific 4-octet hexadecimal number, in the range 0x100–0xFFFFFFFF, that authenticates inbound requests and permits authentication for outbound registration requests
  - *hexKeyVal*—128-bit hexadecimal number, in the range 0x0–0xFFFFFFFFE, that specifies the authentication key for a specific security association
  - *asciiKeyVal*—128-bit alphanumeric value, up to a maximum of 16 characters, that specifies the authentication key for a specific security association
  - *seconds*—Number of seconds, in the range 1–255, by which a registration request can exceed the home agent configured time value; default value is 7 seconds
  - hmac-md5—Specifies the authentication algorithm for Mobile IP messages, default value is hmac-md5
  - keyed-md5—Specifies the authentication algorithm for Mobile IP messages

**Mode** Global Configuration

## ip mobile secure host

**Syntax** ip mobile secure host { nai { *user@realm* | *@realm* | *@* } | *ipAddress* } spi *spi*  
 key { hex *hexKeyVal* | ascii *asciiKeyVal* } [ replay timestamp within *seconds* ]  
 [ algorithm { hmac-md5 | keyed-md5 } ]

no ip mobile secure host { nai { *user@realm* | *@realm* } | *ipAddress* } spi *spi*  
 key { hex *hexKeyVal* | ascii *asciiKeyVal* }

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Configures the security associations for a mobile node. You can configure the security associations for a mobile node only after configuring a corresponding host configuration for the mobile node, and only if you have not configured the AAA service on the virtual router. You can specify the interval within which a registration request can exceed the home agent configured time value by specifying the **replay timestamp within** keyword. The **no** version deletes the security associations for the specified host on the virtual router.



**NOTE:** If you delete a mobile node host by using the **no ip mobile host** command, all security associations that you configured for this host are deleted.

- Options**
- *user@realm*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *user@realm*, where *realm* is the domain name
  - *@realm*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *@realm*, where *realm* is the domain name
  - *@*—Name of the user for the mobile node specification when the **nai** keyword is specified, in the format *@*
  - *ip Address*—IP address of the foreign agent
  - *spi*—Security parameter index (SPI) value, a specific 4-octet hexadecimal number, in the range 0x100–0xFFFFFFFF, that authenticates inbound requests and permits authentication for outbound registration requests
  - *hexKeyVal*—128-bit hexadecimal number, in the range 0x0–0xFFFFFFFFFE, that specifies the authentication key for a specific security association
  - *asciiKeyVal*—128-bit alphanumeric value, up to a maximum of 16 characters, that specifies the authentication key for a specific security association
  - *seconds*—Number of seconds, in the range 1–255, by which a registration request can exceed the home agent configured time value; default value is 7 seconds
  - *hmac-md5*—Specifies the authentication algorithm for Mobile IP messages, default value is *hmac-md5*
  - *keyed-md5*—Specifies the authentication algorithm for Mobile IP messages

**Mode** Global Configuration

## ip mpls forwarding-mode label-switched

---

**Syntax** [ no ] ip mpls forwarding-mode label-switched

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Generates a label for each different FEC that a BGP route points to in a BGP/MPLS VPN. The **no** version restores the default, generating a single label for all BGP routes sent from a given VRF.



.....

**NOTE:** For some types of routes, the router always generates a per-VRF label, regardless of the status of this command. See *Creating labels per FEC* in the *JunosE BGP and MPLS Configuration Guide*, for details.

.....

**Mode** VRF Configuration



## ip mtu

---

**Syntax**    [ no ] ip mtu [ *mtuSize* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum transmission unit size of IP packets sent on an interface. The **no** version restores the default value.

**Options**    • *mtuSize*—Maximum number of packet transmissions permitted on an interface; in the range 160–10240; default value is 0, which means that the router takes the value from a lower protocol layer

**Mode**    Interface Configuration, Profile Configuration, Subinterface Configuration

## ip multicast admission-bandwidth-limit

---

**Syntax** [ no ] ip multicast admission-bandwidth-limit *limitValue*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies multicast admission bandwidth (in kilobits per second) for a given interface. The **no** version removes the admission bandwidth limit.

**Options**

- *limitValue*—Maximum admission bandwidth (in kilobits per second) permitted on an interface; default value is 0, which disables the limit

**Mode** Interface Configuration, Profile Configuration

## ip multicast ioa-packet-replication

---

**Syntax**    ip multicast ioa-packet-replication *interfaceType interfaceSpecifier*  
              no ip multicast ioa-packet-replication

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Enables IPv4 hardware multicast packet replication on port 8 of a high-density Ethernet I/O module or IOA. The **no** version disables hardware multicast packet replication.

**Options**    • *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)  
              • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Interface Configuration

## ip multicast-routing

---

**Syntax** [ no ] ip multicast-routing

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IP multicast routing on the router. The **no** version disables IP multicast routing on the router.

**Mode** Global Configuration

## ip multicast-routing bandwidth-map

---

**Syntax**    ip multicast-routing bandwidth-map *routeMapName*  
              no ip multicast-routing bandwidth-map

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables the QoS adjust function on the router. The **no** version disables the QoS adjust function on the router.

**Options**    • *routeMapName*—Name of the route map you want to use for the bandwidth map

**Mode**    Global Configuration

## ip multicast-routing disable-rpf-check

---

**Syntax**    `ip multicast-routing disable-rpf-check ipAccessList`  
              `no ip multicast-routing disable-rpf-check`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Disables RPF checks for the (S,G) pairs in the specified access list. The **no** version restores the default situation, in which the router performs RPF checks for all (S,G) pairs.

**Options**    • *ipAccessList*—Name of the IP access list that specifies the (S,G) pairs

**Mode**    Global Configuration

## ip multicast-routing permanent-mroute

---

**Syntax**    ip multicast-routing permanent-mroute *accessListName*  
              no ip multicast-routing permanent-mroute

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies that newly created mroutes that match the specified access list do not get timed out. The **no** version of this command prevents any new mroutes from becoming permanent. However, it does not remove any existing permanent mroutes. To remove existing permanent mroutes, use the **clear ip mroute** command.

**Options**    • *accessListName*—Name of the IP access list that contains the mroutes

**Mode**    Global Configuration

## ip multipath round-robin

---

**Syntax** [ no ] ip multipath round-robin

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies round-robin as the mode for ECMP load sharing on an interface. The **no** version restores the default value, hashed.

**Mode** Subinterface Configuration



## ip name-server

---

**Syntax** [ no ] ip name-server *serverIpAddress* [ *serverIpAddress* ]\*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a DNS name server that the router can query for hostname-to-IP address resolution. The **no** version deletes the name server.

**Options**

- *serverIpAddress*—IP or IPv6 address of a DNS name server
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## ip nat

---

**Syntax** [ no ] ip nat { inside | outside }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Marks interfaces that participate in NAT translation as residing on the inside or the outside network. The **no** version unmarks the interface so that it does not participate in NAT translation.

- Options**
- **inside**—Specifies that the interface resides on the inside (private) portion of the network. The inside portion of the network uses nonroutable IP addresses.
  - **outside**—Specifies that the interface resides on the outside (public) portion of the network. The outside portion of the network (for example, the Internet) uses routable legitimate addresses.

**Mode** Interface Configuration, Profile Configuration

---

## ip nat inside source list

---

**Syntax**    `ip nat inside source list accessListName pool poolName [ overload ]`  
`no ip nat inside source list accessListName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates dynamic translation rules that are applied to a source address when routing a packet from the inside network to the outside network, and for translating the destination address when a packet returns from the outside network to the inside network. The **no** version removes the dynamic translation rule.



.....  
**NOTE:** This command does not remove any dynamic translations from the translation table.  
.....

- Options**
- *accessListName*—Name of the access list that you want to use for this dynamic translation
  - *poolName*—Name of the NAT IP address pool that contains addresses you want to use when translating matched access list addresses
  - **overload**—Specifies that the translation process create extended translation table entries (IP address, protocol, and port values)

**Mode**    Global Configuration

## ip nat inside source static

---

**Syntax** [ no ] ip nat inside source static *localIpAddress* *globalIpAddress*  
[ no ] ip nat inside source static { tcp | udp } *localIpAddress* *localPort* *globalIpAddress* *globalPort*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates static translations for a source address when routing a packet from the inside network to the outside network, and “untranslates” the destination address when a packet returns from the outside network to the inside network. The **no** version removes the static translation and purges the associated translations from the translation table.

- Options**
- tcp—Indicates a TCP port
  - udp—Indicates a UDP port
  - *localIpAddress*—Inside local address
  - *localPort*—Inside local TCP or UDP port
  - *globalIpAddress*—Inside global address
  - *globalPort* —Inside global TCP or UDP port

**Mode** Global Configuration

---

## ip nat outside source list

---

**Syntax**    `ip nat outside source list accessListName pool poolName`  
`no ip nat outside source list accessListName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates dynamic translation rules that are applied to a source address when routing a packet from the outside network to the inside network, and used for translating the destination address when a packet returns to the outside network from the inside network. The **no** version removes the dynamic translation rule.



.....  
**NOTE:** This command does not remove any dynamic translations from the translation table.  
.....

- Options**
- *accessListName*—Name of the access list that you want to use for this dynamic translation
  - *poolName*—Name of the NAT IP address pool that contains addresses you want to use when translating matched access list addresses

**Mode**    Global Configuration

## ip nat outside source static

---

**Syntax** [ no ] ip nat outside source static *globalIpAddress localIpAddress*

[ no ] ip nat outside source static { tcp | udp } *globalIpAddress globalPort localIpAddress localPort*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Translates the source address when routing a packet from the outside network to the inside network, and “untranslates” the destination address when a packet travels from the inside network to the outside network. The **no** version removes the static translation and purges the associated translations from the translation table.

- Options**
- tcp—Indicates a TCP port
  - udp—Indicates a UDP port
  - *globalIpAddress*—Inside global address
  - *globalPort*—Inside global TCP or UDP port
  - *localIpAddress*—Inside local address
  - *localPort*—Inside local TCP or UDP port

**Mode** Global Configuration

## ip nat pool

**Syntax** `ip nat pool name [startIpAddress endIpAddress] {netmask networkMask | prefix-length length}`

`no ip nat pool name`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an address pool from which the NAT router obtains an address when performing a dynamic translation. You can create address pools with either a single range or multiple, nonoverlapping ranges. The **no** version removes the NAT pool.



**NOTE:** The router will not allow you to remove a pool that has allocations outstanding. Before removing this type of pool, you must remove the dynamic translation, clear any outstanding translations, and then remove the pool.



**CAUTION:** Specifying a range in “single line” mode from the CLI replaces all other ranges. You cannot specify a range in this mode if any existing ranges are in use. To add additional ranges, issue this command to access IP NAT Pool Configuration mode.

- Options**
- *name*—Name of the address pool; 32 alphanumeric characters maximum
  - *startIpAddress*—First IP address (inclusive) in the NAT pool range you are creating; omitting this value in the command (along with *endIpAddress*) launches the IP NAT Pool Configuration mode, in which you can enter multiple, discontinuous ranges
  - *endIpAddress*—Last IP address (inclusive) in the NAT pool range you are creating; omitting this value in the command (along with *startIpAddress*) accesses IP NAT Pool Configuration mode, in which you can enter multiple, discontinuous ranges
  - *ipAddressMask*—Subnet mask for any NAT pool ranges you specify
  - *length*—Length of the network prefix; the number of bits masking the base address that results in the address that you want to match

**Mode** Global Configuration

## ip nat translation

---

**Syntax** ip nat translation { timeout | udp-timeout | dns-timeout | tcp-timeout | first-timeout | icmp-timeout | gre-timeout } *seconds*

no ip nat translation { timeout | udp-timeout | dns-timeout | tcp-timeout | first-timeout | icmp-timeout | gre-timeout }

**Release Information** Command introduced before JunosE Release 7.1.0.  
**gre-timeout** keyword added in JunosE Release 7.3.0.

**Description** Changes or disables translation timeouts, per virtual router, for existing and newly created translations in the translation table. All timeouts for this command support a range of 1–2147483 seconds (about 25 days). The **no** version enables the timer using its default value.



**NOTE:** GRE translations are used as optimizations to discard GRE traffic. You can use the **gre-timeout** keyword to control GRE aging timeout, even though we do not support NAT for GRE. The GRE aging timer has no effect on any simple translations GRE might use.

- Options**
- **timeout**—Sets aging time for dynamic translations (except for overloaded translations); default value is 86400 seconds (24 hours)
  - **udp-timeout**—Sets aging time for UDP protocol translations; default value is 300 seconds (5 minutes)
  - **dns-timeout**—Sets aging time for DNS protocol translations (port 53 on TCP or UDP); default value is 60 seconds
  - **tcp-timeout**—Sets aging time for TCP protocol translations; default value is 86400 seconds (24 hours)
  - **first-timeout**—Sets aging time for TCP connections terminated with RST or FIN flags; default value is 60 seconds
  - **icmp-timeout**—Sets aging time for ICMP protocol translations; default value is 300 seconds (5 minutes)
  - **gre-timeout**—Sets aging time for GRE protocol translations; default value is 300 seconds (5 minutes)
  - **seconds**—Number of seconds before the router removes an unused NAT table entry

**Mode** Global Configuration



## ip nat translation max-entries

---

**Syntax** ip nat translation max-entries *maximumEntryNumber*  
no ip nat translation max-entries

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the maximum number of translation entries per virtual router (that is, address bindings, not translation rules) that the translation table can contain in global configuration mode. The **no** version removes the configured limit.

**Options**

- *maximumEntryNumber*—Maximum number of translation entries in the current virtual router; default value is no limit

**Mode** Global Configuration

## ip nfs

---

**Syntax**    ip nfs { source-address *ipAddress* |source-interface *interfaceType interfaceSpecifier* }  
              no ip nfs { source-address | source-interface }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the E Series interface that the current virtual router uses to exchange NFS communications with an NFS server. The **no** version prevents this interface from sending or receiving NFS communications for the current virtual router.

- Options**
- *ipAddress*—IP address of an E Series interface that sends and receives NFS communications
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Global Configuration

## ip nfs host

---

**Syntax**    `ip nfs host hostName [ user userID [ group groupID ] ]`  
              `no ip nfs host hostName`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a remote host as an NFS server for the current virtual router. The **no** version disassociates the NFS server from the virtual router.

- Options**
- *hostName*—Name of the remote host
  - *userID*—User identity in the range 0–4294967295 that a user must enter to connect to the remote host; default value is 2001
  - *groupID*—Group identity in the range 0–4294967295 that the user must enter to connect to the remote host; default value is 100

**Mode**    Global Configuration

## ip ospf authentication-key

---

**Syntax**    ip ospf authentication-key *authKey*  
              no ip ospf authentication-key

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a password used by neighboring routers that are using OSPF simple password authentication. The **no** version deletes the password.

**Options**    • *authKey*—Password; string of up to 8 characters

**Mode**    Interface Configuration, Subinterface Configuration

## ip ospf authentication message-digest

---

**Syntax** [ no ] ip ospf authentication message-digest

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the authentication mode for the interface is MD5. The **no** version sets authentication for the interface to none, but leaves any configured MD5 key intact.

**Mode** Interface Configuration, Subinterface Configuration

## ip ospf authentication-none

---

**Syntax** ip ospf authentication-none

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that no authentication is to be used for the interface. The **no** version has no effect.

**Mode** Interface Configuration, Subinterface Configuration

## ip ospf bfd-liveness-detection

**Syntax** ip ospf bfd-liveness-detection [ minimum-interval *minInterval* ]  
 [ minimum-receive-interval *minRecInterval* ]  
 [ minimum-transmit-interval *minTransInterval* ] [ multiplier *multValue* ]  
 no ip ospf bfd-liveness-detection

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables BFD (bidirectional forwarding detection) on an interface running OSPFv2 and defines BFD values to be negotiated between OSPFv2 neighbors for detection of IP data path failures. The **no** version disables BFD on the OSPFv2 interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *minInterval*—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode** Interface Configuration, Subinterface Configuration

## ip ospf cost

---

**Syntax**    ip ospf cost *intfCost*  
              no ip ospf cost

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a cost metric for an interface. Used in the calculation of the SPF routing table. The **no** version resets the path cost to the default.

**Options**    • *intfCost*—Link-state metric cost; number in the range 0–65535; default value is 10

**Mode**    Interface Configuration, Subinterface Configuration



## ip ospf dead-interval

---

**Syntax** ip ospf dead-interval *deadInterval*

no ip ospf dead-interval

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the time period during which the router's neighbors do not see hello packets before they declare the router to be down. The **no** version resets the dead interval to its default.

**Options** • *deadInterval*—Number in the range 0–2147483647 seconds; default value is 40 seconds

**Mode** Interface Configuration, Subinterface Configuration

## ip ospf hello-interval

---

**Syntax**    ip ospf hello-interval *helloInterval*  
              no ip ospf hello-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval between hello packets that the router sends on the interface. The **no** version resets the hello interval to its default.

**Options**    • *helloInterval*—Number in the range 1–65535 seconds; default value is 10 seconds

**Mode**    Interface Configuration, Subinterface Configuration

## ip ospf message-digest-key md5

**Syntax**    `ip ospf message-digest-key keyID md5 [ 0 | 8 ] msgDigestKey`  
               `no ip ospf message-digest-key keyID`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables OSPF MD5 authentication and configures the MD5 key. The **no** version deletes an MD5 key.



**NOTE:** If all the MD5 keys have been deleted, the authentication type is still MD5, but you must configure MD5 keys.

To disable MD5 authentication for the interface, use the **ip ospf authentication-none** command.

To display the password only in encrypted text, use the **service password-encryption** command.

- Options**
- *keyID*—Key identifier in the range 1–255
  - md5—Specifies use of the MD5 algorithm
  - 0—Indicates the *msgDigestKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *msgDigestKey* is entered in encrypted form (ciphertext)
  - *msgDigestKey*—OSPF password; string of up to 16 alphanumeric characters

**Mode**    Interface Configuration, Subinterface Configuration

## ip ospf network

---

**Syntax**    ip ospf network { broadcast | non-broadcast | point-to-point }  
              no ip ospf network

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the OSPF network type to something other than the default for the network medium. The **no** version restores the default value for the medium.

- Options**
- broadcast—Sets the network type to broadcast
  - non-broadcast—Sets the network type to NBMA
  - point-to-point—Sets the network type to point-to-point

**Mode**    Interface Configuration, Subinterface Configuration

## ip ospf priority

---

**Syntax**    ip ospf priority *intfPriority*  
              no ip ospf priority

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the router priority. Used in determining the designated router for the particular network. This designation applies only to multiaccess networks. Every broadcast and nonbroadcast multiaccess network has a designated router. A higher priority value for an OSPF interface signifies a greater likelihood of that router becoming the designated router. A value of 1 means that the router has the least chance of becoming a designated router. The **no** version restores the default value.

**Options**    • *intfPriority*—Priority value, an 8-bit number in the range 1–255; default value is 1

**Mode**    Interface Configuration, Subinterface Configuration

## ip ospf retransmit-interval

---

**Syntax**    ip ospf retransmit-interval *retransInterval*  
              no ip ospf retransmit-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the time between LSA retransmissions for the interface when an acknowledgment for the LSA is not received. The **no** version restores the default value.

**Options**    • *retransInterval*—Number in the range 0–3600 seconds; default value is 5 seconds

**Mode**    Interface Configuration, Subinterface Configuration

## ip ospf shutdown

---

**Syntax** [ no ] ip ospf shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables OSPF on an interface. The **no** version enables OSPF on the interface.

**Mode** Interface Configuration, Subinterface Configuration

## ip ospf transmit-delay

---

**Syntax**    ip ospf transmit-delay *transmDelay*  
              no ip ospf transmit-delay

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the estimated time it takes to transmit a link-state update packet on the interface. The **no** version restores the default value.

**Options**    • *transmDelay*—Link-state transmit delay, a number in the range 0–3600 seconds; default value is 1 second

**Mode**    Interface Configuration, Subinterface Configuration



---

## ip pim

---

**Syntax** In Interface Configuration mode:  
[ no ] ip pim [ dense-mode | sparse-mode | sparse-dense-mode ]

In Profile Configuration mode:  
[ no ] ip pim [ sparse-mode | sparse-dense-mode ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 8.2.0.

**Description** In Interface Configuration mode, enables PIM on an interface. In Profile Configuration mode, enables a PIM interface for a dynamic profile. The **no** version disables PIM on an interface.

- Options**
- dense-mode—Enables PIM in dense mode
  - sparse-mode—Enables PIM in sparse mode
  - sparse-dense-mode—Enables PIM in sparse-dense mode

**Mode** Interface Configuration, Profile Configuration

## ip pim bfd-liveness-detection

---

**Syntax**    ip pim bfd-liveness-detection [ minimum-interval *minInterval* |  
              [ minimum-receive-interval *minRecInterval* ]  
              [ minimum-transmit-interval *minTransInterval* ] ] [ multiplier *multValue* ]  
  
              no ip pim bfd-liveness-detection

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Enables BFD (bidirectional forwarding detection) on an interface running PIM and defines BFD values to be negotiated between PIM neighbors for detection of IP data path failures. You can change the BFD liveness detection parameters at any time without stopping or restarting the existing session; BFD automatically adjusts to the new parameter value. However, no changes to BFD parameters take place until the values resynchronize with each neighbor. The **no** version disables BFD on the PIM interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *minInterval*—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote neighbor multiplies by the local router's negotiated transmit interval to determine the remote neighbor's BFD liveness detection interval. The calculated BFD liveness detection interval can be different on each neighbor. The multiplier value is roughly equivalent to the number of packets that can be missed before the BFD session is declared to be down. The number ranges from 1–25 and the default value is 3

**Mode**    Interface Configuration

## ip pim bsr-candidate

**Syntax** ip pim bsr-candidate *interfaceType interfaceSpecifier*  
 [ *hashMaskLen* [ *priority priority* ] ] [ *period bootstrapPeriod* ]

no ip pim bsr-candidate

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a router as a bootstrap router (BSR) candidate. The **no** version disables the router BSR candidacy.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#). The autoRP announcement messages will contain the IP address for this interface.
  - *hashMaskLen*—Length (up to 32 bits) of the hash mask length field sent in BSMs that the router originates. This mask is combined with the group address before the router calls the hash function. For example, specifying a value of 24 limits the group address to the first 24 bits. The default value is 30 bits
  - *priority*—Value in the range 0–255 of the BSR-Priority field of BSMs that the router originates. In the BSR election process, the BSR with the higher priority is preferred. If the priority values are equal, the router with the higher IP address becomes the BSR. The default value is 0
  - *bootstrapPeriod*—Interval in the range 1–65535 seconds at which the BSR sends bootstrap messages; default value is 60 seconds

**Mode** Global Configuration

## ip pim data-mdt

---

**Syntax** [ no ] ip pim data-mdt

**Release Information** Command introduced in JunosE Release 8.2.0.

**Description** Activates data MDTs and enters IP PIM Data MDT Configuration mode. The **no** version deactivates data MDTs.

**Mode** Global Configuration

## ip pim dr-priority

---

**Syntax**    `ip pim dr-priority priority`  
`no ip pim dr-priority`

**Release Information**    Command introduced in JunosE Release 9.0.0.  
Router Configuration mode added in JunosE Release 10.0.0.

**Description**    Assigns a priority for the interface to be selected as the designated router. An interface with a higher priority value is preferred as a designated router over an interface with a lower priority value. In Interface Configuration mode, the **no** version restores the value that is specified in Router Configuration mode. If the designated router priority is not specified in Router Configuration mode, then the default value of 1 is restored.



**NOTE:** You cannot configure the designated router priority on PIM dense mode interfaces.

**Options**    • *priority*—Value in the range 1–254; default value is 1.

**Mode**    Interface Configuration, Router Configuration

## ip pim group-address-pool

---

**Syntax**    `ip pim group-address-pool poolName groupAddressMinimum groupAddressMaximum`  
              `no ip pim group-address-pool poolName`

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures PIM group address pools from which data MDT group addresses are allocated. The **no** version removes the group address pool.

**Options**

- *poolName*—Name of the group address pool
- *groupAddressMinimum*—Minimum value in the group address range
- *groupAddressMaximum*—Maximum value in the group address range

**Mode**    Global Configuration

## ip pim join-filter

---

**Syntax**    ip pim join-filter *accessListName*

             no ip pim join-filter

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                             Profile Configuration mode added in JunosE Release 8.2.0.

**Description**    Specifies an extended access list that you want this PIM interface to use as a join filter. If an interface-level filter exists, it takes precedence over the global-level filter. The **no** version removes the filter association.

**Options**    • *accessListName*—Name of the access list that you want this interface to use as a PIM join filter; a string of up to 32 alphanumeric characters

**Mode**    Global Configuration, Interface Configuration, Profile Configuration

## ip pim join-prune-interval

---

**Syntax**    ip pim join-prune-interval *interval*  
              no ip pim join-prune-interval

**Release Information**    Command introduced in JunosE Release 10.0.0.

**Description**    Specifies the time interval at which the router sends the PIM join/prune message to the upstream RPF neighbor. In Interface Configuration mode, the **no** version restores the value that is specified in Router Configuration mode. If the message interval is not specified in Router Configuration mode, then the default value of 60 seconds is restored.



.....  
**NOTE:** You cannot configure the designated router priority on PIM dense mode interfaces.  
.....

**Options**    • *interval*—Interval in the range 10–210 seconds at which the router sends the PIM join/prune message; the default value is 60 seconds.

**Mode**    Interface Configuration, Router Configuration



## ip pim query-interval

---

**Syntax** ip pim query-interval *queryTime*

no ip pim query-interval

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 8.2.0.

**Description** Specifies how often the router sends PIM router query messages from this interface. The **no** version specifies the default time interval, 30 seconds.

**Options**

- *queryTime*—Interval in the range 0–210 seconds at which the router sends PIM router query messages from this interface

**Mode** Interface Configuration, Profile Configuration

## ip pim rp-address

---

**Syntax** [ no ] ip pim rp-address *ipAddress* [ *ipAccessList* ] [ override ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a static PIM group-to-RP mapping. The **no** version clears the mapping from this interface.

- Options**
- *ipAddress*—IP address of the router you want to designate as an RP router
  - *ipAccessList*—Name of the IP access list that specifies which multicast groups use this RP
  - **override**—Specifies that this static RP mapping has priority over group-to-RP mappings learned by auto-RP

**Mode** Global Configuration

## ip pim rp-candidate

**Syntax** `ip pim rp-candidate interfaceType interfaceSpecifier [ group-list accessListName ] [ hold-time holdTime ] [ priority priority ] [ interval interval ]`

`no ip pim rp-candidate interfaceType interfaceSpecifier`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a router as a rendezvous point (RP) router candidate. The **no** version stops the router from being an RP candidate.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#). The autoRP announcement messages will contain the IP address for this interface.
  - *accessListName*—Access list containing the set of group prefixes supported by this C-RP. If no group-list is specified, the default value is the entire multicast address range.



**NOTE:** Because BSR has no mechanism for distributing negative entries, you should not configure negative access-list entries (also called deny access-list entries).

- *holdTime*—Amount of time in the range 1–65535 seconds that the BSR keeps an RP in its C-RP list if the BSR does not receive a C-RP advertisement message; default value is 150 seconds
- *priority*—Priority field value in the range 0–255 that the C-RP sends to the BSR in C-RP advertisement messages. In the RP election process, the RP with the lower priority value is preferred; default value is 192
- *interval*—Interval in the range 1–65535 seconds at which the C-RP sends advertisement messages to the BSR; default value is 60 seconds

**Mode** Global Configuration

## ip pim send-rp-announce

---

**Syntax**    `ip pim send-rp-announce interfaceType interfaceSpecifier scope ttl`  
              `[ group-list ipAccessList ] [ interval seconds ]`

`no ip pim send-rp-announce interfaceType interfaceSpecifier [ scope ttl ]`  
              `[ group-list ipAccessList ] [ interval seconds ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sends autoRP announcement messages from a router you configured as an RP. The **no** version clears the specified filters from this interface.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#). The autoRP announcement messages will contain the IP address for this interface.
  - *ttl*—Time-to-live value; the number of hops for which the announcement is valid in the range 1–65535; default value is 64 hops
  - *ipAccessList*—Name of the IP access list that specifies which multicast groups use this RP; default value is no access list
  - *seconds*—Time interval in the range 1–65535 seconds at which the router sends the announcements; default value is 60 seconds

**Mode**    Global Configuration

---

## ip pim send-rp-discovery scope

---

**Syntax**    ip pim send-rp-discovery scope *tvl* [ *interfaceType interfaceSpecifier* ]  
              no ip pim send-rp-discovery

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the router as an RP mapping agent, which records RP-to-group mappings and notifies PIM DRs about the mappings. The **no** version stops the router from acting as an RP mapping agent.

- Options**
- *tvl*—Time-to-live value; number of hops for which the RP discovery message is valid. Specify a value that covers the PIM domain.
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#). If you specify an interface, the autoRP discovery messages will contain the IP address for this interface.

**Mode**    Global Configuration

## ip pim sparse-mode graceful-restart-duration

---

**Syntax**    ip pim sparse-mode graceful-restart-duration *seconds*  
              no ip pim sparse-mode graceful-restart-duration

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Sets duration time for IP PIM sparse-mode graceful restart. The **no** version resets the duration to the default.

**Options**    • sparse-mode—Enables PIM in sparse mode  
              • *seconds*—Restart duration in seconds; default value is 30 seconds

**Mode**    Global Configuration

## ip pim spt-threshold

---

**Syntax** [ no ] ip pim spt-threshold { 0 | *nonzero\_integer* | infinity } [ group-list *ipAccessList* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the network configuration that PIM sparse mode uses when a source starts sending multicast messages. The **no** version restores the default value, 0.

- Options**
- 0—Configures PIM sparse mode to switch to an SPT when a source begins to send multicast messages
  - *nonzero\_integer*—Integer in the range 1–4294967294; prevents PIM sparse mode from switching from a shared tree to an SPT
  - infinity—Prevents PIM sparse mode from switching from a shared tree to an SPT
  - *ipAccessList*—Name of the IP access list that specifies the groups to which the threshold applies

**Mode** Global Configuration

## ip pim ssm

---

**Syntax** ip pim ssm [ default | range *ipAccessList* ]

no ip pim ssm

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SSM and defines the SSM range of IP multicast addresses. The **no** version disables SSM on the router.

- Options**
- **default**—Specifies that SSM use the IANA-specified range of 232/8
  - *ipAccessList*—Name of the IP access list that specifies the range of multicast addresses you want SSM to use

**Mode** Global Configuration



## ip policy

**Syntax** For standard policy lists in Interface Configuration mode:

```
ip policy { input | output | secondary-input } policyName
[ statistics { enabled [ baseline { enabled | disabled } ] [ preserve | merge ] |
disabled [ merge ] } ] merge ]
```

```
no ip policy { input | output | secondary-input } [ policyName ]
```

For secure policy lists in Interface Configuration mode:

```
ip policy { secure-input | secure-output } policyName
[ statistics { enabled [ baseline baselineValue ] [ preserve ] | disabled } ]
```

```
no ip policy { secure-input | secure-output }
```

For policy lists in Profile Configuration mode:

```
ip policy { input | output | secondary-input } policyName
[ statistics { enabled | disabled } ] [ merge ]
```

```
no ip policy { input | output | secondary-input } [ policyName ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**merge** keyword added in JunosE Release 7.2.0.  
 Profile Configuration mode added in JunosE Release 7.2.0.

**Description** Assigns a policy list to the ingress or egress of an interface.

For standard policy lists, specify the **input** or **output** keyword to assign the policy list to the ingress or egress of the interface. If you enter the **ip policy** command and the policy list does not exist, the router inserts a default filter rule. Attaching this policy list to an interface filters all packets on that interface.

For secure policy lists, which are used for packet mirroring, use the **secure-input** or **secure-output** keyword to assign the packet mirroring policy list to the ingress or egress side of the interface. If you use the **ip policy** command and the secure policy list does not exist, the router creates a secure policy list with a default mirror rule that disables mirroring. Attaching this policy list to an interface results in no packet mirroring.

In Profile Configuration mode, assigns the policy list to a profile, which then assigns the policy to an interface.

In Interface Configuration mode, the **no** version removes the association between a policy list and an interface. In Profile Configuration mode, the **no** version removes policy reference from the profile.

- Options**
- **input**—Applies policy to data arriving at this interface before a route lookup
  - **output**—Applies policy to data leaving this interface

- **secondary-input**—Applies policy to data that arrives at this interface after a route lookup
- **secure-input**—Applies secure policy to data arriving at this interface
- **secure-output**—Applies secure policy to data leaving this interface



**NOTE:** The **ip policy** command used with the **secure-input** and **secure-output** keywords provides packet mirroring support. These keywords are available in Interface Configuration mode and do not support the statistics-related keywords. The **ip policy** command used with these keywords replaces the **ip mirror** command, which has been deprecated.

- **policyName**—Name of the policy; a maximum of 40 characters
- **statistics**—Enables or disables collection of policy routing statistics
  - **enabled**—Enables collection of policy routing statistics
  - **baseline enabled**—Enables baselining of policy routing statistics (Interface Configuration mode only)
  - **baseline disabled**—Disables baselining of policy routing statistics (Interface Configuration mode only)
  - **preserve**—Preserves existing statistics for any classifier list that is the same for both the new and old policy attachments when you attach a new policy to an interface
  - **disabled**—Disable collection of policy routing statistics
- **merge**—Enables merging of multiple policies to form a single policy



**NOTE:** The **local-input** keyword for the **ip policy** command is deprecated, and might be completely removed in a future release. We recommend that you remove the keyword from scripts.

**Mode**    Interface Configuration, Profile Configuration

**Related Documentation**

- Setting a Statistics Baseline for Policies
- Configuring CLI-Based Mirroring

## ip policy-list

---

**Syntax** [ no ] ip policy-list *policyName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies an IP policy list. If you execute an **ip policy-list** command and type **exit**, the router creates a policy list with no rules, the default. When a policy list does not have rules, the router inserts a default filter rule. Attaching this policy list to an interface filters all packets on that interface. The **no** version removes a policy list.

**Options** • *policyName*—Name of the policy list

**Mode** Global Configuration

**Related Documentation** • Creating Policy Lists for IP

## ip policy-parameter hierarchical

---

<b>Syntax</b>	<pre>ip policy-parameter hierarchical <i>parameterName</i> { <i>nodeValue</i>   atm   atm-vc   atm-vp <i>vpValue</i>   ethernet   fr-vc   forwarding   ppp-interface   svlan <i>svlanValue</i>   vlan }  no ip policy-parameter <i>parameterName</i></pre>
<b>Release Information</b>	Command introduced in JunosE Release 8.0.0. <b>ppp-interface</b> keyword added in JunosE Release 10.3.0.
<b>Description</b>	Specifies a parameter value for IP interfaces. The <b>no</b> version removes the policy parameter and its contents.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>parameterName</i>—Name of policy parameter</li><li>• <i>nodeValue</i>—Aggregation node number in the range 1–65535</li><li>• <i>vpValue</i>—ATM VPI number in the range 0–255</li><li>• <i>svlanValue</i>—S-VLAN ID number in the range 0–4095</li></ul>
<b>Mode</b>	Interface Configuration, Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Creating a Classifier Group for a Policy List</li></ul>

## ip policy-parameter reference-rate

---

**Syntax** In Interface Configuration mode:

ip policy parameter reference-rate *parameterName* [ increase ] *value*

no ip policy-parameter reference-rate *parameterName* [ increase *value* ]

In Profile Configuration mode:

ip policy parameter reference-rate *parameterName* [ increase ] *value*

no ip policy-parameter reference-rate *parameterName*

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates an IP policy parameter for a reference rate; creates a global parameter if it does not exist. The **no** version removes the policy parameter and its contents; if used with the **increase** keyword, decreases the value.

- Options**
- *parameterName*—Name of policy parameter up to 40 characters
  - increase—Increments the existing reference rate value
  - *value*—Value of the reference rate parameter, in the range 0–4292967295

**Mode** Interface Configuration, Profile Configuration

**Related Documentation**

- Creating a Classifier Group for a Policy List

## ip prefix-list

---

**Syntax**    ip prefix-list *listName* { description *desc* |  
              [ seq *sequence* ] { permit | deny } *ipPrefix* [ ge *geNumber* ] [ le *leNumber* ] }  
  
              no ip prefix-list *listName* [ description |  
              [ seq *sequence* ] [ { permit | deny } *ipPrefix* [ ge *geNumber* ] [ le *leNumber* ] ] }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates a prefix list for route filtering; specifies a list entry—a permit or deny clause for a network address. The **no** version removes the specified prefix list or the specified list entry.

- Options**
- *listName*—Name of the prefix list; a string of up to 32 characters
  - *desc*—Description of the prefix list
  - *sequence*—Number in the range 0–65535 that indicates the position the prefix list entry is to have in the list of entries already configured for the prefix list; if *sequence* is not specified, the value of the last sequence number + 5 is used
  - permit—If the prefix of the route being filtered matches the specified prefix and **permit** is specified, the route is redistributed as controlled by the set actions
  - deny—If the prefix of the route being filtered matches the specified prefix and **deny** is specified, the route is not redistributed
  - *ipPrefix*—Network route to be filtered, in the format *network / length*, where
    - *network*—Base address of the network route to be filtered; for example, 192.168.32.0 or 10.10.0.0
    - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched
  - *geNumber*—Route being filtered matches if its prefix is within the range specified: greater than or equal to *geNumber* and less than or equal to 32
  - *leNumber*—Route being filtered matches if its prefix is within the range specified: greater than or equal to *length* and less than or equal to *leNumber*

**Mode**    Global Configuration

## ip prefix-tree

**Syntax**    `ip prefix-tree treeName { description desc | { permit | deny } ipPrefix }`  
               `no ip prefix-tree treeName [ description | { permit | deny } ipPrefix ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates a prefix tree for best-match route filtering; specifies a tree entry—a deny or permit clause for a network address. The **no** version removes the specified prefix tree or the specified tree entry.

- Options**
- *treeName*—Name of the prefix list; a string of up to 32 characters
  - *desc*—Description of the prefix list
  - **deny**—If the prefix of the route being filtered matches the specified prefix and **deny** is specified, the route is not redistributed
  - **permit**—If the prefix of the route being filtered matches the specified prefix and **permit** is specified, the route is redistributed as controlled by the set actions
  - *ipPrefix*—Network route to be filtered, in the format *network / length*, where
    - *network*—Base address of the network route to be filtered; for example, 192.168.32.0 or 10.10.0.0
    - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched

**Mode**    Router Configuration

## ip profile

---

**Syntax**    ip profile *profileName*

             no ip profile

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Specifies the IP profile that the IPSec layer passes on to the IP layer upon request for upper-layer instantiation. The **no** version removes the association with this profile.

**Options**    • *profileName*—Name of the profile that you want the IPSec layer to pass to the IP layer upon request for upper-layer instantiation

**Mode**    IPSec Tunnel Profile Configuration



## ip proxy-arp

---

**Syntax**    ip proxy-arp [ restricted | unrestricted ]  
              no ip proxy-arp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables proxy ARP on an Ethernet or bridge1483 interface. Proxy ARP is enabled by default. The **no** version disables proxy ARP on an Ethernet or bridge1483 interface.

**Options**    • restricted—Restricts proxy-arp to hosts on the local interface  
              • unrestricted—Enables proxy-arp for all reachable hosts

**Mode**    Interface Configuration, Subinterface Configuration

## ip re-authenticate-auto-detect ip-subscriber

---

**Syntax** [ no ] ip re-authenticate-auto-detect ip-subscriber

**Release Information** Command introduced in JunosE Release 10.0.0.

**Description** Re-authenticates the auto-detected subscribers (dynamic subscriber interfaces) created on static and dynamic IP subscriber interfaces using the DHCP options **dhcp-options**, **dhcp-gi-address**, and **dhcp-mac-address** when the DHCP external application manages the subscriber addresses following a cold boot. The **no** version negates the command or restores the defaults.

**Mode** Interface Configuration, Profile Configuration

## ip redirects

---

**Syntax** [ no ] ip redirects

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the sending of redirect messages if the software is forced to resend a packet through the same interface on which it was received. The **no** version disables the sending of redirect messages.

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

## ip refresh-route

---

**Syntax**    ip refresh-route [ vrf *vrfName* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Reinstalls routes removed from the IP routing table by the **clear ip route** command. There is no **no** version.

**Options**    • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters

**Mode**    Privileged Exec

## ip rip

---

**Syntax** [ no ] ip rip

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures RIP to run on the network specified by the **network** command. Uses the default values: send version is RIP version 1, receive version is RIP version 1 and version 2, authentication is not enabled. The **no** version deletes the RIP interface.

**Mode** Interface Configuration, Subinterface Configuration

## ip rip authentication key

---

**Syntax**    ip rip authentication key [ 0 | 8 ] *authkey*  
              no ip rip authentication key

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the password for text authentication and the key for MD5 authentication. The **no** version clears the key for the interface. Supported only in RIP version 2. Authentication is disabled by default.

- Options**
- 0—Indicates the *authKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *authKey* is entered in encrypted form (ciphertext)
  - *authkey*—Password sent with RIP messages or the key used to encrypt/decrypt RIP messages, depending on the authentication mode set for this interface

**Mode**    Interface Configuration, Subinterface Configuration

## ip rip authentication mode

---

**Syntax** ip rip authentication mode { text | md5 *keyID* }

no ip rip authentication mode

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the type of authentication used on this interface. The **no** version removes authentication from the interface. Supported only in RIP version 2. Authentication is disabled by default.

- Options**
- **text**—Sends a simple text password with each RIP message; if the password is not possessed by neighbors, the message is rejected
  - **md5**—Encrypts and compresses the RIP message with MD5 message-digest algorithms
  - **keyID**—Number identifying the MD5 key; neighbors must share the MD5 key to decrypt the message and encrypt the response

**Mode** Interface Configuration, Subinterface Configuration

## ip rip bfd-liveness-detection

---

**Syntax** ip rip bfd-liveness-detection [ minimum-interval *minInterval* ]  
[ minimum-receive-interval *minRecInterval* ]  
[ minimum-transmit-interval *minTransInterval* ] [ multiplier *multValue* ]  
  
no ip rip bfd-liveness-detection

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Enables BFD (bidirectional forwarding detection) on an interface running RIP and defines BFD values to be negotiated between peers for detection of IP data path failures. The **no** version disables BFD on the RIP interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *minInterval*—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode** Interface Configuration



## ip rip copy-to-dynamic

---

**Syntax** [ no ] ip rip copy-to-dynamic

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables RIP on dynamic, unnumbered IP interfaces. You cannot configure RIP on dynamic interfaces directly. However, this command allows dynamic, unnumbered interfaces (that refer to numbered IP interface for configuration data) to obtain RIP attributes from the numbered IP interface to which they refer. The **no** version disables the feature but does not remove all existing, active RIP interfaces that were created by this command.

**Mode** Interface Configuration

## ip rip receive version

---

**Syntax** ip rip receive version { 1 | 2 | 1 2 | 2 1 | off }

no ip rip receive version

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Restricts the RIP version that the router can receive on an interface. The **no** version sets the interface back to the default value, receiving both RIP version 1 and version 2.

- Options**
- 1—Specifies RIP version 1 only
  - 2—Specifies RIP version 2 only
  - 1 2—Specifies RIP version 1 and version 2
  - 2 1—Specifies RIP version 2 and version 1
  - off—Turns reception off

**Mode** Interface Configuration, Subinterface Configuration

## ip rip send version

---

**Syntax** ip rip send version { 1 | 2 | 12 | 21 | off }  
no ip rip send version

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Restricts the RIP version that the router can send on an interface. The **no** version sets the interface back to the default value, sending only RIP version 1.

- Options**
- 1—Specifies RIP version 1 only
  - 2—Specifies RIP version 2 only
  - 12—Specifies RIP version 1 and version 2
  - 21—Specifies RIP version 2 and version 1
  - off—Turns reception off

**Mode** Interface Configuration, Subinterface Configuration

## ip route

**Syntax** `ip route [ vrf vrfName ] { ipAddress ipMask { ipNextHop [ interfaceType interfaceSpecifier ] | interfaceType interfaceSpecifier } } [ distance ] [ tag tagVal ] [ permanent ] [ [ verify rtr rtrIndex ] [ verify bfd-liveness-detection [ minimum-interval minInterval ] [ minimum-receive-interval minRecInterval ] [ minimum-transmit-interval minTransInterval ] ] [ multiplier multValue ] ] [ last-resort ] [ reject | discard ]`

`no ip route [ vrf vrfName ] ipAddress ipMask [ ipNextHop | interfaceType interfaceSpecifier ] [ distance ]`

**Release Information** Command introduced before JunosE Release 7.1.0.  
**reject** and **discard** keywords added in JunosE Release 12.0.0.

**Description** Establishes static routes and can also enable Bidirectional Forwarding Detection (BFD) for the static route. The **no** version removes static routes or removes BFD from the static route.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *vrfName*—Name of the VRF if the static route is being established within a VRF context; available only in Global Configuration mode
  - *ipAddress*—Destination IP address
  - *ipMask*—IP mask for the destination
  - *ipNextHop*—IP address of the next hop that can be used to reach the destination network
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *distance*—Administrative distance for this route in the range 0–254
  - *tagVal*—Number in the range 0–4294967295 that identifies the tag for this route
  - **permanent**—Specifies that the route will not be removed, even if the interface shuts down
  - **verify rtr**—Installs the static route in the routing table only if the next hop to the specified destination address is resolved and if the specified RTR operation is currently reachable
  - *rtrIndex*—Number of the RTR operation to be verified; there is no default value

- **verify bfd-liveness-detection**—Installs the static route in the routing table only if the next hop to the specified destination address is verifiable by means of BFD liveness detection
- **minInterval**—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
- **minRecInterval**—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
- **minTransInterval**—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
- **multValue**—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3
- **last-resort**—Installs the static route in the routing table even if the specified RTR operation is currently unreachable, provided that no other static route to the same network prefix is available
- **reject**—Discards packets received on the static route for the specified interface that are not processed by the router and sends ICMP unreachable messages to the originator. This option is available only for null interfaces
- **discard**—Discards packets received on the static route for the specified interface that are not processed by the router and does not send ICMP unreachable messages to the originator. This option is available only for null interfaces

**Mode**    Global Configuration

## ip route-cache flow sampled

---

**Syntax** [ no ] ip route-cache flow sampled

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 7.2.0.

**Description** Enables J-Flow statistics on an interface. The **no** version disables J-Flow statistics on the interface.

**Mode** Interface Configuration, Profile Configuration

## ip route-map ip-subscriber

---

**Syntax**    ip route-map ip-subscriber *routeMapName*  
              no ip route-map ip-subscriber

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures an interface for route-map processing and specifies the route map that is applied to the IP interface subscriber. If no route map is specified, then all packets will trigger the creation of a dynamic subscriber interface. The **no** version deletes the route map.

**Options**    • *routeMapName*—Name of route map

**Mode**    Interface Configuration, Profile Configuration

## ip route-type

---

**Syntax** For BGP:

ip route-type [ unicast | both ]

no ip route-type

For IS-IS, OSPF, and RIP:

ip route-type [ unicast | multicast | both ]

no ip route-type

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies whether BGP, IS-IS, OSPF, or RIP routes are available only for unicast forwarding, only for multicast reverse path forwarding checks, or for both. The **no** version restores the default value, **unicast** for BGP or **both** for IS-IS, OSPF, and RIP.

- Options**
- **unicast**—Specifies that routes for the protocol are available only for unicast forwarding
  - **multicast**—Specifies that routes for the protocol are available only for multicast route path forwarding checks; this option is not available for BGP
  - **both**—Specifies that routes for the protocol are available for both unicast forwarding and multicast route path forwarding checks

**Mode** Address Family Configuration (RIP), Router Configuration



## ip router-id

---

**Syntax** [ no ] ip router-id [ *vrfName* ] *ipAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Establishes the IP address of a router. The **no** version removes the IP address assignment.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *ipAddress*—IP address of the router

**Mode** Global Configuration

- Related Documentation**
- Configuring the Loopback Interface and Router ID for BGP for VPWS
  - Configuring the Loopback Interface and Router ID for VPLS

## ip router isis

---

**Syntax**    [ no ] ip router isis [ tag ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures an IS-IS routing process for IP on an interface. The **no** version disables IS-IS for IP on the interface.

**Options**    • *tag*—Meaningful name for a routing process. If not specified, a null tag is assumed. The name must be unique among all IP router processes for a given router. Use the same text for the argument tag as specified in the router isis command.

**Mode**    Interface Configuration, Subinterface Configuration

---

## ip-router-name

---

**Syntax** [ no ] ip-router-name [ *vrName* ]

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Assigns an IPv4 virtual router. The **no** version restores the default router.



**NOTE:** This command replaces the deprecated **router-name** command, which may be removed completely in a future release.

**Options** • *vrName*—Name of the virtual router; string of 1–32 alphanumeric characters

**Mode** Domain Map Configuration

## ip rpf-route

---

**Syntax**    `ip rpf-route ipAddress addressMask`  
              `{ nextHopIpAddress | nextHopInterfaceType nextHopInterfaceSpecifier }`  
              `[ distanceValue ] [ tag tagValue ]`  
  
              `[ no ] ip rpf-route ipAddress addressMask`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Customizes static routes that the router can use to verify source addresses in multicast packets. The **no** version removes the static route.

- Options**
- *ipAddress*—IP address of the destination network
  - *addressMask*—Subnet mask for the destination network
  - *nextHopIpAddress*—IP address of the next hop
  - *nextHopInterfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *nextHopInterfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *distanceValue*—Number in the range 0–255 that indicates the preference for this route
  - *tagValue*—Number in the range 0–4294967295 that identifies the route in the routing table

**Mode**    Global Configuration

## ip rsvp authentication

---

**Syntax** [ no ] { ip | mpls } rsvp authentication

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables MD5 authentication on the RSVP interface in implementations on routers from other vendors. See the [mpls rsvp authentication](#) command for a complete description and syntax.

**Mode** Interface Configuration

## ip rsvp authentication key

---

**Syntax** { ip | mpls } rsvp authentication [ key *authkey* ]  
no { ip | mpls } rsvp authentication [ key [ *authkey* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns a key for MD5 authentication between RSVP peers in implementations on routers from other vendors. See the [mpls rsvp authentication key](#) command for a complete description and syntax.

**Mode** Interface Configuration

## ip rsvp bandwidth

---

**Syntax** { ip rsvp | mpls } bandwidth *bandwidth*  
no { ip rsvp | mpls } bandwidth

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the total bandwidth *reservable* on the interface in a non-E Series implementation. See the [mpls bandwidth](#) command for a complete description and syntax.

**Mode** Interface Configuration

## ip rsvp bfd-liveness-detection

---

**Syntax** { ip | mpls } rsvp bfd-liveness-detection [ minimum-interval *minInterval* |  
[ minimum-receive-interval *minRecInterval* ]  
[ minimum-transmit-interval *minTransInterval* ] ] [ multiplier *multValue* ]  
  
no { ip | mpls } rsvp bfd-liveness-detection

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Enables BFD (bidirectional forwarding detection) on an interface running RSVP-TE and defines BFD values to be negotiated between RSVP-TE neighbors for detection of IP data path failures. See the [mpls rsvp bfd-liveness-detection](#) command for a complete description and syntax.

**Mode** Interface Configuration



## ip rsvp signalling hello

---

**Syntax** { ip | mpls } rsvp signalling hello  
[ refresh { interval *helloInterval* | misses *helloMisses* } ]  
  
{ no | default } { ip | mpls } rsvp signalling hello

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Turns on or configures RSVP-TE hello support. See the [mpls rsvp signalling hello](#) command for a complete description and syntax.

**Mode** Global Configuration, Interface Configuration, Subinterface Configuration

## ip sa-validate

---

**Syntax** [ no ] ip sa-validate

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables source address validation on an interface. This feature verifies that a packet has been sent from a valid source address. When a packet arrives on an interface, the router performs a routing table lookup using the source address. The result from the routing table lookup is an interface to which packets destined for that address are routed. This interface must match the interface that the packet arrived on. If it does not match, the router drops the packet. By default, validation of IP source addresses is disabled for the particular interface or profile. The **no** version disables source address validation.

**Mode** Interface Configuration, Profile Configuration

## ip sa-validate trap-enable

---

**Syntax** [ no ] ip sa-validate [ vrf *vrfName* ] trap-enable

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables the generation of source address validation failure traps. The **no** version disables the generation of source address validation failure traps.

**Options** • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters

**Mode** Global Configuration

## ip service-profile

---

**Syntax**    ip service-profile *profileName*  
              no ip service-profile

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a service profile used in the route map and enters Service Profile configuration mode. The **no** version deletes the profile.

**Options**    • *profileName*—Name of service profile

**Mode**    Global Configuration

---

## ip share-interface

---

**Syntax**    `ip share-interface interfaceType interfaceSpecifier`  
`no ip share-interface`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the layer 2 interface that an IP interface will share in the current virtual router. The command fails if the layer 2 interface does not yet exist.

If you issue this command on a shared IP interface, you cannot issue the **ip share-nexthop** command for the interface. After creating the shared IP interface, you can configure it as you do any other IP interface. The shared interface is operationally up when the layer 2 interface is operationally up and IP is properly configured. You can create operational shared IP interfaces in the absence of a primary IP interface.

The **no** version removes the association between the layer 2 interface and the shared IP interface. You can delete shared and primary IP interfaces independently

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Interface Configuration

## ip share-nexthop

---

**Syntax**    ip share-nexthop *ipAddress* [ virtual-router *vrName* ]  
              no ip share-nexthop

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies that the shared IP interface dynamically tracks a next hop for the specified destination. If the next hop changes, the shared IP interface moves to the new layer 2 interface associated with the IP interface toward the new next hop.

If you issue this command on a shared IP interface, you cannot issue the **ip share-interface** command for the interface. If you issue this command on a shared IP interface, the shared interface cannot dynamically track the next hop for the specified destination if the next-hop IP address is resolvable over MPLS. If you specify a virtual router, the command fails if the VR does not already exist. If you do not specify a VR, the current VR is assumed.

After creating the shared IP interface, you can configure it as you do any other IP interface. The shared interface is operationally up when the layer 2 interface associated with the specified next hop is operationally up and IP is properly configured.

The **no** version halts tracking of the next hop.

- Options**
- *ipAddress*—IP address of the destination for which the next hop is tracked
  - *vrName*—Name of the virtual router for the next hop

**Mode**    Interface Configuration

## ip shutdown

---

**Syntax** [ no ] ip shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Shuts down an IP interface. The **no** version restarts the interface.

**Mode** Interface Configuration, Subinterface Configuration

## ip source-prefix

---

**Syntax** [ no ] ip source-prefix *ipAddress* *ipAddressMask* deny

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures a subscriber interface or a primary IP interface that is enabled for dynamic creation of subscriber interfaces to demultiplex traffic with the specified IP address and mask. On the ERX1440 router or the E320 router, you can configure up to 1024 subnets for static subscriber interfaces per primary IP interface when each subnet has a variable network mask that is less than /32. The number of subnets identifying a single route (/32) is still limited by the global maximum of 16,000 hosts per line module. The **no** version removes the association between the interface and the specified IP address and mask.

- Options**
- *ipAddress*—IP address of the physical interface that receives messages for this subscriber
  - *ipAddressMask*—Network mask for associated IP subnet
  - deny—Filters packets matching this command

**Mode** Interface Configuration, Subinterface Configuration



## ip source-route

---

**Syntax** [ no ] ip source-route [ vrf *vrfName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the forwarding of source-routed packets in a VR or VRF. The **no** version disables forwarding. Forwarding is disabled by default in all VRs.

If the router receives IP packets that contain either the strict source-route or the loose source-route option set in the packets and if you disable forwarding of source-routed packets by entering the **no ip source-route** command, the received packets are discarded. In such a scenario, the router does not process such packets when source-route forwarding is disabled.

**Options** • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters

**Mode** Global Configuration

## ip speed

---

**Syntax**    [ no ] ip speed *adminSpeed*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the speed of an IP interface in bits per second. The **no** version restores the default value, 0 bps.

**Options**    • *adminSpeed*—Speed of the interface in bps in the range 1–4294967295

**Mode**    Interface Configuration, Subinterface Configuration

## ip split-horizon

---

**Syntax** [ no ] ip split-horizon

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables split horizon, preventing the RIP router from advertising routes from the interface originating the route, reducing the possibility of routing loops; this is the default condition. The **no** version disables split horizon.

**Mode** Interface Configuration, Subinterface Configuration

## ip ssh authentication-retries

---

**Syntax**    ip ssh authentication-retries *retryLimit*  
              no ip ssh authentication-retries

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the number of times that a user can retry a failed authentication (such as trying to correct a wrong password) before the server terminates the connection. The **no** version restores the default value, 20 retries.

**Options**    • *retryLimit*—Number of times authentication can be retried after the initial failure within a given connection attempt

**Mode**    Global Configuration

## ip ssh crypto

**Syntax** ip ssh crypto [ client-to-server | server-to-client ] [ no | default ] *cipherAlgorithm*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Adds an encryption algorithm to the specified list of supported algorithms. The **no** version removes or excludes an algorithm from the specified list. The **default** version restores the default algorithms for the specified list. The default list does not include the *none* option.



**NOTE:** If you do not specify a direction (client-to-server or server-to-client), the command applies the algorithm to both inbound and outbound lists.

- Options**
- client-to-server—Adds the specified algorithm to the SSH server's list of supported inbound algorithms
  - server-to-client—Adds the specified algorithm to the SSH server's list of supported outbound algorithms
  - no—Removes or excludes the specified algorithm from the list
  - default—Restores the specified list to the factory defaults, which includes 3des-cbc, twofish-cbc, and blowfish-cbc
  - *cipherAlgorithm*—Algorithm to add to the list

**Mode** Global Configuration

## ip ssh disable-user-authentication

---

**Syntax** [ no ] ip ssh disable-user-authentication

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables RADIUS password authentication, resulting in the acceptance of all SSH clients that pass protocol negotiation. The **no** version restores RADIUS authentication.

**Mode** Global Configuration

## ip ssh mac

**Syntax** ip ssh mac [ client-to-server | server-to-client ] [ no | default ] *macAlgorithm*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Adds a MAC algorithm to the specified list of supported algorithms. The **no** version removes or excludes an algorithm from the specified list. The **default** version restores the default algorithms for the specified list. The default list does not include the *none* option.



**NOTE:** If you do not specify a direction (client-to-server or server-to-client), the command applies the algorithm to both inbound and outbound lists.

- Options**
- **client-to-server**—Adds the specified algorithm to the SSH server's list of supported inbound algorithms
  - **server-to-client**—Adds the specified algorithm to the SSH server's list of supported outbound algorithms
  - **no**—Removes or excludes the specified algorithm from the list
  - **default**—Restores the specified list to the factory defaults, which includes hmac-md5, hmac-sha1, and hmac-sha1-96
  - ***macAlgorithm***—Algorithm to add to the list

**Mode** Global Configuration

## ip ssh sleep

---

**Syntax**    `ip ssh sleep sleepPeriod`

`no ip ssh sleep`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a sleep period in seconds for users that have exceeded the authentication retry limit. Connection attempts from the user at the same host are denied until this period expires. The **no** version restores the default value, 600 seconds.

**Options**    • *sleepPeriod*—Period in the range 0–4294967295 seconds

**Mode**    Global Configuration



## ip ssh timeout

---

**Syntax**    ip ssh timeout *timeout*  
              no ip ssh timeout

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a timeout period in seconds. The SSH server terminates the connection if protocol negotiation—including user authentication—is not complete within this timeout. The **no** version restores the default value, 600 seconds.

**Options**    • *timeout*—Period in the range 10–600 seconds

**Mode**    Global Configuration

## ip ssh user-authentication-protocol

---

**Syntax**    ip ssh user-authentication-protocol *protocol*  
              no ip ssh user-authentication-protocol

**Release Information**    Command introduced in JunosE Release 10.2.0.

**Description**    Configures the SSH user authentication protocol. E Series routers support RADIUS and TACACS+ user authentication protocols. The **no** version restores the SSH user authentication protocol to the default, RADIUS.

**Options**    • *protocol*—User authentication protocol: either RADIUS or TACACS+.

**Mode**    Global Configuration

## ip static-route table-map

---

**Syntax**    `ip static-route table-map [ vrf vrfName ] mapName`  
              `no ip static-route table-map [ vrf vrfName ] [ mapName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Filters static routes before adding them to the routing table. The **no** version deletes the table map.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *mapName*—Name of the table map that you want the router to use

**Mode**    Global Configuration

## ip summary-address

---

**Syntax**    `ip summary-address [ rip ] ipAddress ipAddressMask [ metric ]`  
              `no ip summary-address [ rip ] ipAddress ipAddressMask`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Summarizes specified addresses for RIP. The **no** version removes the summarization.

- Options**
- `rip`—Specifies optional keyword for compatibility with non-E Series implementations
  - `ipAddress`—IP address identifying the route to be summarized
  - `ipAddressMask`—Network mask identifying the route to be summarized
  - `metric`—Specifies a metric for the summary address; default value is 1

**Mode**    Address Family Configuration, Router Configuration

## ip tcp ack-rst-and-syn

---

**Syntax** [ no ] [ ip ] tcp ack-rst-and-syn [ vrf *vrfName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** The **ip** keyword for **tcp** commands is now optional (with the exception of the **ip tcp adjust-mss** command, which is IPv4 specific). For information about this command and any other **ip tcp** command, see the **tcp** commands.

**Mode** Global Configuration

## ip tcp adjust-mss

---

**Syntax** [ ip ] tcp adjust-mss *mssAdjustment*

no [ ip ] tcp adjust-mss

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Modifies the maximum segment size (MSS) for TCP SYN packets traveling through the interface. The router compares the MSS value of incoming or outgoing packets against the MSS adjustment value. For any packet that contains an MSS value larger than the MSS adjustment value, the router replaces the MSS option with the configured adjustment value. If the packet does not contain an MSS value, the router assumes a value of 536 for the packet MSS on which to base the comparison. The **no** version removes the MSS modification.



**NOTE:** The purpose behind using MSS is to alleviate problems with Path MTU Discovery (PMTUD) and resulting “black hole” detection issues. See RFC 2923—TCP Problems with Path MTU Discovery (September 2000) for additional information about the black hole scenario.

- Options**
- **ip**—Specifies optional keyword for use with older scripts
  - *mssAdjustment*—Adjustment value for the MSS; in the range 160–10240

**Mode** Interface Configuration, Profile Configuration

## ip ttl

---

**Syntax**    `ip ttl [ vrfName ] ttlValue`  
              `no ip ttl [ vrfName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the hop count specified by the TTL field in the IP header used by IP for all operations unless overridden by another command. The **no** version restores the default value, 127.

**Options**

- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
- *ttlValue*—Number in the range 1–255

**Mode**    Global Configuration

## ip tunnel reassembly

---

**Syntax** [ no ] ip tunnel reassembly

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the reassembly of fragmented IP tunnel packets that are received on the current virtual router. The **no** version restores the default disabled condition.

**Mode** Global Configuration



## ip unnumbered

**Syntax** [ no ] ip unnumbered *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IP processing on an interface without assigning an explicit IP address to the interface. You must specify an interface location, which is the identifier of another interface on which the router has an assigned IP address. This interface cannot be another unnumbered interface. The **no** version disables IP processing on the interface.



**NOTE:** You can specify an unnumbered interface using RADIUS instead of using this command in a profile. For more information about how to specify an unnumbered interface using RADIUS, see *Configuring RADIUS Attributes* in the *JunosE Broadband Access Configuration Guide*.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Interface Configuration, Profile Configuration, Subinterface Configuration

## ip unreachable

---

**Syntax** [ no ] ip unreachable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the generation of an ICMP unreachable message when a packet is received that cannot be delivered by the router. The **no** version disables this function.

**Mode** Interface Configuration, Subinterface Configuration

## ip use-framed-routes ip-subscriber

---

**Syntax** [ no ] ip use-framed-routes ip-subscriber

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Configures the router to enable a static primary IP interface to use the RADIUS Framed-Route attribute [22]. The primary IP interface applies the framed routes as source IP addresses when creating and configuring dynamic subscriber interfaces. The **no** version disables the primary IP interface support of the Framed-Route RADIUS attribute.

**Mode** Interface Configuration

## ip virtual-router

---

**Syntax** [ no ] ip virtual-router *vrName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a virtual router in an IP profile. Dynamic interfaces created with the profile are assigned to this VR. The **no** version removes the VR from the profile; if a VR is not specified via RADIUS, then any subsequent creation process for dynamic interfaces using the profile fails.



---

**NOTE:**

- You can configure a virtual router using RADIUS instead of adding one to the profile by using this command. For more information about how to configure a virtual router using RADIUS, see *Configuring RADIUS Attributes* in the *JunosE Broadband Access Configuration Guide*.
  - If the VR specified in a profile with this command differs from the VR provided by AAA, IP uses the VR provided by AAA when the dynamic IP upper-layer interface is created.
- 

**Options** • *vrName*—Name of the virtual router; a string of 1–15 alphanumeric characters

**Mode** Profile Configuration

## ip vrf

**Syntax**    `ip vrf vrfName`  
               `no ip vrf vrfName [ wait-for-completion [ waitSeconds ] ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates a VRF or accesses VRF Configuration mode to configure a VRF. The **no** version deletes the VRF.



**NOTE:** After creating the VRF, you must configure a route distinguisher for it through the **rd** command. If the route distinguisher is not configured, the VRF cannot operate.

- Options**
- *vrfName*—Name of the VRF; a string of 1–32 alphanumeric characters
  - *wait-for-completion*—Specifies (in the absence of *waitSeconds*) that the CLI waits for completion of the **no** version operation before it returns a prompt, regardless of how long that takes. Use the **wait-for-completion** keyword with the **no** version if you require a synchronous, deterministic deletion of a VRF, such as when executing Telnet or console commands by means of an external script. If you do not issue the **wait-for-completion** keyword in these circumstances, an **ip vrf** command issued as soon as the prompt appears might fail because the router is still deleting the VRF.
  - *waitSeconds*—Number of seconds in the range 1–64000 that the CLI waits before it returns a prompt, regardless of whether the **no** version operation has completed

**Mode**    Global Configuration

## ip vrf forwarding

---

**Syntax** [ no ] ip vrf forwarding *vrfName* [ fallback global ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns a VRF to an interface or subinterface. Optionally specifies secondary routing table lookup on the parent (global) virtual router forwarding table if a lookup on the initial VRF forwarding table does not yield any results. The **no** version removes the assignment or discontinues the secondary routing table lookup option.



**NOTE:** The **ip vrf forwarding** command changes the prompt to indicate that the CLI is now in Interface or Subinterface Configuration mode within the child VRF. This condition persists only for as long as you are configuring attributes on the given interface within the VRF. Entering a top-level command, such as **interface**, within this VRF context takes the CLI out of the VRF context back to the parent VR context.

When you issue the **ip vrf forwarding** command from within the Interface Configuration or Subinterface Configuration mode of the parent VR, the IP address and other attributes of the interface are deleted from the interface. You must then reconfigure the IP attributes in the context of the VRF after issuing the command.

- Options**
- *vrfName*—Name of the VRF; a string of 1–32 alphanumeric characters
  - **fallback global**—Specifies secondary routing table lookup on the parent (global) virtual router forwarding table, if an initial VRF forwarding table lookup does not yield results.

**Mode** Interface Configuration, Subinterface Configuration

## ip vrrp

---

**Syntax**    [ no ] ip vrrp *vrid*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates a VRRP instance ID. The **no** version removes a VRID. The default is disabled.

**Options**    • *vrid*—VRID identifier; a number in the range 1–255

**Mode**    Interface Configuration

## ip vrrp accept-data

---

**Syntax** [ no ] ip vrrp *vrid* accept-data

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the backup router to process packets with an IP destination address equivalent to the virtual addresses while the backup router is in the master state. The router ignores this attribute when the VRRP entry uses a priority of 255. You must use the default state (disabled) to comply with RFC 3768. When disabled, the master router drops any packets with an IP destination address equivalent to the virtual address. The **no** version restores the default value, disabled.



**NOTE:** When using this attribute and also restricting incoming packets to ICMP only, you must use policy filters to accept only ICMP packets with the virtual address as the destination address.

**Options** • *vrid*—VRID identifier; a number in the range 1–255

**Mode** Interface Configuration



## ip vrrp advertise-interval

---

**Syntax**    `ip vrrp vrid advertise-interval advertiseInterval [ seconds | milliseconds ]`  
`no ip vrrp vrid advertise-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the VRRP advertisement interval time. You must use seconds to comply with RFC 2338. Use milliseconds only if all VRRP instances peering for the given VRID are composed of E Series routers. The **no** version restores the default value, 1 second.

**Options**

- *vrid*—VRID identifier; a number in the range 1–255
- *advertiseInterval*—Advertisement period in seconds or milliseconds; in the range 1–255 seconds or 100–255000 milliseconds
- *seconds*—Specifies interval in seconds
- *milliseconds*—Specifies interval in milliseconds

**Mode**    Interface Configuration

## ip vrrp authentication-key

---

**Syntax**    `ip vrrp vrid authentication-key key`  
              `no ip vrrp vrid authentication-key`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the authentication key. This command is only valid if the **text** keyword was selected in the **ip vrrp authentication-type** command. The **no** version negates the command or restores the default.

**Options**

- *vrid*—VRID identifier; a number in the range 1–255
- *key*—String of 1–8 characters

**Mode**    Interface Configuration

## ip vrrp authentication-type

---

**Syntax**    ip vrrp *vrid* authentication-type { none | text }  
              no ip vrrp *vrid* authentication-type

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the VRRP authentication type. The **no** version restores the default value, none.

- Options**
- *vrid*—VRID identifier; a number in the range 1–255
  - none—Disables authentication
  - text—Specifies simple text password

**Mode**    Interface Configuration

## ip vrrp enable

---

**Syntax** [ no ] ip vrrp *vrid* [ enable ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables a VRID. The **no** version disables a VRID. The default is disabled.

**Options** • *vrid*—VRID identifier; a number in the range 1–255

**Mode** Interface Configuration

## ip vrrp icr-partition

**Syntax** [ no ] ip vrrp *vrid* icr-partition *partitionId*

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Creates an ICR partition that corresponds to the VRRP instance. The state of the ICR partition depends on the state of the VRRP instance. If the VRRP instance is disabled, the ICR partition is in the dormant state. If the VRRP instance is enabled, the ICR partition follows the state of the VRRP instance. The **no** version deletes the partition from the router.

- Options**
- *vrid*—VRID identifier; a number in the range 1–255
  - *partitionId*—Name that identifies the ICR partition; a string of up to 128 alphanumeric characters



**NOTE:** Use the ICR-Partition-Id VSA to determine the ICR partition on which subscribers are logged in. You can configure the same ICR-Partition-Id string for an active ICR partition and its corresponding backup partition. For more information on ICR-PARTITION-ID VSA, see Interaction with RADIUS for ICR.

**Mode** Interface Configuration, Subinterface Configuration

- Related Documentation**
- Naming ICR Partitions
  - Configuring ICR Partitions

## ip vrrp icr-partition group

---

<b>Syntax</b>	<code>ip vrrp <i>vrid</i> icr-partition group <i>partitionGroupingType</i></code>
<b>Release Information</b>	Command introduced in JunosE Release 10.3.0.
<b>Description</b>	Configures the ICR partition to use either S-VLAN-based grouping or VLAN-based grouping for subscribers. If you specify VLAN as the grouping type or partition type, the ICR partition consists of single-tagged VLAN-based subinterfaces. By default, the ICR partition uses S-VLAN-based grouping. There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>vrid</i>—VRID identifier; a number in the range 1–255</li><li>• <i>partitionGroupingType</i>—One of the following partition types:<ul style="list-style-type: none"><li>• <i>svlan</i>—Configures the ICR partition to use double-tagged S-VLAN based subinterfaces.</li><li>• <i>vlan</i>—Configures the ICR partition to use single-tagged VLAN based subinterfaces.</li></ul></li></ul>
<b>Mode</b>	Interface Configuration, Subinterface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Grouping ICR Subscribers Based on S-VLAN IDs</li><li>• Grouping ICR Subscribers Based on VLAN IDs</li><li>• Configuring ICR Partitions</li></ul>

## ip vrrp icr-partition svlan-list

**Syntax** ip vrrp *vrid* icr-partition svlan-list [ *svlanIdValue* ] \*  
 [ use-default-mac ] [ control-interface ] [ advertise-mac ]  
 no ip vrrp *vrid* icr-partition svlan-list [ *svlanIdValue* ] \*

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Adds an S-VLAN to the ICR partition. You can assign only unique S-VLANs to the partition. If you attempt to assign a previously assigned S-VLAN to the ICR partition, the router displays an error message. You can assign S-VLANs only if you have selected S-VLAN based grouping by using the **ip vrrp icr-partition group** command. The **no** version deletes the S-VLAN from the ICR partition.



**NOTE:** You can use the listed optional parameters only when you add a S-VLAN to the ICR partition. You cannot modify an existing subinterface using these parameters. You can specify the optional parameters in any order.

- Options**
- **vrid**—VRID identifier; a number in the range 1–255
  - **svlanIdValue**—S-VLAN identifier; a number in the range 0–4095
  - **use-default-mac**—Configures the S-VLAN to use the default MAC address. By default, the router assigns the VRRP media access control (MAC) address to all subinterfaces of the ICR partition.
  - **control-interface**—Controls traffic on a subinterface that is part of a backup partition. When you use this option, the router changes the state of the corresponding subinterface to Admindown. When the subinterface is in Admindown state, the router blocks all traffic to the interface. However, the router does not block advertisements as long as VRRP is running on a separate subinterface. The router changes the state of the subinterface from Admindown to Up when the state of the partition changes from backup to master.
  - **advertise-mac**—Enables the subinterface to transmit GARP advertisements when the partition moves from backup state to master state. By default, GARP advertisements are blocked on a subinterface.

**Mode** Interface Configuration, Subinterface Configuration

- Related Documentation**
- Grouping ICR Subscribers Based on S-VLAN IDs
  - Configuring ICR Partitions

## ip vrrp icr-partition svlan-list explicit

**Syntax** ip vrrp *vrid* icr-partition svlan-list-explicit [ *svlanIdValue* *vlanIdValue* ] \*  
 [ use-default-mac ] [ control-interface ] [ advertise-mac ]  
 no ip vrrp *vrid* icr-partition svlan-list-explicit [ *svlanIdValue* *vlanIdValue* ] \*

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Adds an S-VLAN range and VLAN range to the ICR partition. You can assign only unique S-VLAN range and VLAN range to the partition. If you attempt to assign a previously assigned S-VLAN range and VLAN range to the ICR partition, the router displays an error message. You can assign S-VLAN range and VLAN range only if you have selected S-VLAN based grouping by using the **ip vrrp icr-partition group** command. The **no** version deletes the S-VLAN range and VLAN range from the ICR partition.



**NOTE:** You can use the listed optional parameters only when you add a S-VLAN, VLAN pair to the ICR partition. You cannot modify an existing subinterface using these parameters. You can specify the optional parameters in any order.

- Options**
- **vrid**—VRID identifier; a number in the range 1–255
  - **svlanIdValue**—S-VLAN identifier; a number in the range 0–4095
  - **vlanIdValue**—VLAN identifier; a number in the range 0–4095
  - **use-default-mac**—Configures the S-VLAN range and VLAN range to use the default MAC address. By default, the router assigns the VRRP media access control (MAC) address to all subinterfaces of the ICR partition.
  - **control-interface**—Controls traffic on a subinterface that is part of a backup partition. When you use this option, the router changes the state of the corresponding subinterface to Admindown. When the subinterface is in Admindown state, the router blocks all traffic to the interface. However, the router does not block advertisements as long as VRRP is running on a separate subinterface. The router changes the state of the subinterface from Admindown to Up when the state of the partition changes from backup to master.
  - **advertise-mac**—Enables the subinterface to transmit GARP advertisements when the partition moves from backup state to master state. By default, GARP advertisements are blocked on a subinterface.

**Mode** Interface Configuration, Subinterface Configuration

**Related Documentation**

- Grouping ICR Subscribers Based on S-VLAN IDs
- Configuring ICR Partitions



## ip vrrp icr-partition svlan-range

**Syntax** `ip vrrp vrid icr-partition svlan-range [ svlanIdStart svlanIdEnd ]`  
`[ use-default-mac ] [ control-interface ] [ advertise-mac ]`

`no ip vrrp vrid icr-partition svlan-range [ svlanIdStart svlanIdEnd ]`

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Adds a range of S-VLANs to the ICR partition. You can only assign unique S-VLANs to the partition. If you attempt to assign a previously assigned S-VLAN range to the ICR partition, the router displays an error message. You can assign S-VLANs only if you have selected S-VLAN based grouping by using the **ip vrrp icr-partition group** command. The **no** version deletes the S-VLAN range from the ICR partition.



**NOTE:** You can use the listed optional parameters only when you add a S-VLAN or a range of S-VLANs to the ICR partition. You cannot modify an existing subinterface using these parameters. You can specify the optional parameters in any order.

- Options**
- **vrid**—VRID identifier; a number in the range 1–255
  - **svlanIdStart**—Starting S-VLAN ID of the S-VLAN subrange you are configuring; a number in the range 0–4095
  - **svlanIdEnd**—Ending S-VLAN ID of the S-VLAN subrange you are configuring; a number in the range 0–4095
  - **use-default-mac**—Configures the S-VLAN range to use the default MAC address. By default, the router assigns the VRRP MAC address to all subinterfaces of the ICR partition.
  - **control-interface**—Controls traffic on a range of subinterfaces that are part of a backup partition. When you use this option, the router changes the state of the corresponding range of subinterfaces to Admindown. When the subinterfaces are in Admindown state, the router blocks all traffic to the interfaces. However, the router does not block advertisements as long as VRRP is running on a separate subinterface. The router changes the state of the range of subinterfaces from Admindown to Up when the state of the partition changes from backup to master.
  - **advertise-mac**—Enables subinterfaces to transmit GARP advertisements when the partition moves from backup state to master state. By default, GARP advertisements are blocked on subinterfaces.

**Mode** Interface Configuration, Subinterface Configuration

**Related Documentation**

- Grouping ICR Subscribers Based on S-VLAN IDs

- Configuring ICR Partitions

## ip vrrp icr-partition vlan-list

**Syntax** `ip vrrp vrid icr-partition vlan-list [ vlanIdValue ] *`  
`[ use-default-mac ] [ control-interface ] [ advertise-mac ]`  
`no ip vrrp vrid icr-partition vlan-list [ vlanIdValue ] *`

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Adds a VLAN to the ICR partition. You can assign only unique VLANs to the partition. If you attempt to assign a previously assigned VLAN to the ICR partition, the router displays an error message. You can assign VLANs only if you have selected VLAN based grouping by using the **ip vrrp icr-partition group** command. The **no** version deletes the VLAN from the ICR partition.



**NOTE:** You can use the listed optional parameters only when you add a VLAN to the ICR partition. You cannot modify an existing subinterface using these parameters. You can specify the optional parameters in any order.

- Options**
- **vrid**—VRID identifier; a number in the range 1–255
  - **vlanIdValue**—VLAN identifier; a number in the range 0–4095
  - **use-default-mac**—Configures the VLAN to use the default MAC address. By default, the router assigns the VRRP media access control (MAC) address to all subinterfaces of the ICR partition.
  - **control-interface**—Controls traffic on a subinterface that is part of a backup partition. When you use this option, the router changes the state of the corresponding subinterface to Admindown. When the subinterface is in Admindown state, the router blocks all traffic to the interface. However, the router does not block advertisements as long as VRRP is running on a separate subinterface. The router changes the state of the subinterface from Admindown to Up when the state of the partition changes from backup to master.
  - **advertise-mac**—Enables the subinterface to transmit GARP advertisements when the partition moves from backup state to master state. By default, GARP advertisements are blocked on subinterfaces.

**Mode** Interface Configuration, Subinterface Configuration

- Related Documentation**
- Grouping ICR Subscribers Based on VLAN IDs
  - Configuring ICR Partitions

## ip vrrp icr-partition vlan-range

**Syntax** `ip vrrp vrid icr-partition vlan-range [ vlanIdStart vlanIdEnd ]`  
`[ use-default-mac ] [ control-interface ] [ advertise-mac ]`  
`no ip vrrp vrid icr-partition vlan-range [ vlanIdStart vlanIdEnd ]`

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Adds a range of VLANs to the ICR partition. You can assign only unique VLANs to the partition. If you attempt to assign a previously assigned VLAN range to the ICR partition, the router displays an error message. You can assign VLANs only if you have selected VLAN based grouping by using the **ip vrrp icr-partition group** command. The **no** version deletes the VLAN range from the ICR partition.



**NOTE:** You can use the listed optional parameters only when you add a VLAN or a range of VLANs to the ICR partition. You cannot modify an existing subinterface using these parameters. You can specify the optional parameters in any order.

- Options**
- **vrid**—VRID identifier; a number in the range 1–255
  - **vlanIdStart**—Starting VLAN ID of the VLAN subrange you are configuring; a number in the range 0–4095
  - **vlanIdEnd**—Ending VLAN ID of the VLAN subrange you are configuring; a number in the range 0–4095
  - **use-default-mac**—Configures the VLAN range to use the default MAC address. By default, the router assigns the VRRP MAC address to all subinterfaces of the ICR partition.
  - **control-interface**—Controls traffic on a range of subinterfaces that are part of a backup partition. When you use this option, the router changes the state of the corresponding range of subinterfaces to Admindown. When the subinterfaces are in Admindown state, the router blocks all traffic to the interfaces. However, the router does not block advertisements as long as VRRP is running on a separate subinterface. The router changes the state of the range of subinterfaces from Admindown to Up when the state of the partition changes from backup partition to master.
  - **advertise-mac**—Enables subinterfaces to transmit GARP advertisements when the partition moves from backup state to master state. By default, GARP advertisements are blocked on subinterfaces.

**Mode** Interface Configuration, Subinterface Configuration

**Related Documentation**

- Grouping ICR Subscribers Based on VLAN IDs

- Configuring ICR Partitions

## ip vrrp preempt

---

**Syntax** [ no ] ip vrrp *vrid* preempt

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables VRRP preemption. The **no** version disables VRRP preemption. The default is enabled.

**Options** • *vrid*—VRID identifier; a number in the range 1–255

**Mode** Interface Configuration

## ip vrrp priority

**Syntax**    `ip vrrp vrid priority priorityValue`  
               `no ip vrrp vrid priority`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the priority of VRRP routers. The **no** version restores the default value, 100.



**NOTE:** If you configure VRRP on a virtual router and associate the IP address with the VRRP instance ID (VRID) so that the virtual address becomes the interface address of the router, the priority of the router automatically changes to 255 making it the master router. This change of priority occurs in JunosE Software Releases 11.0.0 and higher-numbered releases and later to enable full compliance with RFC-Virtual Router Redundancy Protocol (VRRP) (April 2004).

Also, you cannot configure the priority of the VRRP router as 255 by using the **ip vrrp priority** command, unless you configured the router to automatically learn associated addresses by using the **auto** keyword with the **ip vrrp virtual-address** command. In addition, if you change the virtual address of the VRRP router, which is operating as the IP address owner, to an IP address that is no longer the IP address owner, the priority changes automatically to the default value of 100.

- Options**
- *vrid*—VRID identifier; a number in the range 1–255
  - *priorityValue*—Priority value of the VRRP router; a number in the range 1–255; default value is 100

**Mode**    Interface Configuration

## ip vrrp timers-learn

---

**Syntax** [ no ] ip vrrp *vrid* timers-learn

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Configures the VRRP instance to learn the VRRP advertisement interval from the master VRRP instance. This feature is useful only when you have configured different advertisement intervals for the master VRRP instance and the backup VRRP instance. This feature enables the unified ISSU operation to proceed successfully. The **no** version disables the learning timer for the VRRP instance. If you have configured different advertisement intervals for the VRRP master and VRRP backup instances, the VRRP session breaks, and both instances behave like the master instance, and the router displays an error message.

**Options** • *vrid*—VRID identifier; a number in the range 1–255

**Mode** Interface Configuration, Subinterface Configuration



## ip vrrp track

---

**Syntax** `ip vrrp vrid track objectName [ decrement priorityValue ]`

`no ip vrrp vrid track objectName`

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Tracks a specified object and changes the priority of that object when the state of the object changes from an up state to a down state. The priority is decremented by the specified value or by the default value (100; when no decrement value is specified). The object priority is restored when the state of the object changes from a down state to an up state. The **no** version disables any tracking for the object.

- Options**
- *vrid*—VRID identifier; a number in the range 1–255
  - *objectName*—Name of the object to track
  - *priorityValue*—Priority value of the VRRP router; a number in the range 1–255; default value is 100

**Mode** Interface Configuration

## ip vrrp virtual-address

---

**Syntax**    `ip vrrp vrid virtual-address { auto | ipAddress ipAddress [ ipAddress ipAddress ]* }`  
`no ip vrrp vrid virtual-address [ ipAddress ipAddress ]*`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Associates an IP address with a VRID. The **no** version removes a list of IP addresses associated with a VRID. The **no** version clears the auto flag, if auto addresses are being used. There is no default.

- Options**
- *vrid*—VRID identifier; a number in the range 1–255
  - *auto*—Automatically learns or configures associated addresses depending on the priority.
  - *ipAddress*—IP address
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Interface Configuration

## ipsec ca authenticate

---

**Syntax**    ipsec ca authenticate *caName*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Obtains the specified CA's public key (a self-signed certificate) during online digital certificate configuration. The CA must be previously declared by the **ipsec ca identity** command. There is no **no** version; however, to remove the CA certificate, issue the **no ipsec ca identity** command for the specified CA or boot the router using the factory defaults.

**Options**    • *caName*—Name of CA

**Mode**    Global Configuration

## ipsec ca enroll

---

**Syntax**    ipsec ca enroll *caName* [ *password* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Generates a certificate request to the specified CA and retrieves the public key certificate for the router during online digital certificate configuration. The CA must be previously declared by the **ipsec ca identity** command. There is no **no** version.

**Options**

- *caName*—Name of CA
- *password* —Challenge password to access the CA and enable enrollment

**Mode**    Global Configuration

## ipsec ca identity

---

**Syntax** [ no ] ipsec ca identity *name*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the certificate authority (CA) that the router uses for certificate requests and enters IPSec Identity Configuration mode during online digital certificate configuration. The **no** version deletes the identity information and the certificates associated with the specified CA.

**Options** • *name*—Name of CA

**Mode** Global Configuration

## ipsec certificate-database refresh

---

**Syntax** ipsec certificate-database refresh

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Informs the E Series router that a public key certificate has been copied to the router.  
There is no **no** version.

**Mode** Global Configuration

## ipsec certificate-request generate

---

**Syntax** ipsec certificate-request generate rsa *fileName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Generates a certificate request. There is no **no** version.

- Options**
- **rsa**—Specifies that the certificate request is issued for the RSA public key
  - ***fileName***—Name of the certificate request file generated on the E Series router; the filename must include a .crq extension

**Mode** Global Configuration

## ipsec clear sa

---

**Syntax** ipsec clear sa { all [ state *tunnelState* ] | tunnel *tunnelName* } [ phase { 1 | 2 } ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Refreshes ISAKMP/IKE or IPSec SAs. There is no **no** version.

- Options**
- all—Reinitializes all SAs
  - state—Reinitializes SAs on tunnels that are in a specific state
  - *tunnelState*—State of tunnel, up, down, not-present
  - tunnel—Specifies that an SA on a specific tunnel is to be reinitialized
  - *tunnelName*—Name of tunnel
  - phase—Specifies one of the following types of tunnel to be reinitialized:
    - 1—ISAKMP/IKE tunnels
    - 2—IPSec tunnels

**Mode** Global Configuration



---

## ipsec crl

---

**Syntax** ipsec crl { ignored | optional | required }  
no ipsec crl

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls how the router checks certificate revocation lists (CRLs) when determining whether to accept a peer's certificates. The **no** version restores the default setting.



.....  
**NOTE:** This command is replacing the **ike crl** command. The **ike crl** command may be removed completely in a future release.  
.....

- Options**
- **ignored**—Specifies that the router will not try to find or use CRLs
  - **optional**—Specifies that the router will try to find a CRL. If a CRL is found, the peer certificate must not appear in the CRL. If no CRL is found, the peer can still authenticate; this is the default.
  - **required**—Specifies that the router must find a valid CRL; the CRL must be current, and the peer certificate must not appear in the CRL

**Mode** Global Configuration

## ipsec identity

---

**Syntax** [ no ] ipsec identity

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the identity that the router uses in certificate requests and during negotiations with its peers. The **no** version removes the identity configuration.

**Mode** Global Configuration

---

## ipsec ike-policy-rule

---

**Syntax**    ipsec ike-policy-rule *priority*  
              no ipsec ike-policy-rule [ *priority* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines and prioritizes an ISAKMP/IKE policy. ISAKMP/IKE policies define parameters to be used during ISAKMP/IKE negotiation. You can have up to 10 ISAKMP/IKE policies per router. The **no** version removes a policy. If you do not include a priority number with the **no** version, the software removes all ISAKMP/IKE policies.



.....  
**NOTE:** This command is replacing the **ipsec isakmp-policy-rule** command. The **ipsec isakmp-policy-rule** command may be removed completely in a future release.  
.....

**Options**    • *priority*—Identifies and prioritizes the ISAKMP/IKE policy; in the range 1 to 10000, with 1 having the highest priority

**Mode**    Global Configuration

## ipsec isakmp-policy-rule

---

**Syntax**    ipsec isakmp-policy-rule *priority*  
              no ipsec isakmp-policy-rule [ *priority* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines and prioritizes an ISAKMP/IKE policy. ISAKMP/IKE policies define parameters to be used during ISAKMP/IKE negotiation. You can have up to 10 ISAKMP/IKE policies per router. The **no** version removes a policy. If you do not include a priority number with the **no** version, the software removes all ISAKMP/IKE policies.



.....  
**NOTE:** This command has been replaced by the [ipsec ike-policy-rule](#) command and may be removed completely in a future release.  
.....

**Options**    • *priority*—Identifies and prioritizes the ISAKMP/IKE policy; in the range 1–10000, with 1 having the highest priority

**Mode**    Global Configuration

## ipsec key generate

---

**Syntax**    ipsec key generate rsa { 1024 | 2048 }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Generates RSA key pairs. Specify the length of the key in bits, either 1024 or 2048. There is no **no** version. To remove a key pair, use the **ipsec key zeroize** command.

**Mode**    Global Configuration

## ipsec key manual pre-share

---

**Syntax** [ no ] ipsec key manual pre-share { *ipAddress* | ip address *ipAddress* | identity *fqdn* | local-ip-address *localIpAddress* [ remote-ip-address *remoteIpAddress* ] }

**Release Information** Command introduced before JunosE Release 7.1.0.  
**local-ip-address** and **remote-ip-address** keywords added in JunosE Release 7.3.0.  
*localIpAddress* and *remoteIpAddress* variables added in JunosE Release 7.3.0.

**Description** Specifies a preshared key for a remote peer, indexed by remote IP or remote identity. It can also specify a preshared key which is indexed by the local ip / remote IP pair for use in specific pairings or in group preshared keys (remote is wildcard 0.0.0.0).

Manually configured keys are used during the tunnel establishment phase when the ISAKMP/IKE policy specifies preshared key authentication.

You can identify the remote peer by either IP address or fully qualified domain name (FQDN). The **no** version deletes a preshared key.



**NOTE:** You must enter this command in the virtual router context where the IP address or FQDN of the peer is defined.

- Options**
- *ipAddress*—Address of the peer for which the key can be used
  - *fqdn*—Fully qualified domain name of the peer for which the key can be used; a maximum of 80 characters
  - *localIpAddress*—Address of the local peer for which the key can be used
  - *remoteIpAddress*—Address of the remote peer for which the key can be used

**Mode** Global Configuration

---

## ipsec key pubkey-chain rsa

---

**Syntax** [ no ] ipsec key pubkey-chain rsa { address *ipAddress* | name *identityString* }

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables you to configure the public key for a remote peer with which you want to establish IKE SAs. This command accesses IPSec Peer Public Key Configuration mode, from which you can enter the peer public key data without the need for a digital certificate. Public keys are used during the tunnel establishment phase when the ISAKMP/IKE policy specifies RSA digital signature authentication. The **no** version removes the peer public key from the router.

- Options**
- *ipAddress*—IP address of the peer for which the public key can be used, in 32-bit dotted decimal format (for example, 192.168.32.2)
  - *identityString*—Identity of the remote peer for which the public key can be used, either in fully qualified domain name (FQDN) format (for example, group003.customer535.isp.net) or in FQDN format preceded by an optional *user@* specification (for example, tsmith@group003.customer535.isp.net); maximum of 80 characters

**Mode** Global Configuration

## ipsec key zeroize

---

**Syntax** ipsec key zeroize { rsa | pre-share | all }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Deletes RSA key pairs. There is no **no** version.

- Options**
- **rsa**—Removes the RSA key pair from the router
  - **pre-share**—Removes all preshared keys from the router
  - **all**—Removes all keys within the VR context from the router

**Mode** Global Configuration



## ipsec lifetime

---

**Syntax** [ no ] ipsec lifetime { kilobytes *kilobytes* | seconds *seconds* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the default lifetime in volume of traffic or seconds. The default lifetime applies to secure tunnels that do not have a tunnel lifetime defined. When either the volume of traffic or number of seconds limit is reached, IPSec renegotiates the SA. The **no** version restores the default values.

- Options**
- *kilobytes*—Volume of traffic in kilobytes that can pass between IPSec peers before the SA expires; in the range 102400–4294967295; default value is 4294967295 kilobytes; a setting of zero turns off the kilobyte lifetime
  - *seconds*—Number of seconds an SA lives before expiring; in the range 7200–4294967295; default value is 28800 seconds (8 hours)

**Mode** Global Configuration

## ipsec local-endpoint

---

**Syntax** [ no ] ipsec local-endpoint *ipAddress* transport-virtual-router *transportVRName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a default local endpoint used for ISAKMP/IKE negotiations and all IPSec tunnels for a transport virtual router. The **no** version restores the default settings of the local endpoint.

- Options**
- *ipAddress*—IP address to use as the local endpoint
  - *transportVRName*—Name of transport virtual router in which the IP address is defined

**Mode** Global Configuration

## ipsec option dpd

---

**Syntax** [ no ] ipsec option dpd

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IPSec dead peer detection (DPD) for the current virtual router. With DPD enabled, the router detects when connectivity between the router and an IPSec peer has been terminated. The router then sets the status for the tunnel and the upper layer interfaces to down, which enables routing protocols to take alternate routes. Also, administrators can then take corrective action. The **no** version restores the default DPD setting, disabled.

**Mode** Global Configuration

## ipsec option nat-t

---

**Syntax** [ no | default ] ipsec option nat-t

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IPSec Network Address Translation Traversal (NAT-T) for the current virtual router. With NAT-T enabled, IPSec traffic flows transparently through a NAT device, thereby allowing one or more remote hosts located behind the NAT device to use secure L2TP/IPSec tunnels to access the router. The **ipsec option nat-t** command affects only IKE SAs negotiated on this virtual router after the command is issued; it has no effect on previously negotiated IKE SAs. The **no** version disables NAT-T for the current virtual router. The **default** version restores the default NAT-T setting, enabled.

**Mode** Global Configuration

## ipsec option tx-invalid-cookie

---

**Syntax** [ no ] ipsec option tx-invalid-cookie

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Enables transmission of invalid cookie notification for the current virtual router (transport VR). With invalid cookie notification enabled, the router signals to an ISAKMP peer when it does not recognize an IKE phase 1 message received from the peer. The **no** version restores the default setting, disabled.

**Mode** Global Configuration

## ipsec transform-set

---

**Syntax**    ipsec transform-set *transformSetName* *transform0*  
              [ *transform1* [ *transform2* [ *transform3* [ *transform4* [ *transform5* ] ] ] ] ]

no ipsec transform-set *transformSetName*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates a transform set. Transform sets used for manually configured tunnels can have only one transform. Transform sets used for signaled tunnels can have up to six transforms. Transforms are numbered in a priority sequence in the order in which you enter them. Each transform provides a different combination of data authentication and confidentiality. The **no** version deletes the transform set.

- Options**    • *transformSetName*—Name of the transform set
- *transform0* through *transform5*—AH or ESP transform; use the online Help to view available transforms

**Mode**    Global Configuration

## ipsec transport profile

---

**Syntax** [ no ] ipsec transport profile { *profileName* [ [ virtual-router *vrName* ]  
ip address *ipAddress* ] | [ *virtual-router vrName* ] ip address *ipAddress* }  
  
no ipsec transport profile { *profileName*  
| [ virtual-router *vrName* ] ip address *ipAddress* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or configures a transport profile for IPSec and accesses the IPSec Transport Profile Configuration mode. The **no** version deletes the transport profile.

**Options**

- *profileName*—Name of the transport profile
- *vrName*—Name of the VR on which you want to create the profile. If you do not specify a virtual router, the current virtual router context is used
- *ipAddress*—Remote endpoint for the IPSec transport connection. You can enter a single IP address or the wildcard address of 0.0.0.0. If you use the wildcard address, the profile accepts any remote client connection, which is a typical scenario for secure remote access.

**Mode** Global Configuration

## ipsec tunnel profile

---

**Syntax**    ipsec tunnel profile *profileName* [ virtual-router *vrName* ]  
              no ipsec tunnel profile *profileName*

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Creates or configures a tunnel profile for IPSec and accesses the IPSec Tunnel Profile Configuration mode (config-ipsec-tunnel-profile). The **no** version deletes the tunnel profile.

**Options**    • *profileName*—Name of the tunnel profile  
              • *vrName*—Name of the VR on which you want to create the profile. If you do not specify a virtual router, the current virtual router context is used

**Mode**    Global Configuration



---

## ipv6

---

**Syntax** [ no ] ipv6

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables an IPv6 instance on a router that does not already have an explicit IPv6 address. Normally, performing any IPv6 configuration automatically enables IPv6 on the interface. The **no** version disables IPv6 on the router.



.....

**NOTE:** Disabling IPv6 on the router causes only the IPv6 routing protocol-related configurations to be removed. The previously configured IPv6 policy settings, such as policy lists, classifier lists, and rate-limit profiles, and local address pools for IPv6 subscribers are not removed because these parameters can be configured without configuring an IPv6 license.

.....

**Mode** Global Configuration

## ipv6 access-list

---

**Syntax** Extended IPv6 access list:

```
ipv6 access-list accessListName { permit | deny } { srcIPv6Prefix |  
host srcIPHost | any } { dstIPv6Prefix | host dstIPHost | any } [ log ]  
  
no ipv6 access-list accessListName [ { permit | deny } { srcIPv6Prefix |  
host srcIPv6Host | any } { dstIPv6Prefix | host dstIPv6Host | any } [ log ] ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an IPv6 access list. The extended access list enables you to specify a destination address or host, precedence, and type of service. Imposes an implicit last rule of “deny ip any any” to deny all routes that do not match previous rules in the access list. The **no** version removes the IPv6 access list, the specified entry in an access list, or the log for a specified entry.

- Options**
- *accessListName*—String of up to 32 alphanumeric characters
  - permit—Permits access if the conditions are matched
  - deny—Denies access if the conditions are matched
  - *srcIPv6Prefix*—Source IPv6 address and mask length from which the packet is being sent
  - *srcIPv6Host*—Source host IPv6 address; assumes a mask length of 128
  - any—Creates an address of :: with a mask length of 0
  - *dstIPv6Prefix*—Destination IP address and mask length
  - *dstIPv6Host*—Destination host IPv6 address to which the packet is being sent
  - log—Logs an Info event into the ipAccessList log whenever the access-list rule is matched

**Mode** Global Configuration

## ipv6 access-route table-map

---

**Syntax**    `ipv6 access-route [ vrf vrfName ] table-map mapName`  
              `no ipv6 access-route [ vrf vrfName ] table-map [ mapName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **vrf** keyword and *vrfName* variable added in JunosE Release 7.2.0.

**Description**    Filters access routes before an access list adds them to the routing table. The **no** version deletes the table map.

**Options**    • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters  
              • *mapName*—Name of the table map that you want the router to use

**Mode**    Global Configuration

## ipv6 address

**Syntax** [ no ] ipv6 address *ipv6Prefix* [ eui-64 ]  
 [ no ] ipv6 address [ *ipv6Address maskLength* [ eui-64 ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns an IPv6 address (or network) to an interface and enables IPv6 processing on that interface. The **no** version deletes the association from the interface.



**NOTE:** The link-local address for an interface is automatically configured when IPv6 is enabled on the interface.

- Options**
- *ipv6Prefix*—Prefix that defines the IPv6 interface or network in the format *ipv6Address / length*, where
    - *ipv6Address*—Base IPv6 address of the network route that you want to filter (for example, ::ffff:a:b:c:d)
    - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched
  - *ipv6Address*—Base IPv6 address of the network route that you want to filter (for example, ::ffff:a:b:c:d); the *ipv6Address* must appear in hexadecimal format using 16-bit values between colons. Refer to RFC 2373—IP Version 6 Addressing Architecture (July 1998) for details.
  - *maskLength*—Length of the IPv6 mask. A decimal value that indicates how many of the high-order contiguous bits of the address comprise the prefix (the network portion of the address).
  - eui-64—Specifies the use of the eui-64 interface identifier

**Mode** Interface Configuration, Profile Configuration

---

## ipv6 address-pool local

---

**Syntax** [ no ] ipv6 address-pool local

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Enables the IPv6 local address pool functionality to allow configuration of IPv6 local address pools to assign prefixes to DHCPv6 clients. The **no** version disables the IPv6 local address functionality.



.....  
**NOTE:** If you attempt to configure an IPv6 local address pool without enabling the IPv6 local pool feature, an error message is displayed.  
.....

**Mode** Global Configuration

## ipv6 address-pool ndra

---

**Syntax** [ no ] ipv6 address-pool ndra

**Release Information** Command introduced in JunosE Release 13.0.0.

**Description** Enables the IPv6 local address pool functionality to allow configuration of IPv6 local address pools for Neighbor Discovery router advertisements to assign prefixes to Neighbor Discovery router advertisements. The **no** version disables the IPv6 local address functionality for Neighbor Discovery router advertisements.



.....  
**NOTE:** If you attempt to configure an IPv6 local address pools for Neighbor Discovery router advertisements without enabling the IPv6 local address pools for Neighbor Discovery router advertisements feature, an error message is displayed.  
.....

**Mode** Global Configuration

**Related Documentation**

- Configuring IPv6 Neighbor Discovery Local Address Pools

## ipv6 block-multicast-sources

---

**Syntax** [ no ] ipv6 block-multicast-sources

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents mroute creation by blocking multicast traffic that has a scope larger than link-local (for example, global). The **no** version restores the default behavior of creating mroutes upon receiving multicast packets.

**Mode** Global Configuration

## ipv6 classifier-list

**Syntax** `ipv6 classifier-list classifierName [ traffic-class trafficClassName ]`  
`[ color { green | yellow | red } ] [ user-packet-class userPacketClassValue ]`  
`[ source-route-class routeClassValue ] [ destination-route-class routeClassValue ]`  
`[ local { true | false } ]`  
`[ source-address ipv6Prefix | source-host ipv6Address ]`  
`[ destination-address ipv6Prefix | destination-host ipv6Address ]`  
`[ precedence precNum | dsfield dsFieldNum | tcfield tcFieldNum ]`  
`[ protocol [ protocolQualifier ] ]`

`no ipv6 classifier-list classifierName [ classifierNumber ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies an IPv6 classifier control list. The **no** version removes the classifier control list.

- Options**
- *classifierName*—Name of the classifier control list entry
  - *trafficClassName*—Name of the traffic class to match
  - *green*—Matches packet color to green, indicating a low drop preference
  - *yellow*—Matches packet color to yellow, indicating a medium drop preference
  - *red*—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—User packet value to match
  - *routeClassValue*—Value of the source or destination route-class; in the range 0–255
  - *local*—Specifies traffic destined for this interface
    - *true*—Matches packets that are locally destined
    - *false*—Matches packets that are not locally destined
  - *ipv6Prefix*—Prefix that defines the IPv6 interface or network
  - *ipv6Address*—Base IPv6 address of the network route
  - *precNum*—Upper three bits of the traffic class byte; in the range 0–7
  - *dsFieldNum*—Upper six bits of the traffic class byte; in the range 0–63
  - *tcFieldNum*—Whole eight bits of the traffic class byte; in the range 0–255
  - *protocol*—Protocol type to match; **tcp**, **udp**, **icmpv6**, or protocol number in the range 0–255
  - *protocolQualifier*—Specifies the following protocol-specific parameters:
 

For TCP and UDP:

    - *source-port or destination-port*—Specifies that a source or destination port is matched



- *portOperator*—One of the following classifier parameters. See Creating or Modifying Classifier Control Lists for IPv6 Policy Lists for details.
  - lt—Less than
  - gt—Greater than
  - eq—Equal to
  - ne—Not equal
  - range—Range of port numbers
- *portNumber*—Port number of the source or destination port

For TCP only:

- *tcpFlag*; a logic equation that specifies flag bit values; ! means logical NOT and & means logical AND; use any of the following flag names:
  - ack—0x10
  - fin—0x01
  - psh—0x08
  - rst—0x04
  - syn—0x02
  - urg—0x20

For ICMPv6:

- *icmpType*—ICMP message type
- *icmpCode*—ICMP message code
- *classifierNumber*—Index of the classifier control list entry to be deleted



**NOTE:** The `local-input` keyword for the `ipv6 policy` command is deprecated, and may be completely removed in a future release. The keyword should be removed from scripts.

You should recreate any local input policies using the `ipv6 classifier-list local true` command and attaching the policies using the `ipv6 policy secondary-input` command.

**Mode** Global Configuration

**Related Documentation**

- Creating or Modifying Classifier Control Lists for IPv6 Policy Lists

## ipv6 description

---

**Syntax**    `ipv6 description name`  
             `no ipv6 description`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a text description or an alias to an IPv6 interface or subinterface. Use the **show ipv6 interface** command to display the text description. The **no** version removes the description or alias.

**Options**    • *name*—Name for the IP interface; string of up to 256 characters

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 dhcpv6-local auth domain

---

<b>Syntax</b>	[ no ] ipv6 dhcpv6-local auth domain <i>domainName</i>
<b>Release Information</b>	Command introduced in JunosE Release 12.2.0.
<b>Description</b>	Specifies a domain name for a username that is locally configured for a DHCPv6 standalone mode client. In standalone mode, the locally configured username is presented to AAA in an authentication request. The <b>no</b> version removes the configured domain, which is the default behavior.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>domainName</i>—String of 1–32 characters used as the domain name</li></ul>
<b>Mode</b>	Global Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Authentication and Accounting of IPv6 Subscribers Using the DHCPv6 Local Server Overview</li><li>• Interoperation of Authentication of IPv6 Clients and Display of Active Subscriber Information</li><li>• Configuring AAA Authentication for DHCPv6 Local Server Standalone Mode</li></ul>

## ipv6 dhcpv6-local auth include

---

**Syntax** [ no ] ipv6 dhcpv6-local auth include { circuit-type | circuit-identifier }

**Release Information** Command introduced in JunosE Release 12.2.0.

**Description** Includes optional information as part of the locally configured username for a DHCPv6 standalone mode client. In standalone mode, the username is presented to AAA in an authentication request. The **no** version removes the circuit type and circuit identifier information, which is the default behavior.

**Options**

- circuit-type—Specifies the circuit type of the interface on which the DHCPv6 client's request was received
- circuit-identifier—Specifies the circuit identifier of the interface on which the DHCPv6 client's request was received

**Mode** Global Configuration

**Related Documentation**

- Authentication and Accounting of IPv6 Subscribers Using the DHCPv6 Local Server Overview
- Interoperation of Authentication of IPv6 Clients and Display of Active Subscriber Information
- Configuring AAA Authentication for DHCPv6 Local Server Standalone Mode

## ipv6 dhcpv6-local auth password

---

**Syntax** [ no ] ipv6 dhcpv6-local auth password *password*

**Release Information** Command introduced in JunosE Release 12.2.0.

**Description** Assigns a password used to authenticate a locally configured DHCPv6 standalone mode client. In DHCPv6 standalone mode, the password is presented to AAA in an authentication request. The **no** version removes the password configured for the user, which is the default behavior.

**Options** • *password*—String of 1–32 characters used as the password

**Mode** Global Configuration

**Related Documentation**

- Authentication and Accounting of IPv6 Subscribers Using the DHCPv6 Local Server Overview
- Interoperation of Authentication of IPv6 Clients and Display of Active Subscriber Information
- Configuring AAA Authentication for DHCPv6 Local Server Standalone Mode

## ipv6 dhcpv6-local auth user-prefix

---

**Syntax** [ no ] ipv6 dhcpv6-local auth user-prefix *userNamePrefix*

**Release Information** Command introduced in JunosE Release 12.2.0.

**Description** Specifies a user prefix for a username that is locally configured for a DHCPv6 standalone mode client. In DHCPv6 standalone mode, the username is presented to AAA in an authentication request. The **no** version removes the user prefix, which is the default behavior.

**Options**

- *userNamePrefix*—String of 1–32 characters used as the prefix for a locally configured username

**Mode** Global Configuration

**Related Documentation**

- Authentication and Accounting of IPv6 Subscribers Using the DHCPv6 Local Server Overview
- Interoperation of Authentication of IPv6 Clients and Display of Active Subscriber Information
- Configuring AAA Authentication for DHCPv6 Local Server Standalone Mode

## ipv6 dhcpv6-local delegated-prefix

---

**Syntax**    `ipv6 dhcpv6-local delegated-prefix ipv6Prefix`  
              `[ lifetime { days [ hours [ minutes [ seconds ] ] ] | infinite } ]`  
  
              `no ipv6 dhcpv6-local delegated-prefix`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IPv6 prefix and lifetime that is to be delegated, when requested, to the DHCPv6 client on this interface by the DHCPv6 local server. This lifetime overrides the default lifetime that is set in Global Configuration mode. If no lifetime is specified, the default lifetime is used. The **no** version removes the IPv6 prefix from the interface.

**Options**

- *ipv6Prefix*—Prefix that defines the IPv6 interface
- *days*—Number of days in the lifetime; in the range 0–32768
- *hours*—Number of hours in the lifetime; in the range 0–24
- *minutes*—Number of minutes in the lifetime; in the range 0–60
- *seconds*—Number of seconds in the lifetime; in the range 0–60
- *infinite*—Assigns a lifetime that does not expire

**Mode**    Interface Configuration

## ipv6 dhcpv6-local dns-domain-search

---

**Syntax** [ no ] ipv6 dhcpv6-local dns-domain-search *dnsDomainName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Adds the specified DNS domain name to the domain search list. The **no** version removes the specified domain name from the search list.

**Options** • *dnsDomainName*—Name of DNS domain name

**Mode** Global Configuration



## ipv6 dhcpv6-local dns-server

---

**Syntax** [ no ] ipv6 dhcpv6-local dns-server *ipv6Address*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns the specified DNS server to all DHCPv6 clients in the current virtual router. The **no** version removes the specified DNS server.

**Options** • *ipv6Address*—IPv6 address of the DNS server

**Mode** Global Configuration

## ipv6 dhcpv6-local duid-type

---

**Syntax**    `ipv6 dhcpv6-local duid-type duidType`

`no ipv6 dhcpv6-local duid-type`

**Release Information**    Command introduced in JunosE Release 12.2.0.

**Description**    Specifies the DHCP unique identifier (DUID) type that the DHCPv6 local server running on the router uses in communication with the DHCPv6 client and for verifying the identity of the client. Both the server and the client are identified by a DUID. By default, the DHCPv6 local server uses the Type 2 server DUID in the communication between the delegating router and the requesting router, which is the customer premises equipment (CPE) at the edge of the remote client site that acts as the DHCP client. The **no** version removes the configured DUID type and the router reverts to the default Type 2 DUID for the client to identify the server.

**Options**    • *duidType*—DUID type can be either 2 or 3; the default value is 2



**NOTE:** You must enable the DHCPv6 local server using the service **dhcpv6-local** command before configuring the DUID type. Otherwise, an error message states that the DHCPv6 local server is not configured on the router.

**Mode**    Global Configuration

**Related Documentation**    • DHCP Unique ID for Clients and Servers Overview  
• Configuring the Type of DHCP Unique ID for DHCPv6 Local Servers

## ipv6 dhcpv6-local prefix-lifetime

---

**Syntax**    `ipv6 dhcpv6-local prefix-lifetime { days [ hours [ minutes [ seconds ] ] ] | infinite }`  
              `no ipv6 dhcpv6-local prefix-lifetime`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the default lifetime for which a prefix delegated by this DHCPv6 local server is valid. This default is overridden by the interface-specific lifetime. The **no** version restores the default lifetime to 1 day.

- Options**
- *days*—Number of days in the lifetime; in the range 0–32768
  - *hours*—Number of hours in the lifetime; in the range 0–24
  - *minutes*—Number of minutes in the lifetime; in the range 0–60
  - *seconds*—Number of seconds in the lifetime; in the range 0–60
  - *infinite*—Assigns a lifetime that does not expire

**Mode**    Global Configuration

## ipv6 dos-protection-group

---

**Syntax**    `ipv6 dos-protection-group groupName`  
              `no ipv6 dos-protection-group`

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches an IPv6 denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## ipv6 enable

---

**Syntax** [ no ] ipv6 enable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IPv6 processing on an interface that does not already have an explicit IPv6 address. The **no** version disables IPv6 processing on the interface.

**Mode** Interface Configuration

## ipv6 hop-limit

---

**Syntax**    `ipv6 hop-limit [ vrf vrfName ] hopLimit`  
              `no ipv6 hop-limit [ vrf vrfName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **vrf** keyword and *vrfName* variable added in JunosE Release 7.2.0.

**Description**    Specifies the maximum number of hops that the router can use in router advertisements and all IPv6 packets. The **no** version sets the hop limit for IPv6 packets to 255 hops and router advertisements to zero [0] hops (or “ unspecified” ).

**Options**

- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
- *hopLimit*—Maximum number of hops (from 1 to 255) that the router can use in router advertisements and in all IPv6 packets; the original default value is 64 hops

**Mode**    Global Configuration

## ipv6 http

---

**Syntax** [ no ] ipv6 http

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Creates the HTTP local server for IPv6. The **no** version deletes the HTTP local server.

**Mode** Global Configuration

**Related Documentation**

- *Configuring the HTTP Server to Support Guided Entrance in the JunosE Broadband Access Configuration Guide*

## ipv6 http port

---

**Syntax**    `ipv6 http port portNumber`  
`no ipv6 http port`

**Release Information**    Command introduced in JunosE Release 10.1.0.

**Description**    Specifies the port on which the HTTP local server receives connection attempts for IPv6. The **no** version restores the default port number.



.....  
**NOTE:** Port numbers from 1 to 1024 are known as reserved ports. We recommend that you specify a port number that does not belong to this range.  
.....

**Options**    • *portNumber*—Number of the port, in the range 0–65535; the default is port 80

**Mode**    Global Configuration

**Related Documentation**    • *Configuring the HTTP Server to Support Guided Entrance in the JunosE Broadband Access Configuration Guide*



## ipv6 http redirectUrl

**Syntax**    `ipv6 http redirectUrl url [ preserveOriginalUrl ]`

`no ipv6 http redirectUrl`

**Release Information**    Command introduced in JunosE Release 10.1.0.  
 Profile Configuration mode added in JunosE Release 11.0.0.  
**preserveOriginalUrl** keyword added in JunosE Release 12.3.0.

**Description**    Specifies the URL to which a subscriber's initial Web browser session is redirected, enabling initial provisioning and service selection for the subscriber. The first access session is typically used by the Service Manager application to provide initial provisioning and service selection for the subscriber. The **no** version removes the redirection action.



**NOTE:** The HTTP local server must be configured and enabled in the virtual router for the interface on which you use this command. Otherwise, the URL redirect operation will fail.

- Options**
- *url*—Name of the URL; 230 characters maximum
  - `preserveOriginalUrl` —Enables the preservation of the subscriber's originally requested URL

**Mode**    Interface Configuration, Subinterface Configuration, Profile Configuration

**Related Documentation**

- Configuring the Preservation of the Original URL During Redirection of Subscriber Sessions

## ipv6 http server

---

**Syntax** [ no ] ipv6 http server

**Release Information** Command introduced in JunosE Release 10.1.0.

**Description** Enables the HTTP local server to listen for and process IPv6 exception packets. The **no** version disables the HTTP local server.

**Mode** Global Configuration

**Related Documentation**

- *Configuring the HTTP Server to Support Guided Entrance in the JunosE Broadband Access Configuration Guide*

## ipv6 initial-sequence-preference

---

**Syntax**    `ipv6 initial-sequence-preference preference`  
              `no ipv6 initial-sequence-preference`

**Release Information**    Command introduced in JunosE Release 9.3.0.

**Description**    Configures the warm restart replay preference for an IPv6 interface after a high availability switchover. The **no** version restores the default value.

**Options**    • *preference*—Preference value, 0 or 1; 1 indicates highest preference; default value is 0

**Mode**    Subinterface Configuration

## ipv6-local-interface

---

**Syntax**    `ipv6-local-interface { loopback interfaceSpecifier | ipv6Prefix }`  
              `no ipv6-local-interface`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Maps a domain name to a loopback interface. The **no** version deletes the mapping to the user domain name.

- Options**
- *interfaceSpecifier*—Particular loopback interface
  - *ipv6Prefix*—Prefix that defines the IPv6 interface in the format *ipv6Address / length*, where
    - *ipv6Address*—Base IPv6 address of the loopback interface (for example, ::ffff:a:b:c:d)
    - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched

**Mode**    Domain Map Configuration

## ipv6 local ndra-pool

---

**Syntax**    `ipv6 local ndra-pool poolName`  
`no ipv6 local ndra-pool poolName [ force ]`

**Release Information**    Command introduced in JunosE Release 13.0.0.

**Description**    Accesses IPv6 NdRa Pool Configuration mode. Specifies the IPv6 local address pool from which prefixes are allocated to the requesting router in networks that use Neighbor Discovery router advertisements. The **no** version removes the IPv6 local address pool.

- Options**
- *poolName*—Name of the IPv6 local address pool to be used to delegate prefixes to the requesting routers or Neighbor Discovery router advertisement clients; string of up to 16 alphanumeric characters
  - *force*—Forcibly deletes an IPv6 local address pool from which prefixes have been allocated. When a pool from which prefixes have been assigned to Neighbor Discovery router advertisement clients is deleted, the corresponding Neighbor Discovery router advertisement bindings are also deleted.

**Mode**    Global Configuration

**Related Documentation**

- [Configuring IPv6 Neighbor Discovery Local Address Pools](#)

## ipv6 local pool

---

**Syntax**    `ipv6 local pool poolName`  
              `no ipv6 local pool poolName [ force ]`

**Release Information**    Command introduced in JunosE Release 10.1.0.

**Description**    Accesses IPv6 Local Pool Configuration mode. Specifies the IPv6 local address pool from which prefixes are allocated to the requesting router in networks that use DHCPv6. The **no** version removes the IPv6 local pool.

- Options**
- *poolName*—Name of the IPv6 local address pool to be used to delegate prefixes to the requesting routers or DHCPv6 clients; string of up to 16 alphanumeric characters
  - **force**—Forcibly deletes an IPv6 local address pool from which prefixes have been allocated. When a pool from which prefixes have been assigned to DHCPv6 clients is deleted, the corresponding DHCPv6 bindings are also deleted.

**Mode**    Global Configuration

## ipv6 mld

---

**Syntax** [ no ] ipv6 mld

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables MLD on an interface, and sets the MLD version to MLDv2. The **no** version disables MLD on an interface.

**Mode** Interface Configuration, Profile Configuration

## ipv6 mld access-group

---

**Syntax**    `ipv6 mld access-group accessListName`  
              `no ipv6 mld access-group`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Restricts hosts on this subnet to joining multicast groups on the specified IPv6 access list. The **no** version removes the association with the specified access list and allows hosts on the subnetwork to join any multicast group.

**Options**    • *accessListName*—Name of the access list; a string of up to 32 characters

**Mode**    Interface Configuration, Profile Configuration



## ipv6 mld access-source-group

---

**Syntax**    `ipv6 mld access-source-group accessListName`  
              `no ipv6 mld access-source-group`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Restricts hosts on this subnetwork to membership in those source groups (also known as “channels” ) permitted by the specified IPv6 access list. The **no** version removes any access list restriction.

**Options**    • *accessListName*—Name of the access list; a string of up to 32 characters

**Mode**    Interface Configuration, Profile Configuration

## ipv6 mld apply-oif-map

---

**Syntax**    `ipv6 mld apply-oif-map mapName`

`no ipv6 mld apply-oif-map`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Applies the specified outgoing interface (OIF) map to the current interface. The **no** version removes the outgoing interface map from the interface.

**Options**    • *mapName*—Name of the OIF map

**Mode**    Interface Configuration, Profile Configuration

## ipv6 mld explicit-tracking

---

**Syntax** [ no ] ipv6 mld explicit-tracking [ disable-if-mld-v1-detected ]

**Release Information** Command introduced in JunosE Release 8.2.0.

**Description** Enables explicit host tracking for IPv6 MLD interfaces. The **no** version disables explicit host tracking on the interface or with the **disable-if-mld-v1-detected keyword** reverts to the default explicit host tracking.

**Options**

- **disable-if-mld-v1-detected**—Disables explicit host tracking if MLD V1 hosts detected on MLD V2 interfaces

**Mode** Interface Configuration, Profile Configuration

## ipv6 mld group limit

---

**Syntax**    `ipv6 mld group limit groupLimit`  
             `no ipv6 mld group limit`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Limits the number of MLD groups that an interface can accept. The **no** version restores the default situation, in which there is no limit to the number of MLD groups that the interface accepts.

**Options**    • *groupLimit*—Maximum number of MLD groups that an interface can accept, in the range 0–64,000

**Mode**    Interface Configuration, Profile Configuration

---

## ipv6 mld immediate-leave

---

**Syntax** [ no ] ipv6 mld immediate-leave

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Removes an interface immediately when the router receives a leave group membership message from the host associated with this interface. The **no** version restores the default situation, in which the router issues query messages to multicast groups and removes an interface if the associated host does not return a group membership report within a certain length of time.



.....  
**CAUTION:** Issue this command only on MLDv1 interfaces to which one MLD client is connected. Do not issue this command to interfaces to which more than one MLD client is connected.  
.....

**Mode** Interface Configuration, Profile Configuration

## ipv6 mld last-member-query-interval

---

**Syntax**    `ipv6 mld last-member-query-interval tenthsOfaSecond`

`no ipv6 mld last-member-query-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies in tenths of a second the maximum time the router waits for a response after sending a last member query. The router sends a last member query when it receives an MLDv1 leave message or an MLDv2 state change report. The **no** version restores the default value, 10 tenths of a second (1 second).

**Options**

- *tenthsOfaSecond*—Time interval to wait after sending out of a last member query in the range 1–254 tenths of a second. Using a lower value allows members to leave groups more quickly.

**Mode**    Interface Configuration, Profile Configuration

---

## ipv6 mld oif-map

---

**Syntax** [ no ] ipv6 mld oif-map *mapName* { *interfaceType interfaceSpecifier* | self }  
[ *groupPrefix* [ *sourcePrefix* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an outgoing interface (OIF) map. The **no** version removes an outgoing interface map attribute or the entire outgoing interface map.

- Options**
- *mapName*—Name of the OIF map
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - self—Specifies that the multicast outgoing interface is the same as IGMP join interface
  - *groupPrefix*—Group prefix in the form *ipv6Address/maskLength*
  - *sourcePrefix*—Source prefix in the form *ipv6Address/maskLength*

**Mode** Global Configuration

## ipv6 mld-proxy

---

**Syntax** [ no ] ipv6 mld-proxy

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables MLD proxy on an interface and specifies the version. Version 2 is enabled by default. The **no** version disables MLD proxy for an interface.

**Mode** Interface Configuration



---

## ipv6 mld-proxy unsolicited-report-interval

---

**Syntax**    `ipv6 mld-proxy unsolicited-report-interval tenths-of-a-second`  
              `no ipv6 mld-proxy unsolicited-report-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies how often the upstream interface should transmit unsolicited reports. This command has no effect on interfaces other than the upstream value. The **no** version transmits unsolicited reports using the default value, 100-tenths of a second (10 seconds).



.....  
**NOTE:** Issue this command only on the upstream interface. Otherwise, this command will have no effect.  
.....

**Options**    • *tenths-of-a-seconds*—Time interval at which the interface transmits unsolicited reports

**Mode**    Interface Configuration

## ipv6 mld-proxy version

---

**Syntax**    ipv6 mld-proxy version { 1 | 2 }  
              no ipv6 mld-proxy version

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the MLD proxy version for the interface. The **no** version restores the default value, MLDv2.

**Options**    • 1—Sets MLD version 1  
              • 2—Sets MLD version 2

**Mode**    Interface Configuration

## ipv6 mld querier-timeout

---

**Syntax**    `ipv6 mld querier-timeout seconds`  
              `no ipv6 mld querier-timeout`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time that the interface waits before declaring itself as the querier. The **no** version restores the default value, twice the query interval.

**Options**    • *seconds*—Time interval between the last query from the previous router and the first query from this interface

**Mode**    Interface Configuration, Profile Configuration

## ipv6 mld query-interval

---

**Syntax**    `ipv6 mld query-interval seconds`  
             `no ipv6 mld query-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets how often the router sends MLD host-query packets from this interface. The **no** version restores the default value, 125 seconds.

**Options**    • *seconds*—Polling interval in the range 0–65535 seconds

**Mode**    Interface Configuration, Profile Configuration

## ipv6 mld query-max-response-time

---

**Syntax**    `ipv6 mld query-max-response-time tenthsOfaSecond`  
              `no ipv6 mld query-max-response-time`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the period in tenths of a second during which the host is expected to respond to an MLD query. MLD version 1 includes this value in MLD query messages sent out on the interface. The **no** version restores the default value, 100 tenths of a second (10 seconds).

**Options**    • *tenthsOfaSecond*—Time interval between receipt of an MLD query and the response; in the range 1–254 tenths of a second.

**Mode**    Interface Configuration, Profile Configuration

## ipv6 mld robustness

---

**Syntax**    `ipv6 mld robustness numberOfMessages`  
              `no ipv6 mld robustness`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of times that the router sends MLD group-specific queries before declaring a group to no longer have any members on an interface. The **no** version restores the default value, 2.

**Options**

- *numberOfMessages*—Number of times that the router sends MLD group-specific queries in the range 1–4

**Mode**    Interface Configuration, Profile Configuration

---

## ipv6 mld ssm-map enable

---

**Syntax** [ no ] ipv6 mld ssm-map enable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables SSM mapping on the router. SSM mapping statically assigns sources to MLDv1 groups. You must use SSM mapping for MLDv1 hosts to interoperate with PIM SSM. SSM mapping allows the router to use a statically configured list to translate <\*G> memberships to <S,G> memberships. The **no** version disables the SSM map.



.....  
**NOTE:** To operate correctly, the static source addresses configured with the **ipv6 mld ssm-map static** command must fall within the configured PIM SSM range.  
.....

**Mode** Privileged Exec, User Exec

## ipv6 mld ssm-map static

---

**Syntax** [ no ] ipv6 mld ssm-map static *accessListName* *sourceAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an access list and source address for use in SSM mapping. SSM mapping statically assigns sources to MLDv1 groups. You must use SSM mapping for MLDv1 hosts to interoperate with PIM SSM. SSM mapping allows the router to use a statically configured list to translate <\*G> memberships to <S,G> memberships. The **no** version removes the SSM map association.



**NOTE:** To operate correctly, the static source addresses configured with the **ipv6 mld ssm-map static** command must fall within the configured PIM SSM range.

- Options**
- *accessListName*—Name of the access control list
  - *sourceAddress*—Address of the source

**Mode** Privileged Exec, User Exec



## ipv6 mld static-exclude

---

**Syntax** [ no ] ipv6 mld static-exclude *sourceAddress groupAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that an interface not handle multicast traffic for one or more (S,G) combinations. The **no** version removes the (S,G) exclusion from the interface.

**Options**

- *sourceAddress*—Address of the source
- *groupAddress*—Address of the group

**Mode** Interface Configuration, Profile Configuration

## ipv6 mld static-group

---

**Syntax** [ no ] ipv6 mld static-group *groupAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns an interface to handle all multicast traffic for a group. The interface sets no timers for this group. The **no** version removes the group from the interface.

**Options** • *groupAddress*—Address of the group

**Mode** Interface Configuration, Profile Configuration

## ipv6 mld static-include

---

**Syntax** [ no ] ipv6 mld static-include *sourceAddress groupAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns an interface to handle multicast traffic for one or more (S,G) combinations. The **no** version removes the (S,G) association from the interface.

- Options**
- *sourceAddress*—Address of the source
  - *groupAddress*—Address of the group

**Mode** Interface Configuration, Profile Configuration

## ipv6 mld version

---

**Syntax**    ipv6 mld version { 1 | 2 | passive }  
              no ipv6 mld version

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the MLD version for the interface. The **no** version restores the default value, MLDv1.

- Options**
- 1—Sets MLD version 1
  - 2—Sets MLD version 2
  - passive—Configures a mapped OIF as a passive interface with only multicast-data-forwarding capability

**Mode**    Interface Configuration, Profile Configuration

## ipv6 mtu

---

**Syntax**    `ipv6 mtu [ mtuSize ]`

`no ipv6 mtu`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum transmission unit size of IPv6 packets sent on an interface. The **no** version restores the default value.

**Options**

- *mtuSize*—Maximum number of packet transmissions permitted on an interface; in the range 160–10240; default value is 0, which means that the router takes the value from a lower protocol layer

**Mode**    Interface Configuration, Profile Configuration, Subinterface Configuration

## ipv6 multicast admission-bandwidth-limit

---

**Syntax** [ no ] ipv6 multicast admission-bandwidth-limit *limitValue*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies multicast admission bandwidth (in kilobits per second) for a given interface. The **no** version removes the admission bandwidth limit.

**Options**

- *limitValue*—Maximum admission bandwidth (in kilobits per second) permitted on an interface; default value is 0, which disables the limit

**Mode** Interface Configuration, Profile Configuration

## ipv6 multicast ioa-packet-replication

---

**Syntax**    ipv6 multicast ioa-packet-replication *interfaceType interfaceSpecifier*  
              no ipv6 multicast ioa-packet-replication

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Enables IPv6 hardware multicast packet replication on port 8 of a high-density Ethernet I/O module or IOA. The **no** version disables hardware multicast packet replication.

**Options**    • *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)  
              • *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Interface Configuration

## ipv6 multicast-routing

---

**Syntax** [ no ] ipv6 multicast-routing

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IPv6 multicast routing on the router. The **no** version disables IPv6 multicast routing on the router.

**Mode** Global Configuration



## ipv6 multicast-routing bandwidth-map

---

**Syntax**    `ipv6 multicast-routing bandwidth-map routeMapName`  
              `no ipv6 multicast-routing bandwidth-map`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables the QoS adjust function on the router. The **no** version disables the QoS adjust function on the router.

**Options**    • *routeMapName*—Name of the route map you want to use for the bandwidth map

**Mode**    Global Configuration

## ipv6 multicast-routing disable-rpf-check

---

**Syntax**    `ipv6 multicast-routing disable-rpf-check accessListName`  
              `no ipv6 multicast-routing disable-rpf-check`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Disables RPF checks for the (S,G) pairs in the specified access list. The **no** version restores the default situation, in which the router performs RPF checks for all (S,G) pairs.

**Options**    • *accessListName*—Name of the IPv6 access list that specifies the (S,G) pairs

**Mode**    Global Configuration

## ipv6 multicast-routing permanent-mroute

---

**Syntax**    `ipv6 multicast-routing permanent-mroute accessListName`  
              `no ipv6 multicast-routing permanent-mroute`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies that newly created mroutes that match the specified access-list do not get timed out. The **no** version of this command prevents any new mroutes from becoming permanent. However, it does not remove any existing permanent mroutes. To remove existing permanent mroutes, use the **clear ipv6 mroute** command.

**Options**    • *accessListName*—Name of the IPv6 access list that specifies the mroutes

**Mode**    Global Configuration

## ipv6 nd

---

**Syntax** [ no ] ipv6 nd

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 9.0.0.

**Description** Enables the IPv6 Neighbor Discovery process on an interface. By default, the IPv6 Neighbor Discovery process is disabled on the router. However, if you configure an IPv6 address on a static interface, Neighbor Discovery process is automatically enabled. The **no** version disables the Neighbor Discovery process.

**Mode** Interface Configuration, Profile Configuration

## ipv6 nd active-solicitations

---

**Syntax** [ no ] ipv6 nd active-solicitations

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the router can actively solicit neighbors that become stale (inactive). By default, the router does not actively solicit inactive or stale neighbors. The **no** version disables the ability to actively solicit neighbors that become stale.

**Mode** Interface Configuration

## ipv6 nd dad attempts

---

**Syntax**    `ipv6 nd dad attempts numberOfAttempts`  
              `no ipv6 nd dad attempts`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of consecutive neighbor solicitation messages that an interface sends while the router performs duplicate address detection (DAD) on the unicast IPv6 addresses of the interface. The **no** version returns the number of neighbor solicitation messages to its default value (one message without any follow-up messages).

**Options**

- *numberOfAttempts*—Number of neighbor solicitation messages that you want the router to transmit

**Mode**    Interface Configuration

## ipv6 nd managed-config-flag

---

**Syntax** [ no ] ipv6 nd managed-config-flag

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 9.0.0.

**Description** Sets the “managed address configuration” flag in IPv6 router advertisements. By default, the router does not set the "managed address configuration" flag in IPv6 router advertisements. The **no** version clears the flag from IPv6 router advertisements.

**Mode** Interface Configuration, Profile Configuration

## ipv6 nd ns-interval

---

**Syntax**    `ipv6 nd ns-interval milliseconds`  
              `no ipv6 nd ns-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval between IPv6 neighbor solicitation retransmissions on an interface. The **no** version returns the interval between neighbor solicitation retransmission to its default value (zero [0] milliseconds for router advertisements and 1000 milliseconds for Neighbor Discovery activity of the E Series router).

**Options**    • *milliseconds*—Interval between IPv6 neighbor solicit transmissions

**Mode**    Interface Configuration



## ipv6 nd other-config-flag

---

**Syntax** [ no ] ipv6 nd other-config-flag

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 9.0.0.

**Description** Sets the “other stateful configuration” flag in IPv6 router advertisements. By default, the router does not set the "other stateful configuration" flag in IPv6 router advertisements. The **no** version clears the flag from IPv6 router advertisements.

**Mode** Interface Configuration, Profile Configuration

## ipv6 nd prefix-advertisement

---

**Syntax**    `ipv6 nd prefix-advertisement ipv6Prefix/ipv6PrefixLength validLifetime preferredLifetime`  
              `[ onlink ] [ autoconfig ]`

`[ no ] ipv6 nd prefix-advertisement [ ipv6Prefix/ipv6PrefixLength ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              Profile Configuration mode added in JunosE Release 9.0.0.

**Description**    Specifies which IPv6 prefixes the router includes in IPv6 router advertisements. In Profile Configuration mode, you can configure a single prefix. The **no** version removes any prefixes from the IPv6 routing advertisements.

- Options**
- *ipv6Prefix*—IPv6 network number to include in router advertisements
  - *ipv6PrefixLength*—Length of the IPv6 prefix; a decimal value that indicates how many of the higher-order contiguous bits of the IPv6 address comprise the prefix (the network portion of the IPv6 address). A slash (/) must precede this value.



.....  
**NOTE:** When used in an IPv6 profile, the *ipv6PrefixLength* must be set to a length of 64.  
.....

- *validLifetime*—Amount of time in seconds that the router can advertise the specified IPv6 prefix as valid; in the range 0–4294967295
- *preferredLifetime*—Amount of time in seconds that the router can advertise the specified IPv6 prefix as preferred; in the range 0–4294967295
- *onlink*—Indicates that the specified prefix is assigned to the link
- *autoconfig*—Indicates that local host links can use the specified prefix for IPv6 autoconfiguration

**Mode**    Interface Configuration, Profile Configuration

## ipv6 nd proxy

---

**Syntax** [ no ] ipv6 nd proxy

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables IPv6 Neighbor Discovery proxy. By default, the IPv6 Neighbor Discovery proxy is disabled on the router. The **no** version disables IPv6 Neighbor Discovery proxy.

**Mode** Global Configuration

## ipv6 nd ra-interval

**Syntax**    `ipv6 nd ra-interval seconds`  
  
              `no ipv6 nd ra-interval`

<b>Release Information</b>	Command introduced before JunosE Release 7.1.0. Profile Configuration mode added in JunosE Release 9.0.0.
----------------------------	--

<b>Description</b>	Specifies the interval between IPv6 router advertisement retransmissions on an interface. The <b>no</b> version restores the default interval, 200 seconds.
--------------------	---

**Options**

- *seconds*—Number of seconds between IPv6 advertisement retransmissions; in the range 3–1800

<b>Mode</b>	Interface Configuration, Profile Configuration
-------------	--

## ipv6 nd ra-lifetime

---

**Syntax**    `ipv6 nd ra-lifetime seconds`  
`no ipv6 nd ra-lifetime`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 9.0.0.

**Description**    Specifies the router lifetime value in IPv6 router advertisements on an interface. The router lifetime value is the amount of time the router is considered the default router on this interface. The **no** version restores the default router lifetime value, 1800 seconds.

**Options**

- *seconds*—Number of seconds this router is considered the default router on this interface; in the range 0–1800. A value of zero (0) indicates that this router is not a default router on this interface. Nonzero values indicate that the router is a default router on this interface. Nonzero values should not be less than the router advertisement interval.

**Mode**    Interface Configuration, Profile Configuration

## ipv6-ndra-pool-name

---

**Syntax** [ no ] ipv6-ndra-pool-name *poolName*

**Release Information** Command introduced in JunosE Release 13.0.0.

**Description** Specifies the IPv6 prefix pool name of the Neighbor Discovery router advertisement to be used to delegate prefixes to the requesting router, when the RADIUS server does not return a pool name using the Framed-IPv6-Pool attribute or Ipv6-NdRa-Pool attribute. The **no** version removes the IPv6 prefix pool name of the Neighbor Discovery router advertisement from the AAA domain map.

**Options**

- *poolName*—Name of the IPv6 ndra prefix pool to associate with the domain name; string of up to 16 alphanumeric characters

**Mode** Domain Map Configuration

**Related Documentation**

- Configuring IPv6 Neighbor Discovery Local Address Pools

## ipv6 nd reachable-time

---

**Syntax**    `ipv6 nd reachable-time { milliseconds | hours minutes seconds }`  
`no ipv6 nd reachable-time`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 9.0.0.

**Description**    Specifies the amount of time that the E Series router can reach a remote IPv6 node after some reachability confirmation event has occurred. The **no** version restores the default value 0 milliseconds for router advertisements and 3,600,000 milliseconds (1 hour) for Neighbor Discovery activity of the E Series router.

**Options**

- *milliseconds*—Amount of time, in the range 0–21600000 milliseconds, that the E Series router can reach a remote node after some reachability confirmation event has occurred
- *hours minutes seconds*—Amount of time, in the range 0 hours 0 minutes 0 seconds – 6 hours 0 minutes 0 seconds, that the E Series router can reach a remote node after some reachability confirmation event has occurred; this specification is not supported in Profile Configuration mode

**Mode**    Interface Configuration, Profile Configuration

## ipv6 nd suppress-ra

---

**Syntax** [ no ] ipv6 nd suppress-ra

**Release Information** Command introduced before JunosE Release 7.1.0.  
Profile Configuration mode added in JunosE Release 9.0.0.

**Description** Suppresses IPv6 router advertisement transmissions on a local area network (Ethernet) interface. By default, the router automatically sends IPv6 router advertisements and solicitation messages on LAN (Ethernet) interfaces. On such interfaces, you can suppress the sending of router advertisements using this command. This command is useful for only Ethernet interfaces if you want to suppress the sending of router advertisements.

However, for interfaces other than Ethernet interfaces, you must explicitly enable IPv6 router advertisements to be sent by using the **ipv6 nd** command. If you disable Neighbor Discovery process by using the **no ipv6 nd** command on any interface type, and if you enter the **no ipv6 nd suppress-ra** command, the **ipv6 nd** command takes precedence over the **ipv6 nd suppress-ra** command. In such cases, although router advertisements are enabled to be sent, because Neighbor Discovery is disabled, router advertisements are not used to assign prefixes

The **no** version reenables the sending of IPv6 router advertisement transmissions on the LAN (Ethernet) interface.

**Mode** Interface Configuration, Profile Configuration



## ipv6 nd suppress-ra-source-link-layer

---

**Syntax** [ no ] ipv6 nd suppress-ra-source-link-layer

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Suppresses the source link-layer option in IPv6 router advertisement transmissions. This action forces neighbors to solicit the router link layer explicitly, and may prove necessary when enabling inbound load sharing across multiple link-layer addresses. The **no** version reenables the sending of the source link-layer option in IPv6 router advertisement transmissions.

**Mode** Interface Configuration

## ipv6 neighbor

---

**Syntax**    `ipv6 neighbor [ vrf vrfName ] ipv6Address interfaceType interfaceSpecifier hardwareAddress`  
              `no ipv6 neighbor [ vrf vrfName ] ipv6Address interfaceType interfaceSpecifier`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **vrf** keyword and *vrfName* variable added in JunosE Release 7.2.0.

**Description**    Specifies a static entry in the IPv6 Neighbor Discovery cache. The **no** version removes the static entry from the IPv6 Neighbor Discovery cache.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *ipv6Address*—IPv6 address that corresponds to the local data-link address
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *hardwareAddress*—Local, 48-bit data-link address

**Mode**    Global Configuration

## ipv6 ospf area

---

**Syntax** [ no ] ip ospf [ *processId* ] area { *areaId* | *areaIdInt* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an OSPFv3 interface under the specified area ID or moves an OSPFv3 interface from its current area to a specified area. The **no** version removes the interface from the specified area.

- Options**
- *processId*—Integer in the range 1–65535
  - *areaId*—OSPF area ID in IP address format
  - *areaIdInt*—OSPF area ID as a decimal value 0–4294967295

**Mode** Interface Configuration, Subinterface Configuration

## ipv6 ospf bfd-liveness-detection

---

**Syntax**    `ipv6 ospf bfd-liveness-detection [ minimum-interval minInterval |  
                  [ minimum-receive-interval minRecInterval ]  
                  [ minimum-transmit-interval minTransInterval ] ] [ multiplier multValue ]`  
  
              `no ipv6 ospf bfd-liveness-detection`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables BFD (bidirectional forwarding detection) on an interface running OSPFv3 and defines BFD values to be negotiated between OSPFv3 neighbors for detection of IPv6 data path failures. The **no** version disables BFD on the OSPFv3 interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *minInterval*—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf cost

---

**Syntax**    `ipv6 ospf [ processId ] cost intfCost`  
              `no ipv6 ospf [ processId ] cost`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a cost metric for an interface. Used in the calculation of the SPF routing table. The **no** version resets the path cost to the default.

**Options**

- *processId*—Integer in the range 1–65535
- *intfCost*—Link-state metric cost; number in the range 0–65535; default value is 10

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf dead-interval

---

**Syntax**    `ipv6 ospf [ processId ] dead-interval deadInterval`  
             `no ipv6 ospf [ processId ] dead-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time period during which the router's neighbors do not see hello packets before they declare the router to be down. The **no** version resets the dead interval to its default.

**Options**    • *processId*—Integer in the range 1–65535  
             • *deadInterval*—Number in the range 0–2147483647 seconds; default value is 40 seconds

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf hello-interval

---

**Syntax**    `ipv6 ospf [ processId ] hello-interval helloInterval`  
              `no ipv6 ospf [ processId ] hello-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval between hello packets that the router sends on the interface. The **no** version resets the hello interval to its default.

**Options**

- *processId*—Integer in the range 1–65535
- *helloInterval*—Number in the range 1–65535 seconds; default value is 10 seconds

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf mtu-ignore

---

**Syntax** [ no ] ipv6 ospf [ *process/d* ] mtu-ignore

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that the interface ignore the MTU size contained in the DBD packet. The interface accepts data description packets from its neighbor even if it has a different a MTU size. However, the MTU size must be less than 18000. The **no** version resets the default; that the neighbor MTU size must match the MTU size of the OSPFv3 interface from which the packet is received.

**Options** • *process/d*—Integer in the range 1–65535

**Mode** Interface Configuration, Subinterface Configuration



## ipv6 ospf network

---

**Syntax**    `ipv6 ospf [ processid ] network { broadcast | point-to-point }`  
              `no ipv6 ospf [ processid ] network`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a network type (broadcast or point-to-point) for an interface. The **no** version resets the path cost to the default.

**Options**    • *processid*—Integer in the range 1–65535

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf priority

---

**Syntax**    `ipv6 ospf [ processId ] priority intfPriority`  
             `no ipv6 ospf [ processId ] priority`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the router priority. Used in determining the designated router for the particular network. This designation applies only to multiaccess networks. Every broadcast and nonbroadcast multiaccess network has a designated router. A higher priority value for an OSPF interface signifies a greater likelihood of that router becoming the designated router. A value of 1 means that the router has the least chance of becoming a designated router. The **no** version restores the default value.

**Options**

- *processId*—Integer in the range 1–65535
- *intfPriority*—Priority value, an 8-bit number in the range 1–255; default value is 1

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf retransmit-interval

---

**Syntax**    `ipv6 ospf [ processId ] retransmit-interval retransInterval`  
              `no ipv6 ospf [ processId ] retransmit-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the time between LSA retransmissions for the interface when an acknowledgment for the LSA is not received. The **no** version restores the default value.

- Options**    • *processId*—Integer in the range 1–65535  
              • *retransInterval*—Number in the range 0–3600 seconds; default value is 5 seconds

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf shutdown

---

**Syntax**    [ no ] ipv6 [ *processId* ] ospf shutdown

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Disables OSPF on an interface. The **no** version enables OSPF on the interface.

**Options**    • *processId*—Integer in the range 1–65535

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 ospf transmit-delay

---

**Syntax**    `ipv6 ospf [ processId ] transmit-delay transmDelay`  
              `no ipv6 ospf [ processId ] transmit-delay`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the estimated time it takes to transmit a link-state update packet on the interface. The **no** version restores the default value.

**Options**    • *processId*—Integer in the range 1–65535  
              • *transmDelay*—Link-state transmit delay, a number in the range 0–3600 seconds; default value is 1 second

**Mode**    Interface Configuration, Subinterface Configuration

## ipv6 pim bfd-liveness-detection

---

**Syntax**    `ipv6 pim bfd-liveness-detection [ minimum-interval minInterval |`  
              `[ minimum-receive-interval minRecInterval ]`  
              `[ minimum-transmit-interval minTransInterval ] ] [ multiplier multValue ]`  
  
              `no ipv6 pim bfd-liveness-detection`

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Enables BFD (bidirectional forwarding detection) on an interface running PIM and defines BFD values to be negotiated between PIM neighbors for detection of IPv6 data path failures. You can change the BFD liveness detection parameters at any time without stopping or restarting the existing session; BFD automatically adjusts to the new parameter value. However, no changes to BFD parameters take place until the values resynchronize with each neighbor. The **no** version disables BFD on the PIM interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *minInterval*—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote neighbor multiplies by the local router's negotiated transmit interval to determine the remote neighbor's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode**    Interface Configuration

## ipv6 pim bsr-candidate

**Syntax**    `ipv6 pim bsr-candidate interfaceType interfaceSpecifier`  
                  `[ hashMaskLen [ priority ] ] [ period bootstrapPeriod ]`  
                  `no ipv6 pim bsr-candidate`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines a router as a bootstrap router (BSR) candidate. The **no** version disables the router BSR candidacy.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#). The autoRP announcement messages will contain the IP address for this interface.
  - *hashMaskLen*—Length in the range 1–128 bits of the hash mask length field sent in BSMs that the router originates. This mask is combined with the group address before the router calls the hash function. For example, specifying a value of 32 limits the group address to the first 32 bits. The default and maximum hash mask length is 126 bits
  - *priority*—Value in the range 0–255 of the BSR-Priority field of BSMs that the router originates. In the BSR election process, the BSR with the higher priority is preferred. If the priority values are equal, the router with the higher IP address becomes the BSR. The default value is 0 (address comparison only)
  - *bootstrapPeriod*—Interval in the range 1–65535 seconds at which the BSR sends bootstrap messages; default value is 60 seconds

**Mode**    Global Configuration

## ipv6 pim dr-priority

---

**Syntax**    `ipv6 pim dr-priority priority`  
              `no ipv6 pim dr-priority`

**Release Information**    Command introduced in JunosE Release 10.0.0.

**Description**    Assigns a priority for the interface to be selected as the designated router. An interface with a higher priority value is preferred as a designated router over an interface with a lower priority value. In Interface Configuration mode, the **no** version restores the value that is specified in Router Configuration mode. If the designated router priority is not specified in Router Configuration mode, then the default value of one is restored.



---

**NOTE:** You cannot configure the designated router priority on PIM dense mode interfaces.

---

**Options**    • *priority*—Value in the range 1–254; default value is 1.

**Mode**    Interface Configuration, Router Configuration



## ipv6 pim join-filter

---

**Syntax**    `ipv6 pim join-filter accessListName`  
              `no ipv6 pim join-filter`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies an extended access list that you want this PIM router or PIM interface to use as a join filter. If an interface-level filter exists, it takes precedence over the global-level filter. The **no** version removes the filter association.

**Options**    • *accessListName*—Name of the access list that you want this interface to use as a PIM join filter; a string of up to 32 alphanumeric characters

**Mode**    Global Configuration, Interface Configuration

## ipv6 pim join-prune-interval

---

**Syntax**    `ipv6 pim join-prune-interval interval`  
              `no ipv6 pim join-prune-interval`

**Release Information**    Command introduced in JunosE Release 10.0.0.

**Description**    Specifies the time interval at which the router sends the PIM join/prune message to the upstream RPF neighbor. In Interface Configuration mode, the **no** version restores the value that is specified in Router Configuration mode. If the message interval is not specified in Router Configuration mode, then the default value of 60 seconds is restored.



.....  
**NOTE:** You cannot configure the designated router priority on PIM dense mode interfaces.  
.....

**Options**    • *interval*—Interval in the range 10–210 seconds at which the router sends the PIM join/prune message; the default value is 60 seconds.

**Mode**    Interface Configuration, Router Configuration

## ipv6 pim query-interval

---

**Syntax**    `ipv6 pim query-interval queryTime`  
              `no ipv6 pim query-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies how often the router sends PIM router query messages from this interface. The **no** version specifies the default time interval, 30 seconds.

**Options**    • *queryTime*—Interval in the range 0–210 seconds at which the router sends PIM router query messages from this interface

**Mode**    Interface Configuration

## ipv6 pim rp-address

---

**Syntax** [ no ] ipv6 pim rp-address *ipv6Address* [ *ipv6AccessList* ] [ override ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a static PIM group-to-RP mapping. The **no** version clears the mapping from this interface.

- Options**
- *ipv6Address*—IPv6 address of the router you want to designate as an RP router
  - *ipv6AccessList*—Name of the IPv6 access list that specifies which multicast groups use this RP
  - **override**—Specifies that this static RP mapping has priority over group-to-RP mappings learned by auto-RP

**Mode** Global Configuration

## ipv6 pim rp-candidate

**Syntax** `ipv6 pim rp-candidate interfaceType interfaceSpecifier [ group-list accessListName ]`  
`[ hold-time holdTime ] [ priority priority ] [ interval interval ]`

`no ipv6 pim rp-candidate interfaceType interfaceSpecifier`  
`[ group-list accessListName ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a router as a rendezvous point (RP) router candidate. The **no** version stops the router from being an RP candidate.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#). The autoRP announcement messages will contain the IP address for this interface.
  - *accessListName*—Access-list containing the set of group prefixes supported by this C-RP. If no group-list is specified, the default value is the entire multicast address range.



**NOTE:** You should not configure negative (that is, deny) access-list entries. BSR has no mechanism for distributing negative entries.

- *holdTime*—Amount of time in the range 1–65535 seconds that the BSR keeps an RP in its C-RP list if the BSR does not receive a C-RP advertisement message; default value is 150 seconds
- *priority*—Priority field value in the range 0–255 that the C-RP sends to the BSR in C-RP advertisement messages; default value is 192. In the RP election process, the RP with the lower priority value is preferred.
- *interval*—Interval in the range 1–65535 seconds at which the C-RP sends advertisement messages to the BSR; default value is 60 seconds

**Mode** Global Configuration

## ipv6 pim sparse-mode

---

**Syntax** [ no ] ipv6 pim sparse-mode

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables PIM in sparse mode on an interface. The **no** version disables PIM in sparse mode on an interface.

**Mode** Interface Configuration

## ipv6 pim sparse-mode graceful-restart-duration

---

**Syntax**    `ipv6 pim sparse-mode graceful-restart-duration seconds`  
              `no ipv6 pim sparse-mode graceful-restart-duration`

**Release Information**    Command introduced in JunosE Release 10.0.0.

**Description**    Sets duration time for PIM sparse-mode graceful restart. The **no** version resets the duration to the default.

**Options**    • *seconds*—Restart duration in seconds; default value is 30 seconds

**Mode**    Global Configuration

## ipv6 pim spt-threshold

---

**Syntax** [ no ] ipv6 pim spt-threshold { 0 | *nonZeroInteger* | infinity }  
[ group-list *ipv6AccessList* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the network configuration that PIM sparse mode uses when a source starts sending multicast messages. The **no** version restores the default value, 0.

- Options**
- 0—Configures PIM sparse mode to switch to an SPT when a source begins to send multicast messages
  - *nonZeroInteger*—Integer in the range 1–4294967294; prevents PIM sparse mode from switching from a shared tree to an SPT
  - infinity—Prevents PIM sparse mode from switching from a shared tree to an SPT
  - *ipv6AccessList*—Name of the IPv6 access list that specifies the groups to which the threshold applies

**Mode** Global Configuration



## ipv6 pim ssm

---

**Syntax**    `ipv6 pim ssm { default | range ipv6AccessList }`  
              `no ipv6 pim ssm`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables SSM and defines the SSM range of IPv6 multicast addresses. The **no** version disables SSM on the router.

**Options**

- `default`—Specifies that SSM use the IANA-specified range of 232/8
- `ipv6AccessList`—Name of the IPv6 access list that specifies the range of multicast addresses you want SSM to use

**Mode**    Global Configuration

## ipv6 policy

---

**Syntax**    `ipv6 policy { input | output } policyName`  
              `[ statistics { enabled [ baseline { enabled | disabled } ] [ preserve | merge ] |`  
              `disabled [ merge ] } | merge ]`

`no ipv6 policy { input | output | secondary-input } [ policyName ]`

For policy lists in Profile Configuration mode:

`ipv6 policy { input | output } policyName`  
`[ statistics { enabled | disabled } ] [ merge ]`

`no ipv6 policy { input | output | secondary-input } [ policyName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **merge** keyword added in JunosE Release 7.2.0.  
                              Profile Configuration mode added in JunosE Release 7.2.0.

**Description**    In Interface Configuration mode, assigns a policy list to the ingress or egress of an interface. If you enter the **ipv6 policy** command and the policy list does not exist, the router creates a policy list with no rules, the default. When a policy list does not have rules, the router inserts a default filter rule. Attaching this policy list to an interface filters all packets on that interface. You must specify the **input** or **output** keyword to assign the policy list to the ingress or egress of the interface.

In Profile Configuration mode, assigns the policy list to a profile, which then assigns the policy to an interface.

The **no** version removes the association between a policy list and an interface. In Profile Configuration mode, the **no** version removes policy reference from the profile.

- Options**
- **input**—Applies policy to data arriving at this interface before a route lookup
  - **output**—Applies policy to data leaving this interface
  - **secondary-input**—Applies policy to data that arrives at this interface after a route lookup
  - ***policyName***—Name of the policy; a maximum of 40 characters
  - **statistics**—Enables or disables collection of policy routing statistics
    - **enabled**—Enable collection of policy routing statistics
    - **baseline enabled**—Enables baselining of policy routing statistics (Interface Configuration mode only)
    - **baseline disabled**—Disables baselining of policy routing statistics (Interface Configuration mode only)

- **preserve**—Preserves existing statistics for any classifier-list that is the same for both the new and old policy attachments when you attach a new policy to an interface
- **disabled**—Disable collection of policy routing statistics
- **merge**—Enables merging of multiple policies to form a single policy



**NOTE:** The **local-input** keyword for the **ipv6 policy** command is deprecated, and may be completely removed in a future release. The keyword should be removed from scripts.

You should recreate any local input policies using the **ipv6 classifier-list local true** command and attaching the policies using the **ipv6 policy secondary-input** command.

**Mode**    Interface Configuration, Profile Configuration

**Related Documentation**    • Setting a Statistics Baseline for Policies

## ipv6 policy-list

---

**Syntax** [ no ] ipv6 policy-list *policyName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies an IPv6 policy list. If you execute an **ipv6 policy-list** command and type **exit**, the router creates a policy list with no rules, the default. When a policy list does not have rules, the router inserts a default filter rule. Attaching this policy list to an interface filters all packets on that interface. The **no** version removes a policy list.

**Options** • *policyName*—Name of the policy list

**Mode** Global Configuration

**Related Documentation** • [Creating Policy Lists for IPv6](#)

## ipv6 policy-parameter hierarchical

<b>Syntax</b>	ipv6 policy-parameter hierarchical <i>parameterName</i> { <i>nodeValue</i>   atm   atm-vc   atm-vp <i>vpValue</i>   ethernet   fr-vc   forwarding   ppp-interface   svlan <i>svlanValue</i>   vlan }  no ipv6 policy-parameter <i>parameterName</i>
<b>Release Information</b>	Command introduced in JunosE Release 8.0.0. <b>ppp-interface</b> keyword added in JunosE Release 10.3.0.
<b>Description</b>	Specifies a parameter value for IPv6 interfaces. The <b>no</b> version removes the policy parameter and its contents.
<b>Options</b>	<ul style="list-style-type: none"> <li>• <i>parameterName</i>—Name of policy parameter</li> <li>• <i>nodeValue</i>—Aggregation node number in the range 1–65535</li> <li>• <i>vpValue</i>—ATM VPI number in the range 0–255</li> <li>• <i>svlanValue</i>—S-VLAN ID number in the range 0–4095</li> </ul>
<b>Mode</b>	Interface Configuration, Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Creating a Classifier Group for a Policy List</li> </ul>

## ipv6 policy-parameter reference-rate

---

**Syntax** In Interface Configuration mode:

ipv6 policy-parameter reference-rate *parameterName* [ increase ] *value*

no ipv6 policy-parameter reference-rate *parameterName* [ increase *value* ]

In Profile Configuration mode:

ipv6 policy-parameter reference-rate *parameterName* [ increase ] *value*

no ipv6 policy-parameter reference-rate *parameterName*

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates an IPv6 policy parameter for a reference rate; creates a global parameter if it does not exist. The **no** version removes the policy parameter and its contents; if used with the **increase** keyword, decreases the value.

- Options**
- *parameterName*—Name of policy parameter up to 40 characters
  - increase—Increments the existing reference rate value
  - *value*—Value of the reference rate parameter, in the range 0–4292967295

**Mode** Interface Configuration, Profile Configuration

**Related Documentation**

- Creating a Classifier Group for a Policy List

## ipv6 prefix-list

**Syntax** `ipv6 prefix-list listName { description desc | { [ seq sequence ] { permit | deny } ipv6Prefix [ ge geNumber ] [ le leNumber ] } }`

`no ipv6 prefix-list listName [ description | [ seq sequence ] [ { permit | deny } ipv6Prefix [ ge geNumber ] [ le leNumber ] ] ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an IPv6 prefix list for route filtering; specifies a list entry—a permit or deny clause for a network address. The **no** version removes the specified prefix list or the specified list entry.

- Options**
- *listName*—Name of the IPv6 prefix list; a string of up to 32 characters
  - *desc*—Description of the prefix list
  - *sequence*—Number in the range 0–65535 that indicates the position the prefix list entry has in the already existing list of entries for the prefix list; if you do not specify a *sequence*, the command uses the value of the last sequence number + 5
  - *permit*—When specified, the router redistributes any prefix that matches the filtered route based on the set actions
  - *deny*—When specified, the router drops any prefix that matches the filtered route
  - *ipv6Prefix*—Network route that you want to filter, in the format *ipv6Address / length*, where
    - *ipv6Address*—Base IPv6 address of the network route that you want to filter (for example, ::ffff:a:b:c:d)
    - *length*—Length of the network prefix; number of bits masking base address to produce address to be matched
  - *geNumber*—Route being filtered matches if its prefix is within the range specified: greater than or equal to *geNumber* and less than or equal to 32
  - *leNumber*—Route being filtered matches if its prefix is within the range specified: greater than or equal to *length* and less than or equal to *leNumber*

**Mode** Global Configuration

## ipv6-prefix-pool-name

---

**Syntax**    `ipv6-prefix-pool-name poolName`  
              `no ipv6-prefix-pool-name`

**Release Information**    Command introduced in JunosE Release 10.1.0.

**Description**    Specifies the IPv6 local prefix pool name to be used to delegate prefixes to the requesting router, when the RADIUS server does not return a pool name using the Framed-IPv6-Pool attribute. The **no** version removes the IPv6 local pool from the AAA domain map.

**Options**    • *poolName*—Name of the IPv6 local prefix pool to associate with the domain name; string of up to 16 alphanumeric characters

**Mode**    Domain Map Configuration



## ipv6 route

**Syntax** `ipv6 route [ vrf vrfName ] prefix { nextHop | interfaceType interfaceSpecifier }  
[ distance ] [ reject | discard ][ tag tagVal ]`

`no ipv6 route [ vrf vrfName ] prefix [ nextHop | interfaceType interfaceSpecifier ]  
[ distance ]`

**Release Information** Command introduced before JunosE Release 7.1.0.  
**vrf** keyword and *vrfName* variable added in JunosE Release 7.2.0.  
**reject** and **discard** keywords added in JunosE Release 12.0.0.  
**tag** keyword and *tagVal* variable added in JunosE Release 12.3.0.

**Description** Configures a static IPv6 prefix route. The **no** version removes a static IPv6 prefix route.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *prefix*—Combination of both a prefix and prefix length (mask) value. The prefix (IP address or network) defines the IPv6 interface or network. The prefix (mask) length of the IPv6 prefix is a decimal value that indicates how many of the high-order contiguous bits of the address comprise the prefix (the network portion of the address). A slash mark must precede the decimal value. An example of a prefix would be “7fff::0/16”, “7fff::0/32”, “7fff:2:3::0/24”, or “7fff::1/128”.
  - *nextHop*—IPv6 address of the next-hop to reach the destination prefix (network). The next-hop address need not be directly connected; recursion locates the physical next-hop.
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *distance*—Preference value for the IPv6 route. A default value of 1 gives static routes precedence over any other type of route (with the exception of connected routes).
  - **reject**—Discards packets received on the static route for the specified interface that are not processed by the router and sends ICMP unreachable messages to the originator. This option is available only for null interfaces
  - **discard**—Discards packets received on the static route for the specified interface that are not processed by the router and does not send ICMP unreachable messages to the originator. This option is available only for null interfaces
  - *tagVal*—Number in the range 0–4294967295 that identifies the tag for this route; default value is 0

**Mode** Global Configuration

## ipv6 router isis

---

**Syntax**    [ no ] ipv6 router isis [ *tag* ]

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Enables the IS-IS routing protocol on an interface and specifies an IS-IS process for IPv6. The **no** version disables IS-IS routing.

**Options**

- *tag*—Meaningful name for a routing process; name must be unique among all IP router processes for a given router; if not specified, a null tag is assumed, and the process is referenced with a null tag

**Mode**    Interface Configuration

---

## ipv6 router mld

---

**Syntax** [ no ] ipv6 router mld

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates and enables MLD on a virtual router; accesses MLD router configuration mode. The **no** version disables MLD on a virtual router.



.....  
**NOTE:** This command is identical to the **router mld** command.  
.....

**Mode** Global Configuration

## ipv6-router-name

---

**Syntax**    `ipv6-router-name vrName`  
             `no ipv6-router-name [ vrName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Maps a user domain name to an IPv6 virtual router. The **no** version deletes the router name parameter, and the router defaults to the default virtual router.

**Options**    • *vrName*—Name of the virtual router; a string of 1–15 alphanumeric characters

**Mode**    Domain Map Configuration

## ipv6 router ospf

---

**Syntax** [ no ] ipv6 router ospf *processId*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures an IPv6 OSPF routing process. The **no** version disables an IPv6 OSPF routing process.

**Options** • *processId*—Number in the range 1–65535 that identifies the OSPF process

**Mode** Global Configuration

## ipv6 router pim

---

**Syntax** [ no ] ipv6 router pim

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates and enables PIM for IPv6 on a virtual router; accesses PIM router configuration mode. The **no** version deletes PIM from a virtual router.

**Mode** Global Configuration

---

## ipv6 route-type

---

**Syntax** For BGP

ipv6 route-type [ unicast | both ]

no ipv6 route-type

For OSPF

ipv6 route-type [ unicast | multicast | both ]

no ipv6 route-type

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** For BGP, specifies whether BGP IPv6 routes are available only for other unicast protocols or for both unicast protocols and multicast protocols to perform RPF checks. The **no** version restores the default value, unicast.

For OSPF, specifies whether OSPF IPv6 routes are available only for unicast forwarding, only for multicast reverse path forwarding checks, or for both. The **no** version restores the default value, both.

- Options**
- unicast—Specifies that routes for the protocol are available only for unicast forwarding
  - both—Specifies that routes for the protocol are available for both unicast forwarding and multicast route path forwarding checks
  - multicast—Specifies that routes for the protocol are available only for multicast route path forwarding checks

**Mode** Router Configuration

## ipv6 rpf-route

---

**Syntax**    `ipv6 rpf-route [ vrf vrfName ] ipv6Address/addressMask  
                  { nextHopIpv6Address | interfaceType interfaceSpecifier } [ distance ]`

`no ipv6 rpf-route [ vrf vrfName ] ipv6Address/addressMask  
                  [ nextHopIpv6Address | interfaceType interfaceSpecifier ] [ distance ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                             **vrf** keyword and *vrfName* variable added in JunosE Release 7.2.0.

**Description**    Customizes static IPv6 routes that the router can use to verify source addresses in multicast packets. The **no** version removes the static route.

- Options**
- *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters
  - *ipv6Address*—IPv6 address of the destination network
  - *addressMask*—Subnet mask for the destination network
  - *nextHopIpv6Address*—IPv6 address of the next hop
  - *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *distance*—Number in the range 0–255 that indicates the preference for this route

**Mode**    Global Configuration



## ipv6 sa-validate

---

**Syntax** [ no ] ipv6 sa-validate

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables source address validation on an IPv6 interface. This feature verifies that a packet has been sent from a valid source address. When a packet arrives on an interface, the router performs a routing table lookup using the source address. The result from the routing table lookup is an interface to which packets destined for that address are routed. This interface must match the interface that the packet arrived on. If it does not match, the router drops the packet. By default, validation of IPv6 source addresses is disabled for the particular interface or profile. The **no** version disables source address validation.

**Mode** Interface Configuration, Profile Configuration

## ipv6 share-interface

---

**Syntax**    `ipv6 share-interface interfaceType interfaceSpecifier`  
              `no ipv6 share-interface`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the layer 2 interface that an IPv6 interface will share in the current virtual router. The **no** version removes the association between the layer 2 interface and the shared IPv6 interface.

**Options**

- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Interface Configuration

## ipv6 static-route table-map

---

**Syntax**    `ipv6 static-route table-map [ vrf vrfName ] mapName`  
              `no ipv6 static-route table-map [ vrf vrfName ] [ mapName ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.  
                              **vrf** keyword and *vrfName* variable added in JunosE Release 7.2.0.

**Description**    Filters static routes before adding them to the routing table. The **no** version deletes the table map.

**Options**    • *vrfName*—Name of the VRF; string of 1–32 alphanumeric characters  
              • *mapName*—Name of the table map that you want the router to use

**Mode**    Global Configuration

## ipv6 unnumbered

---

**Syntax**    `ipv6 unnumbered interfaceType interfaceSpecifier`  
              `no ipv6 unnumbered`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables or disables IPv6 processing on an interface without assigning an explicit IPv6 address to that interface. The global IPv6 address of the interface, specified by the *interfaceType interfaceSpecifier* values, becomes the source address in packets that the unnumbered interface generates. Unnumbered interfaces are often used in point-to-point connections where an IPv6 address is not required. You must specify an interface location, which is the identifier of another interface on which the router has an assigned IPv6 address. This interface cannot be another unnumbered interface. The **no** version of the command removes the IPv6 address from the interface.



.....  
**NOTE:** Enabling IPv6 on an interface automatically configures the link-local address on an unnumbered interface.  
.....

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Interface Configuration, Profile Configuration

---

## ipv6 virtual-router

---

**Syntax** [ no ] ipv6 virtual-router *vrName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a virtual router in an IPv6 profile. Dynamic interfaces created with the profile are assigned to this VR. The **no** version removes the VR from the profile; if a VR is not specified via RADIUS, then any subsequent creation process for dynamic interfaces using the profile fails.



.....  
**NOTE:** You can configure a virtual router using RADIUS instead of adding one to the profile by using this command. For more information about how to configure a virtual router using RADIUS, see *Configuring RADIUS Attributes* in the *JunosE Broadband Access Configuration Guide*.  
.....

**Options** • *vrName*—Name of the virtual router; a string of 1–15 alphanumeric characters

**Mode** Profile Configuration

## isis authentication-key

---

**Syntax**    isis authentication-key [ level-1 | level-2 ] *authKey*  
              no isis authentication-key [ level-1 | level-2 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Assigns a password for IS-IS level 1 and level 2 hellos used by neighboring routers that are using IS-IS password authentication. The **no** version deletes the password.

- Options**
- level-1—Inserts the password into level 1 hello packets
  - level-2—Inserts the password into level 2 hello packets
  - *authKey*—Password; string of up to 8 characters

**Mode**    Interface Configuration, Subinterface Configuration

## isis bfd-liveness-detection

**Syntax** [ no ] isis bfd-liveness-detection [ minimum-interval *minInterval* ]  
 [ minimum-receive-interval *minRecInterval* ]  
 [ minimum-transmit-interval *minTransInterval* ] [ multiplier *multValue* ]

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables BFD (bidirectional forwarding detection) on an interface running IS-IS and defines BFD values to be negotiated between IS-IS neighbors for detection of IP data path failures. The **no** version disables BFD on the IS-IS interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- *minInterval*—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minRecInterval*—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *minTransInterval*—Minimum proposed interval between BFD control packets sent by the local peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - *multValue*—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode** Interface Configuration, Subinterface Configuration

## isis circuit-type

---

**Syntax** isis circuit-type [ level-1 | level-1-2 | level-2-only ]

no isis circuit-type

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the type of adjacency desired for the specified interface. The **no** version resets the circuit type to level 1 and level 2.

- Options**
- level-1—Establishes a level 1 adjacency if there is at least one area address in common between this router and its neighbors
  - level-1-2—(default) Establishes a level 1 and 2 adjacency if the neighbor is also configured as a level 1-2 router and there is at least one area in common. If there is no area in common, a level 2 adjacency is established.
  - level-2-only—Establishes a level 2 adjacency on the circuit. If the neighboring router is a level 1 only router, no adjacency will be established.

**Mode** Interface Configuration, Subinterface Configuration



## isis csnp-interval

---

**Syntax**    isis csnp-interval *seconds* [ level-1 | level-2 ]  
              no isis csnp-interval [ *seconds* ] [ level-1 | level-2 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the IS-IS CSNP interval for the specified interface. The **no** version restores the default value.

- Options**
- *seconds*—Number in the range 0–65535; the interval of time in seconds between the transmission of CSNPs on multiaccess networks for the designated router; default value is 10 seconds, except for WAN interfaces, where the default value is 0
  - level-1—Sets the interval of time between transmission of CSNPs for level 1 independently
  - level-2—Sets the interval of time between transmission of CSNPs for level 2 independently

**Mode**    Interface Configuration, Subinterface Configuration

## isis hello-interval

---

**Syntax**    isis hello-interval *seconds* [ level-1 | level-2 ]  
              no isis hello-interval [ *seconds* ] [ level-1 | level-2 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the length of time in seconds between hello packets that the router sends on the specified interface. The **no** version restores the default value.

- Options**
- *seconds*—Time (in the range 0–65535 seconds) equal to the *hello multiplier* times the *hello interval seconds*; default value is 10 seconds.
  - level-1—Sets the hello interval for level 1 independently
  - level-2—Sets the hello interval for level 2 independently

**Mode**    Interface Configuration, Subinterface Configuration

## isis hello-multiplier

---

**Syntax**    isis hello-multiplier *multiplier* [ level-1 | level-2 ]  
              no isis hello-multiplier [ *multiplier* | level-1 | level-2 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of IS-IS hello packets a neighbor must miss before the router declares the adjacency to be down. The **no** version restores the *multiplier* default value, 3.

- Options**
- *multiplier*—Value (in the range 3–1000) that the router uses as the hello-multiplier when calculating the advertised hold time. The default multiplier value is 3.
  - level-1—Sets the hello-multiplier independently for level 1 adjacencies
  - level-2—Sets the hello-multiplier independently for level 2 adjacencies

**Mode**    Interface Configuration, Subinterface Configuration

## isis hello padding

---

**Syntax** [ no ] isis hello padding

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Pads IS-IS hello packets to their full maximum transmission unit (MTU) size. The **no** version restores the hello padding to its default, no padding.

**Mode** Interface Configuration

## isis lsp-interval

---

**Syntax**    isis lsp-interval *milliseconds*  
              no isis lsp-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the time delay between successive IS-IS link-state packet transmissions. The **no** version restores the default value, 33 milliseconds.

**Options**    • *milliseconds*—Number of milliseconds in the range 1–4294967295; an interval between successive link-state packets

**Mode**    Interface Configuration, Subinterface Configuration

## isis mesh-group

---

**Syntax**    isis mesh-group { blocked | *number* }  
              no isis mesh-group

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures an interface in the same mesh group to act as a virtual multiaccess network. The **no** version disables the feature.

- Options**
- blocked—Blocks reserved LSPs from being flooded out on this defined configured interface
  - *number*—Mesh group number in the range 1–4294967295

**Mode**    Interface Configuration, Subinterface Configuration

## isis message-digest-key

**Syntax** isis message-digest-key *keyId* hmac-md5 *key*  
 [ start-accept *startAcceptTime* [ { *startAcceptMonth* *startAcceptDay* | *startAcceptDay* *startAcceptMonth* } *startAcceptYear* ] ]  
 [ start-generate *startGenTime* [ { *startGenMonth* *startGenDay* | *startGenDay* *startGenMonth* } *startGenYear* ] ]  
 [stop-accept { never | *stopAcceptTime* [ { *stopAcceptMonth* *stopAcceptDay* | *stopAcceptDay* *stopAcceptMonth* } *stopAcceptYear* ] } ]  
 [ stop-generate { never | *stopGenTime* [ { *stopGenMonth* *stopGenDay* | *stopGenDay* *stopGenMonth* } *stopGenYear* ] } ] [ level-1 | level-2 ]  
 no isis message-digest-key *keyId* [ level-1 | level-2 ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies an HMAC MD5 key that the router uses to create a secure, encrypted message digest of IS-IS level 1 or level 2 hello packets on the interface. Level 1 packets are the default. The digest is inserted into the packet from which it is created. Using this algorithm protects against intrusion by preventing unauthorized routers from forming adjacencies with your router.

You can specify when the router will start (default is the current time) and stop (default is never) accepting packets that include a digest made with this key. You can specify when the router will start (default is the current time plus 2 minutes) and stop (default is never) generating packets that include a digest made with this key. The **no** version deletes the key specified by the *keyId*.

- Options**
- *keyId*—Integer from 1 to 255 that is a unique identifier for the secret key, sent with the message digest in the packet.
  - *key*—String of up to 20 alphanumeric characters; secret key used by the HMAC MD5 algorithm to generate the message digest.
  - *startAcceptTime*, *startAcceptMonth*, *startAcceptDay*, *startAcceptYear*—Time, month, day, year that the router will start accepting packets created with this password. Use military time format *HH : MM [ : SS ]*.
  - *startGenTime*, *startGenMonth*, *startGenDay*, *startGenYear*—Time, month, day, year that the router will start inserting this password into packets. Use military time format *HH : MM [ : SS ]*.
  - never—Specifies that the router never stops accepting or generating packets; overrides previously specified stop times.
  - *stopAcceptTime*, *stopAcceptMonth*, *stopAcceptDay*, *stopAcceptYear*—Time, month, day, year that the router will stop accepting packets created with this password. Use military time format *HH : MM [ : SS ]*.
  - *stopGenTime*, *stopGenMonth*, *stopGenDay*, *stopGenYear*—Time, month, day, year that the router will stop inserting this password into packets. Use military time format *HH : MM [ : SS ]*.

- level-1—Inserts the password into level 1 hello packets
- level-2—Inserts the password into level 2 hello packets

**Mode** Interface Configuration, Subinterface Configuration



---

## isis metric

---

**Syntax**    isis metric *defaultMetric* [ level-1 | level-2 ]  
              no isis metric [ *defaultMetric* | level-1 | level-2 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the metric (cost) for the interface to links at the specified level. If no level is specified, the cost is applied to both level 1 and level 2 links. The **no** version restores the default metric value.

- Options**
- *defaultMetric*—Metric used for the redistributed route; a number in the range 0–63 if the router is configured with the **metric-style narrow** command; a number in the range 0–16777215 if the router is configured with the **metric-style transition** or **metric-style wide** command; default value is 10
  - level-1—Applies metric to level 1 links
  - level-2—Applies metric to level 2 links

**Mode**    Interface Configuration, Subinterface Configuration

## isis network point-to-point

---

**Syntax** [ no ] isis network point-to-point

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the IS-IS circuit type as point-to-point. Issuing this command tears down existing adjacencies, originates or flushes LSPs, and establishes new adjacencies. The **no** version restores the default, treating the circuit as a broadcast circuit.

**Mode** Interface Configuration

## isis priority

---

**Syntax**    isis priority *value* [ level-1 | level-2 ]  
              no isis priority [ level-1 | level-2 ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the priority of this router for designated router election. The **no** version resets priority to the default value, 64.

- Options**
- *value*—Number in the range 0–127; the priority of a router; default value is 64
  - level-1—Sets the priority of a router for level 1 independently
  - level-2—Sets priority of a router for level 2 independently

**Mode**    Interface Configuration, Subinterface Configuration

## isis retransmit-interval

---

**Syntax**    isis retransmit-interval *seconds*  
              no isis retransmit-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the number of seconds between retransmission of LSPs with the same lsp-id for point-to-point links. The **no** version restores the default value.

**Options**    • *seconds*—Number of seconds in the range 1–65535; default value is 5. The number should be greater than the expected round-trip delay between any two routers on the attached network. The setting of this parameter should be conservative, or needless retransmission will result. The value should be larger for serial lines.

**Mode**    Interface Configuration, Subinterface Configuration

## isis retransmit-throttle-interval

---

**Syntax**    isis retransmit-throttle-interval *milliseconds*  
              no isis retransmit-throttle-interval

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the amount of time between retransmissions of any IS-IS LSPs on a point-to-point interface. The **no** version restores the default value, 33 milliseconds.

**Options**    • *milliseconds*—Number of milliseconds in the range 0–65535; the minimum delay between LSP retransmissions on the interface

**Mode**    Interface Configuration, Subinterface Configuration

## isis tag

---

**Syntax** [ no ] isis tag *tagValue*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets a route tag value for the IP addresses on an IS-IS interface before the route is propagated to other routers in an IS-IS domain. To use the route tag, you must reference it in a route map to set values and/or redistribute routes. The **no** version removes the route tag from the interface.

**Options**

- *tagValue*—Number in the range 1–4294967295 that identifies the route tag assigned to the IS-IS interface

**Mode** Interface Configuration, Subinterface Configuration

## issuer-identifier

---

**Syntax**    issuer-identifier *name*  
              no issuer-identifier

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the name of the CA issuer for online digital certificate configuration. In CA authentication requests, the identifier is used together with the enrollment URL specified by the **enrollment url** command. The **no** version removes the name from the configuration.

**Options**    • *name*—Name of CA issuer; in the range 1–200 characters

**Mode**    IPSec CA Identity Configuration

## issu initialize

---

**Syntax**   issu initialize

**Release Information**   Command introduced in JunosE Release 9.0.0.

**Description**   Starts the initialization phase of unified ISSU. There is no **no** version.

**Mode**   Privileged Exec



## issu start

---

**Syntax**    issu start

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Starts the upgrade phase of unified ISSU. There is no **no** version.

**Mode**    Privileged Exec

## issu stop

---

**Syntax**    `issu stop`

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Stops the unified ISSU operation and restores the router to the state existing before you issued the **issu initialize** command. There is no **no** version.

**Mode**    Privileged Exec

## is-type

---

**Syntax**    is-type { level-1 | level-1-2 | level-2-only }  
              no is-type

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the IS-IS level at which the router is to operate. The **no** version restores the default value, level-1-2.

- Options**
- level-1—Causes the router to act as a station router
  - level-1-2—Causes the router to act as both a station router and an area router; the default setting
  - level-2-only—Causes the router to act as an area router

**Mode**    Router Configuration



## CHAPTER 11

# K Commands

## key

---

**Syntax** To assign a RADIUS key:

*key secret*

*no key*

To assign a RADIUS relay key:

*key ipAddress ipMask relaySecret*

*no key ipAddress ipMask*

To assign an ISAKMP/IKE key:

*key keyString*

*no key*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** From RADIUS Configuration mode, specifies the secret for the RADIUS authentication, accounting, dynamic-request server, or preauthentication server that is used to calculate the RADIUS authenticator field during exchanges with the RADIUS server. The **no** version removes the secret and causes the router to drop all requests for the RADIUS client.

From RADIUS Relay Configuration mode, specifies the IP address and mask of the network that will use the relay authentication or accounting server, and the secret used during exchanges between the RADIUS relay server and client. The **no** version removes the secret.

From IPsec Manual Key Configuration mode, configures a manual ISAKMP/IKE preshared key. There is no **no** version. To delete a key, use the **no** version of the **ipsec key manual** command.

- Options**
- *secret*—Authentication, accounting, dynamic-request, or preauthentication server secret text string used by RADIUS to encrypt the client and server authenticator field during exchanges between the router and a RADIUS server. The router encrypts PPP PAP passwords using this text string.
  - *ipAddress*—IP address for client network
  - *ipMask*—IP mask for the client network
  - *relaySecret*—Text string; up to 32 characters
  - *keyString*—Key value in ASCII format; up to 200 characters

**Mode** IPsec Manual Key Configuration, RADIUS Configuration, RADIUS Relay Configuration

**Related Documentation**

- [Configuring RADIUS-Based Mirroring](#)

## key-string

---

**Syntax**    `key-string keyStringData`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Manually configures a 1024-bit or 2048-bit ISAKMP/IKE public key that a remote peer uses for RSA authentication without the need for a digital certificate. The key string represents the public key hexadecimal data that includes the ASN.1 object identifier and sequence tags for RSA encryption. There is no **no** version. To remove a peer public key from the router, use the **no** version of the **ipsec key pubkey-chain rsa** command.

**Options**

- *keyStringData*—Alphanumeric string with a maximum length of 1999 characters; delimited by the first character of the string, which must be repeated at the end of the string and must not occur anywhere else in the string

**Mode**    IPSec Peer Public Key Configuration



## CHAPTER 12

# L Commands

## l2c

---

**Syntax**    [ no ] l2c

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Accesses the L2C Configuration (config-l2c) mode for ANCP. The **no** version exits the L2C Configuration mode and removes all ANCP configuration.

**Mode**    Global Configuration

## l2c end-user-id

---

**Syntax**    `l2c end-user-id idString neighbor neighborName`  
              `no l2c end-user-id idString`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates the GSMP output label associated with the interface. In addition to the label, this command also specifies the access node using the **neighbor** keyword. The **no** version removes the output label association.

**Options**

- *idString*—String to identify the GSMP label
- *neighborName*—Name of the neighboring access node

**Mode**    Interface Configuration, Subinterface Configuration

## l2c ip listen

---

**Syntax** [ no ] l2c ip listen

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a listening TCP socket at the virtual router within the ANCP context. ANCP needs TCP sockets so that neighbors can open GSMP sessions. The **no** version removes the listening TCP socket and stops any new sessions from being established. The **no** version does not terminate any existing GSMP sessions.

**Mode** Global Configuration

## **l2c ip oif**

---

**Syntax** [ no ] l2c ip oif

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates an IGMP session at the virtual router within the context. ANCP needs IGMP sessions so it can convey OIF mapping events to the appropriate ANCP neighbor. The **no** version removes the IGMP session.

**Mode** Global Configuration

## l2c line-configuration

---

**Syntax** l2c line-configuration interface *interfaceType* *interfaceSpecifier* *profileName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Generates a GSMP port management message to the access node for the purpose of configuring a DSL profile string on the specified neighbor interface. There is no **no** version.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *profileName*—Name of profile to be used in the line configuration (port management) message

**Mode** Global Configuration

## l2c max-branches

---

**Syntax** [ no ] l2c max-branches *maxBranches*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the maximum number of branches the ANCP end user can have. The **no** version returns the maximum number of branches to its default value (unlimited branches).

**Options**

- *maxBranches*—Maximum number of branches allowed for the ANCP end user in the range 1–64000

**Mode** Interface Configuration, Subinterface Configuration

## l2c oam

---

**Syntax** `l2c oam { neighbor neighborName end-user-id endUserId | interface interfaceType interfaceSpecifier } [ count countValue ] [ timeout timeoutValue ]`

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Triggers the access node to run a local loopback test on the specified interface. There is no **no** version.

- Options**
- *neighborName*—Name of the neighbor
  - *endUserId*—Output ANCP label
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *countValue*—Number of local loopback messages
  - *timeoutValue*—Time (in seconds) for the access node to wait for a loopback response from the neighbor

**Mode** Privileged Exec, User Exec



## l2c peer-attachment-id

---

**Syntax** l2c peer-attachment-id *idString*

no l2c peer-attachment-id

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates the GSMP input label associated with the interface. The **no** version removes the input label association.

**Options** • *idString*—String to identify the GSMP label

**Mode** Interface Configuration, Subinterface Configuration

## l2tp checksum

---

**Syntax** [ no ] l2tp checksum

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the generation of a UDP data integrity checksum in data packets sent to an L2TP peer. The default setting is disabled. The **no** version disables the generation of the checksums.

**Mode** Global Configuration

## l2tp classifier-list

**Syntax** `l2tp classifier-list classifierName [ traffic-class trafficClassName ]`  
`[ color { green | yellow | red } ] [ user-packet-class userPacketClassValue ]`  
`no l2tp classifier-list classifierName [ classifierNumber ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies a classifier control list. The **no** version removes the classifier control list.

- Options**
- *classifierName*—Name of the classifier control list entry
  - *classifierNumber*—Index of the classifier list entry; use the **show classifier-list** command to see a list of entries with index numbers
  - *trafficClassName*—Name of the traffic class to match
  - *green*—Matches packet color to green, indicating a low drop preference
  - *yellow*—Matches packet color to yellow, indicating a medium drop preference
  - *red*—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—User packet class value

**Mode** Global Configuration

**Related Documentation**

- Creating or Modifying Classifier Control Lists for L2TP Policy Lists

## l2tp destination lockout-test

---

**Syntax** [ no ] l2tp destination lockout-test

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Configures L2TP to test locked-out destinations to verify whether a destination is available before it is returned to service. The **no** version restores the default behavior, in which locked-out destinations are not tested.

**Mode** Global Configuration

## l2tp destination lockout-timeout

---

**Syntax** l2tp destination lockout-timeout *timeOutValue*

no l2tp destination lockout-timeout

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Specifies the amount of time an L2TP destination remains in the lockout state after the destination becomes unavailable. When the timeout period expires, the router either begins the lockout test procedure (if configured to do so) or immediately returns the destination to service. The **no** version restores the default lockout timeout value.

**Options**

- *timeOutValue*—Number of seconds in the range 60–3600; default is 300 seconds (5 minutes)

**Mode** Global Configuration

## l2tp destination profile

---

**Syntax**    l2tp destination profile { *profileName* [ [ virtual-router *vrName* ]  
   ip address *ipAddress* ] | [ virtual-router *vrName* ] ip address *ipAddress* }  
  
             no l2tp destination profile { *profileName* |  
   [ virtual-router *vrName* ] ip address *ipAddress* }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Creates or accesses a destination profile that defines the location of a LAC. The **no** version removes the L2TP destination profile.

- Options**
- *profileName*—Name of the L2TP destination profile
  - *vrName*—Name of the virtual router to be used to reach the destination (that is, the LAC). If you do not specify a virtual router, the current virtual router context is used.
  - *ipAddress*—IP address to be used to reach the destination

**Mode**    Global Configuration

## l2tp destruct-timeout

---

**Syntax**    l2tp destruct-timeout *seconds*  
              no l2tp destruct-timeout

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the maximum time for which the router maintains dynamic destinations, tunnels, and sessions that have terminated. When a subscriber is terminated, the server port that hosted the subscriber session is released after the dynamic interface destruct timeout is exceeded. The server port that is released is available for a new incoming-call request (ICRQ) packet that the LAC sends to the LNS. Until the time any server port is available to be used for a new incoming call, new ICRQ packets are denied because of a lack of system resources. The **no** version restores the default value, 600 seconds.

**Options**    • *seconds*—Time in the range 10–3600 seconds (1 hour)

**Mode**    Global Configuration

## l2tp dial-out connecting-timer-value

---

**Syntax** [ no ] l2tp dial-out connecting-timer-value *connectingTime*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the maximum amount of time allowed for successful establishment of an L2TP dial-out session. The **no** version restores the default value, 30 seconds.

**Options** • *connectingTime*—Range 30–3600 seconds

**Mode** Global Configuration



## l2tp dial-out dormant-timer-value

---

**Syntax** [ no ] l2tp dial-out dormant-timer-value *dormantTime*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines how long the dial-out session stays in the dormant state waiting for a new trigger after the associated L2TP outgoing call is ended. The **no** version set the dormant timer to the default value, 300 seconds (5 minutes).

**Options** • *dormantTime*—Range 0–3600 seconds

**Mode** Global Configuration

## l2tp dial-out max-buffered-triggers

---

**Syntax** [ no ] l2tp dial-out max-buffered-triggers *maxBuffers*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the maximum number of buffered trigger packets held for any dial-out session pending the successful establishment of the L2TP session. The **no** version set the number of trigger buffers to the default value, 0.

**Options** • *maxBuffers*—Range 0–50 buffered packets

**Mode** Global Configuration

## l2tp dial-out session delete

---

**Syntax** l2tp dial-out session delete *triggerIpAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Deletes a dial-out session. There is no **no** version.

**Options** • *triggerIpAddress*—Target IP address of the session

**Mode** Privileged Exec

## l2tp dial-out session reset

---

**Syntax** l2tp dial-out session reset *triggerIpAddress*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Resets the state of a dial-out session by forcing it to the dormant state. There is no **no** version.

**Options** • *triggerIpAddress*—Trigger IP address of the session

**Mode** Privileged Exec

## l2tp dial-out target

---

**Syntax**    l2tp dial-out target *ipAddress ipAddressMask domainName profile profileName*  
              no l2tp dial-out target *ipAddress ipAddressMask*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Defines an L2TP dial-out target that enables the creation of a dial-out session. The **no** version removes the L2TP dial-out route or target.

- Options**
- *ipAddress*—IP address of the target
  - *ipAddressMask*—IP address mask of the target
  - *domainName*—Domain name to be used in the outgoing call Access-Request message
  - *profileName*—Name of profile to be used in the creation of the interface stack

**Mode**    Global Configuration

## l2tp disable calling-number-avp

---

**Syntax** [ no ] l2tp disable calling-number-avp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents the E Series LAC from sending the Calling Number attribute value pair (AVP) in incoming-call-request (ICRQ) packets. The **no** version enables sending of the Calling Number AVP, the default setting.

**Mode** Global Configuration

## l2tp disable challenge

---

**Syntax** [ no ] l2tp disable challenge

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables the generation of local tunnel authentication challenges. The **no** version enables local challenge generation, which is the default setting.

**Mode** Global Configuration

## l2tp disconnect-cause

---

**Syntax** [ no ] l2tp disconnect-cause

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables an E Series LNS to generate, for all L2TP sessions, a PPP Disconnect Cause Code attribute value pair (AVP) and include it in all L2TP Call-Disconnect-Notify (CDN) messages that it sends to an LAC. This action provides a mechanism for the LAC to obtain information about the cause of a session disconnection. The **no** version disables generation of the PPP Disconnect Cause Code AVP, which is the default setting.

**Mode** Global Configuration



## l2tp drain

---

**Syntax** [ no ] l2tp drain

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents the creation of new destinations, tunnels, and sessions for the router. This command works in conjunction with the **l2tp shutdown** command. Both commands affect the status of the administrative state of L2TP on the router; the **l2tp drain** command sets the administrative state to drain. The **no** version allows the creation of new destinations, tunnels, and sessions for the router.

**Mode** Global Configuration

## **l2tp drain destination**

---

**Syntax**    [ no ] l2tp drain destination { *destinationName*  
                  | [ virtual-router *vrName* ] ip *ipAddress* }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Prevents the creation of new tunnels and sessions at a destination. This command works in conjunction with the **l2tp shutdown destination** command. Both commands affect the status of the administrative state of L2TP for the destination; the **l2tp drain destination** command sets the administrative state to drain. The **no** version allows the creation of new tunnels and sessions at a destination.

**Options**    • *destinationName*—Name the router assigns to the LNS  
              • *vrName*—Name of the virtual router on which the destination exists  
              • *ipAddress*—IP address of the LNS

**Mode**    Global Configuration

## l2tp drain tunnel

---

**Syntax** [ no ] l2tp drain tunnel { *destinationName* |  
[ virtual-router *vrName* ] ip *ipAddress* *tunnelName* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents the assignment of new sessions to a tunnel. This command works in conjunction with the **l2tp shutdown tunnel** command. Both commands affect the status of the administrative state of L2TP for the tunnel; the **l2tp drain tunnel** command sets the administrative state to drain. The **no** version allows the assignment of new sessions to a tunnel.

- Options**
- *destinationName*—Name the router assigns to the LNS
  - *vrName*—Name of the virtual router on which the tunnel exists
  - *ipAddress*—IP address of the LNS
  - *tunnelName*—Name of the tunnel

**Mode** Global Configuration

## l2tp failover-resync

---

**Syntax** l2tp failover-resync { failover-protocol | failover-protocol-fallback-to-silent-failover | silent-failover | disable }

no l2tp failover-resync

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** Configures the global L2TP peer resynchronization method that an L2TP failed endpoint uses to resynchronize with its peer non-failed endpoint. This setting can be overridden by a peer resynchronization method that is configured by either an L2TP host profile or an AAA domain map tunnel configuration. The **no** version disables peer resynchronization. The **default** version restores the default peer resynchronization method, failover-protocol-fallback-to-silent-failover.

- Options**
- failover-protocol—Specifies the L2TP failover protocol method
  - failover-protocol-fallback-to-silent-failover—Specifies the L2TP failover protocol method; however, if the peer does not support this method, the silent failover method is used; this is the default setting
  - silent-failover—Specifies the silent failover method
  - disable—Disables peer resynchronization

**Mode** Global Configuration

## l2tp fail-over-within-preference

---

**Syntax** [ no ] l2tp fail-over-within-preference

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables tunnel selection within a preference level. The **no** version restores the default behavior, which is to drop down a preference level when a connection attempt has failed.

**Mode** Global Configuration

## l2tp ignore-receive-data-sequencing

---

**Syntax** [ no ] l2tp ignore-receive-data-sequencing

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Suppresses sequence number checking for data packets received on all L2TP tunnels in the router. This setting affects only packets received on a tunnel, not packets sent on a tunnel. The L2TP LAC still inserts sequence numbers into data packets if the LAC receives packets from the LNS that contain sequence numbers. The **no** version restores the default, which causes the router to check the sequence numbers in data packets that it receives on L2TP tunnels.



.....  
**NOTE:** If you are using IP reassembly, we recommend that you set up the router to ignore sequence numbers in received data packets. Because IP reassembly may reorder L2TP packets, out-of-order packets may be dropped if sequence numbers are being used on L2TP data packets.  
.....

**Mode** Global Configuration

## l2tp ignore-transmit-address-change

---

**Syntax** [ no ] l2tp ignore-transmit-address-change [ ip-address | udp-port ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
**ip-address** and **udp-port** keywords added in JunosE Release 7.1.0.

**Description** Specifies that E Series routers ignore address changes in Start-Control-Connection-Reply (SCCRP) control packets received from the remote endpoint. If you do not include a keyword, the router ignores the entire address change. The **no** version restores the default, which causes the router to accept address changes in response to SCCRPs.

- Options**
- **ip-address**—Ignores only IP address changes
  - **udp-port**—Ignores only UDP port number changes

**Mode** Global Configuration

## l2tp policy

---

**Syntax** l2tp policy { input | output } *policyName* [ statistics  
{ enabled | disabled } [ merge ]  
  
no l2tp policy { input | output }

**Release Information** Command introduced before JunosE Release 7.1.0.  
**merge** keyword added in JunosE Release 7.2.0.

**Description** Assigns an L2TP policy list to a profile, which then assigns the policy to an interface. If you enter the **l2tp policy** command and the policy list does not exist, the router creates a policy list with no rules, the default. Attaching this policy list to an interface filters all packets on that interface. You must specify the **input** or **output** keyword to assign the policy list to the ingress or egress of the interface. The **no** version removes the association between a policy list and a profile.

- Options**
- input—Applies policy to data arriving at the interface
  - output—Applies policy to data leaving the interface
  - *policyName*—Name of the policy; maximum of 40 characters
  - statistics—Enables or disables collection of policy routing statistics
    - enabled—Enables collection of policy routing statistics
    - disabled—Disables collection of policy routing statistics
  - merge—Enables merging of multiple policies to form a single policy

**Mode** Profile Configuration

**Related Documentation**

- Setting a Statistics Baseline for Policies



## l2tp policy-list

---

**Syntax** [ no ] l2tp policy-list [ *policyName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies an L2TP policy list. If you enter an **l2tp policy-list** command and type **exit**, the router creates a policy list with no rules. When a policy list does not have rules, the router inserts a default filter rule. Attaching this policy list to an interface filters all packets on that interface. The **no** version removes a policy list.

**Options** • *policyName*—Name of the policy list

**Mode** Global Configuration

**Related Documentation** • Creating Policy Lists for L2TP

## l2tp policy-parameter hierarchical

---

**Syntax** l2tp policy-parameter hierarchical *parameterName* { *nodeValue* | atm | atm-vc | atm-vp  
*vpValue* | ethernet | fr-vc | forwarding | svlan *svlanValue* | vlan }

no policy-parameter *parameterName*

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Specifies a parameter value for L2TP interfaces. The **no** version removes the policy parameter and its contents.

- Options**
- *parameterName*—Name of policy parameter
  - *nodeValue*—Aggregation node number in the range 1–65535
  - *vpValue*—ATM VPI number in the range 0–255
  - *svlanValue*—SVLAN ID number in the range 0–4095

**Mode** Interface Configuration

**Related Documentation**

- Creating a Classifier Group for a Policy List

## l2tp policy-parameter reference-rate

---

**Syntax** l2tp policy-parameter reference-rate *parameterName* [ increase ] *value*  
no l2tp policy-parameter reference-rate *parameterName*

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates an L2TP policy parameter for a reference rate; creates a global parameter if it does not exist. The **no** version removes the policy parameter and its contents; if used with the **increase** keyword, decreases the value.

- Options**
- *parameterName*—Name of policy parameter up to 40 characters
  - increase—Increments the existing reference rate value
  - *value*—Value of the reference rate parameter, in the range 0–4292967295

**Mode** Profile Configuration

**Related Documentation**

- Creating a Classifier Group for a Policy List

## l2tp reject-transmit-address-change

---

**Syntax** [ no ] l2tp reject-transmit-address-change [ ip-address | udp-port ]

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies that E Series routers reject address changes in Start-Control-Connection-Reply (SCCRP) control packets received from the remote endpoint. If you do not include a keyword, the router rejects the entire address change. The **no** version restores the default, which causes the router to accept address changes in response to SCCRP packets.

- Options**
- ip-address—Rejects only IP address changes
  - udp-port—Rejects only UDP port number changes

**Mode** Global Configuration

## l2tp retransmission

**Syntax** l2tp retransmission *retries* [ established | not-established ]  
 no l2tp retransmission [ *retries* ] [ established | not-established ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the number of retransmission retries, and allows you to apply the retry count to established and/or unestablished tunnels. If you do not include a keyword, the router applies the retry count to all tunnels. The **no** version resets the number of retransmissions to the default value, 5.



**NOTE:** If you perform a stateful SRP switchover on an LNS device, we recommend that you configure the maximum number of retransmission attempts as 10, although the default number of attempts is 5. This recommendation applies for all types of L2TP peer resynchronization methods configured for LNS devices.

- Options**
- *retries*—Number in the range 2–30
  - *established*—Applies the retry count only to established tunnels
  - *not-established*—Applies the retry count only to tunnels that are not established

**Mode** Global Configuration

## **l2tp rx-connect-speed-when-equal**

---

**Syntax**    [ no ] l2tp rx-connect-speed-when-equal

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Generates the L2TP receive (RX) speed AVP when the RX and TX speeds are equal. The **no** version disables generation of the RX speed AVP when the RX and TX speeds are equal.

**Mode**    Global Configuration

## **l2tp shutdown**

---

**Syntax** [ no ] l2tp shutdown

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Closes all destinations, tunnels, and sessions and prevents the creation of new destinations, tunnels, and sessions for the router. This command works in conjunction with the **l2tp drain** command. Both commands affect the status of the administrative state of L2TP on the router; the **l2tp shutdown** command sets the administrative state to disabled. The **no** version enables the creation of new destinations, tunnels, and sessions for the router.

**Mode** Global Configuration

## **l2tp shutdown destination**

---

**Syntax** [ no ] l2tp shutdown destination { *destinationName* |  
[ virtual-router *vrName* ] ip *ipAddress* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Closes all tunnels and sessions at a destination, and prevents the creation of new tunnels and sessions at that destination. This command works in conjunction with the **l2tp drain destination** command. Both commands affect the status of the administrative state of L2TP on the destination; the **l2tp shutdown destination** command sets the administrative state to disabled. The **no** version enables the creation of new tunnels and sessions at that destination.

**Options**

- *destinationName*—Name the router assigns to the LNS
- *vrName*—Name of the virtual router on which the destination exists
- *ipAddress*—IP address of the LNS

**Mode** Global Configuration



## l2tp shutdown session

---

**Syntax** [ no ] l2tp shutdown session { *destinationName* |  
[ virtual-router *vrName* ] ip *ipAddress* *sessionName* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Closes a specific session. The **no** version has no effect because all L2TP sessions are dynamic and cannot be restarted after they have been shut down.

**Options**

- *destinationName*—Name that the router assigns to the LNS
- *vrName*—Name of the virtual router on which the destination exists
- *ipAddress*—IP address of the LNS
- *sessionName*—Name of the session

**Mode** Global Configuration

## l2tp shutdown tunnel

**Syntax** [ no ] l2tp shutdown tunnel { *destinationName* |  
[ virtual-router *vrName* ] ip *ipAddress* *tunnelName* }

**Release Information** Command introduced before JunosE Release 7.1.0.

<b>Description</b>	Closes all sessions in a tunnel, and prevents the creation of new sessions in that tunnel. This command works in conjunction with the <b>l2tp drain tunnel</b> command. Both commands affect the status of the administrative state of L2TP on the tunnel; the <b>l2tp shutdown tunnel</b> command sets the administrative state to disabled. The <b>no</b> version enables the creation of new sessions in that tunnel.
--------------------	--

**Options**

- *destinationName*—Name the router assigns to the LNS
- *vrName*—Name of the virtual router on which the tunnel exists
- *ipAddress*—IP address of the LNS
- *tunnelName*—Name of the tunnel

Mode Global Configuration

## l2tp switch-profile

---

**Syntax** [ no ] l2tp switch-profile *profileName*

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Creates and names an L2TP tunnel switch profile. This command accesses L2TP Tunnel Switch Profile Configuration mode, from which you can define the L2TP tunnel switching behavior for the interfaces to which this profile is assigned. The **no** version removes the named tunnel switch profile from the router.

**Options**

- *profileName*—Name of the tunnel switch profile; a string of up to 64 alphanumeric characters

**Mode** Global Configuration

## l2tp tunnel default-receive-window

---

**Syntax**    l2tp tunnel default-receive-window *receiveWindowSize*  
              no l2tp tunnel default-receive-window

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the default L2TP receive window size (RWS) for a tunnel on both the LAC and the LNS. The RWS is the number of packets that the peer can transmit without receiving an acknowledgment from the router. This command affects only those tunnels configured on the router after the command is issued; it has no effect on previously configured tunnels. The **no** version restores the default behavior, in which the router chooses the default RWS.

**Options**    • *receiveWindowSize*—Default receive window size, in packets; currently, the only supported value is 4

**Mode**    Global Configuration

## **l2tp tunnel idle-timeout**

---

**Syntax**    l2tp tunnel idle-timeout [ *timeOutValue* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the tunnel idle-timeout value. Creates persistent tunnels by setting the value to 0. There is no **no** version.

**Options**    • *timeOutValue*—Number in the range 0–86400 seconds

**Mode**    Global Configuration

## **l2tp tunnel short-drain-timeout**

---

**Syntax**    l2tp tunnel short-drain-timeout [ *timeOutValue* ]

            no l2tp tunnel short-drain-timeout

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Configures the amount of time a disconnected LAC L2TP tunnel waits (the drain timeout) before restarting after a restart request is received. The **no** version restores the default setting.

**Options**    • *timeOutValue*—Short drain timeout in seconds, in the range 0–31; default value is 2 seconds

**Mode**    Global Configuration

## **l2tp tunnel-switching**

---

**Syntax** [ no ] l2tp tunnel-switching

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables tunnel switching chassis-wide. The **no** version restores the default, disabling tunnel switching.

**Mode** Global Configuration

## l2tp tunnel test

---

**Syntax** l2tp tunnel test *authenticateName* [ *tunnelName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Allows you to force the establishment of a tunnel in order to verify the tunnel configuration and to verify connectivity. There is no **no** version.

- Options**
- *authenticateName*—Authenticate name used to look up tunnel test parameters
  - *tunnelName*—Name of the tunnel to be tested

**Mode** Privileged Exec



## l2tp unlock destination

---

**Syntax** l2tp unlock destination { *destinationName* | [ virtual-router *vrName* ] ip *ipAddress* }

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Forces L2TP to immediately unlock the specified L2TP destination and return the destination to the available state. Any remaining lockout time and the lockout test setting (if configured) are not taken into account. There is **no** no version.

**Options**

- *destinationName*—Name of the L2TP destination
- *vrName*—Name of the virtual router on which the destination exists
- *ipAddress*—IP address of the destination

**Mode** Privileged Exec (at privilege level 10 or higher)

## l2tp unlock-test destination

---

**Syntax** l2tp unlock-test destination { *destinationName* |  
[ virtual-router *vrName* ] ip *ipAddress* }

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Forces L2TP to disregard any remaining lockout time and immediately begin the lockout test procedure for the specified destination. If lockout testing is not enabled, this command immediately unlocks the destination. There is **no** no version.

**Options**

- *destinationName*—Name of the L2TP destination
- *vrName*—Name of the virtual router on which the destination exists
- *ipAddress*—IP address of the destination

**Mode** Privileged Exec (at privilege level 10 or higher)

## l2tp weighted-load-balancing

---

**Syntax** [ no ] l2tp weighted-load-balancing

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Allows you to use a weighted load balancing scheme for session distribution. The **no** version restores the default behavior, wherein the session load of a chassis is distributed evenly across all tunnels defined to be at the same preference level.

**Mode** Global Configuration

## l2vpn control-word

---

**Syntax** [ no | default ] l2vpn *l2VpnName* control-word

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Indicates that the local preference is to use the control word for the layer 2 packets encapsulated in the MPLS packets that are sent to the remote PE router. The **no** version indicates that the local preference is to not use the control word for the layer 2 packets encapsulated in the MPLS packets that are sent to the remote PE router. The **default** version accepts the preference determined by the interface stack on which the MPLS interface is stacked.

**Options** • *l2VpnName*—Name of the VPWS instance

**Mode** Global Configuration

**Related Documentation** • [Configuring an VPWS Instance](#)

---

## l2vpn encapsulation-type

---

**Syntax** `l2vpn l2VpnName encapsulation-type { atm-aal5-vcc | atm-vcc-cell | cisco-hdlc | ethernet | frame-relay | ppp | vlan }`

`no l2vpn l2VpnName`

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates a VPWS L2VPN instance and configures the encapsulation type for interfaces in that VPWS instance. The **no** version removes the VPWS instance.

- Options**
- *l2VpnName*—Name of the VPWS instance
  - atm-aal5-vcc—Specifies ATM AAL5 VCC encapsulation
  - atm-vcc-cell—Specifies ATM VCC Cell encapsulation
  - cisco-hdlc—Specifies Cisco HDLC encapsulation
  - ethernet—Specifies Ethernet encapsulation
  - frame-relay—Specifies Frame-Relay encapsulation
  - ppp—Specifies PPP encapsulation
  - vlan—Specifies VLAN encapsulation

**Mode** Global Configuration

**Related Documentation**

- [Configuring an VPWS Instance](#)

## **l2vpn local-site-id remote-site-id**

---

**Syntax**    *l2vpn l2VpnName* local-site-id *localSiteId* remote-site-id *remoteSiteId*  
              no *l2vpn l2VpnName*

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Configures a layer 2 interface as a member of a VPWS L2VPN by specifying local and remote customer site IDs. The **no** version removes the interface as a member of the VPWS L2VPN.

- Options**
- *l2VpnName*—Name of the VPWS instance
  - *localSiteId*—Numerical identifier for the local site in the VPWS L2VPN, in the range 1–65535
  - *remoteSiteId*—Numerical identifier for the remote site in the VPWS L2VPN, in the range 1–65535

**Mode**    Interface Configuration, Subinterface Configuration

**Related Documentation**

- [Configuring Customer-Facing Interfaces in the VPWS Instance](#)

---

## l2vpn rd

---

<b>Syntax</b>	<code>l2vpn l2VpnName rd <i>distinguisher</i></code>
<b>Release Information</b>	Command introduced in JunosE Release 8.1.0.
<b>Description</b>	Specifies the unique two-part route distinguisher for the VPWS L2VPN instance. Once configured, you cannot change or remove the route distinguisher. There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>l2VpnName</i>—Name of the VPWS instance</li><li>• <i>distinguisher</i>—Unique two-part identifier of the format <i>number1:number2</i> where:<ul style="list-style-type: none"><li>• <i>number1</i>—AS number or an IP address</li><li>• <i>number2</i>—Unique integer; 32 bits if <i>number1</i> is an AS number; 16 bits if <i>number1</i> is an IP address</li></ul></li></ul>
<b>Mode</b>	Global Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• Configuring an VPWS Instance</li></ul>

## l2vpn route-target

---

**Syntax** [ no ] l2vpn *l2VpnName* route-target { import | export | both } *extendedCommunity*

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Creates or adds to a list of VPWS L2VPN extended communities that the router uses to determine which routes are imported by the specified VPWS L2VPN instance. The **no** version removes a route target from the specified list.

- Options**
- *l2VpnName*—Name of the VPWS instance
  - **import**—Adds the route target to the import list for the specified VPWS instance; the VPWS accepts only routes that have at least one route target that matches a route target in the import list
  - **export**—Adds the route target to the export list for the specified VPWS instance; all routes advertised from this VPWS are associated with the route targets in the export list; at least one route target in the export list must match a route target in the import list of a VPWS L2VPN receiving the route for the route to be accepted by the VPWS L2VPN.
  - **both**—Adds the route target to both the import list and export list for the specified VPWS instance; recommended setting for a VPWS instance
  - *extendedCommunity*—Two-part number of the format *number1:number2* that identifies an extended community of VPWS L2VPNs where:
    - *number1*—AS number or an IP address
    - *number2*—Unique integer; 32 bits if *number1* is an AS number; 16 bits if *number1* is an IP address

**Mode** Global Configuration

**Related Documentation**

- [Configuring an VPWS Instance](#)



---

## l2vpn sequencing

---

**Syntax** [ no | default ] l2vpn *l2VpnName* sequencing

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Specifies that the local preference is to include nonzero sequence numbers with the control word, enabling the remote PE to detect out-of-order packets. This command has no effect if no control word is sent in the packets. The router always accepts zero sequence numbers and checks the order of nonzero sequence numbers of MPLS packets received from the remote PE. Any out of order packets are dropped, regardless of whether sequencing is configured. The **no** version specifies that the sequencing number in the control word is set to zero, instructing the remote PE router to not attempt to detect out-of-order packets; has no effect if no control word is sent in the packets. The **default** version accepts the preference determined by the interface stack on which the MPLS shim interface is stacked.

**Options** • *l2VpnName*—Name of the VPWS instance

**Mode** Global Configuration

**Related Documentation** • Configuring an VPWS Instance

## l2vpn site-name site-id

---

**Syntax** [ no ] l2vpn l2VpnName site-name *siteName* site-id *siteId*  
[ multi-homed priority *priority* ]

**Release Information** Command introduced in JunosE Release 8.1.0.  
**multi-homed priority** keywords and *priority* variable added in JunosE Release 9.3.0.

**Description** Configures a name and a unique site identifier for a customer site that belongs to the specified VPWS instance. Optionally configures the site to be multihomed. In a VPWS configuration, each customer site is represented by one or more customer edge (CE) devices located at the edge of the customer's network. The **no** version removes the site name and site identifier from the VPWS instance, or removes the multihomed configuration for the customer site and returns it to a single-homed state.

- Options**
- *l2VpnName*—Name of the VPWS instance
  - *siteName*—Name of the site; string of up to 128 alphanumeric characters
  - *siteId*—Numerical identifier for the site, in the range 1–65535; must be unique across the VPWS domain
  - *priority*—Number that sets the priority of this VPWS instance for a multi-homed site, in the range 1–65535; priority is sent in BGP advertisements as the Local-Preference attribute and determines whether the router hosting the VPWS instance becomes the designated VE router for this multihomed site

**Mode** Global Configuration

**Related Documentation**

- Configuring an VPWS Instance

## **l2vpn site-range**

---

**Syntax** `l2vpn l2VpnName site-range siteRange`

`no l2vpn l2VpnName site-range`

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Configures the maximum number of customer sites that can participate in the specified VPWS L2VPN. In a VPWS L2VPN configuration, each customer site is represented by a customer edge (CE) device located at the edge of the customer's network. The **no** version restores the default site range, 1.

- Options**
- *l2VpnName*—Name of the VPWS instance
  - *siteRange*—Maximum number of sites that can participate in the VPWS domain, in the range 1–65535; default value is 1

**Mode** Global Configuration

**Related Documentation**

- [Configuring an VPWS Instance](#)

## lacp

---

**Syntax**    lacp { active | passive }

             no lacp

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures whether an Ethernet link in an IEEE 802.3ad link aggregation group (LAG) bundle participates actively or passively in the Link Aggregation Control Protocol (LACP). LACP controls the transmission of protocol data units (PDUs) to exchange information between partner links in a LAG bundle. By default, Ethernet links do not send LACP PDUs. The **no** version restores the default behavior.

**Options**

- active—Causes the Ethernet link to always transmit LACP PDUs, regardless of whether its partner link is set to active or passive LACP participation
- passive—Causes the Ethernet link to transmit LACP PDUs only when it receives LACP PDUs from its partner link

**Mode**    Interface Configuration

## lacp port-priority

---

**Syntax**    lacp port-priority *portPriority*  
              no lacp port-priority

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the priority for an Ethernet member link, also known as an Ethernet port, in an IEEE 802.3ad link aggregation group (LAG) bundle. The member link with the lowest numerical priority value has the highest priority. The Ethernet member link with the highest priority is selected first to join the LAG bundle. The **no** version restores the default priority value, 32768.

**Options**    • *portPriority*—Priority value; integer in the range 0–65535; default value is 32768

**Mode**    Interface Configuration

## lag dos-protection-group

---

**Syntax**    lag dos-protection-group *groupName*  
              no lag dos-protection-group

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Attaches a lag denial of service (DoS) protection group to an interface. The **no** version removes the attachment of the DoS protection group from the interface.

**Options**    • *groupName*—Name of the DoS protection group; string of up to 31 alphanumeric characters

**Mode**    Interface Configuration

## lease

---

**Syntax**    `lease { days [ hours [ minutes [ seconds ] ] ] | infinite }`  
               `no lease`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the time period for which the supplied IP address is valid. The **no** version restores the default lease time, 30 minutes.



**NOTE:** Ensure that DHCP clients have a minimum lease of 120 minutes before you begin a unified in-service software upgrade to prevent unwanted lease expirations due to the length of the unified ISSU process.

- Options**
- *days*—Number of days for which the IP address is valid; in the range 0–32768
  - *hours*—Number of hours for which the IP address is valid in the range 0–24
  - *minutes*—Number of minutes for which the IP address is valid; in the range 0–60
  - *seconds*—Number of seconds for which the IP address is valid; in the range 0–60
  - *infinite*—Assigns a lease that does not expire

**Mode**    DHCP Local Pool Configuration

## license bfd

---

**Syntax**    `license bfd licenseKey`

`no license bfd`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the Bidirectional Forwarding Detection (BFD) license provided by your sales representative or Juniper Networks Customer Service. The **no** version disables the license.

**Options**    • *licenseKey*—Unique string of up to 15 alphanumeric characters that we provide to you

**Mode**    Global Configuration



## license b-ras

---

**Syntax**    `license b-ras licenseKey`

`no license b-ras`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the B-RAS license provided by your sales representative or Juniper Networks Customer Service. Depending on the license purchased, the router supports up to 2,000, 4,000, 8,000, 16,000, or 20,000 authenticated PPP or SRC sessions. The **no** version disables the license.

**Options**    • *licenseKey*—Unique string of up to 15 alphanumeric characters that we provide to you

**Mode**    Global Configuration

## license ipsec-tunnels

---

**Syntax**    `license ipsec-tunnels licenseKey`  
              `no license ipsec-tunnels`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IPSec license key provided by your sales representative or Juniper Networks Customer Service. Depending on the license purchased, the router supports up to 5,000, 7,500, or 10,000 tunnels per chassis. The **no** version disables the license.

**Options**    • *licenseKey*—Unique string of alphanumeric characters that we provide to you

**Mode**    Global Configuration

## license ipv6

---

**Syntax**    `license ipv6 licenseKey`

`no license ipv6`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the IPv6 license key provided by your sales representative or Juniper Networks Customer Service. The **no** version disables the license.

**Options**    • *licenseKey*—Unique string of alphanumeric characters that we provide to you

**Mode**    Global Configuration

## license issu

---

**Syntax**    `license issu licenseKey`  
`no license issu`

**Release Information**    Command introduced in JunosE Release 9.2.0.

**Description**    Specifies the unified ISSU license key for the ERX1440 router provided by your sales representative or Juniper Networks Customer Service. No license key is required or available for the E120 and E320 routers. The **no** version disables the license.

**Options**    • *licenseKey*—Unique string of alphanumeric characters that we provide to you

**Mode**    Global Configuration

## license l2tp-session

---

**Syntax**    `license l2tp-session licenseKey`  
               `no license l2tp-session`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the L2TP license key provided by your sales representative or Juniper Networks Customer Service. You can use the license on ERX1440 routers, E120 routers, and E320 routers to increase the number of supported L2TP sessions from 16,000 to 32,000. The **no** version removes the license.



**NOTE:** This command is deprecated and might be removed completely in a future release.

JunosE Software no longer requires you to configure a license to enable support for 32,000 L2TP sessions. The ERX1440 routers, E120 routers, and E320 routers support 32,000 L2TP sessions by default; all other models support a maximum of 16,000 L2TP sessions.

Although the `license l2tp-session` command remains in the CLI, the command has no effect on the actual enforced limit.

**Options**    • *licenseKey*—Unique string of alphanumeric characters that we provide to you

**Mode**    Global Configuration

## license mobile-ip home-agent

---

**Syntax**    license mobile-ip home-agent *licenseKey*  
              no license mobile-ip home-agent

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Configures the license key to enable a home agent. The **no** version does not change any existing Mobile IP configurations such as deleting the existing bindings or preventing any new registrations, but disables the license key. You cannot modify, but only delete, the Mobile IP configurations after enabling the **no** version. For example, if you disable the home agent and delete all existing bindings, you cannot re-enable it until a valid license is provided.

**Options**    • *licenseKey*—Unique alphanumeric license key, up to a maximum of 16 alphanumeric characters, to enable a Mobile IP home agent configuration

**Mode**    Global Configuration

## license nat

---

**Syntax**    `license nat licenseKey`

`no license nat`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the NAT license key provided by your sales representative or Juniper Networks Customer Service. The **no** version disables the license.

**Options**    • *licenseKey*—Unique string of alphanumeric characters that we provide to you

**Mode**    Global Configuration

## license service-management

---

**Syntax**    license service-management *licenseKey*  
              no license service-management

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Specifies the Service Manager license key provided by your sales representative or Juniper Networks Customer Service. The **no** version removes the license.

**Options**    • *licenseKey*—Unique string of alphanumeric characters that Juniper Networks provides to you

**Mode**    Global Configuration



## lifetime

**Syntax** To set an IKE lifetime:

*lifetime seconds*

*no lifetime*

To set an IPSec transport profile lifetime:

*lifetime { kilobytes lowKilobytes highKilobytes | seconds txLowSeconds txHighSeconds | seconds txLowSeconds txHighSeconds kilobytes lowKilobytes highKilobytes }*

*no lifetime*

To set an IPSec tunnel profile lifetime:

*lifetime { seconds tunLowSeconds tunHighSeconds | kilobytes lowKilobytes highKilobytes | seconds tunLowSeconds tunHighSeconds kilobytes lowKilobytes highKilobytes }*

*no lifetime*

**Release Information** Command introduced before JunosE Release 7.1.0.

IPSec Tunnel Profile Configuration mode added in JunosE Release 7.3.0.

**Description** From IKE Policy Configuration mode, associates a lifetime with IKE SAs established with this IKE policy. The **no** version restores the lifetime to its default, 28800 seconds (8 hours).

From IPSec Transport Profile Configuration mode, sets a lifetime range for the IPSec connection in volume of traffic and/or in seconds. If the client PC offers a lifetime within this range, the router accepts the offer. The **no** version returns the lifetime to the default, 100000–4294967295 KB and 900–86400 seconds (1–24 hours).

From IPSec Tunnel Profile Configuration mode, specifies the IPSec lifetime range used on IPSec security association negotiations. The **no** version returns the lifetime to its default, 28800 seconds (8 hours) and no traffic volume limit.

- Options**
- *seconds*—Number of seconds an SA lives before expiring; in the range 900–86400 seconds
  - *lowKilobytes*—Lower range of the lifetime in kilobytes; in the range 100000–4294967295 KB; default value is 100000
  - *highKilobytes*—Higher range of the lifetime in kilobytes; in the range 100000–4294967295 KB; default value is 4294967295
  - *txLowSeconds*—Lower range of the lifetime in seconds; in the range 300–86400 seconds; default value is 3600
  - *txHighSeconds*—Higher range of the lifetime in seconds; in the range 300–86400 seconds; default value is 86400

- *tunLowSeconds*—Lower range of the lifetime in seconds; in the range 900–86400 seconds; default value is 3600
- *tunHighSeconds*—Higher range of the lifetime in seconds; in the range 900–86400 seconds; default value is 86400
- *lowKilobytes*—Lower range of the lifetime in kilobytes; in the range 100000–4294967295 KB; default value is 100000
- *highKilobytes*—Higher range of the lifetime in kilobytes; in the range 100000–4294967295 KB; default value is 4294967295

**Mode** IKE Policy Configuration, IPSec Transport Profile Configuration, IPSec Tunnel Profile Configuration

## line

**Syntax**    `line { console lineNumber | vty lineRangeStart [ lineRangeEnd ] }`  
               `no line vty lineNumber`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Opens virtual terminal lines or the console line and allows you to configure the lines. By default five vty lines (0–4) are open. The **no** version removes a vty line or a range of lines from your configuration; users will not be able to run Telnet, SSH, or FTP to lines that you remove. When you remove a vty line, the router removes all lines above that line. For example, **no line vty 6** causes the router to remove lines 6 through 29. You cannot remove lines 0 through 4.



**NOTE:** Once lines are open, login is enabled by default. Before users can access the lines, you must configure a password, disable login using the **no login** command, or configure AAA authentication on the line.

- Options**
- **console**—Specifies the console line
  - **vty**—Specifies vty lines
  - ***lineNumber***—Number of a single line; 0 for the console line
  - ***lineRangeStart***—Start of the vty line range; a number from 0–29
  - ***lineRangeEnd***—End of the vty line range; a number from 0–29

**Mode**    Global Configuration

## line-card switch

---

**Syntax**    line-card switch *primarySlotNum*

**Release Information**    Command introduced in JunosE Release 11.3.0.

**Description**    Enables a switchover to the secondary line module in a high availability pair of line modules, when the primary line module stops functioning or encounters a fault. A switchover to the secondary module occurs only if you previously activated line module high availability on the router using the **mode high-availability slot** command. There is no **no** version.

**Options**    • *primarySlotNum*—Number of the slot in which the line module configured as the primary resides in the router; for the E120 router, a number in the range 0–5; for the E320 router, a number in the range 0–5 or 11–16

**Mode**    Privileged Exec

## link

---

**Syntax**    `link poolName`

`no link`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Links the pool currently being configured to another DHCP local address pool. The linked pool acts as a backup pool. The **no** version removes the link.

**Options**    • *poolName*—Name of pool to which you want to link the pool currently being configured

**Mode**    DHCP Local Pool Configuration

## link failover arp-flush

---

**Syntax** [ no ] link failover arp-flush

**Release Information** Command introduced in JunosE Release 10.3.0.

**Description** Clears the ARP cache on an interface with redundant ports when the primary link fails. The **no** version maintains the ARP entries on the interface.

**Mode** Interface Configuration

## link failover force

---

**Syntax** link failover force

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Forces a GE I/O module to switch from one port to another. There is no **no** version.

**Mode** Interface Configuration

## link failover timeout

---

**Syntax**    link failover timeout *failTime*  
              no link failover timeout

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the time that the router waits for a port on a GE I/O module to become active before the router switches to the redundant port. The **no** version restores the default setting, in which the router sets this time automatically.

**Options**    • *failTime*—Time that the router waits; in the range 100–10000 ms

**Mode**    Interface Configuration



## link selection

---

**Syntax** link selection { primary | secondary }  
no link selection

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables redundancy on a GE I/O module by allowing operation on the specified port only. The **no** version restores the default situation, in which port redundancy is enabled.

- Options**
- primary—Allows operation on only the primary port
  - secondary—Allows operation on only the redundant port

**Mode** Interface Configuration

## list

---

**Syntax**    `list [ index ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Lists the currently configured MPLS explicit path (optionally starting at a particular index).  
There is no **no** version.

**Options**    • *index*—Number of a node in an ordered set of abstract nodes set with the **index** command; in the range 1–255

**Mode**    Explicit Path Configuration

## load-interval

---

**Syntax**    `load-interval timeInterval`

`no load-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the time interval at which the router calculates bit rates and packet rates for an interface. The **no** version restores the default value, 300 seconds. This command is not available for the Ethernet interface on the SRP module.

**Options**    • *timeInterval*—Multiple of 30 seconds; in the range 30–300

**Mode**    Interface Configuration

## load-rebalance

---

**Syntax** [ no ] load-rebalance [ period *rebalancePeriod* start-threshold *rebalanceStartThreshold* [ percent | subscribers ] stop-threshold *rebalanceStopThreshold* [ percent | subscribers ] maximum-improvement *rebalanceMaximumImprovement* [ percent | subscribers ] ]

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Configures the QoS algorithm for rebalancing the links in an 802.3ad link aggregation group (LAG). To configure the algorithm to dynamically rebalance the LAG using existing parameters, issue the **load-rebalance** command without any keywords. The **no** version restores the default parameters.

- Options**
- *rebalancePeriod*—Time period for rebalancing in seconds; in the range 0–86400; the default is 60 seconds
  - *rebalanceStartThreshold*—Amount of imbalance in the LAG that triggers the algorithm to start rebalancing; the default is 0 percent
    - percent—Specifies that the threshold is measured as a percentage of the average load per link; in the range 0–100
    - subscribers—Specifies that the threshold is measured by the number of subscribers away from the average subscriber count per link in the LAG; in the range 0–100000
  - *rebalanceStopThreshold*—Amount of imbalance in the LAG that triggers the algorithm to stop rebalancing; the default is 0 percent
    - percent—Specifies that the amount of imbalance is measured as a percentage of the average load per link; in the range 0–100
    - subscribers—Specifies that the threshold is measured by the number of subscribers away from the average subscriber count link in the LAG; in the range 0–100000
  - *rebalanceMaximumImprovement*—Maximum number of links in the LAG to rebalance; the default is 100 percent
    - percent—Specifies that the maximum number of links is measured as a percentage of the total links; in the range 0–100
    - subscribers—Specifies that the maximum number of links is measured by the number of subscribers; in the range 0–100000

**Mode** Interface Configuration

**Related Documentation**

- [Configuring Load Rebalancing for 802.3ad Link Aggregation Groups](#)

## local host

---

**Syntax** local host *hostname*

no local host

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures an L2TP local hostname to be used with a remote host. The **no** version removes the local hostname from use with a remote host.

**Options** • *hostname*—L2TP local hostname; string of up to 64 characters (no spaces)

**Mode** L2TP Destination Profile Host Configuration

## local-interface

---

**Syntax**    `local-interface { interfaceType interfaceSpecifier | ipAddress ipAddressMask }`  
`no local-interface`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Maps a domain name to a loopback interface. The **no** version deletes the mapping to the user domain name.



.....  
**NOTE:** In Domain Map Configuration mode, this command is replacing the deprecated **loopback** command for mapping a domain name to a loopback interface. The **loopback** command may be removed completely from the Domain Map Configuration mode in a future release.  
.....

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *ipAddress*—IP address of the loopback interface
  - *ipAddressMask*—IP address mask of the loopback interface

**Mode**    Domain Map Configuration

## local ip address

**Syntax** From L2TP Destination Profile Host Configuration mode:

local ip address *ipAddress*

no local ip address

From IPsec Transport Profile Configuration mode:

[ no ] local ip address *transportIpAddress*

From IPsec Tunnel Profile Configuration mode:

local ip address *transportIpAddress* { pre-share *keyString*  
| pre-share-masked *maskedKeyString* }

no local ip address

**Release Information** Command introduced before JunosE Release 7.1.0.  
IPsec Tunnel Profile Configuration mode added in JunosE Release 7.3.0.

**Description** From L2TP Destination Profile Host Configuration mode, configures a local IP address for use with a remote host. The **no** version removes the local IP address from use with a remote host.

From IPsec Transport Profile Configuration mode, specifies the local endpoint of the IPsec transport connection. It also enters Local IPsec Transport Profile Configuration mode. The **no** version deletes the local IP address.

From IPsec Tunnel Profile Configuration mode, specifies the given local IP address as a server address. The router continues to monitor UDP port 500 for incoming user login requests (that is, IKE source address negotiations). When using global preshared keys, consider the following points:

- Global preshared keys enable a group of users to share a single authentication key. Using a shared key for a group of users simplifies the administrative job of setting up keys. However, changing or removing a preshared key for one user (for security reasons) affects other users with the same key.
- Specific keys for individual users take precedence over global keys assigned to the same user. In other words, if a user has both an assigned specific key and a global key that user must use the specific key or authentication fails.
- Avoid specifying the same local endpoint and virtual router in the same profile. Local endpoint and virtual router values override each other. The last value set in the profile is the value used.

The **no** version causes the router to stop monitoring UDP port 500 for user requests and removes any preshared key associations with the local IP address.

- Options**
- *ipAddress*—IP address used in packets sent to the LAC
  - *transportIpAddress*—Local endpoint for the IPSec transport connection
  - *keyString*—Key value in ASCII format
  - *maskedKeyString*—Key value in ascii format
- Mode** IPSec Transport Profile Configuration, IPSec Tunnel Profile Configuration, L2TP Destination Profile Host Configuration



---

## local ip identity

---

**Syntax**    local ip identity  
              { address *ipAddress* | range *ipRangeLow* *ipRangeHigh* | subnet *netAddress* *netMask* }  
  
              no local ip identity

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Overrides the local identity (phase 2 identity) used for IPSec security association negotiations. For IPSec negotiations to succeed, the local and peer identities at one end of the tunnel must match the peer and local identities at the other end (respectively). The **no** version restores the default value, wildcard network value 0.0.0.0/0.

- Options**
- *ipAddress*—IP address used as the local identity for IPSec security association negotiations
  - *ipRangeLow*—Low end of a range used as the local identity for IPSec security association negotiations
  - *ipRangeHigh*—High end of a range used as the local identity for IPSec security association negotiations
  - *netAddress*—IP network address used as the local identity for IPSec security association negotiations
  - *netMask*—IP network mask used as the local identity for IPSec security association negotiations

**Mode**    IPSec Tunnel Profile Configuration

## local ip network

---

**Syntax**    local ip network *ipNetwork ipMask*  
              no local ip network

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Specifies networks that are reachable through the IPSec tunnel. You can configure up to 16 networks for this method of “split-tunneling.” The **no** version removes the specified network from the reachable list.

**Options**

- *ipNetwork*—IP network reachable through the secure connection
- *ipMask*—IPv4 subnetwork mask for the IP network

**Mode**    IPSec Tunnel Profile Configuration

---

## log

---

**Syntax** [ no ] [ suspend ] log

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a IP policy rule that configures logging settings for packets that match the current classifier control list. The **no** version removes a log rule from a policy list; the **suspend** keyword temporarily suspends the rule; the **no suspend** version resumes application of a suspended rule.



.....  
**NOTE:** This command replaces the Policy List Configuration version of the **log** command, which may be removed completely in a future release.  
.....

**Mode** Classifier Group Configuration

**Related Documentation**

- Policy Rule Precedence

## log-adjacency-changes

---

**Syntax** For IS-IS adjacencies:

```
log-adjacency-changes [ severity { severityValue | severityNumber } ]  
[ verbosity verbosityLevel ]
```

```
no log-adjacency-changes
```

For OSPFv3 adjacencies:

```
[ no ] log-adjacency-changes [ severity { severityValue | severityNumber } ]  
[ verbosity verbosityLevel ]
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Generates a log message when the state of an IS-IS adjacency or an OSPFv3 neighbor changes. For OSPFv2 neighbors, use the `ospf log-adjacency-changes` command. Manipulates the same log as the Global Configuration **log** commands. The **no** version disables this function.

- Options**
- **severity**—Sets minimum severity of the log messages for this category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7. The lower the number, the higher the priority:
    - *emergency or 0*—System unusable
    - *alert or 1*—Immediate action needed
    - *critical or 2*—Critical condition exists
    - *error or 3*—Error condition
    - *warning or 4*—Warning condition
    - *notice or 5*—Normal but significant condition
    - *info or 6*—Informational message
    - *debug or 7*—Debug message
  - **verbosity**—Specifies the verbosity of this log category's messages
  - **verbosityLevel**—Specifies the verbosity of the log category's messages; can be any of the following:
    - *high*—Verbose
    - *low*—Terse
    - *medium*—Moderate detail

**Mode** Router Configuration

## log destination

**Syntax** To specify the destination and severity of messages logged:

```
log destination { console | nv-file | syslog ipAddress [ facility facilityId ] }
{ severity { severityValue | severityNumber } | off }
```

```
no log destination [ console | nv-file | syslog [ ipAddress ] ]
```

To specify which event categories are logged to syslog:

```
log destination syslog ipAddress { include | exclude } category [ category ]*
```

```
no log destination syslog ipAddress { include | exclude } [ category ]*
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the logging of system messages. You can direct messages to a destination, limit the messages logged based on severity level, or limit the event categories for which messages are logged. The **no** versions restore default settings or reverse the effect of previous commands that limited event categories.



**NOTE:** You can display traffic logs—such as `ipTraffic`, `icmpTraffic`, `tcpTraffic`, and `udpTraffic`—only via the `show log data` command or from the *SRP module* console. You cannot redirect traffic logs elsewhere, such as to a system log or nonvolatile storage file, or to a Telnet session.

- Options**
- **console**—Configures or modifies logging to the local console
  - **nv-file**—Configures or modifies logging to the nonvolatile log file; the nv-file can accept only events at a severity level of critical or higher in importance
  - **syslog**—Configures or modifies logging to a system log server
  - ***ipAddress***—IP address of the system log application on a remote host
  - **facility**—Specifies the system log facility on the host
  - ***facilityId***—Number in the range 0–7 that identifies the corresponding logging facility, local0–local7
  - **severity**—Sets minimum severity of the log messages displayed; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7. The lower the number, the higher the priority:
    - **emergency or 0**—System unusable
    - **alert or 1**—Immediate action needed
    - **critical or 2**—Critical condition exists
    - **error or 3**—Error condition

- *warning or 4*—Warning condition
- *notice or 5*—Normal but significant condition
- *info or 6*—Informational message
- *debug or 7*—Debug message
- *off*—Disables logging to this destination
- *include*—Sends only the specified event categories to the system log server
- *exclude*—Sends all event categories except those specified to the system log server

Issuing an **include** command after an **exclude** command (or vice versa) overrides the earlier command.

You can issue successive **include** commands or successive **exclude** commands. Successive commands expand the list of included or excluded categories.

- *category*—Log category; refer to the CLI online Help for available options
- *\**—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Global Configuration

## log destination syslog source

---

**Syntax**    log destination syslog *ipAddress* source *interfaceType interfaceSpecifier*  
              no log destination syslog *ipAddress* source [ *interfaceType interfaceSpecifier* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies a source interface type and location for events logged to a system log server. Overrides the type and location of the actual source to enable server access behind firewalls. The **no** version restores the default state, which is to use the actual interface type and location of the source.

**Options**

- *ipAddress*—IP address of the system log application
- *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Global Configuration

## log engineering

---

**Syntax** [ no ] log engineering

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables engineering logs. The **no** version disables engineering logs.

**Mode** Global Configuration



## log fields

---

**Syntax** log fields { timestamp | no-timestamp } { instance | no-instance }  
          { calling-task | no-calling-task }  
  
          no log fields

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Selects optional fields to be added to all logs. The **no** version disables the optional log fields.

- Options**
- timestamp—Includes the timestamp in log messages
  - no-timestamp—Does not include the timestamp in log messages
  - instance—Includes the event ID in log messages
  - no-instance—Does not include the event ID in log messages
  - calling-task—Includes the logging task name in log messages
  - no-calling-task—Does not include the logging task name in log messages

**Mode** Global Configuration

## log filters

---

**Syntax**    no log filters

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    This command has only a **no** version. See the no log filters command for a complete description.

**Mode**    Global Configuration

## log here

---

**Syntax** [ no ] log here

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the current terminal as a log console. The **no** version disables logs destined for a console from being displayed on the current terminal.

**Mode** Global Configuration, Privileged Exec, User Exec

## log severity

**Syntax** `log severity { severityValue | off | severityNumber }  
 [ eventCategory [ instanceTree ] | eventCategory instanceTree | eventCategory ]`

`no log severity [ severityValue | off | severityNumber ] [ eventCategory  
 [ filters | instanceTree ] | eventCategory { filters | instanceTree } | eventCategory | * ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the severity level for systemwide logs (that is, when no individual event category is specified) or for a specific event category. The **no** version returns severity changes to their default settings or the systemwide setting.



**NOTE:** After you change the log severity level for an individual log event category, you cannot use systemwide commands to subsequently change the severity level for that category. To change individually altered log event categories using systemwide commands, you must first change the log event back to its default setting.

- Options**
- *severityValue* and *severityNumber*—Minimum severity of the log messages displayed for the selected category; described either by a descriptive term—*severityValue*—or by a corresponding number—*severityNumber*—in the range 0–7. The lower the number, the higher the priority:
    - *emergency* or 0—System unusable
    - *alert* or 1—Immediate action needed
    - *critical* or 2—Critical condition exists
    - *error* or 3—Error condition
    - *warning* or 4—Warning condition
    - *notice* or 5—Normal but significant condition
    - *info* or 6—Informational message
    - *debug* or 7—Debug message
  - *off*—Disables systemwide log severity for all default level event categories when no event category is specified or disables log severity for a specified event category
  - *eventCategory*—Log category; refer to the CLI online Help for available options
  - *filters*—Removes all log filters for the event category

- *instanceTree*—Log-specific filter parameters; refer to the CLI online Help for available options
- \*—Resets all log severities, systemwide and individual, to default settings

**Mode**    Global Configuration

## log unlimited

---

**Syntax** [ no ] log unlimited [ *eventCategory* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Removes the limit on the number of outstanding buffers for an event category. The **no** version returns the number of buffers to the default value.

**Options** • *eventCategory*—Log category; refer to the CLI online Help for available options

**Mode** Global Configuration, Privileged Exec, User Exec

## log verbosity

---

**Syntax**    log verbosity *verbosityLevel* [ *eventCategory* ]  
              no log verbosity [ *verbosityLevel* ] [ *eventCategory* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the verbosity level for a selected category. The **no** version returns the log verbosity to the default value, low.

**Options**    • *verbosityLevel*—Verbosity for the log category:

- low—Terse (default)
- medium—Moderate detail
- high—Verbose

• *eventCategory*—Log category; refer to the CLI online Help for available options

**Mode**    Global Configuration

## login

---

**Syntax** [ no ] login

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Requires you to log in with a password. The **no** version removes the password requirement and allows connections without a password.



.....  
**NOTE:** If you issue this command when no password has been configured, access to Telnet is refused.  
.....

**Mode** Line Configuration



## login authentication

---

**Syntax** login authentication *authListName*

no login authentication

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Applies an AAA authentication list to the vty sessions that you specified for AAA authentication. The **no** version removes all authentication methods, which means the router accepts Telnet sessions without challenge.

**Options**

- *authListName*—Authentication list name of up to 32 characters

**Mode** Line Configuration

## logout subscribers

---

**Syntax**    logout subscribers { all | domain *domainName* | icr-partition *icrPartitionId* |  
port *interfaceSpecifier* | interface { lag } *interfaceLocation* | username *userName* |  
virtual-router *vrName* }

**Release Information**    Command introduced before JunosE Release 7.1.0.  
**icr-partition** keyword and *icrPartitionLocationId* variable added in JunosE Release 10.3.0  
**interface** and **lag** keywords and *interfaceLocation* variable added in JunosE Release 12.2.0

**Description**    Logs out the authenticated PPP or DHCP local server users. Also, logs out subscribers based on the ICR partition ID. There is no **no** version.

- Options**
- all—Logs out all PPP or DHCP local server sessions.
  - *domainName*—Active PPP or DHCP local server session whose usernames have that domain name.
  - icr-partition—Logs out subscribers based on the location ID of the partition in the ICR cluster.
  - *icrPartitionLocationId*—A unique identifier for each ICR partition on a chassis; a maximum of 128 characters. Note that this ID different from the partition ID, which is configured using the **ip vrrp vrid icr-partition partitionId** command. The partition location ID that you specify here is a combination of the interface within the chassis on which the ICR partition is configured and the VRRP ID, which is system-defined and nonconfigurable.
  - *interfaceSpecifier*—Location of the port with active PPP subscribers; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#).
  - lag—Displays subscribers based on the LAG interface
  - *interfaceLocation*—Location of the member interfaces in a LAG bundle for which subscribers that logged in to those interfaces are displayed; format varies according to interface type; see [“Interface Types and Specifiers” on page 5](#).
  - *userName*—Active PPP or DHCP local server session whose names match the username.
  - *vrName*—Active PPP or DHCP local server session whose interfaces are bound to a specific virtual router.

**Mode**    Privileged Exec

## loopback

**Syntax** For module controllers, the options available vary depending on the module being configured.

CT3 module:

loopback { local | network | payload }

no loopback

[ no ] loopback remote

cOCx/STMx SONET controller (SONET/SDH section layer), OCx/STMx line modules:

loopback { local | network }

no loopback

COCX-F3 module:

loopback { local | network | payload }

no loopback

For interfaces; the options available vary depending on the interface being configured.

ATM interface (cannot be used on a subinterface):

loopback { diagnostic | line }

no loopback

POS interface:

[ no ] loopback { internal | line }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the loopback mode for a module controller or interface. The **no** version clears all loopback on the module or interface (the default), or deletes the mapping to the user domain name.



**NOTE:** In Domain Map Configuration mode, this command has been replaced by the **local-interface** command and may be removed completely from Domain Map Configuration mode in a future release.

- Options**
- local—Loops the data back toward the router; on supported line modules also sends an alarm indication signal (AIS) out toward the network.
  - network payload—Loops the data toward the network after the framer has processed the data.
  - network line—Loops the data toward the network before the data reaches the framer.
  - remote—Sends a signal notifying the device at the remote end to activate or deactivate the line loopback.
  - network—Loops the data toward the network before the data reaches the framer.
  - payload—Loops the data toward the network after the framer has processed the data.
  - diagnostic—Places the interface into internal loopback
  - line—ATM interface: places the interface into external loopback; POS interface: connects the received network signal directly to the transmit network signal. When configured in line loopback mode, the router never receives data from the network.
  - internal—Connects the local transmitted signal to the local received signal

**Mode** Controller Configuration, Interface Configuration

## **`lsp-gen-interval`**

---

**Syntax** `lsp-gen-interval [ level-1 | level-2 ] seconds`  
`no lsp-gen-interval [ level-1 | level-2 ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Sets the minimum interval at which originated IS-IS link-state packets are generated on a per LSP basis. The **no** version restores the default value, 5 seconds.

**Options**

- `level-1`—Sets interval for level 1 only
- `level-2`—Sets interval for level 2 only
- `seconds`—Number in the range 0–120; the minimum interval in seconds; default value is 5 seconds

**Mode** Router Configuration

## **lsp-mtu**

---

**Syntax**    `lsp-mtu bytes`

`no lsp-mtu`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum size of an IS-IS link-state packet generated by the software. The **no** version restores the default value, 1497 bytes.

**Options**    • *bytes*—Number in the range 128–9180; the MTU size in bytes; default value is 1497

**Mode**    Router Configuration

## **`lsp-refresh-interval`**

---

**Syntax**    `lsp-refresh-interval` *seconds*  
             `no lsp-refresh-interval`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the link-state packet rate at which locally generated IS-IS link-state packets are periodically transmitted. The **no** version restores the default value, 900.

**Options**    • *seconds*—Number in the range 1–65535; the refresh interval in seconds; default value is 900

**Mode**    Router Configuration





## CHAPTER 13

# M Commands

macro

**Syntax** macro [ test | verbose ] { *fileName*.mac [ *macroName* [ *arg* ]\* ] |  
name *macroName* [ *arg* ]\* }

**Release Information** Command introduced before JunosE Release 7.1.0.

<b>Description</b>	Executes a macro file, which can consist of one or more macros. If you do not use the <i>macroName</i> option to specify a macro, the command searches in the specified macro file for a macro named “ start,” and returns an error if the “ start” macro is not found. If you do not specify <i>fileName</i> .mac, you must specify <b>name</b> <i>macroName</i> ; the command then searches only in local memory for a file called <i>macroName</i> .mac that contains the <i>macroName</i> macro. There is no <b>no</b> version.
--------------------	---

### Options

- **test**—Displays the output of the macro without issuing the commands to the router, and displays comments
- **verbose**—Echoes each command as the macro executes and displays comments
- **fileName**—Name of the file containing the macro; requires the .mac extension
- **macroName**—Name of a macro within the macro file
- **arg**—Zero or more arguments passed to the macro; if the argument contains a space or other special character, the argument must be enclosed within double quotation marks
- **\***—Indicates that one or more parameters can be repeated multiple times in a list in the command line

Mode All modes

## map-class frame-relay

---

**Syntax** [ no ] map-class frame-relay *mapName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a map class. Command is used when configuring Frame Relay end-to-end fragmentation and reassembly. The **no** version removes the map-class.

**Options** • *mapName*—Name of the map class; use up to 64 characters

**Mode** Global Configuration

## map-group

---

**Syntax** [ no ] map-group *name*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Associates a map list to an NBMA interface when configuring static mapping. The **no** version removes the association. Use in conjunction with the **map-list** command.

**Options** • *name*—Name of the map group

**Mode** Interface Configuration

## map-list

---

**Syntax** [ no ] map-list *name*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates a map list for an NBMA interface when configuring static mapping. The **no** version removes the map list. Use in conjunction with the **map-group** command.

**Options** • *name*—Name of the map list; a string of up to 31 characters

**Mode** Map List Configuration

## mark

**Syntax** For IPv4:

```
[ no ] [ suspend ] mark { tosByteValue mask maskValue |
tos-precedence tosPrecNum | tos tosNum | dsfield dsFieldNum }
profile colorMarkProfileName }
```

For IPv6:

```
[ no ] [ suspend ] mark { tcByteValue mask tcMaskValue | tc-precedence
tcPrecNum | tcfield tcFieldNum | dsfield dsFieldNum } profile
colorMarkProfileName }
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
*colorMarkProfileName* variable added in JunosE Release 7.2.0.

**Description** Sets the precedence field of the ToS byte (for IPv4) or traffic class byte (for IPv6) in the IP header to a specified value for packets that match the current classifier control list. This command is not tied to a rate limit profile, but marks packets based on a classifier control list. The **no** version removes the mark rule from the policy list; the **suspend** version temporarily suspends the mark rule; the **no suspend** version resumes application of a suspended rule.



**NOTE:** This command replaces the Policy List Configuration mode version of the **mark** command, which may be removed completely in a future release.

- Options**
- *tosByteValue*—ToS byte value to be assigned to packets; in the range 0–255
  - *maskValue*—Mask to be used when applying ToS byte values to packets; in the range 1–255
  - *tosPrecNum*—ToS precedence value to be assigned to packets; in the range 0–7
  - *tosNum*—ToS value to be assigned to packets; in the range 0–255
  - *dsFieldNum*—DS field value to be assigned to packets; in the range 0–63
  - *colorMarkProfileName*—Name of the color-mark profile (up to 40 alphanumeric characters)
  - *tcByteValue*—Traffic class field value to be assigned to packets; in the range 0–255
  - *tcMaskValue*—Mask to be used when applying traffic class field values to packets; in the range 1–255
  - *tcPrecNum*—Traffic class field precedence value to be assigned to packets; in the range 0–7
  - *tcFieldNum*—Traffic class field value to be assigned to packets; in the range 0–255

**Mode**   Classifier Group Configuration

**Related  
Documentation**   • Policy Rule Precedence

## mark-clp

---

**Syntax**    [ no ] [ suspend ] mark-clp *clpValue*

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Marks the CLP bit in the ATM header of packets matching the current classifier control list. The **no** version removes the mark rule from a policy list; the **suspend** version temporarily suspends a mark rule; the **no suspend** version resumes application of a suspended rule.

**Options**    • *clpValue*—Value of the CLP bit, 0 or 1

**Mode**    Classifier Group Configuration

**Related Documentation**    • Assigning Values to the ATM CLP Bit  
• Policy Rule Precedence



---

## mark-de

---

**Syntax** [ no ] [ suspend ] mark-de *deValue*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Marks the DE bit in the Frame Relay header of packets matching the current classifier control list. The **no** version removes the mark rule from a policy list; the **suspend** version temporarily suspends a mark rule; the **no suspend** version resumes application of a suspended rule.



**NOTE:** This command replaces the Policy List Configuration version of the **mark-de** command, which may be removed completely in a future release.

**Options** • *deValue*—Value of the DE bit; 0 or 1

**Mode** Classifier Group Configuration

**Related Documentation** • Assigning Values to the ATM CLP Bit  
• Policy Rule Precedence

## mark-exp

---

**Syntax** [ no ] [ suspend ] mark-exp *expValue* [ mask *expMask* ] [ profile *ProfileName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.  
*profileName* variable added in JunosE Release 7.2.0.

**Description** Defines an MPLS policy rule that specifies the value of the EXP bits. The **no** version removes the rule from the policy list; the **suspend** version temporarily suspends the policy rule; the **no suspend** version resumes application of a suspended rule.



.....  
**NOTE:** This command replaces the Policy List Configuration version of the **mark-exp** command, which may be removed completely in a future release.  
.....

- Options**
- *expValue*—EXP bit value assigned to packets; number in the range 0–7
  - *expMask*—Mask applied to modify some of the EXP bits in IP packet; integer in the range 1–7
  - *profileName*—Name of the rate-limit profile to be used in a policy (up to 40 alphanumeric characters)

**Mode** Classifier Group Configuration

- Related Documentation**
- Assigning Values to the ATM CLP Bit
  - Policy Rule Precedence

## mark-user-priority

---

**Syntax** [ no ] [ suspend ] mark-user-priority *userPriorityValue*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines a policy rule that specifies the value of the 802.1p VLAN user priority bits. The **no** version removes the rule from the policy list; the **suspend** version temporarily suspends the policy rule; the **no suspend** version resumes application of a suspended rule.



**NOTE:** This command replaces the Policy List Configuration version of the **mark-user-priority** command, which may be removed completely in a future release.

**Options** • *userPriorityValue*—EXP bit value assigned to packets; number in the range 0–7

**Mode** Classifier List Configuration

**Related Documentation** • Policy Rule Precedence

## mask destination

---

**Syntax**    mask destination *destinationMinimumSize*  
              no mask destination

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Sets the minimum mask size for the destination address for the prefix and destination prefix aggregation caches. The **no** version restores the default mask size.

**Options**    • *destinationMinimumSize*—Mask number in the range 1–32; default is 0

**Mode**    Flow Cache Configuration

## masked-key

---

**Syntax**    masked-key *encryptedKey*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the encrypted form of the preshared key that the router uses in IKE negotiations. Once you enter a preshared key, the router encrypts the key and displays it in masked form to increase the security of the key. If you need to reenter the key, you can enter it in its masked form using this command. There is no **no** version. To delete a key, use the **no** version of the **ipsec key manual** command.

**Options**

- *encryptedKey*—Encrypted key value; to obtain this value, enter the unencrypted key using the **key** command in IPSec Manual Key Configuration mode, and then display the masked version of the key with the **show configuration** command

**Mode**    IPSec Manual Key Configuration

## mask source

---

**Syntax**    `mask source sourceMinimumSize`

`no mask source`

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Sets the minimum mask size for the source address for the prefix and source prefix aggregation caches. The **no** version restores the default mask size.

**Options**    • *sourceMinimumSize*—Mask number in the range 1–32; default is 0

**Mode**    Flow Cache Configuration

---

## mask-val

---

<b>Syntax</b>	[ no ] mask-val <i>value</i>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0. Color Mark Profile Configuration mode added in JunosE Release 7.2.0.
<b>Description</b>	Sets the mask value. For rate limits, use this command with the <a href="#">committed-action</a> , <a href="#">conformed-action</a> , and <a href="#">exceeded-action</a> commands. For color-mark profiles, use the <b>mask-val</b> command in Color Mark Profile Configuration mode. The <b>no</b> version restores the default value, 255.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>value</i>—Mask value in the range 0–255. Use the following mask values to set the appropriate bits in the ToS field of the IP packet header:<ul style="list-style-type: none"><li>• IP Precedence—0xE0 (three most significant bits)</li><li>• DS Field—0xFC (six significant bits)</li><li>• TOS (IP) or Traffic Class field (IPv6)—0xFF (default)</li></ul></li></ul>
<b>Mode</b>	Color Mark Profile Configuration, Rate Limit Profile Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Creating a Two-Rate Rate-Limit Profile</a></li><li>• <a href="#">Setting the Mask Value for MPLS Rate-Limit Profiles</a></li><li>• <a href="#">Setting the Mask Value for IP and IPv6 Rate-Limit Profiles</a></li></ul>

## match as-path

---

**Syntax**    `match as-path listName [ listName ]*`  
              `no match as-path [ listName ]*`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches a BGP AS path access list. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

**Options**

- *listName*—Name of an AS path access list; string of up to 32 characters
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration



## match community

---

**Syntax**    match community *listName* [ *listName* ]\* [ exact-match ]  
              no match community [ *listName* ]\* [ exact-match ]

**Release Information**    Command introduced before JunosE Release 7.1.0.    match distance

**Description**    Matches a BGP community list. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

- Options**
- *listName*—String of up to 32 characters that designates a community list; you can optionally use a regular expression to specify the listName
  - exact-match—Limits the match to a route that contains only the communities contained in the specified list; cannot be used with a community list specified by a regular expression
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration

## match distance

---

**Syntax**    match distance *distance* [ *distance* ]\*  
              no match distance [ *distance* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches any routes that have the specified administrative distance. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.



.....  
**NOTE:** Matching a distance is useful only when applied to a route being redistributed out of a routing table. Distance is used to determine the relative preference between routes to the same prefix in order to pick the best route to that prefix in the routing table. Distance has no meaning in any other circumstance and any attempt to match distance will fail.  
.....

- Options**
- *distance*—Administrative distance in the range 0–255
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration

## match extcommunity

---

**Syntax**    match extcommunity *listName* [ *listName* ]\* [ exact-match ]  
              no match extcommunity [ *listName* ]\*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches a BGP extcommunity list. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

**Options**

- *listName*—Name of the extended-community list
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line
- exact-match—Limits the match to a route that contains only the extended communities contained in the specified list; cannot be used with an extended community list specified by a regular expression

**Mode**    Policy List Configuration, Route Map Configuration

## match ip address

---

**Syntax** match ip address { *accessListName* [ *accessListName* ]\* |  
prefix-list *prefixListName* [ *prefixListName* ]\* | prefix-tree *treeName* [ *treeName* ]\* }  
  
no match ip address [ *accessListName* ]\* | prefix-list [ *prefixListName* ]\* |  
prefix-tree [ *treeName* ]\*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Matches any routes that have a destination network number address that is permitted by a standard or extended access list, a prefix list, or a prefix tree, or performs policy routing on packets. You cannot mix references in the same match command; you can only specify either access list(s), prefix list(s), or prefix tree(s). The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

- Options**
- *accessListName*—String of up to 32 alphanumeric characters
  - *prefixListName*—Name of a single prefix list; string of up to 32 characters
  - *treeName*—Name of a single prefix tree; string of up to 32 characters
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Policy List Configuration, Route Map Configuration

## match ip next-hop

**Syntax** match ip next-hop { *accessListName* [ *accessListName* ]\* |  
 prefix-list *prefixListName* [ *prefixListName* ]\* | prefix-tree *treeName* [ *treeName* ]\* }  
 no match ip next-hop [ *accessListNumber* ]\* | prefix-list [ *listName* ]\* |  
 prefix-tree [ *treeName* ]\*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Matches any routes that have a next-hop router address passed by the specified access list, prefix list, or prefix tree. You cannot mix references in the same match command; you can only specify either access list(s), prefix list(s), or prefix tree(s). The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

**Options**

- *accessListName*—Name of a single standard access list; string of up to 32 characters
- *prefixListName*—Name of a single prefix list; string of up to 32 characters
- *treeName*—Name of a single prefix tree; string of up to 32 characters
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Policy List Configuration, Route Map Configuration

## match ipv6 address

---

**Syntax** match ipv6 address  
          { *accessListName* [ *accessListName* ]\* | prefix-list *prefixListName*  
          [ *prefixListName* ]\* }  
  
no match ipv6 address [ [ *accessListName* ]\* | prefix-list [ *prefixListName* ]\* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Matches any routes that have a destination network number address that is permitted by an access list or prefix list. The **no** version removes all address match clauses from a route map unless you specify either an access list or a prefix list, in which case only the list match is removed from the route map.

**Options**

- *accessListName*—String of up to 32 alphanumeric characters
- *prefixListName*—Name of a single prefix list; string of up to 32 characters
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Policy List Configuration, Route Map Configuration

## match ipv6 next-hop

---

**Syntax** match ipv6 next-hop  
{ *accessListName* [ *accessListName* ]\* | prefix-list *prefixListName*  
[ *prefixListName* ]\* }  
  
no match ipv6 next-hop [ [ *accessListName* ]\* | prefix-list [ *prefixListName* ]\* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Matches any routes that have a next-hop router address passed by the specified access list or prefix list. The **no** version removes all next-hop match clauses from a route map unless you specify either an access list or prefix list, in which case only the list match is removed from the route map.

**Options**

- *accessListName*—String of up to 32 alphanumeric characters
- *prefixListName*—Name of a single prefix list; string of up to 32 characters
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Policy List Configuration, Route Map Configuration

## match ipv6 route-source

---

**Syntax**    match ipv6 route-source *prefixListName* [ *prefixListName* ]\*  
              no match ipv6 route-source [ *prefixListName* ]\*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches any routes that are advertised from addresses contained in the specified prefix list. The **no** version removes all route-source match clauses from a route map unless you specify a prefix list, in which case only that prefix list match is removed from the route map.

**Options**    • *prefixListName*—Name of a single prefix list; string of up to 32 characters  
              • \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration



---

## match level

---

**Syntax**    match level { backbone | level-1 | level-1-2 | level-2 | stub-area }\*  
              no match level [ backbone | level-1 | level-1-2 | level-2 | stub-area ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches import routes for the specified type. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

**Options**

- backbone—Specifies OSPF backbone area
- level-1—Specifies Level 1 area
- level-1-2—Specifies Level 1 and a level 2 area
- level-2—Specifies Level 2 subdomain
- stub-area—Specifies OSPF NSSA area
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration

## match metric

---

**Syntax**    `match metric metricValue [ metricValue ]*`  
              `no match metric [ metricValue ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches a route for the specified metric value. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

- Options**
- *metricValue*—Number in the range 0–4294967295, which indicates the preference value for a specific route in a route map
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration

## match metric-type

---

**Syntax**    match metric-type { external | internal }  
              no match metric-type [ external | internal ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches routes having the specified metric type. The **no** version removes the match clause from a route map.

**Options**    • external—Specifies IS-IS external metric type  
              • internal—Specifies IS-IS internal metric type

**Mode**    Policy List Configuration, Route Map Configuration

## match mpls-label

---

**Syntax** [ no ] match mpls-label

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Matches on MPLS-labeled routes. By including this command in the appropriate route map (export, global export, global import route map), you can restrict importing or exporting to only labeled or only unlabeled routes. The **no** version removes the configuration.

**Mode** Route Map Configuration

## match policy-list

---

**Syntax**    match policy-list *listname* [ *listName* ]\*  
              no match policy-list [ *listName* ]\*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    References a policy list having the specified name. The **no** version removes the match clause from a route map.

**Options**    • *listName*—Name of a policy list; string of up to 32 characters  
              • \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Route Map Configuration

## match route-type

---

**Syntax** match route-type internal [ intra | inter ] [ level-1 | level-2 ]  
[ external [ type-1 | type-2 ] ] [ level-1 | level-2 ]\*

match route-type external [ type-1 | type-2 ] [ level-1 | level-2 ]  
[ internal [ intra | inter ] ] [ level-1 | level-2 ]\*

match route-type { level-1 | level-2 } [ internal [ intra | inter ] ]  
[ level-1 | level-2 ] [ external [ type-1 | type-2 ] ] [ level-1 | level-2 ]\*

match route-type { level-1 | level-2 } [ external [ type-1 | type-2 ] ]  
[ level-1 | level-2 ] [ internal [ intra | inter ] ] [ level-1 | level-2 ]\*

no match route-type [ internal [ intra | inter ] | external [ type-1 | type-2 ] |  
level-1 | level-2 ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Matches routes of the specified type. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

- Options**
- internal—Specifies internal routes
    - intra—OSPF intra-area routes
    - inter—OSPF interarea routes
  - external—Specifies external routes
    - type-1—OSPF type 1 external routes
    - type-2—OSPF type 2 external routes
  - level-1—Specifies IS-IS level 1 routes
  - level-2—Specifies IS-IS level 2 routes
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Policy List Configuration, Route Map Configuration

## match-set summary prefix-tree

---

**Syntax**    match-set summary prefix-tree *treeName*  
              no match-set summary prefix-tree

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets condition for a route map that matches routes based on the network base address set in the specified prefix tree and summarizes them by preserving only the bits set in the prefix tree. The **no** version disables the use of the prefix tree by the route map.

**Options**    • *treeName*—Name of the prefix tree

**Mode**    Route Map Configuration

## match tag

---

**Syntax**    `match tag tagValue [ tagValue ]*`  
              `no match tag [ tagValue ]*`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Matches the tag value of the destination routing protocol. The **no** version removes the match clause from a route map unless you specify a value, in which case only that value is removed from the match clause.

**Options**

- *tagValue*—Number in the range 0–4294967295
- \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Policy List Configuration, Route Map Configuration



## max aci-svs per-pvs

---

**Syntax** [ no] max aci-svs per-pvs *limitvalue*

**Release Information** Command introduced in JunosE Release 12.2.0.

**Description** Sets a limit on the number of ACI-based VLAN subinterfaces per S-VLAN. The **no** version restores the default limit.

**Options**

- *limitvalue*—Number of ACI-based VLAN subinterfaces per S-VLAN that can be configured in the range 1–16,383, with a default value of 16,383

**Mode** Interface Configuration

**Related Documentation**

- ACI-based VLAN Subinterfaces per S-VLAN Overview
- Configuring the Number of ACI-based VLAN Subinterfaces per S-VLAN

## max-branches

---

**Syntax** [ no ] max-branches *maxBranches*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the maximum number of branches the ANCP neighbor can have. The **no** version returns the maximum number of branches to its default value (unlimited branches).

**Options**

- *maxBranches*—Maximum number of branches allowed for the ANCP neighbor in the range 1–64000

**Mode** L2C Neighbor Configuration

## max-discovery-table-entries

---

**Syntax**    max-discovery-table-entries *maxEntries*  
              no max-discovery-table-entries

**Release Information**    Command introduced in JunosE Release 7.2.0.

**Description**    Specifies the maximum number of discovery table entries the ANCP neighbor can have. The **no** version returns the maximum number of table entries to its default value, 10,000 entries.

**Options**    • *maxEntries*—Maximum number of discovery table entries allowed for the ANCP neighbor in the range 1–64000

**Mode**    L2C Neighbor Configuration

## maximum-paths

---

**Syntax** For BGP:

maximum-paths [ ibgp | eibgp ] *maxPaths*

no maximum-paths [ ibgp | eibgp ] [ *maxPaths* ]

For IS-IS and RIP:

maximum-paths *maxPaths*

no maximum-paths

For OSPF:

maximum-paths *maxPaths*

no maximum-paths *maxPaths*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls the maximum number of equal-cost paths to the same destination that BGP, IS-IS, OSPF, or RIP can install in the routing table to support ECMP.

For BGP and RIP, issue the command from Router Configuration mode to apply the value to routes in the global RIB. In Address Family Configuration mode, issue the command only in the context of IPv4 unicast and IPv6 unicast address families to apply the value only to routes in the global RIB or the specific VRF for the IPv4 unicast or IPv6 unicast address family; This command is not supported for VPNv4 or VPNv6 address families.

For IS-IS or OSPF, issue the command from Router Configuration mode.

The **no** version restores the default value, 1 path for BGP or 4 paths for IS-IS, OSPF, and RIP.

- Options**
- **ibgp**—Specifies that the *maxPaths* value applies only to routes received from internal (IBGP) peers; if no keyword is specified, the *maxPaths* value applies only to routes received from external (EBGP) peers
  - **eibgp**—Specifies that the *maxPaths* value applies to routes received from IBGP and EBGP peers; can be used only for VRF IPv4 unicast and IPv6 unicast address families
  - ***maxPaths***—Maximum number of parallel paths (routes) in the range 1–16

**Mode** Address Family Configuration, Router Configuration

## maximum routes

---

**Syntax**    `maximum routes limit { warningThreshold | warning-only }`  
               `no maximum routes`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets a warning threshold and maximum limit for routes imported by a PE router into a VRF from associated CE routers. The **no** version removes the limit and warning threshold.

- Options**
- *limit*—Number in the range 1–4294967295 that when exceeded prevents routes from being imported into the routing table; when first exceeded generates a limit-exceeded log entry; if the route count fluctuates below and up to this value, an interval of five minutes must pass before another limit-exceeded log entry can be generated
  - *warningThreshold*—Percentage in the range 1–100 that when first exceeded generates a warning-threshold-exceeded log entry; if the route count fluctuates around this value, an interval of five minutes must pass before another warning-threshold-exceeded log entry can be generated
  - *warning-only*—Causes the *limit* to function as a *warningThreshold*; specifies that exceeding the *limit* generates a warning-threshold-exceeded log entry instead of a limit-exceeded log entry and permits routes exceeding the *limit* to be added to the routing table; if the route count fluctuates around the *limit*, an interval of five minutes must pass before another warning-threshold-exceeded log entry can be generated

**Mode**    VRF Configuration

## maximum-voql

---

**Syntax**    `maximum-voql maximumVoqlValue`  
`no maximum-voql`

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Specifies a maximum value for the virtual output queue length (VOQL) for all simple shared shapers on the router. The VOQL tracks the amount of data over queued between simple shared-shaper rate periods. The **no** version removes the specified maximum VOQL value from all simple shared shapers on the router.

**Options**

- *maximumVoqlValue*—Maximum value for the VOQL in the range 0–10000; default value is 4000

**Mode**    QoS Shared Shaper Control Configuration

**Related Documentation**

- [Configuring Simple Shared Shaper Algorithm Variables](#)

## max-interfaces

**Syntax** For Tunnel Server Configuration mode:

max-interfaces { *maxInterfacesValue* | all-available }

no max-interfaces

For IPSec Tunnel Profile Configuration mode:

max-interfaces *maxInterfacesValue*

no max-interfaces

**Release Information** Command introduced before JunosE Release 7.1.0.  
IPSec Tunnel Profile Configuration mode added in JunosE Release 7.3.0.

**Description** For Tunnel Server Configuration mode, provisions the maximum number of tunnel-service interfaces to be used on a tunnel-server port. The **default** version restores the default configuration. On dedicated tunnel-server ports, the default configuration is **all-available** (the maximum number of tunnel-service interfaces that the tunnel-service module supports). On shared tunnel-server ports, the default configuration is zero tunnel-service interfaces provisioned. The **no** version unprovisions the tunnel-server port by reducing the number of provisioned tunnel-service interfaces to zero.

For IPSec Tunnel Profile Configuration mode, defines the maximum number of interfaces that the IPSec tunnel profile can instantiate. The **no** version returns the maximum value to zero (0) to indicate no limit to the number of interfaces that can be instantiated on this profile.

- Options**
- *maxInterfacesValue*—For Tunnel Server configuration, the maximum number of tunnel-service interfaces that can be provisioned on a tunnel-server port in the range 0–16000; For IPSec Tunnel Profile configuration, the maximum number of interfaces that the IPSec tunnel profile can instantiate in the range 0–32767
  - all-available—Specifies that the maximum number of tunnel-service interfaces that can be provisioned on a tunnel-server port matches the maximum number supported by the tunnel-server module

**Mode** IPSec Tunnel Profile Configuration, Tunnel Server Configuration

## max-lsp-lifetime

---

**Syntax**    max-lsp-lifetime *seconds*  
              no max-lsp-lifetime

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum time that IS-IS link-state packets persist without being refreshed. The **no** version restores the default time.

**Options**    • *seconds*—Number in the range 1–65535; the lifetime of LSP in seconds; default value is 1200 seconds

**Mode**    Router Configuration



## max-response-failure

---

**Syntax** max-response-failure *maxFailureValue*

no max-response-failure

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Terminates a test when the *maxFailureValue* is reached. That is, when there is no response to a designated number of operation requests, the test is terminated. This feature applies only to pathEcho entries. The **no** version restores the default value, five consecutive failures.

**Options**

- *maxFailureValue*—Number of operation requests not responded to; 0 turns this feature off; default value is 5

**Mode** RTR Configuration

## max-sessions

**Syntax** For RADIUS:

`max-sessions sessionLimit`

`no max-sessions`

For AAA domain map and tunnel group tunnels:

`max-sessions maxSessionsPerTunnel`

`{ no | default } max-sessions`

For L2TP:

`max-sessions maxSessionsPerProfile`

`{ no | default } max-sessions`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** For RADIUS, specifies the number of outstanding requests to a server. The **no** version reverts to the default value.

For AAA domain map, and tunnel group tunnels, sets the maximum sessions per tunnel. The **no** version disables the feature. The **default** version sets the value to zero.

For L2TP, sets the maximum sessions allowed for destination and host profiles by the LNS. The **no** and **default** versions disable the feature.

**Options**

- *sessionLimit*—Maximum number of outstanding requests to a specific server in the range from 10 through to the maximum value; default value is 255

For information about the number of concurrent RADIUS requests that the router supports for authentication and accounting servers, see *JunosE Release Notes, Appendix A, System Maximums*.

- *maxSessionsPerTunnel*—Maximum number of sessions that can be configured on a tunnel in the range 0–4294967295; default value is zero
- *maxSessionsPerProfile*—Maximum number of sessions that can be established at the LNS for a destination or host profile; in the range from 1 through to a maximum of the chassis-wide limit; default value is the chassis-wide limit

For information about the maximum number of L2TP sessions supported per chassis, see *JunosE Release Notes, Appendix A, System Maximums*.

**Mode** Domain Map Tunnel Configuration, L2TP Destination Profile Configuration, L2TP Destination Profile Host Configuration, RADIUS Configuration, Tunnel Group Tunnel Configuration, L2TP Destination Profile Sessions Limit Configuration, L2TP Destination Profile Host Sessions Limit Configuration

## mdl carrier

---

**Syntax** [ no ] mdl carrier

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies that a T3 interface is used in the carrier environment. The **no** version restores the default situation, in which an interface does not operate in the carrier environment.

**Mode** Controller Configuration

## mdl string

---

**Syntax**    `mdl string { eic eicValue | fic ficValue | lic licValue | unit unitValue | pfi pfiCode |  
port portValue | generator genValue }`

`no mdl string { eic | fic | lic | unit | pfi | port | generator }`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Allows you to specify an MDL message on a T3 interface as defined in the ANSI T1.107a-1990 specification. The **no** version restores the default value to the specified MDL message or to all MDL messages.

- Options**
- *eicValue*—Equipment identification code; 1–10 characters; default value is the null value.
  - *ficValue*—Frame identification code; 1–10 characters; default value is the null value.
  - *licValue*—Line identification code; 1–11 characters; default value is the null value.
  - *unitValue*—Unit identification code; 1–6 characters; default value is the null value.
  - *pfiCode*—Facility identification code to send in the MDL path message; 1–38 characters; default value is the null value.
  - *portValue*—Equipment port number to send in the MDL idle signal message; 1–38 characters; default value is the null value.
  - *genValue*—Generator number to send in the MDL test signal message; 1–38 characters; default value is the null value.

**Mode**    Controller Configuration

## mdl transmit

---

**Syntax** [ no ] mdl transmit { path-id | idle-signal | test signal }  
no mdl transmit

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Transmits an MDL message from a T3 interface. The **no** version disables transmission of the specified MDL message or all MDL messages.

- Options**
- path-id—Transmits a path identification message every second; default value is disabled
  - idle-signal—Transmits an idle signal message every second; default value is disabled
  - test-signal—Transmits a test signal message every second; default value is disabled

**Mode** Controller Configuration

## mdt-data-delay

---

**Syntax**    mdt-data-delay *timeout*  
              no mdt-data-delay

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures a timeout before switching to data MDT. The **no** version returns to the default.

**Options**    • *timeout*—Timeout value measured in 0.1 seconds in the range 1-255 seconds; the default is 30

**Mode**    IP PIM Data MDT Configuration

## mdt-data-holddown

---

**Syntax**    mdt-data-holddown *timeout*  
              no mdt-data-holddown

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures the time in seconds before switching back to the default MDT group from the data MDT group. The **no** version returns to the default.

**Options**    • *timeout*—Time before switching back to the default MDT group, in the range 1–300 seconds; the default is 60

**Mode**    IP PIM Data MDT Configuration

## mdt-data-timeout

---

**Syntax**    mdt-data-timeout *timeout*  
              no mdt-data-timeout

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures the time in seconds before leaving the data MDT group. The **no** version returns to the default.

**Options**    • *timeout*—Time before leaving the data MDT group, in the range 1–1200 seconds; the default is 180

**Mode**    IP PIM Data MDT Configuration



## mdt-interval

---

**Syntax**    mdt-interval *time*  
              no mdt-interval

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures the time in seconds between successive MLD join TLVs. The **no** version returns to the default.

**Options**    • *time*—Time between successive MLD join TLV in the range 1–300 seconds; the default is 60

**Mode**    IP PIM Data MDT Configuration

## medium ipv4

---

**Syntax**    medium ipv4  
              no medium

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the medium type of a tunnel to IPv4 (the only medium type currently supported).  
                    The **no** version restores the default value, ipv4.

**Mode**    Domain Map Tunnel Configuration, Tunnel Group Tunnel Configuration

---

## member interface

---

<b>Syntax</b>	[ no ] member interface <i>interfaceType interfaceSpecifier</i>
<b>Release Information</b>	Command introduced before JunosE Release 7.1.0.
<b>Description</b>	Adds a member VLAN or S-VLAN subinterface to a Martini layer 2 circuit associated with a load-balancing group. This command creates an MPLS shim interface and associates it with the group. The <b>no</b> version removes the member subinterface from the circuit. Repeat as needed to remove all member subinterfaces used by a load-balanced circuit, thereby deleting the circuit from the group.
<b>Options</b>	<ul style="list-style-type: none"><li>• <i>interfaceType</i>—One of the following interface types listed in <a href="#">Interface Types and Specifiers on page 5</a><ul style="list-style-type: none"><li>• serial</li><li>• pos</li></ul></li><li>• <i>interfaceSpecifier</i>—Particular interface; format varies according to interface type; see <a href="#">Interface Types and Specifiers on page 5</a></li></ul>
<b>Mode</b>	L2 Transport Load-Balancing-Circuit Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• CE-Side Load Balancing for Martini Layer 2 Transport</li></ul>

## member-interface

---

**Syntax** [ no ] member-interface *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Adds a member interface, also known as a bundle member, to an MLPPP bundle, an MLFR bundle, or an IEEE 802.3ad link aggregation group (LAG) bundle. The **no** version removes the specified member interface from the bundle.

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - serial (MLFR bundle or MLPPP bundle)
    - pos (MLFR bundle only)
    - fastEthernet (IEEE 802.3ad LAG bundle only)
    - gigabitEthernet (IEEE 802.3ad LAG bundle only)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Interface Configuration, Subinterface Configuration

## member-interface-type

---

**Syntax**    member-interface-type {vlan | atm-vc | ip}  
              no member-interface-type

**Release Information**    Command introduced in JunosE Release 9.2.0.

**Description**    Configures the member-interface type for a QoS interface set. The **no** version removes the member-interface type from the parameter definition.

**Options**    • vlan—Specifies the member-interface-type as VLAN  
              • atm-vc—Specifies the member-interface-type as VLAN  
              • ip—Specifies the member-interface-type as VLAN

**Mode**    QoS Interface Set Configuration

**Related Documentation**    • Configuring Interface Sets for QoS

## memory

---

**Syntax** [ no ] memory warning *highUtilization* *abatedUtilization*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures memory warning parameters. When the router reaches the high memory utilization value, it sends warning messages. When memory usage falls to the abated memory utilization value, the router stops sending warning messages. The **no** version returns the memory warning parameters to the default values.

- Options**
- *highUtilization*—High memory utilization value; in the range 1–99; default value is 85
  - *abatedUtilization*—Abated memory utilization value; in the range 1–99; default value is 75

**Mode** Global Configuration

## message-digest-key md5

**Syntax**    message-digest-key *keyID* md5 [ 0 | 8 ] *msgDigestKey*  
               no message-digest-key *keyID*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables OSPF MD5 authentication for the remote-neighbor interface and configures the MD5 key. The **no** version deletes an MD5 key.



**NOTE:** If all the MD5 keys have been deleted, the authentication type is still MD5, but you need to configure MD5 keys.

To disable MD5 authentication for the remote-neighbor interface, use the **authentication-none** command.

- Options**
- *keyID*—Key identifier in the range 1–255
  - md5—Specifies use of the MD5 algorithm
  - 0—Indicates the *msgDigestKey* is entered in unencrypted form (plaintext); this is the default option
  - 8—Indicates the *msgDigestKey* is entered in encrypted form (ciphertext)
  - *msgDigestKey*—OSPF password; string of up to 16 alphanumeric characters

**Mode**    Remote Neighbor Configuration

## metric

---

**Syntax**    `metric globalDefault [ level-1 | level-2 ]`  
`no metric [ level-1 | level-2 ]`

**Release Information**    Command introduced in JunosE Release 9.0.0.

**Description**    Sets the metric to the same value for all active IS-IS IPv4 and IPv6 interfaces at the specified level. If you do not specify level 1 routers or level 2 routers, then the metric is applied to both level 1 and level 2 routers. The **no** version restores the individual default value, 10.

- Options**
- *globalDefault*—Metric used for all IS-IS interfaces; a number in the range 1–16777215; overridden by the **isis metric** command
  - level-1—Configuration applies only to level 1 routing
  - level-2—Configuration applies only to level 2 routing

**Mode**    Router Configuration



## metric-style narrow

---

**Syntax** [ no ] metric-style narrow [ transition ] [ level-1 | level-2 | level-1-2 ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the router to generate and accept only old-style IS-IS TLVs with narrow (six-bit) metric fields. If you issue this command, the value configured with the **isis metric** command can range only from 0–63. The **no** version restores the default value, which is to generate and accept only old-style TLVs with narrow (six-bit) metric fields.

- Options**
- **transition**—Configures the router to additionally accept new-style TLVs with wider metric fields
  - **level-1**—Configuration applies only to level 1 routing
  - **level-2**—Configuration applies only to level 2 routing
  - **level-1-2**—Configuration applies to both level 1 and level 2 routing

**Mode** Router Configuration

## metric-style transition

---

**Syntax** [ no ] metric-style transition [ level-1 | level-2 | level-1-2 ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the router to generate and accept both old-style IS-IS TLVs with narrow (six-bit) metric fields and new-style IS-IS TLVs with wider metric fields. If you issue this command, the value configured with the **isis metric** command can range from 0–16777215. The **no** version restores the default value, which is to generate and accept only old-style TLVs with narrow (six-bit) metric fields.

- Options**
- level-1—Configuration applies only to level 1 routing
  - level-2—Configuration applies only to level 2 routing
  - level-1-2—Configuration applies to both level 1 and level 2 routing

**Mode** Router Configuration

---

## metric-style wide

---

**Syntax** [ no ] metric-style wide [ transition ] [ level-1 | level-2 | level-1-2 ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the router to generate and accept only new-style IS-IS TLVs with wider metric fields. If you issue this command, the value configured with the **isis metric** command can range from 0–16777215. The **no** version restores the default value, which is to generate and accept only old-style TLVs with narrow (six-bit) metric fields.

- Options**
- **transition**—Configures the router to additionally accept old-style TLVs with narrow (six-bit) metric fields
  - **level-1**—Configuration applies only to level 1 routing
  - **level-2**—Configuration applies only to level 2 routing
  - **level-1-2**—Configuration applies to both level 1 and level 2 routing

**Mode** Router Configuration

## minimum-dynamic-rate-percent

---

**Syntax**    minimum-dynamic-rate-percent *minimumDynamicRatePercent*  
              no minimum-dynamic-rate-percent

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Specifies the minimum value of the dynamic shaping rate as a percentage of the shared shaping rate for all simple shared shapers on the router. The **no** version removes the specified minimum dynamic rate from all simple shared shapers on the router.

**Options**    • *minimumDynamicRatePercent*—Minimum percentage value of the dynamic shared shaper in the range 0–100; default value is 0

**Mode**    QoS Shared Shaper Control Configuration

**Related Documentation**    • Configuring Simple Shared Shaper Algorithm Variables

---

## minimum-links

---

**Syntax**    minimum-links *minimumLinkValue*

no minimum-links

**Release Information**    Command introduced in JunosE Release 10.0.0.

**Description**    Configures the minimum number of member links in the link aggregation group (LAG) bundle that must be in the Collecting/Distributing state for the LAG interface to be considered up. The minimum number of member links that you can configure depends on the IOA. For example, for ES2–S1 GE-4 IOA, the number of minimum links is in the range 0–4. For ES2–S1 GE-8 IOA, the number of minimum links is in the range 0–8 and for ES2–S3 GE-20 IOA, the number of minimum links is in the range 0–8. The **no** version resets the minimum number of member links to the default value.

**Options**

- *minimumLinkValue*—Minimum number of links in the LAG bundle in the range 1-8 (8 is the maximum number of member links per LAG bundle); default value is 1

**Mode**    Interface Configuration

**Related Documentation**

- Understanding 802.3ad Ethernet Link Aggregation
- Configuring 802.3ad Link Aggregation

## mirror

**Syntax** To mirror a specified trigger type:

```
mirror triggerType [hex] triggerValue { ip | ipv6 | l2tp } secure-policy-list policyName
```

```
no mirror triggerType [hex] triggerValue { ip | ipv6 | l2tp }
```

To mirror the agent-circuit-id or agent-remote-id trigger types, when the hex variant is used:

```
mirror triggerType hex triggerValue { ip | ipv6 | l2tp } secure-policy-list policyName
```

```
no mirror triggerType hex triggerValue { ip | ipv6 | l2tp }
```

To mirror the dhcp-option-82 trigger type:

```
mirror dhcp-option-82 agent-circuit-id triggerValue1 agent-remote-id triggerValue2 ip  
secure-policy-list policyName
```

```
no mirror dhcp-option-82 agent-circuit-id triggerValue1 agent-remote-id triggerValue2  
ip
```

To mirror the dhcp-option-82 trigger type, when the hex variant is used:

```
mirror dhcp-option-82 hex triggerValue ip secure-policy-list policyName
```

```
no mirror dhcp-option-82 hex triggerValue ip
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**nas-port-id** keyword added in JunosE Release 7.1.0.  
 IPv6 support added in JunosE Release 10.1.0.  
**hex** keyword added in JunosE Release 11.1.0.

**Description** Enables packet mirroring based on the specified trigger and specifies the secure policy to attach to the subscriber's interface. The **no** version disables packet mirroring for the subscriber and removes the trigger configuration.



**NOTE:** The hex variant is applicable only for agent-circuit-id, agent-remote-id, and dhcp-option-82 trigger types. If the hex variant is used then the *triggerValue* must be a hexadecimal number.

- Options**
- *triggerType*—One of the following RADIUS attributes
    - acct-session-id—Acct-Session-Id, RADIUS attribute [44]
    - agent-circuit-id—Agent Circuit ID, RADIUS attribute [26–1], Vendor ID 3561
    - agent-remote-id—Agent Remote ID, RADIUS attribute [26–2], Vendor ID 3561

- `calling-station-id`—Calling-Station-Id, RADIUS attribute [31]
- `dhcp-option-82`—DHCP Option 82, RADIUS attribute [26–159], Vendor ID 4874
- `ip-address`—Framed-IP-Address, RADIUS attribute [8]; associated with the virtual router where the command is issued, RADIUS VSA [26-1]
- `nas-port-id`—NAS-Port-Id, RADIUS attribute [87]
- `username`—User-Name, RADIUS attribute [1]; associated with the virtual router where the command is issued, RADIUS VSA [26-1]
- *triggerValue*—Value of the *triggerType* (the specified RADIUS attribute) that identifies the subscriber
- `ip`—Configures mirroring for an IP subscriber
- `ipv6`—Configures mirroring for an IPv6 subscriber
- `l2tp`—Configures mirroring for an L2TP subscriber
- *policyName*—Secure policy to attach to the subscriber's interface

**Mode**      Global Configuration

**Related Documentation**      • Configuring CLI-Based Mirroring

## mirror analyzer-ip-address

---

**Syntax** mirror analyzer-ip-address *analyzerIpAddress* analyzer-virtual-router *vrName*  
[ analyzer-udp-port *udpPort* [ mirror-identifier *mirrorId*  
[ session-identifier *sessionId* ] ] ]  
  
no mirror

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the mirror action for a classifier group in a secure IP or L2TP policy list. The **no** version deletes the mirror rule.

- Options**
- *analyzerIpAddress*—IP address of the analyzer
  - *vrName*—Name of the virtual router where the analyzer interface is configured
  - *udpPort*—UDP port of the analyzer; required for L2TP packet mirror rules
  - *mirrorId*—Mirror identifier
  - *sessionId*—Session identifier

**Mode** Classifier-Group Configuration

**Related Documentation**

- Configuring CLI-Based Mirroring



## mirror disable

**Syntax** To disable mirroring for a specified trigger type:

```
mirror disable triggerType [hex] triggerValue
```

To disable mirroring for the agent-circuit-id or agent-remote-id trigger types, when the hex variant is used:

```
mirror disable triggerType hex triggerValue
```

To disable mirroring for the dhcp-option-82 trigger type:

```
mirror disable dhcp-option-82 agent-circuit-id triggerValue1 agent-remote-id triggerValue2
```

To disable mirroring for the dhcp-option-82 trigger type, when the hex variant is used:

```
mirror disable dhcp-option-82 hex triggerValue
```

**Release Information** Command introduced before JunosE Release 7.1.0.  
**nas-port-id** added in JunosE Release 7.1.0.  
**hex** keyword added in JunosE Release 11.1.0.

**Description** Disables a packet mirroring session that was dynamically configured for a subscriber; uses the trigger information to identify the subscriber's session. There is no **no** version.



**NOTE:** The hex variant is applicable only for agent-circuit-id, agent-remote-id, and dhcp-option-82 trigger types. If the hex variant is used then the *triggerValue* must be a hexadecimal number.

- Options**
- *triggerType*—One of the following RADIUS attributes that was used as the trigger to start the packet mirroring session
    - acct-session-id—Acct-Session-Id, RADIUS attribute [44]
    - agent-circuit-id—Agent Circuit ID, RADIUS attribute [26–1], Vendor ID 3561
    - agent-remote-id—Agent Remote ID, RADIUS attribute [26–2], Vendor ID 3561
    - calling-station-id—Calling-Station-Id, RADIUS attribute [31]
    - dhcp-option-82—DHCP Option 82, RADIUS attribute [26–159], Vendor ID 4874
    - ip-address—Framed-IP-Address, RADIUS attribute [8]; associated with the virtual router where the command is issued, RADIUS VSA [26–1]
    - nas-port-id—NAS-Port-Id, RADIUS attribute [87]
    - username—User-Name, RADIUS attribute [1]; associated with the virtual router where the command is issued, RADIUS VSA [26–1]

- **triggerValue**—Value of the *triggerType* (the specified RADIUS attribute) that identifies the subscriber

**Mode** Privileged Exec

**Related Documentation**

- [Configuring CLI-Based Mirroring](#)
- [Configuring RADIUS-Based Mirroring](#)

## mirror-enable

---

**Syntax** [ no ] mirror-enable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the use of the secure packet mirroring commands. The secure commands are then visible and can be used during the current CLI session. The **no** version disables the use of packet mirroring commands; the commands no longer appear in the CLI.

**Mode** Privileged Exec

**Related Documentation**

- [Configuring CLI-Based Mirroring](#)

## mirror trap-enable

---

**Syntax** [ no ] mirror trap-enable

**Release Information** Command introduced in JunosE Release 7.2.0.

**Description** Configures the packet mirroring application to generate secure packet mirroring traps. The **no** version disables the trap generation.

**Mode** Global Configuration

**Related Documentation**

- [Monitoring SNMP Secure Packet Mirroring Traps](#)

## mld disable

---

**Syntax** [ no ] mld disable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Disables MLD on a virtual router. The **no** version reenables MLD on a virtual router.

**Mode** Router Configuration

## mode

---

**Syntax**    mode { file-system-synchronization | high-availability [ slot *primarySlotNum* *secondarySlotNum* ] }

no mode [ high-availability [ slot *primarySlotNum* *secondarySlotNum* ] ]

**Release Information**    Command introduced before JunosE Release 7.1.0.  
**slot** keyword and *primarySlotNum* and *secondarySlotNum* variables added in JunosE Release 11.3.0.

**Description**    Enables high availability mode (hitless SRP switchover) operation. The **no** version without optional keywords returns high availability mode operation to its default (file-system-synchronization).

When used with the **slot** keyword, enables stateful line module switchover on a router and configures a line module pair in a 1:1 high availability mode. The **no** version with the **slot** keyword deactivates high availability for line modules, which is the default behavior.

- Options**
- file-system-synchronization—Uses file synchronization to keep the configuration of the standby SRP coordinated with the configuration of the active SRP
  - high-availability—Uses mirroring to keep the configuration and state of the standby SRP coordinated with the configuration and state of the active SRP or line module
  - *primarySlotNum*—Number of the slot in which the line module configured as the primary in a high availability pair resides in the router; for the E120 router, a number in the range 0–5; for the E320 router, a number in the range 0–5 or 11–16
  - *secondarySlotNum*—Number of the slot in which the line module configured as the secondary in a high availability pair resides in the router; for the E120 router, a number in the range 0–5; for the E320 router, a number in the range 0–5 or 11–16

**Mode**    Redundancy Configuration

---

## monitor atm vc

---

**Syntax**    `monitor atm vc atm interfaceSpecifier vcd [ atm interfaceSpecifier vcd ]*`  
              `[ load-interval seconds ] [ display-time-of-day ]`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Displays bit rate and packet rate statistics over a specified time interval for one or more ATM virtual circuits (VCs). There is no **no** version.

- Options**
- *interfaceSpecifier*—ATM interface specifier; see [Interface Types and Specifiers on page 5](#)
  - *vcd*—Virtual circuit descriptor that is an identifier for the VC in other commands; number in the range 1–2147483647
  - *seconds*—Number of seconds in the range 5–30 that specifies the time interval at which the router calculates bit rates and packet rates for the specified VC; default value is 5 seconds
  - *display-time-of-day*—Sets time at which the router calculates the bit rate and packet rate statistics for the current interval
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Privileged Exec, User Exec

## monitor atm vp

---

**Syntax**    monitor atm vp atm *interfaceSpecifier vpi* [ atm *interfaceSpecifier vpi* ]\*  
              [ load-interval *seconds* ] [ display-time-of-day ]

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Displays bit rate and packet rate statistics over a specified time interval for one or more ATM virtual paths (VPs). There is no **no** version.

- Options**
- *interfaceSpecifier*—ATM interface specifier; see [Interface Types and Specifiers on page 5](#)
  - *vpi*—Virtual path identifier of the PVC. The numeric range of the VPI depends on the line module capabilities and current configuration.
  - *seconds*—Number of seconds in the range 5–300 that specifies the time interval at which the router calculates bit rates and packet rates for the specified VP; default value is 5 seconds
  - display-time-of-day—Sets time at which the router calculates the bit rate and packet rate statistics for the current interval
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode**    Privileged Exec, User Exec



## monitor vlan interface

**Syntax** monitor vlan interface *interfaceType interfaceSpecifier*  
 [ *interfaceType interfaceSpecifier* ]\* [ load-interval *seconds* ] [ display-time-of-day ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Displays bit rate and packet rate statistics over a specified time interval for one or more VLAN subinterfaces. There is no **no** version.

- Options**
- *interfaceType*—One of the following interface types listed in [Interface Types and Specifiers on page 5](#)
    - atm
    - fastEthernet
    - gigabitEthernet
    - lag
    - tenGigabitEthernet
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *seconds*—Number of seconds in the range 5–30 that specifies the time interval at which the router calculates bit rates and packet rates for the specified VLAN; default value is 5 seconds
  - display-time-of-day—Sets time at which the router calculates the bit rate and packet rate statistics for the current interval
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Privileged Exec, User Exec

## more

---

**Syntax** To display a file that resides in NVS on the primary SRP module:

`more fileName`

To display a file that resides in NVS on the redundant (standby) SRP module:

`more standby:fileName`

To display a file that resides on a remote server:

`more serverName:filePathName`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Displays the contents of a macro, script, or text file. The file can reside in NVS on the primary SRP module, in NVS on the redundant (standby) SRP module, or on a remote server that you access using FTP. There is no **no** version.

- Options**
- *fileName*—Name of the file you want to display
  - *serverName*—Name of the remote server on which the file resides
  - *filePathName*—Complete path of the file on the remote server

**Mode** Privileged Exec

## motd-banner

---

**Syntax** [ no | default ] motd-banner

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls display of a message-of-the-day banner (configured with the **banner** command) on a particular line when a connection is initiated. The **no** version disables the motd banner on the line; the motd banner is also disabled by the **no exec-banner** command. The **default** version restores the default setting, in which the banner is enabled on all lines.

**Mode** Line Configuration

## mount

---

**Syntax**    mount { disk0 | disk1 }  
              no mount { disk0 | disk1 } [ force ]

**Release Information**    Command introduced in JunosE Release 8.0.0.

**Description**    Mounts the specified flash card. If the card was not safely unmounted previously, the command also performs disk and file system integrity checks before mounting the card and permitting user access. The **no** version prepares the card for safe unmounting by rejecting requests to open files and waiting for currently open files to close; only then is the user notified that the unmounted card can be safely ejected.

**Options**

- disk0—Specifies flash card in slot 0 of the SRP module; although this option is displayed by the CLI, it is rejected when specified because disk0 is required for router operation
- disk1—Specifies flash card in slot 1 of the SRP module; supported only on the E120 router and the E320 router
- force—Forces the dismount even when files on the disk are open for modification

**Mode**    Privileged Exec

## mpls

**Syntax** To enable MPLS on a virtual router in Global Configuration mode, or to create an MPLS major interface in Interface Configuration mode:

```
[ no ] mpls
```

To modify the subscriber policy for MPLS packets in Subscriber Policy Configuration mode:

```
mpls { permit | deny }
```

```
no mpls
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** In Global Configuration mode, creates MPLS in the current virtual router. By default, MPLS does not exist in a VR. The **no mpls** version removes MPLS from the VR, and additionally removes all MPLS major interfaces, MPLS shim interfaces, MPLS load-balancing groups, MPLS minor interfaces, and MPLS forwarding tables from the VR.

In Interface Configuration mode, creates an MPLS major interface stacked on the current layer 2 interface, and automatically enables MPLS in the current VR if it has not already been enabled. If the MPLS major interface already exists, no action is taken and no message is generated. An error message is generated if you issue the command for a layer 2 interface that does not support MPLS major interfaces. You cannot enable MPLS on a loopback interface. The **no mpls** version removes the MPLS major interface.

In Subscriber Policy Configuration mode, modifies the subscriber policy for MPLS to define whether the subscriber (client) interfaces that belong to a bridge group or to a VPLS instance forward (permit) or filter (deny) MPLS packets. The **no** version restores the default value, permit MPLS packets.

In Subscriber Policy Configuration mode, you cannot change the default subscriber policy values for trunk (server) interfaces that belong to a bridge group or to a VPLS instance. You also cannot change the default subscriber policy values for a VPLS virtual core interface, which acts as a trunk interface. The VPLS virtual core interface represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices.



**NOTE:** MPLS does not exist by default and must be created, either explicitly with this command, or implicitly with another **mpls** configuration command. If you create MPLS implicitly, for example by issuing the command **mpls lsp retries 10**, MPLS remains disabled until you enable it, by issuing the **mpls** command.

**Options**

- **permit**—Specifies that the subscriber interface associated with the bridge group or VPLS instance forwards MPLS packets

- deny—Specifies that the subscriber interface associated with the bridge group or VPLS instance filters MPLS packets

**Mode** Global Configuration, Interface Configuration, Subscriber Policy Configuration

**Related Documentation**

- [Configuring MPLS LSPs for VPWS](#)
- [Configuring MPLS LSPs for VPLS](#)

## **mpls atm vci range**

---

**Syntax**    mpls atm vci range *minVCI maxVCI*  
              no mpls atm vci range

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the range for virtual circuit identifiers that can be used in MPLS labels for an MPLS major interface on an ATM AAL5 interface using the interface label space. Creates the MPLS major interface if it does not yet exist. An error message is generated if you issue the command for any other layer 2 interface, as they do not support the interface label space. The **no** version deletes the range.

**Options**    • *minVCI*—Lowest virtual circuit identifier acceptable for a label, a value from 33–65535  
              • *maxVCI*—Highest virtual circuit identifier acceptable for a label, a value from 33–65535

**Mode**    Interface Configuration

## **mpls atm vpi range**

---

**Syntax**    mpls atm vpi range *minVPI maxVPI*

no mpls atm vpi range

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the range for virtual path identifiers that can be used in MPLS labels for an MPLS major interface on an ATM AAL5 interface using the interface label space. Creates the MPLS major interface if it does not yet exist. An error message is generated if you issue the command for any other layer 2 interface, as they do not support the interface label space. The **no** version deletes the range.

**Options**

- *minVPI*—Lowest virtual path identifier acceptable for a label, a value in the range 0–255
- *maxVPI*—Highest virtual path identifier acceptable for a label, a value in the range 0–255

**Mode**    Interface Configuration



## mpls backup-path

---

**Syntax** [ no ] mpls [ traffic-eng ] backup-path *bypassTunnelName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns the specified bypass tunnel to the interface that you want to protect. The **no** version removes the assignment.

- Options**
- **traffic-eng**—Specifies optional keyword for compatibility with non-E Series implementations
  - *bypassTunnelName*—Name of the bypass tunnel

**Mode** Interface Configuration

## mpls bandwidth

---

**Syntax** { ip rsvp | mpls } bandwidth *bandwidth*  
no { ip rsvp | mpls } bandwidth

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies the total bandwidth reservable for MPLS on the interface. The **no** version restores the default value, 0.

- Options**
- ip rsvp—Specifies keyword for compatibility with non-E Series implementations of MPLS
  - mpls—Specifies JunosE MPLS implementation
  - *bandwidth*—Reservable bandwidth in kilobits per second, a value in the range 1–10000000

**Mode** Interface Configuration

## mpls classifier-list

**Syntax** mpls classifier-list *classifierName*  
 [ traffic-class *className* ] [ color { green | yellow | red } ]  
 [ user-packet-class *userPacketClassValue* ] [ exp-bits *expValue* ]  
 [ exp-mask *maskValue* ]  
  
 no mpls classifier-list *classifierName* [ *classifierNumber* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or modifies an MPLS classifier control list. The **no** version deletes the MPLS classifier control list.

- Options**
- *classifierName*—Name of a classifier list entry
  - *className*—Name of a traffic class; the router supports up to eight traffic classes
  - green—Matches packet color to green, indicating a low drop preference
  - yellow—Matches packet color to yellow, indicating a medium drop preference
  - red—Matches packet color to red, indicating a high drop preference
  - *userPacketClassValue*—Value of the user packet class in the range 0–15
  - *expValue*—Value of the EXP bits in the range 0–7
  - *maskValue*—Mask applied to the EXP bits in the range 1–7
  - *classifierNumber*—Index of the classifier control list entry to be deleted; an integer in the range 1–10000

**Mode** Global Configuration

**Related Documentation**

- Creating or Modifying Classifier Control Lists for MPLS Policy Lists

## mpls copy-upc-to-exp

---

**Syntax** [ no ] mpls copy-upc-to-exp

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Sets the initial value of the EXP bits in pushed or swapped labels to the user packet class value associated with the packets. This command does not modify EXP bits in labels already in the received MPLS packet. The **no** version restores the default condition, where the EXP bits are set to 000 (for non-MPLS/IP traffic) or to the IP precedence value from the TOS field of the IP packet header (for IP traffic).

**Mode** Global Configuration

## mpls create-dynamic-interfaces

**Syntax**    mpls create-dynamic-interfaces  
               { ip | ipv6 } on-major-interfaces [ for-vpn-traffic ] [ profile *profileName* ]

no mpls create-dynamic-interfaces  
               { ip | ipv6 } on-major-interfaces [ for-vpn-traffic ]

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Specifies whether dynamic IP interfaces are automatically created on top of all MPLS major interfaces, and if so, which profile is used to create them. By default, one IPv4 dynamic interface without a profile is created and used for both VPN and non-VPN traffic. If IPv6 is enabled on the virtual router, then by default, one IPv6 dynamic interface without a profile is created and used for both VPN and non-VPN traffic. The **no** version restores the default behavior.

- Options**
- **ip**—Specifies that the created dynamic interfaces are IPv4
  - **ipv6**—Specifies that the created dynamic interfaces are IPv6
  - **for-vpn-traffic**—Specifies that the created dynamic interface is used for BGP/MPLS VPN traffic; VPN traffic uses the same IP interface as non-VPN traffic if separate IP interfaces are not created for the VPN traffic
  - ***profileName***—Name of a profile that sets the values that configure the IP interface; if you do not specify a profile, the interface attributes are set to their default values

**Mode**    Global Configuration

## mpls diff-serv phb-id traffic-class

---

**Syntax**    mpls diff-serv phb-id { private *privateId* | standard *standardId* }  
              traffic-class *className* [ color { green | yellow | red } ]  
  
              no mpls diff-serv phb-id { private *privateId* | standard *standardId* }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Maps the specified PHB ID to the internal traffic class and color combination. If color is specified, the PHB ID can be used only for E-LSPs. If color is *not* specified, the PHB ID can be used only for L-LSPs. The **no** version removes the mapping.

- Options**
- *privateId*—Number in the range 0–4032 designating the private PHB identifier
  - *standardId*—Number in the range 0–63 designating the standard PHB identifier using the DSCP bits
  - *className*—Name of a traffic class; the router supports up to eight traffic classes
  - green—Sets packet color to green, indicating a low drop preference
  - yellow—Sets packet color to yellow, indicating a medium drop preference
  - red—Sets packet color to red, indicating a high drop preference

**Mode**    Global Configuration

## mpls disable

---

**Syntax** [ no ] mpls disable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Administratively disables the MPLS major interface. MPLS major interfaces are administratively enabled by default. The **no** version restores the default condition, and creates an MPLS major interface if it does not already exist.

**Mode** Interface Configuration

## mpls explicit-path

---

**Syntax** { ip | mpls } explicit-path { name *name* | identifier *number* } [ enable | disable ]  
no { ip | mpls } explicit-path { name *name* | identifier *number* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Defines an explicit path by name or ID number and also enables or disables the explicit path. The **no** version deletes the explicit path.

- Options**
- ip—Specifies alternative keyword for compatibility with non-E Series implementations
  - mpls—Specifies JunosE MPLS implementation
  - *name*—Name for the explicit path; string of up to 20 characters
  - *number*—Number identifying the explicit path in the range 1–65535
  - enable—Reenables the explicit path that was previously disabled on the virtual router; to prevent a partially configured explicit path from being used, do not enable it until you have finished configuring or modifying the path
  - disable—Disables the explicit path that was previously enabled on the virtual router

**Mode** Global Configuration



---

## mpls ip propagate-ttl

---

**Syntax** [ no | default ] mpls ip propagate-ttl [ forwarded | local ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls the value for the TTL field in the MPLS header at the tunnel ingress when a label is assigned to an IP packet. Enabled by default, this command sets the TTL to the TTL value from the IP packet header.

The **no** version sets the value to 255 to hide the network structure from all traffic, preventing the **traceroute** command from discovering and displaying LSP hops. The **no** version changes the TTL processing model from the default uniform model to the pipe model.

The **default** version reverts to the global default, causing the TTL field to be copied from the IP packet header and enabling the **traceroute** command to show all the hops in the network.

- Options**
- **forwarded**—Reveals the network structure to traceroute for forwarded packets; when used with the **no** version, hides the network structure from traceroute only for local packets, enabling you to hide the structure of the MPLS network from your customers, and sets the tunnel model to pipe for forwarded packets
  - **local**—Reveals the network structure to traceroute for local packets; when used with the **no** version, hides the network structure from traceroute only for local packets, sets the tunnel model to pipe for locally originated packets, and sets the tunnel model to pipe for locally originated packets

**Mode** Global Configuration

## mpls l2transport load-balancing-group

**Syntax** `mpls l2transport load-balancing-group groupNumber`  
`[ mpls-relay remoteIpAddress | route interface tunnel lspName ]`  
`[ vc-id ] vcIdValue [ group-id groupIdValue ]`  
`[ control-word | no-control-word ] [ sequencing | no-sequencing ]`  
`[ relay-format { ethernet | ppp | vlan } ]`

`no mpls l2transport load-balancing-group groupNumber`  
`{ mpls-relay remoteIpAddress | route interface tunnel lspName } [ vc-id ] vcId`

**Release Information** Command introduced before JunosE Release 7.1.0.  
**control-word**, **no-control-word**, **sequencing**, and **no-sequencing** keywords added in JunosE Release 7.1.0.

**Description** Specifies a Martini layer 2 transport circuit, associates it with a load-balancing group, and accesses L2 Transport Load-Balancing-Circuit Configuration mode. The **no** version removes a circuit from the load-balancing group and all subinterfaces that the circuit was configured on.



**NOTE:** Using the **mpls-relay** keywords has the same effect as using the **mpls-relay** command. Using the **route interface** keywords has the same effect as using the **route interface** commands. The **relay-format frame-relay** option is not supported for the **mpls l2transport load-balancing-group** command.

- Options**
- *groupNumber*—Integer in the range 1–127
  - *remoteIpAddress*—IP address of the router on the remote end of the layer 2 circuit
  - *lspName*—Name of the route interface tunnel
  - *vcIdValue*—Integer in the range 1–4294967295 that identifies the virtual connection; the two ends across the MPLS core must match inside each VC type
  - *groupIdValue*—Integer in the range 0–4294967295 that identifies a group of virtual connections; not currently used
  - **control-word**—Indicates that the local preference is to use the control word for the layer 2 packets encapsulated in MPLS packets sent to the remote PE router. The default preference is determined by the interface stack on which the MPLS interface is stacked.
  - **no-control-word**—Indicates that the local preference is to not use the control word for the layer 2 packets encapsulated in MPLS packets sent to the remote PE router. The default preference is determined by the interface stack on which the MPLS interface is stacked.
  - **sequencing**—Specifies that the local preference is to include nonzero sequence numbers with the control word; enabling the remote PE to detect out-of-order packets; has no effect if no control word is sent in the packets. The router always accepts zero sequence

numbers and checks the order of nonzero sequence numbers of MPLS packets received from the remote PE; any out of order packets are dropped, regardless of whether sequencing is configured.

- **no-sequencing**—Specifies that the sequencing number in the control word is set to zero, instructing the remote PE router to not attempt to detect out-of-order packets; has no effect if no control word is sent in the packets.
- **relay-format ethernet**—Specifies that the router uses Ethernet signaling and encapsulation, which causes the VLAN interface to appear as an Ethernet interface to the other side of the connection; enables a VLAN interface on one side of an MPLS tunnel to communicate with an Ethernet or a bridged Ethernet interface on the other side of an MPLS tunnel. The VLAN tag is not included in the MPLS encapsulation. This option is not available on serial or POS interfaces for HDLC layer 2 circuits. It is available only on VLAN interfaces
- **relay-format frame-relay**—Specifies that the router uses legacy (pre-RFC 4619) Frame Relay pseudowire type value for signaling and encapsulation. Enables a router running JunosE Software that supports the pseudowire type value defined in RFC 4619, Encapsulation methods for transport of Frame Relay over MPLS Networks, to interoperate with a router that uses the legacy (pre-RFC 4619) pseudowire type value. This option is available on serial or POS interfaces for Frame Relay layer 2 circuits. It is not supported on E120 and E320 routers.
- **relay-format ppp**—Specifies that the router uses VC-type PPP signaling and PPP encapsulation instead of VC-type HDLC signaling and HDLC encapsulation. The router uses VC-type HDLC signaling and HDLC encapsulation by default. This option is available only on serial and POS interfaces for HDLC layer 2 circuits.
- **relay-format vlan**—Specifies that the router uses VLAN signaling and encapsulation. This option is not available on serial or POS interfaces for HDLC layer 2 circuits. It is available for VLAN interfaces.

**Mode**    Global Configuration

**Related Documentation**    • CE-Side Load Balancing for Martini Layer 2 Transport

## mpls ldp

---

**Syntax**    [ no ] mpls ldp

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables LDP and topology-driven LSP, as does any LDP-related command, using an implicit default profile. You cannot enable LDP and topology-driven LSPs on a loopback interface. The **no** version disables LDP globally or on the interface.

**Mode**    Global Configuration, Interface Configuration, Subinterface Configuration

**Related Documentation**

- [Configuring MPLS LSPs for VPWS](#)
- [Configuring MPLS LSPs for VPLS](#)

## mpls ldp advertise-labels

**Syntax** `mpls ldp advertise-labels { host-only | for routeAccessList [ to neighborAccessList ] | interface interfaceType interfaceSpecifier }`

`no mpls ldp advertise-labels { policy-list | host-only | for routeAccessList [ to neighborAccessList ] | interface interfaceType interfaceSpecifier }`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Controls the distribution of incoming labels advertised by LDP. The **no** version halts advertisement of all incoming labels or the specified labels.

- Options**
- **host-only**—Advertises only labels for host routes (routes with a 32-bit mask)
  - ***routeAccessList***—Name of access list identifying routes for which label advertisement is permitted or denied
  - ***neighborAccessList***—Name of access list identifying neighbors to which the LSR advertises labels
  - ***interfaceType***—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - ***interfaceSpecifier***—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - **policy-list**—Deletes all lists configured with the **for *routeAccessList*** option

**Mode** Global Configuration

## mpls ldp autoconfig

---

**Syntax** From Interface Configuration mode and Subinterface Configuration mode:

```
[ no ] mpls ldp { isis | ospf } autoconfig
```

From Router Configuration mode for IS-IS:

```
mpls ldp autoconfig [ level-1 | level-2 | level-1-2 ]
```

```
no mpls ldp autoconfig
```

From Router Configuration mode for OSPF:

```
mpls ldp autoconfig [ areald | arealdInt ]
```

```
no mpls ldp autoconfig
```

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** In Interface Configuration mode, creates LDP on the current interface. The **no** version removes LDP from the interface.

In Router Configuration mode, creates LDP on all interfaces in the IS-IS or OSPF router, on interfaces in the specified level (IS-IS), or on interfaces in the specified area (OSPF). The **no** version removes the LDP configuration for all qualifying interfaces.

- Options**
- level-1—Enables LDP on all IS-IS level 1 interfaces
  - level-1-2—Enables LDP on all IS-IS level 1-2 interfaces
  - level-2—Enables LDP on all IS-IS level-2-only interfaces
  - areald—OSPF area ID in IP address format
  - arealdInt—OSPF area ID as a decimal value in the range 0–4294967295

**Mode** Interface Configuration, Router Configuration, Subinterface Configuration

## mpls ldp deaggregate

---

**Syntax** [ no ] mpls ldp deaggregate

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Configures LDP to bind each prefix to a separate label on the current virtual router. The **no** version enables LDP to aggregate multiple prefixes to be bound to the same label.

**Mode** Global Configuration

## mpls ldp disable

---

**Syntax** [ no ] mpls ldp disable

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Disables LDP on the interface. The **no** version reenables LDP on the interface.

**Mode** Interface Configuration



## mpls ldp discovery transport-address

---

**Syntax**    mpls ldp discovery transport-address *ipAddress*  
              no mpls ldp discovery transport-address

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies an arbitrary IP address to be used as the transport address of the local peer advertised in LDP discovery hello messages for interfaces that use the platform label space. The peer router uses the transport address to establish the session TCP connection. By default, the router ID is advertised as the transport address. The **no** version restores the default transport address, the LSR router ID.

**Options**    • *ipAddress*—IP address advertised as the transport address

**Mode**    Router Configuration

## mpls ldp egress-label

---

**Syntax**    mpls ldp egress-label { explicit-null | non-null }  
              no mpls ldp egress-label

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Configures LDP to advertise the explicit null label (label 0) or a non-null label for the LSR that is the egress router for the prefix. This command takes effect immediately. The **no** version restores the default, where the egress router advertises the implicit null label (label 3), which causes the router's upstream neighbor to perform a penultimate hop pop.

**Mode**    Global Configuration

## mpls ldp graceful-restart

---

**Syntax**    mpls ldp graceful-restart [ helper ]  
              no mpls ldp graceful-restart

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables LDP graceful restart to preserve MPLS forwarding state across a restart, and helper mode, or only helper mode. LDP graceful restart and helper mode are both disabled by default. The **no** version disables both LDP graceful restart and helper mode.

Graceful restart causes the fault tolerant session TLV to be included in LDP initialization messages with a nonzero value for the reconnect timeout. This action announces to neighbors that the router preserves its forwarding state cross a restart.

Helper mode causes the fault tolerant session TLV to be included in LDP initialization messages. The reconnect timeout value in the TLV is zero when LDP graceful restart is disabled. This TLV announces to neighbors that the router preserves any label-FEC mapping it has received from a neighbor in the event that the neighbor performs an LDP graceful restart.

**Options**    • helper—Configures only helper mode to preserve label-FEC mappings from a neighbor in the event the neighbor gracefully restarts

**Mode**    Global Configuration

## **mpls ldp graceful-restart reconnect-time**

---

**Syntax**    mpls ldp graceful-restart reconnect-time [ *seconds* ]

             no mpls ldp graceful-restart reconnect-time

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Specifies the length of time you want neighbors to wait for the gracefully restarting router to resume sending LDP messages to neighbors after the restart. The **no** version restores the default value, 140 seconds.

**Options**    • *seconds*—Number of seconds in the range 60–300

**Mode**    Global Configuration

## **mpls ldp graceful-restart recovery-time**

---

**Syntax**    mpls ldp graceful-restart recovery-time [ *seconds* ]  
              no mpls ldp graceful-restart recovery-time

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Specifies the length of time the router retains its MPLS forwarding state across a restart. The **no** version restores the default value, 120 seconds.

**Options**    • *seconds*—Number of seconds in the range 120–600

**Mode**    Global Configuration

## **mpls ldp graceful-restart timers max-recovery**

---

**Syntax**    mpls ldp graceful-restart timers max-recovery *seconds*  
              no mpls ldp graceful-restart timers max-recovery

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Specifies the maximum length of time that the router waits for its neighbor to complete a graceful LDP restart after the LDP session is reestablished. The **no** version restores the default value, 120 seconds.

**Options**    • *seconds*—Number of seconds in the range 15–600

**Mode**    Global Configuration

## mpls ldp graceful-restart timers neighbor-liveness

**Syntax**    mpls ldp graceful-restart timers neighbor-liveness *seconds*  
              no mpls ldp graceful-restart timers neighbor-liveness

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Specifies the maximum length of time that the router waits for its neighbor to reestablish an LDP session. The **no** version restores the default value, 120 seconds.

**Options**    • *seconds*—Number of seconds in the range 5–300

**Mode**    Global Configuration

## mpls ldp igp sync holddown

---

**Syntax**    mpls ldp igp sync holddown *holdDownValue*  
              no mpls ldp ldp igp sync holddown

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Configures the LDP-IGP synchronization holddown timer. The **no** version restores the default condition, where the IGP waits for LDP to be operational on the interface indefinitely.

**Options**    • *holdDownValue*—Number of milliseconds in the range 1–65535

**Mode**    Global Configuration



## mpls ldp independent-control

---

**Syntax** [ no ] mpls ldp independent-control

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Specifies independent control as the method used by LDP for label distribution. This command takes effect immediately. The **no** version restores the default method, ordered control.

**Mode** Global Configuration

## mpls ldp ip-forwarding

---

**Syntax** [ no ] mpls ldp ip-forwarding { access-list | prefix-list } *listName* host-only

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Specifies LSPs to be put into the IP routing table for forwarding plain IP traffic. The **no** version removes the listed LSPs or all LSPs from the IP routing table.



.....  
**NOTE:** This command replaces the deprecated **mpls topology-driven-lsp ip-interfaces** command.  
.....

- Options**
- **access-list**—Specifies that *listName* is an access list
  - **prefix-list**—Specifies that *listName* is a prefix list
  - ***listName***—Name of access list or prefix list that specifies LSPs over which IP interfaces are created
  - **host-only**—Specifies that IP interfaces are created only over LSPs to host addresses

**Mode** Global Configuration

## mpls ldp link-hello disable

---

**Syntax** [ no ] mpls ldp link-hello disable

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Suppresses the transmission of LDP link hello messages. This command requires the use of targeted hello messages to form LDP peer adjacencies. The **no** version restores the default condition, where the LSR sends multicast link hello messages.

**Mode** Interface Configuration

## mpls ldp neighbor password

---

**Syntax**    mpls ldp neighbor *ipAddress* password *passwordString*

              [ no ] mpls ldp neighbor *ipAddress* password

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the password used to compute MD5 checksums for authenticating the specified LDP neighbor when the peer attempts to establish a TCP connection. The **no** version deletes the password for the peer.

- Options**
- *ipAddress*—IP address of remote peer
  - *passwordString*—Password; alphanumeric string in the range 1–40 characters

**Mode**    Global Configuration

## mpls ldp profile

**Syntax** In Global Configuration mode:

```
mpls ldp [ interface ] profile [ profileName ]
```

```
no mpls ldp interface profile profileName
```

In Interface Configuration mode:

```
mpls ldp profile profileName
```

```
no mpls ldp profile
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** In Global Configuration mode, creates or modifies a configuration profile for LDP. Places the CLI in LDP Configuration mode. The implicit default LDP profile specifies a value of 0 for hello hold-time; this value signifies 15 seconds for link hellos and 45 seconds for targeted hello messages.

Any change to a profile affects all interfaces that use the profile; changes are effective the next time the interface comes up.

In Interface Configuration mode, creates or enables LDP on the interface with the factory default profile or the specified profile. The **no** version reverts to the default profile on the interface.

In both modes, if you specify a profile not previously configured, it is created with the factory default settings. If you do not specify a profile name, the factory default profile is assumed. The **no** version deletes the specified profile.

- Options**
- *interface*—Keyword required for the **no** version in Global Configuration mode
  - *profileName*—Name of a profile to be created or modified (Global Configuration mode), applied to an interface (Interface Configuration mode), or deleted (both modes); the profile sets the values for the protocol parameters; until you modify the profile settings, the values match those of the implicit default profile

**Mode** Global Configuration, Interface Configuration

## mpls ldp redistribute

---

**Syntax**    `mpls ldp redistribute protocol [ route-map mapName ]`  
              `no mpls ldp redistribute protocol [ route-map mapName ]`

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables redistribution of routes from the specified IGP to LDP, enabling LDP to advertise labeled BGP routes for the inter-AS option C two-stack scenario. The **no** version halts redistribution from the specified IGP or according to the specified route map.

You can specify a route map to redistribute more specific routes to LDP. Only routes that pass the maps clauses are redistributed. If you do not use a route map for fine-grained control of route distribution, and you do not want to redistribute BGP routes, then you do not need to issue this command.

For backward compatibility, if you do not issue this command, LDP continues to advertise labels for IGP routes—including connected, static, IS-IS, OSPF, and RIP routes, but excluding BGP routes. That is, IGP routes other than BGP are redistributed to LDP by default.

- Options**
- *protocol*—Protocol from which routes are redistributed to LDP: BGP, connected, IS-IS, OSPF, RIP, or static
  - *mapName*—Name of the route map used to redistribute more specific routing information from an IGP to LDP

**Mode**    Global Configuration

## mpls ldp session holdtime

---

**Syntax**    `mpls ldp session holdtime holdTime`  
`no mpls ldp session holdtime`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures the LDP session hold time, the period that an LSR maintains a session without receipt of a message from an LDP peer. Each LSR peer sends the session hold time in its initialization message; peers negotiate to use the minimum of the session hold times proposed by the pair of LSRs. This negotiated session hold time is used by the keepalive timer to maintain the session.

The keepalive timer is reset with the receipt of any session message from the peer. In the absence of other LDP protocol messages are being sent, peers periodically send a keepalive message to maintain the LDP session.

The LDP session is terminated when the timer expires. The **no** version restores the default value, 180.

**Options**    • *holdTime*—Number of seconds in the range 15–65535

**Mode**    Global Configuration

## mpls ldp session keepalive interval

---

**Syntax**    mpls ldp session keepalive interval *seconds*  
              no mpls ldp session keepalive interval

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Sets the transmission interval at which LDP sends session keepalive messages to maintain the LDP session. Keepalive messages are sent to LDP peers at this interval in the absence of any other LDP traffic over the session. This command takes effect immediately. The **no** version restores the default interval, 20 seconds.

**Options**    • *seconds*—Number of seconds, in the range 1–65535

**Mode**    Global Configuration



## mpls ldp session retries

---

**Syntax**    mpls ldp session retries *retryNum*  
              no mpls ldp session retries

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of attempts that will be made to set up an LDP session. The **no** version restores the default value, 0, meaning that the attempts will be made until successful.

**Options**    • *retryNum*—Number of attempts in the range 0–65535

**Mode**    Global Configuration

## mpls ldp session retry-time

---

**Syntax**    mpls ldp session retry-time *retryTime*  
              no mpls ldp session retry-time

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval in seconds between attempts to set up an LDP session. The **no** version restores the default value, 30 seconds.

**Options**    • *retryTime*—Interval in the range 0–60

**Mode**    Global Configuration

## mpls ldp strict-security

---

**Syntax** [ no ] mpls ldp strict-security

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures strict LDP authentication mode, which enables sessions to be formed only by peers with configured passwords. The **no** version enables sessions to be formed by peers without configured passwords.

**Mode** Global Configuration

## mpls ldp sync

---

**Syntax** From Interface Configuration mode and Subinterface Configuration mode:

```
[ no ] mpls ldp { isis | ospf } sync
```

From Router Configuration mode for IS-IS:

```
mpls ldp sync [ level-1 | level-2 | level-1-2 ]
```

```
no mpls ldp sync
```

From Router Configuration mode for OSPF:

```
mpls ldp sync [ areald | arealdInt ]
```

```
no mpls ldp sync
```

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** In Interface Configuration mode, synchronizes LDP with the IGP on the current interface. The **no** version removes the configuration for the interface.

In Router Configuration mode, synchronizes LDP with the IGP on all of the protocol's interfaces, on all interfaces in the specified level (IS-IS), or on all interfaces in the specified area (OSPF). The **no** version removes the configuration for all qualifying interfaces.

By default, LDP synchronization is not configured.

LDP—IGP synchronization must be configured on both sides of a link to be effective and avoid asymmetric link costs. In addition, LDP-IGP synchronization is effective only when alternate links with adequate bandwidth are available in the network.

- Options**
- **level-1**—Enables synchronization with LDP on all IS-IS level 1 interfaces
  - **level-1-2**—Enables synchronization with LDP on all IS-IS level 1-2 interfaces
  - **level-2**—Enables synchronization with LDP on all IS-IS level-2-only interfaces
  - ***areald***—OSPF area ID in IP address format
  - ***arealdInt***—OSPF area ID as a decimal value in the range 1–4294967295

**Mode** Interface Configuration, Router Configuration, Subinterface Configuration

## mpls ldp targeted-hello holdtime

---

**Syntax**    mpls ldp targeted-hello holdtime *seconds*  
              no mpls ldp targeted-hello holdtime

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Configures the LDP targeted-hello hold time, the period for which a sending LSR maintains a record of targeted hello messages from the receiving LSR without receipt of another targeted hello message from that LSR. Each LSR peer sends the hold time in its targeted hello messages; peers negotiate to use the minimum of the hold times proposed by the pair of LSRs.

The hold timer is restarted whenever the LSR receives a targeted hello from the peer in the targeted hello adjacency. The timer expires if no targeted hello is received from the peer within the hold time. The LSR deletes the targeted hello adjacency when the timer expires. If all targeted hello adjacencies are deleted for an LDP session, then the LSR terminates the LDP session.

This command takes effect immediately. The **no** version restores the default value, 45 seconds.

**Options**    • *seconds*—Number of seconds, in the range 1–65535

**Mode**    Global Configuration

## mpls ldp targeted-hello interval

---

**Syntax**    mpls ldp targeted-hello interval *seconds*  
              no mpls ldp targeted-hello interval

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Configures the the interval between targeted hello packets sent by LDP. This command takes effect immediately. The **no** version restores the default value, 15 seconds.

**Options**    • *seconds*—Number of seconds, in the range 1–65535

**Mode**    Global Configuration

## mpls ldp targeted-hello receive list

**Syntax** [ no ] mpls ldp targeted-hello receive list  
 { access-list *accessListName* | *ipAddress* [ *ipAddress* ]\* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the list of peer addresses from which MPLS accepts targeted hello messages. When you configure a receive list, hello messages are accepted only from list members. If no list is configured, hello messages are accepted from all addresses. The **no** version removes the list of peer addresses.



**NOTE:** This command is unnecessary if you configure the **mpls ldp targeted-hello send list** command.

- Options**
- *accessListName*—String of up to 32 alphanumeric characters that identifies an access list
  - *ipAddress*—IP address of a peer
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration

## **mpls ldp targeted-hello send list**

---

**Syntax** [ no ] mpls ldp targeted-hello send list  
{ access-list *accessListName* | *ipAddress* [ *ipAddress* ]\* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Configures the list of peer addresses to which MPLS sends targeted hello messages and from which MPLS accepts targeted hello messages. The **no** version removes the list of peer addresses.

- Options**
- *accessListName*—String of up to 32 alphanumeric characters that identifies an access list
  - *ipAddress*—IP address of a peer
  - \*—Indicates that one or more parameters can be repeated multiple times in a list in the command line

**Mode** Global Configuration



## mpls ldp vpls neighbor

**Syntax** [ no ] mpls ldp vpls *vplsName* neighbor *ipAddress*

**Release Information** Command introduced in JunosE Release 8.2.0.

**Description** Configures the remote VPLS edge (VE) device address of a neighbor in the VPLS domain in which the VPLS instance participates. The specified VPLS instance must use LDP as the signaling protocol. If either or both LDP or MPLS are not configured on the current virtual router, issuing this command creates the LDP and MPLS configurations automatically. The **no** version deletes the neighbor from the VPLS domain.

The **mpls ldp vpls neighbor** command is not valid for a VPLS instance that uses BGP as the signaling protocol. To configure a VPLS instance with BGP signaling, use the **bridge vpls rd**, **bridge vpls route-target**, **bridge vpls site-name site-id**, and **bridge vpls site-range** commands.

- Options**
- *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command
  - *ipAddress*—IP address of a neighbor in the VPLS domain

**Mode** Global Configuration

**Related Documentation**

- Configuring MPLS LSPs for VPLS

## **mpls ldp vpls vpls-id**

---

**Syntax**    `mpls ldp vpls vplsName vpls-id vplsId`  
`no mpls ldp vpls vplsName vpls-id`

**Release Information**    Command introduced in JunosE Release 8.2.0.

**Description**    Configures the globally unique VPLS identifier of a VPLS instance that uses LDP as the signaling protocol. All VEs that participate in the same VPLS domain must use the same VPLS identifier. The VPLS identifier configured for a VPLS instance must not be the same as the PWid for Martini configurations for Ethernet layer 2 services over MPLS. The **no** version deletes the VPLS identifier from the VPLS instance.

The **mpls ldp vpls vpls-id** command is not valid for a VPLS instance that uses BGP as the signaling protocol. To configure a VPLS instance with BGP signaling, use the **bridge vpls rd**, **bridge vpls route-target**, **bridge vpls site-name site-id**, and **bridge vpls site-range** commands.

- Options**
- *vplsName*—Name of a VPLS instance created with the **bridge vpls transport-virtual-router** command
  - *vplsId*—VPLS identifier for the VPLS instance, in the range 1–4294967295

**Mode**    Global Configuration

**Related Documentation**

- Configuring MPLS LSPs for VPLS

## mpls lsp no-route retries

---

**Syntax**    mpls lsp no-route retries *retryNum*  
              no mpls lsp no-route retries

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of attempts that will be made to set up an LSP for RSVP-TE after a failure due to no available route. The **no** version restores the default value, 0, which means the attempts will be made until successful.

**Options**    • *retryNum*—Number of retry attempts in the range 0–65535

**Mode**    Global Configuration

## mpls lsp no-route retry-time

---

**Syntax**    mpls lsp no-route retry-time *retryTime*  
              no mpls lsp no-route retry-time

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval in seconds between attempts to set up an LSP for RSVP-TE after a failure due to no available route. The **no** version restores the default value, 5 seconds.

**Options**    • *retryTime*—Interval in the range 1–60

**Mode**    Global Configuration

## mpls lsp retries

---

**Syntax**    mpls lsp retries *retryNum*  
              no mpls lsp retries

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the number of attempts that will be made to set up an LSP for RSVP-TE after a failure other than one due to no available route. The **no** version restores the default value, 0, which means the attempts will be made until successful.

**Options**    • *retryNum*—Number of retry attempts in the range 0–65535

**Mode**    Global Configuration

## mpls lsp retry-time

---

**Syntax**    mpls lsp retry-time *retryTime*  
              no mpls lsp retry-time

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval in seconds between attempts to set up an LSP for RSVP-TE after a failure other than one due to no available route. The **no** version restores the default value, 5 seconds.

**Options**    • *retryTime*—Interval in the range 1–60

**Mode**    Global Configuration

**Syntax** mpls match exp-bits *bitValue* set traffic-class *className* color { green | yellow | red }

no mpls match exp-bits *bitValue*

**Release Information** Command introduced before JunosE Release 7.1.0.

<b>Description</b>	Sets the traffic class and color for incoming MPLS packets whose EXP bits in the MPLS shim header match the specified EXP bits value. The <b>no</b> version reverts to the default behavior for traffic matching the specified EXP bits value, setting neither traffic class nor color.
--------------------	---

- Options**
- *bitValue*—Value in the range 0–7 that matches the corresponding binary value (000–111) for the three EXP bits
  - *className*—Name of a traffic class; the router supports up to eight traffic classes
  - *green*—Sets packet color to green, indicating a low drop preference
  - *yellow*—Sets packet color to yellow, indicating a medium drop preference
  - *red*—Sets packet color to red, indicating a high drop preference

**Mode** Global Configuration

## mpls match traffic-class

---

**Syntax**    mpls match traffic-class *className* color { green | yellow | red } set exp-bits *bitValue*  
              no mpls match traffic-class *className* color { green | yellow | red }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the EXP bits in the MPLS shim header of outgoing MPLS packets that match the specified combination of traffic class and color. The **no** version reverts to the default behavior for traffic matching the specified traffic class and color combination. The default behavior sets the EXP bits to 000 for traffic entering an LSP and has no effect on the EXP bits for transit traffic.

**Options**

- *className*—Name of a traffic class; the router supports up to eight traffic classes
- green—Sets packet color to green, indicating a low drop preference
- yellow—Sets packet color to yellow, indicating a medium drop preference
- red—Sets packet color to red, indicating a high drop preference
- *bitValue*—Value in the range 0–7 that sets the corresponding binary value (000–111) for the three EXP bits

**Mode**    Global Configuration



## mpls policy

**Syntax** `mpls policy { input | output } policyName`  
`[ statistics { enabled [ baseline { enabled | disabled } ] [ preserve | merge ] |`  
`disabled [ merge ] } ] merge ]`  
  
`no mpls policy { input | output } [ policyName ]`

**Release Information** Command introduced before JunosE Release 7.1.0.  
**merge** keyword added in JunosE Release 7.2.0.

**Description** Assigns a policy list to the ingress or egress of an MPLS layer 2 transport interface. If you enter this command when the policy list does not exist, the router will create a policy list with a filter rule as the default. Attaching this policy list to an interface filters all packets on that interface. You must specify the **input** or **output** keyword to assign the policy list to the ingress or egress of the interface. The **no** version removes the association between a policy list and an interface.

- Options**
- **input**—Applies policy to data arriving at this interface
  - **output**—Applies policy to data leaving this interface
  - ***policyName***—Name of the policy; a maximum of 40 characters
  - **statistics**—Enables or disables collection of policy routing statistics
    - **enabled**—Enables collection of policy routing statistics
    - **baseline enabled**—Enables baselining of policy routing statistics
    - **baseline disabled**—Disables baselining of policy routing statistics
  - **preserve**—Preserves existing statistics for any classifier-list that is the same for both the new and old policy attachments when you attach a new policy to an interface
  - **disabled**—Disables collection of policy routing statistics
  - **merge**—Enables merging of multiple policies to form a single policy

**Mode** Interface Configuration

- Related Documentation**
- Configuring HDLC Layer 2 Services
  - Setting a Statistics Baseline for Policies

## mpls policy-list

---

**Syntax** [ no ] mpls policy-list *policyName*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates the specified policy list and accesses Policy List Configuration mode. If you enter the **mpls policy-list** command and the policy list does not exist, the router creates a policy list with no rules, the default. When a policy list does not have rules, the router inserts a default filter rule. Attaching this policy list to an interface filters all packets on that interface. The **no** version deletes the policy list.

**Options** • *policyName*—Name of a policy list; string of up to 40 alphanumeric characters

**Mode** Global Configuration

**Related Documentation** • Creating Policy Lists for MPLS

## mpls policy-parameter hierarchical

<b>Syntax</b>	<p>mpls policy-parameter hierarchical <i>parameterName</i> { <i>nodeValue</i>   atm   atm-vc   atm-vp  <i>vpValue</i>   ethernet   fr-vc   forwarding   svlan <i>svlanValue</i>   vlan }</p> <p>no policy-parameter <i>parameterName</i></p>
<b>Release Information</b>	Command introduced in JunosE Release 8.0.0.
<b>Description</b>	Specifies a parameter value for MPLS interfaces. The <b>no</b> version removes the policy parameter and its contents.
<b>Options</b>	<ul style="list-style-type: none"> <li>• <i>parameterName</i>—Name of policy parameter</li> <li>• <i>nodeValue</i>—Aggregation node number in the range 1–65535</li> <li>• <i>vpValue</i>—ATM VPI number in the range 0–255</li> <li>• <i>svlanValue</i>—SVLAN ID number in the range 0–4095</li> </ul>
<b>Mode</b>	Interface Configuration
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• Creating a Classifier Group for a Policy List</li> </ul>

## mpls policy-parameter reference-rate

---

**Syntax**    mpls policy-parameter reference-rate *parameterName* [ increase ] *value*  
              no mpls policy-parameter reference-rate *parameterName* [ increase *value* ]

**Release Information**    Command introduced in JunosE Release 8.1.0.

**Description**    Creates an MPLS policy parameter for a reference rate; creates a global parameter if it does not exist. The **no** version removes the policy parameter and its contents; if used with the **increase** keyword, decreases the value.

- Options**
- *parameterName*—Name of policy parameter up to 40 characters
  - increase—Increments the existing reference rate value
  - *value*—Value of the reference rate parameter, in the range 0–4292967295

**Mode**    Interface Configuration

**Related Documentation**

- Creating a Classifier Group for a Policy List

## mpls policy-statistics

---

**Syntax**    mpls { enable | disable } policy-statistics *tunnelName*

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables policy statistics to be collected for the specified tunnel or LSP. Statistics collection is disabled by default. There is no **no** version.

**Options**

- enable—Enables the collection of policy statistics
- disable—Disables the collection of policy statistics; this is the default setting
- *tunnelName*—Name of a tunnel or LSP; string of up to 20 alphanumeric characters

**Mode**    Privileged Exec, User Exec

## mpls preserve-vpn-exp

---

**Syntax** [ no ] mpls preserve-vpn-exp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Prevents the value of the EXP bits for a VPN label from being modified by either a per-LSP policy for the outer labels or per-VR traffic class/color rules. In the default condition, per-LSP policies or per-VR rules modify all labels in a given label stack to have the same value for the EXP bits. The **no** version restores the default condition.

**Mode** Global Configuration

## mpls-relay

**Syntax** `mpls-relay remotelpAddress [ vc-id ] vcidValue [ group-id groupIdValue ]`  
`[ control-word | no-control-word ] [ sequencing | no-sequencing ]`  
`[ relay-format { ethernet | frame-relay | ppp | vlan | ethernet-raw-mode } ]`  
`no mpls-relay`

**Release Information** Command introduced before JunosE Release 7.1.0.  
**control-word**, **no-control-word**, **no-sequencing**, and **vlan** keywords added in JunosE Release 7.1.0.  
**frame-relay** keyword added in JunosE Release 9.1.0.  
**ethernet-raw-mode** keyword added in JunosE Release 10.0.0.

**Description** Routes layer 2 traffic to the specified router by creating an MPLS shim interface on the layer 2 interface. The router can use any MPLS LSP to the remote destination address that you specify. You must issue this command in the virtual router where the remote address can be reached; that is, in the virtual router providing core connections. The **no** version removes the shim interface. See also the route interface command.



**NOTE:** This command is supported for configuration on an ATM port (ATM Adaptation Layer 5 [AAL5] over an ATM major interface). Before you can specify VPI/VCI ranges and cell concatenation parameters on the ATM port to enable transmission of multiple ATM virtual circuits over a single pseudowire, you must associate the ATM port with the corresponding pseudowire using the `mpls-relay` or `router interface tunnel` command. For more information about the support for multiple VCs over a single pseudowire, see *Multiple ATM Virtual Circuits over a Single Pseudowire Overview* in the *JunosE BGP and MPLS Configuration Guide*

- Options**
- *remotelpAddress*—IP address of the router on the remote end of the layer 2 circuit
  - *vcidValue*—Integer in the range 1–4294967295 that identifies the virtual connection; the two ends across the MPLS core must match inside each VC type



**NOTE:** The VLAN ID, DLCI, or ATM VPI/VCI are not related to the VC ID and can be different on each end of the connection.

- *groupIdValue*—Integer in the range 0–4294967295 that identifies a group of virtual connections; not currently used
- *control-word*—Indicates that the local preference is to use the control word for the layer 2 packets encapsulated in MPLS packets sent to the remote PE router. The default preference is determined by the interface stack on which the MPLS interface is stacked.

- **no-control-word**—Indicates that the local preference is to not use the control word for the layer 2 packets encapsulated in MPLS packets sent to the remote PE router. The default preference is determined by the interface stack on which the MPLS interface is stacked.
- **sequencing**—Specifies that the local preference is to include nonzero sequence numbers with the control word; enabling the remote PE to detect out-of-order packets; has no effect if no control word is sent in the packets. The router always accepts zero sequence numbers and checks the order of nonzero sequence numbers of MPLS packets received from the remote PE; any out of order packets are dropped, regardless of whether sequencing is configured.
- **no-sequencing**—Specifies that the sequencing number in the control word is set to zero, instructing the remote PE router to not attempt to detect out-of-order packets; has no effect if no control word is sent in the packets.
- **relay-format ethernet**—Specifies that the router uses Ethernet signaling and encapsulation, which causes the VLAN interface to appear as an Ethernet interface to the other side of the connection; enables a VLAN interface on one side of an MPLS tunnel to communicate with an Ethernet or a bridged Ethernet interface on the other side of an MPLS tunnel. The VLAN tag is not included in the MPLS encapsulation. This option is not available on serial or POS interfaces for HDLC layer 2 circuits. It is available only on VLAN interfaces
- **relay-format frame-relay**—Specifies that the router uses legacy (pre-RFC 4619) Frame Relay pseudowire type value for signaling and encapsulation. Enables a router running JunosE Software that supports the pseudowire type value defined in RFC 4619, Encapsulation methods for transport of Frame Relay over MPLS Networks, to interoperate with a router that uses the legacy (pre-RFC 4619) pseudowire type value. This option is available on serial or POS interfaces for Frame Relay layer 2 circuits. It is not supported on E120 and E320 routers.
- **relay-format ppp**—Specifies that the router uses VC-type PPP signaling and PPP encapsulation instead of VC-type HDLC signaling and HDLC encapsulation. The router uses VC-type HDLC signaling and HDLC encapsulation by default. This option is available only on serial and POS interfaces for HDLC layer 2 circuits.
- **relay-format vlan**—Specifies that the router uses VLAN signaling and encapsulation. This option is not available on serial or POS interfaces for HDLC layer 2 circuits. It is available for VLAN interfaces.
- **relay-format ethernet-raw-mode**—Specifies that the router uses Ethernet raw mode encapsulation for packets entering and leaving pseudowires. This service corresponds to PW type 0x0005 "Ethernet" [IANA]. When configured on an S-VLAN subinterface, enables the provider edge (PE) device to strip the S-VLAN tags from all packets entering the Martini circuit (MPLS packet switched network). It is supported on ES2 4G, ES2 10G, and ES2 10G Uplink LMs on E120 and E320 routers. You can enable the raw mode configuration only for MPLS shim interfaces stacked on SVLAN interfaces.





**NOTE:** The `relay-format` keyword determines the pseudowire PW Type value that is used in LDP protocol messages. For a complete list of pseudowire Type values, see <http://www.iana.org/assignments/pwe3-parameters>.

If you do not specify the `relay-format` keyword in the `mpls-relay` or `route interface` command, the pseudowire Type value is chosen based on the type of the interface. For Ethernet interfaces, the pseudowire Type value is chosen as Ethernet (0x0005). For VLAN interfaces, the pseudowire Type value is chosen as Ethernet Tagged Mode (0x0004)

**Mode** Interface Configuration, Subinterface Configuration

**Related Documentation**

- *Configuring an MPLS Pseudowire with VCC Cell Relay, Configuring Ethernet/VLAN Layer 2 Services, Configuring Frame Relay Layer 2 Services, Configuring HDLC Layer 2 Services, Configuring Local ATM Cross-Connects Between Ethernet/VLAN Interfaces, Configuring Ethernet Raw Mode Encapsulation for Martini Layer 2 Transport, and Configuring S-VLAN Tunnels for Layer 2 Services* in the *JunosE BGP and MPLS Configuration Guide*

## **mpls-relay atm cell-packing mcpt-timer**

---

**Syntax**    `mpls-relay atm cell-packing maxCellsPerPacket mcpt-timer timerIdentifier`  
`no mpls-relay atm cell-packing`

**Release Information**    Command introduced in JunosE Release 10.2.0.

**Description**    Configures cell concatenation parameters for an ATM port to calculate the maximum number of ATM cells that the router can concatenate in a single packet and the unique identifier of the ATM Martini cell packing timer that you want to use to detect timeout of the cell collection threshold. You can configure this command on the ATM port only after you associated a pseudowire with the port by using the `mpls-relay` or `route interface tunnel` command. You can use this command only on an ATM port (ATM AAL5 over ATM major interface). The **no** version disables cell concatenation, which is the default behavior.

- Options**
- `atm`—Configures ATM interface parameters for MPLS cross-connect
  - `maxCellsPerPacket`—Maximum number of ATM cells in the range 1–190 that the router can concatenate in a single VCC cell relay-encapsulated packet and transmit on an MPLS pseudowire connection; default value is 1 cell per packet
  - `timerIdentifier`—Integer in the range 1–3 that identifies which of the three ATM Martini cell packing timers (timer 1, timer 2, or timer 3) you want to use to detect timeout of the cell collection time threshold; default value is 1. When the timer expires, the router forwards the packet even if the number of concatenated ATM cells in the packet is fewer than the specified maximum number of cells per packet.

**Mode**    Interface Configuration

- Related Documentation**
- [Multiple ATM Virtual Circuits over a Single Pseudowire Overview](#)
  - [Example: Multiple ATM Virtual Circuits over a Single Pseudowire](#)

## mpls-relay atm vpi-range vci-range

**Syntax** [ no ] mpls-relay atm vpi-range *vpiStart vpiEnd* vci-range *vciStart vciEnd*

**Release Information** Command introduced in JunosE Release 10.2.0.

**Description** Configures a single virtual path identifier (VPI)/virtual circuit identifier (VCI) range of ATM VCs whose cells need to be transported on the single pseudowire. You can configure this command on the ATM port only after you associated a pseudowire with the port by using the **mpls-relay** or **route interface tunnel** command. When you run the **mpls-relay** or **route interface tunnel** command, no default VPI/VCI range is configured. You must specifically configure the VPI/VCI ranges. You can use this command only on an ATM port (ATM AAL5 over ATM major interface). The VPI/VCI values that are not part of the specified range can be used for other existing applications. The **no** version removes the configured VPI/VCI range.



**NOTE:** The total number of VCs configured with the **mpls-relay atm vpi-range vci-range** command cannot exceed the maximum ATM VC capacity of the line module you are using. For details about the ATM VC capacity of supported line modules, see *JunosE Release Notes, Appendix A, System Maximums*.

- Options**
- **atm**—Configures ATM interface parameters for MPLS cross-connect. A local cross-connect enables the router to function as a layer 2 switch. It operates with any supported layer 2 service
  - **vpiStart**—Starting virtual path identifier (inclusive) of the VC subrange you are configuring; number in the range 0–255
  - **vpiEnd**—Ending virtual path identifier (inclusive) of the VC subrange you are configuring; number in the range 0–255
  - **vciStart**—Starting virtual circuit identifier (inclusive) of the VC subrange you are configuring; number in the range 1–65535
  - **vciEnd**—Ending virtual circuit identifier (inclusive) of the VC subrange you are configuring; number in the range 1–65535

**Mode** Interface Configuration

- Related Documentation**
- Multiple ATM Virtual Circuits over a Single Pseudowire Overview
  - Example: Multiple ATM Virtual Circuits over a Single Pseudowire

## mpls-relay disable

---

**Syntax** [ no ] mpls-relay disable

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Administratively disables the MPLS shim interface. The MPLS shim interface must exist before this command can be issued. MPLS shim interfaces are administratively enabled by default. The **no** version restores the default condition.

**Mode** Interface Configuration

## mpls reoptimize

---

**Syntax**    mpls [ traffic-eng ] reoptimize [ *interfaceType interfaceSpecifier* ]

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Performs an immediate check for better paths for all existing LSPs. There is no **no** version.

- Options**
- traffic-eng—Specifies optional keyword for compatibility with non-E Series implementations
  - *interfaceType*—Interface type; see [“Interface Types and Specifiers” on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Privileged Exec, User Exec

## mpls reoptimize timers frequency

---

**Syntax**    mpls [ traffic-eng ] reoptimize timers frequency *seconds*  
              no mpls [ traffic-eng ] reoptimize timers frequency

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the frequency at which existing LSPs are checked for better paths. RSVP-TE adds a random number in the range 0–60 seconds to the specified value to prevent all LSPs from being reoptimized simultaneously. The **no** version restores the default value, 3600 seconds.



.....  
**NOTE:** Low timer values lead to frequent reoptimization of LSPs, which is undesirable for the following reasons:

- Frequent changes to the LSPs increases packet loss.
  - Frequent reoptimization increases the load on the router, especially when the router acts as the LSP head end. The load is particularly noticeable in a scaled network, resulting in high CPU utilization on the router.
- .....

**Options**

- **traffic-eng**—Specifies optional keyword for compatibility with non-E Series implementations
- **seconds**—Number of seconds in the range 0–604800; a value of zero means that no reoptimization is performed

**Mode**    Global Configuration

## mpls rsvp

---

**Syntax** [ no ] mpls rsvp

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables RSVP-TE, as does any RSVP-TE–related command. The **no** version disables RSVP-TE.

**Mode** Global Configuration

## mpls rsvp authentication

---

**Syntax** [ no ] { ip | mpls } rsvp authentication

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables MD5 authentication for RSVP on the interface. Enable authentication after configuring the authentication key. The router generates an error message and discards any RSVP messages if you enable authentication before configuring the authentication key, or remove the key while authentication is still enabled. The **no** version disables authentication.

- Options**
- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
  - **mpls**—Specifies JunosE MPLS implementation

**Mode** Interface Configuration



## mpls rsvp authentication key

**Syntax** { ip | mpls } rsvp authentication [ key *authkey* ]  
 no { ip | mpls } rsvp authentication [ key [ *authkey* ] ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Assigns a key to the interface for MD5 authentication between RSVP peers. Assign the key before you enable authentication on the interface. The **no** version deletes the MD5 key.



**NOTE:** Keys of up to 40 characters are supported for non-Juniper Networks implementations. However, a key with more than 16 characters will cause an authenticated link between E Series and M- or T-series routers to be inoperable.

- Options**
- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
  - **mpls**—Specifies JunosE MPLS implementation
  - **authkey**—Key used to create MD5 digest for messages sent from this interface and to authenticate messages received on this interface; alphanumeric string in the range 1–40 characters

**Mode** Interface Configuration

## mpls rsvp bfd-liveness-detection

**Syntax** { ip | mpls } rsvp bfd-liveness-detection [ minimum-interval *minInterval* |  
[ minimum-receive-interval *minRecInterval* ]  
[ minimum-transmit-interval *minTransInterval* ] ] [ multiplier *multValue* ]  
  
no { ip | mpls } rsvp bfd-liveness-detection

**Release Information** Command introduced in JunosE Release 8.1.0.

**Description** Enables BFD (bidirectional forwarding detection) on an interface running RSVP-TE and defines BFD values to be negotiated between RSVP-TE neighbors for detection of IP data path failures. The **no** version disables BFD on the RSVP-TE interface.



**NOTE:** BFD sessions might not be maintained when the multiplier value is 1 and configured intervals are very short. We recommend that you do not use a multiplier value of 1 with very short intervals.

- Options**
- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
  - **mpls**—Specifies JunosE MPLS implementation
  - ***minInterval***—Minimum proposed transmit interval and required receive interval for BFD control packets; has the same effect as configuring the minimum receive interval and the minimum transmit interval to the same value; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - ***minRecInterval***—Minimum interval at which the local peer must receive BFD control packets sent by the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - ***minTransInterval***—Minimum interval at which the local peer proposes to transmit BFD control packets to the remote peer; number in the range 100–65535 milliseconds—for ES2 4G LM only, the range is 10–65535 milliseconds; default value is 300 milliseconds
  - ***multValue***—Detection multiplier value that the remote peer router multiplies by the local peer's negotiated transmit interval to determine the remote peer's BFD liveness detection interval; equal to the number of BFD packets that can be missed before the BFD session is declared down; number in the range 1–255; default value is 3

**Mode** Interface Configuration

## mpls rsvp disable

---

**Syntax** [ no ] mpls rsvp disable

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Administratively disables RSVP-TE on the interface. The **no** version reenables RSVP-TE on the interface.

**Mode** Interface Configuration

## mpls rsvp egress-label

---

**Syntax**    mpls { rsvp | traffic-eng } egress-label { non-null | explicit-null }  
              no mpls { rsvp | traffic-eng } egress-label

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Specifies that the egress router advertises the explicit null label or a non-null (real) label by means of RSVP-TE. This advertisement ensures that packets received from upstream include a label and that the egress router performs ultimate hop popping. The **no** version restores the default condition, where the egress router advertises the implicit null label for all tunnels (except those requiring PHB) that terminate on the router.

**Options**

- rsvp—Specifies JunosE implementation
- traffic-eng—Specifies keyword for compatibility with non-E Series implementations
- non-null—Advertises a real label, signaling that the egress router pops the last label and performs the IP lookup; this behavior was the default before this release
- explicit-null—Advertises the explicit null label, signaling that the egress router pops the last label and performs the IP lookup

**Mode**    Global Configuration

## mpls rsvp message-bundling

---

**Syntax** [ no ] mpls rsvp message-bundling

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables RSVP-TE to send bundle messages, each of which includes multiple standard RSVP-TE messages, to reduce the overall message-processing overhead. The **no** version disables RSVP-TE message bundling.

**Mode** Global Configuration

## mpls rsvp profile

---

**Syntax** In Global Configuration mode:

```
mpls rsvp [ interface ] profile [ profileName ]
```

```
no mpls rsvp interface profile profileName
```

In Interface Configuration mode:

```
mpls rsvp profile profileName
```

```
no mpls rsvp profile
```

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** In Global Configuration mode, creates or modifies a configuration profile for RSVP-TE. Places the CLI in RSVP Configuration mode. If you specify a profile not previously configured, it is created with the factory default settings. If you do not specify a profile name, the factory default profile is assumed. The implicit default RSVP-TE profile specifies a value of 30,000 ms (30 seconds) for the refresh period and a value of 3 for the timeout factor.

Any change to a profile affects all interfaces that use the profile; changes are effective the next time the interface comes up. The **no** version deletes the specified profile. The **no** version deletes the specified profile.

In Interface Configuration mode, creates or enables RSVP-TE on the interface with the factory default profile or the specified profile, or disables RSVP-TE on the interface. The **no** version reverts to the default profile on the interface.

In both modes, if you specify a profile not previously configured, it is created with the factory default settings. If you do not specify a profile name, the factory default profile is assumed. The **no** version deletes the specified profile. The **no** version deletes the specified profile.

- Options**
- **interface**—Keyword required for the **no** version in Global Configuration mode
  - **profileName**—Name of a profile to be created or modified (Global Configuration mode), applied to an interface (Interface Configuration mode), or deleted (both modes); the profile sets the values for the protocol parameters; until you modify the profile settings, the values match those of the implicit default profile

**Mode** Global Configuration, Interface Configuration

## mpls rsvp refresh-reduction

---

**Syntax** [ no ] mpls rsvp refresh-reduction

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables RSVP-TE summary refresh and reliability features, including the message ID object, the message ack object, and summary refresh messages. The **no** version disables summary refresh and reliability.

**Mode** Global Configuration

## mpls rsvp signalling hello

---

**Syntax** { ip | mpls } rsvp signalling hello  
[ refresh { interval *helloInterval* | misses *helloMisses* } ]  
  
{ no | default } { ip | mpls } rsvp signalling hello

**Release Information** Command introduced in JunosE Release 7.3.0.

**Description** In Global Configuration mode, turns on or configures RSVP-TE hello support for all RSVP-TE interfaces on the current virtual router. Automatically creates RSVP-TE or MPLS on the current virtual router if they do not yet exist there. The **no** version turns off hello support on the current VR. The **default** version restores the default configuration, in which RSVP hello support is not enabled.

In Interface Configuration mode and Subinterface Configuration mode, turns on or configures RSVP-TE hello support on the current interface, and overrides the global configuration. Automatically creates RSVP-TE or MPLS on the current virtual router if they do not yet exist there. This command also creates RSVP-TE on the interface if it is not configured there. The **no** version turns off hello support on the current interface. The **default** version restores the default configuration, in which RSVP hello support is not enabled, and also restores inheritance of the configuration values from the global configuration.

- Options**
- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
  - **helloInterval**—Number of milliseconds specifying the interval at which hellos are sent, in the range 1000–60000; default value is 10000
  - **helloMisses**—Number of RSVP-TE hello messages from a peer that can be missed before that hello adjacency peer is considered to be down, in the range 4–10; default value is 4

**Mode** Global Configuration, Interface Configuration, Subinterface Configuration



## mpls rsvp signalling hello graceful-restart

---

**Syntax** { ip | mpls } rsvp signalling hello graceful-restart [ mode help-neighbor ]  
no { ip | mpls } rsvp signalling hello graceful-restart

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Enables RSVP-TE graceful restart as a restarting node or helper node on the current virtual router. The **no** version disables graceful restart on the current VR.

**Options**

- ip—Specifies alternative keyword for compatibility with non-E Series implementations
- mode help-neighbor—Specifies the current VR acts only as a graceful restart helper node for neighbors that support RSVP-TE graceful restart

**Mode** Global Configuration

## mpls rsvp signalling hello graceful-restart recovery-time

**Syntax** { ip | mpls } rsvp signalling hello graceful-restart recovery-time *recoveryTime*  
no { ip | mpls } rsvp signalling hello graceful-restart recovery-time

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Configures the recovery time for RSVP-TE graceful restart for all interfaces that have RSVP-TE enabled. The **no** version restores the default value.

- Options**
- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
  - **recoveryTime**—Time in milliseconds within which you want the neighboring routers to resynchronize RSVP-TE state and MPLS forwarding state after a graceful restart, in the range 60000–480000; default value is 120000

**Mode** Global Configuration

## mpls rsvp signalling hello graceful-restart restart-time

---

**Syntax** { ip | mpls } rsvp signalling hello graceful-restart restart-time *restartTime*  
no { ip | mpls } rsvp signalling hello graceful-restart restart-time

**Release Information** Command introduced in JunosE Release 8.0.0.

**Description** Configures the restart time for RSVP-TE graceful restart for all interfaces that have RSVP-TE enabled. The **no** version restores the default value.

**Options**

- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
- **restartTime**—Total time in milliseconds for the sender to gracefully restart RSVP-TE and to re-establish hello communication with RSVP-TE neighbors; in the range 60000–3600000; default value is 60000

**Mode** Global Configuration

## mpls rsvp signalling node-hello

---

**Syntax** { ip | mpls } rsvp signalling node-hello  
[ refresh { interval *helloInterval* | misses *helloMisses* } ]  
  
{ no | default } { ip | mpls } rsvp signalling node-hello

**Release Information** Command introduced in JunosE Release 9.0.0.

**Description** Turns on or configures RSVP-TE hellos to include node IDs as source and destination addresses in the hello packets for all RSVP-TE interfaces on the current virtual router. RSVP-TE hellos based on node ID enable the JunosE Software to interoperate its RSVP-TE graceful restart capability with routers that cannot support RSVP-TE graceful restart with link-based hellos.

The **no** version turns off node-hello support on the current VR. The **default** version restores the default configuration, in which RSVP node hello support is not enabled.



.....  
**NOTE:** Node hellos are required only for interoperability with some non-E Series implementations. Node hellos are not required for communications between routers running JunosE Software or for interoperability with routers running Junos OS.  
.....

- Options**
- **ip**—Specifies alternative keyword for compatibility with non-E Series implementations
  - ***helloInterval***—Number of milliseconds specifying the interval at which node hellos are sent, in the range 1000–60000; default value is 10000
  - ***helloMisses***—Number of RSVP-TE node hello messages from a peer that can be missed before that hello adjacency peer is considered to be down, in the range 4–10; default value is 4

**Mode** Global Configuration

## mpls signaling-interface

**Syntax**    mpls signaling-interface *interfaceType interfaceSpecifier*  
               no mpls signaling-interface

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Specifies a particular layer 2 interface as the signaling interface for an MPLS major interface that is stacked on an ATM AAL5 interface. MPLS uses the IPv4 or IPv6 interface stacked on the specified interface for signaling. The **no** version restores the default behavior, wherein MPLS nondeterministically selects a layer 2 interface as the signaling interface.



**NOTE:** You can configure this command only for interfaces that use the interface label space. For interfaces that use the platform label space, the signaling interface is always next to the MPLS major interface, that is, stacked on the same lower interface and is not configurable.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode**    Interface Configuration

## mpls spf-use-any-best-path

---

**Syntax** [ no ] mpls spf-use-any-best-path

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables the SPF calculations to consider both the best IGP (IS-IS or OSPF) paths and the MPLS tunnel to reach the tunnel endpoint. The **no** version restores the default value, which is to always use the MPLS tunnel to reach the tunnel endpoint—the IGP best paths are not considered.

**Mode** Router Configuration

---

## mpls statistics label

---

**Syntax** [ no ] mpls statistics label { interface *interfaceName* atm *vpi vci* | *labelValue* }

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables statistics collection for MPLS in labels. By default, statistics are enabled for in labels depending on the protocol that added the in label to the MPLS forwarding table. Statistics are not stored in NVS. The **no** version disables statistics collection.

- Options**
- *interfaceName*—Name of interface for label in interface label space on an ATM AAL5 interface; up to 15 alphanumeric characters
  - *vpi*—Virtual path identifier for a label, a value in the range 0–255
  - *vci*—Virtual circuit identifier for a label, a value in the range 33–65535
  - *labelValue*—Integer identifying a label in the platform label space, a value in the range 16–1048575

**Mode** Global Configuration

## mpls statistics next-hop

---

**Syntax** [ no ] mpls statistics next-hop *nextHopIndex*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables statistics collection for MPLS next hops. By default, statistics are enabled for next hops depending on the protocol that created the MPLS next hop. Statistics are not stored in NVS. The **no** version disables statistics collection.

**Options** • *nextHopIndex*—Integer uniquely identifying a next hop; in the range 1–1048575

**Mode** Global Configuration



## mpls statistics policy

---

**Syntax** [ no ] mpls statistics policy *tunnelName*

**Release Information** Command introduced in JunosE Release 7.1.0.

**Description** Enables statistics collection for policies attached to an MPLS tunnel. Statistics are not stored in NVS. The **no** version disables statistics collection.

**Options** • *tunnelName*—Name of the MPLS tunnel

**Mode** Global Configuration

## mpls topology-driven-lsp

---

**Syntax** [ no ] mpls topology-driven-lsp

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables topology-driven LSP creation on the virtual router where the LSR automatically creates LSPs when it learns a new IGP route. In the context of the VRF virtual router, enables carrier-of-carriers support on the provider carrier's PE router.

The router advertises labels for new routes immediately to all peers without waiting for a label request message from an upstream peer or a label mapping message from a downstream peer. This mode is downstream-unsolicited, independent control.

The **no** version disables topology-driven LSPs on the virtual router.

**Mode** Global Configuration

## mpls topology-driven-lsp ip-interfaces

**Syntax** [ no ] mpls topology-driven-lsp ip-interfaces [ egress | ingress ]  
 [ { access-list | prefix-list } *listName* ] [ host-only ]

no mpls topology-driven-lsp ip-interfaces [ egress | ingress ] [ host-only ]  
 [ policy-list ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies LSPs to be put into the IP routing table for forwarding plain IP traffic. The **no** version removes the LSPs from the table.



**NOTE:** This command is deprecated and may be removed completely in a future release. The function provided by this command has been replaced by the **ldp ip-forwarding** command.

- Options**
- egress—Has no effect
  - ingress—Has no effect
  - access-list—Specifies that *listName* is an access list
  - prefix-list—Specifies that *listName* is a prefix list
  - *listName*—Name of access list or prefix list that specifies LSPs over which IP interfaces are created
  - host-only— Specifies that only LSPs to host addresses are added to the IP routing table
  - policy-list—Removes previously applied access lists or prefix lists

**Mode** Global Configuration

## mpls traffic-class

---

**Syntax** [ no ] mpls traffic-class *className* [ scheduler-profile *profileName* ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies traffic class for which LSP-level queues are created. The **no** version deletes the traffic class.

- Options**
- *className*—Name of a traffic class; the router supports up to eight traffic classes
  - *profileName*—Name of a scheduler profile to associate with the traffic class

**Mode** Global Configuration

## mpls traffic-eng

---

**Syntax**    mpls traffic-eng level-1 | level-2  
              no mpls traffic-eng level-1 | level-2

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Enables flooding of MPLS traffic-engineering link information into the specified IS-IS level. Flooding is disabled by default. The **no** version disables flooding.

**Options**    • level-1—Floods IS-IS level 1  
              • level-2—Floods IS-IS level 2

**Mode**    Router Configuration

## mpls traffic-eng administrative-weight

---

**Syntax**    mpls traffic-eng administrative-weight *weight*  
              no mpls traffic-eng administrative-weight

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the administrative weight for the interface. The **no** version restores the default value, which matches the IGP-determined weight (cost).

**Options**    • *weight*—Administrative weight, a value in the range 0–4294967295 supersedes any weight conferred upon the link by the IGP

**Mode**    Interface Configuration, Subinterface Configuration

## mpls traffic-eng area

---

**Syntax** [ no ] mpls traffic-eng area { *areald* | *arealdInt* }

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Enables flooding of MPLS traffic-engineering link information into the specified OSPF area. Flooding is disabled by default. The **no** version disables flooding.

**Options**

- *areald*—OSPF area ID in IP address format
- *arealdInt*—OSPF area ID as a decimal value in the range 0–4294967295

**Mode** Router Configuration

## mpls traffic-eng attribute-flags

---

**Syntax**    mpls traffic-eng attribute-flags *bitmask*  
              no mpls traffic-eng attribute-flags

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies attributes for the interface for traffic engineering. The attributes are compared with tunnel affinity bits to determine links eligibility for the tunnel. The **no** version restores the default value, 0x0.

**Options**    • *bitmask*—Mask that sets the attributes, a value in the range 0x0–0xFFFFFFFF

**Mode**    Interface Configuration, Subinterface Configuration



## **mpls traffic-eng egress-label**

---

**Syntax**    mpls { rsvp | traffic-eng } egress-label { non-null | explicit-null }  
              no mpls { rsvp | traffic-eng } egress-label

**Release Information**    Command introduced in JunosE Release 7.3.0.

**Description**    Specifies that the egress router advertises the explicit null label or a non-null label by means of RSVP-TE. See the [mpls rsvp egress-label](#) command for a complete description and syntax.

**Mode**    Global Configuration

## mpls traffic-eng flood thresholds

---

**Syntax**    mpls traffic-eng flood thresholds { up | down } *percentage* [ *percentage* ]\*  
              no mpls traffic-eng flood thresholds { up | down }

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies thresholds for the flooding of the current reservable bandwidth throughout the network. You can configure a set of thresholds for increases or decreases in bandwidth. Flooding is triggered when the reservable bandwidth increases past any up threshold or decreases past any down threshold. The **no** version restores the following default values:

- For increases in bandwidth (up changes)—15, 30, 45, 60, 75, 80, 85, 90, 95, 97, 98, 99, 100
- For decreases in bandwidth (down changes)—100, 99, 98, 97, 96, 95, 90, 85, 80, 75, 60, 45, 30, 15

**Options**

- up—Specifies that an increase in bandwidth past the threshold triggers flooding
- down—Specifies that a decrease in bandwidth past the threshold triggers flooding
- *percentage*—Percentage of reservable bandwidth, a value from 1 to 100 percent for increasing bandwidth and from 0 to 99 percent for decreasing bandwidth
- \*—Indicates that the percentage can be repeated multiple times in a list in the command line

**Mode**    Interface Configuration, Subinterface Configuration

## mpls traffic-eng link-management timers periodic-flooding

**Syntax**    mpls traffic-eng link-management timers periodic-flooding *frequency*  
              no mpls traffic-eng link-management timers periodic-flooding

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies the interval at which bandwidth values are flooded to the entire network. Configuring a value of 0 turns off flooding. The **no** version restores the default value, 180.

**Options**    • *frequency*—Interval in seconds, a value in the range 0–3600

**Mode**    Global Configuration

## **mpls traffic-eng multicast-intact**

---

**Syntax**    [ no ] mpls traffic-eng multicast-intact

**Release Information**    Command introduced in JunosE Release 7.1.0.

**Description**    Enables a multicast network and MPLS traffic engineering (TE) network to interoperate on a router running OSPF. The **no** version disables interoperability between multicast protocols and MPLS-TE.

**Mode**    Router Configuration

---

## mpls traffic-eng router-id

---

**Syntax** [ no ] mpls traffic-eng router-id *interfaceType interfaceSpecifier*

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Specifies a stable interface to be used as a router ID for MPLS traffic engineering with IS-IS or OSPF, typically a loopback interface. The interface acts as the destination node for tunnels originating at other nodes. The **no** version removes the interface as a router ID.

- Options**
- *interfaceType*—Interface type; see [Interface Types and Specifiers on page 5](#)
  - *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)

**Mode** Router Configuration

## mpls tunnel-model

---

**Syntax**    mpls tunnel-model { pipe | uniform }  
              no mpls tunnel-model

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Specifies whether MPLS employs the pipe or uniform tunnel model for differentiated services. The **no** version restores the default, the pipe model.

**Options**    • pipe-model—Specifies that the pipe model is followed  
              • uniform-model—Specifies that the uniform model is followed

**Mode**    Global Configuration

## mpls tunnels profile

---

**Syntax** [ no ] mpls tunnels profile *profileName* [ disable ]

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Creates or disables a tunnel profile for MPLS. The **no mpls tunnels profile** version deletes the tunnel profile. The **no mpls tunnels profile disable** version reenables tunnels previously disabled.

**Options**

- *profileName*—Name of a tunnel configuration profile used for MPLS tunnels
- **disable**—Disables all tunnels associated with the profile

**Mode** Global Configuration

## mrout port admission-bandwidth-limit

---

**Syntax**    `mrout port portNumber admission-bandwidth-limit limitValue`  
              `[ priority-bandwidth-limit priorityBandwidthValue ] [ hysteresis hysteresisValue ]`

`no mrout port portNumber admission-bandwidth-limit`

**Release Information**    Command introduced in JunosE Release 7.1.0.  
                              **hysteresis** and **priority-bandwidth limit** keywords and *hysteresisValue* and *priorityBandwidthValue* variables added in JunosE Release 8.2.0.

**Description**    Configures a limit on the admission bandwidth of outgoing interfaces (OIFs) containing IPv4 or IPv6 mroutes, across different virtual routers, on a port. The **no** version removes any OIF admission bandwidth limits.

- Options**
- *portNumber*—Port number in the form *slot/port*.
  - *limitValue*—Limit on the admission bandwidth (in bits per second) of outgoing interfaces containing IPv4 or IPv6 mroutes, across different virtual routers, on a port. The default is no limit.
  - *priorityBandwidthValue*— Minimum value of admitted priority bandwidth in bps. The default is no limit.
  - *hysteresisValue*—Minimum priority bandwidth limit before the system evaluates mroutes and admits any blocked OIFs; in the range 0-100 percent.

**Mode**    Global Configuration



## mroute port limit

---

**Syntax**    `mroute port portNumber limit limitValue`  
              `no mroute port portNumber limit`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Configures a limit on the number of outgoing interfaces (OIFs) containing IPv4 or IPv6 mroutes, across different virtual routers, on a port. The **no** version removes any OIF port limits.

**Options**

- *portNumber*—Port number in the form *slot/port*.
- *limitValue*—Limit on the number of outgoing interfaces containing IPv4 or IPv6 mroutes, across different virtual routers, on a port. The default is no limit.

**Mode**    Global Configuration

## mru

---

**Syntax**    `mru mruSize`

`no mru`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum allowable size in bytes of the maximum receive unit for interfaces on cOCx/STMx, COCX-F3, CT3, and POS modules. The **no** version restores the default value, which varies according to module type.

- Options**
- *mruSize*—Maximum allowable size of the MRU; default and range varies with module type:
    - Interfaces on cOCx/STMx, CT3, and COCX-F3 modules—Number in the range 4–9996; default value is 1600
    - Interfaces on POS modules—Number in the range 1–9996; default value is 4470

**Mode**    Interface Configuration

## mtrace

---

**Syntax** `mtrace sourceAddress [ destinationAddress [ groupAddress [ responseAddress ] ] ]`  
`[ maxHops ] [ detailed ]`

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Discovers the routes that multicast packets follow when travelling to their destinations. There is no **no** version.

- Options**
- *sourceAddress*—DNS name or unicast IP address of the multicast-capable device at the beginning of the path.
  - *destinationAddress*—DNS name or unicast address of the device at the end of the path. The default destination is the router from which you type the command.
  - *groupAddress*—DNS name or multicast address of the group for which you want to trace routes. The default address is 224.2.0.1 (the group used for MBONE Audio).
  - *responseAddress*—IP address that receives the results of the trace
  - *maxHops*—Maximum number of hops allowed for the trace; default value is 64.
  - *detailed*—Provides a detailed description of the trace, rather than a summary

**Mode** Privileged Exec, User Exec

## mtu

---

**Syntax**    `mtu mtuSize`

`no mtu`

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Sets the maximum allowable size in bytes of the maximum transmission unit for interfaces on cOCx/STMx, CT3, COCX-F3, Ethernet, or POS modules. The **no** version restores the default value, which varies according to module type. This command is not available for the Ethernet interface on the SRP module.

- Options**
- *mtuSize*—Maximum allowable size of the MTU; default and range varies with interface type:
    - Interfaces on cOCx/STMx, CT3, and COCX-F3 modules—Number in the range 4–9996; default value is 1600
    - Interfaces on Ethernet modules—Number in the range 64–9188, except on the FE-2 and FE-8 I/O modules, where the range is 64–9042; you cannot configure MTU on Ethernet interfaces on the SRP module; default value is 1518
    - Interfaces on POS modules—Number in the range 1–9996; default value is 4470

**Mode**    Interface Configuration

---

## multicast

---

**Syntax** multicast { permit | deny }

no multicast

**Release Information** Command introduced before JunosE Release 7.1.0.

**Description** Modifies the subscriber policy for the multicast protocol to define whether the subscriber (client) interfaces that belong to a bridge group or to a VPLS instance forward (permit) or filter (deny) multicast packets. The **no** version restores the default value, permit multicast packets.

You cannot change the default subscriber policy values for trunk (server) interfaces that belong to a bridge group or to a VPLS instance. You also cannot change the default subscriber policy values for a VPLS virtual core interface, which acts as a trunk interface. The VPLS virtual core interface represents all of the MPLS tunnels from the router to the remote VPLS edge (VE) devices.

- Options**
- permit—Specifies that the subscriber interface associated with the bridge group or VPLS instance forwards multicast packets
  - deny—Specifies that the subscriber interface associated with the bridge group or VPLS instance filters multicast packets

**Mode** Subscriber Policy Configuration

## multicast group port limit

---

**Syntax**    multicast group port *interfaceSpecifier* limit *groupLimit*  
              no multicast group port *interfaceSpecifier* limit

**Release Information**    Command introduced before JunosE Release 7.1.0.

**Description**    Limits the number of IGMP or MLD groups that a port can accept. The **no** version restores the default situation, in which there is no limit to the number of IGMP or MLD groups the port can accept.

- Options**
- *interfaceSpecifier*—Particular interface; format varies according to interface type; see [Interface Types and Specifiers on page 5](#)
  - *groupLimit*—Maximum number of IGMP or MLD groups that an interface can accept in the range 0–64,000

**Mode**    Global Configuration

## PART 2

# Index

- [Index on page 1469](#)





# Index

## Symbols

10-Gigabit Ethernet interface.....	17
802.3ad Link Aggregation	
minimum member links.....	1345
802.3ah OAM link-fault management	
enabling on an interface.....	594

## A

### AAA commands

aaa accounting acct-stop on-aaa-failure.....	20
aaa accounting acct-stop on-access-deny.....	21
aaa accounting broadcast.....	22
aaa accounting commands.....	23
aaa accounting default.....	24
aaa accounting duplication.....	25
aaa accounting exec.....	26
aaa accounting immediate-update.....	27
aaa accounting interval.....	28
aaa accounting statistics.....	29
aaa accounting suppress null-username.....	30
aaa accounting vr-group.....	31
aaa authentication default.....	32
aaa authentication enable default.....	33
aaa authentication login.....	34
aaa authorization.....	35
aaa authorization config-commands.....	36
aaa delimiter.....	37
aaa dns.....	40
aaa duplicate-address-check.....	42
aaa duplicate-prefix-check.....	43
aaa duplicate-prefix-check-extension.....	44
aaa intf-desc-format include.....	45
aaa ipv6-dns.....	47
aaa local database.....	49
aaa local select database.....	50
aaa local username.....	51
aaa new-model.....	52
aaa parse-direction.....	53
aaa parse-order.....	54
aaa per profile configuration.....	56, 204
aaa per profile list name.....	57

aaa qos downstream rate.....	59
aaa route-download.....	60, 61
aaa route-download now.....	62, 63
aaa route-download suspend.....	64
aaa service accounting interval.....	65
aaa subscriber limit per-port.....	68
aaa subscriber limit per-vr.....	69
aaa timeout.....	70
aaa tunnel assignment-id-format.....	71
aaa tunnel calling-number-format.....	72
aaa tunnel	
calling-number-format-fallback.....	75
aaa tunnel client-name.....	77
aaa tunnel ignore.....	79
aaa tunnel nas-port-method.....	80
aaa tunnel password.....	81
aaa tunnel switch-profile.....	82
aaa tunnel tx-connect-speed-method.....	83
aaa tunnel-group.....	78
aaa user accounting interval.....	84
aaa virtual-router.....	85
aaa wins.....	86
accounting.....	89
authorization.....	212
baseline aaa.....	228
baseline aaa route-download.....	229
clear ip routes download.....	417
clear ipv6 routes download.....	431
login authentication.....	1277
aaa commands	
aaa per profile configuration.....	55
AAA domain map commands	
aaa domain-map.....	41
auth-router-name.....	213
ip-router-name.....	950
ipv6-local-interface.....	1056
local-interface.....	1258
AAA profile commands	
aaa profile.....	58
allow.....	123
deny.....	520
ANCP commands	
adjustment-factor.....	117
baseline l2c.....	359
clear l2c discovery-table.....	436
clear l2c neighbor.....	437
gsmpp-syn-timeout.....	690
id.....	708
l2c.....	1174

l2c end-user-id.....	1175	atm ilmi-enable.....	183
l2c ip listen.....	1176	atm ilmi-keepalive.....	184
l2c ip oif .....	1177	atm lbo.....	185
l2c line-configuration.....	1178	atm mcpt-timers.....	186
l2c max-branches.....	1179	atm oam.....	187
l2c peer-attachment-id.....	1181	atm oam flush.....	188
max-branches.....	1318	atm oam loopback-location.....	189
max-discovery-table-entries.....	1319	atm pvc.....	192
APS/MSP commands		atm shutdown.....	195
aps force.....	127	atm snmp trap link-status.....	196
aps group.....	128	atm sonet stm-1.....	197
aps lockout.....	129	atm uni-version.....	198
aps manual.....	130	atm vc-per-vp.....	199
aps protect.....	131	atm vp-description.....	200
aps revert.....	132	atm vp-tunnel.....	203
aps unidirectional.....	133	atm-vp qos-parameter.....	201
aps working.....	134	atm-vp qos-profile.....	202
ARP commands		auto-configure.....	215
arp.....	153	auto-configure atm1483.....	216
arp spoof-check.....	154	baseline atm vp interface.....	230
arp timeout.....	155	baseline interface atm.....	240
clear arp.....	374	cbr.....	365
ip proxy-arp.....	933	class-int.....	370
ATM 1483 subinterface.....	6, 13	class-vc.....	371
ATM commands		ds3-scramble.....	561
atm.....	157	e3-scramble.....	568
atm aal5 description.....	158	encapsulation.....	576
atm aal5 shutdown.....	159	inarp.....	722
atm aal5 snmp trap link-status.....	160	interface atm.....	732
atm atm1483 advisory-rx-speed.....	161	ip atm-vc.....	760
atm atm1483 auto-configure.....	162	load-interval.....	1255
atm atm1483 description.....	163	loopback.....	1279
atm atm1483		map-group.....	1288
export-subinterface-description.....	164	map-list.....	1289
atm atm1483 mtu.....	165	monitor atm vc.....	1355
atm atm1483 profile.....	166	monitor atm vp.....	1356
atm atm1483 shutdown.....	167	ATM interface.....	6, 13
atm atm1483 snmp trap link-status.....	168		
atm atm1483 subscriber.....	169	<b>B</b>	
atm auto-configuration.....	170	B-RAS commands	
atm bulk-config.....	171	aaa accounting acct-stop on-aaa-failure.....	20
atm bulk-config modify.....	172	aaa accounting acct-stop on-access-deny.....	21
atm bulk-config shutdown.....	173	aaa accounting broadcast.....	22
atm cac.....	174	aaa accounting commands.....	23
atm cell-packing.....	175	aaa accounting default.....	24
atm class-vc.....	178	aaa accounting duplication.....	25
atm clock internal.....	179	aaa accounting exec.....	26
atm description.....	180	aaa accounting immediate-update.....	27
atm framing.....	182	aaa accounting interval.....	28

aaa accounting statistics.....	29	baseline aaa.....	228
aaa accounting suppress null-username.....	30	baseline aaa route-download.....	229
aaa accounting vr-group.....	31	baseline cops.....	235
aaa authentication default.....	32	baseline dhcp.....	236
aaa delimiter.....	37	baseline local pool.....	267
aaa dhcpv6-delegated-prefix		baseline radius.....	276
delegated-ipv6-prefix.....	38	baseline radius dynamic-request.....	277
aaa dns.....	40	baseline radius relay.....	278
aaa domain-map.....	41	baseline ssc.....	282
aaa duplicate-address-check.....	42	baseline tacacs.....	284
aaa duplicate-prefix-check.....	43	bridge1483 service-profile.....	324
aaa duplicate-prefix-check-extension.....	44	clear ip demux.....	396
aaa intf-desc-format include.....	45	clear ip routes download.....	417
aaa ipv6-dns.....	47	clear ipv6 routes download.....	431
aaa ipv6-nd-ra-prefix framed-ipv6-prefix.....	48	deadtime.....	490
aaa local database.....	49	deny.....	520
aaa local select database.....	50	dhcp delete-binding.....	522
aaa local username.....	51	dhcp-external delete-binding.....	525
aaa parse-direction.....	53	dhcp-external duplicate-mac-address.....	526
aaa parse-order.....	54	dhcpv6 delete-binding.....	527
aaa per profile configuration.....	55, 56, 204	domain.....	549
aaa per profile list name.....	57	grace-period.....	683
aaa profile.....	58	include circuit-identifier.....	723
aaa qos downstream rate.....	59	include dhcp-option 82.....	724
aaa route-download.....	60, 61	include hostname.....	725
aaa route-download now.....	62, 63	include ip-address.....	726
aaa route-download suspend.....	64	include mac-address.....	727
aaa service accounting interval.....	65	include virtual-router-name.....	728
aaa subscriber limit per-port.....	68	ip address-pool.....	753
aaa subscriber limit per-vr.....	69	ip auto-configure	
aaa timeout.....	70	append-virtual-router-name.....	761
aaa tunnel assignment-id-format.....	71	ip auto-configure ip-subscriber.....	762
aaa tunnel calling-number-format.....	72	ip auto-detect ip-subscriber.....	763
aaa tunnel		ip dhcp-capture.....	776
calling-number-format-fallback.....	75	ip dhcp-external auto-configure.....	777
aaa tunnel client-name.....	77	ip dhcp-external	
aaa tunnel ignore.....	79	disregard-giaddr-next-hop.....	778
aaa tunnel nas-port-method.....	80	ip dhcp-external	
aaa tunnel password.....	81	recreate-subscriber-interface.....	779
aaa user accounting interval.....	84	ip dhcp-external server-address.....	780
aaa virtual-router.....	85	ip dhcp-external server-sync.....	781
aaa wins.....	86	ip dhcp-server.....	793
accounting.....	89	ip inactivity-timer.....	857
address.....	95	ip local alias.....	861
address-pool-name.....	111	ip local pool.....	862
allow.....	123	ip local pool snmpTrap.....	863
auth-router-name.....	213	ip local pool warning.....	864
authorization change.....	213	ip local shared-pool.....	865
backup-address-pool-name.....	224		

ip re-authenticate-auto-detect		bgp fast-external-fallover.....	302
ip-subscriber.....	934	bgp graceful-restart.....	303
ip route-map ip-subscriber.....	947	bgp graceful-restart	
ip service-profile.....	960	path-selection-defer-time-limit.....	304
ip use-framed-routes ip-subscriber.....	983	bgp graceful-restart restart-time.....	305
ip-hint.....	823	bgp graceful-restart stalepaths-time.....	306
ip-router-name.....	950	bgp log-neighbor-changes.....	307
ipv6-ndra-pool-name.....	1098	bgp maxas-limit.....	308
ipv6-prefix-pool-name.....	1132	bgp redistribute-internal.....	309
ipv6-router-name.....	1136	bgp router-id.....	310
key.....	1170	bgp shutdown.....	311
l2tp rx-connect-speed-when-equal.....	1210	bgp wait-on-end-of-rib.....	312
license b-ras.....	1237	check-vpn-next-hops.....	368
logout subscribers.....	1278	clear access-list.....	373
loopback.....	1279	clear bgp ipv6.....	377
max-sessions.....	1326	clear bgp ipv6 dampening.....	378
medium ipv4.....	1334	clear bgp ipv6 dynamic-peers.....	380
radius per profile configuration.....	90, 205	clear bgp ipv6 redistribution.....	381
BFD commands		clear bgp ipv6 wait-end-of-rib.....	381
address bfd-liveness-detection.....	102	clear ip bgp.....	389
clear ipv6 bfd session.....	420	clear ip bgp dampening.....	391
ip ospf bfd-liveness-detection.....	899	clear ip bgp dynamic-peers.....	393
ip pim bfd-liveness-detection.....	910	clear ip bgp redistribution.....	394
ip rip bfd-liveness-detection.....	940	clear ip bgp wait-end-of-rib.....	395
ip route.....	944	clear ip routes.....	416
ipv6 ospf bfd-liveness-detection.....	1104	clear ip tunnel-routes.....	418
ipv6 pim bfd-liveness-detection.....	1114	clear ipv6 access-list.....	419
isis bfd-liveness-detection.....	1147	clear ipv6 routes.....	430
license bfd.....	1236	clear ipv6 tunnel-routes.....	432
mpls rsvp bfd-liveness-detection.....	1430	debug ip bgp.....	494
BGP commands		debug ip mbgp.....	496
address-family.....	105	default-fields peer.....	509
aggregate-address.....	120	default-fields route.....	511
auto-summary.....	220	default-information originate.....	513
baseline ip bgp.....	242	disable-dynamic-redistribute.....	533
bgp advertise-best-external-to-internal.....	288	distance bgp.....	541
bgp advertise-inactive.....	289	exit-address-family.....	629
bgp always-compare-med.....	290	export map.....	633
bgp bestpath med confed.....	291	external-paths.....	636
bgp bestpath missing-as-worst.....	292	global export map.....	676
bgp client-to-client reflection.....	293	global import map.....	677
bgp cluster-id.....	294	import map.....	721
bgp confederation identifier.....	295	ip as-path access-list.....	758
bgp confederation peers.....	296	ip bgp-community new-format.....	764
bgp dampening.....	297	ip bgp-confed-as-set new-format.....	765
bgp default ipv4-unicast.....	298	ip community-list.....	771
bgp default local-preference.....	299	ip extcommunity-list.....	811
bgp default route-target filter.....	300	ip fallback global.....	812
bgp enforce-first-as.....	301	ip route parent-router.....	944

ip route vrf.....	944	ipv6 share-interface.....	1142
ip route-type.....	948	match mpls-label.....	1312
ip vrf.....	985	maximum routes.....	1321
ip vrf forwarding.....	986	maximum-paths.....	1320
match as-path.....	1300	mpls topology-driven-lsp.....	1446
match community.....	1301	neighbor activate.....	312
match distance.....	1301	BGP/MPLS VPNs commands	
match extcommunity.....	1303	external-paths.....	636
match ip address.....	1304	booting commands	
match ip next-hop.....	1305	boot backup.....	314
match level.....	1309	boot config.....	315
match metric.....	1310	boot force-backup.....	316
match metric-type.....	1311	boot hotfix.....	317
match mpls-label.....	1312	boot revert-tolerance.....	318
match policy-list.....	1313	boot revert-tolerance never.....	319
match route-type.....	1314	boot subsystem.....	320
match tag.....	1316	boot system.....	321
maximum routes.....	1321	check-disk.....	367
maximum-paths.....	1320	delete.....	518
bgp commands		flash-disk compare.....	643
match description.....	1466	flash-disk duplicate.....	644
BGP/MPLS VPN commands		flash-disk initialize.....	645
address-family.....	105	flash-disk scan.....	646
bgp default route-target filter.....	300	mount.....	1360
bgp wait-on-end-of-rib.....	312	bridged Ethernet commands	
check-vpn-next-hops.....	368	bridge1483 mtu.....	323
clear ip routes vrf.....	416	bridge1483 service-profile.....	324
clear ip tunnel-routes vrf.....	418	encapsulation bridge1483.....	577
clear ipv6 routes vrf.....	430	ip mac-validate.....	866
clear ipv6 tunnel-routes vrf.....	432	bridged IP commands	
debug ip mbgp.....	496	encapsulation bridge1483.....	577
default-information originate.....	513	bridging commands	
domain-id.....	552	arp.....	153
domain-tag.....	557	baseline bridge.....	231
dont-install-routes.....	558	baseline bridge interface.....	232
exit-address-family.....	629	bridge.....	325
export map.....	633	bridge acquire.....	326
global export map.....	676	bridge address.....	327
global import map.....	677	bridge aging-time.....	329
import map.....	721	bridge crb.....	330
ip dynamic-interface-prefix.....	809	bridge learn.....	332
ip fallback global.....	812	bridge route.....	333
ip mpls forwarding-mode label-switched.....	876	bridge snmp-trap link-status.....	334
ip route parent-router.....	944	bridge subscriber-policy.....	335
ip route vrf.....	944	bridge-group.....	331
ip share-interface.....	961	broadcast.....	342
ip share-nexthop.....	962	clear bridge.....	383
ip vrf.....	985	clear bridge address.....	384
ip vrf forwarding.....	986	clear bridge interface.....	385

ip.....	748	<b>D</b>	
mpls.....	1361	default commands vs. no commands.....	3
multicast.....	1465	deprecated commands.....	4
<b>C</b>		DHCP commands	
Cisco HDLC commands		clear ip dhcp-local binding.....	397
baseline hdlc interface.....	239	ip dhcp-capture.....	776
encapsulation hdlc.....	579	ip dhcp-local auth domain.....	782
hdlc down-when-looped.....	695	ip dhcp-local auth include.....	783
hdlc keepalive.....	696	ip dhcp-local auth password.....	784
hdlc shutdown.....	697	ip dhcp-local auth user-prefix.....	785
CLI commands. See user interface commands		DHCP external server commands	
CLNS commands		dhcp-external duplicate-mac-address.....	526
clns configuration-time.....	446	ip dhcp-external recreate-subscriber	
clns holding-time.....	447	interface.....	779
clns host.....	448	DHCP local server commands	
COCX-F3 commands		ip dhcp-local	
interface serial.....	744	auto-configureagent-circuit-identifier.....	786
cOCx/STMx commands		ip dhcp-local cable-modem.....	787
baseline path interface sonet.....	273	ip dhcp-local snmp Traps.....	791
baseline section interface sonet.....	279	link.....	1249
controller sonet.....	474	DHCPv6 local server commands	
crc.....	484	ipv6 dhcpv6-local auth domain.....	1039
interface serial.....	744	ipv6 dhcpv6-local auth include.....	1040
loopback.....	1279	ipv6 dhcpv6-local auth password.....	1041
mru.....	1462	ipv6 dhcpv6-local auth user-prefix.....	1042
mtu.....	1464	ipv6 dhcpv6-local delegated-prefix.....	1043
cOCx/STMx commands and OCx/STMx commands		ipv6 dhcpv6-local dns-domain-search.....	1044
description.....	521	ipv6 dhcpv6-local dns-server.....	1045
conventions		ipv6 dhcpv6-local duid.....	1046
notice icons.....	xxxvii	ipv6 dhcpv6-local prefix-lifetime.....	1047
text and syntax.....	xxxviii	D diagnostic commands	
CT3 commands		diag.....	528
bert.....	286	diag-level.....	529
crc.....	484	digital certificate commands	
description.....	521	common-name.....	463
equipment loopback.....	590	country.....	483
idle-character.....	710	crl.....	485
invert data.....	747	domain-name.....	555
loopback.....	1279	enrollment retry-limit.....	587
mdl carrier.....	1327	enrollment retry-period.....	588
mdl string.....	1328	enrollment url.....	589
mdl transmit.....	1329	ike crl.....	715
mru.....	1462	ipsec ca authenticate.....	1007
mtu.....	1464	ipsec ca enroll.....	1008
customer support.....	xxxix	ipsec ca identity.....	1009
contacting JTAC.....	xxxix	ipsec certificate-database refresh.....	1010
		ipsec certificate-request generate.....	1011
		ipsec crl .....	1013
		ipsec identity.....	1014

- 
- ipsec key generate .....1017
  - ipsec key pubkey-chain rsa.....1019
  - ipsec key zeroize.....1020
  - issuer-identifier.....1163
  - key-string.....1172
  - DNS commands
    - ip domain-lookup.....796
    - ip domain-name.....797
    - ip name-server.....885
  - documentation set
    - comments on.....xxxix
  - DoS protection group commands
    - atm dos-protection-group.....181
    - bridge1483 dos-protection-group.....322
    - dos-protection-group.....559
    - ethernet dos-protection-group.....593
    - frame-relay dos-protection-group.....655
    - hdlc dos-protection-group.....694
    - ip dos-protection-group.....798
    - ipv6 dos-protection-group.....1048
    - lag dos-protection-group.....1234
  - DVMRP commands
    - baseline ip dvmrp.....245
    - clear ip dvmrp routes.....398
    - disable.....531
    - disable-dynamic-redistribute.....533
    - dvmrp destination profile.....566
    - ip dvmrp.....799
    - ip dvmrp accept-filter.....800
    - ip dvmrp announce-filter.....801
    - ip dvmrp auto-summary.....802
    - ip dvmrp disable.....803
    - ip dvmrp metric-offset.....804
    - ip dvmrp route-limit.....806
    - ip dvmrp routehog-notification.....805
    - ip dvmrp summary-address.....807
    - ip dvmrp unicast-routing.....808
  - dynamic interface commands
    - atm atm1483 advisory-rx-speed.....161
    - atm atm1483 auto-configure.....162
    - atm atm1483 description.....163
    - atm atm1483 profile.....166
    - atm atm1483 subscriber.....169
    - atm bulk-config.....171
    - atm bulk-config modify.....172
    - atm bulk-config shutdown.....173
    - atm pvc.....192
    - auto-configure.....215
    - auto-configure atm1483.....216
    - auto-configure vlan.....217
  - E**
    - E120 routers
      - interface types and specifiers.....13
    - E3 commands
      - atm framing.....182
      - clock source.....450
      - controller e3.....473
      - crc.....484
      - description.....521
      - framing.....670
      - load-interval.....1255
      - loopback.....1279
      - mru.....1462
      - mtu.....1464
    - E320 routers
      - interface types and specifiers.....13
    - ERX14xx models
      - interface types and specifiers.....5
    - ERX310 router
      - interface types and specifiers.....5
    - ERX7xx models
      - interface types and specifiers.....5
    - Ethernet commands
      - baseline interface fastEthernet.....240
      - baseline interface gigabitEthernet.....240
      - debounce.....491
      - debounce-interval.....492
      - duplex.....565
      - ethernet description.....592
      - interface fastEthernet.....734
      - interface gigabitEthernet.....735
      - interface lag.....738
      - interface tenGigabitEthernet.....745
      - ip mac-validate.....866
      - lacp.....1232
      - lacp port-priority.....1233
      - link-fault management
        - ethernet oam lfm.....594
        - ethernet oam lfm high-threshold.....595
        - ethernet oam lfm link-monitor
          - frame-seconds.....596
          - ethernet oam lfm link-monitor
            - frame-seconds-summary.....598
            - ethernet oam lfm link-monitor
              - symbol-period.....600
              - ethernet oam lfm mode.....602

ethernet oam lfm		
pdu-lost-threshold.....	603	
ethernet oam lfm pdu-transmit-interval		
.....	604	
ethernet oam lfm remote-failure.....	605	
ethernet oam lfm remote-loopback.....	606	
ethernet oam lfm remote-loopback		
supported.....	607	
member-interface.....	1336	
monitor vlan interface.....	1357	
mtu.....	1464	
Event Manager commands		
boolean-test.....	313	
existence-test.....	627	
<b>F</b>		
Fast Ethernet commands		
load-interval.....	1255	
Fast Ethernet interface.....	7, 14	
file management commands		
copy.....	477	
copy running-configuration.....	479	
copy running-configuration		
startup-configuration.....	480	
copy startup-configuration.....	481	
host.....	703	
hotfix activate.....	705	
filtering show commands.....	4	
flow statistics commands		
cache entries.....	363	
cache timeout.....	364	
enabled.....	571	
export destination.....	632	
export source.....	634	
ip flow statistics.....	819	
ip flow-aggregation cache .....	814	
ip flow-cache entries.....	815	
ip flow-cache timeout.....	816	
ip flow-export.....	817	
ip flow-sampling-mode packet-interval.....	818	
mask destination.....	1296	
mask source.....	1298	
Frame Relay commands		
baseline frame-relay interface.....	237	
encapsulation frame-relay ietf.....	578	
frame-relay class.....	652	
frame-relay description.....	654	
frame-relay fragment.....	656	
frame-relay interface-dlci ietf.....	657	
frame-relay intf-type.....	658	
frame-relay keepalive.....	659	
frame-relay lmi-n391dte.....	660	
frame-relay lmi-n392dce.....	661	
frame-relay lmi-n392dte.....	662	
frame-relay lmi-n393dce.....	663	
frame-relay lmi-n393dte.....	664	
frame-relay lmi-t391dte.....	665	
frame-relay lmi-t392dce.....	666	
frame-relay lmi-type.....	667	
map-class frame-relay.....	1287	
FTP client commands		
ip ftp source-address.....	820	
ip ftp source-interface.....	821	
FTP server commands		
delete.....	518	
ftp-server enable.....	672	
ftp-server flush.....	673	
<b>G</b>		
GE port redundancy commands		
link failover arp-flush.....	1250	
link failover force.....	1251	
link failover timeout.....	1252	
link selection.....	1253	
Gigabit Ethernet interface.....	8, 14	
GRE commands		
gre destination profile.....	684	
gre-tunnel classifier-list.....	686	
gre-tunnel policy.....	687	
gre-tunnel policy-list.....	688	
<b>H</b>		
HDLN commands, Cisco		
baseline hdlc interface.....	239	
encapsulation hdlc.....	579	
hdlc down-when-looped.....	695	
hdlc keepalive.....	696	
hdlc shutdown.....	697	
HTTP local server commands		
baseline ip http.....	246	
ip http.....	824	
ip http access-class.....	825	
ip http max-connection-time.....	826	
ip http port.....	827	
ip http redirectUrl.....	828	
ip http same-host-limit.....	829	
ip http server.....	830	
ipv6 http.....	1051	



- 
- ipv6 http port.....1052
  - ipv6 http redirectUrl.....1053
  - ipv6 http server.....1054
- I**
- ICMP commands
    - ip icmp update-source.....831
  - ICR commands
    - ip vrrp icr-partition.....993
    - ip vrrp icr-partition group.....994
    - ip vrrp icr-partition svlan-list.....995
    - ip vrrp icr-partition vlan-list.....999
    - ip vrrp icr-partition vlan-range.....1000
  - IEEE 802.3ad link aggregation group
    - interface.....8, 14
  - IEEE 802.3ah OAM link-fault management
    - enabling on an interface.....594
  - IGMP commands.....842
    - baseline ip igmp.....247
    - baseline ip igmp-proxy interface.....248
    - igmp disable.....711
    - igmp promiscuous.....712
    - ip igmp.....832
    - ip igmp access-group.....833
    - ip igmp access-source-group.....834
    - ip igmp apply-oif-map.....835
    - ip igmp explicit-tracking.....835
    - ip igmp group limit.....837
    - ip igmp immediate-leave.....838
    - ip igmp last-member query-interval.....839
    - ip igmp oif-map.....840
    - ip igmp promiscuous.....841
    - ip igmp querier.....845
    - ip igmp querier-timeout.....846
    - ip igmp query-interval.....847
    - ip igmp query-max-response-time.....848
    - ip igmp robustness.....849
    - ip igmp static-exclude.....852
    - ip igmp static-group.....853
    - ip igmp static-include.....854
    - ip igmp version.....855
    - ipv6 mld apply-oif-map.....1062
    - multicast group port limit.....1466
    - show ip igmp ssm-map enable.....850
    - show ip igmp ssm-map static.....851
    - See also IGMP proxy commands
  - IGMP proxy commands
    - ip igmp-proxy.....842
    - ip igmp-proxy unsolicited-report-interval.....843
    - ip igmp-proxy V1-router-present-time.....844
  - IKE commands
    - ike local-identity.....716
    - ike peer-identity.....720
    - ike peer-identity distinguished-name.....717
    - ike peer-identity domain-name.....718
    - ike peer-identity ip address.....719
  - interface commands
    - baseline interface serial.....240
    - baseline ip interface.....249
    - baseline ipv6 interface.....259
    - clear ip interface.....400
    - clear ipv6 interface.....421
    - clear ipv6 neighbors.....423
    - description.....521
    - interface.....731
    - interface ip.....736
    - interface ipv6.....737
    - interface loopback .....739
    - interface mlframe-relay.....740
    - interface mldppp.....741
    - interface null.....742
    - interface pos.....743
    - interface serial.....744
    - interface tunnel.....746
    - ip address.....751
    - ip alwaysup.....756
    - ip broadcast-address.....767
    - ip debounce-time.....772
    - ip description.....774
    - ip dynamic-interface-prefix.....809
    - ip redirects.....935
    - ip share-interface.....961
    - ip share-nexthop.....962
    - ip shutdown.....963
    - ip tcp adjust-mss.....978
    - ipv6 description.....1038
    - ipv6 share-interface.....1142
  - interface types and specifiers.....5
    - E120 routers.....13
    - E320 routers.....13
    - ERX14xx models.....5
    - ERX310 routers.....5
    - ERX7xx models.....5

## IP commands

arp.....	153
arp timeout.....	155
baseline ip.....	241
baseline ip tunnel-reassembly.....	254
baseline ip udp.....	255
baseline ip vrrp.....	256
baseline show-delta-counts.....	280
baseline tcp.....	285
clear access-list.....	373
clear arp.....	374
clear ip ospf database.....	406
clear ip ospf neighbor.....	407
clear ip prefix-list.....	412
clear ip prefix-tree.....	413
clear ip rip dynamic-interfaces.....	414
clear ip rip redistribution.....	415
clear ip routes.....	416
clear ip tunnel-routes.....	418
clear ipv6 access-list.....	419
distance.....	540
forwarding-table route-holddown.....	651
ip access-route table-map.....	750
ip access-routes.....	749
ip address.....	751
ip address-pool.....	753
ip alwaysup.....	756
ip analyzer.....	757
ip as-path access-list.....	758
ip auto-configure	
append-virtual-router-name.....	761
ip auto-configure ip-subscriber.....	762
ip auto-detect ip-subscriber.....	763
ip broadcast-address.....	767
ip community-list.....	771
ip debounce-time.....	772
ip demux-type da-prefix.....	773
ip description.....	774
ip destination-prefix.....	775
ip dhcp-capture.....	776
ip dhcp-external auto-configure.....	777
ip dhcp-external server-address.....	780
ip dhcp-external server-sync.....	781
ip dhcp-server.....	793
ip directed-broadcast.....	794
ip disable-forwarding.....	795
ip explicit-path.	
mpls explicit-path See MPLS commands	
ip extcommunity-list.....	811

ip gratuitous-arps.....	822
ip ignore-df-bit.....	856
ip inactivity-timer.....	857
ip initial-sequence-preference.....	858
ip interface.	
no ip interface See Command Reference	
Guide N to Z, IP commands	
ip irdp.....	860
ip local alias.....	861
ip local pool.....	862
ip local pool snmpTrap.....	863
ip local pool warning.....	864
ip local shared-pool.....	865
ip mac-validate.....	866
ip mask-reply.....	867
ip mirror.....	869
ip mtu.....	877
ip multipath round-robin.....	884
ip prefix-list.....	930
ip prefix-tree.....	931, 932
ip proxy-arp.....	933
ip re-authenticate-auto-detect	
ip-subscriber.....	934
ip redirects.....	935
ip refresh-route.....	936
ip rip commands. See RIP commands	
ip route.....	944
ip route-map ip-subscriber.....	947
ip router-id.....	949
ip rsvp bandwidth.	
mpls bandwidth See MPLS commands	
ip rsvp signalling hello graceful-restart	
recovery-time.	
mpls rsvp signalling hello graceful-restart	
recovery-time See MPLS commands	
ip rsvp signalling hello graceful-restart	
restart-time.	
mpls rsvp signalling hello graceful-restart	
restart-time See MPLS commands	
ip rsvp signalling hello graceful-restart.	
mpls rsvp signalling hello graceful-restart	
See MPLS commands	
ip rsvp signalling hello.	
mpls rsvp signalling hello See MPLS	
commands	
ip rsvp signalling node-hello.	
mpls rsvp signalling node-hello See MPLS	
commands	
ip sa-validate.....	958

- 
- ip sa-validate trap-enable.....959
  - ip shutdown.....963
  - ip source-prefix.....964
  - ip source-route.....965
  - ip speed.....966
  - ip ssh. *See* SSH commands
  - ip static-route table-map.....975
  - ip tcp adjust-mss.....978
  - ip ttl.....979
  - ip tunnel reassembly.....980
  - ip unnumbered.....981
  - ip unreachable.....982
  - ip virtual-router.....984
  - ip vrrp.....987
  - ip vrrp accept-data.....988
  - ip vrrp advertise-interval.....989
  - ip vrrp authentication-key.....990
  - ip vrrp authentication-type.....991
  - ip vrrp enable.....992
  - ip vrrp icr-partition.....993
  - ip vrrp icr-partition group.....994
  - ip vrrp icr-partition svlan-list.....995
  - ip vrrp icr-partition svlan-list explicit.....996
  - ip vrrp icr-partition svlan-range.....997
  - ip vrrp icr-partition vlan-list.....999
  - ip vrrp icr-partition vlan-range.....1000
  - ip vrrp preempt.....1002
  - ip vrrp priority.....1003
  - ip vrrp timers-learn.....1004
  - ip vrrp track.....1005
  - ip vrrp virtual-address.....1006
  - ip-hint.....823
  - ipv6 initial-sequence-preference.....1055
  - IP multicast commands
    - ip block-multicast-sources.....766
    - ip multicast admission-bandwidth-limit.....878
    - ip multicast-routing.....880
    - ip multicast-routing bandwidth-map.....881
    - ip multicast-routing disable-rpf-check.....882
    - ip multicast-routing permanent-mroute.....883
    - ip rpf-route.....952
    - ipv6 multicast
      - admission-bandwidth-limit.....1082
    - ipv6 multicast-routing bandwidth-map.....1085
    - mtrace.....1463
  - ip pim commands
    - ip pim sparse-mode
      - graceful-restart-duration.....922
  - IP TCP commands. *See* TCP commands
  - IPSec commands
    - aggressive-mode.....122
    - authentication.....206
    - encryption.....585
    - hash.....693
    - ip address virtual-router.....755
    - ipsec ca authenticate.....1007
    - ipsec ca enroll.....1008
    - ipsec ca identity.....1009
    - ipsec certificate-database refresh.....1010
    - ipsec certificate-request generate.....1011
    - ipsec clear sa.....1012
    - ipsec crl.....1013
    - ipsec identity.....1014
    - ipsec ike-policy-rule.....1015
    - ipsec isakmp-policy-rule.....1016
    - ipsec key generate.....1017
    - ipsec key manual pre-share.....1018
    - ipsec key pubkey-chain rsa.....1019
    - ipsec key zeroize.....1020
    - ipsec lifetime.....1021
    - ipsec local-endpoint.....1022
    - ipsec option dpd.....1023
    - ipsec option nat-t.....1024
    - ipsec option tx-invalid-cookie.....1025
    - ipsec transform-set.....1026
    - ipsec transport profile.....1027
    - ipsec tunnel profile.....1028
    - key.....1170
    - key-string.....1172
    - license ipsec-tunnels.....1238
    - license l2tp-session.....1241
    - lifetime.....1245
    - masked-key.....1297
  - IPSec identity commands
    - common-name.....463
    - country.....483
    - domain-name.....555
  - IPSec transport profile commands
    - application.....125
    - enable ipsec transport.....572
    - ipsec transport profile.....1027
    - lifetime.....1245
    - local ip address.....1259
  - IPSec tunnel commands
    - domain-suffix.....556
    - local ip identity.....1261
    - local ip network.....1262

IPSec tunnel profile commands		
ipsec tunnel profile.....	1028	
IPv6 commands		
baseline ipv6 tcp.....	264	
clear bgp ipv6.....	377	
clear bgp ipv6 dampening.....	378	
clear bgp ipv6 redistribution.....	381	
clear bgp ipv6 wait-end-of-rib.....	381	
clear ipv6 prefix-list.....	429	
clear ipv6 routes.....	430	
clear ipv6 tunnel-routes.....	432	
ipv6.....	1029	
ipv6 access-route table-map.....	1031	
ipv6 address.....	1032	
ipv6 description.....	1038	
ipv6 enable.....	1049	
ipv6 hop-limit.....	1050	
ipv6 mtu.....	1081	
ipv6 neighbor.....	1102	
ipv6 route.....	1133	
ipv6 sa-validate.....	1141	
ipv6 static-route table-map.....	1143	
ipv6 unnumbered.....	1144	
ipv6 virtual-router.....	1145	
license ipv6.....	1239	
IPv6 local address pool commands		
aaa dhcpv6-ndra-pool override.....	39	
baseline ipv6 local ndra-pool.....	260	
baseline ipv6 local pool.....	261	
dns-domain-search.....	545	
dns-server.....	547	
exclude-ndraprefix.....	622	
exclude-prefix.....	623	
ipv6 address-pool local.....	1033	
ipv6 address-pool ndra.....	1034	
ipv6 local ndra-pool.....	1057	
ipv6 local pool.....	1058	
ipv6-ndra-pool-name.....	1098	
ipv6-prefix-pool-name.....	1132	
IPv6 multicast commands		
ipv6 block-multicast-sources.....	1035	
ipv6 multicast-routing.....	1084	
ipv6 multicast-routing		
disable-rpf-check.....	1086	
ipv6 multicast-routing		
permanent-mroute.....	1087	
ipv6 rpf-route.....	1140	
IPv6 neighbor discovery commands		
ipv6 nd.....	1088	
ipv6 nd active-solicitations.....	1089	
ipv6 nd dad attempts.....	1090	
ipv6 nd managed-config-flag.....	1091	
ipv6 nd ns-interval.....	1092	
ipv6 nd other-config-flag.....	1093	
ipv6 nd prefix-advertisement.....	1094	
ipv6 nd proxy.....	1095	
ipv6 nd ra-interval.....	1096	
ipv6 nd ra-lifetime.....	1097	
ipv6 nd reachable-time.....	1099	
ipv6 nd suppress-ra.....	1100	
ipv6 nd suppress-ra-source-link-layer.....	1101	
IS-IS commands		
advertise-passive-only.....	118	
area-authentication.....	136	
area-authentication-key.....	137	
area-message-digest-key.....	139	
baseline clns.....	234	
clear ip isis redistribution.....	401	
clear isis adjacency.....	433	
clear isis database.....	434	
clear isis ipv6 redistribution.....	435	
clns configuration-time.....	446	
clns holding-time.....	447	
clns host.....	448	
debug isis.....	507	
default-information originate.....	513	
disable-dynamic-redistribute.....	533	
distance ip.....	542	
distribute-domain-wide.....	543	
domain-authentication.....	550	
domain-authentication-key.....	551	
domain-message-digest-key.....	553	
full-spf-always.....	674	
ignore-attached-bit.....	713	
ignore-lsp-errors.....	714	
ip route-type.....	948	
ip router isis.....	950	
ipv6 router isis.....	1134	
is-type.....	1167	
isis authentication-key.....	1146	
isis bfd-liveness-detection.....	1147	
isis circuit-type.....	1148	
isis csnp-interval.....	1149	
isis hello-interval.....	1150	
isis hello-multiplier.....	1151	
isis lsp-interval.....	1153	

isis mesh-group.....	1154	identification.....	709
isis message-digest-key.....	1155	l2tp checksum.....	1182
isis metric.....	1157	l2tp destination lockout-test.....	1184
isis network point-to-point.....	1158	l2tp destination lockout-timeout.....	1185
isis priority.....	1159	l2tp destination profile.....	1186
isis retransmit-interval.....	1160	l2tp destruct-timeout.....	1187
isis retransmit-throttle-interval.....	1161	l2tp dial-out connecting-timer-value.....	1188
isis tag.....	1162	l2tp dial-out dormant-timer-value.....	1189
log-adjacency-changes.....	1264	l2tp dial-out max-buffered-triggers.....	1190
lsp-gen-interval.....	1281	l2tp dial-out session delete.....	1191
lsp-mtu.....	1282	l2tp dial-out session reset.....	1192
lsp-refresh-interval.....	1283	l2tp dial-out target.....	1193
max-lsp-lifetime.....	1324	l2tp disable calling-number-avp.....	1194
maximum-paths.....	1320	l2tp disable challenge.....	1195
metric.....	1340	l2tp disconnect-cause.....	1196
metric-style narrow.....	1341	l2tp drain.....	1197
metric-style transition.....	1342	l2tp drain destination.....	1198
metric-style wide.....	1343	l2tp drain tunnel.....	1199
mpls ldp autoconfig.....	1378	l2tp fail-over-within-preference.....	1201
mpls ldp igp sync holdown.....	1388	l2tp failover-resync.....	1200
mpls ldp sync.....	1400	l2tp ignore-receive-data-sequencing.....	1202
mpls spf-use-any-best-path.....	1442	l2tp ignore-transmit-address-change.....	1203
mpls traffic-eng.....	1449	l2tp reject-transmit-address-change.....	1208
mpls traffic-eng router-id.....	1457	l2tp retransmission.....	1209
		l2tp shutdown.....	1211
		l2tp shutdown destination.....	1212
		l2tp shutdown session.....	1213
		l2tp shutdown tunnel.....	1214
		l2tp switch-profile.....	1215
		l2tp tunnel default-receive-window.....	1216
		l2tp tunnel idle-timeout.....	1217
		l2tp tunnel short-drain-timeout.....	1218
		l2tp tunnel test.....	1220
		l2tp tunnel-switching.....	1219
		l2tp unlock destination.....	1221
		l2tp unlock-test destination.....	1222
		l2tp weighted-load-balancing.....	1223
		local host.....	1257
		local ip address.....	1259
		max-sessions.....	1326
		medium ipv4.....	1334
		L2VPN commands	
		address-family.....	105
		LDP commands	
		clear mpls ldp.....	441
		hello hold-time.....	698
		hello interval.....	699
		mpls ldp.....	1376
		mpls ldp advertise-labels.....	1377
<b>J</b>			
J-Flow commands			
clear ip flow stats.....	399		
<b>L</b>			
L2TP commands			
aaa tunnel assignment-id-format.....	71		
aaa tunnel calling-number-format.....	72		
aaa tunnel			
calling-number-format-fallback.....	75		
aaa tunnel switch-profile.....	82		
aaa tunnel tx-connect-speed-method.....	83		
aaa tunnel-group.....	78		
address.....	95		
avp.....	222		
bundled-group-id.....	358		
bundled-group-id-overrides-mlppp-ed.....	359		
client-name.....	445		
default-upper-type mlppp.....	517		
disable proxy lcp.....	535		
disconnect-cause.....	537		
enable ipsec-transport.....	572		
enable proxy authenticate.....	574		
failover-resync.....	641		

mpls ldp deaggregate.....	1379	ethernet oam lfm remote-loopback.....	606
mpls ldp disable.....	1380	ethernet oam lfm remote-loopback	
mpls ldp discovery transport-address.....	1381	supported.....	607
mpls ldp egress-label.....	1382	local user database commands	
mpls ldp graceful-restart.....	1383	aaa authentication default.....	32
mpls ldp graceful-restart		aaa local database.....	49
reconnect-time.....	1384	aaa local select database.....	50
mpls ldp graceful-restart		aaa local username.....	51
recovery-timer.....	1385	ip-address.....	752
mpls ldp graceful-restart timers		ip-address-pool.....	754
max-recovery.....	1386	loopback interface.....	8
mpls ldp graceful-restart timers			
neighbor-liveness.....	1387	<b>M</b>	
mpls ldp independent-control.....	1389	manuals	
mpls ldp ip-forwarding.....	1390	comments on.....	xxxix
mpls ldp link-hello disable.....	1391	mirror commands	
mpls ldp neighbor password.....	1392	mirror.....	1346
mpls ldp profile.....	1393	mirror analyzer-ip-address.....	1348
mpls ldp redistribute.....	1394	mirror disable.....	1349
mpls ldp session holdtime.....	1395	mirror trap-enable.....	1352
mpls ldp session keepalive interval.....	1396	mirror-enable.....	1351
mpls ldp session retries.....	1397	MLD commands.....	1068
mpls ldp session retry-time.....	1398	baseline ipv6 mld.....	262
mpls ldp strict security.....	1399	baseline ipv6 mld-proxy interface.....	263
mpls ldp targeted-hello holdtime.....	1401	ip mld oif-map.....	1067
mpls ldp targeted-hello interval.....	1402	ipv6 mld.....	1059
mpls ldp targeted-hello receive list.....	1403	ipv6 mld access-group.....	1060
mpls ldp targeted-hello send list.....	1404	ipv6 mld access-source-group.....	1061
mpls topology-driven-lsp.....	1446	ipv6 mld explicit-tracking.....	1062
link aggregation commands		ipv6 mld group limit.....	1064
interface lag.....	738	ipv6 mld immediate-leave.....	1065
lacp.....	1232	ipv6 mld last-member query-interval.....	1066
lacp port-priority.....	1233	ipv6 mld querier-timeout.....	1071
member-interface.....	1336	ipv6 mld query-interval.....	1072
link aggregation group interface, IEEE		ipv6 mld query-max-response-time.....	1073
802.3ad.....	8, 14	ipv6 mld robustness.....	1074
link-fault management commands		ipv6 mld ssm-map enable.....	1075
ethernet oam lfm.....	594	ipv6 mld ssm-map static.....	1076
ethernet oam lfm high-threshold.....	595	ipv6 mld static-exclude.....	1077
ethernet oam lfm link-monitor		ipv6 mld static-group.....	1078
frame-seconds.....	596	ipv6 mld static-include.....	1079
ethernet oam lfm link-monitor		ipv6 mld version.....	1080
frame-seconds-summary.....	598	ipv6 mld-proxy version.....	1070
ethernet oam lfm link-monitor		ipv6 router mld.....	1135
symbol-period.....	600	mld disable.....	1353
ethernet oam lfm mode.....	602	See also MLD proxy commands	
ethernet oam lfm pdu-lost-threshold.....	603		
ethernet oam lfm pdu-transmit-interval .....	604		
ethernet oam lfm remote-failure.....	605		

- 
- MLD proxy commands
    - ipv6 mld-proxy.....1068
    - ipv6 mld-proxy
      - unsolicited-report-interval.....1069
  - MLFR commands
    - baseline frame-relay interface.....237
    - baseline frame-relay multilink interface.....238
    - encapsulation mlframe-relay ietf.....580
    - frame-relay interface-dlci ietf.....657
    - frame-relay intf-type.....658
    - frame-relay keepalive.....659
    - frame-relay lmi-n391dte.....660
    - frame-relay lmi-n392dce.....661
    - frame-relay lmi-n392dte.....662
    - frame-relay lmi-n393dce.....663
    - frame-relay lmi-n393dte.....664
    - frame-relay lmi-t391dte.....665
    - frame-relay lmi-t392dce.....666
    - frame-relay lmi-type.....667
    - interface mlframe-relay.....740
    - member-interface.....1336
  - MLPPP commands
    - encapsulation mlppp.....581
    - interface mlppp.....741
    - member-interface.....1336
  - Mobile IP commands
    - baseline ip mobile home-agent.....250
    - clear ip mobile binding.....402
    - ip mobile home-agent.....870
    - ip mobile host.....871
    - ip mobile profile.....872
    - ip mobile secure foreign-agent.....873
    - ip mobile secure host.....874
  - MPLS commands.....1361
    - append-after.....124
    - bandwidth.....225
    - baseline mpls interface.....269
    - baseline mpls label.....270
    - baseline mpls next-hop.....271
    - baseline mpls tunnel.....272
    - cleanup-timeout-factor.....372
    - clear mpls dynamic-interfaces
      - on-major-interfaces.....440
    - clear mpls ldp.....441
    - clear rsvp authentication.....443
    - hello hold-time.....698
    - hello interval.....699
    - index.....729
    - interface tunnel.....746
    - ip explicit-path. *See* mpls explicit-path
    - ip rsvp authentication key. *See* mpls rsvp authentication key
    - ip rsvp authentication. *See* mpls rsvp authentication
    - ip rsvp bandwidth. *See* mpls bandwidth
    - ip rsvp bfd-liveness-detection. *See* mpls rsvp bfd-liveness-detection
    - ip rsvp signalling hello. *See* mpls rsvp signalling hello
    - list.....1254
    - mark-exp.....1294
    - member interface.....1335
    - mpls.....1361
    - mpls atm vci range.....1363
    - mpls atm vpi range.....1364
    - mpls backup-path.....1365
    - mpls bandwidth.....1366
    - mpls classifier-list.....1367
    - mpls copy-upc-to-exp.....1368
    - mpls create-dynamic-interfaces.....1369
    - mpls diff-serv phb-id traffic-class.....1370
    - mpls disable.....1371
    - mpls explicit-path.....1372
    - mpls ip propagate-ttl.....1373
    - mpls l2transport load-balancing-group.....1374
    - mpls ldp.....1376
    - mpls ldp advertise-labels.....1377
    - mpls ldp autoconfig.....1378
    - mpls ldp deaggregate.....1379
    - mpls ldp disable.....1380
    - mpls ldp discovery transport-address.....1381
    - mpls ldp egress-label.....1382
    - mpls ldp graceful-restart.....1383
    - mpls ldp graceful-restart
      - reconnect-time.....1384
    - mpls ldp graceful-restart
      - recovery-timer.....1385
    - mpls ldp graceful-restart timers
      - max-recovery.....1386
    - mpls ldp graceful-restart timers
      - neighbor-liveness.....1387
    - mpls ldp igp sync holddown.....1388
    - mpls ldp independent-control.....1389
    - mpls ldp ip-forwarding.....1390
    - mpls ldp link-hello disable.....1391
    - mpls ldp neighbor password.....1392
    - mpls ldp profile.....1393
    - mpls ldp redistribute.....1394



mpls ldp session holdtime.....	1395
mpls ldp session keepalive interval.....	1396
mpls ldp session retries.....	1397
mpls ldp session retry-time.....	1398
mpls ldp strict security.....	1399
mpls ldp sync.....	1400
mpls ldp targeted-hello holdtime.....	1401
mpls ldp targeted-hello interval.....	1402
mpls ldp targeted-hello receive list.....	1403
mpls ldp targeted-hello send list.....	1404
mpls lsp no-route retries.....	1407
mpls lsp no-route retry-time.....	1408
mpls lsp retries.....	1409
mpls lsp retry-time.....	1410
mpls match exp-bits.....	1411
mpls match traffic-class.....	1412
mpls policy-list.....	1414
mpls policy-statistics.....	1417
mpls preserve-vpn-exp.....	1418
mpls reoptimize.....	1425
mpls reoptimize timers frequency.....	1426
mpls rsvp.....	1427
mpls rsvp authentication.....	1428
mpls rsvp authentication key.....	1429
mpls rsvp bfd-liveness-detection.....	1430
mpls rsvp disable.....	1431
mpls rsvp egress-label.....	1432
mpls rsvp message-bundling.....	1433
mpls rsvp profile.....	1434
mpls rsvp refresh-reduction.....	1435
mpls rsvp signalling hello.....	1436
mpls rsvp signalling hello graceful-restart.....	1437
mpls rsvp signalling hello graceful-restart recovery-time.....	1438
mpls rsvp signalling hello graceful-restart restart-time.....	1439
mpls rsvp signalling node-hello.....	1440
mpls signaling-interface.....	1441
mpls statistics label.....	1443
mpls statistics next-hop.....	1444
mpls statistics policy.....	1445
mpls topology-driven-lsp.....	1446
mpls topology-driven-lsp ip-interfaces.....	1447
mpls traffic-class.....	1448
mpls traffic-eng administrative-weight.....	1450
mpls traffic-eng attribute-flags.....	1452
mpls traffic-eng egress-label. See mpls rsvp egress-label	

mpls traffic-eng flood thresholds.....	1454
mpls traffic-eng link-management timers periodic-flooding.....	1455
mpls tunnel-model.....	1458
mpls tunnels profile.....	1459
mpls-relay.....	1419
mpls-relay atm cell-packing mcpt-timer.....	1422
mpls-relay atm vpi-range vci-range.....	1423
mpls-relay disable.....	1424
See also LDP commands, MPLS (IS-IS) commands, MPLS (OSPF) commands, RSVP-TE commands	
MPLS commands (IS-IS)	
mpls spf-use-any-best-path.....	1442
mpls traffic-eng.....	1449
mpls traffic-eng router-id.....	1457
MPLS commands (OSPF)	
mpls traffic-eng area.....	1451
mpls traffic-eng multicast-intact.....	1456
mpls traffic-eng router-id.....	1457
Multicast command	
mroute port admission-bandwidth-limit.....	1460
mroute port limit.....	1461
Multilink Frame Relay commands. See MLFR commands	
multilink frame relay interface.....	8
multilink PPP interface.....	8

## N

NAT commands	
baseline ip nat.....	251
clear ip nat translation.....	404
ip nat.....	886
ip nat inside source list.....	887
ip nat inside source static.....	888
ip nat outside source list.....	889
ip nat outside source static.....	890
ip nat pool.....	891
ip nat translation.....	892
ip nat translation max-entries.....	893
license nat.....	1243
NFS commands	
host.....	703
ip nfs.....	894
ip nfs host.....	895
no commands vs. default commands.....	3
non-PPP equal access commands	
baseline ip dhcp-local.....	244
baseline ipv6 dhcpv6-local.....	258



default-router .....	516	area virtual-link authentication-key.....	145
dns-server .....	546	area virtual-link authentication-none.....	147
domain-name.....	555	area virtual-link dead-interval.....	148
ip dhcp-local excluded-address.....	788	area virtual-link hello-interval.....	149
ip dhcp-local limit.....	789	area virtual-link message-digest-key	
ip dhcp-local pool.....	790	md5.....	150
ip dhcp-local unique-client-ids.....	792	area virtual-link retransmit-interval.....	151
lease .....	1235	area virtual-link transmit-delay.....	152
notice icons.....	xxxvii	area virtual-link authentication	
NTP commands		message-digest.....	146
clock set.....	449	area.	
clock summer-time date.....	451	no area See Command Reference Guide	
clock summer-time recurring.....	452	N to Z, OSPF commands	
clock timezone.....	453	authentication message-digest.....	209
null interface.....	9	authentication-key.....	208
NVS commands		authentication-none.....	211
check-disk.....	367	auto-cost reference-bandwidth.....	218
flash-disk compare.....	643	automatic-virtual-link.....	219
flash-disk duplicate.....	644	baseline ip ospf.....	252
flash-disk initialize.....	645	baseline ipv6 ospf.....	264
flash-disk scan.....	646	clear bfd session.....	376
mount.....	1360	clear ip ospf redistribution.....	408
<b>O</b>		clear ipv6 ospf counters.....	424
OCx/STMx commands		clear ipv6 ospf process.....	425
baseline path interface sonet.....	273	clear ipv6 ospf redistribution.....	426
baseline section interface sonet.....	279	cost.....	482
clock source.....	450	dead-interval.....	489
controller sonet.....	474	debug ip ospf.....	498
loopback.....	1279	debug ipv6 ospf.....	503
OSPF commands		default-information originate.....	513
address area.....	96	disable-dynamic-redistribute.....	533
address authentication message-digest.....	99	disable-incremental-external-spf.....	534
address authentication-key.....	98	distance.....	540
address authentication-none.....	101	domain-id.....	552
address cost.....	103	domain-tag.....	557
address dead-interval.....	104	dont-install-routes.....	558
address hello-interval.....	107	graceful-restart.....	678
address message-digest-key md5.....	108	graceful-restart helper.....	679
address network.....	109	graceful-restart	
address passive-interface.....	110	helper-abort-topology-change.....	680
address priority.....	112	graceful-restart notify-duration.....	681
address retransmit-interval.....	114	graceful-restart restart-duration.....	682
address transmit-delay.....	116	hello-interval.....	700
area default-cost.....	138	ip ospf authentication message-digest.....	897
area nssa.....	141	ip ospf authentication-key.....	896
area range.....	142	ip ospf authentication-none.....	898
area stub.....	143	ip ospf bfd-liveness-detection.....	899
area virtual-link.....	144	ip ospf cost.....	900
		ip ospf dead-interval.....	901

ip ospf hello-interval.....	902
ip ospf message-digest-key md5.....	903
ip ospf network.....	904
ip ospf priority.....	905
ip ospf retransmit-interval.....	906
ip ospf shutdown.....	907
ip ospf transmit-delay.....	908
ip route-type.....	948
ipv6 ospf area.....	1103
ipv6 ospf bfd-liveness-detection.....	1104
ipv6 ospf cost.....	1105
ipv6 ospf dead-interval.....	1106
ipv6 ospf hello-interval.....	1107
ipv6 ospf mtu-ignore.....	1108
ipv6 ospf network.....	1109
ipv6 ospf priority.....	1110
ipv6 ospf retransmit-interval.....	1111
ipv6 ospf shutdown.....	1112
ipv6 ospf transmit-delay.....	1113
ipv6 route-type.....	1139
ipv6 router ospf.....	1137
maximum-paths.....	1320
message-digest-key md5.....	1339
mpls ldp autoconfig.....	1378
mpls ldp igp sync holddown.....	1388
mpls ldp sync.....	1400
mpls traffic-eng area.....	1451
mpls traffic-eng multicast-intact.....	1456
mpls traffic-eng router-id.....	1457

## P

### PIM commands

clear ip mroute.....	403
clear ip pim auto-rp.....	409
clear ip pim interface count.....	410
clear ip pim remote-neighbor count.....	411
clear ipv6 mroute.....	422
clear ipv6 pim interface.....	427
clear ipv6 pim remote-neighbor.....	428
debug ip pim.....	500
debug ipv6 pim.....	505
ip pim.....	909
ip pim bfd-liveness-detection.....	910
ip pim bsr-candidate.....	911
ip pim data-mdt.....	912
ip pim dr-priority.....	913
ip pim group-address-pool.....	914
ip pim join-filter.....	915
ip pim join-prune-interval.....	916
ip pim query-interval.....	917
ip pim rp-address.....	918
ip pim rp-candidate.....	919
ip pim send rp-announce.....	920
ip pim send rp-discovery scope.....	921
ip pim	
sparse-mode graceful-restart-duration.....	922
ip pim spt-threshold.....	923
ip pim ssm.....	924
ipv6 pim bfd-liveness-detection.....	1114
ipv6 pim bsr-candidate.....	1115
ipv6 pim dr-priority.....	1116
ipv6 pim join-filter.....	1117
ipv6 pim join-prune-interval.....	1118
ipv6 pim query-interval.....	1119
ipv6 pim rp-address.....	1120
ipv6 pim rp-candidate.....	1121
ipv6 pim sparse-mode.....	1122
ipv6 pim sparse-mode	
graceful-restart-duration.....	1123
ipv6 pim spt-threshold.....	1124
ipv6 pim ssm.....	1125
ipv6 router pim.....	1138
mdt-data-delay.....	1330
mdt-data-holddown.....	1331
mdt-data-timeout.....	1332
mdt-interval.....	1333
policy management commands	
aggregation-node.....	121
atm classifier-list.....	177
atm policy.....	190
atm policy-list.....	191
atm-cell-mode.....	176
clear mirror log.....	439
color.....	454
color-aware.....	455
color-mark-profile.....	456
committed-action.....	457
committed-burst.....	458
committed-rate.....	461
conformed-action.....	466
control plane.....	471
enable-frag-stats.....	570
exceeded-action.....	609
exception http-redirect.....	616
excess-burst.....	621
exp-mask.....	631
filter.....	642
forward.....	647

forward interface.....	648	baseline pppoe interface.....	275
forward next-hop.....	649	encapsulation pppoe.....	583
frame-relay classifier-list.....	653	profile command, ip tcp adjust-mss.....	978
frame-relay policy.....	668		
frame-relay policy-list.....	669	<b>Q</b>	
gre-tunnel policy.....	687	QoS commands	
gre-tunnel policy-list.....	688	aaa qos downstream rate.....	59
green-mark.....	685	adjustment-factor.....	117
ip classifier-list.....	768	assured-rate.....	156
ip filter-options all.....	813	buffer-weight.....	343
ip match-policy-list.....	868	clear egress-queue.....	387
ip policy.....	925	clear fabric-queue.....	388
ip policy-list.....	927	committed-drop-threshold.....	459
ip policy-parameter hierarchical.....	928	committed-length.....	460
ip policy-parameter reference-rate.....	929	committed-threshold.....	462
ipv6 classifier-list.....	1036	conformed-drop-threshold.....	467
ipv6 policy.....	1126	conformed-fraction.....	468
ipv6 policy-list.....	1128	conformed-length.....	469
ipv6 policy-parameter hierarchical.....	1129	conformed-threshold.....	470
ipv6 policy-parameter reference-rate.....	1130	controlled-interface-type.....	472
ipv6 prefix-list.....	1131	convergence-factor.....	476
l2tp classifier-list.....	1183	drop-profile.....	560
l2tp policy.....	1204	exceeded-drop-threshold.....	610
l2tp policy-list.....	1205	exceeded-fraction.....	611
l2tp policy-parameter hierarchical.....	1206	exceeded-length.....	612
l2tp policy-parameter reference-rate.....	1207	exceeded-threshold.....	613
log.....	1263	fabric-strict-priority.....	638
mark.....	1290	fabric-weight.....	639
mark-clp.....	1292	forwarding-rate-threshold.....	650
mark-de.....	1293	gre-tunnel classifier-list.....	686
mask-val.....	1299	gre-tunnel policy-list.....	688
mpls policy.....	1413	instance-interface-type.....	730
mpls policy-parameter hierarchical.....	1415	load-rebalance.....	1256
mpls policy-parameter reference-rate.....	1416	mark-exp.....	1294
POS commands		mark-user-priority.....	1295
baseline interface pos.....	240	maximum-voql.....	1322
crc.....	484	minimum-dynamic-rate-percent.....	1344
encapsulation ppp.....	582	mpls classifier-list.....	1367
interface pos.....	743	mpls policy-list.....	1414
loopback.....	1279	mpls policy-statistics.....	1417
mru.....	1462	qos-shaping-mode.....	879
mtu.....	1464	QoS commands,	
POS interface.....	9, 16	member-interface-type.....	1337
PPP commands			
baseline ppp interface.....	274	<b>R</b>	
PPPoE commands		RADIUS commands	
aaa tunnel calling-number-format.....	72	aaa intf-desc-format include.....	45
aaa tunnel		authorization change.....	213
calling-number-format-fallback.....	75	baseline radius.....	276

baseline radius dynamic-request.....	277	ip summary-address.....	976
baseline radius relay.....	278	match-set summary prefix-tree.....	1315
key.....	1170	routing policy commands	
max-sessions.....	1326	match as-path.....	1300
radius per profile configuration.....	205	match community.....	1301
radius commands		match description.....	1466
action-type.....	90	match distance.....	1301
redundancy commands		match extcommunity.....	1303
clear redundancy history.....	442	match ip address.....	1304
disable-autosync.....	532	match ip next-hop.....	1305
disable-switch-on-error.....	536	match ipv6 address.....	1306
ip initial-sequence-preference.....	858	match ipv6 next-hop.....	1307
ipv6 initial-sequence-preference.....	1055	match ipv6 route-source.....	1308
line-card switch.....	1248	match level.....	1309
Response Time Reporter commands		match metric.....	1310
frequency.....	671	match metric-type.....	1311
hops-of-statistics-kept.....	702	match policy-list.....	1313
max-response-failure.....	1325	match route-type.....	1314
RIP commands		match tag.....	1316
address.....	95	match-set summary prefix-tree.....	1315
address authentication key.....	97	RSVP-TE commands	
address authentication mode.....	100	bandwidth.....	225
address bfd-liveness-detection.....	102	cleanup-timeout-factor.....	372
address receive version.....	113	clear rsvp authentication.....	443
address send version.....	115	mark-exp.....	1294
authentication key.....	207	mpls backup-path.....	1365
authentication mode.....	210	mpls bandwidth.....	1366
baseline ip rip.....	253	mpls classifier-list.....	1367
clear ip rip dynamic-interfaces.....	414	mpls diff-serv phb-id traffic-class.....	1370
clear ip rip redistribution.....	415	mpls lsp no-route retries.....	1407
debounce-time.....	493	mpls lsp no-route retry-time.....	1408
debug ip rip.....	502	mpls lsp retries.....	1409
default-information originate.....	513	mpls lsp retry-time.....	1410
default-metric.....	515	mpls policy-list.....	1414
disable.....	531	mpls policy-statistics.....	1417
disable-dynamic-redistribute.....	533	mpls reoptimize.....	1425
distance.....	540	mpls reoptimize timers frequency.....	1426
distribute-list.....	544	mpls rsvp.....	1427
exit-remote-neighbor.....	630	mpls rsvp authentication.....	1428
interface-event-disable.....	733	mpls rsvp authentication key.....	1429
ip rip.....	937	mpls rsvp bfd-liveness-detection.....	1430
ip rip authentication key.....	938	mpls rsvp disable.....	1431
ip rip authentication mode.....	939	mpls rsvp egress-label.....	1432
ip rip bfd-liveness-detection.....	940	mpls rsvp message-bundling.....	1433
ip rip copy-to-dynamic.....	941	mpls rsvp profile.....	1434
ip rip receive version.....	942	mpls rsvp refresh-reduction.....	1435
ip rip send version.....	943	mpls rsvp signalling hello.....	1436
ip route-type.....	948	mpls rsvp signalling hello	
ip split-horizon.....	967	graceful-restart.....	1437

- mpls rsvp signalling hello graceful-restart
    - recovery-time.....1438
  - mpls rsvp signalling hello graceful-restart
    - restart-time.....1439
  - mpls rsvp signalling node-hello.....1440
  - mpls traffic-class.....1448
  - mpls traffic-eng administrative-weight.....1450
  - mpls traffic-eng attribute-flags.....1452
  - mpls traffic-eng flood thresholds.....1454
  - mpls traffic-eng link-management timers
    - periodic-flooding.....1455
- S**
- serial interface.....9
  - Service Manager commands
    - license service-management.....1244
  - show commands, filtering.....4
  - SNMP commands
    - baseline snmp.....281
    - buffer-weight.
      - no buffer-weight See Command Reference Guide N to Z, SNMP commands
    - bulkstats collector.....345
    - bulkstats collector collector-mode.....345
    - bulkstats collector description.....345
    - bulkstats collector interval.....345
    - bulkstats collector max-size.....345
    - bulkstats collector primary-receiver.....345
    - bulkstats collector secondary-receiver.....345
    - bulkstats collector single-interval.....345
    - bulkstats file-format endOfLine-Lf.....346
    - bulkstats interface-type.....349
    - bulkstats interfaces description-format
      - common.....347
    - bulkstats interfaces rfc 1213.....348
    - bulkstats receiver remote-name.....350
    - bulkstats schema.....351
    - bulkstats schema subtree.....352
    - bulkstats schema subtree policy.....353
    - bulkstats schema subtree qos.....354
    - bulkstats traps.....356
    - bulkstats virtual-router-group.....357
    - bulkstats.
      - no bulkstats See Command Reference Guide N to Z, SNMP commands
  - SNMP server event manager commands
    - delta-sampling.....519
  - SONET/SDH interface.....12, 16
  - SSH commands
    - crypto key dss.....486
    - disconnect ssh.....538
    - ip ssh authentication-retries.....968
    - ip ssh crypto.....969
    - ip ssh disable-user-authentication.....970
    - ip ssh mac.....971
    - ip ssh sleep.....972
    - ip ssh timeout.....973
    - ip ssh user-authentication-protocol.....974
  - subscriber interface commands
    - dhcp-external delete-binding.....525
    - ip auto-configure
      - append-virtual-router-name.....761
    - ip auto-configure ip-subscriber.....762
    - ip auto-detect ip-subscriber.....763
    - ip demux-type da-prefix.....773
    - ip destination-prefix.....775
    - ip dhcp-external auto-configure.....777
    - ip dhcp-external server-address.....780
    - ip dhcp-external server-sync.....781
    - ip inactivity-timer.....857
    - ip re-authenticate-auto-detect
      - ip-subscriber.....934
    - ip source-prefix.....964
  - subscriber management commands
    - ip service-profile.....960
  - subscriber policy commands
    - arp.....153
    - bridge subscriber-policy.....335
    - broadcast.....342
    - ip.....748
    - mpls.....1361
    - multicast.....1465
  - support, technical See technical support
  - suspicious control flow detection commands
    - baseline
      - suspicious-control-flow-detectioncounts.....283
    - clear suspicious-control-flow-detection .....444
  - system commands
    - aaa authentication enable default.....33
    - aaa authentication login.....34
    - aaa authorization.....35
    - aaa authorization config-commands.....36
    - aaa new-model.....52
    - access-class in.....87
    - access-list.....88
    - bandwidth oversubscription.....226
    - banner.....227

clear line.....	438
copy.....	477
copy running-configuration	
startup-configuration.....	480
copy startup-configuration.....	481
crypto key dss.....	486
data-character-bits.....	488
delete.....	518
description.....	521
dir.....	530
disconnect ssh.....	538
dsr-detect.....	562
enable password.....	573
enable secret.....	575
erase secrets.....	591
exception dump.....	614
exception gateway.....	615
exception monitor.....	617
exception monitor interval.....	618
exception protocol ftp.....	619
exception source.....	620
exclude-subsystem.....	624
exec-banner.....	625
exec-timeout.....	626
halt.....	692
help.....	701
host.....	703
hostname.....	704
hotfix activate.....	705
ip domain-lookup.....	796
ip domain-name.....	797
ip name-server.....	885
ip nfs.....	894
ip nfs host.....	895
ip ssh authentication-retries.....	968
ip ssh crypto.....	969
ip ssh disable-user-authentication.....	970
ip ssh mac.....	971
ip ssh sleep.....	972
ip ssh timeout.....	973
ip ssh user-authentication-protocol.....	974
ipv6 access-list.....	1030
line.....	1247
login.....	1276
login authentication.....	1277
macro.....	1286
memory.....	1338
more.....	1358
motd-banner.....	1359

## T

T1 commands	
interface serial.....	744
T3 commands	
atm framing.....	182
bert.....	286
cablelength.....	362
channelized.....	366
controller t3.....	475
description.....	521
dsu bandwidth.....	563
dsu mode.....	564
equipment loopback.....	590
idle-character.....	710
load-interval.....	1255
loopback.....	1279
mru.....	1462
mtu.....	1464
TACACS+ commands	
aaa authentication enable default.....	33
baseline tacacs.....	284
TCP commands	
tcp ack-rst-and-syn.....	977
technical support	
contacting JTAC.....	xxxix
text and syntax conventions.....	xxxviii
time commands, system	
clock set.....	449
clock summer-time date.....	451
clock summer-time recurring.....	452
clock timezone.....	453
timing command, clock source.....	450
troubleshooting commands	
baseline log.....	268
bgp log-neighbor-changes.....	307
debug ip bgp.....	494
debug ip mbgp.....	496
debug ip ospf.....	498
debug ip pim.....	500
debug ip rip.....	502
debug ipv6 ospf.....	503
debug ipv6 pim.....	505
debug isis.....	507
log.....	1263
log destination.....	1265
log destination syslog source.....	1267
log engineering.....	1268
log fields.....	1269

log filters.	
no log filters See Command Reference	
Guide N to Z, troubleshooting	
commands	
log here.....	1271
log severity.....	1272
log unlimit.....	1274
log verbosity.....	1275
tunnel interface.....	12
tunnel service command, max-interfaces.....	1323

## U

unified ISSU commands	
issu initialize.....	1164
issu start.....	1165
issu stop.....	1166
license issu.....	1240
user interface commands	
configure.....	464
confirmations explicit.....	465
disable.....	531
do.....	548
enable.....	569
end.....	586
exit.....	628

## V

virtual router command	
ipv6-virtual-router.....	1136
VLAN commands	
auto-configure vlan.....	217
encapsulation vlan.....	584
mark-user-priority.....	1295
mask-val.....	1299
monitor vlan interface.....	1357
VoIP commands	
circuit-id.....	486
circuit-id interface.....	486
VPLS commands	
address-family.....	105
arp.....	153
baseline bridge.....	231
baseline bridge interface.....	232
baseline bridge interface vpls.....	233
bridge.....	325
bridge acquire.....	326
bridge address.....	327
bridge aging-time.....	329
bridge learn.....	332

bridge snmp-trap link-status.....	334
bridge subscriber-policy.....	335
bridge vpls rd.....	336
bridge vpls route-target.....	337
bridge vpls site-name site-id.....	339
bridge vpls site-range.....	340
bridge vpls transport-virtual-router.....	341
bridge-group.....	331
broadcast.....	342
clear bridge.....	383
clear bridge address.....	384
clear bridge interface.....	385
clear bridge interface vpls.....	386
clear ip bgp.....	389
clear ip bgp dampening.....	391
clear ip bgp wait-end-of-rib.....	395
ip.....	748
mpls.....	1361
mpls ldp vpls neighbor.....	1405
mpls ldp vpls vpls-id.....	1406
multicast.....	1465
VPN commands	
ipv6-router-name.....	1136
VPWS commands	
clear ip bgp.....	389
clear ip bgp dampening.....	391
clear ip bgp wait-end-of-rib.....	395
l2vpn control-word.....	1224
l2vpn encapsulation-type.....	1225
l2vpn local-site-id remote-site-id.....	1226
l2vpn rd.....	1227
l2vpn route-target.....	1228
l2vpn sequencing.....	1229
l2vpn site-name site-id.....	1230
l2vpn site-range.....	1231
VRRP commands	
baseline ip vrrp.....	256
ip vrrp.....	987
ip vrrp accept-data.....	988
ip vrrp advertise-interval.....	989
ip vrrp authentication-key.....	990
ip vrrp authentication-type.....	991
ip vrrp enable.....	992
ip vrrp icr-partition.....	993
ip vrrp icr-partition group.....	994
ip vrrp icr-partition svlan-list.....	995
ip vrrp icr-partition vlan-list.....	999
ip vrrp icr-partition vlan-range.....	1000
ip vrrp preempt.....	1002

ip vrrp priority.....	1003
ip vrrp timers-learn.....	1004
ip vrrp track.....	1005
ip vrrp virtual-address.....	1006
VRRP ICR commands	
ip vrrp icr-partition svlan-list explicit.....	996
ip vrrp icr-partition svlan-range.....	997