Juniper Networks | Engineering Simplicity

NorthStar Controller/Planner Getting Started Guide

Published
2022-04-19

Release
5.1.0

Juniper Networks, Inc.
1133 Innovation Way
Sunnyvale, California 94089
USA
408-745-2000
www.juniper.net

Juniper Networks, the Juniper Networks logo, Juniper, and Junos are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

NorthStar Controller/Planner Getting Started Guide
5.1.0
Copyright © 2022 Juniper Networks, Inc. All rights reserved.

The information in this document is current as of the date on the title page.

YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement (“EULA”) posted at https://support.juniper.net/support/eula/. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

Table of Contents

About the Documentation | viii

Documentation and Release Notes | **viii**

Documentation Conventions | **viii**

Documentation Feedback | **xi**

Requesting Technical Support | **xi**

- Self-Help Online Tools and Resources | **xii**
- Creating a Service Request with JTAC | **xii**

1 **NorthStar Controller Installation and Configuration Overview**

Platform and Software Compatibility | 14

- Installation Options | **15**
- Deployment Scenarios | **16**

NorthStar Controller System Requirements | 21

- System Requirements for VMDK Deployment | **25**
- Analytics Requirements | **26**
- Two-VM Installation Requirements | **26**
  - Disk and Memory Requirements | **26**
  - VM Image Requirements | **26**
  - JunosVM Version Requirements | **27**
  - VM Networking Requirements | **27**
- Server Sizing Guidance | **28**
  - Server Requirements | **28**
  - Additional Disk Space for JTI Analytics in ElasticSearch | **29**
  - Additional Disk Space for Network Events in Cassandra | **30**
  - Collector (Celery) Memory Requirements | **30**

Upgrading from Pre-4.3 NorthStar with Analytics | 31

- Export Existing Data (Recommended) | **32**
- Upgrade Procedure with NorthStar Application and NorthStar Analytics on the Same Server | **35**
- Upgrade Procedure with NorthStar Application and NorthStar Analytics on Separate Servers | **36**

Update the Netflow Aggregation Parameter | 37

Import Existing Data (Recommended) | 38

Changing Control Packet Classification Using the Mangle Table | 38

Renew SSL Certificates for NorthStar Web UI | 40

2 **NorthStar Controller Installation on a Physical Server**

Installing the NorthStar Controller | 45

Download the NorthStar Controller Software | 47

If Upgrading, Back Up Your JunosVM Configuration and iptables | 47

Install NorthStar Controller | 47

Configure Support for Different JunosVM Versions | 49

Create Passwords | 51

Enable the NorthStar License | 51

Adjust Firewall Policies | 52

Launch the Net Setup Utility | 52

Configure the Host Server | 54

Configure the JunosVM and its Interfaces | 59

Configure Junos cRPD Settings | 64

Set Up the SSH Key for External JunosVM | 66

Upgrade the NorthStar Controller Software in an HA Environment | 68

Uninstalling the NorthStar Controller Application | 72

Uninstall the NorthStar Software | 72

Reinstate the License File | 73

3 **Running the NorthStar Controller on VMware ESXi**

VMDK Deployment | 75

4 **NorthStar Controller Installation in an OpenStack Environment**

Overview of NorthStar Controller Installation in an OpenStack Environment | 91

Testing Environment | 92

Networking Scenarios | 92

HEAT Templates | 93

HEAT Template Input Values | 94

Known Limitations | 95

Virtual IP Limitations from ARP Proxy Being Enabled | 95

Hostname Changes if DHCP is Used Rather than a Static IP Address | 95

Disk Resizing Limitations | 95

OpenStack Resources for NorthStar Controller Installation | 96

NorthStar Controller in an OpenStack Environment Pre-Installation Steps | 97

Installing the NorthStar Controller in Standalone Mode Using a HEAT Template | 98

Launch the Stack | 98

Obtain the Stack Attributes | 99

Resize the Image | 100

Install the NorthStar Controller RPM Bundle | 102

Configure the JunosVM | 102

Configure SSH Key Exchange | 103

Installing a NorthStar Cluster Using a HEAT Template | 104

System Requirements | 104

Launch the Stack | 104

Obtain the Stack Attributes | 104

Configure the Virtual IP Address | 105

Resize the Image | 106

Install the NorthStar Controller RPM Bundle | 109

Configure the JunosVM | 109

Configure SSH Key Exchange | 109

Configure the HA Cluster | 110

5 **Installing and Configuring Optional Features**

Installing Data Collectors for Analytics | 112

Overview | 112

Analytics Geo-HA | 114

Single-Server Deployment–No NorthStar HA | 114

External Analytics Node(s)–No NorthStar HA | 115

External Analytics Node(s)–With NorthStar HA | 127

Verifying Data Collection When You Have External Analytics Nodes | 130

Replacing a Failed Node in an External Analytics Cluster | 133

Collectors Installed on the NorthStar HA Cluster Nodes | 138

Troubleshooting Logs | 144

Configuring Routers to Send JTI Telemetry Data and RPM Statistics to the Data Collectors | 145

Collector Worker Installation Customization | 150

Secondary Collector Installation for Distributed Data Collection | 151

Configuring a NorthStar Cluster for High Availability | 154

Before You Begin | 154

Set Up SSH Keys | 156

Access the HA Setup Main Menu | 157

Configure the Three Default Nodes and Their Interfaces | 161

Configure the JunosVM for Each Node | 163

(Optional) Add More Nodes to the Cluster | 164

Configure Cluster Settings | 166

Test and Deploy the HA Configuration | 167

Replace a Failed Node if Necessary | 172

Configure Fast Failure Detection Between JunosVM and PCC | 174

6

Configuring Topology Acquisition and Connectivity Between the NorthStar Controller and the Path Computation Clients

Understanding Network Topology Acquisition on the NorthStar Controller | 176

Configuring Topology Acquisition | 178

Overview | 178

Before You Begin | 179

Configuring Topology Acquisition Using BGP-LS | 181

Configure BGP-LS Topology Acquisition on the NorthStar Controller | 181

Configure the Peering Router to Support Topology Acquisition | 182

Configuring Topology Acquisition Using OSPF | 183

Configure OSPF on the NorthStar Controller | 183

Configure OSPF over GRE on the NorthStar Controller | 184

Configuring Topology Acquisition Using IS-IS | **184**

Configure IS-IS on the NorthStar Controller | **185**

Configure IS-IS over GRE on the NorthStar Controller | **185**

Configuring PCEP on a PE Router (from the CLI) | 186

Configuring a PE Router as a PCC | **186**

Setting the PCC Version for Non-Juniper Devices | **188**

Mapping a Path Computation Client PCEP IP Address | 190

7 **Accessing the User Interface**

NorthStar Application UI Overview | 194

UI Comparison | **194**

Browser Compatibility | **195**

The NorthStar Login Window | **195**

NorthStar Controller Web UI Overview | 198

NorthStar Planner UI Overview | 203

Initial Window, Before a Network is Loaded | **204**

NorthStar Planner Window with a Network Loaded | **204**

Menu Options for the NorthStar Planner UI | **205**

RSVP Live Util Legend | **206**

Customizing Nodes and Links in the Map Legends | **207**

About the Documentation

IN THIS SECTION

- Documentation and Release Notes | viii
- Documentation Conventions | viii
- Documentation Feedback | xi
- Requesting Technical Support | xi

Use this guide to install the NorthStar Controller application, perform initial configuration tasks, install optional features, establish connectivity to the network, and access the NorthStar UI. System requirements and deployment scenario server requirements are included.

Documentation and Release Notes

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at https://www.juniper.net/documentation/.

If the information in the latest release notes differs from the information in the documentation, follow the product Release Notes.

Juniper Networks Books publishes books by Juniper Networks engineers and subject matter experts. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration. The current list can be viewed at https://www.juniper.net/books.

Documentation Conventions

Table 1 on page ix defines notice icons used in this guide.

Table 1: Notice Icons

Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.
	Tip	Indicates helpful information.
	Best practice	Alerts you to a recommended use or implementation.

Table 2 on page ix defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
Bold text like this	Represents text that you type.	To enter configuration mode, type the **configure** command: user@host> **configure**
`Fixed-width text like this`	Represents output that appears on the terminal screen.	`user@host>` **show chassis alarms** `No alarms currently active`
Italic text like this	• Introduces or emphasizes important new terms. • Identifies guide names. • Identifies RFC and Internet draft titles.	• A policy *term* is a named structure that defines match conditions and actions. • *Junos OS CLI User Guide* • RFC 1997, *BGP Communities Attribute*

Table 2: Text and Syntax Conventions *(continued)*

Convention	Description	Examples
Italic text like this	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name: [edit] root@# **set system domain-name** *domain-name*
Text like this	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	• To configure a stub area, include the **stub** statement at the **[edit protocols ospf area area-id]** hierarchy level. • The console port is labeled **CONSOLE**.
< > (angle brackets)	Encloses optional keywords or variables.	**stub <default-metric *metric*>;**
| (pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	**broadcast | multicast** **(*string1* | *string2* | *string3*)**
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	**rsvp { # Required for dynamic MPLS only**
[ ] (square brackets)	Encloses a variable for which you can substitute one or more values.	**community name members [*community-ids*]**

Indention and braces ({ })	Identifies a level in the configuration hierarchy.	[edit]
		routing-options {
		  static {
		  route default {
		  nexthop *address*;
		  retain;
		  }
		  }
		}

; (semicolon)	Identifies a leaf statement at a configuration hierarchy level.	
GUI Conventions		

Table 2: Text and Syntax Conventions *(continued)*

Convention	Description	Examples
Bold text like this	Represents graphical user interface (GUI) items you click or select.	• In the Logical Interfaces box, select **All Interfaces**. • To cancel the configuration, click **Cancel**.
> (bold right angle bracket)	Separates levels in a hierarchy of menu selections.	In the configuration editor hierarchy, select **Protocols>Ospf**.

Documentation Feedback

We encourage you to provide feedback so that we can improve our documentation. You can use either of the following methods:

- Online feedback system—Click TechLibrary Feedback, on the lower right of any page on the Juniper Networks TechLibrary site, and do one of the following:



  - Click the thumbs-up icon if the information on the page was helpful to you.
  - Click the thumbs-down icon if the information on the page was not helpful to you or if you have suggestions for improvement, and use the pop-up form to provide feedback.
- E-mail—Send your comments to techpubs-comments@juniper.net. Include the document or topic name, URL or page number, and software version (if applicable).

Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active Juniper Care or Partner Support Services support contract, or are

covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at https://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf.
- Product warranties—For product warranty information, visit https://www.juniper.net/support/warranty/.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: https://www.juniper.net/customers/support/
- Search for known bugs: https://prsearch.juniper.net/
- Find product documentation: https://www.juniper.net/documentation/
- Find solutions and answer questions using our Knowledge Base: https://kb.juniper.net/
- Download the latest versions of software and review release notes: https://www.juniper.net/customers/csc/software/
- Search technical bulletins for relevant hardware and software notifications: https://kb.juniper.net/InfoCenter/
- Join and participate in the Juniper Networks Community Forum: https://www.juniper.net/company/communities/
- Create a service request online: https://myjuniper.juniper.net

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: https://entitlementsearch.juniper.net/entitlementsearch/

Creating a Service Request with JTAC

You can create a service request with JTAC on the Web or by telephone.

- Visit https://myjuniper.juniper.net.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see https://support.juniper.net/support/requesting-support/.

CHAPTER 1

NorthStar Controller Installation and Configuration Overview

Platform and Software Compatibility | **14**

NorthStar Controller System Requirements | **21**

Upgrading from Pre-4.3 NorthStar with Analytics | **31**

Changing Control Packet Classification Using the Mangle Table | **38**

Renew SSL Certificates for NorthStar Web UI | **40**

Platform and Software Compatibility

IN THIS SECTION

- Installation Options | 15
- Deployment Scenarios | 16

The NorthStar Controller 5.1.0 release is qualified to work with Junos OS Release 18.3R2.4. We recommend contacting JTAC for information about the compatibility of other Junos OS releases. Table 3 on page 14 lists feature-specific Junos OS requirements.

Table 3: Feature-Specific Junos OS Requirements

NorthStar Feature	Junos OS Release
Analytics	15.1F6
Segment Routing (SPRING), MD5 authentication for PCEP, P2MP, Admin groups	17.2R1
PCEP-Provisioned P2MP Groups	18.3R2
PCEP-Provisioned P2MP Groups with MVPN (S,G) Service Mapping via Flowspec	19.4R1
EPE	19.2R1.8
Bandwidth sizing and container LSPs for SR-TE LSPs	19.2R1.2

NOTE: The Path Computation Element Protocol (PCEP) configuration on the PCC routers does not persist across upgrades when the SDN package is not part of the installation binary. Before upgrading the Junos OS image to this release, save the existing configuration to a file by using the **save** command. After you upgrade the Junos OS image on each PCC router, use the **load override** command to restore the PCEP configuration.

The NorthStar Controller is supported on the following Juniper platforms: M Series, T Series, MX Series, PTX Series, and QFX10008. As of Junos OS Release 17.4R1, NorthStar Controller is also supported on QFX5110, QFX5100, and QFX5200. Please contact JTAC for more information.

Junos OS supports Internet draft draft-crabbe-pce-pce-initiated-lsp-03 for the stateful PCE-initiated LSP implementation (M Series, MX Series, PTX Series, T Series, and QFX Series).

The following sections provide information that will help guide you in determining which installation instructions you will need based on how you intend to install NorthStar, and how many servers you will need, based on the deployment scenario you choose:

Installation Options

There are three NorthStar Controller installation options for use with Junos VM as summarized in Figure 1 on page 15.

Figure 1: NorthStar/Junos VM Installation Options



You can also install NorthStar Controller using cRPD as summarized in Figure 2 on page 16.

Figure 2: NorthStar/cRPD Installation



For installation procedures, see:

- Installing the NorthStar Controller on page 45

  This topic also includes information about NorthStar cRPD.
- Overview of NorthStar Controller Installation in an OpenStack Environment on page 91
- VMDK Deployment on page 75

Deployment Scenarios

Table 4 on page 17 lists the supported deployment configurations by NorthStar 4.x release.

Table 4: Supported NorthStar Deployment Configurations by 4.x Release

Deployment Configuration	Features Available *NorthStar Release 4.0.0*	Features Available *NorthStar Release 4.1.0*	Features Available *NorthStar Release 4.2.x, 4.3.0*
Description: • NorthStar application (no Analytics, no HA) **Number of Servers:** • NorthStar: 1 • Total: 1	• PCEP and NETCONF provisioning • NETCONF device collection	• PCEP and NETCONF provisioning • NETCONF device collection	• PCEP and NETCONF provisioning • Device collection

Description:
• NorthStar application and Analytics, both installed in a single server
• One or more optional secondary collector servers
Number of Servers:
• NorthStar + Analytics: 1
• Total: 1
• Total with optional secondary collector servers: 2 or more
	• PCEP and NETCONF provisioning
	• NETCONF device collection
	• Telemetry
	• Data Collection:
	  ◦ SNMP
	  ◦ Link latency
	  ◦ Network archive task
	  ◦ LDP
	• Distributed collection (if optional secondary collectors are installed)
		• PCEP and NETCONF provisioning
		• NETCONF device collection
		• Telemetry
		• Data Collection:
		  ◦ SNMP
		  ◦ Link latency
		  ◦ Network archive task
		  ◦ LDP
		• Netflow Collector
		• Distributed collection (if optional secondary collectors are installed)
			• PCEP and NETCONF provisioning
			• LSP bandwidth sizing
			• Device collection
			• Telemetry
			• Data Collection:
			  ◦ SNMP
			  ◦ Link latency
			  ◦ Network archive task
			  ◦ LDP
			• Netflow Collector
			• Distributed collection (if optional secondary collectors are installed)

Table 4: Supported NorthStar Deployment Configurations by 4.x Release *(continued)*

Deployment Configuration	Features Available *NorthStar Release 4.0.0*	Features Available *NorthStar Release 4.1.0*	Features Available *NorthStar Release 4.2.x, 4.3.0*

Description:
• NorthStar application and Analytics, each installed in a separate server
• One or more optional secondary collector servers
Number of servers:
• NorthStar: 1
• Analytics: 1
• Total: 2
• Total with optional secondary collector servers: 3 or more
	• PCEP and NETCONF provisioning
	• NETCONF device collection
	• Telemetry
	• Data Collection:
	  ◦ SNMP
	  ◦ Link latency
	  ◦ Network archive task
	  ◦ LDP
	• Distributed collection (if optional secondary collectors are installed)
		• PCEP and NETCONF provisioning
		• NETCONF device collection
		• Telemetry
		• Data Collection:
		  ◦ SNMP
		  ◦ Link latency
		  ◦ Network archive task
		  ◦ LDP
		• Netflow Collector
		• Distributed collection (if optional secondary collectors are installed)
			• PCEP and NETCONF provisioning
			• LSP bandwidth sizing
			• Device collection
			• Telemetry
			• Data Collection:
			  ◦ SNMP
			  ◦ Link latency
			  ◦ Network archive task
			  ◦ LDP
			• Netflow Collector
			• Distributed collection (if optional secondary collectors are installed)

Description: • NorthStar application HA **Number of servers:** • NorthStar: minimum of 3 (odd numbers only) • Total: 3 or more	• PCEP and NETCONF provisioning • NETCONF device collection • NorthStar HA	• PCEP and NETCONF provisioning • NETCONF device collection • NorthStar HA	• PCEP and NETCONF provisioning • Device collection • NorthStar HA

Table 4: Supported NorthStar Deployment Configurations by 4.x Release *(continued)*

Deployment Configuration	Features Available *NorthStar Release 4.0.0*	Features Available *NorthStar Release 4.1.0*	Features Available *NorthStar Release 4.2.x, 4.3.0*

Description:
• NorthStar application HA and separate, single Analytics server
• One or more optional secondary collector servers
Number of servers:
• NorthStar: minimum of 3 (odd numbers only)
• Analytics: 1
• Total: 4 or more
• Total with optional secondary collector servers: 5 or more
	• PCEP and NETCONF provisioning
	• NETCONF device collection
	• NorthStar HA
	• Telemetry
	• Data Collection:
	  ◦ SNMP
	  ◦ Link latency
	  ◦ Network archive task
	  ◦ LDP
	• Distributed collection (if optional secondary collectors are installed)
		• PCEP and NETCONF provisioning
		• NETCONF device collection
		• NorthStar HA
		• Telemetry
		• Data Collection:
		  ◦ SNMP
		  ◦ Link latency
		  ◦ Network archive task
		  ◦ LDP
		• Netflow Collector
		• Distributed collection (if optional secondary collectors are installed)
			• PCEP and NETCONF provisioning
			• LSP bandwidth sizing
			• Device collection
			• NorthStar HA
			• Telemetry
			• Data Collection:
			  ◦ SNMP
			  ◦ Link latency
			  ◦ Network archive task
			  ◦ LDP
			• Netflow Collector
			• Distributed collection (if optional secondary collectors are installed)

Description:
• Single NorthStar application server and Analytics HA
• One or more optional secondary collector servers
Number of servers:
• NorthStar: 1
• Analytics: minimum of 3 (odd numbers only)
• Total: 4 or more
• Total with optional secondary collector servers: 5 or more
	• PCEP and NETCONF provisioning
	• NETCONF device collection
	• Analytics HA
	• Telemetry
	• Data Collection:
	  ◦ SNMP
	  ◦ Link latency
	  ◦ Network archive task
	  ◦ LDP
	• Distributed collection (if optional secondary collectors are installed)
		• PCEP and NETCONF provisioning
		• NETCONF device collection
		• Analytics HA
		• Telemetry
		• Data Collection:
		  ◦ SNMP
		  ◦ Link latency
		  ◦ Network archive task
		  ◦ LDP
		• Netflow Collector
		• Distributed collection (if optional secondary collectors are installed)
			• PCEP and NETCONF provisioning
			• LSP bandwidth sizing
			• Device collection
			• Analytics HA
			• Telemetry
			• Data Collection:
			  ◦ SNMP
			  ◦ Link latency
			  ◦ Network archive task
			  ◦ LDP
			• Netflow Collector
			• Distributed collection (if optional secondary collectors are installed)

Table 4: Supported NorthStar Deployment Configurations by 4.x Release *(continued)*

Deployment Configuration	Features Available *NorthStar Release 4.0.0*	Features Available *NorthStar Release 4.1.0*	Features Available *NorthStar Release 4.2.x, 4.3.0*

Description:
• NorthStar application HA and separate Analytics HA
• One or more optional secondary collector servers
Number of servers:
• NorthStar: minimum of 3 (odd numbers only)
• Analytics: minimum of 3 (odd numbers only)
• Total: 6 or more
• Total with optional secondary collector servers: 7 or more
	• PCEP and NETCONF provisioning
	• NETCONF device collection
	• NorthStar HA
	• Analytics HA
	• Telemetry
	• Data Collection:
	  ◦ SNMP
	  ◦ Link latency
	  ◦ Network archive task
	  ◦ LDP
	• Distributed collection (if optional secondary collectors are installed)
		• PCEP and NETCONF provisioning
		• NETCONF device collection
		• NorthStar HA
		• Analytics HA
		• Telemetry
		• Data Collection:
		  ◦ SNMP
		  ◦ Link latency
		  ◦ Network archive task
		  ◦ LDP
		• Netflow Collector
		• Distributed collection (if optional secondary collectors are installed)
			• PCEP and NETCONF provisioning
			• LSP bandwidth sizing
			• Device collection
			• NorthStar HA
			• Analytics HA
			• Telemetry
			• Data Collection:
			  ◦ SNMP
			  ◦ Link latency
			  ◦ Network archive task
			  ◦ LDP
			• Netflow Collector
			• Distributed collection (if optional secondary collectors are installed)

Description:
• NorthStar application HA sharing servers with Analytics HA.
• One or more optional secondary collector servers
Number of servers:
• NorthStar + Analytics: minimum of 3 (odd numbers only)
• Total: 3 or more
• Total with optional secondary collector servers: 4 or more
	• PCEP and NETCONF provisioning
	• NETCONF device collection
	• NorthStar HA
	• Analytics HA
	• Telemetry
	• Data Collection:
	  ◦ SNMP
	  ◦ Link latency
	  ◦ Network archive task
	  ◦ LDP
	• Distributed collection (if optional secondary collectors are installed)
		• PCEP and NETCONF provisioning
		• NETCONF device collection
		• NorthStar HA
		• Analytics HA
		• Telemetry
		• Data Collection:
		  ◦ SNMP
		  ◦ Link latency
		  ◦ Network archive task
		  ◦ LDP
		• Netflow Collector
		• Distributed collection (if optional secondary collectors are installed)
			• PCEP and NETCONF provisioning
			• LSP bandwidth sizing
			• Device collection
			• NorthStar HA
			• Analytics HA
			• Telemetry
			• Data Collection:
			  ◦ SNMP
			  ◦ Link latency
			  ◦ Network archive task
			  ◦ LDP
			• Netflow Collector
			• Distributed collection (if optional secondary collectors are installed)

RELATED DOCUMENTATION

NorthStar Controller System Requirements | 21

Installing the NorthStar Controller | 45

NorthStar Controller System Requirements

Before you install the NorthStar Controller software, ensure that your system meets the requirements described in Table 5 on page 21.

Table 5: Hardware Requirements for NorthStar Servers

Server Type	RAM	HDD	Core Processor	Host must support hardware virtualization (VT-d)
NorthStar Application Only	48 GB	500 GB	Intel i5/i7	Yes
NorthStar Application with Analytics	64 GB	1.5 T	Intel i5/i7	Yes
Analytics Only	32 GB	1 T	Intel i5/i7	No
Secondary Collector Only	12 GB	100 GB	Intel i5/i7	No

In addition to the hardware requirements, ensure that:

- You use a supported version of CentOS Linux or Red Hat Enterprise Linux. These are our Linux recommendations:
  - CentOS Linux or Red Hat Enterprise Linux 6.10 (not supported for cRPD installation), 7.2, 7.5, or 7.6 image–earlier CentOS versions are not supported.
  - Install your choice of supported Linux version using the minimal ISO.
  - For CentOS Linux or Red Hat Enterprise Linux release 7.x, manually add the following utilities to your installation:

    ```
    yum –y install net-tools
    yum –y install bridge-utils
    ```

  CentOS can be downloaded from https://www.centos.org/download/.

- The ports listed in Table 6 on page 22 must be allowed by any external firewall being used. The ports with the word **cluster** in their purpose descriptions are associated with high availability (HA) functionality. If you are not planning to configure an HA environment, you can ignore those ports. The ports with the word **Analytics** in their purpose descriptions are associated with the Analytics feature. If you are not planning to use Analytics, you can ignore those ports. The remaining ports listed must be kept open in all configurations.

Table 6: Ports That Must Be Allowed by External Firewalls

Port	Purpose
179	BGP: JunosVM for router BGP-LS—not needed if IGP is used for topology acquisition
161	SNMP
450	NTAD

830	NETCONF communication between NorthStar Controller and routers. This is the default port for NETCONFD, but in some installations, port 22 is preferred. To change to port 22, use a text editor such as vi to modify the netconf_port parameter in **/opt/northstar/data/northstar.cfg**:
	`[root@northstar]# vi /opt/northstar/data/northstar.cfg`
	.
	.
	.
	`netconf_port=22`
	Then restart NETCONFD:
	`[root@northstar]# supervisorctl restart netconf:netconfd`

1514	Syslog: Default Junos Telemetry Interface reports for RPM probe statistics (supports Analytics)
1812	RADIUS authentication
2000	JTI: Default Junos Telemetry Interface reports for IFD (supports Analytics)
2001	JTI: Default Junos Telemetry Interface reports for IFL (supports Analytics)
2002	JTI: Default Junos Telemetry Interface reports for LSP (supports Analytics)
2888	Zookeeper cluster
3000	JTI: In previous NorthStar releases, three JTI ports were required (2000, 2001, 2002). Starting with Release 4.3.0, this single port can be used instead.

Table 6: Ports That Must Be Allowed by External Firewalls *(continued)*

Port	Purpose
3001	Model Driven Telemetry (MDT)
3002	Model Driven Telemetry (MDT)
3888	Zookeeper cluster
4189	PCEP: PCC (router) to NorthStar PCE server
5672	RabbitMQ
6379	Redis
7000	Communications port to NorthStar Planner
7001	Cassandra database cluster
8124	Health Monitor
8443	Web: Web client/REST to secure web server (https)
9000	Netflow
9201	Elasticsearch
9300	Elasticsearch cluster
10001	BMP passive mode: By default, the monitor listens on this port for incoming connections from the network.
17000	Cassandra database cluster
50051	PRPD: NorthStar application to router network

Figure 3 on page 24 details the direction of data flow through the ports, when node clusters are not being used. Figure 4 on page 25 and Figure 5 on page 25 detail the additional flows for NorthStar application HA clusters and analytics HA clusters, respectively.

Figure 3: NorthStar Main Port Map



Figure 4: NorthStar Application HA Port Map



Figure 5: Analytics HA Port Map



NOTE: When upgrading NorthStar Controller, files are backed up to the /opt directory.

System Requirements for VMDK Deployment

The following requirements apply when preparing to run the NorthStar Controller on VMWare ESXi by outputting a VMDK file of the NorthStar disk from the VMWare build software:

- ESXi 5.5, 6.0, and 6.5 are supported.

Analytics Requirements

In addition to ensuring that ports 2000, 2001, 2002, and 1514 are kept open, using the NorthStar analytics features requires that you counter the effects of Reverse Path Filtering (RPF) if necessary. If your kernel does RPF by default, you must do **one** of the following to counter the effects:

- Disable RPF.
- Ensure there is a route to the source IP address of the probes pointing to the interface where those probes are received.
- Specify loose mode reverse filtering (if the source address is routable with any of the routes on any of the interfaces).

Two-VM Installation Requirements

A two-VM installation is one in which the JunosVM is not bundled with the NorthStar Controller software.

Disk and Memory Requirements

The disk and memory requirements for installing NorthStar Controller in an OpenStack or other hypervisor environment are described in Table 7 on page 26.

Table 7: Disk and Memory Requirements for NorthStar OpenStack Installation

VM	Virtual CPU	Virtual RAM	Disk Size	Virtual NIC
NorthStar Application VM	4	32 GB	100 GB	2 minimum
NorthStar-JunosVM	1	4 GB	20 GB	2 minimum

See Table 5 on page 21 for analytics and secondary collector server requirements.

VM Image Requirements

- The NorthStar Controller application VM is installed on top of a Linux VM, so Linux VM is required. You can obtain a Linux VM image in either of the following ways:

  - Use the generic version provided by most Linux distributors. Typically, these are cloud-based images for use in a cloud-init-enabled environment, and do not require a password. These images are fully compatible with OpenStack.
  - Create your own VM image. Some hypervisors, such as generic DVM, allow you to create your own VM image. We recommend this approach if you are not using OpenStack and your hypervisor does not natively support cloud-init.
- The JunosVM is provided in Qcow2 format when inside the NorthStar Controller bundle. If you download the JunosVM separately (not bundled with NorthStar) from the NorthStar download site, it is provided in VMDK format.
- The JunosVM image is only compatible with IDE disk controllers. You must configure the hypervisor to use IDE rather than SATA controller type for the JunosVM disk image.

```
glance image-update --property
hw_disk_bus=ide --property
hw_cdrom_bus=ide
```

JunosVM Version Requirements

If you have, and want to continue using a version of JunosVM older than Release 17.2R1, you can change the NorthStar configuration to support it, but segment routing support would not be available. See "Installing the NorthStar Controller" on page 45 for the configuration steps.

VM Networking Requirements

The following networking requirements must be met for the two-VM installation approach to be successful:

- Each VM requires the following virtual NICs:
  - One connected to the external network
  - One for the internal connection between the NorthStar application and the JunosVM
  - One connected to the management network if a different interface is required between the router facing and client facing interfaces
- We recommend a flat or routed network without any NAT for full compatibility.
- A virtual network with one-to-one NAT (usually referenced as a floating IP) can be used as long as BGP-LS is used as the topology acquisition mechanism. If IS-IS or OSPF adjacency is required, it should be established over a GRE tunnel.

> **NOTE:** A virtual network with n-to-one NAT is not supported.

Server Sizing Guidance

The guidance in this section should help you to configure your servers with sufficient memory to efficiently and effectively support the NorthStar Controller functions. The recommendations in this section are the result of internal testing combined with field data.

Server Requirements

The baseline server specifications presented here apply when the NorthStar application (including the NorthStar Planner and JunosVM) is co-located on the same server with analytics and the collector workers. Also included are server specifications for the NorthStar application, analytics, and secondary collectors on separate servers in the network.

Table 8 on page 28 describes the server specifications we recommend for various network sizes.

> **NOTE:** See our recommendations later in this section for additional disk space to accommodate JTI analytics in ElasticSearch, storing network events in Cassandra, and secondary collector (celery) memory requirements.

Table 8: Server Specifications by Network Size

	Extra Small • < 50 nodes • 20 PCCs • 10K LSPs	Small • < 150 nodes • 50 PCCs • 20K LSPs	Medium • < 500 nodes • 150 PCCs • 80K LSPs	Large • < 1000 nodes • 350 PCCs • 160K LSPs	Extra Large • < 5000 nodes • 1000 PCCs • 400K LSPs
NorthStar Application Server	• CPU: 4 core, 2.4G • RAM: 16G • HD: 150G	• CPU: 8 core, 2.4G • RAM: 64G • HD: 500G	• CPU: 16 core, 2.6G • RAM: 64G • HD: 1T	• CPU: 24 core, 2.8G • RAM: 128G • HD: 2T	• CPU: 24 core, 3.0G • RAM: 256G • HD: 3T
Analytics Server	• CPU: 2 core, 2.4G • RAM: 16G • HD: 150G	• CPU: 4 core, 2.4G • RAM: 64G • HD: 500G	• CPU: 8 core, 2.6G • RAM: 96G • HD: 500G	• CPU: 16 core, 2.6G • RAM: 128G • HD: 2T	• CPU: 16 core, 2.8G • RAM: 256G • HD: 3T

Table 8: Server Specifications by Network Size *(continued)*

	Extra Small • < 50 nodes • 20 PCCs • 10K LSPs	Small • < 150 nodes • 50 PCCs • 20K LSPs	Medium • < 500 nodes • 150 PCCs • 80K LSPs	Large • < 1000 nodes • 350 PCCs • 160K LSPs	Extra Large • < 5000 nodes • 1000 PCCs • 400K LSPs
Secondary Collectors (installed with collector.sh)	• CPU: 2 core, 2.4G • RAM: 4G • HD: 50G	• CPU: 4 core, 2.4G • RAM: 8G • HD: 150G	• CPU: 8 core, 2.6G • RAM: 16G • HD: 500G	• CPU: 16 core, 2.6G • RAM: 16G • HD: 500G **NOTE:** At least two secondary collectors with the stated specifications required for a large network.	• CPU: 16 core, 2.8G • RAM: 32G • HD: 500G **NOTE:** At least five secondary collectors with the stated specifications required for an extra large network.

NOTE: An extra small all-in-one server network is rarely large enough for a production environment, but could be suitable for a demo or trial.

Additional Disk Space for JTI Analytics in ElasticSearch

Considerable storage space is needed to support JTI analytics in ElasticSearch. Each JTI record event requires approximately 330 bytes of disk space. A reasonable estimate of the number of events generated is (<num-of-interfaces> + <number-of-LSPs>) ÷ reporting-interval-in-seconds = events per second.

So for a network with 500 routers, 50K interfaces, and 60K LSPs, with a configured five-minute reporting interval (300 seconds), you can expect something in the neighborhood of 366 events per second to be generated. At 330 bytes per event, it comes out to 366 events x 330 bytes x 86,400 seconds in a day = over 10G of disk space per day or 3.65T per year. For the same size network, but with a one-minute reporting interval (60 seconds), you would have a much larger disk space requirement—over 50G per day or 18T per year.

There is an additional roll-up event created per hour per element for data aggregation. In a network with 50K interfaces and 60K LSPs (total of 110K elements), you would have 110K roll-up events per hour. In

terms of disk space, that would be 110K events per hour x 330 bytes per event x 24 hours per day = almost 1G of disk space required per day.

For a typical network of about 100K elements (interfaces + LSPs), we recommend that you allow for an additional 11G of disk space per day if you have a five-minute reporting interval, or 51G per day if you have a one-minute reporting interval.

See *NorthStar Analytics Raw and Aggregated Data Retention* in the *NorthStar Controller User Guide* for information about customizing data aggregation and retention parameters to reduce the amount of disk space required by ElasticSearch.

Additional Disk Space for Network Events in Cassandra

The Cassandra database is another component that requires additional disk space for storage of network events.

Using that same example of 50K interfaces and 60K LSPs (110 elements) and estimating one event every 15 minutes (900 seconds) per element, there would be 122 events per second. The storage needed would then be 122 events per second x 300 bytes per event x 86,400 seconds per day = about 3.2 G per day, or 1.2T per year.

Using one event every 5 minutes per element as an estimate instead of every 15 minutes, the additional storage requirement is more like 9.6G per day or 3.6T per year.

For a typical network of about 100K elements (interfaces + LSPs), we recommend that you allow for an additional 3-10G of disk space per day, depending on the rate of event generation in your network.

By default, NorthStar keeps event history for 35 days. To customize the number of days event data is retained:

1. Modify the dbCapacity parameter in **/opt/northstar/data/web_config.json**

2. Restart the pruneDB process using the **supervisorctl restart infra:prunedb** command.

Collector (Celery) Memory Requirements

When you use the collector.sh script to install secondary collectors on a server separate from the NorthStar application (for distributed collection), the script installs the default number of collector workers described in Table 9 on page 31. The number of celery processes started by each worker is the number of cores in the CPU plus one. So in a 32-core server (for example), the one installed default worker would start 33 celery processes. Each celery process uses about 50M of RAM.

Table 9: Default Workers, Processes, and Memory by Number of CPU Cores

CPU Cores	Workers Installed	Total Worker Processes	Minimum RAM Required
1-4	4	20 (CPUs +1) x 4 = 20	1 GB
5-8	3	18 (CPUs +1) x 2 = 18	1 GB
16	1	17 (CPUs +1) x 1 = 17	1 GB
32	1	33 (CPUs +1) x 1 = 33	2 GB

See "Secondary Collector Installation for Distributed Data Collection" on page 151 for more information about distributed data collection and secondary workers.

The default number of workers installed is intended to optimize server resources, but you can change the number by using the provided config_celery_workers.sh script. See "Collector Worker Installation Customization" on page 150 for more information. You can use this script to balance the number of workers installed with the amount of memory available on the server.

> **NOTE:** This script is also available to change the number of workers installed on the NorthStar application server from the default, which also follows the formulas shown in Table 9 on page 31.

Upgrading from Pre-4.3 NorthStar with Analytics

IN THIS SECTION

- Export Existing Data (Recommended) | 32
- Upgrade Procedure with NorthStar Application and NorthStar Analytics on the Same Server | 35
- Upgrade Procedure with NorthStar Application and NorthStar Analytics on Separate Servers | 36

Update the Netflow Aggregation Parameter | 37
Import Existing Data (Recommended) | 38

The special upgrade procedure described in this topic is only necessary if you use NorthStar Analytics **and** you are upgrading to NorthStar Release 5.1 from a version of NorthStar earlier than Release 4.3.

In all other cases, you can install NorthStar using the procedure described in "Installing the NorthStar Controller" on page 45.

Export Existing Data (Recommended)

This procedure involves running a utility called es_export_import_util.py on the NorthStar application server to export and save your existing data prior to upgrade.

The utility exports data to a file called exportdata.tar.Z in the **/opt/northstar/northstar_bundle_5.1.0/db_migration** directory.

> **NOTE:** db_migration directory will be created after RPM bundle is installed (Step 3 in "Step-by-Step Procedure" on page 33).

Ensure that this directory has available space equivalent to at least 10% the size of your Elasticsearch database. For example, a 10GB Elasticsearch database would require 1GB in the **/opt/northstar/northstar_bundle_5.1.0/db_migration** directory.

> **NOTE:** Elasticsearch (ES) data is stored on NorthStar Analytics server (if analytics is installed on a separate server than the application) under **/opt/northstar/data/elasticsearch/** directory. You can measure the space of this directory as an estimate of ES DB size using the following command:
>
> ```
> du -hs /opt/northstar/data/elasticsearch/
> ```

When you begin this procedure, the script will tell you how much disk space is required and give you the option to stop the procedure if you do not have enough space to continue.

The amount of time required for the export utility to complete depends on the number of export days and Elasticsearch cache memory/CPU cores you have. You can use the utility's **-l** option to reduce the number of export days.

You can use the following command to see the utility's full set of supported export options:

```
es_export_import_util.py --help
```

To export and save your existing data, use the following procedure:

1. Download the NorthStar 5.1.0 software from the NorthStar Controller Software Download page.

2. Transfer the downloaded tar.gz file to the NorthStar application server.

3. Untar the Northstar_bundle:

   ```
   [root ~]# tar zxf <filename.tar.gz>
   ```

4. Install the RPM bundle:

   ```
   [root ~]# rpm -Uvh northStar_bundle_5_1_0/<rpm-filename>
   ```

5. Navigate to the db_migration directory:

   ```
   [root ~]# cd /opt/northstar/northstar_bundle_5.1.0/db_migration
   ```

6. Launch the export utility and type **yes** to continue if you agree with the setup information provided. An example follows:

   ```
   [root db_migration]# ./es_export_import_util.py -exp

   Warning 1: Time taken for export util depends on number of export days and ES
   cache memory/CPU cores. Reduce the considered number of days using -l option.
   Warning 2: Total indexes=6 and total DB indexes size=599MB. Average DB size of
   an index=99MB and max export DB limit=50000MB.
   Considering export data for last 6 days, requires disk space of 59.4MB under
   current dir

   Please enter 'yes' or 'no' to proceed:yes
   Starting ES data export
   Logs stored at /opt/northstar/logs/es_export_import.log
   ```

```
Export required for datatype=jvision-lsp for the last 6 days
Export required for datatype=jvision-ifd for the last 6 days
Export required for datatype=jvision-ifl for the last 6 days
Export required for datatype=demands for the last 6 days
Export required for datatype=as_demands for the last 6 days
Export required for datatype=rpm-ifl for the last 6 days
Export required for datatype=jnx-cos for the last 6 days
Starting 2 EsExportWorker process with total ES query count in queue=144
Starting process EsExportWorker-0
Starting process EsExportWorker-1
Total rollups data added=13187( jvision-lsp=743 jvision-ifd=8136 jvision-ifl=3230
 demands=0 as_demands=0 rpm-ifl=1079 jnx-cos=0) EsExportWorkers-1 completed in
minutes=1
Total rollups data added=13378( jvision-lsp=637 jvision-ifd=8424 jvision-ifl=3325
 demands=0 as_demands=0 rpm-ifl=993 jnx-cos=0) EsExportWorkers-0 completed in
minutes=1
All EsExportWorker processes completed.
Rollup data exported to ./exportdata.tar.gz . Total time taken in minutes=1
```

Next, upgrade the NorthStar server. Do one of the following:

- If NorthStar Application and NorthStar Analytics are on the same server, see “Upgrade Procedure with NorthStar Application and NorthStar Analytics on the Same Server” on page 35.
- If NorthStar Application and NorthStar Analytics are on separate servers, see “Upgrade Procedure with NorthStar Application and NorthStar Analytics on Separate Servers” on page 36.

Upgrade Procedure with NorthStar Application and NorthStar Analytics on the Same Server

NorthStar analytics must be reinstalled on each NorthStar application server. Use the following procedure:

1. Do one of the following:

   - If Junos VM is present on the same server as the NorthStar application and NorthStar analytics, back up your JunosVM configuration. (Restoration of the JunosVM configuration is performed automatically after the upgrade is complete as long as you use the **net_setup.py** utility to save your backup):

     a. Launch the **net_setup.py** script:

        ```
        [root@hostname~]# /opt/northstar/utils/net_setup.py
        ```

     b. Type **D** and press **Enter** to select Maintenance and Troubleshooting.

     c. Type **1** and press **Enter** to select Backup JunosVM Configuration.

     d. Confirm the backup JunosVM configuration is stored at '**/opt/northstar/data/junosvm/junosvm.conf**'.

   - If Junos VM is present on a different server, separate from the NorthStar application and NorthStar analytics, proceed to Step 2.

2. Save the iptables.

   ```
   iptables-save > /opt/northstar/data/iptables.conf
   ```

3. On the NorthStar application server, navigate to the NorthStar 5.1.0 directory:

   ```
   [root ~]# cd /opt/northstar/northstar_bundle_5.1.0
   ```

4. Uninstall NorthStar analytics:

   ```
   [root northstar_bundle_5.1.0]# ./uninstall-analytics.sh
   ```

5. If Junos VM is present on the same server as the NorthStar application and NorthStar analytics, uninstall the NorthStar JunosVM RPM:

   ```
   [root northstar_bundle_5.1.0]# rpm -e NorthStar-JunosVM
   ```

6. Uninstall Python and its dependency RPMs, and upgrade the NorthStar application:

```
[root northstar_bundle_5.1.0]# rpm -e --quiet NorthStar NorthStar-Utils
NorthStar-Python
[root northstar_bundle_5.1.0]# ./install.sh
```

7. Reinstall NorthStar analytics:

```
[root northstar_bundle_5.1.0]# ./install-analytics.sh
```

Upgrade Procedure with NorthStar Application and NorthStar Analytics on Separate Servers

1. On the NorthStar application server, navigate to the NorthStar 5.1.0 directory:

```
[root ~]# cd /opt/northstar/northstar_bundle_5.1.0
```

2. Upgrade the NorthStar application:

```
[root northstar_bundle_5.1.0]# ./install.sh
```

3. On each NorthStar analytics server:
   a. Untar the Northstar_bundle:

```
[root ~]# tar zxf <filename.tar.gz>
```

   b. Install the RPM bundle:

```
[root ~]# rpm -Uvh northStar_bundle_5_1_0/<rpm-filename>
```

   c. Navigate to the db_migration directory:

```
[root ~]# cd /opt/northstar/northstar_bundle_5.1.0/db_migration
```

   d. Uninstall and reinstall NorthStar analytics:

```
[root northstar_bundle_5.1.0]# cd /opt/northstar/northstar_bundle_5.1.0
./uninstall-analytics.sh

(wait for completion)
[root northstar_bundle_5.1.0]# ./install-analytics.sh
```

4. On the NorthStar application server, prepare and redeploy HA analytics data collector settings:

   ```
   [root northstar_bundle_5.1.0]# /opt/northstar/utils/net_setup.py
   ```

   Select **G** (Data Collector Setting) from the main menu, and then **B** (Prepare and Deploy HA Data Collector Setting) from the Data Collector Configuration Settings menu. See "Installing Data Collectors for Analytics" on page 112 for more information.

5. On the NorthStar application server, ensure that analytics data collector connectivity is UP. From the net_setup.py utility main menu, select **G** (Data Collector Setting), and then select **9** (Test Data Collector Connectivity) from the Data Collector Configuration Settings menu.

Update the Netflow Aggregation Parameter

Between NorthStar Controller Release 4.2.0 and 4.3.0, the possible values for the netflow_aggregate_by_prefix parameter changed. If you are ugrading from Release 4.2.0, you must edit the parameter in the **/opt/northstar/data/northstar.cfg** file to reflect a valid Release 5.1.0 value.

To edit the value, perform the following steps:

1. SSH to the NorthStar server.

2. Using a text editor such as vi, edit the netflow_aggregate_by_prefix= statement in the **/opt/northstar/data/northstar.cfg** file as follows:

   - If you had the value set to **1** in NorthStar Controller Release 4.2.0, change the value to **always**.
   - If you had the value set to **0** in NorthStar Controller Release 4.2.0, change the value to **disabled**.

3. Manually restart the netflowd process:

   ```
   [root ~]# supervisorctl restart analytics:netflowd
   ```

Import Existing Data (Recommended)

In this procedure, you run the es_export_import_util.py utility again on the NorthStar application server to import the data you previously exported and saved.

1. Log in to the NorthStar application server.

2. Navigate to the db_migration directory:

```
[root ~]# cd /opt/northstar/northstar_bundle_5.1.0/db_migration
```

3. Launch the import utility:

```
[root db_migration]# ./es_export_import_util.py -imp
```

RELATED DOCUMENTATION

Installing the NorthStar Controller | 45

Installing Data Collectors for Analytics | 112

Changing Control Packet Classification Using the Mangle Table

The NorthStar application uses default classification for control packets. To support a different packet classification, you can use Linux firewall iptables to reclassify packets to a different priority.

The following sample configuration snippets show how to modify the ToS bits using the mangle table, changing DSCP values to cs6.

Zookeeper:

```
iptables -t mangle -A POSTROUTING -p tcp -sport 3888 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 3888 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -sport 2888 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 2888 -j DSCP -set-dscp-class cs6
```

Cassandra database:

```
iptables -t mangle -A POSTROUTING -p tcp -sport 7001 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 7001 -j DSCP -set-dscp-class cs6

iptables -t mangle -A POSTROUTING -p tcp -sport 17000 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 17000 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -sport 7199 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 7199 -j DSCP -set-dscp-class cs6
```

RabbitMQ:

```
iptables -t mangle -A POSTROUTING -p tcp -sport 25672 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 25672 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -sport 15672 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 15672 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -sport 4369 -j DSCP -set-dscp-class cs6
iptables -t mangle -A POSTROUTING -p tcp -dport 4369 -j DSCP -set-dscp-class cs6
```

NTAD:

```
iptables -t mangle -A POSTROUTING -p tcp -dport 450 -j DSCP -set-dscp-class cs6
```

PCEP protocol:

```
iptables -t mangle -A POSTROUTING -p tcp -sport 4189 -j DSCP -set-dscp-class cs6
```

ICMP packets used by ha_agent (replace the variable *NET-SUBNET* with your configured network subnet):

```
iptables -t mangle -A POSTROUTING -p icmp -s NET-SUBNET –d NET-SUBNET -j DSCP
-set-dscp-class cs6
```

To verify that the class of service setting matches best effort, use the following command on the NorthStar server:

```
tcpdump -i interface-name -v -n -s 1500 “(src host host-IP ) && (ip[1]==0)”
```

To verify that the class of service setting matches cs6, use the following command on the NorthStar server:

```
tcpdump -i interface-name -v -n -s 1500 “(src host host-IP ) && (ip[1]==192)”
```

Renew SSL Certificates for NorthStar Web UI

NorthStar generates SSL certificates during installation. You can renew or replace these SSL certificates generated during installation with the trusted certificates issued or approved by the information technology department in your organization. This topic describes how to replace the SSL certificates for web processes.

The SSL certificate files **cert.pem** and **key.pem** are located at **/opt/northstar/web/certs/**. Both these certificates are in X.509 format and you must restart the web process after you replace the files.

For internal server communications to happen seamlessly, the servers must have valid security certificates installed. However, these certificates do not affect the web processes, and needs to be replaced or renewed only if your security team needs you to do so.

SSL certificates for individual servers are located in these locations:

- Health Monitor—**/opt/northstar/healthMonitor/certs**
- ES Proxy—**/opt/northstar/esauthproxy/certs**
- Web Health—**/opt/northstar/web/routes/v1/health/certs**
- SNMP Collection—**/opt/northstar/snmp-collector/conf**

To replace the SSL certificates for NorthStar web UI:

1. Establish an SSH connection to device on which NorthStar in installed.

2. Navigate to **/opt/northstar/web/**.

```
user@host:~$ cd /opt/northstar/web/
user@host:~/web$ ls -l
total 264
-rwx------.   1 pcs pcs    166 Dec  4  2020 appGlobals.js*
-rwx------.   1 pcs pcs  46457 Jun  3 11:56 app.js*
drwx------.   2 pcs pcs     37 Dec  4  2020 certs/
drwx------.  11 pcs pcs    153 Mar 15 20:07 client/
...
drwx------.   7 pcs pcs   4096 May  7 11:21 test/
drwx------.   6 pcs pcs   4096 May  7 11:22 thirdparty/
drwx------.   2 pcs pcs     55 May  7 11:22 util/
drwx------.   3 pcs pcs     17 Mar 15 20:08 webstart/
```

3. Locate the folder named **certs**. The trusted SSL certificates are stored in this folder.

```
user@host:~/web$ cd certs/
user@host:~/web/certs$ ls -l
total 8
-rwx------. 1 pcs pcs 1294 Feb 17 07:14 cert.pem*
-rwx------. 1 pcs pcs 1679 Feb 17 07:14 key.pem*
```

- cert.pem—Certificate file
- key.pem—Key used to generate the certificate.

4. Verify expiration date of the current SSL certificates.

```
user@host:~/web/certs$ openssl x509 -enddate -noout -in cert.pem
notAfter=Apr 28 12:14:11 2023 GMT
```

5. Run the following command to view the contents of the certificate file:

```
user@host:~/web/certs$ openssl x509  -in cert.pem
```

6. Copy the new certificate files and back up the existing certificate files. You can use the backed up certificate files to restore them later in case you face any issue.

```
user@host:~/web/certs$ cp cert.pem cert.pem.bak
user@host:~/web/certs$ cp key.pem key.pem.bak

user@host:~/web/certs$ ls -l
total 16
-rwx------. 1 pcs pcs 1294 Feb 17 07:14 cert.pem*
-rwx------. 1 pcs pcs 1294 Jul  9 11:55 cert.pem.bak*
-rwx------. 1 pcs pcs 1679 Feb 17 07:14 key.pem*
-rwx------. 1 pcs pcs 1679 Jul  9 11:55 key.pem.bak*
```

NOTE: The names of the certificate files must be **cert.pem** and **key.pem**, respectively.

7. (Optional) Verify the status of the severs and web processes.

```
user@host:~/web/certs$ supervisorctl status
bmp:bmpMonitor                   RUNNING   pid 2492, uptime 42 days, 22:05:18
```

```
collector:worker1                RUNNING   pid 9737, uptime 42 days, 22:02:59
collector:worker2                RUNNING   pid 9739, uptime 42 days, 22:02:59
collector:worker3                RUNNING   pid 9738, uptime 42 days, 22:02:59
collector:worker4                RUNNING   pid 9740, uptime 42 days, 22:02:59
...
web:app                          RUNNING   pid 7769, uptime 29 days, 0:47:11
web:gui                          RUNNING   pid 6536, uptime 29 days, 1:01:44
web:notification                 RUNNING   pid 6530, uptime 29 days, 1:01:44
web:planner                      RUNNING   pid 6529, uptime 29 days, 1:01:44
web:proxy                        RUNNING   pid 6533, uptime 29 days, 1:01:44
web:restconf                     RUNNING   pid 6535, uptime 29 days, 1:01:44
web:resthandler                  RUNNING   pid 6532, uptime 29 days, 1:01:44
```

8. Restart the web processes for the changes to take effect.

```
user@host:~/web/certs$ supervisorctl restart web:*
web:proxy: stopped
web:planner: stopped
web:notification: stopped
web:resthandler: stopped
web:gui: stopped
web:app: stopped
web:restconf: stopped
web:planner: started
web:notification: started
web:app: started
web:resthandler: started
web:proxy: started
web:restconf: started
web:gui: started
user@host:~/web/certs$
```

9. Verify that the severs and web processes are running after the restart.

```
user@host:~/web/certs$ supervisorctl status
bmp:bmpMonitor                   RUNNING   pid 2492, uptime 42 days, 22:06:10
collector:worker1                RUNNING   pid 9737, uptime 42 days, 22:03:51
collector:worker2                RUNNING   pid 9739, uptime 42 days, 22:03:51
collector:worker3                RUNNING   pid 9738, uptime 42 days, 22:03:51
collector:worker4                RUNNING   pid 9740, uptime 42 days, 22:03:51
...
web:app                          RUNNING   pid 14383, uptime 0:00:15
```

```
web:gui                          RUNNING   pid 14387, uptime 0:00:15
web:notification                 RUNNING   pid 14382, uptime 0:00:15
web:planner                      RUNNING   pid 14381, uptime 0:00:15
web:proxy                        RUNNING   pid 14385, uptime 0:00:15
web:restconf                     RUNNING   pid 14386, uptime 0:00:15
web:resthandler                  RUNNING   pid 14384, uptime 0:00:15
user@host:~/web/certs$
```

The certificates have been successfully renewed and web services restarted. You can now verify the certificate information from your web browser.

NOTE: NorthStar overwrites any user-defined certificates during an upgrade. You need to replace the certificates again after an upgrade.

2

CHAPTER

NorthStar Controller Installation on a Physical Server

Installing the NorthStar Controller | 45

Uninstalling the NorthStar Controller Application | 72

Installing the NorthStar Controller

IN THIS SECTION

- Download the NorthStar Controller Software | 47
- If Upgrading, Back Up Your JunosVM Configuration and iptables | 47
- Install NorthStar Controller | 47
- Configure Support for Different JunosVM Versions | 49
- Create Passwords | 51
- Enable the NorthStar License | 51
- Adjust Firewall Policies | 52
- Launch the Net Setup Utility | 52
- Configure the Host Server | 54
- Configure the JunosVM and its Interfaces | 59
- Configure Junos cRPD Settings | 64
- Set Up the SSH Key for External JunosVM | 66
- Upgrade the NorthStar Controller Software in an HA Environment | 68

You can use the procedures described in the following sections if you are performing a fresh install of NorthStar Controller or upgrading from an earlier release, *unless you are using NorthStar analytics and are upgrading from a release older than NorthStar 4.3*. Steps that are not required if upgrading are noted.

> **NOTE:** If you are upgrading from a release older than NorthStar 4.3 and you *are* using NorthStar analytics, you must upgrade NorthStar manually using the procedure described in "Upgrading from Pre-4.3 NorthStar with Analytics" on page 31.

The NorthStar software and data are installed in the /opt directory. Be sure to allocate sufficient disk space. See "NorthStar Controller System Requirements" on page 21 for our memory recommendations.

> **NOTE:** When upgrading NorthStar Controller, ensure that the /tmp directory has enough free space to save the contents of the /opt/pcs/data directory because the /opt/pcs/data directory contents are backed up to /tmp during the upgrade process.

If you are installing NorthStar for a high availability (HA) cluster, ensure that:

- You configure each server individually using these instructions before proceeding to HA setup.
- The database and rabbitmq passwords are the same for all servers that will be in the cluster.
- All server time is synchronized by NTP using the following procedure:

  1. Install NTP.

     ```
     yum -y install ntp
     ```

  2. Specify the preferred NTP server in ntp.conf.

  3. Verify the configuration.

     ```
     ntpq -p
     ```

     NOTE: All cluster nodes must have the same time zone and system time settings. This is important to prevent inconsistencies in the database storage of SNMP and LDP task collection delta values.

NOTE: To upgrade NorthStar Controller in an HA cluster environment, see "Upgrade the NorthStar Controller Software in an HA Environment" on page 68.

The following sections describe the download, installation, and initial configuration of the NorthStar Controller.

NOTE: The NorthStar Controller software includes a number of third-party packages. To avoid possible conflict, we recommend that you only install these packages as part of the NorthStar Controller RPM bundle installation rather than installing them manually.

For HA setup after all the servers that will be in the cluster have been configured, see "Configuring a NorthStar Cluster for High Availability" on page 154.

Download the NorthStar Controller Software

The NorthStar Controller software download page is available at https://www.juniper.net/support/downloads/?p=northstar#sw.

1. From the Version drop-down list, select the version number.

2. Click the NorthStar Application (which includes the RPM bundle) and the NorthStar JunosVM to download them.

If Upgrading, Back Up Your JunosVM Configuration and iptables

If you are doing an upgrade from a previous NorthStar release, and you previously installed NorthStar and Junos VM together, back up your JunosVM configuration before installing the new software. Restoration of the JunosVM configuration is performed automatically after the upgrade is complete as long as you use the *net_setup.py* utility to save your backup.

1. Launch the *net_setup.py* script:

   ```
   [root@hostname~]# /opt/northstar/utils/net_setup.py
   ```

2. Type **D** and press **Enter** to select Maintenance and Troubleshooting.

3. Type **1** and press **Enter** to select Backup JunosVM Configuration.

4. Confirm the backup JunosVM configuration is stored at **'/opt/northstar/data/junosvm/junosvm.conf'**.

5. Save the iptables.

   ```
   iptables-save > /opt/northstar/data/iptables.conf
   ```

Install NorthStar Controller

You can either install the RPM bundle on a physical server or use a two-VM installation method in an OpenStack environment, in which the JunosVM is not bundled with the NorthStar Controller software.

The following optional parameters are available for use with the *install.sh* command:

--vm—Same as ./install-vm.sh, creates a two-VM installation.

--crpd—Creates a cRPD installation.

--skip-bridge—For a physical server installation, skips checking if the external0 and mgmt0 bridges exist.

The default bridges are external0 and mgmt0. If you have two interfaces such as eth0 and eth1 in the physical setup, you must configure the bridges to those interfaces. However, you can also define any bridge names relevant to your deployment.

> **NOTE:** We recommend that you configure the bridges before running *install.sh*.

> **NOTE:** Bridges are not used with cRPD installations.

- For a physical server installation, execute the following commands to install NorthStar Controller:

```
[root@hostname~]# yum install <rpm-filename>
[root@hostname~]# cd /opt/northstar/northstar_bundle_x.x.x/
[root@hostname~]# ./install.sh
```

> **NOTE:** yum install works for both upgrade and fresh installation.

- For a two-VM installation, execute the following commands to install NorthStar Controller:

```
[root@hostname~]# yum install <rpm-filename>
[root@hostname~]# cd /opt/northstar/northstar_bundle_x.x.x/
[root@hostname~]# ./install-vm.sh
```

> **NOTE:** yum install works for both upgrade and fresh installation.

The script offers the opportunity to change the JunosVM IP address from the system default of 172.16.16.2.

```
Checking current disk space
INFO: Current available disk space for /opt/northstar is 34G. Will proceed
with installation.
System currently using 172.16.16.2 as NTAD/junosvm ip
Do you wish to change NTAD/junosvm ip (Y/N)? y
```

```
Please specify junosvm ip:
```

- For a cRPD installation, you must have:
  - CentOS or Red Hat Enterprise Linux 7.x. Earlier versions are not supported.
  - A Junos cRPD license. For information about cRPD, including how to obtain a license, see cRPD Documentation in the Juniper Networks TechLibrary.

> **NOTE:** If you require multiple BGP-LS peering on different subnets for different AS domains at the same time, you should choose the default JunosVM approach. This configuration for cRPD is not supported.

For a cRPD installation, execute the following commands to install NorthStar Controller:

```
[root@hostname~]# yum install <rpm-filename>
[root@hostname~]# cd /opt/northstar/northstar_bundle_x.x.x/
[root@hostname~]# ./install.sh --crpd
```

> **NOTE:** yum install works for both upgrade and fresh installation.

Configure Support for Different JunosVM Versions

If you are using a two-VM installation, in which the JunosVM is not bundled with the NorthStar Controller, you might need to edit the northstar.cfg file to make the NorthStar Controller compatible with the external VM. Use the following procedure. **For a NorthStar cluster configuration, you must perform the procedure for each node in the cluster**.

> **NOTE:** This section is not applicable to cRPD installations.

1. SSH to the NorthStar server.

2. Using a text editor such as vi, edit the ntad_version statement in the **opt/northstar/data/northstar.cfg** file to the appropriate NTAD version according to Table 10 on page 50:

```
[root@ns]# vi /opt/northstar/data/northstar.cfg
...
# NTAD versions(1=No SR; 2=SR, no local addr; 3=V2+local addr 18.2; *4=V3+BGP
peer SID 18.3R2, 18.4R2; 5=V4+OSPF SR 19.1+)
ntad_version=version-number
```

Table 10: NTAD Versions by Junos OS Release

NTAD Version	Junos OS Release	Change
1	Earlier than Release 17.2	Initial version
2	17.2	Segment routing
3	18.2	NTAD version 2 + local address "Local address" refers to multiple secondary IP addresses on interfaces. This is especially relevant in certain use cases such as loopback interface for VPN-LSP binding.
4	18.3R2, 18.4R2	NTAD version 3 + BGP peer SID
5	19.1 and later	NTAD version 4 + OSPF SR

3. Manually restart the toposerver process:

```
[root@ns]# supervisorctl restart northstar:toposerver
```

4. Log into the Junos VM and restart NTAD:

```
restart network-topology-export
```

5. Set up the SSH key for the external VM by selecting option **H** from the Setup Main Menu when you run the net_setup.py script, and entering the requested information.

Create Passwords

NOTE: This step is not required if you are doing an upgrade rather than a fresh installation.

When prompted, enter new database/rabbitmq and web UI Admin passwords.

1. Create an initial database/rabbitmq password by typing the password at the following prompts:

```
Please enter new DB and MQ password (at least one digit, one lowercase, one
uppercase and no space):
Please confirm new DB and MQ password:
```

2. Create an initial Admin password for the web UI by typing the password at the following prompts:

```
Please enter new UI Admin password:
Please confirm new UI Admin password:
```

Enable the NorthStar License

NOTE: This step is not required if you are doing an upgrade rather than a fresh installation.

You must enable the NorthStar license as follows, unless you are performing an upgrade and you have an activated license.

1. Copy or move the license file.

```
[root@northstar]# cp /path-to-license-file/npatpw /opt/pcs/db/sys/npatpw
```

2. Set the license file owner to the PCS user.

```
[root@northstar]# chown pcs:pcs /opt/pcs/db/sys/npatpw
```

3. Restart the necessary NorthStar Controller processes.

```
[root@northstar]# supervisorctl restart northstar_pcs:* && supervisorctl restart
 infra:web
```

4. Check the status of the NorthStar Controller processes until they are all up and running.

```
[root@northstar]# supervisorctl status
```

Adjust Firewall Policies

The iptables default rules could interfere with NorthStar-related traffic. If necessary, adjust the firewall policies.

Refer to "NorthStar Controller System Requirements" on page 21 for a list of ports that must be allowed by iptables and firewalls.

Launch the Net Setup Utility

NOTE: This step is not required if you are doing an upgrade rather than a fresh installation.

Launch the *Net Setup* utility to perform host server configuration.

```
[root@northstar]# /opt/northstar/utils/net_setup.py
```

The main menu that appears is slightly different depending on whether your installation uses Junos VM or is a cRPD installation.

For Junos VM installations (installation on a physical server or a two-server installation), the main menu looks like this:

```
Main Menu:
    ..........................................
    A.) Host Setting
    ..........................................
    B.) JunosVM Setting
```

```
    ........................................
    C.) Check Network Setting
    ........................................
    D.) Maintenance & Troubleshooting
    ........................................
    E.) HA Setting
    ........................................
    F.) Collect Trace/Log
    ........................................
    G.) Analytics Data Collector Setting
      (External standalone/cluster analytics server)
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
```

For cRPD installations, the main menu looks like this:

```
Main Menu:
    ........................................
    A.) Host Setting
    ........................................
    B.) Junos CRPD Setting
    ........................................
    C.) Check Network Setting
    ........................................
    D.) Maintenance & Troubleshooting
    ........................................
    E.) HA Setting
    ........................................
    F.) Collect Trace/Log
    ........................................
    G.) Analytics Data Collector Setting
      (External standalone/cluster analytics server)
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
```

Notice that option B is specific to cRPD and option H is not available as it is not relevant to cRPD.

Configure the Host Server

> **NOTE:** This step is not required if you are doing an upgrade rather than a fresh installation.

1. From the NorthStar Controller setup Main Menu, type **A** and press **Enter** to display the Host Configuration menu:

```
Host Configuration:
 ******************************************************
 In order to commit your changes you must select option Z
 ******************************************************
 ........................................
 1. ) Hostname                                  : northstar
 2. ) Host default gateway                      :
 3A.) Host Interface #1 (external_interface)
         Name                                   : external0
         IPv4                                   :
         Netmask                                :
         Type (network/management)              : network
 3B.) Delete Host Interface #1 (external_interface) data
 4A.) Host Interface #2 (mgmt_interface)
         Name                                   : mgmt0
         IPv4                                   :
         Netmask                                :
         Type (network/management)              : management
 4B.) Delete Host Interface #2 (mgmt_interface) data
 5A.) Host Interface #3
         Name                                   :
         IPv4                                   :
         Netmask                                :
         Type (network/management)              : network
 5B.) Delete Host Interface #3 data
 6A.) Host Interface #4
         Name                                   :
         IPv4                                   :
         Netmask                                :
         Type (network/management)              : network
 6B.) Delete Host Interface #4 data
```

```
   7A.) Host Interface #5
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type (network/management)               : network
   7B.) Delete Host Interface #5 data
   8. ) Show Host current static route
   9. ) Show Host candidate static route
   A. ) Add Host candidate static route
   B. ) Remove Host candidate static route

   ........................................
   X. ) Host current setting
   Y. ) Apply Host static route only
   Z. ) Apply Host setting and static route
   ........................................
   ........................................

Please select a number to modify.
[<CR>=return to main menu]:
```

To interact with this menu, type the number or letter corresponding to the item you want to add or change, and press **Enter**.

2. Type **1** and press **Enter** to configure the hostname. The existing hostname is displayed. Type the new hostname and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
1
current host hostname : northstar
new host hostname : node1
```

3. Type **2** and press **Enter** to configure the host default gateway. The existing host default gateway IP address (if any) is displayed. Type the new gateway IP address and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
2
current host default_gateway :
new host default_gateway : 10.25.152.1
```

4. Type **3A** and press **Enter** to configure the host interface #1 (external_interface). The first item of existing host interface #1 information is displayed. Type each item of new information (interface name, IPv4 address, netmask, type), and press **Enter** to proceed to the next.

   NOTE: The designation of network or management for the type of interface is a label only, for your convenience. NorthStar Controller does not use this information.

```
Please select a number to modify.
[<CR>=return to main menu]:
3A
current host interface1 name : external0
new host interface1 name : external0

current host interface1 ipv4 :
new host interface1 ipv4 : 10.25.153.6

current host interface1 netmask :
new host interface1 netmask : 255.255.254.0

current host interface1 type (network/management) : network
new host interface1 type (network/management) : network
```

5. Type **A** and press **Enter** to add a host candidate static route. The existing route, if any, is displayed. Type the new route and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
A
Candidate static route:
new static route (format: x.x.x.x/xy via a.b.c.d dev <interface_name>):
10.25.158.0/24 via 10.25.152.2 dev external0
```

6. If you have more than one static route, type **A** and press **Enter** again to add each additional route.

```
Please select a number to modify.
[<CR>=return to main menu]:
A
Candidate static route:
[0] 10.25.158.0/24 via 10.25.152.2 dev external0
```

```
new static route (format: x.x.x.x/xy via a.b.c.d dev <interface_name>):
10.25.159.0/24 via 10.25.152.2 dev external0
```

7. Type **Z** and press **Enter** to save your changes to the host configuration.

> **NOTE:** If the host has been configured using the CLI, the Z option is not required.

The following example shows saving the host configuration.

```
Host Configuration:
   *****************************************************
   In order to commit your changes you must select option Z
   *****************************************************
   ..........................................
   1. ) Hostname                                : node1
   2. ) Host default gateway                    : 10.25.152.1
   3A.) Host Interface #1 (external_interface)
            Name                                : external0
            IPv4                                : 10.25.153.6
            Netmask                             : 255.255.254.0
            Type (network/management)           : network
   3B.) Delete Host Interface #1 (external_interface) data
   4A.) Host Interface #2 (mgmt_interface)
            Name                                : mgmt0
            IPv4                                :
            Netmask                             :
            Type (network/management)           : management
   4B.) Delete Host Interface #2 (mgmt_interface) data
   5A.) Host Interface #3
            Name                                :
            IPv4                                :
            Netmask                             :
            Type (network/management)           : network
   5B.) Delete Host Interface #3 data
   6A.) Host Interface #4
            Name                                :
            IPv4                                :
            Netmask                             :
            Type (network/management)           : network
   6B.) Delete Host Interface #4 data
   7A.) Host Interface #5
```

```
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type (network/management)               : network
   7B.) Delete Host Interface #5 data
   8. ) Show Host current static route
   9. ) Show Host candidate static route
   A. ) Add Host candidate static route
   B. ) Remove Host candidate static route
   ........................................
   X.) Host current setting
   Y.) Apply Host static route only
   Z.) Apply Host setting and static route
   ........................................
   ........................................
Please select a number to modify.
[<CR>=return to main menu]:
z
Are you sure you want to setup host and static route configuration? This option
will restart network services/interfaces (Y/N) y
Current host/PCS network configuration:
host current interface external0 IP: 10.25.153.6/255.255.254.0
host current interface internal0 IP: 172.16.16.1/255.255.255.0
host current default gateway: 10.25.152.1
Current host static route:
[0] 10.25.158.0/24 via 10.25.152.2 dev external0
[1] 10.25.159.0/24 via 10.25.152.2 dev external0

Applying host configuration: /opt/northstar/data/net_setup.json
Please wait ...
Restart Networking ...
Current host static route:
[0] 10.25.158.0/24 via 10.25.152.2 dev external0
[1] 10.25.159.0/24 via 10.25.152.2 dev external0
Deleting current static routes ...
Applying candidate static routes
Static route has been added successfully for cmd 'ip route add 10.25.158.0/24 via
 10.25.152.2'
Static route has been added successfully for cmd 'ip route add 10.25.159.0/24 via
 10.25.152.2'
Host has been configured successfully
```

8. Press **Enter** to return to the Main Menu.

Configure the JunosVM and its Interfaces

This section applies to physical server or two-VM installations that use Junos VM. If you are installing NorthStar using cRPD, skip this section and proceed to "Configure Junos cRPD Settings" on page 64.

> **NOTE:** This step is not required if you are doing an upgrade rather than a fresh installation.

From the Setup Main Menu, configure the JunosVM and its interfaces. Ping the JunosVM to ensure that it is up before attempting to configure it. The net_setup script uses IP 172.16.16.2 to access the JunosVM using the login name **northstar**.

1. From the Main Menu, type **B** and press **Enter** to display the JunosVM Configuration menu:

```
Junos VM  Configuration Settings:
   ******************************************************
   In order to commit your changes you must select option Z
   ******************************************************
   ..................................................
   1. ) JunosVM hostname                          : northstar_junosvm
   2. ) JunosVM default gateway                   :
   3. ) BGP AS number                             : 100
   4A.) JunosVM Interface #1 (external_interface)
            Name                                  : em1
            IPv4                                  :
            Netmask                               :
            Type(network/management)              : network
            Bridge name                           : external0
   4B.) Delete JunosVM Interface #1 (external_interface) data
   5A.) JunosVM Interface #2 (mgmt_interface)
            Name                                  : em2
            IPv4                                  :
            Netmask                               :
            Type(network/management)              : management
            Bridge name                           : mgmt0
5B.) Delete JunosVM Interface #2 (mgmt_interface) data
   6A.) JunosVM Interface #3
            Name                                  :
            IPv4                                  :
            Netmask                               :
            Type(network/management)              : network
            Bridge name                           :
   6B.) Delete JunosVM Interface #3 data
```

```
   7A.) JunosVM Interface #4
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type(network/management)                : network
            Bridge name                             :
7B.) Delete JunosVM Interface #4 data
   8A.) JunosVM Interface #5
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type(network/management)                : network
            Bridge name                             :
   8B.) Delete JunosVM Interface #5 data
   9. ) Show JunosVM current static route
   A. ) Show JunosVM candidate static route
   B. ) Add JunosVM candidate static route
   C. ) Remove JunosVM candidate static route

   ..............................................
   X. ) JunosVM current setting
   Y. ) Apply JunosVM static route only
   Z. ) Apply JunosVM Setting and static route
   ..............................................

Please select a number to modify.
[<CR>=return to main menu]:
```

To interact with this menu, type the number or letter corresponding to the item you want to add or change, and press **Enter**.

2. Type **1** and press **Enter** to configure the JunosVM hostname. The existing JunosVM hostname is displayed. Type the new hostname and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
1
current junosvm hostname : northstar_junosvm
new junosvm hostname : junosvm_node1
```

3. Type **2** and press **Enter** to configure the JunosVM default gateway. The existing JunosVM default gateway IP address is displayed. Type the new IP address and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
2
current junosvm default_gateway :
new junosvm default_gateway : 10.25.152.1
```

4. Type **3** and press **Enter** to configure the JunosVM BGP AS number. The existing JunosVM BGP AS number is displayed. Type the new BGP AS number and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
3
current junosvm AS Number : 100
new junosvm AS Number: 100
```

5. Type **4A** and press **Enter** to configure the JunosVM interface #1 (external_interface). The first item of existing JunosVM interface #1 information is displayed. Type each item of new information (interface name, IPv4 address, netmask, type), and press **Enter** to proceed to the next.

> **NOTE:** The designation of network or management for the type of interface is a label only, for your convenience. NorthStar Controller does not use this information.

```
Please select a number to modify.
[<CR>=return to main menu]:
4A
current junosvm interface1 name : em1
new junosvm interface1 name: em1

current junosvm interface1 ipv4 :
new junosvm interface1 ipv4 : 10.25.153.144

current junosvm interface1 netmask :
new junosvm interface1 netmask : 255.255.254.0

current junosvm interface1 type (network/management) : network
new junosvm interface1 type (network/management) : network

current junosvm interface1 bridge name : external0
new junosvm interface1 bridge name : external0
```

6. Type **B** and press **Enter** to add a JunosVM candidate static route. The existing JunosVM candidate static route (if any) is displayed. Type the new candidate static route and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
B
Candidate static route:
new static route (format: x.x.x.x/xy via a.b.c.d):
10.25.158.0/24 via 10.25.152.2
```

7. If you have more than one static route, type **B** and press **Enter** again to add each additional route.

```
Please select a number to modify.
[<CR>=return to main menu]:
B
Candidate static route:
[0] 10.25.158.0/24 via 10.25.152.2 dev any
new static route (format: x.x.x.x/xy via a.b.c.d):
10.25.159.0/24 via 10.25.152.2
```

> **NOTE:** If you are adding a route and not making any other additional configuration changes, you can use option Y on the menu to apply the JunosVM static route only, without restarting the NorthStar services.

8. Type **Z** and press **Enter** to save your changes to the JunosVM configuration.

   The following example shows saving the JunosVM configuration.

```
Junos VM  Configuration Settings:
   ******************************************************
   In order to commit your changes you must select option Z
   ******************************************************
   ..................................................
   1. ) JunosVM hostname                          : northstar_junosvm
   2. ) JunosVM default gateway                   :
   3. ) BGP AS number                             : 100
   4A.) JunosVM Interface #1 (external_interface)
            Name                                  : em1
            IPv4                                  :
            Netmask                               :
```

```
            Type(network/management)                : network
            Bridge name                             : external0
   4B.) Delete JunosVM Interface #1 (external_interface) data
   5A.) JunosVM Interface #2 (mgmt_interface)
            Name                                    : em2
            IPv4                                    :
            Netmask                                 :
            Type(network/management)                : management
            Bridge name                             : mgmt0
   5B.) Delete JunosVM Interface #2 (mgmt_interface) data
   6A.) JunosVM Interface #3
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type(network/management)                : network
            Bridge name                             :
   6B.) Delete JunosVM Interface #3 data
   7A.) JunosVM Interface #4
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type(network/management)                : network
            Bridge name                             :
   7B.) Delete JunosVM Interface #4 data
   8A.) JunosVM Interface #5
            Name                                    :
            IPv4                                    :
            Netmask                                 :
            Type(network/management)                : network
            Bridge name                             :
   8B.) Delete JunosVM Interface #5 data
   9. ) Show JunosVM current static route
   A. ) Show JunosVM candidate static route
   B. ) Add JunosVM candidate static route
   C. ) Remove JunosVM candidate static route
   ..............................................
   X.) JunosVM current setting
   Y.) Apply JunosVM static route only
   Z.) Apply JunosVM Setting and static route
   ..............................................

Please select a number to modify.
[<CR>=return to main menu]:
z
```

```
Are you sure you want to setup junosvm and static route configuration? (Y/N) y

Current junosvm network configuration:
junosvm current interface em0 IP: 10.16.16.2/255.255.255.0
junosvm current interface em1 IP: 10.25.153.144/255.255.254.0
junosvm current default gateway: 10.25.152.1
junosvm current asn: 100
Current junosvm static route:
[0] 10.25.158.0/24 via 10.25.152.2 dev any
[1] 10.25.159.0/24 via 10.25.152.2 dev any
Applying junosvm configuration ...
Please wait ...
Commit Success.
JunosVM has been configured successfully.
Please wait ... Backup Current JunosVM config ...

Connecting to JunosVM to backup the config ...
Please check the result at /opt/northstar/data/junosvm/junosvm.conf
JunosVm configuration has been successfully backed up
```

9. Press **Enter** to return to the Main Menu.

Configure Junos cRPD Settings

From the Setup Main Menu, configure the Junos cRPD settings. This section applies only to cRPD installations (not to installations that use Junos VM).

1. From the Main Menu, type **B** and press **Enter** to display the Junos cRPD Configuration menu:

```
Junos CRPD  Configuration Settings:
   ***************************************************
   In order to commit your changes you must select option Z
   ***************************************************
   .................................................
   1. ) BGP AS number                              : 65412
   2. ) BGP Monitor IPv4 Address                   : 172.25.153.154
   3. ) BGP Monitor Port                           : 10001
   .................................................
   X. ) Junos CRPD current setting
   Z. ) Apply Junos CRPD Setting
   .................................................
```

```
Please select a number to modify.
[<CR>=return to main menu]:
```

To interact with this menu, type the number or letter corresponding to the item you want to add or change, and press **Enter**. Notice that option Y in the lower section is omitted from this menu as it is not relevant to cRPD.

2. Type **1** and press **Enter** to configure the BGP AS number. The existing AS number is displayed. Type the new number and press **Enter**.

```
Please select a number to modify.
[<CR>=return to main menu]:
1
current BGP AS Number : 65412
new BGP AS Number : 64525
```

3. Type **2** and press **Enter** if you need to change the default BGP Monitor IPv4 Address. By default, BMP monitor runs on the same host as cRPD, and the address is configured based on the local address of the host. We therefore recommend **not** changing this address.

4. Type **3** and press **Enter** if you need to change the default BGP Monitor Port. We recommend **not** changing this port from the default of 10001. The BMP monitor listens on port 10001 for incoming BMP connections from the network. The connection is opened from cRPD, which runs on the same host as the BMP monitor.

5. Type Z and press Enter to save your configuration changes. The following example show saving the Junos cRPD configuration.

```
Junos CRPD  Configuration Settings:
   ******************************************************
   In order to commit your changes you must select option Z
   ******************************************************
   ..............................................
   1. ) BGP AS number                          : 64525
   2. ) BGP Monitor IPv4 Address               : 172.17.153.154
   3. ) BGP Monitor Port                       : 10001
   ..............................................
   X. ) Junos CRPD current setting
   Z. ) Apply Junos CRPD Setting
   ..............................................
```

```
Please select a number to modify.
[<CR>=return to main menu]:
z
Are you sure you want to setup junos crpd configuration? (Y/N) y

Current junos crpd  configuration:
junos crpd current bgp asn: 64525
junos crpd current bmp_host: 172.17.153.154
junos crpd bgp_port: 10001
Please wait ...
Commit Success.
Junos CRPD has been configured successfully.
```

Set Up the SSH Key for External JunosVM

This section only applies to two-VM installations. Skip this section if you are installing NorthStar using cRPD.

NOTE: This step is not required if you are doing an upgrade rather than a fresh installation.

For a two-VM installation, you must set up the SSH key for the external JunosVM.

1. From the Main Menu, type **H** and press **Enter**.

   ```
   Please select a number to modify.
   [<CR>=return to main menu]:
   H
   ```

   Follow the prompts to provide your JunosVM username and router login class (super-user, for example). The script verifies your login credentials, downloads the JunosVM SSH key file, and returns you to the main menu.

   For example:

   ```
   Main Menu:
       ..........................................
       A.) Host Setting
       ..........................................
   ```

```
    B.) JunosVM Setting
    ........................................
    C.) Check Network Setting
    ........................................
    D.) Maintenance & Troubleshooting
    ........................................
    E.) HA Setting
    ........................................
    F.) Collect Trace/Log
    ........................................
    G.) Analytics Data Collector Setting
      (External standalone/cluster analytics server)
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
H
Please provide JunosVM login:
admin

2 VMs Setup is detected

Script will create user: northstar. Please provide user northstar router login
class e.g super-user, operator:
super-user

The authenticity of host '10.49.118.181 (10.49.118.181)' can't be established.
RSA key fingerprint is xx:xx:xx:xx:xx:xx:xx:xx:xx:xx:xx:xx:xx:xx:xx:xx.
Are you sure you want to continue connecting (yes/no)? yes

Applying user northstar login configuration
Downloading JunosVM ssh key file. Login to JunosVM
Checking md5 sum. Login to JunosVM
SSH key has been sucessfully updated

Main Menu:
    ........................................
    A.) Host Setting
    ........................................
    B.) JunosVM Setting
```

```
    ........................................
    C.) Check Network Setting
    ........................................
    D.) Maintenance & Troubleshooting
    ........................................
    E.) HA Setting
    ........................................
    F.) Collect Trace/Log
    ........................................
    G.) Analytics Data Collector Setting
      (External standalone/cluster analytics server)
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
    ........................................

Please select a letter to execute.
```

Upgrade the NorthStar Controller Software in an HA Environment

There are some special considerations for upgrading NorthStar Controller when you have an HA cluster configured. Use the following procedure:

1. Before installing the new release of the NorthStar software, ensure that all individual cluster members are working. On each node, execute the **supervisorctl status** script:

   ```
   [root@node-1]# supervisorctl status
   ```

   For an active node, all processes should be listed as RUNNING as shown in this example:

   > **NOTE:** This is just an example. The actual list of processes varies according to the version of NorthStar on the node, your deployment setup, and the optional features installed.

   ```
   [root@node-1 ~]# supervisorctl status
   ```

```
bmp:bmpMonitor                   RUNNING   pid 2957, uptime 0:58:02
collector:worker1                RUNNING   pid 19921, uptime 0:01:42
collector:worker2                RUNNING   pid 19923, uptime 0:01:42
collector:worker3                RUNNING   pid 19922, uptime 0:01:42
collector:worker4                RUNNING   pid 19924, uptime 0:01:42
collector_main:es_publisher      RUNNING   pid 19771, uptime 0:01:53
collector_main:task_scheduler    RUNNING   pid 19772, uptime 0:01:53
config:ns_config_monitor         RUNNING   pid 19129, uptime 0:03:19
docker:dockerd                   RUNNING   pid 4368, uptime 0:57:34
epe:epeplanner                   RUNNING   pid 9047, uptime 0:50:34
infra:cassandra                  RUNNING   pid 2971, uptime 0:58:02
infra:ha_agent                   RUNNING   pid 9009, uptime 0:50:45
infra:healthmonitor              RUNNING   pid 9172, uptime 0:49:40
infra:license_monitor            RUNNING   pid 2968, uptime 0:58:02
infra:prunedb                    RUNNING   pid 19770, uptime 0:01:53
infra:rabbitmq                   RUNNING   pid 7712, uptime 0:52:03
infra:redis_server               RUNNING   pid 2970, uptime 0:58:02
infra:zookeeper                  RUNNING   pid 2965, uptime 0:58:02
junos:junosvm                    RUNNING   pid 2956, uptime 0:58:02
listener1:listener1_00           RUNNING   pid 9212, uptime 0:49:29
netconf:netconfd                 RUNNING   pid 19768, uptime 0:01:53
northstar:configServer           RUNNING   pid 19767, uptime 0:01:53
northstar:mladapter              RUNNING   pid 19765, uptime 0:01:53
northstar:npat                   RUNNING   pid 19766, uptime 0:01:53
northstar:pceserver              RUNNING   pid 19441, uptime 0:02:59
northstar:prpdclient             RUNNING   pid 19763, uptime 0:01:53
northstar:scheduler              RUNNING   pid 19764, uptime 0:01:53
northstar:toposerver             RUNNING   pid 19762, uptime 0:01:53
northstar_pcs:PCServer           RUNNING   pid 19487, uptime 0:02:49
northstar_pcs:PCViewer           RUNNING   pid 19486, uptime 0:02:49
web:app                          RUNNING   pid 19273, uptime 0:03:18
web:proxy                        RUNNING   pid 19275, uptime 0:03:18
```

For a standby node, processes beginning with “northstar”, “northstar_pcs”, and “netconf” should be listed as STOPPED. Also, if you have analytics installed, some of the processes beginning with “collector” are STOPPED. Other processes, including those needed to preserve connectivity, remain RUNNING. An example is shown here.

NOTE: This is just an example; the actual list of processes varies according to the version of NorthStar on the node, your deployment setup, and the optional features installed.

```
[root@node-1 ~]# supervisorctl status
```

```
bmp:bmpMonitor                   RUNNING   pid 8755, uptime 3:36:02
collector:worker1                RUNNING   pid 31852, uptime 0:06:59
collector:worker2                RUNNING   pid 31854, uptime 0:06:59
collector:worker3                RUNNING   pid 31853, uptime 0:06:59
collector:worker4                RUNNING   pid 31855, uptime 0:06:59
collector_main:es_publisher      STOPPED   Apr 07 04:08 PM
collector_main:task_scheduler    STOPPED   Apr 07 04:08 PM
config:ns_config_monitor         STOPPED   Apr 07 04:08 PM
docker:dockerd                   RUNNING   pid 10187, uptime 3:35:35
epe:epeplanner                   RUNNING   pid 15071, uptime 3:27:17
infra:cassandra                  RUNNING   pid 8769, uptime 3:36:02
infra:ha_agent                   RUNNING   pid 31401, uptime 0:08:31
infra:healthmonitor              RUNNING   pid 31784, uptime 0:07:14
infra:license_monitor            RUNNING   pid 8766, uptime 3:36:02
infra:prunedb                    STOPPED   Apr 07 04:10 PM
infra:rabbitmq                   RUNNING   pid 13819, uptime 3:28:47
infra:redis_server               RUNNING   pid 8768, uptime 3:36:02
infra:zookeeper                  RUNNING   pid 8763, uptime 3:36:02
junos:junosvm                    RUNNING   pid 8754, uptime 3:36:02
listener1:listener1_00           RUNNING   pid 31838, uptime 0:07:03
netconf:netconfd                 STOPPED   Apr 07 04:08 PM
northstar:configServer           STOPPED   Apr 07 04:08 PM
northstar:mladapter              STOPPED   Apr 07 04:08 PM
northstar:npat                   STOPPED   Apr 07 04:08 PM
northstar:pceserver              STOPPED   Apr 07 04:08 PM
northstar:prpdclient             STOPPED   Apr 07 04:08 PM
northstar:scheduler              STOPPED   Apr 07 04:08 PM
northstar:toposerver             STOPPED   Apr 07 04:08 PM
northstar_pcs:PCServer           STOPPED   Apr 07 04:08 PM
northstar_pcs:PCViewer           STOPPED   Apr 07 04:08 PM
web:app                          STOPPED   Apr 07 04:09 PM
web:proxy                        STOPPED   Apr 07 04:09 PM
```

2. Ensure that the SSH keys for HA are set up. To test this, try to SSH from each node to every other node in the cluster using user “root”. If the SSH keys for HA are set up, you will not be prompted for a password. If you are prompted for a password, see “Configuring a NorthStar Cluster for High Availability” on page 154 for the procedure to set up the SSH keys.

3. On one of the standby nodes, install the new release of the NorthStar software according to the instructions at the beginning of this topic. Check the processes on this node before proceeding to the other standby node(s) by executing the **supervisorctl status** script.

```
[root@node-1]# supervisorctl status
```

Since the node comes up as a standby node, some processes will be STOPPED, but the “infra” group of processes, the “listener1” process, the “collector:worker” group of processes (if you have them), and the “junos:junosvm” process (if you have it) should be RUNNING. Wait until those processes are running before proceeding to the next node.

4. Repeat this process on each of the remaining standby nodes, one by one, until all *standby* nodes have been upgraded.

5. On the active node, restart the ha-agent process to trigger a switchover to a standby node.

```
[root@node-2]# supervisorctl restart infra:ha_agent
```

One of the standby nodes becomes active and the previously active node switches to standby mode.

6. On the previously active node, install the new release of the NorthStar software according to the instructions at the beginning of this section. Check the processes in this node using **supervisorctl status**; their status (RUNNING or STOPPED) should be consistent with the node’s new standby role.

NOTE: The newly upgraded software automatically inherits the net_setup settings, HA configurations, and all credentials from the previous installation. Therefore, it is not necessary to re-run net_setup unless you want to change settings, HA configurations, or password credentials.

RELATED DOCUMENTATION

NorthStar Controller System Requirements | 21

Configuring a NorthStar Cluster for High Availability | 154

Uninstalling the NorthStar Controller Application | 72

Uninstalling the NorthStar Controller Application

IN THIS SECTION

- Uninstall the NorthStar Software | 72
- Reinstate the License File | 73

You can uninstall the NorthStar Controller application using the supplied uninstall script. One use case for uninstalling is to revert back to a previous version of NorthStar after testing a new version.

The following sections provide the steps to follow.

Uninstall the NorthStar Software

Use the following procedure to uninstall NorthStar:

1. Preserve your license file by copying it to the root directory:

   ```
   cp -prv/u/wandl/db/sys/npatpw /root/
   ```

   NOTE: You can also preserve any other important user or configuration data you have on the server using the same method.

2. Navigate to the NorthStar bundle directory:

   ```
   cd /opt/northstar/northstar_bundle_x_x_x
   ```

3. Run the uninstall script:

   ```
   ./uninstall_all.sh
   ```

4. When prompted, confirm that you want to uninstall NorthStar.

Reinstate the License File

After you have reinstalled the NorthStar application, use the following procedure to reinstate the license file that you copied to the root directory:

1. Copy the license file from the root directory back to its original directory:

   ```
   cp -prv/root/npatpw /u/wandl/db/sys/
   ```

   > **NOTE:** You can also restore any other data preserved in the root directory by copying it back to its original directory.

2. Change the user and group ownership to pcs. This is likely unnecessary if you used -prv (preserve) in the copy command.

   ```
   chown pcs:pcs /u/wandl/db/sys/npatpw
   ```

3

CHAPTER

Running the NorthStar Controller on VMware ESXi

VMDK Deployment | 75

VMDK Deployment

NOTE: The VMDK files needed for this type of NorthStar installation are not available on the NorthStar software download page. Please request the files from your account team or NorthStar Product Line Manager.

The following system requirements apply when preparing to run the NorthStar Controller on VMware ESXi by outputting a VMDK file of the NorthStar disk from the VMware build software.

NOTE: ESXi 5.5, 6.0, and 6.5 are supported.

With this type of deployment, you upload a VMDK file with a pre-installed setup of CentOS minimal, along with the NorthStar Controller application, and a second VMDK file that contains the official JunosVM image. When you create a new VM for the disk, you point to the supplied VMDK image.

The following steps describe the procedure:

> **NOTE:** The screen captures presented are examples only and might vary slightly from what you actually see due to a difference in ESXi version.

1. Create a new virtual machine as shown in Figure 6 on page 76.

Figure 6: Create New Virtual Machine



2. Select Custom as shown in Figure 7 on page 77, and click **Next**.

Figure 7: Select Custom



3. Name the new VM as shown in Figure 8 on page 78, and click **Next**.

Figure 8: Name the New Virtual Machine



4. Select a storage device as shown in Figure 9 on page 79, and click **Next**.

Figure 9: Select Storage Device



5. Select Virtual Machine Version: 8 as shown in Figure 10 on page 80, and click **Next** .

Figure 10: Select Version 8



6. Select Linux, Red Hat Enterprise Linux 6 (64-bit) as shown in Figure 11 on page 81, and click **Next**.

Figure 11: Select the Operating System



7. Select the number of virtual CPUs you require as shown in Figure 12 on page 82, and click **Next**.

Figure 12: Select Number of Virtual CPUs



8. Select the VM memory size as shown in Figure 13 on page 83, and click **Next**.

Figure 13: Select Memory Size



9. Select the number of network interfaces required for your environment as shown in Figure 14 on page 84, and click **Next**.

Figure 14: Select Number of Network Interfaces



10. Select VMware Paravirtual SCSI Controller as shown in Figure 15 on page 85, and click **Next**.

Figure 15: Select SCSI Controller



11. Select “Use an existing virtual disk” as shown in Figure 16 on page 86, and click **Next**.

Figure 16: Select to Use an Existing Virtual Disk



12. Select the VMDK file you downloaded from Juniper Networks as shown in Figure 17 on page 87, and click **Next**.

Figure 17: Specify the Existing Disk



13. Keep the Virtual Device Node as the default as shown in Figure 18 on page 88, and click **Next**.

Figure 18: Do Not Change the Virtual Device Node



14. Review the summary of your configuration as shown in Figure 19 on page 89, and click **Finish** to complete the process.

Figure 19: Review the Summary



15. Power on the new VM and access the console window. Log in with root/northstar.

16. When prompted, change the root password. This will be required only at first login.

17. When prompted, enter new Database and RabbitMQ passwords (first login only).

18. When prompted, enter a new UI Admin password (first login only).

19. Obtain a NorthStar Controller license by following the instructions on the screen or by working with your account team.

4

CHAPTER

NorthStar Controller Installation in an OpenStack Environment

Overview of NorthStar Controller Installation in an OpenStack Environment | **91**

OpenStack Resources for NorthStar Controller Installation | **96**

NorthStar Controller in an OpenStack Environment Pre-Installation Steps | **97**

Installing the NorthStar Controller in Standalone Mode Using a HEAT Template | **98**

Installing a NorthStar Cluster Using a HEAT Template | **104**

Overview of NorthStar Controller Installation in an OpenStack Environment

The NorthStar Controller can be installed in an OpenStack environment in either standalone or cluster mode. Figure 20 on page 91 illustrates standalone mode. Figure 21 on page 92 illustrates cluster mode. Note that in both cases, each node has one NorthStar Controller application VM and one JunosVM.

Figure 20: OpenStack Environment, Standalone Mode



Figure 21: OpenStack Environment, Cluster Mode



Testing Environment

The Juniper Networks NorthStar Controller testing environment included the following OpenStack configurations:

- OpenStack Kilo with Open vSwitch (OVS) as Neutron ML2 plugins on Red Hat 7 Host
- OpenStack Juno with Contrail as Neutron ML2 plugins on Ubuntu 14.04 Host
- OpenStack Liberty with Contrail 3.0.2

Networking Scenarios

There are two common networking scenarios for using VMs on OpenStack:

- The VM is connected to a private network, and it uses a floating IP address to communicate with the external network.

A limitation to this scenario is that direct OSPF or IS-IS adjacency does not work behind NAT. You should, therefore, use BGP-LS between the JunosVM and the network devices for topology acquisition.

- The VM is connected or bridged directly to the provider network (flat networking).

  In some deployments, a VM with flat networking is not able to access OpenStack metadata services. In that case, the official CentOS cloud image used for the NorthStar Controller application VM cannot install the SSH key or post-launch script, and you might not be able to access the VM.

  One workaround is to access metadata services from outside the DHCP namespace using the following procedure:

  > **CAUTION:** This procedure interrupts traffic on the OpenStack system. We recommend that you consult with your OpenStack administrator before proceeding.

  1. Edit the /etc/neutron/dhcp_agent.ini file to change “enable_isolated_metadata = False” to “enable_isolated_metadata = True”.
  2. Stop all neutron agents on the network node.
  3. Stop any dnsmasq processes on network node or on the node that serves the flat network subnet.
  4. Restart all neutron agents on the network node.

HEAT Templates

The following HEAT templates are provided with the NorthStar Controller software:

- northstar310.heat (standalone installation) and northstar310.3instances.heat (cluster installation)

  These templates can be appropriate when the NorthStar Controller application VM and the JunosVM are to be connected to a virtual network that is directly accessible from outside OpenStack, without requiring NAT. Typical scenarios include a VM that uses flat networking, or an existing OpenStack system that uses Contrail as the Neutron plugin, advertising the VM subnet to the MX Series Gateway device.

- northstar310.floating.heat (standalone installation) and northstar310.3instances.floating.heat (cluster installation)

  These templates can be appropriate if the NorthStar Controller application VM and the JunosVM are to be connected to a private network behind NAT, and require a floating IP address for one-to-one NAT.

We recommend that you begin with a HEAT template rather than manually creating and configuring all of your resources from scratch. You might still need to modify the template to suit your individual environment.

HEAT Template Input Values

The provided HEAT templates require the input values described in Table 11 on page 94.

Table 11: HEAT Template Input Values

Parameter	Default	Notes
customer_name	(empty)	User-selected name to identify the NorthStar stack
app_image	CentOS-6-x86_64-GenericCloud.qcow2	Modify this variable with the Centos 6 cloud image name that is available in Glance
junosvm_image	northstar-junosvm	Modify this variable with the JunosVM image name that is available in Glance
app_flavor	m1.large	Instance flavor for the NorthStar Controller VM with a minimum 40 GB disk and 8 GB RAM
junosvm_flavor	m1.small	Instance flavor for the JunosVM with a minimum of a 20 GB disk and 2GB of RAM
public_network	(empty)	UUID of the public-facing network, mainly for managing the server
asn	11	AS number of the backbone routers for BGP-LS peering
rootpassword	northstar	Root password
availability_zone	nova	Availability zone for spawning the VMs
key_name	(empty)	Your ssh-key must be uploaded in advance

Known Limitations

The following limitations apply to installing and using the NorthStar Controller in a virtualized environment.

Virtual IP Limitations from ARP Proxy Being Enabled

In some OpenStack implementations, ARP proxy is enabled, so virtual switch forwarding tables are not able to learn packet destinations (no ARP snooping). Instead, ARP learning is based on the hypervisor configuration.

This can prevent the virtual switch from learning that the virtual IP address has been moved to a new active node as a result of a high availability (HA) switchover.

There is currently no workaround for this issue other than disabling ARP proxy on the network where the NorthStar VM is connected. This is not always possible or allowed.

Hostname Changes if DHCP is Used Rather than a Static IP Address

If you are using DHCP to assign IP addresses for the NorthStar application VM (or NorthStar on a physical server), you should never change the hostname manually.

Also if you are using DHCP, you should not use net_setup.py for host configuration.

Disk Resizing Limitations

OpenStack with cloud-init support is supposed to resize the VM disk image according to the version you select. Unfortunately, the CentOS 6 official cloud image does not auto-resize due to an issue within the cloud-init agent inside the VM.

The only known workaround at this time is to manually resize the partition to match the allocated disk size after the VM is booted for the first time. A helper script for resizing the disk (**/opt/northstar/utils/resize_vm.sh**) is included as part of the NorthStar Controller RPM bundle.

RELATED DOCUMENTATION

- OpenStack Resources for NorthStar Controller Installation | **96**
- NorthStar Controller in an OpenStack Environment Pre-Installation Steps | **97**
- Installing the NorthStar Controller in Standalone Mode Using a HEAT Template | **98**
- Installing a NorthStar Cluster Using a HEAT Template | **104**

OpenStack Resources for NorthStar Controller Installation

Table 12 on page 96 and Table 13 on page 96 describe the required and optional OpenStack resources for running the NorthStar Controller in an OpenStack environment.

Table 12: Required OpenStack Resources

Resource	Description
OS::Nova::Server	Two of these resources are required: one for the NorthStar Controller application VM and one for the JunosVM.
OS::Neutron::Port	At least two of these resources are required for the Ethernet connections of each OS:Nova::Server resource.
OS::Neutron::Net	Each NorthStar installation requires one of this resource for internal communication between the NorthStar Controller application VM and the JunosVM. Connection to an existing OS::Neutron::Net resource for public network connectivity is also required.
OS::Neutron::Subnet	A fixed 172.16.16.0/24 subnet is required for internal communication between the NorthStar Controller application VM and the JunosVM.

Table 13: Optional OpenStack Resources

Resource	Description
OS::Neutron::SecurityGroup	Use this resource (either new or existing) to access the NorthStar Controller application VM and JunosVM from outside OpenStack.
OS::Neutron::FloatingIP	Use this resource if the NorthStar Controller application VM and JunosVM are connected to a virtual private network behind NAT. This resource is not usually necessary in a flat networking scenario or a private network using Contrail.
OS::Nova::ServerGroup	Use this resource with an anti-affinity rule to ensure that no more than one NorthStar Controller application VM, or no more than one JunosVM are spawned in the same compute node. This is for additional redundancy purposes.
OS::Neutron::Port for VIP	Use an additional OS::Neutron::Port for cluster setup, to provide a virtual IP address for the client facing connection.

RELATED DOCUMENTATION

Overview of NorthStar Controller Installation in an OpenStack Environment | 91

NorthStar Controller in an OpenStack Environment Pre-Installation Steps

Before you install the NorthStar Controller in an OpenStack environment, prepare your system by performing the following pre-installation steps.

1. (Optional) Upload an SSH keypair.

   ```
   # nova keypair-add --pub-key ssh-public-key-file keypair-name
   ```

   Alternatively, you can use any existing keypair that is available in your OpenStack system. You can also use Horizon UI to upload the image. Consult your OpenStack user guide for more information about creating, importing, and using keypairs.

2. Upload an official CentOS 6 Cloud image.

   ```
   # glance image-create --name glance-centos-image-name  --disk-format qcow2
   --container-format bare --file image-location-and-filename-to-upload
   ```

   For example:

   ```
   # glance image-create --name northstar_junosvm_17.2R1.openstack.qcow2 --disk-format
    qcow2 --container-format bare --file
   images/northstar_junosvm_17.2R1.openstack.qcow2
   ```

3. Change the JunosVM disk bus type to IDE and the Ethernet driver to e1000.

   ```
   # glance image-update --property hw_disk_bus=ide --property hw_cdrom_bus=ide
   --property hw_vif_model=e1000 junosvm-image-id
   ```

NOTE: The variable *junosvm-image-id* is the UUID of the JunosVM image. You can find this ID in the output of the following command:

```
# glance image-list
```

RELATED DOCUMENTATION

Overview of NorthStar Controller Installation in an OpenStack Environment | 91

OpenStack Resources for NorthStar Controller Installation | 96

Installing the NorthStar Controller in Standalone Mode Using a HEAT Template

This topic describes installing a standalone NorthStar Controller in an OpenStack environment using a HEAT template. These instructions assume you are using one of the provided HEAT templates.

Launch the Stack

Perform the following steps to launch the stack.

1. Create a stack from the HEAT template file using the **heat stack-create** command.

```
# heat stack-create stack-name -f heat-template-name --parameters
customer_name=instance-name;app_image=centos6-image-name;junosvm_image=
junosvm-image-name;public_network=public-network-uuid;key_name=
keypair-name;app_flavor=app-vm-flavor;junosvm_flavor=junosvm-flavor
```

Obtain the Stack Attributes

1. Ensure that the stack creation is complete by examining the output of the **heat stack-show** command.

   ```
   # heat stack-show stack-name | grep stack_status
   ```

2. Obtain the UUID of the NorthStar Controller VM and the JunosVM instances by executing the **resource-list** command.

   ```
   # heat resource-list stack-name | grep ::Server
   ```

3. Using the UUIDs obtained from the **resource-list** command output, obtain the associated IP addresses by executing the **interface-list** command for each UUID.

   ```
   # nova interface-list uuid
   ```

4. Once the NorthStar Controller VM finishes its booting process, you should be able to ping its public IP address.

   NOTE: You can use the **nova console-log** command to monitor the booting status.

   At this point, the NorthStar Controller VM is remotely accessible, but the JunosVM is not because it does not support DHCP. Once the NorthStar Controller RPM bundle installation is completed, the JunosVM can be remotely accessed.

5. Connect to the NorthStar Controller VM using SSH.

   If you are using a different SSH key from the one that is defined in the HEAT template, the default credentials are root/northstar and centos/northstar.

Resize the Image

The CentOS 6 official cloud image does not resize correctly for the selected OpenStack flavor. This results in the NorthStar Controller VM filesystem size being set at 8G instead of the size that is actually specified by the flavor. Using the following procedure, you can adjust your filesystem to be in sync with the allocated disk size. Alternatively, you can hold off on the resizing procedure until after you complete the NorthStar Controller RPM bundle installation. There is a resize-vm script inside /opt/northstar/utils/.

CAUTION: The **fdisk** command can have undesirable effects if used inappropriately. We recommend that you consult with your system administrator before proceeding with this workaround, especially if you are unfamiliar with the **fdisk** command.

1. Determine whether the size of the VM is correct. If it is correct, you do not need to proceed with resizing.

```
# ssh centos@App_Public_IPv4
Warning: Permanently added '172.25.158.161' (RSA) to the list of known hosts.

[centos@app_instance ~]$ df -h
Filesystem      Size  Used Avail Use% Mounted on
/dev/vda1       7.8G  646M  6.8G   9% /
tmpfs           1.9G     0  1.9G   0% /dev/shm
```

2. Use the **fdisk** command to recreate the partition.

```
# ssh centos@App_Public_IPv4
Warning: Permanently added '172.25.158.161' (RSA) to the list of known hosts.

[user@demo-northstar-app centos]# fdisk /dev/vda

WARNING: DOS-compatible mode is deprecated. It's strongly recommended to
        switch off the mode (command 'c') and change display units to
        sectors (command 'u').

Command (m for help): c
DOS Compatibility flag is not set

Command (m for help): u
Changing display/entry units to sectors
```

```
Command (m for help): p

Disk /dev/vda: 85.9 GB, 85899345920 bytes
255 heads, 63 sectors/track, 10443 cylinders, total 167772160 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x00050c05

Device Boot      Start         End      Blocks   Id  System
/dev/vda1   *        2048    16777215     8387584   83  Linux

Command (m for help): d
Selected partition 1

Command (m for help): n
Command action
e   extended
p   primary partition (1-4)
p
Partition number (1-4): 1
First sector (2048-167772159, default 2048):
Using default value 2048
Last sector, +sectors or +size{K,M,G} (2048-167772159, default 167772159):
Using default value 167772159

Command (m for help): w
The partition table has been altered!

Calling ioctl() to re-read partition table.

WARNING: Re-reading the partition table failed with error 16: Device or resource
 busy.
The kernel still uses the old table. The new table will be used at
the next reboot or after you run partprobe(8) or kpartx(8)
Syncing disks.
[user@demo-northstar-app centos]#
```

3. Reboot the VM to apply the partition changes.

```
[user@app_instance centos]# reboot

Broadcast message from centos@app_instance
```

```
    (/dev/pts/0) at 14:54 ...

The system is going down for reboot NOW!
```

4. Wait until the NorthStar Controller VM has returned to an up state.

5. Reconnect to the VM using SSH.

6. Check the partition size again to verify that the partition was resized.

7. If the partition size is still incorrect, use the **resize2fs** command to adjust the filesystem.

```
# resize2fs /dev/vda1
```

Install the NorthStar Controller RPM Bundle

Install the NorthStar Controller RPM bundle for an OpenStack environment as described in *Installing the NorthStar Controller*. The procedure uses the **rpm** and **install-vm.sh** commands.

Configure the JunosVM

For security reasons, the JunosVM does not come with a default configuration. Use the following procedure to manually configure the JunosVM using the OpenStack novnc client.

1. Obtain the novnc client URL.

```
# nova get-vnc-console JunosVM-ID novnc
```

2. Configure the JunosVM as you would in a fresh install of the Junos OS.

3. Copy the root user of the NorthStar Controller VM SSH public key to the JunosVM. This allows configuration from the NorthStar Controller VM to the JunosVM using an ssh-key based connection.

4. On the NorthStar Controller VM, run the net_setup.py script, and select option B to complete the configuration of the JunosVM. Once complete, you should be able to remotely ping the JunosVM IP address.

Configure SSH Key Exchange

Use the following procedure to configure SSH key exchange between the NorthStar Controller VM and the JunosVM.

1. Log in to the NorthStar Controller server and display the contents of the id_rsa.pub file by executing the **concatenate** command.

   ```
   $cat /opt/pcs/.ssh/id_rsa.pub
   ```

   You will need the ssh-rsa string from the output.

2. Log in to the JunosVM and replace the ssh-rsa string with the one from the id_rsa.pub file by executing the following commands.

   ```
   ssh northstar@JunosVM-ip
   configure
   set system login user northstar authenication ssh-rsa replacement-string
   commit
   exit
   ```

3. On the NorthStar Controller server, update the known hosts file by executing the following commands.

   ```
   $su - pcs
   $ssh -o UserKnownHostsFile=/opt/pcs/.ssh/known_hosts -i /opt/pcs/.ssh/id_rsa
   northstar@JunosVM-ip
   exit
   exit
   ```

RELATED DOCUMENTATION

Installing a NorthStar Cluster Using a HEAT Template

This topic describes installing a NorthStar cluster in an OpenStack environment using a HEAT template. These instructions assume that you are using one of the provided HEAT templates.

System Requirements

In addition to the system requirements for installing the NorthStar Controller in a two-VM environment, a cluster installation also requires that:

- An individual compute node is hosting only one NorthStar Controller VM and one JunosVM. You can ensure this by launching the NorthStar Controller VM into a specific availability zone and compute node, or by using a host affinity such as OS::Nova::ServerGroup with an anti-affinity rule.
- The cluster has a single virtual IP address for the client facing connection. If promiscuous mode is disabled in OpenStack (blocking the virtual IP address), you can use the Neutron::Port allowed-address-pair attribute to permit the additional address.

Launch the Stack

Create a stack from the HEAT template file using the **heat stack-create** command.

```
# heat stack-create stack-name -f heat-template-name --parameters
customer_name=instance-name;app_image=centos6-image-name;junosvm_image=
junosvm-image-name;public_network=public-network-uuid;key_name=
keypair-name;app_flavor=app-vm-flavor;junosvm_flavor=junosvm-flavor
```

Obtain the Stack Attributes

1. Ensure that the stack creation is complete by examining the output of the **heat stack-show** command.

```
# heat stack-show stack-name | grep stack_status
```

2. Obtain the UUID of the NorthStar Controller VM and the JunosVM instances for each node in the cluster by executing the **resource-list** command.

```
# heat resource-list stack-name | grep ::Server
```

3. Using the UUIDs obtained from the **resource-list** command output, obtain the associated IP addresses by executing the **interface-list** command for each UUID.

```
# nova interface-list uuid
```

4. Verify that each compute node in the cluster has only one NorthStar Controller VM and only one JunosVM by executing the following command for each UUID:

```
# nova show uuid | grep hypervisor
```

Configure the Virtual IP Address

1. Find the UUID of the virtual IP port that is defined in the HEAT template by examining the output of the **heat resource-list** command.

```
# heat resource-list stack-name | grep vip_port
```

2. Find the assigned virtual IP address for that UUID by examining the output of the **neutron port-show** command.

```
# neutron port-show vip-port-uuid
```

3. Find the UUID of each public-facing NorthStar Controller port by examining the output of the **neutron port-list** command.

```
# neutron port-list | grep stack-name-app_port_eth0
```

For example:

```
# neutron port-list | grep northstarHAexample-app_port_eth0
```

4. Update each public-facing NorthStar Controller port to accept the virtual IP address by executing the **neutron port-update** command for each port.

   ```
   # neutron port-update vip-port-uuid --allowed_address_pairs list=true type=dict
   ip_address=vip-ip
   ```

   For example:

   ```
   # neutron port-update a15578e2-b9fb-405c-b4c4-1792f5207003  --allowed_address_pairs
    list=true type=dict ip_address=172.25.158.139
   ```

5. Wait until each NorthStar Controller VM finishes its booting process, at which time, you should be able to ping its public IP address. You can also use the **nova console-log** command to monitor the booting status of the NorthStar Controller VM.

Resize the Image

The CentOS 6 official cloud image does not resize correctly for the selected OpenStack flavor. This results in the NorthStar Controller VM filesystem size being set at 8G instead of the size that is actually specified by the flavor. Using the following procedure, you can adjust your filesystem to be in sync with the allocated disk size. Alternatively, you can hold off on the resizing procedure until after you complete the NorthStar RPM bundle installation. There is a resize-vm script inside /opt/northstar/utils/.

CAUTION: The **fdisk** command can have undesirable effects if used inappropriately. We recommend that you consult with your system administrator before proceeding with this workaround, especially if you are unfamiliar with the **fdisk** command.

Use the following procedure for each NorthStar Controller VM. Replace *XX* in the commands with the number of the VM (01, 02, 03, and so on).

1. Determine whether the size of the VM is correct. If it is correct, you do not need to proceed with the resizing.

```
# ssh centos@App_XX_Public_IPv4
Warning: Permanently added '172.25.158.161' (RSA) to the list of known hosts.

[centos@app_instance_XX ~]$ df -h
Filesystem      Size  Used Avail Use% Mounted on
/dev/vda1       7.8G  646M  6.8G   9% /
tmpfs           1.9G     0  1.9G   0% /dev/shm
```

2. Use the **fdisk** command to recreate the partition.

```
# ssh centos@App_XX_Public_IPv4
Warning: Permanently added '172.25.158.161' (RSA) to the list of known hosts.

[user@demo-northstar-app centos]# fdisk /dev/vda

WARNING: DOS-compatible mode is deprecated. It's strongly recommended to
        switch off the mode (command 'c') and change display units to
        sectors (command 'u').

Command (m for help): c
DOS Compatibility flag is not set

Command (m for help): u
Changing display/entry units to sectors

Command (m for help): p

Disk /dev/vda: 85.9 GB, 85899345920 bytes
255 heads, 63 sectors/track, 10443 cylinders, total 167772160 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x00050c05

Device Boot      Start         End      Blocks   Id  System
/dev/vda1   *        2048    16777215     8387584   83  Linux

Command (m for help): d
Selected partition 1

Command (m for help): n
Command action
e   extended
```

```
p   primary partition (1-4)
p
Partition number (1-4): 1
First sector (2048-167772159, default 2048):
Using default value 2048
Last sector, +sectors or +size{K,M,G} (2048-167772159, default 167772159):
Using default value 167772159

Command (m for help): w
The partition table has been altered!

Calling ioctl() to re-read partition table.

WARNING: Re-reading the partition table failed with error 16: Device or resource
 busy.
The kernel still uses the old table. The new table will be used at
the next reboot or after you run partprobe(8) or kpartx(8)
Syncing disks.
[user@demo-northstar-app centos]#
```

3. Reboot the VM to apply the partition changes.

```
[user@app_instance_XX centos]# reboot

Broadcast message from centos@app_instance_XX
    (/dev/pts/0) at 14:54 ...

The system is going down for reboot NOW!
```

4. Wait until the NorthStar Controller VM has returned to an up state.

5. Reconnect to the VM using SSH.

6. Check the partition size again to verify that the partition was resized.

7. If the partition size is still incorrect, use the **resize2fs** command to adjust the filesystem.

```
# resize2fs /dev/vda1
```

Install the NorthStar Controller RPM Bundle

Install the NorthStar Controller RPM bundle for an OpenStack environment. The procedure uses the **rpm** and **install-vm.sh** commands.

Configure the JunosVM

For security reasons, the JunosVM does not come with a default configuration. Use the following procedure to manually configure the JunosVM using the OpenStack novnc client.

1. Obtain the novnc client URL.

   ```
   # nova get-vnc-console JunosVM-ID novnc
   ```

2. Configure the JunosVM as you would in a fresh install of the Junos OS.

3. Copy the root user of the NorthStar Controller VM SSH public key to the JunosVM. This allows configuration from the NorthStar Controller VM to the JunosVM using an ssh-key based connection.

4. On the NorthStar Controller VM, run the net_setup.py script, and select option **B** to complete the configuration of the JunosVM. Once complete, you should be able to remotely ping the JunosVM IP address.

Configure SSH Key Exchange

Use the following procedure to configure SSH key exchange between the NorthStar Controller VM and the JunosVM. For High Availability (HA) in a cluster, this must be done for every pair of VMs.

1. Log in to the NorthStar Controller server and display the contents of the id_rsa.pub file by executing the **concatenate** command.

   ```
   $cat /opt/pcs/.ssh/id_rsa.pub
   ```

   You will need the ssh-rsa string from the output.

2. Log in to the JunosVM and replace the ssh-rsa string with the one from the id_rsa.pub file by executing the following commands.

```
ssh northstar@JunosVM-ip
configure
set system login user northstar authenication ssh-rsa replacement-string
commit
exit
```

3. On the NorthStar Controller server, update the known hosts file by executing the following commands.

```
$su - pcs
$ssh -o UserKnownHostsFile=/opt/pcs/.ssh/known_hosts -i /opt/pcs/.ssh/id_rsa
northstar@JunosVM-ip
exit
exit
```

Configure the HA Cluster

HA on the NorthStar Controller is an active/standby solution. That means that there is only one active node at a time, with all other nodes in the cluster serving as standby nodes. All of the nodes in a cluster must be on the same local subnet for HA to function. On the active node, all processes are running. On the standby nodes, those processes required to maintain connectivity are running, but NorthStar processes are in a stopped state.

If the active node experiences a hardware- or software-related connectivity failure, the NorthStar HA_agent process elects a new active node from amongst the standby nodes. Complete failover is achieved within five minutes. One of the factors in the selection of the new active node is the user-configured priorities of the candidate nodes.

All processes are started on the new active node, and the node acquires the virtual IP address that is required for the client-facing interface. This address is always associated with the active node, even if failover causes the active node to change.

See the *NorthStar Controller User Guide* for further information on configuring and using the HA feature.

RELATED DOCUMENTATION

Installing the NorthStar Controller in Standalone Mode Using a HEAT Template | 98

5
CHAPTER

Installing and Configuring Optional Features

Installing Data Collectors for Analytics | **112**

Configuring Routers to Send JTI Telemetry Data and RPM Statistics to the Data Collectors | **145**

Collector Worker Installation Customization | **150**

Secondary Collector Installation for Distributed Data Collection | **151**

Configuring a NorthStar Cluster for High Availability | **154**

Installing Data Collectors for Analytics

IN THIS SECTION

- Overview | 112
- Analytics Geo-HA | 114
- Single-Server Deployment–No NorthStar HA | 114
- External Analytics Node(s)–No NorthStar HA | 115
- External Analytics Node(s)–With NorthStar HA | 127
- Verifying Data Collection When You Have External Analytics Nodes | 130
- Replacing a Failed Node in an External Analytics Cluster | 133
- Collectors Installed on the NorthStar HA Cluster Nodes | 138
- Troubleshooting Logs | 144

Overview

The Analytics functionality streams data from the network devices, via data collectors, to the NorthStar Controller where it is processed, stored, and made available for viewing in the web UI.

NOTE: See the *NorthStar Controller User Guide* for information about collecting and viewing telemetry data.

NOTE: Junos OS Release 15.1F6 or later is required to use Analytics. For hardware requirements for analytics nodes, see "NorthStar Controller System Requirements" on page 21. For supported deployment scenarios, see "Platform and Software Compatibility" on page 14.

If you are not using NorthStar application high availability (HA), you can install a data collector either in the same node where the NorthStar Controller application is installed (single-server deployment) or in one or more external nodes that are dedicated to log collection and storage. In both cases, the supplied install scripts take care of installing the required packages and dependencies.

In a NorthStar application HA environment, you have three options:

- Configure an external analytics node.
- Configure an external analytics cluster. An analytics cluster provides backup nodes in the event of an analytics node failure. This cluster can be local (within the same data center) or geo-diverse (analytics geo-HA).
- Install data collectors in the same nodes that make up the NorthStar cluster. In this scenario, the NorthStar application cluster nodes are also analytics cluster nodes.

The configuration options from the analytics processes are read from the /opt/northstar/data/northstar.cfg file. In a single-server deployment, no special changes are required because the parameters needed to start up the collector are part of the default configuration. For your reference, Table 14 on page 113 lists some of the settings that the analytics processes read from the file.

Table 14: Some of the Settings Read by Collector Processes

Setting	Description
mq_host	Points to the IP address or virtual IP (VIP) (for multiple NorthStar node deployments) of hosts running the messaging bus service (the NorthStar application node). Defaults to **localhost** if not present.
mq_username	Username used to connect to the messaging bus. Defaults to **northstar**.
mq_password_enc	Password used to connect to the messaging bus. There is no default; the service fails to start if this is not configured. On single-server deployments, the password is set during the normal application install process.
mq_port	TCP port number used by the messaging bus. Defaults to **5672**.
es_port	TCP port used by elasticsearch. Defaults to **9200**.
es_cluster_name	Used by elasticsearch in HA scenarios to form a cluster. Nodes in the same cluster must be configured with the same cluster name. Defaults to **NorthStar**.
jvision_ifd_port, jvision_ifl_port and jvision_lsp_port	UDP port numbers the collector listens to for telemetry packets from the devices. Defaults to **3000**. **2000**, **2001** and **2002**, respectively, can also be used.
rpmstats_port	Used to read syslog messages generated from the device with the results of the RPM stats. Defaults to **1514**.

NOTE: If you are upgrading to NorthStar 4.3.0 from an earlier release and you are using NorthStar analytics, you must upgrade NorthStar manually using the procedure described in "Upgrading from Pre-4.3 NorthStar with Analytics" on page 31.

Analytics Geo-HA

NorthStar Controller supports analytics geo-HA as of release 5.1.0. While original analytics HA was designed for local clusters (same data center), geo-HA makes all data available on all nodes, to better serve networks where the nodes are geographically remote from one another. To achieve this, a local RabbitMQ (messaging bus) is installed on each analytics (ElasticSearch) node. This improves the tolerance for latency and helps compensate for the tendency of remote nodes to become out of sync.

The remote ElasticSearch nodes use JTI logstash to retrieve and process the data from the other ElasticSearch nodes. The replication pipeline creates a named queue on each remote server. The queues are persistent so that if any ElasticSearch node goes down, it can recover by resuming the processing of data pushed onto the remote queue. Figure 22 on page 114 shows the interactions within a node and between nodes.

Figure 22: Analytics Geo-HA Interactions



The Analytics Collector Configuration Settings menu within the net_setup.py script has an option to prepare and deploy Geo-HA.

Single-Server Deployment–No NorthStar HA

To install the data collector together with the NorthStar application in a single-server deployment (without NorthStar HA), use the following procedure:

1. On the NorthStar application node, install the NorthStar Controller bundle, using the install.sh script. See the “Installing the NorthStar Controller” on page 45.

2. On the same node, run the install-analytics.sh script.

```
[root@ns ~]# cd /opt/northstar/northstar_bundle_x.x.x/
[root@ns northstar_bundle_x.x.x]# ./install-analytics.sh
```

```
groupadd: group 'pcs' already exists
package NorthStar-libUtils is not installed
Loaded plugins: fastestmirror
Setting up Install Process
Loading mirror speeds from cached hostfile
northstar_bundle                | 2.9 kB     00:00 ...
Resolving Dependencies
--> Running transaction check
---> Package NorthStar-libUtils.x86_64 0:3.1.0-20161127_68470_213 will be
installed
--> Finished Dependency Resolution

Dependencies Resolved
.
.
.
```

3. Verify that the three analytics processes are installed and running by executing **supervisorctl status** on the PC Server:

```
[root@ns ~]# supervisorctl status
```

```
analytics:elasticsearch          RUNNING   pid 7073, uptime 21:57:29
analytics:esauthproxy            RUNNING   pid 7072, uptime 21:57:29
analytics:logstash               RUNNING   pid 7231, uptime 21:57:26
```

External Analytics Node(s)–No NorthStar HA

Figure 23 on page 116 shows a sample configuration with a single NorthStar application node and three analytics nodes comprising an analytics cluster. All the nodes connect to the same Ethernet network, through the eth1 interface. Optionally, you could have a single analytics node rather than creating an analytics cluster. The instructions in this section cover both a single external analytics node and an external analytics cluster.

Figure 23: Analytics Cluster Deployment (No NorthStar HA)



To install one or a cluster of external analytics nodes, use the following procedure:

1. On the NorthStar application node, install the NorthStar Controller application, using the install.sh script. See "Installing the NorthStar Controller" on page 45.

2. On each analytics node, install northstar_bundle.rpm, but do not run the install.sh script. Instead, run the install-analytics.sh script. The script installs all required dependencies such as NorthStar-JDK, NorthStar-Python, and so on. For NorthStar Analytics1, it would look like this:

```
[root@NorthStarAnalytics1]# rpm -Uvh <rpm-filename>
[root@NorthStarAnalytics1]# cd /opt/northstar/northstar_bundle_x.x.x/
[root@NorthStarAnalytics1 northstar_bundle_x.x.x]# install-analytics.sh
groupadd: group 'pcs' already exists
package NorthStar-PCS is not installed
Loaded plugins: fastestmirror
Setting up Update Process
Loading mirror speeds from cached hostfile
northstar_bundle            | 2.9 kB     00:00 ...
No Packages marked for Update
Loaded plugins: fastestmirror
Setting up Update Process
```

```
Loading mirror speeds from cached hostfile
No Packages marked for Update
Loaded plugins: fastestmirror
Setting up Update Process
.
.
.
```

3. The next configuration steps require you to run the net_setup.py script to configure the NorthStar node and the analytics nodes(s) so they can connect to each other. But before you do that, we recommend that you copy the public SSH key of the node where the net_setup.py script is to be executed to all other nodes. The net_setup.py script can be run on either the NorthStar application node or one of the analytics nodes to configure all the nodes. This is not a required step, but it saves typing the passwords of all the systems later when the script is deploying the configurations or testing the connectivity to the different nodes.

   `[root@NorthStarAnalytics1 network-scripts]#` **ssh-copy-id root@192.168.10.200**

   ```
   root@192.168.10.200's password:
   ```

   Try logging into the machine using **ssh root@192.168.10.200** and check in with **.ssh/authorized_keys**.

   Repeat this process for all nodes (192.168.10.100, 192.168.10.200, 192.168.10.201, and 192.168.10.202 in our example).

4. Run net_setup.py on the NorthStar application node or on one of the analytics nodes. The Main Menu is displayed:

   ```
   Main Menu:
       ..........................................
       A.) Host Setting
       ..........................................
       B.) JunosVM Setting
       ..........................................
       C.) Check Network Setting
       ..........................................
       D.) Maintenance & Troubleshooting
       ..........................................
       E.) HA Setting
       ..........................................
       F.) Collect Trace/Log
       ..........................................
       G.) Analytics Data Collector Setting
   ```

```
      (External standalone/cluster analytics server)
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
```

5. Select **G** Analytics Data Collector Setting. The Data Collector Configuration Settings menu is displayed.

```
    Analytics Data Collector Configuration Settings:
        (External standalone/cluster analytics server)
    ******************************************************
    Note: This configuration only applicable for data collector
    installation in separate server
    ******************************************************
    ......................................................

        NorthStar App #1
             Hostname                                :
             Interface
                  Name                               : external0
                  IPv4                               :
    ......................................................
        Analytics Collector #1
             Hostname                                :
             Priority                                : 0
             Interface
                  Name                               : external0
                  IPv4                               :

    1. ) Add NorthStar App
    2. ) Add analytics data collector
    3. ) Modify NorthStar App
    4. ) Modify analytics data collector
    5A.) Remove NorthStar App
    5B.) Delete NorthStar App data
    6A.) Remove analytics data collector
    6B.) Delete analytics data collector data
    ......................................................
    7A.) Virtual IP for Northstar App                 :
```

```
   7B.) Delete Virtual IP for Northstar App
   8A.) Virtual IP for Analytics Collector                    :
   8B.) Delete Virtual IP for Analytics Collector
   ..........................................................
   9. ) Test Analytics Data Collector Connectivity
   A. ) Prepare and Deploy SINGLE Data Collector Setting
   B. ) Prepare and Deploy HA Analytics Data Collector Setting
   C. ) Prepare and Deploy GEO-HA Analytics Data Collector Setting
   D. ) Copy Collector setting to other nodes
   E. ) Add a new Collector node to existing cluster
   F. ) Sync Config with NorthStar App
   ..........................................................

   Please select a number to modify.
   [<CR>=return to main menu]:
```

6. Select options from the Data Collector Configuration Settings menu to make the following configuration changes:

   - Select **3** to modify the NorthStar application node settings, and configure the NorthStar server name and IP address. For example:

     ```
     Please select a number to modify.
     [CR=return to main menu]:
     3
     ```

     ```
     NorthStar App ID : 1

     current NorthStar App #1 hostname (without domain name) :
     new NorthStar App #1 hostname (without domain name) : NorthStarAppServer

     current NorthStar App #1 interface name : external0
     new NorthStar App #1 interface name : eth1

     current NorthStar App #1 interface IPv4 address :
     new NorthStar App #1 interface IPv4 address : 192.168.10.100


     Press any key to return to menu
     ```

   - Select **4** to modify the analytics node IP address. For example:

     ```
     Please select a number to modify.
     [CR=return to main menu]:
     ```

4

```
Collector ID : 1

current collector #1 hostname (without domain name) :
new collector #1 hostname (without domain name) : NorthStarAnalytics1

current collector #1 node priority : 0
new collector #1 node priority : 10

current collector #1 interface name : external0
new collector #1 interface name : eth1

current collector #1 interface IPv4 address :
new collector #1 interface IPv4 address : 192.168.10.200


Press any key to return to menu
```

- Select **2** to add additional analytics nodes as needed. In our analytics cluster example, two additional analytics nodes would be added:

```
Please select a number to modify.
[CR=return to main menu]:
2
```

```
New collector ID : 2

current collector #2 hostname (without domain name) :
new collector #2 hostname (without domain name) : NorthStarAnalytics2

current collector #2 node priority : 0
new collector #2 node priority : 20

current collector #2 interface name : external0
new collector #2 interface name : eth1

current collector #2 interface IPv4 address :
new collector #2 interface IPv4 address : 192.168.10.201


Press any key to return to menu
```

```
Please select a number to modify.
[CR=return to main menu]:
```

2

```
New collector ID : 3

current collector #3 hostname (without domain name) :
new collector #3 hostname (without domain name) : NorthStarAnalytics3

current collector #3 node priority : 0
new collector #3 node priority : 30

current collector #3 interface name : external0
new collector #3 interface name : eth1

current collector #3 interface IPv4 address :
new collector #3 interface IPv4 address : 192.168.10.202


Press any key to return to menu
```

- Select **8A** to configure a VIP address for the cluster of analytics nodes. This is required if you have an analytics cluster. If you have a single external analytics node only (not a cluster), you can skip this step.

  ```
  Please select a number to modify.
  [CR=return to main menu]:
  8A
  ```

  ```
  current Virtual IP for Collector :
  new Virtual IP for Collector : 192.168.10.250

  Press any key to return to menu
  ```

  This VIP serves two purposes:

  - It allows the NorthStar server to send queries to a single endpoint. The VIP will be active on one of the analytics nodes, and will switch over in the event of a failure (a full node failure or failure of any of the processes running on the analytics node).
  - Devices can send telemetry data to the VIP, ensuring that if an analytics node fails, the telemetry data can still be processed by whichever non-failing node takes ownership of the VIP.

The configuration for our analytics cluster example should now look like this:

```
    Analytics Data Collector Configuration Settings:
    (External standalone/cluster analytics server)
```

```
*****************************************************
Note: This configuration only applicable for analytics
data collector installation in separate server
*****************************************************
.....................................................
    NorthStar App #1
         Hostname                                : NorthStarAppServer
         Interface
              Name                               : eth1
              IPv4                               : 192.168.10.100
.....................................................
    Analytics Collector #1
         Hostname                                : NorthStarAnalytics1
         Priority                                : 10
         Interface
              Name                               : eth1
              IPv4                               : 192.168.10.200
    Analytics Collector #2
         Hostname                                : NorthStarAnalytics2
         Priority                                : 20
         Interface
              Name                               : eth1
              IPv4                               : 192.168.10.201
    Analytics Collector #3
         Hostname                                : NorthStarAnalytics3
         Priority                                : 30
         Interface
              Name                               : eth1
              IPv4                               : 192.168.10.202

1. ) Add NorthStar App
2. ) Add analytics data collector
3. ) Modify NorthStar App
4. ) Modify analytics data collector
5A.) Remove NorthStar App
5B.) Delete NorthStar App data
6A.) Remove analytics data collector
6B.) Delete analytics data collector data
.....................................................
7A.) Virtual IP for Northstar App                 :
7B.) Delete Virtual IP for Northstar App
8A.) Virtual IP for Analytics Collector           : 192.168.10.250
8B.) Delete Virtual IP for Analytics Collector
.....................................................
```

```
    9. ) Test Analytics Data Collector Connectivity
    A. ) Prepare and Deploy SINGLE Data Collector Setting
    B. ) Prepare and Deploy HA Analytics Data Collector Setting
    C. ) Prepare and Deploy GEO-HA Analytics Data Collector Setting
    D. ) Copy Collector setting to other nodes
    E. ) Add a new Collector node to existing cluster
    F. ) Sync Config with NorthStar App
    ....................................................

    Please select a number to modify.
    [<CR>=return to main menu]:
```

7. Select **9** to test connectivity between nodes. This is applicable whenever you have external analytics nodes, whether just one or a cluster of them. For example:

```
Please select a number to modify.
[CR=return to main menu]:
9
```

```
Validate NorthStar App configuration interface
Validate Collector configuration interface

Verifying the NorthStar version on each NorthStar App node:
NorthStar App #1 NorthStarAppServer:
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64

Collector #1 NorthStarAnalytics1 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
Collector #2 NorthStarAnalytics2 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
Collector #3 NorthStarAnalytics3 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64

Checking NorthStar App connectivity...
NorthStar App #1 interface name eth1 ip 192.168.10.100: OK

Checking collector connectivity...
Collector #1 interface name eth1 ip 192.168.10.200: OK
Collector #2 interface name eth1 ip 192.168.10.201: OK
Collector #3 interface name eth1 ip 192.168.10.202: OK
Press any key to return to menu
```

8. Select **A** (for a single analytics node), **B** (for an analytics cluster), or **C** for analytics geo-HA to configure the node(s) for deployment.

NOTE: This option restarts the web process in the NorthStar application node.

For our example, select **B**:

```
Please select a number to modify.
[CR=return to main menu]:
B
```

```
Setup mode set to "cluster"

Validate NorthStar App configuration interface
Validate Collector configuration interface

Verifying the NorthStar version on each NorthStar App node:
NorthStar App #1 NorthStarAppServer:
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64

Verifying the NorthStar version on each Collector node:
Collector #1 NorthStarCollector1 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
Collector #2 NorthStarCollector2 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
Collector #3 NorthStarCollector3 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64

WARNING !
The selected menu will restart nodejs process in Northstar App node
Type YES to continue...
```

YES

```
Checking NorthStar App connectivity...
NorthStar App #1 interface name eth1 ip 192.168.10.100: OK

Checking collector connectivity...
Collector #1 interface name eth1 ip 192.168.10.200: OK
Collector #2 interface name eth1 ip 192.168.10.201: OK
Collector #3 interface name eth1 ip 192.168.10.202: OK

Checking analytics process in NorthStar App node ...
Detected analytics is not in NorthStar App node #1: OK

Checking analytics process in collector node ...
```

```
Detected analytics in collector node #1: OK
Detected analytics in collector node #2: OK
Detected analytics in collector node #3: OK

External data collector set to "yes"

Sync configuration for NorthStar App #1: OK

Sync configuration for Collector #1: OK

Sync configuration for Collector #2: OK

Sync configuration for Collector #3: OK

Preparing collector #1 basic configuration ..

Uploading config files to collector01

Preparing collector #2 basic configuration ..

Uploading config files to collector02

Preparing collector #3 basic configuration ..

Uploading config files to collector03

Applying data collector config files

Applying data collector config files at NorthStar App
Deploying NorthStar App #1 collector configuration ...

Applying data collector config files at collector
Deploying collector #1 collector configuration ...
Deploying collector #2 collector configuration ...
Deploying collector #3 collector configuration ...

Deploying collector #1 zookeeper configuration ...
Wait 2 minutes before adding new node
...10 seconds
...20 seconds
...30 seconds
...40 seconds
...50 seconds
...60 seconds
```

```
...70 seconds
...80 seconds
...90 seconds
...100 seconds
...110 seconds

Deploying collector #2 zookeeper configuration ...
Wait 2 minutes before adding new node
...10 seconds
...20 seconds
...30 seconds
...40 seconds
...50 seconds
...60 seconds
...70 seconds
...80 seconds
...90 seconds
...100 seconds
...110 seconds

Deploying collector #3 zookeeper configuration ...


Restart ZooKeeper at collector #1 collector01

Restart ZooKeeper at collector #2 collector02

Restart ZooKeeper at collector #3 collector03



Restart Analytics at collector #1 collector01

Restart Analytics at collector #2 collector02

Restart Analytics at collector #3 collector03



Restart HA Agent at collector #1 collector01
Please wait for HA Agent process initialization
...10 seconds
...20 seconds
```

```
Restart HA Agent at collector #2 collector02
Please wait for HA Agent process initialization
...10 seconds
...20 seconds

Restart HA Agent at collector #3 collector03
Please wait for HA Agent process initialization
...10 seconds
...20 seconds



Restart Nodejs at Northstar App #1 pcs


Collector configurations has been applied successfully

Press any key to return to menu
```

This completes the installation, and telemetry data can now be sent to the analytics nodes via the analytics VIP.

> **NOTE:** If you opt to send telemetry data to an individual node instead of using the VIP of the analytics cluster, and that node goes down, the streams to the node are lost. If you opt to install only one analytics node instead of an analytics cluster that uses a VIP, you run the same risk.

External Analytics Node(s)–With NorthStar HA

Figure 24 on page 128 shows a sample configuration with a NorthStar HA cluster of three nodes and three analytics nodes comprising an analytics cluster, for a total of six nodes. All the nodes connect to the same Ethernet network, through the eth1 interface. In a NorthStar HA environment, you could also opt to have a single analytics node, for a total of four nodes, but analytics collection would not be protected in the event of analytics node failure.

Figure 24: Analytics Cluster Deployment (With NorthStar HA)



For this scenario, you first configure the NorthStar application HA cluster according to the instructions in "Configuring a NorthStar Cluster for High Availability" on page 154.

Once the NorthStar HA cluster is configured, set up the external analytics cluster. The setup steps for the external analytics cluster are exactly the same as in the previous section, *External Analytics Node(s)–No NorthStar HA*. Once you complete them, the configuration should look like this:

```
Analytics Data Collector Configuration Settings:
(External standalone/cluster analytics server)
******************************************************
Note: This configuration only applicable for analytics
data collector installation in separate server
******************************************************
.....................................................
    NorthStar App #1
         Hostname                              : NorthStarAppServer1
         Interface
              Name                             : eth1
```

```
               IPv4                                    : 192.168.10.100
     NorthStar App #2
          Hostname                                     : NorthStarAppServer2
          Interface
               Name                                    : eth1
               IPv4                                    : 192.168.10.101
     NorthStar App #3
          Hostname                                     : NorthStarAppServer3
          Interface
               Name                                    : eth1
               IPv4                                    : 192.168.10.102
.....................................................
     Analytics Collector #1
          Hostname                                     : NorthStarAnalytics1
          Priority                                     : 10
          Interface
               Name                                    : eth1
               IPv4                                    : 192.168.10.200
     Analytics Collector #2
          Hostname                                     : NorthStarAnalytics2
          Priority                                     : 20
          Interface
               Name                                    : eth1
               IPv4                                    : 192.168.10.201
     Analytics Collector #3
          Hostname                                     : NorthStarAnalytics3
          Priority                                     : 30
          Interface
               Name                                    : eth1
               IPv4                                    : 192.168.10.202

1. ) Add NorthStar App
2. ) Add analytics data collector
3. ) Modify NorthStar App
4. ) Modify analytics data collector
5A.) Remove NorthStar App
5B.) Delete NorthStar App data
6A.) Remove analytics data collector
6B.) Delete analytics data collector data
.....................................................
7A.) Virtual IP for Northstar App                   : 192.168.10.249
7B.) Delete Virtual IP for Northstar App
8A.) Virtual IP for Analytics Collector            : 192.168.10.250
8B.) Delete Virtual IP for Analytics Collector
```

```
.....................................................
9. ) Test Analytics Data Collector Connectivity
A. ) Prepare and Deploy SINGLE Data Collector Setting
B. ) Prepare and Deploy HA Analytics Data Collector Setting
C. ) Prepare and Deploy GEO-HA Analytics Data Collector Setting
D. ) Copy Collector setting to other nodes
E. ) Add a new Collector node to existing cluster
F. ) Sync Config with NorthStar App
.....................................................

Please select a number to modify.
[<CR>=return to main menu]:
```

Test connectivity between nodes by selecting **9** from the menu.

Configure the nodes for deployment by selecting **B** for HA analytics or **C** for Geo-HA analytics. This restarts the web process in the NorthStar application node.

Verifying Data Collection When You Have External Analytics Nodes

Verify that data collection is working by checking that all services are running. Only the relevant processes are shown below.

`[root@NorthStarAnalytics1 ~]#` **supervisorctl status**

```
analytics:elasticsearch          RUNNING   pid 4406, uptime 0:02:06
analytics:esauthproxy            RUNNING   pid 4405, uptime 0:02:06
analytics:logstash               RUNNING   pid 4407, uptime 0:02:06
infra:ha_agent                   RUNNING   pid 4583, uptime 0:00:19
infra:healthmonitor              RUNNING   pid 3491, uptime 1:01:09
infra:zookeeper                  RUNNING   pid 4324, uptime 0:03:16
listener1:listener1_00           RUNNING   pid 4325, uptime 0:03:16
```

The analytics node(s) should start processing all records from the network, and pushing statistics to the NorthStar node through RabbitMQ. Check the pcs.log in the NorthStar node to see the statistics being pushed to the PC server. For example:

```
11-28T13:18:02.174126 30749 PCServer  [NorthStar][PCServer][<-AMQP] msg=0x00004018
routing_key = ns_tunnel_traffic
```

```
11-28T13:18:02.174280 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF1-PE1-PE2@PE1 111094
11-28T13:18:02.174429 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF1-PE1-PE3@PE1 824
11-28T13:18:02.174764 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  CS1-PE3-PE3@PE3 0
11-28T13:18:02.174930 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  CS2-PE3-PE2@PE3 0
11-28T13:18:02.175067 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF2-PE3-PE3@PE3 0
11-28T13:18:02.175434 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF2-PE3-PE1@PE3 0
11-28T13:18:02.175614 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF1-PE3-PE1@PE3 0
11-28T13:18:02.175749 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  CS2-PE3-PE3@PE3 0
11-28T13:18:02.175873 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  CS1-PE3-PE1@PE3 0
11-28T13:18:02.175989 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  CS1-PE3-PE2@PE3 0
11-28T13:18:02.176128 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  CS2-PE3-PE1@PE3 824
11-28T13:18:02.176256 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF1-PE3-PE3@PE3 0
11-28T13:18:02.176393 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF1-PE2-PE1@PE2 112552
11-28T13:18:02.176650 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  AF1-PE2-PE1@PE2 0
11-28T13:18:02.176894 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  AF2-PE2-PE1@PE2 0
11-28T13:18:02.177059 30749 PCServer  [NorthStar][PCServer][Traffic] msg=0x00005004
  EF12-PE2-PE1@PE2 0
```

You can also use the REST APIs to get some aggregated statistics. This tests the path from client to nodejs to Elasticsearch.

```
 curl --insecure -X POST -H "Authorization: Bearer
7IEvYhvABrae6m1AgI+zi4V0n7UiJNA2HqliK7PfGhY=" -H "Content-Type: application/json"
-d '{
  "endTime": "now",
  "startTime": "now-1h",
  "aggregation": "avg",
  "counter": "interface_stats.egress_stats.if_bps"
}' "https://localhost:8443/NorthStar/API/v2/tenant/1/statistics/device/top"
```

```
[

  {
    "id": {
      "statisticType": "device",
      "name": "vmx105",
      "node": {
        "topoObjectType": "node",
        "hostName": "vmx105"
      }
    },
    "interface_stats.egress_stats.if_bps": 525088
  },
  {
    "id": {
      "statisticType": "device",
      "name": "PE1",
      "node": {
        "topoObjectType": "node",
        "hostName": "PE1"
      }
    },
    "interface_stats.egress_stats.if_bps": 228114
  },
  {
    "id": {
      "statisticType": "device",
      "name": "PE2",
      "node": {
        "topoObjectType": "node",
        "hostName": "PE2"
      }
    },
    "interface_stats.egress_stats.if_bps": 227747
  },
  {
    "id": {
      "statisticType": "device",
      "name": "PE3",
      "node": {
        "topoObjectType": "node",
        "hostName": "PE3"
      }
    },
```

```
    "interface_stats.egress_stats.if_bps": 6641
  },
  {
    "id": {
      "statisticType": "device",
      "name": "PE4",
      "node": {
        "topoObjectType": "node",
        "hostName": "PE4"
      }
    },
    "interface_stats.egress_stats.if_bps": 5930
  }
]
```

Replacing a Failed Node in an External Analytics Cluster

On the Data Collector Configuration Settings menu, options D and E can be used when physically replacing a failed node. They allow you to replace a node without having to redeploy the entire cluster.

CAUTION: While a node is being replaced in a three-node cluster, HA for analytics data is not guaranteed.

1. Replace the physical node in the network and install northstar_bundle.rpm on the replacement node. In our example, the replacement node is NorthStarAnalytics3.

2. Run the install-analytics.sh script to install all required dependencies such as NorthStar-JDK, NorthStar-Python, and so on. For NorthStarAnalytics3, it would look like this:

   ```
   [root@NorthStarAnalytics3]# rpm -Uvh <rpm-filename>
   [root@NorthStarAnalytics3]# cd /opt/northstar/northstar_bundle_x.x.x/
   [root@NorthStarAnalytics3 northstar_bundle_x.x.x]# install-analytics.sh
   ```

   ```
   groupadd: group 'pcs' already exists
   package NorthStar-PCS is not installed
   Loaded plugins: fastestmirror
   Setting up Update Process
   Loading mirror speeds from cached hostfile
   ```

```
northstar_bundle            | 2.9 kB     00:00 ...
No Packages marked for Update
Loaded plugins: fastestmirror
Setting up Update Process
Loading mirror speeds from cached hostfile
No Packages marked for Update
Loaded plugins: fastestmirror
Setting up Update Process
.
.
.
```

3. Set up the SSH key from an anchor node to the replacement node. The anchor node can be a NorthStar application node or one of the analytics cluster nodes (other than the replacement node). Copy the public SSH key from the anchor node to the replacement node, from the replacement node to the other nodes (NorthStar application nodes and analytics cluster nodes), and from the other nodes (NorthStar application nodes and analytics cluster nodes) to the replacement node.

   For example:

   `[root@NorthStarAnalytics1 network-scripts]#` **ssh-copy-id root@192.168.10.202**

   ```
   root@192.168.10.202's password:
   ```

   Try logging into the machine using **ssh root@192.168.10.202** and check in with **.ssh/authorized_keys**.

4. Run net_setup.py on the node you selected. The Main Menu is displayed:

   ```
   Main Menu:
       ........................................
       A.) Host Setting
       ........................................
       B.) JunosVM Setting
       ........................................
       C.) Check Network Setting
       ........................................
       D.) Maintenance & Troubleshooting
       ........................................
       E.) HA Setting
       ........................................
       F.) Collect Trace/Log
       ........................................
       G.) Analytics Data Collector Setting
   ```

```
      (External standalone/cluster analytics server)
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
```

5. Select **G** Data Collector Setting. The Data Collector Configuration Settings menu is displayed.

```
    Analytics Data Collector Configuration Settings:
         (External standalone/cluster analytics server)
    ******************************************************
    Note: This configuration only applicable for analytics
    data collector installation in separate server
    ******************************************************
    ......................................................
        NorthStar App #1
             Hostname                              : NorthStarAppServer1
             Interface
                  Name                             : eth1
                  IPv4                             : 192.168.10.100
    ......................................................
        NorthStar App #2
             Hostname                              : NorthStarAppServer2
             Interface
                  Name                             : eth1
                  IPv4                             : 192.168.10.101
    ......................................................
        NorthStar App #3
             Hostname                              : NorthStarAppServer3
             Interface
                  Name                             : eth1
                  IPv4                             : 192.168.10.102
    ......................................................
        Analytics Collector #1
             Hostname                              : NorthStarAnalytics1
             Priority                              : 10
             Interface
                  Name                             : eth1
                  IPv4                             : 192.168.10.200
```

```
.....................................................
    Analytics Collector #2
         Hostname                                : NorthStarAnalytics2
         Priority                                : 20
         Interface
              Name                               : eth1
              IPv4                               : 192.168.10.201
.....................................................
    Analytics Collector #3
         Hostname                                : NorthStarAnalytics3
         Priority                                : 30
         Interface
              Name                               : eth1
              IPv4                               : 192.168.10.202

1. ) Add NorthStar App
2. ) Add analytics data collector
3. ) Modify NorthStar App
4. ) Modify analytics data collector
5A.) Remove NorthStar App
5B.) Delete NorthStar App data
6A.) Remove analytics data collector
6B.) Delete analytics data collector data
.....................................................
7A.) Virtual IP for Northstar App                 : 192.168.10.249
7B.) Delete Virtual IP for Northstar App
8A.) Virtual IP for Collector                     : 192.168.10.250
8B.) Delete Virtual IP for Analytics Collector
.....................................................
9. ) Test Analytics Data Collector Connectivity
A. ) Prepare and Deploy SINGLE Data Collector Setting
B. ) Prepare and Deploy HA Analytics Data Collector Setting
C. ) Prepare and Deploy GEO-HA Analytics Data Collector Setting
D. ) Copy Collector setting to other nodes
E. ) Add a new Collector node to existing cluster
F. ) Sync Config with NorthStar App
.....................................................
Please select a number to modify.
[<CR>=return to main menu]:
```

6. Select option **9** to test connectivity to all NorthStar application nodes and analytics cluster nodes.

```
Checking NorthStar App connectivity...
NorthStar App #1 interface name eth1 ip 192.168.10.100: OK
NorthStar App #2 interface name eth1 ip 192.168.10.101: OK
NorthStar App #3 interface name eth1 ip 192.168.10.102: OK

Checking collector connectivity...
Collector #1 interface name eth1 ip 192.168.10.200: OK
Collector #2 interface name eth1 ip 192.168.10.201: OK
Collector #3 interface name eth1 ip 192.168.10.202: OK
```

7. Select option **D** to copy the analytics settings to the other nodes.

```
Validate NorthStar App configuration interface
Validate Collector configuration interface

Verifying the NorthStar version on each NorthStar App node:
NorthStar App #1 NorthStarAppServer1 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
NorthStar App #2 NorthStarAppServer2 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
NorthStar App #3 NorthStarAppServer3 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64

Verifying the NorthStar version on each Collector node:
Collector #1 NorthStarAnalytics1 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
Collector #2 NorthStarAnalytics2 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64
Collector #3 NorthStarAnalytics3 :
NorthStar-Bundle-3.1.0-20170517_195239_70090_547.x86_64

Checking NorthStar App connectivity...
NorthStar App #1 interface name eth1 ip 192.168.10.100: OK
NorthStar App #2 interface name eth1 ip 192.168.10.101: OK
NorthStar App #3 interface name eth1 ip 192.168.10.102: OK

Checking collector connectivity...
Collector #1 interface name eth1 ip 192.168.10.200: OK
Collector #2 interface name eth1 ip 192.168.10.201: OK
Collector #3 interface name eth1 ip 192.168.10.202: OK

Sync configuration for NorthStar App #1: OK
Sync configuration for NorthStar App #2: OK
```

```
Sync configuration for NorthStar App #3: OK

Sync configuration for Collector #1: OK
Sync configuration for Collector #2: OK
Sync configuration for Collector #3: OK
```

8. Select option **E** to add the replacement node to the cluster. Specify the node ID of the replacement node.

9. On any analytics cluster node, use the following command to check Elasticsearch cluster status. Verify that the status is “green” and the number of nodes is correct.

```
[root@NorthStarAnalytics1]# curl -XGET 'localhost:9200/_cluster/health?pretty'
{
"cluster_name" : "NorthStar",
"status" : "green",
"timed_out" : false,
"number_of_nodes" : 3,
"number_of_data_nodes" : 3,
"active_primary_shards" : 10,
"active_shards" : 10,
"relocating_shards" : 0,
"initializing_shards" : 0,
"unassigned_shards" : 0,
"delayed_unassigned_shards" : 0,
"number_of_pending_tasks" : 0,
"number_of_in_flight_fetch" : 0,
"task_max_waiting_in_queue_millis" : 0,
"active_shards_percent_as_number" : 100.0
}
```

Collectors Installed on the NorthStar HA Cluster Nodes

In a NorthStar HA environment, you can achieve failover protection simultaneously for the NorthStar application and for analytics by setting up each node in the NorthStar cluster to also serve as an analytics node. Because nothing is external to the NorthStar cluster, your total number of nodes is the number in the NorthStar cluster (minimum of three). Figure 25 on page 139 shows this installation scenario.

Figure 25: NorthStar HA Cluster Nodes with Analytics



To set up this scenario, you first install both the NorthStar application and analytics on each of the standalone nodes, configure the nodes to be an HA cluster, and finally, configure the nodes to be an analytics cluster. Follow these steps:

1. On each NorthStar application node, install the NorthStar Controller application, using the install.sh script. See the "Installing the NorthStar Controller" on page 45.

2. On each node, install northstar_bundle.rpm, and run the install-analytics.sh script. The script installs all required dependencies such as NorthStar-JDK, NorthStar-Python, and so on. For node ns03 in the example, it would look like this:

```
[root@ns03]# rpm -Uvh <rpm-filename>
[root@ns03]# cd /opt/northstar/northstar_bundle_x.x.x/
[root@ns03 northstar_bundle_x.x.x]# install-analytics.sh
groupadd: group 'pcs' already exists
package NorthStar-PCS is not installed
Loaded plugins: fastestmirror
Setting up Update Process
Loading mirror speeds from cached hostfile
northstar_bundle           | 2.9 kB     00:00 ...
```

```
No Packages marked for Update
Loaded plugins: fastestmirror
Setting up Update Process
Loading mirror speeds from cached hostfile
No Packages marked for Update
Loaded plugins: fastestmirror
Setting up Update Process
.
.
.
```

3. Use the following command on each node to ensure that the three analytics processes are installed and running:

```
[root@ns03 ~]# supervisorctl status | grep analytics:*
analytics:elasticsearch          RUNNING   pid 16238, uptime 20:58:37
analytics:esauthproxy            RUNNING   pid 16237, uptime 20:58:37
analytics:logstash               RUNNING   pid 3643, uptime 20:13:08
```

4. Follow the instructions in "Configuring a NorthStar Cluster for High Availability" on page 154 to configure the nodes for NorthStar HA. This involves running the net_setup.py utility, selecting **E** to access the HA Setup menu, and completing the HA setup steps using that menu.

5. From the HA Setup menu, press **Enter** to return to the main net_setup.py menu. The Main Menu is displayed:

```
Main Menu:
    ..........................................
    A.) Host Setting
    ..........................................
    B.) JunosVM Setting
    ..........................................
    C.) Check Network Setting
    ..........................................
    D.) Maintenance & Troubleshooting
    ..........................................
    E.) HA Setting
    ..........................................
    F.) Collect Trace/Log
    ..........................................
    G.) Data Collector Setting
      (External standalone/cluster analytics server)
```

```
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
```

6. Select **I** to proceed. This menu option applies the settings you have already configured for your NorthStar HA cluster, so you do not need to make any changes.

```
    Internal Analytics Configuration HA Settings:
    ******************************************************
    Note: This configuration only applicable for analytics
    installation in the same server
    ******************************************************
   ........................................................
   Node #1
       Hostname                       : ns03
       Priority                       : 10
       Cluster Communication Interface : eth2
       Cluster Communication IP       : 172.16.18.13
          Interfaces
            Interface #1
               Name                   : eth2
               IPv4                   : 172.16.18.13
               Switchover             : yes
            Interface #2
               Name                   : mgmt0
               IPv4                   :
               Switchover             : yes
            Interface #3
            Interface #4
            Interface #5
   Node #2
       Hostname                       : ns04
       Priority                       : 20
       Cluster Communication Interface : eth2
       Cluster Communication IP       : 172.16.18.14
          Interfaces
            Interface #1
               Name                   : eth2
```

```
               IPv4                    : 172.16.18.14
               Switchover              : yes
            Interface #2
             Name                    : mgmt0
               IPv4                    :
               Switchover              : yes
            Interface #3
            Interface #4
            Interface #5
   Node #3
       Hostname                        : ns05
       Priority                        : 30
       Cluster Communication Interface : eth2
       Cluster Communication IP        : 172.16.18.15
          Interfaces
            Interface #1
               Name                    : eth2
               IPv4                    : 172.16.18.15
               Switchover              : yes
            Interface #2
               Name                    : mgmt0
               IPv4                    :
               Switchover              : yes
            Interface #3
            Interface #4
            Interface #5

   ......................................................
   1.) Prepare and Deploy Internal Analytics HA configs
   ......................................................

Please select a number to modify.
[<CR>=return to main menu]:
```

NOTE: Depending on the geographical location of the nodes, you might want to use analytics geo-HA instead of setting up internal analytics. In that case, instead of selecting **I**, you would select **G** to access the Analytics Data Collector Configuration Settings. After updating those settings, select **C** (Prepare and Deploy GEO-HA Analytics Data Collector Setting). Step 7 below would not apply.

7. Select **1** to set up the NorthStar HA cluster for analytics.

```
WARNING !
The selected menu will restart analytics processes in each cluster member
Type YES to continue...
YES

Checking connectivity of cluster_communication_interface...
Cluster communications status for node ns03 cluster interface eth2 ip 172.16.18.13:
 OK
Cluster communications status for node ns04 cluster interface eth2 ip 172.16.18.14:
 OK
Cluster communications status for node ns05 cluster interface eth2 ip 172.16.18.15:
 OK


Verifying the NorthStar version on each node:
ns03 : NorthStar-Bundle-18.1.0-20180412_071430_72952_187.x86_64
ns04 : NorthStar-Bundle-18.1.0-20180412_071430_72952_187.x86_64
ns05 : NorthStar-Bundle-18.1.0-20180412_071430_72952_187.x86_64

Checking analytics process in each node ...
Detected analytics in node #1 ns03: OK
Detected analytics in node #2 ns04: OK
Detected analytics in node #3 ns05: OK

Applying analytics config files
Deploying analytics configuration in node #1 ns03
Deploying analytics configuration in node #2 ns04
Deploying analytics configuration in node #3 ns05


Restart Analytics at node #1 ns03

Restart Analytics at node #2 ns04

Restart Analytics at node #3 ns05


Internal analytics configurations has been applied successfully

Press any key to return to menu
```

8. On any analytics node, use the following command to check elasticsearch cluster status. Verify that the status is “green” and the number of nodes is correct.

```
[root@ns03 ~]# curl -XGET 'localhost:9200/_cluster/health?pretty'
{
  "cluster_name" : "NorthStar",
  "status" : "green",
  "timed_out" : false,
  "number_of_nodes" : 3,
  "number_of_data_nodes" : 3,
  "active_primary_shards" : 10,
  "active_shards" : 10,
  "relocating_shards" : 0,
  "initializing_shards" : 0,
  "unassigned_shards" : 0,
  "delayed_unassigned_shards" : 0,
  "number_of_pending_tasks" : 0,
  "number_of_in_flight_fetch" : 0,
  "task_max_waiting_in_queue_millis" : 0,
  "active_shards_percent_as_number" : 100.0
}
```

Troubleshooting Logs

The following logs are available to help with troubleshooting:

- /opt/northstar/logs/elasticsearch.msg
- /opt/northstar/logs/logstash.msg
- /opt/northstar/logs/logstash.log

See *Logs* in the *NorthStar Controller User Guide* for more information.

RELATED DOCUMENTATION

Installing the NorthStar Controller | **45**

Configuring Routers to Send JTI Telemetry Data and RPM Statistics to the Data Collectors | **145**

Configuring a NorthStar Cluster for High Availability | **154**

Logs (*NorthStar Controller User Guide*)

Configuring Routers to Send JTI Telemetry Data and RPM Statistics to the Data Collectors

Junos Telemetry Interface (JTI) sensors generate data from the PFE (LSP traffic data, logical and physical interface traffic data), and will only send probes through the data plane. So, in addition to connecting the routing engine to the management network, a data port must be connected to the collector on one of your devices. The rest of the devices in the network can use that interface to reach the collector.

> **NOTE:** You must use Junos OS Release 15.1F6 or later for NorthStar analytics.

To configure the routers, use the following procedure:

1. Configure the devices for telemetry data. On each device, the following configuration is required. The device needs to be set to enhanced-ip mode, which might require a full reboot.

   > **NOTE:** If you are configuring for NorthStar integration with HealthBot, use default remote-port 4000 and set the remote-address to the HealthBot server IP address.

```
set chassis network-services enhanced-ip
set services analytics streaming-server ns remote-address 192.168.10.100
set services analytics streaming-server ns remote-port 3000
set services analytics export-profile ns local-address 11.0.0.10
set services analytics export-profile ns reporting-rate 2
set services analytics export-profile ns format gpb
set services analytics export-profile ns transport udp
set services analytics sensor ifd server-name ns
set services analytics sensor ifd export-name ns
set services analytics sensor ifd resource /junos/system/linecard/interface/
set services analytics sensor ifl server-name ns
set services analytics sensor ifl export-name ns
set services analytics sensor ifl resource
/junos/system/linecard/interface/logical/usage/
set services analytics sensor lsp server-name ns
set services analytics sensor lsp export-name ns
set services analytics sensor lsp resource
/junos/services/label-switched-path/usage/
set services analytics sensor sr-te-color server-name ns
```

```
set services analytics sensor sr-te-color export-name ns
set services analytics sensor sr-te-color resource
/junos/services/segment-routing/traffic-engineering/ingress/usage/
set services analytics sensor sid server-name ns
set services analytics sensor sid export-name ns
set services analytics sensor sid resource
/junos/services/segment-routing/sid/usage/
set services analytics sensor sr-te-tunnels server-name ns
set services analytics sensor sr-te-tunnels export-name ns
set services analytics sensor sr-te-tunnels resource
/junos/services/segment-routing/traffic-engineering/tunnel/ingress/usage/
set protocols mpls sensor-based-stats
set protocols source-packet-routing telemetry statistics
```

In this configuration, the remote address is the IP address of the collector (reachable though a data port). The local address should be the loopback, or router-id, whichever is configured on the device profile to identify the device.

2. NorthStar supports bandwidth sizing and container LSPs for SR-TE LSPs. Junos OS release 19.2R1 or later is required for this functionality. There is additional configuration required on the router to enable collection of segment routing data. For example:

```
set groups jvision services analytics sensor sr-te-tunnels server-name ns
set groups jvision services analytics sensor sr-te-tunnels export-name ns
set groups jvision services analytics sensor sr-te-tunnels resource
/junos/services/segment-routing/traffic-engineering/tunnel/ingress/usage/
```

3. Real-time performance monitoring (RPM) enables you to monitor network performance in real time and to assess and analyze network efficiency. To achieve this, RPM exchanges a set of probes with other IP hosts in the network for monitoring and network tracking purposes.

   Configure RPM probes to measure the interface delays. The following example shows the configuration of probes out of interface ge-0/1/1.0 to the remote address 10.101.105.2. This remote address should be the IP address of the node at the other end of the link.

   NOTE: The test name must match the interface being measured (test ge-0/1/1.0, in this example).

```
set services rpm probe northstar-ifl test ge-0/1/1.0 target address 10.101.105.2
set services rpm probe northstar-ifl test ge-0/1/1.0 probe-count 11
```

```
set services rpm probe northstar-ifl test ge-0/1/1.0 probe-interval 5
set services rpm probe northstar-ifl test ge-0/1/1.0 test-interval 60
set services rpm probe northstar-ifl test ge-0/1/1.0 source-address 10.101.105.1
set services rpm probe northstar-ifl test ge-0/1/1.0 moving-average-size 12
set services rpm probe northstar-ifl test ge-0/1/1.0 traps test-completion
set services rpm probe northstar-ifl test ge-0/1/1.0 hardware-timestamp
```

4. Configure the syslog host using the following commands:

   NOTE: IMPORTANT: To prevent the population of duplicate delay data to the PCS, do not perform this step if you are configuring for integration with HealthBot.

```
set system syslog host 192.168.18.1 daemon info
set system syslog host 192.168.18.1 port 1514
set system syslog host 192.168.18.1 match-strings RPM_TEST_RESULTS
```

5. RPM probes do not yet generate telemetry data, but you can use the rpm-log.slax script to push the results. The script is located in **/opt/northstar/data/logstash/utils/junoscripts**. Install the script to **/var/db/scripts/event** on the router. Enable the script by adding it to the event/scripts configuration:

   NOTE: IMPORTANT: To prevent the population of duplicate delay data to the PCS, do not perform this step if you are configuring for integration with HealthBot.

```
set event-options event-script file rpm-log.slax
```

   The text of the rpm-log.slax script follows. Comments are enclosed in /* */.

```
version 1.2;
ns junos = "http://xml.juniper.net/junos/*/junos";
ns xnm = "http://xml.juniper.net/xnm/1.1/xnm";
ns jcs = "http://xml.juniper.net/junos/commit-scripts/1.0"; import "../import
/junos.xsl";
param $test-owner = event-script-input/trigger-event/attribute-list/attribute
[name=="test-owner"]/value;
param $test-name = event-script-input/trigger-event/attribute-list/attribute
[name=="test-name"]/value;
```

```
param $delay-value;
var $arguments = {
  <argument> {
      <name> “test-name”;
      <description> “Name of the RPM test”;
  }
  <argument> {
     <name> “test-owner”;
     <description> “ Name of the RPM probe owner”;
  }
  <argument> {
     <name> “delay-value”;
     <description> “Delay value to send out, used to generate fake
data”;
  }
}
/* Add embedded event policy to trigger the script */
var $event-definition = {
    <event-options> {
      <policy> {
        <name> “rpm-log”;
        <events> “ping_test_completed”;
        <then> {
          <event-script> {
            <name> “rpm-log.slax”;
            <output-format> “xml”;
          }
        }
      }
    }
}
match / {
  <op-script-results> {
        /* Load Probe results */
        var $get-probe-resultsrpc = <get-probe-results> { <owner> $test-
owner; <test> $test-name;}
        var $probe-results = jcs:invoke($get-probe-resultsrpc);
        /* Extract data of interest */
        var $target-address = $probe-results/probe-test-results/target-address;
        var $probe-type = $probe-results/probe-test-results/probe-type;
        var $loss-percentage = format-number(number($probe-results/probe-test-
results/probe-test-moving-results/probe-test-generic-results/loss-percentage),
'#.##');
       var $jitter = format-number(number($probe-results/probe-test-results/probe-
```

```
test-moving-results/probe-test-generic-results/probe-test-rtt/probe-summary-results/
jitter-delay) div 1000, '#.###');
        var $avg-delay = {
          if ($delay-value) {
                number($delay-value);
          } else {
                expr
format-number(number($probe-results/probe-test-results/probe-test-
moving-results/probe-test-generic-results/probe-test-egress/probe-summary-results/avg-
delay) div 1000, '#.##');
          }
        }
        var $min-delay = {
          if ($delay-value) {
                number($delay-value);
          } else {
                expr
format-number(number($probe-results/probe-test-results/probe-test-
moving-results/probe-test-generic-results/probe-test-egress/probe-summary-results/min-
delay) div 1000, '#.##');
          }
        }
        var $max-delay = {
          if ($delay-value) {
                number($delay-value);
          } else {
                expr
format-number(number($probe-results/probe-test-results/probe-test-
moving-results/probe-test-generic-results/probe-test-egress/probe-summary-results/max-
delay) div 1000, '#.##');
          }
        }

        expr jcs:syslog("daemon.info","RPM_TEST_RESULTS:
","test-owner=",$test-owner,"
test-name=",$test-name," loss=",$loss-percentage," min-rtt=",$min-delay,"
max-rtt=",
$max-delay," avgerage-rtt=",$avg-delay," jitter=",$jitter);
  }
}
```

RELATED DOCUMENTATION

Collector Worker Installation Customization

When you install the NorthStar application, a default number of collector workers are installed on the NorthStar server, depending on the number of cores in the CPU. This is regulated in order to optimize server resources, but you can change the number by using a provided script. Each installed worker starts a number of celery processes equal to the number of cores in the CPU plus one.

Table 15 on page 150 describes the default number of workers installed according to the number of cores in the CPU.

Table 15: Default Worker Groups and Processes by Number of CPU Cores

CPU Cores	Worker Groups Installed	Total Worker Processes	Minimum RAM Required
1-4	4	8-20 (CPUs +1) x 4 = 20	1 GB
5-8	2	12-18 (CPUs +1) x 2 = 18	1 GB
16	1	17 (CPUs +1) x 1 = 17	1 GB
32	1	33 (CPUs +1) x 1 = 33	2 GB

Use the config_celery_workers.sh script to change the number of worker groups installed (post-initial installation). You might want to make a change if, for example:

- You upgrade your hardware with additional CPU cores and you want to increase the worker groups based on the new total number of cores.
- You want to manually determine the number of workers to be started rather than using the automatically-applied formula.

"NorthStar Controller System Requirements" on page 21 provides some guidance about memory requirements for various server uses and sizes.

NOTE: You can also use the config_celery_workers.sh script to change the number of secondary workers installed on a secondary collector server. See "Secondary Collector Installation for Distributed Data Collection" on page 151 for more information about distributed data collection.

To change the number of worker groups installed, launch the config_celery_workers.sh script:

```
/opt/northstar/snmp-collector/scripts/config_celery_workers.sh <option>
```

The available options are:

- -c

  This option automatically determines the number of cores and calculates the number of worker groups to add accordingly, per the formulas in Table 15 on page 150.

  For example:

  ```
  /opt/northstar/snmp-collector/scripts/config_celery_workers.sh -c
  ```

- -w *worker-groups*

  This option adds the specified number of worker groups. The following example starts six worker groups:

  ```
  /opt/northstar/snmp-collector/scripts/config_celery_workers.sh -w 6
  ```

RELATED DOCUMENTATION

Secondary Collector Installation for Distributed Data Collection | 151

Secondary Collector Installation for Distributed Data Collection

When you install NorthStar Controller, a primary collector is installed, for use by Netconf and SNMP collection. You can improve performance of the collection tasks by also installing secondary collector workers to distribute the work. Each secondary collector worker starts a number of worker processes

which is equal to the number of cores in the CPU plus one. You can create as many secondary collector servers as you wish to help with collection tasks. The collector manages all of the workers automatically.

Secondary collectors must be installed in a separate server from the NorthStar Controller. **You cannot install secondary collectors together with the NorthStar application in the same server.**

To install secondary collectors, follow this procedure:

1. On the secondary collector server, run the following:

   rpm -Uvh *rpm-filename*

2. On the secondary collector server, run the collector.sh script:

   ```
   [root@ns-sec-coll]# cd /opt/northstar/northstar_bundle_x.x.x/
   [root@ns-sec-coll northstar]# ./collector.sh install
   ```

   The script prompts you for the NorthStar application IP address, login, and password. If the NorthStar application is in HA mode, you need to provide the VIP address of the NorthStar application. The IP address is used by the secondary collectors to communicate with the primary collector:

   ```
   Config file /opt/northstar/data/northstar.cfg does not exist copying it from
   Northstar APP server, Please enter below info:
   ------------------------------------------------------------------------------------------------------------------------
   Please enter application server IP address or host name: 10.49.166.211
   Please enter Admin Web UI username: admin
   Please enter Admin Web UI password: <not displayed>
   retrieving config file from application server...

   Saving to /opt/northstar/data/northstar.cfg
   Secondary collector installed....
   collector: added process group
   collector:worker1: stopped
   collector:worker3: stopped
   collector:worker2: stopped
   collector:worker4: stopped
   collector:worker1: started
   collector:worker3: started
   collector:worker2: started
   collector:worker4: started
   ```

3. Run the following command to confirm the secondary collector (worker) processes are running:

```
[root@ns-sec-coll]# supervisorctl status
collector:worker1                RUNNING   pid 15574, uptime 0:01:28
collector:worker2                RUNNING   pid 15576, uptime 0:01:28
collector:worker3                RUNNING   pid 15575, uptime 0:01:28
collector:worker4                RUNNING   pid 15577, uptime 0:01:28
```

4. Optionally, use the config_celery_workers.sh script to change the number of workers that are installed.

   The collector.sh script installs a default number of workers, depending on the number of CPU cores on the server. After the initial installation, you can change the number of workers installed using the config_celery_workers.sh script. Table 16 on page 153 shows the default workers installed, the number of total celery processes started, and the amount of RAM required.

   Table 16: Default Worker Groups and Processes by Number of CPU Cores

CPU Cores	Worker Groups Installed	Total Worker Processes	Minimum RAM Required
1-4	4	8-20 (CPUs +1) x 4 = 20	1 GB
5-8	2	12-18 (CPUs +1) x 2 = 18	1 GB
16	1	17 (CPUs +1) x 1 = 17	1 GB
32	1	33 (CPUs +1) x 1 = 33	2 GB

   To change the number of workers, run the config_celery_workers.sh script:

```
[root@pcs02-q-pod08
~]#/opt/northstar/snmp-collector/scripts/config_celery_workers.sh <option>
```

   Use the **-w *worker-groups*** option to add a specified number of worker groups. Since this installation is on a server dedicated to providing distributed data collection, you can increase the number of workers installed up to the server storage capacity to improve performance. The following example starts six worker groups:

```
/opt/northstar/snmp-collector/scripts/config_celery_workers.sh -w 6
```

RELATED DOCUMENTATION

Collector Worker Installation Customization | 150

Configuring a NorthStar Cluster for High Availability

IN THIS SECTION

- Before You Begin | 154
- Set Up SSH Keys | 156
- Access the HA Setup Main Menu | 157
- Configure the Three Default Nodes and Their Interfaces | 161
- Configure the JunosVM for Each Node | 163
- (Optional) Add More Nodes to the Cluster | 164
- Configure Cluster Settings | 166
- Test and Deploy the HA Configuration | 167
- Replace a Failed Node if Necessary | 172
- Configure Fast Failure Detection Between JunosVM and PCC | 174

Before You Begin

Configuring a NorthStar application cluster for high availability (HA) is an optional process. This topic describes the steps for configuring, testing, deploying, and maintaining an HA cluster. If you are not planning to use the NorthStar application HA feature, you can skip this topic.

NOTE: See *High Availability Overview* in the *NorthStar Controller User Guide* for overview information about HA. For information about analytics HA, see "Installing Data Collectors for Analytics" on page 112.

- Download the NorthStar Controller and install it on each server that will be part of the cluster. Each server must be completely enabled as a single node implementation before it can become part of a cluster.

This includes:

- Creating passwords
- License verification steps
- Connecting to the network for various protocol establishments such as PCEP or BGP-LS

> **NOTE:** All of the servers must be configured with the same database and RabbitMQ passwords.

- All server time must be synchronized by NTP using the following procedure:

  1. Install NTP.

     ```
     yum -y install ntp
     ```

  2. Specify the preferred NTP server in ntp.conf.

  3. Verify the configuration.

     ```
     ntpq -p
     ```

     > **NOTE:** All cluster nodes must have the same time zone and system time settings. This is important to prevent inconsistencies in the database storage of SNMP and LDP task collection delta values.

- Run the net_setup.py utility to complete the required elements of the host and JunosVM configurations. Keep that configuration information available.

  > **NOTE:** If you are using an OpenStack environment, you will have one JunosVM that corresponds to each NorthStar Controller VM.

- Know the virtual IPv4 address you want to use for Java Planner client and web UI access to NorthStar Controller (required). This VIP address is configured for the router-facing network for single interface configurations, and for the user-facing network for dual interface configurations. This address is always associated with the active node, even if failover causes the active node to change.
- A virtual IP (VIP) is required when setting up a NorthStar cluster. Ensure that all servers that will be in the cluster are part of the same subnet as the VIP.
- Decide on the priority that each node will have for active node candidacy upon failover. The default value for all nodes is 0, the highest priority. If you want all nodes to have equal priority for becoming

the active node, you can just accept the default value for all nodes. If you want to rank the nodes in terms of their active node candidacy, you can change the priority values accordingly—the lower the number, the higher the priority.

Set Up SSH Keys

Set up SSH keys between the selected node and each of the other nodes in the cluster, and each JunosVM.

1. Obtain the public SSH key from one of the nodes. You will need the ssh-rsa string from the output:

```
[root@rw01-ns ~]# cat /root/.ssh/id_rsa.pub
```

2. Copy the public SSH key from each node to each of the other nodes, from each machine.

   From node 1:

```
[root@rw01-ns northstar_bundle_x.x.x]# ssh-copy-id root@node-2-ip

[root@rw01-ns northstar_bundle_x.x.x]# ssh-copy-id root@node-3-ip
```

   From node 2:

```
[root@rw02-ns northstar_bundle_x.x.x]# ssh-copy-id root@node-1-ip

[root@rw02-ns northstar_bundle_x.x.x]# ssh-copy-id root@node-3-ip
```

   From node 3:

```
[root@rw03-ns northstar_bundle_x.x.x]# ssh-copy-id root@node-1-ip

[root@rw03-ns northstar_bundle_x.x.x]# ssh-copy-id root@node-2-ip
```

3. Copy the public SSH key from the selected node to each remote JunosVM (JunosVM hosted on each other node). To do this, log in to each of the other nodes and connect to its JunosVM.

```
[root@rw02-ns ~]# ssh northstar@JunosVM-ip
[root@rw02-ns ~]# configure
[root@rw02-ns ~]# set system login user northstar authentication ssh-rsa
```

```
replacement-string
[root@rw02-ns ~]# commit
```

```
[root@rw03-ns ~]# ssh northstar@JunosVM-ip
[root@rw03-ns ~]# configure
[root@rw03-ns ~]# set system login user northstar authentication ssh-rsa
replacement-string
[root@rw03-ns ~]# commit
```

Access the HA Setup Main Menu

The /opt/northstar/utils/net_setup.py utility (the same utility you use to configure NorthStar Controller) includes an option for configuring high availability (HA) for a node cluster. Run the /opt/northstar/utils/net_setup.py utility on one of the servers in the cluster to set up the entire cluster.

1. Select one of the nodes in the cluster on which to run the setup utility to configure all the nodes in the cluster.

2. On the selected node, launch the NorthStar setup utility to display the NorthStar Controller Setup Main Menu.

   [root@northstar]# **/opt/northstar/utils/net_setup.py**

```
Main Menu:
    ..........................................
    A.) Host Setting
    ..........................................
    B.) JunosVM Setting
    ..........................................
    C.) Check Network Setting
    ..........................................
    D.) Maintenance & Troubleshooting
    ..........................................
    E.) HA Setting
    ..........................................
    F.) Collect Trace/Log
    ..........................................
    G.) Analytics Data Collector Setting
      (External standalone/cluster analytics server)
    ..........................................
```

```
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
```

3. Type **E** and press **Enter** to display the HA Setup main menu.

   Figure 26 on page 159 shows the top portion of the HA Setup main menu in which the current configuration is listed. It includes the five supported interfaces for each node, the VIP addresses, and the ping interval and timeout values. In this figure, only the first of the nodes is included, but you would see the corresponding information for all three of the nodes in the cluster configuration template. HA functionality requires an odd number of nodes in a cluster, and a minimum of three.

Figure 26: HA Setup Main Menu, Top Portion

```
HA Setup:
   ------------------------------------------------------------
   Node #1
      Hostname                          :
      Site Name                         : site1
      Priority                          : 0
      Cluster Communication Interface   : external0
      Cluster Communication IP          :
        Interfaces
          Interface #1
            Name                        : external0
            IPv4                        :
            Switchover                  : yes
          Interface #2
            Name                        : mgmt0
            IPv4                        :
            Switchover                  : yes
          Interface #3
            Name                        :
            IPv4                        :
            Switchover                  : yes
          Interface #4
            Name                        :
            IPv4                        :
            Switchover                  : yes

...
  ------------------------------------------------------------
   JunosVM #1
       Hostname                         :
       IPv4                             :
   JunosVM #2
       Hostname                         :
       IPv4                             :
   JunosVM #3
       Hostname                         :
       IPv4                             :
   ------------------------------------------------------------
   VIP Interfaces
       VIP Interface #1                 :
       VIP Interface #2                 :
       VIP Interface #3                 :
       VIP Interface #4                 :
       VIP Interface #5                 :

   Ping Interval(s)                     : 10
   Ping Timeout(s)                      : 30
```

NOTE: If you are configuring a cluster for the first time, the IP addresses are blank and other fields contain default values. If you are modifying an existing configuration, the current cluster configuration is displayed, and you have the opportunity to change the values.

NOTE: If the servers are located in geodiverse locations, you can use Site Name to indicate which servers are in the same or different geographical locations.

Figure 27 on page 160 shows the lower portion of the HA Setup main menu. To complete the configuration, you type the number or letter of an option and provide the requested information. After each option is complete, you are returned to the HA Setup main menu so you can select another option.

Figure 27: HA Setup Main Menu, Lower Portion

```
.....
1.) Add node
2.) Remove node
3.) Add JunosVM
4.) Remove JunosVM
5.) Modify Node
6.) Modify Node interface
7.) Delete Node interface data
8.) Modify JunosVM
9.) Modify VIP interfaces
A.) Delete VIP interface data
B.) Modify ping interval
C.) Modify ping timeout
.....
D.) Setup Mode (single/cluster)   : single
E.) PCEP Session (physical_ip/vip): physical_ip
.....
F.) Test HA Connectivity for cluster communication interface only
G.) Test HA Connectivity for all interfaces
H.) Prepare and Deploy HA configs
I.) Copy HA setting to other nodes
J.) Add a new node to existing cluster
K.) Check cluster status
.....

Please select a number to modify.
[<CR>=return to main menu]:
```

Configure the Three Default Nodes and Their Interfaces

The HA Setup main menu initially offers three nodes for configuration because a cluster must have a minimum of three nodes. You can add more nodes as needed.

For each node, the menu offers five interfaces. Configure as many of those as you need.

1. Type **5** and press **Enter** to modify the first node.

2. When prompted, enter the number of the node to be modified, the hostname, the site name, and the priority, pressing **Enter** between entries.

   > **NOTE:** The NorthStar Controller uses **root** as a username to access other nodes.

   The default priority is **0**. You can just press **Enter** to accept the default or you can type a new value.

   For each interface, enter the interface name, IPv4 address, and switchover (yes/no), pressing **Enter** between entries.

   > **NOTE:** For each node, interface #1 is reserved for the cluster communication interface which is used to facilitate communication between nodes. For this interface, it is required that switchover be set to Yes, and you cannot change that parameter.

   When finished, you are returned to the HA Setup main menu.

   The following example configures Node #1 and two of its available five interfaces.

```
Please select a number to modify.
[<CR>=return to main menu]
5
Node ID : 1

    HA Setup:
       ..........................................................
       Node #1
       Hostname                        :
       Site Name                       : site1
       Priority                        : 0
       Cluster Communication Interface : external0
       Cluster Communication IP        :
          Interfaces
```

```
            Interface #1
               Name                    : external0
               IPv4                    :
               Switchover              : yes
            Interface #2
               Name                    : mgmt0
               IPv4                    :
               Switchover              : yes
            Interface #3
               Name                    :
               IPv4                    :
               Switchover              : yes
            Interface #4
               Name                    :
               IPv4                    :
               Switchover              : yes
            Interface #5
               Name                    :
               IPv4                    :
               Switchover              : yes

current node 1 Node hostname (without domain name) :
new node 1 Node hostname (without domain name) : node-1

current node 1 Site Name : site1
new node 1 Site Name : site1

current node 1 Node priority : 0
new node 1 Node priority : 10

current node 1 Node cluster communication interface : external0
new node 1 Node cluster communication interface : external0

current node 1 Node cluster communication IPv4 address :
new node 1 Node cluster communication IPv4 address : 10.25.153.6


current node 1 Node interface #2 name : mgmt0
new node 1 Node interface #2 name : external1

current node 1 Node interface #2 IPv4 address :
new node 1 Node interface #2 IPv4 address : 10.100.1.1

current node 1 Node interface #2 switchover (yes/no) : yes
```

```
new node 1 Node interface #2 switchover (yes/no) :

current node 1 Node interface #3 name :
new node 1 Node interface #3 name :

current node 1 Node interface #3 IPv4 address :
new node 1 Node interface #3 IPv4 address :

current node 1 Node interface #3 switchover (yes/no) : yes
new node 1 Node interface #3 switchover (yes/no) :

current node 1 Node interface #4 name :
new node 1 Node interface #4 name :

current node 1 Node interface #4 IPv4 address :
new node 1 Node interface #4 IPv4 address :

current node 1 Node interface #4 switchover (yes/no) : yes
new node 1 Node interface #4 switchover (yes/no) :

current node 1 Node interface #5 name :
new node 1 Node interface #5 name :

current node 1 Node interface #5 IPv4 address :
new node 1 Node interface #5 IPv4 address :

current node 1 Node interface #5 switchover (yes/no) : yes
new node 1 Node interface #5 switchover (yes/no) :
```

3. Type **5** and press **Enter** again to repeat the data entry for each of the other two nodes.

Configure the JunosVM for Each Node

To complete the node-specific setup, configure the JunosVM for each node in the cluster.

1. From the HA Setup main menu, type **8** and press **Enter** to modify the JunosVM for a node.

2. When prompted, enter the node number, the JunosVM hostname, and the JunosVM IPv4 address, pressing **Enter** between entries.

   Figure 28 on page 164 shows these JunosVM setup fields.

Figure 28: Node 1 JunosVM Setup Fields

```
Please select a number to modify.
[<CR>=return to main menu]:
8
Node ID : 1

current node 1 JunOSVM hostname :
new node 1 JunOSVM hostname : junosVM_node1

current node 1 JunosVM IPv4 address :
new node 1 JunosVM IPv4 address : 172.25.152.238
```

When finished, you are returned to the HA Setup main menu.

3. Type **8** and press **Enter** again to repeat the JunosVM data entry for each of the other two nodes.

(Optional) Add More Nodes to the Cluster

If you want to add additional nodes, type **1** and press **Enter**. Then configure the node and the node's JunosVM using the same procedures previously described. Repeat the procedures for each additional node.

NOTE: HA functionality requires an odd number of nodes and a minimum of three nodes per cluster.

The following example shows adding an additional node, node #4, with two interfaces.

```
Please select a number to modify.
[<CR>=return to main menu]:
1
New Node ID : 4

current node 4 Node hostname (without domain name) :
new node 4 Node hostname (without domain name) : node-4
```

```
current node 4 Site Name : site1
new node 4 Site Name : site1

current node 4 Node priority : 0
new node 4 Node priority : 40

current node 4 Node cluster communication interface : external0
new node 4 Node cluster communication interface : external0

current node 4 Node cluster communication IPv4 address :
new node 4 Node cluster communication IPv4 address : 10.25.153.12


current node 4 Node interface #2 name : mgmt0
new node 4 Node interface #2 name : external1

current node 4 Node interface #2 IPv4 address :
new node 4 Node interface #2 IPv4 address : 10.100.1.7

current node 4 Node interface #2 switchover (yes/no) : yes
new node 4 Node interface #2 switchover (yes/no) :

current node 4 Node interface #3 name :
new node 4 Node interface #3 name :

current node 4 Node interface #3 IPv4 address :
new node 4 Node interface #3 IPv4 address :

current node 4 Node interface #3 switchover (yes/no) : yes
new node 4 Node interface #3 switchover (yes/no) :

current node 4 Node interface #4 name :
new node 4 Node interface #4 name :

current node 4 Node interface #4 IPv4 address :
new node 4 Node interface #4 IPv4 address :

current node 4 Node interface #4 switchover (yes/no) : yes
new node 4 Node interface #4 switchover (yes/no) :

current node 4 Node interface #5 name :
new node 4 Node interface #5 name :

current node 4 Node interface #5 IPv4 address :
```

```
new node 4 Node interface #5 IPv4 address :

current node 4 Node interface #5 switchover (yes/no) : yes
new node 4 Node interface #5 switchover (yes/no) :
```

The following example shows configuring the JunosVM that corresponds to node #4.

```
Please select a number to modify.
[<CR>=return to main menu]
3
New JunosVM ID : 4
current junosvm 4 JunOSVM hostname :
new junosvm 4 JunOSVM hostname : junosvm-4

current junosvm 4 JunOSVM IPv4 address :
new junosvm 4 JunOSVM IPv4 address : 10.25.153.13
```

Configure Cluster Settings

The remaining settings apply to the cluster as a whole.

1. From the HA Setup main menu, type **9** and press **Enter** to configure the VIP address for the external (router-facing) network. This is the virtual IP address that is always associated with the active node, even if failover causes the active node to change. The VIP is required, even if you are configuring a separate user-facing network interface. If you have upgraded from an earlier NorthStar release in which you did not have VIP for external0, you must now configure it.

   NOTE: Make a note of this IP address. If failover occurs while you are working in the NorthStar Planner UI, the client is disconnected and you must re-launch it using this VIP address. For the NorthStar Controller web UI, you would be disconnected and would need to log back in.

   The following example shows configuring the VIP address for the external network.

```
Please select a number to modify.
[<CR>=return to main menu]
9
current VIP interface #1 IPv4 address :
new VIP interface #1 IPv4 address : 10.25.153.100
```

```
current VIP interface #2 IPv4 address :
new VIP interface #2 IPv4 address : 10.100.1.1

current VIP interface #3 IPv4 address :
new VIP interface #3 IPv4 address :

current VIP interface #4 IPv4 address :
new VIP interface #4 IPv4 address :

current VIP interface #5 IPv4 address :
new VIP interface #5 IPv4 address :
```

2. Type **9** and press **Enter** to configure the VIP address for the user-facing network for dual interface configurations. If you do not configure this IP address, the router-facing VIP address also functions as the user-facing VIP address.

3. Type **D** and press **Enter** to configure the setup mode as **cluster** (local cluster).

4. Type **E** and press **Enter** to configure the PCEP session. The default is **physical_ip**. If you are using the cluster VIP for your PCEP session, configure the PCEP session as **vip**.

> **NOTE:** All of your PCC sessions must use either physical IP or VIP (no mixing and matching), and that must also be reflected in the PCEP configuration on the router.

Test and Deploy the HA Configuration

You can test and deploy the HA configuration from within the HA Setup main menu.

1. Type **G** to test the HA connectivity for all the interfaces. You must verify that all interfaces are up before you deploy the HA cluster.

2. Type **H** and press **Enter** to launch a script that connects to and deploys all the servers and all the JunosVMs in the cluster. The process takes approximately 15 minutes, after which the display is returned to the HA Setup menu. You can view the log of the progress at /opt/northstar/logs/net_setup.log.

NOTE: If the execution has not completed within 30 minutes, a process might be stuck. You can sometimes see this by examining the log at /opt/northstar/logs/net_setup.log. You can press **Ctrl-C** to cancel the script, and then restart it.

3. To check if the election process has completed, examine the processes running on each node by logging into the node and executing the **supervisorctl status** script.

```
[root@node-1]# supervisorctl status
```

For the active node, you should see all processes listed as RUNNING as shown here.

NOTE: The actual list of processes depends on the version of NorthStar and your deployment setup.

```
[root@node-1 ~]# supervisorctl status
collector:es_publisher           RUNNING   pid 2557, uptime 0:02:18
collector:task_scheduler         RUNNING   pid 2558, uptime 0:02:18
collector:worker1                RUNNING   pid 404, uptime 0:07:00
collector:worker2                RUNNING   pid 406, uptime 0:07:00
collector:worker3                RUNNING   pid 405, uptime 0:07:00
collector:worker4                RUNNING   pid 407, uptime 0:07:00
infra:cassandra                  RUNNING   pid 402, uptime 0:07:01
infra:ha_agent                   RUNNING   pid 1437, uptime 0:05:44
infra:healthmonitor              RUNNING   pid 1806, uptime 0:04:26
infra:license_monitor            RUNNING   pid 399, uptime 0:07:01
infra:prunedb                    RUNNING   pid 395, uptime 0:07:01
infra:rabbitmq                   RUNNING   pid 397, uptime 0:07:01
infra:redis_server               RUNNING   pid 401, uptime 0:07:01
infra:web                        RUNNING   pid 2556, uptime 0:02:18
infra:zookeeper                  RUNNING   pid 396, uptime 0:07:01
listener1:listener1_00           RUNNING   pid 1902, uptime 0:04:15
netconf:netconfd                 RUNNING   pid 2555, uptime 0:02:18
northstar:mladapter              RUNNING   pid 2551, uptime 0:02:18
northstar:npat                   RUNNING   pid 2552, uptime 0:02:18
northstar:pceserver              RUNNING   pid 1755, uptime 0:04:29
northstar:scheduler              RUNNING   pid 2553, uptime 0:02:18
northstar:toposerver             RUNNING   pid 2554, uptime 0:02:18
northstar_pcs:PCServer           RUNNING   pid 2549, uptime 0:02:18
```

```
northstar_pcs:PCViewer           RUNNING   pid 2548, uptime 0:02:18
northstar_pcs:configServer       RUNNING   pid 2550, uptime 0:02:18
```

For a standby node, processes beginning with “northstar”, “northstar_pcs”, and “netconf” should be listed as STOPPED. Also, if you have analytics installed, some of the processes beginning with “collector” are STOPPED. Other processes, including those needed to preserve connectivity, remain RUNNING. An example is shown here.

> **NOTE:** This is just an example; the actual list of processes depends on the version of NorthStar, your deployment setup, and the optional features you have installed.

`[root@node-1 ~]#` **supervisorctl status**

```
collector:es_publisher           STOPPED   Apr 16 11:53 AM
collector:task_scheduler         STOPPED   Apr 16 11:53 AM
collector:worker1                RUNNING   pid 22366, uptime 6 days, 22:33:52
collector:worker2                RUNNING   pid 22401, uptime 6 days, 22:33:39
collector:worker3                RUNNING   pid 22433, uptime 6 days, 22:33:26
collector:worker4                RUNNING   pid 22465, uptime 6 days, 22:33:14
infra:cassandra                  RUNNING   pid 19461, uptime 6 days, 22:44:17
infra:ha_agent                   RUNNING   pid 23184, uptime 6 days, 22:29:33
infra:healthmonitor              RUNNING   pid 23453, uptime 6 days, 22:28:27
infra:license_monitor            RUNNING   pid 15796, uptime 6 days, 22:53:12
infra:prunedb                    RUNNING   pid 15791, uptime 6 days, 22:53:12
infra:rabbitmq                   RUNNING   pid 19066, uptime 6 days, 22:44:28
infra:redis_server               RUNNING   pid 15798, uptime 6 days, 22:53:11
infra:web                        RUNNING   pid 18343, uptime 6 days, 20:20:55
infra:zookeeper                  RUNNING   pid 21101, uptime 6 days, 22:40:50
listener1:listener1_00           RUNNING   pid 23537, uptime 6 days, 22:28:17
netconf:netconfd                 STOPPED   Apr 16 11:53 AM
northstar:mladapter              STOPPED   Apr 16 11:48 AM
northstar:npat                   STOPPED   Apr 16 11:48 AM
northstar:pceserver              STOPPED   Apr 16 11:48 AM
northstar:scheduler              STOPPED   Apr 16 11:48 AM
northstar:toposerver             STOPPED   Apr 16 11:48 AM
northstar_pcs:PCServer           STOPPED   Apr 16 11:48 AM
northstar_pcs:PCViewer           STOPPED   Apr 16 11:48 AM
northstar_pcs:configServer       STOPPED   Apr 16 11:48 AM
```

4. Set the web UI admin password using either the web UI or net_setup.

- For the web UI method, use the external IP address that was provided to you when you installed the NorthStar application. Type that address into the address bar of your browser (for example, https://10.0.1.29:8443). A window is displayed requesting the confirmation code in your license file (the characters after S-NS-SDN=), and the password you wish to use. See Figure 29 on page 170.

Figure 29: Web UI Method for Setting the Web UI Password



- For the net_setup method, select **D** from the net_setup Main Menu (Maintenance & Troubleshooting), and then **3** from the Maintenance & Troubleshooting menu (Change UI Admin Password).

```
Main Menu:
    ........................................
    A.) Host Setting
    ........................................
    B.) JunosVM Setting
    ........................................
    C.) Check Network Setting
    ........................................
    D.) Maintenance & Troubleshooting
    ........................................
    E.) HA Setting
    ........................................
    F.) Collect Trace/Log
    ........................................
    G.) Data Collector Setting
```

```
    ........................................
    H.) Setup SSH Key for external JunosVM  setup
    ........................................
    I.) Internal Analytics Setting (HA)
    ........................................
    X.) Exit
    ........................................
Please select a letter to execute.
D


Maintenance & Troubleshooting:
   ..............................................
   1.) Backup JunosVM Configuration
   2.) Restore JunosVM Configuration
   3.) Change UI Admin Password
   4.) Change Database Password
   5.) Change MQ Password
   6.) Change Host Root Password
   7.) Change JunosVM root and northstar User Password
   8.) Initialize all credentials ( 3,4,5,6,7 included)
   ..............................................

Please select a number to modify.

[<CR>=return to main menu]:
3
```

Type Y to confirm you wish to change the UI Admin password, and enter the new password when prompted.

```
Change UI Admin Password
Are you sure you want to change the UI Admin password? (Y/N) y

Please enter new UI Admin password :
Please confirm new UI Admin password :
Changing UI Admin password ...
UI Admin password has been changed successfully
```

5. Once the web UI admin password has been set, return to the HA Setup menu (select **E** from the Main Menu). View cluster information and check the cluster status by typing **K**, and pressing **Enter**. In addition to providing general cluster information, this option launches the ns_check_cluster.sh script. You can also run this script outside of the setup utility by executing the following commands:

```
[root@northstar]# cd /opt/northstar/utils/
[root@northstar utils]# ./ns_check_cluster.sh
```

Replace a Failed Node if Necessary

On the HA Setup menu, options I and J can be used when physically replacing a failed node. They allow you to replace a node without having to redeploy the entire cluster which would wipe out all the data in the database.

CAUTION: While a node is being replaced in a three-node cluster, HA is not guaranteed.

1. Replace the physical node in the network and install NorthStar Controller on the replacement node.

2. Run the NorthStar setup utility to configure the replaced node with the necessary IP addresses. Be sure you duplicate the previous node setup, including:
   - IP address and hostname
   - Initialization of credentials
   - Licensing
   - Network connectivity
3. Go to one of the existing cluster member nodes (preferably the same node that was used to configure the HA cluster initially). Going forward, we will refer to this node as the *anchor node*.

4. Set up the SSH key from the anchor node to the replacement node and JunosVM.

   Copy the public SSH key from the anchor node to the replacement node, from the replacement node to the other cluster nodes, and from the other cluster nodes to the replacement node.

   NOTE: Remember that in your initial HA setup, you had to copy the public SSH key from each node to each of the other nodes, *from each machine*.

Copy the public SSH key from the anchor node to the replacement node's JunosVM (the JunosVM hosted on each of the other nodes). To do this, log in to each of the replacement nodes and connect to its JunosVM.

```
[root@node-1 ~]# ssh northstar@JunosVM-ip
[root@node-1 ~]# configure
[root@node-1 ~]# set system login user northstar authentication ssh-rsa
replacement-string
[root@node-1 ~]# commit
```

5. From the anchor node, remove the failed node from the Cassandra database. Run the command **nodetool removenode *host-id***. To check the status, run the command **nodetool status**.

   The following example shows removing the failed node with IP address 10.25.153.10.

```
[root@node-1 ~]# . /opt/northstar/northstar.env
[root@node-1 ~]# nodetool status
Datacenter: datacenter1
=======================
Status=Up/Down
|/ State=Normal/Leaving/Joining/Moving
--  Address        Load       Tokens       Owns    Host ID
           Rack
UN  10.25.153.6  5.06 MB    256          ?
507e572c-0320-4556-85ec-443eb160e9ba  rack1
UN  10.25.153.8  651.94 KB  256          ?
cd384965-cba3-438c-bf79-3eae86b96e62  rack1
DN  10.25.153.10  4.5 MB     256          ?
b985bc84-e55d-401f-83e8-5befde50fe96  rack1
[root@node-1 ~]# nodetool removenode b985bc84-e55d-401f-83e8-5befde50fe96
[root@node-1 ~]# nodetool status
Datacenter: datacenter1
=======================
Status=Up/Down
|/ State=Normal/Leaving/Joining/Moving
--  Address        Load       Tokens       Owns    Host ID
           Rack
UN  10.25.153.6  5.06 MB    256          ?
507e572c-0320-4556-85ec-443eb160e9ba  rack1
UN  10.25.153.8  639.61 KB  256          ?
cd384965-cba3-438c-bf79-3eae86b96e62  rack1
```

6. From the HA Setup menu on the anchor node, select option I to copy the HA configuration to the replacement node.

7. From the HA Setup menu on the anchor node, select option J to deploy the HA configuration, only on the replacement node.

Configure Fast Failure Detection Between JunosVM and PCC

You can use Bidirectional Forward Detection (BFD) in deploying the NorthStar application to provide faster failure detection as compared to BGP or IGP keepalive and hold timers. The BFD feature is supported in PCC and JunosVM.

To utilize this feature, configure **bfd-liveness-detection minimum-interval *milliseconds*** on the PCC, and mirror this configuration on the JunosVM. We recommend a value of 1000 ms or higher for each cluster node. Ultimately, the appropriate BFD value depends on your requirements and environment.

RELATED DOCUMENTATION

High Availability Overview (*NorthStar Controller User Guide*)

CHAPTER 6

Configuring Topology Acquisition and Connectivity Between the NorthStar Controller and the Path Computation Clients

Understanding Network Topology Acquisition on the NorthStar Controller | **176**

Configuring Topology Acquisition | **178**

Configuring PCEP on a PE Router (from the CLI) | **186**

Mapping a Path Computation Client PCEP IP Address | **190**

Understanding Network Topology Acquisition on the NorthStar Controller

After you use BGP-LS to establish BGP peering between the Junos VM and one or more routers in the backbone network, the NorthStar Controller acquires real-time topology changes, which are recorded in the traffic engineering database (TED). To compute optimal paths through the network, the NorthStar Controller requires a consolidated view of the network topology. This routing view of the network includes the nodes, links, and their attributes (metric, link utilization bandwidth, and so on) that comprise the network topology. Thus, any router CLI configuration changes to IGP metric, RSVP bandwidth, Priority/Hold values, and so on are instantly available from the NorthStar Controller UI topology view.

To provide a network view, the NorthStar Controller runs Junos OS in a virtual machine (JunosVM) that uses routing protocols to communicate with the network and dynamically learn the network topology. To provide real-time updates of the network topology, the JunosVM, which is based on a virtual Route Reflector (vRR), establishes a BGP-LS peering session with one or more routers from the existing MPLS TE backbone network. A router from the MPLS TE backbone advertises its traffic engineering database (TED) in BGP-LS. The JunosVM receives real-time BGP-LS updates and forwards this topology data into the Network Topology Abstractor Daemon (NTAD), which is a server daemon that runs in the JunosVM.

The NorthStar Controller stores network topology data in the following routing tables:

- lsdist.0—stores the network topology from TED
- lsdist.1—stores the network topology from IGP database

NTAD then forwards a copy of the updated topology information to the Path Computation Server (PCS), which displays the live topology update from the NorthStar Controller UI.

To provide a real-time topology update of the network, you can configure direct IS-IS or OSPF adjacency between the NorthStar Controller and an existing MPLS TE backbone router, but we recommend that you use BGP-LS rather than direct IGP adjacency or IGP adjacency over GRE.

NOTE:

The current BGP-LS implementation only considers TED information, and some IGP-specific attributes might not be forwarded during topology acquisition. The following IGP attributes are not forwarded:

- Link net mask.
- IGP metric (TED provides TE metric only).

In some cases, using IS-IS or OSPF adjacency instead of BGP-LS might produce stale data because IS-IS and OSPF have a database lifetime period that is not automatically cleared when the adjacency is down. In this case, NTAD will export all information in the OSPF or IS-IS database to the NorthStar Path Computation Server (PCS), so the NorthStar Controller might show incorrect topology.

Starting with NorthStar 4.3.0, BGP Monitoring Protocol (BMP) can be used as an alternative to NTAD. BMP runs automatically when you install NorthStar, but is not used unless you configure NorthStar and the JunosVM to make it the active topology acquisition method.

Unlike NTAD, BMP is a standard protocol which has the advantage of relieving the user of responsibility for version control to prevent mismatches. BMP also has the potential to be more compatible than NTAD with third-party routers. The third party router needs to support BGP-LS and BMP, and receive topology via BGP-LS. One disadvantage however, is that BMP only has access to the lsdist.0 routing table while NTAD accesses both lsdist.0 and lsdist.1.

With BMP, NorthStar can obtain the topology information from the BGP-LS data. When using BMP, only traffic engineering entries (from the TED) are available. NTAD also provides IGP entries if the router is peering with the IGP area. Topology data learned via IGP is not available through BMP.

See “Configuring Topology Acquisition” on page 178 for information about configuring both NTAD and BMP.

RELATED DOCUMENTATION

Configuring Topology Acquisition | 178

Configuring Topology Acquisition

IN THIS SECTION

- Overview | 178
- Before You Begin | 179
- Configuring Topology Acquisition Using BGP-LS | 181
- Configuring Topology Acquisition Using OSPF | 183
- Configuring Topology Acquisition Using IS-IS | 184

Overview

After you have successfully established a connection between the NorthStar Controller and the network, you can configure topology acquisition using Border Gateway Protocol Link State (BGP-LS) or an IGP (OSPF or IS-IS). For BGP-LS topology acquisition, you must configure both the NorthStar Controller and the PCC routers.

We recommend that you use BGP-LS instead of IGP adjacency because:

- The OSPF and IS-IS databases have lifetime timers. If the OSPF or IS-IS neighbor goes down, the corresponding database is not immediately removed, making it impossible for the NorthStar Controller to determine whether the topology is valid.
- Using BGP-LS minimizes the risk of making the JunosVM a transit router between AS areas if the GRE metric is not properly configured.
- Typically, the NorthStar Controller is located in a network operations center (NOC) data center, multihops away from the backbone and MPLS TE routers. This is easily accommodated by BGP-LS, but more difficult for IGP protocols because they would have to employ a tunneling mechanism such as GRE to establish adjacency.

NOTE: If BGP-LS is used, the JunosVM is configured to automatically accept any I-BGP session. However, you must verify that the JunosVM is correctly configured and that it has IP reachability to the peering router.

Before You Begin

Before you begin, complete the following tasks:

- Verify IP connectivity between a switch (or router) and the x86 appliance on which the NorthStar Controller software is installed.
- Configure the Network Topology Acquisition Daemon (NTAD). The NTAD forwards topology information from the network to the NorthStar application, and it must be running on the JunosVM.

  Use the following command to enable the NTAD:

  ```
  junosVM# set protocols topology-export
  ```

  Use the following command to verify that the NTAD is running; if the topology-export statement is missing, the match produces no results:

  ```
  junosVM> show system processes extensive | match ntad
   2462 root         1  96    0  6368K  1176K select   1:41  0.00% ntad
  ```

- Configure BGP Monitoring Protocol (BMP) if you have decided to use BMP as an alternative to NTAD. BMP must be enabled on both the NorthStar and JunosVM sides.

  1. Use a text editing tool such as vi to modify the /opt/northstar/data/northstar.cfg file, changing topology_src_protocol from 1 (which is NTAD) to 2 (which is BMP):

     ```
     vi /opt/northstar/data/northstar.cfg
     .
     .
     .
     topology_src_protocol=2
     ```

  2. Restart toposerver so the change takes effect:

     ```
     supervisorctl restart northstar:toposerver
     ```

  3. On the JunosVM, disable NTAD by deleting the **protocols topology-export** statement.

  4. On the Junos VM, under “firewall”, configure the firewall filter to permit BMP TCP segments from NorthStar toward the Junos VM.

NOTE: Be sure to insert “term bmp” before “term default-discard”.

```
  filter protect-re {
    term mgmt-intf {
        from {
            interface-set mgmt-intf;
        }
        then accept;
    }
   .
   .
   .
    term bmp {
        from {
           protocol tcp;
           port 10001;
        }
        then accept;
    }
    term default-discard {
        then {
            syslog;
            discard;
        }
    }
  }
```

5. On the Junos VM, under “routing options”, enable BMP:

```
    bmp {
        connection-mode active;
        monitor enable;
        station northstar {
            station-address station-address;
            station-port 10001;
        }
    }
}
```

Configuring Topology Acquisition Using BGP-LS

IN THIS SECTION

- Configure BGP-LS Topology Acquisition on the NorthStar Controller | 181
- Configure the Peering Router to Support Topology Acquisition | 182

Configure BGP-LS Topology Acquisition on the NorthStar Controller

To configure BGP-LS topology acquisition on the NorthStar Controller, perform the following configuration steps from the NorthStar JunosVM:

1. Initiate an SSH or a telnet session to the JunosVM external IP or management IP address.

2. Specify the autonomous system (AS) number for the node (BGP peer).

   ```
   [edit routing-options]
   user@northstar_junosvm# set autonomous-system AS_number
   ```

3. Specify the BGP group name and type for the node.

   ```
   [edit protocols bgp]
   user@northstar_junosvm# set group group_1 type internal
   ```

4. Specify a description for the BGP group for the node.

   ```
   [edit protocols bgp group group_1]
   user@northstar_junosvm# set description "NorthStar BGP-TE Peering"
   ```

5. Specify the address of the local end of a BGP session.

   This is the IP address for the JunosVM external IP address that is used to accept incoming connections to the JunosVM peer and to establish connections to the remote peer.

   ```
   [edit protocols bgp group group_1]
   user@northstar_junosvm# set local-address <junosVM IP address>
   ```

6. Enable the traffic engineering features for the BGP routing protocol.

```
[edit protocols bgp group group_1]
user@northstar_junosvm# set family traffic-engineering unicast
```

7. Specify the IP address for the neighbor router that connects with the NorthStar Controller.

```
[edit protocols bgp group group_1]
user@northstar_junosvm# set neighbor <router loopback IP address>
```

> **NOTE:** You can specify the router loopback address if it is reachable by the BGP peer on the other end. But for loopback to be reachable, usually some IGP has to be enabled between the NorthStar JunosVM and the peer on the other end.

Configure the Peering Router to Support Topology Acquisition

To enable the NorthStar Controller to discover the network, you must add the following configuration on each router that peers with the NorthStar Controller. The NorthStar JunosVM must peer with at least one router from each area (autonomous system).

To enable topology acquisition, initiate a telnet session to each PCC router and add the following configuration:

1. Configure a policy.

```
[edit policy-options]
user@PE1# set policy-statement TE term 1 from family traffic-engineering
user@PE1# set policy-statement TE term 1 then accept
```

> **NOTE:** This configuration is appropriate for both OSPF and IS-IS.

2. Import the routes into the traffic-engineering database.

```
[edit protocols mpls traffic-engineering database]
user@PE1# set import policy TE
```

3. Configure a BGP group by specifying the IP address of the router that peers with the NorthStar Controller as the local address (typically the loopback address) and the JunosVM external IP address as the neighbor.

```
[edit routing-options]
user@PE1# set autonomous-system AS Number

[edit protocols bgp group northstar]
user@PE1# set type internal
user@PE1# set description "NorthStar BGP-TE Peering"
user@PE1# set local-address <router-IP-address>
user@PE1# set family traffic-engineering unicast
user@PE1# set export TE
user@PE1# set neighbor <JunosVM IP-address>
```

Configuring Topology Acquisition Using OSPF

IN THIS SECTION

- Configure OSPF on the NorthStar Controller | 183
- Configure OSPF over GRE on the NorthStar Controller | 184

Configure OSPF on the NorthStar Controller

To configure OSPF on the NorthStar Controller:

1. Configure the policy.

```
[edit policy-options]
user@northstar_junosvm# set policy-statement TE term 1 from family traffic-engineering
user@northstar_junosvm# set policy-statement TE term 1 then accept
```

2. Populate the traffic engineering database.

```
[edit]
user@northstar_junosvm# set protocols mpls traffic-engineering database import policy TE
```

3. Configure OSPF.

```
[edit]
user@northstar_junosvm# set protocols ospf area area interface interface interface-type p2p
```

Configure OSPF over GRE on the NorthStar Controller

Once you have configured OSPF on the NorthStar Controller, you can take the following additional steps to configure OSPF over GRE:

1. Initiate an SSH or telnet session using the NorthStar JunosVM external IP address.

2. Configure the tunnel.

```
[edit interfaces]
user@northstar_junosvm# set gre unit 0 tunnel source local-physical-ip
user@northstar_junosvm# set gre unit 0 tunnel destination destination-ip
user@northstar_junosvm# set gre unit 0 family inet address tunnel-ip-addr
user@northstar_junosvm# set gre unit 0 family iso
user@northstar_junosvm# set gre unit 0 family mpls
```

3. Enable OSPF traffic engineering on the JunosVM and add the GRE interface to the OSPF configuration.

```
[edit protocols ospf]
user@northstar_junosvm# set traffic-engineering
user@northstar_junosvm# set area area interface gre.0 interface-type p2p
user@northstar_junosvm# set area area interface gre.0 metric 65530
```

Configuring Topology Acquisition Using IS-IS

IN THIS SECTION

- Configure IS-IS on the NorthStar Controller | 185
- Configure IS-IS over GRE on the NorthStar Controller | 185

Configure IS-IS on the NorthStar Controller

To configure IS-IS topology acquisition and enable IS-IS routing, perform the following steps on the NorthStar JunosVM:

1. Configure interfaces for IS-IS routing. For example:

```
[edit]
user@northstar_junosvm# set interfaces em0 unit 0 family inet address 172.16.16.2/24
user@northstar_junosvm# set interfaces em1 unit 0 family inet address 192.168.179.117/25
user@northstar_junosvm# set interfaces em0 unit 0 family inet address 172.16.16.2/24
user@northstar_junosvm# set interfaces em2 unit 0 family mpls
user@northstar_junosvm# set interfaces lo0 unit 0 family inet address 88.88.88.88/32 primary
user@northstar_junosvm# set routing-options static route 0.0.0.0/0 next-hop 192.168.179.126
user@northstar_junosvm# set routing-options autonomous-system 1001
```

2. Configure the policy.

```
[edit policy-options]
user@northstar_junosvm# set policy-statement TE term 1 from family traffic-engineering
user@northstar_junosvm# set policy-statement TE term 1 then accept
```

3. Populate the traffic engineering database.

```
[edit protocols]
user@northstar_junosvm# set mpls traffic-engineering database import policy TE
```

4. Configure IS-IS.

```
[edit protocols]
user@northstar_junosvm# set isis interface interface level level metric metric
user@northstar_junosvm# set isis interface interface point-to-point
```

Configure IS-IS over GRE on the NorthStar Controller

Once you have configured IS-IS on the NorthStar Controller, you can take the following additional steps to configure IS-IS over GRE:

1. Initiate an SSH or telnet session using the IP address for the NorthStar JunosVM external IP address.

2. Configure the tunnel.

```
[edit interfaces]
user@northstar_junosvm# set gre unit 0 tunnel source local-physical-ip
user@northstar_junosvm# set gre unit 0 tunnel destination destination
user@northstar_junosvm# set gre unit 0 family inet addresstunnel-ip-addr
user@northstar_junosvm# set gre unit 0 family iso
user@northstar_junosvm# set gre unit 0 family mpls
```

3. Add the GRE interface to the IS-IS configuration.

```
[edit protocols isis]
user@northstar_junosvm# set interface gre.0 level level metric 65530
user@northstar_junosvm# set interface gre.0 point-to-point
```

RELATED DOCUMENTATION

Configuring PCEP on a PE Router (from the CLI) | 186

Configuring PCEP on a PE Router (from the CLI)

A Path Computation Client (PCC) supports the configurations related to the Path Computation Element (PCE) and communicates with the NorthStar Controller, which by default is configured to accept a Path Computation Element Protocol (PCEP) connection from any source address. However, you must configure PCEP on each PE router to configure the router as a PCC and establish a connection between the PCC and the NorthStar Controller. A PCC initiates path computation requests, which are then executed by the NorthStar Controller.

Configuring a PE Router as a PCC

Each PCC in the network that the NorthStar Controller can access must be running a Junos OS release that is officially supported by the NorthStar Controller as designated in the *NorthStar Controller Release Notes* (jinstall 32 bit).

NOTE: For a PCEP connection, the PCC can connect to the NorthStar Controller using an in-band or out-of-band management network, provided that IP connectivity is established between the Path Computation Server (PCS) and the specified PCEP local address. In some cases, an additional static route might be required from the NorthStar Controller to reach the PCC, if the IP address is unreachable from the NorthStar Controller default gateway.

To configure a PE router as a PCC:

1. Enable external control of LSPs from the PCC router to the NorthStar Controller.

```
[edit protocols]
user@PE1# set mpls lsp-external-controller pccd
```

2. Specify the loopback address of the PCC router as the local address, for example:

```
[edit protocols]
user@PE1# set pcep pce northstar1 local-address 10.0.0.101
```

NOTE: As a best practice, the router ID is usually the loopback address, but it is not necessarily configured that way.

3. Specify the NorthStar Controller (**northstar1**) as the PCE that the PCC connects to, and specify the NorthStar Controller host external IP address as the destination address.

```
[edit protocols]
user@PE1# set pcep pce northstar1 destination-ipv4-address 10.99.99.1
```

4. Configure the destination port for the PCC router that connects to the NorthStar Controller (PCE server) using the TCP-based PCEP.

```
[edit protocols]
user@PE1# set pcep pce northstar1 destination-port 4189
```

5. Configure the PCE type.

```
[edit protocols]
user@PE1# set pcep pce northstar1 pce-type active
user@PE1# set pcep pce northstar1 pce-type stateful
```

6. Enable LSP provisioning.

```
[edit protocols]
user@PE1# set pcep pce northstar1 lsp-provisioning
```

7. To verify that PCEP has been configured on the router, open a telnet session to access the router, and run the following commands:

```
user@PE1> show configuration protocols mpls
```

Sample output:

```
lsp-external-controller pccd;
```

```
user@PE1> show configuration protocols pcep
```

Sample output:

```
pce northstar1 {
    local-address 10.0.0.101;
    destination-ipv4-address 10.99.99.1;
    destination-port 4189;
    pce-type active-stateful;
    lsp-provisioning;
}
```

Setting the PCC Version for Non-Juniper Devices

The PCEP protocol used by the Junos OS and NorthStar Controller supports *PCEP Extensions for establishing relationships between sets of LSPs* (draft-minei-pce-association-group-00) which defines the format and usage of AssociationObject, the optional object that makes association between LSP groups possible.

There are later versions of this draft that might be supported by other equipment vendors, which introduces the possibility of mismatch between AssociationObject formats. Such a mismatch could cause non-Juniper PCCs to discard LSP provisioning requests from NorthStar. To prevent this, we recommend that you configure all non-Juniper PCCs to omit AssociationObject altogether.

> **NOTE:** The result of omitting AssociationObject in non-Juniper PCC configuration is that NorthStar cannot associate groups of LSPs on those devices. For example, you would not be able to associate a primary LSP with secondary LSPs or a primary LSP with standby LSPs. This does not affect NorthStar's ability to create associations between LSP groups on Juniper PCCs.

Omitting AssociationObject on non-Juniper PCCs involves updating the **pcc_version.config** file on the NorthStar server and activating the update on the non-Juniper PCCs, using the following procedure:

1. Edit the **pcc_version.config** file on the NorthStar server to include the IP addresses of all non-Juniper PCCs. For each IP address, specify **3** as the PCC version. PCC version 3 omits AssociationObject.

   The **pcc_version.config** file is located in **/opt/pcs/db/config/**. The syntax of the configuration is **ver=***ip_address*:*pcc_version*.

   For example:

   ```
   [root@northstar]# cat /opt/pcs/db/config/pcc_version.config
   ver=192.0.2.100:3
   ver=192.0.2.200:3
   ver=192.0.2.215:3
   ```

2. At the PCEP CLI (**pcep_cli** command at the NorthStar Linux shell), execute the **set pcc-version** command to activate the change in PCC version.

   Executing this command restarts the PCEP sessions to the non-Juniper PCCs, applying the new PCC version 3. You can then provision LSPs from the NorthStar UI.

RELATED DOCUMENTATION

Mapping a Path Computation Client PCEP IP Address | 190

Mapping a Path Computation Client PCEP IP Address

A Path Computation Client (PCC) supports the configurations related to the Path Computation Element (PCE) and communicates with the NorthStar Controller, which by default is configured to accept a PCEP connection from any source address. Use the Device Profile window in the NorthStar Controller web UI to map a PCEP IP address for a PCC device.

A PCEP IP address (the local address of the PCC) is required when both of the following are true:

- PCEP is established through an IP address that is not supplied in the TED, such as an out-of-band IP address that uses an fxp0 management interface.
- There is no PCC-owned or PCC-delegated LSP configured on the router.

Before you begin, you must perform the configuration steps described in "Configuring PCEP on a PE Router (from the CLI)" on page 186 to configure the PE router as a PCC and establish a connection between the PCC and the NorthStar Controller.

To map a PCEP IP address for a PCC to the NorthStar Controller:

1. Log in to the NorthStar Controller web UI.

2. Navigate to **More Options**>**Administration**.

3. From the Administration menu at the far left of the screen, select **Device Profile**.

4. The Device List pane shows all the devices in the selected profile along with many of their properties, including the PCEP IP address, if they are already known. If they are not already known, the fields are blank.

   To add or change a PCEP IP address, select the device row and click the Modify button. Figure 30 on page 191 shows the Modify Device window.

Figure 30: Modify Device Window



5. In the PCEP IP field, enter the PCEP IP address for the PCC.

   You can find the PCEP IP address in the PCE statement stanza block. Either of the following two CLI **show** commands can help you locate it:

```
northstar@vmx101> show path-computation-client statistics

PCE jnc
-----------------------------------------
General
    PCE IP address           : 172.25.152.134
    Local IP address         : 172.25.157.129
    Priority                 : 0
    PCE status               : PCE_STATE_UP
    Session type             : PCE_TYPE_STATEFULACTIVE
    LSP provisioning allowed : On
    PCE-mastership           : main

Counters
    PCReqs              Total: 0           last 5min: 0           last hour: 0
```

```
    PCReps              Total: 0            last 5min: 0            last hour: 0

    PCRpts              Total: 204          last 5min: 0            last hour: 0

    PCUpdates           Total: 9            last 5min: 0            last hour: 0

    PCCreates           Total: 21           last 5min: 0            last hour: 0

Timers
    Local  Keepalive timer:   30 [s]  Dead timer:  120 [s]  LSP cleanup timer:
  0 [s]
    Remote Keepalive timer:   30 [s]  Dead timer:  120 [s]  LSP cleanup timer:
  0 [s]

Errors
    PCErr-recv
    PCErr-sent
    PCE-PCC-NTFS
    PCC-PCE-NTFS
```

```
northstar@vmx101> show configuration protocols pcep
pce jnc {
    local-address 172.25.157.129;
    destination-ipv4-address 172.25.152.134;
    destination-port 4189;
    pce-type active stateful;
    lsp-provisioning;
}
```

6. Click **Submit**.

7. Repeat this process for each PCC device for which you want to map a PCEP IP address.

RELATED DOCUMENTATION

Configuring PCEP on a PE Router (from the CLI) | 186

CHAPTER 7

Accessing the User Interface

NorthStar Application UI Overview | **194**

NorthStar Controller Web UI Overview | **198**

NorthStar Planner UI Overview | **203**

NorthStar Application UI Overview

NorthStar has two user interfaces (UIs):

- NorthStar Controller—web UI for working with a live network
- NorthStar Planner—for simulating the effect of various scenarios on the network, without affecting the live network. The NorthStar Planner is currently in transition from a desktop application to a web UI. Until the transition is complete, both the full-featured desktop application and the in-development web UI are available and documented separately.

UI Comparison

Table 17 on page 194 summarizes the major use cases for the NorthStar Controller and NorthStar Planner.

> **NOTE:** All user administration (adding, modifying, and deleting users) must be done from the NorthStar Controller web UI.

> **NOTE:** A subset of the Planner functionality shown here is currently available in the NorthStar Planner web UI.

Table 17: Controller Versus Planner Comparison

NorthStar Controller (web client)	NorthStar Planner (Java client)
Manage, monitor, and provision a live network in real-time.	Design, simulate, and analyze a network offline.
Live network topology map shows node status, link utilization, and LSP paths.	Network topology map shows simulated or imported data for nodes, links, and LSP paths.
Network information table shows live status of nodes, links, and LSPs.	Network information table shows simulated or imported data for nodes, links, and LSPs.
Discover nodes, links, and LSPs from the live network using PCEP or NETCONF.	Import or add nodes, links, and LSPs for network modeling.
Provision LSPs directly to the network.	Add and stage LSPs for provisioning to the network.

Table 17: Controller Versus Planner Comparison *(continued)*

NorthStar Controller (web client)	NorthStar Planner (Java client)
Create or schedule maintenance events to re-route LSPs around the impacted nodes and links.	Create or schedule simulation events to analyze the network model from failure scenarios.
Dashboard reports shows current status and KPIs of the live network.	Report manager provides extensive reports for simulation and planning.
Analytics collects real-time interface traffic or delay statistics and stores the data for querying and chart displays.	Import interface data or aggregate archived data to generate historical statistics for querying and chart displays.

Browser Compatibility

For accessing the NorthStar Controller web UI, we recommend Google Chrome and Mozilla Firefox browsers for Windows and Mac OS. We also recommend that you keep your browser updated to a recent version.

The NorthStar Login Window

Connect to NorthStar using a recommended browser.

Your external IP address is provided to you when you install the NorthStar application. In the address bar of your browser window, type that secure host external IP address, followed by a colon and port number 8443 (for example, **https://10.0.1.29:8443**). The NorthStar login window is displayed, as shown in Figure 31 on page 196. This same login window grants access to the NorthStar Controller (Operator) and both versions of the NorthStar Planner (Planner for web UI, Planner Desktop for desktop application). Make your selection from the Access Portal drop-down menu. For Operator and Planner, enter your username and password, and click **Sign In**.

Figure 31: NorthStar Welcome Window



If you select NorthStar Planner Desktop from the drop-down menu, the window changes as shown in Figure 32 on page 197.

Figure 32: NorthStar Planner Desktop Welcome Window



Click **Download**. Depending on the browser you are using when you initiate the download and launch the NorthStar Planner desktop application, a dialog box might be displayed, asking if you want to open or save the .jnlp file, accept downloading of the application, and agree to run the application. Once you respond to all browser requests, a dialog box is displayed in which you enter your user ID and password. Click **Login**.

You can also launch the NorthStar Planner desktop application from within the NorthStar Controller by navigating to **NorthStar Planner** from the NorthStar Controller More Options menu as shown in Figure 33 on page 197:

Figure 33: More Options Menu in the NorthStar Controller Web UI



NOTE: If you attempt to reach the login window, but instead, are routed to a message window that says, “Please enter your confirmation code to complete setup,” you must go to your license file and obtain the confirmation code as directed. Enter the confirmation code along with your administrator password to be routed to the web UI login window. The requirement to enter the confirmation code only occurs when the installation process was not completed correctly and the NorthStar application needs to confirm that you have the authorization to continue.

WARNING: To avoid a Browser Exploit Against SSL/TLS (BEAST) attack, whenever you log in to NorthStar through a browser tab or window, make sure that the tab or window was not previously used to surf a non-HTTPS website. A best practice is to close your browser and relaunch it before logging in to NorthStar.

A configurable User Inactivity Timer is available to the System Administrator (only). If set, any user who is idle and has not performed any actions (keystrokes or mouse clicks) is automatically logged out of NorthStar after the specified number of minutes. By default, the timer is disabled. To set the timer, navigate to **Administration** > **System Settings** in the NorthStar Controller web UI.

NorthStar Controller Web UI Overview

The NorthStar Controller web UI has five main views:

- Dashboard
- Topology
- Nodes
- Analytics
- Work Orders

Figure 34 on page 198 shows the buttons for selecting a view. They are located in the top menu bar.

Figure 34: Web UI View Selection Buttons



NOTE: The availability of some functions and features is dependent on user group permissions.

The Dashboard view presents a variety of status and statistics information related to the network, in the form of widgets. Figure 35 on page 199 shows a sample of the available widgets.

Figure 35: Dashboard View



The Topology view is displayed by default when you first log in to the web UI. Figure 36 on page 200 shows the Topology view.

Figure 36: Topology View



The Topology view is the main work area for the live network you load into the system. The Layout and Applications drop-down menus in the top menu bar are only available in Topology view.

The Nodes view, shown in Figure 37 on page 201, displays detailed information about the nodes in the network. With this view, you can see node details, tunnel and interface summaries, groupings, and geographic placement (if enabled), all in one place.

Figure 37: Nodes View



The Analytics view, shown in Figure 38 on page 201, provides a collection of quick-reference widgets related to analytics.

Figure 38: Analytics View



The Work Orders view, shown in Figure 39 on page 202, presents a table listing all scheduled work orders. Clicking on a line item in the table displays detailed information about the work order in a second table.

Figure 39: Work Orders View



Functions accessible from the right side of the top menu bar have to do with user and administrative management. Figure 40 on page 202 shows that portion of the top menu bar. These functions are accessible whether you are in the Dashboard, Topology, Nodes, Analytics, or Work Orders view.

Figure 40: Right Side of the Top Menu Bar



The user and administrative management functions consist of:

- User Options (user icon)
  - Account Settings
  - Log Out
- More Options (menu icon)
  - Active Users
  - Administration (the options available to any particular user depend on user group permissions)

> **NOTE:** The “Admin only” functions can only be accessed by the Admin.

    - System Health
    - Analytics
    - Authentication (Admin only)
    - Device Profile
    - Task Scheduler

- License (Admin only)
- Logs
- Subscribers (Admin only)
- System Settings (Admin only)
- Transport Controller
- Users (Admin only)

- Documentation (link to NorthStar customer documentation)
- Planner Desktop (launches the NorthStar Planner Java client UI, without closing your NorthStar Controller web UI)
- About (version and license information)

RELATED DOCUMENTATION

NorthStar Application UI Overview | 194

NorthStar Planner UI Overview

IN THIS SECTION

- Initial Window, Before a Network is Loaded | 204
- NorthStar Planner Window with a Network Loaded | 204
- Menu Options for the NorthStar Planner UI | 205
- RSVP Live Util Legend | 206
- Customizing Nodes and Links in the Map Legends | 207

The following sections describe some of the elements displayed from the NorthStar Planner main window from which all other windows are launched or opened.

Initial Window, Before a Network is Loaded

In the NorthStar Planner view main window, select **File > Open File Manager** to display the File Manager window, and select **File > Open Network Browser** to display the Network Browser window if they are not already open. Many standard functions and features do not become available until a network topology is loaded.

Figure 41 on page 204 shows the NorthStar Planner main window, with the File Manager and Network Browser open.

Figure 41: File Manager and Network Browser Windows



To load a network file, follow the instructions in *Network Browser Window* in the *NorthStar Planner User Guide*.

NorthStar Planner Window with a Network Loaded

Once you load a network topology, the main window shows the Map, Console, and Network Info panes, as shown in Figure 42 on page 205.

Figure 42: NorthStar Planner Main Window with Network Topology



NOTE: To refresh the network view, click **Update** at the top left corner of the window under the tool bar.

Menu Options for the NorthStar Planner UI

Table 18 on page 205 describes the options available from the main window.

Table 18: Menu Options for the NorthStar Planner UI

Menu Option	Description
Application	The Application menu shows a calendar view of maintenance events and provides path optimization information.
File	The File menu contains network file functions such as opening the File Manager, loading network files, and exiting the UI.
Help	The Help menu provides basic system information, including NorthStar product version, server version and IP address, operating system information, and Java virtual machine (JVM) details.

Table 18: Menu Options for the NorthStar Planner UI *(continued)*

Network	The Network menu includes network summary information (network elements, LSP placement, LSP types, hop counts, and LSP bandwidth).
Tools	The Tools menu includes general options to monitor network progress, show login/logout activities, configure the interval between keep-alive messages, and specify network map preferences. An Admin user can also connect to the NorthStar server and perform NorthStar user administration tasks.
Windows	The Windows menu provides options to display, hide, or reset the Map, Console, and Network Info windows of the NorthStar UI.

RSVP Live Util Legend

Use the drop-down menu in the left pane to configure the map view. By default, the RSVP Live Util legend is displayed. The RSVP (Live) Util view allows you to configure the link color based on utilization. The scale of colors can be configured in this section. Both the colors and the range of utilization can be changed and added. A right click on the scale provides access to the menu for configuring the scale (Edit Color, Add Divider, and so on).

Links are not always displayed as a single solid color. Some are displayed as half one color and half another color. The presence of two different colors indicates that the utilization in one direction (A->Z) is different from the utilization in the other direction (Z->A). The half of the link originating from a certain node is colored according to the link utilization in the direction from that node to the other node.

On the color bar, drag the separator between two colors up and down to move the separator and release it at the desired position. The number to the right of the separator indicates the utilization percentage corresponding to the selected position. For example, if you move the separator between the dark-blue segment and light-blue segment of the bar up to 40.0%, some formerly light-blue links might change to dark blue.

Customizing Nodes and Links in the Map Legends

From the RSVP Util drop-down menu, you can use the following four submenus (Filters, Network Elements, Utilization Legends, and Subviews).

- Select **Subviews > Types**. Select the drop-down menu a second time and notice that the Subviews submenu is now shown with the selected option button on its left, and the items underneath it are provided as a shortcut to other menu items in the same category. To view other information such as the vendor and media information, click the relevant item in the list.
- Note that each legend has its own color settings. Some legends, such as “RSVP Util”, change link colors, but leave the node colors the same as for the previous legend. Other legends change the node colors, but not the link colors. Others, such as “Types”, change both.
- Colors can be changed by clicking the button next to the type of element you want to change.
- In addition to colors, node icons and line styles (for example, solid vs. dotted) can be changed by right-clicking one of the buttons for nodes or links. For node icons, the menu is Set This Icon, and for link styles it is Set Line Style. The setting applies when the particular legend in which you set the line style is open.
- Right-click a node or link icon in the left pane. Notice that the menu item Highlight These Items can be used to highlight all nodes (or links) of a particular type.

RELATED DOCUMENTATION

NorthStar Application UI Overview | 194