

aacl-statistics-profile

Syntax	<pre>aacl-statistics-profile <i>profile-name</i> { aacl-fields { <i>field-name</i>; } file <i>filename</i>; report-interval <i>minutes</i>; record-mode (interim-active-only interim-full); }</pre>
Hierarchy Level	[edit services service-set <i>service-set-name</i>], [edit system services local-policy-decision-function statistics]
Release Information	Statement introduced in JUNOS Release 10.0. record-mode option introduced in JUNOS Release 10.2.
Description	Create an AAACL statistics profile, which configures the files to which statistics records are exported and the format that is exported.
Options	<p>file <i>filename</i>—Name of the file to receive the statistics data output. Enclose the name within quotation marks. All files are placed in the directory <code>/var/stats/aacl</code>.</p> <p>record-mode—Record mode for the reporting interval; possible values are <code>interim-active-only</code> which reports only statistics that have changed or <code>interim-full</code> which reports all available statistics.</p> <p>report-interval <i>minutes</i>—Frequency at which statistics are recorded, in minutes. Default: 15 minutes Range: 5 through 1440 minutes</p> <p>The remaining statements are explained separately.</p>
Usage Guidelines	See Configuring Statistics Profiles.
Required Privilege Level	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
Related Topics	For more information on profiles, see the <i>JUNOS Network Management Configuration Guide</i> .

Published: 2010-04-28