

clear-on-abort

Syntax clear-on-abort;

Hierarchy Level [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server reconfigure],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* reconfigure],
[edit logical-systems *logical-system-name* system services dhcp-local-server reconfigure],
[edit logical-systems *logical-system-name* system services dhcp-local-server group *group-name* reconfigure],
[edit routing-instances *routing-instance-name* system services dhcp-local-server reconfigure],
[edit routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* reconfigure],
[edit system services dhcp-local-server reconfigure],
[edit system services dhcp-local-server group *group-name* reconfigure]

Release Information Statement introduced in JUNOS Release 10.0.

Description Delete all DHCP clients or only the DHCP clients serviced by the specified group of interfaces when reconfiguration fails; that is, when the maximum number of retry attempts have been made without success. A group configuration takes precedence over a DHCP local server configuration.

Default Restores the original client configuration when reconfiguration fails.

Required Privilege Level system—To view this statement in the configuration.
system-control—To add this statement to the configuration.

Related Topics

- Configuring Extended DHCP Local Server Dynamic Client Reconfiguration
- Configuring Deletion of the Client When Dynamic Reconfiguration Fails

Published: 2010-04-15