

## mac-address (DHCP Relay Agent)

---

**Syntax** mac-address;

**Hierarchy Level** [edit forwarding-options dhcp-relay authentication username-include],  
[edit forwarding-options dhcp-relay group *group-name* authentication username-include],  
[edit logical-systems *logical-system-name* forwarding-options dhcp-relay authentication username-include],  
[edit logical-systems *logical-system-name* forwarding-options dhcp-relay group *group-name* authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options dhcp-relay authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options dhcp-relay group *group-name* authentication username-include],  
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay authentication username-include],  
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay group *group-name* authentication username-include]

**Release Information** Statement introduced in JUNOS Release 9.1.

**Description** Specify that the MAC address from the client PDU be concatenated with the username during the subscriber authentication process.

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Topics** ■ Using External AAA Authentication Services with DHCP

---

Published: 2010-04-15