

## media-policy

---

<b>Syntax</b>	<pre>media-policy {   data-inactivity-detection {     inactivity-duration <i>seconds</i>;   }   media-release;   no-anchoring;   service-class <i>service-class-name</i>; }</pre>
<b>Hierarchy Level</b>	[edit services border-signaling-gateway gateway <i>gateway-name</i> sip new-call-usage-policy <i>policy-name</i> term <i>term-name</i> then]
<b>Release Information</b>	Statement introduced in JUNOS Release 9.4. media-release statement introduced in JUNOS Release 10.1. no-anchoring statement introduced in JUNOS Release 9.5. service-class statement introduced in JUNOS Release 9.5.
<b>Description</b>	Configure the service class to be applied to traffic that matches the new call usage policy.
<b>Options</b>	<p>media-release—Disable or enable media release for the policy.</p> <p>no-anchoring—Disable or enable media anchoring for the policy.</p> <p>service-class <i>service-class-name</i>—Name of the service class to be applied to traffic that matches the new call usage policy. You must have configured the service class using the service-class statement at the [edit services border-signaling-gateway gateway <i>gateway-name</i> embedded-spdf] hierarchy level.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	■ <a href="#">Configuring a New Call Usage Policy in <i>Session Border Control Solutions Guide Using BGF and IMSG</i></a>

---

Published: 2010-04-28