

## push

---

**Syntax** push;

**Hierarchy Level** [edit interfaces *interface-name* unit *logical-unit-number* input-vlan-map],  
[edit interfaces *interface-name* unit *logical-unit-number* output-vlan-map],  
[edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number*  
input-vlan-map],  
[edit logical-systems *logical-system-name* interfaces *interface-name* unit *logical-unit-number*  
output-vlan-map]

**Release Information** Statement introduced before JUNOS Release 7.4.

**Description** For Gigabit Ethernet IQ and 10-Gigabit Ethernet IQ2 and IQ2-E interfaces and aggregated Ethernet interfaces using Gigabit Ethernet IQ interfaces, specify the VLAN rewrite operation to add a new VLAN tag to the top of the VLAN stack. An outer VLAN tag is pushed in front of the existing VLAN tag. If you include the **push** statement in the configuration, you must also include the **pop** statement at the [edit interfaces *interface-name* unit *logical-unit-number* output-vlan-map] hierarchy level.

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Topics** ■ Stacking a VLAN Tag

---

Published: 2010-04-20