

shortcuts

Syntax shortcuts;
 lsp-metric-into-summary;
}

Hierarchy Level [edit logical-systems *logical-system-name* protocols (ospf | ospf3) traffic-engineering],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* protocols
 (ospf | ospf3) traffic-engineering],
[edit protocols (ospf | ospf3) traffic-engineering],
[edit routing-instances *routing-instance-name* protocols (ospf | ospf3)traffic-engineering]

Release Information Statement introduced before JUNOS Release 7.4.
Statement introduced in JUNOS Release 9.0 for EX Series switches.
Support for OSPFv3 (**ospf3**) introduced in JUNOS Release 9.4.
Support for OSPFv3 (**ospf3**) introduced in JUNOS Release 9.4 for EX Series switches.

Description Configure OSPF to use MPLS label-switched paths (LSPs) as shortcut next hops. By default, shortcut routes calculated through OSPFv2 are installed in the **inet.3** routing table, and shortcut routes calculated through OSPFv3 are installed in the **inet6.3** routing table.

Required Privilege Level routing—To view this statement in the configuration.
routing-control—To add this statement to the configuration.

Related Topics ■ Enabling OSPF Traffic Engineering Support

Published: 2010-04-14