

tacplus-options

Syntax	<pre>tacplus-options { service-name <i>service-name</i>; (no-cmd-attribute-value exclude-cmd-attribute); }</pre>
Hierarchy Level	[edit system]
Release Information	Statement introduced before JUNOS Release 7.4. Statement introduced in JUNOS Release 9.0 for EX Series switches. <code>no-cmd-attribute-value</code> and <code>exclude-cmd-attribute</code> options introduced in JUNOS Release 9.3. <code>no-cmd-attribute-value</code> and <code>exclude-cmd-attribute</code> options introduced in JUNOS Release 9.3 for EX Series switches.
Description	Configure TACACS+ options for authentication and accounting.
Options	<p><code>service-name <i>service-name</i></code>—The name of the authentication service used when configuring multiple TACACS+ servers to use the same authentication service.</p> <p>Default: <code>junos-exec</code></p> <p><code>no-cmd-attribute-value</code>—Set the <code>cmd</code> attribute value to an empty string in the TACACS+ accounting start and stop requests to enable logging of accounting records in the correct log file on a TACACS+ server.</p> <p><code>exclude-cmd-attribute</code>—Exclude the <code>cmd</code> attribute value completely from start and stop accounting records to enable logging of accounting records in the correct log file on a TACACS+ server.</p>
Required Privilege Level	<code>system</code> —To view this statement in the configuration. <code>system-control</code> —To add this statement to the configuration.
Related Topics	<ul style="list-style-type: none">■ Configuring TACACS+ Authentication■ Configuring TACACS+ System Accounting■ JUNOS Software Authentication Order for RADIUS, TACACS+, and Password Authentication

Published: 2010-04-26