

timestamp-tolerance

Syntax timestamp-tolerance *seconds*;

Hierarchy Level [edit logical-systems *logical-system-name* services mobile-ip home-agent virtual-network home-agent-address *ip-address*],
[edit logical-systems *logical-system-name* routing-instances *routing-instances-name* services mobile-ip home-agent virtual-network home-agent-address *ip-address*],
[edit routing-instances *routing-instances-name* services mobile-ip home-agent virtual-network home-agent-address *ip-address*],
[edit services mobile-ip home-agent virtual-network home-agent-address *ip-address*]

Release Information Statement introduced in JUNOS Release 9.3.
Support at the [edit logical-systems *logical-system-name* services mobile-ip home-agent virtual-network home-agent-address *ip-address*], [edit logical-systems *logical-system-name* routing-instances *routing-instances-name* services mobile-ip home-agent virtual-network home-agent-address *ip-address*], and [edit routing-instances *routing-instances-name* services mobile-ip home-agent virtual-network home-agent-address *ip-address*] hierarchy levels added in JUNOS Release 9.5.

Description Configure the acceptable difference between a registration request timestamp and the local time of the home agent.

Options timestamp-tolerance *seconds*—Acceptable difference in time between a registration request timestamp and the local time of the home agent.

Range: 1 through 255 seconds

Default: 7 seconds

Required Privilege Level system—To view this statement in the configuration.
system-control—To add this statement to the configuration.

Related Topics

- Configuring Mobile IP
- Configuring the Mobile IP Home Agent

Published: 2010-04-15