

traceoptions

Syntax traceoptions {
 file <filename *filename*> <files *number*> <match *regex*> <size *size*> <world-readable
 | no-world-readable>;
 flag {
 bgf-core {
 common *trace-level*;
 default *trace-level*;
 firewall *trace-level*;
 gate-logic *trace-level*;
 pic-broker *trace-level*;
 policy *trace-level*;
 statistics *trace-level*;
 }
 default *trace-level*;
 h248-stack {
 control-association *trace-level*;
 default *trace-level*;
 messages;
 media-gateway *trace-level*;
 }
 sbc-utils {
 common *trace-level*;
 configuration *trace-level*;
 default *trace-level*;
 device-monitor *trace-level*;
 ipc *trace-level*;
 memory-management *trace-level*;
 messaging *trace-level*;
 user-interface *trace-level*;
 }
 }
}

Hierarchy Level [edit services pgcp]

Release Information Statement introduced in JUNOS Release 8.4.
Statement extensively revised in JUNOS Release 9.5.

Description Configure PGCP tracing operations. The messages are output to /var/log/pgcpd.

Options The statements are explained separately.

Required Privilege Level interface—To view this statement in the configuration.
interface-control—To add this statement to the configuration.

Related Topics ■ Tracing BGF Operations in *Session Border Control Solutions Guide Using BGF and IMSG*

Published: 2010-04-28