

trigger

Syntax trigger {
 radius-disconnect;
}

Hierarchy Level [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server reconfigure],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* reconfigure],
[edit logical-systems *logical-system-name* system services dhcp-local-server reconfigure],
[edit logical-systems *logical-system-name* system services dhcp-local-server group *group-name* reconfigure],
[edit routing-instances *routing-instance-name* system services dhcp-local-server reconfigure],
[edit routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* reconfigure],
[edit system services dhcp-local-server reconfigure],
[edit system services dhcp-local-server group *group-name* reconfigure]

Release Information Statement introduced in JUNOS Release 10.0.

Description Configure behavior in response to a trigger for all DHCP clients or only the DHCP clients serviced by the specified group of interfaces.

The remaining statement is explained separately.

Required Privilege Level system—To view this statement in the configuration.
system-control—To add this statement to the configuration.

- Related Topics**
- Configuring Extended DHCP Local Server Dynamic Client Reconfiguration
 - Configuring Reconfiguration of the Client on Receipt of RADIUS-Initiated Disconnect
 - radius-disconnect