

vlan-ranges

Syntax `vlan-ranges {
 access-profile profile-name;
 authentication {
 password password-string;
 username-include {
 circuit-type;
 delimiter delimiter-character;
 domain-name domain-name-string;
 interface-name;
 mac-address;
 option-82;
 radius-realm radius-realm-string;
 user-prefix user-prefix-string;
 }
 }
 dynamic-profile profile-name {
 accept (dhcp-v4 | inet);
 ranges (any | low-tag)-(any | high-tag);
 }
}`

Hierarchy Level [edit interfaces *interface-name* dynamic-profile *profile-name*]

Release Information Statement introduced in JUNOS Release 9.5.

Description Configure multiple VLANs. Each VLAN is assigned a VLAN ID number from the range.

Options any—Any valid VLAN ID number.

vlan-id-low—Specify the first VLAN ID number for the group of VLANs.

vlan-id-high—Specify the last VLAN ID number for the group of VLANs.

Range: 1 through 4094

The remaining statements are explained separately.

Required Privilege Level routing—To view this statement in the configuration.
routing-control—To add this statement to the configuration.

Related Topics

- Configuring Single-Level VLAN Ranges for Use with VLAN Dynamic Profiles
- Configuring Dynamic Mixed VLAN Ranges