

## vlan-tag (Dynamic Rewrite Rules)

---

<b>Syntax</b>	vlan-tag (outer   outer-and-inner);
<b>Hierarchy Level</b>	[edit dynamic-profiles <i>profile-name</i> class-of-service interfaces <i>interface-name</i> unit <i>logical-unit-number</i> rewrite-rules ieee-802.1]
<b>Release Information</b>	Statement introduced in JUNOS Release 10.1.
<b>Description</b>	Apply this IEEE-802.1 rewrite rule to the outer or outer and inner VLAN tags in a dynamic profile.
<b>Default</b>	If you do not include this statement, the rewrite rule applies to the outer VLAN tag only.
<b>Options</b>	outer—Apply the rewrite rule to the outer VLAN tag only. outer-and-inner—Apply the rewrite rule to both the outer and inner VLAN tags.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	<ul style="list-style-type: none"><li>■ Guidelines for Configuring Dynamic CoS for Subscriber Access</li><li>■ Applying a Rewrite Rule Definition to a Subscriber Interface in a Dynamic Profile</li><li>■ rewrite-rules</li></ul>

---

Published: 2010-04-15