

[edit accounting-options] Hierarchy Level

```
accounting-options {
  class-usage-profile profile-name {
    destination-classes {
      destination-class-name;
    }
    file filename;
    interval minutes;
    source-classes {
      source-class-name;
    }
  }
  file filename {
    archive-sites {
      site-name;
    }
    files number;
    nonpersistent;
    size bytes;
    start-time time;
    transfer-interval minutes;
  }
  filter-profile profile-name {
    counters {
      counter-name;
    }
    file filename;
    interval minutes;
  }
  interface-profile profile-name {
    fields {
      input-bytes;
      input-errors;
      input-multicast;
      input-packets;
      input-unicast;
      output-bytes;
      output-errors;
      output-multicast;
      output-packets;
      output-unicast;
      rpf-check-bytes;
      rpf-check-packets;
      rpf-check6-bytes;
      rpf-check6-packets;
      unsupported-protocol;
    }
    file filename;
    interval minutes;
  }
  mib-profile profile-name {
    file filename;
    interval seconds;
  }
}
```

```

object-names {
    mib-object-name;
}
operation (get | get-next | walk);
}
policy-decision-statistics-profile profile-name {
    application-aware-access-list-fields {
        address;
        application;
        application-group;
        input-bytes;
        input-interface;
        input-packets;
        mask;
        output-bytes;
        output-packets;
        subscriber-name;
        timestamp;
        vrf-name;
    }
    file filename;
}
routing-engine-profile profile-name {
    fields {
        field-name;
    }
    file filename;
    interval minutes;
}
}

```

Related Topics ■ Notational Conventions Used in JUNOS Configuration Hierarchies

Published: 2010-04-28