

Configuring Static Routing (J-Web Procedure)

You can use the J-Web interface to configure static routes for EX Series switches.

To configure static routes:

1. Select **Configure > Routing > Static Routing**. The Static Routing page displays details of the configured routes.



NOTE: After you make changes to the configuration in this page, you must commit the changes for them to take effect. To commit all changes to the active configuration, select **Commit Options > Commit**. See *Using the Commit Options to Commit Configuration Changes* for details about all commit options.

2. Click one:
 - **Add**—To configure a route. Enter information into the routing page as described in Table 1.
 - **Edit**—To modify an existing route. Enter information into the routing page as described in Table 1.
 - **Delete**—To delete an existing route.

Table 1: Static Routing Configuration Summary

Field	Function	Your Action
Default Route		
Default Route	Specifies the default gateway for the switch. NOTE: IPv6 is not supported on EX2200 and EX4500 switches.	To specify an IPv4 address: <ol style="list-style-type: none">1. Select IPv4.2. Type an IP address—for example, 10.10.10.10.3. Enter the subnet mask or address prefix. For example, 24 bits represents 255.255.255.0. To specify an IPv6 address: <ol style="list-style-type: none">1. Select IPv6.2. Type an IP address—for example, 2001:ab8:85a3::8a2e:370:7334.3. Enter the subnet mask or address prefix.
Static Routes		

Table 1: Static Routing Configuration Summary (continued)

Field	Function	Your Action
Nexthop	Specifies the next-hop address or addresses to be used when routing traffic to the static route.	<p>To add an address:</p> <ol style="list-style-type: none">1. Click Add.2. In the IP address dialog, enter the IP address. <p>NOTE: If a route has multiple next-hop addresses, traffic is routed across each address in round-robin fashion.</p> <ol style="list-style-type: none">3. Click OK. <p>To delete a next-hop address, select it from the list and click Delete.</p>

- Related Topics**
- [Configuring Static Routing \(CLI Procedure\)](#)
 - [Monitoring Routing Information](#)
 - [Layer 3 Protocols Supported on EX Series Switches](#)

Published: 2010-05-03